



Investigation of charges carrier density in phosphorus and boron doped $\text{SiN}_x\text{:H}$ layers for crystalline silicon solar cells

B. Paviet-Salomon ^a  , S. Gall ^a, A. Slaoui ^b

^a Commissariat à l'Énergie Atomique (CEA), Laboratoire d'Innovation pour les Technologies des Énergies Nouvelles et les nanomatériaux (LITEN), Institut National de l'Énergie Solaire (INES), 50 avenue du Lac Léman, 73377 Le Bourget du Lac, France

^b Institut de l'Électronique du Solide et des Systèmes (InESS), Unité Mixte de Recherche 7163 Centre National de la Recherche Scientifique-Université de Strasbourg (UMR 7163 CNRS-UDS), 23 rue du Loess, BP 20 CR, 67037 Strasbourg, France

Received 27 June 2012, Revised 31 October 2012, Accepted 25 November 2012, Available online 8 December 2012.

 [What do these dates mean?](#)

[Show less](#) 

 Share  Cite

<https://doi.org/10.1016/j.mseb.2012.11.009> 

[Get rights and content](#) 

Abstract

Dielectric layers are of major importance in crystalline silicon solar cells processing, especially as anti-reflection coatings and for surface passivation purposes. In this paper we investigate the fixed charge densities (Q_{fix}) and the effective lifetimes (τ_{eff}) of phosphorus

(P) and boron (B) doped silicon nitride layers deposited by plasma-enhanced chemical vapour deposition. P-doped layers exhibit a higher τ_{eff} than standard undoped layers. In contrast, B-doped layers exhibit lower τ_{eff} . A strong Q_{fix} decrease is to be seen when increasing the P content within the film. Based on numerical simulations we also demonstrate that the passivation obtained with P- and B-doped layers are limited by the interface states rather than by the fixed charges.

Highlights

► We investigate the properties of phosphorus and boron-doped silicon nitride films. ► Phosphorus-doped layers yield higher lifetimes than undoped ones. ► The fixed charges density decreases when increasing the films phosphorus content. ► Boron-doped films feature very low lifetimes. ► These doped layers are of particular interest for crystalline silicon solar cells.

Access through your organization

Check access to the full text by signing in through your organization.

Access through **your instit...**

Introduction

Dielectric layers are of major importance in crystalline silicon solar cells processing, especially as anti-reflection coatings and for surface passivation purposes. So far the *p*-type silicon-based PV industry has mainly been relying on the hydrogenated silicon nitride ($\text{SiN}_x\text{:H}$), owing to its interesting anti-reflective properties and high passivation level on n^+ surfaces [1], [2], [3].

However, $\text{SiN}_x\text{:H}$ performs rather poor in passivating p^+ surfaces. This is partly explained by the high density of positive charges contained in $\text{SiN}_x\text{:H}$ films [1], [2]. Though Chen et al. [4] reported that for lightly doped p^+ emitters, $\text{SiN}_x\text{:H}$ layers can reach the same passivation level as thermally grown SiO_2 layers, this is generally not the case [5]. Moreover, when used for *p*-type silicon solar cells rear-side passivation, $\text{SiN}_x\text{:H}$ induces parasitic shunting, hence limiting the cells efficiency [6].

For these reasons other dielectrics or dielectrics stacks have been proposed for p^+ surfaces passivation. Excellent passivation levels have for instance been obtained using aluminium

oxide [7], [8]. In the field of rear-side passivation of *p*-type silicon solar cells, and especially for PERL-like solar cells, efficiencies above 19% have been reported using Al₂O₃/SiN_{*x*}:H or SiO₂/SiN_{*x*}:H stacks [9].

In the last few years there has also been a growing interest for alternative dielectric layers, such as phosphorus (P) and boron (B) doped dielectric layers. It has indeed been found that P-doped silicon carbide alloys, such as SiC(P) [10] and SiCN(P) [11], provide excellent passivation on both *n*- and *p*-type surfaces. Surface passivation with B-doped dielectrics is still subject to discussion, though high passivation levels have been recorded with SiC(B), especially on *p*⁺ emitter [5], [12].

Another interesting feature of doped dielectrics is that they can be used as tunable dopants sources. Blanket diffusion from SiCN(P) has already been demonstrated [13], while laser doping from SiC(P), known as the “PassDop” layer, is widely used for high-efficiency *n*-type silicon solar cells processing [14].

Moreover, if the added amount of P or B is small, the optical properties of the resulting films are not changed in a large extend [15]. Doped dielectrics can hence be used as AR coatings without major modifications, especially concerning the thickness to be deposited.

Nevertheless most of the studies so far focused on doped silicon carbide compounds, and very few investigated the properties of doped SiN_{*x*}:H layers [16]. This work thus aims at studying the properties of P- or B-doped SiN_{*x*}:H layers deposited by plasma-enhanced chemical vapour deposition (PECVD). We focus on the respective influence of the field-effect and the interface states passivation through the measurements of fixed charge densities and effective lifetimes.

Section snippets

Experimental

n- and *p*-type, 1–5Ωcm, 280μm thick, float-zone (FZ) silicon substrates were used for this study. The *n*-type substrates are both sides mirror polished, while the *p*-type substrates were chemically polished using a 1:3:3 HF:HNO₃:CH₃COOH solution.

The doped SiN_{*x*}:H layers were then deposited using a Plasma-Therm Quadra D200A direct PECVD reactor. This system operates at 13.56MHz. All layers were deposited at 300°C. The precursor gases were silane (SiH₄) and ammonia (NH₃), with a ratio $R = \text{NH}_3/\text{SiH}_4 = 3 \dots$

Phosphorus-doped SiN_x:H

The variation of Q_{fix} with the PH₃ flow is plotted in Fig. 2. A positive charge of $9.3 \times 10^{12} \text{cm}^{-2}$ is obtained for the as-deposited standard SiN_x:H layer without PH₃. This value is consistent with other data on similar layers [1], [2], [26], though a little bit higher.

For as-deposited SiN(P) layers, an important decrease of Q_{fix} is to be seen when adding PH₃. Q_{fix} indeed drops from $9.3 \times 10^{12} \text{cm}^{-2}$ to $2.3 \times 10^{12} \text{cm}^{-2}$ when going from 0 sccm (standard SiN_x:H layer, no PH₃ added) to 10 sccm of PH₃. In...

Boron-doped SiN_x:H

The variation of τ_{eff} with the TMB flow for both as-deposited and fired SiN(B) layers is presented in Fig. 8. In both cases a steady decrease of τ_{eff} is to be seen when increasing the TMB flow. Lifetimes below 10 μs are measured for high TMB flows, which is very low considering that we used FZ substrates. Such low lifetimes suggest a very defective interface between the silicon substrate and the SiN(B) layers.

Fig. 9 gives the variation of Q_{fix} with the TMB flow. It is to be noticed that no...

Conclusion

In this paper we investigated the fixed charge density and the effective lifetime of phosphorus and boron-doped silicon nitride layers, deposited by plasma-enhanced chemical vapour deposition.

A strong Q_{fix} decrease with the PH₃ flow is to be seen for SiN(P) layers. The best as-deposited passivation is obtained for a PH₃ flow of 25 sccm, for which τ_{eff} equals 1.2 ms, a value three times higher than for the standard undoped nitride. Moreover this passivation is found to be stable under IR firing,...

Acknowledgements

The author acknowledges the help provided by P. Mur, R. Hida, A. Roule and L. Vandroux for the PECVD deposition of the layers. He also wishes to express his warmest thanks to R. Cabal for fruitful discussions....

References (34)

F.W. Sexton

Solar Energy Materials (1982)

A. Cuevas

Solar Energy Materials and Solar Cells (1999)

J. Maserjian *et al.*

Solid-State Electronics (1974)

S. Gall *et al.*

Energy Procedia (2012)

R. Hezel *et al.*

Journal of Applied Physics (1981)

R. Hezel *et al.*

Journal of the Electrochemical Society (1989)

F.W. Chen *et al.*

Applied Physics Letters (2006)

R. Petres *et al.*

S. Dauwe *et al.*

Progress in Photovoltaics: Research and Applications (2002)

B. Hoex *et al.*

Applied Physics Letters (2007)

P. Saint-Cast *et al.*

Applied Physics Letters (2009)

T. Dullweber *et al.*

Progress in Photovoltaics: Research and Applications (2012)

S. Janz *et al.*

Applied Physics Letters (2006)

R. Ferre *et al.*

Progress in Photovoltaics: Research and Applications (2008)

J. Seiffe *et al.*

R. Ferre *et al.*

Applied Physics Letters (2011)

D. Suwito *et al.*

IEEE Transactions on Electron Devices (2010)

There are more references available in the full text version of this article.

Cited by (10)

Blue-violet emission of silicon carbonitride thin films prepared by sputtering and annealing treatment

2021, Applied Surface Science

Citation Excerpt :

...The photoelectric property of SiCN films did also attracted substantial research interests due to the wide adjustable bandgap from 2.86 eV to 5.0 eV [4,5]. Hence, the SiCN thin film is regarded as a promising candidate for the development of solar cells, blue or violet optoelectronic devices, full-color displays, and high-density optical memories due to the adjustable bandgap and luminescent property [5–8]. SiCN films, as a ternary compound material, show a complex and uncertain microscopic structure, including various cluster forms, multiple phase structures, and bonding types....

[Show abstract](#) ✓

The influence of nitrogen on laser doping from phosphorous doped a-SiNx layers

2016, Solar Energy Materials and Solar Cells

Citation Excerpt :

...The concept of using passivation layers as dopant sources for laser doping was since investigated by various groups. Laser doping from SiNx:P and SiNx:B was demonstrated by Paviet-Salomon *et al.* as well as Hameiri *et al.* for the application as emitter passivation/selective emitters formation or rear side passivation/LBSF formation [14,22,23]. Steinhauser *et al.* presented a similar approach called fPassDop based on SiNx:P for the application as a rear side passivation of n-type silicon solar cells [24]....

[Show abstract](#) ✓

Light-induced enhancement of the minority carrier lifetime in boron-doped Czochralski silicon passivated by doped silicon nitride

2015, Applied Surface Science

Citation Excerpt :

...This implied that the dopant, phosphorus, in P-doped SiNx, got into the silicon substrate after deposition, resulting in the change of the conduction type of the Si substrate. A similar phenomenon was reported by Paviet-Salomo et al. that phosphorus was doped into Si substrate after the deposition of P-doped SiNx [23]. In order to prove that P ions have been doped into the silicon, the doping concentration measurement was conducted on the post-deposited Si wafer by an Electrochemical Capacitance Voltage (ECV) tester (CVP21, Germany Buchanan), and the elemental analysis on the Si surface was carried out by Secondary Ion Mass Spectrometry (TOF-SIMS, 2100 Trift II)....

[Show abstract](#) ✓

Firing-stable PassDop passivation for screen printed n-type PERL solar cells based on a-SiNx:P

2014, Solar Energy Materials and Solar Cells

Citation Excerpt :

...While the formation of an inversion layer results in parasitic shunting on p-type silicon solar cells [6], a-SiNx is suitable for n-type rear side passivation due to the formation of an accumulation layer. Silicon nitride can be doped by both phosphorous and boron and has thus been used to form selective emitters [7–9]. Our approach combines all these techniques to provide a firing-stable PassDop (fPassDop) layer stack based on amorphous, phosphorous doped silicon nitride (a-SiNx:P)....

[Show abstract](#) ✓

Boron laser doping through high quality Al₂O₃ passivation layer for localized B-BSF PERL solar cells

2013, Energy Procedia

[Show abstract](#) ✓

PERC Solar Cells on p-Type Cz-Si Utilizing Phosphorus-Doped SiNx Layers ↗

2022, IEEE Journal of Photovoltaics



[View all citing articles on Scopus](#) ↗

[View full text](#)

Copyright © 2012 Elsevier B.V. All rights reserved.



All content on this site: Copyright © 2024 Elsevier B.V., its licensors, and contributors. All rights are reserved, including those for text and data mining, AI training, and similar technologies. For all open access content, the Creative Commons licensing terms apply.

