Attorney Docket: **5367-694P/CON2\474410**

UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 C.F.R. § 1.53(b))

Dated: February 13, 2020

Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

Sir:

Transmitted herewith for filing is the utility patent application of:

Inventor(s): Ulrich KASTNER-JUNG; Markus KLEIN; Stan MAES; Romana SIGL; Annette HAID; Stephan LINTNER; Julian HERGET; Gregor MATJAN

For: Organic-Light-Emitting Diode

Enclosed are:

- Transmittal letter
- Specification, Claims 1 to 13 & Abstract (154 pages)
- Application Data Sheet
- Copy of Executed Declaration and Power of Attorney (8 pp.) from prior application
- Sixty (60) Sheets of drawings (Figs. 1 to 65C)
- Information Disclosure Statement
- PTO Form SB/08A
- Copy of Notice of Recordation of Assignment Document from the Inventors to OSRAM OPTO SEMICONDUCTORS GMBH (the assignment of the parent application, U.S. Application Serial No. 13/139,514 filed on January 3, 2012 was recorded on November 29, 2011 at Reel/Frame 027296/0115, as indicated in the attached copies, and applies to this continuation application):
- Copy of Notice of Recordation of Assignment Document from the OSRAM OPTO SEMICONDUCTORS GMBH to OSRAM OLED GMBH was recorded on January 21, 2016 Reel/Frame 037567/0993, as indicated in the attached copies, and applies to this continuation application

"In the case of a division or continuation application, a prior assignment recorded against the original application is applied to the divisional or continuation application because the assignment recorded against the original application gives the assignee rights to the subject matter common to both applications" (see MPEP §306).

[x] To the extent not paid otherwise, the Commissioner is hereby authorized to charge payment of the following fees associated with this application or credit any overpayment to Deposit Account No. 503111.

[x] Any patent application processing fees under 37 CFR 1.17 for extension of time fees.

[x] Any filing fees under 37 CFR 1.16(h)(i) for presentation of extra claims.

[x] Priority is claimed for this invention from U.S. Application Serial No. 15/651,508 filed July 17, 2017; U.S. Application Serial No. 13/139,514 filed January 3, 2012 which claims priority under 35 U.S.C. 371 of International application No. PCT/DE2009/001741 filed on December 9, 2009, and of German application no. 10 2008 061 563.3 filed on December 11, 2008.

Respectfully submitted,
COZEN O'CONNOR

By /Edward M. Weisz/

Edward M. Weisz
Reg. No. 37,257
277 Park Avenue
New York, New York 10172
(212) 883-4900

PTO/SB/14 (08-12)
Approved for use through 01/31/2014. OMB 0651-0032
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number

Application Data Sheet 37 CFR 1.76	Attorney Docket Number 5367-694P/CON2\474410
	Application Number
Title of Invention	Organic-Light-Emitting Diode

The application data sheet is part of the provisional or nonprovisional application for which it is being submitted. The following form contains the bibliographic data arranged in a format specified by the United States Patent and Trademark Office as outlined in 37 CFR 1.76. This document may be completed electronically and submitted to the Office in electronic format using the Electronic Filing System (EFS) or the document may be printed and included in a paper filed application.

Secrecy Order 37 CFR 5.2

☐ Portions or all of the application associated with this Application Data Sheet may fall under a Secrecy Order pursuant to 37 CFR 5.2 (Paper filers only. Applications that fall under Secrecy Order may not be filed electronically.)

Inventor Information:

Inventor 1					
Legal Name					
Prefix	Given Name	Middle Name		Family Name	
	Ulrich			**KASTNER-JUNG**	
Residence Information (Select One) US Residency		X Non US Residency		Active US Military Service	
City	**Munich**	State/Province		Country of Residence	**DE**

Mailing Address of Inventor:			
Address 1	**Riβheimerstr.2**		
Address 2			
City	**Munich**	State/Province	
Postal Code	**81247**	Country	**DE**

Inventor 2				
Legal Name				
Prefix	Given Name	Middle Name	Family Name	Suffix
	Markus		**KLEIN**	
Residence Information (Select One) US Residency		X Non US Residency	Active US Military Service	
City **Tegernheim**	State/Province		Country of Residence **DE**	
Mailing Address of Inventor:				
Address 1 **Bienenweg 2b**				
Address 2				
City **Tegernheim**		State/Province		
Postal Code **93105**		Country **DE**		

Inventor 3			
Legal Name			
Prefix	Given Name	Middle Name	Family Name
	Stan		**MAES**
Residence Information (Select One) US Residency		**X** Non US Residency	Active US Military Service
City **Dilsen-Stokken**	State/Province		Country of Residence **BE**
Mailing Address of Inventor:			
Address 1 **Zonnestraat 31**			
Address 2			
City **Dilsen-Stokken**		State/Province	
Postal Code **3650**		Country **BE**	

Inventor 4				
Legal Name				
Prefix	Given Name	Middle Name	Family Name	Suffix
	Romana		**SIGL**	
Residence Information (Select One) US Residency		**X** Non US Residency	Active US Military Service	
City **Salzburg**	State/Province		Country of Residence **AT**	
Mailing Address of Inventor:				
Address 1 **Herrengasse 24/9**				
Address 2				
City **Salzburg**		State/Province		
Postal Code **5020**		Country **AT**		

Inventor 5					
Legal Name					
Prefix	Given Name	Middle Name	Family Name	Suffix	
	Annette		**HAID**		
Residence Information (Select One) US Residency		**X** Non US Residency	Active US Military Service		
City	**Salzburg**	State/Province		Country of Residence	**AT**
Mailing Address of Inventor:					
Address 1	**Grillparzer Str. 4**				
Address 2					
City	**Salzburg**	State/Province			
Postal Code	**5020**	Country	**AT**		

Inventor 6					
Legal Name					
Prefix	Given Name	Middle Name	Family Name	Suffix	
	Stephan		**LINTNER**		
Residence Information (Select One) US Residency		**X** Non US Residency	Active US Military Service		
City	**Salzburg**	State/Province		Country of Residence	**AT**
Mailing Address of Inventor:					
Address 1	**Uferstrasse 30 D**				
Address 2					
City	**Salzburg**	State/Province			
Postal Code	**5026**	Country	**AT**		

Inventor 7					
Legal Name					
Prefix	Given Name	Middle Name	Family Name	Suffix	
	Julian		**HERGET**		
Residence Information (Select One) US Residency		**X** Non US Residency	Active US Military Service		
City	**Marktschellenberg**	State/Province		Country of Residence	**DE**
Mailing Address of Inventor:					
Address 1	**Mehlweg 7**				
Address 2					
City	**Marktschellenberg**	State/Province			
Postal Code	**83487**	Country	**DE**		

Inventor 8					
Legal Name					
Prefix	Given Name	Middle Name	Family Name	Suffix	
	Gregor		**MATJAN**		
Residence Information (Select One) US Residency		**X** Non US Residency	Active US Military Service		
City	**Bergheim**	State/Province		Country of Residence	**AT**

Mailing Address of Inventor:			
Address 1	**Wickenburgalee 6**		
Address 2			
City	**Bergheim**	State/Province	
Postal Code	**5101**	Country	**AT**

Correspondence Information:

Enter either Customer Number or complete the Correspondence Information section below. For further information see 37 CFR 1.33(a).	
☐ **An Address is being provided for the correspondence Information of this application.**	
Customer Number	**27799**
Email Address	nyodocket@cozen.com

Application Information:

Title of the Invention	**Organic-Light-Emitting Diode**		
Attorney Docket Number	**5367-694PCON2\474410**	**Small Entity Status Claimed *No***	
Application Type	***Regular***		
Subject Matter	***Utility***		
Total Number of Drawing Sheets (if any)	**60**	**Suggested Figure for Publication (if any)**	

Publication Information:

☐	Request Early Publication (Fee required at time of Request 37 CFR 1.219)
☐	**Request Not to Publish.** I hereby request that the attached application not be published under 35 U.S.C. 122(b) and certify that the invention disclosed in the attached application **has not and will not** be the subject of an application filed in another country, or under a multilateral international agreement, that requires publication at eighteen months after filing.

Representative Information:

Representative information should be provided for all practitioners having a power of attorney in the application. Providing this information in the Application Data Sheet does not constitute a power of attorney in the application (see 37 CFR 1.32). Either enter Customer Number or complete the Representative Name section below. If both sections are completed the customer Number will be used for the Representative Information during processing.

Please Select One:	• Customer Number	US Patent Practitioner	Limited Recognition (37 CFR 11.9)
Customer Number	27799		

Domestic Benefit/National Stage Information:

This section allows for the applicant to either claim benefit under 35 U.S.C. 119(e), 120, 121, or 365(c) or indicate National Stage entry from a PCT application. Providing this information in the application data sheet constitutes the specific reference required by 35 U.S.C. 119(e) or 120, and 37 CFR 1.78.

Prior Application Status			
Application Number	**Continuity Type**	**Prior Application Number**	**Filing Date (YYYY-MM-DD)**
This application is a	Continuation of	15/651,508	2017-07-17
15/651,508	Continuation of	13/139,514	2012-01-03
13/139,514	371 of International	PCT/DE2009/001741	2009-12-09

Foreign Priority Information:

This section allows for the applicant to claim benefit of foreign priority and to identify any prior foreign application for which priority is not claimed. Providing this information in the application data sheet constitutes the claim for priority as required by 35 U.S.C. 119(b)

Application Number	Country	Filing Date (YYYY-MM-DD)	Priority Claimed
10 2008 061 563.3	**DE**	**2008-12-11**	[X] YES
			[] YES
			[] YES
			[] YES
			[] YES

Statement under 37 CFR 1.55 or 1.78 for AIA (First Inventor to File) Transition

[]	This application (1) claims priority to or the benefit of an application filed before March 16, 2013 and (2) also contains, or contained at any time, a claim to a claimed invention that has an effective filing date on or after March 16, 2013. NOTE: By providing this statement under 37 CFR 1.55 or 1.78, this application, with a filing date on or after March 16, 2013, will be examined under the first inventor to file provisions of the AIA.

Authorization to Permit Access:

[] Authorization to Permit Access to the Instant Application by the Participating Offices

If checked, the undersigned hereby grants the USPTO authority to provide the European Patent Office (EPO), the Japan Patent Office (JPO), the Korean Intellectual Property Office (KIPO), the World Intellectual Property Office (WIPO), and any other intellectual property offices in which a foreign application claiming priority to the instant patent application is filed access to the instant patent application. See 37 CFR 1.14(c) and (h). This box should not be checked if the applicant does not wish the EPO, JPO, KIPO, WIPO, or other intellectual property office in which a foreign application claiming priority to the instant patent application is filed to have access to the instant patent application.

In accordance with 37 CFR 1.1 4(h)(3), access will be provided to a copy of the instant patent application with respect to: 1) the instant patent application-as-filed; 2) any foreign application to which the instant patent application claims priority under 35 U.S.C. 1 19(a)-(d) if a copy of the foreign application that satisfies the certified copy requirement of 37 CFR 1.55 has been filed in the instant patent application; and 3) any U.S. application-as-filed from which benefit is sought in the instant patent application.

In accordance with 37 CFR 1.14(c), access may be provided to information concerning the date of filing this Authorization.

Applicant Information:

Providing assignment information in this section does not substitute for compliance with any requirement of part 3 of Title 37 of CFR to have an assignment recorded by the Office.

Applicant 1

If the applicant is the inventor (or the remaining joint inventor or inventors under 37 CFR 1.45), this section should not be completed.

The information to be provided in this section is the name and address of the legal representative who is the applicant under 37 CFR 1.43; or the name and address of the assignee, person to whom the inventor is under an obligation to assign the invention, or person who otherwise shows sufficient proprietary interest in the matter who is the applicant under 37 CFR 1.46. If the applicant is an applicant under 37 CFR 1.46 (assignee, person to whom the inventor is obligated to assign, or person who otherwise shows sufficient proprietary interest) together with one or more joint inventors, then the joint inventor or inventors who are also the applicant should be identified in this section.

[x] Assignee	[ ] Legal Representative under 35 U.S.C. 117
[ ] Person to whom the inventor is obligated to assign.	[ ] Person who shows sufficient proprietary interest

If applicant is the legal representative, indicate the authority to file the patent application, the inventor is:

Name of the Deceased or Legally Incapacitated Inventor :	

If the Assignee is an Organization check here. [x]

Organization Name	**OSRAM OLED GmbH**

Mailing Address Information:

Address 1	**Wernerwerkstrasse 2**		
Address 2			
City	**Regensburg**	**State/Province**	
Country i	**DE**	Postal Code	**93049**
Phone Number		Fax Number	
Email Address			

Signature:

NOTE: This form must be signed in accordance with 37 CFR 1.33. See 37 CFR 1.4 for signature requirements and certifications					
Signature	/Edward M. Weisz/			Date (YYYY-MM-DD)	2020-02-13
First Name	Edward	Last Name	Weisz	Registration Number	37,257

This collection of information is required by 37 CFR 1.76. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 23 minutes to complete, including gathering, preparing, and submitting the completed application data sheet form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.**

PTO/AIA/01 (06-12)
Approved for use through 01/31/2014. OMB 0651-0032
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

DECLARATION (37 CFR 1.63) FOR UTILITY OR DESIGN APPLICATION USING AN APPLICATION DATA SHEET (37 CFR 1.76)

Title of Invention	Organic-Light-Emitting Diode

As the below named inventor, I hereby declare that:

This declaration is directed to:

☐ The attached application, or

☒ United States application or PCT international application number 15/651,508

filed on July 17, 2017.

The above-identified application was made or authorized to be made by me.

I believe that I am the original inventor or an original joint inventor of a claimed invention in the application.

I hereby acknowledge that any willful false statement made in this declaration is punishable under 18 U.S.C. 1001 by fine or imprisonment of not more than five (5) years, or both.

WARNING:

Petitioner/applicant is cautioned to avoid submitting personal information in documents filed in a patent application that may contribute to identity theft. Personal information such as social security numbers, bank account numbers, or credit card numbers (other than a check or credit card authorization form PTO-2038 submitted for payment purposes) is never required by the USPTO to support a petition or an application. If this type of personal information is included in documents submitted to the USPTO, petitioners/applicants should consider redacting such personal information from the documents before submitting them to the USPTO. Petitioner/applicant is advised that the record of a patent application is available to the public after publication of the application (unless a non-publication request in compliance with 37 CFR 1.213(a) is made in the application) or issuance of a patent. Furthermore, the record from an abandoned application may also be available to the public if the application is referenced in a published application or an issued patent (see 37 CFR 1.14). Checks and credit card authorization forms PTO-2038 submitted for payment purposes are not retained in the application file and therefore are not publicly available.

LEGAL NAME OF INVENTOR

Inventor: Ulrich KASTNER-JUNG Date (Optional): 22/10/2017

Signature:

Note: An application data sheet (PTO/SB/14 or equivalent), including naming the entire inventive entity, must accompany this form or must have been previously filed. Use an additional PTO/AIA/01 form for each additional inventor.

This collection of information is required by 35 U.S.C. 115 and 37 CFR 1.63. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.11 and 1.14. This collection is estimated to take 1 minute to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.**

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

PTO/AIA/01 (06-12)
Approved for use through 01/31/2014. OMB 0651-0032
U.S. Patent and Trademark Office, U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

DECLARATION (37 CFR 1.63) FOR UTILITY OR DESIGN APPLICATION USING AN APPLICATION DATA SHEET (37 CFR 1.76)

Title of Invention	Organic-Light-Emitting Diode

As the below named inventor, I hereby declare that:

This declaration is directed to:

- ☐ The attached application, or
- ▩ United States application or PCT international application number 15/651,508 filed on July 17, 2017

The above-identified application was made or authorized to be made by me.

I believe that I am the original inventor or an original joint inventor of a claimed invention in the application.

I hereby acknowledge that any willful false statement made in this declaration is punishable under 18 U.S.C. 1001 by fine or imprisonment of not more than five (5) years, or both.

WARNING:

Petitioner/applicant is cautioned to avoid submitting personal information in documents filed in a patent application that may contribute to identity theft. Personal information such as social security numbers, bank account numbers, or credit card numbers (other than a check or credit card authorization form PTO-2038 submitted for payment purposes) is never required by the USPTO to support a petition or an application. If this type of personal information is included in documents submitted to the USPTO, petitioners/applicants should consider redacting such personal information from the documents before submitting them to the USPTO. Petitioner/applicant is advised that the record of a patent application is available to the public after publication of the application (unless a non-publication request in compliance with 37 CFR 1.213(a) is made in the application) or issuance of a patent. Furthermore, the record from an abandoned application may also be available to the public if the application is referenced in a published application or an issued patent (see 37 CFR 1.14). Checks and credit card authorization forms PTO-2038 submitted for payment purposes are not retained in the application file and therefore are not publicly available.

LEGAL NAME OF INVENTOR

Inventor: Markus KLEIN Date (Optional): _____

Signature: _____

Note: An application data sheet (PTO/SB/14 or equivalent), including naming the entire inventive entity, must accompany this form or must have been previously filed. Use an additional PTO/AIA/01 form for each additional inventor.

This collection of information is required by 35 U.S.C. 115 and 37 CFR 1.63. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.11 and 1.14. This collection is estimated to take 1 minute to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.**

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

PTO/AIA/01 (06-12)
Approved for use through 01/31/2014. OMB 0651-0032
U.S. Patent and Trademark Office, U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

DECLARATION (37 CFR 1.63) FOR UTILITY OR DESIGN APPLICATION USING AN APPLICATION DATA SHEET (37 CFR 1.76)

Title of Invention	Organic-Light-Emitting Diode

As the below named inventor, I hereby declare that:

This declaration is directed to:
- ☐ The attached application, or
- ☒ United States application or PCT international application number 15/651,508 filed on July 17, 2017

The above-identified application was made or authorized to be made by me.

I believe that I am the original inventor or an original joint inventor of a claimed invention in the application.

I hereby acknowledge that any willful false statement made in this declaration is punishable under 18 U.S.C. 1001 by fine or imprisonment of not more than five (5) years, or both.

WARNING:

Petitioner/applicant is cautioned to avoid submitting personal information in documents filed in a patent application that may contribute to identity theft. Personal information such as social security numbers, bank account numbers, or credit card numbers (other than a check or credit card authorization form PTO-2038 submitted for payment purposes) is never required by the USPTO to support a petition or an application. If this type of personal information is included in documents submitted to the USPTO, petitioners/applicants should consider redacting such personal information from the documents before submitting them to the USPTO. Petitioner/applicant is advised that the record of a patent application is available to the public after publication of the application (unless a non-publication request in compliance with 37 CFR 1.213(a) is made in the application) or issuance of a patent. Furthermore, the record from an abandoned application may also be available to the public if the application is referenced in a published application or an issued patent (see 37 CFR 1.14). Checks and credit card authorization forms PTO-2038 submitted for payment purposes are not retained in the application file and therefore are not publicly available.

LEGAL NAME OF INVENTOR

Inventor: Stan MAES Date (Optional): 13/10/2017

Signature: [signature]

Note: An application data sheet (PTO/SB/14 or equivalent), including naming the entire inventive entity, must accompany this form or must have been previously filed. Use an additional PTO/AIA/01 form for each additional inventor.

This collection of information is required by 35 U.S.C. 115 and 37 CFR 1.63. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.11 and 1.14. This collection is estimated to take 1 minute to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: **Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.**
If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

PTO/AIA/01 (06-12)
Approved for use through 01/31/2014. OMB 0651-0032
U.S. Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

DECLARATION (37 CFR 1.63) FOR UTILITY OR DESIGN APPLICATION USING AN APPLICATION DATA SHEET (37 CFR 1.76)

Title of Invention	Organic-Light-Emitting Diode

As the below named inventor, I hereby declare that:

This declaration is directed to:

☐ The attached application, or

☒ United States application or PCT international application number 15/651,508

filed on July 17, 2017

The above-identified application was made or authorized to be made by me.

I believe that I am the original inventor or an original joint inventor of a claimed invention in the application.


I hereby acknowledge that any willful false statement made in this declaration is punishable under 18 U.S.C. 1001 by fine or imprisonment of not more than five (5) years, or both.

WARNING:

Petitioner/applicant is cautioned to avoid submitting personal information in documents filed in a patent application that may contribute to identity theft. Personal information such as social security numbers, bank account numbers, or credit card numbers (other than a check or credit card authorization form PTO-2038 submitted for payment purposes) is never required by the USPTO to support a petition or an application. If this type of personal information is included in documents submitted to the USPTO, petitioners/applicants should consider redacting such personal information from the documents before submitting them to the USPTO. Petitioner/applicant is advised that the record of a patent application is available to the public after publication of the application (unless a non-publication request in compliance with 37 CFR 1.213(a) is made in the application) or issuance of a patent. Furthermore, the record from an abandoned application may also be available to the public if the application is referenced in a published application or an issued patent (see 37 CFR 1.14). Checks and credit card authorization forms PTO-2038 submitted for payment purposes are not retained in the application file and therefore are not publicly available.

LEGAL NAME OF INVENTOR

Inventor: Romana SIGL Date (Optional): 18.11.2017

Signature: 

Note: An application data sheet (PTO/SB/14 or equivalent), including naming the entire inventive entity, must accompany this form or must have been previously filed. Use an additional PTO/AIA/01 form for each additional inventor.

This collection of information is required by 35 U.S.C. 115 and 37 CFR 1.63. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.11 and 1.14. This collection is estimated to take 1 minute to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.**

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

PTO/AIA/01 (06-12)
Approved for use through 01/31/2014. OMB 0651-0032
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

DECLARATION (37 CFR 1.63) FOR UTILITY OR DESIGN APPLICATION USING AN APPLICATION DATA SHEET (37 CFR 1.76)

Title of Invention	Organic-Light-Emitting Diode

As the below named inventor, I hereby declare that:

This declaration is directed to:

- ☐ The attached application, or
- ▣ United States application or PCT international application number 15/651,508 filed on July 17, 2017

The above-identified application was made or authorized to be made by me.

I believe that I am the original inventor or an original joint inventor of a claimed invention in the application.

I hereby acknowledge that any willful false statement made in this declaration is punishable under 18 U.S.C. 1001 by fine or imprisonment of not more than five (5) years, or both.

WARNING:

Petitioner/applicant is cautioned to avoid submitting personal information in documents filed in a patent application that may contribute to identify theft. Personal information such as social security numbers, bank account numbers, or credit card numbers (other than a check or credit card authorization form PTO-2038 submitted for payment purposes) is never required by the USPTO to support a petition or an application. If this type of personal information is included in documents submitted to the USPTO, petitioners/applicants should consider redacting such personal information from the documents before submitting them to the USPTO. Petitioner/applicant is advised that the record of a patent application is available to the public after publication of the application (unless a non-publication request in compliance with 37 CFR 1.213(a) is made in the application) or issuance of a patent. Furthermore, the record from an abandoned application may also be available to the public if the application is referenced in a published application or an issued patent (see 37 CFR 1.14). Checks and credit card authorization forms PTO-2038 submitted for payment purposes are not retained in the application file and therefore are not publicly available.

LEGAL NAME OF INVENTOR

Inventor: Annette HAID Date (Optional): 08.11.2017

Signature: Annette Haid

Note: An application data sheet (PTO/SB/14 or equivalent), including naming the entire inventive entity, must accompany this form or must have been previously filed. Use an additional PTO/AIA/01 form for each additional inventor.

This collection of information is required by 35 U.S.C. 115 and 37 CFR 1.63. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.11 and 1.14. This collection is estimated to take 1 minute to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.**

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

PTO/AIA/01 (06-12)
Approved for use through 01/31/2014. OMB 0651-0032
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

DECLARATION (37 CFR 1.63) FOR UTILITY OR DESIGN APPLICATION USING AN APPLICATION DATA SHEET (37 CFR 1.76)

Title of Invention	Organic-Light-Emitting Diode

As the below named inventor, I hereby declare that:

This declaration is directed to:

- ☐ The attached application, or
- ▩ United States application or PCT international application number 15/651,508 filed on July 17, 2017

The above-identified application was made or authorized to be made by me.

I believe that I am the original inventor or an original joint inventor of a claimed invention in the application.

I hereby acknowledge that any willful false statement made in this declaration is punishable under 18 U.S.C. 1001 by fine or imprisonment of not more than five (5) years, or both.

WARNING:

Petitioner/applicant is cautioned to avoid submitting personal information in documents filed in a patent application that may contribute to identity theft. Personal information such as social security numbers, bank account numbers, or credit card numbers (other than a check or credit card authorization form PTO-2038 submitted for payment purposes) is never required by the USPTO to support a petition or an application. If this type of personal information is included in documents submitted to the USPTO, petitioners/applicants should consider redacting such personal information from the documents before submitting them to the USPTO. Petitioner/applicant is advised that the record of a patent application is available to the public after publication of the application (unless a non-publication request in compliance with 37 CFR 1.213(a) is made in the application) or issuance of a patent. Furthermore, the record from an abandoned application may also be available to the public if the application is referenced in a published application or an issued patent (see 37 CFR 1.14). Checks and credit card authorization forms PTO-2038 submitted for payment purposes are not retained in the application file and therefore are not publicly available.

LEGAL NAME OF INVENTOR

Inventor: Stephan LINTER Date (Optional): 8.11.2017

Signature: Stephan Linter

Note: An application data sheet (PTO/SB/14 or equivalent), including naming the entire inventive entity, must accompany this form or must have been previously filed. Use an additional PTO/AIA/01 form for each additional inventor.

This collection of information is required by 35 U.S.C. 115 and 37 CFR 1.63. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.11 and 1.14. This collection is estimated to take 1 minute to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.**

If you need assistance in completing this form, call 1-800-PTO-9199 and select option 2.

PTO/AIA/01 (08-12)
Approved for use through 01/31/2014. OMB 0651-0032
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

DECLARATION (37 CFR 1.63) FOR UTILITY OR DESIGN APPLICATION USING AN APPLICATION DATA SHEET (37 CFR 1.76)

Title of Invention	Organic-Light-Emitting Diode

As the below named inventor, I hereby declare that:

This declaration is directed to:

- ☐ The attached application, or
- ▩ United States application or PCT international application number 15/651,508 filed on July 17, 2017

The above-identified application was made or authorized to be made by me.

I believe that I am the original inventor or an original joint inventor of a claimed invention in the application.

I hereby acknowledge that any willful false statement made in this declaration is punishable under 18 U.S.C. 1001 by fine or imprisonment of not more than five (5) years, or both.

WARNING:

Petitioner/applicant is cautioned to avoid submitting personal information in documents filed in a patent application that may contribute to identity theft. Personal information such as social security numbers, bank account numbers, or credit card numbers (other than a check or credit card authorization form PTO-2038 submitted for payment purposes) is never required by the USPTO to support a petition or an application. If this type of personal information is included in documents submitted to the USPTO, petitioners/applicants should consider redacting such personal information from the documents before submitting them to the USPTO. Petitioner/applicant is advised that the record of a patent application is available to the public after publication of the application (unless a non-publication request in compliance with 37 CFR 1.213(a) is made in the application) or issuance of a patent. Furthermore, the record from an abandoned application may also be available to the public if the application is referenced in a published application or an issued patent (see 37 CFR 1.14). Checks and credit card authorization forms PTO-2038 submitted for payment purposes are not retained in the application file and therefore are not publicly available.

LEGAL NAME OF INVENTOR

Inventor: Julian HERGET Date (Optional): 7.11.17

Signature: [signature]

Note: An application data sheet (PTO/SB/14 or equivalent), including naming the entire inventive entity, must accompany this form or must have been previously filed. Use an additional PTO/AIA/01 form for each additional inventor.

This collection of information is required by 35 U.S.C. 115 and 37 CFR 1.63. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.11 and 1.14. This collection is estimated to take 1 minute to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.**

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

PTO/AIA/01 (06-12)
Approved for use through 01/31/2014. OMB 0651-0032
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

DECLARATION (37 CFR 1.63) FOR UTILITY OR DESIGN APPLICATION USING AN APPLICATION DATA SHEET (37 CFR 1.76)

Title of Invention	Organic-Light-Emitting Diode

As the below named inventor, I hereby declare that:

This declaration is directed to:

- ☐ The attached application, or
- ☒ United States application or PCT International application number 15/651,508 filed on July 17, 2017.

The above-identified application was made or authorized to be made by me.

I believe that I am the original inventor or an original joint inventor of a claimed invention in the application.

I hereby acknowledge that any willful false statement made in this declaration is punishable under 18 U.S.C. 1001 by fine or imprisonment of not more than five (5) years, or both.

WARNING:

Petitioner/applicant is cautioned to avoid submitting personal information in documents filed in a patent application that may contribute to identity theft. Personal information such as social security numbers, bank account numbers, or credit card numbers (other than a check or credit card authorization form PTO-2038 submitted for payment purposes) is never required by the USPTO to support a petition or an application. If this type of personal information is included in documents submitted to the USPTO, petitioners/applicants should consider redacting such personal information from the documents before submitting them to the USPTO. Petitioner/applicant is advised that the record of a patent application is available to the public after publication of the application (unless a non-publication request in compliance with 37 CFR 1.213(a) is made in the application) or issuance of a patent. Furthermore, the record from an abandoned application may also be available to the public if the application is referenced in a published application or an issued patent (see 37 CFR 1.14). Checks and credit card authorization forms PTO-2038 submitted for payment purposes are not retained in the application file and therefore are not publicly available.

LEGAL NAME OF INVENTOR

Inventor: Gregor MATJAN Date (Optional): 10/27/2017

Signature: [signature]

Note: An application data sheet (PTO/SB/14 or equivalent), including naming the entire inventive entity, must accompany this form or must have been previously filed. Use an additional PTO/AIA/01 form for each additional inventor.

This collection of information is required by 35 U.S.C. 115 and 37 CFR 1.63. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.11 and 1.14. This collection is estimated to take 1 minute to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

If you need assistance in completing this form, call 1-800-PTO-9199 and select option 2.

FIG 1




FIG 2




FIG 3




FIG 4




FIG 5




FIG 6A



1
107
104
133
123
102
101
130
191
191
190
190

FIG 6B



1
107
104
133
123
102
101
130
191
191
190
190
193
193

FIG 6C



190
192
190
192
1
107
106
133
104
101
102
130
191
191
190
190

FIG 6D



193
193
190
192
190
192
1
107
106
133
104
101
102
130
191
191
190
190
193
193

FIG 7




FIG 8




FIG 9



1
130
140
133
140
131
146
145

FIG 10



1
153
153
153
107
154
157
101
133
d
151
151
152
152
130
155
108

FIG 11



1
153
153
107
154
150
101
133
151
151
152
152
130
155
108

FIG 12



1
153
153
107
154
153
150
101
133
151
152
130
155
108

FIG 13




FIG 14A




FIG 14B




FIG 15




FIG 16




FIG 17




FIG 18




FIG 19




FIG 20




FIG 21



1
190
190
175a
175b
175a
175b
131/
162
161
l
175
α
β
162/
131
133
b
101
107
z
y
x

FIG 22



a)
z
y
x
b) Typ A-1
z
l
x
z
y
c) Typ A-2
z
191
191
x
z
y
d) Typ B
z
190
x

FIG 23



1
190
180
190
180
101,107,133
β
α
175b
175a
130
z
y
x

FIG 24



190
190
180
190
190
180
180
180
1
175a
175b
α
β
130
z
y
x

FIG 25




FIG 26A




FIG 26B




FIG 27



1
192
193
192
193
193
174
131
180
160
133
186
185a
185

FIG 28



1
187
131
107
140
133
140
101
187
130

FIG 29



1
174
107a
160
161
162
107
133
101
180
182
130
181
183

FIG 30



1
174
107a
184
160
161
162
107
133
101
180
130
183
182

FIG 31A




FIG 31B




FIG 32A




FIG 32B




FIG 32C




FIG 32D




FIG 32E




FIG 32F




FIG 32G




FIG 32H




FIG 32I




FIG 33A




FIG 33B




FIG 33C




FIG 33D




FIG 34A




FIG 34B




FIG 34C




FIG 35




FIG 36




FIG 37A




FIG 37B




FIG 38




FIG 39A




FIG 39B




FIG 40A




FIG 40B




FIG 41A




FIG 41B




FIG 41C




FIG 41D




FIG 42A




FIG 42B




FIG 42C




FIG 43



FIG 44A




FIG 44B




FIG 45A




FIG 45B




FIG 45C




FIG 46A




FIG 46B




FIG 47A




FIG 47B




FIG 47C




FIG 47D




FIG 48




FIG 49A




FIG 49B




FIG 50A




FIG 50B




FIG 50C




FIG 50D




FIG 51A




FIG 51B




FIG 52A




FIG 52B




FIG 52C




FIG 53




FIG 54A




FIG 54B




FIG 54C




FIG 55A




FIG 55B




FIG 55C




FIG 55D




FIG 56A




FIG 56B




FIG 56C




FIG 57A




FIG 57B




FIG 58A




FIG 58B




FIG 59




FIG 60A




FIG 60B




FIG 60C




FIG 60D




FIG 61A




FIG 61B




FIG 61C




FIG 62




FIG 63




FIG 64A





FIG 64B







FIG 64C






FIG 65A




FIG 65B





FIG 65C



ORGANIC LIGHT-EMITTING DIODE

RELATED APPLICATIONS

[0001] This application is a continuation of U.S. Application Serial No. 15/651,508 filed July 17, 2017, which is a continuation of 13/139,514 filed January 3, 2012 now U.S. Patent No. 9,797,567 which issued on October 24, 2017 which claims the priority under 35 U.S.C. 371 of International application No. PCT/DE2009/001741 filed on December 9, 2009. Priority is also claimed of German application no. 10 2008 061 563.3 filed on December 11, 2008. The entire contents of all these applications is hereby incorporated by reference.

FIELD OF THE INVENTION

[0002] Organic light-emitting diodes and luminaires are described.

SUMMARY OF THE INVENTION

[0003] One object of the invention is to provide organic light-emitting diodes which can be used particularly diversely.

[0004] This and other objects are attained in accordance with one aspect of the present invention directed to an organic light-emitting diode comprising an organic layer sequence, a radiation exit area and an encapsulation. The organic layer sequence comprises at least one radiation-emitting region which generates electromagnetic radiation in the spectral range from infrared radiation to UV radiation during operation. The radiation exit area is structured, so that the electromagnetic radiation has a directional emission profile. The encapsulation forms a seal of the organic layer sequence against environmental influences.

[0005] The organic light-emitting diodes described below can be, for example, organic light-emitting diodes which are transparent, emit on both sides, emit white light, emit colored light, emit infrared radiation, emit light diffusely, are rigid, are flexible and/or emit directional radiation. The luminaires can be, for example,

luminaires which are used as an alarm clock, which form part of a shower cubicle, which form part of a shower head, which serve as solar protection, which serve as rain protection, which are provided for general lighting, which can be used in mobile fashion and/or which inherently combine a plurality of these functions.

[0006] Embodiments of organic light-emitting diodes described here are presented below. In this case, the embodiments of the organic light-emitting diodes can be combined among one another in any desired manner.

[0007] In accordance with at least one embodiment of an organic light-emitting diode described here, the organic light-emitting diode comprises a radiation-emitting region in which electromagnetic radiation is generated during the operation of the organic light-emitting diode.

[0008] In accordance with at least one embodiment of an organic light-emitting diode described here, the organic light-emitting diode generates electromagnetic radiation in the spectral range from infrared radiation to UV radiation during operation.

[0009] In accordance with at least one embodiment of an organic light-emitting diode described here, the organic light-emitting diode emits infrared radiation during the operation of the organic light-emitting diode.

[00010] In accordance with at least one embodiment of an organic light-emitting diode described here, the organic light-emitting diode emits colored light during the operation of the organic light-emitting diode.

[00011] In accordance with at least one embodiment of an organic light-emitting diode described here, the organic light-emitting diode emits white light during the operation of the organic light-emitting diode.

[00012] In accordance with at least one embodiment of an organic light-emitting

diode described here, the organic light-emitting diode comprises at least one first charge carrier transport layer and at least one second charge carrier transport layer. By way of example, the organic light-emitting diode comprises a hole transport layer and also an electron transport layer as charge carrier transport layers.

[00013] In accordance with at least one embodiment of an organic light-emitting diode described here, a hole transport layer of the organic light-emitting diode comprises a matrix material that is p-doped.

[00014] In accordance with at least one embodiment of an organic light-emitting diode described here, an electron transport layer of the organic light-emitting diode comprises a matrix material that is n-doped.

[00015] In accordance with at least one embodiment of an organic light-emitting diode described here, a hole transport layer of the organic light-emitting diode comprises a matrix material and also a p-type dopant which has Lewis acid character or is a Lewis acid.

[00016] In accordance with at least one embodiment of an organic light-emitting diode described here, the matrix material and the dopant of at least one charge carrier transport layer of the organic light-emitting diode are chosen in such a way that the organic light-emitting diode gives a predetermined color impression in the switched-off operating state. That is to say that, through a suitable choice of matrix material and dopant, the organic light-emitting diode appears for example transparent, bluish, reddish, greenish or in some other color in the switched-off state. Furthermore, it is possible for the organic light-emitting diode to appear white in the switched-off state. Furthermore, the organic light-emitting diode can appear in different colors when viewed from different sides.

[00017] In accordance with at least one embodiment of an organic light-emitting diode described here, the organic light-emitting diode has a hole transport layer comprising a matrix material and a dopant that form a charge transfer complex. In

this case, the charge transfer complex has a first absorption spectrum. In this case, the hole transport layer has a predetermined color impression in the switched-off operating state of the organic light-emitting diode.

[00018] In accordance with at least one embodiment of the organic light-emitting diode, the organic light-emitting diode comprises at least one first electrode and at least one second electrode.

[00019] In accordance with at least one embodiment of the organic light-emitting diode, the organic light-emitting diode comprises at least one transparent electrode.

[00020] In accordance with at least one embodiment of an organic light-emitting diode described here, the transparent electrode is formed with a transparent conductive oxide (TCO).

[00021] In accordance with at least one embodiment of an organic light-emitting diode described here, the transparent electrode is formed with a thin, transparent metal layer.

[00022] In accordance with at least one embodiment of an organic light-emitting diode described here, the transparent electrode is formed with a transparent conductive oxide (TCO) and a thin, transparent metal layer.

[00023] In accordance with at least one embodiment of an organic light-emitting diode described here, the transparent electrode is formed with a thin, transparent metal layer having a thickness of at least 1 nm and at most 50 nm.

[00024] In accordance with at least one embodiment of an organic light-emitting diode described here, at least one electrode of the organic light-emitting diode is configured in reflective fashion.

[00025] In accordance with at least one embodiment of an organic light-emitting

diode described here, the reflectivity of at least one electrode of the organic light-emitting diode is at least 80%, particularly preferably at least 90%. The reflectivity has these high values preferably at least for electromagnetic radiation generated in the organic light-emitting diode during operation.

[00026] In accordance with at least one embodiment of an organic light-emitting diode described here, the organic light-emitting diode has an electrode comprising an LiF-containing layer on a side facing a radiation-emitting region of the organic light-emitting diode. Preferably, the electrode is then a cathode. By way of example, the electrode is in direct contact with the LiF-containing layer. For example, said LiF-containing layer completely covers the electrode at a main area, is in direct contact with the electrode and consists of LiF.

[00027] In accordance with at least one embodiment of an organic light-emitting diode described here, the organic light-emitting diode comprises a radiation-emitting region comprising at least one emission layer which contains an organic material. During operation of the organic light-emitting diode, electromagnetic radiation is generated in the at least one emission layer.

[00028] In accordance with at least one embodiment of an organic light-emitting diode described here, a radiation-emitting region of the organic light-emitting diode comprises at least two emission layers which emit electromagnetic radiation in different or the same wavelength ranges during operation. By way of example, it is possible for one emission layer in the radiation-emitting region to emit colored light during the operation of the organic light-emitting diode. The other emission layer can be designed to emit infrared radiation. Furthermore, it is possible for all the emission layers of the radiation-emitting region to emit colored light. In this case, different emission layers can emit light of different colors, which is mixed for an external observer to form mixed light, for example white mixed light.

[00029] In accordance with at least one embodiment of an organic light-emitting diode described here, the light-emitting diode comprises in a radiation-emitting

region at least one emission layer suitable for emitting light from the spectral range for infrared light.

[00030] In accordance with at least one embodiment of an organic light-emitting diode described here, the light-emitting diode comprises in a radiation-emitting region at least one emission layer suitable for emitting light from the spectral range for red light.

[00031] In accordance with at least one embodiment of an organic light-emitting diode described here, the light-emitting diode comprises in a radiation-emitting region at least one emission layer suitable for emitting light from the spectral range for blue light.

[00032] In accordance with at least one embodiment of an organic light-emitting diode described here, the light-emitting diode comprises in a radiation-emitting region at least one emission layer suitable for emitting light from the spectral range for green light.

[00033] In accordance with at least one embodiment of an organic light-emitting diode described here, the organic light-emitting diode comprises a first emission layer in the radiation-emitting region which emits red light, a second emission layer which emits green light, and also a third emission layer which emits blue light.

[00034] In this case, the emission layers can be arranged to form a layer stack in the radiation-emitting region of the organic light-emitting diode. The emission layer facing the anode contains, for example, a matrix material suitable for transporting holes. The emitter material is then introduced into the matrix material.

[00035] The emission layer facing a cathode of the organic light-emitting diode then preferably contains a matrix material suitable for transporting electrons, the emitter material being introduced into said matrix material.

[00036] The emission layer arranged between the other two emission layers then preferably contains both a material suitable for transporting holes and a further material suitable for transporting electrons. For this purpose, charge transporting layers respectively comprising a first and a second matrix material are preferably arranged between the emission layers. The first matrix material is then a hole transporting matrix material, and the second matrix material is an electron conducting matrix material.

[00037] In accordance with at least one embodiment of an organic light-emitting diode described here, the organic light-emitting diode comprises a radiation-emitting region having at least three emission layers which emit white mixed light during operation.

[00038] In accordance with at least one embodiment of an organic light-emitting diode described here, the organic light-emitting diode is a transparent organic light-emitting diode. In this case, all the layers of the organic light-emitting diode are embodied in radiation-transmissive fashion.

[00039] In accordance with at least one embodiment of an organic light-emitting diode described here, the organic light-emitting diode is embodied in pellucid fashion. That is to say that electromagnetic radiation that passes through the organic light-emitting diode is hardly scattered or not scattered at all therein. If an organic light-emitting diode embodied in pellucid fashion in this way is placed for example onto a sheet of paper with printed text, then the text can still be read through the organic light-emitting diode. Preferably, at most 50% of the electromagnetic radiation passing through in the wavelength range of visible light is scattered and/or absorbed upon passing through the organic light-emitting diode. Particularly preferably, at most 25% of the electromagnetic radiation passing through in the wavelength range of visible light is scattered and/or absorbed upon passing through the organic light-emitting diode.

[00040] In accordance with at least one embodiment of an organic light-emitting

diode described here, the organic light-emitting diode is embodied in radiation-transmissive fashion such that at least 50% of the radiation passing through is not absorbed in the organic light-emitting diode. Preferably, at least 75% of the radiation passing through is not absorbed in the organic light-emitting diode.

[00041] In accordance with at least one embodiment of an organic light-emitting diode described here, the organic light-emitting diode is an organic light-emitting diode which emits on both sides. That is to say that the organic light-emitting diode emits electromagnetic radiation from two radiation exit areas of the organic light-emitting diode during operation. The radiation exit areas can be arranged parallel to one another. Preferably, a radiation-emitting region of the organic light-emitting diode is situated between the two radiation exit areas. In this case, the organic light-emitting diode can be embodied as radiation-transmissive or non-radiation-transmissive. The organic light-emitting diode can furthermore be suitable for emitting electromagnetic radiation having mutually different wavelengths from both radiation passage areas. By way of example, visible light can pass through one radiation passage area, whereas infrared radiation passes through the other radiation passage area.

[00042] In accordance with at least one embodiment of an organic light-emitting diode described here, the organic light-emitting diode comprises at least one charge transporting layer which comprises a hole transporting matrix material and an electron transporting matrix material. The charge transporting layer is then suitable for transporting both holes and electrons.

[00043] In accordance with at least one embodiment of an organic light-emitting diode described here, the organic light-emitting diode comprises a radiation-transmissive electrode having a first layer composed of a first TCO material, a second layer, composed of a second TCO material, and also a third layer, which is arranged between first and second layers and is embodied as a transparent metal layer. In this case, the first and second TCO materials preferably differ from one another. The layers can directly adjoin one another. In this case, the thickness of the

metal layer is, for example, between at least 1 nm and at most 50 nm, particularly preferably between at least 20 nm and at most 40 nm. The thin metal layer can be made so thin that it is netlike. In this case, it is possible that the first TCO layer and the second TCO layer can be situated in openings of the thin metal layer in direct contact with one another. In this case, the organic light-emitting diode can have, for example, an anode and/or a cathode embodied in each case in the layer construction described. If both electrodes of the organic light-emitting diode are embodied in the manner described, then the organic light-emitting diode can be a radiation-transmissive, a transparent or a pellucid organic light-emitting diode. Furthermore, the organic light-emitting diode can then be an organic light-emitting diode which emits on both sides and which is not embodied as radiation-transmissive, but rather emits electromagnetic radiation through both electrodes.

[00044] In accordance with at least one embodiment of an organic light-emitting diode described here, the organic light-emitting diode has a different color expression in the switched-off operating state than in the switched-on operating state. By way of example, the organic light-emitting diode can appear bluish in the switched-off operating state, whereas it emits white light in the switched-on operating state. Furthermore, it is possible for the organic light-emitting diode to give a different color impression in each case from two main areas, for example from two radiation passage areas, in the switched-off state.

[00045] In accordance with at least one embodiment of an organic light-emitting diode described here, the organic light-emitting diode is a transparent organic light-emitting diode which emits on both sides and which appears colored from both emission sides in the switched-off operating state and emits white light in the switched-on state. In this case, the colored impression can be different at the two emission sides of the organic light-emitting diode. By way of example, the organic light-emitting diode can appear red from one side, whereas it appears blue from the other side.

[00046] In accordance with at least one embodiment of an organic light-emitting

diode described here, the organic light-emitting diode is encapsulated. That is to say that the organic light-emitting diode has at least one encapsulation which permits a seal of the functional layers of the organic light-emitting diode against environmental influences, such as moisture or atmospheric gases. The functional layers of the organic light-emitting diode are, for example, electrodes, charge carrier barrier layers, charge carrier transport layers and/or radiation-emitting layers such as emission layers.

[00047] In accordance with at least one embodiment of an organic light-emitting diode described here, the organic light-emitting diode comprises at least one first carrier. The first carrier can be a rigid carrier. By way of example, the first carrier is then formed from a glass, from a ceramic material or a metal. Furthermore, the first carrier can be a flexible carrier. The first carrier is then formed for example from a film or from a laminate.

[00048] In accordance with at least one embodiment of an organic light-emitting diode described here, the organic light-emitting diode comprises a second carrier alongside a first carrier. In this case, the second carrier can be formed from the same materials as the first carrier. Furthermore, it is possible for the first and second carriers to be formed from different materials. At least one of the carriers is at least partly transmissive to electromagnetic radiation generated in the radiation-emitting region of the organic light-emitting diode.

[00049] In accordance with at least one embodiment of an organic light-emitting diode described here, the first carrier and the second carrier are formed with a glass. That is to say that the first carrier and the second carrier contain a glass or consist of a glass. By way of example, both carriers then consist of the same glass.

[00050] In accordance with at least one embodiment of an organic light-emitting diode described here, the organic light-emitting diode comprises at least one carrier formed with a borosilicate glass. The organic light-emitting diode can comprise two carriers, for example, which consist of this glass.

[00051] In accordance with at least one embodiment of an organic light-emitting diode described here, the organic light-emitting diode comprises at least one carrier formed from a soda-lime glass. By way of example, the organic light-emitting diode then comprises two carriers consisting of this glass.

[00052] In accordance with at least one embodiment of an organic light-emitting diode described here, the organic light-emitting diode comprises a first carrier, which is embodied as radiation-transmissive, and a second carrier, which is embodied as non-radiation-transmissive. By way of example, the second carrier is embodied as reflective and/or absorbent for electromagnetic radiation generated in the radiation-emitting region of the organic light-emitting diode.

[00053] In accordance with at least one embodiment of an organic light-emitting diode described here, the organic light-emitting diode comprises a first carrier and also a second carrier. Functional layers of the organic light-emitting diode are arranged between first and second carriers. Furthermore, the first carrier and the second carrier are connected to one another by means of a connecting means, which laterally encloses the functional layers of the organic light-emitting diode and connects the two carriers to one another. In other words, the connecting means and the two carriers form a cavity, in which the functional layers of the organic light-emitting diode are arranged. The connecting means, the first carrier and the second carrier constitute the encapsulation or a part of the encapsulation of the organic light-emitting diode.

[00054] In accordance with at least one embodiment of an organic light-emitting diode described here, the connecting means comprises a glass solder material. By way of example, the connecting means is formed by a glass solder material. The glass solder material can directly adjoin the first and/or the second carrier at least in places.

[00055] In accordance with at least one embodiment of an organic light-emitting

diode described here, the connecting means comprises a glass frit material. By way of example, the connecting means is formed by a glass frit material. The glass frit material can directly adjoin the first and/or the second carrier at least in places.

[00056] In accordance with at least one embodiment of an organic light-emitting diode described here, the connecting means comprises an adhesive. By way of example, the connecting means is formed by an adhesive. The adhesive can directly adjoin the first and/or the second carrier at least in places.

[00057] In accordance with at least one embodiment of an organic light-emitting diode described here, both the first carrier and the second carrier are embodied as radiation-transmissive, transparent or pellucid. Such carriers are particularly well suited to the formation of radiation-transmissive, transparent or pellucid organic light-emitting diodes.

[00058] In accordance with at least one embodiment of an organic light-emitting diode described here, at least one part of the encapsulation for the functional layers of the organic light-emitting diode is formed by an insulation layer, which can contain at least one of the following electrically insulating materials: resist, epoxy resin, silicon oxide, silicon nitride. Alongside its properties for encapsulating the functional layers of an organic light-emitting diode described here, the insulation layer can also serve for electrically insulating the first electrode of the organic light-emitting diode from a second electrode of the organic light-emitting diode.

[00059] In accordance with at least one embodiment of an organic light-emitting diode described here, the organic light-emitting diode has at least one thin-film encapsulation which forms at least one part of the encapsulation of the organic light-emitting diode. The thin-film encapsulation can produce a basic impermeability with respect to environmental influences, such as moisture and atmospheric gases, for the functional layers of the organic light-emitting diode. By way of example, the thin-film encapsulation is produced by applying oxide and/or nitride layers to functional layers of the organic light-emitting diode. The application can be effected by means

of a PECVD method, for example.

[00060] In accordance with at least one embodiment of an organic light-emitting diode described here, the organic light-emitting diode comprises a diffusion barrier for the purpose of encapsulation. The diffusion barrier can be formed for example from an amorphous material, such as amorphous silicon dioxide, for example. The diffusion barrier can be applied by means of atmospheric pressure plasma, for example, to functional layers of the organic light-emitting diode and/or an insulation layer and/or a thin-film encapsulation.

[00061] In accordance with at least one embodiment of an organic light-emitting diode described here, the organic light-emitting diode has an encapsulation comprising at least one first layer embodied as thin-film encapsulation, and also a second layer embodied as diffusion barrier. Preferably, these two layers then directly adjoin one another at least in places, wherein, for example, the thin-film encapsulation is applied to functional layers of the organic light-emitting diode and the diffusion barrier is applied to the thin-film encapsulation.

[00062] In accordance with at least one embodiment of an organic light-emitting diode described here, the organic light-emitting diode comprises a diffusion barrier having a thickness of at least 50 nm and at most 1000 nm, preferably of at least 100 nm and at most 250 nm.

[00063] In accordance with at least one embodiment of an organic light-emitting diode described here, the organic light-emitting diode comprises a diffusion barrier for the purpose of encapsulation, said diffusion barrier having at least two individual layers, wherein the individual layers are deposited one above the other. Preferably, each of the individual layers has a thickness of at least 50 nm and at most 100 nm. In this case, the diffusion barrier can be constructed from individual layers consisting in each case of silicon dioxide or alternately of silicon dioxide and silicon nitride.

[00064] In accordance with at least one embodiment of an organic light-emitting

diode described here, the organic light-emitting diode has a resist layer for the purpose of encapsulation. The resist layer can be used for example as an alternative or in addition to a diffusion barrier.

[00065] In accordance with at least one embodiment of an organic light-emitting diode described here, the organic light-emitting diode has a layer stack composed of a resist layer and a thin-film encapsulation, which are used for sealing the functional layers of the organic light-emitting diode. By way of example, the resist layer is arranged directly onto the functional layers of the organic light-emitting diode. The thin-film encapsulation is then arranged directly on the resist layer. By way of example, the thin-film encapsulation then encloses the resist layer at all exposed areas of the thin-film encapsulation.

[00066] In accordance with at least one embodiment of an organic light-emitting diode described here, the encapsulation of the organic light-emitting diode comprises a pre-encapsulation layer, which can serve as a planarization layer for a thin-film encapsulation of the organic light-emitting diode. By way of example, the pre-encapsulation layer is a transparent oxide or a radiation-transmissive adhesive. The pre-encapsulation layer can then cover a thin-film encapsulation in places, for example. Preferably, the pre-encapsulation layer then covers the thin-film encapsulation at all exposed outer areas of the thin-film encapsulation.

[00067] In accordance with at least one embodiment of an organic light-emitting diode described here, the organic light-emitting diode comprises as encapsulation at least one first carrier and one second carrier which are connected to one another by means of a connecting means, which laterally encloses the functional layers of the organic light-emitting diode. At the same time, the encapsulation comprises between the two carriers at least one of the following layers or encapsulation possibilities: insulation layer, resist layer, pre-encapsulation layer, thin-film encapsulation layer, and/or diffusion barrier.

[00068] In accordance with at least one embodiment of an organic light-emitting

diode described here, the organic light-emitting diode comprises at least one encapsulation layer sequence having at least two encapsulation layers for the purpose of encapsulation. By way of example, the encapsulation layer sequence has at least one first encapsulation layer, which can be applied by means of plasma enhanced chemical vapor deposition. In this case, the first encapsulation layer can directly adjoin the functional layers of the organic light-emitting diode at least in places. Alternatively, the first encapsulation layer can be applied for example by means of deposition methods such as physical vapor deposition, sputtering or the like.

[00069] In accordance with at least one embodiment of an organic light-emitting diode described here, the first encapsulation layer of the encapsulation layer sequence has a thickness of at least 50 nm, preferably at least 100 nm, particularly preferably of at least 1 μm.

[00070] In accordance with at least one embodiment of an organic light-emitting diode described here, the encapsulation layer sequence comprises at least one second encapsulation layer which can be arranged directly on the first encapsulation layer. That is to say that the second encapsulation layer can be in direct contact with the first encapsulation layer. By way of example, the second encapsulation layer covers the entire exposed outer area of the first encapsulation layer.

[00071] In accordance with at least one embodiment of an organic light-emitting diode described here, the organic light-emitting diode comprises a second encapsulation layer deposited onto a first encapsulation layer by means of atomic layer deposition for the purpose of encapsulation.

[00072] In accordance with at least one embodiment of an organic light-emitting diode described here, the second encapsulation layer has a thickness of at least 1 nm, preferably of at least 10 nm, and at most 30 nm.

[00073] In accordance with at least one embodiment of an organic light-emitting

diode described here, the organic light-emitting diode comprises a first carrier encapsulated at least in places with the encapsulation layer sequence having a first encapsulation layer and a second encapsulation layer. The first carrier can be a flexible carrier, for example, which is formed by a plastic film or a laminate. That is to say that the encapsulation layer sequence can also be used for hermetically sealing carriers for functional layers of the organic light-emitting diode.

[00074] In accordance with at least one embodiment of an organic light-emitting diode described here, the entire organic light-emitting diode is covered with the encapsulation layer sequence all around. In this case, it is possible for the organic light-emitting diode to comprise a first carrier, a second carrier and also a connecting means, which form a first encapsulation for the functional layers of the organic light-emitting diode. The encapsulation layer sequence can then be arranged in places or completely at the exposed outer areas of first carrier, second carrier and/or connecting means. Furthermore, it is also possible for the functional layers additionally or alternatively to be sealed directly with the encapsulation layer sequence. That is to say that the functional layers of the organic light-emitting diode then directly adjoin the encapsulation layer sequence.

[00075] In accordance with at least one embodiment of an organic light-emitting diode described here, the organic light-emitting diode comprises the encapsulation layer sequence having a first encapsulation layer and a second encapsulation layer for the purpose of encapsulation, wherein the first encapsulation layer and the second encapsulation layer each comprise an inorganic material, the first encapsulation layer is arranged directly on functional layers of the organic light-emitting diode, and the second encapsulation layer is arranged directly on the first encapsulation layer.

[00076] In accordance with at least one embodiment of an organic light-emitting diode described here, the organic light-emitting diode comprises the encapsulation layer sequence having a first encapsulation layer, a second encapsulation layer and a third encapsulation layer for the purpose of encapsulation, wherein the third

encapsulation layer is arranged directly on the functional layers of the organic light-emitting diode, the first encapsulation layer is arranged directly on the third encapsulation layer, the second encapsulation layer is arranged directly on the first encapsulation layer, the first and second encapsulation layers each comprise an inorganic material, and the third encapsulation layer comprises an amorphous inorganic material. In this case, it is possible for the second and third encapsulation layers to be embodied identically.

[00077] In accordance with at least one embodiment of an organic light-emitting diode described here, the organic light-emitting diode comprises the encapsulation layer sequence having a first layer and a second layer, wherein the first encapsulation layer and the second encapsulation layer each comprise an inorganic material, the second encapsulation layer is arranged directly on the first encapsulation layer, and the encapsulation layer sequence is hermetically impermeable at a temperature of greater than or equal to 60°C and at a relative air humidity of greater than or equal to 85% for longer than 500 hours.

[00078] In accordance with at least one embodiment of an organic light-emitting diode described here, the first encapsulation layer and the second encapsulation layer of the encapsulation layer sequence for encapsulating the organic light-emitting diode each have a volume structure, wherein the volume structure of the second encapsulation layer is independent of the volume structure of the first encapsulation layer. In this case, the volume structure of the second encapsulation layer preferably has a higher amorphicity than the volume structure of the first encapsulation layer. Particularly preferably, the second encapsulation layer is amorphous.

[00079] In accordance with at least one embodiment of an organic light-emitting diode described here, the second encapsulation layer of the encapsulation layer sequence comprising first encapsulation layer and second encapsulation layer has a thickness having a thickness variation which is independent of a surface structure and/or a volume structure of the first encapsulation layer sequence. In this case, the thickness variation is preferably less than or equal to 10%.

[00080] In accordance with at least one embodiment of an organic light-emitting diode described here, the organic light-emitting diode comprises an encapsulation layer sequence having a plurality of first encapsulation layers and a plurality of second encapsulation layers for the purpose of encapsulation, wherein the first and the second encapsulation layers are applied alternately one directly above another.

[00081] In accordance with at least one embodiment of an organic light-emitting diode described here, the encapsulation layer sequence completely encloses the functional layers of the organic light-emitting diode. In this case, the encapsulation layer sequence can also completely enclose a first and/or a second carrier.

[00082] In accordance with at least one embodiment of an organic light-emitting diode described here, the organic light-emitting diode has a first carrier and a second carrier, and also the encapsulation layer sequence arranged between first and second carriers, for the purpose of encapsulation.

[00083] In accordance with at least one embodiment of an organic light-emitting diode described here, the organic light-emitting diode has a first carrier and a second carrier and also a connecting means, which connects first and second carriers to one another, for the purpose of encapsulation. Furthermore, the organic light-emitting diode has the encapsulation layer sequence having at least two encapsulation layers, which covers and thus encapsulates an interface between the connecting means and the first carrier and/or the second carrier.

[00084] In accordance with at least one embodiment of an organic light-emitting diode described here, the organic light-emitting diode has a protective layer arranged between an organic layer sequence of the organic light-emitting diode and an electrode of the organic light-emitting diode. By way of example, said protective layer is a sputtering protective layer that protects the organic layer sequence against damage during the sputtering of electrode material onto the organic layer sequence.

[00085] In accordance with at least one embodiment of an organic light-emitting diode described here, the sputtering protective layer contains or consists of a transition metal oxide. In this case, the sputtering protective layer can be in direct contact with an electrode of the organic light-emitting diode and/or an organic layer of the organic light-emitting diode.

[00086] In accordance with at least one embodiment of an organic light-emitting diode described here, the light emitted through at least one radiation exit area of the organic light-emitting diode does not have a Lambertian emission characteristic. By way of example, this electromagnetic radiation then has a directional emission profile. That is to say that in this case the emission of electromagnetic radiation is not symmetrical, rather an intensified emission in the direction of a main emission direction takes place.

[00087] In accordance with at least one embodiment of an organic light-emitting diode described here, the organic light-emitting diode comprises a structured radiation exit area. By way of example, the radiation exit area of the organic light-emitting diode is structured into a multiplicity of prisms arranged parallel to one another. The radiation exit area can then have first areas and second areas, for example, wherein the first areas are inclined by a first angle relative to a plane running for example parallel to a main extension plane of the organic layer sequence of the organic light-emitting diode. The second areas are then inclined by second angles relative to said plane.

[00088] By way of example, a carrier of the organic light-emitting diode is correspondingly structured in order to form the structured radiation exit area. Furthermore, it is possible for the encapsulation layer sequence, for example the second encapsulation layer to be correspondingly structured. Furthermore, it is also possible for a correspondingly structured layer to be applied for example on a carrier for the organic light-emitting diode or some other encapsulation for the organic light-emitting diode. That is to say that the structured radiation exit area can be formed by the structuring of an element of the encapsulation of the organic light-emitting diode.

However, it is also possible for the structured radiation exit area, for example in the form of a further layer, to be applied as an independent element onto the encapsulation of the organic light-emitting diode.

[00089] In accordance with at least one embodiment of an organic light-emitting diode described here, the radiation exit area of the organic light-emitting diode is structured into a multiplicity of prisms arranged parallel to one another. In this case, the prisms preferably have macroscopic orders of magnitude in one direction. In this direction, the length of the prisms can be at least 1 cm, preferably at least 1 decimeter. In a direction perpendicular thereto, the prisms can have an order of magnitude which is in the submillimeters range, such that no diffraction effects can occur at the prisms in this direction. By way of example, the length of the prisms in this direction is 500 µm or less.

[00090] In accordance with at least one embodiment of an organic light-emitting diode described here, an irradiation exit area of the organic light-emitting diode is structured into a multiplicity of first areas and second areas, wherein the first areas are embodied as radiation-transmissive and the second areas are embodied as reflective. In this way, electromagnetic radiation can leave the radiation passage area only through the first areas. As a result, a directional emission is effected through the first radiation passage area, in a manner dependent on the first angle by which the first areas are inclined.

[00091] In accordance with at least one embodiment of the organic light-emitting diode, the organic light-emitting diode is an organic light-emitting diode which emits on both sides and which has two radiation passage areas arranged at opposite sides of the organic light-emitting diode. In this embodiment, it is possible for both of the radiation exit areas to be structured in the manner described. That is to say that directional electromagnetic radiation is then emitted by the organic light-emitting diode through both radiation exit areas. Furthermore, it is also possible, however, for only one of the radiation exit areas to be structured in the manner described. Electromagnetic radiation having a Lambertian emission characteristic is then

emitted by the organic light-emitting diode from the other radiation exit area, for example.

[00092] In accordance with at least one embodiment of an organic light-emitting diode described here, for the purpose of generating directional electromagnetic radiation, a radiation exit area of the organic light-emitting diode is not structured, rather for example the top side of a carrier of the organic light-emitting diode, to which carrier the functional layers of the organic light-emitting diode are applied, is structured. By way of example, the carrier is then structured into a multiplicity of parallel prisms having first areas and second areas, which are arranged in a manner tilted with respect to one another. The functional layers can then be applied to the first and/or to the second areas at the top side of the carrier. In this case, it is possible that functional layers which are arranged on different areas can be driven separately from one another. It is thus possible to realize for example an organic light-emitting diode which alternately emits electromagnetic radiation in two different main extension directions. In a simple case, the separate drivability can be achieved by virtue of at least one electrode of the organic light-emitting diode not being arranged continuously over the entire organic layer sequence, but rather being separated into regions corresponding to the individual areas of the structured carrier. By means of the angle that the areas of the structured carrier form with one another and also the basic area of the respective areas it is possible to set a specific desired emission characteristic, that is to say a desired emission direction and emission intensity of the electromagnetic radiation generated by the organic light-emitting diode during operation.

[00093] In accordance with at least one embodiment of an organic light-emitting diode described here, the organic light-emitting diode is provided for illuminating an area to be illuminated, on which the organic light-emitting diode is fixed at least indirectly. That is to say that the organic light-emitting diode is arranged at least indirectly on an element to be illuminated having an area to be illuminated. In this case, the organic light-emitting diode can be adhesively bonded onto the element to be illuminated by means of a transparent adhesive, for example. Other fixing

methods such as hook and loop fasteners, screw connections, clamping connections, press-fit connections or the like are also possible. The organic light-emitting diode is preferably embodied as transparent or pellucid at least in places, such that, in the switched-off state, the area to be illuminated can be discerned through the organic light-emitting diode. The area to be illuminated can be, for example, the surface of a tile, of a poster, of a slab, of a traffic sign, of an information board, of a sign, of an image, of a mirror, of a glass pane, or of any other element.

[00094] In accordance with at least one embodiment of an organic light-emitting diode described here, the organic light-emitting diode is designed for illuminating an area to be illuminated, wherein the organic light-emitting diode emits during operation a first component of electromagnetic radiation, which passes toward the outside directly from the radiation-emitting region of the organic light-emitting diode without impinging beforehand on the area to be illuminated. Furthermore, the radiation has a second component, which, before emerging from the organic light-emitting diode, impinges on the area to be illuminated and has been at least partly reflected by the latter.

[00095] In accordance with at least one embodiment of an organic light-emitting diode described here, the relative ratio of the intensities of the two radiation components mentioned, that is to say of the intensities of indirectly emerging electromagnetic radiation and directly emerging electromagnetic radiation, can be set and chosen by means of an optical cavity and/or by means of first electrodes and second electrodes of the organic light-emitting diode that are set with different degrees of transparency.

[00096] In accordance with at least one embodiment of an organic light-emitting diode described here, the organic light-emitting diode is a transparent or pellucid organic light-emitting diode arranged on an area to be illuminated of an element to be illuminated, wherein the area to be illuminated is visible through the organic light-emitting diode in the switched-off state of the organic light-emitting diode. In the switched-on state, the intensity of the directly emitted electromagnetic radiation in

comparison with the indirectly emitted electromagnetic radiation can then be chosen to be so great that the area to be illuminated is no longer discernible. That is to say that the organic light-emitting diode can be switched from a transparent operating state to a luminous operating state in which an area arranged behind the organic light-emitting diode is no longer discernible. Such an intensity distribution can be achieved by means of an optical cavity, for example.

[00097] In accordance with at least one embodiment of an organic light-emitting diode described here, the organic light-emitting diode is a transparent organic light-emitting diode wherein an electrically switchable optical element is arranged at a radiation exit area. The electrically switchable optical element is, for example, an electrically switchable diffuser or an electrochromic material. Such an arrangement of organic light-emitting diode and electrically switchable element can be used for example in conjunction with an element to be illuminated, wherein the element to be illuminated can be, for example, a mirror or a transparent element such as a glass plate. By means of the electrically switchable optical element, such an arrangement can be switched for example from transparent to opalescent. In this way, a concealing screen that can be switched on and off can be realized, for example, which can also be utilized as a luminaire.

[00098] In accordance with at least one embodiment of an organic light-emitting diode described here, the electrically switchable optical element is embodied in structured fashion. That is to say that the electrically switchable optical element is applied in a specific pattern, for example, to a radiation exit area of the organic light-emitting diode. In this way, by way of example, information or a decoration can be inserted into the beam path of the organic light-emitting diode upon the electrically switchable optical element being switched on and can be masked out again upon the electrically switchable optical element being switched off.

[00099] In accordance with at least one embodiment of an organic light-emitting diode described here, the organic light-emitting diode is embodied at least as radiation-transmissive and is arranged with one of its radiation exit areas on a

reflective optical element such as a mirror or a retroreflector.

[000100] In accordance with at least one embodiment of an organic light-emitting diode described here, the organic light-emitting diode is embodied in radiation-transmissive fashion and arranged with one of its radiation exit areas on a reflective optical element such as mirror or a retroreflector. Furthermore, a color filter is arranged at the opposite radiation exit area of the organic light-emitting diode. The color filter has, for example, a high transmission for a first spectral subrange of the visible wavelength spectrum and high absorption for a second spectral subrange of the visible wavelength spectrum. An intensity maximum of the electromagnetic radiation generated by the organic light-emitting diode during operation lies within the first spectral subrange transmitted by the color filter. Advantageously, that proportion of the ambient light which is reflected back from the reflective element to the radiation exit area and is coupled out from the organic light-emitting diode in this way produces substantially the same color impression as the light emitted by the organic light-emitting diode.

[000101] In accordance with at least one embodiment, an organic light-emitting diode described here comprises a reflective layer which reflects electromagnetic radiation impinging on the light-emitting diode from outside back in the direction of the radiation exit area of the organic light-emitting diode. The organic light-emitting diode furthermore comprises, at the radiation exit area, a color filter, such that the organic light-emitting diode brings about the same color impression independently of the operating state. That is to say that the organic light-emitting diode has the same color impression in the switched-off operating state as in the switched-on operating state.

[000102] In accordance with at least one embodiment of an organic light-emitting diode described here, a touch sensor is integrated into the organic light-emitting diode. By way of example, the touch sensor is a capacitively or resistively operating touch sensor. That is to say that the organic light-emitting diode forms for example a light source and simultaneously an operating element.

[000103] Luminaires are specified below which are provided for example for general lighting or as lights in road traffic. In this case, the luminaires can comprise organic light-emitting diodes described here as light sources. The luminaires can furthermore comprise any combination of organic light-emitting diodes described as light sources. Furthermore, it is also possible to combine the luminaires described here or elements of the luminaires described here to form further luminaires.

[000104] In accordance with at least one embodiment of a luminaire described here, the luminaire comprises at least one organic light-emitting diode in accordance with at least one embodiment described here.

[000105] In accordance with at least one embodiment of a luminaire described here, the luminaire is designed for general lighting and furthermore has a wake-up function. That is to say that the luminaire can be operated in the manner of an alarm clock in one operating state of the luminaire.

[000106] In accordance with at least one embodiment of a luminaire described here, the luminaire comprises a driving device, by means of which an activation time - for example a wake-up time - can be set by the user of the luminaire. At said activation time, the luminaire then starts to emit light.

[000107] In accordance with at least one embodiment of a luminaire described here, the luminaire is designed for general lighting and as an alarm clock, wherein the luminaire comprises at least one transparent, pellucid organic light-emitting diode in accordance with at least one of the previous embodiments. The organic light-emitting diode can be arranged, for example, in front of an area to be illuminated, which is visible through the organic light-emitting diode in the switched-off operating state of the luminaire.

[000108] In accordance with at least one embodiment of the luminaire, the luminaire comprises a driving device, which, starting from a specific activation time,

increases the light intensity of the light emitted by the luminaire, for example continuously.

[000109] In accordance with at least one embodiment of a luminaire described here, the luminaire comprises a driving device, which is designed to increase, starting from an activation time, the light intensity of the light emitted by the luminaire in steps, wherein for predeterminable times, the luminaire generates light having a constant light intensity, which is increased in predeterminable time intervals.

[000110] In accordance with at least one embodiment of a luminaire described here, the luminaire is designed to generate light having a light intensity of between zero and at least 1000 cd, preferably at least 5000 cd, particularly preferably at least 10 000 cd. By way of example, for this purpose the luminaire comprises at least one organic light-emitting diode having a phosphorescent emitter material in its radiation-generating region. The organic light-emitting diode can also comprise fluorescent emitter materials in its radiation-generating region, in addition to the phosphorescent emitter material.

[000111] In accordance with at least one embodiment of a luminaire described here, the luminaire comprises at least one touch-sensitive operating element which can be operated by the user of the luminaire by means of a touch sensor. The operating element can be arranged for example in a radiation exit area of the luminaire. Particularly preferably, an organic light-emitting diode in accordance with at least one of the previous embodiments which has an integrated touch sensor is employed for forming the touch-sensitive operating element.

[000112] In accordance with at least one embodiment of the luminaire, the luminaire can be operated by means of a remote control. By way of example, the remote control can exchange information with the luminaire by means of radio or infrared radiation.

[000113] In accordance with at least one embodiment of the luminaire, the

luminaire is subdivided into a multiplicity of segments. By way of example, different segments can be suitable for generating electromagnetic radiation having different wavelengths.

[000114] In accordance with at least one embodiment of a luminaire described here, the luminaire comprises a driving device, which is designed to increase the color temperature of the light emitted by the luminaire continuously or in steps.

[000115] In accordance with at least one embodiment of the luminaire, the luminaire is designed to generate light, preferably white light having color temperatures of at least 4000 K to color temperatures of at most 25 000 K.

[000116] In accordance with at least one embodiment of a luminaire described here, the luminaire comprises a driving device, which is designed to increase the light intensity and also the color temperature of the light generated by the luminaire during operation in steps or continuously, wherein the light intensity is increased, for example, as the color temperature is increased.

[000117] In accordance with at least one embodiment of a luminaire described here, the luminaire is designed to simulate a sunrise in time-lapse fashion. That is to say that, starting from a specific start time, the luminaire generates white light, in the case of which the color temperature is increased continuously or in steps from at least 4000 K to at most 25 000 K, wherein the light intensity is simultaneously increased from 0 cd to a maximum of 10 000 cd. In this case, the rise in the color temperature can take place at the same time or independently of a rise in the light intensity.

[000118] In accordance with at least one embodiment of a luminaire described here, the luminaire serves as a splash guard alongside its use as a light for general lighting. By way of example, the luminaire forms the part of a shower cubicle. Thus, the luminaire can form the part of a wall of a shower cubicle or can be arranged on a wall of the shower cubicle. Furthermore, it is possible for the luminaire to form the

wall for the shower cubicle.

[000119] In accordance with at least one embodiment of the luminaire, the luminaire comprises at least two carriers between which at least one organic light-emitting diode or functional layers of an organic light-emitting diode are arranged. In this case, preferably at least one of the carriers is embodied such that it scatters light diffusely, with the result that the luminaire is not pellucid, but rather also serves as a concealing screen.

[000120] In accordance with at least one embodiment of the luminaire, the luminaire comprises at least one organic light-emitting diode having at least one double encapsulation. In this case, double encapsulation means that at least two of the possibilities described here for encapsulating an organic light-emitting diode are used in combination in order, in this way, to obtain a particularly well hermetically sealed organic light-emitting diode.

[000121] In accordance with at least one embodiment of the luminaire described here, the luminaire is designed to come directly into contact with water.

[000122] In accordance with at least one embodiment of a luminaire described here, the luminaire is designed to be adhesively bonded in the sense of a transfer onto the wall of a shower cubicle.

[000123] In accordance with at least one embodiment of a luminaire described here, the luminaire comprises at least one inorganic light-emitting diode as light source of the luminaire.

[000124] In accordance with at least one embodiment of a luminaire described here, the luminaire comprises at least one organic light-emitting diode as light source and also at least one inorganic light-emitting diode as light source.

[000125] In accordance with at least one embodiment of a luminaire described

here, the luminaire has at least one carrier formed with a radiation-transmissive material suitable for guiding light. By way of example, the carrier is a glass plate.

[000126] In accordance with at least one embodiment of a luminaire described here, at least one inorganic light-emitting diode is arranged at the carrier of the luminaire, said carrier being embodied as an optical waveguide, said at least one inorganic light-emitting diode coupling electromagnetic radiation into the optical waveguide. The electromagnetic radiation coupled in can, for example, be distributed in the optical waveguide and be emitted toward the outside by the latter over a large area.

[000127] In accordance with at least one embodiment of a luminaire described here, the luminaire has an operating state in which infrared radiation is generated. By way of example, the infrared radiation is used for warming a user of the luminaire, for deicing a pane or for heating a moist environment. For example, by means of the infrared radiation, the user of a shower cubicle comprising the luminaire can be warmed and/or the shower cubicle can be dried by means of the infrared radiation after the conclusion of showering. In this case, the infrared radiation can be generated by at least one inorganic or by at least one organic light-emitting diode.

[000128] In accordance with at least one embodiment of the luminaire, the luminaire is suitable for emitting ultraviolet radiation during operation. By way of example, the ultraviolet radiation is generated by at least one inorganic light-emitting diode of the luminaire. In this case, the ultraviolet radiation can be used for tanning a user of the luminaire and/or for disinfecting the environment of the luminaire. By way of example, a luminaire embodied as a splash guard in a shower or integrated in a shower head can be used in this way.

[000129] In accordance with at least one embodiment of the luminaire, the luminaire is integrated in a shower or in a bath tub. By way of example, the luminaire forms a splash guard or is part of a shower head. The luminaire can then serve as an indicating device for the water temperature. By way of example, the luminaire can

be suitable for emitting blue light, which indicates cold water. Furthermore, the luminaire can be suitable for emitting red light, which indicates hot water, and mixed colors comprising red and blue components for indicating warm water.

[000130] In accordance with at least one embodiment of a luminaire described here, the color locus, the light intensity and/or the color temperature can be adjustable by means of the mixing faucet of a water supply. For this purpose, the mixing faucet is connected to a driving device for the luminaire.

[000131] In accordance with at least one embodiment of the luminaire, the luminaire can comprise a touch-sensitive operating element, by means of which, in addition to operating states of the luminaire, it is also possible to set the water temperature and/or the water pressure for example in a shower cubicle or in a bath tub.

[000132] In accordance with at least one embodiment of a luminaire described here, the luminaire serves as a light for general lighting and forms at least the part of a spray or shower head.

[000133] In accordance with at least one embodiment of a luminaire described here, the luminaire is in direct contact with water during operation. That is to say that, for example, water washes around a carrier of the luminaire. In this case, water can wash around the luminaire while the latter is in a switched-on operating state.

[000134] In accordance with at least one embodiment of a luminaire described here, the luminaire is in direct contact with water, wherein the water serves as an optical waveguide for the electromagnetic radiation generated by the luminaire. That is to say that the light generated by the luminaire during operation is at least partly coupled into at least one water jet in which it can propagate like in an optical waveguide. In this way it is possible - for example upon illumination of a multiplicity of water jets with different colors - to give the impression of a rainbow.

[000135] In accordance with at least one embodiment of a luminaire described here, the luminaire comprises at least one organic light-emitting diode having an opening. In this case, the opening preferably extends continuously from one main side of the organic light-emitting diode to the opposite main side of the organic light-emitting diode. The opening can be closed at the edge with a connecting means such as a glass solder material or a glass frit. Furthermore, it is possible to employ even further measures for sealing the organic light-emitting diode in the region of the opening, such as an encapsulation layer sequence, a thin-film encapsulation, a diffusion barrier or the like. Preferably, water flows through the opening in at least one operating state of the organic light-emitting diode. In this case, it is also possible for the organic light-emitting diode to have a multiplicity of openings through which water can flow during the operation of the organic light-emitting diode.

[000136] In accordance with at least one embodiment of a luminaire described here, the luminaire, alongside a light for general lighting, is a mirror and also a display device for displaying simple graphical elements. In this case, the luminaire can be used for example as a bathroom mirror or wardrobe mirror. The luminaire preferably has at least three operating states: a first operating state, in which the luminaire serves for general lighting and emits light, a second operating state, in which the luminaire actively emits no electromagnetic radiation and serves as a mirror, and also a third operating state, in which the luminaire displays simple graphical elements such as patterns or the like. In the third operating state, the luminaire can additionally serve as a mirror and/or for general lighting, wherein the emitted light intensity is then preferably reduced in comparison with the first operating state.

[000137] In accordance with at least one embodiment of a luminaire described here, the luminaire comprises a structured electrically switchable element. The electrically switchable element is structured in accordance with a predetermined pattern, for example. If the electrically switchable optical element is operated in a switched-on electrical operating state, for example, the pattern to be represented is visible. The electrically switchable optical element is, for example, an electrically

switchable diffuser or an electrochromic material. By way of example, the electrically switchable optical element can be used in a luminaire serving for general lighting and as a mirror.

[000138] In accordance with at least one embodiment of a luminaire described here, the luminaire can be operated by means of gesture control. That is to say that the luminaire comprises an optical sensor, for example a camera, and also an evaluation circuit for evaluating the signals of the optical sensor. A switch-on, switch-off or other changes of operating states can then be effected by means of gesture control.

[000139] In accordance with at least one embodiment of a luminaire described here, the luminaire forms a tile or the part of a tile. Preferably, the luminaire is embodied in non-slip fashion in this case.

[000140] In accordance with at least one embodiment of a luminaire described here, the luminaire comprises two carriers between which spacers are arranged at regular distances. The spacers can be posts or dams, for example, which connect the two carriers to one another. The spacers are, for example, formed with a glass solder or a glass frit material or consist of one of these materials.

[000141] In accordance with at least one embodiment of a luminaire described here, the luminaire serves as wall or floor heating. In this case, the luminaire need not necessarily be suitable for generating visible electromagnetic radiation. It is sufficient, for example, if the luminaire comprises at least one organic light-emitting diode suitable for generating infrared radiation. Furthermore, it is possible for the luminaire to comprise organic light-emitting diodes which emit infrared radiation and also organic light-emitting diodes which emit visible light. Furthermore, it is possible for the luminaire to comprise at least one organic light-emitting diode which comprises, in its radiation-generating region, an emission layer comprising an infrared-emitting emitter material, and also at least one emission layer comprising an emitter material which emits colored light.

[000142] In accordance with at least one embodiment of the luminaire, the luminaire is embodied in flexible fashion and can be applied to a carrier in the manner of a transfer. By way of example, the carrier is an element to be illuminated. In this case, the luminaire can be embodied such that it is transparent and emits on both sides, such that the element to be illuminated by the luminaire is visible during the operation of the luminaire. By way of example, the luminaire can, in this way, be adhesively bonded onto a tile which is presented in a manner highlighted by means of the luminaire.

[000143] In accordance with at least one embodiment of a luminaire described here, the luminaire can be operated by means of induction or capacitive driving. That is to say that, in this case, the luminaire has no external connection conductors that are connected to a current source. Rather, the luminaire comprises for example an antenna suitable for picking up electromagnetic radiation, with which the luminaire is operated.

[000144] In accordance with at least one embodiment of a luminaire described here, a large-area luminaire having a multiplicity of organic light-emitting diodes is involved. In this case, the organic light-emitting diodes can be arranged for example in a combined series and parallel circuit. The large-area, segmented luminaire can form, for example, a ceiling light or solar protection.

[000145] In accordance with at least one embodiment of a luminaire described here, the luminaire comprises at least two organic light-emitting diodes which are suitable for generating light of mutually different colors.

[000146] In accordance with at least one embodiment of a luminaire described here, the luminaire comprises at least two organic light-emitting diodes which are mechanically connected to one another by means of connection conductors. Alongside a mechanical stabilization of the luminaire, the connection conductors then also serve for making electrical contact with the organic light-emitting diodes of

the luminaire.

[000147] In accordance with at least one embodiment of a luminaire described here, the luminaire is embodied in flexible fashion, such that it is bendable. In this case, it is possible for the luminaire to maintain its form after bending. That is to say that the luminaire can be brought to a desired form by the user of the luminaire by bending, for example.

[000148] In accordance with at least one embodiment of a luminaire described here, the luminaire has a luminous area comprising an area content of at least 0.1 m^2.

[000149] In accordance with at least one embodiment of a luminaire described here, the luminaire has a luminous area having an area content of at least 0.5 m^2.

[000150] In accordance with at least one embodiment of a luminaire described here, the luminaire has a luminous area having an area content of at least 1.0 m^2.

[000151] In accordance with at least one embodiment of a luminaire described here, the luminaire has a luminous area having an area content of at least 2.5 m^2.

[000152] In accordance with at least one embodiment of a luminaire described here, the luminaire has a luminous area having an area content of at least 5.0 m^2.

[000153] In accordance with at least one embodiment of a luminaire described here, the luminaire has a luminous area having an area content of at least 10.0 m^2.

[000154] In accordance with at least one embodiment of a luminaire described here, the luminaire serves for covering a device used for cooling or heating a room. By way of example, the device is a radiator, an air-conditioning system or a ventilation shaft.

[000155] In accordance with at least one embodiment of a luminaire described here, the luminaire serves as a simple temperature indicator. By way of example, the luminaire in this case comprises a temperature sensor, which detects the ambient temperature or the temperature of an object to which the luminaire is connected. In this case, the luminaire emits light having a color locus and/or a color temperature which is correlated with the measured temperature.

[000156] By way of example, the luminaire is applied as a covering directly on a radiator. In this case, the luminaire, depending on the temperature of the radiator, can emit bluish light - for a cold radiator - or reddish light - for a warm radiator.

[000157] In accordance with at least one embodiment of a luminaire described here, the luminaire has a rear wall comprising at least one cooling device. The cooling device can be, for example, cooling lamellae, cooling channels, or a water cooling system.

[000158] In accordance with at least one embodiment of a luminaire described here, the luminaire can be fixed to a further element by means of a fixing means. By way of example, the fixing means is an adhesive strip, a magnet, screws, clamps or a hook and loop fastener.

[000159] In accordance with at least one embodiment of a luminaire described here, the luminaire has a driving device, by means of which the luminaire can be operated in a flickering manner. That is to say the luminaire emits light which flickers like a candle. This can be realized, for example, by means of a temporal variation of the current intensity with which the luminaire is operated.

[000160] In accordance with at least one embodiment of a luminaire described here, the luminaire serves as a desk lamp for illuminating a work area.

[000161] In accordance with at least one embodiment of a luminaire described here, the luminaire emits electromagnetic radiation in a directional manner. For this

purpose, the luminaire can comprise, for example, an organic light-emitting diode that emits directional light. Furthermore, it is possible for the luminaire to have a structured radiation exit area that leads to a directional emission of light by means of light refraction and/or light reflection.

[000162] In accordance with at least one embodiment of a luminaire described here, the luminaire is used as a light for general lighting and as a room divider. In this case, the luminaire can be embodied as a large-area luminaire, for example, which is embodied not as transparent and not as pellucid, but rather such that it scatters light diffusely. In this way, the luminaire can also serve as a concealing screen.

[000163] In accordance with at least one embodiment of a luminaire described here, the luminaire is a luminaire which emits on both sides and which is embodied such that it scatters light diffusely. That is to say that the luminaire has at least two oppositely arranged radiation exit areas through which, for example, light can leave the luminaire. In this case, the luminaire is embodied as visually impenetrable, such that it serves as a concealing screen.

[000164] In accordance with at least one embodiment of a luminaire described here, the luminaire is embodied such that it can be rolled up and unrolled. By way of example, for this purpose, the luminaire can be subdivided into individual segments which are each formed by a single organic light-emitting diode or at least two organic light-emitting diodes which, in turn, can be embodied in rigid fashion. Furthermore, it is possible for the luminaire to be embodied as fully flexible and to be able to be unrolled and rolled up in this way. In this case, the luminaire can comprise, for example, a single organic light-emitting diode embodied in flexible fashion.

[000165] In accordance with at least one embodiment of a luminaire described here, the luminaire also serves for sound insulation alongside its property as a light for general lighting. By way of example, in this case, the luminaire comprises an insulating material suitable for acoustic insulation.

[000166] In accordance with at least one embodiment of a luminaire described here, the luminaire is embodied as a louver. The luminaire in this case comprises, for example, a multiplicity of organic light-emitting diodes which are electrically contact-connected and mechanically connected to one another by means of a holding device.

[000167] In accordance with at least one embodiment of a luminaire described here, the luminaire serves for room darkening and/or as a concealing screen. That is to say that the luminaire can have a radiation exit area facing away from a window, for example. That side of the luminaire which faces away from the radiation exit area can comprise a radiation-absorbing or radiation-reflecting area facing the window.

[000168] In accordance with at least one embodiment of a luminaire described here, at least parts of the luminaire form an enclosure having at least one side wall and, if appropriate, a top. The luminaire or at least parts of the luminaire can then form, for example, a changing cubicle, a passenger shelter, a rain shelter or the like. By way of example, all the walls and top parts of the enclosure are formed by at least one luminaire.

[000169] In accordance with at least one embodiment of a luminaire described here, the luminaire comprises a light barrier, by means of which an operating state of the luminaire can be switched. By way of example, the luminaire can be switched on or off by means of the light barrier.

[000170] In accordance with at least one embodiment of a luminaire described here, the luminaire forms a dividing wall in an open-plan office.

[000171] In accordance with at least one embodiment of a luminaire described here, the luminaire forms solar protection alongside its properties for general lighting. In this case, the luminaire can have, for example, an outer area that faces away from the radiation exit area of the luminaire and is formed in absorbent or reflective

fashion.

[000172] In accordance with at least one embodiment of a luminaire described here, the luminaire comprises at least one solar cell suitable for generating electric current upon irradiation with sunlight. By way of example, the at least one solar cell is arranged on a side of the luminaire which lies opposite the radiation exit area of the luminaire. The luminaire can furthermore comprise a rechargeable battery that can be charged with light of the solar cell. In this way, by way of example, a quantity of current generated during the day by means of the solar cell can serve for generating light in conditions of poor visibility.

[000173] In accordance with at least one embodiment of a luminaire described here, the luminaire is emergency lighting. By way of example, the emergency lighting can be operated by means of solar power generated by the luminaire.

[000174] In accordance with at least one embodiment of a luminaire described here, the luminaire forms at least part of a garment or of a bag. In this case, the luminaire can comprise at least one organic light-emitting diode with a retroreflector, such that the luminaire increases the visibility of the user of the luminaire even in the switched-off operating state.

[000175] In accordance with at least one embodiment of a luminaire described here, the luminaire is an umbrella. The umbrella can comprise an organic light-emitting diode and/or at least one inorganic light-emitting diode as light source. Furthermore, it is possible for the umbrella to comprise both inorganic and organic light-emitting diodes as light sources.

[000176] In accordance with at least one embodiment of a luminaire described here, the luminaire is integrated into the window of a motor vehicle. In this case, it is possible for only parts of the window to comprise an organic light-emitting diode. Furthermore, it is also possible, however, for the entire window of the motor vehicle to be formed by a transparent organic light-emitting diode. By way of example, all the

windows of the motor vehicle can then be formed by organic light-emitting diodes.

[000177] In accordance with at least one embodiment of a luminaire described here, the luminaire forms an indicator device or a signal light of a motor vehicle. By way of example, the luminaire is a brake light, an indicator light, a rear light or the like. In this case, the luminaire can form at least part of a window of a motor vehicle.

[000178] In accordance with at least one embodiment of a luminaire described here, the luminaire forms a warning sign or a traffic sign.

BRIEF DESCRIPTION OF THE DRAWINGS

[000179] The organic light-emitting diodes described here and also the luminaires described here will be explained in greater detail below on the basis of exemplary embodiments in relation to the associated figures.

[000180] Figure 1 shows, on the basis of a schematic band diagram, the construction of an organic light-emitting diode in accordance with one exemplary embodiment.

[000181] Figure 2 shows, on the basis of a schematic sectional illustration, the construction of an organic light-emitting diode in accordance with one exemplary embodiment.

[000182] Figure 3 shows, on the basis of a schematic sectional illustration, the construction of an organic light-emitting diode in accordance with one exemplary embodiment, wherein the organic light-emitting diode 1 emits white light during operation.

[000183] Figure 4 shows a transparent first electrode for one exemplary embodiment of an organic light-emitting diode described here.

[000184] Figure 5 shows a transparent second electrode for one exemplary embodiment of an organic light-emitting diode described here.

[000185] Figures 6A, 6B, 6C and 6D show, on the basis of schematic sectional illustrations, the construction of organic light-emitting diodes in accordance with different exemplary embodiments which give a desired colored impression in the switched-off operating state.

[000186] Figure 7 shows, on the basis of a schematic plan view, one exemplary embodiment of an organic light-emitting diode encapsulated by means of a connecting means.

[000187] Figure 8 shows, on the basis of a schematic sectional illustration, one exemplary embodiment of an organic light-emitting diode encapsulated by means of a connecting means.

[000188] Figure 9 shows, on the basis of a schematic sectional illustration, one exemplary embodiment for the encapsulation of an organic light-emitting diode.

[000189] Figures 10 to 13, 14A and 14B show, on the basis of schematic sectional illustrations, exemplary embodiments of organic light-emitting diodes which are sealed by means of resist layers, insulation layers, diffusion barriers, thin-film encapsulations and/or pre-encapsulation layers.

[000190] Figures 15 to 19 show, on the basis of schematic sectional illustrations, exemplary embodiments of organic light-emitting diodes which are sealed by means of an encapsulation layer sequence.

[000191] Figure 20 shows, on the basis of a schematic sectional illustration, one exemplary embodiment of an organic light-emitting diode with a sputtering protective layer.

[000192] Figures 21 to 25 show, on the basis of schematic illustrations, the construction of organic light-emitting diodes having a directional emission profile in accordance with different exemplary embodiments.

[000193] Figures 26A, 26B and 27 show, on the basis of schematic sectional illustrations, the construction of exemplary embodiments of organic light-emitting diodes which are used for illuminating an element to be illuminated.

[000194] Figure 28 shows, on the basis of a schematic sectional illustration, the construction of one exemplary embodiment of an organic light-emitting diode 1 with a wavelength conversion substance disposed downstream thereof.

[000195] Figures 29 and 30 show, on the basis of schematic sectional illustrations, exemplary embodiments of organic light-emitting diodes which each have a retroreflector.

[000196] Figures 31A and 31B show, on the basis of schematic sectional illustrations, one exemplary embodiment of an organic light-emitting diode described here wherein the organic light-emitting diode comprises a touch sensor.

[000197] Figures 32A to 32I show, on the basis of schematic illustrations, exemplary embodiments of a luminaire described here which has a wake-up function.

[000198] Figures 33A to 33D show, on the basis of schematic illustrations, exemplary embodiments of a luminaire described here which constitutes a splash guard.

[000199] Figures 34A, 34B, 34C and 35 show, on the basis of schematic illustrations, further exemplary embodiments of a luminaire which constitutes a splash guard.

[000200] Figures 36, 37A, 37B, 38, 39A, 39B, 40A, 40B show, on the basis of schematic illustrations, exemplary embodiments of a luminaire described here with a shower head.

[000201] Figures 41A to 41D and 42A to 42C show, on the basis of schematic illustrations, one exemplary embodiment of a luminaire described here which can be utilized as a mirror.

[000202] Figures 43 and 44A, 44B show, on the basis of schematic illustrations, one exemplary embodiment of a luminaire described here which can be utilized as a tile.

[000203] Figures 45A to 45C and 46A, 46B show, on the basis of schematic illustrations, one exemplary embodiment of a luminaire described here which forms a large-area ceiling light.

[000204] Figures 47A to 47D, 48 to 49A, 49B show, on the basis of schematic illustrations, one exemplary embodiment of a luminaire described here which serves for covering an object.

[000205] Figures 50A to 50D show, on the basis of schematic illustrations, exemplary embodiments of luminaires 2 described here which can be used as large-area desk lights.

[000206] Figures 51A, 51B, 52A to 52C and 53 show, on the basis of schematic illustrations, exemplary embodiments of luminaires 2 described here which can be used as room dividers.

[000207] Figures 54A to 54C show, on the basis of schematic illustrations, exemplary embodiments of luminaires 2 described here which can be used as louvers.

[000208] Figures 55A to 55D show, on the basis of schematic illustrations, exemplary embodiments of luminaires 2 described here which can be used as changing cubicles.

[000209] Figures 56A to 56C show, on the basis of schematic illustrations, an exemplary embodiment of a luminaire described here which can be used as solar protection.

[000210] Figures 57A and 57B show, on the basis of schematic illustrations, one exemplary embodiment of a luminaire described here which forms a bag.

[000211] Figures 58A and 58B show, on the basis of schematic illustrations one exemplary embodiment of a luminaire described here which serves as an emergency light.

[000212] Figure 59 shows, on the basis of a schematic illustration, one exemplary embodiment of a luminaire described here which can be used as advertising means on vehicles.

[000213] Figures 60A to 60D show, on the basis of schematic illustrations, one exemplary embodiment of a luminaire described here which serves as an umbrella.

[000214] Figures 61A to 61C show, on the basis of schematic illustrations, exemplary embodiments of luminaires which are used as signal lamps in a motor vehicle.

[000215] Figures 62 and 63 show, on the basis of a schematic illustration, exemplary embodiments of a luminaire which is used for illumination in a motor vehicle.

[000216] Figures 64A to 64C show, on the basis of schematic illustrations, exemplary embodiments of a luminaire which is used as a warning sign.

[000217] Figures 65A to 65C show, on the basis of schematic illustrations, exemplary embodiments of a luminaire which forms rain protection.

DETAILED DESCRIPTION OF THE DRAWINGS

[000218] Elements which are identical, of identical type or act identically are provided with the same reference symbols in the figures. The figures and the size relationships of the elements illustrated in the figures among one another should not be regarded as to scale. Rather, individual elements may be illustrated with an exaggerated size in order to enable better illustration and/or in order to afford a better understanding.

[000219] Figure 1 shows, on the basis of a schematic band diagram, the construction of an organic light-emitting diode 1 in accordance with one exemplary embodiment.

[000220] The organic light-emitting diode 1 comprises a first electrode 101. The first electrode is an anode, for example. Via the first electrode 1, positive charge carriers - so-called holes - are impressed into the organic light-emitting diode.

[000221] The hole transport layer 102 adjoins the first electrode 101. The hole transport layer 102 transports the positive charge carriers toward the radiation-emitting region 104 of the organic light-emitting diode 1.

[000222] The hole transport layer 102 is succeeded by an electron barrier layer 103, which prevents the penetration of electrons from the radiation-emitting region 104 into the hole transport layer 102.

[000223] The electron barrier layer 3 is succeeded by the radiation-emitting region 104. During the operation of the organic light-emitting diode 1, electromagnetic radiation is generated in the radiation-emitting region. Therefore, the

emission 108 of electromagnetic radiation occurs in the radiation-emitting region. Preferably, electromagnetic radiation in the spectral range of infrared radiation to UV radiation is generated in this case. The radiation-emitting region is explained in greater detail for example with reference to figures 2 and 3.

[000224] The radiation-emitting region 104 is succeeded by a hole barrier layer 105, which prevents the penetration of positive charge carriers into the adjoining electron transport layer 106.

[000225] The electron transport layer 106 adjoins the hole barrier layer 105 and transports negative charge carriers - electrons - from the second electrode 107, embodied as a cathode, to the radiation-emitting region 104.

[000226] The hole transport layer 102 and the electron transport layer 106 are first and second charge carrier transport layers. The hole transport layer 102 and the electron transport layer 106 comprise, for example, a matrix material that is p- and n-doped, respectively.

[000227] Depending on the embodiment of the charge carrier transport layer as hole transport layer 102 or as electron transport layer 106, the matrix material can be selected from a group comprising phenanthroline derivatives, imidazole derivatives, triazole derivatives, oxadiazole derivatives, phenyl-containing compounds, compounds comprising condensed aromatics, carbazole-containing compounds, fluorene derivatives, spirofluorene derivatives and pyridine-containing compounds and also combinations of at least two or more of the materials mentioned.

[000228] For a charge carrier transport layer embodied as hole transport layer 102, the following matrix materials, in particular, are suitable:

[000229] N,N'-bis(naphthalen-1-yl)-N,N'-bis(phenyl)benzidine (NPB),

[000230] N,N'-bis(naphthalen-2-yl)-N,N'-bis(phenyl)benzidine (β-NPB),

[000231] N,N'-bis(3-methylphenyl)-N,N'-bis(phenyl)benzidine (TPD),

[000232] N,N'-bis(3-methylphenyl)-N,N'-bis(phenyl)-9,9-spirobifluorene (spiro-

TPD),

[000233] N,N'-bis(naphthalen-1-yl)-N,N'-bis(phenyl)-9,9-spirobifluorene (spiro-NPB),

[000234] N,N'-bis(3-methylphenyl)-N,N'-bis(phenyl)-9,9-dimethylfluorene (DMFL-TPD),

[000235] N,N'-bis(naphthalen-1-yl)-N,N'-bis(phenyl)-9,9-dimethylfluorene (DMFL-NPB),

[000236] N,N'-bis(3-methylphenyl)-N,N'-bis(phenyl)-9,9-diphenylfluorene (DPFL-TPD),

[000237] N,N'-bis(naphthalen-1-yl)-N,N'-bis(phenyl)-9,9-diphenylfluorene (DPFL-NPB),

[000238] 2,2',7,7'-tetrakis(N,N-diphenylamino)-9,9'-spirobifluorene (spiro-TAD),

[000239] 9,9-bis[4-(N,N-bisbiphenyl-4-yl-amino)phenyl]-9H-fluorene (BPAPF),

[000240] 9,9-bis[4-(N,N-bisnaphthalen-2-yl-amino)phenyl]-9H-fluorene (NPAPF),

[000241] 9,9-bis[4-(N,N-bisnaphthalen-2-yl-N,N'-bisphenylamino)phenyl]-9H-fluorene (NPBAPF),

[000242] 2,2',7,7'-tetrakis[N-naphthalenyl(phenyl)amino]-9,9-spirobifluorene (spiro-2NPB),

[000243] N,N'-bis(phenanthren-9-yl)-N,N'-bis(phenyl)benzidine (PAPB),

[000244] 2,7-bis[N,N-bis(9,9-spirobifluorene-2-yl)amino]-9,9-spirobifluorene (spiro-S),

[000245] 2,2'-bis[N,N-bis(biphenyl-4-yl)amino]-9,9-spirobifluorene (2,2'-spiro-DBP),

[000246] 2,2'-bis(N,N-diphenylamino)-9,9-spirobifluorene (spiro-BPA).

[000247] The dopant for the hole transport layer 102 is a p-type dopant and can in this case comprise or be a metal oxide, an organometallic compound, an organic material or a mixture thereof. Additionally or alternatively, the dopant can comprise a plurality of different metal oxides and/or a plurality of different organometallic compounds and/or a plurality of different organic compounds. In particular, the dopant can have Lewis acid character or be a Lewis acid. Lewis acids, that is to say electron pair acceptors, can be particularly well suited to forming charge transfer

complexes.

[000248] The dopant can comprise one or a plurality of metal oxides comprising one or a plurality of metals, wherein the metals are selected from tungsten, molybdenum, vanadium and rhenium. Particularly preferably, the dopant can comprise one or a plurality of the metal oxides WO_3, MoO_3, V_2O_5, Re_2O_7 and Re_2O_5. While rhenium pentoxide is suitable for enabling, as dopant, a hole transport layer 102 having a blue color impression, the other metal oxides mentioned are suitable for enabling a yellow to orange-colored color impression. Oxides of rhenium, in particular, are Lewis acids which can readily be evaporated at a temperature of less than 250°C and at a pressure of 10^{-6} mbar and are therefore well suited to a p-type doping. It has been possible to show experimentally that the doping properties with regard to the electronic properties of the hole transport layer 102 of rhenium pentoxide and rhenium heptoxide differ only little, such that metal oxides of this type can be chosen depending on a predetermined color impression. The other metal oxides mentioned exhibit similar processing properties for p-type doping.

[000249] Furthermore, the dopant for the p-type doping of the hole transport layer 102 can also comprise organometallic compounds having Lewis acid character. Particularly in the case of organometallic compounds or complexes having an impeller structure, the Lewis acid character of the axial position is particularly pronounced.

[000250] Furthermore, the organometallic compounds can comprise ruthenium and/or rhodium. By way of example, the dopant can comprise as organometallic compound a trifluoroacetate (TFA), for example dirhodium tetratrifluoroacetate ($Rh_2(TFA)_4$), which with (NPB) can give a bluish color impression or the isoelectronic ruthenium compound $Ru_2(TFA)_2(CO)_2$, which enables an orange-colored color impression.

[000251] Furthermore, the dopant for p-type doping can comprise organic materials which comprise aromatic functional groups or are aromatic organic

materials. In particular, the dopant can comprise aromatic materials having a pronounced number of fluorine and/or cyanide (CN) substituents.

[000252] For a charge carrier transport layer embodied as electron transport layer 106, the following matrix materials, in particular, are also suitable:

[000253] 8-hydroxyquinolinolato-lithium (Liq),

[000254] 2,2',2''-(1,3,5-benzinetriyl)-tris(1-phenyl-1-H-benzamidazole) (TPBi),

[000255] 2-(4-biphenylyl)-5-(4-tert-butylphenyl)-1,3,4-oxadiazole (PBD),

[000256] 2,9-dimethyl-4,7-diphenyl-1,10-phenanthroline (BCP),

[000257] 4,7-diphenyl-1,10-phenanthroline (BPhen),

[000258] bis(2-methyl-8-quinolinolate)-4-(phenylphenolato)aluminum (BAlq),

[000259] 1,3-bis[2-(2,2'-bipyridin-6-yl)-1,3,4-oxadiazo-5-yl]benzene (Bpy-OXD),

[000260] 6,6'-bis[5-(biphenyl-4-yl)-1,3,4-oxadiazo-2-yl]-2,2'-bipyridyl (BP-OXD-Bpy),

[000261] 3-(4-biphenylyl)-4-phenyl-5-tert-butylphenyl-1,2,4-triazole (TAZ),

[000262] 4-(naphthalen-1-yl)-3,5-diphenyl-4H-1,2,4-triazole (NTAZ),

[000263] 2,9-bis(naphthalen-2-yl)-4,7-diphenyl-1,10-phenanthroline (NBphen),

[000264] 2,7-bis[2-(2,2'-bipyridin-6-yl)-1,3,4-oxadiazo-5-yl]-9,9-dimethylfluorene (Bby-FOXD),

[000265] 1,3-bis[2-(4-tert-butylphenyl)-1,3,4-oxadiazo-5-yl]benzene (OXD-7).

[000266] For an electron transport layer 106, the matrix material is n-doped. That can mean that the dopant enables an n-type doping of the matrix material of the first charge carrier transport layer. In particular, the dopant can be embodied as an electron donor having a low ionization potential, that is to say a high-level HOMO (Highest Occupied Molecular Orbital).

[000267] In this case, the dopant can comprise or be an alkali metal salt, an alkaline earth metal salt, an organometallic compound or a mixture thereof. Additionally or alternatively, the dopant can comprise a plurality of different alkali metal salts and/or a plurality of different alkaline earth metal salts and/or a plurality of different organometallic compounds. In particular, the dopant can comprise a

carbonate. Furthermore, the dopant can particularly preferably comprise cesium. Cs_2CO_3, for example, can give a bluish color impression in BCP or in BPhen as matrix material.

[000268] Furthermore, the dopant for n-type doping can comprise a metallocene, that is to say an organometallic compound comprising a metal M and two cyclopentadienyl radicals (Cp) in the form $M(Cp)_2$. Alternatively or additionally, the dopant can also comprise a metal-hydropyrimidopyrimidine complex. The metal can comprise or be tungsten, molybdenum and/or chromium, for example.

[000269] By way of example, chromocene or decamethylchromocene can enable grey-colored color impressions for an n-doped electron transport layer 106, while organometallic compounds comprising 1,2,4,6,7,8-hexahydro-2H-pyrimido[1,2-a]pyrimidine (hpp) such as, for instance $W_2(hpp)_4$, $Mo_2(hpp)_4$ and $Cr_2(hpp)_4$ enable red to orange-colored color impressions.

[000270] The matrix materials of the charge carrier transport layers 102, 106 mentioned here and the dopants mentioned here for the matrix materials can form charge transfer complexes which absorb part of an electromagnetic radiation incident from outside on the organic light-emitting diode 1 with a first absorption spectrum and, in a switched-off electronic operating state, bring about a predetermined color impression of the component, which can be perceived by an external observer through the first electrode 101, for example. In this case, the matrix material and the dopant form electron-donor-acceptor complexes, the absorption bands of which preferably lie in the visible wavelength range. In this case, the absorption band of the charge transfer complexes is dependent on the respective energetic position of their HOMOs (Highest Occupied Molecular Orbital) and LUMOs (Lowest Unoccupied Molecular Orbital) relative to one another. Consequently, in addition to the charge carrier conductivity for holes and/or for electrons, the charge transfer complexes can have the first absorption spectrum, which can enable the predetermined color impression.

[000271] Through a suitable choice of the matrix material and of the dopant, at least of the charge carrier transport layer adjoining a radiation-transmissive or transparent electrode, it is possible to ensure electronic properties with regard to the electronic functionality of the organic light-emitting diode, such as, for instance, electrical conductivity and/or the charge carrier injection, and at the same time the predetermined color impression for the desired external appearance, at least in the switched-off electronic operating state (in this respect, also see the exemplary embodiments in figures 6A to 6D).

[000272] The first electrode 101 is a transparent anode, for example. The first electrode 101 is therefore preferably at least partly transmissive to electromagnetic radiation generated in the radiation-emitting region 104. Preferably, the first electrode 101 is transparent to said radiation. In this case, the first electrode can, for example, comprise a transparent conductive oxide or consist of a transparent conductive oxide. Transparent conductive oxides ("TCO" for short) are transparent conductive materials, generally metal oxides, such as, for example, zinc oxide, tin oxide, cadmium oxide, titanium oxide, indium oxide or indium tin oxide (ITO). Alongside binary metal-oxygen compounds such as, for example ZnO, SnO_2 or In_2O_3, ternary metal-oxygen compounds such as, for example, Zn_2SnO_4, $CdSnO_3$, $ZnSnO_3$, $MgIn_2O_4$, $GaInO_3$, $Zn_2In_2O_5$ or $In_4Sn_3O_{12}$ or mixtures of different transparent conductive oxides also belong to the group of TCOs. Furthermore, the TCOs do not necessarily correspond to a stoichiometric composition and can also be p- or n-doped.

[000273] The second electrode 107 can be embodied as a cathode and therefore serve as electron-injecting material. The second electrode 107 can be a cathode which is configured in reflective fashion and which at least partly reflects electromagnetic radiation generated in the radiation-emitting region 104. Preferably, the reflectivity is then at least 70%, at least 80% or particularly preferably at least 90%.

[000274] Inter alia, in particular aluminum, barium, indium, silver, gold,

magnesium, calcium or lithium and also compounds, combinations and alloys thereof can prove to be advantageous as cathode material. In addition, the second electrode 107 can have, on a side facing the radiation-emitting region 104, a layer comprising LiF, which has good electron injection properties. Alternatively or additionally, the second electrode can also comprise one of the abovementioned TCOs or a layer sequence composed of TCO layers and a metal layer. The second electrode 107 can then likewise be transparent.

[000275] Alternatively, the first electrode 101 can also be embodied as a cathode, and the second electrode 107 as an anode.

[000276] The electron barrier layer 103 can contain or consist of, for example, α-NPD (N,N'-di-1-naphthyl-N,N'-diphenyl-4,4'-diaminobiphenyl).

[000277] This material has a HOMO of -5 ± 0.4 eV and a LUMO of more than -2.2 eV. The hole mobility is approximately 10^{-4} cm^2/Vs.

[000278] The hole barrier layer 105 can comprise BCP or BPhen as material. What is important here is the electron mobility of more than 10^{-6} cm^2/Vs, preferably more than 10^{-5} cm^2/Vs, given a very low to even no hole mobility.

[000279] Figure 2 shows, on the basis of a schematic sectional illustration, an enlargement of an excerpt from an organic light-emitting diode 1 described here. In this case, figure 2 shows the radiation-emitting region 104 adjoined by the electron barrier layer 103 and the hole barrier layer 105. In the present case, the radiation-emitting region 104 comprises an emission layer. The emission layer 101 comprises at least one organic material which is suitable for generating electromagnetic radiation upon energization.

[000280] By way of example, the material of the emission layer 101 can be suitable for generating infrared radiation. The emission layer 101 then contains, for example, at least one of the following materials: Yb-tris(8-hydroxyquinoline), Er-

tris(8-hydroxyquinoline), YbQ3, ErQ3.

[000281] Furthermore, it is possible for the emission layer 101 to comprise emitter materials for generating red, green and/or blue light, which emitter materials can be embedded in matrix materials. By way of example, suitable emitter materials are described in conjunction with figure 3.

[000282] Figure 3 shows, on the basis of a schematic sectional illustration, a further exemplary embodiment of an organic light-emitting diode 1 described here. It is clarified with reference to figure 3 that the radiation-emitting region 104 can have a plurality of emission layers 111, 112, 113.

[000283] The first emission layer 111 is, for example, an emission layer suitable for emitting red light. The emission layer 101 then contains, for example, the following phosphorescent emitter material: $Ir(DBQ)_2acac$ (iridium(III)bis(2-methyldibenzo-[f,h]quinoxaline)(acetylacetonate)). This emitter material has a main emission wavelength of above 600 nm, and in the CIE diagram from 1931 an x value of > 0.6 and a y value of < 0.36.

[000284] The red emission layer 101 can comprise a matrix that transports holes. One suitable matrix material is α-NPD (N,N'-di-1-naphthyl-N,N'-diphenyl-4,4'-diaminobiphenyl). The material has a HOMO of -5.5 ± 0.4 eV and a LUMO of -2.1 ± 0.4 eV. The hole mobility is approximately 10^{-4} cm^2/Vs and the triplet position T1 is above 1.8 eV.

[000285] The second emission layer 112 is, for example, an emission layer which emits green light during the operation of the organic light-emitting diode 1. The emission layer 112 then contains, for example, a green emitter material, which can be embedded in a first and second matrix material. By way of example, Irppy (fac-tris(2-phenylpyridyl)iridium) can be used as green emitter material. The material has a main emission wavelength at 500 to 570 nm, and in the CIE diagram from 1931 an x value of approximately 0.37 and a y value of approximately 0.6.

[000286] A hole transporting first matrix material in the second emission layer 112 can be, for example, TCTA (4,4',4"-tris(carbazol-9-yl)triphenylamine), or it can be CBP (4,4'-bis(carbazol-9-yl)biphenyl).

[000287] These materials have a HOMO of -6.0 to -5.3 eV and a LUMO of -2.3 ± 0.1 eV, a T1 of above 2.5 eV and a hole mobility of approximately 10^{-4} cm^2/Vs.

[000288] An electron conducting second matrix material in the second emission layer 112 is, for example, BCP or BPhen, where the electron mobility should be greater than 10^{-5} cm^2/Vs, preferably 10^{-4} cm^2/Vs.

[000289] The third emission layer 113 is then, for example, an emission layer which emits blue light during the operation of the organic light-emitting diode 1. The blue, third emission layer 113 can be a fluorescent emission layer, comprising the blue fluorescent emitter material DPVBi (4,4'-bis(2,2-diphenylethen-1-yl)diphenyl).

[000290] This material has a main emission wavelength at 450 to 770 nm, a full width at half maximum at approximately 60 nm, and in the CIE diagram from 1931 x values of 0.14 to 0.22 and y values of 0.11 to 0.20.

[000291] The blue emitter material can be present in an electron conducting matrix, which can comprise TBADN (2-tert-butyl-9,10-di(2-naphthyl)anthracene) as material. This material has a HOMO of -5.8 to -5.3 eV and LUMO of -2.5 to -1.8 eV. The band gap is more than 3 eV and the electron mobility is greater than 10^{-6} cm^2/Vs, preferably greater than 10^{-5} cm^2/Vs.

[000292] Overall, during the operation of the organic light-emitting diode 1, white mixed light is emitted by the three emission layers 111, 112 and 113 in the radiation-emitting region 104.

[000293] The first electrode 101 and the second electrode 107 can be chosen as

specified in conjunction with figure 1. Furthermore, the hole transport layer 102, the electron barrier layer 103, the hole barrier layer 105 and the electron transport layer 106 can be chosen as described in conjunction with figure 1.

[000294] In the exemplary embodiment of figure 3, the use of at least one of the following matrix materials is advantageous, for example, for the hole transport layer 102: 1-TNATA (4,4',4"-tris(N-(naphth-1-yl)-N-phenylamino)triphenylamine), MTDATA (4,4',4"-tris(N-3-methylphenyl-N-phenylamino)triphenylamine), 2-TNATA (4,4',4"-tris(N-naphth-2-yl)-N-phenylamino)triphenylamine), α-NPB (N,N'-bis(naphthalen-1-yl)-N,N'-bis(phenyl)benzidine), β-NPB (N,N'-bis(naphthalen-2-yl)-N,N'-bis(phenyl)benzidine), TPD (N,N'-bis(3-methylphenyl)-N,N'-bis(phenyl)benzidine), spTAD (2,2',7,7'-diphenylaminospiro-9,9'-bifluorene), Cu-PC (phthalocyanine-copper complexes), further phthalocyanine-metal complexes, pentacene and TAPC (1,1-bis[(4-phenyl)-bis(4',4"-methylphenyl)amino]cyclohexane).

[000295] These materials have a HOMO of -5.2 ± 0.4 eV and a LUMO of -2.2 ± 0.4 eV. The hole mobility is approximately 10^{-4} cm^2/Vs and the conductivity of a doped layer given 2 to 10% by volume of the dopant is approximately 10^{-5} S/cm.

[000296] By way of example, F_4-TCNQ (2,3,5,6-tetrafluoro-7,7,8,8-tetracyanoquinodimethane) serves as dopant in the hole transport layer 102. Further dopants are molybdenum oxide and rhenium oxide, for example.

[000297] The electron transport layer 106 can advantageously contain one of the following materials as matrix material or consist of one of the following materials: BPhen, Alq_3, (tris(8-hydroxyquinoline)aluminum), $BAlq_2$ (bis[2-methyl-8-quinolinato]-[4-phenylphenolato]aluminum(III)), BCP, TPBi (1,3,5-tris(1-phenyl-1H-benzimidazol-2-yl)benzene), TAZ (3-(4-biphenyl)-4-phenyl-5-(4-tert-butylphenyl)-1,2,4-triazole), TAZ2 (3,5-diphenyl-4-naphth-1-yl-1,2,4-triazole), t-Bu-PBD (2-(4-biphenylyl)-5-(4-tert-butylphenyl)-1,3,4-oxadiazole), triazine or triazine derivatives. The matrix material has a HOMO of -6.4 to -6.0 eV, a LUMO of -2.3 to -1.8 eV, an electron mobility of more than 10^{-6} cm^2/Vs, preferably more than 10^{-5} cm^2/Vs, and a

conductivity in a doped layer (given 6 to 50% by volume of dopant) of 10^{-5} S/cm. By way of example, lithium, cesium or calcium can be used as dopant.

[000298] For all of the layers, of course, other matrix materials, dopants or emitter materials are possible, as are other compositions of the mixed matrix materials. Further materials for emitter materials, transport materials and dopants are possible and can be exchanged at any time.

[000299] In addition to the exemplary embodiment of an organic light-emitting diode described here, as described in conjunction with figure 1, the radiation-emitting region 104 in the exemplary embodiment in accordance with figure 3 has a first charge transporting layer 114 and a second charge transporting layer 115.

[000300] The first charge transporting layer 114 is arranged between the first, red-emitting emission layer 111 and the second, green-emitting emission layer 112.

[000301] The first charge transporting layer 114 comprises a first and second matrix material, for example.

[000302] The first matrix material of the first charge transporting layer 114 can comprise a hole transporting matrix material, which can be 1-TNATA or α-NPD, for example. These materials have a HOMO of -5.5 ± 0.6 eV and a LUMO of -2.1 ± 0.4 eV. The hole mobility is approximately 10^{-4} cm^2/Vs and the triplet position T1 is > 1.8 eV.

[000303] An electron conducting second matrix material in the first charge transporting layer 114 can be BCP (2,9-dimethyl-4,7-diphenyl-1,10-phenanthroline), for example. A further example is BPhen (4,7-diphenyl-1,10-phenanthroline).

[000304] These materials have the property that the HOMO is -6.4 to -5.7 eV and the LUMO is -2.3 to -1.8 eV, T1 is > 2.5 eV, and the electron mobility is approximately 10^{-6} cm^2/Vs.

[000305] A second charge transporting layer 115 is arranged between the second emission layer 112, which emits green light, and the third emission layer 113, which emits blue light.

[000306] The second charge carrier transporting layer 115 is composed of a first and a second matrix material. The first matrix material can be a hole transporting matrix material, which can be TCTA or CBP. The second electron conducting matrix material can be BCP or BPhen.

[000307] In the exemplary embodiment described in conjunction with figure 3, electromagnetic radiation is emitted through the transparent first electrode 101, which is embodied as an anode. In this case, the first electrode 101 has a thickness of between 80 nm and 140 nm, for example 120 nm.

[000308] The hole transport layer 102 preferably has a thickness of between 10 nm and 400 nm. The electron barrier layer 103 preferably has a thickness of between 5 nm and 10 nm. The first emission layer 111 preferably has a thickness of between 5 nm and 15 nm, and the first charge carrier transporting layer 114 preferably has a thickness of between 5 nm and 10 nm. The second emission layer 112 preferably has a thickness of between 5 nm and 15 nm. The second charge carrier transporting layer 115 preferably has a thickness of between 5 nm and 10 nm. The third emission layer 113 preferably has a thickness of between 5 nm and 10 nm. The hole barrier layer 105 preferably has a thickness of between 5 nm and 10 nm. The electron transport layer 106 preferably has a thickness of between 20 nm and 300 nm. The second electrode 107, embodied as a cathode, preferably has a thickness of between preferably 100 nm and 200 nm.

[000309] Furthermore, it is possible for first electrode 101 and second electrode 107 in each case to be embodied in transparent fashion. The organic light-emitting diode 1 is then a component which can emit electromagnetic radiation in at least two opposite directions. By way of example, a component which emits white light in two

opposite directions can then be involved. Furthermore, such an organic light-emitting diode 1 can be a transparent organic light-emitting diode. In this case, transparent means that the organic light-emitting diode 1 is transmissive to electromagnetic radiation preferably in the visible frequency range, such that at least 50% of the radiation passing through can pass through the organic light-emitting diode 1, without being absorbed. In this case, the organic light-emitting diode 1 can also be pellucid. That is to say that the light passing through is not or hardly scattered by the organic light-emitting diode 1.

[000310] The organic light-emitting diode in accordance with figure 3 is therefore a radiation-emitting device in which a charge transporting layer is in each case arranged between two emission layers.

[000311] In this case, the charge transporting layers each comprise a matrix, which comprises a hole conducting and an electron conducting matrix material or is a mixture of a first, hole transporting matrix material and a second, electron transporting matrix material.

[000312] In conjunction with the schematic sectional illustrations in figures 4 and 5, further exemplary embodiments are described in greater detail for the first electrode 101 (figure 4) and the second electrode (figure 5). These electrodes can be used in organic light-emitting diodes described here.

[000313] For this purpose, the first electrode 101 and second electrode 107 preferably both comprise a transparent, electrically conductive oxide (TCO) material.

[000314] In this case, at least one of the first electrode 101 and second electrode 107 can comprise a layer sequence having a first TCO layer 121 comprising a first transparent, electrically conductive oxide (TCO), a second TCO layer 122 comprising a transparent metal and a third metal layer 120 comprising a second TCO. The layer sequence having two layers each comprising a TCO and a layer in between, embodied as a transparent metal layer, can enable an electrode

which has a high transverse conductivity owing to the transparent metal layer 120 and a reduced reflectivity owing to the high refractive index layers 121, 122 comprising TCO. For an organic optoelectronic component which is transparent on both sides, that is to say fully transparent, it is also possible for both electrodes 101, 107 each to comprise such a layer sequence. What can thereby be achieved, in particular, is that the two transparent electrodes precisely do not form an optical microresonator or form at least a microresonator having a low quality factor.

[000315] In this case, the first TCO and/or the second TCO can comprise one or more of the abovementioned materials for TCOs. In particular, the first TCO and/or the second TCO can comprise or be composed of ITO, indium zinc oxide, aluminum zinc oxide and/or zinc oxide. Furthermore, the first and/or the second TCO can be doped with aluminum, vanadium and/or gallium or a combination or mixture thereof. A thickness d of a TCO layer 121, 122 comprising a TCO can be, in particular, greater than or equal to 5 nm and less than or equal to 150 nm.

[000316] The transparent metal can comprise aluminum, chromium, molybdenum, nickel, silver, platinum, barium, indium, gold, magnesium, calcium or lithium and also compounds, combinations and alloys thereof or consist of one of the abovementioned materials or combinations or alloys thereof. In this case, a metal layer 120 comprising a transparent metal can have a thickness d of greater than or equal to 1 nm and less than or equal to 50 nm, in particular greater than or equal to 20 nm and less than or equal to 40 nm.

[000317] In particular, the first electrode 101 and/or the second electrode 107 can be embodied in areal fashion or alternatively in a manner structured into first and/or second electrode partial regions. By way of example, the first electrode 101 can be embodied in the form of first electrode strips arranged parallel alongside one another, and the second electrode 107 can be embodied as second electrode strips arranged parallel alongside one another and running perpendicularly to said first electrode strips. Overlaps of the first and second electrode strips can therefore be embodied as separately drivable luminous regions. Furthermore, it is also possible

for only the first 101 or the second electrode 107 to be structured.

[000318] The combination of a transparent metal layer 120 and a transparent TCO layer 121, 122 makes it possible to realize a first 101 and/or a second electrode 107 having both good electrical and good optical properties.

[000319] In this case, "good electrical properties" can mean that the electrode 101, 107 has a low electrical resistance typical of metals and therefore also a good transverse conductivity, that is to say a high electrical conductivity, typical of a metal, along the extension direction of the electrode. In particular, the combination of a transparent metal layer 120 and a transparent TCO layer 121, 122 makes it possible to achieve a lower electrical resistance and hence a higher transverse conductivity than, for example, with a layer composed of a transparent, electrically conductive oxide alone.

[000320] "Good optical properties" can mean, in particular, that the electrode has a high transparency and furthermore a low reflectivity, in particular a lower reflectivity than a layer comprising a transparent metal alone. That can be achieved by virtue of the fact that the TCO layer 121, 122 can act as an antireflection coating. Materials having a high refractive index such as, for instance, dielectric oxides, for instance silicon oxide or tantalum oxide, and, in particular, transparent, electrically conductive oxides or mixtures thereof can be suitable for this purpose.

[000321] In this case, a high refractive index can be, for example, a refractive index of greater than or equal to 1.9. By way of example, TCOs can have refractive indices in the range of approximately 1.9 to approximately 2.1.

[000322] Alternatively or additionally, the first and/or second electrode can also have one or a plurality of layers suitable for antireflection coating and composed of a further material having a high refractive index, for instance from the region of the tellurides or sulfides, for instance ZnSe having a refractive index of approximately 2.5. Furthermore, the materials mentioned can also be present in combinations or

mixtures in the first 101 and/or second electrode 107.

[000323] Figures 6A to 6D show further exemplary embodiments of organic light-emitting diodes 1 described here.

[000324] Figures 6A and 6B show an organic light-emitting diode 1 in a switched-off electronic operating state (figure 6A) and in a switched-on electronic operating state (figure 6B).

[000325] The organic light-emitting diode 1 has a first carrier 130, which is embodied in radiation-transmissive fashion. By way of example, the first carrier 130 consists of a glass. On the first carrier 130 are a transparent first electrode 101 and a second electrode 107 arranged. Between the transparent first electrode 101 and the second electrode 107 an organic layer sequence 133 is arranged. In the exemplary embodiment shown, the organic light-emitting diode 1 is therefore embodied as a bottom emitter since it can emit through the first carrier 130.

[000326] The organic layer sequence 133 has at least one radiation-emitting region 104 and also a hole transport layer 102. In this case, the hole transport layer 102 is arranged between the first electrode 101 and the radiation-emitting region 104.

[000327] In the exemplary embodiment shown, the transparent first electrode 101 is embodied from indium tin oxide (ITO) and serves as an anode, while the second electrode 107 has a 0.7 nm thick LiF layer and a 200 nm thick aluminum layer.

[000328] The hole transport layer 102 comprises a matrix material and a dopant, which form charge transfer complexes. In this case, the charge transfer complexes have a first absorption spectrum. Electromagnetic radiation having a wavelength in the absorption range can be absorbed by the charge transfer complexes with excitation thereof. That part of an electromagnetic radiation incident on the organic

light-emitting diode 1 from outside, here indicated by means of the arrows 190, which corresponds to the absorption spectrum is therefore absorbed, while the non-absorbed part 191 of the electromagnetic radiation 190 can be scattered and reflected by the hole transport layer 102. As a result, the hole transport layer 102 can be perceived by an external observer and, in the switched-off electronic operating state of the organic light-emitting diode 1, brings about a predetermined color impression in the form of the electromagnetic radiation 191.

[000329] In the exemplary embodiment shown, the hole transport layer 102 consists of NPB as matrix material, which is p-doped with 5% Re_2O_7. In this case, the dopant is distributed homogeneously in the matrix material. This gives rise to a uniform yellowish color impression in the switched-off operating state.

[000330] The radiation-emitting region 104 has, for example, a 40 nm thick layer composed of tris(8-hydroxyquinoline)aluminum (Alq_3) as fluorescent electroluminescent material, which simultaneously serves as electron transport material. Arranged between the hole transport layer 102 and the active region 30 is a 10 nm thick NPB layer 123, which improves the hole injection from the hole transport layer 102 into the radiation-emitting region 104. As an alternative thereto, the hole transport layer 102 can also comprise the dopant with a thickness gradient in the matrix material, wherein the dopant concentration can decrease toward the radiation-emitting region 104 continuously or discontinuously.

[000331] As is indicated by the arrows 193 in figure 6B, the organic light-emitting diode 1 emits green-colored electromagnetic radiation through the radiation-emitting region 104, the first electrode 101 and the first carrier 1 in the switched-on operating state. In this case, the dashed arrows 190 and 191 indicate that although electromagnetic radiation which is incident on the organic light-emitting diode 1 from outside can still be scattered and reflected, the color impression brought about thereby is outshone by the electromagnetic radiation 193 generated in the radiation-emitting region and is therefore not perceptible.

[000332] In further exemplary embodiments, the hole transport layer 102 is embodied as a 50 nm thick layer comprising NPB as matrix material and comprising Re_2O_5 as dopant having dopant concentrations of 5%, 20% and 50%. In this case, it is found that the perceptible color impression of the light-emitting diodes 1 in the switched-off electronic operating state changes from light blue to deep blue as the concentration of the dopant increases. In the switched-on electronic operating state, by contrast, green electromagnetic radiation 193 is always emitted.

[000333] In a further exemplary embodiment, the hole transport layer 102 comprises NPB as matrix material and dirhodium tetratrifluoroacetate as dopant in the case of a thickness of 200 nm. While green electromagnetic radiation 193 is emitted in the switched-on electronic operating state, the hole transport layer 102 gives a bluish color impression in the switched-off electronic operating state.

[000334] An organic electronic component as a comparative component having a construction in accordance with figures 6A and 6B, but an undoped hole transport layer 102 composed of NPB, likewise emits green electromagnetic radiation 193, but gives only a pale blue color impression with low color saturation in the switched-off electronic operating state.

[000335] The exemplary embodiments in figures 6A and 6B, shown here purely by way of example, therefore show that a predetermined color impression can be set in the switched-off electronic operating state and can be chosen by means of the choice of matrix material and dopant, while the electromagnetic radiation emitted in the switched-on electronic operating state can always give the same luminous impression.

[000336] Figures 6C and 6D illustrate a further exemplary embodiment for an organic light-emitting diode 1 in a switched-off electronic operating state (figure 6C) and in a switched-on electronic operating state (figure 6D), which embodiment constitutes a modification of the previous exemplary embodiment.

[000337] In contrast to the organic light-emitting diode 1 in figures 6A and 6B, the organic light-emitting diode 1 here additionally has a transparent second electrode 107 composed of a transparent metal film, and also an electron transport layer 106 between the radiation-emitting region 104 and the second electrode 107. Therefore, in the exemplary embodiment shown, the organic light-emitting diode 1 is embodied as an OLED which emits on both sides. The hole transport layer 107 can be embodied as described in connection with the previous exemplary embodiments and can give a light blue color impression, for example, in the switched-off electronic operating state.

[000338] The electron transport layer 106 comprises a matrix material and a dopant, which form charge transfer complexes which absorb part of the electromagnetic radiation 190 incident on the light-emitting diode 1 from outside with a second absorption spectrum. The non-absorbed electromagnetic radiation, here indicated by the arrows 192, can be perceived by an external observer as a predetermined color impression through the second electrode 102. In this case, the color impression which can be perceived through the electron transport layer 106 through the second electrode 107 in the switched-off electronic operating state can be different than the color impression which can be perceived through the first electrode 101 on account of the hole transport layer 102.

[000339] In the exemplary embodiment shown, the electron transport layer 106 is 150 nm thick and comprises BCP as matrix material and Cs_2CO_3 as dopant having a concentration of 10%. As a result, in the switched-off electronic operating state, the electron transport layer 106 gives a deep blue color impression for an external observer. In the switched-on operating state, as shown in figure 6D, this color impression is outshone by the electromagnetic radiation generated in the radiation-emitting region 104, which radiation gives a green luminous impression as in the previous exemplary embodiments.

[000340] While the organic light-emitting diode, in the switched-off electronic operating state, can give a different color impression through the hole transport layer

102 than through the electron transport layer 106, in the switched-on electronic operating state the same luminous impression is given on both sides through the electromagnetic radiation 193 generated in the radiation-emitting region 104.

[000341] In a further exemplary embodiment having a construction in accordance with figures 6C and 6D, the electron transport layer 106, given a thickness of 150 nm, comprises Bpyppy as matrix material and Cs_2CO_3 with a concentration of 10% as dopant. The charge transfer band of the electron transport layer 106 is so intensive that it determines the color impression through the second electrode 107. As a result, the electron transport layer 106 can give a red color impression in the switched-off electronic operating state, while green electromagnetic radiation is once again emitted in the switched-on electronic operating state.

[000342] It is possible to combine the exemplary embodiments in accordance with figures 1 to 6. Such a combination can result, for example, in a transparent organic light-emitting diode which emits on both sides and which appears colored in accordance with a desired color from both sides in the switched-off operating states and emits white light in the switched-on state.

[000343] The encapsulation and hermetic sealing of organic light-emitting diodes 1 described here is explained in greater detail below. The layer construction of the functional layers such as the electrodes 101, 107, and the organic layer sequence 133, can in this case be as described in conjunction with figures 1 to 6. Furthermore, the layer construction can follow any desired combination of the layers and materials described in conjunction with figures 1 to 6.

[000344] A further exemplary embodiment of an organic light-emitting diode 1 described here is explained in greater detail in conjunction with figure 7, on the basis of a schematic plan view. Figure 8 shows an associated sectional illustration.

[000345] The organic light-emitting diode 1 comprises a first carrier 130 and a

second carrier 131. In this case, first carrier 130 and second carrier 131 are preferably embodied in plate-like fashion. That is to say that first carrier 130 and second carrier 131 are substantially planar sheets. The functional layers of the organic light-emitting diode 1 are arranged between first carrier 130 and second carrier 131. In this way, first carrier 130 and second carrier 131 serve for encapsulating the organic layer sequence 133.

[000346] First carrier 130 and second carrier 131 can be formed from the same material or from different materials. At least one of the two carriers is at least partly transmissive to electromagnetic radiation generated in the radiation-emitting region 104 of the organic light-emitting diode 1. Furthermore, it is possible for both carriers to be at least partly transmissive to said electromagnetic radiation.

[000347] By way of example, at least one of the carriers is formed with a glass. That is to say that this carrier contains a glass or preferably consists of a glass. The glass can be, for example, a borosilicate glass. Furthermore, it is possible for the glass to be a soda-lime glass (also: window glass). A soda-lime glass is distinguished by lower production costs by comparison with a borosilicate glass.

[000348] If one of the two carriers is embodied as a non-radiation-transmissive carrier, then said carrier can consist of a metal or contain a metal or consist of a ceramic material or contain a ceramic material.

[000349] Furthermore, it is possible for first carrier 130 and second carrier 131 each to consist of a glass. The two carriers can then also consist of the same glass.

[000350] The organic layer sequence 133 arranged between first carrier 130 and second carrier 131 can be electrically contact-connectable for example by means of the first electrode 101 and the second electrode 107, wherein first electrode 101 and second electrode 107 can be accessible from outside the organic light-emitting diode 1, as is indicated in figure 8, for example.

[000351] For the purpose of connecting first carrier 130 and second carrier 131, in the exemplary embodiments in figures 7 and 8, a connecting means 140 is situated between first carrier 130 and second carrier 131. The connecting means encloses the organic layer sequence 133 in a frame-like manner. In this case, the expression "in a frame-like manner" does not relate to the geometrical form of the course of the connecting means 140. All that is important is that the connecting means 140 laterally completely encloses the organic layer sequence 133. The connecting means 140 is therefore led as a track around the organic layer sequence 133, wherein the connecting means 140 can be in direct contact with first carrier 130 and second carrier 131.

[000352] The connecting means 140 can be, for example, a glass solder material, a glass frit material or an adhesive. Furthermore, it is possible for the organic light-emitting diode 1 to have, alongside the connecting means 140, a further connecting means, which is likewise arranged around the organic layer sequence 133 in a frame-like manner. The materials of the two connecting means can then differ from one another. By way of example, one connecting means can be formed with an adhesive, and the other connecting means can then be formed with a glass solder or a glass frit material.

[000353] An explanation is given, on the basis of the schematic sectional illustration in figure 9, of the fact that the connecting means 140 can be hardened or softened by means of a source 145 of electromagnetic radiation 146.

[000354] If the connecting means 140 is, for example, an adhesive such as Nagase or ThreeBond, then it is possible to use the source 145 for locally curing the adhesive. In this case, the source 145 is arranged in such a way that hardly any or no electromagnetic radiation 146 at all impinges on the organic layer sequence 133. That is to say that the organic layer sequence 133 cannot be damaged by the electromagnetic radiation 146 of the source 145.

[000355] If the connecting means 140 is a glass solder or a glass frit material,

then the glass solder or the glass frit material 140 can be softened by means of the electromagnetic radiation 146. The softened glass solder or glass frit material then wets at least one of the carriers, thereby giving rise to a hermetically impermeable seal of the organic light-emitting diode 1. In particular, in this case, the source 145 can be a laser which emits infrared radiation 146, for example, which penetrates through the second carrier 131 and is only absorbed in the connecting means 140.

[000356] Figure 10 shows, on the basis of a schematic sectional illustration, a further exemplary embodiment of an organic light-emitting diode 1 described here. The organic light-emitting diode 1 comprises a first carrier 130, which can consist of a glass, for example. The glass is preferably at least partly transmissive to electromagnetic radiation generated in the radiation-emitting region 104 of the organic light-emitting diode 1.

[000357] The first carrier 130 is succeeded by a connection line 155. The connection line 155 is a radiation-transmissive, electrically conductive layer. The connection layer 155 can be formed, for example, by one of the transparent electrode materials presented above. The first electrode 101 is arranged on the connection line 155, said first electrode likewise being embodied in transparent fashion.

[000358] Busbars 157 can be arranged in or at the first electrode 101. The busbars can be formed by thin metal strips, for example. By way of example, a layer sequence having layers composed of chromium and aluminum is suitable for forming the busbars. Furthermore, the busbars can consist of aluminum, chromium, silver or mixtures of these materials. The busbars improve the transverse conductivity of the first electrode 101. They can be insulated from the overlying organic layer sequence 133 by an insulation layer, for example, such that current is not directly impressed from the busbars 157 into the organic layer sequence 133. The busbars 157 then serve only for the better distribution of electric current within the first, transparent electrode 101.

[000359] The organic layer sequence 133 is succeeded by the second electrode 107. The second electrode 107 is embodied in reflective fashion, for example, as described above.

[000360] The first electrode 101 can be electrically contact-connected from outside the organic light-emitting diode 1 by means of the connection location 152, which can be formed with a TCO material or a metal. The connection location 152 is electrically insulated from the second electrode 107 by means of an insulation layer 151 containing an electrically conductive material such as a resist, an epoxy resin or a silicon oxide.

[000361] During the operation of the organic light-emitting diode 1, an emission 108 of electromagnetic radiation generated in the organic layer sequence 133, in particular in the radiation-emitting region 104, is effected through the first carrier 130 toward the outside.

[000362] The organic light-emitting diode 1 furthermore has a thin-film encapsulation 154 serving for encapsulating the organic layer sequence 133. The thin-film encapsulation 154 produces a basic impermeability to environmental influences, such as moisture and atmospheric gases, for the organic layer sequence 133. The thin-film encapsulation 154 can be applied by means of a PECVD method (plasma enhanced chemical vapor deposition), for example. The thin-film encapsulation 154 can, for example, consist of oxide and/or nitride layers, such as SiO or SiN, or contain said materials. In this case, it is also possible for the thin encapsulation 154 to comprise a layer sequence which alternately has nitride and oxide layers.

[000363] In this case, the thin-film encapsulation 154 can have lattice defects 163 (in this respect, also see figure 19). Said lattice defects 163 can result, for example, in so-called pinholes or other imperfections which lead to a permeability of the thin-film encapsulation 154 to atmospheric gases or moisture.

[000364] In the exemplary embodiment in figure 10, a diffusion barrier 153 is arranged on the thin-film encapsulation 154. The diffusion barrier 153 is formed from amorphous SiO_2, for example. In this case, the diffusion barrier 153 is deposited by means of atmospheric pressure plasma, for example. The diffusion barrier 153 can, in particular, also be deposited onto the side areas of the organic light-emitting diode 1. Thus, the diffusion barrier 153 can also cover the insulation layer 151 and the connection locations 152 at least in places. The organic light-emitting diode 1 is therefore encapsulated with the diffusion barrier 153 and protected from environmental protection influences both from its outer area facing away from the first carrier 130 and at its side areas.

[000365] The diffusion barrier 153 can also be applied by means of atmospheric pressure plasma in a plurality of individual layers. Consequently, the different partial regions of the diffusion barrier 153 can also have different thicknesses. In this way, a diffusion barrier 153 of increased thickness can be applied where the risk of formation of lattice defects 163 is highest - for example at edges of layers.

[000366] An atmospheric pressure plasma (also called AP plasma or normal pressure plasma) is understood in this case to mean the special case of a plasma in which the pressure approximately corresponds to that of the surrounding atmosphere. The use of an atmospheric pressure plasma has some advantages over the use of a low-pressure plasma encapsulation technique. The apparatus outlay for coating with an atmospheric pressure plasma is significantly less than in the case of the low-pressure plasma. In the case of the low-pressure plasma it is necessary, for example, for the component that is to be coated to be introduced into a chamber and for the pressure then to be reduced therein. After the deposition process, the pressure has to be adapted to normal pressure again and the component has to be removed from the chamber again. In the case where an atmospheric pressure plasma is used, by contrast, it is not necessary to introduce the component - here the organic light-emitting diode 1 - into a closed chamber. The coating with the diffusion barrier 153 is therefore also possible on an assembly line, for example, using an atmospheric pressure plasma.

[000367] The diffusion barrier can have a thickness d of 50 nm to 1000 nm. Preferably, the diffusion barrier 153 has a thickness d of at least 100 nm and at most 250 nm. At the edges of the organic light-emitting diode 1, the thickness of the diffusion barrier 153 can also be chosen to be larger.

[000368] The diffusion barrier 153 can also be produced from individual layers. In this case, two or more individual layers can be deposited one above another. Each of the individual layers can have a thickness of, for example, at least 50 nm and at most 100 nm. The impermeability of the overall layer can be increased by applying individual layers.

[000369] The diffusion barrier 153 can comprise silicon dioxide or consist thereof. In this case, the silicon dioxide can only be formed in the gas phase. In order to form the silicon dioxide, it is possible to use a silane and a further compound serving as oxygen source. By way of example, SiH_4 can be used as silane and N_2O as oxygen source.

[000370] Figure 11 shows, on the basis of a schematic sectional illustration, a further exemplary embodiment of an organic light-emitting diode described here. In contrast to the exemplary embodiment in figure 10, in this exemplary embodiment the diffusion barrier 153 is only arranged at the side areas of the organic light-emitting diode 1. Instead of a diffusion barrier 153, a resist layer 150 is applied to that outer area of the organic light-emitting diode which faces away from the first carrier 130. That is to say that, in this exemplary embodiment, the outer area facing away from the first carrier 130 is encapsulated by a combination of a thin-film encapsulation 154 with a resist layer 150.

[000371] A further exemplary embodiment of an organic light-emitting diode 1 described here is explained in greater detail in conjunction with figure 12. In contrast to the exemplary embodiment in figure 11, in this exemplary embodiment a diffusion barrier 153 produced by means of an atmospheric pressure plasma is arranged

between the thin-film encapsulation 154 and the resist layer 150. The resist layer covers the diffusion barrier 153 at least in places.

[000372] A further exemplary embodiment of an organic light-emitting diode 1 described here is explained in greater detail in conjunction with figure 13. In contrast to the exemplary embodiment in figure 11, in this exemplary embodiment a diffusion barrier 153 produced by means of an atmospheric pressure plasma is additionally applied to the resist layer 150. The diffusion barrier 153 covers the resist layer 150 at all exposed surfaces. A particularly impermeable encapsulation of the organic layer sequence 133 against external environmental influences is realized as a result.

[000373] A further exemplary embodiment of an organic light-emitting diode described here is explained in greater detail in conjunction with figure 14A. In this exemplary embodiment, the insulation layer 151, the connection location 152 and also the thin-film encapsulation 154 are covered at least in places by a pre-encapsulation layer 156, which serves for encapsulating the organic layer sequence 133 and as a planarization layer for the thin-film encapsulation 153 at the side areas of the organic light-emitting diode 1. The pre-encapsulation layer 156 can comprise, for example, a transparent epoxide or a radiation-transmissive adhesive. A second carrier 131 is applied to the pre-encapsulation layer 156, onto the outer area thereof which faces away from the first carrier 130. The second carrier 131 can be a glass plate, for example. It is then possible for an emission 108 to be effected both through the first carrier 130 and through the second carrier 131. The organic light-emitting diode 1 can then be an organic light-emitting diode 1 which emits on both sides. In this case, the diffusion barrier 153 produced by means of atmospheric pressure plasma serves substantially for laterally sealing the organic light-emitting diode 1.

[000374] In this case, it is furthermore possible that first carrier 130 and second carrier 131 can be formed by mutually different materials. By way of example, one of the two carriers can be formed by a non-radiation-transmissive material, such as a metal plate, for example.

[000375] Furthermore, it is possible for first carrier 130 and second carrier 131, as described in conjunction with figures 7 and 8, for example, to be connected to one another by means of a connecting means 140. The connecting means can then be a glass solder or a glass frit material or an adhesive. The connecting means 140 is additionally sealed by the diffusion barrier 153 at the side areas of the organic light-emitting diode 1. Such a organic light-emitting diode 1 is elucidated in greater detail in figure 14B on the basis of a schematic sectional illustration.

[000376] In conjunction with figures 15, 16, 17, 18 and 19, exemplary embodiments of organic light-emitting diodes 1 described here are explained in greater detail wherein at least parts of the organic light-emitting diode 1 are encapsulated by at least two encapsulation layers 161, 162 forming an encapsulation layer sequence 160. That is to say that the encapsulation layer sequence 160 has at least one first encapsulation layer 161 and a second encapsulation layer 162, as a result of which an efficacious and effective encapsulation is made possible. In this case, the effective encapsulation can be brought about precisely by the combination of the two encapsulation layers 161, 162.

[000377] The first encapsulation layer 161 and the second encapsulation layer 162 can each comprise materials suitable for protecting the organic light-emitting diode 1 against harmful influences of the surroundings, such as atmospheric gases and moisture, through the combination of the first encapsulation layer 161 and the second encapsulation layer 162. In this case, the first encapsulation layer 161 and the second encapsulation layer 162 can each comprise an inorganic material or consist of an inorganic material.

[000378] The first encapsulation layer 161 can comprise or consist of an oxide, a nitride or an oxynitride. By way of example, the oxide, nitride or oxynitride can comprise aluminum, silicon, tin, zinc, titanium, zirconium, tantalum, niobium or hafnium. Particularly preferably, the first layer can comprise silicon nitride, such as, for instance, Si_2N_3, silicon oxide (SiO_x), such as, for instance, silicon dioxide, aluminum oxide, such as, for instance, Al_2O_3, and/or titanium oxide, such as TiO_2.

Furthermore, the first encapsulation layer 161 can also consist of a TCO material or contain such a TCO material. Furthermore, it is possible for the first encapsulation layer 161 to comprise or consist of a metal or a metal alloy. In this case, the first encapsulation layer 161 can comprise aluminum and/or aluminum alloys, for example.

[000379] The abovementioned materials can be applied by means of plasma enhanced chemical vapor deposition (PECVD), for example, in order to produce the first encapsulation layer 161. In this case, a plasma can be generated in a volume above and/or around the radiation-emitting layer sequence 133 and the electrodes 101, 107, wherein at least two gaseous starting compounds are fed to the volume, which starting compounds can be ionized in the plasma and excited to react with one another. The generation of the plasma can make it possible that the temperature to which the at least one surface of the component has to be heated in order to make it possible to produce the first encapsulation layer 161 can be lowered in comparison with a plasmaless CVD method.

[000380] As an alternative thereof, the first encapsulation layer 161 can be applied by means of physical vapor deposition, such as sputtering, for instance.

[000381] Furthermore, the first encapsulation layer 161 can also comprise a glass or consist of a glass. In this case, the glass can, for example, comprise one or a plurality of the abovementioned oxides and be able to be applied by means of plasma spraying.

[000382] In the case of plasma spraying, an arc can be generated in a so-called plasma torch between at least one anode and at least one cathode by means of high voltage, through which arc a gas or gas mixture can be conducted and thereby ionized. The gas or gas mixture can comprise argon, nitrogen, hydrogen and/or helium, for example. By way of example, pulverulent material for the first encapsulation layer 161 can be sprayed into the plasma flow generated by the arc and the gas or gas mixture flow. The pulverulent material can be melted by the

temperature of the plasma and applied to the top side 107a of the second electrode 107, for example, by means of the plasma flow. The pulverulent material can be provided, for example, with an average grain size of less than or equal to a few hundred micrometers, preferably less than or equal to 100 µm, and furthermore greater than or equal to 100 nm, preferably greater than or equal to 1 µm. The more finely the material is provided, that is to say the smaller the average grain size, the more uniformly the first encapsulation layer 161 can be applied. The more coarsely the material is provided, that is to say the larger the average grain size, the more rapidly the first encapsulation layer 161 can be applied. Furthermore, the structure and also the quality of the first encapsulation layer can depend on the speed, the temperature and/or the composition of the plasma gas.

[000383] As an alternative to plasma spraying, a first encapsulation layer 161 comprising glass can also be applied by means of flame spraying or by means of a thermal evaporation method.

[000384] The abovementioned methods for applying the first encapsulation layer 161 enable the latter to be applied cost-effectively with a high growth rate. In particular, after application, the first encapsulation layer 161 can have a thickness d of greater than or equal to 50 nm, and particularly preferably a thickness d of greater than or equal to 100 nm. Furthermore, the first encapsulation layer 161 can have a thickness d of less than or equal to 1 µm. By means of such a thick first encapsulation layer, the encapsulation arrangement, alongside the encapsulation, can also enable a mechanical protection of the organic light-emitting diode 1 against damaging external influences.

[000385] The abovementioned methods, in particular at temperatures of the component of less than 120°C, and particularly preferably of less than 80°C, enable the first encapsulation layer 161 to be able to be applied directly on the component, without the component or parts thereof being damaged.

[000386] The volume structure of the first encapsulation layer 161 can be present,

for example, in crystalline and/or polycrystalline form. In this case, it can be possible for the volume structure of the first encapsulation layer to have, for example, structural and/or lattice defects 163 such as, for example, dislocations, grain boundaries and/or stacking faults.

[000387] Furthermore, the first encapsulation layer 161 can have, on the side which faces away from the organic layer sequence 133 and on which the second encapsulation layer 162 is arranged, a surface structure in the form of macroscopic topographical structures such as, for instance, slopes, elevations, angles, edges, corners, depressions, trenches, grooves, microlenses and/or prisms and/or in the form of microscopic topographical structures such as, for instance, a surface roughness and/or pores (in this respect, see figure 19, in particular). In this case, structures of the surface structure which are resolvable by means of visible light are ascribed to the macroscopic structures, while microscopic structures are precisely no longer resolvable by means of visible light. That can mean that here structures designated as macroscopic have dimensions of greater than or equal to approximately 400 nm, while microscopic structures have dimensions which are less than approximately 400 nm.

[000388] The surface structure can be governed by the abovementioned application methods themselves or else be producible, in particular in the case of macroscopic structures, by suitable further method steps such as, for instance, the deposition through a mask and/or subsequent processing by means of mechanical and/or chemical removing methods. Macroscopic structures can be suitable for light refraction and/or scattering, for example, in the case of a transparent encapsulation layer sequence 160.

[000389] In particular both the abovementioned structural and lattice defects of the volume structure of the first encapsulation layer 161 and pores in the surface structure of the first encapsulation layer 161 can form undesirable permeation paths for moisture and/or oxygen, which can enable or at least facilitate diffusion through the first encapsulation layer.

[000390] The second encapsulation layer 162 can be suitable for enabling, in combination with the first encapsulation layer 161, the hermetically impermeable encapsulation of the organic light-emitting diode 1. For this purpose, the second encapsulation layer 162 can be suitable, in particular, for sealing the abovementioned permeation paths that can occur in the first encapsulation layer.

[000391] For this purpose, the second encapsulation layer 162 can be arranged directly on the first encapsulation layer 161 and in direct contact with the first encapsulation layer 161. That can mean that the second encapsulation layer 162 has a common interface with the first encapsulation layer 161, and furthermore an upper surface facing away from the common interface. The common interface is arranged, for example, at the top side 161a of the first encapsulation layer 161.

[000392] The second encapsulation layer 162 can be embodied in such a way that it can at least partly or approximately follow the surface structure of the first encapsulation layer 161, which can mean that, in particular, the top side of the second encapsulation layer 162 also at least partly or approximately follows the topographical structure of the interface.

[000393] The fact that the upper surface of the second encapsulation layer 162 at least partly follows the interface between the first 161 and second encapsulation layer 162 and hence the surface structure of the first encapsulation layer 161 can mean here and hereinafter that the upper surface of the second encapsulation layer 162 likewise has a topographical surface structure. In this case, the topographical surface structure at the top side 162a of the second encapsulation layer 162 can preferably be embodied identically or similarly to the topographical surface structure at the top side 161a of the first encapsulation layer 161. "Identically" or "similarly" can mean in connection with two or more topographical surface structures, in particular, that the two or more topographical surface structures have identical or similar height profiles with mutually corresponding structures, such as elevations and depressions, for instance. By way of example, the two or more topographical surface

structures in this sense can each have elevations and depressions arranged laterally alongside one another in a specific characteristic sequence which, for example, apart from relative height differences between the elevations and depressions, are identical for the two or more topographical surface structures.

[000394] In other words, one surface which at least partly follows the topographical surface structure of another area can have an elevation, arranged above an elevation of the topographical surface structure of the other area, or a depression, arranged above a depression of the topographical surface structure of the other area. In this case, the relative height difference between adjacent elevations and depressions of said one surface can also be different than the relative height difference between the corresponding elevations and depressions of the topographical surface structure of the other area.

[000395] In other words, that can mean that the upper surface of the second encapsulation layer and the interface between the first and second encapsulation layers run parallel or at least approximately parallel. Thus, the second encapsulation layer can have a thickness which is independent or approximately independent of the surface structure of that surface of the first encapsulation layer which faces away from the component. "Approximately parallel", "approximately independent" and "approximately constant" can mean, with regard to the thickness of the second encapsulation layer, that the latter has a thickness variation of less than or equal to 10%, and particularly preferably of less than or equal to 5%, measured in relation to the total thickness of the second encapsulation layer. Such an embodiment of the second encapsulation layer with such a small thickness variation can also be designated as so-called "conformal coating".

[000396] Furthermore, the second encapsulation layer 162 can have a thickness d which is smaller than the dimensions of at least some structures and, in particular, the abovementioned macroscopic structures of the surface structure of the first encapsulation layer. In particular, the second encapsulation layer can also follow those microscopic structures of the surface structure of the first encapsulation layer

whose dimensions are larger than the thickness of the second encapsulation layer.

[000397] The thickness of the second encapsulation layer 162 can furthermore be independent of a volume structure of the first encapsulation layer. That can mean that the first encapsulation layer has no thickness variation of greater than 10% and particularly preferably no thickness variation of greater than 5% even over the partial regions of the first encapsulation layer in which abovementioned lattice and/or structural defects 163 of the volume structure of the first encapsulation layer 161 are situated and which extend, in particular, as far as the common interface 161a with the second encapsulation layer 162.

[000398] Furthermore, the thickness d of the second encapsulation layer 162 can, in particular, also be independent of openings, elevations, depressions and pores in that surface of the first encapsulation layer which faces the second encapsulation layer. In the case where such surface structures are greater than the thickness d of the second encapsulation layer 162 with regard to their dimensions, they can be covered by the second encapsulation layer with uniform and, in the sense above, at least virtually identical thickness by virtue of the second encapsulation layer 162 following the surface structure. In the case where the surface structures are less than or equal to the thickness of the second encapsulation layer 162 with regard to their dimensions, the second encapsulation layer 162 can cover the structure structures without following the latter, and in this case, however, likewise have an, in the above sense, at least virtually constant thickness.

[000399] In particular, the second encapsulation layer 162 can seal openings and/or pores in the first encapsulation layer which have a depth-to-diameter ratio of greater than or equal to 10, and particularly preferably of greater than or equal to 30. The encapsulation layer sequence 160 can have the at least approximately identical thickness d of the second encapsulation layer 162, as described here, in particular also when the first encapsulation layer 161 has a surface structure having overhanging structures, in particular overhanging macroscopic structures, having negative angles.

[000400] Furthermore, the second encapsulation layer 162 can have a volume structure which is independent of the surface structure of the top side 161a of the first encapsulation layer 161 facing the second encapsulation layer 162. In addition, the second encapsulation layer 162 can have a volume structure which is independent of the volume structure of the first encapsulation layer 161. That can mean that surface- and/or volume-specific properties and features of the first encapsulation layer 161 such as, for instance, the abovementioned surface structures and/or lattice and/or structural defects in the volume structure of the first encapsulation layer 161 have no influence on the volume structure of the second encapsulation layer.

[000401] The second encapsulation layer 162 can comprise an oxide, a nitride and/or an oxynitride as described in connection with the first encapsulation layer. Particularly preferably, the second encapsulation layer can comprise aluminum oxide, for instance Al_2O_3, and/or tantalum oxide, for instance Ta_2O_5.

[000402] In particular, the second encapsulation layer 162 can have a volume structure having a higher amorphicity, that is to say irregularity in the sense of short-range and/or long-range order of the materials contained, than the first encapsulation layer. That can mean, in particular, that the second encapsulation layer has such a high amorphicity that no crystallinity or crystal structure can be ascertained. In this case, the second encapsulation layer 162 can be completely amorphous, such that the materials forming the second encapsulation layer 162 have no measurable short-range and/or long-range order, but rather have a purely statistical, irregular distribution.

[000403] As a reference for ascertaining the amorphicity of the second encapsulation layer 162 and also of the first encapsulation layer 161, in this case a shallow angle measurement in an X-ray diffractometer can be used, for example, in which no crystallinity in the form of a crystalline, partly crystalline and/or polycrystalline structure can be ascertained for the amorphous second encapsulation

layer 162.

[000404] Although encapsulation layers having a crystalline, that is to say non-amorphous, volume structure often have a higher density than encapsulation layers having an amorphous volume structure, it was surprisingly ascertained in conjunction with the device comprising the encapsulation layer sequence 160, as described here, that the second encapsulation layer 162, if it has a high amorphicity, nevertheless enables, in combination with the first encapsulation layer 161, a hermetically impermeable encapsulation layer sequence 160. In particular, it can be advantageous in this case that the amorphous second encapsulation layer 162 does not continue structural and/or lattice defects 163 of the first encapsulation layer 161, such that, as a result, no continuous permeation paths for moisture and/or oxygen through the encapsulation arrangement can form either. Precisely through the combination of the first encapsulation layer 161 with the amorphous second encapsulation layer 162 it is possible to achieve an encapsulation layer sequence 160 which has a hermetic impermeability with respect to moisture and/or oxygen and at the same time a sufficiently large total thickness also to ensure a mechanical protection of the component.

[000405] The second encapsulation layer 162 can be producible on the first encapsulation layer 161 by a method in which the surface structure and/or the volume structure of the first encapsulation layer 161 have no influence on the volume structure of the second encapsulation layer 162 to be applied. The second encapsulation layer 162 can be producible, in particular, by means of a method such that the material or materials to be applied for the second encapsulation layer 162 can be applied without long-range order, that is to say with an irregular distribution for producing an amorphous volume structure. In this case, the second encapsulation layer 162 can be applied, for example, in the form of individual layers of the material or materials to be applied, so-called monolayers, wherein each of the monolayers follows the surface structure of the area to be coated. In this case, the constituents and materials of a monolayer can be distributed and applied in a statistically and distributed manner and independently of one another on the entire

area to be coated, wherein, particularly preferably, the entire area is covered continuously with the monolayer. In this case, the area to be coated can be that surface of the first encapsulation layer 161 which faces away from the organic layer sequence 133 or a monolayer already applied on the first encapsulation layer 161.

[000406] A method which enables such individual layers to be applied can be designated as a variant of atomic layer deposition. Atomic layer deposition (ALD) can designate a method in which, in comparison with an above-described CVD method for producing an encapsulation layer 162 on a surface, firstly a first of at least two gaseous starting compounds is fed to a volume, in which the component is provided. The first starting compound can adsorb on the surface. For the encapsulation layer sequence 160 described here it can be advantageous if the first starting compound adsorbs irregularly and without a long-range order on the surface. After preferably complete or virtually complete covering of the surface with the first starting compound, a second of the at least two starting compounds can be fed in. The second starting compound can react with the first starting compound adsorbed at the surface as irregularly as possible but preferably with complete area coverage, as a result of which a monolayer of the second encapsulation layer 162 can be formed. As in the case of a CVD method, it can be advantageous if the at least one surface is heated to a temperature above room temperature. As a result, the reaction for forming a monolayer can be thermally initiated. In this case, the surface temperature, which, for example, can also be the component temperature, that is to say the temperature of the component, can depend on the starting materials, that is to say the first and second starting compounds. By repeating these method steps, a plurality of monolayers can successively be applied one on top of another. In this case, for the production of the encapsulation layer sequence 160 described here it is advantageous if the arrangements of the materials or starting compounds of the individual monolayers are independent of one another from monolayer to monolayer, such that an amorphous volume structure can form not only laterally along the extension plane of the surface to be coated, but also into the height.

[000407] The first and second starting compounds can be, for example, in

connection with the materials mentioned further above for the second encapsulation layer, organometallic compounds such as, for instance, trimethyl metal compounds and also oxygen-containing compounds. In order to produce a second encapsulation layer comprising Al_2O_3, it is possible to provide, for example, trimethylaluminum and also water or N_2O as starting compounds.

[000408] A plasmaless variant of atomic layer deposition ("plasmaless atomic layer deposition", PLALD) can in this case designate an ALD method for which no plasma is generated, as described below, but rather in which, in order to form the monolayers, the reaction of the abovementioned starting compounds is initiated only by means of the temperature of the surface to be coated.

[000409] The temperature of the at least one surface and/or of the component can be, for example, greater than or equal to 60°C and less than or equal to 120°C in the case of a PLALD method.

[000410] A plasma enhanced variant of atomic layer deposition ("plasma enhanced atomic layer deposition", PEALD) can designate an ALD method in which the second starting compound is fed in with simultaneous generation of a plasma, as a result of which, as in the case of PECVD methods, it can be possible for the second starting compound to be excited. As a result, in comparison with a plasmaless ALD method, the temperature to which the at least one surface is heated can be reduced and the reaction between starting compounds can nevertheless be initiated by the generation of plasma. In this case, the monolayers can be applied, for example, at a temperature of less than 120°C and preferably less than or equal to 80°C. In order to produce further monolayers, the steps of feeding in the first starting compound and then feeding in the second starting compound can be repeated.

[000411] The degree of amorphicity of the second encapsulation layer 162 can be implemented by the choice of suitable starting compounds, temperatures, plasma conditions and/or gas pressures.

[000412] After application, the second encapsulation layer 162 can be applied in a thickness d of greater than or equal to 1 nm, particularly preferably of greater than or equal to 10 nm, and less than or equal to 30 nm. That can mean that the second encapsulation layer 162 has greater than or equal to 1 monolayer, particularly preferably greater than or equal to 10 monolayers, and less than or equal to 50 monolayers of the materials of the second encapsulation layer. By virtue of the high density and quality of the second encapsulation layer 162, such a thickness can be sufficient to ensure an effective protection against moisture and/or oxygen for the underlying component in combination with the first encapsulation layer 161. On account of the small thickness d of the second encapsulation layer 162, a short process time and hence a high economic viability of the encapsulation arrangement described here can be ensured. The encapsulation layer sequence 160 can, in particular, be arranged directly and immediately on an electrode 107, 101. That can mean that the first encapsulation layer 161 of the encapsulation layer sequence 160 is arranged directly and immediately for example on the second electrode 107.

[000413] Furthermore, the encapsulation layer sequence 160 can have a third encapsulation layer, which is arranged between the first encapsulation layer 161 and the organic layer sequence 133. In this case, the third encapsulation layer can comprise, in particular, an inorganic material as described in connection with the second encapsulation layer 162. Furthermore, the third encapsulation layer can be amorphous. Furthermore, the third encapsulation layer can have one or a plurality of further features as described in connection with the second encapsulation layer 162. Furthermore, the second and third encapsulation layers can be embodied identically.

[000414] The first encapsulation layer 161 can be arranged directly and immediately on the third encapsulation layer. Furthermore, the third encapsulation layer can be arranged directly on the component. In this case, the third encapsulation layer can enable, for the first encapsulation layer, a homogeneous application surface independently of the surface of the component.

[000415] Furthermore, the encapsulation layer sequence 160 can have a plurality

of first 161 and a plurality of second encapsulation layers 162 which are arranged alternately one above another, wherein the encapsulation layer arranged the closest to the organic layer sequence 133 is a first encapsulation layer 161. The first 161 and second encapsulation layers 162 of the plurality of the first 161 and second encapsulation layers 162, respectively, can each be embodied identically or differently. In this case, here and hereinafter, a "plurality" can mean at least a number of two.

[000416] By means of such repetition of the encapsulation layer construction comprising the first and second encapsulation layers, the encapsulation of the organic light-emitting diode 1 can be improved. Furthermore, the mechanical robustness of the encapsulation layer sequence 160 can be increased. The optical properties of the encapsulation arrangement can be adapted through a suitable choice of the materials of the respective first and second encapsulation layers.

[000417] The following can also be explained in concrete terms with respect to the individual figures 15 to 19:

[000418] A further exemplary embodiment of an organic light-emitting diode 1 described here is explained in greater detail in conjunction with figure 15, on the basis of a schematic sectional illustration. The organic light-emitting diode 1 comprises a first carrier 130. The first carrier can be formed from a radiation-transmissive material, such as a glass, for example, or a non-radiation-transmissive material, such as a metal or a ceramic material, for example. The functional layers 180, that is to say the first electrode 101, the organic layer sequence 133 and also the second electrode 107, are arranged on the first carrier 130. A first encapsulation layer 161, as has just been explained in greater detail, is applied to the side areas and also at the top side 107a of the second electrode 107. The exposed outer area of the first encapsulation layer 161 is completely covered by the second encapsulation layer 162, which is likewise constructed in the manner just explained. The first encapsulation layer 161 and the second encapsulation layer 162 form the encapsulation layer sequence 160.

[000419] A further exemplary embodiment of an organic light-emitting diode 1 described here is explained in greater detail in conjunction with figure 16, on the basis of a schematic sectional illustration. In contrast to the exemplary embodiment described in conjunction with figure 15, the first carrier 130 in this exemplary embodiment is embodied as a flexible carrier. In this case, the flexible carrier is hermetically sealed all around by an encapsulation layer sequence 60 described above. As an alternative to the first carrier 130 being encapsulated all around, it is also possible for only the top side of the flexible carrier facing the organic layer sequence 133 to be provided with the encapsulation layer sequence 160. At all events, a carrier which is flexible and at the same time sealed hermetically impermeably against external influences such as moisture and atmospheric gases is realized in this way. The first carrier 130 can, in this way, be formed for example by an inherently gas- and/or moisture-permeable plastic film which can hermetically terminate the organic light-emitting diode 1 on account of the encapsulation with the encapsulation layer sequence 160.

[000420] A further exemplary embodiment of an organic light-emitting diode 1 described here is explained in greater detail in conjunction with figure 17, on the basis of a schematic sectional illustration. In this exemplary embodiment, the first carrier 130 and the functional layers 180 arranged on the first carrier 130 are enclosed jointly, all around by the encapsulation layer sequence 160. Such an embodiment is particularly well suited to the formation of a flexible organic light-emitting diode 1. In this case, the first carrier 130 can be configured in flexible fashion, for example as a film. The functional layers 180 are encapsulated jointly with the first carrier 130, thus resulting in a certain flexibility for the entire organic light-emitting diode. That is to say that the organic light-emitting diode is pliable and suitable for withstanding a multiplicity of bending cycles without being damaged.

[000421] A further exemplary embodiment of an organic light-emitting diode described here is explained in greater detail in conjunction with figure 18. In this exemplary embodiment, the organic light-emitting diode comprises two carriers 130,

131. Both carriers 130, 131 can be embodied as rigid carriers. By way of example, the carriers 130, 131 are each formed with a glass or consist of a glass. The carriers 130, 131 are connected to one another by a connecting means 140 such as is described further above with figures 7 or 8, for example. The connecting means 140 is, for example, a glass solder or a glass frit material. The connecting means 140 adjoins the second carrier 131 and the first carrier 130 at least in places at its top side 140a and its underside 140b, respectively. The side areas 140c of the connecting means 140 are sealed with the encapsulation layer sequence 160. In this case, the encapsulation layer sequence 160 can also extend over the side areas of first carrier 130 and second carrier 131 (not illustrated).

[000422] Figure 18 represents a general example of the fact that the sealing and encapsulation techniques described here can be combined with one another. Thus, the encapsulation layer sequence 160 described in conjunction with figures 15 to 19 can also be combined in combination with the connecting means 140 described here, the diffusion barrier 153, the thin-film encapsulation 154, the pre-encapsulation layer 156 and/or the resist layer 150. Depending on the requirements made of the organic light-emitting diode 1, therefore, it is possible to choose an encapsulation which enables a longest possible lifetime of the organic light-emitting diode 1 in the respective environment in which the organic light-emitting diode 1 is intended to be used.

[000423] In conjunction with figure 19, the encapsulation layer sequence 160 having the first encapsulation layer 161 and the second encapsulation layer 162 is illustrated in an enlarged fashion. As can be seen from figure 19, the top side 161a of the first encapsulation layer, on which the second encapsulation layer 162 is applied, has a surface structure in the form of a roughness brought about, for example, by the application method by which the first encapsulation layer 161 is produced. Furthermore, the volume structure of the first encapsulation layer 161 has structural or lattice defects 163, such as pores or dislocations, for instance, which are indicated merely schematically and purely by way of example. In this case, the structural and lattice defects 163 can extend - as shown - as far as the top side 161a

of the first encapsulation layer 161, that is to say as far as the interface between the first 161 and the second encapsulation layer 162. The second encapsulation layer 162 is embodied in such a way that structural and lattice defects 163 of this type have no influence on the volume structure of the second encapsulation layer 162. The second encapsulation layer 162 is therefore embodied with a uniformly amorphous volume structure and covers the first encapsulation layer 161 over the whole area, as a result of which possible permeation paths for moisture and/or atmospheric gases which are formed by lattice and structural defects 163 of the volume structure of the first encapsulation layer 161 are also sealed. As a result, a hermetic encapsulation of the organic light-emitting diode 1, in particular against moisture and/or oxygen, can be made possible by means of the encapsulation layer sequence 160 and, in particular, by means of the combination of the first 161 and the second encapsulation layer 162.

[000424] In particular the encapsulation techniques described in conjunction with figures 10 to 19 and combinations of these encapsulation techniques are particularly well suited to the formation of a flexible organic light-emitting diode. A flexible organic light-emitting diode 1 is distinguished, inter alia, by the fact that it is pliable to a certain degree, without being damaged in the process. Preferably, the organic light-emitting diode 1 embodied in a flexible fashion is repeatedly pliable without being damaged in the process. The organic light-emitting diode 1 is then suitable, therefore, for withstanding a plurality of bending cycles without being damaged. Particularly preferably, the organic light-emitting diode 1 can be embodied, for example, flexibly such that it can be wound up onto a roll and can be unwound from the roll, without being damaged in the process.

[000425] In particular the encapsulation layer sequence 160 described here enables such a flexible organic light-emitting diode 1. In order to form a flexible organic light-emitting diode 1, the encapsulation of the organic light-emitting diode is also embodied in a flexible fashion. In this case, flexible means, inter alia, that the encapsulation is pliable to a certain degree, without the encapsulation being damaged in the course of bending.

[000426] Furthermore, in the case of a flexible organic light-emitting diode 1, the first 130 and the second carrier 131 are also embodied in a flexible fashion. By way of example, the carriers 130, 131 are a thin glass layer, a laminate or a film. By way of example, the flexible carrier 130, 131 can be a plastic-glass-plastic laminate or a plastic-metal-plastic laminate.

[000427] A further exemplary embodiment of an organic light-emitting diode 1 described here is explained in greater detail in conjunction with figure 20. In this case, the organic light-emitting diode comprises at least a first electrode 101, an organic encapsulation layer sequence 133 and a second electrode 107. A sputtering protective layer 170 is applied between the organic layer sequence 133 and the second electrode 107. The sputtering protective layer 170 is an electrically conductive, inorganic protective layer.

[000428] The organic layer sequence 133 is protected against impairment and/or damage, in particular during the production of the organic light-emitting diode 1, by means of the electrically conductive, inorganic sputtering protective layer 170. Such impairment or damage can occur, for instance, during the production of the organic light-emitting diode 1. Such impairment or damage of the organic layer sequence 133 can then result in a shorter lifetime of the organic light-emitting diode 1 or in a lower luminance of the electromagnetic radiation generated by the organic light-emitting diode 1.

[000429] By way of example, the second electrode 107 is deposited onto the organic layer sequence 133 by means of a high-energy process, such as sputtering. Such a high-energy process can lead, in the absence of the sputtering protective layer 170, to damage to the organic layer sequence 133 as a result of the bombardment of the organic layer sequence 133 with gas ions and/or the material to be applied by sputtering. By means of the high-energy process, by way of example, a second electrode 107 consisting of a TCO material or a metal can be applied to the organic layer sequence 133.

[000430] The sputtering protective layer 170 can comprise for example a transition metal oxide, which can comprise for example tungsten oxide, vanadium oxide, molybdenum oxide, rhenium oxide, nickel oxide or combinations or mixtures thereof or consists of these materials. Furthermore, the sputtering protective layer 170 can also comprise metals, such as magnesium or silver, for instance.

[000431] In the exemplary embodiment in accordance with figure 20, the sputtering protective layer 170 contains or consists of a transition metal oxide, such as WO_3, V_2O_5, MoO_3, Re_2O_7 or NiO. The second electrode 107 is applied above the sputtering protective layer 170. The second electrode 107 is applied directly to the sputtering protective layer 170 for example by means of a high-energy deposition process, such as sputtering.

[000432] The possibilities for encapsulation, sealing and for protection of the organic layer sequence 133 against damage and external influences, as described in conjunction with figures 7 to 20, can be used for all of the organic light-emitting diodes and luminaires described here. In particular, any combination of the organic light-emitting diodes 1 described in conjunction with figures 1 to 6 can be combined by means of one or a combination of the organic light-emitting diodes 1 described in conjunction with figures 7 to 20. In this way, it is possible to produce, for example, organic light-emitting diodes 1 which emit white light, are transparent, emit on both sides and are protected against external influences particularly well by means of diffusion barriers, thin-film encapsulations, encapsulation layer sequences, and/or connecting means. Combinations of the protection methods for organic light-emitting diodes 1, as described in conjunction with figures 7 to 20, can result for example in a organic light-emitting diode 1 which has an organic layer sequence 133 hermetically sealed by means of an encapsulation layer sequence 160, wherein the organic layer sequence 133 encapsulated in this way is arranged between a first carrier 130 and a second carrier 131. In this case, first carrier 130 and second carrier 131 can be connected to one another by means of a connecting means 140, such as a glass solder, for example. The organic light-emitting diode 1 is then distinguished by a

particularly good encapsulation which allows the organic light-emitting diode to be used, for example, in particularly moist rooms, such as a bathroom. Such an organic light-emitting diode 1 can then even be used in the vicinity of or in sanitary installations such as a bath tub or a shower.

[000433] In the case of the exemplary embodiments described in conjunction with figures 1 to 20, the radiation exit areas of the organic light-emitting diode 1 are in each case embodied in flat fashion. Such organic light-emitting diodes 1 generally have a Lambertian emission characteristic. In conjunction with figures 21 to 25, exemplary embodiments of organic light-emitting diodes 1 described here will now be described in greater detail, wherein the organic light-emitting diode 1 has a directional emission profile.

[000434] In conjunction with figure 21, a first exemplary embodiment of an organic light-emitting diode 1 having a directional emission profile as described here is explained in greater detail on the basis of a schematic perspective illustration. The organic light-emitting diode 1 comprises functional layers 180 having, for example, a first electrode 101, a second electrode 107 and an organic layer sequence 133 arranged between first electrode 101 and second electrode 107.

[000435] The organic light-emitting diode 1 furthermore has a second carrier 131. The second carrier 131 comprises a structured radiation exit area 175. The structured radiation exit area 175 has a multiplicity of first areas 175a and second areas 175b. The first areas 175a are inclined by an angle α relative to a plane running, for example, parallel to the main extension plane (xy plane) of the organic layer sequence 133. The second areas 175b are inclined by an angle β relative to said plane.

[000436] The emission of electromagnetic radiation generated in the organic layer sequence 133 is effected through the second carrier 131 and the radiation passage area 175. In this case, the structured radiation exit area 175 can be applied in the form of a separate layer onto the top side of the second carrier 131 facing away from

the organic layer sequence 133. Furthermore, it is possible for the structured radiation exit area 175 to be formed by a structuring of the second carrier 131. Furthermore, it is possible that, instead of the second carrier 131, for example, an encapsulation layer sequence 160 such as is described in greater detail in conjunction with figures 15 to 19 is arranged on the second electrode 107. In this case, for example, the second encapsulation layer 162 can be embodied as a structured radiation exit area. In this case, the second encapsulation layer can be arranged directly on the first encapsulation layer 161. This is indicated by the dashed line in figure 21.

[000437] In the exemplary embodiment in figure 21, the structured radiation exit area 175 is structured into a multiplicity of prisms arranged parallel to one another, wherein the first areas 175a and the second areas 175b form the top area of the organic light-emitting diode 1 facing away from the organic layer sequence 133. For reasons of clarity, in each case only two of the multiplicity of first areas 175a and second areas 175b are illustrated in figure 21.

[000438] Neither the first areas 175a nor the second areas 175b are arranged parallel to the organic layer sequence 133. Consequently, these areas are also not arranged parallel to the plane (xy plane) in which the organic light-emitting diode 1 - that is to say for example the organic layer sequence - is embodied in planar fashion.

[000439] In this case, the extent of the prisms in the y direction is preferably of macroscopic orders of magnitude, that is to say for example in the range of millimeters to decimeters. For example, the extent of the prisms in the y direction can extend over the entire length of the organic light-emitting diode 1. The width of the prisms in the x direction is preferably greater than the wavelength of the light generated by the organic light-emitting diode 1, such that diffraction effects at the prisms hardly or do not take place. The width of the prisms is preferably of microscopic orders of magnitude, for example in the submillimeters range, such that a structuring in the x direction of the radiation exit area 175 is not visible to the human observer. The width b of a prism can be 500 µm or less, preferably 250 µm or

less. The length l of a prism can be 1 cm or more, preferably 5 cm or more.

[000440] The first areas 175a of the structured radiation exit area 175 are embodied as transparent or at least radiation-transmissive, whereas the second areas 176 are reflective to the electromagnetic radiation generated in the organic light-emitting diode. The second areas 175b can be made reflective at a shallow angle of incidence for example by vapor deposition with metal particles.

[000441] In this way, in the exemplary embodiment of figure 21, only the first areas 175a constitute radiation exit areas of the organic light-emitting diode 1. That is to say that electromagnetic radiation can leave the organic light-emitting diode 1 only through the first areas 175a. In this way, the organic light-emitting diode 1 has an emission profile which has a main emission direction inclined relative to the z axis in the direction of the x axis. In this case, the inclination angle of the main emission direction of the organic light-emitting diode 1 is substantially determined by the angle α.

[000442] Electromagnetic radiation which is generated by the organic layer sequence 133 and which is reflected at the second areas 175b can likewise emerge from the light-emitting device through the radiation-transmissive first areas 175a after one or more internal reflections. Alternatively, it is possible for the organic light-emitting diode 1 to be an organic light-emitting diode 1 which emits on both sides and in which the organic layer sequence 133 and also the electrodes 101, 107 are embodied in radiation-transmissive fashion. In this way, reflected radiation can emerge from the organic light-emitting diode 1 for example on the opposite side of the radiation exit area 175 illustrated. In this case, the opposite radiation exit area can also be structured in the manner described, thus resulting in an organic light-emitting diode 1 which emits electromagnetic radiation directionally on both sides.

[000443] The angles α and β at which the first 175a and second areas 175b are arranged influence the angular distribution of the emitted electromagnetic radiation and the frequency of the internal reflections.

[000444] The structured radiation exit area 175 can be, for example, a separate, correspondingly structured film applied to the second carrier 131. Furthermore, it is possible - as already discussed above - for the structured radiation exit area 175 to be structured directly into the second carrier 131 or to be formed by part of an encapsulation layer sequence 160.

[000445] Different emission profiles (angle-dependent distribution of the emitted intensity) of organic light-emitting diodes 1 having a structured radiation exit area 175 are illustrated in conjunction with figure 22. Firstly, the underlying coordinate system is illustrated in figure 22a. The organic light-emitting diode 1 forms, with its lateral organic layer sequence 133 embodied in planar fashion, the xy plane of the coordinate system. In the case of a non-structured radiation exit area 175, a Lambertian emission profile in the direction of the z axis generally arises for the organic light-emitting diode 1. Directional emission profiles can then be achieved by means of the structuring of the radiation exit area 175.

[000446] By way of example, in conjunction with figures 22b and 22c, a type A-1 and type A-2 emission profile, respectively, is shown, which is distinguished by a symmetrical, cardioid radiation direction distribution having two maxima both in the x direction and in the y direction (type A-1) or in one of the two directions (type A-2). Such emission patterns are particularly well suited for example to general lighting in rooms.

[000447] The emission profile shown in figure 22d, called type B, is greatly asymmetrical in at least one of the directions x and y and is particularly well suited for example to directional lighting. By way of example, such an emission profile can be used for desk lighting in which a work area is illuminated in a directional fashion without dazzling the user. Such an emission profile can be achieved with the exemplary embodiment of an organic light-emitting diode 1 described here as described in conjunction with figure 21.

[000448] In conjunction with figure 23, a further exemplary embodiment of an organic light-emitting diode 1 described here is explained in greater detail on the basis of a perspective schematic illustration.

[000449] In this exemplary embodiment, the top side of the first carrier 130 facing the functional layers 180 is structured into parallel prisms having first areas 175a and second areas 175b. The lateral, planar extent of the organic light-emitting diode 1 and thus of the first carrier 130 lies in the xy plane. Relative to this xy plane, the first areas 175a are inclined by the angle α and the second areas 175b by the angle β. The functional layers 180 are applied to the first areas 175a. The second areas 175b are free of functional layers. In this case, the first carrier 130 can be formed for example with a metal, with a glass, with a ceramic material or with a plastic material. In this case, the first carrier can, in particular, also be embodied in flexible fashion and is formed by a film or a laminate.

[000450] An encapsulation and hermetic sealing of the organic light-emitting diode 1 described in conjunction with figure 23 can be effected for example by means of an encapsulation layer sequence 160 or by other encapsulation methods described in conjunction with figures 7 to 19.

[000451] Advantageously and in contrast to the exemplary embodiment illustrated in conjunction with figure 21, the functional layers 180 in the exemplary embodiment in figure 23 can be separately drivable. In this way, the brightness of the light generated by the organic light-emitting diode 1 can be regulated particularly well by more or fewer of the functional layers 180 being energized - depending on the desired brightness. Furthermore, it is possible for the functional layers 180 to differ particularly with regard to the construction of the organic layer sequence 133, such that different functional layers can emit electromagnetic radiation having different wavelengths.

[000452] In conjunction with figure 24, a further exemplary embodiment of an organic light-emitting diode 1 described here is explained in greater detail on the

basis of a schematic perspective illustration. In this exemplary embodiment, the first carrier 130 is structured into a multiplicity of parallel prisms. In contrast to the exemplary embodiment in figure 23, not only the first areas 175a are covered with functional layers 180, but also the second areas 175b are covered with functional layers 180.

[000453] In the case of the exemplary embodiment in figure 24, the structured radiation exit area 175 is structured in the form of prisms having the cross section of an isosceles triangle. The arrangement shown results in a symmetrical emission characteristic of the type A-2, with two main radiation directions which are inclined from the z axis by the angle $\alpha = \beta$ in positive and negative x directions. In the y direction, to a first approximation a Lambertian emission profile arises given a sufficient extent of the organic light-emitting diode 1. If the angles a and β are chosen not to be identical, the two main radiation directions are inclined from the z axis by different angles. At the same time, the intensity with which emission is effected in the main emission direction differs on account of the resultant areas of the functional layers 180 having different magnitudes.

[000454] Further possibilities for the structuring of the first carrier 130 or generally for the structuring of the radiation exit area 175 are described in conjunction with figures 25a, b, c on the basis of schematic sectional illustrations. In the exemplary embodiment described in conjunction with figure 25a, the angles a and β are chosen to have different magnitudes. This results in a distribution of the type A-2 with different intensities in both main emission directions. For an organic light-emitting diode 1 which emits on both sides, for example, the underside of the first carrier 130 can also be correspondingly structured, as is indicated by the dashed line in figure 25a.

[000455] With reference to figures 25b and 25c it is clarified that the structuring of the radiation exit area 175 need not necessarily be effected by the formation of plane areas 175a, 175b arranged at specific angles with respect to one another, rather that a structuring can be effected in any desired way, for example in the manner of

cylinder sections and the like.

[000456] Overall, with reference to figures 21 to 25 it is clarified that an organic light-emitting diode 1 having a directional emission characteristic can be specified by means of the structuring of carriers, encapsulation layers and/or functional layers. In this case, the beam directing can be effected for example by reflection, refraction and/or corresponding orientation of the functional layers 180.

[000457] Corresponding structurings can be used for all of the encapsulation and sealing techniques described in conjunction with figures 7 to 20. Furthermore, it is possible to use all of the radiation-emitting layer sequences described in conjunction with figures 1 to 6 for organic light-emitting diodes 1 having a directional emission characteristic. Any desired combinations of the organic light-emitting diodes 1 described in conjunction with figures 1 to 25 are also possible.

[000458] A further exemplary embodiment of an organic light-emitting diode 1 described here is explained in greater detail in conjunction with the schematic sectional illustrations in figures 26A and 26B. The organic light-emitting diode 1 described in conjunction with figures 26A and 26B is particularly well suited to the illumination of an area 185a to be illuminated of an element 185 to be illuminated.

[000459] The area 185a to be illuminated of the element 185 is, for example, part of an outer area of the element 185 to be illuminated.

[000460] By way of example, the element 185 to be illuminated can be a tile, a poster, a slab, a traffic sign, an information board, a sign, an image or any other element. The element 185 to be illuminated can also be a mirror, for example, which has a reflective mirror area as area 185a to be illuminated.

[000461] The organic light-emitting diode 1 is applied at least indirectly to the element 185 to be illuminated. The organic light-emitting diode 1 can be fixed for example directly on the element 185 to be illuminated. By way of example, the

organic light-emitting diode 1 can be adhesively bonded by means of a transparent adhesive onto the element 185 to be illuminated. Other fixing methods such as hook and loop fasteners, screw connections, clamping connections, press-fit connections or the like are also possible.

[000462] The organic light-emitting diode 1 is a radiation-transmissive, preferably a transparent organic light-emitting diode 1 such as is described here.

[000463] In the exemplary embodiment in figures 26A and 26B, the organic light-emitting diode 1 comprises a first carrier 130 and a second carrier 131. The functional layers 180, that is to say for example the first electrode 101, the second electrode 107 and also the organical layer sequence 133, are arranged between first carrier 130 and second carrier 131. In this case, the organic light-emitting diode 1 can be encapsulated as described here. That is to say that the organic light-emitting diode 1 need not have two carriers 130, 131, rather it can, for example, also be encapsulated by means of a diffusion barrier 153, a thin-film encapsulation 154, a pre-encapsulation layer 156 and/or an encapsulation layer sequence 160. In this case, it is also possible, in particular, for the organic light-emitting diode 1 with the encapsulation layer sequence 160 to be applied, for example adhesively bonded, onto the area 185a to be illuminated of the element 185 to be illuminated. Furthermore, it may be advantageous if the organic light-emitting diode 1 is embodied in flexible fashion. It can then be adapted particularly well to the course of the area 185a to be illuminated.

[000464] Figure 26a shows the organic light-emitting diode 1 in a switched-off operating state. That is to say that no electromagnetic radiation is generated in the radiation-emitting region 104 of the organic light-emitting diode 1. Electromagnetic radiation 190 impinging from outside on the area 185a to be illuminated can penetrate through the transparent organic light-emitting diode 1 and is reflected from the area 185a to be illuminated. In this way, an observer sees only the area 185a to be illuminated, for example an image, a traffic sign, an information board, a mirror or the like.

[000465] Figure 26b illustrates the organic light-emitting diode 1 schematically in a switched-on operating state. In this switched-on operating state, the radiation-emitting region 104 of the organic light-emitting diode 1 emits electromagnetic radiation 191, which impinges on the area 185a to be illuminated and is at least partly reflected there. Furthermore, electromagnetic radiation 193 can also emerge directly from the organic light-emitting diode 1, without impinging beforehand on the area 185a to be illuminated. The relative ratio of the intensities of indirectly emerging electromagnetic radiation 192 and directly emerging electromagnetic radiation 193 can be adjustable and selectable for example by means of an optical cavity or else by means of first electrodes 101 and second electrodes 107 having different degrees of transparency.

[000466] In this case, an "optical cavity" can mean, here and hereinafter, in particular, that the organic light-emitting diode 1 forms an optical resonator in which electromagnetic radiation having one or more specific wavelengths and/or one or more specific emission directions can preferably be generated, which can also be designated as resonances or modes. For this purpose, by way of example, the first electrode 101, the organic layer sequence 133 and the second electrode 107 can be embodied as an optical cavity. That can mean that the at least partly transparent first electrode 101 and the at least partly transparent second electrode 107 additionally also have a reflectivity for the electromagnetic radiation generated in the radiation-emitting region 104. Alternatively or additionally, the first electrode 101, the organic layer sequence 133 and the second electrode 107 can be arranged between partly reflective layers, which additionally are also partly transparent. The following description of the optical cavity is explained purely by way of example for partly reflective electrodes 101, 107.

[000467] The first electrode 101 and/or the second electrode 107 can have a reflectance R and/or R', respectively, and the organical layer sequence 133 can have a refractive index n for the electromagnetic radiation generated in the radiation-emitting region 104. Since the first 101 and second electrode 107 are partly

transparent, R<1 and R'<1 hold true in this case. The refractive index n can be constant over the organic layer sequence 133 or can be constant at least in partial regions, for example in different organic layers. Furthermore, the refractive index n can also vary over the organic layer sequence 133. The radiation-emitting region 104 of the organic layer sequence can have a thickness d and can be arranged in a manner spaced apart with an average distance L from the first electrode 101 and with an average distance L' from the second electrode 107. In this case, the average distance L and the average distance L' designate the distances from the first electrode 101 and from the second electrode 107, respectively, which are averaged over the thickness d of the radiation-emitting region 104. In this case, the parameters R, R', n, d, L and L' can be chosen in such a way that the organic layer sequence has a specific emission characteristic.

[000468] By way of example, the reflectances R and R' of the first and second electrodes and the refractive index n of the organic layer sequence 133 can be predetermined on account of the respective choice of material, such that the desired emission characteristic can be made possible by the choice of the average distances L and L' and the thickness d of the radiation-emitting region 104. As an alternative thereto, the dimensions of the organic layer sequence 133 and of the radiation-emitting region 104, that is to say the average distances L and L' and the thickness d can be predetermined, for example by the construction or the method for production of the organic light-emitting diode 1. In this case, the desired emission characteristic can be made possible by the choice of the material for the first 101 and second electrode 107 by way of the reflectance R and R' thereof.

[000469] By way of example, the average distances L and L' can be of the order of magnitude of the wavelength of the electromagnetic radiation generated in the radiation-emitting region 104, or smaller. If the electromagnetic radiation has a spectral distribution of a plurality of wavelengths and/or wavelength ranges, the electromagnetic radiation can in this case also be characterized by an average wavelength and the dimensions of the organic layer sequence 133, here and hereinafter, can be related to the average wavelength of the electromagnetic

radiation.

[000470] Furthermore, the average distances L, L' can also be less than or equal to half the wavelength of the electromagnetic radiation, or less than or equal to a quarter of the wavelength of the electromagnetic radiation, or even less than or equal to an eighth of the wavelength of the electromagnetic radiation. Furthermore or additionally, the average distances L and L' can be greater than or equal to 1/20 of the wavelength of the electromagnetic radiation or else greater than or equal to 1/10.

[000471] Such average distances L and L' can bring about, in conjunction with the partly reflective first 101 and second electrode 107, the formation of an at least semilaterally reflective cavity in the radiation-emitting layer sequence. In this case, a photon or wave packet emitted by an excited state (exciton) in the radiation-emitting region 104 can be reflected at the first electrode 101 and at the second electrode 107. By virtue of the fact that the average distances L and L' can be of the order of magnitude of the wavelength of the electromagnetic radiation or smaller, when expressed in a simplified way, a feedback of the emitted wave packet with the excited state can still be possible during the emission of the wave packet, such that the excited state, during the emission of the wave packet, can be influenced by the electromagnetic field of its "own" reflected wave packet. Depending on the phase angle of the reflected wave packet, an amplification or attenuation of the emission of the excited state can thus be made possible. In this case, the phase angle can be dependent on the refractive index n of the organic layer sequence 133, the reflectivities R, R' of the first 101 and second electrode 107 in conjunction with the penetration depth of the electromagnetic radiation into the first 101 and second electrode 107, and also on the distances between the excited state and the first 101 and second electrode 107 in conjunction with the emission direction of the wave packet. As a result, a mode structure which can foster and/or bring about an emission of the electromagnetic radiation in specific directions can be formed in the organic layer sequence. Furthermore, the thickness d of the radiation-emitting region 104 can also influence the formation of emission modes.

[000472] The organic light-emitting diode 1 can have an emission characteristic of the electromagnetic radiation generated in the radiation-emitting region 104, such that the electromagnetic radiation is emitted with a first intensity in the direction of the element 185 to be illuminated and is emitted with a second intensity in the direction of the radiation exit area 174. In this case, the first intensity and the second intensity can be defined at outer areas of the organic light-emitting diode 1, that is to say, for example, at surfaces of the first 101 or second electrode 107, of a carrier 130, 133, or of an encapsulation layer sequence 160, which face away from the organic layer sequence 133. "Intensity in the direction" of the element 185 to be illuminated and of the radiation exit area 174 can respectively denote, for the first and second intensities, the respective total intensity into the half-spaces on that side of the organic light-emitting diode 1 which faces and respectively faces away from the element 185 to be illuminated.

[000473] In this case, the electromagnetic radiation having the first intensity, which is emitted from the organic light-emitting diode 1 in the direction of the element 185 to be illuminated, can illuminate the at least partly non-transparent area 185a to be illuminated. By virtue of the fact that the area 185a to be illuminated is at least partly non-transparent, at least part of the electromagnetic radiation having the first intensity can be reflected in the direction of the radiation exit area 174 and be perceptible by an external observer through the radiation exit area 174. In other words, that can mean that, for an external observer, the area 185a to be illuminated of the carrier element can be illuminated and thus perceptible in a switched-on operating state of the organic light-emitting diode 1. This can be the case, in particular, if the first intensity is greater than the second intensity.

[000474] In this case, such an emission characteristic can be made possible, for example, by the optical cavity as described above.

[000475] Alternatively or additionally, the first 101 and second electrode 107 can have mutually different transmissivities. If, for instance, the first electrode 101 is

arranged on that side of the organic layer sequence 133 which faces the element 185 to be illuminated, and has a greater transmissivity than the second electrode 107, it can be possible that the electromagnetic radiation generated in the radiation-emitting region 104 is emitted with a first intensity in the direction of the element 185 to be illuminated, said first intensity being greater than the second intensity.

[000476] As an alternative thereto, the second intensity can be greater than the first intensity. Such an emission characteristic can be made possible, in turn, by means of an optical cavity, for example. Alternatively or additionally, by way of example, the second electrode 107 can be arranged on that side of the organic layer sequence 133 which faces away from the element 185 to be illuminated, and can have a greater transmissivity than the first electrode 101. In this case, it can be possible that the area 185a to be illuminated is perceptible less clearly in comparison with the switched-off operating state of the organic light-emitting diode 1 since an external observer can perceive the reflected electromagnetic radiation having the first intensity and the electromagnetic radiation having the second intensity that is emitted directly via the radiation exit area of the radiation-emitting arrangement, as a superimposition. Furthermore, in the switched-on operating state, the area 185a to be illuminated can be no longer perceptible at all if the electromagnetic radiation having the first intensity that is reflected at the at least partly non-transparent main surface is outshone in the above sense by the electromagnetic radiation having the second intensity.

[000477] Thus, the organic light-emitting diode 1 and the radiation exit area 174 can appear transparent in the switched-off operating state and can appear non-transparent or likewise at least transparent in the switched-on operating state, depending on the ratio of the first intensity to the second intensity.

[000478] The organic light-emitting diode 1 can be embodied such that it is structured for example in such a way that, in the switched-on operating state, the area 185a to be illuminated is perceptible through first regions of the radiation exit area 174 and not through second regions. In this case, the organic light-emitting

diode 1 can, for example, emit electromagnetic radiation only in partial regions or else emit electromagnetic radiation over a large area. As a result of such segmented illumination and/or segmented emission of the electromagnetic radiation in the direction of an external observer, it can be possible that, for example, different illumination patterns can be generated or indications or information can be inserted temporarily. In the switched-off operating state, these patterns, indications and/or information are not visible and do not impair the appearance and the perceptibility of the area to be illuminated.

[000479] On account of the adjustable intensity ratio it is possible, therefore, that an observer perceives directly emitted light 193, for example only from the organic light-emitting diode 1. Furthermore, it is possible that the observer perceives principally the area 185a to be illuminated of the element 185 to be illuminated. This is possible when the electromagnetic radiation 193 emitted directly toward the outside has a lower intensity than the electromagnetic radiation 191 directed onto the area 185a to be illuminated.

[000480] Furthermore, the impression of the area 185a to be illuminated which is perceived by the observer can also be achieved by an alteration of the wavelength of the light generated by the organic light-emitting diode 1 during operation. For a particularly realistic rendering of the area 185a to be illuminated, however, it may be desirable for the organic light-emitting diode 1 to be a organic light-emitting diode 1 which emits white light and which is transparent. One of the organic light-emitting diodes 1 described here can be used for this purpose.

[000481] In conjunction with figure 27, a further exemplary embodiment of an organic light-emitting diode 1 described here is explained in greater detail on the basis of a schematic sectional illustration. In this exemplary embodiment, in contrast to the exemplary embodiment in figures 26a and 26b, the first carrier 130 is replaced by an encapsulation layer sequence 160 such as is described here. The organic light-emitting diode 1 is once again a transparent organic light-emitting diode 1, which preferably emits white light. An electrically switchable optical element

186 is arranged between the organic light-emitting diode 1 and the element 185 to be illuminated. By way of example, said electrically switchable optical element can be an electrically switchable diffuser. Said diffuser can have two functional states: firstly it can be switched to be diffusely scattering, that is to say opaque; secondly the diffuser can be switched to be transparent.

[000482] By way of example, the diffuser can be formed by an electrode pair having planar, transparent electrode layers, between which a liquid crystal layer is arranged. By applying an external voltage, it is possible to influence the transmission of electromagnetic radiation through the diffuser in a targeted manner.

[000483] If the electrically switchable optical element 186 is switched to be diffuse, as is illustrated in figure 27, electromagnetic radiation 192 generated by the organic light-emitting diode 1 is diffusely scattered in the electrically switchable optical element 186. To the observer, therefore, the area to be illuminated can be perceived only in a blurred fashion or is no longer perceptible at all. In this way, it is possible for the arrangement of organic light-emitting diode 1, electrically switchable optical element 186 and element 185 to be illuminated to be used in the sense of a luminaire for general lighting.

[000484] When the electrically switchable optical element 186 is switched to be transparent, the area 185a to be illuminated is visible.

[000485] In the exemplary embodiment in figure 27, it can be expedient when the area 185a to be illuminated and the element 185 to be illuminated are themselves transparent. In this way, the arrangement constitutes a transparent luminaire which can be switched to be diffuse as necessary. Such luminaires can be used, for example, as changing cubicles, room dividers or similar elements. Even in the state switched to be diffuse, electromagnetic radiation can still pass through the switchable optical element 186 and thus through the element 185. In this way, the organic light-emitting diode 1 with the switchable optical element 186 and the element 185 to be illuminated serves as a luminaire which emits on both sides and

which is visually impenetrable.

[000486] Furthermore, it is possible for the electrically switchable optical element 186 to be an electrochromic element which can change its color when an external voltage is applied. In this way, by way of example, the light reflected back from the area 185a to be illuminated can be dimmed - depending on the magnitude of the applied voltage.

[000487] Overall, in the case of the exemplary embodiment in figure 27, it is also possible for the area 185a to be illuminated to be a mirror. In this case, by means of the electrically switchable optical element 186, the mirror can be switched from a reflective operating state to a diffusely scattering and hence illuminating operating state.

[000488] In the case of the exemplary embodiment in figure 27, it is furthermore also possible for the electrically switchable optical element 186 to be structured in such a way that there are regions in which no electrically switchable optical element 186 is arranged between the organic light-emitting diode 1 and the area 185a to be illuminated. In this way, by way of example, patterns or spatially delimited color shadings can be produced by means of the electrically switchable optical element 186.

[000489] A further exemplary embodiment of an organic light-emitting diode 1 is explained in greater detail in conjunction with figure 28. In this exemplary embodiment, a wavelength conversion substance 187 is disposed downstream of the organic layer sequence 133 at least in an emission direction. In this case, it is possible - as illustrated in figure 28 - for the organic light-emitting diode 1 to be a organic light-emitting diode 1 which emits on both sides, wherein a wavelength conversion substance 187 is disposed downstream of the organic light-emitting diode 1 in both main emission directions. For different main emission directions it is possible to use different wavelength conversion substances 187.

[000490] By way of example, blue light is emitted in the radiation-emitting region 104 of the organic light-emitting diode 1. The organic light-emitting diode 1 which emits on both sides can then emit white light in one direction and colored light, for example, in the other direction. In this case, the desired color impression can respectively be set by the choice of a suitable wavelength conversion substance 187. By way of example, the following wavelength conversion substances 187 are appropriate for this purpose: garnets of rare earths and of the alkaline earth metals, for example YAG:Ce^{3+}, furthermore also nitrides, nitridosilicates, sions, sialons, aluminates, oxides, halophosphates, orthosilicates, sulfides, vanadates, perylenes, cumarin and chlorosilicates, or mixtures of these substances.

[000491] In the exemplary embodiment in figure 28, the wavelength conversion substance 187 is introduced into the first carrier 130 and also the second carrier 131. However, the wavelength conversion substance 187 can also be applied into a matrix material as a layer onto an outer area of the first carrier 130 and/or of the second carrier 131. Furthermore, it is possible for the organic light-emitting diode 1 to have no or only one carrier and to be encapsulated differently. On the basis of the exemplary embodiment in figure 28, all that is elucidated in more specific detail is that the electromagnetic radiation emitted by the organic light-emitting diode 1 during operation can also be determined or concomitantly determined by the use of wavelength conversion substances with regard to its color impression.

[000492] Figures 29 and 30 show, on the basis of schematic sectional illustrations, exemplary embodiments of organic light-emitting diodes which in each case have a retroreflector 183.

[000493] A retroreflector is a reflective optical element which, for a large range of angles of incidence, reflects incident ambient light back substantially in the same direction from which it comes. To put it another way, a part of a light beam that is incident on the retroreflector 183 and a part of said light beam that is reflected by the retroreflector run substantially parallel. In this case, the angle of incidence is the angle between the incident part of the light beam and the normal to the surface of a

main extension plane of the retroreflector 183.

[000494] In particular, the incident and reflected parts form an angle of less than or equal to 15°, preferably of less than or equal to 10°, particularly preferably of less than or equal to 5°. An upper limit for the angle of incidence is, for example, greater than or equal to 45°, preferably greater than or equal to 60°, particularly preferably greater than or equal to 75°.

[000495] In this case, the retroreflector 183 preferably exhibits slight scattering. To put it another way, the incident part of the light beam is reflected back into a narrow, divergent beam cone. The beam cone has a central axis that runs substantially parallel to the incident part of the light beam, that is to say forms therewith for example an angle of less than or equal to 15°, preferably of less than or equal to 10°, and particularly preferably of less than or equal to 5°. The beam cone can have an aperture angle of 5° or less.

[000496] The retroreflection by the retroreflector 183 into a narrow, divergent beam cone is advantageous if the light beam incident from an external light source - such as a headlight of a vehicle - is not intended to be reflected back directly into the external light source, but rather is intended to be perceived for example by an observer in the vicinity of the external light source - for instance by the vehicle driver.

[000497] In the exemplary embodiment in accordance with figure 29, the electrodes 101, 107 and also the organic layer sequence 133 are embodied as at least radiation-transmissive, preferably transparent. In this case, the functional layers 180 are applied to a first carrier 130, which can be formed for example by a transparent film or with a glass. At all events, the first carrier 130 is preferably embodied in transparent fashion. Purely by way of example, the organic light-emitting diode 1 in the exemplary embodiment in figure 29 is encapsulated with an encapsulation layer sequence 160 composed of first encapsulation layer 161 and second encapsulation layer 162, as described here. Alternatively, all other encapsulation methods and combinations of these encapsulation methods as described here are also possible

for forming the organic light-emitting diode 1.

[000498] The organic light-emitting diode 1 can be, in particular, a organic light-emitting diode 1 that is transparent, emits white light and is embodied in flexible fashion. The organic light-emitting diode 1 is applied to the retroreflector 183 at its outer area facing away from the organic layer sequence 133, that is to say with the first carrier 130.

[000499] In the present case, the retroreflector 183 is formed from a reflective plate 182, into which radiation shaping elements 182 are introduced. By way of example, the radiation shaping elements 182 are pyramidal depressions. In this case, the radiation shaping elements 182 can constitute so-called triple mirrors. To put it another way, each radiation shaping element 182 preferably has exactly three side areas. In this case, the side areas can each form an angle of approximately 90°, for example an angle of between 85° and 95°, with one another, inclusive of the limits.

[000500] The radiation shaping elements 182 can be impressed into the reflective plate 181. Preferably, the reflective plate 181 consists of a reflective metal for this purpose.

[000501] In contrast to the exemplary embodiment in figure 29, in the exemplary embodiment in figure 30 the retroreflector is formed by a part of the first carrier 130. By way of example, the first carrier 130 is embodied as a transparent plastic film or as a glass substrate. The radiation shaping elements 182 are situated as depressions on that side of the first carrier 130 which faces away from the organic layer sequence 133. The radiation shaping elements are coated from said side preferably with a reflective layer, for example a metal layer applied by vapor deposition.

[000502] Furthermore, a color filter 184 is disposed downstream of the organic layer sequence 133, which color filter can be formed for example by color filter particles introduced into the first encapsulation layer 161. Furthermore, it is possible

for a color filter 184 as a separate component to be disposed downstream of the organic layer sequence 133 or to be applied as a separate layer onto the encapsulation layer sequence 160.

[000503] The color filter 184 has a high transmission for a first spectral subrange of the visible wavelength spectrum and high absorption for a second spectral subrange of the visible wavelength spectrum. An intensity maximum of the electromagnetic radiation generated by the radiation-emitting region 104 during operation lies within the first spectral subrange transmitted by the color filter 184. As an alternative to a color filter, it is also possible for the retroreflector 183 itself to contain a wavelength-selective mirror layer for reflecting the ambient light, which layer reflects the first subrange and absorbs and/or transmits the second subrange.

[000504] Advantageously, that portion of the ambient light which is reflected back by the retroreflector 183 to the radiation exit area 174 and is coupled out from the organic light-emitting diode 1 produces in this way substantially the same color impression as the light emitted by the organic light-emitting diode 1. Advantageously, therefore, the organic light-emitting diode 1 brings about the same color impression independently of the operating state.

[000505] For embodiments in which only the color impression is of importance, the retroreflector 183 can in this case also be replaced by any other layer embodied in reflective fashion, or some other element embodied in reflective fashion, which need not have retroreflective properties.

[000506] In conjunction with figures 31A and 31B, an exemplary embodiment of an organic light-emitting diode 1 described here is explained in greater detail on the basis of schematic sectional illustrations, the organic light-emitting diode comprising a touch sensor in this exemplary embodiment. By way of example, functions of the organic light-emitting diode 1 or of other devices can be controlled by means of the touch sensor.

[000507] In the exemplary embodiment in figures 31A and 31B, the organic light-emitting diode comprises a first carrier 130, a functional layer sequence 180 arranged onto the first carrier, and also a second carrier 131. In this case, the encapsulation of the organic light-emitting diode can be effected as described here. With that side of the first carrier 130 which faces away from the functional layers 180, the organic light-emitting diode 1 is applied to an element 185 to be illuminated, said element comprising an area 185a to be illuminated.

[000508] Figure 31B illustrates the fact that pictorial representations of operating elements 197a, 197b, 197c are applied to the area 185a to be illuminated. During the operation of the organic light-emitting diode, said operating elements can be illuminated by electromagnetic radiation generated in the radiation-emitting region 104.

[000509] A third electrode 195 is arranged at that side of the second carrier 131 which faces away from the functional layers 180. The third electrode 195 is succeeded by a covering plate 196. The covering plate can be, for example, a transparent film, sheet or layer. The covering plate 196 can serve as anti-scratch protection. Furthermore, it is possible for the covering plate 196 to increase the light coupling-out of electromagnetic radiation generated in the organic light-emitting diode 1.

[000510] The third electrode 195 is electrically conductively connected to a current source 198, which can be operated with DC current or in a pulsed manner. Field lines 198a are thereby generated by the organic light-emitting diode 1. By way of example, a finger or a pen that touches the covering plate 196 alters the profile of the electric field lines 198a. With the aid of an evaluation circuit 199, it is possible to determine the position of the finger, for example, and in this way to effect the assignment to the operation of one of the operating elements 197a, 197b, 197c.

[000511] In this case, it is also possible for some other touch sensor to be used instead of the above-described capacitively operating touch sensor integrated into an

organic light-emitting diode described here.

[000512] Such touch sensors are for example also described in the documents DE 10332956 A1 and DE 10308514 A2, the disclosure content of which is hereby incorporated by reference.

[000513] Furthermore, it is also possible for the operating elements 197a, 197b, 197c not to be represented by images on an area 185a to be illuminated, but rather for the organic light-emitting diode 1 to be constructed at least in places in the manner of a simple organic display suitable for representing simple images or pictograms.

[000514] Luminaires 2 are explained in greater detail below. The luminaires 2 can be luminaires 2 for general lighting such as lamps or lights which have further functions - besides their use for general lighting. Thus, the luminaires 2 can form a concealing screen, noise protection, protection against rain or a splash guard, solar protection or the like. In the luminaires 2 described below, in each case at least one organic light-emitting diode 1 as described in conjunction with figures 1 to 31 can be used as light source. Furthermore, combinations of the organic light-emitting diodes 1 described in conjunction with figures 1 to 31 can also be used as light source.

[000515] The luminaire 2 described in conjunction with figures 32A to 32G has a wake-up function besides its function for general lighting. That is to say that the luminaire 2 forms a light - for example for room lighting, and an alarm clock. By means of the wake-up function, a user of the luminaire 2 can be woken up at a time of day that can be set, by means of the brightness of the luminaire being increased.

[000516] Figure 32A shows an exemplary embodiment of such a luminaire 2 on the basis of a schematic perspective illustration. In this case, the luminaire 2 is fixed in the manner of a picture on a wall 204. In this case, figure 32A shows the luminaire 2 in a switched-off operating state.

[000517] The luminaire 2 comprises, for example, an organic light-emitting diode 1 as explained in greater detail in conjunction with figures 26 and 27. That is to say that the organic light-emitting diode 1 of the luminaire 2 can be transparent and disposed downstream in an area 185a to be illuminated. The area 185a to be illuminated of the organic light-emitting diode 1 is, for example, a picture, a poster, wallpaper, tiles or the like. Furthermore, the area 185a to be illuminated can be the reflective surface of a mirror.

[000518] As can be seen from figure 32A, in the switched-off state of the luminaire 2, the area 185a to be illuminated is visible through the transparent layers of the organic light-emitting diode 1.

[000519] Figure 32B shows the luminaire 2 in a switched-on operating state. In this operating state, the area 185a to be illuminated is no longer discernible. This can be achieved, for example, by utilizing an optical cavity, as described in conjunction with figures 26A and 26B. Furthermore, this can be achieved by means of an electrically switchable optical element 186, as described for example in conjunction with figure 27. The luminaire 2 therefore has at least two operating states: in a first operating state, the area 185a to be illuminated is discernible; in a second operating state, the luminaire 2 serves only for general lighting.

[000520] An exemplary embodiment of the luminaire 2 is explained in greater detail with reference to the basic schematic diagram in figure 32C. In this case, the luminaire 2 comprises the organic light-emitting diode 1 and also a driving device 201. An activation time for the luminaire 2 can be set by means of the driving device 201. Said activation time can be a desired wake-up time t1, for example.

[000521] It is possible in this case for the driving device 201 to regulate only two operating states of the organic light-emitting diode 1. Thus, by means of the driving device 201, the organic light-emitting diode 1 can be switched from the switched-off operating state into the switched-on operating state with maximum light intensity Imax at the desired wake-up time t1.

[000522] In another embodiment of the luminaire 2, as explained with reference to the graphical plot in figure 32D, however, a slow, continuous increase in the light intensity I up to the maximum light intensity Imax takes place at the wake-up time t1.

[000523] In this case, it can be seen from the graphical plot in figure 32D that the light intensity generated by the organic light-emitting diode 1 assumes a finite value as a result of the organic light-emitting diode 1 being switched on at the wake-up time t1 and rises slowly from there. Such a rise can take place, for example, by means of a correspondingly slow increase in the current intensity with which the organic light-emitting diode 1 is operated. Furthermore, it is possible for the light intensity I to be increased by means of pulse width modulation. A combination of these two possibilities can also prove to be advantageous.

[000524] An alternative possibility for slowly increasing the light intensity I is described in greater detail with reference to the graphical illustration in figure 32E. Here, starting from the wake-up time t1, the light intensity I is increased in steps, the light intensity in each case being kept constant for certain time intervals t2.

[000525] Overall, the temporal profiles of the light intensity as described in conjunction with figures 32D and 32E enable the user of the luminaire to be woken up particularly gently. The light intensity increases from a light intensity I=0 up to a light intensity Imax over a time period of 5 minutes, for example.

[000526] In this case, the light intensity Imax is preferably at least 1000 cd, particularly preferably at least 5000 cd. In the extreme case it is possible for the light intensity Imax to be 10 000 cd.

[000527] Such high light intensities are possible in particular with the phosphorescent emitter materials described in conjunction with figures 1 to 6. On account of their high efficiency, these materials allow particularly bright light to be generated. A possible temporal delay of the radiation emission by said

phosphorescent emitter materials is not of importance in the case of the luminaire 2 in accordance with the exemplary embodiments in figures 32D and 32E, since the light intensity I is intended to be increased relatively slowly.

[000528] By way of example, the luminaire 2 can comprise an organic light-emitting diode 1 as described in conjunction with figure 3. The organic light-emitting diode 1 then preferably emits white light.

[000529] An exemplary embodiment of a luminaire which can be controlled and/or regulated in different ways by the user is described in conjunction with figure 32F. Firstly, the luminaire 2 can comprise operating elements 197 for example in the region of a corner of the luminaire. The operating elements 197 can be operated by the user by means of a touch sensor, for example, as described in conjunction with figures 31A and 31B. That is to say that the luminaire 2 comprises, for example, an organic light-emitting diode 1 with a capacitively operating touch sensor.

[000530] Alternatively or additionally, it is possible for the luminaire 2 to be operated by means of a remote control 202.

[000531] By means of the operating elements 197, the operating state of the luminaire can be set, for example. Thus, the desired wake-up time can be predetermined by means of the operating elements 197 and/or the remote control 202. Furthermore, the operating state of the luminaire can be selected by means of the operating elements 197 and/or the remote control 202. By way of example, the luminaire 2 can thereby be switched from the switched-off operating state, in which the area 185a to be illuminated is visible, to a luminous operating state, in which the luminaire 2 serves for room lighting.

[000532] A further exemplary embodiment of a luminaire described here is explained in greater detail in conjunction with the schematic illustration in figure 32G. In this exemplary embodiment, the organic light-emitting diode 1 of the luminaire 2 is subdivided into a multiplicity of segments 203. The segments 203 are individually

drivable functional layers 180, which can differ from one another, for example by virtue of different emitter materials. Furthermore, the segments can be individual organic light-emitting diodes 1. Such a luminaire 2 makes it possible to realize, alongside or as an alternative to a temporal profile of the light intensity I, also a temporal profile of the color locus and/or of the color temperature T.

[000533] By way of example, firstly warm-white, reddish light having a color temperature T of approximately 4000 K can be generated at the wake-up time t1, wherein, for example, segments 203 that generate a reddish white light are principally operated.

[000534] In the temporal profile, it is then possible for the color temperature to rise up to a maximum color temperature Tmax of approximately 25 000 K. At this color temperature, cold, bluish, white light is generated by the organic light-emitting diode 1 of the luminaire 2.

[000535] In this way, therefore, the luminaire 2 is designed to generate white light having color temperatures T of at least 4000 K to at most 25 000 K, wherein the light intensity I can simultaneously rise from 0 cd to 10 000 cd. In the temporal profile, therefore, a sunrise in time lapse is simulated by the luminaire 2. In this way, the luminaire 2 enables the user of the luminaire to be woken up particularly naturally and gently.

[000536] In figures 32H and 32I, two possibilities for temporally varying the color temperature T are illustrated graphically on the basis of graphical plots. In this case, the color temperature T can be increased from T0 approximately 4000 K to Tmax approximately 25 000 K continuously (see figure 32H) or in steps (see figure 32I). The increase in the light intensity I as described in conjunction with figures 32D and 32E can simultaneously be effected.

[000537] Overall, exemplary embodiments of a luminaire which also comprises a wake-up function besides its function for general lighting are described in conjunction

with figures 32A to 32E. The organic light-emitting diode 1 of the luminaire 2 can be embodied in transparent and flexible fashion. The luminaire can be suitable for generating white light having different color temperatures and can be provided for generating light having different color temperatures and light intensities. Behind the organic light-emitting diode 1 of the luminaire 2, an area 185a to be illuminated can be arranged, which can be exchanged by the user. In this way, the luminaire 2 can be combined with any desired posters, wall tiles, pictures, mirrors or the like, which allows particularly diverse use of the luminaire. In this case, the luminaire 2 contains at least one organic light-emitting diode 1 as described in greater detail in conjunction with figures 1 to 31, or an organic light-emitting diode 1 that constitutes a combination of the organic light-emitting diodes 1 described in conjunction with figures 1 to 31.

[000538] A further exemplary embodiment of a luminaire 2 described here is explained in greater detail in conjunction with the schematic illustrations in figures 33A to 33D.

[000539] Figure 33A shows, on the basis of a schematic perspective illustration, a further exemplary embodiment of a luminaire 2 described here. In this case, the luminaire 2 forms large-area room lighting that can be utilized as part of a shower cubicle 215. That is to say that the luminaire 2 performs a double function: firstly it serves as a light for general lighting, and secondly it constitutes a splash guard.

[000540] In this case, the luminaire 2 is emissive on both sides, such that electromagnetic radiation 190 from the luminaire 2 can be directed into the interior of the shower cubicle 215. Furthermore, electromagnetic radiation 191 is emitted in opposite directions from the shower cubicle into the room to be illuminated.

[000541] An exemplary embodiment of a luminaire 2 which can be utilized as part - for example as a boundary wall - of a shower cubicle 215 is explained in greater detail in conjunction with the schematic sectional illustration in figure 33B. The luminaire 2 comprises at least one organic light-emitting diode 1 as explained in

greater detail in conjunction with or in the combination of figures 1 to 32.

[000542] In this case, the organic light-emitting diode 1 comprises a first carrier 130 and also a second carrier 131, which are arranged parallel or substantially parallel to one another. First carrier 130 and second carrier 131 are preferably each formed from a radiation-transmissive material. In this case, first carrier 130 and second carrier 131 are not necessarily transparent; it is sufficient if one of the carriers, or both carriers, is or are embodied as diffusely radiation-transmissive, for example. In this case, the functional layers 180 of the organic light-emitting diode need not necessarily be embodied in transparent fashion; it is sufficient if the functional layers 180 are emissive on both sides.

[000543] A first and/or second carrier 130, 131 embodied in diffuse fashion has the advantage in this case that the luminaire 2 also functions as a concealing screen of the shower cubicle besides its properties for lighting and for a splash guard. First carrier 130 and second carrier 131 can, for example, be formed with an opalescent glass or consist of an opalescent glass. Furthermore, it is possible for at least one of the two carriers to have a surface structuring or a patterning which - in addition to light scattering - can also serve for the artistic decoration of the outer area of the luminaire 2 and/or for beam directing of the electromagnetic radiation 190, 191.

[000544] First carrier 130 and second carrier 131 can be embodied as planar plates. Furthermore, it is possible for the carriers - as illustrated in figures 33A and 33B - to be bent in the manner of a cylinder lateral surface segment and for the luminaire 2 thus to have curved radiation exit areas 174.

[000545] The functional layers 180 of the organic light-emitting diode 1 can be encapsulated, in the cavity formed by the first carrier 130 and the second carrier 131, by means of the carriers 130, 131 and a connecting means 140 arranged marginally. Furthermore, other techniques for encapsulating and sealing the functional layers 180, as described for example in conjunction with figures 7 to 20, are also possible. Furthermore, combinations of said sealing and encapsulation techniques are also

possible.

[000546] In this case, the use of an organic light-emitting diode in a bathroom makes stringent requirements of the hermetic sealing of the organic light-emitting diode 1. The organic light-emitting diode 1 has to withstand a room climate having high air humidity and relatively high temperatures for long times.

[000547] Figure 33C, for example, shows a schematic sectional illustration of an exemplary embodiment of the luminaire 2 in which such a good hermetic sealing can be achieved particularly efficiently. In this case, the sealing by means of the first carrier 130 and the second carrier 131 and also the connecting means 140 is combined with an encapsulation of the functional layers 180 by an encapsulation layer sequence 160. That is to say that the organic light-emitting diode 1 has a double encapsulation in this case: first, it is protected by the carriers 130, 131 and the connecting means 140, and secondly by the particularly impermeable encapsulation layer sequence 160. This enables particularly efficient encapsulation of the luminaire and therefore use in a bathroom in conjunction with long lifetimes of the luminaire 2.

[000548] The connecting means 140 can be, for example, a glass solder or a glass frit material, which is led in a frame-like manner around the functional layers 180 and also the encapsulation layer sequence 160.

[000549] Furthermore, one of the further encapsulation techniques described in conjunction with figures 7 to 20, such as, for example, a diffusion barrier or a thin-film encapsulation, can be used for encapsulation purposes.

[000550] In conjunction with figure 33D, a further exemplary embodiment of the luminaire 2, in which the organic light-emitting diode 1 is well protected at least against splash water from the shower, is explained on the basis of a schematic sectional illustration. In this exemplary embodiment, the organic light-emitting diode 1 is applied to the outer area of a radiation-transmissive plate 205 that faces away

from the shower.

[000551] The organic light-emitting diode 1 can then be, for example, a flexibly embodied organic light-emitting diode 1 which emits on both sides. Such a organic light-emitting diode 1 can have a flexible film as carrier. Furthermore, it is possible for the organic light-emitting diode 1 to be applied to the outer area of the radiation-transmissive plate 205 in the sense of a transfer.

[000552] Overall, applying the organic light-emitting diode 1 to an outer area of the radiation-transmissive plate 205 enables the organic light-emitting diode 1 to be rapidly removed and thus rapidly exchanged. Therefore, the demands with regard to encapsulation that have to be placed on such a light-emitting diode 1 are not as stringent as in the case of luminaires in accordance with figures 33B and 33C, for example. That is to say that in the exemplary embodiment in figure 33D, the lifetime of the organic light-emitting diode 1 does not limit the lifetime of the shower cubicle, rather the organic light-emitting diode 1 can be replaced by a new organic light-emitting diode 1 after it has been damaged.

[000553] In the exemplary embodiments in figures 33B to 33D, the organic light-emitting diode 1 of the luminaire 2 is illustrated as a large-area organic light-emitting diode 1. However, the organic light-emitting diode 1 can also be divided into a multiplicity of segments 203, which can be suitable, for example, for generating electromagnetic radiation having differing wavelengths. Furthermore, it is possible for the luminaire 2 to comprise a multiplicity of organic light-emitting diodes 1 which, for example, can each have a common first carrier 130. In order to form the organic layer sequence 133 and also the electrodes 101 and 107 of the organic light-emitting diode 1, it is possible to use, for example, the materials described in conjunction with figures 1 to 6 and the layer constructions described in conjunction with said figures. Overall, therefore, the organic light-emitting diode 1 can be - depending on the embodiment - a organic light-emitting diode 1 that is transparent, emits on both sides, emits white light, and/or is flexible.

[000554] A further exemplary embodiment of a luminaire 2 described here is explained in greater detail in conjunction with the schematic illustrations in figures 34A to 34C. In this exemplary embodiment, too, the luminaire 2 constitutes large-area room lighting and also part, for example the wall, of a shower cubicle 215.

[000555] To supplement, for example, the exemplary embodiment described in conjunction with figure 33C, the luminaire 2 has, in addition to the at least one organic light-emitting diode 1, at least one second light source, which is embodied as a light-emitting diode 210 in the present case (in this respect, cf. figure 34B, for example). The light-emitting diodes 210 are arranged for example at the top area and/or the bottom area of the second carrier 131. However, they can also be applied on the top and/or bottom area of a radiation-transmissive plate 205, as described in conjunction with figure 33D. Generally, at least one inorganic light-emitting diode 210 can be arranged at a side area of a radiation-transmissive carrier or a radiation-transmissive plate, wherein the carrier or the plate can serve as a large-area optical waveguide for electromagnetic radiation generated by the light-emitting diode.

[000556] As explained in conjunction with the schematic sectional illustration in figure 34C, the second carrier 131 forms for example an optical waveguide for electromagnetic radiation 192 generated by the light-emitting diodes 210. In this case, a reflective layer or coating 211, which is transmissive to electromagnetic radiation 190 generated in the organic layer sequence 133, is preferably applied to the inner side of the second carrier 131 facing the organic layer sequence 133. By contrast, the reflective layer 211 is embodied such that it is reflective for electromagnetic radiation 192 generated by the light-emitting diodes 210. In this case, the reflective layer 211 and/or the second carrier 131 can have structurings that allow the electromagnetic radiation 192 to be distributed as uniformly as possible over the entire area of the second carrier 131. The second carrier 131 therefore serves as a planar optical waveguide that permits the electromagnetic radiation generated by the inorganic light-emitting diodes 210 to be emitted homogeneously into the interior of the shower.

[000557] The light-emitting diodes 210 are preferably inorganic light-emitting diodes suitable for generating UV radiation, infrared radiation and/or visible light. In this case, it is possible for the luminaire to comprise light-emitting diodes 210 for generating infrared radiation and also UV radiation and/or visible light.

[000558] The luminaire 2 can comprise, for example, an operating mode in which infrared radiation 192 is generated by the light-emitting diodes 210. Said infrared radiation is conducted by the second carrier 131 and the reflective layer 211 into the interior of the shower cubicle, where it is used firstly for warming a user; secondly, the radiation can be used for faster drying of the shower cubicle after the shower cubicle has been used.

[000559] In a further operating state, only the light-emitting diodes 210 of the luminaire 2 which emit UV light are activated. In this operating state, the emitted radiation 192 is used for tanning a user and/or for disinfecting the shower after the end of the use thereof.

[000560] In a third operating state, light-emitting diodes 210 that emit infrared light and UV light can be operated simultaneously, as a result of which combinations of the functions mentioned are possible. Furthermore, it is also possible for the luminaire 2 to comprise organic light-emitting diodes 1 that are suitable for generating infrared radiation. Suitable emitter materials are described for example in conjunction with figures 1 to 6.

[000561] Furthermore, it is possible for the luminaire to generate, at least during the operation of the shower, white light with which, depending on the water temperature, red light components (for hot water) or blue light components (for cold water) are admixed for example by means of corresponding inorganic light-emitting diodes 210 or organic light-emitting diodes 1.

[000562] Finally, exemplary embodiments are possible in which, during the operation of the luminaire 2, color profiles of the emitted light are generated or a

desired color temperature can be set. This can be realized for example by means of corresponding organic light-emitting diodes 1 and/or inorganic light-emitting diodes 210.

[000563] Overall, the luminaire 2 described in conjunction with figures 33 and 34 realizes particularly variable, large-area room lighting that simultaneously serves as a splash guard in a shower. In this case, the light color, the light temperature and also the light intensity can be adjustable according to the user's wishes. Furthermore, the luminaire 2 can serve as an indicator device for the water temperature, as a result of which, by way of example, it is possible to prevent use of the shower at excessively cold or excessively hot water temperatures.

[000564] Furthermore, it is possible for the light functions such as color, color temperature and/or color intensity to be changed temporally, as explained in greater detail for example in conjunction with the luminaire in accordance with figures 32A to 32I.

[000565] In conjunction with figure 35 an explanation is given, with reference to a basic schematic diagram, of the fact that the luminaire 2 can be operated by means of operating elements 197 that are addressed by means of a touch sensor. For this purpose, it is possible to use a touch sensor as explained in greater detail for example in conjunction with figures 31A and 31B. In this case, the operating element can be accessible both from the inner side of the shower and from the outer side of the shower.

[000566] Furthermore, it is possible for not only the light function of the luminaire 2 but, for example, also the mixing faucet of the shower and hence the water temperature and the water strength to be regulated by means of the operating element 197.

[000567] On the other hand, it is also possible, however, for, for example, the color of the emitted light of the luminaire 2 to be regulated by means of the mixing faucet

during the operation of the shower. That is to say that, by way of example, the color of the light emitted by the luminaire 2 can be adapted by means of the setting of the water temperature.

[000568] A further exemplary embodiment of a luminaire 2 described here is explained here in greater detail in conjunction with the perspectively schematic illustration in figure 36. In this exemplary embodiment, the luminaire 2 is accorded a double function:

[000569] Firstly, the luminaire 2 serves for general lighting. By way of example, it can constitute the main light in a bathroom.

[000570] Secondly, the luminaire 2 comprises a shower head for a shower.

[000571] That is to say that firstly the luminaire 2 emits electromagnetic radiation 190, 191, and secondly the luminaire 2 distributes water via the shower head 220. In this case, the luminaire 2 can be suitable for emitting electromagnetic radiation 190, 191 having different electromagnetic wavelengths simultaneously or successively. For this purpose, the luminaire 2 can comprise, for example, a plurality of organic light-emitting diodes 1 suitable for generating electromagnetic radiation having mutually different wavelengths. The luminaire 2 can then emit light of different colors for example simultaneously or sequentially. Furthermore, the luminaire can be suitable for emitting white light. For this purpose, the luminaire can comprise one or a plurality of organic light-emitting diodes 1 which each emit white light during operation. Furthermore, it is possible for the luminaire 2 only to emit light of a single color. For this purpose, the luminaire can comprise one or a plurality of organic light-emitting diodes 1 which each emit colored light, for example green or red light, during operation.

[000572] An exemplary embodiment of a luminaire 2 comprising a shower head 220 is described in greater detail in conjunction with the schematic plan view in figure 37A and also the schematic sectional illustration in figure 37B.

[000573] The luminaire 2 comprises the shower head 220. The shower head 220 can be embodied for example as circular, square or in some other shape in the plan view. The shower head 220 can be, on the one hand, the shower head of a handheld shower unit, said shower head having a diameter D of at least 5 cm and at most 20 cm. Furthermore, it is possible for the shower head 220 to be a large-area shower head having, for example, a diameter D of at least 50 cm, preferably at least 80 cm, particularly preferably at least 100 cm. Such a shower head 220 is then preferably fitted directly to the ceiling of a bathroom, for example. Water 222 from such a shower head 220 falls like rain from a relatively large height and in a manner distributed over a relatively large area onto the user of the luminaire 2.

[000574] In this exemplary embodiment, the shower head 220 comprises at least one organic light-emitting diode 1 suitable, for example, for emitting white light 190. For this purpose, the organic light-emitting diode 1 can have a layer construction as described in greater detail in conjunction with figures 1 to 6. Furthermore, the organic light-emitting diode has an encapsulation as explained in greater detail in conjunction with figures 7 to 20. Combinations of the layer sequences described in the figures and of the encapsulations described in the figures are also possible.

[000575] By way of example, the organic light-emitting diode 1 has a double or triple seal. Thus, the organic light-emitting diode 1 can be sealed by means of a first carrier 130, a second carrier 131 and also a connecting means 140. Furthermore, the organic light-emitting diode 1 can comprise an encapsulation layer sequence 160. Overall, a particularly good encapsulation is preferably chosen for the organic light-emitting diode 1 since the organic light-emitting diode 1 is in direct contact with water 222 at least in places. That is to say that, for example, at least one of the carriers 130, 131 is wetted with water 222 during the operation of the shower head 220 of the luminaire 2.

[000576] The luminaire 2 comprises the shower head 220, which has a passage opening 224, by which said shower head is connected to the water supply. Water

222 passes into the shower head 220 via the passage opening 224. The water 222 flows around the organic light-emitting diode 1 at the outer areas thereof and in this way passes to the cover plate 223 of the shower head. The cover plate 223 has openings 221 through which the water 220 can pass from the shower head.

[000577] In this exemplary embodiment, the cover plate 223 is in this case embodied as radiation-transmissive, for example transparent. Electromagnetic radiation 190 from the organic light-emitting diode 1 can leave the cover plate both through the openings 221 and through the other, non-water-pervious regions of the cover plate 223.

[000578] Overall, the organic light-emitting diode 1 is integrated into the shower head 220 in the exemplary embodiment in figures 37A and 37B.

[000579] In conjunction with figure 38, a further exemplary embodiment of a luminaire 2 with shower head 220 as described here is explained in greater detail with reference to a schematic sectional illustration. In this exemplary embodiment, in contrast to the exemplary embodiment in figures 37A and 37B, the organic light-emitting diode 1 is divided into segments 203. In this case, light having mutually different colors is emitted in the segments 203 during the operation of the organic light-emitting diode 1.

[000580] The segments 203 are jointly encapsulated for example by a common carrier pair 130, 131 and a connecting means 140 arranged marginally and in frame-like fashion. The segments 203 can furthermore be sealed jointly, or each segment can be sealed by itself, by means of an encapsulation layer sequence 160. The segments 203 can be individually drivable, such that light of different colors can be generated simultaneously or sequentially. Alongside the described segmentation of the organic light-emitting diode 1, however, it is also possible for the luminaire 2 to comprise a plurality of organic light-emitting diodes 1 suitable for generating light of mutually different colors.

[000581] As a further, optional difference with respect to the exemplary embodiment explained in greater detail in conjunction with figures 37A and 37B, the cover plate 223 of the shower head 220 can in this case be embodied as non-radiation-transmissive. That is to say that electromagnetic radiation 190, 191 can then leave the shower head 220 only together with the water 222 through the openings 221. In this case, the water jets 222 that leave the shower head 220 can serve as a kind of optical waveguide for the electromagnetic radiation 190, 191 generated in the segments 203 of the organic light-emitting diode 1.

[000582] That is to say that, during operation, the shower head 220 can emit differently colored water jets 220 at different locations. The non-radiation-transmissive embodiment of the cover plate 223 can result in a particularly good separation of the different light colors. By way of example, with the shower head 220 it is possible in this way to produce a shower of water which is similar in appearance to a rainbow when viewed from a distance.

[000583] In conjunction with figure 39A, a further exemplary embodiment of a luminaire 2 described here is explained in greater detail with reference to a schematic sectional illustration. Figure 39B shows a schematic plan view of the luminaire 2 from that side of the shower head 220 which faces away from the openings 221.

[000584] In this exemplary embodiment, the organic light-emitting diode 1 is provided with the passage opening 224, which is arranged for example at a central location through the organic light-emitting diode 1. That is to say that the organic light-emitting diode has a hole through which water is flushed during the operation of the shower head 220 of the luminaire 2.

[000585] At the edges 224a of the passage opening 224, the organic light-emitting diode 1 can be sealed for example by means of a glass solder or a glass frit as connecting means 140. Furthermore, the connecting means 140 can be provided with an encapsulation layer sequence 160, which additionally seals the connecting

means. Such a construction is explained in greater detail by way of example in conjunction with figures 14B and 18.

[000586] The functional layers 180 of the organic light-emitting diode 1 can additionally once again be sealed by an encapsulation layer sequence 160, a diffusion barrier 153, a thin-film encapsulation 154, a resist layer 150 or further measures.

[000587] Water 222 passes through the passage opening 224 into a gap arranged between the cover plate 223 of the shower head 220 and the organic light-emitting diode 1. The cover plate 223 once again comprises openings 221 through which the water 220 can pass. In this case, the cover plate 223 can be embodied as radiation-transmissive, then transparent for example, or non-radiation-transmissive. The organic light-emitting diode 1 can emit white light, colored light or light of different colors - as explained for example in conjunction with figure 38.

[000588] In comparison with the exemplary embodiment in figures 37 and 38, in the exemplary embodiment of figure 39, only the underside - facing the cover plate 223 - of the organic light-emitting diode 1 and also the side areas of the organic light-emitting diode 1 in the region of the edge 224 of the passage opening are directly exposed to the water 222. On the other hand, in order to encapsulate the organic light-emitting diode 1, special carriers 130, 131 having a passage opening 224 have to be provided. This can make it more expensive to produce the luminaire 2 as explained in conjunction with figures 39A and 39B.

[000589] In conjunction with figures 40A and 40B, the driving of the luminaire 2 is explained in greater detail with reference to schematic illustrations.

[000590] Figure 40A schematically shows a mixing faucet which can be used to set the water temperature TW by means of a rotary movement of the faucet 22a. In this case, it is possible for the color, that is to say the color locus O and/or the color temperature T, of the light emitted by the organic light-emitting diode 1

simultaneously to be set by way of the water temperature TW. Furthermore, it is possible for the setting of the color locus O and/or of the color temperature T to be effected by means of a translational movement of the mixing faucet. Overall, the mixing faucet 225 described in conjunction with figure 40A is therefore used in exemplary embodiments of the luminaire 2 in which the color locus and the color temperature of the light generated by the organic light-emitting diode 1 can also be set by means of the mixing faucet of the shower.

[000591] Furthermore, it is also possible for the shower head 1 to be driven by means of touch-sensitive operating elements 197 as explained in greater detail for example in conjunction with figure 35. Said operating elements can be integrated as touch-sensitive organic light-emitting diodes, for example, into a wall tile, a tile or into a shower cubicle. In particular, the luminaire 2 with shower head 220 can also be combined with the luminaire 2 embodied as part of a shower cubicle 215. That is to say that the exemplary embodiments described in conjunction with figures 33 to 35 can be combined with a luminaire 2 in accordance with the exemplary embodiments in figures 36 to 40 in one and the same shower.

[000592] Figure 40B shows, on the basis of a schematic illustration, a further possibility for driving the luminaire 2 as explained in greater detail in conjunction with figures 36 to 39. By way of example in a manner supplementing a mixing faucet 225, for driving purposes it is possible to use the regulating device 226, by means of which a specific shower program can be preset. By way of example, a temporal profile of the water temperature and also of the light emitted by the luminaire 2 can be preset by means of the shower program.

[000593] In this case, a luminaire 2 with shower head 220 and at the same time a luminaire 2 with a shower cubicle 215 can be driven. In this case, water temperature, pressure of the water jet, color temperature and/or color locus can be changed in a manner coordinated with one another by the regulating device 226 in temporal succession. By way of example, in this case a simulated sunrise as described in conjunction with figures 32H and 32I, can be simulated by the

luminaire 2, wherein at the same time for example the water temperature is increased or decreased continuously or in steps.

[000594] A further exemplary embodiment of a luminaire 2 described here is explained in greater detail in conjunction with the schematic illustrations in figures 41A to 41D. In this exemplary embodiment, the luminaire 2 comprises the functions of a mirror, a light for general lighting and also a display device for simple graphical elements.

[000595] In this case, figure 41A shows a first operating state of the luminaire 2. In this operating state, the luminaire 2 is not actively radiation-generating. The luminaire 2 appears like a normal mirror that reflects back electromagnetic radiation 191 impinging on it. Such a luminaire 2 can be used for example as a bathroom mirror or wardrobe mirror.

[000596] A second operating state of the luminaire 2 is illustrated graphically in conjunction with figure 41B. In this operating state, the luminaire 2 serves as a light for general lighting. In this operating state, the luminaire 2 principally emits electromagnetic radiation 190 that is generated for example by an organic light-emitting diode 1 of the luminaire 2 during the operation of the luminaire. The luminaire 2 does not serve as a mirror in this operating state. That is to say that electromagnetic radiation 191 impinging on the luminaire 2 externally is in this case outshone by the generated electromagnetic radiation 190.

[000597] A third operating state of the luminaire 2 is illustrated schematically in conjunction with figure 41C. In this operating state, patterns 230 are represented by the luminaire 2. Furthermore, the luminaire 2 can reflect impinging electromagnetic radiation 191 and/or actively emit electromagnetic radiation 190. The fact of whether the luminaire 2 has recognizable reflective properties, that is to say whether electromagnetic radiation 191 that impinges on the luminaire 2 is reflected by the latter in a manner perceptible to the user, is dependent on the light intensity with which electromagnetic radiation 190 is actively generated by the luminaire 2. The

light intensity of the electromagnetic radiation 190 that is actively generated by the luminaire 2 can be set for example by means of the current intensity with which the luminaire 2 is energized.

[000598] In conjunction with figure 41D, an exemplary embodiment of a luminaire 2 which has the operating states described in conjunction with figures 41A to 41C is explained in greater detail with reference to a schematic sectional illustration. In this case, the construction of the luminaire 2 is similar to the construction of the organic light-emitting diode 1 explained in greater detail in conjunction with figure 27.

[000599] In this case, the luminaire 2 comprises a transparent organic light-emitting diode 1. The transparent organic light-emitting diode 1 can comprise functional layers 180 arranged between a first carrier 130 and a second carrier 131. Preferably, the organic light-emitting diode 1 comprises a radiation-emitting region 104 suitable for generating white light. The organic light-emitting diode 1 emits electromagnetic radiation 190 from its two main areas.

[000600] Any exemplary embodiment and also any combination of exemplary embodiments described in conjunction with figures 1 to 6 can be used for forming the organic layer sequence 133. Preferably, embodiments as described in conjunction with figures 7 to 20 or combinations of said embodiments are used for encapsulating and hermetically sealing the organic light-emitting diode 1. All that is important in the exemplary embodiment of the luminaire 2 in figure 41D is that the organic light-emitting diode 1 is embodied in transparent fashion.

[000601] The luminaire 2 furthermore comprises an area 185a to be illuminated of an element 185 to be illuminated. The element 185 to be illuminated is a mirror, and the area 185a to be illuminated constitutes the reflective surface of the mirror.

[000602] An electrically switchable optical element 186 is arranged in a structured manner between the organic light-emitting diode 1, that is to say between the first carrier 130 and the illuminating surface 185a. In the present case, the electrically

switchable optical element 186 forms the pattern 230 to be represented. However, it is also possible for the electrically switchable optical element 186 to be a negative image of the pattern 230 to be represented. A transparent material 188 formed from a transparent plastic or glass, for example, is arranged at locations where no electrically switchable optical element 186 is situated between element 185 to be illuminated and first carrier 130. That is to say that the space between the organic light-emitting diode 1 and the area 185a to be illuminated is filled with the transparent material I88 and the electrically switchable optical element 186.

[000603] The electrically switchable optical element 186, then, has two operating states, for example: in a first operating state, the electrically switchable optical element 186 is transparent. In this operating state, the luminaire 2 can, as shown in figure 41A, be operated as a mirror or, as illustrated in figure 41B, be operated as a light, no pattern 230 being discernible.

[000604] On the other hand, the electrically switchable optical element 186 has at least one second operating state in which, for electromagnetic radiation 190 generated by the luminaire, said electrically switchable optical element is either absorbent, attenuating or acts as a color filter. In this way, in this operating state, a pattern 230 can be generated by illumination of the structured, electrically switchable optical element 186.

[000605] Depending on the embodiment of the electrically switchable optical element 186, the pattern can appear dark - for example black - or colored. The electrically switchable optical element 186 is an electrochromic element, for example, such as is also used in electrically tintable glass panes.

[000606] As already described in conjunction with figures 26 and 27, the proportion of the electromagnetic radiation 190 which passes directly from the luminaire toward the outside without in the process previously reaching the area 185a to be illuminated can be set by means of an optical cavity. In this way, the manufacturer of the luminaire 2 can preset the contrast with which the pattern 230 is intended to

appear in the third operating state.

[000607] In conjunction with figures 42A to 42C, an explanation is given, on the basis of schematic illustrations, of the fact that the luminaire 2 can be operated with a touch-sensitive operating element 197. By way of example, by means of translational movements of the hand on a region of the second carrier 131 of the organic light-emitting diode 1, it is possible to change the operating state or to increase or decrease the brightness of the emitted light (see figures 42A and 42C).

[000608] By means of tapping, as illustrated schematically in figure 42B, on the operating element 197, it is possible, for example, for the luminous function to be switched off and on, that is to say for switching between the first and second operating states to be effected. Overall, a touch-sensitive organic light-emitting diode 1 as explained in greater detail in conjunction with figure 31 can again be used for forming the operating element 197.

[000609] As an alternative to a touch-sensitive control of the luminaire 2, however, it is also possible for gesture control of the luminaire 2 to be effected. In this case, the user of the luminaire 2 does not have to touch the radiation exit area 174 of the luminaire. Rather, a camera is fixed to or in the vicinity of the luminaire 2. By means of an evaluation circuit, a specific command - for example a change of operating state - can be calculated from images recorded by the camera. This construction - which is more complicated in comparison with touch control - affords the advantage that the radiation exit area 174 is not smeared, for example by fingerprints of the user.

[000610] A further exemplary embodiment of a luminaire described here is explained in greater detail in conjunction with the schematic illustrations in figures 43 and 44. In this exemplary embodiment, the luminaire 2 is part of a tile 235.

[000611] As illustrated schematically in conjunction with figure 43, the luminaire 2 can be used both as a wall tile and as a floor tile.

[000612] An exemplary embodiment of such a luminaire is schematically explained in greater detail in conjunction with figures 44A and 44B. The luminaire comprises an organic light-emitting diode 1, which is preferably embodied in non-slip fashion. For this purpose, the first carrier 130 and the second carrier 131 of the organic light-emitting diode 1 can be formed from a shatter-resistant glass. Spacers 238 are arranged at regular distance between the carriers 130, 131, which spacers can, for example, likewise be formed from a glass material. Thus, the spacers 238 can be, for example, posts or dams which are formed with a glass solder or a glass frit material. In this case, the spacers 238 prevent the second carrier 131 from being pressed onto the functional layers 180 of the organic light-emitting diode 1.

[000613] The organic light-emitting diode 1 is preferably embodied as a transparent organic light-emitting diode. The organic light-emitting diode can be provided, for example, as described in conjunction with figures 26 and 27, for illuminating the tile 235. In this case, the connection conductors 236 for making electrical contact with the organic light-emitting diode 1 are arranged at the edge side of the organic light-emitting diode 1, where joints of the tiles 235 extend. In this way, the connection conductors 236 do not disturb the visual impression of the tiles.

[000614] As is illustrated schematically in figures 44A and 44B, adjacent luminaires 2 can be electrically connected to one another via electrical connectors 237 and in this way be connected in series or in parallel with one another, for example. However, it is also possible for each of the luminaires 2 to be individually drivable. Electrical connecting conductors for driving the luminaires 2 extend below the tiles 235, for example.

[000615] Besides or in addition to the generation of white light or colored light, the organic light-emitting diode 1 of the luminaire 2 can also be designed for generating infrared radiation. By way of example, an organic light-emitting diode 1 as explained in greater detail in conjunction with figures 1 to 6 can be used for this purpose. A luminaire 2 comprising such an organic light-emitting diode 1 generates heat during

the operation of the organic light-emitting diode 1, and can thus be used as an alternative to a wall or floor heating system.

[000616] In a simple embodiment of the luminaire 2 described in conjunction with figures 43 and 44, the organic light-emitting diode 1 can be a transparent organic light-emitting diode 1 that is adhesively bonded in a simple manner onto a wall, ceiling or floor tile that has already been laid. Such an organic light-emitting diode 1 can be embodied in flexible fashion, for example, and can be fixable on a tile 235 in the manner of a transfer. By way of example, the functional layers are sealed with an encapsulation layer sequence 160 as described further above. The organic light-emitting diode 1 can then be adhesively bonded onto the tile 235 in particular at the outer area of the encapsulation layer sequence 160. In this way, the luminaire can be used in a simple and cost-effective manner for tiles that have already been laid.

[000617] Besides energization of the luminaire 2 via connection conductors 236, inductive or capacitive driving of the luminaire 2 is also conceivable, for example. In this case, the connection conductors 236 can be dispensed with; the energization can be effected by means of a transmitter of electromagnetic radiation, for example. What can disadvantageously arise in this case is that the luminous intensity of the luminaire 2 is reduced by comparison with a luminaire 2 energized by means of electrical connection conductors 236.

[000618] Figure 45A shows an exemplary embodiment of a luminaire 2 described here on the basis of a schematic perspective illustration. The luminaire 2 is a large-area, segmented luminaire 2.

[000619] The luminaire 2 is fixed to the ceiling of a room in the manner of a ceiling light by means of holding devices 239. The holding devices 239 are, for example, power cables, metal wires or rods containing an electrically conductive material. The holding devices 239 are used to effect - besides mechanical fixing of the luminaire 2 - also electrical contact-connection and thus energization of the luminaire 2.

[000620] As is evident in particular from the schematic illustration in figure 45B, the luminaire 2 comprises a multiplicity of organic light-emitting diodes 1. That is to say that the luminaire 2 is segmented into a multiplicity of organic light-emitting diodes 1. The organic light-emitting diodes 1 can be embodied in flexible or rigid fashion, for example.

[000621] Different organic light-emitting diodes 1 of the luminaire 2 can be provided for generating light of different colors. In this way, the luminaire 2 is suitable for emitting light of different colors and/or different color temperatures during operation. The light emitted by the luminaire 2 can thus be flexibly adapted to the requirements of its use. By way of example, the luminaire 2 can generate light similar to daylight, which is particularly well suited to work. Furthermore, it is possible for reddish light to be generated by means of the same luminaire 2 at another time, said reddish light being particularly well suited as evening lighting, for example.

[000622] The organic light-emitting diodes 1 are preferably embodied as described in conjunction with figures 1 to 31, or constitute combinations of the organic light-emitting diodes 1 described there.

[000623] Besides the organic light-emitting diodes 1, the luminaire 2 comprises connection conductors 236. The connection conductors 236 extend, for example, in the manner of a wire-netting fence, such that they delimit - for example rectangular-sections, in each of which an organic light-emitting diode 1 can be arranged. The connection conductors 236 serve for making electrical contact with the organic light-emitting diodes 1 and also for mechanically connecting the individual organic light-emitting diodes 1. In this way, the organic light-emitting diodes 1 can be arranged in a combined series and parallel circuit.

[000624] Furthermore, it is possible for each of the organic light-emitting diodes 1, or groups of the organic light-emitting diodes 1 which are provided for generating the same light color, to be drivable separately by means of the connection conductors 236. In this case, the connection conductors 236 are embodied for example as cable

assemblies having a multiplicity of individual power lines.

[000625] Besides their property for energizing the organic light-emitting diodes 1, the connection conductors 236 form a framework or a matrix for mechanically fixing the organic light-emitting diodes 1. For this purpose, the connection conductors 236 preferably have a certain rigidity corresponding, for example, to the rigidity of a copper wire. The organic light-emitting diodes 1 themselves can be embodied in flexible fashion, and do not have to serve for mechanically stabilizing the luminaire 2. If the connection conductors 236 are embodied as metal wires, then it is furthermore possible that a desired form of the luminaire 2, for example the wavy form illustrated in figure 45A, can be set in a simple manner by the user or by the manufacturer of the luminaire 2 by means of flexure of the connection conductors 236.

[000626] The luminaire 2 described in conjunction with figures 45 and 46 is preferably a relatively large-area luminaire. That is to say that the luminaire 2 can have sizes in the range of a plurality of square meters. By way of example the luminaire 2 has a luminous area of at least 0.5 m^2, preferably at least 1 m^2. The luminous area is in this case formed by the sum of the radiation exit areas 174 of the individual organic light-emitting diodes 1. In this case, each individual organic light-emitting diode 1 preferably has an area content of its radiation exit area 174 of at least 0.5 dm^2.

[000627] In conjunction with the schematic illustration in figure 45C it is shown that an insulator 240 is arranged at crossover points of the connection conductors 236, said insulator electrically insulating the connection conductors 236 from one another. By way of example, the connection conductors 236 extending from left to right in figure 45B are at negative electrical potential. The connection conductors 236 extending from the bottom to the top in figure 45B are then at positive potential. An insulator 240 at least in the region of the crossover points of the connection conductors 236 prevents the connection conductors 236 from being short-circuited.

[000628] Two alternative possibilities for driving the luminaire 2 are briefly

explained in conjunction with the schematic illustrations in figures 46A and 46B. Thus, the luminaire 2 can be driven for example by means of an operating element 197 arranged at a wall (cf. figure 46A). Alternatively or additionally, it is possible for the luminaire 2 to be operated by means of a remote control 202 (cf. figure 46B). Furthermore, it is possible for the luminaire 2 to be drivable by means of a touch sensor or gesture control.

[000629] An exemplary embodiment of a luminaire 2 described here which serves for covering an object is explained in greater detail in conjunction with the schematic illustrations in figures 47 to 49. By way of example, the luminaire 2 serves for covering the radiator 245.

[000630] A radiator 245 generally has a non-smooth surface, for example a surface having heating lamellae, in which dust can settle particularly easily. The dust-sensitive regions of the radiator 245 can be clad with the luminaire 2 that can be used for covering the radiator. Furthermore, the luminaire 2 enhances the visual impression of the radiator 245. The visible exterior area of the radiator 245 is replaced by the luminaire 2, which can serve as a light for the general lighting of the room in which the radiator is arranged.

[000631] The mounting of the luminaire 2 on the radiator 245 in accordance with an exemplary embodiment of the luminaire 2 that can serve for covering is explained in further detail in conjunction with figures 47A and 47B. Figure 47C shows, on the basis of a schematic view, a rear wall 246 of the luminaire 2, said rear wall facing the radiator 245 when the luminaire 2 is in the mounted state. The rear wall 246 is pervaded by a plurality of cooling channels 247, for example, which can extend along the entire width of the rear wall 246.

[000632] As is evident from the schematic plan view of the top side of the radiator 245 with luminaire 2 in figure 47D, the cooling channels 247 are embodied as indentations in the rear wall 246 of the luminaire 2. That is to say the thickness of the rear wall 246 is reduced in the region of the cooling channels 247.

[000633] If the radiator 245 is operated, then, along the cooling channels 247 convection of air takes place, which upon flowing through the cooling channels 247 cools the rear wall 246 of the luminaire 1. In this way, the organic light-emitting diode 1 is also cooled during operation, such that no permissible heating of the organic light-emitting diode 1 can arise. In addition, the rear wall 246 and the organic light-emitting diode 1 of the luminaire 2 can be thermally insulated from one another by a thermal insulation layer (not illustrated). The thermal insulation layer can be formed for example with a material having poor thermal conductivity, such as styropor.

[000634] Alongside the cooling channels 247, fixing means 248 are provided at the rear wall 246. The fixing means 248 are, in a simple exemplary embodiment, adhesive strips by means of which the luminaire 2 can be fixed to the radiator 245.

[000635] However, it is also possible for the fixing means 248 to be magnets, such that the luminaire 2 adheres to the radiator 245 by means of magnetic forces. Other types of fixtures such as screwing or clamping, for example, are also possible.

[000636] Furthermore, a temperature sensor 249 is arranged at the rear wall 246 of the luminaire 2. The temperature of the radiator 245 is measured by means of the temperature sensor 249. Depending on the measured temperature, it is possible to set, for example, the light intensity and/or the light locus and/or the light temperature of the light emitted by the luminaire 2, that is to say by the organic light-emitting diode 1. That means that there is a correlation between the temperature of the radiator 245 and the electromagnetic radiation 190 emitted by the luminaire 2 through the radiation exit area 174 of the organic light-emitting diode 1. In this way, therefore, the luminaire 2 also serves as a temperature indicator for the heat generated by the radiator 245 during operation.

[000637] Further exemplary embodiments of the luminaire 2 that serves for cladding a heating system are explained in greater detail in conjunction with the schematic perspective illustration in figure 48. In these cases, the luminaire 2 is

arranged in front of a radiator 245 for example by means of a stand 251 or a screw connection 252, such that said radiator is covered by the respective luminaire 2. In these cases, there is not necessarily a connection composed of condensed matter between the radiator and the luminaire 2. Therefore, the luminaire 2 can be arranged at a distance from the radiator 245, wherein the gap between radiator 245 and luminaire 2 is filled with air. In such a case, by way of example, the cooling channels 249 described in conjunction with figures 47A to 47D can be dispensed with since sufficient cooling by means of convection takes place via the gap.

[000638] In conjunction with figures 49A and 49B, a further exemplary embodiment of a luminaire 2 which is used for covering a radiator 245 is described in greater detail with reference to schematic sectional illustrations. In this exemplary embodiment, by way of example, a temperature sensor 249 can be dispensed with. Instead, a regulation of the heat 250 emitted by the radiator 245 is effected simultaneously with a regulation of the electromagnetic radiation 190 emitted by the luminaire 2. That is to say that, with an increase in the temperature generated by the radiator 245, for example the color temperature T of the light 190 emitted by the luminaire 2 is decreased or increased. Such a regulation can be effected by means of a remote control 202, by means of touch-sensitive operating elements 197 and/or by means of the valve control of the radiator 245.

[000639] Overall, any combination of the organic light-emitting diodes 1 described here can be used for the luminaire described in conjunction with figures 47 to 49. In this case, it is also possible, for example, for the rear wall 245 to have an area 185a to be illuminated which is illuminated by the organic light-emitting diode 1 of the luminaire, as described in greater detail for example in conjunction with figures 26 and 27. By way of example, the area 185a to be illuminated is the pictorial reproduction of an open fire. By means of the organic light-emitting diode 1 of the luminaire 2, the area 185a to be illuminated can then be illuminated in flickering fashion in the manner of a candle. In this way, the impression of a blazing fire arises in the region of the radiator 245. Such flickering can be effected, for example, by operation of the organic light-emitting diode 1 of the luminaire 2 with temporally

varying current intensities. This can be achieved in a simple manner by means of a pulse width modulation circuit.

[000640] It is also possible for the luminaire 2 to comprise segmented organic light-emitting diodes 1 or a multiplicity of organic light-emitting diodes 1 which can be suitable for generating light of mutually different colors.

[000641] Besides a covering for a radiator 245, the luminaire 2 can, for example, also be used for covering an air-conditioning system or a ventilation shaft in a low-energy house. In this case, particularly if a temperature sensor 249 is present, the luminaire 2 is particularly well suited to covering and cladding elements which are intended to be used for cooling and/or for heating a room. In this case, the luminaire 2 serves as an esthetically appealing temperature indicator which brightens the room.

[000642] A further exemplary embodiment of a luminaire 2 described here is explained in greater detail in conjunction with figures 50A to 50D.

[000643] Figure 50A shows the luminaire 2 in a schematic perspective illustration. The luminaire 2 is a light having a large-area radiation exit area 174, which can be used for example as a desk lamp for illuminating a work area.

[000644] The luminaire 2 comprises as light source preferably at least one organic light-emitting diode 1 as described in greater detail in conjunction with figures 1 to 31.

[000645] The luminaire 2 has a radiation exit area 174, which can comprise an area of 0.1 m^2 or more. By way of example, the radiation exit area 174 has a rectangular basic shape having a length l of at least 50 cm and a height h of at least 20 cm.

[000646] In this case, the luminaire 2 can be embodied such that it emits on both sides, and so, during operation, it can illuminate, for example, two workstations

arranged opposite each other. In this case, the luminaire 2 can also comprise a transparent organic light-emitting diode 1 and, in this way, itself be embodied in transparent fashion.

[000647] Furthermore, it is possible for the luminaire 2 to have an area 185a to be illuminated which is arranged on the opposite side of the luminaire 2 to the radiation passage area 174. In this way, in the switched-off state, the luminaire 2 can represent for example an image, a calendar or a company logo.

[000648] In conjunction with figure 50B it is schematically illustrated that the luminaire 2 can emit electromagnetic radiation 190 in a directional manner. For this purpose, the luminaire 2 comprises for example at least one organic light-emitting diode 1 embodied for example as described in conjunction with figures 21 to 25. That is to say that the organic light-emitting diode 1 comprises a structured radiation exit area 175, which is structured into areas 175a and 175b, in such a way that electromagnetic radiation 190 is emitted downward, for example toward a desk surface. Advantageously, therefore, no electromagnetic radiation 190 is emitted upward, for example away from a desk surface, into the face of the user of the luminaire 2. The luminaire 2 is therefore a dazzle-free luminaire which can be used particularly well for desk work.

[000649] Furthermore, it proves to be advantageous that the luminaire 2 is embodied with a particularly large area. In this way, a relatively low luminance at the radiation exit area 174 is sufficient for sufficient illumination of the work area. That is to say that, in the luminaire 2, a high luminance does not have to be concentrated on a relatively small radiation exit area, as is the case, for example, in a conventional desk lamp with an incandescent bulb or halogen lamp. Rather, the emitted light can be distributed over a large area and the luminance can therefore be reduced. This results in a luminaire 2 which is particularly dazzle-free and yields light similar to daylight - at least in the region of the work area.

[000650] An example for the operation of the luminaire 2 is explained in greater

detail in conjunction with figure 50C. By way of example, in this case it is possible to integrate a touch-sensitive organic light-emitting diode 1 with a touch-sensitive operating element 197 in the luminaire. By moving over part of the radiation exit area 174 of the luminaire 2, it is then possible for the luminaire 2 to be switched on or dimmed.

[000651] In conjunction with figure 50D it is shown that the luminaire 2, on account of its relatively large length l of at least 50 cm, for example, can also serve for guiding electrical cables. In this case, a cable shaft 255 is integrated into the luminaire 2, which cable shaft can be embodied integrally for example with a stand 251 of the luminaire 2.

[000652] In this case, besides its properties for general lighting, the luminaire 2 also serves as an ordering system.

[000653] Further exemplary embodiments of a luminaire 2 described here are explained in greater detail in conjunction with figures 51 to 53. In this case, the luminaire 2 serves for general lighting and as a room divider.

[000654] The luminaire 2 as shown in conjunction with the schematic illustrations in figures 51A and 51B is a large-area light. The luminaire has a radiation exit area 174 of preferably at least 0.5 m^2, particularly preferably of at least 1 m^2. The radiation exit area 174 of the luminaire is arranged between two stands 251, which can also serve for making electrical contact with the luminaire 2.

[000655] The luminaire 2 comprises at least one organic light-emitting diode 1; preferably, the luminaire 2 comprises a multiplicity of organic light-emitting diodes 1 which are connected in parallel and/or in series with one another, for example. The at least one organic light-emitting diode can then be embodied as described in conjunction with figures 1 to 31.

[000656] The luminaire 2 can comprise a touch-sensitive organic light-emitting

diode 1 with an operating element 197. By means of the operating element 197, the luminaire 2 can be switched on or off and/or dimmed, for example. Furthermore, it is possible that the selection of a color temperature T or of a color locus O for the electromagnetic radiation emitted by the luminaire 2 can be effected by means of the operating element 197.

[000657] The luminaire 2 can be a luminaire which emits on both sides and which is embodied such that it scatters light diffusely. That is to say that, in this case, the luminaire 2 is not embodied in transparent fashion, but rather merely in radiation-transmissive fashion in the manner of an opalescent glass pane, for example. In this way, besides its properties for general lighting, the luminaire 2 also serves as a room divider affording a concealing screen. Furthermore, it is possible for the luminaire 2 to emit electromagnetic radiation 190 only from one side and to appear like a customary room divider from the other side.

[000658] By means of the luminaire 2 it is possible, on account of the large radiation exit area 174, to generate dazzle-free light since relatively low luminances are necessary in order to illuminate a room by means of the luminaire 2.

[000659] In conjunction with figures 52A to 52C it is illustrated that the luminaire 2, embodied as a room divider, can have a radiation exit area 174 of variable size. This can be achieved, for example, by virtue of the fact that the luminaire 2 has a radiation passage area 174 that can be rolled up and unrolled.

[000660] For this purpose, by way of example, as illustrated in conjunction with figure 52B, the luminaire 2 is subdivided into individual lamellae, which can each be formed by rigid organic light-emitting diodes 1. The lamellae, that is to say the individual organic light-emitting diodes 1, are mechanically and electrically connected to one another by connection conductors 236. The connection conductors 236 themselves are embodied in flexible fashion, for example in the sense of a power cable that can be unrolled and rolled up. In this case, the luminaire 2 comprises a multiplicity of organic light-emitting diodes 1 arranged in a series one after another.

[000661] Furthermore, it is possible for the luminaire 2, as illustrated in conjunction with figure 52C, to have a radiation exit area 174 that is not subdivided into individual lamellae. By way of example, the luminaire 2 comprises for this purpose exactly one, large-area organic light-emitting diode 1. Furthermore, it is possible for the luminaire 2 to comprise a multiplicity of organic light-emitting diodes 1 arranged in the manner of a matrix. The organic light-emitting diodes 1 can be flexible organic light-emitting diodes that are introduced between two films. In this way, a large-area luminaire 2 that can be rolled up and unrolled can be constructed from a multiplicity of smaller, flexible organic light-emitting diodes 1.

[000662] In conjunction with figure 53 it is illustrated that the luminaire 2, which forms a room divider, can also involve sound protection. In this case, the luminaire 2 has a rear wall 246 formed with at least one insulating material 256 suitable for acoustic insulation. In a simple case, the rear wall 246 can be a styropor panel. As light source of the luminaire 2, at least one organic light-emitting diode 1 is then connected to the insulating material 256 forming the rear wall 246.

[000663] An exemplary embodiment of a luminaire described here in which the luminaire is embodied as a louver is explained in greater detail in conjunction with figures 54A to 54C. In this case, the luminaire 2 comprises a multiplicity of organic light-emitting diodes 1 which are electrically contact-connected and mechanically held by means of a holding device 239. At one end face, the organic light-emitting diodes 1 comprise a connection plug 257, which engages into the holding device 239. The luminaire 2 can be electrically connected by means of connection conductors 236, for example. The holding device 239 is a rail, for example, in which the individual organic light-emitting diodes 1 are fixed by means of the connection plug. The organic light-emitting diodes 1 can be displaced in the rail.

[000664] In this case, the organic light-emitting diodes 1 can be embodied in flexible or rigid fashion. By way of example, the organic light-emitting diodes 1 have, as first carrier 130, a metal sheet having reflective properties. In this way, that side of

each organic light-emitting diode 1 which faces away from the radiation exit area 174 is embodied in reflective fashion. In this case, besides its properties for room lighting, the luminaire 2 also serves for room darkening and/or as a concealing screen.

[000665] The luminaire 2 can comprise different organic light-emitting diodes 1, such that light of different colors or having different color effects can be generated by means of the luminaire 2. The luminaire 2 is arranged in front of a window for example in the sense of a curtain or louver, and in this way generates, even under poor outside light conditions, daylight-like illumination of the room in which the luminaire 2 is arranged. That is to say that the main light of the room is situated for example in the region of the window in which the luminaire 2 is arranged. In this way, when the luminaire 2 is switched on, illumination of the room similar to that through the window takes place. In this case, the luminaire 2 can form the main light source of a room, such that it is possible to dispense with further light sources in the room.

[000666] In this case, the organic light-emitting diodes 1 used as light sources of the luminaire 2 are preferably embodied as described in one of figures 1 to 31 or as a combination of the organic light-emitting diodes 1 described there.

[000667] A further exemplary embodiment of a luminaire 2 described here is explained in greater detail in conjunction with figures 55A to 55D. In this exemplary embodiment, the luminaire, besides its function for general lighting, also serves as a concealing screen. The luminaire 2 has, for example, at least three radiation exit areas 174 embodied as walls.

[000668] The schematic perspective illustration in figure 55A shows the luminaire 2 in a switched-off operating state. In this switched-off operating state, the luminaire 2 is transparent. For this purpose, the luminaire 2 comprises, for example, at least one organic light-emitting diode 1 as light source which is embodied in transparent fashion.

[000669] In conjunction with the basic perspective schematic diagram in figure 55B,

the luminaire 2 is shown in a switched-on operating state. In this switched-on operating state, the luminaire 2 emits electromagnetic radiation 190. In this case, it is possible for the electromagnetic radiation to be emitted both outward, into the room, and inward, into the cubicle enclosed by the walls of the luminaire 2. In this case, the luminaire 2 serves both for lighting the interior of the cubicle and as an indicator device for indicating that the cubicle is occupied by a user.

[000670] Furthermore, in the switched-on operating state, the luminaire 2 no longer appears transparent, but rather is visually impenetrable. This is achieved, for example, by virtue of the fact that the luminaire 2 comprises an electrically switchable optical element 186 as described in greater detail in conjunction with figure 27. The electrically switchable optical element 186 is then an electrically switchable diffuser or an electrochromic material. The switching of the luminaire 2 into the switched-on, luminous and visually impenetrable operating state, as illustrated in greater detail in figure 55B, can in this case be effected for example by the cubicle being entered.

[000671] By way of example, a switch can be actuated by means of the actuation of doors at the luminaire 2. Furthermore, it is possible for the luminaire 2 to comprise a light barrier 260, as is explained in greater detail for example in conjunction with figures 55C and 55D. In the event of said light barrier being crossed, said light barrier comprising a plurality of light-emitting diodes 210, laser diodes and/or optical sensors, for example, the luminaire 2 is switched on.

[000672] In this case, the luminaire described can be used for example as a changing cubicle. In this case, it is also possible that the color temperature T and/or color locus O of the light generated by the luminaire 2 can be set by the user of the luminaire 2. In this way, the clothing being tried on by the user can be checked by the user under different lighting conditions. The user can thereby check for example the effect of the clothing in daylight, office lighting, twilight and the like.

[000673] Furthermore, the luminaire described can be used as a separating wall in

an open-plan office. The light emitted by the luminaire then serves as an office light and signals that the workstation at which the luminaire 2 is situated is occupied. Switching between transparent and diffuse can also be effected independently of the light emission by the luminaire, such that the user of the luminaire can switch the latter to be non-radiation-transmissive, in diffusely scattering fashion, as necessary, in order to create a more private working atmosphere.

[000674] Figures 56A to 56C show, on the basis of schematic illustrations, a further exemplary embodiment of a luminaire 2 described here. In this exemplary embodiment, the luminaire 2 forms solar protection - besides its properties for general lighting.

[000675] Figure 56A shows the luminaire 2 on the basis of a schematic sectional illustration in a switched-off operating state. The luminaire 2 is in this switched-off operating state for example during the day, upon insolation. In this operating state, the luminaire 2 serves for light protection and casts a shadow 265. For this purpose, the luminaire 2 has a, for example, reflective surface at its top side facing away from the radiation exit area 174, said reflective surface reflecting the impinging radiation 191. Furthermore, it is possible for the luminaire 2 to be embodied, at its top side facing away from the radiation exit area 174, as a solar cell which, for example upon insolation, generates current by means of which the luminaire 2 can be operated later, for example at night. By way of example, the document US 7,317,210 discloses a combination of organic light-emitting diode and solar cell which can be used in this case.

[000676] In conjunction with the schematic illustration in figure 56B, the luminaire 2 is shown in a switched-on operating state. In the switched-on operating state, the luminaire 2 emits electromagnetic radiation 190 from its radiation exit area 174. In this case, the luminaire 2 preferably comprises a multiplicity of organic light-emitting diodes 1 or at least one organic light-emitting diode 1 subdivided into a multiplicity of segments 203. Each of the segments, or each organic light-emitting diode 1, can be suitable for generating light of a different color or having a different color temperature

than other segments 203, or light-emitting diodes 1, of the luminaire 2. Depending on the operation of the organic light-emitting diodes 1 or of the segments 203, it is thus possible to generate different light moods by means of different color loci and/or color temperatures of the emitted light. In this case, the different color loci and/or color temperatures can also be generated in different regions of the luminaire 2. That is to say that, for example, regions of the radiation exit area 174 can, for example, rather emit reddish light, whereas other regions of the radiation exit area 174 rather emit bluish light, for example. In this case, the regions of the radiation exit area 174 preferably each comprise a multiplicity of organic light-emitting diodes 1 or segments 203.

[000677] The construction of the luminaire and also the contact-connection of the individual organic light-emitting diodes 1, or of the segments 203, can be as described in conjunction with figure 45.

[000678] Organic light-emitting diodes 1 as described in conjunction with figures 1 to 31 are preferably used as organic light-emitting diodes 1.

[000679] The luminaire 2 is a large-area luminaire preferably having an area content of a radiation exit area 174 of at least 5 m^2, particularly preferably of at least 10 m^2. In this case, the radiation exit area 174 of the luminaire 2 is composed of the radiation exit areas of the organic light-emitting diodes 1 or of the segments 203.

[000680] In conjunction with figure 56C it is schematically illustrated that power can be supplied to the luminaire 2 via a stand 251, in which connection conductors 236 are laid.

[000681] Further exemplary embodiments of luminaires described here are shown in conjunction with figures 57A and 57B. In these exemplary embodiments, the luminaire 2 is embodied as a bag 266. The luminaire 2 can be used for example as a rucksack or as a school satchel.

[000682] For this purpose, organic light-emitting diodes 1 are applied or integrated at least on places of the bag 266. The organic light-emitting diodes 1 are preferably embodied in flexible fashion, such that they can adapt to the contours of the bag 266. That is to say that the bag 266 has at least one radiation entrance area 174, through which electromagnetic radiation 190, preferably light, leaves the luminaire.

[000683] In this case, the luminaire 2 comprises at least one organic light-emitting diode 1 which - as described by way of example in conjunction with figures 29 and 30 - comprises a retroreflector. In this way, even when the organic light-emitting diode 1 is not switched on, the luminaire 2 reflects impinging electromagnetic radiation and therefore serves, in this case, too, for better visibility of the user of the luminaire 2.

[000684] In conjunction with the schematic illustration in figure 57A it is furthermore explained that the bag 266 can have a slot 286, for example, in which is arranged a rechargeable battery 267 by means of which the organic light-emitting diode 1 of the luminaire 2 is supplied with electric current.

[000685] As an alternative or in addition to the embodiment of the luminaire 2 as a bag, it is furthermore conceivable for the luminaire 2 to be embodied as protective clothing, work clothing, headband, head covering or the like. At all events the luminaire 2 comprises at least one organic light-emitting diode 1 having a retroreflector. The luminaire 2 thus serves for improved visibility of its user both in the switched-on and in the switched-off operating state.

[000686] Further exemplary embodiments of a luminaire 2 described here are explained in greater detail in conjunction with the schematic illustrations in figures 58A and 58B. In these exemplary embodiments, the luminaire 2 serves as emergency lighting, for example as a camping light.

[000687] The luminaire 2 has a radiation exit area 174. Furthermore, the luminaire 2 has a solar cell 269 at the side lying opposite the radiation exit area 174. The solar

cell 269 can be a flexible inorganic or organic solar cell embodied in film-like fashion. At least one organic light-emitting diode 1 that is flexible and preferably emits white light serves as light source of the luminaire 2.

[000688] The luminaire 2 can be operated in two different operating states. Firstly, the luminaire 2 can be rolled to form a cylinder, which is closed by a connector 237. Connection locations for making contact with the luminaire 2 via connection conductors 236 can be situated at the connector 237.

[000689] In another operating state, the luminaire 2 can be rolled out. In this case, the luminaire 2 can be operated in suspended fashion, for example, by means of the connection conductors 236 and, if appropriate, a holding device 239, which can likewise be embodied in the manner of a wire or cable. In conjunction with figure 58A it is illustrated, for example, that the luminaire 2 is suspended from the branches of a tree. In this case, the radiation exit area 174 faces the ground, and the solar cell 269 is directed away from the ground.

[000690] Such a luminaire 2 can be charged by insolation, during the day, for example in the suspended state. At night, the luminaire 2 then continuously emits electromagnetic radiation 190 through the radiation exit area 174. In this case, the luminaire 2 is preferably operated as emergency or camping lighting, such that relatively low luminances are sufficient.

[000691] As an alternative to solar operation, which can be realized for example by means of a rechargeable battery integrated into the luminaire 2, the luminaire 2 can also be connected to an external power source, such as an automobile battery, for example, via the connection conductors 236.

[000692] In conjunction with figure 59, a further exemplary embodiment of a luminaire 2 described here is explained in greater detail with reference to a schematic perspective illustration. The luminaire 2 is a large-area luminaire which can be operated for example by means of a rechargeable battery 267 - in the

present case an automobile battery. The luminaire has a radiation exit area 174. The luminaire is fixed to a motor vehicle such as an automobile or a bus by means of the fixing means 248, for example. The fixing means 248 can be a magnet or an adhesive connection.

[000693] The luminaire 2 preferably comprises at least one organic light-emitting diode 1 as described here. The organic light-emitting diode 1 can be a flexible organic light-emitting diode 1 that illuminates an area 185a to be illuminated. The area 185a to be illuminated is, for example, a billboard or a company logo. The luminaire 2 can thus be used for advertising purposes on motor vehicles.

[000694] A further exemplary embodiment of a luminaire described here is explained in greater detail in conjunction with figures 60A to 60D. In this case, the luminaire 2 forms an umbrella 270. The umbrella 270 emits electromagnetic radiation 190 from its inner area.

[000695] This can be realized, firstly, by virtue of the luminaire 2 comprising at least one organic light-emitting diode 1 embodied in flexible fashion. The organic light-emitting diode 1 can then be situated on the inner side of the crown of the umbrella 270 or form the crown of the umbrella 270.

[000696] By way of example, electrical contact is made with the at least one organic light-emitting diode 1 by means of the struts or paragon rods 270a of the umbrella 270. The organic light-emitting diode 1 of the umbrella 270 can then be energized by means of at least one rechargeable battery 267, which can be arranged in the grip or handle 270d of the umbrella 270 (cf. figure 60D, for example).

[000697] As an alternative or in addition to at least one organic light-emitting diode 1, it is possible for the umbrella 270 to comprise at least one inorganic light-emitting diode 210 as light source. The at least one inorganic light-emitting diode 210 is fixed for example to or in the tube 270a of the umbrella 270. By way of example, the inorganic light-emitting diodes 210 are fixed to the slide 270b or below the slide 270b

of the umbrella 270. The inorganic light-emitting diodes 210 emit onto the inner side of the crown 270e of the umbrella 270, which is embodied as a reflector 271 or organic light-emitting diode 1 having a reflective layer.

[000698] In this case, the reflector 271 can be embodied in such a way that it emits electromagnetic radiation 190 in a directional fashion. It is thereby possible for the umbrella to emit radiation when being held vertically in the direction of movement of the user and, in this way, to illuminate the path ahead of the user.

[000699] Preferably, the inorganic light-emitting diodes 210 are fixedly connected to the slide 270b of the umbrella 270, such that, in the event of the umbrella 270 being open, they are conveyed into a position lying closely below the crown 270e of the umbrella 270. The lighting by the inorganic light-emitting diodes 210 can then be switched on at the same time as the slide 270b is slid up. However, it is also possible that the lighting can be switched on separately, such that it is activated for example only under poor visibility conditions.

[000700] In conjunction with figure 60D it is schematically illustrated that at least one rechargeable battery 267 as power supply for the light sources of the luminaire 2 forming an umbrella 270 can be arranged in the handle 207d of the umbrella. This can be charged, for example, by connection to an electrical power supply. Overall, the luminaire 2 in the exemplary embodiment in figures 60A to 60D constitutes a mobile light which enables improved visibility and an improved view for the user under poor visibility conditions including in road traffic.

[000701] Figures 61A to 61C show a further exemplary embodiment of a luminaire 2 described here in schematic illustrations.

[000702] The luminaire 2 in the present case is a vehicle light such as, for example, a brake light, an indicator light 280 and/or a rear light 281. What is common to the vehicle lights mentioned in this case is that they are integrated in a vehicle window 275. The luminaires 2 comprise, for example, a transparent organic light-emitting

diode, the first carrier 130 and second carrier 131 of which are in each case formed with a glass. The organic light-emitting diodes 1 are therefore integrated as transparent organic light-emitting diodes into parts of the vehicle windows 275. In this way it is possible to form an indicator light 280, for example, which can extend over the entire length of the vehicle. This increases the noticeability of the vehicle in road traffic.

[000703] By way of example, the organic light-emitting diodes 1 described in conjunction with figures 1 to 31 are used as organic light-emitting diode 1 for the luminaire 2 embodied as a vehicle light.

[000704] If the luminaire 2 is a rear light 281 or a brake light, then the luminaire can comprise an organic light-emitting diode 1 having a retroreflector, as explained in greater detail for example in conjunction with figures 29 and 30. In this case, even in the switched-off operating state, the luminaire 2 can reflect back red light, for example when irradiated by an automobile headlight.

[000705] As explained in conjunction with the schematic illustration in figure 61C, the luminaire 2 can be connected to the automobile battery of the motor vehicle for power supply via connection conductors 236.

[000706] In conjunction with figure 62, a further exemplary embodiment of a luminaire described here is explained in greater detail with reference to a schematic perspective illustration. In this exemplary embodiment, for the purpose of forming the luminaire 2, a transparent organic light-emitting diode is integrated over the whole area into a vehicle window 275 - here into the rear window. That is to say that the rear window 275 is formed by a transparent organic light-emitting diode 1. Such a luminaire 2 can serve for example for illuminating the interior of a trunk when the vehicle is not being driven.

[000707] Furthermore, it is possible for the organic light-emitting diode 1 to contain an emitter material suitable for generating infrared electromagnetic radiation. In this

case, the organic light-emitting diode 1 can also be used for deicing a vehicle window 275. The organic light-emitting diode 1 then need not necessarily also be suitable for generating visible light. In particular, it is possible in this case for all the vehicle windows 275 of the motor vehicle to be formed by transparent organic light-emitting diodes which are suitable for generating infrared electromagnetic radiation during operation. In this way, it is also possible, for example, to heat a front window of the motor vehicle, without heating wires threading through the window or without having to arrange in the vehicle a fan that blows hot air onto the vehicle window 275. In this way, it is also possible to prevent the vehicle windows 275 from steaming up.

[000708] By means of an optical cavity as explained in greater detail in conjunction with figures 26 and 27, it is possible for the entire or at least a majority of the infrared radiation generated to be directed toward the outside, out of the vehicle. In this case, by way of example, snow lying on the vehicle windows 275 can be melted away particularly efficiently.

[000709] In conjunction with figure 63, a further exemplary embodiment of a luminaire 2 described here is explained in greater detail with reference to a schematic perspective illustration. In this case, in order to form the luminaire 2, an organic light-emitting diode 1 is integrated in side areas of a trunk. The organic light-emitting diode 1 is integrated into the side areas of a trunk purely by way of example. In principle, it is possible for an organic light-emitting diode 1 to be fitted at any location in the interior of the motor vehicle. In particular, an organic light-emitting diode 1 can also be integrated onto the inner side of the vehicle roof or into the base of the trunk. The organic light-emitting diode 1 allows large-area illumination of the interior of the motor vehicle, without high luminances having to be used for this purpose - on account of the relatively large area of the light exit area 175 of the organic light-emitting diode 1. That means that the organic light-emitting diode 1 allows illumination of the interior of the motor vehicle with relatively low luminances, thus resulting in dazzle-free lighting.

[000710] In conjunction with figures 64A to 64C, a further exemplary embodiment

of a luminaire described here is explained in greater detail with reference to schematic illustrations. In this exemplary embodiment, the luminaire 2 forms a warning sign 285 such as can be used in road traffic, for example. In this case, as shown in figures 64B and 64C, the warning sign 285 is embodied in flexible fashion, such that it can be rolled up and unrolled. In figure 64B it is explained that the warning sign 285 can, for this purpose, be divided into individual organic light-emitting diodes 1 that are connected to one another by means of flexible connection conductors 236 that can be rolled up and unrolled.

[000711] In conjunction with figure 64C it is shown that the warning sign 285 can also be formed by one fully flexible organic light-emitting diode 1.

[000712] In both embodiments of the warning sign 285 it can be expedient for the warning sign 285 to emit electromagnetic radiation from two main areas. That is to say that the warning sign 285 is actively luminous from two sides, for example. By way of example, at least one organic light-emitting diode 1 with retroreflector as explained in greater detail in figures 29 and 30 is employed for forming the warning sign 285. In particular, it is possible for the warning sign 285 to have such organic light-emitting diodes 1 at both sides, such that it actively emits and reflects electromagnetic radiation 190 from both sides.

[000713] Further exemplary embodiments of a luminaire 2 described here are explained in greater detail in conjunction with figures 65A to 65C. In this exemplary embodiment, the luminaire 2 forms rain protection, for example a bus shelter. In this case, the luminaire 2 can comprise a plurality of organic light-emitting diodes 1 embodied in transparent fashion. By way of example, the carriers 130, 131 of the luminaire 2 form the basic body of the bus shelter and thus the rain protection. An encapsulation can then be embodied as in conjunction with the luminaire 2 embodied as a shower cubicle (cf. figures 33 to 35).

[000714] Furthermore, it is also possible, as indicated in figure 65B, for at least one of the organic light-emitting diodes 1 to be embodied as a large-area display device

which, by way of example, can display the next transport links, the time of day, the outside temperature or further simple information.

[000715] Finally, it is also possible, as described in greater detail in conjunction with figure 65C, for one of the luminaires 2 to serve for illuminating an area 185a to be illuminated. The area 185a to be illuminated is, for example, an advertisement such as a poster or the like. In this case, the element 185 to be illuminated is exchangeable, such that the area 185a to be illuminated can be changed from time to time.

[000716] The invention is not restricted to the exemplary embodiments by the description on the basis of said exemplary embodiments. Rather, the invention encompasses any novel feature and also any combination of features, which in particular includes any combination of features in the patent claims, even if this feature or this combination itself is not explicitly specified in the patent claims or exemplary embodiments.

Patent claims

1. A device comprising:

an organic light-emitting diode comprising an organic layer sequence, a radiation exit area and an encapsulation, wherein the organic layer sequence comprises at least one radiation-emitting region which generates electromagnetic radiation in the spectral range from infrared radiation to UV radiation during operation, and wherein the encapsulation forms a seal of the organic layer sequence against environmental influences,

at least one touch-sensitive operating element, wherein the at least one touch-sensitive operating element comprises at least one touch sensor, wherein the device is flexible.

2. The device according to claim 1, wherein the device in bendable or can be rolled.

3. The device according to claim 2, wherein the device maintains its form after bending.

4. The device according to claim 1, wherein the organic light-emitting diode comprises a flexible carrier.

5. The device according to claim 4, wherein the flexible carrier comprises a film or a plastic film or a laminate.

6. The device according to claim 1, wherein the encapsulation is flexible.

7. The device according to claim 1, wherein the touch-sensitive operating element is arranged at a light exit area of the device.

8. The device according to claim 1, wherein the at least one touch sensor is integrated into the organic light-emitting diode.

9. The device according to claim 1, wherein the device is drivable by means of a gesture control.

10. A device comprising:

an organic light-emitting diode comprising an organic layer sequence, a radiation exit area and an encapsulation, wherein the organic layer sequence comprises at least one radiation-emitting region which generates electromagnetic radiation in the spectral range from infrared radiation to UV radiation during operation, and wherein the encapsulation forms a seal of the organic layer sequence against environmental influences,

at least one touch-sensitive operating element, wherein the at least one touch-sensitive operating element comprises at least one touch sensor, wherein

the device is bendable or can be rolled.

11. The device according to claim 10, wherein the touch-sensitive operating element is arranged at a light exit area of the device.

12. The device according to claim 10, wherein the at least one touch sensor is integrated into the organic light-emitting diode.

13. The device according to claim 10, wherein the device is drivable by means of a gesture control.

ABSTRACT OF THE DISCLOSURE

A device comprising an organic light-emitting diode comprising an organic layer sequence, a radiation exit area and an encapsulation, wherein the organic layer sequence comprises at least one radiation-emitting region which generates electromagnetic radiation in the spectral range from infrared radiation to UV radiation during operation, and wherein the encapsulation forms a seal of the organic layer sequence against environmental influences, at least one touch-sensitive operating element, wherein the at least one touch-sensitive operating element comprises at least one touch sensor, wherein the device is flexible.

Attorney Docket # 5367-694PCON2/474410 Patent

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Continuation Application of
Ulrich KASTNER-JUNG et al.
Serial No.: TO BE ASSIGNED
Filing Date: CONCURRENTLY
For: Organic-Light-Emitting Diode

INFORMATION DISCLOSURE STATEMENT

Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

S I R:

In compliance with the duty of disclosure under 37 C.F.R. § 1.56 and in accordance with the practice under 37 C.F.R. §§ 1.97 and 1.98, the Examiner's attention is directed to the documents listed on the enclosed Form PTO/SB/08a.

Because (1) the parent application of this continuation application is identified as U.S. Application Serial No. 15/651,508 filed on July 17, 2017; and (2) the information cited herein was cited or discussed in the parent application, copies of the cited documents are not enclosed pursuant to 37 C.F.R. § 1.98(d).

It is respectfully requested that the above information be considered by the Examiner and that the copy of the enclosed Form PTO/SB/08a be returned indicating that such information has been considered.

In accordance with 37 C.F.R §§1.97(g) and (h), the filing of this Information Disclosure Statement should not be construed as a representation that a search has been made or that information cited is, or is considered to be, material to patentability as defined in §1.56(b), or that any cited document listed or attached

is (or constitutes) prior art. Unless otherwise indicated, the date of publication indicated for an item is taken from the face of the item and Applicants reserve the right to prove that the date of publication is in fact different.

If any fees or charges are deemed required at this time in connection with the application, the same may be charged to our Patent and Trademark Office Deposit Account No. 503111.

Respectfully submitted,
Cozen O'Connor

By /Edward M. Weisz/
Edward M. Weisz
Reg. No. 37,257
277 Park Avenue
New York, New York 10172
(212) 883-4900

Dated: February 13, 2020

PTO/SB/08A (04-03)
Approved for use through 04/30/2003. OMB 0651-0031
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number

Substitute for Form 1449/PTO	*Complete if Known*	
INFORMATION DISCLOSURE STATEMENT BY APPLICANT (Use as many sheets as necessary)	Application Number	
	Filing Date	
	First Named Inventor	Ulrich KASTNER-JUNG
	Art Unit	
	Examiner Name	
Sheet 1 of 4	Attorney Docket No.	5367-694PCON2/474410

U.S. PATENT DOCUMENTS

Examiner Initials*	Cite No. [1]	Document Number Number-Kind-Code [2] (if known)	Publication Date MM-DD-YYYY	Name of Patentee or Applicant of Cited Document	Pages, Columns, Lines, Where Relevant Passages or Relevant Figures Appear
		US-2007/0278937	12-06-2007	Forrest et al.	
		US-2003/0064540	04-03-2003	Auch et al.	
		US-7,280,439	10-09-2007	Shaddox	
		US-2003/0231495	12-18-2003	Searfoss, III	
		US-6,236,622	05-22-2001	Blackman	
		US-2008/0219013	09-11-2008	Budinger et al.	
		US-7,317,210	01-08-2008	Osram Opto Semiconductors GmbH	
		US-2009/0039272	02-12-2009	Osram Opto Semiconductors GmbH	
		US-7,922,358	04-12-2011	Osram Opto Semiconductors GmbH	
		US-2001/0052752	12-2001	Ghosh	
		US-2002/0125822	09-2002	Graff	
		US-2002/0167270	11-2002	Siwinski	
		US-2003/0071804	04-2003	Yamazaki	
		US-2003/0121767	07-2003	Caldwell	
		US-2003/0175553	09-2003	Thompson	
		US-2003/0222577	12-2003	Lu	
		US-2004/0113542	06-2004	Hsiao	
		US-2005/0099824	05-2005	Dowling	
		US-2006/0049381	03-2006	Klein	
		US-2007/0278937	12-2007	Forrest	
		US-2008/0248191	10-2008	Daniels	
		US-2010/0157585	06-2010	Diekmann	
		US-2012/0258294	10-2012	Leyder	
		US-5,734,225	03-1998	Biebuyck et al.	
		US-5,895,228	04-1999	Biebuyck	
		US-7,733,008	06-08-2010	Agency for Science Tech. & Research	
		US-2005/0231101	10-20-2005	Chen	
		US-2001/0043046	11-22-2001	Fukunaga	
		US-2007/0114520	05-24-2007	Osram Opto Seminconductors GmbH	
		US-2007/0230211	10-04-2007	Canon KK	
		US-2009/0072711	03-19-2009	Thomson Licensing	
		US-7,560,727	07-14-2009	Ishikawa	

Examiner Signature		Date Considered	

*EXAMINER: Initial if reference considered, whether or not citation is in conformance with MPEP 609. Draw line through citation if not in conformance and not considered. Include copy of this form with next communication to applicant. [1] Applicant's unique citation designation number (optional). [2] See Kinds Codes of USPTO Patent Documents at www.uspto.gov or MPEP 901.04. [3] Enter Office that issued the document, by the two-letter code (WIPO Standard ST.3). [4] For Japanese patent documents, the indication of the year of the reign of the Emperor must precede the serial number of the patent document. [5] Kind of document by the appropriate symbols as indicated on the document under WIPO Standard ST. 16 if possible. [6] Applicant is to place a check mark here if English language Translation is attached. This collection of information is required by 37 CFR 1.97 and 1.98. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, Washington, DC 20231.**

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number

Substitute for Form 1449/PTO	*Complete if Known*	
	Application Number	
	Filing Date	
INFORMATION DISCLOSURE STATEMENT BY APPLICANT	First Named Inventor	Ulrich KASTNER-JUNG
	Art Unit	
(Use as many sheets as necessary)	Examiner Name	
Sheet 2 of 4	Attorney Docket No.	5367-694PCON2/474410

FOREIGN PATENT DOCUMENTS

Examiner Initials*	Cite No. [1]	Foreign Patent Document Country Code[3]- Number[4]-Kind-Code [5] (if known	Publication Date MM-DD-YYYY	Name of Patentee or Applicant of Cited Document	Pages, Columns, Lines, Where Relevant Passages or Relevant Figures Appear	T[6]
		DE 10 2006 037 222	02-14-2008	Swoboda et al.		
		JP 2007-294143	11-08-2007	Matsuura		
		WO 2008/110959	09-18-2008	Van Woudenberg et al.		
		WO 2008/146232	12-04-2008	Schlangen et al.		
		DE 10308514	09-09-2004	Schott Glas		
		DE 10332956	02-10-2005	Woehr Richard GmbH		
		KR 20080081255	09-09-2008	Osram Opto Semiconductors GmbH		
		KR 20020079438	10-19-2002	Eastman Kodak Co.		
		DE 102008051132	01-21-2010	Osram Opto Semiconductors GmbH		
		WO 2009/040401	04-02-2009	Osram Opto Semiconductors GmbH		
		WO 2009/074127	06-18-2009	Osram Opto Semiconductors GmbH		
		WO 2009/095005	08-06-2009	Osram Opto Semiconductors GmbH		
		WO 2009/106067	09-03-2009	Osram Opto Semiconductors GmbH		
		WO 2010/006571	01-21-2010	Osram Opto Semiconductors GmbH		
		WO 2008/040323	04-2008	Diekmann		
		WO 2008/146232	12-2008	Schlangen		
		JP 2005-510851	04-21-2005	Agency for Science, Tech. & Research		
		KR 100743545	07-23-2007	Lee Young Jong		
		KR 1020050065948	11-11-2013	LG Electronics Inc.		
		JP 2002-033198	01-31-2002	Semiconductor Energy Lab		
		DE 102007059732	06-18-2009	OSRAM Opto Semiconductors GmbH		
		KR 2008-0042275	05-15-2008	Oh et al.		

Examiner Signature		Date Considered	

*EXAMINER: Initial if reference considered, whether or not citation is in conformance with MPEP 609. Draw line through citation if not in conformance and not considered. Include copy of this form with next communication to applicant. [1] Applicant's unique citation designation number (optional). [2] See Kinds Codes of USPTO Patent Documents at www.uspto.gov or MPEP 901.04. [3] Enter Office that issued the document, by the two-letter code (WIPO Standard ST.3). [4] For Japanese patent documents, the indication of the year of the reign of the Emperor must precede the serial number of the patent document. [5] Kind of document by the appropriate symbols as indicated on the document under WIPO Standard ST. 16 if possible. [6] Applicant is to place a check mark here if English language Translation is attached. This collection of information is required by 37 CFR 1.97 and 1.98. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, Washington, DC 20231.**

PTO/SB/08A (04-03)
Approved for use through 04/30/2003. OMB 0651-0031
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number

Substitute for Form 1449/PTO				Complete if Known	
INFORMATION DISCLOSURE STATEMENT BY APPLICANT (Use as many sheets as necessary)				Application Number	
				Filing Date	
				First Named Inventor	Ulrich KASTNER-JUNG
				Art Unit	
				Examiner Name	
Sheet	3	of	4	Attorney Docket	5367-694P/CON2/474410

FOREIGN PATENT DOCUMENTS

Examiner Initials*	Cite No. [1]	Foreign Patent Document Country Code[3]- Number[4]- Kind-Code [5] (if known	Publication Date MM-DD-YYYY	Name of Patentee or Applicant of Cited Document	Pages, Columns, Lines, Where Relevant Passages or Relevant Figures Appear	T[6]
		JP 2007-200887	08-09-2007	Dong-Soo et al.		
		JP 2004-296423	10-21-2004	Toshitaka et al.		
		JP 2008-538155	10-09-2008	Cok et al.		
		JP 4182467B2	11-19-2008	Takashi		
		JP 4228248B2	02-25-2009	Hideo et al.		
		JP 4637390B2	02-23-2011	Shunpei et al.		
		JP 4713010B2	06-29-2011	Kenji		
		JP 4742880B2	08-10-2011	Osamu et al.		
		JP 4828881B2	11-30-2011	Satoshi		
		JP 2003-195775	07-09-2003	Takashi		
		JP 2004-047179	02-12-2004	Tamotsu et al.		

Examiner Signature		Date Considered	

*EXAMINER: Initial if reference considered, whether or not citation is in conformance with MPEP 609. Draw line through citation if not in conformance and not considered. Include copy of this form with next communication to applicant. [1] Applicant's unique citation designation number (optional). [2] See Kinds Codes of USPTO Patent Documents at www.uspto.gov or MPEP 901.04. [3] Enter Office that issued the document, by the two-letter code (WIPO Standard ST.3). [4] For Japanese patent documents, the indication of the year of the reign of the Emperor must precede the serial number of the patent document. [5] Kind of document by the appropriate symbols as indicated on the document under WIPO Standard ST. 16 if possible. [6] Applicant is to place a check mark here if English language Translation is attached. This collection of information is required by 37 CFR 1.97 and 1.98. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, Washington, DC 20231.**

PTO/SB/08A (04-03)
Approved for use through 04/30/2003. OMB 0651-0031
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number

Substitute for Form 1449/PTO		Complete if Known	
INFORMATION DISCLOSURE STATEMENT BY APPLICANT (Use as many sheets as necessary)		Application Number	
		Filing Date	
		First Named Inventor	Ulrich KASTNER-JUNG
		Art Unit	
		Examiner Name	
Sheet 4 of 4		Attorney Docket No.	5367-694PCON2/474410

NON PATENT LITERATURE DOCUMENTS

Examiner Initials*	Cite No.[1]	Include name of the author (in CAPITAL LETTERS), title of the article (when appropriate), title of the item (book, magazine, journal, serial, symposium, catalog, etc.), date, page(s), volume-issue number(s), publisher, city and/or country where published.	T[2]
		Boffi Wedge. Stylepark, May 25, 2011. (1 page). Retrieved from http://www.stylepark.com/en/boffi/wedge.	
		Bus stop shelter intelligent series. May 25, 2011. (2 pages). Retrieved from http://www.wall.de/en/street_furniture/products?category_scope=bus_stop_shelter	
		Cristina Rubinetterie sandwich shower head – new electronic LED shower head, May 12, 2007. (3 pages). Retrieved from http://www.trendir.com/archives/001435.html.	
		Dornbracht RainSky E Showers by Rixson & Green Shortlands Ltd. September 2000. (1 page). Retrieved from http://www.rixson-green.co.uk/dornbracht_showers.htm.	
		Marketing-displays. Illuminated box CLP-S I freetstanding unit, one-sided (1200 x 1760 mm). May 25, 2011. (1 page). Retrieved from http://www.md-displayshop.de/ProductDetails.aspx?id=24&prodi...	
		LCD-Glass; Glass with LCD Film (max height 300 – max width 120). 2009. (2 pages). Retrieved from http://www.vetroin.co.uk/en/TECHNOLOGY/LDC-Glass.html	
		ThinkGeek:Lumadot LED Umbrella. May 25, 2011. (2 pages). Retrieved from http://www.thinkgeek.com/interests/moms/d16b/	
		Luceplan. Strip D22/4 – D22/4 EL. May 25, 2011. Retrieved from http://www.luceplan.com/Dynamic/Prodotti.php?intLangID=1&intC...	
		Multifunctional shower cabin- WELL BOX- Megius SpA. 2011. (1 page). Retrieved from http://www.archiexpo.com/prod/megius-spa/multifunctional-shower...	
		The General Properties of Si, Ge, SiGe, SiO2 and Si3N4 (June 2002, Virginia Semiconductor, Retrieved from the Internet: <URL www.virginiasemi.com/pdf/generalpropertiesSi62002.pdf>)	
		Edgar S. Zaus et al., "Design of Highly Transparent Organic Photodiodes, IEEE Transactions of Electron Devices, Vo. 55, No. 2, February 2008	
		N. R. Mowrer, "Polysiloxanes, Ameron International Performance Coatings and Finishes, November 2003	

Examiner Signature		Date Considered	

*EXAMINER: Initial if reference considered, whether or not citation is in conformance with MPEP 609. Draw line through citation if not in conformance and not considered. Include copy of this form with next communication to applicant. [1] Applicant's unique citation designation number (optional). [2] See Kinds Codes of USPTO Patent Documents at www.uspto.gov or MPEP 901.04. [3] Enter Office that issued the document, by the two-letter code (WIPO Standard ST.3). [4] For Japanese patent documents, the indication of the year of the reign of the Emperor must precede the serial number of the patent document. [5] Kind of document by the appropriate symbols as indicated on the document under WIPO Standard ST. 16 if possible. [6] Applicant is to place a check mark here if English language Translation is attached. This collection of information is required by 37 CFR 1.97 and 1.98. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, Washington, DC 20231.**

UNITED STATES PATENT AND TRADEMARK OFFICE
UNDER SECRETARY OF COMMERCE FOR INTELLECTUAL PROPERTY AND
DIRECTOR OF THE UNITED STATES PATENT AND TRADEMARK OFFICE

JANUARY 26, 2016

PTAS

COZEN O'CONNOR
277 PARK AVENUE
NEW YORK, NY 10172

503658323

UNITED STATES PATENT AND TRADEMARK OFFICE
NOTICE OF RECORDATION OF ASSIGNMENT DOCUMENT

THE ENCLOSED DOCUMENT HAS BEEN RECORDED BY THE ASSIGNMENT RECORDATION BRANCH OF THE U.S. PATENT AND TRADEMARK OFFICE. A COMPLETE COPY IS AVAILABLE AT THE ASSIGNMENT SEARCH ROOM ON THE REEL AND FRAME NUMBER REFERENCED BELOW.

PLEASE REVIEW ALL INFORMATION CONTAINED ON THIS NOTICE. THE INFORMATION CONTAINED ON THIS RECORDATION NOTICE REFLECTS THE DATA PRESENT IN THE PATENT AND TRADEMARK ASSIGNMENT SYSTEM. IF YOU SHOULD FIND ANY ERRORS OR HAVE QUESTIONS CONCERNING THIS NOTICE, YOU MAY CONTACT THE ASSIGNMENT RECORDATION BRANCH AT 571-272-3350. PLEASE SEND REQUEST FOR CORRECTION TO: U.S. PATENT AND TRADEMARK OFFICE, MAIL STOP: ASSIGNMENT RECORDATION BRANCH, P.O. BOX 1450, ALEXANDRIA, VA 22313.

RECORDATION DATE: 01/21/2016
REEL/FRAME: 037567/0993
NUMBER OF PAGES: 7

BRIEF: ASSIGNMENT OF ASSIGNORS INTEREST (SEE DOCUMENT FOR DETAILS).

DOCKET NUMBER: 5367-0

ASSIGNOR:
OSRAM OPTO SEMICONDUCTORS GMBH
DOC DATE: 12/16/2015

ASSIGNEE:
OSRAM OLED GMBH
WERNERWERKSTRASSE 2
REGENSBURG, GERMANY 93049

APPLICATION NUMBER: 10447988
FILING DATE: 05/29/2003
PATENT NUMBER: 6946319
ISSUE DATE: 09/20/2005
TITLE: ELECTRODE FOR AN ELECTRONIC DEVICE

APPLICATION NUMBER: 10555982
FILING DATE: 05/18/2006
PATENT NUMBER: 7951874
ISSUE DATE: 05/31/2011
TITLE: NON-CONJUGATED POLYMERIC PERARYLATED BORANES, USE THEREOF AS ORGANICALLY SEMICONDUCTOR TRANSMITTERS AND/OR TRANSPORT MATERIALS, METHODS FOR PRODUCING SAME AND USES THEREOF

APPLICATION NUMBER: 10843803
FILING DATE: 05/11/2004
PATENT NUMBER: 7550915
ISSUE DATE: 06/23/2009
TITLE: ORGANIC ELECTRONIC DEVICE WITH HOLE INJECTION

APPLICATION NUMBER: 10951479 FILING DATE: 09/27/2004
PATENT NUMBER: 7242141 ISSUE DATE: 07/10/2007
TITLE: INTEGRATED FUSES FOR OLED LIGHTING DEVICE

APPLICATION NUMBER: 10952601 FILING DATE: 09/28/2004
PATENT NUMBER: 7157928 ISSUE DATE: 01/02/2007
TITLE: DETERMINING LEAKAGE IN MATRIX-STRUCTURED ELECTRONIC DEVICES

APPLICATION NUMBER: 10952602 FILING DATE: 09/28/2004
PATENT NUMBER: 7489074 ISSUE DATE: 02/10/2009
TITLE: REDUCING OR ELIMINATING COLOR CHANGE FOR MICROCAVITY OLED DEVICES

APPLICATION NUMBER: 11052943 FILING DATE: 02/07/2005
PATENT NUMBER: 7589465 ISSUE DATE: 09/15/2009
TITLE: NOVEL GETTER MATERIAL

APPLICATION NUMBER: 11159557 FILING DATE: 06/22/2005
PATENT NUMBER: 7554257 ISSUE DATE: 06/30/2009
TITLE: NOVEL METHOD TO GENERATE HIGH EFFICIENT DEVICES WHICH EMIT HIGH QUALITY LIGHT FOR ILLUMINATION

APPLICATION NUMBER: 11268338 FILING DATE: 11/07/2005
PATENT NUMBER: 7329560 ISSUE DATE: 02/12/2008
TITLE: METHOD FOR ENCAPSULATING AT LEAST ONE ORGANIC LIGHT-EMITTING (OLED) DEVICE AND OLED DEVICE

APPLICATION NUMBER: 11292038 FILING DATE: 11/30/2005
PATENT NUMBER: 7521856 ISSUE DATE: 04/21/2009
TITLE: OLED DEVICE

APPLICATION NUMBER: 11645971 FILING DATE: 12/26/2006
PATENT NUMBER: 7710365 ISSUE DATE: 05/04/2010
TITLE: DETERMINING LEAKAGE IN MATRIX-STRUCTURED ELECTRONIC DEVICES

APPLICATION NUMBER: 11658772 FILING DATE: 03/10/2008
PATENT NUMBER: ISSUE DATE:
TITLE: ORGANIC LIGHT EMITTING DIODE WITH INCREASED RADICAL ANION STABIILTY AND APPLICATIONS THEREOF

APPLICATION NUMBER: 11992992 FILING DATE: 05/05/2009
PATENT NUMBER: 8193070 ISSUE DATE: 06/05/2012
TITLE: METHOD FOR BONDING LAYERS, CORRESPONDING DEVICE AND ORGANIC LIGHT-EMITTING DIODE

APPLICATION NUMBER: 12011437 FILING DATE: 01/25/2008
PATENT NUMBER: 7970036 ISSUE DATE: 06/28/2011
TITLE: ORGANIC SEMICONDUCTOR LASER AND METHOD FOR PRODUCING IT

APPLICATION NUMBER: 12148294 FILING DATE: 04/16/2008
PATENT NUMBER: 8400054 ISSUE DATE: 03/19/2013
TITLE: ORGANIC OPTOELECTRONIC COMPONENT

APPLICATION NUMBER: 12157054 FILING DATE: 06/06/2008
PATENT NUMBER: 7982387 ISSUE DATE: 07/19/2011
TITLE: OPTOELECTRONIC COMPONENT

APPLICATION NUMBER: 12157061 FILING DATE: 06/06/2008
PATENT NUMBER: 8173998 ISSUE DATE: 05/08/2012
TITLE: RADIATION EMITTING DEVICE

APPLICATION NUMBER: 12240248 FILING DATE: 09/29/2008
PATENT NUMBER: 8791633 ISSUE DATE: 07/29/2014
TITLE: RADIATION-EMITTING DEVICE

APPLICATION NUMBER: 12240392 FILING DATE: 09/29/2008
PATENT NUMBER: 7922358 ISSUE DATE: 04/12/2011
TITLE: ILLUMINATION DEVICE, LUMINAIRE AND DISPLAY DEVICE

APPLICATION NUMBER: 12290708 FILING DATE: 11/03/2008
PATENT NUMBER: 8154200 ISSUE DATE: 04/10/2012
TITLE: ENCAPSULATION OF ORGANIC DEVICES

APPLICATION NUMBER: 12373504 FILING DATE: 08/12/2009
PATENT NUMBER: 8232393 ISSUE DATE: 07/31/2012
TITLE: NOVEL AROMATIC AZA HETEROCYCLES, METHOD OF PRODUCTION AND USE OF THE MATERIAL IN ORGANIC ELECTRONICS

APPLICATION NUMBER: 12375875 FILING DATE: 08/12/2009
PATENT NUMBER: ISSUE DATE:
TITLE: RADIATION-EMITTING COMPONENT

APPLICATION NUMBER: 12443672 FILING DATE: 01/11/2010
PATENT NUMBER: 8328375 ISSUE DATE: 12/11/2012
TITLE: ORGANIC LIGHTING DEVICE AND LIGHTING EQUIPMENT

APPLICATION NUMBER: 12514986 FILING DATE: 12/22/2009
PATENT NUMBER: 8309284 ISSUE DATE: 11/13/2012
TITLE: NOVEL HIGHLY CONDUCTIVE ORGANIC CHARGE CARRIER TRANSPORT MATERIAL

APPLICATION NUMBER: 12601520 FILING DATE: 04/20/2010
PATENT NUMBER: 8734962 ISSUE DATE: 05/27/2014
TITLE: PHOSPHORESCENT METAL COMPLEX COMPOUND RADIATION EMITTING COMPONENT COMPRISING A PHOSPHORESCENT METAL COMPLEX COMPOUND AND METHOD FOR PRODUCTION OF A PHOSPHORESCENT METAL COMPLEX COMPOUND

APPLICATION NUMBER: 12665934 FILING DATE: 06/07/2010
PATENT NUMBER: 8513702 ISSUE DATE: 08/20/2013
TITLE: USE OF A METAL COMPLEX AS A P-DOPANT FOR AN ORGANIC SEMICONDUCTIVE MATRIX MATERIAL, ORGANIC SEMICONDUCTOR MATERIAL, AND ORGANIC LIGHT-EMITTING DIODES

APPLICATION NUMBER: 12679138 FILING DATE: 11/23/2010
PATENT NUMBER: 8314547 ISSUE DATE: 11/20/2012
TITLE: OPTO-ELECTRONIC COMPONENT

APPLICATION NUMBER: 12679472 FILING DATE: 08/09/2010
PATENT NUMBER: 8974679 ISSUE DATE: 03/10/2015
TITLE: METHOD FOR MANUFACTURING AN OPTO-ELECTRONIC COMPONENT

APPLICATION NUMBER: 12680190 FILING DATE: 09/02/2010
PATENT NUMBER: 8441004 ISSUE DATE: 05/14/2013
TITLE: RADIATION EMITTING DEVICE AND METHOD FOR THE PRODUCTION THEREOF

APPLICATION NUMBER: 12680324 FILING DATE: 09/26/2011
PATENT NUMBER: 8987708 ISSUE DATE: 03/24/2015
TITLE: OPTOELECTRONIC COMPONENT

APPLICATION NUMBER: 12680610 FILING DATE: 07/19/2010
PATENT NUMBER: 8487329 ISSUE DATE: 07/16/2013
TITLE: LIGHT-EMITTING COMPONENT HAVING A WAVELENGTH CONVERTER AND PRODUCTION METHOD

APPLICATION NUMBER: 12680618 FILING DATE: 09/07/2010
PATENT NUMBER: 9139764 ISSUE DATE: 09/22/2015
TITLE: ORGANIC RADIATION-EMITTING COMPONENT

APPLICATION NUMBER: 12808156 FILING DATE: 09/07/2010
PATENT NUMBER: 8653548 ISSUE DATE: 02/18/2014
TITLE: LIGHT-EMITTING DEVICE

APPLICATION NUMBER: 12865346 FILING DATE: 11/29/2010
PATENT NUMBER: 8916397 ISSUE DATE: 12/23/2014
TITLE: METHOD FOR PRODUCING AN ELECTRONIC COMPONENT AND ELECTRONIC COMPONENT

APPLICATION NUMBER: 12865358 FILING DATE: 11/29/2010
PATENT NUMBER: 8658442 ISSUE DATE: 02/25/2014
TITLE: METHOD FOR PRODUCING AN ELECTRONIC COMPONENT AND ELECTRONIC COMPONENT

APPLICATION NUMBER: 12865646 FILING DATE: 11/17/2010
PATENT NUMBER: 8633585 ISSUE DATE: 01/21/2014
TITLE: DEVICE COMPRISING AN ENCAPSULATION UNIT

APPLICATION NUMBER: 12867241 FILING DATE: 11/15/2010
PATENT NUMBER: 8791490 ISSUE DATE: 07/29/2014
TITLE: ORGANIC LIGHT-EMITTING DIODE, CONTACT ARRANGEMENT AND METHOD FOR PRODUCING AN ORGANIC LIGHT-EMITTING DIODE

APPLICATION NUMBER: 12919752 FILING DATE: 02/14/2011
PATENT NUMBER: 8314541 ISSUE DATE: 11/20/2012
TITLE: RADIATION-EMITTING ARRANGEMENT

APPLICATION NUMBER: 12919989 FILING DATE: 01/13/2011
PATENT NUMBER: 8841153 ISSUE DATE: 09/23/2014
TITLE: METHOD FOR PRODUCING A DOPED ORGANIC SEMICONDUCTING LAYER

APPLICATION NUMBER: 12921313 FILING DATE: 12/20/2010
PATENT NUMBER: 8653509 ISSUE DATE: 02/18/2014
TITLE: OPTOELECTRONIC COMPONENT

APPLICATION NUMBER: 12995182 FILING DATE: 02/17/2011
PATENT NUMBER: 8686440 ISSUE DATE: 04/01/2014
TITLE: ORGANIC LIGHT EMITTING COMPONENT AND ILLUMINATION MEANS COMPRISING A COMPONENT OF THIS TYPE

APPLICATION NUMBER: 12995457 FILING DATE: 02/18/2011
PATENT NUMBER: 8723164 ISSUE DATE: 05/13/2014
TITLE: ELECTRONIC DEVICE

APPLICATION NUMBER: 13054397 FILING DATE: 05/04/2011
PATENT NUMBER: 8530928 ISSUE DATE: 09/10/2013
TITLE: ENCAPSULATED OPTOELECTRONIC COMPONENT AND METHOD FOR THE PRODUCTION THEREOF

APPLICATION NUMBER: 13055901 FILING DATE: 04/21/2011
PATENT NUMBER: 8772818 ISSUE DATE: 07/08/2014
TITLE: RADIATION-EMITTING DEVICE AND METHOD FOR PRODUCING A RADIATION-EMITTING DEVICE

APPLICATION NUMBER: 13062449 FILING DATE: 05/23/2011
PATENT NUMBER: 8927325 ISSUE DATE: 01/06/2015
TITLE: METHOD FOR PRODUCING AN ORGANIC RADIATION-EMITTING COMPONENT AND ORGANIC RADIATION-EMITTING COMPONENT

APPLICATION NUMBER: 13081634 FILING DATE: 04/07/2011
PATENT NUMBER: 8294161 ISSUE DATE: 10/23/2012
TITLE: RADIATION EMITTING DEVICE

APPLICATION NUMBER: 13121060 FILING DATE: 08/22/2011
PATENT NUMBER: 8492973 ISSUE DATE: 07/23/2013
TITLE: ORGANIC OPTOELECTRONIC COMPONENT HAVING A RADIATION-EMITTING LAYER CONTAINING AN ORGANIC MATERIAL

APPLICATION NUMBER: 13121090 FILING DATE: 09/08/2011
PATENT NUMBER: 8558223 ISSUE DATE: 10/15/2013
TITLE: ORGANIC ELECTRONIC COMPONENT AND METHOD FOR THE PRODUCTION THEREOF

APPLICATION NUMBER: 13127208 FILING DATE: 07/25/2011
PATENT NUMBER: 9172042 ISSUE DATE: 10/27/2015
TITLE: ORGANIC, RADIATION-EMITTING COMPONENT AND METHOD FOR PRODUCING SUCH A COMPONENT

APPLICATION NUMBER: 13127229 FILING DATE: 10/11/2011
PATENT NUMBER: 8461579 ISSUE DATE: 06/11/2013
TITLE: ORGANIC RADIATION-EMITTING COMPONENT AND METHOD FOR PRODUCING AN ORGANIC RADIATION-EMITTING COMPONENT

APPLICATION NUMBER: 13127231 FILING DATE: 08/23/2011
PATENT NUMBER: 8816329 ISSUE DATE: 08/26/2014
TITLE: RADIATION-EMITTING DEVICE

APPLICATION NUMBER: 13128375 FILING DATE: 08/08/2011
PATENT NUMBER: 8734196 ISSUE DATE: 05/27/2014
TITLE: METHOD FOR PRODUCING AN ORGANIC RADIATION-EMITTING COMPONENT AND ORGANIC RADIATION-EMITTING COMPONENT

APPLICATION NUMBER: 13139514 FILING DATE: 01/03/2012
PATENT NUMBER: ISSUE DATE:
TITLE: ORGANIC-LIGHT-EMITTING DIODE AND LUMINAIRE

APPLICATION NUMBER: 13260560 FILING DATE: 12/14/2011
PATENT NUMBER: ISSUE DATE:
TITLE: THIN-LAYER ENCAPSULATION FOR AN OPTOELECTRONIC COMPONENT, METHOD FOR THE PRODUCTION THEREOF, AND OPTOELECTRONIC COMPONENT

APPLICATION NUMBER: 13260982 FILING DATE: 01/26/2012
PATENT NUMBER: ISSUE DATE:
TITLE: ORGANIC OPTOELECTRONIC COMPONENT AND METHOD FOR PRODUCING AN ORGANIC OPTOELECTRONIC COMPONENT

APPLICATION NUMBER: 13262776 FILING DATE: 04/02/2012
PATENT NUMBER: 8808402 ISSUE DATE: 08/19/2014
TITLE: ARRANGEMENT FOR HOLDING A SUBSTRATE IN A MATERIAL DEPOSITION APPARATUS

APPLICATION NUMBER: 13266095 FILING DATE: 04/10/2012
PATENT NUMBER: 8441187 ISSUE DATE: 05/14/2013
TITLE: RADIATION-EMITTING DEVICE

APPLICATION NUMBER: 13318341 FILING DATE: 02/02/2012
PATENT NUMBER: 8680563 ISSUE DATE: 03/25/2014
TITLE: OPTOELECTRONIC COMPONENT AND METHOD FOR THE PRODUCTION THEREOF

APPLICATION NUMBER: 13375207 FILING DATE: 02/06/2012
PATENT NUMBER: 9203042 ISSUE DATE: 12/01/2015
TITLE: ELECTRONIC COMPONENT AND METHOD FOR PRODUCING AN ELECTRONIC COMPONENT

APPLICATION NUMBER: 13375214 FILING DATE: 03/21/2012
PATENT NUMBER: 8618729 ISSUE DATE: 12/31/2013
TITLE: ORGANIC LIGHT-EMITTING DIODE CONFIGURED SUCH THAT LIGHT IS EFFICIENTLY DECOUPLED FROM PLASMON MODES OF A METAL ELECTRODE.

APPLICATION NUMBER: 13378919 FILING DATE: 03/28/2012
PATENT NUMBER: ISSUE DATE:
TITLE: RADIATION EMITTING DEVICE

APPLICATION NUMBER: 13387690 FILING DATE: 03/29/2012
PATENT NUMBER: 9059423 ISSUE DATE: 06/16/2015
TITLE: ELECTRONIC COMPONENT AND ELECTRICAL CONTACT

APPLICATION NUMBER: 13387978 FILING DATE: 05/15/2012
PATENT NUMBER: 8829496 ISSUE DATE: 09/09/2014
TITLE: ORGANIC COMPONENT AND METHOD FOR THE PRODUCTION THEREOF

APPLICATION NUMBER: 13388275 FILING DATE: 06/11/2012
PATENT NUMBER: 8866181 ISSUE DATE: 10/21/2014
TITLE: METHOD FOR PRODUCING A COMPONENT WITH AT LEAST ONE ORGANIC MATERIAL AND COMPONENT WITH AT LEAST ONE ORGANIC MATERIAL

APPLICATION NUMBER: 13390289 FILING DATE: 08/06/2012
PATENT NUMBER: 9052094 ISSUE DATE: 06/09/2015
TITLE: SEMICONDUCTOR LIGHT SOURCE

APPLICATION NUMBER: 13407558 FILING DATE: 02/28/2012
PATENT NUMBER: 8610114 ISSUE DATE: 12/17/2013
TITLE: RADIATION EMITTING DEVICE

APPLICATION NUMBER: 13434323 FILING DATE: 03/29/2012
PATENT NUMBER: 8552644 ISSUE DATE: 10/08/2013
TITLE: ENCAPSULATION OF ORGANIC DEVICES

APPLICATION NUMBER: 13498307 FILING DATE: 06/05/2012
PATENT NUMBER: 9203029 ISSUE DATE: 12/01/2015
TITLE: METHOD FOR PRODUCING AN ELECTRONIC COMPONENT

APPLICATION NUMBER: 13499542 FILING DATE: 07/27/2012
PATENT NUMBER: ISSUE DATE:
TITLE: ORGANIC ELECTRONIC DEVICE AND METHOD FOR THE PRODUCTION THEREOF

APPLICATION NUMBER: 13499608 FILING DATE: 06/12/2012
PATENT NUMBER: 8785916 ISSUE DATE: 07/22/2014
TITLE: OPTOELECTRONIC ORGANIC COMPONENT AND METHOD FOR THE PRODUCTION THEREOF

APPLICATION NUMBER: 13669222 FILING DATE: 11/05/2012
PATENT NUMBER: 8946986 ISSUE DATE: 02/03/2015
TITLE: ORGANIC LIGHTING DEVICE AND LIGHTING EQUIPMENT

APPLICATION NUMBER: 14150291 FILING DATE: 01/08/2014
PATENT NUMBER: ISSUE DATE:
TITLE: DEVICE COMPRISING AN ENCAPSULATION UNIT

APPLICATION NUMBER: 14152608 FILING DATE: 01/10/2014
PATENT NUMBER: 9130189 ISSUE DATE: 09/08/2015
TITLE: OPTOELECTRONIC COMPONENT AND METHOD FOR THE PRODUCTION THEREOF

APPLICATION NUMBER: 14163240 FILING DATE: 01/24/2014
PATENT NUMBER: ISSUE DATE:
TITLE: METHOD FOR PRODUCING AN ELECTRONIC COMPONENT AND ELECTRONIC COMPONENT

APPLICATION NUMBER: 14211190 FILING DATE: 03/14/2014
PATENT NUMBER: ISSUE DATE:
TITLE: PHOSPHORESCENT METAL COMPLEX COMPOUND RADIATION EMITTING COMPONENT COMPRISING A PHOSPHORESCENT METAL COMPLEX COMPOUND AND METHOD FOR PRODUCTION OF A PHOSPHORESCENT METAL COMPLEX COMPOUND

APPLICATION NUMBER: 14540670 FILING DATE: 11/13/2014
PATENT NUMBER: ISSUE DATE:
TITLE: METHOD FOR PRODUCING AN ELECTRONIC COMPONENT AND ELECTRONIC COMPONENT

APPLICATION NUMBER: 14598685 FILING DATE: 01/16/2015
PATENT NUMBER: ISSUE DATE:
TITLE: ORGANIC LIGHTING DEVICE AND LIGHTING EQUIPMENT

APPLICATION NUMBER: 14885577 FILING DATE: 10/16/2015
PATENT NUMBER: ISSUE DATE:
TITLE: METHOD FOR PRODUCING AN ELECTRONIC COMPONENT AND ELECTRONIC COMPONENT

ASSIGNMENT RECORDATION BRANCH
PUBLIC RECORDS DIVISION

UNITED STATES PATENT AND TRADEMARK OFFICE
UNDER SECRETARY OF COMMERCE FOR INTELLECTUAL PROPERTY AND
DIRECTOR OF THE UNITED STATES PATENT AND TRADEMARK OFFICE

5367-694PUS

NOVEMBER 30, 2011

PTAS

COZEN O'CONNOR
277 PARK AVENUE
NEW YORK, NY 10172

501737711

UNITED STATES PATENT AND TRADEMARK OFFICE
NOTICE OF RECORDATION OF ASSIGNMENT DOCUMENT

THE ENCLOSED DOCUMENT HAS BEEN RECORDED BY THE ASSIGNMENT RECORDATION BRANCH OF THE U.S. PATENT AND TRADEMARK OFFICE. A COMPLETE COPY IS AVAILABLE AT THE ASSIGNMENT SEARCH ROOM ON THE REEL AND FRAME NUMBER REFERENCED BELOW.

PLEASE REVIEW ALL INFORMATION CONTAINED ON THIS NOTICE. THE INFORMATION CONTAINED ON THIS RECORDATION NOTICE REFLECTS THE DATA PRESENT IN THE PATENT AND TRADEMARK ASSIGNMENT SYSTEM. IF YOU SHOULD FIND ANY ERRORS OR HAVE QUESTIONS CONCERNING THIS NOTICE, YOU MAY CONTACT THE ASSIGNMENT RECORDATION BRANCH AT 571-272-3350. PLEASE SEND REQUEST FOR CORRECTION TO: U.S. PATENT AND TRADEMARK OFFICE, MAIL STOP: ASSIGNMENT RECORDATION BRANCH, P.O. BOX 1450, ALEXANDRIA, VA 22313.

RECORDATION DATE: 11/29/2011 REEL/FRAME: 027296/0115
NUMBER OF PAGES: 18

BRIEF: ASSIGNMENT OF ASSIGNORS INTEREST (SEE DOCUMENT FOR DETAILS).

DOCKET NUMBER: 5367-694PUS-299930

ASSIGNOR:
KASTNER-JUNG, ULRICH DOC DATE: 10/26/2011

ASSIGNOR:
KLEIN, MARKUS DOC DATE: 07/22/2011

ASSIGNOR:
MAES, STAN DOC DATE: 08/02/2011

ASSIGNOR:
SIGL, ROMANA DOC DATE: 08/11/2011

ASSIGNOR:
HAID, ANNETTE DOC DATE: 07/28/2011

ASSIGNOR:
LINTNER, STEPHAN DOC DATE: 07/27/2011

ASSIGNOR:
HERGET, JULIAN DOC DATE: 10/18/2011

Pt. 7684500

SDC EX. 1027 - 251/489

ASSIGNOR:
MATJAN, GREGOR DOC DATE: 07/27/2011

ASSIGNEE:
OSRAM OPTO SEMICONDUCTORS GMBH
LEIBNIZSTRASSE 4
REGENSBURG, GERMANY 93055

APPLICATION NUMBER: 13139514 FILING DATE:
PATENT NUMBER: ISSUE DATE:
TITLE: ORGANIC-LIGHT-EMITTING DIODE AND LUMINAIRE

ASSIGNMENT RECORDATION BRANCH
PUBLIC RECORDS DIVISION

PATENT ASSIGNMENT

Electronic Version v1.1
Stylesheet Version v1.1

SUBMISSION TYPE:	NEW ASSIGNMENT
NATURE OF CONVEYANCE:	ASSIGNMENT

CONVEYING PARTY DATA

Name	Execution Date
Ulrich KASTNER-JUNG	10/26/2011
Markus KLEIN	07/22/2011
Stan MAES	08/02/2011
Romana SIGL	08/11/2011
Annette HAID	07/28/2011
Stephan LINTNER	07/27/2011
Julian HERGET	10/18/2011
Gregor MATJAN	07/27/2011

RECEIVING PARTY DATA

Name:	OSRAM Opto Semiconductors GmbH
Street Address:	Leibnizstrasse 4
City:	Regensburg
State/Country:	GERMANY
Postal Code:	93055

PROPERTY NUMBERS Total: 1

Property Type	Number
Application Number:	13139514

CH $40.00 13139514

CORRESPONDENCE DATA

Fax Number: (212)986-0604
Phone: 2128834932
Email: SMENDEZ@COZEN.COM
Correspondence will be sent to the e-mail address first; if that is unsuccessful, it will be sent via US Mail.
Correspondent Name: Cozen O'Connor
Address Line 1: 277 Park Avenue
Address Line 4: New York, NEW YORK 10172

PATENT ASSIGNMENT

Electronic Version v1.1
Stylesheet Version v1.1

SUBMISSION TYPE:	NEW ASSIGNMENT
NATURE OF CONVEYANCE:	ASSIGNMENT

CONVEYING PARTY DATA

Name	Execution Date
Ulrich KASTNER-JUNG	10/26/2011
Markus KLEIN	07/22/2011
Stan MAES	08/02/2011
Romana SIGL	08/11/2011
Annette HAID	07/28/2011
Stephan LINTNER	07/27/2011
Julian HERGET	10/18/2011
Gregor MATJAN	07/27/2011

RECEIVING PARTY DATA

Name:	OSRAM Opto Semiconductors GmbH
Street Address:	Leibnizstrasse 4
City:	Regensburg
State/Country:	GERMANY
Postal Code:	93055

PROPERTY NUMBERS Total: 1

Property Type	Number
Application Number:	13139514

CH $40.00 13139514

CORRESPONDENCE DATA

Fax Number: (212)986-0604
Phone: 2128834932
Email: SMENDEZ@COZEN.COM
Correspondence will be sent to the e-mail address first; if that is unsuccessful, it will be sent via US Mail.
Correspondent Name: Cozen O'Connor
Address Line 1: 277 Park Avenue
Address Line 4: New York, NEW YORK 10172

Electronic Patent Application Fee Transmittal

Application Number:	
Filing Date:	
Title of Invention:	Organic-Light-Emitting Diode
First Named Inventor/Applicant Name:	Ulrich KASTNER
Filer:	Edward M. Weisz/Evelyn Martinez
Attorney Docket Number:	5367-694P/CON2-474410

Filed as Large Entity

Filing Fees for Utility under 35 USC 111(a)

Description	Fee Code	Quantity	Amount	Sub-Total in USD($)
Basic Filing:				
UTILITY APPLICATION FILING	1011	1	300	300
UTILITY SEARCH FEE	1111	1	660	660
UTILITY EXAMINATION FEE	1311	1	760	760
Pages:				
UTILITY APPL SIZE FEE PER 50 SHEETS >100	1081	2	400	800
Claims:				
Miscellaneous-Filing:				
Petition:				

Description	Fee Code	Quantity	Amount	Sub-Total in USD($)
Patent-Appeals-and-Interference:				
Post-Allowance-and-Post-Issuance:				
Extension-of-Time:				
Miscellaneous:				
		Total in USD ($)		**2520**

Electronic Acknowledgement Receipt

EFS ID:	38583034
Application Number:	16790198
International Application Number:	
Confirmation Number:	1309
Title of Invention:	Organic-Light-Emitting Diode
First Named Inventor/Applicant Name:	Ulrich KASTNER
Customer Number:	27799
Filer:	Edward M. Weisz/Evelyn Martinez
Filer Authorized By:	Edward M. Weisz
Attorney Docket Number:	5367-694P/CON2-474410
Receipt Date:	13-FEB-2020
Filing Date:	
Time Stamp:	16:11:59
Application Type:	Utility under 35 USC 111(a)

Payment information:

Submitted with Payment	yes
Payment Type	CARD
Payment was successfully received in RAM	$2520
RAM confirmation Number	E20202CG12242767
Deposit Account	
Authorized User	

The Director of the USPTO is hereby authorized to charge indicated fees and credit any overpayment as follows:

File Listing:

Document Number	Document Description	File Name	File Size(Bytes)/ Message Digest	Multi Part /.zip	Pages (if appl.)
1	Transmittal of New Application	tra.pdf	40226 af6cd58323aa053b89757cc8b7b0088272c8a2a6	no	3
Warnings:					
Information:					
2	Application Data Sheet	ADS.pdf	94563 cf191743466b27858e19c7bb16bee0940fd518d8	no	7
Warnings:					
Information:					
This is not an USPTO supplied ADS fillable form					
3	Oath or Declaration filed	Declaration.pdf	956009 7a0b85e5a5cba99f5340aa974306a1039c42b6fd	no	8
Warnings:					
Information:					
4	Specification	spec.pdf	730783 b2ee161013122f6367297550338c0eb22116110a	no	159
Warnings:					
Information:					
5	Drawings-only black and white line drawings	Drawings.pdf	2954238 e61e6ac900c2f58f7d3b7dc2ecb88773b2d8dbfd	no	60
Warnings:					
Information:					
6	Information Disclosure Statement (IDS) Form (SB08)	IDS.pdf	648795 2338a86b10ca5a12b522c127d46d6e12ab4245af	no	6
Warnings:					

Information:					
This is not an USPTO supplied IDS fillable form					
7	Assignee showing of ownership per 37 CFR 3.73	Assignment.pdf	712406 e19d28622b184ab4be2b4e2b3c2bb7ce368b913f	no	11
Warnings:					
Information:					
8	Fee Worksheet (SB06)	fee-info.pdf	37036 2d120620e9328dcfd24e9886e30ee58efe20fb35	no	2
Warnings:					
Information:					
			Total Files Size (in bytes):	6174056	

This Acknowledgement Receipt evidences receipt on the noted date by the USPTO of the indicated documents, characterized by the applicant, and including page counts, where applicable. It serves as evidence of receipt similar to a Post Card, as described in MPEP 503.

New Applications Under 35 U.S.C. 111

If a new application is being filed and the application includes the necessary components for a filing date (see 37 CFR 1.53(b)-(d) and MPEP 506), a Filing Receipt (37 CFR 1.54) will be issued in due course and the date shown on this Acknowledgement Receipt will establish the filing date of the application.

National Stage of an International Application under 35 U.S.C. 371

If a timely submission to enter the national stage of an international application is compliant with the conditions of 35 U.S.C. 371 and other applicable requirements a Form PCT/DO/EO/903 indicating acceptance of the application as a national stage submission under 35 U.S.C. 371 will be issued in addition to the Filing Receipt, in due course.

New International Application Filed with the USPTO as a Receiving Office

If a new international application is being filed and the international application includes the necessary components for an international filing date (see PCT Article 11 and MPEP 1810), a Notification of the International Application Number and of the International Filing Date (Form PCT/RO/105) will be issued in due course, subject to prescriptions concerning national security, and the date shown on this Acknowledgement Receipt will establish the international filing date of the application.

Doc Code: PA..
Document Description: Power of Attorney

PTO/AIA/82A (07-13)
Approved for use through 11/30/2014. OMB 0651-0051
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

TRANSMITTAL FOR POWER OF ATTORNEY TO ONE OR MORE REGISTERED PRACTITIONERS

NOTE: This form is to be submitted with the Power of Attorney by Applicant form (PTO/AIA/82B) to identify the application to which the Power of Attorney is directed, in accordance with 37 CFR 1.5, unless the application number and filing date are identified in the Power of Attorney by Applicant form. If neither form PTO/AIA/82A nor form PTO/AIA82B identifies the application to which the Power of Attorney is directed, the Power of Attorney will not be recognized in the application.

Application Number	16/790,198
Filing Date	February 13, 2020
First Named Inventor	Ulrich KASTNER
Title	Organic Light Emitting Diode
Art Unit	
Examiner Name	
Attorney Docket Number	5367-694PCON2/474410

SIGNATURE of Applicant or Patent Practitioner

Signature	/Edward M. Weisz/	Date (Optional)	
Name	Edward M. Weisz	Registration Number	37,257
Title (if Applicant is a juristic entity)			
Applicant Name (if Applicant is a juristic entity)			

NOTE: This form must be signed in accordance with 37 CFR 1.33. See 37 CFR 1.4(d) for signature requirements and certifications. If more than one applicant, use multiple forms.

☐ *Total of _____ forms are submitted.

This collection of information is required by 37 CFR 1.131, 1.32, and 1.33. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.11 and 1.14. This collection is estimated to take 3 minutes to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.**

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

PTO/AIA/80 (07-12)
Approved for use through 11/30/2014. OMB 0651-0035
U.S. Patent and Trademark Office; U.S DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

POWER OF ATTORNEY TO PROSECUTE APPLICATIONS BEFORE THE USPTO

I hereby revoke all previous powers of attorney given in the application identified in the attached statement under 37 CFR 3.73(c).

I hereby appoint:

■ Practitioners associated with Customer Number: 27799

OR

☐ Practitioner(s) named below (if more than ten patent practitioners are to be named, then a customer number must be used):

Name	Registration Number	Name	Registration Number

As attorney(s) or agent(s) to represent the undersigned before the United States Patent and Trademark Office (USPTO) in connection with any and all patent applications assigned only to the undersigned according to the USPTO assignment records or assignments documents attached to this form in accordance with 37 CFR 3.73(c).

Please change the correspondence address for the application identified in the attached statement under 37 CFR 3.73(c) to:

☐ The address associated with Customer Number:

OR

☐	Firm or Individual Name			
	Address			
	City		State	Zip
	Country			
	Telephone		Email	

Assignee Name and Address: OSRAM OLED GmbH
Leibnizstrasse 4
Regensburg, Germany 93055

A copy of this form, together with a statement under 37 CFR 3.73(c) (Form PTO/AIA/96 or equivalent) is required to be filed in each application in which this form is used. The statement under 37 CFR 3.73(c) may be completed by one of the practitioners appointed in this form, and must identify the application in which this Power of Attorney is to be filed.

SIGNATURE of Assignee of Record
The individual whose signature and title is supplied below is authorized to act on behalf of the assignee

Signature	ppa K Diekmann	Date	12.10.2017
Name	Dr. Marc Lünnemann Dr. Karsten Diekmann	Telephone	
Title	CEO		

This collection of information is required by 37 CFR 1.31, 1.32 and 1.33. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.11 and 1.14. This collection is estimated to take 3 minutes to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.**

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

Electronic Acknowledgement Receipt

EFS ID:	38588958
Application Number:	16790198
International Application Number:	
Confirmation Number:	1309
Title of Invention:	Organic-Light-Emitting Diode
First Named Inventor/Applicant Name:	Ulrich KASTNER
Customer Number:	27799
Filer:	Edward M. Weisz/Evelyn Martinez
Filer Authorized By:	Edward M. Weisz
Attorney Docket Number:	5367-694P/CON2-474410
Receipt Date:	14-FEB-2020
Filing Date:	
Time Stamp:	10:45:55
Application Type:	Utility under 35 USC 111(a)

Payment information:

Submitted with Payment	no

File Listing:

Document Number	Document Description	File Name	File Size(Bytes)/ Message Digest	Multi Part /.zip	Pages (if appl.)
1	Power of Attorney	POA.pdf	204495 c89de2d71bf915e12dfcf07577e890d7766b7cb9	no	2

Warnings:

Information:	
Total Files Size (in bytes):	204495

This Acknowledgement Receipt evidences receipt on the noted date by the USPTO of the indicated documents, characterized by the applicant, and including page counts, where applicable. It serves as evidence of receipt similar to a Post Card, as described in MPEP 503.

New Applications Under 35 U.S.C. 111

If a new application is being filed and the application includes the necessary components for a filing date (see 37 CFR 1.53(b)-(d) and MPEP 506), a Filing Receipt (37 CFR 1.54) will be issued in due course and the date shown on this Acknowledgement Receipt will establish the filing date of the application.

National Stage of an International Application under 35 U.S.C. 371

If a timely submission to enter the national stage of an international application is compliant with the conditions of 35 U.S.C. 371 and other applicable requirements a Form PCT/DO/EO/903 indicating acceptance of the application as a national stage submission under 35 U.S.C. 371 will be issued in addition to the Filing Receipt, in due course.

New International Application Filed with the USPTO as a Receiving Office

If a new international application is being filed and the international application includes the necessary components for an international filing date (see PCT Article 11 and MPEP 1810), a Notification of the International Application Number and of the International Filing Date (Form PCT/RO/105) will be issued in due course, subject to prescriptions concerning national security, and the date shown on this Acknowledgement Receipt will establish the international filing date of the application.

UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NUMBER	FILING or 371(c) DATE	GRP ART UNIT	FIL FEE REC'D	ATTY.DOCKET.NO	TOT CLAIMS	IND CLAIMS
16/790,198	02/13/2020	2811	2520	5367-694PCON2\474410	13	2

CONFIRMATION NO. 1309

27799
COZEN O'CONNOR
277 PARK AVENUE , 20TH FLOOR
NEW YORK, NY 10172

FILING RECEIPT

OC000000115126813

Date Mailed: 03/04/2020

Receipt is acknowledged of this non-provisional utility patent application. The application will be taken up for examination in due course. Applicant will be notified as to the results of the examination. Any correspondence concerning the application must include the following identification information: the U.S. APPLICATION NUMBER, FILING DATE, NAME OF FIRST INVENTOR, and TITLE OF INVENTION. Fees transmitted by check or draft are subject to collection.

Please verify the accuracy of the data presented on this receipt. If an error is noted on this Filing Receipt, please submit a written request for a corrected Filing Receipt, including a properly marked-up ADS showing the changes with strike-through for deletions and underlining for additions. If you received a "Notice to File Missing Parts" or other Notice requiring a response for this application, please submit any request for correction to this Filing Receipt with your reply to the Notice. When the USPTO processes the reply to the Notice, the USPTO will generate another Filing Receipt incorporating the requested corrections provided that the request is grantable.

Inventor(s)

Ulrich KASTNER-JUNG, Munich, GERMANY;
Markus KLEIN, Tegernheim, GERMANY;
Stan MAES, Dilsen-Stokken, BELGIUM;
Romana SIGL, Salzburg, AUSTRIA;
Annette HAID, Salzburg, AUSTRIA;
Stephan LINTNER, Salzburg, AUSTRIA;
Julian HERGET, Marktschellenberg, GERMANY;
Gregor MATJAN, Bergheim, AUSTRIA;

Applicant(s)

OSRAM OLED GmbH, Regensburg, GERMANY;

Power of Attorney: The patent practitioners associated with Customer Number 27799

Domestic Priority data as claimed by applicant

This application is a CON of 15/651,508 07/17/2017
which is a CON of 13/139,514 01/03/2012 PAT 9797567
which is a 371 of PCT/DE2009/001741 12/09/2009

Foreign Applications (You may be eligible to benefit from the **Patent Prosecution Highway** program at the USPTO. Please see http://www.uspto.gov for more information.)
GERMANY 10 2008 061 563.3 12/11/2008

SDC EX. 1027 - 264/489

Permission to Access Application via Priority Document Exchange: No

Permission to Access Search Results: No

Applicant may provide or rescind an authorization for access using Form PTO/SB/39 or Form PTO/SB/69 as appropriate.

If Required, Foreign Filing License Granted: 02/28/2020

The country code and number of your priority application, to be used for filing abroad under the Paris Convention, is **US 16/790,198**

Projected Publication Date: 06/11/2020

Non-Publication Request: No

Early Publication Request: No

Title

Organic-Light-Emitting Diode

Preliminary Class

257

Statement under 37 CFR 1.55 or 1.78 for AIA (First Inventor to File) Transition Applications: No

PROTECTING YOUR INVENTION OUTSIDE THE UNITED STATES

Since the rights granted by a U.S. patent extend only throughout the territory of the United States and have no effect in a foreign country, an inventor who wishes patent protection in another country must apply for a patent in a specific country or in regional patent offices. Applicants may wish to consider the filing of an international application under the Patent Cooperation Treaty (PCT). An international (PCT) application generally has the same effect as a regular national patent application in each PCT-member country. The PCT process **simplifies** the filing of patent applications on the same invention in member countries, but **does not result** in a grant of "an international patent" and does not eliminate the need of applicants to file additional documents and fees in countries where patent protection is desired.

Almost every country has its own patent law, and a person desiring a patent in a particular country must make an application for patent in that country in accordance with its particular laws. Since the laws of many countries differ in various respects from the patent law of the United States, applicants are advised to seek guidance from specific foreign countries to ensure that patent rights are not lost prematurely.

Applicants also are advised that in the case of inventions made in the United States, the Director of the USPTO must issue a license before applicants can apply for a patent in a foreign country. The filing of a U.S. patent application serves as a request for a foreign filing license. The application's filing receipt contains further information and guidance as to the status of applicant's license for foreign filing.

Applicants may wish to consult the USPTO booklet, "General Information Concerning Patents" (specifically, the section entitled "Treaties and Foreign Patents") for more information on timeframes and deadlines for filing foreign patent applications. The guide is available either by contacting the USPTO Contact Center at 800-786-9199, or it can be viewed on the USPTO website at http://www.uspto.gov/web/offices/pac/doc/general/index.html.

For information on preventing theft of your intellectual property (patents, trademarks and copyrights), you may wish to consult the U.S. Government website, http://www.stopfakes.gov. Part of a Department of Commerce initiative, this website includes self-help "toolkits" giving innovators guidance on how to protect intellectual property in specific countries such as China, Korea and Mexico. For questions regarding patent enforcement issues, applicants may call the U.S. Government hotline at 1-866-999-HALT (1-866-999-4258).

LICENSE FOR FOREIGN FILING UNDER

Title 35, United States Code, Section 184

Title 37, Code of Federal Regulations, 5.11 & 5.15

GRANTED

The applicant has been granted a license under 35 U.S.C. 184, if the phrase "IF REQUIRED, FOREIGN FILING LICENSE GRANTED" followed by a date appears on this form. Such licenses are issued in all applications where the conditions for issuance of a license have been met, regardless of whether or not a license may be required as set forth in 37 CFR 5.15. The scope and limitations of this license are set forth in 37 CFR 5.15(a) unless an earlier license has been issued under 37 CFR 5.15(b). The license is subject to revocation upon written notification. The date indicated is the effective date of the license, unless an earlier license of similar scope has been granted under 37 CFR 5.13 or 5.14.

This license is to be retained by the licensee and may be used at any time on or after the effective date thereof unless it is revoked. This license is automatically transferred to any related applications(s) filed under 37 CFR 1.53(d). This license is not retroactive.

The grant of a license does not in any way lessen the responsibility of a licensee for the security of the subject matter as imposed by any Government contract or the provisions of existing laws relating to espionage and the national security or the export of technical data. Licensees should apprise themselves of current regulations especially with respect to certain countries, of other agencies, particularly the Office of Defense Trade Controls, Department of State (with respect to Arms, Munitions and Implements of War (22 CFR 121-128)); the Bureau of Industry and Security, Department of Commerce (15 CFR parts 730-774); the Office of Foreign AssetsControl, Department of Treasury (31 CFR Parts 500+) and the Department of Energy.

NOT GRANTED

No license under 35 U.S.C. 184 has been granted at this time, if the phrase "IF REQUIRED, FOREIGN FILING LICENSE GRANTED" DOES NOT appear on this form. Applicant may still petition for a license under 37 CFR 5.12, if a license is desired before the expiration of 6 months from the filing date of the application. If 6 months has lapsed from the filing date of this application and the licensee has not received any indication of a secrecy order under 35 U.S.C. 181, the licensee may foreign file the application pursuant to 37 CFR 5.15(b).

SelectUSA

The United States represents the largest, most dynamic marketplace in the world and is an unparalleled location for business investment, innovation, and commercialization of new technologies. The U.S. offers tremendous resources and advantages for those who invest and manufacture goods here. Through SelectUSA, our nation works to promote and facilitate business investment. SelectUSA provides information assistance to the international investor

community; serves as an ombudsman for existing and potential investors; advocates on behalf of U.S. cities, states, and regions competing for global investment; and counsels U.S. economic development organizations on investment attraction best practices. To learn more about why the United States is the best country in the world to develop technology, manufacture products, deliver services, and grow your business, visit http://www.SelectUSA.gov or call +1-202-482-6800.

PATENT APPLICATION FEE DETERMINATION RECORD

Substitute for Form PTO-875

Application or Docket Number: 16/790,198

APPLICATION AS FILED - PART I

FOR	(Column 1) NUMBER FILED	(Column 2) NUMBER EXTRA	SMALL ENTITY RATE($)	SMALL ENTITY FEE($)	OR	OTHER THAN SMALL ENTITY RATE($)	OTHER THAN SMALL ENTITY FEE($)
BASIC FEE (37 CFR 1.16(a), (b), or (c))	N/A	N/A	N/A			N/A	300
SEARCH FEE (37 CFR 1.16(k), (i), or (m))	N/A	N/A	N/A			N/A	660
EXAMINATION FEE (37 CFR 1.16(o), (p), or (q))	N/A	N/A	N/A			N/A	760
TOTAL CLAIMS (37 CFR 1.16(i))	13 minus 20 =	*			OR	x 100 =	0.00
INDEPENDENT CLAIMS (37 CFR 1.16(h))	2 minus 3 =	*				x 460 =	0.00
APPLICATION SIZE FEE (37 CFR 1.16(s))	If the specification and drawings exceed 100 sheets of paper, the application size fee due is $310 ($155 for small entity) for each additional 50 sheets or fraction thereof. See 35 U.S.C. 41(a)(1)(G) and 37 CFR 1.16(s).						800
MULTIPLE DEPENDENT CLAIM PRESENT (37 CFR 1.16(j))							0.00
* If the difference in column 1 is less than zero, enter "0" in column 2.			TOTAL			TOTAL	2520

APPLICATION AS AMENDED - PART II

		(Column 1) CLAIMS REMAINING AFTER AMENDMENT		(Column 2) HIGHEST NUMBER PREVIOUSLY PAID FOR	(Column 3) PRESENT EXTRA	SMALL ENTITY RATE($)	SMALL ENTITY ADDITIONAL FEE($)	OR	OTHER THAN SMALL ENTITY RATE($)	OTHER THAN SMALL ENTITY ADDITIONAL FEE($)
AMENDMENT A	Total (37 CFR 1.16(i))	*	Minus	**	=	x =		OR	x =	
	Independent (37 CFR 1.16(h))	*	Minus	***	=	x =		OR	x =	
	Application Size Fee (37 CFR 1.16(s))									
	FIRST PRESENTATION OF MULTIPLE DEPENDENT CLAIM (37 CFR 1.16(j))							OR		
						TOTAL ADD'L FEE		OR	TOTAL ADD'L FEE	

		(Column 1) CLAIMS REMAINING AFTER AMENDMENT		(Column 2) HIGHEST NUMBER PREVIOUSLY PAID FOR	(Column 3) PRESENT EXTRA	SMALL ENTITY RATE($)	SMALL ENTITY ADDITIONAL FEE($)	OR	OTHER THAN SMALL ENTITY RATE($)	OTHER THAN SMALL ENTITY ADDITIONAL FEE($)
AMENDMENT B	Total (37 CFR 1.16(i))	*	Minus	**	=	x =		OR	x =	
	Independent (37 CFR 1.16(h))	*	Minus	***	=	x =		OR	x =	
	Application Size Fee (37 CFR 1.16(s))									
	FIRST PRESENTATION OF MULTIPLE DEPENDENT CLAIM (37 CFR 1.16(j))							OR		
						TOTAL ADD'L FEE		OR	TOTAL ADD'L FEE	

* If the entry in column 1 is less than the entry in column 2, write "0" in column 3.

** If the "Highest Number Previously Paid For" IN THIS SPACE is less than 20, enter "20".

*** If the "Highest Number Previously Paid For" IN THIS SPACE is less than 3, enter "3".

The "Highest Number Previously Paid For" (Total or Independent) is the highest found in the appropriate box in column 1.

UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NUMBER	FILING OR 371(C) DATE	FIRST NAMED APPLICANT	ATTY. DOCKET NO./TITLE
16/790,198	02/13/2020	Ulrich KASTNER-JUNG	5367-694PCON2\474410

CONFIRMATION NO. 1309

27799
COZEN O'CONNOR
277 PARK AVENUE , 20TH FLOOR
NEW YORK, NY 10172

FORMALITIES LETTER

OC000000115120614

Date Mailed: 03/04/2020

NOTICE TO FILE MISSING PARTS OF NONPROVISIONAL APPLICATION

FILED UNDER 37 CFR 1.53(b)

Filing Date Granted

Items Required To Avoid Abandonment:

An application number and filing date have been accorded to this application. The item(s) indicated below, however, are missing.

Applicant is given **TWO MONTHS** from the date of this Notice within which to file all required items below to avoid abandonment. Extensions of time may be obtained by filing a petition accompanied by the extension fee under the provisions of 37 CFR 1.136(a).

- Surcharge as set forth in 37 CFR 1.16(f) must be submitted.
  The surcharge is due for any one of:
  - late submission of the basic filing fee, search fee, or examination fee,
  - late submission of inventor's oath or declaration,
  - filing an application that does not contain at least one claim on filing, or
  - submission of an application filed by reference to a previously filed application.

SUMMARY OF FEES DUE:

The fee(s) required within **TWO MONTHS** from the date of this Notice to avoid abandonment is/are itemized below. No entity status discount is in effect. If applicant is qualified for small entity status, a written assertion of small entity status must be submitted to establish small entity status. (See 37 CFR 1.27). If applicant is qualified for micro entity status, an acceptable Certification of Micro Entity Status must be submitted to establish micro entity status. (See 37 CFR 1.29 and forms PTO/SB/15A and 15B.)

- $ **160** surcharge.
- $(**0**) previous unapplied payment amount.
- $ **160** TOTAL FEE BALANCE DUE.

Items Required To Avoid Processing Delays:

Applicant is notified that the above-identified application contains the deficiencies noted below. No period for reply is set forth in this notice for correction of these deficiencies. However, if a deficiency relates to the inventor's oath or declaration, the applicant must file an oath or declaration in compliance with 37 CFR 1.63, or a substitute statement in compliance with 37 CFR 1.64, executed by or with respect to each actual inventor no later than the expiration of the time period set in the "Notice of Allowability" to avoid abandonment. See 37 CFR 1.53(f).

- A properly executed inventor's oath or declaration has not been received for the following inventor(s) *as named on the application data sheet:*

  Stephan LINTNER

  An inventor's oath or declaration in compliance with 37 CFR 1.63 or 1.64 executed by or with respect to each inventor must be submitted no later than the date on which the issue fee is paid in response to a notice requiring such fee. See 37 CFR 1.53(f).

  If the name of the inventor provided on the ADS is not correct, applicant must submit a request to correct the inventor name according to 37 CFR 1.48(f), accompanied by the appropriate fee under 37 CFR 1.17(i) and a corrected ADS in compliance with 37 CFR 1.76(c), i.e., identifying the information that is being changed with underlining for insertions, and strike-through or brackets for text removed.

Replies must be received in the USPTO within the set time period or must include a proper Certificate of Mailing or Transmission under 37 CFR 1.8 with a mailing or transmission date within the set time period. For more information and a suggested format, see Form PTO/SB/92 and MPEP 512.

Replies should be mailed to:

Mail Stop Missing Parts
Commissioner for Patents
P.O. Box 1450
Alexandria VA 22313-1450

Registered users of EFS-Web may alternatively submit their reply to this notice via EFS-Web, including a copy of this Notice and selecting the document description "Applicant response to Pre-Exam Formalities Notice". https://sportal.uspto.gov/authenticate/AuthenticateUserLocalEPF.html

For more information about EFS-Web please call the USPTO Electronic Business Center at 1-866-217-9197 or visit our website at http://www.uspto.gov/ebc.

If you are not using EFS-Web to submit your reply, you must include a copy of this notice.

Questions about the contents of this notice and the requirements it sets forth should be directed to the Office of Data Management, Application Assistance Unit, at **(571) 272-4000** or **(571) 272-4200** or **1-888-786-0101**.

/qtran/

Electronic Patent Application Fee Transmittal

Application Number:	16790198
Filing Date:	13-Feb-2020
Title of Invention:	Organic-Light-Emitting Diode
First Named Inventor/Applicant Name:	Ulrich KASTNER-JUNG
Filer:	Edward M. Weisz/Evelyn Martinez
Attorney Docket Number:	5367-694PCON2\474410

Filed as Large Entity

Filing Fees for Utility under 35 USC 111(a)

Description	Fee Code	Quantity	Amount	Sub-Total in USD($)
Basic Filing:				
Pages:				
Claims:				
Miscellaneous-Filing:				
LATE FILING FEE FOR OATH OR DECLARATION	1051	1	160	160
Petition:				
Patent-Appeals-and-Interference:				
Post-Allowance-and-Post-Issuance:				

Description	Fee Code	Quantity	Amount	Sub-Total in USD($)
Extension-of-Time:				
Miscellaneous:				
			Total in USD ($)	**160**

Electronic Acknowledgement Receipt

EFS ID:	39233647
Application Number:	16790198
International Application Number:	
Confirmation Number:	1309
Title of Invention:	Organic-Light-Emitting Diode
First Named Inventor/Applicant Name:	Ulrich KASTNER-JUNG
Customer Number:	27799
Filer:	Edward M. Weisz/Evelyn Martinez
Filer Authorized By:	Edward M. Weisz
Attorney Docket Number:	5367-694PCON2\474410
Receipt Date:	22-APR-2020
Filing Date:	13-FEB-2020
Time Stamp:	15:32:26
Application Type:	Utility under 35 USC 111(a)

Payment information:

Submitted with Payment	yes
Payment Type	CARD
Payment was successfully received in RAM	$160
RAM confirmation Number	E20204LF32558315
Deposit Account	
Authorized User	

The Director of the USPTO is hereby authorized to charge indicated fees and credit any overpayment as follows:

File Listing:

Document Number	Document Description	File Name	File Size(Bytes)/ Message Digest	Multi Part /.zip	Pages (if appl.)
1	Fee Worksheet (SB06)	fee-info.pdf	30816 5f4ad0a1c4bf34dd857e26cdf581860fece10f07	no	2

Warnings:

Information:

Total Files Size (in bytes):	30816

This Acknowledgement Receipt evidences receipt on the noted date by the USPTO of the indicated documents, characterized by the applicant, and including page counts, where applicable. It serves as evidence of receipt similar to a Post Card, as described in MPEP 503.

New Applications Under 35 U.S.C. 111

If a new application is being filed and the application includes the necessary components for a filing date (see 37 CFR 1.53(b)-(d) and MPEP 506), a Filing Receipt (37 CFR 1.54) will be issued in due course and the date shown on this Acknowledgement Receipt will establish the filing date of the application.

National Stage of an International Application under 35 U.S.C. 371

If a timely submission to enter the national stage of an international application is compliant with the conditions of 35 U.S.C. 371 and other applicable requirements a Form PCT/DO/EO/903 indicating acceptance of the application as a national stage submission under 35 U.S.C. 371 will be issued in addition to the Filing Receipt, in due course.

New International Application Filed with the USPTO as a Receiving Office

If a new international application is being filed and the international application includes the necessary components for an international filing date (see PCT Article 11 and MPEP 1810), a Notification of the International Application Number and of the International Filing Date (Form PCT/RO/105) will be issued in due course, subject to prescriptions concerning national security, and the date shown on this Acknowledgement Receipt will establish the international filing date of the application.

PTO/AIA/01 (08-13)
Approved for use through 11/30/2020. OMB 0651-0032
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

DECLARATION (37 CFR 1.63) FOR UTILITY OR DESIGN APPLICATION USING AN APPLICATION DATA SHEET (37 CFR 1.76)

Title of Invention	Organic-Light-Emitting Diode

As the below named inventor, I hereby declare that:

This declaration is directed to:

- ☐ The attached application, or
- ■ United States application or PCT international application number 16/790,198 filed on February 13, 2020

The above-identified application was made or authorized to be made by me.

I believe that I am the original inventor or an original joint inventor of a claimed invention in the application.

I hereby acknowledge that any willful false statement made in this declaration is punishable under 18 U.S.C. 1001 by fine or imprisonment of not more than five (5) years, or both.

WARNING:

Petitioner/applicant is cautioned to avoid submitting personal information in documents filed in a patent application that may contribute to identity theft. Personal information such as social security numbers, bank account numbers, or credit card numbers (other than a check or credit card authorization form PTO-2038 submitted for payment purposes) is never required by the USPTO to support a petition or an application. If this type of personal information is included in documents submitted to the USPTO, petitioners/applicants should consider redacting such personal information from the documents before submitting them to the USPTO. Petitioner/applicant is advised that the record of a patent application is available to the public after publication of the application (unless a non-publication request in compliance with 37 CFR 1.213(a) is made in the application) or issuance of a patent. Furthermore, the record from an abandoned application may also be available to the public if the application is referenced in a published application or an issued patent (see 37 CFR 1.14). Checks and credit card authorization forms PTO-2038 submitted for payment purposes are not retained in the application file and therefore are not publicly available.

LEGAL NAME OF INVENTOR

Inventor: Stephan LINTNER Date (Optional): 28th April 2020

Signature: Stephan Lintner

Note: An application data sheet (PTO/SB/14 or equivalent), including naming the entire inventive entity, must accompany this form or must have been previously filed. Use an additional PTO/AIA/01 form for each additional inventor.

This collection of information is required by 35 U.S.C. 115 and 37 CFR 1.63. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.11 and 1.14. This collection is estimated to take 1 minute to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing the burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.**

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

Electronic Acknowledgement Receipt

EFS ID:	39324893
Application Number:	16790198
International Application Number:	
Confirmation Number:	1309
Title of Invention:	Organic-Light-Emitting Diode
First Named Inventor/Applicant Name:	Ulrich KASTNER-JUNG
Customer Number:	27799
Filer:	Edward M. Weisz/Evelyn Martinez
Filer Authorized By:	Edward M. Weisz
Attorney Docket Number:	5367-694PCON2\474410
Receipt Date:	01-MAY-2020
Filing Date:	13-FEB-2020
Time Stamp:	11:19:35
Application Type:	Utility under 35 USC 111(a)

Payment information:

Submitted with Payment	no

File Listing:

Document Number	Document Description	File Name	File Size(Bytes)/ Message Digest	Multi Part /.zip	Pages (if appl.)
1	Oath or Declaration filed	patent001.pdf	532970 c5123bdbddb067b9df2327c1206fb796e6010cd6	no	1

Warnings:

Information:	
Total Files Size (in bytes):	532970

This Acknowledgement Receipt evidences receipt on the noted date by the USPTO of the indicated documents, characterized by the applicant, and including page counts, where applicable. It serves as evidence of receipt similar to a Post Card, as described in MPEP 503.

New Applications Under 35 U.S.C. 111

If a new application is being filed and the application includes the necessary components for a filing date (see 37 CFR 1.53(b)-(d) and MPEP 506), a Filing Receipt (37 CFR 1.54) will be issued in due course and the date shown on this Acknowledgement Receipt will establish the filing date of the application.

National Stage of an International Application under 35 U.S.C. 371

If a timely submission to enter the national stage of an international application is compliant with the conditions of 35 U.S.C. 371 and other applicable requirements a Form PCT/DO/EO/903 indicating acceptance of the application as a national stage submission under 35 U.S.C. 371 will be issued in addition to the Filing Receipt, in due course.

New International Application Filed with the USPTO as a Receiving Office

If a new international application is being filed and the international application includes the necessary components for an international filing date (see PCT Article 11 and MPEP 1810), a Notification of the International Application Number and of the International Filing Date (Form PCT/RO/105) will be issued in due course, subject to prescriptions concerning national security, and the date shown on this Acknowledgement Receipt will establish the international filing date of the application.

PATENT APPLICATION FEE DETERMINATION RECORD

Substitute for Form PTO-875

Application or Docket Number: 16/790,198

APPLICATION AS FILED - PART I

FOR	(Column 1) NUMBER FILED	(Column 2) NUMBER EXTRA	SMALL ENTITY RATE($)	SMALL ENTITY FEE($)	OR	OTHER THAN SMALL ENTITY RATE($)	OTHER THAN SMALL ENTITY FEE($)
BASIC FEE (37 CFR 1.16(a), (b), or (c))	N/A	N/A	N/A			N/A	300
SEARCH FEE (37 CFR 1.16(k), (i), or (m))	N/A	N/A	N/A			N/A	660
EXAMINATION FEE (37 CFR 1.16(o), (p), or (q))	N/A	N/A	N/A			N/A	760
TOTAL CLAIMS (37 CFR 1.16(i))	13 minus 20 =	*			OR	x 100 =	0.00
INDEPENDENT CLAIMS (37 CFR 1.16(h))	2 minus 3 =	*				x 460 =	0.00
APPLICATION SIZE FEE (37 CFR 1.16(s))	If the specification and drawings exceed 100 sheets of paper, the application size fee due is $310 ($155 for small entity) for each additional 50 sheets or fraction thereof. See 35 U.S.C. 41(a)(1)(G) and 37 CFR 1.16(s).						800
MULTIPLE DEPENDENT CLAIM PRESENT (37 CFR 1.16(j))							0.00
* If the difference in column 1 is less than zero, enter "0" in column 2.			TOTAL			TOTAL	2520

APPLICATION AS AMENDED - PART II

		(Column 1) CLAIMS REMAINING AFTER AMENDMENT		(Column 2) HIGHEST NUMBER PREVIOUSLY PAID FOR	(Column 3) PRESENT EXTRA	SMALL ENTITY RATE($)	SMALL ENTITY ADDITIONAL FEE($)	OR	OTHER THAN SMALL ENTITY RATE($)	OTHER THAN SMALL ENTITY ADDITIONAL FEE($)
AMENDMENT A	Total (37 CFR 1.16(i))	*	Minus	**	=	x =		OR	x =	
	Independent (37 CFR 1.16(h))	*	Minus	***	=	x =		OR	x =	
	Application Size Fee (37 CFR 1.16(s))									
	FIRST PRESENTATION OF MULTIPLE DEPENDENT CLAIM (37 CFR 1.16(j))							OR		
						TOTAL ADD'L FEE		OR	TOTAL ADD'L FEE	

		(Column 1) CLAIMS REMAINING AFTER AMENDMENT		(Column 2) HIGHEST NUMBER PREVIOUSLY PAID FOR	(Column 3) PRESENT EXTRA	SMALL ENTITY RATE($)	SMALL ENTITY ADDITIONAL FEE($)	OR	OTHER THAN SMALL ENTITY RATE($)	OTHER THAN SMALL ENTITY ADDITIONAL FEE($)
AMENDMENT B	Total (37 CFR 1.16(i))	*	Minus	**	=	x =		OR	x =	
	Independent (37 CFR 1.16(h))	*	Minus	***	=	x =		OR	x =	
	Application Size Fee (37 CFR 1.16(s))									
	FIRST PRESENTATION OF MULTIPLE DEPENDENT CLAIM (37 CFR 1.16(j))							OR		
						TOTAL ADD'L FEE		OR	TOTAL ADD'L FEE	

* If the entry in column 1 is less than the entry in column 2, write "0" in column 3.

** If the "Highest Number Previously Paid For" IN THIS SPACE is less than 20, enter "20".

*** If the "Highest Number Previously Paid For" IN THIS SPACE is less than 3, enter "3".

The "Highest Number Previously Paid For" (Total or Independent) is the highest found in the appropriate box in column 1.

UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NUMBER	FILING or 371(c) DATE	GRP ART UNIT	FIL FEE REC'D	ATTY.DOCKET.NO	TOT CLAIMS	IND CLAIMS
16/790,198	02/13/2020	2844	2680	5367-694PCON2\474410	13	2

CONFIRMATION NO. 1309

UPDATED FILING RECEIPT

27799
COZEN O'CONNOR
277 PARK AVENUE , 20TH FLOOR
NEW YORK, NY 10172

OC000000118730130

Date Mailed: 05/05/2020

Receipt is acknowledged of this non-provisional utility patent application. The application will be taken up for examination in due course. Applicant will be notified as to the results of the examination. Any correspondence concerning the application must include the following identification information: the U.S. APPLICATION NUMBER, FILING DATE, NAME OF FIRST INVENTOR, and TITLE OF INVENTION. Fees transmitted by check or draft are subject to collection.

Please verify the accuracy of the data presented on this receipt. If an error is noted on this Filing Receipt, please submit a written request for a corrected Filing Receipt, including a properly marked-up ADS showing the changes with strike-through for deletions and underlining for additions. If you received a "Notice to File Missing Parts" or other Notice requiring a response for this application, please submit any request for correction to this Filing Receipt with your reply to the Notice. When the USPTO processes the reply to the Notice, the USPTO will generate another Filing Receipt incorporating the requested corrections provided that the request is grantable.

Inventor(s)

Ulrich KASTNER-JUNG, Munich, GERMANY;
Markus KLEIN, Tegernheim, GERMANY;
Stan MAES, Dilsen-Stokken, BELGIUM;
Romana SIGL, Salzburg, AUSTRIA;
Annette HAID, Salzburg, AUSTRIA;
Stephan LINTNER, Salzburg, AUSTRIA;
Julian HERGET, Marktschellenberg, GERMANY;
Gregor MATJAN, Bergheim, AUSTRIA;

Applicant(s)

OSRAM OLED GmbH, Regensburg, GERMANY;

Power of Attorney: The patent practitioners associated with Customer Number 27799

Domestic Priority data as claimed by applicant

This application is a CON of 15/651,508 07/17/2017 PAT 10605422
which is a CON of 13/139,514 01/03/2012 PAT 9797567
which is a 371 of PCT/DE2009/001741 12/09/2009

Foreign Applications (You may be eligible to benefit from the **Patent Prosecution Highway** program at the USPTO. Please see http://www.uspto.gov for more information.)
GERMANY 10 2008 061 563.3 12/11/2008

SDC EX. 1027 - 279/489

Permission to Access Application via Priority Document Exchange: No

Permission to Access Search Results: No

Applicant may provide or rescind an authorization for access using Form PTO/SB/39 or Form PTO/SB/69 as appropriate.

If Required, Foreign Filing License Granted: 02/28/2020

The country code and number of your priority application, to be used for filing abroad under the Paris Convention, is **US 16/790,198**

Projected Publication Date: 06/11/2020

Non-Publication Request: No

Early Publication Request: No

Title

Organic-Light-Emitting Diode

Preliminary Class

315

Statement under 37 CFR 1.55 or 1.78 for AIA (First Inventor to File) Transition Applications: No

PROTECTING YOUR INVENTION OUTSIDE THE UNITED STATES

Since the rights granted by a U.S. patent extend only throughout the territory of the United States and have no effect in a foreign country, an inventor who wishes patent protection in another country must apply for a patent in a specific country or in regional patent offices. Applicants may wish to consider the filing of an international application under the Patent Cooperation Treaty (PCT). An international (PCT) application generally has the same effect as a regular national patent application in each PCT-member country. The PCT process **simplifies** the filing of patent applications on the same invention in member countries, but **does not result** in a grant of "an international patent" and does not eliminate the need of applicants to file additional documents and fees in countries where patent protection is desired.

Almost every country has its own patent law, and a person desiring a patent in a particular country must make an application for patent in that country in accordance with its particular laws. Since the laws of many countries differ in various respects from the patent law of the United States, applicants are advised to seek guidance from specific foreign countries to ensure that patent rights are not lost prematurely.

Applicants also are advised that in the case of inventions made in the United States, the Director of the USPTO must issue a license before applicants can apply for a patent in a foreign country. The filing of a U.S. patent application serves as a request for a foreign filing license. The application's filing receipt contains further information and guidance as to the status of applicant's license for foreign filing.

Applicants may wish to consult the USPTO booklet, "General Information Concerning Patents" (specifically, the section entitled "Treaties and Foreign Patents") for more information on timeframes and deadlines for filing foreign patent applications. The guide is available either by contacting the USPTO Contact Center at 800-786-9199, or it can be viewed on the USPTO website at http://www.uspto.gov/web/offices/pac/doc/general/index.html.

For information on preventing theft of your intellectual property (patents, trademarks and copyrights), you may wish to consult the U.S. Government website, http://www.stopfakes.gov. Part of a Department of Commerce initiative, this website includes self-help "toolkits" giving innovators guidance on how to protect intellectual property in specific countries such as China, Korea and Mexico. For questions regarding patent enforcement issues, applicants may call the U.S. Government hotline at 1-866-999-HALT (1-866-999-4258).

LICENSE FOR FOREIGN FILING UNDER

Title 35, United States Code, Section 184

Title 37, Code of Federal Regulations, 5.11 & 5.15

GRANTED

The applicant has been granted a license under 35 U.S.C. 184, if the phrase "IF REQUIRED, FOREIGN FILING LICENSE GRANTED" followed by a date appears on this form. Such licenses are issued in all applications where the conditions for issuance of a license have been met, regardless of whether or not a license may be required as set forth in 37 CFR 5.15. The scope and limitations of this license are set forth in 37 CFR 5.15(a) unless an earlier license has been issued under 37 CFR 5.15(b). The license is subject to revocation upon written notification. The date indicated is the effective date of the license, unless an earlier license of similar scope has been granted under 37 CFR 5.13 or 5.14.

This license is to be retained by the licensee and may be used at any time on or after the effective date thereof unless it is revoked. This license is automatically transferred to any related applications(s) filed under 37 CFR 1.53(d). This license is not retroactive.

The grant of a license does not in any way lessen the responsibility of a licensee for the security of the subject matter as imposed by any Government contract or the provisions of existing laws relating to espionage and the national security or the export of technical data. Licensees should apprise themselves of current regulations especially with respect to certain countries, of other agencies, particularly the Office of Defense Trade Controls, Department of State (with respect to Arms, Munitions and Implements of War (22 CFR 121-128)); the Bureau of Industry and Security, Department of Commerce (15 CFR parts 730-774); the Office of Foreign AssetsControl, Department of Treasury (31 CFR Parts 500+) and the Department of Energy.

NOT GRANTED

No license under 35 U.S.C. 184 has been granted at this time, if the phrase "IF REQUIRED, FOREIGN FILING LICENSE GRANTED" DOES NOT appear on this form. Applicant may still petition for a license under 37 CFR 5.12, if a license is desired before the expiration of 6 months from the filing date of the application. If 6 months has lapsed from the filing date of this application and the licensee has not received any indication of a secrecy order under 35 U.S.C. 181, the licensee may foreign file the application pursuant to 37 CFR 5.15(b).

SelectUSA

The United States represents the largest, most dynamic marketplace in the world and is an unparalleled location for business investment, innovation, and commercialization of new technologies. The U.S. offers tremendous resources and advantages for those who invest and manufacture goods here. Through SelectUSA, our nation works to promote and facilitate business investment. SelectUSA provides information assistance to the international investor

community; serves as an ombudsman for existing and potential investors; advocates on behalf of U.S. cities, states, and regions competing for global investment; and counsels U.S. economic development organizations on investment attraction best practices. To learn more about why the United States is the best country in the world to develop technology, manufacture products, deliver services, and grow your business, visit http://www.SelectUSA.gov or call +1-202-482-6800.

UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NUMBER	FILING OR 371(C) DATE	FIRST NAMED APPLICANT	ATTY. DOCKET NO./TITLE
16/790,198	02/13/2020	Ulrich KASTNER-JUNG	5367-694PCON2\474410

CONFIRMATION NO. 1309

27799
COZEN O'CONNOR
277 PARK AVENUE , 20TH FLOOR
NEW YORK, NY 10172

PUBLICATION NOTICE



Title: Organic-Light-Emitting Diode

Publication No.US-2020-0182422-A1
Publication Date:06/11/2020

NOTICE OF PUBLICATION OF APPLICATION

The above-identified application will be electronically published as a patent application publication pursuant to 37 CFR 1.211, et seq. The patent application publication number and publication date are set forth above.

The publication may be accessed through the USPTO's publically available Searchable Databases via the Internet at www.uspto.gov. The direct link to access the publication is currently http://www.uspto.gov/patft/.

The publication process established by the Office does not provide for mailing a copy of the publication to applicant. A copy of the publication may be obtained from the Office upon payment of the appropriate fee set forth in 37 CFR 1.19(a)(1). Orders for copies of patent application publications are handled by the USPTO's Public Records Division. The Public Records Division can be reached by telephone at (571) 272-3150 or (800) 972-6382, by facsimile at (571) 273-3250, by mail addressed to the United States Patent and Trademark Office, Public Records Division, Alexandria, VA 22313-1450 or via the Internet.

In addition, information on the status of the application, including the mailing date of Office actions and the dates of receipt of correspondence filed in the Office, may also be accessed via the Internet through the Patent Electronic Business Center at www.uspto.gov using the public side of the Patent Application Information and Retrieval (PAIR) system. The direct link to access this status information is currently https://portal.uspto.gov/pair/PublicPair. Prior to publication, such status information is confidential and may only be obtained by applicant using the private side of PAIR.

Further assistance in electronically accessing the publication, or about PAIR, is available by calling the Patent Electronic Business Center at 1-866-217-9197.

Office of Data Managment, Application Assistance Unit (571) 272-4000, or (571) 272-4200, or 1-888-786-0101

Doc Code: PA..
Document Description: Power of Attorney

PTO/AIA/82A (07-13)
Approved for use through 11/30/2014. OMB 0651-0051
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

TRANSMITTAL FOR POWER OF ATTORNEY TO ONE OR MORE REGISTERED PRACTITIONERS

NOTE: This form is to be submitted with the Power of Attorney by Applicant form (PTO/AIA/82B) to identify the application to which the Power of Attorney is directed, in accordance with 37 CFR 1.5, unless the application number and filing date are identified in the Power of Attorney by Applicant form. If neither form PTO/AIA/82A nor form PTO/AIA82B identifies the application to which the Power of Attorney is directed, the Power of Attorney will not be recognized in the application.

Application Number	16/790,198 / Conf. #1309
Filing Date	February 13, 2020
First Named Inventor	Ulrich Kastner-Jung
Title	ORGANIC-LIGHT-EMITTING DIODE
Art Unit	2844
Examiner Name	James Hyonchol Cho
Attorney Docket Number	PICTIV 3.3F-001 CON CON [2]

SIGNATURE of Applicant or Patent Practitioner

Signature	/Richard J. Botos/	Date (Optional)	3/9/2021
Name	Richard J. Botos	Registration Number	32,016
Title (if Applicant is a juristic entity)			
Applicant Name (if Applicant is a juristic entity)			

NOTE: This form must be signed in accordance with 37 CFR 1.33. See 37 CFR 1.4(d) for signature requirements and certifications. If more than one applicant, use multiple forms.

☐ *Total of _____ forms are submitted.

I hereby certify that this paper (along with any paper referred to as being attached or enclosed) is being transmitted via the Office electronic filing system in accordance with 37 CFR § 1.6(a)(4).

Dated: 3/9/2021 Electronic Signature for Richard J. Botos /Richard J. Botos/

Doc Code: PA.
Document Description: Power of Attorney

PTO/AIA/82B (07-13)
Approved for use through 01/31/2018. OMB 0651-0035
U.S. Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

POWER OF ATTORNEY BY APPLICANT

I hereby revoke all previous powers of attorney given in the application identified in either the attached transmittal letter or the boxes below.

Application Number	Filing Date

(Note: The boxes above may be left blank if information is provided on form PTO/AIA/82A.)

☑ I hereby appoint the Patent Practitioner(s) associated with the following Customer Number as my/our attorney(s) or agent(s), and to transact all business in the United States Patent and Trademark Office connected therewith for the application referenced in the attached transmittal letter (form PTO/AIA/82A) or identified above.

OR

175540

☐ I hereby appoint Practitioner(s) named in the attached list (form PTO/AIA/82C) as my/our attorney(s) or agent(s), and to transact all business in the United States Patent and Trademark Office connected therewith for the patent application referenced in the attached transmittal letter (form PTO/AIA/82A) or identified above. (Note: Complete form PTO/AIA/82C.)

Please recognize or change the correspondence address for the application identified in the attached transmittal letter or the boxes above to:

☑ The address associated with the above-mentioned Customer Number

OR

☐ The address associated with Customer Number:

OR

☐ Firm or Individual Name					
Address					
City		State		Zip	
Country					
Telephone		Email			

I am the Applicant (if the Applicant is a juristic entity, list the Applicant name in the box):

PICTIVA DISPLAYS INTERNATIONAL LIMITED

☐ Inventor or Joint Inventor (title not required below)

☐ Legal Representative of a Deceased or Legally Incapacitated Inventor (title not required below)

☑ Assignee or Person to Whom the Inventor is Under an Obligation to Assign (provide signer's title if applicant is a juristic entity)

☐ Person Who Otherwise Shows Sufficient Proprietary Interest (e.g., a petition under 37 CFR 1.46(b)(2) was granted in the application or is concurrently being filed with this document) (provide signer's title if applicant is a juristic entity)

SIGNATURE of Applicant for Patent

The undersigned (whose title is supplied below) is authorized to act on behalf of the applicant (e.g., where the applicant is a juristic entity).

Signature	[signature]	Date (Optional)	[illegible]
Name	Angel Quirion		
Title	Director		

NOTE: Signature - This form must be signed by the applicant in accordance with 37 CFR 1.33. See 37 CFR 1.4 for signature requirements and certifications. If more than one applicant, use multiple forms.

☐ Total of forms are submitted.

This collection of information is required by 37 CFR 1.131, 1.32 and 1.33. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.11 and 1.14. This collection is estimated to take 3 minutes to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

PTO/AIA/96 (08-12)
Approved for use through 01/31/2013. OMB 0651-0031
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

STATEMENT UNDER 37 CFR 3.73(c)

Applicant/Patent Owner: PICTIVA DISPLAYS INTERNATIONAL LIMITED

Application No./Patent No.: 16/790,198 Filed/Issue Date: February 13, 2020

Titled: ORGANIC-LIGHT-EMITTING DIODE

PICTIVA DISPLAYS INTERNATIONAL LIMITED, a corporation

(Name of Assignee) (Type of Assignee, e.g., corporation, partnership, university, government agency, etc.)

states that, for the patent application/patent identified above, it is (choose **one** of options 1, 2, 3 or 4 below):

1. ☑ The assignee of the entire right, title, and interest.

2. ☐ An assignee of less than the entire right, title, and interest (check applicable box):

   ☐ The extent (by percentage) of its ownership interest is _____%. Additional Statement(s) by the owners holding the balance of the interest must be submitted to account for 100% of the ownership interest.

   ☐ There are unspecified percentages of ownership. The other parties, including inventors, who together own the entire right, title and interest are:

   Additional Statement(s) by the owner(s) holding the balance of the interest must be submitted to account for the entire right, title, and interest.

3. ☐ The assignee of an undivided interest in the entirety (a complete assignment from one of the joint inventors was made). The other parties, including inventors, who together own the entire right, title, and interest are:

   Additional Statement(s) by the owner(s) holding the balance of the interest must be submitted to account for the entire right, title, and interest.

4. ☐ The recipient, via a court proceeding or the like (*e.g.*, bankruptcy, probate), of an undivided interest in the entirety (a complete transfer of ownership interest was made). The certified document(s) showing the transfer is attached.

The interest identified in option 1, 2 or 3 above (not option 4) is evidenced by either (choose **one** of options A or B below):

A. ☐ An assignment from the inventor(s) of the patent application/patent identified above. The assignment was recorded in the United States Patent and Trademark Office at Reel _____, Frame _____, or for which a copy thereof is attached.

B. ☑ A chain of title from the inventor(s), of the patent application/patent identified above, to the current assignee as follows:

1. From: Kastner-Jung et al. To: OSRAM Opto Semiconductors GmbH

   The document was recorded in the United States Patent and Trademark Office at
   Reel 027296, Frame 0115, or for which a copy thereof is attached.

2. From: OSRAM Opto Semiconductors GmbH To: OSRAM OLED GmbH

   The document was recorded in the United States Patent and Trademark Office at
   Reel 037567, Frame 0993, or for which a copy thereof is attached.

This collection of information is required by 37 CFR 3.73(b). The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.11 and 1.14. This collection is estimated to take 12 minutes to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.**

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

PTO/AIA/96 (08-12)
Approved for use through 01/31/2013. OMB 0651-0031
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

STATEMENT UNDER 37 CFR 3.73(c)

3. From: OSRAM OLED GmbH To: DOLYA HOLDCO 5 LIMITED

The document was recorded in the United States Patent and Trademark Office at
Reel 053464, Frame 0374, or for which a copy thereof is attached.

4. From: DOLYA HOLDCO 5 LIMITED To: PICTIVA DISPLAYS INTERNATIONAL LIMITED

The document was recorded in the United States Patent and Trademark Office at
Reel 053464, Frame 0395, or for which a copy thereof is attached.

5. From: _____ To: _____

The document was recorded in the United States Patent and Trademark Office at
Reel _____, Frame _____, or for which a copy thereof is attached.

6. From: _____ To: _____

The document was recorded in the United States Patent and Trademark Office at
Reel _____, Frame _____, or for which a copy thereof is attached.

☐ Additional documents in the chain of title are listed on a supplemental sheet(s).

☐ As required by 37 CFR 3.73(c)(1)(i), the documentary evidence of the chain of title from the original owner to the assignee was, or concurrently is being, submitted for recordation pursuant to 37 CFR 3.11.

[NOTE: A separate copy (i.e., a true copy of the original assignment document(s)) must be submitted to Assignment Division in accordance with 37 CFR Part 3, to record the assignment in the records of the USPTO. See MPEP 302.08]

The undersigned (whose title is supplied below) is authorized to act on behalf of the assignee.

/Richard J. Botos/	March 9, 2021
Signature	Date
Richard J. Botos	32,016
Printed or Typed Name	Title or Registration Number

Privacy Act Statement

The **Privacy Act of 1974 (P.L. 93-579)** requires that you be given certain information in connection with your submission of the attached form related to a patent application or patent. Accordingly, pursuant to the requirements of the Act, please be advised that: (1) the general authority for the collection of this information is 35 U.S.C. 2(b)(2); (2) furnishing of the information solicited is voluntary; and (3) the principal purpose for which the information is used by the U.S. Patent and Trademark Office is to process and/or examine your submission related to a patent application or patent. If you do not furnish the requested information, the U.S. Patent and Trademark Office may not be able to process and/or examine your submission, which may result in termination of proceedings or abandonment of the application or expiration of the patent.

The information provided by you in this form will be subject to the following routine uses:

1. The information on this form will be treated confidentially to the extent allowed under the Freedom of Information Act (5 U.S.C. 552) and the Privacy Act (5 U.S.C 552a). Records from this system of records may be disclosed to the Department of Justice to determine whether disclosure of these records is required by the Freedom of Information Act.
2. A record from this system of records may be disclosed, as a routine use, in the course of presenting evidence to a court, magistrate, or administrative tribunal, including disclosures to opposing counsel in the course of settlement negotiations.
3. A record in this system of records may be disclosed, as a routine use, to a Member of Congress submitting a request involving an individual, to whom the record pertains, when the individual has requested assistance from the Member with respect to the subject matter of the record.
4. A record in this system of records may be disclosed, as a routine use, to a contractor of the Agency having need for the information in order to perform a contract. Recipients of information shall be required to comply with the requirements of the Privacy Act of 1974, as amended, pursuant to 5 U.S.C. 552a(m).
5. A record related to an International Application filed under the Patent Cooperation Treaty in this system of records may be disclosed, as a routine use, to the International Bureau of the World Intellectual Property Organization, pursuant to the Patent Cooperation Treaty.
6. A record in this system of records may be disclosed, as a routine use, to another federal agency for purposes of National Security review (35 U.S.C. 181) and for review pursuant to the Atomic Energy Act (42 U.S.C. 218(c)).
7. A record from this system of records may be disclosed, as a routine use, to the Administrator, General Services, or his/her designee, during an inspection of records conducted by GSA as part of that agency's responsibility to recommend improvements in records management practices and programs, under authority of 44 U.S.C. 2904 and 2906. Such disclosure shall be made in accordance with the GSA regulations governing inspection of records for this purpose, and any other relevant (*i.e.*, GSA or Commerce) directive. Such disclosure shall not be used to make determinations about individuals.
8. A record from this system of records may be disclosed, as a routine use, to the public after either publication of the application pursuant to 35 U.S.C. 122(b) or issuance of a patent pursuant to 35 U.S.C. 151. Further, a record may be disclosed, subject to the limitations of 37 CFR 1.14, as a routine use, to the public if the record was filed in an application which became abandoned or in which the proceedings were terminated and which application is referenced by either a published application, an application open to public inspection or an issued patent.
9. A record from this system of records may be disclosed, as a routine use, to a Federal, State, or local law enforcement agency, if the USPTO becomes aware of a violation or potential violation of law or regulation.

CORRECTED APPLICATION DATA SHEET

Application Number:	16/790,198
Filing Date:	February 13, 2020
Title of Invention:	ORGANIC-LIGHT-EMITTING DIODE

Applicant Information

Please amend Applicant Information as follows:

Applicant Number:	1
Applicant Type:	Assignee
Organization Name:	~~OSRAM OLED GmbH~~ PICTIVA DISPLAYS INTERNATIONAL LIMITED
Street of mailing address:	~~Wernerwerkstr. 2~~ 92 Georges Street Lower Dun Laoghaire
City of mailing address:	~~Regensburg~~ Dublin
State or Province of mailing address:	
Country of mailing address:	~~DE~~ IE
Postal or Zip Code of mailing address:	~~93049~~ A96 VR66

Signature:	/Richard J. Botos/	**Date:**	March 9, 2021
Name:	Richard J. Botos	**Registration Number:**	32,016

4829-3477-4239, v. 1

Electronic Acknowledgement Receipt

EFS ID:	42130535
Application Number:	16790198
International Application Number:	
Confirmation Number:	1309
Title of Invention:	Organic-Light-Emitting Diode
First Named Inventor/Applicant Name:	Ulrich KASTNER-JUNG
Customer Number:	27799
Filer:	Richard J. Botos/Elizabeth Gagliano
Filer Authorized By:	Richard J. Botos
Attorney Docket Number:	5367-694PCON2\474410
Receipt Date:	09-MAR-2021
Filing Date:	13-FEB-2020
Time Stamp:	15:10:43
Application Type:	Utility under 35 USC 111(a)

Payment information:

Submitted with Payment	no

File Listing:

Document Number	Document Description	File Name	File Size(Bytes)/ Message Digest	Multi Part /.zip	Pages (if appl.)
1	Power of Attorney	PICTIV_2_--_Power_of_Attorney_Transmittal.pdf	1067305 94c4431548006cb90f10dd68a9d0110ccd92aac3	no	1

Warnings:

Information:					
2	Power of Attorney	PICTIV_2_--_POA_Pictiva_post_AIA_signed.pdf	506668 560dcae7cf725e5407f395dfd73adb5312ded532	no	1
Warnings:					
Information:					
3	Assignee showing of ownership per 37 CFR 3.73	PICTIV_2_--_37_CFR_3_73_c__form.pdf	122611 fcf9a77b86b4f9e36215a0c20a977090248ecc20	no	3
Warnings:					
Information:					
4	Application Data Sheet	PICTIV_2_--_Corrected_ADS.pdf	165576 1345fc3cc2b8df2bb22d9bf412de0c5b6ea19dd4	no	1
Warnings:					
Information:					
This is not an USPTO supplied ADS fillable form					
		Total Files Size (in bytes):	1862160		

This Acknowledgement Receipt evidences receipt on the noted date by the USPTO of the indicated documents, characterized by the applicant, and including page counts, where applicable. It serves as evidence of receipt similar to a Post Card, as described in MPEP 503.

New Applications Under 35 U.S.C. 111

If a new application is being filed and the application includes the necessary components for a filing date (see 37 CFR 1.53(b)-(d) and MPEP 506), a Filing Receipt (37 CFR 1.54) will be issued in due course and the date shown on this Acknowledgement Receipt will establish the filing date of the application.

National Stage of an International Application under 35 U.S.C. 371

If a timely submission to enter the national stage of an international application is compliant with the conditions of 35 U.S.C. 371 and other applicable requirements a Form PCT/DO/EO/903 indicating acceptance of the application as a national stage submission under 35 U.S.C. 371 will be issued in addition to the Filing Receipt, in due course.

New International Application Filed with the USPTO as a Receiving Office

If a new international application is being filed and the international application includes the necessary components for an international filing date (see PCT Article 11 and MPEP 1810), a Notification of the International Application Number and of the International Filing Date (Form PCT/RO/105) will be issued in due course, subject to prescriptions concerning national security, and the date shown on this Acknowledgement Receipt will establish the international filing date of the application.

UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NUMBER	FILING or 371(c) DATE	GRP ART UNIT	FIL FEE REC'D	ATTY.DOCKET.NO	TOT CLAIMS	IND CLAIMS
16/790,198	02/13/2020	2844	2680	5367-694PCON2\474410	13	2

CONFIRMATION NO. 1309

CORRECTED FILING RECEIPT

175540
Botos Churchill IP Law LLP
430 Mountain Avenue
Suite 401
New Providence, NJ 07974

OC000000123998511

Date Mailed: 03/12/2021

Receipt is acknowledged of this non-provisional utility patent application. The application will be taken up for examination in due course. Applicant will be notified as to the results of the examination. Any correspondence concerning the application must include the following identification information: the U.S. APPLICATION NUMBER, FILING DATE, NAME OF FIRST INVENTOR, and TITLE OF INVENTION. Fees transmitted by check or draft are subject to collection.

Please verify the accuracy of the data presented on this receipt. If an error is noted on this Filing Receipt, please submit a written request for a corrected Filing Receipt, including a properly marked-up ADS showing the changes with strike-through for deletions and underlining for additions. If you received a "Notice to File Missing Parts" or other Notice requiring a response for this application, please submit any request for correction to this Filing Receipt with your reply to the Notice. When the USPTO processes the reply to the Notice, the USPTO will generate another Filing Receipt incorporating the requested corrections provided that the request is grantable.

Inventor(s)

Ulrich KASTNER-JUNG, Munich, GERMANY;
Markus KLEIN, Tegernheim, GERMANY;
Stan MAES, Dilsen-Stokken, BELGIUM;
Romana SIGL, Salzburg, AUSTRIA;
Annette HAID, Salzburg, AUSTRIA;
Stephan LINTNER, Salzburg, AUSTRIA;
Julian HERGET, Marktschellenberg, GERMANY;
Gregor MATJAN, Bergheim, AUSTRIA;

Applicant(s)

PICTIVA DISPLAYS INTERNATIONAL LIMITED, Dublin, IRELAND;

Power of Attorney: The patent practitioners associated with Customer Number 175540

Domestic Priority data as claimed by applicant

This application is a CON of 15/651,508 07/17/2017 PAT 10605422
which is a CON of 13/139,514 01/03/2012 PAT 9797567
which is a 371 of PCT/DE2009/001741 12/09/2009

Foreign Applications (You may be eligible to benefit from the **Patent Prosecution Highway** program at the USPTO. Please see http://www.uspto.gov for more information.)
GERMANY 10 2008 061 563.3 12/11/2008

Permission to Access Application via Priority Document Exchange: No

Permission to Access Search Results: No

Applicant may provide or rescind an authorization for access using Form PTO/SB/39 or Form PTO/SB/69 as appropriate.

If Required, Foreign Filing License Granted: 02/28/2020

The country code and number of your priority application, to be used for filing abroad under the Paris Convention, is **US 16/790,198**

Projected Publication Date: Not Applicable

Non-Publication Request: No

Early Publication Request: No

Title

Organic-Light-Emitting Diode

Preliminary Class

315

Statement under 37 CFR 1.55 or 1.78 for AIA (First Inventor to File) Transition Applications: No

PROTECTING YOUR INVENTION OUTSIDE THE UNITED STATES

Since the rights granted by a U.S. patent extend only throughout the territory of the United States and have no effect in a foreign country, an inventor who wishes patent protection in another country must apply for a patent in a specific country or in regional patent offices. Applicants may wish to consider the filing of an international application under the Patent Cooperation Treaty (PCT). An international (PCT) application generally has the same effect as a regular national patent application in each PCT-member country. The PCT process **simplifies** the filing of patent applications on the same invention in member countries, but **does not result** in a grant of "an international patent" and does not eliminate the need of applicants to file additional documents and fees in countries where patent protection is desired.

Almost every country has its own patent law, and a person desiring a patent in a particular country must make an application for patent in that country in accordance with its particular laws. Since the laws of many countries differ in various respects from the patent law of the United States, applicants are advised to seek guidance from specific foreign countries to ensure that patent rights are not lost prematurely.

Applicants also are advised that in the case of inventions made in the United States, the Director of the USPTO must issue a license before applicants can apply for a patent in a foreign country. The filing of a U.S. patent application serves as a request for a foreign filing license. The application's filing receipt contains further information and guidance as to the status of applicant's license for foreign filing.

Applicants may wish to consult the USPTO booklet, "General Information Concerning Patents" (specifically, the section entitled "Treaties and Foreign Patents") for more information on timeframes and deadlines for filing foreign patent applications. The guide is available either by contacting the USPTO Contact Center at 800-786-9199, or it can be viewed on the USPTO website at http://www.uspto.gov/web/offices/pac/doc/general/index.html.

For information on preventing theft of your intellectual property (patents, trademarks and copyrights), you may wish to consult the U.S. Government website, http://www.stopfakes.gov. Part of a Department of Commerce initiative, this website includes self-help "toolkits" giving innovators guidance on how to protect intellectual property in specific countries such as China, Korea and Mexico. For questions regarding patent enforcement issues, applicants may call the U.S. Government hotline at 1-866-999-HALT (1-866-999-4258).

LICENSE FOR FOREIGN FILING UNDER

Title 35, United States Code, Section 184

Title 37, Code of Federal Regulations, 5.11 & 5.15

GRANTED

The applicant has been granted a license under 35 U.S.C. 184, if the phrase "IF REQUIRED, FOREIGN FILING LICENSE GRANTED" followed by a date appears on this form. Such licenses are issued in all applications where the conditions for issuance of a license have been met, regardless of whether or not a license may be required as set forth in 37 CFR 5.15. The scope and limitations of this license are set forth in 37 CFR 5.15(a) unless an earlier license has been issued under 37 CFR 5.15(b). The license is subject to revocation upon written notification. The date indicated is the effective date of the license, unless an earlier license of similar scope has been granted under 37 CFR 5.13 or 5.14.

This license is to be retained by the licensee and may be used at any time on or after the effective date thereof unless it is revoked. This license is automatically transferred to any related applications(s) filed under 37 CFR 1.53(d). This license is not retroactive.

The grant of a license does not in any way lessen the responsibility of a licensee for the security of the subject matter as imposed by any Government contract or the provisions of existing laws relating to espionage and the national security or the export of technical data. Licensees should apprise themselves of current regulations especially with respect to certain countries, of other agencies, particularly the Office of Defense Trade Controls, Department of State (with respect to Arms, Munitions and Implements of War (22 CFR 121-128)); the Bureau of Industry and Security, Department of Commerce (15 CFR parts 730-774); the Office of Foreign AssetsControl, Department of Treasury (31 CFR Parts 500+) and the Department of Energy.

NOT GRANTED

No license under 35 U.S.C. 184 has been granted at this time, if the phrase "IF REQUIRED, FOREIGN FILING LICENSE GRANTED" DOES NOT appear on this form. Applicant may still petition for a license under 37 CFR 5.12, if a license is desired before the expiration of 6 months from the filing date of the application. If 6 months has lapsed from the filing date of this application and the licensee has not received any indication of a secrecy order under 35 U.S.C. 181, the licensee may foreign file the application pursuant to 37 CFR 5.15(b).

SelectUSA

The United States represents the largest, most dynamic marketplace in the world and is an unparalleled location for business investment, innovation, and commercialization of new technologies. The U.S. offers tremendous resources and advantages for those who invest and manufacture goods here. Through SelectUSA, our nation works to promote and facilitate business investment. SelectUSA provides information assistance to the international investor

community; serves as an ombudsman for existing and potential investors; advocates on behalf of U.S. cities, states, and regions competing for global investment; and counsels U.S. economic development organizations on investment attraction best practices. To learn more about why the United States is the best country in the world to develop technology, manufacture products, deliver services, and grow your business, visit http://www.SelectUSA.gov or call +1-202-482-6800.

UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NUMBER	FILING OR 371(C) DATE	FIRST NAMED APPLICANT	ATTY. DOCKET NO./TITLE
16/790,198	02/13/2020	Ulrich KASTNER-JUNG	5367-694PCON2\474410

CONFIRMATION NO. 1309

175540
Botos Churchill IP Law LLP
430 Mountain Avenue
Suite 401
New Providence, NJ 07974

POA ACCEPTANCE LETTER

OC000000123996419

Date Mailed: 03/12/2021

NOTICE OF ACCEPTANCE OF POWER OF ATTORNEY

This is in response to the Power of Attorney filed 03/09/2021.

The Power of Attorney in this application is accepted. Correspondence in this application will be mailed to the above address as provided by 37 CFR 1.33.

Questions about the contents of this notice and the requirements it sets forth should be directed to the Office of Data Management, Application Assistance Unit, at **(571) 272-4000** or **(571) 272-4200** or **1-888-786-0101**.

/atesfai/

UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NUMBER	FILING OR 371(C) DATE	FIRST NAMED APPLICANT	ATTY. DOCKET NO./TITLE
16/790,198	02/13/2020	Ulrich KASTNER-JUNG	5367-694PCON2\474410

CONFIRMATION NO. 1309

POWER OF ATTORNEY NOTICE

27799
COZEN O"CONNOR
3WTC, 175 Greenwich Street
55th Floor
NEW YORK, NY 10007

OC000000123996408

Date Mailed: 03/12/2021

NOTICE REGARDING CHANGE OF POWER OF ATTORNEY

This is in response to the Power of Attorney filed 03/09/2021.

- The Power of Attorney to you in this application has been revoked by the applicant. Future correspondence will be mailed to the new address of record(37 CFR 1.33).

Questions about the contents of this notice and the requirements it sets forth should be directed to the Office of Data Management, Application Assistance Unit, at **(571) 272-4000** or **(571) 272-4200** or **1-888-786-0101**.

/atesfai/

SDC EX. 1027 - 297/489

UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
16/790,198	02/13/2020	Ulrich KASTNER-JUNG	PICTIV 3.3F-001 CC [2]	1309

175540 7590 05/17/2021

Botos Churchill IP Law LLP
430 Mountain Avenue
Suite 401
New Providence, NJ 07974

EXAMINER	
CHO, JAMES HYONCHOL	

ART UNIT	PAPER NUMBER
2844	

NOTIFICATION DATE	DELIVERY MODE
05/17/2021	ELECTRONIC

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Notice of the Office communication was sent electronically on above-indicated "Notification Date" to the following e-mail address(es):

lgagliano@bciplaw.com
pto@bciplaw.com
rbotos@bciplaw.com

Office Action Summary	Application No. 16/790,198	Applicant(s) KASTNER-JUNG et al.	
	Examiner James H Cho	Art Unit 2844	AIA (FITF) Status No

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTHS FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

1)☑ Responsive to communication(s) filed on 2/13/2020.

☐ A declaration(s)/affidavit(s) under **37 CFR 1.130(b)** was/were filed on _____.

2a)☐ This action is **FINAL.** 2b) ☑ This action is non-final.

3)☐ An election was made by the applicant in response to a restriction requirement set forth during the interview on _____; the restriction requirement and election have been incorporated into this action.

4)☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims*

5) ☑ Claim(s) 1-13 is/are pending in the application.

5a) Of the above claim(s) _____ is/are withdrawn from consideration.

6) ☐ Claim(s) _____ is/are allowed.

7) ☑ Claim(s) 1-13 is/are rejected.

8) ☐ Claim(s) _____ is/are objected to.

9) ☐ Claim(s) _____ are subject to restriction and/or election requirement

* If any claims have been determined allowable, you may be eligible to benefit from the **Patent Prosecution Highway** program at a participating intellectual property office for the corresponding application. For more information, please see http://www.uspto.gov/patents/init_events/pph/index.jsp or send an inquiry to **PPHfeedback@uspto.gov.**

Application Papers

10)☑ The specification is objected to by the Examiner.

11)☑ The drawing(s) filed on 2/13/2020 is/are: a)☑ accepted or b)☐ objected to by the Examiner.

Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).

Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).

Priority under 35 U.S.C. § 119

12)☑ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).

Certified copies:

a)☑ All b)☐ Some** c)☐ None of the:

1.☐ Certified copies of the priority documents have been received.

2.☑ Certified copies of the priority documents have been received in Application No. 13/139514.

3.☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

** See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

1) ☑ Notice of References Cited (PTO-892)

2) ☑ Information Disclosure Statement(s) (PTO/SB/08a and/or PTO/SB/08b) Paper No(s)/Mail Date _____.

3) ☐ Interview Summary (PTO-413) Paper No(s)/Mail Date _____.

4) ☐ Other: _____.

DETAILED ACTION

Notice of Pre-AIA or AIA Status

The present application is being examined under the pre-AIA first to invent provisions.

Specification

The disclosure is objected to because of the following informalities: in the cross-reference to related application, the parent application SN 15/651,508 is now issued as United States Patent Number 10,605,422, which is to be updated in the instant application specification.

Appropriate correction is required.

Claim Rejections - 35 USC § 103

In the event the determination of the status of the application as subject to AIA 35 U.S.C. 102 and 103 (or as subject to pre-AIA 35 U.S.C. 102 and 103) is incorrect, any correction of the statutory basis for the rejection will not be considered a new ground of rejection if the prior art relied upon, and the rationale supporting the rejection, would be the same under either status.

The following is a quotation of pre-AIA 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

> (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.

The factual inquiries for establishing a background for determining obviousness under pre-AIA 35 U.S.C. 103(a) are summarized as follows:

1. Determining the scope and contents of the prior art.

2. Ascertaining the differences between the prior art and the claims at issue.

3. Resolving the level of ordinary skill in the pertinent art.

4. Considering objective evidence present in the application indicating obviousness or nonobviousness.

This application currently names joint inventors. In considering patentability of the claims under pre-AIA 35 U.S.C. 103(a), the examiner presumes that the subject matter of the various claims was commonly owned at the time any inventions covered therein were made absent any evidence to the contrary. Applicant is advised of the obligation under 37 CFR 1.56 to point out the inventor and invention dates of each claim that was not commonly owned at the time a later invention was made in order for the examiner to consider the applicability of pre-AIA 35 U.S.C. 103(c) and potential pre-AIA 35 U.S.C. 102(e), (f) or (g) prior art under pre-AIA 35 U.S.C. 103(a).

Claims 1 and 4-9 are rejected under pre-AIA 35 U.S.C. 103(a) as being unpatentable over Hente (US 2011/0187668 A1) in view of Hild (US 2011/0096504 A1)

Regarding claim 1, Hente teaches a device (see Fig. 2) comprising an organic light-emitting diode (102, see para [0017]) comprising an organic layer sequence (106, 108, 110, 112), a radiation exit area (conductive elements transmitting light, see para [0023]), wherein the organic layer sequence comprises at least one radiation-emitting region (conductive elements) on which generates electromagnetic radiation in the spectral range from infrared radiation to UV radiation during operation (visible light which an operator can see in the spectral range from IR radiation and UV radiation, see para [0023]),

at least one touch-sensitive operating element (near filed imaging touch sensors, see para [0001]), wherein the at least one touch-sensitive operating element comprises at least one touch sensor, wherein the device is flexible (touch sensor with substrate made with a flexible material where OLDE is mounted, see para [0020] and claim 8),

but does not teach that the OLED comprising an encapsulation forming a seal of the organic layer sequence against environment influences.

However, Hild teach a flexibly bendable top-emitting OLED (see Fig. 2 and para [0038]) emitting visible light only within a narrow wavelength range comprising of encapsulation forming a seal of the organic layer sequence against water and air as well as for a better heat dissipation (see paras [0011]-[0012], [0048]-[0049], [0056]).

Therefore, it would have been obvious at the time of invention to utilize the OLED of Hild with encapsulation in place of the OLED of Hente since it would provide an additional protection from overheating of the OLED as well as from moisture and air influences.

Regarding claim 4, Hente in view of Hild teaches the device according to claim 1, wherein the organic light-emitting diode comprises a flexible carrier (carrier foil 12 being flexible, see Fig. 2, para [0034]-[0036] of Hild).

Regarding claim 5, Hente in view of Hild teaches the device according to claim 4, wherein the flexible carrier comprises a film or a plastic film (the layer 12b being polycarbonate where a polycarbonate is a type of plastic, see para [0036] of Hild) or a laminate (12 comprises plurality of layers).

Regarding claim 6, Hente in view of Hild teaches the device according to claim 1, wherein the encapsulation is flexible (encapsulation being flexibly bendable layer, see para [0038] of Hild).

Regarding claim 7, Hente in view of Hild teaches the device according to claim 1, wherein the touch-sensitive operating element is arranged at a light exit area of the device (Fig. 3 of Hente where the diode transmitting light).

Regarding claim 8, Hente in view of Hild teaches the device according to claim 1, wherein the at least one touch sensor is integrated into the organic light-emitting diode (touch sensor being integrated in the OLED, see para [0017]-[0018] of Hente).

Regarding claim 9, Hente in view of Hild teaches the device according to claim 1, wherein the device is drivable by means of a gesture control (OLED apparatus generating light by user sliding his or her finger along the surface of the OLED device where sliding finger by a user is considered as being a gesture control, see para [0024] of Hente).

Claims 2-3 and 10-13 are rejected under pre-AIA 35 U.S.C. 103(a) as being unpatentable over Hente (US 2011/0187668 A1) in view of Hild (US 2011/0096504 A1) and Yoshida (US 2003/0071259 A1).

Regarding claims 2-3, the combination of prior arts, Hente and Hild teaches the device according claim 1,

but do not teach the specific of the device being bendable or capable of being rolled and the device maintaining its form after bending.

However, Yoshida teaches an organic EL display having shape changeability by bending by utilizing electrically conductive organic compound (see para [0003], [0005]) with at a low cost enabling forms being maintained after bending (sheet-like display is an electronic paper with various forms, see para [0016], see Fig. 6 which displays flipped bended-page on the left and returned to the original page on the right).

Therefore, it would have been obvious at the time of invention to utilize the materials of Yoshida for the OLED device of Hente and Hild since it would provide enhanced portability like a bendable sheet-like displace device with a cost reduction.

Regarding claim 10, Hente teaches a device (see Fig. 2) comprising an organic light-emitting diode (102, see para [0017]) comprising an organic layer sequence (106, 108, 110, 112), a radiation exit area (conductive elements transmitting light, see para [0023]), wherein the organic layer sequence comprises at least one radiation-emitting region (conductive elements) on which generates electromagnetic radiation in the spectral range from infrared radiation to UV radiation during operation (visible light which an operator can see in the spectral range from IR radiation and UV radiation, see para [0023]),

at least one touch-sensitive operating element (near filed imaging touch sensors, see para [0001]), wherein the at least one touch-sensitive operating element comprises at least one touch sensor, wherein the device is flexible (touch sensor constructed out of a flexible material where OLDE is mounted, see para [0020] and claim 8),

but does not teach that the OLED comprising an encapsulation forming a seal of the organic layer sequence against environment influences.

However, Hild teach a flexibly bendable top-emitting OLED (see Fig. 2 and para [0038]) emitting visible light only within a narrow wavelength range comprising of encapsulation forming a seal of the organic layer sequence against water and air as well as for a better heat dissipation (see paras [0011]-[0012], [0048]-[0049], [0056]).

Therefore, it would have been obvious at the time of invention to utilize the OLED of Hild with encapsulation in place of the OLED of Hente since it would provide an additional protection from overheating of the OLED as well as from moisture and air influences.

Regarding the limitation of the device, the combination of prior arts, Hente and Hild do not teach the specific of the device being bendable or capable of being rolled.

However, Yoshida teaches an organic EL display having shape changeability by bending by utilizing electrically conductive organic compound (see para [0003], [0005]) with at a low cost.

Therefore, it would have been obvious at the time of invention to utilize the materials of Yoshida for the OLED device of Hente and Hild since it would provide enhanced portability like a bendable sheet-like displace device with a cost reduction.

Regarding claim 11, Hente in view of Hild and Yoshida teaches the device according to claim 10, wherein the touch-sensitive operating element is arranged at a light exit area of the device (touch sensor being integrated in the OLED, see para [0017]-[0018] of Hente).

Regarding claim 12, Hente in view of Hild and Yoshida teaches the device according to claim 10, wherein the at least one touch sensor is integrated into the organic light-emitting diode (touch sensor being integrated in the OLED, see para [0017]-[0018] of Hente).

Regarding claim 13, Hente in view of Hild and Yoshida teaches the device according to claim 10, wherein the device is drivable by means of a gesture control (OLED apparatus generating light by user sliding his or her finger along the surface of the OLED device where sliding finger by a user is considered as being a gesture control, see para [0024] of Hente).

Conclusion

The prior art made of record and not relied upon is considered pertinent to applicant's disclosure.

Burns et al. (US 2010/0295812 A1) discloses a touch sensitive active matrix display device.

Birrell (US 2004/0022058 A1) discloses a lighting system in a form of light tile which includes embedded LEDs and control and sensing devices.

Park et al. (US Pat No. 6,926,572) discloses a flat panel display.

Ghosh et al. (US 2002/0003403 A1) discloses an OLED display device including encapsulation assembly.

Any inquiry concerning this communication or earlier communications from the examiner should be directed to James H Cho whose telephone number is (571)272-1802. The examiner can normally be reached on M-F 7:30 AM - 4 PM.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Amy Cohen Johnson can be reached on 571-272-2238. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be

obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

JAMES H CHO
Examiner, Art Unit 2844

/AMY COHEN JOHNSON/
Supervisory Patent Examiner, Art Unit 2844

Notice of References Cited	Application/Control No. 16/790,198	Applicant(s)/Patent Under Reexamination KASTNER-JUNG et al.	
	Examiner James H Cho	Art Unit 2844	Page 1 of 1

U.S. PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date MM-YYYY	Name	CPC Classification	US Classification
*	A	US-20110187668-A1	08-2011	Hente; Dirk	G06F3/0443	345/173
*	B	US-20110096504-A1	04-2011	Hild; Olaf Ruediger	H01L51/5246	361/704
*	C	US-20030071259-A1	04-2003	Yoshida, Hiroaki	C08G61/126	257/40
*	D	US-20040022058-A1	02-2004	Birrell, Peter Charles	F21V23/005	362/249.01
*	E	US-6926572-B2	08-2005	Park; Sang Hee	C23C16/45525	427/255.28
*	F	US-20020003403-A1	01-2002	Ghosh, Amalkumar P.	H01L51/5253	313/512
	G					
	H					
	I					
	J					
	K					
	L					
	M					

FOREIGN PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date MM-YYYY	Country	Name	CPC Classification
	N					
	O					
	P					
	Q					
	R					
	S					
	T					

NON-PATENT DOCUMENTS

*		Include as applicable: Author, Title Date, Publisher, Edition or Volume, Pertinent Pages)
	U	
	V	
	W	
	X	

*A copy of this reference is not being furnished with this Office action. (See MPEP § 707.05(a).)
Dates in MM-YYYY format are publication dates. Classifications may be US or foreign.

Index of Claims	Application/Control No.	Applicant(s)/Patent Under Reexamination
	16/790,198	KASTNER-JUNG et al.
	Examiner	**Art Unit**
	James H Cho	2844

✓	Rejected	-	Cancelled	N	Non-Elected	A	Appeal
=	Allowed	÷	Restricted	I	Interference	O	Objected

CLAIMS

☐ Claims renumbered in the same order as presented by applicant ☐ CPA ☐ T.D. ☐ R.1.47

CLAIM		DATE								
Final	Original	05/05/2021								
	1	✓								
	2	✓								
	3	✓								
	4	✓								
	5	✓								
	6	✓								
	7	✓								
	8	✓								
	9	✓								
	10	✓								
	11	✓								
	12	✓								
	13	✓								

Search Notes	Application/Control No.	Applicant(s)/Patent Under Reexamination
	16/790,198	KASTNER-JUNG et al.
	Examiner	Art Unit
	James H Cho	2844

CPC - Searched*		
Symbol	Date	Examiner
H05B47/125 H05B47/165 H01L51/506 F21S10/02 H05B47/105 H05B45/60 H05B47/16 F24D19/06 B60Q3/745 B60Q3/30 B60Q1/268 B60Q7/00 (text search, see the search history printout)	04/27/2021	JC
B05B1/18 F21V23/0442 F21V33/0016 F21V33/004 F21V33/0052 F21V33/006 G04C19/02 G04G11/00 G04G13/023 H05B33/22(text search, see the search history printout)	04/27/2021	JC

CPC Combination Sets - Searched*		
Symbol	Date	Examiner

US Classification - Searched*			
Class	Subclass	Date	Examiner

* See search history printout included with this form or the SEARCH NOTES box below to determine the scope of the search.

Search Notes		
Search Notes	Date	Examiner
BRS text search, see the search history printout	04/27/2021	JC

Interference Search			
US Class/CPC Symbol	US Subclass/CPC Group	Date	Examiner

Attorney Docket # 5367-694PCON2/474410 Patent

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Continuation Application of
Ulrich KASTNER-JUNG et al.
Serial No.: TO BE ASSIGNED
Filing Date: CONCURRENTLY
For: Organic-Light-Emitting Diode

INFORMATION DISCLOSURE STATEMENT

Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

S I R:

In compliance with the duty of disclosure under 37 C.F.R. § 1.56 and in accordance with the practice under 37 C.F.R. §§ 1.97 and 1.98, the Examiner's attention is directed to the documents listed on the enclosed Form PTO/SB/08a.

Because (1) the parent application of this continuation application is identified as U.S. Application Serial No. 15/651,508 filed on July 17, 2017; and (2) the information cited herein was cited or discussed in the parent application, copies of the cited documents are not enclosed pursuant to 37 C.F.R. § 1.98(d).

It is respectfully requested that the above information be considered by the Examiner and that the copy of the enclosed Form PTO/SB/08a be returned indicating that such information has been considered.

In accordance with 37 C.F.R §§1.97(g) and (h), the filing of this Information Disclosure Statement should not be construed as a representation that a search has been made or that information cited is, or is considered to be, material to patentability as defined in §1.56(b), or that any cited document listed or attached

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /JC/

SDC EX. 1027 - 311/489

is (or constitutes) prior art. Unless otherwise indicated, the date of publication indicated for an item is taken from the face of the item and Applicants reserve the right to prove that the date of publication is in fact different.

If any fees or charges are deemed required at this time in connection with the application, the same may be charged to our Patent and Trademark Office Deposit Account No. 503111.

Respectfully submitted,
Cozen O'Connor

By /Edward M. Weisz/
Edward M. Weisz
Reg. No. 37,257
277 Park Avenue
New York, New York 10172
(212) 883-4900

Dated: February 13, 2020

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /JC/ SDC EX. 1027 - 312/489

PTO/SB/08A (04-03)
Approved for use through 04/30/2003. OMB 0651-0031
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number

Substitute for Form 1449/PTO	*Complete if Known*	
INFORMATION DISCLOSURE STATEMENT BY APPLICANT (Use as many sheets as necessary)	Application Number	
	Filing Date	
	First Named Inventor	Ulrich KASTNER-JUNG
	Art Unit	
	Examiner Name	
Sheet 1 of 4	Attorney Docket No.	5367-694PCON2/474410

U.S. PATENT DOCUMENTS

Examiner Initials*	Cite No. [1]	Document Number Number-Kind-Code [2] (if known)	Publication Date MM-DD-YYYY	Name of Patentee or Applicant of Cited Document	Pages, Columns, Lines, Where Relevant Passages or Relevant Figures Appear
		US-2007/0278937	12-06-2007	Forrest et al.	
		US-2003/0064540	04-03-2003	Auch et al.	
		US-7,280,439	10-09-2007	Shaddox	
		US-2003/0231495	12-18-2003	Searfoss, III	
		US-6,236,622	05-22-2001	Blackman	
		US-2008/0219013	09-11-2008	Budinger et al.	
		US-7,317,210	01-08-2008	Osram Opto Semiconductors GmbH	
		US-2009/0039272	02-12-2009	Osram Opto Semiconductors GmbH	
		US-7,922,358	04-12-2011	Osram Opto Semiconductors GmbH	
		US-2001/0052752	12-2001	Ghosh	
		US-2002/0125822	09-2002	Graff	
		US-2002/0167270	11-2002	Siwinski	
		US-2003/0071804	04-2003	Yamazaki	
		US-2003/0121767	07-2003	Caldwell	
		US-2003/0175553	09-2003	Thompson	
		US-2003/0222577	12-2003	Lu	
		US-2004/0113542	06-2004	Hsiao	
		US-2005/0099824	05-2005	Dowling	
		US-2006/0049381	03-2006	Klein	
		US-2007/0278937	12-2007	Forrest	
		US-2008/0248191	10-2008	Daniels	
		US-2010/0157585	06-2010	Diekmann	
		US-2012/0258294	10-2012	Leyder	
		US-5,734,225	03-1998	Biebuyck et al.	
		US-5,895,228	04-1999	Biebuyck	
		US-7,733,008	06-08-2010	Agency for Science Tech. & Research	
		US-2005/0231101	10-20-2005	Chen	
		US-2001/0043046	11-22-2001	Fukunaga	
		US-2007/0114520	05-24-2007	Osram Opto Seminconductors GmbH	
		US-2007/0230211	10-04-2007	Canon KK	
		US-2009/0072711	03-19-2009	Thomson Licensing	
		US-7,560,727	07-14-2009	Ishikawa	

Examiner Signature	/JAMES H CHO/	Date Considered	04/26/2021

*EXAMINER: Initial if reference considered, whether or not citation is in conformance with MPEP 609. Draw line through citation if not in conformance and not considered. Include copy of this form with next communication to applicant. [1] Applicant's unique citation designation number (optional). [2] See Kinds Codes of USPTO Patent Documents at www.uspto.gov or MPEP 901.04. [3] Enter Office that issued the document, by the two-letter code (WIPO Standard ST.3). [4] For Japanese patent documents, the indication of the year of the reign of the Emperor must precede the serial number of the patent document. [5] Kind of document by the appropriate symbols as indicated on the document under WIPO Standard ST. 16 if possible. [6] Applicant is to place a check mark here if English language Translation is attached. This collection of information is required by 37 CFR 1.97 and 1.98. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, Washington, DC 20231.**

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /JC/

PTO/SB/08A (04-03)
Approved for use through 04/30/2003. OMB 0651-0031
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number

Substitute for Form 1449/PTO	*Complete if Known*	
	Application Number	
	Filing Date	
INFORMATION DISCLOSURE STATEMENT BY APPLICANT	First Named Inventor	Ulrich KASTNER-JUNG
	Art Unit	
(Use as many sheets as necessary)	Examiner Name	
Sheet 2 of 4	Attorney Docket No.	5367-694PCON2/474410

FOREIGN PATENT DOCUMENTS

Examiner Initials*	Cite No. [1]	Foreign Patent Document Country Code[3]- Number[4]-Kind-Code [5] (if known	Publication Date MM-DD-YYYY	Name of Patentee or Applicant of Cited Document	Pages, Columns, Lines, Where Relevant Passages or Relevant Figures Appear	T[6]
		DE 10 2006 037 222	02-14-2008	Swoboda et al.		
		JP 2007-294143	11-08-2007	Matsuura		
		WO 2008/110959	09-18-2008	Van Woudenberg et al.		
		WO 2008/146232	12-04-2008	Schlangen et al.		
		DE 10308514	09-09-2004	Schott Glas		
		DE 10332956	02-10-2005	Woehr Richard GmbH		
		KR 20080081255	09-09-2008	Osram Opto Semiconductors GmbH		
		KR 20020079438	10-19-2002	Eastman Kodak Co.		
		DE 102008051132	01-21-2010	Osram Opto Semiconductors GmbH		
		WO 2009/040401	04-02-2009	Osram Opto Semiconductors GmbH		
		WO 2009/074127	06-18-2009	Osram Opto Semiconductors GmbH		
		WO 2009/095005	08-06-2009	Osram Opto Semiconductors GmbH		
		WO 2009/106067	09-03-2009	Osram Opto Semiconductors GmbH		
		WO 2010/006571	01-21-2010	Osram Opto Semiconductors GmbH		
		WO 2008/040323	04-2008	Diekmann		
		WO 2008/146232	12-2008	Schlangen		
		JP 2005-510851	04-21-2005	Agency for Science, Tech. & Research		
		KR 100743545	07-23-2007	Lee Young Jong		
		KR 1020050065948	11-11-2013	LG Electronics Inc.		
		JP 2002-033198	01-31-2002	Semiconductor Energy Lab		
		DE 102007059732	06-18-2009	OSRAM Opto Semiconductors GmbH		
		KR 2008-0042275	05-15-2008	Oh et al.		

Examiner Signature		Date Considered	

*EXAMINER: Initial if reference considered, whether or not citation is in conformance with MPEP 609. Draw line through citation if not in conformance and not considered. Include copy of this form with next communication to applicant. [1] Applicant's unique citation designation number (optional). [2] See Kinds Codes of USPTO Patent Documents at www.uspto.gov or MPEP 901.04. [3] Enter Office that issued the document, by the two-letter code (WIPO Standard ST.3). [4] For Japanese patent documents, the indication of the year of the reign of the Emperor must precede the serial number of the patent document. [5] Kind of document by the appropriate symbols as indicated on the document under WIPO Standard ST. 16 if possible. [6] Applicant is to place a check mark here if English language Translation is attached. This collection of information is required by 37 CFR 1.97 and 1.98. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, Washington, DC 20231.**

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /JC/

PTO/SB/08A (04-03)
Approved for use through 04/30/2003. OMB 0651-0031
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number

Substitute for Form 1449/PTO

INFORMATION DISCLOSURE STATEMENT BY APPLICANT

(Use as many sheets as necessary)

Sheet 3 of 4

Complete if Known	
Application Number	
Filing Date	
First Named Inventor	Ulrich KASTNER-JUNG
Art Unit	
Examiner Name	
Attorney Docket	5367-694P/CON2/474410

FOREIGN PATENT DOCUMENTS

Examiner Initials*	Cite No. [1]	Foreign Patent Document Country Code[3]- Number[4]- Kind-Code [5] (if known)	Publication Date MM-DD-YYYY	Name of Patentee or Applicant of Cited Document	Pages, Columns, Lines, Where Relevant Passages or Relevant Figures Appear	T[6]
		JP 2007-200887	08-09-2007	Dong-Soo et al.		
		JP 2004-296423	10-21-2004	Toshitaka et al.		
		JP 2008-538155	10-09-2008	Cok et al.		
		JP 4182467B2	11-19-2008	Takashi		
		JP 4228248B2	02-25-2009	Hideo et al.		
		JP 4637390B2	02-23-2011	Shunpei et al.		
		JP 4713010B2	06-29-2011	Kenji		
		JP 4742880B2	08-10-2011	Osamu et al.		
		JP 4828881B2	11-30-2011	Satoshi		
		JP 2003-195775	07-09-2003	Takashi		
		JP 2004-047179	02-12-2004	Tamotsu et al.		

Examiner Signature		Date Considered	

*EXAMINER: Initial if reference considered, whether or not citation is in conformance with MPEP 609. Draw line through citation if not in conformance and not considered. Include copy of this form with next communication to applicant. [1] Applicant's unique citation designation number (optional). [2] See Kinds Codes of USPTO Patent Documents at www.uspto.gov or MPEP 901.04. [3] Enter Office that issued the document, by the two-letter code (WIPO Standard ST.3). [4] For Japanese patent documents, the indication of the year of the reign of the Emperor must precede the serial number of the patent document. [5] Kind of document by the appropriate symbols as indicated on the document under WIPO Standard ST. 16 if possible. [6] Applicant is to place a check mark here if English language Translation is attached. This collection of information is required by 37 CFR 1.97 and 1.98. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, Washington, DC 20231.**

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /JC/

PTO/SB/08A (04-03)
Approved for use through 04/30/2003. OMB 0651-0031
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number

Substitute for Form 1449/PTO	Complete if Known	
INFORMATION DISCLOSURE STATEMENT BY APPLICANT (Use as many sheets as necessary)	Application Number	
	Filing Date	
	First Named Inventor	Ulrich KASTNER-JUNG
	Art Unit	
	Examiner Name	
Sheet 4 of 4	Attorney Docket No.	5367-694PCON2/474410

NON PATENT LITERATURE DOCUMENTS

Examiner Initials*	Cite No.[1]	Include name of the author (in CAPITAL LETTERS), title of the article (when appropriate), title of the item (book, magazine, journal, serial, symposium, catalog, etc.), date, page(s), volume-issue number(s), publisher, city and/or country where published.	T[2]
		Boffi Wedge. Stylepark, May 25, 2011. (1 page). Retrieved from http://www.stylepark.com/en/boffi/wedge.	
		Bus stop shelter intelligent series. May 25, 2011. (2 pages). Retrieved from http://www.wall.de/en/street_furniture/products?category_scope=bus_stop_shelter	
		Cristina Rubinetterie sandwich shower head – new electronic LED shower head, May 12, 2007. (3 pages). Retrieved from http://www.trendir.com/archives/001435.html.	
		Dornbracht RainSky E Showers by Rixson & Green Shortlands Ltd. September 2000. (1 page). Retrieved from http://www.rixson-green.co.uk/dornbracht_showers.htm.	
		Marketing-displays. Illuminated box CLP-S I freetstanding unit, one-sided (1200 x 1760 mm). May 25, 2011. (1 page). Retrieved from http://www.md-displayshop.de/ProductDetails.aspx?id=24&prodi...	
		LCD-Glass; Glass with LCD Film (max height 300 – max width 120). 2009. (2 pages). Retrieved from http://www.vetroin.co.uk/en/TECHNOLOGY/LDC-Glass.html no month	
		ThinkGeek:Lumadot LED Umbrella. May 25, 2011. (2 pages). Retrieved from http://www.thinkgeek.com/interests/moms/d16b/	
		Luceplan. Strip D22/4 – D22/4 EL. May 25, 2011. Retrieved from http://www.luceplan.com/Dynamic/Prodotti.php?intLangID=1&intC...	
		Multifunctional shower cabin- WELL BOX- Megius SpA. 2011. (1 page). Retrieved from http://www.archiexpo.com/prod/megius-spa/multifunctional-shower... no month	
		The General Properties of Si, Ge, SiGe, SiO2 and Si3N4 (June 2002, Virginia Semiconductor, Retrieved from the Internet: <URL www.virginiasemi.com/pdf/generalpropertiesSi62002.pdf>)	
		Edgar S. Zaus et al., "Design of Highly Transparent Organic Photodiodes, IEEE Transactions of Electron Devices, Vo. 55, No. 2, February 2008	
		N. R. Mowrer, "Polysiloxanes, Ameron International Performance Coatings and Finishes, November 2003	

Examiner Signature	/JAMES H CHO/	Date Considered	04/26/2021

*EXAMINER: Initial if reference considered, whether or not citation is in conformance with MPEP 609. Draw line through citation if not in conformance and not considered. Include copy of this form with next communication to applicant. [1]Applicant's unique citation designation number (optional). [2]See Kinds Codes of USPTO Patent Documents at www.uspto.gov or MPEP 901.04. [3]Enter Office that issued the document, by the two-letter code (WIPO Standard ST.3). [4]For Japanese patent documents, the indication of the year of the reign of the Emperor must precede the serial number of the patent document. [5]Kind of document by the appropriate symbols as indicated on the document under WIPO Standard ST. 16 if possible. [6]Applicant is to place a check mark here if English language Translation is attached. This collection of information is required by 37 CFR 1.97 and 1.98. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, Washington, DC 20231.**

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /JC/

Bibliographic Data

Application No: 16/790,198

Foreign Priority claimed: (●) Yes ( ) No

35 USC 119 (a-d) conditions met: [✓] Yes [ ] No [ ] Met After Allowance

Verified and Acknowledged: /JAMES H CHO/ Examiner's Signature | Initials

Title: Organic-Light-Emitting Diode

FILING or 371(c) DATE	CLASS	GROUP ART UNIT	ATTORNEY DOCKET NO.
02/13/2020	315	2844	PICTIV 3.3F-001 CC [2]
RULE			

APPLICANTS

PICTIVA DISPLAYS INTERNATIONAL LIMITED, Dublin, IRELAND

INVENTORS

Ulrich KASTNER-JUNG, Munich, GERMANY

Markus KLEIN, Tegernheim, GERMANY

Stan MAES, Dilsen-Stokken, BELGIUM

Romana SIGL, Salzburg, AUSTRIA

Annette HAID, Salzburg, AUSTRIA

Stephan LINTNER, Salzburg, AUSTRIA

Julian HERGET, Marktschellenberg, GERMANY

Gregor MATJAN, Bergheim, AUSTRIA

CONTINUING DATA

This application is a CON of 15651508 07/17/2017 PAT 10605422

15651508 is a CON of 13139514 01/03/2012 PAT 9797567

13139514 is a 371 of PCT/DE2009/001741 12/09/2009

FOREIGN APPLICATIONS

GERMANY DE10 2008 061 563.3 12/11/2008

IF REQUIRED, FOREIGN LICENSE GRANTED**

02/28/2020

STATE OR COUNTRY

GERMANY

ADDRESS

Botos Churchill IP Law LLP

430 Mountain Avenue

Suite 401
New Providence, NJ 07974
UNITED STATES

FILING FEE RECEIVED

$2,520

EAST Search History

EAST Search History (Prior Art)

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
S241	2	(("10605422") or ("9797567")).PN.	US-PGPUB; USPAT; USOCR	OR	OFF	2021/04/26 08:11
S242	32	("20010043046" | "20010052752" | "20020125822" | "20020167270" | "20030064540" | "20030071804" | "20030121767" | "20030175553" | "20030222577" | "20030231495" | "20040113542" | "20050099824" | "20050231101" | "20060049381" | "20070114520" | "20070230211" | "20070278937" | "20080219013" | "20080248191" | "20090039272" | "20090072711" | "20100157585" | "20120258294" | "5734225" | "5895228" | "6236622" | "7205714" | "7280439" | "7317210" | "7560727" | "7733008" | "7922358").PN. OR ("10605422").URPN.	US-PGPUB; USPAT; USOCR	OR	OFF	2021/04/26 08:13
S244	45	S242 S243	US-PGPUB; USPAT; USOCR	OR	OFF	2021/04/26 08:14
S243	37	("20010052752" | "20020125822" | "20020167270" | "20030064540" | "20030071804" | "20030121767" | "20030175553" | "20030222577" | "20030231495" | "20040113542" | "20050099824" | "20060049381" | "20070278937" | "20080219013" | "20080248191" | "20090039272" | "20100157585" | "20120258294" | "5734225" | "6236622" | "7280439" | "7317120" | "7317210" | "7733008" | "7922358").PN. OR ("9797567").URPN.	US-PGPUB; USPAT; USOCR	OR	OFF	2021/04/26 08:14
S245	1	("20200182422").PN.	US-PGPUB; USPAT; USOCR	OR	OFF	2021/04/26 10:11
S246	1	S245 and radiation same (encapsulation and seal$4)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO;	OR	OFF	2021/04/26 10:12

			DERWENT; IBM_TDB			
S247	1	S245 and radiation same (encapsulation and seal$4 and (flexible bendable rolled))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/04/26 10:14
S248	37	(US-20160238234-$ or US-20100076527-$ or US-20080138624-$ or US-20020003403-$ or US-20110133628-$ or US-20090173957-$ or US-20090091258-$ or US-20080188156-$ or US-20080138539-$ or US-20070114520-$ or US-20060128042-$ or US-20090039272-$ or US-20010043046-$ or US-20050156520-$ or US-20050242709-$ or US-20040080938-$ or US-20090167981-$ or US-20070230211-$ or US-20070176195-$ or US-20070153543-$ or US-20090072711-$ or US-20120256534-$ or US-20100044730-$).did. or (US-6926572-$ or US-6884465-$ or US-7922358-$ or US-7733008-$ or US-6331063-$ or US-6575584-$ or US-8987711-$ or US-7560727-$ or US-7358663-$ or US-7205714-$ or US-8123391-$ or US-9797567-$ or US-7733011-$ or US-6703780-$).did.	US-PGPUB; USPAT	OR	OFF	2021/04/26 10:36
S249	74,089	(F21S10/02 H05B47/105 H05B45/60 H05B47/16 F24D19/06 B60Q3/745 B60Q3/30 B60Q1/268 B60Q7/00 B05B1/18 F21V23/0442 F21V33/0016 F21V33/004 F21V33/0052 F21V33/006 G04C19/02 G04G11/00 G04G13/023 H05B33/22).cpc.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/04/26 10:39
S251	12,520	(H05B47/125 H05B47/165 H01L51/506).cpc.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/04/26 10:40
S252	2,007	(S249 S251) and radiat$4 and (encapsulat$4 seal$4 environment$4 temperature moisture water) and (flex$5 bend$5 rolled)	US-PGPUB; USPAT; USOCR; FPRS; EPO;	OR	ON	2021/04/26 10:43

			JPO; DERWENT; IBM_TDB			
S253	1,359	S252 and (light$3emit$4 LED.u/c. light$3 adj2 emit$4) and (infrared UV.u/c. ultra$3violet)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/04/26 10:44
S254	224	S253 and (touch$4sens$5 touch$4 near3 sens$5)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/04/26 10:45
S258	115	S254 and (flex$5 bend$5 rolled) with (layer substrate planar plane display$4 panel screen monitor die board)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/04/26 10:48
S259	79	S258 and organic	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/04/26 10:49
S260	17	S248 and (flex$5 bend$5 rolled) with (layer substrate planar plane display$4 panel screen monitor die board)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/04/26 11:29
S261	1,009	S251 and (light$3emit$4 LED.u/c. light$3 adj2 emit$4) with organic and (infrared UV.u/c. ultra$3violet)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/04/26 11:40
S262	285	S261 and @ad<"20091231"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO;	OR	ON	2021/04/26 11:41

			DERWENT; IBM_TDB			
S263	89	S262 and (hermetic$5 environment$4 temperature moisture water) with (encapsulat$5 seal$4 tight$4)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/04/26 11:43
S264	32,031	(S249 S251) and @ad<"20091231"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/04/26 12:53
S265	1,203	S264 and (flex$5 bend$5 rolled) with (layer substrate planar plane display$4 panel screen monitor die board)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/04/26 12:54
S266	29	S265 and (touch$4sens$5 touch$4 near3 sens$5)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/04/26 12:55
S267	13	S266 and (light$3emit$4 LED.u/c. light$3 adj2 emit$4) with organic	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/04/26 12:56
S268	1	("20200182422").PN.	US-PGPUB; USPAT; USOCR	OR	OFF	2021/04/26 14:42
S270	27,074	S269 and @ad<"20091231"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/04/26 14:51

S269	125,438	(flex$5 bend$5 rolled) with (light$3emit$4 LED.u/c. light$3 adj2 emit$4)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/04/26 14:51
S273	1,775	S270 and organic and (hermetic$5 environment$4 temperature moisture water) with (encapsulat$5 seal$4 tight$4)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/04/26 14:54
S274	877	S273 and (light$3emit$4 LED.u/c. light$3 adj2 emit$4) same (infrared UV.u/c. ultra$3violet)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/04/26 14:56
S275	874	S274 and (layer substrate plane planar die)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/04/26 14:57
S276	626	S274 and (layer substrate plane planar die) near4 organic	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/04/26 14:58
S278	253	S276 and flexible and encapsulat$4	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/04/26 15:01
S277	610	S276 and flexible	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/04/26 15:01

S279	2	(("20070114520") or ("20040022058")).PN.	US-PGPUB; USPAT; USOCR	OR	OFF	2021/04/26 15:14
S280	93	S278 and (bend$4 rolled)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/04/26 15:19
S281	1	("20100295812").PN.	US-PGPUB; USPAT; USOCR	OR	OFF	2021/04/26 15:20
S283	2,689	S282 and @ad<"20081231"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/04/26 15:23
S282	14,534	bendable with (screen panel display)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2021/04/26 15:23
S285	309	S283 and (light$3emit$4 LED.u/c. light$3 adj2 emit$4) same (display screen panel)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/04/26 15:24
S284	2,689	S282 and @ad<"20081231"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/04/26 15:24
S286	155	S285 and organic	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/04/26 15:25

S287	1	("20040124765").PN.	US-PGPUB; USPAT; USOCR	OR	OFF	2021/04/26 15:28
S288	1	("20060132461").PN.	US-PGPUB; USPAT; USOCR	OR	OFF	2021/04/26 15:29
S289	8	("20020033666" | "20020043929" | "20040032207" | "20040191566" | "20050117293" | "20060290595" | "20070047058" | "20070132371").PN.	US-PGPUB; USPAT	OR	OFF	2021/04/26 15:49
S290	11	("2011/0096504").URPN.	USPAT	OR	OFF	2021/04/26 15:56
S294	943,316	(flexi$5 rolled bend$5) with (screen panel display monitor board PCB.u/c.)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/04/27 10:08
S295	333,328	S294 and @ad<"20081231"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/04/27 10:09
S296	3,903	S295 and (touch$4sens$5 touch$4 near3 sens$5) with (screen panel display monitor board PCB.u/c.)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/04/27 10:10
S299	55	S298 and bend$5	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/04/27 10:11
S298	96	S297 and encapsulat$4	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/04/27 10:11

S297	511	S296 and (organic$2diode organic near4 (diode LED.u/c.))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/04/27 10:11
S300	2	(("20100295812") or ("20110096504")).PN.	US-PGPUB; USPAT; USOCR	OR	OFF	2021/04/27 10:19
S302	11	S296 and (infrared UV.u/c. ultra$3violet) same ((wavelength and radiation) and OLED.u/c.)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/04/27 10:29
S303	30,449	(infrared UV.u/c. ultra$3violet) with ((wavelength and radiation) and (LED.u/c. OLED.u/c. light$3emit$4 light adj2 emit$4))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/04/27 10:31
S304	11,088	S303 and @ad<"20081231"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/04/27 10:32
S305	1,387	S304 and encapsulat$4	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/04/27 10:33
S306	151	S305 and (flexi$5 bend$4) with (LED.u/c. OLED.u/c. light$3emit$4 light adj2 emit$4)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/04/27 10:35
S307	57	S306 and oled	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO;	OR	ON	2021/04/27 10:36

			DERWENT; IBM_TDB			
S308	8	S307 and filter$4 with wavelength	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/04/27 11:03
S309	108	S305 and photochromic with (wavelength and UV.u/c. infrared IR.u/c.)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/04/27 11:50
S310	108	S309 and organic	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/04/27 11:51
S312	27	S311 not S310	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/04/27 11:55
S311	135	S304 and photochromic with (wavelength and UV.u/c. infrared IR.u/c.)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/04/27 11:55
S314	1	S312 and oled	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/04/27 11:56
S313	1,434,815	S312 an oled	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO;	OR	ON	2021/04/27 11:56

			DERWENT; IBM_TDB			
S316	106	S315 and (screen panel display monitor)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/04/27 11:58
S315	120	S304 and OLED.u/c. with (wavelength UV.u/c. IR.u/c. infrared ultra$2violet)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/04/27 11:58
S317	0	S316 and photochromic with (wavelength UV.u/c. infrared IR.u/c.)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/04/27 13:01
S318	35	OLED.u/c. same (photochromic with (wavelength UV.u/c. infrared IR.u/c.))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/04/27 13:02
S320	6	S319 and @ad<"20081231"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/04/27 13:04
S319	35	OLED.u/c. same (photochromic with (wavelength UV.u/c. infrared IR.u/c.))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/04/27 13:04
S323	79	S322 and spectrum with wavelength	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO;	OR	ON	2021/04/27 13:12

			DERWENT; IBM_TDB			
S322	283	S321 and @ad<"20081231"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/04/27 13:12
S321	1,580	OLED.u/c. same (generat$4 with (wavelength UV.u/c. infrared IR.u/c.))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/04/27 13:12
S324	22	S323 and ((LED.u/c. OLED.u/c.) with (UV.u/c. infrared IR.u/c.))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/04/27 13:14
S326	2	S323 and ((LED.u/c. OLED.u/c.) and (UV.u/c.) and (infrared IR.u/c.))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/04/27 13:16
S325	0	S323 and ((LED.u/c. OLED.u/c.) with (UV.u/c.) and (infrared IR.u/c.))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/04/27 13:16
S327	11	S323 and ((LED.u/c. OLED.u/c.) and (UV.u/c. ultra$3violet) and (infrared IR.u/c.))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/04/27 13:19
S328	2	(("10605422") or ("9797567")).PN.	US-PGPUB; USPAT; USOCR	OR	OFF	2021/04/27 13:42

EAST Search History (Interference)

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
S291	2	"Term Removed" or "Term Removed"	US-PGPUB; USPAT	OR	OFF	2021/04/26 10:36

5/4/2021 8:12:17 AM
C:\Users\jcho\Documents\EAST\Workspaces\16790198.wsp

PTO/SB/08a (03-15)
Approved for use through 07/31/2016. OMB 0651-0031
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

INFORMATION DISCLOSURE STATEMENT BY APPLICANT

(Not for submission under 37 CFR 1.99)

Application Number	16790198
Filing Date	2020-02-13
First Named Inventor	Ulrich Kastner-Jung
Art Unit	2844
Examiner Name	James Hyonchol Cho
Attorney Docket Number	PICTIV 3.3F-001 CC [2]

U.S.PATENTS Remove

Examiner Initial*	Cite No	Patent Number	Kind Code[1]	Issue Date	Name of Patentee or Applicant of cited Document	Pages,Columns,Lines where Relevant Passages or Relevant Figures Appear
	1	7205714	B2	2007-04-17	CHEN	

If you wish to add additional U.S. Patent citation information please click the Add button. Add

U.S.PATENT APPLICATION PUBLICATIONS Remove

Examiner Initial*	Cite No	Publication Number	Kind Code[1]	Publication Date	Name of Patentee or Applicant of cited Document	Pages,Columns,Lines where Relevant Passages or Relevant Figures Appear
	1					

If you wish to add additional U.S. Published Application citation information please click the Add button. Add

FOREIGN PATENT DOCUMENTS Remove

Examiner Initial*	Cite No	Foreign Document Number[3]	Country Code[2] i	Kind Code[4]	Publication Date	Name of Patentee or Applicant of cited Document	Pages,Columns,Lines where Relevant Passages or Relevant Figures Appear	T[5]
	1							

If you wish to add additional Foreign Patent Document citation information please click the Add button Add

NON-PATENT LITERATURE DOCUMENTS Remove

Examiner Initials*	Cite No	Include name of the author (in CAPITAL LETTERS), title of the article (when appropriate), title of the item (book, magazine, journal, serial, symposium, catalog, etc), date, pages(s), volume-issue number(s), publisher, city and/or country where published.	T[5]

INFORMATION DISCLOSURE STATEMENT BY APPLICANT (Not for submission under 37 CFR 1.99)		
	Application Number	16790198
	Filing Date	2020-02-13
	First Named Inventor	Ulrich Kastner-Jung
	Art Unit	2844
	Examiner Name	James Hyonchol Cho
	Attorney Docket Number	PICTIV 3.3F-001 CC [2]

	1	

If you wish to add additional non-patent literature document citation information please click the Add button Add

EXAMINER SIGNATURE

Examiner Signature		Date Considered	

*EXAMINER: Initial if reference considered, whether or not citation is in conformance with MPEP 609. Draw line through a citation if not in conformance and not considered. Include copy of this form with next communication to applicant.

[1] See Kind Codes of USPTO Patent Documents at www.USPTO.GOV or MPEP 901.04. [2] Enter office that issued the document, by the two-letter code (WIPO Standard ST.3). [3] For Japanese patent documents, the indication of the year of the reign of the Emperor must precede the serial number of the patent document. [4] Kind of document by the appropriate symbols as indicated on the document under WIPO Standard ST.16 if possible. [5] Applicant is to place a check mark here if English language translation is attached.

INFORMATION DISCLOSURE STATEMENT BY APPLICANT (Not for submission under 37 CFR 1.99)		
	Application Number	16790198
	Filing Date	2020-02-13
	First Named Inventor	Ulrich Kastner-Jung
	Art Unit	2844
	Examiner Name	James Hyonchol Cho
	Attorney Docket Number	PICTIV 3.3F-001 CC [2]

CERTIFICATION STATEMENT

Please see 37 CFR 1.97 and 1.98 to make the appropriate selection(s):

That each item of information contained in the information disclosure statement was first cited in any communication from a foreign patent office in a counterpart foreign application not more than three months prior to the filing of the information disclosure statement. See 37 CFR 1.97(e)(1).

OR

☐ That no item of information contained in the information disclosure statement was cited in a communication from a foreign patent office in a counterpart foreign application, and, to the knowledge of the person signing the certification after making reasonable inquiry, no item of information contained in the information disclosure statement was known to any individual designated in 37 CFR 1.56(c) more than three months prior to the filing of the information disclosure statement. See 37 CFR 1.97(e)(2).

See attached certification statement.

✓ The fee set forth in 37 CFR 1.17 (p) has been submitted herewith.

✓ A certification statement is not submitted herewith.

SIGNATURE

A signature of the applicant or representative is required in accordance with CFR 1.33, 10.18. Please see CFR 1.4(d) for the form of the signature.

Signature	/Richard J. Botos/	Date (YYYY-MM-DD)	2021-07-07
Name/Print	Richard J. Botos	Registration Number	32016

This collection of information is required by 37 CFR 1.97 and 1.98. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 1 hour to complete, including gathering, preparing and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.**

Privacy Act Statement

The Privacy Act of 1974 (P.L. 93-579) requires that you be given certain information in connection with your submission of the attached form related to a patent application or patent. Accordingly, pursuant to the requirements of the Act, please be advised that: (1) the general authority for the collection of this information is 35 U.S.C. 2(b)(2); (2) furnishing of the information solicited is voluntary; and (3) the principal purpose for which the information is used by the U.S. Patent and Trademark Office is to process and/or examine your submission related to a patent application or patent. If you do not furnish the requested information, the U.S. Patent and Trademark Office may not be able to process and/or examine your submission, which may result in termination of proceedings or abandonment of the application or expiration of the patent.

The information provided by you in this form will be subject to the following routine uses:

1. The information on this form will be treated confidentially to the extent allowed under the Freedom of Information Act (5 U.S.C. 552) and the Privacy Act (5 U.S.C. 552a). Records from this system of records may be disclosed to the Department of Justice to determine whether the Freedom of Information Act requires disclosure of these record s.

2. A record from this system of records may be disclosed, as a routine use, in the course of presenting evidence to a court, magistrate, or administrative tribunal, including disclosures to opposing counsel in the course of settlement negotiations.

3. A record in this system of records may be disclosed, as a routine use, to a Member of Congress submitting a request involving an individual, to whom the record pertains, when the individual has requested assistance from the Member with respect to the subject matter of the record.

4. A record in this system of records may be disclosed, as a routine use, to a contractor of the Agency having need for the information in order to perform a contract. Recipients of information shall be required to comply with the requirements of the Privacy Act of 1974, as amended, pursuant to 5 U.S.C. 552a(m).

5. A record related to an International Application filed under the Patent Cooperation Treaty in this system of records may be disclosed, as a routine use, to the International Bureau of the World Intellectual Property Organization, pursuant to the Patent Cooperation Treaty.

6. A record in this system of records may be disclosed, as a routine use, to another federal agency for purposes of National Security review (35 U.S.C. 181) and for review pursuant to the Atomic Energy Act (42 U.S.C. 218(c)).

7. A record from this system of records may be disclosed, as a routine use, to the Administrator, General Services, or his/her designee, during an inspection of records conducted by GSA as part of that agency's responsibility to recommend improvements in records management practices and programs, under authority of 44 U.S.C. 2904 and 2906. Such disclosure shall be made in accordance with the GSA regulations governing inspection of records for this purpose, and any other relevant (i.e., GSA or Commerce) directive. Such disclosure shall not be used to make determinations about individuals.

8. A record from this system of records may be disclosed, as a routine use, to the public after either publication of the application pursuant to 35 U.S.C. 122(b) or issuance of a patent pursuant to 35 U.S.C. 151. Further, a record may be disclosed, subject to the limitations of 37 CFR 1.14, as a routine use, to the public if the record was filed in an application which became abandoned or in which the proceedings were terminated and which application is referenced by either a published application, an application open to public inspections or an issued patent.

9. A record from this system of records may be disclosed, as a routine use, to a Federal, State, or local law enforcement agency, if the USPTO becomes aware of a violation or potential violation of law or regulation.

Electronic Patent Application Fee Transmittal

Application Number:	16790198
Filing Date:	13-Feb-2020
Title of Invention:	Organic-Light-Emitting Diode
First Named Inventor/Applicant Name:	Ulrich KASTNER-JUNG
Filer:	Richard J. Botos/Elizabeth Gagliano
Attorney Docket Number:	PICTIV 3.3F-001 CC [2]

Filed as Large Entity

Filing Fees for Utility under 35 USC 111(a)

Description	Fee Code	Quantity	Amount	Sub-Total in USD($)
Basic Filing:				
Pages:				
Claims:				
Miscellaneous-Filing:				
Petition:				
Patent-Appeals-and-Interference:				
Post-Allowance-and-Post-Issuance:				
Extension-of-Time:				

Description	Fee Code	Quantity	Amount	Sub-Total in USD($)
Miscellaneous:				
SUBMISSION- INFORMATION DISCLOSURE STMT	1806	1	260	260
		Total in USD ($)		**260**

Electronic Acknowledgement Receipt

EFS ID:	43189606
Application Number:	16790198
International Application Number:	
Confirmation Number:	1309
Title of Invention:	Organic-Light-Emitting Diode
First Named Inventor/Applicant Name:	Ulrich KASTNER-JUNG
Customer Number:	175540
Filer:	Richard J. Botos/Elizabeth Gagliano
Filer Authorized By:	Richard J. Botos
Attorney Docket Number:	PICTIV 3.3F-001 CC [2]
Receipt Date:	07-JUL-2021
Filing Date:	13-FEB-2020
Time Stamp:	15:35:43
Application Type:	Utility under 35 USC 111(a)

Payment information:

Submitted with Payment	yes
Payment Type	CARD
Payment was successfully received in RAM	$260
RAM confirmation Number	E202177F35592729
Deposit Account	
Authorized User	

The Director of the USPTO is hereby authorized to charge indicated fees and credit any overpayment as follows:

File Listing:

Document Number	Document Description	File Name	File Size(Bytes)/ Message Digest	Multi Part /.zip	Pages (if appl.)
1	Transmittal Letter	PICTIV_3_3F-001_CON_CON__2__-_Information_Disclosure_Statement_Transmittal.pdf	186932 1950666bc2f1c6e06dc0acf2f85b2f3bdbf712f5	no	1
Warnings:					
Information:					
2	Information Disclosure Statement (IDS) Form (SB08)	PICTIV_3_3F-001_CON_CON__2__-_Information_Disclosure_Statement.pdf	1038515 028add7b95c62543ed7653e375d6936fa74249fd	no	4
Warnings:					
Information:					
3	Fee Worksheet (SB06)	fee-info.pdf	30651 e15212f5941a49c49e2c33c3811564b752e3d489	no	2
Warnings:					
Information:					
		Total Files Size (in bytes):	1256098		

This Acknowledgement Receipt evidences receipt on the noted date by the USPTO of the indicated documents, characterized by the applicant, and including page counts, where applicable. It serves as evidence of receipt similar to a Post Card, as described in MPEP 503.

New Applications Under 35 U.S.C. 111

If a new application is being filed and the application includes the necessary components for a filing date (see 37 CFR 1.53(b)-(d) and MPEP 506), a Filing Receipt (37 CFR 1.54) will be issued in due course and the date shown on this Acknowledgement Receipt will establish the filing date of the application.

National Stage of an International Application under 35 U.S.C. 371

If a timely submission to enter the national stage of an international application is compliant with the conditions of 35 U.S.C. 371 and other applicable requirements a Form PCT/DO/EO/903 indicating acceptance of the application as a national stage submission under 35 U.S.C. 371 will be issued in addition to the Filing Receipt, in due course.

New International Application Filed with the USPTO as a Receiving Office

If a new international application is being filed and the international application includes the necessary components for an international filing date (see PCT Article 11 and MPEP 1810), a Notification of the International Application Number and of the International Filing Date (Form PCT/RO/105) will be issued in due course, subject to prescriptions concerning national security, and the date shown on this Acknowledgement Receipt will establish the international filing date of the application.

I hereby certify that this paper (along with any paper referred to as being attached or enclosed) is being transmitted via the Office electronic filing system in accordance with 37 CFR § 1.6(a)(4).

Dated: July 7, 2021
Electronic Signature for Richard J. Botos: /Richard J. Botos/

Docket No. PICTIV 3.3F-001 CON CON [2]
(PATENT)

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Patent Application of:
Kastner-Jung et al.

Application No.: 16/790,198 | Confirmation No.: 1309

Filed: February 13, 2020 | Art Unit: 2844

For: ORGANIC-LIGHT-EMITTING DIODE | Examiner: James Hynchol Cho

Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

INFORMATION DISCLOSURE STATEMENT

Dear Sir:

It is respectfully requested that the reference listed on the attached form be made of record and considered with respect to the above-referenced U.S. patent application. A copy of each reference which is not a U.S. patent or patent application is enclosed. Submission of the present Information Disclosure Statement should not be taken as an admission that the cited reference is legally available prior art or that the same is pertinent or material.

All required fees are being paid via credit card. However, credit any overpayments to our Deposit Account No. 60-1866.

Dated: July 7, 2021

Respectfully submitted,
Electronic signature: /Richard J. Botos/
Richard J. Botos
Registration No.: 32,016
BOTOS CHURCHILL IP LAW LLP
430 Mountain Ave. Suite 401
New Providence, New Jersey 07974
(908) 738-1770
Attorney for Applicant

4838-7905-0481, v. 1

Electronic Acknowledgement Receipt

EFS ID:	43529491
Application Number:	16790198
International Application Number:	
Confirmation Number:	1309
Title of Invention:	Organic-Light-Emitting Diode
First Named Inventor/Applicant Name:	Ulrich KASTNER-JUNG
Customer Number:	175540
Filer:	Richard J. Botos/Elizabeth Gagliano
Filer Authorized By:	Richard J. Botos
Attorney Docket Number:	PICTIV 3.3F-001 CC [2]
Receipt Date:	17-AUG-2021
Filing Date:	13-FEB-2020
Time Stamp:	13:45:57
Application Type:	Utility under 35 USC 111(a)

Payment information:

Submitted with Payment	no

File Listing:

Document Number	Document Description	File Name	File Size(Bytes)/ Message Digest	Multi Part /.zip	Pages (if appl.)
1	Miscellaneous Incoming Letter	PICTIV_3_3F-001_CON_CON_Matter_2_Amendment_Transmittal.pdf	908338 d6ec1d0e66f9ce2442f5d9e4b33bdaefbe389eae	no	1

Warnings:

Information:					
2	Amendment Copy Claims/Response to Suggested Claims	PICTIV_3_3F-001_CON_CON_Matter_2_Amendment_in_Response_to_NFOA_5_17_2021.pdf	5967562 dd560281d7233ecd429b38c55cdc94e6a631bcd8	no	11
Warnings:					
Information:					
			Total Files Size (in bytes):	6875900	

This Acknowledgement Receipt evidences receipt on the noted date by the USPTO of the indicated documents, characterized by the applicant, and including page counts, where applicable. It serves as evidence of receipt similar to a Post Card, as described in MPEP 503.

New Applications Under 35 U.S.C. 111

If a new application is being filed and the application includes the necessary components for a filing date (see 37 CFR 1.53(b)-(d) and MPEP 506), a Filing Receipt (37 CFR 1.54) will be issued in due course and the date shown on this Acknowledgement Receipt will establish the filing date of the application.

National Stage of an International Application under 35 U.S.C. 371

If a timely submission to enter the national stage of an international application is compliant with the conditions of 35 U.S.C. 371 and other applicable requirements a Form PCT/DO/EO/903 indicating acceptance of the application as a national stage submission under 35 U.S.C. 371 will be issued in addition to the Filing Receipt, in due course.

New International Application Filed with the USPTO as a Receiving Office

If a new international application is being filed and the international application includes the necessary components for an international filing date (see PCT Article 11 and MPEP 1810), a Notification of the International Application Number and of the International Filing Date (Form PCT/RO/105) will be issued in due course, subject to prescriptions concerning national security, and the date shown on this Acknowledgement Receipt will establish the international filing date of the application.

AMENDMENT TRANSMITTAL LETTER

Docket No.
PICTIV 3.3F-001 CC [2]

Application No.	Filing Date	Examiner	Art Unit
16/790,198 / Conf. #1309	February 13, 2020	James Hyonchol Cho	2844

Applicant(s): PICTIVA DISPLAYS INTERNATIONAL LIMITED

Invention: ORGANIC-LIGHT-EMITTING DIODE

TO THE COMMISSIONER FOR PATENTS

Transmitted herewith is an amendment in the above-identified application.

The fee has been calculated and is transmitted as shown below.

CLAIMS AS AMENDED

	Claims Remaining After Amendment	Highest Number Previously Paid		Number Extra Claims Present	Rate	
Total Claims	13	- 20	=	0	$ 100.00	$ 0.00
Independent Claims	2	- 3	=	0	$ 480.00	$ 0.00
Multiple Dependent Claims (check if applicable) ☐						
Other fee (please specify):						
TOTAL ADDITIONAL FEE FOR THIS AMENDMENT:						$ 0.00

☑ Large Entity ☐ Small Entity

☑ No additional fee is required for this amendment.

☐ Please charge Deposit Account No. _____ in the amount of $ _____ .

☐ A check in the amount of $ _____ to cover the filing fee is enclosed.

☐ Payment by credit card. Form PTO-2038 is attached.

☑ The Director is hereby authorized to charge and credit Deposit Account No. 60-1866 as described below. A duplicate copy of this sheet is enclosed.

☑ Credit any overpayment.

☑ Charge any additional filing or application processing fees required under 37 C.F.R. § 1.16 and 1.17.

/Richard J. Botos/ Dated: 8/17/2021

Richard J. Botos
Attorney/Agent Reg. No.: 32,016

BOTOS CHURCHILL IP LAW LLP
430 Mountain Avenue, Suite 401
New Providence, New Jersey 07974

I hereby certify that this paper (along with any paper referred to as being attached or enclosed) is being transmitted via the Office electronic filing system in accordance with 37 CFR § 1.6(a)(4).

Dated: 8/17/2021 Electronic Signature for Richard J. Botos /Richard J. Botos/

I hereby certify that this paper (along with any paper referred to as being attached or enclosed) is being transmitted via the Office electronic filing system in accordance with 37 CFR § 1.6(a)(4).

Dated: August 17, 2021
Electronic Signature for Richard J. Botos: /Richard J. Botos/

Docket No.: PICTIV 3.3F-001 CC [2]
(PATENT)

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Patent Application of:
Kastner-Jung et al.

Application No.: 16/790,198 | Confirmation No.: 1309

Filing Date: February 13, 2020 | Art Unit: 2844

For: ORGANIC LIGHT-EMITTING DIODE | Examiner: James Hyonchol Cho

---

Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

AMENDMENT

Dear Sir:

In response to the Office Action dated May 17, 2021, please amend the above-identified U.S. patent application as follows:

IN THE CLAIMS

1. (Currently Amended) A device comprising:

an organic light-emitting diode comprising an organic layer sequence, a radiation exit area and an encapsulation, wherein the organic layer sequence comprises at least one radiation-emitting region which generates electromagnetic radiation in ~~thea~~ spectral range from infrared radiation to UV radiation during operation, and wherein the encapsulation forms a seal of the organic layer sequence against environmental influences,

at least one touch-sensitive operating element, wherein the at least one touch-sensitive operating element comprises at least one touch sensor, wherein the device is flexible.

2. (Original) The device according to claim 1, wherein the device in bendable or can be rolled.

3. (Original) The device according to claim 2, wherein the device maintains its form after bending.

4. (Original) The device according to claim 1, wherein the organic light-emitting diode comprises a flexible carrier.

5. (Original) The device according to claim 4, wherein the flexible carrier comprises a film or a plastic film or a laminate.

6. (Original) The device according to claim 1, wherein the encapsulation is flexible.

7. (Original) The device according to claim 1, wherein the touch-sensitive operating element is arranged at a light exit area of the device.

8. (Original) The device according to claim 1, wherein the at least one touch sensor is integrated into the organic light-emitting diode.

SDC EX. 1027 - 344/489

9. (Original) The device according to claim 1, wherein the device is drivable by means of a gesture control.

10. (Currently Amended) A device comprising:

an organic light-emitting diode comprising an organic layer sequence, a radiation exit area and an encapsulation, wherein the organic layer sequence comprises at least one radiation-emitting region which generates electromagnetic radiation in ~~a~~the spectral range from infrared radiation to UV radiation during operation, and wherein the encapsulation forms a seal of the organic layer sequence against environmental influences,

at least one touch-sensitive operating element, wherein the at least one touch-sensitive operating element comprises at least one touch sensor, wherein

the device is bendable or can be rolled.

11. (Original) The device according to claim 10, wherein the touch-sensitive operating element is arranged at a light exit area of the device.

12. (Original) The device according to claim 10, wherein the at least one touch sensor is integrated into the organic light-emitting diode.

13. (Original) The device according to claim 10, wherein the device is drivable by means of a gesture control.

SDC EX. 1027 - 345/489

REMARKS

This communication is responsive to the Office Action dated May 17, 2021 (hereinafter the "Office Action"). In this communication, claims 1 and 10 are amended. No claims have been canceled or added. Thus, claims 1-13 are presented for consideration in view of the following remarks. Claims 1 and 10 are amended to correct a minor informality. Applicant respectfully submits that no new matter has been added by the foregoing amendments. The rejections will be addressed in view of the claims as presented herein.

Claim Rejections

Claim Rejections - 35 USC § 103

Claims 1 and 4-9 are rejected under pre-AIA 35 U.S.C. 103(a) as being unpatentable over US Patent Publication No. 2011/0187668 A1 to Hente ("*Hente*" hereinafter) in view of Patent Publication No. 2011/0096504 A1 to Hild ("*Hild*" hereinafter).

The Office Action alleges that *Hente* describes an organic light-emitting diode (102) comprising an organic layer sequence (106, 108, 110, 112), a radiation exit area (conductive elements transmitting light) wherein the organic layer sequence has a least on radiation-emitting region (conductive elements) which generates electromagnetic radiation in the spectral range from infrared radiation to UV radiation during operation (visible light which the operator can see in spectral range from infrared to UV as described in paragraph [0023] of *Hente*. The Office Action alleges that *Hente* also describes a touch-sensitive element (near-field imaging touch sensor described in paragraph [0001]), wherein the at least one touch-sensitive operating element comprises at least one touch sensor. The Office Action also alleges that the device described in *Hente* is flexible, citing paragraph [0020] and claim 8 of *Hente* in support.

The Office Action concedes that *Hente* does not describe encapsulation that seals the organic layer from the environment. The Office Action alleges that contemplates such encapsulation [0011]-[0012], [0048]-[0049], and [0063].

The Office Action regards independent claim 1 (and 4-9) as being obvious over *Hente* in view of *Hild* whereas claims 2-3 and 10-13 (claim 10 is independent) are alleged to be obvious from the combination of documents *Hente*, *Hild* and US Patent Publication No. 2003/0071259 A1 to Yoshida ("*Yoshida*" hereinafter).

According to the Office Action, *Hente* describes an OLED device 200 comprising an OLED means 102 and a near field imaging (NFI) touch sensor (paragraph [0001] and Figure 2).

SDC EX. 1027 - 346/489

The NFI touch sensor is integrated by a NFI touch sensor foil 104 comprising *a second substrate* (paragraph [0019]). The second substrate may be constructed from a flexible material (paragraph [0020]). The OLED means 102 comprises a cathode 106, an organic layer 108, an anode 110 and a substrate 112. Conductive elements 118, 120, 122, 124 may be adapted for transmitting light (paragraph [0023]).





FIG. 2

As noted by the Office Action, *Hente* lacks an OLED with an encapsulation seal. Although the Office Action alleges that *Hild* describes such a seal, applicant disagrees.

The Office Action alleges that *Hild* describes a component that is an OLED and an encapsulation and that can be a flexibly bendable layer system (*see* paragraph [0038] and Figure 2). According to the Office Action, a heat conducting foil 12 can be included in the flexibly bendable layer system which increases the barrier properties relative to water and oxygen.

SDC EX. 1027 - 347/489



The Office Action alleges that the *Hild* teaches a flexibly bendable top-emitting OLED, but this interpretation is contradicted by paragraph [0038] of *Hild* which states:

> [0038] In the case of the flexible component, i.e., bendable over the entire surface, shown in FIG. 2, **the encapsulation or the cover element 5 is replaced by a flexibly bendable layer system which has a heat-conducting foil 12**. As an alternative hereto or also cumulatively hereto, the substrate can however also have a corresponding heat-conducting foil. As shown here, the heat-conducting foil can be the component of a multilayer system but it can also be the single component of the substrate or of the encapsulation. Preferably, at least one layer of the heat-conducting foil 12 is hereby metallised, this can serve not only for heat conduction but also for increasing the barrier properties relative to water and oxygen. In the configuration of the foil substrate 1 and of the flexible cover element 5, it should be noted that at least one of these two surface sides of the organic electronic component is transparent.

Since *Hild* states that the cover-element 5 is replaced by the flexibly bendable layer with the heat conducting foil, applicant submits that claim 1 is not obvious from *Hente* in view of *Hild*. *Hild* describes the cover 5 as a seal, and does not describe the bendable heat-conducting foil 12 as a seal (but as a component that *increases* barrier properties; applicant submits that this is not the same thing a seal or barrier). Note that, in *Hild*, the OLED 3 is surrounded by the foil substrate 1, and the heat conducting material 12. In *Hente*, the OLED layer is not encapsulated. Therefore, applicant submits that *Hild* cannot be relied on to remedy the deficiencies of *Hente* with regard to flexibility and encapsulation when there is no guidance provided by *Hild* on how to modify *Hente* to accommodate those features.

SDC EX. 1027 - 348/489

Specifically, the Office Action fails to describe how the skilled person would integrate the touch sensor foil 104 in *Hente* with the flexible substrate in *Hild*. Including the encapsulation layer of *Hild* into the OLED device with Hente's NFI touch sensor would provide an OLED device without a functioning touch sensor. The skilled person would appreciate that the heat-conducting foil 12, which is used as an encapsulation for the OLED, comprises a metallized layer 12a and a second layer 12b made of, for example, PP, PE or PET (*see* [0036] of *Hild*). The skilled person is aware that a metallized layer exhibits one electric potential over its whole surface. Therefore, different capacitances cannot be set in the NFI touch sensor of *Hente* if the metallized layer of Hild is placed thereon for encapsulation because increased or decreased potentials in a specific location would be distributed over the whole metallized layer to and provide only a single electric potential over the whole surface. According to *Hente,* there is a different change in capacitance depending upon where the user touches the device.

> [0036] . . . .Visible in this figure is a finger 126. There is a capacitance between the operator's finger 126 and each of the conductive elements. The capacitance between the finger 126 and the first conductive element 118 is capacitance 130. The capacitance between the finger 126 and the second conductive element 120 is capacitance 132. The capacitance between the finger 126 and the third conductive element 122 is capacitance 134. The capacitance between the finger and the fourth conductive element 124 is capacitance 136. In this figure it is seen that the finger or the operator's hand 126 is located closer to some of the conductive elements than to other conductive elements. **The effect of this is that when the finger is in this position, the change in the capacitance of conductive elements 118, 120, 122, and 124 will be different. The comparison of these different changes in capacitance is how the sensor is able to detect a touch under varied conditions**. (emphasis added).

Accordingly, it would not be possible to use the *Hente* touch sensor in the designated way if the metallized encapsulation layer were added thereto as the location of the touch would not result in distributed capacitances. To avoid this problem, the metallized layer 12a would have to be omitted from the *Hild* encapsulation layer if it were to be incorporated onto the *Hente* device. However, this goes against what is expressly instructed by *Hild* which relies on including the encapsulation layer of Hild into the OLED device with an NFI touch sensor according to document *Hente* would lead to an OLED device without a functioning touch sensor. This can be explained as the heat-conducting foil 12 which is used as an encapsulation for the OLED comprises a metallized layer 12a and a second layer 12b made of, for example, PP, PE or PET (see [0036] of Hild). As known by a person skilled in the art, a metallized layer exhibits one electric potential

SDC EX. 1027 - 349/489

over its whole surface. Therefore, different capacitances cannot be set in the NFI touch sensor of *Hente* as increased or decreased potentials in a specific location are distributed over the whole metallized layer to gain one electric potential over the whole surface. Accordingly, it is not possible to use the touch sensor in the designated way as the location of a touch disturbing the capacitances cannot be determined. To evade this problem, the metallized layer 12a would have to be omitted. However, this leads to an OLED device with deteriorated properties as the metallized layer 12a is used for heat dissipation purposes. Omitting the metallized layer 12a could therefore lead to a device which overheats and thus loses efficiency because *Hild* uses the metallized layer 12a for heat dissipation purposes. Omitting the metallized layer 12a, which is contrary to what *Hild* expressly teaches, could therefore lead to a device which overheats and thus loses efficiency.

Hente describes a sensor with conductive elements 118, 120, 122, and 124 supported by substrate 112. Light travels through the substrate and the NFI sensor 104 is located on the side of the substrate opposite the OLED means 102. The Examiner has not explained how or where the skilled person would place the NFI sensor 104 described in *Hente* on a flexible substrate. The Examiner has not explained how the skilled person would adapt the conductive elements described in *Hente* to the flexible substrate environment of *Hild*. Also, note that, in *Hild*, the OLED emits in a direction opposite the encapsulation layer. Therefore, in one were to place the encapsulation of *Hild* onto the *Hente* device, that encapsulation layer would be placed over layer 106 which is opposite from substrate 112 in *Hente*, from which light emanates. *See* paragraph [0035] of *Hente*, "[l]ocated next to the anode is the organic layer 108 and on the organic layer 108 is mounted the cathode 106. When a sufficient voltage bias is applied to the anode 110 and cathode 106, light is generated in the organic layer 108. Light then travels through the anode 110 and the substrate 112."

MPEP 2144 states:

> When considering obviousness, **Office personnel are cautioned against treating any line of reasoning as a per se rule.** This section discusses supporting a rejection under 35 U.S.C. 103 by reliance on scientific theory and legal precedent. In keeping with the flexible approach to obviousness under KSR, as well as the requirement for explanation, Office personnel may invoke legal precedent as a source of supporting rationale when warranted and appropriately supported. See MPEP § 2144.04. So, for example, automating a manual activity, making portable, making separable, reversing or duplicating parts, or purifying an old product may form the basis of a rejection. However, such rationales should not be treated as per se rules, but rather must be explained and shown to apply to the facts at hand. A similar caveat applies to any obviousness analysis. **Simply stating the principle (e.g., "art recognized equivalent," "structural similarity") without providing an**

SDC EX. 1027 - 350/489

explanation of its applicability to the facts of the case at hand is generally not sufficient to establish a prima facie case of obviousness.

Applicant submits that the Examiner adopted an overly facile analysis in concluding that it would be obvious to combine, in one device:

i) a radiation exit area

ii) an encapsulation (forming a seal of the organic layer against environmental influences),

iii) wherein the organic layer sequence comprises at least one radiation-emitting region which generates electromagnetic radiation in the spectral range from infrared radiation to UV radiation during operation,

iv) at least one touch-sensitive operating element; and

v) wherein the device is flexible.

Regarding the touch-sensitive operating element for the claimed flexible substrate, applicant describes such an element in, for example, paragraphs [0506]-[0513] and FIGs. 31A and 31B. Again, the Office Action has not explained how *Hente's* near field sensor might be adapted to work with the metallized encapsulant and flexible substrate described in *Hild.*

Regarding the emission spectra of the claimed device, *Hente* says nothing more than the conductive elements are adapted to transmit light, otherwise the amount of visible light that the operator or user is able to see is reduced. *Hild* is silent on the wavelengths of emitted light.

With regard to claims 4-9, those claims depend from claim 1 and are not obvious from the combination of *Hente* and *Hild* for the same reason that claim 1 is not obvious from those references. The Examiner is respectfully requested to withdraw the rejection of claims 1 and 4-9 as obvious from *Hente* in view of *Hild.*

Claims 2-3 and 10-13 are rejected under pre-AIA 35 U.S.C. 103(a) as being unpatentable over *Hente* in view of *Hild* and further in view of US Publication No. 2003/0071259 to Yoshida ("*Yoshida*").

The Office Action alleges that *Yoshida* describes an organic electroluminescent display, especially a so-called "electronic paper" that has shape changeability by bending using an electrically conductive organic compound (citing paragraphs [0003] and [0005] of *Yoshida*). The Office Action alleges that it would be obvious to use the materials described in Yoshida in the OLED device of *Hente* and *Hild.* Applicant disagrees.

SDC EX. 1027 - 351/489

Specifically, as explained above, including the encapsulation layer of *Hild* into the OLED device with an NFI touch sensor according to document *Hente* would lead to an OLED device without a functioning touch sensor. As noted above, the heat-conducting foil 12 which is used as an encapsulation for the OLED has a metallized layer 12a and a second layer 12b made of, for example, PP, PE or PET (*see* [0036] of *Hild*). The skilled person knows that a metallized layer exhibits one electric potential over its whole surface. Therefore, different capacitances cannot be set in the NFI touch sensor of *Hente* as increased or decreased potentials in a specific location are distributed over the entire metallized layer, resulting in one electric potential over the whole surface. Accordingly, it is not possible to use the *Hente* touch sensor in the designated way as the location of a touch disturbing the capacitances could not be ascertained. To avoid this problem, the metallized layer 12a would have to be omitted, which is contrary to what *Hild* expressly teaches. Specifically, elimination of the metallized layer, accord to *Hild*, would lead to an OLED device with reduced performance do to a reduced capability for heat dissipation. Omitting the metallized layer 12a that *Hild* requires could therefore result in a device which overheats and thus loses efficiency. Hence, a person skilled in the art has no incentive to omit the *Hild* metallized layer 12a and no incentive to add that metallized layer to the *Hente* device.

Also, as noted above, neither *Hente*, nor *Hild* nor *Yoshida* expressly state that the spectral range of the emission from the devices they describe is in the claimed range (i.e., from infrared radiation to UV radiation.) *Hente* merely describes that conductive elements are advantageously adapted for transmitting light as otherwise the amount of visible light which is observable is reduced. *Hild* and *Yoshida* are silent in this regard.

For the foregoing reasons, claim 10 is not obvious from *Hente* in view of *Hild* and further in view of *Yoshida*. Claims 2 and 3, which depend from claim 1 and require a bendable or rollable substrate, are not obvious from *Hente* in view of *Hild* and further in view of *Yoshida* for the same reasons that claim 10 is not obvious from those references. Claims 11-13 depend from claim 10 and are not obvious from *Hente* in view of *Hild* and further in view of *Yoshida* for the same reasons that claim 10 is not obvious from these references.

SDC EX. 1027 - 352/489

CONCLUSION

In view of the above, each of the presently pending claims in this application is believed to be in immediate condition for allowance. Accordingly, the Examiner is respectfully requested to withdraw the outstanding rejection of the claims and to pass this application to issue. If, however, for any reason the Examiner does not believe that such action can be taken at this time, it is respectfully requested that the Examiner telephone Applicant's attorney at (908) 738-1770 in order to overcome any additional objections which the Examiner might have. All required fees are being paid via credit card through EFS-Web. However, please charge any additional fees not already paid via credit card, and credit any overpayments to our Deposit Account No. 601866.

Dated: August 17, 2021

Respectfully submitted,

Electronic Signature: /Richard J. Botos/
Richard J. Botos
Registration No. 32,016
Botos Churchill IP Law LLP
430 Mountain Ave., Suite 401
New Providence, NJ 07974
(908) 738-1770
Attorney for Applicant

4822-2435-0966, v. 1

SDC EX. 1027 - 353/489

PTO/SB/06 (09-11)
Approved for use through 1/31/2014. OMB 0651-0032
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

PATENT APPLICATION FEE DETERMINATION RECORD Substitute for Form PTO-875	Application or Docket Number 16/790,198	Filing Date 02/13/2020	☐ To be Mailed

ENTITY: ☑ LARGE ☐ SMALL ☐ MICRO

APPLICATION AS FILED - PART I

FOR	(Column 1) NUMBER FILED	(Column 2) NUMBER EXTRA		RATE ($)	FEE ($)
☐ BASIC FEE (37 CFR 1.16(a), (b), or (c))	N/A	N/A		N/A	
☐ SEARCH FEE (37 CFR 1.16(k), (i), or (m))	N/A	N/A		N/A	
☐ EXAMINATION FEE (37 CFR 1.16(o), (p), or (q))	N/A	N/A		N/A	
TOTAL CLAIMS (37 CFR 1.16(i))	minus 20 =	*		x $100 =	
INDEPENDENT CLAIMS (37 CFR 1.16(h))	minus 3 =	*		x $460 =	
☐ APPLICATION SIZE FEE (37 CFR 1.16(s))	If the specification and drawings exceed 100 sheets of paper, the application size fee due is $310 ($155 for small entity) for each additional 50 sheets or fraction thereof. See 35 U.S.C. 41(a)(1)(G) and 37 CFR 1.16(s).				
☐ MULTIPLE DEPENDENT CLAIM PRESENT (37 CFR 1.16(j))					
* If the difference in column 1 is less than zero, enter "0" in column 2.				TOTAL	

APPLICATION AS AMENDED - PART II

		(Column 1)		(Column 2)	(Column 3)			
AMENDMENT	08/17/2021	CLAIMS REMAINING AFTER AMENDMENT		HIGHEST NUMBER PREVIOUSLY PAID FOR	PRESENT EXTRA		RATE ($)	ADDITIONAL FEE ($)
	Total (37 CFR 1.16(i))	* 13	Minus	** 20	= 0		x $100 =	0
	Independent (37 CFR 1.16(h))	* 2	Minus	*** 3	= 0		x $480 =	0
	☐ Application Size Fee (37 CFR 1.16(s))							
	☐ FIRST PRESENTATION OF MULTIPLE DEPENDENT CLAIM (37 CFR 1.16(j))							
							TOTAL ADD'L FEE	0

		(Column 1)		(Column 2)	(Column 3)			
AMENDMENT		CLAIMS REMAINING AFTER AMENDMENT		HIGHEST NUMBER PREVIOUSLY PAID FOR	PRESENT EXTRA		RATE ($)	ADDITIONAL FEE ($)
	Total (37 CFR 1.16(i))	*	Minus	**	=		x $0 =	
	Independent (37 CFR 1.16(h))	*	Minus	***	=		x $0 =	
	☐ Application Size Fee (37 CFR 1.16(s))							
	☐ FIRST PRESENTATION OF MULTIPLE DEPENDENT CLAIM (37 CFR 1.16(j))							
							TOTAL ADD'L FEE	

* If the entry in column 1 is less than the entry in column 2, write "0" in column 3.	LIE
** If the "Highest Number Previously Paid For" IN THIS SPACE is less than 20, enter "20".	/TINA M. BELL/
*** If the "Highest Number Previously Paid For" IN THIS SPACE is less than 3, enter "3".	
The "Highest Number Previously Paid For" (Total or Independent) is the highest number found in the appropriate box in column 1.	

This collection of information is required by 37 CFR 1.16. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 12 minutes to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.**

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
16/790,198	02/13/2020	Ulrich KASTNER-JUNG	PICTIV 3.3F-001 CC [2]	1309

175540 7590 10/29/2021

Botos Churchill IP Law LLP
430 Mountain Avenue
Suite 401
New Providence, NJ 07974

EXAMINER	
CHO, JAMES HYONCHOL	

ART UNIT	PAPER NUMBER
2844	

NOTIFICATION DATE	DELIVERY MODE
10/29/2021	ELECTRONIC

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Notice of the Office communication was sent electronically on above-indicated "Notification Date" to the following e-mail address(es):

lgagliano@bciplaw.com
pto@bciplaw.com
rbotos@bciplaw.com

Office Action Summary	Application No. 16/790,198	Applicant(s) KASTNER-JUNG et al.	
	Examiner James H Cho	Art Unit 2844	AIA (FITF) Status No

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTHS FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

1)☑ Responsive to communication(s) filed on 8/17/2021.

☐ A declaration(s)/affidavit(s) under **37 CFR 1.130(b)** was/were filed on _____.

2a)☑ This action is **FINAL.** 2b) ☐ This action is non-final.

3)☐ An election was made by the applicant in response to a restriction requirement set forth during the interview on _____; the restriction requirement and election have been incorporated into this action.

4)☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims*

5) ☑ Claim(s) 1-13 is/are pending in the application.

5a) Of the above claim(s) _____ is/are withdrawn from consideration.

6) ☐ Claim(s) _____ is/are allowed.

7) ☑ Claim(s) 1-13 is/are rejected.

8) ☐ Claim(s) _____ is/are objected to.

9) ☐ Claim(s) _____ are subject to restriction and/or election requirement

* If any claims have been determined allowable, you may be eligible to benefit from the **Patent Prosecution Highway** program at a participating intellectual property office for the corresponding application. For more information, please see http://www.uspto.gov/patents/init_events/pph/index.jsp or send an inquiry to **PPHfeedback@uspto.gov.**

Application Papers

10)☐ The specification is objected to by the Examiner.

11)☑ The drawing(s) filed on 2/13/2020 is/are: a)☑ accepted or b)☐ objected to by the Examiner.

Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).

Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).

Priority under 35 U.S.C. § 119

12)☑ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).

Certified copies:

a)☑ All b)☐ Some** c)☐ None of the:

1.☐ Certified copies of the priority documents have been received.

2.☑ Certified copies of the priority documents have been received in Application No. 13/139514.

3.☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

** See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

1) ☐ Notice of References Cited (PTO-892)

2) ☑ Information Disclosure Statement(s) (PTO/SB/08a and/or PTO/SB/08b) Paper No(s)/Mail Date _____.

3) ☐ Interview Summary (PTO-413) Paper No(s)/Mail Date _____.

4) ☐ Other: _____.

DETAILED ACTION

Notice of Pre-AIA or AIA Status

The present application is being examined under the pre-AIA first to invent provisions.

Receipt is acknowledged of the Amendment filed 8/17/2021.

Claim Rejections - 35 USC § 103

The text of those sections of Title 35, U.S. Code not included in this action can be found in a prior Office action.

Claims 1 and 4-9 are rejected under pre-AIA 35 U.S.C. 103(a) as being unpatentable over Hente (US 2011/0187668 A1) in view of Hild (US 2011/0096504 A1)

Regarding claim 1, Hente teaches a device (see Fig. 2) comprising an organic light-emitting diode (102, see para [0017]) comprising an organic layer sequence (106, 108, 110, 112), a radiation exit area (conductive elements transmitting light, see para [0023]), wherein the organic layer sequence comprises at least one radiation-emitting region (conductive elements) on which generates electromagnetic radiation in the spectral range from infrared radiation to UV radiation during operation (visible light which an operator can see in the spectral range from IR radiation and UV radiation, see para [0023]),

at least one touch-sensitive operating element (near filed imaging touch sensors, see para [0001]), wherein the at least one touch-sensitive operating element comprises at least one touch sensor, wherein the device is flexible (touch sensor with substrate made with a flexible material where OLDE is mounted, see para [0020] and claim 8),

but does not teach that the OLED comprising an encapsulation forming a seal of the organic layer sequence against environment influences.

However, Hild teach a flexibly bendable top-emitting OLED (see Fig. 2 and para [0038]) emitting visible light only within a narrow wavelength range comprising of encapsulation forming a seal of the organic layer sequence against water and air as well as for a better heat dissipation (see paras [0011]-[0012], [0048]-[0049], [0056]).

Therefore, it would have been obvious at the time of invention to utilize the OLED of Hild with encapsulation in place of the OLED of Hente since it would provide an additional protection from overheating of the OLED as well as from moisture and air influences.

Regarding claim 4, Hente in view of Hild teaches the device according to claim 1, wherein the organic light-emitting diode comprises a flexible carrier (carrier foil 12 being flexible, see Fig. 2, para [0034]-[0036] of Hild).

Regarding claim 5, Hente in view of Hild teaches the device according to claim 4, wherein the flexible carrier comprises a film or a plastic film (the layer 12b being polycarbonate where a polycarbonate is a type of plastic, see para [0036] of Hild) or a laminate (12 comprises plurality of layers).

Regarding claim 6, Hente in view of Hild teaches the device according to claim 1, wherein the encapsulation is flexible (encapsulation being flexibly bendable layer, see para [0038] of Hild).

Regarding claim 7, Hente in view of Hild teaches the device according to claim 1, wherein the touch-sensitive operating element is arranged at a light exit area of the device (Fig. 3 of Hente where the diode transmitting light).

Regarding claim 8, Hente in view of Hild teaches the device according to claim 1, wherein the at least one touch sensor is integrated into the organic light-emitting diode (touch sensor being integrated in the OLED, see para [0017]-[0018] of Hente).

Regarding claim 9, Hente in view of Hild teaches the device according to claim 1, wherein the device is drivable by means of a gesture control (OLED apparatus generating light by user sliding his or her finger along the surface of the OLED device where sliding finger by a user is considered as being a gesture control, see para [0024] of Hente).

Claims 2-3 and 10-13 are rejected under pre-AIA 35 U.S.C. 103(a) as being unpatentable over Hente (US 2011/0187668 A1) in view of Hild (US 2011/0096504 A1) and Yoshida (US 2003/0071259 A1).

Regarding claims 2-3, the combination of prior arts, Hente and Hild teaches the device according claim 1,

but do not teach the specific of the device being bendable or capable of being rolled and the device maintaining its form after bending.

However, Yoshida teaches an organic EL display having shape changeability by bending by utilizing electrically conductive organic compound (see para [0003], [0005]) with at a low cost enabling forms being maintained after bending (sheet-like display is an electronic paper with various forms, see para [0016], see Fig. 6 which displays flipped bended-page on the left and returned to the original page on the right).

Therefore, it would have been obvious at the time of invention to utilize the materials of Yoshida for the OLED device of Hente and Hild since it would provide enhanced portability like a bendable sheet-like displace device with a cost reduction.

Regarding claim 10, Hente teaches a device (see Fig. 2) comprising an organic light-emitting diode (102, see para [0017]) comprising an organic layer sequence (106, 108, 110, 112), a radiation exit area (conductive elements transmitting light, see para [0023]), wherein the organic layer sequence comprises at least one radiation-emitting region (conductive elements) on which generates electromagnetic radiation in the spectral range from infrared radiation to UV radiation during operation (visible light which an operator can see in the spectral range from IR radiation and UV radiation, see para [0023]),

at least one touch-sensitive operating element (near filed imaging touch sensors, see para [0001]), wherein the at least one touch-sensitive operating element comprises at least one touch sensor, wherein the device is flexible (touch sensor constructed out of a flexible material where OLDE is mounted, see para [0020] and claim 8),

but does not teach that the OLED comprising an encapsulation forming a seal of the organic layer sequence against environment influences.

However, Hild teach a flexibly bendable top-emitting OLED (see Fig. 2 and para [0038]) emitting visible light only within a narrow wavelength range comprising of encapsulation forming a seal of the organic layer sequence against water and air as well as for a better heat dissipation (see paras [0011]-[0012], [0048]-[0049], [0056]).

Therefore, it would have been obvious at the time of invention to utilize the OLED of Hild with encapsulation in place of the OLED of Hente since it would provide an additional protection from overheating of the OLED as well as from moisture and air influences.

Regarding the limitation of the device, the combination of prior arts, Hente and Hild do not teach the specific of the device being bendable or capable of being rolled.

However, Yoshida teaches an organic EL display having shape changeability by bending by utilizing electrically conductive organic compound (see para [0003], [0005]) with at a low cost.

Therefore, it would have been obvious at the time of invention to utilize the materials of Yoshida for the OLED device of Hente and Hild since it would provide enhanced portability like a bendable sheet-like displace device with a cost reduction.

Regarding claim 11, Hente in view of Hild and Yoshida teaches the device according to claim 10, wherein the touch-sensitive operating element is arranged at a light exit area of the device (touch sensor being integrated in the OLED, see para [0017]-[0018] of Hente).

Regarding claim 12, Hente in view of Hild and Yoshida teaches the device according to claim 10, wherein the at least one touch sensor is integrated into the organic light-emitting diode (touch sensor being integrated in the OLED, see para [0017]-[0018] of Hente).

Regarding claim 13, Hente in view of Hild and Yoshida teaches the device according to claim 10, wherein the device is drivable by means of a gesture control (OLED apparatus generating light by user sliding his or her finger along the surface of the OLED device where sliding finger by a user is considered as being a gesture control, see para [0024] of Hente).

Response to Arguments

Applicant's arguments filed 8/17/2021 have been fully considered but they are not persuasive.

The applicant first argues that Hild fails to teach the deficiencies of Hente regarding flexibility and encapsulation because "Hild does not describe the bendable heat-conducting foil 12 as a seal".

Regarding the device being flexible, Hente clearly teaches that "the second substrate is constructed from a flexible material" as well as "a touch sensor constructed out of a flexible material" in paragraph [0020] as discussed in the Office action mailed, and it is further noted that Hild reference teaches "a three-layer flexible foil substrate" where "the OLED stack being constructed from flexibly bendable or ductile materials" in paragraph [0035] and the layer of this heat-conducting foil 12 being "constructed hereby as a metallised layer 12a comprising **ductile** Cu or Al" in paragraph [0036].

Regarding the encapsulation forming a seal of the organic layer sequence, applicant argues that Hild fails to describe "the bendable heat-conducting foil 12 as a seal" and "a component that increases barrier properties" is "not the same thing as a seal or barrier".

The examiner notes that claim 1 recites the encapsulation in terms of forming "a seal of the organic layer sequence against environmental influences", which is layers comprising of 12a and 12b in Fig. 2 of Hild provides an increased protection from water and oxygen as being a barrier as described in paragraph [0038] of Hild where sealing is interpreted as protecting anything from passing through.

Applicant further argues that the touch sensor foil 104 in Hente cannot be integrated with the flexible substrate in Hild since the metallised layer 12a and 12b of Hild would introduce a single electric potential over the whole surface and make it impossible to differentiate different location of touch.

The examiner notes that Hinte describes the sensor being able to detecting a touch under different conditions in paragraph [0036], such that selecting a metallised foil that minimize the effect by a potential introduced by the metallised layers without removing the metallised layer of 12a and 12b is capable and obvious to a person ordinary skill in the art.

Applicant also argues about light traveling through the anode 110 and the substrate 112 of Hinte where the examiner fails to explain the NFI sensor 104 of Hente being on a flexible substrate.

The examiner notes that claims merely recites “the device is flexible” in claim 1, “the device in bendable or can be rolled” in claims 2 and 10, “the organic light-emitting diode comprises a flexible carrier” in claim 4, “the encapsulation is flexible” in claim 6, and there is no claim recitation that “the NFI sensor 104 being on “a flexible substrate”. The examiner notes that Hinte teaches that “the second substrate is constructed from a flexible material. A touch sensor constructed out of a flexible material” in paragraph [0020].

Applicant further argues about the rejection mailed 5/17/2021 is based on “an overly facile analysis” especially regarding the touch sensitive operating element on the flexible substrate, and regarding the conductive elements to transmit the light and the wavelengths of emitted light.

In response to Applicant's argument that there is no suggestion to combine the references based on “an overly facile analysis”, the Examiner recognizes that references cannot be arbitrarily combined and that there must be some reason why one skilled in the art would be motivated to make the proposed combination of primary and secondary references. The test for combining references is what the combination of disclosures taken as a whole would suggest to one of ordinary skill in the art.

The examiner also notes that Hente clearly teaches the device being flexible as discussed above (see para [0020]) where claim has no specific limitation that requires the touch sensor being on a flexible substrate, and the light traveling in Hente is a visible light where a visible light having a wavelength between IR radiation and UV radiation is well known in the art as properly recited the Office action.

Applicant argues about the rejection based on the combination of Hente in view of Hild, and further in view of Yoshida where applicant repeats the similar argument made regarding the heat-conducting foil 12 caused one electrical potential over the whole surface which would limit setting the different capacitances, reduced heat dissipation, and the wavelength of a visible light, which were discussed in the above by the examiner.

Therefore, claims 1 and 4-9 remains rejected under 35 USC 103(a) over Hente in view of Hild, and claims 2-3 and 10-13 remains rejected under 35 USC 103(a) over Hente in view of Hild and Yoshida.

Conclusion

THIS ACTION IS MADE FINAL. Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire THREE MONTHS from the mailing date of this action. In the event a first reply is filed within TWO MONTHS of the mailing date of this final action and the advisory action is not mailed until after the end of the THREE-MONTH shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event, however, will the statutory period for reply expire later than SIX MONTHS from the mailing date of this final action.

Any inquiry concerning this communication or earlier communications from the examiner should be directed to James H Cho whose telephone number is (571)272-1802. The examiner can normally be reached M-F 7 AM - 4 PM.

Examiner interviews are available via telephone, in-person, and video conferencing using a USPTO supplied web-based collaboration tool. To schedule an interview, applicant is encouraged to use the USPTO Automated Interview Request (AIR) at http://www.uspto.gov/interviewpractice.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Amy C Johnson can be reached on 571-272-2238. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of published or unpublished applications may be obtained from Patent Center. Unpublished application information in Patent Center is available to registered users. To file and manage patent submissions in Patent Center, visit: https://patentcenter.uspto.gov. Visit https://www.uspto.gov/patents/apply/patent-center for more information about Patent Center and https://www.uspto.gov/patents/docx for information about filing in DOCX format. For additional questions, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

JAMES H. CHO
Examiner
Art Unit 2844

/AMY COHEN JOHNSON/
Supervisory Patent Examiner, Art Unit 2844

Search Notes	Application/Control No.	Applicant(s)/Patent Under Reexamination
	16/790,198	KASTNER-JUNG et al.
	Examiner	Art Unit
	James H Cho	2844

CPC - Searched*		
Symbol	Date	Examiner
H05B47/125 H05B47/165 H01L51/506 F21S10/02 H05B47/105 H05B45/60 H05B47/16 F24D19/06 B60Q3/745 B60Q3/30 B60Q1/268 B60Q7/00 (text search, see the search history printout)	04/27/2021	JC
B05B1/18 F21V23/0442 F21V33/0016 F21V33/004 F21V33/0052 F21V33/006 G04C19/02 G04G11/00 G04G13/023 H05B33/22(text search, see the search history printout)	04/27/2021	JC

CPC Combination Sets - Searched*		
Symbol	Date	Examiner

US Classification - Searched*			
Class	Subclass	Date	Examiner

* See search history printout included with this form or the SEARCH NOTES box below to determine the scope of the search.

Search Notes		
Search Notes	Date	Examiner
BRS text search, see the search history printout	04/27/2021	JC
updated search	10/23/2021	JC

Interference Search			
US Class/CPC Symbol	US Subclass/CPC Group	Date	Examiner

Index of Claims	Application/Control No.	Applicant(s)/Patent Under Reexamination
	16/790,198	KASTNER-JUNG et al.
	Examiner	Art Unit
	James H Cho	2844

✓	Rejected	-	Cancelled	N	Non-Elected	A	Appeal
=	Allowed	÷	Restricted	I	Interference	O	Objected

CLAIMS

☐ Claims renumbered in the same order as presented by applicant ☐ CPA ☐ T.D. ☐ R.1.47

CLAIM		DATE								
Final	Original	05/05/2021	10/23/2021							
	1	✓	✓							
	2	✓	✓							
	3	✓	✓							
	4	✓	✓							
	5	✓	✓							
	6	✓	✓							
	7	✓	✓							
	8	✓	✓							
	9	✓	✓							
	10	✓	✓							
	11	✓	✓							
	12	✓	✓							
	13	✓	✓							

EAST Search History

EAST Search History (Prior Art)

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
S329	43	(US-20160238234-$ or US-20100076527-$ or US-20080138624-$ or US-20020003403-$ or US-20110133628-$ or US-20090173957-$ or US-20090091258-$ or US-20080188156-$ or US-20080138539-$ or US-20070114520-$ or US-20060128042-$ or US-20090039272-$ or US-20010043046-$ or US-20050156520-$ or US-20050242709-$ or US-20040080938-$ or US-20090167981-$ or US-20070230211-$ or US-20070176195-$ or US-20070153543-$ or US-20090072711-$ or US-20120256534-$ or US-20100044730-$ or US-20040022058-$ or US-20100295812-$ or US-20100096993-$).did. or (US-20070273290-$).did. or (US-6926572-$ or US-6884465-$ or US-7922358-$ or US-7733008-$ or US-6331063-$ or US-6575584-$ or US-8987711-$ or US-7560727-$ or US-7358663-$ or US-7205714-$ or US-8123391-$ or US-9797567-$ or US-7733011-$ or US-6703780-$ or US-8731618-$ or US-6525997-$).did.	US-PGPUB; USPAT	OR	ON	2021/10/23 21:03
L1	1	("7205714").PN.	US-PGPUB; USPAT; USOCR	OR	OFF	2021/10/23 21:10

10/23/2021 9:11:27 PM
C:\Users\jcho\Documents\EAST\Workspaces\16790198.wsp

Doc code: IDS
Doc description: Information Disclosure Statement (IDS) Filed

PTO/SB/08a (03-15)
Approved for use through 07/31/2016. OMB 0651-0031
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

INFORMATION DISCLOSURE STATEMENT BY APPLICANT

(Not for submission under 37 CFR 1.99)

Application Number	16790198
Filing Date	2020-02-13
First Named Inventor	Ulrich Kastner-Jung
Art Unit	2844
Examiner Name	James Hyonchol Cho
Attorney Docket Number	PICTIV 3.3F-001 CC [2]

U.S.PATENTS Remove

Examiner Initial*	Cite No	Patent Number	Kind Code[1]	Issue Date	Name of Patentee or Applicant of cited Document	Pages,Columns,Lines where Relevant Passages or Relevant Figures Appear
	1	7205714	B2	2007-04-17	CHEN	

If you wish to add additional U.S. Patent citation information please click the Add button. Add

U.S.PATENT APPLICATION PUBLICATIONS Remove

Examiner Initial*	Cite No	Publication Number	Kind Code[1]	Publication Date	Name of Patentee or Applicant of cited Document	Pages,Columns,Lines where Relevant Passages or Relevant Figures Appear
	1					

If you wish to add additional U.S. Published Application citation information please click the Add button. Add

FOREIGN PATENT DOCUMENTS Remove

Examiner Initial*	Cite No	Foreign Document Number[3]	Country Code[2] i	Kind Code[4]	Publication Date	Name of Patentee or Applicant of cited Document	Pages,Columns,Lines where Relevant Passages or Relevant Figures Appear	T[5]
	1							

If you wish to add additional Foreign Patent Document citation information please click the Add button Add

NON-PATENT LITERATURE DOCUMENTS Remove

Examiner Initials*	Cite No	Include name of the author (in CAPITAL LETTERS), title of the article (when appropriate), title of the item (book, magazine, journal, serial, symposium, catalog, etc), date, pages(s), volume-issue number(s), publisher, city and/or country where published.	T[5]

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /JC/

INFORMATION DISCLOSURE STATEMENT BY APPLICANT

(Not for submission under 37 CFR 1.99)

Application Number	16790198
Filing Date	2020-02-13
First Named Inventor	Ulrich Kastner-Jung
Art Unit	2844
Examiner Name	James Hyonchol Cho
Attorney Docket Number	PICTIV 3.3F-001 CC [2]

	1	

If you wish to add additional non-patent literature document citation information please click the Add button Add

EXAMINER SIGNATURE

Examiner Signature	/JAMES H CHO/	Date Considered	10/22/2021

*EXAMINER: Initial if reference considered, whether or not citation is in conformance with MPEP 609. Draw line through a citation if not in conformance and not considered. Include copy of this form with next communication to applicant.

[1] See Kind Codes of USPTO Patent Documents at www.USPTO.GOV or MPEP 901.04. [2] Enter office that issued the document, by the two-letter code (WIPO Standard ST.3). [3] For Japanese patent documents, the indication of the year of the reign of the Emperor must precede the serial number of the patent document. [4] Kind of document by the appropriate symbols as indicated on the document under WIPO Standard ST.16 if possible. [5] Applicant is to place a check mark here if English language translation is attached.

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /JC/

INFORMATION DISCLOSURE STATEMENT BY APPLICANT

(Not for submission under 37 CFR 1.99)

Application Number	16790198
Filing Date	2020-02-13
First Named Inventor	Ulrich Kastner-Jung
Art Unit	2844
Examiner Name	James Hyonchol Cho
Attorney Docket Number	PICTIV 3.3F-001 CC [2]

CERTIFICATION STATEMENT

Please see 37 CFR 1.97 and 1.98 to make the appropriate selection(s):

That each item of information contained in the information disclosure statement was first cited in any communication from a foreign patent office in a counterpart foreign application not more than three months prior to the filing of the information disclosure statement. See 37 CFR 1.97(e)(1).

OR

☐ That no item of information contained in the information disclosure statement was cited in a communication from a foreign patent office in a counterpart foreign application, and, to the knowledge of the person signing the certification after making reasonable inquiry, no item of information contained in the information disclosure statement was known to any individual designated in 37 CFR 1.56(c) more than three months prior to the filing of the information disclosure statement. See 37 CFR 1.97(e)(2).

See attached certification statement.

✓ The fee set forth in 37 CFR 1.17 (p) has been submitted herewith.

✓ A certification statement is not submitted herewith.

SIGNATURE

A signature of the applicant or representative is required in accordance with CFR 1.33, 10.18. Please see CFR 1.4(d) for the form of the signature.

Signature	/Richard J. Botos/	Date (YYYY-MM-DD)	2021-07-07
Name/Print	Richard J. Botos	Registration Number	32016

This collection of information is required by 37 CFR 1.97 and 1.98. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 1 hour to complete, including gathering, preparing and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.**

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /JC/

Privacy Act Statement

The Privacy Act of 1974 (P.L. 93-579) requires that you be given certain information in connection with your submission of the attached form related to a patent application or patent. Accordingly, pursuant to the requirements of the Act, please be advised that: (1) the general authority for the collection of this information is 35 U.S.C. 2(b)(2); (2) furnishing of the information solicited is voluntary; and (3) the principal purpose for which the information is used by the U.S. Patent and Trademark Office is to process and/or examine your submission related to a patent application or patent. If you do not furnish the requested information, the U.S. Patent and Trademark Office may not be able to process and/or examine your submission, which may result in termination of proceedings or abandonment of the application or expiration of the patent.

The information provided by you in this form will be subject to the following routine uses:

1. The information on this form will be treated confidentially to the extent allowed under the Freedom of Information Act (5 U.S.C. 552) and the Privacy Act (5 U.S.C. 552a). Records from this system of records may be disclosed to the Department of Justice to determine whether the Freedom of Information Act requires disclosure of these record s.

2. A record from this system of records may be disclosed, as a routine use, in the course of presenting evidence to a court, magistrate, or administrative tribunal, including disclosures to opposing counsel in the course of settlement negotiations.

3. A record in this system of records may be disclosed, as a routine use, to a Member of Congress submitting a request involving an individual, to whom the record pertains, when the individual has requested assistance from the Member with respect to the subject matter of the record.

4. A record in this system of records may be disclosed, as a routine use, to a contractor of the Agency having need for the information in order to perform a contract. Recipients of information shall be required to comply with the requirements of the Privacy Act of 1974, as amended, pursuant to 5 U.S.C. 552a(m).

5. A record related to an International Application filed under the Patent Cooperation Treaty in this system of records may be disclosed, as a routine use, to the International Bureau of the World Intellectual Property Organization, pursuant to the Patent Cooperation Treaty.

6. A record in this system of records may be disclosed, as a routine use, to another federal agency for purposes of National Security review (35 U.S.C. 181) and for review pursuant to the Atomic Energy Act (42 U.S.C. 218(c)).

7. A record from this system of records may be disclosed, as a routine use, to the Administrator, General Services, or his/her designee, during an inspection of records conducted by GSA as part of that agency's responsibility to recommend improvements in records management practices and programs, under authority of 44 U.S.C. 2904 and 2906. Such disclosure shall be made in accordance with the GSA regulations governing inspection of records for this purpose, and any other relevant (i.e., GSA or Commerce) directive. Such disclosure shall not be used to make determinations about individuals.

8. A record from this system of records may be disclosed, as a routine use, to the public after either publication of the application pursuant to 35 U.S.C. 122(b) or issuance of a patent pursuant to 35 U.S.C. 151. Further, a record may be disclosed, subject to the limitations of 37 CFR 1.14, as a routine use, to the public if the record was filed in an application which became abandoned or in which the proceedings were terminated and which application is referenced by either a published application, an application open to public inspections or an issued patent.

9. A record from this system of records may be disclosed, as a routine use, to a Federal, State, or local law enforcement agency, if the USPTO becomes aware of a violation or potential violation of law or regulation.

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /SC/

Doc Code: A.NE.AFCP
Document Description: After Final Consideration Pilot Program Request

PTO/SB/434 (12-20)

CERTIFICATION AND REQUEST FOR CONSIDERATION UNDER THE AFTER FINAL CONSIDERATION PILOT PROGRAM 2.0

Practitioner Docket No.:	Application No.:	Filing Date:
PICTIV 3.3F-001 CON CON [PICTIV.2]	16/790,198	February 13, 2020
First Named Inventor:	**Title:**	
Kastner-Jung et al.	ORGANIC-LIGHT EMITTING DIODE	

APPLICANT HEREBY CERTIFIES THE FOLLOWING AND REQUESTS CONSIDERATION UNDER THE AFTER FINAL CONSIDERATION PILOT PROGRAM 2.0 (AFCP 2.0) OF THE ACCOMPANYING RESPONSE UNDER 37 CFR 1.116.

1. The above-identified application is (i) an original utility, plant, or design nonprovisional application filed under 35 U.S.C. 111(a) [a continuing application (*e.g.*, a continuation or divisional application) is filed under 35 U.S.C. 111(a) and is eligible under (i)], or (ii) an international application that has entered the national stage in compliance with 35 U.S.C. 371(c).
2. The above-identified application contains an outstanding final rejection.
3. Submitted herewith is a response under 37 CFR 1.116 to the outstanding final rejection. The response includes an amendment to at least one independent claim, and the amendment does not broaden the scope of the independent claim in any aspect.
4. This certification and request for consideration under AFCP 2.0 is the only AFCP 2.0 certification and request filed in response to the outstanding final rejection.
5. Applicant is willing and available to participate in any interview requested by the examiner concerning the present response.
6. This certification and request is being filed electronically using the Office's electronic filing system (EFS-Web).
7. Any fees that would be necessary consistent with current practice concerning responses after final rejection under 37 CFR 1.116, *e.g.*, extension of time fees, are being concurrently filed herewith. [There is no additional fee required to request consideration under AFCP 2.0.]
8. By filing this certification and request, applicant acknowledges the following:
    - Reissue applications and reexamination proceedings are not eligible to participate in AFCP 2.0.
    - The examiner will verify that the AFCP 2.0 submission is compliant, *i.e.*, that the requirements of the program have been met (see items 1 to 7 above). For compliant submissions:
        - The examiner will review the response under 37 CFR 1.116 to determine if additional search and/or consideration (i) is necessitated by the amendment and (ii) could be completed within the time allotted under AFCP 2.0. If additional search and/or consideration is required but cannot be completed within the allotted time, the examiner will process the submission consistent with current practice concerning responses after final rejection under 37 CFR 1.116, *e.g.*, by mailing an advisory action.
        - If the examiner determines that the amendment does not necessitate additional search and/or consideration, or if the examiner determines that additional search and/or consideration is required and could be completed within the allotted time, then the examiner will consider whether the amendment places the application in condition for allowance (after completing the additional search and/or consideration, if required). If the examiner determines that the amendment does not place the application in condition for allowance, then the examiner will contact the applicant and request an interview.
            - The interview will be conducted by the examiner, and if the examiner does not have negotiation authority, a primary examiner and/or supervisory patent examiner will also participate.
            - If the applicant declines the interview, or if the interview cannot be scheduled within ten (10) calendar days from the date that the examiner first contacts the applicant, then the examiner will proceed consistent with current practice concerning responses after final rejection under 37 CFR 1.116.

Signature	Date	Practitioner Registration No.
/Richard J. Botos	January 11, 2022	32016
Name (Print/Typed)	**Telephone Number**	
Richard J. Botos	(908) 738-1771	

***Note**: This form must be signed in accordance with 37 CFR 1.33. See 37 CFR 1.4(d) for signature requirements and certifications. Submit multiple forms if more than one signature is required, see below*.*

☐ * Total of _____ forms are submitted.

Privacy Act Statement

The **Privacy Act of 1974 (P.L. 93-579)** requires that you be given certain information in connection with your submission of the attached form related to a patent application or patent. Accordingly, pursuant to the requirements of the Act, please be advised that: (1) the general authority for the collection of this information is 35 U.S.C. 2(b)(2); (2) furnishing of the information solicited is voluntary; and (3) the principal purpose for which the information is used by the U.S. Patent and Trademark Office is to process and/or examine your submission related to a patent application or patent. If you do not furnish the requested information, the U.S. Patent and Trademark Office may not be able to process and/or examine your submission, which may result in termination of proceedings or abandonment of the application or expiration of the patent.

The information provided by you in this form will be subject to the following routine uses:

1. The information on this form will be treated confidentially to the extent allowed under the Freedom of Information Act (5 U.S.C. 552) and the Privacy Act (5 U.S.C 552a). Records from this system of records may be disclosed to the Department of Justice to determine whether disclosure of these records is required by the Freedom of Information Act.
2. A record from this system of records may be disclosed, as a routine use, in the course of presenting evidence to a court, magistrate, or administrative tribunal, including disclosures to opposing counsel in the course of settlement negotiations.
3. A record in this system of records may be disclosed, as a routine use, to a Member of Congress submitting a request involving an individual, to whom the record pertains, when the individual has requested assistance from the Member with respect to the subject matter of the record.
4. A record in this system of records may be disclosed, as a routine use, to a contractor of the Agency having need for the information in order to perform a contract. Recipients of information shall be required to comply with the requirements of the Privacy Act of 1974, as amended, pursuant to 5 U.S.C. 552a(m).
5. A record related to an International Application filed under the Patent Cooperation Treaty in this system of records may be disclosed, as a routine use, to the International Bureau of the World Intellectual Property Organization, pursuant to the Patent Cooperation Treaty.
6. A record in this system of records may be disclosed, as a routine use, to another federal agency for purposes of National Security review (35 U.S.C. 181) and for review pursuant to the Atomic Energy Act (42 U.S.C. 218(c)).
7. A record from this system of records may be disclosed, as a routine use, to the Administrator, General Services, or his/her designee, during an inspection of records conducted by GSA as part of that agency's responsibility to recommend improvements in records management practices and programs, under authority of 44 U.S.C. 2904 and 2906. Such disclosure shall be made in accordance with the GSA regulations governing inspection of records for this purpose, and any other relevant (*i.e.*, GSA or Commerce) directive. Such disclosure shall not be used to make determinations about individuals.
8. A record from this system of records may be disclosed, as a routine use, to the public after either publication of the application pursuant to 35 U.S.C. 122(b) or issuance of a patent pursuant to 35 U.S.C. 151. Further, a record may be disclosed, subject to the limitations of 37 CFR 1.14, as a routine use, to the public if the record was filed in an application which became abandoned or in which the proceedings were terminated and which application is referenced by either a published application, an application open to public inspection or an issued patent.
9. A record from this system of records may be disclosed, as a routine use, to a Federal, State, or local law enforcement agency, if the USPTO becomes aware of a violation or potential violation of law or regulation.

Electronic Acknowledgement Receipt

EFS ID:	44722473
Application Number:	16790198
International Application Number:	
Confirmation Number:	1309
Title of Invention:	Organic-Light-Emitting Diode
First Named Inventor/Applicant Name:	Ulrich KASTNER-JUNG
Customer Number:	175540
Filer:	Richard J. Botos
Filer Authorized By:	
Attorney Docket Number:	PICTIV 3.3F-001 CC [2]
Receipt Date:	11-JAN-2022
Filing Date:	13-FEB-2020
Time Stamp:	21:28:59
Application Type:	Utility under 35 USC 111(a)

Payment information:

Submitted with Payment	no

File Listing:

Document Number	Document Description	File Name	File Size(Bytes)/ Message Digest	Multi Part /.zip	Pages (if appl.)
1	After Final Consideration Program Request	PICTIVA2.pdf	223714 dc73cefbcfd1f2cabfa259d291f5168f41349966	no	2

Warnings:

Information:	
Total Files Size (in bytes):	223714

This Acknowledgement Receipt evidences receipt on the noted date by the USPTO of the indicated documents, characterized by the applicant, and including page counts, where applicable. It serves as evidence of receipt similar to a Post Card, as described in MPEP 503.

New Applications Under 35 U.S.C. 111

If a new application is being filed and the application includes the necessary components for a filing date (see 37 CFR 1.53(b)-(d) and MPEP 506), a Filing Receipt (37 CFR 1.54) will be issued in due course and the date shown on this Acknowledgement Receipt will establish the filing date of the application.

National Stage of an International Application under 35 U.S.C. 371

If a timely submission to enter the national stage of an international application is compliant with the conditions of 35 U.S.C. 371 and other applicable requirements a Form PCT/DO/EO/903 indicating acceptance of the application as a national stage submission under 35 U.S.C. 371 will be issued in addition to the Filing Receipt, in due course.

New International Application Filed with the USPTO as a Receiving Office

If a new international application is being filed and the international application includes the necessary components for an international filing date (see PCT Article 11 and MPEP 1810), a Notification of the International Application Number and of the International Filing Date (Form PCT/RO/105) will be issued in due course, subject to prescriptions concerning national security, and the date shown on this Acknowledgement Receipt will establish the international filing date of the application.

PTO/SB/06 (09-11)
Approved for use through 1/31/2014. OMB 0651-0032
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

PATENT APPLICATION FEE DETERMINATION RECORD Substitute for Form PTO-875	Application or Docket Number 16/790,198	Filing Date 02/13/2020	☐ To be Mailed

ENTITY: ☑ LARGE ☐ SMALL ☐ MICRO

APPLICATION AS FILED - PART I

FOR	(Column 1) NUMBER FILED	(Column 2) NUMBER EXTRA		RATE ($)	FEE ($)
☐ BASIC FEE (37 CFR 1.16(a), (b), or (c))	N/A	N/A		N/A	
☐ SEARCH FEE (37 CFR 1.16(k), (i), or (m))	N/A	N/A		N/A	
☐ EXAMINATION FEE (37 CFR 1.16(o), (p), or (q))	N/A	N/A		N/A	
TOTAL CLAIMS (37 CFR 1.16(i))	minus 20 =	*		x $100 =	
INDEPENDENT CLAIMS (37 CFR 1.16(h))	minus 3 =	*		x $460 =	
☐ APPLICATION SIZE FEE (37 CFR 1.16(s))	If the specification and drawings exceed 100 sheets of paper, the application size fee due is $310 ($155 for small entity) for each additional 50 sheets or fraction thereof. See 35 U.S.C. 41(a)(1)(G) and 37 CFR 1.16(s).				
☐ MULTIPLE DEPENDENT CLAIM PRESENT (37 CFR 1.16(j))					
* If the difference in column 1 is less than zero, enter "0" in column 2.				TOTAL	

APPLICATION AS AMENDED - PART II

		(Column 1)		(Column 2)	(Column 3)			
AMENDMENT	01/11/2022	CLAIMS REMAINING AFTER AMENDMENT		HIGHEST NUMBER PREVIOUSLY PAID FOR	PRESENT EXTRA		RATE ($)	ADDITIONAL FEE ($)
	Total (37 CFR 1.16(i))	* 12	Minus	** 20	= 0		x $100 =	0
	Independent (37 CFR 1.16(h))	* 2	Minus	*** 3	= 0		x $480 =	0
	☐ Application Size Fee (37 CFR 1.16(s))							
	☐ FIRST PRESENTATION OF MULTIPLE DEPENDENT CLAIM (37 CFR 1.16(j))							
							TOTAL ADD'L FEE	0

		(Column 1)		(Column 2)	(Column 3)			
AMENDMENT		CLAIMS REMAINING AFTER AMENDMENT		HIGHEST NUMBER PREVIOUSLY PAID FOR	PRESENT EXTRA		RATE ($)	ADDITIONAL FEE ($)
	Total (37 CFR 1.16(i))	*	Minus	**	=		x $0 =	
	Independent (37 CFR 1.16(h))	*	Minus	***	=		x $0 =	
	☐ Application Size Fee (37 CFR 1.16(s))							
	☐ FIRST PRESENTATION OF MULTIPLE DEPENDENT CLAIM (37 CFR 1.16(j))							
							TOTAL ADD'L FEE	

* If the entry in column 1 is less than the entry in column 2, write "0" in column 3.	LIE
** If the "Highest Number Previously Paid For" IN THIS SPACE is less than 20, enter "20".	/MARSHA R RICHARDS/
*** If the "Highest Number Previously Paid For" IN THIS SPACE is less than 3, enter "3".	
The "Highest Number Previously Paid For" (Total or Independent) is the highest number found in the appropriate box in column 1.	

This collection of information is required by 37 CFR 1.16. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 12 minutes to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.**

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

Electronic Acknowledgement Receipt

EFS ID:	44720986
Application Number:	16790198
International Application Number:	
Confirmation Number:	1309
Title of Invention:	Organic-Light-Emitting Diode
First Named Inventor/Applicant Name:	Ulrich KASTNER-JUNG
Customer Number:	175540
Filer:	Richard J. Botos/Elizabeth Gagliano
Filer Authorized By:	Richard J. Botos
Attorney Docket Number:	PICTIV 3.3F-001 CC [2]
Receipt Date:	11-JAN-2022
Filing Date:	13-FEB-2020
Time Stamp:	17:30:20
Application Type:	Utility under 35 USC 111(a)

Payment information:

Submitted with Payment	no

File Listing:

Document Number	Document Description	File Name	File Size(Bytes)/ Message Digest	Multi Part /.zip	Pages (if appl.)
1	Miscellaneous Incoming Letter	PICTIV_3_3F-001_CON_CON_Matter_2__-_Amendment_Transmittal.pdf	933816 5ed60331237ac3e6cbdb457a0dea7e01b7d8f046	no	1

Warnings:

Information:					
2	Amendment Copy Claims/Response to Suggested Claims	PICTIV_3_3F-001_CON_CON_Matter_2__-_Amendment_in_Response_to_FOA_mailed_10_29_2021.pdf	541412 a2fa19cb004c2c022e547b14943d394b07b03f96	no	11
Warnings:					
Information:					
			Total Files Size (in bytes):	1475228	

This Acknowledgement Receipt evidences receipt on the noted date by the USPTO of the indicated documents, characterized by the applicant, and including page counts, where applicable. It serves as evidence of receipt similar to a Post Card, as described in MPEP 503.

New Applications Under 35 U.S.C. 111

If a new application is being filed and the application includes the necessary components for a filing date (see 37 CFR 1.53(b)-(d) and MPEP 506), a Filing Receipt (37 CFR 1.54) will be issued in due course and the date shown on this Acknowledgement Receipt will establish the filing date of the application.

National Stage of an International Application under 35 U.S.C. 371

If a timely submission to enter the national stage of an international application is compliant with the conditions of 35 U.S.C. 371 and other applicable requirements a Form PCT/DO/EO/903 indicating acceptance of the application as a national stage submission under 35 U.S.C. 371 will be issued in addition to the Filing Receipt, in due course.

New International Application Filed with the USPTO as a Receiving Office

If a new international application is being filed and the international application includes the necessary components for an international filing date (see PCT Article 11 and MPEP 1810), a Notification of the International Application Number and of the International Filing Date (Form PCT/RO/105) will be issued in due course, subject to prescriptions concerning national security, and the date shown on this Acknowledgement Receipt will establish the international filing date of the application.

AFTER FINAL AMENDMENT TRANSMITTAL LETTER			Docket No. PICTIV 3.3F-001 CC [2]
Application No. 16/790,198 /Conf. #1309	Filing Date February 13, 2020	Examiner James Hyonchol Cho	Art Unit 2844

Applicant(s): PICTIVA DISPLAYS INTERNATIONAL LIMITED

Invention: ORGANIC LIGHT-EMITTING DIODE

TO THE COMMISSIONER FOR PATENTS

Transmitted herewith is an amendment in the above-identified application.

The fee has been calculated and is transmitted as shown below.

CLAIMS AS AMENDED					
	Claims Remaining After Amendment	Highest Number Previously Paid	Number Extra Claims Present	Rate	
Total Claims	12	- 20 =	0	$ 100.00	
Independent Claims	2	- 3 =	0	$ 480.00	
Multiple Dependent Claims (check if applicable)	☐				
Other fee (please specify):					
TOTAL ADDITIONAL FEE FOR THIS AMENDMENT:					$ 0.00

☑ Large Entity ☐ Small Entity

☑ No additional fee is required for this amendment.

☐ Please charge Deposit Account No. _____ in the amount of $ _____ .

☐ A check in the amount of $ _____ to cover the filing fee is enclosed.

☐ Payment by credit card. Form PTO-2038 is attached.

☑ The Director is hereby authorized to charge and credit Deposit Account No. 60-1866 as described below. A duplicate copy of this sheet is enclosed.

☑ Credit any overpayment.

☑ Charge any additional filing or application processing fees required under 37 C.F.R. § 1.16 and 1.17.

/Richard J. Botos/ Dated: 1/11/2022

Richard J. Botos
Attorney/Agent Reg. No.: 32,016
BOTOS CHURCHILL IP LAW LLP
430 Mountain Avenue, Suite 401
New Providence, New Jersey 07974

I hereby certify that this paper (along with any paper referred to as being attached or enclosed) is being transmitted via the Office electronic filing system in accordance with 37 CFR § 1.6(a)(4).

Dated: 1/11/2022 Electronic Signature for Richard J. Botos /Richard J. Botos/

I hereby certify that this paper (along with any paper referred to as being attached or enclosed) is being transmitted via the Office electronic filing system in accordance with 37 CFR § 1.6(a)(4).

Dated: January 11, 2022
Electronic Signature for Richard J. Botos: /Richard J. Botos/

Docket No.: PICTIV 3.3F-001 CC [2]
(PATENT)

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Patent Application of:
Kastner-Jung et al.

Application No.: 16/790,198 | Confirmation No.: 1309

Filing Date: February 13, 2020 | Art Unit: 2844

For: ORGANIC LIGHT-EMITTING DIODE | Examiner: James Hyonchol Cho

---

Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

AMENDMENT

Dear Sir:

In reply to the Final Office Action dated October 29, 2021, the following amendments and remarks are respectfully submitted in connection with the above-identified application.

IN THE CLAIMS

1. (Currently Amended) A device comprising:

an organic light-emitting diode comprising an organic layer sequence, a radiation exit area and an encapsulation all disposed on a flexible carrier, wherein the organic layer sequence comprises at least one radiation-emitting region which generates electromagnetic radiation in a spectral range from infrared radiation to UV radiation during operation, and wherein the encapsulation forms a seal of the organic layer sequence against environmental influences~~,~~; and

at least one touch-sensitive operating element, wherein the at least one touch-sensitive operating element comprises at least one touch sensor, and wherein the device is flexible.

2. (Currently Amended) The device according to claim 1, wherein the device [[in]]is bendable or can be rolled.

3. (Original) The device according to claim 2, wherein the device maintains its form after bending.

4. (Canceled).

5. (Original) The device according to claim 4, wherein the flexible carrier comprises a film or a plastic film or a laminate.

6. (Original) The device according to claim 1, wherein the encapsulation is flexible.

7. (Original) The device according to claim 1, wherein the touch-sensitive operating element is arranged at a light exit area of the device.

8. (Original) The device according to claim 1, wherein the at least one touch sensor is integrated into the organic light-emitting diode.

9. (Original) The device according to claim 1, wherein the device is drivable by means of a gesture control.

SDC EX. 1027 - 383/489

10. (Currently Amended) A device comprising:

an organic light-emitting diode comprising an organic layer sequence, a radiation exit area and an encapsulation, wherein the organic layer sequence comprises at least one radiation-emitting region which generates electromagnetic radiation in a spectral range from infrared radiation to UV radiation during operation, and wherein the encapsulation forms a seal of the organic layer sequence against environmental influences,

at least one touch-sensitive operating element, wherein the at least one touch-sensitive operating element comprises at least one touch sensor, wherein

the device is formed on a flexible carrier whereby the device is bendable or can be rolled.

11. (Original) The device according to claim 10, wherein the touch-sensitive operating element is arranged at a light exit area of the device.

12. (Original) The device according to claim 10, wherein the at least one touch sensor is integrated into the organic light-emitting diode.

13. (Original) The device according to claim 10, wherein the device is drivable by means of a gesture control.

SDC EX. 1027 - 384/489

REMARKS

This communication is responsive to the Final Office Action dated October 29, 2021 (hereinafter the "Final Office Action"). In this communication, claims 1, 2, and 10 are amended, and claim 4 is canceled. Thus, claims 1-3 and 5-13 are presented for consideration in view of the following remarks. Support for the amendments may be found by reference to, for example, paragraphs [0419]-[0420] of the specification. Applicant respectfully submits that no new matter has been added by the foregoing amendments. The rejections will be addressed in view of the claims as presented herein.

Claim Rejections

Claim Rejections - 35 USC § 103

Claims 1 and 4-9 are rejected under pre-AIA 35 U.S.C. 103(a) as being unpatentable over US Patent Publication No. 2011/0187668 A1 to Hente ("*Hente*" hereinafter) in view of US Patent Publication No. 2011/0096504 A1 to Hild ("*Hild*" hereinafter).

Hente allegedly describes an organic light-emitting diode (102) comprising an organic layer sequence (cathode 106, an organic layer 108, an anode 110, substrate 112), a radiation exit area (conductive elements transmitting light), wherein the organic layer sequence has a least on radiation-emitting region (conductive elements) which generates electromagnetic radiation in the spectral range from infrared radiation to UV radiation during operation (visible light which the operator can see in spectral range from infrared to UV as described in paragraph [0023] of *Hente*). The organic layer 108 in *Hente* is disposed between the cathode 106 and the anode 110. The conductive elements 118, 120, 122, and 124 of *Hente* may be adapted to transmit light.

The Office Action alleges that *Hente* also describes a touch-sensitive element (near-field imaging (NFI) touch sensor described in paragraph [0001]), wherein the at least one touch-sensitive operating element comprises at least one touch sensor. The NFI touch sensor is integrated by a NFI touch sensor foil 104 comprising a second substrate (paragraph [0019] of *Hente*). *Hente* states that the *second* substrate may be formed from a flexible material (paragraph [0020][1]). *Hente* does not describe the substrate 112 on which the OLED means is mounted as flexible.

[1] *Hente*, paragraph [0020], states, "[i]n another embodiment, the second substrate is constructed from a flexible material. This had the advantage that a touch sensor constructed out of a flexible material such as plastic can be mounted to the OLED means."

SDC EX. 1027 - 385/489

Therefore, *Hente* does not describe a flexible *device* that is an OLED device having an encapsulation that seals the organic layer against environmental influences. *Hente* actually teaches away from this objective by contemplating a second flexible substrate but never contemplating that the substrate 112 that supports the organic device be flexible.

The Office Action suggests that it would be obvious to modify the *Hente* device by adding an encapsulation layer such as described in *Hild*. Applicant addresses the deficiencies of *Hild* as a reference that might suggest such a modification to the skilled person below. However, a more fundamental question is, if *Hente* were modified to have an encapsulation layer, where would such an encapsulation layer be placed? For example, if an encapsulation layer were to be provided in the *Hente* device, would it be placed over the substrate 112 and over the sides of the OLED means or over the cathode 106 and the sides of the OLED means or just over portions of the organic layer 108? It is not at all clear from *Hente* or the secondary references (*Hild* and/or *Yoshida*) how an encapsulation layer might be integrated on the *Hente* device.




FIG. 2


In the Response to Arguments at pages 7-9, the Office Action states that claim 1 merely recites that the device is flexible and that claims 2 and 10 simply recite a device that is bendable or can be rolled. The Office Action seems to suggest that the claims fail to recite flexible device structures, but only flexible device properties.

Applicant amends claims 1 and 10 to recite that the device is formed on a flexible carrier. The flexible carrier 130, the organic sequence 133, the second electrode (i.e., the cathode 107) and

SDC EX. 1027 - 386/489

the encapsulation 154 are illustrated in FIG. 10 of the present application, which is reproduced below.

FIG 10



The Office Action concedes that *Hente* does not describe an encapsulation that seals the organic layer from the environment. The Office Action alleges that *Hild* contemplates such encapsulation, citing [0011]-[0012], [0048]-[0049], and [0056].


Specifically, the Office Action alleges that the *Hild* teaches a flexibly bendable top-emitting OLED, with an encapsulation. Applicant previously argued that the Office's interpretation of *Hild* was contradicted by paragraph [0038] of *Hild*, which states:

> [0038] In the case of the flexible component, i.e., bendable over the entire surface, shown in FIG. 2, **the encapsulation or the cover element 5 is replaced by a flexibly bendable layer system which has a heat-conducting foil 12**. As an alternative hereto or also cumulatively hereto, the substrate can however also have a corresponding heat-conducting foil. As shown here, the heat-conducting foil can be the component of a multilayer system but it can also be the single component of the substrate or of the encapsulation. Preferably, at least one layer of the heat-conducting foil 12 is hereby metallised, this can serve not only for heat conduction but also for increasing the barrier properties relative to water and oxygen. In the configuration of the foil substrate 1 and of the flexible cover element 5, it should be noted that at least one of these two surface sides of the organic electronic component is transparent.

In the response to arguments, the Office Action states that *Hild* contemplates that the heat-conducting foil increases the barrier properties relative to water and oxygen and that the heat conducting foil can be the sole component of an encapsulation. Therefore, the Office Action contends that the description of the heat-conducting foil in *Hild* provides motivation to add an encapsulation to what is described in *Hente*. Applicant disagrees that the skilled person would use a metalized layer such as described in *Hild* to encapsulate the organic layer of the *Hente* OLED.

SDC EX. 1027 - 387/489

Note that, in *Hild*, the OLED 3 is surrounded by the foil substrate 1, and the heat conducting material 12. In *Hente*, the OLED layer is not encapsulated. Furthermore, *Hente* describes an OLED means 102 with a laminated NFI sensor foil 104. *See* paragraph [0035] of *Hente*. As stated in paragraph [0037] of *Hild*, "[t]he foil layer 12b hence forms a cavity in the region of the OLED stack 3, analogously to the case shown in FIG. 1." Therefore, applicant submits that *Hild* cannot be relied on to remedy the deficiencies of *Hente* with regard to flexibility and encapsulation when there is no guidance provided by *Hild* on how to modify *Hente* to provide those features.



Furthermore, the skilled person would not encapsulate the organic layer in *Hente* with a metallized layer, such as the foil substrate 1 and the heat-conducting foil 12. The Office Action does not explain where and how the metallized/metallic layer would be incorporated into the *Hente* device. Because the metallized layer is conductive, current generated in one region will be transmitted throughout the metallized (or metallic) layer. Such metallized or metallic layers would possess only one electric potential over the whole surface. Thus, different capacitances at different locations, which is the stated objective of the *Hente* device, is not achievable if the organic layer 108 of *Hente* were to be encapsulated with a metallized/metallic layer. Applicant refers to paragraphs [0005] and [0036] of *Hente* in this regard.

> [0005] The change in capacitance can be due to an increase or decrease in the capacitance of the individual conductive elements to ground or they can be due to changes in the electric field caused by the approaching object. Both conductive objects and dielectric objects will cause a change in the capacitance between individual elements. Some elements have their capacitance and hence the measured current change more than others. **These localized changes in the current allow the location of the touch to be inferred.** The elements

SDC EX. 1027 - 388/489

which are affected less by the approaching object can be used as a reference compare against when determining the threshold for when a touch has occurred.

[0036] FIG. 2 shows a simplified electrical model of the OLED device superimposed upon a OLED device 200. Visible is a finger 126 which is a [sic] approaching the OLED device 200. This figure shows a model of the different capacitances and their relationship with the components in the OLED device. The same OLED means 102 and NFI sensor foil 104 of FIG. 1 are shown in this figure as a cross section. There are four conductive elements in this FIGS. 118, 120, 122, and 124. There is a capacitance between each of these conductive elements 118, 120, 122, and 124 and the anode 110. The capacitance between the first conductive element 118 and the anode is 150. The capacitance between the second conductive element 120 and the anode is capacitance 152. The capacitance between the third conductive 122 element and the anode is capacitance 154. The capacitance between the fourth conductive element 124 and the anode is 156. The OLED device is modelled as a diode 160 and a capacitance 158 which represents the capacitance between the anode 110 and the cathode 106. The conductive elements also have a stray capacitance between them. Capacitance 140 is the capacitance between the first 118 and the second 120 conductive elements. Capacitance 142 is the capacitance between the second conductive element 120 and the third conductive element 122. Capacitance 144 is the capacitance between the third conductive element 122 and the fourth conductive element 124. Visible in this figure is a finger 126. There is a capacitance between the operator's finger 126 and each of the conductive elements. The capacitance between the finger 126 and the first conductive element 118 is capacitance 130. The capacitance between the finger 126 and the second conductive element 120 is capacitance 132. The capacitance between the finger 126 and the third conductive element 122 is capacitance 134. The capacitance between the finger and the fourth conductive element 124 is capacitance 136. In this figure it is seen that the finger or the operator's hand 126 is located closer to some of the conductive elements than to other conductive elements. **The effect of this is that when the finger is in this position, the change in the capacitance of conductive elements 118, 120, 122, and 124 will be different. The comparison of these different changes in capacitance is how the sensor is able to detect a touch under varied conditions.**

(emphasis added).

If *Hente* were modified to encapsulate the organic layer with a metallized or metal layer, the potential induced by a touch on a distinct location would be distributed over the whole surface of the metallized layer. Consequently, the discrete potential and, thus, the discrete difference in capacitance between the touch region and other regions of the device could not be measured. Therefore, the NFI touch sensor of *Hente* would not able to detect a touch in a particular region if it were modified to include a metallized or metal encapsulation layer as taught by *Hild*. Thus, combining the metallized encapsulation layer of *Hild* with the touch sensor of *Hente* would lead to an OLED device without a touch sensor that works in the manner described by *Hente*.

To evade this problem would require a modification to the metallized or metallic encapsulation layer described in *Hild*, which is not contemplated by *Hild* nor obvious from *Hente*. Specifically, the metallized layer 12 a in FIG. 2 of *Hild* would need to be omitted. Metallized or metallic layer 12 a, which provides flexible encapsulation according to *Hild*, is described in paragraph [0036] of *Hild*, which is reproduced below:

> [0036] Likewise, the rigid cover glass 5 with cavity in the embodiment of FIG. 1 together with thermally conductive layer 7 is replaced in the present case by a flexibly bendable cover element which comprises a flexibly bendable layer system. The flexibly bendable layer system 5 hereby has three layers disposed one above the other, however there can also be more or less than three layers (viewed in the direction from the side orientated away from the substrate to the side orientated towards the substrate): an uppermost, outermost cover layer comprising a carrier foil made of polypropylene, polyethylene, PI or PET (reference number 5 a). Disposed abutting thereon there follows a heat-conducting foil 12 consisting of two layers (which is therefore a component of the cover element 5 here). **The layer of this heat-conducting foil 12 orientated away from the foil substrate is constructed hereby as a metallised layer 12 a comprising ductile Cu or Al. Abutting against the layer 12 a there follows the second layer 12 b of the heat-conducting foil 12 (which, according to the geometric configuration, abuts against the first electrode 2, the second electrode 4 and/or the foil substrate 1 in the regions surrounding the OLED stack 3). This layer 12 b is configured here as PP-, PE-, PI-, PET- or polycarbonate layer.**
> (emphasis added).

Therefore, *Hild* teaches away from the modification to the flexibly bendable layer system 7 that would be necessary to adapt the encapsulation of *Hild* to the *Hente* device. Specifically, omitting the metallized or metallic layer from the heat-conducting foil described in *Hild* would lead to an OLED device with deteriorated properties as *Hild* expressly instructs the metallized layer 12a of is used for heat dissipation. Omitting the metallized or metallic layer 12a from the layer system that is expressly described in *Hild* could therefore lead to a device that overheats and thus loses efficiency. Hence, a person skilled in the art would have no incentive to omit the metallized layer 12a of *Hild* if drawing upon *Hild* to modify *Hente* to provide a flexible encapsulation of the organic layer in the *Hente* device.

For the sake of argument, even assuming that the combination of the flexible metallized or metallic encapsulation of *Hild* with the touch sensor device of *Hente* would lead to a functioning touch sensor, the combination of the NFI touch sensor foil discussed in *Hente* with the metallized layer 12a of *Hild* to reject claims 1 and 4-9 is improper. Such a combination would result in a bizarre situation where the touch sensor of *Hente* is not able to locate the touch (which is an express

SDC EX. 1027 - 390/489

objective of the *Hente* device). The touch sensor being able to locate the touch is an important features of the *Hente*. *See* paragraph [0005] and Figure 2 of *Hente*. Any modification of *Hente* that would reduce the express functions or features of the device described therein would therefore frustrate the purpose of the devices described in *Hente*.

MPEP § 2143.01(V) states "[i]f a proposed modification would render the prior art invention being modified unsatisfactory for its intended purpose, then there is no suggestion or motivation to make the proposed modification. *In re Gordon*, 733 F.2d 900, 221 USPQ 1125 (Fed. Cir. 1984). . . ." MPEP § 2143.01(VI) states: "[i]f the proposed modification or combination of the prior art would change the principle of operation of the prior art invention being modified, then the teachings of the references are not sufficient to render the claims *prima facie* obvious. *In re Ratti*, 270 F.2d 810, 123 USPQ 349 (CCPA 1959). . . . ".

For the foregoing reasons, applicant submits that the proposed combination of *Hente* in view of *Hild* does not render claim 1 obvious. The applicant respectfully requests that this rejection be withdrawn. Regarding the rejection of claims 4-9, those claims depend directly or indirectly from claim 1. As such, claims 4-9 are not obvious from *Hente* in view of *Hild* for the same reason that claim 1 is not obvious from the combination of these references. The Examiner is respectfully requested to withdraw this rejection.

Claims 2-3 and 10-13 are rejected under pre-AIA 35 U.S.C. 103(a) as being unpatentable over *Hente* in view of *Hild* and US Patent Publication No. 2003/0071259 A1 to Yoshida ("*Yoshida*").

Regarding the rejection of claims 2-3, applicant notes that these claims depend from claim 1, which is not obvious based on *Hente* in view of *Hild* for the reasons stated above. The Office Action alleges that *Yoshida* describes an organic electroluminescent display, especially a so-called "electronic paper" that has shape changeability by bending using an electrically conductive organic compound (citing paragraphs [0003] and [0005] of *Yoshida*). The Office Action alleges that it would be obvious to use the materials described in Yoshida in the OLED device of *Hente* and *Hild*. Applicant disagrees.

Yoshida is cited solely for its descript of an electronic paper display that has shape changeability. As such, *Yoshida* does not remedy the deficiencies of *Hente* and *Hild* as references that render obvious claim 1, from which claims 2 and 3 depend. The Examiner is respectfully

SDC EX. 1027 - 391/489

requested to withdraw rejection of claims 2 and 3 based on *Hente* in view of *Hild* and further in view of *Yoshida*.

Regarding the rejection of claims 10-13, claim 10 also recites an organic light-emitting diode having an organic layer sequence, a radiation exit area and an encapsulation, and wherein the encapsulation forms a seal of the organic layer sequence against environmental influences. Claim 10, as amended, provides that the organic light-emitting diode is formed on a flexible carrier. As such claims 10-13 are not obvious from on *Hente* in view of *Hild* and further in view of *Yoshida* for the same reasons that claims 2 and 3 are not obvious in view of these references. Again *Yoshida* does not remedy the deficiencies of the combination of *Hente* in view of *Hild* as references that render obvious the claimed organic light-emitting diode having at least one touch-sensitive operating element, the device also having an organic layer sequence and an encapsulation which is formed on a flexible carrier. The Examiner is respectfully requested to withdraw rejection of claims 10-13 based on *Hente* in view of *Hild* and further in view of *Yoshida*.

CONCLUSION

In view of the above, each of the presently pending claims in this application is believed to be in immediate condition for allowance. Accordingly, the Examiner is respectfully requested to withdraw the outstanding rejection of the claims and to pass this application to issue. If, however, for any reason the Examiner does not believe that such action can be taken at this time, it is respectfully requested that the Examiner telephone Applicant's attorney at (908) 738-1770 in order to overcome any additional objections which the Examiner might have. All required fees are being paid via credit card through EFS-Web. However, please charge any additional fees not already paid via credit card, and credit any overpayments, to our Deposit Account No. 60-1866.

Dated: January 11, 2022

Respectfully submitted,

Electronic Signature: /Richard J. Botos/
Richard J. Botos
Registration No. 32,016
Botos Churchill IP Law LLP
430 Mountain Ave., Suite 401
New Providence, NJ 07974
(908) 738-1770
Attorney for Applicant

4878-4906-9061, v. 1

SDC EX. 1027 - 392/489

UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
16/790,198	02/13/2020	Ulrich KASTNER-JUNG	PICTIV 3.3F-001 CC [2]	1309

175540 7590 02/15/2022

Botos Churchill IP Law LLP
430 Mountain Avenue
Suite 401
New Providence, NJ 07974

EXAMINER
CHO, JAMES HYONCHOL

ART UNIT	PAPER NUMBER
2844	

NOTIFICATION DATE	DELIVERY MODE
02/15/2022	ELECTRONIC

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Notice of the Office communication was sent electronically on above-indicated "Notification Date" to the following e-mail address(es):

lgagliano@bciplaw.com
pto@bciplaw.com
rbotos@bciplaw.com

Advisory Action Before the Filing of an Appeal Brief	**Application No.** 16/790,198	**Applicant(s)** KASTNER-JUNG et al.	
	Examiner James H Cho	**Art Unit** 2844	**AIA (FITF) Status** No

--The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

THE REPLY FILED 11 January 2022 FAILS TO PLACE THIS APPLICATION IN CONDITION FOR ALLOWANCE.

NO NOTICE OF APPEAL FILED

1. ☑ The reply was filed after a final rejection. No Notice of Appeal has been filed. To avoid abandonment of this application, applicant must timely file one of the following replies: (1) an amendment, affidavit, or other evidence, which places the application in condition for allowance; (2) a Notice of Appeal (with appeal fee) in compliance with 37 CFR 41.31; or (3) a Request for Continued Examination (RCE) in compliance with 37 CFR 1.114 if this is a utility or plant application. Note that RCEs are not permitted in design applications. The reply must be filed within one of the following time periods:
   a) ☑ The period for reply expires 3 months from the mailing date of the final rejection.
   b) ☐ The period for reply expires on: (1) the mailing date of this Advisory Action; or (2) the date set forth in the final rejection, whichever is later. In no event, however, will the statutory period for reply expire later than SIX MONTHS from the mailing date of the final rejection.
   c) ☐ A prior Advisory Action was mailed more than 3 months after the mailing date of the final rejection in response to a first after-final reply filed within 2 months of the mailing date of the final rejection.The current period for reply expires ____ months from the mailing date of *the prior Advisory Action* or SIX MONTHS from the mailing date of the final rejection, whichever is earlier.
   Examiner Note: If box 1 is checked, check either box (a), (b) or (c). ONLY CHECK BOX (b) WHEN THIS ADVISORY ACTION IS THE FIRST RESPONSE TO APPLICANTS FIRST AFTER-FINAL REPLY WHICH WAS FILED WITHIN TWO MONTHS OF THE FINAL REJECTION. ONLY CHECK BOX (c) IN THE LIMITED SITUATION SET FORTH UNDER BOX (c). See MPEP 706.07(f).

Extensions of time may be obtained under 37 CFR 1.136(a). The date on which the petition under 37 CFR 1.136(a) and the appropriate extension fee have been filed is the date for purposes of determining the period of extension and the corresponding amount of the fee. The appropriate extension fee under 37 CFR 1.17(a) is calculated from: (1) the expiration date of the shortened statutory period for reply originally set in the final Office action; or (2) as set forth in (b) or (c) above, if checked. Any reply received by the Office later than three months after the mailing date of the final rejection, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

NOTICE OF APPEAL

2. ☐ The Notice of Appeal was filed on _____. A brief in compliance with 37 CFR 41.37 must be filed within two months of the date of filing the Notice of Appeal (37 CFR 41.37(a)), or any extension thereof (37 CFR 41.37(e)), to avoid dismissal of the appeal. Since a Notice of Appeal has been filed, any reply must be filed within the time period set forth in 37CFR 41.37(a).

AMENDMENTS

3. ☑ The proposed amendments filed after a final rejection, but prior to the date of filing a brief, will not be entered because
   a) ☑ They raise new issues that would require further consideration and/or search (see NOTE below);
   b) ☐ They raise the issue of new matter (see NOTE below);
   c) ☐ They are not deemed to place the application in better form for appeal by materially reducing or simplifying the issues for appeal; and/or
   d) ☐ They present additional claims without canceling a corresponding number of finally rejected claims.
   NOTE: See Continuation Sheet (See 37 CFR 1.116 and 41.33(a)).
4. ☐ The amendments are not in compliance with 37 CFR 1.121. See attached Notice of Non-Compliant Amendment (PTOL-324).
5. ☐ Applicant's reply has overcome the following rejection(s): _____
6. ☐ Newly proposed or amended claim(s) _____ would be allowable if submitted in a separate, timely filed amendment canceling the non-allowable claim(s).
7. ☐ For purposes of appeal, the proposed amendment(s):(a) ☐ will not be entered, or (b) ☐ will be entered, and an explanation of how the new or amended claims would be rejected is provided below or appended.

AFFIDAVIT OR OTHER EVIDENCE

8. ☐ A declaration(s)/affidavit(s) under **37 CFR 1.130(b)** was/were filed on _____
9. ☐ The affidavit or other evidence filed after final action, but before or on the date of filing a Notice of Appeal will not be entered because applicant failed to provide a showing of good and sufficient reasons why the affidavit or other evidence is necessary and was not earlier presented. See 37 CFR 1.116(e).
10. ☐ The affidavit or other evidence filed after the date of filing the Notice of Appeal, but prior to the date of filing a brief, will not be entered because the affidavit or other evidence failed to overcome all rejections under appeal and/or appellant fails to provide a showing of good and sufficient reasons why it is necessary and was not earlier presented. See 37 CFR 41.33(d)(1).
11. ☐ The affidavit or other evidence is entered. An explanation of the status of the claims after entry is below or attached.

REQUEST FOR RECONSIDERATION/OTHER

12. ☑ The request for reconsideration has been considered but does NOT place the application in condition for allowance because: See Continuation Sheet.
13. ☐ Note the attached Information *Disclosure Statement*(s). (PTO/SB/08) Paper No(s). _____
14. ☑ Other: PTO-2323 is attached.

STATUS OF CLAIMS

15. The status of the claim(s) is (or will be) as follows:
    Claim(s) allowed:_____.
    Claim(s) objected to:_____.
    Claim(s) rejected:1-13.
    Claim(s) withdrawn from consideration:_____.

/JAMES H CHO/ Examiner, Art Unit 2844	/AMY COHEN JOHNSON/ Supervisory Patent Examiner, Art Unit 2844

Continuation of 3. NOTE: The proposed Claims 1 and 10 include a new issue by stating "all disposed on a flexible carrier" and "formed on a flexible carrier whereby the device is flexible" respectively while canceled claim 4 broadly recited "the organic light-emitting diode comprises a flexible carrier", which requires further consideration and searches.

Continuation of REQUEST FOR RECONSIDERATION/OTHER 12. The request for reconsideration has been considered but does NOT place the application in condition for allowance because:
Applicant's arguments are mostly based on the new issues, "all disposed on a flexible carrier" (claim 1), and "the device is formed on a flexible carrier" (claim 10), which require a further consideration and searches. The examiner also notes that the proposed claim 1 is unclear and indefinite since what the wording "all" is referring to.

Applicant argues that "Hild cannot be relied on to remedy the deficiencies of Hente with regard to flexibility and encapsulation" where "there is no guidance provided by Hild on how to modify Hente to provide those features".

Regarding the obviousness rejection of claim 1, it is noted that Hente clearly teaches that the OLED device comprises an NFI tough sensor foil having a second substrate which is flexible as noted in paragraph [0020] and claim 8 as discussed in the Final Office action mailed 10/29/2021.

The Office Action mailed 10/29/2021 clearly stated that the Hild reference teaches a flexibly bendable top-emitting OLED being encapsulated for forming a sealing against water and air such that providing a corresponding seal for the OLED of Hente is obvious to a person ordinary skill in the art.

The examiner recognizes that reference cannot be arbitrarily combined and there must be some reason by one skilled in the art would be motivated to make the proposed combination of the primary and secondary references.

However, there is no requirement that a motivation to make the modification be expressly articulated. The test for combining references is what the combination of disclosures taken as a whole would suggest to one of ordinary skill in the art.

Applicant also argues about different capacitances due to a metallized/metallic layer of Hild which would make the NFI touch sensor of Hente unable to detect a touch in a particular region. The examiner notes that Fig. 2 of Hild provides the encapsulation using the flexible cover element of 5 as well as the single component of the substrate where the heat-conducting foil of a multilayer system in para [0038]. Therefore , it would have been obvious at the time of invention to utilize the encapsulating teaching of Hild in order to provide a sealing protection to the OLED of Hente.

AFCP 2.0 Decision

Application No.	Applicant(s)	
16/790,198	KASTNER-JUNG et al.	
Examiner	**Art Unit**	**AIA (FITF) Status**
James H Cho	2844	No

This is in response to the After Final Consideration Pilot request filed 11 January 2022.

1. **Improper Request** – The AFCP 2.0 request is improper for the following reason(s) and the after final amendment submitted with the request will be treated under pre-pilot procedure.

   ☐ An AFCP 2.0 request form PTO/SB/434 (or equivalent document) was not submitted.

   ☐ A non-broadening amendment to at least one independent claim was not submitted.

   ☐ The request is not the first proper AFCP 2.0 request submitted in response to the most recent final rejection.

   ☐ Other: _____

2. **Proper Request**

   A. After final amendment submitted with the request will not be treated under AFCP 2.0.
   The after final amendment cannot be reviewed and a search conducted within the guidelines of the pilot program.

   ☑ The after final amendment will be treated under pre-pilot procedure.

   B. Updated search and/or completed additional consideration.
   The examiner performed an updated search and/or completed additional consideration of the after final amendment within the time authorized for the pilot program. The result(s) of the updated search and/or completed additional consideration are:

   ☐ 1. All of the rejections in the most recent final Office action are overcome and a Notice of Allowance is issued herewith.

   ☐ 2. The after final amendment would not overcome all of the rejections in the most recent final Office action . See attached interview summary for further details.

   ☐ 3. The after final amendment was reviewed, and it raises a new issue(s). See attached interview summary for further details.

   ☐ 4. The after final amendment raises new issues, but would overcome all of the rejections in the most recent final Office action. A decision on determining allowability could not be made within the guidelines of the pilot. See attached interview summary for further details, including any newly discovered prior art.

   ☐ 5. Other: _____

   Examiner Note: Please attach an interview summary when necessary as described above.

Receipt date: 01/11/2022

DO NOT ENTER: /JC/

02/09/2022

I hereby certify that this paper (along with any paper referred to as being attached or enclosed) is being transmitted via the Office electronic filing system in accordance with 37 CFR § 1.6(a)(4).

Dated: January 11, 2022
Electronic Signature for Richard J. Botos: /Richard J. Botos/

Docket No.: PICTIV 3.3F-001 CC [2]
(PATENT)

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Patent Application of:
Kastner-Jung et al.

Application No.: 16/790,198 Confirmation No.: 1309

Filing Date: February 13, 2020 Art Unit: 2844

For: ORGANIC LIGHT-EMITTING DIODE Examiner: James Hyonchol Cho

---

Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

AMENDMENT

Dear Sir:

In reply to the Final Office Action dated October 29, 2021, the following amendments and remarks are respectfully submitted in connection with the above-identified application.

PTO/SB/06 (09-11)
Approved for use through 1/31/2014. OMB 0651-0032
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

PATENT APPLICATION FEE DETERMINATION RECORD Substitute for Form PTO-875	Application or Docket Number 16/790,198	Filing Date 02/13/2020	☐ To be Mailed

ENTITY: ☑ LARGE ☐ SMALL ☐ MICRO

APPLICATION AS FILED - PART I

FOR	(Column 1) NUMBER FILED	(Column 2) NUMBER EXTRA		RATE ($)	FEE ($)
☐ BASIC FEE (37 CFR 1.16(a), (b), or (c))	N/A	N/A		N/A	
☐ SEARCH FEE (37 CFR 1.16(k), (i), or (m))	N/A	N/A		N/A	
☐ EXAMINATION FEE (37 CFR 1.16(o), (p), or (q))	N/A	N/A		N/A	
TOTAL CLAIMS (37 CFR 1.16(i))	minus 20 =	*		x $100 =	
INDEPENDENT CLAIMS (37 CFR 1.16(h))	minus 3 =	*		x $460 =	
☐ APPLICATION SIZE FEE (37 CFR 1.16(s))	If the specification and drawings exceed 100 sheets of paper, the application size fee due is $310 ($155 for small entity) for each additional 50 sheets or fraction thereof. See 35 U.S.C. 41(a)(1)(G) and 37 CFR 1.16(s).				
☐ MULTIPLE DEPENDENT CLAIM PRESENT (37 CFR 1.16(j))					
* If the difference in column 1 is less than zero, enter "0" in column 2.				TOTAL	

APPLICATION AS AMENDED - PART II

		(Column 1)		(Column 2)	(Column 3)			
AMENDMENT	03/25/2022	CLAIMS REMAINING AFTER AMENDMENT		HIGHEST NUMBER PREVIOUSLY PAID FOR	PRESENT EXTRA		RATE ($)	ADDITIONAL FEE ($)
	Total (37 CFR 1.16(i))	* 12	Minus	** 20	= 0		x $100 =	0
	Independent (37 CFR 1.16(h))	* 2	Minus	*** 3	= 0		x $480 =	0
	☐ Application Size Fee (37 CFR 1.16(s))							
	☐ FIRST PRESENTATION OF MULTIPLE DEPENDENT CLAIM (37 CFR 1.16(j))							
							TOTAL ADD'L FEE	0

		(Column 1)		(Column 2)	(Column 3)			
AMENDMENT		CLAIMS REMAINING AFTER AMENDMENT		HIGHEST NUMBER PREVIOUSLY PAID FOR	PRESENT EXTRA		RATE ($)	ADDITIONAL FEE ($)
	Total (37 CFR 1.16(i))	*	Minus	**	=		x $0 =	
	Independent (37 CFR 1.16(h))	*	Minus	***	=		x $0 =	
	☐ Application Size Fee (37 CFR 1.16(s))							
	☐ FIRST PRESENTATION OF MULTIPLE DEPENDENT CLAIM (37 CFR 1.16(j))							
							TOTAL ADD'L FEE	

* If the entry in column 1 is less than the entry in column 2, write "0" in column 3.	LIE
** If the "Highest Number Previously Paid For" IN THIS SPACE is less than 20, enter "20".	/ALLYSON PURNELL/
*** If the "Highest Number Previously Paid For" IN THIS SPACE is less than 3, enter "3".	
The "Highest Number Previously Paid For" (Total or Independent) is the highest number found in the appropriate box in column 1.	

This collection of information is required by 37 CFR 1.16. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 12 minutes to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.**

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

PTO/SB/30 (11-17)
Approved for use through 11/30/2020. OMB 0651-0031
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

Request for Continued Examination (RCE) Transmittal

Address to:
Mail Stop RCE
Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

Application Number	16/790,198 / Conf. #1309
Filing Date	February 13, 2020
First Named Inventor	Ulrich Kastner-Jung
Art Unit	2844
Examiner Name	James Hyonchol Cho
Attorney Docket Number	PICTIV 3.3F-001 CON CON [2]

This is a Request for Continued Examination (RCE) under 37 CFR 1.114 of the above-identified application.
Request for Continued Examination (RCE) practice under 37 CFR 1.114 does not apply to any utility or plant application filed prior to June 8, 1995, or to any design application. See Instruction Sheet for RCEs (not to be submitted to the USPTO) on page 2.

1. Submission required under 37 CFR 1.114 Note: If the RCE is proper, any previously filed unentered amendments and amendments enclosed with the RCE will be entered in the order in which they were filed unless applicant instructs otherwise. If applicant does not wish to have any previously filed unentered amendment(s) entered, applicant must request non-entry of such amendment(s).

   a. ☐ Previously submitted. If a final Office action is outstanding, any amendments filed after the final Office action may be considered as a submission even if this box is not checked.

      i. ☐ Consider the arguments in the Appeal Brief or Reply Brief previously filed on _____

      ii. ☐ Other _____

   b. ☑ Enclosed

      i. ☑ Amendment/Reply

      ii. ☐ Affidavit(s)/ Declaration(s)

      iii. ☐ Information Disclosure Statement (IDS)

      iv. ☑ Other Extension Petition

2. Miscellaneous

   a. ☐ Suspension of action on the above-identified application is requested under 37 CFR 1.103(c) for a period of _____ months. (Period of suspension shall not exceed 3 months; Fee under 37 CFR 1.17(i) required)

   b. ☐ Other _____

3. Fees The RCE fee under 37 CFR 1.17(e) is required by 37 CFR 1.114 when the RCE is filed.

   a. ☑ The Director is hereby authorized to charge the following fees, any underpayment of fees, or credit any overpayments, to Deposit Account No. 60-1866.

      i. ☑ RCE fee required under 37 CFR 1.17(e)

      ii. ☑ Extension of time fee (37 CFR 1.136 and 1.17)

      iii. ☐ Other _____

   b. ☐ Check in the amount of $ _____ enclosed

   c. ☐ Payment by credit card (Form PTO-2038 enclosed)

   d. ☑ Payment by EFS-Web

WARNING: Information on this form may become public. Credit card information should not be included on this form. Provide credit card information and authorization on PTO-2038.

SIGNATURE OF APPLICANT, ATTORNEY, OR AGENT REQUIRED

Signature	/Richard J. Botos/	Date	March 25, 2022
Name (Print/Type)	Richard J. Botos	Registration No.	32,016

CERTIFICATE OF MAILING OR TRANSMISSION

I hereby certify that this correspondence is being EFS-Web transmitted to the United States Patent and Trademark Office (USPTO), deposited with the United States Postal Service with sufficient postage as first class mail in an envelope addressed to: Mail Stop RCE, Commissioner for Patents, P. O. Box 1450, Alexandria, VA 22313-1450 or facsimile transmitted to the USPTO on the date shown below.

Signature	/Richard J. Botos/		
Name (Print/Type)	Richard J. Botos	Date	March 25, 2022

This collection of information is required by 37 CFR 1.114. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.11 and 1.14. This collection is estimated to take 12 minutes to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Mail Stop RCE, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.**
If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

PTO/AIA/22 (10-20)
Approved for use through 11/30/2020. OMB 0651-0031
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

PETITION FOR EXTENSION OF TIME UNDER 37 CFR 1.136(a)

Docket Number (Optional): PICTIV 3.3F-001 CON CON [2]

Application Number: 16/790,198 / Conf. #1309

Filed: February 13, 2020

For: ORGANIC-LIGHT EMITTING DIODE

Art Unit: 2844

Examiner: James Hyonchol Cho

This is a request under the provisions of 37 CFR 1.136(a) to extend the period for filing a reply in the above-identified application.

The requested extension and fee are as follows (check time period desired and enter the appropriate fee below):

	Fee	Small Entity Fee	Micro Entity Fee	
☐ One month (37 CFR 1.17(a)(1))	$220	$110	$55	$
☑ Two months (37 CFR 1.17(a)(2))	$640	$320	$160	$ 640
☐ Three months (37 CFR 1.17(a)(3))	$1,480	$740	$370	$
☐ Four months (37 CFR 1.17(a)(4))	$2,320	$1,160	$580	$
☐ Five months (37 CFR 1.17(a)(5))	$3,160	$1,580	$790	$

☐ Applicant asserts small entity status. See 37 CFR 1.27.

☐ Applicant certifies micro entity status. See 37 CFR 1.29.
Form PTO/SB/15A or B or equivalent must either be enclosed or have been submitted previously.

☐ A check in the amount of the fee is enclosed.

☐ Payment by credit card. Form PTO-2038 is attached.

☐ The Director has already been authorized to charge fees in this application to a Deposit Account.

☑ The Director is hereby authorized to charge any fees which may be required, or credit any overpayment, to Deposit Account Number 60-1866.

☑ Payment made via EFS-Web.

WARNING: Information on this form may become public. Credit card information should not be included on this form. Provide credit card information and authorization on PTO-2038.

I am the

☐ applicant.

☑ attorney or agent of record. Registration number 32,016.

☐ attorney or agent acting under 37 CFR 1.34. Registration number _____.

/Richard J. Botos/ — Signature

March 25, 2022 — Date

Richard J. Botos — Typed or printed name

(908) 738-1770 — Telephone Number

NOTE: This form must be signed in accordance with 37 CFR 1.33. See 37 CFR 1.4 for signature requirements and certifications. Submit multiple forms if more than one signature is required, see below*.

☐ * Total of _____ forms are submitted.

This collection of information is required by 37 CFR 1.136(a). The information is required to obtain or retain a benefit by the public, which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.11 and 1.14. This collection is estimated to take 6 minutes to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Mail Stop PCT, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

Privacy Act Statement

The **Privacy Act of 1974 (P.L. 93-579)** requires that you be given certain information in connection with your submission of the attached form related to a patent application or patent. Accordingly, pursuant to the requirements of the Act, please be advised that: (1) the general authority for the collection of this information is 35 U.S.C. 2(b)(2); (2) furnishing of the information solicited is voluntary; and (3) the principal purpose for which the information is used by the U.S. Patent and Trademark Office is to process and/or examine your submission related to a patent application or patent. If you do not furnish the requested information, the U.S. Patent and Trademark Office may not be able to process and/or examine your submission, which may result in termination of proceedings or abandonment of the application or expiration of the patent.

The information provided by you in this form will be subject to the following routine uses:

1. The information on this form will be treated confidentially to the extent allowed under the Freedom of Information Act (5 U.S.C. 552) and the Privacy Act (5 U.S.C 552a). Records from this system of records may be disclosed to the Department of Justice to determine whether disclosure of these records is required by the Freedom of Information Act.
2. A record from this system of records may be disclosed, as a routine use, in the course of presenting evidence to a court, magistrate, or administrative tribunal, including disclosures to opposing counsel in the course of settlement negotiations.
3. A record in this system of records may be disclosed, as a routine use, to a Member of Congress submitting a request involving an individual, to whom the record pertains, when the individual has requested assistance from the Member with respect to the subject matter of the record.
4. A record in this system of records may be disclosed, as a routine use, to a contractor of the Agency having need for the information in order to perform a contract. Recipients of information shall be required to comply with the requirements of the Privacy Act of 1974, as amended, pursuant to 5 U.S.C. 552a(m).
5. A record related to an International Application filed under the Patent Cooperation Treaty in this system of records may be disclosed, as a routine use, to the International Bureau of the World Intellectual Property Organization, pursuant to the Patent Cooperation Treaty.
6. A record in this system of records may be disclosed, as a routine use, to another federal agency for purposes of National Security review (35 U.S.C. 181) and for review pursuant to the Atomic Energy Act (42 U.S.C. 218(c)).
7. A record from this system of records may be disclosed, as a routine use, to the Administrator, General Services, or his/her designee, during an inspection of records conducted by GSA as part of that agency's responsibility to recommend improvements in records management practices and programs, under authority of 44 U.S.C. 2904 and 2906. Such disclosure shall be made in accordance with the GSA regulations governing inspection of records for this purpose, and any other relevant (*i.e.*, GSA or Commerce) directive. Such disclosure shall not be used to make determinations about individuals.
8. A record from this system of records may be disclosed, as a routine use, to the public after either publication of the application pursuant to 35 U.S.C. 122(b) or issuance of a patent pursuant to 35 U.S.C. 151. Further, a record may be disclosed, subject to the limitations of 37 CFR 1.14, as a routine use, to the public if the record was filed in an application which became abandoned or in which the proceedings were terminated and which application is referenced by either a published application, an application open to public inspection or an issued patent.
9. A record from this system of records may be disclosed, as a routine use, to a Federal, State, or local law enforcement agency, if the USPTO becomes aware of a violation or potential violation of law or regulation.

Electronic Patent Application Fee Transmittal

Application Number:	16790198
Filing Date:	13-Feb-2020
Title of Invention:	Organic-Light-Emitting Diode
First Named Inventor/Applicant Name:	Ulrich KASTNER-JUNG
Filer:	Richard J. Botos/Elizabeth Gagliano
Attorney Docket Number:	PICTIV 3.3F-001 CC [2]

Filed as Large Entity

Filing Fees for Utility under 35 USC 111(a)

Description	Fee Code	Quantity	Amount	Sub-Total in USD($)
Basic Filing:				
Pages:				
Claims:				
Miscellaneous-Filing:				
Petition:				
Patent-Appeals-and-Interference:				
Post-Allowance-and-Post-Issuance:				
Extension-of-Time:				

Description	Fee Code	Quantity	Amount	Sub-Total in USD($)
Extension - 2 months with $0 paid	1252	1	640	640
Miscellaneous:				
RCE- 1ST REQUEST	1801	1	1360	1360
		Total in USD ($)		**2000**

Electronic Acknowledgement Receipt

EFS ID:	45322521
Application Number:	16790198
International Application Number:	
Confirmation Number:	1309
Title of Invention:	Organic-Light-Emitting Diode
First Named Inventor/Applicant Name:	Ulrich KASTNER-JUNG
Customer Number:	175540
Filer:	Richard J. Botos/Elizabeth Gagliano
Filer Authorized By:	Richard J. Botos
Attorney Docket Number:	PICTIV 3.3F-001 CC [2]
Receipt Date:	25-MAR-2022
Filing Date:	13-FEB-2020
Time Stamp:	15:45:08
Application Type:	Utility under 35 USC 111(a)

Payment information:

Submitted with Payment	yes
Payment Type	CARD
Payment was successfully received in RAM	$2000
RAM confirmation Number	E20223OF45332352
Deposit Account	
Authorized User	

The Director of the USPTO is hereby authorized to charge indicated fees and credit any overpayment as follows:

File Listing:

Document Number	Document Description	File Name	File Size(Bytes)/ Message Digest	Multi Part /.zip	Pages (if appl.)
1	Miscellaneous Incoming Letter	PICTIV_2_-_Amendment_Transmittal_-_25-Mar-2022.pdf	1958404 0d27ad7088345e21822e5bb34dad3007f5f5ab19	no	1
Warnings:					
Information:					
2	Amendment Submitted/Entered with Filing of Continued Prosecution Application (CPA)/Request for Continued Examination(RCE)	PICTIV_3_3F-001_CON_CON_Matter_2__-_Request_for_continued_examination_-25-Mar-2022.pdf	542296 986351d09e34ca1d8eae9a203f81f6a5bc7218e6	no	12
Warnings:					
Information:					
3	Request for Continued Examination (RCE)	PICTIV_2_RCE.pdf	492833 6faec6b4c8ea9ba1a0cab0abca76f48de36e33f5	no	1
Warnings:					
This is not a USPTO supplied RCE SB30 form.					
Information:					
4	Extension of Time	PICTIV_2_-_Petition_for_Extension_of_Time_-_25Mar-2022.pdf	833994 e81d4647006c4b85bc8c032b55a71bd23faee990	no	2
Warnings:					
Information:					
5	Fee Worksheet (SB06)	fee-info.pdf	40853 e3c2f01680e50ea2f10e35420cbf174cc8c2b169	no	2
Warnings:					
Information:					
		Total Files Size (in bytes):	3868380		

This Acknowledgement Receipt evidences receipt on the noted date by the USPTO of the indicated documents, characterized by the applicant, and including page counts, where applicable. It serves as evidence of receipt similar to a Post Card, as described in MPEP 503.

New Applications Under 35 U.S.C. 111

If a new application is being filed and the application includes the necessary components for a filing date (see 37 CFR 1.53(b)-(d) and MPEP 506), a Filing Receipt (37 CFR 1.54) will be issued in due course and the date shown on this Acknowledgement Receipt will establish the filing date of the application.

National Stage of an International Application under 35 U.S.C. 371

If a timely submission to enter the national stage of an international application is compliant with the conditions of 35 U.S.C. 371 and other applicable requirements a Form PCT/DO/EO/903 indicating acceptance of the application as a national stage submission under 35 U.S.C. 371 will be issued in addition to the Filing Receipt, in due course.

New International Application Filed with the USPTO as a Receiving Office

If a new international application is being filed and the international application includes the necessary components for an international filing date (see PCT Article 11 and MPEP 1810), a Notification of the International Application Number and of the International Filing Date (Form PCT/RO/105) will be issued in due course, subject to prescriptions concerning national security, and the date shown on this Acknowledgement Receipt will establish the international filing date of the application.

AMENDMENT TRANSMITTAL LETTER

Docket No.
PICTIV 3.3F-001 CC [2]

Application No.	Filing Date	Examiner	Art Unit
16/790,198 /Conf. #1309	February 13, 2020	James Hyonchol Cho	2844

Applicant(s): PICTIVA DISPLAYS INTERNATIONAL LIMITED

Invention: ORGANIC LIGHT-EMITTING DIODE

TO THE COMMISSIONER FOR PATENTS

Transmitted herewith is an amendment in the above-identified application.

The fee has been calculated and is transmitted as shown below.

CLAIMS AS AMENDED

	Claims Remaining After Amendment	Highest Number Previously Paid		Number Extra Claims Present	Rate	
Total Claims	12	- 20	=	0	$ 100.00	
Independent Claims	2	- 3	=	0	$ 480.00	
Multiple Dependent Claims (check if applicable)	☐					
Other fee (please specify):						
TOTAL ADDITIONAL FEE FOR THIS AMENDMENT:						$ 0.00

☑ Large Entity ☐ Small Entity

☑ No additional fee is required for this amendment.

☐ Please charge Deposit Account No. _____ in the amount of $ _____ .

☐ A check in the amount of $ _____ to cover the filing fee is enclosed.

☐ Payment by credit card. Form PTO-2038 is attached.

☑ The Director is hereby authorized to charge and credit Deposit Account No. 60-1866 as described below. A duplicate copy of this sheet is enclosed.

☑ Credit any overpayment.

☑ Charge any additional filing or application processing fees required under 37 C.F.R. § 1.16 and 1.17.

/Richard J. Botos/ Dated: 3/25/2022

Richard J. Botos
Attorney/Agent Reg. No.: 32,016
BOTOS CHURCHILL IP LAW LLP
430 Mountain Avenue, Suite 401
New Providence, New Jersey 07974

I hereby certify that this paper (along with any paper referred to as being attached or enclosed) is being transmitted via the Office electronic filing system in accordance with 37 CFR § 1.6(a)(4).

Dated: 3/25/2022 Electronic Signature for Richard J. Botos /Richard J. Botos/

I hereby certify that this paper (along with any paper referred to as being attached or enclosed) is being transmitted via the Office electronic filing system in accordance with 37 CFR § 1.6(a)(4).

Dated: March 25, 2022
Electronic Signature for Richard J. Botos: /Richard J. Botos/

Docket No.: PICTIV 3.3F-001 CC [2]
(PATENT)

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Patent Application of:
Kastner-Jung et al.

Application No.: 16/790,198 | Confirmation No.: 1309

Filing Date: February 13, 2020 | Art Unit: 2844

For: ORGANIC LIGHT-EMITTING DIODE | Examiner: James Hyonchol Cho

---

Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

REQUEST FOR CONTINUED EXAMINATION PURSUANT TO 37 CFR 1.114

Dear Sir:

In reply to the Final Office Action dated October 29, 2021, Applicant submits this Request for Continued Examination.

IN THE CLAIMS

1. (Currently Amended) A device comprising:

an organic light-emitting diode comprising an organic layer sequence, a radiation exit area and an encapsulation wherein the organic layer sequence and the encapsulation are disposed on a flexible carrier, and wherein the organic layer sequence comprises at least one radiation-emitting region which generates electromagnetic radiation in a spectral range from infrared radiation to UV radiation during operation, and wherein the encapsulation forms a seal of the organic layer sequence against environmental influences; and

at least one touch-sensitive operating element, wherein the at least one touch-sensitive operating element comprises at least one touch sensor, and wherein the device is flexible.

2. (Currently Amended) The device according to claim 1, wherein the device [[in]]is bendable or can be rolled.

3. (Original) The device according to claim 2, wherein the device maintains its form after bending.

4. (Canceled).

5. (Original) The device according to claim 4, wherein the flexible carrier comprises a film or a plastic film or a laminate.

6. (Original) The device according to claim 1, wherein the encapsulation is flexible.

7. (Original) The device according to claim 1, wherein the touch-sensitive operating element is arranged at a light exit area of the device.

8. (Original) The device according to claim 1, wherein the at least one touch sensor is integrated into the organic light-emitting diode.

9. (Original) The device according to claim 1, wherein the device is drivable by means of a gesture control.

10. (Currently Amended) A device comprising:

an organic light-emitting diode comprising an organic layer sequence, a radiation exit area and an encapsulation, wherein the organic layer sequence comprises at least one radiation-emitting region which generates electromagnetic radiation in a spectral range from infrared radiation to UV radiation during operation, and wherein the encapsulation forms a seal of the organic layer sequence against environmental influences,

at least one touch-sensitive operating element, wherein the at least one touch-sensitive operating element comprises at least one touch sensor, and wherein

the device is formed on a flexible carrier whereby the device is bendable or can be rolled.

11. (Original) The device according to claim 10, wherein the touch-sensitive operating element is arranged at a light exit area of the device.

12. (Original) The device according to claim 10, wherein the at least one touch sensor is integrated into the organic light-emitting diode.

13. (Original) The device according to claim 10, wherein the device is drivable by means of a gesture control.

SDC EX. 1027 - 410/489

REMARKS

This communication is responsive to the Advisory Action mailed February 15, 2022 (hereinafter the "Advisory Action"). In this communication, claims 1, 2, and 10 are amended, and claim 4 is canceled[1]. Thus, claims 1-3 and 5-13 are presented for consideration in view of the following remarks. Support for the amendments may be found by reference to, for example, paragraphs [0047], [0073], [0419]-[0420], and [0426] of the specification and claims 4 and 5. Applicant respectfully submits that no new matter has been added by the foregoing amendments. The rejections will be addressed in view of the claims as presented herein.

Claim Rejections

Claim Rejections - 35 USC § 103

Claims 1 and 4-9 are rejected under pre-AIA 35 U.S.C. 103(a) as being unpatentable over US Patent Publication No. 2011/0187668 A1 to Hente ("*Hente*" hereinafter) in view of US Patent Publication No. 2011/0096504 A1 to Hild ("*Hild*" hereinafter).

Claims 1 and 10 are amended to specify that the recited devices are formed on a flexible carrier. Such is described in paragraphs [0047], [0073], [0419]-[0420], and [0426] of Applicant's specification.

Hente allegedly describes an organic light-emitting diode (102) comprising an organic layer sequence (cathode 106, an organic layer 108, an anode 110, substrate 112), a radiation exit area (conductive elements transmitting light), wherein the organic layer sequence has a least on radiation-emitting region (conductive elements) which generates electromagnetic radiation in the spectral range from infrared radiation to UV radiation during operation (visible light which the operator can see in spectral range from infrared to UV as described in paragraph [0023] of *Hente*). The organic layer 108 in *Hente* is disposed between the cathode 106 and the anode 110. The conductive elements 118, 120, 122, and 124 of *Hente* may be adapted to transmit light.

The Office Action alleges that *Hente* also describes a touch-sensitive element (near-field imaging (NFI) touch sensor described in paragraph [0001]), wherein the at least one touch-sensitive operating element comprises at least one touch sensor. The NFI touch sensor is integrated

[1] Some of these amendments were made previously in the After Final AFCP request but the amendments were not entered as stated in the Advisory Action mailed February 15, 2021.

by a NFI touch sensor foil 104 comprising a second substrate (paragraph [0019] of *Hente*). *Hente* states that the *second* substrate may be formed from a flexible material (paragraph [0020][2]). *Hente* does not describe the substrate 112 on which the OLED means is mounted as flexible.

Therefore, *Hente* does not describe a flexible *device* that is an OLED device having an encapsulation that seals the organic layer against environmental influences. *Hente* actually teaches away from this objective by contemplating a second flexible substrate but never contemplating that the substrate 112 that supports the organic device be flexible.

The Advisory Action contends that *Hente* contemplates a flexible substrate and cites paragraph [0020] and claim 8 of *Hente* in support of this observation. The Advisory Action completely ignores the fact that *Hente* is clear that the second substrate is laminated to the first substrate (*see* paragraph [0018] of *Hente*, which states "[i]n another embodiment, the OLED device is further comprised of a second substrate[3] adapted for lamination to the OLED means. The second substrate is fabricated from a transparent material, and is laminated to the first substrate."). Laminating a flexible material to an otherwise rigid device does not make the device formed by the lamination flexible. The Office has not explained how *Hente* allows the Office to conclude that *Hente* contemplates a flexible device, when there is nothing in *Hente* that suggests that the first substrate, to which the second flexible substrate is laminated, is itself flexible. *Hente* lacks any suggestion that the complete device is flexible. When a flexible component is added to an otherwise rigid device, is the Office suggesting that somehow, miraculously, the rigid device is rendered flexible by the lamination of flexible substrate to an otherwise rigid substrate? The Applicant apologizes for pointing out that this is an utterly and completely fantastical interpretation of the device described in *Hente*. It is not supported by the reference itself and is inconsistent with *Hente's* description of the device. The *reason* that *Hente* laminates the second (flexible) substrate to the first (rigid) substrate is to provide the touch sensor describe in *Hente*. *Hente* at paragraph [0020]. The lamination in no way alters the properties of the first substrate to which the second substrate is laminated.

---

[2] *Hente*, paragraph [0020], states, "[i]n another embodiment, the second substrate is constructed from a flexible material. This had the advantage that a touch sensor constructed out of a flexible material such as plastic can be mounted to the OLED means."

[3] Claim 8 of Hente recites, "[t]he OLED device of claim 6 wherein the second substrate is flexible." Claim 6 recites the second substrate and depends from claim 5, which recites an OLED device with a first substrate for mounting OLED devices thereto.

SDC EX. 1027 - 412/489

The Office Action suggests that it would be obvious to modify the *Hente* device by adding an encapsulation layer such as described in *Hild*. Applicant addresses the deficiencies of *Hild* as a reference that might suggest such a modification to the skilled person below. However, a more fundamental question is, if *Hente* were modified to have an encapsulation layer, where would such an encapsulation layer be placed? For example, if an encapsulation layer were to be provided in the *Hente* device, would it be placed over the substrate 112 and over the sides of the OLED means or over the cathode 106 and the sides of the OLED means or just over portions of the organic layer 108? It is not at all clear from *Hente* or the secondary references (*Hild* and/or *Yoshida*) how an encapsulation layer might be integrated on the *Hente* device.





FIG. 2

In the Response to Arguments at pages 7-9, the Office Action states that claim 1 merely recites that the device is flexible and that claims 2 and 10 simply recite a device that is bendable or can be rolled. The Office Action seems to suggest that the claims fail to recite flexible device structures, but only flexible device properties.

Applicant amends claims 1 and 10 to recite that the device is formed on a flexible carrier. The flexible carrier 130, the organic sequence 133, the second electrode (i.e., the cathode 107) and the encapsulation 154 are illustrated in FIG. 10 of the present application, which is reproduced below.

SDC EX. 1027 - 413/489

FIG 10



The Office Action concedes that *Hente* does not describe an encapsulation that seals the organic layer from the environment. The Office Action alleges that *Hild* contemplates such encapsulation, citing [0011]-[0012], [0048]-[0049], and [0056].

Specifically, the Office Action alleges that the *Hild* teaches a flexibly bendable top-emitting OLED, with an encapsulation. Applicant previously argued that the Office's interpretation of *Hild* was contradicted by paragraph [0038] of *Hild*, which states:


> [0038] In the case of the flexible component, i.e., bendable over the entire surface, shown in FIG. 2, **the encapsulation or the cover element 5 is replaced by a flexibly bendable layer system which has a heat-conducting foil 12**. As an alternative hereto or also cumulatively hereto, the substrate can however also have a corresponding heat-conducting foil. As shown here, the heat-conducting foil can be the component of a multilayer system but it can also be the single component of the substrate or of the encapsulation. Preferably, at least one layer of the heat-conducting foil 12 is hereby metallised, this can serve not only for heat conduction but also for increasing the barrier properties relative to water and oxygen. In the configuration of the foil substrate 1 and of the flexible cover element 5, it should be noted that at least one of these two surface sides of the organic electronic component is transparent.

In the response to arguments, the Office Action states that *Hild* contemplates that the heat-conducting foil increases the barrier properties relative to water and oxygen and that the heat conducting foil can be the sole component of an encapsulation. Therefore, the Office Action contends that the description of the heat-conducting foil in *Hild* provides motivation to add an encapsulation to what is described in *Hente*. Applicant disagrees that the skilled person would use a metalized layer such as described in *Hild* to encapsulate the organic layer of the *Hente* OLED.

Note that, in *Hild*, the OLED 3 is surrounded by the foil substrate 1, and the heat conducting material 12. In *Hente*, the OLED layer is not encapsulated. Furthermore, *Hente* describes an OLED means 102 with a laminated NFI sensor foil 104. *See* paragraph [0035] of *Hente*. As stated in paragraph [0037] of *Hild*, "[t]he foil layer 12b hence forms a cavity in the region of the OLED

SDC EX. 1027 - 414/489

stack 3, analogously to the case shown in FIG. 1." Therefore, Applicant submits that *Hild* cannot be relied on to remedy the deficiencies of *Hente* with regard to flexibility and encapsulation when there is no guidance provided by *Hild* on how to modify *Hente* to provide those features.



Furthermore, the skilled person would not encapsulate the organic layer in *Hente* with a metallized layer, such as the foil substrate 1 and the heat-conducting foil 12. The Office Action does not explain where and how the metallized/metallic layer would be incorporated into the *Hente* device. Including the encapsulation layer of *Hild* into the OLED device with an NFI touch sensor of *Hente* would lead to an OLED device without a functioning touch sensor. This is because the heat-conducting foil 12 which is used as an encapsulation for the *Hild* OLED has a metallized layer 12a and a second layer 12b made of for example PP, PE or PET (*Hild* at paragraph [0036]). Because the metallized layer is conductive, current generated in one region will be transmitted throughout the metallized (or metallic) layer. Such metallized or metallic layers would distribute only one electric potential over the whole metallic surface. Thus, the measurement of different capacitances at different locations, which is the stated objective of the *Hente* device, is not achievable if the organic layer 108 of *Hente* were to be encapsulated with a metallized/metallic layer. Applicant refers to paragraphs [0005] and [0036] of *Hente* in this regard.

> [0005] The change in capacitance can be due to an increase or decrease in the capacitance of the individual conductive elements to ground or they can be due to changes in the electric field caused by the approaching object. Both conductive objects and dielectric objects will cause a change in the capacitance between individual elements. Some elements have their capacitance and hence the measured current change more than others. **These localized changes in the current allow the location of the touch to be inferred.** The elements

which are affected less by the approaching object can be used as a reference compare against when determining the threshold for when a touch has occurred.

[0036] FIG. 2 shows a simplified electrical model of the OLED device superimposed upon a OLED device 200. Visible is a finger 126 which is a [sic] approaching the OLED device 200. This figure shows a model of the different capacitances and their relationship with the components in the OLED device. The same OLED means 102 and NFI sensor foil 104 of FIG. 1 are shown in this figure as a cross section. There are four conductive elements in this FIGS. 118, 120, 122, and 124. There is a capacitance between each of these conductive elements 118, 120, 122, and 124 and the anode 110. The capacitance between the first conductive element 118 and the anode is 150. The capacitance between the second conductive element 120 and the anode is capacitance 152. The capacitance between the third conductive 122 element and the anode is capacitance 154. The capacitance between the fourth conductive element 124 and the anode is 156. The OLED device is modelled as a diode 160 and a capacitance 158 which represents the capacitance between the anode 110 and the cathode 106. The conductive elements also have a stray capacitance between them. Capacitance 140 is the capacitance between the first 118 and the second 120 conductive elements. Capacitance 142 is the capacitance between the second conductive element 120 and the third conductive element 122. Capacitance 144 is the capacitance between the third conductive element 122 and the fourth conductive element 124. Visible in this figure is a finger 126. There is a capacitance between the operator's finger 126 and each of the conductive elements. The capacitance between the finger 126 and the first conductive element 118 is capacitance 130. The capacitance between the finger 126 and the second conductive element 120 is capacitance 132. The capacitance between the finger 126 and the third conductive element 122 is capacitance 134. The capacitance between the finger and the fourth conductive element 124 is capacitance 136. In this figure it is seen that the finger or the operator's hand 126 is located closer to some of the conductive elements than to other conductive elements. **The effect of this is that when the finger is in this position, the change in the capacitance of conductive elements 118, 120, 122, and 124 will be different. The comparison of these different changes in capacitance is how the sensor is able to detect a touch under varied conditions.**

(emphasis added).

If *Hente* were modified to encapsulate the organic layer with a metallized or metal layer, the potential induced by a touch on a distinct location would be distributed over the whole surface of the metallized layer. Consequently, the discrete potential and, thus, the discrete difference in capacitance between the touch region and other regions of the device could not be measured. Therefore, the NFI touch sensor of *Hente* would not able to detect a touch in a particular region if it were modified to include a metallized or metal encapsulation layer as taught by *Hild*. Thus, combining the metallized encapsulation layer of *Hild* with the touch sensor of *Hente* would lead to an OLED device without a touch sensor that works in the manner described by *Hente*.

To evade this problem would require a modification to the metallized or metallic encapsulation layer described in *Hild*, which is not contemplated by *Hild* nor obvious from *Hente*. Specifically, the metallized layer 12 a in FIG. 2 of *Hild* would need to be omitted. Metallized or metallic layer 12 a, which provides flexible encapsulation according to *Hild*, is described in paragraph [0036] of *Hild*, which is reproduced below:

> [0036] Likewise, the rigid cover glass 5 with cavity in the embodiment of FIG. 1 together with thermally conductive layer 7 is replaced in the present case by a flexibly bendable cover element which comprises a flexibly bendable layer system. The flexibly bendable layer system 5 hereby has three layers disposed one above the other, however there can also be more or less than three layers (viewed in the direction from the side orientated away from the substrate to the side orientated towards the substrate): an uppermost, outermost cover layer comprising a carrier foil made of polypropylene, polyethylene, PI or PET (reference number 5 a). Disposed abutting thereon there follows a heat-conducting foil 12 consisting of two layers (which is therefore a component of the cover element 5 here). **The layer of this heat-conducting foil 12 orientated away from the foil substrate is constructed hereby as a metallised layer 12a comprising ductile Cu or Al. Abutting against the layer 12a there follows the second layer 12b of the heat-conducting foil 12 (which, according to the geometric configuration, abuts against the first electrode 2, the second electrode 4 and/or the foil substrate 1 in the regions surrounding the OLED stack 3). This layer 12b is configured here as PP-, PE-, PI-, PET- or polycarbonate layer.**
> (emphasis added).

Therefore, *Hild* teaches away from the modification to the flexibly bendable layer system 7 that would be necessary to adapt the encapsulation of *Hild* to the *Hente* device. Specifically, eliminating metallized layer 12a would deteriorate the performance of the device because layer 12a is used for heat dissipation purposes. Omitting the metallized or metallic layer 12a from the layer system that is expressly described in *Hild* could therefore lead to a device that overheats and thus loses efficiency. Hence, a person skilled in the art would have no incentive to omit the metallized layer 12a of *Hild* if drawing upon *Hild* to modify *Hente* to provide a flexible encapsulation of the organic layer in the *Hente* device.

For the sake of argument, even assuming that the combination of the flexible metallized or metallic encapsulation of *Hild* with the touch sensor device of *Hente* would lead to a functioning touch sensor, the combination of the NFI touch sensor foil discussed in *Hente* with the metallized layer 12a of *Hild* to reject claims 1 and 4-9 is improper. Such a combination would result in a bizarre situation where the touch sensor of *Hente* is not able to locate a touch by the NFI touch sensor foil (which is an express objective of the *Hente* device). The touch sensor being able to

locate the touch is an important features of the *Hente*. *See* paragraph [0005] and Figure 2 of *Hente*. Any modification of *Hente* that would reduce the express functions or features of the device described therein would therefore frustrate the purpose of the devices described in *Hente*.

MPEP § 2143.01(V) states "[i]f a proposed modification would render the prior art invention being modified unsatisfactory for its intended purpose, then there is no suggestion or motivation to make the proposed modification. *In re Gordon*, 733 F.2d 900, 221 USPQ 1125 (Fed. Cir. 1984). . . ." MPEP § 2143.01(VI) states: "[i]f the proposed modification or combination of the prior art would change the principle of operation of the prior art invention being modified, then the teachings of the references are not sufficient to render the claims *prima facie* obvious. *In re Ratti*, 270 F.2d 810, 123 USPQ 349 (CCPA 1959). . . . ".

For the foregoing reasons, Applicant submits that the proposed combination of *Hente* in view of *Hild* does not render claim 1 obvious. The Applicant respectfully requests that this rejection be withdrawn. Regarding the rejection of claims 4-9, those claims depend directly or indirectly from claim 1. As such, claims 4-9 are not obvious from *Hente* in view of *Hild* for the same reason that claim 1 is not obvious from the combination of these references. The Examiner is respectfully requested to withdraw this rejection.

Claims 2-3 and 10-13 are rejected under pre-AIA 35 U.S.C. 103(a) as being unpatentable over *Hente* in view of *Hild* and US Patent Publication No. 2003/0071259 A1 to Yoshida ("*Yoshida*").

Regarding the rejection of claims 2-3, Applicant notes that these claims depend from claim 1, which is not obvious based on *Hente* in view of *Hild* for the reasons stated above. The Office Action alleges that *Yoshida* describes an organic electroluminescent display, especially a so-called "electronic paper" that has shape changeability by bending using an electrically conductive organic compound (citing paragraphs [0003] and [0005] of *Yoshida*). The Office Action alleges that it would be obvious to use the materials described in Yoshida in the OLED device of *Hente* and *Hild*. Applicant disagrees.

Yoshida is cited solely for its descript of an electronic paper display that has shape changeability. As such, *Yoshida* does not remedy the deficiencies of *Hente* and *Hild* as references that render obvious claim 1, from which claims 2 and 3 depend. The Examiner is respectfully requested to withdraw rejection of claims 2 and 3 based on *Hente* in view of *Hild* and further in view of *Yoshida*.

SDC EX. 1027 - 418/489

Regarding the rejection of claims 10-13, claim 10 also recites an organic light-emitting diode having an organic layer sequence, a radiation exit area and an encapsulation, and wherein the encapsulation forms a seal of the organic layer sequence against environmental influences. Claim 10, as amended, provides that the organic light-emitting diode is formed on a flexible carrier. As such claims 10-13 are not obvious from on *Hente* in view of *Hild* and further in view of *Yoshida* for the same reasons that claims 2 and 3 are not obvious in view of these references. Again *Yoshida* does not remedy the deficiencies of the combination of *Hente* in view of *Hild* as references that render obvious the claimed organic light-emitting diode having at least one touch-sensitive operating element, the device also having an organic layer sequence and an encapsulation which is formed on a flexible carrier. The Examiner is respectfully requested to withdraw rejection of claims 10-13 based on *Hente* in view of *Hild* and further in view of *Yoshida*.

CONCLUSION

In view of the above, each of the presently pending claims in this application is believed to be in immediate condition for allowance. Accordingly, the Examiner is respectfully requested to withdraw the outstanding rejection of the claims and to pass this application to issue. If, however, for any reason the Examiner does not believe that such action can be taken at this time, it is respectfully requested that the Examiner telephone Applicant's attorney at (908) 738-1770 in order to overcome any additional objections which the Examiner might have. All required fees are being paid via credit card through EFS-Web. However, please charge any additional fees not already paid via credit card, and credit any overpayments, to our Deposit Account No. 60-1866.

Dated: March 25, 2022

Respectfully submitted,

Electronic Signature: /Richard J. Botos/
Richard J. Botos
Registration No. 32,016
Botos Churchill IP Law LLP
430 Mountain Ave., Suite 401
New Providence, NJ 07974
(908) 738-1770
Attorney for Applicant

4889-3791-0806, v. 1

UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
16/790,198	02/13/2020	Ulrich KASTNER-JUNG	PICTIV 3.3F-001 CC [2]	1309

175540 7590 08/15/2022

Botos Churchill IP Law LLP
430 Mountain Avenue
Suite 401
New Providence, NJ 07974

EXAMINER
LE, TUNG X

ART UNIT	PAPER NUMBER
2844	

NOTIFICATION DATE	DELIVERY MODE
08/15/2022	ELECTRONIC

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Notice of the Office communication was sent electronically on above-indicated "Notification Date" to the following e-mail address(es):

lgagliano@bciplaw.com
pto@bciplaw.com
rbotos@bciplaw.com

Office Action Summary	Application No. 16/790,198	Applicant(s) KASTNER-JUNG et al.	
	Examiner TUNG X LE	Art Unit 2844	AIA (FITF) Status No

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 2 MONTHS FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

1)☑ Responsive to communication(s) filed on RCE 3/25/2022.

☐ A declaration(s)/affidavit(s) under **37 CFR 1.130(b)** was/were filed on _____.

2a)☐ This action is **FINAL.** 2b) ☐ This action is non-final.

3)☐ An election was made by the applicant in response to a restriction requirement set forth during the interview on _____; the restriction requirement and election have been incorporated into this action.

4)☑ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims*

5) ☑ Claim(s) 1-3 and 5-13 is/are pending in the application.

5a) Of the above claim(s) _____ is/are withdrawn from consideration.

6) ☐ Claim(s) _____ is/are allowed.

7) ☐ Claim(s) _____ is/are rejected.

8) ☑ Claim(s) 1-3 and 5-13 is/are objected to.

9) ☐ Claim(s) _____ are subject to restriction and/or election requirement

* If any claims have been determined allowable, you may be eligible to benefit from the **Patent Prosecution Highway** program at a participating intellectual property office for the corresponding application. For more information, please see http://www.uspto.gov/patents/init_events/pph/index.jsp or send an inquiry to **PPHfeedback@uspto.gov.**

Application Papers

10)☐ The specification is objected to by the Examiner.

11)☐ The drawing(s) filed on _____ is/are: a)☐ accepted or b)☐ objected to by the Examiner.

Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).

Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).

Priority under 35 U.S.C. § 119

12)☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).

Certified copies:

a)☐ All b)☐ Some** c)☐ None of the:

1.☐ Certified copies of the priority documents have been received.

2.☐ Certified copies of the priority documents have been received in Application No. _____.

3.☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

** See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

1) ☑ Notice of References Cited (PTO-892)

2) ☐ Information Disclosure Statement(s) (PTO/SB/08a and/or PTO/SB/08b) Paper No(s)/Mail Date _____.

3) ☐ Interview Summary (PTO-413) Paper No(s)/Mail Date _____.

4) ☐ Other: _____.

DETAILED ACTION

Notice of Pre-AIA or AIA Status

The present application is being examined under the pre-AIA first to invent provisions.

This Office Action is in response to the Applicant's request for continued examination (RCE) filed on March 25, 2022. In virtue of this filing:

- Claim 4 is cancelled; and thus,
- Claims **1-3** and **5-13** are now pending in the instant application.

Quayle Action

1. This application is in condition for allowance except for the following formal matters:

2. Claims 1-2, 5 and 10 are objected to because of the following informalities:

Claim 1, in line 3, --,-- should be inserted after "encapsulation"

Claim 1, in line 4, "and" should be deleted

Claim 2, in line 2, "can be rolled" should be changed to --rollable--

Claim 5, in line 1, "4" should be changed to --1--

Claim 10, in line 9, "can be rolled" should be changed to --rollable--

Appropriate correction is required.

3. Claims 3, 6-9 and 11-13 are also objected as being dependent upon objected claims 1-2 and 10, respectively.

4. Prosecution on the merits is closed in accordance with the practice under *Ex parte Quayle*, 25 USPQ 74, 453 O.G. 213, (Comm'r Pat. 1935).

A shortened statutory period for reply to this action is set to expire **TWO (2) MONTHS** from the mailing date of this letter. Extensions of time may be granted under 37 CFR 1.136 but

in no case can any extension carry the date for reply to this Office action beyond the maximum period of SIX MONTHS set by statute (35 U.S.C. 133).

Allowable Subject Matter

5. Claims 1-3 and 5-13 would be allowable if corrected to overcome the objection set forth above.

Conclusion

6. The prior art made of record and not relied upon is considered pertinent to applicant's disclosure.

Prior art Lang et al. – US 2009/0142556

Prior art Chen – US 2009/0021666

Prior art Wang et al. – US 2006/0141135

Prior art Urushido – US 2005/0110049

7. Any inquiry concerning this communication or earlier communications from the examiner should be directed to TUNG X LE whose telephone number is (571)272-6010. The examiner can normally be reached Monday to Friday from 10am to 6pm.

Examiner interviews are available via telephone, in-person, and video conferencing using a USPTO supplied web-based collaboration tool. To schedule an interview, applicant is encouraged to use the USPTO Automated Interview Request (AIR) at http://www.uspto.gov/interviewpractice.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Amy C Johnson can be reached on 571-272-2238. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of published or unpublished applications may be obtained from Patent Center. Unpublished application information in Patent Center is available to registered users. To file and manage patent submissions in Patent Center, visit: https://patentcenter.uspto.gov. Visit https://www.uspto.gov/patents/apply/patent-center for more information about Patent Center and https://www.uspto.gov/patents/docx for information about filing in DOCX format. For additional questions, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

/TUNG X LE/
Primary Examiner, Art Unit 2844
August 10, 2022

Notice of References Cited	Application/Control No. 16/790,198	Applicant(s)/Patent Under Reexamination KASTNER-JUNG et al.	
	Examiner TUNG X LE	Art Unit 2844	Page 1 of 1

U.S. PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date MM-YYYY	Name	CPC Classification	US Classification
*	A	US-20090142556-A1	06-2009	Lang; Charles D.	H01L51/0015	427/553
*	B	US-20090021666-A1	01-2009	Chen; Hung-Tse	G02F1/133305	349/73
*	C	US-20060141135-A1	06-2006	Wang; Jian	H01L51/0013	427/256
*	D	US-20050110049-A1	05-2005	Urushido, Tatsuhiro	H05K1/0281	257/202
	E					
	F					
	G					
	H					
	I					
	J					
	K					
	L					
	M					

FOREIGN PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date MM-YYYY	Country	Name	CPC Classification
	N					
	O					
	P					
	Q					
	R					
	S					
	T					

NON-PATENT DOCUMENTS

*		Include as applicable: Author, Title Date, Publisher, Edition or Volume, Pertinent Pages)
	U	
	V	
	W	
	X	

*A copy of this reference is not being furnished with this Office action. (See MPEP § 707.05(a).)
Dates in MM-YYYY format are publication dates. Classifications may be US or foreign.

Search Notes	Application/Control No.	Applicant(s)/Patent Under Reexamination
	16/790,198	KASTNER-JUNG et al.
	Examiner	Art Unit
	TUNG X LE	2844

CPC - Searched*		
Symbol	Date	Examiner
H01L: 51/0097, 5209, 5218, 5225, 5246, 5253	08/10/2022	TXL

CPC Combination Sets - Searched*		
Symbol	Date	Examiner

US Classification - Searched*			
Class	Subclass	Date	Examiner

* See search history printout included with this form or the SEARCH NOTES box below to determine the scope of the search.

Search Notes		
Search Notes	Date	Examiner
Updated PE2E Search (see search history printout)	08/10/2022	TXL
Inventors and Assignee Searches	08/10/2022	TXL
CPC Search	08/10/2022	TXL
Citations: Forward and Backward	08/10/2022	TXL

Interference Search			
US Class/CPC Symbol	US Subclass/CPC Group	Date	Examiner

Index of Claims	Application/Control No.	Applicant(s)/Patent Under Reexamination
	16/790,198	KASTNER-JUNG et al.
	Examiner	Art Unit
	TUNG X LE	2844

✓	Rejected	-	Cancelled	N	Non-Elected	A	Appeal
=	Allowed	÷	Restricted	I	Interference	O	Objected

CLAIMS

☐ Claims renumbered in the same order as presented by applicant ☐ CPA ☐ T.D. ☐ R.1.47

CLAIM		DATE								
Final	Original	08/10/2022								
	1	O								
	2	O								
	3	O								
	4	-								
	5	O								
	6	O								
	7	O								
	8	O								
	9	O								
	10	O								
	11	O								
	12	O								
	13	O								

PE2E SEARCH - Search History (Prior Art)

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	British Equivalents	Time Stamp
L1	1	"16790198"	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/09 01:10 PM
L2	7	("20030071259"|"6926572"|"7205714"|"20020003403"|"20040022058"|"20110187668"|"20110096504").PN.	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/09 06:40 PM
L3	1566	(OLED OR (organic near3 diode)) WITH layer WITH sequence	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/09 06:46 PM
L4	55	L3 AND (flexible WITH carrier)	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/09 06:46 PM
L5	46	L4 AND encapsulat$3	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/09 06:49 PM
L6	11	L5 AND (UV WITH radiat$3 WITH infrared)	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/09 06:49 PM
L7	5	L6 AND (touch$3 WITH sens$3)	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/09 06:50 PM
L8	39	("5734225" | "6236622" | "7280439" | "7317120" | "7317210" | "7733008" | "7922358" | "20010052752" | "20020125822" | "20020167270" | "20030064540" | "20030071804" | "20030121767" | "20030175553" | "20030222577" | "20030231495" | "20040113542" | "20050099824" | "20060049381" | "20070278937" | "20080219013" | "20080248191" | "20090039272" | "20100157585" | "20120258294").pn. OR ("9797567").urpn. AND (PGPB | USPT | USOC).dbnm.	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/09 06:55 PM
L9	33	("5734225" | "5895228" | "6236622" | "7205714" | "7280439" | "7317210" | "7560727" | "7733008" | "7922358" | "20010043046" | "20010052752" |	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/09 07:02 PM

		"20020125822" | "20020167270" | "20030064540" | "20030071804" | "20030121767" | "20030175553" | "20030222577" | "20030231495" | "20040113542" | "20050099824" | "20050231101" | "20060049381" | "20070114520" | "20070230211" | "20070278937" | "20080219013" | "20080248191" | "20090039272" | "20090072711" | "20100157585" | "20120258294").pn. OR ("10605422").urpn. AND (PGPB | USPT | USOC).dbnm.					
L10	23	("4356429" | "5645948" | "5693956" | "5770920" | "5796120" | "6150187" | "6198217" | "6558820" | "6690108" | "20010041268" | "20020057055" | "20020167025" | "20030087126").pn. OR ("7733008").urpn. AND (PGPB | USPT | USOC).dbnm.	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/09 07:05 PM
L11	9	("5445899" | "5814417").pn. OR ("6690108").urpn. AND (PGPB | USPT | USOC).dbnm.	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/09 07:05 PM
L12	25	("4287449" | "4602189" | "4613793" | "4758765" | "4963788").pn. OR ("5445899").urpn. AND (PGPB | USPT | USOC).dbnm.	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/09 07:06 PM
L13	61355	(OLED.u/c. OR (organic near3 light$3 near3 emitting near3 diode)) WITH layer	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/10 10:34 AM
L14	12860	L13 AND (organic adj1 layer) AND ((encapsulat$3 OR seal$3 OR insulat$3) adj1 layer)	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/10 10:35 AM

L15	87	L14 AND (radiat$3 WITH infrared WITH UV.u/c.)	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/10 10:37 AM
L16	35	L15 AND touch$3	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/10 10:37 AM
L17	25	L15 AND (touch$3 WITH sens$3)	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/10 10:37 AM
L18	62	L15 NOT L17	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/10 10:38 AM
L19	21	("6303238" | "6479612" | "6670645" | "7138551" | "7151342" | "7554112" | "7736926" | "20040062947" | "20040102577" | "20040127637" | "20050184287" | "20050205860" | "20060142520" | "20070059555" | "20070075626" | "20070218582" | "20080157659" | "20080160270" | "20080233493" | "20080286487" | "20090017268").pn. OR ("8040048").urpn. AND (PGPB | USPT | USOC).dbnm.	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/10 10:42 AM
L20	1379	("4950950" | "5128587" | "5203974" | "5231329" | "5294810" | "5457565" | "5540999" | "5601903" | "5703436" | "5707745" | "5756224" | "5757026" | "5757139" | "5811833" | "5834130" | "5834893" | "5844363" | "5861219" | "5874803" | "5917280" | "5932895" | "5953587" | "5981306" | "5986268" | "5986401" | "5998803" | "6013538" | "6013982" | "6030715" | "6045930" | "6046543" | "6048630" | "6091195" | "6097147" | "6111902" | "6125226").pn. OR ("6303238").urpn. AND (PGPB | USPT | USOC).dbnm.	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/10 10:43 AM
L21	5	("20090124062" | "20140072771" | "20150171354" | "20160081180" |	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/10 10:47 AM

		"20160299283").pn. OR ("10693088").urpn. AND (PGPB | USPT | USOC).dbnm.					
L22	2639	L13 AND ((flexible OR bend$4 OR roll$4) WITH carrier)	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/10 10:51 AM
L23	781	L22 AND (organic adj1 layer) AND ((encapsulat$3 OR seal$3 OR insulat$3) adj1 layer)	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/10 10:52 AM
L24	257	L23 AND (infrared OR UV.u/c.)	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/10 10:53 AM
L25	586	("3949410" | "4058418" | "4392451" | "4416288" | "4471003" | "4487162" | "4658153" | "4663828" | "4761335" | "4763275" | "4766670" | "4784720" | "4855017" | "5041973" | "5086785" | "5108819" | "5118400" | "5147519" | "5178957" | "5204144" | "5306917" | "5313094" | "5331966" | "5360987" | "5403700" | "5427096" | "5434751" | "5439575" | "5455178" | "5455430" | "5469845" | "5477088" | "5501893" | "5525815" | "5539935" | "5545291" | "5549108" | "5560974" | "5567975" | "5625471" | "5648148" | "5687737" | "5691245" | "5746207" | "5753529" | "5757081" | "5767578" | "5772905" | "5783856" | "5790151" | "5811790" | "5817242" | "5824186" | "5837546" | "5860974" | "5871443" | "5904545" | "5907189" | "5915180" | "5917534" | "5928001" | "5955781" | "5968839" | "5976683" | "5978972" | "5998291" | "6009632" | "6024702" | "6057212" | "6080608" | "6097984" | "6121110" | "6148127" | "6150602" | "6165391" | "6165885" | "6171730" | "6225149" | "6236883" | "6265326" | "6274508" | "6276775" | "6277712" | "6281038" | "6282960" | "6284418"	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/10 10:55 AM

		| "6291896" | "6301500" | "6309351" | "6316278" | "6316283" | "6317175" | "6322895" | "6322963" | "6334960" | "6344616" | "6360615" | "6380729" | "6403397" | "6403944" | "6413790" | "6414783" | "6417025" | "6420266" | "6433401" | "6451191" | "6459418" | "6468638" | "6479395" | "6504105" | "6517995" | "6518168" | "6527964" | "6555408" | "6566744" | "6567158" | "6580151" | "6586338" | "6590346" | "6606079" | "6606247" | "6608370" | "6613979" | "6623579" | "6639578" | "6655286" | "6657289" | "6661037" | "6665044" | "6666821" | "6667548" | "6683663" | "6693384" | "6706402" | "6720469" | "6723576" | "6730990" | "6731353" | "6743982" | "6762510" | "6780696" | "6784450" | "6787052" | "6805809" | "6814898" | "6816380" | "6826509" | "6836744" | "6844673" | "6848162" | "6850312" | "6856830" | "6863219" | "6864435" | "6864570" | "6872645" | "6878871" | "6881979" | "6885030" | "6887450" | "6900094" | "6917061" | "6936181" | "6949199" | "6949206" | "6950220" | "6984934" | "6989285" | "7029951" | "7033961" | "7054784" | "7067903" | "7081642" | "7116318" | "7132313" | "7148512" | "7158277" | "7169546" | "7169669" | "7170164" | "7186624" | "7190051" | "7195733" | "7223609" | "7223632" | "7252664" | "7253442" | "7255919" | "7265298" | "7291146" | "7291540" | "7293353" | "7337012" | "7374968" | "7425523" | "7487587" | "7491892" | "7509835" | "7521292" | "7525304" | "7526389" | "7552031"					

		| "7557367" | "7593086" | "7622367" | "7629691" | "7633761" | "7635755" | "7674882" | "7700402" | "7704684" | "7705280" | "7709961" | "7727199" | "7727575" | "7732012" | "7742795" | "7759167" | "7769472" | "7799699" | "7838964" | "7842780" | "7857781" | "7871661" | "7884540" | "7909971" | "7932123" | "7935056" | "7943491" | "7960246" | "7972875" | "7982296" | "8008575" | "8039847" | "8107248" | "8198621" | "8207473" | "8252191" | "8367035" | "8394706" | "8440546" | "20010003043" | "20010012918" | "20010021867" | "20020021445" | "20020026127" | "20020082515" | "20020094701" | "20020095087" | "20020110766" | "20020128700" | "20020151934" | "20030006527" | "20030017848" | "20030032892" | "20030082889" | "20030087476" | "20030097165" | "20030120271" | "20030138704" | "20030149456" | "20030171691" | "20030178316" | "20030222282" | "20030227116" | "20030236455" | "20040005723" | "20040006264" | "20040026684" | "20040061543" | "20040079464" | "20040081384" | "20040085469" | "20040092806" | "20040095658" | "20040106334" | "20040112964" | "20040135094" | "20040136866" |					

		"20040138558" | "20040146560" | "20040149921" | "20040155290" | "20040171969" | "20040178390" | "20040178466" | "20040192062" | "20040192082" | "20040200734" | "20040206448" | "20040211458" | "20040211459" | "20040229830" | "20040243204" | "20040250950" | "20040252559" | "20050020094" | "20050021103" | "20050037511" | "20050038498" | "20050054939" | "20050082526" | "20050107716" | "20050113744" | "20050115308" | "20050124712" | "20050133954" | "20050136501" | "20050171524" | "20050177335" | "20050203366" | "20050214962" | "20050227389" | "20050233546" | "20050238967" | "20050255686" | "20050260706" | "20050261561" | "20060038182" | "20060049485" | "20060056161" | "20060068576" | "20060076561" | "20060084012" | "20060084394" | "20060085976" | "20060102525" | "20060106321" | "20060119853" | "20060127817" | "20060129056" | "20060132025" | "20060134893" | "20060154398" | "20060159837" | "20060169989" | "20060173364" |				

		"20060177479" | "20060178655" | "20060244105" | "20060255341" | "20060273279" | "20060279191" | "20060286488" | "20060286785" | "20070009968" | "20070027514" | "20070031607" | "20070032089" | "20070043416" | "20070058254" | "20070073130" | "20070104944" | "20070108389" | "20070122819" | "20070187862" | "20070212730" | "20070213616" | "20070227586" | "20070233208" | "20070254468" | "20080000871" | "20080008626" | "20080038236" | "20080041617" | "20080046080" | "20080054875" | "20080055581" | "20080077225" | "20080085272" | "20080090322" | "20080102096" | "20080108171" | "20080108942" | "20080140152" | "20080152281" | "20080157234" | "20080157235" | "20080183076" | "20080188912" | "20080193749" | "20080203268" | "20080203431" | "20080208268" | "20080212102" | "20080239755" | "20080257586" | "20080280360" | "20080287167" | "20080288037" | "20080293919" | "20080313552" | "20090001550" | "20090004737" | "20090015560" |				

		"20090028910" | "20090054742" | "20090088750" | "20090105605" | "20090107704" | "20090149930" | "20090183986" | "20090184254" | "20090198293" | "20090199960" | "20090202614" | "20090204168" | "20090208555" | "20090215385" | "20090221896" | "20090232963" | "20090234026" | "20090247909" | "20090273909" | "20090289246" | "20090294803" | "20090308455" | "20090317639" | "20100002402" | "20100028451" | "20100046902" | "20100052112" | "20100055438" | "20100059863" | "20100063404" | "20100065784" | "20100068740" | "20100070068" | "20100072577" | "20100073669" | "20100087782" | "20100096763" | "20100116526" | "20100117660" | "20100120116" | "20100121420" | "20100152619" | "20100176705" | "20100178304" | "20100178722" | "20100188799" | "20100191328" | "20100196447" | "20100200752" | "20100203226" | "20100252840" | "20100271191" | "20100279112" | "20100283069" | "20100289124" | "20100298895" | "20100317132" | "20100324455" |				

		"20100327387" | "20110011179" | "20110018838" | "20110034912" | "20110054583" | "20110068672" | "20110114894" | "20110147715" | "20110170225" | "20110171813" | "20110177332" | "20110187798" | "20110215931" | "20110218756" | "20110218757" | "20110220890" | "20110230747" | "20110266561" | "20110272181" | "20110277813" | "20110316120" | "20120051005" | "20120052268" | "20120065937" | "20120083099" | "20120092178" | "20120105528" | "20120157804" | "20120157986" | "20120157987" | "20120157988" | "20120157989" | "20120158101" | "20120165759" | "20120251824" | "20120256308" | "20120261551" | "20120279762" | "20120320581" | "20120327608" | "20130036928" | "20130041235" | "20130100618").pn. OR ("8886334").urpn. AND (PGPB | USPT | USOC).dbnm.					
L27	27	(pictiva near3 displays near3 international) OR (osram near2 OLED.u/c.)	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/10 10:59 AM
L28	298	((ulrich near2 jung) OR (markus near2 klein) OR (stan near2 maes) OR (romana near2 sigl) OR (annette near2 haid) OR (stephan near2 lintner) OR (julian	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/10 11:07 AM

		near2 herget) OR (gregor near2 matjan)).in.					
L29	27726	(H01L51/0097 OR H01L51/5209 OR H01L51/5218 OR H01L51/5225 OR H01L51/5246 OR H01L51/5253).CPC.	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/10 11:08 AM
L30	28029	L27 OR L28 OR L29	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/10 11:09 AM
L31	2068	L30 AND ((flexible OR bend$4 OR roll$4) WITH carrier)	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/10 11:09 AM
L32	560	L31 AND (organic adj1 layer) AND ((encapsulat$3 OR seal$3 OR insulat$3) adj1 layer)	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/10 11:11 AM
L33	455	L32 NOT L24	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/10 11:11 AM
L34	13	("20050110049" | "20090021666" | "20120146886" | "20130169515" | "20140048314").pn. OR ("9882152").urpn. AND (PGPB | USPT | USOC).dbnm.	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/10 11:14 AM
L35	36	("8377762" | "8698189" | "8933451" | "9287342" | "9543370" | "9659966" | "9698162" | "9882152" | "10020462" | "20060169989" | "20080079889" | "20110227846" | "20120162099" | "20130148312" | "20140097408" | "20140217373" | "20140217397" | "20140232956" | "20140353670" | "20150102298" | "20150116959" | "20150179728" | "20160014883" | "20160195901" | "20160204185" | "20160218305" | "20160239133" | "20160336523" | "20170062532" | "20170092230" |	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/10 11:17 AM

		"20170147117" | "20170237025" | "20170329368" | "20180019418").pn. OR ("10211276").urpn. AND (PGPB | USPT | USOC).dbnm.					

PE2E SEARCH - Search History (Interference)

There are no Interference searches to show.

PTO/SB/06 (09-11)
Approved for use through 1/31/2014. OMB 0651-0032
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

PATENT APPLICATION FEE DETERMINATION RECORD Substitute for Form PTO-875	Application or Docket Number 16/790,198	Filing Date 02/13/2020	☐ To be Mailed

ENTITY: ☑ LARGE ☐ SMALL ☐ MICRO

APPLICATION AS FILED - PART I

FOR	(Column 1) NUMBER FILED	(Column 2) NUMBER EXTRA		RATE ($)	FEE ($)
☐ BASIC FEE (37 CFR 1.16(a), (b), or (c))	N/A	N/A		N/A	
☐ SEARCH FEE (37 CFR 1.16(k), (i), or (m))	N/A	N/A		N/A	
☐ EXAMINATION FEE (37 CFR 1.16(o), (p), or (q))	N/A	N/A		N/A	
TOTAL CLAIMS (37 CFR 1.16(i))	minus 20 =	*		x $100 =	
INDEPENDENT CLAIMS (37 CFR 1.16(h))	minus 3 =	*		x $460 =	
☐ APPLICATION SIZE FEE (37 CFR 1.16(s))	If the specification and drawings exceed 100 sheets of paper, the application size fee due is $310 ($155 for small entity) for each additional 50 sheets or fraction thereof. See 35 U.S.C. 41(a)(1)(G) and 37 CFR 1.16(s).				
☐ MULTIPLE DEPENDENT CLAIM PRESENT (37 CFR 1.16(j))					
* If the difference in column 1 is less than zero, enter "0" in column 2.				TOTAL	

APPLICATION AS AMENDED - PART II

		(Column 1)		(Column 2)	(Column 3)			
AMENDMENT	08/23/2022	CLAIMS REMAINING AFTER AMENDMENT		HIGHEST NUMBER PREVIOUSLY PAID FOR	PRESENT EXTRA		RATE ($)	ADDITIONAL FEE ($)
	Total (37 CFR 1.16(i))	* 12	Minus	** 20	= 0		x $100 =	0
	Independent (37 CFR 1.16(h))	* 2	Minus	*** 3	= 0		x $480 =	0
	☐ Application Size Fee (37 CFR 1.16(s))							
	☐ FIRST PRESENTATION OF MULTIPLE DEPENDENT CLAIM (37 CFR 1.16(j))							
							TOTAL ADD'L FEE	0

		(Column 1)		(Column 2)	(Column 3)			
AMENDMENT		CLAIMS REMAINING AFTER AMENDMENT		HIGHEST NUMBER PREVIOUSLY PAID FOR	PRESENT EXTRA		RATE ($)	ADDITIONAL FEE ($)
	Total (37 CFR 1.16(i))	*	Minus	**	=		x $0 =	
	Independent (37 CFR 1.16(h))	*	Minus	***	=		x $0 =	
	☐ Application Size Fee (37 CFR 1.16(s))							
	☐ FIRST PRESENTATION OF MULTIPLE DEPENDENT CLAIM (37 CFR 1.16(j))							
							TOTAL ADD'L FEE	

* If the entry in column 1 is less than the entry in column 2, write "0" in column 3.	SLIE
** If the "Highest Number Previously Paid For" IN THIS SPACE is less than 20, enter "20".	/APRIL L. WALKER/
*** If the "Highest Number Previously Paid For" IN THIS SPACE is less than 3, enter "3".	
The "Highest Number Previously Paid For" (Total or Independent) is the highest number found in the appropriate box in column 1.	

This collection of information is required by 37 CFR 1.16. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 12 minutes to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.**

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

Electronic Acknowledgement Receipt

EFS ID:	46469410
Application Number:	16790198
International Application Number:	
Confirmation Number:	1309
Title of Invention:	Organic-Light-Emitting Diode
First Named Inventor/Applicant Name:	Ulrich KASTNER-JUNG
Customer Number:	175540
Filer:	Richard J. Botos/Elizabeth Gagliano
Filer Authorized By:	Richard J. Botos
Attorney Docket Number:	PICTIV 3.3F-001 CC [2]
Receipt Date:	23-AUG-2022
Filing Date:	13-FEB-2020
Time Stamp:	16:21:48
Application Type:	Utility under 35 USC 111(a)

Payment information:

Submitted with Payment	no

File Listing:

Document Number	Document Description	File Name	File Size(Bytes)/ Message Digest	Multi Part /.zip	Pages (if appl.)
1	Miscellaneous Incoming Letter	Amendment_Transmittal.pdf	1957885 551e733db37c32a66691b4e212294dfdce371797	no	1

Warnings:

Information:					
2	Response after Ex Parte Quayle Action	Amendment_Under_Ex_parte_Quayle.pdf	106250 c7915c6a07b531a315239819ce5cb2558da4e334	no	5
Warnings:					
Information:					
		Total Files Size (in bytes):	2064135		

This Acknowledgement Receipt evidences receipt on the noted date by the USPTO of the indicated documents, characterized by the applicant, and including page counts, where applicable. It serves as evidence of receipt similar to a Post Card, as described in MPEP 503.

New Applications Under 35 U.S.C. 111

If a new application is being filed and the application includes the necessary components for a filing date (see 37 CFR 1.53(b)-(d) and MPEP 506), a Filing Receipt (37 CFR 1.54) will be issued in due course and the date shown on this Acknowledgement Receipt will establish the filing date of the application.

National Stage of an International Application under 35 U.S.C. 371

If a timely submission to enter the national stage of an international application is compliant with the conditions of 35 U.S.C. 371 and other applicable requirements a Form PCT/DO/EO/903 indicating acceptance of the application as a national stage submission under 35 U.S.C. 371 will be issued in addition to the Filing Receipt, in due course.

New International Application Filed with the USPTO as a Receiving Office

If a new international application is being filed and the international application includes the necessary components for an international filing date (see PCT Article 11 and MPEP 1810), a Notification of the International Application Number and of the International Filing Date (Form PCT/RO/105) will be issued in due course, subject to prescriptions concerning national security, and the date shown on this Acknowledgement Receipt will establish the international filing date of the application.

AMENDMENT TRANSMITTAL LETTER

Docket No.
PICTIV 3.3F-001 CC [2]

Application No.	Filing Date	Examiner	Art Unit
16/790,198 / Conf. #1309	February 13, 2020	Tung X. Le	2844

Applicant(s): PICTIVA DISPLAYS INTERNATIONAL LIMITED

Invention: ORGANIC-LIGHT-EMITTING DIODE

TO THE COMMISSIONER FOR PATENTS

Transmitted herewith is an amendment in the above-identified application.

The fee has been calculated and is transmitted as shown below.

CLAIMS AS AMENDED

	Claims Remaining After Amendment	Highest Number Previously Paid		Number Extra Claims Present	Rate	
Total Claims	12	- 20	=	0	$ 100.00	$ 0.00
Independent Claims	2	- 3	=	0	$ 480.00	$ 0.00
Multiple Dependent Claims (check if applicable) ☐						
Other fee (please specify):						
TOTAL ADDITIONAL FEE FOR THIS AMENDMENT:						$ 0.00

☑ Large Entity ☐ Small Entity

☑ No additional fee is required for this amendment.

☐ Please charge Deposit Account No. _____ in the amount of $ _____ .

☐ A check in the amount of $ _____ to cover the filing fee is enclosed.

☐ Payment by credit card. Form PTO-2038 is attached.

☑ The Director is hereby authorized to charge and credit Deposit Account No. 60-1866 as described below. A duplicate copy of this sheet is enclosed.

☑ Credit any overpayment.

☑ Charge any additional filing or application processing fees required under 37 C.F.R. § 1.16 and 1.17.

/Richard J. Botos/ Dated: 8/23/2022

Richard J. Botos
Attorney/Agent Reg. No.: 32,016
BOTOS CHURCHILL IP LAW LLP
430 Mountain Avenue, Suite 401
New Providence, New Jersey 07974

I hereby certify that this paper (along with any paper referred to as being attached or enclosed) is being transmitted via the Office electronic filing system in accordance with 37 CFR § 1.6(a)(4).

Dated: 8/23/2022 Electronic Signature for Richard J. Botos /Richard J. Botos/

I hereby certify that this paper (along with any paper referred to as being attached or enclosed) is being transmitted via the Office electronic filing system in accordance with 37 CFR § 1.6(a)(4).

Dated: August 23, 2022
Electronic Signature for Richard J. Botos: /Richard J. Botos/

Docket No.: PICTIV 3.3F-001 CC [2]
(PATENT)

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Patent Application of:
Ulrich Kastner-Jung et al.

Application No.: 16/790,198 Confirmation No.: 1309

Filing Date: February 13, 2020 Art Unit: 2844

Title: ORGANIC-LIGHT-EMITTING DIODE Examiner: Tung X. Le

Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

AMENDMENT IN RESPONSE TO EX PARTE QUAYLE ACTION

Dear Sir:

In response to the Office Action dated August 15, 2022, please amend the above-identified U.S. patent application as follows:

IN THE CLAIMS

1. (Currently Amended) A device comprising:

an organic light-emitting diode comprising an organic layer sequence, a radiation exit area and an encapsulation, wherein the organic layer sequence and the encapsulation are disposed on a flexible carrier, ~~and~~ wherein the organic layer sequence comprises at least one radiation-emitting region which generates electromagnetic radiation in a spectral range from infrared radiation to UV radiation during operation, and wherein the encapsulation forms a seal of the organic layer sequence against environmental influences; and

at least one touch-sensitive operating element, wherein the at least one touch-sensitive operating element comprises at least one touch sensor, and wherein the device is flexible.

2. (Currently Amended) The device according to claim 1, wherein the device [[in]]is bendable or ~~can be rolled~~rollable.

3. (Original) The device according to claim 2, wherein the device maintains its form after bending.

4. (Canceled).

5. (Currently Amended) The device according to claim [[4]]1, wherein the flexible carrier comprises a film or a plastic film or a laminate.

6. (Original) The device according to claim 1, wherein the encapsulation is flexible.

7. (Original) The device according to claim 1, wherein the touch-sensitive operating element is arranged at a light exit area of the device.

8. (Original) The device according to claim 1, wherein the at least one touch sensor is integrated into the organic light-emitting diode.

9. (Original) The device according to claim 1, wherein the device is drivable by means of a gesture control.

10. (Currently Amended) A device comprising:

an organic light-emitting diode comprising an organic layer sequence, a radiation exit area and an encapsulation, wherein the organic layer sequence comprises at least one radiation-emitting region which generates electromagnetic radiation in a spectral range from infrared radiation to UV radiation during operation, and wherein the encapsulation forms a seal of the organic layer sequence against environmental influences,

at least one touch-sensitive operating element, wherein the at least one touch-sensitive operating element comprises at least one touch sensor, and wherein

the device is formed on a flexible carrier whereby the device is bendable or ~~can be rolled~~rollable.

11. (Original) The device according to claim 10, wherein the touch-sensitive operating element is arranged at a light exit area of the device.

12. (Original) The device according to claim 10, wherein the at least one touch sensor is integrated into the organic light-emitting diode.

13. (Original) The device according to claim 10, wherein the device is drivable by means of a gesture control.

SDC EX. 1027 - 446/489

REMARKS

This communication is responsive to the Office Action dated August 15, 2022 (hereinafter the "Office Action"). In this communication, claims 1, 2, 5, and 10 have been amended and not claims have been added. Thus, claims 1-3 and 5-13 are presented for consideration in view of the following remarks. The amendments are made at the suggestion of the Office in the Ex Parte Quayle action mailed August 15, 2022. Applicant respectfully submits that no new matter has been added by the foregoing amendments. The rejections will be addressed in view of the claims as presented herein.

Quayle Action

The Quayle Action mailed August 15, 2022 identified typographical errors in claims 1-2, 5 and 10 to which the Office objects. The Office objected to those claims based on the identified informalties. Claims 3, 6-9, and 11-13 were objected to because they depended from one of the claims that contained the informalities identified in the Action.

Applicant has amended claims 1-2, 5 and 10 in the manner suggested in the Quayle Action (page 2). The claims having been amended, applicant submits that the basis for the claim objections has been removed.

As prosecution on the merits is closed, applicant submits no further remarks at this time.

CONCLUSION

In view of the above, each of the presently pending claims in this application is believed to be in immediate condition for allowance. Accordingly, the Examiner is respectfully requested to

withdraw the outstanding rejection of the claims and to pass this application to issue. If, however, for any reason the Examiner does not believe that such action can be taken at this time, it is respectfully requested that the Examiner telephone Applicant's attorney at (908) 738-1770 in order to overcome any additional objections which the Examiner might have. All required fees are being paid via credit card through EFS-Web. However, please charge any additional fees not already paid via credit card, and credit any overpayments to our Deposit Account No. 601866.

Dated: August 23, 2022

Respectfully submitted,

Electronic Signature: /Richard J. Botos/
Richard J. Botos
Registration No. 32,016
Botos Churchill IP Law LLP
430 Mountain Ave., Suite 401
New Providence, NJ 07974
(908) 738-1770
Attorney for Applicant

4865-6355-7934, v. 1

UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

NOTICE OF ALLOWANCE AND FEE(S) DUE

175540 7590 10/21/2022

Botos Churchill IP Law LLP
430 Mountain Avenue
Suite 401
New Providence, NJ 07974

EXAMINER
LE, TUNG X

ART UNIT	PAPER NUMBER
2844	

DATE MAILED: 10/21/2022

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
16/790,198	02/13/2020	Ulrich KASTNER-JUNG	PICTIV 3.3F-001 CC [2]	1309

TITLE OF INVENTION: Organic-Light-Emitting Diode

APPLN. TYPE	ENTITY STATUS	ISSUE FEE DUE	PUBLICATION FEE DUE	PREV. PAID ISSUE FEE	TOTAL FEE(S) DUE	DATE DUE
nonprovisional	UNDISCOUNTED	$1200	$0.00	$0.00	$1200	01/23/2023

THE APPLICATION IDENTIFIED ABOVE HAS BEEN EXAMINED AND IS ALLOWED FOR ISSUANCE AS A PATENT. PROSECUTION ON THE MERITS IS CLOSED. THIS NOTICE OF ALLOWANCE IS NOT A GRANT OF PATENT RIGHTS. THIS APPLICATION IS SUBJECT TO WITHDRAWAL FROM ISSUE AT THE INITIATIVE OF THE OFFICE OR UPON PETITION BY THE APPLICANT. SEE 37 CFR 1.313 AND MPEP 1308.

THE ISSUE FEE AND PUBLICATION FEE (IF REQUIRED) MUST BE PAID WITHIN THREE MONTHS FROM THE MAILING DATE OF THIS NOTICE OR THIS APPLICATION SHALL BE REGARDED AS ABANDONED. THIS STATUTORY PERIOD CANNOT BE EXTENDED. SEE 35 U.S.C. 151. THE ISSUE FEE DUE INDICATED ABOVE DOES NOT REFLECT A CREDIT FOR ANY PREVIOUSLY PAID ISSUE FEE IN THIS APPLICATION. IF AN ISSUE FEE HAS PREVIOUSLY BEEN PAID IN THIS APPLICATION (AS SHOWN ABOVE), THE RETURN OF PART B OF THIS FORM WILL BE CONSIDERED A REQUEST TO REAPPLY THE PREVIOUSLY PAID ISSUE FEE TOWARD THE ISSUE FEE NOW DUE.

HOW TO REPLY TO THIS NOTICE:

I. Review the ENTITY STATUS shown above. If the ENTITY STATUS is shown as SMALL or MICRO, verify whether entitlement to that entity status still applies.

If the ENTITY STATUS is the same as shown above, pay the TOTAL FEE(S) DUE shown above.

If the ENTITY STATUS is changed from that shown above, on PART B - FEE(S) TRANSMITTAL, complete section number 5 titled "Change in Entity Status (from status indicated above)".

For purposes of this notice, small entity fees are 1/2 the amount of undiscounted fees, and micro entity fees are 1/2 the amount of small entity fees.

II. PART B - FEE(S) TRANSMITTAL, or its equivalent, must be completed and returned to the United States Patent and Trademark Office (USPTO) with your ISSUE FEE and PUBLICATION FEE (if required). If you are charging the fee(s) to your deposit account, section "4b" of Part B - Fee(s) Transmittal should be completed. If an equivalent of Part B is filed, a request to reapply a previously paid issue fee must be clearly made, and delays in processing may occur due to the difficulty in recognizing the paper as an equivalent of Part B.

III. All communications regarding this application must give the application number. Please direct all communications prior to issuance to Mail Stop ISSUE FEE unless advised to the contrary.

IMPORTANT REMINDER: Maintenance fees are due in utility patents issuing on applications filed on or after Dec. 12, 1980. It is patentee's responsibility to ensure timely payment of maintenance fees when due. More information is available at www.uspto.gov/PatentMaintenanceFees.

PART B - FEE(S) TRANSMITTAL

Complete and send this form, together with applicable fee(s), by mail or fax, or via EFS-Web.

By mail, send to: Mail Stop ISSUE FEE
Commissioner for Patents
P.O. Box 1450
Alexandria, Virginia 22313-1450

By fax, send to: (571)-273-2885

INSTRUCTIONS: This form should be used for transmitting the ISSUE FEE and PUBLICATION FEE (if required). Blocks 1 through 5 should be completed where appropriate. All further correspondence including the Patent, advance orders and notification of maintenance fees will be mailed to the current correspondence address as indicated unless corrected below or directed otherwise in Block 1, by (a) specifying a new correspondence address; and/or (b) indicating a separate "FEE ADDRESS" for maintenance fee notifications.

CURRENT CORRESPONDENCE ADDRESS (Note: Use Block 1 for any change of address)

175540 7590 10/21/2022

Botos Churchill IP Law LLP
430 Mountain Avenue
Suite 401
New Providence, NJ 07974

Note: A certificate of mailing can only be used for domestic mailings of the Fee(s) Transmittal. This certificate cannot be used for any other accompanying papers. Each additional paper, such as an assignment or formal drawing, must have its own certificate of mailing or transmission.

Certificate of Mailing or Transmission

I hereby certify that this Fee(s) Transmittal is being deposited with the United States Postal Service with sufficient postage for first class mail in an envelope addressed to the Mail Stop ISSUE FEE address above, or being transmitted to the USPTO via EFS-Web or by facsimile to (571) 273-2885, on the date below.

(Typed or printed name)
(Signature)
(Date)

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
16/790,198	02/13/2020	Ulrich KASTNER-JUNG	PICTIV 3.3F-001 CC [2]	1309

TITLE OF INVENTION: Organic-Light-Emitting Diode

APPLN. TYPE	ENTITY STATUS	ISSUE FEE DUE	PUBLICATION FEE DUE	PREV. PAID ISSUE FEE	TOTAL FEE(S) DUE	DATE DUE
nonprovisional	UNDISCOUNTED	$1200	$0.00	$0.00	$1200	01/23/2023

EXAMINER	ART UNIT	CLASS-SUBCLASS
LE, TUNG X	2844	315-360000

1. Change of correspondence address or indication of "Fee Address" (37 CFR 1.363).

❑ Change of correspondence address (or Change of Correspondence Address form PTO/AIA/122 or PTO/SB/122) attached.

❑ "Fee Address" indication (or "Fee Address" Indication form PTO/AIA/47 or PTO/SB/47; Rev 03-02 or more recent) attached. **Use of a Customer Number is required.**

2. For printing on the patent front page, list
(1) The names of up to 3 registered patent attorneys or agents OR, alternatively,
(2) The name of a single firm (having as a member a registered attorney or agent) and the names of up to 2 registered patent attorneys or agents. If no name is listed, no name will be printed.

1 _____
2 _____
3 _____

3. ASSIGNEE NAME AND RESIDENCE DATA TO BE PRINTED ON THE PATENT (print or type)

PLEASE NOTE: Unless an assignee is identified below, no assignee data will appear on the patent. If an assignee is identified below, the document must have been previously recorded, or filed for recordation, as set forth in 37 CFR 3.11 and 37 CFR 3.81(a). Completion of this form is NOT a substitute for filing an assignment.

(A) NAME OF ASSIGNEE (B) RESIDENCE: (CITY and STATE OR COUNTRY)

Please check the appropriate assignee category or categories (will not be printed on the patent) : ❑ Individual ❑ Corporation or other private group entity ❑ Government

4a. Fees submitted: ❑ Issue Fee ❑ Publication Fee (if required) ❑ Advance Order - # of Copies _____

4b. Method of Payment: *(Please first reapply any previously paid fee shown above)*

❑ Electronic Payment via EFS-Web ❑ Enclosed check ❑ Non-electronic payment by credit card (Attach form PTO-2038)

❑ The Director is hereby authorized to charge the required fee(s), any deficiency, or credit any overpayment to Deposit Account No. _____

5. **Change in Entity Status** (from status indicated above)

❑ Applicant certifying micro entity status. See 37 CFR 1.29

❑ Applicant asserting small entity status. See 37 CFR 1.27

❑ Applicant changing to regular undiscounted fee status.

NOTE: Absent a valid certification of Micro Entity Status (see forms PTO/SB/15A and 15B), issue fee payment in the micro entity amount will not be accepted at the risk of application abandonment.
NOTE: If the application was previously under micro entity status, checking this box will be taken to be a notification of loss of entitlement to micro entity status.
NOTE: Checking this box will be taken to be a notification of loss of entitlement to small or micro entity status, as applicable.

NOTE: This form must be signed in accordance with 37 CFR 1.31 and 1.33. See 37 CFR 1.4 for signature requirements and certifications.

Authorized Signature _____ Date _____

Typed or printed name _____ Registration No. _____

SDC EX. 1027 - 450/489

UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
16/790,198	02/13/2020	Ulrich KASTNER-JUNG	PICTIV 3.3F-001 CC [2]	1309

175540 7590 10/21/2022

Botos Churchill IP Law LLP
430 Mountain Avenue
Suite 401
New Providence, NJ 07974

EXAMINER	
LE, TUNG X	
ART UNIT	**PAPER NUMBER**
2844	

DATE MAILED: 10/21/2022

Determination of Patent Term Adjustment under 35 U.S.C. 154 (b)
(Applications filed on or after May 29, 2000)

The Office has discontinued providing a Patent Term Adjustment (PTA) calculation with the Notice of Allowance.

Section 1(h)(2) of the AIA Technical Corrections Act amended 35 U.S.C. 154(b)(3)(B)(i) to eliminate the requirement that the Office provide a patent term adjustment determination with the notice of allowance. See Revisions to Patent Term Adjustment, 78 Fed. Reg. 19416, 19417 (Apr. 1, 2013). Therefore, the Office is no longer providing an initial patent term adjustment determination with the notice of allowance. The Office will continue to provide a patent term adjustment determination with the Issue Notification Letter that is mailed to applicant approximately three weeks prior to the issue date of the patent, and will include the patent term adjustment on the patent. Any request for reconsideration of the patent term adjustment determination (or reinstatement of patent term adjustment) should follow the process outlined in 37 CFR 1.705.

Any questions regarding the Patent Term Extension or Adjustment determination should be directed to the Office of Patent Legal Administration at (571)-272-7702. Questions relating to issue and publication fee payments should be directed to the Customer Service Center of the Office of Patent Publication at 1-(888)-786-0101 or (571)-272-4200.

OMB Clearance and PRA Burden Statement for PTOL-85 Part B

The Paperwork Reduction Act (PRA) of 1995 requires Federal agencies to obtain Office of Management and Budget approval before requesting most types of information from the public. When OMB approves an agency request to collect information from the public, OMB (i) provides a valid OMB Control Number and expiration date for the agency to display on the instrument that will be used to collect the information and (ii) requires the agency to inform the public about the OMB Control Number's legal significance in accordance with 5 CFR 1320.5(b).

The information collected by PTOL-85 Part B is required by 37 CFR 1.311. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 30 minutes to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, Virginia 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, Virginia 22313-1450. Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Privacy Act Statement

The Privacy Act of 1974 (P.L. 93-579) requires that you be given certain information in connection with your submission of the attached form related to a patent application or patent. Accordingly, pursuant to the requirements of the Act, please be advised that: (1) the general authority for the collection of this information is 35 U.S.C. 2(b)(2); (2) furnishing of the information solicited is voluntary; and (3) the principal purpose for which the information is used by the U.S. Patent and Trademark Office is to process and/or examine your submission related to a patent application or patent. If you do not furnish the requested information, the U.S. Patent and Trademark Office may not be able to process and/or examine your submission, which may result in termination of proceedings or abandonment of the application or expiration of the patent.

The information provided by you in this form will be subject to the following routine uses:

1. The information on this form will be treated confidentially to the extent allowed under the Freedom of Information Act (5 U.S.C. 552) and the Privacy Act (5 U.S.C 552a). Records from this system of records may be disclosed to the Department of Justice to determine whether disclosure of these records is required by the Freedom of Information Act.
2. A record from this system of records may be disclosed, as a routine use, in the course of presenting evidence to a court, magistrate, or administrative tribunal, including disclosures to opposing counsel in the course of settlement negotiations.
3. A record in this system of records may be disclosed, as a routine use, to a Member of Congress submitting a request involving an individual, to whom the record pertains, when the individual has requested assistance from the Member with respect to the subject matter of the record.
4. A record in this system of records may be disclosed, as a routine use, to a contractor of the Agency having need for the information in order to perform a contract. Recipients of information shall be required to comply with the requirements of the Privacy Act of 1974, as amended, pursuant to 5 U.S.C. 552a(m).
5. A record related to an International Application filed under the Patent Cooperation Treaty in this system of records may be disclosed, as a routine use, to the International Bureau of the World Intellectual Property Organization, pursuant to the Patent Cooperation Treaty.
6. A record in this system of records may be disclosed, as a routine use, to another federal agency for purposes of National Security review (35 U.S.C. 181) and for review pursuant to the Atomic Energy Act (42 U.S.C. 218(c)).
7. A record from this system of records may be disclosed, as a routine use, to the Administrator, General Services, or his/her designee, during an inspection of records conducted by GSA as part of that agency's responsibility to recommend improvements in records management practices and programs, under authority of 44 U.S.C. 2904 and 2906. Such disclosure shall be made in accordance with the GSA regulations governing inspection of records for this purpose, and any other relevant (i.e., GSA or Commerce) directive. Such disclosure shall not be used to make determinations about individuals.
8. A record from this system of records may be disclosed, as a routine use, to the public after either publication of the application pursuant to 35 U.S.C. 122(b) or issuance of a patent pursuant to 35 U.S.C. 151. Further, a record may be disclosed, subject to the limitations of 37 CFR 1.14, as a routine use, to the public if the record was filed in an application which became abandoned or in which the proceedings were terminated and which application is referenced by either a published application, an application open to public inspection or an issued patent.
9. A record from this system of records may be disclosed, as a routine use, to a Federal, State, or local law enforcement agency, if the USPTO becomes aware of a violation or potential violation of law or regulation.

Notice of Allowability	Application No. 16/790,198	Applicant(s) KASTNER-JUNG et al.	
	Examiner TUNG X LE	Art Unit 2844	AIA (FITF) Status No

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address--

All claims being allowable, PROSECUTION ON THE MERITS IS (OR REMAINS) CLOSED in this application. If not included herewith (or previously mailed), a Notice of Allowance (PTOL-85) or other appropriate communication will be mailed in due course. **THIS NOTICE OF ALLOWABILITY IS NOT A GRANT OF PATENT RIGHTS.** This application is subject to withdrawal from issue at the initiative of the Office or upon petition by the applicant. See 37 CFR 1.313 and MPEP 1308.

1. ☑ This communication is responsive to 8/23/2022.
   ☐ A declaration(s)/affidavit(s) under **37 CFR 1.130(b)** was/were filed on _____.

2. ☐ An election was made by the applicant in response to a restriction requirement set forth during the interview on _____; the restriction requirement and election have been incorporated into this action.

3. ☑ The allowed claim(s) is/are 1-3 and 5-13 . As a result of the allowed claim(s), you may be eligible to benefit from the **Patent Prosecution Highway** program at a participating intellectual property office for the corresponding application. For more information , please see **http://www.uspto.gov/patents/init_events/pph/index.jsp** or send an inquiry to **PPHfeedback@uspto.gov.**

4. ☑ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).

   Certified copies:

   a) ☑ All b) ☐ Some* c) ☐ None of the:

   1. ☑ Certified copies of the priority documents have been received.
   2. ☐ Certified copies of the priority documents have been received in Application No. _____ .
   3. ☐ Copies of the certified copies of the priority documents have been received in this national stage application from the International Bureau (PCT Rule 17.2(a)).

   * Certified copies not received: _____ .

Applicant has THREE MONTHS FROM THE "MAILING DATE" of this communication to file a reply complying with the requirements noted below. Failure to timely comply will result in ABANDONMENT of this application.
THIS THREE-MONTH PERIOD IS NOT EXTENDABLE.

5. ☐ CORRECTED DRAWINGS (as "replacement sheets") must be submitted.
   ☐ including changes required by the attached Examiner's Amendment / Comment or in the Office action of Paper No./Mail Date _____ .

   Identifying indicia such as the application number (see 37 CFR 1.84(c)) should be written on the drawings in the front (not the back) of each sheet. Replacement sheet(s) should be labeled as such in the header according to 37 CFR 1.121(d).

6. ☐ DEPOSIT OF and/or INFORMATION about the deposit of BIOLOGICAL MATERIAL must be submitted. Note the attached Examiner's comment regarding REQUIREMENT FOR THE DEPOSIT OF BIOLOGICAL MATERIAL.

Attachment(s)

1. ☑ Notice of References Cited (PTO-892)
2. ☑ Information Disclosure Statements (PTO/SB/08), Paper No./Mail Date 2/13/2020.
3. ☐ Examiner's Comment Regarding Requirement for Deposit of Biological Material _____.
4. ☐ Interview Summary (PTO-413), Paper No./Mail Date. _____.
5. ☐ Examiner's Amendment/Comment
6. ☑ Examiner's Statement of Reasons for Allowance
7. ☐ Other _____.

/TUNG X LE/
Primary Examiner, Art Unit 2844

DETAILED ACTION

Notice of Pre-AIA or AIA Status

The present application is being examined under the pre-AIA first to invent provisions.

This Office Action is in response to the Applicant's amendment submitted on August 23, 2022. In virtue of this amendment:

- Claim 4 is cancelled; and thus,
- Claims **1-3** and **5-13** are now pending in the instant application.

Allowable Subject Matter

1. Claims 1-3 and 5-13 are allowed.

2. The following is an examiner's statement of reasons for allowance:

Prior art of record fails to disclose or fairly suggest the following limitations:

A device comprising … "*wherein the organic layer sequence and the encapsulation are disposed on a flexible carrier, wherein the organic layer sequence comprises at least one radiation-emitting region which generates electromagnetic radiation in a spectral range from infrared radiation to UV radiation during operation, and wherein the encapsulation forms a seal of the organic layer sequence against environmental influences; and at least one touch-sensitive operating element, wherein the at least one touch-sensitive operating element comprises at least one touch sensor, and wherein the device is flexible*", in combination with the remaining claimed limitations as claimed in independent claim 1 (claims 2-3 and 5-9 are allowed as being dependent on claim 1).

A device comprising … "*wherein the organic layer sequence comprises at least one radiation-emitting region which generates electromagnetic radiation in a spectral range from infrared radiation to UV radiation during operation, and wherein the encapsulation forms a seal*

of the organic layer sequence against environmental influences, at least one touch-sensitive operating element, wherein the at least one touch-sensitive operating element comprises at least one touch sensor, and wherein the device is formed on a flexible carrier whereby the device is bendable or rollable", in combination with the remaining claimed limitations as claimed in independent claim 10 (claims 11-13 are allowed as being dependent on claim 10).

Any comments considered necessary by applicant must be submitted no later than the payment of the issue fee and, to avoid processing delays, should preferably accompany the issue fee. Such submissions should be clearly labeled "Comments on Statement of Reasons for Allowance."

Conclusion

3. The prior art made of record and not relied upon is considered pertinent to applicant's disclosure.

Prior art Lee – US 7,211,945

Prior art Minoura et al. – US 6,787,976

4. Any inquiry concerning this communication or earlier communications from the examiner should be directed to TUNG X LE whose telephone number is (571)272-6010. The examiner can normally be reached Monday to Friday from 10am to 6pm.

Examiner interviews are available via telephone, in-person, and video conferencing using a USPTO supplied web-based collaboration tool. To schedule an interview, applicant is encouraged to use the USPTO Automated Interview Request (AIR) at http://www.uspto.gov/interviewpractice.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Amy C Johnson can be reached on 571-272-2238. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of published or unpublished applications may be obtained from Patent Center. Unpublished application information in Patent Center is available to registered users. To file and manage patent submissions in Patent Center, visit: https://patentcenter.uspto.gov. Visit https://www.uspto.gov/patents/apply/patent-center for more information about Patent Center and https://www.uspto.gov/patents/docx for information about filing in DOCX format. For additional questions, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

/TUNG X LE/
Primary Examiner, Art Unit 2844
October 13, 2022

Notice of References Cited	Application/Control No. 16/790,198	Applicant(s)/Patent Under Reexamination KASTNER-JUNG et al.	
	Examiner TUNG X LE	Art Unit 2844	Page 1 of 1

U.S. PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date MM-YYYY	Name	CPC Classification	US Classification
*	A	US-7211945-B2	05-2007	Lee; Ki Dong	H01L51/5275	313/506
*	B	US-6787976-B2	09-2004	Minoura; Kiyoshi	H01L51/5271	313/506
	C					
	D					
	E					
	F					
	G					
	H					
	I					
	J					
	K					
	L					
	M					

FOREIGN PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date MM-YYYY	Country	Name	CPC Classification
	N					
	O					
	P					
	Q					
	R					
	S					
	T					

NON-PATENT DOCUMENTS

*		Include as applicable: Author, Title Date, Publisher, Edition or Volume, Pertinent Pages)
	U	
	V	
	W	
	X	

*A copy of this reference is not being furnished with this Office action. (See MPEP § 707.05(a).)
Dates in MM-YYYY format are publication dates. Classifications may be US or foreign.

Search Notes	Application/Control No.	Applicant(s)/Patent Under Reexamination
	16/790,198	KASTNER-JUNG et al.
	Examiner	Art Unit
	TUNG X LE	2844

CPC - Searched*		
Symbol	Date	Examiner
H01L: 51/0097, 5209, 5218, 5225, 5246, 5253	08/10/2022	TXL
updated above	10/13/2022	TXL

CPC Combination Sets - Searched*		
Symbol	Date	Examiner

US Classification - Searched*			
Class	Subclass	Date	Examiner

* See search history printout included with this form or the SEARCH NOTES box below to determine the scope of the search.

Search Notes		
Search Notes	Date	Examiner
Updated PE2E Search (see search history printout)	08/10/2022	TXL
Inventors and Assignee Searches	08/10/2022	TXL
CPC Search	08/10/2022	TXL
Citations: Forward and Backward	08/10/2022	TXL
Updated PE2E Search (see search history printout)	10/13/2022	TXL

Interference Search			
US Class/CPC Symbol	US Subclass/CPC Group	Date	Examiner
H01L	51/5218, 51/5253	10/13/2022	TXL

Issue Classification	Application/Control No.	Applicant(s)/Patent Under Reexamination
	16/790,198	KASTNER-JUNG et al.
	Examiner	**Art Unit**
	TUNG X LE	2844

CPC								
Symbol							**Type**	**Version**
F21S	/	10	/	02			F	2013-01-01
F21V	/	23	/	0442			I	2013-01-01
F21V	/	33	/	0016			I	2013-01-01
F21V	/	33	/	004			I	2013-01-01
F21V	/	33	/	0052			I	2013-01-01
F21V	/	33	/	006			I	2013-01-01
G04C	/	19	/	02			I	2013-01-01
G04G	/	11	/	00			I	2013-01-01
G04G	/	13	/	023			I	2013-01-01
H05B	/	33	/	22			I	2013-01-01
B60Q	/	3	/	745			I	2017-02-01
B60Q	/	3	/	30			I	2017-02-01
B60Q	/	1	/	268			I	2013-01-01
B60Q	/	7	/	00			I	2013-01-01
B05B	/	1	/	18			I	2013-01-01
F24D	/	19	/	06			I	2013-01-01
H05B	/	45	/	60			I	2020-01-01
H05B	/	47	/	16			I	2020-01-01
H05B	/	47	/	105			I	2020-01-01
F21S	/	8	/	033			A	2013-01-01
F21S	/	8	/	04			A	2013-01-01
F21S	/	8	/	061			A	2013-01-01
F21S	/	9	/	03			A	2013-01-01
F21Y	/	2105	/	00			A	2013-01-01
F21Y	/	2115	/	15			A	2016-08-01
F21Y	/	2113	/	10			A	2016-08-01
F21Y	/	2113	/	20			A	2016-08-01
H01L	/	2251	/	5361			A	2013-01-01
H01L	/	51	/	504			A	2013-01-01
H01L	/	51	/	5076			A	2013-01-01
H01L	/	51	/	506			A	2013-01-01

NONE		**Total Claims Allowed:**	
(Assistant Examiner)	(Date)	12	
/TUNG X LE/ Primary Examiner, Art Unit 2844	13 October 2022	O.G. Print Claim(s)	O.G. Print Figure
(Primary Examiner)	(Date)	1	21

U.S. Patent and Trademark Office

Part of Paper No.: 20221013

Issue Classification	Application/Control No.	Applicant(s)/Patent Under Reexamination
	16/790,198	KASTNER-JUNG et al.
	Examiner	**Art Unit**
	TUNG X LE	2844

CPC						
Symbol					**Type**	**Version**
Y02B	/	20	/	30	A	2013-01-01
Y02B	/	20	/	40	A	2013-01-01
H05B	/	47	/	195	A	2020-01-01
H05B	/	47	/	125	A	2020-01-01
H05B	/	47	/	165	A	2020-01-01

CPC Combination Sets							
Symbol					**Type**	**Set**	**Ranking**	**Version**
	/		/					

NONE		Total Claims Allowed:	
(Assistant Examiner)	(Date)	12	
/TUNG X LE/ Primary Examiner, Art Unit 2844	13 October 2022	O.G. Print Claim(s)	O.G. Print Figure
(Primary Examiner)	(Date)	1	21

U.S. Patent and Trademark Office — Part of Paper No.: 20221013

Issue Classification	Application/Control No.	Applicant(s)/Patent Under Reexamination
	16/790,198	KASTNER-JUNG et al.
	Examiner	**Art Unit**
	TUNG X LE	2844

INTERNATIONAL CLASSIFICATION				
CLAIMED				
H01L	/	51	/	52

NON-CLAIMED				
	/		/	

US ORIGINAL CLASSIFICATION	
CLASS	**SUBCLASS**

CROSS REFERENCES(S)						
CLASS	**SUBCLASS (ONE SUBCLASS PER BLOCK)**					

NONE		Total Claims Allowed:	
(Assistant Examiner)	(Date)	12	
/TUNG X LE/ Primary Examiner, Art Unit 2844	13 October 2022	O.G. Print Claim(s)	O.G. Print Figure
(Primary Examiner)	(Date)	1	21

U.S. Patent and Trademark Office

Part of Paper No.: 20221013

SDC EX. 1027 - 461/489

Issue Classification	Application/Control No.	Applicant(s)/Patent Under Reexamination
	16/790,198	KASTNER-JUNG et al.
	Examiner	**Art Unit**
	TUNG X LE	2844

☐ Claims renumbered in the same order as presented by applicant ☐ CPA ☐ T.D. ☐ R.1.47

CLAIMS

Final	Original	Final	Original	Final	Original	Final	Original	Final	Original	Final	Original	Final	Original	Final	Original
1	1	9	10												
2	2	10	11												
3	3	11	12												
-	4	12	13												
4	5														
5	6														
6	7														
7	8														
8	9														

NONE		**Total Claims Allowed:**	
(Assistant Examiner)	(Date)	12	
/TUNG X LE/ Primary Examiner, Art Unit 2844	13 October 2022	O.G. Print Claim(s)	O.G. Print Figure
(Primary Examiner)	(Date)	1	21

U.S. Patent and Trademark Office

Part of Paper No.: 20221013

Attorney Docket # 5367-694PCON2/474410 Patent

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Continuation Application of
Ulrich KASTNER-JUNG et al.
Serial No.: TO BE ASSIGNED
Filing Date: CONCURRENTLY
For: Organic-Light-Emitting Diode

INFORMATION DISCLOSURE STATEMENT

Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

S I R:

In compliance with the duty of disclosure under 37 C.F.R. § 1.56 and in accordance with the practice under 37 C.F.R. §§ 1.97 and 1.98, the Examiner's attention is directed to the documents listed on the enclosed Form PTO/SB/08a.

Because (1) the parent application of this continuation application is identified as U.S. Application Serial No. 15/651,508 filed on July 17, 2017; and (2) the information cited herein was cited or discussed in the parent application, copies of the cited documents are not enclosed pursuant to 37 C.F.R. § 1.98(d).

It is respectfully requested that the above information be considered by the Examiner and that the copy of the enclosed Form PTO/SB/08a be returned indicating that such information has been considered.

In accordance with 37 C.F.R §§1.97(g) and (h), the filing of this Information Disclosure Statement should not be construed as a representation that a search has been made or that information cited is, or is considered to be, material to patentability as defined in §1.56(b), or that any cited document listed or attached

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /T.X.L/

SDC EX. 1027 - 463/489

is (or constitutes) prior art. Unless otherwise indicated, the date of publication indicated for an item is taken from the face of the item and Applicants reserve the right to prove that the date of publication is in fact different.

If any fees or charges are deemed required at this time in connection with the application, the same may be charged to our Patent and Trademark Office Deposit Account No. 503111.

Respectfully submitted,
Cozen O'Connor

By /Edward M. Weisz/
Edward M. Weisz
Reg. No. 37,257
277 Park Avenue
New York, New York 10172
(212) 883-4900

Dated: February 13, 2020

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /T.X.L/

PTO/SB/08A (04-03)
Approved for use through 04/30/2003. OMB 0651-0031
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number

Substitute for Form 1449/PTO	*Complete if Known*	
INFORMATION DISCLOSURE STATEMENT BY APPLICANT (Use as many sheets as necessary)	Application Number	
	Filing Date	
	First Named Inventor	Ulrich KASTNER-JUNG
	Art Unit	
	Examiner Name	
Sheet 1 of 4	Attorney Docket No.	5367-694PCON2/474410

U.S. PATENT DOCUMENTS

Examiner Initials*	Cite No. [1]	Document Number Number-Kind-Code [2] (if known)	Publication Date MM-DD-YYYY	Name of Patentee or Applicant of Cited Document	Pages, Columns, Lines, Where Relevant Passages or Relevant Figures Appear
		US-2007/0278937	12-06-2007	Forrest et al.	
		US-2003/0064540	04-03-2003	Auch et al.	
		US-7,280,439	10-09-2007	Shaddox	
		US-2003/0231495	12-18-2003	Searfoss, III	
		US-6,236,622	05-22-2001	Blackman	
		US-2008/0219013	09-11-2008	Budinger et al.	
		US-7,317,210	01-08-2008	Osram Opto Semiconductors GmbH	
		US-2009/0039272	02-12-2009	Osram Opto Semiconductors GmbH	
		US-7,922,358	04-12-2011	Osram Opto Semiconductors GmbH	
		US-2001/0052752	12-2001	Ghosh	
		US-2002/0125822	09-2002	Graff	
		US-2002/0167270	11-2002	Siwinski	
		US-2003/0071804	04-2003	Yamazaki	
		US-2003/0121767	07-2003	Caldwell	
		US-2003/0175553	09-2003	Thompson	
		US-2003/0222577	12-2003	Lu	
		US-2004/0113542	06-2004	Hsiao	
		US-2005/0099824	05-2005	Dowling	
		US-2006/0049381	03-2006	Klein	
		US-2007/0278937	12-2007	Forrest	
		US-2008/0248191	10-2008	Daniels	
		US-2010/0157585	06-2010	Diekmann	
		US-2012/0258294	10-2012	Leyder	
		US-5,734,225	03-1998	Biebuyck et al.	
		US-5,895,228	04-1999	Biebuyck	
		US-7,733,008	06-08-2010	Agency for Science Tech. & Research	
		US-2005/0231101	10-20-2005	Chen	
		US-2001/0043046	11-22-2001	Fukunaga	
		US-2007/0114520	05-24-2007	Osram Opto Seminconductors GmbH	
		US-2007/0230211	10-04-2007	Canon KK	
		US-2009/0072711	03-19-2009	Thomson Licensing	
		US-7,560,727	07-14-2009	Ishikawa	

Examiner Signature	/TUNG X LE/	Date Considered	10/19/2022

*EXAMINER: Initial if reference considered, whether or not citation is in conformance with MPEP 609. Draw line through citation if not in conformance and not considered. Include copy of this form with next communication to applicant. [1] Applicant's unique citation designation number (optional). [2] See Kinds Codes of USPTO Patent Documents at www.uspto.gov or MPEP 901.04. [3] Enter Office that issued the document, by the two-letter code (WIPO Standard ST.3). [4] For Japanese patent documents, the indication of the year of the reign of the Emperor must precede the serial number of the patent document. [5] Kind of document by the appropriate symbols as indicated on the document under WIPO Standard ST. 16 if possible. [6] Applicant is to place a check mark here if English language Translation is attached. This collection of information is required by 37 CFR 1.97 and 1.98. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, Washington, DC 20231.**

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /T.X.L/

PTO/SB/08A (04-03)
Approved for use through 04/30/2003. OMB 0651-0031
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number

Substitute for Form 1449/PTO	*Complete if Known*	
	Application Number	
	Filing Date	
INFORMATION DISCLOSURE STATEMENT BY APPLICANT	First Named Inventor	Ulrich KASTNER-JUNG
	Art Unit	
(Use as many sheets as necessary)	Examiner Name	
Sheet 2 of 4	Attorney Docket No.	5367-694PCON2/474410

FOREIGN PATENT DOCUMENTS

Examiner Initials*	Cite No. [1]	Foreign Patent Document Country Code[3]- Number[4]-Kind-Code [5] (if known	Publication Date MM-DD-YYYY	Name of Patentee or Applicant of Cited Document	Pages, Columns, Lines, Where Relevant Passages or Relevant Figures Appear	T[6]
		DE 10 2006 037 222	02-14-2008	Swoboda et al.		
		JP 2007-294143	11-08-2007	Matsuura		
		WO 2008/110959	09-18-2008	Van Woudenberg et al.		
		WO 2008/146232	12-04-2008	Schlangen et al.		
		DE 10308514	09-09-2004	Schott Glas		
		DE 10332956	02-10-2005	Woehr Richard GmbH		
		KR 20080081255	09-09-2008	Osram Opto Semiconductors GmbH		
		KR 20020079438	10-19-2002	Eastman Kodak Co.		
		DE 102008051132	01-21-2010	Osram Opto Semiconductors GmbH		
		WO 2009/040401	04-02-2009	Osram Opto Semiconductors GmbH		
		WO 2009/074127	06-18-2009	Osram Opto Semiconductors GmbH		
		WO 2009/095005	08-06-2009	Osram Opto Semiconductors GmbH		
		WO 2009/106067	09-03-2009	Osram Opto Semiconductors GmbH		
		WO 2010/006571	01-21-2010	Osram Opto Semiconductors GmbH		
		WO 2008/040323	04-2008	Diekmann		
		WO 2008/146232	12-2008	Schlangen		
		JP 2005-510851	04-21-2005	Agency for Science, Tech. & Research		
		KR 100743545	07-23-2007	Lee Young Jong		
		KR 1020050065948	11-11-2013	LG Electronics Inc.		
		JP 2002-033198	01-31-2002	Semiconductor Energy Lab		
		DE 102007059732	06-18-2009	OSRAM Opto Semiconductors GmbH		
		KR 2008-0042275	05-15-2008	Oh et al.		

Examiner Signature	/TUNG X LE/	Date Considered	10/19/2022

*EXAMINER: Initial if reference considered, whether or not citation is in conformance with MPEP 609. Draw line through citation if not in conformance and not considered. Include copy of this form with next communication to applicant. [1] Applicant's unique citation designation number (optional). [2] See Kinds Codes of USPTO Patent Documents at www.uspto.gov or MPEP 901.04. [3] Enter Office that issued the document, by the two-letter code (WIPO Standard ST.3). [4] For Japanese patent documents, the indication of the year of the reign of the Emperor must precede the serial number of the patent document. [5] Kind of document by the appropriate symbols as indicated on the document under WIPO Standard ST. 16 if possible. [6] Applicant is to place a check mark here if English language Translation is attached. This collection of information is required by 37 CFR 1.97 and 1.98. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, Washington, DC 20231.**

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /T.X.L/

PTO/SB/08A (04-03)
Approved for use through 04/30/2003. OMB 0651-0031
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number

Substitute for Form 1449/PTO

INFORMATION DISCLOSURE STATEMENT BY APPLICANT

(Use as many sheets as necessary)

Sheet 3 of 4

Complete if Known	
Application Number	
Filing Date	
First Named Inventor	Ulrich KASTNER-JUNG
Art Unit	
Examiner Name	
Attorney Docket	5367-694P/CON2/474410

FOREIGN PATENT DOCUMENTS

Examiner Initials*	Cite No. [1]	Foreign Patent Document Country Code[3]- Number[4]- Kind-Code [5] (if known	Publication Date MM-DD-YYYY	Name of Patentee or Applicant of Cited Document	Pages, Columns, Lines, Where Relevant Passages or Relevant Figures Appear	T[6]
		JP 2007-200887	08-09-2007	Dong-Soo et al.		
		JP 2004-296423	10-21-2004	Toshitaka et al.		
		JP 2008-538155	10-09-2008	Cok et al.		
		JP 4182467B2	11-19-2008	Takashi		
		JP 4228248B2	02-25-2009	Hideo et al.		
		JP 4637390B2	02-23-2011	Shunpei et al.		
		JP 4713010B2	06-29-2011	Kenji		
		JP 4742880B2	08-10-2011	Osamu et al.		
		JP 4828881B2	11-30-2011	Satoshi		
		JP 2003-195775	07-09-2003	Takashi		
		JP 2004-047179	02-12-2004	Tamotsu et al.		

Examiner Signature	/TUNG X LE/	Date Considered	10/19/2022

*EXAMINER: Initial if reference considered, whether or not citation is in conformance with MPEP 609. Draw line through citation if not in conformance and not considered. Include copy of this form with next communication to applicant. [1] Applicant's unique citation designation number (optional). [2] See Kinds Codes of USPTO Patent Documents at www.uspto.gov or MPEP 901.04. [3] Enter Office that issued the document, by the two-letter code (WIPO Standard ST.3). [4] For Japanese patent documents, the indication of the year of the reign of the Emperor must precede the serial number of the patent document. [5] Kind of document by the appropriate symbols as indicated on the document under WIPO Standard ST. 16 if possible. [6] Applicant is to place a check mark here if English language Translation is attached. This collection of information is required by 37 CFR 1.97 and 1.98. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, Washington, DC 20231.**

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /T.X.L/

PTO/SB/08A (04-03)
Approved for use through 04/30/2003. OMB 0651-0031
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number

Substitute for Form 1449/PTO

INFORMATION DISCLOSURE STATEMENT BY APPLICANT

(Use as many sheets as necessary)

Sheet 4 of 4

Complete if Known	
Application Number	
Filing Date	
First Named Inventor	Ulrich KASTNER-JUNG
Art Unit	
Examiner Name	
Attorney Docket No.	5367-694PCON2/474410

NON PATENT LITERATURE DOCUMENTS

Examiner Initials*	Cite No.[1]	Include name of the author (in CAPITAL LETTERS), title of the article (when appropriate), title of the item (book, magazine, journal, serial, symposium, catalog, etc.), date, page(s), volume-issue number(s), publisher, city and/or country where published.	T[2]
		Boffi Wedge. Stylepark, May 25, 2011. (1 page). Retrieved from http://www.stylepark.com/en/boffi/wedge.	
		Bus stop shelter intelligent series. May 25, 2011. (2 pages). Retrieved from http://www.wall.de/en/street_furniture/products?category_scope=bus_stop_shelter	
		Cristina Rubinetterie sandwich shower head – new electronic LED shower head, May 12, 2007. (3 pages). Retrieved from http://www.trendir.com/archives/001435.html.	
		Dornbracht RainSky E Showers by Rixson & Green Shortlands Ltd. September 2000. (1 page). Retrieved from http://www.rixson-green.co.uk/dornbracht_showers.htm.	
		Marketing-displays. Illuminated box CLP-S I freetstanding unit, one-sided (1200 x 1760 mm). May 25, 2011. (1 page). Retrieved from http://www.md-displayshop.de/ProductDetails.aspx?id=24&prodi...	
		LCD-Glass; Glass with LCD Film (max height 300 – max width 120). 2009. (2 pages). Retrieved from http://www.vetroin.co.uk/en/TECHNOLOGY/LDC-Glass.html no month	
		ThinkGeek:Lumadot LED Umbrella. May 25, 2011. (2 pages). Retrieved from http://www.thinkgeek.com/interests/moms/d16b/	
		Luceplan. Strip D22/4 – D22/4 EL. May 25, 2011. Retrieved from http://www.luceplan.com/Dynamic/Prodotti.php?intLangID=1&intC...	
		Multifunctional shower cabin- WELL BOX- Megius SpA. 2011. (1 page). Retrieved from http://www.archiexpo.com/prod/megius-spa/multifunctional-shower... no month	
		The General Properties of Si, Ge, SiGe, SiO2 and Si3N4 (June 2002, Virginia Semiconductor, Retrieved from the Internet: <URL www.virginiasemi.com/pdf/generalpropertiesSi62002.pdf>)	
		Edgar S. Zaus et al., "Design of Highly Transparent Organic Photodiodes, IEEE Transactions of Electron Devices, Vo. 55, No. 2, February 2008	
		N. R. Mowrer, "Polysiloxanes, Ameron International Performance Coatings and Finishes, November 2003	

Examiner Signature	/TUNG X LE/	Date Considered	10/19/2022

*EXAMINER: Initial if reference considered, whether or not citation is in conformance with MPEP 609. Draw line through citation if not in conformance and not considered. Include copy of this form with next communication to applicant. [1] Applicant's unique citation designation number (optional). [2] See Kinds Codes of USPTO Patent Documents at www.uspto.gov or MPEP 901.04. [3] Enter Office that issued the document, by the two-letter code (WIPO Standard ST.3). [4] For Japanese patent documents, the indication of the year of the reign of the Emperor must precede the serial number of the patent document. [5] Kind of document by the appropriate symbols as indicated on the document under WIPO Standard ST. 16 if possible. [6] Applicant is to place a check mark here if English language Translation is attached. This collection of information is required by 37 CFR 1.97 and 1.98. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, Washington, DC 20231.**

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /T.X.L/

PE2E SEARCH - Search History (Prior Art)

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	British Equivalents	Time Stamp
L1	1	"16790198"	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/09 01:10 PM
L2	7	("20030071259"|"6926572"|"7205714"|"20020003403"|"20040022058"|"20110187668"|"20110096504").PN.	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/09 06:40 PM
L3	1566	(OLED OR (organic near3 diode)) WITH layer WITH sequence	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/09 06:46 PM
L4	55	L3 AND (flexible WITH carrier)	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/09 06:46 PM
L5	46	L4 AND encapsulat$3	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/09 06:49 PM
L6	11	L5 AND (UV WITH radiat$3 WITH infrared)	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/09 06:49 PM
L7	5	L6 AND (touch$3 WITH sens$3)	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/09 06:50 PM
L8	39	("5734225" | "6236622" | "7280439" | "7317120" | "7317210" | "7733008" | "7922358" | "20010052752" | "20020125822" | "20020167270" | "20030064540" | "20030071804" | "20030121767" | "20030175553" | "20030222577" | "20030231495" | "20040113542" | "20050099824" | "20060049381" | "20070278937" | "20080219013" | "20080248191" | "20090039272" | "20100157585" | "20120258294").pn. OR ("9797567").urpn. AND (PGPB | USPT | USOC).dbnm.	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/09 06:55 PM
L9	33	("5734225" | "5895228" | "6236622" | "7205714" | "7280439" | "7317210" | "7560727" | "7733008" | "7922358" | "20010043046" | "20010052752" |	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/09 07:02 PM

		"20020125822" | "20020167270" | "20030064540" | "20030071804" | "20030121767" | "20030175553" | "20030222577" | "20030231495" | "20040113542" | "20050099824" | "20050231101" | "20060049381" | "20070114520" | "20070230211" | "20070278937" | "20080219013" | "20080248191" | "20090039272" | "20090072711" | "20100157585" | "20120258294").pn. OR ("10605422").urpn. AND (PGPB | USPT | USOC).dbnm.					
L10	23	("4356429" | "5645948" | "5693956" | "5770920" | "5796120" | "6150187" | "6198217" | "6558820" | "6690108" | "20010041268" | "20020057055" | "20020167025" | "20030087126").pn. OR ("7733008").urpn. AND (PGPB | USPT | USOC).dbnm.	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/09 07:05 PM
L11	9	("5445899" | "5814417").pn. OR ("6690108").urpn. AND (PGPB | USPT | USOC).dbnm.	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/09 07:05 PM
L12	25	("4287449" | "4602189" | "4613793" | "4758765" | "4963788").pn. OR ("5445899").urpn. AND (PGPB | USPT | USOC).dbnm.	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/09 07:06 PM
L13	61355	(OLED.u/c. OR (organic near3 light$3 near3 emitting near3 diode)) WITH layer	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/10 10:34 AM
L14	12860	L13 AND (organic adj1 layer) AND ((encapsulat$3 OR seal$3 OR insulat$3) adj1 layer)	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/10 10:35 AM

L15	87	L14 AND (radiat$3 WITH infrared WITH UV.u/c.)	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/10 10:37 AM
L16	35	L15 AND touch$3	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/10 10:37 AM
L17	25	L15 AND (touch$3 WITH sens$3)	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/10 10:37 AM
L18	62	L15 NOT L17	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/10 10:38 AM
L19	21	("6303238" | "6479612" | "6670645" | "7138551" | "7151342" | "7554112" | "7736926" | "20040062947" | "20040102577" | "20040127637" | "20050184287" | "20050205860" | "20060142520" | "20070059555" | "20070075626" | "20070218582" | "20080157659" | "20080160270" | "20080233493" | "20080286487" | "20090017268").pn. OR ("8040048").urpn. AND (PGPB | USPT | USOC).dbnm.	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/10 10:42 AM
L20	1379	("4950950" | "5128587" | "5203974" | "5231329" | "5294810" | "5457565" | "5540999" | "5601903" | "5703436" | "5707745" | "5756224" | "5757026" | "5757139" | "5811833" | "5834130" | "5834893" | "5844363" | "5861219" | "5874803" | "5917280" | "5932895" | "5953587" | "5981306" | "5986268" | "5986401" | "5998803" | "6013538" | "6013982" | "6030715" | "6045930" | "6046543" | "6048630" | "6091195" | "6097147" | "6111902" | "6125226").pn. OR ("6303238").urpn. AND (PGPB | USPT | USOC).dbnm.	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/10 10:43 AM
L21	5	("20090124062" | "20140072771" | "20150171354" | "20160081180" |	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/10 10:47 AM

		"20160299283").pn. OR ("10693088").urpn. AND (PGPB | USPT | USOC).dbnm.					
L22	2639	L13 AND ((flexible OR bend$4 OR roll$4) WITH carrier)	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/10 10:51 AM
L23	781	L22 AND (organic adj1 layer) AND ((encapsulat$3 OR seal$3 OR insulat$3) adj1 layer)	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/10 10:52 AM
L24	257	L23 AND (infrared OR UV.u/c.)	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/10 10:53 AM
L25	586	("3949410" | "4058418" | "4392451" | "4416288" | "4471003" | "4487162" | "4658153" | "4663828" | "4761335" | "4763275" | "4766670" | "4784720" | "4855017" | "5041973" | "5086785" | "5108819" | "5118400" | "5147519" | "5178957" | "5204144" | "5306917" | "5313094" | "5331966" | "5360987" | "5403700" | "5427096" | "5434751" | "5439575" | "5455178" | "5455430" | "5469845" | "5477088" | "5501893" | "5525815" | "5539935" | "5545291" | "5549108" | "5560974" | "5567975" | "5625471" | "5648148" | "5687737" | "5691245" | "5746207" | "5753529" | "5757081" | "5767578" | "5772905" | "5783856" | "5790151" | "5811790" | "5817242" | "5824186" | "5837546" | "5860974" | "5871443" | "5904545" | "5907189" | "5915180" | "5917534" | "5928001" | "5955781" | "5968839" | "5976683" | "5978972" | "5998291" | "6009632" | "6024702" | "6057212" | "6080608" | "6097984" | "6121110" | "6148127" | "6150602" | "6165391" | "6165885" | "6171730" | "6225149" | "6236883" | "6265326" | "6274508" | "6276775" | "6277712" | "6281038" | "6282960" | "6284418"	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/10 10:55 AM

		| "6291896" | "6301500" | "6309351" | "6316278" | "6316283" | "6317175" | "6322895" | "6322963" | "6334960" | "6344616" | "6360615" | "6380729" | "6403397" | "6403944" | "6413790" | "6414783" | "6417025" | "6420266" | "6433401" | "6451191" | "6459418" | "6468638" | "6479395" | "6504105" | "6517995" | "6518168" | "6527964" | "6555408" | "6566744" | "6567158" | "6580151" | "6586338" | "6590346" | "6606079" | "6606247" | "6608370" | "6613979" | "6623579" | "6639578" | "6655286" | "6657289" | "6661037" | "6665044" | "6666821" | "6667548" | "6683663" | "6693384" | "6706402" | "6720469" | "6723576" | "6730990" | "6731353" | "6743982" | "6762510" | "6780696" | "6784450" | "6787052" | "6805809" | "6814898" | "6816380" | "6826509" | "6836744" | "6844673" | "6848162" | "6850312" | "6856830" | "6863219" | "6864435" | "6864570" | "6872645" | "6878871" | "6881979" | "6885030" | "6887450" | "6900094" | "6917061" | "6936181" | "6949199" | "6949206" | "6950220" | "6984934" | "6989285" | "7029951" | "7033961" | "7054784" | "7067903" | "7081642" | "7116318" | "7132313" | "7148512" | "7158277" | "7169546" | "7169669" | "7170164" | "7186624" | "7190051" | "7195733" | "7223609" | "7223632" | "7252664" | "7253442" | "7255919" | "7265298" | "7291146" | "7291540" | "7293353" | "7337012" | "7374968" | "7425523" | "7487587" | "7491892" | "7509835" | "7521292" | "7525304" | "7526389" | "7552031"				

		| "7557367" | "7593086" | "7622367" | "7629691" | "7633761" | "7635755" | "7674882" | "7700402" | "7704684" | "7705280" | "7709961" | "7727199" | "7727575" | "7732012" | "7742795" | "7759167" | "7769472" | "7799699" | "7838964" | "7842780" | "7857781" | "7871661" | "7884540" | "7909971" | "7932123" | "7935056" | "7943491" | "7960246" | "7972875" | "7982296" | "8008575" | "8039847" | "8107248" | "8198621" | "8207473" | "8252191" | "8367035" | "8394706" | "8440546" | "20010003043" | "20010012918" | "20010021867" | "20020021445" | "20020026127" | "20020082515" | "20020094701" | "20020095087" | "20020110766" | "20020128700" | "20020151934" | "20030006527" | "20030017848" | "20030032892" | "20030082889" | "20030087476" | "20030097165" | "20030120271" | "20030138704" | "20030149456" | "20030171691" | "20030178316" | "20030222282" | "20030227116" | "20030236455" | "20040005723" | "20040006264" | "20040026684" | "20040061543" | "20040079464" | "20040081384" | "20040085469" | "20040092806" | "20040095658" | "20040106334" | "20040112964" | "20040135094" | "20040136866" |					

		"20040138558" | "20040146560" | "20040149921" | "20040155290" | "20040171969" | "20040178390" | "20040178466" | "20040192062" | "20040192082" | "20040200734" | "20040206448" | "20040211458" | "20040211459" | "20040229830" | "20040243204" | "20040250950" | "20040252559" | "20050020094" | "20050021103" | "20050037511" | "20050038498" | "20050054939" | "20050082526" | "20050107716" | "20050113744" | "20050115308" | "20050124712" | "20050133954" | "20050136501" | "20050171524" | "20050177335" | "20050203366" | "20050214962" | "20050227389" | "20050233546" | "20050238967" | "20050255686" | "20050260706" | "20050261561" | "20060038182" | "20060049485" | "20060056161" | "20060068576" | "20060076561" | "20060084012" | "20060084394" | "20060085976" | "20060102525" | "20060106321" | "20060119853" | "20060127817" | "20060129056" | "20060132025" | "20060134893" | "20060154398" | "20060159837" | "20060169989" | "20060173364" |				

		"20060177479" | "20060178655" | "20060244105" | "20060255341" | "20060273279" | "20060279191" | "20060286488" | "20060286785" | "20070009968" | "20070027514" | "20070031607" | "20070032089" | "20070043416" | "20070058254" | "20070073130" | "20070104944" | "20070108389" | "20070122819" | "20070187862" | "20070212730" | "20070213616" | "20070227586" | "20070233208" | "20070254468" | "20080000871" | "20080008626" | "20080038236" | "20080041617" | "20080046080" | "20080054875" | "20080055581" | "20080077225" | "20080085272" | "20080090322" | "20080102096" | "20080108171" | "20080108942" | "20080140152" | "20080152281" | "20080157234" | "20080157235" | "20080183076" | "20080188912" | "20080193749" | "20080203268" | "20080203431" | "20080208268" | "20080212102" | "20080239755" | "20080257586" | "20080280360" | "20080287167" | "20080288037" | "20080293919" | "20080313552" | "20090001550" | "20090004737" | "20090015560" |				

		"20090028910" | "20090054742" | "20090088750" | "20090105605" | "20090107704" | "20090149930" | "20090183986" | "20090184254" | "20090198293" | "20090199960" | "20090202614" | "20090204168" | "20090208555" | "20090215385" | "20090221896" | "20090232963" | "20090234026" | "20090247909" | "20090273909" | "20090289246" | "20090294803" | "20090308455" | "20090317639" | "20100002402" | "20100028451" | "20100046902" | "20100052112" | "20100055438" | "20100059863" | "20100063404" | "20100065784" | "20100068740" | "20100070068" | "20100072577" | "20100073669" | "20100087782" | "20100096763" | "20100116526" | "20100117660" | "20100120116" | "20100121420" | "20100152619" | "20100176705" | "20100178304" | "20100178722" | "20100188799" | "20100191328" | "20100196447" | "20100200752" | "20100203226" | "20100252840" | "20100271191" | "20100279112" | "20100283069" | "20100289124" | "20100298895" | "20100317132" | "20100324455"				

		"20100327387" | "20110011179" | "20110018838" | "20110034912" | "20110054583" | "20110068672" | "20110114894" | "20110147715" | "20110170225" | "20110171813" | "20110177332" | "20110187798" | "20110215931" | "20110218756" | "20110218757" | "20110220890" | "20110230747" | "20110266561" | "20110272181" | "20110277813" | "20110316120" | "20120051005" | "20120052268" | "20120065937" | "20120083099" | "20120092178" | "20120105528" | "20120157804" | "20120157986" | "20120157987" | "20120157988" | "20120157989" | "20120158101" | "20120165759" | "20120251824" | "20120256308" | "20120261551" | "20120279762" | "20120320581" | "20120327608" | "20130036928" | "20130041235" | "20130100618").pn. OR ("8886334").urpn. AND (PGPB | USPT | USOC).dbnm.					
L27	27	(pictiva near3 displays near3 international) OR (osram near2 OLED.u/c.)	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/10 10:59 AM
L28	298	((ulrich near2 jung) OR (markus near2 klein) OR (stan near2 maes) OR (romana near2 sigl) OR (annette near2 haid) OR (stephan near2 lintner) OR (julian	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/10 11:07 AM

		near2 herget) OR (gregor near2 matjan)).in.					
L29	27726	(H01L51/0097 OR H01L51/5209 OR H01L51/5218 OR H01L51/5225 OR H01L51/5246 OR H01L51/5253).CPC.	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/10 11:08 AM
L30	28029	L27 OR L28 OR L29	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/10 11:09 AM
L31	2068	L30 AND ((flexible OR bend$4 OR roll$4) WITH carrier)	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/10 11:09 AM
L32	560	L31 AND (organic adj1 layer) AND ((encapsulat$3 OR seal$3 OR insulat$3) adj1 layer)	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/10 11:11 AM
L33	455	L32 NOT L24	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/10 11:11 AM
L34	13	("20050110049" | "20090021666" | "20120146886" | "20130169515" | "20140048314").pn. OR ("9882152").urpn. AND (PGPB | USPT | USOC).dbnm.	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/10 11:14 AM
L35	36	("8377762" | "8698189" | "8933451" | "9287342" | "9543370" | "9659966" | "9698162" | "9882152" | "10020462" | "20060169989" | "20080079889" | "20110227846" | "20120162099" | "20130148312" | "20140097408" | "20140217373" | "20140217397" | "20140232956" | "20140353670" | "20150102298" | "20150116959" | "20150179728" | "20160014883" | "20160195901" | "20160204185" | "20160218305" | "20160239133" | "20160336523" | "20170062532" | "20170092230" | "20170147117" |	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/08/10 11:17 AM

		"20170237025" | "20170329368" | "20180019418").pn. OR ("10211276").urpn. AND (PGPB | USPT | USOC).dbnm.					
L36	91084	L1 amd (layer near2 sequence) AND encapsulation AND (exit near2 area)	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/10/13 08:42 AM
L37	1	L1 AND (layer near2 sequence) AND encapsulation AND (exit near2 area)	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/10/13 10:18 AM
L38	11	("20030071259"|"6926572"|"7205714"|"20020003403"|"20040022058"|"20060141135"|"20110187668"|"20050110049"|"20090142556"|"20090021666"|"20110096504").PN.	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/10/13 10:25 AM
L39	11	("6590346" | "6617784" | "6777871" | "6787976" | "6984934" | "20030117067" | "20030141805").pn. OR ("7205714").urpn. AND (PGPB | USPT | USOC).dbnm.	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/10/13 10:27 AM
L40	106	("5300263" | "5703436" | "5707745" | "5796509" | "5948281" | "6245393" | "6303238" | "6337102").pn. OR ("6984934").urpn. AND (PGPB | USPT | USOC).dbnm.	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/10/13 10:28 AM
L41	1136	osram near2 OLED	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/10/13 10:37 AM
L42	78710	L13 OR L30 OR L41	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/10/13 10:38 AM
L43	3918	L42 AND ((flexible OR bend$4 OR roll$4) WITH carrier)	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/10/13 10:38 AM
L44	344	L43 AND (sequence WITH layer)	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/10/13 10:39 AM
L45	6	("9136447" | "20120056228" | "20120056229" | "20170062671" | "20180040779" | "20190157524").pn. OR ("11158771").urpn. AND (PGPB | USPT |	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/10/13 10:40 AM

		USOC).dbnm.					
L46	10	("20090173957" | "20130069525" | "20140001949").pn. OR ("9136447").urpn. AND (PGPB | USPT | USOC).dbnm.	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/10/13 10:41 AM
L47	6	("9136447" | "20120056228" | "20120056229" | "20170062671" | "20180040779" | "20190157524").pn. OR ("11158771").urpn. AND (PGPB | USPT | USOC).dbnm.	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/10/13 10:41 AM
L48	1	(device AND (organic near5 diode) AND (organic near3 layer near3 sequence) AND (radiation near3 exit near3 area) AND encapsulation AND (flexible near3 carrier) AND (spectral near3 range) AND (touch near3 sensitive)).clm.	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2022/10/13 10:44 AM

PE2E SEARCH - Search History (Interference)

There are no Interference searches to show.

UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

BIB DATA SHEET

CONFIRMATION NO. 1309

SERIAL NUMBER	FILING or 371(c) DATE RULE	CLASS	GROUP ART UNIT	ATTORNEY DOCKET NO.
16/790,198	02/13/2020	315	2844	PICTIV 3.3F-001 CC [2]

APPLICANTS

PICTIVA DISPLAYS INTERNATIONAL LIMITED, Dublin, IRELAND;

INVENTORS

Ulrich KASTNER-JUNG, Munich, GERMANY;
Markus KLEIN, Tegernheim, GERMANY;
Stan MAES, Dilsen-Stokken, BELGIUM;
Romana SIGL, Salzburg, AUSTRIA;
Annette HAID, Salzburg, AUSTRIA;
Stephan LINTNER, Salzburg, AUSTRIA;
Julian HERGET, Marktschellenberg, GERMANY;
Gregor MATJAN, Bergheim, AUSTRIA;

**** CONTINUING DATA ***************************

This application is a CON of 15/651,508 07/17/2017 PAT 10605422
which is a CON of 13/139,514 01/03/2012 PAT 9797567
which is a 371 of PCT/DE2009/001741 12/09/2009

**** FOREIGN APPLICATIONS ***************************

GERMANY 10 2008 061 563.3 12/11/2008

**** IF REQUIRED, FOREIGN FILING LICENSE GRANTED ****

02/28/2020

Foreign Priority claimed	STATE OR COUNTRY	SHEETS DRAWINGS	TOTAL CLAIMS	INDEPENDENT CLAIMS
☑ Yes ☐ No	GERMANY	60	12 ~~13~~	2

35 USC 119(a-d) conditions met ☑ Yes ☐ No ☐ Met after Allowance

Verified and Acknowledged /TUNG X LE/ Examiner's Signature — TXL Initials

ADDRESS

TXL 10/13/2022

Botos Churchill IP Law LLP
430 Mountain Avenue
Suite 401
New Providence, NJ 07974
UNITED STATES

TITLE

Organic-Light-Emitting Diode

FILING FEE RECEIVED		
2680	FEES: Authority has been given in Paper No._____ to charge/credit DEPOSIT ACCOUNT No._____ for following:	☐ All Fees ☐ 1.16 Fees (Filing) ☐ 1.17 Fees (Processing Ext. of time) ☐ 1.18 Fees (Issue) ☐ Other _____ ☐ Credit

BIB (Rev. 05/07).

PART B - FEE(S) TRANSMITTAL

Complete and send this form, together with applicable fee(s), by mail or fax, or via EFS-Web.

By mail, send to: Mail Stop ISSUE FEE
Commissioner for Patents
P.O. Box 1450
Alexandria, Virginia 22313-1450

By fax, send to: (571)-273-2885

INSTRUCTIONS: This form should be used for transmitting the ISSUE FEE and PUBLICATION FEE (if required). Blocks 1 through 5 should be completed where appropriate. All further correspondence including the Patent, advance orders and notification of maintenance fees will be mailed to the current correspondence address as indicated unless corrected below or directed otherwise in Block 1, by (a) specifying a new correspondence address; and/or (b) indicating a separate "FEE ADDRESS" for maintenance fee notifications.

CURRENT CORRESPONDENCE ADDRESS (Note: Use Block 1 for any change of address)

175540 7590 10/21/2022
Botos Churchill IP Law LLP
430 Mountain Avenue
Suite 401
New Providence, NJ 07974

Note: A certificate of mailing can only be used for domestic mailings of the Fee(s) Transmittal. This certificate cannot be used for any other accompanying papers. Each additional paper, such as an assignment or formal drawing, must have its own certificate of mailing or transmission.

Certificate of Mailing or Transmission

I hereby certify that this Fee(s) Transmittal is being deposited with the United States Postal Service with sufficient postage for first class mail in an envelope addressed to the Mail Stop ISSUE FEE address above, or being transmitted to the USPTO via EFS-Web or by facsimile to (571) 273-2885, on the date below.

Richard J. Botos	(Typed or printed name)
/Richard J. Botos/	(Signature)
January 17, 2023	(Date)

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
16/790,198	02/13/2020	Ulrich KASTNER-JUNG	PICTIV 3.3F-001 CC [2]	1309

TITLE OF INVENTION: Organic-Light-Emitting Diode

APPLN. TYPE	ENTITY STATUS	ISSUE FEE DUE	PUBLICATION FEE DUE	PREV. PAID ISSUE FEE	TOTAL FEE(S) DUE	DATE DUE
nonprovisional	UNDISCOUNTED	$1200	$0.00	$0.00	$1200	01/23/2023

EXAMINER	ART UNIT	CLASS-SUBCLASS
LE, TUNG X	2844	315-360000

1. Change of correspondence address or indication of "Fee Address" (37 CFR 1.363).

☐ Change of correspondence address (or Change of Correspondence Address form PTO/AIA/122 or PTO/SB/122) attached.

☐ "Fee Address" indication (or "Fee Address" Indication form PTO/AIA/47 or PTO/SB/47; Rev 03-02 or more recent) attached. **Use of a Customer Number is required.**

2. For printing on the patent front page, list
(1) The names of up to 3 registered patent attorneys or agents OR, alternatively,
(2) The name of a single firm (having as a member a registered attorney or agent) and the names of up to 2 registered patent attorneys or agents. If no name is listed, no name will be printed.

1 Botos Churchill IP Law
2
3

3. ASSIGNEE NAME AND RESIDENCE DATA TO BE PRINTED ON THE PATENT (print or type)

PLEASE NOTE: Unless an assignee is identified below, no assignee data will appear on the patent. If an assignee is identified below, the document must have been previously recorded, or filed for recordation, as set forth in 37 CFR 3.11 and 37 CFR 3.81(a). Completion of this form is NOT a substitute for filing an assignment.

(A) NAME OF ASSIGNEE: Pictiva Displays International Limited

(B) RESIDENCE: (CITY and STATE OR COUNTRY): Ireland

Please check the appropriate assignee category or categories (will not be printed on the patent) : ☐ Individual ☐ Corporation or other private group entity ☐ Government

4a. Fees submitted: ☒ Issue Fee ☐ Publication Fee (if required) ☐ Advance Order - # of Copies

4b. Method of Payment: *(Please first reapply any previously paid fee shown above)*

☒ Electronic Payment via EFS-Web ☐ Enclosed check ☐ Non-electronic payment by credit card (Attach form PTO-2038)

☒ The Director is hereby authorized to charge the required fee(s), any deficiency, or credit any overpayment to Deposit Account No. 60-1866

5. **Change in Entity Status** (from status indicated above)

☐ Applicant certifying micro entity status. See 37 CFR 1.29

☐ Applicant asserting small entity status. See 37 CFR 1.27

☐ Applicant changing to regular undiscounted fee status.

NOTE: Absent a valid certification of Micro Entity Status (see forms PTO/SB/15A and 15B), issue fee payment in the micro entity amount will not be accepted at the risk of application abandonment.
NOTE: If the application was previously under micro entity status, checking this box will be taken to be a notification of loss of entitlement to micro entity status.
NOTE: Checking this box will be taken to be a notification of loss of entitlement to small or micro entity status, as applicable.

NOTE: This form must be signed in accordance with 37 CFR 1.31 and 1.33. See 37 CFR 1.4 for signature requirements and certifications.

Authorized Signature /Richard J. Botos/ Date January 17, 2023

Typed or printed name Richard J. Botos Registration No. 32,016

SDC EX. 1027 - 483/489

Electronic Patent Application Fee Transmittal

Application Number:	16790198
Filing Date:	13-Feb-2020
Title of Invention:	Organic-Light-Emitting Diode
First Named Inventor/Applicant Name:	Ulrich KASTNER-JUNG
Filer:	Richard J. Botos/Gaby Hecht
Attorney Docket Number:	PICTIV 3.3F-001 CC [2]

Filed as Large Entity

Filing Fees for Utility under 35 USC 111(a)

Description	Fee Code	Quantity	Amount	Sub-Total in USD($)
Basic Filing:				
Pages:				
Claims:				
Miscellaneous-Filing:				
Petition:				
Patent-Appeals-and-Interference:				
Post-Allowance-and-Post-Issuance:				
UTILITY APPL ISSUE FEE	1501	1	1200	1200

Description	Fee Code	Quantity	Amount	Sub-Total in USD($)
Extension-of-Time:				
Miscellaneous:				
			Total in USD ($)	**1200**

Electronic Acknowledgement Receipt

EFS ID:	47380582
Application Number:	16790198
International Application Number:	
Confirmation Number:	1309
Title of Invention:	Organic-Light-Emitting Diode
First Named Inventor/Applicant Name:	Ulrich KASTNER-JUNG
Customer Number:	175540
Filer:	Richard J. Botos/Gaby Hecht
Filer Authorized By:	Richard J. Botos
Attorney Docket Number:	PICTIV 3.3F-001 CC [2]
Receipt Date:	17-JAN-2023
Filing Date:	13-FEB-2020
Time Stamp:	14:35:30
Application Type:	Utility under 35 USC 111(a)

Payment information:

Submitted with Payment	yes
Payment Type	CARD
Payment was successfully received in RAM	$1200
RAM confirmation Number	E20231GE35494040
Deposit Account	
Authorized User	
The Director of the USPTO is hereby authorized to charge indicated fees and credit any overpayment as follows:	

File Listing:

Document Number	Document Description	File Name	File Size(Bytes)/ Message Digest	Multi Part /.zip	Pages (if appl.)
1	Issue Fee Payment (PTO-85B)	Issue_Fee_Transmittal.pdf	119355 a03a2e0bc4e7e1cbba405384c2be9c3bf0bc14de	no	1
Warnings:					
Information:					
2	Fee Worksheet (SB06)	fee-info.pdf	38078 483e77212d17c69eb685832b65511c6f3b74223d	no	2
Warnings:					
Information:					
		Total Files Size (in bytes):	157433		

This Acknowledgement Receipt evidences receipt on the noted date by the USPTO of the indicated documents, characterized by the applicant, and including page counts, where applicable. It serves as evidence of receipt similar to a Post Card, as described in MPEP 503.

New Applications Under 35 U.S.C. 111

If a new application is being filed and the application includes the necessary components for a filing date (see 37 CFR 1.53(b)-(d) and MPEP 506), a Filing Receipt (37 CFR 1.54) will be issued in due course and the date shown on this Acknowledgement Receipt will establish the filing date of the application.

National Stage of an International Application under 35 U.S.C. 371

If a timely submission to enter the national stage of an international application is compliant with the conditions of 35 U.S.C. 371 and other applicable requirements a Form PCT/DO/EO/903 indicating acceptance of the application as a national stage submission under 35 U.S.C. 371 will be issued in addition to the Filing Receipt, in due course.

New International Application Filed with the USPTO as a Receiving Office

If a new international application is being filed and the international application includes the necessary components for an international filing date (see PCT Article 11 and MPEP 1810), a Notification of the International Application Number and of the International Filing Date (Form PCT/RO/105) will be issued in due course, subject to prescriptions concerning national security, and the date shown on this Acknowledgement Receipt will establish the international filing date of the application.

PTO/SB/08A (04-03)
Approved for use through 04/30/2003. OMB 0651-0031
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number

Substitute for Form 1449/PTO	*Complete if Known*	
INFORMATION DISCLOSURE STATEMENT BY APPLICANT (Use as many sheets as necessary)	Application Number	
	Filing Date	
	First Named Inventor	Ulrich KASTNER-JUNG
	Art Unit	
	Examiner Name	
Sheet 1 of 4	Attorney Docket No.	5367-694PCON2/474410

U.S. PATENT DOCUMENTS

Examiner Initials*	Cite No. [1]	Document Number Number-Kind-Code [2] (if known)	Publication Date MM-DD-YYYY	Name of Patentee or Applicant of Cited Document	Pages, Columns, Lines, Where Relevant Passages or Relevant Figures Appear
		US-2007/0278937	12-06-2007	Forrest et al.	
		US-2003/0064540	04-03-2003	Auch et al.	
		US-7,280,439	10-09-2007	Shaddox	
		US-2003/0231495	12-18-2003	Searfoss, III	
		US-6,236,622	05-22-2001	Blackman	
		US-2008/0219013	09-11-2008	Budinger et al.	
		US-7,317,210	01-08-2008	~~Osram Opto Semiconductors GmbH~~	Brabec et al.
Change(s) applied to document, /J.G./ 10/25/2022		US-2009/0039272	02-12-2009	~~Osram Opto Semiconductors GmbH~~	Krummacher et al.
		US-7,922,358	04-12-2011	~~Osram Opto Semiconductors GmbH~~	von Malm
		US-2001/0052752	12-2001	Ghosh	
		US-2002/0125822	09-2002	Graff	
		US-2002/0167270	11-2002	Siwinski	
		US-2003/0071804	04-2003	Yamazaki	
		US-2003/0121767	07-2003	Caldwell	
		US-2003/0175553	09-2003	Thompson	
		US-2003/0222577	12-2003	Lu	
		US-2004/0113542	06-2004	Hsiao	
		US-2005/0099824	05-2005	Dowling	
		US-2006/0049381	03-2006	Klein	
		US-2007/0278937	12-2007	Forrest	
		US-2008/0248191	10-2008	Daniels	
		US-2010/0157585	06-2010	Diekmann	
		US-2012/0258294	10-2012	Leyder	
		US-5,734,225	03-1998	Biebuyck et al.	
		US-5,895,228	04-1999	Biebuyck	
		US-7,733,008	06-08-2010	~~Agency for Science Tech. & Research~~	Ke et al.
		US-2005/0231101	10-20-2005	Chen	
		US-2001/0043046	11-22-2001	Fukunaga	
		US-2007/0114520	05-24-2007	~~Osram Opto Seminconductors GmbH~~	Garditz et al.
		US-2007/0230211	10-04-2007	~~Canon KK~~	Osato et al.
		US-2009/0072711	03-19-2009	~~Thomson Licensing~~	Cina et al.
		US-7,560,727	07-14-2009	Ishikawa	

Examiner Signature	/TUNG X LE/	Date Considered	10/19/2022

*EXAMINER: Initial if reference considered, whether or not citation is in conformance with MPEP 609. Draw line through citation if not in conformance and not considered. Include copy of this form with next communication to applicant. [1] Applicant's unique citation designation number (optional). [2] See Kinds Codes of USPTO Patent Documents at www.uspto.gov or MPEP 901.04. [3] Enter Office that issued the document, by the two-letter code (WIPO Standard ST.3). [4] For Japanese patent documents, the indication of the year of the reign of the Emperor must precede the serial number of the patent document. [5] Kind of document by the appropriate symbols as indicated on the document under WIPO Standard ST. 16 if possible. [6] Applicant is to place a check mark here if English language Translation is attached. This collection of information is required by 37 CFR 1.97 and 1.98. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, Washington, DC 20231.**

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /T.X.L/

UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	ISSUE DATE	PATENT NO.	ATTORNEY DOCKET NO.	CONFIRMATION NO.
16/790,198	02/21/2023	11585504	PICTIV 3.3F-001 CC [2]	1309

175540 7590 02/01/2023

Botos Churchill IP Law LLP
430 Mountain Avenue
Suite 401
New Providence, NJ 07974

ISSUE NOTIFICATION

The projected patent number and issue date are specified above.

Determination of Patent Term Adjustment under 35 U.S.C. 154 (b)
(application filed on or after May 29, 2000)

The Patent Term Adjustment is 2 day(s). Any patent to issue from the above-identified application will include an indication of the adjustment on the front page.

If a Continued Prosecution Application (CPA) was filed in the above-identified application, the filing date that determines Patent Term Adjustment is the filing date of the most recent CPA.

Applicant will be able to obtain more detailed information by accessing the Patent Application Information Retrieval (PAIR) WEB site (http://pair.uspto.gov).

Any questions regarding the Patent Term Extension or Adjustment determination should be directed to the Office of Patent Legal Administration at (571)-272-7702. Questions relating to issue and publication fee payments should be directed to the Application Assistance Unit (AAU) of the Office of Patents Stakeholder Experience (OPSE), Stakeholder Support Division (SSD) at (571)-272-4200.

INVENTOR(s) (Please see PAIR WEB site http://pair.uspto.gov for additional inventors):

Ulrich KASTNER-JUNG, Munich, GERMANY;
Markus KLEIN, Tegernheim, GERMANY;
Stan MAES, Dilsen-Stokken, BELGIUM;
Romana SIGL, Salzburg, AUSTRIA;
Annette HAID, Salzburg, AUSTRIA;

APPLICANT(s) (Please see PAIR WEB site http://pair.uspto.gov for additional applicants):

PICTIVA DISPLAYS INTERNATIONAL LIMITED, Dublin, IRELAND;

The United States represents the largest, most dynamic marketplace in the world and is an unparalleled location for business investment, innovation, and commercialization of new technologies. The USA offers tremendous resources and advantages for those who invest and manufacture goods here. Through SelectUSA, our nation works to encourage and facilitate business investment. To learn more about why the USA is the best country in the world to develop technology, manufacture products, and grow your business, visit SelectUSA.gov.