

(12) **United States Patent**
Conrad

(10) **Patent No.:** **US 11,903,546 B2**
(45) **Date of Patent:** **Feb. 20, 2024**

(54) **SURFACE CLEANING APPARATUS**

(71) Applicant: **Wayne Ernest Conrad**, Hampton (CA)

(72) Inventor: **Wayne Ernest Conrad**, Hampton (CA)

(73) Assignee: **Omachron Intellectual Property Inc.**, Hampton (CA)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **17/830,529**

(22) Filed: **Jun. 2, 2022**

(65) **Prior Publication Data**

US 2022/0287520 A1 Sep. 15, 2022

Related U.S. Application Data

(60) Continuation of application No. 17/351,943, filed on Jun. 18, 2021, which is a continuation-in-part of (Continued)

(51) **Int. Cl.**
A47L 5/22 (2006.01)
A47L 5/24 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC *A47L 5/225* (2013.01); *A47L 5/24* (2013.01); *A47L 5/28* (2013.01); *A47L 9/16* (2013.01); *A47L 9/1608* (2013.01); *A47L 9/1625* (2013.01); *A47L 9/1641* (2013.01); *A47L 9/1683* (2013.01); *A47L 9/1691* (2013.01); *A47L 9/322* (2013.01); *A47L 9/325* (2013.01)

(58) **Field of Classification Search**
CPC ... *A47L 5/225*; *A47L 5/24*; *A47L 5/28*; *A47L*

9/16; *A47L 9/1608*; *A47L 9/1625*; *A47L 9/1641*; *A47L 9/1683*; *A47L 9/1691*; *A47L 9/322*; *A47L 9/325*; *A47L 9/106*; *A47L 9/122*

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,600,762 A 9/1926 Hawley
1,797,812 A 3/1931 Waring
(Continued)

FOREIGN PATENT DOCUMENTS

AU 112778 S 11/1991
CA 1077412 A1 5/1980
(Continued)

OTHER PUBLICATIONS

English machine translation of KR101832328B1, published on Feb. 26, 2019.

(Continued)


Primary Examiner — David Redding

(74) *Attorney, Agent, or Firm* — Philip C. Mendes da Costa; BERESKIN & PARR LLP/S.E.N.C.R.L., .s.r.l.

(57) **ABSTRACT**

A surface cleaning apparatus comprises a hand vacuum cleaner, a surface cleaning head and a rigid air flow conduit removably mountable between the surface cleaning head air outlet and the dirty air inlet of the hand vacuum cleaner. The hand vacuum cleaner comprises a main body and a cyclone unit. The cyclone axis of rotation intersects the pistol grip handle. The cyclone axis of rotation is generally horizontal.

15 Claims, 140 Drawing Sheets



Related U.S. Application Data

application No. 16/590,972, filed on Oct. 2, 2019, now Pat. No. 11,389,038, which is a division of application No. 16/156,006, filed on Oct. 10, 2018, now Pat. No. 10,478,030, which is a continuation of application No. 15/088,876, filed on Apr. 1, 2016, now Pat. No. 10,219,662, which is a continuation of application No. 14/822,211, filed on Aug. 10, 2015, now Pat. No. 9,888,817.

(60) Provisional application No. 62/093,189, filed on Dec. 17, 2014.

(51) Int. Cl.

A47L 9/16 (2006.01)

A47L 9/32 (2006.01)

A47L 5/28 (2006.01)

(56) References Cited**U.S. PATENT DOCUMENTS**

1,898,608	A	2/1933	Alexander	4,803,753	A	2/1989	Palmer
1,937,765	A	12/1933	Leathers	4,826,515	A	5/1989	Dyson
2,152,114	A	3/1939	Tongeren	D303,173	S	8/1989	Miyamoto et al.
2,542,634	A	2/1951	Davis et al.	4,853,008	A	8/1989	Dyson
2,678,110	A	5/1954	Madsen	4,853,011	A	8/1989	Dyson
2,731,102	A	1/1956	James	4,853,111	A	8/1989	Macarthur et al.
2,811,219	A	10/1957	Wenzl	4,905,342	A	3/1990	Ataka
2,846,024	A	8/1958	Bremi	4,944,780	A	7/1990	Usmani
2,913,111	A	11/1959	Rogers	4,980,945	A	1/1991	Bewley
2,917,131	A	12/1959	Evans	5,054,157	A	10/1991	Werner et al.
2,937,713	A	5/1960	Stephenson et al.	5,078,761	A	1/1992	Dyson
2,942,691	A	6/1960	Dillon	5,080,697	A	1/1992	Finke
2,942,692	A	6/1960	Benz	5,090,976	A	2/1992	Dyson
2,946,451	A	7/1960	Culleton	5,129,125	A	7/1992	Gamou et al.
2,952,330	A	9/1960	Winslow	5,224,238	A	7/1993	Bartlett
2,981,369	A	4/1961	Yellott et al.	5,230,722	A	7/1993	Yonkers
3,032,954	A	5/1962	Racklyeft	5,254,019	A	10/1993	Noschese
3,085,221	A	4/1963	Kelly	5,267,371	A	12/1993	Soler et al.
3,130,157	A	4/1964	Kelsall et al.	5,287,591	A	2/1994	Rench et al.
3,200,568	A	8/1965	Mcneil	5,307,538	A	5/1994	Rench et al.
3,204,772	A	9/1965	Ruxton	5,309,600	A	5/1994	Weaver et al.
3,217,469	A	11/1965	Eckert	5,309,601	A	5/1994	Hampton et al.
3,269,097	A	8/1966	German	5,347,679	A	9/1994	Saunders et al.
3,320,727	A	5/1967	Farley et al.	5,363,535	A	11/1994	Rench et al.
3,372,532	A	3/1968	Campbell	5,481,780	A	1/1996	Daneshvar
3,426,513	A	2/1969	Bauer	5,515,573	A	5/1996	Frey
3,518,815	A	7/1970	Mcfarland et al.	5,599,365	A	2/1997	Alday et al.
3,530,649	A	9/1970	Porsch et al.	D380,033	S	6/1997	Theiss et al.
3,543,325	A	12/1970	Hamrick	5,709,007	A	1/1998	Chiang
3,561,824	A	2/1971	Homan	5,755,096	A	5/1998	Holleyman
3,582,616	A	6/1971	Wrob	5,815,878	A	10/1998	Murakami et al.
3,675,401	A	7/1972	Cordes	5,815,881	A	10/1998	Sjogreen
3,684,093	A	8/1972	Kono et al.	5,858,038	A	1/1999	Dyson et al.
3,822,533	A	7/1974	Oranje	5,858,043	A	1/1999	Geise
3,898,068	A	8/1975	Mcneil	5,893,938	A	4/1999	Dyson et al.
3,933,450	A	1/1976	Percevault	5,935,279	A	8/1999	Kilstrom
3,988,132	A	10/1976	Oranje	5,950,274	A	9/1999	Kilstrom
3,988,133	A	10/1976	Schady	5,970,572	A	10/1999	Thomas
4,097,381	A	6/1978	Ritzler	6,071,095	A	6/2000	Verkaart
4,187,088	A	2/1980	Hodgson	6,071,321	A	6/2000	Trapp et al.
4,218,805	A	8/1980	Brazier	6,080,022	A	6/2000	Shaberman et al.
4,236,903	A	12/1980	Malmsten	6,122,796	A	9/2000	Downham et al.
4,307,485	A	12/1981	Dessig, III	6,210,469	B1	4/2001	Tokar
4,373,228	A	2/1983	Dyson	6,221,134	B1	4/2001	Conrad et al.
4,382,804	A	5/1983	Mellor	6,228,260	B1	5/2001	Conrad et al.
4,409,008	A	10/1983	Solymes	6,231,645	B1	5/2001	Conrad et al.
4,486,207	A	12/1984	Baillie	6,251,296	B1	6/2001	Conrad et al.
4,494,270	A	1/1985	Ritzau et al.	6,260,234	B1	7/2001	Wright et al.
4,523,936	A	6/1985	Disanza, Jr.	6,345,408	B1	2/2002	Nagai et al.
4,678,588	A	7/1987	Shortt	6,406,505	B1	6/2002	Oh et al.
4,700,429	A	10/1987	Martin et al.	6,434,785	B1	8/2002	Vandenbelt et al.
4,744,958	A	5/1988	Pircon	6,440,197	B1	8/2002	Conrad et al.
4,778,494	A	10/1988	Patterson	6,502,278	B2	1/2003	Oh et al.
				6,519,810	B2	2/2003	Kim
				6,531,066	B1	3/2003	Saunders et al.
				6,553,612	B1	4/2003	Dyson et al.
				6,553,613	B2	4/2003	Onishi et al.
				6,560,818	B1	5/2003	Hasko
				6,581,239	B1	6/2003	Dyson et al.
				6,599,338	B2	7/2003	Oh et al.
				6,599,350	B1	7/2003	Rockwell et al.
				6,613,316	B2	9/2003	Sun et al.
				6,623,539	B2	9/2003	Lee et al.
				6,625,845	B2	9/2003	Matsumoto et al.
				6,640,385	B2	11/2003	Oh et al.
				6,648,934	B2	11/2003	Choi et al.
				6,712,868	B2	3/2004	Murphy et al.
				6,732,403	B2	5/2004	Moore et al.
				6,746,500	B1	6/2004	Park et al.
				6,766,558	B1	7/2004	Matsumoto et al.
				6,782,583	B2	8/2004	Oh
				6,782,585	B1	8/2004	Conrad et al.
				6,810,558	B2	11/2004	Lee
				6,818,036	B1	11/2004	Seaman
				6,833,015	B2	12/2004	Oh et al.
				6,868,578	B1	3/2005	Kasper et al.
				6,874,197	B1	4/2005	Conrad et al.
				6,896,719	B2	5/2005	Coates et al.
				6,929,516	B2	8/2005	Brochu et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,968,596 B2	11/2005	Oh et al.	11,357,374 B2	6/2022	Cho et al.
6,976,885 B2	12/2005	Lord	11,363,928 B2	6/2022	Kim et al.
7,113,847 B2	9/2006	Chmura et al.	11,382,471 B2	7/2022	Kim et al.
7,128,770 B2	10/2006	Oh et al.	2002/0011050 A1	1/2002	Hansen et al.
7,160,346 B2	1/2007	Park	2002/0011053 A1	1/2002	Oh
7,162,770 B2	1/2007	Davidshofer	2002/0062531 A1	5/2002	Oh
7,175,682 B2	2/2007	Nakai et al.	2002/0088208 A1	7/2002	Lukac et al.
7,198,656 B2	4/2007	Maeda et al.	2002/0112315 A1	8/2002	Conrad
7,222,393 B2	5/2007	Kaffenberger et al.	2002/0134059 A1	9/2002	Oh
7,272,872 B2	9/2007	Choi	2002/0134238 A1	9/2002	Conrad et al.
7,278,181 B2	10/2007	Harris et al.	2002/0178535 A1	12/2002	Oh et al.
7,341,611 B2	3/2008	Greene et al.	2002/0178698 A1	12/2002	Oh et al.
7,354,468 B2	4/2008	Arnold et al.	2002/0178699 A1	12/2002	Oh
7,370,387 B2	5/2008	Walker et al.	2003/0037403 A1	2/2003	Lang
7,377,007 B2	5/2008	Best	2003/0046910 A1	3/2003	Lee et al.
7,377,953 B2	5/2008	Oh	2003/0066273 A1	4/2003	Choi et al.
7,386,915 B2	6/2008	Blocker et al.	2003/0106180 A1	6/2003	Tsen
7,395,579 B2	7/2008	Oh	2003/0159238 A1	8/2003	Oh
7,426,768 B2	9/2008	Peterson et al.	2003/0159411 A1	8/2003	Hansen et al.
7,429,284 B2	9/2008	Oh et al.	2003/0200736 A1	10/2003	Ni
7,448,363 B1	11/2008	Rasmussen et al.	2004/0010885 A1	1/2004	Hitzelberger et al.
7,449,040 B2	11/2008	Conrad et al.	2004/0025285 A1	2/2004	Mccormick et al.
7,485,164 B2	2/2009	Jeong et al.	2004/0045126 A1	3/2004	Parker et al.
7,488,363 B2	2/2009	Jeong et al.	2004/0216264 A1	11/2004	Shaver et al.
7,547,337 B2	6/2009	Oh et al.	2005/0081321 A1	4/2005	Milligan et al.
7,547,338 B2	6/2009	Kim et al.	2005/0115409 A1	6/2005	Conrad
7,563,298 B2	7/2009	Oh	2005/0132528 A1	6/2005	Yau
7,565,853 B2	7/2009	Arnold et al.	2005/0198769 A1	9/2005	Lee et al.
7,588,616 B2	9/2009	Conrad et al.	2005/0198770 A1	9/2005	Jung et al.
7,597,730 B2	10/2009	Yoo et al.	2005/0252179 A1	11/2005	Oh et al.
7,628,831 B2	12/2009	Gomiciaga-Pereda et al.	2005/0252180 A1	11/2005	Oh et al.
7,691,161 B2	4/2010	Oh et al.	2006/0037172 A1	2/2006	Choi
7,717,973 B2	5/2010	Oh et al.	2006/0042206 A1	3/2006	Arnold et al.
7,740,676 B2	6/2010	Burnham et al.	2006/0090290 A1	5/2006	Lau
7,770,256 B1	8/2010	Fester	2006/0123590 A1	6/2006	Fester et al.
7,776,120 B2	8/2010	Conrad	2006/0137304 A1	6/2006	Jeong et al.
7,779,506 B2	8/2010	Kang et al.	2006/0137306 A1	6/2006	Jeong et al.
7,803,207 B2	9/2010	Conrad	2006/0137309 A1	6/2006	Jeong et al.
7,805,804 B2	10/2010	Loebig	2006/0137314 A1	6/2006	Conrad et al.
7,811,349 B2	10/2010	Nguyen	2006/0156508 A1	7/2006	Khalil
7,867,308 B2	1/2011	Conrad	2006/0162298 A1	7/2006	Oh et al.
7,882,593 B2	2/2011	Beskow et al.	2006/0162299 A1	7/2006	North
7,922,794 B2	4/2011	Morphey	2006/0168922 A1	8/2006	Oh
7,931,716 B2	4/2011	Oakham	2006/0168923 A1	8/2006	Lee et al.
7,938,871 B2	5/2011	Lloyd	2006/0207055 A1	9/2006	Ivarsson et al.
7,958,598 B2	6/2011	Hwang et al.	2006/0207231 A1	9/2006	Arnold
7,979,959 B2	7/2011	Courtney	2006/0230715 A1	10/2006	Oh et al.
7,996,956 B2	8/2011	Wood et al.	2006/0230723 A1	10/2006	Kim et al.
8,021,453 B2	9/2011	Howes	2006/0230724 A1	10/2006	Han et al.
8,062,398 B2	11/2011	Luo et al.	2006/0236663 A1	10/2006	Oh
8,100,999 B2	1/2012	Ashbee et al.	2006/0254226 A1	11/2006	Jeon
8,101,001 B2	1/2012	Qian	2006/0277711 A1	12/2006	Hong et al.
8,117,712 B2	2/2012	Dyson et al.	2006/0278081 A1	12/2006	Han et al.
8,146,201 B2	4/2012	Conrad	2006/0288516 A1	12/2006	Sawalski
8,151,407 B2	4/2012	Conrad	2007/0067944 A1	3/2007	Kitamura et al.
8,152,877 B2	4/2012	Greene	2007/0077810 A1	4/2007	Gogel et al.
8,156,609 B2	4/2012	Milne et al.	2007/0079473 A1	4/2007	Min et al.
8,161,599 B2	4/2012	Griffith et al.	2007/0079585 A1	4/2007	Oh et al.
8,225,456 B2	7/2012	Hkan et al.	2007/0095028 A1	5/2007	Kim et al.
8,484,799 B2	7/2013	Conrad	2007/0095029 A1	5/2007	Min et al.
8,673,487 B2	3/2014	Churchill	2007/0136984 A1	6/2007	Hsu
8,869,344 B2	10/2014	Conrad	2007/0209334 A1	9/2007	Conrad
9,192,269 B2	11/2015	Conrad	2007/0209335 A1	9/2007	Conrad
9,516,979 B2	12/2016	Gidwell	2007/0271724 A1	11/2007	Hakan et al.
9,675,218 B2	6/2017	Kim et al.	2007/0289089 A1	12/2007	Yacobi
9,711,986 B2	7/2017	Sunderland et al.	2007/0289266 A1	12/2007	Oh
10,219,662 B2 *	3/2019	Conrad A47L 9/1683	2008/0040883 A1	2/2008	Beskow et al.
10,299,651 B2	5/2019	Kim et al.	2008/0134460 A1	6/2008	Conrad
10,405,719 B2	9/2019	Kim et al.	2008/0134462 A1	6/2008	Jansen et al.
10,561,291 B2	2/2020	Kim et al.	2008/0178416 A1	7/2008	Conrad
10,610,075 B2	4/2020	Kim et al.	2008/0178420 A1	7/2008	Conrad
10,660,493 B2	5/2020	Kim et al.	2008/0190080 A1	8/2008	Oh et al.
10,959,589 B2	3/2021	Kim et al.	2008/0196194 A1	8/2008	Conrad
10,973,380 B2	4/2021	Seo et al.	2008/0196745 A1	8/2008	Conrad
11,229,339 B2	1/2022	Cho et al.	2008/0301903 A1	12/2008	Cunningham et al.
			2009/0100633 A1	4/2009	Bates et al.
			2009/0113659 A1	5/2009	Jeon et al.
			2009/0144932 A1	6/2009	Yoo
			2009/0165431 A1	7/2009	Oh

(56)	References Cited			CN	105816104	A	8/2016
	U.S. PATENT DOCUMENTS			CN	205671986	U	11/2016
				CN	107343774		11/2017
				CN	108024674		5/2018
2009/0205160	A1	8/2009	Conrad	CN	211459996	U	9/2020
2009/0205161	A1	8/2009	Conrad	CN	212307697	U	1/2021
2009/0205298	A1	8/2009	Hyun et al.	DE	875134	C	4/1953
2009/0209666	A1	8/2009	Hellberg et al.	DE	9216071	U1	2/1993
2009/0265877	A1	10/2009	Dyson et al.	DE	4232382	C1	3/1994
2009/0282639	A1	11/2009	Dyson et al.	DE	10056935	C2	1/2003
2009/0300874	A1	12/2009	Tran et al.	DE	69907201	T2	5/2003
2009/0300875	A1	12/2009	Inge et al.	DE	60201666	T2	6/2006
2009/0307564	A1	12/2009	Vedantham et al.	DE	60211663	T2	5/2007
2009/0307863	A1	12/2009	Milne et al.	DE	102007011457	A1	10/2007
2009/0307864	A1	12/2009	Dyson	DE	112010001135	T5	8/2012
2009/0308254	A1	12/2009	Oakham	DE	102012211246	A1	1/2014
2009/0313958	A1	12/2009	Gomiciaga-Pereda et al.	EP	493950	B1	4/1998
2009/0313959	A1	12/2009	Gomiciaga-Pereda et al.	EP	1200196	B1	6/2005
2010/0083459	A1	4/2010	Beskow et al.	EP	1815777	A1	8/2007
2010/0132319	A1	6/2010	Ashbee et al.	EP	1594386	B1	4/2009
2010/0154150	A1	6/2010	McLeod	EP	1676516	B1	1/2010
2010/0175217	A1	7/2010	Conrad	EP	1629758	A3	2/2010
2010/0212104	A1	8/2010	Conrad	EP	2308360	A2	4/2011
2010/0224073	A1	9/2010	Oh et al.	EP	1779761	B1	6/2013
2010/0229321	A1	9/2010	Dyson et al.	EP	2848173	A1	3/2015
2010/0229324	A1	9/2010	Conrad	FR	2812531	B1	11/2004
2010/0229328	A1	9/2010	Conrad	GB	700791	A	12/1953
2010/0242210	A1	9/2010	Conrad	GB	1111074	A	4/1968
2010/0243158	A1	9/2010	Conrad	GB	2035787	B	10/1982
2010/0293745	A1	11/2010	Coburn	GB	2163703	B	1/1988
2010/0299865	A1	12/2010	Conrad	GB	2268875	A	1/1994
2010/0299866	A1	12/2010	Conrad	GB	2307849	A	6/1997
2011/0023261	A1	2/2011	Proffitt, II et al.	GB	2282979	B	10/1997
2011/0146024	A1	6/2011	Conrad	GB	2365324	B	7/2002
2011/0168332	A1	7/2011	Bowe et al.	GB	2440111	A	1/2008
2011/0219576	A1	9/2011	Conrad	GB	2465781	A	6/2010
2011/0289719	A1	12/2011	Han et al.	GB	2441962	B	3/2011
2012/0023701	A1	2/2012	Lenkiewicz et al.	GB	2466290	B	10/2012
2012/0030896	A1	2/2012	Crouch et al.	GB	2508035	A	5/2014
2012/0060322	A1	3/2012	Simonelli et al.	GB	2508035	B	3/2015
2012/0079671	A1	4/2012	Stickney et al.	JP	61131720	A	6/1986
2012/0216361	A1	8/2012	Millington et al.	JP	2000140533	A	5/2000
2012/0222245	A1	9/2012	Conrad	JP	2002085297	A	3/2002
2012/0222260	A1	9/2012	Conrad	JP	2003135335	A	5/2003
2012/0222262	A1	9/2012	Conrad	JP	2005040246	A	2/2005
2013/0160232	A1	6/2013	Peace	JP	2006102034	A	4/2006
2014/0137362	A1	5/2014	Smith	JP	2008206613	A	9/2008
2014/0137363	A1	5/2014	Wilson	JP	2009261501	A	11/2009
2014/0137364	A1	5/2014	Stickney et al.	JP	2010081968	A	4/2010
2014/0182080	A1	7/2014	Lee et al.	JP	2010178773	A	8/2010
2014/0208538	A1	7/2014	Visel et al.	JP	2010220632	A	10/2010
2014/0237956	A1	8/2014	Conrad	JP	2011001891	A	1/2011
2015/0135474	A1	5/2015	Gidwell	JP	2011189133	A	9/2011
2015/0230677	A1	8/2015	Andrikanish	JP	2013086228	A	5/2013
2015/0297050	A1	10/2015	Marsh et al.	KR	1020010045598	A	6/2001
2016/0113460	A1	4/2016	Williams et al.	KR	1020020067489	A	8/2002
				KR	1020020085478	A	11/2002
				KR	1020040050174	A	6/2004
				KR	1020060008365	A	1/2006
				KR	1020060118795	A	11/2006
CA	1218962	A1	3/1987	KR	1020060118800	A	11/2006
CA	2450450	A1	12/2004	KR	1020060118802	A	11/2006
CA	2484587	A1	4/2005	KR	1020060118803	A	11/2006
CA	2438079	C	8/2009	KR	1020060122249	A	11/2006
CA	2658014	A1	9/2010	KR	1020060125952	A	12/2006
CA	2659212	A1	9/2010	KR	1020060125954	A	12/2006
CN	1336154	A	2/2002	KR	1020100084127	A	7/2010
CN	1434688	A	8/2003	KR	1020170126377	A	11/2017
CN	1493244	A	5/2004	KR	1020170126378	A	11/2017
CN	1875846	A	12/2006	KR	1020170126379	A	11/2017
CN	1875855	A	12/2006	KR	1020170126380	A	11/2017
CN	1887437	A	1/2007	KR	101832328	B1	2/2018
CN	101061932	A	10/2007	KR	101952658	B1	2/2019
CN	101108110	A	1/2008	KR	101968588	B1	4/2019
CN	201290642	Y	8/2009	KR	102405363	B1	6/2022
CN	101108081	B	10/2010	WO	8002561	A1	11/1980
CN	101108106	B	7/2012	WO	9627446	A1	9/1996
CN	202739907	U	2/2013	WO	9720492	A1	6/1997
CN	202932850	U	5/2013	WO	9809121	A1	3/1998
CN	204363891	U	6/2015				

FOREIGN PATENT DOCUMENTS

(56)

References Cited**FOREIGN PATENT DOCUMENTS**

WO	9843721	A1	10/1998
WO	0107168	A1	2/2001
WO	0147247	A3	11/2001
WO	0217766	A3	2/2003
WO	2004069021	A1	8/2004
WO	2006076363	A2	7/2006
WO	2006026414	A3	8/2007
WO	2007104238	A1	9/2007
WO	2008009883	A1	1/2008
WO	2008009888	A1	1/2008
WO	2008009890	A1	1/2008
WO	2008009891	A1	1/2008
WO	2008035032	A2	3/2008
WO	2008070973	A1	6/2008
WO	2008088278	A2	7/2008
WO	2008135708	A1	11/2008
WO	2009026709	A1	3/2009
WO	2010102396	A1	9/2010
WO	2010142968	A1	12/2010
WO	2010142969	A1	12/2010
WO	2010142970	A1	12/2010
WO	2010142971	A1	12/2010
WO	2011054106	A1	5/2011
WO	2012042240	A1	4/2012
WO	2012117231	A1	9/2012
WO	2015129387	A1	9/2015
WO	2016065151	A1	4/2016
WO	2017046557	A1	3/2017
WO	2017046559	A1	3/2017
WO	2017046560	A1	3/2017
WO	2017196004	A1	11/2017
WO	2017196028	A1	11/2017

OTHER PUBLICATIONS

English machine translation of KR101968588B1, published on Apr. 15, 2019.

English machine translation of KR101952658B1, published on Feb. 27, 2019.

English machine translation of KR1020170126380A, published on Nov. 17, 2017.

English machine translation of KR1020170126379A, published on Nov. 17, 2017.

English machine translation of KR1020170126378A, published on Nov. 17, 2017.

English machine translation of KR1020170126377A, published on Nov. 17, 2017.

English machine translation of KR102405363B1, published on Jun. 7, 2022.

International Preliminary Report on Patentability, received in connection to PCT/CA2015/051332, dated Jun. 29, 2017.

Espacenet: English machine translation of CN212307697U, published on Jan. 8, 2021.

Espacenet: English machine translation of CN211459996U, published on Sep. 11, 2020.

Espacenet: English machine translation of CN108024674A, published on May 11, 2018.

Google Patents: English machine translation of CN107343774, published on Nov. 14, 2017.

English machine translation of KR1020100084127, published on Jul. 23, 2010.

English machine translation of KR1020060125954., published on Dec. 7, 2006.

English machine translation of KR1020060125952, published on Dec. 7, 2006.

English machine translation of KR1020060122249, published on Nov. 30, 2006.

English machine Translation of KR1020060118803, published on Nov. 24, 2006.

English machine translation of KR1020060118802, published on Nov. 24, 2006.

English machine translation of KR1020060118800, published on Nov. 24, 2006.

English machine translation of KR1020060118795, published on Nov. 24, 2006.

English machine translation of KR1020060008365, published on Jan. 26, 2006.

English machine translation of KR1020040050174, published on Jun. 16, 2004.

English machine translation of KR1020020085478, published on Nov. 16, 2002.

English machine translation of KR1020020067489, published on Aug. 22, 2002.

English machine translation of KR1020010045598, published on Jun. 5, 2001.

English machine translation of JP2013086228, published on May 13, 2013.

English machine translation of JP2011189133, published on Sep. 29, 2011.

English machine translation of JP2011001891, published on Jan. 6, 2011.

English machine translation of JP2010220632, published on Oct. 7, 2010.

English machine translation of JP 2010178773, published on Aug. 19, 2010.

English machine translation of JP2010081968, published on Apr. 15, 2010.

English machine translation of JP2009261501, published on Nov. 12, 2009.

English machine translation of JP2008206613, published on Sep. 11, 2008.

English machine translation of JP2006102034, published on Apr. 20, 2006.

English machine translation of JP2005040246, published on Feb. 17, 2005.

English machine translation of JP2003135335, published on May 13, 2003.

English machine translation of JP2002085297, published on Mar. 26, 2002.

English machine translation of JP2000140533, published on May 23, 2000.

English machine translation of JP61131720, published on Jun. 19, 1986.

English machine translation of JP2508035, published on May 21, 2014.

English machine translation of DE102012211246A1, published on Jan. 2, 2014.

English machine translation of DE102007011457, published on Oct. 25, 2007.

English machine translation of CN205671986, published on Nov. 9, 2016.

English machine translation of CN204363891, published on Jun. 3, 2005.

English machine translation of CN202932850, published on May 15, 2013.

English machine translation of CN202739907, published on Feb. 20, 2013.

English machine translation of CN201290642Y, published on Aug. 19, 2009.

English machine translation of CN105816104A, published on Aug. 3, 2016.

English machine translation of CN101108110A, published on Jan. 23, 2008.

English machine translation of CN101108106B, published on Jul. 18, 2012.

English machine translation of CN212307697U, published on Jan. 8, 2021.

English machine translation of CN101108081B, published on Oct. 27, 2010.

English machine translation of CN211459996, published on Sep. 11, 2020.

English machine translation of CN101061932, published on Oct. 31, 2007.

(56)

References Cited

OTHER PUBLICATIONS

English machine translation of DE10056935, published on Jan. 16, 2003.
English machine translation of CN1887437, published on Jan. 3, 2007.
English machine translation of CN1875855, published on Dec. 13, 2006.
English machine translation of CN1875846, published on Dec. 13, 2006.
English machine translation of CN1493244, published on May 5, 2004.
English machine translation of CN1434688, published on Aug. 6, 2003.
English machine translation of DE112010001135T5, published on Aug. 2, 2012.
English machine translation of DE9216071, published on Feb. 25, 1993.
English machine translation of DE69907201, published on May 28, 2003.
English machine translation of DE60211663, published on May 10, 2007.
English machine translation of DE60201666, published on Jun. 1, 2006.
English machine translation of DE4232382, published on Mar. 24, 1994.
English machine translation of FR2812531, published on Nov. 5, 2004.
English machine translation of DE875134, published on Apr. 30, 1953.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6





FIG. 7








FIG. 9

152

104

FIG. 10








FIG. 12




FIG. 12a






FIG. 13








FIG. 16




FIG. 17

168




FIG. 18

168




FIG. 19





FIG. 20






FIG. 22

136




FIG. 23




FIG. 23a




FIG. 46




FIG. 45




FIG. 24




FIG. 25





FIG. 26






FIG. 30




FIG. 31




FIG. 32




FIG. 33




FIG. 36




FIG. 35




FIG. 34




FIG. 36a





FIG. 37






FIG. 39




FIG. 40




FIG. 41




FIG. 42




FIG. 43





FIG. 44






FIG. 44b




FIG. 47




FIG. 48




FIG. 49





FIG. 50






FIG. 52




FIG. 53




FIG. 54




FIG. 55




FIG. 56





FIG. 57






FIG. 59





FIG. 60







FIG. 62






FIG. 64




FIG. 65




FIG. 66




FIG. 67





FIG. 68








FIG. 70











FIG. 73










FIG. 77




FIG. 78




FIG. 79




FIG. 80




FIG. 81




FIG. 82




FIG. 83




FIG. 84




FIG. 85




FIG. 86

160




FIG. 87

160




FIG. 88




FIG. 89

160




FIG. 90




FIG. 91




FIG. 92




FIG. 93

160




FIG. 94

160




FIG. 95






FIG. 95b

FIG. 95C




FIG. 96




FIG. 97a




FIG. 97b




FIG. 98a




FIG. 98b




FIG. 99




FIG. 100




FIG. 101




FIG. 102




FIG. 103




FIG. 104a




FIG. 104b




FIG. 105a

FIG. 105b




FIG. 106




FIG. 107




FIG. 108




FIG. 109




FIG. 110a




FIG. 110b




FIG. 113




FIG. 112




FIG. 111




FIG. 114




FIG. 115




FIG. 116




FIG. 117




FIG. 118




FIG. 119a




FIG. 119b




FIG. 120




FIG. 121a




FIG. 121b




FIG. 122




FIG. 123




FIG. 124




FIG. 125




FIG. 126





FIG. 127






Fig. 129




Fig. 130




Fig. 131






Fig. 132










Fig. 135



637



1

SURFACE CLEANING APPARATUS

CROSS REFERENCE TO RELATED APPLICATIONS

This application is a continuation of co-pending U.S. patent application Ser. No. 17/351,943, filed on Jun. 18, 2021, which is still pending, which is a continuation-in-part of co-pending U.S. patent application Ser. No. 16/590,972 filed on Oct. 2, 2019, which is a divisional of U.S. patent application Ser. No. 16/156,006 filed on Oct. 10, 2018, now issued as U.S. Pat. No. 10,478,030, which is a continuation of U.S. patent application Ser. No. 15/088,876 filed on Apr. 1, 2016, now issued as U.S. Pat. No. 10,219,662, which is a continuation of U.S. patent application Ser. No. 14/822,211, filed Aug. 10, 2015, now issued as U.S. Pat. No. 9,888,817, which claimed priority from U.S. Provisional Patent Application No. 62/093,189, filed Dec. 17, 2014, the entirety of which are hereby incorporated by reference.

FIELD

This disclosure relates to the field of surface cleaning apparatus. In some aspects, this disclosure relates to a type of stick vacuum cleaner wherein a hand vacuum cleaner is removably mounted to a drive handle and provides motive power to draw dirty air into the surface cleaning head.

INTRODUCTION

Various types of surface cleaning apparatus are known. These include upright vacuum cleaner, stick vacuum cleaners, hand vacuum cleaners and canister vacuum cleaners. Stick vacuum cleaners and hand vacuum cleaners are popular as they tend to be smaller and may be used to clean a small area or when a spill has to be cleaned up. Hand vacuum cleaners or handvacs are advantageous as they are lightweight and permit above floor cleaning and cleaning in hard to reach locations. However, they have a limited dirt collection capacity. Upright vacuum cleaners enable a user to clean a floor and may be have a pod that is removably attached for above floor cleaning. In such cases, the pod comprises, e.g., a cyclone, a dirt collection chamber and the suction motor for the upright vacuum cleaner. However, such the pods tend to be bulky since they comprise the total dirt collection capacity for the upright vacuum cleaner.

SUMMARY

In accordance with one aspect of this disclosure, an air treatment assembly for a surface cleaning apparatus, such as a hand vacuum cleaner has an air treatment chamber (such as a cyclone chamber) and an external dirt collection chamber wherein dirt separated in the air treatment chamber travels to the dirt collection chamber via a dirt outlet of the air treatment chamber. A sidewall of the air treatment chamber separates the air treatment chamber and the dirt collection chamber. An end of the air treatment assembly is openable (e.g., the front end of the air treatment assembly if the air treatment assembly is part of a hand vacuum cleaner). When the openable end is moved to the open position, both the air treatment chamber and the dirt collection chamber are opened and at least a portion of the sidewall separating the air treatment chamber and the dirt collection chamber is moved as part of the openable end. Optionally, a portion of the sidewall that extends to the dirt outlet is opened such that the dirt outlet is also opened when the openable end is

2

moved to the open position is openable. An advantage of this design is that the air treatment chamber and the dirt collection chamber may be more easily emptied and any debris that may bridge the dirt outlet, and thereby partially or fully block the dirt outlet, may be more easily removed. For example, elongated debris such as hair that may be extend through the dirt outlet and be difficult to dislodge from the dirt outlet may be more easily removed than if only the dirt collection chamber is opened.

In accordance with this aspect, there is provided a hand vacuum cleaner comprising:

- (a) an air flow path extending from a dirty air inlet to a clean air outlet with a suction motor positioned in the air flow path;
- (b) a main body comprising a handle and the suction motor; and,
- (c) a cyclone bin assembly comprising a cyclone chamber positioned in the air flow path and a dirt collection chamber, the cyclone chamber has a cyclone air inlet, a cyclone air outlet, a dirt outlet, a cyclone chamber front end having a cyclone chamber front end wall and a cyclone chamber rear end having a cyclone chamber rear end wall and cyclone axis of rotation that extends between the cyclone chamber front end wall and the cyclone chamber rear end wall, the dirt collection chamber having a dirt collection chamber front end having a dirt collection chamber front end wall and an axially spaced apart dirt collection chamber rear end having dirt collection chamber rear end wall, a portion of the dirt collection chamber is spaced from the cyclone chamber in a direction transverse to the cyclone axis of rotation whereby the portion faces towards the cyclone chamber and is separated from the cyclone chamber by a sidewall, wherein the front end of the cyclone bin assembly comprises at least a portion of the cyclone chamber, at least a portion of the dirt collection chamber and at least a portion of the sidewall, the front end of the cyclone bin assembly is rotationally mounted between a closed position and an open position in which the rear end of the cyclone chamber and the rear end of the dirt collection chamber are opened.

In some embodiments, the dirt outlet may be provided in the sidewall.

In some embodiments, the cyclone air inlet may be provided at the cyclone chamber front end and the cyclone air outlet may be provided at the cyclone chamber rear end.

In some embodiments, the dirt outlet may be provided in the sidewall.

In some embodiments, the dirt outlet may comprise an opening in the sidewall that extends axially inwardly into the cyclone chamber from the cyclone chamber rear end wall.

In some embodiments, the hand vacuum cleaner may further comprise an inlet conduit, the dirty air inlet may be located at an inlet end of the inlet conduit and the inlet conduit may be part of the front end of the cyclone bin assembly.

In some embodiments, the dirt collection chamber front end may be positioned axially forwardly from the cyclone chamber front end whereby the cyclone axis of rotation extends through a portion of the dirt collection chamber that is located axially outwardly from the cyclone chamber front end.

In some embodiments, the front end of the cyclone bin assembly may be rotationally mounted to a rear end of the cyclone bin assembly.

3

In some embodiments, the front end of the cyclone bin assembly may be rotationally mounted at a location of the rear end wall of the cyclone chamber.

In some embodiments, the front end of the cyclone bin assembly may be rotationally mounted to a rear end of the cyclone bin assembly at a location midway along an axial length of the cyclone bin assembly.

In accordance with this aspect, there is also provided a surface cleaning apparatus comprising:

- (a) an air flow path extending from a dirty air inlet to a clean air outlet with a suction motor positioned in the air flow path; and,
- (b) a cyclone bin assembly comprising a cyclone chamber positioned in the air flow path and a dirt collection chamber, the cyclone chamber has a cyclone air inlet, a cyclone air outlet, a dirt outlet, a cyclone chamber first end having a cyclone chamber first end wall, a cyclone chamber second end having a cyclone chamber second end wall and cyclone axis of rotation that extends between the cyclone chamber first end wall and the cyclone chamber second end wall, the dirt collection chamber having a dirt collection chamber first end wall and an axially spaced apart dirt collection chamber second end having dirt collection chamber second end wall, a portion of the dirt collection chamber is spaced from the cyclone chamber in a direction transverse to the cyclone axis of rotation whereby the portion faces towards the cyclone chamber and is separated from the cyclone chamber by a sidewall, wherein the first end of the cyclone bin assembly comprises at least a portion of the cyclone chamber, at least a portion of the dirt collection chamber and at least a portion of the sidewall, the first end of the cyclone bin assembly is rotationally mounted between a closed position and an open position in which the second end of the cyclone chamber and the second end of the dirt collection chamber are opened.

In some embodiments, the dirt outlet may be provided in the sidewall.

In some embodiments, the cyclone air inlet may be provided at the cyclone chamber first end and the cyclone air outlet may be provided at the cyclone chamber second end.

In some embodiments, the dirt outlet may be provided in the sidewall.

In some embodiments, the dirt outlet may comprise an opening in the sidewall that extends axially inwardly into the cyclone chamber from the cyclone chamber second end wall.

In some embodiments, the surface cleaning apparatus may further comprise an inlet conduit, the dirty air inlet may be located at an inlet end of the inlet conduit and the inlet conduit may be part of the first end of the cyclone bin assembly.

In some embodiments, the dirt collection chamber first end may be positioned axially outwardly from the cyclone chamber first end whereby the cyclone axis of rotation extends through a portion of the dirt collection chamber that is located axially outwardly from the cyclone chamber first end.

In some embodiments, the front end of the cyclone bin assembly may be rotationally mounted to a rear end of the cyclone bin assembly.

In some embodiments, the front end of the cyclone bin assembly may be rotationally mounted at a location of the second end wall of the cyclone chamber.

4

In some embodiments, the front end of the cyclone bin assembly may be rotationally mounted to a rear end of the cyclone bin assembly at a location midway along an axial length of the cyclone bin assembly.

DRAWINGS

FIG. 1 is a front perspective view of a surface cleaning apparatus in accordance with at least one embodiment;

FIG. 2 is a rear perspective view of the apparatus of FIG. 1;

FIG. 3 is a side elevation view of the apparatus of FIG. 1;

FIG. 4 is a front perspective view of the apparatus of FIG. 1 with a supplemental dirt collection chamber partially removed;

FIG. 5 is a front perspective view of a surface cleaning apparatus in accordance with another embodiment;

FIG. 6 is a rear perspective view of the apparatus of FIG. 5;

FIG. 7 is a side elevation view of the apparatus of FIG. 5 with an electrical cord bag;

FIG. 8 is a front elevation view of the apparatus of FIG. 5;

FIG. 9 is a rear elevation view of the apparatus of FIG. 5;

FIG. 10 is a top plan view of the apparatus of FIG. 5;

FIG. 11 is a bottom plan view of the apparatus of FIG. 5;

FIG. 12 is an exploded front perspective view of the apparatus of FIG. 5;

FIG. 12a is an exploded front perspective view of an alternate apparatus of FIG. 5;

FIG. 13 is a front perspective view of a surface cleaning apparatus in accordance with another embodiment;

FIG. 14 is a rear perspective view of the apparatus of FIG. 13;

FIG. 15 is a side elevation view of the apparatus of FIG. 13;

FIG. 16 is a front elevation view of the apparatus of FIG. 13;

FIG. 17 is a rear elevation view of the apparatus of FIG. 13;

FIG. 18 is a top plan view of the apparatus of FIG. 13;

FIG. 19 is a bottom plan view of the apparatus of FIG. 13;

FIG. 20 is a front perspective view of the apparatus of FIG. 13 with a supplemental cyclone bin assembly partially removed;

FIG. 21 is a cross-sectional view taken along line 21-21 in FIG. 1;

FIG. 22 is a bottom perspective view of a handvac of the apparatus of FIG. 1;

FIG. 23 is a perspective cross-sectional view of a cyclone bin assembly of the handvac of FIG. 22 transverse to the cyclone axis;

FIG. 23a is a top plan view of the cross-section of FIG. 23;

FIG. 24 is a front perspective view of the supplemental dirt collection chamber of the apparatus of FIG. 1;

FIG. 25 is a cross-sectional view taken along line 25-25 in FIG. 5;

FIG. 26 is a cross-sectional view taken along line 26-26 in FIG. 13;

FIG. 27 is a front perspective view of the apparatus of FIG. 1 in a lightweight upright mode;

FIG. 28 is a rear perspective view of the apparatus of FIG. 1 in the lightweight upright mode of FIG. 27;

FIG. 29 is a side elevation view of the apparatus of FIG. 1 in the lightweight upright mode of FIG. 27;

5

FIG. 30 is a cross-sectional view taken along line 30-30 in FIG. 27;

FIG. 31 is a front perspective view of the apparatus of FIG. 1 in an above-floor cleaning mode;

FIG. 32 is a rear perspective view of the apparatus of FIG. 1 in the above-floor cleaning mode of FIG. 31;

FIG. 33 is a side elevation view of the apparatus of FIG. 1 in the above-floor cleaning mode of FIG. 31;

FIG. 34 is a front perspective view of the apparatus of FIG. 1 in a stair-cleaning mode;

FIG. 35 is a rear perspective view of the apparatus of FIG. 1 in the stair-cleaning mode of FIG. 34;

FIG. 36 is a front elevation view of the apparatus of FIG. 1 in the stair cleaning mode of FIG. 34;

FIG. 36a is a front perspective view of the apparatus of FIG. 5 in an above-floor cleaning mode;

FIG. 37 is a front perspective view of the apparatus of FIG. 13 in a lightweight upright mode;

FIG. 38 is a rear perspective view of the apparatus of FIG. 13 in the lightweight upright mode of FIG. 37;

FIG. 39 is a side elevation view of the apparatus of FIG. 13 in the lightweight upright mode of FIG. 37;

FIG. 40 is a rear elevation view of the apparatus of FIG. 13 in the lightweight upright mode of FIG. 37;

FIG. 41 is a side elevation view of the apparatus of FIG. 13 in the lightweight upright mode of FIG. 37;

FIG. 42 is a top plan view of the apparatus of FIG. 13 in the lightweight upright mode of FIG. 37;

FIG. 43 is a bottom plan view of the apparatus of FIG. 13 in the lightweight upright mode of FIG. 37;

FIG. 44 is a cross-sectional view taken along line 44-44 in FIG. 37;

FIG. 44a is a perspective view of the apparatus of FIG. 13 in an above-floor cleaning mode;

FIG. 44b is another perspective view of the apparatus of FIG. 13 in the above-floor cleaning mode of FIG. 44a;

FIG. 45 is a rear perspective view of the supplemental dirt collection chamber of FIG. 24;

FIG. 46 is a side elevation view of the supplemental dirt collection chamber of FIG. 24;

FIG. 47 is a front perspective view of a surface cleaning apparatus in accordance with another embodiment;

FIG. 48 is a cross-sectional view taken along line 48-48 in FIG. 47;

FIG. 49 is a cross-section view taken along line 49-49 in FIG. 47;

FIG. 50 is a side elevation view of the apparatus of FIG. 47;

FIG. 51 is a front elevation view of the apparatus of FIG. 47;

FIG. 52 is a front perspective view of an upright section of the apparatus of FIG. 13 including a diversion valve in a closed position;

FIG. 53 is a front perspective view of the upright section of FIG. 52 with a cyclone bin assembly seated on a pedal of the diversion valve;

FIG. 54 is a front perspective view of the upright section of FIG. 52 with the cyclone bin assembly connected to a wand, and the diversion valve in the open position;

FIG. 55 is a cross-sectional view taken along line 55-55 in FIG. 52;

FIG. 56 is a cross-sectional view taken along line 56-56 in FIG. 53;

FIG. 57 is a cross-sectional view taken along line 57-57 in FIG. 54;

6

FIG. 58 is a front perspective view of an upright section of the apparatus of FIG. 13 including another diversion valve in a closed position

FIG. 59 is a front perspective view of the upright section of FIG. 58 with the cyclone bin assembly being connected to a wand, and the diversion valve in the closed position;

FIG. 60 is a front perspective view of the upright section of FIG. 58 with the cyclone bin assembly connected to the wand, and the diversion valve in the open position

FIG. 61 is a cross-sectional view taken along line 61-61 in FIG. 58;

FIG. 62 is a cross-sectional view taken along line 62-62 in FIG. 59;

FIG. 63 is a cross-sectional view taken along line 63-63 in FIG. 60;

FIG. 64 is a front perspective view of an upright section of the apparatus of FIG. 13 including another diversion valve in a closed position;

FIG. 65 is a front perspective view of the upright section of FIG. 64 with the diversion valve in a partially opened position;

FIG. 66 is a front perspective view of the upright section of FIG. 64 mounted to the wand with the diversion valve in an open position;

FIG. 67 is a cross-sectional view of the upright section of FIG. 64;

FIG. 68 is another cross-sectional view of the upright section of FIG. 64;

FIG. 69 is an enlarged view of a portion of FIG. 68;

FIG. 70 is a cross-sectional view taken along line 70-70 in FIG. 65;

FIG. 71 is a cross-sectional view taken along line 71-71 in FIG. 66;

FIG. 72 is a front perspective view of an upright section of the apparatus of FIG. 13 with another diversion valve in a closed position;

FIG. 73 is a front perspective view of the upright section of FIG. 72 being connected to the wand and with the diversion valve in a closed position;

FIG. 74 is a front perspective view of the upright section of FIG. 72 connected to the wand and with the diversion valve in an open position;

FIG. 75 is a cross-section view taken along line 75-75 in FIG. 72;

FIG. 76 is a cross-section view taken along line 76-76 in FIG. 73;

FIG. 77 is a cross-section view taken along line 77-77 in FIG. 74;

FIG. 78 is a side elevation view of the handvac of the apparatus of FIG. 1;

FIG. 79 is a side elevation view of the handvac of the apparatus of FIG. 5;

FIG. 80 is a side elevation view of the apparatus of FIG. 5 in an upright storage position with a surface cleaning head having rearwardly deployed wheels;

FIG. 81 is a side elevation view of the apparatus of FIG. 80 in a reclined in-use position with the rear wheels of the surface cleaning head retracted;

FIG. 82 is a front perspective view of the apparatus of FIG. 13 with a cyclone bin assembly in accordance with at least one embodiment;

FIG. 83 is a rear perspective view of the cyclone bin assembly of FIG. 82 in a closed position;

FIG. 84 is a side elevation view of the cyclone bin assembly of FIG. 82 in a closed position;

FIG. 85 is a front elevation view of the cyclone bin assembly of FIG. 82 in a closed position;

7

FIG. 86 is a front elevation view of the cyclone bin assembly of FIG. 82 with a cyclone chamber portion in an open position;

FIG. 87 is a front elevation view of the cyclone bin assembly of FIG. 82 with the cyclone chamber portion and a dirt collection portion in open positions;

FIG. 88 is a top perspective view of the cyclone bin assembly of FIG. 82 with the cyclone chamber portion and the dirt collection portion in open positions;

FIG. 89 is a front perspective view of the cyclone bin assembly of the apparatus of FIG. 13;

FIG. 90 is a rear perspective view of the cyclone bin assembly of FIG. 89;

FIG. 91 is a front elevation view of the cyclone bin assembly of FIG. 89;

FIG. 92 is a rear elevation view of the cyclone bin assembly of FIG. 89;

FIG. 93 is a side elevation view of the cyclone bin assembly of FIG. 89;

FIG. 94 is a top plan view of the cyclone bin assembly of FIG. 89;

FIG. 95 is a bottom plan view of the cyclone bin assembly of FIG. 89;

FIG. 95*b* is a front perspective view of the cyclone bin assembly of FIG. 89 with a bottom portion in an open position;

FIG. 95*c* is a front perspective view of the cyclone bin assembly of FIG. 89 with top and bottom portions in open positions;

FIG. 96 is a cross-sectional view taken along line 96-96 in FIG. 22;

FIG. 97*a* is a bottom perspective view of the handvac of the apparatus of FIG. 1;

FIG. 97*b* is a partial cross-sectional view taken along line 97*b*-97*b* of FIG. 97*a*;

FIG. 98*a* is a bottom perspective view of the handvac of the apparatus of FIG. 1 with an open door;

FIG. 98*b* a partial cross-sectional view taken along line 98*b*-98*b* of FIG. 98*a*;

FIG. 99 is a partial cross-sectional view of a surface cleaning apparatus having a handvac disconnected from the upright section, and a bypass valve in a first closed position;

FIG. 100 is a cross-sectional view of the surface cleaning apparatus of FIG. 99 having a handvac connected to the upright section and the bypass valve in the first closed position;

FIG. 101 is a cross-sectional view of the surface cleaning apparatus of FIG. 99 having the handvac connected to the upright section and a supplementary cyclone bin assembly, and the bypass valve in a second open position;

FIG. 102 is a cross-sectional view of a surface cleaning apparatus having a having a bypass airflow path and a pre-motor filter in a supplemental cyclone bin assembly;

FIG. 103 is a cross-sectional view of a surface cleaning apparatus having a clean air suction motor in a surface cleaning head;

FIG. 104*a* is a cross-sectional view of a surface cleaning apparatus having a having a clean air suction motor in a supplemental cyclone bin assembly;

FIG. 104*b* is a cross-sectional view of another surface cleaning apparatus having a clean air suction motor in a supplemental cyclone bin assembly;

FIG. 105*a* is a perspective view of a surface cleaning apparatus having a supplemental cyclone bin assembly disconnected from an upright section;

8

FIG. 105*b* is a perspective view of a surface cleaning apparatus having a cyclone chamber and dirt collection chamber disconnected from an upright section;

FIG. 106 is a side elevation view a surface cleaning apparatus in accordance with another embodiment;

FIG. 107 is a partial side elevation view of the apparatus of FIG. 106 with a handvac disconnected from an upright section;

FIG. 108 is a side elevation view of the apparatus of FIG. 106 in a reclined in-use position with an arm assembly in a first position;

FIG. 109 is a side elevation view of the apparatus of FIG. 106 in a steeply reclined in-use position with the arm assembly in a second position;

FIG. 110*a* is a rear perspective view of the handvac of the apparatus of FIG. 1 in an open position;

FIG. 110*b* is a front perspective view of the handvac of FIG. 110*a* in the open position;

FIG. 111 is a front perspective view of the dirt collection chamber of the apparatus of FIG. 1 in an open position;

FIG. 112 is a rear perspective view of the dirt collection chamber of FIG. 111 in the open position;

FIG. 113 is a side elevation view of the dirt collection chamber of FIG. 111 in the open position;

FIG. 114 is a front perspective view of the upright section of the apparatus of FIG. 5 with a cyclone bin assembly in a closed position;

FIG. 115 is a front perspective view of the upright section of FIG. 114 with the cyclone bin assembly in an open position;

FIG. 116 is a cross-sectional view of the handvac of the apparatus of FIG. 1 having a pre-motor filter chamber in an open position;

FIG. 117 is an exploded view of the handvac of FIG. 116;

FIG. 118 is a cross-sectional view of a surface cleaning apparatus having a plurality of cyclone chambers in parallel;

FIG. 119*a* is a cross-sectional view of a surface cleaning apparatus having a dirty air suction motor in a surface cleaning head in series with a clean air suction motor in a handvac;

FIG. 119*b* is a cross-sectional view of the surface cleaning apparatus of FIG. 119*a* with a supplemental cyclone bin assembly removed;

FIG. 120 is a cross-sectional view of a surface cleaning apparatus having a clean air suction motor in a surface cleaning head in series with a clean air suction motor in a handvac;

FIG. 121*a* is a cross-sectional view of a surface cleaning apparatus having a clean air suction motor in a supplemental cyclone bin assembly in series with a clean air suction motor in a handvac;

FIG. 121*b* is a cross-sectional view of the surface cleaning apparatus of FIG. 121*a* with a hose connecting the handvac suction motor and the suction motor of the supplemental cyclone bin assembly;

FIG. 122 is a cross-sectional view of a surface cleaning apparatus having an airflow which bypasses the handvac;

FIG. 123 is a perspective view of a surface cleaning apparatus in accordance with another embodiment;

FIG. 124 is an exploded perspective view of the surface cleaning apparatus of FIG. 123;

FIG. 125 is a cross-sectional view taken along line 125-125 in FIG. 123;

FIG. 126 is enlarged partial view of FIG. 125;

FIG. 127 is an enlarged partial view of FIG. 126;

FIG. 128 is a perspective view of a surface cleaning apparatus in accordance with another embodiment;

FIG. 129 is a cross sectional perspective view of the surface cleaning apparatus of FIG. 128;

FIG. 130 is a front perspective view of the surface cleaning apparatus of FIG. 128 with a front end open;

FIG. 131 is a bottom perspective view of the surface cleaning apparatus of FIG. 128 with the front end open;

FIG. 132 is a perspective view of a surface cleaning apparatus in accordance with another embodiment;

FIG. 133 is a cross sectional perspective view of the surface cleaning apparatus of FIG. 132;

FIG. 134 is a rear perspective view of the surface cleaning apparatus of FIG. 132 with a front end open;

FIG. 135 is a front perspective view of the surface cleaning apparatus of FIG. 132 with the front end open;

FIG. 136 is a perspective cross sectional view of a surface cleaning apparatus in accordance with another embodiment; and,

FIG. 137 is a perspective cross sectional view of the surface cleaning apparatus of FIG. 136 with a front end open.

DESCRIPTION OF VARIOUS EMBODIMENTS

Numerous embodiments are described in this application, and are presented for illustrative purposes only. The described embodiments are not intended to be limiting in any sense. The invention is widely applicable to numerous embodiments, as is readily apparent from the disclosure herein. Those skilled in the art will recognize that the present invention may be practiced with modification and alteration without departing from the teachings disclosed herein. Although particular features of the present invention may be described with reference to one or more particular embodiments or figures, it should be understood that such features are not limited to usage in the one or more particular embodiments or figures with reference to which they are described.

The terms “an embodiment,” “embodiment,” “embodiments,” “the embodiment,” “the embodiments,” “one or more embodiments,” “some embodiments,” and “one embodiment” mean “one or more (but not all) embodiments of the present invention(s),” unless expressly specified otherwise.

The terms “including,” “comprising” and variations thereof mean “including but not limited to,” unless expressly specified otherwise. A listing of items does not imply that any or all of the items are mutually exclusive, unless expressly specified otherwise. The terms “a,” “an” and “the” mean “one or more,” unless expressly specified otherwise.

As used herein and in the claims, two or more parts are said to be “coupled,” “connected,” “attached,” or “fastened” where the parts are joined or operate together either directly or indirectly (i.e., through one or more intermediate parts), so long as a link occurs. As used herein and in the claims, two or more parts are said to be “directly coupled,” “directly connected,” “directly attached,” or “directly fastened” where the parts are connected directly in physical contact with each other. As used herein, two or more parts are said to be “rigidly coupled,” “rigidly connected,” “rigidly attached,” or “rigidly fastened” where the parts are coupled so as to move as one while maintaining a constant orientation relative to each other. None of the terms “coupled,” “connected,” “attached,” and “fastened” distinguish the manner in which two or more parts are joined together.

General Overview

Referring to FIGS. 1-3, a surface cleaning apparatus 100 is shown in accordance with a first embodiment. In the

embodiment shown, the surface cleaning apparatus 100 is a type of upright vacuum cleaner which is referred to as a stick vacuum cleaner. As illustrated, surface cleaning apparatus 100 includes a surface cleaning head 104, an upright section 108, and a hand-carriable vacuum cleaner 112 (also referred to as handvac or hand vacuum cleaner 112).

Upright section 108 may be movably and drivingly connected to surface cleaning head 104. For example, upright section 108 may be permanently or removably connected to surface cleaning head 104 and moveably mounted thereto for movement from a storage position to an in use position, such as by a pivotable joint 116. Joint 116 may permit upright section 108 to pivot (i.e., rotate) with respect to surface cleaning head 104 about a horizontal axis. Accordingly, upright section 108 may be rotatable rearwardly so as to be positionable in a plurality of reclined floor cleaning positions (see for example FIGS. 81 and 108).

Upright section 108 may also be steeringly connected to surface cleaning head 104 for maneuvering surface cleaning head 104. For example, joint 116 may be a swivel joint.

Handvac 112 may be removably connected to upright section 108. When mounted to upright section 108, a user may grasp handvac 112 to manipulate upright section 108 to steer surface cleaning head 104 across a surface to be cleaned. Accordingly, when handvac 112 is mounted to upright section 108, handle 484 is the drive handle of surface cleaning apparatus 100.

Surface cleaning apparatus 100 has at least one dirty air inlet, one clean air outlet, and an airflow path extending between the inlet and the outlet. In the illustrated example, lower end 120 of surface cleaning head 104 includes a dirty air inlet 124, and a rear end 128 of handvac 112 includes a clean air outlet 132. An airflow path extends from dirty air inlet 124 through surface cleaning head 104, upright section 108, and handvac 112 to clean air outlet 132. As exemplified in FIGS. 128 to 135, the handvac 112 may include a main body 129 and a dirty air inlet 131, and an air flow path of the handvac 112 may extend from the dirty air inlet 131 to the clean air outlet 132 with the suction motor 204 positioned in the air flow path.

As exemplified, at least one suction motor, and preferably the only suction motor, and one air treatment member, which may be the only air treatment member, is provided in the handvac 112 to permit handvac 112 to operate independently when disconnected from surface cleaning head 104 and optionally from upright section 108. It will be appreciated that while at least one suction motor and at least one air treatment member are positioned in the airflow path to separate dirt and other debris from the airflow, that when used with other aspects disclosed herein, each of the suction motor and the air treatment member may be provided in the surface cleaning head 104, the upright section 108, and/or the handvac 112.

The air treatment member may be any suitable air treatment member, including, for example, one or more cyclones, filters, and bags. The air treatment member may be an air treatment chamber wherein air is redirected to assist dirt being removed from an incoming air stream and is optionally a cyclone chamber. Preferably, at least one air treatment member is provided upstream of the suction motor to clean the dirty air before the air passes through the suction motor. In the illustrated embodiment, handvac 112 includes a cyclone bin assembly 136 including a cyclone chamber and a dirt collection region. In some embodiments, the dirt collection region may be a portion (e.g., a lower portion) of the cyclone chamber. In other embodiments, the dirt collection region may be a dirt collection chamber that is separated

11

from the cyclone chamber by a dirt outlet of the cyclone chamber. The following description utilizes the exemplified embodiments set out in the drawings, which utilize a cyclone chamber. It will be appreciated that the aspects disclosed herein may be used with an air treatment member as discussed previously and, optionally, an air treatment chamber. It will also be appreciated that if the air treatment member is an air treatment chamber, then the cyclone bin assembly **136** may be referred to as an air treatment assembly.

Plurality of Dirt Collection Chambers

In accordance with one aspect of this disclosure, which may be used by itself or in combination with any one or more other aspects of this disclosure, a stick surface cleaning apparatus may have more than one dirt collection chamber. For example, the handvac may include a first dirt collection chamber, and the upright section may include a second dirt collection chamber. The second dirt collection chamber provides the surface cleaning apparatus with an enlarged dirt collection capacity in comparison with the dirt collection capacity of the handvac alone. Accordingly, the surface cleaning apparatus may operate for longer intervals before one or more of the dirt collection chambers needs to be emptied.

In accordance with this aspect, and as exemplified in FIG. **4**, upright section **108** may have an auxiliary dirt collection assembly **140**, which may comprise or consist of an auxiliary dirt collection chamber **141**. For example, the auxiliary dirt collection chamber **140** may be the only component provided in the auxiliary dirt collection assembly and therefore the auxiliary dirt collection chamber **140** may be the auxiliary dirt collection assembly. Alternately, as disclosed in alternate embodiments, the auxiliary dirt collection assembly may also include one or more of a pre-motor filter, one or more cyclone chambers that may have one or more associated dirt collection chambers and a suction motor.

As illustrated, up flow duct **144** (also referred to as a wand if removable for use, e.g., in an above floor cleaning mode as exemplified in FIGS. **33** and **44a**) may define the airflow path between surface cleaning head **104** and handvac **112**. Auxiliary dirt collection chamber **140** may be a supplemental dirt collection chamber that is selectively mounted to up flow duct **144** and augments the dirt collection capacity of surface cleaning apparatus **100** when mounted to upper section **108**.

It will be appreciated that if up flow duct **144** is the member that supports handvac **112** when auxiliary dirt collection assembly **140** is removed, the up flow duct is designed to be load supporting and may be a rigid tube. Further if the up flow duct is removable to function as an above floor cleaning wand, then the up flow duct may also be a rigid tube. In other embodiments, e.g., the up flow duct is not a load supporting member, then all or a portion of up flow duct **144** may be flexible, such as a flexible hose.

As exemplified in FIGS. **1** and **21**, the dirt collection assembly **140** of the upright section **108** may collect at least a portion of the dirt separated from the dirty airflow by the handvac **112**. Accordingly, the dirt collection assembly **140** of the upright section **108** may be in communication with the dirt collection chamber of handvac **112** all or a portion of the time when the handvac **112** is mounted to the upright section **108**. For example, the dirt collection chamber of handvac **112** may have a door that automatically opens when handvac **112** is mounted to the upright section **108**. Accordingly, dirt separated by handvac **112** may travel to the supplemental dirt collection assembly **140**. Alternately, the door may be manually operable by a user. Accordingly, dirt may only be

12

transferred to the supplemental dirt collection assembly **140** when a user elects to open the door. Alternately, the supplemental dirt collection assembly **140** may receive dirt from an auxiliary air treatment member, in which case the auxiliary dirt collection assembly may comprise a housing having both the auxiliary air treatment member and the auxiliary dirt collection chamber.

The dirt collection chamber of auxiliary dirt collection assembly **140** and handvac dirt collection chamber **188** may be of any suitable volumetric sizes. Preferably, the volumetric storage capacity of the dirt collection chamber of auxiliary dirt collection assembly **140** is at least equal to the volumetric storage capacity of handvac dirt collection chamber **188**, and more preferably larger than the volumetric storage capacity of handvac dirt collection chamber **188**. For example, the volumetric storage capacity of the dirt collection chamber of auxiliary dirt collection assembly **140** may be 1-20 times the volumetric storage capacity of handvac dirt collection chamber **188**, more preferably 1.5-10 times, and most preferably 3-5 times. In alternative embodiments, the volumetric storage capacity of the dirt collection chamber of auxiliary dirt collection assembly **140** may be less than that of handvac dirt collection chamber **188**.

As exemplified in FIG. **21**, handvac **112** may include a cyclone bin assembly **136** including one or more cyclone chambers **184** and one or more dirt collection chambers **188**. The cyclone chamber or chambers and the dirt collection chamber or chambers may be of any design. As exemplified, cyclone chamber **184** includes an air inlet **192** in fluid communication with wand **144**, an air outlet **196** downstream of air inlet **192**, and a dirt outlet **200** in fluid communication with dirt collection chamber **188**. Suction motor **204** or another suction source may draw dirty air to enter air inlet **192** and travel cyclonically across cyclone chamber **184** to dirt outlet **200** where dirt is ejected into dirt collection chamber **188**. Afterwards, the air is discharged from cyclone chamber **184** at air outlet **196**.

As exemplified in FIGS. **21-23**, cyclone bin assembly **136** may include laterally opposed side walls **208**, a top wall **212**, a bottom wall **216**, a first end wall **220**, and a second end wall **224**. As shown, a common interior wall **226** may divide cyclone chamber **184** from dirt collection chamber **188**. For example, cyclone chamber **184** may be defined by top wall **212** and interior wall **226** which extend between end walls **220** and **224**. Top wall **212** and interior wall **226** may be curved to define a substantially cylindrical or frustoconical sidewall of cyclone chamber **184**. In alternative embodiments, cyclone chamber **184** may have a sidewall of any other suitable shape that is conducive to cyclonic flow. In some alternative embodiments, interior wall **226** of cyclone chamber **184** may be discrete from dirt collection chamber **188** instead of forming a common wall dividing cyclone chamber **184** from dirt collection chamber **188**.

Dirt collection chamber **188** may be defined by bottom wall **216**, side walls **208**, and interior wall **226**. In some embodiments, bottom wall **216** may be openable for fluidly connecting handvac dirt collection chamber **188** to supplemental dirt collection assembly **140** of upright section **108**. This may permit dirt separated by cyclone chamber **184** and discharged through dirt outlet **200** to move through opened bottom wall **216** and collect in supplemental dirt collection assembly **140**.

Optionally, when the auxiliary dirt collection assembly is mounted to upright section **108**, dirt separated in the cyclone chamber is collectable in the dirt collection chamber of the auxiliary dirt collection assembly. The auxiliary dirt collection assembly may be selectively connectable in communi-

13

cation with the dirt collection region of the hand vacuum cleaner by, e.g., an openable door 228 (also referred to as a dumping door). The door may be manually openable, such as by a handle, or automatically operated, such as when the auxiliary dirt collection assembly is mounted to upright section 108. In this case, dirt will collect in the handvac 112 and will remain there until door 228 is openable so as to allow the collected dirt to transfer to supplemental dirt collection assembly 140. In the latter case, supplemental dirt collection assembly 140 is automatically connected in communication with a dirt outlet of the cyclone chamber when the auxiliary dirt collection assembly is mounted to upright section 108. In this case, dirt will collect in the supplemental dirt collection assembly 140 when handvac 112 is mounted to the upright section 108.

In the illustrated example, bottom wall 216 includes a door 228, which may be a pivotally openable door 228. As shown, door 228 may be pivotally connected to dirt collection chamber 188 by a hinge 232 for rotation about a hinge axis 236. Door 228 may extend forwardly from a rear end 240 to a front end 244. Preferably, hinge 232 and hinge axis 236 are positioned at rear end 240 of door 228. In alternative embodiments, hinge 232 and hinge axis 236 may be positioned at front end 244 or intermediate front and rear ends 240 and 244.

Door 228 is preferably outwardly pivotal of dirt collection chamber 188. For example, door 228 may be movable between a closed position (FIG. 22) in which door 228 closes bottom wall 216, and an open position (FIG. 21) in which door 228 is rotated away from dirt collection chamber 188 for opening bottom wall 216 to permit dirt to move from handvac dirt collection chamber 188 to supplemental dirt collection assembly 140. As shown, in the open position front end 244 of door 228 may be moved away from handvac dirt collection chamber 188.

Hinge axis 236 may have any suitable orientation. In the illustrated example, hinge axis 236 extends laterally side-to-side of surface cleaning apparatus 100. Hinge axis 236 may be transverse to one or more of cyclone axis 248 of cyclone chamber 184, motor axis 252 of suction motor 204, or downstream direction 256 through air inlet 192. In the example shown, hinge axis 236 is perpendicular to cyclone axis 248, motor axis 252, and downstream direction 256. In alternative embodiments, hinge axis 236 may be substantially parallel to one or more of cyclone axis 248, motor axis 252, or downstream direction 256.

In some embodiments, door 228 may extend upwardly and forwardly between rear end 240 and front end 244. For example, front end 244 may be positioned closer to cyclone chamber 184 and cyclone axis 248 than rear end 240. When door 228 is opened (FIG. 21), this may provide a bottom opening 260 having a transverse width 264 between cyclone chamber 184 and bottom wall 216.

Optionally, the dirt collection region (the dirt collection chamber) of the hand vacuum cleaner is positioned above the supplemental dirt collection assembly 140. Accordingly, dirt that is received in the dirt collection chamber of the hand vacuum cleaner may be transferred by due to gravity to the supplemental dirt collection assembly 140. Accordingly, for example, dirt outlet 200 may be positioned on a bottom end 268 of cyclone chamber 184 for discharging dirt toward bottom wall 216 and opening 260 to be delivered by gravity into supplemental dirt collection assembly 140 of upright section 108.

Reference is now made to FIGS. 21, 22, and 24. Preferably, when handvac 112 is connected to upright section 108, opening 260 is fluidly coupled to an inlet to dirt collection

14

assembly 140. In the illustrated example, door 228 and opening 260 of cyclone bin assembly 136 align with an inlet 272 of dirt collection assembly 140. As shown, inlet 272 may be formed as an opening in an upper portion 276 of dirt collection assembly 140. In some embodiments, inlet 272 may include a door (not shown) which opens automatically and concurrently with door 228. Optionally, the door of inlet 272 may be biased (e.g., by a spring) to close inlet 272 and seal dirt collection assembly 140 when door 228 is closed or handvac 112 is disconnected from upright section 108.

Preferably, opening 260 and inlet 272 of upper portion 276 of dirt collection assembly 140 are sized and positioned to receive at least a portion of door 228 when door 228 is in the open position. This may permit door 228 to open outwardly into the open position as shown in FIG. 21.

If door 228 is moveable from the closed position to the open position automatically upon connecting handvac 112 to upright section 108, then handvac 112 may include an actuator drivingly connected to door 228 to move door 228 (e.g., pivot door 228 about hinge axis 236) to the open position when handvac 112 is connected to upright section 108. In the illustrated embodiment, door 228 includes an arm 280 pivotally connected at hinge 232. As shown, arm 280 may include a lever portion 284 which extends rearwardly of hinge 232, and which may be depressed to pivot door 228 to the open position. Further, dirt collection assembly 140 is shown including an engaging member 288 positioned to align with lever portion 284 of arm 280. In use, engaging member 288 may depress lever portion 284 of arm 280 upon connecting handvac 112 to upright section 108 to automatically pivot door 228 into the open position, whereby opening 260 may be fluidly connected to inlet 272 of supplemental dirt collection assembly 140. In one aspect, this may permit a user, who has used handvac 112 when disconnected from upright section 108, to automatically empty handvac dirt collection chamber 188 by connecting handvac 112 to upright section 108. Afterwards, handvac 112 may be disconnected from upright section 108 with an empty dirt collection chamber 188.

If door 228 is manually moveable from the closed position to the open position then, as exemplified in FIGS. 97a-b and 98a-b, door 228 may be provided with an actuator, e.g., a manually operable lever portion 284. Lever portion 284 may extend downwardly from door 228 such that lever portion 284 is user-accessible and user-operable while handvac 112 is mounted to upright section 108. As exemplified, lever portion 284 may protrude from the bottom wall 216 of cyclone bin assembly 136 to provide user-accessibility to lever portion 284.

As exemplified in FIGS. 21, 22, 24, 97a-b, and 98a-b, whether door 228 is manually or automatically operable, door 228 may be biased to the closed position. For example, door 228 may be biased for rotation about hinge axis 236 toward the closed position by a biasing member (not shown), such as a torsion spring. This may permit door 228 to close automatically upon disconnecting handvac 112 from upright section 108, to prevent dirt from spilling from dirt collection chamber 188 and to permit immediate use of handvac 112 for cleaning. In alternative embodiments, door 228 may not be biased toward the closed position. For example, door 228 may remain in the open position upon disconnecting handvac 112 from upright section 108. In such a case, door 228 may remain open until manually closed. For example, referring to FIGS. 98a-b, door 228 may remain in the open position shown until lever portion 284 of arm 280 is user-activated to move door 228 to the closed position.

Removable Supplemental Dirt Collection Assembly

15

In accordance with another aspect of this disclosure, which may be used by itself or in combination with any one or more other aspects of this disclosure, a surface cleaning apparatus has two or more dirt collection chambers wherein one of the dirt collection chambers is optionally removable, and the surface cleaning apparatus is operable when the removable dirt collection chamber has been removed. Accordingly, as discussed with respect to the previous embodiment, a supplemental dirt collection chamber may be provided on the up flow duct or wand of a stick vacuum cleaner and may be the main dirt collection chamber (e.g., it may collect most or all of the separated dirt when the stick vacuum cleaner is operated with the supplemental dirt collection chamber in position). This may be referred to as a large dirt capacity upright mode or a second upright mode of operation.

The supplemental dirt collection chamber may be removable for emptying and to reconfigure the vacuum to a light weight upright mode or a first upright mode of operation. Once removed, the vacuum cleaner may be operable to separate dirt and collect the separated dirt in another dirt collection chamber (e.g., the handvac dirt collection chamber). An advantage of the light weight upright mode is that the size and weight of the vacuum cleaner may be reduced by removal of the supplemental dirt collection chamber. This may be of assistance when the vacuum cleaner is used to clean around and under furniture, and when the vacuum cleaner is to be carried upstairs.

As exemplified in FIGS. 1 and 4, dirt collection assembly 140 of upright section 108 may be removably connected to wand 144 and handvac 112. This may permit dirt collection assembly 140 to be removed for emptying, or to operate apparatus 100 in a light weight upright mode. It will be appreciated that, in alternate embodiments, wand 144 and dirt collection assembly 140 of upright section 108 may be integrally formed or permanently connected as a one piece assembly.

Dirt collection assembly 140 may be removably mounted to wand 144 in any suitable fashion. In the illustrated embodiment, a lower end 292 of dirt collection assembly 140 may be toed onto a lower end 296 of wand 144, and then dirt collection assembly 140 may be pivoted about lower end 292 toward wand 144 and held in position by a suitable releasable fastening mechanism.

In the illustrated embodiment, handvac 112 may remain in fluid communication with wand 144 and surface cleaning head 104 while supplemental dirt collection assembly 140 is disconnected from wand 144 and removed altogether from apparatus 100. This may permit dirt collection assembly 140 to be removed (e.g., for emptying or to operate apparatus 100 in a light weight upright mode) without disrupting the operation of apparatus 100.

Upstream Air Treatment Member

In accordance with another aspect of this disclosure, which may be used by itself or in combination with any one or more other aspects of this disclosure, an upstream air treatment member may be provided. The upstream air treatment member may be removably connectable upstream of the handvac. For example, the supplemental dirt collection assembly may have one or more cyclone chambers associated therewith. Accordingly, when the supplemental dirt collection assembly is positioned on upright section 108 (e.g., up flow duct 144), a supplemental cyclone chamber assembly 160 may be connected in series or parallel with the cyclone chamber of the handvac. Accordingly, when operated as an upright vacuum, the surface cleaning apparatus may be a dual cyclonic stage surface cleaning apparatus.

16

When used in an above floor cleaning mode, the handvac may be a single cyclonic stage surface cleaning apparatus. Typically, the surface cleaning apparatus may be used as an upright vacuum cleaner (i.e., with the supplemental cyclonic bin assembly attached) for cleaning floors. This may represent the majority of area that is to be cleaned. Therefore, for a majority of the use of the surface cleaning apparatus, it may be used as a dual stage cyclonic surface cleaning apparatus.

In accordance with this aspect, the upright section may include a first air treatment member for separating at least large dirt particles from the airflow, and the air treatment member of the handvac may be positioned downstream of the first air treatment member for separating small dirt particles ("fines") from the airflow. In this case, the greatest volume of separated dirt may be collected in the dirt collection chamber of the upright section, and a lesser volume of fines may be collected in the dirt collection chamber of the handvac. This may reduce the rate at which the handvac dirt collection chamber may be filled, and reduce the frequency at which the handvac dirt collection chamber must be emptied. It will be appreciated that each cyclonic stage may be of any design and may be designed to remove any type of dirt.

It will be appreciated that, in some embodiments, dirt separated by the handvac may be collected in the supplemental dirt collection assembly. In such a case, the dirt collection region of the handvac may be in communication (automatically or manually selectively) with a dirt collection region in the supplemental dirt collection assembly, which region may be isolated from the dirt collection chamber for the cyclonic stage of the supplemental cyclone chamber assembly.

It will be appreciated that, if air travels through up flow duct 144 to handvac 112, when cyclone bin assembly 160 is connected to wand 144, air travelling through wand 144 may be diverted into cyclone bin assembly 160 and returned to wand 144 from cyclone bin assembly 160 downstream of the diversion. Optionally, in accordance with another aspect with is discussed in more detail subsequently, and which is exemplified in the embodiment of FIGS. 20 and 26, in some embodiments the diversion may occur automatically upon mounting of the supplemental cyclone bin assembly 160 to upright section 108. For example, cyclone bin assembly 160 may include a diversion member 428 which may be positionable in the conduit of wand 144 between the upstream and downstream ends 364 and 360 of wand 144. As shown, diversion member 428 may divide wand 144 into an upstream wand portion 440 and a downstream wand portion 444. Diversion member 428 may form an air-tight seal inside wand 144 for redirecting substantially all air travelling through upstream wand portion 440 into air inlet 316 of cyclone bin assembly 160. In turn, air outlet 320 of cyclone bin assembly 160 may discharge into downstream wand portion 444 for travel downstream to handvac 112.

As exemplified in the embodiment of FIGS. 5, 12, and 25 supplemental cyclone bin assembly 160, 160 may be any suitable cyclone bin assembly and may include a cyclone chamber 308 and a dirt collection chamber 141. Cyclone chamber 308 may include an air inlet 316 for receiving dirty air from the surface cleaning head, e.g., via wand 144, an air outlet 320 for discharging air, e.g., to handvac 112, a dirt outlet 324 for discharging separated dirt into dirt collection chamber 141, a vortex finder 400 and a cyclone axis 392. Wand 144 may include an upstream end 360 connected to surface cleaning head 104, and a downstream end 364 connected to air inlet 316 of cyclone chamber 308.

17

From cyclone bin assembly 160, the airflow may flow downstream to handvac 112. Accordingly, handvac cyclone bin assembly 136 is positioned downstream of and in series with supplemental cyclone bin assembly 160. The air may be received in handvac cyclone bin assembly 136 where additional particulate matter may be further separated from the airflow and deposited into dirt collection chamber 188. In many cases, the additional particulate matter separated by cyclone bin assembly 136 may constitute less than 30% of the total volume of dirt separated from apparatus 100, and may constitute all or a majority of the fines that are separated. Accordingly, dirt collection chamber 188 may be filled at a lower volumetric rate than supplemental dirt collection chamber 141. This may help to maintain dirt collection capacity in handvac 112.

In operation, air exiting air outlet 320 of cyclone bin assembly 160 may enter handvac 112 for a second stage of cleaning by cyclone bin assembly 136. As illustrated, handvac 112 may include a nozzle 412 having an upstream end 416 and a downstream end 420. When handvac 112 is connected to upright section 108, upstream end 416 may be fluidly connected with air outlet 320 of upright section 108, and downstream end 420 may be fluidly connected with inlet 192 of handvac cyclone chamber 184.

In operation, air may be drawn into dirty air inlet 124 and enter upstream wand portion 440. Diversion member 428 may redirect the air traveling through upstream wand portion 440 to enter air inlet 316 of cyclone chamber 308. Air may travel through air inlet 316 tangentially to sidewall 376 and spiral downwardly toward lower end wall 368, whereby dirt may be separated from the airflow and pass through dirt outlet 324 to accumulate in dirt collection chamber 141. The airflow may then travel downstream into vortex finder 400 and exit cyclone chamber 308 at air outlet 320 at downstream end 404 of vortex finder 400, into an outlet passage 476. Outlet passage 476 may have a downstream end fluidly connected to downstream wand portion 444. The air may travel through downstream wand portion 444 to downstream wand end 364 into handvac 112. In handvac 112, additional dirt may be separated from the airflow by cyclone bin assembly 136 before the air is discharged through clean air outlet 132.

It will be appreciated that, in accordance with this aspect, cyclone bin assembly 160 may be any suitable cyclone bin assembly. In the example shown in FIGS. 5, 12, and 25, cyclone chamber 308 includes a lower end wall 368, an upper end wall 372, and a sidewall 376 extending between the lower end wall 368 and the upper end wall 372. Preferably, sidewall 376 is substantially cylindrical or frustoconical in accordance with conventional cyclone chamber design.

Dirt outlet 324 may be formed as an opening in sidewall 376 for directing separated dirt into dirt collection chamber 141. In some embodiments, at least a portion of sidewall 376 of cyclone chamber 308 may form a common dividing wall between cyclone chamber 308 and dirt collection chamber 141. In this case, dirt outlet 324 may be formed as an opening in the common portion of sidewall 376.

Dirt outlet 324 may be formed at any suitable position on sidewall 376. In the illustrated example, dirt outlet 324 is positioned at an upper end of cyclone chamber 308 proximate upper end wall 372. More particularly, the illustrated embodiment includes a dirt outlet 324 defined by a slot 380 in sidewall 376 bordered by upper end wall 372. This may increase the capacity of dirt collection chamber 141. More specifically, dirt may accumulate by gravity from the bottom of dirt collection chamber 141 upwardly. Thus, the capacity

18

of the dirt collection chamber 141 may be defined at least in part by the position of dirt outlet 324. Dirt collection chamber 141 is full when the level of dirt in dirt collection chamber 141 rises to dirt outlet 324. Accordingly, the capacity of dirt collection chamber 141 is the volume of the dirt collection chamber 141 below dirt outlet 324. Thus, the capacity of dirt collection chamber 141 may be increased by positioning dirt outlet 324 in an uppermost position, such as proximate the upper end wall 372 of cyclone chamber 308 as shown.

Alternately, in some embodiments as exemplified in FIG. 26, lower end wall 368 may comprise or be an arrester plate 1280 which separates cyclone chamber 308 from dirt collection chamber 141. In this case, dirt outlet 324 may be formed by a gap between arrester plate 1280 and sidewall 376, where dirt particles may fall by gravity into dirt collection chamber 141.

In accordance with another aspect which is discussed in more detail subsequently, as exemplified, cyclone chamber 308 may include an inlet passage 384 for redirecting axially-directed inlet air to flow tangentially to promote cyclonic action in cyclone chamber 308. An upstream end 388 of inlet passage 384 may face axially (i.e., substantially parallel to cyclone axis 392), and a downstream end (not shown) of inlet passage 384 may face tangentially to cyclone chamber 308. Air entering upstream end 388 of inlet passage 384 from air inlet 316 may travel along inlet passage 384 and exit downstream end (not shown) in a tangential direction. After spiraling upwardly around vortex finder 400 of cyclone chamber 308, the airflow may enter vortex finder 400 and exit cyclone chamber 308 through air outlet 320 at a downstream end 404 of vortex finder 400.

Handvac cyclone chamber 184 may be any suitable cyclone chamber. In some embodiments, cyclone chamber 184 is substantially similar to cyclone chamber 308. For example, cyclone chamber 184 may include an air inlet 192, an inlet passage 420, a dirt outlet 200, a vortex finder 424, a dirt outlet 200, an air outlet 196, and a cyclone axis 248. Air from upright section 108 may axially enter air inlet 192, be redirected to a tangential direction by inlet passage 420, spiral upwardly around vortex finder 424, deposit dirt into dirt outlet 200, and then exit cyclone chamber 184 through air outlet 196 at a downstream end of vortex finder 424.

Modes of Operation

In accordance with another aspect of this disclosure, which may be used by itself or in combination with any one or more other aspects of this disclosure, the surface cleaning apparatus is reconfigurable to operate in a plurality of different modes of operation. For example, the surface cleaning apparatus may be operable in two or more of a handvac mode, a stair-cleaning mode, an above-floor cleaning mode, a large dirt capacity upright mode, a lightweight upright mode, or a dual motor upright mode. In some cases, the surface cleaning apparatus may be reconfigurable between different modes of operation with a single act of connection or disconnection. This may permit the surface cleaning apparatus to be quickly reconfigured with minimal interruption.

Referring to FIGS. 1, 5, and 13, surface cleaning apparatus 100, 152, and 168 are shown in a large dirt capacity upright cleaning mode. In the large dirt capacity upright cleaning mode, surface cleaning apparatus 100, 152, and 168 may include surface cleaning head 104, upright section 108 including wand 144 and supplemental dirt collection assembly 140, and handvac 112. The airflow path may extend from dirty air inlet 124 of surface cleaning head 104 downstream through wand 144 and then cyclone bin assem-

19

bly 136 of handvac 112 to separate dirt from the airflow and deposit that dirt into dirt collection chamber 141 of upright section 108 and/or handvac dirt collection chamber 188. In apparatus 152 and 168, cyclone bin assembly 160 is also positioned in the airflow path for separating and collecting dirt from the airflow and cyclone bin assembly 136 of handvac 112 may optionally be bypassed as discussed subsequently.

As exemplified in FIGS. 12 and 12a one or more of the surface cleaning head 104, upright section 108, and handvac 112 may be removably connected to each other so as to be able to be assembled in a number of different combinations to provide apparatus 152 with a number of different modes of operation. In some embodiments, the wand 144 and supplemental assembly 140, 160 of upright section 108 may also be removably connected to each other to provide additional modes of operation. For example, in the large dirt capacity upright cleaning mode, surface cleaning head 104 may be connected to upstream end 360 of wand 144, downstream end 364 of wand 144 may be connected to an air inlet 316 of cyclone bin assembly 160, and air outlet 320 of cyclone bin assembly 160 may be connected to upstream end 416 of handvac nozzle 412.

The large dirt capacity upright cleaning mode as shown may be particularly effective for cleaning large surface areas (e.g., the floor of one or more rooms). The user may grasp handvac handle 484 to steer surface cleaning head 104 across the surface to be cleaned (i.e., handle 484 may be a drive handle of the surface cleaning apparatus). The tall height 492 of apparatus 100, 152, and 168 provided in part by the interposition of wand 144 between surface cleaning head 104 and handvac 112 may permit apparatus 100 to be operated by a user standing upright. The large dirt capacity of dirt collection chamber 141 of upright section 108 may permit extended usage of apparatus 100 before the dirt collection chamber 141 becomes full and must be emptied.

As exemplified in FIGS. 4, 5, 12, 12a, 20 and 27-30, and 37-44 dirt collection assembly 140 or cyclone bin assembly 160 may be selectively disconnected from upright section 108 to reconfigure apparatus 100, 152, or 168 from the large dirt capacity upright mode to a light weight upright mode. Likewise, dirt collection assembly 140 or cyclone bin assembly 160 may be selectively reconnected to upright section 108 to reconfigure apparatus 100, 152, or 168 from a light weight mode to a large dirt capacity upright mode.

Preferably, reconfiguring the apparatus from the large dirt capacity upright mode to the light weight upright mode may require only a single user action (e.g., disconnecting the dirt collection assembly 140 or cyclone bin assembly 160 from the upright section 108 may automatically close a dumping door of the handvac if the dumping door is open and may also automatically close a diversion member if the vacuum cleaner includes a supplemental cyclone bin assembly 160).

As exemplified in apparatus 100, door 228 which may have been open in the large dirt capacity upright mode for connecting dirt collection chambers 188 and 141, may close automatically (i.e., without any further user interaction) upon disconnecting dirt collection chamber 141, to seal bottom wall 216 of dirt collection chamber 141. Exemplary mechanisms include a biasing member, such as a spring and a mechanical or electrical drive member drivingly connected to the door to close the door as supplemental assembly 140, 160 is removed.

As exemplified in apparatus 168, disconnecting cyclone bin assembly 160 from wand 144 may automatically reroute the airflow path to extend directly from upstream wand end 360 to downstream wand end 364 without the intermediary

20

diversion to cyclone bin assembly 160. Therefore, the airflow path between surface cleaning head 104 and handvac 112 is automatically reconfigured by disconnection of cyclone bin assembly 160 to reconfigure apparatus 168 to the light weight upright mode. Accordingly, apparatus 168 may be continually operated while being reconfigured.

In alternative embodiments, door 228 of apparatus 100 may be manually closed as another step before, during or after dirt collection assembly 140 is disconnected from upright section 108 to complete the reconfiguration to the light weight upright mode. For example, a user may manually close the door. In other embodiments, as described in more detail below, a diversion valve of apparatus 168 may require manual closure as another step after cyclone bin assembly 160 is disconnected from wand 144 to complete the reconfiguration to the light weight upright mode. Alternatively, a single actuator may be manually operated to close the door and the diversion valve.

As exemplified in FIG. 4, apparatus 152 may be reconfigurable from the large dirt capacity upright mode to a light weight upright mode by disconnecting assembly 140, 160 from wand 144. In some cases, it may be desirable to momentarily reconfigure an apparatus to the lightweight upright mode to complete a task (e.g., clean under an article of furniture), and afterward reconfigure the apparatus to the large dirt capacity upright mode. In the illustrated example, the airflow path between surface cleaning head 104 and handvac 112 persists during and after reconfiguration of apparatus 100 from the large dirt capacity upright mode to the lightweight upright mode. This may permit apparatus 100, to be operated continuously (i.e., air to continue to travel between inlet 124 and outlet 132) before, during, and after reconfiguration to the lightweight upright mode. In turn, this may allow for a quick reconfiguration with little or no disruption. It will be appreciated that if a cyclone is provided in the supplemental assembly (e.g., assembly 160), there may be a short period during which the diversion valve is not closed during the transition.

In some cases, reconfiguring apparatus 100, 152, or 168 from the large dirt capacity upright mode to the lightweight upright mode may provide a reduction in weight (i.e., by the removal of dirt collection assembly 140 or cyclone bin assembly 160), and a more slender profile. Thus, the lightweight upright mode may make apparatus 100, 152, or 168 easier to lift (e.g., carry upstairs), and easier to maneuver under and around furniture and the like. However, in this mode, all of the dirt separated by cyclone bin assembly 136 in the lightweight upright mode is collected in dirt collection chamber 188. Thus, apparatus 100, 152, or 168 may have less dirt collection capacity in the lightweight upright mode as compared with the large dirt capacity upright mode.

Referring now to FIGS. 31-33, 44a, and 44b, apparatus 100 and 168 are shown in an above-floor cleaning mode. As illustrated, apparatus 100 and 168 in the above-floor cleaning mode include handvac 112 and wand 144. Apparatus 100, 152, and 168 may be reconfigured from the lightweight upright mode to the above-floor cleaning mode by disconnecting surface cleaning head 104 from wand 144. It will be appreciated that assembly 140, 160 may be retained in an above floor cleaning mode if desired. However, this would add extra weight to the apparatus in the above floor cleaning mode.

Referring to FIG. 36a, apparatus 152 is shown in another above-floor cleaning mode. As shown, apparatus 152 in an above-floor cleaning mode may include handvac 112 and an accessory wand 145. Accessory wand 145 may be provided supplementary to wand 144 of upright section 108. For

21

example, accessory wand **145** may be removably mountable to a sidewall of upright section **108**, as shown in FIG. **5**. Still referring to FIG. **36a**, in the above-floor cleaning mode shown, upstream end **360** may provide the dirty air inlet, and downstream end **364** may be removably fluidly connected to handvac nozzle **412**. Accessory wand **145** may have any suitable length **516**. For example, wand **144** may have a length sufficient to permit apparatus **100** to be used as an upright vacuum cleaner in the configuration of FIG. **5**. Accordingly, wand **144** may be 2-4 feet long. In contrast, accessory wand **145** may be shorter than wand **144** (e.g., a user wants to be closer to the area to be cleaned in an above floor cleaning mode) and accordingly accessory wand **145** may be 6-18 inches.

In the above-floor cleaning mode, the upstream end **496** of wand **144** may provide the dirty air inlet of apparatus **100**, **152**, or **168**. The above-floor cleaning mode may be well suited to cleaning surfaces above the floor, or more generally surfaces that are not substantially horizontal, and for cleaning in crevices which surface cleaning head **104** might be unable to access. The wand **144** may provide extended reach for distant cleaning surfaces (e.g., curtains, and ceilings). An auxiliary cleaning tool such as a crevice tool, brush or the like may be attached to the inlet end of the wand.

Preferably, apparatus **100**, **152**, or **168** may be reconfigured from the lightweight upright mode to the above-floor cleaning mode by a single user action—disconnection of surface cleaning head **104** from the upstream end **496** of wand **144**. This may permit the apparatus to be quickly reconfigured with little or no disruption. For example, the apparatus may operate continuously before, during, and after reconfiguration from the lightweight upright mode to the above-floor cleaning mode. This may permit a user to conveniently reconfigure the apparatus to the above-floor cleaning mode to clean a surface inaccessible in the lightweight upright mode, and afterward reconfigure the apparatus to the lightweight upright mode to continue cleaning, e.g., the floor.

In some embodiments, the above-floor cleaning mode may further include dirt collection assembly **140**. For example, a user may reconfigure apparatus **100**, **152**, or **168** from the large dirt capacity upright mode (FIGS. **1**, **5**, and **13**) to the above-floor cleaning mode by disconnecting surface cleaning head **104** from wand **144**, while maintaining dirt collection assembly **140** in place on wand **144**. An above-floor cleaning mode of this configuration may provide apparatus **100** with the reach of the above-floor cleaning mode, and the storage capacity of the large dirt capacity upright mode. In some embodiments, dirt collection assembly **140** may be a one piece assembly with the wand **144** (i.e., irremovably connected to wand **144**), in which case the wand **144** may be an up flow duct.

Referring to FIG. **22**, apparatus **100**, **152**, and **168** may be reconfigured to a handvac mode from any other mode of operation by disconnecting handvac **112** (e.g., from wand **144**). As illustrated, the handvac mode may include handvac **112** alone. In the handvac mode, upstream end **416** of nozzle or inlet conduit **412** may provide the dirty air inlet **131**. Optionally, one or more accessories (not shown), such as a brush, crevice tool, auxiliary wand **145** may be connected to nozzle **412**. If a wand **144** is part of dirt collection assembly **140** then an accessory wand **145** may be provided which is connectable to nozzle **412**.

The handvac mode of apparatus **100** may be lighter, smaller, and more agile than the other modes of operation. However, the handvac mode may have a smaller dirt col-

22

lection capacity than the large dirt capacity upright mode (FIGS. **1**, **5**, and **13**) for example.

In some cases, a user may wish to momentarily disconnect handvac **112** for use in the handvac mode (e.g., to clean a surface that is more accessible in the handvac mode), and then return the apparatus to the previous mode. For example, apparatus **100**, **152**, or **168** may be momentarily reconfigured from the large dirt capacity upright mode (FIGS. **1**, **5**, and **13**) or from the lightweight upright mode (FIGS. **27** and **37**) to the handvac mode be merely removing the handvac and afterward reconfigured again to the upright mode.

It may be beneficial for the dirt collection chamber **188** of handvac **112** to have capacity available for use in the handvac mode upon disconnecting handvac **112** from upright section **108**. Further, it may be beneficial for dirt collection chamber **188** of handvac **112** to reclaim capacity after reconnecting handvac **112** to upright section **108**. This may be achieved by having dirt collection chamber **188** empty into assembly **140**, **160** continually while handvac **112** is attached to the assembly, manually before removal of the handvac or upon removal of the handvac. The dirt capacity may be reclaimed by having dirt collection chamber **188** empty into assembly **140**, **160** upon replacing handvac **112** to the assembly (either manually or automatically upon replacement).

An example of such a reconfiguration is discussed with respect to the embodiment of FIG. **21**. In the illustrated example, handvac dirt collection chamber **188** has a bottom wall **216** that remains open to dirt collection assembly **140** while the handvac is attached to permit dirt from handvac dirt collection chamber **188** to transfer (e.g., by gravity) to dirt collection chamber **141** thereby preventing dirt collection chamber **188** from being filled while the apparatus is used in one of the upright operating modes.

Apparatus **100** may be reconfigured from the handvac mode to the large dirt capacity upright mode by reconnecting handvac **112** to upright section **108**. Preferably, reconnecting handvac **112** to upright section **108** automatically opens handvac dirt collection chamber **188** to dirt collection chamber **141** for transferring at least a portion of the dirt, collected while in the handvac mode, to dirt collection chamber **141** thereby emptying dirt collection chamber **188** so that dirt collection chamber **188** is not full when the handvac is once again used in the handvac mode.

In some embodiments, handvac dirt collection chamber **188** does not empty into assembly **140**, **160** when attached to the assembly, manually or automatically. For example, FIGS. **25** and **26** show exemplary embodiments of apparatus **152** and **168** where assemblies **160** and **188** receive and store dirt separately at all times. As shown, upright dirt collection chamber **141** may receive and collect dirt separated by auxiliary cyclone bin assembly **160**, and handvac dirt collection chamber **188** may separately receive and collect dirt separated by handvac cyclone bin assembly **136**.

Turning now to FIGS. **123-126**, apparatus **152** is shown in accordance with another embodiment. As exemplified, handvac cyclone bin assembly **136** may include a plurality of cyclonic cleaning stages arranged in series. For example, and referring to FIGS. **125** and **126**, cyclone bin assembly **136** may include a first cyclonic cleaning stage **640** arranged in series upstream from a second cyclonic cleaning stage **644**. First cyclonic cleaning stage **640** may include one or more air outlet(s) **196a** which discharge into air inlet(s) **192b** of second cyclonic cleaning stage **644**.

Referring now to FIG. **127**, each cyclonic cleaning stage **640** and **644** may include one or more cyclone chambers **184** in parallel. For example, cyclonic cleaning stages **640** and

23

644 may each include one cyclone chamber 184, or may each include a plurality of cyclone chambers 184. Alternatively, one of cyclonic cleaning stages 640 and 644 may include one cyclone chamber 184 and the other stage may include a plurality of cyclone chambers 184. In the illustrated example, first cyclonic cleaning stage 640 includes one cyclone chamber 184a, and second cyclonic cleaning stage 644 includes a plurality of cyclone chambers 184b arranged in parallel. For example, second cyclonic cleaning stage 644 may include four or more cyclone chambers 184b arranged in parallel.

Second stage cyclone chamber(s) 184b may have any suitable orientation relative to first stage cyclone chamber(s) 184a. For example, each of second stage cyclone chamber(s) 184b may have an air inlet 192b and an air outlet 196b both positioned proximate a rear end 648 of the second cyclonic cleaning stage 644 (rearward with respect to the inlet of the handvac), or both positioned proximate a front end 652 of the second cyclonic cleaning stage 644. Alternatively, each of second stage cyclone chamber(s) 184b may have an air inlet 192 positioned proximate one of the front and rear ends 648 and 652, and an air outlet 196b positioned proximate the other of the front and rear ends 648 and 652. In the illustrated example, second stage cyclone chambers 184b are shown including air inlets 192b at front end 648 and air outlets at rear end 652. This may reduce directional changes in the airflow which may reduce backpressure developed through second stage cyclone chambers 184b for enhanced airflow efficiency. As shown, axes 248b of second stage cyclone chamber 184b may be parallel to axis 248a of first stage cyclone chamber 184a.

Handvac cyclone bin assembly 136 may include one or more dirt collection regions 188. For example, cyclone chambers 184 of first and second cyclonic cleaning stages 640 and 644 may separate dirt into one common dirt collection region 188, or each cyclonic cleaning stage 640 and 644 may include a separate dirt collection region 188. In the latter case, all first stage cyclone chamber(s) 184a may discharge dirt into the first stage dirt collection region 188a, and all second stage cyclone chamber(s) 184b may discharge dirt into the second stage dirt collection region 188b. In the illustrated embodiment, handvac cyclone bin assembly 136 includes one first stage dirt collection region 188a, and a plurality of second stage dirt collection regions 188b, where each second stage dirt collection region 188b receives dirt discharged by a respective second stage cyclone chamber 184b.

Reference is now made to FIGS. 34-36, which show apparatus 100, 152, or 168 in a stair-cleaning mode of operation. As shown, apparatus 100, 152, or 168 in stair-cleaning mode may include handvac 112 directly connected to surface cleaning head 104. For example, nozzle 412 may be connected to pivot joint 116 of surface cleaning head 104.

The stair-cleaning mode of operation may be especially suitable for cleaning stairs and the like, where frequent lifting is required to clean the desired surface areas.

Handvac Center of Gravity in the Upright Modes

In accordance with another aspect of this disclosure, which may be used by itself or in combination with any one or more other aspects of this disclosure, when the apparatus is in an upright mode and, in particular in a large dirt capacity upright mode, the center of gravity of the handvac may be located directly above the cyclone bin assembly (or dirt collection chamber) of the upright section.

As exemplified in FIGS. 21 and 25, apparatus 100 is shown in a large dirt capacity upright mode in a storage position. In the illustrated example, handvac 112 is shown

24

including a handvac center of gravity 524. As shown, center of gravity 524 may be positioned vertically above dirt collection assembly 140/cyclone bin assembly 160 between the front and rear ends 532, 544 and 536, 548 of dirt collection assembly 140/cyclone bin assembly 160. Preferably, center of gravity 524 is positioned substantially centrally between front and rear ends 532, 544 and 536, 548 of dirt collection assembly 140/cyclone bin assembly and may be aligned with the wand.

Alternately, or in addition, as exemplified, center of gravity 524 is positioned between cyclone bin assembly 136 and suction motor 204, inside premotor filter chamber 556 of handvac 112.

Configuration of the Auxiliary Assembly

In accordance with another aspect of this disclosure, which may be used by itself or in combination with any one or more other aspects of this disclosure, a surface cleaning apparatus may have an upright section with an auxiliary dirt collection assembly 140 or auxiliary cyclone bin assembly 160 sized, shaped, and positioned according any one of a plurality of different configurations relative to the wand of the upright section and the handvac.

In some embodiments, a surface cleaning apparatus is provided having an upright mode wherein the auxiliary assembly 140, 160 and the handvac are positioned on the same side of the wand. As exemplified in FIGS. 1, 21, 24, 45, and 46, auxiliary assembly 140, 160 and handvac dirt collection chamber 188 may both extend rearwardly of wand 144. Referring to FIG. 21, rear end 536 of dirt collection assembly 140 is shown positioned a rearward distance 564 from wand axis 568. Bottom wall 216 of dirt collection chamber 188 is shown positioned a rearward distance 576 from wand axis 568. Preferably, distances 564 and 576 are substantially equal. In alternative embodiments, distances 564 and 576 may be different. For example, distance 560 may be greater than distance 576, or distance 576 may be greater than distance 564. If rear end 536 is at an angle to the vertical as exemplified, then the handvac is preferable designed such that the rear end does not extend rearwardly past a projection of the line of rear end 536. Accordingly, the lowest extend to which upright section 108 may be pivoted rearwardly is determined by the auxiliary assembly and not the handvac.

In some embodiments, a surface cleaning apparatus is provided having an upright mode wherein the auxiliary assembly 140, 160 and the handvac are positioned on opposite sides of the wand. As exemplified in FIG. 26, dirt collection assembly 140 of upright section 108 is positioned forwardly of wand 144, and handvac dirt collection chamber 188 is positioned rearwardly of wand 144. An advantage of this design is that the weight of the auxiliary assembly 140, 160 is on the opposite side of wand 144 from the handvac and may assist in offsetting the hand weight of the handvac felt by a user holding the handle of the handvac.

In some embodiments, a surface cleaning apparatus is provided having an upright mode where the auxiliary assembly 140, 160 and handvac are positioned on opposite left and right sides of the wand. For example, in apparatus 168, cyclone bin assembly 160 may be mounted to one of the left or right sides of upright section 108, and handvac 112 may be oriented relative to the upright section 108 such that dirt collection chamber 188 extends to the other of the left or right sides of upright section 108.

In some embodiments, the auxiliary assembly 140, 160 of the upright section surrounds at least a portion of the wand. Referring to FIGS. 1, 21, 24, 45 and 46, apparatus 100 is shown including an upright section 108 having dirt collec-

25

tion assembly 140 which partially surrounds wand 144. In the illustrated example, dirt collection assembly 140 includes a channel 584 for receiving at least a portion of wand 144. As shown, channel 584 may extend the height 588 of dirt collection assembly 140 between lower and upper ends 292 and 596. Channel 584 may also extend in depth from front end 532 rearwardly toward rear end 536.

As exemplified, dirt collection assembly 140 includes left and right portions 600 and 604 on opposite left and right sides of channel 584. In the upright mode of apparatus 100, wand 144 may be at least partially received in channel 584, whereby left and right portions 600 and 604 are positioned to the left and right sides of wand 144. As shown, a front end 532 of dirt collection assembly 140 may extend forwardly of wand 144, such that at least a portion of wand 144 is positioned between the front and rear ends 532 and 536 of dirt collection assembly 140.

In the illustrated embodiment, dirt collection assembly 140 may also surround at least a portion of handvac 112 in the upright mode of apparatus 100. In the illustrated embodiment, an outlet end 608 of wand 144 may be received in channel 584 of dirt collection assembly 140. Accordingly, a front portion of handvac 112 may extend into channel 584 for connection with outlet end 608 of wand 144. In the illustrated embodiment, nozzle 412 and inlet passage 420 of handvac 112 may be positioned inside channel 584 of dirt collection assembly 140 in the upright mode of apparatus 100.

Upright section with a Plurality of Cyclones

In accordance with another aspect of this disclosure, which may be used by itself or in combination with any one or more other aspects of this disclosure, the supplemental cyclone bin assembly 160 may have a plurality of cyclones positioned in series and/or in parallel in the airflow path. The cyclones may be positioned to the same side of the upright section (e.g., front or back, left or right), or on different sides of the upright section (e.g., one front and one back or one on the right side and one on the left side). In one embodiment, the upright section may use two cyclones and the wand may be positioned between the two cyclones.

As exemplified in FIGS. 47-51, auxiliary cyclone assembly 160 comprises first and second supplemental cyclone bin assemblies 161, which may be individual units or may be formed as a single unit or housing. Each cyclone bin assembly 161 is shown including a cyclone chamber 308 and a dirt collection chamber 141. Dirt collection chambers 141 may be combined to form a common repository for dirt separated by both cyclone bin assemblies 161 or each cyclone bin assembly 161 may have a separate dirt collection chamber 141.

Each cyclone chamber 308 may be any suitable cyclone chamber and maybe the same or different. As shown, each cyclone chamber 308 may include a tangential air inlet 344 proximate upper end 374, and an axial air outlet 320 at a downstream end of vortex finder 400.

Cyclone bin assemblies 161 may be positioned in parallel in the airflow path between surface cleaning head 104 and handvac 112. As exemplified, the airflow path may extend from surface cleaning head 104 through an upstream wand portion 440, diverge into the inlets 316 of cyclone chambers 308 through cyclone chambers 308 to their respective air outlets 320. Each cyclone bin assembly 161 may include an outlet passage 476 connecting air outlets 320 to downstream portion 444 of wand 144 where the airflow path converges. From downstream portion 444 of wand 144, the airflow path may extend through handvac 112 and exit out clean air outlet 132.

26

As exemplified, upstream and downstream portions 440 and 444 of wand 144 may be divided by a diversion member 712, which is described subsequently with respect to a further alternate aspect. Air traveling downstream through upstream portion 440 may contact diversion member 712 and be redirected laterally into air inlets 316 of cyclone chambers 308. Outlet passages 476 of cyclone bin assemblies 161 may converge to form a single airflow path in downstream portion 444 of wand 144 above diversion member 712.

Diversion Valve

In accordance with another aspect of this disclosure, which may be used by itself or in combination with any one or more other aspects of this disclosure, a diversion valve is provided which diverts air travelling through upright section 108 (e.g., the wand 144) into the auxiliary assembly 160 (e.g., supplemental cyclone or cyclones 308). Preferably, the diversion valve operates automatically upon the auxiliary assembly 160 being disconnected from and/or connected to the surface cleaning apparatus.

As exemplified in FIG. 20, cyclone bin assembly 160 may be selectively connected to upright section 108 whereby the airflow path may be reconfigured to extend through cyclone bin assembly 160. Similarly, cyclone bin assembly 160 may be selectively disconnected from upright section 108 whereby the airflow path may be reconfigured to extend through wand 144 from end to end without diversion. Preferably, the airflow path reconfiguration is automatic upon connection and/or disconnection of cyclone bin assembly 160 to upright section 108.

In some embodiments, wand 144 may include a diversion outlet 704 and a diversion inlet 708 positioned between the upstream and downstream ends 360 and 364 of wand 144. The diversion outlet 704 and diversion inlet 708 may be selectively opened when connecting cyclone bin assembly 160 to upright section 108 to reconfigure the airflow path to divert into the cyclone bin assembly 160 at diversion outlet 704, and to return to the wand 144 from cyclone bin assembly 160 at diversion inlet 708. Upright section 108 may include a diversion valve for opening and closing diversion outlet 704 and inlet 708.

A diversion valve 712 according to a first embodiment is exemplified in FIGS. 52-57. As exemplified, diversion valve 712 may include a sleeve 716 positioned inside of wand 144, and a pedal 720 for moving sleeve 716 between an open position and a closed position.

Sleeve 716 may be a conduit for fluidly coupling upstream and downstream wand portions 440 and 444 in the closed position of diversion valve 712 (see FIGS. 52 and 55) to bypass diversion outlet and inlet 704 and 708. Preferably, sleeve 716 may be a rigid conduit. Alternatively, sleeve 716 may include flexible and/or collapsible elements. Effectively, sleeve 716 may close diversion outlet and inlet 704 and 708 in the closed position of diversion valve 712. Optionally, diversion valve 712 may include one or more sealing members (e.g., O-rings) which may form an air-tight seal between sleeve 716 and upstream wand portion 440, and between sleeve 716 and downstream wand portion 444 to help prevent the escape of air through diversion outlet and inlet 704 and 708 in the closed position of diversion valve 712.

Sleeve 716 may be movable axially along wand 114 between the closed position (FIGS. 52 and 55) and the open position (FIGS. 54 and 57). Preferably, sleeve 716 is moved to the open position automatically by mounting cyclone bin assembly 160 to upright section 108 (e.g., connecting to wand 144), and/or moved to the closed position automati-

27

cally by dismounting cyclone bin assembly 160 from upright section 108 (e.g., disconnecting from wand 144). In the illustrated embodiment, sleeve 716 is drivingly coupled to a pedal 720. Pedal 720 may be depressed to move sleeve 716 from the closed position of FIGS. 52 and 55 to the open position of FIGS. 54 and 57. As shown, pedal 720 may be positioned axially below sleeve 716 and extend outwardly of wand 144 to be depressed by cyclone bin assembly 160 when mounting cyclone bin assembly 160 to upright section 108. Pedal 720 and sleeve 716 may be integrally molded, or separately formed and connected, to move axially up and down as a unit.

As exemplified, pedal 720 and sleeve 716 may be movably mounted to wand 144 for axial movement between the open and closed position. As shown, pedal 720 and sleeve 716 may move downwardly from the closed position (FIGS. 52 and 55) to the open position (FIGS. 54 and 57). In the closed position, sleeve 716 may extend the airflow path directly across the threshold between the upstream and downstream wand portions 440 and 444. In the open position, sleeve 716 may be retracted into the upstream wand portion 440 to open diversion outlet 704 and inlet 708, and thereby permit the airflow path to be diverted through diversion outlet 704, cyclone bin assembly 160 and diversion inlet 708. As shown, diversion outlet 704 may be positioned at a downstream end 724 of upstream wand portion 440, and diversion inlet 708 may be positioned at an upstream end 728 of downstream wand portion 444.

In an alternative embodiment, sleeve 716 may have one or more openings which align with diversion outlet and inlet 704 and 708 in the open position of valve 712. In the closed position, the openings in sleeve 716 may be closed by alignment with solid wall portions of wand 144, and diversion outlet and inlet 704 and 708 may be closed by alignment with solid wall portions of sleeve 716. In this case, sleeve 716 may be positioned inside the upstream and downstream wand portions 440 and 444 in both the open and closed positions of valve 712.

Preferably, sleeve 716 is biased to the closed position. For example, valve 712 may include a biasing member which acts on sleeve 716 to bias sleeve 716 to the closed position. In the illustrated example, valve 712 includes a spring 732 which acts on pedal 720 to urge pedal 720 and sleeve 716 upwardly to the closed position. In alternative embodiments, sleeve 716 may not be biased to the closed position. For example, sleeve 716 may include an actuator, such as a switch or lever, which must be manually activated to move sleeve 716 to the closed position or is moved by assembly 160 when assembly 160 is removed.

Still referring to FIGS. 52-57, cyclone bin assembly 160 may include an engagement member for mating with pedal 720 to mount cyclone bin assembly 160 on pedal 720. In the illustrated example, a cavity 736 is formed in sidewall 376 of cyclone bin assembly 160 for receiving pedal 720. In use, cyclone bin assembly 160 may be set onto pedal 720 such that pedal 720 is received in cavity 736. Preferably, the weight of cyclone bin assembly 160 on pedal 720 is sufficient to overcome the bias of valve biasing member 732, and move pedal 720 and sleeve 716 downwardly to the open position. In alternative embodiments, additional downward force must be applied by the user to move pedal 720 and sleeve 716 downwardly against the bias of the biasing member 732 and/or an actuator, such as a foot pedal, may be utilized.

Cyclone bin assembly 160 may be toed onto pedal 720 (see e.g., FIGS. 53, 56), and then pivoted on pedal 720 into position (see e.g., FIGS. 54, 57) after pedal 720 and sleeve

28

716 have moved downwardly to the open position. In the illustrated example, cyclone bin assembly 160 may be set onto pedal 720 with cyclone axis 392 extending at a (non-zero) angle to wand axis 740, and then lowered with pedal 720 to move valve 712 to the open position, and finally pivoted about pedal 720 toward wand 144 to complete the connection of cyclone bin assembly 160 to wand 144. A locking member, such as a latch 744, which may be located at the end of the upper end of wand 144, may be provided to secure assembly 160 in position. In some embodiments, cyclone axis 392 may be substantially parallel to wand axis 740 when cyclone bin assembly 160 is connected to wand 144.

Cyclone bin assembly 160 may include a diversion member 428 for dividing wand 144 into upstream and downstream wand portions 440 and 444, and for diverting flow from the upstream wand portion 440 into cyclone bin assembly inlet 316. Diversion member 428 may take any suitable form. In the illustrated embodiment, diversion member 428 is a substantially flat plate which extends outboard of sidewall 376 for protruding into wand 144 through one of diversion outlet 704, diversion inlet 708, or another opening into wand 144. Alternatively, diversion member 428 may be curved to provide a less abrupt change in airflow direction, which may reduce the pressure drop across the diversion member 428. Optionally, diversion member 428 may include or interface with a sealing member (e.g., a deformable elastomeric seal) to form an airtight barrier between upstream and downstream wand portions 440 and 444. Alternately, the diversion member may be a separate member that is installed as a separate step when (i.e., before, during, and/or after) connecting cyclone bin assembly 160 to the wand 144.

As exemplified, when cyclone bin assembly 160 is mounted to wand 144, as shown in FIGS. 54 and 57, air inlet 316 of cyclone chamber 308 is connected to diversion outlet 704 for receiving air from upstream wand portion 440 into cyclone chamber 308, and outlet passage 476 is connected to diversion inlet 708 for discharging air from cyclone bin assembly 160 into downstream wand portion 444.

Cyclone bin assembly 160 may be removably mounted to wand 144 by any suitable mechanism. In the illustrated embodiment, cyclone bin assembly 160 includes a latch 744 on handle 616 for engaging a tab 746 which extends outwardly of wand 144. Latch 744 may be user-operable by a user grasping handle 616 to release latch 744 from tab 746 for disconnecting cyclone bin assembly 160 from wand 144. Preferably, biasing member 732 of valve 712 automatically and immediately moves sleeve 716 to the closed position upon disconnection of cyclone bin assembly 160 to reconfigure the airflow pathway by closing diversion inlet and outlet 704 and 708.

A diversion valve 712 according to a second embodiment is exemplified in FIGS. 58-63. Diversion valve 712 is similar to diversion valve 712 of FIGS. 52-57 in many respects except, for example that sleeve 716 is embodied by a collapsible hose 716 instead of a more rigid conduit.

As exemplified, diversion valve 712 includes a collapsible sleeve 716 positioned inside of wand 144, and a pedal 720 for moving hose 716 between an open position and a closed position.

Sleeve 716 may be a collapsible conduit for fluidly coupling upstream and downstream wand portions 440 and 444 in the closed position of diversion valve 712 (see FIGS. 60 and 63) to bypass diversion inlet and outlet 708 and 712. Optionally, diversion valve 712 may include one or more seals (e.g., O-rings) which form an air-tight seal between

29

sleeve 716 and upstream wand portion 440, and between sleeve 716 and downstream wand portion 444 to help prevent the escape of air through diversion inlet and outlet 704 and 708 in the closed position of diversion valve 716.

In the illustrated embodiment, sleeve 716 has a fixed-position upstream end 756 sealed to upstream wand portion 440, and a downstream end 760 axially movable inside wand 144. Downstream end 760 may be movable toward upstream end 756 to the open position (FIGS. 60 and 63) whereby sleeve 716 is partially collapsed with downstream end 760 positioned in the upstream wand portion 440 upstream of diversion outlet 704. Downstream end 760 may also be movable away from upstream end 756 to the closed position (FIGS. 58 and 61) whereby sleeve 716 is extended with downstream end 760 positioned in the downstream wand portion 444 downstream of diversion inlet 708.

As exemplified, pedal 720 may be drivingly coupled to downstream end 760 of sleeve 716. Pedal 720 may be depressed (e.g. by the weight of cyclone bin assembly 160) to move downstream end 760 into the upstream wand portion 440, collapsing sleeve 716 into the open position of FIGS. 60 and 63. Pedal 720 may also be raised (e.g. automatically by action of biasing member 732 upon release of pedal 720 or pulled upwardly by assembly 160) to move downstream end 760 into the downstream wand portion 444, extending sleeve 716 into the closed position of FIGS. 58 and 61. Alternately, a manual actuator may be used.

A diversion valve 712 according to a third embodiment is exemplified in FIGS. 64-71. As exemplified, diversion valve 712 may include a diversion outlet door 772 and a diversion inlet door 776. Doors 772 and 776 may be opened when cyclone bin assembly 160 is connected to wand 144 for reconfiguring the airflow path to extend through cyclone bin assembly 160. Doors 772 and 776 may also be closed when cyclone bin assembly 160 is disconnected from wand 144 for reconfiguring the airflow path to extend directly across the threshold between upstream and downstream wand portions 440 and 444.

In the illustrated embodiment, doors 772 and 776 are pivotally mounted to wand 144 for movement between a closed position (see FIGS. 64 and 67-69) in which doors 772 and 776 seal diversion outlet 704 and inlet 708 respectively, and an open position (see FIGS. 66 and 71) in which doors 772 and 776 are open to allow air to flow through doors 772 and 776 between wand 144 and cyclone bin assembly 160. Doors 772 and 776 may be pivotally mounted to wand 144 in any suitable manner. In the example shown, doors 772 and 776 are pivotally mounted to wand 144 by a common hinge 780. As shown, door 772 may pivot inwardly about hinge 780 toward a downstream direction, and door 776 may pivot inwardly about hinge 780 toward an upstream direction. In alternative embodiments, each of doors 772 and 776 may be pivotally mounted to wand 144 by a different hinge.

Preferably, doors 772 and 776 open automatically by connecting cyclone bin assembly 160 to wand 144. In the illustrated example, cyclone bin assembly 160 includes an inlet nose 784 for pushing open diversion outlet door 772, and an outlet nose 788 for pushing open diversion inlet door 776. As shown, noses 784 and 788 may extend outwardly of sidewall 376 for projecting through diversion outlet and inlet 704 and 708 respectively upon connecting cyclone bin assembly 160 to wand 144.

Preferably, when cyclone bin assembly 160 is connected to wand 144, an airflow path is formed between diversion outlet 704 and air inlet 316, and between diversion inlet 708 and air outlet 320, such that the airflow path from upstream wand portion 440 to downstream wand portion 444 is

30

reconfigured to extend through cyclone bin assembly 160. In the illustrated example, connecting cyclone bin assembly 160 to wand 144 may include pushing noses 784 and 788 into diversion outlet and inlet 704 and 708 respectively to open doors 772 and 776.

Noses 784 and 788 may take any suitable form. As exemplified, nose 784 may be formed as a diversion member including an inlet passage having an upstream end 792 and a downstream end 796. Upstream end 792 may extend into wand 144 and form a seal with upstream wand portion 440 to redirect the airflow in upstream wand portion 440 to enter nose 784 toward downstream end 796. In the illustrated embodiment, upstream wand portion 440 includes a sealing ring 800 adjacent an upstream side 804 of diversion outlet door 772 onto which downstream end 796 may be seated for forming an airtight seal between upstream wand portion 440 and downstream end 796. Alternatively, or in addition, upstream side 804 may include a sealing member. Downstream end 796 of nose 784 may be integrally formed or otherwise connected with air inlet 316.

In the illustrated example, nose 788 is formed as a triangular plate which projects outwardly from air outlet 320. In other embodiments, nose 788 may have another suitable form for pushing diversion inlet door 776, such as a circular or rectangular plate or a rod for example. As shown, when cyclone bin assembly 160 is connected to wand 144, nose 788 projects into diversion inlet 708 pushing open diversion inlet door 776. This may permit air outlet 320 to sealingly abut diversion inlet 708 for forming an airflow path between air outlet 320 and downstream wand portion 444. Optionally, a seal 808 may be provided at the interface between air outlet 320 and diversion inlet 708 for enhancing the airtightness of the connection.

It will be appreciated that in alternative embodiments, nose 788 may be formed as an outlet passage, which may be curved similar to nose 784. This may make the change in airflow direction across nose 788 less abrupt, which may reduce pressure losses.

Preferably, when cyclone bin assembly 160 is disconnected from wand 144, doors 772 and 776 automatically close to reconfigure the airflow passage to extend directly from upstream wand portion 440 to downstream wand portion 444 without diversion through diversion outlet 704 or inlet 708. For example, doors 772 and 776 may be biased to the closed position by a biasing member, such as a spring. In the illustrated embodiment, diversion valve 712 includes a torsional spring 812. Spring 812 may be positioned to bias both of doors 772 and 776 to the closed position. In the illustrated embodiment, spring 812 is held in a spring housing 816 mounted to an inside face 820 of diversion outlet door 772. As shown, spring 812 may have an arm 824 connected to diversion inlet door 776, effectively biasing doors 772 and 776 away from each other to their respective closed positions. In alternative embodiments, each of doors 772 and 776 may have a separate biasing member.

A diversion valve 712 according to a fourth embodiment is exemplified in FIGS. 72-77. Diversion valve 712 is similar to diversion valve 712 of FIGS. 64-71 in many respects except, for example, the door which selectively closes diversion outlet 704 and inlet 708.

In the illustrated embodiment, diversion valve 712 includes a door 772. Door 772 may be movable between a closed position (FIGS. 72 and 75) in which door 772 seals diversion outlet 704 and inlet 708, and an open position (FIGS. 74 and 77) in which door 772 is unsealed from outlet 704 and inlet 708 to allow the airflow to pass through diversion outlet 704 and inlet 708. As exemplified, diversion

31

valve **712** may include one door **772** for closing both of diversion outlet **704** and inlet **708**, or separate doors **772** for diversion outlet **704** and inlet **708**.

As shown, door **772** may be pivotally mounted to wand **144** in any suitable manner for movement between the open and closed positions. For example, door **772** may be pivotally mounted outside of wand **144** by a hinge **780**. In the illustrated example, door **772** may pivot outwardly about hinge **780** away from wand **144** to the open position, and may pivot inwardly about hinge **780** toward wand **144** to the closed position. Preferably, door **772** is manually openable, whereby a user may grasp door **772** and manually move door **772** from the closed position to the open position. For example, door **772** may have a lever **840**, a handle, or another gripping member for a user to grasp for manipulating the position of door **772**.

Once door **772** is opened, as shown in FIGS. **73** and **76**, cyclone bin assembly **160** may be connected to wand **144**. In the illustrated embodiment, cyclone bin assembly **160** includes a diversion member **428** of the type describe above with reference to FIGS. **52-57**. Diversion member **428** may be moved into wand **144** through diversion outlet **704**, diversion inlet **708**, or another opening in wand **144**, for dividing wand **144** into an upstream portion **440** and a downstream portion **444**, substantially as described above.

When cyclone bin assembly **160** is disconnected from wand **144**, door **772** may be moved back into the closed position for reconfiguring the airflow path in wand **144** to extend directly from upstream portion **440** to downstream portion **444** without diversion. For example, door **772** may be manually moved from the open position to the closed position by hand, or door **772** may move automatically to the closed position by the bias of a biasing member (e.g., a spring).

In some embodiments, door **772** may be held in the closed position by the bias of a biasing member, or by a releasable locking mechanism (e.g., a latch). This may permit door **772** to form a tight seal against diversion outlet **704** and inlet **708**.

In some embodiments, pedal **720** may be foot operable and may be located close to or on the surface cleaning head. Angular Surface of Upright Section

In accordance with another aspect of this disclosure, which may be used by itself or in combination with any one or more other aspects of this disclosure, a surface cleaning apparatus is provided having an upright section with a dirt collection chamber or cyclone bin assembly having a side profile that tapers or narrows from top to bottom. For example, the rear wall of the supplemental dirt collection chamber or supplemental cyclone bin assembly may extend upwardly at an acute angle relative to the wand axis such that the rear wall is farther from the wand axis at the top end than at the bottom end of the dirt collection chamber or cyclone bin assembly. An advantage of this design is that the surface cleaning apparatus may extend under furniture while providing a large dirt collection capacity.

As exemplified in FIGS. **3** and **7**, surface cleaning apparatus **100** and **152** include an upright section **108** having a dirt collection chamber **140** or cyclone bin assembly **160** that extends from a lower end **292**, **856** proximate surface cleaning head **104** to an upper end **596**, **860**. A rear end **536**, **548** of auxiliary assembly **140/160** may extend upwardly from lower end **292** or **856** at a (non-zero) acute angle **848** to wand axis **568**. Angle **848** is preferably between 10 and 70 degrees, and more preferably between 20 and 40 degrees. For example, a distance **538** between wand axis **568** and rear end **536**, **548**, measured normal to wand axis **568**, may

32

increase continually or generally continuously from lower end **292**, **856** upwardly. As shown, distance **538** is greater at upper end **596**, **860** than at lower end **292**, **856**.

Handvac with Angled Bottom Wall

In accordance with another aspect of this disclosure, which may be used by itself or in combination with any one or more other aspects of this disclosure, a handvac may be provided having a bottom, such as a flat bottom wall, for supporting the handvac on a horizontal surface, and which extends at an acute angle (e.g., between 20 and 40 degrees) away from the inlet nozzle axis, and optionally at about the in-use orientation of the hand vac. This may provide the handvac with a resting orientation that is closer to or essentially at the in-use orientation of the handvac. For example, the in-use orientation of the handvac may normally have the inlet nozzle axis extending at a downward angle relative to a horizontal surface to be cleaned. Thus, a user may not have to substantially reorient the handvac upon grasping the handvac in the resting orientation to reposition the handvac into the in-use orientation.

Reference is now made FIG. **78**, where handvac **112** is shown resting on a horizontal surface **876**. As shown, nozzle axis **884** extends at an angle **880** to horizontal surface **876**. Angle **880** may be an acute angle which may be between 10 and 80 degrees, and preferably between 25 and 65 degrees, more preferably between 35 and 55 degrees or between 20 and 40 degrees. It will be appreciated that handvac **112** may be stably supported in any suitable manner, with nozzle axis **884** extending at angle **880** to horizontal surface **876**. For example, handvac **112** may include one or more support elements (e.g., a wall or feet) which collectively provide a support for handvac **112** on a horizontal planar surface at a desired acute angle, and a center of gravity **524** vertically aligned with or between the support elements for stability when handvac **112** is so supported by the support element(s) on the horizontal surface.

As exemplified, bottom wall **216** of handvac **112** may extend at an angle **880** to inlet nozzle axis **884** of nozzle **412**. Bottom wall **216** may be planar, and the plane of bottom wall **216** may intersect with nozzle axis **884** at angle **880**. Bottom wall **216** may provide a flat planar surface for making broad contiguous contact with horizontal surface **876**, or bottom wall **216** may include a plurality of discrete contact points or surfaces which collectively contact the horizontal surface **876** to support the handvac **112** (e.g., as in the feet of a tripod, or the wheels of a car). Preferably, handvac center of gravity **524** is preferably aligned vertically above bottom wall **216** when handvac **112** is supported on horizontal surface **876** by bottom wall **216**. This may permit handvac **112** to rest stably (i.e., statically without tipping over) on horizontal surface **876** while supported solely by bottom wall **216**.

Handvac **112** may have an in-use orientation relative to horizontal surface **876** at which a user may comfortably operate handvac **112** during cleaning. Typically, handvac **112** is most comfortably operated in an orientation that does not require an application of torque by the user's hands when the handvac **112** is held by handle **484**. This may be the case where the center of gravity **524** of the handvac **112** is aligned vertically below the user's hand. Accordingly, the center of gravity **524** may be vertically aligned below handle **484** in comfortable in-use orientations of handvac **112**.

Preferably, center of gravity **524** is aligned vertically below handle **484** when handvac **112** is supported on horizontal surface **876**. In the illustrated embodiment, center of gravity **524** is aligned vertically below handle **484** when bottom wall **216** is horizontal and supporting handvac **112**

33

on a horizontal surface **876**. Thus, the resting orientation of handvac **112** supported by bottom wall **216** on a horizontal surface **876** may be substantially the same as the in-use orientation of handvac **112**. Accordingly, when a user grasps handvac **112** by handle **484** and lifts handvac **112**, handvac **112** may already be in a balanced in-use position with the center of gravity **524** aligned below the user's hands.

In many cases, handvac **112** may be stored on a surface below a user's elbows. A user may angle their forearm downwardly to grasp handle **484** of handvac **112**. In this case, the user's fingers and palm may be naturally aligned for grasping a handle which is angled forwardly of vertical. For example, to grasp a vertically oriented handle that is positioned below a user's elbow, a user may need to contort their wrist to conform to the orientation of the handle.

In the illustrated embodiment, handle axis **888** of handle **484** extends at a (non-zero) forward angle **892** to the vertical (e.g., e.g., when bottom wall **216** is horizontal). This may provide a comfortable handle alignment for grasping by a user when picking up handvac **112**, and when using handvac **112** for cleaning surfaces below the user's elbows. Preferably, angle **892** is an acute angle of between 10 and 80 degrees, more preferably between 20 and 70 degrees and most preferably between 30 and 60 degrees.

Bottom wall **216** may be a wall of any component of handvac **112**. In the illustrated embodiment, bottom wall **216** is a wall of cyclone bin assembly **136**. Preferably, bottom wall **216** is a wall of dirt collection chamber **188**. In the example shown, bottom wall **216** is an openable wall of dirt collection chamber **188**. FIG. **79** shows another embodiment of handvac **112** where bottom wall **216** is not openable.

Referring to FIG. **78**, bottom wall **216** of handvac **112** may include front wheels, rear wheels, or both. Wheels may provide rolling support for handvac **112** when cleaning under furniture, for example. In alternative embodiments, handvac **112** may not include wheels on bottom wall **216** as shown.

Handle Position

In accordance with another aspect of this disclosure, which may be used by itself or in combination with any one or more other aspects of this disclosure, a floor cleaning apparatus is provided having a handvac with a handle, and an upright section with a cyclone bin assembly or dirt collection chamber with a handle. Preferably, the handles are centrally aligned with a plane of symmetry of the apparatus. This may permit the handles to be grasped for a balanced control of the apparatus. For example, the handles may be parallel to the same plane of symmetry.

Alternately, as exemplified in FIG. **2**, one handle may be parallel to a plane of symmetry and the other transverse thereto but positioned such that the plane of symmetry extends through the transversely oriented handle. In the illustrated example, handvac **112** includes a handle **484** which extends along a handle axis **888**. As exemplified, handle axis **888** may lie in a vertical plane **1044**, which is aligned centrally between left and right sides of apparatus **100** (i.e., a plane of symmetry). Turning to FIG. **78**, handle **484** is shown extending in length between a first handle end **1048** at the upper end **1052** of handvac **112**, and a second handle end **1056** intermediate the upper and lower ends **1052** and **1060** of handvac **112**.

Returning to FIG. **2**, assembly **140** is shown including a handle **1064**. As illustrated, handle **1064** may have a handle axis **1068** which extends perpendicularly or transverse to plane **1044** and handle axis **888**. Handle **1064** may be formed in a rear end **536** of assembly **140**. For example, handle **1064** may be flush with rear end **536** and include a

34

concave finger cavity **1072** to facilitate grasping handle **1064**. Preferably, handle **1064** is positioned laterally centrally such that plane **1044** intersects handle **1064**, and optionally bisects handle **1064** at a midpoint between handle ends **1076** and **1080**.

Handles **484** and **1064** may be positioned on opposite sides of surface cleaning apparatus **100**. For example, handle **484** is shown extending from an upper end **1052** proximate the front surface of apparatus **100**, and handle **1064** is shown extending flush with a rear surface of apparatus **100**.

Apparatus **100** may include one or more actuator controls (e.g., buttons, levers, or switches) for controlling various functionality such as opening or disconnected elements, or connecting power to elements. Preferably, at least some of the actuator controls are positioned on or within finger reach of a handle to permit the control to be activated while grasping the handle. This may permit single handed operation of the function provided by the control.

Referring to FIG. **1**, apparatus **100** is shown including a power switch **1084** located on upper end **1052** of handvac **112** proximate first handle end **1048** within finger-reach when grasping handvac handle **484**. As illustrated, power switch **1084** may be laterally centrally positioned such that plane **1044** intersects and more preferably bisects power switch **1084**.

Referring now to FIGS. **15** and **16**, apparatus **168** is shown including an upright section **108** having a cyclone bin assembly **160** with a handle **616**, and handvac **112** with handle **484**. As shown, handle axis **1092** of handle **616**, and handle axis **888** of handvac handle **484** may extend in a same plane **1096**. Preferably, plane **1096** is a vertical plane positioned laterally centrally between left and right sides of apparatus **168** as shown. In the illustrated embodiment, plane **1096** bisects handles **616** and **484**.

In the illustrated embodiment, handvac **112** includes a power switch **1084** located on upper end **1052** of handvac **112** which is bisected by plane **1044**. Handle **616** of cyclone bin assembly **160** is also shown including a button **1100** for releasing latch **744** to disconnect cyclone bin assembly **160** from wand **144**. As illustrated, button **1100** may be positioned laterally centrally between left and right sides of apparatus **168** such that button **1100** is bisected by plane **1096**.

Handvac Axial Alignment

In accordance with another aspect of this disclosure, which may be used by itself or in combination with any one or more other aspects of this disclosure, a plurality of airflow path segments in the handvac may extend in parallel. In some cases, this may reduce the number of bends in the airflow path through the handvac, which may reduce the pressure drop across the airflow path.

As exemplified in FIG. **96**, handvac inlet nozzle **412** may extend in length from an inlet end or upstream nozzle end **416** (dirty air inlet **131**) rearwardly along a nozzle axis **884**, handvac cyclone chamber **184** may extend from an air inlet **192** along a cyclone axis **248** to an air outlet **196**, and handvac suction motor **204** may extend from a motor inlet **1108** along a motor axis **252** to a motor outlet **1112**.

In some embodiments, two or more of nozzle axis **884**, cyclone axis **248**, and motor axis **252** may be parallel. For example, in the illustrated embodiment, nozzle axis **884**, cyclone axis **248**, and motor axis **252** are parallel. In some embodiments, two or more of nozzle axis **884**, cyclone axis **248**, and motor axis **252** may be co-axial. For example, in the illustrated embodiment, nozzle axis **884** and cyclone axis **248** are co-axial. In other embodiments, nozzle axis **884**, cyclone axis **248**, and motor axis **252** may all be co-axial.

35

In the illustrated embodiment, handvac 112 may include an electrical connector 1116 for providing power to an upstream attachment (e.g., a surface cleaning head). As shown, connector 1116 may extend from a front connector end 1120 along a connector axis 1124 to a rear connector end 1128. In some embodiments, connector axis 1124 may be parallel to one or more of nozzle axis 884, cyclone axis 248, and motor axis 252. In the illustrated embodiment, connector axis 1124 is parallel to nozzle axis 884, cyclone axis 248, and motor axis 252.

In some embodiments, handvac 112 may include one or more electrical cables 1132 which extend from electrical connector 1116 rearwardly to electrically couple electrical connector 1116 with a source of power (not shown). In the illustrated embodiment, electrical cables 1132 extend from electrical connector 1116 rearwardly along vortex finder 1136 of cyclone chamber 184 toward motor housing 1138. As shown, at least the portion of electrical cables 1132 which along vortex finder 1136 across cyclone chamber 184 is parallel to cyclone axis 248.

Axial Cyclone Inlet

In accordance with another aspect of this disclosure, which may be used by itself or in combination with any one or more other aspects of this disclosure, a handvac may be provided having a cyclone chamber with an axial inlet. That is, the inlet axis may be parallel to the cyclone axis, and more preferably co-axial with the cyclone axis. In some cases, this may reduce the bends in the airflow path through the cyclone, which may reduce the pressure drop across the cyclone for better pneumatic efficiency. Preferably, the cyclone is a uniflow cyclone wherein the air outlet is at the opposite end from the air inlet. Alternately, or in addition, the axial inlet includes a portion that converts the axial flow to a tangential flow wherein the portion is provided within the diameter of the cyclone chamber. Optionally, the axial inlet is parallel to and may be co-axial with the handvac air inlet.

As exemplified in FIG. 96, handvac cyclone chamber 184 includes an air inlet 192 and an air outlet 196. As shown, air inlet 192 may include an inlet axis 1140 which is parallel to cyclone axis 248. Air inlet 192 may have a circular section transverse to axis 1140 with an inlet diameter 1144, or rectangular with a side dimension 1144. Preferably, the cross-sectional area of air inlet 192 is approximately equal to the cross-sectional area of inlet nozzle 412. Preferably, the cross-sectional area of air inlet 192 is between 80%-125% of the cross-sectional area of the inlet nozzle 412, more preferably 90%-120%, and most preferably 100%-115%.

Preferably, inlet 192 is in fluid communication with an upstream end 388 of an inlet passage 384. Inlet passage 384 may redirect the axial flow through inlet 192 to a tangential flow for developing a cyclonic motion inside cyclone chamber 184. Referring to FIGS. 23 and 23a, inlet passage 384 may extend from upstream passage end 388 to downstream passage end 396 across an arcuate angular extent 1148. Preferably angular extent 1148 is between 45 and 300°, more preferably between 60 and 250°, and most preferably between 90 and 200°.

Returning to FIG. 96, inlet passage 384 is shown having a width 1152, and a height 1108. In some embodiments, the cross-sectional area of inlet passage 384 may be approximately equal to the cross-sectional area of air inlet 192. Preferably, the cross-sectional area of inlet passage 384 is between 80%-125% of the cross-sectional area of the inlet passage 384, more preferably 90%-120%, and most preferably 100%-115%.

36

Vortex finder 1136 may define an outlet passage to air outlet 196 of cyclone chamber 184. As shown, vortex finder 1136 may be substantially cylindrical having a diameter 1160. In the illustrated embodiment, the cross-sectional area of vortex finder 1136 may be approximately equal to the cross-sectional area of inlet nozzle 412. For example, diameter 1160 may be approximately equal to diameter 1164 of inlet nozzle 412. Preferably, the cross-sectional area of vortex finder 1136 is between 80%-125% of the cross-sectional area of the inlet nozzle 412, more preferably 90%-120%, and most preferably 100%-115%.

Uniflow Cyclone

In accordance with another aspect of this disclosure, which may be used by itself or in combination with any one or more other aspects of this disclosure, a handvac may be provided having a cyclone chamber wherein the air outlet is at the opposite end from the air inlet. In some cases, this may reduce the bends in the airflow path through the cyclone, which may reduce the pressure drop across the cyclone for better pneumatic efficiency. Optionally, the cyclone inlet is at the front or inlet end of the handvac and may be parallel to or co-axial with the handvac air inlet.

As exemplified in FIG. 96, handvac inlet 192 is shown positioned at a front end 220 of cyclone chamber 184, and outlet 196 is shown positioned at a rear end 224 of cyclone chamber 184. Inlet 192 may have an inlet axis 1140 that is parallel to the outlet axis 1168 of air outlet 196. In the illustrated embodiment, inlet axis 1140 is co-axial with outlet axis 1168.

Optionally, the suction motor axis may be parallel to or co-axial with axis 1140, 1168. Accordingly, air may travel in a generally uniform direction through the components of the handvac.

Handvac Cyclone Dirt Collection Chamber

In accordance with another aspect of this disclosure, which may be used by itself or in combination with any one or more other aspects of this disclosure, the dirt collection chamber of the handvac may have a dirt inlet which is located at the upper end of the dirt collection chamber when the hand vac is oriented for cleaning a floor (see e.g., FIGS. 81 and 103). In addition, the dirt collection chamber may be shaped to encourage dirt to collect at another end of the handvac away from the dirt outlet of the cyclone chamber (e.g., it may extend downwardly away from the dirt inlet). This may clear the dirt inlet to permit additional dirt to enter.

As exemplified in FIG. 96, dirt may enter dirt collection chamber 188 from cyclone chamber 184 through dirt outlet 200 of cyclone chamber 184. In the illustrated embodiment, dirt outlet 200 is at a rear end 224 of cyclone chamber 184. In use, handvac 112 may be normally oriented with the nozzle 412 at the front end oriented downwardly for cleaning a surface below. Accordingly, dirt entering dirt collection chamber 188 from dirt outlet 200 may fall by gravity toward front end 220 of dirt collection chamber 188 away from dirt outlet 200. This may help to keep dirt outlet 200 clear for subsequent dirt to move through dirt outlet 200 during use.

In the illustrated embodiment, handvac 112 may be supportable on a horizontal surface 876 by contact between dirt collection chamber 188 and the horizontal surface 876. For example, dirt collection chamber 188 may include a bottom wall 216 for supporting handvac 112 on horizontal surface 876. Preferably, as discussed previously, handvac 112 is inclined with nozzle 412 facing downwardly when handvac 112 is supported on horizontal surface 876 by bottom wall 216. In the illustrated embodiment, bottom wall 216 is angled downwardly between front end 220 and rear end 224 for orienting nozzle axis 884 downwardly to horizontal

when handvac **112** is supported on horizontal surface **876**. As shown, this may provide dirt collection chamber **188** with a wedge-like shape having a height **1172** measured between upper and lower dirt collection chamber walls **226** and **216** which increases from the front end **220** to the rear end **224**.

Pre-Motor Filter Housing

In accordance with another aspect of this disclosure, which may be used by itself or in combination with any one or more other aspects of this disclosure, a pre-motor filter housing may be provided in the airflow path between the cyclone bin assembly and the suction motor for directing the airflow through one or more pre-motor filters contained therein.

As exemplified in FIGS. **96** and **117**, handvac **112** has a pre-motor filter chamber **556** containing pre-motor filters **1176** and **1180**, and a suction motor housing **1138** containing suction motor **204**. The airflow path from inlet nozzle **412** to clean air outlet **132** may extend downstream from cyclone bin assembly **136** to pre-motor filter chamber **556** to suction motor housing **1138**. That is, cyclone bin assembly **136**, pre-motor filter chamber **556**, and suction motor housing **1138** may be positioned in the airflow path with pre-motor filter chamber **556** downstream of cyclone bin assembly **136** and suction motor housing **1138** downstream of pre-motor filter chamber **556**.

In the illustrated example, pre-motor filter chamber **556** extends in height **1184** between an upper end **1188** to a lower end **1192** in the direction of pre-motor filter axis **560**, and extends in depth **1216** between front wall **1220** and rear wall **1224**. In some embodiments, cyclone axis **248** and motor axis **252** may be parallel and vertically offset as shown. For example, each of cyclone axis **248** and motor axis **252** may intersect pre-motor filter chamber **556** as shown. In some embodiments, outlet axis **1168** of cyclone chamber outlet **196** and, motor inlet axis **1196** of motor inlet **1108** may be parallel and vertically offset. For example, each of outlet axis **1168** and motor inlet axis **1196** may intersect pre-motor filter chamber **556** as shown.

In some embodiments, cyclone chamber outlet **196** discharges air from cyclone chamber **184** into pre-motor filter chamber **556**, and pre-motor filter chamber **556** discharges air into motor inlet **1108**. For example, cyclone chamber outlet **196** may be positioned at the threshold between cyclone chamber **184** and pre-motor filter chamber **556**, and motor inlet **1108** may be positioned at the threshold between pre-motor filter chamber **556** and suction motor housing **1138**. In alternative embodiments, one or more conduits (not shown) may separate pre-motor filter chamber **556** from cyclone chamber outlet **196** and/or motor inlet **1108**.

In the illustrated embodiment, pre-motor filter chamber **556** extends in length between a front end **1200** and a rear end **1204**. As shown, pre-motor filter chamber **556** may hold pre-motor filters **1176** and **1180** in the airflow path between cyclone chamber outlet **196** and motor inlet **1108** for filtering residual dirt particles remaining in the airflow. In some embodiments, pre-motor filter chamber **556** may hold pre-motor filters **1176** and **1180** in spaced apart relation to front and rear ends **1200** and **1204**. An upstream plenum **1208** may be provided in the space between upstream pre-motor filter **1176** and front end **1200**. A downstream plenum **1212** may be provided in the space between downstream pre-motor filter **1176** and rear end **1204**. Air entering upstream plenum **1208** from cyclone bin assembly **136** may distribute across the surface area of pre-motor filter **1176** for traversing filters **1176** and **1180** to downstream plenum **1212**.

In the illustrated embodiment, cyclone chamber outlet **196** may direct air into an upper portion of upstream plenum **1208**. For example, cyclone chamber outlet **196** may be connected to pre-motor filter chamber **556** proximate upper end **1188**. In the illustrated embodiment, motor inlet **1108** may receive air from a lower portion of downstream plenum **1212**. For example, motor inlet **1108** may be connected to pre-motor filter chamber **556** proximate lower end **1192**. Accordingly, pre-motor filter chamber **556** may be used to redirect the air from transversely to the cyclone and motor axis without requiring conduits having bends therein.

Battery Power

In accordance with another aspect of this disclosure, which may be used by itself or in combination with any one or more other aspects of this disclosure, the surface cleaning head or upright section of the surface cleaning apparatus may include one or more batteries for powering the handvac when the handvac is connected to the surface cleaning head or upright section. The handvac may also include handvac batteries which may power the handvac when connected to or disconnected from the upright section and surface cleaning head (e.g., in an above-floor cleaning mode or handvac mode). When the handvac is electrically connected to the surface cleaning head, the batteries in the surface cleaning head may supplement the batteries in the handvac or be the sole power source.

As exemplified in FIG. **3**, surface cleaning apparatus **100** (or any other surface cleaning apparatus embodiment disclosed herein) may include one or more handvac batteries **1268** mounted to the handvac **112**, and one more supplemental batteries **1272**. Supplemental batteries **1272** may be mounted to any other suitable component of apparatus **100** other than handvac **112**. For example, supplemental batteries **1272** are shown mounted to surface cleaning head **104**. Alternatively or additionally, supplemental batteries **1272** may be mounted to upright section **108**.

As used herein, the plural term "batteries" means one or more batteries. For example, supplemental batteries **1272** may be one battery or a plurality of batteries. Similarly, handvac batteries **1268** may be one battery or a plurality of batteries. Batteries **1272** and **1268** may be any suitable form of battery such as NiCad, NiMH, or lithium batteries, for example. Preferably, batteries **1272** and **1268** are rechargeable, however, in alternative embodiments, one or both of batteries **1272** and **1268** may be non-rechargeable single-use batteries.

In the illustrated embodiment, when handvac **112** is connected to upright section **108**, an electrical connection may be formed between supplemental batteries **1272** and handvac **112**, e.g., for powering suction motor **204**.

In some embodiments, supplemental batteries **1272** may provide handvac **112** with enhanced power for generating greater suction with suction motor **204**. For example, suction motor **204** may operate in a high power consumption mode, drawing power from supplemental batteries **1272**, or supplemental batteries **1272** and handvac batteries **1268** simultaneously.

In some embodiments, supplemental batteries **1272** may provide the handvac **112** with extra energy for prolonged cleaning time between charges. For example, supplemental batteries **1272** may have a greater energy capacity (e.g., measured in Watt-hours) than handvac batteries **1268**, such that handvac **112** may be sustained by supplemental batteries **1272** for a longer operating time. In some embodiments, handvac **112** may draw power from both of supplemental

39

batteries 1272 and handvac batteries 1268, which have a greater combined energy storage capacity than handvac batteries 1268 alone.

In some embodiments, supplemental batteries 1272 may supply power to the handvac in preference to the handvac batteries 1268 to delay or avoid draining the handvac batteries 1268. For example, handvac 112 may draw power from supplemental batteries 1272 until substantially depleted before drawing power from handvac batteries 1268. This may conserve power in handvac batteries 1268 for use when handvac 112 is disconnected from supplemental batteries 1272 (e.g., in an above-floor cleaning mode, or handvac mode of apparatus 100). In some embodiments, handvac 112 may never draw power from handvac batteries 1268 when handvac 112 is electrically connected to supplemental batteries 1272.

In some embodiments, handvac 112 may draw power from supplemental batteries 1272 to recharge handvac batteries 1268. This may help to ensure that handvac batteries 1268 are not depleted when handvac 112 is disconnected from supplemental batteries 1272 (e.g., for use in an above-floor cleaning mode, or handvac mode of apparatus 100). In some cases, supplemental batteries 1272 may recharge handvac batteries 1268 only when apparatus 100 is not turned on.

In some embodiments, supplemental batteries 1272 may be recharged whenever the surface cleaning apparatus is connected to an external power outlet. In some cases, handvac batteries 1268 may be recharged when handvac 112 is electrically connected to an external power outlet (e.g., when surface cleaning head 104 or upright section 108 is connected to a power outlet by an electrical cord (not shown), and handvac 112 is connected to the surface cleaning head 104 or upright section 108).

In some embodiments, one or more of supplemental batteries 1272 and handvac batteries 1268 may be positioned in the airflow path. This may provide cooling for the batteries so positioned, which may help to prevent the batteries from overheating and may improve the performance of the batteries. In the illustrated example, handvac batteries 1268 are positioned in the airflow path inside motor housing 1138. For example, handvac batteries 1268 may be positioned inside motor housing 1138 between suction motor 204 and clean air outlet 132. The air passing over the handvac batteries 1268 may help to keep the batteries 1268 cool.

Supplemental batteries 1272 may be positioned in the airflow path to promote cooling of the batteries 1272. In the illustrated example, supplemental batteries 1272 are shown positioned inside surface cleaning head 104 in the airflow path between dirty air inlet 124 and downstream end 1240. The air passing over batteries 1272 may help to keep batteries 1272 cool.

In alternative embodiments, one or both of supplemental batteries 1272 and handvac batteries 1268 may be positioned outside of the airflow path (e.g., to be cooled passively). Handvac Wheels

In accordance with another aspect of this disclosure, which may be used by itself or in combination with any one or more other aspects of this disclosure, the handvac may be provided with one or more sets of wheels, and a handle which may articulate to facilitate different cleaning postures.

As exemplified in FIGS. 106-109, surface cleaning apparatus 1292 may include a surface cleaning head 104, an upright section 108 (which may receive any assembly 140, 160 discussed previously), and a handvac 112. An airflow path through apparatus 1292 may extend from dirty air inlet

40

124 in surface cleaning head 104, downstream through upright section 108 and then handvac 112 to clean air outlet 1304. Upright section 108 may include a wand 144 having an upstream end 360 drivingly connected to a pivot joint 116 of surface cleaning head 104, and a downstream end 364 connected to an inlet nozzle 412 of handvac 112.

Handvac 112 may include an air treatment member positioned in the airflow path between inlet nozzle 412 for separating dirt from the airflow. In the illustrated example, handvac 112 includes a cyclone bin assembly 136 including a cyclone chamber 184, and a dirt collection chamber 188. Optionally, a bottom wall 216 of dirt collection chamber 188 may be pivotally openable for emptying dirt collection chamber 188.

As exemplified, apparatus 1292 may be movable between an upright storage position (FIG. 106) in which handvac 112 is substantially vertically aligned above surface cleaning head 104 and wand 144 is substantially vertically oriented, and an in-use floor cleaning position (FIG. 108) in which surface cleaning head 104 is positioned behind surface cleaning head 104 and wand 144 extends at an angle to vertical.

In the illustrated example, apparatus 1292 may include a handle 1340. Handle 1340 may be connected to wand 144 by an arm assembly 1344. As shown, arm assembly 1344 may include a first arm 1348 joined to a second arm 1352 by an articulating joint 1356. First arm 1348 may be connected to wand 144 and joint 1356, and second arm 1352 may be connected to handle 1340. Alternately, joint 1356 may be used to connect second arm 1352 to wand 144.

As shown, first arm 1348 may be rigidly connected to wand 144, and extend transversely to wand 144. For example, first arm 1348 may extend perpendicularly to wand 144. Second arm 1352 may be rotatable about joint 1356 between at least two positions. In the first position (FIG. 108), second arm 1352 may extend at an angle to first arm 1348 substantially in parallel with wand 144. In the second position (FIG. 109), second arm 1352 may extend substantially parallel to first arm 1348. An actuator (e.g., a button) 1358 may be provided on handle 1340 for toggle joint 1356 between an unlocked position in which second arm 1352 can move with respect to first arm 1348, and a locked position in which the position of second arm 1352 is fixed with respect to first arm 1348. Optionally, joint 1356 may be locked in a number of alternate positions. Alternately, joint 1356 may not be locked in the second bent position shown in FIG. 109.

The first position (FIG. 108) may be suitable for cleaning open areas where vertical clearance is not an issue. The second position (FIG. 109) may be suitable for cleaning under furniture and the like, where wand 144 must be lowered to clear the furniture height. In the second position, the orientation of second arm 1352 may permit a user to grasp handle 1340 and lower wand 144 while conveniently standing upright.

In some embodiments, handvac 112 may include one or more front wheels 1364. Front wheel 1364 may be positioned to make rolling contact with a horizontal surface when wand 144 is lowered sufficiently. Thus, front wheel 1364 may assist with supporting the weight of handvac 112 and permit handvac 112 to roll across the horizontal surface. In the illustrated example, a front end 1360 of bottom wall 216 is provided with one or more front wheels 1364.

It will be appreciated that if rear end of assembly 140, 160 is tapered as discussed previously, then assembly 140, 160 is configured to permit the vacuum cleaner to extend further under furniture than if the assembly 140, 160 had the depth

41

(front to back when in an upright storage position) as the upper end of the assembly **140**, **160**.

Openable Handvac Cyclone Bin Assembly

In accordance with another aspect of this disclosure, which may be used by itself or in combination with any one or more other aspects of this disclosure, the cyclone bin assembly of the handvac may be opened to empty the cyclone chamber and/or the dirt collection chamber, to access the pre-motor filter or access a door to open the cyclone chamber and/or the dirt collection chamber by moving part or all of the cyclone bin assembly relative to a main body of the handvac which include the suction motor while the parts remain connected together. For example, the parts may be pivotally mounted to each other.

Referring to FIGS. **110a** and **110b**, front portion **1372** of the cyclone bin assembly **136** may be pivotally connected to rear portion **1376** of the cyclone bin assembly **136** for pivoting between the open position shown and a closed position. In the open position, cyclone bin assembly **136** may be accessible, e.g., for emptying or cleaning.

Front portion **1372** may be pivotally connected to rear portion **1376** in any suitable fashion. In the illustrated embodiment, front portion **1372** is pivotally connected to rear portion **1376** by a hinge **1380** for rotation about a hinge axis **1384** between the open and closed positions.

The openable portion (e.g., front portion **1372**) may be mounted to (e.g., rotationally mounted) or removable from the remaining portion (e.g., rear portion **1376**) at any suitable location. As illustrated in FIGS. **110a** and **110b**, the openable portion may be mounted to the remaining portion at the second end wall **224** of the cyclone chamber **184**. As illustrated in FIGS. **128** to **135**, the openable portion may be mounted to the remaining portion at a location, such as midway along an axial length of the cyclone bin assembly **160**. If the openable portion includes a portion of a sidewall separating the air treatment chamber (e.g., cyclone chamber **184**) from dirt collection chamber **188**, then opening an end of the cyclone assembly, including a portion of the sidewall (e.g., some or all of at least one wall extending parallel to a cyclone axis of rotation), rather than just a front door or wall may permit easier removal of debris (e.g., the material in the forward part of the dirt collection chamber can fall out when the end is a front end and is pivoted upwardly). Optionally, at least the portion of common interior wall **226** that divides cyclone chamber **184** from dirt collection chamber **188** that extends to dirt outlet **200** is moveable with the openable portion so as to open dirt outlet **200**.

In the illustrated embodiment of FIGS. **110a** and **110b**, front portion **1372** and rear portion **1376** separate at the interface between cyclone bin assembly **136** and pre-motor filter chamber **556**. For example, front portion **1372** may include cyclone bin assembly **136** except for second end wall **224**, and rear portion may include pre-motor filter chamber **556** and second end wall **224** of cyclone bin assembly **136**. Accordingly, in the open position, access may be provided to empty and clean dirt collection chamber **188** and cyclone chamber **184** of cyclone bin assembly **136**.

Referring to FIG. **116**, in some embodiments handvac **112** may include a handle assembly **300** including handle **484** and suction motor **204**. As exemplified, handle assembly **300** and rear wall **1224** of pre-motor filter chamber **556** may be removable from (entirely, or pivotally connected to) pre-motor filter chamber **556** as a unit to access the pre-motor filters **1176** and **1180** inside pre-motor filter chamber **556**, e.g., for cleaning or replacement. As shown in FIG. **117**, in some embodiments, handle assembly **300** may also be

42

removably connected to rear wall **1224**. In alternative embodiments, handle assembly **300** may be permanently connected to rear wall **1224**.

Openable Dirt Collection Chamber

In accordance with another aspect of this disclosure, which may be used by itself or in combination with any one or more other aspects of this disclosure, the supplemental assembly may have a top and/or bottom openable portion.

As exemplified in FIGS. **111-113**, dirt collection assembly **140** is shown including an upper portion **276** in an open position. Upper portion **276** may be moveably connected to (e.g., pivotally) or removable from dirt collection assembly **140** in any suitable manner. As exemplified, upper portion **276** may be connected to dirt collection chamber **140** by a hinge **1392** for rotation about a hinge axis **1** (not shown) between the open and closed positions.

Upper portion **276** may be retained in the closed position in any suitable fashion. In the illustrated example, dirt collection chamber **140** includes a latch **1400** for securing upper portion **276** in the closed position. Latch **1400** may be user operable for selectively releasing upper portion **276** for movement to the open position.

As exemplified in FIGS. **114** and **115**, upright section **108** of surface cleaning apparatus **152** is shown including a cyclone bin assembly **160**. Cyclone bin assembly **160** is preferably openable for accessing cyclone chamber **308** and dirt collection chamber **141**, e.g., for cleaning or emptying. Preferably, an upper and/or lower portion of cyclone bin assembly **160** may be openable. In the illustrated embodiment, upright section **108** includes an upper portion **1408** and a lower portion **1412**. As shown, upper portion **1408** may be moveably connected to (e.g., pivotally connected to) or removable from lower portion **1412** for movement between a closed position (FIG. **114**) and an open position (FIG. **115**).

Upper portion **1408** may be pivotally connected to lower portion **1412** in any suitable manner. In the illustrated embodiment, lower portion **1412** is pivotally connected to lower portion **1412** by a hinge **1416** for rotation about a hinge axis **1420** between the closed and open positions.

Upper portion **1408** may be retained in the closed position in any suitable manner. For example, upper portion **108** may include a releasable catch for selectively securing upper portion **1408** to lower portion **1412** in the closed position. Openable Dirt Outlet and/or Connecting the Cyclone and Dirt Collection Chamber Volumes

In accordance with another aspect of this disclosure, which may be used by itself or in combination with any one or more other aspects of this disclosure, the dirt outlet from the cyclone chamber may be openable. For example, the dirt collection chamber may be an opening in a wall, e.g., a wall separating an air treatment chamber and a dirt collection chamber. The opening has an outer perimeter defined by the wall in which the dirt outlet is provided or the walls which abut the dirt outlet. During use, dirt may get trapped in the dirt outlet or bridge the dirt outlet. During an emptying operation, a wall or walls defining a first part of the perimeter of the dirt outlet may be moved relative to a wall or walls defining a second part of the dirt outlet thereby opening the dirt outlet.

The dirt outlet may be provided in a common wall dividing cyclone chamber **184** from dirt collection chamber **188**. During an emptying operation, part of the common wall **226** may be moved. As a result, the portion of the cyclone chamber and the portion of the dirt collection chamber that are separated by the common wall **226** become a contiguous volume defined by the volume of the portion of the cyclone chamber and the volume of the portion of the dirt collection

43

chamber that are separated by the common wall. If the part of the common wall **226** that is moved comprises part of the perimeter of the dirt outlet, then the dirt outlet is also opened when the openable portion of the cyclone bin assembly is opened.

It will be appreciated that the openable portion may comprise a part of (e.g., a front part or wall of) the cyclone chamber, and/or an end or portion of the surface cleaning apparatus or air treatment assembly and/or dirt collection chamber. Accordingly, the dirt outlet may be openable and/or part of the common wall **226** may be moveable when the cyclone chamber and/or an end or portion of the surface cleaning apparatus or air treatment assembly and/or dirt collection chamber is opened. For example, the sidewall **226** may be moved as part of opening the cyclone chamber and/or an end or portion of the surface cleaning apparatus or air treatment assembly and/or dirt collection chamber (e.g., to clean or empty debris from the cyclone chamber or another part of the surface cleaning apparatus).

Opening the dirt outlet may allow any debris (e.g., elongated debris such as hair) that is caught in the outlet (e.g., bridging the outlet) to come free or be more easily freed. Opening the dirt outlet when opening the cyclone chamber, opening an end or portion of the surface cleaning apparatus or air treatment assembly, and/or opening the dirt collection chamber may allow a user to more easily remove debris from the device.

As exemplified in FIGS. **128** to **135**, the handvac **114** may include a front end **1402**, a rear end **1404**, a top end **1406**, a bottom end **1410**, a right lateral side **1414**, and a left lateral side **1418**.

The dirt outlet **200** may be opened when a portion or end, (e.g., front end **1402**, a rear end **1404**) of the surface cleaning apparatus (e.g., handvac **112**) is opened. In the illustrated example, the dirt outlet **200** is opened when a front end **1372** of the cyclone bin assembly **136** is opened, although it will be understood that in other examples another end or portion of a surface cleaning apparatus may be opened (e.g., a rear portion). As in the illustrated example, the first end or portion of the handvac **112** may be a first end or portion of the cyclone assembly **136** (e.g., a front end and/or an end comprising an inlet conduit and/or dirty air inlet).

The dirt outlet **200** may be between the openable first end or portion **1372** and the remaining end or portion **1376** of the surface cleaning apparatus. Opening the first end or portion **1372** (e.g., removing the first end or rotating the first end) may open the dirt outlet by moving a wall or a portion of a wall defining an edge or part of the perimeter of the dirt outlet **200** (e.g., a wall in which the dirt outlet **200** is formed or a wall that extends up to an edge of the dirt outlet **200**).

The dirt outlet **200** may be at any position in the walls of the cyclone chamber **184**. As exemplified, the dirt outlet **200** may be provided in a common wall that divides the cyclone chamber **184** from the dirt collection chamber **188**. As in the illustrated example, at least a portion of the dirt collection chamber **188** may be spaced from the cyclone chamber **184** in a direction transverse to the cyclone axis of rotation **1371**. The at least a portion of the dirt collection chamber **188** may face towards the cyclone chamber **184** and be separated from the cyclone chamber by a sidewall **226**. As exemplified, the dirt outlet **200** may be in the sidewall **226**.

The dirt outlet **200** may be at one end of the chamber **184** (e.g., at or adjacent an end wall) and/or adjacent the air inlet and/or air outlet of the chamber **184** (e.g., separated from the air inlet and/or air outlet by less than half the length of the chamber or less than a quarter of the length of the chamber). In the illustrated example, the dirt outlet **200** comprises an

44

opening in the sidewall **226** that extends axially inwardly into the cyclone chamber **184** from the cyclone chamber second end wall **224**.

At least a portion of the sidewall **226** is included in the openable first (e.g., front) end **1372**, and moving the first end **1372** (e.g., including at least a portion of the cyclone chamber **184** and/or at least a portion of the dirt collection chamber **188**) from a closed or cleaning position as exemplified in FIGS. **128**, **129**, **132**, **133** and **136** to the open or emptying position of FIGS. **130**, **131**, **134**, **135** and **137** moves the portion of the sidewall **226** to open the dirt outlet **200**, as exemplified in FIGS. **128** to **135**. As exemplified in FIGS. **96**, **110a**, and **110b**, in some examples, the entire sidewall **226** of the cyclone and dirt collection chambers may be part of the front end **1372** and/or the hinge **1380** may be at or adjacent an end (e.g., the rearward end) of the cyclone chamber **184** and/or the dirt collection chamber **188** (e.g., if the dirt collection chamber **188** and cyclone chamber **184** are not coextensive along the cyclone axis of rotation). Alternately, as exemplified in FIGS. **130**, **131**, **134**, **135** and **137**, only a portion of the sidewall of the cyclone and/or dirt collection chambers may be opened. Alternately, it will be appreciated that the common wall **226** may be moveable with a front wall of the cyclone chamber (see for example FIG. **137**). In such an embodiment, it will be appreciated that the front end or front wall of the dirt collection chamber may not be opened. Similarly, it will be appreciated that the common wall **226** may be moveable with a front wall of the dirt collection chamber. In which case it will be appreciated that the front end or front wall of the cyclone chamber may not be opened.

Extended Dirt Collection Chamber

In accordance with another aspect of this disclosure, which may be used by itself or in combination with any one or more other aspects of this disclosure, all or a portion of the dirt collection chamber may be positioned forward and/or rearward of the cyclone chamber. The dirt collection chamber may include at least a portion that is spaced from the cyclone chamber in a direction transverse to the cyclone axis of rotation and another portion that is forward and/or rearward of the cyclone chamber, e.g., that is intersected by the cyclone axis of rotation or through which a projection of the cyclone chamber extends.

Extending the dirt collection chamber to include a portion that is forward or rearward of the cyclone chamber may provide an additional volume in which to collect debris and/or allow the diameter of the dirt collection chamber, in a direction transverse to the cyclone axis of rotation, to be reduced. Accordingly, the volume of the dirt collection chamber may be increased without increasing the height of the surface cleaning apparatus in a direction transverse the cyclone axis of rotation. For example, if the cyclone chamber is a horizontally extending cyclone chamber, then extending the dirt collection chamber to include a portion that is forward or rearward of the cyclone chamber may allow a larger dirt collection volume without increasing the height of the handvac and/or allow for a similar sized dirt collection chamber while decreasing the height of the collection chamber and cyclone chamber.

As exemplified in FIGS. **136** and **137**, the dirt collection chamber **188** includes a first portion that is below the cyclone chamber and a second portion **1422** that is forward of the cyclone chamber **188**. The first and second portions **1420**, **1422** may be contiguous, in which case the dirt outlet may communicate with either the first portion **1420** or the second portion **1422**. As exemplified, the lower end of the second portion **1422** communicates with a front end of the

first portion 1420. Alternately, the first and second portions need not be contiguous, in which case a first dirt outlet may connect the cyclone chamber in air flow communication with first portion 1420 and a second dirt outlet may connect the cyclone chamber in air flow communication with second portion 1422.

In the exemplified embodiment, second portion 1422 is located between a first (e.g., front) end 1390 having a first (e.g., front) end wall 1394, which is spaced axially forward of the cyclone chamber first end 220, and cyclone chamber first end 220. As exemplified, the lower end of second portion 1422 may be radially spaced from the cyclone axis of rotation by at least the same distance as the lower end of first portion 1420 is radially spaced from the cyclone axis or rotation. Accordingly, as exemplified in FIG. 136, the lower end of first portion 1420 may have a height H_1 that extends between the lower end of first portion 1420 and the cyclone axis of rotation that is the same as height H_2 that extends between the lower end of second portion 1422 and the cyclone axis of rotation. Alternately, H_1 may be greater or less than H_2 .

Second portion 1420 has an axially spaced apart second (e.g., rear) end 1396 having a second (e.g., rear) end wall 1398. Accordingly, as exemplified, second portion 1420 may extend to the rear end of the cyclone chamber and may communicate with a dirt outlet 200 provided at the rear end of common wall 226. Accordingly, as exemplified in FIG. 137, when the front end is opened, the cyclone and the dirt chamber are concurrently opened and the dirt outlet is also opened.

It will be appreciated that, as in FIGS. 128-135, part or a majority of the sidewalls of the cyclone chamber and/or part or a majority of the sidewalls of the dirt collection chamber (in addition to common wall 226) may be moved when the front end is opened.

It will be appreciated that the height H_3 of second portion in a direction transverse to the cyclone axis of rotation may be the same as the height of the rest of the cyclone bin assembly. The height H_3 may be such that the cyclone axis of rotation 1371 extends through first portion 1422. In an alternate embodiment, the cyclone axis of rotation 1371 may not extend through first portion 1422 but a projection of a portion of the cyclone chamber may extend through second portion 1422. In a further alternate embodiment, the height H_3 may be such that a projection of all of the cyclone chamber may extend through second portion 1422.

Handvac Cyclone Bin Assembly Bypass

In accordance with another aspect of this disclosure, which may be used by itself or in combination with any one or more other aspects of this disclosure, the cyclonic air treatment member of the handvac may be bypassed when a supplemental cyclonic bin assembly is provided. This may prevent accumulation of dirt in the handvac so that the handvac may have more or all of its dirt collection capacity available when disconnected from the upright section. Alternately or in addition, a pre-motor filter of handvac 112 may be bypassed when a supplemental cyclonic bin assembly is provided. For example, the supplemental cyclonic bin assembly may be provided with a pre-motor filter. The pre-motor filter may have a larger surface area than the pre-motor filter of handvac 112. Accordingly, by bypassing the pre-motor filter of handvac 112, the pre-motor filter of handvac 112 may only be used in an above floor cleaning mode thereby extending the useable time of the pre-motor filter of handvac 112 before cleaning or replacement may be needed.

Referring to FIGS. 99-101, handvac 112 may include a primary airflow path 1228 and a bypass airflow path 1232. As shown, primary airflow path 1228 may extend from air inlet 192 through cyclone bin assembly 136 to suction motor 204, and bypass airflow path 1232 may extend from air inlet 192 to suction motor 204 bypassing cyclone bin assembly 136. In some embodiments, bypass airflow path 1232 may extend through the pre-motor filters of pre-motor filter chamber 556, and in other embodiments, bypass airflow path 1232 may bypass pre-motor filters of pre-motor filter chamber 556. It will be appreciated that the cyclone and/or the pre-motor filter of the handvac may be bypassed. If both are bypassed, then the handvac may be used to provide some or all of the motive force to draw air through apparatus 168 but not any air treatment upstream of the suction motor.

In the illustrated embodiment, bypass airflow path 1232 is formed in part by a bypass passage 1236. Bypass passage 1236 may have an upstream end 1238 in airflow communication with handvac inlet 416, and a downstream end 1240 in airflow communication with motor inlet 1108. As exemplified by the embodiment illustrated in FIG. 101, upstream end 1238 may be formed in a sidewall of handvac nozzle 412, and downstream end 1239 may be formed in a wall of premotor filter chamber 556. In some embodiments, downstream end 1239 may direct air from bypass passage 1236 into upstream plenum 1208 for routing bypass airflow path 1228 through pre-motor filters 1176 and 1180 as shown. In alternative embodiments, downstream end 1239 may direct air from bypass passage 1236 into downstream plenum 1212 for bypassing pre-motor filters 1176 and 1180.

As exemplified, apparatus 168 may include a bypass valve 1240 for selectively opening and closing primary and bypass airflow paths 1228 and 1232. Bypass valve 1240 may be positioned in any one or more of handvac 112, wand 144, and supplemental cyclone bin assembly 160, and may take any suitable form. For example, in some embodiments bypass valve 1240 may include components parts positioned in two or more of handvac 112, wand 144, and supplemental cyclone bin assembly 108 which cooperate and interact to open and close primary and bypass airflow paths 1228 and 1232.

In the illustrated embodiment bypass valve 1240 is positioned in inlet nozzle 412 of handvac 112. Bypass valve 1240 may be movable between a first position (FIGS. 99 and 100) in which bypass airflow path 1232 is closed and primary airflow path 1228 is open, and a second position (FIG. 101) in which bypass airflow path 1232 is open and primary airflow path 1228 is closed.

As exemplified in FIGS. 99-101, bypass valve 1240 may include a wheel 1242, a door 1244, and an actuator 1246. Wheel 1242 may be rotatably connected to nozzle 412 for rotation about its center. Door 1244 may be rigidly connected to wheel 1242 for rotation as one with wheel 1242. For example, door 1244 and wheel 1242 may rotate together as a unit. As shown, door 1244 and wheel 1242 may be rotatable between a first position (FIGS. 99 and 100) in which door 1244 seals an upstream end 1238 of bypass passage 1236, and a second position (FIG. 101) in which door 1244 seals an air inlet 192 of cyclone chamber 184.

As exemplified, actuator 1246 may include an upper end 1248 connected to wheel 1242 radially outboard of the center of wheel 1242. Actuator 1246 may be movable vertically between a lowered position (FIGS. 99 and 100), and a raised position (FIG. 101). As shown, moving actuator 1246 from the lowered position to the raised position may rotate wheel 1242 and door 1244 clockwise which may move door 1244 to the second position (FIG. 101) in which

47

door 1244 seals air inlet 192 of cyclone chamber 184. Further, moving actuator 1246 from the raised position to the lowered position may rotate wheel 1242 and door 1244 counter clockwise which may move door 1244 to the first position (FIGS. 99 and 100) in which door 1244 seals upstream end 1238 of bypass passage 1236.

In some embodiments, actuator 1246 may be biased to the lowered position (FIGS. 99 and 100). Consequently, door 1244 and wheel 1242 may be biased to the first position (FIGS. 99 and 100) in which door 1244 seals an upstream end 1238 of bypass passage 1236. Actuator 1246 may be biased in any suitable fashion, such as by a linear coil spring 1250. In alternative embodiments, wheel 1242 may be biased clockwise in a suitable manner, such as by a torsional spring.

Actuator 1246 may have a lower end 1252 which extends outside of the airflow path. Lower end 1252 may be acted upon to move actuator 1246 vertically from the lowered position to the raised position for opening bypass airflow path 1232 and closing primary airflow path 1228. As shown, when handvac 112 is disconnected from wand 144 (FIG. 99), bypass valve 1240 may close the bypass airflow path 1232 (e.g., under the bias of spring 1250). Further, when handvac 112 is connected to wand 144 without supplemental cyclone bin assembly 160 (FIG. 100), bypass valve 120 may also close the bypass airflow path 1232. In each of these cases, the air entering handvac 112 is directed through handvac cyclone bin assembly 136 to separate dirt from the airflow. This may permit handvac 112 to operate when disconnected from supplemental cyclone bin assembly 160.

As shown in FIG. 101, when handvac 112 and cyclone bin assembly 160 are both connected to wand 144, an upper end 1254 of cyclone bin assembly 160 (handle 1254 in the illustrated example) may push against actuator lower end 1252 thereby moving actuator 1246 upwardly. This may rotate wheel 1242 and door 1244 counter clockwise, opening bypass airflow path 1232 and closing primary airflow path 1228. As shown, air exiting cyclone bin assembly 160 may travel through bypass airflow path 1232 toward suction motor 204 bypassing cyclone chamber 184. This may permit supplemental cyclone bin assembly 160 to separate and collect dirt from the airflow path instead of handvac cyclone bin assembly 136. In turn, this may inhibit dirt accumulation in handvac dirt collection chamber 188, which may help to maximize the available dirt collection capacity of handvac dirt collection chamber 188 when the user chooses to disconnect cyclone bin assembly 160.

In the illustrated example, lower end 1252 is sloped. This may permit supplemental bin assembly 160 to be toed into wand 144 and then rotated horizontally towards wand 144 to complete the connection with wand 144, whereby the upper end 1254 of supplemental bin assembly 160 may ride the slope of lower end 1252 to push actuator 1246 upwardly.

Accordingly, bypass valve 1240 may be actuated to reconfigure the airflow path through handvac 112 automatically upon connecting and disconnecting supplemental bin assembly 160 from airflow communication with handvac 112. For example, bypass valve 1240 may be biased to close bypass airflow path 1232 whenever handvac 112 is not in airflow communication with supplemental bin assembly 160 so that the air treatment member of handvac 112 may separate dirt from the airflow. Similarly, bypass valve 1240 may be configured to open bypass airflow path 1232 and close primary airflow path 1228 whenever handvac 112 is in airflow communication with supplemental bin assembly 160 so that the air treatment member of handvac 112 does not separate and store dirt from the airflow.

48

The following is a description of numerous embodiments of surface cleaning apparatus 168. In the figures associated with some embodiments, a bypass valve 1232 and/or a diversion valve 712 may be represented schematically. It will be appreciated that the embodiments may be practiced using the bypass valves 1232 and/or diversion valves 712 described above, or other suitable valves.

Referring to FIG. 102, in some embodiments supplemental cyclone bin assembly 160 may include one or more pre-motor filters 1256 (herein after referred to as pre-motor filter 1256 in the singular) positioned in the airflow path. Preferably, pre-motor filter 1256 is positioned downstream of cyclone chamber 308. As shown, pre-motor filter 1256 may be positioned between cyclone chamber air outlet 320 and outlet passage 476.

In some embodiments, pre-motor filter 1256 may separate fine dirt particles from the airflow in substitution for the pre-motor filters 1176 and 1180 of handvac 112. As shown, bypass valve 1232 may divert air from supplemental cyclone bin assembly 160 into a bypass airflow path which bypasses handvac cyclone bin assembly 136 and pre-motor filters 1176 and 1180. For example, downstream end of 1239 of bypass passage 1236 may direct the bypass airflow path 1232 to downstream plenum 1212 for bypassing pre-motor filters 1176 and 1180.

It will be appreciated that a pre-motor filter will have a certain filtering capacity of fine particles at which point the filter should be cleaned or replaced. By incorporating a pre-motor filter into the supplemental cyclone bin assembly 160, and using this filter whenever the supplemental cyclone bin assembly 160 is connected to the handvac, the filtering capacity of the handvac pre-motor filters may be preserved. This may permit extended use of the handvac pre-motor filters before they require cleaning or replacement.

It will also be appreciated that there will be a measurable pressure drop across a pre-motor filter placed in an airflow path. If positioned in series, too many filters may produce a pressure drop that materially reduces air flow at the dirty air inlet. By filtering the airflow alternately by the supplemental pre-motor filter 1256 and by the handvac pre-motor filter when the handvac is used without assembly 140, 160 attached the operational life of the handvac pre-motor filter may be extended.

As exemplified in the alternate embodiment of FIG. 103, surface cleaning head 104 may include a second suction motor 1258. Second suction motor 1258 may operate in parallel with or alternately instead of handvac suction motor 204 when handvac 112 is attached in flow communication with surface cleaning head 104. For example, a portion of air exiting supplemental cyclone bin assembly 160 may proceed to handvac suction motor 204 and a different portion may proceed to second suction motor 1258. In the illustrated embodiment, a second airflow path 1260 from diversion valve 712 to second suction motor 1258 is formed by an airflow conduit 1262 which connects diversion valve 712 to surface cleaning head 104.

As shown, when supplemental cyclone bin assembly 160 is in airflow communication with handvac 112, the airflow path extends through the air treatment member(s) of supplemental cyclone bin assembly 160 (e.g., cyclone chamber 308 and pre-motor filter 1256) and then divides into two parallel air flow paths 1232 and 1260. Bypass airflow path 1232 directs one portion of the airflow to the handvac suction motor 204 bypassing handvac cyclone chamber 184 (and optionally bypassing handvac pre-motor filters 1176

and 1180), and second airflow path 1260 directs a second portion of the airflow path to the second suction motor 1258 in head 104.

It will be appreciated that suction motors 1258 and 204 operating in parallel may generate greater suction at surface cleaning head 104 than any one of suction motors 1258 and 204 may generate operating alone. This may also permit supplemental cyclone bin 160 to include a pre-motor filter 1256 having greater surface area than the pre-motor filter of the handvac, where the additional pressure drop due to the use of two pre-motor filters may be compensated for by the enhanced suction generation of the parallel motors 1258 and 204.

As exemplified in the alternate embodiment of FIG. 104a, supplemental suction motor 160 may include a second suction motor 1258 which may operate in the same way as the embodiment of FIG. 103. Second suction motor 1258 may operate in parallel with handvac suction motor 204. For example, a portion of air exiting supplemental cyclone chamber 160 may proceed to handvac suction motor 204 and a different portion may proceed to second suction motor 1258. In the illustrated embodiment, a second airflow path 1260 from outlet passage 478 to second suction motor 1258 is formed by an airflow conduit 1262.

As shown, when supplemental cyclone bin assembly 160 is in airflow communication with handvac 112, the airflow path extends through the air treatment member(s) of supplemental cyclone bin assembly 160 (e.g., cyclone chamber 308 and pre-motor filter 1256) and then divides into two parallel air flow paths 1232 and 1260. Bypass airflow path 1232 directs one portion of the airflow to the handvac suction motor 204 bypassing handvac cyclone chamber 184 (and optionally bypassing handvac pre-motor filters 1176 and 1180), and second airflow path 1260 directs a second portion of the airflow path to the second suction motor 1258.

As shown, second suction motor 1258 may be positioned below dirt collection chamber 140 and cyclone chamber 308 of supplemental cyclone bin assembly 160, and second suction motor 1258 may be vertically aligned above surface cleaning head 104. This may help to lower the center of gravity of the apparatus 168 for enhanced stability against tipping.

In some embodiments, a pre-motor filter may be positioned in each of bypass airflow path 1232 and second airflow path 1260, as shown. For example, a pre-motor filter 1256 may be positioned in the second airflow path 1260 between outlet passage 478 and second suction motor 1258, and bypass airflow path 1232 may direct the airflow through handvac pre-motor filters 1176 and 1180. In the illustrated embodiment, pre-motor filter 1256 is shown positioned below dirt collection chamber 140 of supplemental cyclone bin assembly 160.

In alternative embodiments, air exiting cyclone chamber 308 may pass through a common pre-motor filter before dividing between the second airflow path 1260 and bypass airflow path 1232. For example, in FIG. 104b pre-motor filter 1256 is shown positioned downstream of cyclone chamber 308 and upstream of outlet passage 478. As shown, bypass airflow path 1232 may bypass handvac pre-motor filters 1176 and 1180. This may permit the filtration capacity of handvac pre-motor filters 1176 and 1180 to be preserved for use when supplemental cyclone bin assembly 160 is disconnected from airflow communication with handvac 112. In alternative embodiments, pre-motor filters 1176 and 1180 may be positioned in the bypass airflow path 1232.

As exemplified in FIG. 105a dirt collection chamber 140 and cyclone chamber 308 may be removable as a sealed unit

from wand 144 and second suction motor 1258. For example, second suction motor 1258 may be mounted or removably mounted to wand 144 so that dirt collection chamber 140 and cyclone chamber 308 may be removed while second suction motor 1258 remains mounted to wand 144. This may permit cleaning and/or emptying of dirt collection chamber 140 and cyclone chamber 308 (e.g., carrying the same to a garbage bin to dump their contents) without having to carry second suction motor 1258 (which may have a non-trivial weight). Also, assembly 160 may be removable as a unit to convert the apparatus to a lightweight or above floor operating mode.

As exemplified in FIG. 118, the air treatment members of handvac 112 and supplementary cyclone bin assembly 160 may operate in parallel. For example, handvac 112 and supplementary cyclone bin assembly 160 may separate dirt from mutually exclusive portions of the airflow entering dirty air inlet 124.

In the illustrated example, wand 144 may define two airflow paths. A first airflow path 1428 may be formed by a first division of wand 144 and may direct airflow moving therein to supplemental cyclone bin assembly 160 for cleaning, and then from supplemental cyclone bin assembly 160 to bypass airflow path 1232 of handvac 112. A second airflow path 1432 may be formed by a second division of wand 144 and may direct airflow moving therein to primary airflow path 1228 of handvac 112 for cleaning by cyclone bin assembly 136.

As exemplified, dirty air entering dirty air inlet 124 may divide into two airflows at wand upstream end 360 and then travel through the first and second airflow paths 1428 and 1432. Dirt may be separated from each airflow stream by a different one of supplementary cyclone bin assembly 160 and handvac 112. In the illustrated embodiment, the two airflows may recombine in pre-motor filter chamber 556. For example, the two airflows may recombine at the upstream plenum 1208 so that both airflows pass through pre-motor filters 1176 and 1180 before exiting through suction motor 204. In alternative embodiments, the two airflows may recombine at the downstream plenum 1212. For example, supplemental cyclone bin assembly 160 may have its own pre-motor filter for filtering the air of the first airflow path 1428.

In some embodiments, surface cleaning apparatus 168 may include two or more suction motors operating in series. In one aspect, this may enhance the suction at dirty air inlet 124 and/or compensate for suction loss from additional or higher efficiency air treatment members.

Referring to FIGS. 119a and 119b, a second suction motor 1258 may be positioned in the airflow path between dirty air inlet 124 and handvac 112. For example, second suction motor 1258 may be a dirty air suction motor positioned in surface cleaning head 104. As shown, dirty air entering dirty air inlet 124 may be drawn through second suction motor 1258 before the airflow is cleaned by supplemental dirt collection chamber 160 and/or handvac 112 and discharged through handvac suction motor 204.

Referring to FIG. 120, second suction motor 1258 may be a clean air motor positioned downstream of handvac suction motor 204. As exemplified, motor outlet 1112 of handvac suction motor 204 may be fluidly connected to second suction motor 1258 in surface cleaning head 104 by an airflow path 1436. As shown, airflow path 1436 may be formed by a conduit 1440.

Referring to FIG. 121a, in some embodiments second suction motor 1258 may be positioned in supplementary cyclone bin assembly 160. For example, second suction

51

motor **1258** may be positioned below dirt collection chamber **140**. As shown, airflow path **1436** from motor outlet **1112** may direct air from suction motor **204** to second suction motor **1258** in supplementary cyclone bin assembly **160**. For example, conduit **1440** may extend from motor outlet **1112** to second suction motor **1258**. Conduit **1440** may take any suitable form. For example, conduit **1440** may be a rigid conduit as shown. Alternatively, FIG. **121b** shows an embodiment where conduit **1440** is a flexible hose.

In some embodiments, when handvac is connected with supplement cyclone bin assembly **160**, handvac **112** may not be positioned in the airflow path through the surface cleaning apparatus. For example, air entering the dirty air inlet **124** of the surface cleaning head may be cleaned by the supplementary cyclone bin assembly **160** and discharged without ever passing through handvac **112**. In this way, handvac **112** may act as a handgrip for manipulating and steering surface cleaning apparatus **168** in the upright mode but not as an air cleaning implement.

In some embodiment, as exemplified in FIG. **122**, the handvac may be bypassed when assembly **160** is attached to upright section **108**. As exemplified, air entering dirt air inlet **124** may move through wand **144** to supplemental cyclone bin assembly **160** and be discharged without moving through handvac **112**. For example, the airflow path through surface cleaning apparatus **168** may direct all air from dirty air inlet **124** through wand **144** to cyclone chamber **308** to outlet passage **476** to second airflow path **1260** to suction motor **1258** of supplemental cyclone bin assembly **160**, which may discharge the air to the outside environment.

Still referring to FIG. **122**, in some embodiments there may be a plurality of suction motors in series. In the illustrated embodiment, surface cleaning head **104** includes a suction motor **1258** positioned in the airflow path between dirty air inlet **124** and wand **144**. In alternative embodiments, suction motor **1258** may be the only suction motor in the airflow path.

While the above description provides examples of the embodiments, it will be appreciated that some features and/or functions of the described embodiments are susceptible to modification without departing from the spirit and principles of operation of the described embodiments. Accordingly, what has been described above has been intended to be illustrative of the invention and non-limiting and it will be understood by persons skilled in the art that other variants and modifications may be made without departing from the scope of the invention as defined in the claims appended hereto. The scope of the claims should not be limited by the preferred embodiments and examples, but should be given the broadest interpretation consistent with the description as a whole.

The invention claimed is:

1. A surface cleaning apparatus comprising:

- (a) a hand vacuum cleaner having a front end having a dirty air inlet, a rear end, a clean air outlet, an upper end, a lower end and a pistol grip handle, the hand vacuum cleaner comprising:
 - (i) a main body comprising an upper end, a lower end, a front end and a rear end, the main body housing a suction motor and fan assembly, the suction motor and fan assembly having a suction motor axis of rotation;
 - (ii) a cyclone unit comprising a cyclone chamber having a cyclone axis of rotation, a front end, an axially spaced apart rear end, a cyclone air inlet, and a cyclone air outlet provided at the rear end of the

52

cyclone unit, wherein the cyclone axis of rotation intersects the pistol grip handle; and

- (iii) a dirt collection chamber that is exterior to the cyclone chamber and a forward end of the dirt collection chamber is openable;

- (b) a surface cleaning head having a front end, a rear end, a dirty air inlet and a surface cleaning head air outlet; and,

- (c) a rigid air flow conduit that is removably mountable to the surface cleaning head and, when attached to the hand vacuum cleaner and the surface cleaning head, extends between the surface cleaning head air outlet and the dirty air inlet of the hand vacuum cleaner,

wherein the dirty air inlet of the hand vacuum cleaner is removably drivingly mounted to a downstream end of the rigid air flow conduit whereby when the hand vacuum cleaner is mounted to the downstream end of the rigid air flow conduit, the pistol grip handle is a driving handle for the surface cleaning apparatus, and wherein when the hand vacuum cleaner is positioned with the front end of the hand vacuum cleaner in front of the rear end of the hand vacuum cleaner, the cyclone axis of rotation is generally horizontal.

2. The surface cleaning apparatus of claim 1 wherein the cyclone unit is removably mounted to the main body.

3. The surface cleaning apparatus of claim 1 wherein the cyclone axis of rotation is generally parallel to the suction motor axis of rotation.

4. The surface cleaning apparatus of claim 1 wherein, when the hand vacuum cleaner is positioned with the front end of the hand vacuum cleaner in front of the rear end of the hand vacuum cleaner, the pistol grip handle extends upwardly and forwardly.

5. The surface cleaning apparatus of claim 1 wherein an enclosed finger grip area is provided on a forward side of the pistol grip handle.

6. The surface cleaning apparatus of claim 1 wherein the cyclone axis of rotation intersects the finger grip area.

7. The surface cleaning apparatus of claim 2 further comprising a pre-motor filter, wherein the pre-motor filter is accessible when the cyclone unit is removed from the main body.

8. A surface cleaning apparatus comprising:

- (a) a hand vacuum cleaner having a front end having a dirty air inlet, a rear end, a clean air outlet, an upper end, a lower end and a pistol grip handle, the hand vacuum cleaner comprising:

- (i) a main body comprising an upper end, a lower end, a front end and a rear end, the main body housing a suction motor and fan assembly, the suction motor and fan assembly having a suction motor axis of rotation; and,

- (ii) a cyclone unit comprising a cyclone chamber having a cyclone axis of rotation, a front end, an axially spaced apart rear end, a cyclone air inlet, and a cyclone air outlet provided at the rear end of the cyclone unit, wherein the cyclone axis of rotation intersects the pistol grip handle;

- (b) a surface cleaning head having a front end, a rear end, a dirty air inlet and a surface cleaning head air outlet; and,

- (c) a rigid air flow conduit that is removably mountable to the surface cleaning head and, when attached to the hand vacuum cleaner and the surface cleaning head, extends between the surface cleaning head air outlet and the dirty air inlet of the hand vacuum cleaner,

53

wherein the dirty air inlet of the hand vacuum cleaner is removably drivingly mounted to a downstream end of the rigid air flow conduit whereby when the hand vacuum cleaner is mounted to the downstream end of the rigid air flow conduit, the pistol grip handle is a driving handle for the surface cleaning apparatus, and wherein when the hand vacuum cleaner is positioned with the front end of the hand vacuum cleaner in front of the rear end of the hand vacuum cleaner, the cyclone axis of rotation is generally horizontal,

wherein a pre-motor filter has a height in a direction transverse to the cyclone axis and the height is larger than a diameter of the cyclone.

9. A surface cleaning apparatus comprising:

- (a) a hand vacuum cleaner having a front end having a dirty air inlet, a rear end, a clean air outlet, an upper end, a lower end and a pistol grip handle, the hand vacuum cleaner comprising:
 - (i) a main body comprising an upper end, a lower end, a front end and a rear end, the main body housing a suction motor and fan assembly, the suction motor and fan assembly having a suction motor axis of rotation; and,
 - (ii) a cyclone unit comprising a cyclone chamber and a dirt collection chamber that is exterior to the cyclone chamber, the cyclone chamber having a cyclone axis of rotation, a front end, an axially spaced apart rear end, a cyclone air inlet, and a cyclone air outlet provided at the rear end of the cyclone unit, wherein the cyclone axis of rotation intersects the pistol grip handle and a line that is parallel to the cyclone axis extends through the dirt collection chamber and a location interior of a radial outer perimeter of a pre-motor filter;

- (b) a surface cleaning head having a front end, a rear end, a dirty air inlet and a surface cleaning head air outlet; and,
- (c) a rigid air flow conduit that is removably mountable to the surface cleaning head and, when attached to the hand vacuum cleaner and the surface cleaning head, extends between the surface cleaning head air outlet and the dirty air inlet of the hand vacuum cleaner,

wherein the dirty air inlet of the hand vacuum cleaner is removably drivingly mounted to a downstream end of the rigid air flow conduit whereby when the hand vacuum cleaner is mounted to the downstream end of the rigid air flow conduit, the pistol grip handle is a driving handle for the surface cleaning apparatus, and wherein when the hand vacuum cleaner is positioned with the front end of the hand vacuum cleaner in front of the rear end of the hand vacuum cleaner, the cyclone axis of rotation is generally horizontal.

10. A surface cleaning apparatus comprising:

- (a) a hand vacuum cleaner comprising:
 - (i) a main body comprising a lower end, an upper end, a front end, a rear end and a pistol grip handle, the main body housing a suction motor and fan assembly, the suction motor and fan assembly having a suction motor axis of rotation, the pistol grip handle is provided at the rear end of the main body and extends upwardly and forwardly when the hand vacuum cleaner is positioned with the front end forward of the rear end;
 - (ii) a cyclone unit comprising a cyclone chamber having a cyclone axis of rotation, a front end and a rear end wherein air exits the cyclone chamber at the rear end of the cyclone chamber, wherein the suction

54

motor axis of rotation is generally parallel to the cyclone axis of rotation; and

- (b) a dirt collection chamber that is exterior to the cyclone chamber and a forward end of the dirt collection chamber is openable;

- (c) a surface cleaning head having a front end, a rear end, a dirty air inlet and a cleaning head air outlet; and,

- (d) a rigid air flow conduit that is removably mountable to the surface cleaning head and, when attached to the hand vacuum cleaner and the surface cleaning head, extends between the cleaning head air outlet and a hand vacuum cleaner air inlet, the rigid air flow conduit having a longitudinally extending conduit axis,

wherein the hand vacuum cleaner is removably mountable to a downstream end of the rigid air flow conduit and, when the hand vacuum cleaner is mounted to the downstream end of the rigid air flow conduit, the handle is a driving handle for the surface cleaning apparatus and the longitudinally extending conduit axis of the rigid air flow conduit is parallel to the cyclone axis of rotation, and

wherein a finger grip area is provided at a location that is forward of the pistol grip handle and rearward of the cyclone.

11. The surface cleaning apparatus of claim 10 further comprising a pre-motor filter, wherein the cyclone axis of rotation intersects the pre-motor filter.

12. The surface cleaning apparatus of claim 10 wherein the cyclone unit is removably mounted to the main body.

13. The surface cleaning apparatus of claim 10 further comprising a pre-motor filter, wherein the pre-motor filter is accessible when the cyclone unit is removed from the main body.

14. A surface cleaning apparatus comprising:

- (a) a hand vacuum cleaner comprising:

- (i) a main body comprising a lower end, an upper end, a front end, a rear end and a pistol grip handle, the main body housing a suction motor and fan assembly, the suction motor and fan assembly having a suction motor axis of rotation, the pistol grip handle is provided at the rear end of the main body and extends upwardly and forwardly when the hand vacuum cleaner is positioned with the front end forward of the rear end; and,
- (ii) a cyclone unit comprising a cyclone chamber having a cyclone axis of rotation, a front end and a rear end wherein air exits the cyclone chamber at the rear end of the cyclone chamber, wherein the suction motor axis of rotation is generally parallel to the cyclone axis of rotation; and

- (b) a surface cleaning head having a front end, a rear end, a dirty air inlet and a cleaning head air outlet; and,
- (c) a rigid air flow conduit that is removably mountable to the surface cleaning head and, when attached to the hand vacuum cleaner and the surface cleaning head, extends between the cleaning head air outlet and a hand vacuum cleaner air inlet, the rigid air flow conduit having a longitudinally extending conduit axis,

wherein the hand vacuum cleaner is removably mountable to a downstream end of the rigid air flow conduit and, when the hand vacuum cleaner is mounted to the downstream end of the rigid air flow conduit, the handle is a driving handle for the surface cleaning apparatus and the longitudinally extending conduit axis of the rigid air flow conduit is parallel to the cyclone axis of rotation, and

wherein the hand vacuum cleaner is removably mountable to a downstream end of the rigid air flow conduit and, when the hand vacuum cleaner is mounted to the downstream end of the rigid air flow conduit, the handle is a driving handle for the surface cleaning apparatus and the longitudinally extending conduit axis of the rigid air flow conduit is parallel to the cyclone axis of rotation, and

55

wherein a finger grip area is provided at a location that is forward of the pistol grip handle and rearward of the cyclone, and

wherein a pre-motor filter has a height in a direction transverse to the cyclone axis and the height is larger than a diameter of the cyclone. 5

15. A surface cleaning apparatus comprising:

(a) a hand vacuum cleaner comprising:

(i) a main body comprising a lower end, an upper end, a front end, a rear end and a pistol grip handle, the main body housing a suction motor and fan assembly, the suction motor and fan assembly having a suction motor axis of rotation, the pistol grip handle is provided at the rear end of the main body and extends upwardly and forwardly when the hand vacuum cleaner is positioned with the front end forward of the rear end; and, 10

(ii) a cyclone unit comprising a cyclone chamber and a dirt collection chamber that is exterior to the cyclone chamber, the cyclone chamber having a cyclone axis of rotation, a front end and a rear end wherein air exits the cyclone chamber at the rear end of the cyclone chamber, wherein the suction motor axis of rotation is generally parallel to the cyclone axis of 15 20

56

rotation and a line that is parallel to the cyclone axis extends through the dirt collection chamber and a location interior of a radial outer perimeter of a pre-motor filter,

(b) a surface cleaning head having a front end, a rear end, a dirty air inlet and a cleaning head air outlet; and,

(c) a rigid air flow conduit that is removably mountable to the surface cleaning head and, when attached to the hand vacuum cleaner and the surface cleaning head, extends between the cleaning head air outlet and a hand vacuum cleaner air inlet, the rigid air flow conduit having a longitudinally extending conduit axis,

wherein the hand vacuum cleaner is removably mountable to a downstream end of the rigid air flow conduit and, when the hand vacuum cleaner is mounted to the downstream end of the rigid air flow conduit, the handle is a driving handle for the surface cleaning apparatus and the longitudinally extending conduit axis of the rigid air flow conduit is parallel to the cyclone axis of rotation, and

wherein a finger grip area is provided at a location that is forward of the pistol grip handle and rearward of the cyclone.

* * * * *