

Ion-Implanted Laser-Annealed p⁺ and n⁺ Regions: A Potential Solution for Industrially Feasible High-Efficiency N-Type Interdigitated Back-Contact Solar Cells

Publisher: IEEE

Cite This

PDF

<< Results

Xinbo Yang ; Ralph Müller ; Lujia Xu ; Qunyu Bi ; Klaus Weber ; Evan Franklin ; Jan Benick All Authors

6
Cites in
Papers

456
Full
Text Views

Alerts

Manage Content Alerts
Add to Citation Alerts

Abstract

Document Sections

I. Introduction

II. Experimental Details

III. Results and Discussion

IV. Conclusion

Authors

Figures

References

Citations

Keywords

Metrics

Download PDF

Abstract:

The main challenge for interdigitated back-contact (IBC) solar cells is to reduce the fabrication complexity, which consists of multiple high-temperature processing and p... [View more](#)

▼ Metadata

Abstract:

The main challenge for interdigitated back-contact (IBC) solar cells is to reduce the fabrication complexity, which consists of multiple high-temperature processing and patterning steps. Patterned ion implantation has been proposed to simplify the manufacture of IBC solar cells, and the annealing of boron and phosphorus implanted areas is still a problem for the application. In this study, a new method consisting of laser annealing and a subsequent low-temperature oxidation (LA&OX) has been developed to co-anneal boron implanted p⁺ and phosphorus implanted n⁺ regions by a single step. We found that an additional laser annealing before oxidation could improve the electrical properties of boron-implanted p⁺ regions effectively; however, it has almost no effect on the phosphorus-implanted n⁺ regions. An industrially feasible IBC solar cell fabrication technology has been proposed based on the patterned ion implantation and LA&OX processing. The main fabrication steps of the IBC solar cell could be reduced to ten steps, and only one high-temperature oxidation step is required. As-designed IBC cell shows a potential efficiency higher than 23% according to simulations with the experimental parameters.

More Like This

Footnotes

Published in: IEEE Journal of Photovoltaics (Volume: 5 , Issue: 1, January 2015)

Page(s): 87 - 93

DOI: 10.1109/JPHOTOV.2014.2361211

Date of Publication: 15 October 2014 

Publisher: IEEE

 **ISSN Information:**

 **Funding Agency:**

References is not available for this document.

 Contents

I. Introduction

N-type interdigitated back-contact (IBC) solar cells offer numerous advantages over conventional solar cells, e.g., no optical shading loss with front metal grid results in high short-circuit current density , independent optimization of surface passivation and optics at the front and large metal coverage on the rear that minimizes series resistance, ease of adopting n-type silicon, and extreme high efficiency [1]. SunPower Corporation has reported an efficiency of 24.2% on a large-area (155.1 cm²) n-type IBC cell using production equipment [2]. Recently, an n-type IBC solar cell with an efficiency of 24.4% has been fabricated with the diffusion method at the Australian National University (ANU) [3]. However, the conventional IBC solar cells is often too costly for commercial production with typically two or more high-temperature diffusions and patterning steps being required. In the meantime, there are numerous disadvantages associated with multiple high-temperature processing steps, including increased processing time, high costs, increased potential for introducing contaminants, and degradation in bulk lifetime. One or more of these diffusions is performed through a diffusion mask, such as silicon dioxide, which needs to be grown at high temperatures and patterned using the photolithography method [4]. Therefore, a simplified, low-cost, and industrially feasible n-type IBC solar cell fabrication technology is highly desired.

Authors

Figures

References



References & Cited By

☐ Select All

1.

E. Kerschaver and G. Beaucarne, "Back-contact solar cells: A review", *Prog. Photovoltaics*, vol. 14, pp. 107-123, 2006.

 Show in Context

 CrossRef

 Google Scholar
2.

P. J. Cousins, D. D. Smith, H.-C. Luan, J. Manning, T. D. Dennis, A. Waldhauer, et al., "Generation 3: Improved performance at lower cost", *Proc. 35th IEEE Photovoltaic Spec. Conf.*, pp. 000275-000278, 2010.

 Show in Context

 View Article

 Google Scholar
3.

E. Franklin, K. C. Fong, K. R. McIntosh, A. Blakers, K. Teng, D. Wang, et al., "Fabrication and characterisation of a 24.4% efficient interdigitated back contact solar cell", *29th Eur. Photovoltaic Sol. Energy Conf.*, 2014.

 Show in Context

 CrossRef

 Google Scholar

4. C. E. Chan, B. J. Hallam and S. R. Wenham, "Simplified interdigitated back contact solar cells", *Energy Procedia*, vol. 27, pp. 543-548, 2012.
[► Show in Context](#) [CrossRef](#)  [Google Scholar](#) 

5. A. Rohatgi, D. Meier, B. McPherson, Y. OK, A. D. Upadhyaya, J. H. Lai, et al., "High-throughput ion implantation for low-cost high-efficiency silicon solar cells", *Energy Procedia*, vol. 15, pp. 10-19, 2012.
[► Show in Context](#) [CrossRef](#)  [Google Scholar](#) 

6. M. Hermle, J. Benick, M. Rüdiger, N. Bateman and S. W. Glunz, "N-type silicon solar cells with implanted emitter", *Proc. 26th Eur. Photovoltaic Sol. Energy Conf.*, pp. 875-878, 2011.
[► Show in Context](#) [Google Scholar](#) 

7. A. Gupta, R. J. Low, N. Bateman, D. Ramappa, H. L. Gossman, Q. Zhai, et al., "High efficiency selective emitter cells by in-situ patterned ion implantation", *Proc. 25th Eur. Photovoltaic Sol. Energy Conf.*, pp. 1158-1162, 2010.
[Google Scholar](#) 

8. C. E. Dubé, B. Tsefreakas, D. Buzby, R. Tavares, W. M. Zhang, A. Gupta, et al., "High efficiency selective emitter cells using patterned ion implantation", *Energy Procedia*, vol. 8, pp. 706-711, 2011.
[CrossRef](#)  [Google Scholar](#) 

9. M. Jeon, J. Lee, S. Kim, W. Lee and E. Cho, "Ion implanted crystalline silicon solar cells with blanket and selective emitter", *Mater. Sci. Eng. B*, vol. 176, pp. 1285-1290, 2011.
[► Show in Context](#) [CrossRef](#)  [Google Scholar](#) 

10. M. Kang, J. H. Lee, H. Boo, S. Tark, H. C. Hwang, W. J. Hwang, et al., "Effects of annealing on ion-implanted Si for interdigitated back contact solar cell", *Current Appl. Phys.*, vol. 12, pp. 1615-1618, 2012.
[► Show in Context](#) [CrossRef](#)  [Google Scholar](#) 

11. R. Müller, C. Reichel, J. Benick and M. Hermle, "Ion implantation for all-alumina IBC solar cells with floating emitter", *Energy Procedia*, vol. 55, pp. 265-271, 2014.
[► Show in Context](#) [CrossRef](#)  [Google Scholar](#) 

12. R. Müller, J. Benick, N. Bateman, J. Schön, C. Reichel, M. A. Richter, et al., "Evaluation of implantation annealing for highly-doped selective boron emitter suitable for screen-printed contacts", *Sol. Energy Mater. Sol. Cells*, vol. 120, pp. 431-435, 2014.
[► Show in Context](#) [CrossRef](#)  [Google Scholar](#) 

13. R. T. Young, C. W. White, G. J. Clark, J. Narayan, W. H. Christie, M. Murakami, et al., "Laser annealing of boron-implanted silicon", *Appl. Phys. Lett.*, vol. 32, pp. 139-141, 1978.
[► Show in Context](#) [CrossRef](#)  [Google Scholar](#) 

14. C. W. White, J. Narayan and R. T. Young, "Laser annealing of ion-implanted semiconductors", *Science*, vol. 204, pp. 461-468, 1979.
[► Show in Context](#) [CrossRef](#)  [Google Scholar](#) 

15. X. Yang, R. Müller, A. Shalav, L. Xu, W. Liang, R. Zhang, et al., "Boron implanted laser annealed p + emitter for n-type interdigitated back-contact solar cells", *Energy Procedia*, vol. 55, pp. 320-325, 2014.
[► Show in Context](#) [CrossRef](#)  [Google Scholar](#) 

- ☐ 16. A. Fell, K. C. Fong, K. R. McIntosh, E. Franklin and A. W. Blakers, "3-D simulation of interdigitated-back-contact silicon solar cells with Quokka including perimeter losses", *IEEE J. Photovoltaics*, vol. 4,

no. 4, pp. 1040-1045, Jul. 2014.

► Show in Context

View Article



Google Scholar 

17. P. E. Gruenbaum, R. A. Sinton and R. M. Swanson, "Light-induced degradation at the silicon/silicon dioxide interface", *Appl. Phys. Lett.*, vol. 52, pp. 1407-1409, 1988.

► Show in Context

CrossRef 

Google Scholar 

18. H. Ryssel and I. Ruge, "Ionen implantation", *Proc. Akademische Verlagsgesellschaft Geest & Portig K.G.*, 1978.

► Show in Context

Google Scholar 

19. K. S. Jones, S. Prussin and E. R. Weber, "A systematic analysis of defects in ion-implanted silicon", *Appl. Phys. A*, vol. 45, pp. 1-34, 1988.

► Show in Context

CrossRef 

Google Scholar 

20. T. J. Ratcliff, A. Shalav, K. C. Fong, R. G. Elliman and A. W. Blakers, "Influence of implantation damage on emitter recombination", *Energy Procedia*, pp. 55-279, 2014.

► Show in Context

CrossRef 

Google Scholar 

21. Z. Hameiri, T. Puzzer, L. Mai, A. B. Sproul and S. R. Wenham, "Laser induced defects in laser doped solar cells", *Prog. Photovoltaics*, vol. 19, pp. 391-405, 2011.

► Show in Context

CrossRef 

Google Scholar 

22. A. Cuevas, P. A. Basore, G. G. Matlakowski and C. Dubois, "Surface recombination velocity of highly doped n-type silicon", *J. Appl. Phys.*, vol. 80, pp. 3370-3375, 1996.

► Show in Context

CrossRef 

Google Scholar 

23. R. Peibst, N. P. Harder, A. Merkle, T. Neubert, S. Kirstein, J. Schmidt, et al., "High efficiency RISE-IBC solar cells: Influence of rear side passivation on p-n junction recombination", *Proc. 28th Eur. Photovoltaic Sol. Energy Conf.*, pp. 971-975, 2013.

► Show in Context

Google Scholar 

24. F. Granek, "High-efficiency back-contact back-junction silicon solar cells", 2009.

► Show in Context

Google Scholar 

25. A. Richter, S. W. Glunz, F. Werner, J. Schmidt and A. Cuevas, "Improved quantitative description of auger recombination in crystalline silicon", *Phys. Rev. B*, vol. 86, pp. 165202-1-165202-14, 2012.

► Show in Context

CrossRef 

Google Scholar 

Citations	▼
Keywords	▼
Metrics	▼
Footnotes	▼

IEEE

Get Published
in the
IEEE Journal of
Selected Areas in
Sensors

Learn More

More Like This

Nd:YAG laser annealing investigation of screen-printed CIGS layer on PET: Layer annealing method for photovoltaic cell fabrication process
2014 IEEE 40th Photovoltaic Specialist Conference (PVSC)
Published: 2014

Defect Passivation in Poly-Si TFTs by Ion Implantation and Pulsed Laser Annealing
IEEE Electron Device Letters
Published: 2006

Show More

The *IEEE Open Journal of Power Electronics* has received its first Journal Impact Factor™

Now accepted for indexing by Clarivate

Learn More

CHANGE
USERNAME/PASSWORD

PAYMENT OPTIONS
VIEW PURCHASED
DOCUMENTS

COMMUNICATIONS
PREFERENCES

PROFESSION AND
EDUCATION

TECHNICAL INTERESTS

US & CANADA: +1 800
678 4333

WORLDWIDE: +1 732
981 0060

CONTACT & SUPPORT

[About IEEE Xplore](#) [Contact Us](#) [Help](#) [Accessibility](#) [Terms of Use](#) [Nondiscrimination Policy](#) [IEEE Ethics Reporting](#)  [Sitemap](#)
[IEEE Privacy Policy](#)

IEEE Account

- » [Change Username/Password](#)
- » [Update Address](#)

Purchase Details

- » [Payment Options](#)
- » [Order History](#)
- » [View Purchased Documents](#)

Profile Information

- » [Communications Preferences](#)
- » [Profession and Education](#)
- » [Technical Interests](#)

Need Help?

- » **US & Canada:** +1 800 678 4333
- » **Worldwide:** +1 732 981 0060
- » [Contact & Support](#)

[About IEEE Xplore](#) [Contact Us](#) [Help](#) [Accessibility](#) [Terms of Use](#) [Nondiscrimination Policy](#) [Sitemap](#) [Privacy & Opting Out of Cookies](#)

A not-for-profit organization, IEEE is the world's largest technical professional organization dedicated to advancing technology for the benefit of humanity.

© Copyright 2024 IEEE - All rights reserved. Use of this web site signifies your agreement to the terms and conditions.