

JOURNAL
OF
APPLIED
PHYSICS

S

25

JAN-JUN

1954

LH
7J82
AP5
25
1-6

89048209449



b89048209449a

Journal of Applied Physics

ELMER HUTCHISSON, *Editor*

EARLE C. GREGG, *Assistant Editor*

Board of Editors

MAURICE A. BIOT

ROBERT D. HEIDENREICH

W. R. SMYTHE

RAY E. BOLZ

LOUIS A. PIPES

ARTHUR V. TOBOLSKY

WALLACE J. ECKERT

ROMAN SMOLUCHOWSKI

A. M. WEINBERG

VOLUME 25

JANUARY-DECEMBER, 1954

Published by the

AMERICAN INSTITUTE OF PHYSICS

Incorporated

INFORMATION FOR CONTRIBUTORS

Send manuscripts to Elmer Hutchisson, Case Institute of Technology, Cleveland 6, Ohio. Textual material (abstract, the body of the paper, tabular material, references, and figure captions) must be in English, typewritten (except mathematical expressions) double spaced with wide margins on a durable, white paper, preferably letter size. The original copy, not the carbon, should be submitted. For general style, spellings, abbreviations, and form, consult recent issues of this journal. Authors' institutions are requested to pay a publication charge of \$8 per page which entitles them to 100 reprints without further charge.

An abstract must accompany each article. It should be adequate as an index and as a summary.

All but the simplest mathematical expressions should be carefully printed in by hand. Be sure to distinguish between capital and small letters. Indicate clearly superscripts and subscripts by inverted carets and carets, respectively. Avoid complicated superscripts and subscripts. Avoid repetition of a complicated expression by representing it by a symbol. Identify in the margin Greek letters and unusual symbols. Use fractional exponents instead of root signs. Use the solidus (/) for fractions wherever its use will save vertical space.

References should appear as footnotes, numbered consecutively, and arranged thus:

¹ A. B. Smith, *Phy. Rev.* 41, 852 (1932).

² H. Lamb, *Hydrodynamics* (Cambridge University Press, Teddington, England), sixth edition, pp. 573, 645.

Tables may be typewritten on sheets separate from the running text. Each table must have a caption which will make the data in the table intelligible without reference to the text. Avoid complicated column headings.

Wherever possible figures should be planned for the width of a column (3 in.). A convenient reduction ratio is about 2:1 or 3:1. Lettering should be large enough on the original that when reduced it shall not be less than about $\frac{1}{16}$ in. (~ 1.5 mm). Line drawings must be in *India ink* on white paper or tracing cloth. Coordinate paper is not desirable but if used must be blue lined and the coordinate lines which are to show must be inked over. Photographs should have maximum black and white contrast.

Identify each original drawing or photograph on the back with the author's name and the figure number. Figures should be numbered consecutively. Captions should be typed on a separate sheet of paper.

A limited number of alterations in proof are unavoidable, but the cost of making extensive alterations after the article has been set in type will be charged to the author.

Proof and all correspondence concerning papers in the process of publication should be addressed to the Publication Manager, American Institute of Physics, 57 East 55 Street, New York 22, New York.

INFORMATION FOR SUBSCRIBERS

The JOURNAL OF APPLIED PHYSICS is devoted to physics in its role as the science basic to other natural sciences and to the arts and industries. Previous to 1937 this publication was known as PHYSICS. It aims to be of service not only in physical laboratories, but also in the laboratories of industrial, chemical, geological, geophysical, meteorological, radio, and similar concerns. The JOURNAL OF APPLIED PHYSICS publishes editorials and reviews, as well as technical papers of applied physics.

Subscriptions and orders for back numbers should be addressed to the American Institute of Physics, 57 East 55 Street, New York 22, New York.

SUBSCRIPTION PRICE

	U. S. and Canada	Elsewhere
To members of the American Institute of Physics and Affiliated Societies	\$10.00	\$11.00
To all others	12.00	13.00

BACK NUMBER PRICE

Yearly back number rate when complete year is available: \$14.00.
Single copies: \$1.25 each.

Advertising rates will be supplied on request.

American Institute of Physics

57 East 55 Street

New York 22, New York

Physics-Math


JOURNAL OF APPLIED PHYSICS

Vol. 25, No. 5

RECEIVED
MAY 25 1954

UNIV. WIS. LIBRARY

May, 1954



Wave Structure of Ridges Produced in Front Surface of Cylindrical Projectile Striking Obliquely a Thin Lead Sheet. See page 676.

JOURNAL OF APPLIED PHYSICS

Vol. 25, No. 5

MAY, 1954

In This Issue

	Page
Circumferential Gap in a Circular Wave Guide Excited by a Dominant Circular-Electric Wave	Leonard S. Sheingold and James E. Storer 545
Impedance of a Top-Loaded Antenna of Arbitrary Length over a Circular Grounded Screen	James R. Wait and Walter J. Surtees 553
Plastic Deformation in Beams under Distributed Dynamic Loads	J. A. Seiler and P. S. Symonds 556
Tube Noise under Large Transit-Time Conditions	S. V. Yadavalli 564
Some Phenomena Associated with Supersonic Liquid Jets	Brian Dunne and Benedict Cassen 569
Transverse Motion of an Electron in a Constant Wave Speed Section of a Linear Accelerator	Ira Jacobs and E. S. Akeley 572
Friction of Clean Metals and Oxides with Special Reference to Titanium	E. S. Machlin and W. R. Yankee 576
On the Band Width of Cavity Antennas	Marshall H. Cohen 582
Multiple Shock Reflection in Corners	Joseph B. Keller 588
Measurement of the Effect of Chlorine Treatment on the Work Function of Titanium and Zirconium	Herbert Malamud and Aaron D. Krumbein 591
Delayed Yield and Strain Rate and Temperature Dependence of Yield Point in Iron	Takeo Yokobori 593
Negentropy and Information in Telecommunications, Writing, and Reading	L. Brillouin 595
Electrolytic Analog Transistor	Harry Letaw, Jr., and John Bardeen 600
Diffusion in Bimetal Vapor-Solid Couples	R. W. Balluffi and L. L. Seigle 607
Stored Energy and Power Flow in Electron Beams	L. R. Walker 615
Information Theory and Knowledge	D. K. C. MacDonald 619
Limiting Pressure on Hydrofoils at Small Submergence Depths	E. V. Laitone 623
Fast Time Analysis of Intermittent Point-to-Plane Corona in Air. III. The Negative Point Trichel Pulse Corona	M. R. Amin 627
Volume and Surface Recombination Rates for Injected Carriers in Germanium	J. P. McKelvey and R. L. Longini 634
Propagation of Microwaves between a Parallel Pair of Doubly Curved Conducting Surfaces	K. S. Kunz 642
Errors in Power Spectra Due to Finite Sample	Lee M. Spetner 653
Approximate Emissivity Calculations for Polyatomic Molecules. I. CO ₂	S. S. Penner 660
Cross Section of Pulled Crystals	Robert G. Pohl 668
Some New Magneto-Mechanical Torsion Experiments	A. W. Cochardt 670
Letters to the Editor:	
Electron Bunches of Short Time Duration	E. W. Ernst and H. VonFoerster 674
Effect Produced by Oblique Impact of a Cylinder on a Thin Target	William A. Allen, Joe M. Mapes, and Wesley G. Wilson 675
New Silicon p-n Junction Photocell for Converting Solar Radiation into Electrical Power	D. M. Chapin, C. S. Fuller, and G. L. Pearson 676
Dissected Amplifiers Using Negative Resistance	W. Shockley and W. P. Mason 677
On the Interaction of Two Plane Shocks Facing in the Same Direction	Otto Laporte and E. B. Turner 678
High-Speed Magnetic Pulsing of Ferrites	R. Conway LeCraw 678
Crossed Electron Beam Technique for Measuring Space-Charge Effects in Beams	Paul D. Coleman, Murray D. Sirkis, and Irving Kaufman 679
Combined Slow-Wave Circuit and Beam Focusing Structure	Philip Rice 680
Announcements	681
Index to Advertisers	xxii

ELMER HUTCHISSON,
Editor

EARLE C. GREGG,
Assistant Editor

Board of Editors
MAURICE A. BIOT
RAY E. BOLZ
WALLACE J. ECKERT
ROBERT D. HEIDENREICH
LOUIS A. PIPES
ROMAN SMOLUCHOWSKI
W. R. SMYTHE
ARTHUR V. TOBOLSKY
ALVIN M. WEINBERG

**Publication of the
American
Institute of Physics**

OFFICERS

FREDERICK SEITZ,
Chairman
GEORGE B. PEGRAM,
Treasurer

GOVERNING BOARD

ROBERT F. BACHER
J. W. BUCHTA
KARL K. DARROW
S. A. GOUDSMIT
DEANE B. JUDD
HUGH S. KNOWLES
C. C. LAURITSEN
W. H. MARKWOOD, JR.
WILLIAM F. MEGGERS
PHILIP M. MORSE
BRIAN O'BRIEN
HARRY F. OLSON
GEORGE B. PEGRAM
ERIC RODGERS
RALPH A. SAWYER
FREDERICK SEITZ
WILLIAM SHOCKLEY
RICHARD M. SUTTON
J. H. VAN VLECK
MARK W. ZEMANSKY

Consultant on Printing
MELVIN LOOS

ADMINISTRATIVE STAFF

HENRY A. BARTON,
Director
WALLACE WATERFALL,
Executive Secretary
THEODORE VORBURGER,
Advertising Manager
RUTH F. BRYANS,
Publication Manager
EDITH I. NEFTTEL
Circulation Manager
KATHRYN SETZE
Assistant Treasurer

The JOURNAL OF APPLIED PHYSICS, published monthly at Prince and Lemon Sts., Lancaster, Pa., is devoted to physics in its role as the science basic to other natural sciences and to the arts and industries. Previous to 1937 this publication was known as PHYSICS. The JOURNAL OF APPLIED PHYSICS publishes editorials and reviews, as well as technical papers of applied physics. Articles appearing in it are indexed regularly, according to their field, by Physics Abstracts, Chemical Abstracts, Engineering Index, Inc., Industrial Arts Index, etc.

Manuscripts should be submitted to Elmer Hutchisson, Editor, Case Institute of Technology, Cleveland 6, Ohio. Unless otherwise stated, submission of a manuscript is a representation that it has been neither copyrighted, published, nor submitted for publication elsewhere. The authors' institutions are requested to pay a publication charge of \$8 per page which, if honored, entitles them to 100 reprints without further charge. Instructions will be sent with galley proofs.

Entered as second class matter January 22, 1937, at the Post Office at Lancaster, Pennsylvania, under the Act of March 3, 1879. Accepted for mailing at the special rate of postage provided for in paragraph (d-2), section 34.40, P. L. & R. of 1948, authorized May 2, 1932.

Subscriptions, renewals, and orders for back numbers should be addressed to the American Institute of Physics, 57 East 55 Street, New York 22, New York.

	Subscription Price	U.S. and Canada	Elsewhere
To members of the American Institute of Physics and Affiliated Societies	\$10.00	\$11.00	
To all others	12.00	13.00	

Back Number Prices

Yearly back number rate when complete year is available: \$14.00.
Single copies: \$1.25 each.

Changes of address should be sent to the American Institute of Physics; corrected proofs should be sent to the Publication Manager, American Institute of Physics. Advertising rates supplied on request. Orders, advertising copy, and cuts should be sent to the American Institute of Physics.



FIG. 1. End view of 0.50 caliber cylindrical steel projectile after it has passed through a 0.005-in. lead target at 45 deg striking angle. The actual diameter of this cylinder is 0.428 in.

Figure 1 is a photograph of the end of a 0.50 caliber cylindrical steel projectile after it has penetrated a 0.005-in. lead target aligned at a 45 deg striking angle. Figure 2 is a photomicrograph of a cross section of a cylinder that shows the wave structure of the ridges. Although the mechanism responsible for production of these waves is somewhat obscure, the critical angle 2ϕ is believed to be the same critical angle discussed by the Los Alamos group¹ in a paper that deals with metal plates accelerated together by high explosive charges. The Los Alamos group has discussed the asymmetric collision of dissimilar solids, but has not yet reported any experimental data. The specimens shown in Figs. 1 and 2 correspond to the asymmetric case.

The experiment was modified to obtain symmetric collision. Steel projectiles with conical noses specified by the half-angle $\pi/2 - \theta$ were fired into steel targets aligned at the striking angle θ . Plastic deformation occurs along one of the elements of the cone provided that $2\theta > 2\phi$. Negligible plastic deformation occurs if $2\theta < 2\phi$. The critical angle 2ϕ determined by this experiment is in excellent agreement with the predicted¹ value for iron. Two preliminary determinations indicate the value $2\phi = 7.7$ deg for a projectile velocity of 0.87 mm/ μ sec. This velocity corresponds to the plate velocity $v_p = 0.43$ mm/ μ sec of Fig. 15 in reference 1.

The experiment discussed is believed to be equivalent to that of the Los Alamos group. No theoretical or experimental difficulty is expected if the technique is extended to higher velocities and to solids other than steel. The experiment is expected to be of value in checking and determining equation of state data of solids in the megabar pressure regime. As a basis for comparison, the compressibility of pure iron has been measured up to a maxi-

mum pressure of only 0.03 megabar.² The pressure produced at the critical angle 2ϕ by the symmetric collision of steel is 0.47 megabar, a value calculated from the published¹ equation of state of iron.

¹ Walsh, Shreffler, and Willig, J. Appl. Phys. 24, 349 (1953).

² P. W. Bridgman, Revs. Modern Phys. 18, 1 (1946).

A New Silicon *p-n* Junction Photocell for Converting Solar Radiation into Electrical Power

D. M. CHAPIN, C. S. FULLER, AND G. L. PEARSON
Bell Telephone Laboratories, Inc., Murray Hill, New Jersey
(Received January 11, 1954)

THE direct conversion of solar radiation into electrical power by means of a photocell appears more promising as a result of recent work on silicon *p-n* junctions. Because the radiant energy is used without first being converted to heat, the theoretical efficiency is high.

Photons of 1.02 electron volts ($\lambda = 1.2$ microns) are able to produce electron-hole pairs in silicon. In the presence of a *p-n* barrier, these electron-hole pairs are separated and made to do work in an external circuit. All of the light of wavelength shorter than 1.2 microns is potentially useful for generating electron-hole pairs but the efficiency of energy conversion decreases for short wavelengths because the energy above the necessary 1.02 electron




FIG. 1. Normalized spectral energy distribution. (A) Silicon photocell equi-energy response. (B) Solar energy at earth's surface. (C) Curve A times Curve B.

volts is wasted. Allowing for this loss and assuming a working voltage of 0.5 volt, which is near the maximum measured, a computation over the entire solar spectrum indicates a limiting efficiency of approximately 22 percent for a cell of negligible internal losses and for utilization of all possible electron-hole pairs.

Several practical factors lower this figure. The untreated silicon surface reflects about half of the incident radiation. Some of this can be saved by proper surface treatment. The second serious loss is recombination of electron-hole pairs before they reach the *p-n* barrier. Penetration of radiation over most of the useful spectrum is extremely shallow so that it becomes necessary to place the *p-n* junction as near to the surface as possible except for the third serious loss. This is the I^2R loss caused by resistance in the surface layer and by contact resistance. Extremely small cells minimize the resistance loss and give useful data. For cells of several square centimeters, special geometry of contacts will minimize resistance losses.

Present work on silicon *p-n* photocells uses a thin layer of *p*-type silicon formed over an *n*-type base. The surface layer is less than 0.0001 inch thick. Figure 1 shows the spectral response for one such cell. Curve A is the measured power output for equal intensities of weak radiation as a function of wavelength. Maxi-



FIG. 2. Photomicrograph of a cross section of a projectile which shows the wave structure formed by 45 deg impact on a 0.010-in. lead target. The average distance from crest to crest is 0.033 in.

imum sensitivity is arbitrarily taken as unity. Ideally the maximum should appear near 1.2 microns with half this sensitivity at 0.6 and one-quarter at 0.3 micron. Curve *B* is the normal distribution of full sunlight¹ with the maximum expressed as unity. Curve *C* is the product of Curve *A* and Curve *B* again reduced to unity for maximum. This curve shows which part of the sun's radiation is most useful for this particular cell.

The photocells described here have been made to deliver power from the sun into a resistance load at the rate of 60 watts per square meter of photocell surface. This is approximately 6 percent efficiency and compares with a measured value of 0.5 percent on a commercially available photocell. The greatest over-all efficiency previously reported for direct conversion of solar radiation into electrical power is that of Telkes² using thermoelectric junctions and amounts to 1 percent.

We wish to thank H. B. Briggs who made the spectral measurements shown in Curve *A*.

¹ W. E. Forsythe, *Measurement of Radiant Energy* (McGraw-Hill Book Company, Inc., New York, 1937).

² Maria Telkes, *J. Appl. Phys.* **18**, 1116 (1947).

Dissected Amplifiers Using Negative Resistance

W. SHOCKLEY AND W. P. MASON

Bell Telephone Laboratories, Inc., Murray Hill, New Jersey

(Received December 28, 1953)

IT is the purpose of this communication to point out a line of attack upon the problem of making high-frequency semiconductor amplifiers. This attack may be described as the dissection of the amplification mechanism into its two constituents: negative resistance and directionality.

Negative resistance is a common feature of all amplifying devices operating from a dc power source. Thus the net ac power from the device when operating as an amplifier is positive. Since this power is the net flux of the ac part of Poynting's vector, it follows that Poynting's vector must have a positive divergence throughout certain "negative resistance regions." For a vacuum-tube triode amplifier, the grid-plate space is such a region, the current being high when the voltage is low and vice versa. Similarly, the space-charge region of the collector junction of a junction transistor amplifier has negative resistance. It should be noted that these negative resistances are not characteristic of the regions *per se* but instead of their behavior in an amplifier circuit.

This method of analysis enables one to evaluate quickly such proposals as the making of a junction transistor from isolated *p-n* junctions (impossible because no negative resistances can occur) or an amplifier from a nonlinear dielectric and dc power source.

Directionality arises in vacuum tubes and transistors because of the separation of input and output circuits. This leads to asymmetry in the current voltage matrix and permits the achievement of high gain by cascading stages without resultant instability.

Because the drift velocity of electrons (or holes) in semiconductors is smaller than the average transit velocity in vacuum tubes, the physical dimensions must be smaller for the same transit times. Although the solid nature of transistors gives them an inherent structural advantage over vacuum tubes, the smaller scale required for them poses serious problems of construction for devices in the highest-frequency ranges.

One way around this difficulty is to make two-terminal negative resistance devices in which only one dimension need be small. A variety of operating principles are possible for the operation of such devices.¹

Two-terminal negative resistance devices have the disadvantage, however, that they do not have directionality; consequently, high gain is associated with narrow margins of stability.

This limitation may be overcome by adding directionality through passive elements² such as Hall effect couplers or gyrators³




FIG. 1. Hall effect plate and three resistances. (Power supplies and connections necessary to power the negative resistances are not shown.)

in wave guides.⁴ Such combinations can simulate conventional amplifying devices such as a vacuum-tube triode. In Fig. 1 the hexagon represents a germanium plate with a magnetic field perpendicular to its plane. It contributes in Eqs. (1) and (2) the terms involving the conductance y_0 and the dimensionless quantity α which is an odd function of the Hall angle with $|\alpha| < 1$:

$$I_1 = (y_0 + y_1 + y_2)V_1 - [\frac{1}{2}(1 - \alpha)y_0 + y_2]V_2, \quad (1)$$

$$I_2 = -[\frac{1}{2}(1 + \alpha)y_0 + y_2]V_1 + (y_0 + y_2 + y_3)V_2. \quad (2)$$

The conductances y_1 , y_2 , and y_3 may correspond to negative resistance elements. For example, if y_1 , y_2 , and y_3 have the values

$$y_1 = y_3 = -(1 + \alpha)y_0/2, \quad (3)$$

$$y_2 = (\alpha - 1)y_0/2, \quad (4)$$

then Eqs. (1) and (2) reduce to

$$I_1 = 0 \text{ and } I_2 = \alpha y_0 V_1. \quad (5)$$

This corresponds to an ideal pentode for $\alpha > 0$ and to such a pentode with voltage reversing transformer for $\alpha < 0$. Thus the circuit can simulate conventional amplifiers and in addition produce new types of devices.

Values of α as high as 0.2 can be obtained in *n*-type germanium at room temperature at fields of 17 500 oersteds. Similar reasoning to that discussed here applies also to the four-terminal Hall effect plate or balanced gyrator.⁵

A simple test⁶ of this principle was made at low frequencies by putting two gas diodes with negative resistance characteristics on either side of the balanced gyrator of reference 3. With this arrangement a gain of 6 db was obtained in one direction, and a loss of 46 db in the other. By more careful balancing of the negative resistances with the input and output resistances of the gyrator, higher gains are possible without instability.

¹ A guide to one method of designing such semiconductor devices is furnished by the work of F. B. Llewellyn on transit time vacuum-tube diodes: *Bell System Tech. J.* **13**, 59-101 (1934); **15**, 573-586 (1936). Methods of extending this approach to semiconductors have been indicated by W. Shockley, U. S. Patent 2,623,102 (Junction Transistor). Another physical effect considered by one of us (W.S.) in unpublished work is the negative differential mobility to be expected for holes in very high electric fields. Interest in this predicted effect was the provoking cause of the research on high field mobilities, see E. J. Ryder and W. Shockley, *Phys. Rev.* **81**, 139 (1951) and E. J. Ryder, *Phys. Rev.* **90**, 766-769 (1953). The theory of this effect has been independently discovered by H. Krömer, *Z. Physik* **134**, 435 (1953), who calls it the "Staueffect" but does not consider its utilization as a power source.

² Passive elements can have the desired directionality, i.e., lead to unsymmetrical current-voltage matrices, only in the presence of magnetic fields. For a proof see H. B. G. Casimir, *Revs. Modern Phys.* **17**, 343-350 (1945).

³ Mason, Hewitt, and Wick, *J. Appl. Phys.* **24**, 166-175 (1953). The fact that transmission through a crystal is nonreciprocal in the presence of a magnetic field was first pointed out by E. M. McMillan, *J. Acoust. Soc. Am.* **19**, 922 (1947).

⁴ C. L. Hogan, *Bell System Tech. J.* **31**, 1-32 (1952).

⁵ This test was made by W. H. Hewitt.