





(43) **Pub. Date:** **Oct. 24, 2013**








FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9





FIG. 11




FIG. 12




FIG. 13







FIG. 14










FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31




FIG. 32




FIG. 33




FIG. 34




FIG. 35






FIG. 36








FIG. 39A




FIG. 39B




FIG. 39C




FIG. 39D

METHODS AND SYSTEMS FOR TREATMENT OF ACUTE ISCHEMIC STROKE

REFERENCE TO PRIORITY DOCUMENTS

[0001] This application is a continuation-in-part of U.S. patent application Ser. No. 13/566,451, filed Aug. 3, 2012, titled “METHODS AND SYSTEMS FOR TREATMENT OF ACUTE ISCHEMIC STROKE;” which in turn claims priority to U.S. Provisional Patent Application Ser. No. 61/579,581, filed Dec. 22, 2011, titled “METHODS AND SYSTEMS FOR TREATMENT OF ACUTE ISCHEMIC STROKE;” U.S. Provisional Patent Application Ser. No. 61/547,597, filed Oct. 14, 2011, titled “METHODS AND SYSTEMS FOR TREATMENT OF ACUTE ISCHEMIC STROKE;” U.S. Provisional Patent Application Ser. No. 61/543,019, filed Oct. 4, 2011, titled “METHODS AND SYSTEMS FOR TREATMENT OF ACUTE ISCHEMIC STROKE;” and U.S. Provisional Patent Application Ser. No. 61/515,736, filed Aug. 5, 2011, titled “METHODS AND SYSTEMS FOR TREATMENT OF ACUTE ISCHEMIC STROKE.” Priority to the aforementioned applications is hereby claimed, the contents of which are incorporated herein in their entirety.

BACKGROUND

[0002] The present disclosure relates generally to medical methods and devices for the treatment of acute ischemic stroke. More particularly, the present disclosure relates to methods and systems for transcervical access of the cerebral arterial vasculature and treatment of cerebral occlusions.

[0003] Acute ischemic stroke is the sudden blockage of adequate blood flow to a section of the brain, usually caused by thrombus or other emboli lodging or forming in one of the blood vessels supplying the brain. If this blockage is not quickly resolved, the ischemia may lead to permanent neurologic deficit or death. The timeframe for effective treatment of stroke is within 3 hours for intravenous (IV) thrombolytic therapy and 6 hours for site-directed intra-arterial thrombolytic therapy or interventional recanalization of a blocked cerebral artery. Reperfusion of the ischemic brain after this time period has no overall benefit to the patient, and may in fact cause harm due to the increased risk of intracranial hemorrhage from fibrinolytic use. Even within this time period, there is strong evidence that the shorter the time period between onset of symptoms and treatment, the better the results. Unfortunately, the ability to recognize symptoms, deliver patients to stroke treatment sites, and finally to treat these patients within this timeframe is rare. Despite treatment advances, stroke remains the third leading cause of death in the United States.

[0004] Endovascular treatment of acute stroke is comprised of either the intra-arterial administration of thrombolytic drugs such as recombinant tissue plasminogen activator (rtPA), or mechanical removal of the blockage, or often a combination of the two. As mentioned above, these interventional treatments must occur within hours of the onset of symptoms. Both intra-arterial (IA) thrombolytic therapy and interventional thrombectomy involve accessing the blocked cerebral artery. Like IV thrombolytic therapy, IA thrombolytic therapy has the limitation in that it may take several hours of infusion to effectively dissolve the clot.

[0005] Mechanical therapies have involved capturing and removing the clot, dissolving the clot, disrupting and suction-

ing the clot, and/or creating a flow channel through the clot. One of the first mechanical devices developed for stroke treatment is the MERCI Retriever System (Concentric Medical, Redwood City, Calif.). A balloon-tipped guide catheter is used to access the internal carotid artery (ICA) from the femoral artery. A microcatheter is placed through the guide catheter and used to deliver the coil-tipped retriever across the clot and is then pulled back to deploy the retriever around the clot. The microcatheter and retriever are then pulled back, with the goal of pulling the clot, into the balloon guide catheter while the balloon is inflated and a syringe is connected to the balloon guide catheter to aspirate the guide catheter during clot retrieval. This device has had initially positive results as compared to thrombolytic therapy alone.

[0006] Other thrombectomy devices utilize expandable cages, baskets, or snares to capture and retrieve clot. A series of devices using active laser or ultrasound energy to break up the clot have also been utilized. Other active energy devices have been used in conjunction with intra-arterial thrombolytic infusion to accelerate the dissolution of the thrombus. Many of these devices are used in conjunction with aspiration to aid in the removal of the clot and reduce the risk of emboli. Frank suctioning of the clot has also been used with single-lumen catheters and syringes or aspiration pumps, with or without adjunct disruption of the clot. Devices which apply powered fluid vortices in combination with suction have been utilized to improve the efficacy of this method of thrombectomy. Finally, balloons, stents and temporary stents have been used to create a patent lumen through the clot when clot removal or dissolution was not possible. Temporary stents, sometimes referred to as stentriever or revascularization devices, may also be utilized to remove or retrieve clot as well as restore flow to the vessel.

Some Exemplary Issues with Current Technology

[0007] Interventions in the cerebral vasculature often have special access challenges. Most neurointerventional procedures use a transfemoral access to the carotid or vertebral artery and thence to the target cerebral artery. However, this access route is often tortuous and may contain stenosis plaque material in the aortic arch and carotid and brachiocephalic vessel origins, presenting a risk of embolic complications during the access portion of the procedure. In addition, the cerebral vessels are usually more delicate and prone to perforation than coronary or other peripheral vasculature. In recent years, interventional devices such as wires, guide catheters, stents and balloon catheters, have all been scaled down and been made more flexible to better perform in the neurovascular anatomy. However, many neurointerventional procedures remain either more difficult or impossible because of device access challenges. In the setting of acute ischemic stroke where “time is brain,” these extra difficulties have a significant clinical impact.

[0008] Another challenge of neurointerventions is the risk of cerebral emboli. During the effort to remove or dissolve clot blockages in the cerebral artery, there is a significant risk of thrombus fragmentation creating embolic particles which can migrate downstream and compromise cerebral perfusion, leading to neurologic events. In carotid artery stenting procedures CAS, embolic protection devices and systems are commonly used to reduce the risk of embolic material from entering the cerebral vasculature. The types of devices include intravascular filters, and reverse flow or static flow systems. Unfortunately, because of the delicate anatomy and access

challenges as well as the need for rapid intervention, these embolic protection systems are not used in interventional treatment of acute ischemic stroke. Some of the current mechanical clot retrieval procedures use aspiration as a means to reduce the risk of emboli and facilitate the removal of the clot. For example, the MERCI Retrieval System recommends attaching a large syringe to the guide catheter, and then blocking the proximal artery and aspirating the guide catheter during pull back of the clot into the guide. However, this step requires a second operator, may require an interruption of aspiration if the syringe needs to be emptied and reattached, and does not control the rate or timing of aspiration. This control may be important in cases where there is some question of patient tolerance to reverse flow. Furthermore, there is no protection against embolic debris during the initial crossing of the clot with the microcatheter and deployment of the retrieval device. Aspiration systems such as the Penumbra System utilize catheters which aspirate at the face of the clot while a separate component is used to mechanically break up the clot. This system is limited in the level of aspiration possible with current catheter designs, and in some cases by the ability to bring larger catheters to the location of the clot.

[0009] One severe drawback to current acute stroke interventions is the amount of time required to restore blood perfusion to the brain, which can be broken down to time required to access to the blocked cerebral artery, and time required to restore flow through the occlusion. Restoration of flow, either through thrombolytic therapy, mechanical thrombectomy, or other means, often takes hours during which time brain tissue is deprived of adequate oxygen. During this period, there is a risk of permanent injury to the brain tissue. Means to shorten the procedure time, and/or to provide oxygen to the brain tissue during the procedure, would reduce this risk.

SUMMARY

[0010] Disclosed are methods and devices that enable safe, rapid and relatively short and straight transcervical access to the cerebral arteries to treat acute ischemic stroke. The methods and devices include distal catheters and devices to remove the occlusion. Methods and devices are also included to provide aspiration and passive flow reversal for the purpose of facilitating removal of the occlusion as well as minimizing distal emboli. The system offers the user a degree of flow control so as to address the specific hemodynamic requirements of the cerebral vasculature. The disclosed methods and devices also include methods and devices to protect the cerebral penumbra during the procedure to minimize injury to brain. In addition, the disclosed methods and devices provide a way to securely close the access site in the carotid artery to avoid the potentially devastating consequences of a transcervical hematoma.

[0011] In one aspect, there is disclosed a device for accessing an artery, comprising: an arterial access device having an internal lumen and a proximal port, the arterial access device sized and shaped to be inserted directly into an arterial access site in the common carotid artery such that the lumen provides a passageway for an interventional device to be inserted via the proximal port into the carotid artery, the arterial access device having a distal portion that is configured to be inserted into an arterial pathway through the access site, and a proximal portion configured to extend outward from the access site when the distal portion is in the arterial pathway, and wherein

the proximal portion has a length configured to provide a distance of between about 30 cm and 50 cm between the arterial access site and the proximal port.

[0012] In another aspect, there is disclosed a device for treating an occlusion in a cerebral artery of a patient, comprising distal catheter sized and shaped such that the distal catheter can be passed through a access site in a carotid artery to an occlusion in a cerebral artery via an arterial pathway, the catheter being configured to be passed through one or more bends in the artery without kinking, wherein at least one bend is greater than 45 degrees and is located within a predetermined distance from the arterial access site.

[0013] In another aspect, there is disclosed a device for accessing an artery, comprising an arterial access device having an internal lumen and a proximal port, the arterial access device sized and shaped to be inserted directly into an arterial access site in the common carotid artery such that the lumen provides a passageway for an interventional device to be inserted into the artery, the arterial access device having a distal portion that is configured to be inserted into the artery, and a proximal portion configured to extend outward from the arteriotomy when the distal portion is in the arterial pathway, wherein the distal portion has a section of increased flexibility, the section of increased flexibility forming at least 10% of the length of the entire distal portion.

[0014] In another aspect, there is disclosed a device for treating an occlusion in a cerebral artery of a patient, comprising distal catheter sized and shaped such that the distal catheter can be passed through an arteriotomy to an occlusion in a cerebral artery via an arterial pathway, wherein the occlusion in the cerebral artery is located a distance X from the location of the arteriotomy, and wherein the distal catheter has a working length less than two times the distance X.

[0015] Other features and advantages should be apparent from the following description of various embodiments, which illustrate, by way of example, the principles of the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

[0016] FIG. 1 illustrates an exemplary embodiment of a system of devices for transcervical access and treatment of acute ischemic stroke showing a balloon-tipped arterial access device inserted directly into the carotid artery, a distal catheter, a thrombectomy device.

[0017] FIG. 2 illustrates an alternate embodiment wherein the arterial access device is inserted into the carotid artery through a separate introducer sheath.

[0018] FIG. 3 illustrates an embodiment in which the introducer sheath has an occlusion balloon and a connection to a flow line.

[0019] FIG. 4 illustrates an alternate embodiment of the arterial access device which has two occlusion balloons and an opening between the two balloons.

[0020] FIG. 5 illustrates an alternate embodiment of the arterial access device which includes two telescoping sections.

[0021] FIG. 6 illustrates an embodiment of a balloon-tipped anchor device.

[0022] FIG. 7 illustrates an embodiment of a mechanically expandable-tipped anchor guide wire.

[0023] FIG. 8 illustrates an embodiment of a distal catheter with a tapered co-axial inner member.

[0024] FIG. 9 illustrates another embodiment of a distal catheter with a tapered co-axial inner member.

[0025] FIG. 10 illustrates an embodiment of a combined arterial access device and distal catheter.

[0026] FIGS. 11 and 12 illustrate embodiments of distal catheters having second lumens to maintain guide wire access.

[0027] FIG. 13 illustrates an embodiment of a distal catheter and arterial access device configured to be telescoping.

[0028] FIG. 14 illustrates an alternate embodiment of the system with the addition of an occlusion device.

[0029] FIG. 15 illustrates an embodiment of the system with the addition of an aspiration source, filter and one-way check valve attached to the arterial access device.

[0030] FIG. 16 illustrates an embodiment of the system with the addition of an aspiration source, filter and one-way check valve attached to both the arterial access device and distal catheter.

[0031] FIG. 17 illustrates an embodiment of the system with the addition of a single aspiration source, filter and one-way check valve attached to both the arterial access device and distal catheter, and a valve connecting the two devices to the aspiration source.

[0032] FIG. 18 illustrates an embodiment of the system with the addition of a flow controller attached to both the arterial access device and distal catheter.

[0033] FIG. 19 illustrates an embodiment of an aspiration source.

[0034] FIG. 20 illustrates an alternate embodiment of an aspiration source.

[0035] FIG. 21 illustrates an embodiment of the system with the addition of a flow reverse circuit that includes a venous return site.

[0036] FIGS. 22-29 illustrate embodiments of thrombectomy devices.

[0037] FIG. 30 illustrates an embodiment of a dual-lumen microcatheter.

[0038] FIG. 31 illustrates an embodiment of a distal perfusion catheter.

[0039] FIG. 32 illustrates an alternate embodiment of a distal perfusion catheter.

[0040] FIGS. 33-36 illustrate different embodiments of distal perfusion catheters with an occlusion balloon.

[0041] FIG. 37 illustrates another embodiment of a distal perfusion catheter.

[0042] FIG. 38 illustrates an embodiment of the system with the addition of a distal balloon catheter configured to perfuse proximal to the balloon.

[0043] FIGS. 39A-39D illustrates steps in usage of a distal balloon catheter configured to perfuse distal and/or proximal to the balloon.

DETAILED DESCRIPTION

[0044] Described herein are methods and devices that enable safe, rapid and relatively short and straight transcervical access to the carotid arteries and cerebral vasculature for the introduction of interventional devices for treating ischemic stroke. Transcervical access provides a short length and non-tortuous pathway from the vascular access point to the target cerebral vascular treatment site, thereby easing the time and difficulty of the procedure, compared for example to a transfemoral approach. Additionally, this access route reduces the risk of emboli generation from navigation of diseased, angulated, or tortuous aortic arch or carotid artery anatomy.

[0045] FIG. 1 shows a system of devices for accessing the common carotid artery CCA via a transcervical approach and for delivering devices to the cerebral vasculature. The system includes an arterial access device **2010** (sometimes referred to as an arterial access sheath), such as a sheath, having an internal lumen and a port **2015**. The arterial access device **2010** is sized and shaped to be inserted into the common carotid artery via a transcervical incision or puncture and deployed into a position that provides access to the cerebral vasculature, for example the common or internal carotid artery. The port **2015** provides access to the arterial access device's internal lumen, which is configured for introducing additional devices into the cerebral vasculature via the arterial access device **2010**.

[0046] In an embodiment, transcervical access to the common carotid artery directly with the arterial access device **2010** is achieved percutaneously via an incision or puncture in the skin. In an alternate embodiment, the arterial access device **2010** accesses the common carotid artery CCA via a direct surgical cut down to the carotid artery. In another embodiment, the arterial access device provides access to the basilar artery BA or posterior cerebral arteries PCA via a cut down incision to in the vertebral artery or a percutaneous puncture of the vertebral artery for access to occlusions in the posterior cerebral vasculature such as the posterior cerebral artery or basilar artery. The arterial access device may include an occlusion balloon, to block antegrade flow. For entry into the common carotid artery, the arterial access device is inserted into an opening directly in the common carotid artery, the opening being positioned above the patient's clavicle and below a bifurcation location where the patient's common carotid artery bifurcates into an internal carotid artery and external carotid artery. For example, the opening may be located at distance of around 5 cm to 7 cm below a bifurcation location where the patient's common carotid artery bifurcates into an internal carotid artery and external carotid artery.

[0047] The arterial access device (or any of the devices described herein) is sized to facilitate access to the arterial occlusion **10** via an access site in the common carotid artery. In this regard, the length of the arterial access device can be defined relative to the location of the arteriotomy and where the arterial access device enters the arteriotomy. An embodiment of the arterial access device has a distal length that is no greater than 20 cm from a location where the arterial access device enters the arteriotomy to the distal end of the arterial access device. In another embodiment, the proximal length of the arterial access device from a location where the arterial access device enters the arteriotomy to a proximal end of the arterial access device is at least 30 cm.

[0048] The system may also include one or more distal catheters **2030** to provide distal access and localized aspiration at a location distal of the distal-most end of the arterial access device **2010**. A single distal catheter may be adequate for accessing and treating the occlusion or occlusions. A second, smaller diameter distal catheter may be inserted through the first catheter or exchanged for the first catheter if more distal access is desired and not possible with the initial distal catheter. In an embodiment, the distal catheter **2030** is configured to be inserted into the internal lumen of the arterial access device **2010** via the port **2015**. The distal catheter **2030** may use a previously placed guide wire, microcatheter, or other device acting as a guide rail and support means to facilitate placement near the site of the occlusion. The distal

catheter may also utilize a dilator element to facilitate placement through the vasculature over a guidewire. Once the distal catheter is positioned at or near the target site, the dilator may be removed. The distal catheter **2030** may then be used to apply aspiration to the occlusion. The catheter **2030** or dilator may also be used to deliver additional catheters and/or interventional devices to the site of the occlusion.

[0049] The methods and devices also include devices for active aspiration as well as passive retrograde flow to facilitate removal of the occlusion and/or minimize distal emboli. The system offers the user a degree of blood flow control so as to address the specific hemodynamic requirements of the cerebral vasculature. The system may include a flow controller, which allows the user to control the timing and mode of aspiration from one or more of the devices.

[0050] With reference still to FIG. 1, a thrombectomy device **4100** such as a stentriever or a coil retriever that has been configured for transcervical access may be deployed through the arterial access device to the site of the thrombotic blockage. The thrombectomy device **4100** is inserted through the arterial access device **2010** and deployed across the occlusion in the cerebral vessel via a microcatheter. If desired, a distal catheter **2030** may be used to facilitate navigation of the thrombectomy device to the site of the occluded vessel, and/or to provide aspiration at the site of the occlusion during retrieval of the clot by the thrombectomy device. The clot is retrieved by pulling back on the thrombectomy device and microcatheter in tandem into the distal catheter **2030**, if used, and thence into the arterial access device **2010**.

[0051] The disclosed methods and devices also include devices to protect the cerebral penumbra during the procedure to minimize injury to the brain. A distal perfusion device may be used during the procedure to provide perfusion to the brain beyond the site of the occlusion, thereby reducing the injury to the brain from lack of blood. These perfusion devices may also provide means to reduce the forward blood pressure on the occlusion in the vessel and thus assist in removing the occlusion with either aspiration, mechanical means, or both.

[0052] In addition, the disclosed methods and devices provide means to securely close the access site to the cerebral arteries to avoid the potentially devastating consequences of a transcervical hematoma. The present disclosure provides additional methods and devices.

EXEMPLARY EMBODIMENTS ARTERIAL ACCESS DEVICE

[0053] The arterial access device **2010** as shown in FIG. 1 is configured to be directly inserted into the common carotid artery CCA without use of a separate introducer sheath. In this configuration, the entry or distal tip of the device is tapered and includes a tapered dilator so as to allow smooth introduction of the device over a guide wire into the artery. The device **2010** may include an occlusion balloon **2020** which is configured to occlude the artery when inflated. In an alternate embodiment, the arterial access device **2010** does not include an occlusion balloon. The arterial access device also includes a proximal adaptor. This proximal adaptor includes a proximal port **2015** with a hemostasis valve, to allow introduction of devices while preventing or minimizing blood loss during the procedure. In an embodiment, this valve is a static seal-type passive valve. In an alternate embodiment, this valve is an adjustable-opening valve such as a Tuohy-Borst or rotating hemostasis valve (RHV). The hemostasis valve may be integral to the proximal adaptor, or may be

attached separately to the proximal end of the adaptor via a Luer connection. The arterial access device **2010** may also include a connection to a flow line **2025** (or shunt) which may be connected to means for passive or active reverse flow. The flow line **2025** has an internal lumen that communicates with an internal lumen of the arterial access device **2010** for shunting blood from the arterial access device. In an embodiment, the flow line **2025** is a side arm or Y-arm **2027** that is attached to and extends from the arterial access device **2010** at a location between the distal and proximal ends of the arterial access device **2010**. As shown in FIG. 1, the flow line **2025** is located distal of the location where devices enter the proximal port **2015** of the arterial access device. In an alternate embodiment, the flow line **2025** is attached to the Y-arm of a separately attached Tuohy Borst valve.

[0054] In an embodiment, the arterial access device having an internal lumen and a proximal port, the arterial access device sized and shaped to be inserted directly into an arterial access site in the common carotid artery such that the lumen provides a passageway for an interventional device to be inserted via the proximal port into the carotid artery. The arterial access device has a distal portion that is configured to be inserted into an arterial pathway through the access site, and a proximal portion configured to extend outward from the access site when the distal portion is in the arterial pathway. The proximal portion may have a length configured to provide a distance of between about 30 cm and 50 cm between the arterial access site and the proximal port.

[0055] The arterial access device **2010** may also include a lumen for balloon inflation. This lumen fluidly connects the balloon to a second Y-arm on the proximal adaptor. This Y-arm is attached to a tubing **2028** which terminates in a one-way stopcock **2029**. An inflation device such as a syringe may be attached to the stopcock **2029** to inflate the balloon when vascular occlusion is desired.

[0056] In an embodiment as shown in FIG. 2, the arterial access device is a guide catheter **2105** which is inserted through the proximal hemostasis valve **2012** of a separate introducer sheath **2110** into the CCA. The arterial access device also includes a proximal adaptor. This proximal adaptor includes a proximal port **2015** with a hemostasis valve, to allow introduction of devices while preventing or minimizing blood loss during the procedure. The guide catheter **2105** may include a lumen for balloon inflation. This lumen is attached to a Y-arm in the proximal adaptor, which is connected to a tubing **2128**. The tubing **2128** terminates in a one-way stopcock **2129** for connection to a balloon inflation device. The guide catheter **2105** may include a second Y-arm **2107** that communicates with a flow line **2125**. Introduction through the separate sheath **2110** allows removal of the guide catheter **2105** for flushing outside the patient and reinserting, or for exchanging the guide catheter **2105** with another guide catheter without removing the introducer sheath **2110**, thus maintaining access to the artery via the transcervical incision. This configuration also allows repositioning of the occlusion balloon **2020** during the procedure without disturbing the arterial insertion site. The embodiment of FIG. 2 also allows removal of the arterial access device **2105** and then insertion of a vessel closure device through the introducer sheath **2110** at the conclusion of the procedure.

[0057] In a variation of this embodiment, as shown in FIG. 3, the introducer sheath **2110** includes an occlusion balloon **2205** and an inflation line and tubing **2318**. The introducer sheath **2110** may also include a connection to a flow line **2310**

for passive or active reverse flow, wherein passive or active reverse flow may be configured as described in U.S. patent application Ser. No. 12/176,250 and U.S. patent application Ser. No. 12/834,869, which are incorporated herein by reference. This embodiment may be useful if the patient had a carotid stenosis in addition to a cerebral artery blockage, and the user wished to treat the carotid stenosis under static or reverse flow conditions as described in the reference patent application either prior or after treating the cerebral artery blockage.

[0058] In yet another embodiment, as shown in FIG. 4, the arterial access device is a device **2105a** with two occlusion balloons **2405** and **2410** and a side opening **2415** positioned between the two balloons. The distal occlusion balloon **2410** is located at or near the distal end of the arterial access device **2105a**, and the proximal occlusion balloon **2405** is located between the distal end and the proximal end of the working portion of the arterial access device. The distal occlusion balloon **2410** is sized and shaped to be placed in the external carotid artery ECA and the proximal occlusion balloon **2405** is sized and shaped to be placed in the common carotid artery CCA. Such a dual balloon configuration stops flow into the internal carotid artery ICA from both the CCA and the ECA, which has an effect functionally the same as an occlusion balloon positioned in the ICA without inserting a device into the ICA. This may be advantageous if the ICA were diseased, whereby access may cause emboli to dislodge and create embolic complications, or the access to the ICA were severely tortuous and difficult to achieve, or both. The side opening **2415** in the working section of the arterial access device **2105** permits a device **2416** to be introduced via the arterial access device **2105a** and inserted into the ICA via the side opening **2415** while flow is stopped or reversed, to reduce or eliminate the risk of distal emboli. This device **2416** may then be advanced to the location of the cerebral artery occlusion to treat the occlusion.

[0059] In yet another embodiment, as shown in FIG. 5 the arterial access device is a multi-part (such as two-part) telescoping system **2105b**. The first part is an introducer sheath **2110b** which is configured to be inserted transcervically into the CCA. The second part is a distal extension **2110c** which is inserted through the proximal end of the introducer sheath **2110b** and which extends the reach of the sheath into the ICA. The distal end of the sheath **2110b** and the proximal end of the extension **2110c** form a lap junction **2113** when the extension is fully inserted, such that there is a continuous lumen through the two devices. The lap junction may be variable length, such that there is some variability in the length of the combined telescoping system **2105b**. The distal extension **2110c** includes a tether **2111** which allows placement and retrieval of the distal extension **2110c** through the sheath **2110b**. In an embodiment, the distal extension includes an occlusion balloon. In this embodiment the tether includes a lumen for inflation of the balloon. This tether can be connected on the proximal end to a balloon inflation device. This configuration provides the advantages of the two-part system shown in FIG. 2, without compromising the luminal area.

[0060] In an embodiment, the working portion of the arterial access device which enters the artery is constructed in two or more layers, including for example a first layer and a second layer. An inner liner is constructed from a low friction polymer such as PTFE (polytetrafluoroethylene) or FEP (fluorinated ethylene propylene) to provide a smooth surface for the advancement of devices through the inner lumen. An outer jacket material providing mechanical integrity to the liner

may be constructed from materials such as Pebax, polyethylene, nylon, or the like. A third layer may consist of a reinforcement between the liner and the jacket. The purpose of the reinforcement layer is to prevent flattening or kinking of the inner lumen as the device navigates through bends in the vasculature, and provide unimpeded means for device access as well as aspiration or reverse flow. The reinforcement may be made from metal such as stainless steel, Nitinol, or the like, or stiff polymer such as PEEK. The structure may be a coil or braid, or tubing which has been laser-cut or machine-cut so as to be flexible. In addition, the device may have a radiopaque marker at the distal tip to facilitate placement of the device using fluoroscopy. In an embodiment, the working portion of the device may have a hydrophilic coating to improve the ease of advancement of the device through the vasculature.

[0061] The arterial access device may be configured so that it can be passed through or navigate bends in the artery without kinking. In an embodiment, the arterial access device can be and is passed through bends of less than or equal to 45 degrees wherein the bends are located within 5 cm, 10 cm, or 15 cm of the arteriotomy measured through the artery. The arterial access device or a corresponding interventional device is configured such that at least a portion of the length of the device has a distal section that is more flexible than a proximal section of the device. For example, the distal section may be at least 10% of the length of the working portion of the catheter wherein the working portion is the portion that is configured to be inserted into an artery. In other embodiments, the distal section is at least 20% or at least 30% of the length of the working portion of the catheter.

[0062] In an embodiment, the working length of the arterial access device is of a length configured to occlude the proximal internal carotid artery when inserted from the CCA, for example 10-15 cm. In an alternate embodiment, the working length of the arterial access device is of a length suitable to be used with a vessel closure device, for example 11 cm or less. In another embodiment the device is of a length configured to occlude the distal cervical internal carotid artery (ICA) when inserted from the CCA, for example 15-25 cm. In yet another embodiment, the arterial access device is of a length configured to occlude the petrous, cavernous, or terminal portion of the ICA when inserted from the CCA, for example 20-35 cm. In this embodiment, the distal-most portion (which may have a length of about 3 to about 6 cm) of the arterial access device may be configured to be more flexible to accommodate the curvature in the petrous portion of the ICA. This additional flexibility may be achieved by using a lower durometer outer jacket material in this section. Alternately, the wall thickness of the jacket material may be reduced, and/or the density of the reinforcement layer may be varied to increase the flexibility. For example the pitch of the coil or braid may be stretched out, or the cut pattern in the tubing may be varied to be more flexible. The distal most portion of the arterial access device may also be tapered or stepped down to a smaller diameter.

[0063] The arterial access device as described above has a working length which is considerably shorter than access devices which are placed from an access location in the femoral artery. The distance from the femoral artery to the CCA is about 60-80 cm, thus devices which utilize a CCA access site may be shorter by approximately this amount. Comparable devices which are designed for femoral arterial access are typically 80-95 cm in length for devices to be deployed in the cervical ICA (e.g. the Balloon Guide, Concentric, Inc.) or

95-105 cm in length designed to access the petrous ICA (e.g. the Neuron 6F Guide, Penumbra, Inc.) The shorter lengths of access devices disclosed herein reduces the resistance to flow through the lumen of these devices and increases the rate at which aspiration may occur. In an example embodiment, the arterial access device has a length of about 10 cm to about 40 cm. In an embodiment, the length of the arterial access device is about 10.5 cm and the guide catheter has a length of about 32 cm.

[0064] The arterial access device may also include a proximal extension to allow the user to insert devices into the proximal port of the proximal extension and from there into the lumen of the arterial access device while minimizing exposure of the user's hands to radiation. In an embodiment, the proximal port is a hemostasis valve. In an embodiment, the proximal extension is configured such that the length between the proximal port and the arterial access site is between 30 and 50 cm. In an embodiment, the proximal extension is removable from the arterial access device. An example of a proximal extension design is described in co-pending U.S. patent application Ser. No. 12/540,341, filed Aug. 12, 2009, which is incorporated herein by reference. U.S. patent application Ser. No. 12/633,730, U.S. patent application Ser. No. 12/645,179, and U.S. patent application Ser. No. 12/966,948 are also incorporated by reference herein.

DISTAL CATHETER EXEMPLARY EMBODIMENTS

[0065] With reference again to FIG. 1, the distal catheter **2030** is configured to be inserted through the arterial access device distal to the ICA and cerebral vessels, to a location as far as the thrombotic occlusion **10**. The distal catheter **2030** has a length longer than the length of the arterial access device such that the distal catheter's distal end can protrude from the distal opening of the arterial access device by about 15-30 cm. The distal catheter is also more flexible than the arterial access device, due to the anatomy of the distal vasculature. A proximal port **2035** with a hemostasis valve may be situated on the proximal end of distal catheter **2030**, to allow introduction of devices such as a microcatheter, guide wire, or thrombectomy device while preventing or minimizing blood loss during the procedure. In an embodiment, this valve is an adjustable-opening valve such as a Tuohy-Borst or rotating hemostasis valve (RHV). The hemostasis valve may be integral to the catheter proximal adaptor, or may be attached separately to the proximal end of the catheter via a Luer connection.

[0066] As with the arterial access device, the distal catheter **2030** may also be made with a two or more layer construction as described above. The distal catheter may be configured according to the description of the working portion of the arterial access device described above. In addition, the distal catheter may have a radiopaque marker at the distal tip to facilitate placement of the device using fluoroscopy. In an embodiment, the working portion of the device may have a hydrophilic coating to improve the ease of advancement of the device through the vasculature. In an embodiment, the distal-most portion is constructed to be more flexible than the proximal portion, by means as described above for the arterial access device.

[0067] The distal catheter **2030** has a working length (which is the length or portion of a device that is specifically sized and shaped to be inserted into the artery and passed

through an arterial pathway (through the artery) to the arterial occlusion or location of treatment) configured to reach the terminal ICA and cerebral vessels when placed through the arterial access device **2010**. In an embodiment, the working length is 40 to 80 cm. A distal catheter with this length would allow a much higher rate of aspiration than catheters designed for transfemoral access. For example, a distal catheter configured for transfemoral access to the cerebral circulation has a length of 115 cm and an inner diameter of 0.057" (the DAC 057 Catheter, Concentric Medical, Mountain View, Calif.) has a flow rate of 113 ml/min with fluid of 3.2 centipoise (cp, equivalent to blood) when connected to an aspiration pump set at a vacuum of 22 inHg. A distal catheter **2030** configured for transcervical access into the CCA to the cerebral circulation (such as described herein) may have a length of 50 cm, with a similar inner diameter. As flow resistance is linear with length of the tube according to Poiseuille's equation for flow through a tube, the catheter **2030** would have a flow rate of more than twice the transfemoral catheter, specifically a flow rate of 260 ml/min with 3.2 cp fluid when connected to an aspiration pump set at 22 inHg, or, about 2.3 times the aspiration rate of a transfemoral system. A similar increase in aspiration rate would also be seen with manual syringe aspiration or other aspiration source. In addition, because the transcervical access site is much closer than the transfemoral site with many less turns, there is less need for as high a degree of torque strength in the walls of the catheter, thus a transcervically placed catheter **2030** may be constructed with thinner wall construction, with equal or better ability to be placed in the target anatomy. A thinner wall would result in large inner lumen, yielding even more advantage in flow rate. As the flow resistance is proportional to diameter to the fourth power, even small improvements in luminal area result in larger advances in increased flow rate. In an embodiment, a distal catheter may be sized to reach the terminal ICA only (and not the more distal cerebral arteries). In this embodiment, the distal catheter may have an inner diameter of 0.070" to 0.095" and a length of 25-50 cm. In another embodiment, the distal catheter may be sized to reach the more distal cerebral arteries, with an inner diameter of 0.035" to 0.060" and a length of 40-80 cm.

[0068] The distal catheter is sized to facilitate access to the arterial occlusion **10** via an access site in the carotid artery. In an embodiment, the distal catheter has a working length of less than 70 cm, less than 60 cm, or less than 50 cm. Alternately, the size of distal catheter can be defined relative to the location of the access site and the arterial occlusion **10**. In an embodiment, the distal catheter is configured to be introduced into the artery at a location in the artery that is less than 40 cm, less than 30 cm, or less than 20 cm from the location of the occlusion **10** as measured through the arterial pathway. The distance may further be defined by a ratio of working length to the distance between the location where the distal catheter enters the arteriotomy and the occlusion **10**. In an embodiment, this ratio is less than 2x.

[0069] As with the arterial access device, the distal catheter may have a variable stiffness shaft. The distal-most portion of the distal catheter may be configured to be more flexible to accommodate the curvature in the cerebral vessels without kinking. In an embodiment, the distal catheter is configured to pass through bends of less than or equal to 45 degrees wherein the bends are located within 5 cm, 10 cm, or 15 cm of the arteriotomy measured through the artery. The distal catheter or a corresponding interventional device is configured such

that at least a portion of the length of the device has a distal section that is more flexible than a proximal section of the device. This length may be from about 3 cm to about 6 cm. Alternately, the flexible distal section may be described as a portion of the overall catheter working portion. In an embodiment, the flexible distal section may be at least 10% of the length of the working portion of the catheter wherein the working portion is the portion that is configured to be inserted into an artery. In other embodiments, the distal section is at least 20% or at least 25% of the length of the working portion of the catheter. This additional flexibility may be achieved by using a lower durometer outer jacket material in this section. The shaft may have two or more increasingly stiff sections towards the more proximal section of the shaft, with the proximal most portion having the stiffest shaft section.

[0070] The distal catheter or interventional device may also be coated with a hydrophilic material. In an embodiment, at least 40% of the working length of the catheter is coated with a hydrophilic material. In other embodiments, at least 50% or at least 60% of the working length of the catheter is coated with a hydrophilic material.

[0071] In an embodiment, an occlusion balloon 2040 may be disposed on the distal catheter 2030 and can be used to occlude an artery such as to limit forward arterial flow or pressure, which would improve the conditions that permit aspiration as well as removal of the occlusion.

[0072] With reference still to FIG. 1, the distal catheter 2030 may also include a proximal adaptor with a Y-arm for a flow line 2045 (or shunt). The flow line 2045 has an internal lumen that communicates with an internal lumen of the distal catheter 2030. The proximal adaptor also includes a proximal hemostasis valve 2035 for the insertion of guidewires, microcatheters, or other catheters. In an embodiment, the proximal adaptor is permanently attached to the distal catheter 2030. In another embodiment, the proximal adaptor is a female Luer connector to which a separate Tuohy-Borst valve with a Y-arm can be attached.

[0073] In another embodiment, a distal catheter system includes an anchor device which is configured to be easily navigable through the vasculature to a location distal to the cerebral occlusion. When the anchor is deployed, it may be used as a rail and counter force to facilitate advancement of the distal catheter to the proximal face of the occlusion. An example as shown in FIG. 6 is a microcatheter 2505 with a distal balloon 2510. The microcatheter 2505 is placed over a guidewire 2515 through the occlusion 10 and then the distal balloon 2510 is inflated. Alternately, the microcatheter has an atraumatic guidewire tip built in and is advanced as a stand-alone device. The distal catheter 2030 can then use the shaft of the microcatheter 2505 as a rail to be advanced towards the occlusion 10, as is done in conventional techniques. However, because the balloon 2510 is inflated, the distal end of the microcatheter 2505 is anchored against the clot and/or the vessel wall and provides counter force to the advancing distal catheter 2030. Some of the force may be translated to the occlusion itself, and may help remove the clot. The guidewire 2515 remains in place during this maneuver, such that if the anchor (i.e., the balloon 2510) and distal catheter 2030 need to be re-advanced to attempt again to remove the occlusion 10, access is maintained across the occlusion with the guide wire 2515.

[0074] The atraumatic distal anchor can be a device other than a balloon. For example, other atraumatic distal anchors may include microcatheters with mechanically expandable-

tips such as a braid, coil, or molly-bolt construction. The expandable tip can be configured to be sufficiently soft and to provide sufficient force along a length of the microcatheter so as to reduce focal pressure against the vessel wall and minimize vessel wall injury.

[0075] Another variation of this embodiment as shown in FIG. 7 is a guidewire 2615 with an expandable tip 2620 such as a balloon or expandable cage or stent. The guidewire 2615 may be placed in the vasculature using a microcatheter and then deployed when the microcatheter is retracted. The expandable portion of the guidewire 2615 device may be formed from separate braided filaments or cut from a single hypotube and expand with a counterforce actuating member. For example the proximal end of the expandable tip may be attached to the distal end of a hollow hypotube, and the distal end attached to a wire which runs the length of the hypotube. When the wire is pulled back, the expandable tip is shortened in length and expanded in diameter. Pushing the wire forward would collapse the expandable tip.

[0076] A cause of difficulty in advancing larger size catheters is the mismatch between the catheter and the inner components. One technique for advancing the larger size catheters is called a tri-axial technique in which a smaller catheter, either a microcatheter or a smaller distal catheter, is placed between the large catheter and the guide wire. However, with current systems the smaller catheter has a diameter mismatch between either the larger catheter, the guide wire, or both, which creates a step in the system's leading edge as the system is advanced in the vasculature. This step may cause difficulty when navigating very curved vessels, especially at a location where there is a side-branch, for example the ophthalmic artery. In an embodiment, as shown in FIG. 8, the distal catheter 2030 is supplied with a tapered co-axial inner member 2652 that replaces the smaller catheter generally used. The inner member 2652 is sized and shaped to be inserted through the internal lumen of the distal catheter. The inner member 2652 has a tapered region with an outer diameter that forms a smooth transition between the inner diameter of the distal catheter 203 and the outer diameter of a guidewire 2515 or microcatheter that extends through an internal lumen of the inner member 2652. In an embodiment, the tapered dilator or inner member 2652, when positioned within the distal catheter, creates a smooth transition between the distal-most tip of the larger distal catheter 2030 and the outer diameter of a guide wire 2515 which may be in the range of 0.014" and 0.018" diameter for example. For example, the inner luminal diameter may be between 0.020" and 0.024". In another embodiment, the inner diameter is configured to accept a microcatheter with an outer diameter in the range of 0.030" to 0.040" or an 0.035" guide wire in the inner lumen, for example the inner luminal diameter may be 0.042" to 0.044".

[0077] In a variation of this embodiment, shown in FIG. 9, in addition to the tapered region, the inner member 2652 includes an extension formed of a uniform diameter or a single diameter, distal-most region 2653 that extends distally past the tapered portion of the inner member 2652. In this embodiment the distal region 2653 of the inner member 2652 may perform some or all of the functions that a microcatheter would do during a stroke interventional procedure, for example cross the occlusion to perform distal angiograms, inject intraarterial thrombolytic agents into the clot, or deliver mechanical thrombectomy devices such as coil retrievers or

stent retrievers. In this manner, a microcatheter would not need to be exchanged for the dilator for these steps to occur.

[0078] The material of the dilator (inner member **2652**) is flexible enough and the taper is long enough to create a smooth transition between the flexibility of the guide wire and the distal catheter. This configuration will facilitate advancement of the distal catheter through the curved anatomy and into the target cerebral vasculature. In an embodiment, the dilator is constructed to have variable stiffness, for example the distal most section is made from softer material, with increasingly harder materials towards the more proximal sections.

[0079] In an embodiment, distal end of the tapered dilator has a radiopaque marker such as a platinum/iridium band, a tungsten, platinum, or tantalum-impregnated polymer, or other radiopaque marker. In an embodiment, the tapered dilator is constructed with variable stiffness. For example, the distal segment of the dilator may be constructed with a softer material, with successively stiffer materials towards the proximal end. As shown in FIG. 1, the distal catheter **2030** can be its own catheter that is separate and removable from the arterial access device. In another embodiment, shown in FIG. 10, the distal catheter and the arterial access device are combined to be a single device **2710** with a continuous lumen extending through the length of the device. A proximal portion **2720** comprises the arterial access sheath and a distal portion **2730** functions as the distal catheter. An occlusion balloon **2715** is located between the distal and proximal portion. The distal portion **2730** is constructed to be more suited for navigating the cerebral vasculature. In particular, the distal portion **2730** is more flexible and tapered to a smaller diameter than the proximal portion **2720**.

[0080] In another embodiment, as shown in FIGS. 11 and 12, the distal catheter has a second lumen to maintain guide wire access to facilitate re-advancement or exchange of the distal catheter without recrossing the target anatomy. In an embodiment, shown in FIG. 11, the distal catheter has two lumens which terminate together at the distal tip: a main lumen and a second guidewire lumen. The termination may be such that a distal-facing surface is arranged at an angle (relative to the longitudinal axis of the catheter), to facilitate tracking of the catheter through the vasculature. In another embodiment, shown in FIG. 12, the second guidewire lumen is inside an extension **1247** that extends out past the termination of the main lumen. The extension **1247** is a distal-most region of the distal catheter that protrudes distally past an opening formed by the main lumen. The extension **1247** forms a shaft having a reduced outer diameter relative to the outer diameter of the distal catheter around the main lumen. The second lumen is smaller than the shaft of the main distal catheter, and may be positioned in or across an occlusion while the distal end of the main lumen is positioned on the proximal face of an occlusion. The distal end of the main lumen may be terminated at an angle as well, to facilitate tracking of the device.

[0081] In yet another embodiment, the distal catheter has an expandable tip portion. The expandable tip facilitates aspiration of an occlusion when an aspiration device is connected to the proximal portion of the distal catheter. The expandable tip portion may be constructed with a mechanical structure such as a braid or stent structure, which can open or close in a repeatable manner. The mechanism for opening the tip may be a pull-wire which shortens the expandable portion, or an outer retention sleeve which maintains the distal section in a

small diameter but when retracted allows the distal tip to expand. The distal section may be covered with a membrane such that when aspiration is applied, either with the tip expanded or not, a vacuum may be applied at the very tip of the catheter. The expandable tip allows the catheter to maintain a small profile during tracking of the catheter to the target anatomy, but then expands the distal luminal area for facilitated capture of occlusive material such as thrombus. The thrombus, once captured into the distal catheter, may be sucked all the way into the aspiration device, or alternately will be lodged in the lumen of the distal catheter where the catheter is no longer expanded, and at that point can be removed by retraction of the entire distal catheter.

[0082] In another embodiment, shown in FIG. 13, the distal catheter **2830** is a telescopic attachment to the distal portion of the arterial access device **2820**. The distal region of the arterial access device **2820** has one or more structures that telescopically extend in the distal direction along the longitudinal axis of the arterial access device. The structures may also be telescopically collapsed such that they do not extend past the distal end of the arterial access device. When the structures are telescopically expanded past the distal end of the arterial access device, the structures collectively form a continuous inner lumen. A tether element such as a wire **2835** may be connected to the distal portion **2830** and extends out the proximal end of arterial access device such that the telescoping actuation may be accomplished from the proximal end of the arterial access device. An expandable member, such as balloon **2815**, may be positioned on the device **2820**.

[0083] FIG. 14 shows an alternate embodiment of the system wherein a secondary device, such as a balloon catheter **2502**, is advanced through the arterial access device **2010** and into a collateral cerebral artery such as the anterior cerebral artery ACA. The balloon catheter **2502** includes an expandable balloon **2530** that can be expanded in the collateral cerebral artery to occlude that artery. Occlusion of the collateral cerebral artery enhances suction and reverse flow through the cerebral vasculature, as described in detail below.

EXEMPLARY EMBODIMENTS OF ASPIRATION AND FLOW CONTROL

[0084] Either or both the arterial access device **2010** and the distal catheter **2030** may be connected to sources of passive or active aspiration via flow lines **2025** or **2045** (FIG. 1) on the devices. The mode of aspiration may be different for each device.

[0085] In FIG. 15, the flow line **2025** of the arterial access device **2010** is connected to a delivery location, such as a receptacle **3100**. A source of aspiration **3125** may be coupled to the flow line **2025**. The receptacle **3100** and source of aspiration **3125** may be separate or may be combined into a single device such as a syringe. A filter **3418** and/or a check valve **3419** may be coupled with flow line **2025**. In FIG. 16, the flow line **2045** of the distal catheter **2030** is additionally or alternately connected to a separate aspiration source **3425** and delivery location, such as receptacle **3105**. The aspiration source **3425** and delivery location may be combined into a single device such as a syringe. A filter **3418** and/or a check valve **3419** may be coupled with the flow line **2045**.

[0086] FIG. 17 shows a system whereby both the arterial access device **2010** and distal catheter **2030** are connected to the same aspiration source **3430** via flow lines **2025** and **2045**, respectively. A valve **3325** controls which device is connected to the aspiration source **3430**. The valve may enable one

device, the other device, both devices, or neither device to be connected to the aspiration source at any given time. The valve may be a 3-way or 4-way stopcock. Alternately, the valve may be a flow controller with a simple actuation which selects the configuration as described above.

[0087] In an embodiment, a flow controller may facilitate control of multiple means of aspiration through multiple devices in a single unit. This configuration may facilitate use of the system by a single operator. The flow controller may include one or more control interfaces that a user may actuate to regulate which device is being aspirated, for example the arterial access device, the distal catheter, both, or neither. FIG. 18 shows an embodiment of a system that utilizes such a flow controller 3400. The flow controller 3400 is connected to the flow line 2025 of the arterial access device 2010 as well as to the flow line 2045 of the distal catheter 2030. In this manner, the flow lines 2025 and 2045 permit fluid to flow from the arterial access device 2010 and the catheter 2030, respectively, to the flow controller 3400. The controller 3400 may be connected to either or both a passive source of aspiration 3410 and an active source of aspiration 3420. The flow controller housing 3429 contains control mechanisms to determine how and when each device is connected to each source of aspiration. The control mechanisms may also control the level of aspiration from each source. In addition, the controller may include a control that permits a pulsatile aspiration mode which may facilitate the breaking up and aspiration of the cerebral occlusion. The flow controller may have an interface for switching between continuous and pulsatile aspiration modes. The control mechanisms may be designed to be operable using one hand. For example, the control mechanisms may be toggle switches, push button switches, slider buttons, or the like. In an embodiment, the flow controller 3400 has an interface that can enable the user to restore immediate antegrade flow to the cerebral circulation, for example with a single button or switch that simultaneously deflates the occlusion balloon on the arterial access device and stops aspiration.

[0088] The active source of aspiration may be an aspiration pump, a regular or locking syringe, a hand-held aspirator, hospital suction, or the like. In one embodiment, a locking syringe (for example a VacLok Syringe) is attached to the flow controller and the plunger is pulled back into a locked position by the user while the connection to the flow line is closed prior to the thrombectomy step of the procedure. During the procedure when the tip of the aspiration device (either the arterial access device or the distal catheter) is near or at the face of the occlusion, the user may open the connection to the aspiration syringe. This would enable the maximum level of aspiration in a rapid fashion with one user, something that is currently not possible with existing technologies. In another embodiment, the aspiration source is a hand-held aspirator which is configured to be able to aspirate and refill without disconnecting the aspiration device. In an example of this embodiment, the hand-held aspirator contains a chamber with a plunger that is moved up and down with a single-handed actuator. The chamber includes input and output valves, such that when the plunger is moved up and down there is a continuous source of aspiration into and out of the chamber without the need to remove and empty the chamber as would be needed with a syringe. The chamber input is connected to the catheter, and the chamber output is con-

nected to a collection receptacle such as blood-collection bag. In an embodiment, this aspiration source is configured to be used with one hand only.

[0089] One disadvantage of current sources of aspiration is that the aspirated blood is received into an external reservoir or syringe. This blood is generally discarded at the end of the procedure, and as such represents blood loss from the patient. In addition, pumps such as centrifugal or peristaltic pumps are known to cause damage to blood cells. Although it is possible to return blood from the external reservoir to the patient, the blood has been exposed to air or has been static for a period of time, and there is risk of thrombus formation or damage to the blood cells. Usually, aspirated blood is not returned to the patient to avoid risk of thromboembolism.

[0090] FIG. 19 shows a cross-sectional view of an exemplary aspiration pump device 3250 which is configured not to harm blood cells and which may be configured to return blood to the central venous system in real time during the procedure, so there is no reservoir in which the blood remains static. The pump 3250 may be connected to either or both the arterial access device 2010 and distal catheter 2030. The pump device 3250 includes a housing 3215 that encloses a chamber 3220 in which is contained a portion of the flow line 2025. An expandable portion 3210 of the flow line 2025 contained within the chamber 3220 is formed of an elastic material that is at a reduced diameter in its natural state (shown in phantom lines in FIG. 19) but may be configured to change to an expanded diameter (shown in solid lines in FIG. 19). One or more seals 3125, such as O-rings, seal the interface between the chamber 3220 and the flow line 2025. A vacuum source 3230 is coupled to the chamber 3220 and is configured to be operated to vary the pressure within the chamber 3220. Two one-way check valves 3235 are located in the flow line 2025 on either side of the expandable portion 3210.

[0091] In operation of the pump device 3250, the vacuum source 3230 is operated to create a reduced pressure within the chamber 3220 relative to the pressure within the flow line lumen 3210. The pressure differential between the chamber 3220 and the flow line lumen 3210 causes the expandable portion 3210 of the flow line 2025 to expand to an increased volume within the chamber 3220, as shown in solid lines in FIG. 32. This expansion causes blood to be pulled into the expandable portion 3210 from the sheath side of the flow line, shown by the “in” arrow, as controlled by the check valves 3235. The vacuum source 3230 may then be turned off so as to normalize the pressure within the chamber 3220. This causes the expandable portion 3210 to revert to its smaller, natural diameter, as shown in phantom lines in FIG. 19. The check valves 3235 causes the blood within the previously-expanded region of the flow line 2025 to be expelled towards location 3120, as shown by the “out” arrow in FIG. 19. The vacuum source 3230 may be operated so as to oscillate the expandable portion 3210 between the expanded and retracted state and together with the one-way check valves 3235 thereby drive fluid through the flow line lumen 3210.

[0092] FIG. 20 shows a pump system 3305 that includes a pair of pump device 3205a and 3205b, each of which is of the type shown in FIG. 32. That is, each device 3205 includes a housing 3215 that contains a chamber in which a portion of the flow line 2025 is contained. The pump devices 3205a and 3205b are connected in parallel to the flow line 2025 such that each pump device 3205 has a flow line 2025 with an expandable portion 3210. The pair of pump devices 3205a and 3205b may be alternated between expanded and retracted states to

create a relatively continuous flow state through the pump system **3305**. For example, the pump device **3205a** may be in the expanded state while the pump **3205b** may be in the retracted state such that the pumps **3205a** and **3205b** are collectively driving fluid through the pump system **3305** without interruption.

[0093] A further advantage pump system **3250** or **3305** is that it may be used in conjunction with a passive reverse flow system which is configured to return blood to the central venous system, as is disclosed elsewhere in this document. These two systems may share a venous return line, and are connected by a valve or other flow control device.

[0094] The passive source of aspiration may be a site with lower pressure, for example a sheath inserted into a central vein (for venous return) or an IV bag placed at a vertical level that would vary depending on what amount of negative pressure is desired. FIG. 21 shows an exemplary embodiment of a system **3500** that uses venous return to establish passive retrograde flow into the arterial access device. The system **3500** includes the arterial access device **3510**, a venous return device **3515**, and a flow line **3520** that provides a passageway for retrograde flow from the arterial access device **3510** to the venous return device **3515**. A flow control assembly **3525** interacts with the flow line **3520**. The flow control assembly, **3525** is adapted to regulate and/or monitor the retrograde flow through the flow line **3520**. The flow control assembly **3525** interacts with the flow pathway through the flow line **3520** to determine the state and level of flow through the flow line.

[0095] In an embodiment, the arterial access device **3510** at least partially inserts into the common carotid artery CCA and the venous return device **3515** at least partially inserts into a venous return site, such as the femoral vein or internal jugular vein, as described in more detail below. The venous return device **3515** can be inserted into the femoral vein FV via a percutaneous puncture in the groin. The arterial access device **3510** and the venous return device **3515** couple to opposite ends of the flow line **3520** at connectors. The distal end of the arterial access device **3510** with the occlusion element **3529** may be positioned in the ICA. Alternately, in some circumstances where the ICA access is extremely tortuous, it may be preferable to position the occlusion element more proximally in the common carotid artery. When flow through the internal carotid artery is blocked (using the occlusion element **3529**), the natural pressure gradient between the internal carotid artery and the venous system causes blood to flow in a retrograde or reverse direction from the cerebral vasculature through the internal carotid artery and through the flow line **3520** into the venous system.

[0096] In another embodiment, the arterial access device **3510** accesses the common carotid artery CCA via a transcervical approach while the venous return device **3515** access a venous return site other than the femoral vein, such as the internal jugular vein. In another embodiment, the system provides retrograde flow from the carotid artery to an external receptacle, for example an IV bag, rather than to a venous return site. The arterial access device **3510** connects to the receptacle via the flow line **3520**, which communicates with the flow control assembly **3525**. The retrograde flow of blood is collected in the receptacle. If desired, the blood could be filtered and subsequently returned to the patient. The pressure of the receptacle could be set at zero pressure (atmospheric pressure) or even lower, causing the blood to flow in a reverse direction from the cerebral vasculature to the receptacle.

EXEMPLARY EMBODIMENTS OF THROMBECTOMY DEVICES

[0097] An exemplary embodiment of a thrombectomy device for use with any of the disclosed systems of devices is a device such as those described above but that are configured for transcervical placement. Specifically, the thrombectomy device has a working length which would allow it to extend out of the arterial access device **2010** or distal catheter **2030** with enough length to access and cross the cerebral occlusion. More specifically, a thrombectomy device with a working length of between 80 and 120 cm. The thrombectomy device may be configured to remove an occlusion as a single piece by not breaking the occlusion into multiple pieces. This may minimize or eliminate the creation of emboli distal to the location of the clot.

[0098] In an embodiment, a microcatheter which has been configured for transcervical access is included as part of system **100**. More specifically, a microcatheter with a working length of between 100 and 140 cm is included in system **100**. The microcatheter may be used for angiograms and/or delivery of thrombectomy devices.

[0099] Additional embodiments of thrombectomy devices are now described. FIG. 22 shows an enlarged, side view of a distal region of an exemplary thrombectomy device **4100** that is formed of a self-expandable member **4112** attached to an elongate flexible catheter **4115** that extends proximally from the expandable member **4112**. The expandable member **4112** is formed of a plurality of longitudinal, intertwined or undulating struts that are arranged to form a plurality of cell structures that may be diamond-shaped. In an embodiment, the struts are coupled to a source of energy that permits sonic energy to be applied to the struts. The expandable member **4112** is configured to transition between a reduced size and an enlarged size wherein the expandable member **4112** expands radially outward from a first diameter to a second, greater diameter relative to the longitudinal axis of the catheter **4115**. The expandable member **4112** may be formed for example from a single tube which has been laser cut in a geometry to create the struts, in a similar manner that many intravascular stents are manufactured. In an embodiment, the expandable member **4112** is made of shape memory material, such as Nitinol. The expandable member **4112** may be configured according to expandable members described in U.S. Patent Publication No. 20110009875, which is incorporated herein by reference in its entirety.

[0100] In use, the expandable member **4112** is advanced through the vascular anatomy via the arterial access device described above. The expandable member **4112** is positioned at the site of the thrombus while in the unexpanded state. The expandable member is then positioned within the location of the thrombus and caused to transition to its expanded state. In an embodiment, once the expandable member **4112** is expanded at the location of the thrombus, the expandable member is maintained in that location for a period of time in order to create a perfusion channel through the thrombus that causes the thrombus to be lysed by the resultant blood flow passing through the thrombus. In such an embodiment, it is possible but not necessary that the expandable member **4112** capture a portion of the thrombus for retrieval outside the patient. When a sufficient portion of the thrombus has been lysed to create a desired flow channel through the obstruction, or outright removal of the obstruction is achieved by the resultant blood flow, the expandable member **4112** may be withdrawn into the sheath **4100** and subsequently removed

from the patient. The expandable portion may capture some or all of the thrombus while being withdrawn into the sheath.

[0101] In an embodiment, also shown in FIG. 22, an elongated perfusion catheter 4120 is positioned longitudinally through the expandable member 4112. The perfusion catheter 4120 has a plurality of perfusion holes that communicate with an internal lumen and a source of perfusion fluid. The perfusion catheter 4120 is configured to perfuse fluid outwardly through perfusion holes 4125. The perfusion holes may be used to perfuse thrombolytic agents such as urokinase or tPA to aid in the dissolution of the clot. Alternately, the perfusion holes may be used to perfuse neuroprotective agents and/or oxygenated blood.

[0102] FIG. 23 shows another embodiment wherein an elongated mechanical member 4205 is positioned longitudinally through the expandable member 4112. The mechanical member 4205 generally extends along the longitudinal axis of the expandable member 4112. The mechanical member is configured to exert mechanical energy onto the thrombus when the expandable member 4112 is positioned within the thrombus. The mechanical member 4205 may be any of a variety of mechanical members, such as a corkscrew wire or a brush. The mechanical member can be moved to exert the mechanical energy, such as by rotating or vibrating the mechanical member 4205. The embodiments of FIGS. 16 and 17 may be combined to provide perfusion and aspiration capabilities along with mechanical disruption capabilities.

[0103] Various other features may be used with or coupled to the expandable member 4112. FIG. 24 shows an embodiment wherein a distal filter 4305 is positioned at or near the distal end of the expandable member 4112. The filter 4305 is configured to capture emboli which may be generated during removal of the thrombotic obstruction, either through natural lysis of the thrombus or mechanical retrieval of the thrombus. In the embodiment of FIG. 25, a parachute-shaped member 4405 is positioned at or near the distal end of the expandable member 4112. The embodiment of FIG. 19 includes a plurality of longitudinal struts 4605 that extend from a proximal end toward a distal end of the expandable member 4112, and are attached to parachute-shaped member 4405. The struts 4605 are configured to be pressed through the thrombus when deployed within the thrombus. When pressed through the thrombus, the struts 4605 pull the parachute-shaped member 4405 around the thrombus to capture it, and the device 4100 can then be withdrawn to pull the thrombus out of the artery.

[0104] In the embodiment of FIG. 26 an expandable dilatation member 4505, for example a dilatation balloon is positioned within the expandable member 4112. The dilation member 4505 may be expanded to dilate the thrombotic occlusion and press the expandable member 4112. Once the dilation member is deflated, the expandable member which is now engaged with the clot may be pulled back to remove the thrombus out of the artery.

[0105] FIG. 27 shows another embodiment of a thrombectomy device comprised of an elongated element 4705 positioned at a distal end of a distal catheter 4710. The elongated element 4705 has an irregular shape along its longitudinal axis, such as a corkscrew or undulating shape. Alternately, the elongated element is slidably positioned inside distal catheter 4710. The elongated element 4705 may be made from spring material such as stainless steel or Nitinol, so that it may be retracted into distal catheter 4710 when crossing the clot. After crossing, the catheter 4710 is pulled back to expose the elongated element 4705 and allow it to take its irregular

shape. The elongated element may be positioned at the site of the thrombus and then manipulated, such as by shaking, rotating, waving, spinning, or moving back and forth, so as to exert mechanical energy onto the thrombus to break up the thrombus. The distal catheter 4710 is connected to an aspiration source to aspirate the thrombus as it is being mechanically disrupted by elongated element 4705.

[0106] In the embodiment of FIG. 28, an elongated catheter 4805 is sized and shaped to be positioned within the thrombus. The catheter 4805 includes perfusion holes 4810 that can be used to spray a perfusion fluid onto the thrombus with sufficient force onto the thrombus to disrupt the thrombus. The elongated catheter 4805 may be delivered through another distal catheter 4820. The distal catheter 4820 may be connected to an aspiration source to aspirate the thrombus as it is being fluidly disrupted by the perfusion fluid from elongated catheter 4805. The distal end of the catheter 4805 may include an expandable occlusion element 4815 to prevent perfusion fluid or disrupted thrombus from traveling downstream.

[0107] In another embodiment, shown in FIG. 29, a catheter 4900 includes dual lumens that run in parallel along the length of the catheter 4900. The dual lumens include an access lumen 4920 for deployment of an intervention device such as a thrombectomy device or a stentriever, as well as a perfusion lumen 4930 for transmission of perfusion fluid, thrombolytic agent, or for aspiration of thrombus material.

[0108] It should be appreciated that other mechanical thrombectomy catheters may be used in a similar manner with the vascular access and reverse flow system as described above. Mechanical thrombectomy devices may include variations on the thrombus retrieval device described earlier, such as coil-tipped retrievers, stent retrievers, expandable cages, wire or filament loops, graspers, brushes, or the like. These clot retrievers may include aspiration lumens to lower the risk of embolic debris leading to ischemic complications. Alternately, thrombectomy devices may include clot disruption elements such as fluid vortices, ultrasound or laser energy elements, balloons, or the like, coupled with flushing and aspiration to remove the thrombus. Some exemplary devices and methods are described in the following U.S. Patents and Patent Publications, which are all incorporated by reference in their entirety: U.S. Pat. No. 6,663,650, U.S. Pat. No. 6,730,104; U.S. Pat. No. 6,428,531, U.S. Pat. No. 6,379,325, U.S. Pat. No. 6,481,439, U.S. Pat. No. 6,929,632, U.S. Pat. No. 5,938,645, U.S. Pat. No. 6,824,545, U.S. Pat. No. 6,679,893, U.S. Pat. No. 6,685,722, U.S. Pat. No. 6,436,087, U.S. Pat. No. 5,794,629, U.S. Patent Pub. No. 20080177245, U.S. Patent Pub. No. 20090299393, U.S. Patent Pub. No. 20040133232, U.S. Patent Pub. No. 20020183783, U.S. Patent Pub. No. 20070198028, U.S. Patent Pub. No. 20060058836, U.S. Patent Pub. No. 20060058837, U.S. Patent Pub. No. 20060058838, U.S. Patent Pub. No. 20060058838, U.S. Patent Pub. No. 20030212384, and U.S. Patent Pub. No. 20020133111.

[0109] A major drawback to current thrombectomy devices is the need to re-cross the occlusion with a guidewire and microcatheter if the thrombectomy device did not remove enough of the occlusion to restore adequate flow, and additional attempts are needed to remove the occlusion. Currently, a single-lumen microcatheter is used to deliver the thrombectomy device. The microcatheter is placed over a guidewire, the guidewire is then removed and the thrombectomy device is delivered. When removing the occlusion both the micro-

catheter and device are pulled back and the access across the occlusion is lost. Thus if the attempt at removal was unsuccessful or incomplete and an additional attempt is required, the guidewire and microcatheter must again cross the occlusion. As mentioned above, this extra step of re-crossing the occlusion takes time and incurs risk of distal vessel injury. An embodiment of this disclosure, shown in FIG. 30, is a microcatheter **4200** which includes at least two lumens, one lumen for a guide wire **2515** and the second to deliver a thrombectomy device **4100** such as a stentriever or coil retriever. The presence of a second lumen for the guide wire may add outer profile to a microcatheter over a microcatheter with just a single lumen. However, the reduced time and risk that may be provided by a second guidewire lumen can be advantageous. In addition, for use transcervically, the guidewire and/or the catheter walls may be scaled down to be less than conventional wall thicknesses, to lower the overall increase needed to add the extra lumen.

EXEMPLARY EMBODIMENTS OF PERFUSION DEVICES

[0110] In an embodiment, the system may include a means to perfuse the cerebral vasculature distal to the thrombotic blockage and ischemic brain tissue via a perfusion catheter delivered, for example, through the arterial access device **2010** to a site distal to the thrombotic occlusion **10**. The perfusion catheter is adapted to deliver a perfusion solution to a desired location. Perfusion solution may include, for example, autologous arterial blood, either from the flow line of a passive reverse flow circuit **3500** or from another artery, oxygenated solution, or other neuroprotective agent. In addition, the perfusion solution may be hypothermic to cool the brain tissue, another strategy which has been shown to minimize brain injury during periods of ischemia. The perfusion catheter may also be used to deliver a bolus of an intra-arterial thrombolytic agent pursuant to thrombolytic therapy. Typically, thrombolytic therapy may take up to 1-2 hours or more to clear a blockage after the bolus has been delivered. Mechanical thrombectomy may also take up to 1 to 2 hours to successfully recanalize the blocked artery. Distal perfusion of the ischemic region may minimize the level of brain injury during the stroke treatment procedure. Embodiments of distal perfusion means are described below.

[0111] FIG. 31 shows a perfusion catheter **3600** positioned across the thrombotic blockage **10**, to enable perfusion distal to the blockage. In an embodiment, the catheter is **3600** positioned over a guidewire placed through a lumen in the catheter. The lumen may serve as both a guidewire lumen and a perfusion lumen. Once placed, the guidewire may be removed to maximize the throughspace of the lumen available for perfusion. Alternately, the guidewire lumen and the perfusion lumen may be two separate lumens within the catheter, so that the guidewire may remain in place in the guidewire lumen during perfusion without interfering with the perfusion lumen. Perfusion exit holes **3615**, which communicate with the perfusion lumen, are located in a distal region of the catheter **3600**. This perfusion lumen may be connected to a perfusion source such as a perfusion pump or syringe and may be used for perfusing fluid such as neuroprotective agents and/or oxygenated blood such as the patient's own arterial blood via the perfusion exit holes **3615** as exhibited by the arrows P in FIG. 32, which represent the flow of perfusion solution out of the catheter **3600**. Alternately, the catheter **3600** may be positioned relative to the

blockage **10** such that the perfusion exit holes **3615** are initially positioned just proximal to, or within, the thrombotic blockage **10** during a bolus of thrombolytic infusion. The catheter can then be re-positioned so that at least some of the perfusion exit holes **3615** are located distal of the blockage **10** to provide distal perfusion with blood or an equivalent solution to the ischemic penumbra. The perfusion catheter may be used in conjunction with mechanical or aspiration thrombectomy as above. The catheter may be positioned through the lumen of access device **2010** or distal catheter **2030**. The catheter may be placed side by side with mechanical thrombectomy means in the lumen, or may be co-axial with mechanical thrombectomy device.

[0112] FIG. 32 shows another embodiment of a perfusion catheter **3600** with a perfusion lumen **3610** that communicates with side holes **3615** and/or an end opening **3616** for perfusing fluid, and a second lumen **3612** for pressure monitoring. The pressure monitoring lumen **3612** is closed off at a distal-most end **3613**. A side opening **3614** to the lumen **3612** is located proximal of the distal-most end **3613** for measuring perfusion pressure. The catheter **3600** is shown without an expandable occlusion element although it could include an expandable occlusion element such as an occlusion balloon. The occlusion element may be positioned either distal to or proximal to the side holes **3615**. In an embodiment, the perfusion source may be controlled by the perfusion pressure measurement to maintain perfusion pressure below 200 mm Hg. In an embodiment, the perfusion flow rate is controlled to maintain perfusion in the range of about 50 ml/min to about 250 ml/min.

[0113] In an alternate embodiment, as shown in FIG. 33, distal perfusion catheter **3700** includes an occlusion balloon **3705**, with perfusion exit holes **3715** positioned distal to, and/or proximal to the occlusion balloon **3705**. As with the previous embodiment, the perfusion catheter **3700** may be used in conjunction with recanalization therapies such as thrombectomy devices, aspiration means or intra-arterial thrombolytic infusion. The catheter **3700** is placed in the vasculature so that the occlusion balloon **3705** is positioned distal to the blockage **10**. The catheter **3700** may be configured to perfuse the region distal of the balloon **3705** with blood or equivalent, and the region proximal of the balloon **3705** with thrombolytic agents. In this regard, the catheter **3700** may include separate perfusion lumens **3720** and **3725** that communicate with separate perfusion exit holes, as shown in FIG. 34. Alternately, as shown in FIG. 35, the distal and proximal perfusion exit holes are connected to the same perfusion lumen **3630**, and regions both distal and proximal to the occlusion balloon are used to infuse blood or alternate perfusion solution. Not shown in either FIG. 34 or 35 is a separate lumen for inflation and deflation of occlusion balloon **3705**. This lumen may be embedded into the wall of the catheter.

[0114] In another embodiment, as shown in FIG. 36, the expandable occlusion device **3705** is a dilatation balloon which may provide a dilatation force on the thrombus while the catheter **3700** is perfusing the distal vasculature.

[0115] The perfusion catheter may also provide perfusion to aid in thrombus removal. FIG. 37 shows a proximal perfusion catheter **3800** being deployed distal of the occlusion via the arterial access device **2010**. The proximal perfusion catheter **3800** includes an expandable occlusion element **3829** such as an occlusion balloon. The proximal perfusion catheter **3800** also includes one or more perfusion exit holes **3820** at a

location proximal to the occlusion element **3829**. The perfusion exit holes **3820** communicate with an internal perfusion lumen in the perfusion catheter **3800** for perfusion of fluid out through the perfusion exit holes **3820**. With reference still to FIG. 37, the proximal perfusion catheter **3800** is deployed into the vasculature via the arterial access device so that the occlusion element **3829** of the perfusion catheter is positioned and expanded distal to the thrombus **10** with the perfusion exit holes **3820** positioned proximal to the occlusion element **3829** and distal to the thrombus **10**. Such an arrangement provides back pressure to assist in removal of the thrombus **10**. In addition, the occlusion element **3829** serves as distal emboli protection. Any of a variety of perfusion fluids may be used including, for example, oxygenated blood, neuroprotection agents, thrombolytics, as well as other fluids, which may be adjusted to a desired temperature. The arterial access device **2010** can be used for aspiration in the arrangement of FIG. 37. The arterial access device **2010** may have occlusion balloon **2020** as well as passive or active aspiration means. The perfusion catheter facilitates removal of the thrombus into the arterial access device **2010** and thence through the flow line **2025** and out of the patient.

[0116] Alternately, as shown in FIG. 38, the proximal perfusion catheter **3800** may be delivered via distal catheter **2030**. When aspiration is initiated through the distal catheter **2030** and perfusion is initiated through proximal perfusion catheter **3800** there is a pressure gradient in a retrograde direction which aids in removal of thrombus **10** from the vessel, and into the lumen of distal catheter **2030**. The arterial access device **2010** and distal catheter **2030** may simultaneously aspirate. Or, the aspiration may be applied sequentially between the arterial access device **2010** and the distal catheter **2030**. For example, the distal catheter **2030**, when positioned as shown in FIG. 38, can aspirate. The distal catheter **2030** can then be withdrawn into the arterial access device **2010** and the aspiration applied from the arterial access device.

[0117] In addition to providing pressure distal to the occlusion, the perfusion fluid from proximal perfusion catheter **3800** can supply blood to smaller vessels (perforators) originating in or just proximal to the occlusion. The shaft of the perfusion catheter **3800** may also be used as a rail or conduit for delivery of a therapeutic device such as stentriever or thrombectomy device.

[0118] In an embodiment, the perfusion lumen and the guide wire lumen are two separate lumens, configured for example as in FIG. 32. In an alternate embodiment, the perfusion lumen of the perfusion catheter **3800** also serves as a guide wire lumen. In such an arrangement, a valve is desirably located at the distal end opening of the perfusion/guide wire lumen. When the guide wire is pushed distally out of the distal end opening of the guide wire lumen, the guide wire opens the valve. The valve automatically closes when the guide wire is retracted proximally back into the lumen. In this manner, the valve seals the distal end opening of the lumen after the guide wire is retracted. The valve can also be a pressure relief valve such that if the perfusion pressure is too high, the valve opens to release the pressure.

[0119] FIGS. 39A-39D show an exemplary method of use of proximal perfusion catheter **3800**. FIG. 39A shows an enlarged view of a guide wire **3912** positioned across the thrombus **10** in a cerebral artery. In FIG. 39B, a distal region of the perfusion catheter **3800** has been positioned across the thrombus **10** (via the guide wire **3912**) with the unexpanded

occlusion element **3829** positioned distal of the thrombus **10**. The guide wire **3912** protrudes out of the distal end of the guide wire lumen of the perfusion catheter **3800**. In FIG. 39C, the guide wire is not shown as it has been retracted back into the guide wire lumen of the perfusion catheter **3800**. If the guide wire lumen also serves as a perfusion lumen for the perfusion catheter **3800**, a distal valve **3916** (such as a duck-bill valve) at the distal end of the guide wire/perfusion lumen has automatically closed such that the lumen can now be used for perfusion via the perfusion exit holes **3820**, as represented by the arrows P in FIG. 34C. When the occlusion element **3829** is unexpanded (as shown in FIG. 39C), the perfusion exit holes **3820** can be used to perfuse distally. In FIG. 39D, the expandable occlusion element **3829** has been expanded in the artery. The perfusion exit holes **3820** can then be used for perfusion proximal of the occlusion element **3829**, as represented by the arrows P1 in FIG. 39D.

[0120] Perfusion catheters **3600** or **3800** may include an element for monitoring blood pressure. In an embodiment, the pressure monitoring element is a dedicated internal lumen in the perfusion catheter **3600** or **3800**, wherein the lumen is fluid-filled and connected to a pressure transducer on the proximal end of the perfusion catheter. A pressure transducer on the catheter itself may also be used. Alternately, a pressure measuring guide wire may be inserted through an internal lumen of the perfusion catheter **3600** or **3800** to a location where pressure is to be monitored.

[0121] An alternate means for cerebral perfusion comprises cerebral retroperfusion as described by Frazee et al. This embodiment involves selective cannulation and occlusion of the transverse sinuses via the internal jugular vein, and infusion of blood via the superior sagittal sinus to the brain tissue, during treatment of ischemic stroke. The following articles, which are incorporated herein by reference in their entirety, described cerebral retroperfusion and are incorporated by reference in their entirety: Frazee, J. G. and X. Luo (1999). "Retrograde transvenous perfusion." *Crit Care Clin* 15(4): 777-88, vii.; and Frazee, J. G., X. Luo, et al. (1998). "Retrograde transvenous neuroperfusion: a back door treatment for stroke." *Stroke* 29(9): 1912-6. This perfusion, in addition to providing protection to the cerebral tissue, may also cause a retrograde flow gradient in the cerebral arteries. Used in conjunction with the system **100**, a retroperfusion component may provide oxygen to brain tissue, as well as aid in capture of embolic debris into the reverse flow line during recanalization of the thrombotic occlusion **10**.

[0122] It should be appreciated that other perfusion catheters or systems may be used with the system **100**, for example those described by U.S. Pat. Nos. 6,435,189 and 6,295,990, which are incorporated by reference in their entirety.

EXEMPLARY METHODS AND DEVICES FOR TRANSCERVICAL VESSEL CLOSURE

[0123] Any type of closing element, including a self-closing element, a suture-based closing element, or a hydrostatic seal element, may be deployed on or about the penetration in the wall of the common carotid artery prior to withdrawing the arterial access device **2010** or introducer sheath **2110** (the procedural sheath) at the end of the procedure. The following U.S. Patent Applications, which are incorporated herein by reference in their entirety, describe exemplary closure devices and methods: U.S. Patent Publication No. 20100042118,

entitled “Suture Delivery Device”, and U.S. Patent Publication No. 20100228269, entitled “Vessel Closure Clip Device”.

[0124] The closing element may be deployed at or near the beginning of the procedure in a step termed “pre-closure”, or, the closing element could be deployed as the sheath is being withdrawn. In an embodiment, the means for vessel closure is a suture-based blood vessel closure device. The suture-based vessel closure device can place one or more sutures across a vessel access site such that, when the suture ends are tied off after sheath removal, the stitch or stitches provide hemostasis to the access site. The sutures can be applied either prior to insertion of the procedural sheath through the arteriotomy or after removal of the sheath from the arteriotomy. The device can maintain temporary hemostasis of the arteriotomy after placement of sutures but before and during placement of a procedural sheath, if a pre-closure step is used, and can also maintain temporary hemostasis after withdrawal of the procedural sheath but before tying off the suture. Some exemplary suture-based blood vessel closure devices are described in the following U.S. Patents, which are incorporated herein by reference in their entirety: U.S. Pat. Nos. 6,562,052; 7,001,400; and 7,004,952.

[0125] In an embodiment, the system includes an ultrasound probe element, which when used with an ultrasound imaging system is configured to identify the desired site of carotid arterial access to determine that is suitable for percutaneous puncture, for example to verify that there is no vascular disease in the vessel. The probe will also visualize surrounding anatomy such as the internal jugular vein, to ensure that access can be achieved without comprising these other structures. In addition, the probe may be used to visualize the access site after vessel closure to verify that hemostasis has been achieved. If needed, the probe may be used to provide localized compression at the site of the puncture as needed to ensure hemostasis. For example, after vessel closure the probe is used to image the closure site. If blood is seen flowing from the site, the probe is pressed down to compress the site. The user periodically relaxes the pressure on the probe to assess if hemostasis has been achieved. If it has not, pressure is reapplied. If it has, the probe may be removed.

EXEMPLARY METHODS OF USE

[0126] As illustrated in FIG. 1, the arterial access device **2010** is transcervically introduced directly into the common carotid artery CCA of the patient. This may be done with a percutaneous puncture or a direct cut-down. In the case of a puncture, ultrasound imaging may be used to accurately make the initial arterial puncture. The arterial access device **2010** is threaded through the vasculature such that the distal tip is positioned in the common carotid artery or the proximal or distal cervical, petrous, or cavernous portion of the internal carotid artery ICA. A removable proximal extension may be used to place the arterial access device **2010** under fluoroscopy without exposing the user’s hand to radiation. U.S. patent application Ser. No. 12/834,869, filed Jul. 12, 2010, describes exemplary embodiments of removable proximal extensions and is incorporated herein by reference.

[0127] Once the arterial access device is positioned, a diagnostic angiogram may be performed via a microcatheter placed through the arterial access device. The microcatheter may be for angiographic injections both proximal and distal to the occlusion. Diagnostic angiograms are performed

throughout the procedure to determine the progress in removing the occlusion or occlusions.

[0128] If the arterial aspiration device has an occlusion balloon, the balloon may be inflated at this time and aspiration may be applied to the arterial access device. Because the tip of the aspiration device is some distance proximal to the occlusion, the aspiration force is not directly applied to the occlusion. However, in some cases, this proximal aspiration may serve to remove some or all of the occlusion. Once aspiration from the access device is finished, the occlusion balloon may be deflated so that antegrade flow may resume in the artery.

[0129] A distal catheter **2030** is placed through the arterial access device and positioned such that the distal tip reaches the site of the occlusion. If desired, a coaxial system of devices comprising a guide wire, a microcatheter, and the distal catheter **2030** are inserted together through the arterial access device **2010** and advanced towards the cerebral occlusion. Alternately, a tapered dilator with or without a microcatheter tip may be substituted for the microcatheter. Alternately, a microcatheter and guide wire may be placed inside the tapered dilator. The removable proximal extension, if used, may be removed prior to introduction of the telescoping devices, or the devices may be inserted through the removable proximal extension. The microcatheter, or tapered dilator, and guide wire are then advanced to access and cross the cerebral occlusion. The microcatheter or dilator may be used to perform the angiogram of the cerebral circulation proximal and distal to the occlusion. The microcatheter may also be used as a rail to advance the distal catheter.

[0130] Typically, the largest size distal catheter will be selected which is able to be safely navigated to the occlusion, to maximize the force and luminal area for aspiration of the occlusion. Aspiration is then initiated through the distal catheter. This may be done manually, with an aspiration pump or other aspirator source, or via the flow controller as described above. If the thrombus is too large or too strongly embedded into the vasculature such that it is not possible to remove the occlusion via aspiration alone, further steps are taken to remove the occlusion. A thrombectomy device may be deployed through the arterial access device to remove the clot. During clot retrieval, passive or active aspiration may be applied via the arterial access device to minimize or eliminate the amount of distal emboli.

[0131] If the distal catheter is unable to reach the occlusion, or if a secondary more distal occlusion needs to be reached after removal of a first occlusion, a second, smaller diameter distal catheter may be inserted through the first distal catheter, and positioned at the site of the occlusion. Alternately, the first distal catheter may be removed and exchanged for the second distal catheter. A guidewire and/or microcatheter may be placed through the first distal catheter to facilitate the exchange. Once at the target site, aspiration may be initiated through the second catheter as above, or additional devices may be inserted to aid in removal of the occlusion.

[0132] If there is difficulty navigating the distal catheter of the desired size to a location just proximal to the clot, a device may be deployed distal to the clot and expanded to act as an anchor to aid in advancing the distal catheter as shown in FIG. 6 or 7. If desirable, a second distal catheter may be used in a telescoping manner to create support for the first distal catheter to access the proximal face of the occlusion. Alternately, a tapered dilator as shown in FIG. 8 may be used in addition to or in place of the microcatheter to facilitate navigation of

the distal catheter. The arterial access device **2010** and the distal catheter **2030** may be connected to means for passive or active aspiration, as shown in FIGS. **15-17**, or a flow controller **3400** as shown in FIG. **18**. In one embodiment, the arterial access device **2010** is connected to passive aspiration and the distal catheter **2030** is connected to active aspiration. In another embodiment, both devices are connected to active aspiration. During the procedure, the user may open or close the connections to the passive and/or active aspiration sources as desired. For example, when the distal catheter **2030** is positioned at the proximal face of the clot, the active aspiration may be initiated to apply suction to the occlusion with the goal to remove the occlusion. If a locking syringe was used and an additional aspiration step is desired, the syringe may be removed, emptied, reattached and re-locked for additional aspiration.

[0133] In another embodiment, the microcatheter is used to deliver a thrombectomy device such as a coil or stentriever in or beyond the occlusion. The device is then pulled towards the distal catheter to remove the occlusion, aided by aspiration of the distal catheter. The occlusion is then pulled back using the distal catheter, thrombectomy device, and/or microcatheter into the arterial access device. In yet another embodiment, the microcatheter has two lumens as shown in FIGS. **11** and **12**, such that the guide wire may be left across the occlusion when the microcatheter and/or thrombectomy device are pulled proximally to remove the occlusion.

[0134] At any time during the procedure, the balloon on the arterial access device may be inflated at this point to reduce forward arterial pressure on the occlusion. The inflated balloon may also increase the stability of the arterial access in the vessel to increase the support for advancement of devices through the arterial access device. Additionally, the arterial access device may be connected to passive or active aspiration as desired to provide embolic protection while not compromising collateral flow to the ischemic penumbra of the patient. This may be accomplished by selective periods of reverse, stopped, and antegrade flow, for example reverse flow initiated during periods when the occlusion is being pulled towards and/or entering the guide catheter. Multiple devices or sizes of devices may be used as needed to remove the occlusion or occlusions. At the conclusion of the procedure, the arterial access catheter may be exchanged for a shorter introducer sheath and a vessel closure device may be used to achieve hemostasis at the access site. Ultrasound may again be employed, in this instance to ascertain and/or ensure hemostasis. If appropriate, the ultrasound probe may be used to apply pressure at the access site until hemostasis is achieved.

[0135] In a variation of this procedure, the arterial access device is inserted through an introducer sheath which has been previously inserted into the CCA. An example of this configuration is shown in FIG. **2**. In this scenario, the arterial access device may be removed and cleared onto a table during the procedure in case the device becomes blocked and aspiration is slowed or stopped, or may be exchanged for another size or type of catheter as needed without loss of arterial access. In addition, there is no need to exchange the sheath at the conclusion of the procedure before utilizing a vessel closure device. The introducer sheath may incorporate a removable proximal extension such that during the procedure there is limited exposure of radiation to the users' hands. If used, the proximal extension may be removed prior to closure of the access site with a vessel closure device.

[0136] In yet another embodiment, the system may be used to deliver intra-arterial thrombolytic therapy, such as through a sidearm in the arterial access device **2010**. For example, thrombolytic therapy may be infused to the thrombotic occlusion **10** through the arterial access device **2010**, or through the distal catheter **2030**. In another embodiment, the system may be used to deliver intra-arterial thrombolytic therapy via a micro catheter which is inserted into the arterial access device **2010**. The micro catheter is delivered to the site of the thrombotic occlusion **10** to infuse a thrombolytic drug. The thrombolytic therapy may be delivered either in conjunction with or as an alternative to mechanical thrombectomy or aspiration.

[0137] In yet a further embodiment, the system is used to provide distal protection and/or perfusion during the procedure. In this embodiment, a perfusion catheter is inserted through the arterial access device **2010** or through the distal catheter **2030**, and positioned across the lumen and inflated at a point distal to the occlusion. The perfusion catheter may be connected to a perfusion pump to perfuse oxygenated blood or perfusion solution to the ischemic brain via a distal opening in the perfusion catheter. In an embodiment, the perfusion catheter is a balloon-tipped catheter. The balloon is inflated at a point distal to the occlusion. This balloon acts to prevent emboli from progressing distally during removal or recanalization of the occlusion. The perfusion catheter may also be connected to a flush source to perfuse proximal to the occlusion balloon via proximal ports in the perfusion catheter. This maneuver essentially provides a back pressure on the occlusion and may aid its removal.

[0138] In the instance where there is also a carotid artery stenosis which requires treatment either before or after treatment of the cerebral occlusion, an angioplasty balloon or stent may be deployed in the stenosis via the introducer sheath. If embolic protection is desirable during intervention of the carotid stenosis, the introducer sheath may have an occlusion balloon and a connection to a reverse flow line as shown in FIG. **3**, and the CAS procedure may be conducted under reverse flow embolic protection as described in co-pending U.S. patent application Ser. No. 12/176,250, which is incorporated herein by reference. The introducer sheath is then used to place the arterial access device into the ICA. Alternately, the introducer sheath may have two occlusion balloons as shown in FIG. **4**, with an opening to allow balloon angioplasty or stenting of the carotid stenosis, and subsequent introduction of devices such as a distal catheter into the ICA and cerebral circulation for treatment of the cerebral occlusion.

[0139] While this specification contains many specifics, these should not be construed as limitations on the scope of an invention that is claimed or of what may be claimed, but rather as descriptions of features specific to particular embodiments. Certain features that are described in this specification in the context of separate embodiments can also be implemented in combination in a single embodiment. Conversely, various features that are described in the context of a single embodiment can also be implemented in multiple embodiments separately or in any suitable sub-combination. Moreover, although features may be described above as acting in certain combinations and even initially claimed as such, one or more features from a claimed combination can in some cases be excised from the combination, and the claimed combination may be directed to a sub-combination or a variation of a sub-combination. Similarly, while operations are depicted in the drawings in a particular order, this should not

be understood as requiring that such operations be performed in the particular order shown or in sequential order, or that all illustrated operations be performed, to achieve desirable results.

[0140] Although embodiments of various methods and devices are described herein in detail with reference to certain versions, it should be appreciated that other versions, embodiments, methods of use, and combinations thereof are also possible. Therefore the spirit and scope of the appended claims should not be limited to the description of the embodiments contained herein.

1. A device for accessing an artery, comprising:
an arterial access device having an internal lumen and a proximal port, the arterial access device sized and shaped to be inserted directly into an arterial access site in the common carotid artery such that the lumen provides a passageway for an interventional device to be inserted via the proximal port into the carotid artery, the arterial access device having a distal portion that is configured to be inserted into an arterial pathway through the access site, and a proximal portion configured to extend outward from the access site when the distal portion is in the arterial pathway, and wherein the proximal portion has a length configured to provide a distance of between about 30 cm and 50 cm between the arterial access site and the proximal port.
2. A device as in claim 1, wherein the arterial access device comprises an introducer sheath.
3. A device as in claim 1, wherein the arterial access device is a multi-part, telescoping system.
4. A device as in claim 1, further comprising a distal catheter configured to be inserted into the arterial access device.
5. A device for treating an occlusion in a cerebral artery of a patient, comprising:
a distal catheter sized and shaped such that the distal catheter can be passed through a access site in a carotid artery to an occlusion in a cerebral artery via an arterial pathway, the catheter being configured to be passed through one or more bends in the artery without kinking, wherein at least one bend is greater than 45 degrees and is located within a predetermined distance from the arterial access site.
6. A device as in claim 5, wherein the bend is located within 5 cm of the arteriotomy.
7. A device as in claim 5, wherein the bend is located within 10 cm of the arteriotomy.
8. A device as in claim 5, wherein the bend is located within 15 cm of the arteriotomy.
9. A device as in claim 5, wherein a distance from the arteriotomy to the at least one bend is measured through a lumen of the artery.
10. A device for accessing an artery, comprising:
an arterial access device having an internal lumen and a proximal port, the arterial access device sized and

shaped to be inserted directly into an arterial access site in the common carotid artery such that the lumen provides a passageway for an interventional device to be inserted into the artery, the arterial access device having a distal portion that is configured to be inserted into the artery, and a proximal portion configured to extend outward from the arteriotomy when the distal portion is in the arterial pathway, wherein the distal portion has a section of increased flexibility, the section of increased flexibility forming at least 10% of the length of the entire distal portion.

11. A device as in claim 10, wherein the section of increased flexibility forms at least 20% of the length of the entire distal portion.
12. A device as in claim 10, wherein the section of increased flexibility forms at least 30% of the length of the entire distal portion.
13. A device for treating an occlusion in a cerebral artery of a patient, comprising:
a distal catheter sized and shaped such that the distal catheter can be passed through a access site in the carotid artery to an occlusion in a cerebral artery via an arterial pathway, wherein the working length of the catheter has a section of increased flexibility, the section of increased flexibility forming at least 10% of the working length.
14. A device as in claim 13, wherein the catheter is configured to be passed through one or more bends in the artery without kinking, wherein at least one bend is greater than 45 degrees and is located within a predetermined distance from the arterial access site.
15. A device as in claim 14, wherein the bend is located within 5 cm of the arteriotomy.
16. A device as in claim 14, wherein the bend is located within 10 cm of the arteriotomy.
17. A device as in claim 14, wherein the bend is located within 15 cm of the arteriotomy.
18. A device for treating an occlusion in a cerebral artery of a patient, comprising:
a distal catheter sized and shaped such that the distal catheter can be passed through an arteriotomy to an occlusion in a cerebral artery via an arterial pathway, wherein the occlusion in the cerebral artery is located a distance X from the location of the arteriotomy, and wherein the distal catheter has a working length less than two times the distance X.
19. A device as in claim 18, wherein the distal catheter is shaped to be inserted axially through an internal lumen of a transcervical access sheath.
20. A device as in claim 18, wherein the distance X is measured along a pathway that travels solely through the lumens of one or more arteries.

* * * * *