



US006546509B2

(12) **United States Patent**
Starr

(10) **Patent No.:** **US 6,546,509 B2**
(45) **Date of Patent:** ***Apr. 8, 2003**

(54) **METHOD AND SYSTEM FOR ADAPTIVE INTERLEAVING**

(75) Inventor: **Thomas J J Starr**, Barrington, IL (US)

(73) Assignee: **Ameritech Corporation**, Hoffman Estates, IL (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **09/884,878**

(22) Filed: **Jun. 19, 2001**

(65) **Prior Publication Data**

US 2002/0016938 A1 Feb. 7, 2002

Related U.S. Application Data

(63) Continuation of application No. 09/482,431, filed on Jan. 13, 2000, now Pat. No. 6,272,652, which is a continuation of application No. 09/062,293, filed on Apr. 19, 1998, now Pat. No. 6,067,646.

(51) **Int. Cl.⁷** **G06F 11/00**

(52) **U.S. Cl.** **714/704; 714/701**

(58) **Field of Search** 714/701, 704, 714/705, 700, 718; 711/157, 154, 127

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,623,022 A * 11/1971 Day 711/157
4,063,038 A 12/1977 Kaul et al.
4,156,867 A 5/1979 Bench et al.
4,312,070 A * 1/1982 Coombes et al. 375/356
4,394,642 A 7/1983 Currie et al.

4,691,176 A 9/1987 Hsiung et al.
4,829,526 A 5/1989 Clark et al.
4,833,693 A 5/1989 Euyboglu
4,901,319 A 2/1990 Ross
4,910,794 A 3/1990 Mahany
5,052,000 A 9/1991 Wang et al.
5,056,105 A 10/1991 Darmon et al.
5,263,051 A 11/1993 Eyuboglu
5,274,667 A 12/1993 Olmstead
5,287,556 A 2/1994 Cahill
5,335,247 A 8/1994 Olmstead
5,384,782 A 1/1995 Elms
5,425,051 A 6/1995 Mahany
5,483,676 A 1/1996 Mahany et al.
5,541,955 A 7/1996 Jacobsmeyer
5,657,342 A 8/1997 Olmstead
5,812,786 A 9/1998 Seazholtz et al.
6,067,646 A * 5/2000 Starr 714/701

* cited by examiner


Primary Examiner—Christine T. Tu

(74) *Attorney, Agent, or Firm*—Brinks Hofer Gilson & Lione

(57) **ABSTRACT**

A method a system for automatically controlling an adaptive interleaver involves monitoring performance parameters of a transmission system and controlling the adaptive interleaver in response to the performance parameters. The SNR and the data rate of the transmission system are preferably determined. The data rate is analyzed and the adaptive interleaver is adjusted in response to the data rate and the SNR. Alternatively, the BER and the data rate of the transmission system are determined. The data rate is analyzed and the adaptive interleaver is adjusted in response to the data rate and the BER. Alternatively, any one of the SNR, BER or data rate can alone be monitored and used to the adaptive interleaver. The system provides a effective system for adjusting an adaptive interleaver in response to performance parameters of a transmission system.

18 Claims, 10 Drawing Sheets






Fig. 1




Fig. 2





Fig. 3

*Fig. 4*




Fig. 5









Fig. 6

*Fig. 7*

*Fig. 8*

*Fig. 9**Fig. 10*

*Fig. 11*

1

METHOD AND SYSTEM FOR ADAPTIVE INTERLEAVING

This application is a continuation of Ser. No. 07/482,431 filed Jan. 13, 2000 now is U.S. Pat. No. 6,272,652, which is a continuation of Ser. No. 09/062,293, filed Apr. 17, 1998 now is a U.S. Pat. No. 6,067,646.

BACKGROUND

The present invention relates generally to transmission systems and more specifically to adaptive interleavers.

Interleaving is a coding technique that is commonly used to increase the performance of transmission systems by decreasing errors in the system. Interleaving rearranges the data that is to be transmitted in a given transmission thereby improving the error-correction performance of redundancy coding techniques. Interleaving increases the transmission latency of the interleaved transmissions. Latency is the time required for data to traverse the end-to-end transmission path.

In most applications, the latency associated with interleaving is only a small portion of the overall latency of the system. However, in telecommunications applications, and particularly with reference to digital subscriber lines, the latency associated with interleaving constitutes a significant portion of the overall latency. High latency can have a substantial negative impact on system performance especially when the system is operating at high data transmission rates. The impact is especially pronounced for systems where many end-to-end transmissions are required to accomplish a task, such as systems utilizing the popular TCP/IP data communications protocol to send a large file. Accordingly, telecommunications system providers generally strive to minimize latency throughout their systems while still utilizing interleaving to offset the adverse effects of errors. Thus, it is desirable to optimize the interleaving used such that only the degree of interleaving necessary to achieve a desired performance level is implemented.

Adaptive interleaving allows for different degrees of interleaving, commonly referred to as the interleave depth, to be applied to different transmissions. Adaptive interleavers are known to those skilled in the art. U.S. Pat. No. 4,901,319 describes an adaptive interleave system, including an adaptive interleaver, that attempts to correct errors that occur as a result of the fading characteristics of a radio channel. The system measures the phase error of transmissions in an effort to identify errors in the transmissions. The system utilizes a complex system and method to predict the next error occurrence based upon the measured phase error, and adjusts the adaptive interleaver in response to the prediction. However, measuring the phase error is not an effective method for identifying errors in many transmission systems. Also, a complex system for predicting the occurrence of errors and controlling an adaptive interleaver can be difficult to implement on many transmission systems.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram of the adaptive interleaver controller of a first preferred embodiment.

FIG. 2 is a more detailed block diagram of the adaptive interleaver controller of FIG. 1.

FIG. 3 is a more detailed block diagram of the adaptive interleaver controller of FIG. 1.

FIG. 4 is a more detailed block diagram of the adaptive interleaver controller of FIG. 1.

2

FIG. 5 is a more detailed block diagram of the adaptive interleaver controller of FIG. 1.

FIG. 6 is a more detailed block diagram of the adaptive interleaver controller of FIG. 1.

FIG. 7 is a flow chart of a method for controlling an adaptive interleaver of a first preferred embodiment.

FIG. 8 is a flow chart of a method for controlling an adaptive interleaver of a second preferred embodiment.

FIG. 9 is a flow chart of a method for controlling an adaptive interleaver of a third preferred embodiment.

FIG. 10 is a flow chart of a method for controlling an adaptive interleaver of a fourth preferred embodiment.

FIG. 11 is a flow chart of a method for controlling an adaptive interleaver of a fifth preferred embodiment.

DETAILED DESCRIPTION OF THE PRESENTLY PREFERRED EMBODIMENTS

The present embodiments provide an effective system for automatically controlling an adaptive interleaver in response to the performance parameters of a transmission system. Referring now to FIG. 1, a controller 5 for determining one or more performance parameters and generating an adaptive interleave control signal in response to the performance parameters is shown. The controller 5 preferably comprises means 1 for analyzing input signals, means 2 for providing an adaptive interleave control signal, means 3 for determining a first performance parameter and means 4 for determining a second performance parameter. The means 3 for determining a first performance parameter preferably comprises a first performance parameter monitor for determining a first performance parameter and generating a first input signal as known to those skilled in the art. The means 4 for determining a second performance parameter preferably comprises a second performance parameter monitor for determining a second performance parameter and generating a second input signal as known to those skilled in the art. The performance parameters are preferably chosen from the group consisting of signal to noise ratio (SNR), bit error rate (BER) and data rate.

As illustrated in the following embodiments, the system preferably determines the SNR and the data rate of the transmission system. The data rate of the system is analyzed and the adaptive interleaver is adjusted in response to the data rate and the SNR. Alternatively, the bit error rate (BER) and the data rate of the transmission system can be determined. The data rate of the system is analyzed and the adaptive interleaver is adjusted in response to the data rate and the BER. Alternatively, any one of the SNR, BER or data rate can alone be determined and used to control the adaptive interleaver. While such a system is of particular importance with regard to digital subscriber lines, those skilled in the art will appreciate that it is applicable to any system that incorporates interleaving.

By way of example, FIG. 2 shows a transmission system 10 comprising an adaptive interleaver 20, a transmitter 30, a transmission channel 35, a receiver/decoder 40 and a controller 50. The adaptive interleaver 20 interleaves data that is transmitted by the transmitter 30 over the transmission channel 35. The receiver/decoder 40 receives and decodes the interleaved data. The controller 50 determines performance parameters of the system in an effort to determine whether interleaving is beneficial and if it can be implemented. The controller also generates an adaptive interleave control signal 58 in response to the performance parameters. The adaptive interleaver preferably adjusts the interleave depth in response to the adaptive interleave control signal 58.

3

The adaptive interleaver **20** preferably comprises means for receiving a multiple bit adaptive interleave control signal and means for adjusting the interleave depth in response to the adaptive interleave control signal as known to those skilled in the art. The adaptive interleaver **20** preferably further comprises means for adaptively interleaving data at different interleave depths as known to those skilled in the art. The adaptive interleaver **20** is preferably coupled with the transmitter **30** and the controller **50**. The phrase "coupled with," as used herein, means coupled either directly or indirectly via one or more intervening elements. One example of an adaptive interleaver is shown in U.S. Pat. No. 4,901,319 which is hereby incorporated by reference.

The adaptive interleaver **20** preferably receives data and interleaves the data by rearranging the order in which the bits that comprise the data are transmitted. The interleave depth is preferably defined as the distance between bits that originally were adjacent to one another. The interleave depth is altered by varying the distance between originally adjacent bits. The data is preferably encoded through the use of coding techniques known to those skilled in the art before it is received by the adaptive interleaver **20**. Alternatively, any suitable adaptive interleaver that is responsive to a multiple bit adaptive interleave control signal, as known to those skilled in the art, can be configured for use in the present embodiments.

The transmitter **30** preferably comprises an Asymmetric Digital Subscriber Line (ADSL) transmitter as known to those skilled in the art. Alternatively, the transmitter **30** can comprise a digital transmitter for use with any form of transmission media as known to those skilled in the art. Alternatively, the transmitter **30** can comprise any transmitter for use with any form of transmission media as known to those skilled in the art. The transmitter **30** is preferably coupled with the adaptive interleaver **20**, the data rate monitor **60** and the transmission channel **35**.

The transmitter **30** modulates data for transmission to the receiver/decoder **40** via the transmission channel **35** as known to those skilled in the art. The transmitter **30** can preferably transmit data at different data rates as known to those skilled in the art. The capacity of the transmission channel **35** is one common factor that can be used as a basis for adjusting the data rate. The capacity of the transmission channel **35** typically depends on factors including the following: the distance a transmission has to travel; the wire gauge of the transmission channel; the number of bridged-taps on the transmission channel; the temperature of the transmission channel; splice loss of the transmission channel; noise present in the transmission channel; and the precision of the transmitter and receiver. While many of these factors are not directly measurable, their cumulative effect may be monitored by measuring one or both of the SNR and BER of the system. Thus, the data rate can be adapted in response to the SNR or BER.

The transmitter **30** typically adapts the data rate by altering the time allowed for the transmission of a symbol comprising a number of bits. Accordingly, a greater or lesser number of bits can be transmitted within a given time interval depending upon the alterations. Alternatively, the data rate can be altered by modulating a greater or lesser number of bits into each transmission. For example, increasing the number of usable points in a Quadrature Amplitude Modulation (QAM) constellation results in the modulation of more bits in each transmission. When the data rate is increased through either of these methods, the SNR of the system is generally decreased. A decrease in the SNR generally results in an increase in the BER when the data

4

rate increases or is unchanged. Thus, to maintain a given BER, there is an upper limit for the data rate for a particular transmission channel. Accordingly, by monitoring the SNR and BER, the data rate can be adapted, through the use of the methods described above, to the maximum data rate possible while maintaining an acceptable BER. The data rate can be adapted once at system start-up, or continuously as known to those skilled in the art.

The transmission channel **35** preferably comprises twisted-pair conductive wire as known to those skilled in the art. Alternatively, the transmission channel can comprise coaxial cable, optical fiber, free-space laser, radio or any other type of transmission media as known to those skilled in the art. The transmission channel **35** is preferably coupled with the transmitter **30** and the receiver/decoder **40**.

The receiver/decoder **40** preferably comprises an ADSL receiver, an adaptive de-interleaver and a sequential decoder as known to those skilled in the art. Alternatively, the receiver/decoder **40** can comprise a digital receiver/decoder for use with any type of transmission media as known to those skilled in the art. Alternatively, the receiver/decoder **40** can comprise any type of receiver/decoder for use with any type of transmission media as known to those skilled in the art. For example, the receiver/decoder **40** can employ a Reed Solomon decoder or any other suitable error correcting decoder as known to those skilled in the art. The receiver/decoder **40** is preferably coupled with the transmission channel **35** and the signal to noise ratio monitor **70**.

The receiver/decoder **40** receives and demodulates the data from the transmitter **30**. After demodulation, the receiver/decoder **40** de-interleaves the data and utilizes decoding techniques known to those skilled in the art to detect and correct errors in the data. For example, the receiver/decoder **40** can analyze data including redundant bits that are generated by an encoder prior transmission, to determine whether any data was corrupted and thus requires correction.

The controller **50** preferably comprises a data rate monitor **60**, a signal to noise ratio monitor **70**, means **54** for analyzing input signals and means **56** for providing an adaptive interleave control signal. The data rate monitor **60** preferably comprises a monitor for determining the data rate of the system **10** as known to those skilled in the art. The data rate monitor **60** is preferably coupled with the transmitter **30** and the controller **50**. The data rate can be determined by counting the number of bits, bytes, symbols, blocks, frames, cells, or packets sent per time interval as known to those skilled in the art. Alternatively, the data rate can be inferred from the frequency of the master clock signal used by the transmitter or from the symbol rate detected by the receiver/decoder **40** as known to those skilled in the art. Alternatively, for manually controlled systems, the value in the data register holding the data rate that is set by the operator can be directly accessed by the data rate monitor **60** to determine the data rate. Alternatively, the data rate can be determined through a variety of other techniques, and any suitable method for determining the data rate can be adapted for use in the presently preferred system. Averaging many measurements of the data rate can be performed to improve the accuracy of the current data rate calculations as known to those skilled in the art.

The data rate monitor **60** determines the data rate and generates an input signal **68** that preferably varies as a function of the data rate. Alternatively, the input signal **68** can take many forms. The input signal **68** can be based in-whole or in-part on the data rate. The input signal **68** can

5

be analog or digital and linear or non-linear as known to those skilled in the art. Alternatively, the input signal **68** can be binary such that input signal **68** is greater than or less than a threshold value based upon the data rate as known to those skilled in the art. The data rate monitor **60** preferably determines the data rate and continuously generates the input signal **68**. Alternatively, the data rate monitor **60** can determine the data rate and generate the input signal **68** in a sampled fashion on a random or non-random basis.

The signal to noise ratio monitor **70** preferably comprises a monitor for determining the SNR as known to those skilled in the art. The SNR monitor **70** is preferably coupled with the transmission channel **35** and the controller **50**. SNR is preferably defined as the ratio of average signal power to average noise power. The signal power can be determined by measuring the maximum amplitude and phase deviation of all received data prior to demodulation. The noise power can be determined by measuring the amplitude and phase distance between adjacent points in the modulation constellation as known to those skilled in the art. Alternatively, the SNR can be determined through a variety of other techniques, and any suitable method of determining the SNR can be adapted for use in the presently preferred system. Averaging many measurements of SNR can be performed to improve the accuracy of the current SNR calculations as known to those skilled in the art.

The signal to noise ratio monitor **70** preferably determines the SNR and generates an input signal **78** that varies as a function of the SNR. Alternatively, the input signal **78** can take many forms. The input signal **78** can be based in-whole or in-part on the SNR. The input signal **78** can be analog or digital and linear or non-linear as known to those skilled in the art. Alternatively, the input signal **78** can be binary such that the input signal **78** is greater than or less than a threshold value based upon the SNR as known to those skilled in the art. The SNR monitor **70** preferably determines the SNR and continuously generates the input signal **78**. Alternatively, the SNR monitor **70** can determine the SNR and generate the input signal **78** in a sampled fashion on a random or non-random basis.

The means **54** for analyzing input signals preferably comprises means for determining whether the current data rate satisfies a threshold, based upon an analysis of the input signal **68**. Alternatively, the means **54** for analyzing input signals can comprise means for determining the current data rate based upon an analysis of the input signal **68**. Alternatively, the means **54** for analyzing input signals can analyze both input signals **68**, **78**. The means **54** for analyzing input signals is preferably implemented in computer readable program code written in any suitable programming language and implemented on an analog or a digital computer utilizing any suitable operating system. The means **54** for analyzing input signals can also be implemented through the use of hardware in the form of a hardwired computer, an integrated circuit, or a combination of hardware and computer readable program code.

The means **56** for providing an adaptive interleave control signal preferably comprises means for providing the input signal **78** as it is received from the SNR monitor **70**. Accordingly, the adaptive interleave control signal **58** is preferably equivalent to the received input signal **78**. Alternatively, the adaptive interleave control signal **58** can take many forms. The adaptive interleave control signal can be based in-whole or in-part on one or both of the input signals **68**, **78**. The adaptive interleave control signal **58** can be analog or digital and linear or non-linear as known to those skilled in the art. Alternatively, the adaptive interleave

6

control signal **58** can be binary such that the adaptive interleave control signal produced is greater than or less than a threshold value based upon one or both of the input signals **68**, **78** as known to those skilled in the art. The means **56** for providing an adaptive interleave control signal is preferably implemented in computer readable program code written in any suitable programming language and implemented on an analog or a digital computer utilizing any suitable operating system. The means **56** for providing an adaptive interleave control signal can also be implemented through the use of hardware in the form of a hardwired computer, an integrated circuit, or a combination of hardware and computer readable program code.

Referring now to FIG. 3, a transmission system **100** comprising the adaptive interleaver **20**, the transmitter **30**, the transmission channel **35**, the receiver/decoder **40** and a controller **150** according to an alternate embodiment is shown. The adaptive interleaver **20**, transmitter **30**, transmission channel **35** and receiver/decoder **40** are all the same as described above.

The controller **150** preferably comprises a data rate monitor **60**, a bit error rate monitor **170**, means **154** for analyzing input signals and means **156** for providing an adaptive interleave control signal. The data rate monitor **60** is the same as described above. The bit error rate monitor **170** preferably comprises a monitor for determining BER as known to those skilled in the art. The bit error rate monitor **170** is preferably coupled with the receiver/decoder **40** and the controller **150**. BER is preferably defined as the relative frequency of error bits to received bits. The BER is preferably determined through the use of a cyclic redundancy code (CRC) in the encoded symbols. A CRC enables a bit error rate monitor to determine when errors in the decoded symbols occur. By monitoring the errors identified through the use of the CRC over a period of time, the BER of the system can be determined. Alternatively, BER can be determined through a variety of other techniques, and any suitable method of determining BER can be adapted for use in the presently preferred system. Averaging many measurements of BER can be performed to improve the accuracy of the current BER calculations as known to those skilled in the art.

The bit error rate monitor **170** preferably generates an input signal **178** that varies as a function of the BER. Alternatively, the input signal **178** can take many forms. The input signal **178** can be based in-whole or in-part on the BER. The input signal **178** can be analog or digital and linear or non-linear as known to those skilled in the art. Alternatively, the input signal **178** can be binary such that the input signal **178** is greater than or less than a threshold value based upon the BER as known to those skilled in the art. The BER monitor **170** preferably determines the BER and continuously generates the input signal **178**. Alternatively, the BER monitor **170** can determine the BER and generate the input signal **178** in a sampled fashion on a random or non-random basis.

The means **154** for analyzing input signals preferably comprises means for determining whether the current data rate exceeds a predetermined threshold, based upon an analysis of the input signal **68**. Alternatively, the means **154** for analyzing input signals can comprise means for determining the current data rate based upon an analysis of the input signal **68**. Alternatively, the means **154** for analyzing input signals can analyze both of the input signals **68**, **178**. The means **154** for analyzing input signals is preferably implemented in computer readable program code written in any suitable programming language and implemented on an

analog or a digital computer utilizing any suitable operating system. The means **154** for analyzing input signals can also be implemented through the use of hardware in the form of a hardwired computer, an integrated circuit, or a combination of hardware and computer readable program code.

The means **156** for providing an adaptive interleave control signal preferably comprises means for providing the input signal **178** as it is received from the BER monitor **170**. Accordingly, the adaptive interleave control signal **158** is preferably equivalent to the received input signal **178**. Alternatively, the adaptive interleave control signal **158** can take many forms. The adaptive interleave control signal **158** can be based in-whole or in-part on one or both of the input signals **68**, **178**. The adaptive interleave control signal **158** can be analog or digital and linear or non-linear as known to those skilled in the art. Alternatively, the adaptive interleave control signal **158** can be binary such that the adaptive interleave control signal **158** is greater than or less than a threshold value based upon one or both of the input signals **68**, **178** as known to those skilled in the art. The means **156** for providing an adaptive interleave control signal in response to the input signals is preferably implemented in computer readable program code written in any suitable programming language and implemented on an analog or a digital computer utilizing any suitable operating system. The means **156** for providing an adaptive interleave control signal in response to the input signals can also be implemented through the use of hardware in the form of a hardwired computer, an integrated circuit, or a combination of hardware and computer readable program code.

While the controller **50**, **150** and adaptive interleaver **20** are preferably implemented as separate elements as shown in FIGS. 1 and 2, they can alternatively be implemented as a single element comprising software, hardware or a combination thereof as described herein and known to those skilled in the art.

Referring now to FIG. 4, a transmission system **180** comprising the adaptive interleaver **20**, the transmitter **30**, the transmission channel **35**, the receiver/decoder **40** and a controller **80** is shown. The adaptive interleaver **20**, transmitter **30**, transmission channel **35** and receiver/decoder **40** are all the same as described above. The controller **80** preferably comprises a signal to noise ratio monitor **72** as described herein. The signal to noise ratio monitor **72** generates a multiple bit adaptive interleave control signal **74** that preferably varies as a function of the SNR. The adaptive interleave control signal **74** can be based in-whole or in-part on the SNR. The adaptive interleave control signal **74** can be analog or digital and linear or non-linear as known to those skilled in the art. Alternatively, the adaptive interleave control signal **74** can be binary such that the adaptive interleave control signal produced is greater than or less than a threshold value based upon the SNR as known to those skilled in the art. The controller **80** is preferably coupled with to the adaptive interleaver **20** such that the adaptive interleave control signal **74** is supplied directly to the adaptive interleaver **20**. The adaptive interleave control signal **74** is preferably utilized by the adaptive interleaver **20** to control the interleave depth to generate an adaptively interleaved signal.

Referring now to FIG. 5, a transmission system **190** comprising the adaptive interleaver **20**, the transmitter **30**, the transmission channel **35**, the receiver/decoder **40** and a controller **90** is shown. The adaptive interleaver **20**, transmitter **30**, transmission channel **35** and receiver/decoder **40** are all the same as described above. The controller **90** preferably comprises a bit error rate monitor **172** as

described herein. The bit error rate monitor **172** generates a multiple bit adaptive interleave control signal **174** that preferably varies as a function of the BER. The adaptive interleave control signal **174** can be based in-whole or in-part on the BER. The adaptive interleave control signal **174** can be analog or digital and linear or non-linear as known to those skilled in the art. Alternatively, the adaptive interleave control signal **174** can be binary such that the adaptive interleave control signal produced is greater than or less than a threshold value based upon the BER as known to those skilled in the art. The controller **90** is preferably coupled with the adaptive interleaver **20** such that the adaptive interleave control signal **174** is supplied directly to the adaptive interleaver **20**. The adaptive interleave control signal **174** is preferably utilized by the adaptive interleaver **20** to control the interleave depth to generate an adaptively interleaved signal.

Referring now to FIG. 6, a transmission system **200** comprising the adaptive interleaver **20**, the transmitter **30**, the transmission channel **35**, the receiver/decoder **40** and a controller **210** is shown. The adaptive interleaver **20**, transmitter **30**, transmission channel **35** and receiver/decoder **40** are all the same as described above. The controller **210** preferably comprises a data rate monitor **202** as described herein. The data rate monitor **202** generates a multiple bit adaptive interleave control signal **204** that preferably varies as a function of the data rate. The adaptive interleave control signal **204** can be based in-whole or in-part on the data rate. The adaptive interleave control signal **204** can be analog or digital and linear or non-linear as known to those skilled in the art. Alternatively, the adaptive interleave control signal **204** can be binary such that the adaptive interleave control signal produced is greater than or less than a threshold value based upon the data rate. The controller **210** is preferably coupled with the adaptive interleaver **20** such that the adaptive interleave control signal **204** is supplied directly to the adaptive interleaver **20**. The adaptive interleave control signal **204** is preferably utilized by the adaptive interleaver **20** to control the interleave depth to generate an adaptively interleaved signal.

The system shown in FIG. 2 can be used to implement the method **300** shown in FIG. 7. The data rate monitor **60** determines the data rate (step **302**, FIG. 7) of the transmission system **10**. The data rate monitor **60** generates an input signal **68** (step **304**) that varies as a function of the data rate. The signal to noise ratio monitor **70** determines a SNR (step **306**) of the system **10**. The signal to noise ratio monitor **70** generates an input signal **78** (step **308**) that varies as a function of the SNR. The controller **50** analyzes the first input signal **68** (step **310**) and determines whether the data rate exceeds a predetermined threshold. The controller **50** provides an adaptive interleave control signal **58** (step **312**) in response to the input signals **68**, **78**.

The system shown in FIG. 3 can be used to implement the method **320** shown in FIG. 8. The data rate monitor **60** determines the data rate (step **322**, FIG. 8) of the transmission system **100**. The data rate monitor **60** generates a first input signal (step **324**) that varies as a function of the data rate. The bit error rate monitor **170** determines a BER (step **326**) for the transmission system **100**. The bit error rate monitor **170** generates a second input signal (step **328**) that varies as a function of the BER. The controller **150** analyzes the first input signal **68** (step **330**) and determines whether the data rate exceeds a predetermined threshold. The controller provides an adaptive interleave control signal (step **332**) in response to the input signals **68**, **178**.

In a preferred embodiment, the predetermined threshold is determined in relation to the data rate. When the data rate is

above a certain level, the system cannot afford the decoder the additional time needed to de-interleave the interleaved data. Thus, for data rates above a certain level, interleaving imposes an unacceptable time delay on the transmissions. Therefore, when the data rate exceeds the predetermined threshold, interleaving is preferably disabled. When the controller **50, 150** determines that the data rate exceeds the predetermined threshold, the controller **50, 150** preferably generates an adaptive interleave control signal **58, 158** (respectively) that controls the adaptive interleaver **20** such that no interleaving is implemented by the adaptive interleaver **20**. Alternatively, when the data rate exceeds the predetermined threshold, the controller **50, 150** can cease generating an adaptive interleave control signal such that no interleaving is implemented by the adaptive interleaver **20**. Thus, interleaving is only implemented when the data rate is below a certain level.

Alternatively, if the data rate is below the predetermined threshold, the controller **50, 150** preferably generates an adaptive interleave control signal **58, 158** that controls the adaptive interleaver **20** such that interleaving is implemented. The adaptive interleave control signal **58, 158** preferably causes the adaptive interleaver **20** to implement an interleave depth that is proportional to the SNR, BER, data rate or combination thereof. Alternatively, the interleave depth can be inversely proportional to the SNR, BER, data rate or combination thereof. Alternatively, the adaptive interleave control signal **58, 158** can cause the adaptive interleaver **20** to implement a number of different interleave depths depending upon the SNR, BER, data rate or combination thereof. For example, the controller **50, 150** can implement five different graduated interleave depths in response to the SNR or BER, assuming that the data rate is high enough to allow for such interleaving. Each of the different graduated interleave depths is implemented when the SNR or BER is within a predetermined range of values.

The system of FIG. 4 can be used to implement the method **340** of FIG. 9. The signal to noise ratio monitor **72** determines a SNR (step **342**) of the transmission system **180**. The signal to noise ratio monitor **72** generates an adaptive interleave control signal **74** (step **344**) that preferably varies as a function of the SNR. The adaptive interleaver **20** receives the adaptive interleave control signal and preferably adapts an interleave depth in response to the adaptive interleave control signal **74**.

The system of FIG. 5 can be used to implement the method **350** of FIG. 10. The bit error rate monitor **172** determines a BER (step **352**) of the transmission system **190**. The bit error rate monitor **172** generates an adaptive interleave control signal **174** (step **354**) that preferably varies as a function of the BER. The adaptive interleaver **20** receives the adaptive interleave control signal preferably adapts an interleave depth in response to the adaptive interleave control signal **174**.

The system of FIG. 6 can be used to implement the method **360** of FIG. 11. The data rate monitor **202** determines a data rate (step **362**) of the system **200**. The data rate monitor **202** generates an adaptive interleave control signal **204** (step **364**) that preferably varies as a function of the data rate. The adaptive interleaver **20** receives the adaptive interleave control signal and preferably adapts an interleave depth in response to the adaptive interleave control signal **204**.

It is to be understood that during operation, the interleave depth implemented by the adaptive interleaver **20** (FIGS. 2, 3, 4, 5 and 6) is generally communicated to the receiver/

decoder **40** at the other end of the transmission channel **35** as known to those skilled in the art. If the interleave depth is adjusted solely as a function of the data rate, both the adaptive interleaver **20** and the receiver/decoder **40** can monitor the current data rate, and can synchronize the interleaving depth through the use of the same interleave depth control rules as known to those skilled in the art. However, if the SNR or the BER is used to determine the interleave depth, additional mechanisms can be used to assure that the interleave depth implemented by the adaptive interleaver **20** matches the interleave depth of a de-interleaver during the decoding process as known to those skilled in the art. Accordingly, the current interleave depth being used by the adaptive interleaver **20** can be transmitted to the receiver/decoder **40** for use in the decoding process. The components and methods required to perform such a transmission and synchronize the encoding and decoding processes are well known to those skilled in the art.

It is to be understood that a wide range of changes and modifications to the embodiments described above will be apparent to those skilled in the art and are contemplated. It is therefore intended that the foregoing detailed description be regarded as illustrative rather than limiting, and that it be understood that it is the following claims, including all equivalents, that are intended to define the spirit and scope of the invention.

I claim:

1. A controller for an adaptive interleaver comprising:

a first monitor operative to receive a first input signal and generate a first performance parameter signal;

a second monitor operative to receive a second input signal and generate a second performance parameter signal;

controller means for providing a control signal in response to the first and second performance parameter signals;

wherein the first and second performance parameter signals are selected from the group consisting of a signal to noise ratio signal, a bit error rate signal, and a data rate signal.

2. The invention of claim 1, wherein the controller means comprises computer readable program code.

3. The invention of claim 1, wherein the controller means comprises hardware.

4. The invention of claim 1, wherein the controller means is operative to determine whether the first and second performance parameter signals exceed a predetermined threshold.

5. The invention of claim 1, wherein the first performance parameter signal is indicative of a first performance parameter and wherein the controller means is operative to determine whether the first performance parameter exceeds a predetermined threshold.

6. The invention of claim 1, wherein the second performance parameter signal is indicative of a second performance parameter and wherein the controller means is operative to determine whether the second performance parameter exceeds a predetermined threshold.

7. The invention of claim 1, further comprising an adaptive interleaver coupled with the controller, the adaptive interleaver being operative to receive the control signal.

8. A transmission system comprising:

a transmission channel;

a transmitter coupled with the transmission channel;

an adaptive interleaver coupled with the transmitter;

11

- a receiver/decoder coupled with the transmission channel;
and
a data rate monitor coupled with the transmitter, the data
rate monitor being operative to generate a first input
signal;
a performance parameter monitor coupled with the
receiver/decoder, the performance parameter monitor
being operative to monitor a performance parameter
and generate a second input signal, wherein the per-
formance parameter is selected from the group consist-
ing of signal to noise ratio and bit error rate; and
a controller coupled with the adaptive interleaver, the
controller being operative to receive the first and sec-
ond input signals and generate an adaptive interleave
control signal in response to the first and second input
signals.
9. The invention of claim 8, wherein the transmission
channel comprises a fiber optic channel.
10. The invention of claim 8, wherein the transmission
channel comprises a conductive wire channel.
11. The invention of claim 8, wherein the first input signal
is indicative of a data rate and wherein the controller is
further operative to determine whether the data rate exceeds
a predetermined threshold.
12. The invention of claim 8, wherein the second input
signal is indicative of a signal to noise ratio and wherein the
controller is further operative to determine whether the
signal to noise ratio exceeds a predetermined threshold.
13. The invention of claim 8, wherein the second input
signal is indicative of a bit error rate and wherein the
controller is further operative to determine whether the bit
error rate exceeds a predetermined threshold.

12

14. A transmission system comprising:
a transmission channel;
a transmitter coupled with the transmission channel;
an adaptive interleaver coupled with the transmitter;
a receiver/decoder coupled with the transmission channel;
and
a performance parameter monitor coupled with the
receiver/decoder, the performance parameter monitor
being operative to monitor a performance parameter
and generate an input signal, wherein the performance
parameter is selected from the group consisting of
signal to noise ratio and bit error rate; and
a controller coupled with the adaptive interleaver, the
controller being operative to receive the input signal
and generate an adaptive interleave control signal in
response to the input signal.
15. The invention of claim 14, wherein the transmission
channel comprises a fiber optic channel.
16. The invention of claim 14, wherein the transmission
channel comprises a conductive wire channel.
17. The invention of claim 14, wherein the input signal is
indicative of a signal to noise ratio and wherein the con-
troller is further operative to determine whether the signal to
noise ratio exceeds a predetermined threshold.
18. The invention of claim 14, wherein the input signal is
indicative of a bit error rate and wherein the controller is
further operative to determine whether the bit error rate
exceeds a predetermined threshold.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 6,546,509 B2
DATED : April 8, 2003
INVENTOR(S) : Thomas J. J. Starr

Page 1 of 1


It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Title page,

Item [63], **Related U.S. Application Data**, delete "Apr. 19, 1998," and substitute -- Apr. 17, 1998, -- in its place.

Signed and Sealed this

Twenty-third Day of March, 2004

A handwritten signature in black ink, reading "Jon W. Dudas". The signature is stylized, with a large loop for the "J" and a cursive "Dudas".

JON W. DUDAS
Acting Director of the United States Patent and Trademark Office