



US009647918B2

(12) **United States Patent**
Raleigh et al.

(10) **Patent No.:** **US 9,647,918 B2**

(45) **Date of Patent:** **May 9, 2017**

(54) **MOBILE DEVICE AND METHOD
ATTRIBUTING MEDIA SERVICES
NETWORK USAGE TO REQUESTING
APPLICATION**

(58) **Field of Classification Search**

None

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,131,020 A 7/1992 Liebesny et al.

5,283,904 A 2/1994 Carson et al.

(Continued)

FOREIGN PATENT DOCUMENTS

CA 2688553 12/2008

CN 1310401 A 2/2000

(Continued)

OTHER PUBLICATIONS

3rd Generation Partnership Project, "Technical Specification Group Services and System Aspects; General Packet Radio Service (GPRS) Enhancements for Evolved Universal Terrestrial Radio Access Network (E-UTRAN) Access," Release 8, Document No. 3GPP TS 23.401, V8.4.0, Dec. 2008.

(Continued)

Primary Examiner — Mounir Moutaouakil

(74) *Attorney, Agent, or Firm* — James E. Harris

(57) **ABSTRACT**

A wireless end-user device has a wireless modem, a network stack configurable to receive and transmit data via the modem and a wireless network, and two Application Programming Interfaces (APIs) available to device applications. The first API allows applications to open and use data flows via the network stack. The second API allows applications to make data transfer requests for media objects associated with network resource identifiers. The second API prompts a media service manager to manage network data transfers for the media object via the network stack. A service classification agent associates wireless network data usage for the media object network data transfers with the device application making the request.

19 Claims, 40 Drawing Sheets

(71) Applicant: **Headwater Partners I LLC**, Tyler, TX (US)

(72) Inventors: **Gregory G. Raleigh**, Woodside, CA (US); **Jeffrey Green**, Sunnyvale, CA (US); **James Lavine**, Corte Madera, CA (US); **Vien-Phuong Nguyen**, Newark, CA (US)

(73) Assignee: **Headwater Research LLC**, Tyler, TX (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **15/227,814**

(22) Filed: **Aug. 3, 2016**

(65) **Prior Publication Data**


US 2016/0344604 A1 Nov. 24, 2016

Related U.S. Application Data

(63) Continuation of application No. 14/339,110, filed on Jul. 23, 2014, which is a continuation of application (Continued)

(51) **Int. Cl.**
H04L 12/26 (2006.01)
H04L 12/801 (2013.01)
(Continued)

(52) **U.S. Cl.**
CPC **H04L 43/0876** (2013.01); **G06F 9/54** (2013.01); **H04L 41/0896** (2013.01);
(Continued)



Related U.S. Application Data

- No. 14/338,807, filed on Jul. 23, 2014, now Pat. No. 9,094,311, which is a continuation of application No. 14/098,527, filed on Dec. 5, 2013, now Pat. No. 9,270,559, which is a continuation of application No. 13/374,959, filed on Jan. 24, 2012, now Pat. No. 8,606,911, which is a continuation-in-part of application No. 12/695,019, filed on Jan. 27, 2010, now Pat. No. 8,275,830, and a continuation-in-part of application No. 12/695,020, filed on Jan. 27, 2010, now Pat. No. 8,406,748, and a continuation-in-part of application No. 12/694,445, filed on Jan. 27, 2010, now Pat. No. 8,391,834, and a continuation-in-part of application No. 12/694,451, filed on Jan. 27, 2010, now Pat. No. 8,548,428, and a continuation-in-part of application No. 12/694,455, filed on Jan. 27, 2010, now Pat. No. 8,402,111, and a continuation-in-part of application No. 12/695,980, filed on Jan. 28, 2010, now Pat. No. 8,340,634, and a continuation-in-part of application No. 13/229,580, filed on Sep. 9, 2011, now Pat. No. 8,626,115, and a continuation-in-part of application No. 13/237,827, filed on Sep. 20, 2011, now Pat. No. 8,832,777, and a continuation-in-part of application No. 13/239,321, filed on Sep. 21, 2011, now Pat. No. 8,898,293, and a continuation-in-part of application No. 13/248,028, filed on Sep. 28, 2011, now Pat. No. 8,924,469, and a continuation-in-part of application No. 13/247,998, filed on Sep. 28, 2011, now Pat. No. 8,725,123, and a continuation-in-part of application No. 13/248,025, filed on Sep. 28, 2011, now Pat. No. 8,924,543, and a continuation-in-part of application No. 13/253,013, filed on Oct. 4, 2011, now Pat. No. 8,745,191, and a continuation-in-part of application No. 13/309,556, filed on Dec. 1, 2011, now Pat. No. 8,893,009, and a continuation-in-part of application No. 13/309,463, filed on Dec. 1, 2011, now Pat. No. 8,793,758, and a continuation-in-part of application No. 13/134,028, filed on May 25, 2011, now Pat. No. 8,589,541, and a continuation-in-part of application No. 13/134,005, filed on May 25, 2011, now Pat. No. 8,635,335, and a continuation-in-part of application No. 12/695,021, filed on Jan. 27, 2010, now Pat. No. 8,346,225, which is a continuation-in-part of application No. 12/380,780, filed on Mar. 2, 2009, now Pat. No. 8,839,388, said application No. 13/134,005 is a continuation-in-part of application No. 12/380,780, filed on Mar. 2, 2009, now Pat. No. 8,839,388, and a continuation-in-part of application No. 12/380,788, filed on Mar. 2, 2009, now Pat. No. 8,321,526.
- (60) Provisional application No. 61/435,564, filed on Jan. 24, 2011, provisional application No. 61/472,606, filed on Apr. 6, 2011, provisional application No. 61/550,906, filed on Oct. 24, 2011, provisional application No. 61/589,830, filed on Jan. 23, 2012, provisional application No. 61/264,126, filed on Nov. 24, 2009, provisional application No. 61/270,353, filed on Jul. 6, 2009, provisional application No. 61/275,208, filed on Aug. 25, 2009, provisional application No. 61/237,753, filed on Aug. 28, 2009, provisional application No. 61/264,120, filed on Nov. 24, 2009, provisional application No. 61/348,022, filed on May 25, 2010, provisional application No. 61/381,159, filed on Sep. 9, 2010, provisional

application No. 61/381,162, filed on Sep. 9, 2010, provisional application No. 61/384,456, filed on Sep. 20, 2010, provisional application No. 61/389,547, filed on Oct. 4, 2010, provisional application No. 61/385,020, filed on Sep. 21, 2010, provisional application No. 61/387,243, filed on Sep. 28, 2010, provisional application No. 61/387,247, filed on Sep. 28, 2010, provisional application No. 61/407,358, filed on Oct. 27, 2010, provisional application No. 61/418,507, filed on Dec. 1, 2010, provisional application No. 61/418,509, filed on Dec. 1, 2010, provisional application No. 61/420,727, filed on Dec. 7, 2010, provisional application No. 61/422,565, filed on Dec. 13, 2010, provisional application No. 61/422,572, filed on Dec. 13, 2010, provisional application No. 61/422,574, filed on Dec. 13, 2010, provisional application No. 61/252,151, filed on Oct. 15, 2009, provisional application No. 61/252,153, filed on Oct. 15, 2009, provisional application No. 61/206,354, filed on Jan. 28, 2009, provisional application No. 61/206,944, filed on Feb. 4, 2009, provisional application No. 61/207,393, filed on Feb. 10, 2009, provisional application No. 61/207,739, filed on Feb. 13, 2009.

- (51) **Int. Cl.**
H04L 12/851 (2013.01)
H04W 28/02 (2009.01)
H04L 12/24 (2006.01)
G06F 9/54 (2006.01)
- (52) **U.S. Cl.**
 CPC *H04L 41/5041* (2013.01); *H04L 47/14* (2013.01); *H04L 47/2441* (2013.01); *H04W 28/0268* (2013.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,325,532	A	6/1994	Crosswy et al.
5,572,528	A	11/1996	Shuen
5,577,100	A	11/1996	McGregor et al.
5,594,777	A	1/1997	Makkonen et al.
5,617,539	A	4/1997	Ludwig et al.
5,630,159	A	5/1997	Zancho
5,633,484	A	5/1997	Zancho et al.
5,633,868	A	5/1997	Baldwin et al.
5,754,953	A	5/1998	Briancon et al.
5,774,532	A	6/1998	Gottlieb et al.
5,794,142	A	8/1998	Vanttila et al.
5,814,798	A	9/1998	Zancho
5,889,477	A	3/1999	Fastenrath
5,892,900	A	4/1999	Ginter et al.
5,903,845	A	5/1999	Buhrmann et al.
5,915,008	A	6/1999	Dulman
5,933,778	A	8/1999	Buhrmann et al.
5,940,472	A	8/1999	Newman et al.
5,974,439	A	10/1999	Bollella
5,983,270	A	11/1999	Abraham et al.
6,035,281	A	3/2000	Crosskey et al.
6,038,452	A	3/2000	Strawczynski et al.
6,038,540	A	3/2000	Krist et al.
6,047,268	A	4/2000	Bartoli et al.
6,058,434	A	5/2000	Wilt et al.
6,061,571	A	5/2000	Tamura
6,064,878	A	5/2000	Denker et al.
6,078,953	A	6/2000	Vaid et al.
6,081,591	A	6/2000	Skoog
6,098,878	A	8/2000	Dent et al.
6,104,700	A	8/2000	Haddock et al.
6,115,823	A	9/2000	Velasco et al.
6,119,933	A	9/2000	Wong et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,125,391 A	9/2000	Meltzer et al.	6,839,340 B1	1/2005	Voit et al.
6,141,565 A	10/2000	Feuerstein et al.	6,873,988 B2	3/2005	Herrmann et al.
6,141,686 A	10/2000	Jackowski et al.	6,876,653 B2	4/2005	Ambe et al.
6,148,336 A	11/2000	Thomas et al.	6,879,825 B1	4/2005	Daly
6,154,738 A	11/2000	Call	6,882,718 B1	4/2005	Smith
6,157,636 A	12/2000	Voit et al.	6,885,997 B1	4/2005	Roberts
6,185,576 B1	2/2001	McIntosh	6,901,440 B1	5/2005	Bimm et al.
6,198,915 B1	3/2001	McGregor et al.	6,920,455 B1	7/2005	Weschler
6,226,277 B1	5/2001	Chuah	6,922,562 B2	7/2005	Ward et al.
6,263,055 B1	7/2001	Garland et al.	6,928,280 B1	8/2005	Xanthos et al.
6,292,828 B1	9/2001	Williams	6,934,249 B1	8/2005	Bertin et al.
6,317,584 B1	11/2001	Abu-Amara et al.	6,934,751 B2	8/2005	Jayapalan et al.
6,381,316 B2	4/2002	Joyce et al.	6,947,723 B1	9/2005	Gurnani et al.
6,393,014 B1	5/2002	Daly et al.	6,947,985 B2	9/2005	Hegli et al.
6,397,259 B1	5/2002	Lincke et al.	6,952,428 B1	10/2005	Necka et al.
6,401,113 B2	6/2002	Lazaridis et al.	6,957,067 B1	10/2005	Iyer et al.
6,418,147 B1	7/2002	Wiedeman	6,959,393 B2	10/2005	Hollis et al.
6,438,575 B1	8/2002	Khan et al.	6,965,667 B2	11/2005	Trabandt et al.
6,445,777 B1	9/2002	Clark	6,965,872 B1	11/2005	Grdina
6,449,479 B1	9/2002	Sanchez	6,967,958 B2	11/2005	Ono et al.
6,477,670 B1	11/2002	Ahmadvand	6,970,692 B2	11/2005	Tysor
6,502,131 B1	12/2002	Vaid et al.	6,982,733 B1	1/2006	McNally et al.
6,505,114 B2	1/2003	Luciani	6,983,370 B2	1/2006	Eaton et al.
6,510,152 B1	1/2003	Gerszberg et al.	6,996,076 B1	2/2006	Forbes et al.
6,532,235 B1	3/2003	Benson et al.	6,996,393 B2	2/2006	Pyhalamm et al.
6,532,579 B2	3/2003	Sato et al.	6,998,985 B2	2/2006	Reisman et al.
6,535,855 B1	3/2003	Cahill et al.	7,002,920 B1	2/2006	Ayyagari et al.
6,539,082 B1	3/2003	Lowe et al.	7,007,295 B1	2/2006	Rose et al.
6,542,500 B1	4/2003	Gerszberg et al.	7,013,469 B2	3/2006	Smith et al.
6,542,992 B1	4/2003	Peirce et al.	7,017,189 B1	3/2006	DeMello et al.
6,546,016 B1	4/2003	Gerszberg et al.	7,024,200 B2	4/2006	McKenna et al.
6,563,806 B1	5/2003	Yano et al.	7,024,460 B2	4/2006	Koopmas et al.
6,570,974 B1	5/2003	Gerszberg et al.	7,027,055 B2	4/2006	Anderson et al.
6,574,321 B1	6/2003	Cox et al.	7,027,408 B2	4/2006	Nabkel et al.
6,574,465 B2	6/2003	Marsh et al.	7,032,072 B1	4/2006	Quinn et al.
6,578,076 B1	6/2003	Putzolu	7,039,027 B2	5/2006	Bridgelall
6,581,092 B1	6/2003	Motoyama	7,039,037 B2	5/2006	Wang et al.
6,598,034 B1	7/2003	Kloth	7,039,403 B2	5/2006	Wong
6,601,040 B1	7/2003	Kolls	7,039,713 B1	5/2006	Van Gunter et al.
6,603,969 B1	8/2003	Vuoristo et al.	7,042,988 B2	5/2006	Juitt et al.
6,606,744 B1	8/2003	Mikurak	7,043,225 B1	5/2006	Patel et al.
6,628,934 B2	9/2003	Rosenberg et al.	7,043,226 B2	5/2006	Yamauchi
6,631,122 B1	10/2003	Arunachalam et al.	7,043,268 B2	5/2006	Yukie et al.
6,636,721 B2	10/2003	Threadgill et al.	7,047,276 B2	5/2006	Liu et al.
6,639,975 B1	10/2003	O'Neal et al.	7,058,022 B1	6/2006	Carolan et al.
6,640,097 B2	10/2003	Corrigan et al.	7,058,968 B2	6/2006	Rowland et al.
6,640,334 B1	10/2003	Rasmussen	7,068,600 B2	6/2006	Cain
6,650,887 B2	11/2003	McGregor et al.	7,069,248 B2	6/2006	Huber
6,651,101 B1	11/2003	Gai et al.	7,082,422 B1	7/2006	Zirngibl et al.
6,654,786 B1	11/2003	Fox et al.	7,084,775 B1	8/2006	Smith
6,654,814 B1	11/2003	Britton et al.	7,092,696 B1	8/2006	Hosain et al.
6,658,254 B1	12/2003	Purdy et al.	7,095,754 B2 *	8/2006	Benveniste H04L 47/10 370/445
6,662,014 B1	12/2003	Walsh	7,102,620 B2	9/2006	Harries et al.
6,678,516 B2	1/2004	Nordman et al.	7,110,753 B2	9/2006	Campen
6,683,853 B1	1/2004	Kannas et al.	7,113,780 B2	9/2006	McKenna et al.
6,684,244 B1	1/2004	Goldman et al.	7,113,997 B2	9/2006	Jayapalan et al.
6,690,918 B2	2/2004	Evans et al.	7,133,386 B2	11/2006	Holur et al.
6,697,821 B2	2/2004	Ziff et al.	7,133,695 B2	11/2006	Beyda
6,725,031 B2	4/2004	Watler et al.	7,136,361 B2 *	11/2006	Benveniste H04L 47/14 370/310.2
6,725,256 B1	4/2004	Albal et al.	7,139,569 B2	11/2006	Kato
6,735,206 B1	5/2004	Ok et al.	7,142,876 B2	11/2006	Trossen et al.
6,748,195 B1	6/2004	Phillips	7,149,229 B1	12/2006	Leung
6,748,437 B1	6/2004	Mankude et al.	7,149,521 B2	12/2006	Sundar et al.
6,751,296 B1	6/2004	Albal et al.	7,151,764 B1	12/2006	Heinonen et al.
6,754,470 B2	6/2004	Hendrickson et al.	7,158,792 B1	1/2007	Cook et al.
6,757,717 B1	6/2004	Goldstein	7,162,237 B1	1/2007	Silver et al.
6,763,000 B1	7/2004	Walsh	7,167,078 B2	1/2007	Pourchot
6,763,226 B1	7/2004	McZeal, Jr.	7,174,156 B1	2/2007	Mangal
6,765,864 B1	7/2004	Natarajan et al.	7,174,174 B2	2/2007	Boris et al.
6,765,925 B1	7/2004	Sawyer et al.	7,177,919 B1	2/2007	Truong et al.
6,782,412 B2	8/2004	Brophy et al.	7,180,855 B1	2/2007	Lin
6,785,889 B1	8/2004	Williams	7,181,017 B1	2/2007	Nagel et al.
6,792,461 B1	9/2004	Hericourt	7,191,248 B2	3/2007	Chattopadhyay et al.
6,829,596 B1	12/2004	Frazee	7,197,321 B2	3/2007	Ersikine et al.
6,829,696 B1	12/2004	Balmer et al.	7,200,112 B2	4/2007	Sundar et al.
			7,203,169 B1	4/2007	Okholm et al.
			7,203,721 B1	4/2007	Ben-Efraim et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

7,203,752 B2	4/2007	Rice et al.	7,505,795 B1	3/2009	Lim et al.
7,212,491 B2	5/2007	Koga	7,508,799 B2	3/2009	Sumner et al.
7,219,123 B1	5/2007	Fiechter et al.	7,512,128 B2	3/2009	DiMambro et al.
7,222,190 B2	5/2007	Klinker et al.	7,515,608 B2	4/2009	Yuan et al.
7,222,304 B2	5/2007	Beaton et al.	7,515,926 B2	4/2009	Bu et al.
7,224,968 B2	5/2007	Dobson et al.	7,516,219 B2	4/2009	Moghaddam et al.
7,228,354 B2	6/2007	Chambliss et al.	7,529,204 B2	5/2009	Bourlas et al.
7,236,780 B2	6/2007	Benco	7,535,880 B1	5/2009	Hinman et al.
7,242,668 B2	7/2007	Kan et al.	7,536,695 B2	5/2009	Alam et al.
7,242,920 B2	7/2007	Morris	7,539,132 B2	5/2009	Werner et al.
7,245,901 B2	7/2007	McGregor et al.	7,540,408 B2	6/2009	Levine et al.
7,248,570 B2	7/2007	Bahl et al.	7,545,782 B2	6/2009	Rayment et al.
7,251,218 B2	7/2007	Jorgensen	7,546,460 B2	6/2009	Maes
7,260,382 B1	8/2007	Lamb et al.	7,546,629 B2	6/2009	Albert et al.
7,266,371 B1	9/2007	Amin et al.	7,548,976 B2	6/2009	Bahl et al.
7,271,765 B2	9/2007	Stilp et al.	7,551,922 B2	6/2009	Roskowski et al.
7,272,660 B1	9/2007	Powers et al.	7,554,983 B1	6/2009	Muppala
7,280,816 B2	10/2007	Fratti et al.	7,555,757 B2	6/2009	Smith et al.
7,280,818 B2	10/2007	Clayton	7,561,899 B2	7/2009	Lee
7,283,561 B1	10/2007	Picher-Dempsey	7,562,213 B1	7/2009	Timms
7,283,963 B1	10/2007	Fitzpatrick et al.	7,564,799 B2	7/2009	Holland et al.
7,286,834 B2	10/2007	Walter	7,565,141 B2	7/2009	Macaluso
7,286,848 B2	10/2007	Vireday et al.	7,574,509 B2	8/2009	Nixon et al.
7,289,489 B1	10/2007	Kung et al.	7,574,731 B2	8/2009	Fascenda
7,290,283 B2	10/2007	Copeland, III	7,577,431 B2	8/2009	Jiang
7,310,424 B2	12/2007	Gehring et al.	7,580,356 B1	8/2009	Mishra et al.
7,313,237 B2	12/2007	Bahl et al.	7,580,857 B2	8/2009	VanFleet et al.
7,317,699 B2	1/2008	Godfrey et al.	7,583,964 B2	9/2009	Wong
7,318,111 B2	1/2008	Zhao	7,586,871 B2	9/2009	Hamilton et al.
7,320,029 B2	1/2008	Rinne et al.	7,593,417 B2	9/2009	Wang et al.
7,322,044 B2	1/2008	Hrastar	7,593,730 B2	9/2009	Khandelwal et al.
7,324,447 B1	1/2008	Morford	7,599,288 B2	10/2009	Cole et al.
7,325,037 B2	1/2008	Lawson	7,599,714 B2	10/2009	Kuzminskiy
7,336,960 B2	2/2008	Zavalkovsky et al.	7,602,746 B2	10/2009	Calhoun et al.
7,346,410 B2	3/2008	Uchiyama	7,609,650 B2	10/2009	Roskowski et al.
7,349,695 B2	3/2008	Oommen et al.	7,609,700 B1	10/2009	Ying et al.
7,353,533 B2	4/2008	Wright et al.	7,610,047 B2	10/2009	Hicks, III et al.
7,356,011 B1	4/2008	Waters et al.	7,610,328 B2	10/2009	Haase et al.
7,356,337 B2	4/2008	Florence	7,610,396 B2	10/2009	Taglienti et al.
7,366,497 B2	4/2008	Nagata	7,614,051 B2	11/2009	Glaum et al.
7,366,654 B2	4/2008	Moore	7,617,516 B2	11/2009	Huslak et al.
7,369,848 B2	5/2008	Jiang	7,620,041 B2	11/2009	Dunn et al.
7,369,856 B2	5/2008	Ovadia	7,620,065 B2	11/2009	Falardeau
7,373,136 B2	5/2008	Watler et al.	7,620,162 B2	11/2009	Aaron et al.
7,373,179 B2	5/2008	Stine et al.	7,627,314 B2	12/2009	Carlson et al.
7,379,731 B2	5/2008	Natsuno et al.	7,627,767 B2	12/2009	Sherman et al.
7,388,950 B2	6/2008	Elsei et al.	7,627,872 B2	12/2009	Hebeler et al.
7,391,724 B2	6/2008	Alakoski et al.	7,633,438 B2	12/2009	Tysowski
7,395,244 B1	7/2008	Kingsford	7,634,388 B2	12/2009	Archer et al.
7,401,338 B1	7/2008	Bowen et al.	7,636,574 B2	12/2009	Poosala
7,403,763 B2	7/2008	Maes	7,636,626 B2	12/2009	Oesterling et al.
7,409,447 B1	8/2008	Assadzadeh	7,643,411 B2	1/2010	Andreasen et al.
7,409,569 B2	8/2008	Illowsky et al.	7,644,151 B2	1/2010	Jerrim et al.
7,411,930 B2	8/2008	Montejo et al.	7,644,267 B2	1/2010	Ylikoski et al.
7,418,253 B2	8/2008	Kavanah	7,647,047 B2	1/2010	Moghaddam et al.
7,418,257 B2	8/2008	Kim	7,650,137 B2	1/2010	Jobs et al.
7,421,004 B2	9/2008	Feher	7,653,394 B2	1/2010	McMillin
7,428,750 B1	9/2008	Dunn et al.	7,657,920 B2	2/2010	Arseneau et al.
7,440,433 B2	10/2008	Rink et al.	7,660,419 B1	2/2010	Ho
7,444,669 B1	10/2008	Bahl et al.	7,661,124 B2	2/2010	Ramanathan et al.
7,450,591 B2	11/2008	Korling et al.	7,664,494 B2	2/2010	Jiang
7,450,927 B1	11/2008	Creswell et al.	7,668,176 B2	2/2010	Chuah
7,454,191 B2	11/2008	Dawson et al.	7,668,612 B1	2/2010	Okkonen
7,457,265 B2	11/2008	Julka et al.	7,668,903 B2	2/2010	Edwards et al.
7,457,870 B1	11/2008	Lownsbrough et al.	7,676,673 B2	3/2010	Weller et al.
7,460,837 B2	12/2008	Diener	7,680,086 B2	3/2010	Eglin
7,472,189 B2	12/2008	Mallya et al.	7,684,370 B2	3/2010	Kezys
7,478,420 B2	1/2009	Wright et al.	7,685,131 B2	3/2010	Batra et al.
7,486,185 B2	2/2009	Culpepper et al.	7,685,254 B2	3/2010	Pandya
7,486,658 B2	2/2009	Kumar	7,685,530 B2	3/2010	Sherrard et al.
7,493,659 B1	2/2009	Wu et al.	7,693,720 B2	4/2010	Kennewick et al.
7,496,652 B2	2/2009	Pezzutti	7,697,540 B2	4/2010	Haddad et al.
7,499,438 B2	3/2009	Hinman et al.	7,710,932 B2	5/2010	Muthuswamy et al.
7,499,537 B2	3/2009	Elsei et al.	7,711,848 B2	5/2010	Maes
7,502,672 B1	3/2009	Kolls	7,719,966 B2	5/2010	Luft et al.
			7,720,206 B2	5/2010	Devolites et al.
			7,720,464 B2	5/2010	Batta
			7,720,505 B2	5/2010	Gopi et al.
			7,720,960 B2	5/2010	Pruss et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

7,724,716 B2	5/2010	Fadell	7,925,778 B1	4/2011	Wijnands et al.
7,725,570 B1	5/2010	Lewis	7,929,959 B2	4/2011	DeAtley et al.
7,729,326 B2	6/2010	Sekhar	7,929,960 B2	4/2011	Martin et al.
7,730,123 B1	6/2010	Erickson et al.	7,929,973 B2	4/2011	Zavalkovsky et al.
7,734,784 B1	6/2010	Araujo et al.	7,930,327 B2	4/2011	Craft et al.
7,742,406 B1	6/2010	Muppala	7,930,446 B2	4/2011	Kesselman et al.
7,746,854 B2	6/2010	Ambe et al.	7,933,274 B2	4/2011	Verma et al.
7,747,240 B1	6/2010	Briscoe et al.	7,936,736 B2	5/2011	Proctor, Jr. et al.
7,747,699 B2	6/2010	Prueitt et al.	7,937,069 B2	5/2011	Rassam
7,747,730 B1	6/2010	Harlow	7,937,450 B2	5/2011	Janik
7,752,330 B2	7/2010	Olsen et al.	7,940,685 B1	5/2011	Breslau et al.
7,756,056 B2	7/2010	Kim et al.	7,940,751 B2	5/2011	Hansen
7,756,534 B2	7/2010	Anupam et al.	7,941,184 B2	5/2011	Prendergast et al.
7,756,757 B1	7/2010	Oakes, III	7,944,948 B2	5/2011	Chow et al.
7,760,137 B2	7/2010	Martucci et al.	7,945,238 B2	5/2011	Baker et al.
7,760,711 B1	7/2010	Kung et al.	7,945,240 B1	5/2011	Klock et al.
7,760,861 B1	7/2010	Croak et al.	7,945,945 B2	5/2011	Graham et al.
7,765,294 B2	7/2010	Edwards et al.	7,948,952 B2	5/2011	Hurtt et al.
7,770,785 B2	8/2010	Jha et al.	7,948,953 B2	5/2011	Melkote et al.
7,774,323 B2	8/2010	Helfman	7,948,968 B2	5/2011	Voit et al.
7,774,456 B1	8/2010	Lownsbrough et al.	7,949,529 B2	5/2011	Weider et al.
7,778,176 B2	8/2010	Morford	7,953,808 B2	5/2011	Sharp et al.
7,778,643 B2	8/2010	Laroia et al.	7,953,877 B2	5/2011	Vemula et al.
7,792,257 B1	9/2010	Vanier et al.	7,957,020 B2	6/2011	Mine et al.
7,792,538 B2	9/2010	Kozisek	7,957,381 B2	6/2011	Clermidy et al.
7,792,708 B2	9/2010	Alva	7,957,511 B2	6/2011	Drudis et al.
7,797,060 B2	9/2010	Grgic et al.	7,958,029 B1	6/2011	Bobich et al.
7,797,204 B2	9/2010	Balent	7,962,622 B2	6/2011	Friend et al.
7,797,401 B2	9/2010	Stewart et al.	7,965,983 B1	6/2011	Swan et al.
7,801,523 B1	9/2010	Kenderov	7,966,405 B2	6/2011	Sundaresan et al.
7,801,783 B2	9/2010	Kende et al.	7,969,950 B2	6/2011	Iyer et al.
7,801,985 B1	9/2010	Pitkow et al.	7,970,350 B2	6/2011	Sheynman
7,802,724 B1	9/2010	Nohr	7,970,426 B2	6/2011	Poe et al.
7,805,140 B2	9/2010	Friday et al.	7,974,624 B2	7/2011	Gallagher et al.
7,805,606 B2	9/2010	Birger et al.	7,975,184 B2	7/2011	Goff et al.
7,809,351 B1	10/2010	Panda et al.	7,978,627 B2	7/2011	Taylor et al.
7,817,615 B1	10/2010	Breau et al.	7,978,686 B2	7/2011	Goyal et al.
7,817,983 B2	10/2010	Cassett et al.	7,979,069 B2	7/2011	Hupp et al.
7,822,837 B1	10/2010	Urban et al.	7,984,130 B2	7/2011	Bogineni et al.
7,826,427 B2	11/2010	Sood et al.	7,984,511 B2	7/2011	Kocher et al.
7,826,607 B1	11/2010	de Carvalho Resende et al.	7,986,935 B1	7/2011	D'Souza et al.
7,843,831 B2	11/2010	Morrill et al.	7,987,496 B2	7/2011	Bryce et al.
7,843,843 B1	11/2010	Papp, III et al.	7,987,510 B2	7/2011	Kocher et al.
7,844,034 B1	11/2010	Oh et al.	7,990,049 B2	8/2011	Shioya
7,844,728 B2	11/2010	Anderson et al.	8,000,276 B2	8/2011	Scherzer et al.
7,848,768 B2	12/2010	Omori et al.	8,000,318 B2	8/2011	Wiley et al.
7,849,161 B2	12/2010	Koch et al.	8,005,009 B2	8/2011	McKee et al.
7,849,477 B2	12/2010	Cristofalo et al.	8,005,459 B2	8/2011	Balsillie
7,853,255 B2	12/2010	Karaoguz et al.	8,005,726 B1	8/2011	Bao
7,856,226 B2	12/2010	Wong et al.	8,005,913 B1	8/2011	Carlander
7,860,088 B2	12/2010	Lioy	8,005,988 B2	8/2011	Maes
7,865,182 B2	1/2011	Macaluso	8,010,080 B1	8/2011	Thenthirupera et al.
7,865,187 B2	1/2011	Ramer et al.	8,010,081 B1	8/2011	Roskowski
7,868,778 B2	1/2011	Kenwright	8,010,082 B2	8/2011	Sutaria et al.
7,873,001 B2	1/2011	Silver	8,015,133 B1	9/2011	Wu et al.
7,873,344 B2	1/2011	Bowser et al.	8,015,234 B2	9/2011	Lum et al.
7,873,705 B2	1/2011	Kalish	8,019,687 B2	9/2011	Wang et al.
7,877,090 B2	1/2011	Maes	8,019,820 B2	9/2011	Son et al.
7,881,199 B2	2/2011	Krstulich	8,019,846 B2	9/2011	Roelens et al.
7,881,697 B2	2/2011	Baker et al.	8,019,868 B2	9/2011	Rao et al.
7,882,029 B2	2/2011	White	8,019,886 B2	9/2011	Harrang et al.
7,886,047 B1	2/2011	Potluri	8,023,425 B2	9/2011	Raleigh
7,889,384 B2	2/2011	Armentrout et al.	8,024,397 B1	9/2011	Erickson et al.
7,890,084 B1	2/2011	Dudziak et al.	8,027,339 B2	9/2011	Short et al.
7,890,111 B2	2/2011	Bugenhagen	8,031,601 B2	10/2011	Feroz et al.
7,894,431 B2	2/2011	Goring et al.	8,032,168 B2	10/2011	Ikaheimo
7,899,039 B2	3/2011	Andreasen et al.	8,032,409 B1	10/2011	Mikurak
7,899,438 B2	3/2011	Baker et al.	8,032,899 B2	10/2011	Archer et al.
7,903,553 B2	3/2011	Liu	8,036,387 B2	10/2011	Kudelski et al.
7,907,970 B2	3/2011	Park et al.	8,036,600 B2	10/2011	Garrett et al.
7,911,975 B2	3/2011	Droz et al.	8,044,792 B2	10/2011	Orr et al.
7,912,025 B2	3/2011	Pattenden et al.	8,045,973 B2	10/2011	Chambers
7,912,056 B1	3/2011	Brassem	8,046,449 B2	10/2011	Yoshiuchi
7,920,529 B1	4/2011	Mahler et al.	8,050,275 B1	11/2011	Iyer
7,921,463 B2	4/2011	Sood et al.	8,050,690 B2	11/2011	Neeraj
			8,050,705 B2	11/2011	Sicher et al.
			8,059,530 B1	11/2011	Cole
			8,060,463 B1	11/2011	Spiegel
			8,064,418 B2	11/2011	Maki

(56)

References Cited

U.S. PATENT DOCUMENTS

8,064,896	B2	11/2011	Bell et al.	8,185,088	B2	5/2012	Klein et al.
8,065,365	B2	11/2011	Saxena et al.	8,185,093	B2	5/2012	Jheng et al.
8,068,824	B2	11/2011	Shan et al.	8,185,127	B1	5/2012	Cai et al.
8,068,829	B2	11/2011	Lemond et al.	8,185,152	B1	5/2012	Goldner
8,073,427	B2	12/2011	Koch et al.	8,185,158	B2	5/2012	Tamura et al.
8,073,721	B1	12/2011	Lewis	8,190,122	B1	5/2012	Alexander et al.
8,078,140	B2	12/2011	Baker et al.	8,190,675	B2	5/2012	Tribbett
8,078,163	B2	12/2011	Lemond et al.	8,191,106	B2	5/2012	Choyi et al.
8,085,808	B2	12/2011	Brusca et al.	8,191,116	B1	5/2012	Gazzard
8,086,398	B2	12/2011	Sanchez et al.	8,191,124	B2	5/2012	Wynn et al.
8,086,497	B1	12/2011	Oakes, III	8,194,549	B2	6/2012	Huber et al.
8,086,791	B2	12/2011	Caulkins	8,194,553	B2	6/2012	Liang et al.
8,090,359	B2	1/2012	Proctor, Jr. et al.	8,194,572	B2	6/2012	Horvath et al.
8,090,616	B2	1/2012	Proctor, Jr. et al.	8,194,581	B1	6/2012	Schroeder et al.
8,094,551	B2	1/2012	Huber et al.	8,195,093	B2	6/2012	Garrett et al.
8,095,112	B2	1/2012	Chow et al.	8,195,153	B1	6/2012	Frencel et al.
8,095,124	B2	1/2012	Balia	8,195,163	B2	6/2012	Gisby et al.
8,095,640	B2	1/2012	Guingo et al.	8,195,661	B2	6/2012	Kalavade
8,095,666	B2	1/2012	Schmidt et al.	8,196,199	B2	6/2012	Hrastar et al.
8,098,579	B2	1/2012	Ray et al.	8,200,163	B2	6/2012	Hoffman
8,099,077	B2	1/2012	Chowdhury et al.	8,200,200	B1	6/2012	Belser et al.
8,099,517	B2	1/2012	Jia et al.	8,200,509	B2	6/2012	Kenedy et al.
8,102,814	B2	1/2012	Rahman et al.	8,200,775	B2	6/2012	Moore
8,103,285	B2	1/2012	Kalhan	8,200,818	B2	6/2012	Freund et al.
8,104,080	B2	1/2012	Burns et al.	8,204,190	B2	6/2012	Bang et al.
8,107,953	B2	1/2012	Zimmerman et al.	8,204,505	B2	6/2012	Jin et al.
8,108,520	B2	1/2012	Ruutu et al.	8,204,794	B1	6/2012	Peng et al.
8,112,435	B2	2/2012	Epstein et al.	8,208,788	B2	6/2012	Ando et al.
8,116,223	B2	2/2012	Tian et al.	8,208,919	B2	6/2012	Kotecha
8,116,749	B2	2/2012	Proctor, Jr. et al.	8,213,296	B2	7/2012	Shannon et al.
8,116,781	B2	2/2012	Chen et al.	8,213,363	B2	7/2012	Ying et al.
8,122,128	B2	2/2012	Burke, II et al.	8,214,536	B2	7/2012	Zhao
8,122,249	B2	2/2012	Falk et al.	8,219,134	B2	7/2012	Maharajh et al.
8,125,897	B2	2/2012	Ray et al.	8,223,655	B2	7/2012	Heinz et al.
8,126,123	B2	2/2012	Cai et al.	8,223,741	B1	7/2012	Bartlett et al.
8,126,396	B2	2/2012	Bennett	8,224,382	B2	7/2012	Bultman
8,126,476	B2	2/2012	Vardi et al.	8,224,773	B2	7/2012	Spiegel
8,126,722	B2	2/2012	Robb et al.	8,228,818	B2	7/2012	Chase et al.
8,130,793	B2	3/2012	Edwards et al.	8,229,394	B2	7/2012	Karlberg
8,131,256	B2	3/2012	Martti et al.	8,229,914	B2	7/2012	Ramer et al.
8,131,281	B1	3/2012	Hildner et al.	8,230,061	B2	7/2012	Hassan et al.
8,131,840	B1	3/2012	Denker	8,233,433	B2	7/2012	Kalhan
8,131,858	B2	3/2012	Agulnik et al.	8,233,883	B2	7/2012	De Froment
8,132,256	B2	3/2012	Bari	8,233,895	B2	7/2012	Tysowski
8,134,954	B2	3/2012	Godfrey et al.	8,238,287	B1	8/2012	Gopi et al.
8,135,388	B1	3/2012	Gailloux et al.	8,239,520	B2	8/2012	Grah
8,135,392	B2	3/2012	Marcellino et al.	8,242,959	B2	8/2012	Mia et al.
8,135,657	B2	3/2012	Kapoor et al.	8,244,241	B2	8/2012	Montemurro
8,140,690	B2	3/2012	Ly et al.	8,249,601	B2	8/2012	Emberson et al.
8,144,591	B2	3/2012	Ghai et al.	8,254,880	B2	8/2012	Aaltonen et al.
8,145,194	B2	3/2012	Yoshikawa et al.	8,254,915	B2	8/2012	Kozisek
8,149,823	B2	4/2012	Turcan et al.	8,255,515	B1	8/2012	Melman et al.
8,150,394	B2	4/2012	Bianconi et al.	8,255,534	B2	8/2012	Assadzadeh
8,150,431	B2	4/2012	Wolovitz et al.	8,255,689	B2	8/2012	Kim et al.
8,151,205	B2	4/2012	Follmann et al.	8,259,692	B2	9/2012	Bajko
8,155,155	B1	4/2012	Chow et al.	8,264,965	B2	9/2012	Dolganow et al.
8,155,620	B2	4/2012	Wang et al.	8,265,004	B2	9/2012	Toutonghi
8,155,666	B2	4/2012	Alizadeh-Shabdiz	8,266,681	B2	9/2012	Deshpande et al.
8,155,670	B2	4/2012	Fullam et al.	8,270,955	B2	9/2012	Ramer et al.
8,156,206	B2	4/2012	Kiley et al.	8,270,972	B2	9/2012	Otting et al.
8,160,015	B2	4/2012	Rashid et al.	8,271,025	B2	9/2012	Brisebois et al.
8,160,056	B2	4/2012	Van der Merwe et al.	8,271,045	B2	9/2012	Parolkar et al.
8,160,598	B2	4/2012	Savoor	8,271,049	B2	9/2012	Silver et al.
8,165,576	B2	4/2012	Raju et al.	8,271,992	B2	9/2012	Chatley et al.
8,166,040	B2	4/2012	Brindisi et al.	8,275,415	B2	9/2012	Huslak
8,166,554	B2	4/2012	John	8,275,830	B2	9/2012	Raleigh
8,170,553	B2	5/2012	Bennett	8,279,067	B2	10/2012	Berger et al.
8,174,378	B2	5/2012	Richman et al.	8,279,864	B2	10/2012	Wood
8,174,970	B2	5/2012	Adamczyk et al.	8,280,351	B1	10/2012	Ahmed et al.
8,175,574	B1	5/2012	Panda et al.	8,280,354	B2	10/2012	Smith et al.
8,180,333	B1	5/2012	Wells et al.	8,284,740	B2	10/2012	O'Connor
8,180,881	B2	5/2012	Seo et al.	8,285,249	B2	10/2012	Baker et al.
8,180,886	B2	5/2012	Overcash et al.	8,291,238	B2	10/2012	Ginter et al.
8,184,530	B1	5/2012	Swan et al.	8,291,439	B2	10/2012	Jethi et al.
8,184,590	B2	5/2012	Rosenblatt	8,296,404	B2	10/2012	McDysan et al.
				8,300,575	B2	10/2012	Willars
				8,301,513	B1	10/2012	Peng et al.
				8,306,518	B1	11/2012	Gailloux
				8,307,067	B2	11/2012	Ryan

(56)

References Cited

U.S. PATENT DOCUMENTS

8,307,095 B2	11/2012	Clark et al.	8,441,955 B2	5/2013	Wilkinson et al.
8,315,198 B2	11/2012	Corneille et al.	8,442,015 B2	5/2013	Behzad et al.
8,315,593 B2	11/2012	Gallant et al.	8,447,324 B2	5/2013	Shuman et al.
8,315,594 B1	11/2012	Mausser et al.	8,447,607 B2	5/2013	Weider et al.
8,315,718 B2	11/2012	Caffrey et al.	8,447,980 B2	5/2013	Godfrey et al.
8,315,999 B2	11/2012	Chatley et al.	8,448,015 B2	5/2013	Gerhart
8,320,244 B2	11/2012	Muqattash et al.	8,452,858 B2	5/2013	Wu et al.
8,320,902 B2	11/2012	Moring et al.	8,461,958 B2	6/2013	Saenz et al.
8,320,949 B2	11/2012	Matta	8,463,232 B2	6/2013	Tuli et al.
8,325,638 B2	12/2012	Jin et al.	8,468,337 B2	6/2013	Gaur et al.
8,325,906 B2	12/2012	Fullarton et al.	8,472,371 B1	6/2013	Bari et al.
8,326,319 B2	12/2012	Davis	8,477,778 B2	7/2013	Lehmann, Jr. et al.
8,326,359 B2	12/2012	Kauffman	8,483,135 B2	7/2013	Cai et al.
8,326,828 B2	12/2012	Zhou et al.	8,483,694 B2	7/2013	Lewis et al.
8,331,223 B2	12/2012	Hill et al.	8,484,327 B2	7/2013	Werner et al.
8,331,293 B2	12/2012	Sood	8,484,568 B2	7/2013	Rados et al.
8,332,375 B2	12/2012	Chatley et al.	8,488,597 B2	7/2013	Nie et al.
8,332,517 B2	12/2012	Russell	8,489,110 B2	7/2013	Frank et al.
8,335,161 B2	12/2012	Footit et al.	8,489,720 B1	7/2013	Morford et al.
8,339,991 B2	12/2012	Biswas et al.	8,494,559 B1	7/2013	Malmi
8,340,628 B2	12/2012	Taylor et al.	8,495,181 B2	7/2013	Venkatraman et al.
8,340,678 B1	12/2012	Pandey	8,495,227 B2	7/2013	Kaminsky et al.
8,340,718 B2	12/2012	Colonna et al.	8,495,360 B2	7/2013	Falk et al.
8,346,210 B2	1/2013	Balsan et al.	8,495,700 B2	7/2013	Shahbazi
8,347,104 B2	1/2013	Pathiyal	RE44,412 E	8/2013	Naqvi et al.
8,347,362 B2	1/2013	Cai et al.	8,503,358 B2	8/2013	Hanson et al.
8,347,378 B2	1/2013	Merkin et al.	8,503,455 B2	8/2013	Heikens
8,350,700 B2	1/2013	Fast et al.	8,504,032 B2	8/2013	Lott et al.
8,351,592 B2	1/2013	Freeny, Jr. et al.	8,504,687 B2	8/2013	Maffione et al.
8,351,898 B2	1/2013	Raleigh	8,504,690 B2	8/2013	Shah et al.
8,352,360 B2	1/2013	De Judicibus et al.	8,504,729 B2	8/2013	Pezzutti
8,352,630 B2	1/2013	Hart	8,505,073 B2	8/2013	Taglienti et al.
8,352,980 B2	1/2013	Howcroft	8,509,082 B2	8/2013	Heinz et al.
8,353,001 B2	1/2013	Herrod	8,514,927 B2	8/2013	Sundararajan et al.
8,355,696 B1	1/2013	Olding et al.	8,516,552 B2	8/2013	Raleigh
8,356,336 B2	1/2013	Johnston et al.	8,520,589 B2	8/2013	Bhatt et al.
8,358,638 B2	1/2013	Scherzer et al.	8,520,595 B2	8/2013	Yadav et al.
8,358,975 B2	1/2013	Bahl et al.	8,521,110 B2	8/2013	Rofougaran
8,363,658 B1	1/2013	Delker et al.	8,521,775 B1	8/2013	Poh et al.
8,363,799 B2	1/2013	Gruchala et al.	8,522,039 B2	8/2013	Hyndman et al.
8,364,089 B2	1/2013	Phillips	8,522,249 B2	8/2013	Beaule
8,364,806 B2	1/2013	Short et al.	8,522,337 B2	8/2013	Adusumilli et al.
8,369,274 B2	2/2013	Sawai	8,523,547 B2	9/2013	Pekrul
8,370,477 B2	2/2013	Short et al.	8,526,329 B2	9/2013	Mahany et al.
8,370,483 B2	2/2013	Choong et al.	8,527,410 B2	9/2013	Markki et al.
8,374,090 B2	2/2013	Morrill et al.	8,527,662 B2	9/2013	Biswas et al.
8,374,592 B2	2/2013	Proctor, Jr. et al.	8,528,068 B1	9/2013	Weglein et al.
8,375,128 B2	2/2013	Tofighbakhsh et al.	8,531,954 B2	9/2013	McNaughton et al.
8,375,136 B2	2/2013	Roman et al.	8,532,610 B2	9/2013	Manning Cassett et al.
8,379,847 B2	2/2013	Bell et al.	8,533,775 B2	9/2013	Alcorn et al.
8,380,247 B2	2/2013	Engstrom	8,538,394 B2	9/2013	Zimmerman et al.
8,385,199 B1	2/2013	Coward et al.	8,538,421 B2	9/2013	Brisebois et al.
8,385,896 B2	2/2013	Proctor, Jr. et al.	8,538,458 B2	9/2013	Haney
8,385,964 B2	2/2013	Haney	8,539,561 B2	9/2013	Gupta et al.
8,385,975 B2	2/2013	Forutanpour	8,543,265 B2	9/2013	Ekhaguere et al.
8,386,386 B2	2/2013	Zhu	8,543,814 B2	9/2013	Laitinen et al.
8,391,262 B1	3/2013	Maki et al.	8,544,105 B2	9/2013	McLean et al.
8,391,834 B2	3/2013	Raleigh	8,548,427 B2	10/2013	Chow et al.
8,396,458 B2	3/2013	Raleigh	8,548,428 B2	10/2013	Raleigh
8,396,929 B2	3/2013	Helfman et al.	8,554,876 B2	10/2013	Winsor
8,402,165 B2*	3/2013	Deu-Ngoc H04W 72/10 709/227	8,565,746 B2	10/2013	Hoffman
8,402,540 B2	3/2013	Kapoor et al.	8,566,236 B2	10/2013	Busch
8,406,427 B2	3/2013	Chand et al.	8,571,474 B2	10/2013	Chavez et al.
8,406,736 B2	3/2013	Das et al.	8,571,501 B2	10/2013	Miller et al.
8,407,763 B2	3/2013	Weller et al.	8,571,598 B2	10/2013	Valavi
8,411,587 B2	4/2013	Curtis et al.	8,571,993 B2	10/2013	Kocher et al.
8,411,691 B2	4/2013	Aggarwal	8,572,117 B2	10/2013	Rappaport
8,412,798 B1	4/2013	Wang	8,572,256 B2	10/2013	Babbar
8,418,168 B2	4/2013	Tyhurst et al.	8,583,499 B2	11/2013	De Judicibus et al.
8,422,988 B1	4/2013	Keshav	8,589,541 B2	11/2013	Raleigh et al.
8,423,016 B2	4/2013	Buckley et al.	8,589,955 B2	11/2013	Roundtree et al.
8,429,403 B2	4/2013	Moret et al.	8,600,895 B2	12/2013	Felsner
8,429,409 B1	4/2013	Wall et al.	8,601,125 B2	12/2013	Huang et al.
8,437,734 B2	5/2013	Ray et al.	8,605,691 B2	12/2013	Soomro et al.
			8,621,056 B2	12/2013	Coussemaecker et al.
			8,626,115 B2	1/2014	Raleigh et al.
			8,630,314 B2	1/2014	York
			8,631,428 B2	1/2014	Scott et al.
			8,634,425 B2	1/2014	Gorti et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

8,635,164	B2	1/2014	Rosenhaft et al.	9,325,737	B2	4/2016	Gutowski et al.
8,639,215	B2	1/2014	McGregor et al.	9,326,173	B2	4/2016	Luft
8,644,702	B1	2/2014	Kalajan	9,344,557	B2	5/2016	Gruchala et al.
8,644,813	B1	2/2014	Gailloux et al.	9,361,451	B2	6/2016	Oberheide et al.
8,645,518	B2	2/2014	David	9,367,680	B2	6/2016	Mahaffey et al.
8,655,357	B1	2/2014	Gazzard et al.	9,369,959	B2	6/2016	Ruutu et al.
8,660,853	B2	2/2014	Robb et al.	9,413,546	B2	8/2016	Meier et al.
8,666,395	B2	3/2014	Silver	2001/0048738	A1	12/2001	Baniak et al.
8,667,542	B1	3/2014	Bertz et al.	2001/0053694	A1	12/2001	Igarashi et al.
8,670,334	B2	3/2014	Keohane et al.	2002/0022472	A1	2/2002	Watler et al.
8,670,752	B2	3/2014	Fan et al.	2002/0049074	A1	4/2002	Eisinger et al.
8,675,852	B2	3/2014	Maes	2002/0116338	A1	8/2002	Gonthier et al.
8,676,925	B1	3/2014	Liu et al.	2002/0120370	A1	8/2002	Parupudi et al.
8,693,323	B1	4/2014	McDysan	2002/0120540	A1	8/2002	Kende et al.
8,694,772	B2	4/2014	Kao et al.	2002/0131404	A1	9/2002	Mehta et al.
8,700,729	B2	4/2014	Dua	2002/0138599	A1	9/2002	Dilman et al.
8,701,015	B2	4/2014	Bonnat	2002/0138601	A1	9/2002	Piponius et al.
8,705,361	B2	4/2014	Venkataraman et al.	2002/0154751	A1	10/2002	Thompson et al.
8,706,863	B2	4/2014	Fadell	2002/0161601	A1	10/2002	Nauer et al.
8,713,535	B2	4/2014	Malhotra et al.	2002/0164983	A1	11/2002	Raviv et al.
8,713,641	B1	4/2014	Pagan et al.	2002/0176377	A1	11/2002	Hamilton
8,719,397	B2	5/2014	Levi et al.	2002/0188732	A1	12/2002	Buckman et al.
8,719,423	B2	5/2014	Wylid	2002/0191573	A1	12/2002	Whitehill et al.
8,725,899	B2	5/2014	Short et al.	2002/0199001	A1	12/2002	Wenocur et al.
8,730,842	B2	5/2014	Collins et al.	2003/0004937	A1	1/2003	Salmenkaita et al.
8,731,519	B2	5/2014	Flynn et al.	2003/0005112	A1	1/2003	Krautkremer
8,732,808	B2	5/2014	Sewall et al.	2003/0013434	A1	1/2003	Rosenberg et al.
8,739,035	B2	5/2014	Trethewey	2003/0018524	A1	1/2003	Fishman et al.
8,744,339	B2	6/2014	Halfmann et al.	2003/0028623	A1	2/2003	Hennessey et al.
8,761,711	B2	6/2014	Grignani et al.	2003/0046396	A1	3/2003	Richter et al.
8,780,857	B2	7/2014	Balasubramanian et al.	2003/0050070	A1	3/2003	Mashinsky et al.
8,787,249	B2	7/2014	Giaretta et al.	2003/0050837	A1	3/2003	Kim
8,793,304	B2	7/2014	Lu et al.	2003/0084321	A1	5/2003	Tarquini et al.
8,799,227	B2	8/2014	Ferguson et al.	2003/0088671	A1	5/2003	Klinker et al.
8,804,517	B2	8/2014	Oerton	2003/0133408	A1	7/2003	Cheng et al.
8,811,338	B2	8/2014	Jin et al.	2003/0134650	A1	7/2003	Sundar et al.
8,811,991	B2	8/2014	Jain et al.	2003/0159030	A1	8/2003	Evans
8,812,525	B1	8/2014	Taylor, III	2003/0161265	A1	8/2003	Cao et al.
8,819,253	B2	8/2014	Simeloff et al.	2003/0171112	A1	9/2003	Lupper et al.
8,825,109	B2	9/2014	Montemurro et al.	2003/0182420	A1	9/2003	Jones et al.
8,831,561	B2	9/2014	Sutaria et al.	2003/0182435	A1	9/2003	Redlich et al.
8,837,322	B2	9/2014	Venkataramanan et al.	2003/0184793	A1	10/2003	Pineau
8,838,686	B2	9/2014	Getchius	2003/0188006	A1	10/2003	Bard
8,838,752	B2	9/2014	Lor et al.	2003/0188117	A1	10/2003	Yoshino et al.
8,855,620	B2	10/2014	Sievers et al.	2003/0220984	A1	11/2003	Jones et al.
8,862,751	B2	10/2014	Faccin et al.	2003/0224781	A1	12/2003	Milford et al.
8,863,111	B2	10/2014	Selitser et al.	2003/0229900	A1	12/2003	Reisman
8,868,725	B2	10/2014	Samba	2003/0233332	A1	12/2003	Keeler et al.
8,875,042	B2	10/2014	Lejeune et al.	2003/0236745	A1	12/2003	Hartsell et al.
8,880,047	B2	11/2014	Konicek et al.	2004/0019539	A1	1/2004	Raman et al.
8,898,748	B2	11/2014	Burks et al.	2004/0021697	A1	2/2004	Beaton et al.
8,908,516	B2	12/2014	Tzamaloukas et al.	2004/0030705	A1	2/2004	Bowman-Amuah
8,930,238	B2	1/2015	Coffman et al.	2004/0039792	A1	2/2004	Nakanishi
8,943,551	B2	1/2015	Ganapathy et al.	2004/0044623	A1	3/2004	Wake et al.
8,948,726	B2	2/2015	Smith et al.	2004/0047358	A1	3/2004	Chen et al.
8,949,597	B1	2/2015	Reeves et al.	2004/0054779	A1	3/2004	Takeshima et al.
8,966,018	B2	2/2015	Bugwadia et al.	2004/0073672	A1	4/2004	Fascenda
8,971,841	B2	3/2015	Menezes et al.	2004/0082346	A1	4/2004	Skytt et al.
8,971,912	B2	3/2015	Chou et al.	2004/0098715	A1	5/2004	Aghera et al.
8,972,537	B2	3/2015	Bastian et al.	2004/0102182	A1	5/2004	Reith et al.
8,977,284	B2	3/2015	Reed	2004/0103193	A1	5/2004	Pandya et al.
8,995,952	B1	3/2015	Baker et al.	2004/0107360	A1	6/2004	Herrmann et al.
9,002,322	B2	4/2015	Cotterill	2004/0127200	A1	7/2004	Shaw et al.
9,002,342	B2	4/2015	Tenhunen et al.	2004/0127208	A1	7/2004	Nair et al.
9,014,973	B2	4/2015	Ruckart	2004/0132427	A1	7/2004	Lee et al.
9,030,934	B2	5/2015	Shah et al.	2004/0133668	A1	7/2004	Nicholas, III
9,032,427	B2	5/2015	Gallant et al.	2004/0137890	A1	7/2004	Kalke
9,049,010	B2	6/2015	Jueneman et al.	2004/0168052	A1	8/2004	Clisham et al.
9,135,037	B1	9/2015	Petrescu-Prahova et al.	2004/0170191	A1	9/2004	Guo et al.
9,137,389	B2	9/2015	Neal et al.	2004/0176104	A1	9/2004	Arcens
9,172,553	B2	10/2015	Dawes et al.	2004/0198331	A1	10/2004	Coward et al.
9,173,090	B2	10/2015	Tuchman et al.	2004/0203755	A1	10/2004	Brunet et al.
9,176,913	B2	11/2015	Millet et al.	2004/0203833	A1	10/2004	Rathunde et al.
9,177,455	B2	11/2015	Remer	2004/0225561	A1	11/2004	Hertzberg et al.
9,282,460	B2	3/2016	Souissi	2004/0225898	A1	11/2004	Frost et al.
				2004/0236547	A1	11/2004	Rappaport et al.
				2004/0243680	A1	12/2004	Mayer
				2004/0243992	A1	12/2004	Gustafson et al.
				2004/0249918	A1	12/2004	Sunshine

(56)

References Cited

U.S. PATENT DOCUMENTS

2004/0255145	A1	12/2004	Chow	2006/0199608	A1	9/2006	Dunn et al.
2004/0259534	A1	12/2004	Chaudhari et al.	2006/0200663	A1	9/2006	Thornton
2004/0260766	A1	12/2004	Barros et al.	2006/0206709	A1	9/2006	Labrou et al.
2004/0267872	A1	12/2004	Serdy et al.	2006/0206904	A1	9/2006	Watkins et al.
2005/0007993	A1	1/2005	Chambers et al.	2006/0218395	A1	9/2006	Maes
2005/0009499	A1	1/2005	Koster	2006/0233108	A1	10/2006	Krishnan
2005/0021995	A1	1/2005	Lal et al.	2006/0233166	A1	10/2006	Bou-Diab et al.
2005/0041617	A1	2/2005	Huotari et al.	2006/0236095	A1	10/2006	Smith et al.
2005/0048950	A1	3/2005	Morper	2006/0242685	A1	10/2006	Heard et al.
2005/0055291	A1	3/2005	Bevente et al.	2006/0258341	A1	11/2006	Miller et al.
2005/0055309	A1	3/2005	Williams et al.	2006/0277590	A1	12/2006	Limont et al.
2005/0055595	A1	3/2005	Frazer et al.	2006/0291419	A1	12/2006	McConnell et al.
2005/0060266	A1	3/2005	Demello et al.	2006/0291477	A1	12/2006	Croak et al.
2005/0060525	A1	3/2005	Schwartz et al.	2007/0005795	A1	1/2007	Gonzalez
2005/0075115	A1	4/2005	Corneille et al.	2007/0019670	A1	1/2007	Falardeau
2005/0079863	A1	4/2005	Macaluso	2007/0022289	A1	1/2007	Alt et al.
2005/0091505	A1	4/2005	Riley et al.	2007/0025301	A1	2/2007	Petersson et al.
2005/0096024	A1	5/2005	Bicker et al.	2007/0033194	A1	2/2007	Srinivas et al.
2005/0097516	A1	5/2005	Donnelly et al.	2007/0033197	A1	2/2007	Scherzer et al.
2005/0107091	A1	5/2005	Vannithamby et al.	2007/0036312	A1	2/2007	Cai et al.
2005/0108075	A1	5/2005	Douglis et al.	2007/0055694	A1	3/2007	Ruge et al.
2005/0128967	A1	6/2005	Scobbie	2007/0060200	A1	3/2007	Boris et al.
2005/0135264	A1	6/2005	Popoff et al.	2007/0061243	A1	3/2007	Ramer et al.
2005/0163320	A1	7/2005	Brown et al.	2007/0061800	A1	3/2007	Cheng et al.
2005/0166043	A1	7/2005	Zhang et al.	2007/0061878	A1	3/2007	Hagiu et al.
2005/0183143	A1	8/2005	Anderholm et al.	2007/0073899	A1	3/2007	Judge et al.
2005/0186948	A1	8/2005	Gallagher et al.	2007/0076616	A1	4/2007	Ngo et al.
2005/0198377	A1	9/2005	Ferguson et al.	2007/0093243	A1	4/2007	Kapadekar et al.
2005/0216421	A1	9/2005	Barry et al.	2007/0100981	A1	5/2007	Adamczyk et al.
2005/0228985	A1	10/2005	Ylikoski et al.	2007/0101426	A1	5/2007	Lee et al.
2005/0238046	A1	10/2005	Hassan et al.	2007/0104126	A1	5/2007	Calhoun et al.
2005/0239447	A1	10/2005	Holzman et al.	2007/0109983	A1	5/2007	Shankar et al.
2005/0245241	A1	11/2005	Durand et al.	2007/0130283	A1	6/2007	Klein et al.
2005/0246282	A1	11/2005	Naslund et al.	2007/0130315	A1	6/2007	Friend et al.
2005/0250508	A1	11/2005	Guo et al.	2007/0140113	A1	6/2007	Gemelos
2005/0250536	A1	11/2005	Deng et al.	2007/0140145	A1	6/2007	Kumar et al.
2005/0254435	A1	11/2005	Moakley et al.	2007/0140275	A1	6/2007	Bowman et al.
2005/0266825	A1	12/2005	Clayton	2007/0143824	A1	6/2007	Shahbazi
2005/0266880	A1	12/2005	Gupta	2007/0147317	A1	6/2007	Smith et al.
2006/0014519	A1	1/2006	Marsh et al.	2007/0147324	A1	6/2007	McGary
2006/0019632	A1	1/2006	Cunningham et al.	2007/0155365	A1	7/2007	Kim et al.
2006/0026679	A1	2/2006	Zakas	2007/0165630	A1	7/2007	Rasanen
2006/0030306	A1	2/2006	Kuhn	2007/0168499	A1	7/2007	Chu
2006/0034256	A1	2/2006	Addagatla et al.	2007/0174490	A1	7/2007	Choi et al.
2006/0035631	A1	2/2006	White et al.	2007/0192460	A1	8/2007	Choi et al.
2006/0040642	A1	2/2006	Boris et al.	2007/0198656	A1	8/2007	Mazzaferrri et al.
2006/0045245	A1	3/2006	Aaron et al.	2007/0201502	A1	8/2007	Abramson
2006/0048223	A1	3/2006	Lee et al.	2007/0213054	A1	9/2007	Han
2006/0068796	A1	3/2006	Millen et al.	2007/0220251	A1	9/2007	Rosenberg et al.
2006/0072451	A1	4/2006	Ross	2007/0226225	A1	9/2007	Yiu et al.
2006/0072646	A1	4/2006	Feher	2007/0226775	A1	9/2007	Andreassen et al.
2006/0075506	A1	4/2006	Sanda et al.	2007/0234402	A1	10/2007	Khosravi et al.
2006/0085543	A1	4/2006	Hrstar et al.	2007/0243862	A1	10/2007	Coskun et al.
2006/0095517	A1	5/2006	O'Connor et al.	2007/0248100	A1	10/2007	Zuberi et al.
2006/0098627	A1	5/2006	Karaoguz et al.	2007/0254675	A1	11/2007	Zorlu Ozer et al.
2006/0099970	A1	5/2006	Morgan et al.	2007/0255769	A1	11/2007	Agrawal et al.
2006/0112016	A1	5/2006	Ishibashi	2007/0255797	A1	11/2007	Dunn et al.
2006/0114821	A1	6/2006	Willey et al.	2007/0255848	A1	11/2007	Sewall et al.
2006/0114832	A1	6/2006	Hamilton et al.	2007/0257767	A1	11/2007	Beeson
2006/0126562	A1	6/2006	Liu	2007/0259656	A1	11/2007	Jeong
2006/0135144	A1	6/2006	Jothipragasam	2007/0259673	A1	11/2007	Willars et al.
2006/0136882	A1	6/2006	Noonan et al.	2007/0263558	A1	11/2007	Salomone
2006/0143066	A1	6/2006	Calabria	2007/0266422	A1	11/2007	Germano et al.
2006/0143098	A1	6/2006	Lazaridis	2007/0274327	A1	11/2007	Kaarela et al.
2006/0156398	A1	7/2006	Ross et al.	2007/0280453	A1	12/2007	Kelley
2006/0160536	A1	7/2006	Chou	2007/0282896	A1	12/2007	Wydroug et al.
2006/0165060	A1	7/2006	Dua	2007/0293191	A1	12/2007	Mir et al.
2006/0168128	A1	7/2006	Sistla et al.	2007/0294395	A1	12/2007	Strub et al.
2006/0173959	A1	8/2006	McKelvie et al.	2007/0294410	A1	12/2007	Pandya et al.
2006/0174035	A1	8/2006	Tufail	2007/0297378	A1	12/2007	Poyhonen et al.
2006/0178917	A1	8/2006	Merriam et al.	2007/0298764	A1	12/2007	Clayton
2006/0178918	A1	8/2006	Mikurak	2007/0299965	A1	12/2007	Nieh et al.
2006/0182137	A1	8/2006	Zhou et al.	2007/0300252	A1	12/2007	Acharya et al.
2006/0183462	A1	8/2006	Kolehmainen	2008/0005285	A1	1/2008	Robinson et al.
2006/0190314	A1	8/2006	Hernandez	2008/0005561	A1	1/2008	Brown et al.
				2008/0010379	A1	1/2008	Zhao
				2008/0010452	A1	1/2008	Holtzman et al.
				2008/0018494	A1	1/2008	Waite et al.
				2008/0022354	A1	1/2008	Grewal et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2008/0025230 A1	1/2008	Patel et al.	2008/0270212 A1	10/2008	Blight et al.
2008/0032715 A1	2/2008	Jia et al.	2008/0279216 A1	11/2008	Sharif-Ahmadi et al.
2008/0034063 A1	2/2008	Yee	2008/0282319 A1	11/2008	Fontijn et al.
2008/0034419 A1	2/2008	Mullick et al.	2008/0293395 A1	11/2008	Matthews et al.
2008/0039102 A1	2/2008	Sewall et al.	2008/0298230 A1	12/2008	Luft et al.
2008/0049630 A1	2/2008	Kozisek et al.	2008/0305793 A1	12/2008	Gallagher et al.
2008/0050715 A1	2/2008	Golczewski et al.	2008/0311885 A1	12/2008	Dawson et al.
2008/0051076 A1	2/2008	O'Shaughnessy et al.	2008/0313315 A1	12/2008	Karaoguz et al.
2008/0052387 A1	2/2008	Heinz et al.	2008/0313730 A1	12/2008	Ifitimie et al.
2008/0056273 A1	3/2008	Pelletier et al.	2008/0316923 A1	12/2008	Fedders et al.
2008/0059474 A1	3/2008	Lim	2008/0318547 A1	12/2008	Ballou et al.
2008/0059743 A1	3/2008	Bychkov et al.	2008/0318550 A1	12/2008	DeAtley
2008/0060066 A1	3/2008	Wynn et al.	2008/0319879 A1	12/2008	Carroll et al.
2008/0062900 A1	3/2008	Rao	2008/0320497 A1	12/2008	Tarkoma et al.
2008/0064367 A1	3/2008	Nath et al.	2009/0005000 A1	1/2009	Baker et al.
2008/0066149 A1	3/2008	Lim	2009/0005005 A1	1/2009	Forstall et al.
2008/0066150 A1	3/2008	Lim	2009/0006116 A1	1/2009	Baker et al.
2008/0066181 A1	3/2008	Haveson et al.	2009/0006200 A1	1/2009	Baker et al.
2008/0070550 A1	3/2008	Hose	2009/0006229 A1	1/2009	Sweeney et al.
2008/0080457 A1	4/2008	Cole	2009/0013157 A1	1/2009	Beaule
2008/0081606 A1	4/2008	Cole	2009/0016310 A1	1/2009	Rasal
2008/0082643 A1	4/2008	Storrie et al.	2009/0036111 A1	2/2009	Danford et al.
2008/0083013 A1	4/2008	Soliman et al.	2009/0042536 A1	2/2009	Bernard et al.
2008/0085707 A1	4/2008	Fadell	2009/0044185 A1	2/2009	Krivopaltsev
2008/0089295 A1	4/2008	Keeler et al.	2009/0046707 A1	2/2009	Smires et al.
2008/0089303 A1*	4/2008	Wirtanen H04W 76/064 370/342	2009/0046723 A1	2/2009	Rahman et al.
2008/0095339 A1	4/2008	Elliott et al.	2009/0047989 A1	2/2009	Harmon et al.
2008/0096559 A1	4/2008	Phillips et al.	2009/0048913 A1	2/2009	Shenfield et al.
2008/0098062 A1	4/2008	Balia	2009/0049156 A1	2/2009	Aronsson et al.
2008/0109679 A1	5/2008	Wright et al.	2009/0049518 A1	2/2009	Roman et al.
2008/0120129 A1	5/2008	Seubert et al.	2009/0054030 A1	2/2009	Golds
2008/0120668 A1	5/2008	Yau	2009/0065571 A1	3/2009	Jain
2008/0120688 A1	5/2008	Qiu et al.	2009/0067372 A1	3/2009	Shah et al.
2008/0125079 A1	5/2008	O'Neil et al.	2009/0068984 A1	3/2009	Burnett
2008/0126287 A1	5/2008	Cox et al.	2009/0070379 A1	3/2009	Rappaport
2008/0127304 A1	5/2008	Ginter et al.	2009/0077622 A1	3/2009	Baum et al.
2008/0130534 A1	6/2008	Tomioka	2009/0079699 A1	3/2009	Sun
2008/0130656 A1	6/2008	Kim et al.	2009/0113514 A1	4/2009	Hu
2008/0132201 A1	6/2008	Karlberg	2009/0125619 A1	5/2009	Antani
2008/0132268 A1	6/2008	Choi-Grogan et al.	2009/0132860 A1*	5/2009	Liu G06F 11/366 714/38.13
2008/0134330 A1	6/2008	Kapoor et al.	2009/0157792 A1	6/2009	Fiatal
2008/0139210 A1	6/2008	Gisby et al.	2009/0163173 A1	6/2009	Williams
2008/0147454 A1	6/2008	Walker et al.	2009/0172077 A1	7/2009	Roxburgh et al.
2008/0160958 A1	7/2008	Abichandani et al.	2009/0180391 A1	7/2009	Petersen et al.
2008/0162637 A1	7/2008	Adamczyk et al.	2009/0181662 A1	7/2009	Fleischman et al.
2008/0162704 A1	7/2008	Poplett et al.	2009/0197585 A1	8/2009	Aaron
2008/0164304 A1	7/2008	Narasimhan et al.	2009/0197612 A1	8/2009	Kiiskinen
2008/0166993 A1	7/2008	Gautier et al.	2009/0203352 A1	8/2009	Fordon et al.
2008/0167027 A1	7/2008	Gautier et al.	2009/0217364 A1	8/2009	Salmela et al.
2008/0167033 A1	7/2008	Beckers	2009/0219170 A1	9/2009	Clark et al.
2008/0168275 A1	7/2008	DeAtley et al.	2009/0248883 A1	10/2009	Suryanarayana et al.
2008/0168523 A1	7/2008	Ansari et al.	2009/0254857 A1	10/2009	Romine et al.
2008/0177998 A1	7/2008	Apsangi et al.	2009/0257379 A1	10/2009	Robinson et al.
2008/0178300 A1	7/2008	Brown et al.	2009/0271514 A1	10/2009	Thomas et al.
2008/0183812 A1	7/2008	Paul et al.	2009/0282127 A1	11/2009	LeBlanc et al.
2008/0184127 A1	7/2008	Rafey et al.	2009/0286507 A1	11/2009	O'Neil et al.
2008/0189760 A1	8/2008	Rosenberg et al.	2009/0287921 A1	11/2009	Zhu et al.
2008/0201266 A1	8/2008	Chua et al.	2009/0288140 A1	11/2009	Huber et al.
2008/0207167 A1	8/2008	Bugenhagen	2009/0299857 A1	12/2009	Brubaker
2008/0212470 A1	9/2008	Castaneda et al.	2009/0307696 A1	12/2009	Vals et al.
2008/0212751 A1	9/2008	Chung	2009/0307746 A1	12/2009	Di et al.
2008/0219268 A1	9/2008	Dennison	2009/0315735 A1	12/2009	Bhavani et al.
2008/0221951 A1	9/2008	Stanforth et al.	2009/0320110 A1	12/2009	Nicolson et al.
2008/0222692 A1	9/2008	Andersson et al.	2010/0017506 A1	1/2010	Fadell
2008/0225748 A1	9/2008	Khemani et al.	2010/0020822 A1	1/2010	Zerillo et al.
2008/0229385 A1	9/2008	Feder et al.	2010/0027469 A1	2/2010	Gurajala et al.
2008/0229388 A1	9/2008	Maes	2010/0027559 A1	2/2010	Lin et al.
2008/0235511 A1	9/2008	O'Brien et al.	2010/0030890 A1	2/2010	Dutta et al.
2008/0240373 A1	10/2008	Wilhelm	2010/0041364 A1	2/2010	Lott et al.
2008/0250053 A1	10/2008	Aaltonen et al.	2010/0041365 A1	2/2010	Lott et al.
2008/0256593 A1	10/2008	Vinberg et al.	2010/0042675 A1	2/2010	Fujii
2008/0262798 A1	10/2008	Kim et al.	2010/0043068 A1	2/2010	Varadhan et al.
2008/0263348 A1	10/2008	Zaltsman et al.	2010/0071053 A1	3/2010	Ansari et al.
2008/0268813 A1	10/2008	Maes	2010/0075666 A1	3/2010	Garner
			2010/0080202 A1	4/2010	Hanson
			2010/0082431 A1	4/2010	Ramer et al.
			2010/0103820 A1	4/2010	Fuller et al.
			2010/0121744 A1	5/2010	Belz et al.

(56)

References Cited

FOREIGN PATENT DOCUMENTS

U.S. PATENT DOCUMENTS					
			CN	1345154 A	4/2002
			CN	1508734 A	6/2004
			CN	1538730 A	10/2004
			CN	1567818 A	1/2005
2010/0131584 A1	5/2010	Johnson	CN	101035308 A	3/2006
2010/0144310 A1	6/2010	Bedingfield	CN	1801829 A	7/2006
2010/0151866 A1	6/2010	Karpov et al.	CN	1802839 A	7/2006
2010/0153781 A1	6/2010	Hanna	CN	1889777 A	7/2006
2010/0167696 A1	7/2010	Smith et al.	CN	101155343 A	9/2006
2010/0188975 A1	7/2010	Raleigh	CN	1867024 A	11/2006
2010/0188990 A1	7/2010	Raleigh	CN	1878160 A	12/2006
2010/0188992 A1	7/2010	Raleigh	CN	1937511 A	3/2007
2010/0188994 A1	7/2010	Raleigh	CN	101123553 A	9/2007
2010/0190469 A1	7/2010	Vanderveen et al.	CN	101080055 A	11/2007
2010/0191576 A1	7/2010	Raleigh	CN	101115248 A	1/2008
2010/0191612 A1	7/2010	Raleigh	CN	101127988 A	2/2008
2010/0191846 A1	7/2010	Raleigh	CN	101183958 A	5/2008
2010/0192170 A1	7/2010	Raleigh	CN	101335666 A	12/2008
2010/0192212 A1	7/2010	Raleigh	CN	101341764 A	1/2009
2010/0195503 A1	8/2010	Raleigh	CN	101815275 A	8/2010
2010/0197268 A1	8/2010	Raleigh	CN	1289326 A1	3/2003
2010/0198698 A1	8/2010	Raleigh et al.	EP	1463238	9/2004
2010/0198939 A1	8/2010	Raleigh	EP	1503548 A1	2/2005
2010/0235329 A1	9/2010	Koren et al.	EP	1545114 A1	6/2005
2010/0241544 A1	9/2010	Benson et al.	EP	1739518	1/2007
2010/0248719 A1	9/2010	Scholaert	EP	1772988	4/2007
2010/0284327 A1	11/2010	Miklos	EP	1850575	10/2007
2010/0287599 A1	11/2010	He	EP	1887732 A1	2/2008
2010/0311402 A1	12/2010	Srinivasan et al.	EP	1978772	10/2008
2010/0318652 A1	12/2010	Samba	EP	2007065 A1	12/2008
2010/0325420 A1	12/2010	Kanekar	EP	2466831 A1	6/2012
2011/0013569 A1	1/2011	Scherzer et al.	EP	3148713 B2	3/2001
2011/0019574 A1	1/2011	Malomsoky et al.	EP	2005339247 A	12/2005
2011/0081881 A1	4/2011	Baker et al.	JP	2006041989	2/2006
2011/0082790 A1	4/2011	Baker et al.	JP	2006155263 A	6/2006
2011/0110309 A1	5/2011	Bennett	JP	2006-197137	7/2006
2011/0126141 A1	5/2011	King et al.	JP	2006-344007	12/2006
2011/0145920 A1	6/2011	Mahaffey et al.	JP	2007-318354	12/2007
2011/0159818 A1	6/2011	Scherzer et al.	JP	2008-301121	12/2008
2011/0173678 A1	7/2011	Kaippallimalil et al.	JP	2009-111919	5/2009
2011/0195700 A1	8/2011	Kukuchka et al.	JP	2009-212707	9/2009
2011/0238545 A1	9/2011	Fanaian et al.	JP	2009-218773	9/2009
2011/0241624 A1	10/2011	Park et al.	JP	2009-232107	10/2009
2011/0264923 A1	10/2011	Kocher et al.	JP	9858505	12/1998
2011/0277019 A1	11/2011	Pritchard, Jr.	JP	9927723 A1	6/1999
2012/0020296 A1	1/2012	Scherzer et al.	WO	9965185	12/1999
2012/0029718 A1	2/2012	Davis	WO	2011002450 A1	1/2001
2012/0101952 A1	4/2012	Raleigh et al.	WO	0245315	6/2002
2012/0108225 A1	5/2012	Luna et al.	WO	02067616 A1	8/2002
2012/0144025 A1*	6/2012	Melander H04L 47/2441 709/224	WO	02093877	11/2002
2012/0155296 A1	6/2012	Kashanian	WO	03014891	2/2003
2012/0166364 A1*	6/2012	Ahmad H04L 12/585 706/10	WO	03017063 A2	2/2003
2012/0166604 A1	6/2012	Fortier et al.	WO	03017065 A2	2/2003
2012/0196644 A1	8/2012	Scherzer et al.	WO	03058880	7/2003
2012/0238287 A1	9/2012	Scherzer	WO	2004028070	4/2004
2012/0330792 A1	12/2012	Kashanian	WO	2004064306 A2	7/2004
2013/0024914 A1	1/2013	Ahmed et al.	WO	2004077797	9/2004
2013/0029653 A1	1/2013	Baker et al.	WO	2004095753	11/2004
2013/0030960 A1	1/2013	Kashanian	WO	2005008995	1/2005
2013/0058274 A1	3/2013	Scherzer et al.	WO	2005083934	9/2005
2013/0065555 A1	3/2013	Baker et al.	WO	2006004467	1/2006
2013/0072177 A1*	3/2013	Ross G06F 8/61 455/418	WO	2006004784	1/2006
2013/0084835 A1	4/2013	Scherzer et al.	WO	2006012610	2/2006
2013/0095787 A1	4/2013	Kashanian	WO	2006050758	5/2006
2013/0103376 A1	4/2013	Gaddam et al.	WO	2006073837	7/2006
2013/0111572 A1	5/2013	Gaddam et al.	WO	2006077481	7/2006
2013/0117140 A1	5/2013	Kashanian	WO	2006093961	9/2006
2013/0117382 A1	5/2013	Gaddam et al.	WO	2006120558	11/2006
2013/0144789 A1	6/2013	Aaltonen et al.	WO	2006130960	12/2006
2013/0149994 A1	6/2013	Gaddam et al.	WO	2007001833	1/2007
2013/0183937 A1	7/2013	Neal et al.	WO	2007014630	2/2007
2013/0326356 A9	12/2013	Zheng et al.	WO	2007018363	2/2007
2014/0073291 A1	3/2014	Hildner et al.	WO	2007053848	5/2007
2014/0241342 A1*	8/2014	Constantinof H04L 65/1079 370/352	WO	2007068288 A1	6/2007
			WO	2007069245	6/2007
			WO	2007097786	8/2007
			WO	2007107701	9/2007

(56)

References Cited

FOREIGN PATENT DOCUMENTS

WO	2007120310	10/2007
WO	2007124279	11/2007
WO	2007126352	11/2007
WO	2007133844	11/2007
WO	2008017837	2/2008
WO	2008051379	5/2008
WO	2008066419	6/2008
WO	2008080139	7/2008
WO	2008080430	7/2008
WO	2008099802	8/2008
WO	2009008817	1/2009
WO	2009091295	7/2009
WO	2010088413	8/2010
WO	2011149532 A1	12/2011
WO	2012047275	4/2012

OTHER PUBLICATIONS

3rd Generation Partnership Project, "Technical Specification Group Services and System Aspects; Policy and Charging Control Architecture," Release 8, Document No. 3GPP TS 23.203, V8.4.0, Dec. 2008.

Alonistioti et al., "Intelligent Architectures Enabling Flexible Service Provision and Adaptability," 2002.

Amazon Technologies, Inc., "Kindle™ User's Guide," 3rd Edition, Copyright 2004-2009.

Chandrasekhar et al., "Femtocell Networks: A Survey," Jun. 28, 2008.

Chaouchi et al., "Policy Based Networking in the Integration Effort of 4G Networks and Services," 2004 IEEE.

Cisco Systems, Inc., "Cisco Mobile Exchange (CMX) Solution Guide: Chapter 2—Overview of GSM, GPRS, and UMTS," Nov. 4, 2008.

Dikaiaikos et al., "A Distributed Middleware Infrastructure for Personalized Services," Nov. 24, 2003.

European Commission, "Data Roaming Tariffs—Transparency Measures," [online] retrieved from http://web.archive.org/web/20081220232754/http://ec.europa.eu/information_society/activities/roaming/data/measures/index_en.htm, Dec. 20, 2008 [retrieved May 16, 2012].

Farooq et al., "An IEEE 802.16 WiMax Module for the NS-3 Simulator," Mar. 2-6, 2009.

Han et al., "Information Collection Services for QoS-Aware Mobile Applications," 2005.

Hartmann et al., "Agent-Based Banking Transactions & Information Retrieval—What About Performance Issues?" 1999.

Hewlett-Packard Development Company, LP, "IP Multimedia Services Charging," white paper, Jan. 2006.

Hossain et al., "Gain-Based Selection of Ambient Media Services in Pervasive Environments," Mobile Networks and Applications. Oct. 3, 2008.

Knight et al., "Layer 2 and 3 Virtual Private Networks: Taxonomy, Technology, and Standardization Efforts," IEEE communications Magazine, Jun. 2004.

Koutsopoulou et al., "Middleware Platform for the Support of Charging Reconfiguration Actions," 2005.

Kyriakakos et al., "Ubiquitous Service Provision in Next Generation Mobile Networks," Proceedings of the 13th IST Mobile and Wireless Communications Summit, Lyon, France, Jun. 2004.

Li, Yu, "Dedicated E-Reading Device: The State of the Art and The Challenges," Scroll, vol. 1, No. 1, 2008.

Nilsson et al., "A Novel MAC Scheme for Solving the QoS Parameter Adjustment Problem in IEEE802.11e EDCA," Feb. 2006.

Oppliger, Rolf, "Internet Security: Firewalls and Beyond," Communications of the ACM, May 1997, vol. 40, No. 5.

Rao et al., "Evolution of Mobile Location-Based Services," Communication of the ACM, Dec. 2003.

Steglich, Stephan, "I-Centric User Interaction," Nov. 21, 2003.

Van Eijk, et al., "GigaMobile, Agent Technology for Designing Personalized Mobile Service Brokerage," Jul. 1, 2002.

Zhu et al., "A Survey of Quality of Service in IEEE 802.11 Networks," IEEE Wireless Communications, Aug. 2004.

Anton, B. et al., "Best Current Practices for Wireless Internet Service Provider (WISP) Roaming"; Release Date Feb. 2003, Version 1.0; Wi-Fi Alliance—Wireless ISP Roaming (WISPr).

Ruckus Wireless—White Paper; "Smarter Wi-Fi for Mobile Operator Infrastructures" 2010.

Accuris Networks, "The Business Value of Mobile Data Offload—a White Paper", 2010.

Wireless Broadband Alliance, "WISPr 2.0, Apr. 8, 2010"; Doc. Ref. No. WBA/RM/WISPr, Version 01.00.

Thurston, Richard, "WISPr 2.0 Boosts Roaming Between 3G and Wi-Fi"; Jun. 23, 2010; Web page from zdnet.com; Zdnet.com/wispr-2-0-boosts-roaming-between-3g-and-wi-fi-3040089325/.

Wi-Fi Alliance Technical Committee Hotspot 2.0 Technical Task Group, "Hotspot 2.0 (Release 1) Technical Specification—Version 1.0.0"; 2012.

Wi-Fi Alliance Hotspot 2.0 Technical Task Group, "Wi-Fi Certified Passpoint™ (Release 1) Deployment Guidelines—Version 1.0—Oct. 2012".

Ahmed et al., "A Context-Aware Vertical Handover Decision Algorithm for Multimode Mobile Terminals and Its Performance," BenQ Mobile, Munich Germany; University of Klagenfurt, Klagenfurt, Austria; 2006.

Kassar et al., "An overview of vertical handover decision strategies in heterogeneous wireless networks," ScienceDirect, University Pierre & Marie Curie, Paris, France, Jun. 5, 2007.

Schiller et al., "Location-Based Services," The Morgan Kaufmann Series in Data Management Systems, 2004.

Sadeh et al., "Understanding and Capturing People's Privacy Policies in a Mobile Social Networking Application," ISR School of Computer Science, Carnegie Mellon University, 2007.

Jing et al., "Client-Server Computing in Mobile Environments," GTE Labs. Inc., Purdue University, ACM Computing Surveys, vol. 31, No. 2, Jun. 1999.

Rivadeneira et al., "A communication architecture to access data services through GSM," San Sebastian, Spain, 1998.

Loopt User Guide, metroPCS, Jul. 17, 2008.

"Jentro Technologies launches Zenlet platform to accelerate location-based content delivery to mobile devices," The Mobile Internet, Boston, MA, Feb. 2008.

"Ads and movies on the run," the Gold Coast Bulletin, Southport, Qld, Jan. 29, 2008.

Richtel, "Cellphone consumerism; If even a debit card is too slow, now you have a new way to act on impulse: [National Edition]," National Post, Canada, Oct. 2, 2007.

Kim, "Free wireless a high-wire act; MetroFi needs to draw enough ads to make service add profits," San Francisco Chronicle, Aug. 21, 2006.

Koutsopoulou et al., "Charging, Accounting and Billing Management Schemes In Mobile Telecommunication Networks and the Internet," IEEE Communications Surveys & Tutorials, First Quarter 2004, vol. 6, No. 1.

Sun et al., "Towards Connectivity Management Adaptability: Context Awareness in Policy Representation and End-to-end Evaluation Algorithm," Dept. of Electrical and Information Engineering, Univ. of Oulu, Finland, 2004.

Sabat, "The evolving mobile wireless value chain and market structure," Nov. 2002.

Nuzman et al., "A compound model for TCP connection arrivals for LAN and WAN applications," Oct. 22, 2002.

Kuntze et al., "Trustworthy content push," Fraunhofer-Institute for Secure Information Technology SIT; Germany; WCNC 2007 proceedings, IEEE.

Blackberry Mobile Data System, version 4.1, Technical Overview, 2006.

Client Guide for Symantec Endpoint Protection and Symantec Network Access Control, 2007.

Ehnert, "Small application to monitor IP traffic on a Blackberry—1.01.03", Mar. 27, 2008; <http://www.ehnert.net/MiniMoni/>.

(56)

References Cited**OTHER PUBLICATIONS**

NetLimiter Lite 4.0.19.0; <http://www.heise.de/download/netlimiter-lite-3617703.html> from vol. 14/2007.

Muntermann et al., "Potentiale und Sicherheitsanforderungen mobiler Finanzinformationsdienste und deren Systeminfrastrukturen," Chair of Mobile Commerce & Multilateral Security, Goethe Univ. Frankfurt, 2004.

Kasper et al., "Subscriber Authentication in mobile cellular Networks with virtual software SIM Credentials using Trusted Computing," Fraunhofer-Institute for Secure Information Technology SIT, Darmstadt, Germany; ICACT 2008.

Fujitsu, "Server Push Technology Survey and Bidirectional Communication in HTTP Browser," Jan. 9, 2008 (JP).

Roy et al., "Energy Management in Mobile Devices with the Cinder Operating System", Stanford University, MIT CSAIL, Jun. 3, 2010. Windows7 Power Management, published Apr. 2009.

Quintana, David, "Mobile Multitasking," Apr. 14, 2010.

Open Mobile Alliance (OMA), Push Architecture, Candidate Version 2.2; Oct. 2, 2007; OMA-AD-Push-V2_2-20071002-C.

VerizonWireless.com news, "Verizon Wireless Adds to Portfolio of Cosumer-Friendly Tools With Introduction of Usage Controls, Usage Controls and Chaperone 2.0 Offer Parents Full Family Security Solution," Aug. 18, 2008.

"The Construction of Intelligent Residential District in Use of Cable Television Network," Shandong Science, vol. 13, No. 2, Jun. 2000.

"Communication Concepts for Mobile Agent Systems," by Joachim Baumann et al.; Inst. of Parallel and Distributed High-Performance Systems, Univ. of Stuttgart, Germany, pp. 123-135, 1997.

"Prevent iCloud Documents & Data from using your data plan," Oct. 26, 2011; CNET webarchive, by Jason Ciprian.

"3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; Policy and charging control architecture (Release 11)," 3GPP Standard; 3GPP TS 23203 v11.6.0; Sophia Antipolis, France; pp. 1-177; Jun. 2012.

"End to End QoS Solution for Real-time Multimedia Application;" Computer Engineering and Applications, 2007, 43 (4):155-159, by Tan Zu-guo, Wang Wen-juan; Information and Science School, Zhanjian Normal College, Zhan jiang, Guangdong 524048, China.

"ASA/PIX: Allow Split Tunneling for VPN Clients on the ASA Configuration Example," Document ID 70917, Jan. 10, 2008.

Dixon et al., Triple Play Digital Services: Comcast and Verizon (Digital Phone, Television, and Internet), Aug. 2007.

3rd Generation Partnership Project; "Technical Specification Group Services and System Aspects; IP Flow Mobility and seamless WLAN offload; Stage 2," Release 10, Document No. 3GPP TS 23261, V1.0.0, Mar. 2010.

3rd Generation Partnership Project, "Technical Specification Group Core Network and Terminals; Access Network Discovery and Selection Function (ANDSF) Management Object (MO)," Release 9, Document No. 3GPP TS 24.312, V9.1.0, Mar. 2010.

Ahmed et al., "Multi Access Data Network Connectivity and IP Flow Mobility in Evolved Packet System (EPS)," 2010 IEEE.

* cited by examiner




FIG. 1





FIG. 2






FIG. 4A




FIG. 4B




FIG. 4C




FIG. 5




FIG. 6




FIG. 7




FIG. 8A




FIG. 8B




FIG. 8C




FIG. 9




FIG. 10





FIG. 11






FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22

	NBS 10%	NBS 25%	NBS 50%	NBS 75%	NBS 90%
Outlook	6	5	4	3	2
Skype	7	6	2	1	0
Safari	5	4	3	2	1
Pandora	5	4	3	2	1
FaceBook	4	3	2	1	0
iTunes	7	6	3	1	0
QuickTime	8	6	4	1	0
AV Software	9	7	5	3	1
Online Backup	3	2	1	1	0
OS Update	2	1	0	0	0

FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31A




FIG. 31B




FIG. 32




FIG. 33




FIG. 34




FIG. 35




FIG. 36

3700 →




FIG. 37

1

MOBILE DEVICE AND METHOD ATTRIBUTING MEDIA SERVICES NETWORK USAGE TO REQUESTING APPLICATION

BACKGROUND

With the advent of mass market digital communications, applications and content distribution, many access networks such as wireless networks, cable networks and Digital Subscriber Line (DSL) networks are pressed for user capacity, with, for example Evolution-Data Optimized (EVDO), High Speed Packet Access (HSPA), Long Term Evolution (LTE), Worldwide Interoperability for Microwave Access (WiMax), DOCSIS, DSL, and Wireless Fidelity (Wi-Fi) becoming user capacity constrained. In the wireless case, although network capacity will increase with new higher capacity wireless radio access technologies, such as Multiple-Input Multiple-Output (MIMO), and with more frequency spectrum and cell splitting being deployed in the future, these capacity gains are likely to be less than what is required to meet growing digital networking demand.

Similarly, although wire line access networks, such as cable and DSL, can have higher average capacity per user compared to wireless, wire line user service consumption habits are trending toward very high bandwidth applications and content that can quickly consume the available capacity and degrade overall network service experience. Because some components of service provider costs go up with increasing bandwidth, this trend will also negatively impact service provider profits. In addition, it is becoming increasingly important to associate device access network services usage (e.g., network data services usage, voice services usage, etc.) to the applications (e.g., application, widget, service, process, embedded object, or any combination of these, etc.) that are using the services.

The foregoing example of trends and issues is intended to be illustrative and not exclusive. Other limitations of the art will become apparent to those of skill in the relevant art upon a reading of the specification and a study of the drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates a functional diagram of a network architecture for providing quality of service (QoS) for device assisted services (DAS) and/or for providing DAS for protecting network capacity in accordance with some embodiments.

FIG. 2 illustrates another functional diagram of another network architecture for providing quality of service (QoS) for device assisted services (DAS) and/or for providing DAS for protecting network capacity in accordance with some embodiments.

FIG. 3 illustrates a functional diagram of an architecture including a device based service processor and a service controller for providing quality of service (QoS) for device assisted services (DAS) and/or for providing DAS for protecting network capacity in accordance with some embodiments.

FIGS. 4A through 4C illustrate a functional diagram for providing quality of service (QoS) for device assisted services (DAS) in accordance with some embodiments.

FIG. 5 illustrates a functional diagram for generating a QoS activity map for quality of service (QoS) for device assisted services (DAS) in accordance with some embodiments.

2

FIG. 6 illustrates a functional diagram for quality of service (QoS) for device assisted services (DAS) for an end to end coordinated QoS service channel control in accordance with some embodiments.

FIG. 7 illustrates a flow diagram for quality of service (QoS) for device assisted services (DAS) in accordance with some embodiments.

FIGS. 8A through 8C each illustrate another flow diagram for quality of service (QoS) for device assisted services (DAS) in accordance with some embodiments.

FIG. 9 illustrates another flow diagram for quality of service (QoS) for device assisted services (DAS) in accordance with some embodiments.

FIG. 10 illustrates another flow diagram for quality of service (QoS) for device assisted services (DAS) in accordance with some embodiments.

FIG. 11 illustrates another flow diagram for quality of service (QoS) for device assisted services (DAS) in accordance with some embodiments.

FIG. 12 illustrates a device stack for providing various service usage measurement techniques in accordance with some embodiments.

FIG. 13 illustrates another device stack for providing various service usage measurement techniques in accordance with some embodiments.

FIG. 14 illustrates a flow diagram for device assisted services (DAS) for protecting network capacity in accordance with some embodiments.

FIG. 15 illustrates another flow diagram for device assisted services (DAS) for protecting network capacity in accordance with some embodiments.

FIG. 16 illustrates another flow diagram for device assisted services (DAS) for protecting network capacity in accordance with some embodiments.

FIG. 17 illustrates another flow diagram for device assisted services (DAS) for protecting network capacity in accordance with some embodiments.

FIG. 18 illustrates another flow diagram for device assisted services (DAS) for protecting network capacity in accordance with some embodiments.

FIG. 19 illustrates another flow diagram for device assisted services (DAS) for protecting network capacity in accordance with some embodiments.

FIG. 20 illustrates another flow diagram for device assisted services (DAS) for protecting network capacity in accordance with some embodiments.

FIG. 21 illustrates another flow diagram for device assisted services (DAS) for protecting network capacity in accordance with some embodiments.

FIG. 22 illustrates another flow diagram for device assisted services (DAS) for protecting network capacity in accordance with some embodiments.

FIG. 23 illustrates a network capacity controlled services priority level chart for device assisted services (DAS) for protecting network capacity in accordance with some embodiments.

FIG. 24 depicts a diagram of a network capacity protection system utilizing device-assisted services (DAS).

FIG. 25 depicts a diagram an example of a differential access control notification system.

FIG. 26 depicts an example of a computer system on which techniques described in this paper can be implemented.

FIG. 27 depicts a diagram of an example of a system for application-specific differential network access control.

FIG. 28 depicts an example of a system for flow tracking.

3

FIG. 29 depicts a flowchart of an example of a method of flow tracking.

FIG. 30 depicts an example of a system with a tagged traffic flow.

FIGS. 31A and 31B depict a flowchart of an example of a method of virtual tagging.

FIG. 32 depicts an example of a system for classification mapping using virtual tagging.

FIG. 33 depicts an example of a media service classification system.

FIG. 34 depicts a conceptual diagram of a proxy encapsulated frame.

FIG. 35 depicts an example of a system for proxy client counting.

FIG. 36 depicts an example of a system for classifying traffic and enforcing a service policy based upon the classification.

FIG. 37 depicts a flowchart of an example of a method for flow tagging and enforcing service policies associated with an identified initiator of the flow.

DETAILED DESCRIPTION

The invention can be implemented in numerous ways, including as a process; an apparatus; a system; a composition of matter; a computer program product embodied on a computer readable storage medium; and/or a processor, such as a processor configured to execute instructions stored on and/or provided by a memory coupled to the processor. In this specification, these implementations, or any other form that the invention may take, may be referred to as techniques. In general, the order of the steps of disclosed processes may be altered within the scope of the invention. Unless stated otherwise, a component such as a processor or a memory described as being configured to perform a task may be implemented as a general component that is temporarily configured to perform the task at a given time or a specific component that is manufactured to perform the task. As used herein, the term 'processor' refers to one or more devices, circuits, and/or processing cores configured to process data, such as computer program instructions.

A detailed description of one or more embodiments of the invention is provided below along with accompanying figures that illustrate the principles of the invention. The invention is described in connection with such embodiments, but the invention is not limited to any embodiment. The scope of the invention is limited only by the claims and the invention encompasses numerous alternatives, modifications and equivalents. Numerous specific details are set forth in the following description in order to provide a thorough understanding of the invention. These details are provided for the purpose of example and the invention may be practiced according to the claims without some or all of these specific details. For the purpose of clarity, technical material that is known in the technical fields related to the invention has not been described in detail so that the invention is not unnecessarily obscured.

As the network capacity gains are less than what is required to meet growing digital networking demand, a network capacity crunch is developing due to increasing network congestion on various wireless networks, such as mobile networks. The increasing popularity of various smart phone devices, net book devices, tablet computing devices, and various other wireless mobile computing devices, which are becoming increasingly popular on 3G, 4G, and other advanced wireless networks, is contributing to the network capacity crunch. Some network carriers have indicated that

4

a relatively small number of users on such devices demand a disproportionately significant amount of their network capacity. For example, AT&T has recently indicated that about 3 percent of its smart phone device users (e.g., Apple iPhone® users) are generating approximately 40 percent of the operator's data traffic.

For example, in wireless networks, managing the wireless access connection capacity and network access connection resources is important to maintain network performance as network resources/capacity demand increases. Many network performance measures can be advantageously maintained or improved as network loading increases if capacity management and/or network resource management is employed. For example, these performance measures include network availability; the ability to deliver connections to all devices, users and/or applications seeking connections and enabled for service on the network; network access attempt success rate; the transmission speed experienced by one or more devices, users or applications; the average transmission speed experienced by all devices, users and/or applications; network bit error rate or packet error rate; the time delay from network access request to delivered access connection; the one-way delay or round-trip delay for a transmission; the delay timing jitter for a transmission; the time variation in transmission speed for one or more connections; the ability of the network to deliver various requested/needed levels of Quality of Service (QoS) to devices, users or applications that require differentiated connection QoS classes; the ability of the network to maintain efficiency (e.g., aggregated service throughput measured across all devices, users, and/or applications); the ability of the network to share or distribute a performance measure (e.g., the performance measures listed above) uniformly or fairly across multiple devices, users, and/or applications that all have the same service quality class or the same service plan performance parameters.

For example, if there is a limited amount of shared bandwidth for a set of user devices (e.g., a set of devices on a wireless network, such as a given base station or base station controller or femto cell or pico cell; or a set of devices on a cable modem networks, etc.), and if multiple and/or all devices allow all applications to indiscriminately access or attempt to access network resources or transmit/receive traffic, then the network can generally become overloaded. As a result, a subset of users/devices or in some cases most or all users/devices obtain poor network performance. As another example, if one or more devices forming a subset of devices on the network allow multiple and/or all applications to indiscriminately access or attempt to access network resources or transmit/receive traffic, then the network can become overloaded. As a result, a subset of users/devices or in some cases most or all users/devices obtain poor network performance.

Traditionally, mobile devices typically have specialized designs that are optimized to preserve network capacity and protect network resources from being over taxed. For example, wireless devices that browse the Internet often use specialized protocols such as WAP and data traffic compression or low resolution techniques rather than standard HTTP protocols and traffic used in wired Internet devices.

However, the wireless devices that implement specialized methods for accessing the Internet and/or other networks often implement complex specifications provided by one or more wireless carriers that own the networks that the device is designed to connect to. Such complex specifications often require time consuming design, testing, and certification processes. These processes in part have the effect of nar-

5

rowing the base of device suppliers to those qualified and willing to perform the specialized design work required, slowing time to market for new devices, increasing the expense to develop new devices and reducing the types of applications that are supported.

Device OEMs have recently created wireless devices that are designed more like standard Internet devices and not fully optimized to preserve network capacity and resources. Many wireless service customers desire this type of device, and the OEMs generally want to reduce the complexity and time to market to deliver such devices. In addition, new market needs and new government requirements sometimes require that carriers offer a more open process for bringing new devices onto their network, in which the process does not require all of the specialized design and certification described above. These and various other factors are driving a growing need and trend for less complex and time consuming wireless device design and certification processes.

This trend has led many carriers to begin selling devices that are designed more as standard Internet service devices that connect to the Internet and other data networks through carrier wireless networks. As the cellular network is opened up to more and more new devices, applications and markets, there is a growing demand to allow general purpose Internet devices and applications to gain access to wireless networks without necessarily going through specialized design and certification process requirements to make the devices and applications efficient and authorized for access to such wireless networks.

However, general purpose Internet devices are not as frugal or sparing with wireless network access bandwidth. Moreover, with the advent of always on wide area network connections to the Internet has led to popular Internet services and applications that typically assume very inexpensive access and generally heed no attention to, for example, network busy state. As more general purpose Internet devices are provided for us on various wireless networks (e.g., mobile wireless networks), a high frequency of inefficient wireless network accesses continue to rise, which can reduce network capacity sometimes to levels that hinder access to service for that device (e.g., user, device, software demand) and/or other devices on that wireless network and/or that wireless network segment. As discussed above, judicious use of wireless network bandwidth, capacity, and resources generally results in better service for all users, but at present, device manufacturers and wireless network providers (e.g., wireless network carriers or carriers) have not provided or implemented more intelligent bandwidth usage techniques. These factors generally result in less carrier control of device design, which poses a threat to longer term network capacity and performance preservation as the volume of devices with less optimized wireless designs continues to grow.

There are many network performance and user performance factors that are impacted by the efficiency of the network, including, for example, overall network congestion; the access network performance experienced by one or more groups of users, devices, applications, network service sources, communication protocols, and/or operating system functions; and/or the performance experienced by a given user, device, application, network service source, communication protocol, and/or operating system function. Under a relatively low capacity demand of a wireless network, network performance as experienced by a group of devices, applications, network service sources, communication protocols, operating system functions, and/or users or by a single device, application, network service source, commu-

6

nication protocol, operating system function, and/or user can degrade somewhat proportionally (e.g., aggregate traffic delivered by the network may be roughly proportional to the peak available network traffic) with incremental increases in network access and/or traffic demand from one or more groups of users, devices, applications, network service sources, communication protocols and/or operating system functions. However, as network resources/network capacity demand increases (e.g., more wireless network data traffic is demanded in aggregate; more devices are serviced by the network; more users are serviced by the network; more applications are serviced by the network; more network service sources are serviced by the network; more operating system functions are serviced by the network; and/or more differentiated QoS sessions are serviced by the network), network availability/performance can decrease and/or the network may not adequately service one or more users, devices, applications, network service sources, communication protocols, and/or operating system functions, or may not service one or more groups of users, devices, applications, network service sources, communication protocols, and/or operating system functions.

There are many examples of how increasing network capacity demand can decrease network performance, including for example, to a decrease in average bandwidth offered per device (e.g., one or more users on a device, application, network service source, communication protocol, and/or operating system function executed/implemented on the device); an increase in traffic delivery latency; an increase in traffic delivery latency jitter; insufficient guaranteed or differentiated bandwidth for one or more differentiated QoS and/or dynamic QoS services (e.g., as described herein) to one or more devices, users, applications, network service sources, communication protocols, and/or operating system functions; increased latency for bandwidth reservation services; increased latency for QoS reservation services; performance problems with one or more communication protocols; unacceptable delays in user experience, and/or various other or similar consequences and device or user impacts resulting from reduced network availability and/or reduced network capacity. Examples of network communication protocols that can have degraded performance with excessive network loading or degraded network performance include, for example, Internet protocol (IP), HTML protocols, voice communication protocols including VOIP protocols, real-time video communication protocols, streaming media protocols (e.g., audio, video, etc), gaming protocols, VPN protocols, file download protocols, background service protocols, software update protocols, and/or various other network communication protocols. Thus, is it important to preserve/protect network capacity.

It is also important to control the number of transactions demanded from a given network resource (e.g., edge network segment, base station, base station controller, MAC resources, pico cell, femto cell, etc.) in a given period of time so that demand does not overcome the transaction servicing ability of that network resource. For example, network resources that should not be subjected to excess transaction demand can include base station or base station controller resources, media access control (MAC) resources, traffic transport resources, AAA resources, security or authentication resources, home agent (HA) resources, DNS resources, resources that play a part in network discovery, gateway or router resources, data session reservation or establishment resources (e.g., network resources required to manage, set up, conduct, and/or close service sessions, PPP sessions, communication flows, communication streams,

QoS flows, radio access bearer reservation resources, tunnels, VPNs, APNs, special service routing, etc.), bandwidth reservation resources, QoS reservation or coordination resources, QoS transport resources, service charging resources, traffic analysis resources, network security resources, and/or various other or similar network resources. In some networks, the network performance degradation due to a given measure of incremental increase in network resource/capacity demand can become relatively large as various network resources become increasingly taxed due to either limited transaction processing capability or limited traffic bandwidth for one or more of the network resources that participate in establishing, servicing, conducting, maintaining, and/or closing the necessary network service connections and/or information exchanges required to conduct a service activity. For example, if the equipment required to establish a PPP session can only handle a certain number of new PPP session openings and/or closings per given period of time, and if device behavior is such that PPP sessions are often opened and/or closed, then the rate of PPP session transactions (e.g., openings and/or closings) can exceed the transaction capacity of the PPP session management resources. This is sometimes referred to as “flooding” or “overloading” a network resource with excess demand or excess connections, and, in such cases, the network resource may begin falling behind in servicing transaction demand in a well controlled manner (e.g., the network resource may continue processing transactions at or near a maximum rate for that network resource), or in some cases, the resource may fall behind transaction demand in a less well controlled manner (e.g., the network resource may become overwhelmed such that its processing rate not only falls below aggregate transaction demand, but the transaction rate processing capability decreases under overload as well). In the PPP session establishment resource example, once the rate of requested transactions exceeds the resource maximum transaction rate, then unmet device demand can grow to a point where one or more devices experiences delays in connecting to and/or communicating (e.g., sending/receiving data) with the network.

As another example, in any type of random access bandwidth reservation protocol, MAC protocol, or bandwidth delivery protocol, in a network without proper management and/or control of traffic access reservations and/or transmissions, as the network demand increases there may be more collisions between reservation requests, traffic transmissions, application demands, network service source demands, communication protocol demands, and/or operating system function demands causing a decreasing network efficiency that can degrade user, device, application and/or network service performance so that performance falls below acceptable levels. As another example, in systems in which there is a QoS service session reservation system, uncontrolled and/or unmanaged QoS reservation requests and/or reservation grants can lead to a situation where the QoS reservation resources and/or QoS service delivery resources are over taxed to the point where QoS service performance falls below desired levels. As another example, in networks that require some form of minimum resource allocation for transmissions, reservations, or network resource transactions, the network can become inefficient if one or more devices, applications, network service sources, operating system functions, and/or communication protocols have a relatively high rate of network resource access attempts, network accesses or data transmissions for small transmission payloads (e.g., minimum MAC reservation factors, minimum security overhead factors, minimum QoS

reservation factors, minimum time responses for establishing a base station connection, minimum time responses for establishing or closing/being released from a session, etc). Even if the data packet comprising the access event is small, the network resources required to complete the access event are often busy servicing the access event for much longer periods of time than are required for the actual data transmission.

Another example of device service activity behavior that can have an impact on network performance is the way the device, device subsystem, and/or modem subsystem power cycling or transitions from one power save state to another. For example, establishing a basic connection from a device to a wireless base station consumes base station resources for a period of time and in some cases can also consume other network resources such as AAA, HLR, HA, gateway, billing, and/or charging gateway resources. If a device terminates the connection to the base station when the modem subsystem (e.g., or some other portion of the device) goes from active connection state to a power save state, then each time the device enters power save state and then exits power save state network resources are consumed, sometimes for time periods measured on the order of seconds or in extreme cases even minutes. If such a device has an aggressive power save algorithm that enters power save state after a short idle period, then the device behavior can consume a proportionally large amount of resources such that the network ability to support multiple devices is diminished, or such that the network cannot support very many similar devices on the network. Another similar example is the establishment of network sessions once the base station connection is established (e.g., establishing a PPP session between the device and a home agent (HA) or other gateway), in which network resources required to open and/or close the network session are ignorantly consumed if a device exhibits aggressive power save state cycling or frequently terminates the data session for other reasons.

Another example of device service activity behavior that can impact network performance is applications that maintain persistent network communication that generates a relatively high frequency of network data packets. Some applications have persistent signaling that falls into this category. Specific examples include frequent device signaling sequences to update widgets on a desktop; synchronize user data such as calendars, contacts, email, and/or other information/content; check or update email or RSS feeds; access social networking websites or tools; online text, voice or video chat tools; update real-time information; and conduct other repetitive actions. Additional application behavior that can significantly tie up network resources and capacity include, for example, conference meeting services, video streaming, content update, software update, and/or other or similar application behavior. For example, even when the user is not directly interacting with or benefiting from this type of application, the application can be running in the background and continuing to consume potentially significant network resources.

For example, the types of service activities and/or device behavior that can reduce network capacity and/or network resource availability include software updates for OS and applications, frequent OS and application background network accesses and signaling, frequent network discovery and/or signaling (e.g., EtherType messages, ARP messages, and/or other messaging related to network access), cloud synchronization services, RSS feeds and/or other background information feeds, application (e.g., web browser) or device behavior reporting, background email downloads,

content subscription service updates and downloads (e.g., music/video downloads, news feeds, etc.), text/voice/video chat clients, virus updates, peer to peer networking applications, inefficient network access sequences during frequent power cycling or power save state cycling, large downloads or other high bandwidth accesses, and/or greedy application programs that continually and/or frequently access the network with small transmissions or requests for information. Various other examples will now be apparent to one of ordinary skill in the art.

Thus, not only can network capacity, network performance, and/or network resource availability be degraded by high device transmission bandwidth demand, but other types of persistent or frequent traffic resulting from network resource requests, network data accesses or other network interaction can also degrade network capacity, network performance, and/or network resource whether or not the aggregate bandwidth demand as measured by the total data throughput is high or not. Thus, techniques are needed to preserve network capacity by, for example, differentially controlling these types of network service usage activities in various ways depending on the type of service activity requesting network access and/or requesting transactions with network resources.

Smart phone and similar devices are exacerbating the problem by making frequent queries of the wireless network as such devices move among cell sites to while in transit, for example, push email, access social networking tools, and/or conduct other repetitive actions. While data traffic is also growing, signaling traffic is outpacing actual mobile data traffic by 30 percent to 50 percent by some estimates. For example, a Yahoo IM user may send a message but then wait a couple of seconds between messages. To preserve battery life, the smart phone typically moves into an idle mode. When the user pushes another message seconds later, the device has to set up a signaling path again, and even when the signaling resource is released by the smart phone, the network typically does not react fast enough to allow for the next station to use resources until several seconds and sometimes minutes. As a result, the base station controller in this example is spending a lot of its resources trying to process the signaling so it cannot perform other tasks, such as allocate additional resources for data network usage, and such inefficiencies exacerbates the data network capacity crunch and dropped calls on such wireless networks.

One approach used by smart phone vendors to address this problem and save battery life on their devices is to implement a fast dormancy feature, which allows the mobile device to quickly make a query to the radio network controller to release the connection so that it can return to the idle state faster. In other words, the device is relaying the fact that the phone is going dormant saving device resources (e.g., signaling channel) rather than network resources. However, the fast dormancy feature can exacerbate this problem by prematurely requesting a network release only to follow on with a request to connect back to the network or by a request to re-establish a connection with the network.

Network carriers have typically attempted to manage network capacity using various purely central/core network based approaches. For example, some carriers have indicated a robust capacity planning process and sufficient investment is needed to alleviate this growing capacity crunch. Purely centralized network solutions with no assistance from a device based software agent (or service processor) can have several limitations. For example, for some device applications, OS functions or other service usage activities, if the activity is blocked somewhere in the net-

work behind the base station after over the air (OTA) spectrum bandwidth is consumed to open or begin to open a communication socket, then there can still be an appreciable amount of network capacity or resources consumed even though the data transfer is not allowed to complete. In addition, if the service usage activity is aggressive in re-attempting to establish the network connection to transfer the data, and the network continues to allow the OTA portion of the connection establishment but blocks the connection somewhere in the network, then a large amount of capacity can be consumed by many devices exhibiting such behavior even though no useful service is being allowed. Accordingly, some embodiments for protecting network capacity include controlling network service usage activities at the source of the demand—the device. Furthermore, in some embodiments, service usage is controlled in a manner that delays, prevents, or reduces the frequency of service usage activity re-try attempts to connect to the network.

In some cases, an additional drawback of purely centralized network solutions to protect network capacity arises when service usage activities are controlled, blocked, throttled, and/or delayed by central network equipment with no mechanisms or support to link to a device user interface (UI) to inform the user what is happening and why it is happening. This can lead to a frustrating user experience and reduced carrier customer satisfaction. Accordingly, in some embodiments, a device based UI is provided to provide the user with real time or near real time information regarding why a service usage activity is being controlled, blocked, throttled, and/or otherwise controlled in order to protect network capacity. In some embodiments, a UI is provided that also informs the user when there are options to set, control, override, or modify service usage controls for the purpose of protecting network capacity. In some embodiments, such user preference inputs also correspond to a change in service usage billing. In some embodiments, such changes in service usage billing due to capacity sparing service control changes by the user are communicated to the user via a UI notification sequence. In some embodiments, techniques for protecting network capacity employ user warnings when a service usage activity classified for differential user notification policies is likely to cause the user to go over service plan caps (e.g., total data byte count usage caps).

What is needed is intelligent network monitoring to provide real-time traffic monitoring network service usage (e.g., at the packet level/layer, network stack application interface level/layer, and/or application level/layer) of the wireless network (e.g., radio access networks and/or core networks) and to effectively manage the network service usage for protecting network capacity (e.g., while still maintaining an acceptable user experience). Using Device Assisted Services (DAS) techniques, and in some cases, network assisted/based techniques, to provide for network service usage monitoring of devices, network carriers/operators would be provided greater insight into what devices, which users and what applications, and when and where network congestion problems occur, enabling operators to intelligently add additional resources to certain areas when necessary (e.g., offloading data traffic onto femto cells or WiFi hotspots and adding more network resources), to differentially control network service usage, and/or to differentially charge for network service usage based on, for example, a network busy state, for protecting network capacity.

Intelligent network monitoring of the wireless network to effectively manage network service usage for protecting

11

network capacity can include providing Device Assisted Services (DAS) for protecting network capacity in accordance with various embodiments described herein. For example, intelligent network monitoring of the wireless network to effectively manage network service usage for protecting network capacity can include differentially controlling over the air software updates and/or performing software updates via wired connections only. As another example, intelligent network monitoring of the wireless network to effectively manage network service usage for protecting network capacity can include differentially controlling various applications that demand significant network resources or network capacity. As another example, intelligent network monitoring of the wireless network to effectively manage network service usage for protecting network capacity can include managing network access connection requests resulting from repeated power down modes in the modem, which can cause resource intensive re-connection and/or re-authentication processes. As another example, intelligent network monitoring of the wireless network to effectively manage network service usage for protecting network capacity can include techniques for keeping PPP sessions alive to avoid the need to consume network resources to re-establish PPP sessions (e.g., unless the application behavior analysis predicts that a mean access time is long enough for the PPP session to be dropped off and yet not causing overall network resource limitations).

Unlike traditional QoS techniques, which are used to establish a single end or end to end guaranteed service level(s) on a network, techniques disclosed herein for protecting network capacity facilitate implementation of services on a network to facilitate differential control of certain services to protect network capacity (e.g., to reduce network congestion, network capacity demand, network resource demand; and/or to increase network availability). As also disclosed herein, techniques disclosed herein for protecting network capacity facilitate implementation of services on a network to facilitate differential control of certain services to protect network capacity can also facilitate QoS implementations by maintaining needed levels of network capacity/availability to facilitate delivery of certain QoS levels/classes. For example, techniques disclosed herein for protecting network capacity can aggregate across multiple services and/or devices to facilitate differential control of certain services to protect network capacity. As another example, techniques disclosed herein for protecting network capacity can be used to provide for dynamic QoS classifications (e.g., dynamically assigning/classifying and re-assigning/reclassifying (based on various criteria, events, and/or measures) network service usage activities to various QoS levels/classes, such as described herein) to facilitate differential control of certain services to protect network capacity.

Accordingly, Device Assisted Services (DAS) for protecting network capacity is provided. In some embodiments, DAS for protecting network capacity provides for protection of network capacity (e.g., network congestion and/or network access/resource demand and/or network availability on an edge element of the network, such as on the Radio Access Network (RAN) of a wireless network, and/or from a device to a base station/base station controller), such as by controlling network service activity usage activities of a device in wireless communication with the network to reduce demands on the network. For example, controlling network service usage activities can include classifying and/or controlling network access requests (e.g., IP address requests), network access reservation requests (e.g., a QoS reservation/sequence), network capacity/resources usage (e.g., band-

12

width usage), and/or any other network service usage activities. In some embodiments, applications, OS functions, and/or other network service usage activities that request IP addresses from network address server resources are classified and/or controlled so that the IP address requests are withheld, delayed, time windowed, reduced in frequency, aggregated or otherwise controlled. In some embodiments, such "IP address request control policies" for one or more applications, OS functions, and/or other network service usage activities are set, updated, and/or modified before communicating it over a network connection to a network element (e.g., a service controller or another network element/function). In some embodiments, network service usage activities are generated/requested by applications, operating system (OS) functions, and/or other software/functions executed on a device in communication with the network. In some embodiments, it is desirable to apply a service usage control policy for the network service usage activities to protect network capacity (e.g., reduce network capacity demand). For example, some applications and/or OS functions have limited capabilities to defer certain traffic types based on fixed settings in the application, and such applications and/or OS functions typically cannot optimize network service usage activities based on a current network busy state (e.g., based on changing levels of network capacity and/or network performance available to the device). In some embodiments, the network busy state (e.g., or conversely the network availability state) is a characterization of the congestion (e.g., or conversely available capacity) of the network for one or more device connections. For example, the network busy state can provide a measure of how busy or congested the network or a network segment (e.g., network edge element) is for one or more device connections. As another example, network availability state can provide a measure of what network connection resources are available to one or more device connections. Thus, network busy state and network availability state can be viewed as converse ways of providing similar information, and as described herein with respect to various embodiments, these terms can be used interchangeably.

In some embodiments, techniques are provided for assigning a priority to a network service usage activity and controlling traffic associated with the network services usage activity based on the assigned priority. In some embodiments, techniques are provided for implementing a differentiated and dynamic background services classification, for example, as a function of network availability state and/or network busy state.

In some embodiments, a service usage control policy is used for assisting in network access control of network service usage activities (e.g., deferring some or all of the network capacity demand from these source activities). In some embodiments, some or all of the network capacity demand is satisfied at a point where the network resources or capacity are more available or less busy. In some embodiments, techniques are provided for classifying network service activities associated with one or more applications or OS functions to a background service class and differentially controlling the background service class traffic. In some embodiments, techniques are provided for classifying one or more network service activities associated with an application or OS function to a background service class, while other network service activities associated with that application or OS function are classified to other service classes (e.g., or to different background service class priority levels).

13

In some embodiments, techniques are provided for determining a network busy state (e.g., for a network edge element connection to a device, such as for a RAN for the device's current wireless network access and/or to the current base station/base station controller in wireless communication with the device). In some embodiments, techniques are provided for implementing a service usage control policy to differentially control network services traffic based on a network busy state for an activity, a group of activities, or for a service class.

In some embodiments, DAS for protecting network capacity includes monitoring a network service usage activity of the communications device in network communication; classifying the network service usage activity for differential network access control for protecting network capacity; and associating the network service usage activity with a network service usage control policy based on a classification of the network service usage activity to facilitate differential network access control for protecting network capacity.

In some embodiments, a network service usage activity is any activity by the device that includes wireless network communication. In some embodiments, an application, an operating system (OS), and/or other device function generates a network service usage activity. In some embodiments, an application, an operating system (OS), and/or other device function generates one or more network service usage activities. Examples of a network service usage activity include the following: a voice connection (e.g., coded voice connection or voice over IP (VOIP) connection), a device application or widget connection, a device OS function connection, an email text connection, an email download connection, a file download connection, a streaming media connection, a location service connection, a map services connection, a software update (e.g., application, operating system, and/or antimalware software update) or firmware update connection, a device backup connection, an RSS feed connection, a website connection, a connection to a server, a web browser connection, an Internet connection for a device based service activity, establishing a sync service account, a user data synchronization service, a device data synchronization service, a network connection flow or stream, a socket connection, a TCP connection, a destination/port assigned connection, an IP connection, a UDP connection, an HTTP or HTTPS connection, a TLS connection, an SSL connection, a VPN connection, a general network services connection (e.g., establishing a PPP session, authenticating to the network, obtaining an IP address, DNS service), and various other types of connections via wireless network communication as will be apparent to one of ordinary skill in the art.

In some embodiments, a network service usage activity is classified, associated with, and/or assigned to a background class (e.g., a background service or QoS class) to facilitate differential network service usage control to protect network capacity. In some embodiments, differential network service usage control includes one or more of the following: monitoring network service usage activity; accounting for network service usage activity; reporting network service usage activity; generating a user notification for a network service usage activity; requesting a user preference for control of network service usage activity; accepting a user preference for network service usage activity; implementation of a network service usage activity policy (e.g., block/allow; traffic control techniques, such as throttle, delay, priority queue, time window, suspend, quarantine, kill, remove, and other well known traffic control techniques); implementing

14

UI intercept procedures; generating a network busy state notification; generating a background class notification; generating a user notification for differential network service usage control of a network service usage activity; and various other techniques as described herein.

In some embodiments, a network availability state includes a state or measure of availability/capacity of a segment of a network (e.g., a last edge element of a wireless network). In some embodiments, a network busy state includes a state or measure of the network usage level or network congestion of a segment of a network (e.g., a last edge element of a wireless network). In some embodiments, network availability state and network busy state are inverse measures. As used herein with respect to certain embodiments, network availability state and network busy state can be used interchangeably based on, for example, a design choice (e.g., designing to assign background policies based on a network busy state or a network availability state yields similar results, but they are different ways to characterize the network performance and/or capacity and/or congestion). In some embodiments, network availability state and network busy state are dynamic measures as such states change based on network usage activities (e.g., based on a time of day, availability/capacity level, congestion level, and/or performance level). In some embodiments, differential network service usage control of a network service usage activity is based on a network busy state or network availability state.

In some embodiments, certain network service usage activities are classified as background services. In some embodiments, lower priority and/or less critical (and/or based on various other criteria/measures) network service usage activities are classified as background services based on a network busy state and differentially controlled based on a network busy state to protect network capacity. In some embodiments, differential network service usage control policies are based on a time of day, a network busy state, background services and/or QoS class changes based on a time of day and/or a network busy state, a random back-off for access for certain network service usage activities, a deterministic schedule for certain network service usage activities, a time windowing in which network service usage control policies for one or more service activities or background/QoS classes changes based on time of day, network busy state, a service plan, and various other criteria, measures, and/or techniques as described herein.

In some embodiments, a network capacity controlled service or network capacity controlled services class includes one or more network services (e.g., background download services and/or various other types or categories of services as described herein) selected for differential network service usage control for protecting network capacity. In some embodiments, a network capacity controlled services classification includes one or more network services associated with a network capacity controlled service/class priority setting for differential network service usage control for protecting network capacity. In some embodiments, a network capacity controlled service or network capacity controlled services class includes one or more network services associated with a QoS class for differential network service usage control for protecting network capacity. In some embodiments, a network capacity controlled service or network capacity controlled services class includes one or more network services associated with a dynamic QoS class for differential network service usage control for protecting network capacity.

For example, differentially controlling network service usage activities based on network capacity controlled ser-

15

vices or dynamic QoS or QoS classifications can protect network capacity by, for example, improving network performance, increasing network availability, reducing network resources demand, and/or reducing network capacity demand (e.g., based on an individual device, aggregate devices connected to an edge element, and/or aggregate devices connected to many edge elements). In some embodiments, differentially controlling network service usage activities based on network capacity controlled services or dynamic QoS or QoS classifications can protect network capacity while maintaining proper device operation. In some embodiments, differentially controlling network service usage activities based on network capacity controlled services or dynamic QoS or QoS classifications can protect network capacity while maintaining an acceptable user experience (e.g., proper and/or expected device operation, proper and/or software/application/OS/function operation, avoiding (whenever possible) significant adverse impact on device functions, and/or user notifications to keep the user informed of various differential control implemented on the device).

In some embodiments, dynamic QoS classifications include QoS classifications that can be dynamically modified (e.g., reclassified, reprioritized, upgraded, and/or downgraded) based on various criteria, measures, settings, and/or user input as described herein (e.g., based on a time of day and/or day of week, based on a network busy state, based on a user preference, and/or based on a service plan). In some embodiments, the various techniques described herein related to DAS for providing network capacity and/or QoS for DAS are applied to dynamic QoS related techniques.

As wireless networks, such as mobile networks, evolve towards higher bandwidth services, which can include or require, for example, various levels of Quality of Service (QoS) (e.g., conversational, interactive data, streaming data, and/or various (end-to-end) real-time services that may benefit from QoS), demands will increase for converged network services to facilitate such services for end-to-end services between networks (e.g., to allow for control and/or support for such services, for example, QoS support, across network boundaries, such as between wireless networks (such as various service provider networks) and IP networks (such as the Internet), and/or other networks). While various efforts have attempted to address such QoS needs, such as policy management frameworks for facilitating QoS end-to-end solutions, there exists a need to facilitate various QoS requirements using Device Assisted Services (DAS).

Accordingly, Quality of Service (QoS) for Device Assisted Services (DAS) is provided. In some embodiments, QoS for DAS is provided.

To establish a QoS channel, differentiated services are typically available, in which one class/level of service has a higher priority than another to provide for differentiated services on a network, such as a wireless network. For example, in a wireless network, various network elements/functions can be provisioned and controlled to establish a single end or end to end QoS channel. In some embodiments, a centralized QoS policy coordination and decision function using DAS techniques to assist in coordinating the QoS channel setup and control among the various elements of a wireless network is provided.

In some embodiments, QoS channel refers to the logical communication channel connected to a device that provides a desired level of QoS service level. For example, the QoS channel can be created with one or more QoS links, in which each link represents a QoS enabled connection that spans a portion of the total end to end network communication path

16

from a near end device to a far end device. For example, the far end device can be on the same network or on a different network, potentially with different access technology and/or a different access network carrier. In some embodiments, the QoS channel includes one or more QoS links in which each link in the channel is QoS enabled, or one or more of the links in the channel is QoS enabled and others are not. As an example, a QoS channel can include the following links: a first device traffic path link, a first device to access network equipment element link (e.g., 2G/3G/4G wireless base station, WiFi access point, cable network head end, DSLAM, fiber aggregation node, satellite aggregation node, or other network access point/node), a first carrier core network, a long haul IPX network, a second carrier core network, a second device to access network equipment element link, and a second device traffic path link as similarly described herein with respect to various embodiments.

In some embodiments, each of the links described above have the ability to provide QoS services for that segment of an overall QoS channel. In some embodiments, the device traffic path link and/or the device to access network equipment element link are QoS enabled, but the carrier core network and/or IPX network links are not QoS enabled. In some embodiments, the core network and/or IPX network have sufficient over-provisioning of bandwidth that QoS is not limited by these network elements and, for example, can be limited by the device traffic link and/or the device to access network equipment element link do not have sufficient excess bandwidth making it desirable to QoS enable these QoS channel links. A common example is a 2G/3G/4G wireless network in which a device traffic path link and the device to access network element link (e.g., Radio Access Bearer (RAB)) are QoS enabled while the carrier core network and IPX network links are not (e.g., are provided at a best effort service level or other service levels).

In some embodiments, a QoS session refers to the QoS enabled traffic for a given device that flows over a QoS channel or QoS link. This QoS traffic supports a QoS service activity. In some embodiments, a QoS service activity includes a device service usage that is requested, configured, or preferably serviced with a given level of QoS. In some embodiments, a device QoS activity is a combination of one or more of the following: application, destination, source, socket (e.g., IP address, protocol, and/or port), socket address (e.g., port number), URL or other similar service identifier, service provider, network type, traffic type, content type, network protocol, session type, QoS identifier, time of day, network capacity (e.g., network busy state), user service plan authorization or standing, roaming/home network status, and/or other criteria/measures as similarly described herein. For example, QoS service activities that are supported by QoS sessions can include VOIP traffic, streaming video traffic, differentiated access bandwidth during busy network periods, real-time interactive traffic, such as network connected multimedia meetings (e.g., shared presentations, picture, video, voice, and/or other such applications/services), best effort interactive, such as Internet browsing, time sensitive services, such as email message body delivery, near real-time interactive services, such as SMS or push to talk, background download services, such as email downloads and other file transfers (e.g., FTP), and/or truly background download services, such as software updates (e.g., OS or application software updates and/or antimalware updates including content/signature updates).

In some embodiments, various QoS levels or classes are supported. For example a conversation class can provide for real-time traffic, which is typically very delay sensitive but

17

can tolerate bit errors and packet losses. The conversational class is typically used for Voice Over IP (VOIP) and video telephony, in which users of such services benefit from the short delay features of the conversational class. A streaming class is similar to the conversational class except that the streaming class typically can tolerate more delay than the conversational class. The streaming class is generally used for when one end of the connection is a user (e.g., human user) and the other end is a machine/computer (e.g., for streaming content applications, such as streaming of video, such as movies or other video content). An interactive class is generally intended for traffic that allows delay variation while requiring reasonably low response time (e.g., web browsing or other applications in which the channel can be unused for long periods of time but when a user makes a request for a new page/data, the response time should be reasonably low). A background class is generally used for lowest priority service usages (e.g., typically used for e-mail with and without downloads/attachments, application software updates, OS software updates, and/or other similar applications/functions). In some embodiments, various QoS classes or services are applicable to the conversational class. In some embodiments, various QoS classes or services are also applicable to the streaming class. In some embodiments, various QoS classes or services are also applicable to the interactive class but typically not applicable to the background class. As will now be apparent to one of ordinary skill in the art, various other classes can be provided with lower or higher granularity based on service usage/channel requirements and/or network architectures.

In some embodiments, a QoS link or a QoS channel supports one QoS session. In some embodiments, a QoS link or a QoS channel supports multiple QoS sessions. In some embodiments, QoS link provisioning is provided to setup the QoS traffic level for a given QoS session or group of QoS sessions.

In some embodiments, a QoS channel is a single ended QoS channel or an end to end QoS channel. For example, if a QoS channel is end to end, then the QoS channel provisioning is accomplished in a coordinated manner for each QoS enabled link in the QoS channel. If a QoS channel is single ended, then the network elements and/or device participate in provisioning as much of one end of the QoS channel as possible, leaving provisioning of the QoS for the other end of the channel as the responsibility of the device and/or network elements that handle the traffic at the other end of the QoS channel. In some embodiments, a single ended QoS channel includes another single ended QoS channel at the other end. In some embodiments, only one end has single ended QoS channel enablement while the other end of the channel is a best effort service level, which, for example, can be used where one end of the QoS channel has tighter constraints on traffic capacity or quality than the other end (e.g., a VOIP call with one end that is QoS enabled on a 3G wireless network that has relatively tight bandwidth compared to a lightly loaded cable modem network device on the other end which may not need to be QoS enabled in order to achieve adequate voice quality).

In some embodiments, a QoS request (e.g., a QoS channel request or QoS service request) is a request for a QoS provisioning event to enable a QoS channel for one or more QoS service activities. In some embodiments, QoS availability assessment includes determining whether one or more of the links in a possible QoS channel are available (e.g., based on network capacity and transmission quality) to provision the necessary level of QoS for a requested QoS channel. In some embodiments, a QoS request is initiated by

18

a device, a user, an application, and/or a network element/function as similarly described herein.

In some embodiments, a service plan refers to the collection of access service capabilities, QoS capabilities, and/or network capacity controlled services that are associated with a communications device. In some embodiments, the access service capabilities, QoS capabilities, and/or network capacity controlled services are determined by the collection of access service control policies for the device. In some embodiments, these service control policies are implemented in the network equipment. In some embodiments, these access service control policies are implemented both in the device and in the network equipment. In some embodiments, these access service control policies are implemented in the device. In some embodiments, there are different levels of service control capabilities (e.g., policies) based on different levels of service plan payments or device standing or user standing. In some embodiments, there are different levels of service control policies based on network type, time of day, network busy status, and/or other criteria/measures as similarly described herein with respect to various embodiments. In some embodiments, the access control and QoS control policies are based on the type of service activity being sought. In some embodiments, the QoS level and access level available for a given service activity for a given device or user is determined by the policies associated with the service plan. In some embodiments, a QoS authorization assessment is performed to determine whether a device or user has sufficient service plan standing to allow the requested level of QoS.

In some embodiments, before a QoS channel or link is provisioned (or before a QoS request is responded to or filled), a QoS availability assessment is performed to determine whether sufficient communication channel resources are available to provision the necessary level of QoS for the QoS channel or link. In some embodiments, this QoS availability assessment is determined by assessing the available QoS capacity for one or more necessary QoS links in the channel. For example, the available QoS link capacity can be assessed for one or more of a device traffic path, a device to access network equipment element link, a core network link, and/or an IPX network link. If the QoS assessment shows that the necessary channel capacity and quality is available for the desired QoS level for one or more desired QoS service activities, then a QoS channel request or QoS service request can be granted. In some embodiments, a QoS link or QoS channel reservation process is provided to reserve QoS capacity and quality in advance of link or channel provisioning to ensure that the available QoS resources are not assigned between the time of QoS availability assessment and QoS channel provisioning.

In some embodiments, the QoS availability assessment is performed after QoS authorization assessment. This prevents the unnecessary exercising of network elements when the device or user does not have sufficient service plan standing to receive the desired level of QoS even if it is available. This can be an important screening function performed on the device in the service processor, or by a centralized network function such as the service controller (e.g., or interchangeably, the home agent; Home Location Register (HLR); Authentication, Authorization, and Accounting (AAA) server/gateway/function; base station; one of the gateways, policy and charging rules function (PCRF), or other network element/function). In some embodiments, QoS availability is assessed without conducting a QoS authorization assessment or before receiving the response to a QoS authorization assessment.

19

In some embodiments, a QoS channel is provisioned to create the QoS channel to support a QoS session (e.g., a QoS service activity). In some embodiments, QoS channel provision includes assigning, routing, and/or otherwise causing the QoS session traffic to flow over one or more QoS links in the assigned QoS channel.

In some embodiments, device assisted service traffic control and QoS apply readily and directly to the problems of managing a QoS device link for QoS channel provisioning. Accordingly, in some embodiments, a service provider is provided to assist in provisioning the device portion of the QoS channel. In some embodiments, the service processor provisions the device link portion of the QoS channel by placing a higher priority on higher QoS level traffic. In some embodiments, this QoS priority is implemented in a number of ways, including routing the higher priority QoS traffic into first priority in the downstream and/or upstream traffic queues. Upstream traffic queuing is performed directly in some embodiments by transmitting guaranteed bit rate traffic first at higher available throttling rates, differentiated QoS traffic second with a controlled throttling rate, best effort traffic third with possibly lower controlled throttled rates, and/or background traffic fourth when/if bandwidth not needed by the higher levels of QoS traffic and at lower controlled throttling rates. For example, downstream traffic can be handled by queuing traffic and delaying or preventing TCP acknowledgements to be returned for the lower levels of QoS priority, while immediately passing the traffic and TCP acknowledgements for higher levels of QoS priority. The device link portion of the QoS channel is thus provisioned by assigning policies for the queuing priority, delay, throttle rate, and TCP acknowledgement return rate for device traffic in accordance with the bandwidth that is available at any point in time for the device. In some embodiments, various device service processor traffic control capabilities regulate or partially regulate QoS in accordance with a set of network policy instructions, including, in some embodiments, a service plan policy set.

In some embodiments the device service processor establishes multiple QoS channels through the device traffic path with each QoS channel having traffic control policies as described herein, with each QoS channel policy set creating a different class of QoS. In some embodiments, employing this multiple QoS channel approach, QoS for a given service activity is provided by routing the traffic for that QoS activity to the appropriate QoS channel with the appropriate QoS policy settings. The routing to the appropriate QoS channel can be provided using various techniques. For example, the routing can be provided by applying a common service traffic control policy set to traffic associated with all QoS service activities that require or request the QoS provided by the common service traffic control policy set. The application of the service traffic control policy set can be accomplished in a number of ways utilizing the embodiments described for the policy implementation agent and the policy control agent described herein. In such embodiments, the problem of assigning a QoS channel to a number of QoS service activities is reduced to applying a pre-determined set of service traffic control policies to each of the QoS service activities, with each pre-determined set of service traffic control policies representing a different QoS class. The device can then manage the overall QoS for all traffic based on the available traffic capacity and quality, the total aggregate traffic demand for each QoS traffic class and the policy rules that determine how each traffic class is provided with

20

differential bit rate and traffic quality as compared to the other traffic classes for a given level of available traffic capacity and quality.

Based on the aggregate demand for each traffic QoS class, and the traffic capacity and quality level available to the device, the service processor can adjust the total available bit rate or percentage of available traffic capacity for each QoS class. For example, in some embodiments, the aggregate demand for the real-time interactive traffic control class (e.g., services, such as VOIP, emergency communication services or high performance real-time competitive gaming) can be determined, and the QoS routing function on the device (e.g., a QoS router agent/function) can first allocate enough constant bit rate traffic capacity from the available traffic capacity to satisfy these services, with each QoS service activity that requires this QoS class being assigned to this QoS channel. As more QoS service activities require this traffic class, the capacity allocated to the QoS channel out of the available device capacity is increased, and when fewer QoS service activities require this traffic class the capacity for this QoS channel is released. In the event that the device does not have any more available capacity with a guaranteed bit rate QoS level, then additional QoS service activities that desire, require or request this QoS level will not be provided this QoS level, and instead will either be provided with a lower QoS level or will not be allowed to connect to the access network. In some embodiments, there can be a hierarchy among the possible QoS service activities so that if there is no more capacity available at a given service QoS level, then the available capacity for that QoS class is provided to the service activities requiring that QoS from highest priority to lowest, until the available QoS class capacity is consumed, and then one or more QoS service activities that are too low on the priority list to obtain service with that QoS class are either bumped to a lower QoS class or are denied access. In some embodiments, once the required capacity to satisfy the real-time constant rate traffic needs is satisfied, the remaining capacity available to the device is then divided among the other QoS channel classes in accordance with a priority policy, with the priority policy being based on the relative priority of each service class, the relative priority of each QoS service activity, or a combination of the relative priority of each QoS service class and each QoS service activity. For example, these relative priority policies can vary from device to device based on service plan selection, device type, user standing, user group, device location, device network connection, type of network, time of day, network busy state, and/or other criteria/measures.

In some embodiments, a QoS link is established between the device and an access network equipment element. For example, such equipment element embodiments can include a 2G/3G/4G wireless base station, a wireless access point, a cable network head end, a DSL network DSLAM, a fiber network device traffic aggregator, a satellite network device traffic aggregator, a frame relay aggregation node, an ATM aggregation node, and/or other network equipment. In some embodiments, a logical communication channel is created between the device and the network equipment element, with the logical communication channel supporting a given level of QoS or QoS class traffic policy set. For example, the logical channel can include a RAB formed between a 2G/3G/4G base station and a wireless end point device. The RAB can be formed by controlling the media access control (MAC) parameters of the base station radio channel so that a given level of QoS class policies can be implemented. For example, the RAB can support constant bit rate, low latency

21

communication traffic for guaranteed bit rate real-time traffic, or a differentiated high priority access channel for streaming traffic, or a best effort random access channel for best effort traffic, or an available unused capacity traffic for background traffic. The QoS channel link created in this manner can be dedicated to a single device, or shared with a subset of devices, or available to all devices. The QoS channel link created in this manner can be used by the device to support a single QoS activity as described herein, or a group of QoS activities as described herein. It will now be apparent to one of ordinary skill in the art that similar settings for cable head end and cable modem MAC can yield similar QoS classes for QoS links for the cable modem case and that similar techniques can be applied for a wireless access point or a satellite system MAC to achieve similar QoS classes for QoS links. It will also now be apparent to one of ordinary skill in the art that by creating multiple logical channels in the device link, and/or adjusting the available access network capacity and quality for each logical device communication channel in the DSLAM or fiber aggregator, similar QoS class QoS links can be established for the DSL and fiber distribution network cases.

In some embodiments the device service processor serves to route QoS service activities to the appropriate logical communication channel established for the desired QoS class supported by a QoS link between the device and the access network equipment element. In some embodiments, the device service processor elements (e.g., the policy implementation agent and/or the policy control agent) can be used in some embodiments to assign the same QoS traffic control policies to one or more QoS service activities that require the same QoS level. In a similar manner, in some embodiments, the device service processor elements can be used to assign or route service activity traffic for a given QoS class to the correct logical communication channel between the device and the access network element (e.g., a 2G/3G/4G base station) that supports the traffic control policies for the desired QoS class. For example, a QoS service link that supports guaranteed bit rate and latency can be established with one or more RABs from a base station to the device, and a second QoS service link can be established that supports differentiated preferred access for streaming content using one or more differentiated access RABs, and a third best effort RAB can be used to support best effort traffic. Each of the required RABs is first requested and then provisioned as described herein based on the aggregate required capacity and quality for one or more QoS service activities that require or desire the specific QoS service class associated with the RAB logical channel policy parameters. Once the set of logical QoS channels is thus established, the service processor (e.g., QoS router agent/function) routes the traffic associated with each QoS service activity to the appropriate RAB. In some embodiments, the service processor can detect increases or decreases in aggregate QoS class demand for each QoS class as QoS activities are initiated or terminated for that QoS class, and the service processor can communicate the required increases or decreases in the RAB assignments required to support that logical QoS channel.

In some embodiments, the access QoS link is established by direct communication from the device in which the device requests the QoS channel or link from the access network equipment element, or the device requests the QoS channel or link from an intermediate networking device, such as a service controller (e.g., or a readily substituted device with similar features, such as a home agent, an HLR, a mobile switching center, a base station, an access gateway,

22

a AAA system, PCRF, or a billing system). In some embodiments, the device service processor bases the QoS channel or link request on an association the device performs to match a QoS service activity with a desired or required QoS class or QoS traffic control policy set. For example, this association of QoS class or QoS traffic control policy set with QoS service activity can be determined by a predefined policy mapping that is stored on the device and used by the service processor. In some embodiments, this policy mapping store is populated and/or updated by a service controller (e.g., or similar function as described herein). In some embodiments, the mapping is determined by a service controller (e.g., or similar function as described herein) based on a report from the device of the QoS service activity that needs the QoS channel or link.

In some embodiments, the required or desired QoS level for one or more QoS service activities is determined by a set of QoS service traffic control policies that are pre-assigned to various QoS service activities. For example, a given application can be pre-assigned a QoS class. As another example, a web service destination such as a VOIP service site can be assigned a QoS class. As another example, a given application can have one QoS assignment level for general Internet traffic but have a QoS assignment for real-time gaming traffic. As another example, a real-time broadcasting website can have a best effort QoS level assigned to programming information and general browsing and have a differentiated streaming QoS level for broadcast traffic content. In some embodiments, detection of QoS need or QoS assignment request for a given activity can be assigned by a device service processor according to a pre-defined QoS policy rules table (e.g., QoS activity table), or can be determined by a service controller based on information reported by the device, or can be requested by an application through a QoS application interface (e.g., QoS API), or can be determined by the nature of incoming traffic.

In embodiments, in which both end points in the QoS channel participate in establishing an end to end QoS channel, the required QoS level is determined and/or communicated by the originating end point. In some embodiments, the required QoS level is determined and/or communicated by the receiving end point. In some embodiments the QoS level is determined and/or communicated by the originating end point service controller (e.g., or the access network element (such as a base station), the HLR, home agent, mobile switching center, AAA, gateway, or other network element/function). In some embodiments, the QoS level is determined and/or communicated by the receiving end point service controller (e.g., or alternatively the access network element (such as a base station), the HLR, home agent, mobile switching center, AAA, gateway, or other network element/function). In some embodiments, the receiving end point service controller (e.g., or the access network element (such as a base station), the HLR, home agent, mobile switching center, AAA, gateway or other network function) and the originating end point service controller (e.g., or other similar function) communicate with one another to coordinate establishment of the QoS channel between the end points.

In some embodiments, the near end or originating end device service processor contacts the far end or terminating device service processor to initiate a QoS channel. In some embodiments, the initiation of the QoS channel from the near end or originating device is performed automatically by the far end device when its service processor detects that a given level of QoS is needed for the communication

between the two devices. In some embodiments, the near end or originating device service processor detects the need for a QoS channel to the far end or terminating device and contacts a central network resources, such as the service controller (e.g., or other equipment element with similar function for this purpose), and the service controller provisions the far end of the QoS channel, either by communicating directly with the far end device or by communicating with the far end device's service controller (e.g., or other equipment element with similar function for this purpose). In some embodiments, in which the far end device service controller is contacted to assist in provisioning the QoS channel, there is a look up function to determine the address of the far end service controller based on a look up index formed from some aspect of the far end device credentials (e.g., phone number, SIM ID, MEID, IMSI, IP address, user name, and/or other device credentials).

In some embodiments, the mapping of QoS service activity to the desired level of QoS class or QoS traffic control policies is determined by providing a QoS API in the device service processor that applications use to request a QoS class or QoS channel connection. In some embodiments, an API is provided so that application developers can create application software that uses the standard interface commands to request and set up QoS channels. In some embodiments, the API does one or more of the following: accepts QoS requests from an application, formats the QoS channel request into a protocol appropriate for transmission to network equipment responsible for assessing QoS channel availability (e.g., including possibly the device traffic control system), coordinates with other network elements (e.g., including possibly the device traffic control system) to reserve a QoS channel, coordinates with other network elements (e.g., including possibly the device traffic control system) to provision a QoS channel, informs the application that the desired QoS channel can be created or not, and/or coordinates with other network elements (e.g., including possibly the device traffic control system) to connect the application with the desired QoS channel class. In some embodiments, the QoS API accepts the application QoS request and communicates and possibly coordinates with one or more QoS network equipment elements, such as a base station, cable head end or access point. In some embodiments, the QoS API accepts the QoS request from the application and communicate and possibly coordinates with an intermediate network element, such as a service processor (e.g., or other similar function as described herein). In some embodiments the QoS API assesses the QoS service plan standing for the device or user before sending QoS channel requests to other network elements, and only initiates the QoS request sequence if required service plan authorization is in place. In this manner, the potentially complex process of establishing a QoS channel with all the specific equipment communication protocols that typically need to be supported to assess QoS channel availability and provision the QoS channel are simplified into a limited set of API commands that are easy for an application development community to learn about and use for QoS differentiated services and applications.

In some embodiments, local traffic control on the device service processor is combined with traffic control in the link between the device and the access network equipment element. In this manner, both the device traffic control path QoS link and the device to access network element QoS link can be coordinated for best device QoS performance results given the available capacity and quality of the access network traffic for the device. In some embodiments, the policies for how the device manages local traffic control,

establishes access network element logical channels (e.g., RABs) and routes traffic to and from the access network element logical channels is all determined by predefined policy rules loaded onto the device by the service controller (or other equivalent network element). In some embodiments, these policies are determined in the service controller itself.

In some embodiments, a QoS user interface (e.g., QoS UI) is presented to the device user. In some embodiments, the QoS UI notifies the user what level of QoS services the device is authorized to receive based on the service plan selection. In some embodiments, the QoS UI notifies the user what level of QoS services are available on the present network the device is connected to at the present time. In some embodiments, the QoS UI notifies the user when a level of QoS service that is higher than that authorized by the user service plan is required or desirable for a given service activity that the device has initiated. In some embodiments, the QoS UI provides the user with a set of one or more upgrade options to upgrade the service plan to include a higher level of QoS for one or more service activities. In some embodiments, the QoS UI provides the user with an opportunity to specify what level of QoS the user would like to employ for one or more service usage activities. In some embodiments, the QoS UI allows the user to specify a service plan setting that provides differentiated QoS during times when the network is busy. In some embodiments, the QoS UI allows the user to purchase one or more grades of service QoS with either a post-pay for a pre-defined service period and one or more pre-defined service usage limits by QoS class, a pre-pay for one or more pre-defined service usage limits by QoS class, or another payment system for differentiated QoS services. In some embodiments, the QoS UI provides the user with an opportunity to QoS enable or pay for QoS services for a connection that is initiated by an incoming connection to the device.

In some embodiments, QoS for DAS techniques include verifying that the device is properly implementing the QoS traffic control policies, for example, in accordance with a service plan. This ensures that errors, hacking, user device software settings manipulations, or other malware events do not result in inappropriate levels of QoS for a given device or group of devices. Accordingly, in some embodiments, the traffic control and QoS verification techniques described herein are employed to verify that the proper level of QoS is applied for a given service usage activity in accordance with a QoS priority policy. For example, verification of QoS channel request policy rules behavior can be implemented in a variety of ways including, as an example, monitoring device QoS channel requests and comparing the level of QoS requested with the level of QoS the device is authorized to receive in the service plan in effect for the device. Verification of proper QoS channel usage behavior by a device can be implemented in a variety of ways including, for example, monitoring network based reports of QoS service usage and comparing the network based reports against the service policy rules that should be in effect given the device service plan. Verification of proper device traffic control to implement a QoS service policy that is in effect can be accomplished in a variety of ways by verifying that the appropriate traffic control policy rules are being properly implemented as described herein. In some embodiments, DAS for protecting network capacity techniques include various verification techniques (e.g., verifying monitoring, traffic controlling, reporting, and/or other functions implemented or performed by the device), as described herein.

25

In some embodiments, the QoS router prioritizes traffic on the device. In some embodiments, the QoS router connects the QoS enabled session to the RAB that has the proper QoS level. In some embodiments, one session is routed to the RAB. In some embodiments, more than one session can be routed to an RAB. In some embodiments, multiple RABs providing multiple QoS levels are created to the device, and the QoS router routes each service activity to the RAB dictated by the QoS policy rules in effect on the device.

In some embodiments, the network collects service usage charges for different QoS classes. In some embodiments, there is differentiated service charging for the different classes of QoS service usage. As an example, since guaranteed bit rate traffic consumes network resources whether the traffic capacity is used or not, there can be a time element involved in the charging calculations. As a more detailed example, guaranteed bit rate services can be charged by the total bandwidth provisioned to the device at a given time multiplied by the amount of time that that bandwidth is made available. In some embodiments, differentiated access traffic that has higher QoS than best effort traffic but is not guaranteed bit rate can be charged at a higher rate than best effort traffic but lower than guaranteed bit rate. In some embodiments, such traffic can be charged based on the time the QoS channel is made available and the total amount of data transmitted over the channel, or can only be based on the total amount of data transmitted over the channel. Best effort traffic is charged in some embodiments based only on the total amount of data used, with the data charges being less than differentiated streaming access services. Background data services in some embodiments are charged at the lowest rate, possibly with only certain times of the day or periods of low network traffic demand being available for such services, and with the service being based on total data transmitted. In some embodiments, all QoS service levels can be charged based on a fixed price for a fixed charging period, possibly with a service usage cap with additional charges if the service cap is exceeded. In such fixed price scenario embodiments, the price charged is again higher for higher levels of QoS. In some embodiments, the network collects service usage charges for different network capacity controlled service classes. In some embodiments, there is differentiated service charging for the different classes of network capacity controlled service usage, as described herein.

In some embodiments, the network equipment (e.g., access network element, gateways, AAA, service usage storage systems, home agent, HLR, mobile data center, and/or billing systems) record and report service usage for one or more of the QoS service classes used by the device. In some embodiments, the device service processor records and reports service usage for one or more of the QoS service classes used by the device and reports the QoS service class usage to the service controller (e.g., or another substitute network element). In some embodiments, in which the device is recording reporting usage for one or more QoS service classes, it is important to verify the device service usage reports to ensure that the device usage reports are not distorted, tampered with, and/or otherwise in error. In some embodiments, verifying service usage reports against service policies in place on the device, service processor agent functional operation verification, test service usage events, agent query response sequences, device service processor software protection techniques, device service processor software environment checks, and several other techniques are provided as described herein. For example, using one or

26

more of these verification techniques can provide a verifiable device assisted QoS service usage charging system. As another example, using one or more of these verification techniques can provide a verifiable network capacity controlled service usage charging system. In some embodiments, the network equipment (e.g., access network element, gateways, AAA, service usage storage systems, home agent, HLR, mobile data center, and/or billing systems) record and report service usage for one or more of the network capacity controlled service classes used by the device, as described herein.

In some embodiments, device assisted traffic control is provided for managing network congestion as follows. For example, when a given base station or group of base stations experience traffic demand that is high relative to the available capacity and/or service quality that can be provided, and such a condition is determined (e.g., detected or reported) based on a network busy state assessment as described below and further herein, then a service controller (e.g., or another network function) can issue, send, and/or implement traffic control throttling policies to/for the devices in accordance with a measure of the excess traffic demand the one or more base stations is experiencing. For example, the device service processors connected to an overly busy base station can be instructed to reduce the traffic control priority for one or more classes of QoS traffic, reducing the queuing priority, throttling rate, delay and/or access allowance for some or all of one or more classes of traffic. As another example, the device service processors connected to an overly busy base station can be instructed to reduce the traffic control priority for one or more classes of network capacity controlled services traffic, reducing the queuing priority, throttling rate, delay and/or access allowance for some or all of one or more classes of such traffic. As another example, one or more classes of network capacity controlled services traffic, such as background download processes, which can include, for example, software updates can be turned off completely or throttled back significantly. As another example, best effort traffic such as Internet browsing can be throttled or reduced for a group of devices connected to base stations experiencing excess traffic demand. As another example, a policy can be implemented on the devices connected to busy base stations in which the device is allowed to browse or conduct other best effort service activities at a relatively high throttling rate for a period of time, but if the device uses more than a certain amount of service (e.g., total data downloaded and/or uploaded) in a certain period of time then the device may be traffic controlled according to an adaptive throttling policy as described herein. In some embodiments, higher QoS level traffic cannot be throttled in such circumstances, such as VOIP traffic where real-time guaranteed bit rate is important to meet user service needs or expectations, while lower priority traffic such as interactive browsing and/or background download are throttled and/or blocked. In some embodiments, the QoS availability assessment processes described herein are adjusted so that higher QoS channels are not provided and provisioned in times or locations in which a given base station or group of base stations experience excess demand or demand above a given threshold.

In some embodiments, users or devices that have service plans with higher QoS levels, or service plans with higher priority during busy network periods have different traffic control policies (e.g., for QoS services and/or network capacity controlled services) applied to them that result in a higher level of traffic performance and/or a higher level of QoS service availability. For example, emergency service

27

workers can be given higher traffic control access policies that result in differentiated services during peak busy times on the network or a portion of the network. In some embodiments, users can obtain a premium service plan for differentiated access during peak busy time periods or may use higher levels of QoS service settings and/or service plans to achieve differentiated service during peak busy periods. As another example, services that demand high levels of QoS classes, such as real-time voice services, instant messaging, push to talk, differentiated video streaming, and/or interactive gaming, are not traffic controlled to the same extent that other lower priority services or lower class service plans are traffic controlled during peak busy times. For example, this type of service differentiation can also be applied based on device type, user group, user standing, user reward zone points, and/or other criteria/measures as similarly described herein.

In some embodiments, the decision to control (e.g., reduce, increase, and/or otherwise control in some manner) the access traffic control settings as described above is made by the device service processor based on the device's assessment of the network capacity, which can be determined using various techniques as described herein. In some embodiments, the decision to control the access traffic control settings as described above is made by a service controller (e.g., or other interchangeable network equipment element or elements as described herein) connected to the device that provides instructions to the device to adjust the access policy settings. For example, the service controller can obtain the network capacity information from access equipment elements, from device reports of traffic capacity and/or quality as described herein, or from reports on traffic capacity and/or quality obtained from dedicated devices used for the purpose of assessing network capacity. In some embodiments, the decision to control the access traffic control settings as described above is based on the time of day, the day of week, or both to accommodate cyclical patterns in network capacity and traffic demand.

In some embodiments, a service controller (e.g., or another network equipment element or elements, as described herein) assesses network busy state and then controls device traffic demand by reducing the offered capacity for one or more service classes (e.g., for QoS services and/or network capacity controlled services) supported by the access network equipment elements, such as a wireless base station. In such embodiments, the service controller (e.g., or similar function) gathers the network capacity information with one of the techniques described herein and instructs one or more of the access network equipment elements to reduce the offered capacity for one or more levels of QoS classes and/or network capacity controlled service classes, to one or more of the devices connected to the access network equipment elements. For example, the determination of which devices to throttle back can be made based on an equal throttling of all devices of a given service plan status, or based on the device traffic usage patterns in the recent past as described herein, or based on a combination of service plan status and recent traffic usage patterns.

In some embodiments, the device is enabled with ambient services that have differentiated QoS services and/or network capacity controlled services as part of the ambient service offering. For example, ambient QoS techniques can be provided using the pre-assigned QoS policies for a given service activity set within the ambient service, or using an ambient service application that requests QoS through the QoS API. Other embodiments for providing QoS differen-

28

tiated service activities within ambient service offerings will now be apparent to one of ordinary skill in the art. As another example, ambient network capacity controlled service techniques can be provided using the pre-assigned network capacity controlled policies for a given service activity set within the ambient service, monitoring and dynamically assigned techniques, and/or using an ambient service application that uses API or emulated API techniques, and/or other techniques as described herein.

In some embodiments, a QoS service control policy is adapted as a function of the type of network the device is connected to. For example, the QoS traffic control policies and/or the QoS service charging policies can be different when the device is connected to a wireless network (e.g., a 3G/4G network where there is in general less available QoS enabled traffic capacity) than when the device is connected to a wired network (e.g., a cable or DSL network where there is in general a higher level of QoS capacity available). In such embodiments, the device service processor and the service controller can coordinate to adapt the QoS service control policies and/or the QoS service charging policies to be different depending on which network the device is connected to. Similarly, the device QoS service control policy and/or QoS service charging policy can also be adapted based on whether the device is connected to a home wireless network or a roaming wireless network. In some embodiments, a network capacity controlled service control policy and/or a network capacity controlled charging policy is adapted as a function of the type of network the device is connected to, as similarly described herein.

In some embodiments, various of the QoS related techniques and/or network capacity controlled services techniques described herein are performed on the device using DAS techniques and/or on the service controller in secure communication with a verified service processor executed on the device using DAS techniques. In some embodiments, various of the QoS related techniques and/or network capacity controlled services techniques described herein are performed by/in coordination/communication with one or more intermediate network elements/functions for assisting in various techniques (e.g., functions) for QoS techniques and/or network capacity controlled services techniques as described herein.

FIG. 1 illustrates a functional diagram of a network architecture for providing quality of service (QoS) for device assisted services (DAS) and/or for providing DAS for protecting network capacity in accordance with some embodiments. In some embodiments, QoS for DAS techniques described herein are implemented using the network architecture shown in FIG. 1. In some embodiments, DAS for protecting network capacity techniques described herein are implemented using the network architecture shown in FIG. 1.

As shown, FIG. 1 includes a 4G/3G/2G wireless network operated by, for example, a central provider. As shown, various wireless devices **100** are in communication with base stations **125** for wireless network communication with the wireless network (e.g., via a firewall **124**), and other devices **100** are in communication with Wi-Fi Access Points (APs) or Mesh **702** for wireless communication to Wi-Fi Access CPE **704** in communication with central provider access network **109**. In some embodiments, one or more of the devices **100** are in communication with other network element(s)/equipment that provides an access point, such as a cable network head end, a DSL network DSLAM, a fiber network aggregation node, and/or a satellite network aggregation node. In some embodiments, each of the wireless

29

devices **100** includes a service processor **115** (as shown) (e.g., executed on a processor of the wireless device **100**), and each service processor connects through a secure control plane link to a service controller **122** (e.g., using encrypted communications).

In some embodiments, service usage information includes network based service usage information (e.g., network based service usage measures or charging data records (CDRs), which can, for example, be generated by service usage measurement apparatus in the network equipment), which is obtained from one or more network elements (e.g., BTS/BSCs **125**, RAN Gateways (not shown), Transport Gateways (not shown), Mobile Wireless Center/HLRs **132**, AAA **121**, Service Usage History/CDR Aggregation, Mediation, Feed **118**, or other network equipment). In some embodiments, service usage information includes micro-CDRs. In some embodiments, micro-CDRs are used for CDR mediation or reconciliation that provides for service usage accounting on any device activity that is desired. In some embodiments, each device activity that is desired to be associated with a billing event is assigned a micro-CDR transaction code, and the service processor **115** is programmed to account for that activity associated with that transaction code. In some embodiments, the service processor **115** periodically reports (e.g., during each heartbeat or based on any other periodic, push, and/or pull communication technique(s)) micro-CDR usage measures to, for example, the service controller **122** or some other network element. In some embodiments, the service controller **122** reformats the heartbeat micro-CDR usage information into a valid CDR format (e.g., a CDR format that is used and can be processed by an SGSN or GGSN or other network elements/equipment used/authorized for generating or processing CDRs) and then transmits it to a network element/function for CDR mediation (e.g., CDR Storage, Aggregation, Mediation, Feed **118**).

In some embodiments, CDR mediation is used to account for the micro-CDR service usage information by depositing it into an appropriate service usage account and deducting it from the user device bulk service usage account. For example, this technique provides for a flexible service usage billing solution that uses pre-existing solutions, infrastructures, and/or techniques for CDR mediation and billing. For example, the billing system (e.g., billing system **123** or billing interface **127**) processes the mediated CDR feed from CDR mediation, applies the appropriate account billing codes to the aggregated micro-CDR information that was generated by the device, and then generates billing events in a manner that does not require changes to the existing billing systems (e.g., using new transaction codes to label the new device assisted billing capabilities). In some embodiments, network provisioning system **160** provisions various network elements/functions for authorization in the network, such as to authorize certain network elements/functions (e.g., CDR storage, aggregation, mediation, feed **118** or other network elements/functions) for providing micro-CDRs, reformatted micro-CDRs, and/or aggregated or reconciled CDRs.

As shown in FIG. 1, a CDR storage, aggregation, mediation, feed **118** is provided. In some embodiments, the CDR storage, aggregation, mediation, feed **118** receives, stores, aggregates and mediates micro-CDRs received from mobile devices **100**. In some embodiments, the CDR storage, aggregation, mediation, feed **118** also provides a settlement platform using the mediated micro-CDRs, as described herein. In some embodiments, another network element provides the settlement platform using aggregated and/or mediated

30

micro-CDRs (e.g., central billing interface **127** and/or another network element/function).

In some embodiments, various techniques for partitioning of device groups are used for partitioning the mobile devices **100** (e.g., allocating a subset of mobile devices **100** for a distributor, an OEM, a MVNO, and/or another partner or entity). As shown in FIG. 1, a MVNO core network **210** includes a MVNO CDR storage, aggregation, mediation, feed **118**, a MVNO billing interface **122**, and a MVNO billing system **123** (and other network elements as shown in FIG. 1). In some embodiments, the MVNO CDR storage, aggregation, mediation, feed **118** receives, stores, aggregates and mediates micro-CDRs received from mobile devices **100** (e.g., MVNO group partitioned devices).

Those of ordinary skill in the art will appreciate that various other network architectures can be used for providing device group partitions and a settlement platform, and FIG. 1 is illustrative of just one such example network architecture for which device group partitions and settlement platform techniques described herein can be provided.

In some embodiments, CDR storage, aggregation, mediation, feed **118** (e.g., service usage **118**, including a billing aggregation data store and rules engine) is a functional descriptor for, in some embodiments, a device/network level service usage information collection, aggregation, mediation, and reporting function located in one or more of the networking equipment apparatus/systems attached to one or more of the sub-networks shown in FIG. 1 (e.g., central provider access network **109** and/or central provider core network **110**), which is in communication with the service controller **122** and a central billing interface **127**. As shown in FIG. 1, service usage **118** provides a function in communication with the central provider core network **110**. In some embodiments, the CDR storage, aggregation, mediation, feed **118** function is located elsewhere in the network or partially located in elsewhere or integrated with/as part of other network elements. In some embodiments, CDR storage, aggregation, mediation, feed **118** functionality is located or partially located in the AAA server **121** and/or the mobile wireless center/Home Location Register (HLR) **132** (as shown, in communication with a DNS/DHCP server **126**). In some embodiments, service usage **118** functionality is located or partially located in the base station, base station controller and/or base station aggregator, collectively referred to as base station **125** in FIG. 1. In some embodiments, CDR storage, aggregation, mediation, feed **118** functionality is located or partially located in a networking component in the central provider access network **109**, a networking component in the core network **110**, the central billing system **123**, the central billing interface **127**, and/or in another network component or function. This discussion on the possible locations for the network based and device based service usage information collection, aggregation, mediation, and reporting function (e.g., CDR storage, aggregation, mediation, feed **118**) can be easily generalized as described herein and as shown in the other figures and embodiments described herein by one of ordinary skill in the art. Also, as shown in FIG. 1, the service controller **122** is in communication with the central billing interface **127** (e.g., sometimes referred to as the external billing management interface or billing communication interface), which is in communication with the central billing system **123**. As shown in FIG. 1, an order management **180** and subscriber management **182** are also in communication with the central provider core network **110** for facilitating order and subscriber management of services for the devices **100** in accordance with some embodiments.

31

In some embodiments, a service processor download **170** is provided, which provides for periodical downloads/updates of service processors (e.g., service processor **115**). In some embodiments, verification techniques include periodically updating, replacing, and/or updating an obfuscated version of the service processor, or performing any of these techniques in response to an indication of a potential compromise or tampering of any service processor functionality (e.g., QoS functionality and/or network capacity controlled services functionality) executed on or implemented on the device **100**.

In some embodiments, the CDR storage, aggregation, mediation, feed **118** (and/or other network elements or combinations of network elements) provides a device/network level service usage information collection, aggregation, mediation, and reporting function. In some embodiments, the CDR storage, aggregation, mediation, feed **118** (and/or other network elements or combinations of network elements) collects device generated/assisted service usage information (e.g., micro-CDRs) for one or more devices on the wireless network (e.g., devices **100**); and provides the device generated service usage information in a syntax and a communication protocol that can be used by the wireless network to augment or replace network generated usage information for the one or more devices on the wireless network. In some embodiments, the syntax is a charging data record (CDR), and the communication protocol is selected from one or more of the following: 3GPP, 3GPP2, or other communication protocols. In some embodiments, as described herein, the CDR storage, aggregation, mediation, feed **118** collects/receives micro-CDRs for one or more devices on the wireless network (e.g., devices **100**). In some embodiments, the CDR storage, aggregation, mediation, feed **118** (e.g., or other network elements and/or various combinations of network elements) includes a service usage data store (e.g., a billing aggregator) and a rules engine for aggregating the collected device generated service usage information. In some embodiments, the network device is a CDR feed aggregator, and the CDR storage, aggregation, mediation, feed **118** (and/or other network elements or combinations of network elements) also aggregates (network based) CDRs and/or micro-CDRs for the one or more devices on the wireless network; applies a set of rules to the aggregated CDRs and/or micro-CDRs using a rules engine (e.g., bill by account, transactional billing, revenue sharing model, and/or any other billing or other rules for service usage information collection, aggregation, mediation, and reporting), and communicates a new set of CDRs for the one or more devices on the wireless network to a billing interface or a billing system (e.g., providing a CDR with a billing offset by account/service). In some embodiments, a revenue sharing platform is provided using various techniques described herein. In some embodiments, QoS usage accounting/charging and/or network capacity controlled services usage accounting/charging is provided using various techniques described herein.

In some embodiments, the CDR storage, aggregation, mediation, feed **118** (and/or other network elements or combinations of network elements) communicates a new set of CDRs (e.g., aggregated and mediated CDRs and/or micro-CDRs that are then translated into standard CDRs for a given wireless network) for the one or more devices on the wireless network to a billing interface (e.g., central billing interface **127**) or a billing system (e.g., central billing system **123**). In some embodiments, the CDR storage, aggregation, mediation, feed **118** (and/or other network elements or combinations of network elements) communicates with a

32

service controller (e.g., service controller **122**) to collect the device generated service usage information (e.g., micro-CDRs) for the one or more devices on the wireless network. In some embodiments, the CDR storage, aggregation, mediation, feed **118** (and/or other network elements or combinations of network elements) communicates with a service controller, in which the service controller is in communication with a billing interface or a billing system. In some embodiments, the CDR storage, aggregation, mediation, feed **118** (and/or other network elements or combinations of network elements) communicates the device generated service usage information to a billing interface or a billing system. In some embodiments, the CDR storage, aggregation, mediation, feed **118** (and/or other network elements or combinations of network elements) communicates with a transport gateway and/or a Radio Access Network (RAN) gateway to collect the network generated/based service usage information for the one or more devices on the wireless network. In some embodiments, the service controller **122** communicates the device assisted service usage information (e.g., micro-CDRs) to the CDR storage, aggregation, mediation, feed **118** (e.g., or other network elements and/or various combinations of network elements).

In some embodiments, the CDR storage, aggregation, mediation, feed **118** (e.g., or other network elements and/or various combinations of network elements) performs rules for performing a bill by account aggregation and mediation function. In some embodiments, the CDR storage, aggregation, mediation, feed **118** (and/or other network elements or combinations of network elements) performs rules for performing a service billing function, as described herein, and/or for performing a service/transactional revenue sharing function, as described herein. In some embodiments, the service controller **122** in communication with the CDR storage, aggregation, mediation, feed **118** (and/or other network elements or combinations of network elements) performs a rules engine for aggregating and mediating the device assisted service usage information (e.g., micro-CDRs). In some embodiments, a rules engine device in communication with the CDR storage, aggregation, mediation, feed **118** (e.g., or other network elements and/or various combinations of network elements) performs a rules engine for aggregating and mediating the device assisted service usage information (e.g., QoS service usage information and/or network capacity controlled services usage information).

In some embodiments, the rules engine is included in (e.g., integrated with/part of) the CDR storage, aggregation, mediation, feed **118**. In some embodiments, the rules engine and associated functions, as described herein, is a separate function/device. In some embodiments, the service controller **122** performs some or all of these rules engine based functions, as described herein, and communicates with the central billing interface **127**. In some embodiments, the service controller **122** performs some or all of these rules engine based functions, as described herein, and communicates with the central billing system **123**.

In some embodiments, a settlement platform service is provided. For example, micro-CDRs can be aggregated and mediated to associate service usage for one or more services used by a communications device (e.g., a user of the communications device). A rules engine or another function can determine a revenue share allocation for the service usage for a particular service to determine the settlement for such service usage for the revenue sharing allocation/model and to distribute accounting and settlement information to

33

one or more of carriers, distribution partners, MVNOs, wholesale partners, and/or other partners or entities. In some embodiments, the service is a transactional service.

In some embodiments, duplicate CDRs are sent from the network equipment to the billing system 123 that is used for generating service billing. In some embodiments, duplicate CDRs are filtered to send only those CDRs/records for devices controlled by the service controller and/or service processor (e.g., managed devices). For example, this approach can provide for the same level of reporting, lower level of reporting, and/or higher level of reporting as compared to the reporting required by the central billing system 123.

In some embodiments, a bill-by-account billing offset is provided. For example, bill-by-account billing offset information can be informed to the central billing system 123 by providing a CDR aggregator feed that aggregates the device assisted service usage data feed to provide a new set of CDRs for the managed devices to the central billing interface 127 and/or the central billing system 123. In some embodiments, transaction billing is provided using similar techniques. For example, transaction billing log information can be provided to the central billing interface 127 and/or the central billing system 123.

In some embodiments, the rules engine (e.g., performed by the service usage 118 or another network element, as described herein) provides a bill-by-account billing offset. For example, device assisted service usage information (e.g., micro-CDRs) includes a transaction type field or transaction code (e.g., indicating a type of service for the associated service usage information). For example, the rules engine can apply a rule or a set of rules based on the identified service associated with the device generated service usage information to determine a bill-by-account billing offset (e.g., a new CDR can be generated to provide the determined bill-by-account billing offset). In some examples, the determined bill-by-account billing offset can be provided as a credit to the user's service usage account (e.g., a new CDR can be generated with a negative offset for the user's service usage account, such as for network chatter service usage, or transactional service usage, or for any other purposes based on one or more rules performed by the rules engine).

As another example, for a transactional service, a first new CDR can be generated with a negative offset for the user's service usage account for that transactional service related usage, and a second new CDR can be generated with a positive service usage value to charge that same service usage to the transactional service provider (e.g., Amazon, eBay, or another transactional service provider). In some embodiments, the service controller 122 generates these two new CDRs, and the service usage 118 stores, aggregates, and communicates these two new CDRs to the central billing interface 127. In some embodiments, the service controller 122 generates these two new CDRs, and the service usage 118 stores, aggregates, and communicates these two new CDRs to the central billing interface 127, in which the central billing interface 127 applies rules (e.g., performs the rules engine for determining the bill-by-account billing offset).

In some embodiments, the service controller 122 sends the device generated CDRs to the rules engine (e.g., a service usage data store and rules engine, such as CDR storage, aggregation, mediation, feed 118), and the rules engine applies one or more rules, such as those described herein and/or any other billing/service usage related rules as would be apparent to one of ordinary skill in the art. In some embodiments, the service controller 122 generates CDRs

34

similar to other network elements, and the rules (e.g., bill-by-account) are performed in the central billing interface 127. For example, for the service controller 122 to generate CDRs similar to other network elements, in some embodiments, the service controller 122 is provisioned on the wireless network (e.g., by network provision system 160) and behaves substantially similar to other CDR generators on the network).

In some embodiments, the service controller 122 is provisioned as a new type of networking function that is recognized as a valid, authorized, and secure source for CDRs by the other necessary elements in the network (e.g., CDR storage, aggregation, mediation, feed 118). In some embodiments, if the necessary network apparatus only recognize CDRs from certain types of networking equipment (e.g., a RAN gateway or transport gateway), then the service controller 122 provides authentication credentials to the other networking equipment that indicate that it is one of the approved types of equipment for providing CDRs. In some embodiments, the link between the service controller 122 and the necessary CDR aggregation and mediation equipment is secured, authenticated, encrypted, and/or signed.

In some embodiments, the CDR storage, aggregation, mediation, feed 118 discards the network based service usage information (e.g., network based CDRs) received from one or more network elements. In these embodiments, the service controller 122 provides the device assisted service usage information (e.g., device based CDRs or micro-CDRs) to the CDR storage, aggregation, mediation, feed 118 (e.g., the CDR storage, aggregation, mediation, feed 118 can just provide a store, aggregate, and communication function(s), as it is not required to mediate network based CDRs and device assisted CDRs), and the device based service usage information is provided to the central billing interface 127 or the central billing system 123.

In some embodiments, the device based CDRs (e.g., micro-CDRs) and/or new CDRs generated based on execution of a rules engine as described herein are provided only for devices that are managed and/or based on device group, service plan, or any other criteria, categorization, and/or grouping, such as based on ambient service or ambient service provider or transactional service or transactional service provider.

In some embodiments, QoS for DAS includes a service processor (e.g., any device assisted element/function) that facilitates coordination for and/or provisions wireless access/radio access bearers (e.g., RABs). In some embodiments, the service processor determines whether a request for QoS is authorized (e.g., according to QoS service level, user standing, available local network capacity (e.g., as reported by other device(s) and/or network)). In some embodiments, device QoS capacity demand reports provide and/or augment network capacity demand reports.

In some embodiments, QoS for DAS includes a service controller (e.g., any network device based service control element/function) that facilitates coordination for and/or provisions wireless access/radio access bearers (e.g., RABs) on a device (e.g., a communications device, such as a mobile wireless communications device and/or an intermediate networking device), on network, and/or on device plus network. In some embodiments, the service controller provides device QoS capacity demand reports to other network equipment/elements/functions, and then also provisions the RAB channel based on various criteria and determinations.

In some embodiments, QoS for DAS provides for device assisted monitoring, information, and/or functionality to facilitate QoS without and/or to assist network based moni-

35

toring, information, and/or functionality (e.g., Deep Packet Inspection (DPI) and/or provides such monitoring, information, and/or functionality that may not be available via network based monitoring, information, and/or functionality (e.g., encrypted activities on the device may not be accessible by DPI or other network based techniques). For example, QoS for DAS can assist in the QoS setup to facilitate the QoS setup and provide such information that may not otherwise be available using network based only techniques. For example, device assisted activity and/or service monitoring techniques can assist in classifying the QoS for the monitored activity and/or service using, for example, a QoS activity map (e.g., as described herein or other similar techniques). For example, using such device assisted techniques eliminates and/or minimizes DPI or other network based techniques that can give rise to privacy concerns/issues, network neutrality concerns/issues, and/or otherwise may not be able to provide similar or equivalent granular service/activity monitoring, as discussed above, and/or also off loads such processing from the network (e.g., network elements/devices/functionality) to the communications devices (e.g., at least for such communications devices that can perform such functions, based on their processing and/or memory capabilities, as would be apparent to one of ordinary skill in the art). In some embodiments, QoS for DAS includes the service provider for providing an initial authorization/clearance for a QoS request (e.g., using various techniques described herein), and the service controller determines if the QoS request should be authorized (e.g., based on various QoS authorization/clearance/approval criteria (e.g., QoS activity maps and/or QoS request rule) and/or network capacity, as described herein). In some embodiments, QoS for DAS includes the service provider for providing a QoS request including a QoS class to the service controller, and the service controller determines if the QoS request should be authorized, as described herein. In some embodiments, DAS for protecting network capacity provides for device assisted monitoring, information, and/or functionality to facilitate protecting network capacity without and/or to assist network based monitoring, information, and/or functionality (e.g., Deep Packet Inspection (DPI) and/or provides such monitoring, information, and/or functionality that may not be available via network based monitoring, information, and/or functionality (e.g., encrypted activities on the device may not be accessible by DPI or other network based techniques). In some embodiments, DAS for protecting network capacity provides for device assisted monitoring, information, and/or functionality to facilitate protecting network capacity without solely relying upon DPI and/or without any use or any significant use of DPI wireless network, which conserves network resources and network capacity by controlling device network access behavior at the device instead of deep in the core network at a DPI gateway (e.g., DPI based techniques consume over the air wireless network capacity even if chatty device behavior is blocked at a DPI gateway, in contrast, DAS for protecting network capacity techniques that do not use DPI based techniques for controlling device service usage can, for example, providing a device based usage notification and service selection UI that does not consume over the air wireless network capacity).

In some embodiments, QoS for DAS and/or DAS for protecting network capacity includes providing or facilitating reports for base station (BTS) for network capacity (e.g., sector, channel, busy state information or network capacity usage/availability, and/or network capacity expected demand) based on, for example, one or more of the follow-

36

ing: monitored application usage on the communications device, monitored user activity on the communications device, location of the communications, other available networks, and/or other monitored or determined activity, service usage measure, and/or metric. In some embodiments, at or after execution of an application that is determined to require network service usage (e.g., may require increased wireless network bandwidth, such as based on a service usage activity map), QoS for DAS sends information to the network (e.g., a network controller or other network device element/function) that capacity demand is forthcoming for the communications device (e.g., potentially initiating a provisioning of a QoS radio access bearer (RAB) or other type of RAB).

In some embodiments, network capacity (e.g., busy state information) is collected from one or more communications devices in communication with a wireless network (e.g., network capacity/usage information measured from each respective communications device's perspective is determined and stored by the service processor on each respective communications device) and reported to the service controller, and the service controller (e.g., or another network element/function) uses this information to determine what resources are available for allocation to various levels of QoS (e.g., to respond to/facilitate various QoS requests) and/or to workload balance across multiple base stations and/or networks (e.g., wired networks, cellular, Wi-Fi, and/or other wireless networks).

In some embodiments, the service processor executed on the communications device sends a QoS request (e.g., a wireless network bearer channel reservation request or Radio Access Bearer (RAB) request) to the service controller. The service controller verifies the request using various verification techniques as described herein. In some embodiments, the service controller facilitates coordination of various device QoS requests with one or more base stations (BTSs) in communication with the communications device to provide for the requested QoS reservation to facilitate the new QoS session. In some embodiments, the service controller provides a QoS routing function by, for example, providing various QoS routing instructions to a device service processor (e.g., aggregating, prioritizing, queuing, authorizing, allocating reservations/RABs, denying, re-routing (such as to other BTSs and/or other networks) and/or otherwise managing QoS requests), in which the BTS may or may not be QoS aware. For example, QoS priority can be based on activity (e.g., service usage and/or application), service level, user standing, network capacity, time of day, and/or QoS priority can be purchased on a transaction basis, a session basis, a pre-pay basis or a plan basis. As another example, QoS priority can also vary by device type, user within a group, group, application type, content type, or any other criteria or measure and/or any combination thereof. In some embodiments, the service controller also facilitates coordination of various device QoS requests with other network elements/functions for QoS implementation and management to provide for an end to end QoS solution.

In some embodiments, QoS can be symmetric for two mobile devices or asymmetric. In some embodiments, QoS resource availability can be from communications devices, BTS(s), other network functions (e.g., service control, service controller and/or any other network elements/functions) or any combination thereof. In some embodiments, the service controller provides QoS demand information to another network element/function. In some embodiments, the service controller provides the central aggregator and policy decision point (PDP). In some embodiments, the

37

service controller controls (e.g., at least in part) QoS related functions for communications devices, BTS(s), and/or a combination of both.

In some embodiments, charging (e.g., monitoring and/or determining associating charging or billing) for QoS service usage/transactions and/or network capacity controlled services usage/transactions is determined using various techniques described herein. For example, the service processor can assist in charging for QoS and/or network capacity controlled activities. In some embodiments, the service processor uses device assisted Charging Data Records (CDRs) or micro-CDRs to assist in charging for QoS and/or network capacity controlled activities (e.g., using QoS class related transaction codes and/or network capacity controlled related transaction codes), as described herein with respect to various embodiments. In some embodiments, charging for QoS and/or network capacity controlled services is performed in whole or in part by one or more network elements/functions (e.g., service controller, SGSN/GGSN/other gateways, and/or billing interfaces/servers).

In some embodiments, service usage information includes network based service usage information. In some embodiments, the network based service usage information includes network based CDRs. In some embodiments, service usage information includes device based service usage information. In some embodiments, device based service usage information includes device assisted CDRs, also referred to herein as micro-CDRs, as described herein. In some embodiments, micro-CDRs are used for CDR mediation or reconciliation that provides for service usage accounting on any device activity that is desired (e.g., providing granular service usage information, such as based on application layer service usage monitoring, transaction service usage monitoring, QoS activities/sessions/transactions, network capacity controlled activities/sessions/transactions, and/or other types of service usage information). In some embodiments, each device includes a service processor (e.g., a service processor executed on a processor of a communications device, such as a mobile device or an intermediate networking device that can communicate with a wireless network).

In some embodiments, each device activity that is desired to be associated with a billing event (e.g., for a QoS related billing event) is assigned a micro-CDR transaction code, and the service processor is programmed to account for that activity associated with that transaction code (e.g., various transaction codes can be associated with service usage associated with certain services, applications, and/or based on QoS classes or priorities, respectively, which can be used for providing granular service usage for these various Internet/network based services/sites/transactions and/or any other Internet/network based services/sites, which can include transactional based services). For example, using these techniques, as described herein, essentially any type of device activity (e.g., including QoS classes and prioritization and/or network capacity controlled classes and prioritization) can be individually accounted for and/or controlled (e.g., throttled, restricted, and/or otherwise controlled as desired). In some embodiments, the service processor periodically reports (e.g., during each heartbeat or based on any other periodic, push, and/or pull communication technique(s)) micro-CDR usage measures to, for example, a service controller or some other network element/function. In some embodiments, the service controller reformats the heartbeat micro-CDR usage information into a valid CDR format (e.g., a CDR format that is used and can be processed by an SGSN or GGSN or some other authorized network

38

element/function for CDRs) and then transmits the reformatted micro-CDRs to a network element/function for performing CDR mediation.

In some embodiments, CDR mediation is used to properly account for the micro-CDR service usage information by depositing it into an appropriate service usage account and deducting it from the user device bulk service usage account. For example, this technique provides for a flexible service usage billing solution that uses pre-existing solutions for CDR mediation and billing. For example, the billing system can process the mediated CDR feed from CDR mediation, apply the appropriate account billing codes to the aggregated micro-CDR information that was generated by the device, and then generate billing events in a manner that does not require changes to existing billing systems, infrastructures, and techniques (e.g., using new transaction codes to label the new device assisted billing capabilities).

In some embodiments, the various QoS techniques performed on or by the communications device (e.g., using a service processor to provide or assist in providing QoS session provisioning, QoS policy management, QoS policy enforcement, and/or QoS accounting/charging, such as QoS charging records and reports) are verified (e.g., using various verification techniques described herein). In some embodiments, the various network capacity controlled services techniques performed on or by the communications device (e.g., using a service processor to provide or assist in providing network capacity controlled services policy management, network capacity controlled services policy enforcement, and/or network capacity controlled services charging, such as network capacity controlled services charging records and reports) are verified (e.g., using various verification techniques described herein).

For example, a QoS request, QoS related policy rules (e.g., QoS activity map, QoS related service plan and/or service policy settings) and implementation, QoS policy enforcement, and QoS charging are verified (e.g., periodically, per transaction, and/or based on some other criteria/metric). In some embodiments, verification techniques include one or more of the following: compare a network based service usage measure with a first service policy associated with the communications device, compare a device assisted service usage measure with the first service policy, compare the network based service usage measure to the device assisted service usage measure, perform a test and confirm a device assisted service usage measure based on the test, perform a User Interface (UI) notification (e.g., which can include a user authentication, password, question/answer challenge, and/or other authentication technique), and/or other similar verification techniques as will now be apparent to one of ordinary skill in the art. Accordingly, in some embodiments, QoS for DAS "closes the loop" for verification of various QoS related techniques, such as QoS requests, QoS grants, QoS usage, and/or QoS charging. In some embodiments, the service processor and the service controller serve as a verifiable QoS management/coordination system for other QoS elements/functions in network. In some embodiments, if such or other verification techniques determine or assist in determining that a QoS request, QoS report, and/or QoS policy behavior (e.g., or similarly, network capacity controlled services monitoring, reporting, and/or policy behavior) does not match expected requests, reports, and/or policy, then responsive actions can be performed, for example, the communications device (e.g., and/or suspect services) can be suspended, quarantined, killed/terminated, and/or flagged for further analysis/scrutiny to determine whether the device is malfunctioning, needs

updating, has been tampered with or compromised, is infected with malware, and/or if any other problem exists.

In some embodiments, the communications device (e.g., the service processor) maintains a QoS flow table that associates or maps device activity to QoS level/class to RAB/QoS channel, and in some embodiments, the communications device also informs a QoS management network function/element of the relative priority of the QoS flows for the communications device (e.g., based on or using the QoS flow table). In some embodiments, the service controller receives or collects information from the communications device and maintains such a QoS flow table for the communications device and, in some embodiments, the service controller also informs a QoS management network function/element of the relative priority of the QoS flows for the communications device (e.g., based on or using the QoS flow table). In some embodiments, flows can be assigned to activities originating at the communications device in a transparent way, or simply by activity class or user preference, or using other techniques.

In some embodiments, the communications device maintains a table of QoS billing rates, scheduled transmission times, and/or other QoS related information to implement an overlay MAC at the data networking level to manage QoS on legacy networks that are not QoS MAC enabled and/or do not have the various functionality to support QoS controls (e.g., and such techniques can also be used to provide for QoS functionality across different networks). In some embodiments, QoS related policies are exchanged between roaming and home service controllers to facilitate QoS support while roaming on a non-home network(s).

In some embodiments, the communications device serves as a network capacity indicator (e.g., collecting network capacity information for a local cell and communicating or reporting that network capacity information to the service controller). For example, permanent local cell communications devices can be placed in local cell areas to augment legacy equipment for such network capacity indicator/reporting functions. Various other techniques for determining network capacity and/or network availability are described herein.

In some embodiments, service partners and/or service providers can subsidize in whole or in part to upgrade a given user or group of users to better QoS related service level agreement (SLA)/class for a preferred destination. In some embodiments, based on monitored service usage and/or other monitored behavior of the communications device, such subsidized QoS upgrade/offers can be presented to a user of the communications device (e.g., as an incentive/reward for desired or preferred user behavior or for other reasons). Similarly, in some embodiments, these techniques are also applied to network capacity controlled services.

In some embodiments, QoS charging is based on QoS channel/reservation, service flow, or RAB charging (e.g., single flow per RAB, multi-flow per RAB, multi-RAB per flow). In some embodiments, charging (e.g., for QoS and/or for network capacity controlled services) is based on one or more of the following: network busy state, time criteria, user service class request, traffic volume and class, time and class, network capacity (e.g., network busy state) and class, time of day and class, location, traffic type, application type, application class, destination, destination type, partner service, and/or other criteria/measures. In some embodiments, QoS charging is verified using the various verification techniques described herein (e.g., test charging events). In some embodiments, network capacity controlled services charging is verified using the various verification techniques

described herein (e.g., test charging events). In some embodiments, QoS charging is by data usage (e.g., by Megabyte (MB)), service flow by time by QoS class, speed by time, network busy state, time of day/day of week, service plan, current network, and/or other criteria/measures. In some embodiments, network capacity controlled services charging is by data usage (e.g., by Megabyte (MB)), service flow by time by network capacity controlled services class, speed by time, network busy state, time of day/day of week, service plan, current network, and/or other criteria/measures.

In some embodiments, QoS for DAS includes coordinating functions with one or more of the following: DAS elements/functions, Radio Access Network (RAN), Transport network, Core network, GRX network, IPX network, and/or other networks/elements/functions.

FIG. 2 illustrates another functional diagram of another network architecture for providing quality of service (QoS) for device assisted services (DAS) and/or for providing DAS for protecting network capacity in accordance with some embodiments. In some embodiments, QoS for DAS techniques described herein are implemented using the network architecture shown in FIG. 2. In some embodiments, DAS for protecting network capacity techniques described herein are implemented using the network architecture shown in FIG. 2.

As shown, FIG. 2 includes various devices **100** including service processors **115**. For example, devices **100** can include various types of mobile devices, such as phones, PDAs, computing devices, laptops, net books, tablets, cameras, music/media players, GPS devices, networked appliances, and any other networked device; and/or devices **100** can include various types of intermediate networking devices, as described herein. The devices **100** are in communication with service control **210** and central provider access and core networks **220**. Service policies and accounting functions **230** are also provided in communication with the central provider access and core networks **220**. For example, devices **100** can communicate via the central provider access and core networks **220** to the Internet **120** for access to various Internet sites/services **240** (e.g., Google sites/services, Yahoo sites/services, Blackberry services, Apple iTunes and AppStore, Amazon.com, FaceBook, and/or any other Internet service or other network facilitated service).

In some embodiments, FIG. 2 provides a wireless network architecture that supports various DAS for protecting network capacity techniques as described herein. Those of ordinary skill in the art will appreciate that various other network architectures can be used for providing various DAS for protecting network capacity techniques as described herein, and FIG. 2 is illustrative of just another such example network architecture for which DAS for protecting network capacity techniques as described herein can be provided.

FIG. 3 illustrates another functional diagram of an architecture **300** including a device based service processor **115** and a service controller **122** for providing quality of service (QoS) for device assisted services (DAS) and/or for providing DAS for protecting network capacity in accordance with some embodiments. In some embodiments, QoS for DAS techniques described herein are implemented using the functions/elements shown in FIG. 3. In some embodiments, DAS for protecting network capacity techniques described herein are implemented using the functions/elements shown in FIG. 3.

41

For example, the architecture 300 provides a relatively full featured device based service processor implementation and service controller implementation. As shown, this corresponds to a networking configuration in which the service controller 122 is connected to the Internet 120 and not directly to the access network 1610. As shown, a data plane (e.g., service traffic plane) communication path is shown in solid line connections and control plane (e.g., service control plane) communication path is shown in dashed line connections. As will be apparent to one of ordinary skill in the art, the division in functionality between one device agent and another is based on, for example, design choices, networking environments, devices and/or services/applications, and various different combinations can be used in various different implementations. For example, the functional lines can be re-drawn in any way that the product designers see fit. As shown, this includes certain divisions and functional breakouts for device agents as an illustrative implementation, although other, potentially more complex, embodiments can include different divisions and functional breakouts for device agent functionality specifications, for example, in order to manage development specification and testing complexity and workflow. In addition, the placement of the agents that operate, interact with or monitor the data path can be moved or re-ordered in various embodiments. For example, the functional elements shown in FIG. 3 are described below with respect to, for example, FIGS. 4, 12, and 13 as well as FIGS. 5 through 11 (e.g., QoS for DAS related embodiments) and FIGS. 14 through 23 (e.g., DAS for protecting network capacity related embodiments).

As shown in FIG. 3, service processor 115 includes a service control device link 1691. For example, as device based service control techniques involving supervision across a network become more sophisticated, it becomes increasingly important to have an efficient and flexible control plane communication link between the device agents and the network elements communicating with, controlling, monitoring, or verifying service policy. In some embodiments, the service control device link 1691 provides the device side of a system for transmission and reception of service agent to/from network element functions. In some embodiments, the traffic efficiency of this link is enhanced by buffering and framing multiple agent messages in the transmissions. In some embodiments, the traffic efficiency is further improved by controlling the transmission frequency or linking the transmission frequency to the rate of service usage or traffic usage. In some embodiments, one or more levels of security or encryption are used to make the link robust to discovery, eavesdropping or compromise. In some embodiments, the service control device link 1691 also provides the communications link and heartbeat timing for the agent heartbeat function. As discussed below, various embodiments disclosed herein for the service control device link 1691 provide an efficient and secure solution for transmitting and receiving service policy implementation, control, monitoring and verification information with other network elements.

As shown in FIG. 3, the service controller 122 includes a service control server link 1638. In some embodiments, device based service control techniques involving supervision across a network (e.g., on the control plane) are more sophisticated, and for such it is increasingly important to have an efficient and flexible control plane communication link between the device agents (e.g., of the service processor 115) and the network elements (e.g., of the service controller 122) communicating with, controlling, monitoring, or verifying service policy. For example, the communication link

42

between the service control server link 1638 of service controller 122 and the service control device link 1691 of the service processor 115 can provide an efficient and flexible control plane communication link, a service control link 1653 as shown in FIG. 3, and, in some embodiments, this control plane communication link provides for a secure (e.g., encrypted) communications link for providing secure, bidirectional communications between the service processor 115 and the service controller 122. In some embodiments, the service control server link 1638 provides the network side of a system for transmission and reception of service agent to/from network element functions. In some embodiments, the traffic efficiency of this link is enhanced by buffering and framing multiple agent messages in the transmissions (e.g., thereby reducing network chatter). In some embodiments, the traffic efficiency is further improved by controlling the transmission frequency and/or linking the transmission frequency to the rate of service usage or traffic usage. In some embodiments, one or more levels of security and/or encryption are used to secure the link against potential discovery, eavesdropping or compromise of communications on the link. In some embodiments, the service control server link 1638 also provides the communications link and heartbeat timing for the agent heartbeat function.

In some embodiments, the service control server link 1638 provides for securing, signing, encrypting and/or otherwise protecting the communications before sending such communications over the service control link 1653. For example, the service control server link 1638 can send to the transport layer or directly to the link layer for transmission. In another example, the service control server link 1638 further secures the communications with transport layer encryption, such as TCP TLS or another secure transport layer protocol. As another example, the service control server link 1638 can encrypt at the link layer, such as using IPSEC, various possible VPN services, other forms of IP layer encryption and/or another link layer encryption technique.

As shown in FIG. 3, the service controller 122 includes an access control integrity server 1654 (e.g., service policy security server). In some embodiments, the access control integrity server 1654 collects device information on service policy, service usage, agent configuration, and/or agent behavior. For example, the access control integrity server 1654 can cross check this information to identify integrity breaches in the service policy implementation and control system. In another example, the access control integrity server 1654 can initiate action when a service policy violation (e.g., QoS policy violation and/or a network capacity controlled services policy violation) or a system integrity breach is suspected.

In some embodiments, the access control integrity server 1654 (and/or some other agent of service controller 122) acts on access control integrity agent 1694 (e.g., service policy security agent) reports and error conditions. Many of the access control integrity agent 1654 checks can be accomplished by the server. For example, the access control integrity agent 1654 checks include one or more of the following: service usage measure against usage range consistent with policies (e.g., usage measure from the network and/or from the device); configuration of agents; operation of the agents; and/or dynamic agent download.

In some embodiments, the access control integrity server 1654 (and/or some other agent of service controller 122) verifies device service policy implementations by comparing various service usage measures (e.g., based on network monitored information, such as by using IPDRs or CDRs,

43

and/or local service usage monitoring information) against expected service usage behavior given the policies that are intended to be in place (e.g., a QoS policy and/or a network capacity controlled services policy). For example, device service policy implementations can include measuring total QoS data passed, QoS data passed in a period of time, IP addresses, data per IP address, and/or other measures such as location, downloads, email accessed, URLs, and comparing such measures expected service usage behavior given the policies that are intended to be in place.

In some embodiments, the access control integrity server 1654 (e.g., and/or some other agent of service controller 122) verifies device service policy, and the verification error conditions that can indicate a mismatch in QoS service measure and QoS service policy include one or more of the following: unauthorized network access (e.g., access beyond ambient service policy limits); unauthorized network speed (e.g., average speed beyond service policy limit); network data amount does not match QoS policy limit (e.g., device not stop at limit without re-up/revising service policy); unauthorized network address; unauthorized service usage (e.g., VOIP, email, and/or web browsing); unauthorized application usage (e.g., email, VOIP, email, and/or web); service usage rate too high for plan, and policy controller not controlling/throttling it down; and/or any other mismatch in service measure and service policy. Accordingly, in some embodiments, the access control integrity server 1654 (and/or some other agent of service controller 122) provides a policy/service control integrity service to continually (e.g., periodically and/or based on trigger events) verify that the service control of the device has not been compromised and/or is not behaving out of policy (e.g., a QoS policy and/or a network capacity controlled services policy).

As shown in FIG. 3, service controller 122 includes a service history server 1650 (e.g., charging server). In some embodiments, the service history server 1650 collects and records service usage or service activity reports from the Access Network AAA Server 1621 and the Service Monitor Agent 1696. For example, although service usage history from the network elements can in certain embodiments be less detailed than service history from the device, the service history from the network can provide a valuable source for verification of device service policy implementation, because, for example, it is extremely difficult for a device error or compromise event on the device to compromise the network based equipment and software. For example, service history reports from the device can include various service tracking information, as similarly described above. In some embodiments, the service history server 1650 provides the service history on request to other servers and/or one or more agents. In some embodiments, the service history server 1650 provides the service usage history to the device service history 1618 (e.g., CDR feed and CDR mediation). In some embodiments, for purposes of facilitating the activation tracking service functions (described below), the service history server 1650 maintains a history of which networks the device has connected to. For example, this network activity summary can include a summary of the networks accessed, activity versus time per connection, and/or traffic versus time per connection. As another example, this activity summary can further be analyzed or reported to estimate the type of service plan associated with the traffic activity for the purpose of bill sharing reconciliation.

As shown in FIG. 3, service controller 122 includes a policy management server 1652 (e.g., policy decision point (PDP) server) for managing service usage policies, such as

44

QoS policies and/or a network capacity controlled services policies. In some embodiments, the policy management server 1652 transmits policies to the service processor 115 via the service control link 1653. In some embodiments, the policy management server 1652 manages policy settings on the device (e.g., various policy settings as described herein with respect to various embodiments) in accordance with a device service profile. In some embodiments, the policy management server 1652 sets instantaneous policies on policy implementation agents (e.g., policy implementation agent 1690). For example, the policy management server 1652 can issue policy settings, monitor service usage and, if necessary, modify policy settings. For example, in the case of a user who prefers for the network to manage their service usage costs, or in the case of any adaptive policy management needs, the policy management server 1652 can maintain a relatively high frequency of communication with the device to collect traffic and/or service measures and issue new policy settings. In this example, device monitored service measures and any user service policy preference changes are reported, periodically and/or based on various triggers/events/requests, to the policy management server 1652. In this example, user privacy settings generally require secure communication with the network (e.g., a secure service control link 1653), such as with the policy management server 1652, to ensure that various aspects of user privacy are properly maintained during such configuration requests/policy settings transmitted over the network. For example, information can be compartmentalized to service policy management and not communicated to other databases used for CRM for maintaining user privacy.

In some embodiments, the policy management server 1652 provides adaptive policy management on the device. For example, the policy management server 1652 can issue policy settings and objectives and rely on the device based policy management (e.g., service processor 115) for some or all of the policy adaptation. This approach can require less interaction with the device thereby reducing network chatter on the service control link 1653 for purposes of device policy management (e.g., network chatter is reduced relative to various server/network based policy management approaches described above). This approach can also provide robust user privacy embodiments by allowing the user to configure the device policy for user privacy preferences/settings so that, for example, sensitive information (e.g., geo-location data, website history, and/or other sensitive information) is not communicated to the network without the user's approval. In some embodiments, the policy management server 1652 adjusts service policy based on time of day. In some embodiments, the policy management server 1652 receives, requests, and/or otherwise obtains a measure of network availability/capacity and adjusts traffic shaping policy and/or other policy settings based on available network availability/capacity (e.g., a network busy state).

As shown in FIG. 3, service controller 122 includes a network traffic analysis server 1656. In some embodiments, the network traffic analysis server 1656 collects/receives service usage history for devices and/or groups of devices and analyzes the service usage. In some embodiments, the network traffic analysis server 1656 presents service usage statistics in various formats to identify improvements in network service quality and/or service profitability. In some embodiments, the network traffic analysis server 1656 estimates the service quality and/or service usage for the network under variable settings on potential service policies. In some embodiments, the network traffic analysis server 1656 identifies actual or potential service behaviors by one

45

or more devices that are causing problems for overall network service quality or service cost. In some embodiments, the network traffic analysis server **1656** estimates the network availability/capacity for the network under variable settings on potential service policies. In some embodiments, the network traffic analysis server **1656** identifies actual or potential service behaviors by one or more devices that are impacting and/or causing problems for overall network availability/capacity.

As shown in FIG. 3, Service Analysis, Test & Download **122B** includes a beta test server **1658** (e.g., policy creation point and beta test server). In some embodiments, the beta test server **1658** publishes candidate service plan policy settings to one or more devices. In some embodiments, the beta test server **1658** provides summary reports of network service usage or user feedback information for one or more candidate service plan policy settings. In some embodiments, the beta test server **1658** provides a mechanism to compare the beta test results for different candidate service plan policy settings or select the optimum candidates for further policy settings optimization, such as for protecting network capacity.

As shown in FIG. 3, service controller **122** includes a service download control server **1660** (e.g., a service software download control server). In some embodiments, the service download control server **1660** provides a download function to install and/or update service software elements (e.g., the service processor **115** and/or agents/components of the service processor **115**) on the device, as described herein.

As shown in FIG. 3 service controller **122** includes a billing event server **1662** (e.g., micro-CDR server). In some embodiments, the billing event server **1662** collects billing events, provides service plan information to the service processor **115**, provides service usage updates to the service processor **115**, serves as interface between device and central billing server **1619**, and/or provides trusted third party function for certain ecommerce billing transactions.

As shown in FIG. 3, the Access Network HLR AAA server **1621** is in network communication with the access network **1610**. In some embodiments, the Access Network AAA server **1621** provides the necessary access network AAA services (e.g., access control and authorization functions for the device access layer) to allow the devices onto the central provider access network and the service provider network. In some embodiments, another layer of access control is required for the device to gain access to other networks, such as the Internet, a corporate network and/or a machine to machine network. This additional layer of access control can be implemented, for example, by the service processor **115** on the device. In some embodiments, the Access Network AAA server **1621** also provides the ability to suspend service for a device and resume service for a device based on communications received from the service controller **122**. In some embodiments, the Access Network AAA server **1621** also provides the ability to direct routing for device traffic to a quarantine network or to restrict or limit network access when a device quarantine condition is invoked. In some embodiments, the Access Network AAA server **1621** also records and reports device network service usage (e.g., device network service usage can be reported to the device service history **1618**).

As shown in FIG. 3, the device service history **1618** is in network communication with the access network **1610**. In some embodiments, the device service history **1618** provides service usage data records used for various purposes in various embodiments. In some embodiments, the device service history **1618** is used to assist in verifying service

46

policy implementation. In some embodiments, the device service history **1618** is used to verify service monitoring. In some embodiments, the device service history **1618** is used to verify billing records and/or billing policy implementation (e.g., to verify service usage charging). In some embodiments, the device service history **1618** is used to synchronize and/or verify the local service usage counter (e.g., to verify service usage accounting).

As shown in FIG. 3, the central billing **1619** (e.g., central provider billing server) is in network communication with the access network **1610**. In some embodiments, the central provider billing server **1619** provides a mediation function for central provider billing events. For example, the central provider billing server **1619** can accept service plan changes. In some embodiments, the central provider billing server **1619** provides updates on device service usage, service plan limits and/or service policies. In some embodiments, the central provider billing server **1619** collects billing events, formulates bills, bills service users, provides certain billing event data and service plan information to the service controller **122** and/or device **100**.

As shown in FIG. 3, in some embodiments, modem selection and control **1811** (e.g., in communication with connection manager **1804** as shown) selects the access network connection and is in communication with the modem firewall **1655**, and modem drivers **1831**, **1815**, **1814**, **1813**, **1812** convert data traffic into modem bus traffic for one or more modems and are in communication with the modem selection and control **1811**. In some embodiments, different profiles are selected based on the selected network connection (e.g., different service profiles/policies for WWAN, WLAN, WPAN, Ethernet and/or DSL network connections), which is also referred to herein as multimode profile setting. For example, service profile settings can be based on the actual access network (e.g., home DSL/cable or work network) behind the Wi-Fi not the fact that it is Wi-Fi (e.g., or any other network, such as DSL/cable, satellite, or T-1), which is viewed as different than accessing a Wi-Fi network at the coffee shop. For example, in a Wi-Fi hotspot situation in which there are a significant number of users on a DSL or T-1 backhaul, the service controller can sit in a service provider cloud or an MVNO cloud, the service controls can be provided by a VSP capability offered by the service provider or the service controller can be owned by the hotspot service provider that uses the service controller on their own without any association with an access network service provider. For example, the service processors can be controlled by the service controller to divide up the available bandwidth at the hotspot according to QoS or user sharing rules (e.g., with some users having higher differentiated priority (e.g., potentially for higher service payments) than other users). As another example, ambient services (e.g., as similarly described herein) can be provided for the hotspot for verified service processors.

In some embodiments, the service processor **115** and service controller **122** are capable of assigning multiple service profiles associated with multiple service plans that the user chooses individually or in combination as a package. For example, a device **100** starts with ambient services that include free transaction services wherein the user pays for transactions or events rather than the basic service (e.g., a news service, eReader, PND service, pay as you go session Internet) in which each service is supported with a bill by account capability to correctly account for any subsidized partner billing to provide the transaction services (e.g., Barnes and Noble may pay for the eReader service and offer a revenue share to the service provider for any book or

47

magazine transactions purchased from the device **100**). In some embodiments, the bill by account service can also track the transactions and, in some embodiments, advertisements for the purpose of revenue sharing, all using the service monitoring capabilities disclosed herein. After initiating services with the free ambient service discussed above, the user may later choose a post-pay monthly Internet, email, and SMS service. In this case, the service controller **122** would obtain from the billing system **123** in the case of network based billing (e.g., or the service controller **122** billing event server **1622** in the case of device based billing) the billing plan code for the new Internet, email and SMS service. In some embodiments, this code is cross referenced in a database (e.g., the policy management server **1652**) to find the appropriate service profile for the new service in combination with the initial ambient service. The new superset service profile is then applied so that the user maintains free access to the ambient services, and the billing partners continue to subsidize those services, the user also gets access to Internet services and may choose the service control profile (e.g., from one of the embodiments disclosed herein). The superset profile is the profile that provides the combined capabilities of two or more service profiles when the profiles are applied to the same device **100** service processor. In some embodiments, the device **100** (service processor **115**) can determine the superset profile rather than the service controller **122** when more than one “stackable” service is selected by the user or otherwise applied to the device. The flexibility of the service processor **115** and service controller **122** embodiments described herein allow for a large variety of service profiles to be defined and applied individually or as a superset to achieve the desired device **100** service features.

As shown in FIG. 3, an agent communication bus **1630** represents a functional description for providing communication for the various service processor **115** agents and functions. In some embodiments, as represented in the functional diagram illustrated in FIG. 3, the architecture of the bus is generally multipoint to multipoint so that any agent can communicate with any other agent, the service controller or in some cases other components of the device, such user interface **1697** and/or modem components. As described below, the architecture can also be point to point for certain agents or communication transactions, or point to multipoint within the agent framework so that all agent communication can be concentrated, or secured, or controlled, or restricted, or logged or reported. In some embodiments, the agent communication bus is secured, signed, encrypted, hidden, partitioned, and/or otherwise protected from unauthorized monitoring or usage. In some embodiments, an application interface agent (not shown) is used to literally tag or virtually tag application layer traffic so that the policy implementation agent(s) **1690** has the necessary information to implement selected traffic shaping solutions. In some embodiments, an application interface agent (not shown) is in communication with various applications, including a TCP application **1604**, an IP application **1605**, and a voice application **1602**.

As shown in FIG. 3, service processor **115** includes an API and OS stack interface **1693**. In some embodiments, the API and OS stack interface **1693** provides the QoS API functionality as similarly described herein with respect to various embodiments. In some embodiments, a QoS API is used to report back QoS availability to applications. In some embodiments, the API and OS stack interface **1693** provides the network capacity controlled API and/or emulated API functionality as similarly described herein with respect to

48

various embodiments. As shown, service processor **115** also includes a router **1698** (e.g., a QoS router agent/function and/or a network capacity controlled services router agent/function) and a policy decision point (PDP) agent **1692**. In some embodiments, the router **1698** provides QoS router functionality as similarly described herein with respect to various embodiments. In some embodiments, the router **1698** provides network capacity controlled services router functionality as similarly described herein with respect to various embodiments. In some embodiments, the QoS router supports multiple QoS channels (e.g., one or more provisioned/allocated QoS links forming a QoS channel between the device and the desired end point, such as an access point/BTS/gateway/network for a single ended QoS channel or other communication device for an end to end QoS channel, depending on the QoS connection/network support/availability/etc.). In some embodiments, the QoS router supports multiple QoS channels, which can each have different QoS classes/levels. In some embodiments, the QoS router routes application/service usage traffic to an appropriate QoS channel. In some embodiments, the QoS router determines the routing/mapping based on, for example, one or more of the following: a QoS API request, a QoS activity map, a user request, a service plan, a service profile, service policy settings, network capacity, service controller or other intermediate QoS network element/function/device, and/or any other criteria/measure, as similarly described herein with respect to various embodiments. In some embodiments, multiple different applications/services are routed to a particular QoS channel using various techniques described herein. In some embodiments, different applications/services are routed to different QoS channels using various techniques described herein. In some embodiments, the QoS router assists in managing and/or optimizing QoS usage for the communications device. In some embodiments, the QoS router assists in managing and/or optimizing QoS usage across multiple communications devices (e.g., based on network capacity for a given cell area/base station or other access point). In some embodiments, PDP agent **1692** provides the PDP agent functionality as similarly described herein with respect to various embodiments. As shown, architecture **300** also includes a suspend resume interface **320**, network QoS provisioning interfaces **330** (e.g., for providing the various QoS techniques described herein), and an activation/suspend resume server **340** and billing interface server **350** in the service controller **122A**.

In some embodiments, device assisted services (DAS) techniques for providing an activity map for classifying or categorizing service usage activities to associate various monitored activities (e.g., by URL, by network domain, by website, by network traffic type, by application or application type, and/or any other service usage activity categorization/classification) with associated IP addresses are provided. In some embodiments, a policy control agent (not shown), service monitor agent **1696** (e.g., charging agent), or another agent or function (or combinations thereof) of the service processor **115** provides a DAS activity map. In some embodiments, a policy control agent (not shown), service monitor agent, or another agent or function (or combinations thereof) of the service processor provides an activity map for classifying or categorizing service usage activities to associate various monitored activities (e.g., by Uniform Resource Locator (URL), by network domain, by website, by network traffic type, by socket (such as by IP address, protocol, and/or port), by socket id (such as port address/number), by port number, by content type, by application or application type, and/or any other service usage activity

49

classification/categorization) with associated IP addresses and/or other criteria/measures. In some embodiments, a policy control agent, service monitor agent, or another agent or function (or combinations thereof) of the service processor determines the associated IP addresses for monitored service usage activities using various techniques to snoop the DNS request(s) (e.g., by performing such snooping techniques on the device **100** the associated IP addresses can be determined without the need for a network request for a reverse DNS lookup). In some embodiments, a policy control agent, service monitor agent, or another agent or function (or combinations thereof) of the service processor records and reports IP addresses or includes a DNS lookup function to report IP addresses or IP addresses and associated URLs for monitored service usage activities. For example, a policy control agent, service monitor agent, or another agent or function (or combinations thereof) of the service processor can determine the associated IP addresses for monitored service usage activities using various techniques to perform a DNS lookup function (e.g., using a local DNS cache on the monitored device **100**). In some embodiments, one or more of these techniques are used to dynamically build and maintain a DAS activity map that maps, for example, URLs to IP addresses, applications to IP addresses, content types to IP addresses, and/or any other categorization/classification to IP addresses as applicable. In some embodiments, the DAS activity map is used for various DAS traffic control and/or throttling techniques as described herein with respect to various embodiments for providing QoS for DAS and/or for providing DAS for protecting network capacity. In some embodiments, the DAS activity map is used to provide the user various UI related information and notification techniques related to service usage as described herein with respect to various embodiments. In some embodiments, the DAS activity map is used to provide service usage monitoring, prediction/estimation of future service usage, service usage billing (e.g., bill by account and/or any other service usage/billing categorization techniques), DAS techniques for ambient services usage monitoring, DAS techniques for generating micro-CDRs, and/or any of the various other DAS related techniques as described herein with respect to various embodiments.

In some embodiments, all or a portion of the service processor **115** functions disclosed herein are implemented in software. In some embodiments, all or a portion of the service processor **115** functions are implemented in hardware. In some embodiments, all or substantially all of the service processor **115** functionality (e.g., as discussed herein) is implemented and stored in software that can be performed on (e.g., executed by) various components in device **100**. In some embodiments, it is advantageous to store or implement certain portions or all of service processor **115** in protected or secure memory so that other undesired programs (e.g., and/or unauthorized users) have difficulty accessing the functions or software in service processor **115**. In some embodiments, service processor **115**, at least in part, is implemented in and/or stored on secure non-volatile memory (e.g., non volatile memory can be secure non-volatile memory) that is not accessible without pass keys and/or other security mechanisms (e.g., security credentials). In some embodiments, the ability to load at least a portion of service processor **115** software into protected non-volatile memory also requires a secure key and/or signature and/or requires that the service processor **115** software components being loaded into non-volatile memory are also securely encrypted and appropriately signed by an authority that is trusted by a secure software

50

downloader function, such as service downloader **1663** as shown in FIG. **3**. In some embodiments, a secure software download embodiment also uses a secure non-volatile memory. Those of ordinary skill in the art will also appreciate that all memory can be on-chip, off-chip, on-board, and/or off-board.

FIGS. **4A** through **4C** illustrates a functional diagram for providing quality of service (QoS) for device assisted services (DAS) in accordance with some embodiments. In some embodiments, QoS for DAS techniques described herein are implemented using the network architecture shown in FIGS. **4A** through **4C**.

Referring to FIG. **4A**, in some embodiments, QoS functionality is performed at the communications device **100** using service processor **115** as similarly described herein. For example, the service processor **115** determines whether or not a QoS request is authorized (e.g., based on the associated service plan and/or other criteria/measures). If the QoS request is authorized, then the service processor **115** communicates with the base station (BTS) **125** to send the QoS request (e.g., a RAB or multi-RAB reservation request) to the local BTS. The BTS determines whether to accept or deny the QoS request (e.g., based on network capacity, such as using a first come first service QoS/network bandwidth or best effort access policy or other techniques, and/or other criteria/measures). The BTS responds to the QoS request accordingly. If the QoS request is granted, the QoS session can be initiated as similarly described herein. In some embodiments, the service processor **115** also performs various QoS charging functions using various techniques described herein, and the service processor **115** periodically sends QoS charging records or reports to the service controller **122** (e.g., and/or another network element/function). In some embodiments, the service processor **115** and the QoS related functions performed by the service processor **115** are periodically verified using the various techniques described herein.

Referring to FIG. **4B**, FIG. **4B** is similar to FIG. **4A** except that the service controller **122** is also shown to be in communication with the service processor **115** of the communications device **100**, which can provide for the download and periodically updating of the QoS rules and/or other service plan/profile/policy information that can include QoS related information. In some embodiments, the service processor **115** also performs various QoS charging functions using various techniques described herein, and the service processor **115** periodically sends QoS charging records or reports to the service controller **122** (e.g., and/or another network element/function). In some embodiments, the service processor **115** and the QoS related functions performed by the service processor **115** are periodically verified using the various techniques described herein.

Referring to FIG. **4C**, at **410**, the service processor **115** sends a QoS request to the service controller **122** (e.g., the service processor can also (at least in part) determine whether the QoS request is authorized as similarly described with respect to FIG. **4A**). At **420**, the service controller **122** sends the QoS request to the BTS **125** if it is determined that the QoS request is authorized using various techniques described herein and/or whether the BTS **125** has network capacity for the QoS request. For example, the service controller can provide a central policy decision point function for QoS related activities (e.g., based on QoS prioritization, network capacity, and/or other criteria/measures/policies). At **430**, the service controller **122** communicates the response to the QoS request accordingly. At **440**, if the QoS request was approved, the device **100** initiates the QoS

51

session (e.g., using a RAB or multi-RAB reservation) via the BTS 125. In some embodiments, the service processor 115 also performs various QoS charging functions using various techniques described herein, and the service processor 115 periodically sends QoS charging records or reports to the service controller 122 (e.g., and/or another network element/function). In some embodiments, the service processor 115 and the QoS related functions performed by the service processor 115 are periodically verified using the various techniques described herein.

In some embodiments, QoS techniques as described herein are implemented in the device (e.g., using the service processor 115) and one or more other network elements/functions, such as the BTS 125, service controller 125, RAN, SGSN/GGSN/other gateways and/or other network elements/functions, in which various of the QoS related functions can be distributed or allocated to such network elements/functions based on various design/network architecture approaches as will now be apparent to one of ordinary skill in the art, in which QoS related activities and/or functions at the device 100 are verified using various verification techniques described herein.

In some embodiments, the device determines QoS availability by directly querying QoS link reservation equipment in the network (e.g., an access point, such as the BTS 125). In some embodiments, the device determines QoS availability based on an intermediate network function that coordinates QoS requests with one or more network QoS link resources. In some embodiments, the device requests a QoS reservation in advance of QoS link establishment with one or more QoS network link resources. In some embodiments, in response to a QoS request, a QoS channel is reported as available only if/after it is determined that the necessary one or more QoS links required to create the QoS channel are available, and, for example, the QoS channel can then be reserved based on a confirmation or automatically be reserved in response to the QoS request.

FIG. 5 illustrates a functional diagram for generating a QoS activity map for quality of service (QoS) for device assisted services (DAS) in accordance with some embodiments. In particular, FIG. 5 illustrates techniques for mapping a service plan or a set of service plan policies/rules for QoS 510 to a set of QoS activity rules 530. As shown, a set of QoS rules/QoS related device state information 510 (e.g., a set of associated service plan, service plan usage, other state such as network capacity or forecasted demand or time of day/day of week, activity usage, QoS level, and/or user preferences) is mapped using a QoS mapping function to a set of QoS activity rules 530 using various techniques described herein. At 530, activity rules (e.g., activity policy rules instructions) 530 are determined using the mapping function 520. In some embodiments, DAS for network capacity controlled services techniques can similarly be implemented using the techniques described with respect to FIG. 5 (e.g., for generating and implementing a network capacity controlled services activity map).

In some embodiments, the service plan includes a list of activity policies, and each activity policy in the service plan specifies how the activity policy is modified by rules state information. In some embodiments, each activity policy then becomes the instruction for the engine (e.g., QoS mapping function 520) that maps the activity policy to QoS activity rules 530. In some embodiments, service controller 122 downloads QoS mapping function 520, which is implemented by service processor 115.

In some embodiments, the service processor determines (e.g., and classifies) application/service usage activity

52

demand with or without granular application/service usage activity (e.g., depending on various user/service plan/service provider/network/legal and/or other privacy restrictions and/or any other related requirements or settings). For example, policies (e.g., service policy settings and/or service profile settings) can be downloaded to provide such application/service usage activity monitoring rules and a QoS activity map for assigning such monitored activities to various QoS classes or priorities, and, in some embodiments, such monitoring and the QoS activity map can also be implemented using various verification techniques described herein (e.g., periodically audited, tested, compared with network service usage information). In some embodiments, the QoS activity map is based on a service plan, service profile, and/or service policy settings associated with the communications device. In some embodiments, the QoS activity map is based on a device group and/or user group. In some embodiments, the QoS activity map is based on user input (e.g., a user of the communications device can identify QoS classes/service levels for various applications and/or service activities, in response to requests for user input, based on user configurations, user defined rules (e.g., to eliminate or mitigate privacy and/or net neutrality concerns/issues), and/or confirmed monitored user behavior QoS related patterns or preferences). In some embodiments, the QoS activity map includes mappings/associations based on one or more of the following: a user preference for a given destination, destination class, application, application class (e.g., by application class instead of with respect to a specific application can also eliminate or mitigate privacy and/or net neutrality concerns/issues), flow, traffic or flow class, time period, time of day, location, network busy state (e.g., provide QoS when you can, then charge more when busy, notify user of busy state), device type, user type, user plan, user group, user standing, partner service, tokens, service type, and/or other criteria or measures.

In some embodiments, various techniques described herein are managed for device 100 for incoming and/or outgoing QoS requests. In some embodiments, as shown in FIG. 6, QoS for DAS includes establishing an end to end coordinated QoS service channel control.

FIG. 6 illustrates a functional diagram for quality of service (QoS) for device assisted services for an end to end coordinated QoS service channel control in accordance with some embodiments. As shown in FIG. 6, a wireless communications device 100A includes a service processor 115A in secure communication with service controller 122A. A wireless communications device 100B includes a service processor 115B in secure communication with service controller 122B. In some embodiments, when, for example, device 100A initiates a QoS request for a QoS class session in communication with device 100B (e.g., a VOIP call or another application service requiring or possibly using a QoS class/level session, such as a conversational or other QoS type of class/level), as sequence of actions are performed using service controller 122A and service controller 122B to facilitate/setup an end to end coordinated QoS service channel control. In some embodiments, as similarly described herein, assuming that service processor 115A and service controller 122A determine that the QoS request from device 100A is authorized for that device, then the service controller 122A contacts registry 650 (e.g., a device registry, such as an HLR, mobile services center, or other central database or registry including, for example, service controller mappings by device/IP address/other) to determine the service controller associated with/responsible for managing QoS/service control for device 100B. The registry 650

53

provides the service controller 122B information (e.g., IP address/other address) based on this lookup determination. In some embodiments, service controller 122A then initiates the QoS request with service controller 122B to determine if the device 100B is authorized and/or available for the QoS session requested by device 100A. In some embodiments, service controllers 122A/B communicate with BTSs 125A/B to determine whether the QoS request can be facilitated (e.g., based on network capacity) as similarly described herein. In some embodiments, the service controllers 122A and 122B provide the central QoS coordination function and can request appropriate QoS channels directly from the respective local BTSs. In some embodiments, the service controllers 122A and 122B also communicate with one or more of the following network elements/functions as shown in FIG. 6 in order to facilitate an end to end coordinated QoS service channel control: RAN 610/670, Core Network 620/660, and IPX network 630. In some embodiments, service controllers 122A and 122B communicate with various necessary network elements for provisioning to facilitate session provisioning through the carrier core network as similarly discussed above. In some embodiments, service controllers 122A and 122B communicate with various necessary network elements for provisioning to facilitate session provisioning through the IPX network as similarly discussed above. As will be apparent to one of ordinary skill in the art, QoS for DAS techniques as described herein can be similarly implemented using these or similar techniques to various other network architectures.

FIG. 7 illustrates a flow diagram for quality of service (QoS) for device assisted services (DAS) in accordance with some embodiments. At 702, the process begins. At 704, QoS rules are received or determined (e.g., a service processor receives or requests the QoS rules, which may be included in service plan, service profile, and/or service policy settings associated with the communications device). In some embodiments, the QoS rules are verified using various techniques as described herein (e.g., periodically updated, replaced, downloaded, obfuscated, and/or tested using by a service controller and/or using other verification techniques). In some embodiments, a QoS API is also used by various applications to initiate a QoS request, as described herein with respect to various embodiments. In some embodiments, the QoS rules are implemented in the form of a QoS activity map in accordance with various embodiments described herein. At 706, the communications device's standing for QoS is determined using various techniques described herein (e.g., based on the service plan, service profile, service policy settings, QoS rules, based on QoS class, current service usage, current billing standing, and/or any other criteria/measure). In some embodiments, in addition to verifying the device/user standing for the QoS request, whether the device is following or in compliance with an assigned QoS reservation request policy is also verified using various techniques described herein. If the device is determined to not be eligible for QoS, then at 708, the device User Interface (UI) provides information concerning the denial/ineligibility for QoS session(s) (e.g., denial/ineligibility explanation and/or options for providing for one or more QoS options, such as a service plan upgrade or payment for a certain/set of/period of time for QoS session(s) access). If the device is determined to be eligible for QoS, then at 710, QoS availability is determined (e.g., based on network capacity, which may be determined at the device, via communication with the service controller, via communication with the BTS, and/or any combination thereof, using the various techniques described herein). If

54

QoS is determined to not be available, then at 712, the UI provides information and/or options concerning the QoS availability (e.g., unavailability explanation and/or options for providing for one or more QoS options, such as a service plan upgrade or payment for a certain/set of/period of time for QoS session(s) access). If QoS is determined to be available, then at 714, a request for network resources for the QoS session is sent to one or more network resources (e.g., service controller, BTS, gateway, core/transport network, IPX/GRX networks, and/or other network elements/functions/resources). At 716, a confirmation of the approved QoS session is received to close the loop for the QoS for DAS (e.g., a QoS schedule is received that provides the QoS session confirmation information, such as a scheduled RAB/multi-RAB and/or other reserved network resource(s) by schedule/other criteria). At 718, one or more verification techniques are performed to verify the QoS for DAS implementation on the device using various verification techniques described herein (e.g., comparing QoS service usage reports from a network source with the associated device policy; comparing QoS service usage reports from a network source with the QoS service usage reports from the device, and/or using other verification techniques as similarly described herein). At 720, the process is completed.

FIGS. 8A through 8C each illustrate another flow diagram for quality of service (QoS) for device assisted services (DAS) in accordance with some embodiments. FIG. 8A illustrates another flow diagram for quality of service (QoS) for device assisted services (DAS) in accordance with some embodiments. At 802, the process begins. In some embodiments, the QoS policies are implemented on the device (e.g., service processor collects/receives an associated service plan that defines/specifies basic policies for QoS, which can include a QoS activity map, which, for example, maps QoS classes based on application, service usage, flow type, destination, time of day, network capacity, and/or other criteria/measures, as similarly described herein). In some embodiments, a QoS API is also used by various applications to initiate a QoS request, as described herein with respect to various embodiments. In some embodiments, the QoS rules are implemented in the form of a verified QoS activity map in accordance with various embodiments described herein. At 804, a QoS request is determined (e.g., by QoS class for a particular associated service/application). In some embodiments, the QoS request is determined at least in part by using the QoS activity map using various techniques described herein, for example, based on service/application usage monitoring on the device (e.g., by the service processor service usage monitoring agent). In some embodiments, the QoS request is determined based on the QoS API. In some embodiments, the QoS request is determined to be associated with an outgoing connection or an incoming connection. At 806, whether the QoS request is authorized is determined (e.g., whether the QoS request supported by the service plan, sufficient charging credit exists for this QoS request, and/or other criteria/measures). If not, then at 808, the UI provides a responsive notification and/or option as similarly described herein. If the QoS request is approved, then at 810, a request for network resources for the QoS session is sent to one or more network resources (e.g., service controller, BTS, gateway, core/transport network, IPX/GRX networks, a/another service controller in communication with another communications device such as for setting up a conversational class QoS connection with the other communications device, and/or other network elements/functions/resources). If the device is determined to be eligible for QoS, then at 810, QoS avail-

55

ability is determined (e.g., based on network capacity, which may be determined at the device, via communication with the service controller, via communication with the BTS or another network element/function, and/or any combination thereof, using the various techniques described herein). If QoS is determined to not be available, then at **812**, the UI provides information and/or options concerning the QoS availability (e.g., unavailability explanation and/or options for providing for one or more QoS options, such as a service plan upgrade or payment for a certain/set of/period of time for QoS session(s) access). If QoS is determined to be available, then at **814**, a request for network resources for the QoS session is sent to one or more network resources (e.g., service controller, BTS, gateway, core/transport network, IPX/GRX networks, and/or other network elements/functions/resources, to setup, for example, a QoS end to end connection—coordinate all resources end to end for the approved and verified QoS flow). At **816**, a confirmation of the approved QoS session is received to close the loop for the QoS for DAS (e.g., a QoS schedule is received that provides the QoS session confirmation information, such as a scheduled RAB/multi-RAB and/or other reserved network resource(s) by schedule/other criteria). At **818**, a QoS router is executed/performed on the communications device to assist in implementing QoS for DAS using various verification techniques described herein (e.g., to perform QoS queuing, throttling, and/or other QoS router related functions as described herein). At **820**, verified QoS charging is performed (e.g., at least in part) on the device using various techniques described herein (e.g., using the service processor, such as the charging/service usage monitoring and/or other agents as described herein). In some embodiments, QoS charging records and/or reports are provided to one or more network elements for managing QoS billing and/or other QoS management/billing related service control functions (e.g., to the service controller and/or the billing interface or billing server). In some embodiments, QoS for DAS also facilitates reestablishing the QoS session/connection/channel/stream if the QoS session/connection/channel/stream is lost or goes down, using similar techniques to those described herein as would be apparent to one of ordinary skill in the art. At **822**, the process is completed. In some embodiments, the QoS provisioning channel is closed when the device session is over to, for example, free up various resources.

FIG. 8B illustrates another flow diagram for quality of service (QoS) for device assisted services (DAS) in accordance with some embodiments. In some embodiments, QoS for DAS includes identifying the QoS requirements (e.g., QoS level or QoS class) for a service activity. At **824**, the process begins. In some embodiments, the QoS policies are implemented on the device (e.g., service processor collects/receives an associated service plan that defines/specifies basic policies for QoS, which can include a QoS activity map, which, for example, maps QoS classes based on application, service usage, flow type, destination, time of day, network capacity, and/or other criteria/measures, as similarly described herein). In some embodiments, the QoS rules are implemented in the form of a verified QoS activity map in accordance with various embodiments described herein. At **826**, the device monitors device activity, such as service/application usage activities. In some embodiments, the device detects the relevant activities based on various service usage monitoring techniques described herein. At **828**, a QoS request is determined, for example, using various techniques described herein. At **830**, a QoS level is determined based on the application and/or various device moni-

56

tored service usage/application activities associated with the QoS request using various techniques described herein. For example, the QoS level can be determined using the QoS activity map, which provides a QoS policy defined by a table associating various QoS levels with a variety of activities that include various device monitored service usage/application activities. In some embodiments, the QoS activity map includes QoS level mappings based on one or more of the following: application, destination/source, traffic type, connection type, content type, time of day/day of week, network capacity, activity usage, service plan selection, current standing, user class, device class, home/roaming, network capabilities, and/or other criteria/measures as similarly described herein. In some embodiments, at **832**, if the QoS level cannot be determined and/or in order to confirm a QoS level or selection among multiple potential appropriate/approved QoS levels, the UI presents options for a user to select the QoS level. At **834**, the QoS request is initiated for the determined QoS level (e.g., QoS class and/or priorities). At **836**, the process is completed.

FIG. 8C illustrates another flow diagram for quality of service (QoS) for device assisted services (DAS) in accordance with some embodiments. In some embodiments, QoS for DAS includes determining whether the network should grant the QoS request for a given device activity. At **842**, the process begins. At **844**, QoS request is determined. At **846**, the communications device's standing for QoS is determined using various techniques described herein (e.g., a service processor in combination with a service controller or based on a communication for authorization of the QoS request sent to the service controller determines whether the QoS request is authorized, which can be based on the service plan, service profile, service policy settings, QoS rules, based on QoS class, current service usage, current billing standing, and/or any other criteria/measure). If the device is determined to not be eligible for QoS, then at **848**, the device User Interface (UI) provides information concerning the denial/ineligibility for QoS session(s) (e.g., denial/ineligibility explanation and/or options for providing for one or more QoS options, such as a service plan upgrade or payment for a certain/set of/period of time for QoS session(s) access). If the device is determined to be eligible for QoS, then at **850**, QoS availability is determined (e.g., based on network capacity, which may be determined at the device, via communication with the service controller, via communication with the BTS or another network element/function, and/or any combination thereof, using the various techniques described herein). If QoS is determined to not be available, then at **852**, the UI provides information and/or options concerning the QoS availability (e.g., unavailability explanation and/or options for providing for one or more QoS options, such as a service plan upgrade or payment for a certain/set of/period of time for QoS session(s) access). If QoS is determined to be available, then at **854**, a request for network resources for the QoS session is sent to one or more network resources (e.g., service controller, BTS, gateway, core/transport network, IPX/GRX networks, and/or other network elements/functions/resources can be queried directly and/or a centralized QoS resource/network function/element/database can be queried for determining such network resources and coordinating such scheduling). At **856**, a confirmation of the approved QoS session is received to close the loop for the QoS for DAS (e.g., a QoS schedule is received that provides the QoS session confirmation information, such as a scheduled RAB/multi-RAB and/or other reserved network resource(s) by schedule/other criteria). At **858**, a QoS router is performed. In some embodiments, the

57

QoS router is performed on the device (e.g., service processor), on a network element/function (e.g., service controller), and/or in combinations thereof. In some embodiments, the QoS router prioritizes multiple QoS requests across a given communications device. In some embodiments, the QoS router prioritizes multiple QoS requests across multiple communications devices and/or across multiple BTSs. In some embodiments, the QoS router performs various QoS class degradation, promotion, and/or other throttling related techniques as similarly described herein (e.g., based on session priority, network capacity, workload balancing, QoS priority rules, and/or other criteria/measures/rules). At 860, the process is completed.

FIG. 9 illustrates another flow diagram for quality of service (QoS) for device assisted services (DAS) in accordance with some embodiments. In some embodiments, QoS for DAS includes QoS session provision for a service activity. At 902, the process begins. At 904, a new QoS session is granted and/or confirmed. At 906, a device service processor (e.g., policy decision point (PDP) agent, also referred to herein as a policy control agent) maps the QoS session grant to a QoS monitoring policy (e.g., based on a service controller provided QoS related policy, based on a service plan associated with the device, user, device/user group, and/or other criteria/measures, as similarly described herein). At 908, the QoS monitoring policy provides commands/instructions to a policy enforcement point (PEP) (e.g., PEP agent, also referred to herein as a policy implementation agent) for managing/enforcing the new QoS priorities/sessions. At 910, the PEP determines whether to allow, block, throttle, and/or queue priority (e.g., and/or otherwise control using various traffic control related techniques) a session based on the QoS monitoring policy. At 912, the process is completed.

FIG. 10 illustrates another flow diagram for quality of service (QoS) for device assisted services (DAS) in accordance with some embodiments. In some embodiments, Radio Access Bearer (RAB) support is available, and the following process is performed in accordance with some embodiments. At 1002, the process begins. At 1004, the device service processor detects a QoS request or QoS need (e.g., a QoS API request, a QoS request or need/benefit of QoS session based on service usage monitoring, such as by application and/or another service usage measure/activity). At 1006, the service processor and/or the service processor in communication with the service controller determines if the service plan allows/supports the requested QoS. If not, then at 1008, a UI event is generated (e.g., notifying the device user that such QoS/QoS level/class is not available, and potentially offering a QoS/service plan upgrade/purchase for that QoS/QoS level/class). At 1010, the service processor communicates the QoS request to the service controller (e.g., using a secure service control link or secure communication channel, as similarly described herein) to request the QoS level/class. At 1012, the service controller determines whether network resources are available using various techniques as described herein. In some embodiments, network capacity is determined using various techniques, such as local device measurements; dedicated local device measurement reports; BTS reports; other network element reports; by assessing, for example, a combination of one or more of available bandwidth, traffic delay or latency, available QoS level, variability in available bandwidth, variability in latency, and/or variability in available QoS level; and/or other techniques as described herein. At 1014, the service controller responds to the QoS request (e.g., grants or denies the QoS request). In some embodiments,

58

another UI event is generated if the QoS request is denied as similarly described herein. At 1016 (assuming the QoS request is granted), the device requests a QoS channel from the BTS. In some embodiments, the request includes a QoS request authorization code received from the service controller. In some embodiments, the service controller provides a notification of the QoS request approval for the communications device to the BTS, so that the BTS can verify the approval of the QoS request. In some embodiments, the BTS confirms the device QoS channel request directly with the service controller. For example, various other techniques for verifying the QoS channel request can also be used as similarly described herein and as would be apparent to one of ordinary skill in the art. In some embodiments, the device service processor and/or service controller provides QoS related reports informing the BTS of how many QoS channels (e.g., RABs) to provision and how many best effort resources to provision based on device demand projections. At 1018 (assuming the QoS channel request is verified), the QoS session is initiated based on an allocated RAB or multi-RAB reservation received from the BTS (e.g., and/or other network elements as similarly described herein). At 1020, the process is completed.

FIG. 11 illustrates another flow diagram for quality of service (QoS) for device assisted services (DAS) in accordance with some embodiments. In some embodiments, RAB support is not available, and the following process is performed in accordance with some embodiments. At 1102, the process begins. At 1104, the device service processor detects a QoS request or QoS need (e.g., a QoS API request, a QoS request or need/benefit of QoS session based on service usage monitoring, such as by application, or other service usage measure/activity). At 1106, the service processor and/or the service processor in communication with the service controller determines if the service plan allows/supports the requested QoS. If not, then at 1108, a UI event is generated (e.g., notifying the device user that such QoS/QoS level/class is not available, and potentially offering a QoS/service plan upgrade/purchase for that QoS/QoS level/class). At 1110, the service processor communicates the QoS request to the service controller (e.g., using a secure service control link or secure communication channel, as similarly described herein) to request the QoS level/class. At 1112, the service controller determines whether network resources are available using various techniques as described herein. In some embodiments, network capacity is determined using various techniques, such as local device measurements, BTS reports, other network element reports, and/or other techniques as described herein. In some embodiments, the service controller throttles other devices on the link so that the requested QoS level can be achieved (e.g., as RAB support is not available). In some embodiments, the service controller time slots traffic from the device end in synchronization with a BTS clock or absolute clock to facilitate the requested QoS level and to achieve necessary network capacity to support/facilitate the requested QoS level (e.g., minimizing jitter/inter-packet delay variation) based on current/forecasted network capacity on the link. At 1114, the service controller responds to the QoS request (e.g., grants or denies the QoS request). In some embodiments, another UI event is generated if the QoS request is denied as similarly described herein. At 1116 (assuming the QoS request is granted), the device initiates the QoS session. At 1118, the device service processor and/or the device service processor in secure communication with the service controller monitors and verifies the QoS session using various monitoring and verification techniques described herein

59

(e.g., checks CDRs to determine if the QoS channel is properly implemented by the device). In some embodiments, a UI event is generated to notify the device user if there are potential problems with the QoS session implementation, to periodically inform the user of QoS charging, and/or other events/information related to QoS activities. At 1120, the process is completed.

FIG. 12 illustrates a device stack for providing various service usage measurement techniques in accordance with some embodiments. FIG. 12 illustrates a device stack providing various service usage measurement from various points in the networking stack for a service monitor agent (e.g., for monitoring QoS related activities and/or for monitoring network capacity controlled services as described herein), a billing agent, and an access control integrity agent to assist in verifying the service usage measures, QoS related activities and functions, and billing reports in accordance with some embodiments. As shown in FIG. 12, several service agents take part in data path operations to achieve various data path improvements, and, for example, several other service agents can manage the policy settings for the data path service, implement billing for the data path service, manage one or more modem selection and settings for access network connection, interface with the user and/or provide service policy implementation verification. Additionally, in some embodiments, several agents perform functions to assist in verifying that the service control or monitoring policies intended to be in place are properly implemented, the service control or monitoring policies are being properly adhered to, that the service processor or one or more service agents are operating properly, to prevent unintended errors in policy implementation or control, and/or to prevent/detect tampering with the service policies or control. As shown, the service measurement points labeled I through VI represent various service measurement points for service monitor agent 1696 and/or other agents to perform various service monitoring activities. Each of these measurement points can have a useful purpose in various embodiments described herein. For example, each of the traffic measurement points that is employed in a given design can be used by a monitoring agent to track application layer traffic through the communication stack to assist policy implementation functions, such as the policy implementation driver/agent 1690 (e.g., policy enforcement point driver/agent), or in some embodiments the modem firewall agent 1655 or the application interface agent, in making a determination regarding the traffic parameters or type once the traffic is farther down in the communication stack where it is sometimes difficult or impossible to make a complete determination of traffic parameters. The particular locations for the measurement points provided in these figures are intended as instructional examples, and other measurement points can be used for different embodiments, as will be apparent to one of ordinary skill in the art in view of the embodiments described herein. Generally, in some embodiments, one or more measurement points within the device can be used to assist in service control verification and/or device or service troubleshooting.

In some embodiments, the service monitor agent and/or other agents implement virtual traffic tagging by tracking or tracing packet flows through the various communication stack formatting, processing and encryption steps, and providing the virtual tag information to the various agents that monitor, control, shape, throttle or otherwise observe, manipulate or modify the traffic. This tagging approach is referred to herein as virtual tagging, because there is not a literal data flow, traffic flow or packet tag that is attached to

60

flows or packets, and the book-keeping to tag the packet is done through tracking or tracing the flow or packet through the stack instead. In some embodiments, the application interface and/or other agents identify a traffic flow, associate it with a service usage activity and cause a literal tag to be attached to the traffic or packets associated with the activity. This tagging approach is referred to herein as literal tagging. There are various advantages with both the virtual tagging and the literal tagging approaches. For example, it can be preferable in some embodiments to reduce the inter-agent communication required to track or trace a packet through the stack processing by assigning a literal tag so that each flow or packet has its own activity association embedded in the data. As another example, it can be preferable in some embodiments to re-use portions of standard communication stack software or components, enhancing the verifiable traffic control or service control capabilities of the standard stack by inserting additional processing steps associated with the various service agents and monitoring points rather than re-writing the entire stack to correctly process literal tagging information, and in such cases, a virtual tagging scheme may be desired. As yet another example, some standard communication stacks provide for unused, unspecified or otherwise available bit fields in a packet frame or flow, and these unused, unspecified or otherwise available bit fields can be used to literally tag traffic without the need to re-write all of the standard communication stack software, with only the portions of the stack that are added to enhance the verifiable traffic control or service control capabilities of the standard stack needing to decode and use the literal tagging information encapsulated in the available bit fields. In the case of literal tagging, in some embodiments, the tags are removed prior to passing the packets or flows to the network or to the applications utilizing the stack. In some embodiments, the manner in which the virtual or literal tagging is implemented can be developed into a communication standard specification so that various device or service product developers can independently develop the communication stack and/or service processor hardware and/or software in a manner that is compatible with the service controller specifications and the products of other device or service product developers.

It will be appreciated that although the implementation/use of any or all of the measurement points illustrated in FIG. 12 is not required to have an effective implementation, such as was similarly shown with respect to various embodiments described herein, various embodiments can benefit from these and/or similar measurement points. It will also be appreciated that the exact measurement points can be moved to different locations in the traffic processing stack, just as the various embodiments described herein can have the agents affecting policy implementation moved to different points in the traffic processing stack while still maintaining effective operation. In some embodiments, one or more measurement points are provided deeper in the modem stack where, for example, it is more difficult to circumvent and can be more difficult to access for tampering purposes if the modem is designed with the proper software and/or hardware security to protect the integrity of the modem stack and measurement point(s).

Referring to FIG. 12, describing the device communications stack from the bottom to the top of the stack as shown, the device communications stack provides a communication layer for each of the modems of the device at the bottom of the device communications stack. Example measurement point VI resides within or just above the modem driver layer. For example, the modem driver performs modem bus com-

61

munications, data protocol translations, modem control and configuration to interface the networking stack traffic to the modem. As shown, measurement point VI is common to all modem drivers and modems, and it is advantageous for certain embodiments to differentiate the traffic or service activity taking place through one modem from that of one or more of the other modems. In some embodiments, measurement point VI, or another measurement point, is located over, within or below one or more of the individual modem drivers. The respective modem buses for each modem reside between example measurement points V and VI. In the next higher layer, a modem selection & control layer for multi-mode device based communication is provided. In some embodiments, this layer is controlled by a network decision policy that selects the most desirable network modem for some or all of the data traffic, and when the most desirable network is not available the policy reverts to the next most desirable network until a connection is established provided that one of the networks is available. In some embodiments, certain network traffic, such as verification, control, redundant or secure traffic, is routed to one of the networks even when some or all of the data traffic is routed to another network. This dual routing capability provides for a variety of enhanced security, enhanced reliability or enhanced manageability devices, services or applications. In the next higher layer, a modem firewall is provided. For example, the modem firewall provides for traditional firewall functions, but unlike traditional firewalls, in order to rely on the firewall for verifiable service usage control, such as access control and security protection from unwanted networking traffic or applications, the various service verification techniques and agents described herein are added to the firewall function to verify compliance with service policy and prevent/detect tampering of the service controls. In some embodiments, the modem firewall is implemented farther up the stack, possibly in combination with other layers as indicated in other Figures and described herein. In some embodiments, a dedicated firewall function or layer is provided that is independent of the other processing layers, such as the policy implementation layer, the packet forwarding layer and/or the application layer. In some embodiments, the modem firewall is implemented farther down the stack, such as within the modem drivers, below the modem drivers, or in the modem itself. Example measurement point IV resides between the modem firewall layer and an IP queuing and routing layer (e.g., QoS IP queuing and routing layer and/or a network capacity controlled services queuing and routing layer). As shown, an IP queuing and routing layer is separate from the policy implementation layer where the policy implementation agent implements a portion of the traffic control and/or service usage control policies. As described herein, in some embodiments, these functions are separated so that a standard network stack function can be used for QoS IP queuing and routing and/or for network capacity controlled services queuing and routing, and the modifications necessary to implement the policy implementation agent functions can be provided in a new layer inserted into the standard stack. In some embodiments, the IP queuing and routing layer is combined with the traffic or service usage control layer. For example, a combined routing and policy implementation layer embodiment can also be used with the other embodiments, such as shown in FIG. 12. Measurement point III resides between the IP queuing and routing layer and a policy implementation agent layer. Measurement point II resides between the policy implementation agent layer and the transport layer, including TCP, UDP, and other IP as shown. The session layer resides above

62

the transport layer, which is shown as a socket assignment and session management (e.g., basic TCP setup, TLS/SSL) layer. The network services API (e.g., HTTP, HTTPS, FTP (File Transfer Protocol), SMTP (Simple Mail Transfer Protocol), POP3, DNS) resides above the session layer. Measurement point I resides between the network services API layer and an application layer, shown as application service interface agent in the device communications stack of FIG. 12.

As shown in FIG. 12, the application service interface layer (e.g., QoS application service interface layer and/or network capacity controlled services interface layer) is above the standard networking stack API and, in some embodiments, its function is to monitor and in some cases intercept and process the traffic between the applications and the standard networking stack API. In some embodiments, the application service interface layer identifies application traffic flows before the application traffic flows are more difficult or practically impossible to identify farther down in the stack. In some embodiments, the application service interface layer in this way assists application layer tagging in both the virtual and literal tagging cases. In the case of upstream traffic, the application layer tagging is straight forward, because the traffic originates at the application layer. In some downstream embodiments, where the traffic or service activity classification relies on traffic attributes that are readily obtainable, such as source address or URL, application socket address, IP destination address, time of day or any other readily obtained parameter, the traffic type can be identified and tagged for processing by the firewall agent or another agent as it initially arrives. In other embodiments, as described herein, in the downstream case, the solution is generally more sophisticated when a traffic parameter that is needed to classify the manner in which the traffic flow is to be controlled or throttled is not readily available at the lower levels of the stack, such as association with an aspect of an application, type of content, something contained within TLS, IPSEC or other secure format, or other information associated with the traffic. Accordingly, in some embodiments the networking stack identifies the traffic flow before it is fully characterized, categorized or associated with a service activity, and then passes the traffic through to the application interface layer where the final classification is completed. In such embodiments, the application interface layer then communicates the traffic flow ID with the proper classification so that after an initial short traffic burst or time period the policy implementation agents can properly control the traffic. In some embodiments, there is also a policy for tagging and setting service control policies for traffic that cannot be fully identified with all sources of tagging including application layer tagging.

As shown in FIG. 12, a service monitor agent, which is also in communication with the agent communication bus 1630, communicates with various layers of the device communications stack. For example, the service monitor agent, performs monitoring at each of measurement points I through VI, receiving information including application information, service usage and other service related information, and assignment information. An access control integrity agent is in communication with the service monitor agent via the agent communications bus 1630, as also shown.

FIG. 13 illustrates another device stack for providing various service usage measurement techniques in accordance with some embodiments. FIG. 13 illustrates an embodiment similar to FIG. 12 in which some of the service processor is implemented on the modem and some of the

63

service processor is implemented on the device application processor in accordance with some embodiments. In some embodiments, a portion of the service processor is implemented on the modem (e.g., on modem module hardware or modem chipset) and a portion of the service processor is implemented on the device application processor subsystem. It will be apparent to one of ordinary skill in the art that variations of the embodiment depicted in FIG. 13 are possible where more or less of the service processor functionality is moved onto the modem subsystem or onto the device application processor subsystem. For example, such embodiments similar to that depicted in FIG. 13 can be motivated by the advantages of including some or all of the service processor network communication stack processing and/or some or all of the other service agent functions on the modem subsystem (e.g., and such an approach can be applied to one or more modems). For example, the service processor can be distributed as a standard feature set contained in a modem chipset hardware or software package or modem module hardware or software package, and such a configuration can provide for easier adoption or development by device OEMs, a higher level of differentiation for the chipset or modem module manufacturer, higher levels of performance or service usage control implementation integrity or security, specification or interoperability standardization, and/or other benefits.

Referring to FIG. 13, describing the device communications stack from the bottom to the top of the stack as shown, the device communications stack provides a communication layer for modem MAC/PHY layer at the bottom of the device communications stack. Measurement point IV resides above the modem MAC/PHY layer. The modem firewall layer resides between measurement points IV and III. In the next higher layer, the policy implementation agent is provided, in which the policy implementation agent is implemented on the modem (e.g., on modem hardware). Measurement point II resides between the policy implementation agent and the modem driver layer, which is then shown below a modem bus layer. The next higher layer is shown as the IP queuing and routing layer, followed by the transport layer, including TCP, UDP, and other IP as shown. The session layer resides above the transport layer, which is shown as a socket assignment and session management (e.g., basic TCP setup, TLS/SSL) layer. The network services API (e.g., HTTP, HTTPS, FTP (File Transfer Protocol), SMTP (Simple Mail Transfer Protocol), POP3, DNS) resides above the session layer. Measurement point I resides between the network services API layer and an application layer, shown as application service interface agent in the device communications stack of FIG. 13.

Additional Embodiments of DAS for Protecting Network Capacity

In some embodiments, DAS for protecting network capacity includes classifying a service activity as a network capacity controlled service and implementing a network capacity controlled services policy. In some embodiments, DAS for protecting network capacity includes device assisted/based techniques for classifying a service activity as a network capacity controlled service and/or implementing a network capacity controlled services policy. In some embodiments, DAS for protecting network capacity includes network assisted/based techniques (e.g., implemented on a network element/function, such as a service controller, a DPI gateway, a BTS/BTSC, etc., or a combination of network elements) for classifying a service activity as a network capacity controlled service and/or implementing a network capacity controlled services policy. In some embodiments,

64

DAS for protecting network capacity includes providing a network access API or an emulated or virtual network access API (e.g., such an API can provide network busy state information and/or other criteria/measures and/or provide a mechanism for allowing, denying, delaying, and/or otherwise controlling network access). In some embodiments, DAS for protecting network capacity includes implementing a service plan that includes a network capacity controlled services policy (e.g., for differential network access control and/or differential charging for network capacity controlled services, which can also be based on a network busy state and/or other criteria/measures).

In some embodiments, DAS for protecting network capacity techniques also provide improved user privacy and facilitate network neutrality requirements. In contrast, network based techniques (e.g., DPI based techniques) can give rise to user privacy and network neutrality concerns and problems as discussed above. In some embodiments, DAS for protecting network capacity techniques include allowing a user to specify (e.g., permit or not permit) whether the network is aware of the user's Internet behavior (e.g., using UI input). In some embodiments, DAS for protecting network capacity techniques include allowing a user to select how they want their traffic usage and service plan costs to be managed.

FIG. 14 illustrates a flow diagram for device assisted services (DAS) for protecting network capacity in accordance with some embodiments. At 1402, the process begins. At 1404, monitoring a network service usage activity of a device in network communication (e.g., wireless network communication) is performed. At 1406, whether the monitored network service usage activity is a network capacity controlled service is determined. At 1408 (the monitored network service usage activity was determined not to be a network capacity controlled service), the network service usage activity is not classified for differential network access control. At 1410, (the monitored network service usage activity was determined to be a network capacity controlled service), the network service usage activity is classified (e.g., into one or more network capacity controlled services) for differential network access control for protecting network capacity. In some embodiments, classifying the network service usage activity includes classifying the network service usage activity into one or more of a plurality of classification categories for differential network access control for protecting network capacity (e.g., one or more network capacity controlled service classifications and/or a priority state classification, such as a background services classification and/or a background priority state classification). At 1412, associating the network service usage activity with a network capacity controlled services control policy based on a classification of the network service usage activity to facilitate differential network access control for protecting network capacity is performed. At 1414, implementing differential network access control for protecting network capacity by implementing different traffic controls for all or some of the network service usage activities (e.g., based on a network busy state or another criteria/measure) is performed. At 1416, the process is completed.

FIG. 15 illustrates another flow diagram for device assisted services (DAS) for protecting network capacity in accordance with some embodiments. At 1502, the process begins. At 1504, monitoring network service usage activities of a device in network communication is performed. At 1506, monitored network service usage activity of the device is reported (e.g., to a network element/function). At 1508, a statistical analysis of a reported network service

65

usage activities across a plurality of devices is performed (e.g., by a network element/function). At 1510, the device receives a network service usage activity classification list (e.g., a network capacity controlled services list, which can be generated, for example, based on the monitored network service usage activities and the statistical analysis as well as other criteria/measures, including, for example, a service plan and/or a network busy state) from the network element. At 1512, implementing differential network access control based on the network service usage activity classification list for protecting network capacity is performed. At 1514, the process is completed. In some embodiments, DAS for protecting network capacity further includes associating the network service usage activity with a network service usage control policy (e.g., a network capacity controlled services policy) based on a classification of the network service usage activity to facilitate differential network access control for protecting network capacity. In some embodiments, DAS for protecting network capacity further includes differentially controlling the network service usage activity (e.g., network capacity controlled service) based on the service usage activity classification list.

FIG. 16 illustrates another flow diagram for device assisted services (DAS) for protecting network capacity in accordance with some embodiments. At 1622, the process begins. At 1624, a first report of network service usage activity of a first device is received (e.g., at a network element/function) from the first device. At 1626, a second report of network service usage activity of a second device (e.g., at a network element/function) from the second device is received. At 1628, a statistical analysis of a plurality of reported service usage activities across a plurality of devices, including the first device and the second device, is performed (e.g., by a network element/function). At 1630, a network service usage activity classification list (e.g., a network capacity controlled services classification list) is sent to the first device (e.g., from a network element/function) for classifying network service usage activities (e.g., network capacity controlled services) based on the network service usage activity classification list for differential network access control for protecting network capacity. At 1632, a network service usage activity classification list is sent to the second device (e.g., from a network element/function) for classifying network service usage activities based on the network service usage activity classification list for differential network access control for protecting network capacity. At 1634, the process is completed. In some embodiments, DAS for protecting network capacity further includes associating the network service usage activity with a service usage control policy (e.g., a network capacity controlled services policy) based on a classification of the network service usage activity to facilitate differential network access control for protecting network capacity. In some embodiments, DAS for protecting network capacity further includes differentially controlling the network service usage activity (e.g., network capacity controlled service) based on the service usage activity classification list (e.g., network capacity controlled services classification list). In some embodiments, classifying network service usage activities is based on which network to which the device is connected. In some embodiments, the network service usage control policy is based on which network to which the device is connected.

FIG. 17 illustrates another flow diagram for device assisted services (DAS) for protecting network capacity in accordance with some embodiments. At 1702, the process begins. At 1704, monitoring a network service usage activity

66

of a plurality of devices in network communication using network based techniques is performed. At 1706, a statistical analysis of monitored network service usage activities across the plurality of devices is performed. At 1708, a network service usage activity classification list (e.g., a network capacity controlled services classification list) is sent to each of the plurality of devices for classifying network service usage activities (e.g., network capacity controlled services) based on the service usage activity classification list for differential network access control for protecting network capacity. At 1710, the process is completed.

FIG. 18 illustrates another flow diagram for device assisted services (DAS) for protecting network capacity in accordance with some embodiments. At 1802, the process begins. At 1804, monitoring network service usage activities of a device in network communication is performed. At 1806, associating a network service usage activity (e.g., a network capacity controlled service) with a service usage control policy (e.g., a network capacity controlled services policy) based on a classification of the network service usage activity (e.g., a network capacity controlled services classification list) for differential network access control for protecting network capacity is performed. At 1808, a user notification based on the service usage control policy is generated. At 1810, the process is completed.

In some embodiments, the service usage control policy includes a service usage notification policy. In some embodiments, the user notification includes one or more of the following: a notification that the application to be downloaded and/or launched is a network capacity controlled service; a list of one or more service activities (e.g., applications, OS/other software functions/utilities, and/or other functions/utilities as described herein) that have a network capacity controlled services classification; type of service policy in effect for one or more network capacity controlled services; notification that a service activity belongs to a network capacity controlled services class; notification that a service activity that is classified as network capacity controlled service can have the service class changed; notification that if the service class is changed for a service activity the service charges will change; notification that one or more networks are available (e.g., one or more alternative networks and/or network busy state information and/or charging information and/or incentives associated with such networks), a service plan upgrade/downgrade offer/option; and an offer for a service plan that rewards a user that responds to the notification a service plan is lower cost/discounted for responding to notification to use or not to use service activity based on usage level warning notification. In some embodiments, the user notification includes a user preference selection, including one or more of the following: a provision to associate an access policy control with the application (e.g., allow/block, notify of usage, notify of usage at a given threshold, traffic control settings, allow during certain times, allow when network not busy, and/or other policy controls as described herein), an over-ride option for selecting the service usage control policy; a modify option to select the service usage control policy; a select option to select a new service plan (e.g., an option to review and select alternative/new service plan upgrade/downgrade options), and an acknowledgement request (e.g., to confirm/acknowledge receipt of the notification, in which the acknowledgement can be transmitted to a network element/function and/or stored locally for later reference/transmission).

67

In some embodiments, before a given device application, process, function, OS service or other service activity is allowed to start, the intention to start is intercepted by a launch manager, the background service policy set or the network protection service policy set for the service activity is retrieved, and any necessary user notification or service launch control policies are implemented prior to allowing the service activity to launch. In such embodiments, a launch intercept manager may be used to implement this functionality. In some embodiments, this launch intercept manager is provided with a list identifying the service activities (e.g. application identifiers, OS function identifiers, aggregate service activity identifiers, and/or component service activity identifiers) that have a launch control policy in effect. In some embodiments, the list of launch control policies includes blocking or delaying launch of the one or more service activities. In some embodiments, the launch control policy includes a user notification before, during or after the service activity is launched. In some embodiments, the user is informed that a service activity that has a background service control policy in effect or a network protection service control policy in effect is attempting to launch, is about to launch or has launched. In a further set of embodiments, the launch is held up until the user is notified and is allowed to decide if they would like to launch the service activity. In some embodiments, the user notification includes a message that the service activity attempting to launch consumes a large amount of service usage and asks the user if they would like to continue (e.g. "This application consumes a large amount of data, would you like to continue?", "This application consumes data even when you are not using it, would you like to continue?" "This application consumes data while you are roaming which adds cost to your usage bill, would you like to continue?", etc). In some embodiments, the decision on whether or not to launch a service activity is pre-programmed into the list identifying the service activities (e.g. application identifiers, OS function identifiers, aggregate service activity identifiers, and/or component service activity identifiers) that have a launch control policy in effect. In some embodiments a portion of the list is pre-programmed by the user in accordance with user preference for controlling usage of service activities. In some embodiments, a portion of the list is pre-programmed by a network element (e.g. a service controller) in accordance with network background service or network protection service policies specified by a service policy design management system operated by a service provider as described herein. In some embodiments, the policy implementation defined by the list identifying the service activities (e.g. application identifiers, OS function identifiers, aggregate service activity identifiers, and/or component service activity identifiers) that have a launch control policy in effect is verified to ensure that the user or malicious software has not defeated the policy enforcement specified in the list. In some embodiments the list identifying the service activities that have a launch control policy in effect includes launch policies that are a function of one or more of: background service state, network busy state (or performance state or QoS state), type of network the device is connected to, home or roaming connection, time of day or day of week.

In some embodiments, the various design techniques described herein that allow for intercepting a service activity intention to launch, and applying a background service policy set or a network protection service policy set can be designed into the OS itself. For example, the intercept and policy implementation functions can be designed into the

68

activity manager, broadcast intent manger, media service manager, service manager, or other application or service activity management function in the Android OS. One of ordinary skill in the art will recognize that similarly, the various design techniques described herein that allow for intercepting a service activity intention to launch, and applying a background service policy set or a network protection service policy set can be designed into application launch management functions in the iPhone OS, windows mobile OS, windows PC OS, Blackberry OS, Palm OS, and other OS designs.

In some embodiments, the pre-launch user notification information indicates one or more of: typical service usage or cost, or projected service usage or cost for the service activity attempting to launch. In some embodiments, the user sets limitations on access for one or more service activities and once this limit is hit then when the service activities with exceeded limits attempt to launch the user is notified. In some embodiments, the user chooses from a set of service restrictions rather than simply blocking or allowing service activity launch, with example service restrictions including but not limited to: a pre-configured set of restriction policies to chose from (e.g. full access, limited access, highly restricted access or block access), block, throttle, delay, aggregate and hold, limit amount of usage per unit time, cap usage, set limit for additional notification, specify type of network, specify busy state (performance, QoS) or background state, or choose from pre-configured settings options.

In some embodiments, the user notification occurs after the user attempts to download or load an application onto the device (e.g., an application downloaded from the web or an online application store for a smart phone or other wireless/network computing device, such as an Apple iPhone or iPad, or Google Android/Chrome based device). In some embodiments, the user notification occurs after the user attempts to run the service activity or to initiate usage of a cloud based service/application (e.g., Google or Microsoft cloud service based apps). In some embodiments, the user notification occurs after one or more of the following: the service usage activity hits a usage threshold event, the service usage activity attempts a network service usage that satisfies a pre-condition, an update to a network capacity protection service activity classification list or policy set, and a network message is sent to the device triggering the notification. In some embodiments, the user notification provides information on the service usage activity that is possible, typical, or likely for the service usage activity. In some embodiments, the user notification includes a user option for obtaining more information about the service usage of the service activity (e.g., a message that the service usage activity may result in a high service usage and/or that the service usage activity may or will result in a high service usage as compared in some way to a limit of the current service plan) to make informed user preference settings.

In some embodiments, a user notification includes displaying (e.g., and as applicable, allowing users to provide UI input) one or more of the following: current and/or past/historical/logged network service usage activity list, current and/or past/historical/logged network capacity controlled service usage activities, current activity policy settings, current or available networks, service plan options (e.g., for how to treat one or more network capacity controlled service traffic types), selection option(s) to assign a network capacity controlled service activity into a different priority traffic control and/or charging buckets, network service usage by activity (e.g., network capacity controlled services and other

69

services), network busy state (e.g., and with resulting policies in force), service activity policy setting vs. busy state and time/day/week, network service activity priority, network service activity usage statistics (e.g., vs. network busy state and/or network service usage control policy state).

In some embodiments, a UI notification is displayed when user attempts a network capacity controlled service activity during a network busy state (e.g., that modifies a network capacity controlled services policy). In some embodiments, the UI notification includes information on service plan choice and a network capacity controlled services policy over-ride option (e.g., one time, time window, usage amount, permanent by activity, and/or all), charging information based on a user selection, and/or service plan upgrade information and options.

In some embodiments, a UI notification is displayed for user input for preferences/configurations for multiple networks (e.g., WiFi, 4G, 3G, and/or other wired or wireless access networks) including charging policy. In some embodiments, a UI notification is displayed when a specified network traffic service usage activity (e.g., based on network capacity controlled services classification, QoS classification, priority classification, time based criteria, network capacity, service plan, charging criteria, and/or other criteria/measures) is being attempted or is occurring and providing options (e.g., allow, block, delay, throttle, and/or other options).

In some embodiments, a UI fuel gauge is displayed (e.g., to depict current and/or historical network service usage, for example, relative to a service plan for the device, by network, relative to network busy state, time based criteria, and/or other criteria/measures). In some embodiments, a user notification includes a communication sent to the user (e.g., an email, SMS or other text message, voice message/call, and/or other electronic form of communication). In some embodiments, the communication sent to the user includes network service usage information, network capacity controlled service usage related information, and/or an instruction to log into a web page or send a communication for more information (e.g. regarding an information update and/or alert or warning message, such as related to network service usage and/or charging for network service usage).

In some embodiments, a notification (e.g., a user or network service cloud notification) is generated based on an aggregate service activity reports usage (e.g., allows network provider to generate user notifications and/or to notify application provider/service activity provider). In some embodiments, a notification (e.g., a user or network service cloud notification) is generated based on a publishing of an updated/new network capacity controlled services list based on an aggregate monitored activity (e.g., based on a service plan, velocity, sockets opening frequency/rate (e.g., messaging layer behavior), total data usage, peak busy time usage to formulate or update black list for monitoring, notifying, and/or controlling, which can be applied to one, multiple, group, or all devices). In some embodiments, a notification (e.g., a user or network service cloud notification) is generated based on data usage trends for particular device relative to an associated service plan and/or other comparable devices or data usage thresholds/statistical based data usage measures.

In some embodiments an application is actually composed of several component applications, processes or functions. Examples of this include but are not limited to: the components of a Java application JAR file; applications that use OS functions; applications that use a proxy service function; applications, functions or processes that coordinate with one

70

another to implement a composite process, function or application; and OS process functions that support an application or overall OS function. In such embodiments it is important to be able to categorize all applications, functions and processes on a device that contribute to the service usage of a service activity so that the service activity can be monitored for service usage, have the service usage accounted for, implement the appropriate user notification when one or more service activity components attempts to start or use the network, implement the appropriate user notification when one or more service activity components reaches a pre-determined service usage level that requires user notification, and implement the appropriate background service or network protection service usage controls as specified herein ((including but not limited to for example: block network access, restrict network access, throttle network access, delay network access, aggregate and hold network access, select for time of day network access restrictions, select network type restrictions, select roaming network access restrictions, select service usage restrictions such as a usage limit, select service cost restrictions such as a cost limit or otherwise place on another form of background service status or network usage restriction as described herein). In the case of service activity components that belong exclusively to one aggregate service activity (e.g. an application, application JAR file or OS function), this may be accomplished by including each of the component service activities on a list that identifies the service activity components that belong to the aggregate service activity, and then monitoring, possibly controlling and providing user notifications based on the aggregate or component behavior of each service activity in accordance with the policies specified for the aggregate service activity. For example, it is necessary to group all application launch behavior and/or network access behavior under the monitoring, launch, notification, accounting and background service controls or network protection service controls (or other background or network protection service policies as specified herein) in accordance with the background service or network protection service policies for the aggregate application that the JAR file supports. As another example, if an OS network synch or update function utilizes various software components or processes to implement the network synch or update function, then each of the software components or process must be monitored and aggregated under the background service policies or network protection service policies for the aggregate OS synch or update function.

In some embodiments, this ability to group usage for a related set of service activity components dedicated to an aggregate service activity as described herein is used to improve usage reporting of service activities to a service controller for the purpose of statistically identifying service activities that are candidates for background service policy controls or network protections service policy controls.

In some cases, multiple applications, processes, functions, OS services or other service activities can utilize a common set of component software applications, processes, functions or OS services. In such cases, in order to implement background service policies and/or network protection service policies for service activity monitoring and accounting, service activity launch control, user notification, or network access control as described herein, it is necessary to associate the specific network access data or information flows to and from the common component software applications, processes or functions that belong to the specific initiating application, process, function or other service activity that is to be managed according to a background service or network

71

protection service policy set. In what follows, a specific set of examples are provided on how to map common component service activity for a set of common OS functions referred to as proxy service functions to a specific application, process, function, OS service or other service activity for the purpose of implementing a background service policy set or a network protection service policy set as described herein. Once these examples are reviewed, it will be obvious to one of ordinary skill in the art how to apply similar mapping of service activity for a common set of components to a service activity that is to be managed in accordance with a background service policy set or a network protection service policy set as described herein.

In some embodiments, this ability to group usage for a common set of service activity components as described herein is used to improve usage reporting of service activities to a service controller for the purpose of statistically identifying service activities that are candidates for background service policy controls or network protections service policy controls.

In some embodiments, a proxy network service manager refers to an intermediary data flow function in a device operating system that sits on a data path between a device application and a device networking stack interface to provide a level of network service abstraction from the network stack interface, a higher level service function above the network stack interface, enhanced or special traffic processing functions, media service transfer management, file download service, HTTP proxy service functions, QoS differentiation, or other similar or related higher level traffic processing. Example Proxy Service Managers include the following: media service manager (e.g. android media service library function), email service manager, DNS function, software download service manager, media download manager (e.g. audio player, streaming media player, movie downloader, media service OS function, etc), data download service manager, Android "media" library function, Android.net library function, Java.net library function, Apache library function, other similar software/library functions or services in other device operating systems, SMTP/IMAP/POP proxy, HTTP proxy, IM proxy, VPN service manager, SSL proxy, etc. Herein these alternative network access data flows that are initiated by an application are termed application proxy service flows. In such embodiments an app can sometimes simply requests a network access service activity from an OS component such as a proxy service component rather than directly accessing the network. In such embodiments, in order to implement background service controls or user notification of application service usage, it is necessary to monitor the application proxy service flows, classify them as being initiated by or belonging to a particular application or service activity, and implement the proper background service classifications, user notifications, application process launch intercept, background service accounting, and background service usage restrictions as described herein in accordance with the policies intended for the initiating application or service activity. This is accomplished by inserting service usage monitors that allow a mapping of (i) the initiating application identifier (e.g. app name, app fingerprint, application identification tag, application process number, application credential, or other secure or non-secure application or process identifier) to (ii) the request to the proxy service and subsequently to (iii) the network service flows between the proxy service and the network elements that service the information communications. Once this mapping is accomplished, the service usage flows of the proxy service can then

72

be accounted back to the initiating application, device software process or other service activity, the proper policies can then be applied to each service usage flow for user notification, service activity launch control, service activity background accounting (including variable charge rating dependent on background service state and/or sponsored service charging), service activity background service controls or network usage restrictions as described herein (including but not limited to for example: block network access, restrict network access, throttle network access, delay network access, aggregate and hold network access, select for time of day network access restrictions, select network type restrictions, select roaming network access restrictions, select service usage restrictions such as a usage limit, select service cost restrictions such as a cost limit or otherwise place on another form of background service status or network usage restriction as described herein).

In some embodiments, this ability to track service usage for an service activity through a proxy service as described herein is used to improve usage reporting of service activities to a service controller for the purpose of statistically identifying service activities that are candidates for background service policy controls or network protections service policy controls.

In some embodiments, the various design techniques described herein that allow for monitoring, accounting for and/or implementing service policy for component service activities that belong to an aggregate service activity can be designed into the OS itself. For example, in certain current mobile OS implementations (e.g. Android, iPhone, BlackBerry, etc) there are some applications available in the market that allow a user to get an estimate for how much data a certain subset of applications are consuming on a wireless service provider network, but it is not possible for the user or application to get an indication of the service usage for certain OS functions, whereas the embodiments disclosed herein will allow for this. As another example, in certain current mobile OS implementations it is not possible to associate proxy service usage (e.g. media download and media streaming proxy library software functions) with the specific applications that use the proxy service, so while the user can be informed of generic common OS functions or proxy services (e.g. in the case of Android: "media service", "media", "gallery", "google service framework" and other generic common OS software library functions or proxy services), there is no way for the user to determine what applications widgets or other service activities are actually generating this common service function usage, whereas the invention described herein permits the user full visibility on such usage monitoring examples. Furthermore, if the OS is retrofitted with the intercept and policy implementation functions can be designed into the activity manager, broadcast intent manager, media service manager, service manager, or other application or service activity management function in the Android OS. One of ordinary skill in the art will recognize that similarly, the various design techniques described herein that allow for intercepting a service activity intention to launch, and applying a background service policy set or a network protection service policy set can be designed into application launch management functions in the iPhone OS, windows mobile OS, windows PC OS, BlackBerry OS, Palm OS, and other OS designs.

FIG. 19 illustrates another flow diagram for device assisted services (DAS) for protecting network capacity in accordance with some embodiments. At 1902, the process begins. At 1904, determining a network busy state of one or more networks is performed. In some embodiments, the one

73

or more networks are selected from an access network, a wired network, and a wireless network. At **1906**, classifying a network service usage activity (e.g., a network capacity controlled service) of a device based on the network busy state determination is performed to facilitate differential network access control for protecting network capacity of the one or more networks. In some embodiments, the network busy state is based on one or more of the following: network performance, network congestion, network availability, network resource availability, network capacity, or any other network service usage measure, and one or more time windows (e.g., time based criteria). In some embodiments, protecting network capacity of the one or more networks includes protecting network capacity of a last edge segment of a wireless network (e.g., RAN, BTS, BTSC, and/or other network elements). In some embodiments, the determining and classifying are performed using device assisted/based techniques. In some embodiments, the determining and classifying are performed using network assisted/based techniques (e.g., implemented on a network element/function, such as a service controller, a DPI gateway, a BTS/BTSC, etc., or a combination of network elements). In some embodiments, the determining and classifying are performed using a combination of device assisted/based techniques and network assisted/based techniques. At **1908**, implementing differential traffic controls is performed based on the service usage activity classification for protecting network capacity is performed. At **1910**, the process is completed. In some embodiments, a network busy state is determined based on one or more of the following: a time of day, a network reported busy state, and/or a device (e.g., near-end and/or far-end) determined/reported network busy state. In some embodiments, a network busy state is determined using one or more of the following: a network probe, a device query, a network probe report (e.g., including a BTS and/or BTSC), a network probe analysis, a device analysis based on performance of native traffic without probe such as TCP timeout, UDP retransmissions, a multiple network test, a device monitored network congestion based on network service usage activity (e.g., application based network access performance data) performed for a network to which the device is connected and/or one or more alternative networks. In some embodiments, a network congestion state is associated with a network busy state (e.g. a network busy state setting/level). For example, a network congestion level of 40% of network usage can be associated with a network busy state setting of 4, a network congestion level of 80% of network usage can be associated with a network busy state setting of 8, and so forth.

FIG. **20** illustrates another flow diagram for device assisted services (DAS) for protecting network capacity in accordance with some embodiments. At **2002**, the process begins. At **2004**, monitoring a network service usage activity of a device in network communication is performed. At **2006**, classifying the network service usage activity (e.g., based on a classification of the network service usage activity for protecting network capacity, for example, as a network capacity controlled service) for protecting network capacity is performed. At **2008**, accounting for network capacity controlled services (e.g., accounting for the network service usage activity based on a classification of the network service usage activity for protecting network capacity) is performed. At **2010**, charging for network capacity controlled services is performed. At **2012**, the process is completed. In some embodiments, DAS for protecting network capacity further includes classifying the network service usage activity as a network capacity controlled service.

74

In some embodiments, DAS for protecting network capacity includes differentially accounting and/or differentially charging for network capacity controlled services and foreground services. In some embodiments, the network service usage control policy includes policies for differentially controlling, accounting, and/or charging for network capacity controlled services (e.g., based on a network busy state, a time based criteria, a service plan, network to which the device or network service usage activity is gaining access from, and/or other criteria/measures). In some embodiments, accounting for network capacity controlled services includes differentially collecting service usage for one or more network capacity controlled service classes in which the accounting is modified/varies (e.g., dynamically) based on one or more of the following: network busy state (e.g., modify/credit accounting during network congestion not satisfying the user preference), network service activity, access network (e.g., the network to which the device/service activity is currently connected), user preference selection, time based criteria (e.g., current time of day/day of week/month), associated service plan, option to time window. In some embodiments, charging for network capacity controlled services includes mapping an accounting to a charging report. In some embodiments, charging for network capacity controlled services includes sending the charging report to a network element (e.g., a service controller, a service cloud, a billing interface/server, and/or another network element/function). In some embodiments, charging for network capacity controlled services includes mediating or arbitrating CDRs/IPDRs for network capacity controlled service(s) vs. other network service usage activities or bulk network service usage activities. In some embodiments, charging for network capacity controlled services includes converting a charging report to a billing record or billing action. In some embodiments, charging for network capacity controlled services includes generating a user notification of network capacity controlled service charges upon request or based a criteria/measure (e.g., a threshold charging level and/or a threshold network service usage level). In some embodiments, charging for network capacity controlled services includes charge by application based on a charging policy (e.g., bill by application according to billing policy rules, such as for billing to a user or to a sponsored service provider, carrier, and/or other entity).

FIG. **21** illustrates another flow diagram for device assisted services (DAS) for protecting network capacity in accordance with some embodiments. In some embodiments, DAS for protecting network capacity includes providing a device service access API that provides an interface for applications, OS functions, and/or other service usage activities to a network access connection (e.g., or stack) for providing differential network access for protecting network capacity. In some embodiments, the differential network access is determined by one or more of the following: a service priority of the service usage activity and a network busy state. At **2102**, the process begins. At **2104**, a device service access API request is received. At **2106**, the device service access API request is responded to. In some embodiments, the differential network access (e.g., for network capacity controlled services and/or based on network busy state and/or other criteria/measures) is implemented by one or more of the following: providing network busy state information to the service usage activity, receiving network busy state information, receiving network capacity demands for the service usage activity, receiving a scheduled time/time slot demand from the service usage activity, receiving and/or providing network location and/or physical location

75

information (e.g., base station, communication channel, cell sector, roaming or non-roaming network to which the device is connected, and/or GPS or other physical location data), providing information to the service usage activity informing it when it is allowed to access the network, providing information to the service usage activity informing it what traffic controls must be applied/implemented, providing information to the service usage activity informing it when the network is available to it for access, and providing information to the service usage activity of its scheduled access time/time slot (e.g., based on one or more of the following: priority, network busy state, and time of day) (e.g., with a specified performance level or service level, such as data transfer size, speed, network capacity controlled service priority level, QoS level, data transfer type, scheduling time(s), and/or network connection parameters), and instructing the device and/or service usage activity to transition to a different state (e.g., power save state, sleep state dormant, idle, wait state, and/or an awake state). At **2108**, differential network access is implemented. At **2110**, the process is completed. In some embodiments, the device service access API is a programmatic interface, a virtual interface, and/or an emulated interface that provides instructions for differential access to a network to protect network capacity, as described herein.

In some embodiments, the API is served or located on the device, on a network element (e.g., using a secure communication between the device and the network element for the API communication, such as HTTPS, TLS, SSL, an encrypted data connection or SS7 control channel, and/or other well known secure communication techniques), and/or both/partly in both. In some embodiments, a network based API is an API that facilitates an API or other interface communication (e.g. secure communication as discussed above) between an application executing on the device and a network element and/or service cloud for protecting network capacity. For example, a network API can provide an interface for an application to communicate with a service cloud (e.g., network server) for obtaining network access control information (e.g., network busy state, multiple network information based on available networks and/or network busy state information of available networks, network capacity controlled service priorities and availability, scheduled time/time slots for network access based on network busy state, service plan, network capacity controlled service, and/or other criteria/measures). As another example, a network API can facilitate an application provider, central network/service provider, and/or a third party with access to communicate with the application to provide and/or request information (e.g., physical location of the application, network location of the application, network service usage information for the application, network busy state information provided to the application, and/or other criteria/measures). As yet another example, a network API can facilitate a broadcast to one or more applications, OS functions, and/or devices (e.g., partitioned based on geography, network, application, OS function, and/or any other criteria/measure) with network capacity related information (e.g., network busy state, availability based on network capacity controlled service classification and/or priority level, scheduled time/time slots for certain network capacity controlled service classification and/or priority level, emergency/high priority software/antimalware/vulnerability update and scheduled time/time slots for such software updates, and/or other criteria/measures). In some embodiments, the network access API for protecting network capacity is an open API or standard/required API (e.g., required or

76

standardized for applications for a certain network service provider, such as to be provided via the Verizon application store or the Apple AppStore) published for application and OS developers so that the applications and OS functions are designed to understand and implement the network access API for protecting network capacity. For example, a certification program can be established to provide application and OS developers with test specifications, working implementations, and/or criteria to make sure the network access API is properly implemented and is functioning in accordance with the specified requirements. In some embodiments, the network access API is an interface for communication with a service controller (e.g., service controller **122**) or another network element/function (e.g., a service usage API for communication with a service usage server or billing interface/server or another network element/function that facilitates a secure communication for sending/receiving or otherwise communicating network access related information for protecting network capacity). In some embodiments, the network API provides for sponsored billing (e.g., reverse billing) of all, classified, and/or a subset of network service usage charges to a sponsored partner associated with the network service usage activity (e.g., application) that accesses the network API. In some embodiments, the network API provides for a sponsored service in which the network service usage activity (e.g., application) that accesses the network API provides a sponsored service partner credential to the network API, the credential is used as a billing mechanism to charge the sponsored partner, the user account is mediated to remove the sponsored partner charge, and the network API provides access service and/or information service (e.g., location information, local information, content information, network information, and/or any other information).

FIG. **22** illustrates another flow diagram for device assisted services (DAS) for protecting network capacity in accordance with some embodiments. At **2202**, the process begins. At **2204**, network service usage activities of a device are monitored (e.g., using a verified/verifiable service processor). At **2206**, a network busy state (e.g., a measure of network capacity, availability, and/or performance) is determined based on the monitored network service usage activities (e.g., using various techniques as described herein). In some embodiments, a service processor on the device is used to determine (e.g., measure and/or characterize) a network busy state experienced by the device (e.g., which can be used to determine the network access control policy for one or more network capacity controlled services). At **2208**, a network busy state report is sent to a network element/function (e.g., a service controller and/or another network element/function as described herein). At **2210**, the process is completed. In some embodiments, the service processor is verified using various techniques described herein. In some embodiments, the network busy state report includes one or more of the following: data rate, latency, jitter, bit error rate, packet error rate, number of access attempts, number of access successes, number of access failures, QoS level availability, QoS level performance, and variability in any of the preceding parameters. In some embodiments, the network busy state report includes one or more of the following: base station ID, cell sector ID, CDMA ID, FDMA channel ID, TDMA channel ID, GPS location, and/or physical location to identify the edge network element that is associated with the network busy state report to a network element. In some embodiments, the monitoring of network service usage activities includes measuring the network performance for traffic the device is transmitting/receiving

77

and/or generating network performance testing traffic. In some embodiments, the network busy state is collected (e.g., and/or used to assist, supplement, and/or verify device based network busy state measures) by one or more network elements that can measure and/or report network busy state (e.g., BTS, BTSC, base station monitor, and/or airwave monitor). For example, airwave monitors and/or base station monitors can be provided to facilitate a reliable characterization of network busy state in a coverage area of one or more base stations and/or base station sectors, such as affixed mobile terminals (e.g., trusted terminals that can include additional network busy state monitoring and/or reporting functionality) installed (e.g., temporarily or permanently) in the coverage area of one or more base stations and/or base station sectors (e.g., in which a sector is the combination of a directional antenna and a frequency channel) so that the affixed mobile terminals perform network busy state monitoring and reporting to the service controller, the local base station, and/or other network element(s)/function(s) as similarly described herein. In some embodiments, the permanently affixed mobile terminals provide network monitors for reporting, for example, network busy state, to a central network element, such as the service controller, which can, for example, aggregate such network busy state information to determine network busy state for one or more network coverage areas. In some embodiments, the permanently affixed mobile terminals are always present in these locations where installed and always on (e.g., performing network monitoring), and can be trusted (e.g., the permanently affixed mobile terminals can be loaded with various hardware and/or software credentials). For example, using the permanently affixed mobile terminals, a reliable characterization of network busy state can be provided, which can then be reported to a central network element and aggregated for performing various network busy state related techniques as described herein with respect to various embodiments. In some embodiments, the network element/function uses the network busy state report (e.g., and other network busy state reports from other devices connected to the same network edge element) to determine the network busy state for a network edge element connected to the device. In some embodiments, network element/function sends a busy state report for the network edge element to the device (e.g., and to other devices connected to the same network edge element), which the device can then use to implement differential network access control policies (e.g., for network capacity controlled services) based on the network busy state. In some embodiments, a network busy state is provided by a network element (e.g., service controller or service cloud) and broadcast to the device (e.g., securely communicated to the service processor).

FIG. 23 illustrates a network capacity controlled services priority level chart for device assisted services (DAS) for protecting network capacity in accordance with some embodiments. In some embodiments, various applications, OS functions, and/or other utilities/tools installed/loaded onto and/or launched/executing/active on a communications device (e.g., device 100) are classified as network capacity controlled services for protecting network capacity. In some embodiments, one or more of the network capacity controlled services are assigned or classified with network capacity controlled service levels or priority levels for protecting network capacity. In some embodiments, one or more of the network capacity controlled services are dynamically assigned or classified with network capacity controlled service levels or priority levels based on one or more criteria/measures (e.g., dynamic criteria/measures),

78

such as network busy state, current access network, time based criteria, an associated service plan, and/or other criteria/measures. In some embodiments, a higher priority level means that the application or utility/function is granted higher relative priority for network access (e.g., a priority level 10 can provide for guaranteed network access and a priority level 0 can provide a blocked network access, while priority levels between 1 through 9 can provide relatively increasing prioritized network access potentially relative to allocated network access and other services requesting network access).

As shown in FIG. 23, the network capacity controlled services are dynamically assigned or classified with network capacity controlled service levels or priority levels based on the network busy state of the current access network. For example, an email application, Microsoft Outlook, is assigned different priority levels for protecting network capacity based on the network busy state, as shown: a priority level 6 for a network busy state (NBS) level of 10% (e.g., up to about 10% of the network capacity is being utilized based on current or recently/last measured/detected/determined network capacity/resources usage using various techniques as described herein), a priority level 5 for a network busy state (NBS) level of 25%, a priority level 4 for a network busy state (NBS) level of 50%, a priority level 3 for a network busy state (NBS) level of 75%, and a priority level 2 for a network busy state (NBS) level of 90%. As also shown, an antivirus (AV) software update application/utility/function is assigned different priority levels for protecting network capacity based on the network busy state: a priority level 9 for a network busy state (NBS) level of 10%, a priority level 7 for a network busy state (NBS) level of 25%, a priority level 5 for a network busy state (NBS) level of 50%, a priority level 3 for a network busy state (NBS) level of 75%, and a priority level 1 for a network busy state (NBS) level of 90%. Various other applications and utilities/functions are shown with various priority level assignments/classifications based on the network busy state levels shown in the network capacity controlled services priority level chart of FIG. 23. As will be apparent to one of ordinary skill in the art, various assignments and/or techniques for dynamically assigning priority levels for network access based on network busy state levels can be applied for protecting network capacity (e.g., based on user preferences, service plans, access networks, a power state of device, a device usage state, time based criteria, and various other factors such as higher priority for urgent software and/or security updates, such as a high priority security or vulnerability software patch or update, and/or urgent or high priority emails or other communications, such as a 911 VOIP call).

Referring again to FIGS. 1 through 3, DAS for protecting network capacity is implemented using a service processor (e.g., a service processor 115) of the device (e.g., a device 100) using various DAS techniques as described herein to facilitate differential network service access control (e.g., for network capacity controlled services) to assist in protecting network capacity in accordance with some embodiments. In some embodiments, the service processor and/or one or more agents of the service processor is/are verified using one or more of the following verification techniques (e.g., and/or to specifically verify monitoring the network service usage activity, classifying one or more service activities into one or more network capacity controlled service classes, associating the one or more network capacity controlled service classes with one or more differential service activity policies, and/or determining a network busy state): compare a

network based service usage measure with a service policy and/or service plan associated with the device, compare a device assisted service usage measure with the service policy and/or service plan associated with the device, compare the network based service usage measure to the device assisted service usage measure, compare a first device assisted service usage measure to a second device assisted service usage measure, verify presence of the service processor and/or one or more agents of the service processor, verify configuration of the service processor, verify service usage activities are reported properly (e.g., using test service usages to generate service usage events/reports for analysis and confirmation), verify billing events are reported properly, compare the network based service usage measure with reported device billing data, verify reporting of a test billing event, verify reporting of the communications device reports billing events from a transaction server, verify presence of an activation tracking system, verify device configuration or operation, verify device standing or service plan standing, verify proper operation of the service processor, verify service processor heartbeat response reports, verify monitoring of a test service event, download a new service processor (e.g., and/or one or more agents or new configuration settings of the service processor) and perform integrity checks, verify a service processor code configuration with agent self-diagnosis checks, verify that the communications device uses the first service only after being authorized, verify user standing, verify a network busy state (e.g., compare and/or statistically process network busy state measures from more than one device in which the network busy state monitoring apparatus, for example, is located in a secure execution environment on the device), verify various differential network access control implementations (e.g., network capacity controlled services are properly monitored/determined/detected, controlled, accounted for, and/or charged for), verify various QoS implementations (e.g., as discussed above), and verify an agent communications log. Various other verification techniques are described herein and similar and other verification techniques for providing DAS for protecting network capacity using device based implementations (e.g., service processors and/or other device based agents or software/hardware techniques) will now be apparent to one of ordinary skill in the art in view of the various embodiments described herein.

In some embodiments, the service processor is secured using various hardware and software techniques described herein, including, for example, implementing all and/or portions of the service processor in a secure virtual machine, protected execution environment, secure storage (e.g., secure memory), secure modem, and/or other secure implementation techniques as described herein and/or other or similar techniques as will now be apparent to one of ordinary skill in the art in view of the various embodiments described herein. For example, the service processor can be implemented in software and executed in a protected area of an OS executed on the device and/or executed in protected execution partitions (e.g., in CPU, APU, SIM chipset, modem, modem secure execution partition, SIM, other hardware function on the device, and/or any combination of the above).

In some embodiments, a network service usage counter is embedded into a secure execution environment (e.g., a program store in secure non-volatile memory located on a modem card and/or a modem chip not accessible by device applications, secure CPU environment for executing program and/or secure program operation for data path monitoring and/or control that cannot be bypassed by device

applications to get to the modem connection to the network) in a device modem (e.g., using measurement points V, VI, and/or other measurement points of FIG. 12). In some embodiments, the service usage counter counts data traffic (e.g., bytes and/or any other measure of service usage, such as file transactions, message transactions, connection time, time of connection or duration of connection, and/or traffic passed or transactions passed for a given QoS or network capacity controlled service priority level), traffic as a function of time, traffic according to a network service activity classification (e.g., by application, destination/source, port, traffic type, content type, time of day, network busy state, and/or any other criteria/measure). In some embodiments, the service usage counter counts data traffic (e.g., as discussed above) while coordinating with a VPN layer established, for example, for both layer-III (e.g., IPSEC) and layer-II (e.g., L2TP tunnel) so that precise over the air service usage measure is counted for billing mediation and/or network service usage charging (e.g., customer billing, sponsored service bill by service and/or any other charging or billing). In some embodiments, the service usage counter counts data traffic (e.g., as discussed above) while coordinating with accelerator software (e.g., a compression/decompression engine) which transforms frames for more efficient over the air transmission. As similarly discussed above, service processor coordination with the accelerator layer facilitates a precise over the air service usage measure for billing mediation and/or network service usage charging. In some embodiments, the service usage counter counts data traffic (e.g., as discussed above) while coordinating with both the VPN layer and accelerator software layer to facilitate a precise over the air service usage measure for billing mediation and/or network service usage charging.

In some embodiments, the service usage counter reports the service usage to a network element (e.g., a service controller, charging gateway, PCRF, AAA, HA, billing system, mediation system, traffic accounting database, base station or base station controller, and/or another network element/function or central network element/function). In some embodiments, the information reported to the network element is encrypted or signed with a corresponding key known by the network element. In some embodiments, the communication link to the network element to pass the service usage count is conducted over a wireless network specific channel such as SMS, MMS, SS-7, or another specialized control channel. In some embodiments, the communications link to the network element to pass the service usage count is conducted over a network channel (e.g., via IP, TCP, UDP, HTTP, HTTPS, TLS, SSL, point to point signed variants of TLS or SSL, or another data network channel via the network control channel connection to the device). In some embodiments, the data network control channel traffic is injected into the PPP stream at the modem. In some embodiments, the data network control channel traffic is passed up to the device networking stack for connection to the network. In some embodiments, a signed or encrypted service usage count from the modem subsystem is coordinated to provide a service usage count for a time period that also corresponds to a similar time period for a service processor heartbeat report that includes a service usage measure or count. For example, this provides the service controller or another network element with a secondary set of information that can be used to verify and/or secure the service usage measures reported by the service processor. Various techniques can be used to synchronize the time period for the modem service usage count and the

81

service processor service usage count. For example, the service processor can request a latest count message from the modem, in which the modem counts all service usage since the previous request for latest count until the present request for latest count, encrypts the latest count message so that the service processor or other application software or OS software on the device cannot decode and/or tamper with the message, and the modem service usage counter then passes the encrypted message to the service processor. The service processor can then pass the encrypted service usage count message from the modem to the service controller along with the service processor service usage accounting message(s) for the same or similar time period. The service controller can then decode both service count messages from the secure modem subsystem and the service processor and correlate the two measures to verify the service usage reporting by, for example, looking for discrepancies that would indicate service usage control or charging errors or device service processor tampering. In some embodiments, the secure modem subsystem records byte counts for streams (e.g., and/or flows, socket connections, or combinations of IP destination/source/ports), potentially along with time of day, network busy state, QoS level, and/or other criteria/measures, and reports these counts for each stream that had traffic activity during the current reporting interval. For example, the service controller can then correlate the stream service usage information with the service usage information provided by the service processor heartbeat service usage report to verify that the service processor service usage report is consistent with the independent measure made in the modem subsystem. In some embodiments, service usage reports (e.g., certified service usage reports) are correlated on the device and/or in the network (e.g., using one or more network elements/functions, such as the service controller).

In some embodiments, a deeper analysis of traffic can be conducted in the modem subsystem service usage count. For example, a layer 7 analysis of the service usage can be conducted for HTTP or HTTPS traffic flowing through the modem in which the modem subsystem service usage counter performs an HTTP level analysis of the traffic to associate web traffic gets and other transfers with a given higher level service classification (e.g., ad server, content server, proxy server, and/or traffic that is referred by the local host serving up a web page). In some embodiments, the modem subsystem service usage count can be augmented for HTTPS, SSL or TLS traffic by including a trusted proxy server embedded in the modem system. For example, the proxy server can be trusted by the device stack so that the encryption keys for HTTPS, TLS or SSL are known by the proxy server allowing the modem based proxy server, located, for example, in a secure execution environment, to perform layer 7 analysis of encrypted traffic in a manner similar to that described above. In some embodiments, the embedded proxy server generates server SSL certificates for each connection to a specific remote host in real time based on a root certificate trusted by the device (e.g., and/or by network service usage activity, such as by application) and also trusted by the embedded proxy server, and the proxy server then becomes a middle man emulating a remote SSL host on one side and emulating the device (e.g., and/or network service usage activity, such as application) on the other side, decrypting the traffic, analyzing it and re-encrypting before forwarding to and from the remote host. Similarly, as in the case of layer 3 and 4 traffic analysis performed by the modem service usage counting subsystem, the layer 7 service usage count messages can be encrypted and passed to the service con-

82

troller via various channels. In some embodiments, the layer 7 modem subsystem service usage counting system records service usage counts for a reporting time period that is similar to the reporting time period used by the service processor so that the service controller can correlate the service processor accounting messages against the modem accounting messages with layer 7 information.

In some embodiments, the secure service usage reporting system elements are located in a secure execution environment that includes the modem driver. In some embodiments, all traffic that gets to the modem for the network traffic being controlled or accounted for is required to go through the secure modem driver so that an independent count can be generated and reported to the service controller as described above without the need to embed the secure service usage counting and reporting elements in the modem.

In some embodiments, the secure service usage reporting system elements are located in a secure execution environment that includes the modem driver and modem hardware interface controller driver (e.g. USB controller for 2/3/4G and SDIO controller for WiFi). In some embodiments, all traffic that gets to the modem for the network traffic being controlled or accounted for is required to go through the secure modem driver and modem hardware interface controller driver (e.g. USB controller for 2/3/4G and SDIO controller for WiFi) so that precise count can be generated by either the modem driver and/or modem hardware interface controller driver (e.g. USB controller for 2/3/4G and SDIO controller for WiFi) and passed to the secure service usage reporting element to send it to the service controller for customer charging/billing. This scheme provides flexibility (e.g., most of the device software and operation system and its services/applications need not be located/executed in the secure execution environment) while ensuring usage counting to occur securely as it pertains to the customer accounting and billing.

In some embodiments, the layer 7 proxy server traffic accounting and reporting techniques used for processing HTTPS, TLS, and SSL traffic, as discussed above, are also used in the service processor itself to allow a detailed accounting of encrypted layer 7 traffic by the device. In some embodiments, the information thus obtained is filtered so that private user information is not transmitted to the network (e.g., service controller, PCRF, and/or any other network element/function) but only service usage information sufficient to allow for accounting of service plan usage, to verify service control policy implementation, or to verify service charging policy implementation is transmitted to the network (e.g., service controller, PCRF, and/or any other network element/function). In some embodiments, the layer 7 proxy server for processing secure or in the clear device service usage accounting messages is located in secure hardware execution environments in the device application processor or within secure software partitions in the operating system.

Various techniques can be used to verify and/or secure service usage controls or service usage charging reports. For example, if the secondary service usage reports indicate that service usage is outside of the service usage policy limits that are intended to be in effect (e.g., based on a service plan and/or service policy associated with the device), then the service controller can indicate an error flag for further analysis and action (e.g., implementing various verification and responsive actions as described herein, such as blocking the activity, throttling the activity, quarantining the device, updating/replacing the service processor, and/or monitoring the device using various additional DAS and/or network

83

assisted monitoring techniques). As another example, if the service usage reports from the service processor do not match up with the secondary service usage reports, then the service controller can indicate an error flag for further analysis and action. For example, the correlation can be based on bulk measures of service usage (e.g., total bytes over a given period of time), or using finer grain measures of service usage (e.g., verifying the accounting between one group of service usage activities, such as application, destination/source, port, content type, time of day, network busy state, QoS level, and/or other criteria/measures) charged to one service plan charging record versus the accounting for another group of service usage activities charged to another service plan charging record. In some embodiments, the correlation process between the two service usage accounting reports is performed continuously on all device traffic in real time or near real time as the usage accounting reports are received. In some embodiments, the usage accounting reports are stored and analyzed or correlated later (e.g., periodically, based on a request or audit, and/or based on certain events, such as threshold network service usage events and/or any other events based on various criteria/measures). In some embodiments, only an audit of a portion of time is used to correlate the two usage accounting reports, which, for example, can reduce network traffic and/or network processing load in the service controller.

In some embodiments, correlation techniques are applied by the service controller to compare two different service usage measures as described above based on one or more of the following: total amount of data (e.g., bytes for file transfers, sessions, and/or other measures), amount of data per unit time, total number of accesses, number of accesses per unit time or frequency of accesses, accesses during a time interval (e.g., peak time), accesses during a network busy state, access requests, and individual versus group transmissions at a point in time (e.g., each for a given set of destinations or destinations and traffic types).

In some embodiments, service usage monitoring includes characterizing service usage activities by streams, flows, destination/port, packet inspection, and/or other criteria/measures using the various techniques as described herein and/or other or similar techniques as would be apparent to one of ordinary skill in the art. In some embodiments, service usage monitoring includes characterizing service usage activities by streams, flows, destination/port, packet inspection, and/or other criteria/measures and then correlating to find network service usage behavior patterns that identify likely association of behavior with one or more service activities being managed.

In some embodiments, DAS for network capacity control includes classifying traffic to determine which network service usage activity(ies) are causing traffic (e.g., increasing network capacity/resources usage beyond a threshold), and then determining if access network service usage activity(ies) are violating any rules (e.g., service usage policies or service plan settings associated with the device/user). In some embodiments, DAS for network capacity control includes generating a list for network capacity controlled services that specifies behavioral characteristics for one or more network service usage activities with expected access limits based on access control policy for each managed network service usage activity (e.g., based on service usage policies or service plan settings associated with the device/user). In some embodiments, DAS for network capacity control includes monitoring and/or controlling network service usage activities based on limits, which, for example, can be based on one or more of the following: total access

84

traffic counters, counters for different types of access traffic, destinations, ports, frequency of accesses, access behavior during a given time, access behavior during a given busy state, access behavior for groups of activities (e.g., verify clumping), and/or other criteria/measures.

Accordingly, in some embodiments, a second secure and trusted service usage measure is provided that the service controller (e.g., or another network element/function) can use to verify or secure the service control or service charging reports for the service processor. In some embodiments, the secure and trusted service usage measure also provides for enhanced verification and service security in cases, in which, for example, network based service usage measures are available for additional correlation with the service processor service usage reports. In cases in which network based service usage measures are either not available or are only available at widely spaced time intervals (e.g., roaming networks or other networks with no timely network based service usage measure), these techniques facilitate real time or near real time verification or security for the device assisted service controls and charging.

In some embodiments, a SIM card performs a portion or all of the secure environment processing described above, with the device modem traffic, or a copy of the device modem traffic, being directed to the SIM secure subsystem for traffic accounting and reporting. In some embodiments, a SIM card is used to store QoS classifications and/or network capacity controlled services classifications for various service usage activities so that the user behavior in using certain network service usage activities and/or the user preferences in controlling certain network service usage activities do not need to be relearned or redownloaded as the user swaps the SIM between different devices. In some embodiments, the SIM keeps a local record of service usage activity for multiple devices that belong to the user or the user family plan, so that the service usage notification and policies can be immediately updated on a given device as the user swaps the SIM from device to device. In some embodiments, the manner in which this service usage history is stored on the SIM is secure so that it cannot be tampered with. In some embodiments, the SIM card is used to implement various application management and/or traffic control techniques described herein. In some embodiments, the SIM card is used to inspect traffic, classify traffic, create reports (e.g., certified service activity usage reports), encrypt the report, send the report to a network element/function, and the network element/function correlates the reports (e.g., using network assisted measures for comparisons and/or using various other techniques as described herein). In some embodiments, a SIM card performs a portion or all of the secure environment processing described above using one or more modem measurement points. For example, the traffic that is to be classified can be routed through the SIM and correlated with what is measured by the modem. In some embodiments, network assisted/based network service usage activity classifications are compared SIM based/assisted classifications for service usage monitoring/reporting verification (e.g., detected inconsistencies in monitored/reported network service usage activities can be identified, such as based on total traffic, streams/flows/sockets activities, and/or other criteria/measures). In some embodiments, the reports include a verified sequence so that reports cannot be spoofed and/or missing reports can be determined.

In some embodiments, a portion or all of the secure environment processing described above are applied to

85

implement and/or verify QoS for DAS techniques and/or DAS for network capacity controlled services techniques as described herein.

In some embodiments, the reports include one or more of the following: a number of times the device is cycled from or to a power cycle state in the modem, a number of times during a time window or network busy state, a power cycle versus number of streams initiated during the cycle, and a power cycle versus the streams that are transmitted during that cycle. In some embodiments, device power cycle events trigger generating of a report.

In some embodiments, monitoring, reporting, control, accounting, charging, and/or policy implementation for network capacity controlled services is verified (e.g., using various verification techniques described herein). If any of the verification techniques determine or assist in determining that the network capacity controlled services monitoring, reporting, control, accounting, and/or charging, and/or policy implementation has been tampered with, disabled, and/or is not properly implemented or functioning, then responsive actions can be performed, for example, the device (e.g., and/or suspect services) can be suspended, quarantined, killed/terminated, and/or flagged for further analysis/scrutiny to determine whether the device is malfunctioning, needs updating, has been tampered with or compromised, is infected with malware, and/or if any other problem exists.

In some embodiments, the service processor monitors a network service usage activity of a device. In some embodiments, monitoring of the service usage activity includes monitoring for multiple networks (e.g., to determine which networks are available and/or a network busy state of the available networks). In some embodiments monitoring a network service usage activity is performed by and/or assisted by a service cloud (e.g., one or more network elements that provide such a service). In some embodiments, monitoring the network service usage activity includes identifying the network service usage activity, measuring the network service usage of the network service usage activity, and/or characterizing the network service usage of the network service usage activity (e.g., using device assisted/ based techniques, network assisted/ based techniques, testing/offline monitoring/analysis techniques, and/or a combination thereof).

In some embodiments, the service processor implements differential network access service control (e.g., for network capacity controlled services), network service usage accounting, network service usage charging, and/or network service usage notification on the device to facilitate DAS for protecting network capacity.

In some embodiments, the service processor (e.g., a service processor 115) is updated, communicated with, set, and/or controlled by a network element (e.g., a service controller 122). In some embodiments, the service processor receives service policy information from a network function selected from a base station (e.g., a base station 125), a RAN gateway, a core gateway, a DPI gateway, a home agent (HA), a AAA server (e.g., AAA server 121), a service controller, and/or another network function or combinations of network functions as described herein and/or as will now be apparent to one of ordinary skill in the art in view of the various embodiments described herein. In some embodiments, the service processor is updated through over the air or over the network OS software updates or application software updates or device firmware updates. In some embodiments, the service processor uses an IP connection, SMS connection, and/or MMS connection, for a control channel with a

86

service controller. In some embodiments, the service processor queries a service controller to determine the association of a monitored network service usage activity with a network service usage control policy. In some embodiments, the device (e.g., service processor) maintains a network capacity controlled services list and/or network capacity controlled services policy for one or more of the active services (e.g., actively executing and/or previously installed/ downloaded to the device) that have been classified as a network capacity controlled service (e.g., as the number of applications continues to grow, as hundreds of thousands of applications are already available on certain platforms, maintaining a list specific and/or a set of policies unique or specific to each application is not efficient). In this embodiment, when a new application is active/launched and/or downloaded to the device, the device can request an updated network capacity controlled services list and/or an updated network capacity controlled services policy accordingly (e.g., and/or periodically refresh such lists/policies).

In some embodiments, differential network access control for protecting network capacity includes controlling network services traffic generated by the device (e.g., network capacity controlled services based on a network service usage control policy (e.g., a network capacity controlled services policy). In some embodiments, differential network access control for protecting network capacity includes providing assistance in control of the distribution of bandwidth among devices, network capacity controlled services (e.g., applications, OS operations/functions, and various other network services usage activities classified as network capacity controlled services), a differentiated QoS service offering, a fair sharing of capacity, a high user load network performance, and/or preventing one or more devices from consuming so much network capacity that other devices cannot receive adequate performance or performance in accordance with various threshold and/or guaranteed service levels. In some embodiments, differential network access control for protecting network capacity includes applying policies to determine which network the service activity should be connected to (e.g., 2G, 3G, 4G, home or roaming, WiFi, cable, DSL, fiber, wired WAN, and/or another wired or wireless or access network), and applying differential network access control rules (e.g., traffic control rules) depending on which network to which the service activity is connected. In some embodiments, differential network access control for protecting network capacity includes differentially controlling network service usage activities based on the service usage control policy and a user input (e.g., a user selection or user preference). In some embodiments, differential network access control for protecting network capacity includes differentially controlling network service usage activities based on the service usage control policy and the network the device or network service activity is gaining access from.

In some embodiments, the network service usage control policy is dynamic based on one or more of the following: a network busy state, a time of day, which network the service activity is connected to, which base station or communication channel the service activity is connected to, a user input, a user preference selection, an associated service plan, a service plan change, an application behavior, a messaging layer behavior, random back off, a power state of device, a device usage state, a time based criteria (e.g., time/day/ week/month, hold/delay/defer for future time slot, hold/ delay/defer for scheduled time slot, and/or hold/delay/defer until a busy state/availability state/QoS state is achieved), monitoring of user interaction with the service activity,

monitoring of user interaction with the device, the state of UI priority for the service activity, monitoring the power consumption behavior of the service activity, modem power cycling or power control state changes, modem communication session set up or tear down, and/or a policy update/modification/change from the network. In some embodiments, the network service usage control policy is based on updated service usage behavior analysis of the network service usage activity. In some embodiments, the network service usage control policy is based on updated activity behavior response to a network capacity controlled service classification. In some embodiments, the network service usage control policy is based on updated user input/preferences (e.g., related to policies/controls for network capacity controlled services). In some embodiments, the network service usage control policy is based on updates to service plan status. In some embodiments, the network service usage control policy is based on updates to service plan policies. In some embodiments, the network service usage control policy is based on availability of alternative networks. In some embodiments, the network service usage control policy is based on policy rules for selecting alternative networks. In some embodiments, the network service usage control policy is based on network busy state or availability state for alternative networks. In some embodiments, the network service usage control policy is based on specific network selection or preference policies for a given network service activity or set of network service activities.

In some embodiments, associating the network service usage activity with a network service usage control policy or a network service usage notification policy, includes dynamically associating based on one or more of the following: a network busy state, a time of day, a user input/preference, an associated service plan (e.g., 25 MB data plan, 5G data plan, or an unlimited data plan or other data/service usage plan), an application behavior, a messaging layer behavior, a power state of device, a device usage state, a time based criteria, availability of alternative networks, and a set of policy rules for selecting and/or controlling traffic on one or more of the alternative networks.

In some embodiments, a network service usage control policy (e.g., a network capacity controlled services policy) includes defining the network service usage control policy for one or more service plans, defining network access policy rules for one or more devices or groups of devices in a single or multi-user scenarios such as family and enterprise plans, defining network access policy rules for one or more users or groups of users, allowing or disallowing network access events or attempts, modulating the number of network access events or attempts, aggregating network access events or attempts into a group of access events or attempts, time windowing network access events or attempts, time windowing network access events or attempts based on the application or function being served by the network access events or attempts, time windowing network access events or attempts to pre-determined time windows, time windowing network access events or attempts to time windows where a measure of network busy state is within a range, assigning the allowable types of access events or attempts, assigning the allowable functions or applications that are allowed network access events or attempts, assigning the priority of one or more network access events or attempts, defining the allowable duration of network access events or attempts, defining the allowable speed of network access events or attempts, defining the allowable network destinations for network access events or attempts, defining the allowable applications for network access events or

attempts, defining the QoS rules for one or more network access events or attempts, defining or setting access policy rules for one or more applications, defining or setting access policy rules for one or more network destinations, defining or setting access policy rules for one or more devices, defining or setting access policy rules for one or more network services, defining or setting access policy rules for one or more traffic types, defining or setting access policy rules for one or more QoS classes, and defining or setting access policy rules based on any combination of device, application, network destination, network service, traffic type, QoS class, and/or other criteria/measures.

In some embodiments, a network service usage control policy (e.g., a network capacity controlled services policy) includes a traffic control policy. In some embodiments, the traffic control policy includes a traffic control setting. In some embodiments, the traffic control policy includes a traffic control/tier, and the traffic control/tier includes the traffic control setting. In some embodiments, the traffic control policy includes one or more of the following: block/allow settings, throttle settings, adaptive throttle settings, QoS class settings including packet error rate, jitter and delay settings, queue settings, and tag settings (e.g., for packet tagging certain traffic flows). In some embodiments, QoS class settings, include one or more of the following: throttle level, priority queuing relative to other device traffic, time window parameters, and hold or delay while accumulating or aggregating traffic into a larger stream/burst/packet/group of packets. In some embodiments, the traffic control policy includes filters implemented as indexes into different lists of policy settings (e.g., using cascade filtering techniques), in which the policy filters include one or more of the following: a network, a service plan, an application, a time of day, and a network busy state. For example, a two dimensional traffic control implementation scheme can be provided using a network busy state and/or a time of day as an index into a traffic control setting (e.g., a certain application's priority level can be increased or decreased based on a network busy state and/or time of day). In some embodiments, the traffic control policy is used for selecting the network from a list of available networks, blocking or reducing access until a connection is made to an alternative network, and/or modifying or replacing a network stack interface of the device to provide for intercept or discontinuance of network socket interface messages to applications or OS functions.

In some embodiments, a traffic control setting is selected based on the network service usage control policy. In some embodiments, the traffic control setting is implemented on the device based on the network service usage control policy. In some embodiments, the implemented traffic control setting controls traffic/traffic flows of a network capacity controlled service. In some embodiments, the traffic control setting is selected based on one or more of the following: a time of day, a day of week, a special time/date (e.g., a holiday or a network maintenance time/date), a network busy state, a priority level associated with the network service usage activity, a QoS class associated with the network service usage activity (e.g., emergency traffic), which network the network service activity is gaining access from, which networks are available, which network the network service activity is connected to, which base station or communication channel the network service activity is connected to, and a network dependent set of traffic control policies that can vary depending on which network the service activity is gaining access from (e.g., and/or various other criteria/measures as described herein). In some

embodiments, the traffic control setting includes one or more of the following: allow/block, delay, throttle, QoS class implementation, queue, tag, generate a user notification, random back off, clear to send received from a network element, hold for scheduled transmission time slot, selecting the network from the available networks, and blocking or reducing access until a connection is made to an alternative network. In some embodiments, the traffic control setting is selected based on a network capacity controlled services priority state of the network service usage activity and a network busy state. In some embodiments, the traffic control setting is selected based on a network capacity controlled services priority state of the network service usage activity and a network busy state and is global (e.g., the same) for all network capacity controlled services activities or varies based on a network service usage activity priority, user preferences or option selection, an application, a time based criteria, a service plan, a network the device or service activity is gaining access from, a redetermination of a network congestion state after adapting to a previously determined network busy state, and/or other criteria/measures as described herein.

In some embodiments, network capacity controlled services traffic (e.g., traffic flows) is differentially controlled for protecting network capacity. For example, various software updates for an OS and one or more applications on the device can be differentially controlled using the various techniques described herein. As another example, security/antimalware software (e.g., antivirus, firewall, content protection, intrusion detection/prevention, and/or other security/antimalware software) can be differentially controlled using the various techniques described herein. As yet another example, network backups/imaging, content downloads (e.g., exceeding a threshold individually and/or in aggregate, such as for image, music, video, eBook content, email attachments, content/media subscriptions, RSS/news feeds, text/image/video chat, software updates, and/or other content downloads) can be differentially controlled using the various techniques described herein.

For example, using the DAS for protecting network capacity techniques described herein an adaptive policy control for protecting network capacity can be provided. A network capacity controlled services list can be generated, updated, reported, and/or received by the device and stored on the device (e.g., the list can be based on adapted to the service plan associated with the device). If a monitored network service usage activity is not on the list, then the device can report the monitored network service usage activity to a network element (e.g., for a monitored network service usage activity that also exceeds a certain threshold, based on a network busy state, based on a time based criteria, and/or other criteria/measure). As an example, monitored network service usage activity can be reported if/when the monitored network service usage activity exceeds a data usage threshold (e.g., 50 MB total data usage per day, a socket opening frequency/rate, velocity of data usage at an instant in time, or more complicated thresholds over time, over peak periods, by content and time, by various other parameters/thresholds). As another example, the monitored network service usage activity can be reported based on testing of the network service usage behavior and/or application developer characterization input. The report can include information that identifies the network service usage activity and various network service usage parameters.

In some embodiments, a notification setting is selected based on a service usage notification policy. In some

embodiments, a notification setting includes a user notification setting (e.g., various user notifications settings as described above with respect to FIG. 18).

In some embodiments, classifying the network service usage activity further includes classifying the network service usage activity (e.g., using a usage threshold filter and/or cascading filter techniques) into one or more of a plurality of classification categories for differential network access control for protecting network capacity. In some embodiments, classifying the network service usage activity, further includes classifying the network service usage activity into one or more network capacity controlled services in which the network capacity controlled services include one or more of the following: applications requiring data network access, application software updates, applications requiring network information, applications requiring GPS or physical location, operating system software updates, security software updates, network based backups, email downloads, and a set of activities configured as network capacity controlled service activities based on a service profile and/or user input (e.g., and/or various other types of network service usage activities as described herein and as will now be apparent to one of ordinary skill in the art). For example, network capacity controlled services can include software updates for OS and applications, OS background network accesses, cloud synchronization services, RSS feeds & other background information feeds, browser/application/device behavior reporting, background email downloads, content subscription service updates and downloads (e.g., music/video downloads, news feeds), text/voice/video chat clients, security updates (e.g., antimalware updates), peer to peer networking application updates, inefficient network access sequences during frequent power cycling or power save state cycling, large downloads or other high bandwidth accesses, and greedy application programs that constantly/repeatedly access the network with small transmissions or requests for information. In some embodiments, a network capacity controlled services list is static, adaptive, generated using a service processor, received from a network element (e.g., service controller or service cloud), received from a network element (e.g., service controller or service cloud) and based at least in part on device activity reports received from the service processor, based on criteria set by pre-testing, report of behavior characterization performed by the application developer, and/or based at least in part on user input. In some embodiments, the network capacity controlled services list includes one or more network service activity background (QoS) classes.

In some embodiments, classifying the network service usage activity further includes classifying the network service usage activity based on one or more of the following: application or widget (e.g., Outlook, Skype, iTunes, Android email, weather channel weather widget, iCal, Firefox Browser, etc), application type (e.g., user application, system application/utility/function/process, OS application/utility/function/process, email, browser, widget, malware (such as a virus or suspicious process), RSS feed, device synchronization service, download application, network backup/imaging application, voice/video chat, peer to peer content application or other peer to peer application, streaming media feed or broadcast reception/transmission application, network meeting application, chat application or session, and/or any other application or process identification and categorization), OS/system function (e.g., any system application/utility/function/process and/or OS application/utility/function/process, such as a OS update and/or OS error reporting), modem function, network communication func-

91

tion (e.g., network discovery or signaling, EtherType messages, connection flow/stream/session set up or tear down, network authentication or authorization sequences, IP address acquisition, and DNS services), URL and/or domain, destination/source IP address, protocol, traffic type, socket (e.g., IP address, protocol, and/or port), socket address/label/identifier (e.g., port address/port number), content type (e.g., email downloads, email text, video, music, eBooks, widget update streams, and download streams), port (e.g., port number), QoS classification level, time of day, on peak or off peak, network time, network busy state, access network selected, service plan selected, user preferences, device credentials, user credentials, and/or status, modem power cycling or power state changes, modem authentication processes, modem link set up or tear down, modem management communications, modem software or firmware updates, modem power management information, device power state, and modem power state. In some embodiments, classifying the network service usage activity further includes associating the classified network service usage activity with an ID (e.g., an application ID, which can be, for example, a unique number, name, and/or signature). In some embodiments, classifying the network service usage activity further includes classifying the network service usage activity using a plurality of classification parameters, including one or more of the following: application ID, remote IP (e.g., URL, domain, and/or IP address), remote port, protocol, content type, a filter action class (e.g., network busy state class, QoS class, time of day, network busy state, and/or other criteria/measures), and access network selected. In some embodiments, classifying the network service usage activity further includes using a combination of parameters as discussed above to determine the classification of the network service usage activity.

In some embodiments, classifying the network service usage activity further includes classifying the network service usage activity as a network capacity controlled service, a non-network capacity controlled service, a blocked or disallowed service, and/or a not yet classified/identified service (e.g., unknown/yet to be determined classification or pending classification). In some embodiments, an application connection, OS connection, and/or other service activity is classified as a network capacity controlled service activity when the device has been inactive (e.g., or in a power save state) for a period of time (e.g., when the user has not interacted with it for a period of time, when it has not displayed user notification policy, and/or a user input has not been received for a period of time, and/or when a power save state is entered). In some embodiments, an application connection, OS connection, and/or other service activity is classified as a network capacity controlled service activity when the monitored network service usage activity exceeds a data usage threshold for more than one application connection, OS connection, and/or other service activity (e.g., aggregated data usage exceeds the data usage threshold); or for a specific application connection. In some embodiments, an application connection, OS connection, and/or other service activity is classified as a network capacity controlled service activity when the monitored network service usage activity exceeds a data usage threshold based on a predetermined list of one or more data usage limits, based on a list received from a network element, usage time limit (e.g., based on a period of time exceeding a usage limit), and/or based on some other usage related criteria/measures. In some embodiments, classifying the network service usage activity further includes classifying the network service usage activity as a network capacity controlled service based

92

on a network peak time, a network busy state, or a network connection to the device falls below a certain performance level (e.g., higher/lower priorities assigned based on various such criteria/other input/factors).

In some embodiments, one or more of the network capacity controlled services are associated with a different network access policy set for one or more networks and/or one or more alternative networks. In some embodiments, one or more of the network capacity controlled services are associated with a different notification policy set for one or more networks and/or one or more alternative networks. In some embodiments, the network capacity controlled services list is stored on the device. In some embodiments, the network capacity controlled services list is received/periodically updated from a network element and stored on the device. In some embodiments, the network capacity controlled services list includes network capacity controlled services, non-network capacity controlled services (e.g., foreground services or services based on various possibly dynamic criteria are not classified as network capacity controlled services), and an unclassified set of services (e.g., grey list including one or more network service activities pending classification based on further analysis and/or input, such as from a network element, service provider, and/or user). In some embodiments, the network capacity controlled services list is based on one or more of the following: predefined/predesignated (e.g., network, service plan, pre-test and/or characterized by an application developer) criteria; device assisted/based monitoring (e.g., using a service processor); network based monitoring (e.g., using a DPI gateway); network assisted analysis (e.g., based on device reports of DAS activity analysis). For example, the device can report device monitored network service usage activities (e.g., all monitored network service usage activities or a subset based on configuration, threshold, service plan, network, and/or user input) to the network element. As another example, the network element can update the network capacity controlled services list and send the updated list to the device. As yet another example, the network element can perform a statistical analysis of network service activities across a plurality of devices based on the device based and/or network based network service usage activity monitoring/reporting. In some embodiments, a network service usage activity is determined to be an active application or process (e.g., based on a user interaction with the device and/or network service usage activity, such as a pop-up and/or other criteria/measures).

In some embodiments, implementing traffic control for network capacity controlled services is provided using various techniques. In some embodiments, the device includes a service processor agent or function to intercept, block, modify, remove or replace UI messages, notifications or other UI communications generated by a network service activity that whose network service usage is being controlled or managed (e.g., using various measurement points as shown in and described with respect to FIGS. 12 and 13). For example, this technique can be used to provide for an improved user experience (e.g., to prevent an application that is being controlled for protecting network capacity from generating repeated and/or confusing messages/alerts to the user). In some embodiments, a network stack interface of the device is replaced or modified to provide for intercept or discontinuance of network socket interface messages to applications or OS functions or other functions/software.

In some embodiments, implementing traffic control for network capacity controlled services using DAS techniques is provided using various techniques in which the network

service usage activity is unaware of network capacity control (e.g., does not support an API or other interface for implementing network capacity control). For example, network service application messaging interface based techniques can be used to implement traffic control. Example network service application messaging interfaces include the following: network stack API, network communication stream/flow interface, network stack API messages, EtherType messages, ARP messages, and/or other messaging or other or similar techniques as will now be apparent to one of ordinary skill in the art in view of the various embodiments described herein. In some embodiments, network service usage activity control policies or network service activity messages are selected based on the set of traffic control policies or service activity messages that result in reduced or modified user notification by the service activity due to network capacity controlled service policies applied to the network service activity. In some embodiments, network service usage activity control policies or network service activity messages are selected based on the set of traffic control policies or service activity messages that result in reduced disruption of device operation due to network capacity controlled service activity policies applied to the network service activity. In some embodiments, network service usage activity control policies or network service activity messages are selected based on the set of traffic control policies or service activity messages that result in reduced disruption of network service activity operation due to network capacity controlled service activity policies applied to the network service activity. In some embodiments, implementing traffic control for network capacity controlled services is provided by intercepting opens/connects/writes. In some embodiments, implementing traffic control for network capacity controlled services is provided by intercepting stack API level or application messaging layer requests (e.g., socket open/send requests). For example, an intercepted request can be copied (e.g., to memory) and queued (e.g., delayed or throttled) or dropped (e.g., blocked). As another example, an intercepted request can be copied into memory and then a portion of the transmission can be retrieved from memory and reinjected (e.g., throttled). As yet another example, intercepting messaging transmissions can be parsed inline and allowed to transmit (e.g., allowed), and the transmission or a portion of the transmission can be copied to memory for classifying the traffic flow. In some embodiments, implementing traffic control for network capacity controlled services is provided by intercepting or controlling or modulating UI notifications. In some embodiments, implementing traffic control for network capacity controlled services is provided by killing or suspending the network service activity. In some embodiments, implementing traffic control for network capacity controlled services is provided by deprioritizing the process(es) associated with the service activity (e.g., CPU scheduling deprioritization).

In some embodiments, implementing traffic control for network capacity controlled services using DAS techniques for network service usage activities that are unaware of network capacity control is provided by emulating network API messaging (e.g., effectively providing a spoofed or emulated network API). For example, an emulated network API can intercept, modify, block, remove, and/or replace network socket application interface messages and/or EtherType messages (e.g., EWOULDBLOCK, ENETDOWN, ENETUNREACH, EHOSTDOWN, EHOSTUNREACH, EALREADY, EINPROGRESS, ECONNREFUSED, EINPROGRESS, ETIMEDOUT, and/or other such

messages). As another example, an emulated network API can modify, swap, and/or inject network socket application interface messages (socket(), connect(), read(), write(), close(), and other such messages) that provide for control or management of network service activity service usage behavior. As yet another example, before a connection is allowed to be opened (e.g., before a socket is opened), transmission, or a flow/stream is initiated, it is blocked and a message is sent back to the application (e.g., a reset message in response to a sync request or another message that the application will understand and can interpret to indicate that the network access attempt was not allowed/ blocked, that the network is not available, and/or to try again later for the requested network access). As yet another example, the socket can be allowed to open but after some point in time (e.g., based on network service usage, network busy state, time based criteria, and/or some other criteria/ measure), the stream is blocked or the socket is terminated. As yet another example, time window based traffic control techniques can be implemented (e.g., during non-peak, not network busy state times), such as by allowing network access for a period of time, blocking for a period of time, and then repeating to thereby effectively spread the network access out either randomly or deterministically. Using these techniques, an application that is unaware of network capacity control based traffic control can send and receive standard messaging, and the device can implement traffic controls based on the network capacity control policy using messaging that the network service usage activity (e.g., application or OS or software function) can understand and will respond to in a typically predictable manner as would now be apparent to one of ordinary skill in the art.

In some embodiments, implementing traffic control for network capacity controlled services using DAS techniques is provided using various techniques in which the network service usage activity is aware of network capacity control (e.g., the network service usage activity supports an API or other interface for implementing network capacity control). For example, a network access API as described herein can be used to implement traffic control for network capacity controlled services. In some embodiments, the API facilitates communication of one or more of the following: network access conditions, network busy state or network availability state of one or more networks or alternative networks, one or more network capacity controlled service policies (e.g., the network service can be of a current network access setting, such as allow/block, throttle, queue, scheduled time/time slot, and/or defer, which can be based on, for example, a current network, a current network busy state, a time based criteria, a service plan, a network service classification, and/or other criteria/measures), a network access request from a network service activity, a query/ polled request to a network service activity, a network access grant to a network service activity (e.g., including a priority setting and/or network capacity controlled service classification, a scheduled time/time slot, an alternative network, and/or other criteria/measures), a network busy state or a network availability state or a network QoS state.

In some embodiments, implementing traffic control for network capacity controlled services using network assisted/ based techniques is provided using various techniques in which the network service usage activity is unaware of network capacity control (e.g., does not support an API or other interface for implementing network capacity control). In some embodiments, DPI based techniques are used to

control network capacity controlled services (e.g., to block or throttle network capacity controlled services at a DPI gateway).

In some embodiments, implementing traffic control for network capacity controlled services using network assisted/ based techniques is provided using various techniques in which the network service usage activity is aware of network capacity control (e.g., does support an API or other interface for implementing network capacity control). In some embodiments, the application/messaging layer (e.g., a network API as described herein) is used to communicate with a network service activity to provide associated network capacity controlled service classifications and/or priorities, network busy state information or network availability of one or more networks or alternative networks, a network access request and response, and/or other criteria/ measures as similarly described herein.

In some embodiments, DAS for protecting network capacity includes implementing a service plan for differential charging based on network service usage activities (e.g., including network capacity controlled services). In some embodiments, the service plan includes differential charging for network capacity controlled services. In some embodiments, the service plan includes a cap network service usage for network capacity controlled services. In some embodiments, the service plan includes a notification when the cap is exceeded. In some embodiments, the service plan includes overage charges when the cap is exceeded. In some embodiments, the service plan includes modifying charging based on user input (e.g., user override selection as described herein, in which for example, overage charges are different for network capacity controlled services and/or based on priority levels and/or based on the current access network). In some embodiments, the service plan includes time based criteria restrictions for network capacity controlled services (e.g., time of day restrictions with or without override options). In some embodiments, the service plan includes network busy state based criteria restrictions for network capacity controlled services (e.g., with or without override options). In some embodiments, the service plan provides for network service activity controls to be overridden (e.g., one time, time window, usage amount, or permanent) (e.g., differentially charge for override, differentially cap for override, override with action based UI notification option, and/or override with UI setting). In some embodiments, the service plan includes family plan or multi-user plan (e.g., different network capacity controlled service settings for different users). In some embodiments, the service plan includes multi-device plan (e.g., different network capacity controlled service settings for different devices, such as smart phone v. laptop v. net book v. eBook). In some embodiments, the service plan includes free network capacity controlled service usage for certain times of day, network busy state(s), and/or other criteria/measures. In some embodiments, the service plan includes network dependent charging for network capacity controlled services. In some embodiments, the service plan includes network preference/ prioritization for network capacity controlled services. In some embodiments, the service plan includes arbitration billing to bill a carrier partner or sponsored service partner for the access provided to a destination, application, or other network capacity controlled service. In some embodiments, the service plan includes arbitration billing to bill an application developer for the access provided to a destination, application or other network capacity controlled service.

In some application scenarios, excess network capacity demand can be caused by modem power state changes on the

device. For example, when an application or OS function attempts to connect to the network for any reason when the modem is in a power save state wherein the modem is not connected to the network, it can cause the modem to change power save state, reconnect to the network, and then initiate the application network connection. In some cases, this can also cause the network to re-initiate a modem connection session (e.g., PPP session) which in addition to the network capacity consumed by the basic modem connection also consumes network resources for establishing the PPP session. Accordingly, in some embodiments, network service usage activity control policies are implemented that limit or control the ability of applications, OS functions, and/or other network service usage activities (e.g., network capacity controlled services) from changing the modem power control state or network connection state. In some embodiments, a service usage activity is prevented or limited from awakening the modem, changing the power state of the modem, or causing the modem to connect to the network until a given time window is reached. In some embodiments, the frequency a service usage activity is allowed to awakening the modem, changing the power state of the modem, or causing the modem is limited. In some embodiments, a network service usage activity is prevented from awakening the modem, changing the power state of the modem, or causing the modem until a time delay has passed. In some embodiments, a network service usage activity is prevented from awakening the modem, changing the power state of the modem, or causing the modem until multiple network service usage activities require such changes in modem state, or until network service usage activity is aggregated to increase network capacity and/or network resource utilization efficiency. In some embodiments, limiting the ability of a network service usage activity to change the power state of a modem includes not allowing the activity to power the modem off, place the modem in sleep mode, or disconnect the modem from the network. In some embodiments, these limitations on network service usage activity to awaken the modem, change the power state of the modem, or cause the modem to connect to a network are set by a central network function (e.g., a service controller or other network element/ function) policy communication to the modem. In some embodiments, these power control state policies are updated by the central network function.

FIG. 24 depicts a diagram of a network capacity protection system 2400 utilizing device-assisted services (DAS). The system 2400 includes wireless devices 2402-1 to 2402-N (referred to collectively as the wireless devices 2402), wireless networks 2404-1 to 2404-N (referred to collectively as the wireless networks 2404), a network traffic analysis engine 2406, a network service usage classification engine 2408, and a differential network access control engine 2410.

The wireless devices 2402 will at a minimum include a processor, memory (though the memory could be implemented in the processor), a radio, and a radio interface (though the radio interface could be implemented as "part of" the radio). In order to make the wireless devices 2402 useful, they will typically have at least one input device and at least one output device, including input and output interfaces, if applicable.

The wireless devices 2402 can be implemented as stations. A station, as used herein, may be referred to as a device with a media access control (MAC) address and a physical layer (PHY) interface to the wireless medium that comply with, e.g., the IEEE 802.11 standard. A station can be described as "IEEE 802.11-compliant" when compliance

with the IEEE 802.11 standard is intended to be explicit. (I.e., a device acts as described in at least a portion of the IEEE 802.11 standard.) One of ordinary skill in the relevant art would understand what the IEEE 802.11 standard comprises today and that the IEEE 802.11 standard can change over time, and would be expected to apply techniques described in this paper in compliance with future versions of the IEEE 802.11 standard if an applicable change is made. IEEE Std 802.11™-2007 (Revision of IEEE Std 802.11-1999) is incorporated by reference. IEEE 802.11k-2008, IEEE 802.11n-2009, IEEE 802.11p-2010, IEEE 802.11r-2008, IEEE 802.11w-2009, and IEEE 802.11y-2008 are also incorporated by reference.

In alternative embodiments, one or more of the wireless devices **2402** may comply with some other standard or no standard at all, and may have different interfaces to a wireless or other medium. It should be noted that not all standards refer to wireless devices as “stations,” but where the term is used in this paper, it should be understood that an analogous unit will be present on all applicable wireless networks. Thus, use of the term “station” should not be construed as limiting the scope of an embodiment that describes wireless devices as stations to a standard that explicitly uses the term, unless such a limitation is appropriate in the context of the discussion.

The wireless networks **2404** will typically include an internetworking unit (IWU) that interconnects wireless devices on the relevant one of the wireless networks **2404** with another network, such as a wired LAN. The IWU is sometimes referred to as a wireless access point (WAP). In the IEEE 802.11 standard, a WAP is also defined as a station. Thus, a station can be a non-WAP station or a WAP station. In a cellular network, the WAP is often referred to as a base station.

The wireless networks **2404** can be implemented using any applicable technology, which can differ by network type or in other ways. The wireless networks **2404** can be of any appropriate size (e.g., metropolitan area network (MAN), personal area network (PAN), etc.). Broadband wireless MANs may or may not be compliant with IEEE 802.16, which is incorporated by reference. Wireless PANs may or may not be compliant with IEEE 802.15, which is incorporated by reference. The wireless networks **2404** can be identifiable by network type (e.g., 2G, 3G, WiFi), service provider, WAP/base station identifier (e.g., WiFi SSID, base station and sector ID), geographic location, or other identification criteria.

The wireless networks **2404** may or may not be coupled together via an intermediate network. The intermediate network can include practically any type of communications network, such as, by way of example but not limitation, the Internet, a public switched telephone network (PSTN), or an infrastructure network (e.g., private LAN). The term “Internet” as used herein refers to a network of networks which uses certain protocols, such as the TCP/IP protocol, and possibly other protocols such as the hypertext transfer protocol (HTTP) for hypertext markup language (HTML) documents that make up the World Wide Web (the web).

In the example of FIG. 24, the network traffic analysis engine **2406** is coupled to the wireless device **2402-1**. In a specific implementation, the network traffic analysis engine **2406** is implemented on a server and is coupled to the wireless device **2402-1** through the Internet. However, at least a portion of the network traffic analysis engine **2406** can alternatively be implemented on the wireless device **2402-1**, with or without a connection to a server that

includes another portion (e.g., a server portion) of the network traffic analysis engine **2406**.

As used in this paper, an engine includes a dedicated or shared processor and, typically, firmware or software modules that are executed by the processor. Depending upon implementation-specific or other considerations, an engine can be centralized or its functionality distributed. An engine can include special purpose hardware, firmware, or software embodied in a computer-readable medium for execution by the processor. As used in this paper, a computer-readable medium is intended to include all mediums that are statutory (e.g., in the United States, under 35 U.S.C. 101), and to specifically exclude all mediums that are non-statutory in nature to the extent that the exclusion is necessary for a claim that includes the computer-readable medium to be valid. Known statutory computer-readable mediums include hardware (e.g., registers, random access memory (RAM), non-volatile (NV) storage, to name a few), but may or may not be limited to hardware.

The network traffic analysis engine **2406** analyzes a subset of traffic between the wireless device **2402-1** and a source or destination. The analyzed traffic may or may not be limited to a network segment, such as between a cellular phone and a base station. The network traffic analysis engine **2406** can analyze traffic for a subset of devices in the wireless network **2404-1** service area. The analyzed traffic may or may not be limited to subscribers.

In the example of FIG. 24, the network service usage classification engine **2408** is coupled to the network traffic analysis engine **2406**. In a specific implementation, the network service usage classification engine **2408** is implemented on a server, which may or may not be the same server on which the network traffic analysis engine **2406** is implemented. However, at least a portion of the network service usage classification engine **2408** can alternatively be implemented on the wireless device **2402-1**, with or without a connection to a server that includes another portion (e.g., a server portion) of the network service usage classification engine **2408**.

The network service usage classification engine **2408** can categorize traffic based upon the service class (e.g., conversational, streaming, interactive, background, or some other service class) requested or needed for a service. The categorization facilitates identification of a snapshot of service class use at a given time, and, in some implementations, predictions of future service class use based upon the snapshot (e.g., making an assumption that future service class use is at least somewhat related to service class use of the snapshot), historical data analysis (e.g., service class usage at certain times of day/days of the week), identification of trends, or the use of some other predictive technology.

In the example of FIG. 24, the differential network access control engine **2410** is coupled to the network service usage classification engine **2408**. In a specific implementation, the network access control engine **2410** is implemented on a server, which may or may not be the same server on which the network traffic analysis engine **2406** and/or the network service usage classification engine **2408** are implemented. However, at least a portion of the network access control engine **2410** can alternatively be implemented on the wireless device **2402-1**, with or without a connection to a server that includes another portion (e.g., a server portion) of the network access control engine **2410**.

The differential network access control engine **2410** uses the predicted service class use from the network service usage classification engine **2408** to dynamically adjust

resources allocated to service classes. For example, the differential network access control engine **2410** can perform a service class availability assessment to determine whether service class capacity for service classes on a channel are sufficient for predicted service usage, and either add resources if service class availability is insufficient for predicted service usage or reduce resources if service class availability is more than sufficient for predicted service usage.

Alternatively, the differential network access control engine **2410** can instead or in addition control applications on devices such that the applications change service usage levels or delay consumption of wireless resources (e.g., by delaying software updates until more resources become available). In an embodiment, a service usage control policy is implemented on the wireless device **2402-1**. This may be necessary in some cases to ensure the wireless device **2402-1** can adjust application settings that are normally fixed, optimize network service usage activation based on network state (e.g., if the network is busy), control over-the-air software updates, throttle resource-hungry applications, manage network service usage requests from repeated power down modes, keep PPP sessions active, or otherwise facilitate dynamic service class adjustments or other device behavior.

In a specific implementation, subscribers can be incented to change service classes by, for example, charging more for higher service classes. The differential network access control engine **2410** can send a notification of differential charges for service classes. Alternatively, the charges could be implemented via subscriber account settings or preferences.

In the example of FIG. **24**, in operation, the network traffic analysis engine **2406** analyzes traffic from one or more devices, including the wireless device **2402-1**. The network service usage classification engine **2408** predicts the amount of resources needed for service classes, and the differential network access control engine **2410** dynamically allocates resources on an as-needed basis to adjust the service classes that are available to the one or more devices and/or adjusts device behavior for a subset of the one or more devices or instructs a subset of the one or more devices to adjust device behavior such that the device consumes service class-specific resources in accordance with an access control policy appropriate for the resources allocated to the applicable service classes.

FIG. **25** depicts a diagram an example of a differential access control notification system **2500**. In the example of FIG. **25**, the system **2500** includes a network service usage analysis engine **2502**, a network service usage classification engine **2504**, a differential network access control engine **2506**, a network service usage control policy datastore **2508**, a network service usage notification engine **2510**, a user interface **2512**, and a service plan update engine **2514**.

In the example of FIG. **25**, the network service usage analysis engine **2502** analyzes network service usage activity. The analysis can include an analysis of traffic sent to or from a device, an application running on a device, a request for services, or other analysis that is informative of past, current, or future network service usage. For example, the network service usage activity can include an attempt to download or load an application onto the communications device, an attempt to execute the network service activity or the network service usage activity attempts to access the network, meeting or exceeding a network service usage threshold, satisfying a network service usage pre-condition, an update to a network capacity controlled service activity

classification list, an update to a network capacity controlled services policy, and a network message is sent to the device triggering the notification, to name several by way of example. The analysis can occur on a non-WAP station, a WAP or base station, a server, or partly on one of these devices or some other device.

In the example of FIG. **25**, the network service usage classification engine **2504** is coupled to the network service usage analysis engine **2502**. The network service usage classification engine **2504** classifies the analyzed network service usage into one or more service classes. The classification can occur on a non-WAP station, a WAP or base station, a server, or partly on one of these devices or some other device.

In the example of FIG. **25**, the differential network access control engine **2506** is coupled to the network service usage classification engine **2504**. The differential network access control engine **2506** determines network access parameters using the service classes associated with the network service usage activity and network service usage control policies stored in the network service usage control policy datastore **2508**. The determination can occur on a non-WAP station, a WAP or base station, a server, or partly on one of these devices or some other device. The network service usage control policy datastore **2508** can be implemented on a wireless device, but it is also possible to maintain the datastore remotely relative to the device (e.g., on a server). In a specific implementation, even if the network service usage control policy datastore **2508** is maintained remotely relative to the wireless device, the wireless device will still have a network service usage control policy implemented.

A datastore can be implemented, for example, as software embodied in a physical computer-readable medium on a general- or specific-purpose machine, in firmware, in hardware, in a combination thereof, or in an applicable known or convenient device or system. Datastores in this paper are intended to include any organization of data, including tables, comma-separated values (CSV) files, traditional databases (e.g., SQL), or other applicable known or convenient organizational formats. Datastore-associated components, such as database interfaces, can be considered "part of" a datastore, part of some other system component, or a combination thereof, though the physical location and other characteristics of datastore-associated components is not critical for an understanding of the techniques described in this paper.

Datastores can include data structures. As used in this paper, a data structure is associated with a particular way of storing and organizing data in a computer so that it can be used efficiently within a given context. Data structures are generally based on the ability of a computer to fetch and store data at any place in its memory, specified by an address, a bit string that can be itself stored in memory and manipulated by the program. Thus some data structures are based on computing the addresses of data items with arithmetic operations; while other data structures are based on storing addresses of data items within the structure itself. Many data structures use both principles, sometimes combined in non-trivial ways. The implementation of a data structure usually entails writing a set of procedures that create and manipulate instances of that structure.

In the example of FIG. **25**, the network service usage notification engine **2510** is coupled to the differential network access control engine **2506** and the network service usage control policy datastore **2508**. The network service usage notification engine **2510** is configured to generate a notification sufficient to indicate relevant access control

101

information. For example, the notification could indicate what network service usage activities are network capacity controlled services, the type of network service policy in effect for one or more network capacity controlled services, that a network service activity belongs to a network capacity controlled services classification, that a service activity that is classified as network capacity controlled services classification can have the classification changed, that if the service class is changed for the network service activity that the associated network service usage charges will change, a service plan upgrade/downgrade offer, and an offer for a service plan that provides discounts and/or incentives for responding to one or more user notifications for protecting network capacity, to name several by way of example.

The notification may or may not also include a user preference selection. For example, the notification could include a provision to associate a network service usage control policy with the network service usage activity, an over-ride option for selecting the network service usage control policy, a modify option to select the service usage control policy, and a select option to select a new service plan, to name several by way of example. Other examples include network service usage activity information for one or more network capacity controlled services, predicted network service usage activity information for one or more network capacity controlled services, an option for obtaining more information about the network service usage of the network service usage activity, a message that the network service usage activity may result in network service usage that exceeds a threshold for a service plan associated with the device, an option to review or select an alternative service plan, an acknowledgement request, and an option to submit the acknowledgement request, to name several more by way of example.

In the example of FIG. 25, the user interface 2512 is coupled to the network service usage notification engine 2510. It may be noted that notifications can be disposed of by consulting user preferences (e.g., when a user indicates that maximum performance or minimum cost should be automatically selected). However, unless subscriber preferences are set as a default, a user is likely to have notifications displayed in the UI 2512. The notification can be in an applicable known or convenient form, such as SMS, email, a popup window, or the like. To the extent a response is permitted, a user can input a response to the notification using an input device (not shown).

In the example of FIG. 25, the service plan update engine 2514 is coupled to the UI 2512. As was previously mentioned, the UI can be bypassed because of, e.g., user preferences that are determinative of a selection provided in the notification. Regardless of how the selection associated with the notification is made, the service plan update engine 2514 can update a service plan, network service usage control policy, user preferences, or other parameters in accordance with the selection. The service plan update engine 2514 can also update accounting if costs accrue.

FIG. 26 depicts an example of a computer system 2600 on which techniques described in this paper can be implemented. The computer system 2600 may be a conventional computer system that can be used as a client computer system, such as a wireless client or a workstation, or a server computer system. The computer system 2600 includes a computer 2602, I/O devices 2604, and a display device 2606. The computer 2602 includes a processor 2608, a communications interface 2610, memory 2612, display controller 2614, non-volatile storage 2616, and I/O controller

102

2618. The computer 2602 may be coupled to or include the I/O devices 2604 and display device 2606.

The computer 2602 interfaces to external systems through the communications interface 2610, which may include a modem or network interface. It will be appreciated that the communications interface 2610 can be considered to be part of the computer system 2600 or a part of the computer 2602. The communications interface 2610 can be an analog modem, ISDN modem, cable modem, token ring interface, satellite transmission interface (e.g. "direct PC"), or other interfaces for coupling a computer system to other computer systems.

The processor 2608 may be, for example, a conventional microprocessor such as an Intel Pentium microprocessor or Motorola power PC microprocessor. The memory 2612 is coupled to the processor 2608 by a bus 2670. The memory 2612 can be Dynamic Random Access Memory (DRAM) and can also include Static RAM (SRAM). The bus 2670 couples the processor 2608 to the memory 2612, also to the non-volatile storage 2616, to the display controller 2614, and to the I/O controller 2618.

The I/O devices 2604 can include a keyboard, disk drives, printers, a scanner, and other input and output devices, including a mouse or other pointing device. The display controller 2614 may control in the conventional manner a display on the display device 2606, which can be, for example, a cathode ray tube (CRT) or liquid crystal display (LCD). The display controller 2614 and the I/O controller 2618 can be implemented with conventional well known technology.

The non-volatile storage 2616 is often a magnetic hard disk, an optical disk, or another form of storage for large amounts of data. Some of this data is often written, by a direct memory access process, into memory 2612 during execution of software in the computer 2602. One of skill in the art will immediately recognize that the terms "machine-readable medium" or "computer-readable medium" includes any type of storage device that is accessible by the processor 2608 and also encompasses a carrier wave that encodes a data signal.

The computer system 2600 is one example of many possible computer systems which have different architectures. For example, personal computers based on an Intel microprocessor often have multiple buses, one of which can be an I/O bus for the peripherals and one that directly connects the processor 2608 and the memory 2612 (often referred to as a memory bus). The buses are connected together through bridge components that perform any necessary translation due to differing bus protocols.

Network computers are another type of computer system that can be used in conjunction with the teachings provided herein. Network computers do not usually include a hard disk or other mass storage, and the executable programs are loaded from a network connection into the memory 2612 for execution by the processor 2608. A Web TV system, which is known in the art, is also considered to be a computer system, but it may lack some of the features shown in FIG. 26, such as certain input or output devices. A typical computer system will usually include at least a processor, memory, and a bus coupling the memory to the processor.

In addition, the computer system 2600 is controlled by operating system software which includes a file management system, such as a disk operating system, which is part of the operating system software. One example of operating system software with its associated file management system software is the family of operating systems known as Windows® from Microsoft Corporation of Redmond,

103

Wash., and their associated file management systems. Another example of operating system software with its associated file management system software is the Linux operating system and its associated file management system. The file management system is typically stored in the non-volatile storage 2616 and causes the processor 2608 to execute the various acts required by the operating system to input and output data and to store data in memory, including storing files on the non-volatile storage 2616.

FIG. 27 depicts a diagram of an example of a system 2700 for application-specific differential network access control. In the example of FIG. 27, the system 2700 includes a network service consuming application 2702, a network service usage analysis engine 2704, an application behavior datastore 2706, a network service usage classification engine 7708, an application traffic prioritization engine 2710, a network service usage control policy datastore 2712, a differential network access control engine 2714, an application traffic cache 2716, an application traffic override engine 2718, and a network interface 2720. The system 2700 is intended to represent a specific implementation of techniques described previously in this paper for illustrative purposes. The techniques may be applicable to an applicable known or convenient (wired or wireless) device for which there is a motivation to control network service usage.

In the example of FIG. 27, the network service consuming application 2702 is an application that is implemented on a device. In an expected use, the application is a software application stored at least in part in memory on a wireless device, though kernel-level instructions could be implemented as firmware or even hardware. The application can be referred to as “running” on the device or as being “executed” by the device in accordance with known uses of those terms. Wireless media are known to have more bandwidth constraints, which is why a wireless device is an expected use, though the technique may be applicable to wired devices in certain situations.

In the example of FIG. 27, the network service usage analysis engine 2704 is coupled to the network service consuming application 2702. The network service usage analysis engine 2704 analyzes traffic from the network service consuming application 2702 and stores relevant data in the application behavior datastore 2706. The data can include all traffic that is sent by the application, or a subset of the traffic (e.g., that which has a certain QoS classification or priority, that which has high resource consumption due to frequent transmission from the application, that which is sent to a particular destination, etc.) The data can also include traffic that is received for the application. The application behavior datastore 2706 can alternatively or in addition be implemented as a traffic source/destination datastore, which can be valuable if differential access control is based upon the source and/or destination of traffic. The application behavior datastore 2706 includes data structures (e.g., records) representative of data that is organized with implementation-specific granularity. For example, the data structures could be representative of frames (L2), packets (L3), or messages. (It may be noted that the term “packets” is often used to mean collections of data that are not limited to L3.) The desired granularity may depend upon where the network service usage analysis engine 2704 is located. Whether the data structures are changed over time (e.g., to change data associated with a record), replaced as records age, or maintained as historical data is also implementation-specific.

In the example of FIG. 27, the network service usage classification engine 2708 is coupled to the network service

104

usage analysis engine 2704 and the application behavior datastore 2706. The network service usage classification engine 2708 can categorize the traffic stored in the application behavior datastore 2706 based on, e.g., network type, time of day, connection cost, whether home or roaming, network busy state, QoS, and whether the particular service usage activity is in foreground of user interaction or in the background of user interaction, or other characteristics that are obtained from network service usage analysis or through other means. Classification rules can include, for example, examining if one or more of the following has taken place within a specified period of time: user has interacted with the device, user has interacted with the service usage activity, user has picked up the device, service usage activity UI content is in the foreground of the device UI, audio or video information is being played by the service usage activity, a certain amount of data has been communicated by the service usage activity, service usage activity is or is not on a foreground or background service list. Rules that define which service usage activities to classify as, e.g., background service usage activities can be user-selected, set by a service provider, or through some other applicable means.

Advantageously, the network service usage analysis engine 2704 can examine a particular service usage activity and the network service usage classification engine 2708 can determine if the particular service usage activity fits a set of one or more classification rules that define the particular service usage activity as, e.g., a background service usage activity.

In the example of FIG. 27, the application traffic prioritization engine 2710 uses a policy stored in the network service usage control policy datastore 2712 to determine an appropriate prioritization for traffic to and/or from the network service consuming application 2702. Prioritization can enable the system 2700 to fine-tune the amount of network resources consumed by the network service consuming application 2702, or the rate of network resource consumption. The control policy can require applications to throttle network resource consumption, prohibit the use of network resources by certain applications, etc.

Advantageously, the application traffic prioritization engine 2710 can determine a particular service usage activity has a particular characteristic, such as being a background service usage activity. This can involve checking whether a condition is satisfied.

In the example of FIG. 27, the differential network access control engine 2714 is coupled to the application traffic prioritization engine 2710 and the network service usage control policy datastore 2712. The differential network access control engine 2714 causes the network service consuming application 2702 traffic to be queued in the application traffic cache 2716. (If no throttling is required to follow the control policy, of course, the traffic need not be cached anywhere other than is typical, such as in an output buffer.) The application traffic cache 2716 is intended to represent a cache that is implemented on top of an output buffer or other standard caching device, and is used by the differential network access control engine 2714 to facilitate control over “rogue” applications, applications having anomalous behavior, or applications that must otherwise be controlled to conform with the control policy.

Advantageously, the differential network access control engine can restrict network access of a particular service usage activity when a condition is satisfied, such as when the service usage activity is a background activity.

In the example of FIG. 27, the application traffic override engine 2718 is coupled to the differential network access

control engine **2714** and the application traffic cache **2716**. The application traffic override engine **2718** enables a user or device to deviate from the control policy. Such deviation can be prompted by, for example, an incentive offer or a notification of cost.

In an illustrative example, the device **2700** blocks chatter for an application running in the background that is attempting to report device or user behavior. The application traffic prioritization engine **2710** determines that the chatter has zero priority, such that the network service consuming application **2702** is prevented from consuming any resources. The user can be sent a notification by the application traffic override engine **2718** that their control policy prohibits the application from consuming network resources, but that the user can opt to deviate from the control policy if they are willing to pay for the consumed resources. If the user is willing to pay for the resources, traffic can be sent at a certain rate from the application traffic cache **2716** through the network interface **2720**, or perhaps sent without using the application traffic cache **2716**.

As another illustrative example, the device **2700** could identify application traffic as a software update. The differential network access control engine **2714** may determine that software updates can be received at a throttled rate (perhaps even slower than the lowest QoS categorization). The application traffic override engine **2718** can receive an indication from the user, from user preferences, service provider settings, or the like that the updates can ignore the control policy for a particular application (or for all applications).

Advantageously, the control policy can set up a priority to communicate cached elements, set minimum update frequencies, provide control policy overrides (typically for payment), or the like to fine-tune differential network access control policies. This can enable the system **2700** to encourage certain behavior, such as sending low QoS traffic when it is cheaper (e.g., when the network does not have a busy state, at historically low-use times of day, when on a certain type of network, such as Wi-Fi, as opposed to another, such as cellular, etc.).

FIG. **28** depicts an example of a system **2800** for flow tracking. In the example of FIG. **28**, the system **2800** includes a network **2802**, a content datastore **2804**, a network element **2806**, and a service policy implemented device **2808**.

In the example of FIG. **28**, the network **2802** is intended to include an applicable communications network such as the Internet, a public switched telephone network (PSTN), an infrastructure network (e.g., private LAN), or some other network that is capable of acting as a link between the various components depicted in FIG. **2**. The term "Internet" as used herein refers to a network of networks which uses certain protocols, such as the TCP/IP protocol, and possibly other protocols such as the hypertext transfer protocol (HTTP) for hypertext markup language (HTML) documents that make up the World Wide Web (the web). A PSTN can include wired or wireless (e.g., 4G/3G/2G) network operated by, for example, a central provider. An infrastructure network that offers wireless connectivity can include wired and wireless devices in communication with wireless access points (WAPs). The wired and wireless devices can include various network equipment including by way of example but not limitation a cable network head end, a DSL network DSLAM, a fiber network aggregation node, and/or a satellite network aggregation node.

The network **2802**, if it includes a wireless network, will typically include an internetworking unit (IWU) that inter-

connects wireless devices on the network **2802** with another network, such as a wired LAN on the network **2802**. The IWU is sometimes referred to as a wireless access point (WAP). In the IEEE 802.11 standard, a WAP is also defined as a station. Thus, a station can be a non-WAP station or a WAP station. In a cellular network, the WAP is often referred to as a base station. The network **2802** can be implemented using an applicable technology, which can differ by network type or in other ways. The network **2802** can include networks of any appropriate size (e.g., metropolitan area network (MAN), personal area network (PAN), etc.). Broadband wireless MANs may or may not be compliant with IEEE 802.16, which is incorporated by reference. Wireless PANs may or may not be compliant with IEEE 802.15, which is incorporated by reference. Networks can be identifiable by network type (e.g., 2G, 3G, WiFi), service provider, WAP/base station identifier (e.g., WiFi SSID, base station and sector ID), geographic location, or other identification criteria.

In the example of FIG. **28**, the network **2802** is coupled to the content datastore **2804**. The content datastore **2804** is intended to illustrate any applicable content that is accessed by the service policy implemented device **2808**. A datastore can be implemented, for example, as software embodied in a physical computer-readable medium on a general- or specific-purpose machine, in firmware, in hardware, in a combination thereof, or in an applicable known or convenient device or system. Datastores in this paper are intended to include any organization of data, including tables, comma-separated values (CSV) files, traditional databases (e.g., SQL), or other applicable known or convenient organizational formats. Datastore-associated components, such as database interfaces, can be considered "part of" a datastore, part of some other system component, or a combination thereof, though the physical location and other characteristics of datastore-associated components is not critical for an understanding of the techniques described in this paper.

Datastores can include data structures. As used in this paper, a data structure is associated with a particular way of storing and organizing data in a computer so that it can be used efficiently within a given context. Data structures are generally based on the ability of a computer to fetch and store data at any place in its memory, specified by an address, a bit string that can be itself stored in memory and manipulated by the program. Thus some data structures are based on computing the addresses of data items with arithmetic operations; while other data structures are based on storing addresses of data items within the structure itself. Many data structures use both principles, sometimes combined in non-trivial ways. The implementation of a data structure usually entails writing a set of procedures that create and manipulate instances of that structure.

In the example of FIG. **28**, the network element **2806** is coupled to the network **2802** and includes hardware **2810** and a network stack **2812**. In operation, the network stack **2812** can be implemented as an engine on the hardware **2810**. As used in this paper, an engine includes a dedicated or shared processor and, typically, firmware or software modules that are executed by the processor. Depending upon implementation-specific or other considerations, an engine can be centralized or its functionality distributed. An engine can include special purpose hardware, firmware, or software embodied in a computer-readable medium for execution by the processor. As used in this paper, a computer-readable medium is intended to include all mediums that are statutory (e.g., in the United States, under 35 U.S.C. 101), and to

107

specifically exclude all mediums that are non-statutory in nature to the extent that the exclusion is necessary for a claim that includes the computer-readable medium to be valid. Known statutory computer-readable mediums include hardware (e.g., registers, random access memory (RAM), non-volatile (NV) storage, to name a few), but may or may not be limited to hardware.

In the example of FIG. 28, the service policy implemented device 2808 is coupled to the network element 2806. As the name suggests, the service policy implemented device 2808 has an implemented service policy. Cellular phones often have implemented service policies, such as those described previously in this paper, but the service policy implemented device 2808 need not necessarily be limited to a cellular phone implementation. In an embodiment, the service policy implemented device 2808 includes any applicable computing device on which a service policy is implemented. The service policy implemented device 2808 can implement device-assisted services as described in this paper.

The service policy implemented device 2808 includes an initiator 2814, an optional control application 2816, and a proxy 2818. In operation, the initiator 2814, optional control application 2816, and proxy 2818 can be implemented as engines. In an instance and/or embodiment in which the optional control application 2816 is not present, the initiator 2814 can invoke the proxy 2818 through, e.g., a media service API. Where the optional control application 2816 is not necessary, the initiator 2814 will typically include an app that is capable of its own rendering or control. The optional control application 2816 can include a rendering or control application that invokes the proxy 2818 on behalf of the initiator 2814. This can be useful for a requesting app that does not include rendering or control capabilities, such as an audio file. In this particular example, the optional control application 2816 can include a media player that has been registered to handle attempts to certain audio files, much like a program on a personal computer can be registered to handle files of certain types (e.g., on a personal computer, an attempt to open a Word document results in launching Microsoft Word to open the Word document because Microsoft Word has been registered to handle files of that type on the personal computer). Proxies 2818 can include download, media (e.g., streaming audio, streaming video, etc.), VoIP, instant messaging (IM), video conference/IM (including, e.g., a 2-way video client), backup, or other managers/services.

In operation, traffic can be tagged at various points. For example, traffic can be tagged at an activity stack between the initiator 2814 and the optional control application 2816. As another example, traffic can be tagged at a manager/service API between the optional control application 2816 and the proxy 2818 (or in an instance or embodiment that does not include the optional control application 2816, at a manager/service API between the initiator 2814 and the proxy 2818). As another example, traffic can be tagged at a network interface between the proxy 2818 and the network stack 2812.

The example of FIG. 28 will now be used to illustrate a specific implementation with reference to actual apps by name by way of example, but not limitation. An initiator (skysport) triggers a control application (HTC player) to utilize a proxy (media service). The activity stack and API data from the HTC player are provided to a classification and enforcement engine. The technique used to obtain traffic information for the purpose of tagging can be by, for example, a hook, call-back, injection point, broadcast receiver, intent filter, or some other applicable mechanism.

108

In this way, traffic from a thread that is identified as that of the media server can be attributed to skysport, and appropriate policy (e.g., traffic control, notification, and billing) can be enforced. Similarly, traffic from a thread that is identified as that of HTC player can be attributed to skysport and appropriate policy can be enforced.

After tagging a flow, it may be desirable to act on the flow in various ways related to the relevant service policy. For example, a mobile data limit can be set. Advantageously, it is possible to go to each app to restrict background and/or foreground data. It is also possible to disable background for a device across the board. Because of the way the flow is tagged, an app will not even be aware of restrictions to, e.g., background data.

FIG. 29 depicts a flowchart 2900 of an example of a method of flow tracking. For illustrative purposes, a mapping (flow tracking) of an application is depicted to the right of the flowchart 2900. In the example of FIG. 29, the flowchart 2900 starts at module 2902 with activating A. In this example, A is intended to identify an electronic traffic source, such as a URL, phone number, or other applicable mechanism for forming a connection such that data can flow between a service policy implemented device and some other device. Thus, activating A can entail clicking on a URL, dialing a phone number, or initiating a connection with another device in some other applicable manner. The data can flow in one direction or in more than one direction, depending upon the instance and/or implementation.

In the example of FIG. 29, the flowchart 2900 continues to module 2904 with an initiator calling an activity stack. In this paper, the activity stack is located between an initiator (e.g., a file and system components that identify the control app) and a control app. Where no control app is used, the term activity stack is not used in favor of making reference to a proxy API. For the purposes of this example, the initiator is the engine, component, or otherwise identifiable thing that is responsible for traffic associated with A. In a system that tracks service usage for the purpose of implementing a service policy in a manner that is described in this paper, it may be desirable to be able to identify the initiator and charge for the traffic appropriately. (As opposed to, for example, charging the proxy or control app or controlling policy in some other manner that is not as finely tuned.) It may be noted that the activity stack is located between an initiator and a control app, but if there is no control app, the initiator instead calls a service API. The initiator can be mapped to A at the activity stack.

In the example of FIG. 29, the flowchart 2900 continues to module 2906 with a control app calling a service API to handle A. An example of a control app that could be used in this manner is the HTC player (or some other media player). In a specific example, the HTC player could be registered to handle files of a certain type. (For the sake of this example, let us assume it is registered to handle "audio files"). A user could click on audio file content of a website. The audio file itself does not have rendering capabilities; so the HTC player runs on the audio file's behalf to play the audio file for a user. The control app can be mapped to A at the service API.

In the example of FIG. 29, the flowchart 2900 continues to module 2908 with a proxy opening a network connection to A. Naturally, opening a connection to A can require certain actions by the proxy, such as finding A in a network. In a specific implementation, the proxy uses an IP lookup to find an IP address (generally having a format 1.2.3.4). The proxy can be mapped to A at the network interface. It is possible that A will have moved to B, in which case a DNS

109

request can be used to find B. If that happens, A can be mapped to B, and the thread can be tracked back to A and, ultimately, the initiator.

In the example of FIG. 29, the flowchart 2900 continues to module 2910 with data flowing from A to the proxy (or from B to the proxy if A was moved to B). The traffic of the data flow can be tagged, and because the initiator, control app (if applicable), and proxy were all mapped to A, it is possible to figure out that the network resources can be charged to A (or to some other component to which the traffic has been mapped, if applicable).

In the example of FIG. 29, the flowchart 2900 continues to module 2912 with the proxy talking to the control app and to module 2914 with the control app controlling the content. Thus, in the example where A is an audio file and the control app is an audio player, the proxy provides streamed audio to the player, which plays the audio content for a user. As was previously noted, the content can be matched to the location of the content (e.g., on a website) and can be treated in a manner that is appropriate for an active service policy.

In the example of FIG. 29, the flowchart 2900 ends at module 2916 with charging traffic associated with A to the initiator. It may be noted that traffic tagging can occur at different points in the network stack, such as at socket flows or IP packet transmissions. Also, an initiator could at least in theory have any number of intervening apps between the initiator and the proxy, and traffic could be tagged between each app. Advantageously, it is possible to track whether apps have other characteristics. For example, tracking is possible when in foreground or background. This can include background service protocols and background network access. This can have an impact on how traffic is charged or otherwise controlled in accordance with the applicable service policy.

Traffic tagging may or may not entail the use of hooks. The amount of control over the proxy will depend upon whether, for example, the proxy was written by the same party that wrote other components of a device framework. It is somewhat more likely that a third party will make use of hooks. It may also be desirable to hook at certain locations, such as in the socket, to tag back to a traffic stack “opened socket for thread” and give a socket-to-thread mapping. Combined with an API mapping, it is possible to map socket-to-app, which can then be pushed to a low level interface where traffic can be observed (e.g., a driver, in a kernel, etc.). As was previously discussed, the activity stack makes it possible to use hooks (if applicable) to map socket-to-control app-to-initiating app. Where every packet is counted at, e.g., a firewall, the low level interface can see the thread and can map each packet to the appropriate app even though the counted packets are, e.g., identified as those of the proxy. This facilitates traffic can being accurately dropped into the appropriate service policy buckets.

Tagging traffic flows enables discrete service control policy enforcement. For example, a service policy could block A (or B) in accordance with a service control policy even if the proxy is not normally blocked (for example, for other content). Blocking can occur at the network and is possible even in the case where an initiator calls a control app that is not necessarily blocked because tagging happens in the activity stack. It may also be the case that a control app should be blocked regardless of whether A (or B) should be blocked, which is possible because the traffic is tagged at the API. It may be noted that blocking is not the only traffic control policy, and other traffic control policies could be used, as well, such as notification.

110

In an implementation in which the proxy includes a VoIP manager, the proxy can run encoding/protocols (SIP, H323, etc.). A VoIP service control cloud can ensure routing to a low latency backbone. The VoIP service manager can do core functions of VoIP there. An API enables running consistent VoIP services with a consistent set of tools for apps. A VoIP service manager can have special performance features, QoS functions, interactive cloud service, and can be charged differently, routed to APN or server, manage offloading to WiFi/2G/3G/4G, manage roaming aspects, and manage presence.

FIG. 30 depicts an example of a system 3000 with a mapped traffic flow. The system 3000 includes a user 3002, a data usage settings datastore 3004, system managers 3006, an ItsOn service engine 3008, an app 3010, a proxy 3012, a thread 3014, a socket 3016, and an ItsOn classification engine 3018. Although reference is made to “ItsOn” in this example, it should be noted that this is simply one specific implementation, and that the techniques described in association with this example are broadly applicable, not limited to any actual ItsOn implementation.

In the example of FIG. 30, a user 3002 can provide data usage settings to the data usage settings datastore 3004 and start/stop/foreground/background/ . . . instructions to the system managers 3006. It may be noted that a user agent, network agent, service provider agent, or some other agent can provide data usage settings instead of or in addition to the user 3002. Similarly, a user agent, network agent, service provider agent, or some other agent can provide start/stop/foreground/background/ . . . instructions instead of or in addition to the user 3002.

In the example of FIG. 30, the data usage settings datastore 3004 includes service policy that can be accessed by the ItsOn service engine 3008. Service policy can be implemented and/or enforced using techniques described elsewhere in this paper. An example of policy that may be used by the ItsOn service engine 3008 is “allow app” or “restrict app.”

In the example of FIG. 30, the system managers 3006 (or a system manager thereof) launch the app 3010 and report app state to the ItsOn service engine 3008. An example of app state is “call-back on state change.” This can, for example, result in a call-back if an app changes from running in the background to running in the foreground, or vice versa, or when the app is shut down.

In the example of FIG. 30, the app 3010 utilizes an API to trigger the proxy 3012 which in turn passes through a socket connection at the socket 3016 as traffic. In operation, the app 3010, the proxy 3012, and the socket 3016 can be implemented as engines. The proxy 3012 generates the thread 3014 and registers the thread with the ItsOn service engine 3008. The socket 3016 registers the socket connection with the ItsOn service engine 3008.

In the example of FIG. 30, the ItsOn service engine 3008 has data sufficient to map the socket to the app, using the thread registration from the proxy 3012 and the socket registration from the socket 3016. The ItsOn service engine 3008 sends the socket-to-app mapping to the ItsOn classification engine 3018, along with a filter, which can be to allow, block, or perform some other filtering. The ItsOn service engine 3008 can be logically (or physically) divided into at least two components: a network policy manager and a traffic stack. The network policy manager can include, e.g., a policy decision point agent. See, e.g., FIG. 3, policy decision point agent 1692. The network policy manager accesses policy in the data usage settings datastore 3004, receives the app state from the system managers 3006, and

111

provides a filter parameter to the ItsOn classification engine 3018. The traffic stack receives the registration of the thread and the registration of the socket and provides the socket app map to the ItsOn classification engine 3018.

In the example of FIG. 30, the ItsOn classification engine 3018 is capable of enforcing policy for a thread (mapped to an app), including, e.g., traffic control, notification, and/or charging. The ItsOn classification engine 3018 can be logically (or physically) divided into at least two components: a firewall (e.g., iptables) and a tagging engine (e.g., qtaguid). The tagging engine receives the socket app map from the traffic stack and provides a tag to the firewall. The firewall receives the filter from the network policy manager and the tag from the tagging engine and provides a count back to the tagging engine. The firewall also filters (e.g., blocks, allows, or performs some other filtering) traffic from the socket 3016.

It is becoming increasingly important to associate device access network service usage (e.g., network data services usage, voice services usage, etc.) to the applications (e.g., application program, widget, service, process, embedded object, or any combination of these, etc.) that are using the services. This information may be used in a variety of ways, including but not limited to: (1) classifying service usage to assist a user to understand one or more aspects of service usage (e.g., notifying a user about which applications are consuming service usage, or how much service usage one or more applications are consuming (e.g., amount of usage); (2) classifying service usage for the purpose of service control policy enforcement (e.g., traffic control, quality-of-service (QoS) control, QoS channel set-up, application-based service classification or usage controls, etc.); (3) classifying service usage for the purpose of service charging accounting.

Various embodiments disclosed herein provide a way for device software agents, integrated into the device in addition to an operating system or as an integral set of functions in an operating system, to track network service usage through a proxy service function back to an originating application that uses the proxy service function to assist in transferring data between a network and the application (e.g., application program, widget, service, process, embedded object, or any combination of these, etc.).

In some existing device operating systems, a proxy service function is used to manage the network service flows between the network and an application (e.g., application program, widget, service, process, embedded object, or any combination of these, etc.), and the proxy service is stored in the operating system (OS) as the application responsible for using services rather than the application actually using the network service. For example, in the Android OS, there exists a “media service” OS library software program function that manages the network stack interface for download of network data (typically, but not limited to, multimedia data). The device makes a request to the media service, which then performs various network stack interface functions to transfer the network data between the device application and the network. The media service can also process media files to determine how best to decode the multimedia and play the multimedia on the device user interface (UI). For example, the media service can determine the media filing coding standard (e.g., MP3, MP4, OGG, H.264, VP8, etc.), decode the media, select a player for the media (e.g., libstagefright (an Android streaming service library function), a third-party or OEM media player, etc.), and send the decoded media to the media player for UI playback. In the case of the media service, the data flows to the network can

112

be classified by various device service usage monitoring agents (e.g., a kernel agent in the network stack) as belonging to the media service, not the originating application, and the OS provides no mechanism for tracking the usage back to the originating application.

Another example in the Android OS is the “media” OS library software program that is used by applications such as the Android browser, Android store app downloader, the Gmail client, OS updater, etc. The media function manages network data transfers for such applications, allowing an application to launch a data transfer request and then continue other operations while the media service is managing the network data transfer. In the case of the media function, the data flows to the network can be classified as belonging to the media function, not the originating application, and the OS provides no techniques or mechanisms to track the usage back to the originating application.

As another example, some higher-level library software functions or framework software functions provide proxy server client functions that encapsulate native application traffic to send application flows to a network proxy server for further network traffic processing, and this proxy client function sits above the network stack. Examples of this include the Android.net library function, the Apache library function, and the Java.net library function, third-party proxy server client functions or tunneling protocol functions, and other proxy server client functions or tunneling protocol functions.

As another example, there are system services (e.g., DNS, certificate management, etc.) for many OS (e.g., Windows 7 and other Windows versions). Similar to the OS functions discussed above, these OS functions manage data transfer with the OS network stack interface for an originating application, and the device network stack service flows can be classified back to these OS functions, but not to the originating applications.

Disclosed herein are techniques and mechanisms to identify an application name, identifier, process, etc. for an application (e.g., application program, widget, service, process, embedded object, or any combination of these, etc.) that requests from a media service manager a data transfer (data transfer request) that includes a network resource identifier (e.g., an IP address, a URL, a remote file name or address, a stream name, an object name, or any combination of these identifiers) that identifies a source (or a proxy to the source) of the data to be transferred or a data object to be transferred. In some embodiments, a software agent (e.g., a service classification and accounting agent) identifies the originating application. In some embodiments, the software agent monitors and stores the application name, identifier, process, etc., for each application that requests a data transfer from the media service manager or that conducts a data transfer with the media service manager. In some embodiments, the software agent (e.g., the service classification and accounting agent) is implemented by including a requesting-application storing function in the media services manager. In some embodiments, the software agent (e.g., the service classification and accounting agent) further identifies and stores information about the network resource identifiers along with the entry specifying the requesting application name, identifier, process, etc.

In some embodiments, techniques or mechanisms within the media service manager transfer the requested data from the network resource identifier by mapping the transfer request and network resource identifier into one or more data flow connections communicated through a device networking stack (and, in some embodiments, managing the result-

113

ing flow of data between the network and device stack and/or between the network stack and the application).

In some embodiments, techniques or mechanisms are used to identify the resulting network data flows. In some embodiments, a service classification and accounting agent identifies the resulting network data flows by monitoring and recording the resulting network data flow identifiers (e.g., a data flow tag, an IP address, a TCP-IP identifier, a layer 7 identifier, a socket tuple, etc.).

In some embodiments, techniques or mechanisms associate the resulting network data flows back to the application name, identifier, process, etc. For example, in an Android system, the resulting network data flows can be associated with the UID. In some embodiments, a service classification and accounting agent associates the resulting network data flows back to the application name, identifier, process, etc. by inspecting the resulting network data flows to determine a match between one or more aspects of the network resource identifier stored in association with the requesting application name, identifier, process, etc. In some embodiments, a service classification and accounting agent associates the resulting network data flows back to the application name, identifier, process, etc. by tracking the data flow from the interface between the media service manager and the application, through each stage of media service manager data flow processing to the resulting network data flow between the media service manager and the network stack. In some embodiments, virtual tagging is used, and the tracking is accomplished by identifying and recording, at each traffic processing step within the media services manager, an association between the traffic flows at one side of the traffic processing step and the traffic flows at the other side of the traffic processing step. In some embodiments with more than one traffic-processing step, the associations made for each step are followed to create an association for all steps. In some embodiments, literal tagging is used, and that tracking is accomplished by tagging the data flows at one side of the media service manager traffic processing and identifying the tag at the other side of the media service manager traffic processing.

In some embodiments, techniques or mechanisms are used to create an accounting record for the resulting network data flow usage or to enforce a network traffic control policy on the resulting network data flows, or to create a service usage notification for the resulting network data flow usage.

In some embodiments, the results of the service usage classification or accounting can be stored in a local device (or operating system) database. The results of the service usage classification or accounting can be provided to a device (or operating system) user interface (UI) function for the purpose of displaying usage classifications to a user. The results of the service usage classification or accounting can be provided to other applications, operating system service functions, other device software functions, or network-based service classification or accounting functions.

In some embodiments, a proxy network service manager refers to an intermediary data flow function in a device operating system that sits on a data path between a device application and a device networking stack interface to provide a level of network service abstraction from the network stack interface, a higher-level service function above the network stack interface, enhanced or special traffic processing functions, media service transfer management, file download service, HTTP proxy service functions, quality-of-service (QoS) differentiation, or other similar or related higher-level traffic processing. Examples of proxy service managers include but are not limited to: a media

114

service manager (e.g., the Android media service library function), an e-mail service manager, a domain name server (DNS) function, a software download service manager, a media download manager, a data download service manager, an Android “media” library function, the Android.net library function, the Java.net library function, an Apache library function, other similar software or library functions or services in other device operating systems, an SMTP, IMAP, or POP proxy, an HTTP proxy, an IM proxy, a VPN service manager, an SSL proxy, etc.

In some embodiments, techniques or mechanisms identify an application name, identifier, process, etc. for an application (e.g., an application program, a widget, a service, a process, an embedded object, or any combination of these, etc.) that requests from a proxy service manager a data transfer (a data transfer request) that includes a network resource identifier (e.g., an IP address, a URL, a remote filename or address, a stream name, an object name, or any combination of these identifiers, etc.) that identifies a source (or a proxy to the source) of the data to be transferred or a data object to be transferred. In some embodiments, a service classification and accounting agent identifies the originating application by monitoring and storing the application name, identifier, process, etc. for each application that requests a data transfer from the proxy service manager or that conducts a data transfer with the proxy service manager. In some embodiments, the service classification and accounting agent is implemented by including a requesting application storing function in a proxy services manager. In some such embodiments, the service classification and accounting agent further identifies and stores information about the network resource identifier along with the entry specifying the requesting application name, identifier, process, etc.

In some embodiments, techniques or mechanisms within the proxy service manager are used to transfer the requested data from the network resource identifier by mapping the transfer request and network resource identifier into one or more data flow connections communicated through a device networking stack (and possibly managing the resulting flow of data between the network and device stack or between the network stack and the application).

In some embodiments, techniques or mechanisms are used to identify the resulting network data flows. In some embodiments, a service classification and accounting agent identifies the resulting network data flows by monitoring and recording the resulting network data flow identifiers (e.g., a data flow tag, an IP address, a TCP-IP identifier, a layer 7 identifier, a socket tuple, etc.).

In some embodiments, techniques or mechanisms are used to associate the resulting network data flows back to the application name, identifier, process, etc. For example, in an Android system, the resulting network data flows can be associated with the UID. In some embodiments, a service classification and accounting agent associates the resulting network data flows back to the application name, identifier, process, etc. by inspecting the resulting network data flows to determine a match between one or more aspects of the network resource identifier stored in association with the requesting application name, identifier, process, etc. In some embodiments, a service classification and accounting agent associates the resulting network data flows back to the application name, identifier, process, etc. by tracking the data flow from the interface between the media service manager and the application, through each stage of media service manager data flow processing to the resulting network data flow between the media service manager and the

115

network stack. In some embodiments, virtual tagging is used, and the tracking is accomplished by identifying and recording, at each traffic processing step within the media services manager, an association between the traffic flows at one side of the traffic processing step and the traffic flows at the other side of the traffic processing step. In some embodiments with more than one traffic-processing step, the associations made for each step are followed to create an association for all steps. In some embodiments, literal tagging is used, and that tracking is accomplished by tagging the data flows at one side of the media service manager traffic processing and identifying the tag at the other side of the media service manager traffic processing.

In some embodiments, techniques or mechanisms are used to create an accounting record for the resulting network data flow usage or to enforce a network traffic control policy on the resulting network data flows, or to create a service usage notification for the resulting network data flow usage.

In some embodiments, the results of the service usage classification or accounting can be stored in a local device (or operating system) database. The results of the service usage classification or accounting can be provided to a device (or operating system) user interface (UI) function for the purpose of displaying usage classifications to a user. The results of the service usage classification or accounting can be provided to other applications, operating system service functions, other device software functions, or network-based service classification or accounting functions.

FIGS. 31A and 31B depict a flowchart 3100 of an example of a method of virtual tagging. As will be appreciated by a person having ordinary skill in the art, the number of detailed embodiments are numerous, and this detailed description is provided for instructive purposes and not to indicate any limitation to the general embodiments described herein. The example references a specific well-known application (Pandora), but the techniques described are broadly applicable. In the example of FIGS. 31A and 31B, the flowchart 3100 starts at module 3102 with Pandora application calls a media service function with a network resource indicator (NRI) that includes a Pandora URL with a song identifier included in the URL descriptor.

In the example of FIGS. 31A and 31B, the flowchart 3100 continues to module 3104 with Pandora receives back from the media service function a media object handle descriptor so that the Pandora application can control playback, etc. by sending commands back to the media service function for that handle descriptor (e.g., pause on xyz song handle, play xyz song handle, etc.).

In the example of FIGS. 31A and 31B, the flowchart 3100 continues to module 3106 with the media service function initiates an HTTP download by calling libstagefright, which conducts the HTTP song download process.

In the example of FIGS. 31A and 31B, the flowchart 3100 continues to module 3108 with, at some point in the download process, the media service function begins playback with a media player under the control of the media service function and in accordance with the Pandora application playback commands for the media object handle for the song being played back.

In the example of FIGS. 31A and 31B, the flowchart 3100 continues to module 3110 with a classification and accounting agent function included in the media service function writing the NRI descriptor into a table located in an application usage/flow mapping element.

In the example of FIGS. 31A and 31B, the flowchart 3100 continues to module 3112 with the classification and accounting agent function associates the NRI with the

116

Pandora application by writing a Pandora application identifier descriptor into the same table entry within the application usage/flow mapping element.

In the example of FIGS. 31A and 31B, the flowchart 3100 continues to module 3114 with the table entry being communicated to a usage/classification reconciliation element.

In the example of FIGS. 31A and 31B, the flowchart 3100 continues to module 3116 with the classification and enforcement agent identifies the network data flows (e.g., socket (e.g., IP address, destination port, source port, protocol, etc.) indexed data flows) originating from the media service function (and/or possibly the libstagefright function originating the flows), identifies the NRI via packet flow layer 7 inspection, and logs the service usage accounting for these packet flows.

In the example of FIGS. 31A and 31B, the flowchart 3100 continues to module 3118 the classification and enforcement agent writes into a table entry the following associations: (1) identifier for the media service function originating the flows (and/or possibly the identifier for the libstagefright function originating the flows), (2) the NRI, (3) the service usage classification for these flows and accounting for these flows, and (4) possibly the service usage accounting for these flows.

In the example of FIGS. 31A and 31B, the flowchart 3100 continues to module 3120 with this table entry being communicated to the usage/classification reconciliation element.

In the example of FIGS. 31A and 31B, the flowchart 3100 continues to module 3122 with the usage/classification reconciliation element using these two table entries, which both have common entries for the NRI and the media service function (and/or possibly the libstagefright function) to make the association between the Pandora application and the service usage classification and possibly the service usage accounting.

In the example of FIGS. 31A and 31B, the flowchart 3100 continues to module 3124 with these parameters may then be written into the usage/classification database.

FIG. 32 depicts an example of a system 3200 for classification mapping using virtual tagging. The system 3200 includes an application 3202, a control application 3204, a proxy service manager 3206, a network stack (driver) 3208, traffic processes 3210-1 to 3210-N (collectively, traffic processes 3210), a flow tracking agent 3212, an application usage/flow mapping engine 3214, a usage/classification reconciliation engine 3216, a usage/classification datastore 3218, a user interface (UI) engine 3220, and an application interface engine 3222. In operation, the application 3202, control application 3204, proxy service manager 3206, network stack (driver) 3208, and flow tracking agent 3212 are implemented as engines.

In the example of FIG. 32, the application 3202 may or may not, depending upon instance and/or implementation, need to use the control application 3204 (e.g., to render content) and/or the proxy service manager 3206. This is represented by the three double arrows from the application 3202 to the control application 3204, the proxy service manager 3206, and the network stack (driver) 3208.

In the example of FIG. 32, traffic processes associated with the application 3202 are depicted as traffic processes 3210. The flow tracking agent 3212 can obtain information about the traffic processes 3210 at the start and end of the traffic flow that comprises the traffic processes 3210. The start and end are intended to illustrate, for example, a hook, call-back, injection point, etc., at a proxy service manager API (the start) and at a socket connection (the end). It may be noted that in an instance or embodiment where the

117

application **3202** does not use the proxy service manager **3206**, data at the socket will accurately identify the app as the initiator of the data flow. In an instance or embodiment where the application **3202** uses the proxy service manager **3206**, data at the socket will be insufficient to identify the application **3203** as the initiator of the data flow, making it desirable to add a virtual tag at the proxy API or some other applicable upstream location. In an instance or embodiment where the application **3203** uses the control application **3204**, an additional virtual tag is necessitated at the activity stack.

In the example of FIG. **32**, the virtual tags are sent from the flow tracking agent **3212** to the app usage/flow mapping engine **3214**, which communicates with the usage/classification reconciliation engine **3216**, which in turn communicates with the network stack (driver) **3208**. The usage/classification reconciliation engine **3216** can track usage of the app, classify the app, and to the extent there is disagreement at different system locations, reconcile usage in accordance with rules. The usage/classification reconciliation engine **3216** saves the usage/classification in the usage/classification datastore **3218**, which can be made available to a user via the user interface **3220** or an application via the application interface **3222**.

In an alternative embodiment, flow tracking agents are coupled between traffic process elements **3210**. For example, between traffic process **3210-1** and traffic process **3210-2**.

In some embodiments, the proxy service manager can perform application identification and classification, usage monitoring, and counting. This allows service usage to be classified and associated with an application prior to proxy processing. Classification can be accomplished with a software agent (e.g., the service classification and accounting agent) added to the proxy service manager software program (or library function). It may be noted that a software agent, in operation, can be implemented as an engine. The service classification and accounting proxy agent can identify which application requested or is processing the data transfer with the network and can include this as part of the data flow classification for the data transfer. The service classification and accounting proxy agent can inspect the traffic to determine other parameters such as network destination (e.g., domain, URL, network address, IP address, traffic flow identifier, port address, etc.) or type of traffic (e.g., data or voice, network protocol (e.g., TCP-IP, UDP, native IP, HTTP, SSL, etc.)). The service classification and accounting proxy agent can also classify the traffic with other parameters such as active network, network state (network busy state, time of day, type of network (e.g., 3G, 4G, WiFi, etc.)). The service classification and accounting proxy agent may also monitor service usage and account for traffic.

In some embodiments, the proxy service manager includes a service classification and accounting proxy agent that uses a flow tracking function as discussed in a previous embodiment description to associate the requesting application network service flows between the requesting application and the proxy service manager and tracks these flows through the traffic processing or other service processing that takes place in the proxy service manager and then tracks the network service flows into the operating system network stack interface. The service classification and accounting proxy agent can then provide the classification or usage accounting results to the usage classification and reconciliation agent, which can then reconcile the service classification and usage that is reported by the proxy service manager service classification and accounting proxy agent against

118

classification or usage accounting results that are reported by other agents on other parts of the data path between the requesting application and the network (e.g., a service classification and accounting driver agent located in the network stack driver that is discussed in various embodiments in other applications and patents, that have been incorporated by reference in the cross-reference to related applications section, above).

In some embodiments, the results of the service usage classification or accounting can be stored in a local device (or operating system) database. The results of the service usage classification or accounting can be provided to a device (or operating system) UI function for the purpose of displaying usage classifications to a user. The results of the service usage classification or accounting can be provided to other applications, operating service functions, other device software functions, or network-based service classification or accounting functions.

In some embodiments, the proxy service manager encapsulates the received frames (or packets) by adding its own header and trailer fields. The encapsulated frames (or packets) traffic is then forwarded with a header (and possibly trailer) to a network proxy server or proxy gateway. The encapsulated frames are then forwarded to the network stack, where the service classification and accounting driver agent inspects the traffic to classify and possibly account for it.

In some embodiments, the classification includes the service classification and accounting driver agent steps of first determining that the frame (or packet) is a packet with a proxy forwarding destination specification, determine the inspection range of proxy encapsulated frame within the encapsulated frame traffic (this is the encapsulated packet byte offset where the destination information and/or other classification information from the original requesting application packet is located), then inspecting this byte offset range to determine the classification of the original requesting application traffic, and then associating the classification or usage accounting with the original packet information and/or the requesting application.

In some embodiments, the results of the service usage classification or accounting can be stored in a local device (or operating system) database. The results of the service usage classification or accounting can be provided to a device (or operating system) UI function for the purpose of displaying usage classifications to a user. The results of the service usage classification or accounting can be provided to other applications, operating service functions, other device software functions, or network-based service classification or accounting functions.

FIG. **33** depicts an example of a media service classification system **3300**. The system **3300** includes an applications layer **3302**, an application framework **3304**, libraries **3306**, a netlink interface **3308**, and a Linux kernel **3310**. The applications layer **3302** includes an ItsOn UI **3312** and an ItsOn service **3314**. Although explicit mention is made of an ItsOn implementation, the techniques described with reference to this example are broadly applicable, and are not limited to any particular ItsOn (or other) specific implementation. It may be noted that other applications, including system apps (e.g., home, phone, browser, contacts, etc.) and other apps (e.g., news, social network, etc.) can reside in the applications layer **3302**, but are omitted to avoid obscuring the drawing.

In the example of FIG. **33**, the application framework **3304** includes an activity manager **3316**. It may be noted that other managers, including a window manager, package

119

manager, telephony manager, location manager, etc. can reside in the application framework **3304**, but are omitted to avoid obscuring the drawing. Moreover, other managers can provide data to, e.g., the ItsOn service **3314** that is useful (e.g., the package manager can provide an indication that an app is installed), but a detailed description is not necessary for an understanding of the techniques presented.

In the example of FIG. **33**, the libraries **3306** include a media services framework datastore **3318** and an android runtime datastore **3320**. It may be noted that other libraries, including surface manager, java.net, android.net, apache, media, WebKit, freetype, SQLite, and libc datastores can reside in the libraries **3306**, but are omitted to avoid obscuring the drawing. The android runtime datastore **3320** can include a core libraries datastore and a dalvik VM datastore, to name two.

In the example of FIG. **33**, the netlink interface **3308** couples the libraries **3306** to the Linux kernel **3310**.

In the example of FIG. **33**, the Linux kernel **3310** includes an ItsOn filter **3322** and an ItsOn classification engine **3324**. It should be noted that although the Linux kernel **3310** is described in association with a particular OS (Linux), the techniques described with reference to this example are broadly applicable to other than Linux kernels, OSs, or other applicable engines. It may be noted that other low level devices, including, e.g., a display driver, audio driver, network stack (e.g., 3G/4G, WiFi, others, or a combination), a camera driver, and a keypad driver can reside in the Linux kernel **3310**, but are omitted to avoid obscuring the drawing.

In the example of FIG. **33**, in operation, the activity manager **3316** (which is called out as a representative manager) can provide runtime state to the ItsOn service **3314**. The ItsOn service **3314** can communicate with the media service framework datastore **3318** and the android runtime library **3320** (and specifically, for example, core libraries of the android runtime library). The media service framework datastore **3318** can provide a mapping through the netlink interface **3308** to the ItsOn classification engine **3324** and the ItsOn service **3314** can provide filters through the netlink interface **3308** to the ItsOn classification engine **3324**. The ItsOn UI **3312** can provide a window into the traffic classification and flow and the ItsOn filter **3322** can facilitate enforcement of applicable policy.

FIG. **34** depicts a proxy encapsulated frame **3400**. The frame **3400** includes a proxy header **3402**, a header **3404**, network traffic payload **3406**, and a proxy trailer **3408**. The header **3404** corresponds to an inspection range of proxy encapsulated frame **3412**.

FIG. **35** depicts an example of a system **3500** for proxy client counting. The system **3500** includes a proxy service manager **3502**, a proxy/library API **3504**, an app ID **3506**, usage classify/count **3508**, a traffic processing/other services **3510**, a service classification and accounting proxy agent **3512**, a flow tracking agent **3514**, a network stack (driver) **3516**, a stack API **3518**, an app ID/library function ID **3520**, usage classify/count **3522**, a service classification and accounting driver agent **3524**, a usage/classification reconciliation engine **3526**, a usage/classification datastore **3528**, a UI interface **3530**, an application interface **3532**, and a UI **3534**.

FIG. **36** depicts an example of a system **3600** for classifying traffic and enforcing a service policy based upon the classification. The system **3600** includes a proxy manager **3602**, an app traffic flow **3604**, a traffic stack **3606**, a socket manager **3608**, and a traffic classification and enforcement engine **3610**. The proxy manager **3602** and the socket manager **3608** can be implemented as engines. The traffic

120

stack **3606** can be implemented as an engine or a datastore. Where the traffic stack **3606** is implemented as a datastore, the proxy manager **3602**, the socket manager **3608**, the traffic classification and enforcement engine **3610**, or some other engine can provide the processor to carry out activities that are attributed to the traffic stack **3606**.

In the example of FIG. **36**, the proxy manager **3602** tags the app traffic flow **3604** at a first point in the flow. The first point in the flow corresponds to an API call by an app to the proxy manager **3602**, or an equivalent activity. The proxy manager **3602** can identify the app making the call and identify the thread that is (or will be) associated with the app. In this way, the proxy manager **3602** can identify a mapping of the app to the app traffic flow **3604**. The proxy manager **3602** registers the thread (e.g., the app-to-flow mapping) at the traffic stack **3606**.

In the example of FIG. **36**, the socket manager **3608** tags the app traffic flow **3604** at a second point in the flow. The second point in the flow corresponds to a socket call by the proxy manager **3602** to the socket manager **3608**, or an equivalent activity. The socket manager **3608** can identify the proxy making the call and identify the thread that is associated with the proxy. In this way, the socket manager **3608** can identify a mapping of the proxy to the app traffic flow **3604**. The socket manager **3608** registers the socket (e.g., the proxy-to-flow mapping) at the traffic stack **3606**.

In the example of FIG. **36**, the traffic classification and enforcement engine **3610** uses the thread registration to identify the app-to-flow and the socket registration to identify the proxy-to-flow. Because the traffic classification and enforcement engine **3610** knows the app called the proxy (from the thread registration) and the proxy called the socket (from the socket registration), the traffic classification and enforcement engine **3610** can properly identify the app as the initiator of the app traffic flow **3604**, as opposed to, for example, the proxy manager **3602** that made the socket call. With this knowledge, the traffic classification and enforcement engine **3610** can use the appropriate traffic control, notification, and charging policies to control the traffic, notify relevant parties, and/or assign the app traffic flow **3604** to the appropriate bucket or buckets.

In the example of FIG. **36**, an optional activity manager **3612** tags the app traffic flow **3604** at a third point in the flow. The third point in the flow corresponds to a control application call made on behalf of the app. The activity manager **3612** can identify the app making the call to the control application and identify the activity that is associated with the app. Conceptually, relative to the description just provided with reference to the proxy manager **3602** and the socket manager **3608**, the activity manager **3612** pushes the app up one more level, such that the data flow is from the app to a control application and to the proxy. Using the registered activity, the traffic classification and enforcement engine **3610** can trace the app traffic flow back up the chain to the app, rather than identifying the control application as the initiator.

FIG. **37** depicts a flowchart **3700** of an example of a method for flow tagging and enforcing service policies associated with an identified initiator of the flow. In the example of FIG. **37**, the flowchart **3700** starts at module **3702** and ends at module **3712**, which include the following: tagging a network activity traffic flow at a first point in the flow, wherein the first point is associated with an API call to a proxy manager for a thread; registering the thread; tagging the network activity traffic flow at a second point in the flow, wherein the second point is associated with a socket call to a socket manager for the thread; registering the socket; using

the registration of the thread and the registration of the socket to determine that the network activity traffic flow is associated with an initiator of the network activity, wherein the initiator of the network activity is not the proxy manager; and enforcing service policies associated with the initiator of the network activity for the network activity traffic flow.

Unless the context clearly indicates otherwise, the word “or” is used in its broadest sense. The phrase “A or B” thus includes “A only,” “B only,” and “A and B.” Phrases of the form “A and/or B” in this document are sometimes used instead of “A or B” for emphasis. The use of “A and/or B” is not to be interpreted as somehow implying that “A or B” has a narrower meaning than “A only,” “B only,” and “A and B.”

Algorithmic descriptions and representations are the means used by those skilled in the data processing arts to effectively convey the substance of their work to others skilled in the art. An algorithm is here, and generally, conceived to be a self-consistent sequence of operations leading to a desired result. The operations are those requiring physical manipulations of physical quantities. Usually, though not necessarily, these quantities take the form of electrical or magnetic signals capable of being stored, transferred, combined, compared, and otherwise manipulated. It has proven convenient at times, principally for reasons of common usage, to refer to these signals as bits, values, elements, symbols, characters, terms, numbers, or the like.

It should be borne in mind, however, that all of these and similar terms are to be associated with the appropriate physical quantities and are merely convenient labels applied to these quantities. Unless specifically stated otherwise as apparent from the following discussion, it is appreciated that throughout the description, discussions utilizing terms such as “processing” or “computing” or “calculating” or “determining” or “displaying” or the like, refer to the action and processes of a computer system, or similar electronic computing device, that manipulates and transforms data represented as physical (electronic) quantities within the computer system’s registers and memories into other data similarly represented as physical quantities within the computer system memories or registers or other such information storage, transmission or display devices.

The present invention, in some embodiments, also relates to apparatus for performing the operations herein. This apparatus may be specially constructed for the required purposes, or it may comprise a general purpose computer selectively activated or reconfigured by a computer program stored in the computer. Such a computer program may be stored in a computer readable storage medium, such as, but is not limited to, read-only memories (ROMs), random access memories (RAMs), EPROMs, EEPROMs, magnetic or optical cards, any type of disk including floppy disks, optical disks, CD-ROMs, and magnetic-optical disks, or any type of media suitable for storing electronic instructions, and each coupled to a computer system bus.

The algorithms and displays presented herein are not inherently related to any particular computer or other apparatus. Various general purpose systems may be used with programs in accordance with the teachings herein, or it may prove convenient to construct more specialized apparatus to perform the required method steps. The required structure for a variety of these systems will appear from the description below. In addition, the present invention is not described with reference to any particular programming language, and various embodiments may thus be implemented using a variety of programming languages.

Although the foregoing embodiments have been described in some detail for purposes of clarity of under-

standing, the invention is not limited to the details provided. There are many alternative ways of implementing the invention. The disclosed embodiments are illustrative and not restrictive.

INCORPORATION BY REFERENCE

This document incorporates by reference for all purposes the following non-provisional U.S. patent applications: application Ser. No. 12/380,778, filed Mar. 2, 2009, entitled VERIFIABLE DEVICE ASSISTED SERVICE USAGE BILLING WITH INTEGRATED ACCOUNTING, MEDIATION ACCOUNTING, AND MULTI-ACCOUNT, now U.S. Pat. No. 8,321,526 (issued Nov. 27, 2012); application Ser. No. 12/380,780, filed Mar. 2, 2009, entitled AUTOMATED DEVICE PROVISIONING AND ACTIVATION, now U.S. Pat. No. 8,839,388 (issued Sep. 16, 2014); application Ser. No. 12/695,019, filed Jan. 27, 2010, entitled DEVICE ASSISTED CDR CREATION, AGGREGATION, MEDIATION AND BILLING, now U.S. Pat. No. 8,275,830 (issued Sep. 25, 2012); application Ser. No. 12/695,020, filed Jan. 27, 2010, entitled ADAPTIVE AMBIENT SERVICES, now U.S. Pat. No. 8,406,748 (issued Mar. 26, 2013); application Ser. No. 12/694,445, filed Jan. 27, 2010, entitled SECURITY TECHNIQUES FOR DEVICE ASSISTED SERVICES, now U.S. Pat. No. 8,391,834 (issued Mar. 5, 2013); application Ser. No. 12/694,451, filed Jan. 27, 2010, entitled DEVICE GROUP PARTITIONS AND SETTLEMENT PLATFORM, now U.S. Pat. No. 8,548,428 (issued Oct. 1, 2013); application Ser. No. 12/694,455, filed Jan. 27, 2010, entitled DEVICE ASSISTED SERVICES INSTALL, now U.S. Pat. No. 8,402,111, now U.S. Pat. No. 8,402,111 (issued Mar. 19, 2013); application Ser. No. 12/695,021, filed Jan. 27, 2010, entitled QUALITY OF SERVICE FOR DEVICE ASSISTED SERVICES, now U.S. Pat. No. 8,346,225 (issued Jan. 1, 2013); application Ser. No. 12/695,980, filed Jan. 28, 2010, entitled ENHANCED ROAMING SERVICES AND CONVERGED CARRIER NETWORKS WITH DEVICE ASSISTED SERVICES AND A PROXY, now U.S. Pat. No. 8,340,634 (issued Dec. 25, 2012); application Ser. No. 13/134,005, filed May 25, 2011, entitled SYSTEM AND METHOD FOR WIRELESS NETWORK OFFLOADING, now U.S. Pat. No. 8,635,335 (issued Jan. 21, 2014); application Ser. No. 13/134,028, filed May 25, 2011, entitled DEVICE-ASSISTED SERVICES FOR PROTECTING NETWORK CAPACITY, now U.S. Pat. No. 8,589,541 (issued Nov. 19, 2013); application Ser. No. 13/229,580, filed Sep. 9, 2011, entitled WIRELESS NETWORK SERVICE INTERFACES, now U.S. Pat. No. 8,626,115 (issued Jan. 7, 2014); application Ser. No. 13/237,827, filed Sep. 20, 2011, entitled ADAPTING NETWORK POLICIES BASED ON DEVICE SERVICE PROCESSOR CONFIGURATION, now U.S. Pat. No. 8,832,777 (issued Sep. 9, 2014); application Ser. No. 13/239,321, filed Sep. 21, 2011, entitled SERVICE OFFER SET PUBLISHING TO DEVICE AGENT WITH ON-DEVICE SERVICE SELECTION, now U.S. Pat. No. 8,898,293; application Ser. No. 13/248,028, filed Sep. 28, 2011, entitled ENTERPRISE ACCESS CONTROL AND ACCOUNTING ALLOCATION FOR ACCESS NETWORKS, now U.S. Pat. No. 8,924,469; application Ser. No. 13/247,998, filed Sep. 28, 2011, entitled COMMUNICATIONS DEVICE WITH SECURE DATA PATH PROCESSING AGENTS, now U.S. Pat. No. 8,725,123 (issued May 13, 2014); application Ser. No. 13/248,025 (RAEP043), filed Sep. 28, 2011, entitled SERVICE DESIGN CENTER FOR DEVICE ASSISTED SERVICES, now U.S. Pat. No. 8,924,543; application Ser.

123

No. 13/253,013, filed Oct. 4, 2011, entitled SYSTEM AND METHOD FOR PROVIDING USER NOTIFICATIONS, now U.S. Pat. No. 8,745,191 (issued Jun. 3, 2014); application Ser. No. 13/309,556, filed Dec. 1, 2011, entitled END USER DEVICE THAT SECURES AN ASSOCIATION OF APPLICATION TO SERVICE POLICY WITH AN APPLICATION CERTIFICATE CHECK, now U.S. Pat. No. 8,893,009; application Ser. No. 13/309,463, filed Dec. 1, 2011, entitled SECURITY, FRAUD DETECTION, AND FRAUD MITIGATION IN DEVICE-ASSISTED SERVICES SYSTEMS, now U.S. Pat. No. 8,793,758 (issued Jul. 29, 2014); and application Ser. No. 13/374,959, filed Jan. 24, 2012, entitled FLOW TAGGING FOR SERVICE POLICY IMPLEMENTATION, now U.S. Pat. No. 8,606,911 (issued Dec. 10, 2013).

This document incorporates by reference for all purposes the following provisional patent applications: Provisional Application No. 61/206,354, filed Jan. 28, 2009, entitled SERVICES POLICY COMMUNICATION SYSTEM AND METHOD; Provisional Application No. 61/206,944, filed Feb. 4, 2009, entitled SERVICES POLICY COMMUNICATION SYSTEM AND METHOD; Provisional Application No. 61/207,393, filed Feb. 10, 2009, entitled SERVICES POLICY COMMUNICATION SYSTEM AND METHOD; and Provisional Application No. 61/207,739, entitled SERVICES POLICY COMMUNICATION SYSTEM AND METHOD, filed Feb. 13, 2009; Provisional Application No. 61/270,353, filed on Jul. 6, 2009, entitled DEVICE ASSISTED CDR CREATION, AGGREGATION, MEDIATION AND BILLING; Provisional Application No. 61/275,208, filed Aug. 25, 2009, entitled ADAPTIVE AMBIENT SERVICES; and Provisional Application No. 61/237,753, filed Aug. 28, 2009, entitled ADAPTIVE AMBIENT SERVICES; Provisional Application No. 61/252,151, filed Oct. 15, 2009, entitled SECURITY TECHNIQUES FOR DEVICE ASSISTED SERVICES; Provisional Application No. 61/252,153, filed Oct. 15, 2009, entitled DEVICE GROUP PARTITIONS AND SETTLEMENT PLATFORM; Provisional Application No. 61/264,120, filed Nov. 24, 2009, entitled DEVICE ASSISTED SERVICES INSTALL; Provisional Application No. 61/264,126, filed Nov. 24, 2009, entitled DEVICE ASSISTED SERVICES ACTIVITY MAP; Provisional Application No. 61/348,022, filed May 25, 2010, entitled DEVICE ASSISTED SERVICES FOR PROTECTING NETWORK CAPACITY; Provisional Application No. 61/381,159, filed Sep. 9, 2010, entitled DEVICE ASSISTED SERVICES FOR PROTECTING NETWORK CAPACITY; Provisional Application No. 61/381,162, filed Sep. 9, 2010, entitled SERVICE CONTROLLER INTERFACES AND WORKFLOWS; Provisional Application No. 61/384,456, filed Sep. 20, 2010, entitled SECURING SERVICE PROCESSOR WITH SPONSORED SIMS; Provisional Application No. 61/389,547, filed Oct. 4, 2010, entitled USER NOTIFICATIONS FOR DEVICE ASSISTED SERVICES; Provisional Application No. 61/385,020, filed Sep. 21, 2010, entitled SERVICE USAGE RECONCILIATION SYSTEM OVERVIEW; Provisional Application No. 61/387,243, filed Sep. 28, 2010, entitled ENTERPRISE AND CONSUMER BILLING ALLOCATION FOR WIRELESS COMMUNICATION DEVICE SERVICE USAGE ACTIVITIES; Provisional Application No. 61/387,247, filed September 28, 2010, entitled SECURED DEVICE DATA RECORDS, 2010; Provisional Application No. 61/407,358, filed Oct. 27, 2010, entitled SERVICE CONTROLLER AND SERVICE PROCESSOR ARCHITECTURE; Provisional Application No. 61/418,507, filed Dec. 1, 2010, entitled APPLICATION

124

SERVICE PROVIDER INTERFACE SYSTEM; Provisional Application No. 61/418,509, filed Dec. 1, 2010, entitled SERVICE USAGE REPORTING RECONCILIATION AND FRAUD DETECTION FOR DEVICE ASSISTED SERVICES; Provisional Application No. 61/420,727, filed Dec. 7, 2010, entitled SECURE DEVICE DATA RECORDS; Provisional Application No. 61/422,565, filed Dec. 13, 2010, entitled SERVICE DESIGN CENTER FOR DEVICE ASSISTED SERVICES; Provisional Application No. 61/422,572, filed Dec. 13, 2010, entitled SYSTEM INTERFACES AND WORKFLOWS FOR DEVICE ASSISTED SERVICES; Provisional Application No. 61/422,574, filed Dec. 13, 2010, entitled SECURITY AND FRAUD DETECTION FOR DEVICE ASSISTED SERVICES; Provisional Application No. 61/435,564, filed Jan. 24, 2011, entitled FRAMEWORK FOR DEVICE ASSISTED SERVICES; Provisional Application No. 61/472,606, filed Apr. 6, 2011, entitled MANAGING SERVICE USER DISCOVERY AND SERVICE LAUNCH OBJECT PLACEMENT ON A DEVICE; Provisional Application No. 61/550,906, filed Oct. 24, 2011, entitled SECURITY FOR DEVICE-ASSISTED SERVICES; and Provisional Application No. 61/589,830, filed Jan. 23, 2012, entitled METHODS AND APPARATUS TO PRESENT INFORMATION ABOUT VOICE, MESSAGING, AND DATA SERVICES ON WIRELESS MOBILE DEVICES.

We claim:

1. A wireless end-user device, comprising:

- a wireless modem configurable to connect to a wireless network;
- a network stack configurable to receive and transmit data via the wireless modem and the wireless network;
- a first network stack Application Programming Interface (API), containing at least one first call accessible to each of a plurality of device applications, the first network stack API callable by each of the plurality of device applications to open and use data packet flows via the network stack, the wireless modem, and the at least one wireless network;
- a second API containing at least one second call accessible to each of the plurality of device applications, the second API callable by each of the plurality of device applications to make a data transfer request for a media object associated with a network resource identifier supplied by the calling device application;
- a media service manager prompted by the second call, to manage network data transfers for the media object by interfacing with the network stack to retrieve the media object associated with the network resource identifier via the wireless modem and the wireless network; and
- one or more service classification and measurement agents to associate wireless network data usage for the media object network data transfers with the device application that requests the data transfer for the media object, to associate wireless network data usage for respective data packet flows opened and used via the first network stack API with the device application opening such respective data packet flow, and to reconcile wireless network data usage for each of the plurality of device applications to track an aggregate wireless network data usage attributable to each of the plurality of device applications via both the first network stack API and the second API.

2. The wireless end-user device of claim 1, wherein to associate wireless network data usage for the media object network data transfers with the device application that makes the data transfer request for the media object com-

125

prises to identify at least one of an application name, an application identifier, or a process identifier for the application that makes the data transfer request.

3. The wireless end-user device of claim 2, wherein the data transfer request comprises a network resource identifier that identifies a source of the data to be transferred, a proxy to the source of the data to be transferred, or the media object to be transferred, in particular, wherein the network resource identifier comprises one or more of an Internet Protocol address, a Uniform Resource Locator, a remote file name/ address, a stream name, and an object name.

4. The wireless end-user device of claim 3, wherein to associate wireless network data usage for the media object network data transfers with the device application that makes the data transfer request for the media object further comprises to store an entry comprising the at least one of the application name, the application identifier, or the process identifier for each of the device applications that makes a data transfer request, each stored entry further comprising information about the corresponding network resource identifier for the data transfer request.

5. The wireless end-user device of claim 4, wherein the one or more service classification and measurement agents includes a requesting application storing function within the media services manager.

6. The wireless end-user device of claim 5, wherein the media service manager is a first media service manager and the requesting application storing function is a first requesting application storing function, the device further comprising a second media service manager of a different type than the first media service manager, the service classification agent including a second requesting application storing function within the second media service manager.

7. The wireless end-user device of claim 6, further comprising a usage and classification database, the one or more service classification and measurement agents to receive application association information stored by the first and second requesting application storing functions, and to maintain the usage and classification database based in part on the received application association information.

8. The wireless end-user device of claim 3, wherein to manage network data transfers for the media object by interfacing with the at least one network stack comprises to map the data transfer request and network resource identifier to one or more data flow connections communicated through the device network stack.

9. The wireless end-user device of claim 1, further comprising a media player and a user interface, wherein the media object comprises media data that is, as a result of the media service manager management of network data transfers for the media object, received by the device and played by the media player through the user interface.

10. The wireless end-user device of claim 9, the media service manager to receive, from the application launching the data transfer request, a network resource indicator that identifies the media object,

return to the application a media object handle descriptor, call a proxy service to perform one or more network data transfers comprising the media object, accept, from the application, commands associated with the media object handle descriptor, and control playback of the media data by the media player based on the commands.

11. The wireless end-user device of claim 1, wherein the one or more service classification and measurement agents comprise:

126

a requesting application storage agent to, for each device application that makes a data transfer request using the second API, store application identification information and network resource identification information;

a network data flow storage agent to, for each network data flow associated with the media service manager, identify network data flow identification information; and

an association agent to match the network data flow identification information for a network data flow with application identification information for the network data transfer associated with the network data flow.

12. The wireless end-user device of claim 1, further comprising:

a local database to store data usage, including data usage for network data transfers managed by the media service manager on behalf of a device application, the stored data usage classified by device application;

a user interface; and

a user interface display agent to display the data usage classified by application to a user.

13. The wireless end-user device of claim 1, the one or more service classification and measurement agents to further associate one or more traffic flows, comprising the media object network data transfers, with the device application that makes the data transfer request, the device further comprising an enforcement agent to, based on the association between the one or more traffic flows and the device application, enforce an application-based usage control on network data usage by one or more of the device applications.

14. A method of operating a wireless end-user device when connected via a wireless modem to a wireless network, the method comprising:

operating a first network stack Application Programming Interface (API), containing at least one first call accessible to each of a plurality of device applications, the first network stack API callable by each of the plurality of device applications to open and use data flows via a network stack coupled to the wireless modem;

operating a second API containing at least one second call accessible to each of the plurality of device applications, the second API callable by each of the plurality of device applications to make a data transfer request for a media object associated with a network resource identifier supplied by the calling device application;

operating a media service manager prompted by the second call, the media service manager managing network data transfers for the media object by interfacing with the network stack to retrieve the media object associated with the network resource identifier via the wireless modem and the wireless network; and

associating wireless network data usage for the media object network data transfers with the device application that requests the data transfer for the media object, associating wireless network data usage for respective data packet flows opened and used via the first network stack API with the device application opening such respective data packet flow, and reconciling wireless network data usage for each of the plurality of device applications to track an aggregate wireless network data usage attributable to each of the plurality of device applications via both the first network stack API and the second API.

15. A wireless end-user device, comprising:

a wireless modem configurable to connect to a wireless network;

127

a network stack configurable to receive and transmit data via the wireless modem and the wireless network;

a first network stack Application Programming Interface (API), containing at least one first call to allow device applications to open and use data flows via the network stack, the wireless modem, and the at least one wireless network;

a second API containing at least one second call to allow device applications to make a data transfer request for a media object associated with a network resource identifier supplied by the device application, wherein the data transfer request comprises a network resource identifier that identifies a source of the data to be transferred, a proxy to the source of the data to be transferred, or the media object to be transferred, in particular, wherein the network resource identifier comprises one or more of an Internet Protocol address, a Uniform Resource Locator, a remote file name/address, a stream name, and an object name;

a media service manager prompted by the second call, to manage network data transfers for the media object by interfacing with the network stack to retrieve the media object associated with the network resource identifier via the wireless modem and the wireless network; and

a service classification agent to associate wireless network data usage for the media object network data transfers with the device application that requests the data transfer for the media object, wherein to associate data usage for the media object network data transfers with the device application that makes the data transfer request for the media object comprises to identify and store at least one of an application name, an application identifier, or a process identifier for the application that makes the data transfer request, each stored entry further comprising information about the corresponding network resource identifier for the data transfer request.

16. The wireless end-user device of claim 15, wherein the service classification agent includes a requesting application storing function within the media services manager.

17. The wireless end-user device of claim 16, wherein the media service manager is a first media service manager and the requesting application storing function is a first requesting application storing function, the device further comprising a second media service manager of a different type than the first media service manager, the service classification agent including a second requesting application storing function within the second media service manager.

18. The wireless end-user device of claim 17, further comprising a usage and classification reconciliation agent

128

and a usage and classification database, the usage and classification reconciliation agent to receive application association information stored by the first and second requesting application storing functions, and to maintain the usage and classification database based in part on the received application association information.

19. A wireless end-user device, comprising:

a wireless modem configurable to connect to a wireless network;

a network stack configurable to receive and transmit data via the wireless modem and the wireless network;

a first network stack Application Programming Interface (API), containing at least one first call to allow device applications to open and use data flows via the network stack, the wireless modem, and the at least one wireless network;

a second API containing at least one second call to allow device applications to make a data transfer request for a media object associated with a network resource identifier supplied by the device application, wherein the data transfer request comprises a network resource identifier that identifies a source of the data to be transferred, a proxy to the source of the data to be transferred, or the media object to be transferred, in particular, wherein the network resource identifier comprises one or more of an Internet Protocol address, a Uniform Resource Locator, a remote file name/address, a stream name, and an object name;

a media service manager prompted by the second call, to manage network data transfers for the media object by interfacing with the network stack to retrieve the media object associated with the network resource identifier via the wireless modem and the wireless network, wherein to manage network data transfers for the media object by interfacing with the at least one network stack comprises to map the data transfer request and network resource identifier to one or more data flow connections communicated through the device networking stack; and

a service classification agent to associate wireless network data usage for the media object network data transfers with the device application that requests the data transfer for the media object, wherein to associate data usage for the media object network data transfers with the device application that makes the data transfer request for the media object comprises to identify at least one of an application name, an application identifier, or a process identifier for the application that makes the data transfer request.

* * * * *