

FILE HISTORY
US 9,745,123

PATENT: 9,745,123
INVENTORS: PETERSEN BRIAN JAMES
SMITH DAVID RICHARD

TITLE: Seed carrier with pivoting conveyor

APPLICATION NO: US14606794A
FILED: 27 JAN 2015
ISSUED: 29 AUG 2017

COMPILED: 29 AUG 2024

Unverferth Exhibit 2024
Par-Kan v. Unverferth
IPR2024-01426

9,745,123

Seed carrier with pivoting conveyor

Transaction History

Date	Transaction Description
01-27-2015	Entity Status Set To Undiscounted (Initial Default Setting or Status Change)
01-27-2015	Initial Exam Team nn
02-06-2015	Electronic Review
02-06-2015	Email Notification
02-06-2015	Email Notification
02-06-2015	Filing Receipt
02-06-2015	Notice Mailed--Application Incomplete--Filing Date Assigned
04-06-2015	Information Disclosure Statement considered
04-06-2015	Reference capture on IDS
04-06-2015	Information Disclosure Statement (IDS) Filed
04-06-2015	Patent Term Adjustment - Ready for Examination
04-06-2015	Payment of additional filing fee-Preexam
04-06-2015	Information Disclosure Statement (IDS) Filed
04-09-2015	Application Dispatched from OIPE
04-09-2015	FITF set to NO - revise initial setting
04-10-2015	Email Notification
04-10-2015	Email Notification
04-10-2015	Change in Power of Attorney (May Include Associate POA)
04-10-2015	Application Is Now Complete
04-10-2015	Filing Receipt - Updated
05-11-2015	Preliminary Amendment
05-11-2015	Preliminary Amendment
07-16-2015	PG-Pub Issue Notification
07-17-2015	Email Notification
08-31-2015	Application ready for PDX access by participating foreign offices
09-03-2015	Case Docketed to Examiner in GAU
01-09-2017	Non-Final Rejection
01-26-2017	Electronic Review
01-26-2017	Email Notification
01-26-2017	Mail Non-Final Rejection
04-26-2017	Response after Non-Final Action
04-26-2017	Electronic Information Disclosure Statement
04-26-2017	Information Disclosure Statement (IDS) Filed
05-03-2017	Date Forwarded to Examiner
06-26-2017	Information Disclosure Statement considered
07-03-2017	Notice of Allowance Data Verification Completed
07-06-2017	Mail Notice of Allowance
07-09-2017	Email Notification
07-10-2017	Electronic Review
07-13-2017	Issue Fee Payment Verified
07-13-2017	Issue Fee Payment Received
07-18-2017	Application Is Considered Ready for Issue
07-25-2017	Dispatch to FDC
08-09-2017	Issue Notification Mailed
08-10-2017	Email Notification
08-29-2017	Recordation of Patent Grant Mailed
08-29-2017	Patent Issue Date Used in PTA Calculation
02-18-2021	Payment of Maintenance Fee, 4th Year, Large Entity

Issue Classification 	Application/Control No. 14606794	Applicant(s)/Patent Under Reexamination PETERSEN ET AL.	
	Examiner WILLIE BERRY JR	Art Unit 3652	

CPC					Type	Version
Symbol						
B65D	88			54	F	2013-01-01
B60P	1			00	A	2013-01-01
A01C	15			003	I	2013-01-01
A01C	15			006	I	2013-01-01
B60P	1			36	I	2013-01-01
B65G	65			32	I	2013-01-01
B65G	65			40	I	2013-01-01
B65G	65			42	I	2013-01-01

CPC Combination Sets					Type	Set	Ranking	Version
Symbol								

/WILLIE BERRY JR/ Examiner, Art Unit 3652 (Assistant Examiner)	6/26/17 (Date)	Total Claims Allowed: 21	
/SAUL RODRIGUEZ/ Supervisory Patent Examiner, Art Unit 3652 (Primary Examiner)	06/26/2017 (Date)	O.G. Print Claim(s) 39	O.G. Print Figure 1

Issue Classification 	Application/Control No. 14606794	Applicant(s)/Patent Under Reexamination PETERSEN ET AL.
	Examiner WILLIE BERRY JR	Art Unit 3652

☒ Claims renumbered in the same order as presented by applicant ☐ CPA ☐ T.D. ☐ R.1.47															
Final	Original	Final	Original	Final	Original	Final	Original	Final	Original	Final	Original	Final	Original	Final	Original
	39		56												
	40		57												
	41		58												
	42		59												
	43		60												
	44														
	45														
	46														
	48														
	49														
	50														
	51														
	52														
	53														
	54														
	55														

/WILLIE BERRY JR/ Examiner, Art Unit 3652 (Assistant Examiner)	6/26/17 (Date)	Total Claims Allowed: 21	
/SAUL RODRIGUEZ/ Supervisory Patent Examiner, Art Unit 3652 (Primary Examiner)	06/26/2017 (Date)	O.G. Print Claim(s) 39	O.G. Print Figure 1

Index of Claims 	Application/Control No. 14606794	Applicant(s)/Patent Under Reexamination PETERSEN ET AL.
	Examiner WILLIE BERRY JR.	Art Unit 3652

✓	Rejected	-	Cancelled	N	Non-Elected	A	Appeal
=	Allowed	÷	Restricted	I	Interference	O	Objected

☐ Claims renumbered in the same order as presented by applicant				☐ CPA		☐ T.D.		☐ R.1.47	
CLAIM		DATE							
Final	Original	01/09/2017	06/26/2017						
	1	-							
	2	-							
	3	-							
	4	-							
	5	-							
	6	-							
	7	-							
	8	-							
	9	-							
	10	-							
	11	-							
	12	-							
	13	-							
	14	-							
	15	-							
	16	-							
	17	-							
	18	-							
	19	-							
	20	-							
	21	-							
	22	-							
	23	-							
	24	-							
	25	-							
	26	-							
	27	-							
	28	-							
	29	-							
	30	-							
	31	-							
	32	-							
	33	-							
	34	-							
	35	-							
	36	-							

Index of Claims 	Application/Control No. 14606794	Applicant(s)/Patent Under Reexamination PETERSEN ET AL.
	Examiner WILLIE BERRY JR.	Art Unit 3652

✓	Rejected	-	Cancelled	N	Non-Elected	A	Appeal
=	Allowed	÷	Restricted	I	Interference	O	Objected

☐ Claims renumbered in the same order as presented by applicant				☐ CPA		☐ T.D.		☐ R.1.47	
CLAIM		DATE							
Final	Original	01/09/2017	06/26/2017						
	37	-							
	38	-							
	39	✓	=						
	40	✓	=						
	41	✓	=						
	42	✓	=						
	43	✓	=						
	44	✓	=						
	45	✓	=						
	46	✓	=						
	47	O	-						
	48	✓	=						
	49	=	=						
	50	=	=						
	51	=	=						
	52	=	=						
	53	=	=						
	54	=	=						
	55	=	=						
	56	=	=						
	57	=	=						
	58	=	=						
	59	=	=						
	60	=	=						

Index of Claims 	Application/Control No. 14606794	Applicant(s)/Patent Under Reexamination PETERSEN ET AL.
	Examiner WILLIE BERRY JR.	Art Unit 3652

✓	Rejected	-	Cancelled	N	Non-Elected	A	Appeal
=	Allowed	÷	Restricted	I	Interference	O	Objected

☐ Claims renumbered in the same order as presented by applicant			☐ CPA			☐ T.D.			☐ R.1.47			
CLAIM			DATE									
Final	Original	01/09/2017										
	1	-										
	2	-										
	3	-										
	4	-										
	5	-										
	6	-										
	7	-										
	8	-										
	9	-										
	10	-										
	11	-										
	12	-										
	13	-										
	14	-										
	15	-										
	16	-										
	17	-										
	18	-										
	19	-										
	20	-										
	21	-										
	22	-										
	23	-										
	24	-										
	25	-										
	26	-										
	27	-										
	28	-										
	29	-										
	30	-										
	31	-										
	32	-										
	33	-										
	34	-										
	35	-										
	36	-										

Index of Claims 	Application/Control No. 14606794	Applicant(s)/Patent Under Reexamination PETERSEN ET AL.
	Examiner WILLIE BERRY JR.	Art Unit 3652

✓	Rejected	-	Cancelled	N	Non-Elected	A	Appeal
=	Allowed	÷	Restricted	I	Interference	O	Objected

☐ Claims renumbered in the same order as presented by applicant			☐ CPA			☐ T.D.			☐ R.1.47			
CLAIM			DATE									
Final	Original	01/09/2017										
	37	-										
	38	-										
	39	✓										
	40	✓										
	41	✓										
	42	✓										
	43	✓										
	44	✓										
	45	✓										
	46	✓										
	47	O										
	48	✓										
	49	=										
	50	=										
	51	=										
	52	=										
	53	=										
	54	=										
	55	=										
	56	=										
	57	=										
	58	=										
	59	=										
	60	=										

Search Notes 	Application/Control No. 14606794	Applicant(s)/Patent Under Reexamination PETERSEN ET AL.
	Examiner WILLIE BERRY JR	Art Unit 3652

CPC- SEARCHED		
Symbol	Date	Examiner

CPC COMBINATION SETS - SEARCHED		
Symbol	Date	Examiner

US CLASSIFICATION SEARCHED			
Class	Subclass	Date	Examiner

SEARCH NOTES		
Search Notes	Date	Examiner
Updated Search in parent applications 13/541,553 & 12/031,867	1/9/17	WB

INTERFERENCE SEARCH			
US Class/ CPC Symbol	US Subclass / CPC Group	Date	Examiner

--	--

Search Notes 	Application/Control No. 14606794	Applicant(s)/Patent Under Reexamination PETERSEN ET AL.
	Examiner WILLIE BERRY JR	Art Unit 3652

CPC- SEARCHED		
Symbol	Date	Examiner
B60P1/00, 36, 42	6/26/17	WB

CPC COMBINATION SETS - SEARCHED		
Symbol	Date	Examiner

US CLASSIFICATION SEARCHED			
Class	Subclass	Date	Examiner
414	523	6/26/17	WB
111	11	6/26/17	WB
198	312, 315, 316, 317, 318	6/26/17	WB

SEARCH NOTES		
Search Notes	Date	Examiner
Updated Search in parent applications 13/541,553 & 12/031,867	1/9/17	WB
Updated Search	6/26/17	WB

INTERFERENCE SEARCH			
US Class/ CPC Symbol	US Subclass / CPC Group	Date	Examiner
All US Class	All US Subclasses	6/26/17	WB

--	--

EAST Search History

EAST Search History

EAST Search History (Prior Art)

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L1	589	(414/523).OCLS	US-PGPUB; USPAT	OR	OFF	2017/06/26 06:58
L2	156	(111/11).OCLS	US-PGPUB; USPAT	OR	OFF	2017/06/26 07:02
L3	730	(198/312,315,316,317,318).OCLS	US-PGPUB; USPAT	OR	OFF	2017/06/26 07:03
L4	1565	B60P1/00.cpc.	US-PGPUB; USPAT; FPRS; EPO; JPO; DERWENT	OR	OFF	2017/06/26 07:07
L5	1272	B60P1/36.cpc.	US-PGPUB; USPAT; FPRS; EPO; JPO; DERWENT	OR	OFF	2017/06/26 07:13
L6	590	B60P1/42.cpc.	US-PGPUB; USPAT; FPRS; EPO; JPO; DERWENT	OR	OFF	2017/06/26 07:17

6/ 26/ 2017 7:58:11 AM

C:\Users\wberry\Documents\EAST\Workspaces\14606794.wsp

EAST Search History

EAST Search History

EAST Search History (Interference)

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L7	1	"main hopper" and discharge and arm and conveyor and hopper and elevator and "hydraulic piston" and first and second and third and axis and rotatable and perpendicular	US- PGPUB; USPAT	AND	OFF	2017/06/26 07:35

6/ 26/ 2017 7:58:39 AM

C:\Users\wberry\Documents\EAST\Workspaces\14606794.wsp



US009745123B2

(12) **United States Patent**
Petersen et al.

(10) **Patent No.:** **US 9,745,123 B2**
(45) **Date of Patent:** **Aug. 29, 2017**

(54) **SEED CARRIER WITH PIVOTING CONVEYOR**

(71) Applicant: **UNVERFERTH MANUFACTURING COMPANY, INC.**, Kalida, OH (US)

(72) Inventors: **Brian James Petersen**, Ottawa, OH (US); **David Richard Smith**, Fort Jennings, OH (US)

(73) Assignee: **UNVERFERTH MANUFACTURING COMPANY, INC.**, Kalida, OH (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 305 days.

(21) Appl. No.: **14/606,794**

(22) Filed: **Jan. 27, 2015**

(65) **Prior Publication Data**
US 2015/0197395 A1 Jul. 16, 2015

Related U.S. Application Data

(63) Continuation of application No. 13/541,553, filed on Jul. 3, 2012, now Pat. No. 8,967,940, which is a (Continued)

(51) **Int. Cl.**
B65F 1/00 (2006.01)
B65D 88/54 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **B65D 88/54** (2013.01); **A01C 15/003** (2013.01); **A01C 15/006** (2013.01); **B60P 1/36** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC B60P 1/00; B60P 1/36; B60P 1/42
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

427,736 A 5/1890 Bufkin 198/317
1,905,434 A 4/1933 Boyer 414/328
(Continued)

FOREIGN PATENT DOCUMENTS

CA 2416677 A1 8/2004
FR 2465667 A1 3/1981

OTHER PUBLICATIONS

Model 2300 Air System and the Model 4800 Air Drill, both made and sold by Concord, as illustrated in the Concord brochure, 12 pages.

(Continued)

Primary Examiner — Saul Rodriguez


Assistant Examiner — Willie Berry, Jr.

(74) *Attorney, Agent, or Firm* — Rothwell, Figg, Ernst & Manbeck, P.C.

(57) **ABSTRACT**

A seed carrier includes a main hopper coupled with a frame via leg members. The main hopper has a discharge. A base plate is coupled with the frame. A support arm is rotatably coupled with the base plate at a first end. A belt driven conveyor having a conveyor hopper at a first end and a discharge at a second end is rotatably coupled with a second end of the support arm at an approximate center of gravity thereof. A latch mechanism is provided for detachably coupling the first end of the conveyor with the first end of the support arm such that the conveyor hopper is positioned below the main hopper discharge. When the conveyor is uncoupled from the first end of the support arm, the conveyor can rotate to a loading position wherein the discharge thereof can be positioned over the main hopper.

21 Claims, 11 Drawing Sheets



Related U.S. Application Data

continuation of application No. 12/031,867, filed on Feb. 15, 2008, now Pat. No. 8,221,047.

- (60) Provisional application No. 60/901,321, filed on Feb. 15, 2007.

(51) Int. Cl.

A01C 15/00 (2006.01)

B60P 1/36 (2006.01)

B65G 65/32 (2006.01)

B65G 65/40 (2006.01)

B65G 65/42 (2006.01)

B60P 1/00 (2006.01)

(52) U.S. Cl.

CPC **B65G 65/32** (2013.01); **B65G 65/40** (2013.01); **B65G 65/42** (2013.01); **B60P 1/00** (2013.01)

(58) Field of Classification Search

USPC 414/523; 111/11; 198/312, 315, 316, 198/317, 318

See application file for complete search history.

(56) References Cited**U.S. PATENT DOCUMENTS**


3,090,515 A 5/1963 Crowther
3,493,136 A 2/1970 Spellman, Jr.
3,498,483 A 3/1970 Meharry 414/523
3,968,771 A 7/1976 Walgenbach et al. 118/303
3,994,512 A 11/1976 Parker et al. 280/687
3,997,215 A 12/1976 Parker et al. 298/24
4,037,745 A 7/1977 Hengen et al.
4,218,169 A 8/1980 Arends
4,274,790 A 6/1981 Barker
4,312,621 A 1/1982 Quanbeck et al.
4,411,581 A 10/1983 Niewold
4,419,037 A 12/1983 Niewold
4,491,216 A 1/1985 Sawby
4,503,803 A 3/1985 Barnes 118/303
4,613,275 A 9/1986 Karlowsky
4,742,938 A 5/1988 Niewold
5,013,208 A 5/1991 Grieshop
5,468,113 A 11/1995 Davis
5,484,249 A 1/1996 Klatt 414/523
5,516,253 A 5/1996 Linscheid et al.
5,520,495 A 5/1996 Sukup 414/523
5,529,455 A 6/1996 Kaster et al.
5,538,388 A 7/1996 Bergkamp et al.
5,582,221 A 12/1996 Smith et al.
5,615,990 A 4/1997 Grieshop 414/526
5,718,556 A 2/1998 Forsyth 414/503
5,785,481 A 7/1998 Ockels
5,800,116 A 9/1998 Smith et al. 414/523
5,888,044 A * 3/1999 Baskerville B60P 1/42
198/311
5,980,189 A 11/1999 Rubner

6,113,339 A 9/2000 Adams 414/502
6,120,233 A 9/2000 Adam 277/402
6,209,880 B1 4/2001 Turnwald et al. 414/526
6,325,588 B1 12/2001 Nolin 198/312
6,604,620 B2 8/2003 Dennis 414/523
6,767,174 B2 7/2004 Cresswell
6,908,380 B2 6/2005 Silver
7,223,059 B2 5/2007 Smith et al.
7,267,519 B2 9/2007 Cresswell et al.
7,393,275 B2 7/2008 Voss et al.
7,428,956 B2 9/2008 Scherman 198/312
7,488,149 B2 2/2009 Waldner 414/532
7,500,814 B2 3/2009 Meyer
7,500,817 B2 * 3/2009 Furrer A01C 15/003
198/311
7,553,228 B2 6/2009 Dillon
8,221,047 B2 7/2012 Petersen et al. 414/523
2003/0057055 A1 3/2003 Haukaas et al. 198/313
2006/0180062 A1 8/2006 Furrer et al.
2009/0110524 A1 4/2009 Hoffmann 414/507

OTHER PUBLICATIONS

Convey-All, BTS 290 Seed Tender Product Specification, 2 pages.
Convey-All Ind. Inc., Engineering Drawings of BT-1500, 4 pages.
Par-Kan Company, Engineering Drawings, 2 pages.
Great Plains Manufacturing, Inc., Parts Manual—Model ADC2220 Air Drill Cart, May 1, 1997, 61 pages.
Great Plains Manufacturing, Inc., Parts Manual—Model ADC2220 Air Drill Cart, Mar. 1, 2000, 69 pages.
Reexamination File History for Control No. 95000691, 374 pages.
Order Denying Request for Inter Partes Reexamination for Control No. 95000691, Nov. 7, 2012, 15 pages.
Par-Kan Company, Final Invalidation Contentions submitted in *Unverferth Mfg. Co., Inc. v. Par-Kan Co.*, Civil Action No. 13-cv-00097 (N.D. Ind.), Oct. 25, 2013, 130 pages.
Par-Kan Company, Preliminary Invalidation Contentions submitted in *Unverferth Mfg. Co., Inc. v. Par-Kan Co.*, Civil Action No. 13-cv-00097 (N.D. Ind.), Jun. 17, 2013, 169 pages.
Declaration of Shawn Gerdeman with Exhibits A-E dated Sep. 18, 2014, 24 pages.
Hiniker Company, Model 4836 Air Seeder Cart with 4800 Air Drill Front Folding Toolbar, Operator's Manual, Jan. 1999, 58 pages.
Hiniker Company, Models 4831, 4832, and 4833 Air Seeder Cart with 4800 Air Seeder Front Folding Toolbar, Assembly Manual, Jan. 2000, 49 pages.
Hiniker 4831, 4832, 4833 Air Seeder, Jul. 21, 1999, 1 page.
Hiniker Company, Fill Auger Support Assembly, 1 page.
Hiniker Company, 4800 Soybean Planter Marketing Material, 6 pages.
Hiniker Company, Product Photographs, 67 pages.
J&M Manufacturing Company, Inc., Annotated Photographs of Hiniker Company 4836 Air Seed Cart, 8 pages.
Great Plains Manufacturing, 220 Bushel Air Cart, 2 pages.
J&M Manufacturing Company, Inc., J&M Mfg. Co., Inc.'s Amended Initial Invalidation Contentions submitted in *Unverferth Mfg. Co., Inc. v. J&M Mfg. Co., Inc.*, Civil Action No. 3:16-cv-02282-JZ (N.D. Ohio), Feb. 7, 2017, 59 pages.

* cited by examiner








FIG. 2








FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG.11

1
SEED CARRIER WITH PIVOTING
CONVEYOR

CROSS-REFERENCE TO RELATED
APPLICATIONS

The present application is a Continuation of U.S. application Ser. No. 13/541,553, filed Jul. 3, 2012, which claims priority to U.S. application Ser. No. 12/031,867, filed Feb. 15, 2008, now U.S. Pat. No. 8,221,047, which claims priority to Provisional Patent Application Ser. No. 60/901,321 filed on Feb. 15, 2007, the entire disclosures of which are incorporated herein by reference.

BACKGROUND OF THE INVENTION

Field of the Invention

The present invention relates generally to a conveyor system for a grain or seed carrier. The conveyor system includes a novel pivot system that allows it to either load or unload a container by pivoting it into a loading or unloading position.

Description of the Related Art

Conveyor systems for moving grain, seed, etc. are well known. Auger systems are used to rapidly move grain such as feed or the like, while belt driven conveyors are often used for moving more expensive payload, such as seed.

One belt driven conveyor system includes a generally flat belt constructed from a flexible, sturdy material such as rubber or nylon. The conveyor is housed in a tube with rollers on both ends so that the belt may rotate in order to transmit material from one end to the other. Such conveyors are used for unloading seed carriers or the like. However, current conveyors have several problems.

First, current conveyors have the problem that the material being moved can be damaged by the rollers. Second, current conveyors do not have a full range of motion as implemented in seed carries. Third, current conveyors are only implemented for unloading.

There is a need for new and improved conveyor systems that allow a wagon to be unloaded and loaded using a single mechanism.

SUMMARY OF THE INVENTION

According to an embodiment of the present invention, a seed tender or carrier is provided that includes a main hopper for holding seed and a conveyor for transferring seed to and from the main hopper.

According to an embodiment of the present invention, in an unloading position, one end of the conveyor may be positioned under the discharge of the main hopper and coupled with a pivoting support arm. In the unload position, the conveyor can be used to transfer seed from the main hopper to another location, such as to a planter, seeding unit, or the like. A pivot mechanism allows the conveyor to be rotated from under the box into a loading position in which the conveyor intake can rest on the ground or on a stand while the conveyor discharge is positioned to allow conveyed material to be discharged into the main hopper. In this loading position, the conveyor can be used to fill the main hopper.

According to an embodiment of the present invention, a conveyor hopper is provided on the intake side of the conveyor.

According to an embodiment of the present invention, the pivot mechanism allows the conveyor to swing from side to

2

side to simplify unloading of the main hopper and the filling of planters, etc. The pivot mechanism can include a hydraulic cylinder that adjusts the vertical height of the conveyor discharge relative for different filling applications.

According to an embodiment of the present invention, a pivot single pivot point can be provided at one end of the support arm to allow the conveyor to be rotated between the loading and unloading position. The conveyor may be balanced on the pivot point at a location near or at the center of gravity, thereby permitting the conveyor to be rotated with minimal effort on the part of the operator.

According to an embodiment of the present invention, the conveyor can be rotated through at least 180 degrees about a vertical axis and so that it may be positioned in either a forward or rearward transport position. This feature enables the tender to be pulled by different vehicles such as by a pick-up truck with the conveyor forward or by a grain truck with the conveyor rearward.

Further applications and advantages of various aspects and embodiments of the present invention are discussed below with reference to the drawing figures.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates a seed carrier according to an embodiment of the present invention.

FIG. 2 is a view of a seed carrier in an unloading position according to an embodiment of the present invention.

FIG. 3 is a view of a seed carrier in a loading position according to an embodiment of the present invention.

FIG. 4 is a view of a base system for the seed carrier according to an embodiment of the present invention.

FIG. 5 is a view of a lever mechanism for the base system according to an embodiment of the present invention.

FIG. 6 is a view of a seed carrier in a transport position according to an embodiment of the present invention.

FIG. 7 is a view of a belt conveyor for the seed carrier according to an embodiment of the present invention.

FIG. 8 is a view of the discharge end of a conveyor according to an embodiment of the present invention.

FIG. 9 is a forward view of a conveyor belt wrapping around a roller according to an embodiment of the present invention.

FIG. 10 is a view of the conveyor hopper in an unloading position according to an embodiment of the present invention.

FIG. 11 illustrates the receiving end of the conveyor according to one embodiment of the present invention.

DETAILED DESCRIPTION OF THE
PREFERRED EMBODIMENTS

While the present invention may be embodied in many different forms, a number of illustrative embodiments are described herein with the understanding that the present disclosure is to be considered as providing examples of the principles of the invention and such examples are not intended to limit the invention to preferred embodiments described herein and/or illustrated herein.

In embodiments of the present invention, the novel conveyor pivot system can be implemented with seed carrier or seeding machines. The following section describes non-limiting examples of illustrative seeding equipment according to embodiments of the present invention. It should be appreciated that the following examples are provided for illustration and the present invention is not intended to be limited to the embodiments described herein.

3

FIG. 1 is a diagram depicting a seed carrier having a tube conveyor according to an embodiment of the present invention. The seed carrier 100 includes a main hopper 105 coupled to a frame 107 by legs 106. A conveyor 104 is supported by a support arm 102 coupled with a pivoting mechanism 101 fixed to the frame 107. The conveyor 104 is pivotably coupled with the support arm by a coupling 103 at a point that is preferably near or at the center of gravity of the conveyor 104. The conveyor 104 is also coupled to the support arm 102 by a latch (not shown) at the bottom of the conveyor. The latch allows the conveyor 104 to be uncoupled from the support arm 102 at the bottom so that the conveyor is free to rotate about the coupling 103. By positioning the coupling 103 at or near the center of gravity of the conveyor 104, the conveyor 104 balances on the pivoting coupling 103 such that little effort is required to rotate the conveyor 104.

The conveyor 104 includes a conveyor hopper 108 at its base, which is shown in the unloading position below the gravity discharge 110 of the main hopper 105. At the other end of the conveyor 104 is the discharge 112. Seed can be gravity feed from the main hopper 105 into the conveyor hopper 108, which can then be moved to the discharge 112 of the conveyor 104 by an internal elevator (not shown). In one embodiment, the elevator is a motor-driven belt type elevator coupled onto rollers at both ends of the conveyor.

The seed carrier 100 may be transported by conventional means such as on a trailer. FIG. 2 illustrates the seed carrier 100 on a three axle trailer 200 according to an embodiment of the present invention. As shown, the conveyor 104 is in the unloading position.

FIG. 3 illustrates the seed carrier 100 in the loading position. As shown, the conveyor 104 is uncoupled from the support arm 102 at its base and rotated 180 degrees about pivot coupling 103 so that the conveyor hopper 108 is positioned at a convenient location away from the carrier while the discharge 112 of the conveyor 104 is located over the main hopper 105. A stand 307 is provided for holding the conveyor hopper 108 in place. The stand 307 may be integrated with the conveyor 104.

Accordingly, in the loading position, grain, seed or like can be feed into the conveyor hopper 108 to be moved to the discharge 112 for filling the main hopper 105.

FIG. 4 is a view of the pivoting base of the support arm 102. As shown, the support arm 102 can be pivotably coupled to a base 401 at a center point so that the support arm 102 is rotatable about a vertical axis. Wheels 403 provide support and can run along a track 402 to facilitate the support arm's 102 motion about the perimeter of the base 401. The support arm 102 can be locked into a selected position of the base 401 by engaging a pin (not shown) with one of a plurality of the holes 407 distributed around the base 401. The pin is disengaged with a hole by actuating a lever mechanism 404, which lifts the pin out of a hole. The lever mechanism 404 may be spring actuated to bias the pin toward the holes, so that simply releasing the lever will allow the pin to engage with one of the holes 407. Also shown, a hydraulic piston 405 is coupled with the support arm 102 for adjusting the height of the support arm 102.

FIG. 5 is an alternative view of the support arm base. As shown, lever mechanism 404 includes a handle 504 coupled with a cross-bars 505 and 506. Cross-bar 506 is coupled to cross-bar 505 on one end and to a plate 508 having a pin 509 on the other end, and with a pivoting coupling 502 at a point near the plate. Rotating the handle 504 applies a downward force to crossbar 506 causing it to rotate about the coupling 502 to raise the plate 508 to disengage the pin 509. While

4

disengaged, the base 401 is free to rotate about its vertical axis. Springs may be provided for biasing the pin 509 toward the holes 407 for engaging therewith, or the pin 509 can be engaged by gravity.

FIG. 6 is a side view of a seed carrier 100 according to an embodiment of the present invention. As shown in FIG. 6, the conveyor 104 includes an elongated discharge spout 602 and is positioned in a transport position. Support members 604 may be mounted on or integral with the legs 106 for holding the conveyor 104 in a forward transport position as shown, or a rearward transport position. As shown, the carrier 100 is fixed to a dual axle trailer 606.

FIG. 7 illustrates a basic belt driven conveyor according to an embodiment of the present invention. The conveyor 104 comprises a belt 702 that winds about a pair of rollers 704. The rollers are positioned outside a tube section 706, a first roller being positioned in the discharge 112 and a second roller being positioned below the conveyor hopper 108. A motor (not shown) or other means for turning the rollers may be provided at either end of the conveyor. A void 707 exists below the rollers 704 to allow the belt 702 to travel on its return path.

FIG. 8 is a view of a conveyor belt according to an embodiment of the present invention. The discharge end of a conveyor is shown where a conveyor belt wraps around a motor driven roller 802. The motor may be a hydraulic motor and therefore, hydraulic hoses 804 provide hydraulic fluid flow to and from the motor. Teeth 806 are provided to push grain or seed up the conveyor. As shown, the conveyor belt is cupped in the tube section but flattens out as it reaches the roller 802. Channeling members (seals) 808 are provided on each side of the belt to form a seal and prevent grain or seed from falling off the edges of the belt as the belt begins to conform to the tubular portion of the conveyor 104.

FIG. 9 is a front view of the belt as it travels over the roller 802. Channeling members (seals) 902 are provided on each side of the belt to form a seal and prevent grain or seed from falling off the edges of the belt as the belt flattens at the roller. As shown, the channeling members 902 are fixed to the conveyor discharge 112 with bolts, but can be fixed by other means or can be integral with the discharge.

Discs 904 are provided at the rollers at the edge of the belt to provide additional channeling/sealing means. The discs 904 are preferably integral with the rollers or coupled therewith so that they may rotate.

FIG. 10 is a side view of the hopper end of the conveyor 104. As shown, conveyor hopper 108 sits above in ingress to the conveyor 104. When coupled to the support arm 102, as shown, the conveyor hopper 108 is positioned below a discharge of the main hopper 106. The discharge 110 may be opened by conventional means. As showed, a wheel handle mechanism 1004 is provided for opening the discharge doors 1006.

The conveyor hopper 108 is preferably manufactured from light weight materials such as plastic, canvas, rubber or vinyl. As shown, the hopper 108 may include a mechanism for opening and closing the hopper. In this embodiment, flexible coupling or hinge is provided at one end 1008 of the hopper 108 and a mechanism 1010 is provided at the end of the hopper 108 and is coupled with the conveyor 104, such that the hopper 108 may be made to have an appropriate fit with the discharge 110 of the main hopper 105. A flap 1012 can be provided at the bottom of the discharge 110.

FIG. 11 is a schematic view of the hopper end of the conveyor. As is shown, a brush seal 1101 can be located across the belt 702. The brush seal 1101 retains the conveyed material within the hopper and does not allow the material

5

to enter the void 707 (shown in FIG. 7) under the roller. Such an arrangement is desirable because it prevents the conveyed material from being subjected to mechanical agitation, which would result in damage to the conveyed material. The brush seal 1101 allows the conveyor teeth 806 to pass, but not the conveyed material.

One will understand that hydraulic power can be provided by a towing vehicle, such as a tractor or the like or alternatively, hydraulic power can be provided on the tender and driving electrically from the towing vehicle, such as a truck.

Thus, a number of preferred embodiments have been fully described above with reference to the drawing figures. Although the invention has been described based upon these preferred embodiments, it would be apparent to those of skill in the art that certain modifications, variations, and alternative constructions could be made to the described embodiments within the spirit and scope of the invention.

We claim:

1. A seed or grain tender comprising:

a main hopper having a main hopper discharge;

a support arm having first and second ends;

said first end of said support arm being located below said main hopper and being rotatable about a first axis of rotation, and said first end of said support arm being rotatable about a second axis of rotation that is perpendicular to said first axis of rotation;

a conveyor having a longitudinal axis and first and second ends, a conveyor hopper at said first end, a conveyor discharge at said second end, and an internal elevator for moving seed or grain from said conveyor hopper to said conveyor discharge;

said second end of said support arm being coupled with said conveyor between said first and second ends of said conveyor, said conveyor being rotatable about a third axis of rotation at said second end of said support arm that is not parallel to said conveyor longitudinal axis, and said conveyor being rotatable in relation to said second end of said support arm about said third axis of rotation between an unloading position wherein said conveyor hopper is disposed below said main hopper discharge to receive agricultural product from said main hopper and a loading position wherein said conveyor discharge is disposed above said main hopper to dispense agricultural product into said main hopper, and

a hydraulic piston extending at an acute angle relative to a horizontal plane to connect with a portion of said support arm spaced from said second axis of rotation.

2. The seed or grain tender of claim 1, wherein said first axis of rotation extends through said main hopper discharge.

3. The seed or grain tender of claim 1, wherein said second axis of rotation extends through said first end of said support arm.

4. The seed or grain tender of claim 1, wherein said third axis of rotation extends through said conveyor.

5. The seed or grain tender of claim 1, wherein said third axis of rotation extends through said second end of said support arm.

6. The seed or grain tender of claim 1, wherein said third axis of rotation extends through said conveyor and said second end of said support arm.

7. The seed or grain tender of claim 1, wherein said third axis of rotation is oriented at an angle having a vertical component.

6

8. The seed or grain tender of claim 1, wherein said second end of said support arm is coupled with said conveyor at or near said approximate center of gravity of said conveyor.

9. The seed or grain tender of claim 1, further comprising a stand coupled with said first end of said conveyor and movable between a stowed position allowing said conveyor hopper to be positioned below said main hopper discharge when said conveyor is in said unloading position and an extended position supporting said conveyor hopper above the ground when said conveyor is in said loading position.

10. A seed or grain tender comprising:

a main hopper having an upper portion with a main hopper intake opening and a lower portion with a main hopper discharge;

a support arm having a first end proximate said lower portion of said main hopper and a second end;

wherein said support arm is pivotable about a first axis of rotation proximate said first end of said support arm to cause said support arm to be movable between an operating position wherein said support arm extends outwardly relative to said main hopper and a storage position wherein said support arm is folded inwardly towards said main hopper in relation to said operating position, said support arm further being pivotable about a second axis of rotation proximate said first end of said support arm to cause an elevation of said second end of said support arm to be adjustable;

a conveyor having a longitudinal axis and first and second ends, a conveyor hopper at said first end, a conveyor discharge at said second end, and an internal elevator for moving seed or grain from said conveyor hopper to said conveyor discharge; and

said second end of said support arm being coupled with said conveyor between said first and second conveyor ends, said conveyor being rotatable about a third axis of rotation proximate said second end of said support arm that is not parallel to said conveyor longitudinal axis, and said conveyor being rotatable in relation to said second end of said support arm about said third axis of rotation between an unloading position wherein said conveyor hopper is disposed below said main hopper discharge to receive agricultural product from said main hopper and a loading position wherein said conveyor discharge is disposed above said intake opening of said main hopper to dispense agricultural product into said main hopper.

11. The seed or grain tender of claim 10, wherein said first axis of rotation extends through said main hopper discharge.

12. The seed or grain tender of claim 10, wherein said second axis of rotation extends through said first end of said support arm.

13. The seed or grain tender of claim 10, wherein said third axis of rotation extends through said conveyor.

14. The seed or grain tender of claim 10, wherein said third axis of rotation extends through said second end of said support arm.

15. The seed or grain tender of claim 10, wherein said third axis of rotation extends through said conveyor and said second end of said support arm.

16. The seed or grain tender of claim 10, wherein said third axis of rotation is oriented at an angle having a vertical component.

17. The seed or grain tender of claim 16, wherein said first axis of rotation is vertical.

18. The seed or grain tender of claim 17, wherein said second axis of rotation is horizontal.

19. The seed or grain tender of claim 10, wherein said second end of said support arm is coupled with said conveyor at an approximate center of gravity of said conveyor.

20. The seed or grain tender of claim 10, further comprising a hydraulic piston extending at an acute angle relative to a horizontal plane to connect with a portion of said support arm spaced from said second axis of rotation. 5

21. The seed or grain tender of claim 10, further comprising a stand coupled with said first end of said conveyor and movable between a stowed position allowing said conveyor hopper to be positioned below said main hopper discharge when said conveyor is in said unloading position and an extended position supporting said conveyor hopper above the ground when said conveyor is in said loading position. 15

* * * * *



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
 United States Patent and Trademark Office
 Address: COMMISSIONER FOR PATENTS
 P.O. Box 1450
 Alexandria, Virginia 22313-1450
 www.uspto.gov

BIB DATA SHEET

CONFIRMATION NO. 1047

SERIAL NUMBER	FILING or 371(c) DATE	CLASS	GROUP ART UNIT	ATTORNEY DOCKET NO.	
14/606,794	01/27/2015	414	3652	1994-363US2	
APPLICANTS UNVERFERTH MANUFACTURING COMPANY, INC., Kalida, OH; INVENTORS Brian James PETERSEN, Ottawa, OH; David Richard SMITH, Fort Jennings, OH; ** CONTINUING DATA ***** This application is a CON of 13/541,553 07/03/2012 PAT 8967940 which is a CON of 12/031,867 02/15/2008 PAT 8221047 which claims benefit of 60/901,321 02/15/2007 ** FOREIGN APPLICATIONS ***** ** IF REQUIRED, FOREIGN FILING LICENSE GRANTED ** 02/05/2015					
Foreign Priority claimed ☐ Yes ☒ No 35 USC 119(a-d) conditions met ☐ Yes ☒ No Verified and <u>WILLIE WENDELL BERRY JR.</u> Acknowledged <u>Examiner's signature</u>		☐ Not after Allowance STATE OR COUNTRY OH	SHEETS DRAWINGS 11	TOTAL CLAIMS 38	INDEPENDENT CLAIMS 2
ADDRESS ROTHWELL, FIGG, ERNST & MANBECK, P.C. 607 14th Street, N.W. SUITE 800 WASHINGTON, DC 20005 UNITED STATES					
TITLE SEED CARRIER WITH PIVOTING CONVEYOR					
FILING FEE RECEIVED 3180	FEES: Authority has been given in Paper No. _____ to charge/credit DEPOSIT ACCOUNT No. _____ for following:			☐ All Fees ☐ 1.16 Fees (Filing) ☐ 1.17 Fees (Processing Ext. of time) ☐ 1.18 Fees (Issue) ☐ Other ☐ Credit	

Electronic Acknowledgement Receipt	
EFS ID:	21323642
Application Number:	14606794
International Application Number:	
Confirmation Number:	1047
Title of Invention:	SEED CARRIER WITH PIVOTING CONVEYOR
First Named Inventor/Applicant Name:	Brian James PETERSEN
Customer Number:	6449
Filer:	Jason M. Shapiro/Carole Klayuhn
Filer Authorized By:	Jason M. Shapiro
Attorney Docket Number:	1994-363US2
Receipt Date:	27-JAN-2015
Filing Date:	
Time Stamp:	17:39:26
Application Type:	Utility under 35 USC 111(a)

Payment information:					
Submitted with Payment			no		
File Listing:					
Document Number	Document Description	File Name	File Size(Bytes)/ Message Digest	Multi Part /.zip	Pages (if appl.)
1	Application Data Sheet	1994-363US2-ADS.pdf	1101826 c9e0113722553201010c086100002100001 [...]	no	7
Warnings:					
Information:					

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

Application Data Sheet 37 CFR 1.76		Attorney Docket Number	1994-363US2
		Application Number	
Title of Invention	SEED CARRIER WITH PIVOTING CONVEYOR		
The application data sheet is part of the provisional or nonprovisional application for which it is being submitted. The following form contains the bibliographic data arranged in a format specified by the United States Patent and Trademark Office as outlined in 37 CFR 1.76. This document may be completed electronically and submitted to the Office in electronic format using the Electronic Filing System (EFS) of the document may be printed and included in a paper filed application.			

Secrecy Order 37 CFR 5.2

☐	Portions or all of the application associated with this Application Data Sheet may fall under a Secrecy Order pursuant to 37 CFR 5.2. (Paper filers only. Applications that fall under Secrecy Order may not be filed electronically.)
--------------------------	--

Inventor Information:

Inventor 1 Remove					
Legal Name					
Prefix	Given Name	Middle Name	Family Name	Suffix	
	Brian	James	PETERSEN		
Residence Information (Select One) ☒ US Residency ☐ Non US Residency ☐ Active US Military Service					
City	Ottawa	State/Province	OH	Country of Residence	US
Mailing Address of Inventor:					
Address 1		16124 Road L			
Address 2					
City	Ottawa	State/Province	OH		
Postal Code	45785	Country i	US		
Inventor 2 Remove					
Legal Name					
Prefix	Given Name	Middle Name	Family Name	Suffix	
	David	Richard	SMITH		
Residence Information (Select One) ☒ US Residency ☐ Non US Residency ☐ Active US Military Service					
City	Fort Jennings	State/Province	OH	Country of Residence	US
Mailing Address of Inventor:					
Address 1		21761 Road 21			
Address 2					
City	Fort Jennings	State/Province	OH		
Postal Code	45844	Country i	US		
All Inventors Must Be Listed - Additional Inventor Information blocks may be generated within this form by selecting the Add button. Add					

Correspondence Information:

Enter either Customer Number or complete the Correspondence Information section below. For further information see 37 CFR 1.33(a).

Under the Paperwork Reduction Act of 1985, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

Application Data Sheet 37 CFR 1.76		Attorney Docket Number	1994-363US2
		Application Number	
Title of Invention	SEED CARRIER WITH PIVOTING CONVEYOR		

☐ An Address is being provided for the correspondence information of this application.			
Customer Number	06449		
Email Address	pto-pat-email@rfem.com	Add Email	Remove Email

Application Information:

Title of the Invention	SEED CARRIER WITH PIVOTING CONVEYOR		
Attorney Docket Number	1994-363US2	Small Entity Status Claimed	☐
Application Type	Nonprovisional		
Subject Matter	Utility		
Total Number of Drawing Sheets (if any)	11	Suggested Figure for Publication (if any)	

Filing By Reference :

Only complete this section when filing an application by reference under 35 U.S.C. 111(c) and 37 CFR 1.57(a). Do not complete this section if application papers including a specification and any drawings are being filed. Any domestic benefit or foreign priority information must be provided in the appropriate section(s) below (i.e., "Domestic Benefit/National Stage Information" and "Foreign Priority Information").

For the purposes of a filing date under 37 CFR 1.53(b), the description and any drawings of the present application are replaced by this reference to the previously filed application, subject to conditions and requirements of 37 CFR 1.57(a).

Application number of the previously filed application	Filing date (YYYY-MM-DD)	Intellectual Property Authority or Country

Publication Information:

☐ Request Early Publication (Fee required at time of Request 37 CFR 1.219)
☐ Request Not to Publish. I hereby request that the attached application not be published under 35 U.S.C. 122(b) and certify that the invention disclosed in the attached application has not and will not be the subject of an application filed in another country, or under a multilateral international agreement, that requires publication at eighteen months after filing.

Representative Information:

Representative information should be provided for all practitioners having a power of attorney in the application. Providing this information in the Application Data Sheet does not constitute a power of attorney in the application (see 37 CFR 1.32). Either enter Customer Number or complete the Representative Name section below. If both sections are completed the customer Number will be used for the Representative information during processing.

Please Select One:	☒ Customer Number	☐ US Patent Practitioner	☐ Limited Recognition (37 CFR 11.9)
Customer Number	06449		

Application Data Sheet 37 CFR 1.76		Attorney Docket Number	1994-363US2
		Application Number	
Title of Invention	SEED CARRIER WITH PIVOTING CONVEYOR		

Domestic Benefit/National Stage Information:

This section allows for the applicant to either claim benefit under 35 U.S.C. 119(e), 120, 121, or 365(c) or indicate National Stage entry from a PCT application. Providing this information in the application data sheet constitutes the specific reference required by 35 U.S.C. 119(e) or 120, and 37 CFR 1.78.

When referring to the current application, please leave the application number blank.

Prior Application Status	Pending	Remove			
Application Number	Continuity Type	Prior Application Number	Filing Date (YYYY-MM-DD)		
	Continuation of	13541553	2012-07-03		
Prior Application Status	Patented	Remove			
Application Number	Continuity Type	Prior Application Number	Filing Date (YYYY-MM-DD)	Patent Number	Issue Date (YYYY-MM-DD)
13541553	Continuation of	12031867	2008-02-15	8221047	2012-07-17
Prior Application Status	Expired	Remove			
Application Number	Continuity Type	Prior Application Number	Filing Date (YYYY-MM-DD)		
12031867	Claims benefit of provisional	60901321	2007-02-15		
Additional Domestic Benefit/National Stage Data may be generated within this form by selecting the Add button.					

Foreign Priority Information:

This section allows for the applicant to claim priority to a foreign application. Providing this information in the application data sheet constitutes the claim for priority as required by 35 U.S.C. 119(b) and 37 CFR 1.55(d). When priority is claimed to a foreign application that is eligible for retrieval under the priority document exchange program (PDX)¹ the information will be used by the Office to automatically attempt retrieval pursuant to 37 CFR 1.55(h)(1) and (2). Under the PDX program, applicant bears the ultimate responsibility for ensuring that a copy of the foreign application is received by the Office from the participating foreign intellectual property office, or a certified copy of the foreign priority application is filed, within the time period specified in 37 CFR 1.55(g)(1).

Remove			
Application Number	Country ¹	Filing Date (YYYY-MM-DD)	Access Code ² (if applicable)
Additional Foreign Priority Data may be generated within this form by selecting the Add button.			

Application Data Sheet 37 CFR 1.76		Attorney Docket Number	1994-363US2
		Application Number	
Title of Invention	SEED CARRIER WITH PIVOTING CONVEYOR		

Statement under 37 CFR 1.55 or 1.78 for AIA (First Inventor to File) Transition Applications

This application (1) claims priority to or the benefit of an application filed before March 16, 2013 and (2) also contains, or contained at any time, a claim to a claimed invention that has an effective filing date on or after March 16, 2013. ☐ NOTE: By providing this statement under 37 CFR 1.55 or 1.78, this application, with a filing date on or after March 16, 2013, will be examined under the first inventor to file provisions of the AIA.
--

Authorization to Permit Access:

☐ Authorization to Permit Access to the Instant Application by the Participating Offices If checked, the undersigned hereby grants the USPTO authority to provide the European Patent Office (EPO), the Japan Patent Office (JPO), the Korean Intellectual Property Office (KIPO), the World Intellectual Property Office (WIPO), and any other intellectual property offices in which a foreign application claiming priority to the instant patent application is filed access to the instant patent application. See 37 CFR 1.14(c) and (h). This box should not be checked if the applicant does not wish the EPO, JPO, KIPO, WIPO, or other intellectual property office in which a foreign application claiming priority to the instant patent application is filed to have access to the instant patent application. In accordance with 37 CFR 1.14(h)(3), access will be provided to a copy of the instant patent application with respect to: 1) the instant patent application-as-filed; 2) any foreign application to which the instant patent application claims priority under 35 U.S.C. 119(a)-(d) if a copy of the foreign application that satisfies the certified copy requirement of 37 CFR 1.55 has been filed in the instant patent application; and 3) any U.S. application-as-filed from which benefit is sought in the instant patent application. In accordance with 37 CFR 1.14(c), access may be provided to information concerning the date of filing this Authorization.

Applicant Information:

Providing assignment information in this section does not substitute for compliance with any requirement of part 3 of Title 37 of CFR to have an assignment recorded by the Office.
--

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

Application Data Sheet 37 CFR 1.76		Attorney Docket Number	1994-363US2
		Application Number	
Title of Invention	SEED CARRIER WITH PIVOTING CONVEYOR		

Applicant 1			
If the applicant is the inventor (or the remaining joint inventor or inventors under 37 CFR 1.45), this section should not be completed. The information to be provided in this section is the name and address of the legal representative who is the applicant under 37 CFR 1.43; or the name and address of the assignee, person to whom the inventor is under an obligation to assign the invention, or person who otherwise shows sufficient proprietary interest in the matter who is the applicant under 37 CFR 1.46. If the applicant is an applicant under 37 CFR 1.46 (assignee, person to whom the inventor is obligated to assign, or person who otherwise shows sufficient proprietary interest) together with one or more joint inventors, then the joint inventor or inventors who are also the applicant should be identified in this section.			
Clear			
☒ Assignee	☐ Legal Representative under 35 U.S.C. 117	☐ Joint Inventor	
☐ Person to whom the inventor is obligated to assign.		☐ Person who shows sufficient proprietary interest	
If applicant is the legal representative, indicate the authority to file the patent application, the inventor is:			
Name of the Deceased or Legally Incapacitated Inventor:			
If the Applicant is an Organization check here. ☒			
Organization Name	UNVERFERTH MANUFACTURING COMPANY, INC.		
Mailing Address Information For Applicant:			
Address 1	601 South Broad Street		
Address 2			
City	Kalida	State/Province	OH
Country	US	Postal Code	45853
Phone Number		Fax Number	
Email Address			
Additional Applicant Data may be generated within this form by selecting the Add button.			

Assignee Information including Non-Applicant Assignee Information:

Providing assignment information in this section does not substitute for compliance with any requirement of part 3 of Title 37 of CFR to have an assignment recorded by the Office.	
Assignee 1	
Complete this section if assignee information, including non-applicant assignee information, is desired to be included on the patent application publication. An assignee-applicant identified in the "Applicant Information" section will appear on the patent application publication as an applicant. For an assignee-applicant, complete this section only if identification as an assignee is also desired on the patent application publication.	
If the Assignee or Non-Applicant Assignee is an Organization check here. ☒	

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

Application Data Sheet 37 CFR 1.76		Attorney Docket Number	1994-363US2
		Application Number	
Title of Invention	SEED CARRIER WITH PIVOTING CONVEYOR		
Organization Name	UNVERFERTH MANUFACTURING COMPANY, INC.		
Mailing Address Information For Assignee including Non-Applicant Assignee:			
Address 1	601 South Broad Street		
Address 2			
City	Kalida	State/Province	OH
Country ⁱ	US	Postal Code	45853
Phone Number		Fax Number	
Email Address			
Additional Assignee or Non-Applicant Assignee Data may be generated within this form by selecting the Add button.			

Signature:

NOTE: This form must be signed in accordance with 37 CFR 1.33. See 37 CFR 1.4 for signature requirements and certifications.			
Signature			Date (YYYY-MM-DD)
First Name	Jason M.	Last Name	Shapiro
Registration Number	35354		
Additional Signature may be generated within this form by selecting the Add button.			

This collection of information is required by 37 CFR 1.76. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 23 minutes to complete, including gathering, preparing, and submitting the completed application data sheet form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.**

Privacy Act Statement

The Privacy Act of 1974 (P.L. 93-579) requires that you be given certain information in connection with your submission of the attached form related to a patent application or patent. Accordingly, pursuant to the requirements of the Act, please be advised that: (1) the general authority for the collection of this information is 35 U.S.C. 2(b)(2); (2) furnishing of the information solicited is voluntary; and (3) the principal purpose for which the information is used by the U.S. Patent and Trademark Office is to process and/or examine your submission related to a patent application or patent. If you do not furnish the requested information, the U.S. Patent and Trademark Office may not be able to process and/or examine your submission, which may result in termination of proceedings or abandonment of the application or expiration of the patent.

The information provided by you in this form will be subject to the following routine uses:

1. The information on this form will be treated confidentially to the extent allowed under the Freedom of Information Act (5 U.S.C. 552) and the Privacy Act (5 U.S.C. 552a). Records from this system of records may be disclosed to the Department of Justice to determine whether the Freedom of Information Act requires disclosure of these records.
2. A record from this system of records may be disclosed, as a routine use, in the course of presenting evidence to a court, magistrate, or administrative tribunal, including disclosures to opposing counsel in the course of settlement negotiations.
3. A record in this system of records may be disclosed, as a routine use, to a Member of Congress submitting a request involving an individual, to whom the record pertains, when the individual has requested assistance from the Member with respect to the subject matter of the record.
4. A record in this system of records may be disclosed, as a routine use, to a contractor of the Agency having need for the information in order to perform a contract. Recipients of information shall be required to comply with the requirements of the Privacy Act of 1974, as amended, pursuant to 5 U.S.C. 552a(m).
5. A record related to an International Application filed under the Patent Cooperation Treaty in this system of records may be disclosed, as a routine use, to the International Bureau of the World Intellectual Property Organization, pursuant to the Patent Cooperation Treaty.
6. A record in this system of records may be disclosed, as a routine use, to another federal agency for purposes of National Security review (35 U.S.C. 181) and for review pursuant to the Atomic Energy Act (42 U.S.C. 218(c)).
7. A record from this system of records may be disclosed, as a routine use, to the Administrator, General Services, or his/her designee, during an inspection of records conducted by GSA as part of that agency's responsibility to recommend improvements in records management practices and programs, under authority of 44 U.S.C. 2904 and 2906. Such disclosure shall be made in accordance with the GSA regulations governing inspection of records for this purpose, and any other relevant (i.e., GSA or Commerce) directive. Such disclosure shall not be used to make determinations about individuals.
8. A record from this system of records may be disclosed, as a routine use, to the public after either publication of the application pursuant to 35 U.S.C. 122(b) or issuance of a patent pursuant to 35 U.S.C. 151. Further, a record may be disclosed, subject to the limitations of 37 CFR 1.14, as a routine use, to the public if the record was filed in an application which became abandoned or in which the proceedings were terminated and which application is referenced by either a published application, an application open to public inspections or an issued patent.
9. A record from this system of records may be disclosed, as a routine use, to a Federal, State, or local law enforcement agency, if the USPTO becomes aware of a violation or potential violation of law or regulation.

1/11




FIG. 1

2/11






FIG. 2

3/11



4/11



5/11





FIG. 5

6/11



7/11




FIG. 7

8/11




FIG. 8

9/11





FIG.9

10/11



11/11




FIG.11

TITLE OF THE INVENTION

SEED CARRIER WITH PIVOTING CONVEYOR

BACKGROUND OF THE INVENTION

Cross-Reference to Related Applications

[0001] The present application is a Continuation of U.S. application Serial No. 13/541,553, filed July 3, 2012, which claims priority to U.S. application Serial No. 12/031,867, filed February 15, 2008, now Patent No. 8,221,047, which claims priority to Provisional Patent Application Serial. No. 60/901,321 filed on Feb. 15, 2007, the entire disclosures of which are incorporated herein by reference.

Field of the Invention

[0002] The present invention relates generally to a conveyor system for a grain or seed carrier. The conveyor system includes a novel pivot system that allows it to either load or unload a container by pivoting it into a loading or unloading position.

Description of the Related Art

[0003] Conveyor systems for moving grain, seed, etc. are well known. Auger systems are used to rapidly move grain such as feed or the like, while belt driven conveyors are often used for moving more expensive payload, such as seed.

[0004] One belt driven conveyor system includes a generally flat belt constructed from a flexible, sturdy material such as rubber or nylon. The conveyor is housed in a tube with rollers on both ends so that the belt may rotate in order to transmit material from one end to the other. Such conveyors are used for unloading seed carriers or the like. However, current conveyors have several problems.

[0005] First, current conveyors have the problem that the material being moved can be damaged by the rollers. Second, current conveyors do not have a full range of motion as implemented in seed carries. Third, current conveyors are only implemented for unloading.

[0006] There is a need for new and improved conveyor systems that allow a wagon to be unloaded and loaded using a single mechanism.

SUMMARY OF THE INVENTION

[0007] According to an embodiment of the present invention, a seed tender or carrier is provided that includes a main hopper for holding seed and a conveyor for transferring seed to and from the main hopper.

[0008] According to an embodiment of the present invention, in an unloading position, one end of the conveyor may be positioned under the discharge of the main hopper and coupled with a pivoting support arm. In the unload position, the conveyor can be used to transfer seed from the main hopper to another location, such as to a planter, seeding unit, or the like. A pivot mechanism allows the conveyor to be rotated from under the box into a loading position in which the conveyor intake can rest on the ground or on a stand while the conveyor discharge is positioned to allow conveyed material to be discharged into the main hopper. In this loading position, the conveyor can be used to fill the main hopper.

[0009] According to an embodiment of the present invention, a conveyor hopper is provided on the intake side of the conveyor.

[0010] According to an embodiment of the present invention, the pivot

mechanism allows the conveyor to swing from side to side to simplify unloading of the main hopper and the filling of planters, etc. The pivot mechanism can include a hydraulic cylinder that adjusts the vertical height of the conveyor discharge relative for different filling applications.

[0011] According to an embodiment of the present invention, a pivot single pivot point can be provided at one end of the support arm to allow the conveyor to be rotated between the loading and unloading position. The conveyor may be balanced on the pivot point at a location near or at the center of gravity, thereby permitting the conveyor to be rotated with minimal effort on the part of the operator.

[0012] According to an embodiment of the present invention, the conveyor can be rotated through at least 180 degrees about a vertical axis and so that it may be positioned in either a forward or rearward transport position. This feature enables the tender to be pulled by different vehicles such as by a pick-up truck with the conveyor forward or by a grain truck with the conveyor rearward.

[0013] Further applications and advantages of various aspects and embodiments of the present invention are discussed below with reference to the drawing figures.

BRIEF DESCRIPTION OF THE DRAWINGS

[0014] FIG. 1 illustrates a seed carrier according to an embodiment of the present invention.

[0015] FIG. 2 is a view of a seed carrier in an unloading position according to an embodiment of the present invention.

[0016] FIG. 3 is a view of a seed carrier in a loading position according to an embodiment of the present invention.

[0017] Fig. 4 is a view of a base system for the seed carrier according to an embodiment of the present invention.

[0018] Fig. 5 is a view of a lever mechanism for the base system according to an embodiment of the present invention.

[0019] Fig. 6 is a view of a seed carrier in a transport position according to an embodiment of the present invention.

[0020] Fig. 7 is a view of a belt conveyor for the seed carrier according to an embodiment of the present invention.

[0021] Fig. 8 is a view of the discharge end of a conveyor according to an embodiment of the present invention.

[0022] Fig. 9 is a forward view of a conveyor belt wrapping around a roller according to an embodiment of the present invention.

[0023] Fig. 10 is a view of the conveyor hopper in an unloading position according to an embodiment of the present invention.

[0024] Fig. 11 illustrates the receiving end of the conveyor according to one embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0025] While the present invention may be embodied in many different forms, a number of illustrative embodiments are described herein with the understanding that the present disclosure is to be considered as providing examples of the principles of the invention and such examples are not intended to limit the invention to preferred embodiments described herein and/or illustrated herein.

[0026] In embodiments of the present invention, the novel conveyor pivot system

can be implemented with seed carrier or seeding machines. The following section describes non-limiting examples of illustrative seeding equipment according to embodiments of the present invention. It should be appreciated that the following examples are provided for illustration and the present invention is not intended to be limited to the embodiments described herein.

[0027] FIG. 1 is a diagram depicting a seed carrier having a tube conveyor according to an embodiment of the present invention. The seed carrier 100 includes a main hopper 105 coupled to a frame 107 by legs 106. A conveyor 104 is supported by a support arm 102 coupled with a pivoting mechanism 101 fixed to the frame 107. The conveyor 104 is pivotably coupled with the support arm by a coupling 103 at a point that is preferably near or at the center of gravity of the conveyor 104. The conveyor 104 is also coupled to the support arm 102 by a latch (not shown) at the bottom of the conveyor. The latch allows the conveyor 104 to be uncoupled from the support arm 102 at the bottom so that the conveyor is free to rotate about the coupling 103. By positioning the coupling 103 at or near the center of gravity of the conveyor 104, the conveyor 104 balances on the pivoting coupling 103 such that little effort is required to rotate the conveyor 104.

[0028] The conveyor 104 includes a conveyor hopper 108 at its base, which is shown in the unloading position below the gravity discharge 110 of the main hopper 105. At the other end of the conveyor 104 is the discharge 112. Seed can be gravity feed from the main hopper 105 into the conveyor hopper 108, which can then be moved to the discharge 112 of the conveyor 104 by an internal elevator (not shown). In one embodiment, the elevator is a motor-driven belt type elevator coupled onto rollers at

both ends of the conveyor.

[0029] The seed carrier 100 may be transported by conventional means such as on a trailer. Fig. 2 illustrates the seed carrier 100 on a three axle trailer 200 according to an embodiment of the present invention. As shown, the conveyor 104 is in the unloading position.

[0030] Fig. 3 illustrates the seed carrier 100 in the loading position. As shown, the conveyor 104 is uncoupled from the support arm 102 at its base and rotated 180 degrees about pivot coupling 103 so that the conveyor hopper 108 is positioned at a convenient location away from the carrier while the discharge 112 of the conveyor 104 is located over the main hopper 105. A stand 307 is provided for holding the conveyor hopper 108 in place. The stand 307 may be integrated with the conveyor 104.

[0031] Accordingly, in the loading position, grain, seed or like can be feed into the conveyor hopper 108 to be moved to the discharge 112 for filling the main hopper 105.

[0032] Fig. 4 is a view of the pivoting base of the support arm 102. As shown, the support arm 102 can be pivotably coupled to a base 401 at a center point so that the support arm 102 is rotatable about a vertical axis. Wheels 403 provide support and can run along a track 402 to facilitate the support arm's 102 motion about the perimeter of the base 401. The support arm 102 can be locked into a selected position of the base 401 by engaging a pin (not shown) with one of a plurality of the holes 407 distributed around the base 401. The pin is disengaged with a hole by actuating a lever mechanism 404, which lifts the pin out of a hole. The lever mechanism 404 may be spring actuated to bias the pin toward the holes, so that simply releasing the lever will allow the pin to engage with one of the holes 407. Also shown, a hydraulic piston 405 is coupled with

the support arm 102 for adjusting the height of the support arm 102.

[0033] Fig. 5 is an alternative view of the support arm base. As shown, lever mechanism 404 includes a handle 504 coupled with a cross-bars 505 and 506. Cross-bar 506 is coupled to cross-bar 505 on one end and to a plate 508 having a pin 509 on the other end, and with a pivoting coupling 502 at a point near the plate. Rotating the handle 504 applies a downward force to crossbar 506 causing it to rotate about the coupling 502 to raise the plate 508 to disengage the pin 509. While disengaged, the base 401 is free to rotate about its vertical axis. Springs may be provided for biasing the pin 509 toward the holes 407 for engaging therewith, or the pin 509 can be engaged by gravity.

[0034] Fig. 6 is a side view of a seed carrier 100 according to an embodiment of the present invention. As shown in FIG. 6, the conveyor 104 includes an elongated discharge spout 602 and is positioned in a transport position. Support members 604 may be mounted on or integral with the legs 106 for holding the conveyor 104 in a forward transport position as shown, or a rearward transport position. As shown, the carrier 100 is fixed to a dual axle trailer 606.

[0035] Fig. 7 illustrates a basic belt driven conveyor according to an embodiment of the present invention. The conveyor 104 comprises a belt 702 that winds about a pair of rollers 704. The rollers are positioned outside a tube section 706, a first roller being positioned in the discharge 112 and a second roller being positioned below the conveyor hopper 108. A motor (not shown) or other means for turning the rollers may be provided at either end of the conveyor. A void 707 exists below the rollers 704 to allow the belt 702 to travel on its return path.

[0036] Fig. 8 is a view of a conveyor belt according to an embodiment of the present invention. The discharge end of a conveyor is shown where a conveyor belt wraps around a motor driven roller 802. The motor may be a hydraulic motor and therefore, hydraulic hoses 804 provide hydraulic fluid flow to and from the motor. Teeth 806 are provided to push grain or seed up the conveyor. As shown, the conveyor belt is cupped in the tube section but flattens out as it reaches the roller 802. Channeling members (seals) 808 are provided on each side of the belt to form a seal and prevent grain or seed from falling off the edges of the belt as the belt begins to conform to the tubular portion of the conveyor 104.

[0037] Fig. 9 is a front view of the belt as it travels over the roller 802. Channeling members (seals) 902 are provided on each side of the belt to form a seal and prevent grain or seed from falling off the edges of the belt as the belt flattens at the roller. As shown, the channeling members 902 are fixed to the conveyor discharge 112 with bolts, but can be fixed by other means or can be integral with the discharge.

[0038] Discs 904 are provided at the rollers at the edge of the belt to provide additional channeling/sealing means. The discs 904 are preferably integral with the rollers or coupled therewith so that they may rotate.

[0039] FIG. 10 is a side view of the hopper end of the conveyor 104. As shown, conveyor hopper 108 sits above in ingress to the conveyor 104. When coupled to the support arm 102, as shown, the conveyor hopper 108 is positioned below a discharge of the main hopper 106. The discharge 110 may be opened by conventional means. As showed, a wheel handle mechanism 1004 is provided for opening the discharge doors 1006.

[0040] The conveyor hopper 108 is preferably manufactured from light weight materials such as plastic, canvas, rubber or vinyl. As shown, the hopper 108 may include a mechanism for opening and closing the hopper. In this embodiment, flexible coupling or hinge is provided at one end 1008 of the hopper 108 and a mechanism 1010 is provided at the end of the hopper 108 and is coupled with the conveyor 104, such that the hopper 108 may be made to have an appropriate fit with the discharge 110 of the main hopper 105. A flap 1012 can be provided at the bottom of the discharge 110.

[0041] FIG. 11 is a schematic view of the hopper end of the conveyor. As is shown, a brush seal 1101 can be located across the belt 702. The brush seal 1101 retains the conveyed material within the hopper and does not allow the material to enter the void 707 (shown in FIG. 7) under the roller. Such an arrangement is desirable because it prevents the conveyed material from being subjected to mechanical agitation, which would result in damage to the conveyed material. The brush seal 1101 allows the conveyor teeth 806 to pass, but not the conveyed material.

[0042] One will understand that hydraulic power can be provided by a towing vehicle, such as a tractor or the like or alternatively, hydraulic power can be provided on the tender and driving electrically from the towing vehicle, such as a truck.

[0043] Thus, a number of preferred embodiments have been fully described above with reference to the drawing figures. Although the invention has been described based upon these preferred embodiments, it would be apparent to those of skill in the art that certain modifications, variations, and alternative constructions could be made to the described embodiments within the spirit and scope of the invention.

We claim:

1. A seed or grain tender comprising:

a frame;

a main hopper mounted on said frame and having a main hopper discharge;

a base mounted on said frame below said main hopper discharge;

a support arm having first and second ends;

a first coupling connecting said first end of said support arm with said base, said first coupling being rotatable in relation to said base about a first vertical axis of rotation, and said first end of said support arm being rotatable in relation to said first coupling about a first horizontal axis of rotation;

a conveyor having a longitudinal axis and first and second ends, a conveyor hopper at said first end, a conveyor discharge at said second end, and an internal elevator for moving seed or grain from said conveyor hopper to said conveyor discharge; and

a second coupling connecting said second end of said support arm with said conveyor at an approximate center of gravity of said conveyor, said second coupling defining a second vertical axis of rotation that is not parallel to said conveyor longitudinal axis, and said conveyor being rotatable in relation to said second end of said support arm about said second vertical axis of rotation between an unloading position wherein said conveyor hopper is disposed below said main hopper discharge to receive agricultural product from said main hopper and a loading position wherein said conveyor discharge is disposed above said main hopper to dispense agricultural product into said main hopper.

2. The seed or grain tender of claim 1, wherein said support arm extends upwardly at an acute angle from said base.

3. The seed or grain tender of claim 2, wherein said conveyor is parallel to said support arm in said unloading position.

4. The seed or grain tender of claim 3, wherein said conveyor is disposed above said support arm in said unloading position.
5. The seed or grain tender of claim 1, wherein said first end of said conveyor is detachably connectable to said first end of said support arm in said unloading position.
6. The seed or grain tender of claim 5, further comprising a latch for detachably connecting said first end of said conveyor to said first end of said support arm in said unloading position.
7. The seed or grain tender of claim 1, wherein said conveyor is rotatable in relation to said second coupling about a second horizontal axis of rotation.
8. The seed or grain tender of claim 7, wherein said second horizontal axis of rotation extends through said second coupling.
9. The seed or grain tender of claim 1, further comprising a stand coupled with said first end of said conveyor and movable between a stowed position allowing said conveyor hopper to be positioned below said main hopper discharge when said conveyor is in said unloading position and an extended position supporting said conveyor hopper above the ground when said conveyor is in said loading position.
10. The seed or grain tender of claim 1, wherein said first vertical axis extends through said first end of said support arm.
11. The seed or grain tender of claim 1, wherein said first vertical axis extends through said base.
12. The seed or grain tender of claim 1, wherein said second end of said support arm terminates at or near said approximate center of gravity of said conveyor.

13. The seed or grain tender of claim 1, wherein said first end of said support arm is fixed at a first height and said second end of said support arm is pivotable between a range of heights.
14. The seed or grain tender of claim 1, further comprising a lift device for adjusting a height of said second end of said support arm.
15. The seed or grain tender of claim 14, wherein said lift device is a pressurized cylinder.
16. The seed or grain tender of claim 14, wherein said lift device is a hydraulic cylinder.
17. The seed or grain tender of claim 1, wherein said first coupling is a U-shaped member with a horizontal base portion and a pair of upright portions, and wherein said first horizontal axis extends through said upright portions of said first coupling.
18. The seed or grain tender of claim 1, further comprising a locking mechanism for locking or unlocking said support arm in relation to said base.
19. The seed or grain tender of claim 18, wherein said locking mechanism includes a pin releasably engageable with one of a plurality of holes formed in said base.
20. The seed or grain tender of claim 19, wherein said pin is spring-biased toward said holes in said base.
21. The seed or grain tender of claim 19, wherein said internal elevator includes a motor-driven belt.
22. A seed or grain tender comprising:
a frame;
a main hopper mounted on said frame and having a main hopper discharge;

- a base mounted on said frame below said main hopper discharge;
- a support arm having first and second ends;
- a first coupling connecting said first end of said support arm with said base, said first coupling being rotatable in relation to said base about a first vertical axis of rotation, and said first end of said support arm being rotatable in relation to said first coupling about a first horizontal axis of rotation;
- a lift device extending from said base to a portion of said support arm between said first and second ends such that said support arm extends upwardly at an acute angle from said base;
- a conveyor having a longitudinal axis and first and second ends, a conveyor hopper at said first end, a conveyor discharge at said second end, and a motor-driven elevator for moving seed or grain from said conveyor hopper to said conveyor discharge; and
- a second coupling connecting said second end of said support arm with said conveyor at an approximate center of gravity of said conveyor, said second coupling defining a second vertical axis of rotation that is not parallel to said conveyor longitudinal axis, and said conveyor being rotatable in relation to said second end of said support arm about said second vertical axis of rotation between an unloading position wherein said conveyor hopper is disposed below said main hopper discharge to receive agricultural product from said main hopper and a loading position wherein said conveyor discharge is disposed above said main hopper to dispense agricultural product into said main hopper, wherein said conveyor is disposed parallel to and above said support arm in said unloading position; and
- a locking mechanism for locking and unlocking said support arm in relation to said base.

23. The seed or grain tender of claim 22, wherein said conveyor is disposed above said support arm in said unloading position.

24. The seed or grain tender of claim 22, wherein said first end of said conveyor is detachably connectable to said first end of said support arm in said unloading position.

25. The seed or grain tender of claim 24, further comprising a latch for detachably connecting said first end of said conveyor to said first end of said support arm in said unloading position.

26. The seed or grain tender of claim 22, wherein said conveyor is rotatable in relation to said second coupling about a second horizontal axis of rotation.

27. The seed or grain tender of claim 26, wherein said second horizontal axis of rotation extends through said second coupling.

28. The seed or grain tender of claim 22, further comprising a stand coupled with said first end of said conveyor and movable between a stowed position allowing said conveyor hopper to be positioned below said main hopper discharge when said conveyor is in said unloading position and an extended position supporting said conveyor hopper above the ground when said conveyor is in said loading position.

29. The seed or grain tender of claim 22, wherein said first vertical axis extends through said first end of said support arm.

30. The seed or grain tender of claim 22, wherein said first vertical axis extends through said base.

31. The seed or grain tender of claim 22, wherein said second end of said support arm terminates at or near said approximate center of gravity of said conveyor.

32. The seed or grain tender of claim 22, wherein said first end of said support arm is fixed at a first height and said second end of said support arm is pivotable between a range of heights.

33. The seed or grain tender of claim 22, wherein said lift device is a pressurized cylinder.

34. The seed or grain tender of claim 22, wherein said lift device is a hydraulic cylinder.

35. The seed or grain tender of claim 22, wherein said first coupling is a U-shaped member with a horizontal base portion and a pair of upright portions, and wherein said first horizontal axis extends through said upright portions of said first coupling.

36. The seed or grain tender of claim 22, wherein said locking mechanism includes a pin releasably engageable with one of a plurality of holes formed in said base.

37. The seed or grain tender of claim 36, wherein said pin is spring-biased toward said holes in said base.

38. The seed or grain tender of claim 22, wherein said internal elevator includes a motor-driven belt.

ABSTRACT

A seed carrier includes a main hopper coupled with a frame via leg members. The main hopper has a discharge. A base plate is coupled with the frame. A support arm is rotatably coupled with the base plate at a first end. A belt driven conveyor having a conveyor hopper at a first end and a discharge at a second end is rotatably coupled with a second end of said support arm at an approximate center of gravity thereof. A latch mechanism is provided for detachably coupling the first end of the conveyor with the first end of the support arm such that the conveyor hopper is positioned below the main hopper discharge. When the conveyor is uncoupled from the first end of the support arm, the conveyor can rotate to a loading position wherein the discharge thereof can be positioned over the main hopper.

File History Content Report

The following content is missing from the original file history record obtained from the United States Patent and Trademark Office. No additional information is available.

Document Date - 2015-01-27

Document Title - Applicant Communication Re: Entity Status Set to Undiscounted
(Initial Default Setting or Status Change)

This page is not part of the official USPTO record. It has been determined that content identified on this document is missing from the original file history record.



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1501
Alexandria, Virginia 22313-1501
www.uspto.gov

APPLICATION NUMBER	FILING or 371(c) DATE	USPTO UNIT	FIL FEE REC'D	ATTY DOCKET NO.	TOT CLAIMS	IND CLAIMS
14/606,794	01/27/2015	3652	0.00	1994-363US2	38	2

CONFIRMATION NO. 1047

FILING RECEIPT



OC000000073257169

6449
ROTHWELL, FIGG, ERNST & MANBECK, P.C.
607 14th Street, N.W.
SUITE 800
WASHINGTON, DC 20005

Date Mailed: 02/06/2015

Receipt is acknowledged of this non-provisional patent application. The application will be taken up for examination in due course. Applicant will be notified as to the results of the examination. Any correspondence concerning the application must include the following identification information: the U.S. APPLICATION NUMBER, FILING DATE, NAME OF APPLICANT, and TITLE OF INVENTION. Fees transmitted by check or draft are subject to collection. Please verify the accuracy of the data presented on this receipt. **If an error is noted on this Filing Receipt, please submit a written request for a Filing Receipt Correction. Please provide a copy of this Filing Receipt with the changes noted thereon. If you received a "Notice to File Missing Parts" for this application, please submit any corrections to this Filing Receipt with your reply to the Notice. When the USPTO processes the reply to the Notice, the USPTO will generate another Filing Receipt incorporating the requested corrections**

Inventor(s)

Brian James PETERSEN, Ottawa, OH;
David Richard SMITH, Fort Jennings, OH

Applicant(s)

UNVERFERTH MANUFACTURING COMPANY, INC., Kalida, OH

Power of Attorney: None

Domestic Priority data as claimed by applicant

This application is a CON of 13/541,553 07/03/2012
which is a CON of 12/031,867 02/15/2008 PAT 8221047
which claims benefit of 60/901,321 02/15/2007

Foreign Applications for which priority is claimed (You may be eligible to benefit from the **Patent Prosecution Highway** program at the USPTO. Please see <http://www.uspto.gov> for more information.) - None.

Foreign application information must be provided in an Application Data Sheet in order to constitute a claim to foreign priority. See 37 CFR 1.55 and 1.76.

If Required, Foreign Filing License Granted: 02/05/2015

The country code and number of your priority application, to be used for filing abroad under the Paris Convention, is **US 14/606,794**

Projected Publication Date: To Be Determined - pending completion of Missing Parts

Non-Publication Request: No

Early Publication Request: No

page 1 of 3

Title

SEED CARRIER WITH PIVOTING CONVEYOR

Preliminary Class

414

Statement under 37 CFR 1.55 or 1.78 for AIA (First Inventor to File) Transition Applications: No

PROTECTING YOUR INVENTION OUTSIDE THE UNITED STATES

Since the rights granted by a U.S. patent extend only throughout the territory of the United States and have no effect in a foreign country, an inventor who wishes patent protection in another country must apply for a patent in a specific country or in regional patent offices. Applicants may wish to consider the filing of an international application under the Patent Cooperation Treaty (PCT). An international (PCT) application generally has the same effect as a regular national patent application in each PCT-member country. The PCT process **simplifies** the filing of patent applications on the same invention in member countries, but **does not result** in a grant of "an international patent" and does not eliminate the need of applicants to file additional documents and fees in countries where patent protection is desired.

Almost every country has its own patent law, and a person desiring a patent in a particular country must make an application for patent in that country in accordance with its particular laws. Since the laws of many countries differ in various respects from the patent law of the United States, applicants are advised to seek guidance from specific foreign countries to ensure that patent rights are not lost prematurely.

Applicants also are advised that in the case of inventions made in the United States, the Director of the USPTO must issue a license before applicants can apply for a patent in a foreign country. The filing of a U.S. patent application serves as a request for a foreign filing license. The application's filing receipt contains further information and guidance as to the status of applicant's license for foreign filing.

Applicants may wish to consult the USPTO booklet, "General Information Concerning Patents" (specifically, the section entitled "Treaties and Foreign Patents") for more information on timeframes and deadlines for filing foreign patent applications. The guide is available either by contacting the USPTO Contact Center at 800-786-9199, or it can be viewed on the USPTO website at <http://www.uspto.gov/web/offices/pac/doc/general/index.html>.

For information on preventing theft of your intellectual property (patents, trademarks and copyrights), you may wish to consult the U.S. Government website, <http://www.stopfakes.gov>. Part of a Department of Commerce initiative, this website includes self-help "toolkits" giving innovators guidance on how to protect intellectual property in specific countries such as China, Korea and Mexico. For questions regarding patent enforcement issues, applicants may call the U.S. Government hotline at 1-866-999-HALT (1-866-999-4258).

LICENSE FOR FOREIGN FILING UNDER
Title 35, United States Code, Section 184
Title 37, Code of Federal Regulations, 5.11 & 5.15

GRANTED

The applicant has been granted a license under 35 U.S.C. 184, if the phrase "IF REQUIRED, FOREIGN FILING LICENSE GRANTED" followed by a date appears on this form. Such licenses are issued in all applications where the conditions for issuance of a license have been met, regardless of whether or not a license may be required as set forth in 37 CFR 5.15. The scope and limitations of this license are set forth in 37 CFR 5.15(a) unless an earlier license has been issued under 37 CFR 5.15(b). The license is subject to revocation upon written notification. The date indicated is the effective date of the license, unless an earlier license of similar scope has been granted under 37 CFR 5.13 or 5.14.

This license is to be retained by the licensee and may be used at any time on or after the effective date thereof unless it is revoked. This license is automatically transferred to any related applications(s) filed under 37 CFR 1.53(d). This license is not retroactive.

The grant of a license does not in any way lessen the responsibility of a licensee for the security of the subject matter as imposed by any Government contract or the provisions of existing laws relating to espionage and the national security or the export of technical data. Licensees should apprise themselves of current regulations especially with respect to certain countries, of other agencies, particularly the Office of Defense Trade Controls, Department of State (with respect to Arms, Munitions and Implements of War (22 CFR 121-128)); the Bureau of Industry and Security, Department of Commerce (15 CFR parts 730-774); the Office of Foreign Assets Control, Department of Treasury (31 CFR Parts 500+) and the Department of Energy.

NOT GRANTED

No license under 35 U.S.C. 184 has been granted at this time, if the phrase "IF REQUIRED, FOREIGN FILING LICENSE GRANTED" DOES NOT appear on this form. Applicant may still petition for a license under 37 CFR 5.12, if a license is desired before the expiration of 6 months from the filing date of the application. If 6 months has lapsed from the filing date of this application and the licensee has not received any indication of a secrecy order under 35 U.S.C. 181, the licensee may foreign file the application pursuant to 37 CFR 5.15(b).

SelectUSA

The United States represents the largest, most dynamic marketplace in the world and is an unparalleled location for business investment, innovation, and commercialization of new technologies. The U.S. offers tremendous resources and advantages for those who invest and manufacture goods here. Through SelectUSA, our nation works to promote and facilitate business investment. SelectUSA provides information assistance to the international investor community; serves as an ombudsman for existing and potential investors; advocates on behalf of U.S. cities, states, and regions competing for global investment; and counsels U.S. economic development organizations on investment attraction best practices. To learn more about why the United States is the best country in the world to develop technology, manufacture products, deliver services, and grow your business, visit <http://www.SelectUSA.gov> or call +1-202-482-6800.



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NUMBER	FILING OR 371(C) DATE	FIRST NAMED APPLICANT	ATTY. DOCKET NO./TITLE
14/606,794	01/27/2015	Brian James PETERSEN	1994-363US2

CONFIRMATION NO. 1047

FORMALITIES LETTER



6449
ROTHWELL, FIGG, ERNST & MANBECK, P.C.
607 14th Street, N.W.
SUITE 800
WASHINGTON, DC 20005

Date Mailed: 02/06/2015

NOTICE TO FILE MISSING PARTS OF NONPROVISIONAL APPLICATION

FILED UNDER 37 CFR 1.53(b)

Filing Date Granted

Items Required To Avoid Abandonment:

An application number and filing date have been accorded to this application. The item(s) indicated below, however, are missing. Applicant is given **TWO MONTHS** from the date of this Notice within which to file all required items below to avoid abandonment. Extensions of time may be obtained by filing a petition accompanied by the extension fee under the provisions of 37 CFR 1.136(a).

- The statutory basic filing fee is missing.
- The application search fee must be submitted.
- The application examination fee must be submitted.
- Additional claim fees of \$ **1440** as an undiscounted entity, including any required multiple dependent claim fee, are required. Applicant must submit the additional claim fees or cancel the additional claims for which fees are due.
- Surcharge as set forth in 37 CFR 1.16(f) must be submitted.
The surcharge is due for any one of:
 - late submission of the basic filing fee, search fee, or examination fee,
 - late submission of inventor's oath or declaration,
 - filing an application that does not contain at least one claim on filing, or
 - submission of an application filed by reference to a previously filed application.

SUMMARY OF FEES DUE:

The fee(s) required within **TWO MONTHS** from the date of this Notice to avoid abandonment is/are itemized below. No entity status discount is in effect. If applicant is qualified for small entity status, a written assertion of small entity status must be submitted to establish small entity status. (See 37 CFR 1.27). If applicant is qualified for micro entity status, an acceptable Certification of Micro Entity Status must be submitted to establish micro entity status. (See 37 CFR 1.29 and forms PTO/SB/15A and 15B.)

- \$ **280** basic filing fee.
- \$ **140** surcharge.
- \$ **600** search fee.
- \$ **720** examination fee.
- \$ **1440** for **18** total claims over 20.

- \$(0) previous unapplied payment amount,
- \$ 3180 TOTAL FEE BALANCE DUE.

Items Required To Avoid Processing Delays:

Applicant is notified that the above-identified application contains the deficiencies noted below. No period for reply is set forth in this notice for correction of these deficiencies. However, if a deficiency relates to the inventor's oath or declaration, the applicant must file an oath or declaration in compliance with 37 CFR 1.63, or a substitute statement in compliance with 37 CFR 1.64, executed by or with respect to each actual inventor no later than the expiration of the time period set in the "Notice of Allowability" to avoid abandonment. See 37 CFR 1.53(f).

- A properly executed inventor's oath or declaration has not been received for the following inventor(s):
Brian James PETERSEN
David Richard SMITH

Replies must be received in the USPTO within the set time period or must include a proper Certificate of Mailing or Transmission under 37 CFR 1.8 with a mailing or transmission date within the set time period. For more information and a suggested format, see Form PTO/SB/92 and MPEP 512.

Replies should be mailed to:

Mail Stop Missing Parts
Commissioner for Patents
P.O. Box 1450
Alexandria VA 22313-1450

Registered users of EFS-Web may alternatively submit their reply to this notice via EFS-Web, including a copy of this Notice and selecting the document description "Applicant response to Pre-Exam Formalities Notice".
<https://portal.uspto.gov/authenticate/AuthenticateUserLocalEPF.html>

For more information about EFS-Web please call the USPTO Electronic Business Center at 1-866-217-9197 or visit our website at <http://www.uspto.gov/ebc>.

If you are not using EFS-Web to submit your reply, you must include a copy of this notice.

/s/ztal

Office of Data Management, Application Assistance Unit (571) 272-4000, or (571) 272-4200, or 1-888-786-0101

Electronic Acknowledgement Receipt	
EFS ID:	21976870
Application Number:	14606794
International Application Number:	
Confirmation Number:	1047
Title of Invention:	SEED CARRIER WITH PIVOTING CONVEYOR
First Named Inventor/Applicant Name:	Brian James PETERSEN
Customer Number:	6449
Filer:	Brian S. Rosenbloom/Carole Klavuhn
Filer Authorized By:	Brian S. Rosenbloom
Attorney Docket Number:	1994-363US2
Receipt Date:	06-APR-2015
Filing Date:	27-JAN-2015
Time Stamp:	14:58:32
Application Type:	Utility under 35 USC 111(a)

Payment information:

Submitted with Payment	yes
Payment Type	Deposit Account
Payment was successfully received in RAM	\$3180
RAM confirmation Number	1238
Deposit Account	022135
Authorized User	
The Director of the USPTO is hereby authorized to charge indicated fees and credit any overpayment as follows: Charge any Additional Fees required under 37 C.F.R. Section 1.16 (National application filing, search, and examination fees)	

Charge any Additional Fees required under 37 C.F.R. Section 1.21 (Miscellaneous fees and charges)					
File Listing:					
Document Number	Document Description	File Name	File Size(Bytes)/ Message Digest	Multi Part / zip	Pages (if appl.)
1	Applicant Response to Pre-Exam Formalities Notice	1994-363US2-ResponseToNOMP.pdf	111795 508001f8eac0c131cc7eeabdbd60c0bf17d7731d7	no	1
Warnings:					
Information:					
2	Oath or Declaration filed	1994-363US2-Decs.pdf	365674 7ff0cd2a64f7f9fa-e41cde81ef4c3ade9af1d04c5	no	2
Warnings:					
Information:					
3	Power of Attorney	1994-363US2-POA.pdf	410253 f117f0adbb851c0a74dc78cc0ebd4e1ae5fd	no	2
Warnings:					
Information:					
4		1994-363US2-IDS.pdf	1358905 f1f088bdcc07d8f8eaa38b1f9303d896e71dccc7d	yes	13
	Multipart Description/PDF files in .zip description				
	Document Description	Start	End		
	Transmittal Letter	1	1		
	Information Disclosure Statement (IDS) Form (SB08)	2	13		
Warnings:					
Information:					
5	Fee Worksheet (SB06)	fee-info.pdf	38922 8fc68b1111f0e8ec048f1185607f082b10c2868	no	2
Warnings:					
Information:					
Total Files Size (in bytes):			2285549		

This Acknowledgement Receipt evidences receipt on the noted date by the USPTO of the indicated documents, characterized by the applicant, and including page counts, where applicable. It serves as evidence of receipt similar to a Post Card, as described in MPEP 503.

New Applications Under 35 U.S.C. 111

If a new application is being filed and the application includes the necessary components for a filing date (see 37 CFR 1.53(b)-(d) and MPEP 506), a Filing Receipt (37 CFR 1.54) will be issued in due course and the date shown on this Acknowledgement Receipt will establish the filing date of the application.

National Stage of an International Application under 35 U.S.C. 371

If a timely submission to enter the national stage of an international application is compliant with the conditions of 35 U.S.C. 371 and other applicable requirements a Form PCT/DO/EO/903 indicating acceptance of the application as a national stage submission under 35 U.S.C. 371 will be issued in addition to the Filing Receipt, in due course.

New International Application Filed with the USPTO as a Receiving Office

If a new international application is being filed and the international application includes the necessary components for an international filing date (see PCT Article 11 and MPEP 1810), a Notification of the International Application Number and of the International Filing Date (Form PCT/RO/105) will be issued in due course, subject to prescriptions concerning national security, and the date shown on this Acknowledgement Receipt will establish the international filing date of the application.

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Appl. No. : 14/606,794
 First Inventor : Brian James PETERSEN et al.
 Filed : January 27, 2015
 TC/A.U. : 3652
 Examiner :

Docket No. : 1994-363US2
 Customer No. : 06449
 Confirmation No. : 1047

Mail Stop: Missing Parts
 Commissioner for Patents
 P.O. Box 1450
 Alexandria, Virginia 22313-1450


RESPONSE TO NOTICE TO FILE MISSING PARTS

In response to the Notice to File Missing Parts mailed February 6, 2015, the items checked below are attached in the order listed:

X	Fee transmittal itemizing payment of the fees enumerated thereon. If any additional payment is required, please charge such to Deposit Account No. 02-2135.
X	Information Disclosure Statement
X	A declaration executed by the inventor(s)
X	A power of attorney and Transmittal
	Other

Remarks:

X Customer Number or Bar Code Label 6449					
Name		Brian S. Rosenbloom, Reg. No. 41,276			
Signature				Date	2/15/16
Address		Rothwell, Figg, Ernst & Manbeck, p.c. Suite 800, 607 14th Street, N.W.			
City	Washington	State	D.C.	Zip Code	20005
Country	U.S.A.	Telephone	202-783-6040	Fax	202-783-6031

DECLARATION (37 CFR 1.63) FOR UTILITY OR DESIGN APPLICATION USING AN APPLICATION DATA SHEET (37 CFR 1.76)	
Caution: A person may not execute an oath or declaration for an application unless that person has reviewed and understands the contents of the application, including the claims, and is aware of the duty to disclose to the US Patent and Trademark Office all information known to the person to be material to patentability as defined in 37 CFR 1.56.	
Title of Invention	Seed Carrier With Pivoting Conveyor
As the below named inventor, I hereby declare that: This declaration is directed to: ☐ The attached application, or ☒ United States application or PCT international application number <u>14/606,794</u> filed on <u>January 27, 2015</u> . The above-identified application was made or authorized to be made by me. I believe that I am the original inventor or an original joint inventor of a claimed invention in the application. I hereby acknowledge that any willful false statement made in this declaration is punishable under 18 U.S.C. 1001 by fine or imprisonment of not more than five (5) years, or both.	
LEGAL NAME OF INVENTOR	
Typed Name of Inventor: Brian James PETERSEN	
Signature of Inventor:	 Date (optional): 2-23-2015

DECLARATION (37 CFR 1.63) FOR UTILITY OR DESIGN APPLICATION USING AN APPLICATION DATA SHEET (37 CFR 1.76)	
Caution: A person may not execute an oath or declaration for an application unless that person has reviewed and understands the contents of the application, including the claims, and is aware of the duty to disclose to the US Patent and Trademark Office all information known to the person to be material to patentability as defined in 37 CFR 1.56.	
Title of Invention	Seed Carrier With Pivoting Conveyor
As the below named inventor, I hereby declare that: This declaration is directed to: ☐ The attached application, or ☒ United States application or PCT international application number <u>14/606,794</u> filed on <u>January 27, 2015</u> . The above-identified application was made or authorized to be made by me. I believe that I am the original inventor or an original joint inventor of a claimed invention in the application. I hereby acknowledge that any willful false statement made in this declaration is punishable under 18 U.S.C. 1001 by fine or imprisonment of not more than five (5) years, or both.	
LEGAL NAME OF INVENTOR	
Typed Name of Inventor: David Richard SMITH	
Signature of Inventor: 	Date (optional): 2-23-15

POWER OF ATTORNEY BY APPLICANT		
<i>(Note: this form MUST be accompanied by Transmittal Form to identify application to which this Power of Attorney is directed, or the Power of Attorney will not be recognized in the Application)</i>		
I hereby revoke all previous powers of attorney given in the application identified in the attached transmittal letter.		
I hereby appoint Practitioners associated with the following Customer Number as my/our attorney(s) or agent(s), to transact all business in the United States Patent and Trademark Office connected therewith for the application referenced in the attached transmittal letter (form PTO/AIA/82A or equivalent): Customer Number 06449.		
Please recognize or change the correspondence address for the above-identified application to the address associated with Customer Number 06449.		
ACKNOWLEDGEMENT AND CONSENT TO OBTAIN INSTRUCTIONS FROM ANOTHER PARTY		
The undersigned hereby acknowledges that the practitioners appointed herein may obtain instructions as to any action to be taken in the U.S. Patent and Trademark Office on any application to which this power of attorney may be directed, or on any patent which may issue on any such application, from third-party agents or attorneys of Applicant, who have been authorized by Applicant to convey such instructions, and Applicant expressly consents to this arrangement. In the event of a change in the persons from whom instructions are to be taken, the practitioners appointed herein shall be so notified by the Applicant.		
I am the Applicant (check one below):		
☐	Inventor or Joint Inventor	
☐	Legal Representative of a Deceased or Legally Incapacitated Inventor	
☒	Assignee or Person to Whom the Inventor is Under an Obligation to Assign	
☐	Person Who Otherwise Shows Sufficient Proprietary Interest (e.g., a petition under 37 CFR 1.46(b)(2) was granted in the application or is concurrently being filed with this document)	
Signature of Applicant for Patent		
Signature	<i>R. Steven Unverferth</i>	Date <i>3-2-15</i>
Typed/Printed Name	<i>R. Steven Unverferth</i>	
Title and Company	<i>Pres. Unverferth Mfg Co Inc</i>	

TRANSMITTAL FOR POWER OF ATTORNEY TO ONE OR MORE REGISTERED PRACTITIONERS			
<i>(Note: This form is to be submitted with the Power of Attorney by Applicant form to identify the application to which the Power of Attorney is directed, in accordance with 37 CFR 1.5. If the Power of Attorney by Applicant form is not accompanied by this transmittal form or an equivalent, the Power of Attorney will not be recognized in the application.)</i>			
Application Number	14/606,794		
Filing Date	January 27, 2015		
First Named Inventor	Brian James Petersen et al.		
Title	SEED CARRIER WITH PIVOTING CONVEYOR		
Art Unit	3652		
Examiner Name			
Attorney Docket Number	1994-363US2	Client Ref. Number	
Signature of Patent Practitioner			
Signature			Date 3-24-15
Name	Jason M. Shapiro		Telephone 202-783-6040
Registration Number	35,354		

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Application No. : 14/606,794
First Inventor : Brian James PETERSEN et al.
Filed : January 27, 2015
TC/A.U. : 3652
Examiner :
Docket No. : 1994-363US2
Customer No. : 06449
Confirmation No. : 1047

INFORMATION DISCLOSURE STATEMENT

Commissioner for Patents
P.O. Box 1450
Alexandria, Virginia 22313-1450

Dear Sir:

Under the provisions of 37 C.F.R. §§ 1.56, 1.97 and 1.98, Applicants submit herewith Form PTO-SB08 and PTO-892 listing publications that the Office may wish to consider in examination of the subject application.

Pursuant to 1.98(d), copies of the references are not included because they were previously submitted to the Office in prior application Serial No. 13/541,553, and to which priority is or has been claimed under 35 USC § 120.

Respectfully submitted,

By



Brian S. Roscubloom
Attorney for Applicants
Registration No. 41,276
ROTHWELL, FIGG, ERNST & MANBECK, p.c.
Suite 800, 607 14TH Street, N.W.
Washington, D.C. 20005
Telephone: (202)783-6040

INFORMATION DISCLOSURE STATEMENT BY APPLICANT (Not for submission under 37 CFR 1.99)	Application Number	14606794
	Filing Date	2015-01-27
	First Named Inventor	Brian James PETERSEN et al.
	Art Unit	3852
	Examiner Name	
	Attorney Docket Number	1994-363US2

CERTIFICATION STATEMENT	
Please see 37 CFR 1.97 and 1.98 to make the appropriate selection(s):	
☐ That each item of information contained in the information disclosure statement was first cited in any communication from a foreign patent office in a counterpart foreign application not more than three months prior to the filing of the information disclosure statement. See 37 CFR 1.97(e)(1).	
OR	
☐ That no item of information contained in the information disclosure statement was cited in a communication from a foreign patent office in a counterpart foreign application, and, to the knowledge of the person signing the certification after making reasonable inquiry, no item of information contained in the information disclosure statement was known to any individual designated in 37 CFR 1.56(c) more than three months prior to the filing of the information disclosure statement. See 37 CFR 1.97(e)(2).	
☐ See attached certification statement.	
☐ The fee set forth in 37 CFR 1.17 (p) has been submitted herewith.	
☒ A certification statement is not submitted herewith.	
SIGNATURE	
A signature of the applicant or representative is required in accordance with CFR 1.33, 10.18. Please see CFR 1.4(d) for the form of the signature.	
Signature	
Date (YYYY-MM-DD)	2015-01-06
Name/Print	Brian S. Rosenbloom
Registration Number	41,276
This collection of information is required by 37 CFR 1.97 and 1.98. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 1 hour to complete, including gathering, preparing and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.	

Privacy Act Statement

The Privacy Act of 1974 (P.L. 93-579) requires that you be given certain information in connection with your submission of the attached form related to a patent application or patent. Accordingly, pursuant to the requirements of the Act, please be advised that: (1) the general authority for the collection of this information is 35 U.S.C. 2(b)(2); (2) furnishing of the information solicited is voluntary; and (3) the principal purpose for which the information is used by the U.S. Patent and Trademark Office is to process and/or examine your submission related to a patent application or patent. If you do not furnish the requested information, the U.S. Patent and Trademark Office may not be able to process and/or examine your submission, which may result in termination of proceedings or abandonment of the application or expiration of the patent.

The information provided by you in this form will be subject to the following routine uses:

1. The information on this form will be treated confidentially to the extent allowed under the Freedom of Information Act (5 U.S.C. 552) and the Privacy Act (5 U.S.C. 552a). Records from this system of records may be disclosed to the Department of Justice to determine whether the Freedom of Information Act requires disclosure of these records.
2. A record from this system of records may be disclosed, as a routine use, in the course of presenting evidence to a court, magistrate, or administrative tribunal, including disclosures to opposing counsel in the course of settlement negotiations.
3. A record in this system of records may be disclosed, as a routine use, to a Member of Congress submitting a request involving an individual, to whom the record pertains, when the individual has requested assistance from the Member with respect to the subject matter of the record.
4. A record in this system of records may be disclosed, as a routine use, to a contractor of the Agency having need for the information in order to perform a contract. Recipients of information shall be required to comply with the requirements of the Privacy Act of 1974, as amended, pursuant to 5 U.S.C. 552a(m).
5. A record related to an International Application filed under the Patent Cooperation Treaty in this system of records may be disclosed, as a routine use, to the International Bureau of the World Intellectual Property Organization, pursuant to the Patent Cooperation Treaty.
6. A record in this system of records may be disclosed, as a routine use, to another federal agency for purposes of National Security review (35 U.S.C. 181) and for review pursuant to the Atomic Energy Act (42 U.S.C. 218(c)).
7. A record from this system of records may be disclosed, as a routine use, to the Administrator, General Services, or his/her designee, during an inspection of records conducted by GSA as part of that agency's responsibility to recommend improvements in records management practices and programs, under authority of 44 U.S.C. 2904 and 2906. Such disclosure shall be made in accordance with the GSA regulations governing inspection of records for this purpose, and any other relevant (i.e., GSA or Commerce) directive. Such disclosure shall not be used to make determinations about individuals.
8. A record from this system of records may be disclosed, as a routine use, to the public after either publication of the application pursuant to 35 U.S.C. 122(b) or issuance of a patent pursuant to 35 U.S.C. 151. Further, a record may be disclosed, subject to the limitations of 37 CFR 1.14, as a routine use, to the public if the record was filed in an application which became abandoned or in which the proceedings were terminated and which application is referenced by either a published application, an application open to public inspections or an issued patent.
9. A record from this system of records may be disclosed, as a routine use, to a Federal, State, or local law enforcement agency, if the USPTO becomes aware of a violation or potential violation of law or regulation.

Doc code: IDS

Doc description: Information Disclosure Statement (IDS) Filed

PTO/SB/08a (01-10)

Approved for use through 07/31/2012. OMB 0651-0031

U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

INFORMATION DISCLOSURE STATEMENT BY APPLICANT (Not for submission under 37 CFR 1.99)	Application Number	14606794
	Filing Date	2015-01-27
	First Named Inventor	Brian James PETERSEN et al.
	Art Unit	3652
	Examiner Name	
	Attorney Docket Number	1994-363US2

U.S. PATENTS						
Examiner Initial*	Cite No	Patent Number	Kind Code ¹	Issue Date	Name of Patentee or Applicant of cited Document	Pages, Columns, Lines where Relevant Passages or Relevant Figures Appear
	1	3090515		1963-05-21	Crowther	
	2	3493136		1970-02-03	Spellman, Jr.	
	3	3498483		1970-03-03	Meharry	
	4	4037745		1977-07-26	Hengen et al.	
	5	4411581		1983-10-25	Niewold	
	6	4742938		1988-05-10	Niewold	
	7	5520495		1996-05-28	Sukup	
	8	5718556		1998-02-17	Forsyth	

EFS Web 2.1.17

INFORMATION DISCLOSURE STATEMENT BY APPLICANT (Not for submission under 37 CFR 1.99)	Application Number		14606794
	Filing Date		2015-01-27
	First Named Inventor	Brian James PETERSEN et al.	
	Art Unit	3652	
	Examiner Name		
	Attorney Docket Number	1994-363US2	

	9	3968771		1976-07-13	Walgenbach et al.	
	10	4503803		1985-03-12	Barnes	
	11	5800116		1998-09-01	Smith et al.	
	12	6209880		2001-04-03	Turnwald et al.	
	13	6325588		2001-12-04	Nolin	
	14	6604620		2003-08-12	Dennis	
	15	6767174		2004-07-27	Cresswell	
	16	7488149		2009-02-10	Waldner	
	17	7500817		2009-03-10	Furrer et al.	
	18	5529455		1996-06-25	Kaster et al.	
	19	7393275		2008-07-01	Voss et al.	

EFS Web 2.1.17

INFORMATION DISCLOSURE STATEMENT BY APPLICANT (Not for submission under 37 CFR 1.99)	Application Number		14606794
	Filing Date		2015-01-27
	First Named Inventor	Brian James PETERSEN et al.	
	Art Unit	3652	
	Examiner Name		
	Attorney Docket Number	1994-363US2	

	20	5888044		1999-03-30	Baskerville	
	21	7267519		2007-09-11	Cresswell, et al.	
	22	7500814		2009-03-10	Meyer	
	23	4218169		1980-08-19	Arends	
	24	4274790		1981-06-23	Barker	
	25	4312621		1982-01-26	Quanbeck et al.	
	26	4419037		1983-12-06	Neiwold	
	27	4491216		1985-01-01	Sawby	
	28	4613275		1986-09-23	Karlowsky	
	29	5013208		1991-05-07	Grieshop	
	30	5468113		1995-11-21	Davis	

EFS Web 2.1.17

INFORMATION DISCLOSURE STATEMENT BY APPLICANT (Not for submission under 37 CFR 1.99)	Application Number		14606794
	Filing Date		2015-01-27
	First Named Inventor	Brian James PETERSEN et al.	
	Art Unit	3652	
	Examiner Name		
	Attorney Docket Number	1994-363US2	

	31	5516253		1996-05-14	Linscheid et al.	
	32	5538388		1996-07-23	Bergkamp et al.	
	33	5582221		1996-12-10	Smith et al.	
	34	5615990		1997-04-01	Grieshop	
	35	5785481		1998-07-28	Ockels	
	36	5980189		1999-11-09	Rubner	
	37	6120233		2000-09-19	Adam	
	38	6908380		2005-06-21	Silver	
	39	7223059		2007-05-29	Smith et al.	
	40	7553228		2009-06-30	Dillon	
	41	6113339		2000-09-05	Adams	

EFS Web 2.1.17

INFORMATION DISCLOSURE STATEMENT BY APPLICANT (Not for submission under 37 CFR 1.99)	Application Number	14606794
	Filing Date	2015-01-27
	First Named Inventor	Brian James PETERSEN et al.
	Art Unit	3652
	Examiner Name	
	Attorney Docket Number	1994-363US2

	42	5484249		1996-01-16	Clatt			
If you wish to add additional U.S. Patent citation information please click the Add button.								
U.S.PATENT APPLICATION PUBLICATIONS								
Examiner Initial*	Cite No	Publication Number	Kind Code ¹	Publication Date	Name of Patentee or Applicant of cited Document	Pages, Columns, Lines where Relevant Passages or Relevant Figures Appear		
	1	20030057055		2003-03-27	Haukaas et al.			
	2	20060180062		2006-04-17	Furrer et al.			
If you wish to add additional U.S. Published Application citation information please click the Add button.								
FOREIGN PATENT DOCUMENTS								
Examiner Initial*	Cite No	Foreign Document Number ³	Country Code ²	Kind Code ⁴	Publication Date	Name of Patentee or Applicant of cited Document	Pages, Columns, Lines where Relevant Passages or Relevant Figures Appear	T ⁵
	1							☐
If you wish to add additional Foreign Patent Document citation information please click the Add button								
NON-PATENT LITERATURE DOCUMENTS								
Examiner Initials*	Cite No	Include name of the author (in CAPITAL LETTERS), title of the article (when appropriate), title of the item (book, magazine, journal, serial, symposium, catalog, etc), date, pages(s), volume-issue number(s), publisher, city and/or country where published.						T ⁵
	1	Model 2300 Air System and the Model 4800 Air Drill, both made and sold by Concord, as illustrated in the Concord brochure, 12 pages.						☐
	2	Convey-Air, BTS 290 Seed Tender Product Specification, 2 pages.						☐

EFS Web 2.1.17

INFORMATION DISCLOSURE STATEMENT BY APPLICANT (Not for submission under 37 CFR 1.99)	Application Number		14606794
	Filing Date		2015-01-27
	First Named Inventor	Brian James PETERSEN et al.	
	Art Unit	3652	
	Examiner Name		
	Attorney Docket Number	1994-363US2	

3	Convey-All Ind. Inc., Engineering Drawings of BT-1500, 4 pages.	☐
4	Par-Kan Company, Engineering Drawings, 2 pages.	☐
5	Great Plains Manufacturing, Inc., Parts Manual - Model ADC2220 Air Drill Cart, May 1, 1997, 61 pages.	☐
6	Great Plains Manufacturing, Inc., Parts Manual - Model ADC2220 Air Drill Cart, March 1, 2000, 69 pages.	☐
7	Reexamination File History for Control Number 95000691, 374 pages.	☐
8	Order Denying Request for Inter Partes Reexamination for Control Number 95000691, November 7, 2012, 15 pages.	☐
9	Par-Kan Company, Final Invalidity Contentions submitted in Unverferth Mfg. Co., Inc. v. Par-Kan Co., Civil Action No. 13-cv-00097 (N.D. Ind.), October 25, 2013, 130 pages.	☐
10	Par-Kan Company, Preliminary Invalidity Contentions submitted in Unverferth Mfg. Co., Inc. v. Par-Kan Co., Civil Action No. 13-cv-00097 (N.D. Ind.), June 17, 2013, 169 pages.	☐
11	Declaration of Shawn Gerdeman with Exhibits A-E dated September 18, 2014, 24 pages.	☐
If you wish to add additional non-patent literature document citation information please click the Add button		
EXAMINER SIGNATURE		
Examiner Signature		Date Considered
*EXAMINER: Initial if reference considered, whether or not citation is in conformance with MPEP 609. Draw line through a citation if not in conformance and not considered. Include copy of this form with next communication to applicant.		

INFORMATION DISCLOSURE STATEMENT BY APPLICANT (Not for submission under 37 CFR 1.99)	Application Number	14606794
	Filing Date	2015-01-27
	First Named Inventor	Brian James PETERSEN et al.
	Art Unit	3652
	Examiner Name	
	Attorney Docket Number	1994-363US2

¹ See Kind Codes of USPTO Patent Documents at www.USPTO.GOV or MPEP 901.04. ² Enter office that issued the document, by the two-letter code (WIPO Standard ST.3). ³ For Japanese patent documents, the indication of the year of the reign of the Emperor must precede the serial number of the patent document. ⁴ Kind of document by the appropriate symbols as indicated on the document under WIPO Standard ST.16 if possible. ⁵ Applicant is to place a check mark here if English language translation is attached.

Other Prior Art

According to the information contained in form PTO-1449 or PTO-892, there are one or more other prior art/non-patent literature documents missing from the original file history record obtained from the United States Patent and Trademark Office. Upon your request we will attempt to obtain these documents from alternative resources. Please note that additional charges will apply for this service.

This page is not part of the official USPTO record. It has been determined that content identified on this document is missing from the original file history record.

Notice of References Cited	Application/Control No. 19/541,353	Applicant(s)/Patent Under Reexamination PETERSEN ET AL.	
	Examiner GLENN MYERS	Art Unit 3652	Page 1 of 1

FOR S.N. 14/606,794

U.S. PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date MM-YYYY	Name	Classification
*	A	US-6,120,233	09-2000	Adam, Gerald E.	414/502
*	B	US-5,718,556	02-1998	Forsyth, Daniel L.	414/503
*	C	US-5,520,495	05-1996	Sukup, Eugene G.	414/523
*	D	US-3,498,483	03-1970	MEHARRY JAMES L	414/523
*	E	US-1,905,434	04-1933	FERNAND BOYER	414/328
*	F	US-5,484,249	01-1996	Klatt, Dennis	414/523
	G	US-			
	H	US-			
	I	US-			
	J	US-			
	K	US-			
	L	US-			
	M	US-			

FOREIGN PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date MM-YYYY	Country	Name	Classification
	N					
	O					
	P					
	Q					
	R					
	S					
	T					

NON-PATENT DOCUMENTS

*		Include as applicable: Author, Title Date, Publisher, Edition or Volume, Pertinent Pages)
	U	
	V	
	W	
	X	

*A copy of this reference is not being furnished with this Office action. (See MPEP § 707.05(a).)
Dates in MM-YYYY format are publication dates. Classifications may be US or foreign.

U.S. Patent and Trademark Office
PTO-892 (Rev. 01-2001)

Notice of References Cited

Part of Paper No. 20140625

FOR SN 141606, 794

Notice of References Cited	Application/Control No. ~~13/641,558~~	Applicant(s)/Patent Under Reexamination PETERSEN ET AL.	
	Examiner JOSHUA RUDAWITZ	Art Unit 3652	Page 1 of 2

U.S. PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date MM-YYYY	Name	Classification
*	A	US-427,736 A	05-1890	Bufkin	198/317
*	B	US-3,968,771 A	07-1976	Walgenbach et al.	118/303
*	C	US-3,994,512 A	11-1976	Parker et al.	280/687
*	D	US-3,997,215 A	12-1976	Parker et al.	298/24
*	E	US-4,503,803 A	03-1985	Barnes, Ronald A.	118/303
*	F	US-5,615,990 A	04-1997	Grieshop, Maurice	414/526
*	G	US-5,800,116 A	09-1998	Smith et al.	414/523
*	H	US-5,888,044 A	03-1999	Baskerville, Gregory Eugene	414/523
*	I	US-6,209,880 B1	04-2001	Turnwald et al.	277/402
*	J	US-6,325,588 B1	12-2001	Nolin, Karl W.	414/526
*	K	US-2003/0057055 A1	03-2003	Haukaas et al.	198/313
*	L	US-6,604,620 B2	08-2003	Dennis, Andrew	198/312
*	M	US-6,767,174 B2	07-2004	Cresswell, Mark	414/523

FOREIGN PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date MM-YYYY	Country	Name	Classification
	N					
	O					
	P					
	Q					
	R					
	S					
	T					

NON-PATENT DOCUMENTS

*		Include as applicable: Author, Title Date, Publisher, Edition or Volume, Pertinent Pages)
	U	
	V	
	W	
	X	

*A copy of this reference is not being furnished with this Office action. (See MPEP § 707.05(a).)
Dates in MM-YYYY format are publication dates. Classifications may be US or foreign.

U.S. Patent and Trademark Office
PTO-892 (Rev. 01-2001)

Notice of References Cited

Part of Paper No. 20130923

Notice of References Cited	Application/Control No. ~~13/541,553~~	Applicant(s)/Patent Under Reexamination PETERSEN ET AL.	
	Examiner JOSHUA RUDAWITZ	Art Unit 3652	Page 2 of 2

FOR S.N. 14/606,794

U.S. PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date MM-YYYY	Name	Classification
*	A	US-7,428,956 B2	09-2008	Scherman, Patrick John	198/312
*	B	US-7,488,149 B2	02-2009	Waldner, Samuel	414/532
*	C	US-7,500,817 B2	03-2009	Furrer et al.	414/522
*	D	US-2009/0110524 A1	04-2009	Hoffmann, Mark A.	414/507
*	E	US-8,221,047 B2	07-2012	Petersen et al.	414/523
	F	US-			
	G	US-			
	H	US-			
	I	US-			
	J	US-			
	K	US-			
	L	US-			
	M	US-			

FOREIGN PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date MM-YYYY	Country	Name	Classification
	N					
	O					
	P					
	Q					
	R					
	S					
	T					

NON-PATENT DOCUMENTS

*		Include as applicable: Author, Title Date, Publisher, Edition or Volume, Pertinent Pages)
	U	
	V	
	W	
	X	

*A copy of this reference is not being furnished with this Office action. (See MPEP § 707.05(a).)
Dates in MM-YYYY format are publication dates. Classifications may be US or foreign.

U.S. Patent and Trademark Office
PTO-892 (Rev. 01-2001)

Notice of References Cited

Part of Paper No. 20130923

Electronic Patent Application Fee Transmittal				
Application Number:		14606794		
Filing Date:		27-Jan-2015		
Title of Invention:		SEED CARRIER WITH PIVOTING CONVEYOR		
First Named Inventor/Applicant Name:		Brian James PETERSEN		
Filer:		Brian S. Rosenbloom/Carole Klavuhn		
Attorney Docket Number:		1994-363US2		
Filed as Large Entity				
Filing Fees for Utility under 35 USC 111(a)				
Description	Fee Code	Quantity	Amount	Sub-Total in USD(\$)
Basic Filing:				
Utility application filing	1011	1	280	280
Utility Search Fee	1111	1	600	600
Utility Examination Fee	1311	1	720	720
Pages:				
Claims:				
Claims in Excess of 20	1202	18	80	1440
Miscellaneous-Filing:				
Late Filing Fee for Oath or Declaration	1051	1	140	140

Description	Fee Code	Quantity	Amount	Sub-Total in USD(\$)
Petition:				
Patent Appeals and Interference:				
Post-Allowance and Post-Issuance:				
Extension of Time:				
Miscellaneous:				
Total in USD (\$)				3180



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NUMBER	FILING OR 371(C) DATE	FIRST NAMED APPLICANT	ATTY. DOCKET NO./TITLE
14/606,794	01/27/2015	Brian James PETERSEN	I994-363US2

CONFIRMATION NO. 1047

POA ACCEPTANCE LETTER



6449
ROTHWELL, FIGG, ERNST & MANBECK, P.C.
607 14th Street, N.W.
SUITE 800
WASHINGTON, DC 20005

Date Mailed: 04/10/2015

NOTICE OF ACCEPTANCE OF POWER OF ATTORNEY

This is in response to the Power of Attorney filed 04/06/2015.

The Power of Attorney in this application is accepted. Correspondence in this application will be mailed to the above address as provided by 37 CFR 1.33.

/dgela/

Office of Data Management, Application Assistance Unit (571) 272-4000, or (571) 272-4200, or 1-888-786-0101



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1501
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NUMBER	FILING or 371(c) DATE	USPTO UNIT	FIL.FEE REC'D	ATTY. DOCKET NO.	TOT. CLAIMS	IND. CLAIMS
14/606,794	01/27/2015	3652	3180	1994-363US2	38	2

CONFIRMATION NO. 1047

UPDATED FILING RECEIPT



OC000000074521475

6449
ROTHWELL, FIGG, ERNST & MANBECK, P.C.
607 14th Street, N.W.
SUITE 800
WASHINGTON, DC 20005

Date Mailed: 04/10/2015

Receipt is acknowledged of this non-provisional patent application. The application will be taken up for examination in due course. Applicant will be notified as to the results of the examination. Any correspondence concerning the application must include the following identification information: the U.S. APPLICATION NUMBER, FILING DATE, NAME OF APPLICANT, and TITLE OF INVENTION. Fees transmitted by check or draft are subject to collection. Please verify the accuracy of the data presented on this receipt. **If an error is noted on this Filing Receipt, please submit a written request for a Filing Receipt Correction. Please provide a copy of this Filing Receipt with the changes noted thereon. If you received a "Notice to File Missing Parts" for this application, please submit any corrections to this Filing Receipt with your reply to the Notice. When the USPTO processes the reply to the Notice, the USPTO will generate another Filing Receipt incorporating the requested corrections**

Inventor(s)

Brian James PETERSEN, Ottawa, OH;
David Richard SMITH, Fort Jennings, OH

Applicant(s)

UNVERFERTH MANUFACTURING COMPANY, INC., Kalida, OH

Power of Attorney: The patent practitioners associated with Customer Number 06449

Domestic Priority data as claimed by applicant

This application is a CON of 13/541,553 07/03/2012 PAT 8967940
which is a CON of 12/031,867 02/15/2008 PAT 8221047
which claims benefit of 60/901,321 02/15/2007

Foreign Applications for which priority is claimed (You may be eligible to benefit from the **Patent Prosecution Highway** program at the USPTO. Please see <http://www.uspto.gov> for more information.) - None.

Foreign application information must be provided in an Application Data Sheet in order to constitute a claim to foreign priority. See 37 CFR 1.55 and 1.76.

If Required, Foreign Filing License Granted: 02/05/2015

The country code and number of your priority application, to be used for filing abroad under the Paris Convention, is **US 14/606,794**

Projected Publication Date: 07/16/2015

Non-Publication Request: No

Early Publication Request: No

page 1 of 3

Title

SEED CARRIER WITH PIVOTING CONVEYOR

Preliminary Class

414

Statement under 37 CFR 1.55 or 1.78 for AIA (First Inventor to File) Transition Applications: No

PROTECTING YOUR INVENTION OUTSIDE THE UNITED STATES

Since the rights granted by a U.S. patent extend only throughout the territory of the United States and have no effect in a foreign country, an inventor who wishes patent protection in another country must apply for a patent in a specific country or in regional patent offices. Applicants may wish to consider the filing of an international application under the Patent Cooperation Treaty (PCT). An international (PCT) application generally has the same effect as a regular national patent application in each PCT-member country. The PCT process **simplifies** the filing of patent applications on the same invention in member countries, but **does not result** in a grant of "an international patent" and does not eliminate the need of applicants to file additional documents and fees in countries where patent protection is desired.

Almost every country has its own patent law, and a person desiring a patent in a particular country must make an application for patent in that country in accordance with its particular laws. Since the laws of many countries differ in various respects from the patent law of the United States, applicants are advised to seek guidance from specific foreign countries to ensure that patent rights are not lost prematurely.

Applicants also are advised that in the case of inventions made in the United States, the Director of the USPTO must issue a license before applicants can apply for a patent in a foreign country. The filing of a U.S. patent application serves as a request for a foreign filing license. The application's filing receipt contains further information and guidance as to the status of applicant's license for foreign filing.

Applicants may wish to consult the USPTO booklet, "General Information Concerning Patents" (specifically, the section entitled "Treaties and Foreign Patents") for more information on timeframes and deadlines for filing foreign patent applications. The guide is available either by contacting the USPTO Contact Center at 800-786-9199, or it can be viewed on the USPTO website at <http://www.uspto.gov/web/offices/pac/doc/general/index.html>.

For information on preventing theft of your intellectual property (patents, trademarks and copyrights), you may wish to consult the U.S. Government website, <http://www.stopfakes.gov>. Part of a Department of Commerce initiative, this website includes self-help "toolkits" giving innovators guidance on how to protect intellectual property in specific countries such as China, Korea and Mexico. For questions regarding patent enforcement issues, applicants may call the U.S. Government hotline at 1-866-999-HALT (1-866-999-4258).

LICENSE FOR FOREIGN FILING UNDER
Title 35, United States Code, Section 184
Title 37, Code of Federal Regulations, 5.11 & 5.15

GRANTED

The applicant has been granted a license under 35 U.S.C. 184, if the phrase "IF REQUIRED, FOREIGN FILING LICENSE GRANTED" followed by a date appears on this form. Such licenses are issued in all applications where the conditions for issuance of a license have been met, regardless of whether or not a license may be required as set forth in 37 CFR 5.15. The scope and limitations of this license are set forth in 37 CFR 5.15(a) unless an earlier license has been issued under 37 CFR 5.15(b). The license is subject to revocation upon written notification. The date indicated is the effective date of the license, unless an earlier license of similar scope has been granted under 37 CFR 5.13 or 5.14.

This license is to be retained by the licensee and may be used at any time on or after the effective date thereof unless it is revoked. This license is automatically transferred to any related applications(s) filed under 37 CFR 1.53(d). This license is not retroactive.

The grant of a license does not in any way lessen the responsibility of a licensee for the security of the subject matter as imposed by any Government contract or the provisions of existing laws relating to espionage and the national security or the export of technical data. Licensees should apprise themselves of current regulations especially with respect to certain countries, of other agencies, particularly the Office of Defense Trade Controls, Department of State (with respect to Arms, Munitions and Implements of War (22 CFR 121-128)); the Bureau of Industry and Security, Department of Commerce (15 CFR parts 730-774); the Office of Foreign Assets Control, Department of Treasury (31 CFR Parts 500+) and the Department of Energy.

NOT GRANTED

No license under 35 U.S.C. 184 has been granted at this time, if the phrase "IF REQUIRED, FOREIGN FILING LICENSE GRANTED" DOES NOT appear on this form. Applicant may still petition for a license under 37 CFR 5.12, if a license is desired before the expiration of 6 months from the filing date of the application. If 6 months has lapsed from the filing date of this application and the licensee has not received any indication of a secrecy order under 35 U.S.C. 181, the licensee may foreign file the application pursuant to 37 CFR 5.15(b).

SelectUSA

The United States represents the largest, most dynamic marketplace in the world and is an unparalleled location for business investment, innovation, and commercialization of new technologies. The U.S. offers tremendous resources and advantages for those who invest and manufacture goods here. Through SelectUSA, our nation works to promote and facilitate business investment. SelectUSA provides information assistance to the international investor community; serves as an ombudsman for existing and potential investors; advocates on behalf of U.S. cities, states, and regions competing for global investment; and counsels U.S. economic development organizations on investment attraction best practices. To learn more about why the United States is the best country in the world to develop technology, manufacture products, deliver services, and grow your business, visit <http://www.SelectUSA.gov> or call +1-202-482-6800.

Electronic Acknowledgement Receipt

EFS ID:	22303958
Application Number:	14606794
International Application Number:	
Confirmation Number:	1047
Title of Invention:	SEED CARRIER WITH PIVOTING CONVEYOR
First Named Inventor/Applicant Name:	Brian James PETERSEN
Customer Number:	6449
Filer:	Jason M. Shapiro/Carole Klayuhm
Filer Authorized By:	Jason M. Shapiro
Attorney Docket Number:	1994-363US2
Receipt Date:	11-MAY-2015
Filing Date:	27-JAN-2015
Time Stamp:	13:48:11
Application Type:	Utility under 35 USC 111(a)

Payment information:

Submitted with Payment						no
File Listing:						
Document Number	Document Description	File Name	File Size(Bytes)/ Message Digest	Multi Part /.zip	Pages (if appl.)	
1	Preliminary Amendment	1994-363US2-PreAmd.pdf	-483232	no	8	
			109208FFD5e5dcaBQJcuaKk-BE-3UAFmmevLz+SeiaC GUMH+-			
Warnings:						
Information:						

Total Files Size (in bytes):	483232
This Acknowledgement Receipt evidences receipt on the noted date by the USPTO of the indicated documents, characterized by the applicant, and including page counts, where applicable. It serves as evidence of receipt similar to a Post Card, as described in MPEP 503. <u>New Applications Under 35 U.S.C. 111</u> If a new application is being filed and the application includes the necessary components for a filing date (see 37 CFR 1.53(b)-(d) and MPEP 506), a Filing Receipt (37 CFR 1.54) will be issued in due course and the date shown on this Acknowledgement Receipt will establish the filing date of the application. <u>National Stage of an International Application under 35 U.S.C. 371</u> If a timely submission to enter the national stage of an international application is compliant with the conditions of 35 U.S.C. 371 and other applicable requirements a Form PCT/DO/EO/903 indicating acceptance of the application as a national stage submission under 35 U.S.C. 371 will be issued in addition to the Filing Receipt, in due course. <u>New International Application Filed with the USPTO as a Receiving Office</u> If a new international application is being filed and the international application includes the necessary components for an international filing date (see PCT Article 11 and MPEP 1810), a Notification of the International Application Number and of the International Filing Date (Form PCT/RO/105) will be issued in due course, subject to prescriptions concerning national security, and the date shown on this Acknowledgement Receipt will establish the international filing date of the application.	

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Application No. : 14/606,794
First Named Inventor : Brian James PETERSEN et al.
Filed : January 27, 2015
TC/A.U. : 3652
Examiner :

Docket No. : 1994-363US2
Customer No. : 06449
Confirmation No. : 1047

Commissioner for Patents
P.O. Box 1450
Alexandria, Virginia 22313-1450

PRELIMINARY AMENDMENT

Please amend the above-identified application, prior to examination on the merits, as follows:

Amendments to the claims begin on page 2 of this paper.

Remarks are on page 8 of this paper.

Amendments to the Claims:

Cancel claims 1-38, and insert the following claims:

39. (New) A seed or grain tender comprising:

a main hopper having a main hopper discharge;

a support arm having first and second ends;

said first end of said support arm being located below said main hopper and being rotatable about a first axis of rotation, and said first end of said support arm being rotatable about a second axis of rotation that is perpendicular to said first axis of rotation;

a conveyor having a longitudinal axis and first and second ends, a conveyor hopper at said first end, a conveyor discharge at said second end, and an internal elevator for moving seed or grain from said conveyor hopper to said conveyor discharge; and

said second end of said support arm being coupled with said conveyor between said first and second ends of said conveyor, said conveyor being rotatable about a third axis of rotation at said second end of said support arm that is not parallel to said conveyor longitudinal axis, and said conveyor being rotatable in relation to said second end of said support arm about said third axis of rotation between an unloading position wherein said conveyor hopper is disposed below said main hopper discharge to receive agricultural product from said main hopper and a loading position wherein said conveyor discharge is disposed above said main hopper to dispense agricultural product into said main hopper.

40. (New) The seed or grain tender of claim 39, wherein said first axis of rotation extends through said main hopper discharge.

41. (New) The seed or grain tender of claim 39, wherein said second axis of rotation extends through said first end of said support arm.

42. (New) The seed or grain tender of claim 39, wherein said third axis of rotation extends through said conveyor.

43. (New) The seed or grain tender of claim 39, wherein said third axis of rotation extends through said second end of said support arm.

44. (New) The seed or grain tender of claim 39, wherein said third axis of rotation extends through said conveyor and said second end of said support arm.

45. (New) The seed or grain tender of claim 39, wherein said third axis of rotation is oriented at an angle having a vertical component.

46. (New) The seed or grain tender of claim 39, wherein said second end of said support arm is coupled with said conveyor at or near said approximate center of gravity of said conveyor.

47. (New) The seed or grain tender of claim 39, further comprising a hydraulic piston extending at an acute angle relative to a horizontal plane to connect with a portion of said support arm spaced from said second axis of rotation.

48. (New) The seed or grain tender of claim 39, further comprising a stand coupled with said first end of said conveyor and movable between a stowed position allowing said conveyor hopper to be positioned below said main hopper discharge when said conveyor is in said unloading position and an extended position supporting said conveyor hopper above the ground when said conveyor is in said loading position.

49. (New) A seed or grain tender comprising:

a main hopper having an upper portion with a main hopper intake opening and a lower portion with a main hopper discharge;

a support arm having a first end proximate said lower portion of said main hopper and a second end;

wherein said support arm is pivotable about a first axis of rotation proximate said first end of said support arm to cause said support arm to be movable between an operating position wherein said support arm extends outwardly relative to said main hopper and a storage position wherein said support arm is folded inwardly towards said main hopper in relation to said operating position, said support arm further being pivotable about a second axis of rotation proximate said first end of said support arm to cause an elevation of said second end of said support arm to be

adjustable;

a conveyor having a longitudinal axis and first and second ends, a conveyor hopper at said first end, a conveyor discharge at said second end, and an internal elevator for moving seed or grain from said conveyor hopper to said conveyor discharge; and

said second end of said support arm being coupled with said conveyor between said first and second conveyor ends, said conveyor being rotatable about a third axis of rotation proximate said second end of said support arm that is not parallel to said conveyor longitudinal axis, and said conveyor being rotatable in relation to said second end of said support arm about said third of axis of rotation between an unloading position wherein said conveyor hopper is disposed below said main hopper discharge to receive agricultural product from said main hopper and a loading position wherein said conveyor discharge is disposed above said intake opening of said main hopper to dispense agricultural product into said main hopper.

50. (New) The seed or grain tender of claim 49, wherein said first axis of rotation extends through said main hopper discharge.

51. (New) The seed or grain tender of claim 49, wherein said second axis of rotation extends through said first end of said support arm.

52. (New) The seed or grain tender of claim 49, wherein said third axis of rotation extends through said conveyor.

53. (New) The seed or grain tender of claim 49, wherein said third axis of rotation extends through said second end of said support arm.

54. (New) The seed or grain tender of claim 49, wherein said third axis of rotation extends through said conveyor and said second end of said support arm.

55. (New) The seed or grain tender of claim 49, wherein said third axis of rotation is oriented at an angle having a vertical component.

56. (New) The seed or grain tender of claim 55, wherein said first axis of rotation is vertical.

57. (New) The seed or grain tender of claim 56, wherein said second axis of rotation is horizontal.

58. (New) The seed or grain tender of claim 49, wherein said second end of said support arm is coupled with said conveyor at an approximate center of gravity of said conveyor.

59. (New) The seed or grain tender of claim 49, further comprising a hydraulic piston extending at an acute angle relative to a horizontal plane to connect with a portion of said support arm spaced from said second axis of rotation.

60. (New) The seed or grain tender of claim 49, further comprising a stand coupled with said first end of said conveyor and movable between a stowed position allowing said conveyor hopper to be positioned below said main hopper discharge when said conveyor is in said unloading position and an extended position supporting said conveyor hopper above the ground when said conveyor is in said loading position.

REMARKS

Claims 1-38 are cancelled. Claims 39-60 are added. No new matter has been added. Early and favorable examination is respectfully requested.

Respectfully submitted,

By /Jason M. Shapiro/
Jason M. Shapiro
Attorney for Applicants
Registration No. 35,354
ROTHWELL, FIGG, ERNST & MANBECK, p.c.
Suite 800, 607 14th Street, N.W.
Washington, D.C. 20005
Telephone: (202)783-6040

2471809



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NUMBER	FILING OR 371(C) DATE	FIRST NAMED APPLICANT	ATTY. DOCKET NO./TITLE
14/606,794	01/27/2015	Brian James PETERSEN	I994-363US2

CONFIRMATION NO. 1047

PUBLICATION NOTICE



0000000076319947

6449

ROTHWELL, FIGG, ERNST & MANBECK, P.C.
607 14th Street, N.W.
SUITE 800
WASHINGTON, DC 20005

Title:SEED CARRIER WITH PIVOTING CONVEYOR

Publication No.:US-2015-0197395-A1

Publication Date:07/16/2015

NOTICE OF PUBLICATION OF APPLICATION

The above-identified application will be electronically published as a patent application publication pursuant to 37 CFR 1.211, et seq. The patent application publication number and publication date are set forth above.

The publication may be accessed through the USPTO's publically available Searchable Databases via the Internet at www.uspto.gov. The direct link to access the publication is currently <http://www.uspto.gov/patft/>.

The publication process established by the Office does not provide for mailing a copy of the publication to applicant. A copy of the publication may be obtained from the Office upon payment of the appropriate fee set forth in 37 CFR 1.19(a)(1). Orders for copies of patent application publications are handled by the USPTO's Office of Public Records. The Office of Public Records can be reached by telephone at (703) 308-9726 or (800) 972-6382, by facsimile at (703) 305-8759, by mail addressed to the United States Patent and Trademark Office, Office of Public Records, Alexandria, VA 22313-1450 or via the Internet.

In addition, information on the status of the application, including the mailing date of Office actions and the dates of receipt of correspondence filed in the Office, may also be accessed via the Internet through the Patent Electronic Business Center at www.uspto.gov using the public side of the Patent Application Information and Retrieval (PAIR) system. The direct link to access this status information is currently <http://pair.uspto.gov/>. Prior to publication, such status information is confidential and may only be obtained by applicant using the private side of PAIR.

Further assistance in electronically accessing the publication, or about PAIR, is available by calling the Patent Electronic Business Center at 1-866-217-9197.

Office of Data Management, Application Assistance Unit (571) 272-4000, or (571) 272-4200, or 1-888-786-0101



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22315-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
14/606,794	01/27/2015	Brian James PETERSEN	1994-363US2	1047
6449 7590 01/26/2017 ROTHWELL, FIGG, ERNST & MANBECK, P.C. 607 14th Street, N.W. SUITE 800 WASHINGTON, DC 20005			EXAMINER BERRY JR, WILLIE WENDELL	
			ART UNIT 3652	PAPER NUMBER
			NOTIFICATION DATE 01/26/2017	DELIVERY MODE ELECTRONIC

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Notice of the Office communication was sent electronically on above-indicated "Notification Date" to the following e-mail address(es):

PTO-PAT-Email@rfem.com

Office Action Summary	Application No. 14/606,794	Applicant(s) PETERSEN ET AL.	
	Examiner WILLIE BERRY JR	Art Unit 3652	AIA (First Inventor to File) Status No

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTHS FROM THE MAILING DATE OF THIS COMMUNICATION.

Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133).
Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

1) ☒ Responsive to communication(s) filed on 1/27/15.
☐ A declaration(s)/affidavit(s) under **37 CFR 1.130(b)** was/were filed on ____.

2a) ☐ This action is **FINAL**. 2b) ☒ This action is non-final.

3) ☐ An election was made by the applicant in response to a restriction requirement set forth during the interview on ____; the restriction requirement and election have been incorporated into this action.

4) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims*

5) ☒ Claim(s) 39-60 is/are pending in the application.
5a) Of the above claim(s) ____ is/are withdrawn from consideration.

6) ☒ Claim(s) 49-60 is/are allowed.

7) ☒ Claim(s) 39-46 and 48 is/are rejected.

8) ☒ Claim(s) 47 is/are objected to.

9) ☐ Claim(s) ____ are subject to restriction and/or election requirement.

* If any claims have been determined allowable, you may be eligible to benefit from the **Patent Prosecution Highway** program at a participating intellectual property office for the corresponding application. For more information, please see http://www.uspto.gov/patents/init_events/pph/index.jsp or send an inquiry to PPHfeedback@uspto.gov.

Application Papers

10) ☐ The specification is objected to by the Examiner.

11) ☐ The drawing(s) filed on ____ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).

Priority under 35 U.S.C. § 119

12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).

Certified copies:

a) ☐ All b) ☐ Some** c) ☐ None of the:

1. ☐ Certified copies of the priority documents have been received.

2. ☐ Certified copies of the priority documents have been received in Application No. ____.

3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

** See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

1) ☒ Notice of References Cited (PTO-892)

2) ☒ Information Disclosure Statement(s) (PTO/SB/08a and/or PTO/SB/08b)
Paper No(s)/Mail Date ____

3) ☐ Interview Summary (PTO-413)
Paper No(s)/Mail Date ____

4) ☐ Other: ____

The present application is being examined under the pre-AIA first to invent provisions.

DETAILED ACTION

Specification

Applicant is reminded of the proper language and format for an abstract of the disclosure.

The abstract should be in narrative form and generally limited to a single paragraph on a separate sheet within the range of 50 to 150 words in length. The abstract should describe the disclosure sufficiently to assist readers in deciding whether there is a need for consulting the full patent text for details.

The language should be clear and concise and should not repeat information given in the title. It should avoid using phrases which can be implied, such as, "The disclosure concerns," "The disclosure defined by this invention," "The disclosure describes," etc. In addition, the form and legal phraseology often used in patent claims, such as "means" and "said," should be avoided.

In the instant case, the abstract is objected to for its use of legal phraseology, "said."

Claim Rejections - 35 USC § 102

In the event the determination of the status of the application as subject to AIA 35 U.S.C. 102 and 103 (or as subject to pre-AIA 35 U.S.C. 102 and 103) is incorrect, any

correction of the statutory basis for the rejection will not be considered a new ground of rejection if the prior art relied upon, and the rationale supporting the rejection, would be the same under either status.

The following is a quotation of the appropriate paragraphs of pre-AIA 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless –

(e) the invention was described in (1) an application for patent, published under section 122(b), by another filed in the United States before the invention by the applicant for patent or (2) a patent granted on an application for patent by another filed in the United States before the invention by the applicant for patent, except that an international application filed under the treaty defined in section 351(a) shall have the effects for purposes of this subsection of an application filed in the United States only if the international application designated the United States and was published under Article 21(2) of such treaty in the English language.

Claim(s) 39-44 is/are rejected under pre-AIA 35 U.S.C. 102(e) as being anticipated by patent no. 7,500,817 to Furrer et al.

Regarding claim 39, Furrer et al. discloses a seed or grain tender comprising: a main hopper (13) having a main hopper discharge (49); a support arm having first and second ends (not numbered, but shown in fig. 1A; note: the support is shown next to element [30] and attached to element [31]); said first end of said support arm being located below said main hopper and being rotatable about a first axis of rotation (not numbered, but shown in fig. 1A; note: first axis of rotation is the axis of rotation of the element [28]), and said first end of said support arm being rotatable about a second axis of rotation (not numbered, but shown in fig. 1A; note: the axis about which the support arm pivots is the second axis of rotation) that is perpendicular to said first axis of rotation; a conveyor (col. 4, lines 29-38) having a longitudinal axis and first and second ends, a conveyor hopper (34) at said first end, a conveyor discharge (36) at said second

end, and an internal elevator (col. 4, lines 29-38) for moving seed or grain from said conveyor hopper to said conveyor discharge; and said second end of said support arm being coupled with said conveyor between said first and second ends of said conveyor, said conveyor being rotatable about a third axis of rotation at said second end of said support arm that is not parallel to said conveyor longitudinal axis, and said conveyor being rotatable in relation to said second end of said support arm about said third of axis of rotation between an unloading position wherein said conveyor hopper is disposed below said main hopper discharge to receive agricultural product from said main hopper and a loading position wherein said conveyor discharge is disposed above said main hopper to dispense agricultural product into said main hopper (not numbered, but shown in figures 1 and 3).

Regarding claim 40, Furrer et al. discloses the seed or grain tender of claim 39, wherein said first axis of rotation extends through said main hopper discharge (not numbered, but shown in fig. 1).

Regarding claim 41, Furrer et al. discloses the seed or grain tender of claim 39, wherein said second axis of rotation extends through said first end of said support arm (not numbered, but shown in fig. 1A).

Regarding claim 42, Furrer et al. discloses the seed or gain tender of claim 39, wherein said third axis of rotation extends through said conveyor (not numbered, but shown in fig. 2).

Regarding claim 43, Furrer et al. discloses the seed or grain tender of claim 39, wherein said third axis of rotation extends through said second end of said support arm (not numbered, but shown in fig. 2).

Regarding claim 44, Furrer et al. discloses as discussed in previous response to claims 42 and 43.

Claim Rejections - 35 USC § 103

The following is a quotation of pre-AIA 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

Claims 45 and 46 is/are rejected under pre-AIA 35 U.S.C. 103(a) as being unpatentable over Furrer et al.

Regarding claim 45, Furrer et al. discloses the claimed invention except for the axis of rotation having an angle with a vertical component.

It would have been obvious to one having ordinary skill in the art at the time the invention was made to have provided the axis of rotation oriented at an angle having a vertical component, since it has been held that where the general conditions of a claim are disclosed in the prior art, discovering the optimum or workable ranges involves only routine skill in the art. *In re Aller*, 105 USPQ 233.

Regarding claim 46, Furrer et al. discloses the claimed invention except for the specific location of the support arm.

It would have been obvious to one having ordinary skill in the art at the time the invention was made to have placed the support arm near the center of gravity of the conveyor, since it has been held that rearranging parts of an invention involves only routine skill in the art. *In re Japikse*, 86 USPQ 70.

Claims 48 is/are rejected under pre-AIA 35 U.S.C. 103(a) as being unpatentable over Furrer et al. in view of patent no. 5,888,044 to Baskerville.

Regarding claim 48, Furrer et al. discloses the claimed invention except for the stand.

Baskerville discloses that it is known to have a stand (73) in a seed cart.

It would have been obvious to one having ordinary skill in the art at the time the invention was made to have modified Furrer et al. with the teachings of Baskerville for the purpose of enhancing versatility of the seed cart.

Allowable Subject Matter

Claims 49-60 are allowed.

Claim 47 is objected to as being dependent upon a rejected base claim, but would be allowable if rewritten in independent form including all of the limitations of the base claim and any intervening claims.

The following is an examiner's statement of reasons for allowance: The prior art does not show separately or in combination the detailed embodiment of a seed or grain tender comprising: a support arm having a first end proximate said lower portion of said main hopper and a second end; wherein said support arm is pivotable about a first axis

of rotation proximate said first end of said support arm to cause said support arm to be movable between an operating position wherein said support arm extends outwardly relative to said main hopper and a storage position wherein said support arm is folded inwardly towards said main hopper in relation to said operating position, said support arm further being pivotable about a second axis of rotation proximate said first end of said support arm to cause an elevation of said second end of said support arm to be adjustable;

Any comments considered necessary by applicant must be submitted no later than the payment of the issue fee and, to avoid processing delays, should preferably accompany the issue fee. Such submissions should be clearly labeled "Comments on Statement of Reasons for Allowance."

Conclusion

Any inquiry concerning this communication or earlier communications from the examiner should be directed to WILLIE BERRY JR whose telephone number is (571)272-6191. The examiner can normally be reached on Mon-Fri, 11:30-8pm.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Saul Rodriguez can be reached on (571)272-7097. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR.

Application/Control Number: 14/606,794
Art Unit: 3652

Page 8

Status information for unpublished applications is available through Private PAIR only.
For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should
you have questions on access to the Private PAIR system, contact the Electronic
Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a
USPTO Customer Service Representative or access to the automated information
system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

/SAUL RODRIGUEZ/
Supervisory Patent Examiner, Art
Unit 3652

Wbj.

Notice of References Cited	Application/Control No. 14/606,794		Applicant(s)/Patent Under Reexamination PETERSEN ET AL.	
	Examiner WILLIE BERRY JR		Art Unit 3652	Page 1 of 1

U.S. PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date MM-YYYY	Name	CPC Classification	US Classification
*	A	US-7,500,817 B2	03-2009	Furrer; G. Jason	A01C15/003	198/311
*	B	US-5,888,044 A	03-1999	Baskerville; Gregory Eugene	B60P1/42	198/311
	C	US-				
	D	US-				
	E	US-				
	F	US-				
	G	US-				
	H	US-				
	I	US-				
	J	US-				
	K	US-				
	L	US-				
	M	US-				

FOREIGN PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date MM-YYYY	Country	Name	CPC Classification
	N					
	O					
	P					
	Q					
	R					
	S					
	T					

NON-PATENT DOCUMENTS

*		(Include as applicable: Author, Title Date, Publisher, Edition or Volume, Pertinent Pages)
	U	
	V	
	W	
	X	

*A copy of this reference is not being furnished with this Office action. (See MPEP § 707.05(a)).
Dates in MM-YYYY format are publication dates. Classifications may be US or foreign.

U.S. Patent and Trademark Office
PTO-892 (Rev. 01-2001)

Notice of References Cited

Part of Paper No. 20170109

Receipt date: 04/06/2015

14606794 - GAU: 3652

INFORMATION DISCLOSURE STATEMENT BY APPLICANT (Not for submission under 37 CFR 1.99)	Application Number	14606794
	Filing Date	2015-01-27
	First Named Inventor	Brian James PETERSEN et al.
	Art Unit	3852
	Examiner Name	
	Attorney Docket Number	1994-363US2

CERTIFICATION STATEMENT			
Please see 37 CFR 1.97 and 1.98 to make the appropriate selection(s):			
☐ That each item of information contained in the information disclosure statement was first cited in any communication from a foreign patent office in a counterpart foreign application not more than three months prior to the filing of the information disclosure statement. See 37 CFR 1.97(e)(1).			
OR			
☐ That no item of information contained in the information disclosure statement was cited in a communication from a foreign patent office in a counterpart foreign application, and, to the knowledge of the person signing the certification after making reasonable inquiry, no item of information contained in the information disclosure statement was known to any individual designated in 37 CFR 1.56(c) more than three months prior to the filing of the information disclosure statement. See 37 CFR 1.97(e)(2).			
☐ See attached certification statement.			
☐ The fee set forth in 37 CFR 1.17 (p) has been submitted herewith.			
☒ A certification statement is not submitted herewith.			
SIGNATURE			
A signature of the applicant or representative is required in accordance with CFR 1.33, 10.18. Please see CFR 1.4(d) for the form of the signature.			
Signature		Date (YYYY-MM-DD)	2015-04-06
Name/Print	Brian S. Rosenbloom	Registration Number	41,276
This collection of information is required by 37 CFR 1.97 and 1.98. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 1 hour to complete, including gathering, preparing and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.			

Privacy Act Statement

The Privacy Act of 1974 (P.L. 93-579) requires that you be given certain information in connection with your submission of the attached form related to a patent application or patent. Accordingly, pursuant to the requirements of the Act, please be advised that: (1) the general authority for the collection of this information is 35 U.S.C. 2(b)(2); (2) furnishing of the information solicited is voluntary; and (3) the principal purpose for which the information is used by the U.S. Patent and Trademark Office is to process and/or examine your submission related to a patent application or patent. If you do not furnish the requested information, the U.S. Patent and Trademark Office may not be able to process and/or examine your submission, which may result in termination of proceedings or abandonment of the application or expiration of the patent.

The information provided by you in this form will be subject to the following routine uses:

1. The information on this form will be treated confidentially to the extent allowed under the Freedom of Information Act (5 U.S.C. 552) and the Privacy Act (5 U.S.C. 552a). Records from this system of records may be disclosed to the Department of Justice to determine whether the Freedom of Information Act requires disclosure of these records.
2. A record from this system of records may be disclosed, as a routine use, in the course of presenting evidence to a court, magistrate, or administrative tribunal, including disclosures to opposing counsel in the course of settlement negotiations.
3. A record in this system of records may be disclosed, as a routine use, to a Member of Congress submitting a request involving an individual, to whom the record pertains, when the individual has requested assistance from the Member with respect to the subject matter of the record.
4. A record in this system of records may be disclosed, as a routine use, to a contractor of the Agency having need for the information in order to perform a contract. Recipients of information shall be required to comply with the requirements of the Privacy Act of 1974, as amended, pursuant to 5 U.S.C. 552a(m).
5. A record related to an International Application filed under the Patent Cooperation Treaty in this system of records may be disclosed, as a routine use, to the International Bureau of the World Intellectual Property Organization, pursuant to the Patent Cooperation Treaty.
6. A record in this system of records may be disclosed, as a routine use, to another federal agency for purposes of National Security review (35 U.S.C. 181) and for review pursuant to the Atomic Energy Act (42 U.S.C. 218(c)).
7. A record from this system of records may be disclosed, as a routine use, to the Administrator, General Services, or his/her designee, during an inspection of records conducted by GSA as part of that agency's responsibility to recommend improvements in records management practices and programs, under authority of 44 U.S.C. 2904 and 2906. Such disclosure shall be made in accordance with the GSA regulations governing inspection of records for this purpose, and any other relevant (i.e., GSA or Commerce) directive. Such disclosure shall not be used to make determinations about individuals.
8. A record from this system of records may be disclosed, as a routine use, to the public after either publication of the application pursuant to 35 U.S.C. 122(b) or issuance of a patent pursuant to 35 U.S.C. 151. Further, a record may be disclosed, subject to the limitations of 37 CFR 1.14, as a routine use, to the public if the record was filed in an application which became abandoned or in which the proceedings were terminated and which application is referenced by either a published application, an application open to public inspections or an issued patent.
9. A record from this system of records may be disclosed, as a routine use, to a Federal, State, or local law enforcement agency, if the USPTO becomes aware of a violation or potential violation of law or regulation.

Receipt date: 04/06/2015

14606794 - GAU: 3652

Doc code: IDS

Doc description: Information Disclosure Statement (IDS) Filed

PTO/SB/08a (01-10)

Approved for use through 07/31/2012. OMB 0651-0031

U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

INFORMATION DISCLOSURE STATEMENT BY APPLICANT (Not for submission under 37 CFR 1.99)	Application Number	14606794
	Filing Date	2015-01-27
	First Named Inventor	Brian James PETERSEN et al.
	Art Unit	3652
	Examiner Name	
	Attorney Docket Number	1994-363US2

U.S. PATENTS						
Examiner Initial*	Cite No	Patent Number	Kind Code ¹	Issue Date	Name of Patentee or Applicant of cited Document	Pages, Columns, Lines where Relevant Passages or Relevant Figures Appear
	1	3090515		1963-05-21	Crowther	
	2	3493136		1970-02-03	Spellman, Jr.	
	3	3498483		1970-03-03	Meharry	
	4	4037745		1977-07-26	Hengen et al.	
	5	4411581		1983-10-25	Niewold	
	6	4742938		1988-05-10	Niewold	
	7	5520495		1996-05-28	Sukup	
	8	5718556		1998-02-17	Forsyth	

EFS Web 2.1.17

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /W.W.B/
ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /W.B./

Receipt date: 04/06/2015

14606794 -- GAU: 3652

INFORMATION DISCLOSURE STATEMENT BY APPLICANT (Not for submission under 37 CFR 1.99)	Application Number		14606794
	Filing Date		2015-01-27
	First Named Inventor	Brian James PETERSEN et al.	
	Art Unit	3652	
	Examiner Name		
	Attorney Docket Number	1994-363US2	

	9	3968771		1976-07-13	Walgenbach et al.	
	10	4503803		1985-03-12	Barnes	
	11	5800116		1998-09-01	Smith et al.	
	12	6209880		2001-04-03	Turnwald et al.	
	13	6325588		2001-12-04	Nolin	
	14	6604620		2003-08-12	Dennis	
	15	6767174		2004-07-27	Cresswell	
	16	7488149		2009-02-10	Waldner	
	17	7500817		2009-03-10	Furrer et al.	
	18	5529455		1996-06-25	Kaster et al.	
	19	7393275		2008-07-01	Voss et al.	

EFS Web 2.1.17

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /W.B./

Receipt date: 04/06/2015

14606794 -- GAU: 3652

INFORMATION DISCLOSURE STATEMENT BY APPLICANT (Not for submission under 37 CFR 1.99)	Application Number		14606794
	Filing Date		2015-01-27
	First Named Inventor	Brian James PETERSEN et al.	
	Art Unit	3652	
	Examiner Name		
	Attorney Docket Number	1994-363US2	

	20	5888044		1999-03-30	Baskerville	
	21	7267519		2007-09-11	Cresswell, et al.	
	22	7500814		2009-03-10	Meyer	
	23	4218169		1980-08-19	Arends	
	24	4274790		1981-06-23	Barker	
	25	4312621		1982-01-26	Quanbeck et al.	
	26	4419037		1983-12-06	Neiwold	
	27	4491216		1985-01-01	Sawby	
	28	4613275		1986-09-23	Karlowsky	
	29	5013208		1991-05-07	Grieshop	
	30	5468113		1995-11-21	Davis	

EFS Web 2.1.17

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /W.B./

Receipt date: 04/06/2015

14606794 -- GAU: 3652

INFORMATION DISCLOSURE STATEMENT BY APPLICANT (Not for submission under 37 CFR 1.99)	Application Number		14606794
	Filing Date		2015-01-27
	First Named Inventor	Brian James PETERSEN et al.	
	Art Unit	3652	
	Examiner Name		
	Attorney Docket Number	1994-363US2	

	31	5516253		1996-05-14	Linscheid et al.	
	32	5538388		1996-07-23	Bergkamp et al.	
	33	5582221		1996-12-10	Smith et al.	
	34	5615990		1997-04-01	Grieshop	
	35	5785481		1998-07-28	Ockels	
	36	5980189		1999-11-09	Rubner	
	37	6120233		2000-09-19	Adam	
	38	6908380		2005-06-21	Silver	
	39	7223059		2007-05-29	Smith et al.	
	40	7553228		2009-06-30	Dillon	
	41	6113339		2000-09-05	Adams	

EFS Web 2.1.17

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /W.B./

Receipt date: 04/06/2015

14606794 -- GAU: 3652

INFORMATION DISCLOSURE STATEMENT BY APPLICANT (Not for submission under 37 CFR 1.99)	Application Number	14606794
	Filing Date	2015-01-27
	First Named Inventor	Brian James PETERSEN et al.
	Art Unit	3652
	Examiner Name	
	Attorney Docket Number	1994-363US2

42	5484249		1996-01-16	klatt				
If you wish to add additional U.S. Patent citation information please click the Add button.								
U.S. PATENT APPLICATION PUBLICATIONS								
Examiner Initial*	Cite No	Publication Number	Kind Code ¹	Publication Date	Name of Patentee or Applicant of cited Document	Pages, Columns, Lines where Relevant Passages or Relevant Figures Appear		
	1	20030057055		2003-03-27	Haukaas et al.			
	2	20060180062		2006-04-17	Furrer et al.			
If you wish to add additional U.S. Published Application citation information please click the Add button.								
FOREIGN PATENT DOCUMENTS								
Examiner Initial*	Cite No	Foreign Document Number ³	Country Code ²	Kind Code ⁴	Publication Date	Name of Patentee or Applicant of cited Document	Pages, Columns, Lines where Relevant Passages or Relevant Figures Appear	T ⁵
	1							☐
If you wish to add additional Foreign Patent Document citation information please click the Add button								
NON-PATENT LITERATURE DOCUMENTS								
Examiner Initials*	Cite No	Include name of the author (in CAPITAL LETTERS), title of the article (when appropriate), title of the item (book, magazine, journal, serial, symposium, catalog, etc), date, pages(s), volume-issue number(s), publisher, city and/or country where published.						T ⁵
	1	Model 2300 Air System and the Model 4800 Air Drill, both made and sold by Concord, as illustrated in the Concord brochure, 12 pages.						☐
	2	Convey-Air, BTS 290 Seed Tender Product Specification, 2 pages.						☐

EFS Web 2.1.17

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /W.B./

Receipt date: 04/06/2015

14606794 -- GAU: 3652

INFORMATION DISCLOSURE STATEMENT BY APPLICANT (Not for submission under 37 CFR 1.99)	Application Number	14606794
	Filing Date	2015-01-27
	First Named Inventor	Brian James PETERSEN et al.
	Art Unit	3652
	Examiner Name	
	Attorney Docket Number	1994-363US2

3	Convey-All Ind. Inc., Engineering Drawings of BT-1500, 4 pages.	☐
4	Par-Kan Company, Engineering Drawings, 2 pages.	☐
5	Great Plains Manufacturing, Inc., Parts Manual - Model ADC2220 Air Drill Cart, May 1, 1997, 61 pages.	☐
6	Great Plains Manufacturing, Inc., Parts Manual - Model ADC2220 Air Drill Cart, March 1, 2000, 69 pages.	☐
7	Reexamination File History for Control Number 95000691, 374 pages.	☐
8	Order Denying Request for Inter Partes Reexamination for Control Number 95000691, November 7, 2012, 15 pages.	☐
9	Par-Kan Company, Final Invalidity Contentions submitted in Unverferth Mfg. Co., Inc. v. Par-Kan Co., Civil Action No. 13-cv-00097 (N.D. Ind.), October 25, 2013, 130 pages.	☐
10	Par-Kan Company, Preliminary Invalidity Contentions submitted in Unverferth Mfg. Co., Inc. v. Par-Kan Co., Civil Action No. 13-cv-00097 (N.D. Ind.), June 17, 2013, 169 pages.	☐
11	Declaration of Shawn Gerdeman with Exhibits A-E dated September 18, 2014, 24 pages.	☐
If you wish to add additional non-patent literature document citation information please click the Add button		
EXAMINER SIGNATURE		
Examiner Signature	/WILLIE W BERRY JR/	Date Considered 01/09/2017
*EXAMINER: Initial if reference considered, whether or not citation is in conformance with MPEP 609. Draw line through a citation if not in conformance and not considered. Include copy of this form with next communication to applicant.		

EFS Web 2.1.17

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /W.B./

Receipt date: 04/06/2015

14606794 -- GAU: 3652

INFORMATION DISCLOSURE STATEMENT BY APPLICANT (Not for submission under 37 CFR 1.99)	Application Number	14606794
	Filing Date	2015-01-27
	First Named Inventor	Brian James PETERSEN et al.
	Art Unit	3652
	Examiner Name	
	Attorney Docket Number	1994-363US2

¹ See Kind Codes of USPTO Patent Documents at www.USPTO.GOV or MPEP 901.04. ² Enter office that issued the document, by the two-letter code (WIPO Standard ST.3). ³ For Japanese patent documents, the indication of the year of the reign of the Emperor must precede the serial number of the patent document. ⁴ Kind of document by the appropriate symbols as indicated on the document under WIPO Standard ST.16 if possible. ⁵ Applicant is to place a check mark here if English language translation is attached.

Receipt date: 04/06/2015

14606794 - GAU: 3652

Notice of References Cited	Application/Control No. 14/606,794 14/541,353	Applicant(s)/Patent Under Reexamination PETERSEN ET AL.	
	Examiner GLENN MYERS	Art Unit 3652	Page 1 of 1

U.S. PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date MM-YYYY	Name	Classification
*	A	US-6,120,233	09-2000	Adam, Gerald E.	414/502
*	B	US-5,718,556	02-1998	Forsyth, Daniel L.	414/503
*	C	US-5,520,495	05-1996	Sukup, Eugene G.	414/523
*	D	US-3,498,483	03-1970	MEHARRY JAMES L	414/523
*	E	US-1,905,434	04-1933	FERNAND BOYER	414/328
*	F	US-5,484,249	01-1996	Klatt, Dennis	414/523
	G	US-			
	H	US-			
	I	US-			
	J	US-			
	K	US-			
	L	US-			
	M	US-			

FOREIGN PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date MM-YYYY	Country	Name	Classification
	N					
	O					
	P					
	Q					
	R					
	S					
	T					

NON-PATENT DOCUMENTS

*		Include as applicable: Author, Title Date, Publisher, Edition or Volume, Pertinent Pages)
	U	
	V	
	W	
	X	

*A copy of this reference is not being furnished with this Office action. (See MPEP § 707.05(a).)
Dates in MM-YYYY format are publication dates. Classifications may be US or foreign.

U.S. Patent and Trademark Office
PTO-892 (Rev. 01-2001)

Notice of References Cited

Part of Paper No. 20140625

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /W.B./

Receipt date: 04/06/2015

14606794 - GAU: 3652

FOR SN 141606, 794

Notice of References Cited	Application/Control No. ~~13/641,558~~	Applicant(s)/Patent Under Reexamination PETERSEN ET AL.	
	Examiner JOSHUA RUDAWITZ	Art Unit 3652	Page 1 of 2

U.S. PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date MM-YYYY	Name	Classification
*	A	US-427,736 A	05-1890	Bulkin	198/317
*	B	US-3,968,771 A	07-1976	Walgenbach et al.	118/303
*	C	US-3,994,512 A	11-1976	Parker et al.	280/687
*	D	US-3,997,215 A	12-1976	Parker et al.	298/24
*	E	US-4,503,803 A	03-1985	Barnes, Ronald A.	118/303
*	F	US-5,615,990 A	04-1997	Grieshop, Maurice	414/526
*	G	US-5,800,116 A	09-1998	Smith et al.	414/523
*	H	US-5,888,044 A	03-1999	Baskerville, Gregory Eugene	414/523
*	I	US-6,209,880 B1	04-2001	Turnwald et al.	277/402
*	J	US-6,325,588 B1	12-2001	Nolin, Karl W.	414/526
*	K	US-2003/0057055 A1	03-2003	Haukaas et al.	198/313
*	L	US-6,604,620 B2	08-2003	Dennis, Andrew	198/312
*	M	US-6,767,174 B2	07-2004	Cresswell, Mark	414/523

FOREIGN PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date MM-YYYY	Country	Name	Classification
	N					
	O					
	P					
	Q					
	R					
	S					
	T					

NON-PATENT DOCUMENTS

*		Include as applicable: Author, Title Date, Publisher, Edition or Volume, Pertinent Pages)
	U	
	V	
	W	
	X	

*A copy of this reference is not being furnished with this Office action. (See MPEP § 707.05(a).)
Dates in MM-YYYY format are publication dates. Classifications may be US or foreign.

U.S. Patent and Trademark Office
PTO-892 (Rev. 01-2001)

Notice of References Cited

Part of Paper No. 20130923

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /W.B./

Receipt date: 04/06/2015

14606794 - GAU: 3652

FOR S.N. 14/606,794

Notice of References Cited	Application/Control No. ~~13/541,553~~	Applicant(s)/Patent Under Reexamination PETERSEN ET AL.	
	Examiner JOSHUA RUDAWITZ	Art Unit 3652	Page 2 of 2

U.S. PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date MM-YYYY	Name	Classification
*	A	US-7,428,956 B2	09-2008	Scherman, Patrick John	198/312
*	B	US-7,488,149 B2	02-2009	Waldner, Samuel	414/532
*	C	US-7,500,817 B2	03-2009	Furrer et al.	414/522
*	D	US-2009/0110524 A1	04-2009	Hoffmann, Mark A.	414/507
*	E	US-8,221,047 B2	07-2012	Petersen et al.	414/523
	F	US-			
	G	US-			
	H	US-			
	I	US-			
	J	US-			
	K	US-			
	L	US-			
	M	US-			

FOREIGN PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date MM-YYYY	Country	Name	Classification
	N					
	O					
	P					
	Q					
	R					
	S					
	T					

NON-PATENT DOCUMENTS

*		Include as applicable: Author, Title Date, Publisher, Edition or Volume, Pertinent Pages)
	U	
	V	
	W	
	X	

*A copy of this reference is not being furnished with this Office action. (See MPEP § 707.05(a).)
Dates in MM-YYYY format are publication dates. Classifications may be US or foreign.

U.S. Patent and Trademark Office
PTO-892 (Rev. 01-2001)

Notice of References Cited

Part of Paper No. 20130923

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /W.B./

Electronic Acknowledgement Receipt	
EFS ID:	29031608
Application Number:	14606794
International Application Number:	
Confirmation Number:	1047
Title of Invention:	SEED CARRIER WITH PIVOTING CONVEYOR
First Named Inventor/Applicant Name:	Brian James PETERSEN
Customer Number:	6449
Filer:	George R. Repper/Marilyn Davis
Filer Authorized By:	George R. Repper
Attorney Docket Number:	1994-363US2
Receipt Date:	26-APR-2017
Filing Date:	27-JAN-2015
Time Stamp:	13:51:39
Application Type:	Utility under 35 USC 111(a)

Payment information:

Submitted with Payment:	yes
Payment Type	CARD
Payment was successfully received in RAM	\$180
RAM confirmation Number	042717INTEFSW13534000
Deposit Account	022135
Authorized User	Marilyn Davis
The Director of the USPTO is hereby authorized to charge indicated fees and credit any overpayment as follows: 37 CFR 1.21 (Miscellaneous fees and charges)	

File Listing:					
Document Number	Document Description	File Name	File Size(Bytes)/ Message Digest	Multi Part /.zip	Pages (if appl.)
1	Amendment/Req. Reconsideration- After Non-Final Reject	1194_363US2Response.pdf	109572 8540900e52097f1c2080d14a1e7f0e0d0e427	no	10
Warnings:					
Information:					
2	Information Disclosure Statement (IDS) Form (SB08)	1994_363US2SB08.PDF	1035763 5b40c911614011f00a8f5c5220631e1e01f1c2a01	no	5
Warnings:					
Information:					
A U.S. Patent Number Citation or a U.S. Publication Number Citation is required in the Information Disclosure Statement (IDS) form for autoloading of data into USPTO systems. You may remove the form to add the required data in order to correct the Informational Message if you are citing U.S. References. If you chose not to include U.S. References, the image of the form will be processed and be made available within the Image File Wrapper (IFW) system. However, no data will be extracted from this form. Any additional data such as Foreign Patent Documents or Non Patent Literature will be manually reviewed and keyed into USPTO systems.					
3	Foreign Reference	FR2465667.pdf	5219002 10b42761c40900ec0275e4c3039f9934f11c1a0f	no	7
Warnings:					
Information:					
4	Foreign Reference	TranslationofFR2465667.pdf	4352896 9090a000167f524e0c01177f00a00201f1c1a0f	no	7
Warnings:					
Information:					
5	Foreign Reference	CA2416677.pdf	9303918 1400c557d0c52800c54cc330f9246c304f5c2535	no	17
Warnings:					
Information:					

6	Non Patent Literature	NPL1_HinikerModel4836OperatorManual.pdf	9987099	no	58
			33076c41d1830924771e2461e689120639a1c3a		
Warnings:					
Information:					
7	Non Patent Literature	NPL2_HinikerModel4831AssemblyManual.pdf	8306400	no	49
			3063c316323e5e405c1d55a408b187a071323d96a3		
Warnings:					
Information:					
8	Non Patent Literature	NPL3_HinikerModel4831ProductSheet.pdf	231205	no	1
			1f1f7944523cc338a927391f3a27407633b1955a5		
Warnings:					
Information:					
9	Non Patent Literature	NPL4_HinikerFillAugerSupportAssembly.pdf	228633	no	1
			49c5271622007111a2053f833a4c3999181087c86		
Warnings:					
Information:					
10	Non Patent Literature	NPL5_HinikerCompany4800SoybeanPlanter.pdf	2808363	no	6
			798359e82856e4a30818771176330c23a12c956e		
Warnings:					
Information:					
11	Non Patent Literature	NPL7_AnnotatedPhotographsofHinikerAirSeederCart.pdf	4843229	no	8
			1183543a41330071c22f420f9c05c0a707cc08e		
Warnings:					
Information:					
12	Non Patent Literature	NPL8_GreatPlainsManufacturing220BushelAirCart.pdf	800111	no	2
			18333165806d5796d37750039a7cc47a6b1a13d		
Warnings:					
Information:					

13	Non Patent Literature	NPL9_J_M_sAmendedInitialInvalidityContentions_February_7_2017.pdf	210095 354236ad768f9a15e87a1923623e902e802b812b	no	59
Warnings:					
Information:					
14	Non Patent Literature	NPL_6a_HinkerCompanyProductPhotographs.pdf	23348084 a86e888006a07c00932a33e588ee133c5180b	no	33
Warnings:					
Information:					
15	Non Patent Literature	NPL_6b_HinkerCompanyProductPhotographs.pdf	24098469 716d18b1c0f8c1d6a09e23e735623e15e48971	no	34
Warnings:					
Information:					
16	Fee Worksheet (SB06)	fee-info.pdf	31005 840201050e7709e032e087ff9f088b2e8155a9e	no	2
Warnings:					
Information:					
Total Files Size (in bytes):			94913844		
This Acknowledgement Receipt evidences receipt on the noted date by the USPTO of the indicated documents, characterized by the applicant, and including page counts, where applicable. It serves as evidence of receipt similar to a Post Card, as described in MPEP 503. <u>New Applications Under 35 U.S.C. 111</u> If a new application is being filed and the application includes the necessary components for a filing date (see 37 CFR 1.53(b)-(d) and MPEP 506), a Filing Receipt (37 CFR 1.54) will be issued in due course and the date shown on this Acknowledgement Receipt will establish the filing date of the application. <u>National Stage of an International Application under 35 U.S.C. 371</u> If a timely submission to enter the national stage of an international application is compliant with the conditions of 35 U.S.C. 371 and other applicable requirements a Form PCT/DO/EO/903 indicating acceptance of the application as a national stage submission under 35 U.S.C. 371 will be issued in addition to the Filing Receipt, in due course. <u>New International Application Filed with the USPTO as a Receiving Office</u> If a new international application is being filed and the international application includes the necessary components for an international filing date (see PCT Article 11 and MPEP 1810), a Notification of the International Application Number and of the International Filing Date (Form PCT/RO/105) will be issued in due course, subject to prescriptions concerning national security, and the date shown on this Acknowledgement Receipt will establish the international filing date of the application.					

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Appl. No. : 14/606,794
First Named Inventor : Brian James PETERSEN
Filed : January 27, 2015
TC/A.U. : 3652
Examiner : Willie Wendell Berry Jr.

Docket No. : 1994-363.US2
Customer No. : 06449
Confirmation No. : 1047

RESPONSE

Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

Dear Sir:

In response to the non-final Office Action mailed January 26, 2017, Applicant respectfully requests consideration of the remarks contained on the following pages. This paper is being timely filed on or before April 26, 2017. Authorization is hereby given to charge Deposit Account No. 02-2135 for any fees deemed necessary.

Amendments to the Specification begin on page 2 of this paper

Amendments to the Claims begin on page 3 of this paper.

Remarks begin on page 8 of this paper.

AMENDMENTS TO THE SPECIFICATION

Please amend the Abstract in the specification as follows (deletions are double bracketed and additions are underlined):

A seed carrier includes a main hopper coupled with a frame via leg members. The main hopper has a discharge. A base plate is coupled with the frame. A support arm is rotatably coupled with the base plate at a first end. A belt driven conveyor having a conveyor hopper at a first end and a discharge at a second end is rotatably coupled with a second end of ~~[[said]]~~ the support arm at an approximate center of gravity thereof. A latch mechanism is provided for detachably coupling the first end of the conveyor with the first end of the support arm such that the conveyor hopper is position below the main hopper discharge. When the conveyor is uncoupled from the first end of the support arm, the conveyor can rotate to a loading position wherein the discharge thereof can be positioned over the main hopper.

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

1-38. (Cancelled)

39. (Currently Amended) A seed or grain tender comprising:

a main hopper having a main hopper discharge;

a support arm having first and second ends;

said first end of said support arm being located below said main hopper and being rotatable about a first axis of rotation, and said first end of said support arm being rotatable about a second axis of rotation that is perpendicular to said first axis of rotation;

a conveyor having a longitudinal axis and first and second ends, a conveyor hopper at said first end, a conveyor discharge at said second end, and an internal elevator for moving seed or grain from said conveyor hopper to said conveyor discharge; [[and]]

said second end of said support arm being coupled with said conveyor between said first and second ends of said conveyor, said conveyor being rotatable about a third axis of rotation at said second end of said support arm that is not parallel to said conveyor longitudinal axis, and said conveyor being rotatable in relation to said second end of said support arm about said third axis of rotation between an unloading position wherein said conveyor hopper is disposed below said main hopper discharge to receive agricultural product from said main hopper and a loading position wherein said conveyor discharge is disposed above said main hopper to dispense agricultural product into said main hopper, and

a hydraulic piston extending at an acute angle relative to a horizontal plane to connect with a portion of said support arm spaced from said second axis of rotation.

40. (Previously Presented) The seed or grain tender of claim 39, wherein said first axis of rotation extends through said main hopper discharge.

41. (Previously Presented) The seed or grain tender of claim 39, wherein said second axis of rotation extends through said first end of said support arm.

42. (Previously Presented) The seed or grain tender of claim 39, wherein said third axis of rotation extends through said conveyor.

43. (Previously Presented) The seed or grain tender of claim 39, wherein said third axis of rotation extends through said second end of said support arm.

44. (Previously Presented) The seed or grain tender of claim 39, wherein said third axis of rotation extends through said conveyor and said second end of said support arm.

45. (Previously Presented) The seed or grain tender of claim 39, wherein said third axis of rotation is oriented at an angle having a vertical component.

46. (Previously Presented) The seed or grain tender of claim 39, wherein said second end of said support arm is coupled with said conveyor at or near said approximate center of gravity of said conveyor.

47. (Cancelled)

48. (Previously Presented) The seed or grain tender of claim 39, further comprising a stand coupled with said first end of said conveyor and movable between a stowed position allowing said conveyor hopper to be positioned below said main hopper discharge when said conveyor is in said unloading position and an extended position supporting said conveyor hopper above the ground when said conveyor is in said loading position.

49. (Previously Presented) A seed or grain tender comprising:

a main hopper having an upper portion with a main hopper intake opening and a lower portion with a main hopper discharge;

a support arm having a first end proximate said lower portion of said main hopper and a second end;

wherein said support arm is pivotable about a first axis of rotation proximate said first end of said support arm to cause said support arm to be movable between an operating position wherein said support arm extends outwardly relative to said main hopper and a storage position wherein said support arm is folded inwardly towards said main hopper in relation to said operating position, said support arm further being pivotable about a second axis of rotation proximate said first end of said support arm to cause an elevation of said second end of said support arm to be adjustable;

a conveyor having a longitudinal axis and first and second ends, a conveyor hopper at said first end, a conveyor discharge at said second end, and an internal elevator for moving seed or grain from said conveyor hopper to said conveyor discharge; and

said second end of said support arm being coupled with said conveyor between said first and second conveyor ends, said conveyor being rotatable about a third axis of rotation proximate

said second end of said support arm that is not parallel to said conveyor longitudinal axis, and said conveyor being rotatable in relation to said second end of said support arm about said third of axis of rotation between an unloading position wherein said conveyor hopper is disposed below said main hopper discharge to receive agricultural product from said main hopper and a loading position wherein said conveyor discharge is disposed above said intake opening of said main hopper to dispense agricultural product into said main hopper.

50. (Previously Presented) The seed or grain tender of claim 49, wherein said first axis of rotation extends through said main hopper discharge.

51. (Previously Presented) The seed or grain tender of claim 49, wherein said second axis of rotation extends through said first end of said support arm.

52. (Previously Presented) The seed or grain tender of claim 49, wherein said third axis of rotation extends through said conveyor.

53. (Previously Presented) The seed or grain tender of claim 49, wherein said third axis of rotation extends through said second end of said support arm.

54. (Previously Presented) The seed or grain tender of claim 49, wherein said third axis of rotation extends through said conveyor and said second end of said support arm

55. (Previously Presented) The seed or grain tender of claim 49, wherein said third axis of rotation is oriented at an angle having a vertical component.

56. (Previously Presented) The seed or grain tender of claim 55, wherein said first axis of rotation is vertical.

57. (Previously Presented) The seed or grain tender of claim 56, wherein said second axis of rotation is horizontal.

58. (Previously Presented) The seed or grain tender of claim 49, wherein said second end of said support arm is coupled with said conveyor at an approximate center of gravity of said conveyor.

59. (Previously Presented) The seed or grain tender of claim 49, further comprising a hydraulic piston extending at an acute angle relative to a horizontal plane to connect with a portion of said support arm spaced from said second axis of rotation.

60. (Previously Presented) The seed or grain tender of claim 49, further comprising a stand coupled with said first end of said conveyor and movable between a stowed position allowing said conveyor hopper to be positioned below said main hopper discharge when said conveyor is in said unloading position and an extended position supporting said conveyor hopper above the ground when said conveyor is in said loading position.

REMARKS

The non-final Office Action dated January 26, 2017, has been received and carefully reviewed. The preceding amendments and following remarks form a full and complete response thereto. Claim 39 has been amended. Specifically, claim 39 has been amended to incorporate the subject matter of claim 47, which was indicated as containing allowable subject matter. In view of the amendment to claim 39, claim 47 has been cancelled. Claims 39-46 and 48-60 are currently pending. Reconsideration of all outstanding rejections is respectfully requested in view of the following remarks.

Allowable Subject Matter

Applicants would like to thank the Examiner for the indication of allowable subject matter. In the Office Action, claims 49-60 were allowed. Further, claim 47 was indicated as being directed to allowable subject matter and allowable if rewritten in independent form. The subject matter of dependent claim 47 has been incorporated into independent claim 39 for the sole purpose of advancing prosecution. Thus, claim 39 now recites the subject matter of claim 47 in independent form. Moreover, claims 40-46 and 49 depend from claim 39. Accordingly, Applicant submits that all pending claims are in condition for allowance.

Objection to the Specification

The abstract was objected to for its use of the term "said," which was alleged to be legal phraseology. For purposes of advancing prosecution, the abstract has been amended to replace the term "said" with the word "the." Thus, Applicant respectfully requests withdrawal of the objection to the specification.

Response to Rejections Under 35 U.S.C. § 103

Claims 39-44 were rejected under pre-AIA 35 U.S.C. § 102(e) as being anticipated by U.S. Patent No. 7,500,817 to Furrer et al. ("Furrer"). Claims 45 and 46 were rejected under pre-AIA 35 U.S.C. § 103(a) as being unpatentable over Furrer. Finally, claim 48 was rejected under pre-AIA 35 U.S.C. § 103(a) as being unpatentable over Furrer in view of U.S. Patent No. 5,888,044 to Baskerville ("Baskerville"). Applicant respectfully submits that the claimed invention is neither anticipated by nor obvious over the cited art.

While Applicant disagrees with the rejection, claim 39 has been amended to incorporate the subject matter of claim 47 for the purpose of advancing prosecution, as claim 47 was not rejected and was indicated as containing allowable subject matter. Accordingly, Applicant respectfully submits that amended claim 39 is patentable over the cited art. Moreover, as claims 40-46 and 49 depend from claim 39, these claims are also patentable over the cited art. Therefore, Applicant respectfully requests withdrawal of the rejections under 35 U.S.C. §§ 102 and 103.

Conclusion

All of the stated grounds of rejections have been properly traversed, accommodated, or rendered moot. Applicants therefore respectfully request that the Examiner reconsider all presently outstanding rejections, and that they be withdrawn. Applicants respectfully submit that present claims 39-46 and 48-60 are now in condition for allowance.

If for any reason the Examiner determines that the application is not now in condition for allowance, it is respectfully requested that the Examiner contact, by telephone, the Applicants'

undersigned attorney at the indicated telephone number to arrange for an interview to expedite the disposition of this application.

Respectfully submitted,

By /George R. Repper/
George R. Repper
Attorney for Applicants
Registration No. 31,414
ROTHWELL, FIGG, ERNST & MANBECK, P.C.
607 14th Street, N.W., Suite 800
Washington, D.C. 20005
Telephone: (202)783-6040

INFORMATION DISCLOSURE STATEMENT BY APPLICANT (Not for submission under 37 CFR 1.99)	Application Number	14606794
	Filing Date	2015-01-27
	First Named Inventor	Brian James PETERSEN
	Art Unit	3652
	Examiner Name	Willie Wendell Berry Jr.
	Attorney Docket Number	1994-363,US2

CERTIFICATION STATEMENT			
Please see 37 CFR 1.97 and 1.98 to make the appropriate selection(s):			
That each item of information contained in the information disclosure statement was first cited in any communication from a foreign patent office in a counterpart foreign application not more than three months prior to the filing of the information disclosure statement. See 37 CFR 1.97(e)(1).			
OR			
That no item of information contained in the information disclosure statement was cited in a communication from a foreign patent office in a counterpart foreign application, and, to the knowledge of the person signing the certification after making reasonable inquiry, no item of information contained in the information disclosure statement was known to any individual designated in 37 CFR 1.56(c) more than three months prior to the filing of the information disclosure statement. See 37 CFR 1.97(e)(2).			
☐ See attached certification statement.			
☒ The fee set forth in 37 CFR 1.17 (p) has been submitted herewith.			
☒ A certification statement is not submitted herewith.			
SIGNATURE			
A signature of the applicant or representative is required in accordance with CFR 1.33, 10.18. Please see CFR 1.4(d) for the form of the signature.			
Signature	/George R. Repper/	Date (YYYY-MM-DD)	2017-04-26
Name/Print	George R. Repper	Registration Number	31,414
This collection of information is required by 37 CFR 1.97 and 1.98. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 1 hour to complete, including gathering, preparing and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.			

Privacy Act Statement

The Privacy Act of 1974 (P.L. 93-579) requires that you be given certain information in connection with your submission of the attached form related to a patent application or patent. Accordingly, pursuant to the requirements of the Act, please be advised that: (1) the general authority for the collection of this information is 35 U.S.C. 2(b)(2); (2) furnishing of the information solicited is voluntary; and (3) the principal purpose for which the information is used by the U.S. Patent and Trademark Office is to process and/or examine your submission related to a patent application or patent. If you do not furnish the requested information, the U.S. Patent and Trademark Office may not be able to process and/or examine your submission, which may result in termination of proceedings or abandonment of the application or expiration of the patent.

The information provided by you in this form will be subject to the following routine uses:

1. The information on this form will be treated confidentially to the extent allowed under the Freedom of Information Act (5 U.S.C. 552) and the Privacy Act (5 U.S.C. 552a). Records from this system of records may be disclosed to the Department of Justice to determine whether the Freedom of Information Act requires disclosure of these records.
2. A record from this system of records may be disclosed, as a routine use, in the course of presenting evidence to a court, magistrate, or administrative tribunal, including disclosures to opposing counsel in the course of settlement negotiations.
3. A record in this system of records may be disclosed, as a routine use, to a Member of Congress submitting a request involving an individual, to whom the record pertains, when the individual has requested assistance from the Member with respect to the subject matter of the record.
4. A record in this system of records may be disclosed, as a routine use, to a contractor of the Agency having need for the information in order to perform a contract. Recipients of information shall be required to comply with the requirements of the Privacy Act of 1974, as amended, pursuant to 5 U.S.C. 552a(m).
5. A record related to an International Application filed under the Patent Cooperation Treaty in this system of records may be disclosed, as a routine use, to the International Bureau of the World Intellectual Property Organization, pursuant to the Patent Cooperation Treaty.
6. A record in this system of records may be disclosed, as a routine use, to another federal agency for purposes of National Security review (35 U.S.C. 181) and for review pursuant to the Atomic Energy Act (42 U.S.C. 218(c)).
7. A record from this system of records may be disclosed, as a routine use, to the Administrator, General Services, or his/her designee, during an inspection of records conducted by GSA as part of that agency's responsibility to recommend improvements in records management practices and programs, under authority of 44 U.S.C. 2904 and 2906. Such disclosure shall be made in accordance with the GSA regulations governing inspection of records for this purpose, and any other relevant (i.e., GSA or Commerce) directive. Such disclosure shall not be used to make determinations about individuals.
8. A record from this system of records may be disclosed, as a routine use, to the public after either publication of the application pursuant to 35 U.S.C. 122(b) or issuance of a patent pursuant to 35 U.S.C. 151. Further, a record may be disclosed, subject to the limitations of 37 CFR 1.14, as a routine use, to the public if the record was filed in an application which became abandoned or in which the proceedings were terminated and which application is referenced by either a published application, an application open to public inspections or an issued patent.
9. A record from this system of records may be disclosed, as a routine use, to a Federal, State, or local law enforcement agency, if the USPTO becomes aware of a violation or potential violation of law or regulation.

Doc code: IDS

Doc description: Information Disclosure Statement (IDS) Filed

PTO/SB/08a (03-15)

Approved for use through 07/31/2016, OMB 0651-0031

U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

INFORMATION DISCLOSURE STATEMENT BY APPLICANT (Not for submission under 37 CFR 1.99)	Application Number	14606794
	Filing Date	2015-01-27
	First Named Inventor	Brian James PETERSEN
	Art Unit	3652
	Examiner Name	Willie Wendell Berry Jr.
	Attorney Docket Number	1994-363.US2

U.S. PATENTS							Remove	
Examiner Initial*	Cite No	Patent Number	Kind Code ¹	Issue Date	Name of Patentee or Applicant of cited Document	Pages, Columns, Lines where Relevant Passages or Relevant Figures Appear		
	1							
If you wish to add additional U.S. Patent citation information please click the Add button.							Add	
U.S. PATENT APPLICATION PUBLICATIONS							Remove	
Examiner Initial*	Cite No	Publication Number	Kind Code ¹	Publication Date	Name of Patentee or Applicant of cited Document	Pages, Columns, Lines where Relevant Passages or Relevant Figures Appear		
	1							
If you wish to add additional U.S. Published Application citation information please click the Add button.							Add	
FOREIGN PATENT DOCUMENTS							Remove	
Examiner Initial*	Cite No	Foreign Document Number ³	Country Code ^{2j}	Kind Code ⁴	Publication Date	Name of Patentee or Applicant of cited Document	Pages, Columns, Lines where Relevant Passages or Relevant Figures Appear	T ⁵
	1	2465667	FR	A1	1981-03-27	DEBOFFLES, Regis		×
	2	2416677	CA	A1	2004-08-13	HUNDEBY, David R.		□
If you wish to add additional Foreign Patent Document citation information please click the Add button							Add	
NON-PATENT LITERATURE DOCUMENTS							Remove	

EFS Web 2.1.17

INFORMATION DISCLOSURE STATEMENT BY APPLICANT (Not for submission under 37 CFR 1.99)	Application Number		14606794
	Filing Date		2015-01-27
	First Named Inventor	Brian James PETERSEN	
	Art Unit	3652	
	Examiner Name	Willie Wendell Berry Jr.	
	Attorney Docket Number	1994-363,US2	

Examiner Initials*	Cite No	Include name of the author (in CAPITAL LETTERS), title of the article (when appropriate), title of the item (book, magazine, journal, serial, symposium, catalog, etc), date, pages(s), volume-issue number(s), publisher, city and/or country where published.	T ⁵
	1	Hiniker Company, Model 4836 Air Seeder Cart with 4800 Air Drill Front Folding Toolbar, Operator's Manual, January 1999, 58 pages.	
	2	Hiniker Company, Models 4831, 4832, and 4833 Air Seeder Cart with 4800 Air Seeder Front Folding Toolbar, Assembly Manual, January 2000, 49 pages.	
	3	Hiniker 4831, 4832, 4833 Air Seeder, July 21, 1999, 1 page.	
	4	Hiniker Company, Fill Auger Support Assembly, 1 page.	
	5	Hiniker Company, 4800 Soybean Planter Marketing Material, 6 pages.	
	6	Hiniker Company, Product Photographs, 67 pages.	
	7	J&M Manufacturing Company, Inc., Annotated Photographs of Hiniker Company 4836 Air Seed Cart, 8 pages.	
	8	Great Plains Manufacturing, 220 Bushel Air Cart, 2 pages.	
	9	J&M Manufacturing Company, Inc., J&M Mfg. Co., Inc.'s Amended Initial Invalidity Contentions submitted in Unverferth Mfg. Co., Inc. v. J&M Mfg. Co., Inc., Civil Action No. 3:16-cv-02282-JZ (N.D. Ohio), February 7, 2017, 59 pages.	
If you wish to add additional non-patent literature document citation information please click the Add button			Add

INFORMATION DISCLOSURE STATEMENT BY APPLICANT (Not for submission under 37 CFR 1.99)	Application Number	14606794
	Filing Date	2015-01-27
	First Named Inventor	Brian James PETERSEN
	Art Unit	3652
	Examiner Name	Willie Wendell Berry Jr.
	Attorney Docket Number	1994-363.US2

EXAMINER SIGNATURE	
Examiner Signature	Date Considered
*EXAMINER: Initial if reference considered, whether or not citation is in conformance with MPEP 609. Draw line through a citation if not in conformance and not considered. Include copy of this form with next communication to applicant.	
¹ See Kind Codes of USPTO Patent Documents at www.USPTO.GOV or MPEP 901.04. ² Enter office that issued the document, by the two-letter code (WIPO Standard ST.3). ³ For Japanese patent documents, the indication of the year of the reign of the Emperor must precede the serial number of the patent document. ⁴ Kind of document by the appropriate symbols as indicated on the document under WIPO Standard ST.16 if possible. ⁵ Applicant is to place a check mark here if English language translation is attached.	



**MODEL 4836
AIR SEEDER CART WITH
4800 AIR DRILL
FRONT FOLDING TOOLBAR**

OPERATOR'S MANUAL

DO NOT USE OR OPERATE THIS EQUIPMENT UNTIL THIS MANUAL
HAS BEEN READ AND THOROUGHLY UNDERSTOOD

PART NUMBER 80305341

JM-22-0000310



DELIVERY REPORT

Dealer & Customer Note: This check list must be executed in entirety at time of retail and returned by the dealer to Hiniker Company for warranty validation.

PRE DELIVERY SERVICE & INSPECTION

- ☐ Are the drill units correctly spaced for customer's row spacing?
- ☐ Are all hydraulic fittings, hoses and hydraulic cylinder connections tight?
- ☐ Is all captive air removed from hydraulic cylinders and hydraulic system?
- ☐ Has machine been checked for any loose hardware?
- ☐ Are all decals and S.M.V. sign clean and undamaged?

Dealer Name: _____

Dealer Address: _____ State _____ Zip _____

Phone (____) _____

Pre Delivery By: _____

DELIVERY TO CUSTOMER

- ☐ Show and explain each CAUTION, WARNING and DANGER machine decal.
- ☐ Insure customer understands safety hazards related to each decal.
- ☐ Explain to customer NOTICE and IMPORTANT machine instructions.
- ☐ Show customer frequent safety related copy throughout Operator's Manuals.
- ☐ Lead customer through full lubrication requirements.
- ☐ Show customer TROUBLE SHOOTING Section in Operator's Manual.
- ☐ Emphasize to customer the importance of COULTER and SEED placement. Show how to adjust the 4800 Air Drill for seed depth, seed shoe and seed rotary closer.
- ☐ Emphasize to customer need to read, and understand, Operator's Manual BEFORE STARTING MACHINE!
- ☐ Emphasize to customer the importance of knowing how to calibrate the seed metering equipment.
- ☐ Emphasize to customer the importance of safety in knowing how to hitch up to hitch and unhitch 4836 trailer.
- ☐ Explain to customer the Hiniker Company Warranty coverage.

The above items were reviewed with me at time of delivery.

Customer's Signature _____

Customer's Address _____ State _____ Zip _____

Phone (____) _____

- ☐ 1st Copy— Send to Hiniker Company



JM-22-0000311

Stamp

Hiniker Company
Attn: Warranty Dept.
Airport Road
P.O. Box 3407
Mankato, MN 56002-3407

Fold

Fold & Staple

JM-22-0000312



DELIVERY REPORT

Dealer & Customer Note: This check list must be executed in entirety at time of retail and returned by the dealer to Hiniker Company for warranty validation.

PRE DELIVERY SERVICE & INSPECTION

- ☐ Are the drill units correctly spaced for customer's row spacing?
- ☐ Are all hydraulic fittings, hoses and hydraulic cylinder connections tight?
- ☐ Is all captive air removed from hydraulic cylinders and hydraulic system?
- ☐ Has machine been checked for any loose hardware?
- ☐ Are all decals and S.M.V. sign clean and undamaged?

Dealer Name: _____

Dealer Address: _____ State _____ Zip _____

Phone (____) _____

Pre Delivery By: _____

DELIVERY TO CUSTOMER

- ☐ Show and explain each CAUTION, WARNING and DANGER machine decal.
- ☐ Insure customer understands safety hazards related to each decal.
- ☐ Explain to customer NOTICE and IMPORTANT machine instructions.
- ☐ Show customer frequent safety related copy throughout Operator's Manuals.
- ☐ Lead customer through full lubrication requirements.
- ☐ Show customer TROUBLE SHOOTING Section in Operator's Manual.
- ☐ Emphasize to customer need to read, and understand, Operator's Manual BEFORE STARTING MACHINE!
- ☐ Emphasize to customer the importance of COULTER and SEED placement. Show how to adjust the 4800 Air Drill for seed depth, seed shoe and seed rotary closer.
- ☐ Emphasize to customer the importance of knowing how to calibrate the seed metering equipment.
- ☐ Emphasize to customer the importance of safety in knowing how to hitch up to hitch and unhitch 4836 trailer.
- ☐ Explain to customer the Hiniker Company Warranty coverage.

The above items were reviewed with me at time of delivery.

Customer's Signature: _____

Customer's Address: _____ State _____ Zip _____

Phone (____) _____

- ☐ 2nd Copy - Retained by Dealer



JM-22-0000313



DELIVERY REPORT

Dealer & Customer Note: This check list must be executed in entirety at time of retail and returned by the dealer to Hiniker Company for warranty validation.

PRE DELIVERY SERVICE & INSPECTION

- ☐ Are the drill units correctly spaced for customer's row spacing?
- ☐ Are all hydraulic fittings, hoses and hydraulic cylinder connections tight?
- ☐ Is all captive air removed from hydraulic cylinders and hydraulic system?
- ☐ Has machine been checked for any loose hardware?
- ☐ Are all decals and S.M.V. sign clean and undamaged?

Dealer Name: _____

Dealer Address: _____ State _____ Zip _____

Phone (____) _____

Pre Delivery By: _____

DELIVERY TO CUSTOMER

- ☐ Show and explain each CAUTION, WARNING and DANGER machine decal.
- ☐ Insure customer understands safety hazards related to each decal.
- ☐ Explain to customer NOTICE and IMPORTANT machine instructions.
- ☐ Show customer frequent safety related copy throughout Operator's Manuals.
- ☐ Lead customer through full lubrication requirements.
- ☐ Show customer TROUBLE SHOOTING Section in Operator's Manual.
- ☐ Emphasize to customer need to read, and understand, Operator's Manual BEFORE STARTING MACHINE!
- ☐ Emphasize to customer the importance of COULTER and SEED placement. Show how to adjust the 4800 Air Drill for seed depth, seed shoe and seed rotary closer.
- ☐ Emphasize to customer the importance of knowing how to calibrate the seed metering equipment.
- ☐ Emphasize to customer the importance of safety in knowing how to hitch up to hitch and unhitch 4836 trailer.
- ☐ Explain to customer the Hiniker Company Warranty coverage.

The above items were reviewed with me at time of delivery.

Customer's Signature _____

Customer's Address _____ State _____ Zip _____

Phone (____) _____

- ☐ 3rd Copy - Retain by Customer



JM-22-0000314

TABLE OF CONTENTS

80305341

1/99

FN #1023,#E1060

INTRODUCTION	1
SAFETY	2 & 3
DECAL, SMV SIGN, WARNING LIGHT LOCATION	4 & 5
SPECIFICATIONS.....	6
LUBRICATION	7
PREPARING FOR FIELD USE	8 & 9
OPERATION PROCEDURES AND ADJUSTMENTS.....	10 - 13
Adjustment Photo	10
Down Pressure	11
Gauge Wheel.....	11
Rotary Closer Down Pressure	12
Rotary Closer Angle Adjustment.....	12
Seed Tube Adjustment	13
Seed Shoe Adjustment.....	13
TRANSPORTING.....	14 & 15
CALIBRATION	16 - 19
TOOLBAR HEIGHT ADJUSTMENT.....	20
ELECTRIC CLUTCH.....	21 & 22
AIR DELIVERY BLOWER.....	23 & 24
MAINTENANCE.....	25
TROUBLE SHOOTING.....	26 & 27
ASSEMBLY	28 - 41
Assembly Drawings	47 - 49
OPTIONAL EQUIPMENT	42
Ballast Weight.....	42
Weight Bracket	42 - 43
Air Blower Screen	43
Fill Auger	44 & 45
Markers	45
Hydraulic Plumbing Drawings	47
ASSEMBLY DIAGRAM	49 - 51
WARRANTY	52

JM-22-0000315

INTRODUCTION

Congratulations on your purchase of a new Hiniker 4836 Air Seeder Cart and 4800 Air Drill. Your selection is an indication of your awareness of the intense research, engineering, design and quality control that has produced your durable and dependable air drill from Hiniker.

This manual is provided as set-up and assembly instructions, and as an aid to the operator in explaining settings and adjustments for all soil, residue and functional applications of the Hiniker Air Drill and Air Seeder Cart. Also, its operational care and maintenance requirements. Careful application of the recommended procedures contained in this manual will assure you of many years of dependable, efficient operation.

Your Hiniker Air Drill has been designed to accept additional attachments to broaden its scope of operation and make your job easier under unusual or adverse field conditions. These attachments are described in the attachment section of this manual and are available through your local Hiniker Dealer.

"Right hand" and "left hand" sides of your air drill are determined by facing the direction that the 4836 Air Seeder Cart and 4800 Air Drill travels while in use.


Always obtain original Hiniker service parts because substitute parts could adversely affect equipment performance and warranty.

A triplicate (3 copies) delivery report is to be filled out by your Hiniker Dealer when you accept this equipment. One copy is to be given to you. Do not accept this equipment

until you are satisfied all items thereon have been checked, and you understand them.

Check that your dealer has forwarded the HINIKER delivery report copy, along with the machine serial number, because it helps maintain maximum service and warranty benefits. This does not put you on any mailing list and information is not available to others.

The serial number tag is located on the left side of the trailer, near the eyebolt holding the 5 x 8 cylinder.



DWG. NO. 3627

Record the following information for later reference when obtaining service parts:

Purchase Date _____

Purchaser's Name _____

Dealer's Name _____

Machine Serial No. _____

SAFETY

TAKE NOTE! THIS SAFETY ALERT SYMBOL FOUND THROUGHOUT THIS MANUAL IS USED TO CALL YOUR ATTENTION TO INSTRUCTIONS INVOLVING YOUR PERSONAL SAFETY AND THE SAFETY OF OTHERS. FAILURE TO FOLLOW THESE INSTRUCTIONS CAN RESULT IN INJURY OR DEATH.



THIS SYMBOL MEANS

- ATTENTION
- BECOME ALERT!
- YOUR SAFETY IS INVOLVED!

SIGNAL WORDS:

Note the use of the signal words **DANGER**, **WARNING** and **CAUTION** with the safety messages. The appropriate signal word for each has been selected using the following guidelines:

DANGER: Indicates an imminently hazardous situation that, if not avoided, will result in death or serious injury. This signal word is to be limited to the most extreme situations typically for machine components which, for functional purposes, cannot be guarded.



WARNING: YOUR SAFETY AND THE SAFETY OF THOSE AROUND YOU DEPEND UPON YOUR USING CARE AND GOOD JUDGEMENT IN THE OPERATION OF THIS EQUIPMENT. KNOW THE POSITIONS AND FUNCTIONS OF ALL CONTROLS BEFORE ATTEMPTING TO OPERATE.

WARNING: Indicates a potentially hazardous situation that, if not avoided, could result in death or serious injury, and includes hazards that are exposed when guards are removed. It may also be used to alert against unsafe practices.

CAUTION: Indicates a potentially hazardous situation that, if not avoided, may result in minor or moderate injury. It may also be used to alert against unsafe practices.

All equipment has limitations. Understand the speed, braking, steering, stability, and load characteristics of the machine before starting to operate. Read your OPERATOR'S MANUAL!




The following are safety requirements that apply to your 4800 Air Drill. Review them often as safety reminders.

- Check all controls and operating functions of the machine in a safe area before starting to work.
 - Keep off, keep others off, and insure every one is clear before starting, actuating hydraulics for lifting and lowering, and fold toolbar.
 - When service demands working on, under, or around, tillage implement, proper precautions should be taken to stabilize or secure implement. (Lowering stands, blocking of implement, etc.)
 - When transporting the machine, ensure all warning devices, such as SMV sign, flashing warning lights, and reflective devices are in place, clean, and clearly visible.
 - Watch where you are going. Note all hazards and obstructions such as ditches, overhead electrical wires, narrow gates, etc. when transporting and/or operating the machine. Refer to page 6 of this manual for transport width specifications.
- Never ride or permit others to ride on tractor drawbar or on machine; nor allow anyone other than yourself on the tractor while in operation.
- Never operate 4800 Air Drill without having safety chain properly in place between tractor and trailer.
 - Reduce tractor speed when transporting over uneven or rough terrain.

- When transporting down steep hills or slopes, shift tractor into lower gear.
- Never fold toolbar wings forward when others are standing on the trailer or catwalk.
- Escaping hydraulic fluid under pressure can have sufficient force to penetrate the skin causing serious personal injury. Before connecting lines, be sure to relieve all pressures in the system by moving hydraulic control levers in both directions before attaching couplers.
- Before disconnecting lines, be sure to relieve all pressures to the system.
- Be sure all connections are tight and that lines, pipes, and hoses are not damaged or worn.
- A very small leak from a hydraulic line, pipe, hose, or fitting can be almost invisible. Use a piece of cardboard or wood when checking for suspected leaks rather than your hands.
- If injury is received from escaping fluid, see a doctor at once, as serious reaction or infection can result if proper medical treatment is not received immediately.
- Never operate wing fold cylinders on folding toolbar models without (4) restrictor fittings, one at each end of lift cylinder.

4 Decal Location



DWG. NO. 3650


JM-22-0000319

1. SAFETY DECAL



Decal (1) 85501787, on top of left hand tongue tubing near front end.

2.



Decal (1) 85501783, on side of left hand tongue tubing near front jack mount.

3.



Decal (2) 80302332, on the low front of tank, one on each end.

4.



Decal (2) 850-001-305 Red Reflective Tapes, on the outer rear tank leg, one on each end.

5. MODEL DECAL



Decal (2) 80305266, on the side of tank, one on each end.


REMEMBER: If Safety Decals, SMV Sign or Warning Lights have been damaged, removed, become illegible or parts replaced without decals, new decals or lights must be installed. New decals, SMV Sign or Warning Lights are available from your authorized dealer or Hiniker Company.

6.




Decal (3) 71505168 on the rear, on each end of tank.

7. SMV SIGN




(1) Sign 850-001-354, on rear of tank.

8. WARNING LIGHTS



(1) Right Hand 36100001, on L.H. inner toolbar

9.



(1) Left Hand 36100000, on L.H. inner toolbar

SPECIFICATIONS

STANDARD EQUIPMENT

4836 TANK/TRAILER and 4800 AIR DRILL

- 7 x 7 Inch Single Center Frame Toolbar.
- 7 x 7 Inch Toolbar Wings with End Plates and Block Removing Rod.
- Safety Lights and Wiring.
- Hitch Mounting Brackets.
- One Pair Of Toolbar Wing Rests.
- Infinite Speed Roll Meter with Soybean Rates From 30 To 175 Lbs. Per Acre.
- Two Wheel Trailer Cart, with Three Point Hitch.
- Two 19L x 16.1 Tires/Rims On Trailer Cart.
- Wheel Spacing At 74 Inch Center.
- Hopper Capacity 130 Bushels.
- 13 GPM Hydraulic Motor On Air Delivery Blower.
- Hydraulic Hoses To Tractor From Hydraulic Motor.
- Air Pressure Gauge On Air Delivery Manifold.
- Safety Chain

TILLAGE UNIT

- 16 Inch Disc Opener with 3 X 16 Rubber Gauge Wheel and Mounted Individual Row Unit.
- Parallel Linkage with 8" Total Travel.
- Seed Tube with Cast Chrome Seed Opening Boot and Seed Shoe Block.
- 12 Inch Angled Metal Rotary Seed Closing Disc Mounted On Spring Loaded Arm That Adjusts For Angle and Down Pressure.
- Weight Transfer Systems with Variable Adjustment Up To 500 Lbs/Row.

TRACTOR REQUIRED EQUIPMENT

- Closed Center Hydraulic System Providing At Least 13 GPM.
- 12 Volt D.C. Electrical System.

MODEL NO.	NO. OF ROWS	ROW SPACING	TRANSPORT WIDTH W/O MARKERS	TRANSPORT HEIGHT W/O MARKERS	APPROX. WEIGHT LBS.	OPTIONAL CONCRETE BLOCK WEIGHT LBS.
4831	24	15	15'10"	8'11"	11,025	495
4832	36	10	15'10"	8'11"	12,705	495
4833	32	15	15'10"	8'11"	12,605	855

JM-22-0000321

LUBRICATION

4800 TOOLBAR



CAUTION: *Never clean, lubricate, inspect, repair, or adjust your machine, nor allow anyone else to, while it is in operation.*

Lubrication of moving parts and wear surfaces is essential to the extended service life of those parts. Inspect your machine frequently to ensure that all parts are working smoothly in addition to inspection and lubrication at required intervals as indicated.




PHOTO NO. 3935




PHOTO NO. 3936

The use of sealed ball bearings and oil impregnated bushings throughout the drill limits the grease fittings requiring periodic lubrication. Following are the fitting locations and hourly intervals requiring a high quality SAE multi-purpose grease.

200 HOURS

- FOLDING TOOLBAR HINGE - No restriction of grease volume in single hinge fitting.
- OUTER TOOLBAR WING LIFT - No restriction of grease volume in single hinge fitting.

Variable speed box (arrow 1). The ZERO-MAX drive runs in oil and is filled at the factory with **Chevron Delo 100 Motor Oil SAE 40**. If ZERO-MAX No. 400 lubricant (Chevron Delo 100) is not available from your ZERO-MAX distributor or service station, use **Mobil-Delvac 1140**. In an emergency, use a good grade of SAE 40 detergent motor oil.

The proper quantity of lubricant when refilling the Zero-Max drive is 95 ounces (2.812 liters).

Lubricate all roller chains periodically with a high quality chain lubricant (arrow 2, five chain assemblies).




PHOTO NO. 3937

JM-22-0000322

PREPARING FOR FIELD USE

PREPARING 4836 TANK/TRAILER AND 4800 AIR DRILL

Prior to the operation of your new drill or one which has been stored, inspect all hardware and verify proper torque on all bolts and nuts in accordance with the recommended torque specifications listed below.

STANDARD MARKINGS AND TORQUE SPECIFICATIONS				
Manufacturer marks may vary. These are all SAE Grade 5 (3-line). 				
SAE Grade Number	1 or 2	5	8	
Capscrew Head Markings				
Capscrew Body Size (Inches) - (Thread)	Torque FT-LB (kgm)	Torque FT-LB (kgm)	Torque FT-LB (kgm)	
1/4 - 20	5 (0.6815)	8 (1.1064)	12 (1.6596)	
- 28	6 (0.2898)	10 (1.3830)	14 (1.9362)	
5/16 - 18	11 (1.5213)	17 (2.3511)	24 (3.3192)	
- 24	13 (1.7979)	19 (2.6277)	27 (3.7341)	
3/8 - 16	18 (2.4894)	31 (4.2873)	44 (6.0852)	
- 24	20 (2.7660)	35 (4.8405)	49 (6.7767)	
7/16 - 14	28 (3.8132)	49 (6.7767)	70 (9.6810)	
- 20	30 (4.1490)	55 (7.6065)	78 (10.7874)	
1/2 - 13	39 (5.3937)	75 (10.3725)	105 (14.5215)	
- 20	41 (5.6703)	85 (11.7555)	120 (16.5960)	
9/16 - 12	51 (7.0533)	110 (15.2130)	155 (21.4365)	
- 18	55 (7.6065)	120 (16.5960)	170 (23.5110)	
5/8 - 11	83 (11.4789)	150 (20.7450)	210 (29.0430)	
- 18	95 (13.1385)	170 (23.5110)	240 (33.1920)	
3/4 - 10	105 (14.5215)	270 (37.3410)	375 (51.8625)	
- 16	115 (15.9045)	295 (40.7985)	420 (58.0860)	
7/8 - 9	160 (22.1280)	395 (54.6285)	605 (83.6715)	
- 14	175 (24.2025)	435 (60.1605)	675 (93.3525)	
1 - 8	235 (32.5005)	590 (81.5970)	910 (125.8530)	
- 14	250 (34.5750)	660 (91.2780)	990 (136.9170)	

DWG. NO. 1935



CAUTION: Loose bolts can cause elongation of holes and part failures resulting in dangerous operating conditions and equipment breakdown. Check all bolts and nuts periodically during equipment operation and keep them tightened to torques specified. When bolt replacement becomes necessary, replace worn bolt with equal SAE grade bolt number.

TRACTOR REQUIREMENTS

Tractor horsepower requirements are moderate, but soil types, soil conditions, and field terrain such as rolling or hilly conditions may affect the amount of horsepower required. The approximate horsepower required for the following drills are:

MINIMUM TRACTOR REQUIREMENTS	
4831	180 HP
4832	180 HP
4833	200 HP

If the recommended tractor size is being used and the front of the tractor seems light, or difficulty is encountered when turning, weight will have to be added to the front of the tractor. The importance of this weight will probably be more noticeable when planting in rolling or hilly areas.

Usual methods of adding weight to the front of the tractor will include supplemental tractor weight, accessory rock boxes, and front or saddle tanks which may be used for liquid fertilizer or herbicide.

In hilly areas this is especially important because when the front of the tractor raises, the rear of the drill penetrates deeper resulting in seed being placed too deep to emerge.

NOTE: For complete tractor operating instructions refer to your tractor operators manual.



CAUTION: Front end ballast may not always maintain the required stability if the tractor is driven too fast over rough ground with the planter in raised position. Be safe and drive slowly under these conditions.

JM-22-0000323

TRACTOR AND HITCH PREPARATION

For complete tractor operating instructions and use of 3-point hitch implements, refer to your tractor operator's manual.

Place tractor on level surface and check tire inflation to ensure equal tire pressure. Lower draft arms to their lowest position and adjust lift links so that both draft arms are the same distance off the ground as measured from the draft arm sockets.

Reference tractor operator's manual for proper adjustment of draft arms and center link. If a quick hitch coupler is to be used, install it to the 3-point hitch at this time in accordance with the tractor operator's manual.




PHOTO NO. 3938

Attach 4836 trailer/tank to tractor, and adjust front hitch to have level frame. With tractor attached to trailer, place two (2 x 4's) down on the ground in front of each of the trailer tires and drive forward, raising trailer 1 1/2 inches.




PHOTO NO. 3939

Attach trailer lower lift arms (arrow 1) to lower hitch on 4800 air drill toolbars. *Note: Position of lower hitch latch (arrow 2). This will allow hitch pin (arrow 3) to float up and down in lower lift arm hook.*




PHOTO NO. 3940

Install upper hitch arm (arrow 1) as shown in upper hole on toolbar hitch. Adjust length to have 7 x 7 toolbar running level in the planting position, with bottom of toolbar approximately 21 inches off the ground.

TIRE INFLATION

While it is always important to have tires inflated to the correct pressure as specified in the tractor operator's manual, the additional weight of the 4836 Seeder Attachment makes this check essential to avoid premature tire failure.



CAUTION: After attaching 4800 Air Drill to tractor, check front end stability. Tractor front end stability is necessary for safe and efficient operation. Therefore, it is important that the proper amount of weight be installed on the front of the tractor, as recommended in your tractor's operator's manual.

TOWING

When towing 4836 Seeder on highways:

- Use safety towing chain between the trail hitch and the towing tractor. (Safety towing chains are marketed by HINIKER.)
- Use a tractor of sufficient size and weight, required for field operation.
- Do not tow faster than 25 MPH (40 KPH).
- Check local regulation on towing width and warning lights.

JM-22-0000324

OPERATION PROCEDURES AND ADJUSTMENTS

ADJUSTMENT PHOTO




PHOTO. NO. 3603

NOTE: REFERENCE ADJUSTMENT PHOTO FOR ALL OPERATION PROCEDURES AND ADJUSTMENTS.

JM-22-0000325

DOWN PRESSURE




PHOTO NO. 3604

Always operate with parallel links (Arrow 1 & 2) level or near level. Have tractor carry toolbar 20 inches off ground, and adjust toolbar gauge wheel to that same dimension.

Down pressure requirements will vary depending on no till or tilled condition, soil type condition and soil moisture. Two spring anchors (Arrow 3 & 4) are provided for these different conditions.

NO-TILL CONDITION HEAVY DOWN PRESSURE




PHOTO NO. 3605

Install down pressure spring with large 1 inch hook opening at bottom, over front 7/8 diameter (Arrow 1). Upper 3/4 pin (Arrow 2) will install best in front hole with parallel link in down position, as shown in photo. With parallel links level, the down pressure will vary from 165 lbs at front (Arrow 2) to 500 lbs at rear (Arrow 3).

TILLED CONDITION LIGHT DOWN PRESSURE




PHOTO NO. 3606

Install down pressure spring with 1 inch hook opening at bottom over rear 7/8 diameter (Arrow 1). Upper 3/4 pin (Arrow 2) will install best in the third hole with parallel link in down position as shown in photo. With parallel links level, the down pressure will vary from 90 lbs at front (arrow 3) to 220 lbs at rear (Arrow 4).

GAUGE WHEEL




PHOTO NO. 3604A

Adjust gauge wheel by removing lock pin (Arrow 1), then raise or lower vertical flat bar (Arrow 2) and repin at the desired seed depth wanted.

ROTARY CLOSER DOWN PRESSURE




PHOTO NO. 3607

To increase down pressure on rotary closer, move front anchor up on mast weld (Arrow 1) and move rear anchor ahead on support arm (Arrow 2). See adjusting tip below.

To decrease down pressure on rotary closer, move front anchor down on the mast weld (Arrow 3) and move rear anchor rearward on support arm (Arrow 4).

ADJUSTING ASSEMBLY TIP




PHOTO NO. 3608

When increasing down pressure and moving rear anchor ahead, lift up support arm (Arrow 1) and use vise grip to secure the end of front strap (Arrow 2). Move rear anchor (Arrow 3) ahead.

ROTARY CLOSER ANGLE ADJUSTMENT




PHOTO NO. 3609

The rotary closer support (Arrow 1) has three angle settings, to increase or decrease the amount of loose soil thrown. Different soil types, the amount of residue, no-till or tilled condition and ground speed will vary the rotary closure angle. Always install the three 5/16 hex cap screws coming up from the bottom. Hold rotary closer support in one hand and turn 5/16 whiz nut (Arrow 2) with the other.

NOTE: The rotary closer only moves loose soil.

SEED TUBE ADJUSTMENT




PHOTO NO. 3610

To raise or lower seed tube boot outlet (Arrow 1) loosen 3/4 hex cap screw (Arrow 2) and 3/8 hex cap screw (Arrow 3). Move to desired height and retighten both 3/4 hex cap screw and 3/8 hex cap screw to hold seed tube boot in place.

When properly adjusted, bottom edge of seed boot should be 1/4" or less above bottom edge of disc.

NOTE: As disc blade wears in size and becomes smaller, always recheck position of seed tube boot to coulter blade. Do not allow it to run too deep. In some cases the disc blade must be replaced, when it is smaller than 14 1/2 inches in diameter.

SEED SHOE ADJUSTMENT




PHOTO NO. 3610A

The seed shoe (Arrow 1) has two adjustments, height and tension. To change height loosen 3/4 hex cap screw (Arrow 2) and 3/8 hex cap screw (Arrow 3). Move to desired height and retighten cap screws. To change seed shoe tension, loosen 5/16 hex cap screw (Arrow 4). Pull adjusting bar (Arrow 5) rearward to increase tension and push forward to decrease tension.

NOTE: In wetter soils the seed shoe should be in light tension setting.

TRANSPORTING




PHOTO NO. 3941

When traveling long distances with hopper full of seed, all slide straps (arrow 1) may be lowered into closed position.

When folding the toolbar in the transport position, the outer toolbar wings sit on rests.




PHOTO NO. 3942

The 30 ft. toolbar wing rests (arrow 1) are bolted to the front posts of the 130 Bu. tank (arrow 2).



PHOTO NO. 3943




PHOTO NO. 3944

The 40 ft. toolbar wing rests (arrow 1) are bolted onto a cross tube (arrow 2) placed in front of the catwalk (arrow 3). The cross tube is bolted to the trailer.




PHOTO NO. 3945




PHOTO NO. 3936A

A guide (arrow 1) is bolted to both the left and right outer toolbar wings. The guide is used to determine the distance the outer wings must fold before the wheel lifts (arrow 2) can be raised.

NOTE: Both the left and right outer wing guides must be touching the vertical end of the wing rest (arrow 3) before raising the wheel lift. Check both sides are up to back stop before raising wheel lift arms and locking for transport.



IMPORTANT: When toolbar lowers onto toolbar rest, it will move rearward 2 to 3 inches. Failure to take precaution may result in bodily injury or equipment damage.

PLASTIC SHIELD




PHOTO NO. 3947

To protect the seed metering device from debris when in the field and transporting, the plastic shield (arrow 1) can be rolled down using the crank (arrow 2) on the left side of the tank.




PHOTO NO. 3948

If access to the seed metering device is needed, the shield can be rolled up. The shield is locked into the rolled up position by the crank (arrow 1) snapping into the flat spring (arrow 2). The flat spring is found above the crank on the left side of the tank.

The crank can be moved to the right side of the tank if needed. Remove the 1/4" bolt, hex nut, and lockwasher holding the crank into the roll up pipe. Remove the crank and move it to the right side of tank and install in right side of roll up pipe as previously done on the left side. Remove the flat spring by removing the 1/4" self tapping screw. Transfer the flat spring to the right side of the tank using the hole provided on the tank and the 1/4" self tapping screw.

CALIBRATION

The following variables affect the rates as shown on the rate charts:

1. Quality of Seed - Two bags of seed that weigh the same may have different quantities of seed because of moisture content trash, unfilled kernels, or seed size.
2. Wheel Slippage - It can vary depending on drive tire size, seed bed condition, and soil type. Speed also affects wheel slippage.
3. Drive Tire - Size, type, and air pressure affect seeding rates. Use the recommended tire size and proper air pressure.
4. Operator Judgement - Land may contain more or less area than assumed. Overlapping rows or leaving too wide a space between rows will affect overall rate.




PHOTO. NO. 3949

Remove first mixing chamber (arrow 1). Raise first slide strap (arrow 2), and hang bucket on self tapping screws (arrow 3). Shut off remaining outlets with slide straps (arrow 4).

NOTE: Weight your bucket before starting to calibrate.

See seed chart page 19 and select the amount of seed (pounds per acre). **NOTE:** The amounts shown are approximate per acre.

Seed calibrating can be done by an in-shop test using calibrating sprocket provided on hopper. Follow step 1 and step 2.

STEP 1 (IN SHOP)




PHOTO. NO. 3937C

Disengage both electric clutches (arrow 1) on the left and right side of the tank.

STEP 2 (IN SHOP)




PHOTO. NO. 3952

Disengage handle (arrow 1) from the 32 teeth sprocket (arrow 2) by pulling handle and placing end of handle onto the sprocket hub (arrow 3) of the 32 teeth sprocket.




PHOTO NO. 3937A

By engaging the electric clutches and the handle from the 32 teeth sprocket, the calibration sprocket (arrow 1) can turn freely.

STEP 3 (IN SHOP)




PHOTO NO. 3937B

Select the amount of seed, pounds per acre, from seed chart and the number to be used on variable speed box (arrow 1). With bucket in place, turn 1 1/8" hex (arrow 2) counter clockwise. (See chart below for number of revolutions), then get a total weight of bucket/soybeans. Now subtract weight of bucket. This amount $\times$ 300 (1/300 acre) = total pounds per acre.

Example: #3.2 on variable speed box, weight of soybeans in bucket (15 inch row) = .4 lbs.

$$.4 \times 300 = 120 \text{ lb per acre.}$$

REVOLUTIONS OF CALIBRATION SPROCKET		
ROW SPACING	NUMBER OF REV	DISTANCE TRAVELED
15 INCH	32 1/2	116 FT.
10 INCH	48 1/2	174 FT.

REFERENCE INFORMATION

1 acre = 43,560 Sq. Ft. 43,560 divided by 300 = 145 Sq. Ft.

(15 Inch Row) One Outlet = 15" = 1.25'

145 Sq.Ft. divided by 1.25' = 116 Ft.

(10 Inch Row) One Outlet = 10" = .8333'

145 Sq.Ft. divided by .8333 = 174 Ft.

18 Calibration

REMOVING AND CHANGING SEED METERING WHEELS




PHOTO. NO. 3949B

The seed chart on page 19 indicates different seed metering wheels for various types of seed. These wheels are color coded for easy identification.

To remove and change seed metering wheels, first lower the seed slide gates (arrow 1) to a closed position. Remove the wing nuts (arrow 2 and 3) and their bolts. Next remove the sprocket roller chain (arrow 4). Now the entire metering wheel assembly can be removed and placed on a bench.




PHOTO NO. 3941A

Remove the metering shaft bearing bolts (arrow 1). The metering wheels and shaft assembly will now lift out of the seed venturis. To remove the seed metering wheels, slide the bearing and metering wheels off the shaft.

Reverse this procedure for the installation of the new metering wheels.

JM-22-0000333

SEED CHARTS AND CALIBRATION


The following population charts are approximate for each gear box setting. Soybean rates are based on 2650 seeds per pound. There are many variables which will affect the actual seeding rate. These include seed size and weight. Always calibrate 4800 seeder before starting to seed or when changing varieties. As population rates increase, planting speed may have to be reduced so capacity of the seed hose is not exceeded. Be sure to factor in the germination percent of your seed when determining final seed population.

Calibration of the 4800 Seeder is both quick and simple. After selecting the desired rate on the appropriate chart, calibrate to check the actual rate. If the actual rate is high or low, reset and calibrate again.

GEARBOX SETTING	15 Inch Rows					10 Inch Rows				
	Soybeans	Wheat	Wheat	Oats	Oats	Soybeans	Wheat	Wheat	Oats	Oats
	White Meter Wheel	Red Meter Wheel	Black Meter Wheel	Black Meter Wheel	Red Meter Wheel	White Meter Wheel	Red Meter Wheel	Black Meter Wheel	Black Meter Wheel	Red Meter Wheel
	lbs/acre					lbs/acre				
1.0	29	29	18	7	17	43	43	27	10	25
1.2	35	35	22	8	20	52	52	33	12	30
1.4	43	43	27	10	24	64	64	40	15	36
1.6	50	50	32	12	29	75	75	48	18	43
1.8	58	58	37	13	32	87	87	55	19	48
2.0	66	66	42	15	37	99	99	63	22	55
2.2	74	74	47	17	41	111	111	70	25	61
2.4	82	82	52	19	46	123	123	78	28	69
2.6	90	90	57	21	51	135	135	85	31	76
2.8	100	100	63	23	56	150	150	94	34	84
3.0	108	108	68	25	61	162	162	102	37	91
3.2	120	120	76	28	67	180	180	114	42	100
3.4	129	129	82	30	73	193	193	123	45	109
3.6	144	144	91	33	78	216	216	136	49	117
3.8	148	148	94	34	83	222	222	141	51	124
4.0	164	164	104	38	92	246	246	156	57	138
4.2	172	172	109	40	98	258	258	163	60	147
4.4	190	190	120	44	107	285	285	180	66	160
4.6	203	203	128	47	114	304	304	192	70	171
4.8	217	217	137	50	122	325	325	205	75	183
5.0	234	234	148	54	131	351	351	222	81	196

JM-22-0000334

TOOLBAR HEIGHT ADJUSTMENT



DWG. NO. 3416




PHOTO NO. 3958




PHOTO NO. 3957

Toolbar height can be adjusted using three eye bolts. The center eye bolt (arrow 1) is attached to the center cylinder found on the trailer. The other two eye bolts (arrow 2) can be found on the outer toolbar wing lift.

A starting height when adjusting the toolbar is 19". The toolbar height may need to be adjusted depending upon field conditions.

NOTE: It is important to keep the adjusting nut on the center eye bolt, in the center of the thread adjustment on eye bolts. This will assure proper toolbar height when transporting.

ELECTRIC CLUTCH




PHOTO. NO. 3937C

The seed metering mechanism is turned on and off by an electric clutch (arrow 1).
The electric clutch operating parameters are as follows:


VOLTAGE - 12V D.C.
CURRENT DRAW - 4.84 AMPS
RESISTANCE +/- 5% 2.48 OHM

When servicing worn clutch components, the rotor and armature must be replaced as a pair. If service is required for new components, they may be replaced individually.

22 Electric Clutch

CONSOLE INSTALLATION

Select an easily accessible area to mount the console in the tractor cab. Mount the bracket to the cab using the 1/4-20 bolts and nuts. Mount the console to the bracket using the #8-32 bolts and nuts.



DWG. NO. 3638


Attaching the lead with the circuit breaker to the positive battery terminal and the remaining lead to the negative terminal.

Route the 10 foot clutch cable from the clutch switch box to the hitch area of the tractor. Connect the 20 foot clutch cable to the 10 foot cable and route along the left tongue to the Seeder bin support. Connect the clutch "y" cable to the 20 foot cable and route to the clutches. The 2 pin connector with the Green and Black wires connects to the clutch on the right side and the 2 pin connector with the Red and Black wires connects to the clutch on the left side. Secure all wiring to the top of frame members to prevent possible damage by pinching or chafing.

NOTE: Allow room at the hitch for proper turning.

CLUTCH OPERATION

The Clutch Control Box has three switches. The two left most switches, labeled Left and Right, will determine which clutches will operate when the Clutch Control Switch is activated. The Clutch Control Switch, located on the right, is the master clutch control. This allows the ability to turn on either or both clutches with one switch.




DWG. NO. 3639

Once the electric clutch is turned on, and the electric clutches engage activating the seed metering mechanism, a time delay will occur before the metered seed reaches the disc opener unit.

NOTE: Because the 4800 seeder has a ground wheel drive arrangement, the seeder must be in motion before the seed can be metered and delivered to the ground engaging seed boots.

Because of the previously mentioned start up time delay, "skips" could occur when stopping and starting the 4800 seeder in the field. To prevent these "skips" or unseeded areas, it may be necessary on headlands to turn seeder switch on approximately 10 feet before entering seeding point.

NOTE: Lower seed rates will require a greater distance. To determine correct distance for your seed rate, place a start flag and travel forward. Watch for seed coming out of seed boots, stop and measure that distance.



DWG. NO. 3640

JM-22-0000337

AIR DELIVERY BLOWER

The Hiniker 4800 seeder air delivery blower is designed to be operated with closed center tractor hydraulic systems (tractors with load sensing or pressure-on-demand hydraulics are classified as closed center systems). Open center tractor hydraulics are NOT compatible with system.

Minimum tractor standby pressure required to operate the air delivery blower hydraulic system is approximately 2000 psi at 13 gallons per minute (GPM) depending on frame configuration, planting speed and the number of rows on planter. Some tractors have specific selective control valves for operating hydraulic orbit motors. For complete tractor operating instructions, refer to your tractor operators manual.

To operate the 4800 seeder air delivery blower, first connect the blower hydraulic hoses to the tractor couplers.

Start the tractor engine and bring it up to operating speed.

To engage fan motor, move hydraulic motor selector valve control lever from "float" to a "detent" position.





PHOTO. NO. 3098

Use tractor flow control lever "A" and slowly increase rate of flow to bring air pressure indicated on planter seed hopper air gauge (photo 3184) to recommended operational air pressure.



Air Pressure Gauge

PHOTO. NO. 3184

When operating at the desired engine and planting ground speed, the air pressure gauge should read from 16 to 20 ounces per square inch for soybeans, 8 to 12 for wheat.

If desired air pressure cannot be obtained check the following:

- Check to see if the tractor coupler flow control is fully open.
- Check to see if the hydraulic blower hoses are properly installed and in the correct tractor couplers.
- Ensure tractor engine speed is properly set.
- Check tractor hydraulic standby pressure and flow to be at 2000 psi and a minimum of 13 gpm.


24 Air Delivery Blower

- Ensure that tractor has a closed center hydraulic system.
- Check for restrictions in air pressure gauge hose.
- Check to see that hydraulic selector lever is displaced in the proper direction and in a "detent" position.

The hydraulic blower motor is designed to run at a maximum of 4500 rpm.

 **WARNING: DO NOT REMOVE BLOWER INLET SCREEN TO CHECK BLOWER RPM (REVOLUTIONS PER MINUTE). BLOWER RPM SHOULD BE CHECKED, IF NECESSARY, WITH A STROBE STYLE TACHOMETER WITH THE BLOWER INLET SCREEN IN PLACE.**

With the air pressure gauge reading the recommended operation air pressure, the blower should be running within its rpm limits.



BLOWER ROTATION

DWG. NO. 3438

The air delivery blower hydraulic motor is of a bi-rotational design meaning it will run in either direction. See drawing 3438 for correct blower rotation.



IMPORTANT: THE BLOWER MUST BE RUNNING AND MAINTAINING MINIMUM SPECIFIED AIR PRESSURE WITH THE DRIVE CLUTCH ENGAGED AND THE MACHINE IN MOTION.



PHOTO. NO. 3960

The blower is provided with a "coasting" feature which allows the blower to free wheel or continue to rotate and coast to a stop once the hydraulic selector lever on the tractor is moved to an "off" or "float" position. A cross over check valve (item 1) in the blower plumbing permits the blower motor to "coast". If the blower motor and blower fan do not free wheel after being turned off, there may be a problem with the check valve (item 1). The inability to "coast" can cause undue stress on the hydraulic orbit motor and its plumbing. If the check valve is removed for cleaning etc. or replaced it must be reinstalled with the "free flow" arrow facing the direction as indicated in photo above.



WARNING: EXCESSIVE AMOUNTS OF DUST OR DIRT TAKEN IN BY THE SEEDER BLOWER COULD CAUSE WEAR TO THE BLOWER IMPELLER. THIS WEAR COULD WEAKEN THE IMPELLER AND POSSIBLY CAUSE IT TO FAIL OR COME APART WHILE RUNNING. FREQUENT INSPECTION OF THE BLOWER IMPELLER, WHICH CAN BE VIEWED THROUGH THE INLET SCREEN, COULD PREVENT THIS FAILURE AND POSSIBLE INJURY.



WARNING: DO NOT INSERT OBJECTS INTO BLOWER INLET SCREEN OR WORK ON THE BLOWER WHILE THE BLOWER IS RUNNING. SERIOUS PERSONAL INJURY COULD RESULT.



WARNING: DO NOT REMOVE SEED DELIVERY TUBES FROM THE SEEDING UNITS WHILE THE AIR DELIVERY BLOWER IS RUNNING. "PROJECTILES" EXITING THE TUBES UNDER AIR PRESSURE COULD STRIKE AN INDIVIDUAL, POSSIBLY CAUSING SERIOUS INJURY.

JM-22-0000339

MAINTENANCE

When unit is received, inspect immediately for damaged or missing parts. Even though all units are carefully inspected and prepared for shipment at the factory, handling enroute may cause concealed damage or cause nuts, bolts, or locking collars to work loose. If concealed damage is found, call your dealer and report your findings.

BEFORE START UP

1. Inspect all fasteners to make sure they are secure.
 - a. Hopper and trailer bolts.
 - b. Set screws in fan, housing and motor mounting bolts.
2. Be sure to follow the directions for connection of hydraulic hoses using like-brand connectors as on tractor and in regulating fluid flow for closed center tractors. Failure to do so may result in damage to your hydraulic system.

BLOWER HOUSING AND METAL PARTS

3. The blower housing and impeller are maintenance free and should not require any maintenance during the life of the unit. After operation in dusty conditions, the air intake screen should be removed and the impeller blades cleaned to prevent an accumulation of foreign matter that could interfere with operation of the fan. Inspect periodically to check for possible excessive wear or cracks and check the alignment of the impeller with housing.

MANIFOLD

4. Be sure to clear manifold of collected dust or debris by daily removing expansion plugs in manifold. Failure to do so can cause accumulation which interferes with air passage and delivery material through pneumatic tubes.

DRIVES AND CLUTCHES




PHOTO. NO. 3937D

Check that roller chain assemblies are properly aligned and roller chain idler are properly adjusted to ensure proper running seed metering. Check for properly aligned seed metering shaft and smooth running.

LUBRICATION

Oil roller chain daily and check oil level in variable speed box as indicated on lubrication page 7.

TROUBLE SHOOTING NO-TILL CONDITIONS


TROUBLE	CAUSE	REMEDY
Residue pushing ahead of disc opener.	Disc not turning.	Gauge wheel set too shallow. Adjust by lifting gauge wheel.
	Residue caught between disc opener and gang.	Raise machine and clean out residue until disc turns freely.
	Disc opener worn too small.	Replace disc.
	Disc opener not turning.	Raise front or lower rear of machine until level.
Residue pushing ahead of gauge wheel.	Gauge wheel not turning.	Disc not penetrating. Increase down pressure or add ballast to toolbar.
	Residue caught between gauge wheel and gang.	Raise machine and clean out residue until gauge wheel turns freely.
Disc opener not cutting residue.	Disc opener pushing	Apply more down pressure on gang and/or add ballast to toolbar.
	Disc opener worn and/or not sharp.	Gauge wheel set too shallow. Adjust by lifting gauge wheel. Replace disc opener.
Seed not covered.	Rotary closer not in proper adjustment.	Adjust an angle of rotary closer.
	Not enough down pressure on rotary closer.	Increase down pressure on rotary closer arm.
	Driving too slow.	Must drive minimum 4-5 MPH.
	Field conditions too wet. Soil sticking to disc opener.	Wait for soil to dry.
	Disc opener not penetrating.	Apply more down pressure and/or add ballast to toolbar.
Disc opener slabbing.	Disc opener too deep.	Lower gauge wheel.
	Soil too wet.	Let field dry.

JM-22-0000341

TROUBLE SHOOTING TILL CONDITIONS

TROUBLE	CAUSE	REMEDY
Residue pushing ahead of gauge wheel.	Gauge wheel not turning. Too much down pressure on gang.	Carry toolbar with tractor. Decrease down pressure on gang. You may have to move position of down pressure spring to negative pressure position.
Residue pushing ahead of disc opener.	Disc opener not turning.	Carry toolbar at 20" off ground. Parallel linkage will be level. Too much down pressure. Decrease down pressure on gang.
Disc opener slabbing.	Disc opener too deep. Field conditions too wet.	Lower gauge wheel. Let field dry.
Seed not covered.	Rotary closer not in proper position Driving too slow. Disc opener and seed tube set too shallow.	Adjust angle of rotary closer. Must drive minimum 4-5 MPH. Raise gauge wheel.
SEED BOUNCING OUT - OF SEED FURROW	AIR PRESSURE too high -	REDUCE AMOUNT OF HYDRAULIC OIL FLOW TO BLOWER FAN. ONLY USE ENOUGH AIR PRESSURE TO DELIVER SEED TO FURROW.

ASSEMBLY



STEP 1

Place center toolbar on stands, holding it 19 inches off floor. Attach 3-point hitch members from 4836 tank/trailer assembly to center toolbar hitch plate using hitch pin provided. (arrow 1 and 2).


STEP 2

Place both inner wings inline with center toolbar as shown in drawing.

STEP 3

Extend wing fold cylinder and attach to inner wing toolbar (arrow 3) using pin provided.

JM-22-0000343



DWG. NO. 3626


STEP 4

Install both outer wings using pivot pin (arrow 1). *NOTE: Drag link anchor (arrow 2) must be installed to front as shown in drawing.*

STEP 5

Install left and right wing wheel lift. *NOTE: The roller lock (arrow 3) must be installed on inside.* Install 3/4" u-bolt (arrow 4). Use the Assembly Diagrams for proper placement of Wheel Lift & Toolbar Guide for your model size and row spacing. (Refer to page 49 to 51).


JM-22-0000344



DWG. NO. 3624

STEP 6

Check for proper toolbar alignment between center frame and both inner wings. Adjust number of shim (arrow 1) as required.



DWG. NO. 3623


Step 7

Adjust for the number of shim (arrow 1) between inner wings and outer wing. Note: Use

(4) shims for 15 inch rows and use (7) shims for 10 inch row spacing.

JM-22-0000345

STEP 8




Right Hand Shown

PHOTO NO. 3962

Install front drag link using 1 inch hex bolt provided mounting on top of trailer. Pull strap as shown. *NOTE: At this time do not adjust length of eye bolt in drag link.*

STEP 9




Right Hand Shown

PHOTO NO. 3963

When installing drag link assembly the middle pivot and lock must be installed as shown, with Belleville washer on bottom and lock on top.

STEP 10




Right Hand Shown

PHOTO NO. 3964

Install rear drag link to toolbar outer wing anchor strap as shown. *NOTE: Position of drag link under anchor strap and Belleville washer under drag link.*


STEP 11



DWG. NO. 3622

When installing Belleville washer (arrow 1), *NOTE: Position of washers to have the beveled sides together as shown in enlarged view.* Also, tighten bolt down on spacer (arrow 2). At that point, the Belleville washer will be at proper tension.

STEP 12A




30 Ft. Toolbar
Right Hand Shown

PHOTO NO. 3942A

Reinstall right and left hand wing rest (arrow 1) mounted to the front tank posts using existing 5/8 u-bolts, lockwashers and hex nuts.

STEP 12B



40 Ft. Toolbar
Right Hand Shown

PHOTO NO. 3943A

Install front cross tube weld (arrow 1), center it on trailer tongue. *NOTE: Position of vertical 3 x 4 tube (arrow 2) mounts to the rear.* Install (2) 5/8 bolts (arrow 3) using lockwasher and hex nuts. Reinstall right and left hand wing rest (arrow 4) to the front cross tube, using original (2) 5/8 u-bolt (arrow 5) with lockwashers and hex nuts.

STEP 13






PHOTO NO. 3966

Install bulkhead plate (arrow 1) using 5/8 u-bolt (arrow 2) with lockwasher and hex nuts. *NOTE: Bulkhead plate mounts left of center and between two 4800 disc opener units.*



DWG. NO. 3659

Reinstall front hose stand (arrow 1), from cat walk step. Using (1) 1/2 x 1 1/2 hex bolt (arrow 2) with 1/2 flatwasher (arrow 3), 1/2 lockwasher (arrow 4) and 1/2 hex nut (arrow 5).



DWG. NO. 3635

REF. NO.	PART NUMBER	DESCRIPTION	QTY	REF. NO.	PART NUMBER	DESCRIPTION	QTY
1	80305265	Blower & Plumbing Assembly	1	16	957-001-034	Hose Assy 3/8 x 180" 30' Toolbar	1
2	81004342	4 x 16 Cylinder Assembly	2	17	957-001-074	Hose Assy 3/8 x 240" 40' Toolbar	1
3	624001	HYD Cylinder 1 1/2 x 4	1	17	957-001-072	Hose Assy 3/8 x 378" 30' Toolbar	1
4	80305383	5 x 8 Cylinder	1		957-001-076	Hose Assy 3/8 x 498" 40' Toolbar	1
5	80305385	4 3/4 x 8 Cylinder	1	18	957-001-073	Hose Assy 3/8 x 288" 30' Toolbar	1
6	80305384	4 1/2 x 8 Cylinder	1		957-001-075	Hose Assy 3/8 x 348" 40' Toolbar	1
7	957-004-015	Hose Assy 3/8 x 264"	1	19	956-003-001	STR-ADPT 9/16 MJIC x 3/4 MORB w/o Restrictor	1
8	957-004-014	Hose Assy 3/8 x 318"	3	20	956-005-001-	Fitting-Elbow 90° 9/16 MJIC x 3/4 MORB	5
9	957-009-011	Hose Assy 1/2 x 200"	1	21	956-006-002	Fitting-Bulkhead Elbow 90° 9/16 MJIC x 9/16 MJIC	1
10	957-009-010	Hose Assy 1/2 x 210"	1	22	956-007-003	Fitting-Bulkhead Tee 9/16 MJIC x 9/16 MJIC x 9/16 MJIC	2
11	957-001-018	Hose Assy 3/8 x 79"	1				
12	957-001-013	Hose Assy 3/8 x 59"	1	23	956-007-010	Fitting Tee 9/16 FJIC x 9/16 MJIC x 9/16 MJIC	2
13	957-002-020	Hose Assy 3/8 x 66"	2	24	956-008-024	Restrictor Fitting 3/4 MORB x 9/16 MJIC	4
14	957-001-071	Hose Assy 3/8 x 36"	1	25	956-005-002	Fitting-Elbow 90° 9/16 MJIC x 9/16 FJIC	4
15	957-001-061	Hose Assy 3/8 x 56"	1				


JM-22-0000348

STEP 14

HYDRAULIC PLUMBING

Inspect all hydraulic fittings and hoses for damage, wear, and tightness. Ensure that all hoses are secured to frame in such a manner as to prevent possible damage or wear due to chafing or pinching by moving parts.


NOTE: DO NOT overtighten hydraulic fittings. Fittings should be installed and tightened in accordance with the torque table. Only pipe threaded connections should be treated with a thread sealant compatible to hydraulic systems and the sealant applied to male portion of threads only.

HYDRAULIC FITTING INSTALLATION PROCEDURES AND TORQUE TABLE	
SAE Flare Connection	
	1) Tighten nut finger tight until it bottoms the seat.
	2) Using a wrench, rotate nut to tighten. Turn nut 1/3 turn to apply proper torque.
SAE Straight Thread "O" Ring Seal	
	1) Insure jam nut and washer are backed up to the back side of smooth portion of elbow adapter.
	2) Lubricate "O" Ring-VERY IMPORTANT!
	3) Thread into port until washer bottoms onto spot face.
	4) Position elbows by backing up adapter.
	5) Tighten jam nut.

DWG. NO. 1966

JM-22-0000349

STEP 14A



LH SHOWN

PHOTO NO. 3935A

Install right and left hand toolbar fold cylinder as shown in photo. *NOTE: Restrictor fittings (arrow 1 and 2).*

STEP 14B





PHOTO NO. 3969

Install hydraulic hoses and fittings to transport lock cylinder (arrow 1) as shown in photo. Install hydraulic hose and fitting to center rockshaft lift cylinder (arrow 2).

STEP 14C



TOOLBAR FOLD PLUMBING

DWG. NO. 3968A

Install (2) bulkhead tee fittings (arrow 1) into bulkhead plate. Add (2) inline tee (arrow 2) which runs to transport lock cylinder.

NOTE: 90° bulkhead fitting is return line from left hand wheel lift cylinder.

STEP 14D



RH SHOWN

PHOTO NO. 3958A

Install hydraulic hoses and fitting to right and left hand wheel lift cylinder.

NOTE: After 4800 seeder units have been installed, hydraulic hose must be tied up as shown in photo.

STEP 14E





PHOTO NO. 3960A

Install hydraulic hoses to blower plumbing as shown in photo.

STEP 14F



DWG. NO. 3632

Install hydraulic hoses through pivot pin hose guide as shown in drawing.

NOTE: Optional marker hoses will also run through hose guide.

STEP 15




PHOTO NO. 3973

Attach 4836 tank/trailer to tractor hitch, and attach safety chain as shown in photo. Connect all hydraulic lines to tractor outlets.

STEP 16



IMPORTANT: Before operating hydraulic toolbar lift cylinders, all captive air must be removed from system. This may be done by removing cylinder pin from rod end of cylinder and cycling system until system is purged of air. Reattach cylinder rod pin and cautiously cycle toolbar lift through full cycle. Failure to take precaution may result in bodily injury or equipment damage.

Raise toolbar and remove stands from under toolbar. Raise toolbar to highest position.

STEP 17



IMPORTANT: Never operate wing fold cylinders without (4) restrictor fittings part number 956-008-024 for 4 inch cylinder, one at each end of both cylinders. Failure to have restrictors in place may result in body injury or equipment damage.

Fold toolbar forward, only half way at this time. Return toolbar to straight inline and lower toolbar to have bottom of toolbar 19 inches off the ground.

This section should be expanded to include folding the wings.

STEP 18



CAUTION: A lifting device such as crane, loader, or forklift is required for handling large parts and shipping bundles. Do not attempt to remove disc opener units from shipping bundle while in vertical position. Bundle may fall, causing severe injury or death, if not handled with proper equipment. While removing bundling straps, wires, or brackets be certain to keep clear of any parts that may drop. Support heavy sections with hoist or blocks before removing wires or straps.




PHOTO NO. 3974A

When moving right and left hand disc opener shipping bundle, attach lift chain around rear mast shank, and between parallel link and gauge wheel, as shown in photo.



CAUTION: When removing any bundling straps, wires or brackets, be certain to keep clear of any parts which may drop. Support heavy sections with hoist or blocks before removing wires or straps.

STEP 19




PHOTO NO. 3974

With disc opener shipping bundle laying securely on the floor as shown in photo, cut the shipping band (arrow 1) and unbolt angle strap (arrow 2). Lift top unit off and lay securely on the floor.

STEP 20





PHOTO NO. 3976

With disc opener laying on the floor, remove down pressure spring assembly. First remove klik pin (arrow 1) and 3/4" flat washer, then 3/4" pin (arrow 2). At this time the spring will be loose inside of disc opener. Set spring and handle aside at this time. It will all be reassembled later.

NOTE: All hardware should be tightened only enough to insure safety during assembly. Torque hardware to specified values, as shown on torque chart on page 8, only after assembly has been completed.

RIGHT AND LEFT SIDE DISC OPENER IDENTIFICATION



DWG. NO. 3634

Notice gauge wheel on inside, starting at tool-bar center and the rotary closer support arm offset to outside.

STEP 21




PHOTO NO. 3621A

Before mounting disc opener up to the toolbar, see assembly diagrams on pages 47 to 49 for proper location of disc opener. Move disc opener up to toolbar with front mast locks engaged. Install (2) 1/2 u-bolts (arrow 1) with (4) 1/2 lockwashers and (4) 1/2 hex nuts (arrow 2).

STEP 22




PHOTO NO. 3605A

After disc opener has been mounted up to toolbar and u-bolt and hex nuts are tight, re-install down pressure spring (arrow 1).

NOTE: The large 1 inch hook opening is at bottom, use front 7/8 diameter rod anchor.

Reinstall adjusting handle (arrow 2) and 3/4" pin (arrow 3) with 3/4" flat washers and klik pin (arrow 4).

STEP 23




PHOTO NO. 3977

Continue to mount disc openers across the toolbar working from center out.

See Assembly Diagrams on pages 49 to 51 for proper location of disc openers.

STEP 24




PHOTO NO. 3978

Continue to mount disc opener around hinges and center the last disc opener with the wheel lift, at outer toolbar wing.

STEP 25




PHOTO NO. 3945A

Raise toolbar up to full height, all five sections will be level at this time. Fold toolbar wings forward until toolbar guide (arrow 1) nose piece will enter wing rest plate. Adjust position of toolbar guide, to be inline with front edge of wing rest plate.

STEP 26




PHOTO NO. 3936B

Fold toolbar wing all the way forward until toolbar guide (arrow 1) hits toolbar rest back stop (arrow 2). **NOTE:** Check that both sides are up to back stop before raising wheel lift arms and locking for transport.



IMPORTANT: When toolbar lowers onto toolbar rest, it will move rearward 2 to 3 inches. Failure to take precaution may result in bodily injury or equipment damage.

STEP 27




PHOTO NO. 3627

To insure uniform down pressure on all disc openers, check that the down pressure spring bottom hook is anchored on front 7/8 diameter tube.

NOTE: This should be a start position for all units.

STEP 28




PHOTO NO. 3626

Check for uniform rotary closer down pressure strap anchor location front and rear. If required move front into middle hole on rear mast (arrow 1). Move rear anchor into third hole (arrow 2) as shown in photo.

NOTE: This should be a start position for all units.

STEP 29




PHOTO NO. 3628

To insure uniform angle on all rotary closers, check that all units are flush at front edge (arrow 1) and the rotary closer bearing (arrow 2) is on the same side as the disc opener coulters (arrow 3).

NOTE: This should be a starting angle for all units.

STEP 30




PHOTO NO. 3981

Install seed tube run from seed tank outlet to disc opener. See assembly diagrams on page 49 to 51 for proper length and position of hose running through hose guides.

STEP 31





PHOTO NO. 3982

Install seed through front hose rest (arrow 1).

NOTE: Drive wheel must have clearance over top of the tire.

STEP 32 40 FOOT TOOLBAR ONLY




RH Shown

PHOTO NO. 3983

Install (2) outer wing seed tube support straps (arrow 1) using (2) 1/2 x 8 1/2" hex bolt (arrow 2) with lockwasher and hex nuts. Install (2) cross straps (arrow 3) using (4) 3/8 x 1 1/2" hex bolt (arrow 4) with lockwasher and hex nuts.

NOTE: Number of seed tubes in support stand from outer toolbar disc openers.

STEP 33 30 & 40 FOOT TOOLBAR




RH Shown

PHOTO NO. 3984

Install (2) inner wing seed tube support and vertical strap (arrow 1) using (2) 1/2 x 8 1/2" hex bolt (arrow 2) with lockwasher and hex nut. Install cross straps (arrow 3) using (4) 3/8 x 1 1/2" hex bolt (arrow 4) with lockwasher and hex nuts.

NOTE: Number of seed tubes in support stand.

STEP 34



RH Shown

PHOTO NO. 3985

Install right and left hand light mount bracket (arrow 1) using (1) 1/2 x 8 1/2" hex bolt (arrow 2) and (1) 3/8 x 1 1/2" hex bolt (arrow 3) with lockwasher and hex nuts. Install light (arrow 4) use (4) 1/4 x 1 1/4" hex bolts (arrow 5) with 1/4" whiz nuts.

NOTE: Amber and red light will be visible from rear when toolbar is in transport.

STEP 35




PHOTO NO. 3986

Continue to install all electrical wires using wiring diagram on page 22. Run rear light wire through rear pivot pin holder (arrow 1) and front 7-point plug wire through front loop (arrow 2).




PHOTO NO. 3942B

Continue to install dual electric clutch wiring (arrow 1) and blocked seed detector (arrow 2). Use wiring diagram on page 22.

ASSEMBLY OPTIONAL EQUIPMENT

BALLAST WEIGHT



DWG. NO. 3628

To add additional weight to toolbar, concrete blocks can be ordered. Install concrete blocks as shown. *NOTE: Position of block pull rod and large corner notch to the inside.*

QUANTITY REQUIRED RIGID TOOLBAR	
30 Foot Toolbar	22
40 Foot Toolbar	38

ORDER ITEM NUMBER	DESCRIPTION
810-001-176	Concrete block 22 lbs. each.

WEIGHT BRACKET




PHOTO. NO. 3988

Install tractor front suitcase weight mounting bracket (arrow 1), using (4) 5/8" u-bolts and (8) 5/8" lockwashers and (8) hex nuts (arrow 2).




PHOTO NO. 3989

Case/IH suitcase weights fit this mounting. The clamping lock (arrow 1) fits on the bottom edge of mounting bracket.

JM-22-0000357




PHOTO NO. 3990

To fit JD suit case weights, lower support (arrow 1) must be installed using (2) 5/8 x 2" carriage bolts with (2) 5/8 lockwashers and (2) 5/8 hex nuts (arrow 2).





PHOTO NO. 3991

Shown in photo: JD suitcase weight attached to weight bracket assembly. Notice locking stud in the middle (arrow 1). A minimum of (2) suit case weights must be used. Secure with through bolts.

ORDER ITEM NUMBER	DESCRIPTION
80305512	WEIGHT BRACKET COMPONENTS

AIR BLOWER SCREEN



To avoid clogging the air inlet screen of the air blower with possible debris, a cylindrical screen is offered as an option. The cylindrical screen has a larger surface area compared to the flat screen offered with the 4836 tank/trailer. The additional surface area still allows enough air to flow into the air blower even if debris begins to clog the screen.

The cylindrical screen is attached to the blower using the (6) 1/4" self tapping screws and washers that are currently used to attach the flat screen onto the blower. The screen cover is attached to the cylindrical screen with (6) 1/4" self tapping screws which are included with this option.

ORDER ITEM NUMBER	DESCRIPTION
80305510	BLOWER SCREEN COMPONENTS

FILL AUGER

A fill auger can be ordered as an option with the unit. You have a choice of either an auger made by Kasco Manufacturing or Remlinger Manufacturing. Included with the fill auger are the components needed for its support. The fill auger support is attached to the trailer and allows the fill auger to rotate easily for use in the field or for transporting.




PHOTO NO. 3992




PHOTO NO. 3993

First, the front and rear support brackets must be attached to the tank. Two people will be needed for this operation. The front bracket (arrow 1) is attached at the front of the tank on the right side. The rear bracket (arrow 2) is attached at the rear of the tank, also on the right side. The brackets are attached by first removing the first (2) 5/16 whiz lock bolts (arrow 3) on the right side of the tank. One person will need to get inside the tank to hold the whiz lock nuts as the bolts are being removed. Next, line up the bottom holes of the support brackets with the holes left from the screws, as shown in the pictures above. Now, re-insert the whiz lock bolts and nuts.




PHOTO NO. 3994

Attach the outer tube weld (arrow 1) to the right trailer tongue in front of the front mounting plate, using (2) of the 5/8" u-bolts provided.


Attach the lower support weld (arrow 2) to the left side of the trailer in front of the front mounting plate, using the other (2) 5/8" u-bolts. Make sure the upper braces of the lower support weld face toward the center of the trailer.

Set the spacer (arrow 3) on top of the outer tube weld.



PHOTO NO. 3995

Insert the vertical tube weld (arrow 1) so the bottom of the weld goes through the outer collar of the lower support weld, the spacer and the outer tube weld. The collar of the vertical tube weld should line up inside the collar of the lower support weld. Some adjustment may be needed with the placement of the outer tube weld and lower support weld on the trailer to assure proper alignment for the vertical tube weld to be inserted.



NOTE: If auger is not balanced properly, the auger clamps can be loosened, and the auger moved forward or backward, depending upon proper balance of the auger.

REMLINGER AUGER

To prepare the Remlinger Auger for proper installation, a small amount of welding is needed. Two support tabs need to be welded to the channel, as shown in view A-A of the drawing above. A horseshoe tab also needs to be welded to the channel, as shown in the top drawing of view B-B. The horseshoe tab must be welded 81 1/2 inches from the support tabs. After installing the auger onto the support, if auger is not balanced properly, the clamps can be loosened and the auger moved until it is balanced.

KASCO AUGER

To prepare the Kasco Auger for proper installation, a small amount of welding is needed. Unlike the Remlinger auger, the support tabs are already welded to the tubing provided with the auger. The horseshoe tab still needs to be welded 81 1/2 inches from the support tabs as shown in the bottom drawing of view B-B. After installing the auger onto the support, if auger is not balanced properly, the clamps can be loosened and the auger moved until it is balanced.

46 Assembly Optional Equipment

Once the vertical tube weld has been inserted properly, tighten the 5/8" u-bolts to torque and insert the 3/8" bolt and nut to the bottom of the vertical tube weld.




PHOTO NO. 3996

Attach the swing arm weld (arrow 1) to the vertical tube weld. Line up the holes on the square tubing of the swing arm with the holes on the swing arm supports of the vertical tube weld, and insert the 3/4" bolt and nut. The ratchet jack (arrow 2) can be attached to the ratchet jack supports on the swing arm and the vertical tube weld as shown in the picture above.

ORDER ITEM NUMBER	DESCRIPTION
80305509	FILL AUGER COMPONENTS




PHOTO NO. 3997

Install hydraulic selector valve using selector valve anchor (arrow 1) and rear strap (arrow 2) with (2) 3/8 x 4" hex bolt (arrow 3) and (2) lockwashers and hex nuts. Install (1) 5/16 x 1 3/4" hex bolt (arrow 4) with whiz lock nut. Install hydraulic plumbing as shown in diagram on page 47.

MARKERS




PHOTO NO. 3964

NOTE - Contact:


Yetter Manufacturing Co.
1-800-447-5777
Colchester IL. 62326-0358

for complete marker assembly with mounting brackets. 6150 Series Hydraulic Flat Folding Marker shown in photo.

Additional assembly instructions is shown on page 48, Fitting Yetter 6150 Marker on 4800 Air Drill.

JM-22-0000361


HYDRAULIC PLUMBING DIAGRAM FOR OPTIONAL FILL AUGER & MARKERS



DWG. NO 3635


REF. NO.	PART NUMBER	DESCRIPTION	QTY	REF. NO.	PART NUMBER	DESCRIPTION	QTY
1	80305516	HYD Valve	1	5	206-01019	Union 3/4 MJIC (2)	1
2	203-35510	O-Ring Pipe Plug	2	6	957-005-021	Hose Assy 3/8 x 50"	1
3	956-003-003	Fitting-Straight Adapter 1/2 MNPT x 9/16 MJIC	2	7	957-001-074	Hose Assy 3/8 x 240"	1
4	956-005-003	Fitting-Elbow 90° 1/2 MNPT x 9/16 MJIC	1	8	957-005-003	Hose Assy 3/8 x 191"	1
				9	956-003-001	STR-ADPT 9/16 MJIC x 3/4 MORB	4

JM-22-0000362



JM-22-0000363

4838 40 FOOT 32 ROW 15 INCH SPACING														TOTAL HOSE LENGTH RECD
SEED 4800 ARI BEEDER	200 HOSES	200 HOSES	200 HOSES	200 HOSES	200 HOSES	200 HOSES	200 HOSES	200 HOSES	200 HOSES	200 HOSES	200 HOSES	200 HOSES	200 HOSES	400 FEET
HOSE NUMBER	1 & 32	2 & 31	3 & 30	4 & 29	5 & 28	6 & 27	7 & 26	8 & 25	9 & 24	10 & 23	11 & 22	12 & 21	13 & 20	




DWG. NO. 3633

Assembly Diagrams 49

JM-22-0000364


4832 39 FOOT 36 ROW 10 INCH SPACING																			TOTAL HOSE LENGTH REQ'D
OWNER 4000 AIR SELLER	202 HOSES	212 HOSES	200 HOSES	56 HOSES	105 HOSES	177 HOSES	195 HOSES	67 HOSES	81 HOSES	141 HOSES	156 HOSES	108 HOSES	105 HOSES	131 HOSES	126 HOSES	104 HOSES	108 HOSES	10 HOSES	475 FEET
HOSE NUMBER	1 & 25	2 & 26	3 & 24	4 & 33	5 & 32	6 & 31	7 & 30	8 & 29	9 & 28	10 & 27	11 & 26	12 & 25	13 & 24	14 & 23	15 & 22	16 & 21	17 & 20	18 & 19	



DWG. NO. 3629

JM-22-0000365

4831 30 FOOT 24 ROW 16 INCH SPACING													TOTAL HOSE LENGTH REQD
SERIES 4800 AIR SEEDER	220 INCHES	208 INCHES	191 INCHES	180 INCHES	185 INCHES	154 INCHES	140 INCHES	138 INCHES	129 INCHES	127 INCHES	122 INCHES	127 INCHES	320 FEET
HOSE NUMBER	1 & 24	2 & 23	3 & 22	4 & 21	5 & 20	6 & 19	7 & 18	8 & 17	9 & 16	10 & 15	11 & 14	12 & 13	



DWG. NO. 3630

Assembly Diagrams 51

JM-22-0000366

HINIKER WARRANTY

The only warranty Hiniker Company (Hiniker) gives and the only warranty the dealer is authorized to give is as follows:

We warranty products sold by Hiniker or authorized Hiniker dealers to be in accordance with our published specifications or those specifications agreed to by us in writing at time of sale. Our obligation and liability under this warranty is expressly limited to repairing or replacing, at our option, within one year after date of retail delivery, to the original purchaser, any product not meeting the specification. **WE MAKE NO OTHER WARRANTY, EXPRESS OR IMPLIED AND MAKE NO WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR ANY PARTICULAR PURPOSE.** Our obligation under this warranty shall not include any transportation charges or costs or any liability for direct, indirect or consequential damage or delay. If requested by Hiniker Company, products or parts for which a warranty claim is made are to be returned freight prepaid to our factory. Any improper use, operation beyond rated capacity, substitution of parts not approved by Hiniker Company, or any alteration or repair by others in such manner as in our judgment affects the product materially and adversely shall void this warranty. **NO EMPLOYEE OR REPRESENTATIVE IS AUTHORIZED TO CHANGE THIS WARRANTY IN ANY WAY OR GRANT ANY OTHER WARRANTY.**

HINIKER reserves the right to make improvement changes on any of our products without notice.

HINIKER does not warrant the following:

1. Used products.
2. Any product that has been repaired, modified or altered in a way not approved by Hiniker Company.
3. Depreciation or damage caused by normal wear, lack of reasonable and proper maintenance, failure to follow Operator Manual instructions, misuse, lack of proper protection during storage, or accident.
4. Parts replacement and service necessitated by normal wear or maintenance.

A DELIVERY REPORT FORM must be filled out and received by **HINIKER COMPANY** to initiate the warranty coverage.

**HINIKER COMPANY
AIRPORT ROAD
P. O. BOX 3407
MANKATO, MN 56002-3407
PHONE (507) 625-6621
FAX (507) 625-5883**