



Espacenet

WO2014115681A1 ELECTROLYTIC COPPER FOIL AND METHOD FOR PRODUCING SAME

Applicants: FURUKAWA ELECTRIC CO LTD [JP]

Inventors: SHINOZAKI KENSAKU [JP],SUZUKI AKITOSHI [JP],FUJISAWA KIMIKO [JP],EZURA TAKESHI [JP]

Classifications:

IPC **C25D1/00; C25D1/04;**

CPC **C25D1/04 (EP); C25D3/38 (EP);**

Priorities: JP2013011517A 2013-01-24

Application: JP2014050960W·2014-01-20

Publication: WO2014115681A1·2014-07-31

Published as: **CN104903495A; CN104903495B; JP5706045B2; JPWO2014115681A1; KR101660201B1; KR20150107735A; TW201443289A; TWI526579B;** WO2014115681A1

ELECTROLYTIC COPPER FOIL AND METHOD FOR PRODUCING SAME

Abstract

[Problem] To provide an electrolytic copper foil having high mechanical strength under normal conditions, and resistant to thermal deterioration even when heated to about 300°C. [Solution] An electrolytic copper foil containing a metal that exists in the form of an oxide in a liquid at pH 4 or below, or an oxide thereof, and containing chlorine at a level of more than 10 ppm but less than 50 ppm; and a method for producing the same.

SK nexilis EX2017
Solus v. SK nexilis
IPR2024-01463