

1996



ANNUAL BOOK OF ASTM STANDARDS

SECTION

5

Petroleum Products, Lubricants,
and Fossil Fuels



VOLUME
05.01

Petroleum Products and Lubricants (I):
D 56 – D 2596

Revision issued annually

MAR 08 '96

1996




SECTION

5

ANNUAL BOOK OF ASTM STANDARDS

**Petroleum Products, Lubricants,
and Fossil Fuels**



VOLUME
05.01

**Petroleum Products and Lubricants (I):
D 56 - D 2596**

Includes standards of the following committee:

D-2 on Petroleum Products and Lubricants

Publication Code Number (PCN): 01-050196-12



RC000.6
A56K
1996
V.05.01

SCIENCE & TECHNOLOGY

Editorial Staff

Director, Editorial Services:

Roberta A. Storer

Manager, Standards Publications:

Joan L. Cornillot

Paula C. Fazio

Senior Indexer:

H. Joel Shupak

Editors:

Nicole C. Baldini

Lisa Bernhardt

Elizabeth L. Gutman

Sharon L. Kauffman

Joanne G. Kramer

Christine M. Leinweber

Vernice A. Mayer

Patricia A. McGee

Felicia Quinzi

Todd J. Sandler

Richard F. Wilhelm

Editorial Assistant:

Elizabeth Barszczewski

Library of Congress Catalog Card Number: 83-641658

ISBN 0-8031-2356-6 (set)

ISBN 0-8031-2303-5 (section)

ISBN 0-8031-2304-3 (volume)

Copyright © 1996 AMERICAN SOCIETY FOR TESTING AND MATERIALS, West Conshohocken, PA. Prior editions copyrighted 1995 and earlier, by the American Society for Testing and Materials. All rights reserved. This material may not be reproduced or copied, in whole or in part, in any printed, mechanical, electronic, film, or other distribution and storage media, without the written consent of the publisher.

Photocopy Rights

Authorization to photocopy items for internal or personal use, or the internal or personal use of specific clients, is granted by the AMERICAN SOCIETY FOR TESTING AND MATERIALS for users registered with the Copyright Clearance Center Inc. (CCC) Transactional Reporting Service, provided that the base fee of \$2.50 per copy, plus \$0.50 per page is paid directly to CCC, Suite 910, 222 Rosewood Dr., Danvers, MA 01923; Tel. (508) 750-8400. For those organizations that have been granted a photocopy license by CCC, a separate system of payment has been arranged. The fee code for users of the Transactional Reporting Service is 0-8031-2304-3/96 \$2.50 + .50.

Printed in Easton, MD, U.S.A.

Standard Test Method for Needle Penetration of Petroleum Waxes¹

This standard is issued under the fixed designation D 1321; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

NOTE—Equations 1 and 2 were corrected editorially and the designation date changed effective April 10, 1995.

1. Scope

1.1 This test method covers the empirical estimation of the consistency of waxes derived from petroleum by measurement of the extent of penetration of a standard needle. This test method is applicable to waxes having a penetration of not greater than 250.

NOTE 1—This test method is similar to the needle method for determining the penetration of bituminous material, Test Method D 5. Cone methods applicable to greases and to petrolatum are described in Test Methods D 217 and Test Method D 937, respectively.

1.2 The values stated in SI units are to be regarded as the standard. The values given in parentheses are for information only.

1.3 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Referenced Documents

- 2.1 *ASTM Standards:*
 - D 5 Test Method for Penetration of Bituminous Materials²
 - D 217 Test Methods for Cone Penetration of Lubricating Grease³
 - D 937 Test Method for Cone Penetration of Petrolatum³
 - D 938 Test Method for Congealing Point of Petroleum Waxes, Including Petrolatum³
 - E 1 Specification for ASTM Thermometers⁴

3. Terminology

3.1 Definition:

3.1.1 *penetration, n, of petroleum wax*—the depth in tenths of a millimetre to which a standard needle penetrates into the wax under defined conditions.

4. Summary of Test Method

4.1 The sample is melted, heated to 17°C (30°F) above its congealing point, poured into a container, and then air cooled under controlled conditions. The sample then is

conditioned at test temperature in a water bath. Penetration is measured with a penetrometer, which applies a standard needle to the sample for 5 s under a load of 100 g.

5. Significance and Use

5.1 Petroleum waxes differ in hardness. Needle penetration is a measurement of hardness. Hardness may have a significant effect upon other physical properties.

6. Apparatus

6.1 *Penetrometer*, for applying the standard needle to the surface of the sample specimen and for measuring the extent of penetration at the conclusion of the test. The penetrometer shall be constructed in such a manner that the accurate placement of the tip of the needle at the level surface of the specimen may be made while maintaining a “zero” reading on the indicator. The apparatus shown in Fig. 1 represents a composite drawing illustrating the two available types of instrument, one with an adjustable table and the other with an adjustable needle assembly; the use of either type instru-




FIG. 1 Penetrometer

¹ This test method is under the jurisdiction of ASTM Committee D-2 on Petroleum Products and Lubricants and is the direct responsibility of Subcommittee D02.10 on Petroleum Wax.

Current edition approved Apr. 10, 1995. Published June 1995. Originally published as D 1321 - 54 T. Last previous edition D 1321 - 92.

² *Annual Book of ASTM Standards*, Vol 04.03.

³ *Annual Book of ASTM Standards*, Vol 05.01.

⁴ *Annual Book of ASTM Standards*, Vol 14.03.

ment is released, be provided to maintain indicator divisions millimeter

6.2 Ti

nism attively, a s

6.3 Ne

mately 8

shown in

to a cone

min to 9°

of the cor

mm (0.0

The tape

hardened

Rockwell

be ground

shall be f

shall be s

shall be s

the trunc

(8 μ m.) (

0.05 g. Tl

a weight

plunger.

NOTE 2

measure a

with these

6.4 Te

under op

diameter

thickness

threads c

inside wa

base plat

glycerin a

6.5 Te

23.9 $\pm$ 2

6.6 W

maintain

(Note 6).

window 1

be possit

depth of

perforate

ment is permissible. The loaded needle must fall, when released, without appreciable friction. The instrument shall be provided with leveling screws and a spirit level to maintain the plunger shaft in a true vertical position. The indicator scale shall be calibrated in tenths of a millimetre divisions and shall have a range of at least 250 tenths of millimetres.

6.2 Timing Device—An automatic timing release mechanism attached to the penetrometer may be used. Alternatively, a stop watch graduated in 0.1-s intervals may be used.

6.3 Needle and Plunger—The needle shall be approximately 83 mm in length and conform to the dimensions shown in Fig. 2. It shall be symmetrically tapered at one end to a cone whose angle shall be within the range from $8^{\circ} 55'$ to $9^{\circ} 25'$ min over the entire length of the cone. The axis of the cone shall be coincident with the shaft axis within 0.13 mm (0.005 in.) maximum runout (total indicator reading). The tapered section of the needle shall be made from fully hardened and tempered stainless steel, Grade 440-C or equal, Rockwell hardness C57 to 60. After tapering, the point shall be ground off to a truncated cone, the smaller base of which shall be from 0.14 to 0.16 mm in diameter. The truncation shall be square with the needle axis within 2° and the edge shall be sharp and free from burrs. The conical surface and the truncation shall be finished to a smoothness of $0.02 \mu\text{m}$ ($8 \mu\text{in.}$) (rms). The final weight of the needle shall be 2.5 ± 0.05 g. The total weight of the plunger shall be 47.5 ± 0.05 g; a weight of 50 ± 0.05 g is required for mounting on the plunger.

NOTE 2—The National Institute of Standards and Technology will measure and certify the accuracy of penetration needles in accordance with these permissible variations.

6.4 Test Specimen Container, consisting of a brass cylinder open at both ends, having a 25.4-mm (1-in.) inside diameter, 31.8-mm ($1\frac{1}{4}$ -in.) height, and 3.2-mm ($\frac{1}{8}$ -in.) wall thickness. To prevent slippage of very hard wax, a few screw threads or grooves shall be cut into the center part of the inside wall of the cylinder. The cylinder shall be placed on a base plate of brass, wetted with an equal volume mixture of glycerin and water, when casting a test specimen.

6.5 Test Room or Cabinet, capable of being maintained at $23.9 \pm 2.2^{\circ}\text{C}$ ($75 \pm 4^{\circ}\text{F}$).

6.6 Water Bath, of at least 10-L capacity capable of being maintained at the test temperature within $\pm 0.1^{\circ}\text{C}$ ($\pm 0.2^{\circ}\text{F}$) (Note 6). The water bath should be made of glass or have a window to permit a horizontal view of the specimen. It shall be possible to immerse the test specimen in the bath to a depth of not less than 102 mm (4 in.) and to support it on a perforated conditioning shelf not less than 51 mm (2 in.)

from the bottom of the bath. The bath also shall be equipped with a rigid perforated test shelf about 51 mm below the water level to support the specimen during the penetration by the needle.

6.7 Thermometer, for use in the water bath. An ASTM Precision Thermometer, total immersion, having a range from 25 to 55°C or 77 to 131°F and conforming to the requirements for Thermometer 64C or 64F as prescribed in Specification E 1.

6.8 Brass Plate, 63.5 by 38 by 6.4 mm ($2\frac{1}{2}$ by $1\frac{1}{2}$ by $\frac{1}{4}$ in.) for supporting test specimen during preparation of the sample. The specimen support is placed on corks during the cooling period.

7. Preparation of Test Specimen

7.1 Heat the wax sample to approximately 17°C (30°F) above its congealing point (as determined by Test Method D 938, using care to prevent local overheating. Stir until the sample is homogeneous and free from air bubbles. In the test room or cabinet maintained at $23.9 \pm 2.2^{\circ}\text{C}$ ($75 \pm 4^{\circ}\text{F}$), place the brass plate on two corks (No. 16 or 18 recommended), and wet the upper surface of the plate with a mixture of equal volumes of glycerin and water. Place the test specimen container on the plate and then pour the melted wax into it in such a way that a convex meniscus is formed. Allow the container and contents to cool in the room at $23.9 \pm 2.2^{\circ}\text{C}$ for 1 h. Then shave any excess wax from the top of the container and remove the brass plate. Place the smooth wax surface up. Condition the specimen in the bath at the test temperature within 0.1°C ($\pm 0.2^{\circ}\text{F}$) for 1 h.

NOTE 3—Very hard waxes occasionally will shrink away from the walls of the test specimen container; in such cases, it is permissible to wedge the specimen in the container.

8. Procedure

8.1 Reverse the penetrometer base and place the penetrometer head over the edge of the water bath and above the perforated test shelf used for supporting the specimen. It may be necessary to place a weight on the base of the penetrometer to counter-balance the head (Note 5). Level the penetrometer and the perforated shelf in the water bath.

NOTE 4—Alternatively, the penetrometer may be placed in the water bath. Likewise a small bath may be placed on the penetrometer stand provided the test temperature (within 0.1°C ($\pm 0.2^{\circ}\text{F}$)) and the required water circulation above and below the test specimen are maintained, and provided further that the temperature of the small bath is measured immediately prior to testing each specimen using the thermometer specified in 6.7. Emergent stem corrections shall be applied when the correction equals or exceeds 0.05°C (0.1°F). One of the above alternatives will be required if the penetrometer is the adjustable table type.

8.2 Place the specimen container on the perforated test shelf with the smooth wax surface that had contacted the brass plate at the top. Make certain that the container or test shelf cannot teeter during testing. Adjust the water level so that it is 25 mm (1 in.) above the top surface of the specimen, and maintain it at the test temperature.

NOTE 5—The test may be performed at any temperature in the range from 25 to 55°C (77 to 130°F). Temperatures 25 , 35 , 45 , or 50°C (of 77 , 95 , 113 , or 122°F) normally are used.

8.3 Place a 50-g weight above the penetrometer needle, making a total load of 100 ± 0.15 g for the needle and all




FIG. 2 Standard Needle

attachments. Observe that the release mechanism does not drag on the shaft and that the indicator on the scale is in the "zero" position. Adjust either the indicator assembly or the table, depending upon the type of instrument, until the tip of the needle nearly touches the surface of the specimen. Securely lock the movable assembly in this position.

8.4 Then, by means of the slow-motion adjustment, bring the needle tip to just touch the surface of the specimen, watching the reflection of the needle tip as an aid to accurate setting. After 5 min, release the needle shaft and hold it free for 5 s, timing this interval automatically or with a stop watch graduated to 0.1 s (Note 6). Then gently depress the indicator shaft until it is stopped by the needle shaft, and read the penetration from the indicator scale.

NOTE 6—If an automatic timing release mechanism is not used, the timing can be done conveniently by starting the stop watch before the beginning of the test, releasing the needle shaft as the second hand crosses a unit graduation of the watch and engaging the shaft of the needle when the watch indicates exactly 5 s later.

8.5 Make four tests at points about equally spaced (not less than 12.7 mm (1/2 in.) apart) on a circumference at least 3.2 mm (1/8 in.) from the side of the container. Before each test, wipe the needle carefully toward its point with a clean, dry cloth to remove all adhering wax, position the needle as described in 8.4, and proceed with the test.

TABLE 1 Repeatability and Reproducibility Calculated for Different Values of Penetration

Penetration, $\bar{x}$	Repeatability	Reproducibility
10	2	5
20	2	6
30	2	7
40	3	7
50	3	8
60	4	9
70	4	10
80	5	11
90	5	12
100	6	13
125	8	17
150	11	22
175	14	29
200	19	37

The American Society for Testing and Materials takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, 1916 Race St., Philadelphia, PA 19103.

9. Report

9.1 Record as a single test value the average scale reading for the four penetrations on the prepared specimen and report to the nearest 0.1 mm. Also report the actual test temperature used.

10. Precision and Bias⁵

10.1 The precision of this test method as determined by statistical examination of interlaboratory results is as follows:

10.1.1 *Repeatability*—The difference between successive results obtained by the same operator with the same apparatus under constant operating conditions on identical test material would, in the long run, in the normal and correct operation of the test method, exceed the following values in only one case in twenty.

$$\text{Repeatability} = 1.72 [10^{0.00524 (\bar{x})}] \quad (1)$$

where $\bar{x}$ = penetration.

10.1.2 *Reproducibility*—The difference between two single and independent results obtained by different operators working in different laboratories on identical test material would, in the long run, exceed the following values in only one case in twenty.

$$\text{Reproducibility} = 4.81 [10^{0.00442 (\bar{x})}] \quad (2)$$

where $\bar{x}$ = penetration.

10.1.3 The repeatability and reproducibilities for the different penetration values calculated from the above equations are shown in Table 1.

10.2 *Bias*—The procedure in Test Method D 1321 for measuring the needle penetration of petrolatum waxes has no bias because the value of the needle penetration can be defined only in terms of a test method.

11. Keywords

11.1 hardness; needle penetration; penetration; petroleum wax

⁵ Supporting data are available from ASTM Headquarters. Request RR:D02-1205.



1. Scope

1.1 smoke relation and sm

NOTE that requ (IP Desi

1.2 safety of the health limitat ments,

2. Ref

2.1

D21

Bu

D17

tic

2.2

IP 5

3. Ter

3.1

3.1.1

flame

4. Sun

4.1

that is known be ach to the

¹ This Petroleum Curre publisher
² Disc
³ Ann
⁴ Insti Standard