



IPR2025-00032
Tesla EX1007 Page 1



IPR2025-00032
Tesla EX1007 Page 2



IPR2025-00032
Tesla EX1007 Page 3

Public Utilities Fortnightly

HD
2763
.A2
P8x

V2G

From Wheels to Wires

p. 16


**********ALL FOR ADC 493
PF84459 JAN 2003 1 SCK 138

664318, DWIGHT B WALDO LIBRARY
WESTERN MICHIGAN UNIVERSITY
1903 W MICHIGAN AVE
KALAMAZOO MI 49008-5200

Public Utilities
Fortnightly
February 15, 2002 Vol.140, No. 4

Articles

16 **The V2G Concept: A New Model For Power?**
Blurring the line between transportation and utility infrastructure, new fuel cell and electric vehicles being proposed could be a new power source for electric utilities.
By By Steven E. Letendre, Ph.D., and Willett Kempton, Ph.D.



28 **The Aftermath of Alliance**
What does its downfall mean for the industry?
By Jennifer Alvey

32 **Gas-Power Infrastructure: The Missing Link?**
Fixing electric transmission congestion has been dominating market design policy debates since the beginning of restructuring. Could the gas pipeline infrastructure offer a solution?
By Ron Hrehor and Don Sytsma

38 **The Energy Tech Chronicles: Will Bust Turn to Boom?**
Once the darlings of Wall Street, energy technology companies have fallen on hard times. Will environmental policy changes and new investments by the government, as well as energy and automobile companies, once again fuel their rise?
By Philip J. Deutch



Departments

4 Frontlines
By Richard Stavros

8 People

10 Benchmarks

Perspective 12
Overcapacity … Just Part of the Cycle of Growth
By Betsy Vaninetti


News Analysis 46
Onward, Kyoto!
By Jennifer Alvey

Off Peak 50

Advertising

48 Advertising Index

Professional Directory 48



The Gas-Power Vision: Five Obstacles

1. Alignment and Synchronization of Interests
2. Power Generation Developers' Commercial Demand
3. Gas Transmission Operators Pricing of Capacity Issues
4. Gas Transmission System Design
5. Regulatory Obligations to Ensure Equality of Services

See p. 32

Western Michigan University
FEB 13 2002
LIBRARY

California: Beginning Anew



The 2002 rhetoric sounds like pro-electric competition, but is it too little, too late?

IT'S NO SECRET THAT CALIFORNIANS LIKE HAPPY ENDINGS. JUST LOOK at most Hollywood movies, which like to tie up the story's loose ends in less than two hours (usually). But in its recent efforts to tie up the loose ends left from the California Crisis, is the state setting itself up for a sequel, California Crisis II: A Not So Beautiful Market.

Like all sequels, this one may include a new cast of characters, in addition to some of the old. GOP gubernatorial candidate and former Los Angeles mayor Richard Riordan, while supporting federal price caps, believes in direct access, deregulation, renegotiation of long-term contracts, and the abolishment of California's new power authority. Businessman Bill Simon supports direct access, opposes federal price caps, believes California got electric competition wrong, and wants to abolish the power authority. Secretary of State Bill Jones is pretty much in line with Mr. Simon, and we all know where Gov. Gray Davis falls on the issues—he wants greater state involvement in markets. It's amazing that these candidates can voice a pro-competition position without pies being thrown, and after the billions the state spent on the Crisis.

While it may look hopeful that a competitive market will emerge from California after all, it doesn't seem reassuring that new organizations are being proposed that may not have experience in running or managing markets.

On the regulatory side, there is a proposal to consolidate duties carried out by the California Public Utilities Commission, Energy Commission, Department of Conservation and the energy division of the California Department of Water Resources. While consolidation is good, will what is put in its place be better?


Furthermore, on the market side, the California ISO has issued a proposed market redesign, that recommends, of all things, a power exchange to be encouraged or set up to manage a day-ahead market. I know PhDs who still have nightmares over the Cal-PX. Let's hope they do better the second time. In any case, whatever the sequel to the Crisis will be—a happy ending, a thriller—it's guaranteed to keep the industry on the edge of their seats.

■■■

Meanwhile, for those of you interested in having a weekly taste of electric transmission and power market design, analysis and news, I direct you to a new offering from *Public Utilities Fortnightly*, called Grid Week, which was launched in late January by my predecessor Bruce W. Radford. This new publication promises to be insightful, cutting edge, and no doubt will generate news itself.

For a trial, call (800) 368-5001.

I hope you enjoy this issue and your trial to Grid Week.



Public Utilities Fortnightly

PUBLISHER
Susan M. Johnson

EDITOR-IN-CHIEF
Bruce W. Radford

EXECUTIVE EDITOR
Richard Stavros

MANAGING EDITOR
Jay S. Polachek

SENIOR EDITOR
Mark Hand

ASSOCIATE EDITOR
Jennifer L. Alvey

EDITORIAL ASSISTANT
Cameron Nyhen

CONTRIBUTING LEGAL EDITORS
Lori A. Burkhart
Phillip S. Cross

ART DIRECTOR
Lindsay Alexander

GRAPHIC DESIGNER
Alex Stephen

ADVERTISING SALES MANAGER
Joseph D. Paparello

ACCOUNT EXECUTIVE
Andrés M. Mancini

SALES COORDINATOR
Jean O. Cole

MANAGER, CIRCULATION AND FULFILLMENT
Pia Aladdin

CUSTOMER SERVICE
Janet Clark
Yvonne Patrick
Christy Cochran

© Copyright 2002 by Public Utilities Reports Inc. All Rights Reserved. Public Utilities Fortnightly (ISSN 1074-6099) is published semi-monthly, except monthly in August and December, by Public Utilities Reports Inc. Executive and editorial offices at 8229 Boone Boulevard, Suite 401, Vienna, VA 22182. Tel: 703-847-7720, Fax: 703-847-0683. Email: pur@pur.com

EXECUTIVE MANAGEMENT: Randall F. Spencer, Chairman, President and CEO; Susan M. Johnson, Executive Vice President and Secretary; Jennings B. Yowell, Vice President and Treasurer; Robert V. Burns, Assistant Vice President and Chief Financial Officer.

POSTMASTER: Send address changes to Public Utilities Fortnightly, 8229 Boone Blvd.,Suite 401, Vienna, VA 22182-2623. Periodicals postage paid at Vienna, VA and additional mailing offices.

SUBSCRIPTIONS: $139 per year (22 issues) U.S. and possessions; Canada and all other countries, $190 (International Surface Airlift.) Single copy $15. Copies not delivered due to subscriber's failure to send change of address six weeks in advance cannot be replaced. Replacement copies must be claimed within 30 days of cover date for free replacement.

CHANGE OF ADDRESS: Notices should provide old mailing label as well as new address including Zip or Postal Code to: Public Utilities Fortnightly, 8229 Boone Blvd., Suite 401, Vienna, VA 22182-2623 or call 1-800-368-5001. Please allow 4 to 6 weeks for changes.

The Public Utilities Fortnightly Database is accessible through LEXIS®/NEXIS® and WESTLAW®

All rights to editorial content are reserved by Public Utilities Reports Inc. No article, photograph or illustration may be reproduced in whole or in part without the written permission of the publisher, except permission to photocopy which is granted to users registered with the Copyright Clearance Center, 222 Rosewood Drive, Danvers, MA 01923. Federal copyright law prohibits unauthorized reproduction by any means and imposes fines of up to $25,000 for violations.

For more information on Public Utilities Reports Inc. and Public Utilities Fortnightly visit us on the Web at www.pur.com.

REPRINTS: For high-quality reprints of 100 or more, please call 703-847-7720.

IPR2025-00032
Tesla EX1007 Page 6

The V2G Concept: A New Model For Power?

Connecting utility infrastructure and automobiles.

By Steven E. Letendre, Ph.D., and Willett Kempton, Ph.D.


ELECTRIC-DRIVE VEHICLES CAN BE THOUGHT OF as mobile, self-contained, and—in the aggregate—highly reliable power resources. "Electric-drive vehicles" (EDVs) include three types: battery electric vehicles, the increasingly popular hybrids, and fuel-cell vehicles running on gasoline, natural gas, or hydrogen. All these vehicles have within them power electronics which generate clean, 60 Hz AC power, at power levels from 10kW (for the Honda Insight) to 100kW (for GM's EV1). When vehicle power is fed into the electric grid, we refer to it as "Vehicle-to-Grid" power, or V2G.

Electric utility planners and strategists, when they think about electric-drive vehicles at all, have seen battery vehicles as night-charge (valley-filling) load, and perhaps have seen fuel cell vehicles as possible generation resources for some distant future. In contrast, a recent study we conducted for the California Air Resources Board (CARB) and the Los Angeles Department of Water and Power, shows all three types of EDVs (battery, hybrid, and fuel cell) have potential roles to play as utility resources, and that ancillary services are the most lucrative use for vehicle power.

The electric power resource from vehicles is potentially quite large. In California alone, we calculate that CARB's zero emission vehicle mandates will provide 424 MW of power capacity by 2004, and 2.2 GW by 2008 (Kempton et al., 2001: 22). Looking further into the future, the Electric Power Research Institute (EPRI) predicts that power from electric-drive vehicles could reduce the global requirement for central station generation capacity by up to 20 percent by the year 2050 (EPRI 2001).

Our study assesses the technical requirements, electrical capacity, and economic value of V2G. We examined a range of EDVs to provide four types of power: baseload, peak, spinning reserves, and regulation (up and down). V2G for baseload power does not make sense, as the per-kWh cost is too high and drive train designs assume low operating time (average 1 hour/day). However, the economic value of other forms of V2G appears high, more than enough to offset the initially higher costs of electric-drive vehicles. To realize this potential, however, will require some minor design modifications to current vehicles, and some coordination of vehicle and infrastructure planning.

IPR2025-00032
Tesla EX1007 Page 7



IPR2025-00032
Tesla EX1007 Page 8

V2G: How it Would Work


California, along with New York, Massachusetts, Vermont, and Maine, have embarked on policies to encourage the development and spread of electric-drive and low pollution vehicles. The goal is to reduce air pollution from mobile sources. These policy initiatives, advances in power electronics, and the opening of electricity markets across the country create opportunities for electric-drive vehicles to reduce air pollution, and at the same time increase the reliability and efficiency of the electric power system. This opportunity is based on using the electric storage of battery vehicles, or the generation capacity of hybrid and fuel cell vehicles, for ancillary services and/or peak power.

Three elements are required for V2G: 1) power connection for electrical energy flow from vehicle to grid, 2) control or logical connection, needed for the grid operator to determine available capacity, request ancillary services or power from the vehicle, and to meter the result, and 3) precision certified metering on board the vehicle. For fueled vehicles (fuel cell and hybrid), a fourth element, a connection for gaseous fuel (natural gas or hydrogen), could be added so that on board fuel is not depleted.

The first V2G requirement is the power connection. Battery vehicles must already be connected to the grid in order to recharge their batteries; to add V2G capability requires little or no modification to the charging station and no modification to the cables or connectors, but on board power electronics must be designed for this purpose. AC Propulsion, Inc., a manufacturer of electric vehicle drive trains, tested the first vehicle power electronics built for this purpose in August 2000. They informally reported that designing in reverse power flow had "zero incremental cost." Propulsion's current V2G power electronics, though, with extensive control and safety to ensure no back feeding of power onto the grid during an outage, added $400 to the initial cost, assuming moderate production runs. Thus, the on board power connections and power control needed for V2G have already been demonstrated, and are now a standard feature of one company's vehicle-drive units. (The same company is currently testing demonstration vehicles that provide regulation up and regulation down in real time, controlled via a signal from the California Independent System Operator.) The ease of adapting on board conductive chargers (versus inductive chargers) to V2G was one reason CARB adopted, in June 2001, staff recommendation to make on board conductive the standard for all new EV charging stations in California. By providing V2G-capable charging stations today for battery EDVs, utilities are also building portals for V2G for future hybrid and fuel cell vehicles.

The second requirement for V2G is control, for the utility or system operator to request vehicle power exactly when needed. This is essential because vehicle power has value greater than the cost to produce it only if the buyer (the system operator) can determine the precise timing of dispatch. The automobile industry is moving towards making real-time communications a standard part of vehicles. This field, called "telematics" has already begun with luxury vehicles; over a period of time it will be available for most new car models. Whether using built-in vehicle telematics, or in the interim using add-on communications, the

Figure 1: Suggested design of vehicle dashboard control, allowing driver to limit loss of range of vehicle and monitor power transactions.



Source: Kempton and Letendre, 1997

IPR2025-00032
Tesla EX1007 Page 9

vehicle could receive a radio signal from the grid operator indicating when power is needed.

The third element of precision, certified, tamper-resistant metering, measures exactly how much power or ancillary services a vehicle did provide, and at which times. Such devices are currently available to manufacture for under $10. The telematics could again be used to transmit meter readings back to the buyer for credit to the vehicle owner's account.


Thinking about the metering of V2G expands our usual concept of a "utility meter." Electronic metering and telematics appear to have efficiency advantages in eliminating the meter reader, transfer of billing data to the central computer, and the monthly meter-read cycle. More unnerving, electronic metering and telematics also eliminates the service address! An onboard meter would transmit its own serial number or account number with its readings, via telematics, and presumably this would be billed in conjunction with a traditional metered account with a service address. A large-scale V2G system would automate accounting and reconciliation of potentially millions of small transactions, similar to the recording and billing of calls from millions of cellular phone customers. In the most refined system, the vehicle could use some form of positioning (either GPS or the cell-phone positioning now required for 911), or an electronic link like the Bluetooth system, in order to automatically determine which tied-down traditional meter it is plugged in to. Thus, the mobile-metered kWhs or ancillary services would be added or subtracted to the amount registered on the fixed-meter to reconcile both billing amounts. On board metering and verification of where the vehicle is plugged in are required for business models that allow a vehicle to sell power while at a public power station or otherwise away from its home garage. However, since the vehicle will often be plugged into the owner's building meter anyway, these are refinements that could be saved until second-generation V2G systems.

The system operator or local utility may not wish to do business with hundreds or thousands of small providers of peak power or ancillary services. In this case, a third party could aggregate EDVs into MW blocks to sell in bulk power and ancillary services markets. At 16 kW per vehicle, a 1 MW block is 63 vehicles. Potential businesses to serve as aggregators include energy service companies (ESCOs), cell-phone operators (accustomed to automated dispatch and billing of millions of individual transactions), telematics service providers working with automobile manufacturers or fleet operators, power marketers, or possibly even service-oriented local distribution companies.

An initial concern often voiced about the V2G concept is that vehicle owners would not want to drain their vehicle's battery or an on board liquid fuel. To avoid V2G being seen as a threat to vehicle range, it is essential that the driver be able to limit any draw down so travel is not affected. Following Kempton and Letendre (1997), that can be done with a control that the driver sets according to driving needs. The power buyer must limit the degree of battery discharge or fuel tank rundown in accordance with the vehicle owners settings. An example control panel is shown in Figure 1. Whether the control is physical, on the dash, or on a Web

By providing V2G-capable charging stations today for battery EDVs, utilities are also building portals for V2G for future hybrid and fuel cell vehicles.

Evolution of Propulsion



Source: GM

IPR2025-00032
Tesla EX1007 Page 10

page, the idea is basically the same. The driver has two parameters to set—the length of the expected next trip (in the case shown in Figure 1, 10 miles at 6:45 the next morning), and the minimum range that must always be maintained, e.g. for an emergency room trip, two miles. (As we will see in Figure 2, when providing regulation up and down rather than peak or spinning reserves, there is little impact on range.)

One conceptual barrier to understanding vehicles as a power source is an initial belief that their power would be unpredictable or unavailable because they would be on the road. Although any one vehicle's plug availability is unpredictable, the availability of thousands or tens of thousands of vehicles is highly predictable and can be estimated from traffic and road-use data. For example, peak late-afternoon traffic occurs during the hours when electric use is highest (from 3-6 p.m.). A supposition one might have from personal experience, that the majority of the vehicles are on the road during rush hour traffic, is false. Based on road use data, we have calculated that over 92 percent of vehicles are parked and thus potentially available to the grid during any given hour, including the peak traffic hours of 3-6 PM (Kempton et al. 2001).


Economic Value of V2G

V2G opportunities and their financial value vary with the type of vehicle and the power market. Battery EDVs can store electricity, charging during low demand times and discharging when power is scarce and prices are high. Of potentially greater value, they can also provide ancillary services, notably regulation up, regulation down, and spinning reserves. Figure 2 illustrates power flow and battery state of charge for a battery EDV being used for regulation up and regulation down. The figure applies to a vehicle used for commuting and that is plugged in at home and work. The two large spikes of power out of the battery at 8 a.m. and 5 p.m. are the commute trip (brief negative driving spikes result from regenerative braking). Since both regulation up and regulation down are provided, the net effect on battery charge is minimal, except after each commute, when regulation is controlled to provide a net charge.

Fuel cell and hybrid EDVs are a somewhat different case than battery powered EDVs in that they represent a new source of power generation. Our earlier analyses suggested that vehicles could not compete for baseload power, but could be competitive when called upon to provide peak power and ancillary services (Kempton and Letendre 1997, 1999; Kempton and Kubo 2000). Consequently, the values reported below derive from V2G in the day-ahead market for power (during peak periods), spinning reserves, and regulation. The values presented here were derived using market-clearing prices in California's competitive electricity markets (but do not rely on prices in the atypical year 2000).

Formulas were derived to calculate the power capacity of each vehicle type. Calculated capacity depends on the charger capacity, residential and commercial electrical service capacity, fuel or electricity needed for the next trip, whether a piped gaseous fuel source is connected to the vehicle,

Figure 2: Power Flow and State of Charge
How an electric vehicle provides regulation services.




Source: Brooks and Gage, 2001

IPR2025-00032
Tesla EX1007 Page 11

and other factors. All vehicle technical parameters were derived from production or prototype EDVs. The battery vehicles have power capacity on the order of 10 kW and fuel cell vehicles have up to approximately 40 kW. The hybrid vehicles are of interest when operating in the motor-generator mode, fueled by gasoline or a natural gas line, with power capacity up to 30 kW. For many scenarios, output is limited by line capacity to the existing 6 kW charging stations (Level 2), or near term standards that allow 16 kW (Level 3AC charger).

A key element regarding the economics of V2G is the cost of electricity generated by each EDV type. We calculate that battery vehicles can provide electricity to the grid at a cost of $0.23/kWh for current lead-acid batteries, $0.45/kWh for the Honda EV Plus with nickel metal hydride (NiMH) batteries, and $0.32/kWh for the Th!nk City car with nickel cadmium (NiCd) battery. The fuel cell vehicle can generate electricity at a cost ranging between $0.09—$0.38 kWh, the wide range being due to the projected costs of H_2, with the lower figure based on the longer-term assumption of a mature hydrogen market. A fuel cell vehicle with hydrogen recharge through a garage reformer could generate electricity at $0.19/kWh from natural gas (at $0.84/therm). The hybrid vehicles in motor-generator mode can generate electricity at a cost of $0.21/kWh if fueled with gasoline (at $1.50 per gallon) and at $0.19/kWh if fueled with natural gas. Based only on these simple costs per kWh, it appears that in the near term the most attractive EDV types are the lead-acid battery vehicles, a fuel cell vehicle recharged from a natural gas reformer, and the hybrid vehicle. However, to understand the best niche for V2G power, the simple per kWh cost comparison is inadequate.

The cost of electricity from the EDVs noted above is too high to be competitive with baseload power. However, EDV power could be competitive in three other markets: peak power, spinning reserves,



IPR2025-00032
Tesla EX1007 Page 12

Hydrogen Power: A New Initiative, a New Fuel Cell Car

Against a backdrop of futuristic vehicles at the Detroit Auto Show, Secretary of Energy Spencer Abraham and executives of Ford, General Motors and DaimlerChrysler in early January announced a new cooperative automotive research partnership between the DOE and the U.S. Council for Automotive Research (USCAR). The new public-private partnership will promote the development of hydrogen as a primary fuel for cars and trucks, as part of U.S. efforts to reduce dependence on foreign oil.

Of those futuristic vehicles, General Motors unveiled its Autonomy fuel cell car, which it says is the first vehicle designed exclusively for the fuel cell. After a century of making gasoline-burning cars, General Motors sees a not-so-distant future when vehicles powered by hydrogen will revolutionize the industry and make transportation more affordable for the world's population.

Because fuel cells consume hydrogen and emit only water and heat, automakers have talked for years about the arrival of the cleaner technology over the next decade as a way to make cars more environmentally friendly and curtail the need for foreign oil.


The Autonomy houses all the essential elements of the car, including the fuel cell to provide power, in a skateboard-like chassis between the four wheels and under the body and seats of the vehicle. The chassis could be fitted with a wide variety of bodies, such as a minivan interior for a family in the United States, or a pickup truck bed for hauling livestock in China, General Motors says.

Because the Autonomy chassis has a 20-year lifespan, a growing family could change from a sporty sedan to a larger sport utility vehicle simply by switching the body, a far cheaper alternative to buying a new vehicle. Or, if the vehicle needs more power, the fuel cell can be expanded.

A vehicle using the Autonomy chassis could look completely different from those on the road today. Because the gasoline-burning engine is gone and all the controls, such as steering and braking, are operated by electronic wires rather than mechanical connections, car designers are free to come up with new interpretations of cars and trucks. —R.S.



Autonomy's "Skateboard"



Source: General Motors

IPR2025-00032
Tesla EX1007 Page 13

and regulation services. The latter two electricity markets are called "ancillary services," and in each, the power producer is paid a contract price for being connected and available, in addition to per kWh energy payments. Grid operators maintain reserve generating capacity available for immediate power production. The term "spinning" reserves refers to generators spinning and synchronized with the grid, ready for immediate power feed into the grid. Typically, these reserves are called upon when a power plant drops off-line unexpectedly due to equipment failure. By contrast, regulation is needed throughout the day and night. Grid operators must continuously match the generation of power to the consumption. Regulation requires a generating facility that can ramp power up or down under real time control of the grid operator.

In California and a few other power markets, this function, called regulation or automatic generation control (AGC), is unbundled from power generation, and is sold separately. Even when provided internally to a company, regulation has costs—at a minimum, generators must be kept at idle or partial speed.

For each combination of vehicle and power market, we calculate the value of the power in California's electricity markets and the cost to the vehicle owner for providing power, assuming V2G power is produced only when revenue will exceed cost. This method is more comprehensive than earlier methods that used avoided costs (Kempton and Letendre 1997) or retail time-of-use rates (Kempton and Kubo 2000). Other benefits, including reduced air pollution, increased reliability of the electric system, and other distributed benefits (i.e., reduced line losses and avoidance of transmission and distribution upgrades) are not included in the economic calculations, nor are transaction costs. Calculation of vehicle owner costs is comprehensive, including capital costs of any additional equipment required, fuel, and shortening of battery pack and internal

Fuel cell and hybrid EDVs are a somewhat different case than battery powered EDVs in that they represent a new source of power generation.

Table 1: Vehicle owner's annual net profit from V2G

These are representative mid-range figures extracted from full analysis in the report.

	Peak power	Spinning reserves	Regulation services
Battery, full function	$267 (510—243)	$720 (775—55)	$3,162 (4479—1317)
Battery, city car	$75 (230—155)	$311 (349—38)	$2,573 (4479—1906)
Fuel cell, on board H_2	$-50 (loss) to $1,226 (2200—974 to 2250)	$2,430 to $2,685 (3342—657 to 912)	$-2,984 (loss) to $811 (2567—1756 to 5551)
Hybrid, gasoline	$322 (1500—1178)	$1,581 (2279—698)	$-759 (loss) (2567—3326)

Source: Kempton et al, 2001

IPR2025-00032
Tesla EX1007 Page 14

combustion engine lifetime due to additional use.

Some key V2G economic results are summarized in Table 1. From Table 1, one notices that some vehicles are better suited than others for individual power markets. Matching the vehicle type to power market is important, as it is possible to both gain and lose money.

Taking the three markets in turn, peak power is the least promising. In our model, battery-powered vehicles serve the peak power market by charging their batteries during off-peak hours when price is low (e.g., 4.5 ¢/kWh) and selling power to the grid when the price is high (e.g., over 30 ¢/kWh). The fueled vehicles sell peak power when power prices are above the costs to produce power. Although the table shows potential profits by the historical rule of thumb, for two of the three years of actual market prices from California's now defunct Power Exchange, we find that the price was never high enough to justify selling electricity in the bulk power market during peak price periods.

Spinning reserves shows economic viability for most vehicles we analyzed, and for all those shown in Table 1. Net revenues for the spinning reserve market is particularly large for the fueled vehicles and is relatively insensitive to fuel prices because a large portion of the revenue stream is from contract payments for time available, rather than for power generated.

Regulation services involve higher numbers, for both revenue and cost, because vehicles can sell regulation more of the time. The battery vehicles appear to be especially suitable for regulation. This is because regulation demands shallower cycling than peak or spinning reserves, thus causing less battery degradation. Also, batteries experience very little net discharge when providing both regulation up and regulation down. The estimated net value of regulation services from battery EDVs is several thousand dollars per year. Fuel cell vehicles and hybrids in motor-generator mode could provide only regulation up, not down, and the economics are not attractive.

Vehicles can provide ancillary services of a higher quality than currently available—fast response, available in small increments, and distributed. In a recent presentation, California Independent System Operator (ISO) staff described several possible advantages of V2G over current methods: Fast response to AGC signals, improved frequency control, less wear and tear on generators, and the possibility of frequency response service and line overload relief (Hawkins 2001). Possible concerns to study include the impact on distribution systems, making V2G visible to the EMS system, and generally, the lack of experience of system operators with distributed resources. An additional consideration by the Califonia ISO is that V2G appears to be "an ideal complement to wind generation," since the regulation function of battery EDVs can be used to smooth out small or unexpected fluctuations in wind power production (Hawkins 2001). Thus, the demand for and value of V2G grid services may increase in the future, as intermittent, renewable energy resources become a larger fraction of electric generation.

Over just a decade or two, V2G could revolutionize the ancillary services market, improve grid stability and reliability, and support increased generation from intermittent renewables.

As the V2G-capable EDV fleet grows, it will begin to saturate existing ancillary service markets. We estimate that in California the market for regulation services, the highest value market, could be met with 109,000 to 174,000 vehicles, and spinning reserves with an additional 76,000 to 273,000 vehicles. Peak power could be a still larger market, but only at lower V2G costs than we currently project. These vehicle saturation numbers represent a small fraction of the total vehicle fleet in California, but they should be sufficient to stimulate more than a decade of projected sales, past the time that production volumes bring down EDV sticker prices.

IPR2025-00032
Tesla EX1007 Page 15

Conclusions

Overall, we conclude that all three types of EDVs—battery, hybrid, and fuel cell—could become a significant component of the nation's electric grid. The largest value is in ancillary services such as spinning reserves and regulation. For battery and fuel cell vehicles, and possibly plug-in hybrids, the net value of this power is over $2,000 annually per vehicle, enough to quickly and economically usher in the era of a low- and zero-pollution light vehicle fleet.

Several policy issues are raised by this analysis. Initially, demonstration projects would help answer questions which are not amenable to the modeling approach presented here. Also, some policy review would be helpful now. From the electric industry side, it would be appropriate to review rate structures and interconnect and safety standards in order to assess changes or additions appropriate for V2G power. Interconnection standards are currently being addressed to accommodate emerging distributed energy technologies (e.g., photovoltaics, stationary fuel cells, and micro-turbines). Charging station infrastructure planning should similarly be reviewed for its application to V2G power (as CARB has already done for California).

Individual utilities acquiring electric-drive vehicle fleets might start by reviewing their buying specifications. With the low incremental cost of adding V2G at the design stage—and with products already on the market—now may be the time to add V2G as a specification for new purchases. Utilities may start to ask, why not have our fleet of customer service or meter-reader vehicles providing regulation services while parked? If experience with utility-fleet vehicles providing V2G is positive, the next questions might be: How much vehicle ancillary service do we want to acquire in total? Do we want an aggregator to sell us MW blocks, or is aggregation an interesting opportunity for one of our business units?

Over just a decade or two, V2G could revolutionize the ancillary services market, improve grid stability and reliability, and support increased generation from intermittent renewables. The associated revenue stream could make electric-drive vehicles more attractive to buyers. These synergistic developments could have substantial benefits to the electric industry, to the environment, and to society as a whole. F

Steven Letendre is a professor of management and environmental studies at Green Mountain College in Poultney, VT. He has worked as a utility economist at the Research Triangle Institute in North Carolina, and is the author of numerous articles on distributed generation and economics and electric utility policy. Willett Kempton teaches and conducts research on environmental policy at the University of Delaware. He is senior policy scientist in the university's Center for Energy and Environmental Policy, and is an associate professor in the College of Marine Studies.

References

Alec Brooks, Tom Gage, 2001, "Integration of Electric Drive Vehicles with the Electric Power Grid — a New Value Stream". Paper presented at the 18th International Electric Vehicle Symposium and Exhibition, 20-24 October 2001, Berlin, Germany. (Full written version available from http://www.acpropulsion.com/EVS18/ACP_V2G_EVS18.pdf)

Electric Power Research Institute (EPRI) (2001) Press release available at http://www.epri.com/corporate/discover_epri/news/2001releases/010219_car.html

David Hawkins, 2001, "Vehicle to Grid—A Control Area Operators Perspective." Presentation at the EVAA Electric Transportation Industry Conference, Sacramento, CA, December 2001. Presentation slides available at: http://www.acpropulsion.com/ETI_2001/Hawkins_ETI.pdf

Kempton, W. and Steven Letendre, (1997) "Electric vehicles as a new power source for electric utilities." Transportation Research. Part D, Transport and Environment. 2 (3): 157-175.

Kempton W, Kubo T, (2000) "Electric-drive vehicles for peak power in Japan," Energy Policy 28: 9—18. (Available in Japanese translation at http://www.udel.edu/V2G)

Kempton W, Letendre S, (1999) "Electric Vehicles' value if integrated with the utility system," Presented at Transportation Research Board, 78th annual Meetings, Washington DC. TRB Paper #P993734.

W. Kempton, J. Tomic, S. Letendre, A. Brooks, and T. Lipman. (2001) "Vehicle-to-Grid Power: Battery, Hybrid, and Fuel Cell Vehicles as Resources for Distributed Electric Power in California." Davis, CA: Institute of Transportation Studies Report # IUCD-ITS-RR 01-03. 77+xiv pages. PDF version available at http://www.udel.edu/V2G

Acknowledgments

This article draws from a report sponsored by the California Air Resources Board (CARB) and the Los Angeles Department of Water and Power (LADWP). This report is available in PDF (Portable Document Format) at the our web site, which also has other documents and resources on vehicle-to-grid power, http://www.udel.edu/V2G. We would like to acknowledge our collaborators on the CARB/LADWP project: Jasna Tomic, University of Delaware; Alec Brooks and Tom Gage, AC Propulsion, and Timothy Lipman, University of California, Berkeley and Davis. Notification: The statements and conclusions in this article based on the above-cited report are those of the contractor and not necessarily those of the California Air Resources Board, and the mention of commercial products, their use in connection with material reported herein is not to be construed as actual or implied endorsement of such products.

IPR2025-00032
Tesla EX1007 Page 16

CUST. LOT NO.	ITEM NO.	DEPARTMENT	CATEGORY	BINDING CLASS	BINDERY JOB / PIECE NO.
9-19-A	111		serial	excel-stan...	

CUSTOMER #	TITLE I.D.	COLLECTION
0221700	6075	

NAME
Western Michigan
Waldo Library
1201 Oliver Street
Kalamazoo, MI 49008

ISSN. / ISBN.	BIND. FREQ.	PUB. FREQ.
ADL0063	1	0

☐ SAVE TITLE (NEW) ☐ PERMANENT CHANGE
☐ DO NOT SAVE TITLE ☐ SAMPLE / RUB SENT

PID	LEAF
TITLE PAGE	FRONT COVER
TABLE CONT.	BACK COVER
INDEX	ADS

INSTRUCTIONS

☐ IMPRINT ☐ PANEL LINES
☐ RECASE / NEW COVER ☐ HAND TRIM
☐ SEW THRU FOLD ☐ BIND AS IS
☐ ADHESIVE BIND ☐ POCKET / CLOTH
☐ MOUNT COVER ☐ POCKET / PAPER

LEVEL	SPINE LETTERING
26	PUBLIC
	UTILITIES
	FORTNIGHTLY
14	140
9	JAN.
	-JUNE
7	2002
5	HD
4	2763
3	.A2
2	P8x

62 351 WM 2679
09/02 XL 02-217-00 GBC

SET OF	DATE SENT
1	
COVER COLOR	PRINT DATE
490	091002
PRINT COLOR	ENTRY DATE
W	SMAN
HEIGHT	UPDATE
0-0/16	
WIDTH	SPINE
0-0/16	0-0/16

BINDERY USE ONLY

☐ HAND TRIM ☐ SP. BK CUT
☐ STF (MACH) ☐ STUBBING
☐ STF (HAND) ☐ SEPARATORS
☐ STF (SINGLE) ☐ MENDING
☐ RECASE ☐ REM. STAPLES
☐ PKT / PAPER ☐ TRIM XRX. PGS.
☐ MOUNT COVER ☐ FOLD XRX. PGS.
☐ ALL ADS OUT ☐ ENTERING
☐ IMPRINT ☐ PANEL LINES
☐ EXTRA TIME _____ MIN.
REASON _____

BOOK ☐

TYPE OF MATERIAL - PLEASE DESIGNATE ☑

☐ STANDARDIZED BOOK (NO COLOR / FOIL CHOICE)
☐ CUSTOM BOOK (CHOICE OF COLOR / FOIL)
☐ THESIS (CHOICE OF COLOR AND / OR FOIL)
☐ OTHER
☐ MUSIC BOOK / SCORE (CHOICE OF COLOR / FOIL)
☐ FLEXBIND-S PAPERBACK (NO COLOR CHOICE)
☐ FLEXBIND-M PAPERBACK (MYLAR)

recyclable

BAR CODE DATA

BINDERY COPY