US009158494B2

(12) **United States Patent**
Sirpal et al.

(10) **Patent No.: US 9,158,494 B2**
(45) **Date of Patent: Oct. 13, 2015**

(54) **MINIMIZING AND MAXIMIZING BETWEEN PORTRAIT DUAL DISPLAY AND PORTRAIT SINGLE DISPLAY**

(75) Inventors: **Sanjiv Sirpal**, Oakville (CA); **Mohammed Selim**, Oakville (CA)

(73) Assignee: **Z124**, George Town (KY)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 494 days.

(21) Appl. No.: **13/366,483**

(22) Filed: **Feb. 6, 2012**

(65) **Prior Publication Data**

US 2013/0080929 A1 Mar. 28, 2013

Related U.S. Application Data

(60) Provisional application No. 61/539,884, filed on Sep. 27, 2011.

(51) **Int. Cl.**
G06F 3/048 (2013.01)
G06F 3/14 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC ***G06F 3/1423*** (2013.01); ***B29D 11/00673*** (2013.01); ***E05D 3/12*** (2013.01); ***G02B 6/0001*** (2013.01); ***G06F 1/1601*** (2013.01); ***G06F 1/1616*** (2013.01); ***G06F 1/1637*** (2013.01); ***G06F 1/1641*** (2013.01); ***G06F 1/1692*** (2013.01); ***G06F 3/01*** (2013.01); ***G06F 3/041*** (2013.01); ***G06F 3/048*** (2013.01); ***G06F 3/0412*** (2013.01); ***G06F 3/0481*** (2013.01); ***G06F 3/0483*** (2013.01); ***G06F 3/04883*** (2013.01); ***G06F 3/04897*** (2013.01); ***G06F 9/44*** (2013.01); ***G06F 9/4443*** (2013.01); ***G06T 3/00*** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC G06F 3/048
USPC 715/760, 761
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,157,763 A 10/1992 Peters et al.
5,889,517 A 3/1999 Ueda et al.
(Continued)

FOREIGN PATENT DOCUMENTS

EP 1648149 4/2006
WO WO 2010/028403 3/2010
(Continued)

OTHER PUBLICATIONS

U.S. Appl. No. 13/187,026, filed Jul. 20, 2011, Chen.
(Continued)

Primary Examiner — Andrea Leggett
(74) *Attorney, Agent, or Firm* — Sheridan Ross P.C.

(57) **ABSTRACT**

Methods and devices for minimizing and maximizing displayed output associated with applications are provided. More particularly, an application presented as two or more pages in a portrait mode can be minimized to present one of the two or more pages following a minimization operation. The page that continues to be displayed can comprise a primary or preferred page, while the page that is dismissed can comprise a secondary or ancillary page. With respect to a maximization operation received with respect to a page of an application results in the display of an additional page associated with that application. Maximization can include controlling the respective screens on which first and second pages of the maximized application are displayed.

20 Claims, 51 Drawing Sheets



GOOGLE EXHIBIT 1001

(51) **Int. Cl.**

G09G 5/34	(2006.01)
H04M 1/02	(2006.01)
G06F 1/16	(2006.01)
G09G 5/00	(2006.01)
G06F 3/041	(2006.01)
G09G 1/00	(2006.01)
H05K 5/02	(2006.01)
H05K 5/00	(2006.01)
H05K 13/00	(2006.01)
H04N 5/445	(2011.01)
H05K 7/02	(2006.01)
E05D 3/12	(2006.01)
H05K 13/04	(2006.01)
H05K 5/04	(2006.01)
H05K 7/14	(2006.01)
B29D 11/00	(2006.01)
F21V 8/00	(2006.01)
G06F 3/01	(2006.01)
G06F 3/0489	(2013.01)
G06T 3/00	(2006.01)
G06F 9/44	(2006.01)
G06F 3/0481	(2013.01)
G06F 3/0483	(2013.01)
G06F 3/0488	(2013.01)
G09G 5/14	(2006.01)
H04W 72/06	(2009.01)
H04W 88/06	(2009.01)
H04W 48/18	(2009.01)

(52) **U.S. Cl.**

CPC .. ***G09G 1/00*** (2013.01); ***G09G 5/00*** (2013.01); ***G09G 5/14*** (2013.01); ***G09G 5/34*** (2013.01); ***H04M 1/0266*** (2013.01); ***H04N 5/44591*** (2013.01); ***H04W 72/06*** (2013.01); ***H04W 88/06*** (2013.01); ***H05K 5/0017*** (2013.01); ***H05K 5/0226*** (2013.01); ***H05K 5/04*** (2013.01); ***H05K 7/02*** (2013.01); ***H05K 7/1452*** (2013.01); ***H05K 13/00*** (2013.01); ***H05K 13/046*** (2013.01); *G06F 3/1438* (2013.01); *G06F 3/1446* (2013.01); *H04W 48/18* (2013.01)

USPC **715/761**; 715/760

(56) **References Cited**

U.S. PATENT DOCUMENTS

7,137,074	B1	11/2006	Newton et al.
7,636,899	B2	12/2009	Purcell et al.
7,739,604	B1	6/2010	Lyons et al.
8,108,782	B2	1/2012	Rajpal et al.
8,290,540	B2	10/2012	Kittel et al.
8,300,022	B2	10/2012	Brenneman et al.
8,385,057	B2	2/2013	Liu et al.
8,423,911	B2	4/2013	Chaudhri
2002/0021278	A1	2/2002	Hinckley et al.
2002/0089505	A1	7/2002	Ording
2002/0140698	A1	10/2002	Robertson et al.
2002/0140746	A1	10/2002	Gargi
2004/0066408	A1	4/2004	Meyers et al.
2004/0095401	A1	5/2004	Tomimori
2006/0085384	A1	4/2006	Sato et al.
2006/0183505	A1	8/2006	Willrich
2007/0036346	A1	2/2007	Kwon
2007/0048717	A1	3/2007	Hsieh
2007/0234222	A1	10/2007	Yamaguchi et al.
2008/0096593	A1	4/2008	Park
2008/0111822	A1	5/2008	Horowitz et al.
2008/0119237	A1	5/2008	Kim
2008/0148152	A1	6/2008	Blinnikka et al.
2008/0152297	A1	6/2008	Ubillos
2008/0165152	A1	7/2008	Forstall et al.
2008/0204424	A1	8/2008	Jin et al.
2008/0307350	A1	12/2008	Sabatelli et al.
2009/0061970	A1	3/2009	Wylie et al.
2009/0113330	A1	4/2009	Garrison et al.
2009/0143141	A1	6/2009	Wells et al.
2009/0177617	A1	7/2009	Lee
2009/0199128	A1	8/2009	Matthews et al.
2009/0204925	A1	8/2009	Bhat et al.
2009/0278806	A1	11/2009	Duarte et al.
2009/0298418	A1	12/2009	Michael et al.
2009/0307623	A1	12/2009	Agarawala et al.
2009/0319672	A1	12/2009	Reisman
2010/0007603	A1	1/2010	Kirkup
2010/0064244	A1	3/2010	Kilpatrick, II et al.
2010/0064536	A1	3/2010	Caskey et al.
2010/0079355	A1	4/2010	Kilpatrick et al.
2010/0081475	A1	4/2010	Chiang et al.
2010/0085274	A1	4/2010	Kilpatrick, II et al.
2010/0085382	A1*	4/2010	Lundqvist et al. 345/659
2010/0144433	A1	6/2010	Yamada et al.
2010/0146422	A1	6/2010	Seong et al.
2010/0146428	A1	6/2010	Ng et al.
2010/0169822	A1	7/2010	Hollemans
2010/0182247	A1	7/2010	Petschnigg et al.
2010/0188352	A1	7/2010	Ikeda
2010/0211872	A1	8/2010	Rolston et al.
2010/0245106	A1	9/2010	Miller et al.
2010/0245209	A1	9/2010	Miller et al.
2010/0289826	A1	11/2010	Park et al.
2011/0107272	A1	5/2011	Aguilar
2011/0119611	A1	5/2011	Ahn et al.
2011/0143769	A1	6/2011	Jones et al.
2011/0167380	A1	7/2011	Stallings et al.
2011/0187662	A1	8/2011	Lee et al.
2011/0193806	A1	8/2011	Kim et al.
2011/0202834	A1	8/2011	Mandryk et al.
2011/0237303	A1	9/2011	Matsuda
2012/0081268	A1	4/2012	Sirpal et al.
2012/0081271	A1	4/2012	Gimpl et al.
2012/0081280	A1	4/2012	Schrock et al.
2012/0081309	A1	4/2012	Sirpal et al.
2012/0081311	A1	4/2012	Sirpal et al.
2012/0081400	A1	4/2012	Schrock et al.
2012/0084675	A1	4/2012	Sirpal et al.
2012/0084710	A1	4/2012	Sirpal et al.
2012/0117495	A1	5/2012	Sirpal et al.
2012/0124490	A1	5/2012	Sirpal et al.
2012/0124515	A1	5/2012	Li et al.
2012/0266098	A1	10/2012	Webber
2013/0079062	A1	3/2013	Sirpal et al.
2013/0097532	A1	4/2013	Reeves et al.

FOREIGN PATENT DOCUMENTS

WO	WO 2012/044780	4/2012
WO	WO 2012/044801	4/2012
WO	WO 2012/044809	4/2012

OTHER PUBLICATIONS

U.S. Appl. No. 13/624,591, filed Sep. 21, 2012, Sirpal et al.

U.S. Appl. No. 13/627,577, filed Sep. 26, 2012, Sirpal et al.

U.S. Appl. No. 13/629,211, filed Sep. 27, 2012, Reeves et al.

Burns, "Motorola ATRIX 4G Laptop Dock Review," at www.androidcommunity.com/motorola-atrix-4g-laptop-dock-review-20110220/, Feb. 20, 2011, 5 pages.

Catacchio, "This smartphone has two huge screens . . . that rotate," The Next Web at www.thenextweb.com/asia/2010/10/07/this-smartphone-has-two-huge-screens-that-rotate/, Jul. 21, 2011, 2 pages.

Google images, accessed Apr. 18, 2011, 6 pages.

Harman03, "Kyocera Echo Dual-screen Android Phone," posted 4 weeks from Apr. 18, 2011, 3 pages.

"Lapdock™ for Motorola ATRIX," at www.motorola.com/Consumers/US-EN/Consumer-Product-and-Services/Mobile . . . , accessed Apr. 18, 2011, 1 page.

(56) **References Cited**

OTHER PUBLICATIONS

"Motorola ATRIX 4G Laptop Dock Review," at www.phonearena.com/reviews/Motorola-ATRIX-4G-Laptop-Dock-Review_id2667, Mar. 2, 2011, 6 pages.
Stein, S., "How does the Motorola Atrix 4G Lapdock compare with a laptop?" Crave—CNET, at www.news.cnet.com/8301-17938_105-20031251-1.html, Feb. 9, 2011, 7 pages.
Website entitled, "Kyocera Echo," at www.echobykyocera.com/, 2011, 6 pages.
Website entitled, "Sony Tablet," at www.store.sony.com/webapp/wcs/stores/servlet/CategoryDisplay?catalogId=10551&storeId=10151&langId=-1&categoryId=8198552921644795521, 2011, 3 pages.
International Search Report and Written Opinion for International Patent Application No. PCT/US11/53942, mailed Feb. 21, 2012, 8 pages.
International Search Report and Written Opinion for International Patent Application No. PCT/US11/53902, mailed Feb. 22, 2012, 9 pages.
International Search Report and Written Opinion for International Patent Application No. PCT/US11/53963, mailed Feb. 22, 2012, 7 pages.
Soegaard, "Affordances." Interaction Design Foundation, (2010), 7 pages, [Retrieved May 29, 2013 from www.interaction-design.org/encyclopedia/affordances.html].
International Preliminary Report on Patentability for International (PCT) Patent Application No. PCT/US2011/053942, mailed Apr. 11, 2013 7 pages.
International Preliminary Report on Patentability for International (PCT) Patent Application No. PCT/US2011/053902, mailed Apr. 11, 2013 8 pages.
International Preliminary Report on Patentability for International (PCT) Patent Application No. PCT/US2011/053963, mailed Apr. 11, 2013 6 pages.
Official Action for U.S. Appl. No. 13/247,982, mailed Aug. 15, 2013 14 pages.
Official Action for U.S. Appl. No. 13/247,797, mailed Sep. 12, 2013 13 pages.
Notice off Allowance for U.S. Appl. No. 13/247,797, mailed Oct. 11, 2013 13 pages.
Official Action for U.S. Appl. No. 13/247,369, mailed Oct. 10, 2013 16 pages.
Official Action for U.S. Appl. No. 13/223,778, mailed Jun. 6, 2013 38 pages.
Official Action for U.S. Appl. No. 13/223,778, mailed Nov. 7, 2013 37 pages.
Extended European Search Report for European Patent Application No. 11829892.6 dated Jul. 2, 2014, 7 pages.
Official Action for U.S. Appl. No. 13/247,982 mailed Feb. 5, 2014. 13 pages.
Official Action for U.S. Appl. No. 13/247,369 mailed May 2, 2014 21 pages.
Official Action for U.S. Appl. No. 13/629,211 mailed Apr. 17, 2014, 14 pages.
"iPhone User Guide for iPhone OS 3.1 Software," Apple Inc., 2009, 217 pages.
Ritchie, "iOS 4 features: Background app killing," imore.com, Aug. 10, 2010 [retrieved Dec. 14, 2013], 3 pages. Retrieved from: www.imore.com/ios-4-features-background-app-killing.
Official Action for U.S. Appl. No. 13/247,982 mailed Nov. 13, 2014, 17 pages.
Official Action for U.S. Appl. No. 13/247,369 mailed Jan. 7, 2015 7 pages.
Official Action for U.S. Appl. No. 13/624,591, mailed Dec. 4, 2014, 27 pages.
Official Action for U.S. Appl. No. 13/629,211 mailed Jan. 16, 2015, 16 pages.
"Windows Media Player 10 Mobile for Smartphone." Microsoft Corporation, 2004, 20 pages.
Official Action for U.S. Appl. No. 13/247,208, mailed Sep. 12, 2014, 8 pages.
Official Action for U.S. Appl. No. 13/223,778, mailed Oct. 3, 2014 42 pages.
Official Action for U.S. Appl. No. 13/627,577, mailed Aug. 1, 2014 18 pages.
Notice of Allowance for U.S. Appl. No. 13/627,577, mailed Nov. 26, 2014 11 pages.
Official Action for U.S. Appl. No. 13/629,211 mailed Oct. 16, 2014, 14 pages.
Notice of Allowance for U.S. Appl. No. 13/247,982, mailed May 28, 2015, 8 pages.
Official Action for U.S. Appl. No. 13/223,778, mailed Apr. 24, 2015 48 pages.
Official Action for U.S. Appl. No. 13/624,591, mailed Jun. 19, 2015, 34 pages.
Official Action for U.S. Appl. No. 13/629,211 mailed Jun. 18, 2015, 18 pages.

* cited by examiner


100
168
104
120
160
108
124
110
114
116
112
116c
116b
116a
112a
112b
112c

FIG. 1A


100
168
104
120
108
124
110
114
112
116
112a
112b
112c
116a
116b
116c

FIG. 1B


100
156
FIG. 1F
100
144
148
152
158
FIG. 1E
100
172b
160
128
176
172a
164
FIG. 1C
100
132
136
140
FIG. 1D


100
172a
172b

FIG. 1G



FIG. 1H



FIG. 1I



FIG. 1J


100
Screen 1
Gesture Capture Region
120
104
Touch Sensitive Display
110
112
Configurable Area
124
Screen 2
Gesture Capture Region
108
Touch Sensitive Display
114
116
Configurable Area
216a
208
212
204
216b
Display Controller
Memory
Data Storage
Processor
Display Controller
220
224
228
Cellular Telephony Module
Power Source and Power control Module
Antenna
232
252
260
256
Other Wireless communication Module
Port Interface
Integrated Audio I/O
236
GPS
Hardware Buttons
Position Sensor(s)
Accelerometer(s)
Image Capture
Audio I/O Interface
I/O Module
158
172
176
240
244
248

FIG. 2


100
336
Docked
340
Landscape
304
Closed
332
Transition
Transition
308
328
Image/
Video
Capture
312
Easel
100
324
Inbound/
Outbound
call
316
Modified
Easel
320
Open
100
344
Docked
348
Landscape

FIG. 3A

376 352 356 360

		PORTRAIT						LANDSCAPE					
		OPEN	CLOSED	EASEL	MODIFIED EASEL	PHONE	IMAGE / VIDEO	OPEN	CLOSED	EASEL	MODIFIED EASEL	PHONE	IMAGE / VIDEO
PORTRAIT	OPEN	X	HT	HT	HT	P	I	AT	HAT	HAT	HAT	P	I
	CLOSED	HT	X	HAT	HAT	P	I	HAT	AT	HAT	HAT	P	I
	EASEL	HT	HT	X	X	P	I	HAT	HAT	HAT	HAT	P	I
	PHONE	HT	X	HT	HT	X	I	HAT	HAT	HAT	HAT	X	I
	IMAGE / VIDEO	HT	HT	HT	X	P	X	HAT	HAT	HAT	HAT	X	HAT
LANDSCAPE	OPEN	AT	HAT	HAT	HAT	P	I	X	HT	HAT	HAT	P	I
	CLOSED	HAT	AT	HAT	HAT	P	I	HT	X	HAT	HAT	P	I
	EASEL	HAT	HAT	HAT	HAT	P	I	HT	HT	X	HAT	P	I
	MODIFIED EASEL	HAT	HAT	HAT	HAT	P	I	HT	HT	HAT	X	P	I
	IMAGE / VIDEO	HAT	HAT	HAT	HAT	HAT	AT	HT	HT	HT	HAT	P	X
	DOCKED	DOCKING SIGNAL											

364 368 372

Key:
H - Hall Effect Sensor(s)
a - accelerometer(s)
T- Timer
P – communications Trigger
I – Image / Video capture Request

FIG. 3B

Tap



FIG. 4A

Long Press



FIG. 4B

Drag



FIG. 4C

Flick



FIG. 4D

Pinch



FIG. 4E

Spread



FIG. 4F


420
432a
428b
432b
400
428a
412
436

FIG. 4G


432a
432b
400
428b
420
416
428a
436

FIG. 4H


500
Memory
Framework
Multi-Display Management Module
Window Management Module
Window Stack
Task Management Module
Task Stack
Application Model Manager
Input Management Module
Event Buffer
Display Controller
Surface Cache Module
Operating System
Application Manager
Desktop
Application Store
Application 1 564a
Application 2 564b
Kernel
Frame Buffers
Driver 1
Driver 2
Driver 3
Processor
504
508
516
518
520
524
532
540
542
544
548
550
552
556
560
562
566
512a
512b
512c
528
536

FIG. 5A


524
Multi-Display Management Module
568
Display Configuration Module
572
Preferences Module
574
Device State Module
576
Gesture Module
580
Requirements Module
584
Event Module
588
Binding Module

FIG. 5B



FIG. 6B



FIG. 6A



FIG. 6C



FIG. 6E



FIG. 6D



FIG. 6F



FIG. 6H



FIG. 6G



FIG. 6I



FIG. 6J


700
760
764
722
Desktop 1 (Touch Sensitive Display 1)
724
Inactive Window 6 (Touch Sensitive Display 1)
720
Inactive Window 5 (Touch Sensitive Display 1)
704
Active Window 1 (Touch Sensitive Display 1)
708
Active Window 2 (Touch Sensitive Display 2)
712
Inactive Window 3 (Touch Sensitive Display 2)
716
Inactive Window 4 (Touch Sensitive Display 2)
718
Desktop 2 (Touch Sensitive Display 2)

FIG. 7A


728
744
740
732
736
748
752
756
758
Window 1
(Inactive)
Window 2
(Inactive)
Window 3
(Active -- Touch Sensitive
Display 1 & 2)
Window 4
(Inactive)
Window 5
(Inactive)
Window 6
(Inactive)
Desktop
(Active -- Touch Sensitive
Display 1 & 2)

FIG. 7B


760
768
770
764
774
Composite Display
(Touch Sensitive Display 1 & 2)
Active Window 3
Active Window 4
Active Window 8

FIG. 7C


774
770
778
782
786
Window 8
Window 7
Window 4
Window 6
Window 2
Window 5
Window 1
Desktop
Window 3
760
768

FIG. 7D


790
774
Window 8
Window 7
Window 6
Window 5
Window 4
Window 2
Window 3
Window 1
Desktop
760
770
778
768
782
786

FIG. 7E


800
804
Window Identifier
808
Dimensions
812
Stack Position Identifier
816
Display Identifier
820
Active Indicator
824
828

FIG. 8


900
904
Start
908
Receive activation of a window
912
Determine associated display
916
Determine position in stack
920
Generate logic structure
924
End

FIG. 9



FIG. 10



FIG. 11



FIG. 12



FIG. 13A



FIG. 13B



FIG. 14



FIG. 15


1000
1004
1010
Dual Screen Application – Max Mode Portrait
1020
1008
1012a
1012b
1012c

FIG. 16


1000
1010
1704
1708
Dual Screen Application – Max Mode Landscape
Window 1
Window 2

FIG. 17


1000
1004
1010
1808
Application Area
1804
1 2 3 4 5 6 7 8 9 0
Q W E R T Y U I O P
A S D F G H J K L
SHIFT Z X C V B N M DEL
?123 @ . Enter

FIG. 18


1000
1004
1010
1908
Application Area
Max Mode
1804
1 2 3 4 5 6 7 8 9 0
Q W E R T Y U I O P
A S D F G H J K L
SHIFT Z X C V B N M DEL
?123 @ . Enter

FIG. 19


1000
1010
2004
Application Area
Type to Compose
1 2 3 4 5 6 7 8 9 0
Q W E R T Y U I O P
A S D F G H J K L
SHIFT Z X C V B N M DEL
?123 @ . Enter
1804

FIG. 20


1000
2104
2108
Application Area
1
Application Area
2
1 2 3 4 5 6 7 8 9 0
Q W E R T Y U I O P
A S D F G H J K L
SHIFT Z X C V B N M DEL
?123 @ . Enter
1804

FIG. 21



FIG. 22



FIG. 23



FIG. 24



FIG. 25



FIG. 26



FIG. 27



FIG. 28



FIG. 29


1000
2618
3008
Application Area
3004
1 2 3 4 5 6 7 8 9 0
Q W E R T Y U I O P
A S D F G H J K L
SHIFT Z X C V B N M DEL
?123 @ . Enter

FIG. 30



FIG. 31A



FIG. 31B



FIG. 32A



FIG. 32B


S4500
START
S4502
Display Desktop on SP
S4504
Logically Divide Desktop on SmartPad
S4506
Display 1st Screen of Desktop in One Logical Portion of SP Display
S4508
Display 2nd Screen of Desktop in Second Logical Portion of SP Display
S4510
Allow Carousel Movement of "Panels"
S4512
END

FIG. 33


S4600
START
S4602
Display Desktop on SP
S4604
Logically Divide Desktop on SmartPad
S4608
Display 1st Screen of Desktop in One Logical Portion of SP Display
S4610
Display 2nd Screen of Desktop Bridging First and Second Logical Portion of SP Display
S4612
Display 3rd Screen of Desktop in Second Logical Portion of SP Display
S4614
Allow Carousel Movement of "Panels"
S4616
END

FIG. 34


S4800
START
S4802
Enter Multiple Application Mode
S4804
Arrange Stack with One Or More Applications Being Partially Visible Behind a First Application
S4806
Optionally Arrange Stack with One Or More Applications Being Partially Visible Behind a Second Application
S4808
Upon Receipt of Gesture, Allow Carousel-Like Scrolling Through Stack Until End of Stack, or Allow Continuous "Circular" Scrolling through the Stack in an Alternative Embodiment
S4810
END

FIG. 35


4900
4904
Start
4908
Execute (Email Client) application
4912
Create manifest
4916
Receive manifest
4920
Determine application display mode
4924
Set display binding
4928
Provide display binding to the application
4932
Determine if configuration change has occurred?
YES
NO
4936
Determine if an application mode/event has occurred?
YES
NO
4940
End

FIG. 36



Fig. 37A



Fig. 37B



Fig. 38A



Fig. 38B



Fig. 39A



Fig. 39B


Start
No
Open App?
Yes
4004
4008
Present first and second pages
4012
Receive input from user minimizing application?
No
Yes
Continue presentation of primary page, discontinue presentation of ancillary page
4016
4020
Receive input from user maximizing application?
No
4024
Yes
Present first and second pages of application
4028
No
Device powered off?
Yes
End

Fig. 40

MINIMIZING AND MAXIMIZING BETWEEN PORTRAIT DUAL DISPLAY AND PORTRAIT SINGLE DISPLAY

CROSS REFERENCE TO RELATED APPLICATION

The present application claims the benefits of and priority, under 35 U.S.C. §119(e), to U.S. Provisional Application Ser. No. 61/539,884, filed Sep. 27, 2011, entitled "MOBILE DEVICE;" which is incorporated herein by reference in its entirety for all that it teaches and for all purposes.

BACKGROUND

A substantial number of handheld computing devices, such as cellular phones, tablets, and E-Readers, make use of a touch screen display not only to deliver display information to the user but also to receive inputs from user interface commands. While touch screen displays may increase the configurability of the handheld device and provide a wide variety of user interface options, this flexibility typically comes at a price. The dual use of the touch screen to provide content and receive user commands, while flexible for the user, may obfuscate the display and cause visual clutter, thereby leading to user frustration and loss of productivity.

The small form factor of handheld computing devices requires a careful balancing between the displayed graphics and the area provided for receiving inputs. On the one hand, the small display constrains the display space, which may increase the difficulty of interpreting actions or results. On the other, a virtual keypad or other user interface scheme is superimposed on or positioned adjacent to an executing application, requiring the application to be squeezed into an even smaller portion of the display.

This balancing act is particularly difficult for single display touch screen devices. Single display touch screen devices are crippled by their limited screen space. When users are entering information into the device, through the single display, the ability to interpret information in the display can be severely hampered, particularly when a complex interaction between display and interface is required.

SUMMARY

There is a need for a dual multi-display handheld computing device that provides for enhanced power and/or versatility compared to conventional single display handheld computing devices. These and other needs are addressed by the various aspects, embodiments, and/or configurations of the present disclosure. Also, while the disclosure is presented in terms of exemplary embodiments, it should be appreciated that individual aspects of the disclosure can be separately claimed.

Additionally, it is desirable to have a multi-display device that can selectively display pages of information in response to a minimization operation or a maximization operation. More particularly, an application operated in connection with a multi-display device can present information on multiple pages. For instance, where the multi-display device has at least two screens, a first page of the application can be presented on the first screen of the device, while a second page of the application can be presented on the second screen of the device. In response to a minimization operation, the second page of the application can continue to be displayed, while the first page of the application can be dismissed. Where a single page of the application is displayed, user input in the form of a maximization command can result in the first page of the

application being presented by the first screen, and the second page of the application being presented by the second screen. Moreover, the presentation of the first and second pages by the first and second screens respectively can be made, regardless of whether the first or the second screen was presented at the time the input from the user to maximize the application was received, and regardless of the screen on which the first or second page was presented. Accordingly, the application can be controlled in connection with the operation of a multi-display device to preferably present one of multiple pages of output associated with the application.

In some embodiments, a method for controlling a display of a device is provided, the method comprising:

presenting a first page of a first application on a first screen of the device, wherein the first page is a control page;

presenting a second page of the first application on a second screen of the device, wherein the second page is a content page;

receiving a first input from a user, wherein the first input includes an input to minimize the first application to one of the first and second screens of the device, wherein the second page of the first application is displayed by one of the first screen of the device and the second screen of the device, and wherein the first page of the first application is not displayed.

In some embodiments, a device is provided, the device comprising:

a screen, including:

a touch screen display, wherein the touch screen display is located within a first area of the screen;

a gesture capture region, wherein the gesture capture region is located within a second area of the screen;

memory;

a processor;

application programming stored in the memory and executed by the processor, wherein the application programming is operable to:

present a first page of a first application in a first portion of the screen;

present a second page of the first application in a second portion of the screen;

receive input entered by a user in the gesture capture region;

in response to a first input entered by the user to minimize the first application to one of the first and second portions of the screen, present the second page of the first application in one of the first and second portions of the screen and to discontinue the presentation of the first page of the application.

In some embodiments, a computer readable medium having stored thereon computer executable instructions is provided, the computer executable instructions causing a processor to execute a method for selectively presenting an application across a display of a device, the computer executable instructions comprising:

instructions to display a first page of a first application on a first display portion of the device;

instructions to display a second page of the first application on a second display portion of the device;

in response to a first input received from a user to minimize the first application to one of the first and second display portions of the device, display the second page of the first application on one of the first and second display portions of the device and to discontinue the display of the first page of the application.

The phrases "at least one", "one or more", and "and/or" are open-ended expressions that are both conjunctive and disjunctive in operation. For example, each of the expressions

"at least one of A, B and C", "at least one of A, B, or C", "one or more of A, B, and C", "one or more of A, B, or C" and "A, B, and/or C" means A alone, B alone, C alone, A and B together, A and C together, B and C together, or A, B and C together.

The term "a" or "an" entity refers to one or more of that entity. As such, the terms "a" (or "an"), "one or more" and "at least one" can be used interchangeably herein. It is also to be noted that the terms "comprising", "including", and "having" can be used interchangeably.

The term "automatic" and variations thereof, as used herein, refers to any process or operation done without material human input when the process or operation is performed. However, a process or operation can be automatic, even though performance of the process or operation uses material or immaterial human input, if the input is received before performance of the process or operation. Human input is deemed to be material if such input influences how the process or operation will be performed. Human input that consents to the performance of the process or operation is not deemed to be "material".

The term "computer-readable medium" as used herein refers to any tangible storage and/or transmission medium that participate in providing instructions to a processor for execution. Such a medium may take many forms, including but not limited to, non-volatile media, volatile media, and transmission media. Non-volatile media includes, for example, NVRAM, or magnetic or optical disks. Volatile media includes dynamic memory, such as main memory. Common forms of computer-readable media include, for example, a floppy disk, a flexible disk, hard disk, magnetic tape, or any other magnetic medium, magneto-optical medium, a CD-ROM, any other optical medium, punch cards, paper tape, any other physical medium with patterns of holes, a RAM, a PROM, and EPROM, a FLASH-EPROM, a solid state medium like a memory card, any other memory chip or cartridge, a carrier wave as described hereinafter, or any other medium from which a computer can read. A digital file attachment to e-mail or other self-contained information archive or set of archives is considered a distribution medium equivalent to a tangible storage medium. When the computer-readable media is configured as a database, it is to be understood that the database may be any type of database, such as relational, hierarchical, object-oriented, and/or the like. Accordingly, the disclosure is considered to include a tangible storage medium or distribution medium and prior art-recognized equivalents and successor media, in which the software implementations of the present disclosure are stored.

The term "desktop" refers to a metaphor used to portray systems. A desktop is generally considered a "surface" that typically includes pictures, called icons, widgets, folders, etc. that can activate show applications, windows, cabinets, files, folders, documents, and other graphical items. The icons are generally selectable to initiate a task through user interface interaction to allow a user to execute applications or conduct other operations.

The term "screen," "touch screen," or "touchscreen" refers to a physical structure that includes one or more hardware components that provide the device with the ability to render a user interface and/or receive user input. A screen can encompass any combination of gesture capture region, a touch sensitive display, and/or a configurable area. The device can have one or more physical screens embedded in the hardware. However a screen may also include an external peripheral device that may be attached and detached from the device. In embodiments, multiple external devices may be attached to the device. Thus, in embodiments, the screen can enable the user to interact with the device by touching areas on the screen and provides information to a user through a display. The touch screen may sense user contact in a number of different ways, such as by a change in an electrical parameter (e.g., resistance or capacitance), acoustic wave variations, infrared radiation proximity detection, light variation detection, and the like. In a resistive touch screen, for example, normally separated conductive and resistive metallic layers in the screen pass an electrical current. When a user touches the screen, the two layers make contact in the contacted location, whereby a change in electrical field is noted and the coordinates of the contacted location calculated. In a capacitive touch screen, a capacitive layer stores electrical charge, which is discharged to the user upon contact with the touch screen, causing a decrease in the charge of the capacitive layer. The decrease is measured, and the contacted location coordinates determined. In a surface acoustic wave touch screen, an acoustic wave is transmitted through the screen, and the acoustic wave is disturbed by user contact. A receiving transducer detects the user contact instance and determines the contacted location coordinates.

The term "display" refers to a portion of one or more screens used to display the output of a computer to a user. A display may be a single-screen display or a multi-screen display, referred to as a composite display. A composite display can encompass the touch sensitive display of one or more screens. A single physical screen can include multiple displays that are managed as separate logical displays. Thus, different content can be displayed on the separate displays although part of the same physical screen.

The term "displayed image" refers to an image produced on the display. A typical displayed image is a window or desktop. The displayed image may occupy all or a portion of the display.

The term "display orientation" refers to the way in which a rectangular display is oriented by a user for viewing. The two most common types of display orientation are portrait and landscape. In landscape mode, the display is oriented such that the width of the display is greater than the height of the display (such as a 4:3 ratio, which is 4 units wide and 3 units tall, or a 16:9 ratio, which is 16 units wide and 9 units tall). Stated differently, the longer dimension of the display is oriented substantially horizontal in landscape mode while the shorter dimension of the display is oriented substantially vertical. In the portrait mode, by contrast, the display is oriented such that the width of the display is less than the height of the display. Stated differently, the shorter dimension of the display is oriented substantially horizontal in the portrait mode while the longer dimension of the display is oriented substantially vertical.

The term "composite display" refers to a logical structure that defines a display that can encompass one or more screens. A multi-screen display can be associated with a composite display that encompasses all the screens. The composite display can have different display characteristics based on the various orientations of the device.

The term "gesture" refers to a user action that expresses an intended idea, action, meaning, result, and/or outcome. The user action can include manipulating a device (e.g., opening or closing a device, changing a device orientation, moving a trackball or wheel, etc.), movement of a body part in relation to the device, movement of an implement or tool in relation to the device, audio inputs, etc. A gesture may be made on a device (such as on the screen) or with the device to interact with the device.

The term "module" as used herein refers to any known or later developed hardware, software, firmware, artificial intel-

ligence, fuzzy logic, or combination of hardware and software that is capable of performing the functionality associated with that element.

The term "gesture capture" refers to a sense or otherwise a detection of an instance and/or type of user gesture. The gesture capture can occur in one or more areas of the screen, A gesture region can be on the display, where it may be referred to as a touch sensitive display or off the display where it may be referred to as a gesture capture area.

A "multi-screen application" or "multiple-display application" refers to an application that is capable of multiple modes. The multi-screen application mode can include, but is not limited to, a single screen mode (where the application is displayed on a single screen) or a composite display mode (where the application is displayed on two or more screens). A multi-screen application can have different layouts optimized for the mode. Thus, the multi-screen application can have different layouts for a single screen or for a composite display that can encompass two or more screens. The different layouts may have different screen/display dimensions and/or configurations on which the user interfaces of the multi-screen applications can be rendered. The different layouts allow the application to optimize the application's user interface for the type of display, e.g., single screen or multiple screens. In single screen mode, the multi-screen application may present one window pane of information. In a composite display mode, the multi-screen application may present multiple window panes of information or may provide a larger and a richer presentation because there is more space for the display contents. The multi-screen applications may be designed to adapt dynamically to changes in the device and the mode depending on which display (single or composite) the system assigns to the multi-screen application. In alternative embodiments, the user can use a gesture to request the application transition to a different mode, and, if a display is available for the requested mode, the device can allow the application to move to that display and transition modes.

A "single-screen application" refers to an application that is capable of single screen mode. Thus, the single-screen application can produce only one window and may not be capable of different modes or different display dimensions. A single-screen application may not be capable of the several modes discussed with the multi-screen application.

The term "window" refers to a, typically rectangular, displayed image on at least part of a display that contains or provides content different from the rest of the screen. The window may obscure the desktop.

The terms "determine", "calculate" and "compute," and variations thereof, as used herein, are used interchangeably and include any type of methodology, process, mathematical operation or technique.

It shall be understood that the term "means" as used herein shall be given its broadest possible interpretation in accordance with 35 U.S.C., Section 112, Paragraph 6. Accordingly, a claim incorporating the term "means" shall cover all structures, materials, or acts set forth herein, and all of the equivalents thereof. Further, the structures, materials or acts and the equivalents thereof shall include all those described in the summary of the invention, brief description of the drawings, detailed description, abstract, and claims themselves.

The preceding is a simplified summary of the disclosure to provide an understanding of some aspects of the disclosure. This summary is neither an extensive nor exhaustive overview of the disclosure and its various aspects, embodiments, and/or configurations. It is intended neither to identify key or critical elements of the disclosure nor to delineate the scope of the disclosure but to present selected concepts of the disclosure in a simplified form as an introduction to the more detailed description presented below. As will be appreciated, other aspects, embodiments, and/or configurations of the disclosure are possible utilizing, alone or in combination, one or more of the features set forth above or described in detail below.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. **1**A includes a first view of an embodiment of a multi-screen user device;

FIG. **1**B includes a second view of an embodiment of a multi-screen user device;

FIG. **1**C includes a third view of an embodiment of a multi-screen user device;

FIG. **1**D includes a fourth view of an embodiment of a multi-screen user device;

FIG. **1**E includes a fifth view of an embodiment of a multi-screen user device;

FIG. **1**F includes a sixth view of an embodiment of a multi-screen user device;

FIG. **1**G includes a seventh view of an embodiment of a multi-screen user device;

FIG. **1**H includes a eighth view of an embodiment of a multi-screen user device;

FIG. **1**I includes a ninth view of an embodiment of a multi-screen user device;

FIG. **1**J includes a tenth view of an embodiment of a multi-screen user device;

FIG. **2** is a block diagram of an embodiment of the hardware of the device;

FIG. **3**A is a block diagram of an embodiment of the state model for the device based on the device's orientation and/or configuration;

FIG. **3**B is a table of an embodiment of the state model for the device based on the device's orientation and/or configuration;

FIG. **4**A is a first representation of an embodiment of user gesture received at a device;

FIG. **4**B is a second representation of an embodiment of user gesture received at a device;

FIG. **4**C is a third representation of an embodiment of user gesture received at a device;

FIG. **4**D is a fourth representation of an embodiment of user gesture received at a device;

FIG. **4**E is a fifth representation of an embodiment of user gesture received at a device;

FIG. **4**F is a sixth representation of an embodiment of user gesture received at a device;

FIG. **4**G is a seventh representation of an embodiment of user gesture received at a device;

FIG. **4**H is a eighth representation of an embodiment of user gesture received at a device;

FIG. **5**A is a block diagram of an embodiment of the device software and/or firmware;

FIG. **5**B is a second block diagram of an embodiment of the device software and/or firmware;

FIG. **6**A is a first representation of an embodiment of a device configuration generated in response to the device state;

FIG. **6**B is a second representation of an embodiment of a device configuration generated in response to the device state;

FIG. **6**C is a third representation of an embodiment of a device configuration generated in response to the device state;

FIG. **6**D is a fourth representation of an embodiment of a device configuration generated in response to the device state;

FIG. **6**E is a fifth representation of an embodiment of a device configuration generated in response to the device state;

FIG. **6**F is a sixth representation of an embodiment of a device configuration generated in response to the device state;

FIG. **6**G is a seventh representation of an embodiment of a device configuration generated in response to the device state;

FIG. **6**H is a eighth representation of an embodiment of a device configuration generated in response to the device state;

FIG. **6**I is a ninth representation of an embodiment of a device configuration generated in response to the device state;

FIG. **6**J is a tenth representation of an embodiment of a device configuration generated in response to the device state;

FIG. **7**A is representation of a logical window stack;

FIG. **7**B is another representation of an embodiment of a logical window stack;

FIG. **7**C is another representation of an embodiment of a logical window stack;

FIG. **7**D is another representation of an embodiment of a logical window stack;

FIG. **7**E is another representation of an embodiment of a logical window stack;

FIG. **8** is block diagram of an embodiment of a logical data structure for a window stack;

FIG. **9** is a flow chart of an embodiment of a method for creating a window stack;

FIG. **10** illustrates an exemplary smartpad (SP);

FIG. **11** illustrates an exemplary method of associating the smartpad with the device;

FIG. **12** illustrates a docked device with the smartpad;

FIGS. **13**A-**13**B illustrate an exemplary method for screen orientation;

FIG. **14** illustrates a method for displaying an application when the SP is in a landscape mode;

FIG. **15** illustrates a method for displaying an application when the SP is in a portrait mode;

FIG. **16** illustrates an example of a dual screen application in portrait max mode;

FIG. **17** illustrates an example of a dual screen application in max mode landscape;

FIG. **18** illustrates an example of keyboard management on the SP;

FIG. **19** illustrates an example of keyboard management on the SP with an application area in max mode;

FIG. **20** illustrates another example of keyboard management for the SP in landscape mode;

FIG. **21** illustrates an example of a dual screen application running in a dual screen emulation mode on the SP with a virtual keyboard;

FIG. **22** illustrates an example of application window stack management on the SP;

FIG. **23** illustrates another example of application window stack management on the SP;

FIG. **24** illustrates an example of multi application mode of the SP, wherein in the multi application mode the SP emulates the device in its mini-tablet form;

FIG. **25** illustrates another example of multi application mode of the SP;

FIG. **26** illustrates another example of multi application mode of the SP;

FIG. **27** illustrates another example of multi application mode of the SP;

FIG. **28** illustrates a method for managing screen display;

FIG. **29** illustrates an exemplary method for managing screen display with the desktop;

FIG. **30** illustrates an exemplary method of managing screen display with a keyboard;

FIGS. **31**A and **31**B illustrate desktop management on the SP;

FIGS. **32**A and **32** B illustrate exemplary methods for desktop panel management;

FIG. **33** illustrates an exemplary method for managing the display of the desktop and/or one or more panels on the SP;

FIG. **34** illustrates an exemplary method for merging panels for display on the SP;

FIG. **35** illustrates an exemplary method for stack management in multi application mode;

FIG. **36** illustrates an exemplary method for managing the display of an application based on application mode and device configuration;

FIG. **37**A is a representation of an output of a multiple screen device in accordance with embodiments of the present invention;

FIG. **37**B is a representation of an output of the multiple screen device illustrated in FIG. **37**A, after a minimization operation;

FIG. **38**A is a representation of an output of a multiple screen device in accordance with embodiments of the present invention;

FIG. **38**B is a representation of the output of the multiple screen device illustrated in FIG. **38**A, after a maximization operation;

FIG. **39**A is a representation of an output of a multiple screen device in accordance with embodiments of the present invention;

FIG. **39**B is a representation of the output of the multiple screen device illustrated in FIG. **39**A, after a maximization operation; and

FIG. **40** is a flowchart depicting aspects of a method for minimizing and maximizing between portrait dual display and portrait single display in accordance with embodiments of the present invention.

In the appended figures, similar components and/or features may have the same reference label. Further, various components of the same type may be distinguished by following the reference label by a letter that distinguishes among the similar components. If only the first reference label is used in the specification, the description is applicable to any one of the similar components having the same first reference label irrespective of the second reference label.

DETAILED DESCRIPTION

Presented herein are embodiments of a device. The device can be a communications device, such as a cellular telephone, or other smart device. The device can include two screens that are oriented to provide several unique display configurations. Further, the device can receive user input in unique ways. The overall design and functionality of the device provides for an enhanced user experience making the device more useful and more efficient.

Mechanical Features:

FIGS. **1**A-**1**J illustrate a device **100** in accordance with embodiments of the present disclosure. As described in greater detail below, device **100** can be positioned in a number of different ways each of which provides different functionality to a user. The device **100** is a multi-screen device that includes a primary screen **104** and a secondary screen **108**, both of which are touch sensitive. In embodiments, the entire front surface of screens **104** and **108** may be touch sensitive and capable of receiving input by a user touching the front surface of the screens **104** and **108**. Primary screen **104** includes touch sensitive display **110**, which, in addition to being touch sensitive, also displays information to a user. Secondary screen **108** includes touch sensitive display **114**,

which also displays information to a user. In other embodiments, screens **104** and **108** may include more than one display area.

Primary screen **104** also includes a configurable area **112** that has been configured for specific inputs when the user touches portions of the configurable area **112**. Secondary screen **108** also includes a configurable area **116** that has been configured for specific inputs. Areas **112***a* and **116***a* have been configured to receive a "back" input indicating that a user would like to view information previously displayed. Areas **112***b* and **116***b* have been configured to receive a "menu" input indicating that the user would like to view options from a menu. Areas **112***c* and **116***c* have been configured to receive a "home" input indicating that the user would like to view information associated with a "home" view. In other embodiments, areas **112***a-c* and **116***a-c* may be configured, in addition to the configurations described above, for other types of specific inputs including controlling features of device **100**, some non-limiting examples including adjusting overall system power, adjusting the volume, adjusting the brightness, adjusting the vibration, selecting of displayed items (on either of screen **104** or **108**), operating a camera, operating a microphone, and initiating/terminating of telephone calls. Also, in some embodiments, areas **112***a*-C and **116***a*-C may be configured for specific inputs depending upon the application running on device **100** and/or information displayed on touch sensitive displays **110** and/or **114**.

In addition to touch sensing, primary screen **104** and secondary screen **108** may also include areas that receive input from a user without requiring the user to touch the display area of the screen. For example, primary screen **104** includes gesture capture area **120**, and secondary screen **108** includes gesture capture area **124**. These areas are able to receive input by recognizing gestures made by a user without the need for the user to actually touch the surface of the display area. In comparison to touch sensitive displays **110** and **114**, the gesture capture areas **120** and **124** are commonly not capable of rendering a displayed image.

The two screens **104** and **108** are connected together with a hinge **128**, shown clearly in FIG. **1**C (illustrating a back view of device **100**). Hinge **128**, in the embodiment shown in FIGS. **1**A-**1**J, is a center hinge that connects screens **104** and **108** so that when the hinge is closed, screens **104** and **108** are juxtaposed (i.e., side-by-side) as shown in FIG. **1**B (illustrating a front view of device **100**). Hinge **128** can be opened to position the two screens **104** and **108** in different relative positions to each other. As described in greater detail below, the device **100** may have different functionalities depending on the relative positions of screens **104** and **108**.

FIG. **1**D illustrates the right side of device **100**. As shown in FIG. **1**D, secondary screen **108** also includes a card slot **132** and a port **136** on its side. Card slot **132** in embodiments, accommodates different types of cards including a subscriber identity module (SIM). Port **136** in embodiments is an input/output port (I/O port) that allows device **100** to be connected to other peripheral devices, such as a display, keyboard, or printing device. As can be appreciated, these are merely some examples and in other embodiments device **100** may include other slots and ports such as slots and ports for accommodating additional memory devices and/or for connecting other peripheral devices. Also shown in FIG. **1**D is an audio jack **140** that accommodates a tip, ring, sleeve (TRS) connector for example to allow a user to utilize headphones or a headset.

Device **100** also includes a number of buttons **158**. For example, FIG. **1**E illustrates the left side of device **100**. As shown in FIG. **1**E, the side of primary screen **104** includes three buttons **144**, **148**, and **152**, which can be configured for specific inputs. For example, buttons **144**, **148**, and **152** may be configured to, in combination or alone, control a number of aspects of device **100**. Some non-limiting examples include overall system power, volume, brightness, vibration, selection of displayed items (on either of screen **104** or **108**), a camera, a microphone, and initiation/termination of telephone calls. In some embodiments, instead of separate buttons two buttons may be combined into a rocker button. This arrangement is useful in situations where the buttons are configured to control features such as volume or brightness. In addition to buttons **144**, **148**, and **152**, device **100** also includes a button **156**, shown in FIG. **1**F, which illustrates the top of device **100**. In one embodiment, button **156** is configured as an on/off button used to control overall system power to device **100**. In other embodiments, button **156** is configured to, in addition to or in lieu of controlling system power, control other aspects of device **100**. In some embodiments, one or more of the buttons **144**, **148**, **152**, and **156** are capable of supporting different user commands. By way of example, a normal press has a duration commonly of less than about 1 second and resembles a quick tap. A medium press has a duration commonly of 1 second or more but less than about 12 seconds. A long press has a duration commonly of about 12 seconds or more. The function of the buttons is normally specific to the application that is currently in focus on the respective display **110** and **114**. In a telephone application for instance and depending on the particular button, a normal, medium, or long press can mean end call, increase in call volume, decrease in call volume, and toggle microphone mute. In a camera or video application for instance and depending on the particular button, a normal, medium, or long press can mean increase zoom, decrease zoom, and take photograph or record video.

There are also a number of hardware components within device **100**. As illustrated in FIG. **1**C, device **100** includes a speaker **160** and a microphone **164**. Device **100** also includes a camera **168** (FIG. **1**B). Additionally, device **100** includes two position sensors **172**A and **172**B, which are used to determine the relative positions of screens **104** and **108**. In one embodiment, position sensors **172**A and **172**B are Hall effect sensors. However, in other embodiments other sensors can be used in addition to or in lieu of the Hall effect sensors. An accelerometer **176** may also be included as part of device **100** to determine the orientation of the device **100** and/or the orientation of screens **104** and **108**. Additional internal hardware components that may be included in device **100** are described below with respect to FIG. **2**.

The overall design of device **100** allows it to provide additional functionality not available in other communication devices. Some of the functionality is based on the various positions and orientations that device **100** can have. As shown in FIGS. **1**B-**1**G, device **100** can be operated in an "open" position where screens **104** and **108** are juxtaposed. This position allows a large display area for displaying information to a user. When position sensors **172**A and **172**B determine that device **100** is in the open position, they can generate a signal that can be used to trigger different events such as displaying information on both screens **104** and **108**. Additional events may be triggered if accelerometer **176** determines that device **100** is in a portrait position (FIG. **1**B) as opposed to a landscape position (not shown).

In addition to the open position, device **100** may also have a "closed" position illustrated in FIG. **1**H. Again, position sensors **172**A and **172**B can generate a signal indicating that device **100** is in the "closed" position. This can trigger an event that results in a change of displayed information on screen **104** and/or **108**. For example, device **100** may be

programmed to stop displaying information on one of the screens, e.g., screen **108**, since a user can only view one screen at a time when device **100** is in the "closed" position. In other embodiments, the signal generated by position sensors **172**A and **172**B, indicating that the device **100** is in the "closed" position, can trigger device **100** to answer an incoming telephone call. The "closed" position can also be a preferred position for utilizing the device **100** as a mobile phone.

Device **100** can also be used in an "easel" position which is illustrated in FIG. **1**I. In the "easel" position, screens **104** and **108** are angled with respect to each other and facing outward with the edges of screens **104** and **108** substantially horizontal. In this position, device **100** can be configured to display information on both screens **104** and **108** to allow two users to simultaneously interact with device **100**. When device **100** is in the "easel" position, sensors **172**A and **172**B generate a signal indicating that the screens **104** and **108** are positioned at an angle to each other, and the accelerometer **176** can generate a signal indicating that device **100** has been placed so that the edge of screens **104** and **108** are substantially horizontal. The signals can then be used in combination to generate events that trigger changes in the display of information on screens **104** and **108**.

FIG. **1**J illustrates device **100** in a "modified easel" position. In the "modified easel" position, one of screens **104** or **108** is used as a stand and is faced down on the surface of an object such as a table. This position provides a convenient way for information to be displayed to a user in landscape orientation. Similar to the easel position, when device **100** is in the "modified easel" position, position sensors **172**A and **172**B generate a signal indicating that the screens **104** and **108** are positioned at an angle to each other. The accelerometer **176** would generate a signal indicating that device **100** has been positioned so that one of screens **104** and **108** is faced downwardly and is substantially horizontal. The signals can then be used to generate events that trigger changes in the display of information of screens **104** and **108**. For example, information may not be displayed on the screen that is face down since a user cannot see the screen.

Transitional states are also possible. When the position sensors **172**A and B and/or accelerometer indicate that the screens are being closed or folded (from open), a closing transitional state is recognized. Conversely when the position sensors **172**A and B indicate that the screens are being opened or folded (from closed), an opening transitional state is recognized. The closing and opening transitional states are typically time-based, or have a maximum time duration from a sensed starting point. Normally, no user input is possible when one of the closing and opening states is in effect. In this manner, incidental user contact with a screen during the closing or opening function is not misinterpreted as user input. In embodiments, another transitional state is possible when the device **100** is closed. This additional transitional state allows the display to switch from one screen **104** to the second screen **108** when the device **100** is closed based on some user input, e.g., a double tap on the screen **110**,**114**.

As can be appreciated, the description of device **100** is made for illustrative purposes only, and the embodiments are not limited to the specific mechanical features shown in FIGS. **1**A-**1**J and described above. In other embodiments, device **100** may include additional features, including one or more additional buttons, slots, display areas, hinges, and/or locking mechanisms. Additionally, in embodiments, the features described above may be located in different parts of device **100** and still provide similar functionality. Therefore, FIGS. **1**A-**1**J and the description provided above are nonlimiting.

Hardware Features:

FIG. **2** illustrates components of a device **100** in accordance with embodiments of the present disclosure. In general, the device **100** includes a primary screen **104** and a secondary screen **108**. While the primary screen **104** and its components are normally enabled in both the opened and closed positions or states, the secondary screen **108** and its components are normally enabled in the opened state but disabled in the closed state. However, even when in the closed state a user or application triggered interrupt (such as in response to a phone application or camera application operation) can flip the active screen, or disable the primary screen **104** and enable the secondary screen **108**, by a suitable command. Each screen **104**, **108** can be touch sensitive and can include different operative areas. For example, a first operative area, within each touch sensitive screen **104** and **108**, may comprise a touch sensitive display **110**, **114**. In general, the touch sensitive display **110**, **114** may comprise a full color, touch sensitive display. A second area within each touch sensitive screen **104** and **108** may comprise a gesture capture region **120**, **124**. The gesture capture region **120**, **124** may comprise an area or region that is outside of the touch sensitive display **110**, **114** area, and that is capable of receiving input, for example in the form of gestures provided by a user. However, the gesture capture region **120**, **124** does not include pixels that can perform a display function or capability.

A third region of the touch sensitive screens **104** and **108** may comprise a configurable area **112**, **116**. The configurable area **112**, **116** is capable of receiving input and has display or limited display capabilities. In embodiments, the configurable area **112**, **116** may present different input options to the user. For example, the configurable area **112**, **116** may display buttons or other relatable items. Moreover, the identity of displayed buttons, or whether any buttons are displayed at all within the configurable area **112**, **116** of a touch sensitive screen **104** or **108**, may be determined from the context in which the device **100** is used and/or operated. In an exemplary embodiment, the touch sensitive screens **104** and **108** comprise liquid crystal display devices extending across at least those regions of the touch sensitive screens **104** and **108** that are capable of providing visual output to a user, and a capacitive input matrix over those regions of the touch sensitive screens **104** and **108** that are capable of receiving input from the user.

One or more display controllers **216***a*, **216***b* may be provided for controlling the operation of the touch sensitive screens **104** and **108**, including input (touch sensing) and output (display) functions. In the exemplary embodiment illustrated in FIG. **2**, a separate touch screen controller **216***a* or **216***b* is provided for each touch screen **104** and **108**. In accordance with alternate embodiments, a common or shared touch screen controller **216** may be used to control each of the included touch sensitive screens **104** and **108**. In accordance with still other embodiments, the functions of a touch screen controller **216** may be incorporated into other components, such as a processor **204**.

The processor **204** may comprise a general purpose programmable processor or controller for executing application programming or instructions. In accordance with at least some embodiments, the processor **204** may include multiple processor cores, and/or implement multiple virtual processors. In accordance with still other embodiments, the processor **204** may include multiple physical processors. As a particular example, the processor **204** may comprise a specially configured application specific integrated circuit (ASIC) or other integrated circuit, a digital signal processor, a controller, a hardwired electronic or logic circuit, a programmable

logic device or gate array, a special purpose computer, or the like. The processor **204** generally functions to run programming code or instructions implementing various functions of the device **100**.

A communication device **100** may also include memory **208** for use in connection with the execution of application programming or instructions by the processor **204**, and for the temporary or long term storage of program instructions and/or data. As examples, the memory **208** may comprise RAM, DRAM, SDRAM, or other solid state memory. Alternatively or in addition, data storage **212** may be provided. Like the memory **208**, the data storage **212** may comprise a solid state memory device or devices. Alternatively or in addition, the data storage **212** may comprise a hard disk drive or other random access memory.

In support of communications functions or capabilities, the device **100** can include a cellular telephony module **228**. As examples, the cellular telephony module **228** can comprise a GSM, CDMA, FDMA and/or analog cellular telephony transceiver capable of supporting voice, multimedia and/or data transfers over a cellular network. Alternatively or in addition, the device **100** can include an additional or other wireless communications module **232**. As examples, the other wireless communications module **232** can comprise a Wi-Fi, BLUETOOTH™, WiMax, infrared, or other wireless communications link. The cellular telephony module **228** and the other wireless communications module **232** can each be associated with a shared or a dedicated antenna **224**.

A port interface **252** may be included. The port interface **252** may include proprietary or universal ports to support the interconnection of the device **100** to other devices or components, such as a dock, which may or may not include additional or different capabilities from those integral to the device **100**. In addition to supporting an exchange of communication signals between the device **100** and another device or component, the docking port **136** and/or port interface **252** can support the supply of power to or from the device **100**. The port interface **252** also comprises an intelligent element that comprises a docking module for controlling communications or other interactions between the device **100** and a connected device or component.

An input/output module **248** and associated ports may be included to support communications over wired networks or links, for example with other communication devices, server devices, and/or peripheral devices. Examples of an input/output module **248** include an Ethernet port, a Universal Serial Bus (USB) port, Institute of Electrical and Electronics Engineers (IEEE) 1394, or other interface.

An audio input/output interface/device(s) **244** can be included to provide analog audio to an interconnected speaker or other device, and to receive analog audio input from a connected microphone or other device. As an example, the audio input/output interface/device(s) **244** may comprise an associated amplifier and analog to digital converter. Alternatively or in addition, the device **100** can include an integrated audio input/output device **256** and/or an audio jack for interconnecting an external speaker or microphone. For example, an integrated speaker and an integrated microphone can be provided, to support near talk or speaker phone operations.

Hardware buttons **158** can be included for example for use in connection with certain control operations. Examples include a master power switch, volume control, etc., as described in conjunction with FIGS. **1**A through **1**J. One or more image capture interfaces/devices **240**, such as a camera, can be included for capturing still and/or video images. Alternatively or in addition, an image capture interface/device **240** can include a scanner or code reader. An image capture interface/device **240** can include or be associated with additional elements, such as a flash or other light source.

The device **100** can also include a global positioning system (GPS) receiver **236**. In accordance with embodiments of the present invention, the GPS receiver **236** may further comprise a GPS module that is capable of providing absolute location information to other components of the device **100**. An accelerometer(s) **176** may also be included. For example, in connection with the display of information to a user and/or other functions, a signal from the accelerometer **176** can be used to determine an orientation and/or format in which to display that information to the user.

Embodiments of the present invention can also include one or more position sensor(s) **172**. The position sensor **172** can provide a signal indicating the position of the touch sensitive screens **104** and **108** relative to one another. This information can be provided as an input, for example to a user interface application, to determine an operating mode, characteristics of the touch sensitive displays **110**, **114**, and/or other device **100** operations. As examples, a screen position sensor **172** can comprise a series of Hall effect sensors, a multiple position switch, an optical switch, a Wheatstone bridge, a potentiometer, or other arrangement capable of providing a signal indicating of multiple relative positions the touch screens are in.

Communications between various components of the device **100** can be carried by one or more buses **222**. In addition, power can be supplied to the components of the device **100** from a power source and/or power control module **260**. The power control module **260** can, for example, include a battery, an AC to DC converter, power control logic, and/or ports for interconnecting the device **100** to an external source of power.

Device State:

FIGS. **3**A and **3**B represent illustrative states of device **100**. While a number of illustrative states are shown, and transitions from a first state to a second state, it is to be appreciated that the illustrative state diagram may not encompass all possible states and/or all possible transitions from a first state to a second state. As illustrated in FIG. **3**, the various arrows between the states (illustrated by the state represented in the circle) represent a physical change that occurs to the device **100**, that is detected by one or more of hardware and software, the detection triggering one or more of a hardware and/or software interrupt that is used to control and/or manage one or more functions of device **100**.

As illustrated in FIG. **3**A, there are twelve exemplary "physical" states: closed **304**, transition **308** (or opening transitional state), easel **312**, modified easel **316**, open **320**, inbound/outbound call or communication **324**, image/video capture **328**, transition **332** (or closing transitional state), landscape **340**, docked **336**, docked **344** and landscape **348**. Next to each illustrative state is a representation of the physical state of the device **100** with the exception of states **324** and **328**, where the state is generally symbolized by the international icon for a telephone and the icon for a camera, respectfully.

In state **304**, the device is in a closed state with the device **100** generally oriented in the portrait direction with the primary screen **104** and the secondary screen **108** back-to-back in different planes (see FIG. **1**H). From the closed state, the device **100** can enter, for example, docked state **336**, where the device **100** is coupled with a docking station, docking cable, or in general docked or associated with one or more other devices or peripherals, or the landscape state **340**, where the device **100** is generally oriented with the primary screen **104** facing the user, and the primary screen **104** and the secondary screen **108** being back-to-back.

In the closed state, the device can also move to a transitional state where the device remains closed by the display is moved from one screen **104** to another screen **108** based on a user input, e.g., a double tap on the screen **110**, **114**. Still another embodiment includes a bilateral state. In the bilateral state, the device remains closed, but a single application displays at least one window on both the first display **110** and the second display **114**. The windows shown on the first and second display **110**, **114** may be the same or different based on the application and the state of that application. For example, while acquiring an image with a camera, the device may display the view finder on the first display **110** and displays a preview for the photo subjects (full screen and mirrored left-to-right) on the second display **114**.

In state **308**, a transition state from the closed state **304** to the semi-open state or easel state **312**, the device **100** is shown opening with the primary screen **104** and the secondary screen **108** being rotated around a point of axis coincidence with the hinge. Upon entering the easel state **312**, the primary screen **104** and the secondary screen **108** are separated from one another such that, for example, the device **100** can sit in an easel-like configuration on a surface.

In state **316**, known as the modified easel position, the device **100** has the primary screen **104** and the secondary screen **108** in a similar relative relationship to one another as in the easel state **312**, with the difference being one of the primary screen **104** or the secondary screen **108** are placed on a surface as shown.

State **320** is the open state where the primary screen **104** and the secondary screen **108** are generally on the same plane. From the open state, the device **100** can transition to the docked state **344** or the open landscape state **348**. In the open state **320**, the primary screen **104** and the secondary screen **108** are generally in the portrait-like orientation while in landscaped state **348** the primary screen **104** and the secondary screen **108** are generally in a landscape-like orientation.

State **324** is illustrative of a communication state, such as when an inbound or outbound call is being received or placed, respectively, by the device **100**. While not illustrated for clarity, it should be appreciated the device **100** can transition to the inbound/outbound call state **324** from any state illustrated in FIG. **3**. In a similar manner, the image/video capture state **328** can be entered into from any other state in FIG. **3**, with the image/video capture state **328** allowing the device **100** to take one or more images via a camera and/or videos with a video capture device **240**.

Transition state **322** illustratively shows primary screen **104** and the secondary screen **108** being closed upon one another for entry into, for example, the closed state **304**.

FIG. **3**B illustrates, with reference to the key, the inputs that are received to detect a transition from a first state to a second state. In FIG. **3**B, various combinations of states are shown with in general, a portion of the columns being directed toward a portrait state **352**, a landscape state **356**, and a portion of the rows being directed to portrait state **360** and landscape state **364**.

In FIG. **3**B, the Key indicates that "H" represents an input from one or more Hall Effect sensors, "A" represents an input from one or more accelerometers, "T" represents an input from a timer, "P" represents a communications trigger input and "I" represents an image and/or video capture request input. Thus, in the center portion **376** of the chart, an input, or combination of inputs, are shown that represent how the device **100** detects a transition from a first physical state to a second physical state.

As discussed, in the center portion of the chart **376**, the inputs that are received enable the detection of a transition from, for example, a portrait open state to a landscape easel state—shown in bold—"HAT." For this exemplary transition from the portrait open to the landscape easel state, a Hall Effect sensor ("H"), an accelerometer ("A") and a timer ("T") input may be needed. The timer input can be derived from, for example, a clock associated with the processor.

In addition to the portrait and landscape states, a docked state **368** is also shown that is triggered based on the receipt of a docking signal **372**. As discussed above and in relation to FIG. **3**, the docking signal can be triggered by the association of the device **100** with one or more other device **100**s, accessories, peripherals, smart docks, or the like.

User Interaction:

FIGS. **4**A through **4**H depict various graphical representations of gesture inputs that may be recognized by the screens **104**, **108**. The gestures may be performed not only by a user's body part, such as a digit, but also by other devices, such as a stylus, that may be sensed by the contact sensing portion(s) of a screen **104**, **108**. In general, gestures are interpreted differently, based on where the gestures are performed (either directly on the display **110**, **114** or in the gesture capture region **120**, **124**). For example, gestures in the display **110**, **114** may be directed to a desktop or application, and gestures in the gesture capture region **120**, **124** may be interpreted as for the system.

With reference to FIGS. **4**A-**4**H, a first type of gesture, a touch gesture **420**, is substantially stationary on the screen **104**,**108** for a selected length of time. A circle **428** represents a touch or other contact type received at particular location of a contact sensing portion of the screen. The circle **428** may include a border **432**, the thickness of which indicates a length of time that the contact is held substantially stationary at the contact location. For instance, a tap **420** (or short press) has a thinner border **432***a* than the border **432***b* for a long press **424** (or for a normal press). The long press **424** may involve a contact that remains substantially stationary on the screen for longer time period than that of a tap **420**. As will be appreciated, differently defined gestures may be registered depending upon the length of time that the touch remains stationary prior to contact cessation or movement on the screen.

With reference to FIG. **4**C, a drag gesture **400** on the screen **104**,**108** is an initial contact (represented by circle **428**) with contact movement **436** in a selected direction. The initial contact **428** may remain stationary on the screen **104**,**108** for a certain amount of time represented by the border **432**. The drag gesture typically requires the user to contact an icon, window, or other displayed image at a first location followed by movement of the contact in a drag direction to a new second location desired for the selected displayed image. The contact movement need not be in a straight line but have any path of movement so long as the contact is substantially continuous from the first to the second locations.

With reference to FIG. **4**D, a flick gesture **404** on the screen **104**,**108** is an initial contact (represented by circle **428**) with truncated contact movement **436** (relative to a drag gesture) in a selected direction. In embodiments, a flick has a higher exit velocity for the last movement in the gesture compared to the drag gesture. The flick gesture can, for instance, be a finger snap following initial contact. Compared to a drag gesture, a flick gesture generally does not require continual contact with the screen **104**,**108** from the first location of a displayed image to a predetermined second location. The contacted displayed image is moved by the flick gesture in the direction of the flick gesture to the predetermined second location. Although both gestures commonly can move a displayed image from a first location to a second location, the temporal

duration and distance of travel of the contact on the screen is generally less for a flick than for a drag gesture.

With reference to FIG. **4**E, a pinch gesture **408** on the screen **104**,**108** is depicted. The pinch gesture **408** may be initiated by a first contact **428***a* to the screen **104**,**108** by, for example, a first digit and a second contact **428***b* to the screen **104**,**108** by, for example, a second digit. The first and second contacts **428***a,b* may be detected by a common contact sensing portion of a common screen **104**,**108**, by different contact sensing portions of a common screen **104** or **108**, or by different contact sensing portions of different screens. The first contact **428***a* is held for a first amount of time, as represented by the border **432***a*, and the second contact **428***b* is held for a second amount of time, as represented by the border **432***b*. The first and second amounts of time are generally substantially the same, and the first and second contacts **428** *a, b* generally occur substantially simultaneously. The first and second contacts **428** *a, b* generally also include corresponding first and second contact movements **436** *a, b*, respectively. The first and second contact movements **436** *a, b* are generally in opposing directions. Stated another way, the first contact movement **436***a* is towards the second contact **436***b*, and the second contact movement **436***b* is towards the first contact **436***a*. More simply stated, the pinch gesture **408** may be accomplished by a user's digits touching the screen **104**,**108** in a pinching motion.

With reference to FIG. **4**F, a spread gesture **410** on the screen **104**,**108** is depicted. The spread gesture **410** may be initiated by a first contact **428***a* to the screen **104**,**108** by, for example, a first digit and a second contact **428***b* to the screen **104**,**108** by, for example, a second digit. The first and second contacts **428***a,b* may be detected by a common contact sensing portion of a common screen **104**,**108**, by different contact sensing portions of a common screen **104**,**108**, or by different contact sensing portions of different screens. The first contact **428***a* is held for a first amount of time, as represented by the border **432***a*, and the second contact **428***b* is held for a second amount of time, as represented by the border **432***b*. The first and second amounts of time are generally substantially the same, and the first and second contacts **428** *a, b* generally occur substantially simultaneously. The first and second contacts **428** *a, b* generally also include corresponding first and second contact movements **436***a, b*, respectively. The first and second contact movements **436** *a, b* are generally in a common direction. Stated another way, the first and second contact movements **436** *a, b* are away from the first and second contacts **428***a, b*. More simply stated, the spread gesture **410** may be accomplished by a user's digits touching the screen **104**,**108** in a spreading motion.

The above gestures may be combined in any manner, such as those shown by FIGS. **4**G and **4**H, to produce a determined functional result. For example, in FIG. **4**G a tap gesture **420** is combined with a drag or flick gesture **412** in a direction away from the tap gesture **420**. In FIG. **4**H, a tap gesture **420** is combined with a drag or flick gesture **412** in a direction towards the tap gesture **420**.

The functional result of receiving a gesture can vary depending on a number of factors, including a state of the device **100**, display **110**, **114**, or screen **104**, **108**, a context associated with the gesture, or sensed location of the gesture. The state of the device commonly refers to one or more of a configuration of the device **100**, a display orientation, and user and other inputs received by the device **100**. Context commonly refers to one or more of the particular application(s) selected by the gesture and the portion(s) of the application currently executing, whether the application is a single- or multi-screen application, and whether the application is a multi-screen application displaying one or more windows in one or more screens or in one or more stacks. Sensed location of the gesture commonly refers to whether the sensed set(s) of gesture location coordinates are on a touch sensitive display **110**, **114** or a gesture capture region **120**, **124**, whether the sensed set(s) of gesture location coordinates are associated with a common or different display or screen **104**,**108**, and/or what portion of the gesture capture region contains the sensed set(s) of gesture location coordinates.

A tap, when received by an a touch sensitive display **110**, **114**, can be used, for instance, to select an icon to initiate or terminate execution of a corresponding application, to maximize or minimize a window, to reorder windows in a stack, and to provide user input such as by keyboard display or other displayed image. A drag, when received by a touch sensitive display **110**, **114**, can be used, for instance, to relocate an icon or window to a desired location within a display, to reorder a stack on a display, or to span both displays (such that the selected window occupies a portion of each display simultaneously). A flick, when received by a touch sensitive display **110**, **114** or a gesture capture region **120**, **124**, can be used to relocate a window from a first display to a second display or to span both displays (such that the selected window occupies a portion of each display simultaneously). Unlike the drag gesture, however, the flick gesture is generally not used to move the displayed image to a specific user-selected location but to a default location that is not configurable by the user.

The pinch gesture, when received by a touch sensitive display **110**, **114** or a gesture capture region **120**, **124**, can be used to minimize or otherwise increase the displayed area or size of a window (typically when received entirely by a common display), to switch windows displayed at the top of the stack on each display to the top of the stack of the other display (typically when received by different displays or screens), or to display an application manager (a "pop-up window" that displays the windows in the stack). The spread gesture, when received by a touch sensitive display **110**, **114** or a gesture capture region **120**, **124**, can be used to maximize or otherwise decrease the displayed area or size of a window, to switch windows displayed at the top of the stack on each display to the top of the stack of the other display (typically when received by different displays or screens), or to display an application manager (typically when received by an off-screen gesture capture region on the same or different screens).

The combined gestures of FIG. **4**G, when received by a common display capture region in a common display or screen **104**,**108**, can be used to hold a first window stack location in a first stack constant for a display receiving the gesture while reordering a second window stack location in a second window stack to include a window in the display receiving the gesture. The combined gestures of FIG. **4**H, when received by different display capture regions in a common display or screen **104**,**108** or in different displays or screens, can be used to hold a first window stack location in a first window stack constant for a display receiving the tap part of the gesture while reordering a second window stack location in a second window stack to include a window in the display receiving the flick or drag gesture. Although specific gestures and gesture capture regions in the preceding examples have been associated with corresponding sets of functional results, it is to be appreciated that these associations can be redefined in any manner to produce differing associations between gestures and/or gesture capture regions and/or functional results.

Firmware and Software:

With reference to FIG. **5**, the memory **508** may store and the processor **504** may execute one or more software components. These components can include at least one operating system (OS) **516**, an application manager **562**, a desktop **566**, and/or one or more applications **564***a* and/or **564***b* from an application store **560**. The OS **516** can include a framework **520**, one or more frame buffers **548**, one or more drivers **512**, previously described in conjunction with FIG. **2**, and/or a kernel **518**. The OS **516** can be any software, consisting of programs and data, which manages computer hardware resources and provides common services for the execution of various applications **564**. The OS **516** can be any operating system and, at least in some embodiments, dedicated to mobile devices, including, but not limited to, Linux, ANDROID™, iPhone OS (IOS™), WINDOWS PHONE 7™, etc. The OS **516** is operable to provide functionality to the phone by executing one or more operations, as described herein.

The applications **564** can be any higher level software that executes particular functionality for the user. Applications **564** can include programs such as email clients, web browsers, texting applications, games, media players, office suites, etc. The applications **564** can be stored in an application store **560**, which may represent any memory or data storage, and the management software associated therewith, for storing the applications **564**. Once executed, the applications **564** may be run in a different area of memory **508**.

The framework **520** may be any software or data that allows the multiple tasks running on the device to interact. In embodiments, at least portions of the framework **520** and the discrete components described hereinafter may be considered part of the OS **516** or an application **564**. However, these portions will be described as part of the framework **520**, but those components are not so limited. The framework **520** can include, but is not limited to, a Multi-Display Management (MDM) module **524**, a Surface Cache module **528**, a Window Management module **532**, an Input Management module **536**, a Task Management module **540**, an Application Model Manager **542**, a Display Controller, one or more frame buffers **548**, a task stack **552**, one or more window stacks **550** (which is a logical arrangement of windows and/or desktops in a display area), and/or an event buffer **556**.

The MDM module **524** includes one or more modules that are operable to manage the display of applications or other data on the screens of the device. An embodiment of the MDM module **524** is described in conjunction with FIG. **5**B. In embodiments, the MDM module **524** receives inputs from the other OS **516** components, such as, the drivers **512**, and from the applications **564** to determine continually the state of the device **100**. The inputs assist the MDM module **524** in determining how to configure and allocate the displays according to the application's preferences and requirements, and the user's actions. Once a determination for display configurations is made, the MDM module **524** can bind the applications **564** to a display. The configuration may then be provided to one or more other components to generate a window with a display.

The Surface Cache module **528** includes any memory or storage and the software associated therewith to store or cache one or more images of windows. A series of active and/or non-active windows (or other display objects, such as, a desktop display) can be associated with each display. An active window (or other display object) is currently displayed. A non-active windows (or other display objects) were opened and, at some time, displayed but are now not displayed. To enhance the user experience, before a window transitions from an active state to an inactive state, a "screen shot" of a last generated image of the window (or other display object) can be stored. The Surface Cache module **528** may be operable to store a bitmap of the last active image of a window (or other display object) not currently displayed. Thus, the Surface Cache module **528** stores the images of non-active windows (or other display objects) in a data store.

In embodiments, the Window Management module **532** is operable to manage the windows (or other display objects) that are active or not active on each of the displays. The Window Management module **532**, based on information from the MDM module **524**, the OS **516**, or other components, determines when a window (or other display object) is visible or not active. The Window Management module **532** may then put a non-visible window (or other display object) in a "not active state" and, in conjunction with the Task Management module Task Management **540** suspends the application's operation. Further, the Window Management module **532** may assign, through collaborative interaction with the MDM module **524**, a display identifier to the window (or other display object) or manage one or more other items of data associated with the window (or other display object). The Window Management module **532** may also provide the stored information to the application **564**, the Task Management module **540**, or other components interacting with or associated with the window (or other display object). The Window Management module **532** can also associate an input task with a window based on window focus and display coordinates within the motion space.

The Input Management module **536** is operable to manage events that occur with the device. An event is any input into the window environment, for example, a user interface interactions with a user. The Input Management module **536** receives the events and logically stores the events in an event buffer **556**. Events can include such user interface interactions as a "down event," which occurs when a screen **104**, **108** receives a touch signal from a user, a "move event," which occurs when the screen **104**, **108** determines that a user's finger is moving across a screen(s), an "up event, which occurs when the screen **104**, **108** determines that the user has stopped touching the screen **104**, **108**, etc. These events are received, stored, and forwarded to other modules by the Input Management module **536**. The Input Management module **536** may also map screen inputs to a motion space which is the culmination of all physical and virtual display available on the device.

The motion space is a virtualized space that includes all touch sensitive displays **110**,**114** "tiled" together to mimic the physical dimensions of the device **100**. For example, when the device **100** is unfolded, the motion space size may be 960×800, which may be the number of pixels in the combined display area for both touch sensitive displays **110**, **114**. If a user touches on a first touch sensitive display **110** on location (**40**, **40**), a full screen window can receive touch event with location (**40**, **40**). If a user touches on a second touch sensitive display **114**, with location (**40**, **40**), the full screen window can receive touch event with location (**520**, **40**), because the second touch sensitive display **114** is on the right side of the first touch sensitive display **110**, so the device **100** can offset the touch by the first touch sensitive display's **110** width, which is 480 pixels. When a hardware event occurs with location info from a driver **512**, the framework **520** can upscale the physical location to the motion space because the location of the event may be different based on the device orientation and state. The motion space may be as described in U.S. patent application Ser. No. 13/187,026, filed Jul. 20, 2011, entitled "Systems and Methods for Receiving Gesture

Inputs Spanning Multiple Input Devices," which is hereby incorporated by reference in its entirety for all that it teaches and for all purposes.

A task can be an application and a sub-task can be an application component that provides a window with which users can interact to do something, such as dial the phone, take a photo, send an email, or view a map. Each task may be given a window in which to draw a user interface. The window typically fills a display (for example, touch sensitive display **110**,**114**), but may be smaller than the display **110**, **114** and float on top of other windows. An application usually consists of multiple sub-tasks that are loosely bound to each other. Typically, one task in an application is specified as the "main" task, which is presented to the user when launching the application for the first time. Each task can then start another task or sub-task to perform different actions.

The Task Management module **540** is operable to manage the operation of one or more applications **564** that may be executed by the device. Thus, the Task Management module **540** can receive signals to launch, suspend, terminate, etc. an application or application sub-tasks stored in the application store **560**. The Task Management module **540** may then instantiate one or more tasks or sub-tasks of the application **564** to begin operation of the application **564**. Further, the Task Management Module **540** may launch, suspend, or terminate a task or sub-task as a result of user input or as a result of a signal from a collaborating framework **520** component. The Task Management Module **540** is responsible for managing the lifecycle of applications (tasks and sub-task) from when the application is launched to when the application is terminated.

The processing of the Task Management Module **540** is facilitated by a task stack **552**, which is a logical structure associated with the Task Management Module **540**. The task stack **552** maintains the state of all tasks and sub-tasks on the device **100**. When some component of the operating system **516** requires a task or sub-task to transition in its lifecycle, the OS **516** component can notify the Task Management Module **540**. The Task Management Module **540** may then locate the task or sub-task, using identification information, in the task stack **552**, and send a signal to the task or sub-task indicating what kind of lifecycle transition the task needs to execute. Informing the task or sub-task of the transition allows the task or sub-task to prepare for the lifecycle state transition. The Task Management Module **540** can then execute the state transition for the task or sub-task. In embodiments, the state transition may entail triggering the OS kernel **518** to terminate the task when termination is required.

Further, the Task Management module **540** may suspend the application **564** based on information from the Window Management Module **532**. Suspending the application **564** may maintain application data in memory but may limit or stop the application **564** from rendering a window or user interface. Once the application becomes active again, the Task Management module **540** can again trigger the application to render its user interface. In embodiments, if a task is suspended, the task may save the task's state in case the task is terminated. In the suspended state, the application task may not receive input because the application window is not visible to the user.

The frame buffer **548** is a logical structure(s) used to render the user interface. The frame buffer **548** can be created and destroyed by the OS kernel **518**. However, the Display Controller **544** can write the image data, for the visible windows, into the frame buffer **548**. A frame buffer **548** can be associated with one screen or multiple screens. The association of a frame buffer **548** with a screen can be controlled dynamically by interaction with the OS kernel **518**. A composite display may be created by associating multiple screens with a single frame buffer **548**. Graphical data used to render an application's window user interface may then be written to the single frame buffer **548**, for the composite display, which is output to the multiple screens **104**,**108**. The Display Controller **544** can direct an application's user interface to a portion of the frame buffer **548** that is mapped to a particular display **110**,**114**, thus, displaying the user interface on only one screen **104** or **108**. The Display Controller **544** can extend the control over user interfaces to multiple applications, controlling the user interfaces for as many displays as are associated with a frame buffer **548** or a portion thereof. This approach compensates for the multiple physical screens **104**,**108** that are in use by the software component above the Display Controller **544**.

The Application Manager **562** is an application that provides a presentation layer for the window environment. Thus, the Application Manager **562** provides the graphical model for rendering by the Task Management Module **540**. Likewise, the Desktop **566** provides the presentation layer for the Application Store **560**. Thus, the desktop provides a graphical model of a surface having selectable application icons for the Applications **564** in the Application Store **560** that can be provided to the Window Management Module **556** for rendering.

Further, the framework can include an Application Model Manager (AMM) **542**. The Application Manager **562** may interface with the AMM **542**. In embodiments, the AMM **542** receives state change information from the device **100** regarding the state of applications (which are running or suspended). The AMM **542** can associate bit map images from the Surface Cache Module **528** to the tasks that are alive (running or suspended). Further, the AMM **542** can convert the logical window stack maintained in the Task Manager Module **540** to a linear ("film strip" or "deck of cards") organization that the user perceives when the using the off gesture capture area **120** to sort through the windows. Further, the AMM **542** may provide a list of executing applications to the Application Manager **562**.

An embodiment of the MDM module **524** is shown in FIG. **5**B. The MDM module **524** is operable to determine the state of the environment for the device, including, but not limited to, the orientation of the device, whether the device **100** is opened or closed, what applications **564** are executing, how the applications **564** are to be displayed, what actions the user is conducting, the tasks being displayed, etc. To configure the display, the MDM module **524** interprets these environmental factors and determines a display configuration, as described in conjunction with FIGS. **6**A-**6**J. Then, the MDM module **524** can bind the applications **564** or other device components to the displays. The configuration may then be sent to the Display Controller **544** and/or the other components within the OS **516** to generate the display. The MDM module **524** can include one or more of, but is not limited to, a Display Configuration Module **568**, a Preferences Module **572**, a Device State Module **574**, a Gesture Module **576**, a Requirements Module **580**, an Event Module **584**, and/or a Binding Module **588**.

The Display Configuration Module **568** determines the layout for the display. In embodiments, the Display Configuration Module **568** can determine the environmental factors. The environmental factors may be received from one or more other MDM modules **524** or from other sources. The Display Configuration Module **568** can then determine from the list of factors the best configuration for the display. Some embodi-

ments of the possible configurations and the factors associated therewith are described in conjunction with FIGS. **6**A-**6**F.

The Preferences Module **572** is operable to determine display preferences for an application **564** or other component. For example, an application can have a preference for Single or Dual displays. The Preferences Module **572** can determine an application's display preference (e.g., by inspecting the application's preference settings) and may allow the application **564** to change to a mode (e.g., single screen, dual screen, max, etc.) if the device **100** is in a state that can accommodate the preferred mode. However, some user interface policies may disallow a mode even if the mode is available. As the configuration of the device changes, the preferences may be reviewed to determine if a better display configuration can be achieved for an application **564**.

The Device State Module **574** is operable to determine or receive the state of the device. The state of the device can be as described in conjunction with FIGS. **3**A and **3**B. The state of the device can be used by the Display Configuration Module **568** to determine the configuration for the display. As such, the Device State Module **574** may receive inputs and interpret the state of the device. The state information is then provided to the Display Configuration Module **568**.

The Gesture Module **576** is shown as part of the MDM module **524**, but, in embodiments, the Gesture module **576** may be a separate Framework **520** component that is separate from the MDM module **524**. In embodiments, the Gesture Module **576** is operable to determine if the user is conducting any actions on any part of the user interface. In alternative embodiments, the Gesture Module **576** receives user interface actions from the configurable area **112**,**116** only. The Gesture Module **576** can receive touch events that occur on the configurable area **112**,**116** (or possibly other user interface areas) by way of the Input Management Module **536** and may interpret the touch events (using direction, speed, distance, duration, and various other parameters) to determine what kind of gesture the user is performing. When a gesture is interpreted, the Gesture Module **576** can initiate the processing of the gesture and, by collaborating with other Framework **520** components, can manage the required window animation. The Gesture Module **576** collaborates with the Application Model Manager **542** to collect state information with respect to which applications are running (active or paused) and the order in which applications must appear when a user gesture is performed. The Gesture Module **576** may also receive references to bitmaps (from the Surface Cache Module **528**) and live windows so that when a gesture occurs it can instruct the Display Controller **544** how to move the window(s) across the display **110**,**114**. Thus, suspended applications may appear to be running when those windows are moved across the display **110**,**114**.

Further, the Gesture Module **576** can receive task information either from the Task Manage Module **540** or the Input Management module **536**. The gestures may be as defined in conjunction with FIGS. **4**A through **4**H. For example, moving a window causes the display to render a series of display frames that illustrate the window moving. The gesture associated with such user interface interaction can be received and interpreted by the Gesture Module **576**. The information about the user gesture is then sent to the Task Management Module **540** to modify the display binding of the task.

The Requirements Module **580**, similar to the Preferences Module **572**, is operable to determine display requirements for an application **564** or other component. An application can have a set display requirement that must be observed. Some applications require a particular display orientation. For example, the application "Angry Birds" can only be displayed in landscape orientation. This type of display requirement can be determined or received, by the Requirements Module **580**. As the orientation of the device changes, the Requirements Module **580** can reassert the display requirements for the application **564**. The Display Configuration Module **568** can generate a display configuration that is in accordance with the application display requirements, as provided by the Requirements Module **580**.

The Event Module **584**, similar to the Gesture Module **576**, is operable to determine one or more events occurring with an application or other component that can affect the user interface. Thus, the Event Module **584** can receive event information either from the event buffer **556** or the Task Management module **540**. These events can change how the tasks are bound to the displays. The Event Module **584** can collect state change information from other Framework **520** components and act upon that state change information. In an example, when the phone is opened or closed or when an orientation change has occurred, a new message may be rendered in a secondary screen. The state change based on the event can be received and interpreted by the Event Module **584**. The information about the events then may be sent to the Display Configuration Module **568** to modify the configuration of the display.

The Binding Module **588** is operable to bind the applications **564** or the other components to the configuration determined by the Display Configuration Module **568**. A binding associates, in memory, the display configuration for each application with the display and mode of the application. Thus, the Binding Module **588** can associate an application with a display configuration for the application (e.g. landscape, portrait, multi-screen, etc.). Then, the Binding Module **588** may assign a display identifier to the display. The display identifier associated the application with a particular display of the device **100**. This binding is then stored and provided to the Display Controller **544**, the other components of the OS **516**, or other components to properly render the display. The binding is dynamic and can change or be updated based on configuration changes associated with events, gestures, state changes, application preferences or requirements, etc.

User Interface Configurations:

With reference now to FIGS. **6**A-J, various types of output configurations made possible by the device **100** will be described hereinafter.

FIGS. **6**A and **6**B depict two different output configurations of the device **100** being in a first state. Specifically, FIG. **6**A depicts the device **100** being in a closed portrait state **304** where the data is displayed on the primary screen **104**. In this example, the device **100** displays data via the touch sensitive display **110** in a first portrait configuration **604**. As can be appreciated, the first portrait configuration **604** may only display a desktop or operating system home screen. Alternatively, one or more windows may be presented in a portrait orientation while the device **100** is displaying data in the first portrait configuration **604**.

FIG. **6**B depicts the device **100** still being in the closed portrait state **304**, but instead data is displayed on the secondary screen **108**. In this example, the device **100** displays data via the touch sensitive display **114** in a second portrait configuration **608**.

It may be possible to display similar or different data in either the first or second portrait configuration **604**, **608**. It may also be possible to transition between the first portrait configuration **604** and second portrait configuration **608** by providing the device **100** a user gesture (e.g., a double tap gesture), a menu selection, or other means. Other suitable

gestures may also be employed to transition between configurations. Furthermore, it may also be possible to transition the device **100** from the first or second portrait configuration **604**, **608** to any other configuration described herein depending upon which state the device **100** is moved.

An alternative output configuration may be accommodated by the device **100** being in a second state. Specifically, FIG. **6**C depicts a third portrait configuration where data is displayed simultaneously on both the primary screen **104** and the secondary screen **108**. The third portrait configuration may be referred to as a Dual-Portrait (PD) output configuration. In the PD output configuration, the touch sensitive display **110** of the primary screen **104** depicts data in the first portrait configuration **604** while the touch sensitive display **114** of the secondary screen **108** depicts data in the second portrait configuration **608**. The simultaneous presentation of the first portrait configuration **604** and the second portrait configuration **608** may occur when the device **100** is in an open portrait state **320**. In this configuration, the device **100** may display one application window in one display **110** or **114**, two application windows (one in each display **110** and **114**), one application window and one desktop, or one desktop. Other configurations may be possible. It should be appreciated that it may also be possible to transition the device **100** from the simultaneous display of configurations **604**, **608** to any other configuration described herein depending upon which state the device **100** is moved. Furthermore, while in this state, an application's display preference may place the device into bilateral mode, in which both displays are active to display different windows in the same application. For example, a Camera application may display a viewfinder and controls on one side, while the other side displays a mirrored preview that can be seen by the photo subjects. Games involving simultaneous play by two players may also take advantage of bilateral mode.

FIGS. **6**D and **6**E depicts two further output configurations of the device **100** being in a third state. Specifically, FIG. **6**D depicts the device **100** being in a closed landscape state **340** where the data is displayed on the primary screen **104**. In this example, the device **100** displays data via the touch sensitive display **110** in a first landscape configuration **612**. Much like the other configurations described herein, the first landscape configuration **612** may display a desktop, a home screen, one or more windows displaying application data, or the like.

FIG. **6**E depicts the device **100** still being in the closed landscape state **340**, but instead data is displayed on the secondary screen **108**. In this example, the device **100** displays data via the touch sensitive display **114** in a second landscape configuration **616**. It may be possible to display similar or different data in either the first or second portrait configuration **612**, **616**. It may also be possible to transition between the first landscape configuration **612** and second landscape configuration **616** by providing the device **100** with one or both of a twist and tap gesture or a flip and slide gesture. Other suitable gestures may also be employed to transition between configurations. Furthermore, it may also be possible to transition the device **100** from the first or second landscape configuration **612**, **616** to any other configuration described herein depending upon which state the device **100** is moved.

FIG. **6**F depicts a third landscape configuration where data is displayed simultaneously on both the primary screen **104** and the secondary screen **108**. The third landscape configuration may be referred to as a Dual-Landscape (LD) output configuration. In the LD output configuration, the touch sensitive display **110** of the primary screen **104** depicts data in the first landscape configuration **612** while the touch sensitive display **114** of the secondary screen **108** depicts data in the second landscape configuration **616**. The simultaneous presentation of the first landscape configuration **612** and the second landscape configuration **616** may occur when the device **100** is in an open landscape state **340**. It should be appreciated that it may also be possible to transition the device **100** from the simultaneous display of configurations **612**, **616** to any other configuration described herein depending upon which state the device **100** is moved.

FIGS. **6**G and **6**H depict two views of a device **100** being in yet another state. Specifically, the device **100** is depicted as being in an easel state **312**. FIG. **6**G shows that a first easel output configuration **618** may be displayed on the touch sensitive display **110**. FIG. **6**H shows that a second easel output configuration **620** may be displayed on the touch sensitive display **114**. The device **100** may be configured to depict either the first easel output configuration **618** or the second easel output configuration **620** individually. Alternatively, both the easel output configurations **618**, **620** may be presented simultaneously. In some embodiments, the easel output configurations **618**, **620** may be similar or identical to the landscape output configurations **612**, **616**. The device **100** may also be configured to display one or both of the easel output configurations **618**, **620** while in a modified easel state **316**. It should be appreciated that simultaneous utilization of the easel output configurations **618**, **620** may facilitate two-person games (e.g., Battleship®, chess, checkers, etc.), multi-user conferences where two or more users share the same device **100**, and other applications. As can be appreciated, it may also be possible to transition the device **100** from the display of one or both configurations **618**, **620** to any other configuration described herein depending upon which state the device **100** is moved.

FIG. **6**I depicts yet another output configuration that may be accommodated while the device **100** is in an open portrait state **320**. Specifically, the device **100** may be configured to present a single continuous image across both touch sensitive displays **110**, **114** in a portrait configuration referred to herein as a Portrait-Max (PMax) configuration **624**. In this configuration, data (e.g., a single image, application, window, icon, video, etc.) may be split and displayed partially on one of the touch sensitive displays while the other portion of the data is displayed on the other touch sensitive display. The Pmax configuration **624** may facilitate a larger display and/or better resolution for displaying a particular image on the device **100**. Similar to other output configurations, it may be possible to transition the device **100** from the Pmax configuration **624** to any other output configuration described herein depending upon which state the device **100** is moved.

FIG. **6**J depicts still another output configuration that may be accommodated while the device **100** is in an open landscape state **348**. Specifically, the device **100** may be configured to present a single continuous image across both touch sensitive displays **110**, **114** in a landscape configuration referred to herein as a Landscape-Max (LMax) configuration **628**. In this configuration, data (e.g., a single image, application, window, icon, video, etc.) may be split and displayed partially on one of the touch sensitive displays while the other portion of the data is displayed on the other touch sensitive display. The Lmax configuration **628** may facilitate a larger display and/or better resolution for displaying a particular image on the device **100**. Similar to other output configurations, it may be possible to transition the device **100** from the Lmax configuration **628** to any other output configuration described herein depending upon which state the device **100** is moved.

The device **100** manages desktops and/or windows with at least one window stack **700**, **728**, as shown in FIGS. **7**A and **7**B. A window stack **700**, **728** is a logical arrangement of active and/or inactive windows for a multi-screen device. For example, the window stack **700**, **728** may be logically similar to a deck of cards, where one or more windows or desktops are arranged in order, as shown in FIGS. **7**A and **7**B. An active window is a window that is currently being displayed on at least one of the touch sensitive displays **110**, **114**. For example, windows **104** and **108** are active windows and are displayed on touch sensitive displays **110** and **114**. An inactive window is a window that was opened and displayed but is now "behind" an active window and not being displayed. In embodiments, an inactive window may be for an application that is suspended, and thus, the window is not displaying active content. For example, windows **712**, **716**, **720**, and **724** are inactive windows.

A window stack **700**, **728** may have various arrangements or organizational structures. In the embodiment shown in FIG. **7**A, the device **100** includes a first stack **760** associated with a first touch sensitive display **110** and a second stack associated with a second touch sensitive display **114**. Thus, each touch sensitive display **110**, **114** can have an associated window stack **760**, **764**. These two window stacks **760**, **764** may have different numbers of windows arranged in the respective stacks **760**, **764**. Further, the two window stacks **760**, **764** can also be identified differently and managed separately. Thus, the first window stack **760** can be arranged in order from a first window **704** to a next window **720** to a last window **724** and finally to a desktop **722**, which, in embodiments, is at the "bottom" of the window stack **760**. In embodiments, the desktop **722** is not always at the "bottom" as application windows can be arranged in the window stack below the desktop **722**, and the desktop **722** can be brought to the "top" of a stack over other windows during a desktop reveal. Likewise, the second stack **764** can be arranged from a first window **708** to a next window **712** to a last window **716**, and finally to a desktop **718**, which, in embodiments, is a single desktop area, with desktop **722**, under all the windows in both window stack **760** and window stack **764**. A logical data structure for managing the two window stacks **760**, **764** may be as described in conjunction with FIG. **8**.

Another arrangement for a window stack **728** is shown in FIG. **7**B. In this embodiment, there is a single window stack **728** for both touch sensitive displays **110**, **114**. Thus, the window stack **728** is arranged from a desktop **758** to a first window **744** to a last window **756**. A window can be arranged in a position among all windows without an association to a specific touch sensitive display **110**, **114**. In this embodiment, a window is in the order of windows. Further, at least one window is identified as being active. For example, a single window may be rendered in two portions **732** and **736** that are displayed on the first touch sensitive screen **110** and the second touch sensitive screen **114**. The single window may only occupy a single position in the window stack **728** although it is displayed on both displays **110**, **114**.

Yet another arrangement of a window stack **760** is shown in FIGS. **7**C through **7**E. The window stack **760** is shown in three "elevation" views. In FIG. **7**C, the top of the window stack **760** is shown. Two sides of the window stack **760** are shown in FIGS. **7**D and **7**E. In this embodiment, the window stack **760** resembles a stack of bricks. The windows are stacked on each other. Looking from the top of the window stack **760** in FIG. **7**C, only the top most windows in the window stack **760** are seen in different portions of the composite display **764**. The composite display **764** represents a logical model for the entire display area of the device **100**, which can include touch sensitive display **110** and touch sensitive display **114**. A desktop **786** or a window can occupy part or all of the composite display **764**.

In the embodiment shown, the desktop **786** is the lowest display or "brick" in the window stack **760**. Thereupon, window **1 782**, window **2 782**, window **3 768**, and window **4 770** are layered. Window **1 782**, window **3 768**, window **2 782**, and window **4 770** only occupy a portion of the composite display **764**. Thus, another part of the stack **760** includes window **8 774** and windows **5** through **7** shown in section **790**. Only the top window in any portion of the composite display **764** is actually rendered and displayed. Thus, as shown in the top view in FIG. **7**C, window **4 770**, window **8 774**, and window **3 768** are displayed as being at the top of the display in different portions of the window stack **760**. A window can be dimensioned to occupy only a portion of the composite display **760** to "reveal" windows lower in the window stack **760**. For example, window **3 768** is lower in the stack than both window **4 770** and window **8 774** but is still displayed. A logical data structure to manage the window stack can be as described in conjunction with FIG. **8**.

When a new window is opened, the newly activated window is generally positioned at the top of the stack. However, where and how the window is positioned within the stack can be a function of the orientation of the device **100**, the context of what programs, functions, software, etc. are being executed on the device **100**, how the stack is positioned when the new window is opened, etc. To insert the window in the stack, the position in the stack for the window is determined and the touch sensitive display **110**, **114** to which the window is associated may also be determined. With this information, a logical data structure for the window can be created and stored. When user interface or other events or tasks change the arrangement of windows, the window stack(s) can be changed to reflect the change in arrangement. It should be noted that these same concepts described above can be used to manage the one or more desktops for the device **100**.

A logical data structure **800** for managing the arrangement of windows or desktops in a window stack is shown in FIG. **8**. The logical data structure **800** can be any data structure used to store data whether an object, record, file, etc. The logical data structure **800** can be stored in any type of database or data storage system, regardless of protocol or standard. In embodiments, the logical data structure **800** includes one or more portions, fields, attributes, etc. that store data in a logical arrangement that allows for easy storage and retrieval of the information. Hereinafter, these one or more portions, fields, attributes, etc. shall be described simply as fields. The fields can store data for a window identifier **804**, dimensions **808**, a stack position identifier **812**, a display identifier **816**, and/or an active indicator **820**. Each window in a window stack can have an associated logical data structure **800**. While only a single logical data structure **800** is shown in FIG. **8**, there may be more or fewer logical data structures **800** used with a window stack (based on the number of windows or desktops in the stack), as represented by ellipses **824**. Further, there may be more or fewer fields than those shown in FIG. **8**, as represented by ellipses **828**.

A window identifier **804** can include any identifier (ID) that uniquely identifies the associated window in relation to other windows in the window stack. The window identifier **804** can be a globally unique identifier (GUID), a numeric ID, an alphanumeric ID, or other type of identifier. In embodiments, the window identifier **804** can be one, two, or any number of digits based on the number of windows that can be opened. In alternative embodiments, the size of the window identifier

804 may change based on the number of windows opened. While the window is open, the window identifier 804 may be static and remain unchanged.

Dimensions 808 can include dimensions for a window in the composite display 760. For example, the dimensions 808 can include coordinates for two or more corners of the window or may include one coordinate and dimensions for the width and height of the window. These dimensions 808 can delineate what portion of the composite display 760 the window may occupy, which may the entire composite display 760 or only part of composite display 760. For example, window 4 770 may have dimensions 880 that indicate that the window 770 will occupy only part of the display area for composite display 760, as shown in FIGS. 7*c* through 7E. As windows are moved or inserted in the window stack, the dimensions 808 may change.

A stack position identifier 812 can be any identifier that can identify the position in the stack for the window or may be inferred from the window's control record within a data structure, such as a list or a stack. The stack position identifier 812 can be a GUID, a numeric ID, an alphanumeric ID, or other type of identifier. Each window or desktop can include a stack position identifier 812. For example, as shown in FIG. 7A, window 1 704 in stack 1 760 can have a stack position identifier 812 of 1 identifying that window 704 is the first window in the stack 760 and the active window. Similarly, window 6 724 can have a stack position identifier 812 of 3 representing that window 724 is the third window in the stack 760. Window 2 708 can also have a stack position identifier 812 of 1 representing that window 708 is the first window in the second stack 764. As shown in FIG. 7B, window 1 744 can have a stack position identifier 812 of 1, window 3, rendered in portions 732 and 736, can have a stack position identifier 812 of 3, and window 6 756 can have a stack position identifier 812 of 6. Thus, depending on the type of stack, the stack position identifier 812 can represent a window's location in the stack.

A display identifier 816 can identify that the window or desktop is associated with a particular display, such as the first display 110 or the second display 114, or the composite display 760 composed of both displays. While this display identifier 816 may not be needed for a multi-stack system, as shown in FIG. 7A, the display identifier 816 can indicate whether a window in the serial stack of FIG. 7B is displayed on a particular display. Thus, window 3 may have two portions 732 and 736 in FIG. 7B. The first portion 732 may have a display identifier 816 for the first display while the second portion 736 may have a display identifier 816 for the second display 114. However, in alternative embodiments, the window may have two display identifier 816 that represent that the window is displayed on both of the displays 110, 114, or a display identifier 816 identifying the composite display. In another alternate embodiment, the window may have a single display identifier 816 to represent that the window is displayed on both of the displays 110, 114.

Similar to the display identifier 816, an active indicator 820 may not be needed with the dual stack system of FIG. 7A, as the window in stack position 1 is active and displayed. In the system of FIG. 7B, the active indicator 820 can indicate which window(s) in the stack is being displayed. Thus, window 3 may have two portions 732 and 736 in FIG. 7. The first portion 732 may have an active indicator 820 while the second portion 736 may also have an active indicator 820. However, in alternative embodiments, window 3 may have a single active indicator 820. The active indicator 820 can be a simple flag or bit that represents that the window is active or displayed.

An embodiment of a method 900 for creating a window stack is shown in FIG. 9. While a general order for the steps of the method 900 is shown in FIG. 9. Generally, the method 900 starts with a start operation 904 and ends with an end operation 928. The method 900 can include more or fewer steps or can arrange the order of the steps differently than those shown in FIG. 9. The method 900 can be executed as a set of computer-executable instructions executed by a computer system and encoded or stored on a computer readable medium. Hereinafter, the method 900 shall be explained with reference to the systems, components, modules, software, data structures, user interfaces, etc. described in conjunction with FIGS. 1-8.

A multi-screen device 100 can receive activation of a window, in step 908. In embodiments, the multi-screen device 100 can receive activation of a window by receiving an input from the touch sensitive display 110 or 114, the configurable area 112 or 116, a gesture capture region 120 or 124, or some other hardware sensor operable to receive user interface inputs. The processor may execute the Task Management Module 540 may receive the input. The Task Management Module 540 can interpret the input as requesting an application task to be executed that will open a window in the window stack.

In embodiments, the Task Management Module 540 places the user interface interaction in the task stack 552 to be acted upon by the Display Configuration Module 568 of the Multi-Display Management Module 524. Further, the Task Management Module 540 waits for information from the Multi-Display Management Module 524 to send instructions to the Window Management Module 532 to create the window in the window stack.

The Multi-Display Management Module 524, upon receiving instruction from the Task Management Module 540, determines to which touch portion of the composite display 760, the newly activated window should be associated, in step 912. For example, window 4 770 is associated with the a portion of the composite display 764 In embodiments, the device state module 574 of the Multi-Display Management Module 524 may determine how the device is oriented or in what state the device is in, e.g., open, closed, portrait, etc. Further, the preferences module 572 and/or requirements module 580 may determine how the window is to be displayed. The gesture module 576 may determine the user's intentions about how the window is to be opened based on the type of gesture and the location of where the gesture is made.

The Display Configuration Module 568 may use the input from these modules and evaluate the current window stack 760 to determine the best place and the best dimensions, based on a visibility algorithm, to open the window. Thus, the Display Configuration Module 568 determines the best place to put the window at the top of the window stack 760, in step 916. The visibility algorithm, in embodiments, determines for all portions of the composite display, which windows are at the top of the stack. For example, the visibility algorithm determines that window 3 768, window 4 770, and window 8 774 are at the top of the stack 760 as viewed in FIGS. 7C through 7E. Upon determining where to open the window, the Display Configuration Module 568 can assign a display identifier 816 and possibly dimensions 808 to the window. The display identifier 816 and dimensions 808 can then be sent back to the Task Management Module 540. The Task Management Module 540 may then assign the window a stack position identifier 812 indicating the windows position at the top of the window stack.

In embodiments, the Task Management Module 540 sends the window stack information and instructions to render the window to the Window Management Module 532. The Win-

dow Management Module **532** and the Task Management Module **540** can create the logical data structure **800**, in step **924**. Both the Task Management Module **540** and the Window Management Module **532** may create and manage copies of the window stack. These copies of the window stack can be synchronized or kept similar through communications between the Window Management Module **532** and the Task Management Module **540**. Thus, the Window Management Module **532** and the Task Management Module **540**, based on the information determined by the Multi-Display Management Module **524**, can assign dimensions **808**, a stack position identifier **812** (e.g., window **1 782**, window **4 770**, etc.), a display identifier **816** (e.g., touch sensitive display **1 110**, touch sensitive display **2 114**, composite display identifier, etc), and an active indicator **820**, which is generally always set when the window is at the "top" of the stack. The logical data structure **800** may then be stored by both the Window Management Module **532** and the Task Management Module **540**. Further, the Window Management Module **532** and the Task Management Module **540** may thereinafter manage the window stack and the logical data structure(s) **800**.

Demand for portable electronic devices with high levels of functionality continues to rise and personal electronic devices continue to become increasingly more portable. While computer power, battery life, screen size and overall functionality of portable phones and smart phones continues to increase, user reliance on these devices increases. Many users of such devices rely heavily on such devices for general communication, accessing the internet, cloud computing, and accessing various locally stored information such as contact information, files, music, pictures and the like. It is often desirable therefore to connect such heavily relied on devices to an additional computing device or display, such as a monitor or tablet device, such as a SmartPad (SP) **1000** (see FIG. **10**).

Accordingly, it is desirable for the device **100** to be able to interface with an additional device, such as the SmartPad **1000**, that enables functionality similar to, for example, both a tablet computer system and smart phone. Furthermore, a need exists for the above-described device to allow for various pre-existing features of both devices, such as sending and receiving phone calls and further allowing for the accessibility of applications running on the device **100**. A need also exists for the above device **100** to provide the benefits of both a tablet computer system and cellular phone in one integrative device by allowing for common operations and functionality without compromising the form factor of the device.

One exemplary embodiment is directed toward a selectively removable device and smartpad system. The smartpad system is discussed in greater detail hereinafter, and can have various features for complementing the communications device, such as a smart phone or device **100**. For example, the smartpad may supplement the device **100** by providing increased screen size, increased processor size, increased battery or power supply, or the like. Similarly, the device **100** may compliment the SP **1000** by providing connectivity through one or more wireless networks, access to various stored information, and the like. It will expressly recognized therefore that two or more devices of the present invention may be provided in a connected or docked and generally symbiotic relationship. It will further be recognized that the devices provide various features, benefits and functionality in their independent state(s).

In accordance with one exemplary embodiment, the device **100** is capable of being received by the SP **1000** through a recessed feature of the SP **1000** having corresponding dimensions to the device **100**. In one exemplary embodiment, the SP **1000** is provided and preferably sized for receiving a predetermined device **100**. In alternative embodiments, however, it is contemplated that the SP **1000** is provided, the smartpad capable of receiving a plurality of communications devices of different sizes. In such embodiments, the SP **1000** may receive communications devices of various sizes by, for example, the inclusion of additional elements, such as spacers and various adjustable features.

In accordance with one exemplary embodiment, the device **100** and SP **1000** have a docking relationship that is established when the device **100** is connected to the SP **1000** during various modes of operation. For example, in one embodiment, a system is provided comprising the SP **1000** and the device **100**, the SP **1000** capable of physically receiving the device **100**, wherein the device **100** is operable as the primary computing device. In such an embodiment, the SP **1000** may, for example, simply provide enhanced audio and visual features for the device **100** that comprises its own CPU, memory, and the like. It is further contemplated that the system can be placed in a mode of operation wherein the device **100** docked to the SP **1000** provide it in a more passive mode where, for example, the device **100** draws power from the SP **1000** such as to recharge a battery of the device **100**.

In accordance with another exemplary embodiment, the device **100** and SP **1000** are provided wherein the device **100** is received or docked with the SP **1000** and wherein a substantial area of the device **100** is positioned within one or more compartments of the SP **1000**. For example, where as various known devices comprise docking features which require or result in the docked item to be generally exposed, thereby substantially altering the external dimensions of the host device and/or creating a potential for damaging one or both devices upon impact, an exemplary embodiment contemplates the SP **1000** which receives the device **100** in a manner such that the external dimensions of the SP **1000** are not substantially altered when the devices are connected. In such an arrangement, the device **100** and associated connection means are generally protected and the SP **1000** is allowed to substantially maintain its original shape. In accordance with one exemplary embodiment, the SP **1000** is capable of receiving and/or docking the device **100** wherein the device **100** is received in lockable association with the SP **1000**. As used herein, the term "lockable" is not intended to designate or limit it to any particular arrangement. Rather, lockable is intended to refer to various embodiments as described herein and will be recognized by one of ordinary skill in the art. In one embodiment, the device **100** is connectable to the SP **1000** wherein the SP **1000** comprises extension springs for first electively securing the device **100** in a docked manner and an ejection feature for releasing the device **100** from the SP **1000**. Moreover, as will be described in greater detail below, it should be appreciated that the device **100** and SP **1000** can communicate using wired and/or wireless technology(ies) with equal success. Moreover, and in accordance with another exemplary embodiment, the hinged device **100** is selectively connectable to the SP **1000** wherein the device **100** is received by the SP **1000** in an open position and where in one or more preexisting ports of the SP **1000** correspond with internal receiving features of the SP **1000**, such that the device **100** and the SP **1000** may be operated simultaneously in various modes of use.

In accordance with some exemplary embodiments, the SP **1000** is provided with an eject or release button to facilitate the removal of a stored or docked device **100**.

FIG. **10** illustrates an exemplary SmartPad (SP) **1000** according to an exemplary embodiment. The exemplary SmartPad at least provides a larger touch sensitive display operatively coupleable to device **100**.

While the following description uses the term "smart" in conjunction with the display device **1000**, it is to be appreciated that this term does not necessarily connotate that there is intelligence in the SmartPad. Rather, it is to be appreciated that there can be "intelligence," including one or more of a processor(s), memory, storage, display drivers, etc., in the SmartPad, and/or one or more of these elements shared with the device **100** via, for example, one or more of a port, bus, connection, or the like. In general, any one or more of the functions of the device **100** is extendable to the SmartPad **700** and vice versa.

The exemplary SmartPad **700** includes a screen **1004**, a SP touch sensitive display **1010**, a SP configurable area **1008**, a SP gesture capture region(s) **1012** and a SP camera **1016**. The SP **1000** also includes a port (not visible in this orientation) adapted to receive the device **100** as illustrated at least in FIG. **11**.

The device **100** docks with the SmartPad **1000** via the port on the SP **1000** and the corresponding port **136** on device **100**. As discussed, port **136** in some embodiments is an input/output port (I/O port) that allows the device **100** to be connected to other peripheral devices, such as a display, keyboard, printing device and/or SP **1000**. In accordance with one exemplary embodiment, the docking is accomplished by the device **100** sliding into the left-hand side of the SP **1000**, with the device **100** being in an open state and the device **100** engaging a port in the SP **1000** corresponding to port **136**. In accordance with one exemplary embodiment, the device **100** engages a doored cassette-like slot in the SP **1000** into which the device **100** slides. (See for example FIG. **13**) It should be appreciated however that there may be other configurations for physically and electrically engaging the two devices—in general, the manner of engagement is not important provided the device **100** and SP **1000** are in electrical communication with one another.

The SP **1000** includes a screen **1004**. In some embodiments, the entire front surface of the SP **1000** may be touch sensitive and capable of receiving input by a user touching the front surface of the screen **1004**. The screen **1004** includes touch sensitive display **1010**, which, in addition to being touch sensitive, is also capable of displaying information to a user.

The screen **1004** also includes a configurable area **1008** that has been configured for specific inputs when the user touches portions of the configurable area **1008**. Area **1012***a* is configured to receive a "back" input indicating that a user would like to view information previously displayed. Area **1012***b* is configured to receive a "menu" input indicating that the user would like to view options from a menu. Area **1012***c* is configured to receive a "home" input indicating that the user would like to view information associated with a "home" view.

In other embodiments, areas **1012***a-c* may be configured, in addition to the configurations described above, for other types of specific inputs including controlling features of device **100** and/or device **1000**, some non-limiting examples including adjusting overall system power, adjusting the volume, adjusting the brightness, adjusting the vibration, selecting of displayed items on screen **1004**, operating the SP camera **1016**, operating a microphone, and initiating/terminating of telephone calls. Also, in some embodiments, areas **1012***a-c* may be configured for specific inputs depending upon the application running on device **100**/SP **1000** and/or information displayed on the touch sensitive displays **1010**.

In addition to touch sensing, screen **1004** may also include areas that receive input from a user without requiring the user to touch the display area of the screen. For example, screen **1004** can include gesture capture area **1012**. These areas are able to receive input by recognizing gestures made by a user without the need for the user to actually touch the surface of the display area. In comparison to touch sensitive display **1010** and **1014**, the gesture capture area **1012** may not be capable of rendering a displayed image.

While not illustrated, there may also be a number of hardware components within SP **1000**. As illustrated in FIG. **10**, SP **1000** can include a speaker, a microphone and one or more cameras **1016**. Upon docking the device **100** in the SP **1000**, the corresponding device(s) (e.g., the speaker) in the device **100** could be disabled in favor of the speaker in the SP **1000**. Similarly, other components, such as the screen **1004**, microphone, speaker, etc, could be disabled on the device **100** in favor of the SP **1000**.

In general, the touch sensitive display **1010** may comprise a full color, touch sensitive display. A second area within each touch sensitive screen **1004** may comprise the SP gesture capture region **1012**. The SP gesture capture region **1012** may comprise an area or region that is outside of the SP touch sensitive display **1010** area that is capable of receiving input, for example in the form of gestures provided by a user. However, the SP gesture capture region **1012** does not necessarily include pixels that can perform a display function or capability.

A third region of the SP touch sensitive screen **1004** may comprise the configurable area **1012**. The configurable area **1012** is capable of receiving input and has display or limited display capabilities. In embodiments, the configurable area **1012** may present different input options to the user. For example, the configurable area **1012** may display buttons or other relatable items. Moreover, the identity of displayed buttons, or whether any buttons are displayed at all within the configurable area **1012** of the SP touch sensitive screen **1004** may be determined from the context in which the device **1000** is used and/or operated. In an exemplary embodiment, the touch sensitive screen **1004** comprise liquid crystal display devices extending across at least those regions of the touch sensitive screen **1004** that is capable of providing visual output to a user, and a capacitive input matrix over those regions of the touch sensitive screen **1004** that is capable of receiving input from the user.

As discussed above with reference to FIGS. **4**A through **4**H, the various graphical representations of gesture inputs that may be recognized by the screens **104**, **108** are also recognizable by screen **1004**. As discussed, the gestures may be performed not only by a user's body part, such as a digit, but also by other devices, such as a stylus, that may be sensed by the contact sensing portion(s) of a screen **1004**. In general, gestures are interpreted differently, based on where the gestures are performed (either directly on the display **1004** or in the gesture capture region **1020**). For example, gestures in the display **1010** may be directed to a desktop or application, and gestures in the gesture capture region **1020** may be interpreted as for the system.

In addition to the above, the SP touch sensitive screen **1004** may also have an area that assists a user with identifying which portion of the screen is in focus. This could be a bar of light or in general and indicator that identifies which one or more portions of the SP touch sensitive screen **1004** are in focus. (See for example, FIG. **29**)

One or more display controllers (such as display controllers **216***a*, **216***b* and/or dedicated display controller(s) on the SP **1000**) may be provided for controlling the operation of the touch sensitive screen **1004** including input (touch sensing) and output (display) functions.

In accordance with one exemplary embodiment, a separate touch screen controller is provided for the SP **1000** in addition to each of the controllers for the touch screens **104** and **108**. In accordance with alternate embodiments, a common or shared touch screen controller may be used to control any one or more of the touch sensitive screens **104** and **108**, and/or **1004**. In accordance with still other embodiments, the functions of the touch screen controllers may be incorporated into other components, such as a processor and memory or dedicated graphics chip(s).

In a similar manner, the SP **1000** may include a processor complementary to the processor **204**, either of which may comprise a general purpose programmable processor or controller for executing application programming or instructions. In accordance with at least some embodiments, the processors may include multiple processor cores, and/or implement multiple virtual processors. In accordance with still other embodiments, the processors may include multiple physical processors. As a particular example, the processors may comprise a specially configured application specific integrated circuit (ASIC) or other integrated circuit, a digital signal processor, a controller, a hardwired electronic or logic circuit, a programmable logic device or gate array, a special purpose computer, or the like. The processors generally function to run programming code or instructions implementing various functions of the device **100** and/or SP **1000**.

The SP **1000** can also optionally be equipped with an audio input/output interface/device(s) (not shown) to provide analog audio to an interconnected speaker or other device, and to receive analog audio input from a connected microphone or other device. As an example, the audio input/output interface/device(s) **256** may comprise an associated amplifier and analog to digital converter usable with SP **1000**. Alternatively or in addition, the device **100** can include an integrated audio input/output device **256** and/or an audio jack for interconnecting an external speaker or microphone via SP **1000**. For example, an integrated speaker and an integrated microphone can be provided, to support near talk or speaker phone operations.

Hardware buttons (not shown) but similar to hardware buttons **158** can be included for example for use in connection with certain control operations. Examples include a master power switch, volume control, etc., as described in conjunction with FIGS. **1**A through **1**J. One or more image capture interfaces/devices **1016**, such as a camera, can be included for capturing still and/or video images. Alternatively or in addition, an image capture interface/device **1016** can include a scanner or code reader. An image capture interface/device **1016** can include or be associated with additional elements, such as a flash or other light sources.

Communications between various components of the device **100** and SP **1000** can be carried by one or more buses and/or communications channels. In addition, power can be supplied to one or more of the components of the device **100** and Sp **1000** from a power source and/or power control module **260**. The power control module **260** and/or device **100** and/or SP **1000** can, for example, include a battery, an AC to DC converter, power control logic, and/or ports for interconnecting the device **100**/**1000** to an external source of power.

The middleware **520** may also be any software or data that allows the multiple processes running on the devices to interact. In embodiments, at least portions of the middleware **520** and the discrete components described herein may be considered part of the OS **516** or an application **564**. However, these portions will be described as part of the middleware **520**, but those components are not so limited. The middleware **520** can include, but is not limited to, a Multi-Display Management (MDM) class **524**, a Surface Cache class **528**, a Window Management class **532**, an Activity Management class **536**, an Application Management class **540**, a display control block, one or more frame buffers **548**, an activity stack **552**, and/or an event buffer **556**—all of the functionality thereof extendable to the SP **1000**. A class can be any group of two or more modules that have related functionality or are associated in a software hierarchy.

The MDM class **524** also includes one or more modules that are operable to manage the display of applications or other data on the screen of the SP **1000**. An embodiment of the MDM class **524** is described in conjunction with FIG. **5**B. In embodiments, the MDM class **524** receives inputs from the OS **516**, the drivers **512** and the applications **564**. The inputs assist the MDM class **524** in determining how to display the information required by the user. Once a determination for display configurations is determined, the MDM class **524** can bind the applications **564** to a display configuration. The configuration may then be provided to one or more other components to generate the display on the SP **1000**.

FIG. **11** illustrates an exemplary embodiment showing the device **100** docking with the SP **1000**. More specifically, the device **100** is being inserted into a slot (not shown) on the SP **1000**. On completion of the inserting of device **100** into SP **1000** (See FIG. **12**), device **100** communicates with the SP **1000** via bus or other wired or wireless electrical means **1204**. The device **100** is also connected with, for example, the camera/video camera **1016**, microphone (Mic), and power port **1208**.

In conjunction with the docking of device **100** with SP **1000**, one or more of the devices can begin power management. For example, one or more of the device **100** and SP **1000** can include power supplies, such as batteries, solar, or in general any electrical supply, any one or more of which being usable to supply one or more of the device **100** and SP **1000**. Furthermore, through the use of, for example, an AC power adaptor connected to port **1208**, the SP **1000** can supply power to device **100**, such as to charge device **100**. It will be appreciated that the power management functionality described herein can be distributed between one or more of the device **100** and SP **1000**, with power being sharable between the two devices.

In addition to power management functions, upon the device **100** being docked with the SP **1000**, the displays on device **100** can be turned off to, for example, save power. Furthermore, electrical connections are established between the device **100** and SP **1000** such that the speaker, microphone, display, input capture region(s), inputs, and the like, received by SP **1000** are transferable to device **100**. Moreover, the display on device **1000** is enabled such that information that would have been displayed on one or more of the touch sensitive displays **110** and **114** is displayed on touch sensitive display **1010**. As will be discussed in greater detail herein, the SP **1000** can emulate the dual display configuration of the device **100** on the single display **1010**.

The SP **1000** can optionally be equipped with the headphone jack **1212** and power button **1216**. Moreover, any hardware buttons or user input buttons on the device **100** could be extended to and replicated on the SP **1000**.

This dock event between the device **100** and SP **1000** can be seen as states **336** or **344** in FIG. **3**A. As will be appreciated, and in accordance with one of the illustrative embodiments herein, the device **100** is docked with SP **1000** with the device being in the open state **210**. However, it is to be appreciated that the device **100** can be docked with the SP

1000 in the closed state 304, or docked via, for example, a cable without the device 100 necessarily being inserted into the SP 1000.

FIGS. 13A-B illustrate application reorientation according to an exemplary embodiment of the invention. In particular, FIG. 13A illustrates the device 100 being inserted into the SP 1000. Before being associated with the SP 1000, the device 100 has two applications, both in the landscape mode, represented by application "B" in landscape on a first screen and application "C" in landscape on a second screen (partially obscured by SP 1000).

FIG. 13B illustrates the re-orientation of the windows for the two applications based on the device 100 being associated with the SP 1000, the SP 1000 being in the landscape orientation. In accordance with this exemplary embodiment, application "B" on the device 100 is re-oriented to be in the portrait orientation on the SP 1000, and in a similar manner, application "C" on the device 100 is reoriented to the portrait orientation on the right-hand side the touch sensitive display 1010. As will be appreciated, the reorientation of the application(s) from the device 100 to the SP 1000 can occur in a similar manner for a single application running on the device 100. For example, if there is only one application running on device 100, and the application is running in landscape mode, when the device 100 is docked with the SP 1000, the orientation of the application is reoriented to be appropriate for the current orientation of the SP 1000. For example, if the application on the device 100 is in portrait mode, and the SP 1000 is in landscape mode, the application is reoriented from portrait mode on the device 100 to landscape mode on the SP 1000. In a similar manner, if the application on the device is in landscape mode, and upon being docked to the SP 1000 in portrait mode, the application is reoriented into portrait mode for appropriate viewing on the SP 1000.

In accordance with one exemplary embodiment, the accelerometer 176 on device 100 is used to determine the orientation of both the device 100 and SP 1000, and consequently the orientation of the touch screen display 1010. Therefore, the accelerometer(s) 176 outputs a signal that is used in connection with the display of information to control the orientation and/or format in which information is to be displayed to the user on display 1010. As is to be appreciated, reorientation can include one or more of a portrait to landscape conversion, a landscape to portrait conversion, a resizing, a re-proportioning and/or a redrawing of the window(s) associated with the application(s).

On reorienting of the running application(s), the application(s) is displayed on display 1010 on SP 1000.

In accordance with an optional exemplary embodiment, priority can be given to the application that is in focus. For example, and using again applications "B" and "C" as illustrated in FIG. 13B, if instead application C was in focus before docking, application C could be reoriented and displayed on the left-hand portion of display 1010, and application B, which was not in focus before docking, displayed on the right-hand portion of display 1010 upon docking

In accordance with another optional embodiment, the application in focus could be displayed in full-screen mode on display 1010 with the application(s) not in focus placed into a window stack that is, for example, in a carousel-type arrangement as discussed hereinafter.

FIG. 14 illustrates an exemplary embodiment of a single application mode for the SP 1000. In the single application mode, all applications are launched and displayed in full screen. The single application mode can be indicated by a multi-tasking icon in the annunciator bar, or at some other location on screen 1004.

Displaying of the application(s) are managed by one or more of the display controller 544, framework 520, window management module 532, display configuration module 568, as well as middleware 520 and associated classes. In single application mode, all dual screen capable applications can be launched in either a dual screen or max mode, where the application is displayed substantially filling the display 1010. This is applicable to when the SP 1000 is either in the portrait mode, as illustrated in FIG. 14, or in the landscape mode, as illustrated in FIG. 15. In these figures, the "A" represents the single application with the X1, X2 being variables representing the coordinates and/or location of the window in which the application "A" is to be displaced. A similar notation is used hereinafter for the multi-application mode, with it being appreciated that, for example, X1 may contain the coordinate information for the displaying of the window for a first application, and X2 may contain the coordinate information for the displaying of a window corresponding to a second application, and so on.

Therefore, in one exemplar embodiment, when a single application is executed, a single application can launch in the full screen mode and can be correlated to the max mode as discussed in relation to FIG. 6I where a single application spans both screens of the device 100. This max mode is applicable to both the portrait and landscape orientations as illustrated in FIG. 14 and FIG. 15 with the display configuration module 568 appropriately (re)sizing the window for the application to fit on substantially all or all of the display 1010.

This resizing can occur regardless of whether a native application on the device 100 actually supports the orientation of the SP 1000. Therefore, even if the application does not support a particular orientation on device 100, the display configuration module 568 can appropriately re-render and/or re-size the window for the application for appropriate display on the SP 1000.

FIG. 16 and FIG. 17 illustrate an exemplary method of rending a single application, that is a dual screen application, in the portrait max mode and landscape max mode, respectively. More specifically, in FIG. 16, the rendering of a dual screen application in portrait mode will display on display 1010 one of the two screens substantially or completely filling display 1010. A user then, for example using a gesture, could scroll between the two screens of the single application. In the landscape mode, as illustrated in FIG. 17, the screen 1010 is divided into a first portion 1704 and a second portion 1708. In this exemplary embodiment, the first screen of the dual screen application is rendered in first portion 1704, and the second screen of the dual screen application is rendered in the second portion 1708. While a certain portion of the screen 1010 is illustratively logically divided for the first portion 1704 and the second portion 1708, it should be appreciated that the screen real estate assigned to each portion can vary, for example, based on one or more of optimum display for the window(s), type of information being displayed in each portion, user preferences, rules associated with the application, and/or the like.

In accordance with a first example, the first portion is allocated one third of the screen 1010's resolution, while the second portion 1708 is allocated two thirds of the screen real estate. In accordance with another example, the screen 1010 is split 50/50. In accordance with yet another example, the first portion could be allocated 70% of the screen 1010's real estate, while the second portion 1708 could be allocated 30%. The managing and resizing of these windows can again be done in cooperation with the display configuration module 568, as well as the windows management module 532 and

display controllers for successful rendering of the location of the window(s) on the SP **1000**.

As will be appreciated, and in a manner similar to the operation of device **1000**, should the SP **1000** change orientation (e.g., from landscape to portrait or vice versa) the window(s) for the application(s) can be redrawn in the appropriate orientation taking into account window prioritization based on whether a particular application and current focus is for a dual screen application or a single screen application.

Focus can also be taken into consideration when determining which window of the application should be displayed when the SP **1000** is in the portrait position. For example, if the application is an e-mail client, and the application natively is displayed on dual screens on device **1000** (a first screen being directed toward showing inbox content, and the second screen being a preview window for a specific item in the inbox) the system can evaluate which window is currently in focus, and ensure that window is displayed in the portrait max mode when the SP **1000** is in the portrait orientation.

In FIG. **17** the SP **1000** is configured to merge windows from the dual screen application on to a single display **1010**. In this landscape orientation, data (e.g., a single image, application, window, icon, video, etc.) from a first window is displayed in a first portion of the display **1010** while data (e.g., a single image, application, window, icon, video, etc.) is shown in a second portion of the display **1010**. Similar to other output configurations, it may be possible to transition the SP **1000** from the shown output configuration to any other output configuration described herein, depending on, for example, into which state the SP **1000** is moved.

Some other exemplary embodiments of windows management within the SP **1000** upon the device **100** docking with the SP **1000** are as follows: For example, a device **100** is docked to the SP **1000**, with the SP **1000** in a portrait orientation and there are two single-screen applications running on the device **1000**, the application in focus is placed in a lower portion of the display **1010**, and the application not in focus is placed on an upper portion of the display **1010**. Another exemplary scenario, where the device **100** is docked to a portrait-oriented SP **1000** where one dual-screen application is running on the device **100** and the SP **1000** is in a dual application mode, applies gravity drop as discussed herein.

In another exemplary scenario, where the device **100** is running two single-screen applications, and the SP **1000** is in a landscape dual application mode, the first application is assigned to a first portion of the display **1010** and the second application is assigned to a second portion of the display **1010**.

In yet another exemplary scenario where the device **100** is running one dual-screen application and the SP **1000** is in dual application landscape mode, both screens of the dual screen application can be shown on the SP **1000**.

Stickiness can also apply to the SP **1000** such that, for example, when a first application is in focus, upon docking to a single application mode SP **1000**, the application remains visible after docking. As another example of stickiness, if a second application is in focus upon docking to a single application mode SP **1000**, application two remains visible after docking

In accordance with another example, the device **100** is running one dual-screen application and is docked to a landscape-oriented SP **1000** in max mode, the windows are reoriented to be side-by-side, opposed to one above the other.

FIGS. **18** through FIG. **21** generally illustrate the management and display of a virtual keyboard **1804** on display **1010**. More specifically, in FIG. **18**, in portrait mode, the virtual keyboard **1804** is positioned below application area **1808**, where an application is displayed in, for example, max mode. In general, it is preferred that the keyboard can be glued to the lower-portion of the display **1010**, regardless of whether the SP is in the landscape or portrait mode. However, it is to be appreciated that, for example, based on user preferences, the screen can be glued to another portion of the screen, or can be moved to another location via, for example, a gesture. In FIG. **18**, the application area **1808** displays, for example, a standard application with the virtual keyboard **1804** being displayed in the lower portion of display **1010**. In FIG. **19**, for example, the application area **1908** is showing a dual-screen enabled application in max mode. The keyboard **1804** is again similarly displayed in the lower portion of the display **1010**.

In FIG. **20**, in SP landscape mode, the keyboard **1804** is displayed in the lower portion of display **1010** with the application area **2004** substantially or completely filling the displayable area above the keyboard **1804**. In FIG. **21**, the SP is again in landscape mode and displaying a dual-screen enabled application in max mode, the application area **1 2104** and application area **2 2108**, the keyboard **1804** is displayed below the two application areas.

In general, in the embodiments illustrated in FIG. **18** through FIG. **21**, a first determination is made as to whether a keyboard should be displayed. If the keyboard is to be displayed, the next determination is made as to the orientation of the SP. If the SP is in a portrait mode, the virtual keyboard is presented also in a portrait mode, preferable on the lower portion of the screen. If the SP is in a landscape mode, the keyboard is optionally re-sized to be substantially displayed on a lower portion of the display with, for example, one or more application windows being located above the virtual keyboard. With the orientation of the SP change, the keyboard is also reoriented to be coincident with the orientation of the SP. Similarly, when the keyboard is no longer required, the keyboard is hidden with the application area(s) being expanded to again substantially fill the display **1010**.

FIG. **22** and FIG. **23** illustrate exemplary methods of managing window positions on the SP **1000**. In particular, in FIG. **22**, application X **2204** is in view on display **1010**. On receiving user input, such as the swipe motion represented by **2208** in the gesture capture region **1020**, application X is "scrolled" to the left to be replaced with the dual-screen application A1|A2, as shown in FIG. **23**. If the same gesture **2208** were to be repeated again, application Z would come into view. Similarly, if in FIG. **22** gesture **2208** was in the opposite direction, to the right, application Y would come into view on display **1010**. Scrolling through available windows is of course applicable to both the landscape and portrait mode of the SP in a similar manner. For example, in portrait mode, instead of the gesture traversing from left to right or right to left, the gesture could traverse in a downward motion, or in an upward motion, with the virtual stacks of the windows being located "above" or "below" the device, similar to a rolodex. Thus, when the user initiates a downward type gesture, the next application "above" is displayed on display **1010**.

FIG. **24** illustrates the multi application mode of the SP **1000**, wherein in the multi application mode the SP **1000** emulates the device **100** in its mini-tablet form—with this mode optionally being invoked by selection of a multi application button (shown and described hereinafter). A simplified way of understanding this mode is to appreciate that the mode emulates the device **100** being opened. In this multi application mode, the SP **1000** can inherit the rules regarding the display of information on the device **100**—For example, that all applications are launched in single screen mode. One

exception could be applications that support a max mode can be by default automatically expanded to this mode if provided the opportunity.

In this mode, each application has the ability to determine how the application appears in each orientation (e.g., portrait and landscape).

FIG. **26** illustrates an exemplary method of managing the multiple application mode of the SP **1000**. In the multiple application mode, multiple applications can be managed and displayed within the display **1010**. In multi application mode, the SP**1000** having the single screen emulates the dual screens of the device **100**. To initiate the multiple application mode, a button/toggle **2618** is selected, which allows the user to select multiple applications for display in the display **1010**. In this exemplary embodiment, a first application **2604** C, is shown in the upper-portion of the portrait mode SP **1000** and a second application **2608** D, is shown in a lower-portion of screen **1010**. In conjunction with the displaying of multiple applications in the multiple application mode, focus indicator **2616** can be provided to assist the user with identifying which application is in focus. As discussed, this focus indicator can be a light bar, or other indicator (such as an indicator in the screen **1010** or beside **2608**) drawing the user's attention to which application is in focus. In the exemplary embodiment in FIG. **26**, application D **2608** is in focus as represented by the focus bar **2616**. In accordance with this exemplary embodiment, and while the focus bar **2616** is shown in the gesture capture region **1020**, it should be appreciated that the focus indicator could be located in some other portion of the SP **1000**. For example, the window for the application in focus could be slightly re-sized to allow for the display of a bar of pixels adjacent to the window, which would similarly alert the user to the fact that that application is in focus. Similarly, the application in focus could appear at normal brightness while the application not in focus could be slightly dimmed. In general, any technique could be used to assist the user in readily determining which application is in focus.

To change focus, a user could use any of the gestures discussed herein or could, for example, simply touch the area where application C is displayed, thereby changing focus to application C, at which point a corresponding relocation of the focus indicator **2616** to adjacent to application C would occur.

FIG. **27** illustrates a similar scenario for a landscape mode SP **1000**. In particular, and upon selection of the multi application mode, the display **1010** is divided between, in this example, a first application D **2712**, and a second application F **2708**. Here, application D is displayed on the right-hand portion of display **1010** and application F displayed on the left-hand portion of display **1010**. While in this exemplary embodiment, the display real estate is split 50/50 between the two applications, it should be appreciated that one application could be displayed on a larger portion of the display **1010** than the other. In this particular exemplary embodiment, application D is in focus, as represented by focus indicator **2416**.

In the multiple application mode, in both portrait and landscape orientations, each application could have its own associated window stack as show in FIG. **22** and FIG. **23**, or there could be one stack shared between all of the displayed applications. More specifically, if each application has its own stack, with a stack structure similar to that illustrated in FIG. **22**, a stack would be available for the first application, such as application C, and a similar stack would be available for application D. Each of these stacks could be independently scrolled through using, for example, a gesture as discussed above.

FIG. **28** illustrates an exemplary method for managing screen display characteristics according to another embodiment of this invention. In accordance with this embodiment, a determination is made whether an application can be maximized, and if it can be maximized, it is expanded to the dual screen mode or max mode, as appropriate, to substantially fill the display **1010** as illustrated in the figure. Here, application E**1**, which is an application that can be maximized, has been expanded using the max mode to substantially or completely fill display **1010**.

In FIG. **28**, button **2618** allows a user to toggle between a single screen mode (as illustrated in FIG. **28**) and an emulated dual screen mode, for example, as illustrated in FIG. **26** and FIG. **27**. Here, button **2618** does not include the "|" therefore indicating to the user the SP **1000** is in single screen mode.

FIG. **29** illustrates an exemplary method of managing windows. In this exemplary embodiment, and similar to the operation of the device **100**, when the last application in the stack is moved to the side, the desktop is displayed. Even more specifically, as shown in FIG. **29**, application F **2908** is displayed in an upper portion of display **1010** and the desktop **2912** is displayed in the lower portion of display **1010**. Here the desktop is in focus, as illustrated by the focus indicator **2916**. This configuration is available since the user has selected the dual-screen emulation mode button **2618**.

FIG. **30** illustrates an exemplary method of displaying a keyboard according to one embodiment. In particular, when the SP is in portrait mode, the SP will have a keyboard area **3004** and an application area **3008**. Upon display of the keyboard **3004**, the application in application area **3008** is resized to substantially or completely fill the area of the screen not occupied by the keyboard **3004**.

FIG. **31**A and FIG. **31**B illustrate desktop availability in both the single application mode and dual application mode in both the SP landscape mode and SP portrait mode. In particular, and in accordance with an exemplary embodiment, the desktop **3104** will occupy the entirety of the screen **1010**. Additionally, and in accordance with this exemplary embodiment where the desktop is shown in a full-screen mode, the annunciator bar **1312** can be expanded across the entirety of the screen **1010**. This can occur in both the portrait mode as shown in FIG. **31**A as well as the landscape mode as illustrated in FIG. **31**B. From here, upon selection of the application launcher **3116**, the application launcher can optionally expand across the entirety of the screen **1010** in either the portrait or landscape mode. Similarly, the file explorer, which is launched by pressing the file explorer button **3120**, can be similarly expanded into substantially all or all of the screen **1010** space.

FIG. **32**A and FIG. **32**B illustrate screen redrawing that may required to transition the desktop from the device **100** to the SP **1000**. In particular, in FIG. **32**A, six exemplary desktop panels are shown **3204-3224**. These desktop panels are moveable in a carousel-like fashion based on gesture input from a user. However, it may not be possible to directly translate these panels to display correctly on the SP **1000** without the panels being distorted or not occupying the entirety of the screen **1010**. Accordingly, in accordance with one exemplary embodiment, one or more of the panels **3204-3224** can be resized when displayed on the SP **1000** to accommodate all or substantially all of the screen **1010**. In accordance with another exemplary embodiment, more than two of the panels can be shown on the screen **1010**, such as a portion of panel D**2** **3208**, a portion of panel D**3** **3212** and a portion of panel D**4** **3216**. In this manner, the desktop illustrated on the SP **1000** will have a similar look-and-feel to the desktop panels shown on device **100**. The same carousel-like motion

is available via a gesture input to the SP **1000** such that a user can scroll to the one or more panels of the desktop.

FIG. **33** illustrates an exemplary method of emulating the multi-screen display of the device **100** on the SP**1000**. In particular, control begins in step S**4500** and continues to step S**4502**. In step S**4502**, the desktop is displayed on the SP. Next, in step S**4504**, the desktop is logically divided on the SP into, for example, two sections. Then in step S**4506**, a first screen of the desktop is displayed in a first logical portion of the SP display. Then, in step S**4508**, a second screen of the desktop is displayed in a second logical portion of the SP display. Control then continues to step S**4510**.

In step S**4510**, carousel movement of the "panels" shown in the display can be initiated through user input, such as a gesture. Control then continues to step S**4512** where the control sequence ends.

FIG. **34** outlines an exemplary method of displaying multiple "panels" of the desktop on the SP. In particular, control begins in step S**4600** and continues to step S**4602**. In step S**4602**, a portion of the desktop is displayed on the SP. Next, in step S**4604**, the desktop is logically divided on the smartpad to accommodate multiple desktop "panels." Then, in step S**4608**, the first screen or panel of the desktop is displayed in one logical portion of the SP display. Then, in step S**4610**, a second screen or panel of the desktop is displayed bridging a first and a second logical portion of the SP display. Then, a third screen or panel of the desktop is displayed in the second logical portion of the SP display. Control then continues to step S**4614**.

In step S**4614** carousel movement of the panels can be affected by, for example, an input of a gesture by the user. Control then continues to step S**4616** where the control sequence ends.

FIG. **35** outlines an exemplary method of windows management in multiple application mode. In particular, control begins in step S**4800** and continues to step S**4802**. In step S**4802**, multiple application mode is entered. Next, in step S**4804**, the windows stack is arranged with one or more applications being partially visible behind a first application. Next, in step S**4806**, the stack can be arranged with one or more applications also partially being visible behind a second application. Then, in step S**4808**, and upon receiving an input gesture from a user, carousel-like scrolling can be enabled through the stack until the end of the stack is reached, or in a second embodiment, the stack can have a "circular" arrangement where continuous scrolling through the stack is possible. Control then continues to step S**4810** where the control sequence ends.

To avoid unnecessarily obscuring the present disclosure, the preceding description omits a number of known structures and devices. This omission is not to be construed as a limitation of the scopes of the claims. Specific details are set forth to provide an understanding of the present disclosure. It should however be appreciated that the present disclosure may be practiced in a variety of ways beyond the specific detail set forth herein.

For example, the smartpad could have multiple physical and/or logical screens/displays. Additionally, the smartpad could be used with one or more input devices such as a stylus, mouse, or the like. Moreover, the smartpad could be populated with a processor, memory, communications means and the like that would allow for stand-alone operation. Even further, the smartpad could be associated or docked with other types of communications devices such as a smartphone such that the smartpad could be used as a display and/or I/O interface therefore.

An embodiment of a method **4900** for executing an application is shown in FIG. **36**. While a general order for the steps of the method **4900** is shown in FIG. **36**. Generally, the method **4900** starts with a start operation **4904** and ends with an end operation **4940**. The method **4900** can include more or fewer steps or can arrange the order of the steps differently than those shown in FIG. **36**. The method **4900** can be executed as a set of computer-executable instructions executed by a computer system and encoded or stored on a computer readable medium. Hereinafter, the method **4900** shall be explained with reference to the systems, components, modules, software, data structures, user interfaces, etc. described in conjunction with FIGS. **1-35**.

An application is executed, in step **4908**. In embodiments, a processor **204** receives indication to execute an application through a user interface **110**, **114**, **112**, **116**, etc. The indication can be a selection of an icon associated with the application. In other embodiments, the indication can be a signal generated from another application or event, such as receiving an e-mail or other communication, which causes the application to execute automatically. The processor **204** can retrieve the application **564***a* from the application store **560** and begin its execution. In executing the application **564***a*, a user interface can be generated for a user.

In creating a user interface, the application **564***a* can begin executing to create a manifest, in step **4912**. A manifest is a data structure that indicates the capabilities of the application **564***a*. The manifest can generally be created from the resources in the resources directory of the application **564***a*. The resources directory can indicate the types of modes, locations, or other indications for how the user interface should be configured in the multi-display device **100**. For example, the several modes can include: "classic mode" that indicates that the application **564***a* is capable of being displayed on a single screen or display **110**/**114**; "dual mode" that indicates that the application **564***a* is capable of being displaced on two or more displays **110** and **114**; "max mode" that indicates the application **564***a* is capable of being displayed or desires to be displayed across multiple displays **110** and **114**; and/or "bilateral mode" that indicates that the application **564***a* is capable of being displayed on 2 or more displays **110** and **114** when the device **100** is in easel mode (see FIGS. **1**I and/or **1**J).

Similarly, the manifest can include a desired or allowed location within the displays **110**/**114**. The possible locations can include: "left", which indicates that the application **564***a* desires to be displayed on the left display **110**; "right", which indicates that the application **564***a* desires to be displayed on the right display **114**; and/or other indications of where a location should be including possible "top" and/or "bottom" of one or more of the displays **110**/**114**.

The application **564***a* can also indicate that it desires to be displayed in a "minimum" window, which is a window that occupies less than the full area of a single display. There may be other modes possible for the application **564***a*, which may be included in the manifest. The manifest can be sent from the application **564***a* to the multi-display management module **524**.

The multi-display management module **524** can receive the manifest, in step **4916**. In receiving the manifest, the multi-display management module **524** can use the information to determine a display binding for the application **564***a*. The manifest may be received more than once from the application **564***a* based on changes in how the application **564***a* is being executed, where the application **564***a* desires to have a different display setting for the new mode. Thus, with the manifest, the application **564***a* can indicate to the multi-dis-

play management module **524** how best to or what is the desired for the application's user interface. The multi-display management module **524** can use the information in the manifest to determine the best fit for the user interface depending on how the device **100** is currently configured.

The multi-display management module **524** can determine the application display mode, in step **4920**. Here the multi-display management module **524** receives or retrieves an indication of the device **100** configuration. For example, the multi-display management module **524** can determine if the device is in single display configuration (see FIG. **6**A, **6**B, **6**D, or **6**E), dual display configuration (see FIG. **6**C or **6**F), bilateral display configuration (see FIG. **6**G or **6**H), or one of the other display configurations (see FIG. **6**I or **6**J).

Further, the multi-display management module **524** can determine if the device **100** is in a portrait or landscape orientation. With this information, the multi-display management module **524** may then consider the capabilities or preferences listed for the application **564***a* in the received manifest. The combined information may then allow the multi-display management module **524** to determine a display binding. The display binding can include which of the one or more displays **110** and/or **114** are going to be used to display the application's user interface(s). For example, the multi-display management module **524** can determine that the primary display **110**, the secondary display **114**, or all displays **110** and **114** of the device **100** will be used to display the application's user interface.

The display modes setting can be assigned by creating or setting a number in the display binding. This number can be "0" for the primary display **110**, "1" for the secondary display **114**, or "2" for dual displays **110** and **114**. The display mode setting can also indicate if the application **564***a* should display the user interface in portrait or landscape orientation. Further, there may be other settings, for example, providing a max mode or other setting that may indicate how the application **564***a* is to be displayed on the device. The display binding information is stored in a data structure to create and set a binding, in step **4924**.

The established display binding may then be provided, by the multi-display management module **524**, to the application **564***a*, in step **4928**. The provided display binding data structure can become an attribute of the application **564***a*. An application **564***a* may thereinafter store the display binding attribute in the memory of the device **100**. The application **564***a* with the display binding may then generate a user interface based on this display binding. The application **564***a* may be unaware of the position of the display **110**/**114** but may, from the display binding, be able to determine the size of the available user interface to generate a window that has particular characteristics for that display setting.

When a configuration change happens to the device **100**, the multi-display management module **524** may change the display binding and send a new display binding to the application **564***a*. In embodiments, the multi-display management module **524** may indicate to the application **564***a* that there is a new binding or, in other embodiments, the application **564***a* may request a display configuration change or a new display binding, in which case the multi-display management module **524** may send a new display binding to the application **564***a*. Thus, the multi-display management module **524** can change the configuration of the display for the application **564***a* by altering the display binding for the application **564***a* during the execution of that application **564***a*.

The multi-display management module **524** thereinafter, while the application **564***a* is executing, can determine if there has been a configuration change to the device **100**, in step **4932**. The configuration change may be an event (see FIGS. **3**A and **3**B) triggered by one or more signals from one or more hardware sensor **172**, **176**, etc. For example, if the device **100** is changed from portrait **304** to landscape **340** orientation, Hall effect sensors **172** may indicate to the framework **520** that a display configuration change has been made. Other changes may include transitions from a single display **304** to a dual display configuration **320**, by opening the device. Other types of configuration changes may be possible and may be signaled to alert the multi-display management module **524** of the configuration change. If a configuration change has been made, the method **4900** proceeds YES to step **4920** so that the multi-display management module **524** can determine new application display mode settings and create a new display binding, which may be passed to the application **564***a*. If there are no configuration changes, the method **4900** precedes NO to step **4936**.

In step **4936**, a new application mode change may be determined. Application mode changes can also occur in the application **564***a*, and thus, the application **564***a* can determine if something has occurred within the application **564***a* that requires a different display setting. The mode change can create a desire to change the display **110**/**114**, and thus, require the application **564***a* to generate a new manifest. If the application **564***a* does sense a mode change or an event has occurred that requires a change in display setting, the method **4900** proceeds YES back to step **4912**. At step **4912**, a new manifest or preference is created by the application **564***a* that may be received by the multi-display management module **524** to determine if the multi-display management module **524** can change the display binding. If it is possible to provide the preferred display, the multi-display management module **524** can create a new display binding and send display binding back to the application **564***a* and allow the application **564***a* to alter its user interface. If no mode change is sensed or an event is not received to create a mode change, the method **4900** proceeds NO to end operation **4940**.

FIG. **37**A depicts a device **100** with first **104** and second **108** screens. In this example, the screens **104**, **108** are in a dual portrait mode or orientation. Moreover, the device **100** is shown executing or accessing a first application **564***a*. In the state depicted in FIG. **37**A, the first screen **104** displays a first set of information comprising a first page **708** of the first application **564***a*. The second screen **108** displays a second set of information comprising a second page **3712** of the first application **564***a*. As an example, and without limitation, the first application **564***a* may comprise a browser application. Moreover, the first page **3708** may comprise a control page or other ancillary page **3710**. For example, and without limitation, the control page **3710** may present a list of bookmarks, a list of most visited websites, or a browsing history. The second page **3712** may comprise a content page or other primary page **3714**. As examples, and without limitation, the content page **3714** may comprise the content of a website accessed by the browser application, or a landing page generated by the browser application. The gesture **3716** shown in FIG. **37**A depicts a gesture or other touch input provided by a user to minimize the view of the first application **564***a* from two pages to one. As shown, the gesture **3716** may be entered in an area or region of the screens **104**, **108** that is outside of the areas or regions of the screens **104**, **108** in which the pages **3708**, **3712** of the first application **564***a* are presented or displayed. For instance, the gesture **3716** can be received in the gesture capture region **120** of the first screen **104** or the gesture capture region **124** of the second screen **108**. As a further example, the gesture **3716** may be entered in the touch sensitive display region **110** of a first screen **104** or the touch

sensitive display region **114** of the second screen **108**. Although the specific gesture **3716** illustrated in the figure comprises a drag gesture **400**, other gestures or inputs can be used, depending on the configuration of the device **100**.

FIG. **37**B depicts the output of the screens **104**, **108** after the receipt of the gesture **3716** from the user. In particular, the first screen **104** now displays a page or other output **3720** related to a second application **564***b* in a stack **760**, or alternatively a desktop view, for example where a second application **564***b* is not active. The second screen **108** continues to display the second page **3712** of the first application **564***a*. Accordingly, the minimization operation command entered with respect to the display generated in association with the first application **564***a* has the effect of discontinuing or dismissing the first page **3708** of the first application **564***a*. The display of the second page **3712** of the first application **564***a* continues. In particular, any minimization operation performed with respect to the first application **564***a* while the first **3708** and second **3712** pages are displayed results in the first page **3708** (in this example the control or ancillary page **3710**) being closed, while the second page **3712** (in this example the content or primary page **3714**) persists.

FIG. **38**A depicts an output configuration similar or the same as that depicted in FIG. **37**B. However, in FIG. **38**A, input, in this example in the form of a gesture **3724**, comprising a maximization operation command is received with respect to the first application **564***a*. In this example, the gesture **3724** is depicted as a drag gesture **400** received in the gesture capture region **124** of the second screen **108**. Alternatively, the input to perform a maximization operation could have been entered through any other gesture or command operable to maximize the first application **564***a*. The result of the receipt of the gesture **3724** is depicted in FIG. **38**B. In particular, the maximization command results in the display of the first page **3708** associated with the first application **564***a* in the first screen **104**, while the second screen **108** continues to display the second page **3712** associated with the first application **564***a*. Accordingly, when a maximization command is received with respect to the first application **564***a*, and while the second page **3712** associated with the first application **564***a* is being displayed, the first page **3708** is displayed by the first screen **104**, in place of the page **3720** associated with the second application **564***b*. In accordance with further embodiments, where the command to maximize the first application **564***a* is received while the second page **3712** is displayed in the first screen, the maximization operation results in the first page **3708** being displayed in the first screen **104**, and the second page **3712** being displayed in the second screen **108**.

FIG. **39**A depicts another exemplary output of the screens **104**, **108** of the device **100** in accordance with embodiments of the present invention. In this example, the device has been controlled such that the first screen **104** displays the second page **3712** associated with the first application **564***a* in the first screen **104** of the device **100**, while the second screen **108** has been controlled to display a page **3720** associated with a second application **564***b*, or a desktop view. A gesture **3728** or other input comprising a maximization command is depicted. The result of the maximization operation performed in response to that command is shown in FIG. **39**B. In particular, the receipt of the maximization command has resulted in the display of the second page **3712** associated with the first application **564***a* in the second screen **108** of the device **100**, in place of the page **3720** associated with the second application **564***b* or the desktop display. In addition, the first page **3708** of the first application **564***a* is displayed in the first screen **104**.

With reference now to FIG. **40**, aspects of a method for minimizing or maximizing a display of application information with respect to an application **564** that presents information in primary and ancillary pages are depicted. Initially, at step **4004**, a determination is made as to whether a command to open an application **564** has been received. A command to open an application **564** can be entered by a user providing input to the device **100**. Alternatively or in addition, a command to open an application **564** can be received through operation of programming associated with or executed by the device **100**, or through a command received by an interconnected device. Until a command to open an application **564** is received, the process may idle at step **4004**. After a command to open an application **564** is received, the device **100** presents first and second pages of output associated with the opened application **564** (e.g., a first application **564***a*) in the first **104** and second **108** screens of the device **108** (step **4008**). Moreover, in accordance with embodiments of the present invention, one of the pages **3708** or **3712** is a preferred or primary page **3714**, while the other of the pages **3708** or **3712** is an ancillary or secondary page **3710**.

At step **4012**, a determination is made as to whether input has been received from a user minimizing the opened application **564**. If such input has been received, presentation of the preferred or primary page **3714** is continued, while the presentation of the ancillary or secondary page **3710** is discontinued (step **4016**). In accordance with embodiments of the present invention, the preferred page **3714** can occupy either the first **104** or second **108** screen of the device **100**. Moreover, following the receipt of the minimization command, the preferred or primary **3714** page can continue to be presented in the screen **104** or **108** that originally presented that page **3714**. Alternatively, the screen **104** or **108** used to present the primary page **3714** can be changed. Whether the screen **104** or **108** used to present the primary page is switched or not can depend on the nature of the minimization command. For example, if the device **100** is switched from a dual portrait mode to a single portrait mode, the screen **104** or **108** remaining as the primary screen following the change to the single portrait mode can be used to display the primary page **3714**.

After performing minimization, a determination can be made as to whether input from a user in the form of a maximization command has been received (step **4020**). If a command to perform a maximization operation with respect to the application **564** has been received, the first **3708** and second **3712** pages of the application **564** are presented by the device **100** (step **4024**). That is, in accordance with embodiments of the present invention, both the primary **3714** and the secondary **3710** pages are displayed as a result of the maximization operation. Moreover, the maximization command can result in the display of the primary page **3714** in a predetermined one of the first **104** and second **108** screens, without regard to whether doing so results in moving an auxiliary page **3710** displayed when the maximization command was received to a different screen **104** or **108**.

After acting on a maximization command at step **4024**, or after determining that no input has been received at steps **4012** or **4020**, a determination may be made as to whether the device **100** has been powered off (step **4028**). If the device **100** has not been powered off, the process can return to step **4004**. Alternatively, the process can end.

In accordance with embodiments of the present invention, methods disclosed herein can be performed by the execution of application programming stored in memory **208**, **508** and by a processor **204**, **504**. For example, a windows management module or class **532** can include functionality to receive

and act on input received from a user. Moreover, such input can include window management input, and can include the execution of steps to open or close applications **564**, or windows presenting pages associated with such application **564**, for example in connection with minimization and maximization operations. In addition, although certain embodiments have been described in connection with operation on a device **100** having first **104** and second **108** screens, the invention is not limited to operation on such a device. For example, embodiments of the present invention can be performed on a device or a combination of devices operating in concert with one another that have more than two screens, and/or in connection with a screen comprising virtual screens or windows.

Furthermore, while the exemplary aspects, embodiments, and/or configurations illustrated herein show the various components of the system collocated, certain components of the system can be located remotely, at distant portions of a distributed network, such as a LAN and/or the Internet, or within a dedicated system. Thus, it should be appreciated, that the components of the system can be combined in to one or more devices, such as a tablet-like device, or collocated on a particular node of a distributed network, such as an analog and/or digital telecommunications network, a packet-switch network, or a circuit-switched network. It will be appreciated from the preceding description, and for reasons of computational efficiency, that the components of the system can be arranged at any location within a distributed network of components without affecting the operation of the system. For example, the various components can be located in a switch such as a PBX and media server, gateway, in one or more communications devices, at one or more users' premises, or some combination thereof. Similarly, one or more functional portions of the system could be distributed between a telecommunications device(s) and an associated computing device.

Furthermore, it should be appreciated that the various links connecting the elements can be wired or wireless links, or any combination thereof, or any other known or later developed element(s) that is capable of supplying and/or communicating data to and from the connected elements. These wired or wireless links can also be secure links and may be capable of communicating encrypted information. Transmission media used as links, for example, can be any suitable carrier for electrical signals, including coaxial cables, copper wire and fiber optics, and may take the form of acoustic or light waves, such as those generated during radio-wave and infra-red data communications.

Also, while the flowcharts have been discussed and illustrated in relation to a particular sequence of events, it should be appreciated that changes, additions, and omissions to this sequence can occur without materially affecting the operation of the disclosed embodiments, configuration, and aspects.

In yet another embodiment, the systems and methods of this disclosure can be implemented in conjunction with a special purpose computer, a programmed microprocessor or microcontroller and peripheral integrated circuit element(s), an ASIC or other integrated circuit, a digital signal processor, a hard-wired electronic or logic circuit such as discrete element circuit, a programmable logic device or gate array such as PLD, PLA, FPGA, PAL, special purpose computer, any comparable means, or the like. In general, any device(s) or means capable of implementing the methodology illustrated herein can be used to implement the various aspects of this disclosure. Exemplary hardware that can be used for the disclosed embodiments, configurations and aspects includes computers, handheld devices, telephones (e.g., cellular, Internet enabled, digital, analog, hybrids, and others), and other hardware known in the art. Some of these devices include processors (e.g., a single or multiple microprocessors), memory, nonvolatile storage, input devices, and output devices. Furthermore, alternative software implementations including, but not limited to, distributed processing or component/object distributed processing, parallel processing, or virtual machine processing can also be constructed to implement the methods described herein.

In yet another embodiment, the disclosed methods may be readily implemented in conjunction with software using object or object-oriented software development environments that provide portable source code that can be used on a variety of computer or workstation platforms. Alternatively, the disclosed system may be implemented partially or fully in hardware using standard logic circuits or VLSI design. Whether software or hardware is used to implement the systems in accordance with this disclosure is dependent on the speed and/or efficiency requirements of the system, the particular function, and the particular software or hardware systems or microprocessor or microcomputer systems being utilized.

In yet another embodiment, the disclosed methods may be partially implemented in software that can be stored on a storage medium, executed on programmed general-purpose computer with the cooperation of a controller and memory, a special purpose computer, a microprocessor, or the like. In these instances, the systems and methods of this disclosure can be implemented as program embedded on personal computer such as an applet, JAVA® or CGI script, as a resource residing on a server or computer workstation, as a routine embedded in a dedicated measurement system, system component, or the like. The system can also be implemented by physically incorporating the system and/or method into a software and/or hardware system.

Although the present disclosure describes components and functions implemented in the aspects, embodiments, and/or configurations with reference to particular standards and protocols, the aspects, embodiments, and/or configurations are not limited to such standards and protocols. Other similar standards and protocols not mentioned herein are in existence and are considered to be included in the present disclosure. Moreover, the standards and protocols mentioned herein and other similar standards and protocols not mentioned herein are periodically superseded by faster or more effective equivalents having essentially the same functions. Such replacement standards and protocols having the same functions are considered equivalents included in the present disclosure.

The present disclosure, in various aspects, embodiments, and/or configurations, includes components, methods, processes, systems and/or apparatus substantially as depicted and described herein, including various aspects, embodiments, configurations embodiments, subcombinations, and/or subsets thereof. Those of skill in the art will understand how to make and use the disclosed aspects, embodiments, and/or configurations after understanding the present disclosure. The present disclosure, in various aspects, embodiments, and/or configurations, includes providing devices and processes in the absence of items not depicted and/or described herein or in various aspects, embodiments, and/or configurations hereof, including in the absence of such items as may have been used in previous devices or processes, e.g., for improving performance, achieving ease and\or reducing cost of implementation.

The foregoing discussion has been presented for purposes of illustration and description. The foregoing is not intended to limit the disclosure to the form or forms disclosed herein.

In the foregoing Detailed Description for example, various features of the disclosure are grouped together in one or more aspects, embodiments, and/or configurations for the purpose of streamlining the disclosure. The features of the aspects, embodiments, and/or configurations of the disclosure may be combined in alternate aspects, embodiments, and/or configurations other than those discussed above. This method of disclosure is not to be interpreted as reflecting an intention that the claims require more features than are expressly recited in each claim. Rather, as the following claims reflect, inventive aspects lie in less than all features of a single foregoing disclosed aspect, embodiment, and/or configuration. Thus, the following claims are hereby incorporated into this Detailed Description, with each claim standing on its own as a separate preferred embodiment of the disclosure.

Moreover, though the description has included description of one or more aspects, embodiments, and/or configurations and certain variations and modifications, other variations, combinations, and modifications are within the scope of the disclosure, e.g., as may be within the skill and knowledge of those in the art, after understanding the present disclosure. It is intended to obtain rights which include alternative aspects, embodiments, and/or configurations to the extent permitted, including alternate, interchangeable and/or equivalent structures, functions, ranges or steps to those claimed, whether or not such alternate, interchangeable and/or equivalent structures, functions, ranges or steps are disclosed herein, and without intending to publicly dedicate any patentable subject matter.

What is claimed is:

1. A method for controlling a display of a device, comprising:

presenting a first page of a first application on a first display of the device, wherein the first page is an auxiliary page;

presenting a second page of the first application on a second display of the device, wherein the second page is a primary page, wherein the first and second pages present different content and are distinct pages, and wherein the auxiliary page is a child of the primary page;

receiving a first input from a user, wherein the first input includes an input to minimize the first application to one of the first and second displays of the device, wherein the second page of the first application is displayed by one of the first display of the device and the second display of the device, and wherein the first page of the first application is not displayed.

2. The method of claim **1**, wherein the first input from the user is received in a gesture capture region of the device, and wherein the gesture capture region is included as part of at least one of the first and second displays of the device.

3. The method of claim **2**, wherein the first page of the first application is presented by a first touch display included in the first display of the device, wherein the second page of the first application is presented by a second touch display included in the second display of the device, and wherein the gesture capture region is outside of an area of the first touch display and is outside of an area of the second touch display.

4. The method of claim **1**, wherein after receiving the first input a first page of a second application is presented by the first display.

5. The method of claim **1**, wherein the first page of the first application includes a modal window, and wherein after receiving the first input the modal window is dismissed.

6. The method of claim **1**, wherein the device is oriented such that the first and second displays are presented in a dual portrait format, and wherein the first input includes a gesture that is input from a side of the device corresponding the first display towards a side of the device corresponding to the second display.

7. The method of claim **6**, wherein as the first input is received the first page of the first application is slid behind the second page of the first application.

8. The method of claim **7**, wherein as the first input is received a first page of a second application is revealed on the first display of the device.

9. The method of claim **1**, wherein the first application is a web browser, and wherein the primary page is a content page that includes web content.

10. The method of claim **1**, further comprising:

after receiving the first input, receiving a second input from the user, wherein the second input includes an input to maximize the first application to both of the first and second displays of the device, wherein the first page of the first application is presented on the first display of the device and the second page is displayed on the second display of the device.

11. The method of claim **10**, further comprising:

after receiving the first input and before receiving the second input, receiving a third input from the user moving the second page of the first application to the first display of the device, wherein while receiving the second input the second page of the first application is moved from the first display of the device to the second display of the device.

12. The method of claim **10**, further comprising:

after receiving the first and second inputs, receiving a third input from the user dismissing the first page of the application, wherein one of a first page of a second application or a desktop is presented by the first display of the device;

after receiving the third input, receiving a fourth input from the user to maximize the first application to the first and second displays of the device, wherein the second display of the device presents the second page of the first application, and wherein the first display of the device presents the first page of the first application.

13. The method of claim **1**, wherein the first display of the device is the left hand display while the device is in a dual-portrait mode, and wherein the second display of the device is the right hand display while the device is in the dual-portrait mode.

14. A device, comprising:

a first display, including:

a touch display, wherein the touch display is located within a first area of the first display;

a gesture capture region, wherein the gesture capture region is located within a second area of the first display;

a second display, including:

a second touch display, wherein the second touch display is located within a first area of the second display;

a second gesture capture region, wherein the second gesture capture region is located within a second area of the second display memory;

a processor in communication with the first display, second display, and memory;

application programming stored in the memory and executed by the processor, wherein the application programming is operable to:

present a first page of a first application in a first portion of the first display;

present a second page of the first application in a second portion of the second display, wherein the first and

second pages present different content and are distinct pages, and wherein the second page is a child of the first page;

receive input entered by a user in the gesture capture region;

in response to a first input entered by the user to minimize the first application to one of the first and second portions of the display, present the second page of the first application in one of the first and second portions of the display and discontinue the presentation of the first page of the application.

15. The device of claim **14**, wherein with the device oriented such that the first and second displays are in a dual portrait mode when the first display on the left and the second display on the right, wherein the first portion of the display corresponds to a first touch display included in the first display, wherein the second portion of the display corresponds to a second touch display included in the second display, and wherein the gesture capture region is included in at least one of the first and second displays in an area outside of the first touch display and the second touch display.

16. The device of claim **15**, wherein the application programming is further operable to receive a second input to maximize the first application to both the first and second touch displays, wherein in response to the second input the first page of the first application is presented by the first touch display and the second page of the first application is presented by the second touch display.

17. The device of claim **16**, wherein prior to receiving the second input the second page of the first application is presented by the first touch display.

18. A non-transitory computer readable medium having stored thereon computer-executable instructions, the computer-executable instructions causing a processor to execute a method for selectively presenting an application across a display of a device, the computer-executable instructions comprising:

instructions to display a first page of a first application on a first display portion of the device;

instructions to display a second page of the first application on a second display portion of the device, wherein the first and second pages present different content and are distinct pages, and wherein the second page is a child of the first page;

in response to a first input received from a user to minimize the first application to one of the first and second display portions of the device, display the second page of the first application on one of the first and second display portions of the device and discontinue the display of the first page of the application.

19. The computer readable medium of claim **18**, wherein the device includes multiple displays, wherein the first display portion of the device includes a first display of the multiple displays, wherein the second display portion of the device includes a second display of the multiple displays, and wherein in response to one of the first input and a second input received from the user the second page of the first application is displayed on the first display of the device.

20. The computer readable medium of claim **19**, wherein in response to an input received from the user to maximize the first application the first page of the first application is displayed on the first display of the device and the second page of the application is displayed on the second display of the device.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE

CERTIFICATE OF CORRECTION

PATENT NO. : 9,158,494 B2
APPLICATION NO. : 13/366483
DATED : October 13, 2015
INVENTOR(S) : Sirpal et al.

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

In the claims

Claim 18, column 54, line 11, after "the first page;" insert -- and --.

Signed and Sealed this
Eighth Day of March, 2016

Michelle K. Lee

Michelle K. Lee
Director of the United States Patent and Trademark Office