

(12) **United States Patent**
Bourque

(10) **Patent No.:** **US 10,500,321 B2**
(45) **Date of Patent:** ***Dec. 10, 2019**

(54) **IMPLANTABLE BLOOD PUMP**

(56) **References Cited**

(71) Applicant: **TC1 LLC**, St. Paul, MN (US)

U.S. PATENT DOCUMENTS

(72) Inventor: **Kevin Bourque**, Reading, MA (US)

845,816 A 3/1907 Prindle
888,654 A 5/1908 Prindle
(Continued)

(73) Assignee: **TC1 LLC**, St. Paul, MN (US)

FOREIGN PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 2 days.

CN 300837668 10/2008
EP 150320 5/1990

This patent is subject to a terminal disclaimer.

(Continued)

OTHER PUBLICATIONS

(21) Appl. No.: **15/594,373**

Antaki et al., Pedia Flow TM Maglev Ventricular Assist Device: A Prescriptive Design Approach, Cardiovascular Engineering and Technology, vol. 1, No. 1, Mar. 2010, pp. 104-121.

(22) Filed: **May 12, 2017**

(Continued)

(65) **Prior Publication Data**

US 2017/0246365 A1 Aug. 31, 2017

Primary Examiner — Eric D. Bertram

(74) Attorney, Agent, or Firm — Kilpatrick Townsend and Stockton LLP

Related U.S. Application Data

(60) Division of application No. 14/735,990, filed on Jun. 10, 2015, now Pat. No. 9,675,741, which is a (Continued)

(57) **ABSTRACT**


(51) **Int. Cl.**
A61M 1/12 (2006.01)
A61M 1/10 (2006.01)
(Continued)

A method for assisting blood circulation in a patient includes drawing a flow of blood from a patient's heart into a blood flow channel formed by a housing. The flow of blood is passed through a motor stator to a rotor disposed within the blood flow channel. The motor stator is arranged circumferentially around the blood flow channel. The rotor has permanent magnetic poles for magnetic levitation and rotation of the rotor. The motor stator is controlled to act as a radial bearing for magnetic levitation of the rotor and to rotate the rotor within the blood flow channel. The rotor is levitated within the blood flow channel in the direction of the rotor axis of rotation via passive magnetic interaction between the rotor and the motor stator. The flow of blood is output from the blood flow channel to the patient.

(52) **U.S. Cl.**
CPC **A61M 1/1036** (2014.02); **A61M 1/101** (2013.01); **A61M 1/1015** (2014.02);
(Continued)

(58) **Field of Classification Search**
CPC **A61M 1/122**
See application file for complete search history.

16 Claims, 6 Drawing Sheets



Related U.S. Application Data

- continuation of application No. 13/212,813, filed on Aug. 18, 2011, now Pat. No. 9,091,271.
- (60) Provisional application No. 61/375,504, filed on Aug. 20, 2010.
- (51) **Int. Cl.**
F04D 13/06 (2006.01)
F04D 29/048 (2006.01)
- (52) **U.S. Cl.**
 CPC **A61M 1/1029** (2014.02); **A61M 1/1031** (2014.02); **A61M 1/1086** (2013.01); **A61M 1/122** (2014.02); **A61M 1/127** (2013.01); **F04D 13/064** (2013.01); **F04D 13/066** (2013.01); **F04D 13/0633** (2013.01); **F04D 13/0646** (2013.01); **F04D 29/048** (2013.01); **A61M 1/1008** (2014.02); **A61M 1/1012** (2014.02); **A61M 2205/3365** (2013.01); **Y10T 29/49009** (2015.01)

(56) References Cited

U.S. PATENT DOCUMENTS

1,026,101 A	5/1912	Marsh	5,220,232 A	6/1993	Rigney, II et al.
2,128,988 A	9/1938	Russell	5,341,059 A	8/1994	Fukuyama et al.
2,747,512 A	5/1956	Paul	5,360,317 A	11/1994	Clausen et al.
2,864,552 A	12/1958	Norman	5,385,581 A	1/1995	Bramm et al.
3,005,117 A	10/1961	Buchhold	5,470,208 A	11/1995	Kletschka
3,066,849 A	12/1962	Beams	5,678,306 A	10/1997	Bozeman, Jr. et al.
3,122,101 A	2/1964	Baker et al.	5,708,346 A	1/1998	Schob
3,225,608 A	12/1965	Ivan	5,725,357 A	3/1998	Nakazeki et al.
3,401,640 A	9/1968	John et al.	5,798,454 A	8/1998	Nakazeki et al.
3,499,274 A	3/1970	Ferguson	5,808,437 A	9/1998	Schob
3,575,536 A	4/1971	Jacobs et al.	5,917,297 A	6/1999	Gerster et al.
3,597,022 A	8/1971	Waldron	5,928,131 A	7/1999	Prem
3,608,088 A	9/1971	Dorman et al.	5,947,703 A	9/1999	Nojiri et al.
3,611,815 A	10/1971	Fischell	6,053,705 A	4/2000	Schob et al.
3,647,324 A	3/1972	Rafferty et al.	6,100,618 A	8/2000	Schoeb et al.
3,650,581 A	3/1972	Boden et al.	6,130,494 A	10/2000	Schob
3,938,913 A	2/1976	Isenberg et al.	6,146,325 A	11/2000	Lewis et al.
3,957,389 A	5/1976	Rafferty et al.	6,222,290 B1	4/2001	Schob et al.
4,082,376 A	4/1978	Wehde et al.	6,227,797 B1	5/2001	Watterson et al.
4,135,253 A	1/1979	Reich et al.	6,234,772 B1	5/2001	Wampler et al.
4,213,207 A	7/1980	Wilson	6,244,835 B1 *	6/2001	Antaki F04D 3/005
4,340,260 A	7/1982	Forster et al.	6,249,067 B1	6/2001	Schob et al.
4,382,199 A	5/1983	Isaacson	6,264,635 B1	7/2001	Wampler et al.
4,398,773 A	8/1983	Boden et al.	6,278,251 B1	8/2001	Schöb
4,405,286 A	9/1983	Studer	6,293,901 B1	9/2001	Prem
4,408,966 A	10/1983	Maruyama	6,302,661 B1	10/2001	Khanwilkar et al.
4,475,866 A	10/1984	Kambe et al.	6,351,048 B1	2/2002	Schob et al.
4,507,048 A	3/1985	Belenger et al.	6,355,998 B1	3/2002	Schob et al.
4,589,822 A	5/1986	Clausen et al.	6,394,769 B1	5/2002	Bearnsen et al.
4,642,036 A	2/1987	Young	6,447,266 B2	9/2002	Antaki et al.
4,688,998 A	8/1987	Olsen et al.	6,468,041 B2	10/2002	Ozaki
4,704,121 A	11/1987	Moise	6,559,567 B2	5/2003	Schob
4,763,032 A	8/1988	Bramm et al.	6,575,717 B2	6/2003	Ozaki et al.
4,779,614 A	10/1988	Moise	6,589,030 B2	7/2003	Ozaki
4,844,707 A	7/1989	Kletschka	6,605,032 B2	8/2003	Benkowski et al.
4,876,492 A	10/1989	Lester et al.	6,623,475 B1	9/2003	Siess
4,878,831 A	11/1989	Ewing	6,626,644 B2	9/2003	Ozaki
4,929,158 A	5/1990	Girault	6,634,224 B1	10/2003	Schob et al.
4,944,748 A	7/1990	Bramm et al.	6,640,617 B2	11/2003	Schob et al.
4,957,504 A	9/1990	Chardack	6,641,378 B2	11/2003	Davis et al.
5,055,005 A	10/1991	Kletschka	6,688,861 B2	2/2004	Wampler
5,078,741 A	1/1992	Bramm et al.	6,707,200 B2	3/2004	Carroll et al.
5,106,273 A	4/1992	Lemarquand et al.	6,711,943 B1	3/2004	Schob
5,112,200 A	5/1992	Isaacson et al.	6,817,836 B2	11/2004	Nose et al.
5,112,202 A	5/1992	Oshima et al.	6,949,066 B2	9/2005	Bearnsen et al.
5,126,612 A	6/1992	Girault	7,070,398 B2	7/2006	Olsen et al.
5,127,792 A	7/1992	Katsuta et al.	7,112,903 B1	9/2006	Schob
5,159,219 A	10/1992	Chu et al.	7,138,776 B1	11/2006	Gauthier et al.
5,177,387 A	1/1993	Memichael et al.	7,150,711 B2	12/2006	Nüsser et al.
5,195,877 A	3/1993	Kletschka	D534,548 S	1/2007	Urano et al.
			7,160,242 B2	1/2007	Yanai
			7,229,258 B2	6/2007	Wood et al.
			7,229,474 B2	6/2007	Hoffmann et al.
			7,239,098 B2	7/2007	Masino
			7,284,956 B2	10/2007	Nose et al.
			7,338,521 B2	3/2008	Antaki et al.
			7,462,019 B1	12/2008	Allarie et al.
			7,497,116 B2	3/2009	Miyakoshi et al.
			7,511,443 B2	3/2009	Townsend et al.
			7,578,782 B2	8/2009	Miles et al.
			7,591,777 B2	9/2009	Larose
			7,645,225 B2	1/2010	Medvedev et al.
			7,699,588 B2	4/2010	Mendler
			7,854,631 B2	12/2010	Townsendl et al.
			7,861,582 B2	1/2011	Miyakoshi et al.
			7,887,479 B2	2/2011	Larose et al.
			7,951,062 B2	5/2011	Morello
			7,976,271 B2	7/2011	Larose et al.
			8,152,493 B2	4/2012	Larose et al.
			8,157,720 B2	4/2012	Marseille et al.
			8,303,482 B2	11/2012	Schima et al.
			8,382,830 B2	2/2013	Maher et al.
			8,506,470 B2	8/2013	Larose et al.
			8,517,699 B2	8/2013	Horvath
			8,556,795 B2	10/2013	Bolyard et al.
			8,597,350 B2	12/2013	Rudser et al.
			8,764,621 B2	7/2014	Badstibner et al.
			8,870,739 B2	10/2014	Larose et al.

(56)

References Cited**U.S. PATENT DOCUMENTS**

8,882,477	B2	11/2014	Fritz, IV et al.	
8,956,275	B2	2/2015	Bolyard et al.	
9,091,271	B2 *	7/2015	Bourque	A61M 1/101
2003/0021683	A1	1/2003	Capone et al.	
2004/0236420	A1	11/2004	Yamane et al.	
2005/0004421	A1	1/2005	Pacella et al.	
2005/0025630	A1	2/2005	Ayre et al.	
2005/0135948	A1	6/2005	Olsen et al.	
2005/0147512	A1	7/2005	Chen et al.	
2007/0100196	A1	5/2007	Larose et al.	
2009/0064755	A1	3/2009	Fleischli et al.	
2009/0234447	A1	9/2009	Larose et al.	
2010/0130809	A1	5/2010	Morello	
2010/0150749	A1	6/2010	Horvath	
2010/0152526	A1	6/2010	Pacella et al.	
2010/0241223	A1	9/2010	Lee et al.	
2010/0327687	A1	12/2010	Iannello et al.	
2011/0002794	A1	1/2011	Haefliger et al.	
2011/0031836	A1	2/2011	Nussbaumer	
2011/0054239	A1	3/2011	Sutton et al.	
2011/0071337	A1	3/2011	Thompson et al.	
2011/0144413	A1	6/2011	Foster	
2011/0187217	A1	8/2011	Nussbaumer	
2011/0237863	A1	9/2011	Ricci et al.	
2011/0245582	A1	10/2011	Zafirelis et al.	
2011/0313237	A1	12/2011	Miyakoshi et al.	
2012/0035411	A1	2/2012	Larose et al.	
2012/0046514	A1	2/2012	Bourque	
2012/0059212	A1	3/2012	Larose et al.	
2012/0134832	A1	5/2012	Wu	
2012/0226097	A1	9/2012	Smith et al.	
2012/0245680	A1 *	9/2012	Masuzawa	A61M 1/1086 623/3.11
2012/0245681	A1	9/2012	Casas et al.	
2012/0253103	A1	10/2012	Robert	
2012/0310036	A1	12/2012	Peters et al.	
2013/0331934	A1	12/2013	Kabir et al.	
2014/0100413	A1	4/2014	Casas et al.	

2014/0194985	A1	7/2014	Vadala, Jr.
2014/0275723	A1	9/2014	Fritz, IV et al.
2014/0303426	A1	10/2014	Kerkhoffs et al.
2014/0357937	A1	12/2014	Reyes et al.
2015/0051438	A1	2/2015	Taskin

FOREIGN PATENT DOCUMENTS



EP	60569	12/1990
EP	378251	6/1994
EP	2357374	8/2011
GB	1491710	11/1977
JP	01257792	10/1989
JP	02016390	1/1990
JP	03088996	4/1991
JP	04148095	5/1992
JP	2000510929	8/2000
JP	2002512333	4/2002
JP	2003093500	4/2003
JP	D1373017	10/2009
JP	2011530315	12/2011
TW	D136032	7/2010
WO	9953974	10/1999
WO	2005032620	4/2005
WO	2006137496	12/2006
WO	2010015836	2/2010
WO	2010023815	3/2010
WO	2010036815	4/2010
WO	2012028181	3/2012

OTHER PUBLICATIONS

Barletta et al., Design of a bearing less blood pump, Proc.3rd Int. Symp. on Magnetic Suspension Technology, Dec. 13-15, 1995, pp. 265-274.

Izraelev et al., A Passively-Suspended Tesla Pump Left Ventricular Assist Device, NIH Public Access, vol. 55, No. 6, 2009, pp. 556-561.

* cited by examiner






FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8






FIG. 9



1

IMPLANTABLE BLOOD PUMP**CROSS-REFERENCES TO RELATED APPLICATIONS**

This application is a divisional of U.S. application Ser. No. 14/735,990, filed Jun. 10, 2015, now U.S. Pat. No. 9,675,741, issued Jun. 13, 2017, and titled "Implantable Blood Pump," which application is a continuation application of U.S. application Ser. No. 13/212,813, filed Aug. 18, 2011, now U.S. Pat. No. 9,091,271, issued Jul. 28, 2015, and titled "Implantable Blood Pump," which application claims the benefit of U.S. Provisional Application Ser. No. 61/375,504, filed Aug. 20, 2010, and titled "Implantable Blood Pump," the entire contents of which are incorporated herein by reference in their entirety.

FIELD

This description relates to implantable blood pumps.

BACKGROUND

Ventricular assist devices, known as VADs, are implantable blood pumps used for both short-term and long-term applications where a patient's heart is incapable of providing adequate circulation. For example, a patient suffering from heart failure may use a VAD while awaiting a heart transplant. In another example, a patient may use a VAD while recovering from heart surgery. Thus, a VAD can supplement a weak heart or can effectively replace the natural heart's function. VADs can be implanted in the patient's body and powered by an electrical power source outside the patient's body.

BRIEF SUMMARY

In one general aspect, an implantable blood pump includes a housing and a blood flow conduit. Within the housing, the blood pump includes a stator located about the blood flow conduit and a magnetically-levitated rotor.

In another general aspect, an implantable blood pump includes a housing defining an inlet opening and an outlet opening. Within the housing, a dividing wall defines a blood flow conduit extending between the inlet opening and the outlet opening of the housing. The blood pump has a rotary motor that includes a stator and a rotor. The stator is disposed within the housing circumferentially about the dividing wall such that the inner blood flow conduit extends through the stator.

In another general aspect, an implantable blood pump includes a puck-shaped housing having a first face defining an inlet opening, a peripheral sidewall, and a second face opposing the first face. The blood pump has an internal dividing wall defining an inner blood flow conduit extending between the inlet opening and an outlet opening of the housing. The puck-shaped housing has a thickness from the first face to the second face that is less than a width of the housing between opposing portions of the peripheral sidewall. The blood pump also has a motor having a stator and a rotor. The stator is disposed in the housing circumferentially about the blood flow conduit and includes magnetic levitation components operable to control an axial position and a radial position of the rotor. The rotor is disposed in the inner blood flow conduit and includes an impeller operable

2

to pump blood from the inlet opening to the outlet opening through at least a portion of the magnetic levitation components of the stator.

Implementations of the above aspects may include one or more of the following features. For example, the stator is disposed circumferentially about at least a part of the rotor and is positioned relative to the rotor such that in use blood flows within the blood flow conduit through the stator before reaching the rotor. The rotor has permanent magnetic poles for magnetic levitation of the rotor. A passive magnetic control system is configured to control an axial position of the rotor relative to the stator, and an active electromagnetic control system is configured to radially center the rotor within the inner blood flow conduit. An electromagnetic control system controls at least one of a radial position and an axial position of the rotor relative to the stator, and the electromagnetic control system has control electronics located within the housing about the dividing wall.

The control electronics are located between the inlet opening and the stator. The control electronics can be configured to control the active magnetic control system. The rotor has only one magnetic moment. The stator includes a first coil for driving the rotor and a second coil for controlling a radial position of the rotor, and the first coil and the second coil are wound around a first pole piece of the stator. The housing has a first face that defines the inlet opening, a second face opposing the first face, and a peripheral wall extending from the first face to the second face. The housing includes a rounded transition from the second face to the peripheral wall. The housing defines a volute located such that in use blood flows within the blood flow conduit through the stator before reaching the volute. The volute can be located between the stator and the second face. The housing can also include a cap that includes the second face, defines at least part of the volute, and defines at least part of the outlet. The cap is engaged with the peripheral wall of the housing. The housing also includes an inlet cannula extending from the first face and in fluid communication with the inlet opening. The inlet cannula can be inserted into the patient's heart. The outlet opening is defined in the second face and/or the peripheral wall. A thickness of the housing between the first face and the second face is less than a width of the housing.

In another general aspect, a method includes inserting a puck-shaped blood pump housing into a patient's body. The blood pump is inserted such that an opening defined in a first flat face of the housing that is proximate to a stator of the blood pump faces the patient's heart. Additionally, the blood pump is inserted such that a second rounded face of the housing that is proximate to an impeller of the blood pump faces away from the patient's heart. The first face is disposed against a portion of the patient's heart such that the second face of the housing faces away from the heart of the patient. In some implementations, the method includes inserting an inlet cannula of the housing into the patient's heart.

In another general aspect, making a blood pump includes assembling a motor stator and control electronics in a puck-shaped housing circumferentially about an internal dividing wall. The internal dividing wall defines an inner blood flow conduit that extends from an inlet opening to an outlet opening of the housing. The stator is assembled in the housing such that the inner blood flow conduit extends through the motor stator. Disposed within the inner blood flow conduit is a magnetically-levitated rotor. The rotor is surrounded by the stator such that impeller blades carried by the rotor are downstream of the stator from the inlet opening.

In use, the impeller pumps blood from the inlet opening to the outlet opening through the stator.

Implementations may include one or more of the following features. For example, the rotor has only one magnetic moment. The stator includes at least one first coil for driving the rotor and at least one second coil for controlling a radial position of the rotor, the at least one first coil and the at least one second coil being wound around a first pole piece of the stator. The housing includes a first face that defines the inlet opening, and further comprising engaging an end cap with a peripheral wall of the housing, the end cap including a second face, defining at least part of a volute, and defining at least part of the outlet opening. The housing includes a rounded transition from the second face to the peripheral wall. The housing further includes an inlet cannula extending from the first face and in fluid communication with the inlet opening. A thickness of the housing between the first face and the second face is less than a width of the housing.

In another general aspect, a method of pumping blood includes magnetically rotating a centrifugal pump impeller of a blood pump device to draw blood from a patient's heart through an inlet opening of a housing of the blood pump device into an inner blood flow conduit within a stator in the housing, through the inner blood flow conduit, and through an outlet opening of the housing. The method includes selectively controlling a radial position of the impeller within the inner blood flow conduit.

The details of one or more implementations are set forth in the accompanying drawings and the description below. Other features will be apparent from the description and drawings, and from the claims.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is an illustration of a blood pump in a use position implanted in a patient's body.

FIG. 2 is a cross-sectional view of the blood pump of FIG. 1.

FIG. 3 is a partial cut-away perspective view of a stator of a blood pump.

FIG. 4 is a bottom perspective view of a blood pump.

FIG. 5 is a top perspective view of the blood pump of FIG. 4.

FIG. 6 is a front view of the blood pump of FIG. 4.

FIG. 7 is a back view of the blood pump of FIG. 4.

FIG. 8 is a right side view of the blood pump of FIG. 4.

FIG. 9 is a left side view of the blood pump of FIG. 4.

FIG. 10 is a bottom view of the blood pump of FIG. 4.

FIG. 11 is a top view of the blood pump of FIG. 4.

DETAILED DESCRIPTION

With reference to FIGS. 1 and 4-11, a left ventricular assist blood pump 100 having a puck-shaped housing 110 is implanted in a patient's body with a first face 111 of the housing 110 positioned against the patient's heart H and a second face 113 of the housing 110 facing away from the heart H. The first face 111 of the housing 110 includes an inlet cannula 112 extending into the left ventricle LV of the heart H. The second face 113 of the housing 110 has a chamfered edge 114 to avoid irritating other tissue that may come into contact with the blood pump 100, such as the patient's diaphragm. To construct the illustrated shape of the puck-shaped housing 110 in a compact form, a stator 120 and electronics 130 of the pump 100 are positioned on the inflow side of the housing toward first face 111, and a rotor 140 of the pump 100 is positioned along the second face 113.

This positioning of the stator 120, electronics 130, and rotor 140 permits the edge 114 to be chamfered along the contour of the rotor 140, as illustrated in at least FIGS. 2, 4, and 6-9, for example.

Referring to FIG. 2, the blood pump 100 includes a dividing wall 115 within the housing 110 defining a blood flow conduit 103. The blood flow conduit 103 extends from an inlet opening 101 of the inlet cannula 112 through the stator 120 to an outlet opening 105 defined by the housing 110. The rotor 140 is positioned within the blood flow conduit 103. The stator 120 is disposed circumferentially about a first portion 140a of the rotor 140, for example about a permanent magnet 141. The stator 120 is also positioned relative to the rotor 140 such that, in use, blood flows within the blood flow conduit 103 through the stator 120 before reaching the rotor 140. The permanent magnet 141 has a permanent magnetic north pole N and a permanent magnetic south pole S for combined active and passive magnetic levitation of the rotor 140 and for rotation of the rotor 140. The rotor 140 also has a second portion 140b that includes impeller blades 143. The impeller blades 143 are located within a volute 107 of the blood flow conduit such that the impeller blades 143 are located proximate to the second face 113 of the housing.

The puck-shaped housing 110 further includes a peripheral wall 116 that extends between the first face 111 and a removable cap 118. As illustrated, the peripheral wall 116 is formed as a hollow circular cylinder having a width W between opposing portions of the peripheral wall 116. The housing 110 also has a thickness T between the first face 111 and the second face 113 that is less than the width W. The thickness T is from about 0.5 inches to about 1.5 inches, and the width W is from about 1 inch to about 4 inches. For example, the width W can be approximately 2 inches, and the thickness T can be approximately 1 inch.

The peripheral wall 116 encloses an internal compartment 117 that surrounds the dividing wall 115 and the blood flow conduit 103, with the stator 120 and the electronics 130 disposed in the internal compartment 117 about the dividing wall 115. The removable cap 118 includes the second face 113, the chamfered edge 114, and defines the outlet opening 105. The cap 118 can be threadably engaged with the peripheral wall 116 to seal the cap 118 in engagement with the peripheral wall 116. The cap 118 includes an inner surface 118a of the cap 118 that defines the volute 107 that is in fluid communication with the outlet opening 105.

Within the internal compartment 117, the electronics 130 are positioned adjacent to the first face 111 and the stator 120 is positioned adjacent to the electronics 130 on an opposite side of the electronics 130 from the first face 111. The electronics 130 include circuit boards 131 and various components 133 carried on the circuit boards 131 to control the operation of the pump 100 by controlling the electrical supply to the stator 120. The housing 110 is configured to receive the circuit boards 131 within the internal compartment 117 generally parallel to the first face 111 for efficient use of the space within the internal compartment 117. The circuit boards also extend radially-inward towards the dividing wall 115 and radially-outward towards the peripheral wall 116. For example, the internal compartment 117 is generally sized no larger than necessary to accommodate the circuit boards 131, and space for heat dissipation, material expansion, potting materials, and/or other elements used in installing the circuit boards 131. Thus, the external shape of the housing 110 proximate the first face 111 generally fits the

shape of the circuit boards **131** closely to provide external dimensions that are not much greater than the dimensions of the circuit boards **131**.

With continued reference to FIG. 2 and with reference to FIG. 3, the stator **120** includes a back iron **121** and pole pieces **123a-123f** arranged at intervals around the dividing wall **115**. The back iron **121** extends around the dividing wall **115** and is formed as a generally flat disc of a ferromagnetic material, such as steel, in order to conduct magnetic flux. The back iron **121** is arranged beside the control electronics **130** and provides a base for the pole pieces **123a-123f**.

Each of the pole piece **123a-123f** is L-shaped and has a drive coil **125** for generating an electromagnetic field to rotate the rotor **140**. For example, the pole piece **123a** has a first leg **124a** that contacts the back iron **121** and extends from the back iron **121** towards the second face **113**. The pole piece **123a** also has a second leg **124b** that extends from the first leg **124a** towards the dividing wall **115** proximate the location of the permanent magnet **141** of the rotor **140**. Each of the pole pieces **123a-123f** also has a levitation coil **127** for generating an electromagnetic field to control the radial position of the rotor **140**.

Each of the drive coils **125** and the levitation coils **127** includes multiple windings of a conductor around the pole pieces **123a-123f**. Particularly, each of the drive coils **125** is wound around two adjacent ones of the pole pieces **123**, such as pole pieces **123d** and **123e**, and each levitation coil **127** is wound around a single pole piece. The drive coils **125** and the levitation coils **127** are wound around the first legs of the pole pieces **123**, and magnetic flux generated by passing electrical current through the coils **125** and **127** during use is conducted through the first legs and the second legs of the pole pieces **123** and the back iron **121**. The drive coils **125** and the levitation coils **127** of the stator **120** are arranged in opposing pairs and are controlled to drive the rotor and to radially levitate the rotor **140** by generating electromagnetic fields that interact with the permanent magnetic poles S and N of the permanent magnet **141**. Because the stator **120** includes both the drive coils **125** and the levitation coils **127**, only a single stator is needed to levitate the rotor **140** using only passive and active magnetic forces. The permanent magnet **141** in this configuration has only one magnetic moment and is formed from a monolithic permanent magnetic body **141**. For example, the stator **120** can be controlled as discussed in U.S. Pat. No. 6,351,048, the entire contents of which are incorporated herein by reference. The control electronics **130** and the stator **120** receive electrical power from a remote power supply via a cable **119** (FIG. 1).

The rotor **140** is arranged within the housing **110** such that its permanent magnet **141** is located upstream of impeller blades in a location closer to the inlet opening **101**. The permanent magnet **141** is received within the blood flow conduit **103** proximate the second legs **124b** of the pole pieces **123** to provide the passive axial centering force through interaction of the permanent magnet **141** and ferromagnetic material of the pole pieces **123**. The permanent magnet **141** of the rotor **140** and the dividing wall **115** form a gap **108** between the permanent magnet **141** and the dividing wall **115** when the rotor **140** is centered within the dividing wall **115**. The gap **108** may be from about 0.2 millimeters to about 2 millimeters. For example, the gap **108** is approximately 1 millimeter. The north permanent magnetic pole N and the south permanent magnetic pole S of the permanent magnet **141** provide a permanent magnetic attractive force between the rotor **140** and the stator **120** that acts

as a passive axial centering force that tends to maintain the rotor **140** generally centered within the stator **120** and tends to resist the rotor **140** from moving towards the first face **111** or towards the second face **113**. When the gap **108** is smaller, the magnetic attractive force between the permanent magnet **141** and the stator **120** is greater, and the gap **108** is sized to allow the permanent magnet **141** to provide the passive magnetic axial centering force having a magnitude that is adequate to limit the rotor **140** from contacting the dividing wall **115** or the inner surface **118a** of the cap **118**. The rotor **140** also includes a shroud **145** that covers the ends of the impeller blades **143** facing the second face **113** that assists in directing blood flow into the volute **107**. The shroud **145** and the inner surface **118a** of the cap **118** form a gap **109** between the shroud **145** and the inner surface **118a** when the rotor **140** is levitated by the stator **120**. The gap **109** is from about 0.2 millimeters to about 2 millimeters. For example, the gap **109** is approximately 1 millimeter.

As blood flows through the blood flow conduit **103**, blood flows through a central aperture **141** formed through the permanent magnet **141**. Blood also flows through the gap **108** between the rotor **140** and the dividing wall **115** and through the gap **109** between the shroud **145** and the inner surface **108a** of the cap **118**. The gaps **108** and **109** are large enough to allow adequate blood flow to limit clot formation that may occur if the blood is allowed to become stagnant. The gaps **108** and **109** are also large enough to limit pressure forces on the blood cells such that the blood is not damaged when flowing through the pump **100**. As a result of the size of the gaps **108** and **109** limiting pressure forces on the blood cells, the gaps **108** and **109** are too large to provide a meaningful hydrodynamic suspension effect. That is to say, the blood does not act as a bearing within the gaps **108** and **109**, and the rotor is only magnetically-levitated.

Because the rotor **140** is radially suspended by active control of the levitation coils **127** as discussed above, and because the rotor **140** is axially suspended by passive interaction of the permanent magnet **141** and the stator **120**, no rotor levitation components are needed proximate the second face **113**. The incorporation of all the components for rotor levitation in the stator **120** (i.e., the levitation coils **127** and the pole pieces **123**) allows the cap **118** to be contoured to the shape of the impeller blades **143** and the volute **107**. Additionally, incorporation of all the rotor levitation components in the stator **120** eliminates the need for electrical connectors extending from the compartment **117** to the cap **118**, which allows the cap to be easily installed and/or removed and eliminates potential sources of pump failure.

In use, the drive coils **125** of the stator **120** generates electromagnetic fields through the pole pieces **123** that selectively attract and repel the magnetic north pole N and the magnetic south pole S of the rotor **140** to cause the rotor **140** to rotate within stator **120**. As the rotor **140** rotates, the impeller blades **143** force blood into the volute **107** such that blood is forced out of the outlet opening **105**. Additionally, the rotor draws blood into pump **100** through the inlet opening **101**. As blood is drawn into the blood pump by rotation of the impeller blades **143** of the rotor **140**, the blood flows through the inlet opening **101** and flows through the control electronics **130** and the stator **120** toward the rotor **140**. Blood flows through the aperture **141a** of the permanent magnet **141** and between the impeller blades **143**, the shroud **145**, and the permanent magnet **141**, and into the volute **107**. Blood also flows around the rotor **140**, through the gap **108** and through the gap **109** between the shroud **145** and the inner surface **118a** of the cap **118**. The blood exits the volute **107** through the outlet opening **105**.

7

A number of implementations have been described. Nevertheless, it will be understood that various modifications may be made without departing from the spirit and scope of the claimed invention. For example, the cap 118 can be engaged with the peripheral wall 116 using a different attachment mechanism or technique, including snap-fit engagement, adhesives, or welding. Additionally, while the cap 118 has been described as defining the outlet opening 105 and the chamfered edge 114, the outlet opening 105 and/or the chamfered edge 114 can be defined by the peripheral wall 116 or by both the peripheral wall 116 and the cap 118. Similarly, the dividing wall 115 can be formed as part of the cap 118.

Additionally, the rotor 140 can include two or more permanent magnets. The number and configuration of the pole pieces 123 can also be varied. The operation of the control electronics 130 is selected to account for the number and position of pole pieces of the stator and permanent magnets of the rotor. Also, the cap 118 can be engaged with the peripheral wall using other techniques, such as adhesives, welding, snap-fit, shrink-fit, or other technique or structure. Similarly, the first face III may be formed from a separate piece of material than the peripheral wall 116 and the first face III, including the inlet cannula 112, can be attached to the peripheral wall 116, such as by welding, after the control electronics 130 and the stator 120 have been mounted in the internal compartment 117. The shroud 145 may be omitted and optionally replaced by other flow control devices to achieve a desired pump efficiency. As another option, the control electronics 130 can be located external to the pump 100, such as in a separate housing implanted in the patient's abdomen, or external to the patient's body.

In some implementations, the dimensions of the housing 110 can be larger or smaller than those described above. Similarly, the ratio of the width W of the housing 110 to the thickness T of the housing can be different than the ratio described above. For example, the width W can be from about 1.1 to about 5 times greater than the thickness T. Additionally, the permanent magnet 141 of the rotor 140 can include two or more pairs of north and south magnetic poles. While the peripheral wall 116 and the dividing wall 115 are illustrated as cylinders having circular cross-sectional shapes, one or both can alternatively be formed having other cross-sectional shapes, such as oval, or an irregular shape. Similarly, the peripheral wall 116 can be tapered such that the housing does not have a constant width W from the first face III to the second face III.

As mentioned above, in some implementations, the blood pump 100 can be used to assist a patient's heart during a transition period, such as during a recovery from illness and/or surgery or other treatment. In other implementations, the blood pump 100 can be used to partially or completely replace the function of the patient's heart on a generally permanent basis, such as where the patient's aortic valve is surgically sealed.

Accordingly, other embodiments are within the scope of the following claims.

What is claimed is:

1. A method for assisting blood circulation in a patient, the method comprising:

drawing a flow of blood from a patient's heart into a blood flow channel formed by a housing;

passing the flow of blood through a motor stator to a rotor disposed within the blood flow channel, the motor stator being arranged circumferentially around the

8

blood flow channel, the rotor having permanent magnetic poles for magnetic levitation and rotation of the rotor;

passing a first portion of the flow of blood through a central aperture formed through the rotor;

passing a second portion of the flow of blood through a gap formed between the rotor and the housing;

controlling delivery of current to the motor stator to control a radial position of the rotor within the blood flow channel and to control rotation of the rotor within the blood flow channel, the rotor being rotated around a rotor axis of rotation;

levitating the rotor within the blood flow channel in the direction of the rotor axis of rotation via only a passive magnetic interaction between the rotor and the motor stator; and

outputting the flow of blood from the blood flow channel to the patient.

2. The method of claim 1, wherein the motor stator axially overlaps the permanent magnetic poles of the rotor with respect to the rotor axis of rotation.

3. The method of claim 1, wherein the motor stator comprises a back iron and a plurality of pole pieces supported by the back iron, the back iron being configured to conduct magnetic flux and having an aperture through which the blood flow channel passes.

4. The method of claim 3, further comprising supporting control electronics within the housing and between the back iron and the patient's heart, the control electronics being configured to control the delivery of current to the motor stator for controlling the rotation and radial levitation of the rotor within the blood flow channel.

5. The method of claim 1, wherein the rotor and housing are configured and the delivery of current to the motor stator is controlled such that the gap between the rotor and the housing is between about 0.2 mm to about 2 mm.

6. The method of claim 1, comprising impelling the first portion of the flow of blood via impeller blades of the rotor to force the flow of blood from the blood flow channel to the patient.

7. The method of claim 6, wherein:

the first portion of the flow of blood is impelled substantially centrifugally via the rotor; and

the flow of blood is output from the blood flow channel in a direction transverse to the rotor axis of rotation.

8. The method of claim 1, wherein the rotor is levitated within the blood flow channel in the direction of the rotor axis of rotation such that the rotor is separated from the housing in the direction of the rotor axis of rotation via axial gaps between about 0.2 mm to about 2 mm.

9. A method for assisting blood circulation in a patient, the method comprising:

drawing a flow of blood from a patient's heart into a blood flow channel formed by a housing;

passing the flow of blood through a motor stator to a rotor disposed within the blood flow channel, the motor stator being arranged circumferentially around the blood flow channel, the rotor having permanent magnetic poles for magnetic levitation and rotation of the rotor;

passing a first portion of the flow of blood through a central aperture formed through the rotor;

passing a second portion of the flow of blood through a gap formed between the rotor and the housing;

controlling the motor stator to act as a radial bearing for magnetic levitation of the rotor and to rotate the rotor within the blood flow channel,

9

levitating the rotor within the blood flow channel in the direction of the rotor axis of rotation via only a passive magnetic interaction between the rotor and the motor stator; and

outputting the flow of blood from the blood flow channel 5 to the patient.

10. The method of claim 9, wherein the motor stator axially overlaps the permanent magnetic poles of the rotor with respect to the rotor axis of rotation.

11. The method of claim 9, wherein the motor stator 10 comprises a back iron and a plurality of pole pieces supported by the back iron, the back iron being configured to conduct magnetic flux and having an aperture through which the blood flow channel passes.

12. The method of claim 11, further comprising support- 15 ing control electronics within the housing and between the back iron and the patient's heart, the control electronics being configured to control the delivery of current to the motor stator for controlling the rotation and radial levitation of the rotor within the blood flow channel.

10

13. The method of claim 9, wherein the rotor and housing are configured and the delivery of current to the motor stator is controlled such that the gap between the rotor and the housing is between about 0.2 mm to about 2 mm.

14. The method of claim 9, comprising impelling the first portion of the flow of blood via impeller blades of the rotor to force the flow of blood from the blood flow channel to the patient.

15. The method of claim 14, wherein:

the first portion of the flow of blood is impelled substantially centrifugally via the rotor; and
the flow of blood is output from the blood flow channel in a direction transverse to the rotor axis of rotation.

16. The method of claim 9, wherein the rotor is levitated 15 within the blood flow channel in the direction of the rotor axis of rotation such that the rotor is separated from the housing in the direction of the rotor axis of rotation via axial gaps between about 0.2 mm to about 2 mm.

* * * * *