

US 8,374,575 B2

Page 2

U.S. PATENT DOCUMENTS

5,767,788 A 6/1998 Ness
5,778,315 A 7/1998 Proietti
5,796,634 A 8/1998 Craport et al.
5,805,999 A 9/1998 Inoue
5,815,538 A 9/1998 Grell et al.
5,832,381 A 11/1998 Kauppi
5,847,976 A 12/1998 Lescourret
5,875,398 A 2/1999 Snapp
5,890,062 A 3/1999 Courtney et al.
5,920,820 A 7/1999 Qureshi et al.
5,929,752 A 7/1999 Janky et al.
5,950,125 A 9/1999 Buhrmann et al.
5,961,569 A 10/1999 Craport et al.
5,961,572 A 10/1999 Craport et al.
5,978,747 A 11/1999 Craport et al.
6,023,241 A 2/2000 Clapper
6,028,537 A 2/2000 Suman et al.
6,032,042 A 2/2000 Kauppi
6,035,189 A 3/2000 All-Vehmas
6,035,198 A 3/2000 Wiehe
6,038,446 A 3/2000 Courtney et al.
6,047,051 A 4/2000 Ginzboorg
6,049,711 A 4/2000 Ben-Yehzekel
6,061,561 A 5/2000 Alanara et al.
6,078,578 A 6/2000 Matsumoto
6,091,959 A 7/2000 Souissi et al.
6,138,003 A 10/2000 Kingdon et al.
6,144,336 A 11/2000 Preston et al.
6,157,841 A 12/2000 Bolduc et al.
6,166,626 A 12/2000 Janky et al.
6,173,182 B1 1/2001 Cha
6,201,803 B1 3/2001 Munday et al.
6,208,866 B1 3/2001 Rouhollahzadeh et al.
6,215,863 B1 4/2001 Bennett et al.
6,236,359 B1 5/2001 Watters et al.
6,236,858 B1 5/2001 Griffith
6,240,069 B1 5/2001 Alperovich
6,246,376 B1 6/2001 Bork et al.
6,246,861 B1 6/2001 Messier et al.
6,252,543 B1 6/2001 Camp
6,256,498 B1 7/2001 Ludwig
6,259,923 B1 7/2001 Lim et al.
6,275,771 B1 8/2001 Berstis et al.
6,311,060 B1 10/2001 Evans et al.
6,314,365 B1 11/2001 Smith
6,317,718 B1 11/2001 Fano
6,321,092 B1 11/2001 Fitch et al.
6,324,404 B1 11/2001 Dennison et al.
6,330,452 B1 12/2001 Fattouche et al.
6,360,101 B1 3/2002 Irvin
6,360,102 B1* 3/2002 Havinis et al. 455/457
6,360,167 B1 3/2002 Millington et al.
6,374,306 B1 4/2002 Tognazzini
6,377,810 B1 4/2002 Geiger et al.
6,393,274 B1 5/2002 Peltonen
6,397,065 B1 5/2002 Huusko et al.
6,400,946 B1 6/2002 Vazvan
6,400,956 B1 6/2002 Richton
6,408,186 B1 6/2002 Park et al.
6,421,009 B2 7/2002 Suprunov
6,438,376 B1 8/2002 Elliott et al.
6,438,381 B1 8/2002 Alberth, Jr. et al.
6,446,118 B1 9/2002 Gottlieb
6,449,486 B1 9/2002 Rao
6,456,854 B1 9/2002 Chern
D464,033 S 10/2002 Piano Poirier
6,466,788 B1 10/2002 Carlsson
6,532,360 B1 3/2003 Shaffer
6,564,064 B1 5/2003 Ciganer et al.
6,580,914 B1 6/2003 Smith
6,580,918 B1 6/2003 Leickel
6,584,314 B1 6/2003 Haumont
6,587,691 B1 7/2003 Granstam
6,603,969 B1 8/2003 Vuoristo
6,603,977 B1 8/2003 Walsh et al.
6,611,687 B1 8/2003 Clark
6,618,593 B1 9/2003 Drutman et al.
6,618,671 B2 9/2003 Dooley et al.

6,622,020 B1 9/2003 Seki
6,628,938 B1 9/2003 Rachabathuni et al.
6,647,257 B2 11/2003 Owensby
6,662,014 B1* 12/2003 Walsh 455/456.2
6,665,389 B1 12/2003 Haste, III
6,677,894 B2 1/2004 Sheynblat
6,714,791 B2 3/2004 Friedman
6,716,101 B1* 4/2004 Meadows et al. 455/456.1
6,735,564 B1 5/2004 Puhakainen
6,778,837 B2 8/2004 Bade et al.
6,795,710 B1 9/2004 Creemer
6,798,358 B2 9/2004 Joyce et al.
6,799,094 B1 9/2004 Vaida et al.
6,806,813 B1 10/2004 Cheng et al.
6,816,735 B1 11/2004 Rayburn et al.
6,826,398 B1 11/2004 Lagerstrom et al.
6,836,667 B1 12/2004 Smith
6,870,822 B2 3/2005 Balogh
6,879,838 B2 4/2005 Rankin et al.
6,882,837 B2 4/2005 Fernandez et al.
6,882,856 B1 4/2005 Alterman
6,885,874 B2* 4/2005 Grube et al. 455/520
6,912,398 B1 6/2005 Domnitz
6,912,545 B1 6/2005 Lundy et al.
6,920,319 B2 7/2005 Knutsson et al.
6,920,328 B2 7/2005 Wollrab
6,928,279 B2 8/2005 Seligmann et al.
6,932,698 B2 8/2005 Sprogis
6,944,447 B2 9/2005 Portman et al.
6,968,179 B1 11/2005 De Vries
6,975,998 B1* 12/2005 Jones 705/8
6,999,777 B1* 2/2006 Ganesh 455/456.1
7,013,148 B1 3/2006 Ganesh
7,072,956 B2 7/2006 Parupudi
7,130,630 B1 10/2006 Enzmann
7,177,651 B1* 2/2007 Almasy 455/456.1
7,203,674 B2 4/2007 Cohen
7,215,965 B2* 5/2007 Fournier et al. 455/456.1
7,248,872 B2* 7/2007 Bassett et al. 455/433
7,269,426 B2 9/2007 Kokkonen et al.
7,269,428 B1 9/2007 Wallenius
7,272,220 B1 9/2007 Zhang
7,324,823 B1 1/2008 Rosen
7,409,429 B2 8/2008 Kaufman
7,570,958 B2 8/2009 Krasner
2001/0029184 A1 10/2001 L'Anson et al.
2002/0042277 A1* 4/2002 Smith 455/456
2002/0086683 A1 7/2002 Kohar et al.
2002/0102989 A1* 8/2002 Calvert et al. 455/456
2002/0115453 A1 8/2002 Poulin et al.
2002/0141434 A1 10/2002 Grundvig
2002/0164998 A1* 11/2002 Younis 455/456
2002/0183059 A1* 12/2002 Noreen et al. 455/427
2003/0013456 A1* 1/2003 Bates et al. 455/456
2003/0023726 A1 1/2003 Rice et al.
2003/0045301 A1 3/2003 Wollrab
2003/0119522 A1 6/2003 Barclay et al.
2004/0054428 A1 3/2004 Sheha
2004/0077359 A1* 4/2004 Bernas et al. 455/456.1
2004/0127231 A1 7/2004 Dorr
2004/0180669 A1* 9/2004 Kall 455/456.1
2008/0288355 A1 11/2008 Rosen
2009/0029717 A1 1/2009 Bates et al.

FOREIGN PATENT DOCUMENTS

WO WO 99/51051 3/1999
WO WO 00/28760 5/2000
WO WO 00/35228 6/2000
WO WO 00/38350 6/2000
WO WO 00/64075 10/2000
WO WO 00/76194 12/2000
WO WO 00/76243 12/2000
WO WO 01/01711 1/2001
WO WO 01/01718 1/2001
WO WO 01/03406 1/2001
WO WO 01/03454 1/2001
WO WO 01/03461 1/2001
WO WO 01/10718 1/2001
WO WO 01/20938 3/2001

WO	WO 01/33885	5/2001
WO	WO 01/39525	5/2001
WO	WO 01/39528	5/2001
WO	WO 01/41468	6/2001
WO	WO 01/50544	7/2001
WO	WO 01/86880	11/2001
WO	WO 01/89251	11/2001
WO	WO 02/03718	1/2002

OTHER PUBLICATIONS

ETSI TS 101 527 "Digital Cellular Telecommunications System (Phase 2+): Location Services (LCS): Mobile Station (MS): Serving Mobile Location Centre (SM-LC)," Radio Resource LCS Protocol (RRLP), GSM 04.31, version 8.1.0. 1999.

Wrolstad, Jay, "Sprint Claims First With E911-Capable Phone," newsfactor.com (as viewed at <http://www.newsfactor.com/perl/story/13952.html> on Jan. 22, 2007), Oct. 4, 2001).

Wrolstad, Jay, "Sprint Rolls Out E911 Services," newsfactor.com (as viewed at <http://www.newsfactor.com/perl/story/15506.html> on Jan. 22, 2007), Dec. 26, 2001).

"Sprint PCS First Quarterly E911 Implementation Report," Before the Federal Communications Commission, In the Matter of Revision of the Commission's Rules to Ensure Compatibility With Enhanced 911 Emergency Calling Systems, Feb. 1, 2002.

"Who is Integrated Data Communications?," presented at the FCC E911 Automatic Location Identification Round Table, Jun. 28, 1999.

"Wireless Telecommunications Bureau Seeks Comment on Request to Commence Rulemaking to Establish Fair Location Information Practices," DA 01-696, (as viewed at <http://www.fcc.gov/Bureaus/Wireless/PublicNotices/9001/da010696.html> on Jan. 22, 2007), Mar. 16, 2001.

"Go2 Systems & Integrated Data Communications to Deliver Location Services Automatically to Wireless Phones; Alliance Enables Automatic Recognition of Wireless Caller's Location," Business Wire (as viewed at http://www.findarticles.com/p/articles/mi_m0EIN/is_2000_Feb_28/ai/59621222 on Jan. 22, 2007), Feb. 28, 2000.

"Before the Federal Communications Commission: In the Matter of: E911 Automatic Location Identification Round Table," Transcript, Jun. 28, 1999.

"Pulver.com's Location Based Services Report," pulver.com (as visited at <http://pulver.com/lbareport/lastlbareport.16jan01.txt> on Jan. 22, 2007), Jan. 2001.

"Pulver.com's Location Based Services Report," pulver.com (as visited at <http://pulver.com/lbareport/lastlbareport.26feb01.txt> on Jan. 22, 2007), Feb. 2001.

"Pulver.com's Location Based Services Report," pulver.com (as visited at <http://pulver.com/lbareport/lastlbareport.26mar01.txt> on Jan. 22, 2007), Mar. 2001.

"Pulver.com's Location Based Services Report," pulver.com (as visited at <http://pulver.com/lbareport/lastlbareport.05apr01.txt> on Jan. 22, 2007), Apr. 2001.

"Pulver.com's Location Based Services Report," pulver.com (as visited at <http://pulver.com/lbareport/lastlbareport.01may01.txt> on Jan. 22, 2007), May, 2001.

"Pulver.com's Location Based Services Report," pulver.com (as visited at <http://pulver.com/lbareport/lastlbareport.10jun01.txt> on Jan. 22, 2007), Jun. 2001.

"Pulver.com's Location Based Services Report," pulver.com (as visited at <http://pulver.com/lbareport/lastlbareport.05jul01.txt> on Jan. 22, 2007), Jul. 2001.

"Pulver.com's Location Based Services Report," pulver.com (as visited at <http://pulver.com/lbareport/lastlbareport.01aug01.txt> on Jan. 22, 2007), Aug. 2001.

"Pulver.com's Location Based Services Report," pulver.com (as visited at <http://pulver.com/lbareport/lastlbareport.04sep01.txt> on Jan. 22, 2007) Sep. 2001.

"Pulver.com's Location Based Services Report," pulver.com (as visited at <http://pulver.com/lbareport/lastlbareport.02oct01.txt> on Jan. 22, 2007), Oct. 2001.

"Pulver.com's Location Based Services Report," pulver.com (as visited at <http://pulver.com/lbareport/lastlbareport.02nov01.txt> on Jan. 22, 2007), Nov. 2001.

"Pulver.com's Location Based Services Report," pulver.com (as visited at <http://pulver.com/lbareport/lastlbareport.03dec01.txt> on Jan. 22, 2007), Dec. 2001.

"Pulver.com's Location Based Services Report," pulver.com (as visited at <http://pulver.com/lbareport/lastlbareport.07jan02.txt> on Jan. 22, 2007), Jan. 2002.

"Pulver.com's Location Based Services Report," pulver.com (as visited at <http://pulver.com/lbareport/lastlbareport.04feb02.txt> on Jan. 22, 2007), Feb. 2002.

"Pulver.com's Location Based Services Report," pulver.com (as visited at <http://pulver.com/lbareport/lastlbareport.04mar02.txt> on Jan. 22, 2007), Mar. 2002.

"Spring PCS First Quarterly E911 Implementation Report," Before the Federal Communications Commission, In the Matter of Revision of the Commission's Rules To Ensure Compatibility With Enhanced 911 Emergency Calling Systems, Feb. 1, 2002.

"Who is Integrated Data Communications?," presented at the FCC E-911 Automatic Location Identification Round Table, Jun. 28, 1999.

"Wireless Telecommunications Bureau Seeks Comment On Request To Commence Rulemaking To Establish Fair Location Information Practices," DA 01-696 (as viewed at <http://www.fcc.gov/Bureaus/Wireless/PublicNotices/9001/da010696.html> on Jan. 22, 2007), Mar. 16, 2001.

"Go2 Systems & Integrated Data Communications to Deliver Location Services Automatically to Wireless Phones; Alliance Enables Automatic Recognition of Wireless Caller's Location," Business Wire (as viewed at http://www.findarticles.com/p/articles/mi_m0EIN/is_2000_Feb_28/ai/59621222 on Jan. 22, 2007), Feb. 28, 2000.

"Before the Federal Communications Commission: In the Matter of: E-911 Automatic Location Identification Round Table," Transcript, Jun. 28, 1999.

"Pulver.com's Location Based Services Report," pulver.com (as viewed at <http://pulver.com/lbareport/lastlbareport.16jan01.txt> on Jan. 22, 2007), Jan. 2001.

"Pulver.com's Location Based Services Report," pulver.com (as visited at <http://pulver.com/lbareport/lastlbareport.01may01.txt> on Jan. 22, 2007), May 2001.

"Pulver.com's Location Based Services Report," pulver.com (as visited at <http://pulver.com/lbareport/lastlbareport.04sep01.txt> on Jan. 22, 2007), Sep. 2001.

"Pulver.com's Location Based Services Report," pulver.com (as visited at <http://pulver.com/lbareport/lastlbareport.04sep01.txt> on Jan. 22, 2007), Sep. 2001.

"Pulver.com's Location Based Services Report," pulver.com (as visited at <http://pulver.com/lbareport/lastlbareport.04sep01.txt> on Jan. 22, 2007), Sep. 2001.

* cited by examiner





FIG. 1

**FIG. 2**




FIG. 3




FIG. 4




FIG. 5

500




FIG. 6

600




FIG. 7




FIG. 8

800




FIG. 9

Let Mike Gerome Locate You By

Country

State

City

Exact Location

1020

1010

FIG. 10

1000




FIG. 11

1100




FIG. 12

1200




FIG. 13

1300




FIG. 14

1400





FIG. 15

**FIG. 16**





FIG. 17

**FIG. 18**

1

SYSTEMS AND METHODS FOR LOCATING CELLULAR PHONES AND SECURITY MEASURES FOR THE SAME

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 10/400,196, filed on Mar. 25, 2003, which claims the benefit of U.S. Provisional Application No. 60/367,967, filed on Mar. 25, 2002, both of which are incorporated by reference herein in their entirety.

BACKGROUND OF THE INVENTION

This invention relates to systems and methods for determining a device's location. More particularly, this invention relates to systems and methods for remotely determining a device's location.

The Global Positioning System (GPS) has been developed in which a ground-based system can receive GPS signals from satellites and determine its location based on the time that it takes the GPS signals to reach the ground-based system. Generally, three satellite signals are needed to determine where in the world a receiver is located (i.e., position triangulation).

GPS systems have been integrated into cellular phones. However, these systems are deficient because the location of a device that is determined by these GPS signals are only minimally utilized. It is therefore desirable to provide systems and methods which better utilize the information about a device's location.

SUMMARY OF THE INVENTION

In accordance with the present invention, systems and methods are provided for locating cellular phones. More particularly, the present invention provides systems and methods for allowing a user of a cellular phone (e.g., a requesting user or a requestor) to locate the position of a different user's cellular phone (e.g., a requested user) based upon requestor-assigned access rights.

One object of the present invention is to provide a security feature which allows a user to limit and/or deny location access to a particular user. In preferred embodiments, only the users that have been granted access to the location of a user's cellular phone can actually locate that user's cellular phone. Furthermore, different types of access levels may be provided that allow a user to filter location information to a different user. In this manner, a cell phone user may give access, through his or her cell phone, to a friend so that the friend can locate him or her dependent on the level of access that is granted to that friend.

For example, suppose that Phil tells Bill that he will be shopping in Manhattan and that Bill should locate him when Bill gets to Manhattan through their cell phones. In such an example, Phil may grant Bill access the exact location of his cell phone for a specific period of time (e.g., the next two hours). As a result, when Bill tries to access Phil's location, Bill will be told exactly where in Manhattan Phil's cell phone is located. Thus, Bill does not have to contact Phil directly to see where he is and, therefore, Phil does not have to spend any time giving Bill verbal directions; Bill can simply see what store Phil is currently in and go to it.

As mentioned previously, levels in the scope of access may be controlled by a user such that, for example, only a user's

2

exact location, approximate location, city, state, or country can be accessed by a particular user.

Location alerts and monitoring features are also provided. For example, Phil may give Jen, a resident of Pittsburgh, city access so that when Phil travels into Pittsburgh, Jen will be alerted of Phil's presence. Such an alert may take the form of, for example, a display on Jen's cell phone that communicates to Jen "Phil is in Pittsburgh."

Locating a cellular phone may be accomplished in several ways. For example, satellite positioning systems such as the Global Positional System and the soon to be deployed Galileo system may be used to locate a user's cell phone.

User positions and security settings may be regularly or manually transmitted to a remote system, such a remote database so that requesting users can locate a requested user's position even if the requested user turns his/her cell phone OFF. Placing the security measures on a remote system (e.g., remote database, computer, or server) provides an information brokering scheme such that the system is still operable even when cell phones are added, removed, or modified from the system.

Additionally, the present invention may be configured to provide additional information about the location of a user. Such additional information may be, for example, a map, a location marker on a map, a map that changes as the user moves, a compass, coordinates of the located cell phone, directions to the located cell phone, where a user is in relation to another user, and information about the location the located user is currently positioned in or nearby locations such as landmarks. Such information may be provided by a remote information provider (e.g., a remote map information provider) and accessed by an information broker through a communications network.

Many other features are also employed that realizes advantageous locating functionality. As per an example, suppose that a wife wants to see if her husband has left work yet. She can locate her husband, without having to talk to him, and realize that he is driving home on a highway. Thus, a travel time option may be provided to the user. This option would compute the distance between the wife's location and husband's location by taking multiple location readings of the husband's location to see how fast the husband is traveling. Alternatively, because the husband's position will map to a highway, the system may assume that the user is driving and may provide the wife with an estimate on the husband's arrival time based on an assumed route. In this manner, the present invention may determine how much time it will take the husband to reach the wife and display this information to the wife.

As per other examples, a "see my friends" option may also be provided that brings up a map of a desired area. Dots or symbols may be present on the map to signify the location of all user's from which the requesting user has location information for. Similarly, a "find closest friend" option may be employed which finds the closest user with which the requesting user has location access to.

A cell phone location may be accessed by a variety of other devices. Alternatively, a cell phone may be used to access the location of a variety of other devices. For example, if the wife was at home, that wife may connect to the internet and access a remote database to either provide the most recent location information about the husband's cell phone to her or request a location update from the husband's cell phone. The wife's location may be already stored in such a database by associating the location to the IP address of the computer or by a manual input of the wife's location. The wife's identity may be determined by, for example, a login and password on a

3

website. Thus, the above-identified security measures are not limited to device-to-device locating rather user to user locating; the wife may only access the husband's location if the husband has granted access for the wife to do so. If, by accident, the wife's cell phone breaks, she may login on a friend's cell phone and determine the husband's location according to the device that the husband is logged into.

Security is preferably taken into account in the present invention and, therefore, location rights for a specific user may be given to a different user only by that specific user. However, a user may request location access rights from a different user. For example, a user may be provided with a request location screen on his cell phone and that user (e.g., user "X") may enter in the cell phone number of the cell phone whose location is desired. The user associated to the entered cell phone number may then receive an alert that says "user X has requested access to your location." Location access may then be given or denied on multiple levels and the requesting user notified of the decision.

The location feature of the present invention may be turned ON or OFF at any time. Users may be added, individually or in groups, to a list of users with location access rights to a specific user by that specific user. A specific user may, at any time, modify, delete, or add users allowed to access his or her location. Login and password information may be included to increase security or to create a user profile, allowing a specific user to log into any cell phone and be recognized by the present invention (and thereby be located with that cell phone or locatable device).

BRIEF DESCRIPTION OF THE DRAWINGS

The principles and advantages of the present invention can be more clearly understood from the following detailed description considered in conjunction with the following drawings, in which the same reference numerals denote the same structural elements throughout, and in which:

FIG. 1 is a network topology of a cell phone locating network in accordance with the principles of the present invention;

FIG. 2 is a flow chart of the locating feature in accordance with the principles of the present invention;

FIG. 3 is an illustration of a cell phone in accordance with the principles of the present invention;

FIG. 4 is a display screen for a locate feature in accordance with the principles of the present invention;

FIG. 5 is a display screen for a retrieving location status feature in accordance with the principles of the present invention;

FIG. 6 is a display screen for a displaying location feature in accordance with the principles of the present invention;

FIG. 7 is a display screen listing options for a locate feature in accordance with the principles of the present invention;

FIG. 8 is a display screen of a failed locate feature due to insufficient rights in accordance with the principles of the present invention;

FIG. 9 is a display screen of adding and modifying locate rights and options to a user in accordance with the principles of the present invention;

FIG. 10 is a display screen of assigning location rights to a user in accordance with the principles of the present invention;

FIG. 11 is a display screen of alert options in accordance with the principles of the present invention;

FIG. 12 is a display screen of an alert feature in accordance with the principles of the present invention;

4

FIG. 13 is a display screen of a login feature in accordance with the principles of the present invention;

FIG. 14 is a display screen of a login feature in accordance with the principles of the present invention;

FIG. 15 is a wireless device in accordance with the principles of the present invention;

FIG. 16 is an embodiment of a network topology in accordance with the principles of the present invention;

FIG. 17 is an embodiment of a locating feature in accordance with the principles of the present invention; and

FIG. 18 is an embodiment of a communications signal in accordance with the principles of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

FIG. 1 depicts a network topology of device location network 100 incorporating principles of the present invention. Network 100 includes one or more positioning satellites 110, 112, and 114 that can locate the position of one or more cell phones 120, 122, 126, and 124 (and other locatable devices) on Earth 101. Positioning satellites 110, 112, and 114 may be, for example, the Global Positioning System (GPS) or the upcoming Galileo satellite network.

Preferably, any cell phone in network 100 may locate a different cell phone, as long as access to location information is allowed, through the utilization of positioning satellites 110, 112, and 114. Persons skilled in the art will appreciate that other positioning systems and methods may be used in locating the position of a user on a cell phone of network 100.

To route information to and from a cell phone of network 100 additional facilities and communication paths may be included. For example, a main facility (not shown in FIG. 1) containing user location access rights may be included in network 100. Such a main facility may retrieve location information directly from a positioning system or a cellular phone and then route this information to a cellular phone or positioning system.

Persons skilled in the art will appreciate that if the Global Positioning System (GPS) is used as the positioning system then GPS receivers will be incorporated into cellular phones of the present invention. Persons skilled in the art will also appreciate that devices other than cellular phones may include positioning features. For example, watches, clothing, laptop computers, personal digital assistants (PDAs), may all contain location systems (e.g., GPS) and utilize the security principles of the present invention to allow different user's to access these locations.

FIG. 2 shows flow chart 200 of a simplified locating feature constructed in accordance with the principles of the present invention. Step 202 initiates when a user requests the location of another user's cell phone. Step 206 evaluates if the user initiating the location request has the rights to access the location of the desired user. If no access rights for the requesting user have been granted then step 204 will preferably inform the requesting user that he/she has not been given access to the requested location. In this manner, every user may assign rights (e.g. govern the security) to whom may or may not locate him/her. In preferred embodiments, these rights will be stored in, or functionality executed from, a remote facility and accessed and utilized by a user's cell phone or other requesting device (e.g., a watch or PDA).

If access has been given by a particular user that allows for the requesting user to locate that particular user, step 208 is initiated and the allowed location information is provided to the user in step 210. Step 208 may optionally filter the location information such that only a portion information is passed to the requesting user. The requested user may have,

5

for example, defined that the requesting user only can obtain the city, state, or country of his/her location. Persons skilled in the art will appreciate that only the location of the desired user needs to have a cell phone or a positioning system. The requesting user may use other means (e.g., the internet) to request the location of the desired user.

Persons skilled in the art will appreciate that the location of a user's cell phone may be retrieved, in step 208, from a remote database, facility, distribution center, or any other system. More particularly, a remote database may periodically request the location of a cell phone user with a positioning system and store this information. This database may also keep a record of those people allowed to access that user's location, the extent to which access is allowed, and the extent to which a user has requested a user's location. A user may update, add, manipulate, or remove access at any time by doing so at this database. Thus, a requesting user only has to contact the remote database, have his/her identity recognized, have his/her access rights for the requested user location determined, and, if the requesting user has the correct access rights, be provided with the requested user's location.

Instead of a remote database periodically obtaining location information for a user, the database can obtain a user's locations when a request is made for that user's location, providing the requesting user has access to the requested user's location. However, persons skilled in the art will recognize that a remote database is utilized in the above examples that contains the locations, in most circumstances, of a multitude of users. Thus, to increase security even more, a requesting user's cell phone may directly request a user's location from the requested user's cell phone without the need for a database. In such an example a user adds, manipulates, or removes access rights locally on his/her cell phone and does not have to worry about security issues that surround placing his location on a remote database. Furthermore, in such an embodiment a user's location does not have to be saved anywhere, a positioning system can just be "read" by a requesting user with the appropriate access rights.

However, by recording a user's location on a device, e.g., a cell phone's memory or in a remote database, novel applications may be utilized. For example, whenever a user makes a credit card purchase, a credit card authorization system can record the location of a cell phone associated to the purchasing user. In this manner, a new system and method of fraud protection is introduced. The credit card authorization system may, for example, reject a purchase if the purchaser's cell phone (or watch, clothing, PDA, or other positioning enabled device) is not in the vicinity of the purchase. Alternatively, the credit card authorization system may request a second form of identification if the purchaser's cell phone location does not correlate to the location of the purchase. Additionally, the credit card authorization system may call the purchaser's cell phone and request authorization for the credit card purchase. However, such features would preferably first involve the user/purchaser giving the credit card authorization system access to the location of his/her cell phone.

As per another application, a unique dating/matching service could be embodied. For example, a user may store a number of preferences in a matching profile. These preferences may describe what type of person he is interested in meeting. Additionally, a user may store, preferably locally (for the dating/matching feature) but alternatively at a remote location, his/her own profile that has data describing similar attributes for what he/she is looking for. For example, an entry in a user's profile may be "male" and an entry in "looking for" profile may be "female." When a user comes within a certain distance of a user (determined by comparing locations of a

6

user) that fits his/her "looking for" profile, the user may be alerted of the proximity of a matching user. Preferably, the particular user is only alerted if the "looking for" user has entered in attributes similar to the particular user's attributes and is also alerted of the particular user. The next stages of such an application could include, for example, requesting access to a form of communication. Such a form of communication could be for example, talking on the phone, instant messaging, or delivering an email address. Persons skilled in the art will therefore appreciate that many useful applications may be constructed using the principles of the present invention.

FIG. 3 depicts cell phone 300 constructed in accordance with the principles of the present invention. Cell Phone 300 preferably includes speaker 330, antenna 310, display screen 320, control keys 360, alpha-numeric keys 350, and microphone 340. Cell phone 300 also preferably may include, for example, a communications transmitter (not shown), communications receiver (not shown), memory (not shown), positioning device (not shown), and a microprocessor (not shown).

Cell phone 300 may also include locate button 380. Cell phone 300 may be configured such that if locate button 380 is pressed, a locate feature is initiated (e.g., display screen 400 of FIG. 4 is initiated). Alternatively, cell phone 300 may be configured such that if locate button 380 is pressed, a location signal is sent to a remote storage area (e.g., a remote database), thus manually updating the user's location. This latter functionality may be useful when a user does not want his/her location accessed. As in another alternative embodiment, cell phone 380 may be configured such that if locate button 380 is pressed, the locating features of cell phone 300 are toggled between ON and OFF. Person skilled in the art will appreciate that locate button 380 may be configured to produce a variety of useful functionalities.

FIG. 4 depicts display screen 400 that is displaying a locate feature constructed in accordance with the principles of the present invention. The locate feature of display screen 400 may be included, for example, in cell phone 300 of FIG. 3 and displayed to the user of cell phone 300 of FIG. 3 when that user requests the location of a different user of the present invention. The programming for the feature may, for example, be stored in the memory of the cell phone and executed by the processor at a user's request. Locate Feature 400 includes identifier list 410 of alpha-numeric identifiers for users stored in the memory on cell phone 300 (FIG. 3) or at a remote location. More particularly the user of display 410 may locate a user contained in identifier list 410 by selecting an appropriate user identifier 420.

The user identifiers (e.g., "Susan Pracht") in identifier list 410 are selectable and may be selected by control keys 360 of FIG. 3. Highlight window 410 may be used to prompt the user what identifier from list 410 is currently selected any may be controlled, for example, by the input keys of the cell phone (e.g., keys 350 and 360 of FIG. 3). Identifiers may be associated to, for example, cellular telephone number, user profiles, or any other identifier that may be associated to a locatable device or user interacting with a locatable device.

Persons skilled in the art will appreciate that display screen 400 may be provided to a user of devices other than wireless devices. For example, display screen 410 may be provided to a user of a personal computer with no positioning system. Preferably, however, the security measures in accordance with the principles of the present invention are still abided to (e.g., access has been granted to the identifier associated to the requesting user). In this manner, a user can control who can access his/her wireless device (e.g., cell phone).

Persons skilled in the art will appreciate that identifier list **410** may be configured, for example, to contain only those users in which the user of cell phone **300** (FIG. **3**) has locate access rights to or any user stored in cell phone **300**. Persons skilled in the art will also appreciate that devices other than cell phone **300** may be used to incorporate the features of the present invention. Such devices could include, for example, personal digital assistants (PDAs), laptop, GPS pagers, GPS watches, car positioning devices, or any other devices that can be located. One advantage of the present invention is that it allows a mobile device with a positioning system to locate a different mobile device with a positioning system while still retaining a high level of location security and privacy.

FIG. **5** is display screen **500** for retrieving location status feature in accordance with the principles of the present invention. The selected identifier may be incorporated into display screen **500** through location status display **510** to inform the user of the status of the location retrieval. For example, display screen **500** may display "locating user" while a request is being processed by a remote facility or database.

FIG. **6** shows display screen **600** for a display location feature constructed in accordance with the principles of the present invention. When a location is retrieved for the requested user, the location may be displayed on Display Screen **600** through primary location information **610**. Depending on what scope the requesting user has access to primary location information **610** may include, for example, the country, state, city, exact location, or any combination thereof of location information to the user. For example, if the user requesting the location of a desired user has been given unlimited location access by the desired user, primary information **610** may include the exact location of the user.

Secondary location information **620** may be included to supplement the requested users exact location so that the requesting user may have more of an idea of where the requested user is located. For example, if the desired user is located in a mall, primary location information **610** may be the address of the mall. In such an example, secondary location information **620** may be included and display, to the requesting user, the name of the mall.

Directional information **630** may also be included on display **600** or any other display of the present invention. Directional information **630** may include a digital compass **632** so that the user of cell phone **300** (FIG. **3**) knows what direction he or she is facing in. Digital compass **632** may be connected to a direction sensitive device (e.g., mechanical compass) in order to gather directional information. Directional arrow **633** may also be included in Display **600** to indicate where the requested user's location is relative to the location and direction of cell phone **300** (FIG. **3**) (e.g., the requesting user). Persons skilled in the art will appreciate that for some directional information **630** the location of the requesting user must be obtained. This information may be obtained either from cell phone **300**, a remote facility, or by any other suitable means. If the information is gathered from a location gathering device other than the requesting user's device (e.g., cell phone **300** (FIG. **3**)), then the user's device may communicate from this other location gathering device. Once both the locations of the requesting and requested/desired users are known, this information may be utilized in a number of features incorporating the principles of the present invention.

Distance information **634** is one such feature that displays the distance between the locations of the requested and requesting users (e.g., distance between the locations of the requested and requesting devices). Directional information **630** may contain many other elements to enhance the utility of the present invention. For example, a map (not shown in FIG.

6) may be included in display **600**. This map may be of the area surrounding either the requested, the requesting user's location or both. Information may be included on the map to show the shortest path between the location as well as information about the surrounding area (e.g., area names, store names, etc.). Other information may include, for example, time to reach the destination according to specific types of travel (e.g., subway, walking, running, driving) and the direction the requested user is traveling in.

Many uses for this information may be utilized by a user. For example, if Jane calls Bill and Bill says "I am roaming midtown manhattan shopping why don't you join me", no other call to Bill is needed. Bill simply has to give Jane access to his location and Bill can continue shopping without having to worry about meeting up with Jane at a specific location.

In some instances, it may be beneficial to find the speed and direction of a requested user. For example, if a wife wants to see how long before her husband arrives home, the wife can use this feature of the present invention. This feature may find the husbands location multiple times in a determined amount of time. Through this information the feature may determine the speed and direction that the user is traveling. Using this speed, for example, this feature may display to the wife that the husband "is 10 minutes away" in directional information **630**. In doing so, the need for a call to the husband to determine his location is eliminated.

Persons skilled in the art that the location of multiple users may be displayed on display screen **600**. For example, suppose Jeff, Susan, and Chrissy are at a concert. If all three of these users have unlimited access to the other users, principles of the present invention would allow for a map to be displayed on each of the three locating devices with locator designations for each of the users. Using such map, the group may be able to find themselves in relative location to one another and decide, if need be, on the easiest location for them to meet. Thus map **660** may be included on display screen **600** and display the locations of multiple users (e.g., user's **621** and **622**).

More region **640** designates that more options or information may be retrieved or performed using principles of the present invention. A user may use control keys **340** (FIG. **3**) on cell phone **300** (FIG. **3**) to perform the functionality associated with more region **640**.

FIG. **7** shows display screen **700** for locate listing options in accordance with the principles of the present invention. Display screen **700** includes selectable options list **710** and highlight window **720** and may be displayed to the user, for example, through the activation of functionality associated by more region **640** (FIG. **6**). Options list **710** may include any of the features of the present invention. For example, options list **710** may include options activating a display screen of a map of the requesting user's location, a map of the requested user's location, directions to the requested user's location from the requesting user's location, travel time for the requesting user, travel time for the requested user, and options to set location alerts.

FIG. **8** shows display screen **860** of a failed locate feature due to insufficient rights in accordance with the principles of the present invention. Display screen **800** may be displayed if a requesting user attempts to located a requested user but has not been given access rights by the request user to his or her location. In such an instance insufficient rights message **801** may be prompted on display screen **800**.

FIG. **9** shows display screen **900** of adding and modifying locate rights and options to a user in accordance with the principles of the present invention. A user may give or modify access rights through display **900** to a user identifier in select-

9

able user identifier listing **910**. Highlight window **920** may be included to enhance the selecting process.

FIG. **10** shows display screen **1000** of assigning location rights to a user in accordance with the principles of the present invention. Display screen **1000** may be displayed, for example, after a user has been selected to be given location rights. Display screen **1000** contains selectable location rights listing **1010**, in which the selecting process may be enhanced by highlight window **1020**. Possible location access rights may be, for example, by country, state, city, exact location, or any other scope of location. Other rights may be assigned such as particular times in the day or time periods at which locations may be accessed.

FIG. **11** shows display screen **1100** of alert options in accordance with the principles of the present invention. Display screen **1100** allows for a user to set up alerts depending on the location of specific users. Selectable alert listings **1110** are included and may be selectable with highlight window **1120**. Examples of alerts that may be included in display screen **1100** may occur, for example, if the requested user is in a specific city or the same city as the user of display **1100**, is within a certain distance, or if a user located the user of display **1100**.

The alerts of the present invention may realize useful functionality. For example, suppose Susan Pracht lives in Pittsburgh and rarely comes to the city of the user of display screen **1100** on cell phone **300** (FIG. **3**) which is New York City. The user of cell phone **300** (FIG. **3**) may then use display screen **1100** and set an alert such that if Susan Pracht ever enters New York City, he or she would be alerted of Susan Pracht's presence.

FIG. **12** shows display screen **1200** of an alert feature in accordance with the principles of the present invention. Display screen **1200** includes an alert message and is displayed to a user when an event occurs that is designated by the user in display screen **1100** (FIG. **11**). Continuing the example from FIG. **11**, if Susan Pracht enters New York City, alert message **1210** would prompt the user that this event has occurred.

FIG. **13** shows display screen **1300** of a login feature in accordance with the principles of the present invention. In order for users to be identified by other user's cell phones or locating devices a user profile may need to be stored remotely from such devices. In such instances user profiles would be used as the locating identifier and the devices into which these profiles are logged into (recognized by) would allow for the user to be located. Display screen **1300** allows for a user to log into a locating device of the present invention. Logging into a device also adds a level of security to the present invention, especially when combined with a password. A user may use the controls of the device of the present invention to enter login **1310** of display **1300**.

In this manner a user may use another user's location device (e.g., cell phone) to locate a user or may use, for example, the internet to locate a user. Additionally, in this manner, a user may change the device being located. For example, a user may use his or her car GPS system or other systems in accordance with the principles of the present invention to be located instead of his or her cell phone. To further this example, a user may log into a web site on the internet and designate his or her current location as home, or any other location, thus eliminating the need for locatable device entirely.

FIG. **14** shows display screen **1400** of a login feature in accordance with the principles of the present invention. Display screen **1400** may be used by a user to enter a password associated to his profile, identity, or cell phone functionality access. A user may enter password **1410** using the controls of

10

the device of display screen **1400** (e.g., cell phone **300** of FIG. **3**). By including a login/password scheme a user can be identified by a remote facility (e.g., a remote database) so that the user's location can be recorded/updated by multiple devices. Additionally, a login/password adds an extra level of security.

FIG. **15** shows cell phone **1500** that may be utilized to carry out the functionality in accordance with the principles of the present invention. Cell phone **1500** includes receiver/transmitter **1510**, microprocessor **1520**, positioning system **1530**, and memory **1540**.

Persons skilled in the art will appreciate that receiver/transmitter **1510** may directly communicate with memory **1540** if receiver/transmitter **1510** does not have its own memory (e.g., if receiver/transmitter **1510** are configured to utilize a buffer for capturing incoming communications bursts before demodulation and decryptions).

Positioning system **1530** may be, for example, a GPS system or a similar positioning system. Positioning system **1530** may include its own receiver for receiving particular signals utilized in positioning cell phone **1500**.

FIG. **16** shows network topology **1600**, in which all components of, or a part of the components of, may be utilized to carry out the features in accordance with the principles of the present invention. In this manner, persons skilled in the art will appreciate that multiple system configurations may be utilized. Topology **1600** introduces the diversity of systems that can be utilized to realize such configurations.

Generally, topology **1600** includes multiple mobile devices (e.g., multiple instances of mobile device **1601**), access control devices and location broker devices (e.g., database **1602** and cell phone base station **1603**), and non-mobile devices (e.g., grounded non-wireless device **1605**). Persons skilled in the art will appreciate that other devices or facilities may be included in topology **1600**. For example, one or more positioning systems **1601** may be included in topology **1600** in order to locate particular devices. For example, a positioning receiver (e.g., GPS receiver) may be included in wireless device **1601** with positing system **1601** being a positioning transmitter (e.g., GPS satellite network).

One or more wireless devices **1601** may be included in topology **1600** and may be, for example, watches, PDAs, cellular phones, radios, cars, or any other mobile device whose location can be determined.

As previously mentioned, access control and location broker devices may be included in topology **1600**. Such devices may be utilized, for example, to store user access rights for a particular user and may contain functionality to request and route a device's location. These devices may be considered information broker's such that devices may be added, removed, or modified without creating the necessity of having to modify the other devices of topology **1600**.

Database **1602** is one such information broker. Database **1602** may, for example, be located in cell phone base station **1603** if database **1602** is utilized to assist in cell phone locating. Database **1602** may be utilized, for example, to store a history of a device's locations, a user's list of assigned access rights to other users, a log of a user's call activity, a log of a location initiations, a user profile, login/password information, or any other sort of information. Many features may be provided that utilize such information. For example, n approximate location may be determined for a device that is turned OFF (e.g., by utilizing the device's location history). As per another example, if a cell phone is lost and a new one replaced, information such as, for example, phone books, activity logs, and assigned user access rights may be downloaded/flushed into the cell phone.

Database **1602** may be accessed either directly (e.g., manually by an user of the device) or indirectly (e.g., periodically) by a cell phone or other device. Alternatively, a device or cell phone may access database **1602** directly (e.g., manually by an administrator of the database) or indirectly (e.g., periodically) by database **1602**.

A credit card authorization system is an example of additional system **1606** that may be added to topology **1600** to realize new features. Such a credit card authorization system, as described above, could utilize a device's location in order to decrease credit card fraud. System **1600** may also be, for example, systems needed to realize the described dating functionalities or another information provider (e.g., a map information provider).

Non-wireless devices **1605** (e.g., a personal computer) may be included in topology **1600**. Such devices may have locations associated to them or contain a positioning system. These locations may then be associated to a user that is recognized as using the device. For example, if a particular user logs into a non-mobile personal computer, that user's location will be recognized as being the location associated to the personal computer.

The devices of topology **1600** communicate with each other through communications network **1610**. Communications network **1610** may include, for example, any type of communications, routing, amplification, encryption, decryption, parsing, modulation, or demodulation technologies. For example, positioning system **1601** may communicate with wireless device **1601** by sending multiple wireless positioning signals. At the same time, database **1602** may be providing non-wireless device **1605** with a device's location over conventional telephone wires.

FIG. 17 shows locating feature **1700** in accordance with the principles of the present invention. Locating feature **1701** starts at step **1701** and waits at step **1702** until a location is requested. As stated, a location can be requested in a number of instances and by a variety of different means.

For example, a location may be requested by a user of a cell phone that desires to locate a friend by locating that friend's cell phone. Alternatively, a device may be triggered to request a location of a mobile device when an event occurs. For example, a credit card authorization system may request the location of a user's cell phone and the location of a store that just used a credit card associated to the requested user.

If a location is requested, access rights to the requested location for the requesting device and/or user are obtained at step **1703**. Step **1703** may be employed for example, as a call to a database storing a list of assigned access rights for the requested device/user and finding if any access rights were assigned to the requestor's identity. As per another example, step **1703** may be employed as a direct call to the requested device/user.

Step **1704** determines if the requestor has been assigned access rights to obtain the requested device/user's location. Persons skilled in the art will appreciate that some devices may always have access to a user's location regardless if a user has assigned access rights to the requesting device. In this manner, a device may be set up to always let a user access a location. For example, a mother may purchase a cell phone for a minor and may configure the cell phone to always allow her location information.

If access rights do exist for the requesting device/user at step **1704** then step **1705** may be initiated and location information may be provided to the requester. Such location information may be filtered according to the assigned access rights. For example, if a user has only been assigned access rights to obtain the requested user's city location, only the city

that the requested user/device is currently located in (or the last city location available) may be obtained. The process then finishes at step **1707** after the assigned location information has been delivered to the requester at step **1705**. Persons skilled in the art will appreciate that steps may be added to, removed, or modified from locating feature **1700**. For example, instead of finish step **1707**, step **1702** may be initiated after step **1706** has completed.

If a requestor has not been assigned rights to access the requested user/device's location as determined by step **1704**, then step **1712** may be initiated. Step **1712** informs the requestor that the requester does not have access rights to obtain the location of a user/device. Step **1711** may follow and provide an opportunity for the requester to obtain the access rights. More particularly, step **1711** asks the requester if the requestor would like to request access rights. If the requestor does not want to request access rights, locating feature **1700** may, for example, return to step **1702**. Else, access rights may be requested at step **1721**. Step **1722** follows and if access rights were given then step **1705** may be initiated. Else, step **1712** may, for example, be re-initiated.

FIG. 18 shows one embodiment of a cell phone burst that has been configured to embed a device or user's location **1801** between control signals (e.g., synchronization signals) and data signals. Persons skilled in the art will appreciate that some cell phone burst standards (e.g., TDMA and CDMA) have signal portions that are reserved for future technologies. In one embodiment, this reserved portion is utilized to house location information **1801**. A cell phone tower or base information may then strip received signals **1800** of location information **1801**, store location information **1801** into a database or other storage device, and deliver the received signals to its desired location. In this manner, a user may refresh his/her location information every time that a cell phone base station receives or routes information for the user. By stripping location information **1801** from signal **1800**, the intended receiver does not have access to the location of the device transmitting signal **1800**. A signal similar to signal **1800** may be sent to a cell phone that has requested, and has the appropriate location access rights, to location **1801**. Location **1701** may also be stored in other portions of signal **1700** that are not reserved portions. For example, a received signal **1800** may store location information in the data portions of signal **1800**. In embodiments where additional information is sent about location **1801** (e.g., a map associated with location **1801**) utilizing a main data portion of signal **1800** is preferred. Persons skilled in the art will appreciate that signal burst **1800** may actually be any type of communication signal such as, for example, information returned from a database inquiry.

Persons skilled in the art will also appreciate that the systems and methods of the present invention may be implemented using other locating features and configurations. For example, a user may be manually requested to allow location access rights every time his/her location is requested. As per another example, a user may organize his/her user list into groups and assign access rights to that group (e.g., family member user group, close friend user group). All such modifications are within the scope of the present invention, which is limited only by the claims that follow.

What is claimed is:

1. A method comprising:

obtaining a location of a first wireless telephone;
transmitting said location from said first wireless telephone to a remote server;

changing, at the direction of said first wireless telephone, a list of users on said remote server for a profile associated with said first wireless telephone that are allowed to

13

access said location, wherein each user of said list of users is representative of one of a plurality of wireless telephones;
 transmitting said location from said remote server to at least one of said users of said list of users; 5
 determining a second location associated with one of said plurality of wireless telephones; and
 providing directional information to said one of said plurality of wireless telephones, wherein said directional information is representative of directions between said location and said second location. 10

2. The method of claim 1, wherein said changing comprises adding an additional user to said list of users.

3. The method of claim 1, further comprising transmitting the address of said location to said at least one of said users of said list of users. 15

4. The method of claim 1, further comprising:
 obtaining the address of said location from a remote information provider; and
 transmitting the address of said location to said at least one of said users of said list of users. 20

5. The method of claim 1, further comprising:
 receiving said location by at least one of said plurality of wireless telephones; and
 displaying said location on said at least one of said plurality of wireless telephones. 25

6. The method of claim 1, further comprising determining a third location associated with one of said plurality of wireless telephones.

7. The method of claim 1, further comprising: 30
 receiving said location by at least one of said plurality of wireless telephones; and
 displaying the name of said location on said at least one of said plurality of wireless telephones.

8. The method of claim 1, further comprising determining the distance between said first wireless telephone and at least one of said plurality of wireless telephones. 35

9. The method of claim 1, further comprising:
 receiving said location by at least one of said plurality of wireless telephones; and
 displaying a map on said at least one of said plurality of wireless telephones with a marker representative of said location. 40

10. The method of claim 1, wherein the location is obtained by way of manual input that is received by way of a locate button provided on said first wireless telephone. 45

11. The method of claim 1, further comprising:
 determining a third location of a device based on the IP address of said device; and
 transmitting said location to said device. 50

12. The method of claim 1, further comprising:
 receiving manual input for a third location wherein said third user is associated with said manually input third location.

13. A method comprising: 55
 determining a location of a first wireless telephone;
 transmitting said location from said first wireless telephone to a remote server;
 changing a list of users on said remote server for a profile associated with said first wireless telephone that are allowed to access said location, wherein each user of said list of users is representative of one of a plurality of wireless telephones; 60
 transmitting an alert message, comprising information associated with said location, from said remote server to a user of said list of users when said user is within a certain distance of said location; 65

14

determining a second location associated with said wireless telephone associated with said one user; and
 providing directional information to said wireless telephone associated with said user, wherein said directional information is representative of directions between said location and said second location.

14. A method comprising:
 obtaining a location of a first wireless telephone;
 transmitting said location from said first wireless telephone to a remote server;
 changing, at the direction of said first wireless telephone, a list of users on said remote server for a profile associated with said first wireless telephone that are allowed to access said location, wherein each user of said list of users is representative of one of a plurality of wireless telephones; and
 transmitting said location from said remote server to at least one of said users of said list of users;
 receiving manual input for a second location;
 determining an identity of a second user for a device by way of a login; and
 transmitting said location to said device, wherein said second user is associated with said manually input second location.

15. A method comprising:
 obtaining a location of said first wireless telephone;
 transmitting said location from said first wireless telephone to a remote server;
 changing a list of users on said remote server for a profile associated with said first wireless telephone that are allowed to access said location, wherein each user of said list of users is representative of one of a plurality of wireless telephones;
 transmitting an alert message, comprising information associated with said location, from said remote server to a user of said list of users when said user is within a certain distance of said location;
 determining a second location associated with said wireless telephone associated with said one user; and
 providing directional information to said wireless telephone associated with said user, wherein said directional information is representative of directions between said location and said second location.

16. The method of claim 15, wherein said changing comprises adding an additional user to said list of users.

17. The method of claim 15, further comprising transmitting the address of said location to at least one of said users of said list of users.

18. The method of claim 15, further comprising:
 obtaining the address of said location from a remote information provider; and
 transmitting the address of said location to at least one of said users of said list of users.

19. The method of claim 15, further comprising determining a third location associated with said wireless telephone associated with said user.

20. The method of claim 15, further comprising:
 receiving said location by said wireless telephone associated with said user; and
 displaying the name of said location on said wireless telephone associated with said user.

21. The method of claim 15, further comprising determining the distance between said first wireless telephone and said wireless telephones associated with said user.

22. The method of claim 15, further comprising:
 receiving said location by said wireless telephone associated with said user; and

15

displaying a map on said wireless telephone associated with said user, wherein a marker is displayed on said map that is representative of said location.

23. The method of claim 13, wherein said changing comprises adding an additional user to said list of users.

24. The method of claim 13, further comprising transmitting the address of said location to at least one of said users of said list of users.

25. The method of claim 13, further comprising:
obtaining the address of said location from a remote information provider; and
transmitting the address of said location to at least one of said users of said list of users.

26. The method of claim 13, further comprising determining a third location associated with said wireless telephone associated with said user.

27. The method of claim 13, further comprising:
receiving said location by said wireless telephone associated with said user; and
displaying the name of said location on said wireless telephone associated with said user.

28. The method of claim 13, further comprising determining the distance between said first wireless telephone and said wireless telephones associated with said user.

29. The method of claim 13, further comprising:
receiving said location by said wireless telephone associated with said user; and
displaying a map on said wireless telephone associated with said user, wherein a marker is displayed on said map that is representative of said location.

30. A method comprising:
obtaining a location of said first wireless telephone;
changing, at the direction of said first wireless telephone, a list of users on a remote server for a profile associated with said first wireless telephone that are allowed to access said location, wherein each user of said list of users is representative of one of a plurality of wireless telephones;
transmitting said location from said remote server to at least one of said users of said list of users;
determining a second location associated with one of said plurality of wireless telephones; and
providing directional information to said one of said plurality of wireless telephones, wherein said directional information is representative of directions between said location and said second location.

31. The method of claim 30, wherein said changing comprises adding an additional user to said list of users.

32. The method of claim 30, further comprising transmitting the address of said location to said at least one of said users of said list of users.

33. The method of claim 30, further comprising:
obtaining the address of said location from a remote information provider; and
transmitting the address of said location to said at least one of said users of said list of users.

34. The method of claim 30, further comprising:
receiving said location by at least one of said plurality of wireless telephones; and
displaying said location on said at least one of said plurality of wireless telephones.

16

35. The method of claim 30, further comprising determining a third location associated with one of said plurality of wireless telephones.

36. The method of claim 30, further comprising:
receiving said location by at least one of said plurality of wireless telephones; and
displaying the name of said location on said at least one of said plurality of wireless telephones.

37. The method of claim 30, further comprising determining the distance between said first wireless telephone and at least one of said plurality of wireless telephones.

38. A method comprising:
obtaining a location of said first wireless telephone;
changing a list of users on a remote server for a profile associated with said first wireless telephone that are allowed to access said location, wherein each user of said list of users is representative of one of a plurality of wireless telephones;

transmitting an alert message, comprising information associated with said location, from said remote server to a user of said list of users when said user is within a certain distance of said location;

determining a second location associated with said wireless telephone associated with said one user; and
providing directional information to said wireless telephone associated with said user, wherein said directional information is representative of directions between said location and said second location.

39. The method of claim 38, wherein said changing comprises adding an additional user to said list of users.

40. The method of claim 38, further comprising transmitting the address of said location to at least one of said users of said list of users.

41. The method of claim 38, further comprising:
obtaining the address of said location from a remote information provider; and
transmitting the address of said location to at least one of said users of said list of users.

42. The method of claim 38, further comprising determining a third location associated with said wireless telephone associated with said user.

43. The method of claim 38, further comprising:
receiving said location by said wireless telephone associated with said user; and
displaying the name of said location on said wireless telephone associated with said user.

44. The method of claim 38, further comprising determining the distance between said first wireless telephone and said wireless telephones associated with said user.

45. The method of claim 38, further comprising:
receiving said location by said wireless telephone associated with said user; and
displaying a map on said wireless telephone associated with said user, wherein a marker is displayed on said map that is representative of said location.

46. The method of claim 38, wherein location is obtained by way of manual input manual input that is received by way of a locate button provided on said first wireless telephone.

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 8,374,575 B2
APPLICATION NO. : 11/387384
DATED : February 12, 2013
INVENTOR(S) : Jeffrey D. Mullen

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

In the Claims

Claim 30, Column 15, Line 32: "said first wireless telephone" should read --a first wireless telephone--.

Signed and Sealed this
Thirtieth Day of November, 2021



Drew Hirshfeld
*Performing the Functions and Duties of the
Under Secretary of Commerce for Intellectual Property and
Director of the United States Patent and Trademark Office*