DECLARATION OF KAREN LEE

I, Karen Lee, pursuant to 28 U.S.C. § 1746, hereby declare as follows:

1. I am a Translator at TransPerfect, Inc.

2. I submit this declaration to certify the accuracy of the English translation of CN2187379Y_一种轻便鞋.

3. My statements are based on personal knowledge and my review of CN2187379Y_一种轻便鞋 and its Chinese to English translation. If called as a witness about the facts contained in these statements, I could testify competently based on such personal knowledge and the investigation I have conducted.

4. Attached as Exhibit A is a true and accurate copy of CN2187379Y_一种轻便鞋.

5. Attached as Exhibit B is a true and accurate copy of an English translation of CN2187379Y_一种轻便鞋 ("the CN2187379Y_一种轻便鞋 Translation").

6. The CN2187379Y_一种轻便鞋 Translation is a true and accurate translation of CN2187379Y_一种轻便鞋 from Chinese to English.

7. All statements made herein of my own knowledge are true, and all statements made on information and belief are believed to be true. Further, I am aware that these statements are made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 U.S.C. § 1001.

I declare under penalty of perjury under the laws of the United States of America that the foregoing is true and correct. Executed on March 18, 2024, at New York, New York.

Karen Lee

EXHIBIT A

[19]中华人民共和国专利局

[11] 授权公告号 CN 2187379Y

[12] 实用新型专利说明书

[21] ZL 专利号 94202604.7

[51]Int.Cl[5]

A43B 1/04

[45]授权公告日 1995年1月18日

[22]申请日 94.2.1 [24]颁证日 94.10.30

[21]申请号 94202604.7

[73]专利权人 李文学

地址 050051河北省石家庄市工农路48号3-203

[72]设计人 李文学

[74]专利代理机构 河北省科技专利事务所

代理人 米文智

说明书页数: 附图页数:

[54]实用新型名称 一种轻便鞋

[57]摘要

一种轻便鞋，它由鞋面和鞋底构成，其特点是鞋面用两层具有弹性的绒线编织物制成，鞋面的鞋口处具有定型结构，内装松紧带。本实用新型轻便、透气、保暖、舒适，可广泛用作各年龄段的休闲鞋。



Skechers EX1056-p.3
Skechers v Nike

权 利 要 求 书

1. 一种轻便鞋由鞋底、鞋面构成，其特征在于，鞋面是由双层具有弹性的绒线编织物制成，鞋面的鞋口处具有定型结构，在其内装设松紧带。

2. 如权利要求1所述的轻便鞋，其特征在于，鞋口处可以加高，制成高腰靴型轻便鞋。

说　明　书

一　种　轻　便　鞋

本实用新型属于鞋类。

现有的鞋类品种繁多，每双鞋均由鞋底和鞋面构成. 鞋面由皮革、人造革、毡、呢、棉布等为料制成，这些材料由于质地致密，一般强度较大但伸缩性均不大，用这些伸缩性不大的材料制成的鞋为适应不同人的脚的需要，制鞋时，将鞋严格按长度分为多个号；又按人脚的肥瘦程度将每个号又分为多个型. 虽有多号多型的鞋，也难完全适应每个人的脚. 另外多数鞋重量较大，透气性较差，穿着不舒适。

本实用新型的目的是提供一种伸缩性大，重量轻，透气性好，穿着舒适的轻便鞋。

该实用新型是这样实现的：一种轻便鞋，由鞋底、鞋面构成，其特征在于鞋面是由双层具有弹性的绒线编织物制成，鞋面内外两层的编织花纹方向互为垂直；鞋面的鞋口处具有定型结构，定型结构内装设松紧带。

前述的轻便鞋，其特征在于鞋口处可以加高，制成高腰靴型轻便鞋。

绒线编织物具有伸缩性大，保暖性和透气性好的特点，因而穿着舒适，但由于其伸缩性大，特别是垂直编织花纹的方向上变形性较大，强度也较低，本实用新型为取其之长，避其之短，采用双层结构的绒线编织物，并且使双层绒线编织物的编织花纹相同或垂直，因而克服其不足. 并且在鞋口处还增设了定型结构，这样使本实用新型的轻便鞋既保持一定形状和强度，还穿着舒适，透气，轻便，保暖，随脚和美观。

制作本实用新型的鞋，鞋底可选布底、皮革底、胶底、塑料底、及塑胶底等，按不同长度作成各种型号的鞋底，其肥瘦可取中型的. 该实用新型的鞋面，可选用毛线、人造毛线、混仿毛线. 用编织机或手工按大小号鞋的需要，编织成各种型号的鞋面. 编织用的绒线可以是一种颜色，也可以是不同颜色，编织鞋面时，可以用平针，或其它针法编织成，也可编织图案. 鞋面的鞋口处定型结构是采用与外层鞋面编织花纹不同方向的编

Skechers EX1056-p.5
Skechers v Nike

织物实现的，定型结构内装设具有弹性的松紧带，用以保持或恢复鞋口的一定形状. 将编纺织好的鞋面与鞋底进行连接，即制成本实用新型. 鞋底和鞋面连接的方法可采用粘接，绳绱或压模的方法连接。

本实用新型的鞋面都是单独编织而成的，不进行剪裁，因而也不会脱线，再是鞋面为双层结构，并且内外两层编织方向相同或垂直，保证鞋在各个方向的受力强度，使穿着牢固。

本实用新型的鞋面因采用绒线编织，故具有伸缩性，每个鞋号仅只作成中型即可，靠鞋面的伸缩性，肥瘦脚都能穿，且穿着极其舒适随脚。

本实用新型若配以微孔塑胶底，可使鞋重量更小，成为十分轻便的休闲鞋。

按本实用新型制作的鞋，透气性很好，使脚和鞋易于保持干燥清洁；本新型还有很好的保暖性. 为了进一步提高保暖效果，鞋面还可以加厚，或编织成多层. 也可以自鞋口处加高制成高腰靴型轻便鞋。

图1为本实用新型结构示意图。

图中. 1-外层鞋面； 2-定型结构； 3-松紧带； 4-内层鞋面； 5-鞋底

本实用新型可以按下述步骤制成：

选用微孔塑料鞋底5，然后取毛线在编织机上用平针编织与鞋底5相应大小号的外层鞋面1。编制外层鞋面1时，由鞋前端起针往后编织，并适当加针，达一定长度时，进行分针，织成"人"字形，满足一定要求时，再合拢后跟，制成外层鞋面1. 编织内层鞋面4时，按照外层鞋面1底的大小起针向鞋口处编织，使内层鞋面4与外层鞋面1的编织花纹方向相同或垂直，织到鞋口处即制成了内层鞋面4，将外层鞋面1套在内层鞋面4的外面即制成轻便鞋的鞋面. 于鞋口处，垂直外层鞋面1的编织花纹方向上挑针编织定型结构2的编织条，为使定型结构能有效地定型，定型结构内装设具有弹性的松紧带3，鞋面和定型结构2制好后，将鞋面连接到鞋底5上，即制成本实用新型的轻便鞋。

还可按下述步骤制成带图案的鞋：

按实施例1的方法步骤，在编织外层鞋面1时，编织出图案，将有图案的外层鞋面1和按上文编织成的内层鞋面4重叠在一起制成的鞋面，连接在鞋底5上，制成有图案的轻便鞋，其穿着不仅轻便，透气，舒适，还十分美观。

Skechers EX1056-p.6
Skechers v Nike

说 明 书 附 图



EXHIBIT B

[19] Patent Office of the People's Republic of China [11] Authorized official number CN 2187379Y

[12] Utility model patent specification

[21] ZL patent number 94202604.7

[45] Authorized publication date: January 18, 1995 [51] Int.Cl^5
A43B 1/04

[22] Application date: February 1, 1994 [24] Award date: October 30, 1994
[73] Patent holder: Li Wenxue
Address: No. 48 Gongnong Road, Shijiazhuang City, Hebei Province, 050051 3-203
[72] Designer Li Wenxue

[21] Application number: 94202604.7
[74] Patent agency: Hebei Science and Technology Patent Office
Agent Mi Wenzhi

Number of pages in the Specifications:

Number of pages in the attached drawing:

---

[54] Utility model name: A type of lightweight shoes
[57] Abstract

A type of lightweight shoes, which consist of an upper and a sole. Its characteristic is that the upper is made of two layers of elastic wool knitted fabric. The upper has a shaping structure at the opening of the shoe, and an elastic band is installed inside it. The utility model is light, breathable, heat-retaining and comfortable, and can be widely used as casual shoes for all ages.



(BJ) No. 1452

Claims

1. A type of lightweight shoes, which consist of a sole and an upper. The upper is characterized in that the upper is made of two layers of elastic wool knitted fabric. The upper has a shaping structure at the opening of the shoe, and an elastic band is installed inside it.

2. The lightweight shoes as claimed in Claim 1 are characterized in that the shoe opening can be raised to make high top, boot-type lightweight shoes.

A type of lightweight shoes

The utility model is considered footwear.

There are many types of footwear, and each pair of shoes is composed of a sole and an upper. The upper is made of leather, artificial leather, felt, wool, or cotton and so on. Due to their dense texture, these materials are generally strong but not very elastic. In order to adapt to the needs of different people's feet, shoes made of these materials with low elasticity are divided into multiple sizes strictly according to length when making shoes; although there are many sizes and types of shoes, it is difficult to fully adapt to everyone's feet. In addition, most shoes are heavy, have poor air permeability, and are uncomfortable to wear.

The purpose of this utility model is to provide a lightweight shoe with significant elasticity, light weight, good air permeability and comfortable wearing.

The utility model is achieved as follows: lightweight shoes, which consist of a sole and an upper. It is characterized in that the upper is made of two layers of elastic wool knitted fabric, and the directions of the knitting patterns of the inner and outer layers of the upper are perpendicular to each other; the upper has a shaping structure at the opening of the shoe, and an elastic band is installed inside the shaping structure.

The aforementioned lightweight shoes are characterized by the fact that the opening of the shoe can be increased to create a high-top boot-type lightweight shoe.

The wool knitted fabric has the characteristics of high elasticity, good warmth retention and breathability, so it is comfortable to wear. However, due to its high elasticity, especially in the direction of vertical knitting patterns, it has greater deformation and lower strength. In order to take advantage of its advantages and avoid its shortcomings, this utility model adopts a two-layer structure of wool knitted fabric, and makes the knitting patterns of the two-layer wool knitted fabric the same or vertical, thereby overcoming its shortcomings and adding a shaping structure at the opening of the shoe. In this way, the lightweight shoes of the present invention not only maintain a certain shape and strength, but are also comfortable to wear, breathable, light, warm, adaptable to the feet and beautiful.

To make the shoes of this utility model, the soles can be made of cloth soles, leather soles, rubber soles, plastic soles, or plastic cement soles, and various types of soles can be made according to different lengths. The wide and narrow ones are preferably medium-sized. The upper of this utility model can be made of wool, artificial wool, or mixed imitation wool, using a knitting machine or by hand. Various types of uppers can be knitted according to the size of the shoes. The yarn used for knitting can be one color or different colors. When knitting the upper, it can be knitted with flat knits or other knits. Patterns can be knitted as well. The shaping structure of the upper at the opening of the shoe is achieved by using knitted fabrics with different directions from the woven pattern of the outer upper layer.

An elastic band is installed in the shaping structure to maintain or restore the shape of the shoe opening, and connect the knitted upper to the sole, that is, when the utility model is made, the sole and the upper can be connected by bonding, rope or molding.

The uppers of the utility model are woven separately without cutting, so they will not come off. Furthermore, the uppers have a two-layer structure, and the inner and outer layers are woven in the same or vertical direction, ensuring the strength of the shoe in all directions and make it firm to wear.

The shoe upper of the present utility model is woven with wool, so it has elasticity. Each shoe can only be made into a medium type. Due to the elasticity of the shoe upper, it can be worn by either wide or narrow feet, and it is extremely comfortable to wear.

If the utility model is equipped with an emblem hole plastic sole, the shoe can be made even lighter and become a very light casual shoe.

The shoes made according to the utility model have very good air permeability, making it easy to keep feet and shoes dry and clean; the shoes also have good warmth retention properties. In order to further improve the warmth retention effect, the uppers can also be thickened or woven into multiple layers, and the top of the shoe can be heightened to make a high-top boot-type lightweight shoe as well.

Figure 1 is a schematic structural diagram of the utility model.

In the picture, 1-outer upper; 2-shaping structure; 3-elastic band; 4-inner upper; 5-sole

The utility model can be made according to the following steps:

Microporous plastic soles 5 are selected, and then wool is knitted on a knitting machine with flat knits to knit the soles and outer uppers 1 of corresponding sizes. When knitting the outer shoe upper 1, start from the front of the shoe and knit it backwards, and add knits as appropriate. When it reaches a certain length, split the knits to knit it into a herringbone shape. When certain requirements are met, the heel is then closed to make the outer upper 1. When knitting the inner shoe upper 4, start the needle according to the size of the bottom of the outer shoe upper 1 and knit it toward the opening of the shoe, so that the inner shoe upper 4 and the outer shoe upper 1 have the same or perpendicular knitting pattern direction, and knit to the opening of the shoe. That is, the inner shoe upper 4 is made, and the outer shoe upper 1 is put on the outside of the inner shoe upper 4 to make the upper of a lightweight shoe. At the opening of the shoe, select needles to knit the braid strips of the shaping structure 2 vertically in the direction of the knitting pattern of the outer upper 1. In order to effectively shape the shaping structure, an elastic band 3 is installed in the shaping structure. After the upper and the shaping structure 2 are made, the upper is connected to the sole 5 to form the lightweight shoe of the present utility model.

Patterned shoes can also be made by following these steps:

According to the method steps of Embodiment 1, when knitting the outer shoe upper 1, a pattern is woven, and the upper made by overlapping the patterned outer shoe upper 1 and the inner shoe upper 4 knitted as above is connected to the sole 5, forming patterned lightweight shoes, which are not only light, breathable and comfortable to wear, but also very beautiful.

Drawing Attached to the Specifications