US010354980B1

(12) **United States Patent**
Mushiga et al.

(10) **Patent No.: US 10,354,980 B1**
(45) **Date of Patent: Jul. 16, 2019**

(54) **THREE-DIMENSIONAL MEMORY DEVICE CONTAINING BONDED CHIP ASSEMBLY WITH THROUGH-SUBSTRATE VIA STRUCTURES AND METHOD OF MAKING THE SAME**

(71) Applicant: **SANDISK TECHNOLOGIES LLC**, Plano, TX (US)

(72) Inventors: **Mitsuteru Mushiga**, Yokkaichi (JP); **Akio Nishida**, Yokkaichi (JP); **Kenji Sugiura**, Yokkaichi (JP); **Hisakazu Otoi**, Yokkaichi (JP); **Masatoshi Nishikawa**, Yokkaichi (JP)

(73) Assignee: **SANDISK TECHNOLOGIES LLC**, Addison, TX (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **15/928,407**

(22) Filed: **Mar. 22, 2018**

(51) **Int. Cl.**
H01L 25/00 (2006.01)
H01L 25/065 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC ***H01L 25/0657*** (2013.01); ***H01L 23/5226*** (2013.01); ***H01L 24/89*** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC H01L 21/8221; H01L 25/0657
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,717,231 A 2/1998 Tserng et al.
5,915,167 A 6/1999 Leedy
(Continued)

FOREIGN PATENT DOCUMENTS

JP 2016-004860 A 1/2016
JP 2016-157832 A 9/2016
JP 2017-130660 A 7/2017

OTHER PUBLICATIONS

Ariyoshi, J. et al., "Compact Three-Dimensional Memory Device Having a Seal Ring and Methods of Manufacturing the Same," U.S. Appl. No. 15/928,337, filed Mar. 22, 2018.
(Continued)

Primary Examiner — George R Fourson, III
(74) *Attorney, Agent, or Firm* — The Marbury Law Group, PLLC

(57) **ABSTRACT**

Multiple semiconductor chips can be bonded through copper-to-copper bonding. The multiple semiconductor chips include a logic chip and multiple memory chips. The logic chip includes a peripheral circuitry for operation of memory devices within the multiple memory chips. The memory chips can include front side bonding pad structures, backside bonding pad structures, and sets of metal interconnect structures providing electrically conductive paths between pairs of a first side bonding pad structure and a backside bonding pad structure. Thus, electrical control signal can vertically propagate between the logic chip and an overlying memory chip through at least one intermediate memory chip located between them. The backside bonding pad structures can be formed as portions of integrated through-substrate via and pad structures that extend through a respective semiconductor substrate.

16 Claims, 29 Drawing Sheets



(51) **Int. Cl.**

H01L 27/11582	(2017.01)
H01L 27/1157	(2017.01)
H01L 23/522	(2006.01)
H01L 23/00	(2006.01)
H01L 21/822	(2006.01)

(52) **U.S. Cl.**
CPC ***H01L 25/50*** (2013.01); ***H01L 27/1157*** (2013.01); ***H01L 27/11582*** (2013.01); *H01L 21/8221* (2013.01); *H01L 2224/80895* (2013.01); *H01L 2225/06548* (2013.01)

(58) **Field of Classification Search**
USPC 257/777; 438/108
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

7,368,328 B2 5/2008 Abbott et al.
7,557,439 B1 * 7/2009 Sasaki H01L 21/6835 257/686
7,585,419 B2 9/2009 Cheng
7,602,028 B2 10/2009 Son et al.
8,242,593 B2 8/2012 Kacker et al.
8,247,260 B2 8/2012 Sivaram et al.
8,803,206 B1 8/2014 Or-Bach et al.
9,240,330 B2 1/2016 Takeda et al.
9,240,550 B2 1/2016 Dellmann et al.
9,257,414 B2 2/2016 Chen et al.
9,293,630 B2 3/2016 Kim
9,305,934 B1 4/2016 Ding et al.
9,449,987 B1 9/2016 Miyata et al.
9,502,471 B1 11/2016 Lu et al.
9,530,790 B1 12/2016 Lu et al.
9,543,318 B1 1/2017 Lu et al.
9,741,694 B2 8/2017 Yu et al.
2005/0280112 A1 12/2005 Abbott
2006/0097363 A1 5/2006 Abbott et al.
2006/0286485 A1 12/2006 Cheng
2007/0090524 A1 4/2007 Abbott
2007/0132085 A1 * 6/2007 Shibata G11C 5/04 257/686
2007/0194455 A1 * 8/2007 Ikeda H01L 25/0657 257/777
2007/0269932 A1 11/2007 Abbott et al.
2008/0087932 A1 4/2008 Son et al.
2008/0150155 A1 * 6/2008 Periaman H01L 21/563 257/777
2008/0315421 A1 * 12/2008 Periaman H01L 25/0657 257/758
2009/0039492 A1 * 2/2009 Kang G11C 5/02 257/686
2009/0108469 A1 4/2009 Kang et al.
2009/0189290 A1 7/2009 Kacker et al.
2010/0009488 A1 1/2010 Sivaram et al.
2010/0240174 A1 9/2010 Yu et al.
2010/0283145 A1 11/2010 Chang et al.
2011/0024910 A1 2/2011 Mostafazadeh et al.
2011/0316159 A1 12/2011 Kang et al.
2012/0049361 A1 * 3/2012 Park G11C 5/025 257/738
2012/0051113 A1 * 3/2012 Choi G11C 5/025 365/51
2012/0061827 A1 * 3/2012 Fujita H01L 21/30655 257/737
2012/0243355 A1 * 9/2012 Shin G11C 29/021 365/200
2012/0267689 A1 * 10/2012 Chen H01L 27/0207 257/203
2013/0021866 A1 * 1/2013 Lee H01L 25/0657 365/230.01
2013/0026652 A1 * 1/2013 Fujii H01L 23/3128 257/774
2013/0147041 A1 6/2013 Chan et al.
2013/0187280 A1 * 7/2013 Yuan H01L 23/585 257/773
2013/0193585 A1 * 8/2013 Lin H01L 21/76898 257/774
2014/0084375 A1 3/2014 Lee et al.
2014/0117430 A1 * 5/2014 Lee H01L 25/18 257/296
2015/0064899 A1 3/2015 Ji et al.
2015/0061099 A1 5/2015 Mu et al.
2015/0187742 A1 7/2015 Kwon et al.
2015/0294955 A1 10/2015 Chen et al.
2015/0357240 A1 12/2015 Law et al.
2016/0079164 A1 3/2016 Fukuzumi et al.
2016/0133603 A1 * 5/2016 Ahn H01L 25/16 365/63
2016/0307910 A1 10/2016 Son et al.
2018/0204791 A1 7/2018 Chen et al.

OTHER PUBLICATIONS

Mushiga, M. et al., "Three-Dimensional Memory Device Containing Bonded Chip Assembly With Through-Substrate Via Structures and Method of Making the Same," U.S. Appl. No. 15/928,340, filed Mar. 22, 2018.
U.S. Appl. No. 15/638,672, filed Jun. 30, 2017, Sandisk Technologies LLC.
U.S. Appl. No. 15/873,101, filed Jan. 17, 2018, Sandisk Technologies LLC.
U.S. Appl. No. 15/892,648, filed Feb. 9, 2018, Sandisk Technologies LLC.
USPTO Office Communication, Non-Final Office Action for U.S. Appl. No. 15/928,340, dated Aug. 10, 2018, 24 pages.
International Search Report and Written Opinion of the International Searching Authority for International Patent Application No. PCT/US2018/062107, dated Mar. 14, 2019, 12 pages.

* cited by examiner



FIG. 1A



FIG. 1B



FIG. 2



FIG. 3


600
100
270
232
246
180
170
132
146
8
88
58
59
74
61
76
59
98
303
302
588
586
10
6
86
96
760
9
200
20
96
284
282
280
265
165
303
302
94
586
588

FIG. 4


600
100
270
232
246
180
170
132
146
8
88
58
59
74
61
76
59
298
98
303
302'
588
586
10
6
86
96
760
9
200
20
96
290
284
282
280
265
165
298
296
303
302'
94
586
588
1000

FIG. 5


600
100
270
232
246
180
170
132
146
8
88
58
59
74
61
76
59
298
98
303
302
588
586
10
6
86
96
1100
760
9
200
20
96
290
284
282
280
265
165
298
296
303
302
94
586
588
1000

FIG. 6


600
100
270
232
246
180
170
132
146
8
88
58
59
74
76
61
59
298
98
303
302
588
586
10
6
86
1100
96
760
9
200
20
96
290
284
282
280
265
165
298
296
303
302
94
586
588
1000

FIG. 7


600
100
270
232
246
180
170
132
146
8
88
74
58
59
61
76
98
298
302
305
588
586
10
6
86
96
1100
760
9
200
20
290
284
282
280
265
165
296
94
1000

FIG. 8


600
100
270
232
246
180
170
132
146
8
88
58
74
76
61
59
59
298
98
302
305
588
586
10
6
306
86
1100
96
760
9
200
20
96
290
284
282
280
265
165
298
296
302
305
94
586
588
1000

FIG. 9


600
100
270
232
246
180
170
132
146
8
88
58
59
74
61
76
59
298
98
302
588
586
10
6
306
86
96
1100
760
9
310L
200
20
96
290
284
282
280
265
165
298
296
302
308L
94
586
588
1000

FIG. 10


600
100
270
232
246
180
170
132
146
8
88
58
59
74
61
76
59
298
98
302
588
586
10
6
306
86
8F
96
1100
760
9
200
20
8B
96
290
284
282
280
265
165
298
296
316
302
308
318
94
586
588
310
1000

FIG. 11


600
100
270
232
246
180
170
132
146
8
88
58
59
74
76
461
298
98
302
310
588
586
10
6
306
86
8F
96
760
9
320
1100'
200
20
8B
96
290
284
282
280
265
165
298
296
316
302
308
318
94
586
588
1000

FIG. 12


408
498
742
403
402'
674
758
754
752
750
756
490
780
720
409
788
785
786
784
782
742
760
766
764
762
700
498
742
403
402'
4000

FIG. 13


408
498
742
403
402
674
758
754
752
750
1400
490
780
756
720
409
788
785
786
784
782
742
760
766
764
762
700
498
742
403
402
4000

FIG. 14


408
498
742
402
410
674
406
758
754
752
750
1400
490
780
756
720
409
788
785
786
784
782
742
760
766
764
762
700
742
416
402
407
418
498
4000

FIG. 15


408
498
742
402
410
674
406
758
754
752
750
490
780
756
720
409
420
1400'
788
785
786
784
782
742
760
766
764
762
700
498
742
416
402
407
418
4000

FIG. 16A


408
498
742
674
758
754
752
750
756
490
780
720
409
420
1400'
788
785
786
784
782
742
760
766
764
762
700
742
498
4000'

FIG. 16B



FIG. 17C



FIG. 17B



FIG. 17A


100
270
232
246
180
170
132
146
8
408
88
58
59
74
61
76
59
298
98
302
310
498
742
402
410
588
586
10
6
674
306
406
86
758
754
752
750
96
9
490
409
780
756
720
200
760
788
785
786
784
782
742
20
760
96
290
766
764
762
700
284
282
280
265
165
298
296
316
302
308
318
498
742
416
402
407
418
94
586
588
1000
4000

FIG. 18A


100
270
232
246
180
170
132
146
8
408
88
58
59
74
61
76
59
298
98
302
310
498
588
586
10
674
6
306
86
758
754
752
750
96
9
490
780
756
720
409
200
760
788
785
786
784
782
742
20
760
96
290
766
764
762
700
284
282
280
265
165
298
296
316
302
308
318
498
742
94
586
588
1000
4000'

FIG. 18B





FIG. 19C



FIG. 19B



FIG. 19A



FIG. 19D



FIG. 19E



FIG. 19F



FIG. 19I



FIG. 19H



FIG. 19G



FIG. 19L



FIG. 19K



FIG. 19J



FIG. 20A

FIG. 20B



FIG. 20C


920
900
800
918
850
520
298
1001
818
318
298
1002
318
298
1003
318
498
4000/4000'

FIG. 21


600
100
270
232
246
180
170
132
146
8
88
58
59
74
76
61
59
298
98
302
305
588
586
10
6
306
86
1100
96
9
760
200
20
96
290
284
282
280
265
165
298
296
302
305
94
586
588
1000

FIG. 22A


600
100
270
232
246
180
170
132
146
8
88
58
59
74
61
76
59
298
98
302
588
586
10
6
306
86
96
1100
760
9
310L
200
20
96
290
284
282
280
265
165
298
296
302
308L
94
586
588
1000

FIG. 22B


600
100
270
232
246
180
170
132
146
8
88
58
59
74
76
61
59
298
98
302
588
586
10
6
306
86
8F
1100
96
760
9
200
20
8B
96
290
284
282
280
265
165
298
296
316
302
308
318
94
586
588
310
1000

FIG. 22C

THREE-DIMENSIONAL MEMORY DEVICE CONTAINING BONDED CHIP ASSEMBLY WITH THROUGH-SUBSTRATE VIA STRUCTURES AND METHOD OF MAKING THE SAME

FIELD

The present disclosure relates generally to the field of semiconductor devices, and particularly to a three-dimensional memory device containing bonded chip assemblies with through-substrate via (TSV) structures and methods of manufacturing the same.

BACKGROUND

Three-dimensional NAND flash memory devices can be used in imaging products, removable storage products, enterprise and client solid state devices, and embedded memory devices. In order to achieve high density at a lower cost, the pitch of memory openings should be reduced, and the number of word lines in an alternating stack of insulating layers and word lines should be increased. This increases the complexity of the etch process for forming memory openings and the metal replacement process employed to form the word lines. Use of multi-tier structures for the three-dimensional NAND memory devices further increases complexity in the manufacturing process.

SUMMARY

According to an aspect of the present disclosure, a chip assembly structure is provided, which comprises: a first semiconductor chip comprising a first semiconductor substrate, first semiconductor devices located over a front side surface of the first semiconductor substrate, and first integrated through-substrate via and pad structures including a respective first through-substrate via structure and a respective first bonding pad structure and comprising a first metallic material, wherein the first integrated through-substrate via and pad structures vertically extend from the front side surface of the first semiconductor substrate to a backside surface of the first semiconductor substrate and are electrically isolated from the first semiconductor substrate by a respective tubular insulating spacer and by a backside insulating layer contacting the backside surface of the first semiconductor substrate, wherein each of the first integrated through-substrate via and pad structures has a greater lateral dimension within a horizontal plane including the front side surface of the first semiconductor substrate than within a horizontal plane including the backside surface of the first semiconductor substrate; and a second semiconductor chip comprising a second semiconductor substrate, second semiconductor devices located over a front side surface of the second semiconductor substrate, and second bonding pad structures electrically connected to a respective one of the second semiconductor devices, wherein the first bonding pad structures are directly bonded to a respective one of the second bonding pad structures.

According to another aspect of the present disclosure, a chip assembly structure is provided, which comprises: a first semiconductor chip comprising a first semiconductor substrate, first semiconductor devices located over a front side surface of the first semiconductor substrate, first through-substrate via structures vertically extending from the front side surface of the first semiconductor substrate to a backside surface of the first semiconductor substrate and are electrically isolated from the first semiconductor substrate by a respective tubular insulating spacer and by a backside insulating layer contacting the backside surface of the first semiconductor substrate, and first backside bonding pad structures located on the first through-substrate via structures at a backside of the first semiconductor substrate, wherein the first semiconductor devices comprise a three-dimensional memory device including an alternating stack of insulating layers and electrically conductive layers and a two-dimensional array of memory stack structures including a respective vertical stack of memory elements located at levels of the electrically conductive layers, a second semiconductor chip comprising a second semiconductor substrate, second semiconductor devices located over a front side surface of the second semiconductor substrate, and second bonding pad structures electrically connected to a respective one of the second semiconductor devices, wherein the first backside bonding pad structures are directly bonded to a respective one of the second bonding pad structures, wherein the second semiconductor devices in the second semiconductor chip comprise peripheral devices that provide control signals for operation of the two-dimensional array of memory stack structures in the first semiconductor chip, and a third semiconductor chip comprising a third semiconductor substrate, third semiconductor devices located over a front side surface of the third semiconductor substrate, and third-chip backside bonding pad structures electrically connected to a respective one of the third semiconductor devices, wherein the first semiconductor chip further comprises first front side bonding pad structures electrically connected to the first backside bonding pad structures and directly bonded to a respective one of the third-chip backside bonding pad structures.

According to yet another aspect of the present disclosure, a method of forming a chip assembly structure comprises forming sacrificial pillar structures extending from a front side surface of the first semiconductor substrate toward an in-process backside surface of the first semiconductor substrate, forming first semiconductor devices over the front surface of the first semiconductor substrate, thinning the first semiconductor substrate after forming the first semiconductor devices by removing a material of the first semiconductor substrate from above the in-process backside surface until the sacrificial pillar structures are exposed in a backside surface of the first semiconductor substrate, forming through-substrate cavities by removing the sacrificial pillar structures, forming first integrated through-substrate via and pad structures in the through-substrate cavities and over the backside surface of the first semiconductor substrate; and bonding the first integrated through-substrate via and pad structures to respective one of second bonding pads located on a second semiconductor substrate by surface activated bonding.

According to yet another aspect of the present disclosure, a method of forming a chip assembly structure is provided, which comprises: providing a first semiconductor chip comprising a first semiconductor substrate, first semiconductor devices located over a front side surface of the first semiconductor substrate, and first integrated through-substrate via and pad structures including a respective first through-substrate via structure and a respective first bonding pad structure and comprising a first metallic material, wherein the first integrated through-substrate via and pad structures vertically extend from the front side surface of the first semiconductor substrate to a backside surface of the first semiconductor substrate and are electrically isolated from the first semiconductor substrate by a respective tubular

insulating spacer and by a backside insulating layer contacting the backside surface of the first semiconductor substrate, wherein each of the first integrated through-substrate via and pad structures has a greater lateral dimension within a horizontal plane including the front side surface of the first semiconductor substrate than within a horizontal plane including the backside surface of the first semiconductor substrate; providing a second semiconductor chip comprising a second semiconductor substrate, second semiconductor devices located over a front side surface of the second semiconductor substrate, and second bonding pad structures electrically connected to a respective one of the second semiconductor devices; and bonding the first semiconductor chip and the second semiconductor chip by aligning the first bonding pad structures with a respective one of the second bonding pad structures and inducing surface activated bonding between the first and second bonding pad structures.

According to still another aspect of the present disclosure, a method of forming a chip assembly structure is provided, which comprises the steps of: providing a first semiconductor chip comprising a first semiconductor substrate, first semiconductor devices located over a front side surface of the first semiconductor substrate, first through-substrate via structures vertically extending from the front side surface of the first semiconductor substrate to a backside surface of the first semiconductor substrate and are electrically isolated from the first semiconductor substrate by a respective tubular insulating spacer and by a backside insulating layer contacting the backside surface of the first semiconductor substrate, first backside bonding pad structures located on the first through-substrate via structures at a backside of the first semiconductor substrate, and first front side bonding pad structures electrically connected to the first integrated through-substrate via and pad structures, wherein the first semiconductor devices comprise a three-dimensional memory device including an alternating stack of insulating layers and electrically conductive layers and a two-dimensional array of memory stack structures including a respective vertical stack of memory elements located at levels of the electrically conductive layers, providing a second semiconductor chip comprising a second semiconductor substrate, second semiconductor devices located over a front side surface of the second semiconductor substrate, and second bonding pad structures electrically connected to a respective one of the second semiconductor devices, wherein the second semiconductor devices in the second semiconductor chip comprise peripheral devices that provide control signals for operation of the three-dimensional memory device of the first semiconductor chip, bonding the first backside bonding pad structures to a respective one of the second bonding pad structures by surface activated bonding, providing a third semiconductor chip comprising a third semiconductor substrate, third semiconductor devices located over a front side surface of the third semiconductor substrate, and third-chip bonding pad structures electrically connected to a respective one of the third semiconductor devices, and bonding the first front side bonding pad structures on the first semiconductor chip to a respective one of the third-chip bonding pad structures by surface activated bonding.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. **1**A is a top-down view of a first exemplary structure including a first semiconductor substrate after formation of via openings through an upper portion of the first semiconductor substrate according to an embodiment of the present disclosure.

FIG. **1**B is a vertical cross-sectional view of the first exemplary structure along a vertical plane B-B' of FIG. **1**A.

FIG. **2** is a vertical cross-sectional view of the first exemplary structure after formation of an insulating material liner and a sacrificial material layer according to an embodiment of the present disclosure.

FIG. **3** is a vertical cross-sectional view of the first exemplary structure after formation of sacrificial pillar structures according to an embodiment of the present disclosure.

FIG. **4** is a vertical cross-sectional view of the first exemplary structure after formation of first semiconductor devices including a three-dimensional memory device according to an embodiment of the present disclosure.

FIG. **5** is a vertical cross-sectional view of the first exemplary structure after formation of front side bonding pad structures on a first semiconductor chip according to an embodiment of the present disclosure.

FIG. **6** is a vertical cross-sectional view of the first exemplary structure after attaching a first front side handle substrate to the first semiconductor chip according to an embodiment of the present disclosure.

FIG. **7** is a vertical cross-sectional view of the first exemplary structure after thinning the first semiconductor substrate according to an embodiment of the present disclosure.

FIG. **8** is a vertical cross-sectional view of the first exemplary structure after removal of the sacrificial pillar structures according to an embodiment of the present disclosure.

FIG. **9** is a vertical cross-sectional view of the first exemplary structure after formation of a backside insulating layer according to an embodiment of the present disclosure.

FIG. **10** is a vertical cross-sectional view of the first exemplary structure after formation of a metallic liner and a metal fill material layer according to an embodiment of the present disclosure.

FIG. **11** is a vertical cross-sectional view of the first exemplary structure after patterning the metallic liner and the metal fill material layer into first integrated through-substrate via and pad structures according to an embodiment of the present disclosure.

FIG. **12** is a vertical cross-sectional view of an optional derivative of the first exemplary structure after attaching a first back-side handle substrate and removing the first front side handle substrate according to an embodiment of the present disclosure.

FIG. **13** is a vertical cross-sectional view of a second exemplary structure after forming sacrificial pillar structures, second semiconductor devices, and front side bonding pad structures according to an embodiment of the present disclosure.

FIG. **14** is a vertical cross-sectional view of the second exemplary structure after attaching a second front side handle substrate to a second semiconductor chip according to an embodiment of the present disclosure.

FIG. **15** is a vertical cross-sectional view of the second exemplary structure after formation of second integrated through-substrate via and pad structures according to an embodiment of the present disclosure.

FIGS. **16**A and **16**B are vertical cross-sectional views of an optional derivatives of the second exemplary structure after attaching a second back-side handle substrate and removing the second front side handle substrate according to embodiments of the present disclosure.

FIGS. **17**A-**17**C illustrate sequential vertical cross-sectional views during formation of a first exemplary chip assembly structure according to an embodiment of the present disclosure.

FIGS. **18**A and **18**B are magnified views of the respective first and first alternative exemplary chip assembly structures after bonding the first semiconductor chip with the second semiconductor chip according to embodiments of the present disclosure.

FIGS. **19**A-**19**L illustrate sequential vertical cross-sectional views during formation of a second exemplary chip assembly structure according to an embodiment of the present disclosure.

FIGS. **20**A-**20**C illustrate sequential vertical cross-sectional views during formation of a third exemplary chip assembly structure according to an embodiment of the present disclosure.

FIG. **21** is a vertical cross-sectional view of a fourth chip assembly structure after electrically connecting a plurality of semiconductor chips after connecting an interposer and a packaging substrate according to an embodiment of the present disclosure.

FIGS. **22**A-**22**C illustrate sequential vertical cross-sectional views during formation of an alternative first integrated through-substrate via and pad structures according to an alternative embodiment of the present disclosure.

DETAILED DESCRIPTION

The present inventors realized that CMOS processes for forming transistors in a CMOS configuration (e.g., CMOS devices) for peripheral (e.g., driver) circuitry for the three-dimensional NAND memory devices are dependent on the overall thermal budget of the memory device. The high thermal budget used to form the three-dimensional NAND memory devices has a negative effect on the doped regions and layers of the CMOS device performance while shrinking the CMOS device size. In particular, CMOS-under-array (CUA) type peripheral circuits which are located directly below the three-dimensional NAND memory devices are negatively affected by hydrogen diffusion from the overlying memory devices.

Therefore, in one embodiment of the present disclosure, the peripheral circuits containing the CMOS devices can be formed on a separate substrate from the substrate containing three-dimensional NAND memory devices. The substrates can then be bonded to each other to form a bonded structure (e.g., a chip assembly structures) containing both the peripheral circuit substrate bonded to the three-dimensional NAND memory device substrate. The peripheral circuits may be located directly under the three-dimensional NAND memory devices in the bonded structure, which results in the CUA type peripheral circuits. In one embodiment of the present disclosure, at least one of the above substrates can include through-substrate via structures to interconnect the memory and CMOS peripheral devices.

In a via-middle process integration scheme, the through-substrate via structures are formed from the front side of the substrate before performing back-end-of-line (BEOL) processes that form metal interconnect structures. The substrate is subsequently thinned by backside grinding, which exposes copper or another conductor of the through-substrate via structures. The thinned substrate can be subsequently bonded to another substrate employing bump processes. However, a typical thermal budget limitation lower than 500 degrees Celsius is imposed after beginning of the BEOL processes, and containment of copper contamination after exposure of copper through backside grinding poses a challenge.

In the via-last process integration scheme, the through-substrate via structures are formed after formation of the metal interconnect structures and backside grinding of the substrate. In this scheme, a support wafer is typically used for wafer thinning, and thus, dielectric film deposition processes are conducted at low temperatures, such as lower than 230 degrees Celsius, for example. In addition, both a high level of wafer thinning uniformity and a high level of through-substrate via reactive ion etch (RIE) depth uniformity are desired, which increases process complexity.

Both the via-middle process integration scheme and the via-last process integration scheme have challenges in unit processes in order to provide high wafer chip yield. Various embodiments of the present disclosure provide a replacement-scheme through-substrate via (TSV) first process integration scheme. At least one CMOS chip and at least one memory chip can be separately formed on different substrates, and can be bonded together (e.g., by a surface activated bonding process, such as copper direct bonding) to form the chip assembly structure.

The embodiments of the disclosure can be employed to form various structures including a multilevel memory structure, non-limiting examples of which include semiconductor devices such as three-dimensional monolithic memory array devices comprising a plurality of NAND memory strings.

The drawings are not drawn to scale. Multiple instances of an element may be duplicated where a single instance of the element is illustrated, unless absence of duplication of elements is expressly described or clearly indicated otherwise. Ordinals such as "first," "second," and "third" are employed merely to identify similar elements, and different ordinals may be employed across the specification and the claims of the instant disclosure. The same reference numerals refer to the same element or similar element. Unless otherwise indicated, elements having the same reference numerals are presumed to have the same composition. Unless otherwise indicated, a "contact" between elements refers to a direct contact between elements that provides an edge or a surface shared by the elements.

As used herein, a first element located "on" a second element can be located on the exterior side of a surface of the second element or on the interior side of the second element. As used herein, a first element is located "directly on" a second element if there exist a physical contact between a surface of the first element and a surface of the second element. As used herein, a "prototype" structure or an "in-process" structure refers to a transient structure that is subsequently modified in the shape or composition of at least one component therein.

As used herein, a "layer" refers to a material portion including a region having a thickness. A layer may extend over the entirety of an underlying or overlying structure, or may have an extent less than the extent of an underlying or overlying structure. Further, a layer may be a region of a homogeneous or inhomogeneous continuous structure that has a thickness less than the thickness of the continuous structure. For example, a layer may be located between any pair of horizontal planes between, or at, a top surface and a bottom surface of the continuous structure. A layer may extend horizontally, vertically, and/or along a tapered surface. A substrate may be a layer, may include one or more layers therein, or may have one or more layer thereupon, thereabove, and/or therebelow.

A monolithic three-dimensional memory array is one in which multiple memory levels are formed above a single substrate, such as a semiconductor wafer, with no intervening substrates. The term "monolithic" means that layers of each level of the array are directly deposited on the layers of each underlying level of the array. In contrast, two dimensional arrays may be formed separately and then packaged together to form a non-monolithic memory device. For example, non-monolithic stacked memories have been constructed by forming memory levels on separate substrates and vertically stacking the memory levels, as described in U.S. Pat. No. 5,915,167 titled "Three-dimensional Structure Memory." The substrates may be thinned or removed from the memory levels before bonding, but as the memory levels are initially formed over separate substrates, such memories are not true monolithic three-dimensional memory arrays. The various three-dimensional memory devices of the embodiments of the present disclosure can include monolithic three-dimensional NAND memory devices assembled non-monolithically with the CMOS containing peripheral (i.e., driver) circuits into a chip assembly.

Generally, a semiconductor die, or a semiconductor package, can include a memory chip. Each semiconductor package contains one or more dies (for example one, two, or four). The die is the smallest unit that can independently execute commands or report status. Each die contains one or more planes (typically one or two). Identical, concurrent operations can take place on each plane, although with some restrictions. Each plane contains a number of blocks, which are the smallest unit that can be erased by in a single erase operation. Each block contains a number of pages, which are the smallest unit that can be programmed, i.e., a smallest unit on which a read operation can be performed.

Referring to FIGS. **1**A and **1**B, a first exemplary structure according to an embodiment of the present disclosure is illustrated, which includes a first semiconductor substrate **8**, such as silicon wafer. The first semiconductor substrate **8** includes a first substrate semiconductor layer **9** composed of a semiconductor material such as silicon. The first substrate semiconductor layer **9** can be an upper part of the first semiconductor substrate **8**, a doped well in the upper part of the first semiconductor substrate **8** and/or a semiconductor layer (e.g., an epitaxial silicon layer) located on the front side of the first semiconductor substrate **8**. A photoresist layer (not shown) is applied over the top surface of the first semiconductor substrate **8**, and is lithographically patterned to form openings therein. The openings in the photoresist layer can be discrete openings having a maximum lateral dimension in a range from 300 nm to 30,000 nm, such as from 1,000 nm to 10,000 nm, although lesser and greater maximum lateral dimensions can also be employed. In an illustrative example, the openings in the photoresist layer can have a circular shape or an elliptical shape. An anisotropic etch process is performed to transfer the pattern of the openings in the photoresist layer into an upper portion of the first semiconductor substrate **8**. Via openings **301** are formed through an upper portion of the first semiconductor substrate **8**. The depth of the via openings **301** can be less than the thickness of the first substrate semiconductor layer **9**. For example, the depth of the via openings **301** can be in a range from 30 microns to 600 microns, although lesser and greater depths can also be employed. In one embodiment, the via openings **301** can be formed as an array of discrete via openings. In one embodiment, the via openings **301** can be formed with a non-zero taper angle with respect to the vertical direction that is perpendicular to the top surface of the first substrate semiconductor layer **9**. Thus, each via opening **301** can be wider at a top portion than at a bottom portion. Correspondingly, the maximum lateral dimension of a via opening **301** at a top portion can be greater than the maximum lateral dimension of the via opening **301** at a bottom portion.

Referring to FIG. **2**, an insulating material liner layer **302**L and a sacrificial material layer **303**L are sequentially formed in the via openings **301**. The insulating material liner layer **302**L includes an electrically insulating material such as silicon oxide. The insulating material liner layer **302**L can be formed by oxidation of surface portions of the first semiconductor substrate **8**. For example, if the first semiconductor substrate **8** includes silicon, the insulating material liner layer **302**L can include thermal silicon oxide that is substantially free of carbon and hydrogen. Alternatively, the insulating material liner layer **302**L can by formed by a conformal deposition method such as low pressure chemical vapor deposition (LPCVD). The thickness of the insulating material liner layer **302**L can be in a range from 50 nm to 500 nm, although lesser and greater thicknesses can also be employed. The sacrificial material layer **303**L includes a material that can be removed selective to the materials of the insulating material liner layer **302**L and the first substrate semiconductor layer **9**. For example, the sacrificial material layer **303**L can include silicon nitride, germanium, a silicon-germanium alloy with a high percentage of germanium (such as more than 50%), organosilicate glass, or a polymer. Cavities may, or may not, be formed within volumes of the via openings **301** after deposition of the sacrificial material layer **303**L.

Referring to FIG. **3**, the sacrificial material of the sacrificial material layer **303**L and the insulating material of the insulating material liner layer **302**L are planarized such that excess portions of the sacrificial material layer **303**L and the insulating material liner layer **302**L that overlie the top surface of the first substrate semiconductor layer **9** are removed. A chemical mechanical planarization (CMP) process and/or a recess etch process may be employed to remove the excess portions of the sacrificial material layer **303**L and the insulating material liner layer **302**L. Each remaining portion of the sacrificial material layer **303**L constitutes a sacrificial pillar structure **303**. In one embodiment, each sacrificial pillar structure **303** can have a tapered sidewall such that a horizontal cross-sectional shape of the sacrificial pillar structure **303** decreases with a vertical distance from the top surface of the first substrate semiconductor layer **9**. Each remaining portion of the insulating material liner layer **302**L constitutes an insulating material liner **302'**.

Generally, the sacrificial pillar structures **303** are formed within an upper portion of the first semiconductor substrate **8** such that the sacrificial pillar structures **303** extend from the front side surface **8**F of the first semiconductor substrate **8** toward, but not all the way to, an in-process backside surface **8**B of the first semiconductor substrate **8**. As described below, the first semiconductor substrate **8** is subsequently thinned from the backside such that in-process backside surface of the first semiconductor substrate **8** is removed and a new backside surface of the first semiconductor substrate **8** is formed at a location more proximal to the front side of the first semiconductor substrate **8**.

Referring to FIG. **4**, first semiconductor devices **600** are formed on the front side surface of the first semiconductor substrate **8**. In one embodiment, the first semiconductor devices **600** can include a three-dimensional memory device, such as a three-dimensional NAND memory device. The three-dimensional memory device can include an alter-

nating stack of insulating layers (**132**, **232**) and electrically conductive layers (**146**, **246**) and a two-dimensional array of memory stack structures **58** including a respective vertical stack of memory elements located at levels of the electrically conductive layers. Two tiers of alternating stacks are shown in the example of FIG. **4**. However, one tier or more than two tiers can be formed instead.

An insulating material layer **760** including an insulating material such as silicon oxide can be formed over the first substrate semiconductor layer **9**. A patterned stack of a metal layer **6** and semiconductor material layer **10** can be formed above the insulating material layer **760**. Gaps between patterned portions of the semiconductor material layer **10** can be filled with an insulating material.

At least one alternating stack of insulating layers and sacrificial material layers can be formed with stepped surfaces. For example, a first alternating stack of first insulating layers **132** and first sacrificial material layers can be deposited and patterned to form first stepped surfaces. A first insulating cap layer **170** can be optionally formed over the first alternating stack prior to patterning the first stepped surfaces. A first retro-stepped dielectric material portion **165** can be formed on the first stepped surfaces. An inter-tier dielectric layer **180** can be formed above the first alternating stack and the first retro-stepped dielectric material portion **165**. First-tier memory openings can be formed through the first alternating stack by a combination of a lithographic patterning process and a first anisotropic etch process. First-tier memory opening fill structures and first-tier support opening fill structures can be formed in the first-tier memory opening and the first-tier support openings as sacrificial structures.

A second alternating stack of second insulating layers **232** and second sacrificial material layers can be deposited and patterned to form second stepped surfaces. A second insulating cap layer **270** can be optionally formed over the second alternating stack prior to patterning the second stepped surfaces. A second retro-stepped dielectric material portion **265** can be formed on the second stepped surfaces. Second-tier memory openings can second-tier support openings can be formed through the second alternating stack by a combination of a lithographic patterning process and a second anisotropic etch process. The second-tier memory openings can directly overlie the first-tier memory opening fill structures and the first-tier support opening fill structures. Inter-tier memory openings and inter-tier support openings can be formed by removing the first-tier memory opening fill structures and the first-tier support opening fill structures underneath the second-tier memory openings.

A series of processing steps can be sequentially performed to simultaneously form a memory stack structure **58** within each inter-tier memory opening and a support pillar structure **20** within each inter-tier support opening. Each of the memory stack structures **58** and the support pillar structures **20** can include, from outside to inside, a blocking dielectric layer, a charge storage layer, a tunneling dielectric layer, and a vertical semiconductor channel. An anisotropic etch can be performed to form openings through bottom portions of the tunneling dielectric layer, the charge storage layer, and the blocking dielectric layer prior to formation of the vertical semiconductor channel. Thus, the vertical semiconductor channel can contact the semiconductor material layer **10**. A surface portion of the semiconductor material layer **10** adjoined to the vertical semiconductor channels can constitute a horizontal semiconductor channel **59**. A drain region (not explicitly shown) can be formed at an upper portion of each vertical semiconductor channel.

A first contact level dielectric layer **280** can be formed over the second insulating cap layer **270**. Backside trenches can be formed through the first and second alternating stacks by a combination of a lithographic process and an anisotropic etch process. The first and second sacrificial material layers (which include a sacrificial material such as silicon nitride) can be removed selective to the first and second insulating layers (**132**, **232**), and can be replaced with first electrically conductive layers **146** and second electrically conductive layers **246**, respectively. The memory stack structures **58** and the support pillar structures **20** provide structural support while the first and second sacrificial layers are removed from the first and second alternating stacks. Source regions **61** can be formed in upper portions of the semiconductor material layer **10** that underlie the backside trenches. An insulating spacer **74** and a backside contact via structure **76** can be formed within each backside trench to provide electrical contact to the source regions **61**.

A second contact level dielectric layer **282** can be deposited over the first contact level dielectric layer **280**. Contact via structures can be subsequently formed. The contact via structures can include, for example, drain contact via structures **88** that provide electrical contact to the drain regions located in an upper portion of each memory stack structure **58**, and word line contact via structures **86** contacting a top surface of a respective one of the first and second electrically conductive layers (**146**, **246**). The first and second electrically conductive layers (**146**, **246**) comprise word lines/control gate electrodes of the three-dimensional NAND memory device.

Through-memory-level via cavities can be formed through the first and second contact level dielectric layers (**282**, **280**), through the second alternating stack (**232**, **246**), the first alternating stack (**132**, **146**), the second retro-stepped dielectric material portion **265**, and/or the first retro-stepped dielectric material portion **165**, and through the insulating material layer **760** to a top surface of a respective one of the sacrificial pillar structures **303**. An insulating spacer material layer can be conformally deposited and anisotropically etched to form an insulating spacer **586** having a tubular configuration at a periphery of each through-memory-level via cavity. At least one conductive material, such as a combination of a metallic liner and a metal fill material (e.g., tungsten) can be deposited in remaining volumes of the through-memory-level via cavities to form through-memory-level via structures **588**. Each through-memory-level via structure **588** can contact a top surface of a respective one of the sacrificial pillar structures **303**. The through-memory-level via cavities can be formed before or after formation of the electrically conductive layers (**146**, **246**). For example, the cavities can be formed before formation of the electrically conductive layers (**146**, **246**) and filled with a sacrificial or insulating material before formation of the through-memory-level via structure **588**. Alternatively, the cavities can be formed through insulating pillars extending through the alternating stacks after formation of the electrically conductive layers (**146**, **246**).

A line level dielectric layer **284** can be formed above the second contact level dielectric layer **282**. Various metal structures (**98**, **96**, **94**) can be formed within the line level dielectric layer **284**, which can include bit lines **98** electrically connected through the drain contact via structures **88** to the drain regions of vertical field effect transistors located within the memory stack structures **58**, interconnection metal lines **96** that provide electrical connection to the word line contact via structures **86** and to the first and second electrically conductive layers (**146**, **246**), and interconnec-

tion metal pads **94** that contact top surfaces of the through-memory-level via structures **588**. The region in which the word line contact via structures **86** are formed is herein referred to as a contact region **200**. The three-dimensional array of memory elements includes portions of charge storage layers within the memory stack structures **58** that are located at levels of the first and second electrically conductive layers (**146**, **246**).

Referring to FIG. **5**, additional interconnect level dielectric layers **290** and additional metal interconnect structures can be formed over the line level dielectric layer **284**. The additional metal interconnect structures can include bonding pad connection via structures **296** and front side bonding pad structures **298**. In one embodiment, the front side bonding pad structures **298** can include, and/or consist essentially of, copper. A first semiconductor chip **1000** is provided at this processing step. The first semiconductor chip **1000** can be formed as a die on the first semiconductor substrate **8** as part of a two-dimensional array of dies. Alternatively, the first semiconductor chip **1000** can be diced from the first semiconductor substrate **8** as a singulated semiconductor chip. The front side of the first semiconductor chip is the side of the three-dimensional NAND memory device, and the back side of the first semiconductor chip **1000** is the opposite side (e.g., the back side of the first semiconductor substrate **8** containing the bonding pad structures **318**).

Referring to FIG. **6**, a first front side handle substrate **1100** can be attached to the front side of the first semiconductor chip **1000**. The first front side handle substrate **1100** can have a thickness in a range from 0.5 mm to 3 mm, although lesser and greater thicknesses can also be employed. The first front side handle substrate **1100** can include any rigid material, which may be an insulating material, a semiconducting material, or a conductive material. The first front side handle substrate **1100** can be attached to the first semiconductor chip **1000** by an adhesive layer (not expressly shown) or by any other suitable temporary bonding material.

Referring to FIG. **7**, the first semiconductor substrate **8** can be thinned from the backside. Specifically, the material of the first semiconductor substrate **8** can be removed from above the in-process backside surface (i.e., the initial backside surface) of the first semiconductor substrate **8** by grinding, polishing, and/or etching. The first front side handle substrate **1100** provides structural support during the thinning of the first semiconductor substrate **8**. The first semiconductor substrate **8** can be thinned until the backside surfaces of the sacrificial pillar structures **303** are physically exposed. The bottom horizontal portions of the insulating material liners **302'** are removed during thinning of the first semiconductor substrate **8**. Each remaining portion of the insulating material liners **302'** can have a tubular configuration, and is herein referred to as a tubular insulating spacer **302**. A new backside surface of the first semiconductor substrate **8** is provided after thinning the first semiconductor substrate **8**. In one embodiment, the backside surfaces of the sacrificial pillar structures **303**, the backside surfaces of the insulating material liners **302**, and the backside surface of the first semiconductor substrate **8** can be formed within a same horizontal plane.

Referring to FIG. **8**, the sacrificial pillar structures **303** can be removed selective to the materials of the tubular insulating spacers **302** and the first substrate semiconductor layer **9**. For example, if the tubular insulating spacers **302** include silicon oxide and if the sacrificial pillar structures **303** include silicon nitride, a wet etch employing hot phosphoric acid can be performed to remove the sacrificial pillar structures **303** selective to the insulating material liners **302** and the first substrate semiconductor layer **9**. Through-substrate cavities **305** are formed in volumes formed by removing the sacrificial pillar structures **303**.

While the present disclosure is described employing an embodiment in which bottom surfaces of the through-memory-level via structures **588** are physically exposed above each through-substrate cavity **305**, embodiments are expressly contemplated herein in which any other type of metal interconnect structures (such as metal lines, metal via structures, and/or metal plates) are physically exposed above at least one through-substrate cavity **305**.

Referring to FIG. **9**, an insulating material is anisotropically deposited on the backside surface of the first semiconductor substrate **8**. In this case, the first exemplary structure can be placed in a deposition chamber upside down, and a depletive deposition process may be employed as the anisotropic deposition process. In a depletive deposition process, more material is deposited on horizontal surfaces that are proximal to a reactant stream within the deposition chamber than on vertical surfaces or on recessed surfaces that are distal from the reactant stream. Thus, more insulating material is deposited on the horizontal backside surface of the first substrate semiconductor layer **9** than on sidewalls of the tubular insulating spacers **302** or on the physically exposed surfaces of the through-memory-level via structures **588**. For example, plasma enhanced physical deposition (PECVD) process can be used to deposit the insulating material.

In one embodiment, chemical vapor deposition (CVD) of silicon oxide by decomposition of tetraethylorthosilicate (TEOS) can be used to deposit the insulating material. The CVD silicon oxide includes carbon and hydrogen at atomic concentrations greater than 1 part per million. Thus, the deposited insulating material has a greater thickness on the backside surface of the first semiconductor substrate **8** than at horizontal surfaces of metal interconnect structures (such as the through-memory-level via structures **588**) that are physically exposed above the through-substrate cavities **305**. An optional isotropic etch back process (such as a wet etch process employing dilute hydrofluoric acid) can be subsequently performed to remove any residual portion of the deposited insulating material from the surfaces of the through-memory-level via structures **588**. Horizontal surfaces of the metal interconnect structures (such as the through-memory-level via structures **588**) are physically exposed after the silicon oxide deposition and/or after the optional isotropic etch back process. The remaining horizontal portion of the insulating material constitutes a backside insulating layer **306**. The thickness of the backside insulating layer **306** can be in a range from 50 nm to 500 nm, although lesser and greater thicknesses can also be employed.

Referring to FIG. **10**, a metallic liner **308**L and a metal fill material layer **310**L can be sequentially deposited in the through-substrate cavities **305** and over the backside surface (i.e., over the backside insulating layer **306**) of the first semiconductor substrate **8**. The metallic liner **308**L includes any suitable diffusion barrier material, such as a metal (e.g., Ti or Ta), a metal alloy (e.g., Co(W,P)) and/or a conductive metallic nitride material (such as titanium nitride or tantalum nitride), and is formed on sidewalls of the through-substrate cavities **305**. The metallic liner **308**L can be deposited by a conformal deposition process such as a low pressure chemical vapor deposition (LPCVD) process. The metal fill material layer **310**L includes a metal fill material such as copper or tungsten. The metal fill material layer **310**L can be

deposited on the metallic liner **308**L in remaining volumes of the through-substrate cavities **305**.

Referring to FIG. **11**, the metallic liner **308**L and the metal fill material layer **310**L can be patterned into first through-substrate via structures **316** by chemical mechanical planarization (e.g., polishing) from the back side of the first semiconductor substrate **8**. Optionally first bonding pad structures **318** can be formed on the exposed portions of the first through-substrate via structures **316** that are exposed through layer **306** on the back side of the first semiconductor substrate **8**. For example, the first bonding pad structures **318** can be formed by selective deposition, such as by selective electroplating or electroless plating of copper on the first through-substrate via structures **316** to form first integrated through-substrate via and pad structures (**318**, **316**). Alternatively, the first bonding pad structures **318** can be omitted, and bonding pad structures from a second substrate can directly contact the first through-substrate via structures **316** after formation of a bonded structure.

Each first integrated through-substrate via and pad structure (**318**, **316**) includes a backside bonding pad structure **318** and a first through-substrate via structure **316**. The first bonding pad structures **318** protrude from the horizontal plane including the top surface of the backside insulating layer **306**. The first through-substrate via structure **316** includes vertically extending portions of the metallic liner **308**L and the metal fill material layer **310**L that are embedded within the first semiconductor substrate **8** and the backside insulating layer **306**. The backside bonding pad structure **318**, which are also referred to as backside bonding pad structures **318**, can be physically exposed on the backside of the first semiconductor chip **1000**. Each first integrated through-substrate via and pad structure (**318**, **316**) includes a patterned portion of the metallic liner **308**L, which is herein referred to as a metallic liner **308**, and a patterned portion of the metal fill material layer **310**L and any selectively grown bonding pad material thereon, which are herein referred to as a metallic fill material portion **310**.

Referring to FIG. **12**, an optional derivative of the first exemplary structure is illustrated, which can be derived from the first exemplary structure of FIG. **11** by forming a pad level dielectric layer **320** on the backside insulating layer **306**. The pad level dielectric layer **320** includes a planarizable dielectric material such as silicon oxide. The pad level dielectric layer **320** can be deposited, for example, by chemical vapor deposition or spin-coating, and can be planarized such that the top surface (in an upside down position) of the pad level dielectric layer **320** is coplanar with the top surface of the first integrated through-substrate via and pad structures (**318**, **316**).

A first back-side handle substrate **1100'** can be attached to the physically exposed surface of the pad level dielectric layer **320** and/or to the physically exposed surfaces of the first integrated through-substrate via and pad structures (**318**, **316**) employing an adhesive material layer or by any other suitable bonding methods. The first front side handle substrate **1100**, can be detached from the front side surface of the first semiconductor chip **1000**. A suitable surface clean process can be performed to remove residual adhesive materials from the top surface of the additional interconnect level dielectric layers **290**. In this case, the front side bonding pad structures **298** can be physically exposed on the front side of the first semiconductor chip **1000**.

Generally, a first semiconductor chip **1000** is provided, which comprises a first semiconductor substrate **8**, first semiconductor devices **600** located over a front side surface **8**F of the first semiconductor substrate **8**, and first integrated through-substrate via and pad structures (**318**, **316**) that includes a respective first through-substrate via structure **316** and a respective backside bonding pad structure **318** and comprises a first metallic material. The first integrated through-substrate via and pad structures (**318**, **316**) vertically extend from the front side surface **8**F of the first semiconductor substrate **8** to a backside surface **8**B of the first semiconductor substrate **8** and are electrically isolated from the first semiconductor substrate **8** by a respective tubular insulating spacer **302** and by a backside insulating layer **306** contacting the backside surface of the first semiconductor substrate **8**. Each of the first integrated through-substrate via and pad structures (**318**, **316**) has a greater lateral dimension within a horizontal plane including the front side surface of the first semiconductor substrate **8** than within a horizontal plane including the backside surface of the first semiconductor substrate **8**. In one embodiment, the first semiconductor devices **600** comprise a three-dimensional memory device including an alternating stack of insulating layers (**132**, **232**) and electrically conductive layers (**146**, **246**) and a two-dimensional array of memory stack structures **58** including a respective vertical stack of memory elements located at levels of the electrically conductive layers (**146**, **246**). First bonding pad structures (**318** or **298**) are electrically connected to a respective one of the first semiconductor devices.

Referring to FIG. **13**, a second exemplary structure according to an embodiment of the present disclosure is illustrated. The second exemplary structure includes through-substrate via structures in a substrate supporting peripheral devices. The second exemplary structure can be provided employing the processing steps of FIGS. **1**A and **1**B, **2**, and **3**. The second exemplary structure comprises a second semiconductor substrate **408** (e.g., silicon wafer) including a second substrate semiconductor layer **409** (e.g., doped well and/or epitaxial silicon layer), insulating material liners **402'**, and sacrificial pillar structures **403**. The insulating material liners **402'** in the second exemplary structure can have the same compositional and structural characteristics as the insulating material liners **302'** in the first exemplary structure. The sacrificial pillar structures **403** in the second exemplary structure can have the same compositional and structural characteristics as the sacrificial pillar structures **303** in the first exemplary structure.

Semiconductor devices, which are herein referred to as second semiconductor devices **700**, are formed on the second substrate semiconductor **409**. In one embodiment, the second semiconductor devices comprise peripheral devices that provide control signals for operation of the two-dimensional array of memory stack structures in the first semiconductor chip **1000**.

In an illustrative example, shallow trench isolation structures **720** can be formed in an upper portion of the second substrate semiconductor layer **409** to provide electrical isolation among the semiconductor devices. The semiconductor devices **700** can include, for example, field effect transistors including respective transistor active regions **742** (i.e., source regions and drain regions), gate structures **750**, and channel regions underlying the gate structures **750** and located between a respective pair of transistor active regions **742**. Only a subset of the transistor active regions **742** are illustrated for clarity. The field effect transistors may be arranged in a CMOS configuration. Each gate structure **750** can include, for example, a gate dielectric **752**, a gate electrode **754**, a dielectric gate spacer **756** and a gate cap dielectric **758**. The semiconductor devices can include any semiconductor circuitry to support operation of a memory

structure to be subsequently formed, which is typically referred to as a driver circuitry, which is also known as peripheral circuitry. As used herein, a peripheral circuitry refers to any, each, or all, of word line decoder circuitry, word line switching circuitry, bit line decoder circuitry, bit line sensing and/or switching circuitry, power supply/distribution circuitry, data buffer and/or latch, or any other semiconductor circuitry that can be implemented outside a memory array structure for a memory device. For example, the semiconductor devices can include word line switching devices for electrically biasing word lines of three-dimensional memory structures to be subsequently formed.

Dielectric material layers **760** are formed over the semiconductor devices. The dielectric material layers **760** constitute a dielectric layer stack embedding metal interconnect structures **780**. The dielectric material layers **760** can include, for example, a dielectric liner **762** such as a silicon liner that blocks diffusion of mobile ions and/or apply appropriate stress to underlying structures, interconnect level dielectric layers **764** that overlies the dielectric liner **762**, and a passivation dielectric layer **766** (such as a silicon nitride layer) that functions as a diffusion barrier layer and overlies the interconnect level dielectric layer **764**. Each dielectric material layer among the interconnect level dielectric layers **764** may include any of doped silicate glass, undoped silicate glass, organosilicate glass, silicon nitride, silicon oxynitride, and dielectric metal oxides (such as aluminum oxide). In one embodiment, each of the interconnect level dielectric layers **764** can comprise, or consist essentially of, dielectric material layers having dielectric constants that do not exceed the dielectric constant of undoped silicate glass (silicon oxide) of 3.9. The metal interconnect structures **780** can include various device contact via structures **782**, intermediate metal line structures (**784**, **785**), intermediate metal via structures **786**, and topmost metal line structures **788**.

A bonding pad level dielectric layer **490** overlies the dielectric material layers **760**. Front side bonding pad structures **498** can be formed through the bonding pad level dielectric layer **490** and the passivation dielectric layer **766** directly on a respective one of the topmost metal line structures **788**. In one embodiment, the front side bonding pad structures **498** can include, and/or consist essentially of, copper. A second semiconductor chip **4000** is provided at this processing step. The second semiconductor chip **4000** can be formed as a die on the second semiconductor substrate **408** as part of a two-dimensional array of dies. Alternatively, the second semiconductor chip **4000** can be diced from the second semiconductor substrate **408** as a singulated semiconductor chip.

Referring to FIG. **14**, a second front side handle substrate **1400** can be attached to the front side of the second semiconductor chip **4000**. The second front side handle substrate **1400** can have a thickness in a range from 0.5 mm to 3 mm, although lesser and greater thicknesses can also be employed. The second front side handle substrate **1400** can include any rigid material, which may be an insulating material, a semiconducting material, or a conductive material. The second front side handle substrate **1400** can be attached to the second semiconductor chip **4000** by an adhesive layer (not expressly shown) or by any other suitable temporary bonding material.

Referring to FIG. **15**, the processing steps of FIGS. **7-11** can be sequentially performed to thin the second semiconductor substrate **408** and to form tubular insulating spacers **302**, to remove the sacrificial pillar structures **403** selective to the materials of the tubular insulating spacers **302** and the second substrate semiconductor layer **409**, to form a backside insulating layer **406** (which can be compositionally and structurally the same as the backside insulating layer **306** in the first exemplary structure), and to form second through-substrate via structures **416** or second integrated through-substrate via and pad structures (**418**, **416**).

Each second integrated through-substrate via and pad structure (**418**, **416**) includes a second bonding pad structure **418** and a second through-substrate via structure **416**. The first bonding pad structures **418** protrude from the horizontal plane including the top surface of the backside insulating layer **406**. The second through-substrate via structure **416** includes vertically extending portions of the metallic liner and the metal fill material layer that are embedded within the second semiconductor substrate **408** and the backside insulating layer **406**. The second bonding pad structure **418**, which are also referred to as backside bonding pad structures **418**, can be physically exposed on the backside of the second semiconductor chip **1400**. Each second integrated through-substrate via and pad structure (**418**, **416**) includes a patterned portion of the metallic liner, which is herein referred to as a metallic liner **407**, and a patterned portion of a metal fill material layer and any optional deposited bonding pad metal, which are herein referred to as a metallic fill material portion **410**.

Referring to FIG. **16**A, an optional derivative of the second exemplary structure is illustrated, which can be derived from the second exemplary structure of FIG. **15** by forming a pad level dielectric layer **420** on the backside insulating layer **406**. The pad level dielectric layer **420** includes a planarizable dielectric material such as silicon oxide. The pad level dielectric layer **420** can be deposited, for example, by chemical vapor deposition or spin-coating, and can be planarized such that the top surface (in an upside down state) of the pad level dielectric layer **420** is coplanar with the top surface of the second integrated through-substrate via and pad structures (**418**, **416**). FIG. **16**B illustrates a second semiconductor chip **4000'** of an alternative embodiment, which differs from the second semiconductor chip **4000** shown in FIGS. **13** to **16**A in that the second semiconductor chip **4000'** of this alternative embodiment lacks the second integrated through-substrate via and pad structure (**418**, **416**). In other words, the second semiconductor chip **4000'** containing the CMOS peripheral circuits (i.e., second semiconductor devices **700**) lacks the second through-substrate via structures **416**. The second semiconductor chip **4000'** can be used as the bottom most or top most chip in the bonded chip assembly structure.

A second back-side handle substrate **1400'** can be attached to the physically exposed surface of the pad level dielectric layer **420** and/or to the physically exposed surfaces of the second integrated through-substrate via and pad structures (**418**, **416**) employing an adhesive material layer or by any other suitable bonding methods. The second front side handle substrate **1400** can be detached from the front side surface of the second semiconductor chip (**4000**, **4000'**). A suitable surface clean process can be performed to remove residual adhesive materials from the top surface of the bonding pad level dielectric layer **490**. In this case, the front side bonding pad structures **498** can be physically exposed on the front side of the second semiconductor chip (**4000**, **4000'**).

Generally, a second semiconductor chip (**4000**, **4000'**) comprising a second semiconductor substrate **408** is provided. The second semiconductor devices **700** are located over a front side surface of the second semiconductor substrate **408**, and second bonding pad structures (**418** or

498) are electrically connected to a respective one of the second semiconductor devices 700.

FIGS. 17A-17C illustrate sequential vertical cross-sectional views during formation of a first exemplary chip assembly structure according to an embodiment of the present disclosure. Referring to FIG. 17A, a first semiconductor chip 1000 attached to a first handle substrate (1100 or 1100') and a second semiconductor chip (4000, 4000') attached to a second handle substrate (1400' or 1400) are provided. In case a first front side handle substrate 1100 is employed, backside bonding pad structures 318 are physically exposed on the back side of the first semiconductor chip 1000 that faces the second semiconductor chip (4000, 4000'). In case a first back-side handle substrate 1100' is employed, front side bonding pad structures 298 are physically exposed on the front side of the first semiconductor chip 1000 that faces the second semiconductor chip (4000, 4000'). In case a second back-side handle substrate 1400' is employed, front side bonding pad structures 498 are physically exposed on the front side of the second semiconductor chip 4000 that faces the first semiconductor chip 1000. In case a second front side handle substrate 1400 is employed, backside bonding pad structures 418 are physically exposed on the back side of the first semiconductor chip 1000 that faces the second semiconductor chip 4000. The first semiconductor chip 1000 can include first bonding pad structures (298, 318), and the second semiconductor chip (4000, 4000') can include second bonding pad structures (498, 418). If both first and second bonding pad structures are present, then the pattern of the first bonding pad structures (298, 318) can be a mirror image of the pattern of the second bonding pad structures (498, 418).

Referring to FIG. 17B, the first semiconductor chip 1000 and the second semiconductor chip (4000, 4000') can be bonded by aligning the first bonding pad structures (318 or 298) with a respective one of the second bonding pad structures (498 or 418), and by inducing surface activated bonding between the first and second bonding pad structures. For example, the first bonding pad structures (318 or 298) and the second bonding pad structures (498 or 418) can comprise, or consist essentially of, copper, and the surface activated bonding can be induced by annealing the first exemplary chip assembly structure while the first bonding pad structures (318 or 298) and the second bonding pad structures (498 or 418) are in physical contact.

Referring to FIG. 17C, the first handle substrate (1100 or 1100') can be detached from the first semiconductor chip 1000, and the second handle substrate (1400' or 1400) can be detached from the second semiconductor chip (4000, 4000'). Various methods for deactivating the adhesive force between the handle substrates and the semiconductor chips can be employed. Methods for deactivating the adhesive force include, but are not limited to, ultraviolet radiation, chemical etching, thermal treatment or mechanical separation. Suitable surface cleaning processes can be performed to clean the first semiconductor chip 1000 and the second semiconductor chip (4000, 4000') as needed. In one embodiment, the second semiconductor devices in the second semiconductor chip (4000, 4000') can comprise peripheral (e.g., driver circuit) devices that provide control signals for operation of the two-dimensional array of memory stack structures in the first semiconductor chip 1000.

Referring to FIG. 18A, an embodiment of the first exemplary chip assembly structure is illustrated after bonding the first semiconductor chip 1000 with the second semiconductor chip 4000. In this embodiment, the backside bonding pad structures 318 of the first semiconductor chip 1000 are bonded to the front side bonding pad structures 498 of the first semiconductor chip 4000 through copper-to-copper bonding.

FIG. 18B illustrates an alternative embodiment of the first alternative exemplary chip assembly structure after bonding the first semiconductor chip 1000 with the second semiconductor chip 4000' shown in FIG. 16B. If the second semiconductor chip 4000' of the alternative embodiment is used, then the second back-side handle substrate 1400' can be omitted.

FIGS. 19A-19L illustrate sequential vertical cross-sectional views during formation of a second exemplary chip assembly structure according to an embodiment of the present disclosure.

Referring to FIG. 19A, two instances of the first semiconductor chip 1000 illustrated in FIG. 11 or FIG. 12 can be provided, which are herein referred to as a first semiconductor chip 1001 and a second semiconductor chip 1002, respectively, hereafter. The first semiconductor chip 1001 can be provided on a backside (i.e., bottom side) of a front side handle substrate 1100, and the second semiconductor chip 1002 can be provided on a front side (i.e., top side) of a backside handle substrate 1100'. The first semiconductor chip 1001 can include backside bonding pad structures 318 as first bonding pad structures, and the second semiconductor chip 1002 can include front side bonding pad structures 298 as second bonding pad structures. The pattern of the first bonding pad structures 318 can be a mirror image of the pattern of the second bonding pad structures 298.

Referring to FIG. 19B, the first semiconductor chip 1001 and the second semiconductor chip 1002 can be bonded by aligning the first bonding pad structures 318 with a respective one of the second bonding pad structures 298, and by inducing surface activated bonding between the first and second bonding pad structures. For example, the first bonding pad structures 318 and the second bonding pad structures 298 can comprise, or consist essentially of, copper, and the surface activated bonding can be induced by annealing the first exemplary chip assembly structure while the first bonding pad structures 318 and the second bonding pad structures 298 are in physical contact.

Referring to FIG. 19C, one of the front side handle substrate 1100 and the backside handle substrate 1100' can be detached. For example, the backside handle substrate 1100' can be detached from the second semiconductor chip 1002. Various methods for deactivating the adhesive force between the backside handle substrate 1100' and the second semiconductor chip 1002 can be employed. Suitable surface cleaning processes can be performed to clean the bottom surface of the second semiconductor chip 1002 as needed.

Referring to FIG. 19D, a third instance of the first semiconductor chip 1000 described in FIG. 11 or FIG. 12 is provided on a front side (i.e., top side) of a backside handle substrate 1100', which is here in referred to as a third semiconductor chip 1003. The third semiconductor chip 1003 comprises a third semiconductor substrate (which can be structurally and compositionally the same as the first semiconductor substrate 8), third semiconductor devices 600 (which may be three-dimensional memory devices) located over a front side surface of the third semiconductor substrate, and third-chip bonding pad structures (which can be structurally and compositionally the same as the front side bonding pad structures 298) located on a front side of the third semiconductor chip 1003 and electrically connected to a respective one of the third semiconductor devices. The bonded stack of the first semiconductor chip 1001 and the second semiconductor chip 1002 can include backside bond-

ing pad structures **318** as first bonding pad structures, and the third semiconductor chip **1003** can include front side bonding pad structures **298** as second bonding pad structures. The pattern of the first bonding pad structures **318** can be a mirror image of the pattern of the second bonding pad structures **298**.

Referring to FIG. **19**E, the second semiconductor chip **1002** and the third semiconductor chip **1003** can be bonded by aligning the first bonding pad structures **318** of the second semiconductor chip **1002** with a respective one of the second bonding pad structures **298** of the third semiconductor chip **1003**, and by inducing surface activated bonding between the first and second bonding pad structures.

Referring to FIG. **19**F, one of the front side handle substrate **1100** and the backside handle substrate **1100'** can be detached. For example, the backside handle substrate **1100'** can be detached from the third semiconductor chip **1003**. Various methods for deactivating the adhesive force between the backside handle substrate **1100'** and the third semiconductor chip **1003** can be employed. Suitable surface cleaning processes can be performed to clean the bottom surface of the third semiconductor chip **1003** as needed.

Referring to FIG. **19**G, a fourth instance of the first semiconductor chip **1000** described in FIG. **11** or FIG. **12** is provided on a front side (i.e., top side) of a backside handle substrate **1100'**, which is here in referred to as a fourth semiconductor chip **1004**.

Referring to FIG. **19**H, the processing steps of FIG. **19**E can be performed mutatis mutandis to bond the fourth semiconductor chip **1004** to the chip assembly structure including the first, second, and third semiconductor chips (**1001**, **1002**, **1003**).

Referring to FIG. **19**I, the processing steps of FIG. **19**F can be performed mutatis mutandis to detach the backside handle substrate **1100'**.

Referring to FIG. **19**J, a fifth instance of the first semiconductor chip **1000** described in FIG. **11** or FIG. **12** is provided on a front side (i.e., top side) of a backside handle substrate **1100'**, which is here in referred to as a fifth semiconductor chip **1005**.

Referring to FIG. **19**K, the processing steps of FIG. **19**E can be performed mutatis mutandis to bond the fifth semiconductor chip **1005** to the chip assembly structure including the first, second, third, and fourth semiconductor chips (**1001**, **1002**, **1003**, **1004**).

Referring to FIG. **19**L, the processing steps of FIG. **19**F can be performed mutatis mutandis to detach the backside handle substrate **1100'**.

The set of processing steps of FIGS. **19**D-**19**F can be repeated mutatis mutandis as many times as needed to provide a chip assembly structure that includes N bonded semiconductor chips **1000**, in which N is an integer greater than 1, such as 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, or a greater integer.

In one embodiment, the first semiconductor devices in the first semiconductor chip **1000** can include a three-dimensional memory device including an alternating stack of insulating layers (**132**, **232**) and electrically conductive layers (**146**, **246**) and a two-dimensional array of memory stack structures **58** including a respective vertical stack of memory elements located at levels of the electrically conductive layers (**146**, **246**), and the second semiconductor devices in the second semiconductor chip **1000** can comprise an additional three-dimensional memory device including an additional alternating stack of additional insulating layers (**132**, **232**) and additional electrically conductive layers (**146**, **246**) and an additional two-dimensional array of memory stack structures **58** including a respective vertical stack of memory elements located at levels of the additional electrically conductive layers. At least one additional semiconductor chip **1000** that is identical to the first and/or second semiconductor chips **1000** can be bonded to the bottom or to the top of the stack of the first and second semiconductor chips **1000**. After stacking (N−1) semiconductor chips **1000**, in which N is an integer greater than 2, an N-th semiconductor chip that is the same as the second semiconductor chip **4000** illustrated in FIG. **15**, **16**A or **16**B can be bonded to the stack of the (N−1) semiconductor chips **1000**. The N-th semiconductor chip includes N-th semiconductor devices. In this case, the N-th semiconductor devices in the N-th semiconductor chip can comprise peripheral devices that provide control signals for operation of the two-dimensional array of memory stack structures in the first through (N−1)-th semiconductor chip.

Referring to FIGS. **20**A-**20**C, a third chip assembly structure is illustrated during a fabrication process. In this case, the integer N is 4. The third chip assembly structure of FIG. **20** can be derived from the chip assembly structure of FIG. **19**F. A second semiconductor chip **4000** illustrated in FIG. **16**A or **16**B can be employed as an N-th semiconductor chip **4000** (such as a fourth semiconductor chip) at the processing steps of FIG. **20**A. For example, the (N−1)-th semiconductor chip **1003** (which is the third semiconductor chip for the case of N=4) includes backside bonding pad structures **318** as first bonding pad structures, and the N-th semiconductor chip **4000** includes front side bonding pad structures **498** as second bonding pad structures. The pattern of the first bonding pad structures **318** can be a mirror image of the pattern of the second bonding pad structures **498**.

Referring to FIG. **20**B, the (N−1)-th semiconductor chip **1003** and the N-th semiconductor chip **4000** can be bonded by aligning the first bonding pad structures **318** with a respective one of the second bonding pad structures **498**, and by inducing surface activated bonding between the first and second bonding pad structures. For example, the first bonding pad structures **318** and the second bonding pad structures **498** can comprise, or consist essentially of, copper, and the surface activated bonding can be induced by annealing the first exemplary chip assembly structure while the first bonding pad structures **318** and the second bonding pad structures **498** are in physical contact

Referring to FIG. **20**C, the front side handle substrate **1100** and the backside handle substrate **1100'** can be detached. Various methods for deactivating the adhesive force between the backside handle substrate **1100'** and the N-th semiconductor chip **4000**, and for deactivating the adhesive force between the front side handle substrate **1100** and the (N−1)-th semiconductor chip **1103** can be employed. Suitable surface cleaning processes can be performed subsequently.

Referring to FIG. **21**, a fourth chip assembly structure is illustrated, which can be derived from the third chip assembly structure by attaching a topmost semiconductor chip **1001** or a bottommost semiconductor chip **4000** to an interposer **800**. For example, copper bonding pads **520** can be provided on one side of the interposer with a mirror image of the pattern of the bonding pad structures (such as the front side bonding pads **298** of the topmost semiconductor chip **1001**). Copper-to-copper bonding can be employed to form a chip assembly structure in which multiple instances of the first semiconductor chip **1000** as provided at the processing steps of FIG. **11** or FIG. **12**, and an instance of the second semiconductor chip (**4000**, **4000'**)

as provided at the processing steps of FIG. **15**, **16**A or **16**B are bonded to the interposer **800**.

Subsequently, a packaging substrate **900** can be provided, on which the interposer **800** can be mounted. In one embodiment, electrical connections between the packaging substrate **900** and the interposer **800** can be provided by wire bonding. Interposer-side wire bonding pads **818** can be provided on the interposer **800**, and packaging-substrate-side wire bonding pads **918** can be provided on the packaging substrate **900**. Interconnection wires **850** can be employed to provide electrical connection between pairs of an interposer-side wire bonding pad **818** and a packaging-substrate-side wire bonding pad **918**. An array of solder balls **920** may be employed to attach the packaging substrate **900** to another electronic component such as a circuit board.

FIGS. **22**A-**22**C illustrate sequential vertical cross-sectional views during formation of an alternative first integrated through-substrate via and pad structures according to an alternative embodiment of the present disclosure. The alternative structure shown in FIG. **22**A can be derived from the structure shown in FIG. **9** by recessing the backside insulating layer **306** away from the through-substrate cavities **305**. For example, a photoresist layer (not shown) can be deposited over the backside insulating layer **306** and into the through-substrate cavities **305**. The photoresist layer is then patterned to expose regions of the backside insulating layer **306** that surround the through-substrate cavities **305**. The exposed regions of the backside insulating layer **306** are removed by etching, followed by removing the photoresist layer by ashing to form the alternative structure shown in FIG. **22**A.

Referring to FIG. **22**B, the metallic liner **308**L and a metal fill material layer **310**L can be sequentially deposited in the through-substrate cavities **305** and over the remaining portions of the backside insulating layer **306**, used the process described above with respect to FIG. **10**.

Referring to FIG. **22**C, the metallic liner **308**L and the metal fill material layer **310**L can be recessed by chemical mechanical planarization using the remaining portions of the backside insulating layer **306** as a polish step. The polishing step results in the first integrated through-substrate via and pad structures (**316**, **318**) being embedded in the backside insulating layer **306**, and having an exposed back side surface that is co-planar with the back side surface of the backside insulating layer **306**. The process then proceeds as described above with respect to any of the FIGS. **17**A to **21**.

Referring to all drawings and according to various embodiments of the present disclosure, a chip assembly structure is provided, which comprises: a first semiconductor chip (**1000**, **1003**) comprising a first semiconductor substrate **8**, first semiconductor devices located over a front side surface of the first semiconductor substrate **8**, and first integrated through-substrate via and pad structures (**318**, **316**) including a respective first through-substrate via structure **316** and a respective first bonding pad structure **318** and comprising a first metallic material, wherein the first integrated through-substrate via and pad structures (**318**, **316**) vertically extend from the front side surface of the first semiconductor substrate **8** to a backside surface of the first semiconductor substrate **8** and are electrically isolated from the first semiconductor substrate **8** by a respective tubular insulating spacer **302** and by a backside insulating layer **306** contacting the backside surface of the first semiconductor substrate **8**, wherein each of the first integrated through-substrate via and pad structures (**318**, **316**) has a greater lateral dimension within a horizontal plane including the front side surface of the first semiconductor substrate **8** than within a horizontal plane including the backside surface of the first semiconductor substrate **8**; and a second semiconductor chip **4000** comprising a second semiconductor substrate **408**, second semiconductor devices **710** located over a front side surface of the second semiconductor substrate **408**, and second bonding pad structures {(**418**, **416**), **498**} electrically connected to a respective one of the second semiconductor devices **710**, wherein the first bonding pad structures **318** are directly bonded to a respective one of the second bonding pad structures {(**418**, **416**), **498**} by surface activated bonding, which can be a metal-to-metal bonding, such as copper-to-copper bonding.

In one embodiment, each first through-substrate via structure **316** of the first integrated through-substrate via and pad structures (**318**, **316**) has a tapered straight sidewall that continuously extends between the front side surface of the first semiconductor substrate **8** to the backside surface of the first semiconductor substrate **8**.

In one embodiment, the tubular insulating spacers **302** comprise thermal silicon oxide that is substantially free of carbon and hydrogen, and the backside insulating layer **306** comprises chemical vapor deposition silicon oxide that includes carbon and hydrogen at atomic concentrations greater than 1 part per million.

In one embodiment, each of the first integrated through-substrate via and pad structures (**318**, **316**) includes: a metallic liner **308** contacting an inner sidewall of a respective tubular insulating spacer **302**; and a metallic fill material portion **310** comprising copper and including a via metal portion embedded in the metallic liner **308** and a pad metal portion having a greater lateral extent than the via metal portion.

In one embodiment, the first semiconductor devices comprise a including an alternating stack of insulating layers (**132**, **232**) and electrically conductive layers (**146**, **246**) and a two-dimensional array of memory stack structures **58** including a respective vertical stack of memory elements located at levels of the electrically conductive layers (**146**, **246**), and the second semiconductor devices **710** in the second semiconductor chip **4000** comprise peripheral devices that provide control signals for operation of three-dimensional memory device of the first semiconductor chip (**1000**, **1003**).

In some embodiments, the chip assembly structure can further comprise a third semiconductor chip **1002** comprising a third semiconductor substrate **8**, third semiconductor devices located over a front side surface of the third semiconductor substrate **8**, and third-chip bonding pad structures **318** electrically connected to a respective one of the third semiconductor devices, wherein the first semiconductor chip **1002** further comprises front side bonding pad structures **298** electrically connected to the first integrated through-substrate via and pad structures (**318**, **316**) and bonded to a respective one of the third-chip bonding pad structures **318** by surface activated bonding. As noted above, ordinals merely identify multiple instances of similar elements, and different ordinals may be employed across the specification and the claims of the instant disclosure.

In one embodiment, the third semiconductor devices **1002** comprise an additional three-dimensional memory device including an additional alternating stack of additional insulating layers (**132**, **232**) and additional electrically conductive layers (**146**, **246**) and an additional two-dimensional array of memory stack structures **58** including a respective vertical stack of memory elements located at levels of the additional electrically conductive layers (**146**, **246**); and the second semiconductor devices **710** in the second semicon-

ductor chip **4000** comprise additional peripheral devices that provide control signals for operation of the additional three-dimensional memory device of the third semiconductor chip **1002**.

In some embodiments, the first semiconductor chip (**1000**, **1003**) further comprises sets of metal interconnect structures (**588**, **94**, **296**) located between the first semiconductor substrate **8** and the front side bonding pad structures **298**, wherein each set of metal interconnect structures (**588**, **94**, **296**) provide an electrically conductive path between a respective pair of a front side bonding pad structures **298** and a first integrated through-substrate via and pad structure (**318**, **316**), and at least one set of metal interconnect structures (**588**, **94**, **296**) extends through the alternating stack of insulating layers (**132**, **232**) and electrically conductive layers (**146**, **246**).

In some embodiment, a chip assembly structure is provided, which comprises: a first semiconductor chip **1003** comprising a first semiconductor substrate **8**, first semiconductor devices located over a front side surface of the first semiconductor substrate **8**, first through-substrate via structures **316** vertically extending from the front side surface of the first semiconductor substrate **8** to a backside surface of the first semiconductor substrate **8** and are electrically isolated from the first semiconductor substrate **8** by a respective tubular insulating spacer **302** and by a backside insulating layer **306** contacting the backside surface of the first semiconductor substrate **8**, and first bonding pad structures **318** located on the first through-substrate via structures **316** at a backside of the first semiconductor substrate **8**, wherein the first semiconductor devices comprise a three-dimensional memory device including an alternating stack of insulating layers (**132**, **232**) and electrically conductive layers (**146**, **246**) and a two-dimensional array of memory stack structures **58** including a respective vertical stack of memory elements located at levels of the electrically conductive layers (**146**, **246**); a second semiconductor chip **4000** comprising a second semiconductor substrate **408**, second semiconductor devices **710** located over a front side surface of the second semiconductor substrate **408**, and second bonding pad structures (**418** or **498**) electrically connected to a respective one of the second semiconductor devices **710**, wherein the first bonding pad structures **318** are directly bonded to a respective one of the second bonding pad structures (**418** or **498**), such as by surface activated bonding, wherein the second semiconductor devices **710** in the second semiconductor chip **4000** comprise peripheral devices that provide control signals for operation of the two-dimensional array of memory stack structures **58** in the first semiconductor chip **1003**; and a third semiconductor chip **1002** comprising a third semiconductor substrate **8**, third semiconductor devices located over a front side surface of the third semiconductor substrate **8**, and third-chip bonding pad structures (**318** or **298**) electrically connected to a respective one of the third semiconductor devices, wherein the first semiconductor chip **1003** further comprises front side bonding pad structures **298** electrically connected to the first bonding pad structures **318** and directly bonded to a respective one of the third-chip bonding pad structures (**318** or **298**), such as by surface activated bonding.

In one embodiment, the third semiconductor devices comprise an additional three-dimensional memory device including an additional alternating stack of additional insulating layers (**132**, **232**) and additional electrically conductive layers (**146**, **246**) and an additional two-dimensional array of memory stack structures **58** including a respective vertical stack of memory elements located at levels of the additional electrically conductive layers (**146**, **246**), and the second semiconductor devices **710** of the second semiconductor chip **4000** comprise additional peripheral devices that provide control signals for operation of the additional two-dimensional array of memory stack structures **58** in the third semiconductor chip **1002**.

In one embodiment, the first semiconductor chip **1003** further comprises sets of metal interconnect structures (**588**, **94**, **296**) located between the first semiconductor substrate **8** and the front side bonding pad structures **298**, wherein each set of metal interconnect structures (**588**, **94**, **296**) provide an electrically conductive path between a respective pair of a front side bonding pad structure **298** and a first bonding pad structure **318**, and at least one set of metal interconnect structures (**588**, **94**, **296**) extends through the alternating stack of insulating layers (**132**, **232**) and electrically conductive layers (**146**, **246**).

In one embodiment, the first through-substrate via structures **316** and the first bonding pad structures **318** are portions of first integrated through-substrate via and pad structures (**318**, **316**); each of the first through-substrate via structures **316** has a greater lateral dimension within a horizontal plane including the front side surface of the first semiconductor substrate **8** than within a horizontal plane including the backside surface of the first semiconductor substrate **8**; the tubular insulating spacers **302** comprise thermal silicon oxide that is substantially free of carbon and hydrogen; the backside insulating layer **306** comprises chemical vapor deposition silicon oxide that includes carbon and hydrogen at atomic concentrations greater than 1 part per million; and each first through-substrate via structure **316** of the first integrated through-substrate via and pad structures (**318**, **316**) has a tapered straight sidewall that continuously extends between the front side surface of the first semiconductor substrate **8** to the backside surface of the first semiconductor substrate **8**.

According to an aspect of the present disclosure, the backside insulating layers (**306**, **406**) are formed prior to formation of semiconductor devices on substrate semiconductor layers (**9**, **409**). Since there is no thermal budget relating to any semiconductor device at this processing step, thermal silicon oxide formed by thermal oxidation or a chemical vapor deposition silicon oxide densified by a high temperature anneal, and thus, having a very low hydrogen content, can be employed for the backside insulating layers (**306**, **406**). Thus, a high quality silicon oxide material having high breakdown electrical field strength can be employed for the backside insulating layers (**306**, **406**) of the devices of the present disclosure.

According to another aspect of the present disclosure, step coverage of the sacrificial material layer **303**L is not important, and conformal or non-conformal deposition processes can be employed to deposit the sacrificial material layer. If voids are formed within the volume of the via openings **301**, such voids may be employed to accelerate access of the etchant during removal of the sacrificial pillar structures (**303**, **403**). Devices and metal interconnect structures are formed while the sacrificial pillar structures are present, and some metal interconnect structures (**588**, **782**) are formed directly on the sacrificial pillar structures (**303**, **403**).

In case copper is deposited to form the integrated through-substrate via and pad structure {(**318**, **316**), (**418**, **416**)}, copper is not deposited until the first semiconductor substrate is thinned. Thus, substrate thinning-induced copper contamination cab be avoided.

The first semiconductor chips **1000** can be formed without CMOS devices, or only with CMOS devices that are not

critically affected by high temperature anneal processes that are employed to form a three-dimensional array of memory cells. The second semiconductor chip **4000** can provide high performance CMOS devices for peripheral circuitry that controls the operation of the three-dimensional memory device of the first semiconductor chips **4000**. Metal-to-metal bonding, such as copper-to-copper bonding, can be employed to induce bonding, in which metal atoms (such as copper atoms) diffuse across the interface between opposing, and contacting, pairs of metal bonding pads (such as copper pads). Logic devices provided in a separate semiconductor chip, such as a second semiconductor chip **4000**, avoid performance degradation when logic devices are subjected to high temperature anneal processes during manufacturing of the three-dimensional memory devices.

The chip bonding method of the embodiments of the present disclosure provides additional non-limiting advantages. Multiple memory chips, such as multiple instances of the first semiconductor chip **1000** including a respective three-dimensional memory device, can be stacked to share a common logic control chip, such as a second semiconductor chip **4000**. Thus, the number of unit processes required to form a single memory chip can be reduced. Since the stacked chips (**1000**, **4000**) are bonded without gaps thereamongst, any increase in resistance and capacitance associated with bonding can be minimized.

Although the foregoing refers to particular preferred embodiments, it will be understood that the disclosure is not so limited. It will occur to those of ordinary skill in the art that various modifications may be made to the disclosed embodiments and that such modifications are intended to be within the scope of the disclosure. Compatibility is presumed among all embodiments that are not alternatives of one another. The word "comprise" or "include" contemplates all embodiments in which the word "consist essentially of" or the word "consists of" replaces the word "comprise" or "include," unless explicitly stated otherwise. Where an embodiment employing a particular structure and/or configuration is illustrated in the present disclosure, it is understood that the present disclosure may be practiced with any other compatible structures and/or configurations that are functionally equivalent provided that such substitutions are not explicitly forbidden or otherwise known to be impossible to one of ordinary skill in the art. All of the publications, patent applications and patents cited herein are incorporated herein by reference in their entirety.

What is claimed is:

1. A chip assembly structure comprising:

a first semiconductor chip comprising a first semiconductor substrate, first semiconductor devices located over a front side surface of the first semiconductor substrate, first through-substrate via structures vertically extending from the front side surface of the first semiconductor substrate to a backside surface of the first semiconductor substrate and are electrically isolated from the first semiconductor substrate by a respective tubular insulating spacer and by a backside insulating layer contacting the backside surface of the first semiconductor substrate, and first backside bonding pad structures located on the first through-substrate via structures at a backside of the first semiconductor substrate, wherein the first semiconductor devices comprise a three-dimensional memory device including an alternating stack of insulating layers and electrically conductive layers and a two-dimensional array of memory stack structures including a respective vertical stack of memory elements located at levels of the electrically conductive layers;

a second semiconductor chip comprising a second semiconductor substrate, second semiconductor devices located over a front side surface of the second semiconductor substrate, and second bonding pad structures electrically connected to a respective one of the second semiconductor devices, wherein the first backside bonding pad structures are directly bonded to a respective one of the second bonding pad structures, wherein the second semiconductor devices in the second semiconductor chip comprise peripheral devices that provide control signals for operation of the two-dimensional array of memory stack structures in the first semiconductor chip; and

a third semiconductor chip comprising a third semiconductor substrate, third semiconductor devices located over a front side surface of the third semiconductor substrate, and third-chip backside bonding pad structures electrically connected to a respective one of the third semiconductor devices, wherein the first semiconductor chip further comprises first front side bonding pad structures electrically connected to the first backside bonding pad structures and directly bonded to a respective one of the third-chip backside bonding pad structures;

wherein the first backside bonding pad structures are directly bonded to the respective one of the second bonding pad structures through copper-to-copper surface activated bonding.

2. The chip assembly structure of claim **1**, wherein the first front side bonding pad structures are directly bonded to the respective one of the third-chip backside bonding pad structures through copper-to-copper surface activated bonding.

3. The chip assembly structure of claim **1**, wherein:

the third semiconductor devices comprise an additional three-dimensional memory device including an additional alternating stack of additional insulating layers and additional electrically conductive layers and an additional two-dimensional array of memory stack structures including a respective vertical stack of memory elements located at levels of the additional electrically conductive layers; and

the second semiconductor devices of the second semiconductor chip comprise additional peripheral devices that provide control signals for operation of the additional two-dimensional array of memory stack structures in the third semiconductor chip.

4. The chip assembly structure of claim **3**, wherein:

the three-dimensional memory device in the first semiconductor chip comprises a first two-dimensional array of vertical NAND strings; and

the additional three-dimensional memory device in the third semiconductor chip comprises a second two-dimensional array of vertical NAND strings.

5. A chip assembly structure comprising:

a first semiconductor chip comprising a first semiconductor substrate, first semiconductor devices located over a front side surface of the first semiconductor substrate, first through-substrate via structures vertically extending from the front side surface of the first semiconductor substrate to a backside surface of the first semiconductor substrate and are electrically isolated from the first semiconductor substrate by a respective tubular insulating spacer and by a backside insulating layer

contacting the backside surface of the first semiconductor substrate, and first backside bonding pad structures located on the first through-substrate via structures at a backside of the first semiconductor substrate, wherein the first semiconductor devices comprise a three-dimensional memory device including an alternating stack of insulating layers and electrically conductive layers and a two-dimensional array of memory stack structures including a respective vertical stack of memory elements located at levels of the electrically conductive layers;

a second semiconductor chip comprising a second semiconductor substrate, second semiconductor devices located over a front side surface of the second semiconductor substrate, and second bonding pad structures electrically connected to a respective one of the second semiconductor devices, wherein the first backside bonding pad structures are directly bonded to a respective one of the second bonding pad structures, wherein the second semiconductor devices in the second semiconductor chip comprise peripheral devices that provide control signals for operation of the two-dimensional array of memory stack structures in the first semiconductor chip; and

a third semiconductor chip comprising a third semiconductor substrate, third semiconductor devices located over a front side surface of the third semiconductor substrate, and third-chip backside bonding pad structures electrically connected to a respective one of the third semiconductor devices, wherein the first semiconductor chip further comprises first front side bonding pad structures electrically connected to the first backside bonding pad structures and directly bonded to a respective one of the third-chip backside bonding pad structures;

wherein a subset of the first front side bonding pad structures is electrically shorted to a respective one of the first backside bonding pad structures by a respective one of the first through-substrate via structures and a respective set of metal interconnect structures.

6. The chip assembly structure of claim **5**, wherein each set of metal interconnect structures comprises:

a through-memory-level via structure that vertically extends through dielectric material portions located at a same level as the first semiconductor devices within the first semiconductor chip;

at least one interconnection metal pad located at a same level as metal lines located within the first semiconductor chip; and

a bonding pad connection via structure electrically shorted to the at least one interconnection metal pad and contacting a respective one of the first front side bonding pad structures.

7. A chip assembly structure comprising:

a first semiconductor chip comprising a first semiconductor substrate, first semiconductor devices located over a front side surface of the first semiconductor substrate, first through-substrate via structures vertically extending from the front side surface of the first semiconductor substrate to a backside surface of the first semiconductor substrate and are electrically isolated from the first semiconductor substrate by a respective tubular insulating spacer and by a backside insulating layer contacting the backside surface of the first semiconductor substrate, and first backside bonding pad structures located on the first through-substrate via structures at a backside of the first semiconductor substrate, wherein the first semiconductor devices comprise a three-dimensional memory device including an alternating stack of insulating layers and electrically conductive layers and a two-dimensional array of memory stack structures including a respective vertical stack of memory elements located at levels of the electrically conductive layers;

a second semiconductor chip comprising a second semiconductor substrate, second semiconductor devices located over a front side surface of the second semiconductor substrate, and second bonding pad structures electrically connected to a respective one of the second semiconductor devices, wherein the first backside bonding pad structures are directly bonded to a respective one of the second bonding pad structures, wherein the second semiconductor devices in the second semiconductor chip comprise peripheral devices that provide control signals for operation of the two-dimensional array of memory stack structures in the first semiconductor chip; and

a third semiconductor chip comprising a third semiconductor substrate, third semiconductor devices located over a front side surface of the third semiconductor substrate, and third-chip backside bonding pad structures electrically connected to a respective one of the third semiconductor devices, wherein the first semiconductor chip further comprises first front side bonding pad structures electrically connected to the first backside bonding pad structures and directly bonded to a respective one of the third-chip backside bonding pad structures;

wherein:

the first semiconductor chip further comprises sets of metal interconnect structures located between the first semiconductor substrate and the front side bonding pad structures, wherein each set of metal interconnect structures provide an electrically conductive path between a respective pair of a front side bonding pad structure and a first bonding pad structure, and at least one set of metal interconnect structures extends through the alternating stack of insulating layers and electrically conductive layers;

the first through-substrate via structures and the first backside bonding pad structures are portions of first integrated through-substrate via and pad structures;

each of the first through-substrate via structures has a greater lateral dimension within a horizontal plane including the front side surface of the first semiconductor substrate than within a horizontal plane including the backside surface of the first semiconductor substrate; and

the tubular insulating spacers comprise thermal silicon oxide that is substantially free of carbon and hydrogen, and the backside insulating layer comprises chemical vapor deposition silicon oxide that includes carbon and hydrogen at atomic concentrations greater than 1 part per million.

8. The chip assembly structure of claim **7**, wherein each first through-substrate via structure of the first integrated through-substrate via and pad structures has a tapered straight sidewall that continuously extends between the front side surface of the first semiconductor substrate to the backside surface of the first semiconductor substrate.

9. A method of forming a chip assembly structure comprising:

providing a first semiconductor chip comprising a first semiconductor substrate, first semiconductor devices

located over a front side surface of the first semiconductor substrate, first through-substrate via structures vertically extending from the front side surface of the first semiconductor substrate to a backside surface of the first semiconductor substrate and are electrically isolated from the first semiconductor substrate by a respective tubular insulating spacer and by a backside insulating layer contacting the backside surface of the first semiconductor substrate, first backside bonding pad structures located on the first through-substrate via structures at a backside of the first semiconductor substrate, and first front side bonding pad structures electrically connected to the first integrated through-substrate via and pad structures, wherein the first semiconductor devices comprise a three-dimensional memory device including an alternating stack of insulating layers and electrically conductive layers and a two-dimensional array of memory stack structures including a respective vertical stack of memory elements located at levels of the electrically conductive layers;

providing a second semiconductor chip comprising a second semiconductor substrate, second semiconductor devices located over a front side surface of the second semiconductor substrate, and second bonding pad structures electrically connected to a respective one of the second semiconductor devices, wherein the second semiconductor devices in the second semiconductor chip comprise peripheral devices that provide control signals for operation of the three-dimensional memory device of the first semiconductor chip;

bonding the first backside bonding pad structures to a respective one of the second bonding pad structures by surface activated bonding;

providing a third semiconductor chip comprising a third semiconductor substrate, third semiconductor devices located over a front side surface of the third semiconductor substrate, and third-chip bonding pad structures electrically connected to a respective one of the third semiconductor devices;

bonding the first front side bonding pad structures on the first semiconductor chip to a respective one of the third-chip bonding pad structures by surface activated bonding;

disposing the first backside bonding pad structures directly on the respective one of the second bonding pad structures; and

bonding the first backside bonding pad structures to the second bonding pad structures by copper direct bonding during an anneal process.

10. The method of claim **9**, further comprising:

disposing the first front side bonding pad structures directly on a respective one of the third-chip backside bonding pad structures; and

bonding the first front side bonding pad structures to the third-chip backside bonding pad structures by copper direct bonding.

11. The method of claim **9**, wherein:

the third semiconductor devices comprise an additional three-dimensional memory device including an additional alternating stack of additional insulating layers and additional electrically conductive layers and an additional two-dimensional array of memory stack structures including a respective vertical stack of memory elements located at levels of the additional electrically conductive layers; and

the second semiconductor devices of the second semiconductor chip comprise additional peripheral devices that provide control signals for operation of the additional two-dimensional array of memory stack structures in the third semiconductor chip.

12. The method of claim **11**, wherein:

the three-dimensional memory device in the first semiconductor chip comprises a first two-dimensional array of vertical NAND strings; and

the additional three-dimensional memory device in the third semiconductor chip comprises a second two-dimensional array of vertical NAND strings.

13. The method of claim **9**, wherein the first semiconductor chip further comprises sets of metal interconnect structures located between the first semiconductor substrate and the front side bonding pad structures, wherein each set of metal interconnect structures provide an electrically conductive path between a respective pair of a front side bonding pad structure and a first bonding pad structure, and at least one set of metal interconnect structures extends through the alternating stack of insulating layers and electrically conductive layers.

14. The method of claim **13**, wherein:

the first through-substrate via structures and the first backside bonding pad structures are portions of first integrated through-substrate via and pad structures; and

each of the first through-substrate via structures has a greater lateral dimension within a horizontal plane including the front side surface of the first semiconductor substrate than within a horizontal plane including the backside surface of the first semiconductor substrate.

15. A chip assembly structure comprising:

a first semiconductor chip comprising a first semiconductor substrate, first semiconductor devices located over a front side surface of the first semiconductor substrate, first through-substrate via structures vertically extending from the front side surface of the first semiconductor substrate to a backside surface of the first semiconductor substrate and are electrically isolated from the first semiconductor substrate by a respective tubular insulating spacer and by a backside insulating layer contacting the backside surface of the first semiconductor substrate, and first backside bonding pad structures located on the first through-substrate via structures at a backside of the first semiconductor substrate, wherein the first semiconductor devices comprise a three-dimensional memory device including an alternating stack of insulating layers and electrically conductive layers and a two-dimensional array of memory stack structures including a respective vertical stack of memory elements located at levels of the electrically conductive layers;

a second semiconductor chip comprising a second semiconductor substrate, second semiconductor devices located over a front side surface of the second semiconductor substrate, and second bonding pad structures electrically connected to a respective one of the second semiconductor devices, wherein the first backside bonding pad structures are directly bonded to a respective one of the second bonding pad structures, wherein the second semiconductor devices in the second semiconductor chip comprise peripheral devices that provide control signals for operation of the two-dimensional array of memory stack structures in the first semiconductor chip;

a third semiconductor chip comprising a third semiconductor substrate, third semiconductor devices located over a front side surface of the third semiconductor substrate, and third-chip backside bonding pad structures electrically connected to a respective one of the third semiconductor devices, wherein the first semiconductor chip further comprises first front side bonding pad structures electrically connected to the first backside bonding pad structures and directly bonded to a respective one of the third-chip backside bonding pad structures;

an interposer bonded to a topmost semiconductor chip by solder ball bonding to first bonding pads located on a top surface of the topmost semiconductor chip, wherein the topmost semiconductor chip is selected from the third semiconductor chip or a topmost one of at least one additional semiconductor chip bonded to the third semiconductor chip by copper-to-copper bonding; and

a packaging substrate attached to the interposer, wherein bonding pads of the packaging substrate are electrically connected to second bonding pads of the interposer.

16. A method of forming a chip assembly structure comprising:

providing a first semiconductor chip comprising a first semiconductor substrate, first semiconductor devices located over a front side surface of the first semiconductor substrate, first through-substrate via structures vertically extending from the front side surface of the first semiconductor substrate to a backside surface of the first semiconductor substrate and are electrically isolated from the first semiconductor substrate by a respective tubular insulating spacer and by a backside insulating layer contacting the backside surface of the first semiconductor substrate, first backside bonding pad structures located on the first through-substrate via structures at a backside of the first semiconductor substrate, and first front side bonding pad structures electrically connected to the first integrated through-substrate via and pad structures, wherein the first semiconductor devices comprise a three-dimensional memory device including an alternating stack of insulating layers and electrically conductive layers and a two-dimensional array of memory stack structures including a respective vertical stack of memory elements located at levels of the electrically conductive layers;

providing a second semiconductor chip comprising a second semiconductor substrate, second semiconductor devices located over a front side surface of the second semiconductor substrate, and second bonding pad structures electrically connected to a respective one of the second semiconductor devices, wherein the second semiconductor devices in the second semiconductor chip comprise peripheral devices that provide control signals for operation of the three-dimensional memory device of the first semiconductor chip;

bonding the first backside bonding pad structures to a respective one of the second bonding pad structures by surface activated bonding;

providing a third semiconductor chip comprising a third semiconductor substrate, third semiconductor devices located over a front side surface of the third semiconductor substrate, and third-chip bonding pad structures electrically connected to a respective one of the third semiconductor devices;

bonding the first front side bonding pad structures on the first semiconductor chip to a respective one of the third-chip bonding pad structures by surface activated bonding;

bonding an interposer by solder ball bonding to a topmost semiconductor chip in an assembly including the first, second, and third semiconductor chips, wherein the topmost semiconductor chip is selected from the third semiconductor chip or a topmost one of at least one additional semiconductor chip bonded to the third semiconductor chip by copper-to-copper bonding; and

attaching a packaging substrate to the interposer, wherein bonding pads of the packaging substrate are electrically connected to second bonding pads of the interposer by wire bonding.

* * * * *