



US009635540B2

(12) **United States Patent**
Mullen

(10) **Patent No.:** **US 9,635,540 B2**
(45) **Date of Patent:** **Apr. 25, 2017**

(54) **SYSTEMS AND METHODS FOR LOCATING CELLULAR PHONES AND SECURITY MEASURES FOR THE SAME**

(76) Inventor: **Jeffrey D. Mullen**, Scarsdale, NY (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

5,097,416 A	3/1992	Matthews
5,197,092 A	3/1993	Bamburak
5,305,201 A	4/1994	Matthews
5,327,144 A	7/1994	Stilp et al.
5,337,334 A	8/1994	Antero Alvesalo
5,341,410 A	8/1994	Aron et al.
5,384,824 A	1/1995	Alvesalo
5,388,147 A	2/1995	Grimes
5,442,805 A	8/1995	Sagars et al.

(Continued)

(21) Appl. No.: **10/400,296**

FOREIGN PATENT DOCUMENTS

(22) Filed: **Mar. 25, 2003**

WO	WO99/007170	2/1999
WO	WO99/009775	2/1999

(65) **Prior Publication Data**

US 2004/0203923 A1 Oct. 14, 2004

(Continued)

Related U.S. Application Data

OTHER PUBLICATIONS

(60) Provisional application No. 60/367,967, filed on Mar. 25, 2002.

ETSI TS 101 513, "Digital Cellular Telecommunications System (Phase 2): Location Services (LCS)," GSM 12.71, version 8.0.1. 1999.

(Continued)

(51) **Int. Cl.**

H04M 11/00 (2006.01)

H04W 8/14 (2009.01)

H04W 64/00 (2009.01)

H04W 8/16 (2009.01)

Primary Examiner — William Deane, Jr.

(52) **U.S. Cl.**

CPC **H04W 8/14** (2013.01); **H04W 64/00** (2013.01); **H04W 8/16** (2013.01)

(57) **ABSTRACT**

(58) **Field of Classification Search**

CPC **H04W 64/006**

USPC 455/404.1, 404.2, 410, 456.1–456.3, 457

See application file for complete search history.


Systems and methods for locating a cellular phone are provided. More particularly, systems and methods are provided that allow the location of a requested user's cellular phone to be provided to a requesting user's device (e.g., a second cellular phone) based on access rights defined by the requested user. Location descriptions may be provided at a multitude of levels. For example, if a cellular phone, or an identity associated to (e.g., logged into) a cellular phone, has been given access rights to a cell phone's exact location for an indefinite amount of time, that cell phone can receive, on command, the exact location of the approved cell phone. Other levels of location information that can be granted include, for example, proximities, states, and countries.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,654,879 A	3/1987	Goldman et al.
5,043,736 A	8/1991	Darnell et al.
5,086,390 A	2/1992	Matthews

35 Claims, 17 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

5,479,482	A	12/1995	Grimes	6,400,956	B1	6/2002	Richton	
5,502,757	A	3/1996	Bales et al.	6,408,186	B1	6/2002	Park et al.	
5,519,760	A	5/1996	Borkowski et al.	6,421,009	B2	7/2002	Suprunov	
5,537,460	A	7/1996	Holliday, Jr. et al.	6,438,376	B1	8/2002	Elliott et al.	
5,548,816	A	8/1996	DeVaney	6,438,381	B1	8/2002	Alberth, Jr. et al.	
5,551,058	A	8/1996	Hutcheson et al.	6,442,391	B1	8/2002	Johansson	
5,555,286	A	9/1996	Tendler	6,446,118	B1	9/2002	Gottlieb	
5,719,563	A	2/1998	Thompson	6,449,486	B1	9/2002	Rao	
5,767,788	A	6/1998	Ness	6,456,854	B1	9/2002	Chern	
5,778,315	A	7/1998	Proietti	D464,033	S	10/2002	Piano Poirier	
5,796,634	A	8/1998	Craport et al.	6,462,674	B2	10/2002	Ohmura	
5,805,999	A	9/1998	Inoue	6,466,788	B1 *	10/2002	Carlsson	455/435.2
5,815,538	A	9/1998	Grell et al.	6,532,360	B1	3/2003	Shaffer	
5,832,381	A	11/1998	Kauppi	6,564,064	B1	5/2003	Ciganer et al.	
5,847,976	A	12/1998	Lescourret	6,580,914	B1	6/2003	Smith	
5,875,398	A	2/1999	Snapp	6,580,918	B1	6/2003	Leickel	
5,889,474	A	3/1999	LaDue	6,584,314	B1	6/2003	Haumont	
5,890,062	A	3/1999	Courtney et al.	6,587,691	B1	7/2003	Granstam	
5,920,820	A	7/1999	Qureshi et al.	6,603,969	B1	8/2003	Vuoristo	
5,929,752	A	7/1999	Janky et al.	6,603,977	B1	8/2003	Walsh et al.	
5,950,125	A	9/1999	Buhrmann et al.	6,611,687	B1	8/2003	Clark	
5,950,137	A	9/1999	Kim	6,618,593	B1 *	9/2003	Drutman et al.	455/456.3
5,961,569	A	10/1999	Craport et al.	6,618,671	B2	9/2003	Dooley et al.	
5,961,572	A	10/1999	Craport et al.	6,622,020	B1	9/2003	Seki	
5,978,747	A	11/1999	Craport et al.	6,628,938	B1	9/2003	Rachabathuni et al.	
5,987,019	A	11/1999	Lipsanen et al.	6,636,732	B1	10/2003	Boling	
5,999,124	A	12/1999	Sheynblat	6,647,257	B2	11/2003	Owensby	
6,023,241	A	2/2000	Clapper	6,662,014	B1	12/2003	Walsh	
6,028,537	A	2/2000	Suman et al.	6,662,614	B1	12/2003	Lim	
6,032,042	A	2/2000	Kauppi	6,665,389	B1	12/2003	Haste, III	
6,035,189	A	3/2000	Ali-Vehmas	6,677,894	B2	1/2004	Sheynblat	
6,035,198	A	3/2000	Wiehe	6,714,791	B2	3/2004	Friedman	
6,038,446	A	3/2000	Courtney et al.	6,716,101	B1 *	4/2004	Meadows et al.	455/456.1
6,047,051	A	4/2000	Ginzboorg	6,725,032	B1	4/2004	Sheridan	
6,049,711	A	4/2000	Ben-Yehzekel	6,735,564	B1	5/2004	Puhakainen	
6,057,759	A	5/2000	Marsh	6,765,528	B2	7/2004	Tranchina	
6,061,561	A	5/2000	Alanara et al.	6,778,837	B2 *	8/2004	Bade et al.	455/456.1
6,078,578	A	6/2000	Matsumoto	6,795,710	B1	9/2004	Creemer	
6,080,063	A	6/2000	Khosla	6,798,358	B2	9/2004	Joyce et al.	
6,088,586	A	7/2000	Haverty	6,799,094	B1	9/2004	Vaida et al.	
6,091,959	A	7/2000	Souissi et al.	6,806,813	B1	10/2004	Cheng et al.	
6,138,003	A *	10/2000	Kingdon et al.	6,816,735	B1	11/2004	Rayburn et al.	
6,144,336	A	11/2000	Preston et al.	6,826,398	B1	11/2004	Lagerstrom et al.	
6,157,841	A	12/2000	Bolduc et al.	6,836,667	B1	12/2004	Smith	
6,166,626	A	12/2000	Janky et al.	6,870,822	B2	3/2005	Balogh	
6,173,182	B1	1/2001	Cha	6,879,836	B2	4/2005	Nakamoto	
6,201,803	B1	3/2001	Munday et al.	6,879,838	B2	4/2005	Rankin et al.	
6,208,866	B1	3/2001	Rouhollahzadeh et al.	6,882,837	B2	4/2005	Fernandez et al.	
6,215,863	B1	4/2001	Bennett et al.	6,882,856	B1	4/2005	Alterman	
6,236,359	B1	5/2001	Watters et al.	6,885,874	B2 *	4/2005	Grube et al.	455/520
6,236,858	B1	5/2001	Griffith	6,912,398	B1	6/2005	Domnitz	
6,240,069	B1	5/2001	Alperovich	6,912,545	B1	6/2005	Lundy et al.	
6,246,376	B1	6/2001	Bork et al.	6,920,319	B2	7/2005	Knutsson et al.	
6,246,861	B1	6/2001	Messier et al.	6,920,328	B2 *	7/2005	Wollrab	455/456.1
6,252,543	B1	6/2001	Camp	6,928,279	B2	8/2005	Seligmann et al.	
6,256,498	B1	7/2001	Ludwig	6,932,698	B2	8/2005	Sprogis	
6,259,923	B1	7/2001	Lim et al.	6,944,447	B2	9/2005	Portman et al.	
6,275,544	B1	8/2001	Aiello	6,968,179	B1 *	11/2005	De Vries	455/414.1
6,275,771	B1	8/2001	Berstis et al.	6,970,853	B2	11/2005	Schutzer	
6,287,200	B1	9/2001	Sharma	6,975,998	B1	12/2005	Jones	
6,311,060	B1	10/2001	Evans et al.	6,999,777	B1	2/2006	Ganesh	
6,314,365	B1	11/2001	Smith	7,010,110	B2	3/2006	Jorasch et al.	
6,317,718	B1	11/2001	Fano	7,013,148	B1	3/2006	Ganesh	
6,321,092	B1	11/2001	Fitch et al.	7,072,956	B2	7/2006	Parupudi	
6,324,404	B1	11/2001	Dennison et al.	7,130,630	B1	10/2006	Enzmann	
6,330,452	B1	12/2001	Fattouche et al.	7,177,651	B1 *	2/2007	Almassy	455/456.1
6,360,101	B1	3/2002	Irvin	7,203,674	B2	4/2007	Cohen	
6,360,102	B1 *	3/2002	Havinis et al.	7,215,965	B2	5/2007	Fournier et al.	
6,360,167	B1	3/2002	Millington et al.	7,248,872	B2	7/2007	Bassett et al.	
6,374,306	B1	4/2002	Tognazzini	7,269,426	B2 *	9/2007	Kokkonen et al.	455/456.1
6,377,565	B1	4/2002	Puckette	7,269,428	B1 *	9/2007	Wallenius et al.	455/456.2
6,377,810	B1 *	4/2002	Geiger et al.	7,272,220	B1	9/2007	Zhang	
6,393,274	B1	5/2002	Peltonen	7,275,258	B2	9/2007	Arbab	
6,397,065	B1	5/2002	Huusko et al.	7,324,823	B1	1/2008	Rosen	
6,400,946	B1	6/2002	Vazvan	7,333,776	B1	2/2008	York	
				7,409,429	B2	8/2008	Kaufman et al.	
				7,570,958	B2	8/2009	Krasner	
				7,983,947	B2	7/2011	Kaiwa	
				8,073,087	B2	12/2011	Casaccia	

(56)

References Cited

U.S. PATENT DOCUMENTS

8,478,304	B1	7/2013	David et al.	
2001/0029186	A1	10/2001	L'Anson et al.	
2001/0048364	A1	12/2001	Kaithoff et al.	
2001/0055328	A1	12/2001	Dowling	
2002/0003470	A1	1/2002	Auerbach	
2002/0042277	A1 *	4/2002	Smith	455/456
2002/0086683	A1 *	7/2002	Kohar et al.	455/456
2002/0090912	A1	7/2002	Cannon	
2002/0090985	A1	7/2002	Tochner et al.	
2002/0102989	A1 *	8/2002	Calvert et al.	455/456
2002/0115453	A1 *	8/2002	Poulin et al.	455/456
2002/0138581	A1	9/2002	Macintosh et al.	
2002/0141434	A1	10/2002	Grundvig	
2002/0164998	A1	11/2002	Younis	
2002/0183059	A1	12/2002	Noreen et al.	
2003/0004743	A1	1/2003	Callegari	
2003/0013456	A1 *	1/2003	Bates et al.	455/456
2003/0013461	A1 *	1/2003	Mizune et al.	455/456
2003/0023726	A1 *	1/2003	Rice et al.	709/225
2003/0060214	A1	3/2003	Hendrey	
2003/0069692	A1 *	4/2003	Krasner et al.	701/213
2003/0119522	A1 *	6/2003	Barclay et al.	455/456
2003/0144009	A1	7/2003	Nowlin	
2004/0033795	A1	2/2004	Walsh et al.	
2004/0038706	A1	2/2004	Wasser et al.	
2004/0054428	A1	3/2004	Sheha	
2004/0077359	A1	4/2004	Bernas et al.	
2004/0127231	A1	7/2004	Dorr	
2004/0180669	A1 *	9/2004	Kall	455/456.1
2004/0198386	A1	10/2004	Dupray	
2005/0009608	A1	1/2005	Robarts et al.	
2005/0222756	A1	10/2005	Davis et al.	
2008/0288355	A1	11/2008	Rosen	
2009/0005019	A1	1/2009	Patel et al.	
2009/0029717	A1 *	1/2009	Bates et al.	455/456.1
2009/0197612	A1	8/2009	Kiiskinen	
2012/0106728	A1	5/2012	Ghaffari et al.	

FOREIGN PATENT DOCUMENTS

WO	WO99/051051	3/1999
WO	WO 00/028760	5/2000
WO	WO 00/035228	6/2000
WO	WO 00/038350	6/2000
WO	WO 00/064075	10/2000
WO	WO 00/076194	12/2000
WO	WO 00/076243	12/2000
WO	WO 01/001711	1/2001
WO	WO 01/01718	1/2001
WO	WO 01/003406	1/2001
WO	WO 01/003454	1/2001
WO	WO 01/003461	1/2001
WO	WO 01/010718	1/2001
WO	WO 01/020938	3/2001
WO	WO 01/033885	5/2001
WO	WO 01/039525	5/2001
WO	WO 01/039528	5/2001
WO	WO 01/041468	6/2001
WO	WO 01/050544	7/2001
WO	WO 01/086834	11/2001
WO	WO 01/086880	11/2001
WO	WO 01/089251	11/2001
WO	WO 02/003718	1/2002

OTHER PUBLICATIONS

ETSI TS 101 527 "Digital Cellular Telecommunications System (Phase 2+): Location Services (LCS): Mobile Station (MS): Serving Mobile Location Centre (SMLC)," Radio Resource LCS Protocol (RRLP), GSM 04.31, version 8.1.0. 1999.

Wrolstad, Jay, "Sprint Claims First With E911-Capable Phone," newsfactor.com (as viewed at <http://www.newsfactor.com/perl/story/13952.html> on Jan. 22, 2007), Oct. 4, 2001.

Wrolstad, Jay, "Sprint Rolls Out E911 Services," newsfactor.com (as viewed at <http://www.newsfactor.com/perl/story/15506.html> on Jan. 22, 2007), Dec. 26, 2001.

"Sprint PCS First Quarterly E911 Implementation Report," Before the Federal Communications Commission, In the Matter of Revision of the Commission's Rules to Ensure Compatibility With Enhanced 911 Emergency Calling Systems, Feb. 1, 2002.

"Who is Integrated Data Communications?," presented at the FCC E-911 Automatic Location Identification Round Table, Jun. 28, 1999.

"Wireless Telecommunications Bureau Seeks Comment on Request to Commence Rulemaking to Establish Fair Location Information Practices," (as viewed at http://www.fcc.gov/Bureaus/Wireless/Public_Notices/2001/da010696.html on Jan. 22, 2007), Mar. 16, 2001.

"Go2 Systems & Integrated Data Communications to Deliver Location Services Automatically to Wireless Phones; Alliance Enables Automatic Recognition of Wireless Caller's Location," Business Wire (as viewed at http://www.findarticles.com/p/articles/mi_m0EIN/is_2000_Feb_28/ai_596_21222 on Jan. 22, 2007), Feb. 28, 2000.

"Before the Federal Communications Commission: In the Matter of: E-911 Automatic Location Identification Round Table," Transcript, Jun. 28, 1999.

"Pulver.com's Location Based Services Report," pulver.com (as visited at <http://pulver.com/lbsreport/lastlbsreport.16jan01.txt> on Jan. 22, 2007), Jan. 2001.

"Pulver.com's Location Based Services Report," pulver.com (as visited at <http://pulver.com/lbsreport/lastlbsreport.26feb01.txt> on Jan. 22, 2007), Feb. 2001.

"Pulver.com's Location Based Services Report," pulver.com (as visited at <http://pulver.com/lbsreport/lastlbsreport.26mar01.txt> on Jan. 22, 2007), Mar. 2001.

"Pulver.com's Location Based Services Report," pulver.com (as visited at <http://pulver.com/lbsreport/lastlbsreport.05apr01.txt> on Jan. 22, 2007), Apr. 2001.

"Pulver.com's Location Based Services Report," pulver.com (as visited at <http://pulver.com/lbsreport/lastlbsreport.01may01.txt> on Jan. 22, 2007), May 2001.

"Pulver.com's Location Based Services Report," pulver.com (as visited at <http://pulver.com/lbsreport/lastlbsreport.10jun01.txt> on Jan. 22, 2007), Jun. 2001.

"Pulver.com's Location Based Services Report," pulver.com (as visited at <http://pulver.com/lbsreport/lastlbsreport.05jul01.txt> on Jan. 22, 2007), Jul. 2001.

"Pulver.com's Location Based Services Report," pulver.com (as visited at <http://pulver.com/lbsreport/lastlbsreport.01aug01.txt> on Jan. 22, 2007), Aug. 2001.

"Pulver.com's Location Based Services Report," pulver.com (as visited at <http://pulver.com/lbsreport/lastlbsreport.04sep01.txt> on Jan. 22, 2007), Sep. 2001.

"Pulver.com's Location Based Services Report," pulver.com (as visited at <http://pulver.com/lbsreport/lastlbsreport.02oct01.txt> on Jan. 22, 2007), Oct. 2001.

"Pulver.com's Location Based Services Report," pulver.com (as visited at <http://pulver.com/lbsreport/lastlbsreport.02nov01.txt> on Jan. 22, 2007), Nov. 2001.


"Pulver.com's Location Based Services Report," pulver.com (as visited at <http://pulver.com/lbsreport/lastlbsreport.03dec01.txt> on Jan. 22, 2007), Dec. 2001.


"Pulver.com's Location Based Services Report," pulver.com (as visited at <http://pulver.com/lbsreport/lastlbsreport.07jan02.txt> on Jan. 22, 2007), Jan. 2002.

"Pulver.com's Location Based Services Report," pulver.com (as visited at <http://pulver.com/lbsreport/lastlbsreport.04feb02.txt> on Jan. 22, 2007), Feb. 2002.

"Pulver.com's Location Based Services Report," pulver.com (as visited at <http://pulver.com/lbsreport/lastlbsreport.04mar02.txt> on Jan. 22, 2007), Mar. 2002.

* cited by examiner

**FIG. 1**

200**FIG. 2**




FIG. 3

400




FIG. 4

500




FIG. 5


600

FIG. 6

700




FIG. 7

800




FIG. 8

900




FIG. 9

1000




FIG. 10

1100




FIG. 11

1200







FIG. 12

1300**FIG. 13****1400****FIG. 14**

**FIG. 15**

1600




FIG. 16




FIG. 17

1800




FIG. 18

1

SYSTEMS AND METHODS FOR LOCATING CELLULAR PHONES AND SECURITY MEASURES FOR THE SAME

CROSS-REFERENCE TO RELATED APPLICATION

This application claims the benefit of U.S. Provisional Application No. 60/367,967, filed on Mar. 25, 2002, which is hereby incorporated by reference herein in its entirety.

BACKGROUND OF THE INVENTION

This invention relates to systems and methods for determining a device's location. More particularly, this invention relates to systems and methods for remotely determining a device's location.

The Global Positioning System (GPS) has been developed in which a ground-based system can receive GPS signals from satellites and use these signals to determine the location of the ground-based system based on the time the GPS signals took to reach the ground-based system. Generally, three satellite signals are needed to determine where in the world a receiver is located (i.e., position triangulation).

GPS systems have been integrated into cellular phones. However, these systems are deficient because the location of a device, as determined by these GPS signals, is only minimally utilized. It is therefore desirable to provide systems and methods that better utilize the information about a device's location.

SUMMARY OF THE INVENTION

In accordance with the present invention, systems and methods are provided for locating cellular phones. More particularly, the present invention provides systems and methods for allowing a user of a cellular phone (e.g., a requesting user or a requester) to locate the position of a different user's cellular phone (e.g., a requested user) based upon access rights assigned by the requested user.

One object of the present invention is to provide a security feature which allows a user to limit and/or deny location access to a particular user. In preferred embodiments, only the users that have been granted access to the location of a user's cellular phone can actually locate that user's cellular phone. Furthermore, different types of access levels may be provided that allow a user to filter location information to a different user. In this manner, a cell phone user may give access, through his or her cell phone, to a friend so that the friend can locate him or her dependent on the level of access that is granted to that friend.

For example, suppose that Phil tells Bill that he will be shopping in Manhattan and that Bill should locate him when Bill gets to Manhattan through their cell phones. In such an example, Phil may grant Bill access the exact location of his cell phone for a specific period of time (e.g., the next two hours). As a result, when Bill tries to access Phil's location, Bill will be told exactly where in Manhattan Phil's cell phone is located. Thus, Bill does not have to contact Phil directly to see where Phil is located and, therefore, Phil does not have to spend any time giving Bill verbal directions; Bill can simply see what store Phil is currently in and go to that store.

As mentioned previously, levels in the scope of access may be controlled by a user such that, for example, only a

2

user's exact location, approximate location, city, state, or country can be accessed by a particular user.

Location alerts and monitoring features are also provided. For example, Phil may give Jen, a resident of Pittsburgh, city access so that when Phil travels into Pittsburgh, Jen will be alerted of Phil's presence. Such an alert may take the form of, for example, a display on Jen's cell phone that communicates to Jen "Phil is in Pittsburgh."

Locating a cellular phone may be accomplished in several ways. For example, satellite positioning systems such as the Global Positional System and the soon to be deployed Galileo system may be used to locate a user's cell phone.

User positions and security settings may be regularly or manually transmitted to a remote system, such as a remote database so that requesting users can locate a requested user's position even if the requested user turns his/her cell phone OFF. Placing the security measures on a remote system (e.g., remote database, computer, or server) provides an information brokering scheme such that the system is still operable even when cell phones are added, removed, or modified from the system.

Additionally, the present invention may be configured to provide additional information about the location of a user. Such additional information may be, for example, a map, a location marker on a map, a map that changes as the user moves, a compass, coordinates of the located cell phone, directions to the located cell phone, where a user is in relation to another user, and information about the location the located user is currently positioned in or nearby locations such as landmarks. Such information may be provided by a remote information provider (e.g., a remote map information provider) and accessed by an information broker through a communications network.

Many other features are also employed that realize advantageous locating functionality. For example, suppose that a wife wants to see if her husband has left work yet. She can locate her husband, without having to talk to him, and realize that he is driving home on a highway. Thus, a travel time option may be provided to the user. This option would compute the distance between the wife's location and husband's location by taking multiple location readings of the husband's location to see how fast the husband is traveling. Alternatively, because the husband's position will map to a highway, the system may assume that the user is driving and may provide the wife with an estimate on the husband's arrival time based on an assumed route. In this manner, the present invention may determine how much time it will take the husband to reach the wife and display this information to the wife.

As per other examples, a "see my friends" option may also be provided that brings up a map of a desired area. Dots or symbols may be present on the map to signify the location of all users from which the requesting user has location information for. Similarly, a "find closest friend" option may be employed which finds the closest user with which the requesting user has location access to.

A cell phone location may be accessed by a variety of other devices. Alternatively, a cell phone may be used to access the location of a variety of other devices. For example, if the wife was at home, that wife may connect to the internet and access a remote database to either provide the most recent location information about the husband's cell phone to her or request a location update from the husband's cell phone. The wife's location may be already stored in such a database by associating the location to the IP address of the computer or by a manual input of the wife's location. The wife's identity may be determined by, for

3

example, a login and password on a website. Thus, the above-identified security measures are not limited to device-to-device locating, but rather user-to-user locating; the wife may only access the husband's location if the husband has granted access for the wife to do so. If, by accident, the wife's cell phone breaks, she may login on a friend's cell phone and determine the husband's location according to the device that the husband is logged into.

Security is preferably taken into account in the present invention and, therefore, location rights for a specific user may be given to a different user only by that specific user. However, a user may request location access rights from a different user. For example, a user may be provided with a request location screen on his cell phone and that user (e.g., user "X") may enter in the cell phone number of the cell phone whose location is desired. The user associated to the entered cell phone number may then receive an alert that says "user X has requested access to your location." Location access may then be given or denied on multiple levels and the requesting user notified of the decision.

The location feature of the present invention may be turned ON or OFF at any time. Users may be added, individually or in groups, to a list of users with location access rights to a specific user by that specific user. A specific user may, at any time, modify, delete, or add users allowed to access his or her location. Login and password information may be included to increase security or to create a user profile, allowing a specific user to log into any cell phone and be recognized (and thereby be located with that cell phone or locatable device).

BRIEF DESCRIPTION OF THE DRAWINGS

The principles and advantages of the present invention can be more clearly understood from the following detailed description considered in conjunction with the following drawings, in which the same reference numerals denote the same structural elements throughout, and in which:

FIG. 1 is a network topology of a cell phone locating network in accordance with the principles of the present invention;

FIG. 2 is a flow chart of the locating feature in accordance with the principles of the present invention;

FIG. 3 is an illustration of a cell phone in accordance with the principles of the present invention;

FIG. 4 is a display screen for a locate feature in accordance with the principles of the present invention;

FIG. 5 is a display screen for a retrieving location status feature in accordance with the principles of the present invention;

FIG. 6 is a display screen for a displaying location feature in accordance with the principles of the present invention;

FIG. 7 is a display screen listing options for a locate feature in accordance with the principles of the present invention;

FIG. 8 is a display screen of a failed locate feature due to insufficient rights in accordance with the principles of the present invention;

FIG. 9 is a display screen of adding and modifying locate rights and options to a user in accordance with the principles of the present invention;

FIG. 10 is a display screen of assigning location rights to a user in accordance with the principles of the present invention;

FIG. 11 is a display screen of alert options in accordance with the principles of the present invention;

4

FIG. 12 is a display screen of an alert feature in accordance with the principles of the present invention;

FIG. 13 is a display screen of a login feature in accordance with the principles of the present invention;

FIG. 14 is a display screen of a login feature in accordance with the principles of the present invention;

FIG. 15 is a wireless device in accordance with the principles of the present invention;

FIG. 16 is an embodiment of a network topology in accordance with the principles of the present invention;

FIG. 17 is an embodiment of a locating feature in accordance with the principles of the present invention; and

FIG. 18 is an embodiment of a communications signal in accordance with the principles of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

FIG. 1 depicts a network topology of device location network 100 that incorporates principles of the present invention. Network 100 includes one or more positioning satellites 110, 112, and 114 that can locate the position of one or more cell phones 120, 122, 126, and 124 (and other locatable devices) on Earth 101. Positioning satellites 110, 112, and 114 may be, for example, the Global Positioning System (GPS) or the upcoming Galileo satellite network.

Preferably, any cell phone in network 100 may locate a different cell phone, as long as access to location information is allowed, through the utilization of positioning satellites 110, 112, and 114. Persons skilled in the art will appreciate that other positioning systems and methods may be used in locating the position of a user on a cell phone of network 100.

To route information to and from a cell phone of network 100 additional facilities and communication paths may be included. For example, a main facility (not shown in FIG. 1) containing user location access rights may be included in network 100. Such a main facility may retrieve location information directly from a positioning system or a cellular phone and then route this information to a cellular phone or positioning system.

Persons skilled in the art will appreciate that if the Global Positioning System (GPS) is used as the positioning system then GPS receivers will be incorporated into cellular phones of the present invention. Persons skilled in the art will also appreciate that devices other than cellular phones may include positioning features. For example, watches, clothing, laptop computers, personal digital assistants (PDAs), may all contain location systems (e.g., GPS) and utilize the security principles of the present invention to allow different user's to access these locations.

FIG. 2 shows flow chart 200 of a simplified locating feature constructed in accordance with the principles of the present invention. Step 202 initiates when a user requests the location of another user's cell phone. Step 206 evaluates if the user initiating the location request has the rights to access the location of the desired user. If no access rights for the requesting user have been granted then step 204 will preferably inform the requesting user that he/she has not been given access to the requested location. In this manner, every user may assign rights (e.g. govern the security) to whom may or may not locate him/her. In preferred embodiments, these rights will be stored in, or functionality executed from, a remote facility and accessed and utilized by a user's cell phone or other requesting device (e.g., a watch or PDA).

If access has been given by a particular user that allows for the requesting user to locate that particular user, step 208

is initiated and the allowed location information is provided to the user in step 210. Step 208 may optionally filter the location information such that only a portion information is passed to the requesting user. The requested user may have, for example, defined that the requesting user only can obtain the city, state, or country of his/her location. Persons skilled in the art will appreciate that only the location of the desired user needs to have a cell phone or a positioning system. The requesting user may use other means (e.g., the internet) to request the location of the desired user.

Persons skilled in the art will appreciate that the location of a user's cell phone may be retrieved, in step 208, from a remote database, facility, distribution center, or any other system. More particularly, a remote database may periodically request the location of a cell phone user with a positioning system and store this information. This database may also keep a record of those people allowed to access that user's location, the extent to which access is allowed, and the extent to which a user has requested a user's location. A user may update, add, manipulate, or remove access at any time by doing so at this database. Thus, a requesting user only has to contact the remote database, have his/her identity recognized, have his/her access rights for the requested user location determined, and, if the requesting user has the correct access rights, be provided with the requested user's location.

Instead of a remote database periodically obtaining location information for a user, the database can obtain a user's locations when a request is made for that user's location, provided that the requesting user has access to the requested user's location. However, persons skilled in the art will recognize that a remote database is utilized in the above examples to contain the locations, in most circumstances, of a multitude of users. Thus, to increase security even more, a requesting user's cell phone may directly request a user's location from the requested user's cell phone without the need for a database. In such an example a user adds, manipulates, or removes access rights locally on his/her cell phone and does not have to worry about security issues that surround placing his location on a remote database. Furthermore, in such an embodiment a user's location does not have to be saved anywhere, a positioning system can just be "read" by a requesting user with the appropriate access rights.

However, by recording a user's location on a device, e.g., a cell phone's memory or in a remote database, novel applications may be utilized. For example, whenever a user makes a credit card purchase, a credit card authorization system can record the location of a cell phone associated to the purchasing user. In this manner, a new system and method of fraud protection is introduced. The credit card authorization system may, for example, reject a purchase if the purchaser's cell phone (or watch, clothing, PDA, or other positioning enabled device) is not in the vicinity of the purchase. Alternatively, the credit card authorization system may request a second form of identification if the purchaser's cell phone location does not correlate to the location of the purchase. Additionally, the credit card authorization system may call the purchaser's cell phone and request authorization for the credit card purchase. However, such features would preferably first involve the user/purchaser giving the credit card authorization system access to the location of his/her cell phone.

As per another application, a unique dating/matching service could be embodied. For example, a user may store a number of preferences in a matching profile. These preferences may describe what type of person the user is interested

in meeting. Additionally, a user may store, preferably locally (for the dating/matching feature), but alternatively at a remote location, the user's own profile that has data describing similar attributes for what the user is looking for. For example, an entry in a user's profile may be "male" and an entry in a "looking for" profile may be "female." When a user comes within a certain distance of a user (determined by comparing locations of a user) that fits his/her "looking for" profile, the user may be alerted of the proximity of a matching user. Preferably, the particular user is only alerted if the "looking for" user has entered in attributes similar to the particular user's attributes and is also alerted of the particular user. The next stages of such an application could include, for example, requesting access to a form of communication. Such a form of communication could be for example, talking on the phone, instant messaging, or delivering an email address. Persons skilled in the art will therefore appreciate that many useful applications may be constructed using the principles of the present invention.

FIG. 3 depicts cell phone 300 constructed in accordance with the principles of the present invention. Cell phone 300 preferably includes speaker 330, antenna 310, display screen 320, control keys 360, alpha-numeric keys 350, and microphone 340. Cell phone 300 also preferably may include, for example, a communications transmitter (not shown), communications receiver (not shown), memory (not shown), positioning device (not shown), and a microprocessor (not shown).

Cell phone 300 may also include locate button 380. Cell phone 300 may be configured such that if locate button 380 is pressed, a locate feature is initiated (e.g., display screen 400 of FIG. 4 is initiated). Alternatively, cell phone 300 may be configured such that if locate button 380 is pressed, a location signal is sent to a remote storage area (e.g., a remote database), thus manually updating the user's location. This latter functionality may be useful when a user does not want his/her location accessed. As in another alternative embodiment, cell phone 380 may be configured such that if locate-button 380 is pressed, the locating features of cell phone 300 are toggled between ON and OFF. Person skilled in the art will appreciate that locate button 380 may be configured to produce a variety of useful functionalities.

FIG. 4 depicts display screen 400 that is displaying a locate feature constructed in accordance with the principles of the present invention. The locate feature of display screen 400 may be included, for example, in cell phone 300 of FIG. 3 and displayed to the user of cell phone 300 of FIG. 3 when that user requests the location of a different user of the present invention. The programming for the feature may, for example, be stored in the memory of the cell phone and executed by the processor at a user's request. Locate feature 400 includes identifier list 410 of alpha-numeric identifiers for users stored in the memory on cell phone 300 (FIG. 3) or at a remote location. More particularly the user of display 410 may locate a user contained in identifier list 410 by selecting an appropriate user identifier 420.

The user identifiers (e.g., "Susan Pracht") in identifier list 410 are selectable and may be selected by control keys 360 of FIG. 3. Highlight window 410 may be used to prompt the user what identifier from list 410 is currently selected any may be controlled, for example, by the input keys of the cell phone (e.g., keys 350 and 360 of FIG. 3). Identifiers may be associated to, for example, cellular telephone number, user profiles, or any other identifier that may be associated to a locatable device or user interacting with a locatable device.

Persons skilled in the art will appreciate that display screen 400 may be provided to a user of devices other than

wireless devices. For example, display screen **410** may be provided to a user of a personal computer with no positioning system. Preferably, however, the security measures in accordance with the principles of the present invention are still abided to (e.g., access has been granted to the identifier associated to the requesting user). In this manner, a user can control who can access his/her wireless device (e.g., cell phone).

Persons skilled in the art will appreciate that identifier list **410** may be configured, for example, to contain only those users in which the user of cell phone **300** (FIG. 3) has locate access rights to or any user stored in cell phone **300**. Persons skilled in the art will also appreciate that devices other than cell phone **300** may be used to incorporate the features of the present invention. Such devices could include, for example, personal digital assistants (PDAs), laptop, GPS pagers, GPS watches, car positioning devices, or any other devices that can be located. One advantage of the present invention is that it allows a mobile device with a positioning system to locate a different mobile device with a positioning system while still retaining a high level of location security and privacy.

FIG. 5 is display screen **500** for retrieving location status feature in accordance with the principles of the present invention. The selected identifier may be incorporated into display screen **500** through location status display **510** to inform the user of the status of the location retrieval. For example, display screen **500** may display "locating user" while a request is being processed by a remote facility or database.

FIG. 6 shows display screen **600** for a display location feature constructed in accordance with the principles of the present invention. When a location is retrieved for the requested user, the location may be displayed on Display Screen **600** through primary location information **610**. Depending on what scope the requesting user has access to, primary location information **610** may include, for example, the country, state, city, exact location, or any combination thereof of location information to the user. For example, if the user requesting the location of a desired user has been given unlimited location access by the desired user, primary information **610** may include the exact location of the user.

Secondary location information **620** may be included to supplement the requested users exact location so that the requesting user may have more of an idea of where the requested user is located. For example, if the desired user is located in a mall, primary location information **610** may be the address of the mall. In such an example, secondary location information **620** may be included and display, to the requesting user, the name of the mall.

Directional information **630** may also be included on display **600** or any other display of the present invention. Directional information **630** may include a digital compass **632** so that the user of cell phone **300** (FIG. 3) knows what direction he or she is facing in. Digital compass **632** may be connected to a directional sensitive device (e.g., mechanical compass) in order to gather directional information. Directional arrow **633** may also be included in display **600** to indicate where the requested user's location is relative to the location and direction of cell phone **300** (FIG. 3) (e.g., the requesting user). Persons skilled in the art will appreciate that for some directional information **630** the location of the requesting user must be obtained. This information may be obtained either from cell phone **300**, a remote facility, or by any other suitable means. If the information is gathered from a location-gathering device other than the requesting user's device (e.g., cell phone **300** (FIG. 3)), then the user's device

may communicate with this other location gathering device. Once both the locations of the requesting and requested/ desired users are known, this information may be utilized in a number of features incorporating the principles of the present invention.

Distance information **634** is one such feature that displays the distance between the locations of the requested and requesting users (e.g., distance between the locations of the requested and requesting devices). Directional information **630** may contain many other elements to enhance the utility of the present invention. For example, a map (not shown in FIG. 6) may be included in display **600**. This map may be of the area surrounding either the requested, the requesting user's location or both. Information may be included on the map to show the shortest path between the location as well as information about the surrounding area (e.g., area names, store names, etc.). Other information may include, for example, time to reach the destination according to specific types of travel (e.g., subway, walking, running, driving) and the direction the requested user is traveling in.

Location information may be utilized by a user in a variety of ways. For example, if Jane calls Bill and Bill says "I am roaming midtown Manhattan shopping why don't you join me", no other call to Bill is needed. Bill simply has to give Jane access to his location and Bill can continue shopping without having to worry about meeting up with Jane at a specific location.

In some instances, it may be beneficial to find the speed and direction of a requested user. For example, if a wife wants to see how long before her husband arrives home, the wife can use this feature of the present invention. This feature may find the husbands location multiple times in a determined amount of time. Through this information the feature may determine the speed and direction that the user is traveling. Using this speed, for example, this feature may display to the wife that the husband "is 10 minutes away" in directional information **630**. In doing so, the need for a call to the husband to determine his location is eliminated.

Persons skilled in the art will appreciate that the location of multiple users may be displayed on display screen **600**. For example, suppose Jeff, Susan, and Chrissy are at a concert. If all three of these users have unlimited access to the other users, the principles of the present invention would allow for a map to be displayed on each of the three locating devices with locator designations for each of the users. Using such a map, the group may be able to find themselves relative to one another and decide, if need be, on the easiest location for them to meet. Thus map **660** may be included on display screen **600** and display the locations of multiple users (e.g., user's **621** and **622**).

More region **640** designates that more options or information may be retrieved or performed using principles of the present invention. A user may use control keys **340** (FIG. 3) on cell phone **300** (FIG. 3) to perform the functionality associated with more region **640**.

FIG. 7 shows display screen **700** for locate listing options in accordance with the principles of the present invention. Display screen **700** includes selectable options list **710** and highlight window **720** and may be displayed to the user, for example, through the activation of functionality associated by more region **640** (FIG. 6). Options list **710** may include any of the features of the present invention. For example, options list **710** may include options activating a display screen of a map of the requesting user's location, a map of the requested user's location, directions to the requested user's location from the requesting user's location, travel

time for the requesting user, travel time for the requested user, and options to set location alerts.

FIG. 8 shows display screen 800 of a failed locate feature due to insufficient rights in accordance with the principles of the present invention. Display screen 800 may be displayed if a requesting user attempts to locate a requested user, but has not been given access rights by the requested user to the requested user's location. In such an instance, insufficient rights message 801 may be prompted on display screen 800.

FIG. 9 shows display screen 900 for adding and modifying locate rights and options to a user in accordance with the principles of the present invention. A user may give or modify access rights through display 900 to a user identifier in selectable user identifier listing 910. Highlight window 920 may be included to enhance the selecting process.

FIG. 10 shows display screen 1000 for assigning location rights to a user in accordance with the principles of the present invention. Display screen 1000 may be displayed, for example, after a user has been selected to be given location rights. Display screen 1000 contains selectable location rights listing 1010, in which the selecting process may be enhanced by highlight window 1020. Possible location access rights may be, for example, by country, state, city, exact location, or any other scope of location. Other rights may be assigned such as particular times in the day or time periods at which locations may be accessed.

FIG. 11 shows display screen 1100 of alert options in accordance with the principles of the present invention. Display screen 1100 allows for a user to set up alerts depending on the location of specific users. Selectable alert listings 1110 are included and may be selectable with highlight window 1120. Examples of alerts that may be included in display screen 1100 may occur, for example, if the requested user is in a specific city or the same city as the user of display 1100, is within a certain distance, or if a user located the user of display 1100.

The alerts of the present invention may realize useful functionality. For example, suppose Susan Pracht lives in Pittsburgh and rarely comes to the city of the user of display screen 1100 on cell phone 300 (FIG. 3) which is New York City. The user of cell phone 300 (FIG. 3) may then use display screen 1100 and set an alert such that if Susan Pracht ever enters New York City, he or she would be alerted of Susan Pracht's presence.

FIG. 12 shows display screen 1200 of an alert feature in accordance with the principles of the present invention. Display screen 1200 includes an alert message and is displayed to a user when an event occurs that is designated by the user in display screen 1100 (FIG. 11). Continuing the example from FIG. 11, if Susan Pracht enters New York City, alert message 1210 would prompt the user that this event has occurred.

FIG. 13 shows display screen 1300 of a login feature in accordance with the principles of the present invention. In order for users to be identified by other user's cell phones or locating devices a user profile may need to be stored remotely from such devices. In such instances user profiles would be used as the locating identifier and the devices into which these profiles are logged into (recognized by) would allow for the user to be located. Display screen 1300 allows for a user to log into a locating device of the present invention. Logging into a device also adds a level of security to the present invention, especially when combined with a password. A user may use the controls of the device of the present invention to enter login 1310 of display 1300.

In this manner, a user may use another user's location device (e.g., cell phone) to locate a user or may use, for

example, the internet to locate a user. Additionally, in this manner, a user may change the device being located. For example, a user may use his or her car GPS system or other systems in accordance with the principles of the present invention to be located instead of his or her cell phone. To further this example, a user may log into a web site on the internet and designate his or her current location as home, or any other location, thus eliminating the need for a locatable device entirely.

FIG. 14 shows display screen 1400 of a login feature in accordance with the principles of the present invention. Display screen 1400 may be used by a user to enter a password associated to that user's profile, identity, or cell phone functionality access. A user may enter password 1410 using the controls of the device of display screen 1400 (e.g., cell phone 300 of FIG. 3). By including a login/password scheme a user can be identified by a remote facility (e.g., a remote database) so that the user's location can be recorded/updated by multiple devices. Additionally, a login/password adds an extra level of security.

FIG. 15 shows cell phone 1500 that may be utilized to carry but the functionality in accordance with the principles of the present invention. Cell phone 1500 includes receiver/transmitter 1510, microprocessor 1520, positioning system 1530, and memory 1540.

Persons skilled in the art will appreciate that receiver/transmitter 1510 may directly communicate with memory 1540 if receiver/transmitter 1510 does not have its own memory (e.g., if receiver/transmitter 1510 are configured to utilize a buffer for capturing incoming communications bursts before-demodulation and decryptions).

Positioning system 1530 may be, for example, a GPS system or a similar positioning system. Positioning system 1530 may include its own receiver for receiving particular signals utilized in positioning cell phone 1500.

FIG. 16 shows network topology 1600 that includes a variety of components, all of which, or some of which, may be utilized to carry out the features in accordance with the principles of the present invention. In this manner, persons skilled in the art will appreciate that multiple system configurations may be utilized. Topology 1600 introduces the diversity of systems that can be utilized to realize such configurations.

Generally, topology 1600 includes multiple mobile devices (e.g., multiple instances of mobile device 1601), access control devices and location broker devices (e.g., database 1602 and cell phone base station 1603), and non-mobile devices (e.g., grounded non-wireless device 1605). Persons skilled in the art will appreciate that other devices or facilities may be included in topology 1600. For example, one or more positioning systems 1601 may be included in topology 1600 in order to locate particular devices. For example, a positioning receiver (e.g., GPS receiver) may be included in wireless device 1601 with positioning system 1601 being a positioning transmitter (e.g., GPS satellite network).

One or more wireless devices 1601 may be included in topology 1600 and may be, for example, watches, PDAs, cellular phones, radios, cars, or any other mobile device whose location can be determined.

As previously mentioned, access control and location broker devices may be included in topology 1600. Such devices may be utilized, for example, to store user access rights for a particular user and may contain functionality to request and route a device's location. These devices may be considered information brokers such that devices may be

11

added, removed, or modified without creating the necessity of having to modify the other devices of topology 1600.

Database 1602 is one such information broker. Database 1602 may, for example, be located in cell phone base station 1603 if database 1602 is utilized to assist in cell phone locating. Database 1602 may be utilized, for example, to store a history of a device's locations, a user's list of assigned access rights to other users, a log of a user's call activity, a log of location initiations, a user profile, login/password information, or any other sort of information. Many features may be provided that utilize such information. For example, an approximate location may be determined for a device that is turned OFF (e.g., by utilizing the device's location history). As per another example, if a cell phone is lost and a new one replaced, information such as, for example, phone books, activity logs, and assigned user access rights may be downloaded/flushed into the cell phone.

Database 1602 may be accessed either directly (e.g., manually by an user of the device) or indirectly (e.g., periodically) by a cell phone or other device. Alternatively, a device or cell phone may access database 1602 directly (e.g., manually by an administrator of the database) or indirectly (e.g., periodically) by database 1602.

A credit card authorization system is an example of additional system 1606 that may be added to topology 1600 to realize new features. Such a credit card authorization system, as described above, could utilize a device's location in order to decrease credit card fraud. System 1600 may also be, for example, systems needed to realize the described dating functionalities or another information provider (e.g., a map information provider).

Non-wireless devices 1605 (e.g., a personal computer) may be included in topology 1600. Such devices may have locations associated to them or contain a positioning system. These locations may then be associated to a user that is recognized as using the device. For example, if a particular user logs into a non-mobile personal computer, that user's location will be recognized as being the location associated to the personal computer.

The devices of topology 1600 communicate with each other through communications network 1610. Communications network 1610 may include, for example, any type of communications, routing, amplification, encryption, decryption, parsing, modulation, or demodulation technologies. For example, positioning system 1601 may communicate with wireless device 1601 by sending multiple wireless positioning signals. At the same time, database 1602 may be providing non-wireless device 1605 with a device's location over conventional telephone wires.

FIG. 17 shows locating feature 1700 in accordance with the principles of the present invention. Locating feature 1701 starts at step 1701 and waits at step 1702 until a location is requested. As stated, a location can be requested in a number of instances and by a variety of different means.

For example, a location may be requested by a user of a cell phone that desires to locate a friend by locating that friend's cell phone. Alternatively, a device may be triggered to request a location of a mobile device when an event occurs. For example, a credit card authorization system may request the location of a user's cell phone and the location of a store that just used a credit card associated to the requested user.

If a location is requested, access rights to the requested location for the requesting device and/or user are obtained at step 1703. Step 1703 may be employed for example, as a call to a database storing a list of assigned access rights for the

12

requested device/user and finding if any access rights were assigned to the requestor's identity. As per another example, step 1703 may be employed as a direct call to the requested device/user.

Step 1704 determines if the requestor has been assigned access rights to obtain the requested device/user's location. Persons skilled in the art will appreciate that some devices may always have access to a user's location regardless if a user has assigned access rights to the requesting device. In this manner, a device may be set up to always let a user access a location. For example, a mother may purchase a cell phone for a minor and may configure the cell phone to always allow her location information.

If access rights do exist for the requesting device/user at step 1704 then step 1705 may be initiated and location information may be provided to the requester. Such location information may be filtered according to the assigned access rights. For example, if a user has only been assigned access rights to obtain the requested user's city location, only the city that the requested user/device is currently located in (or the last city location available) may be obtained. The process then finishes at step 1707 after the assigned location information has been delivered to the requestor at step 1705. Persons skilled in the art will appreciate that steps may be added to, removed, or modified from locating feature 1700. For example, instead of finish step 1707, step 1702 may be initiated after step 1706 has completed.

If a requester has not been assigned rights to access the requested user/device's location as determined by step 1704, then step 1712 may be initiated. Step 1712 informs the requester that the requester does not have access rights to obtain the location of a user/device. Step 1711 may follow and provide an opportunity for the requestor to obtain the access rights. More particularly, step 1711 asks the requestor if the requestor would like to request access rights. If the requester does not want to request access rights, locating feature 1700 may, for example, return to step 1702. Else, access rights may be requested at step 1721. Step 1722 follows and if access rights were given then step 1705 may be initiated. Else, step 1712 may, for example, be re-initiated.

FIG. 18 shows one embodiment of a cell phone burst that has been configured to embed a device or user's location 1801 between control signals (e.g., synchronization signals) and data signals. Persons skilled in the art will appreciate that some cell phone burst standards (e.g., TDMA and CDMA) have signal portions that are reserved for future technologies. In one embodiment, this reserved portion is utilized to house location information 1801. A cell phone tower or base may then strip received signals 1800 of location information 1801, store location information 1801 into a database or other storage device, and deliver the received signals to its desired location. In this manner, a user may refresh his/her location information every time that a cell phone base station receives or routes information for the user. By stripping location information 1801 from signal 1800, the intended receiver does not have access to the location of the device transmitting signal 1800. A signal similar to signal 1800 may be sent to a cell phone that has requested, and has the appropriate location access rights, to location 1801. Location 1801 may also be stored in other portions of signal 1800 that are not reserved portions. For example, a received signal 1800 may store location information in the data portions of signal 1800. In embodiments where additional information is sent about location 1801 (e.g., a map associated with location 1801) utilizing a main data portion of signal 1800 is preferred. Persons skilled in

13

the art will appreciate that signal burst **1800** may actually be any type of communication signal such as, for example, information returned from a database inquiry.

Persons skilled in the art will also appreciate that the systems and methods of the present invention may be implemented using other locating features and configurations. For example, a user may be manually requested to allow location access rights every time his/her location is requested. As per another example, a user may organize his/her user list into groups and assign access rights to that group (e.g., family member user group, close friend user group). All such modifications are within the scope of the present invention, which is limited only by the claims that follow.

What is claimed is:

1. A method of mobile-to-mobile locating, said method comprising:

requesting a location of a first wireless device by a second wireless device from a server located remotely from said first and second wireless devices;

determining that said second wireless device does not have location access rights for said first wireless device;

asking said second wireless device if said location access rights are to be requested from said first wireless device after determining that said second wireless device does not have said location access rights for said first wireless device;

requesting that said location access rights be assigned for said second wireless device by said first wireless device;

assigning said location access rights on said server to said second wireless device by said first wireless device;

storing said location access rights on said server;

determining said access rights assigned by said first wireless device to said second wireless device on said server; and

providing said location from said server to said second wireless device dependent upon said access rights.

2. The method of claim 1, wherein said first and second wireless devices are cellular phones.

3. The method of claim 1, wherein said location access rights include the ability to obtain said location, wherein said location is provided to said second wireless device from said server even when said first wireless device is OFF.

4. The method of claim 1, wherein said location access rights comprise a plurality of access levels.

5. The method of claim 1, wherein said location is used to provide a location marker on a map on said second wireless device.

6. The method of claim 1, wherein said location is used to provide directions from said second wireless device to said location on said second wireless device.

7. The method of claim 1, wherein said location is used to provide directions from said second wireless device to said location and a travel time on said second wireless device.

8. The method of claim 1, further comprising requesting a second location of said first wireless device and using said location and said second location to determine how fast said first wireless device is traveling.

9. The method of claim 1, wherein said location access rights comprise a plurality of levels of access rights, at least one of said plurality of levels of access rights comprise the exact location of said first wireless device, and another one of said plurality of levels of access rights comprise an approximate location of said first wireless device.

14

10. The method of claim 1, wherein said access rights comprise a plurality of levels of access rights, at least one of said plurality of levels of access rights comprise an approximate location of said first wireless device, and said approximate location comprises a city or state.

11. The method of claim 1, further comprising requesting said location of said first wireless device by a non-wireless device.

12. The method of claim 1, further comprising obtaining a second location from a non-wireless device.

13. The method of claim 1, further comprising receiving a login and password from said second wireless device to identify said second wireless device.

14. The method of claim 1, wherein said location of said first wireless device is requested by receiving input, in the form of a telephone number of said first wireless device, on said second wireless device.

15. The method of claim 1, further comprising using said first wireless device to modify said location access rights for said second wireless device.

16. The method of claim 1, further comprising the ability to use said first wireless device to delete said location access rights for said second wireless device.

17. The method of claim 1, further comprising filtering information about said location such that only a portion of the information is passed to said second wireless device.

18. The method of claim 1, further comprising alerting said second wireless device when said first wireless device is within a distance of second wireless device.

19. The method of claim 1, further comprising selecting said first wireless device from an identifier list.

20. The method of claim 1, further comprising selecting said first wireless device from an identifier list wherein said identifier list comprises a list of telephone numbers.

21. The method of claim 1, further comprising selecting said first wireless device from an identifier list wherein said identifier list comprises a list of user profiles.

22. The method of claim 1, further comprising requesting a second location from said first wireless device from a non-wireless device, wherein said non-wireless device does not comprise a positioning system.

23. The method of claim 1, wherein said location is provided by a positioning system.

24. The method of claim 1, further comprising: providing a first dating matching profile by said first wireless device;

providing a second dating matching profile by said second wireless device;

obtaining a second location, wherein said second location is the location of said second wireless device; and utilizing said location, said second location, said first dating matching profile, and said second dating matching profile to provide an alert.

25. The method of claim 1, further comprising providing a compass in said second wireless device.

26. The method of claim 1, wherein a directional arrow is utilized to display the location of said first wireless device relative to said location of said second wireless device on said second wireless device.

27. The method of claim 1, further comprising providing a compass in said second wireless device, wherein said compass is utilized to display the direction that said second wireless device is traveling in.

28. The method of claim 1, further comprising setting location alerts associated with said first wireless device on said second wireless device.

29. The method of claim 1, wherein said location access rights are only assigned for a period of time.

30. The method of claim 1, further comprising alerting said second wireless device when said first wireless device enters a geographic area. 5

31. The method of claim 1, wherein said server stores a history of locations for said first wireless device.

32. The method of claim 1, wherein said server stores a history of locations for said first wireless device and said history is utilized to provide an approximate location of said first wireless device when said first wireless device is turned OFF. 10

33. The method of claim 1, further comprising displaying on said second wireless device the opportunity to request said location access rights from said first wireless device. 15

34. The method of claim 1, wherein said first wireless device is requested to manually allow said location access rights for said second wireless device every time said second wireless device requests said location.

35. The method of claim 1, wherein one of said location access rights is the ability to not allow said second wireless device to access said location. 20

* * * * *