




US 20130133160A1

(19) **United States**(12) **Patent Application Publication**
Lloyd et al.(10) **Pub. No.: US 2013/0133160 A1**(43) **Pub. Date: May 30, 2013**(54) **GARMENT HANGING ACCESSORY**(52) **U.S. Cl.**USPC **24/303**; 24/327; 24/334; 24/331(76) Inventors: **Nicole Lloyd**, Costa Mesa, CA (US);
Kim Lloyd, Fort Lauderdale, FL (US)

(57)

ABSTRACT

A garment-hanging accessory includes a strip of material having a first end and a second end; and a clip having an engaging end biased into a normally closed position and openable upon application of pressure upon opposing levers at an opposite end of the clip, the levers connected by a spring secured about a fulcrum point between the levers, each end of the strip of material secured to a respective opposite side of each of the opposing levers, opposite ends of each lever, not secured to either of the ends of the strip of material, co-acting to define a garment engaging end when the clip is in its normally closed position. The unsecured portion of the strip opposite the clip is suspended upon a primary garment hanger.

(21) Appl. No.: **13/306,239**(22) Filed: **Nov. 29, 2011****Publication Classification**(51) **Int. Cl.****A44B 11/06** (2006.01)**H01F 7/02** (2006.01)**F16B 2/20** (2006.01)




FIG.1
PRIOR ART




FIG. 5




FIG. 2




FIG. 3




FIG.4




FIG. 8




FIG. 9




FIG. 5A




FIG. 7




FIG. 6

GARMENT HANGING ACCESSORY

AREA OF INVENTION

[0001] The present invention relates to garment hanging accessories and, more particularly, to a garment hanging system adapted to hang upon a primary clothing hanger.

BACKGROUND OF THE INVENTION

[0002] As is well-known to women who wear various types of blouses, tube tops dresses, skirts, undergarments and swimwear, such garments often are provided with so-called hanging loops, the purpose of which is to facilitate the hanging of such garments in one's wardrobe in a manner which is more visible, less wrinkled and therefore functional than simply folding the same and keeping them in a credenza or chest of drawers. There is a wide range of articles of clothing which are today provided with such hanging loops since the design of the original garment does not allow the item to hang correctly on a typical hanger whether it is a blouse, tube top, dress or skirt. Because of the range of articles of clothing which are today provided with such hanging loops, one must either purchase special-purpose types of hangers to use therewith or must attempt to appropriately wrap one or more of the loops of the garment about an otherwise conventional shirt or blouse-type hanger which may or may not itself be provided with hooks, protrusion or regions proportioned to accommodate the loops of such garments.

[0003] Regardless of the manner in which one chooses to suspend or display such garments in one's closet or wardrobe, a remaining and often bothersome issue for many women is that the hanging loops of a given garment, whether it be a blouse, tube top, dress, skirt, lingerie piece or swimsuit, have a potential to work their way outside of the garment where they are typically affixed. When this occurs, the hanging loop may become visible to the public which, to most women, is unwanted, embarrassing, bothersome, and can be skin irritating depending on the material of the loop. The present invention is therefore directed to a group of garment hanging accessories which permit one using the same to simply remove or cut-off the garment straps that have been provided and, thereafter, for purposes of hanging, arrangement and organization within one's wardrobe or closet, to employ the present inventive garment-hanging accessory in conjunction with an otherwise conventional shirt, blouse, tube top, or other general purpose type of hanger.

[0004] The invention is equally applicable to garments not originally provided with such loops as well as for men's slacks to avoid creases once folded over the bottom of a typical hanger.

[0005] The present invention therefore responds to the long-felt need in the art for a garment-hanging accessory of the types set forth herein.

SUMMARY OF THE INVENTION

[0006] A garment-hanging accessory includes a strip of material having a first end and a second end; and a clip having an engaging end biased into a normally closed position and openable upon application of pressure upon opposing levers at an opposite end of said clip, said levers connected by a spring secured about a fulcrum point between said levers, each end of said strip of material secured to a respective opposite side of each of said opposing levers, opposite ends of each lever, not secured to either of said ends of said strip of

material, co-acting to define a garment engaging end when said clip is in said normally closed position. The unsecured portion of the strip opposite the clip is suspended upon a primary garment hanger.

[0007] It is an object of the present invention to provide a garment-hanging accessory which enables a user to dispense with the need for use of otherwise conventional garment hanging loops.

[0008] It is another object to provide an accessory of the above type which permits is the user thereof to remove conventional garment hanging loop from blouses, tube tops, dresses, skirts, swimwear, lingerie and the like and, in lieu hereof, employ a garment-hanging accessory of the type set forth herein, such that the article of clothing may be readily suspended upon an otherwise conventional shirt or blouse-type of hanger.

[0009] It is a further object of the invention, to provide a garment-hanging accessory which provides a means by which multiple garments may be suspended from a single hanger to provide for better coordination and choice of suitable outfits of interests for men and women.

[0010] It is a still further object to provide an accessory of the above type without regard to whether the article of clothing was originally provided with hanging loops.

[0011] The above and yet other objects and advantages of the present invention will become apparent from the hereinafter set forth Brief Description of the Drawings, Detailed Description of the Invention and Claims appended herewith.

BRIEF DESCRIPTION OF THE DRAWINGS

[0012] FIG. 1 is a representational view of one type of a garment provided with conventional garment-hanging loops. Various other garments are similarly provided with conventional hanging loops.

[0013] FIG. 2 is a perspective view of a first embodiment of the present inventive garment-hanging accessory.

[0014] FIG. 3 is an enlarged view of a left hand portion of FIG. 2.

[0015] FIG. 4 is an operational view of the present invention showing the use of the embodiment of FIG. 2 used in conjunction with a conventional shirt or blouse-type hanger in which the clip elements thereof are attached to the waistline of the suspended garment.

[0016] FIG. 5 is a representational view of a second embodiment of the invention.

[0017] FIG. 5A is a cross-sectional view taken along Line 5A-5a of FIG. 5.

[0018] FIG. 6 is a view of a third embodiment of the invention in which the strap portion thereof is suspended by passage thereof through a slot or opening within the levers of the clip of the present invention.

[0019] FIG. 7 is a side elevational view of a shirt or blouse hanger upon which two pairs of accessories of the embodiment of FIG. 5 have been suspended upon the hanger, illustrating the manner in which four articles of clothing may be suspended upon a typical shirt or blouse hanger.

[0020] FIG. 8 is a view, further to that of FIG. 5, showing the manner in which a zip-tie may be employed, in lieu of a bra strap adjuster, to reduce the length of a strap used in the present system.

[0021] FIG. 9 is a perspective view of a fourth embodiment of the invention in which magnets of opposing polarity may

be used in lieu of clips for purposes of securement to an article of clothing to be suspended, in any of the preceding embodiments.

DETAILED DESCRIPTION OF THE INVENTION

[0022] With reference to FIG. 1, there is shown a typical prior art female garment as, for example, a skirt **10**, or under skirt, provided with loops **12** which are typically connected at the inside of waistlines **34** of the skirt at area **14**. As above noted, loops of this type are common in many types of women's garments for purposes of facilitating the hanging thereof upon special-purpose hangers that may be purchased for such purpose. Also, loops **12** may be positioned differently on different types of clothing, including tube tops. In most cases, the loops of such garments, during the wearing thereof, possesses a tendency to pull-out from beneath the waist line where they are typically positioned during the normal use and thereupon often become visible, causing potential embarrassment and annoyance to the user.

[0023] In the practice of the present invention, such loops **12** are cut from the garment **10** after the purchase thereof and, in lieu of such loops, there is provided a structure **16** of the types shown in FIGS. 2 and 3 in which is shown a first embodiment of the present invention. It is noted that the present invention is equally of value in the hanging of garments, such as underwear, not originally provided with any loops.

[0024] The inventive garment hanging accessory includes a strip of material **18** having ends **20** and **22** thereof which are secured to respectively opposing surfaces of levers **24** and **26** of a clip **28** which are biased into a normally closed position by a spring **30**, an end of which is shown in FIGS. 2 and 3. This spring may for example comprise a coil spring such that engagement ends **32** of clip **28** is normally closed, in the manner shown in FIGS. 2 and 3 and is openable upon application of pressure upon said opposing levers **24** and **26**. In effect, spring **30** biases levers **24** and **26** about a fulcrum point **23** of the structure and co-acts with said levers and garment engaging ends **32** of the clip to secure a garment of interest in, for example, the manner shown in FIG. 4 opposite to clip end of strap **18** is hanging end **40** of the accessory. Therefrom, it may be appreciated that a garment such as skirt **10** or nearly any other female garment may be readily secured and suspended through the use of two of the structures shown in FIG. 2, in which engagement ends **32** of the clip **28** are secured to garment **10A** at or near waistline **34** of the garment and from hanging end **40**.

[0025] FIG. 4 therefore shows a garment hanger **36**, such as a shirt or blouse hanger, this inclusive of a sub-hanger area **38** upon which ends **40** of straps **18** are then hung. However, it is to be understood that straps **18** may be hung upon the is hanger from area **42** of the hanger or any other area as well, and on hangers of other configurations, from any part of any hanger that the loop of strip **18** may be placed in or over, without unbalancing the hanger. This enables pants to be hung on shirt-type or other hangers. It is also to be understood that multiple pairs of the present garment hanging accessory **16** may be hung about different parts of a given hanger **36**, as is discussed below relative to FIG. 7.

[0026] In FIG. 5 is shown a further embodiment **116** of the present invention in which clips **128** and **129** are provided at each end of a strip **118** and in which a bra length adjuster element **144** is also employed. It is to be understood that adjuster element **144** would typically be used on both sides of

strap **118** and, additionally, may be readily employed within strip **18** shown in FIGS. 2 and 3. The benefit of the provision of clips **128/129** at each end of strips **118** and **119** is that it enables the hanging of a large number of smaller garments **110** and **111** in the manner shown in FIG. 7.

[0027] Shown in FIG. 5A is a cross-section taken along Line 5A-5A of FIG. 5, indicating that an anti-strip surface **121** may be provided to the underside of strip **118** and to any strip used in the present invention, particularly at the area of contact with a primary hanger **36**. See FIG. 4.

[0028] With reference to the side elevational view of FIG. 6, there is shown a further embodiment **216** of a clip **228** which may be advantageously employed in the practice of the invention. Said clip, like that of earlier embodiments may be provided with padding **246** upon the inner surfaces of forward end **232**, or that of the forward ends of any of the above-described embodiments of clip **23** or **123**. Further, and particularly to the embodiment of FIG. 6, lever **224** and **226** are shown to include openings **248** within levers **224** and **226** of clip **228** such that strap **218** may pass through opening **248**, this as opposed to the securement of end **27** (see FIG. 3) of strip **18** to each inner surface of levers **24** and **26** of clip **28**. Where this embodiment is employed, a loop may be formed of strip **218** after ends thereof have passed through opening **248** of levers **224** and **226**. Alternatively, opposite ends of strips **218** and **219** may then be fastened together to form the embodiment shown in FIG. 2 or provided with a clip similar to clip **228**, in the manner shown in the embodiment of FIG. 5.

[0029] In FIG. 8 is shown the use of a zip tie **50** in applications where one wishes to shorten or adjust the length of strip **18**, **118**, or **218**. As such, tie **50** may be viewed as an equivalent of bra strap adjuster **144** that may as such be employed in any embodiment of the present invention.

[0030] Shown in FIG. 9 is a further embodiment **316** of the invention in which magnets **323** and **325** of opposite polarity are used in combination in lieu of the clips **28** shown in the embodiment of FIG. 2 with strap **318** shown therebetween. It is to be appreciated that magnets **323** and **325** may be employed in lieu of clips in any of the embodiments described above.

[0031] While there has been shown and described above the preferred embodiment of the instant invention it is to be appreciated that the invention may be embodied otherwise than is herein specifically shown and described and that, within said embodiment, certain changes may be made in the form and arrangement of the parts without departing from the underlying ideas or principles of this invention as set forth in the Claims appended herewith.

We claim:

1. A garment-hanging accessory, comprising:

- (a) a strip of material having a first end and a second end; and
- (b) a clip having an engaging end biased into a normally closed position and openable upon application of pressure upon opposing levers at an opposite end of said clip, said levers connected by a spring secured about a fulcrum point between said levers, each end of said strip of material secured to a respective opposite side of each of said opposing levers, opposite ends of each lever, not secured to either of said ends of said strip of material, co-acting to define a garment engaging end when said clip is in said normally closed position.

2. The garment-hanging accessory as recited in claim 1, in which said spring comprises a coil spring.

3. The garment-hanging accessory as recited in claim 1, in which said strip comprises an expansible material.

4. the garment-hanging accessory as recited in claim 1, in which each inner side of said garment-engaging end includes a padded surface.

5. The garment-hanging accessory as recited in claim 1, in which said strip of material includes at least one length-adjusting element.

6. The garment-hanging accessory as recited in claim 5, in which said length adjusting element comprises a bra-strap length adjuster.

7. The garment-hanging accessory as recited in claim 5, in which said length adjusting element comprises a zip tie.

8. A garment-hanging accessory comprising:

(a) two strips of material configured into the general geometry of an elongate loop; and

(b) a first clip and a second clip, said first clip secured at a first end of said loop and said second clip secured at a second end of said loop, each of said clips having an engaging end and biased into a normally closed position and openable upon application of pressure upon opposing levers at opposite ends of each clip, said levers connected by a spring secured about a fulcrum point between said levers, each end of said elongate loop of said strip of material secured to an end of said clip opposite to said garment engaging end, said levers of each clip co-acting to define said garment engaging end thereof when either of said clips is in its said normally closed position.

9. The garment-hanging accessory as recited in claim 8, in which each inner side of each engaging end of said clips includes a padded surface.

10. The garment-hanging accessory as recited in claim 8, in which said spring comprises a coil spring.

11. The garment-hanging accessory as recited in claim 8, in which said strip is expansible.

12. The garment-hanging accessory as recited in claim 8, in which said strip of material includes at least one length-adjusting element.

13. The garment-hanging accessory as recited in claim 12, in which said length adjusting element comprises a bra-strap length adjuster.

14. The garment-hanging accessory as recited in claim 12, in which said length adjusting element comprises a zip tie.

15. A garment-hanging accessory, comprising:

(a) a strip of material having a first end and a second end; and

(b) a magnet of a first polarity secured to said first end, and a magnet of an opposite polarity secured to said second end,

whereby contact between said magnets creates an element for engaging a garment to be secured.

16. The garment-hanging accessory as recited in claim 14, in which each inner side of said garment-engaging end includes a padded surface.

17. The garment-hanging accessory as recited in claim 14, in which said strip of material includes at least one length-adjusting element.

18. The garment-hanging accessory as recited in claim 17, in which said length adjusting element comprises a bra-strap length adjuster.

19. The garment-hanging accessory as recited in claim 17, in which said length adjusting element comprises a zip tie.

20. The accessory as recited in claim 1, in which a portion of a side of said strip of material in contact with a primary garment-hanging accessory is provided with an anti-slip surface.

* * * * *