



US007681034B1

(12) **United States Patent**
Lee et al.

(10) **Patent No.:** **US 7,681,034 B1**
(45) **Date of Patent:** **Mar. 16, 2010**

(54) **METHOD AND APPARATUS FOR SECURING
ELECTRONIC DATA**

FOREIGN PATENT DOCUMENTS

EP 0 672 991 A2 9/1995

(76) Inventors: **Chang-Ping Lee**, 765 San Antonio Rd.,
Apt. 65, Palo Alto, CA (US) 94303;
Denis Jacques Paul Garcia, 696 Towle
Way, Apt. 33, Palo Alto, CA (US) 94306

(Continued)

OTHER PUBLICATIONS

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 1407 days.

U.S. Appl. No. 10/076,254, filed Feb. 12, 2002, Alain Rossmann,
Method and Architecture for Providing Pervasive Security to Digital
Assets.

(21) Appl. No.: **10/074,996**

(Continued)

(22) Filed: **Feb. 12, 2002**

Primary Examiner—Christopher A Revak
(74) *Attorney, Agent, or Firm*—Sterne Kessler Goldstein &
Fox PLLC

Related U.S. Application Data

(60) Provisional application No. 60/339,634, filed on Dec.
12, 2001.

(57) **ABSTRACT**

(51) **Int. Cl.**
G06F 21/22 (2006.01)
H04L 9/00 (2006.01)
H04K 1/00 (2006.01)

(52) **U.S. Cl.** **713/164**; 713/160; 713/189;
726/26; 705/51

(58) **Field of Classification Search** None
See application file for complete search history.

(56) **References Cited**


U.S. PATENT DOCUMENTS

4,203,166	A	5/1980	Ehram et al.	
4,734,568	A	3/1988	Watanabe	
4,757,533	A	7/1988	Allen et al.	
4,796,220	A	1/1989	Wolfe	
4,799,258	A	1/1989	Davies	380/21
4,827,508	A	5/1989	Shear	

Techniques for securing electronic data and keeping the elec-
tronic data secured at all times are disclosed. According to
one embodiment, a client module in a client machine is con-
figured to provide access control to secured documents that
may be located in a local store, another computer machine or
somewhere over a data network. The client module includes a
document-securing module configured to operate in a path
through which a document being accessed is caused to pass so
that the document can be examined or detected for the secu-
rity nature. If the document is secured, the document-secu-
ring module obtains a user or group key to decrypt security
information in the secured document for access rules therein.
If a user accessing the document is determined to have the
access privilege to the secured document, a file key is
retrieved from the security information and a cipher module is
activated to decrypt the encrypted data portion with the file
key. Likewise, if a document is to be secured, the cipher
module encrypts clear data from the document to create the
encrypted data portion. The document-securing module inte-
grates proper or desired security information with the
encrypted data portion to produce the secured document.

(Continued)

52 Claims, 30 Drawing Sheets



US 7,681,034 B1

Page 2

U.S. PATENT DOCUMENTS

4,888,800	A	12/1989	Marshall et al.	5,968,177	A	10/1999	Batten-Carew et al.
4,972,472	A	11/1990	Brown et al.	5,970,502	A	10/1999	Salkewicz et al.
5,032,979	A	7/1991	Hecht et al.	5,987,440	A	11/1999	O'Neil et al. 705/44
5,052,040	A	9/1991	Preston et al.	5,991,879	A	11/1999	Still
5,058,164	A	10/1991	Elmer et al.	5,999,907	A	12/1999	Donner
5,144,660	A	9/1992	Rose	6,014,730	A	1/2000	Ohtsu
5,204,897	A	4/1993	Wyman	6,023,506	A	2/2000	Ote et al.
5,220,657	A	6/1993	Bly et al.	6,032,216	A	2/2000	Schmuck et al.
5,235,641	A	8/1993	Nozawa et al.	6,038,322	A	3/2000	Harkins
5,247,575	A	9/1993	Sprague et al.	6,044,155	A	3/2000	Thomlinson et al.
5,276,735	A	1/1994	Boebert et al. 380/21	6,055,314	A	4/2000	Spies et al.
5,301,247	A	4/1994	Rasmussen et al.	6,058,424	A	5/2000	Dixon et al.
5,319,705	A	6/1994	Halter et al.	6,061,790	A	5/2000	Bodnar
5,369,702	A	11/1994	Shanton	6,069,057	A	5/2000	Wu
5,375,169	A	12/1994	Seheidt et al.	6,085,323	A	7/2000	Shimizu et al.
5,404,404	A	4/1995	Novorita	6,088,717	A	7/2000	Reed et al. 709/201
5,406,628	A	4/1995	Beller et al.	6,088,805	A	7/2000	Davis et al. 713/202
5,414,852	A	5/1995	Kramer et al.	6,098,056	A	8/2000	Rusnak et al. 705/75
5,495,533	A	2/1996	Linehan et al.	6,101,507	A	8/2000	Cane et al.
5,499,297	A	3/1996	Boebert 380/23	6,105,131	A	8/2000	Carroll
5,502,766	A	3/1996	Boebert et al. 380/25	6,122,630	A	9/2000	Strickler et al.
5,535,375	A	7/1996	Eshel et al.	6,134,327	A	10/2000	Van Oorschot
5,557,765	A	9/1996	Lipner et al.	6,134,658	A	10/2000	Multerer et al.
5,570,108	A	10/1996	McLaughlin et al.	6,134,660	A	10/2000	Boneh et al.
5,584,023	A	12/1996	Hsu	6,134,664	A	10/2000	Walker
5,600,722	A	2/1997	Yamaguchi et al. 380/21	6,141,754	A	10/2000	Choy
5,606,663	A	2/1997	Kadooka	6,145,084	A	11/2000	Zuili
5,655,119	A	8/1997	Davy	6,158,010	A	12/2000	Moriconi et al. 713/201
5,661,806	A	8/1997	Nevoux et al.	6,161,139	A	12/2000	Win et al. 709/229
5,671,412	A	9/1997	Christiano	6,182,142	B1	1/2001	Win et al. 709/229
5,673,316	A	9/1997	Auerbach et al.	6,185,684	B1	2/2001	Pravetz et al.
5,677,953	A	10/1997	Dolphin	6,192,408	B1	2/2001	Vahalia et al.
5,680,452	A	10/1997	Shanton	6,205,549	B1	3/2001	Pravetz et al.
5,684,987	A	11/1997	Mamiya et al.	6,212,561	B1	4/2001	Sitaraman et al.
5,689,718	A	11/1997	Sakurai et al.	6,223,285	B1	4/2001	Komuro et al.
5,699,428	A	12/1997	McDonnal et al.	6,226,618	B1	5/2001	Downs et al.
5,708,709	A	1/1998	Rose	6,226,745	B1	5/2001	Wiederhold 713/200
5,715,403	A	2/1998	Stefik	6,240,188	B1	5/2001	Dondeti et al.
5,717,755	A	2/1998	Shanton	6,249,873	B1	6/2001	Richard et al. 713/200
5,720,033	A	2/1998	Deo	6,253,193	B1	6/2001	Ginter et al.
5,729,734	A	3/1998	Parker et al.	6,260,040	B1	7/2001	Kauffman et al.
5,732,265	A	3/1998	Dewitt et al.	6,260,141	B1	7/2001	Park
5,745,573	A	4/1998	Lipner et al. 380/21	6,263,348	B1	7/2001	Kathrow et al.
5,748,736	A	5/1998	Mittra	6,272,631	B1	8/2001	Thomlinson et al. 713/155
5,751,287	A	5/1998	Hahn et al.	6,272,632	B1	8/2001	Carmen et al. 713/168
5,757,920	A	5/1998	Misra et al.	6,282,649	B1	8/2001	Lambert et al.
5,765,152	A	6/1998	Erickson	6,289,450	B1	9/2001	Pensak et al. 713/167
5,778,065	A	7/1998	Hauser et al.	6,292,895	B1	9/2001	Baltzley
5,787,169	A	7/1998	Eldridge et al.	6,292,899	B1	9/2001	McBride
5,787,173	A	7/1998	Seheidt et al.	6,295,361	B1	9/2001	Kadansky et al.
5,787,175	A	7/1998	Carter	6,301,614	B1	10/2001	Najork et al.
5,790,789	A	8/1998	Suarez	6,308,256	B1	10/2001	Folmsbee
5,790,790	A	8/1998	Smith et al.	6,308,273	B1	10/2001	Goertzel et al.
5,813,009	A	9/1998	Johnson et al.	6,314,409	B2	11/2001	Schneck et al. 705/54
5,821,933	A	10/1998	Keller et al.	6,317,777	B1	11/2001	Skarbo et al.
5,825,876	A	10/1998	Peterson	6,332,025	B2	12/2001	Takahashi et al.
5,835,592	A	11/1998	Chang et al.	6,336,114	B1	1/2002	Garrison
5,835,601	A	11/1998	Shimbo et al.	6,339,423	B1	1/2002	Sampson et al.
5,857,189	A	1/1999	Riddle	6,339,825	B2	1/2002	Pensak et al. 713/158
5,862,325	A	1/1999	Reed et al. 395/200.31	6,341,164	B1	1/2002	Dilkie et al.
5,870,468	A	2/1999	Harrison	6,343,316	B1	1/2002	Sakata
5,870,477	A	2/1999	Sasaki et al.	6,347,374	B1	2/2002	Drake et al.
5,881,287	A	3/1999	Mast	6,349,337	B1	2/2002	Parsons et al.
5,892,900	A	4/1999	Ginter et al.	6,351,813	B1	2/2002	Mooney et al.
5,893,084	A	4/1999	Morgan et al.	6,356,903	B1	3/2002	Baxter et al.
5,898,781	A	4/1999	Shanton	6,356,941	B1	3/2002	Cohen
5,922,073	A	7/1999	Shimada	6,357,010	B1	3/2002	Viets et al.
5,923,754	A	7/1999	Angelo et al.	6,363,480	B1	3/2002	Perlman
5,933,498	A	8/1999	Schneck et al. 380/4	6,370,249	B1	4/2002	Van Oorschot
5,944,794	A	8/1999	Okamoto et al.	6,381,698	B1	4/2002	Devanbu et al.
5,953,419	A	9/1999	Lohstroh et al.	6,389,433	B1	5/2002	Bolosky et al.
				6,389,538	B1	5/2002	Gruse et al.
				6,393,420	B1	5/2002	Peters

US 7,681,034 B1

Page 3

6,405,315 B1	6/2002	Burns et al.	6,931,530 B2	8/2005	Pham et al.
6,421,714 B1	7/2002	Rai et al.	6,931,597 B1 *	8/2005	Prakash 715/741
6,442,688 B1	8/2002	Moses et al.	6,938,042 B2	8/2005	Aboulhosn et al.
6,442,695 B1	8/2002	Dutcher et al.	6,941,355 B1	9/2005	Donaghey et al.
6,446,090 B1	9/2002	Hart	6,941,456 B2	9/2005	Wilson
6,449,721 B1	9/2002	Pensak et al.	6,941,472 B2	9/2005	Moriconi et al.
6,453,353 B1	9/2002	Win et al.	6,944,183 B1	9/2005	Iyer et al.
6,466,932 B1	10/2002	Dennis et al.	6,947,556 B1	9/2005	Matyas, Jr. et al.
6,477,544 B1	11/2002	Bolosky et al.	6,950,818 B2	9/2005	Dennis et al.
6,490,680 B1	12/2002	Scheidt et al.	6,950,936 B2	9/2005	Subramaniam et al.
6,505,300 B2	1/2003	Chan et al.	6,950,941 B1	9/2005	Lee et al.
6,510,349 B1	1/2003	Schneck et al.	6,950,943 B1	9/2005	Bacha et al.
6,519,700 B1	2/2003	Ram et al.	6,952,780 B2	10/2005	Olsen et al.
6,529,956 B1	3/2003	Smith et al.	6,957,261 B2	10/2005	Lortz
6,530,020 B1	3/2003	Aoki	6,959,308 B2	10/2005	Gramsamer et al.
6,530,024 B1	3/2003	Proctor	6,961,849 B1	11/2005	Davis et al.
6,542,608 B2	4/2003	Scheidt et al.	6,968,060 B1	11/2005	Pinkas
6,549,623 B1	4/2003	Scheidt et al.	6,971,018 B1	11/2005	Witt et al.
6,550,011 B1	4/2003	Sims	6,978,376 B2	12/2005	Giroux et al.
6,557,039 B1	4/2003	Leong et al.	6,978,377 B1	12/2005	Asano et al.
6,567,914 B1	5/2003	Just et al.	6,988,133 B1	1/2006	Zavalkovsky et al.
6,571,291 B1	5/2003	Chow	6,988,199 B2	1/2006	Toh et al.
6,584,466 B1	6/2003	Serbinis et al.	6,993,135 B2	1/2006	Ishibashi
6,587,946 B1	7/2003	Jakobsson	6,996,718 B1	2/2006	Henry et al.
6,588,673 B1	7/2003	Chan et al.	7,003,117 B2	2/2006	Kacker et al.
6,594,662 B1	7/2003	Sieffert et al.	7,003,560 B1	2/2006	Mullen et al.
6,598,161 B1	7/2003	Kluttz et al.	7,003,661 B2	2/2006	Beattie et al.
6,603,857 B1	8/2003	Batten-Carew et al.	7,010,809 B2 *	3/2006	Hori et al. 726/26
6,608,636 B1	8/2003	Roseman	7,013,332 B2	3/2006	Friedel et al.
6,611,599 B2	8/2003	Natarajan	7,013,485 B2	3/2006	Brown et al.
6,611,846 B1	8/2003	Stoodley	7,020,645 B2	3/2006	Bisbee et al.
6,615,349 B1	9/2003	Hair	7,024,427 B2	4/2006	Bobbitt et al.
6,615,350 B1	9/2003	Schell et al.	7,035,854 B2	4/2006	Hsiao et al.
6,625,650 B2	9/2003	Stelliga	7,035,910 B1	4/2006	Dutta et al.
6,629,243 B1	9/2003	Kleinman et al.	7,046,807 B2 *	5/2006	Hirano et al. 380/234
6,633,311 B1	10/2003	Douvikas et al.	7,051,213 B1	5/2006	Kobayashi et al.
6,640,307 B2	10/2003	Viets et al.	7,058,696 B1	6/2006	Phillips et al.
6,646,515 B2	11/2003	Jun et al.	7,058,978 B2	6/2006	Feuerstein et al.
6,647,388 B2	11/2003	Numao et al.	7,073,063 B2	7/2006	Peinado
6,678,835 B1	1/2004	Shah et al.	7,073,073 B1	7/2006	Nonaka et al.
6,687,822 B1	2/2004	Jakobsson	7,076,067 B2	7/2006	Raike et al.
6,711,683 B1 *	3/2004	Laczko et al. 713/189	7,076,312 B2	7/2006	Law et al.
6,718,361 B1	4/2004	Basani et al.	7,076,469 B2	7/2006	Schreiber et al.
6,735,701 B1	5/2004	Jacobson	7,076,633 B2	7/2006	Tormasov et al.
6,738,908 B1	5/2004	Bonn et al.	7,080,077 B2	7/2006	Ramamurthy et al.
6,775,779 B1 *	8/2004	England et al. 726/26	7,095,853 B2	8/2006	Morishita
6,782,403 B1	8/2004	Kino et al.	7,096,266 B2	8/2006	Lewin et al.
6,801,999 B1	10/2004	Venkatesan et al.	7,099,926 B1	8/2006	Ims et al.
6,807,534 B1	10/2004	Erickson	7,104,416 B2	9/2006	Stuart et al.
6,807,636 B2	10/2004	Hartman et al.	7,107,269 B2	9/2006	Arlein et al.
6,810,389 B1	10/2004	Meyer	7,117,322 B2	10/2006	Hochberg et al.
6,810,479 B1	10/2004	Barlow et al.	7,120,635 B2	10/2006	Bhide et al.
6,816,871 B2	11/2004	Lee	7,120,757 B2	10/2006	Tsuge
6,826,698 B1	11/2004	Minkin et al.	7,124,164 B1	10/2006	Chemtob
6,834,333 B2	12/2004	Yoshino et al.	7,130,964 B2	10/2006	Ims et al.
6,834,341 B1	12/2004	Bahl et al.	7,131,071 B2	10/2006	Gune et al.
6,845,452 B1	1/2005	Roddy et al.	7,134,041 B2	11/2006	Murray et al.
6,851,050 B2	2/2005	Singhal et al.	7,136,903 B1	11/2006	Phillips et al.
6,862,103 B1 *	3/2005	Miura et al. 358/1.15	7,145,898 B1	12/2006	Elliott
6,865,555 B2 *	3/2005	Novak 705/59	7,146,388 B2	12/2006	Stakutis et al.
6,874,139 B2 *	3/2005	Krueger et al. 717/127	7,146,498 B1	12/2006	Takechi et al.
6,877,136 B2	4/2005	Bess et al.	7,159,036 B2	1/2007	Hinchliffe et al.
6,889,210 B1 *	5/2005	Vainstein 705/57	7,171,557 B2	1/2007	Kallahalla et al.
6,891,953 B1	5/2005	DeMello et al.	7,174,563 B1	2/2007	Brownlie et al.
6,892,201 B2	5/2005	Brown et al.	7,177,427 B1	2/2007	Komuro et al.
6,892,306 B1	5/2005	En-Seung et al.	7,178,033 B1	2/2007	Garcia
6,907,034 B1 *	6/2005	Begis 370/354	7,181,017 B1	2/2007	Nagel et al.
6,909,708 B1	6/2005	Krishnaswamy et al.	7,185,364 B2	2/2007	Knouse et al.
6,915,434 B1	7/2005	Kuroda et al.	7,187,033 B2	3/2007	Pendharkar
6,920,558 B2	7/2005	Sames et al.	7,188,181 B1	3/2007	Squier et al.
6,922,785 B1 *	7/2005	Brewer et al. 713/153	7,194,764 B2	3/2007	Martherus et al.
6,924,425 B2 *	8/2005	Naples et al. 84/609	7,200,747 B2	4/2007	Riedel et al.
6,931,450 B2	8/2005	Howard et al.	7,203,317 B2	4/2007	Kallahalla et al.

US 7,681,034 B1

Page 4

7,203,968	B2	4/2007	Asano et al.	2003/0046238	A1	3/2003	Nonaka et al.
7,219,230	B2	5/2007	Riedel et al.	2003/0050919	A1	3/2003	Brown et al.
7,224,795	B2	5/2007	Takada et al.	2003/0051039	A1	3/2003	Brown et al.
7,225,256	B2	5/2007	Villavicencio	2003/0056139	A1	3/2003	Murray et al.
7,227,953	B2	6/2007	Shida	2003/0074580	A1	4/2003	Knouse et al.
7,233,948	B1	6/2007	Shamoon et al.	2003/0078959	A1	4/2003	Yeung et al.
7,237,002	B1	6/2007	Estrada et al.	2003/0079175	A1	4/2003	Limantsev
7,249,044	B2	7/2007	Kumar et al.	2003/0081784	A1	5/2003	Kallahalla et al.
7,260,555	B2	8/2007	Rossmann et al.	2003/0081787	A1	5/2003	Kallahalla et al.
7,265,764	B2	9/2007	Alben et al.	2003/0088517	A1	5/2003	Medoff
7,266,684	B2	9/2007	Jancula	2003/0088783	A1	5/2003	DiPierro
7,280,658	B2	10/2007	Amini et al.	2003/0101072	A1	5/2003	Dick et al.
7,287,055	B2	10/2007	Cannata et al.	2003/0110169	A1	6/2003	Zuili
7,290,148	B2	10/2007	Tozawa et al.	2003/0110266	A1	6/2003	Rollins et al.
7,308,702	B1	12/2007	Thomsen et al.	2003/0110397	A1	6/2003	Supramaniam
7,313,824	B1	12/2007	Bala et al.	2003/0115146	A1	6/2003	Lee et al.
7,319,752	B2	1/2008	Asano et al.	2003/0115218	A1	6/2003	Bobbitt et al.
7,380,120	B1	5/2008	Garcia	2003/0115570	A1	6/2003	Bisceglia
7,383,586	B2	6/2008	Cross et al.	2003/0120601	A1	6/2003	Ouye
7,386,529	B2	6/2008	Kiessig et al.	2003/0120684	A1	6/2003	Zuili et al.
7,461,405	B2 *	12/2008	Boudreault et al. 726/27	2003/0126434	A1	7/2003	Lim et al.
2001/0011254	A1	8/2001	Clark	2003/0154381	A1	8/2003	Ouye
2001/0021255	A1	9/2001	Ishibashi	2003/0159066	A1	8/2003	Staw et al.
2001/0021926	A1	9/2001	Schneck et al.	2003/0177070	A1	9/2003	Viswanath et al.
2001/0023421	A1	9/2001	Numao et al.	2003/0177378	A1	9/2003	Wittkotter
2001/0032181	A1	10/2001	Jakstadt et al.	2003/0182579	A1	9/2003	Leporini et al.
2001/0034839	A1	10/2001	Karjoth et al.	2003/0196096	A1	10/2003	Sutton
2001/0044903	A1	11/2001	Yamamoto et al.	2003/0197729	A1	10/2003	Denoue et al.
2001/0056550	A1	12/2001	Lee	2003/0200202	A1	10/2003	Hsiao et al.
2002/0010679	A1	1/2002	Felsher	2003/0217264	A1	11/2003	Martin et al.
2002/0016921	A1	2/2002	Olsen et al.	2003/0217333	A1	11/2003	Smith et al.
2002/0016922	A1	2/2002	Richards et al.	2003/0226013	A1	12/2003	Dutertre
2002/0031230	A1	3/2002	Sweet et al.	2003/0233650	A1	12/2003	Zaner et al.
2002/0035624	A1	3/2002	Kim	2004/0022390	A1	2/2004	McDonald et al.
2002/0042756	A1	4/2002	Kumar et al.	2004/0025037	A1	2/2004	Hair
2002/0046350	A1	4/2002	Lordemann et al.	2004/0039781	A1	2/2004	LaVallee et al.
2002/0050098	A1	5/2002	Chan	2004/0064710	A1	4/2004	Vainstein
2002/0056042	A1	5/2002	Van Der Kaay et al.	2004/0068524	A1	4/2004	Aboulhosn et al.
2002/0062240	A1	5/2002	Morinville	2004/0068664	A1	4/2004	Nachenberg et al.
2002/0062245	A1	5/2002	Niu et al.	2004/0073718	A1	4/2004	Johannessen et al.
2002/0069077	A1	6/2002	Brophy et al.	2004/0088548	A1	5/2004	Smetters et al.
2002/0069272	A1	6/2002	Kim et al.	2004/0098580	A1	5/2004	DeTreville
2002/0069363	A1	6/2002	Winburn	2004/0103202	A1	5/2004	Hildebrand et al.
2002/0073320	A1	6/2002	Rinkevich et al.	2004/0103280	A1	5/2004	Balfanz et al.
2002/0077986	A1	6/2002	Kobata et al.	2004/0133544	A1	7/2004	Kiessig et al.
2002/0077988	A1	6/2002	Sasaki et al.	2004/0158586	A1	8/2004	Tsai
2002/0087479	A1	7/2002	Malcolm	2004/0193602	A1	9/2004	Liu et al.
2002/0099947	A1	7/2002	Evans	2004/0193905	A1	9/2004	Lirov et al.
2002/0124180	A1	9/2002	Hagman	2004/0193912	A1	9/2004	Li et al.
2002/0129235	A1	9/2002	Okamoto et al.	2004/0199514	A1	10/2004	Rosenblatt et al.
2002/0133699	A1	9/2002	Pueschel	2004/0215956	A1	10/2004	Venkatachary et al.
2002/0138762	A1	9/2002	Horne	2004/0215962	A1	10/2004	Douceur et al.
2002/0143710	A1	10/2002	Liu	2004/0243853	A1	12/2004	Swander et al.
2002/0143906	A1	10/2002	Tormasov et al.	2005/0021467	A1	1/2005	Franzdonk
2002/0156726	A1	10/2002	Kleckner et al.	2005/0021629	A1	1/2005	Cannata et al.
2002/0157016	A1	10/2002	Russell et al.	2005/0028006	A1	2/2005	Leser et al.
2002/0162104	A1	10/2002	Raike et al.	2005/0039034	A1	2/2005	Doyle et al.
2002/0169963	A1	11/2002	Seder et al.	2005/0071275	A1	3/2005	Vainstein et al.
2002/0169965	A1	11/2002	Hale et al.	2005/0071657	A1	3/2005	Ryan
2002/0172367	A1	11/2002	Mulder et al.	2005/0071658	A1	3/2005	Nath et al.
2002/0174109	A1	11/2002	Chandy et al.	2005/0081029	A1	4/2005	Thornton et al.
2002/0176572	A1	11/2002	Ananth	2005/0086531	A1	4/2005	Kenrich
2002/0178271	A1	11/2002	Graham et al.	2005/0091484	A1	4/2005	Thornton et al.
2002/0194484	A1	12/2002	Bolosky et al.	2005/0120199	A1	6/2005	Carter
2002/0198798	A1	12/2002	Ludwig et al.	2005/0138371	A1	6/2005	Supramaniam
2003/0009685	A1	1/2003	Choo et al.	2005/0138383	A1	6/2005	Vainstein
2003/0014391	A1	1/2003	Evans et al.	2005/0177716	A1	8/2005	Ginter et al.
2003/0023559	A1	1/2003	Choi et al.	2005/0177858	A1	8/2005	Ueda
2003/0028610	A1	2/2003	Pearson	2005/0198326	A1	9/2005	Schlimmer et al.
2003/0033528	A1	2/2003	Ozog et al.	2005/0223242	A1	10/2005	Nath
2003/0037133	A1	2/2003	Owens	2005/0223414	A1	10/2005	Kenrich et al.
2003/0037237	A1	2/2003	Abgrall et al.	2005/0235154	A1	10/2005	Serret-Avila
2003/0037253	A1	2/2003	Blank et al.	2005/0256909	A1	11/2005	Aboulhosn et al.

2005/0273600	A1	12/2005	Seeman
2005/0283610	A1	12/2005	Serret-Avila et al.
2005/0288961	A1	12/2005	Tabrizi
2006/0005021	A1	1/2006	Torrubia-Saez
2006/0075465	A1	4/2006	Ramanathan et al.
2006/0093150	A1	5/2006	Reddy et al.
2006/0168147	A1	7/2006	Inoue et al.
2006/0230437	A1	10/2006	Boyer et al.
2007/0006214	A1	1/2007	Dubal et al.
2007/0067837	A1	3/2007	Schuster

FOREIGN PATENT DOCUMENTS

EP	0 674 253	A1	9/1995
EP	0 809 170	A1	11/1997
EP	0 913 966	A2	5/1999
EP	0 913 967	A2	5/1999
EP	0 950 941	A2	10/1999
EP	0 950 941	A3	10/1999
EP	1 107 504	B1	6/2001
EP	1 107504	A2	6/2001
EP	1 130 492	A2	9/2001
EP	1 154 348	A2	11/2001
EP	1324565	A1	7/2003
GB	2 328 047	A	2/1999
JP	2001-036517		2/2001
WO	WO 96/41288	A1	12/1996
WO	WO 00/56028		9/2000
WO	WO 01/61438	A2	8/2001
WO	WO 01/63387	A2	8/2001
WO	WO 01/63387	A3	8/2001
WO	WO 01/77783	A2	10/2001
WO	WO 01/78285	A1	10/2001
WO	WO 01/84271	A2	11/2001

OTHER PUBLICATIONS

"Expiration Mechanism for Chipcards," IBM Technical Disclosure Bulletin, Oct. 1, 2001, UK.

McDaniel et al., "Antigone: A Flexible Framework for Secure Group Communication," Proceedings of the 8th USENIX Security Symposium, Aug. 23, 1999.

"Inside Encrypting File System", Part 1, from MSDN Oct. 2001 version, exact publication date is unknown but believed prior to Dec. 12, 2001.

"Inside Encrypting File System", Part 2, from MSDN Oct. 2001 version, exact publication date is unknown but believed prior to Dec. 12, 2001.

"Security with Encrypting File System", from MSDN Oct. 2001 version, exact publication date is unknown but believed prior to Dec. 12, 2001.

"How EFS Works", from MSDN Oct. 2001 version, exact publication date is unknown but believed prior to Dec. 12, 2001.

"Encrypting File System", from MSDN Oct. 2001 version, exact publication date is unknown but believed prior to Dec. 12, 2001.

"Features of EFS", from MSDN Oct. 2001 version, exact publication date is unknown but believed prior to Dec. 12, 2001.

"Windows 2000 EFS", in the Apr. 1999 issue of *Windows NT Magazine*.

Examination Report, completion date Jun. 18, 2008, for European Patent Application No. EP 02 258 532.7-1244, 6 pgs.

Office Action, dated May 10, 2005, for European Patent Application No. 02258532.7, 5 pgs.

Office Action, dated Dec. 5, 2006, for European Patent Application No. 02258532.7, 5 pgs.

Boneh et al., "Hierarchical Identity Based Encryption with Constant Size Ciphertext," *Advances in Cryptology- EUROCRYPT 2005*, vol. 3493, Jun. 20, 2005, pp. 440-456.

Boneh et al., "IBE Secure E-mail," Stanford University, Apr. 8, 2002, <http://crypto.stanford.edu/ibe/>.

Stallings, William, "Cryptography and Network Security: Principles and Practice," 1999, pp. 333-337, Second Edition, Prentice Hall, Upper Saddle River, New Jersey.

"Affect," *The American Heritage Dictionary of the English Language*, Fourth Edition, Houghton Mifflin Company, 2002. Retrieved May 4, 2006 from <http://dictionary-reference.com/search?q=affect>. Microsoft Windows 2000 server. Windows 2000 Group Policy White Paper, 2000.

Symantec. Norton Antivirus Corporate Edition Implementation Guide, 1999.

Crocker, Steven Teye, "Multi-level cryptographic transformations for securing digital assets," U.S. Appl. No. 10/404,566, filed Mar. 31, 2003.

Crocker, Steven Teye, "Effectuating access policy changes to designated places for secured files," U.S. Appl. No. 10/259,075, filed Sep. 27, 2002.

Kenrich, Michael Frederick, "Multi-Level File Digest", U.S. Appl. No. 10/894,493, filed Jul. 19, 2004.

Kingham, Gary Mark, "Method and system for protecting electronic data in enterprise environment," U.S. Appl. No. 10/159,220, filed May 31, 2002.

Nath, Satyajit, "Method and system for securing digital assets using content type designations," U.S. Appl. No. 10/405,587, filed Apr. 1, 2003.

Prakash, Nalini J., "Method and apparatus for securing/unsecuring files by file crawling," U.S. Appl. No. 10/325,102, filed Dec. 20, 2002.

Rossmann, Alain, "Hybrid systems for securing digital assets," U.S. Appl. No. 10/325,013, filed Dec. 20, 2002.

A Real-Time Push-Pull Communications Model for Distributed Real-Time and Multimedia Systems, Jan. 1999, School of Computer Sciences Carnegie Mellon University, Kanaka Juvva, Raj Rajkumar. U.S. Appl. No. 10/889,685, entitled "Method and Apparatus for Controlling the Speed Ranges of a Machine" inventor Thomas, Jul. 13, 2004, 18 pgs.

U.S. Appl. No. 10/028,397, entitled "Method and system for restricting use of a clipboard application," inventor Zuili, Dec. 21, 2001, 38 pgs.

U.S. Appl. No. 10/368,277, entitled "Method and apparatus for uniquely identifying files," inventor Ouye, Feb. 18, 2003, 25 pgs.

U.S. Appl. No. 10/327,320, entitled "Security system with staging capabilities" inventor Vainstein, Dec. 20, 2002, 39 pgs.

U.S. Appl. No. 10/286,524, entitled "Security system that uses indirect password-based encryption," inventor Gutnik, Nov. 1, 2002, 38 pgs.

U.S. Appl. No. 10/242,185, entitled "Method and system for protecting encrypted files transmitted over a network" inventor Ryan, Sep. 11, 2002, 33 pgs.

U.S. Appl. No. 10/642,041, entitled "Method and system for fault-tolerant transfer of files across a network" inventor Kenrich, Aug. 15, 2003, 32 pgs.

U.S. Appl. No. 10/610,832, entitled "Method and system for enabling users of a group shared across multiple file security systems to access secured files" inventor Ryan, Jun. 30, 2003, 33 pgs.

U.S. Appl. No. 10/448,806, entitled "Method and System for Using Remote Headers to Secure Electronic Files" inventor Ryan, May 30, 2003, 35 pgs.

U.S. Appl. No. 10/074,194, entitled "Methods for identifying compounds that inhibit or reduce PTP1B expressions" inventor Rondinone, Feb. 12, 2002, 69 pgs.

U.S. Appl. No. 10/074,804, entitled "Secured Data Format for Access Control," inventor Garcia, Feb. 12, 2002, 108 pgs.

U.S. Appl. No. 10/075,194, entitled "System and Method for Providing Multilocation Access Management to Secured Items," inventor Vainstein et al., Feb. 12, 2002, 110 pgs.

U.S. Appl. No. 10/074,825, entitled "Method and Apparatus for Accessing Secured Electronic Data Off-line," inventor Lee et al., Feb. 12, 2002, 108 pgs.

U.S. Appl. No. 10/105,532, entitled "System and Method for Providing Different Levels of Key Security for Controlling Access to Secured Items," inventor Hildebrand et al., Mar. 20, 2002, 86 pgs.

U.S. Appl. No. 10/186,203, entitled "Method and System for Implementing Changes to Security Policies in a Distributed Security System," inventor Huang, Jun. 26, 2002, 65 pgs.

U.S. Appl. No. 10/201,756, entitled "Managing Secured Files in Designated Locations," inventor Alain, Jul. 22, 2002, 121 pgs.

U.S. Appl. No. 10/206,737, entitled "Method and System for Updating Keys in a Distributed Security System," inventor Hildebrand, Jul. 26, 2002, 60 pgs.

U.S. Appl. No. 10/246,079, entitled "Security System for Generating Keys from Access rules in a Decentralized Manner and Methods Therefor," inventor Hildebrand, Sep. 17, 2002, 78 pgs.

U.S. Appl. No. 10/259,075, entitled "Effectuating Access Policy Changes to Designated Places for Secured Files," inventor Crocker, Sep. 27, 2002, 60 pgs.

U.S. Appl. No. 10/286,575, entitled "Method and Architecture for Providing Access to Secured Data from Non-Secured Clients," inventor Vainstein, Nov. 1, 2002, 46 pgs.

U.S. Appl. No. 10/295,363, entitled "Security System Using Indirect Key Generation from Access Rules and Methods Therefor," inventor Vainstein, Nov. 15, 2002, 70 pgs.

U.S. Appl. No. 11/889,310, entitled "Methods and Systems for Providing Access Control to Electronic Data," inventor Rossmann, Aug. 10, 2007, 90 pgs.

U.S. Appl. No. 11/797,367, entitled "Method and System for Managing Security Tiers," inventor Vainstein, May 2, 2007, 11 pgs.

Adobe Acrobat 5.0 Classroom in a Book, Adobe Press, Jun. 26, 2001, pp. 1-4.

Adobe Acrobat Security Settings, Acrobat 7.0, Nov. 15, 2004, pp. 1-4.

"Security Options". Dec. 20, 2001. DC & Co, pp. 1-2.

Microsoft Press Computer Dictionary, 1997, Microsoft Press, Third Edition, p. 426.

Search Report, completion date May 8, 2003, for European Patent Application No. EP 02 25 8530, 2 pages.

Search Report, completion date Oct. 2, 2003, for European Patent Application No. EP 02 25 8531, 2 pages.

Search Report, completion date Apr. 14, 2005, for European Patent Application No. EP 02 25 8533, 2 pages.

Search Report, completion date Mar. 16, 2005, for European Patent Application No. EP 02 25 8534, 2 pages.

Search Report, completion date Mar. 2, 2005, for European Patent Application No. EP 02 25 8535, 2 pages.

Search Report, completion date Mar. 3, 2005, for European Patent Application No. EP 02 25 8537, 2 pages.

Search Report, completion date May 12, 2005, for European Patent Application No. EP 02 25 8539, 2 pages.

Search Report, completion date Jul. 6, 2005, for European Patent Application No. EP 02 25 8529, 4 pages.

Search Report, completion date Oct. 8, 2003, for European Patent Application No. EP 02 25 8536, 2 pages.

Search Report, completion date May 8, 2003, for European Patent Application No. EP 02 25 8540, 2 pages.

* cited by examiner




FIG. 1A







FIG. 1B

FIG. 1C

**Fig. 1D**






Fig. 2B




Fig. 2C.1




Fig. 2C.2

The diagram illustrates the transformation of an XML document. On the left is the original XML, and on the right is the encrypted XML. Brackets and arrows indicate the mapping between elements.

Original XML (Left):

```

<header>
  <header_version>
    1.0
  </header_version>
  <key_blocks_list>
    <key_blocks_list_version>
      1.0
    </key_blocks_list_version>
    <key_block>
      <key_block_version>
        1.0
      </key_block_version>
      <group_id> www.xyz.com/marketing </group_id>
    </key_block>
  </key_blocks_list>
</header>

<<< I'm encrypted with Marketing's public-key */
<group_id> www.xyz.com/marketing </group_id>
<crypto>
  <dek_mat>P39GJ439833IOOE93I5UR93U3945U439</dek_mat>
  <enc_algo>
    RUNDIAEL
  </enc_algo>
  <key_size> 256 </key_size>
  <block_size> 128 </block_size>
  <ses_enc_block_size> 4096 </ses_enc_block_size>
</crypto>
**>

```

Encrypted XML (Right):

```

<header>
  <header_version>
    1.0
  </header_version>
  <key_blocks_list>
    <key_blocks_list_version>
      1.0
    </key_blocks_list_version>
    <key_block>
      <key_block_version>
        1.0
      </key_block_version>
      <group_id> www.xyz.com/marketing </group_id>
    </key_block>
  </key_blocks_list>
</header>

<<< I'm encrypted with Marketing's public-key */
<group_id> www.xyz.com/marketing </group_id>
<crypto>
  <dek_mat>P39GJ439833IOOE93I5UR93U3945U439</dek_mat>
  <enc_algo>
    RUNDIAEL
  </enc_algo>
  <key_size> 256
  </key_size>
  <block_size> 128
  </block_size>
  <ses_enc_block_size> 4096
  </ses_enc_block_size>
</crypto>
**>

```

Annotations:

- 266** points to the `<group_id>` element in the original XML.
- 267** points to the `<group_id>` element in the encrypted XML.
- 268** points to the `<crypto>` block in the original XML.
- 269** points to the `<crypto>` block in the encrypted XML.
- 270** points to the `<dek_mat>` element in the encrypted XML.
- 271** points to the `<key_size>` element in the encrypted XML.
- 272** points to the `<ses_enc_block_size>` element in the encrypted XML.

Fig. 2C.3

275

AdmGrp : GUI

Group to pickup users:

Group C

User Names

User 15
User 16
User 17
User 18
User 19

Add
Delete

Group to setup:

Group B

User Names

User 20
User 21
User 22
User 23
User 24
User 25
User 26
User 27
User 28
User 29
User 30

Add
Delete

Default rights for files in this group:

☒ Read
☒ Update
☒ Delete
☐ Change group

Rights about other groups:

☐ Adm Rights
☒ Close
☐ Grant group creation
☐ Grant to set or no closed groups

Apply
Administrator Menu

Fig. 2D




Fig. 2E





Fig. 3

**Fig. 4A**

Process of receiving
access rules 430





Fig. 4B

Fig. 4CProcess of accessing
a secure document 450





Fig. 5A

User ID	User	Open	Edit	Write	Print	Copy	Download	Others
01243	User A	Y	Y	Y	Y	Y	Y	Y
17364	User B	Y			Y			
18465	G User C	Y	Y	Y			Y	
• • • •								

Fig. 5B.1

All user keys	Key/Key pair	Location	others
John's	111101101010101	128.1.100.64, ...	
Mike's, Dell's	101011000111111	64.100.1.128, ...	
Finance group	010101010111111	64.100.1.100, ...	
• • • •			

Fig. 5B.2



Server Assisted Process
of Accessing secure
document 530




Fig. 5B.4

Server Assisted Process
of securing a document
550




Fig. 5B.5




Fig. 5C

584

USER	PASSWORD	ACCESS PRIVILEGES
John	*****	L=10, T=24, D=ALL, C=ALL
Dell	*****	L=1, T=8, D=M-F, C=A
Mike	*****	L=5, T=12, D=M-S, C=A & B
• • •		

585

586

587

Fig. 5D

For Local Server C

USER	PASSWORD
John	*****
• • •	



For Local Server B



USER	PASSWORD
John	*****
Mike	*****
• • •	


For Local Server A


USER	PASSWORD
John	*****
Dell	*****
Mike	*****
• • •	


Fig. 5E







**Fig. 6A**

**Fig. 6B**

**Fig. 6C**



**Fig. 7B**




Fig. 7C

1

METHOD AND APPARATUS FOR SECURING ELECTRONIC DATA

CROSS-REFERENCE TO RELATED APPLICATION

This application claims the benefits of U.S. Provisional Application No. 60/339,634, filed Dec. 12, 2001, and entitled "Pervasive Security Systems," which is hereby incorporated by reference for all purposes.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to the area of protecting data in an enterprise environment, and more particularly, relates to processes, systems, architectures and software products for providing pervasive security to digital assets at all times.

2. Description of Related Art

The Internet is the fastest growing telecommunications medium in history. This growth and the easy access it affords have significantly enhanced the opportunity to use advanced information technology for both the public and private sectors. It provides unprecedented opportunities for interaction and data sharing among businesses and individuals. However, the advantages provided by the Internet come with a significantly greater element of risk to the confidentiality and integrity of information. The Internet is a widely open, public and international network of interconnected computers and electronic devices. Without proper security means, an unauthorized person or machine may intercept any information traveling across the Internet and even get access to proprietary information stored in computers that interconnect to the Internet, but are otherwise generally inaccessible by the public.

There are many efforts in progress aimed at protecting proprietary information traveling across the Internet and controlling access to computers carrying the proprietary information. Cryptography allows people to carry over the confidence found in the physical world to the electronic world, thus allowing people to do business electronically without worries of deceit and deception. Every day hundreds of thousands of people interact electronically, whether it is through e-mail, e-commerce (business conducted over the Internet), ATM machines, or cellular phones. The perpetual increase of information transmitted electronically has led to an increased reliance on cryptography.

One of the ongoing efforts in protecting the proprietary information traveling across the Internet is to use one or more cryptographic techniques to secure a private communication session between two communicating computers on the Internet. The cryptographic techniques provide a way to transmit information across an insecure communication channel without disclosing the contents of the information to anyone eavesdropping on the communication channel. Using an encryption process in a cryptographic technique, one party can protect the contents of the data in transit from access by an unauthorized third party, yet the intended party can read the data using a corresponding decryption process.

A firewall is another security measure that protects the resources of a private network from users of other networks. However, it has been reported that many unauthorized accesses to proprietary information occur from the inside, as opposed to from the outside. An example of someone gaining unauthorized access from the inside is when restricted or proprietary information is accessed by someone within an organization who is not supposed to do so. Due to the open nature of the Internet, contractual information, customer data,

2

executive communications, product specifications, and a host of other confidential and proprietary intellectual property remains available and vulnerable to improper access and usage by unauthorized users within or outside a supposedly protected perimeter.

A governmental report from General Accounting Office (GAO) details "significant and pervasive computer security weaknesses at seven organizations within the U.S. Department of Commerce, the widespread computer security weaknesses throughout the organizations have seriously jeopardized the integrity of some of the agency's most sensitive systems." Further it states: "Using readily available software and common techniques, we demonstrated the ability to penetrate sensitive Commerce systems from both inside Commerce and remotely, such as through the Internet," and "Individuals, both within and outside Commerce, could gain unauthorized access to these systems and read, copy, modify, and delete sensitive economic, financial, personnel, and confidential business data . . ." The report further concludes "[i]ntruders could disrupt the operations of systems that are critical to the mission of the department."

In fact, many businesses and organizations have been looking for effective ways to protect their proprietary information. Typically, businesses and organizations have deployed firewalls, Virtual Private Networks (VPNs), and Intrusion Detection Systems (IDS) to provide protection. Unfortunately, these various security means have been proven insufficient to reliably protect proprietary information residing on private networks. For example, depending on passwords to access sensitive documents from within often causes security breaches when the password of a few characters long is leaked or detected. Therefore, there is a need to provide more effective ways to secure and protect digital assets at all times.

SUMMARY OF INVENTION

This section is for the purpose of summarizing some aspects of the present invention and to briefly introduce some preferred embodiments. Simplifications or omissions may be made to avoid obscuring the purpose of the section. Such simplifications or omissions are not intended to limit the scope of the present invention.

The present invention is related to processes, systems, architectures and software products for providing pervasive security to digital assets at all times and is particularly suitable in an enterprise environment. In general, pervasive security means that digital assets are secured at all times and can only be accessed by authenticated users with appropriate access rights or privileges, wherein the digital assets may include, but not be limited to, various types of documents, multimedia files, data, executable code, images and texts.

In one aspect of the present invention, a server module executable in a server computer is configured to provide access control (AC) management for a group of users, software agents or devices with a need to access secured documents under the access control management. Within the server module, various access rules for the secured documents and/or access privileges for the users or software agents can be created, updated and managed so that the users, software agents or devices with the proper access privileges can access the secured documents if granted by the corresponding access rules in the secured documents. According to one embodiment, a secured document includes a header and encrypted data portion. The header includes encrypted security information to control the access to the encrypted data portion. A user key associated with an authenticated user must be retrieved in order to decrypt the encrypted security

information. Once the security information becomes available, the access rules are retrieved from the security information and can be measured against the access privileges of the user who is accessing the secured document. If such measurement succeeds, a file key is retrieved from the security information and used to decrypt the encrypted data portion, subsequently, a clear version of the secured document is made available to the user.

In another aspect of the present invention, the AC management is performed in a distributed fashion. A number of local server computers are employed to operate largely on behalf of a central server responsible for the centralized AC management. Such a distributed fashion ensures the dependability, reliability and scalability of the AC management undertaking by the central server. According to one embodiment, a cache version of the server module is loaded and executed in a local server. As a result, it is not necessary for a client machine to have live consultation with the central server when accessing secured documents. In fact, the secured documents can still be accessed even if the central server is down or a connection thereto is not available.

In still another aspect of the present invention, the local version for a local server can be dynamically reconfigured depending on a user's current location. According to one embodiment, a local version for a local server is so configured that it only services the users, software agents or devices that are local to the local server or have previously been authenticated by the local server. When a user moves from one location to another location, upon detecting a new location of the user who has moved from a previous location, a local version for the new location is reconfigured to add support for the user while at the same time a local version for the previous location is reconfigured to remove support for the user. As a result, the security is enhanced while the AC management can be efficiently carried out to ensure that only one access from the user is permitted at any time across an entire organization, regardless of how many locations the organization has or what access privileges the user may be granted.

In still yet another aspect of the present invention, the format of the secured document is so designed that the security information of a document stays with the document being secured at all times. As such, this integrated mechanism facilitates the transportation of secured documents to other locations without the loss of the security information therein and/or creating difficulty of accessing the secured documents from the other locations. According to one embodiment, a secured file or secured document includes two parts: an attachment, referred to as a header, and an encrypted document or data portion. The header includes security information that points to or includes the access rules and a file key. The access rules facilitate restrictive access to the secured document and essentially determine who/when/how/where the secured document can be accessed. The file key is used to encrypt/decrypt the encrypted data portion. Only those who have the proper access privileges are permitted to retrieve the file key to encrypt/decrypt the encrypted data portion. Depending on an exact implementation, the header may include other information (e.g., a flag, a signature or version number) to facilitate the detection of the security nature of the document. Alternatively, the two parts, encrypted security information and the encrypted data portion, may be encrypted again to be a secured file or secured document.

In still yet another aspect of the present invention, a client module executable in a client machine is configured to provide access control to the secured documents that may be located in a local store, another computer machine or somewhere over a data network. According to one embodiment,

the client module includes a document-securing module that is implemented to operate in an operating system. In particular, the document-securing module operates in a path through which a document being accessed would pass, as such, the document can be examined or detected for the security nature. If the document is secured, the document-securing module obtains a user or group key to decrypt the security information in the header thereof for the access rules. If a user accessing the document is determined to have the access privilege to the secured document, a file key is retrieved from the security information and a cipher module is activated to decrypt the encrypted data portion with the file key. Likewise, if a document is to be secured, the cipher module encrypts clear data from the document to create the encrypted data portion. The document-securing module integrates proper or desired security information with the encrypted data portion to produce the secured document. As the document securing module operates in an operating system, the en/decryption process is transparent to the user.

In still yet another aspect of the present invention, a client module in a client machine activates an off-line access module to provide an off-line access mechanism for those users on the go. When a user decides to be away from a network premises or on a business trip, an off-line access request may be generated by an off-line access module in the client machine and forwarded to an AC server. In response, the AC server may grant the off-line access request to the user as well as the client machine from which the user will access secured documents off-line. According to one embodiment, the AC server may provide amended or tentative access rules, access privileges or a user key that will automatically expire when a predetermined time ends or become invalid the next time the client machine is connected to the AC server. As a result, the user can access some or all the secured documents in the client machine and, at the same time, create secured documents, all accessed or secured with the tentative access rules, access privileges or the user key. During the off-line access period, an access report manager may be activated to record all activities of the user accessing the secured documents. When the client machine is once again connected to the AC server, the access activities of the secured documents can be reported to the AC server to facilitate the access control management and synchronization of the secured documents accessed or created off-line.

One of the objects in the present invention is to provide a generic securing mechanism that can protect secured digital assets at all times.

Other objects, features, and advantages of the present invention will become apparent upon examining the following detailed description of an embodiment thereof, taken in conjunction with the attached drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

These and other features, aspects, and advantages of the present invention will become better understood with regard to the following description, appended claims, and accompanying drawings where:

FIG. 1A shows a basic system configuration in which the present invention may be practiced in accordance with a preferred embodiment thereof;

FIG. 1B shows a configuration in which a central server and local servers are employed;

FIG. 1C shows a configuration suitable for a small group of users with no local servers employed;

5

FIG. 1D shows internal construction blocks of a computing device (e.g., a client machine, a central server and a local server) in which the present invention may be implemented and executed;

FIG. 2A is an illustration diagram of securing a created document;

FIG. 2B illustrates an exemplary structure of a secured document including a header and an encrypted data portion;

FIG. 2C.1 illustrates another exemplary structure of a secured document including multiple users' information in a header and an encrypted portion;

FIG. 2C.2 illustrates still another exemplary structure of a secured document including security blocks in a header and an encrypted portion;

FIG. 2C.3 shows an exemplary header in a markup language corresponding to that of the secured document structure illustrated in FIG. 2C.2;

FIG. 2D shows an exemplary graphic user interface (GUI) that can be used to establish or create the access rules by users;

FIG. 2E shows a directory structure including a clear folder and secured (active) folders, wherein the clear folder is generally for storing system files or files that are not intended for protection and the secured folders are for data files and documents in secured form;

FIG. 3 shows an exemplary implementation of how a document-securing module interacting with and operating within an operating system (e.g., WINDOWS 2000) ensures that a document made secured is transparent to a user;

FIG. 4A shows a flowchart of the process of securing a document being created according to one embodiment of the present invention;

FIG. 4B shows a flowchart of an exemplary process of receiving the access rules and may be incorporated into the process of FIG. 4A to facilitate the process of securing a document;

FIG. 4C shows a flowchart of a process of accessing a secured document according to one embodiment, and shall be understood in conjunction with FIG. 3;

FIG. 5A shows a function block diagram of a (access control) server device in which a server module resides in a memory space and is executable by one or more processors in the server device;

FIG. 5B.1 and FIG. 5B.2 illustrate, respectively, two structures, one showing exemplary access privileges for the users and the other showing what may be in a user key manager according to one embodiment of the present invention;

FIG. 5B.3 shows a flowchart of updating a user key process;

FIG. 5B.4 shows a flowchart of a server-assisted process of accessing secured documents according to one embodiment, and shall be understood in conjunction with FIG. 3;

FIG. 5B.5 shows a flowchart of a server assisted process of securing a document according to one embodiment, and shall also be understood in conjunction with FIG. 3;

FIG. 5C shows a functional block diagram of a local server device which, in many ways, is similar to that of the server as illustrated in FIG. 5A;

FIG. 5D shows a table of all the users with different access privilege, the table being managed by a central server;

FIG. 5E shows respective tables, each accessed by a local server, as a result, users need only to check with a corresponding local server; none would be affected if other local servers are down for whatever reasons or are disconnected from the central server;

FIG. 5F illustrates the accessibility for each of the users, instead of having three identical cache modules, each permit-

6

ting John to access from any of the three locations, only one cache module is configured to permit John to access from one of the three locations at one time;

FIG. 5G shows a dynamic caching access control management by adding John to another cache module that now can service John moved from another location;

FIG. 5H and FIG. 5I show respectively the changing accessibility for user as a result of the dynamic caching access control management;

FIG. 6A shows a flowchart of a user authentication process that may be implemented in a central server or a local server;

FIG. 6B shows a flowchart of dynamically configuring the access control management process which may be implemented in one or more local servers in conjunction with a central server;

FIG. 6C shows a flowchart of reconfiguring the local modules' process, according to one embodiment, and may be used in FIG. 6B;

FIG. 7A shows a functional block diagram of a client machine that may be used to practice the present invention;

FIG. 7B shows a flowchart of providing off-line access processing in accordance with one embodiment of the present invention; and

FIG. 7C illustrates an amendment of the access rules placed into a secured document that can be accessed by Users, A, B, C and D, wherein User A has requested off-line access and has been granted the request, while Users B, C and D cannot access the secured documents off-line.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The present invention is related to processes, systems, architectures and software products for providing pervasive security to digital assets at all times. In general, pervasive security means that digital assets are secured at all times and can only be accessed by authenticated users with appropriate access privileges. The present invention is particularly suitable in an enterprise environment.

In the following description, numerous specific details are set forth in order to provide a thorough understanding of the present invention. However, it will become obvious to those skilled in the art that the present invention may be practiced without these specific details. The description and representation herein are the common means used by those experienced or skilled in the art to most effectively convey the substance of their work to others skilled in the art. In other instances, well-known methods, procedures, components, and circuitry have not been described in detail to avoid unnecessarily obscuring aspects of the present invention.

Reference herein to "one embodiment" or "an embodiment" means that a particular feature, structure, or characteristic described in connection with the embodiment can be included in at least one embodiment of the invention. The appearances of the phrase "in one embodiment" in various places in the specification are not necessarily all referring to the same embodiment, nor are separate or alternative embodiments mutually exclusive of other embodiments. Further, the order of blocks in process flowcharts or diagrams representing one or more embodiments of the invention do not inherently indicate any particular order nor imply any limitations in the invention.

To facilitate the description of the present invention, it deems necessary to provide definitions for some terms that will be used throughout the disclosure herein. It should be noted that the definitions following are to facilitate the understanding and describe the present invention according to an

embodiment. The definitions may appear to include some limitations with respect to the embodiment, the actual meaning of the terms has applicability well beyond such embodiment, which can be appreciated by those skilled in the art:

Digital Asset—defines a type of electronic data that includes, but is not limited to, various types of documents, multimedia files, streaming data, dynamic or static data, executable code, images and texts.

File or document—interchangeably used herein, indicates one type of digital asset and generally is in a clear mode which means that it can be accessed by one or more applications without a priori knowledge, wherein the access of a file or document is a request that results in the file or document being opened, viewed, edited, played, listened to, printed, or in a format or outcome desired by a user who has requested the access of the file or document.

Secured file or secured document—defines a type of digital asset that cannot be accessed without a priori knowledge. Example of a priori knowledge may include, but not be limited to, a password, a secret phrase, biometric information or one or more keys.

Encrypted file or encrypted document means a file or document that has been encrypted with a cipher (i.e., an implementation of cryptographic techniques).

File key—is one example of a priori knowledge that is also referred to as a cipher key and, once obtained, can be used to unlock or decrypt the encrypted document.

User key—is another cipher key associated with or identifying a user or a group of users and can be used to obtain the file key. According to one format of the secured file, a user key is used to retrieve a file key that, in turn, unlocks or decrypts the encrypted document while a different user key or the same user key may be used to hide or encrypt the file key.

Access Privilege—is one or more rights a user may have with respect to a secured file or secured document. A user may only be able to access a secured file from a designated location during a specific period if his/her access privilege limits him/her to do so. Optionally, access privilege may specify other limitations on a specific host whence user is logged in, a file transfer protocol, an access application (model and/or version), a permit to grant access privilege to others (e.g. a consultant) or membership in other groups, etc.

Access rules—are flags or designated permits to limit what a user can do with a secured file or secured document. According to one embodiment of the present invention, at least some of the access rules can be included in a secured file or secured document. In some cases, the access rules may be extensible by a user with appropriate access privilege.

Client device, computer, or machine—interchangeably used herein, is a terminal device typically used by a user to access secured documents.

Server device, computer, or machine—interchangeably used herein, is a computing device. According to one embodiment, such computing device can provide access control (AC) management for secured documents that are accessible from a client machine or a user.

Client module—generally means an executable version of an embodiment of the present invention and typically is loaded in a client device to deliver functions, features, benefits and advantages contemplated in the present invention.

Server module—generally means an executable version of an embodiment of the present invention and typically is loaded in a server device to deliver functions, features, benefits and advantages contemplated in the present invention.

Server and Client—unless otherwise specifically or explicitly stated, a server may mean either a server machine or a

server module, a client may mean either a client machine or a client module, and in either case, the particular meaning shall be evident in the context.

Embodiments of the present invention are discussed herein with reference to FIGS. 1A-7C. However, those skilled in the art will readily appreciate that the detailed description given herein with respect to these figures is for explanatory purposes as the invention extends beyond these limited embodiments.

FIG. 1A shows a basic system configuration in which the present invention may be practiced in accordance with one embodiment thereof. Documents or files, such as product descriptions, customer lists and price schedules, may be created using an authoring tool executed on a client computer **100**, that may be a desktop computing device, a laptop computer, or a mobile computing device. Exemplary authoring tools may include Microsoft Office (e.g., Microsoft Word, Microsoft PowerPoint, and Microsoft Excel), Adobe Frame-Maker and Adobe Photoshop.

According to one embodiment, the client computer **100** is loaded with a client module that is a linked and compiled, or interpreted, version of one embodiment of the present invention and is capable of communicating with a server **104** or **106** over a data network (i.e., the Internet or a local area network). According to another embodiment, the client computer **100** is coupled to the server **104** through a private link. As will be further explained below, a document created by an authoring tool is secured by the client module that will be described in detail below. The client module, when executed, is configured to ensure that a secured document is secured at all times in a store (e.g., a hard disk or other data repository). By virtue of the present invention, the documents are stored in a secured mode and can only be accessed by users with proper access privileges. In general, an access privilege or access privileges for a user may include, but not be limited to, a viewing permit, a copying permit, a printing permit, an editing permit, a transferring permit, an uploading/downloading permit, and a location permit.

According to one embodiment, a created document is caused to go through an encryption process that is preferably transparent to a user. In other words, the created document is encrypted or decrypted under the authoring application so that the user is not aware of the process. A key (referred to herein as a user key) to retrieve a file key to decrypt an encrypted document is associated with an access privilege. Only a user with a proper access privilege can access the secured document.

In one setting, a secured document may be uploaded via the network **110** to a computing or storage device **102** that may serve as a central repository. Although not necessary, the network **110** provides preferably a private link between the computer **100** and the computing device **102**. Such link may be provided by an internal network in an enterprise or a secured communication protocol (e.g., VPN and HTTPS) over the Internet. Alternatively, such link may be simply provided by a TCP/IP link. As such, secured documents on the computer **100** may be remotely accessed.

In another setting, the computer **100** and the computing or storage device **102** are inseparable, in which case the computing or storage device **102** may be a local store to retain secured documents or receive secured network resources (e.g. dynamic Web contents, results of a database query, or a live multimedia feed). Regardless of where the secured documents or secured sources are actually located, a user, with a proper access privilege, can access the secured documents or

sources from the computer **100** or the device **102** using an application (e.g., Internet Explorer, Microsoft Word or Acrobat Reader).

The server machine **104**, sometimes referred to as a local server, is a computing device coupled between a network **108** and the network **110**. According to one embodiment, the server **104** executes a local version of a server module of a linked and compiled version of one embodiment of the present invention. As will be detailed below, a local version is a localized server module configured to service a group of designated users or client computers, or a location. Another server machine **106**, also referred to as a central server, is a computing device coupled to the network **108**. The server **106** executes the server module and provides centralized access control (AC) management for an entire organization or business. Accordingly, respective local modules in local servers, in coordination with the central server, form a distributed mechanism to provide a distributed AC management. Such distributed access control management ensures the dependability, reliability and scalability of centralized AC management undertaken by the central server for an entire enterprise or a business location. As will be further explained below, the server module in the central server maintains or interfaces to a database that includes, but is not limited to, a list of users and corresponding access privileges for the entire organization or business and rules for folders or files, while a local module can be configured to maintain or interface to a portion or whole of the database, hence, servicing a group of users local to the local server.

FIG. **1B** shows a configuration in which a central server and local servers are employed. The configuration may correspond to a large enterprise having multiple geographic locations or offices. A central server **106** maintains a database managing the access privileges and the access rules in the entire enterprise. One of the features in this configuration is the underlying capability to provide fault tolerance and efficient AC management for a large group of users. Instead of having the central server **106** performing the AC management for each of the users at one single location, a number of local servers **104** (e.g., **104-A**, **104-B**, . . . and **104-N**) are employed in a distributed manner to service the individual locations or offices. Each of local servers **104** executes a local module derived or duplicated from the server module being executed at the central server **106** to manage those users who are local to respective local servers **104**. The central server **106** can centralize the AC management in addition to managing the users if necessary.

According to one embodiment, a local module can be a customized version of the server module that runs efficiently for only a few locations or a group of users. For example, a local server **104-A** is only responsible for the users or computers **102-A** in location A, while a local server **104-B** is only responsible for the users or computers **102-B** in location B. As a result, even if the central server **106** has to be taken down for maintenance or is not operative at the time a user needs to access secured documents, the access control will not be disruptive. The detailed operation of the local servers **104** in cooperation with the central server **106** will be further described below.

According to another embodiment, a local module is a replicated version of the server module and exchanges any updates with the server module when connected (e.g. periodically or at request). Depending on implementation, part or all of the server module can be duplicated in a local server to ensure that communications with users or their client machines are efficient and fault tolerance. As a result, even if the central server **106** has to be taken down for maintenance or

is not operative at the time a user needs to access secured documents, the access control will not be disruptive. For example, in such a situation, any of the local servers **104** can step up and take the place of the central server. When the central server **106** is running or communicating with the local servers **104**, information collected at the respective local servers about the users or their activities is sent back to the central server **106**. The detailed operation of the local servers **104** in cooperation with the central server **106** in this regard will also be further provided below.

FIG. **1C** shows a configuration suitable for a small group of users. In this configuration, no local servers are employed. A server computer **112** is loaded with the server module and each of the users or terminal computers **116** (only one is shown therein) is loaded with a client module. As a result, the server computer **112** performs the AC management for each of the users or the terminal computers **116**.

It should be noted that there is no clear distinction between a small group and a large group of users as far as the number is concerned. Given the description herein, those skilled in the art will understand how to distribute or balance the AC management among one or more other computing devices. To facilitate the following description of the present invention, the setting shown in FIG. **1B** will be assumed. Those skilled in the art will understand that the description herein is equally applicable to FIG. **1C** or situations in which other possible settings between one or more central servers and one or more local servers are desired.

FIG. **1D** shows internal construction blocks of a computing device **118** in which one embodiment of the present invention may be implemented and executed. The device **118** may correspond to a client device (e.g., computer **100**, **102** in FIG. **1A** and FIG. **1B** or computer **116** in FIG. **1C**) or a server device (e.g., server **104**, **106** in FIG. **1A** and FIG. **1B** or server **112** in FIG. **1C**). As shown in FIG. **1D**, the device **118** includes a central processing unit (CPU) **122** interfaced to a data bus **120** and a device interface **124**. CPU **122** executes instructions to process data and perhaps manage all devices and interfaces coupled to data bus **120** for synchronized operations. The instructions being executed can, for example, pertain to drivers, operating system, utilities or applications. A device interface **124** may be coupled to an external device, such as the computing device **102** of FIG. **1A**, hence, the secured documents therefrom can be received into memory **132** or storage **136** through data bus **120**. Also interfaced to data bus **120** is a display interface **126**, a network interface **128**, a printer interface **130** and a floppy disk drive interface **138**. Generally, a client module, a local module or a server module of an executable version of one embodiment of the present invention can be stored to storage **136** through floppy disk drive interface **138**, network interface **128**, device interface **124** or other interfaces coupled to data bus **120**. Execution of such module by CPU **122** can cause the computing device **118** to perform as desired in the present invention. In one embodiment, the device interface **124** provides an interface for communicating with a capturing device **125** (e.g. a finger print sensor, a smart card reader or a voice recorder) to facilitate the authentication of a user of the computing device **118**.

Main memory **132**, such as random access memory (RAM), is also interfaced to data bus **120** to provide CPU **122** with instructions and access to memory storage **136** for data and other instructions. In particular, when executing stored application program instructions, such as a document securing module in the present invention, CPU **122** is caused to manipulate the data to achieve results contemplated by the present invention. Read-Only Memory, (ROM) **134** is pro-

vided for storing executable instructions, such as a basic input/output operation system (BIOS) for operation of keyboard **140**, display **126** and pointing device **142**, if there are any.

Referring now to FIG. 2A, an illustration diagram of securing a created document **200** is shown. After the document **200** is created with an application or authoring tool (e.g., Microsoft WORD), upon an activation of a "Save," "Save As" or "Close" command or automatic saving invoked by an operating system, the application itself, or an application that is previously registered with the server, the created document **200** is caused to undergo a securing process **201**. The securing process **201** starts with an encryption process **202**, namely the document **200** that has been created or is being written into a store is encrypted by a cipher with a file key. In other words, the encrypted document could not be opened without the file key (i.e., a cipher key).

A set of access rules **204** for the document **200** is received and associated with a header **206**. In general, the access rules **204** determine or regulate who and/or how the document **200**, once secured, can be accessed. In some cases, the access rules **204** also determine or regulate when or where the document **200** can be accessed. Typically, a header is a file structure, small in size and includes, or perhaps links to, security information about a resultant secured document. Depending on an exact implementation, the security information can be entirely included in a header or pointed to by a pointer that is included in the header. According to one embodiment, the access rules **204**, as part of the security information, is included in the header **206**. The security information further includes the file key and, in some cases, an off-line access permit (e.g. in the access rules) should such access be requested by an authorized user. The security information is then encrypted by a cipher with a user key associated with an authorized user to produce encrypted security information **210**. The encrypted header, if no other information is added thereto, is attached to the encrypted document **212** to generate a secured document **208**.

It is understood that a cipher may be implemented based on one of many encryption/decryption schemes. Examples of such schemes may include, but not be limited to, Data Encryption Standard algorithm (DES), Blowfish block cipher and Twofish cipher. Therefore, the operations of the present invention are not limited to a choice of those commonly-used encryption/decryption schemes. Any encryption/decryption scheme that is effective and reliable may be used. Hence, the details of encryption/decryption schemes are not further discussed herein so as to avoid obscuring aspects of the present invention.

In essence, the secured document **208** includes two parts, the document itself and the corresponding security information therefor, both are in encrypted form. To access the document, one needs to obtain the file key that is used to encrypt the document and is now included in the encrypted security information. To obtain the file key, one needs to be authenticated to get a user or group key and pass an access test in which the access rules in the security information are measured against the user's access privilege.

According to one embodiment, the encrypted security information that includes the access rules or the header is placed at the beginning of the encrypted document (data portion) to facilitate early detection of the secured nature of a secured document. One of the advantages of such placement is to enable an access application (i.e., an authoring or viewing tool) to immediately activate a document securing module to decrypt the header. Upon the success of the decryption of the header with an authenticated user key, the access rules can

be checked against the user's access privilege. If the user who requested the secured document does have the proper access privilege, the clear contents of the document will be loaded into the access application, otherwise a denial notification (e.g., a message or a blank document) is sent to the user. However, the encrypted security information or the header may be placed anywhere around or in the encrypted document and sometimes may not be embedded contiguously in the encrypted data portion. By the virtue of the present invention, the encrypted header is always attached to the encrypted data portion, namely, the security information stays with the document being secured. This integrated mechanism facilitates the transporting of secured documents to other locations without the loss of the security information therein.

One of the features in the present invention is that the document being secured is transparent to the user. In other words, a secured document or file is configured to have a file extension identical to that of the file before being secured so that an application designated to access the file can be executed to access the secured file. For example, a newly created Microsoft word document, xyz.doc, can be accessed by an application WINWORD.EXE. After it goes through the securing process, the secured document is maintained to keep the same file name, i.e., xyz.doc, which still can be accessed by the same application WINWORD.EXE, except now the application may fail to open the document if the access rules therein do not permit a user to do so.

Alternatively, a secured document in a folder appears substantially similar to a regular document and launches the same application when activated except the application would fail to access the contents therein. For example, icons or file names of secured documents may appear in a different color or with a visual indication to distinguish from non-secured documents. When a secured document is unintentionally end up in a machine or readable medium (e.g. CD or disk), if a user of the machine or a machine to read the readable medium has no proper user key or if the user cannot be authenticated, the secured document would not be successfully accessed.

It should be noted that the header in a secured document may be configured differently than noted above of a few formats herein without departing the principles of the present invention. For example, a secured document may include a header with a plurality of encrypted headers, each can be accessible only by one designated user or a group users. Alternatively, a header in a secured document may include more than one set of security information, each set being for one designated user or a group of users while a single file key can be used by all. Some or all of the access rules may be viewed or updated respectively by users who can access the secured document.

As will be further described below, to access a secured document, a user needs a user key or keys to decrypt the encrypted security information or header first. In one embodiment, the key or keys are associated with a user's login to a local server or a central server. Appropriate access privilege associated with the user is validated if the user has been authenticated or previously registered with the server and properly logged in. Depending on the permission or the access privileges, the access rules in the secured document determine whether the contents in the document shall be revealed to the user.

According to one embodiment, the access rules are present in a markup language, such as HTML and SGML. In a preferred embodiment, the markup language is Extensible Access Control Markup Language (XACML) that is essentially an XML specification for expressing policies for information access. In general, XACML can address fine grained

13

control of authorized activities, the effect of characteristics of the access requester, the protocol over which the request is made, authorization based on classes of activities, and content introspection (i.e., authorization based on both the requestor and attribute values within the target where the values of the attributes may not be known to the policy writer). In addition, XACML can suggest a policy authorization model to guide implementers of the authorization mechanism.

The following shows an example of the access rules expressed in XACML:

```
<rule>
  <doc_type>
    PDF
  </doc_type>
  <grantor name="ACCTG"/>
  <grantee name="MKTG"/>
  <grantee name="PR"/>
  <action>
    VIEW
  </action>
  <action>
    PRINT
  </action>
  <conditions>
  <delivery_channels>
    HTTPS
  </delivery_channels>
  <min_time_day>
    1700
  </min_time_day>
  <expiry_date>
    3 Aug. 2002
  </expiry_date>
  </conditions>
</rule>
```

The literal meaning of the above example is that "any new PDF documents created by ACCTG (accounting group), can be VIEWed and PRINTed by MKTG (marketing group) and PR (public relationship group), on the condition that the documents are downloaded over secured HTTP, accessed before 5:00 PM in the day, before Aug. 3, 2002."

FIG. 2B illustrates an exemplary structure of a secured document 220 including a header 222 and an encrypted portion 224. The header 222 includes a security information block 226 having encrypted security information that essentially controls the access to the encrypted document 224. In a certain implementation, the header 222 includes a flag 227 (e.g., a predetermined set of data) to indicate that the document 220 is secured. The security information block 226 includes one or more user IDs 228, access rules 229, at least one file key 230 and other information 231. The user IDs 228 maintain a list of authorized users who may be measured against by the access rules 229 before the file key 230 can be retrieved. The access rules 229 determine at least who and how the encrypted document 224 can be accessed. Depending on an implementation, the other information 231 may be used to include other information facilitating a secure access to the encrypted document 224, the example may include version numbers or author identifier.

In general, a document is encrypted with a cipher (e.g., a symmetric or asymmetric encryption scheme). Encryption is the transformation of data into a form that is impossible to read without appropriate knowledge (e.g., a key). Its purpose is to ensure privacy by keeping information hidden from anyone to whom it is not intended, even those who have access to other encrypted data. Decryption is the reverse of encryption. Encryption and decryption generally require the

14

use of some secret information, referred to as a key. For some encryption mechanisms, the same key is used for both encryption and decryption; for other mechanisms, the keys used for encryption and decryption are different. For the purpose of controlling the access to the document, the key or keys, referred collectively to as a file key, may be the same or different keys for encryption and decryption and are preferably included in the security information contained in or pointed to by the header and, once obtained, can be used to decrypt the encrypted document.

To ensure that the key is not to be retrieved or accessible by anyone, the key itself is guarded by the access privileges and rules. If a user requesting the document has the proper access privileges that can be granted by the access rules, the key will be retrieved to proceed with the decryption of the encrypted document.

To ensure that the security information or the header (if no flag is implemented) is not readily revealed, the header itself is encrypted with a cipher. Depending on an exact implementation, the cipher for the header may or may not be identical to the one used for the document. The key (referred to as a user key) to decrypt the encrypted header can, for example, be stored in a local store of a terminal device and activated only when the user associated with it is authenticated. As a result, only an authorized user can access the secured document.

Optionally, the two encrypted portions (i.e., the encrypted header and the encrypted document) can be encrypted again and only decrypted by a user key. In another option, the encrypted portions (either one or all) can be error checked by error checking portion 225, such as using cyclical redundancy check, to ensure that no errors have incurred to the encrypted portion(s) or the secured document 220.

FIG. 2C.1 illustrates an exemplary structure of a secured document 236 including a header 238 and an encrypted portion 239. The header 238 permits four different entities to access the secured document 236. The four different entities 240-243 include two individual users and two group users, wherein the group users mean that everyone in a group could access the document with the same privileges. The two individual users have two different access privileges. User A can only read the document while user D can edit and read the document. While everyone in Group B can read and edit the document, everyone in Group C can only print the document. Each entity has a corresponding ID to be associated with the corresponding users and its own access rules. According to one embodiment, the header 238 in the secured document 236 is partitioned into corresponding four sub-headers 240-243, each designated to one user or group and keeping a file key therein and encrypted with a separate user key. In other words, when User A is requesting the secured document 236, only the header 240 designated to User A is decrypted with a user key (e.g., key A) belonging to the user A and authenticated with the user, the rest of the sub-headers 241-243 remain encrypted. In any case, once one of the sub-headers 241-243 is decrypted, the secured document can be decrypted with a key (e.g., file key) retrieved from the decrypted sub-header.

FIG. 2C.2 illustrates another exemplary structure of a secured document 250 including a header 252 and an encrypted portion 254. The header 252 further includes a user block 256 and a rules block 258. The user block 256 includes a clear portion and an encrypted portion 260. The clear portion includes user/group ID(s) and block version number(s). The encrypted portion 260 is encrypted with a user key according to a cipher. If there are N number of distinctive groups/users with possible different access privileges, there will be N such encrypted portions, each encrypted with a

15

corresponding user key. The encrypted portion **260** includes, among other things, the file key that, once retrieved, can be used to decrypt the encrypted data portion **254**. In addition, the encrypted portion **260** includes the cipher information to facilitate the encryption/decryption of the encrypted portion **254**.

The rules block **258** can be encrypted individually or with the encrypted document **254** using the file key that is eventually stored in the user block **256**. One of the advantages of using the file key instead of the individual user key to encrypt the rules block **258** is to provide a mechanism for all authorized users/groups to view who has what access rules and rights. According to one embodiment, a random number or a result from an initialization process (e.g. a vector) may be added in the beginning of the rules block **258** to prevent an attack against the rules block **258**.

FIG. 2C.3 shows an exemplary header **266** corresponding to that of the secured document structure in FIG. 2C.2. The header **266** includes a number of segments. In addition to those segments in clear mode, segments **267-269** are encrypted. Specifically, the secured file is configured to be accessed by two groups: marketing and engineering. All users in the two groups are supposed to be able to access the file with an authenticated user key. According to one embodiment, the segment **267** is encrypted with a user key specifically designated to marketing users, while the segment **268** is encrypted with a user key specifically designated to engineering. However, both of the segments **267** and **268** could be respectively encrypted with a single user key. In any event, the encrypted segments in the header **266** include a file key **270** in addition to corresponding cipher information about the cipher being used.

The rules block (i.e., a segment) **269** includes two sets **271** and **272** of access rules (details on rules not shown), one for each of the two user groups. The rules block **269** is encrypted with a key, such as the file key **270** or some other key depending on what cipher is used. According to one embodiment, one of the encrypted segments in the user blocks **267** and **268** shall be decrypted **269** with an authenticated user key to retrieve the file key **270**. Before the file key **270** is applied to the decryption of the encrypted data portion, the rules block **269** is decrypted with the file key **270**. The access rules are then measured against the access privilege of the user. If the user is not permitted to access the secured document, the file key **270** will not be applied to the decryption of the encrypted data portion. If the user is permitted to access the secured document, the file key **270** will then be applied to the decryption of the encrypted data portion.

It should be noted that FIG. 2C.1, FIG. 2C.2 and FIG. 2C.3 are only exemplary structures of secured documents. In an alternative implementation, the file key necessary to decrypt the document may be encrypted alone and kept in a separate block in the header. The file key becomes retrievable when one of the sub-headers (no longer keeping the file key) is decrypted. In still another alternative implementation, one or more flags or messages may be included in the security information of a secured document, the flags or messages indicate how secure the secured document can be. For example, a secured document can be classified as a normal, confidential, secret or a top-secret document, requiring different level of access. Accordingly, multiple-levels of encryption on the file key and/or access rules may be employed to ensure that only an authorized user or users are permitted to access the secured document. Other implementation options are also possible given the description herein and are not to be listed one by one to avoid obscuring aspects of the present invention.

16

FIG. 2D shows an exemplary graphic user interface (GUI) **275** that can be used to establish or create access rules. The GUI **275** can be activated and/or displayed when a user finishes with a secured document and is ready to save it into a designated place (e.g., a folder or a repository) or a clear or new document is ready to be placed into a designated place. According to one embodiment, all data in the designated place will have substantially similar access rules. Depending on an exact implementation, the GUI **275** can be dynamically generated or controlled by the central server to include users who may have the need to access the data in that designated place. The GUI **275** facilitates the determination of the access rules that the user intends to impose. As shown in FIG. 2D, a selected group of users can be selected to add into an access list **276**. Actions **277** determine how the data in the designated place can be accessed. The actions **277** can be set using the GUI **275**. As a result, the parameters defining the access rules can be graphically determined and now gathered from the GUI **277** to be included in the document (e.g., in the security information of the header). In one embodiment, the access rules are kept in a temporary file (e.g., in a markup language format) associated with a designated folder and optionally encrypted. The temporary file can then be attached to an encrypted portion when the document is being written as a secured file into a local store.

Sometimes, a user may have a need to export or import a set of predefined access rules. In this case, the temporary file having the access rules may be exported, downloaded or imported into another device or folder. The exportation/importation of access rules provides convenience for a user because the user need not create the access rules from scratch.

One of the features for setting up a set of access rules for a particular place or folder is to provide a securing mechanism for users to create secured documents without specifying as to who/how/when/where the documents can be accessed. FIG. 2E shows a directory structure **280** including a clear folder **281** and a secured folder **282**. The clear folder **281** is generally for storing system files or files that are not intended to be protected. The secured folder **282** includes multiple subfolders that can be structured respectively for each access level. For example, a document "employee list" can be accessed by anyone who has access privileges to access level A. Similarly, documents "product milestone" and "product specification" or "product schedule" can be accessed by anyone who has an access privileges to folder **284** for access level B and to folder **286** for access level C, respectively. Likewise, a created document, if placed in folder "design team 2", will be automatically encrypted with the corresponding access rules that will permit only those who has access privileges to access level B. In this embodiment the access levels are hierarchical, meaning that a user with access level A authorization can access not only access A items but also the lower access levels B and C which are subsets of access level A.

Unlike prior art systems in which documents to be secured are encrypted by an encryption process initiated by a user, one of the features in the present invention is to activate a cipher process (i.e., encryption/decryption process) transparently as far as the user is concerned. In other words, the user is not made aware that a document is being made secured through the cipher process while being wrote into a store.

FIG. 3 shows an exemplary implementation **300** of how a document securing module (DSM) **302** interacting with and operating within an operating system **304** (e.g., WINDOWS 2000) to ensure that a document is made secure in a manner that is transparent to the user.

An application **306** (e.g. a server registered application, such as Microsoft Word) operates over operating system (OS)

304 and may be activated to access a document stored in a store 308. The store 308 may be a local storage place (e.g., hard disk) or remotely located (e.g., another device). Depending on the security nature (secured vs. non-secured) of the document being accessed, the DSM 302 may activate a cipher module 310. According to one embodiment, the DSM 302 is analogous in many ways to a device driver that essentially converts more general input/output instructions of an operating system to messages that a device/module being supported can understand. Depending on the OS in which the present invention is implemented, DSM may be implemented as a VxD (virtual device driver), a kernel or other applicable format. The cipher module 310 is included in or controlled by the DSM 302 and can be activated for operations when a secured document is involved.

In operation, a user selects a secured document that is associated with an application 306 (e.g., MS WORD, PowerPoint, or printing). The application 306 acts on the secured document calls an API (e.g., createFile, a Common Dialog File Open Dialog with Win32 API in MS Windows) to access the installable file system (IFS) manger 312. If it is detected that an "Open" request is made from the application 306, the request is passed to an appropriate file system driver (FSD) 314 to access the requested secured document. At the same time, the cipher module 310 is activated and an authenticated user key is retrieved from a local store to decrypt the header in the requested secure document. If the encrypted header is decrypted and the access rules therein are measured successfully against the user's access privileges, then a file key is retrieved from the header of the secured document and the cipher module 310 proceeds to decrypt the encrypted document in the DSM 302. The clear contents are then returned to the application 306 through the IFS manager 312. For example, if the application 306 is an authoring tool, the clear contents are displayed. If the application 306 is a printing tool, the clear contents are sent to a designated printer.

If it is detected that a "New" request is made, which means a secured document is being created or authored, a file key is generated in the DSM 302 (e.g., by the cipher module 310) and the file key will be subsequently used to encrypt the contents in a document being created. To ensure that the local store always has the encrypted documents, every time, a "Write" request (e.g., a "save" command in Microsoft Word) is made manually by a user or automatically by the application 306 or the OS 304, whatever contents in the document being processed or authored are encrypted by the cipher module 310 with the file key in the DSM 302. When a "Close" request is made, the file key is stored in a header that also includes whatever access rules that the user has applied thereto. The header is then encrypted with an authenticated user key and attached to the encrypted document before the document is sent to the appropriate FSD (e.g., 314) for storage in the store 308 (e.g., a folder or a designated location). As a result, a secured document is created.

In another embodiment, an operating system (OS) access, known as the ProcessID property, can be used to activate an application (as an argument to the AppActivate method). The parameter ProcessID identifies the application and an event handler thereof takes necessary parameters to continue the OS access to the Installable File System (IFS) Manager 312 that is responsible for arbitrating access to different file system components. In particular, the IFS Manager 312 is configured to act as an entry point for processes such as opening, closing, reading, writing files and etc. With one or more flags or parameters passed along, the access activates the DSM 302. If the document being accessed by the application is regular (non-secured), the document will be fetched from one

of the File System Driver (FSD) (e.g., FSD 314) and passed through the DSM 302 and subsequently loaded into the application through the IFS Manager 312. On the other hand, if the document being accessed by the application is secured, the DSM 302 activates the cipher module 310 and proceeds to obtain an authenticated user key to retrieve the access rules therein. If the access privileges satisfy the access rules, a file key will be retrieved to decrypt the encrypted data portion of the secured document by the cipher. As a result, the data portion or the document in clear mode will be loaded into the application through the IFS Manager 312.

According to one embodiment, the DSM 302 resides on a local disk (e.g., storage 136 of FIG. 1D) in a file that is structured like a dynamic-link library (DLL), typically with a SYS or IFS extension, and is loaded during system initialization. Once the DSM 302 is installed and initialized, a kernel communicates with it in terms of logical requests for file opens, reads, writes, seeks, closes, and so on. Through the IFS Manager 312, the FSD 314 translates these requests—using control structures and tables found on the volume itself—into requests for sector reads and writes for which it can call special kernel entry points called File System Helpers (FsHlps). The kernel passes the demands for sector I/O to an appropriate device driver and returns the results (e.g., the requested document) to the FSD 314. Upon receiving the results from the FSD 314 indicating that the requested document is secured, the DSM 302 activates the cipher module 310 included therein to decrypt the document if permitted by the access rules in the secured document.

FIG. 4A shows a flowchart of a process 400 of securing a document being created according to one embodiment of the present invention. At 402, a blank document is opened or created by an authoring application chosen and activated by a user. In a preferred procedure, the user may save the document in a folder that has already setup with a set of access rules. At 404, the set of predetermined access rules is received, preferably, in a markup language. As described above, the access rules may also be received by importation of a previously created file including desirable access rules, defaults of the user access privileges or individually created user access privileges.

At 406, a secret cipher key (i.e., a file key) is generated from a cipher module for the document and typically stored in a temp file that is generally not accessible by an ordinary user. The temp file will be erased automatically when the secured document is done (e.g., at a "Close" command from the application). At 408, the document is checked to see if a request to write the document into a local store is made. If such request is detected (which could be made manually by the user or periodically by the authoring tool or an OS), the document is encrypted with the file key at 410. One of the features in the present invention is that the stored document is always encrypted in storage even if it is still being processed (e.g., authored, edited or revised). When the user is done with the document, a "Close" request is activated to close the document. At 412, such a request is detected. As soon as such request is received, it means that a secured version of the document is being written into the store. At 413, the access rules and the file key are included in security information that is encrypted with the authenticated user key. Depending on implementation, a flag or signature and the security information can be included in the header. Alternatively, the header could include the security information without a flag. At 414, the header is attached to the encrypted document from 410 and subsequently the secured document is placed into the store at 418.

As described above, the secured document includes two encrypted portions, the header with encrypted security information and the encrypted data portion (i.e., the encrypted document). The two parts in the secured documents are encrypted respectively with two different keys, the file key and the user key. Alternatively, the two encrypted portions may be encrypted again with another key (or use the same user key) at 416.

In the case that there are a number of sets of access rules, each for a particular user or a group of users, it can be understood that the encrypted access rules at 413 are integrated with other sets of the encrypted access rules in a rules block as illustrated in FIG. 2C.2. As such, an access from one user or group will not affect other users or groups but the other users or groups will see perhaps an updated version of the encrypted document.

FIG. 4B shows a flowchart of an exemplary process 430 of receiving the access rules. The process 430 may be performed at 404 in FIG. 4A to facilitate the process of securing a document. To put less burden on a user, the present invention, as will be further described below, provides a one-time authentication mechanism, which significantly differs from prior art systems in which user authentication is required for each access to a secured document. In operation, once a user has been authenticated to access a secured document, authentication of the user would not be required. Also, once the user is authenticated, he/she can access other secured documents without being authenticated again as well.

Generally, there are at least two situations in which the user has to be authenticated before being able to access secured documents. In a first situation, a client machine is coupled to a network (e.g., LAN), a user thereof needs to authenticate himself/herself by providing his/her credential information when it is a first time to use the client machine. Commonly, the credential information is a set of username and password. If the user is registered, the provided credential information will match the user's identity in the server and hence the user will be authenticated. Once the user is authenticated, a user key associated with the user can be activated or authenticated. The user can now use the client machine and subsequently access secured documents. Other possible credential information may include the user's biometric information such as finger print and voice, etc. that can be obtained from a dedicated device attached to the client machine. One such device may be a finger print sensor from DigitalPersona, Inc. at 805 Veterans Boulevard, Suite 301, Redwood City, Calif. 94063. When biometric information of the user is captured, it can verify what the user claims to be. Depending on an implementation, a user key may be locally stored or retrieved remotely. In any event, the user key, before authenticated, is preferably in an illegible format (e.g., encrypted or scrambled with a pass phrase associated with the user) to prevent a possible hacking thereto. The user's authentication or the biometric information of the user may be used to validate, retrieve or authenticate the user key. As a result, an authenticated user key in clear form is readily available for the user to access any secured document. In a second situation, a client machine coupled to a network can accommodate whatever the user thereof intends to do except for requesting a secured document. When it comes to a request to a secured document, the user authentication process is invoked.

Referring back to FIG. 4B, the user authentication process is invoked, communication to a server (e.g., server 104 or 106) is checked at 432. If it is detected that no communication to the server is available, which may mean that the client machine may not be on a network or the server is down or other causes, the user may have at least three options. First,

the user can now access only non-secured documents or may generate secured documents at 434 if a public user key is available or retained in the client machine. Second, the user can keep trying to communicate with the server, in which case the process 430 goes back to 432 till a secured communication link is established. Third, the user may take advantage of another feature offered by the present invention, offline access at 433. In short, the user may access a limited number of secured documents on the client machine, the details of which will be provided below.

It is assumed that a secured link (possibly over HTTPS, VPN, SSL) is established between the client machine and the server. Now the process 430 goes to 436 where the user and/or the client machine itself needs to be authenticated. In some cases, it is needed to ensure that a secured document can only be accessed by a user from a permitted machine. Hence, in such cases, it is necessary to authenticate the user as well as the client machine from which the user is to access secured documents.

As far as the user is concerned, the user needs to furnish his/her credential information (e.g., username/password) to be verified. Once the user is authenticated by the server, the client machine needs to be authenticated. To ensure that a user is confined to one or more designated local computers and can only access secured document from these designated local computers, there is a determination of whether the user is using one of the designated local computers to access the secured documents. In operation and at 436, the client machine's identifier (e.g., a number from a network card) is checked by the server to determine: 1) whether this client machine can be used to access secured documents; and 2) whether the combination of the client machine and the user is valid. If the check process is successful, the process 430 goes to 438 otherwise the user can only work on non-secured documents at 434.

A user key associated with the user is authenticated at 438. At this point, the user is able to access secured documents. Certainly, the corresponding access privileges with the user as well as the access rules in a secured document ultimately determine whether the user can open the secured document.

After the user and the client machine the user is using are respectively authenticated or verified, the user key is activated (e.g., ready to use). The user key may have been newly generated or stored in an illegible format. The user authentication process retrieves the user key to a form that can be readily used and/or get the user key to the client machine.

It is assumed that the user is accessing or creating a secured document. At 440, the user access privilege originally set up by an administrator is activated, which determines when, where and what kind of secured documents he/she can access. Likewise, the default access rules for specific folders to store secured documents may be available for viewing or gathered at 442 and could be saved into a temp file to be eventually attached (in an encryption format) to an encrypted document being accessed or created by the user.

Although the description of the process 430 in FIG. 4B is based on the user authorization process formed in conjunction with a server. It is clear to those skilled in the art that the description is readily applied to other means for conducting the user authentication. For example, the user key can be authenticated, validated or retrieved by biometric information of the user as described above.

Referring now to FIG. 4C, there is shown a flowchart of process 450 of accessing a secured document according to one embodiment and shall be understood in conjunction with FIG. 3. At 452, an application is launched with a document being specified, for example, WINWORD.EXE is activated

to open a file named xyz.doc. As explained above, a handler from the OS identifies the application and enters the OS wherein the IFS manger is called upon at 454. The IFS manger activates a DSM module at 456 and at the same time, the IFS manger passes the handler to receive at 458 the selected document from a store. As the selected document passes through the DSM module, the selected document is determined whether it is secured or non-secured at 460. In general, there are at least two ways to examine the secure nature of the selected document. A first possible way is that the DSM module looks for a flag at the beginning of the document. As described above, in some secured documents, a flag, such as a set of predetermined data, is placed in the header to indicate that the document being accessed is secured. If no such flag is found, the process 450 goes to 470, namely, the selected document is assumed non-secured and thus allowed to pass the DSM module and loaded into the application from the IFS manger. A second possible way is that the DSM module looks for a header in a secured document. Being a secured document, there is a header attached to an encrypted data portion. The data format of the header shall be irregular in comparison with the selected document if it were non-secured. If the DSM module determines that the selected document has no irregular data format as required by the application, the process 450 goes to 470, namely, the selected document is assumed to be non-secured and thus allowed to pass through the DSM module and be loaded into the application from the IFS manger.

Now if it is determined at 460 that the selected document is indeed secured, the process 450 goes to 462 wherein the header or security information therein is decrypted with the authenticated user key. At 464, the access rules in the decrypted security information are retrieved. At 466, the access rules are compared to (or measured against) the access privileges associated with the user. If the measurement fails, which means that the user is not permitted to access this particular document, a notification or alert message may be generated by the DSM module to be displayed to the user at 467. Alternatively, the application itself can display an alerting message when it fails to open the selected document. If the measurement passes successfully, which means that the user is permitted to access this particular document, a file key is retrieved from the security information at 468 and used to decrypt the encrypted data portion in the selected (secured) document by a cipher module activated by the DSM module. As a result, at 470 the decrypted document or clear contents of the selected document is loaded into the application from the IFS manger.

Referring now to FIG. 5A, there is shown a functional block diagram of a server device 500 in which a server module 502 resides in a memory space 503 and is executable by one or more processors 501. The server device 500 also includes a network interface 504 to facilitate the communication between the server 500 and other devices on a network and a local storage space 505. The server module 502 is an executable version of one embodiment of the present invention and delivers, when executed, features/results contemplated in the present invention. According to one embodiment, the server module 502 comprises an administration interface 506, an account manager 508, a user key manager 510, a user monitor 512, a local server manager 514, a partner access manager 516, an access report manager 518, and a rules manager 520.

Administration Interface 506:

As the names suggests, the administration interface 506 facilitates a system administrator to register users and grant

respective access privileges to the users and is an entry point to the server module from which all sub-modules or the results thereof can be initiated, updated and managed. In one embodiment, the system administrator sets up hierarchy access levels for various active folders, storage locations, users or group of users. For example, as shown in FIG. 5B.1, different users can be assigned to different access privileges. User A may be an executive or a branch supervisor who has all the access privileges to any secured documents. User B has limited access privileges while everyone in user group C shares the same access privileges. The privileges may include, but not be limited to: open, edit write, print, copy, download and others. Examples of the other privileges are: altering access privileges for other users, accessing secured documents from one or more locations, and setting up a set of access rules for a folder different from those previously set up (perhaps by the system administrator). The respective user IDs assigned to the users facilitate the management of all the users. Unless specifically stated differently, a user or a corresponding user ID is interchangeably used herein to identify a human user, a software agent, or a group of users and/or software agents. Besides a human user who needs to access a secured document, a software application or agent sometimes needs to access the secured document in order to proceed forward. Accordingly, unless specifically stated, the "user" as used herein does not necessarily pertain to a human being. In general, a user who will access a secured document is associated with a user key to allow an encrypted header in a secured document to be unlocked (decrypted). The expiration or regeneration of a user key may be initiated by the system administrator. According to one embodiment, the administration interface 506 is a user graphic interface showing options for various tasks that an authenticated system administrator or operator may need to perform.

Account Manager 508:

Essentially, the account manager is a database or an interface to a database 507 (e.g., an Oracle database) maintaining all the registered users and their respective access privileges, and perhaps corresponding user keys (e.g., private and public keys). In operation, the account manager 508 authenticates a user when the user logs onto the server 500 and also determines if the user can access secured documents from the location the user is currently at. In general, the account manager 508 is where an enterprise may be able to control its users.

User Key Manager 510:

This module is configured to keep a copy of keys for each of the users in an organization. According to one embodiment, the user key manager 510 is not activated to retrieve the keys therein. In some situations, a key can be retrieved by the system administrator to access a secured document in case the key in a client machine is corrupted or the user or users who have the access privilege to access the secured document are no longer available. Optionally, the user key manager 510 is configured to expire some or all of the keys therein for security reasons. In one case, a user is no longer with the organization, the corresponding user key can be manually expired in the user key manager 510. In another case, a user's key has been used for a long period, the user key manager is configured to expire the old user's key and replace it with a newly generated key. Such replacement can be made transparent to the user and the new key may be uploaded to a client machine next time the user logs on therefrom. According to another embodiment, the user key manager 510 keeps a private key and a public key for each of the users. The public key is used to encrypt security information in a header and the private key

is used to decrypt the security information in the header. FIG. 5B.2 shows an exemplary table that may be maintained by the user key manager 510 in conjunction with account manager 508.

User Monitor 512:

This module is configured to monitor user's requests and whereabouts. Typically, a user is granted to access secured documents from one or more designated locations or networked computers. If a user has a higher access privilege (e.g., to permit to access from other than the locations or networked computers), the user monitor 512 may be configured to ensure that the user can have only one access from one of the registered locations or computers at all times. In addition, the user monitor 512 may be configured and scheduled to periodically push or respond to a pull request of an update of access privileges.

Local Server Manager 514:

This module is designed to be responsible for distributing an appropriate local module for a local server servicing a predetermined location or a predetermined group of users. According to one embodiment, the local server manager 514 replicates some or all of the server module 502 being executed on the server 500 and distributes the replicated copy to all the local servers. As a result, a user can access secured documents anywhere within the network premises covered by the local servers without being authenticated at a single central server, namely the server 500. According to another embodiment, the local server manager 514 replicates some of the server module 502 being executed on the server 500 and distributes the replicated copy to a corresponding local server. In this embodiment, each of the local servers will have its own customized replication from the server module 502. When a user has a sufficiently high access privilege (e.g., to permit to access from more than one locations or one computers) and the user monitor 512 can detect that the user has moved from an originally configured location serviced by one local server to another permitted location serviced by another local server. Upon a notification, the local server manager 514 is configured to reconfigure a local module for the local server that the user has newly contacted. Namely, the user is added as a user to the local server being newly contacted. If it is required that the user can access from only one computer at a time, regardless where it is in an organization, the local server manager 514 can also reconfigure the local module for the local server that the user has previously contacted. As a result, the user is removed from the local server that the user previously contacted.

Partners Access Manager 516:

A special module to manage non-employees accounts. The non-employees may be consultants to a business that requires the consultants to access certain secured documents. The partners access manager 516 generally works in accordance with other modules in the server but puts additional restrictions on such users being directly managed by the partners access manager 516. In one application, the partners access manager 516 generates a request to the user key manager 510 to expire a key or key pair for a consultant when an engagement with the consultant ends.

Access Report Manager 518:

A module is configured to record or track possible access activities and primarily works with a corresponding sub-module in a client module being executed in a client machine. The access report manager 518 is preferably activated by the system administrator and the contents gathered in the access

report manager 518 shall be only accessed by the system administrator or with authority.

Rules Manager 520:

In general, the rules manager 520 is an enforcement mechanism of various access rules. According to one aspect, the rules manager 520 is configured to specify rules based on i) data types (e.g., Microsoft Word), ii) group users or individual, iii) applicable rights, and iv) duration of access rules. Typically, a set of rules is a policy. A policy can be enabled, disabled, edited, deployed and undone (e.g., one or two levels). Policies managed by the rules manager 520 operate preferably on a global level. They are downloaded to the client machine during the login process (after the user is authenticated) and can be updated dynamically. In addition, respective policies may be associated with active folders (i.e., those designated places to store secured documents). These policies are also downloaded and updated on the client machine. Simple policies are also embedded in the document and provide document specific policies. According to one embodiment, a header is received by a local server from a client and the access rules from the header are retrieved. The key manager 510 is called upon to decrypt the encrypted security information in the header. The rules manager 520 is also called upon to parse the access rules from the security information and evaluate or measure the access rules against the access privilege of the user to determine whether the secured document can be accessed by the user. If the evaluation or measurement succeeds, a file key is retrieved and sent back to the client.

It should be pointed out that the server module 502 in FIG. 5A lists some exemplary modules according to one embodiment of the present invention and not every module in the server module 502 has to be implemented in order to practice the present invention. Those skilled in the art can understand that given the description herein, various combinations of the modules as well as modifications thereof without departing the spirits of the present invention, may achieve various desired functions, benefits and advantages contemplated in the present invention.

Referring now to FIG. 5B.3, there is shown a flowchart of a process 510 to update a user key 510. As described above, in some cases, there is a need to expire a user key and update the expired user key with a new one. Preferably, the process 510 is proceeded unnoticeably to the user, such as when the user logs onto the server. Optionally, the user is notified of the updating of his/her user key. In general, there can be at least two situations that demand the expiration/updating of a user key. When a user terminates with an organization, for security reasons, it is desirable to invalidate the user key associated with the user. Accordingly, at 511, the process 510 awaits a manual request. When a system administrator is notified of a departing employee, such a manual request can take place.

Alternatively, an organization or the system administrator can set up a time table to expire every user key under the management, say every six months, to replace the expired user key with a new one. At 512, the process awaits a timed request.

In any case, when the process 510 is caused to proceed forward with a request from 511 or 512, at 514, the key manager in the server module is consulted with to look up a user key being targeted or sought. Once the target key is retrieved, a corresponding new key is generated at 516 with a cipher. According to one embodiment, the cipher in use is the same one or substantially identical one used in a client module to encrypt/decrypt the header in a secured document. This will ensure that the newly generated user key is usable when

25

available in a client device. According to another embodiment, a pair of keys associated with a user is updated. Since the two keys are retained in the server and never leave the server, any appropriate cipher may be applicable for use to update the user keys.

Depending on the actual situation and an implementation in which the user key(s) is being replaced, the newly generated key(s) may be kept with the key manager or released to a client machine next time a corresponding user logs on therefrom. At **518**, the process **510** awaits a decision whether the newly generated keys remain with the server or is downloadable to a client. When the decision is to retain the newly generated key(s) in the server, the process **510** goes to **522** in which the new key are set to be associated with the same user. When the decision is to release the newly generated keys to the user next time the user logs onto the server, the process **510** goes to **522**. At **522**, the process **510** awaits a contact from the user. As described above, the user may login on any time from a client machine when he/she needs to access a secured document. When such contact does happen, the server will receive the credential information from the user to ensure that the user is who he/she claims to be. After the user is authenticated, the new keys are encrypted with the credential information at **524**. The credential information is provided by the user when requesting for authentication and may include a set of username and password or a biometric feature (e.g., a fingerprint) of the user. Regardless what a cipher is used, the newly generated keys are converted into an illegible format at **524**. The encrypted new keys are then uploaded or transmitted to the client machine at **526**. Upon receiving the encrypted new keys, the client machine is caused at **528** to decrypt the encrypted new keys to make the new user keys readily available for accessing secured documents or securing documents. In some cases, the client module in the client machine may be scheduled to scan in designated folders all available secured documents whose headers were originally encrypted by the old user key. These documents can be now encrypted again with the new key to ensure that the secured documents are indeed secured. In a preferable embodiment, the updating of user keys can be made to perform transparently as far as the users are concerned. In other words, the users are not aware that the process **510** has happened and the new keys are now installed.

Referring now to FIG. **5B.4**, there is shown a flowchart of a server assisted process **530** of accessing secured documents according to one embodiment of the present invention. The process **530** is discussed below with reference to FIG. **3**. One of the features in the process **530**, as will be further described below, is that a user key or user keys (i.e., a private and a public key) never leave the server where the keys are generated, which may enhance the level of security to the keys.

It is assumed that a user attempts to access secured documents from a client machine and has been authenticated by a server (e.g., server **500**) running the access control management. When a secured document is selected, document securing module (DSM) **302** of FIG. **3** determines that a user key is required to access the security information in the secured document. According to this embodiment, the DSM **302** is configured to separate the header from the secured document and then send the header to the server. At **532**, such header is received from the client machine. As described before, the header includes security information in an encrypted form. At **534**, a private user key associated with the user is retrieved. The private user key can, for example, be retrieved from the key manager. The encrypted security information in the

26

header is then decrypted with the retrieved private user key at **536**. As a result, the access rules for this secured document are obtained at **538**.

At the same time, the access privilege for the user is retrieved at **540**. The access privilege can, for example, be retrieved from the account manager. With the given access privilege and the access rules of the document, an evaluation takes place at **542** to determine if an access right can be granted. If the user's access privilege does not permit access according to the access rules, the process **530** goes to **544**. At **544**, an error message may be generated to forward to the client machine so that the user knows his access privilege does not allow him to access the selected document. However, on the other hand, if the user's access privilege does permit access according to the access rules, the process **530** goes to **546**. At **546**, the file key in the security information can be retrieved. At **548**, the file key is forwarded to the client machine. With the received file key, the DSM **302** activates the cipher module **310** to decrypt the encrypted data portion of the selected document.

FIG. **5B.5** shows a flowchart of a server assisted process **550** of securing a document according to one embodiment of the present invention. The process **550** is discussed below with reference to FIG. **3**. It is assumed that a user has just finished a document and decided to secure the document. One possible way to secure the document, as described above, is to place it in a designated folder that is preset for or associated with a set of access rules. In other words, all documents in the folder may have substantially similar access rules.

Accordingly, the DSM **302** is activated and in return also activates the cipher module **310**. If the document is being secured for the first time, the cipher module **310** will generate a new file key. If the file is already in existence, typically the cipher module **310** will not generate a new file key unless requested to do so. Before the process **550** starts, it is also assumed that the user has been authenticated and a link between the client machine and the server is established.

Upon receiving the file key at **552** from the client machine, a public user key associated with the user is retrieved, for example, from the key manager at **554**. The access rules for the document are obtained at **556**. As described above, there are a number of ways to obtain the access rules. One possible way is to receive them directly from the client machine. Another possible way is to get from the rules manager locally if the document is placed in a folder setup by the system. Given the access rules and the file key, it is now possible to form the security information at **558**. The security information is then encrypted with the public user key at **560**. In one embodiment similar to FIG. **2C.2**, the access rules and the file key are placed in a segment if there are other segments already in the rules block.

At **562**, the header for the document is generated. Depending on implementation, the header may include other information (e.g., a flag) that is not encrypted. Alternatively, a user block including the current user is also added into the header. The header is then forwarded at **564** to the client machine where the header is attached or integrated with the encrypted data portion to produce a secured document. It should be noted that the process **550** is also applicable when a secured document is being revised and saved into a store.

FIG. **5C** shows a functional block diagram of a local server device **570**. The local server device **570** is generally similar to that of a server as illustrated in FIG. **5A**. Accordingly, many parts illustrated in FIG. **5C** are not to be described again to avoid obscuring aspects of the present invention. As shown in FIG. **5C**, the local server device **570** also executes a module, referred herein as a local module **572** which is configured to

27

be a complete or partial replication of the server module **502** of FIG. **5A**. As one of the features in the present invention, the local module **572** provides the dependability, reliability and scalability of the centralized access control management being undertaken by the central server **500** of FIG. **5A**. As such, not all authentication requests need to be handled at one central point without losing control of the access control management. As another feature of the present invention, the users are not affected if the central server is brought down for maintenance and the connection to the central server is not available. If a number of local servers are used and each has a replication of the server module, the reliability of servicing the users is greatly enhanced. The possibility that a user wants to access a secured document but could not be authenticated is minimized.

According to one embodiment, the local module **572** is a localized version of some of the server module **502** in the central server **500** and services the users local to the local server. For example, in FIG. **5D**, it shows a table **584** of all the users managed by the central server **500**. Among the users, John's access privilege **585** is at level 10 (assumed highest) and can access secured documents all days at all times from any of the three locations. Dell's access privilege **586** is at level 1 (assumed lowest) and can access secured documents 8 hours (e.g., 9:00 AM-5 PM) a day, Monday to Friday and only from location A. Mike's access privilege **587** is at level 5 and can access secured documents 12 hours Monday to Saturday and only from locations A and B. If three local servers are employed respectively for the three locations A, B and C, there can be three different access control management possibilities as shown in FIG. **5E**, each assigned to one local server. As a result, the local users need only to check with the corresponding local server and none of the users would be affected if other local servers are down for whatever reasons or disconnected from the central server.

FIG. **5F** illustrates the accessibility for each of the users. Working with the user monitor **512** in the server module **500**, the local module **572** can be configured dynamically. In one embodiment, instead of having three local modules, each permitting John to access from any of the three locations, only one local module is configured to permit John to access from one of the three locations at one time. One of the advantages of the additional security this dynamic configuration mechanism provides is that secured documents can be accessed by John from only one location at a time. In fact, it is not a desirable security feature for a person to log into a system or to access secured documents from two physical locations at the same time. Also for security reasons, it is preferably that a user, regardless of his/her access privilege, be permitted only a single access location at all times.

FIG. **5G** shows a dynamic configuration affecting access control management. At one time, the system knows that John is accessing from location A. When John moves to location B, upon his login, the central server (i.e., the user monitor in the server module) detects his whereabouts and thus notifies the local server manager **514** to reconfigure the local modules for both location A and location B. As shown in FIG. **5G**, the local access control management **589** in a local server for location A is no longer responsible for John, while the local access control management **590** in a local server for location B takes over to be responsible for John. As a result, John is now permitted to access secured documents from location B but no longer from location A. FIG. **5H** illustrates graphically that now John's accessibility has moved from location A to location B. Hence, John together with Mike, both can access

28

secured documents from location B and both of them are temporarily not permitted to access documents from location A.

If Mike happens to move to location A, again the local modules will be reconfigured as shown in FIG. **5I**. Because of John's access privilege, John can access secured documents from location C if he moves thereto.

FIG. **6A** shows a flowchart of a user authentication process **600** that may be implemented in the central server **500** or the local server **570**. As described above, there are at least two situations that will call upon the process **600**—initial login to a networked client machine and first access to a secured document. When either of these situations happens, a client module in the client machine initiates a request that is transmitted to a server running a module providing the access control management to start the process **600**.

At **602**, the server awaits the request. Upon receiving the request from the client machine, the server proceeds at **604** to determine if the user and the client machine from which the user attempts to access a secured document have been authenticated. If both have already been authenticated, there will be no more authentication processing for either of the user or the client machine. On the other hand, the authentication processing continues when the user and the client machine have not already been authenticated. In one embodiment, the server may initiate a secured link with the client machine if both the server and the client machine are coupled to an open network, such link may be over HTTPS or supported through VPN. Alternatively, there may be a direct link between the client and the server if another authentication means is employed.

At **606**, the server responds to the received request with an authentication response. Depending on implementation, such response may be a dialog box to be displayed on the screen of the client machine, a command or other demand. In any case, the response requires that credential information be provided by the user. As described before, the credential information may be a set of username and password or biometric information of the user and must be received from the user at **608** before the authentication may proceed forward.

At **610**, upon receiving the credential information, the server needs to determine if the user is an authorized one to access any secured documents maintained in a repository, a local store, the server itself or other device accessible over the network. This may involve in a match of the received credential with what is previously stored in the server. It should be noted that the server may be the central server or a local server. Those skilled in the art can understand that the description is equally applied in either one of the settings. If the match fails, namely the user is unauthorized, the process **600** goes back to the beginning to continue waiting for a request. In other words, the current request to access the secured documents or login to the system is abandoned. If the match succeeds, the user is recognized as being authorized.

At the same time, the client machine goes to a similar authentication by, perhaps, an IP address thereof, or a network card identification therein, or other means that uniquely identifies the client machine.

With authentication of both the user and the client machine, the process **600** goes to **612** where the user's access privilege is retrieved and activated. Depending on implementation, an activation of the user's access privilege may be a downloading of a file containing the access privilege to the client machine, a decryption of a local file containing the access privilege, or simply an activation of the user in a memory space of the server. In any case, at this point, the user's access

privilege is readily accessible, thus permitting the user to access the secured documents from the authenticated client machine.

According to one embodiment, XML-RPC is used to facilitate the communication between a server (e.g., a local server or a central server) and a client machine. XML-RPC is a simple and portable way to make remote procedure calls over HTTP. It can be used with Perl, Java, Python, C, C++, PHP and many other programming languages. In addition, XML-RPC allows software running on disparate operating systems, running in different environments to make procedure calls over a data network. It is remote procedure calling using HTTP as the transport and XML as the encoding. XML-RPC is designed to be as simple as possible, while allowing complex data structures to be transmitted, processed and returned.

In the embodiment of implementing the dynamic configuration mechanism, the user contacts the server from a client machine, the local module in the local server is examined to determine if it has authorization to service the user from the client machine at this location. If not, the local server will communicate with the central server to determine if the local module shall be reconfigured or updated to subsequently support the user from the client machine at this location. With the reconfigured local module, the user and the client machine can be authenticated and the user's access privilege is made accessible, thus permitting the user to access secured documents from the authenticated client machine.

To continue the above embodiment employing one or more local servers to store a localized version of the server module so as to provide only localized access control management. FIG. 6B shows a flowchart of dynamically configuring the access control management process 620 which may be implemented in one or more local servers. The process 620 is performed 610 and 612 of FIG. 6A. At 610, the user has been determined to be authenticated. Next, at 622, the server needs to determine the number of locations or computers from which the user is authorized to access the secured document. In operation, the user's access privilege is examined. Typically, the user's access privilege includes information identifying where (e.g., a permitted location, a geographic location or a local area network) and/or which local computers the user can utilize (e.g. permitted computers). In some case, a user travels a lot among a few offices in several geographic locations, thus the user could be privileged to access secured documents from either one of these geographic locations/computers.

At 624, the current location of the user from which the request is received is examined to determine if it is from the permitted locations in the access privilege. When the current location is not among the permitted locations, the process 620 goes to 626 which may send a notification to the user or simply denies the request. If the current location is among the permitted locations, the process 620 goes to 628 where the local module providing localized access control management at present time is examined (e.g., in the local server manager 514 of FIG. 5A) to determine if the user is under the localized access control management thereof. If the user is under the localized access control management by the local module, the process 620 goes to 612 of FIG. 6A. If the user is not under the localized access control management by the local module, the server needs to determine at 630 which local module previously provided localized access control management for the user. Once the information is gathered from the local modules of different local servers, a reconfiguration of the local modules takes place at 632. Essentially, the user support is removed from one local module and added to another local module, which will be further described in FIG. 6C.

At 634, the newly configured local modules are respectively uploaded to the corresponding local servers. As a result, the user can access secured documents from the new location while the system is assured that only one location/computer access permit is granted at all times.

One of the features in the mechanism of dynamically reconfiguring local modules is the dependability, reliability and scalability of the central access control management by the central server 500 of FIG. 5A. When an enterprise has many employees in multiple locations, the local servers can be added to accommodate the needs without compromising the performance. In fact, the users are not much affected for a predetermined period if the respective connections between the central server and the local servers are not available.

FIG. 6C shows a flowchart of reconfiguring the local modules process 640 according to one embodiment. The process 640 is, for example, processing performed at 632 of FIG. 6B. At 642, a first local module that previously supports the user at first location is identified. At 644, the first local module is reconfigured to essentially remove support to the user at the first location. The newly configured first local module is then uploaded at 646 to the corresponding local server to be effective, such that the user is no longer supported at that local server. At 648, a second local module that is to support the user at 2nd location (i.e., currently where the user is) is identified. At 650, the 2nd local module is reconfigured to essentially add the support to the user at the 2nd location. The newly configured second local module is then uploaded at 652 to the corresponding local server to be effective as such the user is now supported at the local server.

The configuration of a user's access to secured document is sometimes referred to as a provisioning process. The dynamic provisioning that has been described above is believed to provide the necessary security means needed by a large enterprise having employees in several locations without the loss of the centralized access control management at a central server. Further, the use of multiple local servers to support the central server can provide increased dependability, reliability and scalability.

Referring now to FIG. 7A, there is shown a functional block diagram of a client machine 700. As used herein, the client machine 700 is a computing device primarily used by a user to access secured documents. The client machine 700 can, for example, be a desktop computer, a mobile device or a laptop computer. According to one embodiment, the client machine 700 includes a processor 701, a client module 702, a memory space 703, a network interface 705 and a local store 707. The client module 702 resides in the memory space 703 and, when executed by the processor 701, delivers features, advantages and benefits contemplated in the present invention. Through the network interface 705, the client machine 700 is capable of communicating over a data network with other computers, such as a server. From the client machine 700, a user can access secured documents located in a repository (store) 706 that may be in the client machine 700, another networked device, or other storage means. A client module 702 is an executable version of one embodiment of the present invention. According to one embodiment, the client module 702 includes a number of sub-modules including an access report module 704, a user verifying module 710, a key manager 708, a document securing module 711 and an off-line access manager 714.

Access Report Module 704:

This module is a software agent configured to record access activity and associated with an authenticated user. It reports to an access report module in the central server so that a record

31

may be established as to what secured document has been accessed by which user during what time. In particular, the access report module **704** is activated to capture access activities of the user when the client machine is not networked. The access activities will be later synchronized with the counterpart in the server to facilitate the access control management for the offline access.

Key Manager **708**:

One of the purposes for the key manager **708** is to ensure that a secured document is still usable when the secured document is being accessed by an application that suddenly crashes. According to one embodiment, after the encrypted header is decrypted, the file key is then copied or a copy thereof is stored (cached) into the key manager **708**. The file key is then used to decrypt the encrypted document. A clear document is now available to the application. If the application crashes due to power outage or interfered by another application or OS, the file key in the header could be damaged. If no copy of the file key is available, the secured document may not be usable any more because the encrypted document would not be decrypted without the file key. In this case, the reserved key maintained in the key manager can be used to replace the damaged key and decrypt the encrypted document. After the user saves the file again, the file key is put back into the header. Another purpose for the key manager **708** is to cache a user key or keys of an authenticated user.

User Verifying Module **710**:

This module is responsible for determining if a user who is accessing a secured document has been authenticated otherwise it will initiate a request for authentication with a local server or a central server. In other words, the user verifying module **710** is always consulted before a permission is granted to the user seeking access to a secured document. According to one embodiment, a user key or keys of an authenticated user are stored (cached) in the key manager **708** once the user is authenticated by the user verifying module **710** via the server. When a secured document is accessed, the user key must be retrieved from the key manager **708** to decrypt the encrypted security information in the header of the secured document.

Document Securing Module **711**:

As described above, the DSM **711** includes a cipher **712** that is used to generate a file/user key and encrypt/decrypt a document/header. In addition, other securing means may be implemented in the DSM **711**, for example, a filter to block copying contents in a secured document into a non-secured document or a link from a secured document/original source to another document or recipient source.

Off-Line Access Manager **714**:

This module becomes effective only when the networked client machine is off the network, namely, the communication with a local server or a central server is not currently available. For example, a user is on the road and still needs to access some secured documents in a laptop computer. When live consultation is not available, the off-line access manager **714** is activated to ensure that the authorized user still can access the secured document but only for a limited time and perhaps with a limited privilege.

It should be pointed out that the client module **702** in FIG. 7A lists some exemplary sub-modules according to one embodiment of the present invention and not every module in the server module **702** has to be implemented in order to practice the present invention. Those skilled in the art can understand that given the description herein, various combi-

32

nations of the sub-modules, may achieve certain functions, benefits and advantages contemplated in the present invention.

Many aspects of the operations of the client module **702** have been described above. The client module **702** can provide off-line access capability to a user to permit working with a secured document remotely with respect to a server (i.e., the central server or a local server). The dependence on the server (either one of the central server or local server) is so minimal that the feature can be equally applied to mobile users. Referring now to FIG. 7B, there is shown a flowchart of providing the off-line access process **720** in accordance with one embodiment of the present invention.

When a user has decided to be away from a company's premises for a certain period and will need to access some secured documents in a client machine (e.g., a laptop computer) that is to be carried with the user, the user may get preauthorization from the server before the user disconnects the client machine from the network. At **722**, the preauthorization request is made in the client machine to seek an approval of an off-line access request from a server (e.g., a central server or a local server). Depending on an exact implementation, a response to the preauthorization request received from the server may be a dialog box requesting further information from the user for the server to proceed with the off-line access request.

At **724**, the user enters necessary information to the off-line access request that may include a specific time period, the user's identity. Perhaps, the off-line access request may also include the names of the secured documents or directories/folders in which secured documents are located and will be accessed off-line. In general, the specific time is manually entered or selected while the user's identity is automatically entered since the user typically has been previously authenticated and the client machine has the user's identity. The off-line access request is then forwarded to the server where the off-line access request is processed. It is assumed that the user is authorized to have such off-line access privilege.

In operation, there are a number of possible ways to enable the off-line access capability. One exemplary way is to place a time-sensitive access amendment to the desired secured documents, for example, the user is pre-authenticated by granting a pair of newly generated short-lived user keys or uploading the user's key or keys in illegible format to the client machine (only the private key is needed if only to access secured documents and both are needed if also to secure newly created documents). In other words, the user's access privilege or the access rules in the selected secured documents have been updated for the requested period. Accordingly, depending on implementation, the amended access rules, the amended access privilege or a time-sensitive user key(s) is received from the server at **726**.

At **728**, the original access rules or the user's original access privilege or the original user key(s) is modified, updated or temporarily overwritten. When the amended access rules are received, the secured documents are processed to include the amendments in the access rules so that the user can access them later even when off-line. When the amended access privilege is received, the user's original access privilege is temporarily revised with the received amendments so that the user can now access secured documents off-line. When the time-sensitive user keys are received, the user's original keys are suspended (e.g. put into an illegible format and they are no longer readily usable) and the newly received keys will be effective during the off-line access period. FIG. 7C illustrates that an amendment of the access rules is placed into a secured document that can be

33

accessed by Users, A, B, C and D, wherein User A has requested for the off-line access and has been granted off-line access for the request, while Users B, C and D cannot access the secured documents off-line.

For security purposes, the amendment will typically expire by the end of the specific off-line time regardless if the user has returned or not. This feature is important to the situations in which the client machine (e.g. a laptop computer) is separated from the user or possessed by an unauthorized person, because the secured documents in the client machine can be no longer accessed with the expired user keys even if the user's confidential information (username/password) is hacked. Therefore, at 730, the process 720 keeps checking if the off-line time has ended. If not, the user can still access the secured documents off-line. When it is detected that the off-line time has expired, the process 720 goes to 734 wherein the original access rules are restored so that the secured documents can no longer be accessed off-line.

Similarly, the user's amended access privilege may be configured to expire as well when it is detected that the off-line time is expired, the process 720 goes to 734 wherein the user's original access privilege is restored so that the secured documents can no longer be accessed off-line. According to one embodiment, the amended access privilege is overwritten by the original access privilege.

To account for the situation in which the user may cut short of his/her travel, the process 720 may be configured to initiate the restoration of the original setting for the secured documents or the user's access privilege. At 732, the client machine detects that a connection to a access control server has been made; hence, it is assumed that the off-line access is no longer needed. The process 720 goes to 734 where the restoration of the original setting for the secured documents, the user's access privilege or user's keys takes place. As a result, the secured documents can no longer be accessed off-line from the client machine.

In any case, it is preferable to invoke the access report module 704 in the client module 702 to record the access activities by the user during the off-line access. The next time the user connects to the server, the access activities of the secured documents can be reported to the server to facilitate the access control management or synchronization of the secured documents accessed during the off-line period.

There are numerous functions, benefits and advantages in the present invention. One of the functions, benefits and advantages is that the securing mechanism contemplated in the present invention keep selected digital assets under protection at all times by employing access rules in the secured digital assets. As such only authorized user with authenticated machines can access the secured digital assets. Other functions, benefits and advantages are apparent to those skilled in the art given the detailed description herein.

The present invention may be implemented as a method, a system, a computer readable storage medium, a computer program product, and other forms that achieve what is desired herein. Those skilled in the art will understand that the description could be equally applied to or used in other various different settings with respect to various combinations, embodiments, or settings provided in the description herein.

The processes, sequences or steps and features discussed above are related to each other and each is believed independently novel in the art. The disclosed processes, sequences or steps and features may be performed alone or in any combination to provide a novel and unobvious system or a portion of a system. It should be understood that the processes, sequences or steps and features in combination yield an equally independently novel combination as well, even if

34

combined in their broadest sense, i.e., with less than the specific manner in which each of the processes, sequences or steps and features has been reduced to practice.

The forgoing description of embodiments is illustrative of various aspects/embodiments of the present invention. Various modifications to the present invention can be made to the preferred embodiments by those skilled in the art without departing from the true spirit and scope of the invention as defined by the appended claims. Accordingly, the scope of the present invention is defined by the appended claims rather than the foregoing description of embodiments.

We claim:

1. A computer implemented method for securing a file, the method comprising:
 - determining whether the file stored in a file system and being accessed is secured;
 - if the file is determined to be secured, activating a cipher module and loading the file from the file system through the cipher module into an application; and
 - if the file is determined to be non-secured, loading the file from the file system into the application without activating the cipher module, wherein the file includes a header having a file key, the file key is encrypted with a user key, and the user key is different from the file key.
2. The method of claim 1, wherein the cipher module, once activated, operates within an operating system.
3. The method of claim 1, wherein the file further includes an encrypted portion and the header includes or points to security information including the file key used to decrypt the encrypted portion.
4. The method of claim 3, wherein the loading the file from the file system through the cipher module into the application comprises:
 - retrieving the file key;
 - decrypting the encrypted portion with the file key in the cipher module; and
 - sending the file in clear mode to the application.
5. The method of claim 4, wherein the retrieving the file key comprises:
 - obtaining the user key; and
 - decrypting security information including the file key with the user key to retrieve the file key.
6. The method of claim 1, further comprising:
 - launching the application when a request to access the file is received.
7. A computer implemented method for securing a file, the method comprising:
 - determining if the file stored in a file system and being accessed includes a header, wherein existence of the header indicates that the file is secured, wherein the header includes a file key, the file key is encrypted with a user key, and the user key is different from the file key;
 - activating a cipher module and loading the file from the file system through the cipher module into an application if the file is determined to be secured; and
 - loading the file from the file system into the application without activating the cipher module if the file is determined to be non-secured.
8. A computer implemented method for securing a file, the method comprising:
 - determining if the file stored in a file system and being accessed has a flag, wherein existence of the flag indicates that the file is secured, wherein the file includes a header having a file key, the file key is encrypted with a user key, and the user key is different from the file key;

35

activating a cipher module and loading the file from the file system through the cipher module into an application if the file is determined to be secured; and

loading the file from the file system into the application without activating the cipher module if the file is determined to be non-secured.

9. A computer implemented method for securing a file, the method comprising:

determining whether the file stored in a file system and being accessed is secured, wherein the file includes a header and an encrypted portion, the header including or pointing to security information including a file key used to decrypt the encrypted portion, wherein the security information including the file key is encrypted with a user key, and wherein the security information further includes access rules to control how and by whom the file is to be accessed;

if the file is determined to be secured, activating a cipher module, loading the file from the file system through the cipher module into an application, retrieving the file key, obtaining the user key, decrypting the security information with the user key to retrieve the file key, and decrypting the encrypted portion with the file key in the cipher module, and sending the file in clear mode to the application; and

if the file is determined to be non-secured, loading the file from the file system into the application without activating the cipher module.

10. The method of claim 9, wherein the loading the file from the file system through the cipher module into the application only happens if an access privilege is within permissions granted by the access rules.

11. A computer implemented method for securing a file, the method comprising:

maintaining a file key in a temporary memory space;

encrypting the file with the file key in a cipher module to produce an encrypted portion;

preparing security information for the encrypted portion, the security information being encrypted with a user key and including the file key and access rules to control access to the encrypted portion, wherein the access rules in the security information comprise user information identifying who has access to the encrypted portion and how the encrypted portion is to be accessed; and

attaching the security information to the encrypted portion.

12. The method of claim 11, further comprising deleting the file key from the temporary memory space when the attaching the security information to the encrypted portion is complete.

13. The method of claim 11, wherein the encrypting the file with the file key, the preparing the security information, and the attaching the security information happen whenever the file is caused to be stored.

14. The method of claim 11, wherein the encrypting the file with the file key, the preparing the security information, and the attaching the security information happen upon receiving an instruction from an application or an operating system supporting the application.

15. The method of claim 14, wherein the instruction is one of (i) Save, (ii) Close or (iii) Exit, all provided in the application.

16. The method of claim 14, wherein the instruction is generated from an automatic operation of saving the file being opened into a storage space, the automatic operation being triggered by the application itself or the operating system.

36

17. The method of claim 11, wherein the user key is associated with a member selected from a group consisting of a user, a device, a software module, and a group of users.

18. The method of claim 11, further comprising: launching an application that accesses the file.

19. A computer implemented method for providing access control to a file, the method comprising:

forwarding a request to access the file to a file system manager in an operating system;

activating a document securing module by the file system manager to determine whether the file stored in a file system driver and being accessed is secured, wherein the file includes a header having a file key, the file key is encrypted with a user key, and the user key is different from the file key;

activating a cipher module if the file is determined to be secured; and

loading the file from the file system driver through the cipher module into an application.

20. The method of claim 19, further comprising:

retrieving security information from the file if the file is determined to be secured, the security information including the file key and access rules; and

obtaining an access privilege requesting to access the file.

21. The method of claim 20, wherein the activating the cipher module proceeds successfully when the access privilege is within permissions granted by the access rules.

22. The method of claim 21, wherein the activating the cipher module comprises decrypting an encrypted portion of the file with the file key.

23. The method of claim 19, further comprising:

launching the application under the operating system when the request to access the file is received.

24. A computer-readable storage medium having stored thereon, computer-executable instructions that, if executed by a computing device, cause the computing device to perform a method comprising:

determining whether the file stored in a file system and being accessed is secured;

if the file is determined to be secured,

activating a cipher module; and

loading the file from the file system through the cipher module into an application; and

if the file is determined to be non-secured,

loading the file from the file system into the application without activating the cipher module;

wherein the file includes a header having a file key, the file key is encrypted with a user key, and the user key is different from the file key.

25. The computer-readable storage medium of claim 24, wherein the file further includes an encrypted portion and the header includes or points to security information including the file key used to decrypt the encrypted portion.

26. The computer readable storage medium of claim 24, wherein the program code stored on the medium, if executed, causes the application to be launched when a request to access the file is received.

27. A computer-readable storage medium having stored thereon, computer-executable instructions that, if executed by a computing device, cause the computing device to perform a method comprising:

determining if the file stored in a file system and being accessed includes a header, wherein existence of the header indicates that the file is secured, wherein the header includes a file key, the file key is encrypted with a user key, and the user key is different from the file key;

37

if the file is determined to be secured,
 activating a cipher module; and
 loading the file from the file system through the cipher
 module into the application; and
 if the file is determined to be non-secured,
 loading the file from the file system into the application
 without activating the cipher module.

28. The computer-readable storage medium of claim 27,
 wherein the loading the file from the file system driver
 through the cipher module into the application comprises:

retrieving the file key;
 decrypting an encrypted portion with the file key in the
 cipher module; and
 sending the file in clear mode to the application.

29. The computer-readable storage medium of claim 28,
 wherein the retrieving the file key comprises:

obtaining the user key; and
 decrypting security information including the file key with
 the user key to retrieve the file key.

30. A computer-readable storage medium having stored
 thereon, computer-executable instructions that, if executed
 by a computing device, cause the computing device to per-
 form a method comprising:

determining whether the file stored in a file system and
 being accessed is secured, wherein the file includes a
 header and an encrypted portion, the header including or
 pointing to security information including a file key used
 to decrypt the encrypted portion, wherein the security
 information including the file key is encrypted with a
 user key, and wherein the security information further
 includes access rules of how and by whom the file is to be
 accessed;

if the file is determined to be secured,
 activating a cipher module; and
 loading the file from the file system through the cipher
 module into the application;
 retrieving the file key;
 obtaining the user key;
 decrypting the security information with the user key to
 retrieve the file key;
 decrypting the encrypted portion with the file key in the
 cipher module; and

sending the file in clear mode to the application; and
 if the file is determined to be non-secured,
 loading the file from the file system into the application
 without activating the cipher module.

31. The computer-readable storage medium of claim 30,
 wherein the loading the file from the file system through the
 cipher module into the application proceeds if an access privi-
 lege is within permissions granted by the access rules.

32. A computer-readable storage medium having stored
 thereon, computer-executable instructions that if executed by
 a computing device, cause the computing device to perform a
 method comprising:

maintaining a file key in a temporary memory space;
 encrypting the file with the file key in a cipher module to
 produce an encrypted file, wherein the file has been
 opened with an application and the cipher module oper-
 ates transparently as far as a user executing the applica-
 tion is concerned; and

storing, in a storage space, a secured file including the
 encrypted file and a header, wherein the header includes
 or points to security information including the file key,
 wherein the security information further includes access
 rules of how and by whom the file is to be accessed.

38

33. The computer-readable storage medium of claim 32,
 the method further comprising deleting the file key from the
 temporary memory space if the application closes the file.

34. The computer-readable storage medium of claim 32,
 wherein the encrypting the file with the file key happens if the
 file is caused to be stored.

35. The computer-readable storage medium of claim 32,
 wherein the encrypting the file with the file key happens an
 instruction from the application or an operating system sup-
 porting the application.

36. The computer-readable storage medium of claim 35,
 wherein the instruction is one of (i) Save, (ii) Close or (iii)
 Exit, all provided in the application.

37. The computer-readable storage medium of claim 35,
 wherein the instruction is generated from an automatic opera-
 tion of saving the file being opened into the storage space, the
 automatic operation is either triggered by the application
 itself or the operating system.

38. The computer-readable storage medium of claim 32,
 further comprising encrypting the security information with a
 user key associated with a member selected from a group
 consisting of a user, a device, a software module, and a group
 of users.

39. The computer-readable storage medium of claim 32,
 further comprising attaching the header to the encrypted file,
 wherein the header includes the security information
 encrypted in addition to a flag indicating that the file is
 secured.

40. The computer readable storage medium of claim 32,
 wherein the program code stored on the medium, if executed,
 causes the application to be launched.

41. A computing device for securing a file, comprising:
 an application configured to access the file that includes
 security information and an encrypted portion, the secu-
 rity information further including a file key and access
 rules, the encrypted portion being an encrypted version
 of the file; and

a cipher module configured to activate upon determining
 that the file being accessed is secured;

wherein the security information is configured to be
 encrypted with a user key, is configured to be decrypted
 with the user key when authenticated, and includes
 access rules of how and by whom the file is to be
 accessed; and

wherein the file key is configured to be retrieved to decrypt
 the encrypted portion only after the access rules have
 been successfully measured against access privilege.

42. The computing device of claim 41, further comprising
 an operating system configured to support operations of the
 application, and wherein the cipher module is embedded in
 the operating system.

43. The computing device of claim 41, wherein the cipher
 module is configured to operate in a path through which the
 file is caused to pass when accessed by the application.

44. The computing device of claim 41, further including a
 memory space and a storage space, and wherein the file key is
 temporarily kept in the memory space when the file is suc-
 cessfully loaded into the application.

45. The computing device of claim 44, wherein the file key
 is deleted from the memory space as soon as the file is written
 back to the storage space.

46. The computing device of claim 41, wherein the user key
 becomes authenticated by an authentication process.

47. The computing device of claim 41, wherein the com-
 puting device is coupled to a second computing device over a

39

data network and the user key becomes authenticated only after successful logging from the computing device into the second computing device.

48. The computing device of claim **41**, wherein the computing device is provided with means for capturing biometric data and the user key becomes authenticated only after the biometric data is successfully verified.

49. The computing device of claim **41**, wherein the user key becomes authenticated after the computing device receives credential information.

40

50. The computing device of claim **49**, wherein the credential information includes at least one of a password, biometric information, or personalized information.

51. The computing device of claim **50**, wherein the biometric information is captured from a device coupled to the computing device.

52. The computing device of claim **41**, wherein the application is launched to access the file.

* * * * *