



US010368281B2

(12) **United States Patent**
Ganesan

(10) **Patent No.:** **US 10,368,281 B2**
(45) **Date of Patent:** ***Jul. 30, 2019**

(54) **TELEPHONE WITH AUTOMATIC SWITCHING BETWEEN CELLULAR AND VOIP NETWORKS**

(58) **Field of Classification Search**

CPC H04W 88/06; H04W 36/14; H04W 8/005;
H04W 48/18; H04W 48/20; H04W 60/04;
(Continued)

(71) Applicant: **Vasu Networks Corporation**,
Cupertino, CA (US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,009,328 A 12/1999 Muszynski
6,175,737 B1 1/2001 Kao
(Continued)

(72) Inventor: **Vasudevan Ganesan**, Cupertino, CA
(US)

(73) Assignee: **Vasu Networks Corporation**, San Jose,
CA (US)

FOREIGN PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

CN 1723719 A 1/2006
DE 200310113 1/2004
(Continued)

This patent is subject to a terminal disclaimer.

OTHER PUBLICATIONS

(21) Appl. No.: **15/480,293**

3GPP Organization Project, "3rd Generation Partnership Project;
Technical Specification Group Services and System Aspects Service
Aspects; Handover requirements between UTRAN and GERAN or
other radio systems (Release 8)", Mar. 2006, pp. 1-20
(Continued)

(22) Filed: **Apr. 5, 2017**

(65) **Prior Publication Data**

US 2017/0208522 A1 Jul. 20, 2017

Primary Examiner — Tu X Nguyen

(74) Attorney, Agent, or Firm — Haverstock & Owens
LLP

Related U.S. Application Data

(63) Continuation of application No. 14/806,482, filed on
Jul. 22, 2015, now Pat. No. 9,648,538, which is a
(Continued)


(57) **ABSTRACT**

A mobile communication device includes, in part, a cellular communication module, a first antenna adapted to receive and transmit data between the mobile communication module and a cellular network, a Wireless Fidelity (Wi-Fi) communication module, a second antenna adapted to receive and transmit data between the Wi-Fi communication module and a VoIP network, a signal monitoring circuit, and a switching circuit adapted to switch an existing communication from the cellular communication module to the Wi-Fi communication module or vice versa.

(51) **Int. Cl.**
H04W 36/00 (2009.01)
H04W 36/14 (2009.01)
(Continued)

(52) **U.S. Cl.**
CPC **H04W 36/14** (2013.01); **H04M 1/2535**
(2013.01); **H04M 1/725** (2013.01);
(Continued)

45 Claims, 2 Drawing Sheets



Related U.S. Application Data

continuation of application No. 13/899,303, filed on May 21, 2013, now Pat. No. 9,125,128, which is a continuation of application No. 13/168,585, filed on Jun. 24, 2011, now Pat. No. 8,467,789, which is a continuation of application No. 11/031,498, filed on Jan. 6, 2005, now Pat. No. 7,991,399.

- (60) Provisional application No. 60/534,466, filed on Jan. 6, 2004.

(51) Int. Cl.

H04W 48/18 (2009.01)

H04M 1/253 (2006.01)

H04M 1/725 (2006.01)

H04W 36/30 (2009.01)

H04W 48/16 (2009.01)

H04W 52/02 (2009.01)

H04W 24/00 (2009.01)

H04W 84/04 (2009.01)

H04W 88/06 (2009.01)

H04W 84/12 (2009.01)

(52) U.S. Cl.

CPC **H04M 1/72522** (2013.01); **H04W 36/30** (2013.01); **H04W 48/16** (2013.01); **H04W 48/18** (2013.01); **H04W 52/0235** (2013.01); **H04M 2250/06** (2013.01); **H04W 24/00** (2013.01); **H04W 84/042** (2013.01); **H04W 84/12** (2013.01); **H04W 88/06** (2013.01); **Y02D 70/122** (2018.01); **Y02D 70/142** (2018.01); **Y02D 70/146** (2018.01); **Y02D 70/23** (2018.01)

(58) Field of Classification Search

CPC . H04W 76/02; H04W 84/045; H04W 52/367; H04W 56/001; H04W 60/00; H04W 72/0406; H04W 28/18; H04W 36/0016; H04W 76/06; H04W 76/068; H04W 92/02; H04W 92/10
USPC 455/432, 442, 443, 444, 436
See application file for complete search history.

(56) References Cited**U.S. PATENT DOCUMENTS**

6,195,543 B1 2/2001 Granberg
6,473,413 B1 10/2002 Chiou et al.
6,515,983 B1 2/2003 Utas
6,553,022 B2 4/2003 Hartmaier
6,584,087 B1 6/2003 Czaja et al.
6,754,833 B1 6/2004 Black et al.
6,795,700 B2 9/2004 Karaoguz et al.
6,862,444 B2 3/2005 Karaoguz et al.
6,996,107 B2 2/2006 Janoska
7,127,232 B2 10/2006 O'Neil et al.
7,142,847 B2 11/2006 Umeda et al.
7,254,119 B2 8/2007 Jiang et al.
7,382,763 B2 6/2008 Ludwig et al.
7,398,088 B2 7/2008 Belkin et al.
7,483,984 B1 1/2009 Jonker et al.
7,512,796 B2 3/2009 Haverinen et al.
8,041,360 B2 10/2011 Ibe et al.
8,514,867 B2 8/2013 Ganesan
8,520,605 B2 8/2013 Ganesan
8,958,434 B2 2/2015 Ganesan
2001/0049790 A1 12/2001 Faccin et al.
2002/0073226 A1 6/2002 Sridhar
2002/0078174 A1 6/2002 Sim et al.
2002/0085516 A1 7/2002 Bridgelall
2002/0114305 A1 8/2002 Oyama et al.

2002/0147008 A1 10/2002 Kallio
2002/0150228 A1 10/2002 Umeda et al.
2002/0152305 A1 10/2002 Jackson et al.
2002/0183038 A1 12/2002 Comstock et al.
2003/0009580 A1 1/2003 Chen
2003/0012350 A1 1/2003 Wong et al.
2003/0053632 A1 3/2003 Bousis
2003/0058876 A1 3/2003 Connor
2003/0061206 A1 3/2003 Qian
2003/0083079 A1 5/2003 Clark et al.
2003/0086366 A1 5/2003 Branlund et al.
2003/0087629 A1 5/2003 Juitt et al.
2003/0112766 A1 6/2003 Reidel et al.
2003/0133421 A1 7/2003 Sundar
2003/0157899 A1 8/2003 Trossen et al.
2003/0163697 A1 8/2003 Pabla
2003/0177196 A1 9/2003 Bhasin et al.
2003/0185172 A1 10/2003 Rue
2003/0217007 A1 11/2003 Fukushima et al.
2003/0217091 A1 11/2003 Echigo et al.
2003/0224792 A1 12/2003 Verma et al.
2003/0232615 A1 12/2003 Kim et al.
2004/0005878 A1 1/2004 Olin et al.
2004/0030791 A1 2/2004 Dorenbosch et al.
2004/0052223 A1 3/2004 Karaoguz
2004/0053599 A1 3/2004 Karaoguz
2004/0076144 A1 4/2004 Ishidoshiro
2004/0083360 A1 4/2004 Walsh
2004/0085959 A1 5/2004 Ohkawa
2004/0087307 A1 5/2004 Ibe et al.
2004/0095916 A1 5/2004 Maki
2004/0105424 A1 6/2004 Skoczowski et al.
2004/0114559 A1 6/2004 Wang
2004/0127208 A1 7/2004 Nair et al.
2004/0132427 A1 7/2004 Lee et al.
2004/0137902 A1 7/2004 Chaskar et al.
2004/0141484 A1 7/2004 Rogalski et al.
2004/0153676 A1* 8/2004 Krantz G06F 1/3203
713/300
2004/0170173 A1 9/2004 Pan
2004/0174880 A1 9/2004 White et al.
2004/0176128 A1 9/2004 Grabelsky et al.
2004/0181811 A1 9/2004 Rakib
2004/0192294 A1 9/2004 Pan et al.
2004/0203666 A1 10/2004 Foster et al.
2004/0203788 A1 10/2004 Fors et al.
2004/0203802 A1 10/2004 McCormick et al.
2004/0204097 A1 10/2004 Scheinert et al.
2004/0205158 A1 10/2004 Hsu
2004/0218575 A1 11/2004 Ibe et al.
2004/0229618 A1 11/2004 Adatrao et al.
2004/0246990 A1 12/2004 Krishnamurthi et al.
2004/0267880 A1 12/2004 Patiejunas
2005/0025164 A1 2/2005 Kavanagh
2005/0044138 A1 2/2005 Albert et al.
2005/0059400 A1 3/2005 Jagadeesan et al.
2005/0090259 A1 4/2005 Jain et al.
2005/0135286 A1 6/2005 Nurminen
2005/0147049 A1 7/2005 Ganesan
2005/0149740 A1 7/2005 Kotzin et al.
2005/0239498 A1* 10/2005 Dorenbosch H04W 76/02
455/552.1
2005/0259958 A1 11/2005 Johansson
2006/0003796 A1 1/2006 Vireday
2006/0009219 A1 1/2006 Jaakkola
2006/0010272 A1 1/2006 Solomon
2006/0040711 A1 2/2006 Whistler
2006/0050663 A1 3/2006 Ganesan
2006/0050687 A1 3/2006 Ganesan
2006/0050721 A1 3/2006 Ganesan
2006/0080423 A1 4/2006 Brewer et al.
2006/0092901 A1 5/2006 Parantainen
2006/0098643 A1 5/2006 Pfeffer
2006/0105766 A1 5/2006 Azad
2006/0141984 A1 6/2006 Taglienti
2006/0146767 A1 7/2006 Moganti
2006/0234678 A1 10/2006 Juitt et al.
2006/0291455 A1 12/2006 Katz et al.
2007/0026862 A1 2/2007 Hicks, III

(56)

References Cited

U.S. PATENT DOCUMENTS

2007/0076665	A1	4/2007	Nair et al.
2007/0112948	A1	4/2007	Uhlik
2007/0124490	A1	5/2007	Kalavade et al.
2007/0249390	A1	10/2007	Purkayastha et al.
2009/0070489	A1	3/2009	Lu et al.
2009/0191864	A1	7/2009	Mousseau
2010/0074228	A1	3/2010	Hicks et al.
2011/0010282	A1	1/2011	Olin et al.
2011/0044310	A1	2/2011	Uhlik
2014/0204902	A1	7/2014	Maltsev

FOREIGN PATENT DOCUMENTS

EP	0936777	A1	8/1999
EP	1471665	A1	10/2004
GB	2287858	A	9/1995
JP	200226994	A	1/2002
JP	2004320473	A	11/2004

WO	03056719	A1	7/2003
WO	2003061177	A2	7/2003
WO	2003061177	A3	7/2003
WO	2004013998	A2	2/2004
WO	2004057903	A1	7/2004

OTHER PUBLICATIONS

3GPP Organization Project, "3rd Generation Partnership Project; Technical Specification Group Services and System Aspects Service Aspects; Service Principles (Release 8)", Mar. 2006, pp. 1-45.

3GPP Organization Project, 3rd Generation Partnership Project; Technical Specification Group Services and System Aspects Service Aspects; Service Requirements for the All-IP Network (AIPN); V8.0.0, Stage 1, (Release 8), pp. 1-24.

Unlicensed Mobile Access (UMA); Protocols (Stage 3), R1.0.4, May 2, 2005, pp. 1-162.

Office Action from Chinese Patent Application No. 201510039302.4, dated Feb. 8, 2018.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3

1

TELEPHONE WITH AUTOMATIC SWITCHING BETWEEN CELLULAR AND VOIP NETWORKS

CROSS-REFERENCES TO RELATED APPLICATIONS

This Patent Application is a continuation application of co-pending U.S. patent application Ser. No. 14/806,482, filed on Jul. 22, 2015, and entitled "TELEPHONE WITH AUTOMATIC SWITCHING BETWEEN CELLULAR AND VOIP NETWORKS," which is a continuation application of U.S. patent application Ser. No. 13/899,303, filed on May 21, 2013, and entitled "TELEPHONE WITH AUTOMATIC SWITCHING BETWEEN CELLULAR AND VOIP NETWORKS," which is a continuation application of U.S. patent application Ser. No. 13/168,585, filed on Jun. 24, 2011, and entitled "TELEPHONE WITH AUTOMATIC SWITCHING BETWEEN CELLULAR AND VOIP NETWORKS," which is a continuation application of U.S. Pat. No. 7,991,399, filed on Jan. 6, 2005, and entitled "TELEPHONE WITH AUTOMATIC SWITCHING BETWEEN CELLULAR AND VOIP NETWORKS," which claims benefit under 35 USC 119(e) of the filing date of U.S. provisional application No. 60/534,466, filed on Jan. 6, 2004, entitled "Radiotelephone With Automatic Switching Between Cellular And Wi Fi Networks Using Wi-Fi Signal Strength Values." The content of all of the above is incorporated herein by reference in its entirety.

BACKGROUND OF THE INVENTION

A small portion of the radio frequency (RF) spectrum is assigned to each communications carrier. The assigned spectrum, therefore, must be used efficiently in order to allow the maximum number of frequency users to have access to this spectrum. Multiple access modulation techniques have been developed to provide optimum utilizing of the RF spectrum. Examples of such modulation techniques include time division multiple access (TDMA), frequency division multiple access (FDMA), and code division multiple access (CDMA).

There is a wide variance in the performance of wireless networks. A conventional wireless cellular network, covers a relatively large geographical area but provides a relatively low bandwidth. Such wireless networks use regulated portions of the radio spectrum and are shared by many users. The infrastructure costs of wireless networks are relatively high due to the size and complexity of the cellular network equipment.

Other wireless networks, such as CDMA2000-EV-DO/DV networks, offer higher bandwidth and enhanced data services, such as web browsing. However, these networks also pack many users into a relatively small portion of the regulated spectrum. Other types of radio networks are adapted to improve spectral efficiency with increased and smaller coverage areas. For example, an IEEE 802.11x (or Wi-Fi) network may transmit at speeds up to 11 Mbps using a Direct Sequence Spread Spectrum (DSSS) mode or at speeds up to 54 Mbps using an Orthogonal Frequency Division Multiplexing (OFDM) mode.

An access point conforming to an IEEE 802.11x (e.g., IEEE 802.11b) network may cover an area of a few hundred feet in diameter. Each such access point is connected to a larger network (e.g., Internet). In order to cover larger geographical areas, a relatively large number of IEEE 802.11x network access points and a relatively large wire-

2

line back haul networks are required. In part, due to the back haul costs, the resulting IEEE 802.11x based network may thus be more expensive to set up and operate than a similarly based wireless network. In other words, many tradeoffs often exist between and among the coverage areas, the maximum bit-rates, and the costs associated with different types of wireless networks.

Demand for high bandwidth and quality of service (QoS) associated with mobile communication devices with full roaming capability is on the rise. One known communication device includes a cellular communication module adapted to enable communication using wireless cellular networks as well as a Wi-Fi communication module adapted to enable communication using a Voice over IP (VoIP) protocol. In such devices, to change the communication mode from cellular to VoIP or vice versa, the user has to manually change the device's setting by, e.g., pressing one or more keys.

In yet other communication devices known to be under development, to switch the communication mode from, for example, cellular to VoIP, the cellular network first detects the position of the mobile communication device to determine whether the mobile communication device is in a Wi-Fi area. If it so detects, the cellular network sends a switching signal to the mobile communication device to enable the communication to continue the communication using the VoIP protocol. However, obtaining and maintaining accurate position of many mobile communication devices concurrently poses a challenging task. Consequently, in such systems, the switching of the call from cellular to VoIP or vice versa may result in the loss of the call.

BRIEF SUMMARY OF THE INVENTION

In accordance with the present invention, a mobile communication device is configured so as to automatically switch a communication that is already in progress using a wireless cellular network (hereinafter alternatively referred to as cellular network) to a wireless Voice over IP (VoIP) network or vice versa. The mobile communication devices is adapted to include, in part, a cellular communication module, a first antenna adapted to receive and transmit data between the mobile communication module and a cellular network, a Wireless Fidelity (Wi-Fi) communication module, a second antenna adapted to receive and transmit data between the Wi-Fi communication module and a VoIP network, a signal monitoring circuit, and a switching circuit adapted to switch an existing in-progress communication between the cellular communication module and the Wi-Fi communication module. The second antenna and associated circuitry are maintained in on-states continuously to monitor and detect Wi-Fi signals.

If the mobile communication device is in an in-progress (i.e., pre-established) communication via its cellular communication module and through a cellular network, and the Wi-Fi antenna system detects a Wi-Fi signal having a first predefined level (strength), a timer disposed in the mobile communication device is activated to establish a first time window of a first predefined size. If the Wi-Fi signal level detected during the first time window remains equal to or greater than the first predefined level, at the expiration of the first time window, the switching circuit causes the in-progress communication to be switched from its cellular communication module to its Wi-Fi communication module and through a VoIP network without losing the in-progress communication.

In some embodiments, upon activating the timer, the Wi-Fi communication module is caused to change state from a sleep mode, during which the Wi-Fi communication module consumes relatively small amount of power, to a stand-by mode during which the Wi-Fi communication module consumes an intermediate amount of power. Subsequently, before the communication is switched to the Wi-Fi communication module, the Wi-Fi communication module is caused to be placed in a full active mode, during which the Wi-Fi communication module consumes an amount of power larger than the intermediate amount of power.

If the mobile communication device is in a pre-established communication via its Wi-Fi communication module and through a VoIP network, and the Wi-Fi antenna system detects that the level of the received Wi-Fi signal is below a second predefined value, the timer is activated to establish a second time window of a second predefined size. If the Wi-Fi signal level detected during the second time window is equal to or greater than a third predefined value, the pre-established communication via the Wi-Fi communication module is maintained without any change. If the Wi-Fi signal level detected during the second time window is less than the third predefined value, the timer is reset and reactivated to establish a third time window of a third size. If the Wi-Fi signal level detected during the third time window is less than the third predefined value, at the expiration of the third time window, the switching circuit causes the in-progress communication to be switched from its Wi-Fi communication module to its cellular communication module and through a cellular network without losing the in-progress communication.

In some embodiments, upon activating the timer to establish the second time window, the cellular communication module is caused to change state from a sleep mode, during which the cellular communication module consumes relatively small amount of power, to a stand-by mode during which the cellular communication module consumes an intermediate amount of power. Subsequently, before the communication is switched to the Wi-Fi communication module, the cellular communication module is caused to be placed in a full active mode, during which the cellular communication module consumes an amount of power larger than the intermediate amount of power.

In some embodiments, the Wi-Fi communication module is adapted to communicate with an access point of a Wi-Fi local area network using an 802.11x wireless protocol, and the cellular communication module is adapted to communicate with a base station of a wireless cellular network using any one of GSM, CDMA, or CDMA2000 protocols.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a simplified high-level block diagram of a mobile communication device, in accordance with one embodiment of the present invention.

FIG. 2 shows Wi-Fi signal threshold level and timing window used to determine whether to switch a communication from the cellular communication module to the Wi-Fi communication module of the communication device of FIG. 1, in accordance with one embodiment.

FIG. 3 shows Wi-Fi signal threshold levels and timing windows used to determine whether to switch a communication from the Wi-Fi communication module to the cellular communication module of the communication device of FIG. 1, in accordance with one embodiment.

DETAILED DESCRIPTION OF THE INVENTION

In accordance with the present invention, a mobile communication device is configured so as to automatically switch an existing communication from a wireless cellular network (hereinafter alternatively referred to as cellular network) to a wireless Voice over IP (VoIP) network, or to switch an existing communication from a VoIP network to a cellular network. It is understood that the Wireless Fidelity (Wi-Fi) signals, as defined, for example, in IEEE 802.11x standards or other equivalent standards may be used to communicate with a Voice over IP (VoIP) network. The mobile communication device is adapted to include, in part, a cellular communication module, a first antenna adapted to receive and transmit data between the mobile communication module and a cellular network, a Wi-Fi communication module, a second antenna adapted to receive and transmit data between the Wi-Fi communication module and a VoIP network, a signal monitoring circuit, and a switching circuit adapted to switch an existing in-progress communication between the cellular communication module and the Wi-Fi communication module. The second antenna and associated circuitry are maintained in on-states continuously to monitor and detect Wi-Fi signals.

It is understood the wireless cellular network includes, in part, a multitude of base stations. Each such base station is adapted to communicate with the mobile communication device when the mobile communication device is located within the coverage area of the base station via RF signals carried over cellular network. It is also understood that each such coverage area is defined by an area centered at the base station and having a radius of, e.g., several miles. It is further understood that a Wi-Fi network may include, in part, a multitude of access points. Each such access point is adapted to communicate with the mobile communication device, when the mobile communication device is located within the coverage area of the access point, via VoIP packets. It is also understood that the mobile communication device may also include blocks adapted for computation and thus be a communication/computation device.

If the mobile communication device is in an in-progress (i.e., pre-established) communication via its cellular communication module and through a cellular network, and the Wi-Fi antenna system detects a Wi-Fi signal having a first predefined level (strength), a timer disposed in the mobile communication device is activated to establish a first time window of a first predefined size. If the Wi-Fi signal level detected during the first time window remains equal to or greater than the first predefined level, at the expiration of the first time window, the switching circuit causes the in-progress communication to be switched from its cellular communication module to its Wi-Fi communication module and through a VoIP network without losing the in-progress communication.

In some embodiments, upon activating the timer, the Wi-Fi communication module is caused to change state from a sleep mode, during which the Wi-Fi communication module consumes relatively small amount of power, to a stand-by mode during which the Wi-Fi communication module consumes an intermediate amount of power. Subsequently, before the communication is switched to the Wi-Fi communication module, the Wi-Fi communication module is caused to be placed in a full active mode, during which the Wi-Fi communication module consumes an amount of power larger than the intermediate amount of power.

5

If the mobile communication device is in a pre-established communication via its Wi-Fi communication module and through a VoIP network, and the Wi-Fi antenna system detects that the level of the received Wi-Fi signal is below a second predefined value, the timer is activated to establish a second time window of a second predefined size. If the Wi-Fi signal level detected during the second time window is equal to or greater than a third predefined value, the pre-established communication via the Wi-Fi communication module is maintained without any change. If the Wi-Fi signal level detected during the second time window is less than the third predefined value, the timer is reset and reactivated to establish a third time window of a third size. If the Wi-Fi signal level detected during the third time window is less than the third predefined value, at the expiration of the third time window, the switching circuit causes the in-progress communication to be switched from its Wi-Fi communication module to its cellular communication module and through a cellular network without losing the in-progress communication.

In some embodiments, upon activating the timer to establish the second time window, the cellular communication module is caused to change state from a sleep mode, during which the cellular communication module consumes relatively small amount of power, to a stand-by mode during which the cellular communication module consumes an intermediate amount of power. Subsequently, before the communication is switched to the Wi-Fi communication module, the cellular communication module is caused to be placed in a full active mode, during which the cellular communication module consumes an amount of power larger than the intermediate amount of power.

FIG. 1 is a simplified high-level block diagram of a mobile communication device 100, in accordance with one embodiment of the present invention. Mobile communication device 100, which is adapted to automatically switch communication between cellular and VoIP networks, is shown as including, in part, a cellular communication module (hereinafter alternatively referred to as cellular module) 3 coupled to a cellular antenna 1, a Wi-Fi communication module (hereinafter alternatively referred to as Wi-Fi module) 4 coupled to a Wi-Fi antenna 2, an audio/video amplifier 5, a network switch unit 6, a timer unit 7, a Wi-Fi signal level monitor 8, a microphone 20, a speaker 21, and a display monitor 22. Mobile communication device 100 is adapted to establish and maintain communication via either a cellular module 3, through a wireless network (not shown), and/or via Wi-Fi module 4, through a VoIP network (not shown). Cellular module 3 further includes a transceiver 30 adapted to transmit signal to and receive signal from a cellular network. Wi-Fi module 4 further includes a transceiver 32 adapted to transmit signal to and receive signal from a VoIP network. Depending on the level of detected Wi-Fi signal emitted from a Wi-Fi access point, a call initially established via cellular module 3 may be switched to be handled by Wi-Fi module 4, or a call initially established via Wi-Fi module 4 may be switched to be handled by cellular module 3.

Assume that mobile communication device 100 is in communications with a cellular network and is entering the coverage area of a Wi-Fi access point adapted to transmit and receive Wi-Fi signals. As is known, a Wi-Fi access point may be used to gain access to a VoIP network. Wi-Fi antenna 2 together with Wi-Fi module 4 and Wi-Fi signal monitor 8 continuously monitor for to detect Wi-Fi signals. If a detected Wi-Fi signal level is greater than a predefined threshold value V_{th1} , Wi-Fi signal level monitor 8 activates timer 7 via signal line 10 and sends a wake-up signal to

6

network switch unit 6 via signal line 12, thereby to change the state of network switch unit 6 from a sleep mode, during which network switch unit consumes relatively small power, to a stand-by mode, during which network switch unit consumes an intermediate amount of power. Network switch unit 6, in turn, supplies wake-up switching signals to cellular module 3 via signal line 15 and to Wi-Fi module 4 via signal line 13. This causes phone cellular module 3 and Wi-Fi module 4 to activate their respective switching modules. The detected Wi-Fi signal level may be determined, for example, by taking multiple samples of the incoming Wi-Fi signal(s) and computing a signal level from these samples. In one embodiment, an average of the amplitudes/phases of the sampled signals may be used to detect the Wi-Fi signal level.

If the detected Wi-Fi signal level is greater than V_{th1} , timer unit 7 is activated to establish a first time window of a first predefined size T_1 , as shown in FIG. 2. During time window T_1 , Wi-Fi antenna 2 together with Wi-Fi module 4 and Wi-Fi signal monitor 8 continue to monitor and detect the level of received Wi-Fi signal. If the Wi-Fi signal level detected during time window T_1 remains equal to or greater than V_{th1} , at the expiration of time window T_1 , timer unit 7 sends a cellular tear-down signal and a Wi-Fi link-up signal to the network switch unit 6 via signal line 11. In response, network switch unit 6 sends the tear-down signal to cellular module 3 via signal line 15, and sends the link-up signal to Wi-Fi module 4 via signal line 13. Network switch unit 6 also instructs audio/video amplifier 5, via signal line 14, to generate an audio/video alert signal. The generated audio alert signal is subsequently reproduced by speaker 21 via signal line 18, and the generated video alert signal is subsequently reproduced by display monitor 22 via signal line 23. The audio/video alert tones are adapted to notify the mobile communication device user of a network switch from cellular to Wi-Fi.

Cellular module 3 is adapted to terminate connection to the cellular network and to switch off connection to audio/video amplifier 5 after receiving the tear-down signal. Wi-Fi module 4 is adapted to activate connection to VoIP network and to switch on connection to audio/video amplifier 5—for passing voice signal to audio amplifier 5 and video signal to display monitor 22—after receiving a Wi-Fi link-up signal. The previously established communication link is thus continued uninterrupted via the VoIP network and through loudspeaker 21, microphone 20 and display monitor 23.

Assume that mobile communication device 100 is in communications with a VoIP network and may be leaving the coverage area of the Wi-Fi access point. Wi-Fi antenna 2 together with Wi-Fi module 4 and Wi-Fi signal monitor 8 continuously monitor for to detect Wi-Fi signals. If the detected Wi-Fi signal level falls below a second predefined threshold value V_{th2} , Wi-Fi signal level monitor 8 activates timer 7 and sends a wake-up signal to network switch unit 6 to change the state of network switch unit 6 from the sleep mode to stand-by mode. Network switch unit 6, in turn, supplies wake-up switching signals to cellular module 3 and to Wi-Fi module 4 to enable these modules to activate their respective switching procedures.

Once activated, timer unit 7 establishes a second time window of a second predefined size T_2 , as shown in FIG. 3. During time window T_2 , Wi-Fi antenna 2 together with Wi-Fi module 4 and Wi-Fi signal monitor 8 continue to monitor and detect the level of received Wi-Fi signal. If the Wi-Fi signal level detected during time window T_2 is equal to or greater than a third predefined threshold value V_{th3} , where V_{th3} is smaller than V_{th2} , the previously established VoIP communication continues without switching.

If the Wi-Fi signal level detected during time window T_2 is smaller than V_{th3} , at the expiration of time window T_2 , timer unit 7 is reset and activated to establishes a third time window of a third predefined size T_3 , where T_3 is smaller than T_2 . If the Wi-Fi signal level detected during time window T_3 is equal to or greater than V_{th3} , the previously established VoIP communication continues without switching.

If the Wi-Fi signal level detected during time window T_3 is less than V_{th3} , at the expiration of time window T_3 , timer unit 7 sends a Wi-Fi tear-down signal and a cellular link-up signal to network switch unit 6. In response, network switch unit 6 sends the tear-down signal to Wi-Fi module 3, and sends the link-up signal to cellular module 4. Network switch unit 6 also instructs audio/video amplifier 5 to generate an audio/video alert signals. The generated audio alter signals is subsequently reproduced by speaker 21, and the generated video alert signal is subsequently reproduced by display monitor 22. The audio/video alert tones are adapted to notify the mobile communication device user of a network switch from Wi-Fi to cellular

Wi-Fi module 4 is adapted to terminate connection to the VoIP network and to switch off connection to audio/video amplifier 5 after receiving the tear-down signal. Cellular module 4 is adapted to activate connection to the cellular network and to switch on connection to audio/video amplifier 5 after receiving a Wi-Fi link-up signal. The previously established communication link is thus continued uninterrupted and through loudspeaker 21, microphone 20 and display monitor 23.

In accordance with some embodiments, if the mobile communication device detects both an Wi-Fi signal from an access point and a cellular signal from a mobile cellular base station before establishing a communication link, the mobile communication device first attempts to establish communication with the Wi-Fi access point using Wi-Fi module 4.

The above embodiments of the present invention are illustrative and not limiting. Various alternatives and equivalents are possible. It is understood that the functionality associated with any blocks described above may be centralized or distributed, whether locally or remotely. It is also understood that one or more blocks of each mobile communication device may be performed by hardware, firmware or software, or some combinations thereof. The invention is not limited by the type of cellular network, e.g., CDMA, GSM, otherwise used to carry communication. Nor is the invention limited by the VoIP network. The invention is not limited by the Wi-Fi signals, such as those defined by IEEE 802.11x, where x may be a, b, g, or WiMAX used to carry VoIP communication. The invention is not limited by the type of integrated circuit(s) in which the present invention may be disposed. Nor is the invention limited to any specific type of process technology, e.g., CMOS, Bipolar, or BiCMOS that may be used to manufacture the present invention. Other additions, subtractions or modifications are obvious in view of the present invention and are intended to fall within the scope of the appended claims.

What is claimed is:

1. A device comprising:

a switching system to switch operation between a first communication module and a second communication module, wherein during an established communication if a context changes, the established communication is switched to a second communication over a second network, wherein switching is based on detecting a second context being preferred over the context within a set of networks, wherein upon activation of a timer,

the switching system causes the second communication module to change state from a sleep mode to an active mode, wherein the timer is activated to establish a time window of a predefined size, wherein if a Wi-Fi signal monitor detects that a Wi-Fi signal level is below a second predefined threshold value V_{th2} , the timer is activated to establish a second time window of a second predefined size T_2 , wherein a third predefined threshold value V_{th3} is smaller than V_{th2} .

2. The device of claim 1, wherein a tear-down signal causes the communication module to go into a sleep mode.

3. The device of claim 1 wherein if during time window T_2 , the Wi-Fi signal monitor detects that the Wi-Fi signal level is smaller than V_{th3} , upon expiration of time window T_2 , the timer unit is activated to establish a third time window of a third predefined size T_3 , where T_3 is smaller than T_2 , wherein if during time window T_3 the Wi-Fi signal monitor detects that the Wi-Fi signal level is smaller than V_{th3} , the switching circuit sends a tear-down signal to the Wi-Fi communication module and a link-up signal to the cellular communication module, wherein said tear-down signal causes the Wi-Fi communication module to discontinue handling a previously established communication over the Wi-Fi network and wherein said link-up signal causes the cellular communication module to handle the previously established communication over the Wi-Fi network via a cellular network.

4. The device of claim 3 wherein at the expiration of the predefined time period T_2 , the network switching circuit causes the cellular communication module to change state from a sleep mode to an active mode.

5. The device of claim 1, wherein the communications comprise a telephone call.

6. The device of claim 1, wherein the communications comprise a transmission of content.

7. The device of claim 6, wherein the content comprises at least one of fixed and mobile.

8. The device of claim 1, wherein the communications comprise a data exchange.

9. The device of claim 1 wherein the previously established communication comprises: a cellular communication, a VoIP communication/session, a voice communication/session, a video communication/session, a multimedia communication/session, a data communication/session, a SIP or IMS based communication and/or a Wi-Fi communication.

10. The device of claim 9 wherein the previously established communication is proprietary or standard.

11. The device of claim 1 wherein the established communication comprises a cellular communication or a Wi-Fi communication, and the second communication comprises a cellular communication or a Wi-Fi communication.

12. A method comprising:

determining a first context;

activating a timer to establish a first time window of a first predefined size T_1 based on the detected first context; determining a second context during the first time window;

automatically switching a communication in progress via a wireless network to a communication via a Wi-Fi network based on the second detected context;

detecting a third context;

establishing a second time window of a second predefined size T_2 if the third detected context falls below a second predefined threshold value V_{th2} ;

detecting a fourth context during the second time window; and

continuing a Wi-Fi communication without change if the fourth detected context is equal to or greater than a third predefined threshold value V_{th3} , wherein V_{th3} is smaller than V_{th2} .

13. The method of claim 12, wherein the communication comprises a telephone call.

14. The method of claim 12, wherein the communication comprises a transmission of content.

15. The method of claim 14, wherein the content comprises at least one of fixed and mobile.

16. The method of claim 12 wherein the determining and switching are performed, in part, by a mobile communication device.

17. The method of claim 12 wherein the determining and switching are performed, in part, by a server.

18. The method of claim 17 wherein the server comprises a network-based device.

19. The method of claim 17 wherein the server comprises a switch and/or router.

20. The method of claim 17 wherein the server comprises a network-based switch and/or router.

21. The method of claim 17 wherein the server comprises an access point or a base station.

22. The method of claim 17 wherein the server comprises software, firmware and/or hardware.

23. A mobile communication device comprising:

a first communication module adapted to communicate with a first wireless network;

a second communication module adapted to communicate with an access point associated with a second network; and

a switching system to switch operation between the first communication module and the second communication module, wherein if a context changes, the second communication module is activated and a second communication type is initiated, wherein if the context does not change, the second communication type is continued without switching, wherein switching is based on detecting a second context being preferred over the context within a set of known networks or from a newly discovered network, wherein upon activation of a timer, the switching system causes the second communication module to change state from a sleep mode to an active mode, wherein the timer is activated to establish a time window of a predefined size, wherein if a Wi-Fi signal monitor detects that a Wi-Fi signal level is below a second predefined threshold value V_{th2} , the timer is activated to establish a second time window of a second predefined size T_2 , wherein a third predefined threshold value V_{th3} is smaller than V_{th2} .

24. The mobile communication device of claim 23, wherein the first communication module comprises a first Wi-Fi communication module, and the first wireless network comprises a first Wi-Fi network access point.

25. The mobile communication device of claim 24, wherein the second communication module comprises a second Wi-Fi communication module, and the second wireless network comprises a second Wi-Fi network access point.

26. The mobile communication device of claim 23, wherein the communication comprises a telephone call.

27. The mobile communication device of claim 23, wherein the communication comprises a transmission of content.

28. The mobile communication device of claim 27, wherein the content comprises at least one of fixed and mobile.

29. The mobile communication device of claim 23, wherein the communication comprises a data exchange.

30. The mobile communication device of claim 23 wherein the context comprises a signal level.

31. A method comprising:

determining, with a server, a first signal level;

activating, with the server, a timer to establish a first time window of a first predefined size T_1 if the detected first signal level is greater than a first predefined threshold value;

determining, with the server, a second signal level during the first time window;

if the second detected signal level falls below the first predefined threshold value, then searching for alternative Wi-Fi signals having signal level above the first predefined threshold value, with the server;

if an alternative signal level is above the first predefined threshold value, then switching a Wi-Fi communication in progress to a source of the alternative Wi-Fi signal, with the server; and

if no alternative signal level is above the first predefined threshold value, then switching a Wi-Fi communication in progress to the wireless network, with the server, wherein if a signal monitor detects that the alternative signal level is below a second predefined threshold value, a timer is activated to establish a second time window of a second predefined size, wherein a third predefined threshold value is smaller than a second predefined threshold value.

32. The method of claim 31, further comprising:

continuing a Wi-Fi communication without change if the second detected signal is equal to or greater than the first predefined threshold value.

33. The method of claim 31, wherein the communication comprises a telephone call.

34. The method of claim 31, wherein the communication comprises a transmission of content.

35. The method of claim 34, wherein the content comprises at least one of fixed and mobile.

36. The method of claim 31, wherein the communication comprises a data exchange.

37. A device comprising:

a switching system to switch operation between a first communication module and a second communication module, wherein during an established communication if a monitor detects that a context changes, the established communication is switched to a second communication over a network, wherein switching is based on detecting a second context being preferred over the context within a set of known networks, wherein upon activation of a timer, the switching system causes the second communication module to change state from a sleep mode to an active mode, wherein the timer is activated to establish a time window of a predefined size, wherein if the monitor detects that a signal level is below a second predefined threshold value V_{th2} , the timer is activated to establish a second time window of a second predefined size T_2 , wherein a third predefined threshold value V_{th3} is smaller than V_{th2} .

38. The device of claim 37 wherein the network is operated by a different network provider.

39. The device of claim 37 wherein the network includes a plurality of access points, and the established communication is switched between the plurality of access points.

40. The device of claim 37 wherein the device comprises a terminal, a mobile device, a sensor, an access point, and/or a controller device.

11

41. The device of claim 37 wherein the first communication comprises a first WiFi communication and the second communication comprises a second WiFi communication.

42. The device of claim 37 wherein the first communication comprises a first cellular communication and the second communication comprises a second cellular communication.

43. The device of claim 37 wherein the first communication comprises a cellular communication and the second communication comprises a WiFi communication, or the first communication comprises the WiFi communication and the second communication comprises the cellular communication.

44. The device of claim 37 wherein the first communication and the second communication comprise at least one of: a cellular communication, a VoIP communication/session, a voice communication/session, a video communication/session, a multimedia communication/session, a data communication/session, a SIP or IMS based communication and/or a WiFi communication.

45. A method comprising:
monitoring a context of a first communication link;

12

when a network is detected as available with a second communication link with a context preferable to the first communication link, notifying an interface server and establishing the second communication link between the interface server and an end destination device without disrupting the first communication link; and

re-directing the second communication link from the interface server to a mobile communication device, thereby establishing the second communication link between the communication device and a second network, wherein upon activation of a timer, a switching system causes a second communication module to change state from a sleep mode to an active mode, wherein the timer is activated to establish a time window of a predefined size, wherein if a Wi-Fi signal monitor detects that a Wi-Fi signal level is below a second predefined threshold value V_{th2} , the timer is activated to establish a second time window of a second predefined size T_2 , wherein a third predefined threshold value V_{th3} is smaller than V_{th2} .

* * * * *