

 Back to results  (LifeVac);

Choking intervention device and method of use thereof

Abstract

A choking intervention device for clearing an object obstructing a breathing passage of a choking victim includes a bellows assembly and a removable facemask configured to enclose a person's mouth and nose. The bellows assembly includes a bellows having a base with an opening thereon. The opening is configured to provide access to an interior volume of the bellows assembly. The bellows assembly further includes a handle on the bellows at a side opposite the base. The facemask is coupled to the base of the bellows and is configured to enclose the choking victim's mouth and nose.

Classifications

 **A61B17/24** Surgical instruments, devices or methods for use in the oral cavity, larynx, bronchial passages or nose; Tongue scrapers

View 8 more classifications

Landscapes

Health & Medical Sciences

Heart & Thoracic Surgery

Show more

WO2015167709A1

WIPO (PCT)

[Download PDF](#)

[Find Prior Art](#)

[Similar](#)

Other languages: [French](#)

Inventor: [Lih ARTHUR](#)

Worldwide applications

2014 [US](#) 2015 [WO](#)

Application PCT/US2015/022731 events ⓘ

2015-03-26 Application filed by Life Vac Llc

2015-11-05 Publication of WO2015167709A1

Info: [Patent citations \(17\)](#), [Cited by \(18\)](#), [Legal events](#), [Similar documents](#), [Priority and Related Applications](#)

External links: [Espacenet](#), [Global Dossier](#), [PatentScope](#), [Discuss](#)

Claims

Hide Dependent ^

CLAIMS What is claimed is:

1. A choking intervention device for clearing an object obstructing a breathing passage of a choking victim, the device comprising:

a bellows assembly comprising:

a bellows having a base with an opening configured to provide an access to an interior volume of the bellows assembly; and

a handle provided on the bellows at a side opposite the base; and

a facemask coupled to the base of the bellows and configured to enclose the choking victim's mouth and nose.
2. The device of claim 1, wherein the facemask further comprises a seal configured to provide a seal between the facemask and a face of the victim when the facemask is placed over the choking victim's mouth and nose.
3. The device of claim 1, wherein the facemask further comprises a connector configured to: slidably insert into the opening on the base of the bellows; and

provide fluid communication between the interior volume of the bellows and the facemask.
4. The device of claim 1, wherein the bellows assembly and the facemask are a single piece of polymer configured via injection molding.
5. The device of claim 3, wherein the bellows assembly and the facemask are two separate pieces and the facemask is removable from the bellows assembly between the opening and the connector.
6. The device of claim 5, wherein the bellows assembly is configured to couple to different size face masks.
7. The device of claim 1, wherein the facemask is configured to be of universal size.
8. The device of claim 1, further comprising at least one relief valve configured to allow air to escape from inside the bellows assembly when the bellows is compressed and prevent air from entering the bellows assembly when the bellows is expanded, when the facemask is positioned over the victim's mouth and nose.
9. The device of claim 8, wherein the at least one relief valve is disposed on at least one of (i) the bellows assembly, and (ii) the facemask.
10. The device of claim 8, wherein the bellows is configured to be compressed when the handle is pushed towards the victim's mouth and nose.
11. The device of claim 10, wherein the bellows is configured to expand and create a pressure differential between a throat and an esophagus of the victim when the handle is pulled away from the victim's mouth and nose.
12. The device of claim 1, wherein the device is portable and not mounted.

13. The device of claim 1, wherein the device is configured to be used by the choking victim.

14. A method of clearing an object obstructing a breathing passage of a choking victim using a device comprising a bellows assembly and a facemask coupled to the bellows, the method comprising:

enclosing the choking victim's mouth and nose with the facemask;

pushing a handle on the bellows assembly towards the choking victim's mouth and nose and compressing a bellows of the bellows assembly;

providing a seal between the facemask and a face of the victim;

providing fluid communication between an interior volume of the bellows and the facemask; allowing air to escape from inside the bellows assembly when the bellows is being compressed;

pulling the handle away from the victim's mouth and nose;

expanding the bellows and creating a pressure differential between a throat and an esophagus of the victim by pulling the handle away from the victim's mouth and nose, and preventing outside air from entering the bellows assembly when the bellows is expanding.

15. The method of claim 14, wherein the method is performed by the victim.

16. A bellows assembly comprising:

a bellows having a base with an opening configured to provide an access to an interior volume of the bellows assembly and dimensioned to be attached to a facemask via a facemask connector;

a handle provided on the bellows at a side opposite the base; and

a relief valve configured, when the facemask is positioned over a person's mouth and nose, to allow air to escape from inside the bellows assembly when the bellows is compressed and prevent air from entering the bellows assembly when the bellows expands.

Description

CHOKING INTERVENTION DEVICE AND METHOD OF USE THEREOF

RELATED APPLICATION

[0001] The present application claims priority of provisional patent application No. 61/925,460 filed January 9, 2014, the contents of which are incorporated herein in their entirety.

FIELD OF THE INVENTION

[0002] The present disclosure generally relates to first aid devices, and more specifically to a device for removal of an object obstructing an airway.

BACKGROUND OF THE DISCLOSURE

[0003] Choking (i.e., the unintentional obstruction of the respiratory tract by inhalation of ingestion of a foreign object) is one of the leading causes of accidental death in children. In one estimate, approximately 4,000 individuals in the United States die every year due to choking, making it one of the top five causes of death in the United States. In the year 2000 alone, 160 children 14 years or younger died from choking. For every choking death, there are more than 100 visits to emergency departments for choking incidents. According to the Centers for Disease Control and Prevention (CDC), an estimated 17,537 children 14 years and younger were treated for choking in an emergency department, in 2001 alone.

[0004] Choking may or may not fully block the respiratory tract. In cases where the respiratory tract is fully blocked, or blocked sufficiently to impair breathing, every minute a child is choking can diminish the chances of full recovery. For example, if the obstruction is removed and the child is able to breathe normally within 4 minutes, brain damage is unlikely. On the other hand, when the brain is without oxygen for 4 to 6 minutes, brain damage is possible. Brain damage becomes probable when the brain is deprived of oxygen for 6 to 10 minutes. If the oxygen deprivation exceeds 10 minutes, brain death is likely.

[0005] In view of the foregoing, first aid should be administered as soon as possible to avoid brain damage and death. However, many people who witness a choking situation may not be familiar or proficient with first aid treatments. For example, the Heimlich maneuver, in which a second individual performs abdominal thrusts to the victim's torso below from behind the body and beneath the rib cage to create pressure in the lungs to possibly expel the obstructing object, is not known by many. For over 100 million individuals in the United States, the Heimlich maneuver may not even be an option due to various factors, such as: disability, pregnancy, obesity, or simply being alone.

[0006] The victim may also not be able to be moved into a proper position for the Heimlich maneuver due to weight or the environment they are in. The Heimlich may also fail because the victim may lack sufficient air in the lungs to develop enough pressure to expel the object. For example, the victim may have ingested the obstructing object immediately upon completing an exhaling step in the breathing cycle or have already exhaled the air by coughing.

[0007] For such situations, a source of suction to expel the object from the victim's throat would be a better solution. Instead, critical time is typically wasted for emergency medical personnel to arrive to the scene, which is often too late to prevent permanent damage or death.

[0008] Although choking intervention devices are known in the art, they are generally complex in that they include many parts. Such complexity not only increases the overall cost but also makes prior art devices less reliable in that more components could fail. Indeed, prior art devices typically are piston driven and have rubber seals for the piston, where the seals degrade over time, thereby limiting the effectiveness of the tool. Thus, after years of storage, such prior art devices may fail to provide proper suction because of the degradation of the seals. Further, many prior art choking intervention devices require mounting and are therefore not truly portable, thereby limiting their range of use. Keeping them in a glove compartment of a vehicle or in a picnic basket may not be a convenient option.

[0009] Accordingly, it would be beneficial to have a simple and effective way to clear the airways in an emergency situation. It would be also beneficial to have a device and method that is cost effective, reliable, and does not degrade over time. It would be further beneficial to have a device and method that does not rely for help on a second party in a choking emergency situation. SUMMARY OF THE DISCLOSURE

[0010] In one embodiment a choking intervention device includes a bellows assembly and a removable facemask that is configured to enclose a person's mouth and nose. The bellows assembly further includes a bellows, which has a base with an opening formed thereon and a handle provided on the bellows at a side opposite the base.

[0011] In one embodiment, the facemask further includes a seal configured to provide a seal between the facemask and a face when the facemask is placed over the person's mouth and nose.

[0012] In one embodiment, the facemask further comprises a connector configured to slidably insert into the opening on the base of the bellows. The connector is further configured to provide fluid communication between the interior volume of the bellows and the facemask.

[0013] In one embodiment, the bellows assembly and the facemask are a single piece of polymer constructed via injection molding.

[0014] In one embodiment the bellows assembly and the facemask are two separate pieces. The facemask is removable from the bellows assembly between the opening and the connector.

[0015] In one embodiment, the bellows assembly is configured to couple to different size face masks. For example, the different face masks may be dimensioned in discrete sizes (e.g., small, medium, large, extra-large) to better accommodate the mouth and nose of the choking victim. In other another embodiment, the facemask is configured to be of universal size.

[0016] In one embodiment, the choking intervention device further includes at least one relief valve configured to allow air to escape from inside the bellows assembly when the bellows is being compressed and prevent air from entering the bellows assembly when the bellows is being expanded, when the facemask is positioned over the victim's mouth and nose. For example, the relief valve may be disposed on at least one of (i) the bellows assembly and (ii) the facemask. [0017] The bellows is configured to be compressed when the handle is pushed towards the victim's mouth and nose, and to expand to create a pressure differential between a throat and an esophagus of the victim when the handle is pulled away from the victim's mouth and nose.

[0018] The choking intervention device is portable and does not need to be mounted. It can be used by the choking victim themselves during a choking emergency.

[0019] Also discussed is a method of clearing an object obstructing a breathing passage of a choking victim using a device comprising a bellows assembly and a facemask coupled the bellows. The choking victim's mouth and nose with the facemask is enclosed. A handle on the bellows assembly is pushed towards the choking victim's mouth and nose. The bellows of the bellows assembly is thereby compressed.

[0020] A seal is provided between the facemask and the face (i.e., mouth and nose) of the victim. Fluid communication is provided between an interior volume of the bellows and the facemask. Air is allowed to escape from inside the bellows assembly when the bellows is being compressed.

[0021] The handle is then pulled away from the victim's mouth and nose. Outside air (e.g., outside the chamber created between the choking intervention device and the victim) is prevented from entering the bellows assembly when the bellows is being expanded by the unidirectional release valve.

[0022] The bellows is expanded and a pressure differential created between the throat and the esophagus of the victim by pulling the handle away from the victim's mouth and nose. The obstructing object is thereby dislodged from the breathing passage of the choking victim. The steps can be repeated several times until the breathing passage is cleared.

BRIEF DESCRIPTION OF THE DRAWINGS

[0023] These and other features, aspects, and advantages of the present invention will become better understood with regard to the following description, appended claims, and accompanying drawings, wherein: [0024] FIG. 1 illustrates a side view of an exemplary embodiment of a choking intervention device.

[0025] FIG. 2 illustrates a plan view of the underside of the bellows assembly of the exemplary embodiment of FIG. 1;

[0026] FIG. 3 illustrates an exploded view of the exemplary choking intervention device of FIG. 1; and

[0027] FIG. 4 illustrates another exemplary embodiment of a choking intervention device. DETAILED DESCRIPTION

[0028] In the following detailed description, numerous specific details are set forth by way of examples in order to provide a thorough understanding of the relevant teachings. However, it should be apparent to those skilled in the art that the present teachings may be practiced without such details. In other instances, well known methods, procedures, components, and/or circuitry have been described at a relatively high-level, without detail, in order to avoid unnecessarily obscuring aspects of the present teachings.

[0029] The various examples disclosed herein generally relate to first aid devices and more particularly to devices and methods for removal of an object obstructing an airway. The choking intervention devices described herein are used for clearing an object obstructing a breathing passage of a choking victim. The victim's mouth and nose is enclosed with the choking intervention device to provide a seal between the device and the victim. When a handle of the choking intervention device is pulled away from the victim's mouth and nose, the object is dislodged from the breathing passage of the choking victim.

[0030] FIG. 1 illustrates a side view of an exemplary choking intervention device. The choking intervention device of FIG. 1 comprises a bellows assembly 102 that is configured to sealably couple to a facemask 110. The bellows assembly 102 may have a plunger shape that includes a bellows 104 and a handle 106 disposed on a top portion of the bellows assembly 102 at a side opposite the base 114. [0031] The bellows assembly 102 may include a relief valve 108 configured to allow air to escape from the bellows assembly 102 when the bellows 104 is being compressed. Thus, the relief valve 108 prevents substantial pressure to be built inside the bellows assembly 102 when the bellows 104 is compressed (while the bellows assembly is sealably coupled to the facemask and the facemask is positioned over the victim's mouth and nose). The relief valve 108 is unidirectional in that it allows air to escape during compression but prevents air from escaping during suction.

[0032] In one embodiment the relief valve 108 is positioned between the handle 106 and the bellows 104, as illustrated in FIG. 1. In various implementations, the relief valve 108 is positioned on the distal end of the handle 106 or on a base 114 of the bellows 104. The handle 108 portion of the bellows assembly 102 may be ergonomically shaped in that its distal end is wider than its proximal end with respect to the bellows 104. In one embodiment, the bellows assembly 102 is a single piece made via injection mold.

[0033] In one embodiment, the facemask 110 includes a seal 112, such as a gasket or other appropriate device capable of forming a seal between a person's face and the facemask 110 when the facemask 110 is placed over the person's mouth and nose. The facemask 110 has a connector 118 (shown in FIG. 3) at an end opposite to the seal 112, wherein the connector 118 is configured to allow the facemask 110 to removably connect to the bellows assembly 102. In various implementations, the facemask 110 may be of plastic or of the same material as the bellows assembly 102. In one embodiment, both the bellows assembly 102 and the facemask 110 are a single piece made via injection mold.

[0034] When the facemask 1 10 joins the bellows assembly 102, connector 118 creates a tight seal around the opening 116 of the base of the bellows 1 14. To that end, the connector 1 18 of the facemask 1 10 is configured and dimensioned to insert into the opening 116 (shown in FIG. 2) formed through the base 1 14 of the bellows 104. When the connector 118 is inserted and properly seated in the (e.g., circular) opening 1 16, a substantially airtight seal is formed between the connector 118 and the base 114. In one embodiment, a (e.g., rubber gasket) on the perimeter of the opening 1 16 further facilitates the seal between the connector 1 18 and the base 1 14.

[0035] It will be understood that to effectively prevent obstructions during choking, it would be advantageous for a choking intervention device to be affordable, sanitary, and/or ubiquitous (e.g., readily available). In this regard, in one embodiment, the facemask 110 portion of the present disclosure is a disposable and/or replaceable item. As an additional benefit, the choking intervention device of this exemplary embodiment avoids spreading infections between users.

[0036] While the facemask portion 110 may be configured as a "one size fits all" (e.g., universal size), in one embodiment, the facemask 110 may be dimensioned in discrete sizes (e.g., small, medium, large, extra-large) to better accommodate the mouth and nose of the choking victim (e.g., configured for different age groups). For example, a choking intervention device kit may include the bellows assembly 102 and multiple face masks 110, with at least one face mask 110 dimensioned for an adult and at least one for use on a child and/or infant choking victim. The different sized facemasks 110 are configured to provide a better seal to be formed and maintained between the victim's face and the seal 112 of the facemask 110.

[0037] In one embodiment, the bellows assembly 102 is configured to be in a collapsed form when at rest (e.g., not in use). During a choking emergency, a user of the choking intervention device may place the facemask 110, attached to the collapsed bellows assembly 102, over the choking victim's mouth and nose, thereby creating a sealed chamber between the bellows assembly 102, facemask 1 10, and the victim. A force is exerted on the bellows assembly in an expansion direction by pulling the handle 106 away from the choking victim. The suction generated by the expansion of the bellows 104 is operative to dislodge a foreign object obstructing the choking victim's respiratory tract such as to allow sufficient airflow to the lungs. A pressure differential created within the throat and esophagus causes the lodged object to be dislodged and sucked through the facemask 1 12.

[0038] Alternatively, the bellows assembly 102 may be configured to be in an extended state when at rest. In this configuration a user of the choking intervention device may place the facemask 1 10, attached to the bellows assembly 102, over the choking victim's mouth and nose, and exert force on the bellows assembly in a compression direction by pushing the handle 106 towards the choking victim. The relief valve 108 prevents air from being pushed into the respiratory tract of the choking victim. Once the bellows 104 is (e.g., substantially) compressed, the user provides force on the bellows assembly 102 in an expansion direction by pulling the handle 106 away from the choking victim. The suction generated by the expansion of the bellows 104 is intended to dislodge a foreign object obstructing the choking victim's respiratory tract sufficiently to allow sufficient airflow to the lungs.

[0039] During the choking intervention, several iterations of the above-described procedures may be applied to dislodge the foreign object. In both above-described configurations of the bellows assembly 102 the relief valve 108 prevents air from being pushed into the respiratory tract of the choking victim during compression of the bellows 104. Thus, the relief valve prevents further lodging the foreign object in the respiratory tract during the intervention.

[0040] The duration of the suction is short, typically less than one second. The suction power of the bellows assembly 102 is approximately three times stronger than the choke pressure of the obstruction. However, the volume of the air removed is minimal. Thus, damage to the lungs of the victim is not of immediate concern.

[0041] As shown in the embodiments of FIGS. 1 and 3, the relief valve 108 may be positioned on a surface of the bellows assembly. While the relief valve 108 is shown on a top surface of the bellows 404, the illustration is a non-limiting example. Thus the relief valve 108 may be positioned at any suitable location on the bellows assembly 102, such as the base 114 of the bellows assembly 102, top of the handle 106, etc.

[0042] FIG. 4 illustrates another exemplary embodiment of a choking intervention device, where a relief valve 410 is positioned on a facemask 408 (in addition to or instead of the relief valve on the bellows assembly discussed in the context of FIG. 1). In the example of FIG. 4, the choking intervention device includes a bellows assembly 402 and a facemask 408. The bellows assembly 402 has a bellows 404 and a handle 406 disposed on a top surface of the bellows 404.

[0043] In one embodiment, the facemask 408 includes a seal 412, such as a gasket or other appropriate device capable of forming a seal between a person's face and the facemask 408 when the facemask 408 is placed over the person's mouth and nose. Additionally, the facemask 408 has the relief valve 410 positioned thereon to allow air to escape from the facemask 408 when the bellows 404 is compressed. A connector 414 fixedly coupled to the facemask 408 is configured to allow the facemask 408 to removably connect to the bellows assembly 402 in a similar manner as described in the context of the discussion of FIG. 1 above. When the connector 414 is inserted and slidably seated in the opening of the base of the bellows, a substantially airtight seal is formed between the connector 414 and the base 114 of the bellows, thereby sealingly unifying the bellows assembly 402 with the facemask 408.

[0044] While the relief valve 410 is shown at a particular position on the facemask 408, the illustration is provided as a non-limiting example only. Thus, the relief valve 410 may be positioned at any suitable location on the facemask 408. In one example, the relief valve is positioned on the connector 414.

[0045] The embodiments discussed herein provide a choking intervention device that is light and portable. Unlike prior art devices, the embodiments described herein do not require any mounting of the device. Since there are no mounting requirements to a support structure (e.g., a table), the device can be stored at a convenient location in the home, at the office, in the glove compartment of a vehicle, included in a picnic basket, etc. Further, since the choking intervention device is not piston driven, it does not require seals, which may degrade over time. In this regard, the device may be stored for decades and still perform reliably in a choking emergency situation. The overall simplicity of the design not only keeps production costs low but makes the device reliable and affordable.

[0046] While the foregoing has described what are considered to be the best mode and/or other examples, it is understood that various modifications may be made therein and that the subject matter disclosed herein may be implemented in various forms and examples, and that the teachings may be applied in numerous applications, only some of which have been described herein. It is intended by the following claims to claim any and all applications, modifications and variations that fall within the true scope of the present teachings.

[0047] Unless otherwise stated, all measurements, values, ratings, positions, magnitudes, sizes, and other specifications that are set forth in this specification, including in the claims that follow, are approximate, not exact. They are intended to have a reasonable range that is consistent with the functions to which they relate and with what is customary in the art to which they pertain. [0048] The scope of protection is limited solely by the claims that now follow. That scope is intended and should be interpreted to be as broad as is consistent with the ordinary meaning of the language that is used in the claims when interpreted in light of this specification and the prosecution history that follows and to encompass all structural and functional equivalents. Notwithstanding, none of the claims are intended to embrace subject matter that fails to satisfy the requirement of Sections 101, 102, or 103 of the Patent Act, nor should they be interpreted in such a way. Any unintended embracement of such subject matter is hereby disclaimed.

[0049] Except as stated immediately above, nothing that has been stated or illustrated is intended or should be interpreted to cause a dedication of any component, step, feature, object, benefit, advantage, or equivalent to the public, regardless of whether it is or is not recited in the claims.

[0050] It will be understood that the terms and expressions used herein have the ordinary meaning as is accorded to such terms and expressions with respect to their corresponding respective areas of inquiry and study except where specific meanings have otherwise been set forth herein. Relational terms such as first and second and the like may be used solely to distinguish one entity or action from another without necessarily requiring or implying any actual such relationship or order

entities or actions. The terms "comprises," "comprising," or any other variation thereof, are intended to cover a non-exclusive inclusion, such that a process, method, article, or apparatus that comprises a list of elements does not include only those elements but may include other elements not expressly listed or inherent to such process, method, article, or apparatus. An element preceded by "a" or "an" does not, without further constraints, preclude the existence of additional identical elements in the process, method, article, or apparatus that comprises the element.

[0051] The Abstract of the Disclosure is provided to allow the reader to quickly ascertain the nature of the technical disclosure. It is submitted with the understanding that it will not be used to interpret or limit the scope or meaning of the claims. In addition, in the foregoing Detailed Description, it can be seen that various features are grouped together in various embodiments for the purpose of streamlining the disclosure. This method of disclosure is not to be interpreted as reflecting an intention that the claimed embodiments require more features than are expressly recited in each claim. Rather, as the following claims reflect, inventive subject matter lies in less than all features of a single disclosed embodiment. Thus the following claims are hereby incorporated into the Detailed Description, with each claim standing on its own as a separately claimed subject matter

Patent Citations (17)

Publication number	Priority date	Publication date	Assignee	Title
US3316903A *	1963-09-26	1967-05-02	Albert M Richards	Inhalator
US3939830A *	1975-03-10	1976-02-24	Da Costa Harry	Manually operable dechoking and resuscitating device
US4934360A *	1989-01-05	1990-06-19	Heilbron Delphine R	Disposable manual resuscitator
US5313938A *	1986-06-18	1994-05-24	Allen Samuel Garfield	Valved resuscitation pump having secretion removal means
US20030028158A1 *	1997-07-07	2003-02-06	Bahman Litkouhi	Apparatus and method for removing a lodged mass from an animal airway
WO2007073211A1 *	2005-12-19	2007-06-28	Gary Noel Stevenson	Improvements relating to resuscitators
Family To Family Citations				
DE230740C				
FR668573A	1927-12-20	1929-11-04		Apparatus for determining the flow of blood and activating skin respiration
FR746185A	1931-12-05	1933-05-23		Improvements to pneumatic suction cups
CH399657A	1963-02-14	1965-09-30	Mayr Max	Manually operated pump for artificial breathing
US4768237A *	1987-06-08	1988-09-06	Emanuel Torti	Toilet plunger
US4971053A	1988-07-19	1990-11-20	Edward Tarrats	Suction mask to relieve choking
US5609149A	1995-10-04	1997-03-11	Takach; Stephen J.	Anti-choke device
US5782837A	1997-04-23	1998-07-21	York; Richard	Esophagus clearing device
US7351245B2	2004-09-21	2008-04-01	Bernice Joy Rozinsky	Apparatus and method for dislodging object from throat
USD613468S1	2009-08-25	2010-04-06	Waxman Consumer Products Group Inc.	Sink plunger
WO2012091949A1	2010-12-30	2012-07-05	Hooper Medical Devices, Llc	Vacuum assist device to remove object from trachea

* Cited by examiner, † Cited by third party

Cited By (18)

Publication number	Priority date	Publication date	Assignee	Title
DE102017115283A1	2017-07-07	2019-01-10	Domma & Marx GbR (vertretungsberechtigter Gesellschafter: Peter Domma, 66287 Quierschied)	Device for removing particles from the throat and respiratory tract
DE202022102066U1	2022-04-19	2022-04-27	Nabil Chehade	Device for removing objects blocking the respiratory airway
Family To Family Citations				
US11324877B2	2009-12-17	2022-05-10	Dechoker LLC	Airway assist device
US11701462B2	2016-07-15	2023-07-18	Dechoker LLC	Airway assist device
KR102251873B1 *	2019-02-22	2021-05-13	배정환	Esophageal foreign substances removal device
USD1057936S1	2020-06-08	2025-01-14	Dechoker LLC	Airway assist device

TW202146065A *	2020-06-08	2021-12-16	美商迪秋可公司	Airway assist device
CN112932633A *	2021-03-10	2021-06-11	武汉大学中南医院	Device and method for sucking foreign body in trachea
US11478575B1 *	2021-08-03	2022-10-25	Dcstar Inc	Removal device for removing obstruction in respiratory tract and connector
US11633530B2	2021-08-03	2023-04-25	Dcstar Inc	Suction device for sucking obstruction in respiratory tract and use method therefor
USD1021084S1 *	2021-08-30	2024-04-02	Dcstar Inc	Bellows device
US11446460B1	2021-10-08	2022-09-20	Dechoker LLC	Pressure regulated airway assist device
US12017035B2	2022-08-30	2024-06-25	Dechoker LLC	Keyed interlocking airway assist device
US20240206898A1 *	2022-12-21	2024-06-27	John Daniel Bergeron	Choking Intervention Device
US12239343B1 *	2023-11-15	2025-03-04	Dcstar Inc	Respiratory obstruction removal device
USD1050428S1 *	2024-06-27	2024-11-05	Dcstar Inc	Bellows device
USD1051352S1 *	2024-07-29	2024-11-12	Wei Liu	Anti suffocation device
USD1051353S1 *	2024-07-31	2024-11-12	Yudi Liu	Choking rescue device

* Cited by examiner, † Cited by third party, ‡ Family to family citation

Similar Documents

Publication	Publication Date	Title
US10052115B2	2018-08-21	Choking intervention device and method of use thereof
US5313938A	1994-05-24	Valved resuscitation pump having secretion removal means
KR101479200B1	2015-01-05	Nose Mask for Preventing Inhalation of Virus, Fine Dust and Bacteria
WO2009047763A1	2009-04-16	Respiration bag
US11419622B2	2022-08-23	Automated device for choking
US11806049B1	2023-11-07	Automated airway obstruction clearance/drowning rescue device and method of making and using the same
US3946736A	1976-03-30	Respirator assist device
CN205007007U	2016-02-03	Prevent device of choking
CN2652347Y	2004-11-03	Tracheal cannula isolation cover for fulminating respiratory system infectious disease
CN208852094U	2019-05-14	Negative pressure emergency device for airway obstruction
KR101245521B1	2013-03-20	Shield for Artificial Respiration
JP3236189U	2022-02-03	Mask assembly
US20230211098A1	2023-07-06	Infectious aerosol capture mask with suction tube adapter for active and passive use
CN203763610U	2014-08-13	Contamination emergency treatment device for nursing
CN202538100U	2012-11-21	Artificial respirator with sputum aspiration function
US20120172847A1	2012-07-05	Vacuum assist device to remove object from trachea
US12239343B1	2025-03-04	Respiratory obstruction removal device
CN215606163U	2022-01-25	Suction device for respiratory tract blockage
WO2012091949A1	2012-07-05	Vacuum assist device to remove object from trachea
CN208610961U	2019-03-19	A kind of airway obstruction unblocker
CN106617392B	2018-06-22	Haze mask
CN219307514U	2023-07-07	Disposable sputum aspirator
CN214129704U	2021-09-07	A child suction device

CN205549169U	2016-09-07	Artificial respiration blow gun
CN204798545U	2015-11-25	Breathe artificial respirator for internal medicine

Priority And Related Applications

Applications Claiming Priority (3)

Application	Filing date	Title
US201461925460P	2014-01-09	
US14/264,590	2014-04-29	
US14/264,590	2014-04-29	Choking intervention device and method of use thereof

Legal Events

Date	Code	Title	Description
2015-12-16	121	Ep: the epo has been informed by wipo that ep was designated in this application	Ref document number: 15786385 Country of ref document: EP Kind code of ref document: A1
2016-10-31	NENP	Non-entry into the national phase	Ref country code: DE
2017-05-03	32PN	Ep: public notification in the ep bulletin as address of the addressee cannot be established	Free format text: NOTING OF LOSS OF RIGHTS PURSUANT TO RULE 112(1) EPC (EPO FORM 1205A DATED 28/02/2017)
2017-10-04	122	Ep: pct application non-entry in european phase	Ref document number: 15786385 Country of ref document: EP Kind code of ref document: A1

Concepts

[machine-extracted](#)

[Download](#) [Filter table](#)

Name		Image	Sections	Count	Query match
method	title,claims,description	20	0.000		
respiratory gaseous exchange	claims,abstract,description	10	0.000		
esophagus	claims,description	5	0.000		
communication	claims,description	4	0.000		
fluid	claims,description	4	0.000		
injection moulding	claims,description	2	0.000		
polymer	claims,description	2	0.000		
Show all concepts from the description section					

Data provided by IFI CLAIMS Patent Services