US 20040165563A1

(19) United States

(12) Patent Application Publication

(10) Pub. No.: US 2004/0165563 A1

(43) Pub. Date: Aug. 26, 2004

Hsu et al.

(54) WIRELESS LOCAL ACCESS NETWORK SYSTEM DETECTION AND SELECTION

(76) Inventors: **Raymond T. Hsu**, San Diego, CA (US); **Ragulan Sinnarajah**, Markham (CA)

Correspondence Address:
Patent Department
QUALCOMM Incorporated
5775 Morehouse Drive
San Diego, CA 92121-1714 (US)

(21) Appl. No.: **10/374,810**

(22) Filed: **Feb. 24, 2003**

Publication Classification

(51) **Int. Cl.**[7] **H04Q 7/24**

(52) **U.S. Cl.** **370/338**

(57) **ABSTRACT**

Method and apparatus for detection and selection of Wireless Local Area Network (WLAN) service. A remote station, which may be in conjunction with a wireless computing device, may scan for a cellular paging indicator and a WLAN beacon using one or two tuners. When WLAN coverage is available, a packet data session may be transferred thereto.



* * *

Samsung v. Four Batons
IPR2025-00494
Exhibit 1006



FIG. 1



FIG. 2A



FIG. 2B



FIG. 4



FIG. 3A



FIG. 3B


250
252
USER SELECTS MAP DISPLAY OF WLAN LOCATIONS
254
WLAN IDENTIFIED IN RANGE
256
AUTOMATED SCAN?
NO
YES
258
MS SCANS FOR WLAN
260
USER INITIATES WLAN SCAN
262
ACCESS WLAN?
264
WLAN REG. REQUEST

FIG. 5B


200
202
N
E
S
W
City
KEYPAD
204

FIG. 5A


350
START
354
WAKE FOR PAGING INDICATOR
356
ACTIVE OR PASSIVE SCAN?
PASSIVE
ACTIVE
358
REQUEST WLAN BEACON
360
WLAN SCAN
END

FIG. 7


WLAN BEACON
AP
320
PAGE INDICATOR
BTS
322
TUNER A
304
TUNER B
306
ESSID LIST
302
300

FIG. 6


500
FTP SERVER
514
HA
516
ACCESS ROUTER
510
INTERNET
502
WLAN
AP
512
PDSN
504
cdma2000
WLAN
BS
506
MS
508

FIG. 8


CELLULAR NETWORK 606
MS 602
LAPTOP 600
AP 604
DATA SESSION
WLAN ADVERTISEMENT
ENABLE WLAN SCAN
DISCONNECT CELL
DISCONNECT DATA SESSION
ACQUIRE AP WLAN SIGNAL
AUTHENTICATION
DATA SESSION

FIG. 9


MS
702
AP
704
CELL NETWORK
706
DATA SESSION
SCAN FOR WLAN
INSTRUCTION MESSAGE
DETECT WLAN
NOTIFY CELL OF RESULT
INSTRUCTION TO
SWITCH TO WLAN
AUTHENTICATE

FIG. 10A


MS
702
AP
704
CELL NETWORK
706
DATA SESSION
SCAN FOR WLAN
INSTRUCTION MESSAGE
DETECT WLAN
AUTHENTICATE
TIME OUT AND
TERMINATE
DATA SESSION

FIG. 10B


CELL NETWORK
706
AP
704
MS
702
DATA SESSION
SCAN FOR WLAN
INSTRUCTION MESSAGE
NO DETECTION
SEARCH RESULT
CONTINUE DATA
SESSION

FIG. 10C

WIRELESS LOCAL ACCESS NETWORK SYSTEM DETECTION AND SELECTION

REFERENCE TO CO-PENDING APPLICATIONS FOR PATENT

[0001] The present application for patent is related to the following co-pending U.S. patent applications:

[0002] "WIRELESS LOCAL ACCESS NETWORK SYSTEM DETECTION AND SELECTION" by Raymond T. Hsu et al., having Attorney Docket No. 030040, filed concurrently herewith, assigned to the assignee hereof, and expressly incorporated by reference herein; and

[0003] "WIRELESS LOCAL ACCESS NETWORK SYSTEM DETECTION AND SELECTION" having Attorney Docket No. 030043, filed concurrently herewith, assigned to the assignee hereof, and expressly incorporated by reference herein.

BACKGROUND

[0004] 1. Field

[0005] The present invention relates generally to communication systems, and more specifically to detection of a Wireless Local Access Network (WLAN) by a mobile station in a cellular communication system.

[0006] 2. Background

[0007] Wireless Local Access Networks (WLANs) provide wireless access to a communication network within a local geographical area, such as a building or in a cybercafe. WLANs are currently considered by many cellular carriers to alleviate loading of a cellular system, so as to increase capacity. Additionally, users desire access to local WLANs to enhance reception and data rates of communications through a wireless device. A problem exists in detecting and selecting WLAN systems. The purpose of system detection is to detect the availability of a wireless access medium (e.g., cdma2000, WLAN, etc.). The purpose of system selection is to select an access medium for transporting application contents. System selection may be based on the availability of access media, preference policy, application status, user intervention, etc., or a combination thereof.

[0008] Typically, a cellular system transmits a paging indicator periodically to page a mobile station when there is a pending communication. Similarly, a WLAN may be advertised by a beacon transmitted by the WLAN. Both the paging indicator and the beacon require the mobile station to scan for the transmitted signal. As the mobile station often has little information as to the location and accessibility of a WLAN, the mobile station may scan for the WLAN periodically expending considerable power. There is a need therefore for an efficient, accurate method of system detection and selection.

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] **FIG. 1** is a mobile station adapted for system detection and selection.

[0010] **FIG. 2A** is a communication configuration including cellular system capability and WLAN access.

[0011] **FIG. 2B** illustrate signaling messages for advertising WLAN.

[0012] **FIG. 3A** is a timing diagram of signal flow in a system as in **FIG. 2A**.

[0013] **FIG. 3B** is a timing diagram of signal flow in a system as in **FIG. 2A**.

[0014] **FIG. 4** is a timing diagram of signal flow in a system as in **FIG. 2A**.

[0015] **FIG. 5A** is a mobile station having a display format associated with WLAN detection.

[0016] **FIG. 5B** is a flow diagram of a method for system detection and selection.

[0017] **FIG. 6** is a block diagram of a mobile station with multiple tuners in communication with a WLAN and a cellular system.

[0018] **FIG. 7** is a flow diagram of a method for system detection.

[0019] **FIG. 8** is a communication system supporting wireless cellular communications, wireless local area network communications, and Internet communications.

[0020] **FIG. 9** is a timing diagram illustrating WLAN detection and selection.

[0021] **FIG. 10A** is a timing diagram illustrating WLAN detection and selection.

[0022] **FIG. 10B** is a timing diagram illustrating WLAN detection and selection.

[0023] **FIG. 10C** is a timing diagram illustrating WLAN detection and selection.

DETAILED DESCRIPTION

[0024] The word "exemplary" is used herein to mean "serving as an example, instance, or illustration." Any embodiment described herein as "exemplary" is not necessarily to be construed as preferred or advantageous over other embodiments.

[0025] An HDR subscriber station, referred to herein as an access terminal (AT), may be mobile or stationary, and may communicate with one or more HDR base stations, referred to herein as modem pool transceivers (MPTs). An access terminal transmits and receives data packets through one or more modem pool transceivers to an HDR base station controller, referred to herein as a modem pool controller (MPC). Modem pool transceivers and modem pool controllers are parts of a network called an access network. An access network transports data packets between multiple access terminals. The access network may be further connected to additional networks outside the access network, such as a corporate intranet or the Internet, and may transport data packets between each access terminal and such outside networks. An access terminal that has established an active traffic channel connection with one or more modem pool transceivers is called an active access terminal, and is said to be in a traffic state. An access terminal that is in the process of establishing an active traffic channel connection with one or more modem pool transceivers is said to be in a connection setup state. An access terminal may be any data device that communicates through a wireless channel or

through a wired channel, for example using fiber optic or coaxial cables. An access terminal may further be any of a number of types of devices including but not limited to PC card, compact flash, external or internal modem, or wireless or wireline phone. The communication link through which the access terminal sends signals to the modem pool transceiver is called a reverse link. The communication link through which a modem pool transceiver sends signals to an access terminal is called a forward link.

[**0026**] **FIG. 1** illustrates the components and interfaces for the system detection and selection according to one embodiment. Within system **50**, a user **52** represents a user of a wireless mobile unit, wherein the user **52** is a human capable of manually selecting an access medium or implementing an automatic selection process. An application **54** is a computer-readable program or protocol stack (e.g., Transmission Control Protocol (TCP)/Internet Protocol (IP) stack) requiring an access medium for transport. The application **54** communicates with the user **52** via interface C. The application **54** also communicates with a preference database **56** via interface B, and with a selector **58** via interface E.

[**0027**] The preference database **56** is a memory device storing a system selection criterion. The system selection criteria may be configured manually by the user **52** or manipulated automatically by the application **54**. In one embodiment, the system selection criterion considers the availability of wireless access and selects WLAN when available. In one example, if the system **50** is currently communicating via the cellular network, such as a cdma2000 network, the system **50** is instructed to continue such communication but to continue to try to detect the availability of WLAN. The application **54** may configure the preference database **56** automatically. The user **52** may manually configure the preference database **56** and enable/disable the application **54**.

[**0028**] An Access Medium Detector (AMD) **60** detects the availability of a wireless access medium and reports the results to the selector **58**. The selector **58** is responsible for enabling or disabling one or more Access Medium Detectors **60** and selecting an access medium based on the detection results, system selection criteria, application status, and/or user request. The Selector **60** may inform the system selection result to the user **52** and/or application **54**. The selector **60** communicates with application **54** via interface E, with preference database **56** via interface F, and with AMDs **60** via interface G. The selector **58** further communicates with user **52** via interface D.

[**0029**] Interface A: The user **52** may manually load new system selection criteria or modify existing system selection criteria in the preference database **56**. System selection criteria are rules that the selector **58** will use for decision making. For example, if an application is active (i.e., sending/receiving data) and the WLAN access medium is available, then the system should select the WLAN access medium to transport data traffic. The user may input system selection criteria via a user-graphic interface (e.g., window-based programs).

[**0030**] Interface B: The application **54** may automatically load new system selection criteria or modify existing system selection criteria in the preference database **56**. For example, an application **54** having a preference to use a given access medium X, and the preference may be loaded in the preference database **56** automatically when the application **54** is downloaded or installed.

[**0031**] Interface C: The user **52** may enable or disable the application **54**. The user **52** may configure the application **54** setting for system selection. For example, the user **52** may configure the application **54** to prohibit automatic interaction with the preference database **56**, such as when the user **52** decides to manually control the application **54**-level preference via Interface A.

[**0032**] Interface D: The selector **58** may prompt the user to select an access medium. In another scenario, without such prompt the user **52** may request a specific access medium, wherein such request overrides other system selection criteria.

[**0033**] Interface E: The application **54** may provide status information to facilitate the selector **58** in system selection. For example, whether the application **54** is enabled or disabled influences the Selector **58** decision to enable or disable the Access Medium Detector **60**. The Selector **58** may provide the system selection result to the application **54**, based on the indication from the access medium detector(s) and system selection criteria stored in the preference database. For example, if the Selector **58** selects an access medium with higher bandwidth, the application **54** may switch to a codec with better quality. In another example, the Selector **58** relays the system detection results to the application **54** from an Access Medium Detector **60**, so that the application **54** may display the results to the user **52**.

[**0034**] Interface F: The Selector **58** obtains the system selection criteria from the preference database **56**. If there is a change in the system selection criteria (e.g., modified by the user **52**), the Selector **58** must fetch the new criteria from the preference database **56**. The Selector identifies a change in the criteria by a variety of methods, such as: (1) The user **52** (or Application **54**) provides information to the Selector **58** via the D (or E) Interface indicating a preference database **56** update, or (2) The Selector **58** periodically checks the preference database **56** for updates.

[**0035**] Interface G: The Selector **58** may enable or disable one or more Access Medium Detectors **60** based on user input, application status, and/or system selection criteria from the preference database **56**. The Access Medium Detector **60** may indicate the detection result to the Selector **58**.

[**0036**] Provisioning the MS With WLAN Information

[**0037**] The following discussion details provisioning of the WLAN information in the Mobile Station (MS) and methods implemented at the MS to minimize unnecessary WLAN scanning based on WLAN advertisement from the cellular network via signaling messages. A network supporting cdma2000 protocols is provided as an example in the following discussion. In the context of the present description, provisioning refers to the communication of WLAN parameters and configuration information to the MS necessary for establishment of communication with the WLAN.

[**0038**] A conventional provisioning method manually configures the MS with the necessary information (e.g., 802.11a/b frequencies, list of service identifiers, etc.) for the MS to detect WLAN coverage provided by a service pro-

vider. Extended Service Set Identifier (ESSID) may be used to identify all Access Points (AP) in a WLAN operator network. Different operators will use different ESSIDs. Thus, the list of ESSIDs may correspond to a list of WLAN operators accessible by the MS.

[**0039**] An alternative to manual provisioning is to provision the MS with the WLAN information via an Over-The-Air Provisioning (OTAP) type protocol. The detail of OTAP is described in the IS-683 standards that can be extended to support the provisioning of WLAN parameters. Another alternative is to automatically provision the MS with the WLAN information advertised via 1× signaling messages (discussed hereinbelow). The latter alternative is more dynamic than OTAP.

[**0040**] Once the MS has the necessary WLAN information, the MS determines when to scan for WLAN coverage. Generally, the WLAN will transmit a periodic beacon, which is a signal transmitted to advertise the WLAN. When the MS is able to receive the beacon, the MS is able to access the WLAN. The user **52** may enable or disable WLAN scan, however, the process may not be user friendly, because of the manual operations required by the user. An automated operation may be preferred, which is transparent to the user. According to one embodiment, a scanning method transparent to the user **52** provides for the MS to scan periodically. Periodic scanning is expensive when the MS is not in WLAN coverage area as scanning drains battery power.

[**0041**] If a cellular system, such as cdma2000, also provides WLAN service or has roaming agreement(s) with other WLAN operators, several options may be implemented for the cellular network to advertise WLAN information via cellular signaling messages in order to facilitate the MS to scan for WLAN coverage efficiently. Alternate embodiments may implement other cellular systems.

[**0042**] WLAN Advertisement via Signaling Messages.

[**0043**] In a first embodiment, a Base Station Controller (BSC) and Base Transceiver System (BTS) are configured with the knowledge of WLAN coverage in a cell sector. When the cellular service provider also provides WLAN services, the WLAN information is available to the cellular system. When there is WLAN coverage in the cell sector, the BTS periodically broadcasts WLAN provisioning information (e.g., 802.11a/b frequencies, ESSID, preferred roaming list, etc.) as overhead messages via common channels. The MS receives the WLAN provisioning information and uses the information to scan for WLAN. The WLAN provisioning information may be included within existing overhead messages. Alternately, the WLAN provisioning information may be provided in a signaling message defined specifically for WLAN provisioning.

[**0044**] **FIG. 2A** illustrates sectors within a cell of a cellular communication network. The cell includes sector A **102**, sector B **104**, and sector C **106**. Within the cell are multiple WLANS, including WLAN **#1120** and WLAN **#2130**. The WLAN **#1120** is identified by an ESSID(1). The WLAN **#2130** is identified by an ESSID(2). As illustrated, the WLAN **#2130** is contained within sector B **104**, while WLAN **#1120** includes a portion within sector B **104** and a portion within sector A **102**.

[**0045**] The preferred roaming list is a list of ESSIDs, each corresponding to a WLAN provider having a roaming agreement with the cellular system. The broadcast signaling messages may be triggered by cellular system provisioning, i.e., the cellular system broadcasts the message all the time whether or not there are MSs with WLAN capability. The cellular system continually transmits the WLAN provisioning information so as to advertise the WLAN. Alternately, the WLAN provisioning information may be transmitted via signaling messages, wherein the signaling messages are triggered on receipt of at least one registration message, and wherein the registration message indicates an MS with WLAN capability. Such WLAN capability indication may be a 1-bit flag in a registration message. Note that one benefit of registration triggered signaling is that the BTS may avoid broadcasting unnecessary WLAN provisioning information.

[**0046**] Upon receipt of the WLAN request from a MS, the BS may transmit the WLAN advertisement in a variety of ways. The BS may transmit the WLAN advertisement on a common channel, wherein multiple users are able to access the information. The BS may transmit the information directly to the MS using a signaling message. The BS may transmit only specific information, such as location identification for the WLAN.

[**0047**] Upon receiving the WLAN provisioning information in an overhead signaling message, the MS has no guarantee to detect an AP because the WLAN coverage within a cell sector may not be consistent. The probability of WLAN coverage increases in densely populated areas, such as shopping centers, stadiums, etc. Cellular systems desire to increase capacity in populated areas, and WLANs provide a means for increasing capacity in such areas. Cellular systems, therefore, implement WLANs in populated areas. On the other hand, WLAN coverage is not expected in rural areas, as capacity is generally not a concern in less populated areas.

[**0048**] Within cell **100**, the BS (not shown) supporting sector B **104** transmits an identifier of those WLAN for which the BS has knowledge. For example, if the network has relationship with the WLAN **#1120**, the BS in sector B **104** may transmit an advertisement of the WLAN **#1129**, wherein the advertisement provides the ESSID(1). In this way, when the MS (not shown) receives the advertisement, the MS is able to scan for the WLAN **#1129** based on the ESSID(1). Similarly, the BS of sector A **102** would also be able to advertise WLAN **#1120**. Additionally, if the cell network has a relationship with WLAN **#2130**, the BS of sector B **104** may also advertise for WLAN **#2130** providing ESSID(2).

[**0049**] **FIG. 2B** illustrates two embodiments of signaling messages. In a first embodiment, the system parameter message includes system parameter information **112** and a WLAN advertisement field **116**. The WLAN advertisement field **116** may be a single bit, wherein one polarity indicates WLAN availability and the opposite polarity indicates no availability. The WLAN advertisement **116** may be a multiple bit field providing further information, such as location information, or instruction to the MS regarding accessing WLAN information. In a second embodiment the system parameter message includes system parameter information **140**, a WLAN advertisement **142**, and a location information or Global Positioning System (GPS) **144**.

[**0050**] In alternate embodiments, the WLAN provisioning/advertisement information is not broadcast periodically

in overhead messages over common channels. When a MS wants to receive WLAN provisioning/advertisement information for a given cell sector, the MS uses a cellular signaling message, such as a cdma2000 registration message to request the WLAN provisioning/advertisement information from the BSC. Alternately, the MS may use a specific WLAN request message. In response, the BSC provides the WLAN provisioning/advertisement information upon demand. If the MS does not have a traffic channel, the BSC sends the reply to the MS over a common channel. The reply identifies available WLAN coverage in the designated cell sector. Note that the sector is identified by an identifier such as the Base_ID as used in cdma2000. When there is WLAN coverage in the sector, the reply from the BSC also includes the necessary WLAN provisioning/advertisement information so as to allow the MS to scan for WLAN coverage.

[**0051**] To avoid excessive signaling traffic (such as when multiple MSs request WLAN provisioning/advertisement information), the BSC may transmit the reply (i.e., the WLAN provisioning/advertisement information) via common channel(s). The WLAN information may be provided redundantly. In one embodiment, upon receipt of a request from a MS for WLAN provisioning/advertisement information, the BSC transmits the WLAN provisioning/advertisement information for a predetermined time period. The provision of such information on a common channel avoids excessive signaling messages incurred when other MSs request the same information at a proximate time.

[**0052**] The MS receives WLAN location information from the cellular network, wherein the WLAN location information identifies the APs supporting the WLAN. The location information may be latitude and longitude identifiers of an AP. The MS receives the WLAN location information and then displays the WLAN location information at the MS. The display may provide the AP location(s) in the context of a local map which may be stored in the MS. The display may be as illustrated in **FIG. 5**A, wherein a mobile wireless device **200** includes a keypad **204** and a display **202**. The display identifies the location of the WLAN APs in a graphical manner. The display may be a textual message.

[**0053**] There are several methods for the MS to obtain the location information of APs supporting the WLAN. In one embodiment, the MS obtains the location information of APs from the signaling overhead messages via common channels or dedicated channels, as described hereinabove. In an alternate embodiment, the user instructs the MS to request the location information of APs from an application server. The server in this case may reside in the backend of the operator network, so the MS uses higher-layer protocols (e.g., IP) to communicate with the server and obtain the location information of APs.

[**0054**] In one embodiment, illustrated in **FIG. 5B, a** method **250** provides a method of manual WLAN selection. At step **252** the user selects the map display function for identifying WLAN locations on the wireless device. The WLAN is identified within range at step **254**. If an automated scan is enabled at decision diamond **256**, processing continues to step **258** for the device to scan for WLANs. Else, processing continues to step **260** for the user to scan for WLANs. If a WLAN is accessible at decision diamond **262**, the wireless device then sends a WLAN registration request at step **264**. Else, processing returns to step **254** to await a WLAN identified in range.

[**0055**] **FIG. 3A** is a timing diagram for detection of a WLAN, wherein the MS sends a specific WLAN query or request for WLAN information to the BS. In response, the BS transmits the WLAN information to the MS, such as via a common channel WLAN advertisement. When a WLAN is available, the MS scans for the WLAN according to the WLAN information provided by the BS and sends a registration request to the WLAN to establish communication.

[**0056**] **FIG. 3B** is a timing diagram for detection of a WLAN, wherein the MS sends a registration request to the BS (i.e., cellular network). The registration request may include a specific request for WLAN information. Alternatively, the registration request may not specifically request WLAN information, but rather prompts the BS to provide WLAN information. In response to the registration request, the BS provides the WLAN information to the MS. When a WLAN is available, the MS scans for the WLAN according to the WLAN information provided by the BS and sends a registration request to the WLAN to establish communication.

[**0057**] **FIG. 4** is a timing diagram for detection of a WLAN, wherein the MS sends a registration request to the BS (i.e., cellular network). The registration request may include a specific request for WLAN information. Alternatively, the registration request may not specifically request WLAN information, but rather prompts the BS to provide WLAN information. In response to the registration request, the BS broadcasts the WLAN information on a common channel. When a WLAN is available, the MS scans for the WLAN according to the WLAN information provided by the BS and sends a registration request to the WLAN to establish communication.

[**0058**] MS With One Tuner

[**0059**] When the Mobile Station (MS) has one tuner for communication. In such a device, the single tuner is used for communication with both the cellular system and the WLAN system. The MS detects WLAN coverage and performs system selection between WLAN and cellular system, wherein the MS may only tune to one system (WLAN or cellular) at a given time.

[**0060**] The MS performs system detection and selection in the following scenarios: (1) the MS is idle (not active in communication) with respect to the cellular network, having no dedicated channel, and desires to scan for WLAN; (2) the MS has an active packet data session with the cellular network, having a dedicated channel, and desires to scan for WLAN; (3) the MS is tuned to the WLAN, and desires to receive cellular pages; and (4) the MS is tuned to the WLAN but with low signal strength.

[**0061**] In scenario (1) described above, if the MS is idle in the cellular network (i.e., no dedicated channel), the MS may decide to scan for WLAN coverage based on one or more factors, e.g., user command, pre-configured preference, WLAN availability advertisement as received from the cellular network, etc. The MS tunes to the cellular network during each assigned paging slot interval. In this way, the MS is able to receive any page indicator from the cellular network. Once the MS monitors for cellular page indicator, the MS then is able to tune to the WLAN frequencies and use passive or active scanning to detect WLAN coverage.

[**0062**] In scenario (2) described above, the MS has an active packet data session in the cellular network (i.e., with

dedicated channel). The MS may choose not to scan for WLAN while active data session in the cellular network. In this case, while the MS is active in the cellular network, the MS does not switch to WLAN even though it could access to WLAN. Although the MS might not be able to take the advantage of high-speed WLAN access, the MS would not experience service interruption. After the MS becomes idle in the cellular network, the MS tunes away from the cellular network to scan for the WLAN.

[**0063**] Alternatively, the cellular network may direct the MS to scan for WLAN coverage. In this case, the cellular network instructs the MS to scan for WLAN coverage. If there is WLAN coverage, the network may direct the MS to handover its packet data session to WLAN. This procedure might be useful when the network is overloaded or when the MS has low power strength. The procedure is described hereinbelow and is similar to the candidate frequency search procedure in a system supporting cdma2000.

[**0064**] The MS indicates any WLAN capability to the cellular network via over-the-air registration. If the MS is in a cell sector that has WLAN hot spots, the network may send a signaling message to request the MS to scan for WLAN coverage. The signaling request message contains WLAN information (e.g., frequencies, ESSID, etc.) and is sent over the MS's dedicated channel. The MS tunes to WLAN frequencies and actively or passively scans for the WLAN beacon. Then, the MS may have the following behaviors. (1) If the MS detects WLAN coverage, the MS tunes back to the cellular network to notify the WLAN search result. The cellular network then sends a signaling message to instruct the MS to handoff to WLAN. The MS tunes to WLAN and performs access authentication and optionally Mobile IP registration to handover its packet data session to WLAN. If access authentication or Mobile IP registration fails, the MS may tune back to the cellular network and originate for packet data service option.

[**0065**] (2) If the MS detects WLAN coverage, the MS does not return to the cellular network to notify the WLAN search result. Instead, the MS proceeds to perform WLAN access authentication and optionally Mobile IP registration to handover its packet data session to WLAN. In this case, if the cellular network didn't receive the signaling reply message after a timeout, the network assumes that the MS has left the cellular system and hence removes the MS's packet data session.

[**0066**] (3) If the MS fails to detect WLAN coverage, the MS re-tunes to the cellular network and sends a signaling reply message to inform the cellular network about the WLAN search result, and the network restores the active state of the MS's packet data session.

[**0067**] Continuing with scenario (2) as given hereinabove, still further, the MS may send a request to the cellular network to save the state information of the MS while the MS tunes away to scan for WLAN coverage. In this case, the MS requests the cellular network to save the state information while scanning for WLAN coverage. The MS sends a signaling request message (similar to the CDMA Offtime Report Message) to the 1× network. If the MS is in a cell sector that has WLAN hot spots, the network may send a signaling reply message that contains the necessary WLAN information for the MS to scan for WLAN coverage. If the MS detects WLAN coverage and is authenticated for access, the MS may proceed with Mobile IP registration to handover its packet data session via WLAN. If the MS fails to detect WLAN coverage or fails WLAN access authentication, the MS re-tunes to cellular network and sends a signaling message to request the cellular network to restore the active state of the MS's packet data session. If the cellular network did not receive the signaling request message after a specified timer has expired, the network assumes that the MS has left the cellular system and hence removes the MS's packet data session.

[**0068**] According to scenario (3) the MS is currently tuned to the WLAN. If the MS is not transmitting or receiving frames over the WLAN, the MS periodically tunes back to the cellular network and monitors the Paging Indicator on the Quick Paging Channel. If the Paging Indicator is "0," then there is no page for the MS, and the MS immediately tunes back to the WLAN frequency. In this case, the time the MS spent on the cellular frequency is minimal (in the order of ms). If the Paging Indicator is "1," then the MS monitors the Paging Channel for its paging slot. In a cdma2000 type network, the Paging Indicator occurs at most 100 ms before the MS's paging slot. The paging slot is 80 ms. Paging Indicator of "1" does not guarantee that the page is for the MS because a second MS's International Mobile Subscriber Identity (IMSI) may be hashed coincidentally to the same Paging Indicator as the first MS. Thus, the MS may spend a maximum of 180 ms on the paging channel for nothing. If the page is for the MS, it will reply with Paging Response and stay in the cellular network to receive the incoming circuit-switched voice call.

[**0069**] At the time the MS is scheduled to monitor the cellular network paging, if the MS is in the middle of transmitting or receiving frames over the WLAN, the MS should stay in the WLAN to complete the data delivery and thus skip a paging cycle. Potentially, the MS could miss a page, and the call set-up time of an incoming circuit-switched voice call increases. If the MS receives a page for an incoming circuit-switched voice call, the MS may respond as follows.

[**0070**] 1. Upon receiving the page, the MS may remain tuned to the cellular network to send Paging Response and accept the call. After the voice call, the MS may tune to the WLAN to continue the packet data session (if the MS still has WLAN coverage).

[**0071**] 2. Upon receiving the page, the MS immediately tunes back to the WLAN and sends a Disassociation message to the AP. Then, the MS switches to the cellular network, sends a Paging Response, and accepts the call. After the voice call, the MS may need to start a new packet data session in either the cellular network or the WLAN.

[**0072**] According to scenario (4), if the MS is tuned to the WLAN but detects the signal strength has dropped below an acceptable threshold, the MS may tune to the cellular network and proceeds to handover the packet data session to cellular network.

[**0073**] **FIG. 10A** illustrates one example of scenario (2), wherein the MS **702** currently has a packet data session with the cell network **706**. The MS **702** scans for a WLAN instruction message from the cell network **706**. Using the WLAN instruction message, which provisions the MS, the

MS scans for WLAN coverage. Upon detection of the WLAN, the MS **702** notifies the cell network of the result. As illustrated, the MS **702** detects a WLAN (AP **704**), and in response sends a notification to the cellular network of the scan result. The cellular network may then instruct the MS **702** to switch to the WLAN. The decision to switch from the cellular network **706** to the WLAN is based on loading of the network, bandwidth of the user, data requirements, etc. Once the cellular network **706** instructs the MS **702** to switch, the cellular network **706** removes the data session. The MS **702** then initiates authentication with the AP **704**. Note that if the authentication fails the MS may need to re-establish with the cellular network.

[**0074**] **FIG. 10B** illustrates another example of scenario (2), wherein the MS **702** currently has a packet data session with the cell network **706**. The MS **702** scans for a WLAN instruction message from the cell network **706**. Using the WLAN instruction message, which provisions the MS, the MS scans for WLAN coverage. Upon detection of the WLAN, the MS **702** notifies the cell network of the result. As illustrated, the MS **702** detects a WLAN (AP **704**), and in response initiates authentication with the AP **704**. The cellular network **706** then starts a timer, and when a time out period is expired, the cellular network **706** removes the data session.

[**0075**] **FIG. 10C** illustrates still another example, wherein the MS **702** is currently has a packet data session with the cell network **706**. The MS **702** scans for a WLAN instruction message from the cell network **706**. Using the WLAN instruction message, which provisions the MS, the MS scans for WLAN coverage. When no WLAN is detected, the MS **702** sends the search result to the cellular network **706**. The MS **702** continues the data session with the cellular network **706**.

[**0076**] Two Tuners

[**0077**] In the following example, the Mobile Station (MS) has two tuners that can tune to a cellular frequency and the WLAN frequency simultaneously. A MS **300** is illustrated in **FIG. 6** having an ESSID list **302**, which is stored in memory, a first tuner, tuner A **304**, and a second tuner, tuner B **306**. Tuner A is configured for communication with a WLAN. Tuner B **306** is configured for communication with a wireless cellular network. As illustrated, when MS **300** is within range of accessing AP **320**, tuner A **304** scans for a WLAN beacon transmitted by AP **320**. The WLAN beacon is transmitted periodically and identifies the WLAN supported by AP **320**. Tuner B **306** scans for a paging indicator from the cellular network transmitted by Base station Transceiver System (BTS) **322**. In this way, the MS **300** may scan for WLAN coverage while also scanning for cellular pages. Thus, the MS **300** detects WLAN coverage and performs system selection between WLAN and the cellular system using one tuner for each access medium.

[**0078**] The MS **300** may implement any of a variety the physical configurations. For example, a "Type A" device is a single handheld device (e.g., phone, Personal Digital Assistant (PDA)) having a built-in WLAN tuner and a cellular network tuner, or a slotted-in WLAN tuner card and cellular tuner card (e.g., CDMA2000 card). Additionally, a "Type B" device is a laptop computing device, such as a personal computer, having a WLAN tuner card, wherein the laptop computing device is connected to a cellular handset, such as a handset supporting cdma2000 communications.

[**0079**] For a type A device, the MS **300** is a single physical device (e.g., handset, PDA) that supports both WLAN and cellular network protocols. The MS **300** has two Radio Frequency (RF) tuners: a first for the cellular network; and a second for the WLAN.

[**0080**] Returning to **FIG. 6**, note that the WLAN beacon and the page indicator are not necessarily transmitted at a same time or with a same period. The MS **300** scans for the WLAN beacon with tuner A **304** over a cycle having a first period. The MS **300** scans for the page indicator of the cellular network over a cycle having a second period. Typically the second period is shorter than the first period. In other words, the page indicators are generated more frequently than the WLAN beacons.

[**0081**] Power conservation is an important design criterion in system detection and selection. Conservation of power at the mobile device is highly desirable to extend the operational time of the device between recharging the battery. If the MS **300** decides to scan for WLAN coverage, it is desirable to minimize power consumption during such scan while still monitoring cellular paging.

[**0082**] The MS **300** may decide to scan for WLAN coverage based on one or more factors, e.g., user command(s), pre-configured preference(s), application status (e.g., ongoing packet data session), WLAN availability advertisement as received from the cellular network, etc. One WLAN protocol defined by IEEE 802.11, and referred to herein as "802.11," allows the MS **300** to scan for WLAN coverage passively or actively. In passive scanning, the MS **300** listens for the WLAN beacon sent by the AP **320** on WLAN frequencies. The WLAN beacon contains the ESSID of AP **320**, referred to as ESSID (AP **320**). If the ESSID(AP **320**) matches an ESSID stored in the MS **300** ESID list **302**, this is an indication that the MS **300** has detected WLAN coverage, and that such coverage is provided by the MS **300** service provider. In active scanning, the MS **300** transmits a Probe Request that contains the ESSID of the MS **300**. If the AP **320** receives the Probe Request and the ESSID of the MS **300** matches the ESSID of the AP **320**, the AP **320** transmits a Probe Response to the MS **300**. If the MS has a list of multiple ESSIDs, the MS may transmit a Probe Request containing an ESSID having the highest preference. The ESSID preference may be stored as a system selection parameter in the Preference Database (described hereinabove).

[**0083**] For conserving power, it is desirable to maximize a sleep mode for MS **300**. In other words, it is desirable to maximize the time when MS **300** is using reduced power, or is in a sleep mode. Additionally, and as a result of such maximization, it is desirable to minimize the MS awake-time, or full power operation. Therefore, when the MS **300** periodically wakes, such as to check for pages or WLAN beacons, the MS **300** should simultaneously scan for any WLAN beacon as well as monitor for a cellular page indicator. If the paging cycle and beacon cycle are not synchronous, then the MS **300** wakes up according to the paging cycle to monitor the paging Indicator. In this scenario, when the MS **300** wakes, the MS **300** uses active scanning to scan for the WLAN beacon. If the paging cycle and beacon cycle are synchronous, then the MS wakes up periodically to monitor the paging Indicator and passively listen for any WLAN beacon. Synchronous paging and

beacon cycles provide a more power-efficient operation due to the use of passive scanning; however, such synchronization requires the AP **320** clock be synchronized with the cellular network timing.

[**0084**] One method for synchronization of the paging cycle and WLAN beacon cycle is to schedule the WLAN beacon to arrive at the same time as the first paging indicator in the Quick Paging Channel. According to this method, each MS is scheduled to wake just before the scheduled WLAN beacon arrival time. Note that due to potential collisions, the WLAN beacon may not be sent at the scheduled time; thus, there is no guarantee that a given WLAN beacon will arrive at the scheduled or anticipated time. The WLAN beacon is transmitted as a frame of data and therefore, complies with the same rules for accessing the shared medium as other transmissions. After receiving the WLAN beacon, some MS may need to stay awake a little longer in order to scan for the paging indicator. Again, this method requires synchronization of the clocks for generating the WLAN beacon and the cellular network paging indicator. Such synchronization is not always feasible or available.

[**0085**] After the MS **300** detects WLAN coverage, receives the WLAN beacon, the MS **300** uses certain criteria to handover a packet data session from the cellular network to the WLAN. The criteria may include whether the MS is idle in cellular network (i.e., no dedicated channel) or whether the WLAN signal strength is stable, etc. The MS **300** may wait for a pending packet data session to go dormant in the cellular network. The MS **300***d* then performs packet data session handover (i.e., sending Mobile IP registration via WLAN). This may be useful to minimize service interruption. Similarly, the MS **300** may perform packet data session handover when the WLAN signal strength is above an acceptable threshold for a specified period of time. In this way, the MS **300** ensures that access to the WLAN is sustainable. The measure may be any measure of channel quality and/or signal strength. The threshold may be predetermined or may dynamically be adjusted based on the actual performance of the communication. This may be useful to avoiding any ping-pong effect whereby the MS **300** switches between WLAN access and cellular network access due to changing conditions or signal strength that is at the margin of tolerance for operation. Still further, upon detection of the WLAN, the MS **300** may notify the user and wait for the user to manually select WLAN.

[**0086**] Another consideration is to minimize power consumption while the MS **300** is receiving data via the WLAN and is monitoring for cellular paging. After the MS **300** performs the handover of the packet data session to the WLAN, the MS **300** may receive data via the WLAN as well as incoming circuit-switched voice calls via the cellular network. The MS **300** relies on the cellular sleep mode to conserve power while monitoring for cellular paging. The 802.11 protocol has a similar method for the MS **300** to conserve power while waiting for incoming data. If the cdma2000 Quick Paging Channel, or other similar mechanism, is supported, the MS **300** may further conserve power by synchronizing the cellular sleep mode and the 802.11 power-saving mode.

[**0087**] According to the 802.11 power-saving mode the MS **300** sends an Association Request (AR) to the AP **320**, wherein the AR indicates a number (e.g., N) of beacon periods that the MS **300** is to be in the power saving mode. The AP **320** keeps track a list of MSs that have enabled the power saving mode. The AP **320** buffers frames destined for the MS **300** while it is in the power saving mode. The AP **320** periodically sends a beacon containing the Traffic Indication Map (TIM) (not shown) indicating whether each MS has frames buffered in the AP **320**. The MS **300** wakes up every N beacon periods to monitor the beacon and the included TIM. If the TIM indicates pending frames for the MS **300**, the MS **300** sends a Power-Save Poll to the AP **320**, to which the AP **320** responds by sending one frame of data to the MS **300**. The frame will include a control field, wherein a control bit indicates if there are more frames buffered for the MS **300**. If the control bit is set, the MS **300** is required to send another Power-Save Poll to the AP **320**. If the control bit is cleared, there are no pending frames for MS **300**.

[**0088**] The MS **300** may achieve further power conservation when the 802.11 power-saving mode is synchronized with the cellular sleep mode. In this way, the MS wakes up periodically to monitor for both beacon (and included TIM) as well as to monitor for the cellular page indicator. Synchronization may be achieved by synchronizing the clock of the AP **320** to the cellular timing, wherein the cellular paging interval and WLAN beacon interval are in lock-step. For example, when the WLAN beacon interval is equal to the cellular paging interval, the beacon may be scheduled to arrive at the same time as the first paging indicator in the cellular system, such as provided on the cdma2000 Quick Paging Channel. Each MS wakes up just before the beacon arrival. Some MS may need to stay a little longer (e.g., 40 ms after WLAN beacon arrival) to receive the paging indicator.

[**0089**] For systems such as those without the cdma2000 Quick Paging Channel, the Beacon cycle and paging cycle generally are not synchronous, i.e., the time difference between the WLAN beacon and the cellular paging slot may vary for each MS. If the time difference is small, then the MS can wake up to monitor both the Beacon and its paging slot before goes back to sleep. If the time difference is large, such procedure may not be power-efficient for each MS to wake up and stay awake to monitor both the WLAN beacon and the paging slot. Note that each MS may have a designated paging slot, and therefore, the differential time required to receive both the WLAN beacon and the paging indicator may not be the same for each MS and typically will be different.

[**0090**] **FIG. 7** illustrates a process **350** applicable to the MS **300**. The MS **300** first wakes for a cellular paging indicator (step **354**). The MS **300** may schedule this waking to coincide with a common time for a first paging indicator slot and a WLAN beacon, or may use some other criteria to determine when to wake. The MS **300** determines (decision diamond **356**) whether to perform active WLAN scanning or passive WLAN scanning. For active scanning, the MS **300** sends a request for a WLAN beacon (step **358**), and continues to then scan for the WLAN beacon (step **360**). In this way, the MS **300** avoid extended power consumption while for waiting for a next scheduled WLAN beacon transmission. For passive scanning, the MS scans for the WLAN beacon (step **360**) until a beacon is detected.

[0091] **FIG. 8** illustrates communication flow within a network **500** including both cellular communications and Internet Protocol (IP) communications. The Internet **502** is coupled to a Home Agent (HA) **516** associated with MS **508**. The Internet is further coupled to a File Transfer Protocol (FTP) server **514**, an Access Router **510**, and a Packet Data Service Node (PDSN) **504**. The Access Router **510** communicates with an AP **512** via a wireless interface. The interface between the Access Router **510** and the AP **512** is a WLAN interface, wherein the Access Router **510** and the AP **512** are part of a WLAN. When the MS **508** is situated so as to communicate with the AP **512**, the MS **508** accesses the WLAN via a wireless interface with the AP **512**. For cellular communications, the MS **508** communicates over the air with a BS **506**. The BS **506** is configured for communication with PDSN **504** via an interface identified as cdma2000. Such interface may be consistent with another cellular protocol.

[0092] Note that a wireless device may include multiple tuners, wherein each tuner is adapted for communication with a different access medium, e.g., WLAN and cellular network. Alternately, a wireless device may be coupled to another wireless device, wherein each includes a tuner, and the combination results in multiple tuners. In one such configuration, a laptop (computing device) operates together with a cellular handset. The laptop includes a WLAN card or built-in WLAN port, while the handset supports cellular communications. WLAN information (e.g., ESSID) is provisioned in the laptop to scan for WLAN coverage.

[0093] **FIG. 9** illustrates signal and message flow in such a configuration. As illustrated, the laptop **600** is coupled to the MS **602** for communication. The laptop **600** has a tuner, which is currently adapted for communication with a WLAN, such as via AP **604**. The MS **602** has a tuner, which is currently adapted for communication with a cellular network **606**, such as a cdma2000 network.

[0094] In the configuration illustrated in **FIG. 9**, the laptop **600** is currently processing a packet data session with the cellular network **606** through the MS **602**. During the packet data session, when the MS **602** receives a WLAN availability advertisement from the cellular network **606**, the MS **602** may notify the laptop **600** via a signaling protocol defined between the MS **602** and the laptop **600**. On receipt of such notification the laptop **600** may choose to scan for WLAN coverage. The laptop **600** may then perform system selection based on WLAN signal strength and acquire a WLAN signal from AP **604**. The laptop **600** and the AP **604** then authenticate the connection. Once authentication is completed, the laptop **600** disconnects from the cellular network through the MS **602**. The MS **602** then disconnects the packet data session with the cellular network **606**. From this point, the packet data session is processed between the laptop **600** and the AP **604**.

[0095] As detailed in the example given above and with respect to **FIG. 9**, when the laptop **600** has a current packet data session with the cellular network **606**, the laptop may detect a strong WLAN signal through the resident tuner. The laptop **600** may choose to switch to WLAN access immediately. Upon WLAN detection, the laptop **600** needs to be authenticated for WLAN access. For single subscription/authentication of WLAN and cdma2000, the secret is stored in the handset's User Interface Module (UIM) (not shown), which may be removable or non-removable. Thus, signaling messages are needed between the laptop **600** and MS **602** to perform WLAN access authentication. If the WLAN access authentication is successful, the laptop **600** performs Mobile IP registration via the WLAN (i.e., via AP **604**). If the Mobile IP registration is successful, the laptop **600** sends a message (e.g., AT command) to the MS **602** to release the packet data session. The MS **602** may identify the data session by a Service Option (SO), such as SO **33** in cdma2000. The laptop **600** may then maintain the packet data session via the cellular network until handover of the packet data session to the WLAN is completed.

[0096] Alternatively, the laptop may switch to the WLAN if the packet data session currently has no data pending transfer so as to minimize service interruption (e.g., downloading a file). Upon detecting a strong WLAN signal, the laptop **600** waits for a given time period (e.g., several seconds) to detect any activity of data transfer. If no activity is detected, the laptop **600** performs WLAN access authentication, followed by Mobile IP registration via the WLAN, and finally release of the cellular packet data service option, as described above.

[0097] When the laptop **600** is accessing WLAN and the signal strength deteriorates below an acceptable threshold, the laptop **600** may trigger the MS **602** to originate a packet data service option. The trigger may be an explicit signaling message (e.g., AT commands) or Mobile IP registration message, etc. wherein the laptop **600** desires to send via the cellular network. If the Mobile IP registration is successful, the laptop **600** continues the packet data session via the cellular network. In order to avoid ping-pong effect between WLAN and the cellular network, hysteresis mechanisms may be used, such as, switching to the WLAN only when the WLAN signal remains above a specified threshold for a specified period of time. The laptop may switch between the WLAN and the cellular network automatically (e.g., operation transparent to the user) or manually initiated by the user.

[0098] Those of skill in the art would understand that information and signals may be represented using any of a variety of different technologies and techniques. For example, data, instructions, commands, information, signals, bits, symbols, and chips that may be referenced throughout the above description may be represented by voltages, currents, electromagnetic waves, magnetic fields or particles, optical fields or particles, or any combination thereof.

[0099] Those of skill would further appreciate that the various illustrative logical blocks, modules, circuits, and algorithm steps described in connection with the embodiments disclosed herein may be implemented as electronic hardware, computer software, or combinations of both. To clearly illustrate this interchangeability of hardware and software, various illustrative components, blocks, modules, circuits, and steps have been described above generally in terms of their functionality. Whether such functionality is implemented as hardware or software depends upon the particular application and design constraints imposed on the overall system. Skilled artisans may implement the described functionality in varying ways for each particular application, but such implementation decisions should not be interpreted as causing a departure from the scope of the present invention.

[0100] The various illustrative logical blocks, modules, and circuits described in connection with the embodiments disclosed herein may be implemented or performed with a general purpose processor, a digital signal processor (DSP), an application specific integrated circuit (ASIC), a field programmable gate array (FPGA) or other programmable logic device, discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described herein. A general purpose processor may be a microprocessor, but in the alternative, the processor may be any conventional processor, controller, microcontroller, or state machine. A processor may also be implemented as a combination of computing devices, e.g., a combination of a DSP and a microprocessor, a plurality of microprocessors, one or more microprocessors in conjunction with a DSP core, or any other such configuration.

[0101] The steps of a method or algorithm described in connection with the embodiments disclosed herein may be embodied directly in hardware, in a software module executed by a processor, or in a combination of the two. A software module may reside in RAM memory, flash memory, ROM memory, EPROM memory, EEPROM memory, registers, hard disk, a removable disk, a CD-ROM, or any other form of storage medium known in the art. An exemplary storage medium is coupled to the processor such the processor can read information from, and write information to, the storage medium. In the alternative, the storage medium may be integral to the processor. The processor and the storage medium may reside in an ASIC. The ASIC may reside in a user terminal. In the alternative, the processor and the storage medium may reside as discrete components in a user terminal.

[0102] The previous description of the disclosed embodiments is provided to enable any person skilled in the art to make or use the present invention. Various modifications to these embodiments will be readily apparent to those skilled in the art, and the generic principles defined herein may be applied to other embodiments without departing from the spirit or scope of the invention. Thus, the present invention is not intended to be limited to the embodiments shown herein but is to be accorded the widest scope consistent with the principles and novel features disclosed herein.

What is claimed is:

1. A method for identifying a Wireless Local Area Network (WLAN) comprising:

scanning for a cellular paging indicator;

scanning for a WLAN beacon;

determining if the WLAN is accessible;

if the WLAN is accessible, registering with the WLAN.

2. The method as in claim 1, wherein scanning for a WLAN beacon comprises:

requesting a WLAN beacon; and

scanning for a WLAN beacon.

3. The method as in claim 1, wherein the WLAN beacon and the cellular paging indicator are synchronously transmitted.

4. The method as in claim 1, further comprising:

if the remote station has a current packet data session active in a cellular network:

detecting the WLAN beacon;

waiting for a the current packet data session to become dormant;

performing packet data session handover to the WLAN.

5. The method as in claim 4, wherein performing a packet data session handover comprises:

comparing a signal strength of the WLAN beacon to a threshold; and

if the signal strength of the WLAN beacon is greater than the threshold, performing packet data session handover to the WLAN.

6. The method as in claim 4, wherein performing packet data session handover comprises:

performing mobile Internet Protocol (IP) registration via the WLAN.

7. The method as in claim 1, further comprising:

when the remote station is in a power saving mode, waking the remote station to scan for a cellular paging indicator.

8. The method as in claim 7, wherein the WLAN beacon and the cellular paging indicator are synchronous.

9. The method as in claim 7, wherein the WLAN beacon has a first assigned time slot, the cellular paging indicator has a second assigned time slot, scanning for the WLAN beacon comprises:

waiting for a timer period equal to the difference between the second and first assigned time slots;

scanning for the WLAN beacon.

10. The method as in claim 1, further comprising:

scanning for the cellular paging indicator by a first tuner; and

scanning for the WLAN beacon by a second tuner.

11. The method as in claim 1, wherein scanning for the WLAN beacon comprises:

if a packet data session is active in a cellular network, prohibiting scanning for the WLAN beacon; and

if there is no packet data session active in the cellular network, scanning for the WLAN beacon.

12. The method as in claim 1, wherein scanning for the WLAN beacon comprises:

receiving instruction from the cellular network to scan for the WLAN beacon; and

scanning for the WLAN beacon.

13. The method as in claim 1, wherein scanning for the WLAN beacon comprises:

requesting the cellular network to save state information while scanning for the WLAN beacon; and

scanning for the WLAN beacon.

14. A method, comprising:

establishing a packet data session via a cellular network;

receiving an instruction to scan for Wireless Local Area Network (WLAN) beacon;

registering with the WLAN in response to the instruction; and

sending a message to release a packet data session from the cellular network.

15. The method as in claim 14, further comprising:

monitoring a signal strength of signals received from the WLAN; and

if the signal strength falls below a threshold, re-establishing the packet data session with the cellular network.

16. An apparatus for identifying a Wireless Local Area Network (WLAN) comprising:

means for scanning for a cellular paging indicator;

means for scanning for a WLAN beacon;

means for determining if the WLAN is accessible;

if the WLAN is accessible, registering with the WLAN.

17. An apparatus, comprising:

means for establishing a packet data session via a cellular network;

means for receiving an instruction to scan for Wireless Local Area Network (WLAN) beacon;

means for registering with the WLAN in response to the instruction; and

means for sending a message to release a packet data session from the cellular network.

* * * * *