




US 20040200721A1

(19) **United States**(12) **Patent Application Publication**
Bhullar et al.(10) **Pub. No.: US 2004/0200721 A1**(43) **Pub. Date: Oct. 14, 2004**(54) **BIOSENSOR**(22) Filed: **Aug. 29, 2001**(76) Inventors: **Raghibir S. Bhullar**, Indianapolis, IN
(US); **Henning Groll**, Indianapolis, IN
(US); **John T. Austera**, Indianapolis, IN
(US); **Douglas P. Walling**, Indianapolis,
IN (US); **Timothy I. Ranney**, Lebanon,
IN (US); **James L. Pauley JR.**, Fishers,
IN (US)**Publication Classification**(51) **Int. Cl.⁷** **G01N 27/327**(52) **U.S. Cl.** **204/403.01**(57) **ABSTRACT**

The present invention relates to a biosensor. The biosensor includes a support substrate, an electrically conductive coating positioned on the support substrate, the coating being formed to define electrodes and a code pattern, wherein there is sufficient contrast between the conductive coating and the substrate such that the code pattern is discernible, and a cover cooperating with the support substrate to define a channel. At least a portion of the electrodes are positioned in the channel.

Correspondence Address:

**THE LAW OFFICE OF JILL L. WOODBURN,
L.L.C.****JILL L. WOODBURN****128 SHORE DR.****OGDEN DUNES, IN 46368 (US)**(21) Appl. No.: **09/942,515**




FIG. 1






FIG. 2






FIG. 5




FIG. 6

BIOSENSOR

FIELD OF THE INVENTION

[0001] The present invention relates to a biosensor, more particularly to an electrochemical biosensor with a code pattern thereon.

BACKGROUND AND SUMMARY OF THE INVENTION

[0002] Electrochemical biosensors are known. They have been used to determine the concentration of various analytes from biological samples, particularly from blood. Electrochemical biosensors are described in U.S. Pat. Nos. 5,413,690; 5,762,770; 5,798,031; and 5,997,817 the disclosure of each of which is expressly incorporated herein by reference. It is also known to include a code on a test strip that identifies the manufacturing batch of the strip. See WO 99/22236.

[0003] According to one aspect of the present invention a biosensor is provided. The biosensor comprises a support substrate, an electrically conductive coating positioned on the support substrate, the coating being formed to define electrodes and a code pattern, wherein there is sufficient contrast between the conductive coating and the substrate such that the code pattern is discernible, and at least one reagent positioned on at least one electrode.

[0004] According to another aspect of the present invention a biosensor is provided. The biosensor comprises a support substrate, an electrically conductive coating positioned on the support substrate, the coating being formed to define electrodes and a code pattern, wherein there is sufficient contrast between the conductive coating and the substrate such that the code pattern is discernible, and a cover cooperating with the support substrate to define a channel. At least a portion of the electrodes are positioned in the channel.

[0005] In addition, a method of forming a biosensor is provided in accordance with the present invention. The method comprises the steps of providing a substrate coated with a electrically conductive material, ablating the electrically conductive material to form electrodes and a code pattern, wherein there is sufficient contrast between the conductive coating and the substrate such that the code pattern is discernible, and applying a reagent to at least one of the electrodes.

[0006] Still further, in accordance with the present invention a biosensor is provided. The biosensor comprises a support substrate and an electrically conductive coating positioned on the support substrate. The coating is formed to define electrodes and means for identifying the biosensor, wherein there is sufficient contrast between the conductive coating and the substrate such that the identifying means is discernible.

[0007] Additional features of the invention will become apparent to those skilled in the art upon consideration of the following detailed description of the preferred embodiment exemplifying the best mode of carrying out the invention as presently perceived.

BRIEF DESCRIPTION OF THE DRAWINGS

[0008] The detailed description particularly refers to the accompanying figures in which:

[0009] **FIG. 1** is a perspective view of a biosensor in accordance with the present invention, showing the biosensor formed to include a code pattern formed thereon.

[0010] **FIG. 2** is an exploded assembly view of the biosensor of **FIG. 1**, showing the biosensor including an electrode array positioned at one end, a spacer substrate including a notch, and a cover formed to extend over a portion of the notch.

[0011] **FIG. 3** is a view taken along lines 3-3 of **FIG. 1**.

[0012] **FIG. 4** is a view taken along lines 4-4 of **FIG. 1**.

[0013] **FIG. 5** is an enlarged top view of an alternative code pattern formed on a biosensor in accordance with the present invention.

[0014] **FIG. 6** is an enlarged top view of an alternative code pattern formed on a biosensor in accordance with the present invention.

DETAILED DESCRIPTION OF THE INVENTION

[0015] The present invention relates to a biosensor and a method for manufacturing a biosensor that has a specific code pattern. This code pattern is beneficially formed from the same electrically conductive material and in the same manner as the electrodes of the biosensor, which reduces steps in the manufacturing process. Laser ablation is preferably used in forming the code pattern while generating the electrode pattern. The code pattern can be read in a number of ways, non-limiting examples of which include optically or electrically depending on the structures formed onto the biosensor. The structures could show contrast in their optical reflectivity, their electrical conductivity, or their resistance respectively. The structures could also be high reflectivity areas surrounded by low reflectivity areas or vice versa, or areas of high electrical conductivity surrounded by areas of low conductivity. Aspects of the invention are presented in **FIGS. 1-6**, which are not drawn to scale and wherein like components in the several views are numbered alike.

[0016] **FIGS. 1-4** illustrate an aspect of the invention in the form of a biosensor **10** having an electrode-support substrate **12**, an electrical conductor **13** positioned on the substrate **12** that is disrupted to define electrodes **14, 16**, a spacer substrate **18** positioned on substrate **12**, and a cover substrate **20** positioned on the spacer substrate **18**. Biosensor **10** is preferably rectangular in shape. It is appreciated however, that biosensor **10** can assume any number of shapes in accordance with this disclosure. Biosensor **10** is preferably produced from rolls of material however, it is understood that biosensor **10** can be constructed from individual sheets in accordance with this disclosure. Thus, the selection of materials for the construction of biosensor **10** necessitates the use of materials that are sufficiently flexible for roll processing, but which are still rigid enough to give a useful stiffness to finished biosensor **10**.

[0017] Referring to **FIG. 4**, the support substrate **12** includes a first surface **22** facing the spacer substrate **18** and a second surface **24**. In addition, as shown in **FIG. 2**, substrate **12** has opposite first and second ends **26, 28** and opposite edges **30, 32** extending between the first and second ends **26, 28**. Substrate **12** is generally rectangular in shape, it is appreciated however, that support may be formed in a

variety of shapes and sizes in accordance with this disclosure. Substrate **12** is formed of a flexible polymer and preferably from a flexible polymer and preferably from a polymer such as a polyester or polyimide, polyethylene naphthalate (PEN). A non-limiting example of a suitable PEN is 5 mil (125 μm) thick KALADDEX®, a PEN film commercially available from E.I. DuPont de Nemours, Wilmington, Del., which is coated with gold by ROWO Coating, Henbolzbelm, Germany.

[0018] Electrodes **14**, **16** are created or isolated from conductor **13** on first surface **22** of substrate **12**. Non-limiting examples of a suitable electrical conductor **13** include aluminum, carbon (such as graphite), cobalt, copper, gallium, gold, indium, iridium, iron, lead, magnesium, mercury (as an amalgam), nickel, niobium, osmium, palladium, platinum, rhenium, rhodium, selenium, silicon (such as highly doped polycrystalline silicon), silver, tantalum, tin, titanium, tungsten, uranium, vanadium, zinc, zirconium, mixtures thereof, and alloys, oxides, or metallic compounds of these elements. Preferably, electrical conductor **13** is selected from the following materials: gold, platinum, palladium, iridium, or alloys of these metals, since such noble metals and their alloys are unreactive in biological systems. Most preferably, electrical conductor **13** is gold.

[0019] Electrodes **14**, **16** are isolated from the rest of the electrical conductor **13** by laser ablation. See FIG. 4. Techniques for forming electrodes on a surface using laser ablation are known. See, for example, U.S. patent application Ser. No. 09/411,940, filed Oct. 4, 1999, and entitled "LASER DEFINED FEATURES FOR PATTERNED LAMINATES AND ELECTRODE", the disclosure of which is expressly incorporated herein by reference. Preferably, electrodes **14**, **16** are created by removing the electrical conductor **13** from an area extending around the electrodes to form a gap of exposed support substrate **12**. Therefore, electrodes **14**, **16** are isolated from the rest of the electrically-conductive material on substrate **12** by a gap having a width of about 25 μm to about 500 μm , preferably the gap has a width of about 100 μm to about 200 μm . Alternatively, it is appreciated that electrodes **14**, **16** may be created by laser ablation alone on substrate **12**. It is appreciated that while laser ablation is the preferred method for forming electrodes **14**, **16** given its precision and sensitivity, other techniques such as lamination, screen-printing, or photolithography may be used in accordance with this disclosure.

[0020] As shown in FIG. 2, electrodes **14**, **16** cooperate with one another to define an electrode array **36**. In addition, electrodes **14**, **16** each include a contact **34** and a lead **38** extending between the contact **34** and the array **36**. It is appreciated that the leads **38** extending from the array can be formed to have many lengths and extend to a variety of locations on the electrode-support substrate **12**. It is appreciated that the configuration of the electrode array, the number of electrodes, as well as the spacing between the electrodes may vary in accordance with this disclosure and that a greater than one array may be formed as will be appreciated by one of skill in the art.

[0021] Referring again to FIGS. 2 and 3, a recess **35** is formed from the electrical conductor **13** by laser ablation using techniques as described above. Recess is created by removing the electrical conductor **13** to expose the first

surface **22** of the support substrate **12** adjacent to the first end **26**. It is appreciated that a portion of the first surface **22** may also be removed to form the recess **35** in accordance with this disclosure.

[0022] In addition, as shown in FIGS. 1, 2, and 4, the discernible code pattern **40** is formed from the electrical conductor **13** by laser ablation using techniques as described above with reference to electrodes **14**, **16**. Specifically, the code pattern **40** is created by removing the electrical conductor **13** in a pre-defined pattern to expose the first surface **22** of the support substrate **12**. While pattern **40** is illustratively a barcode type pattern, it is appreciated that the pattern **40** can take on any number of shapes and patterns, non-limiting examples of which are shown in FIGS. 5 and 6.

[0023] It is also appreciated that the pattern **40** can be provided in a human readable, optical readable, or electrical readable form in accordance with this disclosure. The structures could show contrast in their optical reflectivity, their electrical conductivity, or their resistivity respectively. To aid in contrasting the electrical conductivity of the code pattern **40**, the electrical conductor **13** of the pattern **40** may be coated with a second conductive material (not shown) that is different from the electrical conductor **13**. Non-limiting examples of the second conductive material include carbon and silver. It is appreciated, however, that a wide variety of materials may be coated on the electrical conductor **13** to change the electrical property of the code pattern **40**.

[0024] It is also appreciated; electrodes **14**, **16** could be formed from layers of electrically conductive materials having different colors, reflectivity, conductance, etc. Thus, the code pattern can be formed by removing a portion of the electrical conductor layers, leaving behind areas of high reflectivity surrounded by low reflectivity areas or vice versa, areas of high electrical conductivity surrounded by areas of low conductivity or vice versa. It is also possible to laser etch a code pattern that has a known resistance and this area can be read electrochemically to identify or recognize the code pattern. Moreover, it is appreciated that the code pattern can be a combination of any of the above readable forms in accordance with the present invention.

[0025] As shown in FIG. 4, the code pattern **40** is isolated from the rest of the electrically conductive material **13** on substrate **12** by gaps **42**. Gaps **42** can have a wide variety of widths in accordance with this disclosure depending upon the specific use of the code pattern **40**. Non-limiting examples of widths of the gaps include from about 1 μm to about 1000 μm . Alternatively, it is appreciated that the code pattern **40** may be created by laser ablation alone on substrate **12**. It is appreciated that while laser ablation is the preferred method for forming the code pattern **40** given its precision and sensitivity, other techniques such as lamination, screen-printing, or photolithography may be used in accordance with this disclosure.

[0026] The manufacturer of biosensor **10** may maintain a central database containing a set of code patterns, each of which uniquely identifies an individual biosensor, or batch of biosensors. There may also be associated with each code pattern a set of calibration data for the biosensor **10**. It is appreciated that the code patterns may be associated with any number of identification or data sets in accordance with the present invention.

[0027] Spacer substrate **18** of biosensor **10** includes an upper surface **44** and a lower surface **46** facing the substrate **12**. In addition, the spacer substrate **18** includes opposite first and second ends **48**, **50**. First end **48** includes a notch **52**, which is defined by a border **54**. The border illustratively includes three generally linear sides. It is appreciated that the notch can take on a variety of shapes and sizes in accordance with this disclosure. When biosensor **10** is assembled, the border **54** extends about at least a portion of the array **36** so that the array **36** is at least partially exposed in the notch **52**.

[0028] Spacer substrate **18** is formed of a flexible polymer and preferably from a flexible polymer and preferably from a polymer such as an adhesive coated polyethylene terephthalate (PET) polyester. A non-limiting example of a suitable PET is 3 mil (75 μ m) thick white PET film both sides of which are coated with a pressure-sensitive adhesive (Product # ARcare 8877) commercially available from Adhesives Research, Inc. Glen Rock, Pa. It is appreciated that spacer substrate **18** may be constructed of a variety of materials and may be coupled to the substrate **12** and the cover substrate **20** using a wide variety of commercially available adhesives, or by welding (heat or ultrasonic) when large portions of the surface **22** of the electrode support substrate **12** are exposed and not covered by electrical conductor **13**.

[0029] The cover substrate **20** is coupled to the upper surface **44** of the spacer substrate **18**. See FIG. 3. The cover substrate **20** includes opposite first and second ends **56**, **58**. The cover substrate **20** is coupled to the spacer substrate **18** such that the first end **56** is spaced-apart from the end **48** of the spacer substrate **18** and the second end **58** is spaced-apart from the end **50** of the spacer substrate **18**. When biosensor **10** is assembled, cover substrate **20** cooperates with the spacer support **20** and the electrode-support **12** to define a capillary channel **60**.

[0030] Cover substrate **20** is generally rectangular in shape, it is appreciated, however, that the cover substrate may be formed in a variety of shapes and sizes in accordance with this disclosure. Cover substrate **20** is formed from a flexible polymer and preferably from a polymer such as polyester. A non-limiting example of a suitable polymer is 3.9 mil (99 μ m) thick 3M hydrophilic polyester film (3M Product #9971), commercially available from 3M Healthcare, St. Paul, Minn.

[0031] Referring now to FIGS. 1 and 3, the capillary channel **60** is generally linear in shape and is defined by the cover substrate **20**, the electrode support substrate **12**, and the border **54** of the spacer substrate **18**. When biosensor **10** is assembled, channel **60** extends across the electrode array **36**. Cover substrate **20** does not extend across the entire notch **52**, therefore, a portion of the notch serves as an air outlet in accordance with this disclosure.

[0032] An electrochemical reagent **62** is positioned on the array **36**. The reagent **62** provides electrochemical probes for specific analytes. The term analyte, as used herein, refers to the molecule or compound to be quantitatively determined. Non-limiting examples of analytes include carbohydrates, proteins, such as hormones and other secreted proteins, enzymes, and cell surface proteins; glycoproteins; peptides; small molecules; polysaccharides; antibodies (including monoclonal or polyclonal Ab); nucleic acids; drugs; toxins; viruses of virus particles; portions of a cell wall; and other compounds processing epitopes. The analyte of interest is preferably glucose.

[0033] The choice of the specific reagent **62** depends on the specific analyte or analytes to be measured, and are well known to those of ordinary skill in the art. An example of a reagent that may be used in biosensor **10** of the present invention is a reagent for measuring glucose from a whole blood sample. A non-limiting example of a reagent for measurement of glucose in a human blood sample contains 62.2 mg polyethylene oxide (mean molecular weight of 100-900 kilo Daltons), 3.3 mg NATROSOL 244M, 41.5 mg AVICEL RC-591 F, 89.4 mg monobasic potassium phosphate, 157.9 mg dibasic potassium phosphate, 437.3 mg potassium ferricyanide, 46.0 mg sodium succinate, 148.0 mg trehalose, 2.6 mg TRITON X-100 surfactant, and 2,000 to 9,000 units of enzyme activity per gram of reagent. The enzyme is prepared as an enzyme solution from 12.5 mg coenzyme PQQ and 1.21 million units of the apoenzyme of quinoprotein glucose dehydrogenase. This reagent is further described in U.S. Pat. No. 5,997,817, the disclosure of which is expressly incorporated herein by reference.

[0034] Non-limiting examples of enzymes and mediators that may be used in measuring particular analytes in biosensor **10** are listed below in Table 1.

TABLE 1

Analyte	Enzymes	Mediator (Oxidized Form)	Additional Mediator
Glucose	Glucose Dehydrogenase and Diaphorase	Ferricyanide	
Glucose	Glucose-Dehydrogenase (Quinoprotein)	Ferricyanide	
Cholesterol	Cholesterol Esterase and Cholesterol Oxidase	Ferricyanide	2,6-Dimethyl-1,4-Benzoquinone 2,5-Dichloro-1,4-Benzoquinone or Phenazine Ethosulfate
HDL Cholesterol	Cholesterol Esterase and Cholesterol Oxidase	Ferricyanide	2,6-Dimethyl-1,4-Benzoquinone 2,5-Dichloro-1,4-Benzoquinone or Phenazine Ethosulfate
Triglycerides	Lipoprotein Lipase, Glycerol Kinase, and Glycerol-3-Phosphate Oxidase	Ferricyanide or Phenazine Ethosulfate	Phenazine Methosulfate
Lactate	Lactate Oxidase	Ferricyanide	2,6-Dichloro-1,4-Benzoquinone
Lactate	Lactate Dehydrogenase and Diaphorase	Ferricyanide Phenazine Ethosulfate, or Phenazine Methosulfate	
Lactate Dehydrogenase	Diaphorase	Ferricyanide	Phenazine Ethosulfate, or Phenazine Methosulfate
Pyruvate	Pyruvate Oxidase	Ferricyanide	
Alcohol	Alcohol Oxidase	Phenylenediamine	
Bilirubin	Bilirubin Oxidase	1-Methoxy-Phenazine Methosulfate	
Uric Acid	Uricase	Ferricyanide	

[0035] In some of the examples shown in Table 1, at least one additional enzyme is used as a reaction catalyst. Also,

some of the examples shown in Table 1 may utilize an additional mediator, which facilitates electron transfer to the oxidized form of the mediator. The additional mediator may be provided to the reagent in lesser amount than the oxidized form of the mediator. While the above assays are described, it is contemplated that current, charge, impedance, conductance, potential, or other electrochemically indicated property of the sample might be accurately correlated to the concentration of the analyte in the sample with biosensor **10** in accordance with this disclosure.

[0036] A plurality of biosensors **10** are typically packaged in a vial, usually with a stopper formed to seal the vial. It is appreciated, however, that biosensors **10** may be packaged individually, or biosensors can be folded upon one another, rolled in a coil, stacked in a cassette magazine, or packed in blister packaging.

[0037] Biosensor **10** is used in conjunction with the following:

[0038] 1. a power source in electrical connection with contacts **34** and capable of supplying an electrical potential difference between electrodes **14**, **16** sufficient to cause diffusion limited electro-oxidation of the reduced form of the mediator at the surface of the working electrode; and

[0039] 2. a meter in electrical connection with contacts **34** and capable of measuring the diffusion limited current produced by oxidation of the reduced form of the mediator with the above-stated electrical potential difference is applied.

[0040] The meter is provided with a pattern reader that is capable of reading the code pattern **40** into a memory of the meter. The reader can be an electrical or optical reader in accordance with the present invention. The reader is formed to read the code pattern **40** when the biosensor **10** is inserted into the meter. When, however, the code pattern is in a human readable form, it is appreciated that the meter may include an interface, which permits the user to input the information from the code pattern manually. There are many ways to optically read code pattern **40** such as laser scanners, pen-like wands, and charge-couple-device (CCD) scanners. A non-limiting example of a suitable optical reader suitable for use with the present invention includes a light emitting diode(s) (LED), a lens, and a photodiode. It is appreciated that the reader may be an independent internal component of the meter.

[0041] The meter may further be formed to transfer the code pattern from the meter to a memory unit where it is stored. It is appreciated that the memory unit can be formed to store information regarding the specifics of the code pattern as well as patient information including previous meter readings. The meter will normally be adapted to apply an algorithm to the current measurement, whereby an analyte concentration is provided and visually displayed. Improvements in such power source, meter, and biosensor system are the subject of commonly assigned U.S. Pat. No. 4,963,814, issued Oct. 16, 1990; U.S. Pat. No. 4,999,632, issued Mar. 12, 1991; U.S. Pat. No. 4,999,582, issued Mar. 12, 1991; U.S. Pat. No. 5,243,516, issued Sep. 7, 1993; U.S. Pat. No. 5,352,351, issued Oct. 4, 1994; U.S. Pat. No. 5,366,609, issued Nov. 22, 1994; White et al., U.S. Pat. No. 5,405,511, issued Apr. 11, 1995; and White et al., U.S. Pat.

No. 5,438,271, issued Aug. 1, 1995, the disclosures of each of which are expressly hereby incorporated by reference.

[0042] Many fluid samples may be analyzed. For example, human body fluids such as whole blood, plasma, sera, lymph, bile, urine, semen, cerebrospinal fluid, spinal fluid, lacrimal fluid and stool specimens as well as other biological fluids readily apparent to one skilled in the art may be measured. Fluid preparations of tissues can also be assayed, along with foods, fermentation products and environmental substances, which potentially contain environmental contaminants. Preferably, whole blood is assayed with this invention.

[0043] To manufacture biosensor **10** a roll of metallized electrode support material is fed through guide rolls into an ablation/washing and drying station. A laser system capable of ablating support **12** is known to those of ordinary skill in the art. Non-limiting examples of which include excimer lasers, with the pattern of ablation controlled by mirrors, lenses, and masks. A non-limiting example of such a custom fit system is the LPX-300 or LPX-200 both commercially available from LPKF Laser Electronic GmbH, of Garbsen, Germany.

[0044] In the laser ablation station, the metallic layer of the metallized film is ablated in a pre-determined pattern, to form a ribbon of isolated electrode sets on the electrode support material, code patterns, and a recess in the film adjacent to each electrode array. To ablate electrodes **14**, **16**, recess **35**, and code patterns **40** in 50 nm thick gold conductor **13**, 90 mJ/cm² energy is applied. It is appreciated, however, that the amount of energy required may vary from material to material, metal to metal, or thickness to thickness. The ribbon is then passed through more guide rolls, with a tension loop and through an optional inspection system where both optical and electrical inspection can be made. The system is used for quality control in order to check for defects.

[0045] Upon leaving the laser ablation station, the metallized film is fed into a reagent dispensing station. Reagents that have been compounded are fed into a dispensing station where it is applied in a liquid form to the center of respective the array **34**. Reagent application techniques are well known to one of ordinary skill in the art as described in U.S. Pat. No. 5,762,770, the disclosure of which is expressly incorporated herein by reference. It is appreciated that reagents may be applied to the array **34** in a liquid or other form and dried or semi-dried onto the array **34** in accordance with this disclosure.

[0046] In a separate process, a double-sided pressure-sensitive film with dual release liners is fed into a window punch unit where notches are formed. The film is then fed into a lamination & kiss-cutting station. At the same time, a roll of cover substrate material is fed over a guide roll into the lamination & kiss-cutting station, where the release liner is removed from the upper surface **44** and rewound into a roll. The upper surface **33** of the spacer substrate material is applied to the cover substrate material. Next, the film is kiss cut and a portion of the cover substrate material is removed, leaving behind the cover substrate material coupled to the spacer substrate material, extending across a portion of the notch.

[0047] The cover material/spacer substrate subassembly is fed into a sensor lamination & cut/pack station. The reagent-

coated electrode-support substrate material is fed from the dispensing station into the sensor lamination & cut/pack station as well. The remaining release liner is removed from the spacer substrate and the spacer substrate is positioned on the electrode-support substrate material so that at least a portion of the electrode array **36** is aligned with the notch **52**. Next, the resulting assembled material is cut to form individual biosensors **10**, which are sorted and packed into vials, each closed with a stopper, to give packaged biosensor strips.

[0048] In use, the meter is turned on and the biosensor is inserted into the meter. It is appreciated that the user may turn on the meter, or it may turn on automatically upon insertion of the biosensor. The LED emits a light that is directed through a lens towards the code pattern of the biosensor. The light is reflected off of the code pattern, through the lens, and toward the photodiode. The photodiode measures the intensity of the light that is reflected back from the code pattern and generates a corresponding voltage waveform. A decoder deciphers this waveform and translates it into a reading of the code pattern. It is appreciated that many commercially available optical readers may be used in accordance with the present invention. Preferably, the optical reader will be custom fit reader.

[0049] In use, a user of biosensor **10** places a finger having a blood collection incision against the recess **35** in the notch **52**. Capillary forces pull a liquid blood sample flowing from the incision through the capillary channel **60** across the reagent **62** and the array **34**. The liquid blood sample dissolves the reagent **62** and engages the array **34** where the electrochemical reaction takes place.

[0050] In use for example, after the reaction is complete, a power source (e.g., a battery) applies a potential difference between the electrodes **14**, **16** respectively. When the potential difference is applied, the amount of oxidized form of the mediator at the reference electrode and the potential difference must be sufficient to cause diffusion-limited electro-oxidation of the reduced form of the mediator at the surface of the working electrode. A current measuring meter (not shown) measures the diffusion-limited current generated by the oxidation of the reduced form of the mediator at the surface of the working electrode.

[0051] The measured current may be accurately correlated to the concentration of the analyte in sample when the following requirements are satisfied:

[0052] 1. The rate of oxidation of the reduced form of the mediator is governed by the rate of diffusion of the reduced form of the mediator to the surface of the working electrode.

[0053] 2. The current produced is limited by the oxidation of reduced form of the mediator at the surface of the working electrode.

[0054] The processes and products described above include disposable biosensor **10** especially for use in diagnostic devices. Also included, however, are electrochemical sensors for non-diagnostic uses, such as measuring an analyte in any biological, environmental, or other sample. As discussed above, biosensor **10** can be manufactured in a variety of shapes and sizes and be used to perform a variety of assays, non-limiting examples of which include current, charge, impedance conductance, potential or other electrochemical indicative property of the sample applied to biosensor.

[0055] In accordance with another embodiment of the present invention, biosensor **110** is illustrated in FIG. 5.

Biosensor **110** is formed in a similar manner to biosensor **10** except that biosensor **110** includes a code pattern **140**. Code pattern **140** includes nine isolated pads **160**. It is appreciated that the number of pads can be greater or fewer than nine in accordance with this disclosure. Each pad **160** is separated by from the surrounding electrical conductor by a gap **170**.

[0056] Code pattern **140** is used once biosensor **110** is attached to a meter circuit board (not shown) that includes a connector. Generally, the connector will include two contacts per possible pad location on biosensor **110**. Code pattern **140** of the present invention enables the meter to check continuity at each pad **160** location or determine that a pad does not exist in a pre-determined location. If a pad **160** is present, the meter will recognize the presence of a pad **160** by a continuity check. One of ordinary skill in the art will be well aware of methods suitable for performing a continuity check.

[0057] Code pattern **140** is formed from the electrical conductor by laser ablation using techniques as described above with reference to electrodes **14**, **16**, shown for example in FIG. 1. Specifically, removing the electrical conductor in a pre-defined pattern to expose the first surface of the support substrate **12** creates the code pattern **140**. Code pattern **140** can also be coated with a second electrical conductor (not shown) to modify the electrical resistivity of the pattern **140**. While pattern **140** illustratively includes nine spaced-apart generally square-shaped pads, it is appreciated that the pattern **140** can take on any number of shapes and patterns in accordance with this disclosure. In addition, it is appreciated that the pattern **140** can be read optically or electrically in accordance with this disclosure.

[0058] In use, when the user inserts biosensor **110** into the meter (not shown), the biosensor **110** makes contact to the connector and the electronics of the meter inquire as to how many pads **160** are showing continuity. Predetermined lot information may be stored in a memory unit of the meter. It is appreciated that the memory unit may also store a variety of patient information including previous meter readings. This memory unit is formed with memory components, a non-limiting example of which is known as RAM, which is well known in the prior art. The results of the continuity query may be used to set the appropriate code information in the meter, which enables the meter to eliminate chemistry or reagent variation.

[0059] In accordance with another embodiment of the present invention, biosensor **210** is illustrated in FIG. 6. Biosensor **210** is formed in a similar manner to biosensor **10**, except that biosensor **210** includes a code pattern **240**. Code pattern **240** includes nine pads **260** that are in communication with one another. It is appreciated that the number of pads can vary in accordance with this disclosure. Each pad **260** is separated from the surrounding electrical conductor by gaps **270**.

[0060] Code pattern **240** is formed from the electrical conductor by laser ablation using techniques as described above with reference to electrodes **14**, **16**, shown for example in FIG. 1. Specifically, removing the electrical conductor in a pre-defined pattern to expose the first surface of the support substrate **12** creates the code pattern **240**. Code pattern **240** can also be coated with a second electrical conductor (not shown) to modify the electrical resistivity of the pattern **240**.

[0061] While pattern **240** illustratively includes nine generally square-shaped pads that are interconnected, it is

appreciated that the pattern **240** can take on any number of shapes and patterns in accordance with this disclosure, which would give various resistance levels. These differing resistance levels can be correlated to a reagent lot. For example, the pattern **240** can be varied by disconnecting the internal links between the pads **260**. This disconnection can be done, for example, by a laser. By changing the number of interconnected pads, the resistance of the remaining interconnected pads **260** will be different. In addition, it is appreciated that the pattern **240** can be read optically or electrically in accordance with this disclosure.

[0062] In use, when the user inserts biosensor **210** into the meter (not shown), the biosensor **210** makes contact to the connector and the electronics of the meter inquire as to how many pads **260** are showing continuity. Information related to this continuity is similar to that previously described with reference to biosensor **110**.

[0063] In addition, the biosensor **210** will make contact with electronics of the meter, which determines the resistance between the interconnected pads. Thus, in preferred embodiments, the meter will determine which pads exist on the biosensor **210**, and the resistance of the interconnected pads **260**. The information can be stored in the meter as described above with reference to biosensors **10** and **110**.

[0064] Although the invention has been described in detail with reference to a preferred embodiment, variations and modifications exist within the scope and spirit of the invention, on as described and defined in the following claims.

1. A biosensor comprising:

a support substrate,

an electrically conductive coating positioned on the support substrate, the coating being formed to define electrodes and a bar code pattern, wherein there is sufficient contrast between the conductive coating and the substrate such that the bar code pattern is optically discernible from the substrate in order to identify the bar code pattern, and

at least one reagent positioned on at least one electrode.

2. (canceled)

3. The biosensor of claim 1 wherein the conductive coating is gold.

4. (canceled)

5. The biosensor of claim 1 further comprising a second electrically conductive coating positioned on the code pattern.

6. The biosensor of claim 1 wherein the code pattern is electrically discernible from the substrate in order to identify the code pattern.

7. The biosensor of claim 1 wherein the code pattern includes recesses formed in the conductive coating.

8. The biosensor of claim 1 wherein the support substrate includes opposite first and second ends and the code pattern is positioned adjacent to the second end.

9. The biosensor of claim 1 further comprising a cover substrate extending across at least a portion of the electrodes.

10. The biosensor of claim 1 wherein code pattern includes pads that are spaced-apart from the surrounding electrically conductive coating.

11. The biosensor of claim 10 wherein the pads are isolated from one another.

12. The biosensor of claim 10 wherein the pads are interconnected.

13. A biosensor comprising:

a support substrate

an electrically conductive coating positioned on the support substrate, the coating being formed to define electrodes and a bar code pattern, wherein there is sufficient contrast between the conductive coating and the substrate such that the code pattern is optically discernible from the substrate in order to identify the bar code pattern, and

a cover cooperating with the support substrate to define a channel and at least a portion of the electrodes are positioned in the channel.

14. (canceled)

15. The biosensor of claim 13 further comprising a second electrically conductive coating positioned on the code pattern.

16. The biosensor of claim 13 wherein the code pattern is electrically discernible from the substrate in order to identify the bar code pattern.

17. The biosensor of claim 13 wherein the support substrate includes opposite first and second ends and the code pattern is positioned adjacent to the second end.

18. The biosensor of claim 17 wherein the electrodes cooperate to define an array positioned adjacent to the first end.

19. The biosensor of claim 18 wherein the channel extends from the first end to the array.

20. (canceled)

21. The biosensor of claim 13 wherein the conductive coating is gold.

22. The biosensor of claim 13 wherein code pattern includes pads that are spaced-apart from the surrounding electrically conductive coating.

23. The biosensor of claim 22 wherein the pads are isolated from one another.

24. The biosensor of claim 22 wherein the pads are interconnected.

25-29. (canceled)

30. A biosensor comprising:

a support substrate,

an electrically conductive coating positioned on the support substrate, the coating being formed to define electrodes and means for identifying the biosensor, wherein there is sufficient contrast between the conductive coating and the substrate such that the identifying means for identifying the biosensor is optically discernible from the substrate in order to identify the means for identify the biosensor, wherein the means for identifying the biosensor is a bar code.

31. The biosensor of claim 30 further comprising a cover that cooperates with the support substrate to define a channel and at least a portion of the electrodes are positioned in the channel.

32. (canceled)

* * * * *