



US009185435B2

(12) **United States Patent**
Shankar et al.

(10) **Patent No.:** **US 9,185,435 B2**
(45) **Date of Patent:** **Nov. 10, 2015**

(54) **METHODS AND APPARATUS TO CHARACTERIZE HOUSEHOLDS WITH MEDIA METER DATA**

(58) **Field of Classification Search**
USPC 725/9-21
See application file for complete search history.

(71) Applicant: **The Nielsen Company (US), LLC**,
Schaumburg, IL (US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,540,003 A 11/1970 Murphy
3,696,297 A 10/1972 Otero

(Continued)

FOREIGN PATENT DOCUMENTS

EP 0228242 7/1987
EP 0228458 7/1987

(Continued)

OTHER PUBLICATIONS

Applets at Kassel, "Applets and Applications," Department of Engineering Measurement, Aug. 27, 1996, retrieved from <<http://web.archive.org/web/19970802020436/http://www.uni-kassel.de/fb16/ipm/mt/java/javae.html>>, retrieved on May 24, 2006 (5 pages).

(Continued)

Primary Examiner — Yassin Alata

(74) *Attorney, Agent, or Firm* — Hanley, Flight & Zimmerman, LLC

(21) Appl. No.: **14/313,390**

(22) Filed: **Jun. 24, 2014**

(65) **Prior Publication Data**

US 2014/0380348 A1 Dec. 25, 2014

Related U.S. Application Data

(60) Provisional application No. 61/839,344, filed on Jun. 25, 2013, provisional application No. 61/844,301, filed on Jul. 9, 2013, provisional application No. 61/986,409, filed on Apr. 30, 2014, provisional application No. 62/007,535, filed on Jun. 4, 2014.


(51) **Int. Cl.**
H04H 60/32 (2008.01)
H04N 21/233 (2011.01)
(Continued)

(52) **U.S. Cl.**
CPC **H04N 21/233** (2013.01); **G06Q 30/0204** (2013.01); **H04H 60/66** (2013.01);
(Continued)

(57) **ABSTRACT**

Methods, apparatus, systems and articles of manufacture are disclosed to characterize households with media meter data. An example method includes identifying, with a processor, a target set of household categories associated with a target research geography, when a quantity of households within the target research geography representing the target set of household categories does not satisfy a threshold value, generating a first subset of categories and a second subset of categories from the target set of household categories, identifying a first set of households representing the first subset of categories from the target set of household categories and identifying an associated total number of household tuning minutes and a total number of household exposure minutes associated therewith, for each category in the second subset of categories from the target set of household categories, calculating a household tuning proportion and an exposure proportion, the household tuning proportion and exposure proportion based on the total number of household tuning minutes and exposure minutes, respectively, and calculating the panelist behavior probability based on the exposure proportion and the household tuning proportion.

23 Claims, 23 Drawing Sheets



- (51) **Int. Cl.**
- | | | | | |
|------------------------------|--|-------------|---------|----------------------|
| <i>H04N 21/258</i> | (2011.01) | 5,007,017 A | 4/1991 | Kobayashi |
| <i>H04N 21/239</i> | (2011.01) | 5,008,929 A | 4/1991 | Olsen et al. |
| <i>H04N 21/239</i> | (2011.01) | 5,019,963 A | 5/1991 | Alderson et al. |
| <i>H04N 21/25</i> | (2011.01) | 5,023,907 A | 6/1991 | Johnson et al. |
| <i>H04N 21/24</i> | (2011.01) | 5,023,929 A | 6/1991 | Call |
| <i>G06Q 30/02</i> | (2012.01) | 5,038,211 A | 8/1991 | Hallenbeck |
| <i>H04N 21/442</i> | (2011.01) | 5,038,374 A | 8/1991 | Kaufman et al. |
| <i>H04N 21/658</i> | (2011.01) | 5,042,027 A | 8/1991 | Takase et al. |
| <i>H04H 60/66</i> | (2008.01) | 5,047,867 A | 9/1991 | Strubbe et al. |
| <i>H04H 60/45</i> | (2008.01) | 5,049,873 A | 9/1991 | Robins et al. |
| | | 5,062,147 A | 10/1991 | Pickett et al. |
| | | 5,063,610 A | 11/1991 | Alwadish |
| | | 5,088,108 A | 2/1992 | Uddenfeldt et al. |
| (52) U.S. Cl. | | 5,101,402 A | 3/1992 | Chiu et al. |
| CPC | <i>H04N 21/239</i> (2013.01); <i>H04N 21/2407</i> | 5,109,350 A | 4/1992 | Henwood et al. |
| | (2013.01); <i>H04N 21/251</i> (2013.01); <i>H04N</i> | 5,140,419 A | 8/1992 | Galumbeck et al. |
| | <i>21/252</i> (2013.01); <i>H04N 21/25883</i> (2013.01); | 5,150,116 A | 9/1992 | West |
| | <i>H04N 21/44204</i> (2013.01); <i>H04N 21/6582</i> | 5,150,414 A | 9/1992 | Ng |
| | (2013.01); <i>H04H 60/45</i> (2013.01) | 5,155,591 A | 10/1992 | Wachob |
| | | 5,159,685 A | 10/1992 | Kung |
| | | 5,161,109 A | 11/1992 | Keating et al. |
| (56) References Cited | | 5,166,866 A | 11/1992 | Kim et al. |
| U.S. PATENT DOCUMENTS | | 5,181,113 A | 1/1993 | Chang |
| 3,818,458 A | 6/1974 Deese | 5,204,947 A | 4/1993 | Bernstein et al. |
| 3,906,454 A | 9/1975 Martin | 5,208,588 A | 5/1993 | Nishiyama |
| 4,058,829 A | 11/1977 Thompson | 5,210,530 A | 5/1993 | Kammerer et al. |
| 4,125,892 A | 11/1978 Fukuda et al. | 5,212,684 A | 5/1993 | MacNamee et al. |
| 4,166,290 A | 8/1979 Furtman et al. | 5,214,792 A | 5/1993 | Alwadish |
| 4,236,209 A | 11/1980 Lombardo, Jr. et al. | 5,220,522 A | 6/1993 | Wilson et al. |
| 4,258,386 A | 3/1981 Cheung | 5,220,655 A | 6/1993 | Tsutsui |
| 4,283,709 A | 8/1981 Lucero et al. | 5,223,827 A | 6/1993 | Bell et al. |
| 4,355,372 A | 10/1982 Johnson et al. | 5,223,924 A | 6/1993 | Strubbe |
| 4,356,545 A | 10/1982 West | 5,226,120 A | 7/1993 | Brown et al. |
| 4,473,824 A | 9/1984 Claytor | 5,231,593 A | 7/1993 | Notess |
| 4,516,216 A | 5/1985 Armstrong | 5,235,680 A | 8/1993 | Bijnagte |
| 4,546,382 A | 10/1985 McKenna et al. | 5,237,677 A | 8/1993 | Hirosawa et al. |
| 4,566,030 A | 1/1986 Nickerson et al. | 5,237,681 A | 8/1993 | Kagan et al. |
| 4,602,279 A | 7/1986 Freeman | 5,237,684 A | 8/1993 | Record et al. |
| 4,603,232 A | 7/1986 Kurland et al. | 5,239,540 A | 8/1993 | Rovira et al. |
| 4,658,290 A | 4/1987 McKenna et al. | 5,241,625 A | 8/1993 | Epard et al. |
| 4,677,552 A | 6/1987 Sibley, Jr. | 5,241,671 A | 8/1993 | Reed et al. |
| 4,695,880 A | 9/1987 Johnson et al. | 5,245,429 A | 9/1993 | Virginio et al. |
| 4,700,378 A | 10/1987 Brown | 5,247,517 A | 9/1993 | Ross et al. |
| 4,706,121 A | 11/1987 Young | 5,247,575 A | 9/1993 | Sprague et al. |
| 4,713,791 A | 12/1987 Saluski | 5,247,697 A | 9/1993 | Ban |
| 4,718,025 A | 1/1988 Minor et al. | 5,249,260 A | 9/1993 | Nigawara et al. |
| 4,725,886 A | 2/1988 Galumbeck et al. | 5,251,324 A | 10/1993 | McMullan, Jr. |
| 4,740,912 A | 4/1988 Whitaker | 5,253,346 A | 10/1993 | Okabayashi et al. |
| 4,745,549 A | 5/1988 Hashimoto | 5,260,878 A | 11/1993 | Luppy |
| 4,745,559 A | 5/1988 Willis et al. | 5,262,860 A | 11/1993 | Fitzpatrick et al. |
| 4,751,578 A | 6/1988 Reiter et al. | 5,267,314 A | 11/1993 | Stambler |
| 4,757,456 A | 7/1988 Benghiat | 5,267,351 A | 11/1993 | Reber et al. |
| 4,774,658 A | 9/1988 Lewin | 5,276,458 A | 1/1994 | Sawdon |
| 4,783,648 A | 11/1988 Homma et al. | 5,276,789 A | 1/1994 | Besaw et al. |
| 4,792,921 A | 12/1988 Corwin | 5,281,962 A | 1/1994 | Vanden Heuvel et al. |
| 4,817,080 A | 3/1989 Soha | 5,283,639 A | 2/1994 | Esch et al. |
| 4,823,290 A | 4/1989 Fasack et al. | 5,287,363 A | 2/1994 | Wolf et al. |
| 4,831,582 A | 5/1989 Miller et al. | 5,297,249 A | 3/1994 | Bernstein et al. |
| 4,845,658 A | 7/1989 Gifford | 5,299,115 A | 3/1994 | Fields et al. |
| 4,849,879 A | 7/1989 Chinnaswamy et al. | 5,301,350 A | 4/1994 | Rogan et al. |
| 4,868,866 A | 9/1989 Williams, Jr. | 5,309,243 A | 5/1994 | Tsai |
| 4,887,308 A | 12/1989 Dutton | 5,315,093 A | 5/1994 | Stewart |
| 4,907,188 A | 3/1990 Suzuki et al. | 5,315,580 A | 5/1994 | Phaal |
| 4,912,466 A | 3/1990 Call | 5,317,140 A | 5/1994 | Dunthorn |
| 4,912,522 A | 3/1990 Oates et al. | 5,321,831 A | 6/1994 | Hirose |
| 4,924,488 A | 5/1990 Kosich | 5,321,838 A | 6/1994 | Hensley et al. |
| 4,930,011 A | 5/1990 Kiewit | 5,327,237 A | 7/1994 | Gerdes et al. |
| 4,935,870 A | 6/1990 Burk, Jr. et al. | 5,327,554 A | 7/1994 | Palazzi, III et al. |
| 4,954,699 A | 9/1990 Coffey et al. | 5,331,544 A | 7/1994 | Lu et al. |
| 4,958,284 A | 9/1990 Bishop et al. | 5,333,302 A | 7/1994 | Hensley et al. |
| 4,961,132 A | 10/1990 Uehara | 5,339,239 A | 8/1994 | Manabe et al. |
| 4,972,367 A | 11/1990 Burke | 5,339,412 A | 8/1994 | Fueki |
| 4,972,504 A | 11/1990 Daniel, Jr. et al. | 5,347,632 A | 9/1994 | Filepp et al. |
| 4,977,455 A | 12/1990 Young | 5,349,662 A | 9/1994 | Johnson et al. |
| 4,977,594 A | 12/1990 Shear | 5,351,278 A | 9/1994 | Koshishiba et al. |
| 4,989,230 A | 1/1991 Gillig et al. | 5,351,293 A | 9/1994 | Michener et al. |
| 5,006,978 A | 4/1991 Neches | 5,355,327 A | 10/1994 | Stent et al. |
| | | 5,355,484 A | 10/1994 | Record et al. |
| | | 5,359,367 A | 10/1994 | Stockill |

(56)

References Cited

U.S. PATENT DOCUMENTS

5,361,359	A	11/1994	Tajalli et al.	5,878,224	A	3/1999	Smith
5,367,677	A	11/1994	Stanfill	5,878,384	A	3/1999	Johnson et al.
5,371,846	A	12/1994	Bates	5,881,360	A	3/1999	Fong
5,374,951	A	12/1994	Welsh	5,892,917	A	4/1999	Myerson
5,375,070	A	12/1994	Hershey et al.	5,926,168	A	7/1999	Fan
5,379,380	A	1/1995	Mori et al.	5,931,912	A	8/1999	Wu et al.
5,388,211	A	2/1995	Hornbuckle	5,933,811	A	8/1999	Angles et al.
5,388,252	A	2/1995	Dreste et al.	5,935,207	A	8/1999	Logue et al.
5,388,258	A	2/1995	Larsson et al.	5,936,541	A	8/1999	Stambler
5,390,281	A	2/1995	Luciw et al.	5,948,061	A	9/1999	Merriman et al.
5,398,336	A	3/1995	Tantry et al.	5,951,643	A	9/1999	Shelton et al.
5,406,569	A	4/1995	Isozaki	5,956,483	A	9/1999	Grate et al.
5,408,607	A	4/1995	Nishikawa et al.	5,958,010	A	9/1999	Agarwal et al.
5,410,598	A	4/1995	Shear	5,963,914	A	10/1999	Skinner et al.
5,412,778	A	5/1995	Andres	5,964,839	A	10/1999	Johnson et al.
5,414,809	A	5/1995	Hogan et al.	5,974,148	A	10/1999	Stambler
5,418,728	A	5/1995	Yada	5,974,299	A	10/1999	Massetti
5,461,708	A	10/1995	Kahn	5,977,964	A	11/1999	Williams et al.
5,481,294	A	1/1996	Thomas et al.	5,982,917	A	11/1999	Clarke et al.
5,483,658	A	1/1996	Grube et al.	5,986,653	A	11/1999	Phathayakorn et al.
5,485,897	A	1/1996	Matsumoto et al.	5,991,735	A	11/1999	Gerace
5,491,820	A	2/1996	Belove et al.	5,999,178	A	12/1999	Hwang et al.
5,495,282	A	2/1996	Mostafa et al.	6,005,597	A	12/1999	Barrett et al.
5,495,581	A	2/1996	Tsai	6,006,260	A	12/1999	Barrick, Jr. et al.
5,499,340	A	3/1996	Barritz	6,014,638	A	1/2000	Burge et al.
5,524,073	A	6/1996	Stambler	6,018,619	A	1/2000	Allard et al.
5,550,928	A	8/1996	Lu et al.	6,049,695	A	4/2000	Cottam
5,555,303	A	9/1996	Stambler	6,052,730	A	4/2000	Felciano et al.
5,557,333	A	9/1996	Jungo et al.	6,067,440	A	5/2000	Diefes
5,560,038	A	9/1996	Haddock	6,070,145	A	5/2000	Pinsley et al.
5,568,471	A	10/1996	Hershey et al.	6,078,324	A	6/2000	Phathayakorn et al.
5,572,643	A	11/1996	Judson	6,108,637	A	8/2000	Blumenau
5,594,911	A	1/1997	Cruz et al.	6,112,238	A	8/2000	Boyd et al.
5,594,934	A	1/1997	Lu et al.	6,112,240	A	8/2000	Pogue et al.
5,600,364	A	2/1997	Hendricks et al.	6,115,608	A	9/2000	Duran et al.
5,604,867	A	2/1997	Harwood	6,115,742	A	9/2000	Franklin et al.
5,608,445	A	3/1997	Mischler	6,119,098	A	9/2000	Guyot et al.
5,615,264	A	3/1997	Kazmierczak et al.	6,138,155	A	10/2000	Davis et al.
5,623,652	A	4/1997	Vora et al.	6,167,358	A	12/2000	Othmer et al.
5,634,100	A	5/1997	Capps	6,173,311	B1	1/2001	Hassett et al.
5,646,998	A	7/1997	Stambler	6,185,586	B1	2/2001	Judson
5,648,965	A	7/1997	Thadani et al.	6,216,129	B1	4/2001	Eldering
5,671,283	A	9/1997	Michener et al.	6,219,786	B1	4/2001	Cunningham et al.
5,673,382	A	9/1997	Cannon et al.	6,226,677	B1	5/2001	Slemmer
5,696,702	A	12/1997	Skinner et al.	6,237,033	B1	5/2001	Doeberl et al.
5,706,502	A	1/1998	Foley et al.	6,250,930	B1	6/2001	Mintz
5,708,709	A	1/1998	Rose	6,256,739	B1	7/2001	Skopp et al.
5,708,780	A	1/1998	Levergood et al.	6,264,560	B1	7/2001	Goldberg et al.
5,710,915	A	1/1998	McElhiney	6,275,854	B1	8/2001	Himmel et al.
5,710,918	A	1/1998	Lagarde et al.	6,278,966	B1	8/2001	Howard et al.
5,712,979	A	1/1998	Graber et al.	6,279,036	B1	8/2001	Himmel et al.
5,715,453	A	2/1998	Stewart	6,279,112	B1	8/2001	O'Toole, Jr. et al.
5,717,860	A	2/1998	Graber et al.	6,286,036	B1	9/2001	Rhoads
5,717,923	A	2/1998	Dedrick	6,298,348	B1	10/2001	Eldering
5,724,521	A	3/1998	Dedrick	6,317,787	B1	11/2001	Boyd et al.
5,732,218	A	3/1998	Bland et al.	6,324,546	B1	11/2001	Ka et al.
5,737,619	A	4/1998	Judson	6,360,261	B1	3/2002	Boyd et al.
5,740,549	A	4/1998	Reilly et al.	6,381,632	B1	4/2002	Lowell
5,781,893	A	7/1998	Felthauser et al.	6,393,479	B1	5/2002	Glommen et al.
5,787,253	A	7/1998	McCreery et al.	6,397,359	B1	5/2002	Chandra et al.
5,793,302	A	8/1998	Stambler	6,408,335	B1	6/2002	Schwaller et al.
5,796,952	A	8/1998	Davis et al.	6,418,470	B2	7/2002	Blumenau
5,799,292	A	8/1998	Hekmatpour	6,434,532	B2	8/2002	Goldband et al.
5,801,747	A	9/1998	Bedard	6,446,261	B1	9/2002	Rosser
5,819,156	A	10/1998	Belmont	6,449,604	B1	9/2002	Hansen et al.
5,819,285	A	10/1998	Damico et al.	6,457,025	B2	9/2002	Judson
5,823,879	A	10/1998	Goldberg et al.	6,466,970	B1	10/2002	Lee et al.
5,829,001	A	10/1998	Li et al.	6,473,407	B1	10/2002	Ditmer et al.
5,835,923	A	11/1998	Shibata et al.	6,483,813	B1	11/2002	Blencowe
5,838,919	A	11/1998	Schwaller et al.	6,484,316	B1	11/2002	Lindberg
5,841,433	A	11/1998	Chaney	6,569,095	B2	5/2003	Eggers
5,848,396	A	12/1998	Gerace	6,601,100	B2	7/2003	Lee et al.
5,857,190	A	1/1999	Brown	6,606,745	B2	8/2003	Maggio
5,870,546	A	2/1999	Kirsch	6,609,239	B1	8/2003	Xavier
5,872,588	A	2/1999	Aras et al.	6,621,881	B2	9/2003	Srinivasan
				6,625,648	B1	9/2003	Schwaller et al.
				6,662,195	B1	12/2003	Langseth et al.
				6,662,227	B2	12/2003	Boyd et al.
				6,671,715	B1	12/2003	Langseth et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,712,702	B2	3/2004	Goldberg et al.
6,719,660	B2	4/2004	Palazzolo
6,735,775	B1	5/2004	Massetti
6,766,370	B2	7/2004	Glommen et al.
6,807,558	B1	10/2004	Hassett et al.
6,842,782	B1	1/2005	Malik et al.
6,859,833	B2	2/2005	Kirsch et al.
6,993,590	B1	1/2006	Gauthier et al.
7,017,143	B1	3/2006	Andrew et al.
7,139,723	B2	11/2006	Conkwright et al.
7,146,329	B2	12/2006	Conkwright et al.
7,150,030	B1	12/2006	Eldering et al.
7,181,412	B1	2/2007	Fulgoni et al.
7,216,149	B1	5/2007	Briscoe et al.
7,222,071	B2	5/2007	Neuhauser et al.
7,260,823	B2	8/2007	Schlack et al.
7,260,837	B2	8/2007	Abraham et al.
7,376,722	B1	5/2008	Sim et al.
7,451,151	B2	11/2008	Horvitz et al.
7,483,835	B2	1/2009	Neuhauser et al.
7,493,655	B2	2/2009	Brown
7,757,250	B1	7/2010	Horvitz et al.
7,953,791	B2	5/2011	Or Sim et al.
7,953,839	B2	5/2011	Sim et al.
8,046,797	B2	10/2011	Bentolila et al.
8,112,511	B2	2/2012	Sim et al.
8,311,888	B2	11/2012	Ramer et al.
2001/0049620	A1	12/2001	Blasko
2002/0040394	A1	4/2002	Shapira
2002/0040395	A1	4/2002	Davis et al.
2002/0049762	A1	4/2002	Shah et al.
2002/0072966	A1	6/2002	Eldering et al.
2002/0077787	A1	6/2002	Rappaport et al.
2002/0078191	A1	6/2002	Lorenz
2002/0099812	A1	7/2002	Davis et al.
2002/0099818	A1	7/2002	Russell et al.
2002/0099819	A1	7/2002	Hattori et al.
2002/0103664	A1	8/2002	Olsson et al.
2002/0112048	A1	8/2002	Gruyer et al.
2002/0124074	A1	9/2002	Levy et al.
2002/0150054	A1	10/2002	Sohraby et al.
2002/0161673	A1	10/2002	Lee et al.
2003/0018969	A1	1/2003	Humpleman et al.
2003/0046303	A1	3/2003	Chen et al.
2003/0046385	A1	3/2003	Vincent
2003/0062223	A1	4/2003	Coyle et al.
2003/0110485	A1	6/2003	Lu et al.
2003/0144868	A1	7/2003	MacIntyre et al.
2003/0149975	A1	8/2003	Eldering et al.
2003/0163563	A1	8/2003	Bean
2003/0182387	A1	9/2003	Geshwind
2003/0187677	A1	10/2003	Malireddy et al.
2003/0208578	A1	11/2003	Taraborelli
2003/0231203	A1	12/2003	Gallella
2004/0024717	A1	2/2004	Sneeringer
2004/0221033	A1	11/2004	Davis et al.
2005/0114511	A1	5/2005	Davis et al.
2006/0074769	A1	4/2006	Looney et al.
2006/0075421	A1	4/2006	Roberts et al.
2007/0011039	A1	1/2007	Oddo
2007/0022032	A1	1/2007	Anderson et al.
2007/0174295	A1	7/2007	Abraham et al.
2007/0276940	A1	11/2007	Abraham et al.
2008/0120650	A1	5/2008	Orihara et al.
2008/0140479	A1	6/2008	Mello et al.
2008/0256235	A1	10/2008	Or Sim et al.
2008/0263200	A1	10/2008	Or Sim et al.
2008/0300965	A1*	12/2008	Doe 705/10
2009/0112703	A1	4/2009	Brown
2010/0228855	A1	9/2010	Sim et al.
2011/0004682	A1	1/2011	Honnold et al.
2011/0208860	A1	8/2011	Sim et al.
2011/0258049	A1	10/2011	Ramer et al.
2012/0254911	A1	10/2012	Doe

FOREIGN PATENT DOCUMENTS

EP	0388658	9/1990
EP	0451384	10/1991
EP	0632382	1/1995
EP	0747841	12/1996
JP	2004357311	12/2004
JP	2008011365	1/2008
KR	20130008978	1/2013
WO	9826529	6/1998
WO	0111606	2/2001

OTHER PUBLICATIONS

Applet Demos, 1995-1996 (2 pages).

Arbitron Inc., "Smartplus 8.0: Keeps Getting Smarter So You Can Too," 2007, retrieved from <http://www.arbitron.com/ad_agencies/smartplus8.html>, retrieved on Sep. 21, 2007 (13 pages).

Arlitt et al., "Internet Web Servers: Workload Characterization and Performance Implications," IEEE/ACM Transactions on Networking, vol. 5, No. 5, Oct. 1997 (15 pages).

Bank, "Java Security," MIT, Dec. 8, 1995, retrieved from <<http://groups.csail.mit.edu/mac/users/jbank/javapaper/javapaper.html>>, retrieved on Apr. 30, 2015 (11 pages).

Becker, "Department of Engineering Measurement," UNI Kassel, Sep. 20, 1996 (1 page).

Beckett, "Combined Log System," Computing Laboratory, University of Kent, retrieved from <http://www.igd.fhg.de/archive/1995_www95/papers/46/comblog.html>, retrieved on May 24, 2006 (8 pages).

Berners-Lee, "WorldWideWeb: Proposal for a HyperText Project," Nov. 12, 1990 (7 pages).

Berners-Lee, "Information Management: A Proposal," CERN, Mar. 1989, May 1990, retrieved from <<http://www.w3.org/History/1989/proposal.html>>, retrieved on May 24, 2006 (14 pages).

Bertot et al., "Web Usage Statistics: Measurement Issues and Analytical Techniques," Government Information Quarterly, vol. 14, No. 4, 1997 (23 pages).

Boyan, "Anonymous Surfing, The Anonymizer Homepage," Anonymizer, Sep. 1, 1995, retrieved from <http://web.archive.org/web/19990208003332m_1/anonymizer.cs.cmu.edu:8080/>, retrieved on May 24, 2006 (1 page).

Catledge et al., "Characterizing Browsing Strategies in the World-Wide Web," School of Literature, Communication and Culture, Graphics, Visualization, & Usability Center, Georgia Institute of Technology (9 pages).

Cern, "Computer News Letter Oct.-Dec. 1991," Ref. CERN-CNL-1991-204, vol. 26, Issue No. 3, retrieved from <<http://ref.web.cern.ch/ref/CERN/CNL/1991/204/>>, retrieved on May 24, 2006 (2 pages).

Cooley et al., "Data Preparation for Mining World Wide Web Browsing Patterns," Knowledge and Information Systems, vol. 1, 1999 (27 pages).

Cooley et al., "Web Mining: Information and Pattern Discovery on the World Wide Web," Department of Computer Science, University of Minnesota, Jul. 16, 1997 (2 pages).

Cooper, "Design Considerations in Instrumenting and Monitoring Web-Based Information Retrieval Systems," Journal of the American Society for Information Science, vol. 49, No. 10, 1998 (17 pages).

Crovella et al., "Self-Similarity in World Wide Web Traffic: Evidence and Possible Causes," IEEE/ACM Transactions on Networking, vol. 5, No. 6, Dec. 1997 (25 pages).

Crovella et al., "Explaining World Wide Web Traffic Self-Similarity," Computer Science Department, Boston University, Technical Report TR-95-015, Oct. 12, 1995 (19 pages).

Dean et al. (1995) "Security Flaws in the HotJava Web Browser," Department of Computer Science, Princeton University, Nov. 3, 1995 (8 pages).

December et al., "HTML and CGI Unleashed," Sams.net Publishing, 1995 (841 pages.) (NPL in 5 parts).

E-mail Counter Logs, 1996 (33 pages).

Fielding, "wwwstat: HTTPd Logfile Analysis Software," Department of Information and Computer Science, University of California,

(56)

References Cited**OTHER PUBLICATIONS**

- Irvine, retrieved from <<http://ftp.ics.uci.edu/pub/websoft/wwwstat/>>, retrieved on May 24, 2006 (3 pages).
- Girdley et al., "Web Programming with Java," Sams.net Publishing, 1996 (499 pages) (NPL in 2 parts).
- Google Groups, "Access Counters," retrieved from <http://groups.google.com/group/comp.infosystems.www.authoring.html/browse_thread/thread/dfb1a837f29e165e/a0e0e6a131c6102d?q=access . . . > retrieved on May 24, 2006 (3 pages).
- Google Groups, "Javascript," retrieved from <http://groups.google.com/group/comp.society.privacy/browse_thread/thread/9b12496aeda7fd78/dd2ebe5f8966fd05?q=javascript&mum=1&hl=>, retrieved on May 24, 2006 (3 pages).
- Google Groups, "Javascript Counter Script," retrieved from <http://groups.google.com/group/comp.databases.oracle/browse_thread/thread/97671e385d1bac94n777a82875e328555?q=javascript+counter+sc . . . >, retrieved on May 24, 2006 (2 pages).
- Google Groups, "Javascript Exploit," retrieved from <http://groups.google.com/group/comp.sys.mac.misc/browse_thread/thread/f9285c7d4e4354cd/eb94d50669840159?q=javascript+exploit&mum=1>, retrieved on May 24, 2006 (3 pages).
- Google Groups, "Garrett Casey," retrieved from <Google Groups: comp.infosystems.www.authoring.cgi> (2 pages).
- Google Groups, "Xferstats," retrieved from <http://groups.google.com/group/alt.sources/browse_thread/thread/c9e60d434be3ad86/0a180fb213f27e2b?q=xferstats&mum=199&hl=en>, retrieved on May 24, 2006 (10 pages).
- Google Groups, "Cgi Hit Counter," retrieved from <http://groups.google.com/group/comp.infosystems.www.users/browse_thread/thread/390de231bb3f0097/64bdc80086f124b?q=cgi+hit+counter> retrieved on May 24, 2006 (2 pages).
- Gotta et al., "Performance Evaluation of Web Applications," Proceeding of the Computer Measurement Group International Conference, 1998 (13 pages).
- Grobe, "An Early History of Lynx: Multidimensional Collaboration," Academic Computing Services, University of Kansas, Apr. 10, 1997, retrieved from <<http://people.cc.ku.edu/~grobe/early-lynx.html>>, retrieved on May 24, 2006 (8 pages).
- Gundavaram, "CGI Programming on the World Wide Web," o'Reilly & Associates, Inc., 1996 (455 pages) (NPL in 2 parts).
- Hallam-Baker et al., "Extended Log File Format," W3C, Working Draft WD-logfile-960323, retrieved from <<http://www.w3.org/TR/WD-logfile.html>>, retrieved on May 24, 2006 (6 pages).
- Hello Net! Counter (1 page).
- Holgermetzger, "A Netscape Timeline," Mar. 1993 through Mar. 17, 2006, retrieved from <http://www.holgermetzger.de/Netscape_History.html>, retrieved on May 24, 2006 (4 pages).
- Houston, "A Vision of Advertising Technology—How It Will Work and Why Advertisers Must Involve Themselves in the Process," Modern Media, Aug. 1994, retrieved from <<http://www.web.archive.org/web/19961111095749/www.modernmedia.com/clippings/articles/sm> . . . >, retrieved on Jun. 8, 2005 (6 pages).
- W3, "Logging Control in W3C httpd," w3.org, Jul. 1995, retrieved from <<http://www.w3.org/Daemon/User/Config/Logging.html>>, retrieved on May 24, 2006 (3 pages).
- Intellectual Property Office of the United Kingdom, "Examination Report," issued in connection with United Kingdom Patent Application No. GB0920943.8, mailed Nov. 10, 2010 (6 pages).
- Intellectual Property Office of the United Kingdom, "Examination Report," issued in connection with United Kingdom Patent Application No. GB0920943.8, mailed Apr. 11, 2011 (5 pages).
- International Bureau, "International Preliminary Report on Patentability," issued in connection with International Patent Application No. PCT/US2008/059874, mailed Dec. 10, 2009 (7 pages).
- International Searching Authority, "International Search Report," issued in connection with International Patent Application No. PCT/US2008/059874, mailed Mar. 2, 2009 (3 pages).
- International Searching Authority, "Written Opinion," issued in connection with International Patent Application No. PCT/US2008/059874, mailed Mar. 2, 2009 (5 pages).
- International Preliminary Examining Authority, "International Preliminary Examination Report," issued in connection with International Patent Application No. PCT/AU00/00937, issued Nov. 2, 2001 (3 pages).
- IP Australia, "Examiner's First Report," issued in connection with Australian Patent Application No. 2008260397, mailed Nov. 17, 2010 (2 pages).
- IP Australia, "Notice of Acceptance," issued in connection with Australian Patent Application No. 2008260397, mailed Aug. 7, 2012 (2 pages).
- Japan Patent Office, "Notice of Reasons for Rejection," issued in connection with Japanese Patent Application No. 2001-516087, mailed May 18, 2010 (14 pages).
- Japan Patent Office, "Notice of Reasons for Rejection," issued in connection with Japanese Patent Application No. 2001-516087, mailed Jan. 25, 2011 (8 pages).
- Lamers, "WebThreads, LLC of Vienna, VA, USA is Pleased to Announce WebThreads™ 1.0.1 Website Interactivity and Visitor Tracking Solution," Oct. 8, 1996 (5 pages).
- Javaworld, JavaWorld: IDG's Magazine for the Java Community, vol. 1, Issue 1, retrieved from <www.javaworld.com>. Mar. 8, 1996 (1 page).
- Javaworld, JavaWorld: IDG's Magazine for the Java Community, vol. 1, Issue 2, retrieved from <www.javaworld.com>. Apr. 1, 1996 (1 page).
- Javaworld, JavaWorld Editorial Calendar, Feb. 26, 1996 (1 page).
- Johnson, "Implementation Guide, HBX On-Demand Web Analytics," WebSideStory, Inc., 2006 (12 pages).
- Kamba, "Personalized Online Newspaper," NEC, vol. 49, No. 7, 1996 (Abstract in English Only) (6 pages).
- Kent et al., "Official Netscape JavaScript Book," 1996 (508 pages) (NPL in 2 parts).
- Kiesler et al., "Homenet: A Field Trial of Residential Internet Services," Carnegie Mellon University, Apr. 1995, retrieved from <<http://homenet.hcii.cs.cmu.edu/progress/reportl.html>> (12 pages).
- Kraut et al., "Homenet: A Field Trial of Residential Internet Services," Carnegie Mellon University, Apr. 1995, retrieved from <http://www.acm.org/sigchi/chi96/proceedings/papers/Kraut/rek_txt.htm> (14 pages).
- Levine, "Computer Privacy Digest V8#024" Computer Privacy Digest Sun, vol. 8, Issue No. 024, Mar. 17, 1996, retrieved from <http://web.archive.org/web/20000829051834/itu.rdg.ac.uk/misc/Mailing_Lists/cpd/00000002.htm>, retrieved on May 24, 2006 (19 pages).
- Loverso, "Netscape Navigator 2.0 Exposes User's Browsing History," The Risks Digest, vol. 7, Issue 79, Feb. 1996, retrieved from <<http://catless.ncl.ac.uk/Risks/17.79.html>>, retrieved on Dec. 11, 2005 (2 pages).
- Lynnworth, "Tracking Home Page Hits," Dr. Dobbs Journal, Dec. 1, 1995, retrieved from <<http://www.drdoobs.com/article/print?articleId=184409739&siteSectionName=web-development>>, retrieved on Apr. 30, 2015 (7 pages).
- Mayer-Schonberger, "The Internet and Privacy Legislation: Cookies for a Treat?" West Virginia University, retrieved from <<http://web.archive.org/web/19990203034203/www.wvjolt.wvu.edu/wvjolt/current/issue1/articles/mayer/> . . . >, retrieved on May 24, 2006 (7 pages).
- McGraw et al., "Untangling the Woven Web: Testing Web-based Software," Reliable Software Technologies Corporation, Apr. 1, 1996 (9 pages).
- Consoli, "Nielsen Unveils National TV/Internet Fusion," Mediaweek, Nov. 1, 2006, retrieved from <<http://mediaweek.print-this.clickability.com/pt/cpt?action=cpt&title=> . . . >, retrieved on Sep. 21, 2007 (2 pages).
- Microsoft Corporation, "Screen Shots of Windows NT 3.1," retrieved from <<http://www.cs.umd.edu/hcil/museum/systems/winnt31src.html>>, retrieved on Jun. 7, 2005 (4 pages).
- Montgomery, "Using Clickstream Data to Predict WWW Usage," Carnegie Mellon University, Aug. 1999 (27 pages).

(56)

References Cited**OTHER PUBLICATIONS**

Mulvenna et al., "The 'Soft-Push': Mining Internet Data for Marketing Intelligence," Working Conference: Electronic Commerce in the Framework of Mediterranean Countries Development, Ioannina, Greece (12 pages).

National Defense University, "Information Operations Timeline," retrieved from <http://www.jfsc.ndu.edu/schools_programs/jciws/iw/io_timeline.asp>, retrieved on May 24, 2006 (9 pages).

Naughton, "The JAVA Handbook," 1996 (446 pages) (NPL in 2 parts).

Net.Genesis et al., "Build a Web Site: The Programmer's Guide to Creating, Building, and Maintaining Web Presence," 1995 (721 pages) (NPL in 3 parts).

Netscape Communication and Sun Microsystems, "Sun and Netscape Announce JavaScript," Dec. 4, 1995 (8 pages).

Nardone, "The Modem Media Internet Reach and Involvement Scale (IRIS)," Modem Media, Feb. 1995, retrieved from <<http://web.archive.org/web/19961111095728/www.modemmedia.com/clippings/articles/iris>>, retrieved on Jun. 8, 2005 (3 pages).

Naor et al., "Secure Accounting and Auditing on the Web," Computer Networks and ISDN Systems, vol. 30, 1998 (10 pages).

Nielsen, "Classic HTTP Documents," W3C, May 14, 1998, retrieved from <<http://www.w3.org/Protocols/Classic.html>>, retrieved on May 24, 2006 (1 page).

O'Connell, "A New Pitch: Advertising on the World Wide Web is a Whole New Ball Game," Modem Media, May 1995, retrieved from <<http://web.archive.org/web/19961111095738/www.modemmedia.com/clippings/articles/ne...>>, retrieved on Jun. 8, 2005 (8 pages).

Older Counter.html history, "Older History of Changes," 1995-1996, retrieved from <<http://www.ualberta.ca/GEO/Counter.History.html>>, retrieved on May 24, 2006, (8 pages).

Ostermann, "Tcptrace Homepage," retrieved from <<http://www.tcptrace.org>>, retrieved on Jun. 12, 2006 (1 page).

Padmanabhan et al., "Analysis of Web Site Usage Data: How Much Can We Learn About the Consumer from Web Logfiles?," Center for Digital Economy Research, Stern School of Business, Working Paper Stern #IS-96-18, Dec. 1996 (33 pages).

Pierrakos et al., "Web Usage Mining as a Tool for Personalization: A Survey," User Modeling and User-Adapted Interaction, vol. 13, 2003 (62 pages).

Powell, "Tomorrow's Heavyweight?" Network World, vol. 15, No. 49, Dec. 7, 1998 (1 page).

Internet Profiles Corporation, "I/PRO is First to Develop a Solution for Measuring Java Applets," Apr. 12, 1996 (2 pages).

Realnetworks Inc., "Real System 5.0 Security Features Whitepaper," 1997 (10 pages).

Realnetworks Inc., "RealServer Administration Guide Version 5.0," 1995-1997 (262 pages).

Rodley, "Writing Java Applets," 1996 (438 pages) (NPL in 2 parts).

Schmittlein, "Why Does the NBD Model Work?" (Abstract), Marketing Science at the University of Florida, vol. 4, No. 3, Summer 1985, retrieved from <<http://bear.cba.ufl.edu/centers/mks/abstracts/vol4/no3/schmittleinbe.>> (1 page).

Seshan et al., "SPAND: Shared Passive Network Performance Discovery," Proceedings of the USENIX Symposium on Internet Technologies and Systems, Monterey, California, Dec. 1997 (13 pages).

Shahabi et al., "Knowledge Discovery from Users Web-Page Navigation," 1997 retrieved from <<http://www.ict.griffith.edu.au/~vlad/teaching/kdd.d/readings.d/shahabi97knowledge.pdf>> (11 pages).

Siochi et al., "Computer Analysis of User Interfaces Based on Repetition in Transcripts of User Sessions," ACM Transactions on Information Systems, vol. 9, No. 4, Oct. 1991 (27 pages).

Staten, "Navigator Tricks Raise Concerns (Privacy Concerns Raised by the Addition of JavaScript and HTTP Cookie to Netscape Communications' Navigator 3.0 Web Browser)," MacWeek, vol. 10, No. 11, Mar. 18, 1996 retrieved from <<http://www.dialogclassic.com/main.vmgw>>, retrieved on Jun. 7, 2005 (2 pages).

The Nielsen Company (US), LLC, "Complaint for Patent Infringement," Case 2:11-cv-00168-RGD-TEM, filed with the United States

District Court for the Eastern District of Virginia Alexandria Division and transferred to the Norfolk Division on Mar. 15, 2011 (13 pages).

United States Patent and Trademark Office, "Final Office Action," issued in connection with U.S. Appl. No. 12/100,685, mailed Nov. 16, 2009 (9 pages).

United States Patent and Trademark Office, "Non-Final Office Action," issued in connection with U.S. Appl. No. 12/100,685, mailed Feb. 12, 2009 (15 pages).

United States Patent and Trademark Office, "Final Office Action," issued in connection with U.S. Appl. No. 09/763,338, mailed Jul. 12, 2007 (20 pages).

United States Patent and Trademark Office, "Non-Final Office Action," issued in connection with U.S. Appl. No. 12/100,698, mailed Jan. 20, 2010 (18 pages).

United States Patent and Trademark Office, "Non-Final Office Action," issued in connection with U.S. Appl. No. 12/100,698, mailed Sep. 25, 2009 (17 pages).

United States Patent and Trademark Office, "Non-Final Office Action," issued in connection with U.S. Appl. No. 12/780,890, mailed Oct. 1, 2010 (9 pages).

United States Patent and Trademark Office, "Non-Final Office Action," issued in connection with U.S. Appl. No. 13/098,358, mailed Jul. 27, 2011 (10 pages).

United States Patent and Trademark Office, "Non-Final Office Action," issued in connection with U.S. Appl. No. 09/763,338, mailed Nov. 21, 2006 (18 pages).

United States Patent and Trademark Office, "Notice of Allowance," issued in connection with U.S. Appl. No. 12/100,698, mailed Feb. 25, 2011 (12 pages).

United States Patent and Trademark Office, "Notice of Allowance," issued in connection with U.S. Appl. No. 12/100,698, mailed Oct. 20, 2010 (11 pages).

United States Patent and Trademark Office, "Notice of Allowance," issued in connection with U.S. Appl. No. 12/780,890, mailed Mar. 22, 2011 (12 pages).

United States Patent and Trademark Office, "Notice of Allowance," issued in connection with U.S. Appl. No. 13/098,358, mailed Dec. 13, 2011 (12 pages).

United States Patent and Trademark Office, "Notice of Allowance," issued in connection with U.S. Appl. No. 09/763,338, mailed Jan. 2, 2008 (7 pages).

United States Patent and Trademark Office, "Requirement for Restriction/Election," issued in connection with U.S. Appl. No. 09/763,338, mailed Aug. 1, 2006 (6 pages).

European Patent Office, "Office Action," issued in connection with European Patent Application No. 00949006.1, mailed Apr. 18, 2008 (7 pages).

Google Groups, "Wwwstat," retrieved from <http://groups.google.com/group/comp.infosystems.www/browse_thread/thread/784aa9c20470d342/fc0cde0742990875?q=wwwstat&mum=43...>, retrieved on May 24, 2006 (8 pages).

Google Groups, "Fwgstat," retrieved from <http://groups.google.com/group/comp.infosystems.gopher/browse_thread/thread/15dc16c0284c02d0/953bf38f2cee15ea?q=fwgstat&mum=34...>, retrieved on May 24, 2006 (3 pages).

Google Groups, "Fwgstat," retrieved from <http://groups.google.com/group/comp.infosystems.gopher/browse_thread/thread/4790232128a9157/d1534978dddf998?q=fwgstat&mum=33...>, retrieved on May 24, 2006 (10 pages).

Google Groups, "Getsites," retrieved from <http://groups.google.com/group/comp.infosystems.www/browse_thread/threada36eeb6daea735d8/0fa7adf53e51b894?q=getsites&mum=19&h...>, retrieved on May 24, 2006 (2 pages).

Google Groups, "Cgi Hit Counter," retrieved from <http://groups.google.com/group/comp.lang.perl1/browse_thread/thread/b4ef428d8c96d525/3e18b779b1dad79e?q=cgi+hit+counter&mum=74&...> retrieved on May 24, 2006 (7 pages).

Google Groups, "Wusage 1.0," retrieved from <http://groups.google.com/group/comp.infosystems.www/browse_thread/thread/a07834d8b38dbc4f/f05bf1df25d47fd3?q=wusage+1.0&mum=1...>, retrieved on May 24, 2006 (2 pages).

Google Groups, "Getstats," retrieved from <http://groups.google.com/group/comp.infosystems.www/browse_thread/thread/>

(56)

References Cited**OTHER PUBLICATIONS**

1009129delaaf6aa/ed924b219923cc7d?q=getstats&mum=1 & h1 . . . >, retrieved on May 24, 2006 (3 pages).

Ibiblio, "Ibiblio—Ten Years in the Making—Aligning the Sites," retrieved from <<http://www.ibiblio.org/history/>> , retrieved on May 24, 2006 (10 pages).

Javapage, "Java," retrieved from <[http://web.archive.org/web/20040712072256/http://www.groton.k12.ct.us/WWW/fsr/student/Spring02/W...>](http://web.archive.org/web/20040712072256/http://www.groton.k12.ct.us/WWW/fsr/student/Spring02/W...), retrieved on May 24, 2006 (4 pages).

Mobasher, "Introduction," retrieved from <<http://maya.cs.depaul.edu/~mobasher/webminer/survey/node1.html>>, Jul. 16, 1997 (2 pages).

Mobasher, "A Taxonomy of Web Mining," retrieved from <<http://maya.cs.depaul.edu/~mobasher/webminer/survey/node2.html>>, Jul. 16, 1997 (1 page).

Mobasher, "Content Mining," retrieved from <<http://maya.cs.depaul.edu/~mobasher/webminer/survey/node3.html>>, Jul. 16, 1997 (1 page).

Mobasher, "Agent-Based Approach," retrieved from <<http://maya.cs.depaul.edu/~mobasher/webminer/survey/node4.html>>, Jul. 16, 1997 (2 pages).

Mobasher, "DataBase Approach," retrieved from <<http://maya.cs.depaul.edu/~mobasher/webminer/survey/node5.html>>, Jul. 16, 1997 (2 pages).

Mobasher, "Web Usage Mining," retrieved from <<http://maya.cs.depaul.edu/~mobasher/webminer/survey/node6.html>>, Jul. 16, 1997 (2 pages).

Mobasher, "Pattern Discovery Tools," retrieved from <<http://maya.cs.depaul.edu/~mobasher/webminer/survey/node7.html>>, Jul. 16, 1997 (2 pages).

Mobasher, "Pattern Analysis Tool," retrieved from <<http://maya.cs.depaul.edu/~mobasher/webminer/survey/node8.html>>, Jul. 16, 1997 (2 pages).

Mobasher, "Pattern Discovery from Web Transactions," retrieved from <<http://maya.cs.depaul.edu/~mobasher/webminer/survey/node9.html>>, Jul. 16, 1997 (1 page).

Mobasher, "Preprocessing Tasks," retrieved from <<http://maya.cs.depaul.edu/~mobasher/webminer/survey/node10.html>>, Jul. 16, 1997 (1 page).

Mobasher, "Data Cleaning," retrieved from <<http://maya.cs.depaul.edu/~mobasher/webminer/survey/node11.html>>, Jul. 16, 1997 (1 page).

Mobasher, "Transaction Identification," retrieved from <<http://maya.cs.depaul.edu/~mobasher/webminer/survey/node12.html>>, Jul. 16, 1997 (1 page).

Mobasher, "Discovery Techniques on Web Transactions," retrieved from <<http://maya.cs.depaul.edu/~mobasher/webminer/survey/node13.html>>, Jul. 16, 1997 (1 page).

Mobasher, "Path Analysis," retrieved from <<http://maya.cs.depaul.edu/~mobasher/webminer/survey/node14.html>>, Jul. 16, 1997 (1 page).

Mobasher, "Association Rules," retrieved from <<http://maya.cs.depaul.edu/~mobasher/webminer/survey/node15.html>>, Jul. 16, 1997 (1 page).

Mobasher, "Sequential Patterns," retrieved from <<http://maya.cs.depaul.edu/~mobasher/webminer/survey/node16.html>>, Jul. 16, 1997 (1 page).

Mobasher, "Clustering and Classification," retrieved from <<http://maya.cs.depaul.edu/~mobasher/webminer/survey/node17.html>>, Jul. 16, 1997 (1 page).

Mobasher, "Analysis of Discovered Patterns," retrieved from <<http://maya.cs.depaul.edu/~mobasher/webminer/survey/node18.html>>, Jul. 16, 1997 (1 page).

Mobasher, "Visualization Techniques," retrieved from <<http://maya.cs.depaul.edu/~mobasher/webminer/survey/node19.html>>, Jul. 16, 1997 (1 page).

Mobasher, "Olap Techniques," retrieved from <<http://maya.cs.depaul.edu/~mobasher/webminer/survey/node20.html>>, Jul. 16, 1997 (1 page).

Mobasher, "Data and Knowledge Querying," retrieved from <<http://maya.cs.depaul.edu/~mobasher/webminer/survey/node21.html>>, Jul. 16, 1997 (1 page).

Mobasher, "Usability Analysis," retrieved from <<http://maya.cs.depaul.edu/~mobasher/webminer/survey/node22.html>>, Jul. 16, 1997 (1 page).

Mobasher, "Web Usage Mining Architecture," retrieved from <<http://maya.cs.depaul.edu/~mobasher/webminer/survey/node23.html>>, Jul. 16, 1997 (3 pages).

Mobasher, "Research Directions," retrieved from <<http://maya.cs.depaul.edu/~mobasher/webminer/survey/node24.html>>, Jul. 16, 1997 (1 page).

Mobasher, "Data Pre-Processing for Mining," retrieved from <<http://maya.cs.depaul.edu/~mobasher/webminer/survey/node25.html>>, Jul. 16, 1997 (1 page).

Mobasher, "The Mining Process," retrieved from <<http://maya.cs.depaul.edu/~mobasher/webminer/survey/node26.html>>, Jul. 16, 1997 (1 page).

Mobasher, "Analysis of Mined Knowledge," retrieved from <<http://maya.cs.depaul.edu/~mobasher/webminer/survey/node27.html>>, Jul. 16, 1997 (1 page).

Mobasher, "Conclusion," retrieved from <<http://maya.cs.depaul.edu/~mobasher/webminer/survey/node28.html>>, Jul. 16, 1997 (1 page).

Mobasher, "References," retrieved from <<http://maya.cs.depaul.edu/~mobasher/webminer/survey/node29.html>>, Jul. 16, 1997 (6 pages).

Mobasher, "About This Document," retrieved from <<http://maya.cs.depaul.edu/~mobasher/webminer/survey/node30.html>>, Jul. 16, 1997 (1 page).

Muquit, "WWW Homepage Access Counter and Clock!" retrieved from <<http://www.muquit.com/muquit/software/Count/Count.html>>, retrieved on May 24, 2006 (32 pages).

Thomson Jr., "Creation of the NSFnet," Commercialization of the Internet, 2000, retrieved from <<http://johnthomson.org/j561/NSFcreate-4.html>>, retrieved on May 24, 2006 (2 pages).

Thomson Jr., "The Beginning of Commercialization of the NSFnet," Commercialization of the Internet, 2000, retrieved from <<http://johnthomson.org/j561/NSFcomm-5.html>>, retrieved on May 24, 2006 (1 page).

Thomson Jr., "Criticism of the NSF Grows," Commercialization of the Internet, 2000, retrieved from <<http://johnthomson.org/j561/NSFcriticism-6.html>>, retrieved on May 24, 2006 (1 page).

Thomson Jr., "The NSF Starts to Change Their Policy," Commercialization of the Internet, 2000, retrieved from <<http://johnthomson.org/j561/NSFpolicy-7.html>>, retrieved on May 24, 2006 (1 page).

Thomson Jr., "Changes in NSF Policy Becomes Law—The Internet is Commercialized, Commercialization of the Internet, 2000, retrieved from <<http://johnthomson.org/j561/NSFlaw-9.html>>, retrieved on May 24, 2006 (1 page).

W3 C, "HTTP: A Protocol for Network Information: Basic HTTP as Defined in 1992," retrieved from <<http://www.w3.org/Protocols/HTTP/HTTP2.html>>, retrieved on May 24, 2006 (2 pages).

"The World Wide Web Servers: W3 Servers," w3.org, retrieved from <<http://www.w3.org/History/19921103-hypertext/hypertext/DataSources/WWW/Servers.html>>, retrieved on May 24, 2006 (2 pages).

"The World Wide Web Project," w3.org, retrieved from <<http://www.w3.org/History/19921103-hypertext/hypertext/WWW/TheProject.html>>, retrieved on May 24, 2006 (1 page).

"Demonstrations—JENC92," w3.org, retrieved from <<http://www.w3.org/Conferences/JENC92/Demonstrations.html>>, retrieved on May 24, 2006 (1 page).

BL, "An Updated Quick Look at Viola WWW," retrieved from <<http://www.w3.org/History/19921103-hypertext/hypertext/Viola/Review.html>>, retrieved on May 24, 2006 (2 pages).

W3C, "HyperText Transfer Protocol Design Issues," retrieved from <<http://www.w3.org/Protocols/DesignIssues.html>>, retrieved on May 24, 2006 (3 pages).

"WorldWideWeb for C5," Presentation, w3.org, May 17, 1991, retrieved from <http://www.w3.org/Talks/C5_17_May_91.html>, retrieved on May 24, 2006 (1 page).

W3C, "Change History for httpd," retrieved from <<http://www.w3.org/Daemon/Features.html>>, retrieved on May 24, 2006 (15 pages).

(56)

References Cited**OTHER PUBLICATIONS**

- W3C, "A Little History of the Word Wide Web (1945-1995)," retrieved from <<http://www.w3.org/History.html>>, retrieved on May 24, 2006 (6 pages).
- Wandschneider, "ActiveX Controls Framework: Sample Code for Authoring Non-MFC Controls," Microsoft Corporation, Apr. 1996, retrieved from <http://msdn.microsoft.com/archive/en-us/dnaractivex/html/msdn_ctrlfink.asp?frame=true>, retrieved on Mar. 22, 2007 (15 pages).
- Watt, "Management Tools Get with the Web," Network World, vol. 14, No. 25, Jun. 23, 1997 (1 page).
- Weber, "New Software Helps Advertisers Get Through Tangled Web Pages," The Wall Street Journal, Oct. 23, 1996 (2 pages).
- Websidestory and Aig, "On Demand Analytics Presentation," Jun. 22, 2005 (10 pages).
- Weston, "Netscape 2.0b2 allows for invasion of privacy," TBTF, Dec. 2, 1995, retrieved from <<http://www.tbtf.com/resource/b2-privacy-bug.html>>, retrieved on May 24, 2006 (2 pages).
- Wilson, "Browser Timelines (Releases Important to HTML and CSS Development)=Index DOT HTML/Css," retrieved from <<http://www.blooberry.com/indexdot/history/browsers6.htm>> retrieved on May 24, 2006 (3 pages).
- Wilson, "Opera (Opera Software) Index DOT Html/Css," retrieved from <<http://www.blooberry.com/indexdot/history/opera.htm>> retrieved on May 24, 2006 (3 pages).
- Zaiane et al., "Discovering Web Access Patterns and Trends by Applying OLAP and Data Mining Technology on Web Logs," IEEE International Forum on Research and Technology Advances in Digital Libraries, Apr. 1998 (12 pages).
- Ziegler, "Startup Net Count Seeks to Tally How Many Web Surfers See Ads," The Wall Street Journal, Oct. 11, 1996 (2 pages).
- McGrew, "Web Authoring FAQ," The Web Design Group, 2005, posted to comp.infosystems.www.authoring.html, retrieved from File://P:\P Drive Files\Clients \Nielsen-NetRatings\ Settled Cases\Sane Solutions, LLC\ retrieved on Dec. 21, 2006 (59 pages).
- WwwTalk 1991 Archives, "Messages from Monday Oct. 28, 1991 to Friday, Dec. 13, 1991," retrieved from <<http://ksi.cpsc.ucalgary.ca/archives/WWW-talk/www-talk-1991.index.html>>, retrieved on May 24, 2006 (1 page).
- European Patent Office, "Communication Pursuant to Article 94(3) EPC," issued in connection with European Patent Application No. 00949006.1, mailed Oct. 7, 2014 (6 pages).
- Screen Shot of ftp.ist.utl.pt, 1999 (1 page).
- Pestana et al., "A Visual History of Web Measurement: Vendor Emergence, Technology Deployment and Seminal Events" (1 page).
- "Third International World-Wide Web Conference—Technology, Tools and Applications," Apr. 10-14, 1995, retrieved from <http://www.igd.fhg.de/archive/1995_www95/>, retrieved on May 24, 2006 (1 page).
- Sanders, "Plexus Log File Summaries," email message from sanders@bsd.com, Jun. 18, 1993, retrieved from <<http://ksi.cpsc.ucalgary.ca/archives/WWW-TALK/www-talk-1993q2.messages/563.html>> retrieved from May 24, 2006 (4 pages).
- "2.4—Windows Based Only Internet BBS Software—The Official BBS FAQ," retrieved from <<http://www.sysopworld.com/bbsfaq/ch02.2.4.htm>>, retrieved on May 24, 2006 (23 pages).
- Java@mt.e-technik.uni-kassel.de, "Counter," retrieved from <<http://web.archive.org/web/19970802020140/www.uni-kassel.de/fb16/ipm/mt/java/counteru.html>>, retrieved on May 24, 2006 (1 page).
- "Linear IP Advertising Infrastructure" (1 page).
- "Applet Collection" (5 pages).
- Arbitron Inc., "Respondent-Level Data: Your Key to Reaching the Hispanic Listener," retrieved from <http://arbitronratings.com/ad_agencies/rld_vs_hispsumm.htm?inframe>, retrieved on Sep. 21, 2007 (1 page).
- Abrams et al., "Multimedia Traffic Analysis Using CHITRA95," ACM Multimedia 95—Electronic Proceedings, Nov. 5-9, 1995, retrieved from <<http://ei.cs.vt.edu/~succeed/95multimediaAWAFPR/95multimediaAWAFPR.html>>, retrieved on Jun. 9, 2006 (17 pages).
- Abrams, "A Tool to Aid in Model Development and Validation," NCR Corporation, Annual Simulation Symposium, 1986 (10 pages).
- Anderson et al., "Next Generation Intrusion Detection Expert System (NIDES)—Software Users Manual Beta—Update Release," SRI International, Dec. 1, 1994 (316 pages).
- Barber, e-mail dated May 3, 1996, (2 pages).
- Baskaran, "Gamelan Who's Who More Info," Earth Web, Inc., 1996 (2 pages).
- Bates, "The Design of Browsing and Berrypicking Techniques for the Online Search Interface," Graduate School of Library and Information Science, University of California at Los Angeles, 1989, retrieved from <file://P:\ Drive Files\CLIENTS\Nielsen-NetRatings\SettledCases\Sane Solutions LLC\>, retrieved on Dec. 21, 2006 (19 pages).
- Berners-Lee et al., "Uniform Resource Locators" Network Working Group, Dec. 1994 (23 pages).
- Berners-Lee, "Presentation of WWW to Online Publishing 93—World-Wide Web," retrieved from <<http://www.w3.org/Talks/OnlinePublishing93/Overview.html>>, retrieved on May 24, 2006 (1 page).
- Berners-Lee et al., "Hypertext Transfer Protocol—HTTP/1.0," Network Working Group, May 1996, retrieved from <<http://www.w3.org/Protocols/rfc1945/rfc1945>>, retrieved on Mar. 22, 2007 (57 pages).
- Berners-Lee, "The World Wide Web Browser," retrieved from <<http://www.w3.org/People/Berners-Lee/WorldWideWeb.html>>, retrieved on May 24, 2006 (4 pages).
- Bernstein et al., "Architectures for Volatile Hypertext," Hypertext '91 Proceedings, Dec. 1991 (18 pages).
- Bestavros et al., "Application-Level Document Caching in the Internet," Proceeding of the Second International Workshop on Services in Distributed and Networked Environments (SDNE '95) (8 pages).
- Bieber et al., "Backtracking in a Multiple-window Hypertext Environment," ECHT '94 Proceedings, Sep. 1994 (9 pages).
- Bl, "Plenary Talk at WWW Geneva 94," retrieved from <<http://www.w3.org/Talks/WWW94Tim/>> retrieved on May 24, 2006 (4 pages).
- Bl et al., "W3 Project—Assorted Design Notes—Working Notes," W3.org, retrieved from <<http://www.w3.org/History/1994/WWW/WorkingNotes/Overview.html>>, retrieved on May 24, 2006 (2 pages).
- Blackarrow, Inc., "Meeting the Challenges of Video Advertising in an IP ABR Environment," 2012 (10 pages).
- Blythe et al., "Lynx Users Guide Version 2.3," retrieved from <http://www.cse.unsw.edu.au/help/doc/lynx/lynx_help/Lynx_users_guide.html>, retrieved on Jun. 12, 2006 (12 pages).
- Boyns, "Crazy Counter," modified Mar. 8, 1996 (2 pages).
- Boyns, "Crazy Counter (GIF89a)," modified Mar. 8, 1996 (1 page).
- Boyns, "CrazyCounter.java," 1996 (5 pages).
- Braun et al., "Applied Network Research: 1994 Annual Status Report," Applied Network Research, San Diego Supercomputer Center and University of California, San Diego, Apr. 19, 1995 (15 pages).
- Brueggeman, "Monitoring CDROM Usage," UCSD Scripps Institution of Oceanography Library (5 pages).
- Carmel et al., "Browsing in Hypertext: A Cognitive Study," IEEE Transactions on Systems, Man, and Cybernetics, vol. 22, No. 5, Sep./Oct. 1992 (23 pages).
- Chankhunthod et al., "A Hierarchical Internet Object Cache," ATEC '96 Proceedings of the 1996 Annual Conference on USENIX Annual Technical Conference, 1996 (11 pages).
- Chen, "Supporting Advertisement on Electronic Publications," IBM Technical Disclosure Bulletin, Aug. 1996 (2 pages).
- Claffy et al., "Traffic Characteristics of the T1 NSFNET Backbone," INFOCOM '93 Proceedings, Twelfth Annual Joint Conference of the IEEE Computer and Communications Societies, Networking: Foundation for the Future, IEEE, 1993 (11 pages).
- Cove et al., "Online Text Retrieval Via Browsing," Information Processing and Management, vol. 24, No. 1, 1988 (10 pages).
- Cunha et al., "Characteristics of WWW Client-Based Traces," Computer Science Department, Boston University, Jul. 18, 1995 (19 pages).
- Davis et al., "Instant Java Applets," Macmillan Computer Publishing USA, 1996 (234 pages).

(56)

References Cited**OTHER PUBLICATIONS**

Dellecave Jr., "The Net Effect," Sales & Marketing Management: An Executive's Guide to Sales and Marketing Technology, Mar. 1996 (9 pages).

Desjardins, "Activity Monitor 1.1 User's Guide," 1994 (5 pages).

Digital Envoy, "NetAcuity IP Intelligence Whitepaper," Digital Envoy, Inc., 2002-2003 (10 pages).

Earth Station 9, "Computers and the Internet," <<http://www.earthstation9.com/counters.htm>>, retrieved from May 24, 2006 (2 pages).

Earthweb, Inc., "Java-Enhanced Communication Tools," Gamelan, The Official Directory for Java, 1996 (7 pages).

Engagement Marketing Group, "Advanced Advertising Media Project—Phase One: Summary Report—Remaking Video-on-Demand to Deliver Media Value," May 11, 2011 (50 pages).

European Patent Office, "Supplementary Partial Search Report," issued in connection with European Patent Application No. 00949006.1, mailed Apr. 19, 2006 (4 pages).

European Patent Office, "Supplementary Search Report," issued in connection with European Patent Application No. 00949006.1, mailed Jul. 12, 2006 (5 pages).

European Patent Office, "Extended Search Report," issued in connection with European Patent Application No. 10012280.3, mailed Mar. 17, 2014 (6 pages).

European Patent Office, "Office Action," issued in connection with European Patent Application No. 00949006.1, mailed Oct. 7, 2014 (6 pages).

Feliciano et al., "Lamprey: Tracking Users on the World Wide Web," Section on Medical Informatics, Stanford University, 1996 (5 pages).

Fielding, "Wwwstat Manual," retrieved from <<http://ftp.ics.uci.edu/pub/websoft/wwwstat/wwwstat.html>>, retrieved on Jun. 12, 2006 (11 pages).

Finke, "Monitoring Usage of Workstations with a Relational Database," 1994 LISA—San Diego, California, Sep. 19-23, 1994 (10 pages).

Fleishman, "Web Log Analysis: Who's Doing What, When? Part 2," retrieved from <http://www.webdeveloper.com/management/management_log_analysis_2.html> (4 pages).

Fuller, "Measuring User Motivation From Server Log Files," Usability Research, retrieved from <<http://www.microsoft.com/usability/webconf/fuller/fuller.htm>>, Oct. 30, 2000 (15 pages).

Gellman, "They Could be Monitoring Your Every Web Move," GCN, retrieved from <http://www.gcn.com/print/15_9/31672-1.html>, retrieved on Apr. 20, 2006 (3 pages).

Girdley et al., "Web Programming with Java," 1996 (9 pages).

Gile, "Reporting Application Usage in a LAN Environment," ACM SIGUCCS, vol. 18, 1990 (13 pages).

Gilula et al., "A Direct Approach to Data Fusion," Journal of Marketing Research, vol. 43, Feb. 2006 (22 pages).

Goldmail, "GoldMail Thinks Consumers Should Get Paid for Reading Advertising!" Google Groups, Jul. 7, 1996 (4 pages).

Goldmail, "GoldMail Revolutionizes Internet Advertising!" Google Groups, Jul. 7, 1996 (4 pages).

Glassman, "A Caching Relay for the World Wide Web," Systems Research Center, Digital Equipment Corporation, 1994 (10 pages).

Google Groups, "Java Project" "I am Volunteering My time," retrieved from <http://groups.google.com/group/comp.lang.java.programmer/browse_thread/thread/5430a3...>, retrieved on Apr. 12, 2006 (3 pages).

Google Groups, "Counter," retrieved from <http://groups-beta.google.com/group/comp.lang.javascript/browse_thread/thread/4874a9f9c...>, retrieved on Jun. 8, 2005 (4 pages).

Google Groups, "Can U Make a Hit Counter in a Java Applet?," retrieved from <http://groups.google.com/group/comp.lang.java/browse_thread/thread/f2a41d0cb5c8ee4/c8...>, retrieved on May 2, 2006 (10 pages).

Google Groups, "Xferstats," retrieved from <http://groups.google.com/group/comp.unix.xenix/browse_thread/thread/cb3dlaed21bc0e3e/8d9ce54693af9e98?q=xferstats&num=200...>, retrieved on May 24, 2006 (3 pages).

Google Groups, "Hit Counter" retrieved from <http://groups.google.com/group/comp.infosystems.www.authoring.html/browse_thread/e515dad2e5d1e8cc/0ebdc329e9ec00cc?q=hit+c...> retrieved on May 24, 2006 (7 pages).

Google Groups, "Garrett Casey Counter," retrieved from <Google Groups: comp.infosystems.www.misc.entrepreneurs> (3 pages).

Greenberg, "Using Unix: Collected Traces of 168 Users," Advanced Technologies, The Alberta Research Council (14 pages).

Hansen et al., "Automated System Monitoring and Notification With Swatch," Seventh System Administration Conference (LISA '93), Monterey California, Nov. 1993 (9 pages).

Haran, "PC-Meter Tracks Computer Users," Advertising Age, Oct. 2, 1995, retrieved from <<http://adage.com/print/85520>>, retrieved on Jun. 2, 2015 (2 pages).

Highbeam Research, "Harris Computer Systems and Webster Network Strategies Announce Alliance to Offer WWW Monitoring Capabilities Through Firewalls," Business Wire, Mar. 4, 1996, retrieved from <<http://www.highbeam.com>> (5 pages).

Hilbert et al., "Agents for Collecting Application Usage Data Over the Internet," Department of Information and Computer Science, University of California, Irvine (9 pages).

"Horace's Java—Page View Timer Demo—Form 1," Aug. 7, 1999 (2 pages).

Horak, "IOMON—Protected Mode I/O Port Monitor," Technical University of Prague, Faculty of Nuclear Science and Physical Engineering (6 pages).

International Searching Authority, "International Search Report," issued in connection with International Patent Application No. PCT/US2015/015219, mailed May 22, 2015 (4 pages).

International Searching Authority, "Written Opinion," issued in connection with International Patent Application No. PCT/US2015/015219, mailed May 22, 2015 (7 pages).

Ivler, "Advertising Models and Associated Software . . .," Google Groups, May 15, 1996 (5 pages).

Johnson et al., "Automatic Touring in a Hypertext System," IEEE Twelfth Annual International Phoenix Conference on Computers and Communications, 1993 (7 pages).

Kamba et al., "The Krakatoa Chronicle—An Interactive, Personalized, Newspaper on the Web," Georgia Institute of Technology (15 pages).

Kugel et al., "Decay Effects in Online Advertising: Quantifying the Impact of Time Since Last Exposure," Presented at the ARF 50th Annual Convention, New York City, Apr. 26-28, 2004 (19 pages).

Lee et al., "Intelligent Agents for Matching Information Providers and Consumers on the World-Wide-Web," Proceedings of the Thirtieth Annual Hawaii International Conference on System Sciences, IEEE, 1997 (11 pages).

Lubow, "An Engineer's Guide to Autocad," Industrial Engineering, vol. 19, No. 8, Aug. 1987 (6 pages).

Long, "Gwstat v1.1—Generate Graphs of HTTPD Server Traffic," BUBL Administrator, Jul. 14, 1994, retrieved from <<http://www.bubl.ac.uk/archive/internet/www/servers/gswtat6.htm>>, retrieved on Jun. 12, 2006 (1 page).

Marchionini, "Information-Seeking Strategies of Novices Using a Full-Text Electronic Encyclopedia," Journal of the American Society for Information Science, vol. 40, No. 1, 1989 (16 pages).

McCanne et al., "The BSD Packet Filter: A New Architecture for User-level Packet Capture," Lawrence Berkeley Laboratory, Berkeley, California, Dec. 19, 1992 (11 pages).

McGee, "Web Pages: A Programmer's Perspective," Jun. 10, 1996, retrieved from <<http://www.dfpug/loseblattsammlung/migration/whitepapers/webpages.htm>>, retrieved on Mar. 22, 2007 (13 pages).

McGrath, "The Tail-Less Mouse," Computer Graphics World, vol. 11, Oct. 1988 (5 pages).

McKenzie et al., "An Empirical Analysis of Web Page Revisitation," Department of Computer Science, University of Canterbury, 2001 (7 pages).

Mogul, "Efficient Use of Workstations for Passive Monitoring of Local Area Networks," WRL Research Report 90/5, Western Research Laboratory, Jul. 1990 (29 pages).

(56)

References Cited**OTHER PUBLICATIONS**

- Mosaic Communications Corporation, "Welcome to Netscape," retrieved from <http://www.hnehosting.com/mirrors/Origin_of_a_Browser/mcom.10.1994/home/welcome.html>, retrieved on May 24, 2006 (2 pages).
- Mueller, "InfoTicker Java Applet," Google Groups, May 11, 1996, retrieved from <http://groups.google.com/group/comp.infosystems.www.announce/browse_thread/thread/cc...>, retrieved on May 2, 2006 (2 pages).
- NCSA, "In the Beginning There was NCSA Mosaic . . ." NCSA, retrieved from <<http://www.ncsa.uiuc.edu/News/MosaicHistory/>>, retrieved on Jun. 12, 2006 (15 pages).
- Netscape, "Mosaic Communications Changes Name to "Netscape Communications Corporation,"" Netscape Communications Corporation, retrieved from <<http://www.holgermetzger.de/netscape/NetscapeCommunicationsNewsRelease.htm>>, retrieved on May 24, 2006 (2 pages).
- Neumann, "Forum on Risks to the Public in Computers and Related Systems," Risks-Forum Digest, vol. 17, Issue 83, Mar. 4, 1996 (11 pages).
- Ousterhout et al., "A Trace-Driven Analysis of the UNIX 4.2 BSD File System," Computer Science Division, Electrical Engineering and Computer Sciences, University of California, Apr. 25, 1985 (30 pages).
- Pallap, "Marketing on the Internet," Journal of Consumer Marketing, vol. 13, No. 4, Aug. 1996 (17 pages).
- Perlman, "Asynchronous Design/Evaluation Methods for Hypertext Technology Development," Hypertext '89 Proceedings, Nov. 1989 (21 pages).
- Pew, "Instant Java," Sun Microsystems, Inc., 1996 (370 pages).
- Philip Morris, "Teenage Attitudes and Behavior Study—Methodology 2006" (9 pages).
- Pitkow et al., "A Simple Yet Robust Caching Algorithm Based on Dynamic Access Patterns," Proceedings of the Second International WWW Conference, GVU Technical Report; VU-GIT-94-39 (8 pages).
- Pitkow et al., "Results From the First World-Wide Web User Survey," Journal of Computer Networks and ISDN Systems, vol. 27, No. 2, 1994 (15 pages).
- Pitkow et al., "Using the Web as a Survey Tool: Results From the Second WWW User Survey," Third International WWW Conference, GVU Technical Report; GVU-GIT-94-40 (12 pages).
- Pitkow et al., "Results From the Third WWW User Survey," Graphics, Visualization, & Usability Center, Georgia Institute of Technology (10 pages).
- Poler, "Improving WWW Marketing Through User Information and Non-Intrusive Communication," Internet Profiles Corporation (I/PRO) (4 pages).
- Progressive Networks, Inc., "RealServer Administration and Content Creation Guide Version 4.0," Progressive Networks, Inc., 1995-1997 (366 pages).
- Progressive Networks, Inc., "RealAudio Server Administration and Content Creation Guide Version 3.0," Progressive Networks, Inc., 1995-1996 (292 pages).
- Raggett, "HTML 3.2 Reference Specification," W3C, Jan. 14, 1997, retrieved from <<http://www.w3.org/TR/REC-html32>>, retrieved from Mar. 22, 2007 (49 pages).
- Regents of the University of California, "Changes to wwwstat: httpd Logfile Analysis Package," 1994, 1996, retrieved from <<http://ftp.ics.uci.edu/pub/websoft/wwwstat/Changes>>, retrieved on Jun. 12, 2006 (4 pages).
- Resonate, "Network Traffic Mangement, Database Traffic Management," Resonate, Inc. 2005 (2 pages).
- Reuters, "Study Faults Online Ads for Kids, FTC Probes," Google Groups, Mar. 28, 1996 (3 pages).
- Shepard, "TCP Packet Trace Analysis," MIT/LCS/TR-494, MIT Laboratory for Computer Science, Feb. 1991 (70 pages).
- Stengle, "Tying TV Advertising to Action: Leveraging the Second Screen to Raise the Effectiveness & Measurability of TV Advertising," BlackArrow USA, 2012 (8 pages).
- Sukaviriya et al., "A Second Generation User Interface Design Environment: The Model and the Runtime Architecture," GIT-GVU-92-24, Graphics, Visualization & Usability Center, Georgia Institute of Technology, Sep. 1992 (10 pages).
- Sunsite, "Hot Java Readme and Link to the Software on SunSITE," SunSITE Software Information and Technology Exchange, retrieved from <http://www.ibiblio.org/hotjava/>, retrieved on May 24, 2006 (1 page).
- Symantec, "Using Norton pcANYWHERE for DOS," Symantec Corporation, 1994 (30 pages).
- "Tcpslice(8):—Linux Man Page," retrieved from <<http://www.die.net/doc/linux/man/man8/tcpslice.8.html>>, retrieved on Jun. 12, 2006 (3 pages).
- Tapley et al., "The Official Gamelan Java Directory," EarthWeb, 1996 (6 pages).
- "Tcpslice—Linux Command—Unix Command," tcpslice, 2006, retrieved from <http://linux.about.com/library/cmd/blcmd18_tcpslice.htm>, retrieved on Jun. 12, 2006 (3 pages).
- Thielman, "Comcast Pushes VOD Reruns into the C3 Window," Adweek, Dec. 2, 2013, retrieved from <<http://www.adweek.com/news/television/comcast-pushes-vod-reruns-c3...>>, retrieved on Feb. 10, 2014 (1 page).
- Tcpdump.org, "Tcpdump—dump traffic on a network," retrieved from <http://www.tcpdump.org/tcpdump_man.html>, retrieved on Jun. 12, 2006 (26 pages).
- Tolle, "Performance Measurement and Evaluation of Online Information Systems," Proceedings of the 1985 ACM Computer Science Conference—Agenda for Computing Research: The Challenge for Creativity, Mar. 12-14, 1985 (8 pages).
- "Tradewinds," Harvard Business School, vol. 2, No. 5, May 1995 (11 pages).
- User Society, "First International Conference on the World-Wide Web," May 1994, retrieved from <<http://www.94.web.cern.ch/WWW94/>>, retrieved on May 24, 2006 (2 pages).
- W3.Org, "CGI—Common Gateway Interface," W3C, retrieved from <<http://www.w3.org/CGI/>>, retrieved on May 24, 2006 (2 pages).
- Warren, "Audience Tracking System for Electronic Newspapers" Google Groups, May 3, 1995 (3 pages).
- Weiler et al., "Usability Lab Tools: One Year Later," CHI'94, Conference Companion, 1994 (p. 330).
- Wright, "Matt's Script Archive: Book'em Dano:Readme," 1996, retrieved from <<file://P:\PDrive\Files\CLIENTS\Nielsen-NetRatings\Settled Cases\Sane Solutions, LLC>>, retrieved on Dec. 21, 2006 (2 pages).
- Wu et al., "Virtual Proxy Servers for WWW and Intelligent Agents on the Internet," Proceedings of the Thirtieth Annual Hawaii International Conference on System Sciences, 1997 (10 pages).
- Yahoo!, "Yahoo! Search Directory > Web Programming > Access Counters," retrieved from <http://dir.yahoo.com/Computers_and_internet/Internet/World_Wide_Web/Programming/Access_Counters/>, retrieved on May 24, 2006 (5 pages).
- Zeigler, "Startup Net Count Seeks to Tally How Many Web Surfers See Ads," The Wall Street Journal, Oct. 1996 (2 pages).
- Zillmer, "How to Make Your Web Ads Pay Off," Marketing Magazine, vol. 101, No. 23, Jun. 10, 1996 (4 pages).

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7





FIG. 8






FIG. 10




FIG. 11

Calculate cell parameters for each demographic group

$$AVP = \frac{\sum \text{Weighted Visitor Exposure Minutes for demographic of interest}}{\sum \text{Weighted Household Tuning Minutes}}$$

Example: Calculate cell parameters for Female 6-11 and Male 55-64

Possible Visitor?	Female 6-11	Male 55-64
Tuning Characteristics ¹²⁰²	Watching Disney using M-F 12:30 - 5 PM daypart	
HH Characteristics ¹²⁰⁴	Older Family Life Stage, 2 TV sets	
Visitor Exposure Minutes	3,892 ¹²¹⁰	1,081 ¹²¹⁶
HH Tuning Minutes	3,109 ¹²¹²	3,109 ¹²¹⁸
	1214	1220
Visitor Parameters	(3,892/3,109) = 1.252	(1,081/3,109) = .348

Note that 1.252 and .348 are themselves the AVPs (not probabilities) that are later used to calculate probability values with the Poisson Distribution

FIG. 12

CATEGORY OF INTEREST	VISITOR EXPOSURE MINUTES	HOUSEHOLD TUNING MINUTES
LIFE STAGE = OLDER FAMILY	443,940	733,317
TV SETS = 2	150,844	285,877
TOTAL MINUTES	1,741,474	8,200,347

EXPOSURE PROPORTION FOR LIFE STAGE = OLDER FAMILY

$$= \frac{\text{Visitor Exposure Min.}}{\text{Total Exposure Min.}} = \frac{443,940}{1,741,474} = 0.255$$

TUNING PROPORTION FOR LIFE STAGE = OLDER FAMILY

$$= \frac{\text{HH Tuning Min.}}{\text{Total Tuning Min.}} = \frac{733,317}{8,200,347} = 0.089$$

EXPOSURE PROPORTION FOR TV SETS = 2

$$= \frac{\text{Visitor Exposure Min.}}{\text{Total Exposure Min.}} = \frac{150,844}{1,741,474} = 0.087$$

TUNING PROPORTION FOR TV SETS = 2

$$= \frac{\text{HH Tuning Min.}}{\text{Total Tuning Min.}} = \frac{285,877}{8,200,347} = 0.035$$

Expected Exposure Min. = (Tot. Exp. Min)*(Exp. Proportion 1)*(Exp. Proportion n)

$$= (1,741,474)*(0.255)*(0.087) = 38,635$$

Expected Tuning Min. = (Tot. Tun. Min)*(Tun. Proportion 1)*(Tun. Proportion n)

$$= (8,200,347)*(0.089)*(0.035) = 25,544$$

AVP = $\frac{38,635}{25,544} = 1.504$

FIG. 13





FIG. 14






FIG. 16

1700




FIG. 17




FIG. 18




FIG. 19

2000

MEDIA METER CREDITING




FIG. 20




FIG. 21

2200




FIG. 22




FIG. 23

1

METHODS AND APPARATUS TO CHARACTERIZE HOUSEHOLDS WITH MEDIA METER DATA

RELATED APPLICATION

This application claims the benefit of U.S. Provisional Application Ser. No. 61/839,344, which was filed on Jun. 25, 2013, U.S. Provisional Application Ser. No. 61/844,301, which was filed on Jul. 9, 2013, U.S. Provisional Application Ser. No. 61/986,409, which was filed on Apr. 30, 2014, and U.S. Provisional Application Serial No. 62,007,535, which was filed on Jun. 4, 2014, all of which are hereby incorporated herein by reference in their entireties.

FIELD OF THE DISCLOSURE

This disclosure relates generally to market research, and, more particularly, to methods and apparatus to characterize households with media meter data.

BACKGROUND

In recent years, panelist research efforts included installing metering hardware in qualified households that fit one or more demographics of interest. In some cases, the metering hardware is capable of determining whether a media presentation device (such as a television set) is powered on and tuned to a particular station via a hardwired connection from the media presentation device to the meter. In other cases, the metering hardware is capable of determining which household member is exposed to a particular portion of media via one or more button presses on a People Meter by the household member near the television.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates an example media distribution environment in which households may be characterized with media meter data.

FIG. 2 is a schematic illustration of an example imputation engine constructed in accordance with the teachings of this disclosure.

FIG. 3 is a plot illustrating an example viewing index effect based on an age of collected data.

FIG. 4 is an example weighting allocation table to apply a temporal weight to collected minutes.

FIG. 5 is an example dimension subset map to illustrate independent distribution of household dimensions used to characterize households with media meter data.

FIGS. 6-9 are flowcharts representative of example machine readable instructions that may be executed to implement the example imputation engine of FIGS. 1 and 2.

FIG. 10 is an example visitor table to illustrate example visitor tuning minutes and exposure minutes for a demographic of interest.

FIG. 11 is a schematic illustration of an example visitor imputation engine constructed in accordance with the teachings of this disclosure.

FIG. 12 are example cell parameter calculations including example demographics of interest and example categories of interest to determine average visitor parameters to be used to impute a number of visitors.

FIG. 13 are example independent parameter calculations to determine average visitor parameters to be used to impute a number of visitors.

2

FIG. 14 are example probability values and cumulative probability values generated by the example visitors imputation engine of FIGS. 1 and 11.

FIG. 15 is a flowchart representative of example machine readable instructions that may be executed to implement the example visitor imputation engine of FIGS. 1 and 11.

FIG. 16 is a schematic illustration of an example ambient tuning engine constructed in accordance with the teachings of this disclosure.

FIGS. 17-19 are flowcharts representative of example machine readable instructions that may be executed to implement the example ambient tuning engine of FIGS. 1, 10 and 16.

FIG. 20 is an example crediting chart illustrating example categories of collected viewing minutes.

FIG. 21 is a schematic illustration of an example on/off detection engine constructed in accordance with the teachings of this disclosure.

FIG. 22 is a flowchart representative of example machine readable instructions that may be executed to implement the example on/off detection engine of FIGS. 1 and 21.

FIG. 23 is a schematic illustration of an example processor platform that may execute the instructions of FIGS. 6-9, 15, 17-19 and/or 22 to implement the example ambient tuning engine, the example imputation engine and the example on/off detection engine of FIGS. 1, 2, 10, 16 and/or 21.

DETAILED DESCRIPTION

Market researchers seek to understand the audience composition and size of media, such as radio programming, television programming and/or Internet media so that advertising prices can be established that are commensurate with audience exposure and demographic makeup (referred to herein collectively as “audience configuration”). As used herein, “media” refers to any sort of content and/or advertisement which is presented or capable of being presented by an information presentation device, such as a television, radio, computer, smart phone or tablet. To determine aspects of audience configuration (e.g., which household member is currently watching a particular portion of media and the corresponding demographics of that household member), the market researchers may perform audience measurement by enlisting any number of consumers as panelists. Panelists are audience members (household members) enlisted to be monitored, who divulge and/or otherwise share their media exposure habits and demographic data to facilitate a market research study. An audience measurement entity typically monitors media exposure habits (e.g., viewing, listening, etc.) of the enlisted audience members via audience measurement system(s), such as a metering device and a People Meter. Audience measurement typically involves determining the identity of the media being displayed on a media presentation device, such as a television.

Some audience measurement systems physically connect to the media presentation device, such as the television, to identify which channel is currently tuned by capturing a channel number, audio signatures and/or codes identifying (directly or indirectly) the programming being displayed. Physical connections between the media presentation device and the audience measurement system may be employed via an audio cable coupling the output of the media presentation device to an audio input of the audience measurement system. Additionally, audience measurement systems prompt and/or accept audience member input to reveal which household member is currently exposed to the media presented by the media presentation device.

As described above, audience measurement entities may employ the audience measurement systems to include a device, such as the People Meter (PM), having a set of inputs (e.g., input buttons) that are each assigned to a corresponding member of a household. The PM is an electronic device that is typically disposed in a media exposure (e.g., viewing) area of a monitored household and is proximate to one or more of the audience members. The PM captures information about the household audience by prompting the audience members to indicate that they are present in the media exposure area (e.g., a living room in which a television set is present) by, for example, pressing their assigned input key on the PM. When a member of the household selects their corresponding input, the PM identifies which household member is present, which includes other demographic information associated with the household member, such as a name, a gender, an age, an income category, etc. However, in the event a visitor is present in the household, the PM includes at least one input (e.g., an input button) for the visitor to select. When the visitor input button is selected, the PM prompts the visitor to enter an age and a gender (e.g., via keyboard, via an interface on the PM, etc.).

The PM may be accompanied by a base metering device (e.g., a base meter) to measure one or more signals associated with the media presentation device. For example, the base meter may monitor a television set to determine an operational status (e.g., whether the television is powered on or powered off, a media device power sensor), and/or to identify media displayed and/or otherwise emitted by the media device (e.g., identify a program being presented by a television set). The PM and the base meter may be separate devices and/or may be integrated into a single unit. The base meter may capture audience measurement data via a cable as described above and/or wirelessly by monitoring audio and/or video output by the monitored media presentation device. Audience measurement data captured by the base meter may include tuning information, signatures, codes (e.g., embedded into or otherwise broadcast with broadcast media), and/or a number of and/or identification of corresponding household members exposed to the media output by the media presentation device (e.g., the television).

Data collected by the PM and/or the base meter may be stored in a memory and transmitted via one or more networks, such as the Internet, to a data store managed by a market research entity such as The Nielsen Company (US), LLC. Typically, such data is aggregated with data collected from a large number of PMs and/or base meters monitoring a large number of panelist households. Such collected and/or aggregated data may be further processed to determine statistics associated with household behavior in one or more geographic regions of interest. Household behavior statistics may include, but are not limited to, a number of minutes a household media device was tuned to a particular station, a number of minutes a household media device was used (e.g., viewed) by a household panelist member and/or one or more visitors, demographics of an audience (which may be statistically projected based on the panelist data) and instances when the media device is on or off. While examples described herein employ the term “minutes,” such as “household tuning minutes,” “exposure minutes,” etc., any other time measurement of interest may be employed without limitation.

To ensure audience measurement systems are properly installed in panelist households, field service personnel have traditionally visited each panelist household, assessed the household media components, physically installed (e.g., connected) the PM and/or base meter to monitor a media presentation device(s) of the household (e.g., a television), and

trained the household members how to interact with the PM so that accurate audience information is captured. In the event one or more aspects of the PM and/or base meter installation are inadvertently disrupted (e.g., an audio cable connection from the media device to the base meter is disconnected), then subsequent field service personnel visit(s) may be necessary. In an effort to allow collected household data to be used in a reliable manner (e.g., a manner conforming to accepted statistical sample sizes), a relatively large number of PMs and/or base meters are needed. Each such PM and/or base meter involves one or more installation efforts and installation costs. As such, efforts to increase statistical validity (e.g., by increasing panel size and/or diversity) for a population of interest result in a corresponding increase in money spent to implement panelist households with PMs and/or base meters.

In an effort to increase a sample size of household behavior data and/or reduce a cost associated with configuring panelist households with PMs and/or base meters, example methods, apparatus, systems and/or articles of manufacture disclosed herein employ a media meter (MM) to collect household panelist behavior data. Example MMs disclosed herein are distinguished from traditional PMs and/or base meters that include a physical connection to the media presentation device (e.g., a television). In examples disclosed herein, the MM captures audio without a physical connection to the media device. In some examples, the MM includes one or more microphones to capture ambient audio in a room shared by the media device. In some such examples, the MM captures codes embedded by one or more entities (e.g., final distributor audio codes (FDAC)), and does not include one or more inputs that are to be selected by one or more household panelists to identify which panelist is currently viewing the media device. Rather than collecting audience composition data directly from panelists, example methods, apparatus, systems and/or articles of manufacture disclosed herein apply one or more models to impute which household members are exposed to particular media programming to collected MM data. Such example imputation techniques are described in further detail below and referred to herein as “persons imputation.” Additionally, example methods, apparatus and/or articles of manufacture disclosed herein apply one or more models to impute a number of visitors in each household and corresponding age/demographic characteristics of such visitors. In other words, examples disclosed herein facilitate a manner of determining a probability of household exposure activity, a number of visitors and/or corresponding visitor ages in a stochastic manner that avoids the expense of additional PM device installation in panelist households.

In some examples, a household includes two or more media devices, such as a first television located in a first room and a second television located in a second room. In the event the panelist household includes first and second meters physically connected to the first and second televisions, then the physical connection unambiguously identifies which audio data is originating from which television in the household, even if such audio from the first television propagates to the second room having the second television (and/or vice versa). Circumstances in which media played in one room can be heard and/or otherwise detected in another room (which may also have a media presentation device and accompanying meter) are referred to herein as “spillover.” In the event the panelist household includes first and second MMs located in the first and second rooms, respectively, then spillover audio data “heard” (detected) from the first room may erroneously be credited by the second MM as media presented in the second room (and/or vice versa). Media tuning events logged by a MM as occurring in one room, but actually occurring in

5

a second different room (e.g., due to spillover) are referred to herein as “ambient tuning.” In other words, because the MM includes microphones to collect audio emitted from media devices, the possibility exists that the first MM in the first room is picking-up and/or otherwise detecting audio from the media device in an adjacent (e.g., the second) room. Ambient tuning is distinguished from “real tuning” in that real tuning occurs when the MM properly credits the media presentation device (e.g., television) associated with the room in which the MM is located with a media exposure for media actually presented on that media presentation device. Example methods, apparatus, systems and/or articles of manufacture disclosed herein apply models to identify instances of ambient tuning (e.g., due to spillover) as distinguished from real (legitimate) tuning. Similarly, example methods, apparatus, systems and/or articles of manufacture disclosed herein apply models to identify instances of when a media presentation device is turned on as distinguished from instances of when the media device is powered off. This is important in avoiding crediting of media exposure when no such exposure is occurring. For example, in the event a household member is in a first room with an associated media presentation device in a powered-off state, but the associated meter in that first room is detecting audio from a second media device in a second room, examples disclosed herein identify the occurrence as spillover and do not credit the detection as an actual media exposure.

Turning to FIG. 1, an example media distribution environment **100** includes a network **102** (e.g., the Internet) communicatively connected to panelist households within a region of interest (e.g., a target research geography **104**). In the illustrated example of FIG. 1, some panelist households **106** include People Meters (PMs) and media meters (MMs) **106** and some other panelist households **108** include only MMs to capture household media exposure information. Households having both MMs and PMs are referred to herein as MMPM households **106**. Households that do not have a PM, but have a MM are referred to herein as MMHs (media meter households) **108**. Behavior information collected by the example MMPMs **106** and the example MMHs **108** are sent via the example network **102** to an example imputation engine **110**, an example visitor imputation engine, an example ambient tuning engine **120**, and/or an example on/off detection engine **130** for analysis. As described above, because MMHs **108** do not include PMs, they do not include physical button inputs to be selected by household members to identify which household member is currently watching particular media, and they do not include physical button inputs to be selected by household visitors to identify age and/or gender information. Therefore, example methods, systems, apparatus and/or articles of manufacture disclosed herein model household characteristics that predict a likelihood that a particular household member is watching the identified media being accessed in the MMHs **108**.

Example households that include a PM collect panelist audience data. As used herein, “panelist audience data” includes both (a) media identification data (e.g., code(s) embedded in or otherwise transmitted with media, signatures, channel tuning data, etc.) and (b) person information identifying the corresponding household member(s) and/or visitors that are currently watching/viewing/listening to and/or otherwise accessing the identified media. On the other hand, MMH households **108** include only a MM to collect media data. As used herein, “media data” and/or “media identifier information” are used interchangeably and refer to information associated with media identification (e.g., codes, signatures, etc.), but does not include person information identify-

6

ing which household member(s) and/or visitors are currently watching/viewing/listening to and/or otherwise accessing the identified media. As described in further detail below, example methods, apparatus, systems and/or articles of manufacture disclosed herein impute person identifying data to media data collected from MMH household(s) **108**.

Although examples disclosed herein refer to code readers and collecting codes, techniques disclosed herein could also be applied to systems that collect signatures and/or channel tuning data to identify media. Audio watermarking is a technique used to identify media such as television broadcasts, radio broadcasts, advertisements (television and/or radio), downloaded media, streaming media, prepackaged media, etc. Existing audio watermarking techniques identify media by embedding one or more audio codes (e.g., one or more watermarks), such as media identifying information and/or an identifier that may be mapped to media identifying information, into an audio and/or video component. In some examples, the audio or video component is selected to have a signal characteristic sufficient to hide the watermark. As used herein, the terms “code” or “watermark” are used interchangeably and are defined to mean any identification information (e.g., an identifier) that may be transmitted with, inserted in, or embedded in the audio or video of media (e.g., a program or advertisement) for the purpose of identifying the media or for another purpose such as tuning (e.g., a packet identifying header). As used herein “media” refers to audio and/or visual (still or moving) content and/or advertisements. To identify watermarked media, the watermark(s) are extracted and used to access a table of reference watermarks that are mapped to media identifying information.

Unlike media monitoring techniques based on codes and/or watermarks included with and/or embedded in the monitored media, fingerprint or signature-based media monitoring techniques generally use one or more inherent characteristics of the monitored media during a monitoring time interval to generate a substantially unique proxy for the media. Such a proxy is referred to as a signature or fingerprint, and can take any form (e.g., a series of digital values, a waveform, etc.) representative of any aspect(s) of the media signal(s) (e.g., the audio and/or video signals forming the media presentation being monitored). A good signature is one that is repeatable when processing the same media presentation, but that is unique relative to other (e.g., different) presentations of other (e.g., different) media. Accordingly, the term “fingerprint” and “signature” are used interchangeably herein and are defined herein to mean a proxy for identifying media that is generated from one or more inherent characteristics of the media.

Signature-based media monitoring generally involves determining (e.g., generating and/or collecting) signature(s) representative of a media signal (e.g., an audio signal and/or a video signal) output by a monitored media device and comparing the monitored signature(s) to one or more references signatures corresponding to known (e.g., reference) media sources. Various comparison criteria, such as a cross-correlation value, a Hamming distance, etc., can be evaluated to determine whether a monitored signature matches a particular reference signature. When a match between the monitored signature and one of the reference signatures is found, the monitored media can be identified as corresponding to the particular reference media represented by the reference signature that with matched the monitored signature. Because attributes, such as an identifier of the media, a presentation time, a broadcast channel, etc., are collected for the reference signature, these attributes may then be associated with the monitored media whose monitored signature matched the

reference signature. Example systems for identifying media based on codes and/or signatures are long known and were first disclosed in Thomas, U.S. Pat. No. 5,481,294, which is hereby incorporated by reference in its entirety.

Persons Imputation

FIG. 2 is a schematic illustration of an example implementation of the imputation engine 110 of FIG. 1. In the illustrated example of FIG. 2, the imputation engine 110 includes the visitor imputation engine 112, a People Meter (PM) interface 202, a media meter (MM) interface 204, a categorizer 206, a weighting engine 210 and a probability engine 212. As described in further detail below, the example visitor imputation engine 112 employs one or more portions of the example imputation engine 110. The example probability engine 212 of FIG. 2 includes an example dimension manager 214, an example cell probability engine 216 and an example independent distribution engine 218. The example cell probability engine 216 of FIG. 2 includes an example category fit manager 220, an example minutes aggregator 222 and an example imputation engine 224. The example independent distribution engine 218 of FIG. 2 includes an example category qualifier 226, an example proportion manager 228 and an example distribution engine 230.

In operation, the example PM interface 202 acquires people meter data from any and all PMs within the example panelist households 104. In particular, the example PM interface 202 acquires PM data from the PM devices located in the example MMPM households 106 (i.e., households that have both MM devices and PM devices). The PM devices have input (s) (e.g., buttons for each household member to select to identify their respective presence in the audience currently exposed to media). In some examples, the MMPM households 106 are associated with a particular geographic area of focus, such as nationwide (sometimes referred to as a “National People Meter” (NPM)), while in other examples the MMPM households 106 are associated with a subset of a particular geographic area of focus, such as a localized geography of interest (e.g., a city within a nation (e.g., Chicago), and sometimes referred to as “Local People Meter” (LPM)).

For example, in the event an analysis of the Charlotte designated market area (DMA) is desired, then the example PM interface 202 captures data from LPM households within a time zone corresponding to the desired DMA (e.g., the Eastern time zone). In some examples, desired data may be streamed back to one or more storage repositories, from which the example imputation engine 110, the example ambient tuning engine 120 and/or the example on/off detection engine 130 may retrieve the data. The example PM interface 202 of the illustrated examples collects, acquires and/or otherwise captures PM data (panelist audience data) from panelist households 104 (having both PMs and MMs) and records or aggregates the media exposure minutes to respective persons within the household as one or more of the possible audience members (e.g., viewers) of the corresponding media. In other words, the captured panelist audience data is at a persons-level rather than at a household level, which facilitates an ability to generate person probabilities, as described in further detail below.

The example categorizer 206 of FIG. 2 categorizes the acquired panelist audience data in any number of categories, such as by age, by gender, by whether a household is of size one (e.g., a single person household) or of size two or more (e.g., two or more persons in the household), by a station/affiliate, by a genre and/or by daypart. In some examples, categories include those related to race, ethnicity, geography,

language, metro vs. non-metro, etc. In still other examples, categories include an age of the head of household, a room location (e.g., a living room, a master bedroom, other bedroom, etc.), and/or the presence of children. In the event one or more categories improve results, it may be used for analysis, while categories that do not illustrate improvements or cause negative impacts may be removed during the analysis.

As used herein, categories refer to classifications associated with collected exposure minutes (also known as “viewing minutes”). Categories may include, but are not limited to, a daypart associated with collected exposure minutes (e.g., Monday through Friday from 5:00 AM to 6:00 AM, Sunday from 10:00 PM to 1:00 AM, etc.), a station associated with collected exposure minutes (e.g., WISN, WBBM, etc.), an age/gender associated with collected exposure minutes (e.g., males age 2-5, females age 35-44, etc.), and a genre (e.g., kids programs, home repair programs, music programs, sports programs, etc.) associated with collected exposure minutes. In still other examples, the categorizer 206 categorizes the acquired panelist audience data by education (e.g., 8 years or less, 9 years to high school graduate, some college to Bachelor degree, master’s degree or higher, etc.), life stage (e.g., pre-family, young family, older family, post family, retired, etc.) and/or a number of media presentation devices (e.g., television sets in the household. One or more combinations of station/affiliate/genre/demographic attribute(s) may be categorized in different ways based on, for example, variations between data available for one or more age/gender levels. For example, some local markets have ten stations in which a sample size for men age 45-54 may exhibit a data sample size of statistical significance for seven of those ten stations. In other examples, a local market may have relatively fewer stations where the age/gender levels are of sufficient size to support statistical significance. In some such examples, the age/gender groupings are adjusted (e.g., from males age 40-45 to males age 40-50) to increase an available sample size to achieve a desired statistical significance.

To impute panelist audience data (e.g., exposure minutes, which is sometimes referred to herein as “viewing minutes”) to media data, the example PM interface 202 identifies Local People Meter (LPM) data that has been collected within a threshold period of time. On a relative scale, when dealing with, for example, television exposure, an exposure index, which provides an indication of how well LPM data accurately imputes exposure minutes, may be computed in a manner consistent with Equation (1).

Exposure Index = Equation (1)

$$\frac{\text{No. of imputed LPM exposure min. for ea. cat.}}{\text{No. of actual LPM exposure min. for ea. cat.}}$$

In the illustrated example of Equation (1), the exposure index is calculated as the ratio of the number of imputed LPM viewing minutes for each category of interest and the number of actual LPM viewing minutes for each category of interest.

The example exposure index of Equation (1) may be calculated on a manual, automatic, periodic, aperiodic and/or scheduled basis to empirically validate the success and/or accuracy of imputation efforts disclosed herein. Index values closer to one (1) are indicative of a greater degree of accuracy when compared to index values that deviate from one (1). Depending on the type of category associated with the collected exposure minutes, corresponding exposure index val-

ues may be affected to a greater or lesser degree based on the age of the collected data. FIG. 3 is an example plot 300 of exposure index values by daypart. In the illustrated example of FIG. 3, the plot 300 includes an x-axis of daypart values 302 and a y-axis of corresponding exposure index values 304. Index value data points labeled “1-week” appear to generally reside closer to index values of 1.00, while index value data points labeled “3-weeks” appear to generally reside further away from index values of 1.00. In other words, panelist audience data that has been collected more recently results in index values closer to 1.00 and, thus, reflects an imputation accuracy better than panelist audience data that has been collected from longer than 1-week ago.

As described above, collected data that is more recent exhibits an imputation accuracy that is better than an imputation accuracy that can be achieved with relatively older collected data. Nonetheless, some data that is relatively older will still be useful, but such older data is weighted less than data that is more recent to reflect its lower accuracy. The example weighting engine 210 applies a temporal weight, and applies corresponding weight values by a number of days since the date of collection. Relatively greater weight values are applied to data that is relatively more recently collected. In some examples, weight values applied to collected tuning minutes and collected exposure minutes are based on a proportion of a timestamp associated therewith. For instance, a proportionally lower weight may be applied to a portion of collected minutes (e.g., tuning minutes, exposure minutes) when an associated timestamp is relatively older than a more recently collection portion of minutes.

FIG. 4 illustrates an example weighting allocation table 400 generated and/or otherwise configured by the example weighting engine 210. In the illustrated example of FIG. 4, a MMPM household 106 acquired exposure minutes (i.e., individualized panelist audience data) via a PM device (row “A”), and acquired household tuning minutes (i.e., minutes tuned in a household without individualizing to a specific person within that household) via a MM device (row “B”). The example individualized panelist audience and household tuning minutes are collected over a seven (7) day period. In that way, the most recent day (current day 402) is associated with a weight greater than any individualized panelist audience and/or household tuning minutes from prior day(s). The example individualized panelist minutes of row “A” may be further segmented in view of a desired category combination for a given household. As described above, categories that characterize a household may include a particular age/gender, size of household, viewed station, daypart, number of televisions, life stage, education level and/or other demographic attribute(s). For purposes of illustration, examples described below, the household age/gender category for the household is male, age 45-54, the tuned station is associated with a premium pay channel (genre) during the daypart associated with Monday through Friday between 6:00 PM and 7:00 PM.

In the illustrated example of FIG. 4, the weighting engine 210 applies a unitary weight value to the first six (6) days of individualized panelist minutes and household tuning minutes, and applies a weight value of six (6) to the most current day. While a value of six (6) is disclosed above, like the other values used herein, such value is used for example purposes and is not a limitation. In operation, the example weighting engine 210 of FIG. 2 may employ any weighting value in which the most current day value is relatively greater than values for one or more days older than the current day. The example weighting engine 210 may generate a weighted sum of the collected individualized panelist audience exposure minutes (hereinafter referred to herein as “exposure min-

utes”) in a manner consistent with example Equation (2), and may generate a weighted sum of the collected household tuning minutes in a manner consistent with example Equation (3).

$$\text{Exposure Min.} = \left[W_1 \left(\sum_{d=1}^n EM_d \right) \right] + [W_2 EM_c] \quad \text{Equation (2)}$$

$$\text{Tuning Min.} = \left[W_1 \left(\sum_{d=1}^n TM_d \right) \right] + [W_2 TM_c] \quad \text{Equation (3)}$$

In the illustrated examples of Equation (2) and Equation (3), W_1 reflects a relatively lower weighting value than W_2 , in which W_2 is the weighting value associated with the current day exposure minutes value. Additionally, d reflects one of n days of the collected data prior to the current day, EM_d reflects exposure minutes for corresponding days prior to the current day, TM_d reflects household tuning minutes for corresponding days prior to the current day, EM_c reflects exposure minutes for the current day, and TM_c reflects household tuning minutes for the current day.

In connection with example data shown in the illustrated example of FIG. 4 (e.g., days one through six having 20, 10, 10, 0, 0 and 10 exposure minutes, respectively, the current day having 40 exposure minutes, days one through six having 40, 30, 50, 0, 0 and 30 household tuning minutes and the current day having 50 household tuning minutes), application of example Equation (2) results in a weighted exposure minutes value of 290 and application of example Equation (3) results in a weighted household tuning minutes value of 450. In some examples, the probability engine 212 calculates an imputation probability that a MM panelist (e.g., a panelist household with only a MM device and no associated PM device) with the aforementioned category combination of interest (e.g., male, age 45-54 tuned to a premium pay channel during Monday through Friday between the daypart of 6:00 PM and 7:00 PM) is actually viewing this tuning session. The imputation probability is calculated by the example probability engine 212 by dividing the weighted exposure minutes (e.g., 290 minutes) by the weighted household tuning minutes (e.g., 450 minutes) to yield a 64.4% chance that the MM panelist with this same household category combination is associated with this tuning behavior. While examples disclosed herein refer to probability calculations, in some examples odds may be calculated to bound results between values of zero and one. For example, odds may be calculated as a ratio of a probability value divided by (1-Probability). If desired, the odds may be converted back to a probability representation.

However, while the market researcher may have a particular category combination of interest, a corresponding probability value accuracy may be improved when different probability calculation techniques are applied in view of corresponding available sample sizes of households sharing the particular category combination of interest. As described in further detail below, if collected LPM data associated with the category combination of interest (e.g., male, age 45-54, tuned to premium channel during 6:00 PM to 7:00 PM with three household members, one television and the head of household have some college credit or a bachelor’s degree) is greater than a threshold value, then a cell probability technique may yield a probability value with acceptable accuracy. As used herein, an acceptable accuracy relates to a sample size that is capable and/or otherwise required to establish results having a statistical significance. However, in the event

11

the collected Local People Meter (LPM) data associated with the category combination of interest falls below the threshold value, then the cell probability technique yields unacceptably low probability value accuracy. Instead, example methods, apparatus, systems and/or articles of manufacture disclosed herein employ independent distribution probability calculations when the collected LPM data associated with the category combination of interest is below a threshold value, such as below a threshold value that is capable of facilitating one or more calculations to yield results having statistical significance.

The example category manager **214** of FIG. 2 identifies categories and/or a category combinations of interest and determines whether the particular category combination of interest has a threshold number of households within a donor pool. As described above, the donor pool may be a localized geography (a Local People Meter (LPM), such as the panelist households within the geographic region of interest **104**). However, as a geographic region of interest decreases in size, a corresponding number of qualifying households that match the category combination of interest also decreases. In some cases, the number of qualifying households is below a threshold value, which causes one or more traditional probability calculation methods (e.g., cell probability) to exhibit poor predictive abilities and/or results that fail to yield statistical significance. On the other hand, in the event the donor pool of households exceeds a threshold value count, then such traditional probability calculation methods (e.g., cell probability) exhibit satisfactory predictive capabilities under industry standard(s).

In operation, the example category manager **214** of FIG. 2 generates a logical “AND” condition test for a set of categories of interest. For example, if the categories of interest include (1) a particular station, (2) a particular daypart, (3) a particular number of household members, (4) a particular age, (5) a particular gender, (6) a particular number of television sets in the household, (7) a particular education level of the head of household, and (8) a particular life stage, then the category manager **214** determines whether the combination of all eight categories of interest are represented by a threshold number of households within the donor pool. If so, then the example category manager **214** invokes the example cell probability engine **216** to calculate a probability value of the category combination occurring within MMH households **108**. Generally speaking, when a number of households sharing the combination of categories of interest (e.g., items (1) through (8) above) are greater than the threshold value, a corresponding level of confidence in probability calculation via the cell probability technique is deemed satisfactory.

In the event a market researcher seeks probability information for a male aged **50** watching a premium pay channel between the hours of 6:00 PM and 6:30 PM, the example category fit manager **220** of the illustrated example identifies which previously established category groups already exist that would best fit this desired task. In other words, the specific and/or otherwise unique research desires of the market researcher may not align exactly with existing categorical groups collected by LPM and/or NPM devices. Instead, the example category fit manager **220** identifies that the closest categorical combination of industry standard and/or otherwise expected data is with males age 45-54 between the hours of 6:00 PM and 7:00 PM. The example minutes aggregator **222** of the illustrated example identifies a total number of household tuning minutes in all households associated with the identified closest categorical combination, and also identifies a total number of exposure minutes associated with the males age 45-54 in such households. For example, the min-

12

utes aggregator **222** may identify forty-five (45) qualifying households that have males 45-54 (e.g., the household could have more than just the males 45-54) in which a premium pay genre station was tuned between the hours of 6:00 PM to 7:00 PM, three household members with one television set and a head of household having some college credit or bachelor's degree.

Within these forty-five (45) qualifying households, the tuning minutes aggregator **222** may identify two-hundred (200) household tuning minutes total, but only one hundred and two (102) of those minutes were associated with the males 45-54. The example imputation engine **224** of the illustrated example calculates a probability for imputation as the ratio of exposure minutes for the males 45-54 and the total household tuning minutes for all qualifying households in a manner consistent with example Equation (4).

$$\text{Probability of Imputation} = \frac{\text{Exposure minutes by Persons of Interest}}{\text{Tuning Minutes of Qualifying Households}} \quad \text{Equation (4)}$$

In the illustrated example of Equation (4), the probability of imputation using the examples disclosed above is 0.51 (i.e., 102 exposure minutes divided by 200 tuning minutes, in this example). In some examples, the probability value calculated by the example cell probability engine **216** is retained and/or otherwise imputed to MMH households **108** based on a normal distribution, such as a comparison of the calculated probability value to a random or pseudo-random number. In the event the calculated probability value is greater than the random number, then the household member having the categorical combination of interest is credited as viewing a tuning segment. In other words, the household tuning data is imputed to the MMH household **108** as exposure data for the categorical combination of interest. On the other hand, in the event the calculated probability value is less than the random or pseudo-random number, then the household member having the categorical combination of interest is not credited as viewing the tuning segment. In other words, the household tuning data is not imputed to the MMH household **108**.

As discussed above, when the combinations of all categories of interest are represented by a number of households less than a threshold value within the donor pool, the cell probability calculation approach may not exhibit a level of confidence deemed suitable for statistical research. Generally speaking, a number of households in a research geography of interest matching a single one of the categories of interest may be relatively high. However, as additional categories of interest are added, the number of households having an inclusive match for all such categories decreases. In some circumstances, the number of matching households available in the donor pool after performing a logical “AND” of all categories of interest eventually results in a donor pool having a population lower than a threshold value, which may not exhibit statistical confidence when applying the cell probability technique described above. In such examples, the probability engine **212** prevents a traditional cell probability technique from being employed to calculate a probability of whether a household of interest should be credited with exposure behavior for the categorical combination of interest (e.g., whether the male age 45-54 of the household should be credited with captured exposure (tuning) behavior of the household). Instead, the example probability engine **212** invokes the example independent distribution engine **218** when the number of households having the desired combination of category

13

ries of interest is below a threshold value. As described in further detail below, instead of using a pool of households that match all categories of interest, households are employed that match some of the categories of interest are used when calculating a probability of viewing.

In operation, the example category qualifier **226** of FIG. 2 identifies all households within the donor pool (e.g., within the LPM collection geography, such as the Charlotte DMA) that have the same set of key predictors (i.e., particular categories within the set of categories of interest). In some examples, key predictors reflect a set of categories that exhibit a relatively greater degree of success than other combinations of categories. For instance, a first set of key predictors may include a first set of categories related to a geography of interest, such as sunscreen products in geographic vicinity to ocean vacation areas, or skiing products in geographic vicinity to mountain ranges. While examples disclosed herein refer to a Local People Meter (LPM), such examples are not limited thereto. In some examples, a National People Meter (NPM) may be employed as a collection geography that reflects a relatively larger area, such as a nation. In particular, a subset of the example eight (8) original categories of interest may include (1) households matching a household size category, (2) households matching a same member gender category, and (3) households matching a same member age category. In other words, while the original eight example categories of interest included the aforementioned three categories, the remaining categories are removed from consideration when identifying households from the available data pool. For example, the remaining categories are removed that are related to (4) households matching a same tuned station category, (5) households matching a same education category, (6) households matching a same number of television sets category, (7) households matching a same daypart category, and (8) households matching a same life stage/household size category.

Because, in the illustrated example, the donor pool is constructed with only MMPM households **106**, the example category qualifier **226** retrieves and/or otherwise obtains a total household tuning minutes value and a total exposure minutes value for the available households meeting the size/gender/age criteria of interest (e.g., dimensions (1), (2) and (3) from above). For example, if the size/gender/age criteria of interest is for a household size of two or more people having a male age 45-54, then the example category qualifier **226** identifies a number of households from that size/gender/age subset.

FIG. 5 illustrates an example category subset map **500** created by the independent distribution engine **226** of the example of FIG. 2. The example independent distribution engine assembles household tuning minutes and exposure minutes from subsets of the categories of interest. In the illustrated example of FIG. 5, the map **500** includes a total household tuning minutes count and a total exposure minutes count associated with the key predictor categories **502** of size/age/gender. In this example, the category qualifier **226** identified a total of two-hundred (200) households matching the size/gender/age criteria. The two-hundred households include a total of 4500 tuning minutes (i.e., minutes that identify a tuned station but do not identify a corresponding household member) and a total of 3600 exposure minutes (e.g., minutes for an identified station and also identified individuals who were present in the audience).

The example proportion manager **228** of FIG. 2 selects one or more remaining categories of interest that fall outside the key predictor categories to determine corresponding available matching households, household tuning minutes and exposure minutes. The example remaining categories may be

14

referred to as secondary predictors or secondary categories that affect the probability of media exposure. While example key predictor categories disclosed herein include household size, gender and age, example methods, apparatus, systems and/or articles of manufacture may include any other, additional and/or alternate type(s) of categories for the key predictors. Additionally, while example secondary categories disclosed herein include tuned station, education, number of media presentation devices (e.g., TV sets), daypart and life-stage, example methods, apparatus, systems and/or articles of manufacture may additionally and/or alternatively include any other type of categories as the secondary categories.

For example, the proportion manager **228** of the illustrated example selects one or more secondary categories to determine a corresponding number of matching households, household tuning minutes and exposure minutes. Again, and as described above, the temporal units of “minutes” are employed herein as a convenience when discussing example methods, apparatus, systems and/or articles of manufacture disclosed herein, such that one or more additional and/or alternative temporal units (e.g., seconds, days, hours, weeks, etc.) may be considered, without limitation. In the illustrated example of FIG. 5, a tuned station category **504** (e.g., one of the secondary categories of interest) is identified by the proportion manager **228** to have eighty (80) households, which match the desired station of interest (e.g., station “WAAA”), in which those households collected 1800 household tuning minutes and 1320 exposure minutes. Additionally, the example proportion manager **228** of FIG. 2 selects an education category **506** (e.g., one of the secondary categories of interest) and determines that one-hundred and ten (110) households match the desired education level of interest (e.g., households in which the head of household has 9 years of school to high school graduation), in which those households collected 1755 household tuning minutes and 1200 exposure minutes. Further, the example proportion manager **228** of FIG. 2 selects a number of television sets category **508** (e.g., one of the secondary categories of interest) and determines that one-hundred (100) households match the desired number of TV sets within a household value, in which those households collected 2100 household tuning minutes and 1950 exposure minutes. Other example categories considered by the example proportion manager **228** of FIG. 2 include a daypart category **510** (e.g., one of the secondary categories of interest), in which the proportion manager **228** of FIG. 2 determines that one-hundred (100) households match the desired daypart category, in which those households collected 1365 household tuning minutes and 825 exposure minutes. The example proportion manager **228** of FIG. 2 also selects a life stage/household size category **512** (e.g., one of the secondary categories of interest) and determines that seventy (70) households match the desired type of life stage/household size value, in which those households collected 1530 household tuning minutes and 1140 exposure minutes.

Generally speaking, the proportion manager **228** of the illustrated example identifies secondary category contributions of household tuning minutes and exposure minutes independently from the household tuning and exposure minutes that may occur for only such households that match all of the desired target combination of categories of interest. After each individual secondary category contribution household tuning minute value and exposure minute value is identified, the example distribution engine **230** calculates a corresponding household tuning proportion and exposure proportion that is based on the key predictor household tuning and exposure minute values. As described in further detail below, the example distribution engine **230** calculates a household tun-

15

ing proportion and an exposure proportion associated with each of the secondary categories of interest (e.g., the tuned station category **504**, the education category **506**, the number of sets category **508**, the daypart category **510** and the life stage/size category **512**). In other words, examples disclosed herein capture, calculate and/or otherwise identify contributory effects of one or more secondary categories of interest by calculating and/or otherwise identifying a separate corresponding tuning proportion and separate corresponding exposure proportion for each one of the secondary categories. As described in further detail below, separate contributory effects of the one or more secondary categories are aggregated to calculate expected tuning minutes and expected exposure minutes.

In the illustrated example of FIG. 5, the distribution engine **230** divides the household tuning minutes associated with the tuned station category **504** (e.g., 1800 household tuning minutes) by the total household tuning minutes associated with the key predictor categories **502** (e.g., 4500 household tuning minutes) to calculate a corresponding tuned station category tuning proportion **514**. Additionally, the distribution engine **230** of the illustrated example divides the exposure minutes associated with the tuned station category **504** (e.g., 1320 exposure minutes) by the total exposure minutes associated with the key predictor categories **502** (e.g., 3600 household viewing minutes) to calculate a corresponding tuned station category viewing proportion **516**. For the sake of example, the calculated tuned station category tuning proportion **514** is 0.40 (e.g., 1800 household tuning minutes divided by 4500 total exposure minutes) and the calculated tuned station category viewing proportion **516** is 0.37 (e.g., 1320 exposure minutes divided by 3600 total exposure minutes).

The example distribution engine **230** of FIG. 2 also calculates a household tuning proportion and exposure proportion in connection with the example education category **506**. In the illustrated example of FIG. 5, the distribution engine **230** divides the household tuning minutes associated with the education category **504** (e.g., 1755 household tuning minutes) by the total household tuning minutes associated with the key predictor categories **502** (e.g., 4500 household tuning minutes) to calculate a corresponding education category household tuning proportion **518**. Additionally, the example distribution engine **230** of the illustrated example divides the exposure minutes associated with the education category **506** (e.g., 1200 exposure minutes) by the total exposure minutes associated with the key predictor categories **502** (e.g., 3600 exposure minutes) to calculate a corresponding education category exposure proportion **520**. For the sake of example, the calculated education category household tuning proportion **518** is 0.39 (e.g., 1755 household tuning minutes divided by 4500 total household tuning minutes) and the calculated education category exposure proportion **520** is 0.33 (e.g., 1200 exposure minutes divided by 3600 total exposure minutes).

The example distribution engine **230** of FIG. 2 also calculates a household tuning proportion and exposure proportion in connection with the example household sets category **508**. In the illustrated example of FIG. 5, the distribution engine **230** divides the household tuning minutes associated with the household sets category **508** (e.g. 2100 household tuning minutes) by the total household tuning minutes associated with the key predictor categories **502** (e.g., 4500 household tuning minutes) to calculate a corresponding household sets category household tuning proportion **522**. Additionally, the example distribution engine **230** of the illustrated example divides the exposure minutes associated with the household sets category **508** (e.g., 1950 exposure minutes) by the total

16

exposure minutes associated with the key predictor categories **502** (e.g., 3600 exposure minutes) to calculate a corresponding household sets category exposure proportion **524**. For the sake of example, the calculated household sets category household tuning proportion **522** is 0.47 (e.g., 2100 household tuning minutes divided by 4500 total household tuning minutes) and the calculated household sets category exposure proportion **524** is 0.54 (e.g., 1950 exposure minutes divided by 3600 total exposure minutes).

The example distribution engine **230** of FIG. 2 also calculates a household tuning proportion and exposure proportion in connection with the example daypart category **510**. In the illustrated example of FIG. 5, the distribution engine **230** divides the household tuning minutes associated with the daypart category **510** (e.g., 1365 household tuning minutes) by the total household tuning minutes associated with the key predictor categories **502** (e.g., 4500 household tuning minutes) to calculate a corresponding daypart category household tuning proportion **526**. Additionally, the example distribution engine **230** of FIG. 2 divides the exposure minutes associated with the daypart category **510** (e.g., 825 exposure minutes) by the total exposure minutes associated with the key predictor categories **502** (e.g., 3600 exposure minutes) to calculate a corresponding daypart category exposure proportion **528**. For the sake of example, the calculated daypart category household tuning proportion **526** is 0.30 (e.g., 1365 household tuning minutes divided by 4500 total household tuning minutes) and the calculated daypart category exposure proportion **528** is 0.23 (e.g., 825 exposure minutes divided by 3600 total exposure minutes).

The example distribution engine **230** of FIG. 2 also calculates a household tuning proportion and exposure proportion in connection with the example life stage/size category **512**. In the illustrated example of FIG. 5, the distribution engine **230** divides the household tuning minutes associated with the life stage/size category **512** (e.g. 1530 household tuning minutes) by the total household tuning minutes associated with the key predictor categories **502** (e.g., 4500 household tuning minutes) to calculate a corresponding life stage/size category household tuning proportion **530**. Additionally, the example distribution engine **230** of FIG. 2 divides the exposure minutes associated with the life stage/size category **512** (e.g., 1140 exposure minutes) by the total exposure minutes associated with the key predictor categories **502** (e.g., 3600 exposure minutes) to calculate a corresponding life stage/size category exposure proportion **532**. In this example, the calculated life stage/size category tuning proportion **530** is 0.34 (e.g., 1530 household tuning minutes divided by 4500 total household tuning minutes) and the calculated life stage/size category exposure proportion **532** is 0.32 (e.g., 1140 exposure minutes divided by 3600 total exposure minutes).

As described above, each of the target combinations of categories of interest has an independently calculated household tuning proportion value and an independently calculated exposure proportion value. The example distribution engine **230** of FIG. 2 calculates the product of all household tuning proportion values (e.g., the tuned station category household tuning proportion **514**, the education category household tuning proportion **518**, the household sets category household tuning proportion **522**, the daypart category household tuning proportion **526**, and the life stage/size category household tuning proportion **530**) to determine total expected household tuning minutes **534**. Additionally, the example distribution engine **230** of FIG. 2 calculates the product of all household exposure proportion values (e.g., the tuned station category exposure proportion **516**, the education category exposure proportion **520**, the household sets category exposure propor-

17

tion 524, the daypart category exposure proportion 528, and the life stage/size category exposure proportion 532) to determine total expected exposure minutes 536. A final independent distribution is calculated by the example distribution engine 230 in a manner consistent with example Equation (5), and reflects a panelist behavior probability associated with the target combination of categories of interest.

$$\text{Independent Distribution Probability} = \frac{\text{Expected Exposure Minutes}}{\text{Expected Household Tuning Minutes}} \quad \text{Equation (5)}$$

In the example exposure and household tuning minutes discussed above, the resulting independent distribution probability is 0.52. In effect, the resulting independent distribution probability is interpreted as a male 45-54 who lives in a three (3) person household, classified as an older family, with a head of house education of nine (9) years to high school graduate, with two (2) television sets in the household, has a 52% likelihood of watching station WAAA during the daypart of Monday through Friday from 9:00 AM to 12:00 PM.

While an example manner of implementing the imputation engine 110 of FIG. 1 is illustrated in FIGS. 2-5, one or more of the elements, processes and/or devices illustrated in FIG. 2 may be combined, divided, re-arranged, omitted, eliminated and/or implemented in any other way. Additionally, while an example manner of implementing the visitor imputation engine 112 of FIGS. 1, 2 and 11, and described in further detail below, one or more of the elements, processes and/or devices illustrated in FIG. 11 may be combined, divided, rearranged, omitted, eliminated and/or implemented in any other way. Additionally, while an example manner of implementing the ambient tuning engine 120 and the example on/off detection engine 130 of FIG. 1 is illustrated in FIGS. 10 and 15, respectively, and as described in further detail below, one or more of the elements, processes and/or devices illustrated in FIGS. 10 and 15 may be combined, divided, rearranged, omitted, eliminated and/or implemented in any other way. Further, the example people meter interface 202, the example categorizer 206, the example weighting engine 210, the example media meter interface 204, the example probability engine 212, the example category manager 214, the example cell probability engine 216, the example category fit manager 220, the example minutes aggregator 222, the example imputation engine 224, the example independent distribution engine 218, the example category qualifier 226, the example proportion manager 228, the example distribution engine 230 and/or, more generally, the example imputation engine 110 and/or the example visitor imputation engine 112 of FIG. 1 may be implemented by hardware, software, firmware and/or any combination of hardware, software and/or firmware. Additionally, an example average visitor parameter (AVP) calculator 1102, an example distribution engine 1104, an example random number generator 1106, an example visitor assignor 1108, an example simultaneous tuning monitor 1602, an example crediting manager 1604, an example station comparator 1606, an example tuning type assignor 1608, an example automatic gain control monitor 1610, an example code presence manager 1612, an example modeling engine 1614, an example code stacking manager 1616 and/or, more generally, the example ambient tuning engine 120 of FIGS. 1 and 16 may be implemented by hardware, software, firmware and/or any combination of hardware, software and/or firmware. Thus, for example, any of the example people meter interface 202, the example categorizer

18

206, the example weighting engine 210, the example media meter interface 204, the example probability engine 212, the example category manager 214, the example cell probability engine 216, the example category fit manager 220, the example minutes aggregator 222, the example imputation engine 224, the example independent distribution engine 218, the example category qualifier 226, the example proportion manager 228, the example distribution engine 230, the example average visitor parameter (AVP) calculator 1102, an example distribution engine 1104, an example random number generator 1106, an example visitor assignor 1108, the example simultaneous tuning monitor 1602, the example crediting manager 1604, the example station comparator 1606, the example tuning type assignor 1608, the example automatic gain control monitor 1610, the example code presence manager 1612, the example modeling engine 1614, the example code stacking manager 1616 and/or, more generally, the example imputation engine 110, the example visitor imputation engine 112, the example ambient tuning engine 120, and/or the example on/off detection engine 130 of FIG. 1 could be implemented by one or more analog or digital circuit(s), logic circuits, programmable processor(s), application specific integrated circuit(s) (ASIC(s)), programmable logic device(s) (PLD(s)) and/or field programmable logic device(s) (FPLD(s)).

When reading any of the apparatus or system claims of this patent to cover a purely software and/or firmware implementation, at least one of the example people meter interface 202, the example categorizer 206, the example weighting engine 210, the example media meter interface 204, the example probability engine 212, the example category manager 214, the example cell probability engine 216, the example category fit manager 220, the example minutes aggregator 222, the example imputation engine 224, the example independent distribution engine 218, the example category qualifier 226, the example proportion manager 228, the example distribution engine 230, the example average visitor parameter (AVP) calculator 1102, an example distribution engine 1104, an example random number generator 1106, an example visitor assignor 1108, the example simultaneous tuning monitor 1602, the example crediting manager 1604, the example station comparator 1606, the example tuning type assignor 1608, the example automatic gain control monitor 1610, the example code presence manager 1612, the example modeling engine 1614, the example code stacking manager 1616 and/or, more generally, the example imputation engine 110, the example visitor imputation engine 112, the example ambient tuning engine 120, and/or the example on/off detection engine 130 of FIG. 1 is/are hereby expressly defined to include a tangible computer readable storage device or storage disk such as a memory, a digital versatile disk (DVD), a compact disk (CD), a Blu-ray disk, etc. storing the software and/or firmware. Further still, the example imputation engine 110, the example visitor imputation engine 112, the example ambient tuning engine 120, and/or the example on/off detection engine 130 of FIGS. 1, 2, 11, 16 and/or 21 may include one or more elements, processes and/or devices in addition to, or instead of, those illustrated in FIGS. 2, 11, 16 and/or 21 and/or may include more than one of any or all of the illustrated elements, processes and devices.

Flowcharts representative of example machine readable instructions for implementing the imputation engine 110, the visitor imputation engine 112, the ambient tuning engine 120 and the on/off detection engine 130 of FIGS. 1, 2, 11, 16 and 21 are shown in FIGS. 6-9, 15, 17-19 and 22. In these examples, the machine readable instructions comprise program(s) for execution by a processor such as the processor

19

2312 shown in the example processor platform 2300 discussed below in connection with FIG. 23. The program(s) may be embodied in software stored on a tangible computer readable storage medium such as a CD-ROM, a floppy disk, a hard drive, a digital versatile disk (DVD), a Blu-ray disk, or a memory associated with the processor 2312, but the entire program(s) and/or parts thereof could alternatively be executed by a device other than the processor 2312 and/or embodied in firmware or dedicated hardware. Further, although the example program(s) is/are described with reference to the flowcharts illustrated in FIGS. 6-9, 15, 17-19 and 22, many other methods of implementing the example imputation engine 110, the example visitor imputation engine 112, the example ambient tuning engine 120 and/or the example on/off detection engine 130 may alternatively be used. For example, the order of execution of the blocks may be changed, and/or some of the blocks described may be changed, eliminated, or combined.

As mentioned above, the example processes of FIGS. 6-9, 15, 17-19 and 22 may be implemented using coded instructions (e.g., computer and/or machine readable instructions) stored on a tangible computer readable storage medium such as a hard disk drive, a flash memory, a read-only memory (ROM), a compact disk (CD), a digital versatile disk (DVD), a cache, a random-access memory (RAM) and/or any other storage device or storage disk in which information is stored for any duration (e.g., for extended time periods, permanently, for brief instances, for temporarily buffering, and/or for caching of the information). As used herein, the term tangible computer readable storage medium is expressly defined to include any type of computer readable storage device and/or storage disk and to exclude propagating signals and to exclude transmission media. As used herein, "tangible computer readable storage medium" and "tangible machine readable storage medium" are used interchangeably. Additionally or alternatively, the example processes of FIGS. 6-9, 15, 17-19 and 22 may be implemented using coded instructions (e.g., computer and/or machine readable instructions) stored on a non-transitory computer and/or machine readable medium such as a hard disk drive, a flash memory, a read-only memory, a compact disk, a digital versatile disk, a cache, a random-access memory and/or any other storage device or storage disk in which information is stored for any duration (e.g., for extended time periods, permanently, for brief instances, for temporarily buffering, and/or for caching of the information). As used herein, the term non-transitory computer readable medium is expressly defined to include any type of computer readable storage device and/or storage disk and to exclude propagating signals and to exclude transmission media. As used herein, when the phrase "at least" is used as the transition term in a preamble of a claim, it is open-ended in the same manner as the term "comprising" is open ended.

The program 600 of FIG. 6 begins at block 602 where the example people meter interface 202 acquires PM data associated with household members from the PM devices located in the example MMPM households 106 that have both MM devices and PM devices. As described above, the PM devices have input (s) (e.g., buttons for each household member and a visitor button to identify their respective presence in the audience currently exposed to media). The example PM interface 202 identifies collected data that is within a threshold period of time from a current day in an effort to weight such data according to its relative age. As described above in connection with example Equation (1), an accuracy of the viewing index is better when the corresponding collected data is more recent. The example categorizer 206 categorizes the acquired

20

PM data based on one or more categories of interest (block 604). In some examples, the categorizer 206 categorizes and/or otherwise identifies particular households associated with one or more categories, such as an age/gender combination of interest, a particular household size of interest, a particular life stage of interest, a particular viewed station/affiliate/genre of interest, a particular daypart of interest, a number of television sets of interest within the household (e.g., households with one television set, households with 2-3 television sets, households with three or more television sets, etc.), and/or an education level of the head of household. While a relatively large number of MMPM households 106 will have at least one of the aforementioned categories, a substantially smaller number of MMPM households 106 will represent all of the target combination of categories of interest to a market researching during a market study.

As described above in connection with FIG. 4, the example weighting engine 210 applies weights in proportions that are based on a number of days since the date of collection of the donor data (block 606). The example media meter interface 204 also acquires household tuning data from media meters in the MMH households 108 (block 608). Depending on whether a threshold number of households exist in the donor pool (e.g., the donor pool of MMPM households in the region of interest 104) that match all of the categories of interest, the example probability engine 212 will invoke a corresponding probability calculation technique (block 610) as described in further detail below in connection with FIG. 7.

FIG. 7 includes additional detail from the illustrated example of FIG. 6. When generating probabilities, the example category manager identifies categories of interest to use. Generally speaking, example methods, apparatus, systems and/or articles of manufacture disclosed herein generate probabilities based on a target combination of categories of interest such as, for example, determining the likelihood of viewing for (1) a male age 45-54 (2) who lives in a three-person household, (3) classified as an older family (4) with the head of the household having an education of nine (9) years of school to high-school graduate, (5) with two television sets in the household and (6) is watching station WAAA (7) between the daypart of 9:00 AM to 12:00 PM. The example category manager 214 identifies categories of interest for which a probability of viewing (exposure) is desired (block 702), such as the example seven categories referred to above. Based on the identified target combination of categories of interest, such as the example above having the male age 45-54 et al., the example category manager 214 determines whether the available pool of data, previously weighted by the example weighting engine 210, includes a threshold number of households that match all (e.g., all seven) of the target combination of categories of interest (block 704).

Assuming, for the sake of example, the threshold number of households to match all of the categories of interest is thirty (30), and the pool of data includes that threshold amount of available households (block 704), the example cell probability engine 216 is invoked by the probability engine 212 to calculate a probability value via a cell probability technique (block 706). On the other hand, if the pool of data does not satisfy the threshold amount of thirty households (e.g., has less than 30 households) (block 704), then the example probability engine 212 invokes the example independent distribution engine 218 to calculate a probability value via an independent distribution technique (block 708).

FIG. 8 illustrates an example manner of implementing the cell probability calculation (block 706) of FIG. 7. In the illustrated example of FIG. 8, the category fit manager 220 culls and/or otherwise limits tuning and viewing data to fit

21

previously established categories (block 802). As described above, in the event a market researcher has an interest for a male age 50, industry standard panelist data acquisition techniques may not exactly fit the desired demographic category. Instead, the industry standard available data may be categorized in terms of males between an age range of 45-54. Because the desired category of interest is for a male age 50, the example category fit manager 220 identifies the closest relevant category grouping that will satisfy the market researcher, which in this example, includes the group of men between the ages of 45-54. The example minutes aggregator 222 identifies a total number of household tuning minutes from the selected category (block 804) and identifies a total number of exposure minutes from the selected category (block 806). In other words, of all the households that match the categories of men age 45-54, the total number of household tuning minutes and exposure minutes are identified.

The example imputation engine 224 of FIG. 2 calculates a probability for imputation based on the aforementioned totals (block 808). As described above, the probability of imputation may be calculated by the example imputation engine 224 in a manner consistent with example Equation (4). The example imputation engine 224 invokes a random number generator to generate a random or pseudo-random number (block 810) and, if the resulting random or pseudo-random number is less than or equal to the probability value (block 812), a household member within a household having a media meter 108 is assigned as a viewer of the tuning segment (block 814). On the other hand, in the event the resulting random or pseudo-random number is not less than or equal to the probability value, then the household member within the household having the media meter 108 is not assigned as a viewer of the tuning segment (block 816).

Returning to block 704 of FIG. 7, and continuing with the assumption that the threshold number of households to match all of the categories of interest is thirty (30), and the pool of data fails to include that threshold number of qualifying households (block 704), then the example independent distribution engine 218 is invoked by the probability engine 212 to calculate a probability value via an independent distribution technique (block 710).

FIG. 9 illustrates an example implementation of the independent distribution probability calculation (block 708) of FIG. 7. In the illustrated example of FIG. 9, the category qualifier 226 identifies all panelist households (e.g., LPM, NPM, etc.) within the donor pool that have the same set of key predictors (block 902). Additionally, the example category qualifier 226 identifies a corresponding number of total tuning minutes associated with the key predictors, and a corresponding number of total household exposure minutes associated with the key predictors. As described above, key predictors may refer to a particular combination of a household size, a gender of interest within the household, and/or an age of interest within the household. For example, the category qualifier 226 may identify all households within the donor pool that have two or more household members, in which one of them is a male age 45-54. For illustration purposes, assume the example category qualifier identified two hundred (200) households that have two or more members therein, in which one of them is a male age 45-54. Also assume that the combined number of identified households (200) reflect 4500 total household tuning minutes and 3600 total exposure minutes.

In addition to key predictors having an influence on the probability of viewing, one or more additional secondary predictors may also influence the probability of viewing. As described above, the market researcher may have a combined

22

set or target combination of categories of interest, but a number of households having all of those combined set of categories of interest does not exceed a threshold value (e.g., thirty (30) households). However, while the combined set of categories of interest may not be represented en masse from the donor pool, sub portions of the combined set or target combination of categories may include a relatively large representation within the donor pool. Example methods, apparatus, systems and/or articles of manufacture disclosed herein identify independent sub portions (subgroups) of the combined set of categories of interest and corresponding households associated with each subgroup of interest, which are applied independently to calculate a household exposure probability.

The example proportion manager 228 identifies a number of households from the key predictors group (e.g., 200 households having a size 2+ and a male age 45-54) that match a subgroup of interest (block 904). From the subgroup of interest, the example proportion manager 228 identifies a number of household tuning minutes and divides that value by the total household tuning minutes to calculate a household tuning proportion associated with the subgroup of interest (block 906). For example, if the subgroup of interest is all households tuned to the same station (e.g., WAAA) (e.g., the tuned station category) and such households reflect 1800 tuning minutes, then the example proportion manager 228 divides 1800 by the total household tuning minutes of 4500 to calculate a tuned station category household tuning proportion of 0.40 (block 906). The example proportion manager 228 also identifies a number of exposure minutes and divides that value by the total exposure minutes to calculate an exposure proportion associated with the subgroup of interest (e.g., the example tuned station category) (block 908). For example, if the subgroup of interest is all households tuned to the same station (e.g., WAAA) (e.g., the household tuned station dimension) and such households reflect 1320 exposure minutes, then the example proportion manager 228 divides 1320 by the total exposure minutes of 3600 to calculate a tuned station category exposure proportion of 0.37 (block 908). If more subgroups of interest from the donor pool are available (block 910), then the example proportion manager 228 selects the next subgroup of interest (block 912) and control returns to block 904.

After category household tuning proportion values and exposure proportion values have been calculated for each subgroup of interest, the example distribution engine 230 calculates the product of all household tuning proportion values and the total household tuning minutes (e.g., 4500 in this example) from the categories of interest (block 914), and calculates the product of all exposure proportion values and the total exposure minutes (e.g., 3600 in this example) from the categories of interest (block 916). A final independent distribution probability may then be calculated as the ratio of the exposure minutes and the household tuning minutes in a manner consistent with example Equation (5). For example, and as described above in connection with FIG. 5, the resulting ratio of expected exposure minutes (17.47) and expected household tuning minutes (33.65) may be a value of 0.52. This resulting ratio indicates a 52% likelihood that the panelist member is a male age 45-54 that lives in a three person household, classified as an older family, with the head of household education of 9 years to high school graduate, with two television sets in the household, and watching station WAAA on Mondays through Fridays between 9:00 AM to 12:00 PM.

Visitor Imputation

As disclosed above, persons imputation utilizes who is in the household and what the household viewed such that for a

23

given tuning segment, one or more household members may be assigned and/or otherwise associated with exposure. However, panelist households may have visitors that are exposed to media within the household, in which the available visitor information is limited to an age and a gender. As described above, the example PM includes inputs (e.g., buttons) for each household member as well as button(s) for entering age and gender information for any visitors interacting with the media device (e.g., a television). Example methods, apparatus, systems and/or articles of manufacture disclosed herein apply a model to, in view of collected panelist household visitor information, determine a number and corresponding age/gender of visitors for households that do not employ a PM.

Visitor imputation disclosed herein exhibits some similarities to persons imputation, and aspects of FIGS. 1-9 will be referred to in the following disclosure, as necessary. For example, both the persons imputation disclosed above and the visitor imputation disclosed below utilize tuning and exposure information to assign tuning segments and calculate ratios of exposure to tuning minutes. However, the visitor imputation viewing/tuning ratio, being the ratio of total visitor exposure to total household-level tuning exposure, reflects an average count of visitor exposure and not a probability. FIG. 10 further illustrates a manner in which visitor information is processed as compared to household member exposure information.

In the illustrated example of FIG. 10, information for a first household 1002, a second household 1004 and a third household 1006 exhibit twelve, fifteen and eight minutes, respectively, of time tuned by a particular station of interest (as determined by each household with both MM devices and PM devices). While the illustrated example of FIG. 10 only includes three households, such example is for illustrative purposes only and any number of household may be considered. One member of the first household 1002 was exposed to seven minutes out of twelve total tuning minutes, which results in a probability of viewing of 7/12 (58.3%). In the second household 1004, a first member was exposed to the full fifteen minutes, while a second member was exposed to five minutes of the tuned duration, resulting in a probability of viewing of (15+5)/(15+15) (66.7%). In the third household 1006, a first member of that household was exposed to the full eight minutes, resulting in a probability of viewing of 8/8 (100%). An overall viewing probability for the example households is determined in a manner consistent with example Equation 6.

$$\text{Probability Viewed} = \frac{\sum \text{HH Member Exposure Minutes}}{\sum \text{HH Tuning Minutes (by Person)}} \quad \text{Equation 6}$$

In the illustrated example of Equation 6, HH refers to household, and applying the example data from FIG. 10 to Equation 6 is shown in example Equation 7.

$$= \frac{(7) + (15 + 5) + (8)}{(12) + (15 + 15) + (8)} = \frac{35}{50} = .70. \quad \text{Equation 7}$$

In the illustrated example of Equation 7, the households of interest for the example demographic group of males age 25-34 have a viewing probability of 0.70. However, the following analysis of visitors in the same households of interest

24

calculates an average visitor viewing ratio in a manner consistent with example Equation 8.

$$\text{Ave. Visitor Viewing} = \quad \text{Equation 8}$$

$$\frac{\sum \text{Visitor Exposure Minutes for Each Person}}{\sum \text{Household Tuning Minutes}}.$$

Applying the example data from FIG. 10 to Equation 8 is shown in example Equation 9.

$$= \frac{(12 + 10) + (15) + (5)}{(12) + (15) + (8)} = \frac{42}{35} = 1.20. \quad \text{Equation 9}$$

In the illustrated example of Equation 9, the households of interest for the visitors that are reporting male age 25-34 exhibit an average of 1.20 minutes of viewing time for each tuned minute.

FIG. 11 is a schematic illustration of an example implementation of the example visitor imputation engine 112 of FIG. 1. The example visitor imputation engine 112 of FIG. 1 is constructed in accordance with the teachings of this disclosure, and includes an average visitor parameter (AVP) calculator 1102, a distribution engine 1104, a random number generator 1106, and a visitor assignor 1108. As described above, operation of the example visitor imputation engine 112 may occur in conjunction with one or more portions of the example imputation engine 110 of FIGS. 1 and 2. In operation, the example people meter interface 202 acquires PM data associated with visitors, in which the PM data is from the PM devices located in the example MMPM households 106 that have both MM devices and PM devices. The example PM interface 202 identifies collected visitor data that is within a threshold period of time from a current day in an effort to weight such data according to its relative age, as described above in connection with example Equation (1).

The example visitor imputation engine 112 invokes the example categorizer 206 and/or example category qualifier 226 to categorize the acquired PM visitor data based on one or more categories of interest. As described above, for a given category or categories of interest, particular households associated with such categories are identified. Depending on whether a threshold number of households exist in the donor pool of visitor data that match all of the desired categories of interest, the example AVP calculator 1102 will invoke a corresponding AVP calculation technique. For example, if more than a threshold number of households exist that have the desired categories of interest (e.g., 30 households), then the cell category approach may be used to calculate AVP, while the independent category approach may be used to calculate AVP, such as the independent category approach described in connection with example FIG. 5.

In the event the threshold number of households exist for a given set of categories of interest, the example AVP calculator 1102 calculates the AVP in a manner consistent with example Equation 8, and shown in FIG. 12. In the illustrated example of FIG. 12, categories of interest include particular tuning characteristics 1202 (e.g., households that watch Disney station between 12:30 and 5:00 PM on Mondays through Fridays) and particular household characteristics 1204 (e.g., households in an Older Family Life Stage with 2 television sets). Additionally, the example analysis of FIG. 12 is performed for two types of visitors; one associated with females age 6-11 (column 1206) and one associated with males age

25

55-64 (column **1208**). Among households that matched the desired set of characteristics of interest exhibited (as determined by collected PM visitor data), there were 3,892 minutes of visitor female age 6-11 exposure (cell **1210**) and 3,109 total household tuning minutes (cell **1212**). Application of example Equation 8 yields an AVP of 1.252 (cell **1214**) for such visitors that are female age 6-11. Additionally, households that matched the desired set of characteristics of interest exhibited 1,081 minutes of visitor male age 55-64 exposure (cell **1216**), and the total household tuning minutes (cell **1218**) remains the same at 3,109. Application of example Equation 8 yields an AVP of 0.348 (cell **1220**) for such visitors that are male age 55-64.

On the other hand, in the event a threshold number of households are not available for the desired categories of interest (e.g., less than 30 households), then the example AVP calculator **1102** calculates the AVP in a manner consistent with Equation 8 after determining expected exposure minutes and expected tuning minutes as category proportions, as described above in connection with FIG. 5. FIG. **13** illustrates example tuning data and exposure data for target demographic of females age 6-11, where the threshold number of households meeting the category combination of interest (e.g., life-stage=older family plus TV sets=2) were not available. In the illustrated example of FIG. **13**, households reflecting the category "Life Stage=Older Family" exhibited 443,940 female age 6-11 visitor exposure minutes (cell **1302**) and 733,317 tuning minutes (cell **1304**), and households reflecting the category "TV Sets=2" exhibited 150,844 female age 6-11 visitor exposure minutes (cell **1306**) and 285,877 tuning minutes (cell **1308**). Additionally, a total amount of female age 6-11 visitor exposure minutes exhibited 1,741,474 minutes (cell **1310**), and a total amount of household tuning minutes exhibited 8,200,347 minutes (cell **1312**).

The example AVP calculator **1102** and/or the example distribution engine **230** calculates an exposure proportion for each category of interest **1314** and a tuning proportion for each category of interest **1316**. Continuing with the illustrated example of FIG. **13**, the exposure proportion associated with the life stage category is the ratio of visitor exposure minutes to total viewing minutes to yield a proportion factor of 0.255 (result **1318**). Additionally, the exposure proportion associated with the TV sets category is 0.087 (result **1320**). The example tuning proportion associated with the life stage category is the ratio of household tuning minutes to total tuning minutes to yield a tuning proportion of 0.089 (result **1322**), and a tuning proportion of 0.035 associated with the TV sets category (result **1324**). While the illustrated example of FIG. **13** includes two (2) categories of interest, example methods, apparatus, systems and/or articles of manufacture may include any number of categories of interest.

The example AVP calculator **1102** calculates an expected exposure minutes value (cell **1326**) as the product of the total exposure minutes (cell **1310**) and any number of calculated exposure proportion values that occur based on the number of categories of interest (e.g., result **1318** and result **1320**). The example AVP calculator **1102** also calculates an expected tuning minutes value (cell **1328**) as the product of the total tuning minutes (cell **1312**) and any number of calculated tuning proportion values that occur based on the number of categories of interest (e.g., result **1322** and result **1324**). In a manner consistent with example Equation 8, the example AVP calculator **1102** calculates the AVP value (cell **1330**), which is used to determine a number of visitors and associated ages, as described in further detail below.

To determine a number of visitors and corresponding ages, example methods, apparatus, systems and/or articles of

26

manufacture disclosed herein employ a distribution model. While the type of distribution model described below is a Poisson distribution, this distribution is used for example purposes and not limitation. The Poisson distribution is a discrete probability distribution to express the probabilities of given numbers of events when their average rate is known, and applied herein to assign a number of visitors watching a given tuning segment (the previously calculated AVP being the known average rate). Probabilities for the Poisson distribution are defined in a manner consistent with example Equation 10.

$$p(v) = \frac{(\lambda_d^v * e^{-\lambda_d})}{v!} \quad \text{Equation 10}$$

In the illustrated example of Equation 10, v reflects a number of visitors, $p(v)$ reflects a probability calculated for " v " visitors, and λ_d reflects the AVP for a given demographic group of interest (e.g., female age 6-11). The example distribution engine **1104** defines the distribution, such as the example Poisson distribution above, and calculates probability values for a candidate number of visitors of interest, as shown in further detail in FIG. **14**.

In the illustrated example of FIG. **14**, eleven (11) different number of visitor values **1402** are selected by the example distribution engine **1104** for a first demographic group of interest **1404** (e.g., female age 6-11), and eleven (11) different number of visitor values **1406** are selected by the example distribution engine **1104** for a second demographic group of interest **1408** (e.g., male age 55-64). For each discrete number of visitor value, the example distribution engine **1104** calculates a corresponding probability value (see row **1410** associated with females age 6-11, and see row **1412** associated with males age 55-64). The example distribution engine **1104** also calculates the corresponding cumulative probabilities $c(v)$ within each demographic group of interest (see row **1414** associated with females age 6-11, and see row **1416** associated with males age 55-64). The example cumulative distribution of FIG. **14** allows arrangement of the probabilities between boundaries of zero and one as a matter of convenience such that the example random number generator **1106** can identify a lookup value.

For each demographic group of interest, the example visitor assignor **1108** invokes the random number generator **1106** to generate a random number that, when referenced against the cumulative distribution values, reveals a number of visitors to attribute to that demographic group of interest. For example, if the random number generator produces a value of 0.757000 for the first group **1404** associated with females age 6-11, then this value is associated by the example visitor assignor **1108** to fall within a visitor (v) value of 2. Additionally, if the random number generator produces a value of 0.52700 for the second group **1408** associated with males age 55-64, then this value is associated by the example visitor assignor **1108** to fall within a visitor (v) value of 1. As a result, the first group **1404** is deemed to have two visitors, each having an age somewhere between 6-11, and the second group **1408** is deemed to have one visitor having an age somewhere between the ages of 55-64. The example random number generator **1106** is again employed to randomly assign corresponding ages for each of the two visitors from the first group **1404** between the ages of 6-11, and to randomly assign an age for the visitor from the second group **1408** between the ages of 55-64. While the aforementioned example was performed for a target demographic group of interest of females

27

between the ages of 6-11 and males between the ages of 55-64, the same process may be repeated for all demographic groups of interest to possibly assign other visitors to a given tuning segment.

The program **1500** of FIG. **15** begins at block **1502** where the example PM interface **202** acquires and identifies data associated with visitors that have selected visitor button(s) of panelist households within a region of interest (e.g., a DMA). The example weighting engine **210** applies weights to the collected visitor data in proportions that are based on an amount of time since the date of collection of the donor data (block **1504**). As described above, index value data points that are more recent in time generally reside closer to an index value of 1.00 (see FIG. **3**). In other words, an accuracy of the viewing index is better when the corresponding collected data is more recent.

When performing an analysis of a market of interest, the example categorizer **206** categorizes the acquired PM data based on one or more categories of interest (block **1506**). As described above, categories of interest may include, but are not limited to an age/gender combination of interest, a particular household size of interest, a particular life stage of interest, a particular viewed station/affiliate/genre of interest, a particular daypart of interest, a number of television sets of interest within the household (e.g., households with one television set, households with 2-3 television sets, households with three or more television sets, etc.), and/or an education level of the head of household. While a relatively large number of MMPM households **106** will have at least one of the aforementioned categories, a substantially smaller number of MMPM households **106** will represent all of the target combination of categories of interest to a market researching during a market study.

If the example visitor imputation engine **112** determines that a threshold number of households associated with a preferred and/or otherwise desired set of characteristics is satisfied (e.g., a threshold of at least 30 households) (block **1508**), then the AVP value(s) are calculated by the example AVP calculator **1102** in a manner consistent with FIG. **12** (block **1510**). On the other hand, in the event the example visitor imputation engine **112** determines that a threshold number of households is not satisfied (block **1508**), then the AVP value(s) are calculated by the example AVP calculator **1102** in a manner consistent with FIG. **13** (block **1512**). In particular, the example AVP calculator **1102** and/or the example distribution engine **230** calculates an exposure proportion for each category of interest, and calculates a tuning proportion for each category of interest. The product of each calculated category-specific exposure proportion and total exposure minutes yields expected exposure minutes, and the product of each calculated category-specific tuning proportion and total tuning minutes yields expected tuning minutes. The resulting expected exposure minutes and expected tuning minutes are applied to example Equation 8 to generate corresponding AVP values.

The example distribution engine **1104** defines a distribution model to apply, such as the Poisson distribution (block **1514**), and calculates probabilities for any number of visitors (v) of interest in a manner consistent with example Equation 10 (block **1516**). For example, FIG. **14** illustrates eleven (11) different number of visitor values **1402** from zero (0) to ten (10). The example distribution engine **1104** also calculates cumulative probabilities so that selections from the distribution can be selected from values bounded between zero (0) and one (1) (block **1518**). The example distribution engine **1104** invokes the random number generator **1106** to select a corresponding number of visitors (v) from the cumulative

28

probabilities set for each demographic set of interest (block **1520**). Once each demographic set of interest has a determined number of visitors, bounded age values are randomly selected for each visitor to be associated with tuning minutes (block **1522**).

Ambient Tuning

As described above, employing a MM without a PM to characterize household media exposure behavior facilitates substantial cost savings when compared to employing PM devices, which may be physically connected to media devices (e.g., televisions) and require professional installation. For example, a MM may be mailed to a panelist, plugged in to power and function without professional installation and/or without connection to the panelist's electronics (e.g., media electronics such as DVD players, set top boxes, televisions, etc.). Although using MM devices without PMs result in substantial panelist household cost savings, some households have two or more media devices located in rooms in a relative proximity to where sound from a first media device reaches the room in which the second media device is located, and vice versa. In such circumstances, a MM device from the first room may incorrectly credit exposure minutes based on audio spillover associated with the second media device in the second room (and vice versa). When MM devices incorrectly credit exposure minutes, one or more household tuning estimates and/or projections may be overreported/inflated. Example methods, apparatus, systems and/or articles of manufacture disclosed herein distinguish instances of ambient tuning (e.g., due to spillover) from instances of real tuning.

FIG. **16** is a schematic illustration of an example implementation of the example ambient tuning engine **120** of FIG. **1**. The example ambient tuning engine **120** of FIG. **1** is constructed in accordance with the teachings of this disclosure. In the illustrated example of FIG. **16**, the ambient tuning engine **120** includes the PM interface **202** and the MM interface **204** as disclosed above in connection with FIG. **2**. Additionally, the illustrated example of FIG. **16** includes a simultaneous tuning monitor **1602**, a crediting manager **1604**, a station comparator **1606**, a tuning type assignor **1608**, a modeling engine **1614**, a code stacking manager **1616**, an automatic gain control (AGC) monitor **1610** and a code presence manager **1612**.

In operation, the example PM interface **202** and the example MM interface **204** collect household tuning data from MMPM households **106** and MMH households **108** within a region of interest **104** (e.g., panelist households within a direct marketing area (DMA)) that comprise an available data pool (e.g., LPM households, NPM households, etc.). The example ambient tuning engine **120** invokes the example simultaneous tuning monitor **1602** to identify whether instances of simultaneous tuning minutes from collected household data are either ambient or real. As used herein, "simultaneous tuning" refers to instances where two or more meters within a household are detecting the same media (e.g., the same television station). To illustrate, assume a first MM proximate to a first television in a first room detects station WAAA, and a second MM proximate to a second television in a second room also detects station WAAA. One possibility that may be true is that both media devices (e.g., televisions) are powered on and tuned to station WAAA. However, another possibility is that the first television is on and tuned to station WAAA while the second television is tuned to another station while muted. Yet another possibility is that the first television is on and tuned to station WAAA

while the second television is not powered on. In such circumstances, the second MM device may be detecting audio (e.g., spillover) from the first television and, thus, improperly inflating media exposure (e.g., consumption) metrics associated with the second television and/or household members.

In some examples, the crediting manager **1604** identifies quantities of time (e.g., minutes) where the MM device credited a station, and the example station comparator **1606** determines whether an AP device paired with the MM device is also crediting the same station. If so, then the example tuning type assignor **1608** assigns the corresponding tuning minute as real. On the other hand, if the example crediting manager **1604** identifies minutes where the MM devices credited a station (e.g., embedded codes detected by the MM device, embedded codes passed-on by the MM device and detected by the ambient tuning engine **120** during post-processing, signature post processing, etc.), and the example station comparator **1606** determines that the paired AP device is not tuned to the same station, then the example station comparator **1606** determines whether a separate metering device within the household is tuned to the same station, such as another AP and/or MM device associated with a second television in a second room of the household. If so, then that household tuning minute is deemed and/or otherwise labeled as ambient tuning/spillover, which should be ignored to prevent improper overrepresentation. On the other hand, in the event the example station comparator **1606** determines that no other metering device in the household is also tuned to the same station, then the example tuning type assignor **1608** assigns the minute as non-tuning. The example simultaneous tuning monitor **1602** continues to evaluate each received tuning minute within the pool of data collected from the example panelist households **104**.

To develop a stochastic approach to determine the occurrence of spillover in which derived model coefficients are derived for use in MMH households **108**, the example ambient tuning engine **120** collects additional predictive variables indicative of the occurrence or non-occurrence of spillover. The predictive variables are applied to a model, such as a regression model, to generate coefficients/parameters that facilitate calculation of a probability that spillover is occurring or not occurring within the MMH households **108**. At least three predictive variables indicative of the occurrence or non-occurrence of spillover include automatic gain control (AGC) values, the presence of embedded codes, such as final distributor audio codes (FDACs), and the duration of the collected segment.

Generally speaking, by comparing AGC values between two separate MM devices within a household (e.g., calculating a difference therebetween), an indication of spillover may be evaluated. A MM device placed relatively close to a first television, for example, is more likely to have a low AGC value because of a higher relative volume when compared to an AGC value associated with sound from a television relatively farther away. AGC values are typically established by acoustic gain circuits that apply greater gain (e.g., amplification) when attempting to discern and/or otherwise detect sound energy that has a relatively low volume than when attempting to detect sound energy of a higher volume. Volume may be lower, for example, due to a greater distance from a source of the originating sound energy. Additionally, quantities and/or densities of detected codes per unit of time are additional example predictive variable(s) that may be applied to the model to derive an indication of the likelihood of the occurrence or non-occurrence of spillover. Without limita-

tion, segment duration is another predictive variable useful in the indication of spillover, as described in further detail below.

The example AGC monitor **1610** of FIG. **16** assigns each collected minute to a corresponding AGC value. The example code presence manager **1612** of FIG. **16** assigns each collected minute an indicator corresponding to the presence or absence of an embedded code. In some examples, code detection activity(ies) may occur during post processing of raw audio information collected by meter(s). In other examples, the codes are detected in real time or near real time. The example ambient tuning engine **120** of FIG. **16** segregates instances of simultaneous tuning minutes based on whether embedded codes have been detected. For example, the modeling engine **1614** prepares a regression model with dependent variables reflecting the previously determined real or ambient status occurrence(s). The example AGC monitor **1610** determines a minimum (e.g., lowest) AGC for the household devices for a particular monitored time period and/or collected set of audio data. For each device and minute, the example AGC monitor **1610** determines an AGC difference value with respect to the minimum AGC value and each collected minute.

The example code presence manager **1612** of FIG. **16** identifies one of three possible scenarios for the type and presence of codes in collected MM data for devices (e.g., TV sets, radio, etc.) within a household. A first possible scenario is that no codes are present in the collected MM data for any of the devices of the household of interest. A second possible scenario is that the collected MM data has some codes for some of the devices within the household, but not all of the devices have associated codes detected in the collected minutes. A third possible scenario is that the collected MM data for the household has codes in all of the data collected. In other words, each collected minute of tuning data has corresponding codes in all devices within that household.

If none of the meters within the household have collected codes in the collected minutes, then the example simultaneous tuning monitor **1602** of FIG. **16** places a greater weight on a type of segment duration for the household. For instance, if a television is tuned to station WAAA, then the MM device closest to that television will have a relatively longer collected segment duration than a MM device located further away from the television. The sound emanating from a television located further away from that same MM device may fluctuate in intensity such that the MM device may not capture full segment durations. The example simultaneous tuning monitor **1602** of FIG. **16** identifies, for each household, a longest (e.g., maximum) segment duration and calculates a duration difference to be applied to the logistic regression fit of the collected data in a manner consistent with example Equation (11).

$$\text{Log} \left[\frac{\text{Probability}(\text{Simultaneous Minute} = \text{Ambient})}{\text{Probability}(\text{Simultaneous Minute} = \text{Real})} \right] = \text{Equation (11)}$$

$$B_0 + B_1 X_1 + \dots + B_k X_k$$

In the illustrated example of Equation (11), the model has the response (dependent) dependent variable as the ambient or real value to which each simultaneous tuning minute is assigned. Independent variables $X_1, \dots, X_k$ may be coded and/or otherwise categorized with model coefficients $B_1, \dots, B_k$. Categories may be represented by any scale, such as AGC values ranging from zero to one hundred having sub-groups therein.

31

If some of the meters within the household have collected codes in the collected minutes (e.g., collected raw audio with codes embedded therein and subsequently identified during audio data post processing), but others do not, then the example modeling engine **1614** of FIG. **16** builds a model in a manner consistent with example Equation (11) using data associated with the AGC difference values. If all of the meters within the household have collected codes in the collected minutes, then the example code stacking manager **1616** determines a maximum unstacked count and a maximum stacked count for the household devices. As used herein, a stacked code refers to an instance of code repair and/or imputation when part of a code is detected. In such cases where the entire code content is not correctly collected by the MM device, a stacking procedure fills-in portions of the code that were not detected. Generally speaking, meter devices (e.g., MMs) that are relatively closer to the media device (e.g., television) will have a better ability to collect unstacked codes that are not in need of repair or padding due to, for example, a relatively closer proximity to the meter device(s). However, when the meter devices operate at a distance relatively farther away from the monitored device, the ability for the meter devices to accurately collect the entire code becomes more difficult and erroneous. The code stacking manager **1616** of the illustrated example determines a difference between meter devices within the household of the stacked and unstacked count values, which is applied to the model. Additionally, the simultaneous tuning monitor **1602** of the illustrated example identifies a maximum average of seconds of collected code for all meter devices within the household, and calculates a difference between those household devices. The difference of seconds of collected code, the stacked and unstacked code count difference values, and the AGC difference values are applied to the example model of Equation (11) to derive the corresponding model coefficients (e.g., $B_1, \dots, B_k$).

As described above, the example code presence manager **1612** of FIG. **16** identifies one of the three possible scenarios for the type and presence of codes in the household and, based on the detected scenario, applies a different combination of predictive variables (e.g., AGC values, segment duration, count of stacked versus unstacked codes). Each of these scenarios applies the corresponding predictive variables to the example model of Equation (11), and the example modeling engine **1614** of FIG. **16** calculates a probability of spillover in a manner consistent with example Equation (12).

$$\text{Probability}(\text{Minute} = \text{Ambient}) = \frac{1}{[1 + e^{-(B_0 + B_1 X_1 + \dots + B_k X_k)}]} \quad \text{Equation (12)}$$

Each simultaneous tuning minute may be identified as either ambient tuning or real tuning based on the resulting probability value and a threshold established by, for example, a market researcher. For example, if the probability value is greater than or equal to 0.50, then the minute may be designated as ambient tuning. On the other hand, the minute may be designated as real tuning for probability values less than 0.50.

The program **1700** of FIG. **17** begins at block **1702** where the example PM interface **202** and the example MM interface **204** of the illustrated example collect tuning data from MMPM households **106** and MMH households **108** within panelist households **104**. The example simultaneous tuning monitor **1602** of FIG. **16** identifies whether simultaneous tuning minutes within such households are either ambient or real (block **1704**), as described in further detail below in connection with FIG. **18**.

32

FIG. **18** includes additional detail from the illustrated example of FIG. **17**. When identifying whether simultaneous tuning minutes are ambient or real, the example crediting manager **1604** of FIG. **16** identifies minutes where a MM device (e.g., a MM device in the MMPM household **106**) within the household of interest credited a station (block **1802**). The station comparator **1606** of FIG. **16** determines whether an AP device in the household of interest is also crediting the same station as the MM device at the same time (block **1804**). In some examples, the crediting manager **1604** compares a timestamp associated with minutes collected from the MM device with a timestamp associated with minutes collected from the PM device of the same household. If the timestamps match and the detected stations are the same, then the example tuning type assignor **1608** of FIG. **16** assigns that corresponding minute as real tuning (block **1806**). The example simultaneous tuning monitor **1602** determines if there are additional minutes from the household of interest to analyze (block **1808**). If so, then the example simultaneous tuning monitor **1602** selects the next minute for analysis (block **1810**) and control returns to block **1804**.

If the example station comparator **1606** of FIG. **16** determines that the AP device is not crediting the same station as the MM device within the household (block **1804**), which could be due to multiple media presentation devices (e.g., TV sets) within the household being tuned to different stations or turned off, then the example station comparator **1606** of the illustrated example determines whether the other device is tuned to the same station (block **1812**). As described above, example methods, apparatus, systems and/or articles of manufacture disclosed herein employ MMPM households **106** that have both MM devices and PM devices so that ambiguity of actual device behavior is eliminated. Once model coefficients are generated based on such observed behaviors in the MMPM households **106**, the data collected from the MMH households **108** may be imputed with the coefficients to allow an indication of spillover to be calculated. As such, panelist households without PMs can be effectively utilized. As a result, a greater number of panelist households may be implemented in the example region of interest **104** without the added capital expense of PM devices that require professional installation, relatively greater training, and/or more routine maintenance than MM devices.

If the example station comparator **1606** determines that the other device in the household is tuned to the same station (block **1812**) (e.g., based on the detection of the same codes), then the example tuning type assignor **1608** assigns the corresponding minute as ambient tuning (also referred to herein as spillover) (block **1814**). On the other hand, if the example station comparator **1606** determines that the other device in the household is not tuned to the same station (block **1812**), then the example tuning type assignor **1608** of the illustrated example assigns the corresponding minute as a non-tuning minute (block **1816**).

Returning to FIG. **17**, the example AGC monitor **1610** of the illustrated example assigns each minute to a corresponding AGC value (block **1706**). As described above, the AGC value associated with a collected minute in some example predictive variables assist in calculating a probability of ambient tuning occurrences. Additionally, another example predictive variable discussed above includes the presence or absence of embedded codes within the collected minute of media. The example code presence manager **1612** of the illustrated example assigns each minute an indicator regarding the presence or absence of embedded codes (block **1708**). The example ambient tuning engine **120** segregates instances of simultaneous tuning minutes based on whether such

33

embedded codes have been detected (block 1710), as described further below in connection with FIG. 19.

In the illustrated example of FIG. 19 (block 1710), the modeling engine 1614 of the illustrated example prepares a regression model with dependent variables reflecting corresponding real or ambient status indicators (block 1902). For each household device of interest, the example AGC monitor 1610 determines a minimum AGC value across two or more MM devices (block 1904) and determines a difference value therebetween (block 1906). In view of the possibility that the MM devices within the household of interest may either collect no codes, collect some codes for some of the minutes and not others, or collect codes for all of the minutes, the example code presence manager 1612 of the illustrated example identifies which circumstance applies (block 1908).

If the example code presence manager 1612 of the illustrated example identifies a first category in which no codes are detected, the example simultaneous tuning monitor 1602 determines a maximum segment duration associated with the MM devices (block 1910), and calculates a difference therebetween (block 1912). The example modeling engine 1614 of FIG. 16 applies a logistic regression fit to the collected data in a manner consistent with example Equation (11) (block 1914), as described above. In particular, when the household does not detect any codes in the collected minutes, the example model of Equation (11) is tailored to consider (1) the AGC values and (2) differences in collected segment durations (block 1914).

If the example code presence manager 1612 of the illustrated example identifies a second category in which some codes are detected in some minutes, while no codes are detected in other minutes (block 1908), then the example modeling engine 1614 of FIG. 16 applies a logistic regression fit to the collected data in a manner consistent with example Equation (11) (block 1916). However, in this application of example Equation (11), the model employs (1) the AGC values and (2) the presence or absence of codes in corresponding collected minutes (block 1916).

If the example code presence manager 1612 identifies a third category in which all codes are detected in all collected minutes (block 1908), then the example code stacking manager 1616 of this example determines whether the detected codes are, themselves, complete (block 1918). As described above, while the example MM devices may detect and/or otherwise capture codes that may have been embedded in media from a media device (e.g., a television), the quality of the detected codes may differ. Such differences may be due to, for example, the MM device collecting audio from a television that is relatively far away from where the MM device is located. In such situations, one or more stacking operations may supplement missing portions of the detected code with accurate code data. The example code stacking manager 1616 of this example identifies a difference between MM devices in the household regarding the number of stacked codes versus unstacked codes detected (block 1920). Additionally, the example simultaneous tuning monitor 1602 calculates an average (e.g., a maximum average) seconds of code per metering device in the household, and a corresponding difference value between each metering device (block 1922). The example modeling engine 1614 of the illustrated example applies the logistic regression fit to the collected data in a manner consistent with example Equation (11) (block 1924). However, in this application of example Equation (11), the model employs (1) the AGC values, (2) the differences between stacked/unstacked embedded codes and (3) the differences between the average number of seconds of code between metering devices (block 1924).

34

Returning to FIG. 17, the example modeling engine 1614 of this example applies calculated coefficients from the model (e.g., Equation (11)) to a probability calculation in a manner consistent with example Equation (12) to determine a probability that tuning for a given minute should be categorized as spillover (ambient tuning) (block 1712).

On/Off Detection

As described above, employing a MM to characterize household media viewing behavior may be performed in a stochastic manner rather than by employing a PM to save money that would otherwise be spent on the relatively expensive PM devices. When a MM device is employed to collect audio signal (tuning) data from a household, some of the collected minutes may include codes (e.g., embedded codes collected in the raw audio and passed on to the on/off detection engine 130 for post processing), some of the collected minutes may be analyzed via signature analysis (e.g., analysis of the raw audio collected by the MM device and passed on to the on/off detection engine 130 for audio signature comparison against one or more signature database(s)), and some of the collected minutes may have neither codes nor have corresponding signature matches for media identification.

FIG. 20 illustrates an example crediting chart 2000 having a block of twenty-four (24) hours of tuning data collected from an example MM device in an example household. In the illustrated example of FIG. 20, some portions of collected minutes from the household are associated with codes 2002, which also indicates that a media device (e.g., a television) within the household is turned on. Additionally, some portions of collected minutes from the household are associated with signatures of the detected media 2004 that, when compared to a reference database, allow identification of media. However, still other portions of collected minutes from the household have neither codes nor signatures that match known media in a reference database 2006.

Minutes that have neither codes nor corresponding signatures that may be used with a reference database are referred to herein as all other tuning (AOT) minutes. In such circumstances with a PM device, the media device (e.g., television) will be detected in an on state (e.g., power status ON based on a power status detector of the PM device), but no station and/or media can be credited with tuning. In other circumstances, a media device may be in a muted state or an off state (e.g., power status OFF), thus no audio is emitted that can be used for crediting. Example methods, systems, apparatus and/or articles of manufacture disclosed herein apply a stochastic manner of determining whether AOT minutes are associated with an off state or an on state, which may be associated with other media device usage separate from media programming (e.g., video game usage, video conferencing, etc.).

FIG. 21 is a schematic illustration of the example on/off detection engine 130 of FIG. 1 and constructed in accordance with the teachings of this disclosure. In the illustrated example of FIG. 21, the on/off detection engine 130 includes the PM interface 202, the MM interface 204, the AGC monitor 1610 and the modeling engine 1614 as disclosed above in connection with FIGS. 2 and 16.

In operation, the example PM interface 202 collects minutes from a PM device (e.g., an active/passive people-meter) within the household related to three categories of media device usage. A first category of media device usage associated with some collected minutes is related to a particular station or media, such as media identified by way of codes or signature matching. A second category of media device usage

35

associated with other collected minutes is related to instances of non-programming related usage, such as video game play, video conferencing activity, home picture viewing, etc. A third category of media device usage associated with still other collected minutes is related to instances where the media device is powered off.

The example MM interface **204** also collects minutes from a MM device within the household. As described above, because the MM interface **204** is not physically connected to the media device, it cannot directly verify whether the media device is powered on and, instead, collects only audio-based information via one or more built-in microphones. The example MM interface **204** may collect minutes data that either credits a station or media, or designates the collected minutes as AOU. The example AGC monitor **1610** collects AGC values from each of the example MM interface **204** and the example PM interface **202** for each corresponding minute, and the example modeling engine **1614** prepares a regression model to fit the collected data in a manner consistent with example Equation (13).

$$\text{Log} \left[\frac{\text{Probability}(\text{Given Minute} = \text{HUT})}{\text{Probability}(\text{Given Minute} = \text{OFF})} \right] = \frac{B_0 + B_1 X_1 + \dots + B_k X_k}{\text{Equation (13)}}$$

In the illustrated example of Equation (13), HUT is indicative of a “household using television” on (e.g., an ON power status), off is indicative of an OFF power status, and the independent variables (X) include AGC values, daypart information and/or a number of minutes since a code reader credit occurred.

The example modeling engine **1614** uses derived coefficients (B) to calculate a probability for each minute as either on (HUT) or off in a manner consistent with example Equation (14).

$$\text{Probability}(\text{AOU Minute} = \text{HUT}) = \frac{1}{1 + e^{-(B_0 + B_1 X_1 + \dots + B_k X_k)}} \quad \text{Equation (14)}$$

The program **2200** of FIG. **22** begins at block **2202** where the example PM interface **202** collects minutes from the PM device related to minutes where a station was credited, minutes where the television was in use, but had no crediting, and where the television was powered off. The example MM interface **204** collects minutes from the MM device in the dual panel household related to minutes where a station was credited, and minutes of AOU (block **2204**). The example AGC monitor **1610** collects AGC values associated with each minute collected by the example PM interface **202** and MM interface **204** (block **2206**).

The example modeling engine **1614** prepares a model based on AGC values, day parts and a number of minutes since a last MM device credit in a manner consistent with example Equation (13) (block **2208**). The model may include, but is not limited to, a regression model, in which coefficients may be derived after fitting the collected data. The derived model coefficients are used by the example modeling engine **1614** to calculate a probability that any particular minute of interest was associated with either an on state or an off state of the household media device. These derived coefficients may be associated with panelist households within the region of interest **104** having only MM devices **108** (block **2210**).

36

FIG. **23** is a block diagram of an example processor platform **2300** capable of executing the instructions of FIGS. **6-9**, **15**, **17-19** and **22** to implement the ambient tuning engine **120**, the imputation engine **110**, the visitor imputation engine **112**, and the on/off detection engine **130** of FIGS. **1**, **2**, **11**, **16** and **21**. The processor platform **2300** can be, for example, a server, a personal computer, an Internet appliance, a digital video recorder, a personal video recorder, a set top box, or any other type of computing device.

The processor platform **2300** of the illustrated example includes a processor **2312**. The processor **2312** of the illustrated example is hardware. For example, the processor **2312** can be implemented by one or more integrated circuits, logic circuits, microprocessors or controllers from any desired family or manufacturer.

The processor **2312** of the illustrated example includes a local memory **2313** (e.g., a cache). The processor **2312** of the illustrated example is in communication with a main memory including a volatile memory **2314** and a non-volatile memory **2316** via a bus **2318**. The volatile memory **2314** may be implemented by Synchronous Dynamic Random Access Memory (SDRAM), Dynamic Random Access Memory (DRAM), RAMBUS Dynamic Random Access Memory (RDRAM) and/or any other type of random access memory device. The non-volatile memory **2316** may be implemented by flash memory and/or any other desired type of memory device. Access to the main memory **2314**, **2316** is controlled by a memory controller.

The processor platform **2300** of the illustrated example also includes an interface circuit **2320**. The interface circuit **2320** may be implemented by any type of interface standard, such as an Ethernet interface, a universal serial bus (USB), and/or a PCI express interface.

In the illustrated example, one or more input devices **2322** are connected to the interface circuit **2320**. The input device(s) **2322** permit(s) a user to enter data and commands into the processor **2312**. The input device(s) can be implemented by, for example, an audio sensor, a microphone, a camera (still or video), a keyboard, a button, a mouse, a touchscreen, a track-pad, a trackball, isopoint and/or a voice recognition system.

One or more output devices **2324** are also connected to the interface circuit **2320** of the illustrated example. The output devices **2324** can be implemented, for example, by display devices (e.g., a light emitting diode (LED), an organic light emitting diode (OLED), a liquid crystal display, a cathode ray tube display (CRT), a touchscreen, a light emitting diode (LED), a printer and/or speakers). The interface circuit **2320** of the illustrated example, thus, typically includes a graphics driver card, a graphics driver chip or a graphics driver processor.

The interface circuit **2320** of the illustrated example also includes a communication device such as a transmitter, a receiver, a transceiver, a modem and/or network interface card to facilitate exchange of data with external machines (e.g., computing devices of any kind) via a network **2326** (e.g., an Ethernet connection, a digital subscriber line (DSL), a telephone line, coaxial cable, a cellular telephone system, etc.).

The processor platform **2300** of the illustrated example also includes one or more mass storage devices **2328** for storing software and/or data. Examples of such mass storage devices **2328** include floppy disk drives, hard drive disks, compact disk drives, Blu-ray disk drives, RAID systems, and digital versatile disk (DVD) drives.

The coded instructions **2332** of FIGS. **6-9**, **15**, **17-19** and **22** may be stored in the mass storage device **2328**, in the volatile

37

memory 2314, in the non-volatile memory 2316, and/or on a removable tangible computer readable storage medium such as a CD or DVD.

From the foregoing, it will be appreciated that the above disclosed methods, apparatus and articles of manufacture allow audience measurement techniques to occur with a substantially larger quantity of households, in which each household has a substantially lower metering equipment cost by employing audio-based code reader devices instead of relatively more expensive people meter devices. Examples disclosed herein permit a determination of behavior probability that can be applied to households that do not have a People Meter device and, instead, employ a media meter that captures audio without a physical connection to a media device (e.g., a television). Such examples allow behavior probability calculations based on utilization of other households that include the People Meter device, in which the calculations reveal behavior probabilities in a stochastic manner that adheres to expectations of statistical significance.

Example methods, systems, apparatus and/or articles of manufacture disclosed herein also facilitate a stochastic manner of determining a probability of ambient tuning within households that do not employ a People Meter device. In some examples disclosed herein, both a panelist audience meter (e.g., a People Meter) and a media meter (e.g., captures audio without a physical connection to a media device) are employed to obtain data associated with media code status and one or more automatic gain control (AGC) values. Based on the obtained code status and AGC values, examples disclosed herein create model coefficients that may be applied to households with only media meters in a manner that determines a probability of ambient tuning that upholds expectations of statistical significance. Additionally, data obtained related to AGC values are disclosed herein to be used with daypart information to calculate model coefficients indicative of whether a media device (e.g., a television) is powered on or powered off.

Additional example methods, systems, apparatus and/or articles of manufacture disclosed herein identify probabilities of a number of visitors in a household and their corresponding ages. In particular, examples disclosed herein calculate an average visitor parameter (AVP) based on exposure minutes and tuning minutes, which are further applied to a Poisson distribution to determine a probability of having a certain number of visitors in a household. Such probabilities are in view of a target demographic of interest having a particular age range, which may be selected based on inputs from a random number generator.

Although certain example methods, apparatus and articles of manufacture have been disclosed herein, the scope of coverage of this patent is not limited thereto. On the contrary, this patent covers all methods, apparatus and articles of manufacture fairly falling within the scope of the claims of this patent.

What is claimed is:

1. A method to calculate a panelist behavior probability, comprising:

identifying, with a processor, a target set of household categories associated with a target research geography; when a quantity of panelist households within the target research geography representing the target set of household categories does not satisfy a threshold value required to support statistical significance, increasing an available sample size of households by generating a first subset of categories and a second subset of categories from the target set of household categories;

38

identifying a first set of households representing the first subset of categories from the target set of household categories and identifying an associated total number of household tuning minutes and a total number of household exposure minutes associated with the first set of households;

for each category in the second subset of categories from the target set of household categories, calculating a household tuning proportion and an exposure proportion, the household tuning proportion for each category in the second subset being based on a ratio of respective category tuning minutes and the total number of household tuning minutes associated with the first set of households, and the exposure proportion for each category in the second subset based on a ratio of respective category exposure minutes and the total number of exposure minutes associated with the first set of households; and

calculating the panelist behavior probability for the combined first and second subset of categories based on the respective exposure proportions and the household tuning proportions.

2. A method as defined in claim 1, further including applying a temporal weight to the total number of household tuning minutes, the temporal weight having a greater bias associated with a first portion of the total number of household tuning minutes acquired more recently than a second portion of the total number of tuning minutes.

3. A method as defined in claim 2, further including applying a proportionally lower weight to the second portion of the total number of tuning minutes having a relatively older acquisition timestamp.

4. A method as defined in claim 1, further including applying a temporal weight to the total number of household exposure minutes, the temporal weight having a greater bias associated with a first portion of the total number of household exposure minutes acquired more recently than a second portion of the total number of exposure minutes.

5. A method as defined in claim 4, further including applying a proportionally lower weight to the second portion of the total number of exposure minutes having a relatively older acquisition timestamp.

6. A method as defined in claim 1, further including:

multiplying the household tuning proportions for each category together and multiplying by the total number of household tuning minutes to calculate expected household tuning minutes associated with the second subset of categories;

multiplying the exposure proportions for each category together to form a combined exposure proportion; and multiplying the combined exposure proportion by the total number of exposure minutes to calculate expected exposure minutes associated with the second subset of categories.

7. A method as defined in claim 6, wherein a ratio of the expected exposure minutes and the expected household tuning minutes results in the panelist behavior probability for the target research geography.

8. A method as defined in claim 1, wherein the second subset of categories includes at least one of households tuned to a particular station, households associated with a particular education level, households with a particular number of television sets, households tuned to a station during a particular daypart, or households having a particular life stage.

9. An apparatus to calculate panelist behavior probability, comprising:

a categorizer to identify a target set of household categories associated with a target research geography;

a category manager to, when a quantity of panelist households within the target research geography representing the target set of household categories does not satisfy a threshold value sufficient to support statistical significance, increase an available sample size of households by generating a first subset of categories and a second subset of categories from the target set of household categories;

a proportion manager to:

identify a first set of households representing the first subset of categories from the target set of household categories;

identify a total number of household tuning minutes and a total number of household exposure minutes associated associated with the first set of households;

calculate a household tuning proportion and an exposure proportion for each category in the second subset of categories from the target set of household categories, the household tuning proportion based on a ratio of category tuning minutes and the total number of household tuning minutes associated with the first set of households, and the exposure proportion based on a ratio of category exposure minutes and the total number of exposure minutes associated with the first set of households; and

a distribution engine to calculate the panelist behavior probability for the combined first and second subset of categories based on the respective exposure proportions and the household tuning proportions.

10. An apparatus as defined in claim 9, further including a weighting engine to apply a temporal weight to the total number of household tuning minutes, the temporal weight having a greater bias associated with a first portion of the total number of household tuning minutes acquired more recently than a second portion of the total number of tuning minutes.

11. An apparatus as defined in claim 10, wherein the weighting engine is to apply a proportionally lower weight to the second portion of the total number of tuning minutes having a relatively older acquisition timestamp.

12. An apparatus as defined in claim 9, further including a weighting engine to apply a temporal weight to the total number of household exposure minutes, the temporal weight having a greater bias associated with a first portion of the total number of household exposure minutes acquired more recently than a second portion of the total number of exposure minutes.

13. An apparatus as defined in claim 12, wherein the weighting engine is to apply a proportionally lower weight to the second portion of the total number of exposure minutes having a relatively older acquisition timestamp.

14. An apparatus as defined in claim 9, wherein the distribution engine is to:

multiply the household tuning proportions for each category together and multiply by the total number of household tuning minutes to calculate expected household tuning minutes associated with the second subset of categories;

multiply the exposure proportions for each category together to form a combined exposure proportion; and multiply the combined exposure proportion by the total number of exposure minutes to calculate expected exposure minutes associated with the second subset of categories.

15. An apparatus as defined in claim 14, wherein the distribution engine is to calculate a ratio of the expected exposure minutes and the expected household tuning minutes to identify the panelist behavior probability for the target research geography.

16. An apparatus as defined in claim 9, wherein the second subset of categories includes at least one of households tuned to a particular station, households associated with a particular education level, households with a particular number of television sets, households tuned to a station during a particular daypart, or households having a particular life stage.

17. A tangible machine readable storage medium comprising instructions that, when executed, cause a machine to at least:

identify a target set of household categories associated with a target research geography;

when a quantity of panelist households within the target research geography representing the target set of household categories does not satisfy a threshold value sufficient to support statistical significance;

increase an available sample size of households by generating a first subset of categories and a second subset of categories from the target set of household categories;

identify a first set of households representing the first subset of categories from the target set of household categories and identify an associated total number of household tuning minutes and a total number of household exposure minutes associated with the first set of households;

for each category in the second subset of categories from the target set of household categories, calculate a household tuning proportion and an exposure proportion, the household tuning proportion for each category in the second subset based on a ratio of respective category tuning minutes and the total number of household tuning minutes associated with the first set of households, and the exposure proportion for each category in the second subset being based on a ratio of respective category exposure minutes and the total number of household exposure minutes associated with the first set of households; and

calculate a panelist behavior probability for the combined first and second subset of categories based on the respective exposure proportions and the household tuning proportions.

18. A storage medium as defined in claim 17, wherein the instructions, when executed, further cause the machine to apply a temporal weight to the total number of household tuning minutes, the temporal weight having a greater bias associated with a first portion of the total number of household tuning minutes acquired more recently than a second portion of the total number of tuning minutes.

19. A storage medium as defined in claim 18, wherein the instructions, when executed, further cause the machine to apply a proportionally lower weight to the second portion of the total number of tuning minutes having a relatively older acquisition timestamp.

20. A storage medium as defined in claim 17, wherein the instructions, when executed, further cause the machine to apply a temporal weight to the total number of household exposure minutes, the temporal weight having a greater bias associated with a first portion of the total number of household exposure minutes acquired more recently than a second portion of the total number of exposure minutes.

21. A storage medium as defined in claim 20, wherein the instructions, when executed, further cause the machine to

41

apply a proportionally lower weight to the second portion of the total number of exposure minutes having a relatively older acquisition timestamp.

22. A storage medium as defined in claim 17, wherein the instructions, when executed, further cause the machine to: 5
 multiply the household tuning proportions for each category together and multiply by the total number of household tuning minutes to calculate expected household tuning minutes associated with the second subset of categories; 10
 multiply the exposure proportions for each category together to form a combined exposure proportion; and
 multiply the combined exposure proportion by the total number of exposure minutes to calculate expected exposure minutes associated with the second subset of categories. 15

23. A storage medium as defined in claim 22, wherein the instructions, when executed, further cause the machine to identify the panelist behavior probability for the target research geography based on a ratio of the expected exposure 20 minutes and the expected household tuning minutes.

* * * * *

42

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 9,185,435 B2
APPLICATION NO. : 14/313390
DATED : November 10, 2015
INVENTOR(S) : Shankar et al.


Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

In the claims,

Column 39 line 19 (claim 9): delete “associated”

Signed and Sealed this
Eighth Day of March, 2016



Michelle K. Lee
Director of the United States Patent and Trademark Office