







Figure - 2





Figure - 3






Figure - 5




Figure - 6




Figure - 7





Figure - 8

Figure - 9

1

WIRELESS METHOD AND APPARATUS FOR MONITORING AND CONTROLLING FOOD TEMPERATURE

FIELD OF THE INVENTION

The invention relates generally to monitoring and controlling temperature and, more specifically, a method and apparatus for monitoring and controlling food temperature.

BACKGROUND OF THE INVENTION

Produced food travels from processing plants to grocery stores, where the food product remains on display case shelves for extended periods of time. For improved food quality, the food product should not exceed critical temperature limits while being displayed in the grocery store display cases. For uncooked food products, the product temperature should not exceed 41° F. For cooked food products, the product temperature should not be less than 140° F. In other words, the critical temperature limits are approximately 41° and 140° F. Between these critical temperature limits, bacteria grow at a faster rate.

One attempt to maintain food product temperature within safe limits is to monitor the discharge air temperature to ensure that the display case does not become too warm or too cold. But the food product temperature and discharge air temperature do not necessarily correlate; that is, discharge air temperature and food product temperature will not necessarily have the same temperature trend because food product temperatures can vary significantly from discharge air temperature due to the thermal mass of the food product. Further, during initial startup and display case defrost, the air temperature can be as high as 70° F. while food product temperature is much lower for this typically short interval. Finally, it is impractical to measure the temperature of food products at regular intervals in order to monitor food product temperature in a display case.

More specifically, in a conventional refrigeration system, a main controller typically logs or controls temperature. Conventionally, the main controller is installed in the compressor room, which is located on the roof or back of the grocery store. The conventional method for monitoring and controlling the display case temperature requires a discharge air temperature sensor mounted in the display case. The discharge air temperature sensor is typically connected to an analog input board, which is also typically located in the compressor room. A temperature wire must be pulled from the display case to the compressor room, which is typically difficult and increasingly expensive depending on how far away the compressor room is from the display case. Further, this wiring and installation process is more expensive and extremely cumbersome when retrofitting a store.

SUMMARY OF THE INVENTION

An apparatus, system, and method for controlling a refrigeration system according to the invention overcomes the limitations of the prior art by providing wireless transmission of simulated product temperature data. An apparatus according to the invention includes a plurality of circuits having at least one refrigeration case and a compressor rack. An electronic evaporator pressure regulator in communication with each circuit controls the temperature of one of the circuits. A sensor in communication with each circuit measures a parameter from the circuit, and a transceiver in communication with the sensor wirelessly transmits the

2

measured parameter. A receiver receives the wirelessly transmitted measured parameter. A controller in communication with the receiver controls each electronic evaporator pressure regulator and a suction pressure of said compressor rack based upon the wirelessly transmitted measured parameter from each of the circuits.

Preferably, at least one of the sensors in communication with each of the circuits is a product-simulating probe operable to simulate a product temperature. The probe for simulating product temperature includes a housing containing a thermal mass having thermo-physical properties similar to food product, and a temperature sensing element for measuring the temperature of the thermal mass. Preferably, the thermal mass is contained within a plastic bag within the housing. The transceiver, which is connected to the temperature-sensing element, wirelessly transmits the measured temperature data to the receiver. The transceiver may be disposed within the housing, or positioned external to the housing. The housing preferably includes a middle plate supporting the thermal mass in a first portion of the housing and containing the temperature sensing element in a second portion of said housing. Most preferably, the middle plate includes a channel communicating with the second portion and extending into the first portion, and the temperature-sensing element is positioned within the channel such that the thermal mass substantially surrounds the channel.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram of a refrigeration system employing a method and apparatus for refrigeration system control according to the teachings of the preferred embodiment in the present invention;

FIG. 2 is a perspective view of a product-simulating probe according to the invention;

FIG. 3 is a perspective view of the bottom of the product-simulating probe of FIG. 2;

FIG. 4 is an exploded view of the product-simulating probe of FIGS. 2 and 3;

FIG. 5 is a block diagram illustrating one configuration for transferring product temperature data from a display case to a main controller according to the invention;

FIG. 6 is a block diagram of another configuration for transferring product temperature data from a display case to a main controller according to the invention;

FIG. 7 is a block diagram illustrating yet another configuration for transferring product temperature data and other monitored data from a display case to a main controller according to the invention;

FIG. 8 is a flow chart illustrating circuit temperature control using an electronic pressure regulator; and

FIG. 9 is a flow chart illustrating floating circuit or case temperature control based upon a product simulator temperature probe.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring to FIG. 1, a detailed block diagram of a refrigeration system 10 according to the teachings of the preferred embodiment in the present invention is shown. The refrigeration system 10 includes a plurality of compressors 12 piped together in a compressor room 6 with a common suction manifold 14 and a discharge header 16 all positioned within a compressor rack 18. The compressor rack 18 compresses refrigerant vapor that is delivered to a condenser 20 where the refrigerant vapor is liquefied at high pressure.

3

This high-pressure liquid refrigerant is delivered to a plurality of refrigeration cases **22** in a grocery store floor space **8** by way of piping **24**. Each refrigeration case **22** is arranged in separate circuits **26** consisting of a plurality of refrigeration cases **22** that operate within a similar temperature range. FIG. 1 illustrates four (4) circuits **26** labeled circuit A, circuit B, circuit C and circuit D. Each circuit **26** is shown consisting of four (4) refrigeration cases **22**. Those skilled in the art, however, will recognize that any number of circuits **26** within a refrigeration system **10**, as well as any number of refrigeration cases **22** may be employed within a circuit **26**. As indicated, each circuit **26** will generally operate within a certain temperature range. For example, circuit A may be for frozen food, circuit B may be for dairy, circuit C may be for meat, etc.

Because the temperature requirement is different for each circuit **26**, each circuit **26** includes a pressure regulator **28**, preferably an electronic stepper regulator (ESR) or valve, that acts to control the evaporator pressure and hence, the temperature of the refrigerated space in the refrigeration cases **22**. Preferably, each refrigeration case **22** also includes its own evaporator and its own expansion valve (not shown), which may be either a mechanical or an electronic valve for controlling the superheat of the refrigerant. In this regard, refrigerant is delivered by piping **24** to the evaporator in each refrigeration case **22**. The refrigerant passes through the expansion valve where a pressure drop occurs to change the high-pressure liquid refrigerant to a lower-pressure combination of liquid and vapor. As the warmer air from the refrigeration case **22** moves across the evaporator coil, the low-pressure liquid turns into a gas. This low-pressure gas is delivered to the pressure regulator **28** associated with that particular circuit **26**. At the pressure regulator **28**, the pressure is dropped as the gas returns to the compressor rack **18** through the common suction manifold **14**. At the compressor rack **18**, the low-pressure gas is again compressed to a higher pressure and delivered to the condenser **20**, which again creates a high-pressure liquid to start the refrigeration cycle over.

To control the various functions of the refrigeration system **10**, a main refrigeration controller **30** is used and configured or programmed to execute a control algorithm and includes configuration and logging capabilities. The refrigeration controller **30** controls the operation of each pressure regulator (ESR) **28**, as well as the suction pressure set point for the entire compressor rack **18**. The refrigeration controller **30** is preferably an Einstein Area Controller offered by CPC, Inc. of Atlanta, Ga., or any other type of programmable controller that may be programmed, as discussed herein and as discussed more fully in U.S. patent application Ser. No. 09/539,563, filed Mar. 31, 2000, entitled "Method And Apparatus For Refrigeration System Control Using Electronic Evaporator Pressure Regulators," incorporated herein by reference. The refrigeration controller **30** controls the bank of compressors **12** in the compressor rack **18** through an input/output module **32**. The input/output module **32** has relay switches to turn the compressors **12** on and off to provide the desired suction pressure. A separate case controller, such as a CC-100 case controller, also offered by CPC, Inc. of Atlanta, Ga. may be used to control the superheat of the refrigerant to each refrigeration case **22** by way of a communication network or bus, as discussed more fully in the aforementioned U.S. patent application Ser. No. 09/539,563, filed Mar. 31, 2000, entitled "Method And Apparatus For Refrigeration System Control Using Electronic Evaporator Pressure Regulators."

4

Alternatively, a mechanical expansion valve may be used in place of the separate case controller. Should separate case controllers be utilized, the main refrigeration controller **30** may be used to configure each separate case controller, also via the communication bus.

In order to monitor the suction pressure for the compressor rack **18**, a pressure transducer **40** is preferably positioned at the input of the compressor rack **18** or just past the pressure regulators **28**. The pressure transducer **40** delivers an analog signal to an analog input board **38**, which measures the analog signal and delivers this information to the main refrigeration controller **30**, via the communication bus **34**. The analog input board **38** may be a conventional analog input board utilized in the refrigeration control environment. The pressure transducer **40** enables adaptive control of the suction pressure for the compressor rack **18**, further discussed herein and as discussed more fully in the aforementioned U.S. patent application Ser. No. 09/539 563, filed Mar. 31, 2000, entitled "Method And Apparatus For Refrigeration System Control Using Electronic Evaporator Pressure Regulators."

To vary the openings in each pressure regulator **28**, an electronic stepper regulator (ESR) board **42** drives up to eight (8) electronic stepper regulators **28**. The ESR board **42** is preferably an ESR-8 board offered by CPC, Inc. of Atlanta, Ga., which consists of eight (8) drivers capable of driving the stepper valves **28**, via control from the main refrigeration controller **30**. The main refrigeration controller **30**, input/output module **32**, and ESR board **42** are located in a compressor room **6** and are preferably daisy chained via the communication bus **34** to facilitate the exchange of data between them. The communication bus **34** is preferably either an RS-485 communication bus or a LonWorks Echelon bus.

The suction pressure at the compressor rack **18** is dependent in the temperature requirement for each circuit **26**. For example, assume circuit A operates at 10° F., circuit B operates at 15° F., circuit C operates at 20° F. and circuit D operates at 25° F. The suction pressure at the compressor rack **18**, which is sensed through the pressure transducer **40**, requires a suction pressure set point based on the lowest temperature requirement for all the circuits **26**, which, for this example, is circuit A, or the lead circuit. Therefore, the suction pressure at the compressor rack **18** is set to achieve a 10° F. operating temperature for circuit A. This requires the pressure regulator **28** to be substantially opened 100% in circuit A. Thus, if the suction pressure is set for achieving 10° F. at circuit A and no pressure regulator valves **28** were used for each circuit **26**, each circuit **26** would operate at the same temperature. Because each circuit **26** is operating at a different temperature, however, the electronic stepper regulators or valves **28** are closed a certain percentage for each circuit **26** to control the corresponding temperature for that particular circuit **26**. To raise the temperature to 15° F. for circuit B, the stepper regulator valve **28** in circuit B is closed slightly, the valve **28** in circuit C is closed further, and the valve **28** in circuit D is closed even further providing for the various required temperatures.

Each electronic pressure regulator (ESR) **28** is preferably controlled by the main controller **30** based on food product temperatures approximated by a product simulating probe **50**, or based on multiple temperature readings including air-discharge temperature sensed by a discharge temperature sensor **48** and/or food product temperatures approximated by a product simulating probe **50** and transmitted through a display module **46**.

In order to control the opening of each pressure regulator **28** based on the temperature of the food product inside each

5

refrigeration case 22, the product temperature is approximated using the product-simulating probe 50 according to the invention. In this regard, each refrigeration case 22 is shown having a product-simulating probe 50 associated therewith. Each refrigeration case 22 may have a separate product-simulating probe 50 to take average/minimum/maximum temperatures used to control the pressure regulator 28 or a single product-simulating probe 50 may be used for a given circuit 26 of refrigeration cases 22, especially because each refrigeration case 22 in operates within substantially the same temperature range for a given circuit 26. These temperature inputs are wirelessly transmitted to an analog input receiver 94, which returns the information to the main refrigeration controller 30 via a communication bus 96.

The product-simulating probe 50, as shown in FIGS. 2-4, provides temperature data to the main controller 30. Preferably, the product simulating probe 50 is an integrated temperature measuring and transmitting device including a box-like housing 70 encapsulating a thermal mass 74 and a temperature sensing element 80 and including a wireless transceiver 82. The housing 70 includes a cover 72 secured to a base 86, and magnets 84 mounted to the cover 72 facilitate easy attachment of the probe 50 to the display case 22. Preferably, the cover 72 is adhered to the base 86 to seal the thermal mass 74 therein. In place of magnets 84, a bracket 85 may be used by securing the bracket 85 to the display case 22 and attaching the probe 50 by sliding the bracket into a complimentary slot 87 on the base 86 of the probe 50.

The thermal mass 74 is a container housing a material having thermo-physical characteristics similar to food product. Because food product predominantly contains water, the thermo-physical simulating material is preferably either salt water or a solid material that has the same thermal characteristics as water, such as low-density polyethylene (LDPE) or propylene glycol. The container for the thermal mass is preferably a plastic bag, and most preferably a pliable polypropylene bag, sealably containing the simulating material. Alternatively, a more rigid material can be used, but should include a centrally disposed channel 77 for accommodating the temperature sensing element 80 in close proximity to the material having thermo-physical characteristics similar to food product. Preferably, the thermal mass 74 is a 16-ounce (1-pint) sealed-plastic container filled with four percent (4%) salt water.

The temperature-sensing element 80 is embedded in the center of the thermal mass 74 so that the temperature product probe 50 measures the simulated internal temperature of food products. The temperature-sensing element 80 is preferably a thermistor. A middle plate 78 seals the temperature sensing element 80 and transceiver 82 relative the thermal mass 74 and includes a transversely extending tube 76 that supports the temperature sensing element 80 within the channel 77 of the thermal mass 74. When a pliable plastic material is used to contain the material having thermo-physical characteristics similar to food product, the pliable plastic material forms the channel 77 by accommodating the tube 76 within the thermal mass 74. A gasket 89 is disposed between the middle plate 78 and the base 86 to seal the space between the middle plate 78 and the bottom of the base 86 containing the transceiver 82. Fasteners 91 received through the base 86 secure the middle plate 78 to the base 86 through threaded reception in nut inserts 93 in-molded or secured to the middle plate 78.

The wireless transceiver 82 preferably includes a signal-conditioning circuit, is mounted between the base 86 and the

6

middle plate 82, and is connected to the temperature sensing element 80 via a wire 88. The wireless transceiver 82 is preferably a radio frequency (RF) device that transmits and receives parametric data and control inputs and outputs. Preferably, the wireless transceiver 82 is a standalone transceiver and/or transmitter that can be positioned independently of other hardware, such as repeaters, operating on internal or external power, that retransmit at the same or different radio frequencies as the parametric data and control inputs and outputs, and one or more transceivers 82 or receivers 94 that are linked to the main controller 30. The wireless transceiver 82 preferably operates on an internal power source, such as a battery, but can alternatively be powered by an external power source.

Preferably, as shown in FIG. 5, the product simulating probe 50 monitors the performance of the display case 22. Preferably, one probe 50 is placed within each display case 22. The product-simulating probe 50 wirelessly transmits simulated product temperature data to the receiver 94, which collects the temperature data and retransmits it to the main controller 30 via the communication bus 96. The main controller 30 logs and analyzes the temperature data, and controls the temperature of the display cases 22 based on the monitored temperature data.

As shown in FIG. 6, an alternative embodiment of the invention includes disposing a transceiver 82' apart from a product simulating probe 50' and then connecting the transceiver 82' to the probe 50' via a wire 84. For this variation of the invention, the product simulating probe 50' does not include an internal transceiver 82, but is connected to an external transceiver 82' connected to the temperature sensing element 80 via the wire 84. Optionally, as shown, a discharge air temperature sensor 48, or any other sensor, can similarly be connected to the transceiver 82' for transmission of measured data. The wireless transceiver 82' is mounted externally on the display case 22; for example, mounted on the top of the display case 22. The method of transmitting the temperature data from the product simulating probe 50' to the main controller 30 remains the same as described above.

As opposed to using an individual product simulating probe 50 or probe 50' with an external transceiver 82' to transmit the temperature for a refrigeration case 22 to the receiver 94, a temperature display module 46 may alternatively be used as shown in FIG. 7. The temperature display module 46 is preferably a TD3 Case Temperature Display, also offered by CPC, Inc. of Atlanta, Ga. The display module 46 is preferably mounted in each refrigeration case 22, and is connected to a wireless transceiver 82'. Each module 46 preferably measures up to three (3) temperature signals, but more or fewer can be measured depending on the need. These measured signals include the case discharge air temperature measured by a discharge temperature sensor 48, the simulated product temperature measured by a product simulator temperature probe 50', and a defrost termination temperature measured by a defrost termination sensor 52. These sensors may also be interchanged with other sensors, such as return air sensor, evaporator temperature or clean switch sensor. The display module 46 also includes an LED display 54 that can be configured to display any of the temperatures and/or case status (defrost/refrigeration/alarm).

The display module 46 will measure the case discharge air temperature, via the discharge temperature sensor 48 and the product simulated temperature, via the product probe temperature sensor 50 and then wirelessly transmit this data to the main refrigeration controller 30 via the wireless transceiver 82', which transmits data to the receiver 94 connected

to the main controller **30** via the communication bus **96**. This information is logged and used for subsequent system control utilizing the novel methods discussed herein.

Further, the main controller **30** can be configured by the user to set alarm limits for each case **22**, as well as defrosting parameters, based on temperature data measured by the probe **50**, or discharge temperature sensor **48**, or any other sensor including the defrost termination sensor **52**, return air sensor, evaporator temperature or clean switch sensor. When an alarm occurs, the main controller **30** preferably notifies a remotely located central monitoring station **100** via a communication bus **102**, including LAN/WAN or remote dial-up using, e.g., TCP/IP. Further, the main controller **30** can notify a store manager or refrigeration service company via a telephone call or page using a modem connected to a telephone line. The alarm and defrost information can be transmitted from the main refrigeration controller **30** to the display module **46** for displaying the status on the LED display **54**.

Referring to FIG. **8**, a temperature control logic **70** is shown to control the electronic pressure regulator (ESR) **28** for the particular circuit **26** being analyzed. In this regard, each electronic pressure regulator **28** is controlled by measuring the case temperature with respect to the particular circuit **26**. As shown in FIG. **1**, each circuit A,B,C,D includes product-simulating probes **50**, **50'** that wirelessly transmit temperature data to the analog signal receiver **94**. The receiver **94** measures the case temperature and transmits the data to the refrigeration controller **30** using the communication network **34**. The temperature control logic or algorithm **70** is programmed into the refrigeration controller **30**.

The temperature control logic **110** may either receive case temperatures ($T_1, T_2, T_3, \dots T_n$) from each case **22** in the particular circuit **26** or a single temperature from one case **22** in the circuit **26**. Should multiple temperatures be monitored, these temperatures ($T_1, T_2, T_3, \dots T_n$) are manipulated by an average/min/max temperature block **72**. Block **72** can either be configured to take the average of each of the temperatures ($T_1, T_2, T_3, \dots T_n$) received from each of the cases **22**. Alternatively, the average/min/max temperature block **112** may be configured to monitor the minimum and maximum temperatures from the cases **22** to select a mean value to be utilized or some other appropriate value. Selection of which option to use will generally be determined based upon the type of hardware utilized in the refrigeration control system **10**. From block **112**, the temperature (T_{ct}) is applied to an error detector **114**. The error detector **114** compares the desired circuit temperature set point (SP_{ct}) which is set by the user in the refrigeration controller **30** to the actual measured temperature (T_{ct}) to provide an error value (E_{ct}). Here again, this error value (E_{ct}) is applied to a PI/PID/Fuzzy Logic algorithm **108**, which is a conventional refrigeration control algorithm, to determine a particular percent (%) valve opening (VO_{ct}) for the particular electronic pressure regulator (ESR) **28** being controlled via the ESR board **42**.

While the temperature control logic **110** is efficient to implement, logistically it had inherent disadvantages. For example, each case temperature measurement sensor required connecting each display case **22** to the analog input board **38**, which is generally located in the compressor room **6**. This created a lot of wiring and high installation costs. The invention described herein, however, overcomes this limitation by wirelessly arranging the transmission of temperature data from product simulating probes **50**, **50'**, or from other temperature sensors including the discharge temperature sensor **48**, defrost termination sensor **52**, return air

sensor, evaporator temperature or clean switch sensor, etc. A further improvement to this configuration is to use the display module **46**, as shown in circuit A of FIG. **1**, as well as FIG. **7**. In this regard, a temperature sensor within each case **22** passes the temperature information to the display module **46**, which wirelessly transmits the data to the receiver **94**, which sends the data to the controller **30**. Under either version, the temperature data is transferred directly from the refrigeration case **22** to the refrigeration controller **30** without the need for the analog input board **38**, or for wiring the various sensors to the analog input board **38**, thereby substantially reducing wiring and installation costs.

Referring now to FIG. **9**, a floating circuit temperature control logic **116** is illustrated based upon temperature measurements from the product-simulating probe **50**, **50'**. The floating circuit temperature control logic **116** begins at start block **118**. From start block **118**, the control logic proceeds to differential block **120**. In differential block **120**, the average product simulation temperature for the past one-hour or other appropriate time period is subtracted from a maximum allowable product temperature to determine a difference (diff). In this regard, measurements from the product probe **50** are preferably taken, for example, every ten seconds with a running average taken over a certain time period, such as one hour. The type of product being stored in the particular refrigeration case **22** generally controls the maximum allowable product temperature. For example, for meat products, a limit of 41° F. is generally the maximum allowable temperature for maintaining meat in a refrigeration case **22**. To provide a further buffer, the maximum allowable product temperature can be set 5° F. lower than this maximum (i.e., 36° for meat).

From differential block **120**, the control logic **116** proceeds to determination block **122**, determination block **124** or determination block **126**. In determination block **122**, if the difference between the average product simulator temperature and the maximum allowable product temperature from differential block **120** is greater than 5° F., a decrease of the temperature set point for the particular circuit **26** by 5° F. is performed at change block **128**. From here, the control logic returns to start block **118**. This branch identifies that the average product temperature is too warm, and therefore, needs to be cooled down. At determination block **124**, if the difference is greater than -5° F. and less than 5° F., this indicates that the average product temperature is sufficiently near the maximum allowable product temperature and no change of the temperature set point is performed in block **130**. Should the difference be less than -5° F. as determined in determination block **126**, an increase in the temperature set point of the circuit by 5° F. is performed in block **132**.

By floating the circuit temperature for the entire circuit **26** or the particular case **22** based upon the simulated product temperature, the refrigeration case **22** may be run in a more efficient manner since the control criteria is determined based upon the product temperature and not the case temperature which is a more accurate indication of desired temperatures. It should further be noted that while a differential of 5° F. has been identified in the control logic **116**, those skilled in the art would recognize that a higher or a lower temperature differential, may be utilized to provide even further fine tuning and all that is required is a high and low temperature differential limit to float the circuit temperature. It should further be noted that by using the floating circuit temperature control logic **116** in combination with the floating suction pressure control logic **80** further energy efficiencies can be realized. Variations of the above appara-

9

tus and method are described in U.S. patent application Ser. No. 09/539,563, filed Mar. 31, 2000, entitled "Method And Apparatus For Refrigeration System Control Using Electronic Evaporator Pressure Regulators," incorporated herein by reference.

The foregoing discussion discloses and describes merely exemplary embodiments of the present invention. One skilled in the art will readily recognize from such discussion, and from the accompanying drawings and claims, that various changes, modifications and variations can be made therein without departing from the spirit and scope of the invention.

What is claimed is:

1. A system for controlling refrigeration, comprising:
 - at least one refrigeration case;
 - a simulated product temperature sensor operable to measure a simulated product temperature from said at least one refrigeration case;
 - a transceiver in communication with said simulated product temperature sensor and operable to wirelessly transmit data including said simulated product temperature;
 - a receiver adapted to receive said wirelessly transmitted data including said simulated product temperature;
 - a controller in communication with said receiver and operable to control a temperature of said at least one refrigeration case based upon said wirelessly transmitted data from said at least one refrigeration case.
2. The system of claim 1 wherein said simulated product temperature sensor includes a housing containing a thermal mass having thermo-physical properties similar to food product, and a thermistor for measuring the temperature of said thermal mass.
3. The system of claim 2 wherein said thermistor is positioned approximately centrally in said thermal mass.
4. The system of claim 3 wherein said thermal mass is salt water.
5. The system of claim 4 wherein said transceiver is disposed within said container.
6. The system of claim 4 wherein said transceiver is positioned external to said container.
7. The system of claim 1 further comprising an ambient case air temperature sensor operable to measure an ambient case air temperature in said at least one refrigeration case and in communication with said transceiver.
8. The system of claim 1 further comprising a defrost termination temperature sensor operable to measure a defrost termination temperature in said at least one refrigeration case and in communication with said transceiver.
9. The system of claim 1 further comprising a temperature display module connected to an ambient temperature sensor operable to measure an ambient refrigerant temperature, a defrost termination temperature sensor operable to measure a defrost termination temperature and said simulated product temperature sensor; said wirelessly transmitted data further including said ambient air temperature and said defrost termination temperature; said temperature display module being in communication with said transceiver for wirelessly transmitting said data to said receiver.
10. The system of claim 1 wherein said controller is configured to include user-defined alarm limits for said wirelessly transmitted data and further comprising a remote monitoring station for remote monitoring said wirelessly transmitted data and remotely signaling said alarm limits.
11. A method for refrigeration system control, said method comprising:
 - setting a maximum allowable product temperature for a circuit having at least one refrigeration case;

10

determining a simulated product temperature for the circuit;

wirelessly transmitting said simulated product temperature from said circuit to a system controller;

calculating a difference between the simulated product temperature and the maximum allowable product temperature; and

adjusting a temperature set point of the circuit based upon the calculated difference.

12. The method as defined in claim 11 further comprising decreasing the temperature set point of the circuit if the calculated difference is greater than a first limit and increasing the temperature set point of the circuit if the calculated difference is less than a second limit.

13. The method as defined in claim 12 further comprising maintaining the temperature set point of the circuit if the calculated difference is between the first limit and the second limit.

14. The method as defined in claim 11 wherein said simulated product temperature is an average simulated product temperature based upon a plurality of simulated product temperatures taken over a predetermined period.

15. The method as defined in claim 11 further comprising the step of configuring said system controller to include user-defined alarm limits for a predetermined calculated difference between said simulated product temperature and said maximum allowable product temperature.

16. The method as defined in claim 11 further comprising the step of remotely monitoring said simulated product temperature.

17. A method for refrigeration system control, said method comprising:

- measuring a first parameter from at least one refrigeration case;

- wirelessly transmitting said measured first parameter to a receiver;

- communicating said measured first parameter from said receiver to a controller;

- electronically controlling said at least one refrigeration case to affect said measured first parameter;

- measuring a second parameter from another refrigeration case;

- wirelessly transmitting said measured second parameter to said receiver;

- communicating said measured second parameter from said receiver to said controller;

- electronically controlling said another refrigeration case to affect said measured second parameter; and

- floating a circuit temperature set point based upon said measured first parameter.

18. A method for refrigeration system control, said method comprising:

- measuring a first parameter from at least one refrigeration case in a first refrigeration circuit;

- measuring a second parameter from at least one other refrigeration case in a second refrigeration circuit;

- wirelessly transmitting said measured first parameter and said measured second parameter to a receiver;

- communicating said measured first parameter and said measured second parameter to a controller;

- electronically controlling said at least one refrigeration case to affect said measured first parameter;

- electronically controlling said at least one other refrigeration case to affect said measured second parameter; and

11

floating a circuit temperature set point of at least one of said first circuit and said second circuit based upon said measured first parameter or said measured second parameter.

19. A method for refrigeration system control, said method comprising:

measuring a simulated product temperature measurement from at least one refrigeration case;

wirelessly transmitting said simulated product temperature measurement to a receiver;

communicating said simulated product temperature measurement to a controller; and

electronically controlling said at least one refrigeration case to affect said simulated product temperature measurement.

20. A method for refrigeration system control comprising: measuring a first parameter from at least one refrigeration case;

wirelessly transmitting said measured first parameter to a receiver;

communicating said measured first parameter from said receiver to a controller; and

electronically controlling said at least one refrigeration case to affect said measured first parameter

measuring a second parameter from another refrigeration case;

wirelessly transmitting said measured second parameter to said receiver;

12

communicating said measured second parameter from said receiver to said controller; and

electronically controlling said another refrigeration case to affect said measured second parameter;

wherein said first parameter is a defrost termination temperature measurement of said at least one refrigeration case and said second parameter is an ambient case air temperature of said another refrigeration case.

21. A method for refrigeration system control comprising: measuring a first parameter from at least one refrigeration case in a first refrigeration circuit;

measuring a second parameter from at least one other refrigeration case in a second refrigeration circuit;

wirelessly transmitting said measured first parameter and said measured second parameter to a receiver;

communicating said measured first parameter and said measured second parameter from said receiver to a controller;

electronically controlling said at least one refrigeration case to affect said measured first parameter; and

electronically controlling said at least one other refrigeration case to affect said measured second parameter;

wherein said first parameter is a defrost termination temperature measurement of said at least one refrigeration case and said second parameter is an ambient case air temperature of said at least one other refrigeration case.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 6,502,409 B1
DATED : January 7, 2003
INVENTOR(S) : William Gatling et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Title page.

Item [56], **References Cited**, U.S. PATENT DOCUMENTS, "4,829,779" reference,
"Munsone t al." should be -- Munson et al. --.

Column 3.

Line 42, "executes" should be -- execute --.
Line 64, after "fully" insert -- in --.

Column 4.


Line 17, "09/539 563" should be -- 09/539,563 --.

Column 5.

Line 9, after "case 22" delete "in".
Line 29, "complimentary" should be -- complementary --.
Line 52, after "relative" insert -- to --.

Signed and Sealed this

Eighteenth Day of November, 2003

A handwritten signature in black ink, appearing to read "James E. Rogan", written over a horizontal line.

JAMES E. ROGAN
Director of the United States Patent and Trademark Office