IEEE.org IEEE Xplore IEEE SA IEEE Spectrum More Sites Donate Cart Create Account Personal Sign In

Downl PDF

Browse My Settings Help

Access provided by: Sidley Austin LLP File Cabinet Sign Out Show Usage

Access provided by: Sidley Austin LLP File Cabinet Sign Out Show Usage

All

ADVANCED SEARCH

Conferences > 2014 IEEE 40th Photovoltaic S...

Comparison of POCl3 diffusion with phosphorus ion implantation for Czochralski and Quasi-mono silicon solar cells

Publisher: IEEE

Cite This PDF

Eunhwan Cho ; Youngwoo Ok ; Kyungsun Ryu ; Brian Rounsaville ; Ajay D. Upadhyaya ; Vijaykumar Upadhyaya ; Ajeet Rohatgi All Authors

4 Cites in Papers

248 Full Text Views

Alerts

Manage Content Alerts

Add to Citation Alerts

Abstract

Document Sections

I. Introduction

II. Experimental

III. Results and Discussion

IV. Conclusion

Authors

Figures

References

Citations

Keywords

Metrics

More Like This

Abstract:
Both ion implanted and POCl 3 diffused emitters are used for industrial production of p-type Si solar cells. Formation of phosphorus doped emitter is known to perform ge... **View more**

Metadata

Abstract:
Both ion implanted and $POCl_3$ diffused emitters are used for industrial production of p-type Si solar cells. Formation of phosphorus doped emitter is known to perform gettering of impurities, however, gettering efficiency of these two diffusion techniques is not well quantified for single crystal Cz Si and Cast multi or Quasi-mono Si wafers. In addition, ion implantation can provide higher quality emitter with in situ oxide passivation[1]. This paper compares the performance of Quasi-mono and Cz Si cells fabricated with $POCl_3$ and ion-implanted emitters. Quasi-mono wafers have more defects and are expected to benefit from gettering. Large area screen printed p-type industrial cells with full Al-BSF cell structure were fabricated on commercial grade single crystal Cz Si and two different Cast Quasi-mono Si wafers with 50% and 80% mono-crystalline regions. Bulk lifetime was measured to evaluate the gettering efficiency of each technology before and after each emitter formation[2]. $POCl_3$ diffusion gave greater improvement in bulk lifetime of Quasi-mono wafers compared to ion implanted wafers, resulting in 0.7 ~ 1% higher absolute efficiency and over 5 ~ 15mV higher Voc compared to the implanted cells. However, in the case of Cz cells, bulk lifetime remained high and comparable for the two emitters. Therefore, Cz cells with implanted emitter gave 0.4% higher efficiency and 7mV higher Voc due to a higher quality emitter with in situ front oxide passivation.

Published in: 2014 IEEE 40th Photovoltaic Specialist Conference (PVSC)

Date of Conference: 08-13 June 2014

DOI: 10.1109/PVSC.2014.6925554

Date Added to IEEE *Xplore*: 16 October 2014

Publisher: IEEE

ISBN Information:

Conference Location: Denver, CO, USA

Print ISSN: 0160-8371

References is not available for this document.

Contents

I. Introduction

Crystalline Si cells account for ~ 90% of the market share with ~ 55% cast Si cells and ~35% single crystal Cz cells [3]. Cast Si wafers are produced by conventional directional solidification process and by tailoring the growth conditions and seeding one can make either multi or Quasi-mono Si. Even though cast Si wafers have the advantage of lower cost, these wafers produce somewhat lower cell efficiency due to impurities, dislocations and grain boundaries. PV industry is trying to improve cast Si material by introducing single crystal seed and by tailoring the growth conditions which can lead to nearly mono or Quasi-mono materials [4]. Cast materials are known to benefit significantly from the traditional $POCl_3$ emitter formation due to gettering of defects and impurities which drives the impurities into the emitter region via a kickout mechanism [5]. However, it has been shown recently that the emerging ion-implanted emitter can lead to higher quality and more uniform emitter which also benefits from in situ oxide passivation during the implant annealing. This paper compares the $POCl_3$ diffused emitter and the ion-implanted emitter cells on Cz and Cast Si materials to assess the trade-off between gettering and quality of the two types of emitters.

Continue Reading

Authors

Figures

References

Export

References & Cited By

Select All

1. A. Rohatgi, D. L. Meier, B. McPherson, Y.-W. Ok, A. D. Upadhyaya, J.-H. Lai, et al., "High-throughput ionimplantation for low-cost high-efficiency silicon solar cells", Energy Procedia, Vol. 15, pp. 10-19, 2012.
CrossRef Google Scholar

2. T. S. Horanyi, T. Pavelka, and P. Tutto, "Insitu Bulk Lifetime Measurement On Silicon With a Chemically Passivated Surface", Applied Surface Science, Vol. 63, pp. 306-311, Jan 1993.
CrossRef Google Scholar

3. M. Abdelhamid, R. Singh, and M. Omar, "Review of Microcrack Detection Techniques for Silicon Solar Cells", Ieee Journal of Photovoltaics, Vol. 4, pp. 514-524, Jan 2014.
View Article Google Scholar

4. B. Wu, N. Stoddard, R. Ma, and R. Clark, "Bulk multicrystalline silicon growth for photovoltaic (PV) application", Journal of Crystal Growth, Vol. 310, pp. 2178-2184, Apr 2008.
CrossRef Google Scholar

5. J. S. Kang and D. K. Schroder, "Gettering In Silicon", Journal of Applied Physics, Vol. 65, pp. 2974-2985, Apr 1989.
CrossRef Google Scholar

6. B. Rounsaville, I. B. Cooper, K. Tate, M. Kadish, A. Das, and A. Rohatgi, "Analysis of cast mono-crystalline ingot characteristics with applications to solar cells", in Photovoltaic Specialists Conference (PVSC), 2012 38th IEEE, pp. 003009-003014, 2012.
View Article Google Scholar

7. V. Vahanissi, A. Haarahiltunen, M. Yli-Koski, and H. Savin, "Gettering of Iron in Silicon Solar Cells With Implanted Emitters", Ieee Journal of Photovoltaics, Vol. 4, pp. 142-147, Jan 2014.
View Article Google Scholar

8. A. Cuevas and D. Macdonald, "Measuring and interpreting the lifetime of silicon wafers", Solar Energy, Vol. 76, pp. 255-262, 2004.
CrossRef Google Scholar

Downl PDF

View More

Citations

Keywords

Metrics

More Like This

Tradeoffs Between Impurity Gettering, Bulk Degradation, and Surface Passivation of Boron-Rich Layers on Silicon Solar Cells
IEEE Journal of Photovoltaics
Published: 2013

Passivation Effects on Low-Temperature Gettering in Multicrystalline Silicon
IEEE Journal of Photovoltaics
Published: 2017

Show More

Downl
PDF

IEEE Personal Account

CHANGE USERNAME/PASSWORD

Purchase Details

PAYMENT OPTIONS

VIEW PURCHASED DOCUMENTS

Profile Information

COMMUNICATIONS PREFERENCES

PROFESSION AND EDUCATION

TECHNICAL INTERESTS

Need Help?

US & CANADA: +1 800 678 4333

WORLDWIDE: +1 732 981 0060

CONTACT & SUPPORT

Follow

About IEEE *Xplore* | Contact Us | Help | Accessibility | Terms of Use | Nondiscrimination Policy | IEEE Ethics Reporting | Sitemap | IEEE Privacy Policy

A not-for-profit organization, IEEE is the world's largest technical professional organization dedicated to advancing technology for the benefit of humanity.

© Copyright 2024 IEEE - All rights reserved, including rights for text and data mining and training of artificial intelligence and similar technologies.

IEEE Account

» Change Username/Password

» Update Address

Purchase Details

» Payment Options

» Order History

» View Purchased Documents

Profile Information

» Communications Preferences

» Profession and Education

» Technical Interests

Need Help?

Downl
PDF

» **US & Canada:** +1 800 678 4333

» **Worldwide:** +1 732 981 0060

» Contact & Support

About IEEE *Xplore* | Contact Us | Help | Accessibility | Terms of Use | Nondiscrimination Policy | Sitemap | Privacy & Opting Out of Cookies

A not-for-profit organization, IEEE is the world's largest technical professional organization dedicated to advancing technology for the benefit of humanity.
© Copyright 2024 IEEE - All rights reserved. Use of this web site signifies your agreement to the terms and conditions.