



US 20040133787A1

(19) **United States**(12) **Patent Application Publication****Doughty et al.**(10) **Pub. No.: US 2004/0133787 A1**(43) **Pub. Date:****Jul. 8, 2004**

(54) **SYSTEM, METHOD AND APPARATUS FOR
ENABLING TRANSACTIONS USING A
BIOMETRICALLY ENABLED
PROGRAMMABLE MAGNETIC STRIPE**

(60) Provisional application No. 60/368,363, filed on Mar. 28, 2002.

Publication Classification

(75) Inventors: **Ralph O. Doughty**, Colleyville, TX
(US); **Patrick R. Antaki**, Plano, TX
(US)

(51) **Int. Cl.⁷** **H04L 9/00**

(52) **U.S. Cl.** **713/186**

Correspondence Address:

CHALKER FLORES, LLP
12700 PARK CENTRAL, STE. 455
DALLAS, TX 75251 (US)

(57) **ABSTRACT**

The present invention provides a system, method and apparatus that includes a user device having a magnetic field generator disposed within a substrate that is normally inactive, a biometric sensor mounted on the substrate, a memory disposed within the substrate and a processor disposed within the substrate that is communicably coupled to the magnetic field generator, the biometric sensor and the memory. The processor is operable to process biometric information received from the biometric sensor to verify that a user is authorized to use the apparatus and activate the magnetic field generator when the user is verified. A power source is also disposed within the substrate. The magnetic field generator can create a spatially varying magnetic signal using a magnetic stripe and one or more induction coils, or create a time-varying magnetic signal for emulating data obtained from swiping a magnetic stripe card through a magnetic card reader.


(73) Assignee: **Innovation Connection Corporation**,
Richardson, TX (US)

(21) Appl. No.: **10/680,050**

(22) Filed: **Oct. 7, 2003**

Related U.S. Application Data

(63) Continuation-in-part of application No. 10/400,306,
filed on Mar. 27, 2003.






FIG. 1 (PRIOR ART)




FIG. 2 (PRIOR ART)




FIG. 3




FIG. 4A




FIG. 4B




FIG. 5A




FIG. 5B





FIG. 6






Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12




Fig. 13A




Fig. 13B




Fig. 14




Fig. 15




Fig. 16




Fig. 17




Fig. 18




Fig. 19




Fig. 20

SYSTEM, METHOD AND APPARATUS FOR ENABLING TRANSACTIONS USING A BIOMETRICALLY ENABLED PROGRAMMABLE MAGNETIC STRIPE

PRIORITY CLAIM

[0001] This patent application is a continuation-in-part of U.S. patent application Ser. No. 10/400,306 filed on Mar. 27, 2003, which is a non-provisional patent application of U.S. provisional patent application serial No. 60/368,363 filed on Mar. 28, 2002.

TECHNICAL FIELD OF THE INVENTION

[0002] The present invention relates generally to the field of electronic devices and equipment used in the authentication and processing of commercial and security related transactions and, more particularly, to a system, method and apparatus for enabling transactions using biometrically enabled programmable magnetic stripes.

BACKGROUND OF THE INVENTION

[0003] The security of current magnetic stripe cards is suspect due to the ease of card theft and 'skimming' of card data for creating and using fake cards. As shown in **FIG. 1**, current magnetic stripe cards **100**, such as access, credit, debit, identification, security, stored value and vendor-specific cards, typically have a strip of magnetic material **102**, which is commonly referred to as a magnetic stripe, embedded in a plastic or laminated substrate **104**. This magnetic stripe **102** carries data for the cardholder, such as name, account number, card expiration date, and other important information. This information is typically stored in three data tracks within the magnetic stripe **102** that carry a pattern of magnetization, which is a magnetic representation of the stored information. Other common features of magnetic stripe cards **100** that are well known to those skilled in the art, such as the cardholder's name, account number, expiration date, issuer, signature stripe, validation code, photograph, etc., are not shown. The magnetic patterns on the magnetic stripes **102** are easily created, read and damaged. As a result, the security of cards **100** that rely solely on magnetic stripes **102** for information storage and authentication is low and renders their use in applications involving highly sensitive information suspect. These types of cards are easily stolen and/or the data is "skimmed" for the creation and use of fake or counterfeit cards.

[0004] One way to increase the security of information bearing cards is the use of smart cards, also referred to as chip cards. Although smart cards **200** may also include a magnetic stripe, they primarily rely on an integrated circuit, also commonly referred to as a controller or processor, embedded within the plastic or laminated substrate **204** below the terminals **202** to store the cardholder's information as shown in **FIG. 2**. The integrated circuit is communicably coupled to a set of metallic terminals **202** that are designed to interface with a special reader. Other common features of smart cards **200** that are well known to those skilled in the art, such as the cardholder's name, account number, expiration date, issuer, signature stripe, validation code, photograph, etc., are not shown. A smart card **200** is capable of incorporating multiple applications or accounts on a single card or other media. As a result, smart cards **200**

are widely recognized as a viable way to improve the effectiveness and security of a given card or device. Such smart cards **200** require a different reader from the standard magnetic stripe readers that currently make up virtually the entire card reader infrastructure throughout the world. As a result, the acceptance and wide-spread use of "true" smart cards (without a magnetic stripe) has been slow.

[0005] Various compromise technologies have been developed that incorporate some of the flexibility and security features of smart cards into a magnetic stripe card using either an adapter or a programmable magnetic stripe. For example, a smart card to magnetic stripe adapter is disclosed in US Patent Application Publication 2003/0057278 A1 published on Mar. 27, 2003 entitled "Advanced Magnetic Stripe Bridge (AMSB)" by Jacob Y. Wong. The Wong patent application describes an adapter or bridge that is used with magnetic stripe card readers such that a smart card or other card without a magnetic stripe can be placed into the bridge and electrically connected to the card. The bridge has one edge that is the size of a credit card so that the bridge can be swiped through the magnetic stripe reader while the card is still in the bridge. With this link in place, the data from the card is transmitted from the on-card processor through the bridge in a format that emulates the data generated by swiping the track(s) of a typical magnetic card through a magnetic stripe reader. As a result, the magnetic stripe reader is able to accept data from the magnetic stripe-less card. Similarly, one developer, ViVOTech, Inc., places a fixed bridge in the magnetic stripe reader that is capable of receiving radio frequency ("RF") data and then emulates the feed of data into the magnetic stripe reader via RF to complete the transaction without requiring physical contact of the card with the reader. Both of these technologies require either a fixed or mobile adaptor to be added to the card-reader infrastructure to enable data to be read from the card. While this is possible, it is still a modification to the world-wide infrastructure that is undesirable for unfettered use of the card. The use of such a bridge is cumbersome, adds cost and reduces reliability. In addition, this method also does not incorporate authentication of the user to provide protections against skimming or use by unauthorized individuals.

[0006] The use of a programmable magnetic stripe is disclosed in US Patent Application Publication 2002/0003169 A1 published on Jan. 10, 2002 entitled "Universal Credit Card Apparatus and Method" by J. Carl Cooper. The Cooper patent application describes a card in which a number of electrical coils are built into the card with one coil under each data bit on the magnetic stripe on the card so that each coil, when excited under the control of the on-card processor, creates a magnetic field that can magnetize the data bit in the magnetic track to be either a 0 or 1, thereby yielding a binary code that, when applied in accordance with the ISO standard for magnetic stripe cards, can be read by standard card readers. With this on-card capability in place, the processor can essentially "write" any data stored in the processor's memory to the on-card magnetic stripe. As with the adapter, the Cooper patent application does not provide any protections against card skimming or use by unauthorized persons. Moreover, because of the need for numerous individual coils (one beneath each data bit on the magnetic stripe), significant cost is incurred when adding these coils to the on-card design. The power requirements of such a card are also problematic.

[0007] There is, therefore, a need for a practical and secure card that has the advantages of a smart card and will interface with magnetic stripe readers without the use of adapters. Moreover, there is a need for a proper authentication in multiple account/application cards and devices to reduce the risk to the device holder in the event of loss or fraudulent capture of the data within the multiple accounts on the device.

SUMMARY OF THE INVENTION

[0008] The present invention provides a system, method and apparatus for a practical and secure card or device that has the advantages of a smart card and will interface with existing world-wide magnetic stripe readers without the use of adapters or bridges. Moreover, the present invention allows for proper authentication in multiple account/application cards and devices to reduce the risk to the device holder due to loss of the device or fraudulent capture of the data within the multiple accounts on the device. As a result, the present invention provides a secure and flexible system for security and/or commercial transactions using access, credit, debit, identification, security, stored value and vendor-specific cards and/or devices.

[0009] The present invention as described herein provides stringent protections for magnetic stripe cards and devices through the use of on-card/device biometric authentication of the user and programmable magnetic stripes such that the data within the tracks of the stripe can be spatially manipulated and managed by the logic within the processor/controller of the card or device. This allows magnetic stripe data to be modified or completely erased for protection of the cardholder, and then re-created on-demand by the programmable features built into the card or device. Alternatively, the data can be stored in the on-card processor/controller and then transmitted via time-varying signal to the card reader thereby emulating the swipe of a magnetic stripe through the magnetic card reader. In addition, the card or device can provide such information via a contactless communication system. These capabilities also enable multiple sets of data and applications to be incorporated onto a single card, device or media, thereby making it a universal card/device with numerous sets of data (e.g., accounts) and/or applications that can be temporarily downloaded onto the magnetic stripe from the memory of the on-card processor, used in the desired application, and then modified or erased. Finally, some or all of the above features can be disabled until the owner of the card enables them through use of an on-card biometrics sensor and logic that is pre-registered to the cardholder. As a result, maximum security is guaranteed since the card cannot be used if it is lost or stolen, and skimming can be virtually eliminated by prompt modification or erasure of the magnetic stripe data following the basic transaction authorized by the owner.

[0010] The present invention provides an apparatus or user device that includes a substrate, a magnetic field generator disposed within the substrate that is normally inactive, a biometric sensor mounted on the substrate, a memory disposed within the substrate and a processor disposed within the substrate that is communicably coupled to the magnetic field generator, the biometric sensor and the memory. The processor is operable to process biometric information received from the biometric sensor to verify that a user is authorized to use the apparatus and activate the magnetic

field generator when the user is verified. A power source is also disposed within the substrate and electrically connected to the magnetic field generator, the biometric sensor and the processor. The magnetic field generator can create a spatial magnetic signal using a magnetic stripe and one or more induction coils, or create a time-varying magnetic signal for emulating data obtained from swiping a magnetic stripe card through a magnetic card reader. As a result, the magnetic field generator emulates a programmable magnetic stripe.

[0011] The present invention also provides a method for enabling a transaction using an apparatus containing information associated with one or more users, a magnetic field generator that is normally inactive and a biometric sensor. The method includes the steps of receiving authentication data from the biometric sensor, determining whether the authentication data is valid for one of the users, and activating the magnetic field generator and generating a magnetic signal corresponding to the information associated with the authenticated user whenever the authentication data is valid. The method can be performed by a computer program, such as middleware, embodied in a computer readable medium wherein each step is implemented as one or more code segments.

[0012] In addition, the present invention provides a system having one or more user devices, one or more system interfaces operable to communicate with the user device and a system processor communicably coupled to the one or more system interfaces. Each user device includes a substrate, a magnetic field generator disposed within the substrate that is normally inactive, a biometric sensor mounted on the substrate, a memory disposed within the substrate and a device processor disposed within the substrate and communicably coupled to the magnetic field generator, the biometric sensor and the memory. The device processor is operable to process biometric information received from the biometric sensor to verify that a user is authorized to use the apparatus and activate the magnetic field generator when the user is verified. The user device also includes a power source disposed within the substrate and electrically connected to the magnetic field generator, the biometric sensor and the device processor.

BRIEF DESCRIPTION OF THE DRAWINGS

[0013] For a more complete understanding of the features and advantages of the present invention, reference is now made to the detailed description of the invention along with the accompanying figures in which corresponding numerals in the different figures refer to corresponding parts and in which:

[0014] **FIG. 1** depicts a standard credit card with a magnetic stripe in accordance with the prior art;

[0015] **FIG. 2** depicts a smart card in accordance with the prior art;

[0016] **FIG. 3** depicts a block diagram of a system for enabling transactions in accordance with one embodiment of the present invention;

[0017] **FIG. 4A** depicts the front of an exemplary embodiment of a card for enabling transactions using a biometrically enabled programmable magnetic stripe in accordance with the present invention;

[0018] FIG. 4B depict the back of an exemplary embodiment of a card for enabling transactions using a biometrically enabled programmable magnetic stripe in accordance with the present invention;

[0019] FIG. 5A depicts a block diagram of a programmable magnetic stripe using multiple inductive coils in accordance with one embodiment of the present invention;

[0020] FIG. 5B depicts a block diagram of a programmable magnetic stripe using a single induction coil for sending emulated time-varying magnetic stripe data to a magnetic card reader directly from the on-card controller in accordance with another embodiment of the present invention;

[0021] FIG. 6 depicts an exemplary embodiment of the combined elements of a biometrically enabled programmable magnetic stripe on a device for secure physical and commercial transactions in accordance with the present invention;

[0022] FIG. 7 is a flow chart of an exemplary authentication method for using a device in accordance with the present invention;

[0023] FIG. 8 depicts one embodiment of an exemplary device for effecting secure physical and commercial transactions in a contactless manner using biometrics identity validation in accordance with the present invention;

[0024] FIG. 9 depicts an exemplary environment in which the device of FIG. 8 may operate in accordance with the present invention;

[0025] FIG. 10 is a flow chart of an exemplary method for using the device of FIG. 8 in the environment of FIG. 9 in accordance with the present invention;

[0026] FIG. 11 is a diagram illustrating another embodiment of an exemplary device for effecting secure physical and commercial transactions in a contactless manner using biometrics identity validation in accordance with the present invention;

[0027] FIG. 12 is an illustration of one embodiment of a biometric sensor that may be used in the device of FIG. 11 in accordance with the present invention;

[0028] FIG. 13A illustrates various layers that form one embodiment of the biometric sensor of FIG. 12 in accordance with the present invention;

[0029] FIG. 13B illustrates various layers that form a portion of one embodiment of the device of FIG. 11 in accordance with the present invention;

[0030] FIG. 14 is a diagram of an exemplary power circuit that may be used in the device of FIG. 11 in accordance with the present invention;

[0031] FIG. 15 is a flow chart of an exemplary method for storing a template fingerprint analog in the device of FIG. 11 in accordance with the present invention;

[0032] FIG. 16 is a flow chart of an exemplary method for using the device of FIG. 11 in accordance with the present invention;

[0033] FIG. 17 is a flow chart of an exemplary method for using the device of FIG. 1 in an air transportation environment in accordance with the present invention;

[0034] FIG. 18 is a flow chart of an exemplary method for using the device of FIG. 1 in a healthcare environment in accordance with the present invention;

[0035] FIG. 19 is flow chart of an exemplary method for storing a biometric template analog in the device of FIG. 8 in accordance with the present invention; and

[0036] FIG. 20 is a flow chart of an exemplary method for using the device of FIG. 8 in a financial transaction in accordance with the present invention.

DETAILED DESCRIPTION OF ILLUSTRATIVE EMBODIMENTS

[0037] While the production and application of various embodiments of the present invention are discussed in detail below in relation to authentication and processing of commercial and security related transactions, it should be appreciated that the present invention provides many applicable inventive concepts that may be embodied in a wide variety of specific contexts. The specific embodiments discussed herein are merely illustrative of specific ways to make and use the invention and do not delimit the scope of the invention.

[0038] The present invention provides a system, method and apparatus for a practical and secure card or device that has the advantages of a smart card and will interface with existing world-wide magnetic stripe readers without the use of adapters or bridges. Moreover, the present invention allows for proper authentication in multiple account/application cards and devices to reduce the risk to the device holder due to loss of the device or fraudulent capture of the data within the multiple accounts on the device. As a result, the present invention provides a secure and flexible system for security and/or commercial transactions using access, credit, debit, identification, security, stored value and vendor-specific cards and/or devices.

[0039] The present invention as described herein provides stringent protections for magnetic stripe cards and devices through the use of on-card/device biometric authentication of the user and programmable magnetic stripes such that the data within the tracks of the stripe can be manipulated and managed by the logic within the processor/controller of the card or device. This allows magnetic stripe data to be modified or completely erased for protection of the cardholder, and then re-created on-demand by the programmable features built into the card or device. Alternatively, the data can be stored in the on-card processor/controller and then transmitted via time-varying signal to the card reader thereby emulating the swipe of a magnetic stripe through the magnetic card reader. In addition, the card or device can provide such information via a contactless communication system. These capabilities also enable multiple sets of data and applications to be incorporated onto a single card, device or media, thereby making it a universal card/device with numerous sets of data (e.g., accounts) and/or applications that can be temporarily downloaded onto the magnetic stripe from the memory of the on-card processor, used in the desired application, and then modified or erased. Finally, some or all of the above features can be disabled until the owner of the card enables them through use of an on-card biometrics sensor and logic that is pre-registered to the cardholder. As a result, maximum security is guaranteed since the card cannot be used if it is lost or stolen, and

skimming can be virtually eliminated by prompt modification or erasure of the magnetic stripe data following the basic transaction authorized by the owner.

[0040] Now referring to **FIG. 3**, a block diagram of a system **300** for enabling transactions in accordance with one embodiment of the present invention is shown. More specifically, the present invention provides a system **300** having one or more user devices **302**, one or more system interfaces **304** operable to communicate with the user device(s) **302** and a system processor or controller **306** communicably coupled to the one or more system interfaces **304**. Each user device **302** includes a magnetic field generator **308** that is normally inactive, a biometric sensor **310**, a memory **312**, a device processor or controller **314** and a power source **316**. Note that the memory **312** and device processor **314** may be integrated into a single integrated circuit. The device processor **314** may also include a smart card processor and an application specific integrated circuit ("ASIC") chip. In addition, the power source **316** may be controlled by a power management unit **318**. The magnetic field generator **308**, biometric sensor **310** and memory **312** are all communicably coupled to the device processor **314**. The magnetic field generator **308**, biometric sensor **310**, memory **312** and device processor **314** are all electrically connected to the power source **316** via the power management unit **318**. If the user device **302** does not include a power management unit **318**, the magnetic field generator **308**, biometric sensor **310**, memory **312** and device processor **314** will all be electrically connected to the power source **316**. The device processor **314** is operable to process biometric information received from the biometric sensor **310** to verify that a user is authorized to use the device **302** and activate the magnetic field generator **308** when the user is verified.

[0041] The magnetic field generator **308** emulates a programmable magnetic stripe by either creating a spatial magnetic signal or a time-varying magnetic signal for emulating data obtained from swiping a magnetic stripe card through a magnetic card reader (See **FIG. 5B**). The spatial magnetic signal is created using a magnetic stripe either mounted on the substrate or disposed within the substrate, one or more induction coils disposed within the substrate underneath the magnetic stripe, and a controller disposed within the substrate that is connected to the one or more induction coils and operable to generate a magnetic signal via the one or more induction coils and the magnetic stripe (See **FIG. 5B**). In either case, the magnetic signal includes binary data to enable a transaction, such as a user name, user number, device expiration date, transaction approval/denial, etc. A typical magnetic stripe contains three-tracks wherein each track contains a set of magnetic data cells. Note that the magnetic field generator **308** may be configured to read a magnetic stripe from another device so that device **302** can replace the other device. The information read from the magnetic stripe would be stored in memory **312** for later transmission by the magnetic field generator **308** upon proper authentication.

[0042] The biometric sensor **310** may include a fingerprint sensor, retina sensor or voice sensor or other sensor device capable of detecting unique characteristics of a person that can then be compared to stored data. One example of such a fingerprint sensor includes a matrix of points operable to detect high and low points corresponding to ridges and valleys of a fingerprint. Another example of a fingerprint

sensor includes an emitter and a detector wherein light projected by the emitter is reflected from a user's finger onto the detector.

[0043] When the device **302** is initialized or linked to a user, the biometric sensor **310** is used to collect biometric information about the user. This biometric information is stored as a biometric analog of the user in the memory **312**. Thereafter, and as will be described below in reference to **FIG. 7**, biometric information or authentication data is obtained by the biometric sensor **310** and sent to the device processor **314** for authentication. The device processor **314** determines whether the authentication data is valid for one of the users by comparing the authentication data to the biometric template stored in memory **312**. If the authentication data is valid, the device processor **314** activates the magnetic field generator **308** and provides binary data to the magnetic field generator **308** to be transmitted as a magnetic signal. The magnetic field generator **308** then generates the magnetic signal corresponding to the information associated with the authenticated user and the selected application. The device processor **314** will then deactivate the magnetic field generator **308** after the magnetic field generator **308** has been active for a specified period of time. Alternatively, the device processor **314** may deactivate the magnetic field generator **308** when the biometric sensor **310** no longer detects the authorized user, or a transaction complete signal is received. The present invention reduces power consumption of the device **302** and increases security by (1) keeping the magnetic field generator **308** normally inactive, (2) activating the magnetic field generator **308** and transmitting the magnetic signal only after the user has been authenticated, and (3) disabling the magnetic field generator sometime thereafter. Additional power consumption can be reduced by keeping the device **302** in a sleep or low power mode until certain activation parameters have been satisfied, such as receiving an external signal, contact with the biometric sensor **310** or a user input/command.

[0044] The power source **316** may include a battery, a piezoelectric generator, a solar panel, an electromagnetic energy converter (such as used in passive Radio Frequency Identification ("RFID") systems), a kinetic energy converter or any combination thereof. For example, the power source **316** may include a battery, a power generator, a converter and a multiplexer. The converter is electrically connected to the power generator and operable to convert power received from the power generator into power usable by the device **302** or to charge the battery. The battery management unit **318** is connected to the battery. The power multiplexer is connected to the battery management unit **318** and the converter. The power multiplexer is operable to determine whether to draw power from the battery management unit, from the converter, or from both.

[0045] The device **302** may also include a user interface **320** that is communicably coupled to the device processor **314** and electrically connected to the power source **316** (via power management unit **318**). The user interface **320** may include a touch pad, one or more buttons, a display, a voice sensor or other known user interfaces. The device **302** may also include a contactless interface **322** that is communicably coupled to the device processor **314** and electrically connected to the power source **316** (via power management unit **318**). The contactless interface **322** may include an antenna for wireless communication, an optical transceiver

or other known contactless communication methods. In addition, device **302** may also include a smart card interface **324** that is communicably coupled to the device processor **314** and electrically connected to the power source **316** (via power management unit **318**). Moreover, device **302** may include an optical or other type of input/output (VO) interface **326** that is communicably coupled to the device processor **314** and electrically connected to the power source **316** (via power management unit **318**).

[0046] The components of the device **302** are typically disposed within or mounted on a substrate. For example, the biometric sensor **310**, user interface **320**, smart card interface **324** and optical or other I/O interface **326** are typically mounted on the substrate; whereas the memory **312**, device processor **314**, power source **316** and power management unit **318** are typically disposed within the substrate. The magnetic field generator **308** and contactless interface **322** can be mounted on the substrate or disposed within the substrate. The type of material used for the substrate and the resulting properties of the substrate will depend on the desired application and working environment for the device **302**. In many cases, the substrate will be a semi-flexible material, such as plastic, or a laminate material. The substrate can then be integrated into a card, such as an access card, a credit card, a debit card, an identification card, a mini-card, a security card, a stored value card and a vendor-specific card, etc. The substrate may also be integrated into a travel credential, such as a passport, an immigration card and a visa, etc. In addition, the substrate may be integrated into a personal communication device, such as a personal data assistant (PDA), a telecommunications device, a pager, a computer and an electronic mail transceiver, etc. Moreover, the substrate may be integrated into a personal device/belonging, such as a watch, a jewelry, a key ring, a tag and eye glasses, etc.

[0047] The one or more system interfaces **304** may include a device initialization interface **328**, a magnetic reader **330**, a wireless communications interface (transceiver) **332**, a smart card reader **334**, or an optical or other input/output interface **336**. The one or more system interfaces **304** are used to communicate with the user device **302** physically or contactlessly, depending on the desired application and implementation. Other non-system interfaces may include a battery recharger, personal computer interface or personal data assistant (PDA). The one or more system interfaces **304** are communicably coupled to a system processor or controller **306**, which in turn may be communicably coupled to a database **338** or one or more remote systems or computers **342** via network **340**. Network **340** may be a local area network or wide area network, such as the Internet.

[0048] Referring now to FIG. 4A, the front **400** of an exemplary embodiment of a card for enabling transactions using a biometrically enabled programmable magnetic stripe in accordance with the present invention is shown. The card is shown in the form of a credit or debit card, but may also be used as an access card, an identification card, a mini-card, a security card, a stored value card and a vendor-specific card, etc. The front **400** of the card includes the issuer's name **402**, a biometric sensor **310**, a photo or I/O interface **404** (user interface **320** or other I/O interface **326**), a smart card interface **324**, a card number **406**, an expiration date **408**, the card holder's name **410** and a hologram **412**. Other information and features may also be placed on or within the

card. As will be appreciated by those skilled in the art, the features described above can be rearranged or eliminated to fit a specific application for the card.

[0049] Now referring to FIG. 4B, the back **450** of an exemplary embodiment of a card for enabling transactions using a biometrically enabled programmable magnetic stripe in accordance with the present invention is shown. The back **450** of the card includes the magnetic field generator **308** (programmable magnetic stripe), an area for the card holder to place an authorized signature **452** and the issuer's contact information and disclaimers **454**. Other information and features may also be placed on or within the card. As will be appreciated by those skilled in the art, the features described above can be rearranged or eliminated to fit a specific application for the card.

[0050] Referring now to FIG. 5A, a block diagram of a programmable magnetic stripe **500** (308FIG. 3) using multiple inductive coils **518-530** in accordance with one embodiment of the present invention is shown. The programmable magnetic stripe **500** (308FIG. 3) includes a magnetic stripe **502**, multiple inductive coils **518-530** and a control circuit **532**. The magnetic stripe **502** contains one or more sets of magnetic data cells **504-516**. For example, magnetic stripe **502** will typically contain three tracks or sets of magnetic data cells **504-516**. The individual inductive coils **518-530** are mounted immediately beneath each of the binary magnetic data cells **504-516**. Each inductive coil **518-530** is electrically connected to the control circuit **532**, which may be integrated into the device processor **314** (FIG. 3). When a positive or negative current is applied to each inductive coil **518-530**, it changes the polarity of the magnetized particles in the binary magnetic data cell **504-516** of the data track in the magnetic stripe **502** immediately above it, thereby creating a spatially varying binary code or magnetic signal in the magnetic stripe **502** material that can be read by standard magnetic card readers when such binary code is applied in accordance with ISO standards.

[0051] Now referring to FIG. 5B, a block diagram of a programmable magnetic stripe **550** (308FIG. 3) using a single induction coil **552** for sending emulated time-varying magnetic stripe data to a magnetic card reader directly from the on-card controller in accordance with another embodiment of the present invention is shown. The programmable magnetic stripe **550** (308FIG. 3) includes a magnetic stripe **502**, a single inductive coil **552** and a control circuit **554**. The magnetic stripe **502** contains one or more sets of magnetic data cells **504-516**. For example, magnetic stripe **502** will typically contain three tracks or sets of magnetic data cells **504-516**. The long inductive coil **552** is mounted immediately beneath the entire length of the magnetic stripe **502** and its corresponding binary magnetic data cells **504-516** such that a time-varying signal can be transmitted to the heads of the magnetic card reader as the card is swiped through the reader. The data rate is determined based on the minimum and maximum swipe speeds that standard readers can accommodate. In other words, the single inductive coil **552** is long enough for it to be in the physical proximity of the card reader heads for the entire time period required to transmit the time-varying signal from the card to the card reader. The inductive coil **552** is electrically connected to the control circuit **554**, which may be integrated into the device processor **314** (FIG. 3). By establishing the configuration in this manner, the inductive coil **552** can be pulsed with

varying currents and current directions so that the time-varying data stream of a card being swiped through the reader is emulated, thus providing the same magnetic data stream to the reader heads of the magnetic stripe reader as would be seen if a card with binary data in multiple spatially distributed data cells **504-516** in the magnetic stripe **502** were swiped through the reader. This magnetic signal will, therefore, emulate the data that would be generated by the swipe of a magnetic stripe card with the desired information embedded in the individual data cells **504-516** of the stripe **502**.

[0052] Note that the individual data cells **504-516** are normally empty of data. There are several ways in which the card can be activated so that the data transfer can be started. For example, the card can be initially activated by the authorized user using an on-card "enable button", such as a low-power capacitance sensor, that can be built into the ring of the biometrics sensor **302** (**FIG. 3**) and used to "wake up" the card when the user is ready to authenticate himself/herself and begin using the card. Authentication of the card user is time stamped for use in determining the length of time to allow transmission of the emulated data. In addition, the magnetic reader **330** (**FIG. 3**) may have a start sentinel that signals a detector on the card to alert the card that it is in the presence of the card reader **330** (**FIG. 3**). Once the card is alerted that it is being swiped through the reader **330** (**FIG. 3**), it begins transmission of the emulated time-varying data from the device processor to the inductive coils **552**, thereby generating an exact emulation and transmission to the reader **330** (**FIG. 3**) of the data that would have been produced by swiping the card through the reader **330** (**FIG. 3**) with spatially varying data included in the individual data cells **504-516**. All such transmission of emulated card data is contingent upon valid biometric authentication of the card user, followed by detection of the card that it is in the presence of the reader head and the reader **330** (**FIG. 3**) has recognized the start sentinel on the card so that the reader **330** (**FIG. 3**) is ready to accept the stream of emulated data provided by the device processor. The transmission of data from the device processor **314** (**FIG. 3**) is suspended once the initial reading of data by the magnetic card reader **330** (**FIG. 3**) has been completed. This action prevents skimming of card information after the basic transaction has been completed.

[0053] Referring now to **FIG. 6**, a programmable magnetic card **600** is equipped with inductive coils as illustrated in **FIG. 5A** or **5B**. An on-card biometrics sensor **310** is incorporated to enable positive authentication of the user of the card. This is accomplished by transmitting a biometrics template from the biometrics sensor **310** to the on-card control processor **314** that performs matching operations on the template sent from the biometrics sensor **310** with a template obtained from the authorized user of the card, such authorized template being resident in the control processor **314** (memory **312**) from initial registration of the authorized card owner and/or user. Once such biometrics matching has been accomplished, the control processor **314** then authorizes the necessary account numbers and/or card applications to be downloaded into the individual data tracks of the programmable magnetic stripe **308** (magnetic field generator; see also **502FIGS. 5A and 5B**), which then enables the card to be used in standard card-readers throughout the existing world-wide infrastructure.

[0054] Now referring to **FIG. 7**, a flow chart of an exemplary authentication method **700** for using a device, such as device **300** (**FIG. 3**), in accordance with the present invention is shown. The device contains information associated with one or more users, a magnetic field generator that is normally inactive and a biometric sensor. The device can be used to enable any type of transaction, such as an access transaction, a control transaction, a financial transaction, a commercial transaction or an identification transaction. The device is normally in standby or sleep mode as shown in block **702**. If one or more activation parameters are satisfied, as determined in decision block **704**, the device is switched to active mode in block **708**. Otherwise, the device remains in standby mode as shown in block **706**. The one or more activation parameters may include detecting data from the biometric sensor (e.g., **310FIG. 3**), detecting an external signal from an interface (e.g., **308, 322, 324, 326FIG. 3**) or receiving data from a user interface (e.g., **320FIG. 3**). If authentication data is not received after the device is switched to active mode, as determined in decision block **710**, and the active period has timed out, as determined in decision block **712**, the device is switched to standby mode in block **714** and again waits for activation parameters in block **704**. If, however, the active mode has not timed out, as determined in decision block **712**, the device continues to wait for authentication data to be received until the active period has timed out. If, however, authentication data is received from the biometric sensor, as determined in decision block **710**, the authentication data is verified in block **716**. The verification process determines whether the authentication data is valid for one of the users by comparing the authentication data with a stored biometric template of the one or more users that are authorized or registered to use the device. If the authentication data is not valid, as determined in decision block **718**, and the active period has timed out, as determined in decision block **712**, the device is switched to standby mode in block **714** and again waits for activation parameters in block **704**. If, however, the active mode has not timed out, as determined in decision block **712**, the device will again wait for authentication data to be received until the active period has timed out.

[0055] If, however, the authentication data is valid, as determined in decision block **718**, the information associated with the authenticated user is accessed in block **720** and provided to the device outputs in block **722**. The information can be a simple approval or denial of the transaction, or private information of the user that is required to enable or complete the transaction. As previously described in reference to **FIG. 3**, the device outputs may include a magnetic field generator **308** (programmable magnetic stripe), a contactless interface **322**, a smart card interface **324**, or an optical or other I/O interface **326**. Using the magnetic field generator **308** for example, this step would involve activating the magnetic field generator **308** and generating a magnetic signal corresponding to the information associated with the authenticated user. In addition, the authentication step (block **716**), the information access step (block **720**) or the information output step (block **722**) may also display information to the user, allow the user to select the information to enable the transaction or allow the user to select the device output or interface to be used. Once the transaction is complete, as determined in decision block **724**, the information is cleared from the device output(s) in block **728**, the device is switched to standby mode in block **714**

and the device waits for various activation parameters in block 704. If, however, the transaction is not complete, as determined in decision block 724 and the process has not timed out, as determined in decision block 726, the process continues to wait for the transaction to be completed. If the process has timed out, as determined in decision block 726, the information is cleared from the device output(s) in block 728, the device is switched to standby mode in block 714 and the device waits for various activation parameters in block 704. The process can be set to interrupt the transaction and deny it if the process times out (e.g., the magnetic field generator has been active for a specified period of time) or the biometric sensor no longer detects the authorized user. Note that this method can be performed by a computer program, such as middleware, embodied in a computer readable medium wherein each step is implemented as one or more code segments, all of which are performed on the card/device.

[0056] Referring now to FIG. 8, one embodiment of an exemplary device 800 for effecting secure physical and commercial transactions in a contactless manner using biometrics is shown. As will be described later in greater detail, the device 800 includes multiple components, such as a biometric sensor 802, a radio frequency (“RF”) antenna 804, a controller 806, control buttons 808, a dynamic information display 810, a magnetic information media component 812, and a RF power conversion and power management unit 814. A number of inter-component communications paths 816 provide connections between various components of the device 800.

[0057] The RF antenna 804 may perform multiple functions. For example, it may capture RF energy from a RF field emanated by a RF power source and may also support two-way communication with an associated reader/writer device (not shown). The antenna 804 may be a single antenna capable of performing both functions or may comprise multiple antennae, with one antenna for capturing RF energy from the RF field and another antenna for supporting the two-way communication with the reader/writer device. The communications may include, for example, authenticated identification of a person operating the device 800, various purchases and financial transactions, air ticket booking and airport security check points, and other interactions between the device 800 and the reader/writer device. These communications may be secured using mechanisms such as data encryption. It is understood that other communications components, such as audio or optical components, may replace or supplement the antenna 804. In addition, the antenna 804 may be operable to function with wavelengths other than RF.

[0058] The biometric sensor 802 is used for sensing a physical attribute of a user of the device 800 and generating an analog of this physical attribute. The analog may then be made available to the controller 806. More specifically, the biometric sensor 802 is designed to sense some physical attribute of a person and extract a distinctive analog of that person. To be useful for establishing positive identification, the analog may need to be individualized sufficiently so as to be unique to every person. In addition, a trusted copy—a template—of the analog should be captured. Analogs later sensed by the biometric sensor 802 may then be compared against the template analog. Various physical attributes may

be used for identification purposes, such as fingerprints, voice prints, and retinal or iris prints.

[0059] The controller 806 interacts with the biometric sensor 802 and other components of the device 800 to perform various functions. For example, the controller 806 may capture the analog of the physical attribute for long term storage as a trusted template analog of an authorized user, as well as for immediate comparison to a stored trusted template analog during an authentication procedure. The controller 806 may also determine whether the comparison indicates a match between the template analog and the analog captured by the biometric sensor 802. In addition, the controller 806 may control the dynamic information display 810, respond to input from the control buttons 810, and control the magnetic information media component 812. Furthermore, the controller 806 may support two-way communications with an associated reader/writer device (FIG. 9) via the RF antenna 804. The controller may be a single controller/processor or may comprise multiple controllers/processors.

[0060] The dynamic information display 810 may be used to display information to a user, as well as to enable a process with which the user may interact using the control buttons 810. The magnetic information media component 812 may be manipulated so that it provides information via a magnetic field. The RF power unit 814 may convert RF radio energy to electrical energy, and may control storage and distribution of the electrical energy to the other components in the device 800. It is understood that the device 800 may also have a battery and/or other power means to use as a backup or alternative power source for the RF power control unit 814.

[0061] Referring now to FIG. 9, the device is illustrated in an exemplary environment 900 that enables contactless interaction with a reader/writer device 902. To achieve this contactless interaction, the device 800 is shown with the antenna 804, as described in reference to FIG. 8. The device 902 uses one or more antennae 903 to communicate with device 800, as well as emanate a RF field 906 with the purpose of supplying power to compatible devices, such as device 800. In operation, a two-way communication link 908 may be established between the reader/writer device 902 and the device 800.

[0062] It is understood that many different reader/writer configurations may be used. For example, the reader/writer device 902 may be in communication with other devices or with a network. Furthermore, the reader/writer device 902 may be in communication with other devices or with a network. Furthermore, the reader/writer device 902 may include the RF power source, or they may be separate devices. For the purposes of clarity, the reader/writer device 902 of the present invention example includes the RF power source, although alternate sources of RF power may be used.

[0063] Referring to FIG. 10 and with continued reference to FIGS. 8 and 9, the device 800 may be operated in the environment 900 using a method 1000 as follows. In step 1002, the device 800 is placed into the RF field 906 emanated by the reader/writer device 902. When placed into the RF field, the device 800 captures power from the RF field 906, which powers up the device’s 800 electronics. In step 1004, the biometric sensor 802 is actuated by a user. The method of actuation may depend on the type of biometric

sensor (e.g., a fingerprint for a fingerprint sensor, speaking for a voice sensor, etc.). In step **1006**, an authentication process is performed by the device **800**. As in the previous step, the authentication process may depend on the type of biometric sensor. For example, the detected fingerprint or voice may be compared to a template in the memory of the device **800**. In step **1008**, a determination is made as to whether the user is authenticated. If the authentication process fails to validate the user, the method **1000** may return to step **1004**. If the user is validated by the authentication process, the method continues to step **1010**, where the device **800** continues the desired transaction with the reader/writer device **902**. Once this occurs, the device **800** may be removed from the RF field **906** in step **1012**, which powers down the device **800**.

[**0064**] Referring now to **FIG. 11**, in another embodiment, a device **1100** illustrates an implementation of the present disclosure using a form factor similar to that of a credit card. The credit card form factor of the device **1100** includes several components, such as a fingerprint sensor **1102**, a RF antenna **1104**, a first controller **1106**, a second controller **1108**, function selector buttons **1110**, an electro-luminescent display **1112** and a magnetic strip **1114**. In the present example, the first controller **1106** is an application specific integrated circuit ("ASIC") chip and the second controller is a smart card chip, although it is understood that the functionality of both controllers may be provided by a single controller.

[**0065**] The ASIC **1106** is a custom integrated circuit chip developed for use in the device **1100**. The ASIC **1106** includes Random Access Memory ("RAM") which may be used for temporarily storing a current fingerprint analog detected by the fingerprint sensor **1102** and for temporarily storing intermediate results of processing calculations (e.g., fingerprint comparisons, etc.). The ASIC **1106** may also include non-volatile memory (e.g., Flash memory or EEPROM) to store and retrieve one or more fingerprint template analogs that are used for comparison against the current fingerprint analog.

[**0066**] Circuitry contained within the ASIC **1106** provides an interface between the ASIC **1106** and the fingerprint sensor **1102**. In the present example, the ASIC **1106** contains a microprocessor core with dedicated program and temporary memory, enabling the ASIC **1106** to use an array of processing elements for executing instructions stored with the ASIC **1106** in parallel. The instructions enable the ASIC **1106** to perform a comparison between the current fingerprint analog and a template fingerprint analog. Other instructions included within the ASIC **1106** may provide support for an authorization signal to be sent to the smart card **1108** after an authentication process has been completed. In addition, the ASIC **1106** may be used to drive the electroluminescent display **1112**, read the function control buttons **1110**, and drive the programmable magnetic strip **1114**.

[**0067**] The smart card chip **1108** may support various application programs. These applications may include, for example, storage/retrieval of personal demographics information, storage/retrieval of a digitized picture of the cardholder, an "electronic purse" functionality, financial transactions, purchases, etc. In addition, the smart card chip **1108** may support two-way communication data transfers and may perform various encryption functions to support secure

communications. In the present example, the communications and encryption are based on known standards, but proprietary protocols may be used if desired. It is envisioned that the smart card chip **1108** may support smart card interactions such as identification validation, credit card transactions, and others. Note that the control and processing functions of the device **1100** can be handled by the ASIC **1106**, the smart card chip **1108**, any combination of the ASIC **1106** and the smart card chip **1108**, or a single chip.

[**0068**] The fingerprint sensor **1102** is designed to detect fingerprint information and provide the detected information to other components of the device **1100**. In the present example, the fingerprint sensor **1102** comprises a polymer thick film ("PTF") construction, which provides the fingerprint sensor **1102** with the flexibility and ruggedness needed for implementation on the device **1100**. As described in greater detail below in **FIGS. 12 and 10**, the fingerprint sensor **1102** comprises a matrix of points that are operable to detect high and low points corresponding to ridges and valley of a fingerprint. The points are captured and used by the ASIC **1106** to determine whether the detected fingerprint analog matches a fingerprint template analog that is stored in memory.

[**0069**] Referring now to **FIG. 12**, in one embodiment, the PTF sensor **1102** comprises a rectangular arrangement of row electrodes **1202** and column electrodes **1204**. It is noted that more or fewer columns and rows may be included in the PTF sensor **1102**, depending on such factors as the desired resolution of the PTF sensor **1102** (e.g., the number of data points desired). Electrical connections from the row and column electrodes **1202**, **1204** may rout to the ASIC **1106**.

[**0070**] In operation, a fingerprint analog detected by the PTF sensor **1102** may be captured by the ASIC **1106** as a sequence of numerical values. For purposes of illustration, the row and column electrodes **1202**, **1204** may be viewed as a two dimensional matrix of pixels, with numerical values representing intersections between the row and column electrodes. The numerical values may be associated with gray scale values, and an analog representing a fingerprint may be generated from the matrix of gray scale values. It is understood that there is no need to transform the captured analog into a visible image since the matching between the stored template fingerprint analog and the candidate fingerprint analog need not rely on a visual process. However, it is convenient to conceptualize the numerical values as an image for purposes of evaluating the sensor resolution used to support fingerprint authentication. It is generally accepted that a graphical resolution of from 100 dots per inch ("dpi") to 500 dpi is sufficient for fingerprint authentication. In the present example, the PTF sensor **1102** comprises 200 row electrodes and 200 column electrodes arranged in a 1/2" by 1/2" matrix, which corresponds to a graphical resolution of 400 dpi.

[**0071**] Referring now to **FIG. 13A**, a schematic depiction of functional layers of one embodiment of the PTF sensor **1102** of **FIG. 11** is shown. The PTF sensor **1102** is comprised of functional layers including an annularly shaped topside electrode **1302**; an insulator with backside reflector **1304**; and electro-luminescent layer **1306**; insulator layers **1308**, **1312**, **1316**, and **1320**; row electrodes **1310**; column electrodes **1314**; an electro-resistive layer **1318**; and elec-

trode 1322; and a substrate layer 1324. The substrate layer 1324 may be a portion of the substrate for the entire device 1100.

[0072] In operation, when a user of the device 1100 places a finger or thumb (henceforth only finger will be specified, although it is understood that both fingers and thumb are intended) on the surface of the PTF sensor 1102, the finger contacts the topside electrode 1302 and becomes electrically grounded to the topside electrode 1302. When a voltage is applied to row electrodes 1310, and electric field is generated between the row electrodes 1310 and the topside electrode 1302. The strength of the generated field varies depending on how close the finger is to the topside electrode 1302. For example, fingerprint ridges may be relatively close to the topside electrode 1302 of the PTF sensor 1102, varying the generated field in a detectable manner. Fingerprint valleys may be more distant from the PTF sensor 1102 than the fingerprint ridges, which may vary the generated field in a detectable manner that may be differentiated from the variations caused by the fingerprint ridges.

[0073] The electro-luminescent layer 1306 may emit more or less light as the electric field that impinges upon it varies, thereby generating an analog of the fingerprint incident upon the PTF sensor 1102. The reflector component of the insulator with backside reflector layer 1304 serves to reflect the omni directional light emitted by the electro-luminescent layer 1306 and thus intensify the fingerprint analog. The PTF sensor 1102 may be operated by applying a bias voltage to only one row electrode at a time, successively biasing and unbiasing one row after another. This has the effect of causing the electro-luminescent layer 1306 to generate an analog of an elongated thin strip of the fingerprint. By sensing each of these analogs and combining them upon completion of row sequencing, a complete analog may be collected.

[0074] It is a property of the electro-resistive layer 1318 that when it is placed in an electrical field its resistance varies with the intensity of light incident upon it. The light emitted by the electro-luminescent layer 1306, which is an analog of the fingerprint, passes through the intervening layers 1308, 1310, 1312, 1314, and 1316 to impinge upon the electro-resistive layer 1318. The electro-resistive layer 1318 is placed in an electric field by placing a DC voltage bias on the electrode 1322 relative to the column electrodes 1314, causing the electro-resistive layer to exhibit varying resistance depending upon the intensity of light incident upon it and thereby forming an analog of the fingerprint. A voltage is applied to the column electrodes 1314, and the impedance between the column electrodes 1314 and the electrode 1322 can be measured. This measured impedance is directly related to the varying resistance of the electro-resistive layer 1318 and hence an analog of the fingerprint. So by activating each row electrode in succession, as described above, an analog of the fingerprint can be captured and stored.

[0075] The ASIC 1106 may control the sequential activation of the row electrodes 1310, the reading back of the varying resistance from the column electrodes 1314, and other functions of the PTF sensor 1102. It is understood that other approaches may be used, such as reading one column at a time for each row or reading multiple row/columns at once. Furthermore, while the preceding description focuses

on the use of the PTF sensor 1102 as a fingerprint sensor, the principle of operation of the PTF sensor 1102 is general and not limited to capturing fingerprint analogs.

[0076] Referring now to FIG. 13B, one embodiment of a portion of the device 1100 illustrates the biometric sensor 1102, display 1112, and RF antenna 1104 formed on the substrate 1324. The biometric sensor includes layers 1302-1322 as described with respect to FIG. 10, the display 1112 comprises layer 1326-1336, and the RF antenna comprises layers 1338-1348. As is illustrated in FIG. 13B, each of the components 1102, 1112, 1104 share a number of layers (e.g., 1322, 1336, and 1348). This sharing simplifies the design of the device 1100 and may also reduce manufacturing costs.

[0077] Referring again to FIG. 11, the RF antenna 1104, which may include one or more antennae, may capture RF energy from a RF field emanated by a RF power source and may also support two-way communication with an associated reader/writer device (not shown). The RF energy which is captured is converted to electrical energy and accumulated within the device 1100. In some embodiments of the device 1100, a rechargeable battery may power the electronic components when no RF energy field is present. Such a battery may be charged via a RF energy field or alternative charging means.

[0078] The electro-luminescent display 1112 provides the capability to display information to a user of the device 1100. For example, the information may include a credit card number to support "card not present" transactions, a residual balance of an "electronic purse," air travel flight and seat assignment information, and similar information. Furthermore, interaction with the display 1112 may be accomplished via the function control buttons 1110. For example, the buttons 1110 may be used to select a credit card number (if the device 1100 stores multiple numbers) viewed via the display 1112 or to enter a personal identification number. The pliability of the electro-luminescent display 1112 aids its use in the card-like form factor of the device 1100. While two control buttons 1110 are illustrated, it is understood that other numbers and configurations of function control buttons may be used.

[0079] A dynamic magnetic strip 1114 is provided to provide compatibility with existing reader devices. The dynamic magnetic strip 1114 may be used in either fixed or dynamic mode. In dynamic mode, magnetically stored information—such as a credit card number—may be changed under control of the ASIC 1106.

[0080] Referring now to FIG. 14, an illustrative power circuit 1400, such as may be used in the device 1100 of FIG. 11, is depicted. When appropriate RF energy is incident upon the device 1100, the RF energy couples into a RF antenna 1402. From the antenna 1402, the energy enters a RF-to-DC power converter 1404, which includes a full-wave rectifier to convert the AC RF field into a DC-like circuit. Capacitance may be provided to buffer the AC peak variations into a DC-like source. The intermediate power generated by this process may be used for a variety of purposes, such as charging a battery 1406 if the battery 1406 is below its full capacity and feeding power to the device 1100. The battery 1406 may be charged through a battery management unit 1408. A smart power multiplexer 1410 may be used to determine whether to draw power from the battery management unit 1408, directly from the RF-to-DC power converter 1404, or from both.

[0081] A voltage regulator **1412** creates a stable DC voltage level to power the device **1100**. When no RF energy is coupled into the RF antenna **1402**, the RF-to-DC converter **1404** may not function and power may be drawn from the battery management unit **1408** by the smart power multiplexer **1410**. As before, the voltage regulator **1112** creates a stable DC voltage level to power the device **1100**. It is understood that, in other embodiments, the power circuit **1400** may not employ a battery or rechargeable battery, and may relay solely on power captured from the RF field.

[0082] Referring now to **FIG. 15**, an exemplary template storage method **1500** illustrates one embodiment for capturing and storing a template of a fingerprint analog for the device **1100** of **FIG. 11**. In step **1502**, a user places the device **1100** in a RF field emanated by a reader/writer device. As described previously, the device **1100** captures power from the RF field. In step **1504**, the user places his thumb or finger on the fingerprint sensor **1102** and, in step **1506**, the device **1100** determines whether a template fingerprint analog is already stored. If it is determined that no template fingerprint analog is stored, the method **1500** continues to step **1508**. In step **1508**, the user's incident fingerprint is sensed by the fingerprint sensor **1102**, a fingerprint analog is generated by the fingerprint sensor **1102**, and the ASIC **1106** stores the fingerprint analog as a template fingerprint analog. If a fingerprint template analog is already stored, the method **1500** continues to step **1510**, where the device **1100** is removed from the RF field. It is understood that other events may occur before step **1510** if a fingerprint template analog is already stored, such as illustrated in **FIG. 16**.

[0083] Although not shown in the present example, multiple template fingerprint analogs may be stored in the device **1100**. The template fingerprint analogs may represent multiple fingerprints of a single person or may represent the fingerprints of different people. This may be accomplished, for example, by implementing a method for allowing the device **1100**'s owner to securely control initialization of multiple template fingerprint analogs and to selectively engage which template fingerprint analog will be used to authenticate identity and authorize transactions. Alternately, if the device **1100** is to be used in environments requiring higher security, the user of the device **1100** may need to appear in person and validate his or her identity using traditional methods (e.g., a driver's license, birth certificate, etc.). After validation, the user's template fingerprint analog may be placed into the device **1000** as described above or through other means (e.g., a scanner that transfers the template fingerprint analog into the device **1000**).

[0084] Referring now to **FIG. 16**, in another embodiment, a method **1600** illustrates one method of operation for the device **1100**. In step **1602**, as has been described previously, the device **1100** is placed into a RF field emanated by a reader/writer device. When placed into the RF field, the device **1100** captures power, energizing its electronics. In step **1604**, a user places one of his fingers onto the fingerprint sensor **1102**. As described above, the fingerprint sensor **1102** captures an analog of the fingerprint and passes the analog to the SAIC **1106**.

[0085] In step **1606**, an authentication process is performed by comparing the captured fingerprint analog to one

or more template fingerprint analogs stored in memory. In step **1608**, a determination is made as to whether the user is authentication (e.g., whether the captured fingerprint analog matches a stored template fingerprint analog). If the authentication process fails to validate the user, the method **1600** may return to step **1604** as shown or may end, requiring the user to remove the device **1100** from the RF field and begin again with step **1602**. If the user is validated by the authentication process, the method continues to step **1610**, where the device **1100** conducts a communications handshake process with the reader/writer device via a contactless two-way communication link. In step **1612**, the device **1100** continues the desired transaction with the reader/writer device. Once this occurs, the device **1100** may be removed from the RF field, which powers down the device **1100**.

[0086] Referring now to **FIG. 17**, in another embodiment, a method **1700** illustrates using the present disclosure in an air transportation environment. A traveler desiring to make a remote reservation presents a device (such as the device **800** of **FIG. 8**) to a reader/writer device. In the present example, the reader/writer device is attached to a personal computer ("PC") via a wired or wireless connection. The PC may enable the traveler to access an application, such as a web based flight reservation application.

[0087] In step **1702**, a determination is made as to whether the traveler has selected a remote reservation and ticketing process. If the traveler has selected such a process, the method **1700** continues to step **1704**, where the device **800** is used in conjunction with PC and the reader/writer to verify the traveler's identification and approve the transaction and associated payments. In addition, flight information may be transferred from the reader/writer device into the device **800**.

[0088] The method **1700** then continues to step **1706**, where a determination is made as to whether the traveler has selected to remotely check-in baggage. If the traveler has not selected to remotely check-in baggage, the method **1700** continues to step **1712**. If the traveler has selected to remotely check-in baggage, the method **1700** continues to step **1708**, where the device **800** is used in conjunction with PC and the reader/writer to verify the traveler's identification. In addition, flight and ticket information may be read from the device **800** to further automate the baggage check-in process. After the traveler has entered any desired information (e.g., number of bags, etc.), baggage reference information may be transferred into the traveler's device **800** for later transfer into and use by the airline's ticketing and baggage tracking systems.

[0089] Returning to step **1702**, if it is determined that the traveler has not selected a remote reservation and ticketing process, the method **1700** continues to step **1710**, where the traveler may use the device **800** with a reader/writer device at a counter or self-service kiosk in a manner similar to the process of the remote check-in of step **1704**. More specifically, the traveler may use the device **800** to verify the traveler's identification and approve a purchase transaction, as well as any associated payments. In addition, flight information may be transferred from the reader/writer device into the device **800**.

[0090] Continuing to step **1712**, the traveler may use the device **800** with the reader/writer device at the counter or self-service kiosk in a manner similar to the process of the remote baggage check-in of step **1708**. More specifically, the

traveler may use the device **800** to verify the traveler's identification, provide flight and ticket information, and store baggage reference information that is transferred from the reader/writer device.

[0091] After the ticketing and baggage check-in, the method **1700** continues to steps **1714**, **1716**, and **1718**, where the traveler may present the device **800** to other reader/writer devices for identification and ticket authentication. For example, this may occur at security checkpoints, gates, and/or at boarding. It is understood that some of the reader/writer devices may be in communication with airline and/or government databases.

[0092] Referring now to **FIG. 18**, in another embodiment, a method **1800** illustrates using the present disclosure in a health care environment. In step **1802**, a determination is made as to whether a patient desires to perform a pre check-in process before arriving at a healthcare facility. If it is determined that the patient does desire to perform a pre check-in process, the method **1800** continues to step **1804**, where the patient may present a device (such as the device **800** of **FIG. 8**) to a reader/writer device. In the present example, the reader/writer device is attached to a personal computer via a wired or wireless connection. The PC may enable the patient to access an application, such as a web-based healthcare application. Upon presentation of the device in step **1804**, the patient may be identified, payment and care instructions may be approved, and medical information (e.g., records, prescriptions, etc.) may be activated. The device **800** may also be used to provide the patient with medical alerts.

[0093] In step **1806**, if the patient has not performed the pre check-in process of step **1804**, the patient may use the device **800** to perform similar functions at the healthcare facility. The method then continues to step **1808**, where the device may be used to access provider services. For example, the device **800** may be used to interact with a reader/writer device at a desk or workstation in the healthcare facility (e.g., an examination room). This interaction may authenticate the patient's identification, provide access to pertinent medical records, verify that the records are updated, and store one or more prescriptions.

[0094] Continuing to step **1810**, the patient may present the device **800** to a reader/writer device at a pharmacy. The device **800** may be used to authenticate the patient's identification for a prescription and provide the prescription to the pharmacy. Furthermore, the device **800** may provide insurance/payment information and enable the patient to approve the transaction.

[0095] Referring now to **FIGS. 19 and 20**, in another embodiment, methods **1900** and **2000** illustrate using the present disclosure in a financial transaction environment. The financial transaction environment includes making retail purchases in either a physical store or on-line (e.g., over the Internet). The present disclosure may be implemented in the financial transaction environment by using a device, such as the device **800** of **FIG. 8**, to identify buyers, verify the identity of the buyer rapidly in a localized venue, associate the buyer's identity with a credit or debit account, and/or assure the availability and legitimacy of funds in these accounts for payment transactions.

[0096] Payments for retail purchases are generally accomplished in one of three ways: with cash; with a check; or with

a credit or debit card. In a cash transaction, there is generally no need for validating the identification of the buyer. In a transaction where a check is used, there generally is a need for identification of the buyer. This identification may occur by way of the buyer's presentation of a driver's license or alternate, approved identification card, presentation of a credit card to indicate credit-worthiness, or by a telecommunication connection to check security processing service to assure fund availability for, and legitimacy of, the check presented for payment.

[0097] In a transaction where a credit or debit card is used, there are generally various procedural mechanisms in place to assure buyer identification and legitimate ownership of the card presented for the payment transaction. For example, the payment may require the entry of numeric PIN ("Personal Identification Number") security code by the buyer and assumed owner of the card. Alternatively, sales personnel may compare the buyer's signature on the back of the card presented for payment versus the requested signature on the purchase receipt provided for the goods or services purchased. In some cases, cards have a photograph of the card owner on them, and sales personnel may make cursory comparisons of this photograph with the buyer to establish identification. However, both photographic comparison and PIN-based card authorization have weaknesses for assuring identification, and both have potential risk for fraudulent processing. Photographs can be falsified and PIN numbers can be stolen. In the case of on-line purchases, buyers are not present to provide authorizing signatures, photographic comparisons cannot be made with existing processing infrastructure, and PIN-based transactions can be compromised with identity theft.

[0098] Referring specifically to **FIG. 19**, before the device **800** is usable in financial transactions, it should be initialized by the buyer/owner with the registration of a selected fingerprint pattern into secured memory of the device **800**. To register a selected fingerprint, the device owner holds the device **800** in the RF field generated by a point of sale ("POS") device, which may be a kiosk, personal computer, cash register, or similar device. The RF energy from the POS device provides for the power of the device **800** and display activation in step **1902**. In step **1904**, a determination is made as to whether the device **800** has been previously used. For example, the device **800** may determine if a fingerprint template analog is already stored in memory. If the device **800** has been previously used, the method **1900** ends. If the device has not been previously used, the device **800** continues to step **1906**, where the owner is prompted to actuate the biometric sensor. For example, this may entail the owner briefly touching the biometric sensor **802** on the device **800** with a selected finger or thumb. The fingerprint information is read from the biometric sensor **802** and stored in the device **800** in steps **1908**, **1910** while the owner maintains contact with the biometric sensor **802**. The owner may maintain contact with the biometric sensor **802** until, in step **1912**, an acknowledgement is displayed on the display **800** that the fingerprint pattern has been successfully registered in the device **800** as an encrypted template.

[0099] Referring specifically to **FIG. 20**, to authorize a payment transaction where invoice information is displayed by the POS device, the user of the device **800** holds the device **800** within a RF field generated by a RF reader connected to the POS device in step **2002**. For example, the

user may hold the device **810** at an approximate six inch distance from the RF reader. In step **2004**, the user actuates the biometric sensor **802** (e.g., touches the fingerprint sensor with his/her finger or thumb) to effect a comparative match with his/her previously registered fingerprint securely stored in the memory of the card. A successful match effects an encrypted approval and transfer of cardholder account data to the seller's administrative account receivables processing system.

[0100] In step **2006**, a determination is made as to whether the user desires to transfer electronic receipt information to the device **800**. If not, the method **2000** continues to step **2010**, where the device **800** is removed from the RF field. If it is determined in step **2006** that the user does want to transfer electronic receipt information to the device **800**, the method **2000** continues to step **2008**, where the device **800** stores the information in memory. The method **2000** may then continue to step **2008**, where the device **800** is removed from the RF field.

[0101] While the preceding description shows and describes one or more embodiments, it will be understood by those skilled in the art that various changes in form and entail may be made therein without departing from the spirit and scope of the present disclosure. For example, the present disclosure may be implemented in a variety of form factors, such as a wristwatch or wristwatch band, a key ring, or a variety of other physical structures. Therefore, the claims should be interpreted in a broad manner, consistent with the present disclosure.

What is claimed is:

1. An apparatus comprising:
 - a substrate;
 - a magnetic field generator disposed within the substrate that is normally inactive;
 - a biometric sensor mounted on the substrate;
 - a memory disposed within the substrate;
 - a processor disposed within the substrate and communicably coupled to the magnetic field generator, the biometric sensor and the memory, wherein the processor is operable to process biometric information received from the biometric sensor to verify that a user is authorized to use the apparatus and activate the magnetic field generator when the user is verified; and
 - a power source disposed within the substrate and electrically connected to the magnetic field generator, the biometric sensor and the processor.
2. The apparatus as recited in claim 1, wherein the magnetic field generator creates a time-varying magnetic signal for emulating data obtained from swiping a magnetic stripe card through a magnetic card reader.
3. The apparatus as recited in claim 1, wherein the magnetic field generator comprises a programmable magnetic stripe.
4. The apparatus as recited in claim 3, wherein the programmable magnetic stripe comprises:
 - a magnetic stripe either mounted on the substrate or disposed within the substrate;
 - one or more induction coils disposed within the substrate underneath the magnetic stripe; and

a controller disposed within the substrate that is connected to the one or more induction coils and operable to generate a spatially varying or time-varying magnetic signal via the one or more induction coils and the magnetic stripe.

5. The apparatus as recited in claim 4, wherein the magnetic signal includes binary data describing a user name, user number and apparatus expiration date.

6. The apparatus as recited in claim 4, wherein the magnetic stripe contains three-tracks and each track contains a set of magnetic data cells.

7. The apparatus as recited in claim 1, wherein the processor comprises a smart card processor and an ASIC chip.

8. The apparatus as recited in claim 1, wherein the power source is controlled by a power management unit.

9. The apparatus as recited in claim 1, wherein the power source is selected from the group consisting of a battery, a piezoelectric generator, a solar panel, an electromagnetic energy converter; a kinetic energy converter and combinations thereof.

10. The apparatus as recited in claim 1, wherein the power source comprises:

- a battery;
- a power generator;
- a converter electrically connected to the power generator and operable to convert power received from the power generator into power usable by the apparatus or to charge the battery;
- a battery management unit connected to the battery; and
- a power multiplexer connected to the battery management unit and the converter and operable to determine whether to draw power from the battery management unit, from the converter, or from both.

11. The apparatus as recited in claim 1, wherein the biometric sensor is selected from the group consisting of a fingerprint sensor, retina sensor, iris sensor or voice sensor.

12. The apparatus as recited in claim 1, wherein the biometric sensor comprises a matrix of points operable to detect high and low points corresponding to ridges and valleys of a fingerprint.

13. The apparatus as recited in claim 1, wherein the biometric sensor comprises an emitter and a detector wherein light projected by the emitter is reflected from a user's finger onto the detector.

14. The apparatus as recited in claim 1, further comprising a user interface mounted on the substrate that is communicably coupled to the processor and electrically connected to the power source.

15. The apparatus as recited in claim 14, wherein the user interface is selected from the group consisting of a touch pad, one or more buttons, a display and a voice sensor.

16. The apparatus as recited in claim 1, further comprising an output interface mounted on the substrate that is communicably coupled to the processor and electrically connected to the power source.

17. The apparatus as recited in claim 16, wherein the output interface is selected from the group consisting of an antenna for wireless communication and an optical transmitter.

18. The apparatus as recited in claim 1, further comprising a smart card interface mounted on the substrate that is

communicably coupled to the processor and electrically connected to the power source.

19. The apparatus as recited in claim 1, further comprising a contactless interface disposed within the substrate that is communicably coupled to the processor and electrically connected to the power source.

20. The apparatus as recited in claim 19, wherein the contactless interface is selected from the group consisting of an antenna for wireless communication and an optical transceiver.

21. The apparatus as recited in claim 1, wherein the substrate is semi-flexible.

22. The apparatus as recited in claim 1, wherein the substrate is integrated into a card selected from the group consisting of an access card, a credit card, a debit card, an identification card, a mini-card, a security card, a stored value card and a vendor-specific card.

23. The apparatus as recited in claim 1, wherein the substrate is integrated into a travel credential selected from the group consisting of a passport, an immigration card and a visa.

24. The apparatus as recited in claim 1, wherein the substrate is integrated into a personal communication device selected from a group consisting of a personal data assistant, a telecommunications device, a pager, a computer and an electronic mail transceiver.

25. The apparatus as recited in claim 1, wherein the substrate is integrated into a personal device/belonging selected from a group consisting of a watch, a jewelry, a key ring, a tag and eye glasses.

26. The apparatus as recited in claim 1, wherein the processor and the memory are integrated into a single integrated circuit.

27. The apparatus as recited in claim 1, wherein the memory contains a biometric analog of a user.

28. The apparatus as recited in claim 1, wherein the processor provides binary data to the magnetic field generator after a user has been authenticated using the biometric sensor.

29. The apparatus as recited in claim 1, wherein the processor deactivates the magnetic field generator after the magnetic field generator has been active for a specified period of time.

30. The apparatus as recited in claim 1, wherein the processor deactivates the magnetic field generator when the biometric sensor no longer detects the authorized user.

31. A method for enabling a transaction using an apparatus containing information associated with one or more users, a magnetic field generator that is normally inactive and a biometric sensor, the method comprising the steps of:

receiving authentication data from the biometric sensor;

determining whether the authentication data is valid for one of the users; and

activating the magnetic field generator and generating a magnetic signal corresponding to the information associated with the authenticated user whenever the authentication data is valid.

32. The method as recited in claim 31, wherein the information associated with the authenticated user enables approval of the transaction.

33. The method as recited in claim 31, further comprising the step of activating the magnetic field generator and

generating a magnetic signal that enables denial of the transaction whenever the authentication data is not valid.

34. The method as recited in claim 31, further comprising the step of receiving one or more activation parameters.

35. The method as recited in claim 34, wherein the one or more activation parameters includes detecting data from the biometric sensor, detecting an external signal or receiving data from a user interface.

36. The method as recited in claim 31, wherein the transaction is an access transaction, a control transaction, a financial transaction, a commercial transaction or an identification transaction.

37. The method as recited in claim 31, wherein the step of determining whether the authentication data is valid comprises comparing the authentication data to one or more biometric templates stored on the device.

38. The method as recited in claim 31, wherein the magnetic signal is a time-varying magnetic signal for emulating data obtained from swiping a magnetic stripe card through a magnetic card reader.

39. The method as recited in claim 31, further comprising the step of deactivating the magnetic field generator after the magnetic field generator has been active for a specified period of time.

40. The method as recited in claim 31, further comprising the step of deactivating the magnetic field generator when the biometric sensor no longer detects the authorized user.

41. The method as recited in claim 31, further comprising the step of selecting the information to enable the transaction.

42. The method as recited in claim 31, wherein the magnetic signal is a time-varying magnetic signal for emulating the data obtained from swiping a magnetic stripe card through a magnetic card reader.

43. The method as recited in claim 31, further comprising the step of displaying information to the user.

44. The method as recited in claim 31, further comprising the step of transmitting the information associated with the user via a wireless communications antenna.

45. The method as recited in claim 31, further comprising the steps of:

receiving power from an external power source in a contactless manner; and

converting the power received from the external power source into power compatible with the apparatus.

46. A computer program embodied in a computer readable medium for enabling a transaction using an apparatus containing information associated with one or more users, a magnetic field generator that is normally inactive and a biometric sensor, the computer program comprising:

a code segment for receiving authentication data from the biometric sensor;

a code segment for determining whether the authentication data is valid for one of the users; and

a code segment for activating the magnetic field generator and generating a magnetic signal corresponding to the information associated with the authenticated user whenever the authentication data is valid.

47. The computer program as recited in claim 46, wherein the information associated with the authenticated user enables approval of the transaction.

48. The computer program as recited in claim 46, further comprising a code segment for activating the magnetic field generator and generating a magnetic signal that enables denial of the transaction whenever the authentication data is not valid.

49. The computer program as recited in claim 46, further comprising a code segment for receiving one or more activation parameters.

50. The computer program as recited in claim 49, wherein the one or more activation parameters includes detecting data from the biometric sensor, detecting an external signal or receiving data from a user interface.

51. The computer program as recited in claim 46, wherein the transaction is an access transaction, a control transaction, a financial transaction, a commercial transaction or an identification transaction.

52. The computer program as recited in claim 46, wherein the code segment for determining whether the authentication data is valid comprises comparing the authentication data to one or more biometric templates stored on the device.

53. The computer program as recited in claim 46, wherein the magnetic signal is a time-varying magnetic signal for emulating data obtained from swiping a magnetic stripe card through a magnetic card reader.

54. The computer program as recited in claim 46, further comprising a code segment for deactivating the magnetic field generator after the magnetic field generator has been active for a specified period of time.

55. The computer program as recited in claim 46, further comprising a code segment for deactivating the magnetic field generator when the biometric sensor not longer detects the authorized user.

56. The computer program as recited in claim 46, further comprising a code segment for selecting the information to enable the transaction.

57. The computer program as recited in claim 46, wherein the magnetic signal is a time-varying magnetic signal for emulating the data obtained from swiping a magnetic stripe card through a magnetic card reader.

58. The computer program as recited in claim 46, further comprising a code segment for displaying information to the user.

59. The computer program as recited in claim 46, further comprising a code segment for transmitting the information associated with the user via a wireless communications antenna.

60. A system comprising:

- one or more user devices, each user device comprising
 - a substrate,
 - a magnetic field generator disposed within the substrate that is normally inactive,
 - a biometric sensor mounted on the substrate,
 - a memory disposed within the substrate,
 - a device processor disposed within the substrate and communicably coupled to the magnetic field generator, the biometric sensor and the memory, wherein the processor is operable to process biometric information received from the biometric sensor to verify that a user is authorized to use the apparatus and activate the magnetic field generator when the user is verified, and

- a power source disposed within the substrate and electrically connected to the magnetic field generator, the biometric sensor and the device processor;

- one or more system interfaces operable to communicate with the user device; and

- a system processor communicably coupled to the one or more system interfaces.

61. The system as recited in claim 60, wherein the one or more system interfaces includes an optical interface, a smart card interface, a wireless communication interface, a magnetic reader, an initialization interface or a recharger.

62. The system as recited in claim 60, further comprising a database communicably coupled to the system processor.

63. The system as recited in claim 60, further comprising one or more remote computers communicably coupled to the system processor via a network.

64. The system as recited in claim 60, wherein the magnetic field generator creates a time-varying magnetic signal for emulating data obtained from swiping a magnetic stripe card through a magnetic card reader.

65. The system as recited in claim 60, wherein the magnetic field generator comprises a programmable magnetic stripe.

66. The system as recited in claim 65, wherein the programmable magnetic stripe comprises:

- a magnetic stripe either mounted on the substrate or disposed within the substrate;

- one or more induction coils disposed within the substrate underneath the magnetic stripe; and

- a controller disposed within the substrate that is connected to the one or more induction coils and operable to generate a magnetic signal via the one or more induction coils and the magnetic stripe.

67. The system as recited in claim 66, wherein the magnetic signal includes binary data describing a user name, user number and apparatus expiration date.

68. The system as recited in claim 66, wherein the magnetic stripe contains three-tracks and each track contains a set of magnetic data cells.

69. The system as recited in claim 60, wherein the device processor comprises a smart card processor and an ASIC chip.

70. The system as recited in claim 60, wherein the power source is controlled by a power management unit.

71. The system as recited in claim 60, wherein the power source is selected from the group consisting of a battery, a piezoelectric generator, a solar panel, an electromagnetic energy converter, a kinetic energy converter and combinations thereof.

72. The system as recited in claim 60, wherein the power source comprises:

- a battery;

- a power generator;

- a converter electrically connected to the power generator and operable to convert power received from the power generator into power usable by the apparatus or to charge the battery;

- a battery management unit connected to the battery; and

a power multiplexer connected to the battery management unit and the converter and operable to determine whether to draw power from the battery management unit, from the converter, or from both.

73. The system as recited in claim 60, wherein the biometric sensor is selected from the group consisting of a fingerprint sensor, retina sensor, iris sensor or voice sensor.

74. The system as recited in claim 60, wherein the biometric sensor comprises a matrix of points operable to detect high and low points corresponding to ridges and valleys of a fingerprint.

75. The system as recited in claim 60, wherein the biometric sensor comprises an emitter and a detector wherein light projected by the emitter is reflected from a user's finger onto the detector.

76. The system as recited in claim 60, further comprising a user interface mounted on the substrate that is communicably coupled to the device processor and electrically connected to the power source.

77. The system as recited in claim 76, wherein the user interface is selected from the group consisting of a touch pad, one or more buttons, a display and a voice sensor.

78. The system as recited in claim 60, further comprising an output interface mounted on the substrate that is communicably coupled to the device processor and electrically connected to the power source.

79. The system as recited in claim 78, wherein the output interface is selected from the group consisting of an antenna for wireless communication and an optical transmitter.

80. The system as recited in claim 60, further comprising a smart card interface mounted on the substrate that is communicably coupled to the device processor and electrically connected to the power source.

81. The system as recited in claim 60, further comprising a contactless interface disposed within the substrate that is communicably coupled to the device processor and electrically connected to the power source.

82. The system as recited in claim 81, wherein the contactless interface is selected from the group consisting of an antenna for wireless communication and an optical transceiver.

83. The system as recited in claim 60, wherein the substrate is semi-flexible.

84. The system as recited in claim 60, wherein the substrate is integrated into a card selected from the group consisting of an access card, a credit card, a debit card, an identification card, a mini-card, a security card, a stored value card and a vendor-specific card.

85. The system as recited in claim 60, wherein the substrate is integrated into a travel credential selected from the group consisting of a passport, an immigration card and a visa.

86. The system as recited in claim 60, wherein the substrate is integrated into a personal communication device selected from a group consisting of a personal data assistant, a telecommunications device, a pager, a computer and an electronic mail transceiver.

87. The system as recited in claim 60, wherein the substrate is integrated into a personal device/belonging selected from a group consisting of a watch, a jewelry, a key ring, a tag and eye glasses.

88. The system as recited in claim 60, wherein the device processor and the memory are integrated into a single integrated circuit.

89. The system as recited in claim 60, wherein the memory contains a biometric analog of a user.

90. The system as recited in claim 60, wherein the device processor provides binary data to the magnetic field generator after a user has been authenticated using the biometric sensor.

91. The system as recited in claim 60, wherein the device processor deactivates the magnetic field generator after the magnetic field generator has been active for a specified period of time.

92. The system as recited in claim 60, wherein the device processor deactivates the magnetic field generator when the biometric sensor no longer detects the authorized user.

* * * * *