



US011270174B2

(12) **United States Patent**
Narendra et al.

(10) **Patent No.:** **US 11,270,174 B2**

(45) **Date of Patent:** ***Mar. 8, 2022**

(54) **MOBILE PHONE WITH MAGNETIC CARD EMULATION**

19/07741 (2013.01); *G06K 19/07758*
(2013.01); *G06K 19/07762* (2013.01); *G06Q*
20/204 (2013.01);

(71) Applicant: **iCashe, Inc.**, Portland, OR (US)

(Continued)

(72) Inventors: **Siva G. Narendra**, Portland, OR (US);
Thomas N. Spitzer, Portland, OR (US);
Prabhakar Tadepalli, Bangalore (IN)

(58) **Field of Classification Search**

None

See application file for complete search history.

(73) Assignee: **iCashe, Inc.**, Portland, OR (US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,701,601 A 10/1987 Francini et al.

4,786,791 A 11/1988 Hodama

(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

FOREIGN PATENT DOCUMENTS

(21) Appl. No.: **17/021,347**

DE 3632294 A1 4/1988

DE 10054890 A1 4/2002

(22) Filed: **Sep. 15, 2020**

(Continued)

(65) **Prior Publication Data**

US 2021/0004655 A1 Jan. 7, 2021

OTHER PUBLICATIONS

International Search Report PCT Application No. PCT/US2005/019988, dated Dec. 16, 2005, 5 pages.

(Continued)

Related U.S. Application Data

(63) Continuation of application No. 16/218,733, filed on Dec. 13, 2018, now Pat. No. 10,803,370, which is a (Continued)

Primary Examiner — Kristy A Haupt

(74) *Attorney, Agent, or Firm* — Mughal IP P.C.

(51) **Int. Cl.**

G06K 19/06 (2006.01)

H04M 1/72412 (2021.01)

(Continued)


(57) **ABSTRACT**

An electronic transaction card communicates with an add-on slot of an intelligent electronic device. The add-on slot may be a memory card slot. The intelligent electronic device may be a mobile phone or other device with or without network connectivity. The electronic transaction card may have magnetic field producing circuitry compatible with magnetic card readers, smartcard circuitry, other point-of-sale interfaces, or any combination thereof.

(52) **U.S. Cl.**

CPC **G06K 19/06206** (2013.01); **G06K 7/0008**
(2013.01); **G06K 19/06187** (2013.01); **G06K**
19/07 (2013.01); **G06K 19/073** (2013.01);
G06K 19/0703 (2013.01); **G06K 19/0723**
(2013.01); **G06K 19/0727** (2013.01); **G06K**

27 Claims, 16 Drawing Sheets



Related U.S. Application Data

continuation of application No. 15/658,208, filed on Jul. 24, 2017, now Pat. No. 10,185,909, which is a continuation of application No. 14/948,325, filed on Nov. 22, 2015, now Pat. No. 9,715,649, which is a continuation of application No. 14/747,770, filed on Jun. 23, 2015, now Pat. No. 9,202,156, which is a continuation of application No. 14/680,684, filed on Apr. 7, 2015, now Pat. No. 9,092,708, which is a continuation of application No. 13/592,323, filed on Aug. 22, 2012, now Pat. No. 9,004,361, which is a continuation of application No. 13/304,663, filed on Nov. 27, 2011, now Pat. No. 8,573,494, which is a continuation of application No. 13/114,434, filed on May 24, 2011, now Pat. No. 8,091,786, which is a continuation of application No. 12/941,410, filed on Nov. 8, 2010, now Pat. No. 7,954,715, which is a continuation of application No. 12/539,369, filed on Aug. 11, 2009, now Pat. No. 7,828,214, which is a continuation of application No. 11/063,291, filed on Feb. 22, 2005, now Pat. No. 7,581,678.

(51) **Int. Cl.**

G06K 19/073 (2006.01)
G06Q 20/20 (2012.01)
G06Q 20/32 (2012.01)
G06K 7/00 (2006.01)
G06Q 20/34 (2012.01)
G06K 19/07 (2006.01)
G06K 19/077 (2006.01)

(52) **U.S. Cl.**

CPC **G06Q 20/327** (2013.01); **G06Q 20/341**
 (2013.01); **G06Q 20/353** (2013.01); **H04M**
1/72412 (2021.01)

(56)

References Cited**U.S. PATENT DOCUMENTS**

4,791,283 A 12/1988 Burkhardt
 4,864,109 A 9/1989 Minematsu et al.
 5,212,478 A 5/1993 Moseley
 5,378,887 A 1/1995 Kobayashi
 5,386,106 A 1/1995 Kumar
 5,537,584 A 7/1996 Miyai et al.
 5,574,273 A 11/1996 Nakagawa et al.
 5,585,787 A 12/1996 Wallerstein
 5,629,981 A 5/1997 Nerlikar
 5,700,037 A 12/1997 Keller
 5,710,421 A 1/1998 Kokubu
 5,834,756 A 11/1998 Gutman et al.
 5,909,491 A 6/1999 Luo
 5,940,510 A 8/1999 Curry et al.
 5,949,880 A 9/1999 Curry et al.
 5,952,641 A 9/1999 Korshun
 5,955,961 A 9/1999 Wallerstein
 6,016,476 A 1/2000 Maes et al.
 6,021,944 A 2/2000 Arakaki
 6,039,260 A 3/2000 Eisele
 6,045,043 A 4/2000 Bashan et al.
 6,068,184 A 5/2000 Barnett
 6,105,013 A 8/2000 Curry et al.
 6,182,891 B1 2/2001 Furuhashi et al.
 6,189,786 B1 2/2001 Itou et al.
 6,206,293 B1 3/2001 Gutman et al.
 6,219,439 B1 4/2001 Burger
 6,223,954 B1 5/2001 Carow
 6,223,984 B1 5/2001 Renner et al.
 6,237,095 B1 5/2001 Curry et al.
 6,250,557 B1 6/2001 Forslund et al.
 6,315,195 B1 11/2001 Ramachandran

6,402,029 B1 6/2002 Gangi
 6,450,407 B1 9/2002 Freeman et al.
 6,481,623 B1 11/2002 Grant et al.
 6,568,600 B1 5/2003 Carpier et al.
 6,588,660 B1 7/2003 Buescher et al.
 6,592,044 B1 7/2003 Wong et al.
 6,594,759 B1 7/2003 Wang
 6,598,031 B1 7/2003 Ice
 6,607,127 B2 8/2003 Wong
 6,609,654 B1 8/2003 Anderson et al.
 6,631,849 B2 10/2003 Blossom
 6,636,833 B1 10/2003 Flitcroft et al.
 6,669,487 B1 12/2003 Nishizawa et al.
 6,705,520 B1 3/2004 Pitroda et al.
 6,712,277 B2 3/2004 Spencer
 6,715,679 B1 4/2004 Infosino
 6,721,196 B1 4/2004 Grassl
 6,747,547 B2 6/2004 Benson
 6,764,005 B2 7/2004 Cooper
 6,769,607 B1 8/2004 Pitroda et al.
 6,805,288 B2 10/2004 Routhenstein et al.
 6,811,082 B2 11/2004 Wong
 6,836,843 B2 12/2004 Seroussi et al.
 6,857,566 B2 2/2005 Wankmueller
 6,882,900 B1 4/2005 Terranova
 6,883,718 B1 4/2005 Le et al.
 6,905,072 B2 6/2005 Ramachandran
 6,907,123 B1 6/2005 Schier
 6,908,030 B2 6/2005 Rajasekaran et al.
 6,925,568 B1 8/2005 Heinonen
 6,937,526 B2 8/2005 Furukawa
 6,952,788 B2 10/2005 Rommelmann et al.
 6,995,651 B2 2/2006 Amtmann et al.
 7,059,520 B1 6/2006 Shtesl
 7,088,246 B2 8/2006 Fukuoka
 7,185,146 B2 2/2007 Masuyama et al.
 7,213,766 B2 5/2007 Ryan et al.
 7,221,473 B2 5/2007 Jeran et al.
 7,281,101 B2 10/2007 Mizushima et al.
 7,295,790 B2 11/2007 Morimoto et al.
 7,333,062 B2 2/2008 Leizerovich et al.
 7,350,717 B2 4/2008 Conner et al.
 7,353,993 B2 4/2008 Fujimoto
 7,410,102 B2 8/2008 Winkler
 7,493,484 B2 2/2009 Lee
 7,558,107 B2 7/2009 Sakurai et al.
 7,558,110 B2 7/2009 Mizushima et al.
 7,581,678 B2 9/2009 Narendra et al.
 7,607,580 B2 10/2009 Takita et al.
 7,673,080 B1 3/2010 Yu et al.
 RE41,352 E 5/2010 Wood, Jr.
 7,716,082 B1 5/2010 Blalock
 RE41,471 E 8/2010 Wood, Jr.
 7,789,303 B2 9/2010 Fukasawa
 7,792,516 B2 9/2010 Soderstrom
 7,828,214 B2 11/2010 Narendra et al.
 RE42,254 E 3/2011 Wood, Jr.
 7,898,994 B2 3/2011 Zhao et al.
 7,933,571 B2 4/2011 Black et al.
 7,941,197 B2 5/2011 Jain et al.
 7,948,356 B2 5/2011 Kawamura et al.
 7,954,715 B2 6/2011 Narendra et al.
 7,954,716 B2 6/2011 Narendra et al.
 7,954,717 B2 6/2011 Narendra et al.
 7,961,101 B2 6/2011 Narendra et al.
 7,991,158 B2 8/2011 Narendra et al.
 8,072,331 B2 12/2011 Narendra et al.
 8,082,575 B2 12/2011 Doughty et al.
 8,083,145 B2 12/2011 Narendra et al.
 8,091,786 B2 1/2012 Narendra et al.
 8,103,881 B2 1/2012 Doughty et al.
 9,092,708 B1 7/2015 Narendra et al.
 9,202,156 B2 12/2015 Narendra et al.
 9,715,649 B2* 7/2017 Narendra G06K 19/07741
 2001/0002035 A1 5/2001 Kayanakakis
 2001/0006902 A1 7/2001 Ito
 2001/0013551 A1 8/2001 Ramachandran
 2001/0034246 A1 10/2001 Hutchison et al.
 2002/0007434 A1 1/2002 Campardo

(56)

References Cited

U.S. PATENT DOCUMENTS

2002/0025796 A1	2/2002	Taylor et al.	2005/0127166 A1	6/2005	Minemura
2002/0043566 A1	4/2002	Goodman et al.	2005/0133606 A1	6/2005	Brown
2002/0044043 A1	4/2002	Chaco et al.	2005/0136964 A1	6/2005	Le Saint et al.
2002/0095588 A1	7/2002	Shigematsu et al.	2005/0168339 A1	8/2005	Arai et al.
2002/0096570 A1	7/2002	Wong et al.	2005/0177724 A1	8/2005	Ali et al.
2002/0099665 A1	7/2002	Burger et al.	2005/0197859 A1	9/2005	Wilson et al.
2002/0130187 A1	9/2002	Berg et al.	2005/0204077 A1	9/2005	Kou
2002/0138422 A1	9/2002	Natsuno	2005/0204092 A1	9/2005	Masuyama et al.
2002/0138735 A1	9/2002	Felt et al.	2005/0212657 A1	9/2005	Simon
2002/0139849 A1	10/2002	Gangi	2005/0223143 A1	10/2005	Kang et al.
2002/0148892 A1	10/2002	Bardwell	2005/0224589 A1	10/2005	Park et al.
2002/0153424 A1	10/2002	Li	2005/0240778 A1	10/2005	Saito
2002/0158747 A1	10/2002	Mcgregor et al.	2005/0246546 A1	11/2005	Takagi et al.
2002/0178124 A1	11/2002	Lewis	2005/0253687 A1	11/2005	Martinez et al.
2002/0180584 A1	12/2002	Mcgregor et al.	2005/0258245 A1	11/2005	Bates et al.
2002/0186845 A1	12/2002	Dutta et al.	2005/0268058 A1	12/2005	Drasnin et al.
2003/0025939 A1	2/2003	Jeran et al.	2005/0268330 A1	12/2005	Di Rienzo
2003/0028481 A1	2/2003	Flitcroft et al.	2006/0011731 A1	1/2006	Anders et al.
2003/0038177 A1	2/2003	Morrow	2006/0027655 A1	2/2006	Smets et al.
2003/0052168 A1	3/2003	Wong	2006/0045555 A1	3/2006	Morimoto et al.
2003/0057278 A1	3/2003	Wong	2006/0077039 A1	4/2006	Ibi et al.
2003/0061168 A1	3/2003	Routhenstein	2006/0097851 A1	5/2006	Amtmann et al.
2003/0079096 A1	4/2003	Murakami	2006/0124755 A1	6/2006	Ito
2003/0080183 A1	5/2003	Rajasekaran et al.	2006/0169778 A1	8/2006	Chung
2003/0084220 A1	5/2003	Jones et al.	2006/0172606 A1	8/2006	Irisawa
2003/0085288 A1	5/2003	Luu	2006/0186209 A1	8/2006	Narendra et al.
2003/0115126 A1	6/2003	Pitroda	2006/0219776 A1	10/2006	Finn
2003/0128124 A1	7/2003	Amtmann et al.	2006/0226217 A1	10/2006	Narendra et al.
2003/0159050 A1	8/2003	Gantman et al.	2006/0268764 A1	11/2006	Harris
2003/0200180 A1	10/2003	Phelan et al.	2006/0279413 A1	12/2006	Yeager
2003/0209604 A1	11/2003	Harrison	2007/0033334 A1	2/2007	Katayama et al.
2003/0218066 A1	11/2003	Fernandes et al.	2007/0076877 A1	4/2007	Camp et al.
2003/0220876 A1	11/2003	Burger et al.	2007/0108280 A1	5/2007	Li et al.
2003/0231550 A1	12/2003	Macfarlane	2007/0110404 A1	5/2007	Ching et al.
2004/0006654 A1	1/2004	Bando	2007/0145135 A1	6/2007	Jogand-Coulomb et al.
2004/0027881 A1	2/2004	Furukawa	2007/0145152 A1	6/2007	Jogand-Coulomb et al.
2004/0030660 A1	2/2004	Shatford	2007/0195458 A1	8/2007	Sawai et al.
2004/0035942 A1	2/2004	Silverman	2007/0205864 A1	9/2007	Mutti et al.
2004/0050930 A1	3/2004	Rowe	2007/0257797 A1	11/2007	Rancien et al.
2004/0058705 A1	3/2004	Morgan et al.	2007/0293202 A1	12/2007	Moshir et al.
2004/0064612 A1	4/2004	Pinto et al.	2008/0046649 A1	2/2008	Ito
2004/0065733 A1	4/2004	Fukuoka	2008/0065830 A1	3/2008	Aoki et al.
2004/0077372 A1	4/2004	Halpern	2008/0068173 A1	3/2008	Alexis et al.
2004/0087339 A1	5/2004	Goldthwaite et al.	2008/0073436 A1	3/2008	Nishizawa et al.
2004/0094624 A1	5/2004	Fernandes et al.	2008/0136619 A1	6/2008	Moran
2004/0122685 A1	6/2004	Bunce	2008/0147950 A1	6/2008	Chen
2004/0133787 A1	7/2004	Doughty et al.	2008/0148077 A1	6/2008	Lee et al.
2004/0162932 A1	8/2004	Mizushima et al.	2008/0153416 A1	6/2008	Washiro
2004/0177045 A1	9/2004	Brown	2008/0186174 A1	8/2008	Alexis et al.
2004/0188519 A1	9/2004	Cassone	2008/0214111 A1	9/2008	Moshir et al.
2004/0199469 A1	10/2004	Barilova et al.	2008/0244208 A1	10/2008	Narendra et al.
2004/0227859 A1	11/2004	Liang	2008/0279381 A1	11/2008	Narendra et al.
2004/0243785 A1	12/2004	Shanmugasundaram et al.	2008/0311849 A1	12/2008	Washiro
2004/0243806 A1	12/2004	Mckinley et al.	2008/0318535 A1	12/2008	Black et al.
2004/0251303 A1	12/2004	Cooper	2009/0065571 A1	3/2009	Jain
2004/0255145 A1	12/2004	Chow	2009/0065572 A1	3/2009	Jain
2005/0006462 A1	1/2005	Rouille et al.	2009/0069049 A1	3/2009	Jain
2005/0017068 A1	1/2005	Zalewski et al.	2009/0069050 A1	3/2009	Jain et al.
2005/0022002 A1	1/2005	Poisner	2009/0069051 A1	3/2009	Jain et al.
2005/0029349 A1	2/2005	Mcgregor et al.	2009/0069052 A1	3/2009	Jain et al.
2005/0038736 A1	2/2005	Saunders	2009/0070272 A1	3/2009	Jain
2005/0039027 A1	2/2005	Shapiro	2009/0070691 A1	3/2009	Jain
2005/0044044 A1	2/2005	Burger et al.	2009/0070861 A1	3/2009	Jain
2005/0050367 A1	3/2005	Burger et al.	2009/0108063 A1	4/2009	Jain et al.
2005/0052924 A1	3/2005	Nishizawa et al.	2009/0150610 A1	6/2009	Hsu et al.
2005/0060586 A1	3/2005	Burger et al.	2009/0152361 A1	6/2009	Narendra et al.
2005/0071282 A1	3/2005	Lu et al.	2009/0199283 A1	8/2009	Jain
2005/0077349 A1	4/2005	Bonalle et al.	2009/0250521 A1	10/2009	Fujita et al.
2005/0092830 A1	5/2005	Blossom	2009/0265552 A1	10/2009	Moshir et al.
2005/0108096 A1	5/2005	Burger et al.	2009/0270127 A1	10/2009	Kakimoto
2005/0109838 A1	5/2005	Linlor	2009/0290582 A1	11/2009	Suenaga et al.
2005/0116026 A1	6/2005	Burger et al.	2009/0298540 A1	12/2009	Narendra et al.
2005/0121512 A1	6/2005	Wankmueller	2009/0315667 A1	12/2009	Kawamura et al.
2005/0122209 A1	6/2005	Black	2010/0033307 A1	2/2010	Narendra et al.
2005/0127164 A1	6/2005	Wankmueller	2010/0033310 A1	2/2010	Narendra et al.
			2010/0049878 A1	2/2010	Yu et al.
			2010/0213265 A1	8/2010	Narendra et al.
			2011/0000960 A1	1/2011	Harris
			2011/0053644 A1	3/2011	Narendra et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2011/0073663	A1	3/2011	Narendra et al.
2011/0073665	A1	3/2011	Narendra et al.
2011/0077052	A1	3/2011	Narendra et al.
2011/0110404	A1	5/2011	Washiro
2011/0171996	A1	7/2011	Narendra et al.
2011/0180610	A1	7/2011	Narendra et al.
2011/0220726	A1	9/2011	Narendra et al.
2011/0223972	A1	9/2011	Narendra et al.
2011/0240748	A1*	10/2011	Doughty G06Q 20/40145 235/492
2011/0269438	A1	11/2011	Narendra et al.
2011/0271044	A1	11/2011	Narendra et al.
2011/0272468	A1	11/2011	Narendra et al.
2011/0272469	A1	11/2011	Narendra et al.

FOREIGN PATENT DOCUMENTS

EP	161060	A1	11/1985
EP	0818757	A2	1/1998
EP	1014290	A2	6/2000
EP	1117068	A1	7/2001
EP	1178450	A2	2/2002
EP	1189465	A1	3/2002
EP	1291748	A2	3/2003
EP	1308874	A2	5/2003
GB	2316908	A	3/1998
JP	4102112	A	4/1992
JP	2000010668	A	1/2000
JP	2005018671	A	1/2005
JP	2007199847	A	8/2007
JP	2007328689	A	12/2007
TW	200905471	A	2/2009
TW	201020934	B	6/2010
TW	201023662	A	6/2010
TW	1336449		1/2011
TW	201126422	A	8/2011
WO	9626500	A1	8/1996
WO	9812674	A2	3/1998
WO	0014678	A1	3/2000
WO	0188659	A2	11/2001
WO	03029942	A2	4/2003
WO	03077473	A1	9/2003
WO	03081519	A2	10/2003
WO	2004012352	A1	2/2004
WO	2004095169	A2	11/2004
WO	2005027030	A1	3/2005
WO	2005119607	A2	12/2005
WO	2005119608	A1	12/2005
WO	2006091709	A2	8/2006
WO	2006108184	A1	10/2006
WO	2007011937	A2	1/2007
WO	2008121566	A1	10/2008
WO	2009147548	A2	12/2009
WO	2010099093	A1	9/2010

OTHER PUBLICATIONS

International Search Report PCT Application No. PCT/US2005/022993, dated Oct. 21, 2005, 3 pages.

International Search Report PCT Application No. PCT/US2006/013603, dated Jan. 9, 2006, 3 pages.

International Search Report PCT Application No. PCT/US2006/027847, dated Mar. 29, 2007, 5 pages.

International Search Report PCT Application No. PCT/US2008/057588, dated Aug. 7, 2008, 1 pages.

International Written Opinion PCT Application No. PCT/US2005/019988, dated Dec. 4, 2006, 9 Pages.

International Written Opinion PCT Application No. PCT/US2005/019988, dated Jan. 11, 2006, 8 pages.

International Written Opinion PCT Application No. PCT/US2005/022993, dated Dec. 4, 2006, 6 pages.

International Written Opinion PCT Application No. PCT/US2006/006361, dated Aug. 28, 2007, 8 pages.

International Written Opinion PCT Application No. PCT/US2006/006361, dated Sep. 22, 2006, 13 pages.

International Written Opinion PCT Application No. PCT/US2006/013603, dated Oct. 9, 2007, 7 pages.

International Written Opinion PCT Application No. PCT/US2006/027847, dated Jan. 22, 2008, 10 pages.

International Written Opinion PCT Application No. PCT/US2008/057588, dated Aug. 7, 2008, 5 pages.

International Written Opinion PCT Application No. PCT/US2008/057588, dated Oct. 6, 2009, 6 pages.

International Written Opinion PCT Application No. PCT/US2010/025014, dated Apr. 15, 2010, 9 pages.

International Written Opinion PCT Application No. PCT/US2010/025014, dated Sep. 9, 2011, 6 pages.

Lee, Youbok; "Antenna Circuit Design for RFID Applications", Microchip, AN710, 2003 Microchip Technology Inc., (2003), 50 pages.

Official Letter from Taiwan Patent Office 115.001TW1, Application 95105997, and Search Report dated Oct. 20, 2010, 6 pages.

U.S. Appl. No. 13/592,323 Office Action dated Sep. 30, 2014, 6 pages.

U.S. Appl. No. 14/680,684 Office Action dated May 22, 2015, 5 pages.

U.S. Appl. No. 14/747,770 Office Action dated Sep. 25, 2015, 7 pages.

U.S. Appl. No. 14/833,113 Office Action dated Sep. 24, 2015, 9 pages.

U.S. Appl. No. 14/866,998 Office Action dated Nov. 5, 2015, 7 pages.

U.S. Appl. No. 14/929,297 Office Action dated Sep. 16, 2016, 8 pages.

U.S. Appl. No. 14/948,325 Office Action dated Sep. 20, 2016, 7 pages.

U.S. Appl. No. 15/658,208 Office Action dated Apr. 19, 2018, 7 pages.

U.S. Appl. No. 16/218,733 Office Action dated Nov. 29, 2019, 6 pages.

Final Office Action dated Dec. 26, 2007 for U.S. Appl. No. 11/063,291.

Non-Final Office Action dated Dec. 11, 2008 for U.S. Appl. No. 11/063,291.

Non-Final Office Action dated Feb. 26, 2007 for U.S. Appl. No. 11/063,291.

Non-Final Office Action dated Jul. 8, 2010 for U.S. Appl. No. 12/539,369.

Non-Final Office Action dated Jul. 23, 2008 for U.S. Appl. No. 11/063,291.

Notice of Allowance dated Apr. 14, 2011 for U.S. Appl. No. 12/941,410.

Notice of Allowance dated Jul. 10, 2009 for U.S. Appl. No. 11/063,291.

Notice of Allowance dated Sep. 30, 2010 for U.S. Appl. No. 12/539,369.

* cited by examiner




FIG. 1





FIG. 2A

*FIG. 2B*




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20






FIG. 21

*FIG. 22*

*FIG. 23*

1

MOBILE PHONE WITH MAGNETIC CARD
EMULATION

CLAIM FOR PRIORITY

This application is a continuation of, and claims the benefit of priority to U.S. patent application Ser. No. 16/218,733, filed Dec. 13, 2018, now issued as U.S. Pat. No. 10,803,370 on Oct. 13, 2020, which is a continuation of, and claims the benefit of priority to U.S. patent application Ser. No. 15/658,208, filed Jul. 24, 2017, now issued as U.S. Pat. No. 10,185,909 on Jan. 22, 2019, which is a continuation of, and claims the benefit of priority to U.S. patent application Ser. No. 14/948,325, filed Nov. 22, 2015, now issued as U.S. Pat. No. 9,715,649 on Jul. 25, 2017, which is a continuation of, and claims the benefit of priority to U.S. patent application Ser. No. 14/747,770, filed Jun. 23, 2015, now issued as U.S. Pat. No. 9,202,156 on Dec. 1, 2015 which is a continuation of, and claims the benefit of priority to U.S. patent application Ser. No. 14/680,684, filed Apr. 7, 2015, now issued as U.S. Pat. No. 9,092,708 on Jul. 28, 2015 which is a continuation of, and claims the benefit of priority to U.S. patent application Ser. No. 13/592,323, filed Aug. 22, 2012, now issued as U.S. Pat. No. 9,004,361 on Apr. 14, 2015, which is a continuation of, and claims the benefit of priority to U.S. patent application Ser. No. 13/304,663, filed Nov. 27, 2011, now issued as U.S. Pat. No. 8,573,494 on Nov. 5, 2013, which is a continuation of, and claims the benefit of priority to U.S. patent application Ser. No. 13/114,434, filed May 24, 2011, now issued as U.S. Pat. No. 8,091,786, on Jan. 10, 2012, which is a continuation of, and claims the benefit of priority to U.S. patent application Ser. No. 12/941,410, filed Nov. 8, 2010, now issued as U.S. Pat. No. 7,954,715 on Jun. 7, 2011, which is a continuation of, and claims the benefit of priority to U.S. patent application Ser. No. 12/539,369, filed Aug. 11, 2009, now issued as U.S. Pat. No. 7,828,214 on Nov. 9, 2010, which is a continuation of, and claims the benefit of priority to U.S. patent application Ser. No. 11/063,291, filed Feb. 22, 2005, now issued as U.S. Pat. No. 7,581,678 on Sep. 1, 2009, and which is incorporated by reference in entirety.

FIELD

The present invention relates generally to electronic devices, and more specifically to electronic devices that may perform transactions.

BACKGROUND

Magnetic cards have many purposes. Examples include credit cards, debit cards, stored value cards, identification cards, access entry cards, and the like. Many of these cards have information stored in a magnetic stripe in a static manner. For example, a credit card may have a credit card number, a cardholder's name, and an issuing bank's name statically encoded in a magnetic strip. Likewise, an identification card or access entry card may have statically encoded information that identifies an individual or allows access to a controlled access area. When the card is swiped through a magnetic card reader, the information is transferred to the magnetic card reader to perform a transaction, such as a financial transaction or identification transaction.

2

BRIEF DESCRIPTION OF THE DRAWINGS

FIGS. 1, 2A, and 2B show intelligent electronic devices and electronic transaction cards;

FIG. 3 shows a block diagram of an electronic transaction card;

FIG. 4 shows an electronic transaction card in a magnetic card reader;

FIG. 5 shows an intelligent electronic device and card in a card reader;

FIGS. 6-8 show adapters for use with electronic transaction cards;

FIGS. 9 and 10 show an electronic transaction card having a smartcard interface;

FIG. 11 shows an adapter in combination with an electronic transaction card;

FIG. 12 shows an adapter having an aperture to receive an electronic transaction card;

FIG. 13 shows another adapter embodiment;

FIG. 14 shows an electronic transaction card;

FIG. 15 shows an electronic transaction card and adapter combination;

FIG. 16 shows an example swallow-type card reader;

FIG. 17 shows a combination electronic transaction card and adapter being swiped through a magnetic card reader;

FIG. 18 shows a financial transaction card;

FIG. 19 shows a memory card;

FIG. 20 shows a block diagram of a combination memory card and electronic transaction card;

FIG. 21 shows a diagram of how a card may be utilized;

FIG. 22 shows a block diagram of a combination memory card and electronic transaction card; and

FIG. 23 shows a block diagram of a phone and a card.

DESCRIPTION OF EMBODIMENTS

In the following detailed description, reference is made to the accompanying drawings that show, by way of illustration, various embodiments of an invention. These embodiments are described in sufficient detail to enable those skilled in the art to practice the invention. It is to be understood that the various embodiments of the invention, although different, are not necessarily mutually exclusive. For example, a particular feature, structure, or characteristic described in connection with one embodiment may be implemented within other embodiments without departing from the spirit and scope of the invention. In addition, it is to be understood that the location or arrangement of individual elements within each disclosed embodiment may be modified without departing from the spirit and scope of the invention. The following detailed description is, therefore, not to be taken in a limiting sense, and the scope of the present invention is defined only by the appended claims, appropriately interpreted, along with the full range of equivalents to which the claims are entitled. In the drawings, like numerals refer to the same or similar functionality throughout the several views.

FIG. 1 shows an intelligent electronic device and an electronic transaction card. Intelligent electronic device **102** is shown as a mobile phone in FIG. 1, but this is not a limitation of the present invention. For example, intelligent electronic device **102** may be a personal digital assistant (PDA), a smartphone, a mobile phone, a handheld computer, or any other device capable of operating as described herein.

Intelligent electronic device **102** includes add-on slot **110**. Add-on slot **110** is a slot capable of accepting electronic transaction card **104**. For example, add-on slot **110** may have

3

physical dimensions compatible with electronic transaction card **104**, and may have a communications interface that operates using a protocol compatible with electronic transaction card **104**. In some embodiments, electronic transaction card **104** includes an identification number that provides a relationship to intelligent electronic device **102**. For example, electronic transaction card **104** may include an ID number that provides a unique pairing relationship or a non-unique pairing relationship between electronic transaction card **104** and intelligent electronic device **102**.

In some embodiments of the present invention, add-on slot **110** is a memory card slot designed to accept and communicate with memory cards. As used herein, the term “memory card slot” refers to any add-on slot capable of accepting a card having memory accessible by an intelligent electronic device such as that shown in FIG. 1. For example, a memory card slot may be a proprietary card slot designed to accept memory cards that adhere to a proprietary communications protocol. Also for example, a memory card slot may be compatible with an industry standard communications protocol, or may be compatible with a widely accepted communications protocol that is not necessarily formally documented as an industry standard. Examples include slots that are compatible with the Multimedia Memory Card (MMC) protocol, Memory Stick DUO protocol, secure digital (SD) protocol, and Smart Media protocol. The foregoing list is meant to be exemplary, and not exhaustive. Add-on slot **110** may be compatible with many memory card slot protocols other than those explicitly listed above without departing from the scope of the invention.

Electronic transaction card **104** includes electrical contacts **108** and stripe **106**. Electrical contacts **108** are contacts that provide a communications interface to communicate with add-on slot **110**. For example, electrical contacts **108** may provide connectivity compliant with a communications protocol for memory cards.

Stripe **106** represents an area on an external face of electronic transaction card **104** at which one or more time-varying magnetic fields emanate. For example, one or more time-varying magnetic fields may emanate from the location of stripe **106** to communicate with a magnetic card reader. In some embodiments, the time-varying magnetic field may emulate the time-varying magnetic field produced when a typical magnetic card is swiped through a magnetic card reader. For example, a time-varying magnetic field produced at stripe **106** may emulate the swipe of a credit card, a debit card, or any other card having a magnetic stripe compatible with a magnetic card reader.

In some embodiments of the present invention, stripe **106** may be a visible stripe on electronic transaction card **104**. When stripe **106** is visible, it may be used to indicate the location at which the time-varying magnetic field will emanate. In other embodiments of the present invention, stripe **106** may not be visible. For example, circuitry may be included within electronic transaction card **106** to produce the time-varying magnetic field and no visible indication may be present on an external face of electronic transaction card **104**.

As used herein, the term “stripe” generally refers to a location on an electronic transaction card, whether a visible stripe exists or not. In this description, the term “stripe” may also be used to refer to a visible marking on a face of an electronic transaction card. Further, a “stripe” may include the functionality provided by one or more time-varying magnetic fields that emanate from the card. For example, the term “stripe” may refer to multiple magnetic tracks, or multiple “stripes,” or emulation thereof.

4

Stripes, as described herein, may be compatible with one or more standards. A stripe may be compatible with a standard by being in compliance with the standard or by being partially in compliance with the standard. For example, stripe **106** may be compatible with an American National Standards Institute (ANSI) magnetic stripe standard, or an International Organization for Standardization (ISO) magnetic stripe standard. In addition, in some embodiments, a stripe may emulate more than one magnetic track, and the emulated tracks may or may not be offset from the location specified in a standard. For example, one or more wires may be utilized to generate time-varying magnetic fields compatible with a standard, and the wires may be located at or near stripe **106** in a location different than the magnetic track offset described in an associated standard.

As used herein, the term “transaction” refers to any beneficial use of an electronic transaction card. For example, any time stripe **106** emits a time-varying magnetic field to be read by a magnetic card reader or a hybrid smartcard reader, a transaction may take place. Transactions may include financial transactions, access control transactions, or any other type of transaction involving any of the electronic transaction card embodiments described herein. Further, as described in more detail below, in some embodiments of the present invention, transactions may utilize smartcard interfaces on electronic transaction cards in addition to, or in lieu of, stripes that emit time-varying magnetic fields.

In operation, intelligent electronic device **102** may program electronic transaction card **104** for use in a transaction involving stripe **106**. For example, intelligent electronic device **102** may program electronic transaction card **104** to operate as a credit card, a debit card, or the like. Electronic transaction card **104** may then be used with a magnetic stripe or smartcard based merchant point-of-sale terminal to effect a transaction. Also for example, intelligent electronic device **102** may program electronic transaction card **104** to operate in any other environment where stripe **106** may be beneficially utilized with a magnetic card reader.

FIG. 2A shows intelligent electronic device **202** and electronic transaction card **220**. Intelligent electronic device **202** includes add-on slot **210** to receive electronic transaction card **220**. Intelligent electronic device **202** is shown having add-on slot on one side, but this is not a limitation of the present invention. For example, add-on slot **210** may be located on top, bottom, or any other surface of intelligent electronic device **202**. Also for example, an add-on slot may be created by a clamshell design when the shell is closed. In these embodiments, each side of the clamshell may incorporate a portion of the add-on slot such that the add-on slot is “open” when the clamshell is open.

Electronic transaction card **220** may have any form factor compliant with add-on slot **210**. Electronic transaction card **220** is shown having a form factor with an aspect ratio different from that of electronic transaction card **104** (FIG. 1). Electronic transaction card **220** includes stripe **222** and may have electrical contacts to interface with add-on slot **210**. The electrical contacts may be on the back side of electronic transaction card **220**, recessed on an edge of electronic transaction card **220**, or on the front side of electronic transaction card **220**. In some embodiments, electronic transaction card **220** includes a “contactless” interface to add-on slot **210**. For example, electronic transaction card **220** may include an interface to add-on slot **210** that communicates using electric or magnetic fields, infrared (IR) light, or any other suitable communications mechanism.

Electronic transaction card **220** may have an area for imprinting. For example, as shown in FIG. 2A, electronic

5

transaction card **220** may have space for imprinting a brand (for a bank or otherwise), and a cardholder's name. Further, electronic transaction card **220** may include space for a cardholder's signature. Electronic transaction card **220** may include any other information, coded or uncoded, visible or nonvisible, without departing from the scope of the present invention.

Intelligent electronic device **202** may include a mechanism to allow intelligent electronic device **202** to communicate with a wired or wireless network. For example, intelligent electronic device **202** may include circuitry to communicate with a cellular phone network. Note that in these embodiments, intelligent electronic device **202** may or may not be a phone. For example, intelligent electronic device **202** may be a cellular telephone with an add-on slot for use with an electronic transaction card. Also for example, intelligent electronic device may be a non-telephonic device that has cellular network connectivity. Examples include personal digital assistants, and handheld devices dedicated to the use of electronic transaction cards. Further, intelligent electronic device **202** may be a non-telephonic device having wired or wireless connectivity to a network other than a cellular network, and in some embodiments, intelligent electronic device **202** may be a device without network connectivity. Examples include, but are not limited to: Blackberry devices available from Research in Motion (RIM), music players such as MP3 players, cameras, and the like.

In operation, intelligent electronic device **202** may program electronic transaction card to perform a transaction. In some embodiments, communications over a network may play a role in the transaction. For example, intelligent electronic device **202** may receive authorization for the transaction over a network. Also for example, intelligent electronic device **202** may program electronic transaction card **220** to perform a transaction, and then report the transaction to an entity using the network.

Electronic transaction card **220** may be utilized in financial transactions. For example, electronic transaction card **220** may be programmed to operate as a credit card or a stored value card. In these embodiments, electronic transaction card **220** may be programmed to emit one or more time-varying magnetic fields to emulate the swiping of a credit card or stored value card. In some of these embodiments, electronic transaction card **220** may use one number repeatedly, or may use a different number for each transaction. For example, electronic transaction card **220** may be programmed to have one number, similar to how a credit card uses the same number repeatedly. Also for example, electronic transaction card **220** may be programmed to use a different number for each transaction. These numbers are referred to herein as "single transaction account numbers" or "STANs."

Single transaction account numbers may be generated by the card issuer or locally by either an intelligent electronic device or an electronic transaction card. Generation of STANs may be accomplished in any of several ways. For example, when an electronic transaction card is issued, the cardholder may receive several pre-assigned single-use transaction numbers. The numbers may also have a pre-specified sequence. In some embodiments, this sequence may be known only to the issuing bank and the cardholder's intelligent electronic device and/or electronic transaction card. A card issuing bank may authorize payments based on the expected sequence of account numbers, and if out-of-sequence account numbers are used, then the issuing bank may consider that transaction as a potentially fraudulent

6

transaction. The issuing bank may also use this feature to track the merchant involved in the potentially fraudulent transaction.

According to another example, a pre-assigned sequence of STANs may be reset to the original starting number on the list depending on user input or other triggers. In addition, the list of numbers may be periodically downloaded via a cellular phone network or other network connectivity.

FIG. 2B shows intelligent electronic device **230** and electronic transaction card **240**. Intelligent electronic device **230** is an example of a "wearable" device that is capable of communicating with an electronic transaction card. For example, intelligent electronic device **230** is shown having the form factor of a wristwatch. Some embodiments of the present invention may have other wearable form factors. For example, a wearable intelligent electronic device may be worn in such a manner that it contacts human skin, or it may be worn on clothing. Any wearable intelligent electronic device may be employed without departing from the scope of the present invention. Further, intelligent electronic device **230** may have any of the capabilities described herein.

Intelligent electronic device **230** may include an add-on slot to accept electronic transaction card **230**. The add-on slot may be any of the add-on slot embodiments described herein. Electronic transaction card **240** may be any electronic transaction card. For example, electronic transaction card **240** may be any electronic transaction card embodiment described herein.

FIG. 3 shows a block diagram of an electronic transaction card. Electronic transaction card **300** is an electronic transaction card capable of communicating with an intelligent electronic device, and capable of communicating with a magnetic card reader. For example, electronic transaction card **300** may be electronic transaction card **104** (FIG. 1) or electronic transaction card **220** (FIG. 2A).

Electronic transaction card **300** includes electrical contacts **302**, intelligent electronic device (IED) interface **304**, nonvolatile memory **306**, processing device **308**, volatile memory **310**, magnetic field producing circuits **312**, swipe sensor **314**, and stripe **320**.

Electrical contacts **302** correspond to electrical contacts **108** (FIG. 1). IED interface **304** is coupled to electrical contacts **302** to provide a communications interface between electronic transaction card **300** and an intelligent electronic device. For example, IED interface **304** may be an interface compatible with an add-on slot such as add-on slot **110** (FIG. 1) or add-on slot **210** (FIG. 2A).

Magnetic field producing circuit **312** includes one or more circuits to produce time-varying magnetic fields at or near the location of stripe **320**. For example, one or more current carrying conductors may be excited to produce a magnetic field, and the current may be varied in amplitude and reversed in polarity to cause the magnetic field to be time-varying. In some embodiments, the number of magnetic field producing circuits corresponds to the number of tracks being emulated for stripe **320**. For example, stripe **320** may emulate two, three, four, or more magnetic tracks on a magnetic card such as a credit card. In these embodiments, electronic transaction card **300** may include two, three, four, or more magnetic field producing circuits **312**. Magnetic field producing circuits **312** may also include circuits to allow control of the time-varying magnetic field. For example, magnetic field producing circuits **312** may include voltage drivers, current drivers, registers to hold digital data, sequential circuits to translate the digital data to magnetic fields, and the like.

Swipe sensor **314** senses when electronic transaction card **300** has been swiped in a magnetic card reader, and provides a swipe indication to processing device **308**. The swipe sensor may be a mechanical switch, an electronic switch, or any other type of suitable switch. For example, a mechanical switch may get pressed when electronic transaction card **300** is swiped. Also for example, an electrical sensor may include two or more contacts (not shown) that get shorted when swiped past a metal head within a card reader. Further, a Hall effect sensor or light-based sensor may be utilized. The present invention is not limited by the type of swipe sensor utilized. In some embodiments, swipe sensor **314** is omitted.

Processing device **308** represents a processor capable of communicating with the other blocks shown in electronic transaction card **300**. For example, processing device **308** may be a microprocessor, a digital signal processor (DSP), a microcontroller, or the like. Further, processing device **308** may be formed from state machines or other sequential logic. In operation, processing device **308** may read instructions from volatile memory **310** and/or nonvolatile memory **306** and perform actions in response thereto. For example, processing device **308** may execute program instructions that influence communications between electronic transaction card **300** and an intelligent electronic device, or between electronic transaction card **300** and a magnetic card reader.

Volatile memory **310** represents memory that may lose its state when power is removed from electronic transaction card **300**. For example, volatile memory **310** may be static random access memory (SRAM). Volatile memory **308** may be utilized by processing device **308** when executing programs. For example, a program may be copied into volatile memory **308** prior to execution. Also for example, processing device **308** may use volatile memory **308** to store data during the execution of a program.

Nonvolatile memory **306** represents memory that does not lose its state when power is removed from electronic transaction card **300**. Nonvolatile memory **306** may be any suitable type of memory such as Flash memory with floating gate transistor memory cells. Examples include NOR Flash memory, NAND Flash memory, and multibit/cell Flash memory.

Nonvolatile memory **306** may hold program instructions that are executable by processing device **308**. For example, prior to being sold, a manufacturer or distributor may program nonvolatile memory **306** with program information to influence the operation of electronic transaction card **300**. Also for example, an intelligent electronic device may provide program information to electronic transaction card **300** through IED interface **304**.

Nonvolatile memory **306** may also hold program instructions that are executable by a processing device other than processing device **308**. For example, a manufacturer, distributor, reseller, or other participant in the chain of commerce may program nonvolatile memory **306** with program information to be transferred to an intelligent electronic device. Information to be transferred may include device drivers, application software, or the like.

Electronic transaction card **300** may include one or more power sources (not shown). For example, electronic transaction card **300** may include a battery or a capacitor such as a supercapacitor. In some embodiments, a rechargeable battery may be included. The rechargeable battery may accept a charge from an add-on slot in an intelligent electronic device. In some embodiments, a capacitor may accept a charge from an intelligent electronic device. The capacitor may provide power to electronic transaction card **300** for

enough time to perform a transaction. Further, the capacitor may be sized to ensure that a transaction may only be performed during a limited time period after removing the electronic transaction card from an add-on slot, thereby ensuring that a stolen card may not be used repeatedly without the cardholder's consent. Also in some embodiments, electronic transaction card **300** may be programmed to go dormant if a transaction is not performed within a limited time period after removing the card from an intelligent electronic device.

Electronic transaction card **300** may include one or more integrated circuits. For example, processing device **308** may be on one integrated circuit die, and the memories may be on another integrated circuit die. In some embodiments, all active devices are included on a single integrated circuit die. In some embodiments, various integrated circuit dice are mounted on a common substrate to provide a high level of integration using separate dice. Any amount of circuit integration may be practiced without departing from the scope of the present invention.

Electronic transaction card **300** has dimensions "a" and "b." In some embodiments of the present invention, stripe **320** has a length that is substantially equal to a, and in some embodiments, stripe **320** has a length less than a. Further, in some embodiments, a is less than the stripe length of a standard credit card (approximately three and three eighths inches), and in some embodiments, a is much less than the stripe length of a standard credit card. For example, in some embodiments, a is less than 75% the length of a standard credit card stripe. Further, in some embodiments, a is less than 50% the length of a standard credit card stripe. In still further embodiments, a is less than 25% the length of a standard credit card stripe.

In some embodiments, dimensions a and b are substantially equal to the dimensions of a memory card. For example, dimensions a and b may conform to the dimensions of an MMC memory card, a Memory Stick PRO DUO memory card, or other memory card. Further, in some embodiments, electronic transaction card **300** has a thickness compatible with a magnetic card reader.

FIG. 4 shows an electronic transaction card and a card reader. Electronic transaction card **410** is a card having a stripe compatible with a magnetic card reader. For example, electronic transaction card **410** may be electronic transaction card **104** (FIG. 1), electronic transaction card **220** (FIG. 2A), electronic transaction card **300** (FIG. 3), or any other electronic transaction card described herein. Magnetic card reader **420** is a card reader compatible with magnetic cards. For example, magnetic card reader **420** may operate as part of a merchant point-of-sale terminal, an access control device, or the like. When a magnetic card is swiped through magnetic card reader **420**, one or more time-varying magnetic fields are produced relative to the location of a magnetic read head (not shown) in magnetic card reader **420**.

In the operation depicted in FIG. 4, electronic transaction card **410** is swiped through magnetic card reader **420**. During the swiping operation, electronic transaction card **420** produces one or more time-varying magnetic fields to emulate the swiping of a magnetic card. For example, a swipe sensor within electronic transaction card **410** may detect the swiping action depicted in FIG. 4, and a magnetic field producing circuit may generate one or more time-varying magnetic fields as electronic transaction card **410** passes by a magnetic read head in magnetic card reader **420**.

FIG. 5 shows an intelligent electronic device, an electronic transaction card, and a magnetic card reader. Electronic transaction card **510** is shown being swiped through

9

magnetic card reader **520** while attached to intelligent electronic device **500**. The operation depicted in FIG. **5** represents a transaction occurring while electronic transaction card **510** is coupled to an add-on slot of intelligent electronic device **500**.

FIG. **6** shows an adapter for use with an electronic transaction card. Adapter **600** includes a body portion having dimensions “w” and “l”, and a receiving portion shown at **610**. Adapter **600** is useful to receive an electronic transaction card at receiving portion **610** to provide a larger card having the functionality of an electronic transaction card. For example, in some embodiments of the present invention, dimensions w and/or are compatible with swallow-type magnetic card readers, and a combination of adapter **600** and an electronic transaction card may be compatible with such readers.

Receiving portion **610** may include an interface compatible with a connector on an electronic transaction card. For example, an electronic transaction card may have an interface that is compatible with both an add-on slot of an electronic transaction device and receiving portion **610** of adapter **600**.

FIG. **7** shows adapter **600** having an electronic transaction card **710** coupled thereto. Electronic transaction card **710** includes a stripe capable of emitting one or more time-varying magnetic fields as described above. The combination of electronic transaction card **710** and adapter **600** allow the functionality of electronic transaction card **710** to be useful in the larger form factor of adapter **600**.

In some embodiments, adapter **600** includes active or passive circuitry in support of the operation of electronic transaction card **710**. For example, adapter **600** may include electrical contacts, a battery, an integrated circuit, or other circuits. Also for example, adapter **600** may include one or more swipe sensors to provide a swiping indication to electronic transaction card **710**.

FIG. **8** shows an adapter having a smartcard interface **810**. In embodiments represented by FIG. **8**, an adapter may be utilized to perform a transaction involving a smartcard reader while utilizing an electronic transaction card. For example, an electronic transaction card may be coupled to adapter **800** at receiving portion **820**, and the electronic transaction card may provide data useful for a smartcard transaction.

FIG. **9** shows an electronic transaction card having a smartcard interface. Electronic transaction card **900** includes electrical contacts **908** and **910**. Electrical contacts **908** are similar to electrical contacts **108** (FIG. **1**). For example, electrical contacts **908** may be compatible with an add-on slot of an intelligent electronic device such as intelligent electronic device **102** (FIG. **1**). Electrical contacts **910** are arranged to provide the communications interface to a smartcard reader.

In some embodiments, electronic transaction card **900** includes a smartcard interface as well as a stripe to produce the time-varying magnetic field. For example, as shown in FIG. **10**, the backside of electronic transaction card **900** may include stripe **1010**. The various electronic transaction cards described herein may include a stripe, a smartcard interface, or a combination thereof.

FIG. **11** shows an adapter in combination with an electronic transaction card. Adapter **1100** is shown having electronic transaction card **900** coupled in a recessed portion on a side having dimension w. In some embodiments, this configuration places electrical contacts **910** at a location expected by smartcard readers.

10

FIG. **12** shows an adapter having an aperture to receive an electronic transaction card. Adapter **1200** includes aperture **1210** to receive an electronic transaction card. In some embodiments, aperture **1210** passes completely through adapter **1200**, and in other embodiments, aperture **1210** is a recessed portion on the face of adapter **1200**. Adapter **1200** may receive electronic transaction cards having a stripe, a smartcard interface, or a combination of the two.

FIG. **13** shows an adapter having a body portion **1300**, a recessed portion **1310**, and stripe **1320**. Recessed portion **1310** may receive an electronic transaction card as described above with respect to FIGS. **6-7**. Further, stripe **1320** may be utilized to communicate with a magnetic card reader. For example, adapter **1300** may include a magnetic field producing circuit such as magnetic field producing circuit **312** (FIG. **3**) to produce a time-varying magnetic field. In operation, an electronic transaction card may be coupled to adapter **1300** at recessed portion **1310**, and provide transaction information to be used by stripe **1320** for a transaction with a magnetic card reader. In some embodiments, an electronic transaction card having neither a stripe nor a smartcard interface may be coupled to adapter **1300** at recessed portion **1310** to effect a transaction using stripe **1320**.

The various adapters shown in the previous figures may have recessed portions, apertures, or stripes anywhere on the adapter without departing from the scope of the present invention. For example, in some embodiments, a recessed portion may be on the side of the adapter having a smaller dimension, and in other embodiments a recessed portion may be on the side of the adapter having a larger dimension. Also for example, in some embodiments, a stripe may be on the side of the adapter having a smaller dimension, and in other embodiments a stripe may be on the side of the adapter having a larger dimension.

FIG. **14** shows an electronic transaction card. Electronic transaction card **1400** includes stripe **1410** and add-on slot compatible portion **1402**. Add-on slot compatible portion **1402** includes electrical contacts **1408** to communicate with an add-on slot in an intelligent electronic device. For example, add-on slot compatible portion **1402** may be physically and electrically compatible with add-on slot **110** (FIG. **1**) or add-on slot **210** (FIG. **2A**).

Electronic transaction card **1400** may include any of the circuits, features, or functionality described herein. For example, electronic transaction card **1400** may include magnetic field producing circuits, swipe sensors, processing devices, volatile and nonvolatile memory, various interfaces, and electrical contacts.

Electronic transaction card **1400** is shown having stripe **1410** along an edge having dimension “l.” In some embodiments, electronic transaction card **1400** may have stripe **1410** along an edge other than that shown in FIG. **14**.

In operation, electronic transaction card **1400** may be left coupled to an electronic transaction device when being swiped through a magnetic card reader, similar to the operation shown in FIG. **5**. Further, electronic transaction card **1400** may be removed from an intelligent electronic device prior to being swept through a magnetic card reader, similar to the operation shown in FIG. **4**.

FIG. **15** shows an electronic transaction card and an adapter in combination. The combination of electronic transaction card **1400** and adapter **1500** form a card having dimensions “w” and “l” as described above with reference to previous figures. The resulting card may be suitable for swallow-type magnetic card readers.

11

FIG. 16 shows a combination electronic transaction card and adapter 1610 being inserted into a swallow-type magnetic card reader. As shown in FIG. 16, the swallow-type magnetic card reader is part of an automated teller machine (ATM), but this is not a limitation of the present invention. For example, the swallow-type reader may be part of a point-of-sale device, an access entry device, or any other type of device capable of incorporating a swallow-type magnetic card reader.

FIG. 17 shows a combination electronic transaction card and adapter being swiped through a magnetic card reader. Adapter 1710 and electronic transaction card 1720 are shown being swiped through magnetic card reader 1730. Electronic transaction card 1720 may be any of the electronic transaction card embodiments described herein. For example, electronic transaction card 1720 may include a stripe, a smartcard interface, or a combination of the two. Although adapter 1710 is shown as an adapter having a recessed portion on one side, the combination adapter/card in FIG. 17 represents any of the adapter/card combinations described herein. For example, adapter 1710 may be any of adapters 600 (FIGS. 6, 7), adapter 800 (FIG. 8), adapter 1100 (FIG. 11), adapter 1200 (FIG. 12), adapter 1300 (FIG. 13), or adapter 1500 (FIG. 15).

FIG. 18 shows a financial transaction card. Financial transaction card 1800 includes stripe 1802, financial card circuits 1804, memory card emulation circuitry 1806, and memory card compatible interface 1808. Financial transaction card 1800 is an example of a financial card that might be issued by a bank or other financial institution. For example, financial transaction card 1800 might be a debit card, a credit card, a stored value card, or other card issued for the purposes of financial transactions.

Financial card circuits 1804 interact with stripe 1802 to produce time-varying magnetic fields compatible with a magnetic card reader. For example, financial card circuits 1804 and stripe 1802 may provide financial transaction data to a point-of-sale terminal. Financial transaction card 1800 also includes memory card emulation circuitry 1806 to emulate the operation of a memory card. The combination of memory card emulation circuitry 1806 and memory card compatible interface 1808 allow financial transaction card 1800 to perform as a memory card. For example, memory card compatible interface 1808 may be compatible with a memory card interface in an add-on slot of an intelligent electronic device.

FIG. 19 shows a memory card. Memory card 1900 includes memory card compatible interface 1930, memory card circuits 1920, financial card emulation circuitry 1910, and stripe 1902. Memory card 1900 is an example of a card that may be fabricated and sold by a memory card manufacturer or a manufacturer that is in the business of selling electronic peripheral devices. By including financial card emulation circuitry 1910 and stripe 1902 in memory card 1900, the manufacturer of memory card 1900 may add features desired by consumers. For example, the combination of stripe 1902 and financial card emulation circuitry 1910 may emulate the operation of a financial card such as a credit card, debit card, stored value card, or the like.

FIG. 20 shows a block diagram of a combination memory card and electronic transaction card. Card 2000 includes memory 2010, processing element 2020, magnetic/smartcard circuitry 2030, card reader interface 2040, memory card circuitry 2050, and memory card slot compatible interface 2060. Processing element 2020 may be any processing element suitable to communicate with memory 2010 and the other blocks shown in FIG. 20. Magnetic/smartcard circuitry

12

2030 may include circuits to produce time-varying magnetic fields or signals compatible with a smart card reader. Card reader interface 2040 may include a stripe as described above, or may include electrical contacts compatible with a smartcard reader. Memory card circuitry 2050 may be any type of memory circuitry accessible by an intelligent electronic device. The intelligent electronic device may access memory card circuitry 2050 through memory card slot compatible interface 2060.

Memory 2010 is shown having card software 2012 and application software 2014. In some embodiments, card 2000 is sold or distributed having both card software 2012 and application software 2014 in memory 2010. For example, memory 2010 may be nonvolatile memory having card software 2012 for execution by processing element 2020. Also for example, memory 2010 may have application software 2014 meant to be installed on a device other than card 2000. Application software 2014 may include drivers, user interface software, single transaction account number (STAN) generation software, or any other software that may be installed on a device other than card 2000.

Application software 2014 may operate in any of multiple languages on multiple operating systems. For example, application software 2014 may provide a user interface in any regional language. Also for example, application software 2014 may run on any operating system (OS).

FIG. 21 shows a block diagram of how card 2000 (FIG. 20) may be utilized. A card issuer 2110 may issue card 2000 to a cardholder 2130. As issued by card issuer 2110, card 2000 may include card software and application software as shown in FIG. 21. Cardholder 2130 may couple card 2000 with intelligent electronic device 2140 and install application software on the intelligent electronic device. For example, intelligent electronic device 2140 may be a mobile phone capable of executing application software, and card 2000 may supply application software to be installed on the mobile phone. Also for example, intelligent electronic device 2140 may be a non-telephonic device such as a personal digital assistant (PDA), or other dedicated hardware, capable of receiving card 2000 in an add-on slot.

FIG. 22 shows a block diagram of a combination memory card and electronic transaction card. Card 2200 includes processing element 2020, magnetic/smartcard circuitry 2030, card reader interface 2040, memory card circuitry 2050, and memory card slot compatible interface 2060, all of which are described above with reference to FIG. 20. Card 2200 also includes nonvolatile memory 2210 and volatile memory 2220. As shown in FIG. 22, nonvolatile memory 2210 includes card software 2212 to be executed by processing element 2020. Also as shown in FIG. 22, card 2200 includes volatile memory 2220 having financial transaction data 2222 held therein. Financial transaction data 2222 may be programmed into volatile memory 2220 by processing element 2020 in response to communications from an intelligent electronic device coupled to memory card slot compatible interface 2060. For example, a mobile phone executing single transaction account number generation software may provide a single transaction account number as financial transaction data that gets stored in volatile memory 2220 in preparation for a transaction. In other embodiments, financial transaction data 2222 represents two, three, four, or more time-varying magnetic fields to be generated by the combination of magnetic/smartcard circuitry 2030 and card reader interface 2040.

FIG. 23 shows a block diagram of a phone and a card. Phone 2310 may be a cellular telephone, and card 2350 may be any of the electronic transaction card embodiments

13

described herein. Phone **2310** includes display **2312**, processor **2314**, single transaction account number (STAN) generation software **2316**, and authentication software **2318**. Card **2350** includes processor **2352**, card software **2354**, financial transaction data **2356**, and point-of-sale (POS) interface **2358**.

Single transaction account number generation software **2316** may be installed on the phone **2310** when card **2350** is inserted in a memory slot. For example, referring now back to FIGS. **20** and **21**, STAN generation software **2316** may correspond to application software **2014**. Authentication software **2318** may only allow authorized users access to phone **2310** and/or card **2350**.

In operation, a user interacting with phone **2310** may gain access to features by satisfying requirements of authentication software **2318**. Using STAN generation software **2316**, a user may generate financial transaction data **2356** which is held on card **2350** in preparation for a transaction. Card **2350** may then interact with a card reader using point-of-sale interface **2358** to effect a transaction. This transaction may be effected with card **2350** coupled to phone **2310** or decoupled from phone **2310**. Further, the transaction using card **2350** may be effected while card **2350** is coupled to any of the adapter embodiments described herein.

The following paragraphs provide further disclosure of various invention embodiments. Each embodiment is fully defined by the recitation of the corresponding paragraph, and no other elements are to be considered essential for that particular embodiment. The embodiments include:

- A. An apparatus comprising:
 - a stripe to communicate with a magnetic card reader; and
 - an interface to communicate with an intelligent electronic device;
 - wherein the apparatus has dimensions smaller than a credit card.
- A1. The apparatus of A wherein the stripe includes circuitry to produce at least one time-varying magnetic field.
- A2. The apparatus of A wherein the interface is compatible with an add-on slot in the intelligent electronic device.
- A3. The apparatus of A2 wherein the interface comprises a memory card interface.
- A4. The apparatus of A further comprising a processing element coupled to the interface and to the stripe.
- A5. The apparatus of A4 further comprising a memory element to hold programming information for the stripe.
- A6. The apparatus of A4 further comprising an embedded swipe sensor to sense when the stripe is swiped through a magnetic card reader.
- A7. The apparatus of A further comprising nonvolatile memory accessible by the intelligent electronic device.
- B. A financial card comprising:
 - a point-of-sale compatible electronic transaction stripe;
 - a memory card compatible interface; and
 - memory card emulation circuitry coupled to the memory card compatible interface.
- C. A memory card comprising:
 - a memory card compatible interface;
 - a point-of-sale compatible electronic transaction stripe;
 - and
 - financial card emulation circuitry coupled to the point-of-sale compatible electronic transaction stripe.
- D. A financial card apparatus comprising:
 - a point-of-sale compatible portion having a stripe to
 - communicate with a point-of-sale transaction device;
 - and

14

a memory card compatible portion having at least one electrical contact to communicate with a memory card slot in an intelligent electronic device.

- E. A memory card comprising:
 - a memory card interface operable to couple the memory card to an intelligent electronic device;
 - a nonvolatile memory device accessible through the memory card interface; and
 - a stripe operable to communicate with a magnetic card reader.
- F. A memory card comprising:
 - a memory card slot interface; and
 - circuitry for producing a time-varying magnetic field compatible with a magnetic card reader.
- F1. The memory card of F wherein the circuitry is configured to produce a plurality of time-varying magnetic fields compatible with a point-of-sale transaction device.
- G. An apparatus comprising:
 - means for communicating through a memory card slot in an intelligent electronic device;
 - means for producing at least one time-varying magnetic field to represent financial transaction data; and
 - means for storing the financial transaction data.
- H. A card comprising:
 - a memory card compatible interface;
 - a smartcard compatible interface; and
 - a stripe to produce at least one time-varying magnetic field compatible with a magnetic card reader.
- I. A memory card compatible with a memory card slot in a mobile phone, the memory card including nonvolatile memory accessible by the mobile phone, a point-of-sale interface to communicate with a point-of-sale terminal, and volatile memory to hold financial transaction data.
- I1. The memory card of I wherein the point-of-sale interface comprises circuitry to produce at least one time-varying magnetic field.
- I2. The memory card of I1 further including a processing device coupled to the nonvolatile memory, volatile memory, and point-of-sale interface.
- J. An electronic financial transaction device having a thickness compatible with a point-of-sale card reader, a width less than a credit card width, a length less than a credit card length, an electronically programmable stripe situated along the length, and at least one electrical contact to provide an interface to an intelligent electronic device.
- J1. The electronic financial transaction device of J wherein the at least one electrical contact comprises a memory card interface compatible with a memory card slot in the intelligent electronic device.
- J2. The electronic financial transaction device of J wherein the electronically programmable stripe includes a circuit to emulate a magnetic stripe in a credit card.
- J3. The electronic financial transaction device of J2 further comprising a swipe sensor to detect when the electronic financial device is swiped through a point-of-sale terminal.
- K. A card comprising:
 - means for storing financial transaction data;
 - means for communicating with a memory card slot in an intelligent electronic device; and
 - means for creating a time-varying magnetic field that represents the financial transaction data.
- K1. The card of K wherein the means for storing financial transaction data comprises volatile memory.
- K2. The card of K wherein the financial transaction data comprises a single transaction account number.

15

- K3. The card of K further comprising a processing device coupled to read the financial transaction data and influence the operation of the means for creating a time-varying magnetic field.
- L. An adapter for use with any of A-K, the adapter comprising: 5
 a body portion having exterior dimensions larger than dimensions of A-G; and
 a receiving portion to receive any of A-G, wherein the receiving portion is located on the body portion to expose any of A-G for use in magnetic card reader transactions. 10
- M. An apparatus comprising a body portion with dimensions compatible with a swallow-type magnetic card reader, wherein the body portion includes a memory card compatible area to receive a memory card with magnetic stripe functionality. 15
- M1. The apparatus of M further comprising a smartcard interface.
- M2. The apparatus of M further comprising at least one electrical component coupled to the memory card compatible area portion to interface to the memory card. 20
- M3. The apparatus of M wherein the memory card compatible area comprises a recessed portion of at least one side of the apparatus. 25
- M4. The apparatus of M wherein memory card compatible area comprises at least one metallic contact on a periphery of an aperture in the apparatus.
- N. A financial card to be used with a magnetic card reader at a point-of-sale, the financial card including a memory card interface to allow the financial card to be inserted in a memory card slot of a mobile phone, and including a stripe compatible with the magnetic card reader, wherein the stripe is shorter than a magnetic credit card stripe. 30
- O. A card compatible with a magnetic card reader and compatible with a memory slot in an intelligent electronic device, the card including software to be installed on the intelligent electronic device. 35
- O1. The card of O wherein the software includes a module for single transaction account number generation. 40
- O2. The card of O1 wherein the software is configured to run on a mobile phone.
- O3. The card of O wherein the card comprises:
 a memory slot compatible portion; and
 a magnetic card reader compatible portion. 45
- O4. The card of O3 wherein the magnetic card reader compatible portion comprises circuitry to produce at least one time-varying magnetic field for use in a financial transaction.
- P. A card comprising: 50
 a memory card interface mechanically compatible with a memory card slot in an intelligent electronic device;
 a processing device coupled to the memory card interface; and
 circuitry to produce a time-varying magnetic field compatible with a point-of-sale device. 55
- Q. A card comprising:
 a memory card interface electrically compatible with a memory card slot in an intelligent electronic device;
 a processing device coupled to the memory card interface; and
 circuitry to produce a time-varying magnetic field compatible with a point-of-sale device. 60
- Q1. Any of the cards of P-Q further comprising nonvolatile memory exposed through the memory card interface. 65
- Q2. Any of the cards of P-Q further comprising volatile memory to hold financial transaction information.

16

- Q3. Any of the cards of P-Q further comprising a software component that when executed by the processing device causes the circuitry to produce at least one time-varying magnetic field representing the financial transaction information.
- Q4. Any of the cards of P-Q further comprising a visible stripe at which the at least one time-varying magnetic field emanates.
- Q5. Any of the cards of P-Q further comprising a battery.
- Q6. Any of the cards of P-Q further comprising a capacitor to provide power to the card.
- Q7. The card of Q wherein the card has a size substantially equivalent to a credit card.
- R. A credit card sized adapter to receive any of the cards of P-Q. 15
- R1. The adapter of R wherein the credit card sized adapter includes a smartcard interface.
- R2. The adapter of R wherein the adapter includes a first edge having a width and a second edge having a length, wherein the second edge includes a recessed portion to accept the card.
- R3. The adapter of R wherein the credit card sized adapter includes a first edge having a width and a second edge having a length, wherein the first edge includes a recessed portion to accept the card. 25
- S. A combination financial card and memory card apparatus comprising:
 electrical contacts to provide an interface to a mobile phone;
 a transaction stripe to produce at least one time-varying magnetic field representing transaction information;
 a processing device; and
 a software component to receive the transaction information from the mobile phone;
 wherein the electrical contacts are provided on a physical portion of the combination financial card and memory card apparatus having dimensions compatible with a memory card slot. 30
- S1. The combination financial card and memory card apparatus of S further comprises an application software component to be installed on the mobile phone.
- T. In combination:
 a memory card having a transaction stripe compatible with a magnetic card reader; and
 a credit card sized adapter to receive the memory card and to expose the transaction stripe for use in magnetic card reader transactions. 45
- U. In combination:
 a memory card having an interface compatible with a memory card slot in a mobile phone and a smartcard interface; and
 a credit card sized adapter to receive the memory card and to expose the smartcard interface for use in smartcard transactions. 50
- V. A financial transaction system comprising:
 a mobile phone having a memory card slot;
 a memory card compatible with the memory card slot, wherein the memory card includes circuitry to transmit financial transaction data to a point-of-sale device; and
 a software component to produce single transaction account numbers for use as financial transaction data. 55
- W. A system comprising:
 a wearable intelligent electronic device having a card slot; and
 a card comprising a card slot interface and circuitry for producing a time-varying magnetic field compatible with a magnetic card reader. 65

17

Although the present invention has been described in conjunction with certain embodiments, it is to be understood that modifications and variations may be resorted to without departing from the spirit and scope of the invention as those skilled in the art readily understand. Such modifications and variations are considered to be within the scope of the invention and the appended claims.

What is claimed is:

1. A mobile phone comprising:
 - a memory to hold transaction data for use in a plurality of transactions;
 - a current carrying conductor capable of producing a time-varying magnetic field that represents the transaction data in the plurality of transactions;
 - a network interface for connecting the mobile phone to a network, wherein one or more parts of the transaction data are downloadable to the mobile phone via the network;
 - a driver to excite the current carrying conductor; and
 - a processor coupled to control the driver.
2. The mobile phone of claim 1 wherein the time-varying magnetic field represents a point-of-sale transaction.
3. The mobile phone of claim 1 wherein the time-varying magnetic field represents an access transaction.
4. The mobile phone of claim 1 wherein the time-varying magnetic field represents a credit card transaction.
5. The mobile phone of claim 1 wherein the time-varying magnetic field emulates a swipe of a magnetic card.
6. The mobile phone of claim 1 wherein the driver comprises a current driver.
7. The mobile phone of claim 1 wherein the network is one of a cellular network or a wireless local area network.
8. The mobile phone of claim 1 wherein downloaded transaction data is valid for a limited number of transactions and the one or more parts of the transaction data is downloaded periodically.
9. The mobile phone of claim 1, wherein the transaction data includes a transaction number used for each transaction of the plurality of transactions.
10. A mobile phone comprising:
 - a memory to hold transaction data for use in a plurality of transactions;
 - a conductor that when excited by a reversing polarity current produces a time-varying magnetic field that represents the transaction data in the plurality of transactions;
 - a network interface for connecting the mobile phone to a network, wherein one or more parts of the transaction data are downloadable to the mobile phone via the network;
 - a driver to excite the conductor; and
 - a processor coupled to control the driver.

18

11. The mobile phone of claim 10 wherein the time-varying magnetic field represents a point-of-sale transaction.

12. The mobile phone of claim 10 wherein the time-varying magnetic field represents an access transaction.

13. The mobile phone of claim 10 wherein the time-varying magnetic field represents a credit card transaction.

14. The mobile phone of claim 10 wherein the time-varying magnetic field emulates a swipe of a magnetic card.

15. The mobile phone of claim 10 wherein the driver comprises a current driver.

16. The mobile phone of claim 10 wherein the network is one of a cellular network or a wireless local area network.

17. The mobile phone of claim 10 wherein downloaded transaction data is valid for a limited number of transactions and the one or more parts of the transaction data is downloaded periodically.

18. The mobile phone of claim 10, wherein the transaction data includes a transaction number used for each transaction of the plurality of transactions.

19. A mobile phone comprising:
 - a memory to hold transaction data for use in a plurality of transactions;
 - a conductor that when excited by a reversing polarity current that varies in amplitude produces a time-varying magnetic field that represents the transaction data in the plurality of transactions;
 - a network interface for connecting the mobile phone to a network, wherein one or more parts of the transaction data are downloadable to the mobile phone via the network;
 - a driver to excite the conductor; and
 - a processor coupled to control the driver.

20. The mobile phone of claim 19 wherein the time-varying magnetic field represents a point-of-sale transaction.

21. The mobile phone of claim 19 wherein the time-varying magnetic field represents an access transaction.

22. The mobile phone of claim 19 wherein the time-varying magnetic field represents a credit card transaction.

23. The mobile phone of claim 19 wherein the time-varying magnetic field emulates a swipe of a magnetic card.

24. The mobile phone of claim 19 wherein the driver comprises a current driver.

25. The mobile phone of claim 19 wherein the network is one of a cellular network or a wireless local area network.

26. The mobile phone of claim 19 wherein downloaded transaction data is valid for a limited number of transactions and the one or more parts of the transaction data is downloaded periodically.

27. The mobile phone of claim 19, wherein the transaction data includes a transaction number used for each transaction of the plurality of transactions.

* * * * *