

UNITED STATES PATENT AND TRADEMARK OFFICE

BEFORE THE PATENT TRIAL AND APPEAL BOARD

MOBILEYE GLOBAL, INC,

PETITIONER,

v.

MANDLI COMMUNICATIONS, INC.,

PATENT OWNER.

Case No. IPR2024-01111

U.S. Patent No. 9,671,328

Declaration of Kelley M. Hayes Greenhill

I, Kelley M. Hayes Greenhill, state and declare as follows:

I. Introduction

1. I have prepared this Declaration in connection with the Petition for *Inter Partes* Review of U.S. Patent No. 9,671,328, which I understand will be filed concurrently with this Declaration.

2. I am currently the Director of the Research & Information Services team at Finnegan, Henderson, Farabow, Garrett & Dunner, LLP, located at 901 New York Avenue, NW, Washington, DC 20001-4413.

3. I am over eighteen years of age, and I am competent to make this Declaration. I make this Declaration based on my own personal knowledge and my knowledge of library science practices.

4. I earned a Master of Science in Library Science from the Catholic University of America in 1995, and a Bachelor of Arts in Political Science from Duquesne University in 1989. I have worked as a librarian for over twenty-five years. I have been employed at Finnegan, Henderson, Farabow, Garrett & Dunner, LLP since 2019. Before that, from 1995 to 2015, I was employed in the Library Department of Sterne, Kessler, Goldstein & Fox, PLLC. And from 2015 to 2019, I was employed in the Knowledge and Research Service Group (formerly, Information Research Service) at Northrop Grumman Corporation.

5. I am a member of the American Association of Law Libraries.

II. Standard Library Practices for Receiving, Cataloging, and Making Materials Publicly Available

6. I have knowledge of and experience with standard library practices regarding the receipt, cataloging, and making materials available to the public. I have knowledge of and experience with the Machine-Readable Cataloging (MARC) system, an industry-wide standard that libraries use to catalog materials. I also have knowledge of and experience with OCLC (previously called Online Computer Library Center, Inc.) and OCLC Control Numbers, which are unique accession numbers assigned by the OCLC system when a bibliographic record is catalogued and made available to the public through WorldCat. OCLC control numbers are often used by the public to search for specific records within WorldCat, which is an online database of 559,887,458 bibliographic records and 3,446,566,579 holdings from libraries throughout the world as of April 2024.¹

7. The MARC record system was developed during the 1960s to standardize bibliographic catalog records so they could be read by computers and shared among libraries. By the mid-1970s, MARC had become the international standard for cataloging bibliographic materials and is still used today. Many libraries provide public access to their MARC records via the Internet and/or their electronic cataloging systems at the libraries. In a MARC record, each field provides specific

¹ *Inside WorldCat*, WorldCat, <https://www.oclc.org/en/worldcat/inside-worldcat.html> (last visited June 17, 2024).

information about the cataloged item, including how materials are held and when they were made available to the public.

8. The MARC record system uses specific three-digit numeric codes (i.e., field tags) from 001-999 to identify each field in a catalog record. For example, field tag 008 provides the six-digit date the item was received and catalogued (i.e., the date entered on file at the library). The first six characters of field tag 008 are in the “YYMMDD” format. Descriptions for all of the character positions of field tag 008 are outlined here on the Library of Congress website. *See 008 - All Materials (NR)*, The Library of Congress, <https://www.loc.gov/marc/bibliographic/bd008a.html> (last visited Jun. 17, 2024).

9. MARC field tags relevant to this Declaration are explained below. MARC field tag 245 identifies the item’s full title statement for the work and field tag 310 denotes the current stated publication frequency of either an item or an update to an item. Field tag 500 general information for which a specialized note field (i.e., a specific 5XX field) has not been defined as in this case subsequent publishers.

10. Based on standard library practice, when a library receives an item, it stamps (and/or labels) the item with the library name, barcode, often with a date that is within a few days of receipt. Then, the library will catalog the item.

11. Normally, after an item is cataloged, the public may access the item by

searching a library catalog, browsing the library shelves, and either requesting or electronically accessing the item from the library. Standard library practice is to make the item available to the public within a few days of cataloging it.

III. Serial Publications

12. A serial publication, often known as a “journal” or “periodical,” is a resource that is issued in successive parts and has no predetermined conclusion. These successive parts are commonly referred to as “issues,” and each issue is usually chronologically numbered and dated. The presence of enumeration, years of coverage, and/or other chronological information also indicates a serial publication.

13. There are significant differences between cataloging finite resources (books/monographs) and continuing resources (serials). For serials, the catalog record provides information about the serial as a whole, including the first or earliest available issue. It also provides information as to holdings – the volumes and issues, with dates, received by the library and made available to the public. In serials cataloging, there are identifying characteristics unique to serials that are slightly different from monographs (books). The issue date for a print serial publication, for example, generally appears on the cover (front or back), the masthead page, the title page (if any), the table of contents page(s), or on the pages of the individual articles contained in the issue. The initial periodicals record will sometimes not reflect all subsequent changes in publication details (including minor variations in title, etc.).

More information regarding the unique aspects of cataloguing serials can be found at this link: <https://www.loc.gov/aba/pcc/conser/sccptpt/Basic-2014/Basic-Trainee-Mannual.pdf>.

IV. Ownership and Date-Stamp

14. Libraries have different policies on whether or not to date stamp publications. It is becoming increasingly common for libraries to no longer date stamp publications. In the past, it was standard practice to affix an ownership stamp somewhere within the publication, usually on the cover page, verso of the cover page, or a designated page within the publication. The timing of when an ownership stamp is entered on the monograph or periodical can vary from one library to another. It could occur when received in acquisitions after shipment to the library or at the time of cataloging. Therefore, it is possible for there to be instances when the date of receipt precedes the cataloging date or vice versa.

V. Copyright Office Record

15. The United States Copyright Office, a part of the Library of Congress, is the official U.S. government body that maintains records of copyright registrations in the United States, including providing public access to an online Copyright Catalog. The records contained in this catalog are publicly accessible and are routinely used by copyright title researchers who are attempting to clear a chain of title for copyrighted works.

VI. *ASTM D 4383-96*

16. This Declaration relates to the public accessibility, of the following: “Standard Specification for Plowable, Raised Retroreflective Pavement Markers,” *ASTM D4383-96* in Annual Book of ASTM Standards, vol. 04.03, 1997 edition, West Conshohocken, PA: American Society for Testing and Materials (referred to herein as “*ASTM D 4383-96*”). I understand that *ASTM D 4383-96* has been submitted as **Exhibit 1008** in this proceeding.

17. *ASTM D 4383-96*, **Appendix 1**, was received from a representative of BEA DOX, LLC.

18. I have inspected *ASTM D 4383-96*. *ASTM D 4383-96* appears to be in a condition that creates no suspicion about its authenticity. Specifically, the text of the standard is complete, no pages are missing, the text on the pages appear to flow seamlessly, from one page to the next and there are no visible alterations to the document. I understand from the BEA DOX representative, *ASTM D 4383-96* was found in the Library of Congress, a place where, if authentic, a copy would likely be found.

19. **Appendix 1** is a true and accurate copy of the **Exhibit 1008**. It contains the cover, front matter, foreword, table of contents, pages 450 - 459 and back cover including a date stamp for the Library of Congress. The date stamp affixed to the

front matter indicates *ASTM D 4383-96* was received by the Library of Congress on “JUL 22 1997.”

20. Based on this evidence and standard library practice, it is my professional opinion that *ASTM D 4383-96* would have been process and catalogued within a few days of receipt of July 22, 1997, and made accessible to the public.

21. **Appendix 2** to this Declaration is a true and accurate copy of the Library of Congress catalog holdings record for it holdings *ASTM D 4383-96*, which was downloaded from <https://lccn.loc.gov/83641658> on June 25, 2024. This website also includes a link to the MARC record was downloaded on June 25, 2024, and is provided as **Appendix 3**.

22. The Library of Congress public catalog record sets forth the public holdings and location information for members of the interested public seeking a physical copy of the resource. **Appendix 2**. The public catalog record of *ASTM D 4383-96* indicates that it should be requested in “Jefferson or Adams Building Readings Rooms.”

23. The Library of Congress MARC record for *ASTM D 4383-96*, MARC field tag 008 reads 760521d19702001pauar 0 a0eng. **Appendix 3**. As discussed above, the first six characters “760521” are in the typical “YYMMDD” format and confirm that *The Annual Book of ASTM Standards*, a serial, was cataloged by the Library of Congress on May 21, 1976, with the ‘d’ indicating it is “Continuing

resource ceased publication” starting in 1970 and ending in 2001. For a serial or continuing resource, characters 007-10, shown here as “1970,” contain the beginning date of the publication. Characters 11-14, shown here as “2001” contain the ending date. Other information in the MARC record confirms that this record is associated with *ASTM D 4383-96*. For example, field tag 245 denotes the title statement of the was as “a Annual book of ASTM standards.” Field tag 310 denotes the publication frequency of an item or an update to an item as “|a Annual.” Field tag 500 identifies the place of publication, publisher and copyright date as “a Published in: Conshohocken, PA, <1996->; West Conshohocken, PA, -2001.” The information from field tags 245, 310 and 500 match the information in **Exhibit 1008** showing that the *1997 Annual Book of ASTM Standards* volume 04.03 was published as an annual in 1997.

24. Based on standard library practices when publications such as *ASTM D 4383-96* are received, they are processed, cataloged, shelved and made available to the public within a few days of receipt. Based on the evidence presented in the **Appendices 2 and 3**, it is my professional opinion that *ASTM D 4383-96* would have been made public accessible at the Library of Congress within a few days of July 22, 1997, when the Library of Congress received *ASTM D 4383-96*.

25. **Appendix 4** to this Declaration is true and accurate copy of the United States Copyright Office record for *ASTM D 4383-96* with Registration record

number TX0004502832, which was retrieved from <https://cocatalog.loc.gov/cgi-bin/Pwebrecon.cgi?v1=11&ti=1,11&Search%5FArg=Annual%20book%20of%20A%20S%20T%20M%20standards&Search%5FCode=TALL&CNT=25&PID=bKsxjsf7UwgPpkB0BRKHwDT1&SEQ=20240626145046&SID=4> on June 26, 2024.

Appendix 4 lists a publication date of “1997-07-02.” **Appendix 4** includes title information that lists “Annal book of A S T M standards,” which is consistent with *ASTM D 4383-96* listing of Annual book of ASTM standards as title.

26. Based on standard library practices, a publication’s publication date indicates that the publication was accessible and available to the public on or a few of the publication date. Based on the information in **Appendix 4**, it is my professional opinion that *ASTM D 4383-96* would have been publicly accessible on or within a few days of July 2, 1997.


VII. Conclusion

27. In signing this Declaration, I understand it will be filed as evidence in a contested case before the Patent Trial and Appeal Board of the United States Patent and Trademark Office. I understand I may be subject to cross-examination in this case and that cross-examination will take place within the United States. If cross-examination is required of me, I will appear for cross-examination within the United States during the time allotted for cross-examination.

Declaration of Kelley Hayes Greenhill

28. I declare that all statements made herein of my knowledge are true, that all statements made on information and belief are believed to be true, and that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code.

Respectfully submitted,


Kelley M. Hayes Greenhill

Executed on July 23, 2024, in Washington, DC.

APPENDIX 1

LIBRARY OF CONGRESS
0 028 154 325 8

1997 ANNUAL BOOK OF
ASTM STANDARDS



1997

Bind/Abel



ANNUAL BOOK OF ASTM STANDARDS

SECTION

4

Construction



VOLUME
04.03 Road and Paving Materials;
Vehicle-Pavement Systems

Revision issued annually

ISBN 0-8031-2381-7
ISSN 0192-2998

Road and Paving Materials;
Vehicle-Pavement Systems

VOLUME
04.03

SECTION
4

TA 401
.A653
1997



SECTION
4

1997

ANNUAL BOOK OF ASTM STANDARDS

Construction



VOLUME
04.03 Road and Paving Materials;
Vehicle-Pavement Systems

Includes standards of the following committees:

D-4 on Road and Paving Materials
E-17 on Pavement Management Technologies

Publication Code Number (PCN): 01-040397-08

ASTM 100 Barr Harbor Drive, West Conshohocken, PA 19428 ■ (610) 832-9500 ■ FAX: 610-832-9555



TA 401
A 653

VOL 22 1997, SECTION 4

Editorial Staff

Director, Editorial Services:

Roberta A. Storer

Manager, Standards Publications:

Joan L. Cornillot

Paula C. Fazio-Fluehr

Senior Indexer:

H. Joel Shupak

Editors:

Jennifer C. Azara

Nicole C. Baldini

Lisa Bernhardt

Elizabeth L. Gutman

Joanne G. Kramer

Christine Leinweber

Vernice A. Mayer

Patricia A. McGee

Todd J. Sandler

Richard F. Wilhelm

Editorial Assistants:

Audrey Lewandowski

Karen L. Riley

Library of Congress Catalog Card Number: 83-641658

ISBN 0-8031-2468-6 (set)

ISBN 0-8031-2378-7 (section)

ISBN 0-8031-2381-7 (volume)

Copyright © 1997 AMERICAN SOCIETY FOR TESTING AND MATERIALS, West Conshohocken, PA. Prior editions copyrighted 1996 and earlier, by the American Society for Testing and Materials. All rights reserved. This material may not be reproduced or copied, in whole or in part, in any printed, mechanical, electronic, film, or other distribution and storage media, without the written consent of the publisher.

Photocopy Rights

Authorization to photocopy items for internal, personal, or educational classroom use, or the internal, personal, or educational classroom use of specific clients, is granted by the American Society for Testing and Materials (ASTM) provided that the appropriate fee is paid to the Copyright Clearance Center, 222 Rosewood Drive, Danvers, MA 01923, Tel: 508-750-8400; online: <http://www.copyright.com/>

Printed in Easton, MD, U.S.A.



Foreword

Organized in 1898, ASTM has grown into one of the largest voluntary standards development systems in the world. ASTM is a not-for-profit organization which provides a forum for producers, users, ultimate consumers, and those having a general interest (representatives of government and academia) to meet on common ground and write standards for materials, products, systems, and services.

From the work of 132 standards-writing committees, ASTM publishes more than 9,800 standards each year. These standards and other related technical information are sold throughout the world.

ASTM Headquarters has no technical research or testing facilities; such work is done voluntarily by 33,300 technically qualified ASTM members located throughout the world. Membership in the Society is open to all concerned with the fields in which ASTM is active. A membership application may be found at the back of this volume. Additional information may be obtained from Member and Committee Services, ASTM, 100 Barr Harbor Drive, West Conshohocken, PA 19428; tel. (610) 832-9693.

1997 Annual Book of ASTM Standards

The 1997 *Annual Book of ASTM Standards* consists of 72 volumes, divided among 16 sections, of which this volume is one. It contains approved ASTM standards, provisional standards, and related material. These terms are defined as follows in the *Regulations Governing ASTM Technical Committees*:

Categories:

standard—as used in ASTM, a document that has been developed and established within the consensus principles of the Society and that meets the approval requirements of ASTM procedures and regulations.

Discussion—The term “standard” serves in ASTM as an adjective in the title of documents, such as test methods or specifications, to connote specified consensus and approval. The various types of standard documents are based on the needs and usages as prescribed by the technical committees of the Society.

provisional standard—a document published for a limited period of time by the Society to meet a demand for more rapid issuance of specific documents, such as an emergency situation, regulatory requirements, or other special circumstances.

Discussion—Provisional standards are not full consensus documents because they require subcommittee consensus only. (These documents replace emergency standards and proposals.)

Types:

The various types of ASTM documents are to provide a flexibility of form, communication, and usage for both the technical committees and the myriad users of ASTM documents. The type of ASTM document that is developed and titled is based on the technical content and intended use, not on the degree of consensus achieved. The two categories of ASTM documents (standard and provisional standard) can be of the following forms and types:

classification—a systematic arrangement or division of materials, products, systems, or services into groups based on similar characteristics such as origin, composition, properties, or use.

guide—a series of options or instructions that does not recommend a specific course of action.

Discussion—Whereas a practice prescribes a general usage principle, a guide only suggests an approach. The purpose of a guide is to offer guidance, based on a consensus of viewpoints, but not to establish a fixed procedure. A guide is intended to increase the awareness of the user to available techniques in a given subject area and to provide information from which subsequent evaluation and standardization can be derived.

LISTED BY SUBJECTS

SUBJECTS	VOLUME	SUBJECTS	VOLUME
Temperature Measurement.....	14.03	Traveled Surface Characteristics.....	04.03
Textiles.....	07.01, 07.02	Vacuum Cleaners.....	15.07
Thermal Insulation.....	04.06	Vehicle-Pavement Systems.....	04.03
Thermal Measurements.....	14.02	Vitrified clay Pipe.....	04.05
Thermocouples.....	14.03	Waste Management.....	11.04
Thermostats, Electrical Heating and Resistance, Con- tacts, and Connectors.....	03.04	Water.....	11.01, 11.02
Tires.....	09.02	Wear and Erosion.....	03.02
		Wood.....	04.10



Contents

1997 ANNUAL BOOK OF ASTM STANDARDS, VOLUME 04.03

ROAD AND PAVING MATERIALS; PAVEMENT MANAGEMENT TECHNOLOGIES

A complete Subject Index begins on p. 871

This contents includes only those standards included in Volume 04.03 and those standards that appeared previously that have been superseded or discontinued within the past three years. Since the standards in this book are arranged in alphanumeric sequence, no page numbers are given in this contents.

In the serial designations prefixed to the following titles, the number following the dash indicates the year of adoption as standard or, in the case of revision, the year of last revision. Thus, standards adopted or revised during the year 1997 have as their final number, 97. A letter following this number indicates more than one revision during that year, that is, 97a indicates the second revision in 1997, 97b the third revision, etc. Standards that have been reapproved without change are indicated by the year of last reapproval in parentheses as part of the designation number, for example, (1997). A superscript epsilon indicates an editorial change since the last revision or reapproval—e1 for the first change, e2 for the second change, etc.

§D 5 - 95	Test Method for Penetration of Bituminous Materials
D 8 - 94	Terminology Relating to Materials for Roads and Pavements
D 20 - 91 ^{e1}	Test Method for Distillation of Road Tars
§D 70 - 82 (1990)	Test Method for Specific Gravity and Density of Semi-Solid Bituminous Materials
§D 75 - 87 (1992) ^{e1}	Practice for Sampling Aggregates
§D 98 - 95	Specification for Calcium Chloride
D 113 - 86 (1992)	Test Method for Ductility of Bituminous Materials
D 139 - 95	Test Method for Float Test for Bituminous Materials
§D 140 - 93	Practice for Sampling Bituminous Materials
§D 242 - 95	Specification for Mineral Filler for Bituminous Paving Mixtures
D 243 - 94	Test Method for Residue of Specified Penetration
§D 244 - 95	Test Methods for Emulsified Asphalts
D 290 - 91a	Practice for Bituminous Mixing Plant Inspection
§D 345 - 90 ^{e1}	Test Method for Sampling and Testing Calcium Chloride for Roads and Structural Applications
D 402 - 94	Test Method for Distillation of Cut-Back Asphaltic (Bituminous) Products
§D 448 - 86 (1993)	Classification for Sizes of Aggregate for Road and Bridge Construction
§D 490 - 92	Specification for Road Tar
D 517 - 92 ^{e1}	Specification for Asphalt Plank
§D 545 - 84 (1993) ^{e1}	Test Methods for Preformed Expansion Joint Fillers for Concrete Construction (Nonextruding and Resilient Types)
§D 546 - 94	Test Method for Sieve Analysis of Mineral Filler for Road and Paving Materials
D 632 - 94	Specification for Sodium Chloride
D 633 - 87 (1991)	Volume Correction Table for Road Tar
§D 692 - 94a	Specification for Coarse Aggregate for Bituminous Paving Mixtures
§D 693 - 84 (1993) ^{e1}	Specification for Crushed Aggregate for Macadam Pavements
§D 946 - 82 (1993)	Specification for Penetration-Graded Asphalt Cement for Use in Pavement Construction
§D 977 - 91	Specification for Emulsified Asphalt
§D 979 - 96	Practice for Sampling Bituminous Paving Mixtures
§D 994 - 94	Specification for Preformed Expansion Joint Filler for Concrete (Bituminous Type)
§D 995 - 95b	Specification for Mixing Plants for Hot-Mixed, Hot-Laid Bituminous Paving Mixtures
§D 1073 - 94	Specification for Fine Aggregate for Bituminous Paving Mixtures
D 1074 - 96	Test Method for Compressive Strength of Bituminous Mixtures
§D 1075 - 96	Test Method for Effect of Water on Compressive Strength of Compacted Bituminous Mixtures
§D 1139 - 95	Specification for Aggregate for Single or Multiple Bituminous Surface Treatments
§D 1188 - 96	Test Method for Bulk Specific Gravity and Density of Compacted Bituminous Mixtures Using Paraffin-Coated Specimens
D 1190 - 96	Specification for Concrete Joint Sealer, Hot-Poured Elastic Type
D 1191 - 84 (1994) ^{e1}	Test Methods for Concrete Joint Sealers (Discontinued 1996—Replaced by D 5329†)
§D 1369 - 84 (1994)	Practice for Quantities of Materials for Bituminous Surface Treatments
§D 1461 - 85 (1994)	Test Method for Moisture or Volatile Distillates in Bituminous Paving Mixtures
§D 1559 - 89	Test Method for Resistance to Plastic Flow of Bituminous Mixtures Using Marshall Apparatus

§ Approved for use by agencies of the Department of Defense. Consult the DoD Index of Specifications and Standards for the specific year of issue which has been adopted by the Department of Defense.

† Although this standard has been officially withdrawn from Society approval, a brief description is included for information only.

CONTENTS

D 1560 - 92	Test Methods for Resistance to Deformation and Cohesion of Bituminous Mixtures by Means of Hveem Apparatus
D 1561 - 92	Practice for Preparation of Bituminous Mixture Test Specimens by Means of California Kneading Compactor
D 1665 - 91	Test Method for Engler Specific Viscosity of Tar Products
§D 1751 - 83 (1991)	Specification for Preformed Expansion Joint Filler for Concrete Paving and Structural Construction (Nonextruding and Resilient Bituminous Types)
§D 1752 - 84 (1996) ^{ei}	Specification for Preformed Sponge-Rubber and Cork Expansion Joint Fillers for Concrete Paving and Structural Construction
D 1754 - 94	Test Method for Effect of Heat and Air on Asphaltic Materials (Thin-Film Oven Test)
D 1854 - 96	Specification for Jet-Fuel Resistant Concrete Joint Sealer, Hot-Poured Elastic Type
D 1855 - 89	Test Methods for Jet-Fuel-Resistant Concrete Joint Sealer, Hot-Poured Elastic Type (Discontinued 1996†)
D 1856 - 95a	Test Method for Recovery of Asphalt from Solution by Abson Method
D 1985 - 91	Practice for Preparing Concrete Blocks for Testing Sealants, for Joints and Cracks
§D 2026 - 72 (1993)	Specification for Cutback Asphalt (Slow-Curing Type)
§D 2027 - 76 (1992)	Specification for Cutback Asphalt (Medium-Curing Type)
§D 2028 - 76 (1992)	Specification for Cutback Asphalt (Rapid-Curing Type)
D 2041 - 95	Test Method for Theoretical Maximum Specific Gravity and Density of Bituminous Paving Mixtures
D 2042 - 81 (1993)	Test Method for Solubility of Asphalt Materials in Trichloroethylene
§D 2170 - 95	Test Method for Kinematic Viscosity of Asphalts (Bitumens)
D 2171 - 94	Test Method for Viscosity of Asphalts by Vacuum Capillary Viscometer
§D 2172 - 95	Test Methods for Quantitative Extraction of Bitumen from Bituminous Paving Mixtures
§D 2397 - 94	Specification for Cationic Emulsified Asphalt
D 2399 - 83 (1991)	Practice for Selection of Cutback Asphalts
§D 2419 - 95	Test Method for Sand Equivalent Value of Soils and Fine Aggregate
D 2489 - 84 (1994) ^{ei}	Test Method for Degree of Particle Coating of Bituminous-Aggregate Mixtures
D 2493 - 95a	Viscosity-Temperature Chart for Asphalts
§D 2628 - 91	Specification for Preformed Polychloroprene Elastomeric Joint Seals for Concrete Pavements
D 2726 - 96a ^{ei}	Test Method for Bulk Specific Gravity and Density of Non-Absorptive Compacted Bituminous Mixtures
D 2728 - 83 (1991)	Practice for Paving Uses and Application Temperatures for Road Tars
D 2828 - 96	Specification for Nonbituminous Inserts for Contraction Joints in Portland Cement Concrete Airfield Pavements, Sawable Type
§D 2835 - 89 (1993)	Specification for Lubricant for Installation of Preformed Compression Seals in Concrete Pavements
D 2872 - 88 (1995) ^{ei}	Test Method for Effect of Heat and Air on a Moving Film of Asphalt (Rolling Thin-Film Oven Test)
§D 2940 - 92	Specification for Graded Aggregate Material for Bases or Subbases for Highways or Airports
§D 2950 - 91	Test Method for Density of Bituminous Concrete in Place by Nuclear Method
D 2993 - 83 (1991)	Specification for Acrylonitrile-Butadiene Rubberized Tar
D 2994 - 87 (1991)	Test Methods for Rubberized Tar
D 2995 - 93	Practice for Determining Application Rate of Bituminous Distributors
D 3042 - 95	Test Method for Insoluble Residue in Carbonate Aggregates
D 3141 - 96	Specification for Asphalt for Undersealing Portland-Cement Concrete Pavements
D 3142 - 84 (1989)	Test Method for Specific Gravity or API Gravity of Liquid Asphalts by Hydrometer Method
D 3143 - 95	Test Method for Flash Point of Cutback Asphalt with Tag Open-Cup Apparatus
D 3202 - 94	Practice for Preparation of Bituminous Mixture Beam Specimens by Means of the California Kneading Compactor
D 3203 - 94	Test Method for Percent Air Voids in Compacted Dense and Open Bituminous Paving Mixtures
D 3204 - 93	Specification for Preformed Cellular Plastic Joint Fillers for Relieving Pressure
D 3205 - 86 (1991)	Test Method for Viscosity of Asphalt with Cone and Plate Viscometer
D 3279 - 90	Test Method for <i>n</i> -Heptane Insolubles
D 3289 - 85 (1990) ^{ei}	Test Method for Specific Gravity or Density of Semi-Solid and Solid Bituminous Materials by Nickel Crucible
D 3319 - 90	Test Method for Accelerated Polishing of Aggregates Using the British Wheel
§D 3381 - 92	Specification for Viscosity-Graded Asphalt Cement for Use in Pavement Construction
D 3387 - 83 (1996)	Test Method for Compaction and Shear Properties of Bituminous Mixtures by Means of the U.S. Corps of Engineers Gyratory Testing Machine (GTM)
D 3398 - 93	Test Method for Index of Aggregate Particle Shape and Texture
D 3405 - 96	Specification for Joint Sealants, Hot-Applied, for Concrete and Asphalt Pavements
D 3406 - 95	Specification for Joint Sealant, Hot-Applied, Elastomeric-Type, for Portland Cement Concrete Pavements
D 3407 - 78 (1994) ^{ei}	Test Methods for Joint Sealants, Hot-Poured, for Concrete and Asphalt Pavements
D 3496 - 93	Test Method for Preparation of Bituminous Mixture Specimens for Dynamic Modulus Testing
D 3497 - 79 (1995)	Test Method for Dynamic Modulus of Asphalt Mixtures
D 3515 - 96	Specification for Hot-Mixed, Hot-Laid Bituminous Paving Mixtures
D 3542 - 92	Specification for Preformed Polychloroprene Elastomeric Joint Seals for Bridges
D 3549 - 93a	Test Method for Thickness or Height of Compacted Bituminous Paving Mixture Specimens
D 3569 - 95	Specification for Joint Sealant, Hot-Applied, Elastomeric, Jet-Fuel-Resistant-Type, for Portland Cement Concrete Pavements
D 3581 - 96	Specification for Joint Sealant, Hot-Poured, Jet-Fuel-Resistant Type, for Portland Cement Concrete and Tar-Concrete Pavements
D 3582 - 89	Test Methods for Joint Sealant, Hot-Poured, Jet-Fuel-Resistant Type, for Portland Cement Concrete and Tar-Concrete Pavements (Discontinued 1996—Replaced by D 5329†)

CONTENTS

D 3583 - 85 (1991) ^{ei}	Methods of Testing Joint Sealant, Hot-Applied, Elastomeric-Type, for Portland Cement Concrete Pavements, or Joint Sealant, Hot-Applied, Elastomeric, Jet-Fuel-Resistant-Type, for Portland Cement Concrete Pavements (Discontinued 1996†)
D 3625 - 96	Practice for Effect of Water on Bituminous-Coated Aggregate Using Boiling Water
D 3628 - 93a	Practice for Selection and Use of Emulsified Asphalts
D 3633 - 94	Test Method for Electrical Resistivity of Membrane-Pavement Systems
D 3637 - 84 (1991)	Test Methods for Permeability of Bituminous Mixtures
D 3665 - 94	Practice for Random Sampling of Construction Materials
§D 3666 - 96a	Specification for Minimum Requirements for Agencies Testing and Inspecting Bituminous Paving Materials
D 3743 - 84 (1995)	Terminology Relating to Bridge Deck and Substructure Protection
D 3744 - 94	Test Method for Aggregate Durability Index
D 3910 - 96	Practices for Design, Testing, and Construction of Slurry Seal
D 3963/D 3963M - 96a	Specification for Epoxy-Coated Reinforcing Steel
D 4013 - 81 (1993)	Practice for Preparation of Test Specimens of Bituminous Mixtures by Means of Gyratory Shear Compactor
D 4014 - 89 (1995)	Specification for Plain and Steel-Laminated Elastomeric Bearings for Bridges
D 4070 - 91 (1996) ^{ei}	Specification for Adhesive Lubricant for Installation of Preformed Elastomeric Bridge Compression Seals in Concrete Structures
D 4071 - 84 (1995) ^{ei}	Practice for Use of Portland Cement Concrete Bridge Deck Waterproof Barrier Membrane Systems
D 4123 - 82 (1995)	Test Method for Indirect Tension Test for Resilient Modulus of Bituminous Mixtures
D 4124 - 91	Test Methods for Separation of Asphalt into Four Fractions
D 4125 - 94	Test Method for Asphalt Content of Bituminous Mixtures by the Nuclear Method
D 4215 - 96	Specification for Cold-Mixed, Cold-Laid Bituminous Paving Mixtures
D 4280 - 96	Specification for Extended Life Type, Non-Plowable, Prismatic, Raised, Retroreflective Pavement Markers
D 4311 - 96	Practice for Determining Asphalt Volume Correction to a Base Temperature
D 4383 - 96	Specification for Plowable, Raised Retroreflective Pavement Markers
D 4460 - 85 (1991)	Practice for Calculating Precision Limits Where Values are Calculated from Other Test Methods
D 4469 - 92	Test Method for Calculating Percent Asphalt Absorption by the Aggregate in an Asphalt Pavement Mixture
D 4505 - 96	Specification for Preformed Plastic Pavement Marking Tape for Extended Service Life
D 4552 - 92	Practice for Classifying Hot-Mix Recycling Agents
D 4561 - 96	Practice for Quality Control Systems for Organizations Producing and Applying Bituminous Paving Materials
D 4580 - 86 (1992)	Practice for Measuring Delaminations in Concrete Bridge Decks by Sounding
D 4592 - 96	Specification for Preformed Plastic Pavement Marking Tape for Limited Service Life
D 4694 - 96	Test Method for Deflections with a Falling-Weight-Type Impulse Load Device
D 4695 - 96	Guide for General Pavement Deflection Measurements
D 4748 - 87 (1995) ^{ei}	Test Method for Determining the Thickness of Bound Pavement Layers Using Short-Pulse Radar
D 4788 - 88 (1993)	Test Method for Detecting Delaminations in Bridge Decks Using Infrared Thermography
D 4791 - 95	Test Method for Flat Particles, Elongated Particles, or Flat and Elongated Particles in Coarse Aggregate
D 4792 - 95	Test Method for Potential Expansion of Aggregates from Hydration Reactions
D 4867/D 4867M - 96	Test Method for Effect of Moisture on Asphalt Concrete Paving Mixtures
D 4887 - 89 (1993) ^{ei}	Test Method for Preparation of Viscosity Blends for Hot Recycled Bituminous Materials
D 4956 - 95	Specification for Retroreflective Sheeting for Traffic Control
D 4957 - 95	Test Method for Apparent Viscosity of Asphalt Emulsion Residues and Non-Newtonian Bitumens by Vacuum Capillary Viscometer
D 5078 - 95	Specification for Crack Filler, Hot-Applied, for Asphalt Concrete and Portland Cement Concrete Pavements
D 5148 - 95	Test Method for Centrifuge Kerosine Equivalent
D 5167 - 91	Practice for Melting of Hot-Applied Joint and Crack Sealant and Filler for Evaluation
D 5212 - 91	Specification for High Load Rotational Confined Elastomeric Bearings for Bridges and Structures
D 5249 - 95	Specification for Backer Material for Use With Cold and Hot-Applied Joint Sealants in Portland-Cement Concrete and Asphalt Joints
D 5329 - 96	Test Methods for Sealants and Fillers, Hot-Applied, for Joints and Cracks in Asphaltic and Portland Cement Concrete Pavements
D 5339 - 94	Practice for a Quality Assurance Plan for Structural Steel Fabrication for Highway Structures
D 5340 - 93	Test Method for Airport Pavement Condition Index Surveys
D 5360 - 93	Practice for Design and Construction of Bituminous Surface Treatments
D 5361 - 95	Practice for Sampling Compacted Bituminous Mixtures for Laboratory Testing
D 5404 - 93	Test Method for Recovery of Asphalt from Solution Using the Rotovapor Apparatus
D 5444 - 94	Test Method for Mechanical Size Analysis of Extracted Aggregate
D 5484 - 94	Specification for Steel Grid Bridge Flooring
D 5505 - 94	Practice for Classifying Emulsified Recycling Agents
D 5506 - 94	Practice for Organizations Engaged in the Certification of Personnel Testing and Inspecting Bituminous Paving Materials
D 5535 - 94	Terminology Relating to Formed-In-Place Sealants for Joints and Cracks in Pavements
D 5545 - 94 ^{ei}	Test Method for Identification of Cationic Slow Set Emulsified Asphalts
D 5546 - 94a	Test Method for Solubility of Polymer Modified Asphalt Materials in 1,1,1-Trichloroethane
D 5581 - 96	Test Method for Resistance to Plastic Flow of Bituminous Mixtures Using Marshall Apparatus (6 Inch-Diameter Specimen)
D 5624 - 94	Test Method for Determining the Transverse-Aggregate Spread Rate for Surface Treatment Applications
D 5710 - 95	Specification for Trinidad Lake Modified Asphalt
D 5711 - 95	Test Method for Adherent Fines Test
D 5801 - 95	Test Method for Toughness and Tenacity of Bituminous Materials

CONTENTS

D 5821 - 95	Test Method for Determining the Percentage of Fractured Particles in Coarse Aggregate
D 5840 - 95	Specification for Type II Polymer Modified Asphalt Cement for Use in Pavement Construction
D 5841 - 95	Specification for Type III Polymer Modified Asphalt Cement for Use in Pavement Construction
D 5892 - 96a	Specification for Type IV Polymer Modified Asphalt Cement for Use in Pavement Construction
D 5893 - 96	Specification for Cold-Applied, Single Component, Chemically Curing Silicone Joint Sealant for Portland Cement Concrete Pavements
D 5976 - 96	Specification for Type I Polymer Modified Asphalt Cement for Use in Pavement Construction
D 5977 - 96	Specification for High Load Rotational Spherical Bearings for Bridges and Structures
E 274 - 90	Test Method for Skid Resistance of Paved Surfaces Using a Full-Scale Tire
E 303 - 93	Test Method for Measuring Surface Frictional Properties Using the British Pendulum Tester
E 445/E 445M - 88 (1996)	Test Method for Stopping Distance on Paved Surfaces Using a Passenger Vehicle Equipped with Full-Scale Tires
E 501 - 94	Specification for Standard Rib Tire for Pavement Skid-Resistance Tests
E 503/E 503M - 88 (1994)	Test Methods for Measurement of Skid Resistance on Paved Surfaces Using a Passenger Vehicle Diagonal Braking Technique
E 524 - 88 (1994) [†]	Specification for Standard Smooth Tire for Pavement Skid-Resistance Tests
E 556 - 95	Test Method for Calibrating a Wheel Force or Torque Transducer Using a Calibration Platform (User Level)
E 660 - 90 (1996)	Practice for Accelerated Polishing of Aggregates or Pavement Surfaces Using a Small-Wheel, Circular Track Polishing Machine
E 670 - 94	Test Method for Side Force Friction on Paved Surfaces Using the Mu-Meter
E 707 - 90 (1996)	Test Method for Skid Resistance Measurements Using the North Carolina State University Variable-Speed Friction Tester
E 867 - 95a	Terminology Relating to Traveled Surface Characteristics
E 950 - 94	Test Method for Measuring the Longitudinal Profile of Traveled Surfaces With an Accelerometer Established Inertial Profiling Reference
E 965 - 96	Test Method for Measuring Pavement Macrotexture Depth Using a Volumetric Technique
E 1082 - 90 (1995)	Test Method for Measurement of Vehicular Response to Traveled Surface Roughness
E 1136 - 93	Specification for a Radial Standard Reference Test Tire
E 1166 - 91 (1995)	Guide for Network Level Pavement Management
E 1170 - 92	Practices for Simulating Vehicular Response to Longitudinal Profiles of a Vehicular Traveled Surface
E 1215 - 93	Specification for Trailers Used for Measuring Vehicle Response to Road Roughness
E 1274 - 88 (1993) [†]	Test Method for Measuring Pavement Roughness Using a Profilograph
E 1318 - 94	Specification for Highway Weigh-In-Motion (WIM) Systems With User Requirements and Test Method
E 1337 - 90 (1996)	Test Method for Determining Longitudinal Peak Braking Coefficient of Paved Surfaces Using a Standard Reference Test Tire
E 1364 - 95	Test Method for Measuring Road Roughness by Static Level Method
E 1393 - 90 (1996)	Test Method for Determining the Polishability of Bituminous Pavement Surfaces and Specimens by Means of the Penn State Reciprocating Polishing Machine
E 1442 - 94	Practice for Highway-Traffic Monitoring
E 1448 - 92	Practice for Calibration of Systems Used for Measuring Vehicular Response to Pavement Roughness
E 1489 - 96	Practice for Computing Ride Number of Roads from Longitudinal Profile Measurements Made by an Inertial Profile Measuring Device
E 1500 - 93	Practice for Computing Mean Square Numerics from Road Surface Elevation Profile Records
E 1551 - 93a	Specification for Special Purpose, Smooth-Tread Tire, Operated on Fixed Braking Slip Continuous Friction Measuring Equipment
E 1572 - 93	Practice for Classifying Highway Vehicles from Known Axle Count and Spacing
E 1656 - 94	Guide for Classification of Automated Pavement Condition Survey Equipment
E 1703/E 1703M - 95	Test Method for Measuring Rut-Depth of Pavement Surfaces Using a Straightedge
E 1777 - 96	Guide for Prioritization of Data Needs for Pavement Management
E 1778 - 96a	Terminology Relating to Pavement Distress
E 1844 - 96	Specification for a Size 10 x 4.5 Smooth-Tread Friction Test Tire
E 1845 - 96	Practice for Calculating Pavement Macrotexture Mean Profile Depth
PS 36 - 95	Provisional Practice for Accelerated Aging of Asphalt Binder Using a Pressurized Aging Vessel (PAV)

RELATED MATERIAL

Metrc Practice (Excerpts) (E 380)	PAGE
Index	859
ASTM Membership Application Blank	871



List by Subjects

1997 ANNUAL BOOK OF ASTM STANDARDS, VOLUME 04.03

ROAD AND PAVING MATERIALS; PAVEMENT MANAGEMENT TECHNOLOGIES

A complete Subject Index begins on p. 871

Since the standards in this book are arranged in alphanumeric sequence, no page numbers are given in this list.

AGGREGATES

Specifications for:

§D 1139 - 95
§D 692 - 94a
§D 693 - 84 (1993)[†]
§D 1073 - 94
§D 2940 - 92
§D 242 - 95
D 5106 - 91

Aggregate for Single or Multiple Bituminous Surface Treatments
Coarse Aggregate for Bituminous Paving Mixtures
Crushed Aggregate for Macadam Pavements
Fine Aggregate for Bituminous Paving Mixtures
Graded Aggregate Material for Bases or Subbases for Highways or Airports
Mineral Filler for Bituminous Paving Mixtures
Steel Slag Aggregates for Bituminous Paving Mixtures (see Vol 11.04)

Test Methods for:

D 3319 - 90
D 3744 - 94
D 5148 - 95
D 5821 - 95
D 4791 - 95
D 3398 - 93
D 3042 - 95
D 4792 - 95
§D 2419 - 95
§D 546 - 94

Accelerated Polishing of Aggregates Using the British Wheel
Aggregate Durability Index
Centrifuge Kerosine Equivalent
Determining the Percentage of Fractured Particles in Coarse Aggregate
Flat Particles, Elongated Particles, or Flat and Elongated Particles in Coarse Aggregate
Index of Aggregate Particle Shape and Texture
Insoluble Residue in Carbonate Aggregates
Potential Expansion of Aggregates from Hydration Reactions
Sand Equivalent Value of Soils and Fine Aggregate
Sieve Analysis of Mineral Filler for Road and Paving Materials

Practices for:

D 3625 - 96
§D 75 - 87 (1992)[†]

Effect of Water on Bituminous-Coated Aggregate Using Boiling Water
Sampling Aggregates

Classification for:

§D 448 - 86 (1993)

Sizes of Aggregate for Road and Bridge Construction

Terminology Relating to:

D 8 - 94

Materials for Roads and Pavements

BITUMINOUS MATERIALS

Specifications for:

D 2993 - 83 (1991)
D 3141 - 96
§D 2397 - 94
§D 2027 - 76 (1992)
§D 2028 - 76 (1992)
§D 2026 - 72 (1993)
§D 977 - 91
§D 946 - 82 (1993)
§D 490 - 92
D 5710 - 95
D 5976 - 96
D 5840 - 95
D 5841 - 95
D 5892 - 96a
§D 3381 - 92

Acrylonitrile-Butadiene Rubberized Tar
Asphalt for Undersealing Portland-Cement Concrete Pavements
Cationic Emulsified Asphalt
Cutback Asphalt (Medium-Curing Type)
Cutback Asphalt (Rapid-Curing Type)
Cutback Asphalt (Slow-Curing Type)
Emulsified Asphalt
Penetration-Graded Asphalt Cement for Use in Pavement Construction
Road Tar
Trinidad Lake Modified Asphalt
Type I Polymer Modified Asphalt Cement for Use in Pavement Construction.
Type II Polymer Modified Asphalt Cement for Use in Pavement Construction
Type III Polymer Modified Asphalt Cement for Use in Pavement Construction
Type IV Polymer Modified Asphalt Cement for Use in Pavement Construction
Viscosity-Graded Asphalt Cement for Use in Pavement Construction

[†] Approved for use by agencies of the Department of Defense. Consult the DoD Index of Specifications and Standards for the specific year of issue which has been adopted by the Department of Defense.

APPENDIX

(Nonmandatory Information)

X1. FORMULAS USED IN DETERMINING VOLUME CORRECTIONS TO A BASE TEMPERATURE

X1.1 *Volume Correction Formulas*—The formulas used in Table 1 were derived from the original tables listed in Guide D 1250 – 80 for Group 0 and 1 Oils in Tables 7.25. A linear regression analysis for the tables is listed below for each factor.

$$A = 1.0211326242 - 3.548988118 \times 10^{-4} [T(F)] + 4.49881 \times 10^{-8} [T(F)]^2 \quad (X1.1)$$

where:

A = volume correction factor, and
 $T(F)$ = temperature of asphalt cement in °F.

$$B = 1.02413769 - 4.0641418 \times 10^{-4} [T(F)] + 6.79176 \times 10^{-8} [T(F)]^2 \quad (X1.2)$$

where:

B = volume correction factor, and
 $T(F)$ = temperature of asphalt cement in °F.

X1.1.1 These two formulas generate the same values as the original table at all temperatures except those listed below:

Factor A		
Temperature, °F	D 1250 Table	Calculated Value
7	1.0186	1.0187
49	1.0038	1.0039
59	1.0003	1.0004
246	0.9365	0.9366
Factor B		
Temperature, °F	D 1250 Table	Calculated Value
17	1.0174	1.0172
336	0.8952	0.8953
372	0.8823	0.8824
449	0.8554	0.8553
479	0.8451	0.8450
499	0.8383	0.8382

The differences are always in the 4th digit and the difference is never more than one. The 10 exceptions out of 1000

results indicates an exceptionally good fit to the original data.

X1.2 *Temperature Correction to 15°C*—Because the original tables were developed around correcting asphalt cement to a base temperature of 60°F (15.6°C) it was determined to use the formulas used to derive this table in converting to a new base temperature of 15°C. The first step is to convert the 60°F formula to an equivalent 15.6°C formula by replacing (°F) = 32 + 1.8(°C). This results in new (A) and (B) factor formulas listed below:

$$A = 1.00982193004 - 6.3363523212 \times 10^{-4} [T(°C)] + 1.45761444 \times 10^{-7} [T(°C)]^2 \quad (X1.3)$$

$$B = 1.01120198386 - 7.2372141648 \times 10^{-4} [T(°C)] + 2.20053024 \times 10^{-7} [T(°C)]^2 \quad (X1.4)$$

X1.2.1 To convert to a base temperature of 15°C rather than 15.6°C, a value of 15°C was substituted into the above equations. The result for each factor is listed below:

$$A = 1.0003502$$

$$B = 1.0003957$$

X1.2.2 To convert to a base temperature of 15°C the following adjustment was made to A and B Factor Formulas:

$$A = (1.00982193004 + 1.0003502) - (6.3363523212 \times 10^{-4} + 1.0003502) [T(°C)] + (1.45761444 \times 10^{-7} + 1.0003502) [T(°C)]^2 \quad (X1.5)$$

$$A = 1.0094684142 - 6.33413410744 \times 10^{-4} [T(°C)] + 1.45710416212 \times 10^{-7} [T(°C)]^2 \quad (X1.6)$$

$$B = (1.01120198386 + 1.0003957) - (7.2372141648 \times 10^{-4} + 1.0003957) [T(°C)] + (2.20053024 \times 10^{-7} + 1.0003957) [T(°C)]^2 \quad (X1.7)$$

$$B = 1.0108020095 - 7.2343515319 \times 10^{-4} [T(°C)] + 2.1996598346 \times 10^{-7} [T(°C)]^2 \quad (X1.8)$$

These calculated formulas and the resulting table is listed in this practice.

The American Society for Testing and Materials takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, 100 Barr Harbor Drive, West Conshohocken, PA 19428.

Standard Specification for Plowable, Raised Retroreflective Pavement Markers¹

This standard is issued under the fixed designation D 4383; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This specification covers a type of plowable, retro-reflective, raised pavement marker for lane marking and delineation.

1.2 Retroreflective markers are intended for nighttime visibility.

1.3 The values stated in SI units are to be regarded as the standard. The values given in parentheses are for information only.

1.4 The following precautionary caveat pertains only to the test methods portion, Section 10, of this specification: *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Referenced Documents

2.1 ASTM Standards:

- A 536 Specification for Ductile Iron Castings²
- C 184 Test Method for Fineness of Hydraulic Cement by the 150-μm (No. 100) and 75-μm (No. 200) Sieves³
- C 430 Test Method for Fineness of Hydraulic Cement by the 45-μm (No. 325) Sieve³
- D 5 Test Method for Penetration of Bituminous Materials⁴
- D 36 Test Method for Softening Point of Bitumen (Ring-and-Ball Apparatus)⁵
- D 70 Test Method for Specific Gravity and Density of Semi-Solid Bituminous Materials⁴
- D 92 Test Method for Flash and Fire Points by Cleveland Open Cup⁶
- D 788 Classification System for Poly(Methyl Methacrylate) (PMMA) Molding and Extrusion Compounds⁷
- D 1754 Test Method for Effect of Heat and Air on Asphaltic Materials (Thin-Film Oven Test)⁴
- D 1856 Test Method for Recovery of Asphalt from Solution by Abson Method⁴
- D 2171 Test Method for Viscosity of Asphalts by Vacuum Capillary Viscometer⁴

D 2669 Test Method for Apparent Viscosity of Petroleum Waxes Compounded with Additives (Hot Melts)⁸

D 2712 Test Method for Hydrocarbon Traces in Propylene Concentrates by Gas Chromatography⁸

D 3407 Test Methods for Joint Sealants, Hot-Poured, for Concrete and Asphalt Pavements⁴

D 3935 Specification for Polycarbonate (PC) Unfilled and Reinforced Material⁹

D 4402 Test Method for Viscosity Determinations of Unfilled Asphalts Using the Brookfield Thermoset Apparatus⁵

E 284 Terminology of Appearance¹⁰

E 308 Practice for Computing the Colors of Objects by Using the CIE System¹⁰

E 808 Practice for Describing Retroreflection¹⁰

E 809 Practice for Measuring Photometric Characteristics of Retroreflectors¹⁰

E 811 Practice for Measuring Colorimetric Characteristics of Retroreflectors Under Nighttime Conditions¹⁰

2.2 Federal Specifications:¹¹

FF-W-1825A Wool and Gauze, Metallic

TT-T-291 Thinner, Paint, Mineral Spirits, Regular and Odorless

2.3 AASHTO Standards:¹²

AASHTO No. M 237 Epoxy Resin Adhesive for Bonding Traffic Markers to Hardened Concrete

AASHTO No. T 237 Testing Epoxy Resin Adhesive

3. Terminology

3.1 Definitions:

3.1.1 *coefficient of luminous intensity*, R_l (specific intensity)—the ratio of the luminous intensity (I) of the retroreflector in the direction of observation to the illuminance (E) at the retroreflector on a plane perpendicular to the direction of the incident light, expressed in candelas per lux (cd/lx) (see Practice E 808 and Terminology E 284).

3.1.1.1 *Discussion*—When values are low the coefficient of (retroreflected) luminous intensity may be given in millicandelas per lux. In inch-pound units, R_l is given in candelas per footcandle (cd/ftc). Historically the term specific intensity and symbol (SI) have been used to designate this term but R_l is preferred.

3.1.2 *color*—expressed by chromaticity coordinates according to the CIE (Commission Internationale de l'Eclairage 1931) standard colorimetric system.

¹ This specification is under the jurisdiction of ASTM Committee D-4 on Road and Paving Materials and is the direct responsibility of Subcommittee D04.38 on Highway Traffic Materials.

Current edition approved May 10, 1996. Published July 1996. Originally published as D 4383 – 84. Last previous edition D 4383 – 95.

² Annual Book of ASTM Standards, Vol 01.02.

³ Annual Book of ASTM Standards, Vol 04.01.

⁴ Annual Book of ASTM Standards, Vol 04.03.

⁵ Annual Book of ASTM Standards, Vol 04.04.

⁶ Annual Book of ASTM Standards, Vol 05.01.

⁷ Annual Book of ASTM Standards, Vol 08.01.

⁸ Annual Book of ASTM Standards, Vol 05.02.

⁹ Annual Book of ASTM Standards, Vol 08.02.

¹⁰ Annual Book of ASTM Standards, Vol 06.01.

¹¹ Available from U.S. Government Printing Office, Washington, DC 20402.

¹² Available from American Association of State Highway and Transportation Officials, 444 N. Capitol, Washington, DC 20001.

3.1.3 *horizontal entrance angle*—the angle in the horizontal plane between the direction of incident light and the normal to the leading edge of the marker.

3.1.3.1 *Discussion*—This angle corresponds to the second component of the entrance angle β_2 . (See Practice E 808.) The direction given in Practice E 808 should be used when designating this angle.

3.1.4 *observation angle*—the angle at the reflector between the illumination axis and the observation axis. (See Practice E 808.)

3.2 Description of Term Specific to This Standard:

3.2.1 *raised retroreflective pavement markers, raised retroreflective marker, retroreflective marker, and marker*—used interchangeably in this specification to refer to a molded plastic prismatic retroreflector, the reflecting area of which is covered with an abrasion-resistant lens surface. The terms do not include the metal holder sometimes used to protect markers from plow blades.

4. Classification

4.1 Markers shall be classified as to type, color, and intended application.

4.1.1 Types of Markers:

4.1.1.1 *Type A*—Two-way retroreflective markers, one color.

4.1.1.2 *Type B*—One-way retroreflective markers, one color.

4.1.1.3 *Type D*—One-way retroreflective markers, two colors (one-way retroreflective red with nonretroreflecting white surface on opposite side).

4.1.1.4 *Type E*—Two-way retroreflective marker, two colors.

4.1.2 Color of Markers:

4.1.2.1 *W*—White.

4.1.2.2 *Y*—Yellow.

4.1.2.3 *R*—Red.

4.1.2.4 *B*—Blue.

4.1.2.5 *G*—Green.

4.1.3 Intended Application of Markers:

4.1.3.1 Marker to be mounted in a holder.

4.1.3.2 Marker to be mounted in a recess.

4.1.4 Show classification in the order detailed in 4.1.1 through 4.1.3.2: type, color, and application.

4.2 Holders shall be classified as to the design installed height of the holder above the pavement.

5. Ordering Information

5.1 Orders for markers under this specification should include the following information:

5.1.1 Quantity,

5.1.2 Type of marker—Retroreflective one-way or retroreflective two-way, and

5.1.3 Color of marker.

5.2 Orders for holders under this specification should include the following information:

5.2.1 Design installed maximum height of the holder.

6. Construction Requirements for Retroreflective Markers

6.1 To withstand plowing, raised retroreflective markers are protected either by recessing within a groove below the pavement surface (see Appendix X1), mounting within a

holder having metal ramps to deflect plowblades, or by other methods approved by the purchaser.

6.2 Retroreflective Markers:

6.2.1 The retroreflective marker shall be the prismatic type molded of polymethyl methacrylate (Classification D 788, Grade 8), impact modified polymethyl methacrylate (Classification D 788, see Note 1) or polycarbonate (Specification D 3935, Grade PC110B34750.)

NOTE 1—A grade has not been stipulated because the committee responsible has not yet assigned a number.

6.2.2 The installed height of the marker shall be not less than 1.5 mm (0.06 in.) below the surface of the road for recessed type markers or below the top of the casting for plow blade deflecting type.

6.2.3 The marker width shall be approximately 102 mm (4 in.).

6.2.4 The angle between the face of the marker and the base shall be no greater than 45°.

6.2.5 Markers to be mounted in a holder may preferably be laminated to an elastomeric pad.

6.2.6 The base of the marker shall be flat within 1.3 mm (0.05 in.). If the bottom of the marker is configured, the outermost faces of the configurations shall not deviate more than 1.3 mm (0.05 in.) from a flat surface.

6.2.7 Other construction meeting the performance requirements will be acceptable following a six-month road test during the time of the year when weather and traffic conditions are most critical to determine cleanability and durability.

6.3 Holder:

6.3.1 The installed height of the holder shall not exceed 10.9 mm (0.43 in.) above the road surface.

6.3.2 The holder shall be nodular iron, conforming to Specification A 536, Grade 72-45-05, hardened to 51-55 HRC.

6.3.3 To minimize plow blade impact and damage to the casting, the plow blade deflecting ramps of the holder shall be angled not more than 6° to the surface of the road.

6.3.4 The ramps shall be so designed that there shall be no vertical surfaces above the road level that can be contacted by the plow blade moving in the normal travel direction of the road.

6.3.5 Surfaces of the holder shall be free of scale, dirt, rust, oil, grease, or any other contaminant which may reduce its bond to the adhesive with which the holder is installed or with which the marker is mounted.

6.3.6 The holder shall be designed to be partially recessed below the pavement surface to withstand plow impact.

6.3.7 Other holder constructions may be acceptable at the option of the purchaser following a six-month road test during the time of the year when weather conditions are most critical to determine durability.

7. Performance Requirements

7.1 *Coefficient of Luminous Intensity Before Abrasion*—Measured in accordance with 10.1 the coefficient of luminous intensity R_i of the retroreflective faces before abrasion shall be not less than the values in Table 1.

7.2 *Abrasion Resistance*—After abrasion in accordance with 10.2, the coefficient of luminous intensity R_i of the retroreflective faces measured in accordance with 10.1 shall

TABLE 1 Coefficient of Luminous Intensity R_i

NOTE—Entrance angle component β_1 and rotation angle ϵ are 0°.

Entrance Angle β_2	Observation Angle α	Minimum Value R_i , mcd/lx				
		White	Yellow	Red	Green	Blue
0°	0.2°	279	167	70	93	26
	0.2°	112	67	28	37	10
+20°/-20°	0.2°	3.0	1.8	0.75	1.0	0.28
	0.2°	1.2	0.72	0.3	0.4	0.11

be not less than the values in Table 1.

NOTE 2—On two-color units the red lens may not be covered with an abrasion-resistant lens surface and if so should not be abraded.

7.3 *Color*—When the retroreflector is illuminated by a CIE Standard Source A and when measured in accordance with 10.3, the color of the retroreflected light shall fall within the color gamuts given by the following corner points and shown in Fig. 1:

7.3.1 White

Point No.	x	y
1	0.310	0.348
2	0.453	0.440
3	0.500	0.440
4	0.500	0.380
5	0.440	0.380
6	0.310	0.283

7.3.2 Yellow

Point No.	x	y
1	0.545	0.424
2	0.559	0.439
3	0.609	0.390
4	0.597	0.390

7.3.3 Red

Point No.	x	y
1	0.650	0.330
2	0.668	0.330
3	0.734	0.265
4	0.721	0.259

7.3.4 Blue

Point No.	x	y
1	0.039	0.320
2	0.160	0.320
3	0.160	0.240
4	0.183	0.218
5	0.088	0.142

7.3.5 Green

Point No.	x	y
1	0.009	0.733
2	0.288	0.520
3	0.209	0.395
4	0.012	0.494

7.4 *Lens Impact Strength*—When impacted in accordance with 10.5.1 the face of the lens shall show no more than two radial cracks longer than 6.4 mm (0.25 in.). There shall be no radial cracks extending to the edge of the abrasion-resistant area. There shall be no delamination.

7.4.1 *Temperature Cycling*—When subjected to tempera-




FIG. 1 Color Gamut per 7.3

ture cycling in accordance with 10.5.2 there shall be no cracking or delamination.

7.5 Adhesive Bond Strength:

7.5.1 For markers intended to be installed in recesses, adhesive bond strength measured in accordance with 10.4.1 shall be not less than 3.4 MPa (500 psi). For adhesives other than those stipulated in 10.4.5 the strength criteria shall be established by the purchaser.

7.5.2 For markers installed in holders, adhesive bond strength measured in accordance with 10.4.2 shall be not less than 45.4 kg (100 lb).

7.5.3 For replacement markers not installed in holders, adhesive bond strength measured in accordance with 10.4.3 shall be not less than 0.08 MPa (12 psi).

7.6 *Compressive Strength*—Tested in accordance with 10.6, a marker shall support a load of 2721 kg (6000 lb) without breakage or significant deformation of the marker. Significant deformation shall be understood to be 3.2 mm (0.13 in.). For markers laminated to an elastomeric pad, remove the pad before testing.

7.7 *Ramp Hardness of Holders*—Measured in accordance with 10.7, the hardness of the ramps shall be 51-55 HRC.

8. Sampling

8.1 For markers supplied not mounted in holders, 26 markers selected at random will constitute a representative sample for each lot consisting of 10 000 markers or less. Forty markers will constitute a representative sample for lots consisting of more than 10 000 markers. The lot size shall not exceed 25 000 markers.

8.2 For markers supplied mounted in holders, the purchaser may require the sample quantities specified in 8.1 or, alternatively for practicality of testing, may require 10 samples of the markers installed in holders and, in addition, require that the manufacturer submit 26 or 40 loose markers,

as in 8.1, certified to be representative of the markers shipped in holders.

9. Number of Tests and Retests

9.1 For coefficient of luminous intensity before abrasion (7.1), the entire sample of retroreflective pavement markers shall be photometered in accordance with 10.1. The failure of more than 10 % of the retroreflective faces shall be cause for rejection of the entire lot represented by the sample.

9.2 For abrasion resistance (7.2), four retroreflective faces passing the photometric requirements of (7.1) shall be subjected to abrasion in accordance with 10.2 and rephotometered in accordance with 10.1; the failure of more than one retroreflective face shall be cause for rejection of the entire lot.

9.3 For adhesive bond strength (7.5), compressive strength (7.6), and color (7.3), three specimens shall be tested for each requirement. Specimens previously subjected to measurement of coefficient of luminous intensity before abrasion, 10.1, measurement of abrasion resistance, 10.2, and to color tests may be used for tests of adhesive bond strength and compressive strength. Failure of more than one specimen shall be cause for rejection of the lot.

9.4 For lens impact strength (7.4.1), resistance to temperature cycling (7.4.2), and ramp hardness of holders (7.7), ten specimens shall be tested for each requirement. Failure of more than one of the specimens in any one test shall be cause for rejection of the entire lot.

9.5 At the discretion of the purchaser, a resample may be taken consisting of double the number of samples originally taken. Tolerances for resamples shall be in the same ratio as specified in 9.1 through 9.4.

10. Test Methods


10.1 *Coefficient of Luminous Intensity*—Measure the coefficient of luminous intensity in accordance with Practice E 809 with high resolution angular aperture size in accordance with Table 1 of Practice E 809. Recommended dimensions are as follows: test distance 30.5 ± 0.06 m (100 ± 0.2 ft), receptor diameter 25.4 ± 0.5 mm (1.0 ± 0.02 in.), source diameter 25.4 ± 0.5 mm (1.0 ± 0.02 in.). Other test distances 15.2 m (50 ft) and above may be used provided that the angular aperture requirements are met. Measure the distance from the light source exit pupil to the center of the retroreflective face of the marker. Place the base of the marker on a plane parallel to the illumination axis ($\beta_1 = 0$) and perpendicular to the observation half plane ($\beta_2 = 0$). (See Practice E 809 and Fig. 2.)

10.1.1 If the markers are mounted in a holder photometer the markers in the holder, and if the holder shadows the retroreflective area divide the measured coefficient of luminous intensity by the ratio of the unshadowed retroreflective area to the total retroreflective area for comparison with Table 1.

10.2 *Determination of Abrasion Resistance*:

10.2.1 Select at random four retroreflective faces previously passing the photometric test of 10.1.

10.2.2 Place on the selected retroreflective face a 25.4 ± 5 -mm (1 ± 0.2 -in.) diameter flat pad of No. 3 coarse steel wool conforming to Federal Specification FF-W-1825A. Apply a



Location of retroreflector axis, datum axis and retroreflector center for use in testing raised pavement markers.

Retroreflector Center-located on the surface of the effective retroreflective area, centered both vertically and horizontally.

Retroreflector Axis-extends parallel to the road surface from retroreflector center.

Datum Axis-extends vertically from the road surface plane starting at retroreflector center.

FIG. 2 Position of Marker for Photometry

load of 22 ± 2 kg (50 ± 0.5 lb) and rub the entire surface 100 times.

10.2.3 Photometer in accordance with 10.1.

10.2.4 Remove markers mounted in a holder for abrasion and photometry after abrasion.

10.3 *Color*—Measure color in accordance with Practice E 811 at 0.2° observation angle and 0° entrance angle. The source and receptor angular aperture shall each be 6 min of arc.

10.4 *Adhesive Bond Strength*:

10.4.1 *For Markers Intended to Be Installed in Recesses*:

10.4.1.1 Measure adhesive bond strength in accordance with Sections 12 and 13 of AASHTO No. T 237 but substitute a pavement marker for the concrete block and a 25.4-mm (1.0-in.) diameter plug for the specified 50.8-mm (2.0-in.) plug. Position the pavement marker against a test plate having a hole through which the plug can be inserted and attached to a tensile member.

10.4.1.2 Adhesive used for test should conform to AASHTO No. M 237, Type 1.

10.4.1.3 Conditioning temperature for components shall be $23.0 \pm 2.0^\circ\text{C}$ ($73.4 \pm 3.6^\circ\text{F}$).

10.4.1.4 Cure the assembly for 24 h at $23.0 \pm 2.0^\circ\text{C}$ ($73.4 \pm 3.6^\circ\text{F}$).

10.4.1.5 Rate of loading shall be 5.1 mm (0.2 in.)/min.

10.4.2 *For Markers Installed in Holders*:

10.4.2.1 Adhere a 25.4-mm (1.0-in.) diameter pipe plug to the center of the top surface of the marker with epoxy conforming to AASHTO No. M 237, Table I. Allow 24 h

cure at $23.0 \pm 2.0^\circ\text{C}$ ($73.4 \pm 3.6^\circ\text{F}$).

10.4.2.2 Position the holder against a test plate having a hole through which the plug can be inserted and attached to a tensile member. The hole shall be large enough that it will permit the marker to pass through.

10.4.2.3 Determine force required to separate the marker from the holder at a rate of loading of 5.1 mm (0.2 in.)/min.

10.4.3 *For Replacement Markers Not Installed in Holders*:

10.4.3.1 Remove release paper (if present) from the bottom of the marker. Apply manufacturer-approved adhesive to the face of a sand blasted 25.4-mm (1.0-in.) steel test plug and position the plug on the center of the marker. Apply a compressive force of 75 lb to the test plug for 6 s.

10.4.3.2 Cure 72 h at $23 \pm 2^\circ\text{C}$ ($73.4 \pm 3.6^\circ\text{F}$).

10.4.3.3 Cut through the adhesive along the circumference of the test plug to limit the area of the adhesive to be tested.

10.4.3.4 Attach the test plug and marker to the platens of a tensile machine and separate the platens at a rate of 5.1 mm (0.2 in.)/min.

10.4.3.5 Conditioning temperature for components shall be $23 \pm 2^\circ\text{C}$ ($73.4 \pm 3.6^\circ\text{F}$).

10.4.4 *Source of Error*:

10.4.4.1 Variation in thickness of epoxy has been found to influence test results.

10.4.4.2 Lack of parallelism of surfaces of test plug and marker can result in low readings.

10.4.4.3 Variations in adhesive used for testing the marker will affect the test results.

10.4.5 *Precision and Bias*:

10.4.5.1 Since the test is destructive, correlation is affected by differences between test samples. Variations of 20 % within a given lot of markers may be expected.

10.4.5.2 No formal interlaboratory data on precision and accuracy are available. A correlation study to develop these data is planned.

10.5 *Resistance to Lens Cracking*:

10.5.1 Separate markers laminated to an elastomeric pad from the pad before testing.

10.5.2 *Lens Impact Strength*—Condition the markers in a convection oven at 55°C (130°F) for 1 h.

10.5.2.1 While at the elevated temperature, impact the reflective face of the marker by allowing a 190-g (0.42-lb) dart fitted with a 6.4-mm (0.25-in.) radius semispherical head to drop 457 mm (18 in.) perpendicularly onto the approximate center of the reflective surface. For impact testing, set the marker on a steel fixture designed to hold the reflecting face horizontal, and place the fixture on a solid

surface such as a concrete floor.

NOTE 3—Markers laminated to an elastomeric pad shall be separated from the pad before testing.

10.5.2.2 Inspect for cracking and delamination.

10.5.3 *Resistance to Temperature Cycling*—Subject samples to 3 cycles of 60°C (140°F) for 4 h followed by -7°C (20°F) for 4 h.

10.5.3.1 Inspect for cracking and delamination.

10.5.4 *Precision and Bias*—No statement is made about either the precision or bias of the test for resistance to lens cracking since the result merely states whether there is conformance to the criteria for success specified in the procedure.

10.6 *Compressive Strength*:

10.6.1 Condition markers at $23.0 \pm 2.0^\circ\text{C}$ ($73.4 \pm 3.6^\circ\text{F}$) for 4 h prior to testing.

10.6.2 Position marker base down at the center of a 13-mm (0.5-in.) thick flat steel plate larger than the marker.

10.6.3 On top of the marker place a 9.5-mm (0.375-in.) thick elastomeric pad larger than the marker and having a shore A durometer of 60.

10.6.4 On top of the elastomeric pad place a 13 mm (0.5 in.) thick flat steel plate larger than the marker.

10.6.5 Apply a load at a rate of 2.5 mm (0.1 in.)/min.

NOTE 4—Markers laminated to an elastomeric pad shall be separated from the pad before testing.

10.7 *Holder Ramp Hardness Test*:

10.7.1 Prepare spot for test on horizontal surface of ramp close to angled portion by using a hand grinder to remove only a slight amount of metal to smooth surface.

10.7.2 Place the holder in a Rockwell hardness tester with ramps facing upward, and position the holder on the flat anvil of the tester with the smooth area below the indenter.

10.7.3 Check hardness at three locations approximately 1.5 mm (0.06 in.) apart on smooth area, and average the three readings to obtain the hardness.

11. Packaging

11.1 Shipments shall be made in containers which are acceptable to common carriers and packaged in such a manner as to ensure delivery in perfect condition. Any damaged shipments shall be replaced by the contractor. Each package shall be clearly marked as to the name of the manufacturer, type, color, quantity enclosed, and date of manufacture.

12. Keywords

12.1 delineation; plowable markers; raised pavement markers; retroreflective markers

ANNEX

(Mandatory Information)

A1. SPECIFICATION FOR BITUMINOUS ADHESIVE FOR PAVEMENT MARKERS

A1.1 Scope

A1.1.1 This specification establishes the requirements for bituminous installation adhesive to be used for placement of recessed, raised, retroreflective pavement markers. The adhesive shall be suitable for bonding the above markers to portland cement concrete, asphaltic concrete, and chip sealed road surfaces and applicable when road surface and marker temperatures are in the range from 4.4 to 71°C (40 to 160°F). The adhesive properties will not deteriorate when heated to and applied at temperatures up to 218°C (425°F) using either air or oiljacketed melters.

A1.2 General Properties of Adhesive

A1.2.1 The bituminous installation adhesive is an asphaltic material with a homogeneously mixed mineral filler. The adhesive shall not contain rubber polymers since necessary application temperatures cause decomposition, resulting in unsatisfactory performance. The adhesive shall conform to the following requirements:

Property	Minimum	Maximum	Test Method
Softening point, °C (°F)	93 (200)	110 (230)	D 36
Penetration mm × 10 ⁻¹	10	18	D 5
Flow, mm (in.)	—	5.1 (0.2)	D 3407, as modified in A1.4.1
Heat stability flow, mm (in.)	—	5.1 (0.2)	As in A1.4.2
Viscosity, 204°C (400°F), P	30	75	D 2669, as modified in A1.4.3, or D 4402
Flash point, C.O.C., °C (°F)	288 (550)	—	D 92
Shelf life, years	—	2	—

A1.3 General Properties of Filler-Free Material and of Filler Alone

A1.3.1 Asphalt properties determined on the filler-free material derived from the extraction and Abson recovery process as explained in X2.4.4 are as follows:

Property	Minimum	Maximum	Test Method
Penetration, 100 g, 5 s, 25°C (77°F)	25	—	D 5
Viscosity, 135°C (275°F), P	12	100	D 2171
Viscosity ratio, 135°C (275°F)	—	2.2	As explained in A1.4.5

A1.3.2 Filler properties determined using the filler separation technique described in A1.4.6 are as follows:

Property	Minimum	Maximum	Test Method
Filler content, % by weight	65	75	As in A1.4.6
Filler fineness, % passing			
45 µm (No. 325) sieve	75	—	C 430
75 µm (No. 200) sieve	95	—	C 184
150 µm (No. 100) sieve	100	—	C 184

A1.4 Test Methods

A1.4.1 Flow shall be determined in accordance with

Section 6 of Test Methods D 3407 with the exception that the oven temperature shall be 70 ± 1°C (158 ± 2°F) and sample preparation shall be in accordance with 7.1 of Test Method D 5.

A1.4.2 Heat stability flow shall be determined in accordance with Section 6 of Test Methods D 3407 with the exception that 1000 g of adhesive shall be placed in a covered quart can, heated to 218°C (425°F) and maintained at this temperature for 4 h prior to preparing the sample panel (6.1).

A1.4.3 Determine viscosity in accordance with Test Methods D 2669 or D 4402. If using Test Method D 2669, use a spindle speed of 10 r/min, and heat the adhesive to approximately 210°C (410°F) and allow to cool; determine viscosity at 204.4 ± 0.5°C (400 ± 1°F). If using Test Method D 4402, the test method describes the spindle and speed to be used with various models.

A1.4.4 Properties of the base asphalt are to be determined on the material obtained from the following extraction and Abson recovery methods. The asphalt shall be extracted by heating the adhesive just to the point where it will easily flow and then transferring 125 to 150 g into 400 mL of trichloroethylene with a temperature of 52 to 65°C (125 to 150°F). This mixture shall be thoroughly stirred to dissolve the asphalt. The trichloroethylene asphalt mixture shall be decanted and the asphalt shall be recovered using the Abson recovery methods, Test Method D 1856, as modified by the following. The extraction methods of Test Method D 2712 shall not apply and there shall be no filtration of the solvent-asphalt mixture. The extraction solution of trichloroethylene and asphalt shall be centrifuged for at least 30 min at 770 times gravity in a batch centrifuge. A continuous centrifuge can be used if the extract solution is charged at a rate not to exceed 150 mL/min while the unit is operating at a speed calculated to produce a centrifuge force of not less than 3000 times gravity, as specified in 9.2 of Test Method D 1856. Decant this solution into the distillation flask, taking care not to include any filler sediment. Apply heat and bubble carbon dioxide slowly to bring the solution temperature to 149°C (300°F). At this point, the carbon dioxide flow is increased to 800 to 900 mL/min. The solution temperature is maintained at 160 to 168°C (320 to 335°F) with this carbon dioxide flow rate for at least 20 min and until the trichloroethylene vapors have been completely removed from the distillation flask. The above extraction-recovery method shall be repeated as necessary to obtain the desired quantity of asphalt. The asphalt recovered shall be used to determine penetration, 135°C (275°F) viscosity, and 135°C (275°F) viscosity ratio.

A1.4.5 The 135°C (275°F) viscosity ratio shall be determined by comparing the 135°C (275°F) viscosity on the base asphalt before and after the Thin-Film Oven Test. The Thin-Film Oven Test shall be performed in accordance with Test Method D 1754. The specific gravity shall be deter-

mined by pycnometer in accordance with Test Method D 70 for use in the Thin-Film Oven Test. The 135°C (275°F) viscosity ratio shall be calculated by dividing the viscosity after the Thin-Film Oven Test by the original 135°C (275°F) viscosity.

A1.4.6 To determine the filler content, use the data from the separation described in A1.4.4. The samples used for the asphalt recovery are weighed before the extractions. The extracted filler is weighed after extraction. The bitumen is determined by difference.

A1.4.7 Determine the fineness of the filler according to Test Method C 430 for material finer than the 45 µm (No. 325) sieve. Using a second test sample, determine the

percentage of the material passing the 150 µm (No. 100) and 75 µm (No. 200) sieve according to Test Method C 184.

A1.5 Packaging and Labeling

A1.5.1 The adhesive shall be packaged in self-releasing cardboard containers that will stack properly. The containers shall be divided into compartments so that four equal individual parts are obtained from each container. The containers shall have a net weight of approximately 25 kg (55 lb). The label for the container shall clearly show the manufacturer, quantity, lot or batch number, and an indication that the material is bituminous adhesive for pavement markers.

APPENDIX

(Nonmandatory Information)

X1. STORAGE, PLACEMENT, AND INSTALLATION OF PLOWABLE RAISED PAVEMENT MARKERS

X1.1 Storage

X1.1.1 Markers should be stored indoors and should be protected from any source of moisture both during shipment to the jobsite and at the jobsite. The markers should be maintained at a high enough temperature as to preclude moisture condensation, and, at the time of placement, both the markers and their containers should be dry.

X1.2 Placement of Plowable Markers

X1.2.1 Before beginning pavement marker application, the contractor should accurately and adequately lay out, by reference points, the location of all pavement markers to ensure their proper placement. Pavement markers should not be placed on pavement surfaces that show visible evidence of cracking, checking, spalling, or failure of underlying base material. If, during the pre-installation layout operation, it is determined that a marker would be placed at a point with one of the aforementioned pavement surface defects or at a pavement construction joint or within the intersection of a driveway or public street as a result of typical marker spacing, the affected marker should be relocated longitudinally a sufficient distance to a point approved by the engineer. The distance the marker may be relocated should not exceed 10 % of the typical marker spacing. Where it would be necessary to relocate the marker a distance greater than 10 % of the typical marker spacing, the affected marker should be deleted. The reflective face of the marker should be perpendicular to a line parallel to the roadway centerline.

X1.3 Installation of Plowable Markers of the Plow Blade Deflecting Type

X1.3.1 At the time of installation, the pavement marker holder should be free of dirt, dust, oil grease, rust, moisture, or any foreign matter that will impair adhesion to the pavement. It should be the contractor's responsibility to clean each contaminated holder by sand blasting or other acceptable procedure to remove all such foreign matter prior to installation.

X1.3.2 The pavement should be machined to match the bottom contour of the marker holder. The holders should be installed within seven days after the slots are cut into the pavement.

X1.3.3 The adhesive should be an epoxy adhesive complying with the formulations given in Table X1.1.

X1.3.4 The epoxy adhesive should be mixed by combining components A and B in a ratio of 1:1 by volume. The epoxy adhesive requires that the mixing operation and placing of the pavement markers be done rapidly. Any mixed batch that becomes so viscous that it cannot be readily extruded from under the holder under light pressure should not be used. The adhesive should be maintained at 15 to 27°C (60 to 80°F) before mixing. Any heating of the epoxy should be by the application of indirect heat. The adhesive should not be heated above 49°C (120°F).

X1.3.5 During installation of the holders with epoxy adhesive, the ambient temperature and pavement temperature should be at least 10°C (50°F).

X1.3.6 Before installing the markers, the recesses should be brushed or blown clean of loose material and should be dry. Sufficient epoxy should be placed in the recess to ensure that all voids beneath and around the holder are filled so as to create a watertight seal around the holder. The holder should be hand placed into the recess in such a manner as to ensure that the tips of the holder's snowplow deflecting surface(s) are below the pavement surface.

TABLE X1.1 Epoxy Adhesive Formulation

Components	Parts By Weight
Component A:	
Epoxy resin (EPON 828 or equal)	100.0
Titanium dioxide	8.0
No. 13 talc	37.0
Component B:	
N-Aminoethyl piperazine (Jefferson or equal)	25.0
Nonyl phenol	50.0
Talc (Fiberline C-400, Sierra or equal)	70.0
Molacco Black	0.12
Cabasil ^a	0.5

^a Cabasil was added to inhibit settling.

X1.4 Installation of Recessed Plowable Markers

X1.4.1 Recommended Dimensions of Groove for Recessed Markers:

X1.4.1.1 Groove length should be 1.1 m (42 in.) minimum from leading edge of the reflective marker to the beginning of the groove.

X1.4.1.2 Groove depth should be sufficient to accommodate the reflective marker with the top of the marker flush with or recessed to 1.5 mm (0.06 in.) below the pavement surface.

X1.4.1.3 Groove bottom may parallel the pavement surface or be tapered.

X1.4.2 Application of Recessed Plowable Markers:

X1.4.2.1 Before installing markers the recesses should be brushed or blown clean of loose material and should be dry.

X1.4.2.2 The marker should be positioned with its top surface flush to 1.5 mm (0.06 in.) below the pavement surface.

X1.4.2.3 Markers should be cemented to the pavement with Rapid Set Type adhesive conforming to AASHTO No. M 237, Type 1, Standard Set Type adhesive conforming to AASHTO No. 237, Type 2, or with bituminous adhesive corresponding to the requirements of Annex A1. The engineer should be the judge as to when Rapid Set Type adhesive has set sufficiently to bear traffic. If rapid set adhesive is to be used the engineer should determine that deterioration of the adhesive caused by accumulated water will not be a problem.

X1.4.2.4 Regardless of the type of adhesive used, markers should not be placed under the following conditions:

(1) When either the pavement or the air temperature is 0°C (32°F) or less when using rapid set epoxy, 10°C (50°F) or less when using standard set epoxy or 4.4°C (40°F) or less when using bitumen.

(2) If the relative humidity of the air is greater than 80 %.

(3) If the pavement is not surface dry.

(4) On new asphalt concrete surfacing until the surfacing has been opened to public traffic for a period of not less than 14 days.

X1.4.2.5 The adhesive should be placed uniformly on the groove surface or on the bottom of the marker in a quantity sufficient to result in complete coverage of the area of contact of the marker with no voids present and with a slight excess after the marker has been pressed in place. The marker should be placed in position and pressure applied until the top surface of the marker is flush with the pavement surface. Excessive adhesive around the edge of the marker, excess adhesive on the pavement, and adhesive on the exposed surfaces of the markers should be immediately removed. Soft rags moistened with mineral spirits conforming to Federal Specification TT-T-291 or kerosine may

be used, if necessary, to remove adhesive from exposed faces of pavement markers. No other solvent should be used. The marker should be protected against impact until the adhesive has hardened to the degree designated by the engineer.

X1.4.2.6 The adhesive requires that the mixing operation and placing of the markers be done rapidly. When hand mixing the Standard Set Type adhesive, not more than 1 L (1 qt), and the markers should be aligned and pressed into place within 5 min after mixing operations are started. Any mixed batch which becomes so viscous that the adhesive cannot be readily extruded from under the marker on application of slight pressure should not be used. Rapid Set Type adhesive should not be mixed by hand.

X1.4.2.7 The Rapid Set Type adhesive should be mixed by a two-component type automatic mixing and extrusion apparatus. When machine mixing the Standard Set Type adhesive or the Rapid Set Type adhesive, the markers should be placed within 60 s after the adhesive has been mixed and extruded and no further movement of the marker should be allowed. In addition, no more than 90 s should be permitted between the time the adhesive is pumped into the mixing head and the time this adhesive is in place on the roadway and not subject to further movement. The mixed adhesive should not remain in the mixing head for more than 45 s. Adhesive remaining in the mixing head longer than this period should be wasted before resuming the operation. Automatic mixing equipment for the epoxy adhesive should use positive displacement pumps and should properly meter the 2 components in the specified ratio, ± 5 % by volume of either component. At the beginning of each day and at any other time ordered by the engineer, the ratio should be checked by the contractor in the presence of the engineer. This check should be made by disconnecting the mixing heads, or using suitable bypass valves, and filling two suitable containers with the unmixed components. The mixing head should properly mix the two components so that there is no trace of black or white streaks in the mixed material.

X1.4.2.8 Voids in a cured, undisturbed sample of the mixed adhesive obtained from the extrusion nozzle should not exceed 4 %.

X1.4.2.9 Bituminous adhesive should be dispensed from a thermostatically controlled melter-aplicator at a temperature of 191 to 218°C (375 to 425°F). The adhesive should be stirred frequently to ensure even heating. The adhesive should be dispensed in a puddle larger than the bottom of the marker, and the marker should be dropped onto the puddle as quickly as possible, preferably within 5 s of adhesive placement. The marker should be pressed lightly onto the adhesive. The adhesive will set up in approximately 2 min and typically requires no protection from traffic.

The American Society for Testing and Materials takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, 100 Barr Harbor Drive, West Conshohocken, PA 19428.

Standard Practice for Calculating Precision Limits Where Values are Calculated from Other Test Methods¹

This standard is issued under the fixed designation D 4460; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This practice describes techniques for calculating precision limits when values are calculated from two other methods having precision limits.

1.2 *This standard does not purport to address all of the safety problems, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Referenced Documents

- 2.1 *ASTM Standards:*
D 1188 Test Method for Bulk Specific Gravity and Density of Compacted Bituminous Mixtures Using Paraffin-Coated Specimens²
D 2041 Test Method for Theoretical Maximum Specific Gravity of Bituminous Paving Mixtures²
D 3203 Test Method for Percent Air Voids in Compacted Dense and Open Bituminous Paving Mixtures²
E 177 Practice for Use of the Terms Precision and Bias in ASTM Test Methods³

3. Definitions

3.1 For definitions of terms used in this document, consult Practice E 177, or a standard dictionary, or a statistical text from Refs. (1, 2, and 3).⁴

4. Significance and Use

4.1 Precision limits for a test result which is calculated by addition, subtraction, multiplication, or division of two other test results that have valid precision limits can be calculated directly. This saves the cost and delay of conducting an interlaboratory study.

4.2 At the heart of statistical theory is the concept of a frequency distribution of a random variable. The precision limit of the random variable is determined by the standard deviation of the variable. The standard deviation of a random variable that is the sum, difference, product, or

quotient of two other random variables can be calculated simply so long as the individual variables are independent and the standard deviations are small relative to their mean values. These restrictions are usually met in ASTM methods. In those cases where these restrictions are not met, other methods can be used. Only cases complying with the restrictions are covered in this standard.

5. Procedure

5.1 The standard deviation on which precision limits for a test result are based can be calculated from the following equations:

$$\sigma_{x \pm y} = \sqrt{\sigma_x^2 + \sigma_y^2} \quad (1)$$

where:

$\sigma_{x \pm y}$ = standard deviation for determining precision limits of a test result for a new standard based on either an addition or subtraction of test results from two other standards,

σ_x = standard deviation from precision statement of one of the standards on which new standard is based, and

σ_y = standard deviation from precision statement of other standard on which new standard is based.

The distributions of the test results from the two standards should be independent.

$$\sigma_{xy} = \sqrt{\bar{y}^2 \sigma_x^2 + \bar{x}^2 \sigma_y^2} \quad (2)$$

where:

σ_{xy} = standard deviation for determining precision limits of test results for a new standard based on the products of two other test results from two other standards,

σ_x = standard deviation from precision statement of one of the standards on which new standard is based,

$\bar{x}$ = mean or average value of X variable,

σ_y = standard deviation from precision statement of other standard on which new standard is based, and

$\bar{y}$ = mean or average value of Y variable.

$$\sigma_{\frac{x}{y}} = \sqrt{\frac{\bar{y}^2 \sigma_x^2 + \bar{x}^2 \sigma_y^2}{\bar{y}^4}}$$

where

$\sigma_{\frac{x}{y}}$ = standard deviation for determining precision limits of test results for a new standard based on the quotient of two test results from two other standards.

$\sigma_x, \sigma_y, \bar{x}, \bar{y}$ = definitions given above.

An example in Appendix X1. illustrates how the equations are applied.

¹ This practice is under the jurisdiction of ASTM Committee D-4 on Road and Paving Materials and is the direct responsibility of Subcommittee D04.94 on Statistical Procedures and Evaluation of Data.

Current edition approved Feb. 22, 1985. Published October 1985.

² Annual Book of ASTM Standards, Vol 04.03.

³ Annual Book of ASTM Standards, Vol 14.02.

⁴ The boldface numbers in parentheses refer to the list of references at the end of this standard.

APPENDIX 2



CATALOG

1. Annual book of ASTM standards.

LCCN	83641658
Type of material	Periodical or Newspaper
Corporate name	American Society for Testing and Materials.
Main title	Annual book of ASTM standards.
Published/Created	Philadelphia, Pa. : ASTM, ©1970-©2001.
Publication history	1970-2001.
Description	32 volumes : illustrations ; 24 cm Each vol. issued in parts.
Current frequency	Annual
ISSN	0192-2998
Linking ISSN	0192-2998
LC classification	TA401 .A653
Continues	American Society for Testing and Materials. Book of ASTM standards 0195-783X (DLC) 80000635 (OCoLC)5829001
Continued by	ASTM International. Annual book of ASTM standards (DLC) 2003223650 (OCoLC)52526499
Variant title	Annual book of American Society for Testing and Materials standards
Portion of title	Annual book of A.S.T.M. standards Annual A.S.T.M. standards ASTM standards
Spine title	Annual ASTM standards
Serial key title	Annual book of ASTM standards
Abbreviated title	Annu. book ASTM stand.
LC Subjects	Materials--Standards--United States--Periodicals. Materials--Testing--Standards--United States--Periodicals.
Other Subjects	Materials--Standards. Materials--Testing--Standards. ASTM-Standard ASTM-Standard. United States.
Form/Genre	Standards, Engineering. Reference works. Periodicals. Zeitschrift Reference works.
Notes	Published in: Conshohocken, PA, <1996->; West Conshohocken, PA, -2001.
Indexed by	Chemical abstracts 0009-2258
Indexes	Index to ASTM standards issued as last part of each vol.
Reproduction no./Source	ASTM, 100 Barr Harbor Drive, West Conshohocken, PA 19428
Additional formats	Also issued online. Online version: American Society for Testing and Materials. Annual book of ASTM standards (OCoLC)567458226
CODEN	ABASCV
Dewey class no.	620.1/1/0218

Geographic area code n-us---
NAL class no. 290.9 Am34S
National bib agency no. 01106076X
191306-2
015272191
Other system no. (OCoLC)ocm02187052
Invalid LCCN sn 79009540 82647297 82647125
Content type text
Media type unmediated
Carrier type volume
Source of description Latest issue consulted: 2001, vol. 7.02.

CALL NUMBER TA401 .A653
Set 1

Request in Jefferson or Adams Building Reading Rooms

Older receipts 1977:00.01, 1986:v.7.01-1986:v.7.02
1997:sec.01.01-1999:sec.02.09, 1999:sec.03.03, 1999:sec.3.05-1999:sec.03.06,
1999:sec.04.02-1999:sec. 07.01,
1999:sec.08.02, 1999:08.04, 1999:sec.10.01-03- 1999:sec.10.05, 1999:sec.11.01,
1999:sec.11.03-11.05, 1999:sec.14.01-2000:sec.01.06
1999:01:01-1999:01-02, 1999:01:05, 1999:04.08, 1999:07.01-07.02
1998:03:03
2000:v.01:01-2000:v.01.08
2000:v.02.01-2000:v.02.05
2000:v.03.01-2000:v.03.06
2000:v.04.01-2000:v.04:05, 2000:v.04.08, 2000:v.04.10-2000:v.04.11
2000:v.05.01-2000:v.04:06
2000:v.06.01-2000:v.06.03
2000:v.07.01-2000:v.07.02
2000:v.08.01-2000:v.08.04
2000:v.09.01-2000:v.09.02
2000:v.10:01-2000:v.10:05
2000:v.11.01-2000:v.11.03, 2000:v.11.05
2000:v.12.01-2000:v.12.02
2000:v.13.01
2000:v.14.01-2000:v.14.02
2000:v.15.01-2000:v.15.02, 2000:v.15.04-2000:15.06
2001:v.00.01
2001:v.01.01-2001:v.01-08
2001:v.02.01-2001:v.02.02, 2001:v.02.04-2001:v.02.05
2001:v.03.01-2001:v.03.06
2001:v.04.01-v.04.07, 2001:v.04.09-2001:v.04.11
2001:v.05.01-2001:v.05.03, 2001:v.05.05-2001:v.05.06
2001:v.06.01-2001:v.06.02, 2001:v.06.04
2001:v.07.01-2001:v.07.02
2001:v.08.01, 2001:v.08.03-2001:v.08.04
2001:v.09.01-2001:v.09.02
2001:v.10.01-2001:v.10.03
2001:v.11.01-2001:v.11.05
2001:v.12.01-2001:v.12.02
2001:v.13.01
2001:v.14.01, 2001:v.14.03-2001:v.14.04
2001:v.15.02-2001:v.15.09,
1977:00.01, 1986:v.7.01-1986:v.7.02
1997:sec.01.01-1999:sec.02.09, 1999:sec.03.03, 1999:sec.3.05-1999:sec.03.06,
1999:sec.04.02-1999:sec. 07.01,
1999:sec.08.02, 1999:08.04, 1999:sec.10.01-03- 1999:sec.10.05, 1999:sec.11.01,
1999:sec.11.03-11.05, 1999:sec.14.01-2000:sec.01.06
1999:01:01-1999:01-02, 1999:01:05, 1999:04.08, 1999:07.01-07.02
1998:03:03

2000:v.01:01-2000:v.01.08
2000:v.02.01-2000:v.02.05
2000:v.03.01-2000:v.03.06
2000:v.04.01-2000:v.04.05, 2000:v.04.08, 2000:v.04.10-2000:v.04.11
2000:v.05.01-2000:v.04:06
2000:v.06.01-2000:v.06.03
2000:v.07.01-2000:v.07.02
2000:v.08.01-2000:v.08.04
2000:v.09.01-2000:v.09.02
2000:v.10:01-2000:v.10:05
2000:v.11.01-2000:v.11.03, 2000:v.11.05
2000:v.12.01-2000:v.12.02
2000:v.13.01
2000:v.14.01-2000:v.14.02
2000:v.15.01-2000:v.15.02, 2000:v.15.04-2000:15.06
2001:v.00.01
2001:v.01.01-2001:v.01-08
2001:v.02.01-2001:v.02.02, 2001:v.02.04-2001:v.02.05
2001:v.03.01-2001:v.03.06
2001:v.04.01-v.04.07, 2001:v.04.09-2001:v.04.11
2001:v.05.01-2001:v.05.03, 2001:v.05.05-2001:v.05.06
2001:v.06.01-2001:v.06.02, 2001:v.06.04
2001:v.07.01-2001:v.07.02
2001:v.08.01, 2001:v.08.03-2001:v.08.04
2001:v.09.01-2001:v.09.02
2001:v.10.01-2001:v.10.03
2001:v.11.01-2001:v.11.05
2001:v.12.01-2001:v.12.02
2001:v.13.01
2001:v.14.01, 2001:v.14.03-2001:v.14.04
2001:v.15.02-2001:v.15.09,

CALL NUMBER	TA401 .A653 Set 2
Request in	Jefferson or Adams Building Reading Rooms
Older receipts	1979:pt.45-2001:pt.15.06 1979:pt.45-2001:pt.15.06

CALL NUMBER	TA401 .A653 Set 3
Request in	Jefferson or Adams Building Reading Rooms
Older receipts	2001:pt.04.05 2001:pt.04.05

CALL NUMBER	TA401 .A653 sect. 04 Section 04--Construction Set 1 Latest edition only
Request in	Jefferson or Adams Building Reading Rooms
Older receipts	2016:v.04.02 2016:v.04.02

LC CATALOG
Library of Congress
101 Independence Ave., SE
Washington, DC 20540

Questions? Ask a Librarian:
<https://ask.loc.gov/>

APPENDIX 3

LIBRARY

CATALOG

[Search Navigation](#) ▼

3 of 3



PERIODICAL OR NEWSPAPER

Annual book of ASTM standards

[Full Record](#)[MARC Tags](#)

000 04623cas a2200985 a 4500
001 11271378
005 20231217095210.0
008 760521d19702001pauar 0 a0eng
010 — |a 83641658 |z sn 79009540 |z 82647297 |z 82647125
016 7_ |a 01106076X |2 DE-101
016 7_ |a 191306-2 |2 DE-600
016 7_ |a 015272191 |2 Uk
022 0_ |a 0192-2998 |l 0192-2998 |2 1
030 — |a ABASCV
035 — |a (OCoLC)ocm02187052
037 — |b ASTM, 100 Barr Harbor Drive, West Conshohocken, PA 19428
040 — |a DLC |b eng |c UDI |d COO |d NSD |d MUL |d DLC |d NST |d DLC |d OCL |d NSD |d AIP |
d NST |d AIP |d OCL |d NST |d CRL |d GUA |d NST |d NSD |d NST |d AGL |d IUL |d OCL |d
OCLCQ |d CLU |d DLC |d OCLCQ |d LVB |d OCLCQ |d HEBIS |d DEBBG |d GBVCP |d UK
MGB |d OCLCQ |d CUI |d OCLCF |d OCLCO |d OCLCQ |d GUA |d ORZ |d I8M |d OCLCO |
d OCLCQ |d OKS |d OCLCO |d XFF |d OCLCO |d CSA |d OCLCO |d OCLCA |d CPO |d OC
LCQ |d OCLCO |d XFF |d DCHUA |d OCL |d OCLCO |d MNU |d OCLCO |d BUF |d OCLCO |
d GU1 |d OCLCL
042 — |a pcc |a nsdp
043 — |a n-us---
050 00 |a TA401 |b .A653
070 0_ |a 290.9 |b Am34S
072 _0 |a X000

082	04	a 620.1/1/0218 2 19
110	2_	a American Society for Testing and Materials.
210	0_	a Annu. book ASTM stand.
222	_0	a Annual book of ASTM standards
245	10	a Annual book of ASTM standards.
246	3_	a Annual book of American Society for Testing and Materials standards
246	30	a Annual book of A.S.T.M. standards
246	30	a Annual A.S.T.M. standards
246	18	a Annual ASTM standards
246	30	a ASTM standards
249	0_	i ACQUIRE Title: a Annual book of ASTM standards subject index; alphanumeric list
260	—	a Philadelphia, Pa. : b ASTM, c ©1970-©2001.
300	—	a 32 volumes : b illustrations ; c 24 cm
310	—	a Annual
336	—	a text b txt 2 rdacontent
337	—	a unmediated b n 2 rdamedia
338	—	a volume b nc 2 rdacarrier
362	0_	a 1970-2001.
500	—	a Published in: Conshohocken, PA, <1996->; West Conshohocken, PA, -2001.
510	0_	a Chemical abstracts x 0009-2258
515	—	a Each vol. issued in parts.
530	—	a Also issued online.
555	—	a Index to ASTM standards issued as last part of each vol.
588	—	a Latest issue consulted: 2001, vol. 7.02.
590	—	a SERBIB/SERLOC merged record
592	—	a ACQN: aq 98013125
650	_0	a Materials x Standards z United States v Periodicals.
650	_0	a Materials x Testing x Standards z United States v Periodicals.
650	_5	a Normes techniques.
650	_5	a Matériaux x Essais x Normes z États-Unis v Périodiques.
650	_5	a Normalisation z États-Unis.
650	_6	a Ingénierie x Associations.
650	_6	a Matériaux x Essais.
650	_6	a Construction x Matériaux x Essais.
650	_6	a Résistance des matériaux.
650	_7	a Materials x Standards. 2 fast 0 (OCoLC)fst01011874
650	_7	a Materials x Testing x Standards. 2 fast 0 (OCoLC)fst01011890

651	_7	a United States. 2 fast 0 (OCoLC)fst01204155 1 https://id.oclc.org/worldcat/entity/E39PBJtxgQXMWqmjMjjwXRHgrq
650	_7	a ASTM-Standard 2 gnd
650	07	a ASTM-Standard. 2 swd
655	_0	a Standards, Engineering.
655	_7	a Reference works. 2 fast 0 (OCoLC)fst01919963
655	_7	a Periodicals. 2 fast 0 (OCoLC)fst01411641
655	_7	0 (DE-588)4067488-5 a Zeitschrift 2 gnd-content
655	_7	a Reference works. 2 lcgft
776	08	i Online version: a American Society for Testing and Materials. t Annual book of ASTM standards w (OCoLC)567458226
780	00	a American Society for Testing and Materials. t Book of ASTM standards x 0195-783X w (DLC) 80000635 w (OCoLC)5829001
785	00	a ASTM International. t Annual book of ASTM standards w (DLC) 2003223650 w (OCoLC)52526499
850	—	a AzU a CU a CU-RivP a CU-S a CU-SB a CaAEU a CaNBSU a CaOTU a CaSSU a CoFS a DLC a DNAL a DNGA a DeU a FU a GU a IC a ICRL a InU a KMK a MnSU a NBuU-SE a NNC a NSyU a NcRS a NvU a OU a OkU a P a PPD a TxCM a TxDaM
853	20	8 1 a (year) w a
863	41	8 1.1 a 1993
890	—	a Annual book of ASTM standards (American Society for Testing and Materials) Philadelphia, Pa. i 83-641658
906	—	a 7 b cbc c serials d 3 e ncip f 19 g n-oclcserc
920	—	a Keep 1
991	—	b c-GenColl h TA401 i .A653 w SERIALS
991	—	b c-GenColl h TA401 i .A653 p 0003633485A t Copy 1 v 11.01 w CCF
991	—	b c-GenColl h TA401 i .A653 p 00036334629 t Copy 1 v 11.02 w CCF
991	—	b c-GenColl h TA401 i .A653 p 00036334587 t Copy 1 v 11.03 w CCF
991	—	b c-GenColl h TA401 i .A653 p 00054068542 t Copy 1 v 9:2 w CCF
991	—	b r-SciRR w ACQUIRE
991	—	b r-SciRR h TA401 i .A653 t Copy 1 w GenBib bi 89-011376
992	—	b 93000584 w ACQUIRE
992	—	b call x7-5305 w SERLOC

[Request this Item](#)
[LC Find It](#)

Item Availability



CALL NUMBER

TA401 .A653

Set 1

Request in

Jefferson or Adams Building Reading Rooms

Status

Not Charged

Older receipts

1977:00.01, 1986:v.7.01-1986:v.7.02
1997:sec.01.01-1999:sec.02.09, 1999:sec.03.03, 1999:sec.3.05-
1999:sec.03.06, 1999:sec.04.02-1999:sec. 07.01,
1999:sec.08.02, 1999:08.04, 1999:sec.10.01-03- 1999:sec.10.05,
1999:sec.11.01, 1999:sec.11.03-11.05, 1999:sec.14.01-2000:sec.01.06
1999:01:01-1999:01-02, 1999:01:05, 1999:04.08, 1999:07.01-07.02
1998:03:03
2000:v.01:01-2000:v.01.08
2000:v.02.01-2000:v.02.05
2000:v.03.01-2000:v.03.06
2000:v.04.01-2000:v.04:05, 2000:v.04.08, 2000:v.04.10-2000:v.04.11
2000:v.05.01-2000:v.04:06
2000:v.06.01-2000:v.06.03
2000:v.07.01-2000:v.07.02
2000:v.08.01-2000:v.08.04
2000:v.09.01-2000:v.09.02
2000:v.10:01-2000:v.10:05
2000:v.11.01-2000:v.11.03, 2000:v.11.05
2000:v.12.01-2000:v.12.02
2000:v.13.01
2000:v.14.01-2000:v.14.02
2000:v.15.01-2000:v.15.02, 2000:v.15.04-2000:15.06
2001:v.00.01
2001:v.01.01-2001:v.01-08
2001:v.02.01-2001:v.02.02, 2001:v.02.04-2001:v.02.05
2001:v.03.01-2001:v.03.06
2001:v.04.01-v.04.07, 2001:v.04.09-2001:v.04.11
2001:v.05.01-2001:v.05.03, 2001:v.05.05-2001:v.05.06
2001:v.06.01-2001:v.06.02, 2001:v.06.04
2001:v.07.01-2001:v.07.02
2001:v.08.01, 2001:v.08.03-2001:v.08.04
2001:v.09.01-2001:v.09.02
2001:v.10.01-2001:v.10.03
2001:v.11.01-2001:v.11.05
2001:v.12.01-2001:v.12.02
2001:v.13.01

2001:v.14.01, 2001:v.14.03-2001:v.14.04

2001:v.15.02-2001:v.15.09,

CALL NUMBER

[TA401 .A653](#)

Set 2

Request in

Jefferson or Adams Building Reading Rooms

Status

c.2 1983, pt. 15.09 Gift; American Institute of Architects / American Architectural Foundation; 2010; (DLC/PP-2010:100) In Process 09-07-2022

c.2 1986, pt. 1.02 Gift; American Institute of Architects / American Architectural Foundation; 2010; (DLC/PP-2010:100) In Process 09-07-2022

c.2 1987, pt. 1.06 Gift; American Institute of Architects / American Architectural Foundation; 2010; (DLC/PP-2010:100) In Process 09-07-2022

c.2 1987, pt. 1.03 Gift; American Institute of Architects / American Architectural Foundation; 2010; (DLC/PP-2010:100) In Process 09-07-2022

c.2 1987, pt. 4.08 Gift; American Institute of Architects / American Architectural Foundation; 2010; (DLC/PP-2010:100) In Process 09-07-2022

c.2 1987, pt. 6.02 Gift; American Institute of Architects / American Architectural Foundation; 2010; (DLC/PP-2010:100) In Process 09-07-2022

c.2 1987, pt. 6.03 Gift; American Institute of Architects / American Architectural Foundation; 2010; (DLC/PP-2010:100) In Process 09-07-2022

c.2 1987, pt. 15.02 Gift; American Institute of Architects / American Architectural Foundation; 2010; (DLC/PP-2010:100) In Process 09-07-2022

Older receipts

1979:pt.45-2001:pt.15.06

CALL NUMBER

[TA401 .A653](#)

Set 3

Request in

Jefferson or Adams Building Reading Rooms

Status

Not Charged

Older receipts

2001:pt.04.05

CALL NUMBER

[TA401 .A653 sect. 04](#)
Section 04--Construction
Set 1
Latest edition only

Request in

Jefferson or Adams Building Reading Rooms

Older receipts

2016:v.04.02

APPENDIX 4



United States Copyright Office

Try the [Copyright Public Records System \(CPRS\)](#) pilot with enhanced search features and filters.

[Help](#)
[Search](#)
[History](#)
[Titles](#)
[Start Over](#)

Public Catalog

Copyright Catalog (1978 to present) at DC4

Search Request: Left Anchored Title = Annual book of A S T M standards

Search Results: Displaying 11 of 47 entries

[◀ previous](#)
[next ▶](#)

Labeled View

Annual book of A S T M standards : [revision issued annually / Robert P...

Type of Work: Serial

Title: Annual book of A S T M standards : [revision issued annually / Robert P. Lukens, managing standards editor ... [et al.]].

Serial Publication Year: 1997

Serial Key Title: Annual book of A S T M standards

Imprint: Philadelphia : ASTM.

ISSN: 0192-2998

Description: print material.

Notes: Pub. in 48 parts; pub. in 66 v. divided among 16 sections beginning 1983; pub. in multiple vols. divided among 16 sections per section 2, v. 9, 1996.

Description based on: Pt. 46, 1981.

Copyright Claimant: American Society for Testing and Materials (employer for hire)

Issues Registered: 1997, section 1, v. 01.05. Created 1997; Pub. 1997-04-01; Reg. 1997-04-28; TX0004448393
 1997, section 1, v. 01.01. Created 1997; Pub. 1997-04-30; Reg. 1997-07-01; TX0004511610
 1997, section 5, v. 05.02. Created 1997; Pub. 1997-05-14; Reg. 1997-07-01; TX0004511604
 1997, section 5, v. 05.03. Created 1997; Pub. 1997-05-14; Reg. 1997-07-01; TX0004512031
 1997, section 5, v. 05.04. Created 1997; Pub. 1997-05-14; Reg. 1997-07-01; TX0004502831
 1997, section 15, v. 15.01. Created 1997; Pub. 1997-05-14; Reg. 1997-07-01; TX0004512020
 1997, section 5, v. 05.01. Created 1997; Pub. 1997-05-15; Reg. 1997-07-01; TX0004514352
 1997, section 1, v. 01.07. Created 1997; Pub. 1997-05-20; Reg. 1997-07-01; TX0004511609
 1997, section 6, v. 06.01. Created 1997; Pub. 1997-05-20; Reg. 1997-07-01; TX0004514354
 1997, section 6, v. 06.03. Created 1997; Pub. 1997-05-27; Reg. 1997-07-01; TX0004511608
 1997, section 4, v. 04.08. Created 1997; Pub. 1997-06-02; Reg. 1997-07-01; TX0004505908
 1997, section 8, v. 08.04. Created 1997; Pub. 1997-06-02; Reg. 1997-07-01; TX0004511607
 1997, section 15, v. 15.08. Created 1997; Pub. 1997-06-02; Reg. 1997-07-01; TX0004514355
 1997, section 3, v. 03.04. Created 1997; Pub. 1997-06-03; Reg. 1997-07-01; TX0004511606
 1997, section 6, v. 06.02. Created 1997; Pub. 1997-06-03; Reg. 1997-07-01; TX0004512021
 1997, section 6, v. 06.04. Created 1997; Pub. 1997-06-03; Reg. 1997-07-01; TX0004514353
 1997, section 10, v. 10.04. Created 1997; Pub. 1997-06-03; Reg. 1997-07-01; TX0004511605
 1997, section 2, v. 02.05. Created 1997; Pub. 1997-06-09; Reg. 1997-06-24; TX0004497884
 1997, section 4, v. 04.09. Created 1997; Pub. 1997-06-09; Reg. 1997-06-24; TX0004501912
 1997, section 10, v. 10.02. Created 1997; Pub. 1997-06-09; Reg. 1997-06-24; TX0004497878
 1997, section 10, v. 10.05. Created 1997; Pub. 1997-06-09; Reg. 1997-06-24; TX0004497882
 1997, section 11, v. 11.01. Created 1997; Pub. 1997-06-09; Reg. 1997-06-24; TX0004497877
 1997, section 11, v. 11.02. Created 1997; Pub. 1997-06-09; Reg. 1997-06-24; TX0004497876
 1997, section 15, v. 15.02. Created 1997; Pub. 1997-06-09; Reg. 1997-06-24; TX0004497879
 1997, section 2, v. 02.01. Created 1997; Pub. 1997-06-16; Reg. 1997-06-24; TX0004497885
 1997, section 2, v. 02.03. Created 1997; Pub. 1997-06-16; Reg. 1997-06-24; TX0004497119
 1997, section 2, v. 02.04. Created 1997; Pub. 1997-06-16; Reg. 1997-06-24; TX0004497118
 1997, section 10, v. 10.01. Created 1997; Pub. 1997-06-16; Reg. 1997-06-24; TX0004497883
 1997, section 10, v. 10.03. Created 1997; Pub. 1997-06-16; Reg. 1997-06-24; TX0004497880
 1997, section 14, v. 14.01. Created 1997; Pub. 1997-06-16; Reg. 1997-06-24; TX0004497881
 1997, section 4, v. 04.05. Created 1997; Pub. 1997-06-23; Reg. 1997-07-08; TX0004512205
 1997, section 8, v. 08.01. Created 1997; Pub. 1997-06-23; Reg. 1997-07-08; TX0004512208
 1997, section 14, v. 14.02. Created 1997; Pub. 1997-06-23; Reg. 1997-07-08; TX0004512210


1997, section 15, v. 15.09. Created 1997; Pub. 1997-06-23; Reg. 1997-07-10; TX0004512026
 1997, section 1, v. 01.03. Created 1997; Pub. 1997-06-30; Reg. 1997-07-08; TX0004512209
 1997, section 1, v. 01.04. Created 1997; Pub. 1997-06-30; Reg. 1997-07-08; TX0004512206
 1997, section 1, v. 01.06. Created 1997; Pub. 1997-06-30; Reg. 1997-07-08; TX0004512204
 1997, section 4, v. 04.04. Created 1997; Pub. 1997-06-30; Reg. 1997-07-08; TX0004512207
 1997, section 1, v. 01.02. Created 1997; Pub. 1997-07-02; Reg. 1997-07-02; TX0004502833
 1997, section 4, v. 04.10. Created 1997; Pub. 1997-07-02; Reg. 1997-07-09; TX0004502830
 1997, section 14, v. 14.03. Created 1997; Pub. 1997-07-02; Reg. 1997-07-09; TX0004502832
 1997, section 4, v. 04.03. Created 1997; Pub. 1997-07-09; Reg. 1997-07-22; TX0004515680
 1997, section 8, v. 08.02. Created 1997; Pub. 1997-07-09; Reg. 1997-07-22; TX0004515679
 1997, section 3, v. 03.01. Created 1997; Pub. 1997-07-23; Reg. 1997-07-28; TX0004515697
 1997, section 9, v. 09.01. Created 1997; Pub. 1997-07-23; Reg. 1997-07-28; TX0004520164
 1997, section 8, v. 08.03. Created 1997; Pub. 1997-07-25; Reg. 1997-08-19; TX0004528711
 1997, section 3, v. 03.02. Created 1997; Pub. 1997-08-01; Reg. 1997-08-19; TX0004521139
 1997, section 9, v. 09.02. Created 1997; Pub. 1997-08-01; Reg. 1997-08-19; TX0004521138
 1997, section 12, v. 12.01. Created 1997; Pub. 1997-08-07; Reg. 1997-08-19; TX0004530865
 1997, section 12, v. 12.02. Created 1997; Pub. 1997-08-07; Reg. 1997-08-19; TX0004521137
 1997, section 13, v. 13.01. Created 1997; Pub. 1997-08-07; Reg. 1997-08-19; TX0004521136
 1997, section 15, v. 15.05. Created 1997; Pub. 1997-08-07; Reg. 1997-08-19; TX0004534212
 1997, section 15, v. 15.06. Created 1997; Pub. 1997-08-07; Reg. 1997-08-19; TX0004521140
 1997, section 11, v. 11.05. Created 1997; Pub. 1997-08-26; Reg. 1997-09-11; TX0004475109
 1997, section 2, v. 02.02. Created 1997; Pub. 1997-08-28; Reg. 1997-09-11; TX0004475108
 1997, section 4, v. 04.01. Created 1997; Pub. 1997-09-08; Reg. 1997-10-02; TX0004557834
 1997, section 5, v. 05.05. Created 1997; Pub. 1997-09-08; Reg. 1997-10-02; TX0004557835
 1997, section 11, v. 11.04. Created 1997; Pub. 1997-09-12; Reg. 1997-10-02; TX0004557822
 1997, section 15, v. 15.04. Created 1997; Pub. 1997-09-12; Reg. 1997-10-02; TX0004559864
 1997, section 3, v. 03.03. Created 1997; Pub. 1997-09-17; Reg. 1997-10-02; TX0004559863
 1997, section 4, v. 04.02. Created 1997; Pub. 1997-09-19; Reg. 1997-10-02; TX0004559862
 1997, section 11, v. 11.03. Created 1997; Pub. 1997-10-01; Reg. 1997-10-22; TX0004575085
 1997, section 3, v. 03.05. Created 1997; Pub. 1997-10-05; Reg. 1997-10-22; TX0004563335
 1997, section 3, v. 03.06. Created 1997; Pub. 1997-10-10; Reg. 1997-10-22; TX0004575084
 1997, section 4, v. 04.07. Created 1997; Pub. 1997-10-10; Reg. 1997-10-22; TX0004571119
 1997, section 15, v. 15.03. Created 1997; Pub. 1997-10-10; Reg. 1997-10-22; TX0004563336
 1997, section 4, v. 04.06. Created 1997; Pub. 1997-10-15; Reg. 1997-11-12; TX0004584449
 1997, section 4, v. 04.11. Created 1997; Pub. 1997-10-23; Reg. 1997-11-12; TX0004584448
 1997, section 7, v. 07.01. Created 1997; Pub. 1997-10-23; Reg. 1997-11-12; TX0004577558
 1997, section 7, v. 07.02. Created 1997; Pub. 1997-10-23; Reg. 1997-11-12; TX0004580140
 1997, section 15, v. 15.07. Created 1997; Pub. 1997-11-03; Reg. 1997-11-12; TX0004580139
 1997, section 0, v. 00.01. Created 1997; Pub. 1997-12-19; Reg. 1998-01-13; TX0004604234

Basis of Claim: New matter: compilation of prev. pub. text & additions.

Spine Title: Annual A S T M standards.

Names: [Lukens, Robert P.](#)

[American Society for Testing and Materials](#)



Save, Print and Email (Help Page)	
Select Download Format	Full Record Format for Print/Save
Enter your email address:	
Email	

[Help](#) [Search](#) [History](#) [Titles](#) [Start Over](#)

[Contact Us](#) | [Request Copies](#) | [Get a Search Estimate](#) | [Frequently Asked Questions \(FAQs\) about Copyright](#) | [Copyright Office Home Page](#) | [Library of Congress Home Page](#)