

U.S. Patent No. 12,019,461 Side-by-Side Listing of Claims 1 and 17

Claim 1	Claim 17
[1.1] A fluid processing method, comprising:	[17.1] A method, comprising:
	[17.2] measuring, with one or more sensors at a first fluid tank located at a first fluid-handling site, one or more properties associated with a first fluid;
[1.2] receiving, with a first computer system disposed at a first fluid-handling site, information comprising one or more properties of a first fluid from one or more sensors disposed at a first fluid tank itself disposed at the first fluid-handling site, the fluid-handling site comprising one or more fluid-handling devices, the one or more fluid-handling devices comprising one or more of a first pump, a first filter, and a first valve;	[17.3] receiving, with a first computer system disposed at a first fluid handling site, information associated with the one or more properties associated with the first fluid;
[1.3] providing, with the first computer system disposed at a first fluid handling site, remote control of a first fluid-handling device of the one or more fluid-handling devices;	[17.4] providing, with the first computer system, remote control of a first fluid-handling device of a plurality of fluid-handling devices, the first fluid-handling device comprising at least one of a first pump, a first filter, and a first valve;
[1.4] receiving, with a server system, from the first computer system, via a network, a first fluid property of the one or more properties associated with the first fluid sensed by a first sensor of the one or more sensors;	[17.5] receiving, with a server system, from the first computer system, via a network, a first fluid property of the one or more properties associated with the first fluid sensed by a first sensor of the one or more sensors;

IPR2025-00671

TankLogix, LLC v. SitePro, Inc.

TankLogix's Exhibit 1012

EX1012, Page 1

[1.5] obtaining, with the server system, credentials from a first client computing device;	[17.6] obtaining, with the server system, credentials from a first client computing device;
[1.6] determining, with the server system, based on the credentials, that a user of the first client computing device is authorized to interact with the first fluid handling site, wherein the server system hosts data about other fluid handling sites the user is not authorized to interact;	[17.7] determining, with the server system, based on the credentials, that a user of the first client computing device is authorized to interact with the first fluid handling site, wherein the server system hosts data about other fluid handling sites the user is not authorized to interact;
[1.7] after the determination, providing, with the server system, via the network, information by which the first client computing device presents a user interface indicating the first fluid property, the first client computing device being remote from the server system and the first computer system;	[17.8] after the determination, providing, with the server system, via the network, information by which the first client computing device presents a user interface indicating the first fluid property, the first client computing device being remote from the server system and the first computer system;
[1.8] receiving, with the server system, from the first client computing device, a first command to change a state of the first fluid-handling device; and	[17.9] receiving, with the server system, from the first client computing device, a first command to change a state of the first fluid-handling device; and
[1.9] causing, with the server system, the first computer system disposed at the first fluid handling site to effectuate the command by changing the state of the first fluid-handling device to a sequence of different target states that change over time.	[17.10] causing, with the server system, the first computer system disposed at the first fluid handling site to effectuate the command by changing the state of the first fluid-handling device to a sequence of different target states that change over time.