US012236728B2

(12) **United States Patent**
Wright

(10) **Patent No.: US 12,236,728 B2**
(45) **Date of Patent: Feb. 25, 2025**

(54) **METHOD AND SYSTEM FOR LOGGING VEHICLE BEHAVIOUR**

(71) Applicant: **Andrew William Wright**, Virginia Water (GB)

(72) Inventor: **Andrew William Wright**, Virginia Water (GB)

(73) Assignee: **AUTO TELEMATICS LTD.**, Yorkshire (GB)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **18/676,284**

(22) Filed: **May 28, 2024**

(65) **Prior Publication Data**

US 2024/0312262 A1 Sep. 19, 2024

Related U.S. Application Data

(63) Continuation of application No. 17/729,962, filed on Apr. 26, 2022, now Pat. No. 12,002,301, which is a (Continued)

(30) **Foreign Application Priority Data**

Dec. 15, 2010 (GB) 1021292
Jan. 25, 2011 (GB) 1101259
(Continued)

(51) **Int. Cl.**
G07C 5/02 (2006.01)
G06F 17/00 (2019.01)
(Continued)

(52) **U.S. Cl.**
CPC ***G07C 5/02*** (2013.01); ***G06F 17/00*** (2013.01); ***G06Q 40/08*** (2013.01); ***G07C 5/008*** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC G07C 5/02; G07C 5/008; G07C 5/0858; G07C 5/0866; G06F 17/00; G06Q 40/08;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,992,943 A 2/1991 McCracken
5,638,273 A 6/1997 Coiner et al.
(Continued)

FOREIGN PATENT DOCUMENTS

DE 202008013951 U1 1/2009
EP 1615178 A2 1/2006
(Continued)

OTHER PUBLICATIONS

Oct. 2019 Subject Matter Eligibility Guidance.*
(Continued)

Primary Examiner — Tyler D Paige
(74) *Attorney, Agent, or Firm* — BAKER HOSTETLER LLP

(57) **ABSTRACT**

A mobile telecommunications device configured to log driving information associated with a vehicle is described. The mobile telecommunications device comprises: a sensor set comprising at least one of an image sensor, an audio sensor, an accelerometer and a positioning module, or a combination thereof; a processor; and a memory; the mobile telecommunications device being configured to: determine, based at least in part on sensor data from the device's sensor set, a start of a driving period during which the mobile device is present in the vehicle and the vehicle is in use, process the sensor data from the sensor set during the driving period to derive driving information associated with how the vehicle is driven, mobile telecommunications device being configured to process the sensor data automatically, using a neural network provided in the mobile device, to determine
(Continued)



USAA-1001

whether the driving information represents an acceptable or unacceptable driving pattern; and store at least some of the driving information to the memory.

28 Claims, 25 Drawing Sheets

Related U.S. Application Data

continuation of application No. 16/665,746, filed on Oct. 28, 2019, now Pat. No. 11,321,970, which is a continuation of application No. 16/222,893, filed on Dec. 17, 2018, now Pat. No. 10,950,068, which is a continuation of application No. 15/454,944, filed on Mar. 9, 2017, now Pat. No. 10,198,878, which is a continuation of application No. 15/061,910, filed on Mar. 4, 2016, now Pat. No. 9,633,487, which is a continuation of application No. 13/994,455, filed as application No. PCT/GB2011/052491 on Dec. 15, 2011, now Pat. No. 9,311,271.

(30) **Foreign Application Priority Data**

Jun. 10, 2011 (GB) 1109759
Oct. 31, 2011 (GB) 1118777

(51) **Int. Cl.**

G06Q 40/08	(2012.01)
G07C 5/00	(2006.01)
G07C 5/08	(2006.01)
G09B 5/02	(2006.01)
G09B 19/14	(2006.01)
H04M 1/60	(2006.01)
H04M 1/72406	(2021.01)
H04M 1/72409	(2021.01)
H04M 1/72454	(2021.01)
H04M 1/72412	(2021.01)

(52) **U.S. Cl.**

CPC ***G07C 5/0858*** (2013.01); ***G07C 5/0866*** (2013.01); ***G09B 5/02*** (2013.01); ***G09B 19/14*** (2013.01); ***H04M 1/6041*** (2013.01); ***H04M 1/6075*** (2013.01); ***H04M 1/72406*** (2021.01); ***H04M 1/724098*** (2022.02); ***H04M 1/72454*** (2021.01); *H04M 1/72412* (2021.01); *H04M 2201/36* (2013.01); *H04M 2250/12* (2013.01); *H04M 2250/74* (2013.01)

(58) **Field of Classification Search**

CPC G09B 5/02; G09B 19/14; H04M 1/6041; H04M 1/6075; H04M 1/72406; H04M 1/724098; H04M 1/72454; H04M 1/72412; H04M 2201/36; H04M 2250/12; H04M 2250/74

USPC 701/33.4

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,073,004	A	6/2000	Balachandran
6,724,920	B1	4/2004	Berenz et al.
7,110,570	B1	9/2006	Berenz et al.
7,756,617	B1	7/2010	Cluff et al.
7,765,058	B2	7/2010	Doering
7,821,421	B2	10/2010	Tamir et al.
7,908,191	B1	3/2011	Dinamani et al.
8,140,358	B1	3/2012	Ling et al.
8,554,468	B1	10/2013	Bullock
8,682,399	B2	3/2014	Rabu
8,781,442	B1	7/2014	Link, II
9,311,271	B2	4/2016	Wright
9,633,487	B2	4/2017	Wright
10,192,369	B2	1/2019	Wright
10,198,878	B2	2/2019	Wright
10,198,879	B2	2/2019	Wright
10,950,068	B2	3/2021	Wright
2005/0030224	A1	2/2005	Koch
2005/0046584	A1	3/2005	Breed
2006/0053038	A1	3/2006	Warren et al.
2006/0103513	A1	5/2006	Ihara et al.
2007/0027583	A1	2/2007	Tamir et al.
2007/0135979	A1	6/2007	Plante
2007/0135980	A1	6/2007	Plante
2007/0150139	A1	6/2007	Hardy
2007/0208503	A1	9/2007	Harnsberger
2007/0219685	A1	9/2007	Plante
2008/0242261	A1	10/2008	Shimanuki et al.
2008/0249969	A1	10/2008	Tsui et al.
2008/0255722	A1	10/2008	McClellan et al.
2008/0255888	A1	10/2008	Berkobin et al.
2009/0005975	A1	1/2009	Forstall et al.
2009/0109037	A1	4/2009	Farmer
2009/0157255	A1	6/2009	Plante
2010/0030540	A1	2/2010	Choi
2010/0039254	A1	2/2010	Cooper et al.
2010/0130182	A1	5/2010	Rosen
2010/0131304	A1*	5/2010	Collopy G06Q 30/0224 705/4
2010/0131307	A1	5/2010	Collopy et al.
2010/0131691	A1	5/2010	Chatterjee et al.
2010/0157061	A1	6/2010	Katsman et al.
2010/0216509	A1	8/2010	Reimer et al.
2010/0297930	A1	11/2010	Harris
2010/0317314	A1	12/2010	Roland
2011/0037595	A1	2/2011	Kapuria et al.
2011/0109462	A1	5/2011	Deng et al.
2011/0112717	A1	5/2011	Resner
2011/0117856	A1	5/2011	Veluppillai et al.
2011/0141006	A1	6/2011	Rabu
2011/0160964	A1	6/2011	Obradovich
2011/0161116	A1	6/2011	Peak et al.
2011/0212717	A1	9/2011	Rhoads et al.
2011/0307188	A1	12/2011	Peng et al.
2012/0072244	A1	3/2012	Collins et al.
2012/0083960	A1	4/2012	Zhu et al.
2012/0166583	A1	6/2012	Koonce et al.
2012/0246102	A1	9/2012	Sudharsan
2013/0005414	A1	1/2013	Bindra et al.
2013/0060583	A1	3/2013	Collins et al.
2013/0302758	A1	11/2013	Wright
2015/0120336	A1	4/2015	Grokop et al.
2015/0187013	A1	7/2015	Adams et al.
2017/0178422	A1	6/2017	Wright
2017/0178423	A1	6/2017	Wright
2017/0178424	A1	6/2017	Wright
2017/0278313	A1	9/2017	Maslar et al.

FOREIGN PATENT DOCUMENTS

EP	1764749	A2	3/2007
EP	1914691	A1	4/2008
EP	2177811	A2	4/2010
JP	2008-244674	A	10/2008
WO	WO 2006/075419	A1	7/2006
WO	WO 2006/127534	A1	11/2006
WO	WO 2007/067775	A2	6/2007
WO	WO 2007/114716	A1	10/2007
WO	WO 2010/042545	A2	4/2010

OTHER PUBLICATIONS

Barbeau et al.; "TRAC-IT—A Software Architecture Supporting Simutaneous Travel Behavior Data Collection & Real-time Location-Based Services for GPS-Enabled Mobile Phones"; Proceedings of

(56) **References Cited**

OTHER PUBLICATIONS

the Nat'l Academy of Sciences Transportation Research Board 88.sup.th Annual Meeting; Paper #09-3175; Jan. 2009; 20 pages.
Barbeau et al.; "Dynamic Management of Real-Time Location Data on GPS-Enabled Mobile Phones"; The 2.sup.nd Int'l Conf. on Mobile Ubiquitous Computing, Systems, Services and Techniques; 2008; p. 343-348.
Meyer, Stefan; "Fahrtenbuch—iPhone Apps Plus"; https://web.archive.org/web/20091210215707/http://www.iphoneappsplus.com/- -business/fahrtenbuch/index.htm; retrieved Jan. 19, 2016; 2 pages (XP055242544).
"iPhone & iPad iOS Entwicklung"; NeuMedienFraktion; http://www.neuemedienfraktion.de/iPhone/iPhone.html; retrieved Jan. 19, 2016; 2 pages (XP055242566).
Kanjo et al.; "MobGeoSen: facilitating personal geosensor data collection and visualization using mobile phones"; Personal and Ubiquitous Computing; vol. 12 No. 8; 2008; p. 599-607.
European Patent Application No. 11813683.7; Office Action Article 94(3); dated Jan. 26, 2016; 6 pages.
European Patent Application No. 17165104.5; Extended Search Report; dated Oct. 16, 2017; 12 pages.
Thompson et al.; "Using Smartphones to Detect Car Accidents and Provide Situational Awareness to Emergency Responders"; Mobile Wireless Middleware, Operating Systems, and Applications; 2010; p. 29-42.
Langle et al.; "Are You a Safe Driver"; Int'l Conf. on Computational Science and Engineering; 2009; p. 502-507.

* cited by examiner


1
5
DB
Insurance Server
7
Emergency Services Server
13
Communication Network
11
PC
15
3
9
Content Provider Server

Fig. 1


3
17
19
21
Mobile phone
Suction holder attached to windscreen
Flexible arm
A

Fig.2


17
21
Image Capture Module
27
Audio Capture Module
34a
Buffer
34
Storage
33
Processor Module
Neural Network
29
Communications Module
31
Wireless Telecommunications Sub-module
34b
Protected Storage
23
Accelerometer
25
GPS Receiver

Fig .3


Download Application and install on mobile device
36
Configure mobile device in vehicle
38
Specify recording strategy
40
Register start of a driving period
42
Sample and record sensor data and generate driving information
44
Analyse sensor data and driving information
46
Data File period expired?
60
No
Incident detected?
48
No
Yes
Yes
Store data file in buffer
62
Securely store sensor data and driving information in protected storage
50
Start new data file period
58
Transmit S.O.S message To emergency services server
54
Transmit sensor data and driving information to insurance server
52
Driving period terminated?
56
No
Yes
End Process

Fig. 4a


Step 44
64
Analyse audio data
66
Analyse accelerometer data
68
Analyse GPS data
72
Sensor data observed, which is associated with a driving incident?
70
Zero-velocity for pre-determined period observed?
Yes
Yes
No
No
Step 50
Step 60

Fig. 4b


80
230
Main Menu
User Manual
Witness User Manual
Main Menu
File Management 86
82
Settings 88
Accident Management 90
92
WITNESS
Recording Screen Button 84
94
Recording Screen
100
Keep Current Video
104
Take Photo
106
Exit Recorder
108
Start / Stop
110
S
SW
200°
96
Mph
0
00:00
102
98

Fig. 5


112
230
Main Menu
User Manual
The recording screen also displays your current heading, speed and recording time.
During recording, the exit button becomes the map display button. Pressing this toggles the display of a map overlay showing your current position.
Pressing the "Keep Current Video" button will automatically copy the current video and the previous video to the kept videos section in the library. Use this button if an incident occurs whilst you are driving and you wish to keep it.
114
104
106
116
110
S
S
SW
180°
Stock Hill
Mph
00:44

Fig. 6


118
230
Main Menu
User Manual
File management
120
Main Menu
Recordings
Edit
Recording 1
2 May 2011 06:53, 4.5 Mb
124
Last Stretch Home
20 April 2011 18:07, 40.3 Mb
Inside View
20 April 2011 18:01, 11.0 Mb
Accident At Long Cross
21 April 2011 12:12, 24.4 Mb
122
Video
Map
Export
Keep
126
128
130
132
The top section of the file management screen contains the recording stack. The recording stack contains your recent video segments, the number of which depends upon your personal settings.
The bottom section contains videos segments that you have chosen to keep.
Main Menu
Recordings
Done
Recording 1
2 May 2011 06:53, 4.5 Mb
Last Stretch Home
20 April 2011 18:07, 40.3 Mb
Inside View
20 April 2011 18:01, 11.0 Mb
Accident At Long Cross
21 April 2011 12:12, 24.4 Mb
Video
Map
Export
Keep
Your kept recordings can be deleted individually, but the video stack can only be cleared from the setting screen.

Fig. 7


142
230
Main Menu
User Manual
Recording Playback
5 of 11
146
20 Apr 2011 18:07:47, 29 Mph, G:-0.2
Lat: 51.1857, Lon: -2.5290, Hdg:306°
144
156
152
150
154
148
The playback screen shows your recorded video along with the associated telemetry data. The data displayed shows the date and time of the recording, the current speed, the forward and reverse G force, the current GPS position and the current heading.
The G force measures the force of braking and acceleration with the phone mounted with the screen facing rearward, and the back of the phone facing forwards.
Video playback is controlled via the scrub bar at the bottom. The vertical slider on the left is the playback speed. Other controls are loop, pause and eject.

Fig. 8


230
158
Main Menu
User Manual
Please Note:
The playback video screen is a floating view and can be zoomed by pinching and moved with a single finger. A double tap will reset the view.
Map Playback
160
Recordings
20 April 2011
Tap pin to show recorded vehicle data
162
18:01:13 48 Mph G:0,2
Lat: 51.1922 Lon: -2.4269 Hdg:228°
168
164
166
Map playback shows where a recording was made via a blue breadcrumb trail. A pin shows the vehicle position and can be tapped to reveal telemetry data.
The scrub slider will move the pin according to the recorded telemetry.

Fig. 9


172
230
Main Menu
User Manual
Video Export
174
Export
Video Export Quality
Low
Med
High
Begin Export To Camera Roll
Cancel Export
Choose the video quality according to your preference and the video will be exported to the camera roll with the telemetry data embedded within the video
Medium and high quality reveal good results but with fairly large files usually too big to e-mail, although trimming within the camera roll can shorten the video to just the bit you need. Low quality produces small files but the quality suffers.
Please remember that the iphone is not a desktop computer and therefore long video segments exported at high quality may take several minutes to complete.

Fig. 10


176
230
Main Menu
User Manual
Settings
178
Main Menu
Settings
Video segment length in minutes
1 2 3 4 5 6
Video quality
640 X 480
Low Med
High
Number of video segments
3 4 5 6 7 8 9 10
G Sensitivity: 1.950
More Settings
182
180
Video recording can be adjusted to allow up to an hour of recorded video in the video stack.
Choose the segment length in minutes and the number of segments you would like according to the available space on your device. Each minute of video at high quality will use 26Mb of space. 1 hour will use 1.5Gb.
G Sensitivity adjusts the automatic triggering of crash detection. Raise the sensitivity if you find that crash detection is triggered during normal driving due to differences in vehicle suspension.

Fig. 11



Choose your preferred speed units here which will be used throughout the app. Even if you change the speed units after a recording is made, then the correct speed units will be used in playback and export.

You are able to choose whether to have the map overlay display at a certain speed during recording on the main recording screen. Please select the option and set the speed if you would like this to happen.

Please note: If you change the speed units, you will need to re-adjust the map trigger speed accordingly.

Fig. 12


230
194
Main Menu
User Manual
Personal Details
196
More Settings
Change PIN
198
Name:
200
Car Reg:
202
Mobile No:
e-mail address to use in an emergency:
204
Allow the video stack to be deleted by the user
206
NO
YES
These details will be used in the event of an accident to send an automated message.
Enter your name, the registration number of the car the device will be used in, the telephone number of this device and the e-mail address of the person you would like contacted
You can also set here the option to prevent the video stack from being cleared.
This screen can be protected with a PIN number, but please make sure you remember it or make a note of it somewhere. Re-setting the PIN can only be accomplished by deleting and re-installing the app which will result in all video and data being lost

Fig. 13


184
230
Main Menu
User Manual
Accident Management
In the event of an accident, Witness provides the necessary tools you need in order to gather and keep the correct information.
212
214
Main Menu
Accident Management
Back
Witness Details
214
Accident Advice / What To Do
A N Other
245, The Street
Big City
BC34 V87
216
Witnesses
Photos
220
Tel: 12345 123456
Drivers
Your Details
Mob: 89765 123456
another@another.com
Car Registration: N/A
222
226
Witness and driver details can be stored and viewed from within the internal database.
There is also a place to store your insurance details should you need them. Please enter these now so they are in the phone for future use.

Fig. 14

230
Accident Management
What should you do?
Make sure you and others are safe
* Is anyone injured?
* Is the accident causing a hazard?
* Has someone left the scene?
If yes to any of these, then call the emergency services
1. Witnesses - Collect the names and addresses of any witnesses.
2. Photographs - Take pictures of the scene of the accident, damage to cars and other property, and the occupants of the other vehicle.
3. Drivers - Collect names, addresses, registration numbers and insurance details of all other drivers involved.

Fig. 15


230
Accident Management
2 of 2
4. Your details - You must give your details to other drivers. DO NOT ADMIT LIABILITY.
5. Inform your insurance company - Even if you aren't going to make a claim.
6. Inform the police - If someone is injured (or a dog or farm animal) Report in person to a police Station and take your insurance details, driver's licence and MOT certificate.
Close this view and use the built in tools included with this application to help you collect the data.

Fig. 16

230
218
Back
Witness Details
Full name of witness
House number or name
Street name
Postal town or city name
Postal / Zip code
Home telephone number

Fig. 17


230
224
Back
Drivers Details
Full name of driver
House number or name
Street name
Postal town or city name
Postal / Zip code
Home telephone number

Fig. 18


230
228
Accident Management
Your Details
Insurance company:
Insurance policy number:
Policy expiry date:

Fig. 19


230
Main Menu
Recordings
Edit
134
Recording 1
25 May 2011 14:45, 128.6 Mb
134
Recording 2
25 May 2011 14:50, 128.6 Mb
134
Recording 3
25 May 2011 14:55, 127.5 Mb
134
Recording 4
25 May 2011 15:00, 131.5 Mb
134
Recording 5
25 May 2011 15:05, 5.0 Mb
134
Recording 6
26 May 2011 11:01, 12.6 Mb
134
Recording 7
25 May 2011 14:25, 127.2 Mb
Video
Map
Export
Keep

Fig. 20


230
Main Menu
Recordings
Edit
136
Recording 1
25 May 2011 14:45, 128.6 Mb
136
Recording 2
25 May 2011 14:50, 128.6 Mb
136
Recording 3
25 May 2011 14:55, 127.5 Mb
136
Recording 4
25 May 2011 15:00, 131.5 Mb
136
Recording 5
25 May 2011 15:05, 5.0 Mb
136
Recording 6
26 May 2011 11:01, 12.6 Mb
136
Recording 7
25 May 2011 14:25, 127.2 Mb
Video
Map
Export
Keep

Fig. 21


230
Main Menu
Recordings
Edit
138
Recording 1
25 May 2011 14:45, 128.6 Mb
138
Recording 2
25 May 2011 14:50, 128.6 Mb
138
Recording 3
25 May 2011 14:55, 127.5 Mb
138
Recording 4
25 May 2011 15:00, 131.5 Mb
138
Recording 5
25 May 2011 15:05, 5.0 Mb
138
Recording 6
26 May 2011 11:01, 12.6 Mb
138
Recording 7
25 May 2011 14:25, 127.2 Mb
Video
Map
Export
Keep

Fig. 22


230
Main Menu
Recordings
Edit
140
Recording 1
25 May 2011 14:45, 128.6 Mb
140
Recording 2
25 May 2011 14:50, 128.6 Mb
140
Recording 3
25 May 2011 14:55, 127.5 Mb
140
Recording 4
25 May 2011 15:00, 131.5 Mb
140
Recording 5
25 May 2011 15:05, 5.0 Mb
140
Recording 6
26 May 2011 11:01, 12.6 Mb
140
Recording 7
25 May 2011 14:25, 127.2 Mb
Video
Map
Export
Keep

Fig. 23



Fig. 24

METHOD AND SYSTEM FOR LOGGING VEHICLE BEHAVIOUR

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 17/729,962, filed Apr. 26, 2022, which is a continuation of U.S. patent application Ser. No. 16/665,746, filed Oct. 28, 2019, which is a continuation of U.S. patent application Ser. No. 16/222,893 filed Dec. 17, 2018, which is a continuation of U.S. patent application Ser. No. 15/454,944 filed Mar. 9, 2017, which is a continuation of U.S. patent application Ser. No. 15/061,910 filed Mar. 4, 2016 and now issued as U.S. Pat. No. 9,633,487, which is a continuation of U.S. patent application Ser. No. 13/994,455 filed Jul. 24, 2013 and now issued as U.S. Pat. No. 9,311,271, which is a 371 of international patent application PCT/GB2011/052491 filed Dec. 15, 2011, which claims foreign priority to GB patent application no. 1118777.0 filed Oct. 31, 2011, GB patent application no. 1109759.9 filed Jun. 10, 2011, GB patent application no. 1101259.8 filed Jan. 25, 2011, and GB patent application no. 1021292.6 filed Dec. 15, 2010, the contents of which are incorporated in their entirety as if fully presented herein.

FIELD OF THE INVENTION

The present invention relates to methods and systems for logging driving information associated with vehicle behaviour. Moreover, the present invention relates to a mobile device adapted for installation to a vehicle and configured to log such driving information, for example, video footage associated with how the vehicle is driven. Such driving information may subsequently be utilised to determine the cause of an event such as an accident, to modify driver behaviour and/or to determine insurance premiums.

BACKGROUND

Data logging devices are commonly installed on aircraft that log data about events associated with the behaviour of the aircraft and also the crew controlling the aircraft. Such data logging devices are commonly termed "black boxes" and are very useful for determining the cause of problems that have affected the aircraft, especially when no other record of a significant event such as a crash exists.

Similar data logging devices exist for road vehicles, and can be used to realise similar advantages. Vehicle users as well as authorities can use such devices to determine the cause of traffic accidents or other vehicle-related events, whether these stem from vehicle malfunction or driver negligence.

Some of these data logging devices can be integrated with the car data network, and so may take inputs from sensors integrated with the vehicle, such as those measuring the speed of the vehicle. However, these can be difficult and costly to install. Others having their own internal sensor set are more readily retrofitted to a vehicle. Nonetheless, such data logging devices for road vehicles are less prevalent perhaps due to their unjustifiable expense. Accordingly, the uptake of data logging devices that can be retrofitted to road vehicles, as are known in the art, has been minimal.

It is an object of the present invention to alleviate the above-mentioned problems, at least in part.

SUMMARY OF THE INVENTION

According to a first aspect of the present invention there is provided a mobile telecommunications device configured to log driving information associated with a vehicle is described. The mobile telecommunications device comprises: a sensor set comprising an image sensor and at least one of an audio sensor, an accelerometer or a positioning module, or a combination thereof; a user interface; a processor; and a memory. The mobile telecommunications device is configured to: determine, based on the inputs received by the user interface and sensor data from the device's sensor set, a start of a driving period during which the mobile device is removably affixed to the vehicle and the vehicle is in use, wherein the start of the driving period is determined without data from sensors of the vehicle; process the sensor data from the sensor set during the driving period to derive driving information associated with how the vehicle is driven; and store a selection of the driving information to the memory. The driving information comprises images captured by the image sensor and the mobile telecommunications device is controlled by a downloaded application to process the captured images to make a safety determination for the vehicle and in response to making an unsafe determination for the vehicle, to issue an alert signal.

Advantageously, the use of a mobile telecommunication device enables a data logging device to be conveniently and inexpensively retrofitted to a vehicle. Mobile telecommunication devices such as "smart-phones" are becoming increasingly widespread, and these devices tend to have the requisite sensor sets to capture data concerning vehicle behaviour. Thus, a generic mobile telecommunication device already owned by a driver of the vehicle can be loaded with the application to provide such data logging functionality that would otherwise necessitate a dedicated black-box. Thus, the functionality of a black-box can be realised without additional expense.

Following on from this, it will be appreciated that the mobile device is ideally a portable mobile telecommunication device. Ideally, the mobile device is a hand-portable mobile device. Advantageously, the portability permits the mobile device to be conveniently fitted to and removed from the vehicle.

Furthermore, such a mobile telecommunication device presents additional advantages over known dedicated black-box systems as the data logging functionality of the mobile telecommunication device can be continually refined. This can be achieved without physically upgrading the hardware of the device, and also without significant user intervention. Specifically, the application may be arranged to determine whether a software update exists and if so, control the mobile device to download at least portions of an improved version of the application. Conveniently, downloading may be via the wireless telecommunication module. Said downloading may be automatic, or may be user-confirmed. For the avoidance of doubt, the application will typically be stored on a portion of the memory of the mobile device and executed therefrom, as is known in the art. Also, it will be appreciated that the application, or portion thereof, may be downloaded via the wireless telecommunication module and/or via an intermediary device. For example, the application may be side loaded to the mobile device from an intermediary computing device.

The application may be sourced from an application store and/or content provider. For example, the content provider may comprise the Apple® Appstore®. The content provider may comprise a cloud computing provider.

It will be appreciated that the use of such a generic mobile device in this context may be counter-intuitive to a person skilled in the art—such generic devices are not designed to withstand events such as catastrophic crashes. Furthermore,

such generic devices are usually not necessarily configured to appropriately detect conditions that may need to be recorded. Such devices are usually kept in a user's pocket or bag, and so are not best placed to generate sensor data associated with the behaviour of a vehicle. However, the inventor of the present invention has realised that such a mobile device that is adapted for installation to the vehicle can overcome such drawbacks and fulfil a role similar to a black box. To this end, the mobile telecommunication device may comprise an adapter arranged to hold the device securely to the vehicle.

Advantageously, as well as protecting the device from damage, the adapter improves the suitability and reliability of the sensor data and so the driving information associated with when and/or how the vehicle is being driven. For example, if the sensor set comprises an accelerometer, the acceleration of the vehicle can be more accurately measured due to the mobile device being firmly attached to the vehicle. Similarly, if the sensor set comprises an image sensor, for example, for capturing video footage of the road ahead, better footage can be obtained as the mobile device can be held in the correct position and orientation relative to the vehicle. In particular, the mobile device may be positioned by the adapter so that its image sensor views the road ahead through a windshield of the vehicle.

As mentioned, the device is arranged to log driving information associated with the vehicle, when that vehicle is being driven. This is realised by registering the start of the driving period during which the mobile device is installed to the vehicle and the vehicle is being driven by the driver. Advantageously, this prevents driving information from being needlessly recorded. As will be appreciated the mobile device has only a finite storage capacity and so registering the start of the driving period is useful for minimising the unnecessary usage of memory. In particular, where the mobile device comprises an image sensor, and the sensor data comprises a sequence of images (e.g., a video) the storage space can be very quickly filled by the memory.

To this end, it is preferred that when the application is executed, it controls the mobile device to register the start of a driving period in response to an initialisation input. The initialisation input may comprise a user input—for example, the user manually executing the application on the mobile device. The initialisation input is also generated automatically in response to the mobile device being installed to the vehicle and/or the vehicle being driven. The initialisation input may be generated automatically in response to the sensor data having predetermined values. For example, if the sensor data reflects a detected speed above a predetermined threshold—for example, 20 kilometres per hour—then this can be used to trigger the start of the driving period. Similarly, if the sensor data reflects that the mobile device is held securely to the vehicle in a predetermined position (for example, via the adapter) this can also be used to trigger the start of the driving period. To this end, the adapter and/or the mobile device may comprise a registration module configured to register the installation of the mobile device to the vehicle and/or the adapter. The registration module may comprise a proximity sensor to detect the proximity of the mobile device to the vehicle. The registration module may comprise a NFC (near field communication) device. The registration module may be arranged to determine a match between the location of the mobile device and the location of the vehicle. The match may be performed by receiving and comparing a first positioning input associated with the position of the vehicle and a second positioning input associated with the position of the mobile device. The registration module and/or adapter may be a smart holster.

Preferably, the executed application controls the mobile device to manage voice-calls incoming to the mobile device during a driving period. For example, said voice-call management may comprise temporarily disabling and/or diverting voice-calls incoming to the mobile device during a driving period. Advantageously, this safety feature discourages users from making or receiving phone calls whilst driving. It will be appreciated that a driver is less able to control a vehicle effectively whilst also manipulating a mobile device, and in many countries doing so is illegal. However, the provision of a 'hands-free' mode or accessory—as are well known in the art—may obviate the need for a user to manipulate the mobile device. Accordingly, the executed application may be arranged to control the mobile device to selectively disable and/or divert voice-calls incoming to the mobile device during a driving period, in dependence on the detection of a hands-free accessory or hands-free mode enabled on the mobile device.

Furthermore, the executed application may be arranged to control the mobile device to enable a hands-free mode of operation on detection of a driving period. For example, the enabled hands-free mode of operation may comprise enabling voice-activated commands. In light of this, it is preferred that the adapter is configured to hold the mobile device in a way that facilitates reception of voice commands from the user. In particular, the mobile device may be held in a position relative to the user to permit clear reception of the user's voice. Typically, this position is about the dashboard in a vehicle such as car or van. Furthermore, the adapter is configured with an opening through which an audio sensor of the mobile device is able to receive the user's voice.

Also, even though a driver's control of a vehicle may be affected by manipulating the mobile device, under certain circumstances, this may not be objectionable—for example, when the vehicle is stationary. Accordingly, the executed application may be arranged to control the mobile device to selectively disable and/or divert voice-calls incoming to the mobile device during a driving period, in dependence on the driving information—for example, the speed and location of the vehicle.

Furthermore, it will be appreciated that the driver may not be the only user within the vehicle, and so disabling functions of the mobile device may not be appropriate under all circumstances, as a passenger of the vehicle may want to use the mobile device whilst the driver is driving. Under these circumstances, the executed application is arranged to control the mobile device to register the presence of a non-driver (for example, via image recognition, or entry of an unlock code) and unlock, or retain the original functionality of the mobile device. Furthermore, the executed application may be arranged to run in the background. Accordingly, the mobile device may be used for other purposes, such as making or receiving a telephone call.

It is advantageous to store only selected driving information for the purpose of logging how a vehicle is being driven during the driving period. Whilst it may be possible to sample and process sensor data at a relatively high rate (i.e. many times a second), continually storing driving information derived from that sensor data at such a high rate can use up a lot of storage space on the mobile device, the majority of which is likely to be redundant. Therefore, by being selective about the driving information that is stored, storage utilisation can be made more efficient.

In particular, the executed application may control the mobile device to store a summary of the driving period. The summary may comprise compressed and/or summarised driving information. For example, the sensor data can be processed at a first sampling rate and then down-sampled to a fraction of the first sampling rate for storage as driving information. Put another way, the mobile device can be controlled by the executed application to down-sample sensor data from a first sampling rate to a second sampling and store the sensor data as driving information at said second sampling rate. Advantageously, this retains a snapshot of when and/or how the vehicle is being driven, but with fewer data points, and so requiring less storage space.

Nonetheless, under certain circumstances, it is more useful to retain information at higher or the highest possible sampling rates. In particular, it is more important to have detailed information associated with the behaviour of a vehicle during a crash than when the vehicle is being driven normally.

Accordingly, the executed application may be arranged to control the mobile device to detect the occurrence of a predetermined event of significance (such as a crash) and in response store driving information associated with that event to the memory. Preferably, said driving information associated with that event comprises driving information in the lead up to and immediately following the event. In particular, detailed driving information in the lead up to, and immediately following a predetermined event of significance is preferably stored. It will be understood that the driving information associated with the detected event may be transmitted via the wireless telecommunication module in addition to, or instead of storing said data. Said transmitted driving information may be transmitted to a remote data logging system.

To this end the mobile device may comprise an event detector for detecting the occurrence of an event.

Preferably, the event detector is arranged to detect the occurrence of a predetermined event by correlating data, such as sensor data, against an event indication model. The application may comprise the event indication model.

Preferably, the event indication model comprises a set of predetermined data values corresponding to a predetermined event. Accordingly, the event detector is arranged to compare the set of predetermined data values against corresponding sensor data to determine whether the predetermined event has occurred.

For example, the event indication model may indicate that a serious crash has occurred if values returned by an accelerometer sensor exceed predetermined data values of the event indication model, thereby representing a sustained vehicle deceleration beyond a threshold level. Following on from this, it will be appreciated that detection of an event may be dependent on matching a sequence of data values that have occurred over time. Moreover, the event indication model may comprise a sequence of predetermined data values, the sequence being associated by a function of time. Thus, the event detector may be arranged to compare the sequence of predetermined data values against corresponding sensor data that have been generated over a given time period. Put another way, the event detector and event indication model are arranged to indicate the occurrence of an event in dependence on the correlation between a set of predetermined data values occurring over time. Thus, a set of values returned from sensor data over a period of time are compared against a corresponding sequence of predetermined data values of the event indication model. Typically, this is to determine a rate of change of variables associated with a sensor set.

It will be understood that an event indication model may comprise a plurality of sets of predetermined data values, each set corresponding to different sensor data. For example, an event indication model associated with a serious accident event may contain data values corresponding to both the deceleration of the vehicle, and the orientation of the vehicle. Thus, if a vehicle is involved in a serious impact, and overturns, this is represented by the model, and so can be detected by the event detector.

Preferably, the event indication model comprises a pattern of predetermined data values. Preferably, the event detector is arranged to detect the occurrence of an event by carrying out pattern recognition by matching sensor data values to the pattern of predetermined data values of the event indication model. Preferably, there is a plurality of event indication models. Each event indication model may be associated with a separate predetermined event.

Preferably, the executed application may be arranged to control the mobile device to process sensor data from the sensor set during a plurality of driving periods to derive driving information associated with when and/or how the vehicle is driven for each of the driving periods. Preferably, sensor data processed during a first set of driving periods define a benchmark against which sensor data is compared during subsequent sets of driving periods. In particular, the executed application may be arranged to control the mobile to modify one or more event indication models in response to the benchmark. Advantageously, such a benchmark ensures that the event indication models may be tailored to the standard behaviour of a particular vehicle. As will be appreciated, different sensor types, mobile devices, mounting positions, vehicles, drivers and road conditions may generate different sets of sensor data for driving behaviour that is considered standard or safe. Accordingly, the benchmark allows the mobile device to account for variable driving conditions.

Preferably, a plurality of benchmarks may be defined. A benchmark may be defined for each driver. A benchmark may be defined for each vehicle to which the mobile device is to be installed. Ideally, a benchmark is defined for each driver-vehicle pair. To this end, the mobile device may be arranged to receive an input to specify a driver, a vehicle or a driver-vehicle pair. Advantageously, this ensures that different drivers and vehicles do not disrupt the accurate event detecting capabilities of the event detector.

Once a predetermined event has been detected by the event detector, it is desirable to take an appropriate action in response to that detected event. Accordingly, the executed application may be arranged to control the mobile device to take at least one predetermined action in response to a detected event. The action taken may comprise transmitting driving information and/or sensor data, via the wireless telecommunication module of the mobile device, to a remote system. Advantageously, this enables a remote system to be notified of the occurrence of a particular event, and the details associated with that event. For example, the remote system may be arranged to deploy emergency services based on a transmitted notification concerning the occurrence of a crash, and also the location of the mobile device (and so the vehicle) are also included in the transmitted information. A further advantage of transmitting driving information and/or sensor data to a remote system is that such data then does not need to be stored on or processed by the mobile device.

Thus, this can free the storage space on the mobile device, and also allow the processor of the mobile device to carry out other tasks.

A further advantage associated with sending driving information to a remote system is that the driving information can be assessed remotely. This assessment can be performed automatically or manually—either way it advantageously removes the processing burden from the mobile device. Alternatively, if transmission bandwidths are small, the processing can be executed automatically on the processing device. In this case, the use of virtual neural networks can be used to determine whether the driving information represents acceptable or unacceptable driving patterns.

The action taken may comprise storing data captured at a higher (or the highest possible) sampling rate than when an event is not detected. Thus, as described above, this may involve preventing the down-sampling of sensor data. Furthermore, the action taken may comprise protecting said driving information from being overwritten.

The action taken may comprise providing feedback to a user to indicate that an event has been detected. Preferably, the mobile device is configured to receive a user interaction to confirm or deny whether the detected event has actually occurred following said feedback. Advantageously, such user feedback can be used to modify event indication models thereby to refine the effectiveness of the event detector. The mobile device may comprise a speaker. Accordingly, such feedback may be provided via an audio prompt. The mobile device may comprise a display screen. Accordingly, such feedback may be provided via a visual prompt. The feedback may comprise notifying a user that a further action has been scheduled, and will be taken within a predetermined period. For example, the feedback may indicate to a user that an event such as a serious crash has been detected, and so the next action to be taken will be to contact emergency services within 10 seconds. Preferably, the feedback includes a prompt to receive a user input. For example, the prompt may be arranged to receive a user input to cancel a subsequently scheduled action. Advantageously, this prevents actions being taken needlessly as a result of an incorrect determination of an event.

The feedback may provide reassurance and/or guidance to a user. For example, a user may be provided with an important checklist of things to do following an accident or incident. For example, the user may be guided to use a camera (image sensor) on the mobile device to take photographs of the vehicles involved in the incident, including the number plates of those vehicles. The user may be guided to use a text input device on the mobile device to note the name, address, etc of third parties involved in incident.

The action taken may comprise communicating to a remote system that an incident has been detected (e.g. via a low bandwidth data connection or via text message). If appropriate—or in response to a request from a communication to the mobile device from the remote system—the action taken may comprise transmitting all or selected portions of the driving information associated with the detected event.

Preferably, the executed application is arranged to control the mobile device to prioritise essential communications, such as calls to the emergency services.

Preferably, the memory comprises a long term memory for persistently storing driving information and/or sensor data. Preferably the memory comprises a buffer. The buffer may comprise a short term memory for transiently storing driving information and/or sensor data. Preferably, the short term memory is arranged to receive driving information and/or sensor data at a higher update rate than the long term memory. Preferably, the long term memory has a larger capacity than the short term memory.

Preferably, the executed application controls the mobile device to write driving information and/or sensor data to the short term memory at a predetermined update rate during the driving period. Ideally, the driving information and/or sensor data is written to the short term memory in a predetermined sequence, ideally a chronological sequence. Preferably, the executed application controls the mobile device to overwrite driving information and/or sensor data previously written to the short term memory. Advantageously, this ensures that recording of sensor data and/or driving information, especially data that is recorded at a relatively high update rate, is not prevented during the driving period due to the short term memory becoming full.

Preferably, the driving information and/or sensor data is overwritten in accordance with the predetermined sequence. Advantageously, this can ensure that the most relevant, up-to-date data is retained in the short-term memory.

Preferably, the action taken in response to a detected event comprises transferring data from the short-term memory to the long-term memory. Advantageously, this can ensure that the most recent information associated with an event is persistently stored in the long term memory, and is not overwritten.

Preferably, the sensor set comprises an accelerometer for detecting the acceleration of the mobile device. Accordingly, the corresponding sensor data may comprise acceleration data generated by the accelerometer. The accelerometer may be a single axis or dual axis accelerometer. However, it is preferable that the accelerometer is a three-axis accelerometer so that movement of the vehicle may be determined in three-dimensional space. Furthermore, as the mobile device may be mounted by a user in one of a number of different orientations relative to the vehicle, a three-axis accelerometer ensures that acceleration along the axis aligned with the general forward movement of the vehicle may be effectively detected. This is particularly important to determine an event such as heavy braking of the vehicle and/or a crash.

Preferably, the sensor set comprises an image sensor such as a camera. Accordingly, the corresponding sensor data may comprise images and/or a sequence of images generated from the image sensor. Said sequence of images may be processed and/or stored in the form of a video. Advantageously, this can improve the space utilisation of the sequence of images. Preferably, the mobile device is arranged to receive a user input to store a user-selected image or sequence of images to the memory. The image sensor data may be processed to determine safety information and feedback said safety information to the driver. For example, the mobile device may be controlled to determine the proximity of the mobile device to other vehicles. Said determination may be via comparing the apparent size of the number plate of other vehicles in an image with a known size of a standard number-plate, and from that the distance to those other vehicles. Thus, the mobile device can make a determination that another vehicle is too close, and issue a warning to the driver to slow down to avoid a collision. Similarly, images of the road ahead may be processed to determine whether a vehicle is drifting out of lane (e.g. because the driver is falling asleep). In response to such a determination, an alert can be issued. Similarly, images of road signs may be processed to assess driver behaviour.

It will be appreciated that the mobile device may comprise a plurality of image sensors. For example, the mobile device may have a forward-facing camera and a rear-facing

camera. Accordingly, it may be possible to view images of the road ahead, external to the vehicle, and also from inside the vehicle. In particular, the mobile device may be arranged to capture images or a sequence of images of the driver. Images of the driver according to the present aspect of the present invention processed to make a safety determination. For example, the images may be processed to detect whether the driver is falling asleep. In particular, a blink rate of the driver may be detected by processing the image data. Similarly, a determination may be made whether the driver has their eyes closed. In response to such a determination that a driver is falling asleep, the mobile device may be arranged to issue an alert so as to wake the driver.

Preferably, the sensor set comprises an audio sensor such as a microphone. Accordingly, the corresponding sensor data may comprise audio data.

Advantageously, an image sensor and/or an audio sensor can provide an important record of an event such as a crash.

Preferably, the sensor set comprises a positioning module arranged to determine the position of the mobile device. The positioning module may comprise a GPS module. The positioning module may be arranged to utilise the wireless telecommunication module to self-localise, for example by determining a position relative to one or more mobile telecommunication cell towers. Advantageously, the positioning module can allow the mobile device to determine its position (and so the position of the vehicle) over time. Accordingly, the positioning module can thus determine the speed of the mobile device and vehicle. Thus, the corresponding sensor data may comprise latitude, longitude, elevation, speed and other data obtainable from positioning modules such as GPS modules as is known in the art.

Preferably, the sensor set comprises an orientation sensor for determining the orientation of the mobile device. Said orientation sensor may comprise an electronic compass for determining a bearing, and so the direction in which the mobile device is facing. Accordingly, the corresponding sensor data may comprise orientation and bearing data. Advantageously, such data can be used to augment the data of the positioning module. Furthermore, the executed application may be arranged to use the data from the orientation sensor to determine whether the mobile device has been fitted to vehicle, and whether the mobile device has been fitted in the correct orientation. Advantageously, the data from the orientation sensor may also be used to determine whether a significant event has occurred, such as the vehicle overturning.

Preferably, the sensor set comprises a user-input device arranged to receive an input from a user. The user input device may comprise at least one of buttons and a touch-sensitive display screen. Advantageously, this allows a user to input data to the mobile device.

Preferably, the mobile device comprises a timer. Preferably, the executed application is arranged to control the mobile device to record sensor data and/or driving information against time as determined by the timer. Accordingly, the timer can be used to time-synchronise sensor data and/or driving information.

Preferably, the executed application is arranged to encrypt the driving information stored on the memory. Advantageously, this reduces the possibility of said driving information being modified without authorisation. This is an important consideration when such driving data may be used as evidence, for example, when determining the cause of an accident.

Preferably, the mobile device is arranged to interface with an external device to receive external driving information from said external device. It will be appreciated that the sensor set onboard the mobile device may be supplemented by a sensor set external to the mobile device. For example, the external device may be an engine management system of the vehicle and/or the external device may be arranged to connect to the on-car data network of the vehicle. Thus, the external device may have access to information associated with the behaviour of the vehicle (for example, the speed of the vehicle, how much the brake pedal is being pressed, etc). Such driving information can be processed and/or stored by the mobile device under control of the executed application in a manner similar to driving information derived from sensor data internal to the mobile device.

Preferably, the mobile device is arranged to interface with an external device wirelessly, for example via a Bluetooth® connection. Advantageously, this removes the need for the mobile device to be physically connected to the external device. As will be appreciated, following a driving period, a user may want to leave the vehicle and so take a personal mobile telecommunication device with them, and so a wireless interface with such an external device obviates the inconvenience of physically detaching and then subsequently re-attaching the mobile device.

Preferably, the mobile device is further controlled by the application to determine a unique identifier associated with the mobile device and retrieve from the memory and transmit via the wireless telecommunication module to a remote system said driving information paired with said unique identifier.

Advantageously, by pairing an identifier uniquely associated with the mobile device enables the remote system to unambiguously determine the source of the driving information. Accordingly, said driving information can be matched to a particular driver and/or vehicle. This is particularly useful when assessing a risk profile of said driver.

Preferably, the mobile device is controlled by the executed application to process the driving information to generate a driving score. The driving information may comprise the driving score.

Preferably, the mobile device comprises a display screen. Preferably, the display screen is touch-sensitive. Advantageously, the display screen may thereby be user-interactable. Preferably, the mobile device comprises a graphical user interface (GUI). The graphical user interface comprises user-interactable artefacts such as buttons. Preferably, the user-interactable artefacts may be displayed on the screen and receive a user input for selection or control of those artefacts. The mobile device may be controlled to selectively hide those artefacts in dependence on the state of the mobile device.

Preferably, the mobile device is controlled by the application to provide feedback about the driving information and/or values of the sensor data. Ideally, such feedback is via the display screen. For example, a detected speed may be displayed, a time elapsed may be displayed, a bearing/heading may be displayed, a detected position may be displayed and/or a detected image or sequence of images may be displayed (e.g. via a video feed).

In some embodiments there is provided a mobile telecommunications device adapted for installation to a vehicle and configured to log driving information associated with the vehicle when driven, the mobile device comprising: a sensor set comprising at least one of an image sensor, an audio sensor, an accelerometer and a positioning module; a processor for processing sensor data from at least the sensor set to derive said driving information; a memory for storing said derived driving information; a wireless telecommuni-

cations module operable to download a controlling application; and a registration means for registering the start of a driving period during which the mobile device is installed to the vehicle and the vehicle is being driven by a driver; wherein, the processor is arranged to process sensor data from the sensor set during the driving period to derive driving information associated with when and/or how the vehicle is driven and store a selection of the driving information to the memory.

In another embodiment there is provided a mobile telecommunications device adapted for installation to a vehicle and configured to log driving information associated with the vehicle when driven, the mobile device comprising: a sensor interface arranged to receive sensor data from a sensor set; a processor for processing the sensor data to derive said driving information; a memory for storing said derived driving information; a wireless telecommunications module operable to download a controlling application; and a registration means for registering the start of a driving period during which the mobile device is installed to the vehicle and the vehicle is being driven by a driver; wherein, the processor is arranged to process sensor data from the sensor set during the driving period to derive driving information associated with when and/or how the vehicle is driven and store a selection of the driving information to the memory.

Preferably, the sensor interface is arranged to receive sensor data from a sensor set external to the mobile device. Preferably, the sensor interface is arranged to interface with an external device as described in relation to the first aspect of the present invention. Advantageously, this enables a mobile device to utilise a richer or better equipped sensor set than that local to the mobile device.

In another embodiment there is provided a mobile device adapted for installation to a vehicle and configured to log driving information associated with the vehicle when driven. Preferably, the mobile device comprises a sensor interface arranged to receive sensor data from an external sensor set. The mobile device may comprise an internal sensor set. Preferably, the mobile device comprises a processor for processing the sensor data to derive said driving information. Preferably, the mobile device comprises a memory for storing said derived driving information. Preferably, the mobile device is a mobile telecommunication device, comprising a wireless telecommunications module. Preferably, the wireless telecommunications module is operable to download an application. Preferably, the mobile device comprises a registration means for registering the start of a driving period during which the mobile device is installed to the vehicle and the vehicle is being driven by a driver. Preferably, the processor is arranged to process sensor data from the sensor set during the driving period to derive driving information associated with when and/or how the vehicle is driven. Preferably, the mobile device is arranged to store a selection of the driving information to the memory. Preferably, the mobile device is arranged to transmit a selection of the driving information via the wireless telecommunication module. The mobile device may be arranged to transmit a selection of the driving information via the wireless telecommunication module to a remote system such as a remote data-logging system. Advantageously, transmitting (rather than storing) selected driving information prevents storage space local to the mobile device being used up.

In another embodiment there is provided a method of logging driving information associated with a vehicle when driven, the method comprising: adapting and installing a mobile device to the vehicle, the mobile device comprising a memory; registering the start of a driving period during which the mobile device is installed to the vehicle and the vehicle is being driven by a driver; processing sensor data from a sensor set during the driving period to derive driving information associated with when and/or how the vehicle is driven; and storing a selection of the driving information to the memory of the mobile device.

In another embodiment there is provided a data-logging system for logging driving information comprising: a database for storing a plurality of accounts, each account having a unique identifier and the database being arranged to store driving information associated with at least one of a vehicle and a driver; a communications interface arranged to communicate with a remote mobile device, and receive therefrom: a unique identifier for association of the mobile device with a corresponding one of the plurality of accounts; and driving information to be logged to that corresponding account.

The remote mobile device may be a mobile device in accordance with one of the first to fourth aspects of the present invention.

Preferably, the driving information comprises a driving score. Preferably, the driving information comprises sensor data captured and processed by the mobile device during a driving period during which the mobile device is installed to a vehicle being driven by a driver.

Preferably, the system is arranged to process the driving information logged to the corresponding account to generate a driving score. The driving score may be used to determine a risk profile for at least one of the vehicle and driver.

According to a second aspect of the present invention there is provided a method of using a mobile telecommunications device to make a safety determination for a vehicle when in use, the method comprising: downloading a software program to the mobile telecommunications device, the software program in use configuring a processor of the mobile telecommunications device when the mobile telecommunications device is removably affixed to the vehicle, to: register the start of a driving period during which the mobile telecommunications device is removably affixed to the vehicle and the vehicle is being driven by a driver; the start of the driving period being determined based on the inputs received by a user interface of the mobile telecommunications device and sensor data from a sensor set of the device, the sensor set comprising a plurality of sensors selected from a group of sensors including an image sensor, and at least one of an audio sensor, an accelerometer and a positioning module, the start of the driving period also being determined without data from sensors of the vehicle; process, at the mobile telecommunications device, sensor data from the sensor set during the driving period to derive driving information associated with how the vehicle is driven; the driving information including images captured by the image sensor; and store a selection of the driving information to a memory of the mobile telecommunications device; processing the captured images to make a safety determination for the vehicle; and issuing an alert signal in response to making an unsafe determination for the vehicle from the processing step.

According to a third aspect of the present invention there is provided a non-transitory computer-readable medium having instructions comprising a software application stored thereon, wherein the instructions are configured to be executed on a processor of a mobile telecommunications device to enable the mobile telecommunications device to log driving information associated with a driver of a vehicle, the mobile telecommunications device including a display;

a sensor set comprising a plurality of sensors selected from a group of sensors including an image sensor, and at least one of an audio sensor, an accelerometer and a positioning module; the processor; a user interface and a memory, wherein the instructions, upon execution by the processor, enable the mobile telecommunications device to: register the start of a driving period during which the mobile telecommunications device is removably affixed to the vehicle and the vehicle is being driven by a driver; the start of the driving period being determined based on the inputs received by the user interface of the mobile telecommunications device and sensor data from the sensor set, the start of the driving period also being determined without data from sensors of the vehicle; process, at the mobile telecommunications device, sensor data from the sensor set during the driving period to derive driving information associated with how the vehicle is driven; the driving information including images captured by the image sensor; store a selection of the driving information to the memory of the mobile telecommunications device; process the captured images to make a safety determination for the vehicle; and issue an alert signal in response to making an unsafe determination for the vehicle from the processing step.

For brevity, it will be understood that features, functions and advantages of different aspects of the present invention may be combined or substituted where context allows. For example, features, functions or advantages of the mobile device described in relation to the first to fourth aspects of the present invention may be provided as method steps in the method of logging driving information according to the fifth aspect of the present invention.

BRIEF DESCRIPTION OF THE DRAWINGS

In order that the invention may be more readily understood, reference will now be made, by way of example, to the accompanying drawings in which:

FIG. **1** is a schematic illustration of a system within which the mobile device of various embodiments of the present invention may be used;

FIG. **2** is an illustration of the automobile of FIG. **1** configured with a mobile device in accordance various embodiments of the present invention;

FIG. **3** is a schematic illustration of the functional components of the mobile device of FIG. **2**;

FIG. **4***a* is a process flow chart, illustrating method steps executable by the mobile device of FIGS. **2** and **3**;

FIG. **4***b* is a more detailed process flow chart, providing an example of how a driving incident or event may be detected in accordance with embodiments of the present invention; and

FIGS. **5** to **24** illustrate a graphical user interface of the mobile device according to FIGS. **1** to **4***b*.

DETAILED DESCRIPTION OF THE EMBODIMENTS

Specific embodiments are now described with reference to the appended figures.

A preferred embodiment of the present invention relates to a mobile telecommunications device for recording events associated with a vehicle, such as a car. In particular, the mobile telecommunications device is loaded with an application—a 'mobile app'—which is arranged to record and document the events surrounding an incident involving the vehicle (a 'driving incident'), such as a vehicle collision. The mobile application may be referred to as the 'Witness' application in the ensuing description.

FIG. **1** illustrates a system **1** within which a vehicle, such as an automobile **3** configured with a mobile telecommunications device executing the Witness application, may communicate with one or more remotely located devices or systems. Such devices may relate to one or more servers, such as, an emergency services server **7**, a content provider server **9**, and a personal computer **11**. Communication between the automobile **3** and the one or more remotely located devices **5**, **7**, **9**, **11** may be effected via a shared communication network **13**. The shared communication network may relate to a wide area network (WAN) such as the Internet, and may also comprise telecommunications networks. For example, the mobile telecommunications device of the present embodiments may be arranged to communicate with any one of the remotely located devices **5**, **7**, **9**, **11** via a mobile telecommunications base station **15**, which is coupled to the shared mobile telecommunications network **13**.

A main purpose of the mobile telecommunications device, when arranged within a vehicle in motion, such as the illustrated automobile **3**, is to monitor and process sensor data captured by the mobile device, to derive driving information associated with the moving automobile **3**. As mentioned previously, this driving information is subsequently used by the mobile device to determine if a driving incident or event has occurred. The term "driving incident" as used within the present context may relate to an event such as a collision, a near-miss, dangerous driving, erratic driving or similar. Similarly, the driving information may be used as a means for monitoring a driver's driving performance, and determining a driving characteristic, or user profile for the subject driver. In other words, the sensor data and/or the driving information may be used to determine for example, if the driver is a cautious driver, or a reckless driver. Further details of this alternative embodiment are described below.

The mobile telecommunication device's functionality is provided by the Witness application, which is installed in the device's local non-volatile storage, and which is executed by the device's native processor. The application may be downloaded to the mobile device via the shared communications network **13** and telephone base station **15**, from the content provider server **9**.

In use (once the application has been configured for execution on the mobile telecommunications device), when a driving incident has been detected by the mobile telecommunications device, data, comprising one or more of mobile device sensor data, derived driving information, and captured image data may be automatically forwarded to one or more of the remotely located devices **5**, **7**, **9**, **11**. For example, the mobile device may be configured such that when a driving incident is detected, such as a collision involving an automobile **3**, driving information (including image data captured by the mobile device) derived from the sensor data is automatically forwarded, via the base station **15** and shared communications network **13**.

Similarly, once a driving incident has been detected, data may also be automatically forwarded to the emergency services server **7**. For example, such data may comprise the position information of the automobile **3**, along with an automated S.O.S. message requesting assistance from the emergency services. Forwarded data may also comprise sensor data, and any relevant derived driving information, such as speed of impact, the g-forces the vehicle was subjected to during the collision, or any other information wherefrom the severity of the collision may be determined,

and which may be used to assist the emergency services in coordinating the appropriate level of response.

Optionally, an electronic message may be sent to a personal contact preselected by the user. For example, an automated message, such as an e-mail, may be forwarded to the PC **11** of the user nominated personal contact, informing the personal contact that the user of the vehicle **3** has been involved in a driving incident. Similarly, and due to the mobile device's telecommunications functionality, an electronic text message, such as an SMS (Short Message Service) may be forwarded to the telephone of the user selected personal contact, informing the contact of the driving incident. The mobile device may be equally be arranged to communicate with a personal contact via any known electronic messaging service and/or instant messaging service too. For example, via Apple's® iMessage, or RIM's® BlackBerry Messenger (BBM) service.

This functionality of forwarding a message to a nominated contact, may also be of particular benefit for managing large fleets of vehicles. For example, a car hire service. In this way, if any of the vehicles comprised in the fleet are involved in a driving incident, the car hire service may be automatically notified of the identity of the specific vehicle involved in the driving incident. In such embodiments, the nominated personal contact would be preselected by the vehicle fleet manager. The option of providing a second user selected personal contact is also envisaged. In this way, a message may be forwarded to both the car hire service for example, and to the driver's selected personal contact.

In preferred embodiments the mobile telecommunications device relates to a mobile telephone having native processing functionality, and preferably relates to a smartphone. Preferably, the mobile telephone comprises a camera arranged to enable image capture, and preferably arranged to enable a sequence of images to be captured taken in temporal succession. In other words, in preferred embodiments the mobile telephone comprises a camera configured to enable video footage of a sequence of events to be captured.

Alternatively, the mobile telecommunications device may relate to a PDA, a notepad such as an iPad®, or any other mobile device comprising local processing means and means for communicating with a telecommunications network.

FIG. **2** provides a more detailed view of the automobile **3** of FIG. **1**, and illustrates a preferred arrangement of the mobile telecommunications device **17** within the automobile **3**. In the illustrated embodiment, the mobile telecommunications device **17** relates to a smartphone configured with an image capture device, such as a camera. Preferably, the device **17** is arranged within the vehicle, such that the camera has a clear line of sight of the road in the principle direction of travel of the automobile **3**. For example, the device **17** may be attached to the windshield **19** of the automobile **3** in an adapter **21**. The adapter **21** may comprise a flexible telescopic arm, configured with a suction cup at one end for affixing the adapter to the windshield **19**, and a dock arranged at the opposite end for securely holding the telecommunications device **17** in place. The telescopic arm enables the position of the device **17** to be varied, such that a clear line of sight in the direction of travel may be obtained.

The details of the adapter **21** are irrelevant for present purposes, with the exception that it must enable a clear line of sight in the principle direction of travel of the vehicle to be obtained, and it must firmly affix the mobile to the vehicle. Affixing the mobile telecommunications device **17** to the automobile **3**, ensures that the mobile device **17** is able to accurately capture the automobile's state of motion. By principle direction of travel is intended the main direction of travel of the vehicle when operated in a conventional way, indicated by the arrow A in FIG. **2**. In other words, the forward direction of travel. The skilled reader will appreciate that whilst most vehicles, such as an automobile, may have more than one direction of travel (e.g. travelling backwards when in reverse gear), the majority of vehicles have a primary direction of travel, which is the intended direction of travel for any transit of substantial length and/or distance. Arranging the telecommunications device **17** relative to the direction of principal travel, ensures that the camera (not shown) of the telecommunications device **17** is well placed to capture any image data which may be pertinent to a subsequently detected driving incident, such as a collision.

FIG. **3** is a schematic of the modular components of the mobile telecommunications device **17** of FIG. **2**. Preferably the mobile telecommunications device **17** comprises: an image capture module **21**, an accelerometer **23**, a GPS receiver **25**, an audio capture module **27**, a communications module **29**, a processor module **31** and a storage module **33**. The image capture module **21**, accelerometer **23**, GPS receiver **25**, and audio capture module **27** form a sensor set and are generically referred to as data capture modules in the ensuing description, and are differentiated from the communications module **29**, processor module **31** and storage module **33**, in that they comprise sensors for sampling physical data.

This sampled physical data, which is also referred to as sensor data, is subsequently processed by the processor module **31** and stored in the storage module **33**.

The image capture module **21** may relate to any image capture device, such as an integrated camera commonly found in smartphones or similar mobile devices. As mentioned previously, the image capture module **21** is preferably configured to capture a plurality of images taken in temporal succession, such as provided by a video camera.

The accelerometer **23** is arranged to provide information regarding the motion of the automobile **3** along all three dimensional axes. For example, the accelerometer **23** provides information regarding the pitch, yaw and roll of the automobile **3**. Sensor data captured from the accelerometer **23** may be used to determine the g-forces the automobile has been subjected to. This is particularly useful in determining the severity of a collision. In general, the greater the g-forces experienced in a collision, the greater the risk of serious injury to the passengers of the vehicle. This information may assist the emergency services in forming an initial assessment of the severity of a collision. Furthermore, this type of data may also assist the emergency services and/or insurance provider to obtain a better understanding of the driving incident. For example, in the event of a collision, this data may assist the emergency services to obtain a better understanding of how the collision occurred. This information may subsequently be used for dispute resolution, and/or for determining culpability.

The GPS receiver **25** is arranged to provide location information, such as positional coordinates, and can also provide velocity information. When combined with the accelerometer sensor data, the GPS receiver data can be used to provide a very accurate model of a driving incident, such as a collision. In particular, the GPS sensor data provides velocity data, such as the velocity of impact. The velocity data enables one to determine if a vehicle was being driven at speeds greater than the legally permitted maximum speeds.

The audio capture module **27** provides means, such as a microphone, for recording audio data, which might be generated by a driving incident. This includes any sounds generated externally to the vehicle, for example the sound of an impact, or the sound of the crumple zone being crushed. Additionally, sounds generated internally to the vehicle are also recorded. Such audio data may also help to recreate a driving incident, and understanding the causes of the incident.

The communication module **29** provides the mobile telecommunications device **17** with functionality for communicating with the remotely located devices **5**, **7**, **9**, **11** of FIG. **1**. The communication module **29** comprises a wireless telecommunications sub-module **31** enabling communication over a telecommunications network. An optional wi-fi communication sub-module is also envisaged. Similarly, the presence of wired communication modules are also envisaged, such as a USB port and/or an IEEE 1394 interface (more commonly known as FireWire™) to support wired communication with a remote device, such as a personal computer or similar. Such a connection may be useful for the purposes of side-loading the application to the mobile device.

As mentioned previously, sensor data captured from any one of the aforementioned data capture modules **21**, **23**, **25**, **27** is processed by the processor module **33**, to generate driving information. By driving information is intended any data which may be derived from raw sensor data captured by any one of the aforementioned modules **21**, **23**, **25**, **27**. For example, g-force data is driving information which is derived from the sensor data sampled by the accelerometer **23**. The skilled reader will be familiar with the plurality of types of driving information that may be derived from sensor data sampled by the aforementioned modules, and accordingly a complete list of the different types of driving information that may be derived from sampled sensor data is omitted for brevity.

The processor module **33** is also configured to analyse sampled sensor data and generated driving information to determine if a driving incident has occurred (described in more detail below).

Sampled sensor data is stored in storage **34**, which is operatively coupled to the processor module **33**, along with any generated driving information. The storage **34** is preferably configured with a FIFO (First In First Out) storage buffer **34***a*, and a permanent storage component **34***b*. In preferred embodiments, the data capture modules are configured to sample data at periodic intervals. Preferably, these intervals are sufficiently small, of the order of milliseconds, such that for practical purposes the data capture modules may be considered to sample data continuously. The sampled data, along with any derived driving information is preferably stored in the storage buffer **34***a*, unless a driving incident has been identified, in which case the associated sensor data and driving information is stored in the permanent storage component **34***b* to avoid undesirable overwriting.

In preferred embodiments, the FIFO storage buffer **34***a* is provided with a finite amount of storage space. Nonetheless, said storage space may be predefined by the user as will be described below. In any case, once this storage space has been exhausted, the oldest recorded data is overwritten by newly sampled data, and this cycle of overwriting older data with newly sampled data is continuously carried out during operation of the telecommunications device **17**, unless a driving incident has been detected, in which case, and as mentioned previously, all data related to the driving incident is stored in a long term protected storage **34***b* to safeguard it from being overwritten by newer data.

In preferred embodiments, the mobile telecommunications device **17** may be configured with a data recording strategy by the user. This might define the frequency with which sensor data is sampled. In other words, how many measurements are made per unit of time. Furthermore, the recording strategy also defines how data is recorded. In preferred embodiments, sampled sensor data is stored in data files in the buffer **34***a*. Each data file represents a plurality of sequentially sampled sensor data, captured over a defined period of time, which will be referred to as a 'data file period'. This is best illustrated by considering captured image data, such as video footage. A video period may be defined, which period defines the unit of physical time covered by captured video footage comprised in a single video data file—this is the data file period for image data. The video data file is subsequently stored in the buffer **34***a*. For example, a five minute video period setting, instructs the processor **33** to store all sequentially captured image data captured by the image capture module **21** over a period of five minutes, in a separate video data file. It is to be understood that whilst the image capture module **21** is continuously sampling image data (in other words, it is continuously capturing image data), this plurality of captured image data is grouped together for storage in video data files, each data file representing a five minute data file period.

Sampled sensor data and derived driving information is also continuously analysed by the processor module **33** for the purposes of detecting a driving incident. As soon as a driving incident is identified, the associated sensor data and derived driving information is stored in a data file in accordance with the data recording strategy. Returning to the example described in the preceding paragraph, this entails combining the video footage captured within a temporal window of five minutes leading up to the detected driving incident, in a single video file, and storing this data file in protected storage **34***b*. Whilst each different type of sensor data may be recorded in separate data files, in preferred embodiments all the different types of sensor data sampled by the mobile telecommunications device **17** are stored together in a single data file in accordance with the user selected data recording strategy. This means that the five minute data file referred to above, preferably also comprises GPS data, accelerometer data, and audio data sampled over the five minute time period.

Data files are stored in the buffer **34***a*, unless they are associated with a driving incident, in which case they are then stored in protected storage **34***b*, which cannot be overwritten. Once the storage space comprised in the buffer **34***a* has been exhausted, the oldest data file is overwritten by a newer data file.

Data compression methods may also be used in conjunction with the present invention to improve the use of storage. For example, data comprised in data files which have not been associated with a driving incident may be compressed using compression techniques, which techniques will be known to the skilled reader. Similarly, within a data file associated with a driving incident, sensor data captured at time coordinates which are distant from the determined driving incident may be compressed. In this way, the resolution of sensor data which is directly pertinent to a driving incident is maintained, whilst sensor data which may be less relevant to the driving incident is maintained at a lower resolution.

Since the sensors of the mobile telecommunications device **17** are continuously recording sensor data, even when a driving incident is detected, the device **17** may be configured to comprise sensor data and/or driving information recorded/derived shortly after the driving incident in the same data file, since this data may also be relevant for understanding a driving incident. Furthermore, this also enables the mobile telecommunications device to record multiple driving incidents. For example, a multiple collision.

The processor module **33** may be configured with encryption means, enabling stored data files to be encrypted to prevent data tampering. Envisaged encryption means may comprise both software solutions and hardware solutions. For example, the processor module may comprise a cryptoprocessor, or the processor may be configured with code to carry out a cryptographic process.

FIG. **4***a* is a flow chart outlining the method carried out by the mobile telecommunications device **17**, to determine if a driving incident has occurred, in accordance with a preferred embodiment. An application is downloaded from the content provider server **9** of FIG. **1**, onto the mobile telecommunications device **17**, at step **36**, as previously described. This may be done over a telecommunications network. The application provides the mobile telecommunications device **17** with the previously described functionality, when executed on the device. The mobile telecommunications device is configured within the vehicle, at step **38**. This may comprise affixing the mobile telecommunications device **17** to the vehicle via an adapter, as described previously.

The recording strategy is specified at step **40**. As mentioned previously, this comprises setting the period of time that each recorded data file represents. Furthermore, it may also comprise defining the size of the buffer **34***a* and/or the number of data files that are to be stored within the buffer. Preferably, the recording strategy is specified only once, upon first use of the mobile telecommunications device **17**. Where the recording strategy has already been defined, method step **40** is skipped, and the method continues with step **42**.

The start of a driving period is registered, at step **42**. The start of the driving period determines when the recording of sampled sensor data begins. The start of a driving period may be manually entered by the user via the application's graphical user interface (GUI). Alternatively, the start of the driving period may be automated. For example, the mobile device **17** may be configured to initiate the driving period once sensor data above a minimum threshold value is recorded, indicative of the vehicle being in motion. For example, once a velocity greater than 20 kilometres per hour is detected.

Alternatively, the start of the driving period may be initiated once the application determines that the mobile telecommunications device **17** has been affixed to the vehicle. For example, the adapter **21** may comprise a registration module (not shown) arranged to register the installation and fixation of the mobile device to the vehicle and/or adapter. The registration module may comprise an NFC device. When the mobile device is brought into close proximity with the registration module, a driving period is initiated.

Once the driving period has been initiated, sensor data is sampled and recorded in storage **34**, at step **44**. Additionally, the sampled sensor data is used to generate driving information by the processor module **33**. The sampled sensor data and the driving information is continuously analysed by the processor module **33**, at step **46**.

The processor module **33** determines if a driving incident has been detected, at step **48**. This is determined on the basis of the analysis carried out at step **46**. If a driving incident has been detected, all the sensor data and driving information associated with the data file period, is stored in a data file in protected storage **34***b*, at step **50**.

There are several ways in which a driving incident may be detected. Preferably, this is an automated process, wherein the processor module **33** determines a driving incident has occurred on the basis of an observed marked variation in sensor data and/or driving information. The term 'marked variation' is to be understood to relate to a significant change in sensor data and/or driving information occurring over a very short time period. In other words, a detected impulse in recorded sensor data and/or driving information, indicative of a significant change in the state of motion of the vehicle occurring over a short time period. For example, a sudden increase in the g-forces the vehicle is subjected to, may be indicative of a collision and if observed, result in a driving incident being determined to have occurred by the processor module **33**.

Predefined threshold values may also be used to automate the detection of a driving incident. For example, each data type and/or derived driving information (e.g. acceleration, velocity, g-force, pitch, roll, yaw etc.) may be associated with a threshold value. When any one of these threshold values is exceeded, the processor module **33** may be configured to determine that a driving incident has occurred. Similarly, the automated detection of a driving incident may require that a threshold condition associated with a combination of predefined threshold values, each threshold value being associated with a different data type and/or type of driving information, must be exceeded, in order for the processor module **33** to automatically determine that a driving incident has occurred. For example, in the event of a collision, it is reasonable to expect to observe a marked variation in g-force, accompanied by a marked variation in velocity. Accordingly, the threshold condition may require that in order for a collision to be automatically detected, both a marked variation in g-force and a marked variation in speed, in excess of predefined threshold values must be observed.

Similarly, the occurrence of a driving incident may also be recorded manually by the user via the application GUI. This may be beneficial for the purposes of documenting data associated with a low velocity collision—colloquially referred to as a 'fender-bender'—which may not result in any marked variations in sampled sensor data, and therefore may not be automatically detected.

Similarly, once a driving incident has been detected, an S.O.S. message may be automatically forwarded from the mobile telecommunications device **17** to the emergency services server **7**, at step **54**. The S.O.S. message may also comprise sensor data and derived driving information, which may assist the emergency services in coordinating their response.

As mentioned previously, the mobile telecommunications device **17** will continue to sample and record sensor data even once a driving incident has been detected, unless the mobile telecommunications device **17** detects that the driving period has terminated, at step **56**. If the driving period has terminated, the present method is terminated and the device stops recording sensor data. The end of a driving period may be automatically detected by the processor module **33**, if certain conditions are met. For example, if the measured velocity of the vehicle remains zero for a predetermined period of time, the processor module **33** may infer

that the vehicle is stationary and no longer being driven, and accordingly ceases recording sensor data, and the method is terminated. If instead the processor determines that the driving period has not yet terminated, a new data file period is initiated, at step **58**, and steps **44** through **62** are repeated.

Where a driving incident is not detected at step **48**, the processor module **33** will determine if the data file period has expired, at step **60**. If the data file period has expired, then the sensor data and the derived driving information generated during the data file period is combined and stored in a single data file, for storage in the buffer **34***b*, at step **62**. The processor **3** then determines, at step **56**, if the driving period has terminated. If the driving period has not terminated, a new data file period is initiated, at step **58**. The mobile telecommunications device **17** continues to sample sensor data, to derive driving information, and steps **44** through **62** are repeated, until the driving period is determined to have terminated.

FIG. **4***b* provides more detail regarding how a driving incident may be automatically detected (i.e. steps **46** and **48** of FIG. **4***a*) in a preferred embodiment, where the mobile telecommunications device **17** is configured to sample audio data, accelerometer data, and GPS data only. Each one of these types of data is analysed in turn, at steps **64**, **66** and **68**. The analysis may comprise comparing measured sensor data and/or derived driving information with a data model. The model may comprise defined threshold values for different data types. Sampled sensor data and/or driving information may be compared with the data model to determine if a driving incident has occurred.

For example, the analysis of sampled audio data, at step **64**, may comprise comparing the recorded audio data with predetermined audio data models representing specific sounds. Such sounds may relate to the sound of tyre squeals, the sound of deforming metal, the sound of breaking glass, passenger screaming and/or shouting, the sound of airbag deployment, and any other sound which may be associated with a driving incident. Effectively, this may be considered audio fingerprinting, which serves to identify specific sounds associated with a driving incident by carrying out a signal profile analyses of the audio signal captured by the audio capture module **27**. To achieve this, the storage device **34** may comprise a database of prestored audio sound files. The audio sound files represent sounds associated with a driving incident. The captured audio signal is compared with the sound files comprised in the database, to identify matches between the captured audio signal and the database of sound files. This facilitates the audio fingerprinting of specific sounds, indicative of a driving incident, present within the captured audio data signal captured by the audio capture module **27**.

Similarly, the analysis of sampled accelerometer data, at step **66**, may comprise comparing the sampled data with predetermined accelerometer data models. The data models represent specific states of motion of the vehicle. For example, this might comprise defining threshold values for yaw, pitch and roll, which if exceeded, indicate a state of motion of the vehicle indicative of a driving incident. For example, a measured yaw value above a predetermined threshold value may be indicative of the vehicle having lost traction and is fishtailing and/or skidding. Similarly, a roll and/or pitch value above a predetermined threshold value may be indicative of the vehicle having overturned.

Accelerometer sensor data is also used for deriving driving information such as g-forces. Analysis of g-force data is also used to determine if a driving incident has occurred. For example, approximate g-force values for detecting certain driving incidents are as follows:

- Harsh braking—a deceleration of greater than 2.5 m/s^2 or forward G-force of greater than 0.7 G for more than 400 msec.
- Harsh acceleration—from stationary, an acceleration greater than 2.5 m/s^2 or backward G-force of greater than 0.7 G for more than 800 msec.
- Harsh swerving—lateral G-forces greater than 0.7 G for more than 400 msec.

The data models are preferably preconfigured and are comprised within the application executed on the mobile telecommunications device. Different data models are used depending on the type of vehicle the telecommunications device is being used with. Different vehicle types will experience different states of motion during regular operation, which must be considered in determining if a driving incident has occurred. For example, a motorcycle will display more roll and/or pitch than an automobile during regular operation. Accordingly, different data models and/or threshold values must be used to automate the identification of a driving incident for different vehicle types. The specific data models used may be selected during an initial configuration of the mobile telecommunications device, by indicating the type of vehicle the device is being used with.

On the basis of the audio data analysis and the accelerometer data analysis, the mobile telecommunications device determines, at step **72**, if a driving incident has occurred. If it is determined that a driving incident has occurred, then the telecommunications device proceeds with step **50** of FIG. **4***a*. If instead a driving incident is not detected, the telecommunications device proceeds with step **60** of FIG. **4***a*.

The GPS data analysis, at step **68**, comprises analysing positional data and velocity data for any anomalous readings. For example, a sudden deceleration followed by a zero-velocity reading lasting a predetermined period of time, may be indicative of a collision. If such a zero-velocity reading is observed at step **70**, in conjunction with anomalous audio and/or accelerometer sensor at step **72**, then a driving incident is determined and the mobile telecommunications device proceeds with step **50** of FIG. **4***a*. This is a further example of a threshold condition, discussed previously.

The previously described mobile telecommunications device and method may also be used to monitor and generate a driver profile. The driver profile may be indicative of the type of driver a user is. For example, this may comprise determining if a user is a calm and patient driver, or an aggressive driver. Also, this may comprise determining whether a user regularly flouts speed limits, and/or ignores safety distances.

For example, analysis of captured image data, such as video footage, may be used to determine if a user regularly flouts safety distances. In preferred embodiments, the mobile telecommunications device is arranged within the subject vehicle to have a clear line of sight of the road in the direction of principle motion. Accordingly, the number plate of any vehicle preceding the subject vehicle will be captured by the image capture module. Since the physical dimensions of number plates are standardised and known in each country, they may be used as a metric to scale the captured image. When combined with the known optical characteristics of the image capture module, this enables the distance of the image capture module from the image object (i.e. the preceding vehicle) to be determined at the time of image capture. This information may then be used to see if a user adheres to recommended safety distances.

Image analysis can also be used to determine driving conditions and the driving environments. For example, image processing can detect road signs, such as stop signs or traffic lights. Furthermore, driving conditions, as affected by the weather can be determined. For example, if the windscreen wipers are detected to be in motion, it can be inferred to be raining. Once the driving conditions are so determined, an assessment of the driving performance of a user can be made by determining whether the user reacts or behaves appropriately to the driving conditions. For example, if the driver is seen to be jumping red lights, or driving dangerously in rain or snow, then a higher risk profile may be assigned to that driver.

Similarly, accelerometer and g-force data may be used to determine if a user has an erratic driving style. For example, a user that generates sharp variations in g-force data and accelerometer data during regular operation of a vehicle, may be considered to drive erratically, and therefore at greater risk of being involved in an accident,

The mobile telecommunications device may also be configured to interface and communicate directly with a vehicles native telemetry systems. For example, the majority of modem cars have inbuilt electronic control systems or engine management systems, arranged to collect data regarding vehicle system performance. This data may be communicated to the mobile telecommunications device either via a wired physical connection, such as USB (Universal Serial Bus), or via a wireless communication protocol such as Bluetooth®. This data may subsequently be used by the mobile telecommunications device to complement sensor data captured directly by the telecommunications device. In this way a more accurate model of a driving incident, and/or of a user profile may be generated. For example, native vehicle telemetric systems may comprise electronic tyre pressure sensors, and are able to detect if a tyre is under and/or over-inflated. This information may be communicated to the mobile telecommunications device and may help to explain the causes for a driving incident, such as a sudden loss of traction resulting from a burst tyre.

Further features of the Witness application, are set out below.

Benchmarking

It will be appreciated that different sensor types, phones, mounting positions, vehicles, drivers and road conditions may generate differing outputs for driving behaviour that is 'safe'. To account for this, the Witness application may have the following functionality:

During a 'training mode' (e.g. first week of enabling the Witness application) the input from the sensors are used to build up a 'benchmark' for a particular driver's typical driving conditions.

Assuming an accident does not occur during this training mode, the benchmark data can be subsequently used to assess the occurrence of driving incident.

There is preferably an option to notify the Witness application of a change in parameters (e.g. different driver, driving off-road etc). Thus a number of 'profiles' may be set up. Each profile may require an independent training mode period.

If the Witness application incorrectly detects that a driving incident has occurred, it can receive feedback from the user to modify its sensitivities. E.g. a more aggressive driver is actually driving.

Crash/Collision Management

On detection of a crash (or other driving incident) the Witness application is arranged to take one or more of the following actions:

Announce that it has detected an accident (audio/screen prompt)

Call the emergency services (with option to cancel)—e.g: Audio/screen prompt: 'Witness has detected that you have been involved in a (serious) accident and will call the emergency services. If this is not the case, please cancel within 10 seconds.'

Provide reassurance

Provide the user with a checklist of things to do:

Take photographs of vehicles involved in the incident (inc number plates)

Take down name, address, insurance details etc of 3rd parties involved in incident

Communicate to the insurance company that an incident has been detected (e.g. low bandwidth data or text message)

Protect the high quality recorded data so it is not overwritten

If appropriate—or in response to a request from a communication to the phone from the insurance company—transmit all or selected portions of the recorded data associated with the incident. Data processing for generating a user profile

Further features of the user profile generation embodiment are summarised:

If the Witness application incorrectly detects an event or incident of significance, and receives feedback that the vehicle was not involved in an accident (but was in a near miss)—this could alter the risk profile of the driver. For example—if this happens frequently, but no accident occurs over a given period, this could be an indicator that the driver is good at reacting to potential hazards.

Erratic driving (e.g. jerky steering or braking detected by G-force sensor).

Driving faster than the speed limit allocated to a given road (detected by GPS).

Further details regarding the features and functionality of the Witness application, in particular the graphical user interface of the Witness application, are now described.

Referring to FIG. **5**, a first page **80** of the Witness application user manual is shown in which an image of the Main Menu (the top-level menu) **82** is displayed. The Main Menu is displayed when a user first runs the application on a smart-phone, such as the iPhone® 4. The main menu includes the following user-selectable buttons:

Recording Screen **84**

File Management **86**

Settings **88**

Accident Management **90**

Information **92** (displays up a manual, as shown in FIGS. **5** to **14**).

Selecting the Recording Screen button **84** opens the Recording Screen **94**—the second image shown in FIG. **5**. The Recording Screen **94** contains a video feed **96** from the camera of the smart-phone, which occupies the majority of the visible screen area. Overlaid on to the video feed is the detected speed of the vehicle **98** (e.g. 0 mph), heading **100** (e.g. south by south-west) and the elapsed recorded time **102** (e.g. 00:00). Displayed in a left column of the Recording Screen are additional user selectable buttons:

Keep current video **104** (pressing this button will automatically copy the current video—and the previous video segment—to the protected storage **34***b*, and prevents that information from being overwritten. The user is advised to press this button in the event of a driving incident that needs to be recorded).

Take photo **106** (captures a still photograph).

Exit Recorder **108** (returns to main screen).

Start/Stop Recording **110** (starts recording video footage—and other data).

Referring to FIG. **6**, a second page **112** of the Witness application user manual is shown, in which an image of the Recording Screen **114** is shown and described operating in a map-displaying mode rather than a video-feed mode.

During recording, (i.e. when the 'Start/Stop Recording' button **110** is pressed) the Exit Recorder button in the Recording Screen is substituted with a Map Display button **116**. Pressing it will toggle between the modes showing the video feed and a map of the current location.

Referring to FIG. **7**, a third page **118** of the Witness application user manual is shown, in which the File Management Screen **120** is shown and described. The File Management Screen **120** can be accessed by pressing the File Management Button **86** in the Main Menu.

The File Management Screen **120** displays video and associated data (e.g. telemetry data) that has been previously recorded. The stored data is contained in either a protected area of storage or in a "Recording Stack". Data files in the protected area are saved and so not overwritten as part of a Recording Strategy. In contrast, data files in the Recording Stack may be overwritten as part of the Recording Strategy.

As illustrated in FIG. **7**, the bottom section of the list represents the "Kept" data files **122**, whereas the top section of the list represents the "Recording Stack" **124**. "Kept" data files **122** can be edited and deleted from the File Management Screen **120**, whereas "Recording Stack" data files cannot. Editing "Kept" data files can involve renaming them.

The recorded data files are listed on screen along with the time and date of the recording and the electronic size of the data file. Accordingly, the user is provided with feedback about how big the data files are, and so if the smart-phone is low in storage, the user can elect to delete certain "Kept" data files. "Recording Stack" data files will be automatically overridden by the Recording Strategy.

The controls on the toolbar at the bottom of the recordings screen allow a user to change the selection mode of the video stack and includes:

Video **126** (when highlighted, if a data file is selected, a video recording playback screen will be displayed).

Map **128** (when highlighted, if a data file is selected, then a map will be displayed showing the area over which the recording was made).

Export **130** (when highlighted, a selected data file will be passed to an Export Screen where export options will be provided).

Keep **132** (when highlighted, if a "Recording Stack" data file is selected, then a user will be prompted to name it, and then it will be stored as a "Kept" data file).

The icons in the File Management Screen change in dependence on the selected mode. For example, FIG. **20** shows the icons **134** displayed when the Video selection mode is highlighted; FIG. **21** shows the icons **136** displayed when the Map selection mode is highlighted; FIG. **22** shows the icons **138** displayed when the Export selection mode is highlighted and FIG. **23** shows the icons **140** displayed when the Keep selection mode is highlighted. Advantageously, this provides improved feedback to a user about what selection mode is highlighted and so what action is likely from the selection of a data file.

Referring to FIG. **8**, a fourth page **142** of the Witness application user manual is shown, in which an image of a Recording Playback screen **144** is shown and described. The Recording Playback screen is invoked by highlighting the Video Mode **126** in the File Management Screen **120** and selecting an appropriate data file.

In the Recording Playback screen **144** it is possible to play back a pre-recorded video feed associated with a chosen data file. As well as playing back the recorded video feed, the Recording Playback screen also displays other associated data such as telemetry data **146**. For example, date, time, speed, forward/backward G-forces, latitude, longitude and heading information is overlaid onto the video feed. As the video is played back, these values will typically change depending on the behaviour of the vehicle, as recorded by the mobile device.

Forward and backward G-forces are those that correspond to the forward and backward movement of the vehicle and are the primary metric for determining an event such as a crash. However, other G-forces (e.g. up/down and side-to-side) may also be measured by the device—even if they are not necessarily displayed on the mobile screen.

As recited in FIG. **8**, the Recording Playback screen provides further user controls in the form of:

Playback Position Scrub Bar **148** (horizontal bar at bottom of screen)

Playback Speed Bar **150** (vertical bar at left side of screen)

Pause **152** (pauses playback)

Eject **154** (return to previous screen)

Loop **156** (plays the data file continuously)

The Playback Position Scrub Bar **148** allows a user to jump to different positions within the recording without necessarily needing to watch all of the recorded footage. Advantageously, this allows a user to more quickly locate a desired item of footage within a given data file. Also, the Playback Speed Bar **150** can be used to speed up or slow down the playback of the data file. This allows a desired item of footage to be found more quickly through sped-up playback, and also allows an item of footage to be more carefully analysed through slowed-down playback. Furthermore, it is possible to zoom in and out of a region of the video file using a 'pinch and zoom' movement as is standard with most multi-touch touch-screen devices.

Referring to FIG. **9**, a fifth page **158** of the Witness application user manual is shown, in which a different type of Recording Playback screen **160** is shown and described. Specifically, the image represents playback of a pre-recorded data file as can be invoked by highlighting the Map Mode **128** in the File Management Screen **120** and selecting an appropriate data file.

In contrast with the Video Mode playback, this Map Mode playback shows a map of the area **162** where the recording took place. A blue breadcrumb trail **164** is overlaid on to the map showing the extent of movement of the vehicle during the recorded period. A scrub slider **166** is shown, which is user-operable to adjust the time within the recorded period. As the slider is adjusted, a pin **168** moves along the blue breadcrumb **164** to show the position of the vehicle at the time as specified by the slider **166**. Tapping the pin **168** displays associated telemetry data **170** at that position and time.

Referring to FIG. **10**, a sixth page **172** of the Witness application user manual is shown, in which an image of a Video Export Screen **174** is described. The Video Export Screen **174** may be invoked by highlighting the Export button **130** in the File Management Screen **120** and selecting an appropriate data file.

The Video Export Screen **174** allows the quality of the video associated with the selected data file to be adjusted, before that video is exported. Advantageously, this can allow

the user to control the size of the data to be exported. Telemetry data (i.e. sensor data) is also exported, embedded within the video file. Video data can be exported with or without sound, depending on the permissions of the user. Export typically involves copying data files from the mobile device to a local computer (e.g. via a data cable) or a remote server (e.g. via a wireless connection).

Referring to FIG. **11**, a seventh page **176** of the Witness application user manual is shown, in which an image of the Settings Screen **178** is displayed and described. The Settings Screen **178** allows the operation of the Recording Strategy to be controlled. Specifically, the Settings Screen allows a user to select the number of video segments that the application should store, and the size of those segments (i.e. a data file period). Accordingly, the user is able to set a limit to the storage usage of the Recording Stack (i.e. the size of the buffer **34***a*) part of the program. The user can also control the storage usage of the Recording Stack through the use of the video quality buttons.

Note that the Witness application may be arranged to calculate the remaining memory available on the smartphone and suggest the appropriate settings automatically.

The Recording Strategy involves maintaining a user-controlled number of video segments. When a new video recording is initialised—instantiating a new segment—this is written over the oldest video segment. Thus only the most recently recorded videos are maintained in the Recording Stack.

Another setting that can be controlled in the Settings Screen **178** is the G-force threshold at which the Witness application will assume that a crash has taken place. It is expected that different vehicles and driving styles will need different G-force thresholds to be set to ensure a reasonable sensitivity to crash forces whilst also prevent crash detection false positives. It should be noted that although the manual recites "Raise the sensitivity if you find that crash detection is triggered during normal driving . . . " it is the sensitivity threshold that is to be raised, and not the sensitivity itself. A slider **180** allows the sensitivity threshold to be set via the touch-sensitive screen.

The Settings Screen **178** also has a button **182** to allow a user to define more settings via a More Settings Screen.

Referring to FIG. **12**, an eighth page **184** of the Witness application user manual is shown, in which an image of the More Settings Screen **186** is displayed and described. Here, it is possible for the user to select speed units **188** and also select whether the map should be displayed during recording **190**, and at which speed it should be displayed in favour of the video feed. This is a safety feature of the Witness application that hides the video feed during recording when the vehicle is detected as travelling above a predetermined speed. The video feed is replaced by a map of the location of the vehicle—as is typical with in-vehicle GPS devices. Note that although the on-screen video feed is replaced with a map, video recording continues in the background.

In alternatives, the application may be arranged to detect the vehicle speed, and at a particular speed, switch off the screen entirely. It should be understood that the device will continue to record video, telemetry and other information even when the screen is switched off. Entirely switching off the screen of the device is advantageous as it significantly reduces the drain on the battery of the mobile device.

Note that the Witness application is also arranged to interface with the phone to detect low-light conditions and in response change the brightness of the screen to prevent the user/driver being dazzled. This can also save battery life.

The More Settings Screen **186** also includes a Personal Details button **192** which, when pressed invokes a Personal Details Screen.

Referring to FIG. **13**, a ninth page **194** of the Witness application user manual is shown, in which an image of the Personal Details Screen **196** is displayed and described.

Here, the name **198**, vehicle registration number **200**, mobile number **202** and email address **204** to be used in an emergency, can be specified by the user. In the event of a detected incident, these details, along with information regarding the detected incident (e.g. time of incident, location and optionally telemetry data) will be emailed to the specified email address automatically. This can ensure that the chosen recipient of that email will be informed immediately about the occurrence and nature of the detected incident.

This Personal Details Screen **196** also allows the user to set whether it is possible for the video stack to be deleted **206**. A security PIN protects the changing of this option so that if a first user having the PIN (for example, a parent) can review the driving style and behaviour of a second user not having the PIN (for example, their son or daughter) by reviewing the Recording Stack—as the Recording Stack cannot be deleted by that second user. As shown in FIG. **24**, the PIN can be set for the first time by entering it twice into the appropriate PIN fields **208**.

Referring to FIG. **14**, a tenth page **210** of the Witness application user manual is shown, in which images of an Accident Management Screen **212** and Witness Details Screen **214** are displayed and described.

The Accident Management Screen **212** can be invoked by the user selecting the accident management button **90** on the Main Menu, or can be automatically switched to after the Witness application has detected that there has been an incident (e.g. via G-forces exceeding a threshold level). Similarly, data can automatically be permanently stored as "Kept" and/or sent if high G-forces are detected.

As can be seen on the Accident Management Screen **212**, there are the following user selectable buttons:

Accident Advice/What to do **214**

This option provides guidance as to what to do during an accident—see FIGS. **15** and **16** for the displayed Accident Advice Screens.

Witnesses **216**

This option invokes functionality to allow the collection of information from or about witnesses to an incident. An image of the Witnesses Detail information summary screen **214** is shown in FIG. **14**. FIG. **17** shows the Witness Detail information collection screen **218**. Voice notes can also be taken via the microphone of the smart-phone.

Photos **220**

This option enables the camera to allow a user to capture images associated with an incident.

Drivers **222**

This option invokes functionality to allow collection about the other drivers involved in an incident. The Drivers Detail information collection screen **224** is shown in FIG. **18**.

Your Details **226**

This option provides a readily available store of the details of the user—as to be provided to other drivers—and can contain name and address. The 'Your Details' screen **228** is shown in FIG. **19**.

Details recorded via the Accident Management Screen **212** are electronically authenticated and feature a time-stamp. In alternatives, this data may be encrypted to ensure the integrity of the stored data.

Furthermore, in alternatives, the exchange of the details of the drivers and witnesses can be conducted, at least in part, via Bluetooth® (for example, between mobile devices)—and/or via email. Relevant information associated with the driver is pre-stored on the Witness application in a format that can be sent readily, via a communication channel such as Bluetooth® or email.

Finally, note that in each Screen or Menu, there is a button **230** provided to go back to the previous menu. Also, when certain actions are performed or selected by a user, the Witness application is arranged to provide an audible feedback signal (for example, a beep). For example, this could be in response to starting a recording, keeping a video segment and/or a stopped recording.

ALTERNATIVES AND EXTENSIONS

The Witness application can be extended to interface with remote users to allow them to control the operation of the application as well as view information logged by the application.

With such a monitoring system, it is unpractical to actively monitor each and every mobile device and receiving and handling the sheer quantity of data from each and every device would also be very difficult.

Consequently, the device monitoring system and the mobile devices are advantageously arranged to automatically and intelligently interface with one another in a way that minimises the computational and bandwidth burden on the device monitoring system.

In particular, each mobile device running the Witness application is arranged to make a determination as to whether there is a need to transfer data to the device monitoring system. For example, the Witness application may be arranged to automatically send data to the device monitoring system that only has high G-force activity associated with it, as this may be indicative of a crash or another driving incident. Alternatively, the Witness application may be arranged to send detailed or high-bandwidth information if a user indicates that an accident has occurred.

In either case, the video segments and associated sensor and/or derived driving information data associated with the relevant event will be sent. However, no other data (for example, from another date) will be sent.

Alternatively, less computationally or bandwidth intensive information may be sent on a periodic basis—for example, every day, week or month. Such general information may be sent to establish a profile of a particular user. For example, many high G-force related activities may indicate that the driver is driving aggressively. A determination about the profile can be made automatically by requesting and automatically analysing further data. For example, the location and speed information can be used to determine whether a vehicle is found to frequently break the speed limit. If this is the case, then the profile of the user can be set accordingly.

Such general and periodically obtained information can also be used to remotely adjust the settings of the application. For example, many high G-force related activities may instead indicate that the set up of the car is such that the mobile device is subjected to high G forces (rather than the driver driving aggressively). If the driving is determined to be safe, but the mobile device is setting off many false positives, then the device monitoring system can automatically adjust the settings of the application. For example, the G-force sensitivity threshold may be increased remotely.

Thus, the initial data that is automatically transmitted from the mobile device to the vehicle monitoring system is limited in bandwidth so as not to overload the vehicle monitoring system as a whole. However, after processing or analysis is performed on the initial data, further information may be requested. For example, further information may be requested automatically by the system or manually by a controller. Such further information may include high resolution video logs and sensor data and derived driving information such as G-force measurements.

It will be understood that the mobile device may also automatically keep certain data at random. Furthermore, the reason for keeping certain data may also be logged (e.g. logged as a result of a manual request by the user, or in response to a high G-force event).

However, so that users do not wrongfully benefit from such incentives, it is necessary to enforce the correct and consistent use of the Witness application.

Accordingly, the application may include measures to guarantee that the application is enabled whenever a given insured vehicle is being driven.

Such measures may involve matching data recorded by the Witness application with that recorded independently by the vehicle. For example, the Witness application records the distance travelled during every journey. To ensure the summed distances of all journeys tracked by the Witness application tally with the total travelled distance of the vehicle, the user may be prompted to enter the odometer mileage periodically.

It will be appreciated that such a tallying exercise depends on the Witness application being used every time one particular vehicle is driven. However, in alternatives, if the Witness application is used with different vehicles, the Witness application may be arranged to register the different vehicles so that their respective odometer readings can be tallied with distance recordings associated with each respective vehicle.

Other measures can be implemented in conjunction with the Witness application to guarantee that the application is enabled whenever a given vehicle is being driven. For example, the mobile device on which the Witness application is installed may comprise an NFC device, such as an RFID tag. The NFC device may be compatible with a complementary device on a so-called 'smart-holster' into which the mobile device may be fitted during operation.

The smart-holster interacts with the NFC device on the smart-phone to determine whether or not the smart-phone is inserted into the smart-holster. The smart-holster can then be interfaced with the engine management system of the vehicle so that the vehicle may be activated and driven only when the mobile device is in place within the smart-holster.

It will be appreciated that the mobile device has so far been described in the context of a smart-phone. However, it will be appreciated by a person skilled in the art that other devices may also be suitable for performing the functions described in relation to the Witness application. For example, the Witness application may be adapted to run on a general purpose tablet-style computing device, such as an iPad®.

Furthermore, it will be understood that features, advantages and functionality of the different embodiments described herein may be combined where context allows. In addition, a skilled person will appreciated that the functionality described above may be implemented using the mobile device suitably programmed.

Having described several exemplary embodiments of the present invention and the implementation of different functions of the device in detail, it is to be appreciated that the skilled addressee will readily be able to adapt the basic

configuration of the device to carry out described functionality without requiring detailed explanation of how this would be achieved. Therefore, in the present specification several functions of the device have been described in different places without an explanation of the required detailed implementation as this not necessary given the abilities of the skilled addressee to code functionality into the device.

The invention claimed is:

1. A data-logging system configured to monitor how safely a vehicle is being driven by a driver throughout a driving period and to log, during the driving period, driving information representing movement of the vehicle whilst the vehicle is being driven by the driver, the data-logging system comprising:

a remote data-logging server;

a mobile telecommunications device including a user interface, a processor, a memory, and a sensor set comprising at least an accelerometer and a positioning module; and

an application comprising computer-executable instructions downloaded onto the memory, wherein the computer-executable instructions, when executed by the processor, cause the mobile telecommunications device to:

process, using the processor, raw sensor data representing at least acceleration of the vehicle and position of the vehicle from the sensor set to generate derived driving information representing how safely the vehicle is being driven by the driver throughout the driving period, wherein the driving period is defined by a duration of a vehicle journey, and the derived driving information includes a driving score, and wherein the processing of the raw sensor data, by the processor, includes determining a driving incident occurring within the driving period by comparing the raw sensor data against at least one predetermined threshold value and detecting the driving incident when the raw sensor data exceeds the at least one predetermined threshold, the driving incident including at least one of harsh braking, harsh acceleration, harsh swerving or a vehicle accident;

generate the derived driving information without data from vehicle sensors throughout the driving period in which the mobile telecommunications device is within the vehicle and the vehicle is being driven by the driver; and

transmit at least some of the derived driving information including the driving incident to the remote data-logging server,

wherein the remote data-logging server is configured to log the at least some of the derived driving information received from the mobile telecommunications device and comprises:

a database for storing a plurality of accounts, at least one of the plurality of accounts having a unique identifier, and the database being configured to store the selection of the derived driving information transmitted from the mobile telecommunications device to the at least one account, the derived driving information being associated by the unique identifier to the vehicle and the driver; and

a communications interface configured to communicate with the mobile telecommunications device and receive therefrom:

the unique identifier for association of the mobile telecommunications device with the at least one of the plurality of accounts; and

the at least some of the derived driving information transmitted from the mobile telecommunications device to be logged to the at least one of the plurality of accounts.

2. The data-logging system of claim **1**, wherein execution of the computer-executable instructions by the processor further causes the mobile telecommunications device to:

store the raw sensor data relating to the driving incident; and

transmit the stored raw sensor data to the remote data-logging server.

3. The data-logging system of claim **2**, wherein execution of the computer-executable instructions by the processor further causes the mobile telecommunications device to store the raw sensor data generated before, during, and after the driving incident that is continuously collected, associated with the driving incident.

4. The data-logging system of claim **1**, wherein execution of the computer-executable instructions by the processor further causes the mobile telecommunications device to register a start of the driving period in response to an initialization input generated automatically in response to the raw sensor data having predetermined values.

5. The data logging system of claim **1**, wherein the remote data-logging server is further configured to process the derived driving information logged to the at least one of the plurality of accounts over a plurality of driving periods, including the driving period, to generate an aggregated driving score used to determine a risk profile for at least one of the vehicle and the driver.

6. The data logging system of claim **1**, wherein the driving period comprises a plurality of portions of time throughout the driving period, and the execution of the computer executable instructions by the processor further causes the processor to select a portion of time related to the driving incident from the plurality of portions of time for transmission to the remote logging server and to reduce the amount of data transmitted by transmitting raw sensor data relating to the selected portion of time to the remote data logging server.

7. The data-logging system of claim **6**, wherein the driving incident, determined by the processor, is defined by a marked variation in a change of the raw sensor data over at least a portion of the plurality of portions of time during the driving period indicative of a difference in a state of motion of the vehicle occurring over the at least a portion of the plurality of portions.

8. The data-logging system of claim **7**, wherein execution of the computer-executable instructions by the processor further causes the mobile telecommunications device to select, prior to transmitting of the derived driving information, the raw sensor data relating to the driving incident.

9. The data-logging system of claim **8**, wherein, to select the raw sensor data relating to the driving incident, execution of the computer-executable instructions by the processor further cause the mobile telecommunications device to select the raw sensor data generated before, during, and after the driving incident.

10. The data-logging system of claim **9**, wherein execution of the computer-executable instructions by the processor further causes the mobile telecommunications device to transmit the selected raw sensor data to the remote data-logging server.

11. The data-logging system of claim 7, wherein the at least a portion of the plurality of portions comprises a five-minute time period.

12. The data logging system of claim 6, wherein the remote-logging server is configured to store the raw data relating to the selected portion of time related to the driving incident to the at least one account.

13. A data-logging system configured to monitor how safely a vehicle is being driven by a driver throughout a driving period and to log driving information representing movement of the vehicle whilst the vehicle is being driven by the driver during the driving period, the data-logging system comprising:

a remote data-logging server;

a mobile telecommunications device including a user interface, a processor, a memory, and a sensor set comprising at least an accelerometer and a positioning module; and

an application comprising computer-executable instructions downloaded onto the memory, wherein the computer-executable instructions, when executed by the processor, cause the mobile telecommunications device to:

process, using the processor, raw sensor data from the sensor set representing at least acceleration of the vehicle and position of the vehicle to generate derived driving information representing how safely the vehicle is being driven by the driver throughout the driving period, wherein the driving period is defined by a duration of a vehicle journey comprising a plurality of portions of time, and wherein processing of the raw sensor data, by the processor, includes determining a driving incident occurring within the driving period by comparing the raw sensor data against at least one predetermined threshold value and detecting the driving incident when the raw sensor data exceeds the at least one predetermined threshold, the driving incident including at least one of harsh breaking, harsh acceleration, harsh swerving or a vehicle accident;

generate the derived driving information without data from vehicle sensors throughout the driving period in which the mobile telecommunications device is within the vehicle and the vehicle is being driven by the driver; and

transmit at least some of the derived driving information including the driving incident to the remote data-logging server;

wherein the remote data-logging server is configured to log at least some of the derived driving information, including the driving incident, received from the mobile telecommunications device and comprises:

a database for storing a plurality of accounts, at least one of the plurality of accounts having a unique identifier, and the database being configured to store the selection of the derived driving information, associated by the unique identifier to the vehicle and the driver, to the at least one account; and

a communications interface configured to communicate with the mobile telecommunications device, and receive therefrom:

the unique identifier for association of the mobile telecommunications device with the at least one of the plurality of accounts; and

the derived driving information transmitted from the mobile telecommunications device to be logged to the at least one of the plurality of accounts, and

wherein the remote data-logging server is further configured to process the derived driving information logged to the at least one of the plurality of accounts to determine a risk profile for at least one of the vehicle and driver.

14. The data-logging system of claim 13, wherein the at least one driving incident is defined by an occurrence of the raw sensor data exceeding a predetermined value during the driving period.

15. The data-logging system of claim 14, wherein execution of the computer-executable instructions by the processor further causes the mobile telecommunications device to:

store the raw sensor data relating to the at least one driving incident; and

transmit the stored raw sensor data to the remote data-logging server.

16. The data-logging system of claim 15, wherein execution of the computer-executable instructions by the processor further causes the mobile telecommunications device to store the raw sensor data generated before, during, and after the at least one driving incident.

17. The data-logging system of claim 13, wherein execution of the computer-executable instructions by the processor further causes the mobile telecommunications device to determine the at least one driving incident as a marked variation in a change of the raw sensor data over at least a portion of the plurality of portions of time during the driving period indicative of a difference in a state of motion of the vehicle occurring over the at least a portion of the plurality of portions.

18. The data-logging system of claim 17, wherein execution of the computer-executable instructions by the processor further causes the mobile telecommunications device to select, prior to transmitting the selection of the derived driving information, the raw sensor data relating to the at least one driving incident.

19. The data-logging system of claim 18, wherein to select the raw sensor data relating to the at least one driving incident, execution of the computer-executable instructions by the processor further causes the mobile telecommunications device to select the raw sensor data generated before, during, and after the at least one driving incident.

20. The data-logging system of claim 19, wherein execution of the computer-executable instructions by the processor further causes the mobile telecommunications device to transmit the selected raw sensor data to the remote data-logging server.

21. The data-logging system of claim 13, wherein the sensor set further comprises an image sensor.

22. The data-logging system of claim 13, wherein the driving information further comprises one or more of velocity, direction of travel, an indication of exceeding a velocity limit, or data representing jerky steering.

23. The data-logging system of claim 13, wherein execution of the computer-executable instructions by the processor further causes the mobile telecommunications device to register the start of the driving period in response to an initialization input generated automatically in response to the raw sensor data having predetermined values.

24. A data-logging system configured to monitor how safely a vehicle is being driven by a driver throughout a driving period and to log driving information representing movement of the vehicle whilst the vehicle is being driven by the driver during the driving period, the data-logging system comprising:

a remote data-logging server;

a mobile telecommunications device including a user interface, a processor, a memory, and a sensor set comprising at least an accelerometer and a positioning module;

an application comprising computer-executable instructions downloaded onto the memory, wherein the computer-executable instructions, when executed by the processor, cause the mobile telecommunications device to:

process, using the processor, raw sensor data from the sensor set representing at least acceleration of the vehicle and position of the vehicle, to generate derived driving information representing how safely the vehicle is being driven by the driver throughout the driving period, wherein the driving period is defined by a duration of a vehicle journey comprising a plurality of portions of time, and wherein the driving information includes at least one driving incident, the at least one driving incident being determined by the processor establishing an occurrence of the raw sensor data exceeding a predetermined value during the driving period, the driving incident including at least one of harsh braking, harsh acceleration, harsh swerving, or a vehicle accident;

generate the derived driving information without data from vehicle sensors throughout the driving period in which the mobile telecommunications device is within the vehicle and the vehicle is being driven by the driver;

store the raw sensor data relating to the at least one driving incident; and

transmit at least some of the derived driving information, including the at least one driving incident, and the stored raw sensor data corresponding to the at least one driving incident;

wherein the remote data-logging server is configured to log the derived driving information and the raw sensor data received from the mobile telecommunications device and comprises:

a database for storing a plurality of accounts, at least one of the plurality of accounts having a unique identifier and the database being configured to store the at least some derived driving information associated by the unique identifier to the vehicle and the driver, and the raw sensor data, to the at least one of the plurality of accounts;

a communications interface configured to communicate with the mobile telecommunications device, and receive therefrom:

the unique identifier for association of the mobile telecommunications device with the at least one of the plurality of accounts; and

the at least some derived driving information and the raw sensor data to be logged to the at least one of the plurality of accounts,

wherein the remote data-logging server is further configured to process the derived driving information and the raw sensor data logged to the at least one of the plurality of accounts to determine a risk profile for at least one of the vehicle and driver.

25. A mobile telecommunications device configured to log driving information associated with how safely a vehicle is being driven, the mobile telecommunications device comprising:

a sensor set comprising at least an accelerometer and a positioning module;

a processor;

a memory; and

an application comprising computer-executable instructions downloaded onto the memory, wherein the computer-executable instructions, when executed by the processor, cause the mobile telecommunications device to:

determine, based on the raw sensor data from the sensor set, a start of a driving period at which the mobile telecommunications device is within the vehicle and the vehicle is in use, wherein the driving period is defined by a duration from a start to an end of a vehicle journey and the duration is comprised of a plurality of portions of time;

process, using the processor, the raw sensor data from the sensor set representing at least acceleration of the vehicle and position of the vehicle throughout the driving period to derive driving information associated with how safely the vehicle is driven by the driver, the driving information representing movement of the vehicle whilst the vehicle is being driven by the driver throughout the driving period, wherein the processing of the raw sensor data, by the processor, includes determining a driving incident occurring within the driving period by comparing the raw sensor data against at least one predetermined threshold value, and detecting the driving incident when the raw sensor data exceeds the at least one predetermined threshold, the driving incident including at least one of harsh braking, harsh acceleration, harsh swerving or a vehicle accident;

wherein the driving information is derived without data from vehicle sensors throughout the driving period;

transmit at least some of the derived driving information including the driving incident to a remote data-logging server; and

wherein the mobile telecommunications device is controlled by a downloaded application to register the start of the driving period in response to an initialization input generated automatically in response to the raw sensor data having a predetermined start value.

26. The mobile telecommunications device of claim **25**, wherein execution of the computer-executable instructions by the processor further causes the mobile telecommunications device to detect the end of the driving period in response to an ending input generated automatically in response to the raw sensor data having a predetermined end value.

27. The mobile telecommunications device of claim **25**, wherein the driving period comprises a plurality of portions of time throughout the driving period, and the execution of the computer executable instructions by the processor further causes the processor to select a portion of time related to the driving incident from the plurality of portions of time for transmission to the remote logging server and to reduce the amount of data transmitted by transmitting raw sensor data relating to the selected portion of time to the remote data logging server.

28. The mobile telecommunications device of claim **25**, wherein execution of the computer-executable instructions by the processor further causes the mobile telecommunications device to determine the at least one driving incident as a marked variation in a change of the raw sensor data over at least a portion of the plurality of portions of time during

the driving period indicative of a difference in a state of motion of the vehicle occurring over the at least a portion of the plurality of portions.

* * * * *