

UNITED STATES PATENT AND TRADEMARK OFFICE

BEFORE THE PATENT TRIAL AND APPEAL BOARD

CLEARCORRECT OPERATING, LLC.,
Petitioner,

v.

ALIGN TECH., INC.,
Patent Owner,

Case Nos. IPR2025-00818
IPR2025-00819
IPR2025-00820
IPR2025-00821
Patent Nos. 10,973,613,
11,154,384,
11,648,090,
11,648,091

Declaration of Kelley M Hayes Greenhill Regarding Internet Archive URL's

I, Kelley M Hayes Greenhill, state and declare as follows:

I. Introduction

1. I have prepared this Declaration in connection with *Inter Partes* Review proceedings of U.S. Patent Nos. 10,973,613; 11,154,384; 11,648,090; and 11,648,091, instituted as IPR2025-00818, -819, -820, and -821, respectively.

2. I am currently the Director of Research and Information Services at Finnegan, Henderson, Farabow, Garrett & Dunner, LLP, located at 901 New York Ave., NW, Washington DC 20001.

3. I am over eighteen years of age and am competent to make this Declaration. I make this Declaration based upon my own personal knowledge and my professional knowledge of library science practices.

4. I earned a Master of Science in Library and Information Science degree from the Catholic University of America in 1995, and a Bachelor of Arts in Political Science degree from Duquesne University in 1989. I have worked as a law librarian for over thirty years. I have been employed by Finnegan, Henderson, Farabow, Garrett & Dunner, LLP since 2019. Before that, from 2015 to 2019, I was employed as a Research Librarian at Northrop Grumman Corporation, and from 1995 to 2015, I was employed as a Law Library Manager for Sterne, Kessler, Goldstein & Fox, p.l.l.c.

II. Standard Library Practice for Receiving, Cataloging, and Making Materials, Publicly Available and Accessible

5. I have knowledge of and experience with standard library practices regarding the receipt, cataloging, searching, accessing, and making print and electronic materials available and accessible to the public. I also have knowledge of and experience with searching, identifying, and downloading materials from the Internet Archive located at <https://web.archive.org/>

III. The Internet Archive

6. The Internet Archive is a 501(c)(3) non-profit founded in 1996. Its core mission is to provide “universal access to all knowledge” by permanently preserving digital cultural artifacts and offering free public access to them. It is a publicly available digital library of Internet sites and other cultural artifacts that can be searched and accessed in digital form. Like a physical library, it provides free access to everyone.

7. The Internet Archive created a resource known as the “Wayback Machine” (<https://web.archive.org/>). The Wayback Machine is named in reference to the famous Mr. Peabody’s WABAC (pronounced way-back) machine from the Rocky and Bullwinkle cartoon show. If you want to see what a webpage looked like last year, ten years ago, or in 1999, use the Wayback Machine. You provide it with a web address (a URL), and it shows you a calendar of snapshots over time, in the past.

8. The Wayback Machine makes it possible to search and browse more than 450 billion publicly available web pages stored in the Internet Archive's web archive. Visitors to the Wayback Machine can search the Archive by keyword or a website URL. If archived records for a URL or the key words are available, the visitor will be presented with a display of available dates. The visitor may select one of those dates and be taken to the collection of web captures associated with the specific web crawl and point (date) in time the capture came from.

9. This archived data made viewable by the Wayback Machine is obtained using web archiving software that automatically stores copies of files available via the Internet, each file preserved as it existed at a particular point in time.

10. The Internet Archive assigns a URL to all archived files within the Wayback Machine in the following format: [http://web.archive.org/web/\[Year in yyyy\]\[Month in mm\]\[Day in dd\]\[Time code in hh:mm:ss\]/\[Archived URL\]](http://web.archive.org/web/[Year in yyyy][Month in mm][Day in dd][Time code in hh:mm:ss]/[Archived URL]). This is known as an “extended URL” format.

11. For example, the Internet Archive extended URL <http://web.archive.org/web/19970126045828/http://www.archive.org/> denotes the URL for the record of the Internet Archive home page archived on January 26, 1997 at 4:58 a.m. and 28 seconds (1997/01/26 at 04:58:28).

IV. Public Availability of *Internet Archive URL's*

This Declaration relates to the public availability for the following references appended as Appendices A-F:

Appendix A

12. **Appendix A** is Align Technology, patents website, dated March 9, 2026, <https://web.archive.org/web/20260309051347/https://www.aligntech.com/patents>. (“*Align Tech patents*”).

13. As detailed in the steps below, I searched the Internet Archive’s Wayback Machine, located the *Align Tech patents*, reference, and reviewed the reference URL to determine the date of its public availability.

14. I first navigated to the Internet Archive website at <https://archive.org/>. I next navigated to The Wayback Machine (which is prominently displayed on the homepage of the Internet Archive website) and clicked on its URL: <https://web.archive.org/>. In the search box, I entered the search term “aligntech.com/patents” which took me to a page displaying the 2 URL’s captured for the URL prefix: https://web.archive.org/web/*/aligntech.com/patents*. I then navigated to the URL’s mentioning aligntech.com/patents, reviewed them, and then chose (clicked on) the extended URL <https://www.aligntech.com/patents> which was saved 70 times between September 22, 2019 and May 13, 2026. I next clicked on the year “2026” and then the first snapshot listed under March 9, 2026 detailed as 05:13:47. This took me to the following extended URL:

<https://web.archive.org/web/20260309051347/https://www.aligntech.com/patents>, which is the *Align Tech patents*, reference attached here as **Appendix A**.

15. The date details of extended URL

<https://web.archive.org/web/20260309051347/https://www.aligntech.com/patents>, as outlined above, reveal that *Align Tech patents* was archived by the Wayback Machine on March 9, 2026, at 5:13 a.m. and 47 seconds.

16. Based on the information in Appendix A and my search and review of the aforementioned documents on the Internet Archive's Wayback Machine, members of the interested public could have accessed Align Tech patents by searching the Internet Archive's Wayback Machine at or after March 9, 2026, at 5:13 a.m. and 47 seconds.

Appendix B

17. **Appendix B** is Bay Materials Announces Zendurz® FLX™ Thermoformable Material for Orthodontic Clear Aligner Therapy Appliances, Cision PR Newswire, dated November 28, 2018, <https://web.archive.org/web/20190527023742/https://www.prnewswire.com/news-releases/bay-materials-announces-zendura-flx-thermoformable-material-for-orthodontic-clear-aligner-therapy-appliances-300756563.html>. (“*Cision Press Release*”).

18. As detailed in the steps below, I searched the Internet Archive's Wayback Machine, located the *Cision Press Release*, reference, and reviewed the reference URL to determine the date of its public availability.

19. I first navigated to the Internet Archive website at <https://archive.org/>. I next navigated to The Wayback Machine (which is prominently displayed on the homepage of the Internet Archive website) and clicked on its URL:

<https://web.archive.org/>. In the search box, I entered the following link

[“www.prnewswire.com/news-releases/bay-materials-announces-zendura-flx-thermoformable-material-for-orthodontic-clear-aligner-therapy-appliances-300756563.html](https://www.prnewswire.com/news-releases/bay-materials-announces-zendura-flx-thermoformable-material-for-orthodontic-clear-aligner-therapy-appliances-300756563.html)

” which took me to a page displaying 1 URL for the URL prefix:

https://web.archive.org/web/*/www.prnewswire.com/news-releases/bay-materials-announces-zendura-flx-thermoformable-material-for-orthodontic-clear-aligner-therapy-appliances-300756563.html*. I then navigated to the URL's mentioning *Cision Press Release*, reviewed them, and then chose (clicked on) the extended URL https://web.archive.org/web/*/www.prnewswire.com/news-releases/bay-materials-announces-zendura-flx-thermoformable-material-for-orthodontic-clear-aligner-therapy-appliances-300756563.html* which was saved 4 times between May 27, 2019 and January 18, 2022. I next clicked on the year “2019” and then the first snapshot listed under May 27, 2019 detailed as 02:37:42. This took me to the

following extended URL:

<https://web.archive.org/web/20190527023742/https://www.prnewswire.com/news-releases/bay-materials-announces-zendura-flx-thermoformable-material-for-orthodontic-clear-aligner-therapy-appliances-300756563.html>, which is the *Cision Press Release*, reference attached here as **Appendix B**.

20. The date details of extended URL

<https://web.archive.org/web/20190527023742/https://www.prnewswire.com/news-releases/bay-materials-announces-zendura-flx-thermoformable-material-for-orthodontic-clear-aligner-therapy-appliances-300756563.html> as outlined above, reveal that *Cision Press Release* was archived by the Wayback Machine on May 27, 2019, at 2:37 a.m. and 42 seconds.

21. Based on the information in **Appendix B** and my search and review of the aforementioned documents on the Internet Archive's Wayback Machine, members of the interested public could have accessed *Cision Press Release* by searching the Internet Archive's Wayback Machine at or after May 27, 2019, at 2:37 a.m. and 42 seconds.

Appendix C

22. **Appendix C** is Eastman Tritan Copolyester FX200, Product Data Sheet, dated March 29, 2010,

<https://web.archive.org/web/20110928075902/http://ws.eastman.com/ProductC>

[atalogApps/PageControllers/ProdDatasheet_PC.aspx?product=71069060,](http://atalogApps/PageControllers/ProdDatasheet_PC.aspx?product=71069060)

(“Copolyester FX200”).

23. As detailed in the steps below, I searched the Internet Archive's Wayback Machine, located the *Copolyester FX200*, reference, and reviewed the reference URL to determine the date of its public availability.

24. I first navigated to the Internet Archive website at <https://archive.org/>. I next navigated to The Wayback Machine (which is prominently displayed on the homepage of the Internet Archive website) and clicked on its URL:

https://web.archive.org/. In the search box, I entered the link “ws.eastman.com/ProductCatalogApps/PageControllers/ProdDatasheet_PC.aspx?product=71069060” which took me to a page displaying a timeline and calendars for the URL prefix:

https://web.archive.org/web/20260000000000*/ws.eastman.com/ProductCatalogA
pps/PageControllers/ProdDatasheet_PC.aspx?product=71069060. I then clicked
on the year “2011” and then the first snapshot listed under September 28, 2011
detailed as 7:59:02. This took me to the following extended URL:

https://web.archive.org/web/20110928075902/ws.eastman.com/ProductCatalogApps/PageControllers/ProdDatasheet_PC.aspx?product=71069060, which is the *Copolyester FX200*, reference attached here as **Appendix C**.

25. The date details of extended URL

https://web.archive.org/web/20110928075902/ws.eastman.com/ProductCatalogApps/PageControllers/ProdDatasheet_PC.aspx?product=71069060 as outlined above, reveal that *Copolyester FX200* was archived by the Wayback Machine on September 28, 2011, at 7:59 a.m. and 2 seconds.

26. Based on the information in **Appendix C** and my search and review of the aforementioned documents on the Internet Archive's Wayback Machine, members of the interested public could have accessed *Copolyester FX200* by searching the Internet Archive's Wayback Machine at or after September 28, 2011, at 7:59 a.m. and 2 seconds.

Appendix D

27. **Appendix D** is Invisalign website, *21M smiles. 21M lives changed.* dated March 27, 2026, <https://web.archive.org/web/20260327233208/invisalign.com/provider>, ("*21M smiles. 21M lives changed.*").

28. As detailed in the steps below, I searched the Internet Archive's Wayback Machine, located the *21M smiles. 21M lives changed.*, reference, and reviewed the reference URL to determine the date of its public availability.

29. I first navigated to the Internet Archive website at <https://archive.org/>. I next navigated to The Wayback Machine (which is prominently displayed on the

homepage of the Internet Archive website) and clicked on its URL:

<https://web.archive.org/>. In the search box, I entered the search term

“Invisalign.com/provider” which took me to a page displaying the 2,203 URL’s captured for the URL prefix:

https://web.archive.org/web/*/invisalign.com/provider*. I then navigated to the URL’s mentioning Invisalign.com provider, reviewed them, and then chose (clicked on) the extended URL

https://web.archive.org/web/20260518204227*/http://www.invisalign.com:80/provider which was saved 273 times between November 17, 2011 and May 18, 2026. I next clicked on the year “2026” and then the first snapshot listed under March 27, 2026 detailed as 23:32:08. This took me to the following extended URL:

<https://web.archive.org/web/20260327233208/http://www.invisalign.com/provider>, which is the *21M smiles. 21M lives changed.*, reference attached here as

Appendix D.

30. The date details of extended URL

<https://web.archive.org/web/20260327233208/http://www.invisalign.com/provider>, as outlined above, reveal that *21M smiles. 21M lives changed.* was archived by the Wayback Machine on March 27, 2026, at 11:32 p.m. and 8 seconds.

31. Based on the information in **Appendix D** and my search and review of the aforementioned documents on the Internet Archive’s Wayback Machine,

members of the interested public could have accessed *21M smiles. 21M lives changed.* by searching the Internet Archive's Wayback Machine at or after March 27, 2026, at 11:32 p.m. and 8 seconds.

Appendix E

32. **Appendix E** is Eastman Tritan™ copolyester FX100, Technical Data Sheet, dated April 22, 2021, <https://web.archive.org/web/20240415114925/https://productcatalog.eastman.com/tds/ProdDatasheet.aspx?product=71068695&pn=eastman-tritan-fx100-copolyester> ("*copolyester FX100*").

33. As detailed in the steps below, I searched the Internet Archive's Wayback Machine, located the *copolyester FX100*, reference, and reviewed the reference URL to determine the date of its public availability.

34. I first navigated to the Internet Archive website at <https://archive.org/>. I next navigated to The Wayback Machine (which is prominently displayed on the homepage of the Internet Archive website) and clicked on its URL: <https://web.archive.org/>. In the search box, I entered the search term <https://productcatalog.eastman.com/tds/>" which took me to a page displaying a 2,762 URL's captured for the URL prefix: https://web.archive.org/web/*/https://productcatalog.eastman.com/tds/*. I then navigated to the URL's mentioning "fx100",

https://web.archive.org/web/20240415000000*/http://productcatalog.eastman.com/tds/ProdDatasheet.aspx?product=71068695&pn=eastman-tritan-fx100-copolyester,

clicked on the year “2024” and then the first snapshot listed under April 15, 2024 detailed as 11:49:25. This took me to the following extended URL:

<https://web.archive.org/web/20240415114925/productcatalog.eastman.com/tds/ProdDatasheet.aspx?product=71068695&pn=eastman-tritan-fx100-copolyester>, which is the *copolyester FX100*, reference attached here as **Appendix E**.

35. The date details of extended URL

<https://web.archive.org/web/20240415114925/http://productcatalog.eastman.com/tds/ProdDatasheet.aspx?product=71068695&pn=eastman-tritan-fx100-copolyester> as outlined above, reveal that *copolyester FX100* was archived by the Wayback Machine on April 15, 2024, at 11:49 a.m. and 25 seconds.

36. Based on the information in **Appendix E** and my search and review of the aforementioned documents on the Internet Archive’s Wayback Machine, members of the interested public could have accessed *copolyester FX100* by searching the Internet Archive’s Wayback Machine at or after April 15, 2024, at 11:49 a.m. and 25 seconds.

Appendix F

37. **Appendix F** is Eastman Tritan™ copolyester FX100, Product Data Sheet, dated March 30,

2010, https://web.archive.org/web/20140122132516/http://ws.eastman.com/ProductCatalogApps/PageControllers/ProdDatasheet_PC.aspx?product=71068695

(“*Tritan Copolyester FX100*”).

38. As detailed in the steps below, I searched the Internet Archive’s Wayback Machine, located the *Tritan Copolyester FX100*, reference, and reviewed the reference URL to determine the date of its public availability.

39. I first navigated to the Internet Archive website at <https://archive.org/>. I next navigated to The Wayback Machine (which is prominently displayed on the homepage of the Internet Archive website) and clicked on its URL: <https://web.archive.org/>. In the search box, I entered the following link [ws.eastman.com/ProductCatalogApps/PageControllers/ProdDatasheet_PC.aspx?product=71068695](ws.eastman.com/ProductCatalogApps/PageControllers/ProdDatasheet_PC.aspx?product=71068695) which took me to a page displaying a timeline and calendar with URL’s captured for the URL prefix: https://web.archive.org/web/20140101000000*///ws.eastman.com/ProductCatalogApps/PageControllers/ProdDatasheet_PC.aspx?product=71068695. I then clicked on the year “2014” and then the first snapshot listed under January 22, 2014 detailed as 13:25:16. This took me to the following extended URL: https://web.archive.org/web/20140122132516///ws.eastman.com/ProductCatalogApps/PageControllers/ProdDatasheet_PC.aspx?product=71068695, which is the *Tritan Copolyester FX100*, reference attached here as **Appendix F**.

40. The date details of extended

URL https://web.archive.org/web/20140122132516///ws.eastman.com/ProductCatalogApps/PageControllers/ProdDatasheet_PC.aspx?product=71068695 as outlined above, reveal that *Tritan Copolyester FX100* was archived by the Wayback Machine on January 22, 2014, at 1:25 p.m. and 16 seconds.

41. Based on the information in **Appendix F** and my search and review of the aforementioned documents on the Internet Archive's Wayback Machine, members of the interested public could have accessed *Tritan Copolyester FX100* by searching the Internet Archive's Wayback Machine at or after January 22, 2014, at 1:25 p.m. and 16 seconds.

V. Conclusion

42. I declare that all statements made herein of my knowledge are true, that all statements made on information and belief are believed to be true, and that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code.

Declaration of Kelley M Hayes Greenhill

Dated: May 29, 2026.

Kelley Hayes Greenhill


Kelley M Hayes Greenhill

APPENDIX A

align™

Transforming smiles, changing lives.

About Solutions Careers Investors Patents Newsroom Contact us



Patents

Align Technology is a global medical device company that is changing lives through better smiles. We reimagine and reinvent the way dental treatment is presented and delivered to millions of people around the world. We are a leading provider of advanced digital dentistry platforms. The following Align Technology products are protected by patents in the United States and elsewhere. This web page is provided to satisfy the virtual patent marking provisions of various jurisdictions including the virtual patent marking provisions of Section 16 of the America Invents Act. It is also intended to serve as notice under 35 U.S.C. § 287(a). Other products not listed here may be protected by one or more patents in the United States and elsewhere. Additional patents are pending in the United States and elsewhere.



The Invisalign® process and family of clear aligner products (including, but not limited to, Invisalign® Comprehensive Package, Invisalign® Comprehensive Phase 2 Package, Invisalign® Lite Package, Invisalign® Express Package, Invisalign® retainers, Invisalign® Express 5, Invisalign® Express 10, Invisalign® Assist, Invisalign® GO clear aligners, Vivera® retainers, Invisalign® First clear aligners, and Invisalign Palatal Expander) are covered by one or more of the following U.S. Patents and other pending applications and foreign equivalents:

US 7,553,157	US 11,194,312
US 7,711,447	US 11,202,691
US 7,854,609	US 11,213,368
US 7,878,805	US 11,213,369
US 7,916,911	US 11,234,794
US 8,038,444	US 11,241,758
US 8,155,780	US 11,247,242
US 8,641,414	US 11,259,896
US 8,899,976	US 11,273,011
US 8,899,977	US 11,278,375
US 8,995,732	US 11,284,972
US 9,004,915	US 11,284,973
US 9,107,722	US 11,284,974
US 9,301,814	US 11,295,444
US 9,326,830	US 11,298,211
US 9,403,238	US 11,304,779
US 9,433,477	US 11,334,996
US 9,566,132	US 11,344,385
US 9,655,691	US 11,357,598
US 9,655,693	US 11,369,456
US 9,839,494	US 11,376,100
US 9,844,421	US 11,379,097
US 9,939,999	US 11,382,720
US 9,943,386	US 11,382,721
US 9,943,991	US 11,383,322
US 10,004,578	US 11,389,272
US 10,052,176	US 11,395,717
US 10,085,823	US 11,417,431
US 10,123,853	US 11,420,362
US 10,136,964	US 11,426,259
US 10,143,537	US 11,449,191
US 10,271,923	US 11,453,156
US 10,299,894	US 11,464,604
US 10,335,252	US 11,471,253
US 10,405,947	US 11,478,334
US 10,420,631	US 11,484,389
US 10,421,152	US 11,484,395
US 10,456,217	US 11,490,996
US 10,501,214	US 11,497,584
US 10,512,524	US 11,521,732
US 10,537,405	US 11,529,215
US 10,537,406	US 11,534,861
US 10,524,879	US 11,547,532
US 10,525,855	US 11,552,000



The iTero® family of intraoral scanner products (including, but not limited to, iTero Lumina, iTero Element 5D, iTero Element 2, iTero Element Flex, iTero Element, iTero HD2.9, iTero HDU) are covered by one or more of the following U.S. Patents and other pending applications and foreign equivalents:

US 7,286,954	US 10,772,506
US 7,319,529	US 10,779,914
US 7,890,290	US 10,791,934
US 8,948,482	US 10,791,936
US 9,214,014	US 10,835,128
US 9,299,192	US 10,884,238
US 9,431,887	US 10,888,400
US 9,491,863	US 10,898,077
US 9,510,757	US 10,945,609
US 9,589,329	US 10,952,827
US 9,660,418	US 10,964,425
US 9,675,430	US 11,007,039
US 9,709,803	US 11,134,834
US 9,830,688	US 11,135,039
US 9,939,999	US 11,147,458
US 10,004,572	US 11,152,106
US 10,105,199	US 11,202,574
US 10,111,581	US 11,238,586
US 10,117,581	US 11,284,802
US 10,148,066	US 11,321,817
US 10,219,875	US 11,369,271
US 10,275,862	US 11,357,603
US 10,288,875	US 11,392,210
US 10,327,872	US 11,422,362
US 10,390,913	US 11,426,053
US 10,405,951	US 11,426,077
US 10,470,846	US 11,439,483
US 10,485,639	US 11,455,727
US 10,499,793	US 11,523,885
US 10,507,087	US 11,638,525
US 10,507,088	US 11,672,631
US 10,507,089	US 11,678,953
US 10,568,722	US 11,690,517
US 10,599,227	US 11,759,277
US 10,603,136	US 11,844,153
US 10,610,107	US 11,896,461
US 10,600,160	US 11,911,240
US 10,624,720	US 11,928,832
US 10,702,164	US 11,930,154
US 10,709,527	US 11,826,225
US 10,756,511	US 11,563,929
	US 11,950,880
	US 11,950,981
	US 11,954,262
	US 11,972,572

US 10,595,966	US 11,564,777	US 12,011,338
US 10,610,332	US 11,565,441	US 12,035,885
US 10,613,515	US 11,567,472	US 12,048,512
US 10,646,307	US 11,571,277	US 12,062,180
US 10,650,517	US 11,576,753	US 12,070,367
US 10,653,502	US 11,576,754	US 12,143,558
US 10,653,503	US 11,589,743	US 12,156,785
US 10,695,956	US 11,596,499	US 12,178,685
US 10,702,357	US 11,623,368	US 12,193,912
US 10,722,328	US 11,628,044	US 12,251,186
US 10,729,515	US 11,631,176	US 12,263,063
US 10,733,805	US 11,633,261	US 12,268,474
US 10,758,321	US 11,633,877	US 12,274,600
US 10,758,322	US 11,642,195	US 12,279,929
US 10,766,055	US 11,648,087	US 12,329,358
US 10,773,337	US 11,648,089	US 12,357,151
US 10,779,915	US 11,648,090	US 12,373,039
US 10,783,629	US 11,648,091	US 12,390,311
US 10,789,394	US 11,651,494	
US 10,813,721	US 11,654,001	US RE49605
US 10,828,130	US 11,654,003	US D742,518
US 10,828,719	US 11,660,167	US D760,901
US 10,893,918	US 11,667,412	US D768,861
US 10,888,395	US 11,672,629	US D771,817
US 10,912,627	US 11,678,954	US D774,193
US 10,912,629	US 11,678,956	US D806,248
US 10,925,690	US 11,701,203	US D816,222
US 10,970,839	US 11,707,344	US D816,223
US 10,973,611	US 11,714,398	US D925,739
US 10,973,613	US 11,717,384	US D1,026,227
US 10,980,616	US 11,717,381	US D1,042,842
US 10,996,813	US 11,717,380	US D1,061,895
US 11,000,350	US 11,723,753	US D1,073,069
US 11,004,159	US 11,730,574	US D1,089,653
US 11,007,036	US 11,737,852	
US 11,007,037	US 11,737,853	
US 11,109,946	US 11,744,451	
US 11,013,582	US 11,744,676	
US 11,020,206	US 11,751,974	
US 11,024,431	US 11,752,523	
US 11,026,766	US 11,766,313	
US 11,033,359	US 11,766,314	
US 11,033,360	US 11,771,526	
US 11,033,362	US 11,786,341	
US 11,077,966	US 11,801,121	
US 11,086,490	US 11,801,124	
US 11,096,763	US 11,810,207	
US 11,103,330	US 11,809,214	
US 11,116,605	US 11,823,356	
US 11,129,694	US 11,839,520	
US 11,138,727	US 11,850,111	
US 11,141,243	US 11,850,680	
US 11,154,381	US 11,890,159	
US 11,154,384	US 11,890,160	
	US 11,897,181	
	US 11,903,793	
	US 11,911,929	
	US 11,925,525	
	US 11,937,991	
	US 11,950,977	
	US 11,958,248	
	US 11,962,892	
	US 11,969,311	
	US 11,972,873	
	US 11,974,896	
	US 11,974,897	
	US 11,974,898	
	US 11,975,463	
	US 11,978,547	
	US 11,980,523	
	US 11,985,414	
	US 11,986,369	
	US 11,991,439	
	US 11,991,440	
	US 11,992,382	
	US 11,998,418	
	US 12,004,919	
	US 12,016,745	
	US 12,016,748	
	US 12,023,216	
	US 12,036,084	
	US 12,036,087	
	US 12,036,093	
	US 12,048,604	
	US 12,048,605	
	US 12,048,606	
	US 12,053,344	
	US 12,059,321	
	US 12,064,310	
	US 12,064,311	
	US 12,064,312	
	US 12,064,316	
	US 12,067,210	
	US 12,076,207	
	US 12,082,987	
	US 12,086,964	
	US 12,097,085	
	US 12,099,342	
	US 12,109,089	
	US 12,109,090	
	US 12,115,719	
	US 12,125,581	
	US 12,127,906	
	US 12,133,783	
	US 12,138,137	

US 12,144,705
US 12,144,701
US 12,171,634
US 12,182,886
US 12,186,152
US 12,193,905
US 12,208,542
US 12,207,986
US 12,211,123
US 12,213,855
US 12,213,856
US 12,220,288
US 12,226,284
US 12,226,279
US 12,226,281
US 12,226,283
US 12,232,929
US 12,232,930
US 12,232,924
US 12,232,926
US 12,239,506
US 12,240,176
US 12,251,289
US 12,257,125
US 12,257,773
US 12,263,632
US 12,263,620
US 12,268,569
US 12,272,067
US 12,275,191
US 12,319,002
US 12,322,093
US 12,329,598
US 12,329,599
US 12,347,567
US 12,357,427
US 12,357,433
US 12,370,016
US 12,376,945
US 12,376,944
US 12,376,943
US 12,377,493
US 12,390,310
US 12,390,960
US 12,402,983
US 12,412,648
US 12,419,725
US D1,027,186
US D1,063,077
US D1,064,272

Last updated September 30, 2025

[Privacy](#) [Terms of use](#) [Data Subject Request](#) [CVD](#)
[invisalign.com](#) [itero.com](#)
© 2026 Align Technology, Inc.



[Cookie Preferences](#)

APPENDIX B

Bay Materials Announces Zendura® FLX™ Thermoformable Material for Orthodontic Clear Aligner Therapy Appliances


Zendura®
Orthodontic Clear Aligner & Retainer Material

NEWS PROVIDED BY
Bay Materials →
Nov 28, 2018, 07:00 ET

SHARE THIS ARTICLE
f t in e y

FREMONT, Calif., Nov. 28, 2018 /PRNewswire/ -- Bay Materials LLC, the industry leader in high performance thermoformable plastic materials for orthodontic clear aligner therapy, today announced the commercial release of Zendura® FLX™, an entirely new and unique material engineered specially for fabricating clear aligner appliances.

Studies show that clear aligner therapy continues to grow rapidly in the U.S. and internationally spurred by public demand for a more comfortable and satisfying method of orthodontic treatment.



The latest addition to Bay's growing portfolio of clear aligner therapy materials, FLX provides patients with greater initial comfort, making the whole orthodontic treatment significantly more patient friendly, while also delivering teeth movement force superior to other commercially available aligner materials. FLX's greater elasticity allows it to more easily accommodate the use of engagers and treat a wider range of cases.

Zendura FLX generates 40% less initial force than earlier generation materials, providing greatly improved patient comfort and acceptance. FLX also retains 150% more orthodontic force after a normal wear period than competitive materials. Taken together, FLX's many standout features make it the new benchmark in performance and durability.

Engineered by a team of world-class material scientists to provide the optimum balance of elasticity, force retention, durability and clarity, the secret to FLX's superior performance is its elastomeric layer encased in a dual shell construction. The thin, rigid shells grip the teeth evenly and firmly, while the elastomeric layer applies gentle yet consistent, continual pressure to move teeth reliably and predictably over the prescribed period of time. The dual rigid shells also provide protection from bruxing.

"FLX is not intended to replace our standard Zendura material for fabricating orthodontic appliances," said Dr. Ray Stewart, founder and CEO of Bay Materials. "It will be the ideal aligner material for many cases, while our standard Zendura may be the better material for other cases. Our standard Zendura will remain unrivaled as a post-treatment retainer material."

FLX features a proprietary 3-layer design and is 0.030" (0.76mm) in thickness.

"Bay Materials' Zendura FLX aligner material appears to be light years ahead of the competition," said Kjeld Aamodt, DDS, MS. "My patients love it because its flexibility makes it more comfortable on day one of every stage and it stays virtually invisible. Not only is FLX best-in-class in clarity and stain resistance — you just can't see it — but also the material's teeth movement force and other physical properties allow my cases to track more predictably and reliably. I love what I'm seeing."

About Bay Materials

Bay Materials, founded in 2000, is a Silicon Valley-based polymer materials company engaged in manufacturing and marketing advanced materials for the orthodontic industry. Its Zendura brand of material is widely regarded as the best commercially available clear thermoplastic material for fabricating orthodontic clear aligners and post-treatment retainers.

Bay Materials also provides materials-intensive product development services for select companies. For more information, please visit www.baymaterials.com and www.zenduradental.com.

For further information contact:
Chip Hennen
650.566.0800 x313
chenhen@baymaterials.com

SOURCE Bay Materials

Related Links
<https://baymaterials.com>

Also from this source

Bay Materials Announces Significant Facilities Expansion...



Bay Materials anuncia o registro de produtos Zendura® no Brasil...



Explore

More news releases in similar topics

Health Care & Hospitals

Dentistry

Medical Equipment

Medical Pharmaceuticals

New Products & Services

You just read:

Bay Materials Announces Zendura® FLX™ Thermoformable Material for Orthodontic Clear Aligner Therapy Appliances

NEWS PROVIDED BY
Bay Materials →
Nov 28, 2018, 07:00 ET

SHARE THIS ARTICLE



<https://www.prnewswire.com/news-releases/bay-materials-announces-zendura-flx-thermoformable-material-for-orthodontic-clear-aligner-therapy-appliances>

Contact PR Newswire

888-776-0942
from 8 AM - 10 PM ET
Contact Us ^
  

Products

Cision Communication Cloud®
For Marketers
For Public Relations
For IR & Compliance
For Agency
For Small Business
All Products

About

About PR Newswire
About Cision
Become a Publishing Partner
Become a Channel Partner
Careers
Global Sites ^

My Services

All New Releases
Online Member Center
ProNet™

[Terms of Use](#) | [Privacy Policy](#) | [Information Security Policy](#) | [Site Map](#) | [RSS](#) | [Cookie Settings](#)

Copyright © 2019 PR Newswire Association LLC. All Rights Reserved. A Cision company.

APPENDIX C



Product Data Sheet

Eastman Tritan Copolyester FX200

Application/Uses

- Consumer and durable goods
- Graphic Arts
- Leisure and safety
- Specialty films

Key Attributes

- Does not contain Bisphenol-A (BPA)
- Does not contain plasticizers
- Excellent clarity
- Good chemical resistance
- No pre-drying of film prior to thermoforming
- Tremendous toughness
- Very good heat resistance
- Wide thermoforming window

Product Description

Eastman Tritan FX200 is an amorphous copolyester that combines excellent clarity and toughness with outstanding heat and chemical resistance. Films manufactured from this new-generation copolyester can be thermoformed without pre-drying and with a wide processing window that allows for product designs that reflect intricate detail. Eastman Tritan FX200 copolyester may be used in repeated use food contact articles under United States Food and Drug Administration (FDA) regulations. Eastman Tritan FX200 copolyester is certified to NSF/ANSI Standard 51 for Food Equipment Materials.

Typical Properties (Preliminary)

General Properties			
Thickness of Film Tested	ASTM D 374	0.254 mm (0.010 in.)	
Density	ASTM D 1505	1.19 g/cm ³	
Water Vapor Transmission Rate ^d			
@ 23°C (73°F)	ASTM F 1249	4 g/m ² -24h (0.3 g/100in. ² -24h)	
@ 38°C (100°F)		10 g/m ² -24h (1 g/100in. ² -24h)	
Gas Permeability, CO ₂	ASTM D 1434	211 cm ³ -mm/m ² -24h-atm (534 cm ³ -mil/100in. ² -24h-atm)	
Gas Permeability, O ₂	ASTM D 3985	44 cm ³ -mm/m ² -24h-atm (111 cm ³ -mil/100in. ² -24h-atm)	
Elmendorf Tear Resistance			
M.D.	ASTM D 1922	3.7 N (384 gf)	
T.D.		4.2 N (433 gf)	
PPT Tear Resistance			
M.D.	ASTM D 2582	40 N (9 lbf)	
T.D.		40 N (9 lbf)	
Tear Propagation Resistance, Split Tear Method ^e			
M.D.	ASTM D 1938	3 N (1 lbf)	
M.D.		10 N/mm (55 lbf/in.)	
T.D.		2 N (1 lbf)	
T.D.		9 N/mm (51 lbf/in.)	
Tear Resistance, Trouser @ 200 mm/min			
M.D.	ISO 6383-1	10 N/mm (56 lbf/in.)	
T.D.		9 N/mm (52 lbf/in.)	
Tensile Strength @ Yield			
M.D.	ASTM D 882	43 MPa (6300 psi)	
T.D.		41 MPa (6000 psi)	
Tensile Strength @ Break			
M.D.	ASTM D 882	57 MPa (8300 psi)	
T.D.		42 MPa (5900 psi)	
Elongation @ Yield			
M.D.	ASTM D 882	8%	
T.D.		8%	
Elongation @ Break			
M.D.	ASTM D 882	114%	
T.D.		115%	
Tensile Modulus			
M.D.	ASTM D 882	1500 MPa (2.2 x 10 ⁵ psi)	
T.D.		1400 MPa (2.1 x 10 ⁵ psi)	
Dart Impact ^f			
@ 23°C (73°F)	ASTM 1709A	825 g (1.82 lb)	
@ -18°C (0°F)		825 g (1.82 lb)	
@ -30°C (-22°F)		852 g (1.88 lb)	
Puncture Resistance (Dynatup); Total Energy	ASTM D 3763	4.5 J (3.3 ft-lb)	
Water Absorption, 24 hours	ASTM D 570	0.5%	
Surface Energy			
Polar	ASTM D 5946	8 dynes/cm	
Dispersive		39 dynes/cm	
Total		47 dynes/cm	
Taber Abrasion (average at 25 cycles)	ASTM 1044	20% haze	
Thermal Properties			
Glass Transition Temperature (T _g)	DSC	119°C (247°F)	
Specific Heat			
@ 60°C (140°F)	DSC	1.7 J/g-°C (0.42 Btu/lb-°F)	
@ 100°C (212°F)		1.9 J/g-°C (0.46 Btu/lb-°F)	
@ 150°C (302°F)		2.3 J/g-°C (0.54 Btu/lb-°F)	
@ 200°C (392°F)		2.4 J/g-°C (0.58 Btu/lb-°F)	
@ 250°C (482°F)		2.6 J/g-°C (0.62 Btu/lb-°F)	
Coefficient of Linear Thermal Expansion	ASTM D 696	8 (x10 ⁻⁵ /°C) (5 (x10 ⁻⁵ /°F))	
Optical Properties			
Refractive Index	ASTM D 542	1.54	
Yellowness Index	ASTM D 1925	0.5	
UV % Transmission at 380 nm	UV/Vis Spectro	89%	
Haze	ASTM D 1003	0.8%	
Gloss @ 60°	ASTM D 2457	158	
Light Transmission (Total Transmittance)	ASTM D 1003	93%	

Comments

Properties reported here are based on limited testing. Eastman makes no representation that the material in any particular shipment will conform exactly to the values given.

29-Mar-2010 7:33:16 AM

APPENDIX D

21M smiles¹. 21M lives changed.

Recently, we passed a huge milestone: 21 million Invisalign® smiles worldwide. That's truly a mind-boggling number, and it's all thanks to you and your teams, who guide every unique patient through Invisalign treatment.

Become a provider



Clear aligners are just the tip of the iceberg.


As an Invisalign® provider, you'll quickly discover that Invisalign® treatment is so much more than just a clear aligner, it's an entire ecosystem specifically designed to help you provide the very best teeth straightening imaginable.



Align Digital Workflow

Go digital and streamline your practice's workflow from end-to-end by adopting the seamless Align Digital Workflow.

[Learn more](#)



Innovations

With exclusive technology, like SmartTrack™, SmartForce™ and SmartStage™, perhaps it's no surprise that Invisalign treatment is the most advanced clear aligner system.³

[Learn more](#)



Lifelong Learning

Align Education offers a wealth of content, courses and resources designed to help you continually add to your existing knowledge, so you can take your practice to the next level.


[Learn more](#)

PREDICTABLE OUTCOMES

Cutting-edge solutions developed using over 25 years of insights from over 21 million¹ patients



Countless cases. One proven solution.⁸



From simple tooth movement to more complex cases, Invisalign® technology can help you achieve your clinical goals with confidence. That's because Invisalign® clear aligner therapy has demonstrated success in treating multiple case types from Class I, II, and III malocclusions.

[Learn more](#)



For orthodontists

With our seamless end-to-end digital workflow, you can instantly streamline your practice's treatment process without sacrificing the quality of your work as an Invisalign orthodontist or patient outcomes.

[Learn More](#)




For general practitioners

Take your practice to the next level by adding an easier way to visualize, plan, and treat mild to moderate orthodontic treatments that's powered by a single digital workflow and backed by world-class support specifically designed to help general dentists.

[Learn More](#)

A solution for the whole family.



Invisalign for adults

The Invisalign® system was designed to help you do it all — from creating digital impressions to keeping transformed smiles in place.


[Learn more](#) ➔



Invisalign for teens

Using cutting-edge technology, like Invisalign® Mandibular Advancement with Enhanced Precision Wings, you can provide innovative treatment for growing teens and tweens.

[Learn More](#) ➔



Invisalign for kids

With Invisalign First™ clear aligners, as children grow, their smiles grow with them. That's because you can use it to correct early dental problems, including developing malocclusions in primary or permanent teeth.

[Learn more](#) ➔

1. Data on file at Align Technology, as of September 30, 2025.
2. Based on Invisalign primary orders submitted that qualified for ClinCheck Live Plan (a successful iTero™ scan, a preferences template, and without a CBCT scan) in Jan-Jun 2025. Total orders analyzed is 230,601. Time is measured from when all materials are received for an order until the ClinCheck plan is available for doctor review. 91.17% of qualified orders were available for review in 15 minutes or less with a median time of 7 minutes. These orders represent 47.26% of total orders submitted with a preferences template. Includes Invisalign trained doctors in the NA, LATAM, EMEA, and APAC regions. Data on File at Align Technology, as of October 28, 2025.
3. Data on file at Align Technology, as of September 23, 2020.
4. Based on a global survey of 1,786 doctors (dentists and orthodontists who use clear aligners) by IQVIA in NA, EMEA, LATAM, and APAC. Data on File at Align Technology, as of June 30, 2022.
5. Data on file at Align Technology, as of September 23, 2020.
6. Study sponsored by Align Technology and based on adult Class I, nonextraction, mild to moderate crowding cases with SmartTrack material. David W. White, Katie C. Julien, Helder Jacob, Phillip M. Campbell and Peter H. Buschang. Discomfort associated with Invisalign and traditional brackets: A randomized, prospective trial. The Angle Orthodontist Nov 2017, Vol. 87, No. 6 pp. 801-808
7. Compared to Invisalign aligners previously made from single-layer (EX30) material.
8. Actual patient results shown. The before/after smiles were applied to the same face photo for visual emphasis.



Need more information on Invisalign®



Invisalign Solutions

For General Dentists

For Orthodontists

Why Invisalign

What Invisalign Treats

Align Digital Platform

Align Digital Platform

Connect

Scan

Diagnose

Plan

Treat

Monitor

Retain

Education And Support

Clinical Education

Practice Support

Events

FAQs

Become a Provider

Provider Log In

APPENDIX E



Technical Data Sheet

Eastman Tritan™ copolyester FX100



Applications

- Decorative laminates-metal
- Decorative laminates-wood
- Extruding
- Graphic arts
- Multi-layer film food contact
- Multi-layer film non food contact
- Packaging component films
- Packaging components non food contact
- Protective film
- Transaction cards

Key Attributes

- Bisphenol-A (BPA) free
- Clear, high gloss appearance
- Easy to extrude
- Excellent heat resistance
- Good scratch resistance
- Great for high temperature packaging
- Great for transaction cards and identification cards
- Not a material of concern
- Outstanding chemical resistance
- PVC alternative
- Plasticizer free
- Tremendous toughness

Product Description

Eastman Tritan™ FX100 is a copolyester resin for extruded film applications where enhanced heat resistance and toughness are required. It works great in hot fill packaging for food, transaction and identification cards, and protective laminates.

Packaging brands and film converters prefer Tritan™ FX100 for its ability to provide a clear, aesthetically pleasing package that stands up to the strenuous requirements for hot filling, while also providing safety that consumers expect. Its great for brands looking to replace materials of concern or differentiate their packaging by transitioning from opaque to clear.

Transaction and identification card producers, brands, and governments alike value Tritan FX100 for its excellent bend strength and chemical resistance, which provides longer useful life and better security. Compared to PVC and other material alternatives, Transaction cards made with Tritan™ have been found to withstand more than 10 times the number of flexural cycles using industry standard fitness for use testing protocols.

Tritan FX100 may be used in various food contact applications under the U.S. Food & Drug Administration (FDA) regulations.

This product has received a Platinum level Material Health Certificate from the Cradle to Cradle Products Innovation Institute. A Material Health Certificate is awarded to products that meet the Material Health requirements of the multi-attribute Cradle to Cradle Certified™ Product Standard. The Cradle to Cradle Products Innovation Institute is a nonprofit organization that administers the publicly available Cradle to Cradle Certified™ Product Standard, which provides designers and manufacturers with criteria and requirements for continually improving product materials and manufacturing processes. The Material Health Certificate provides manufacturers with a trusted way to communicate their efforts to identify and replace chemicals of concern in their products. For more information about Cradle to Cradle certification and to obtain printable certificates for Eastman copolyesters, visit www.c2ccertified.org. Search for Eastman Chemical Company in the Material Health Certificate Registry.

Typical Properties

Property ^a	Test Method ^b	Typical Value, Units ^c
General Properties		
Thickness of Film Tested	D 374	0.254 mm (0.010 in.)
Density	ASTM D 1505	1.19 g/cm ³
Water Vapor Transmission Rate ^d @ 23°C (73°F) @ 38°C (100°F)	ASTM F 1249	4 g/m ² -24h (0.2 g/100in. ² -24h) 11 g/m ² -24h (1 g/100in. ² -24h)
Gas Permeability, CO ₂	ASTM D 1434	149 cm ³ -mm/m ² -24h-atm (379 cm ³ -mil/100in. ² -24h-atm)
Gas Permeability, O ₂	ASTM D 3985	32 cm ³ -mm/m ² -24h-atm (82 cm ³ -mil/100in. ² -24h-atm)
Elmendorf Tear Resistance M.D. T.D.	ASTM D 1922	5.1 N (524 gf) 5.6 N (575 gf)
PPT Tear Resistance M.D. T.D.	ASTM D 2582	42 N (10 lbf) 56 N (13 lbf)
Tear Propagation Resistance, Split Tear Method ^e M.D. H.D. T.D.	ASTM D 1938	4 N (0.8 lbf) 13 N/mm (75 lbf/in.) 12 N/mm (66 lbf/in.) 3 N (0.7 lbf)
Tear Resistance, Trouser @ 200 mm/min M.D. T.D.	ISO 6383-1	11 N/mm (63 lbf/in.) 11 N/mm (63 lbf/in.)
Tensile Strength @ Yield M.D. T.D.	ASTM D 882	41 MPa (5900 psi) 40 MPa (5800 psi)
Tensile Strength @ Break M.D. T.D.	ASTM D 882	59 MPa (8500 psi) 52 MPa (7600 psi)
Elongation @ Yield M.D. T.D.	ASTM D 882	7 % 7 %
Elongation @ Break M.D. T.D.	ASTM D 882	179 % 203 %
Tensile Modulus M.D. T.D.	ASTM D 882	1500 MPa (2.1 x 10 ⁵ psi) 1400 MPa (2.0 x 10 ⁵ psi)
Dart Impact ^f @ 23°C (73°F) @ -30°C (-22°F)	ASTM 1709A	882 g (1.94 lb) 913 g (2.01 lb)
Puncture Resistance (Dynatup); Total Energy	ASTM D 3763	4.6 J (3.4 ft-lb)
Water Absorption, 24 hours	ASTM D 570	0.5 %
Surface Energy Dispersive Polar Total	ASTM D 5946	39 dynes/cm 8 dynes/cm 46 dynes/cm
Taber Abrasion (average at 25 cycles)	ASTM 1044	23 % haze
Optical Properties		
Refractive Index	ASTM D 542	1.55
Yellowness Index	ASTM D 1925	0.5
UV % Transmission at 380 nm	UV/Vis Spectro	89 %
Haze	ASTM D 1003	0.7 %
Gloss @ 60°	ASTM D 2457	161
Light Transmission (Total Transmittance)	ASTM D 1003	92 %
Thermal Properties		
Glass Transition Temperature (T _g)	DSC	110 °C (229 °F)
Specific Heat @ 100°C (212°F) @ 150°C (302°F) @ 200°C (392°F) @ 250°C (482°F) @ 60°C (140°F)	DSC	1.9 J/g-°C (0.45 Btu/lb-°F) 2.2 J/g-°C (0.54 Btu/lb-°F) 2.4 J/g-°C (0.58 Btu/lb-°F) 2.6 J/g-°C (0.62 Btu/lb-°F) 1.7 J/g-°C (0.41 Btu/lb-°F)
Coefficient of Linear Thermal Expansion	ASTM D 696	9 (x10-5/°C) (5 (x10-5/°F))

^aUnless noted otherwise, all tests are run at 23°C (73°F) and 50% relative humidity
^bUnless noted otherwise, the test method is ASTM
^cUnits are in SI or US customary units
^d(a) Test conducted at 23°C (73°F) and 100% relative humidity (b) Test conducted at 38°C (100°F) and 100% relative humidity
^e@ 254 mm/min (10 in./min)
^f12.7 mm (1/2 in.) dia. head, 127 mm (5 in.) dia. clamp, 660 mm (26 in.) drop

Technical Disclaimer

Eastman makes no representation and disclaims any warranty that the material in any particular shipment will conform exactly to the values given. Values as well as the performance of the final molded article may be affected by various factors such as the part design, mold design or tooling, drying, processing conditions as well as coloring or pigmentation of the product. No warranty of merchantability or fitness for use is made, and nothing herein waives any of the Seller's conditions of sale. You must make your own determination of the suitability of this product in your specific application due to the many factors (e.g. design, processing and conditions of use) that affect the performance of the final molded article. Suitability of use should be evaluated with appropriate testing and analysis. The processing melt temperature and mold temperature refer to the actual resin melt temperature and actual mold surface temperature respectively. Consider overall resin residence time, part shot size utilization and part geometry to set appropriate processing melt temperature and mold temperature in order to minimize IV loss and maximize molded part performance.

Comments

Properties reported here are based on limited testing. Eastman makes no representation that the material in any particular shipment will conform exactly to the values given.

Eastman and its marketing affiliates shall not be responsible for the use of this information, or of any product, method, or apparatus mentioned, and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and for the health and safety of your employees and purchasers of your products. No warranty is made of the merchantability of fitness of any product, and nothing herein waives any of the Seller's conditions of sale.

4/22/2021 1:41:30 PM

© 2024 Eastman Chemical Company or its subsidiaries. All rights reserved. As used herein, ® denotes registered trademark status in the U.S. only.

APPENDIX F

EASTMAN

Product Data Sheet

Eastman Tritan™ Copolyester FX100

Application/Uses

- Consumer and durable goods
- Graphic Arts
- Leisure and safety
- Specialty films

Key Attributes

- Does not contain Bisphenol-A (BPA)
- Does not contain plasticizers
- Excellent clarity
- Good heat resistance
- No pre-drying of film prior to thermoforming
- Outstanding chemical resistance
- Tremendous toughness
- Wide thermoforming window

Product Description

Eastman Tritan™ FX100 is an amorphous copolyester that combines excellent clarity and toughness with outstanding heat and chemical resistance. Films manufactured from this new-generation copolyester can be thermoformed without pre-drying and with a wide processing window that allows for product designs that reflect intricate detail. Eastman Tritan™ FX100 copolyester may be used in repeated use food contact articles under United States Food and Drug Administration (FDA) regulations. Eastman Tritan™ FX100 copolyester is certified to NSF/ANSI Standard 51 for Food Equipment Materials.

Typical Properties

Property ^a	Test ^b Method	Typical Value, Units ^c
General Properties		
Thickness of Film Tested	D 374	0.254 mm (0.010 in.)
Density	ASTM D 1505	1.19 g/cm ³
Water Vapor Transmission Rate ^d @ 23°C (73°F)	ASTM F 1249	4 g/m ² -24h (0.2 g/100in. ² -24h)
@ 38°C (100°F)		11 g/m ² -24h (1 g/100in. ² -24h)
Gas Permeability, CO ₂	ASTM D 1434	149 cm ³ -mm/m ² -24h-atm (379 cm ³ -mil/100in. ² -24h-atm)
Gas Permeability, O ₂	ASTM D 3985	32 cm ³ -mm/m ² -24h-atm (82 cm ³ -mil/100in. ² -24h-atm)
Elmendorf Tear Resistance M.D.	ASTM D 1922	5.1 N (524 gf)
T.D.		5.6 N (575 gf)
PPT Tear Resistance M.D.	ASTM D 2582	42 N (10 lbf)
T.D.		56 N (13 lbf)
Tear Propagation Resistance, Split Tear Method ^e M.D.	ASTM D 1938	4 N (0.8 lbf)
M.D.		13 N/mm (75 lbf/in.)
T.D.		3 N (0.7 lbf)
T.D.		12 N/mm (66 lbf/in.)
Tear Resistance, Trouser @ 200 mm/min M.D.	ISO 6383-1	11 N/mm (63 lbf/in.)
T.D.		11 N/mm (63 lbf/in.)
Tensile Strength @ Yield M.D.	ASTM D 882	41 MPa (5900 psi)
T.D.		40 MPa (5800 psi)
Tensile Strength @ Break M.D.	ASTM D 882	59 MPa (8500 psi)
T.D.		52 MPa (7600 psi)
Elongation @ Yield M.D.	ASTM D 882	7%
T.D.		7%
Elongation @ Break M.D.	ASTM D 882	179%
T.D.		203%
Tensile Modulus M.D.	ASTM D 882	1500 MPa (2.1 x 10 ⁵ psi)
T.D.		1400 MPa (2.0 x 10 ⁵ psi)
Dart Impact ^f @ 23°C (73°F)	ASTM 1709A	882 g (1.94 lb)
@ -30°C (-22°F)		913 g (2.01 lb)
Puncture Resistance (Dynatup); Total Energy	ASTM D 3763	4.6 J (3.4 ft-lb)
Water Absorption, 24 hours	ASTM D 570	0.5%
Surface Energy Polar	ASTM D 5946	8 dynes/cm
Dispersive		39 dynes/cm
Total		46 dynes/cm
Taber Abrasion (average at 25 cycles)	ASTM 1044	23% haze
Thermal Properties		
Glass Transition Temperature (T _g)	DSC	110°C (229°F)
Specific Heat @ 60°C (140°F)	DSC	1.7 J/g-°C (0.41 Btu/lb-°F)
@ 100°C (212°F)		1.9 J/g-°C (0.45 Btu/lb-°F)
@ 150°C (302°F)		2.2 J/g-°C (0.54 Btu/lb-°F)
@ 200°C (392°F)		2.4 J/g-°C (0.58 Btu/lb-°F)
@ 250°C (482°F)		2.6 J/g-°C (0.62 Btu/lb-°F)
Coefficient of Linear Thermal Expansion	ASTM D 696	9 (x10-5/°C) (5 (x10-5/°F))
Optical Properties		
Refractive Index	ASTM D 542	1.55
Yellowness Index	ASTM D 1925	0.5
UV % Transmission at 380 nm	UV/Vis Spectro	89%
Haze	ASTM D 1003	0.7%
Gloss @ 60°	ASTM D 2457	161
Light Transmission (Total Transmittance)	ASTM D 1003	92%

^a Unless noted otherwise, all tests are run at 23°C (73°F) and 50% relative humidity.
^b Unless noted otherwise, the test method is ASTM.
^c Units are in SI or US customary units.
^d (a) Test conducted at 23°C (73.4°F) and 100% relative humidity. (b) Test conducted at 38°C (100.4°F) and 100% relative humidity.
^e @ 254 mm/min (10 in./min)
^f 12.7 mm (1/2 in.) dia. head, 127 mm (5 in.) dia. clamp, 660 mm (26 in.) drop

Comments
Properties reported here are based on limited testing. Eastman makes no representation that the material in any particular shipment will conform exactly to the values given.

Eastman and its marketing affiliates shall not be responsible for the use of this information, or of any product, method, or apparatus mentioned, and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and for the health and safety of your employees and purchasers of your products. No warranty is made of the merchantability of fitness of any product, and nothing herein waives any of the Seller's conditions of sale.

30-Mar-2010 1:07:22 PM