



US010238162B2

(12) **United States Patent
Knight**

(10) **Patent No.: US 10,238,162 B2**

(45) **Date of Patent: Mar. 26, 2019**

(54) **ENERGY AND IMPACT TRANSFORMER
LAYER**

(75) Inventor: **Robert T. Knight**, El Cerrito, CA (US)

(73) Assignee: **Brainguard Technologies, Inc.**, El
Cerrito, CA (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 1139 days.

(21) Appl. No.: **13/554,563**

(22) Filed: **Jul. 20, 2012**

(65) **Prior Publication Data**

US 2013/0019385 A1 Jan. 24, 2013

Related U.S. Application Data

(60) Provisional application No. 61/510,401, filed on Jul.
21, 2011.

(51) **Int. Cl.**

A42B 3/04 (2006.01)

A42B 3/06 (2006.01)

A42B 3/14 (2006.01)

A41D 13/015 (2006.01)

A42B 3/08 (2006.01)

A42B 3/12 (2006.01)

A42B 3/20 (2006.01)

A42B 3/22 (2006.01)

A42C 2/00 (2006.01)

(52) **U.S. Cl.**

CPC **A42B 3/064** (2013.01); **A41D 13/015**
(2013.01); **A42B 3/04** (2013.01); **A42B 3/063**
(2013.01); **A42B 3/08** (2013.01); **A42B 3/12**
(2013.01); **A42B 3/121** (2013.01); **A42B 3/125**
(2013.01); **A42B 3/14** (2013.01); **A42B 3/20**
(2013.01); **A42B 3/22** (2013.01); **A42C 2/007**
(2013.01)

(58) **Field of Classification Search**

CPC A42B 3/063; A42B 3/04; A42B 3/121;
A42B 3/125; A42B 3/06; A42B 3/064;

A41D 13/015

USPC 2/411, 425, 410

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,809,420 A * 5/1974 Weller B60R 19/26
188/268

3,872,511 A * 3/1975 Nichols A42B 3/121
2/413

(Continued)

FOREIGN PATENT DOCUMENTS

WO WO-2004032659 4/2004

OTHER PUBLICATIONS

"Helmet with Fluid Layer that Protects Against a Common Cause of
Head Injury", *Office of Technology Licensing, University of Florida*,
[Online]. Retrieved from the Internet: <[http://apps.research.ufl.edu/
otl/pdf/marketing/13586.pdf](http://apps.research.ufl.edu/otl/pdf/marketing/13586.pdf)> Accessed on Jul. 12, 2012, 2 pgs.

(Continued)



Primary Examiner — Sally Haden

(74) *Attorney, Agent, or Firm* — Kwan & Olynick LLP

(57) **ABSTRACT**

Protective gear such as a helmet includes multiple shell
layers connected through energy and impact transformer
layers. The energy and impact transformer layers may
include conical structures used to dissipate mechanical
energy applied to an outer shell layer while allowing an
outer shell layer the ability to rotate with respect to a middle
or inner shell layer. The conical structures may be three
dimensional pyramids, three dimensional parabolic struc-
tures, and may be outwardly or inwardly oriented.

7 Claims, 6 Drawing Sheets



REVELYST 1012

(56)

References Cited

U.S. PATENT DOCUMENTS

- 3,877,076 A * 4/1975 Summers A42B 3/124
2/414
- 3,946,441 A 3/1976 Johnson
- 4,213,202 A * 7/1980 Larry A41D 31/005
2/456
- 4,307,471 A * 12/1981 Lovell A42B 3/065
2/411
- 4,345,338 A * 8/1982 Frieder, Jr. A42C 2/007
2/414
- 4,352,484 A 10/1982 Gertz et al.
- 4,432,099 A * 2/1984 Grick A42B 3/124
2/412
- 5,204,998 A * 4/1993 Liu A42B 3/121
2/411
- 5,713,082 A 2/1998 Bassette et al.
- 5,815,846 A 10/1998 Calonge
- 5,956,777 A * 9/1999 Popovich A42B 3/065
2/412
- 6,378,140 B1 4/2002 Abraham et al.
- 6,401,262 B2 * 6/2002 Bacchiega A41D 31/0061
2/411
- 6,434,755 B1 8/2002 Halstead et al.
- 6,658,671 B1 12/2003 Von Holst et al.
- 6,996,856 B2 2/2006 Puchalski
- 7,076,811 B2 7/2006 Puchalski
- 7,089,602 B2 * 8/2006 Talluri A42B 3/063
2/411
- 7,254,843 B2 8/2007 Talluri
- 8,046,845 B1 * 11/2011 Garcia A42B 3/061
2/2.5
- 8,104,593 B2 * 1/2012 Lin A42B 3/063
188/372
- 8,176,574 B2 5/2012 Bryant et al.
- 8,756,719 B2 * 6/2014 Veazie A42B 3/121
2/411
- 8,873,914 B2 * 10/2014 Ellis F16F 7/00
188/266
- 8,931,606 B2 * 1/2015 Hawkins F16F 1/50
188/371
- 8,955,169 B2 * 2/2015 Weber A42B 3/125
2/410
- 2001/0032351 A1 * 10/2001 Nakayama A42B 3/064
2/412
- 2002/0172783 A1 * 11/2002 Hawkins B29C 70/70
428/34.1
- 2004/0117896 A1 * 6/2004 Madey A42B 3/12
2/411
- 2006/0059606 A1 * 3/2006 Ferrara A01N 25/18
2/412
- 2006/0070170 A1 * 4/2006 Copeland A41D 31/0044
2/411
- 2006/0070171 A1 * 4/2006 Copeland A41D 31/005
2/455
- 2007/0068755 A1 * 3/2007 Hawkins A41D 13/0518
188/371
- 2007/0190292 A1 * 8/2007 Ferrara A42B 3/121
428/166
- 2007/0190293 A1 * 8/2007 Ferrara B29C 45/0053
428/166
- 2008/0066217 A1 * 3/2008 Depreitere A42B 3/124
2/412
- 2008/0083140 A1 * 4/2008 Ellis A42B 3/064
36/140
- 2008/0086916 A1 * 4/2008 Ellis A43B 7/1425
36/103
- 2008/0256686 A1 * 10/2008 Ferrara A41D 13/0155
2/413
- 2010/0186150 A1 * 7/2010 Ferrara A42B 3/128
2/412
- 2010/0258988 A1 * 10/2010 Darnell A42B 3/064
267/141
- 2011/0004980 A1 1/2011 Leatt et al.
- 2012/0151664 A1 * 6/2012 Kirshon A42B 3/12
2/413
- 2013/0061371 A1 * 3/2013 Phipps A42B 3/064
2/411
- 2013/0185837 A1 * 7/2013 Phipps A42B 3/12
2/2.5
- 2013/0247284 A1 * 9/2013 Hoshizaki A42B 3/12
2/413
- 2013/0254978 A1 * 10/2013 McInnis A42B 3/064
2/413
- 2013/0312161 A1 * 11/2013 Anderson A41D 13/015
2/413
- 2014/0000012 A1 * 1/2014 Mustapha H01F 7/02
2/414
- 2014/0007322 A1 * 1/2014 Marz A42B 3/065
2/411
- 2014/0013491 A1 * 1/2014 Hoshizaki A42B 3/064
2/411
- 2014/0013492 A1 * 1/2014 Bottlang A42B 3/125
2/414
- 2014/0109298 A1 * 4/2014 Faden F41H 1/08
2/411
- 2014/0109299 A1 * 4/2014 Kwan A41D 13/015
2/413
- 2014/0109304 A1 * 4/2014 Kwan A41D 13/015
2/461
- 2014/0208486 A1 * 7/2014 Krueger A42B 3/064
2/414
- 2015/0208751 A1 * 7/2015 Day A42B 3/124
2/414

OTHER PUBLICATIONS

- Goel, R et al., "Design of an Advanced Helmet Liner User Simulations", [Online]. Retrieved from the Internet: < http://mvl.mit.edu/MVLPubs/MVL_10.07_Goel.pdf > Accessed on /13/12, 8 pgs.
- "Proposal for a Novel Helmet Design", *Brainguard Technologies*, 14 pgs.
- Viano, David C., et al., "Concussion in Professional Football: Brain Responses by Finite Element Analysis: Part 9", *Neurosurgery*, vol. 57, No. 5, (Nov. 2005), 891-916.
- Bosch, Henricus V., "Crash Helmet Testing and Design Specifications", *University Press Facilities*, Eindhoven, The Netherlands, (2006), 179.
- Collins, Micky et al., "Examining Concussion Rates and Return to Play in High School Football Players Wearing Newer Helmet Technology: A Three-Year Prospective Cohort Study", *Neurosurgery*, vol. 58, No. 2, (Feb. 2006), 275-286.
- "Lazer Helmets", [Online]. Retrieved from the Internet: < <http://www.lazerhelmets.com/wp-content/uploads/2011/04/Catalogue-Motorcycling-2010-UK.pdf> >, (2010).
- May, Philip R., et al., "Woodpecker Drilling Behavior: An Endorsement of the Rotational Theory of Impact Brain Injury", *Arch Neural*, vol. 36, (Jun. 1979), 370-373.
- Wang, Lizhen et al., "Why do Woodpeckers Resist Head Impact Injury: A Biomechanical Investigation", *PLoS One*, vol. 6, No. 10, (Oct. 2011), 1-8.

* cited by examiner




Figure 1




Figure 2




Figure 3




Figure 4




Figure 5




Figure 6

1

ENERGY AND IMPACT TRANSFORMER LAYER

CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims priority to U.S. Provisional Patent Application No. 61/510,401, entitled SMART BIOMECHANICS AWARE ENERGY CONSCIOUS PROTECTIVE GEAR WITH TISSUE PROTECTION, filed on Jul. 21, 2011, the entirety of which is incorporated herein by reference for all purposes.

TECHNICAL FIELD

The present disclosure relates to an energy and impact transformer layer.

DESCRIPTION OF RELATED ART

Protective gear such as sports and safety helmets are designed to reduce direct impact forces that can mechanically damage an area of contact. Protective gear will typically include padding and a protective shell to reduce the risk of physical head injury. Liners are provided beneath a hardened exterior shell to reduce violent deceleration of the head in a smooth uniform manner and in an extremely short distance, as liner thickness is typically limited based on helmet size considerations.

Protective gear is reasonably effective in preventing injury. Nonetheless, the effectiveness of protective gear remains limited. Consequently, various mechanisms are provided to improve protective gear and energy and impact transformer layers between protective gear shell layers.

BRIEF DESCRIPTION OF THE DRAWINGS

The disclosure may best be understood by reference to the following description taken in conjunction with the accompanying drawings, which illustrate particular embodiments.

FIG. 1 illustrates types of forces on axonal fibers.

FIG. 2 illustrates one example of a piece of protective gear.

FIG. 3 illustrates one example of a container device system.

FIG. 4 illustrates another example of a container device system.

FIG. 5 illustrates one example of a multiple shell system.

FIG. 6 illustrates one example of a multiple shell helmet.

DESCRIPTION OF EXAMPLE EMBODIMENTS

Reference will now be made in detail to some specific examples of the invention including the best modes contemplated by the inventors for carrying out the invention. Examples of these specific embodiments are illustrated in the accompanying drawings. While the invention is described in conjunction with these specific embodiments, it will be understood that it is not intended to limit the invention to the described embodiments. On the contrary, it is intended to cover alternatives, modifications, and equivalents as may be included within the spirit and scope of the invention as defined by the appended claims.

For example, the techniques of the present invention will be described in the context of helmets. However, it should be noted that the techniques of the present invention apply to a wide variety of different pieces of protective gear. In the

2

following description, numerous specific details are set forth in order to provide a thorough understanding of the present invention. Particular example embodiments of the present invention may be implemented without some or all of these specific details. In other instances, well known process operations have not been described in detail in order not to unnecessarily obscure the present invention.

Various techniques and mechanisms of the present invention will sometimes be described in singular form for clarity. However, it should be noted that some embodiments include multiple iterations of a technique or multiple instantiations of a mechanism unless noted otherwise. For example, a protective device may use a single strap in a variety of contexts. However, it will be appreciated that a system can use multiple straps while remaining within the scope of the present invention unless otherwise noted. Furthermore, the techniques and mechanisms of the present invention will sometimes describe a connection between two entities. It should be noted that a connection between two entities does not necessarily mean a direct, unimpeded connection, as a variety of other entities may reside between the two entities. For example, different layers may be connected using a variety of materials. Consequently, a connection does not necessarily mean a direct, unimpeded connection unless otherwise noted.

Overview

Protective gear such as a helmet includes multiple shell layers connected through energy and impact transformer layers. The energy and impact transformer layers may include conical structures used to dissipate mechanical energy applied to an outer shell layer while allowing an outer shell layer the ability to rotate with respect to a middle or inner shell layer. The conical structures may be three dimensional pyramids, three dimensional parabolic structures, and may be outwardly or inwardly oriented.

Example Embodiments

Protective gear such as knee pads, shoulder pads, and helmets are typically designed to prevent direct impact injuries or trauma. For example, many pieces of protective gear reduce full impact forces that can structurally damage an area of contact such as the skull or knee. Major emphasis is placed on reducing the likelihood of cracking or breaking of bone. However, the larger issue is preventing the tissue and neurological damage caused by rotational forces, shear forces, oscillations, and tension/compression forces.

For head injuries, the major issue is neurological damage caused by oscillations of the brain in the cranial vault resulting in coup-contracoup injuries manifested as direct contusions to the central nervous system (CNS), shear injuries exacerbated by rotational, tension, compression, and/or shear forces resulting in demyelination and tearing of axonal fibers; and subdural or epidural hematomas. Because of the emphasis in reducing the likelihood of cracking or breaking bone, many pieces of protective gear do not sufficiently dampen, transform, dissipate, and/or distribute the rotational, tension, compression, and/or shear forces, but rather focus on absorbing the direct impact forces over a small area, potentially exacerbating the secondary forces on the CNS. Initial mechanical damage results in a secondary cascade of tissue and cellular damage due to increased glutamate release or other trauma induced molecular cascades.

Traumatic brain injury (TBI) has immense personal, societal and economic impact. The Center for Disease Control and Prevention documented 1.4 million cases of TBI in the

USA in 2007. This number was based on patients with a loss of consciousness from a TBI resulting in an Emergency Room visit. With increasing public awareness of TBI this number increased to 1.7 million cases in 2010. Of these cases there were 52,000 deaths and 275,000 hospitalizations, with the remaining 1.35 million cases released from the ER. Of these 1.35 million discharged cases at least 150,000 people will have significant residual cognitive and behavioral problems at 1-year post discharge from the ER. Notably, the CDC believes these numbers under represent the problem since many patients do not seek medical evaluation for brief loss of consciousness due to a TBI. These USA numbers are similar to those observed in other developed countries and are likely higher in third-world countries with poorer vehicle and head impact protection. To put the problem in a clearer perspective, the World Health Organization (WHO) anticipates that TBI will become a leading cause of death and disability in the world by the year 2020.

The CDC numbers do not include head injuries from military actions. Traumatic brain injury is widely cited as the “signature injury” of Operation Enduring Freedom and Operation Iraqi Freedom. The nature of warfare conducted in Iraq and Afghanistan is different from that of previous wars and advances in protective gear including helmets as well as improved medical response times allow soldiers to survive events such as head wounds and blast exposures that previously would have proven fatal. The introduction of the Kevlar helmet has drastically reduced field deaths from bullet and shrapnel wounds to the head. However, this increase in survival is paralleled by a dramatic increase in residual brain injury from compression and rotational forces to the brain in TBI survivors. Similar to that observed in the civilian population the residual effects of military deployment related TBI are neurobehavioral symptoms such as cognitive deficits and emotional and somatic complaints. The statistics provided by the military cite an incidence of 6.2% of head injuries in combat zone veterans. One might expect these numbers to hold in other countries.

In addition to the incidence of TBI in civilians from falls and vehicular accidents or military personnel in combat there is increasing awareness that sports-related repetitive forces applied to the head with or without true loss of consciousness can have dire long-term consequences. It has been known since the 1920’s that boxing is associated with devastating long-term issues including “dementia pugilistica” and Parkinson-like symptoms (i.e. Mohammed Ali). We now know that this repetitive force on the brain dysfunction extends to many other sports. Football leads the way in concussions with loss of consciousness and post-traumatic memory loss (63% of all concussions in all sports), wrestling comes in second at 10% and soccer has risen to 6% of all sports related TBIs. In the USA 63,000 high school students suffer a TBI per year and many of these students have persistent long-term cognitive and behavioral issues. This disturbing pattern extends to professional sports where impact forces to the body and head are even higher due to the progressive increase in weight and speed of professional athletes. Football has dominated the national discourse in the area but serious and progressive long-term neurological issues are also seen in hockey and soccer players and in any sport with the likelihood of a TBI. Repetitive head injuries result in progressive neurological deterioration with neuropathological findings mimicking Alzheimer’s disease. This syndrome with characteristic post-mortem neuropathological findings on increases in Tau proteins and amyloid plaques is referred to as Chronic Traumatic Encephalopathy (CTE).

The human brain is a relatively delicate organ weighing about 3 pounds and having a consistency a little denser than gelatin and close to that of the liver. From an evolutionary perspective, the brain and the protective skull were not designed to withstand significant external forces. Because of this poor impact resistance design, external forces transmitted through the skull to the brain that is composed of over 100 billion cells and up to a trillion connecting fibers results in major neurological problems. These injuries include contusions that directly destroy brain cells and tear the critical connecting fibers necessary to transmit information between brain cells.

Contusion injuries are simply bleeding into the substance of the brain due to direct contact between the brain and the bony ridges of the inside of the skull. Unfortunately, the brain cannot tolerate blood products and the presence of blood kicks off a biological cascade that further damages the brain. Contusions are due to the brain oscillating inside the skull when an external force is applied. These oscillations can include up to three cycles back and forth in the cranial vault and are referred to as coup-contra coup injuries. The coup part of the process is the point of contact of the brain with the skull and the contra-coup is the next point of contact when the brain oscillates and strikes the opposite part of the inside of the skull.

The inside of the skull has a series of sharp bony ridges in the front of the skull and when the brain is banged against these ridges it is mechanically torn resulting in a contusion. These contusion injuries are typically in the front of the brain damaging key regions involved in cognitive and emotional control.

Shear injuries involve tearing of axonal fibers. The brain and its axonal fibers are extremely sensitive to rotational forces. Boxers can withstand hundreds of punches directly in the face but a single round-house punch or upper cut where the force comes in from the side or bottom of the jaw will cause acute rotation of the skull and brain and typically a knock-out. If the rotational forces are severe enough, the result is tearing of axons.

FIG. 1 below shows how different forces affect axons. Compression **101** and tension **103** can remove the protective coating on an axon referred to as a myelin sheath. The myelin can be viewed as the rubber coating on a wire. If the internal wire of the axon is not cut the myelin can re-grow and re-coat the “wire” which can resume axonal function and brain communication. If rotational forces are significant, shear forces **105** tear the axon. This elevates the problem since the ends of cut axons do not re-attach. This results in a permanent neurological deficit and is referred to as diffuse axonal injury (DAI), a major cause of long-term neurological disability after TBI.

Some more modern pieces of protective gear have been introduced with the awareness that significant injuries besides musculoskeletal or flesh injuries in a variety of activities require new protective gear designs.

U.S. Pat. No. 7,076,811 issued to Puchalski describes a helmet with an impact absorbing crumple or shear zone. “The shell consists of three (or more) discrete panels that are physically and firmly coupled together providing rigid protection under most circumstances, but upon impact the panels move relative to one another, but not relative to the user’s head, thereby permitting impact forces to be dissipated and/or redirected away from the cranium and brain within. Upon impact to the helmet, there are sequential stages of movement of the panels relative to each other, these movements initially being recoverable, but with sufficient vector forces the helmet undergoes structural changes

in a pre-determined fashion, so that the recoverable and permanent movements cumulatively provide a protective 'crumple zone' or 'shear zone'."

U.S. Pat. No. 5,815,846 issued to Calonge describes "An impact resistant helmet assembly having a first material layer coupled to a second material layer so as to define a gas chamber therebetween which contains a quantity that provides impact dampening upon an impact force being applied to the helmet assembly. The helmet assembly further includes a containment layer disposed over the second material layer and structured to define a fluid chamber in which a quantity of fluid is disposed. The fluid includes a generally viscous gel structured to provide some resistance against disbursement from an impacted region of the fluid chamber to non-impacted regions of the fluid chamber, thereby further enhance the impact distribution and dampening of the impact force provided by the helmet assembly."

U.S. Pat. No. 5,956,777 issued to Popovich describes "A helmet for protecting a head by laterally displacing impact forces, said helmet comprising: a rigid inner shell formed as a single unit; a resilient spacing layer disposed outside of and in contact with said inner shell; and an articulated shell having a plurality of discrete rigid segments disposed outside of and in contact with said resilient spacing layer and a plurality of resilient members which couple adjacent ones of said rigid segments to one another."

U.S. Pat. No. 6,434,755 issued to Halstead describes a football helmet with liner sections of different thicknesses and densities. The thicker, softer sections would handle less intense impacts, crushing down until the thinner, harder sections take over to prevent bottoming out.

Still other ideas relate to using springs instead of crushable materials to manage the energy of an impact. Springs are typically associated with rebound, and energy stored by the spring is returned to the head. This may help in some instances, but can still cause significant neurological injury. Avoiding energy return to the head is a reason that non-rebounding materials are typically used.

Some of the protective gear mechanisms are not sufficiently biomechanically aware and are not sufficiently customized for particular areas of protection. These protective gear mechanisms also are not sufficiently active at the right time scales to avoid damage. For example, in many instances, materials like gels may only start to convert significant energy into heat after significant energy has been transferred to the brain. Similarly, structural deformation mechanisms may only break and absorb energy after a significant amount of energy has been transferred to the brain.

Current mechanisms are useful for particular circumstances but are limited in their ability to protect against numerous types of neurological damage. Consequently, an improved smart biomechanics aware and energy conscious protective gear mechanism is provided to protect against mechanical damage as well as neurological damage.

According to various embodiments, protective gear such as a helmet includes a container device to provide a structural mechanism for holding an energy and impact transformer. The design of this element could be a part of the smart energy conscious biomechanics aware design for protection. The energy and impact transformer includes a mechanism for the dissipation, transformation, absorption, redirection or force/energy at the right time scales (in some cases as small as a few milliseconds or hundreds of microseconds).

In particular embodiments, the container mechanism provides structure to allow use of an energy and impact trans-

former. The container mechanism may be two or three shells holding one or more layers of energy and impact transformer materials. That is, a multiple shell structure may have energy and impact transformer materials between adjacent shell layers. The shells may be designed to prevent direct penetration from any intruding or impeding object. In some examples, the outer shell may be associated with mechanisms for impact distribution, energy transformation, force dampening, and shear deflection and transformation. In some examples, the container mechanism can be constructed of materials such as polycarbonate, fiberglass, Kevlar, metal, alloys, combinations of materials, etc.

According to various embodiments, the energy and impact transformer provides a mechanism for the dissipation, transformation, absorption, and redirection of force and energy at the appropriate time scales. The energy and impact transformer may include a variety of elements. In some examples, a mechanical transformer element connects multiple shells associated with a container mechanism with mechanical structures or fluids that help transform the impact or shear forces on an outer shell into more benign forces or energy instead, of transferring the impact or shear forces onto an inner shell.

In some examples, a mechanical transformer layer is provided between each pair of adjacent shells. The mechanical transform may use a shear truss-like structure connecting an outer shell and an inner shell that dampens any force or impact. In some examples, shear truss structure layers connect an outer shell to a middle shell and the middle shell to an inner shell. According to various embodiments, the middle shell or center shell may slide relative to the inner shell and reduce the movement and/or impact imparted on an outer shell. In particular embodiments, the outer shell may slide up to several centimeters relative to the middle shell. In particular embodiments, the material used for connecting the middle shell to the outer shell or the inner shell could be a material that absorbs/dissipates mechanical energy as thermal energy or transformational energy. The space between the outer shell, the middle shell, and the inner shell can be filled with absorptive/dissipative material such as fluids and gels.

According to various embodiments, the energy and impact transformer may also include an electro-rheological element. Different shells may be separated by an electro-rheological element with electric field dependent viscosity. The element may essentially stay solid most of the time. When there is stress/strain on an outer shell, the electric field is activated so that the viscosity changes depending on the level of stress/strain. Shear forces on an inner shell are reduced to minimize impact transmission.

In particular embodiments, the energy and impact transformer also includes a magneto-rheological element. Various shells may be separated by magneto rheological elements with magnetic field dependent viscosity. The element may essentially stay solid most of the time. When there is stress/strain on an outer shell, the magnetic field is activated so that the viscosity changes depending on the level of stress/strain. Shear forces on an inner shell are reduced to minimize impact transmission.

Electro-rheological and magneto-rheological elements may include smart fluids with properties that change in the presence of electric field or a magnetic field. Some smart fluids undergo changes in viscosity when a magnetic field is applied. For example, a smart fluid may change from a liquid, to a gel when magnets line up to create a magnetic field. Smart fluids may react within milliseconds to reduce impact and shear forces between shells.

7

In other examples, foam and memory foam type elements may be included to absorb and distribute forces. In some examples, foam and memory foam type elements may reside beneath the inner shell. A magnetic suspension element may be used to actively or passively reduce external forces. An inner core and an outer core may be separated by magnets that resist each other, e.g. N-poles opposing each other. The inner and outer cores naturally would want to move apart, but are pulled together by elastic materials. When an outer shell is impact and the magnets are pushed closer, forces between the magnets increase through the air gap.

According to various embodiments, a concentric geodesic dome element includes a series of inner shells, each of which is a truss based geodesic dome, but connected to the outer geodesic through structural or fluidic mechanisms. This allows each geodesic structure to fully distribute its own shock load and transmit it in a uniform manner to the dome underneath. The sequence of geodesic structures and the separation by fluid provides uniform force distribution and/or dissipation that protects the inner most shell from these impacts.

In particular embodiments, a fluid/accordion element would separate an inner shell and an outer shell using an accordion with fluid/gel in between. This would allow shock from the outer core to be transmitted and distributed through the enclosed fluid uniformly while the accordion compresses to accommodate strain. A compressed fluid/piston/spring element could include piston/cylinder like elements with a compressed fluid in between that absorbs the impact energy while increasing the resistance to the applied force. The design could include additional mechanical elements like a spring to absorb/dissipate the energy.

In still other examples, a fiber element involves using a rippled outer shell with texture like that of a coconut. The outer shell may contain dense coconut fiber like elements that separate the inner core from the outer core. The shock can be absorbed by the outer core and the fibrous filling. Other elements may also be included in an inner core structure. In some examples, a thick stretchable gel filled bag wrapped around the inner shell could expand and contract in different areas to instantaneously transfer and distribute forces. The combination of the elasticity of a bag and the viscosity of the gel could provide for cushioning to absorb/dissipate external forces.

According to various embodiments, a container device includes multiple shells such as an outer shell, a middle shell, and an inner shell. The shells may be separated by energy and impact transformer mechanisms. In some examples, the shells and the energy and impact transformer mechanisms can be integrated or a shell can also operate as an energy and impact transformer.

FIG. 2 illustrates one example of a particular piece of protective gear, let 201 includes a shell layer 211 and a lining layer 213. The shell layer 211 includes attachment points 215 for a visor, chin bar, face guard, face cage, or face protection mechanism generally. In some examples, the shell layer 211 includes ridges 217 and/or air holes for breathability. The shell layer 211 may be constructed using plastics, resins, metal, composites, etc. In some instances, the shell layer 211 may be reinforced using fibers such as aramids. The shell layer 211 helps to distribute mechanical energy and prevent penetration. The shell layer 211 is typically made using lighter weight materials to prevent the helmet itself from causing injury.

According to various embodiments, a chin strap 221 is connected to the helmet to secure helmet positioning. The shell layer 211 is also sometimes referred to as a container

8

or a casing. In many examples, the shell layer 211 covers a lining layer 213. The lining layer 213 may include lining materials, foam, and/or padding to absorb mechanical energy and enhance fit. A lining layer 213 may be connected to the shell layer 211 using a variety of attachment mechanisms such as glue or Velcro. According to various embodiments, the lining layer 213 is pre-molded to allow for enhanced fit and protection. According to various embodiments, the lining layer may vary, e.g. from 4 mm to 40 mm in thickness, depending on the type of activity a helmet is designed for. In some examples, custom foam may be injected into a fitted helmet to allow for personalized fit. In other examples, differently sized shell layers and lining layers may be provided for various activities and head sizes.

The shell layer 211 and lining layer 213 protect the skull nicely and have resulted in a dramatic reduction in skull fractures and bleeding between the skull and the brain (subdural and epidural hematomas). Military helmets use Kevlar to decrease penetrating injuries from bullets, shrapnel etc. Unfortunately, these approaches are not well designed to decrease direct forces and resultant coup-contra coup injuries that result in both contusions and compression-tension axon injuries. Furthermore, many helmets do not protect against rotational forces that are a core cause of a shear injury and resultant long-term neurological disability in civilian and military personnel. Although the introduction of Kevlar in military helmets has decreased mortality from penetrating head injuries, the survivors are often left with debilitating neurological deficits due to contusions and diffuse axonal injury.

FIG. 3 illustrates one example of a container device system. According to various embodiments, protective gear includes multiple container devices 301 and 303. In particular embodiments, the multiple container devices are loosely interconnected shells holding an energy and impact transformer 305. The multiple container devices may be multiple plastic and/or resin shells. In some examples, the containers devices 301 and 303 may be connected only through the energy and impact transformer 305. In other examples, the container devices 301 and 303 may be loosely connected in a manner supplementing the connection by the energy and impact transformer 305.

According to various embodiments, the energy and impact transformer 305 may use a shear truss-like structure connecting the container 301 and container 303 to dampen any force or impact. In some examples, the energy and impact transformer 305 allows the container 301 to move or slide with respect to container 303. In some examples, up to several centimeters of relative movement is allowed by the energy and impact transformer 305.

In particular embodiments, the energy and impact transformer 305 could be a material that absorbs/dissipates mechanical energy as thermal energy or transformational energy and may include electro-rheological, magneto-rheological, foam, fluid, and/or gel materials.

FIG. 4 illustrates another example of a container device system. Container 401 encloses energy and impact transformer 403. In some examples, multiple containers or multiple shells may not be necessary. The container may be constructed using plastic and/or resin. And may expand or contract with the application of force. The energy and impact transformer 403 may similarly expand or contract with the application of force. The energy and impact transformer 403 may receive and convert energy from physical impacts on a container 401.

FIG. 5 illustrates one example of a multiple shell system. An outer shell 501, a middle shell 503, and an inner shell 505

may hold energy and impact transformative layers **511** and **513** between them. Energy and impact transformer layer **511** residing between shells **501** and **503** may allow shell **501** to move and/or slide with respect to middle shell **503**. By allowing sliding movements that convert potential head rotational forces into heat or transformation energy, shear forces can be significantly reduced.

Similarly, middle shell **503** can move and slide with respect to inner shell **505**. In some examples, the amount of movement and/or sliding depends on the viscosity of fluid in the energy and impact transformer layers **511** and **513**. The viscosity may change depending on electric field or voltage applied. In some other examples, the amount of movement and/or sliding depends on the materials and structures of materials in the energy and impact transformer layers **511** and **513**.

According to various embodiments, when a force is applied to an outer shell **501**, energy is transferred to an inner shell **505** through a suspended middle shell **503**. The middle shell **503** shears relative to the top shell **501** and inner shell **505**. In particular embodiments, the energy and impact transformer layers **511** and **513** may include thin elastomeric trusses between the shells in a comb structure. The energy and impact transformer layers **511** and **513** may also include energy dampening/absorbing fluids or devices. In some embodiments, the thin elastomeric trusses in impact transformer layer **511** are arranged such that each thin elastomeric truss is diagonally connected to outer shell layer **501** and to middle shell layer **503** in one direction. In such embodiments, each of the thin elastomeric trusses is parallel to its adjacent thin elastomeric trusses. In some embodiments, the thin elastomeric trusses in impact transformer layer **513** are also arranged such that each thin elastomeric truss is diagonally connected to middle shell layer **503** and to inner shell layer **505** in one direction. Also in such embodiments, each of the thin elastomeric trusses is parallel to its adjacent thin elastomeric trusses. In some embodiments, the thin elastomeric trusses in layer **511** and the thin elastomeric trusses in layer **513** are oriented in different or even opposite directions.

According to various embodiments, a number of different physical structures can be used to form energy and impact transformer layers **511** and **513**. In some examples, energy and impact transformer layer **511** includes a layer of upward or downward facing three dimensional conical structures separating outer shell **501** and middle shell **503**. Energy and impact transformer layer **513** includes a layer of upward or downward facing conical structures separating middle shell **503** and inner shell **505**. The conical structures in energy and impact transformer layer **511** and the conical structures in energy and impact transformer layer **513** may or may not be aligned. In some examples, the conical structures in layer **511** are misaligned with the conical structures in layer **513** to allow for improved shear force reduction.

In some examples, conical structures are designed to have a particular elastic range where the conical structures will return to the same structure after force applied is removed. The conical structures may also be designed to have a particular plastic range where the conical structure will permanently deform if sufficient rotational or shear force is applied. The deformation itself may dissipate energy but would necessitate replacement or repair of the protective gear.

Conical structures are effective in reducing shear, rotational, and impact forces applied to an outer shell **501**. Conical structures reduce shear and rotational forces applied from a variety of different directions. According to various

embodiments, conical structures in enemy and impact transformer layers **511** are directed outwards with bases situated on middle shell **503** and inner shell **505** respectively. In some examples, structures in the energy and impact transformer layer may be variations of conical structures, including three dimensional pyramid structures and three dimensional parabolic structures. In still other examples, the structures may be cylinders.

FIG. 6 illustrates one example of a multiple shell helmet. According to various embodiments, helmet **601** includes an outer shell layer **603**, an outer energy and impact transformer **605**, a middle shell layer **607**, an inner energy and impact transformer **609**, and an inner shell layer **611**. The helmet **601** may also include a lining layer within the inner shell layer **611**. In particular embodiments, the inner shell layer **611** includes attachment points **615** for a chin strap for securing helmet **601**. In particular embodiments, the outer shell layer **603** includes attachment points for a visor, chin bar, face guard, face cage, and/or face protection mechanism **615** generally. In some examples, the inner shell layer **611**, middle shell layer **607**, and outer shell layer **603** includes rides **617** and/or air holes for breathability. The outer shell layer **603**, middle shell layer **607**, and inner shell layer **611** may be constructed using plastics, resins, metal, composites, etc. In some instances, the outer shell layer **603**, middle shell layer **607**, and inner shell layer **611** may be reinforced using fibers such as aramids. The energy and impact transformer layers **605** and **609** can help distribute mechanical energy and shear forces so that less energy is imparted on the head.

According to various embodiments, a chin strap **621** is connected to the inner shell layer **611** to secure helmet positioning. The various shell layers are also sometimes referred to as containers or casings. In many examples, the inner shell layer **611** covers a lining layer (not shown). The lining layer may include lining materials, foam, and/or padding to absorb mechanical energy and enhance fit. A lining layer may be connected to the inner shell layer **611** using a variety of attachment mechanisms such as glue or Velcro. According to various embodiments, the lining layer is pre-molded to allow for enhanced fit and protection. According to various embodiments, the lining layer may vary, e.g. from 4 mm to 40 mm in thickness, depending on the type of activity a helmet is designed for. In some examples, custom foam may be injected into a fitted helmet to allow for personalized fit. In other examples, differently sized shell layers and lining layers may be provided for various activities and head sizes.

The middle shell layer **607** may only be indirectly connected to the inner shell layer **611** through enemy and impact transformer **609**. In particular embodiments, the middle shell layer **607** floats above inner shell layer **611**. In other examples, the middle shell layer **607** may be loosely connected to the inner shell layer **611**. In the same manner, outer shell layer **603** floats above middle shell layer **607** and may only be connected to the middle shell layer through energy and impact transformer **605**. In other examples, the outer shell layer **603** may be loosely and flexibly connected to middle shell layer **607** and inner shell layer **611**. The shell layers **603**, **607**, and **611** provide protection against penetrating forces while energy and impact transformer layers **605** and **609** provide protection against compression forces, shear forces, rotational forces, etc. According to various embodiments, energy and impact transformer layer **605** allows the outer shell **603** to move relative to the middle shell **607** and the energy and impact transformer layer **609** allows the outer shell **603** and the middle shell **607** to move relative to the inner shell **611**. Compression, shear, rotation,

11

impact, and/or other forces are absorbed, deflected, dissipated, etc., by the various layers.

According to various embodiments, the skull and brain are not only provided with protection against skull fractures, penetrating injuries, subdural and epidural hematomas, but also provided with some measure of protection against direct forces and resultant coup-contra coup injuries that result in both contusions and compression-tension axon injuries. The skull is also protected against rotational forces that are a core cause of a shear injury and resultant long-term neurological disability in civilian and military personnel.

In some examples, the energy and impact transformer layers 605 and 609 may include passive, semi-active, and active dampers. According to various embodiments, the outer shell 603, middle shell 607, and the inner shell 611 may vary in weight and strength. In some examples, the outer shell 603 has significantly more weight, strength, and structural integrity than the middle shell 607 and the inner shell 611. The outer shell 603 may be used to prevent penetrating forces, and consequently may be constructed using higher strength materials that may be more expensive or heavier.

Although the foregoing invention has been described in some detail for purposes of clarity of understanding, it will be apparent that certain changes and modifications may be practiced within the scope of the appended claims. Therefore, the present embodiments are to be considered as illustrative and not restrictive and the invention is not to be limited to the details given herein, but may be modified within the scope and equivalents of the appended claims.

The invention claimed is:

1. Protective gear, comprising:

a helmet, the helmet comprising:

an outer shell layer;

a middle shell layer;

an inner shell layer;

an outer energy and impact transformer layer connecting the outer shell layer to the middle shell layer, wherein the outer energy and impact transformer layer comprises a first plurality of thin elastomeric trusses configured to absorb energy from mechanical forces imparted onto the outer shell layer, wherein the outer energy and impact transformer layer allows the outer shell layer to rotate relative to the middle shell layer, wherein the first plurality of thin elastomeric trusses are arranged such that each thin elastomeric truss of the first plurality of thin elastomeric trusses diagonally connects the outer shell layer to the middle shell layer in a first direction and wherein each thin elastomeric truss of the first plurality of thin elastomeric trusses is parallel to adjacent thin elastomeric trusses of the first plurality of thin elastomeric trusses, wherein the outer energy and impact transformer layer is filled with an absorptive fluid or gel; and

an inner energy and impact transformer layer connecting the middle shell layer to the inner shell layer,

12

wherein the inner energy and impact transformer layer comprises a second plurality of thin elastomeric trusses configured to absorb energy from mechanical forces imparted onto the middle shell layer, wherein the inner energy and impact transformer layer allows the middle shell layer to rotate relative to the inner shell layer, wherein the second plurality of thin elastomeric trusses are arranged such that each thin elastomeric truss of the second plurality of thin elastomeric trusses diagonally connects the middle shell layer to the inner shell layer in a second direction and wherein each thin elastomeric truss of the second plurality of thin elastomeric trusses is parallel to adjacent thin elastomeric trusses of the second plurality of thin elastomeric trusses, wherein the second direction is opposite to the first direction, wherein the inner energy and impact transformer layer is filled with an absorptive fluid or gel; wherein the outer, middle, and inner shell layers are configured to protect against penetrating forces and are comprised of reinforcing aramids and one or more of the following materials: plastics, resins, metal, and composites;

wherein the energy and impact transformer layers are configured to protect against compression forces, shear forces, impact forces, and rotational forces, wherein the energy and impact transformer layers also include passive, semi-active, and active dampers;

wherein the outer shell has more weight, strength, and structural integrity than the middle shell and inner shell layers;

wherein the first and second pluralities of thin elastomeric trusses are comprised of an elastomeric truss material that absorbs and dissipates mechanical energy as thermal energy, wherein the elastomeric truss material is different in composition from a material of the outer, middle, and inner shell layers.

2. The helmet of claim 1, wherein the absorptive fluid or gel in either of the energy and impact transformer layers comprises a smart fluid that undergoes changes in viscosity when a magnetic field is applied.

3. The helmet of claim 1, wherein the outer energy and impact transformer layer comprises a magneto-rheological element.

4. The helmet of claim 1, wherein mechanical forces include impact forces.

5. The helmet of claim 1, wherein mechanical forces include rotational and shear forces.

6. The helmet of claim 1, wherein a lining layer is connected to the inner shell layer, wherein the lining layer is configured to conform to a human head.

7. The helmet of claim 6, wherein the lining layer comprises foam.

* * * * *