



US 20060063129A1

(19) **United States**(12) **Patent Application Publication**
Hirsch(10) **Pub. No.: US 2006/0063129 A1**(43) **Pub. Date: Mar. 23, 2006**(54) **COOLING DEVICE AND METHOD FOR
INTRAORAL DEVICE ILLUMINATION
SOURCE**923, filed on Jan. 25, 2000, now abandoned, which is
a continuation of application No. 09/193,916, filed on
Nov. 17, 1998, now Pat. No. 6,022,214.(76) Inventor: **James A. Hirsch**, Santa Barbara, CA
(US)**Publication Classification**

Correspondence Address:

**PROCOPIO, CORY, HARGREAVES &
SAVITCH LLP
530 B STREET
SUITE 2100
SAN DIEGO, CA 92101 (US)**(51) **Int. Cl.****A61C 17/06** (2006.01)(52) **U.S. Cl.** **433/93; 433/29**

(57)

ABSTRACT

A method of using a heat sink device with an intraoral illumination device includes inserting an intraoral illumination device at least partially in a patient's mouth, connecting a heat sink device to the intraoral illumination device, the heat sink device including an illumination device that emits light and heat when activated and a heat sink member thermally coupled to the illumination device; activating the illumination device so that light is transmitted to the intraoral illumination device and into the patient's mouth, aspirating fluid from the patient's mouth at negative pressure; and causing aspirated fluid to flow past the heat sink member at negative pressure so that heat is removed from the heat sink member, causing the illumination device to be cooled.

(21) Appl. No.: **11/223,098**(22) Filed: **Sep. 9, 2005****Related U.S. Application Data**

(63) Continuation-in-part of application No. 10/375,230, filed on Feb. 27, 2003, now Pat. No. 6,974,321, which is a continuation-in-part of application No. 10/006,732, filed on Nov. 15, 2001, now Pat. No. 6,575,746, which is a continuation of application No. 09/777,491, filed on Feb. 5, 2001, now Pat. No. 6,338,627, which is a continuation of application No. 09/490,





FIG. 1






FIG. 2

FIG. 3





FIG. 2




FIG. 5




FIG. 6




FIG. 7





FIG. 9




FIG. 10






FIG. 11A

FIG. 11B






FIG. 15








FIG. 16








FIG. 19A




FIG. 19B




FIG. 19C




FIG. 19D





FIG. 19E






FIG. 21




FIG. 22

COOLING DEVICE AND METHOD FOR INTRAORAL DEVICE ILLUMINATION SOURCE

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This is a continuation-in-part of pending prior application Ser. No. 10/375,230 filed Feb. 27, 2003, which is a continuation-in-part of pending prior application **10/006,732** filed Nov. 15, 2001, which issued on Jun. 10, 2003 as U.S. Pat. No. 6,575,746, which is a continuation of prior application Ser. No. 09/777,491 filed Feb. 5, 2001 which issued on Jan. 15, 2002 as U.S. Pat. No. 6,338,627, which is a continuation of prior application Ser. No. 09/490,923 filed on Jan. 25, 2000, now abandoned, which is a continuation of prior application Ser. No. 09/193,916 filed on Nov. 17, 1998, which issued on Feb. 8, 2000 as U.S. Pat. No. 6,022,214.

FIELD OF THE INVENTION

[0002] The invention relates to dental appliances for illuminating and/or vacuum suction of the mouth, and accessories and methods therefor.

BACKGROUND OF THE INVENTION

[0003] Illuminating the interior of a dental patient's mouth during dental examination and/or operation is difficult because the patient's mouth must be illuminated through a narrow opening, i.e., the patient's mouth, and the dental operator must work in close proximity to the mouth, often blocking the light source. Proper illumination is essential for dental examination and/or operation.

[0004] The oral cavity is typically illuminated by a focused light source mounted approximately two to three feet above a dental chair that the patient rests on. The light source is configured to direct light onto and into the patient's mouth. The amount of light entering the oral cavity using this type of lighting is somewhat limited due to the fact that the light source is remote from the patient's mouth. Additionally, the dental operator must often position oneself or his or her instruments between the light source and the patient's mouth to properly view the patient's mouth, blocking light from entering the mouth. The blocking of light casts an effective shadow in the patient's mouth or in areas of the patient's mouth such as certain teeth.

[0005] In order to inhibit this blocking or shadowing, fiber optic lighting has been incorporated into handheld dental instruments. Typically multiple fiber optic strands extend longitudinally along the instrument and include a light outlet end configured to direct light towards the end of the instrument. However, this type of lighting has a number of drawbacks. Light is only directed on a limited area in the mouth and does not provide illumination for the entire oral cavity. Additionally, the presence of this type of lighting, typically as an add-on feature on the instrument interferes with the comfortable and proper use of the instrument. The fiber optic bundles also—degrade over time because the fiber optics and instrument go through autoclaving numerous times. Components of the instrument, e.g., turbines, may be easily changed once degraded but the fiber optic bundles can not.

[0006] Other devices have been designed specifically for illuminating a patient's teeth, but these devices suffer from

any or all of the following drawbacks: inadequate illumination of the patient's teeth, and interference with other dental instruments used during the examination and/or operation.

[0007] The present inventors have recognized the desirability of using LED(s) or other illumination sources in conjunction with and/or adjacent to intraoral illumination and aspiration devices. A problem with the use of LED(s) or other illumination sources in this manner is that these illumination device(s) emit heat, which can damage the device or accessories and be uncomfortable or hazardous for the patient.

SUMMARY OF THE INVENTION

[0008] An aspect of the invention involves a method of using a heat sink device with an intraoral illumination device. The method includes inserting an intraoral illumination device at least partially in a patient's mouth, connecting a heat sink device to the intraoral illumination device, the heat sink device including an illumination device that emits light and heat when activated and a heat sink member thermally coupled to the illumination device; activating the illumination device so that light is transmitted to the intraoral illumination device and into the patient's mouth, aspirating fluid from the patient's mouth at negative pressure; and causing aspirated fluid to flow past the heat sink member at negative pressure so that heat is removed from the heat sink member, causing the illumination device to be cooled.

[0009] Another aspect of the invention involves a method of using a heat sink with an intraoral illumination device. The method includes providing a heat sink with one or more LEDs to illuminate the patient's mouth through the intraoral illumination device, the one or more LEDs emitting heat when activated, the heat sink including a fluid delivery lumen for delivering aspirated cooling fluid under a vacuum condition in the region of the one or more LEDs; and removing heat from the region of the one or more LEDs by causing aspirated fluid under a vacuum condition to flow through the region of the one or more LEDs.

[0010] A still further aspect of the invention involves a heat sink device for use with an intraoral illumination device configured for illumination of and aspiration of fluid from the patient's mouth. The heat sink device includes an illumination device configured to emit light and heat when activated; and a heat sink member thermally coupled to the illumination device and configured to receive aspirated fluid from the patient's mouth at negative pressure so that heat is removed from the heat sink member, causing the illumination device to be cooled.

[0011] Other, more particular features and advantages of the inventions are set forth in the following detailed description and drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

[0012] The drawings illustrate both the design and utility of preferred embodiments of the present invention, in which similar elements are referred to by common reference numbers, wherein:

[0013] **FIG. 1** is a front perspective view of a preferred embodiment of the intraoral illumination device of the present invention shown inside a patient's mouth;

[0014] FIG. 2 is a front perspective view of the components of the intraoral illumination device illustrated in FIG. 1 in a disassembled state;

[0015] FIG. 3 is a front perspective view of the intraoral illumination device illustrated in FIG. 1;

[0016] FIG. 4 is a rear perspective view of the intraoral illumination device illustrated in FIG. 1;

[0017] FIG. 5 is a top plan view of the intraoral illumination device illustrated in FIG. 1;

[0018] FIG. 6 is a front elevational view of the intraoral illumination device illustrated in FIG. 1;

[0019] FIG. 7 is an end view of the intraoral illumination device illustrated in FIG. 1;

[0020] FIGS. 8A and 8B are cross-sectional views of the intraoral illumination device illustrated in FIG. 1 and illustrate the evacuation of fluids through the evacuation system of the device;

[0021] FIG. 9 is a front perspective view of an alternative preferred embodiment of the intraoral illumination device;

[0022] FIG. 10 is a rear perspective view of the intraoral illumination device illustrated in FIG. 9;

[0023] FIG. 11a is a partial perspective view of an alternative embodiment of an integrated light carrier and vacuum tube connector;

[0024] FIG. 11b is a partial perspective view of an alternative embodiment of an integrated light carrier and vacuum tube that the integrated light carrier and vacuum tube connector illustrated in FIG. 11 may be connected with;

[0025] FIG. 12 is a front perspective view of an alternative preferred embodiment of the intraoral illumination device and shows the intraoral illumination device in conjunction with a preferred embodiment of a multi-lumen tube;

[0026] FIG. 13 is a rear, top perspective view of a preferred embodiment of a light dispersion piece that may be used with the intraoral illumination device illustrated in FIG. 12;

[0027] FIG. 14 is a cross sectional view of a connection section of the intraoral illumination device and an end portion of the multi-lumen tube;

[0028] FIG. 15 is a cross sectional view of the multi-lumen tube taken along lines 15-15 of FIG. 14;

[0029] FIG. 16 is a perspective view of an embodiment of a transition mechanism that may be used to transition a separate light carrier and vacuum tube into the single multi-lumen tube; and

[0030] FIG. 17 is perspective view of an embodiment of a connector that may be used to couple the transition mechanism to the multi-lumen tube.

[0031] FIG. 18A is a front perspective view of a further embodiment of an intraoral illumination device in conjunction with an embodiment of an optional vacuum-only adapter shown separated from the intraoral illumination device.

[0032] FIG. 18B is a rear perspective view of the intraoral illumination device and the optional vacuum-only adapter illustrated in FIG. 18A.

[0033] FIG. 19A is a front elevational view of the intraoral illumination device illustrated in FIG. 18A.

[0034] FIG. 19B is a left side elevational view of the intraoral illumination device illustrated in FIG. 18A.

[0035] FIG. 19C is a bottom plan view of the intraoral illumination device illustrated in FIG. 18A.

[0036] FIG. 19D is a right side elevational of the intraoral illumination device illustrated in FIG. 18A.

[0037] FIG. 19E is a rear elevational view of the intraoral illumination device illustrated in FIG. 18A.

[0038] FIG. 20A is a front elevational view of the intraoral device adapter illustrated in FIG. 18A.

[0039] FIG. 20B is a left side elevational view of the intraoral device adapter illustrated in FIG. 18A.

[0040] FIG. 20C is a bottom plan view of the intraoral device adapter illustrated in FIG. 18A.

[0041] FIG. 20D is a right side elevational view of the intraoral device adapter illustrated in FIG. 18A.

[0042] FIG. 20E is a rear elevational view of the intraoral device adapter illustrated in FIG. 18A.

[0043] FIG. 21 is a rear perspective view of an embodiment of a combined illumination, aspiration and heat sink device for use with an intraoral illumination device.

[0044] FIG. 22 is an exploded perspective view of the combined illumination, aspiration and heat sink device illustrated in FIG. 21

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

[0045] An aspect of the invention involves a combined illumination, aspiration and heat sink device for use with an intraoral illumination device. Before describing the combined illumination, aspiration and heat sink device, a number of embodiments of intraoral illumination devices, which represent other aspects of the invention, will first be described.

[0046] With reference to FIGS. 1 and 2, an embodiment of an intraoral illumination device, indicated generally by the reference numeral 20, will now be described. The intraoral illumination device 20 generally includes a tongue and cheek retractor 22, a dispersion piece 24, and a bite block or piece 26. The tongue and cheek retractor 22 is a disposable piece, and the dispersion piece 24 and bite piece 26 are sterilizable for reuse. In an alternative embodiment, the entire intraoral illumination device 20 is disposable. The dispersion piece 24 is coupled to a light carrier such as a fiber optic bundle 28 and extraoral light source 30 for illuminating the dispersion piece 24. A fluid evacuation tube 32 is in communication with the bite block 26 and a fluid evacuation system 34 of the device 20 for evacuating fluids from a patient's mouth 36.

[0047] The intraoral illumination device 20 will now be described generally in use. The patient opens his or her mouth 36 and a health care provider inserts the device 20

into an intraoral cavity 38 of the patient's mouth 36 between the patient's upper jaw 40 and lower jaw 42. The patient rests his or her jaws 40, 42 during the process to be performed by gently biting on the bite block 26 with his or her rear teeth 44. To help isolate the area of the mouth 36 being worked on and protect the patient's mouth from being injured by the dental tools, the tongue and cheek retractor 22 urges the patient's cheek and tongue away from the area of isolation. Fluids produced in the patient's mouth 36 during the process are removed through the fluid evacuation system 34 of the device 20 and vacuum tube 32. Light transmitted through the light carrier 28 to the dispersion piece 24 is dispersed outward from the dispersion piece 24, towards the front of the patient's mouth, from a rear, central part of the intraoral cavity 38 flooding the patient's mouth with light. Illuminating the area of interest in the patient's mouth in this manner eliminates the aforementioned problems with blocked light or shadowing.

[0048] Although this invention has been described in connection with illuminating, isolating, and removing fluids from a patient's mouth for dentistry, it will be readily understood by those skilled in the art how the present invention may have other mouth-related applications where illumination in the mouth is required other than dentistry such as, but not by way of limitation, oral surgery or other dental operations.

[0049] With reference to FIGS. 1-7, each of the components of the device 20 will now be described. The tongue and cheek retractor 22 is made of a single molded piece of soft, flexible, biocompatible material such as Pebax, santoprene, or a molded vinyl material. However, it will be readily understood by those skilled in the art that other soft, flexible materials could be used. The tongue and cheek retractor 22 is preferably produced by a gas-assist injection molding process in order to produce the internal vacuum channels described below. However, it will be readily understood by those skilled in the art that other molding processes such as an injection molding process could also be used. As discussed in more detail below, the tongue and cheek retractor 22 may be a separate piece that can be easily added to or removed from the dispersion piece 24. The tongue and cheek retractor 22 also may come in two different main configurations, depending on the side of the mouth being examined and/or operated on, i.e., left side, right side, and different sizes for different size and shaped mouths. The retractor 22 has an inner surface 46 and an outer surface 48.

[0050] The retractor 22 includes a curved main body portion 50 and a cheek retractor portion 52.

[0051] The main body portion 50 includes an upper roof portion 54 configured to rest against the roof of the patient's mouth 36 during use and a lower tongue retractor portion 56 to keep the tongue protected and retracted. The lower tongue retractor portion 56 helps to isolate the area of interest in the mouth 36 and protect the tongue from instruments such as dental drills during the dental procedure. The tongue retractor portion 56 includes internal evacuation channels 58. Evacuation holes 60 on both the inner surface 46 and outer surface 48 of the tongue retractor portion 56 communicate with the evacuation channels 58. The evacuation channels 58 terminate at an upper part of the tongue retractor portion 56 at a main receiving channel 62. The main receiving channel 62 includes a lip 64 for slidably receiving the

dispersion piece 24. A pair of shallow evacuation channels 66 extend along a portion of the main receiving channel 62. Evacuation holes 66 allow communication of the evacuation channels 58 with the outer surface 48 of the retractor 22.

[0052] The cheek retractor portion 52 has a curved, fish-tail shape and includes a pair of evacuation channels 68 exposed to the outer surface 48 of the retractor 22 that communicate with the evacuation channels 66. The cheek retractor portion 52 protects adjacent cheek tissue during the dental procedure and helps to isolate the area of interest of the mouth 36 during the dental procedure by retracting the cheek tissue.

[0053] The dispersion piece 24 is an illumination member and is preferably made of a single, injection-molded piece of light-dispersive, biocompatible, sterilizable material. The dispersion piece 24 may be made of a rigid material such as acrylic or a flexible material such as a molded flexible urethane. However, it will be readily understood by those skilled in the art that other clear, flexible or rigid materials may be used. The dispersion piece 24 preferably has an arcuate, semi-circular shape and includes a generally U-shaped dispersion lens 70, a fluid evacuation portion 72, and a pivot portion 74.

[0054] The dispersion lens 70 includes a flange 76 that is slidably received by the lip 64 of the main receiving channel 62 for attaching the dispersion piece 24 to the tongue and cheek retractor 22. The dispersion lens 70 may have a composition that is varied, e.g., graduated, to control the amount of dispersion in different areas of the lens 70 and evenly distribute the overall illumination. This helps prevent "hot spots" in the dispersion lens 70, i.e., areas of the lens 70 that emit a greater concentration of light. These "hot spots" make it difficult for the health care provider to observe the patient's mouth. For example, in the area where the fiber optic bundle 28 connects with the dispersion lens 70, there may be a less textured composition to inhibit the breaking up of internal reflections, and a progressively more textured composition as one approaches the opposite end of the lens 70. It will be readily understood by those skilled in the art that the tongue and cheek retractor 22 or other covering may have a similar varied composition to control dispersion of light in a similar manner. The dispersion lens 70 optically communicates with the light carrier 28 through a stem 78 and a separate connector 79. The light carrier 28 is preferably adapted to be directly connected to a commercially available illumination source as those found in most dentist offices or adapted to be connected to such sources through a connector or transition mechanism (not shown). Alternatively, the stem 78 and connector 79 may be a single integrated molded piece. The stem 78 serves as a light coupling between the light carrier 28 and dispersion lens 70.

[0055] In use, light shines outward from the lens 70 and is scattered by the lens 70 to illuminate the patient's mouth 36. When in place, the configuration of the device 20 causes light to be transmitted by the dispersion lens 70 from a central, rear part of the intraoral cavity, substantially between the patient's rear teeth 44. The U-shaped dispersion lens 70 has a generally 180 degree arcuate shape. This generally 180 degree arcuate shape and the dispersional qualities of the lens 24 spread the total area of illumination. Illuminating the mouth from the central, rear part of the intraoral cavity and the above-described attributes of the

lens **24** eliminate shadows caused by a single-point light source, and shadows caused by the health care provider or equipment used by the health care provider. The intraoral illumination device **20** may replace or be used with dental instruments including fiber optic lighting.

[0056] The fluid evacuation portion **72** includes a first main evacuation channel **80** and a second main evacuation channel **82** for evacuating fluids from the device **20**.

[0057] The pivot portion **74** includes a first well **84** and a second well **86** that respectively communicate with the first and second main evacuation channels **80**, **82**. A first recess **88** and second recess **90** are used to further communicate the wells **84**, **86** with the fluid evacuation tube **32** in a manner to be described. Respective pivot pins **92** extend from each well **84**, **86**.

[0058] The bite block **26** is made of a single piece of biocompatible, sterilizable material such as rubber. The bite block **26** may be formed by a compression molding process, a transfer molding process, a casting process, an injection molding process, or similar process. The bite block **26** includes ribs **94** and ridges **96** along opposite faces **98** of the bite block **26**. The ribs **94** and ridges **96** help to prevent the bite block **26** from slipping between the molar and bicuspid teeth **44** of the patient. When held or engaged between the patient's teeth, the bite block **26** functions to hold the dispersion lens **70** in a rear, central part of the interior cavity of the patient's mouth so that light can be transmitted outward therefrom for illuminating the interior cavity.

[0059] A pivot portion **100** of the bite block **26** includes opposite receiving grooves **102**. The receiving grooves **102** receive the pivot pins **92** of the dispersion lens **70** for pivotally connecting the dispersion piece **24** and tongue and cheek retractor **22** to the bite block **26**. This pivoting ability allows the health care provider to adjust, i.e., swivel, the dispersion piece **24** and tongue and cheek retractor **22** to accommodate patients with different arch widths.

[0060] The intraoral illumination device **20** may also come in different sizes and to accommodate different mouth sizes and shapes.

[0061] In an alternative embodiment of the device (FIGS. **9**, **10**, **12**), the dispersion piece **24** and bite piece **26** are not pivotally connected to each other, i.e., the connection is fixed. If the connection is fixed, it is especially important to provide the intraoral illumination device **20** in different configurations and sizes to accommodate the different mouth sizes and shapes. Likewise, if the device (FIGS. **9**, **10**, **12**) is disposable, it is important to provide the device in different configurations and sizes to accommodate the different mouth sizes and shapes.

[0062] The bite block **26** includes an internal evacuation channel **104** in communication with the first and second main evacuation channels **80**, **82** through the first and second recesses **88**, **90**, respectively, for evacuating fluids from the patient's mouth **36** during the procedure. The recesses **88**, **90** are sized to allow constant sealed communication of the internal evacuation channel **104** with the main evacuation channels **80**, **82**, regardless of the pivoted position or articulation of the dispersion piece **24** and tongue and cheek retractor **22**. External evacuation channels **106** are located on the outside of the bite block **26** and are in communication with the internal evacuation channel **104** for further removal

of fluids from the mouth **36**. Fluids are vacuumed from the internal evacuation channel **104** of the bite block **26** through an exit port **108**.

[0063] During use, the patient rests his or her jaws **40**, **42** on the faces **98** of the bite block **26**, eliminating the need to strain one's jaw muscles to keep the mouth open. This resting of the jaws **40**, **42** causes the bite block **26** to hold the dispersion piece **24** and tongue and cheek retractor **22** in the rear, central part of the oral cavity. The bite block **26** also serves as an evacuation exit for fluids and as a means for positioning and holding the dispersion piece **24** and tongue and cheek retractor **22** in the oral cavity.

[0064] Before inserting the intraoral illumination device **20** in the patient's mouth **36**, the health care provider ensures that the intraoral illumination device **20** is configured for examining and/or operating on the specific area of the patient's mouth of interest, i.e., right side, left side. If the device **20** includes a replaceable tongue and cheek retractor **22**, the tongue and cheek retractor **22** used with the device **20** should be the proper configuration and size for the area of the patient's mouth of interest. A tongue and cheek retractor **22** specific to the size and area of the mouth of interest is added to the dispersion piece **24** by sliding the flange **76** of the dispersion lens **70** into the main receiving channel **62** of the tongue and cheek retractor **22**. Alternatively, if the device is disposable (FIGS. **9**, **10**, **12**), a device specific to the size and area of the mouth of interest is used. The device is then inserted into the patient's mouth **36** in the manner described above. If the provider desires to examine the opposite side of the patient's mouth **36**, the health care provider removes the device **20** from the patient's mouth, removes the tongue and cheek retractor **22** from the dispersion piece **24** by sliding the retractor **22** off of the flange **76**, flips the bite block **26** and dispersion piece **24**, which are common for both sides of the mouth **36**, adds a new tongue and cheek retractor **22** configured for use with the opposite side of the mouth **36**, and places the device **20** back into the patient's mouth **36** so that bite block **26** resides in the opposite side of the patient's mouth **36**. Alternatively, if the device is disposable, the health care provider must ensure that a device adapted for use with the size and side of the mouth being examined is used. After use of the intraoral illumination device **20**, the tongue and cheek retractor **22** is disposed and the bite piece **26** and dispersion piece **24** are autoclaved or sterilized by a similar method. If a disposable intraoral illumination device is used, the device is simply disposed of in a proper biohazardous receptacle.

[0065] With reference to FIGS. **8A** and **8B**, the fluid evacuation system **34** of the intraoral illumination device **20** will now be described in greater detail. During dental examination and/or operation, a number of fluids, e.g., saliva from the parotid gland, blood, water from the dental equipment, are produced in the patient's mouth **36**. It is important to remove these fluids for the comfort of the patient, to prevent fluids and material from being aspirated into the throat or lungs of the patient, and to assist the health care provider in observing and/or operating within the patient's mouth **36**. The fluid evacuation system **34** removes fluids from all areas of the mouth, e.g., operating side, vestibule area on the operation side, the lingual vestibule (along the side of the tongue), contra-lateral side vestibule, eliminating the need for constant patient mouth rinsing and the need for a dental assistant to aspirate debris.

[0066] The fluid evacuation system **34** is comprised of the aforementioned evacuation channels and holes located in fluid evacuation members such as the tongue and cheek retractor **22**, dispersion piece **24**, and bite block **26**. As used herein, the term “fluid evacuation member” refers to a piece that includes one or more evacuation channels for removing fluids from the patient’s mouth. For example, as illustrated in **FIGS. 8A and 8B**, fluid is drawn from the tongue area through the evacuation holes **60** and evacuation channels **58** in the tongue retractor portion **56**. This fluid is further drawn through the second main evacuation channel **82** of the dispersion piece **24**, and the bite block **26**, and out the vacuum tube **32**. The suction drawing the fluids and debris out the vacuum tube **32** is provided by a vacuum source **110** (**FIG. 1**).

[0067] With reference to **FIGS. 9 and 10**, an intraoral illumination device **112** constructed in accordance with an alternative preferred embodiment of the invention will now be described. Elements of the intraoral illumination device **112** similar to those described above with respect to the intraoral illumination device **20** are referred to by common reference numbers, but with an “a” suffix, e.g., dispersion piece **24a**. The intraoral illumination device **112** is similar to the intraoral illumination device described above, except it is adapted for use as a disposable unit, eliminating the need for sterilization and the associated costs and spread-of-disease risks. The device **112** includes an integrated bite block and light carrier/fluid evacuation tube connector **114**. The connector **114** is an over-molded piece, has a bi-lumen configuration, and is configured to extend significantly outside of the mouth of the patient where it connects with a combined bi-lumen light carrier and vacuum tube **116**. Because this connection between the connector **114** and combined light carrier and vacuum tube **116** is substantially outside of the patient’s mouth, the combined light carrier and vacuum tube **16** can be re-used, i.e., does not have to be disposable and does not need to be autoclaved, avoiding degradation, especially of the light carrier, e.g., fiber optic bundle. As discussed above, the bite block **26a** and dispersion piece **24a** may be fixed relative to each other. Alternatively, as discussed above, the dispersion piece **24a** may be pivotally connected to the bite block **26a** in order to accommodate different size arch widths. Regardless, the bite block **26a**, dispersion piece **24a**, and tongue and cheek retractor **22a** together form a single, integrated disposable piece.

[0068] With reference to **FIGS. 11A and 11B**, an alternative embodiment of an integrated bite block and light carrier/fluid evacuation connector **118** and combined light carrier and vacuum tube **120** are shown. In this embodiment, the light carrier portions and fluid evacuation portions are coaxially aligned.

[0069] With reference to **FIGS. 12 and 13**, an intraoral illumination device **122** constructed in accordance with an additional preferred embodiment of the invention will now be described. Elements of the intraoral illumination device **122** similar to those described above with respect to the intraoral illumination devices **20**, **112** are referred to by common reference numbers, and with a “b” suffix. Similar to the intraoral illumination device **112** described above, the intraoral illumination device **122** is adapted for use as a disposable unit, eliminating the need for autoclaving and the associated costs and spread-of-disease risks. The device **112** preferably has a two-piece, integrated construction. The

device includes a dispersion piece **124** surrounded by a tongue and cheek retractor **126**.

[0070] The dispersion piece **124** is preferably made of single, rigid, light-dispersive material such as acrylic or a flexible material such as a molded flexible urethane. However, it will be readily understood by those skilled in the art that other clear, flexible or rigid materials may be used. The dispersion piece **124** has an arcuate, light-dispersing section **128**, a bite block section **130**, and an optical connection section **132**. The light-dispersing section **128** is received within a main receiving channel **134** of the tongue and cheek retractor **126**. The light-dispersing section **128** may have a composition that is varied, e.g., graduated, to control the amount of dispersion in different areas of this section **128** and evenly distribute the overall lumination. The bite block section **130** includes a generally rigid support structure for the bite block. The optical connection section **132** is configured to optically connect the light-dispersing section **128** to the light source through a light carrier such as a fiber optic bundle.

[0071] The tongue and cheek retractor **126** includes a main body section **50b**, a cheek retractor portion **52b**, an upper roof portion **54b**, and a tongue retractor portion **56b**. Fluid evacuation channels (not shown) within the tongue and cheek retractor **126** communicate with the outside of the tongue and cheek retractor (such as through evacuation holes **60b**) to remove fluids from the patient’s mouth. The fluid evacuation channels communicate with the main evacuation channel **134**. The tongue and cheek retractor **126** includes a bite block **136** and a connection section **138**. The connection section **138** is configured to extend outside of a patient’s mouth and attach to a multi-lumen tube **140**. The connection section **138** includes a retention barb **142**. The connection section **138** also houses a pair of fluid evacuation channels **144** and the optical connection section **132**.

[0072] The multi-lumen tube **140** includes fluid evacuation lumens **146** in order to communicate the fluid evacuation system in the device **122** with a vacuum source and a light carrier **148** in order to optically couple the dispersion piece **124** with a light source. The multi-lumen tube **140** includes a connector **150** for attaching the intraoral illumination device to the multi-lumen tube **140**. A slot **152** in the connector **150** is configured to receive and retain the retention barb **142** when the connection section **138** is fully engaged with the multi-lumen tube **140**.

[0073] With reference to **FIG. 16**, an embodiment of a transition mechanism **154** to transition a pre-existing light carrier **156** and a vacuum tube **158** at the health care provider’s into the single, multi-lumen tube **140** is shown. The transition mechanism **154** includes the appropriate connections for attachment to pre-existing light carriers **156** and vacuum tubes **158** or may include separate connectors for interfacing between light carriers **156** and vacuum tubes **158** and the transition mechanism **154**. In an alternative pre-embodiment, the transition mechanism **154** may include a light source and/or a vacuum source, eliminating the need to connect with a light carrier **156** and/or vacuum tube **158**. With reference to **FIG. 17**, a special connector **160** may interface between the transition mechanism **154** and the multi-lumen tube **140** to further transition the transition mechanism **154** into the multi-lumen tube **140**. However, it will be readily apparent to those skilled in the art how

transitioning devices such as the special connector **160** may be located within the transition mechanism **154**, eliminating the need for a special connector.

[0074] Together, the intraoral illumination device **122**, multi-lumen tube **140**, transition mechanism **154**, and light source form an intraoral illumination system and the intraoral illumination device **122** in conjunction with one or more of the following form an intraoral illumination kit: the multi-lumen tube **140**, the transition mechanism **154**, the light source, the vacuum source, the special connector **160**, and separate connector(s) for attaching light carrier **156** and/or vacuum tube **158** to the transition mechanism **154**.

[0075] The method of manufacturing the intraoral illumination device will now be described. The intraoral illumination device is manufactured in a two-step process known as multi-shot injection molding. The acrylic dispersion piece **124** is molded first in a two-piece mold including a first mold having a first mold cavity and a second mold having a second mold cavity, and, then, the second mold is removed. The second mold is replaced by a third mold having a third mold cavity that has the details of the tongue and cheek retractor **126**. Next, rubber is injected over the dispersion piece **124** to form the tongue and cheek retractor **126**. A gas-assist injection molding process is then used to produce the fluid evacuation channels and cavities within the tongue and cheek retractor **126**. Fluid evacuation holes are created in various locations of the tongue and cheek retractor **126** to provide specific area suction within a patient's mouth. The fluid evacuation holes may be created by a laser cutting process, or similar cutting process.

[0076] The multi-lumen tube **140** is extruded with the light tube **148** enclosed within the tube **140**. The light tube **148** is made from a semi-flexible, solid-core plastic, optical material such as a fiber optic bundle and is covered with a cladding such as Teflon before extrusion. With reference to FIG. 15, the multi-lumen tube **140** is extruded so as to have an elliptical shape with the light tube **148** in the center. The tube **140** is extruded so that a portion of the light tube **148** extends beyond the distal end of the multi-lumen tube **140**. After extrusion, the multi-lumen tube **140** is over-molded with a custom connector **150**. Alternatively, the connector **150** may be a separate piece made of a material such as stainless steel and fixed to the end of the tube **140**. The connector **150** is configured to inhibit leakage and ensure a tight connection with the connection section **138** of the intraoral illumination device **122**.

[0077] Thus, the intraoral illumination device of the present invention eliminates the problem of shadowing resulting from overhead light sources, single-point light sources, or other illumination sources of the past by transmitting dispersed light outwards from a rear, central part of the intraoral cavity, generally between the patient's rear teeth. The generally 180 degree arc of the dispersion piece spreads the area of illumination, eliminating shadows caused from a single point light source. The fluid evacuation system of the device vacuums oral fluids, water delivered by a dental hand piece, and debris. The fluid evacuation system prevents these fluids and debris from being aspirated or swallowed down the throat of the patient, improves the comfort of the patient, eliminates the need of the patient to continually rinse his or her mouth, and reduces the amount of spray emitted from the patient's mouth. The tongue and

cheek retractor retracts and protects the cheek and tongue of the patient, helping to reduce interference between these parts of the mouth and the procedure. The bite block allows the patient to rest the muscles of mastication, eliminating the need to strain to keep his or her mouth open. Because the device simultaneously removes fluids and debris, isolates the area of interest in the mouth, and illuminates the area of interest, the time of the procedure and the need for an assistant is greatly reduced.

[0078] With reference to FIG. 18A-19E, an intraoral illumination device (hereinafter "intraoral device") **200** constructed in accordance with another embodiment of the invention will now be described. The intraoral device **200** preferably has a single-piece, integrated, homogenous-material, injection-molded construction. The intraoral device **200** is preferably injection molded out of a translucent (e.g., transparent), flexible, soft, elastic, resilient, biocompatible thermoplastic elastomer. The intraoral device **200** is also vertically symmetrical so that an upper half **210** is symmetric with respect to a lower half **220**. This allows the same intraoral device **200** to be positioned on either the left side or the right side of the patient's mouth. The intraoral device **200** may also come in different sizes for different-size mouths. The intraoral device **200** is also disposable after each use.

[0079] The intraoral device **200** may be used with an optional vacuum-only adapter **230** if intraoral illumination is not desired with the intraoral device **200**. Further, in an alternative embodiment of the intraoral device **200**, the intraoral device **200** may not include the illumination aspects described in more detail below. In such an embodiment, the intraoral device **200** does not illuminate the patient's mouth.

[0080] The single-piece intraoral device **200** generally includes integrated tongue and cheek retractor **240**, bite piece **250**, and connection section **570**, each of which will be described in turn below.

[0081] The tongue and cheek retractor **240** has inner surfaces **260** and outer surfaces **270**. The retractor **240** includes an incurved main body portion **280** and a forwardly angled cheek retractor (or "whale tail") portion **290** joined by isthmus portion **300**.

[0082] The retractor **240** includes an upper front flap **310**, an upper rear flap **320**, a lower front flap **330**, and a lower rear flap **340**. The front flaps **310**, **330** and rear flaps **320**, **340** are separated by upper gap **350** and lower gap **360**, respectively. The flaps **320**, **330**, **340**, **350** all extend from and share a common, central spine **365**. The spine **365** extends longitudinally a majority of the length of the retractor **240** and divides the upper half **210** from the lower half **220** of the intraoral device **200**. In addition to serving as the intersection location for the flaps **320**, **330**, **340**, **350**, the spine **365** may serve as a light pipe and a separator for an upper internal evacuation channel and a lower internal evacuation channel. The upper front flap **310** and upper rear flap **320** include respective S-shaped upper edges or rims **370**, **380** and the lower front flap **330** and the lower rear flap **340** include respective s-shaped lower edges or rims **390**, **400**.

[0083] The flaps **310**, **320**, **330**, **340** include evacuation holes **410** adjacent the edges **370**, **380**, **390**, **400**. The evacuation holes **410** in the upper flaps **310**, **320** may be

generally aligned with each other and communicate with an upper internal evacuation channel formed in the upper gap **350** and the evacuation holes **410** in the lower flaps **330**, **340** are generally aligned with each other and communicate with a lower internal evacuation channel formed in the lower gap **360**. Although twenty evacuation holes **410** are shown, the number of evacuation holes **410** and/or location of the evacuation holes **410** may vary. The upper half **210** and/or the lower half **220** may include zero or more evacuation holes **410**. The number of evacuation holes **410** in the upper half **210** may be the same or different from the number of evacuation holes **410** in the lower half **220**. In an alternative embodiment, the evacuation holes may not be aligned with each other.

[0084] The upper front flap **310** and the upper rear flap **320** are configured to rest or flex against the palatal area or roof of the patient's mouth **36** during use. The upper roof of the mouth spans the upper gap **350** and pushes or bends the upper front flap **310** and the upper rear flap **320** forward to create a seal along the upper edges **370**, **380**, creating a sealed upper internal evacuation channel in the upper gap **350**. The lower front flap **330** and the lower rear flap **340** are configured to rest or flex against the lingual area of mouth or tongue to keep the tongue protected and retracted during use. The tongue and floor of the patient's mouth span the lower gap **360** and forms a seal along the lower edges **390**, **400**, creating a sealed lower internal evacuation channel in the lower gap **360**.

[0085] The cheek retractor portion **290** has an angled, curved, generally whale-tail shape. In use, the cheek retractor portion **290** is flexed inward towards the main body portion **280** and rests against the inner cheek tissue between the cheek tissue and the outside of the teeth. With the cheek retractor portion **290** flexed, the upper flaps **310**, **320** and lower flaps **330**, **340** are closed together, forming a seal along the upper edges **370**, **380** and the lower edges **390**, **400** of the retractor **240** adjacent where the isthmus portion **300** and cheek retractor portion **290** join. A front **420** and/or rear **430** of the cheek retractor portion **290** may include texturing, detail, or a varied composition to disperse light and prevent "hot spots" that can make it difficult for the health care provider to observe the patient's mouth, or lensing (e.g., fresnel lens) to focus light on different areas of the mouth.

[0086] With reference especially to FIGS. 19A and 19E, the cheek retractor portion **290** is shown as having a maximum height (or width) about $\frac{2}{3}$ the maximum height (or width) of the main body portion **280**. In alternative embodiments, the cheek retractor portion **290** may have smaller or larger maximum heights. For example, in an alternative embodiment, the cheek retractor portion **290** may have a whale-tail shape as shown, but with a maximum height or width substantially the same as the maximum height or width of the main body portion **280**.

[0087] When the tongue and cheek retractor **240** is positioned within the patient's mouth (similar to that shown in FIG. 1), the flexed upper flaps **310**, **320**, the flexed lower flaps **330**, **340**, and the flexed cheek retractor portion **290** form an envelope for isolating an area of interest in the patient's mouth and protect the upper roof, tongue and cheek of the patient's mouth from instruments such as dental drills during the dental procedure and prevent aspiration of debris or dropped items into the patient's throat.

[0088] The bite piece **250** includes symmetric, opposite tooth-engaging portions **440** joined by an intermediate connection portion **450**. The intermediate connection portion **450** is more flexible than the tooth engaging portions **440** and allows flexible, resilient, elastic movement of the tooth engaging portions **440** in vertical, longitudinal, and lateral directions with respect to each other to allow vertical, longitudinal, and lateral biting movement by the patient for maximum biting comfort. The bite piece **250** also may be moved or indexed forward and rearward a molar notch to allow for better or more comfortable posterior or anterior positioning of the bite piece **250** and intraoral device **200**.

[0089] The bite piece **250** allows 0-50% vertical compressibility (i.e., the bite piece **250** may be compressed vertically when a patient bites on it from 0% of the height of the bite piece **250** to as much as 50% of the height of the bite piece in a general vertical direction V shown in FIG. 19E). In a preferred embodiment, the bite piece **250** allows at least 5% vertical compressibility, in a more preferred embodiment, the bite piece **250** allows at least 10% compressibility, and in a most preferred embodiment, the bite piece **250** allows at least 15% vertical compressibility.

[0090] The bite piece **250** allows 0-75% longitudinal displacement (i.e., displacement of one tooth-engaging portion **440** 0-75% of the width of the tooth-engaging portion **440** relative to the opposite tooth engaging portion **440** in a general longitudinal direction Lo shown in FIG. 19C). In a preferred embodiment, the bite piece **250** allows at least 5% longitudinal displacement, in a more preferred embodiment, the bite piece **250** allows at least 10% longitudinal displacement, and in a most preferred embodiment, the bite piece **250** allows at least 15% longitudinal displacement of the tooth-engaging portions.

[0091] The bite piece **250** allows 0-20% lateral displacement (i.e., displacement of one tooth-engaging portion **440** 0-20% of the length of the tooth-engaging portion **440** relative to the opposite tooth engaging portion **440** in a general lateral direction L shown in FIG. 19C). In a preferred embodiment, the bite piece **250** allows at least 2% lateral displacement, in a more preferred embodiment, the bite piece **250** allows at least 4% lateral displacement, and in a most preferred embodiment, the bite piece **250** allows at least 6% lateral displacement of the tooth-engaging portions.

[0092] The intermediate connection portion **450** includes two opposite vertical walls **460**. Inner surfaces **470** of the two vertical walls **460**, inner surfaces **480** of the tooth engaging portions **440**, and an inner dividing wall **490** form a generally rectangular block-shaped suction cavity **500**. The inner dividing wall **490** includes a pair of vacuum holes **510** to allow a vacuum force to be provided in the cavity **500** for suctioning fluids in the area of the retro molar pad and the maxillary tuberosity of the patient's mouth. The tooth engaging portions **440** include parallel, generally laterally extending tooth-engaging ridges **520**. The tooth-engaging ridges **520** include vertically extending cylindrical chambers **530**. Disposed between the ridges **520** is a groove **540**. At the bottom of the groove **540** are two adjacent, vertically extending cross-shaped members **550**. Vertically extending dividers **560** are disposed at ends of the cross-shaped members **550**. The cross-shaped members **550** and the vertically extending dividers **560** are biting surfaces that

may be engaged by the bottom of the top teeth and the top of the bottom teeth to help keep the bite piece 250 in position.

[0093] The connection section 570 extends from the bite piece 250 and a proximal portion 580 of the retractor 240. The connection section 570 is configured to extend outside of a patient's mouth and attach to a multi-lumen tube for delivering illumination and vacuum suction to the intraoral device 200 (or the vacuum-only adapter 230 for delivering only vacuum suction to the intraoral device 200).

[0094] The connection section 570 includes an open-ended tube 590 having a generally elliptical cross-section that tapers slightly in height as the tube 590 intersects the bite piece 250 and the proximal portion 580 of the retractor 240. An interior of the open-ended tube 590 defines a main vacuum channel 595. Adjacent the bite piece 250 and the proximal portion 580 of the retractor 240, the connection section 570 includes a cylindrical tube-shaped illumination connector 600 for transmitting light to the spine 365 and for supporting the plug portion 640 or other plug. On opposite vertical sides of the illumination connector 600, where the illumination connector 600 joins the proximal portion 580 of the retractor 240, upper and lower vacuum ports 610, 620 communicate the main vacuum channel 595 with the upper and lower internal evacuation channels of the retractor 240. The main vacuum channel 595 communicates with the suction cavity 500 through the vacuum holes 510 in the inner dividing wall 490. The wall of the tube 590 includes a pair of adjacent, vertically spaced slots 630 for retaining corresponding retention barbs in the plug portion 640 of the vacuum-only adapter 230.

[0095] With reference to FIGS. 20A-20E, the vacuum-only adapter 230 will now be described in more detail. The adapter 230 includes a plug portion 640 and a handling portion 650.

[0096] The plug portion 640 includes a generally elliptical outer cross-section that is slightly smaller in dimension than the generally elliptical cross-section of the tube 590 so that the tube 590 may slidably receive the plug portion 640. A cylindrical plug 660 slightly smaller in dimension than the inner dimension of the illumination connector 600 extends from a distal end 670 of the adapter 230. The cylindrical plug 660 is matingly received by the illumination connector 600 when the plug portion 640 is plugged into the tube 590. The plug portion 640 includes a beveled surface 680 adjacent the distal end 670. When the plug portion 640 is plugged into the tube 590, the beveled surface 680 engages a corresponding angled surface within the connection section 570. Thus, the beveled surface 680 may be used to ensure that the adapter 230 is properly oriented when plugged into the connection section 570. With the plug portion 640 plugged into the connection section 570, the plug portion 640 helps to keep the bite piece 250 from collapsing in the front. A pair of barbs 690 extend from the plug portion 640 on a side opposite from the beveled surface 680. When the plug portion 640 is plugged into the tube 590, the barbs 690 engage the corresponding slots 630 in the connection section 570 to retain the adapter 230 in the connection section 570. A pair of vacuum lumens 700 extend longitudinally within the adapter 230, along the cylindrical plug 660. Near a proximal end 710 of the adapter 230, each vacuum lumen 700 may terminate in a receiver 720 for receiving cylindrical vacuum lines of a vacuum hose.

[0097] The handling portion 650 may have an overall dimension slightly larger than the dimension of the plug portion 640 and include opposite incurved sides 730 to facilitate handling of the handling portion 650 with one's fingers.

[0098] One or more further embodiments of the intraoral device may include one or more of the implementations described immediately below.

[0099] A separate plug, adapter, or tube having one or more LEDs may plug into the connection section of the intraoral device for illuminating the intraoral device.

[0100] The plug, adapter, or tube may include suitable electronics to control intensity of light from the one or more LEDs.

[0101] A slidable/movable filter may be employed with a separate curing light. The movable filter may be moved to a first position to filter out light that causes composite filling material to cure, preventing curing, and moved away from this position to allow light from the curing light to cure the composite filling material.

[0102] The plug, adapter, or tube may include a suction control mechanism that provides upper and lower evacuation channel control to control suction to the upper evacuation channel, the lower evacuation channel or both evacuation channels of the intraoral device.

[0103] The plug, adapter, or tube may include temperature control (e.g., through the use of one or more temperature sensors such as a thermistor) to turn off or turn down the one or more LEDs if the temperature in the region becomes too high. For example the one or more LEDs may be turned down to a lower intensity and heat level. When the one or more LEDs are sufficiently cooled to a desired temperature by the fluid cooling system described below, the one or more LEDs may be turned up to a higher intensity or normal level. In addition to or instead of lowering the one or more LEDs, the fluid cooling system may increase cooling (e.g., increase flow rate, decrease temperature level of cooling fluid) of the one or more LEDs if it is determined that the temperature in the region becomes too high.

[0104] A proximal end of the tubing used to deliver vacuum suction, electricity, and cooling fluid may include a plug-in hook up or connector to connect to vacuum, electricity, and water sources. Adjacent a proximal end of the tubing, an on/off switch may be located to actuate vacuum suction, electricity, and/or cooling fluid flow.

[0105] Using one or more LED's as the light source for the intraoral device in the manner described above eliminates the need for lengthy and heavy fiber optics and allows the tubing to drop 90 degrees from patient's mouth to the floor. This eliminates the leverage and pulling on the side of the patient's mouth caused by lengthy and heavy fiber optics in the past; fiber optics can't be bent at sharp 90 degree angles.

[0106] The plug, adapter, or tube may include a heat sink for removing heat emitted from the one or more LEDs. An example heat sink may include a fluid cooling system that circulates a cooling fluid (e.g., water) in the area of the one or more LEDs. For example, vacuum tubing that includes one or more vacuum lumens to remove fluid from the patient's mouth may also carry a cooling fluid delivery lumen for delivering cooling fluid to the region of the one or

more LEDs. After removing heat from the region of the one or more LEDs, the cooling fluid may be withdrawn through the one or more vacuum lumens. In another embodiment of the heat sink, which is also applicable to the heat sink device **800** described below, a thermostat or temperature control may be used with the heat sink fluid cooling system so that cooling may be automatically controlled. For example, but not by way of limitation, the flow rate of the cooling fluid through the fluid cooling system may be increased/decreased, the temperature of the cooling fluid may be increased/decreased, and/or the cooling fluid may be caused to circulate/recirculate through the heat sink and the fluid cooling system and withdrawn on an as-needed basis. The same or a different thermostat or temperature control may be used for controlling the intensity/heat level of the one or more LEDs as described further above.

[0107] For example, with reference to **FIGS. 21 and 22**, a combined illumination, aspiration and heat sink device (hereinafter heat sink device **800**) for use with an intraoral illumination device for providing the heat sink function (and other functions) will be described. The heat sink device **800** will be described as being used with the intraoral illumination device **200** described above with respect to **FIGS. 18A-19E**; however, the heat sink device **800** may be used with other intraoral illumination devices such as, but not limited to, the other intraoral illumination devices shown and described herein. Further, the heat sink device **800** may be used in applications where vacuum suction cooling of a heat-emitting illumination device is desired, other than for intraoral illumination and aspiration applications. Still further, the heat sink device **800** may be used for applications where a cooling fluid under positive pressure (not vacuum pressure) is used. Thus, in another embodiment of the heat sink device **800** and method described below, the cooling fluid is circulated and/or recirculated through the device **800** under positive pressure (not negative, vacuum pressure).

[0108] The heat sink device **800** includes an illumination and vacuum suction head **810**, a main body housing **820**, which houses a removable illumination stick **830**, a heat sink member **840**, and a valve body **850**, and a lower body housing **860**. The illumination and vacuum suction head **810**, the main body housing **820**, and the valve body **850** are made of an autoclavable hard plastic or metal material. Each of these elements will be described in turn below.

[0109] The illumination and vacuum suction head **810** includes a light pipe **870** and a plug housing **880**. The plug housing **880** houses the light pipe **870** and internal fluid channels (not shown). A plug portion **890** includes a generally cylindrical configuration with flat sidewalls **900**. The exposed end of the light pipe **870** is cylindrical and includes a slightly smaller dimension than the inner dimension of the illumination connector **600** (**FIG. 19A**) so as to be matingly received therein when the plug portion **890** is plugged into the tube **590**. A rear portion **910** of the head **810** is angled approximately 90 degrees from the plug portion **890**. The rear portion **910** includes a hole **915** that receives a head **930** of the removable illumination stick **830**.

[0110] The removable illumination stick **830** includes an elongated narrow body **920**, which is housed within the main body housing **820** and connected to the head **930**. The head **930** carries one or more illumination sources. In the embodiment shown, the illumination source is a single white LED

940. The LED **940** is bonded or soldered to a copper plate **950**, which is attached to a heat transfer plate **960** carried by the body **920**. The body **920** also carries suitable electronics for operating the LED **940**. The illumination stick **830** includes a touch pad resistor or mechanical switch on its rear side for controlling the intensity level of the LED **940**.

[0111] The heat sink member **840** includes an elliptical transfer plate heat sink **970**. The heat sink **970** includes a central hole **980** configured to receive and engage the body **920** and heat transfer plate **960** of the illumination stick **830**. Integrated with the heat sink **970** are cooling tubes **990**. Top ends of the cooling tubes **990** mate with the internal fluid channels of the illumination and vacuum suction head **810**. Fasteners **1000** may be used to fix the heat sink member **840** and the illumination stick **830** to the vacuum suction head **810** and the main body housing **820**. The heat sink member **840** and the illumination stick **830** may be removable for cleaning, sterilizing, and autoclaving.

[0112] The main body housing **820** is hollow and includes a slightly curved frustoconical configuration. The main body housing **820** houses the removable illumination stick **830**, the heat sink member **840**, and the valve body **850**. Valve handles **1010** are pivotally connected to the main body housing **820** and operably coupled with the valve body **850** for controlling flow therethrough. When the heat sink device **800** is in use, the valve handles **1010** are located adjacent the patient's mouth so that the patient can control suction of saliva from the patient's mouth. Movement of one of the valve handles **1010** controls suction through the upper internal evacuation channel of the intraoral illumination device **200** (**FIG. 19A**) and movement of the other valve handle **1010** controls suction through the lower internal evacuation channel of the intraoral illumination device **200**. Movement of one of the valve handles **1010** to an open position allows suction through the upper internal evacuation channel. Movement of the same valve handle **1010** to a closed position prevents suction through the upper internal evacuation channel. Controlling local suction in this manner is important for increasing patient comfort. Suction pulling across the teeth can result in pain and increased sensitivity. More local suction in the bottom of the patient's mouth, where it is needed most, eliminates uncomfortable suction across the patient's upper teeth when it is not needed. In dental offices with insufficient vacuum pressure, this also provides more local suction in the bottom of the patient's mouth, where it is needed most. Movement of the other valve handle **1010** to an open position allows suction through the lower internal evacuation channel. Movement of the same valve handle **1010** to a closed position prevents suction through the lower internal evacuation channel. Each valve handle **1010** may be opened, closed, or partially opened to provide extensive suction control in the intraoral illumination device **200**.

[0113] In the embodiment of the heat sink device **800** shown, upper and lower suction change relationship when the heat sink device **800** is used on the other side of the patient's mouth. The vacuum control handles **1010** change the off/on position from handles **1010** down/off to handles **1010** up/off because through holes are orientated at 45 degrees from the centerline of the handles **1010**.

[0114] The valve body **850** is generally cylindrical and includes an upper body portion **1020**, an annular flange

1030, and lower body portion **1040**. The upper body portion **1020** includes internal fluid channels **1050** that matingly receive the bottom ends of the cooling tubes **990**. The fluid channels **1050** communicate with valve chamber **1060**. Valve member(s) (not shown) are operably associated with the valve chamber **1060** and the valve handles **1010** for controlling suction through the internal evacuation channels of the intraoral illumination device **200** in the manner described above. Below the valve chamber **1060** is a single internal fluid chamber, which runs from the valve chamber **1060** to the bottom end of the lower body portion **1040**.

[0115] The lower body housing **860** is cylindrical and includes an annular recessed ledge **1070** at an upper end and a cylindrical vacuum tube **1080** at a lower end. Wires **1090**, which communicate a power source (not shown) with the electronics and LED **940** of the removable illumination stick **830** for powering the same, run inside the vacuum tube **1080**. The lower body portion **1040** of the valve body **850** mates with the cylindrical vacuum tube **1080**. The vacuum tube **1080** is in communication with a vacuum source (not shown) to provide vacuum suction for the heat sink device **800**. A commutator board **1100** is disposed between the recessed ledge **1070** and the annular flange **1030** of the valve body **850**. The commutator board **1100** includes two concentric circular tracks that radially offset spring probes **1110** extend upwardly through for electrically communicating wires **1090** with the commutator board **1100**. This configuration allows the lower body housing **860** to turn relative to the rest of the heat sink device **800** without putting the heat sink device **800** under torsional stress. The commutator board **1100** includes contact pins that a bottom of the illumination stick **830** is electrically coupled to.

[0116] Although not shown, in another embodiment of the invention, the heat sink device **800** may be controlled by a remote control and a wireless connection. The remote control may wirelessly communicate with the heat sink device **800** through a radio frequency (RF) link. The wireless link may include but not by way of limitation, a Blue Tooth link, an infrared link, and a wireless data network link. In alternative embodiments, the remote control may have a wired connection to the heat sink device **800**. In further embodiments, the heat sink device **800** is voice operated, or control features may be integrated with a dental chair or other dental equipment for controlling the heat sink device **800**. In the embodiment where the heat sink device **800** is controlled wirelessly through a RF remote control, the remote control may be pointed into or towards the patient's mouth for controlling, but not by way of limitation, the illumination level in the patient's mouth, the areas of aspiration in the patient's mouth, the amount or flow rate of aspiration, and/or the cooling/temperature level of the fluid cooling system and/or one or more LEDs.

[0117] The heat sink device **800** will now be described in use. The heat sink device **800** is connected to the intraoral illumination device **200** by plugging the plug portion **890** into the tube **590**. This causes the light pipe **870** to be plugged into the illumination connector **600**. This may be done before or after the intraoral illumination device **200** is inserted into the patient's mouth.

[0118] The vacuum source and the power source are activated. The vacuum source creates vacuum suction in the heat sink device **800**. This causes fluid and other debris to be

sucked from the patient's mouth, through the intraoral illumination device **200**, and into the heat sink device **800**. Movement of one of the valve handles **1010** to an open position allows suction through the upper internal evacuation channel; movement of the same valve handle **1010** to a closed position prevents suction through the upper internal evacuation channel; movement of the other valve handle **1010** to an open position allows suction through the lower internal evacuation channel; and movement of the same valve handle **1010** to a closed position prevents suction through the lower internal evacuation channel. Closing one valve handle **1010** and opening the other valve handle **1010** will create a greater suction force in the upper channel or lower channel than if both valve handles **1010** were open. Thus, each valve handle **1010** may be opened, closed, or partially opened to provide extensive suction control in the intraoral illumination device **200**.

[0119] The light level in the intraoral illumination device **200** is controlled by pressing the button or touch sensor on the rear of the main body housing **820**, over the touch pad resistor switch, one or more times. For example, pressing once may activate the LED **940** and set the LED **940** at a low intensity level. Pressing the rear of the main body housing **820** one or more additional times may cause the LED **940**, and, hence, the inside of the patient's mouth, to become increasingly brighter.

[0120] During use of the heat sink device **800**, heat is emitted by the LED **940**. This heat is transferred via the heat transfer plate **960** to the transfer plate heat sink **970** of the heat sink member **840**. The heat is then transferred via the cooling tubes **990** to the aspirated fluid flowing under negative pressure through the cooling tubes **990**. This negative pressure fluid is removed from the heat sink member **840** by the vacuum source. Thus, the heat sink device **800** utilizes the fluid suctioned out of the patient's mouth to remove heat from (and cool) the LED **940**.

[0121] To sterilize the heat sink device **800**, the heat sink device **800** is disassembled into the components shown in FIG. 22, the light stick **920** is removed so no aspirated fluid comes in contact with the light stick **920**, and the components of the heat sink device **800** are placed in an autoclave and sterilized.

[0122] In an alternative embodiment of the invention, the light stick **920** may be autoclaved together with the other components of the heat sink device **800** so that separation will not be necessary.

[0123] In a further embodiment of the invention, the heat sink device **800** is disposable. For example, the heat sink device **800** may be designed for single use (or a fixed number of uses), and then disposed of.

[0124] Although the heat sink device **800** is described above as including a removable illumination stick **830** with a white LED **940** as the one or more illumination sources for a general visibility application, in alternative embodiments of the invention, the removable illumination stick **830** may be replaced in the heat sink device **800** with different illumination sticks **830** with different LED's for performing different functions (e.g., bleaching, curing or oral diagnosis, and oral cancer screenings). Different illumination sticks **830** may have different wavelength illuminators, timing functions, and data logging functions. For example, but not

by way of limitation, another embodiment of a removable illumination stick **830** may include one or more blue LEDs (and/or one or more white LEDs) for curing and/or tooth whitening/bleaching applications. The same or a different illumination stick **830** may be used for transluminating teeth in the patient's mouth. Another illumination stick **830** may include an amber LED combined with a curing LED for non-curing safe light. For example, the curing LED could be used for curing while the other LED is off, and then the other LED could be used for non-curing safe light for general illumination while the curing LED is off. Also, the illumination stick **830** may include a single, multi-colored LED that is controlled to provide whatever light is needed for the application desired. For example, the single, multi-colored LED may be controlled to provide the light need for curing and then later controlled to provide the light needed for general illumination. The electronics (e.g., microprocessor) in the illumination stick **830** may control the time and other parameters of the illumination aspect of each application procedure. The heat sink device **800** includes data logging functions to collect usage data such as total time used and how long the device is used at a time. This data logging is helpful for trouble shooting any problems with the heat sink device **800**.

[0125] Although the illumination stick **830** is described as being replaceable, in alternative embodiments, the illumination stick **830** may be permanently attached in the heat sink device **800**.

[0126] Although this invention has been described in terms of certain preferred embodiments, other embodiments apparent to those of ordinary skill in the art are also within the scope of this invention. Accordingly, the scope of the invention is intended to be defined only by the claims that follow.

What is claimed is:

1. A method of using a heat sink device with an intraoral illumination device, the method comprising:

inserting an intraoral illumination device at least partially in a patient's mouth, the intraoral illumination device configured for illumination of and aspiration of fluid from the patient's mouth;

connecting a heat sink device to the intraoral illumination device, the heat sink device including an illumination device that emits light and heat when activated and a heat sink member thermally coupled to the illumination device;

activating the illumination device so that light is transmitted to the intraoral illumination device and into the patient's mouth, and heat is emitted from the illumination device,

aspirating fluid from the patient's mouth at negative pressure;

causing aspirated fluid to flow past the heat sink member at negative pressure so that heat is removed from the heat sink member, causing the illumination device to be cooled.

2. The method of claim 1, wherein the heat sink member includes an illumination and vacuum suction head with a light pipe that couples with the intraoral illumination device, connecting includes coupling the light pipe to the intraoral

illumination device, and the method further includes transmitting light from the illumination source to the illumination device through the light pipe.

3. The method of claim 1, wherein the heat sink member includes a removable illumination stick with the illumination device and electronics for operating the illumination device.

4. The method of claim 3, wherein the method includes using the illumination stick in the heat sink member for an intraoral application, replacing the illumination stick in the heat sink member with a different illumination stick for a different intraoral application, and using the different illumination stick in the same heat sink member for the different intraoral application.

5. The method of claim 3, wherein the illumination device of the illumination stick is one or more white LEDs and the electronics are configured for controlling the one or more white LEDs for a general visibility application, and the method includes using the illumination stick to illuminate the patient's mouth for improved general visibility.

6. The method of claim 3, wherein the illumination device of the illumination stick is one or more blue LEDs and the electronics are configured for controlling the one or more blue LEDs for a curing application, and the method includes using the illumination stick for curing material in the patient's mouth.

7. The method of claim 3, wherein the illumination device of the illumination stick is at least one of a blue LED and a white LED, and the electronics are configured for controlling the LED for teeth whitening, and the method includes using the illumination stick for whitening one or more of the patient's teeth.

8. The method of claim 3, wherein the illumination device of the illumination stick is one or more LEDs and the electronics are configured for controlling the one or more LEDs for tooth translumination, and the method includes using the illumination stick for transluminating one or more of the patient's teeth.

9. The method device of claim 1, wherein the intraoral illumination device includes a first fluid channel and a second fluid channel, and the heat sink device includes first lever for controlling aspiration flow through the first fluid channel and a second lever for controlling aspiration flow through the second fluid channel, and the method includes operating the first lever and the second lever for controlling aspiration flow through the first fluid channel and second fluid channel.

10. A method of using a heat sink with an intraoral illumination device, the method comprising:

providing a heat sink with one or more LEDs to illuminate the patients mouth through the intraoral illumination device, the one or more LEDs emitting heat when activated, the heat sink including a fluid delivery lumen for delivering aspirated cooling fluid under a vacuum condition in the region of the one or more LEDs;

removing heat from the region of the one or more LEDs by causing aspirated fluid under a vacuum condition to flow through the region of the one or more LEDs.

11. A heat sink device for use with an intraoral illumination device configured for illumination of and aspiration of fluid from the patient's mouth, comprising:

an illumination device configured to emit light and heat when activated;

a heat sink member thermally coupled to the illumination device and configured to receive aspirated fluid from the patient's mouth at negative pressure so that heat is removed from the heat sink member, causing the illumination device to be cooled.

12. The heat sink device of claim 11, wherein the heat sink member includes an illumination and vacuum suction head with a light pipe that couples with the intraoral illumination device for transmitting light from the illumination source to the illumination device.

13. The heat sink device of claim 11, wherein the heat sink member includes a removable illumination stick with the illumination device and electronics for operating the illumination device.

14. The heat sink device of claim 13, wherein the illumination device of the illumination stick is one or more white LEDs and the electronics are configured for controlling the one or more white LEDs for a general visibility application.

15. The heat sink device of claim 13, wherein the illumination device of the illumination stick is one or more blue

LEDs and the electronics are configured for controlling the one or more blue LEDs for a curing application.

16. The heat sink device of claim 13, wherein the illumination device of the illumination stick is at least one of a blue LED and a white LED and the electronics are configured for controlling the at least one LED for teeth whitening.

17. The heat sink device of claim 13, wherein the illumination device of the illumination stick is one or more LEDs and the electronics are configured for controlling the one or more LEDs for tooth translumination.

18. The heat sink device of claim 13, wherein the intraoral illumination device includes a first fluid channel and a second fluid channel, and the heat sink device includes first lever for controlling aspiration flow through the first fluid channel and a second lever for controlling aspiration flow through the second fluid channel.

* * * * *