

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Inventors: Edwin S. Olson et al.

Title: SORBENTS FOR THE OXIDATION AND REMOVAL OF MERCURY

Attorney Docket No.: 4820.001US10

Customer No.: 21186

PATENT APPLICATION TRANSMITTAL

Commissioner for Patents

P.O. Box 1450

Alexandria, VA 22313-1450

We are transmitting herewith the following attached items and information (as indicated with an "X"):

X **CONTINUATION under 37 CFR 1.53(b) of prior Patent Application No. 15/974,343 comprising:**

X Application Data Sheet (8 pgs).

X Copy of signed Declaration from prior application (3 pgs).

X Specification (61 pgs, including claims numbered 1 through 20 and a 1 page Abstract).

X Formal Drawings (11 sheets).

X Certification and Request for Prioritized Examination (Track 1) (1 pg), including authorization to charge Deposit Account 19-0743 in the amount of \$4000.00 for the Prioritized Examination (Track 1) filing fee as set forth in 37 C.F.R. § 1.17(c); and Authorization to charge Deposit Account 19-0743 for the Processing Fee (Track 1) set forth in 37 C.F.R. § 1.17(i) in the amount of \$140.00.

X Authorization to charge Deposit Account 19-0743 in the amount of \$5,860.00

The filing fee has been calculated below as follows:

	No. Filed	No. Extra	Rate	Fee
TOTAL CLAIMS	20 - 20	0	x \$100.00 =	\$0.00
INDEPENDENT CLAIMS	1 - 3	0	x \$460.00 =	\$0.00
[] MULTIPLE DEPENDENT CLAIMS PRESENTED				\$0.00
BASIC FEE				\$300.00
SEARCH FEE				\$660.00
EXAMINATION FEE				\$760.00
PRIORITIZED EXAMINATION (TRACK 1) FILING FEE				\$4,000.00
PROCESSING FEE (TRACK 1)				\$140.00
	No. of pages (75% fore-filing)	Extra sets of 50 pages	Rate	
APPLICATION SIZE FEE	(54 - 100) / 50	0	\$400.00	\$0.00
TOTAL				\$5,860.00

Please charge any additional required fees or credit overpayment to Deposit Account No. 19-0743. If applicable, any papers or fees supplied herewith are considered to be timely filed pursuant to 37 C.F.R. § 1.7(a), the response period falling on a Federal Holiday, Saturday or Sunday being extended to the next succeeding business day.

SCHWEGMAN LUNDBERG & WOESSNER, P.A.

Customer Number: 21186

By Nicholas P. Lanzatella
Nicholas P. Lanzatella
Reg. No. 63,803

Date of Deposit: June 4, 2018

This paper or fee is being filed on the date indicated above using the USPTO's electronic filing system EFS-Web, and is addressed to The Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

Application Data Sheet 37 CFR 1.76	Attorney Docket Number	4820.001US10
	Application Number	Unknown
Title of Invention	SORBENTS FOR THE OXIDATION AND REMOVAL OF MERCURY	

The application data sheet is part of the provisional or nonprovisional application for which it is being submitted. The following form contains the bibliographic data arranged in a format specified by the United States Patent and Trademark Office as outlined in 37 CFR 1.76.
 This document may be completed electronically and submitted to the Office in electronic format using the Electronic Filing System (EFS) or the document may be printed and included in a paper filed application.

Secrecy Order 37 CFR 5.2:

☐ Portions or all of the application associated with this Application Data Sheet may fall under a Secrecy Order pursuant to 37 CFR 5.2 (Paper filers only. Applications that fall under Secrecy Order may not be filed electronically.)

Inventor Information:

Inventor 1: Edwin S. Olson				
Legal Name				
Prefix	Given Name	Middle Name	Family Name	Suffix
	Edwin	S.	Olson	
Residence Information (Select One)				
☒ US Residency ☐ Non US Residency ☐ Active US Military Service				
City	Grand Forks	State/Province	ND	Country of Residence United States of America
Mailing Address of Inventor:				
Address 1	223 Circle Hills Drive			
Address 2				
City	Grand Forks	State/Province	ND	
Postal Code	58201	Country	United States of America	
Inventor 2: Michael J. Holmes				
Legal Name				
Prefix	Given Name	Middle Name	Family Name	Suffix
	Michael	J.	Holmes	
Residence Information (Select One)				
☒ US Residency ☐ Non US Residency ☐ Active US Military Service				
City	Thompson	State/Province	ND	Country of Residence United States of America
Mailing Address of Inventor:				
Address 1	614 6th Avenue Northeast			
Address 2				
City	Thompson	State/Province	ND	
Postal Code	58278	Country	United States of America	

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

Application Data Sheet 37 CFR 1.76	Attorney Docket Number	4820.001US10
	Application Number	Unknown
Title of Invention	SORBENTS FOR THE OXIDATION AND REMOVAL OF MERCURY	
<p>The application data sheet is part of the provisional or nonprovisional application for which it is being submitted. The following form contains the bibliographic data arranged in a format specified by the United States Patent and Trademark Office as outlined in 37 CFR 1.76.</p> <p>This document may be completed electronically and submitted to the Office in electronic format using the Electronic Filing System (EFS) or the document may be printed and included in a paper filed application.</p>		

Inventor 3: John H. Pavlish				
Legal Name				
Prefix	Given Name	Middle Name	Family Name	Suffix
	John	H.	Pavlish	
Residence Information (Select One)				
☒ US Residency ☐ Non US Residency ☐ Active US Military Service				
City	East Grand Forks	State/Province	MN	Country of Residence United States of America
Mailing Address of Inventor:				
Address 1	42204 210th Street SW			
Address 2				
City	East Grand Forks	State/Province	MN	
Postal Code	56721	Country	United States of America	

Correspondence Information:

Enter either Customer Number or complete the Correspondence Information section below.
 For further information see 37 CFR 1.33(a).

☐ An Address is being provided for the correspondence information of this application.	
Customer Number	21186
Email Address	request@slwip.com

Application Information:

Title of the Invention	SORBENTS FOR THE OXIDATION AND REMOVAL OF MERCURY		
Attorney Docket Number	4820.001US10	Small Entity Status Claimed ☐	
Application Type	Non-Provisional		
Subject Matter	Utility		
Suggested Class (if any)		Sub Class (if any)	
Suggested Technology Center (if any)			
Total Number of Drawing Sheets (if any)	11	Suggested Figure for Publication (if any)	

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

Application Data Sheet 37 CFR 1.76	Attorney Docket Number	4820.001US10
	Application Number	Unknown
Title of Invention	SORBENTS FOR THE OXIDATION AND REMOVAL OF MERCURY	
<p>The application data sheet is part of the provisional or nonprovisional application for which it is being submitted. The following form contains the bibliographic data arranged in a format specified by the United States Patent and Trademark Office as outlined in 37 CFR 1.76.</p> <p>This document may be completed electronically and submitted to the Office in electronic format using the Electronic Filing System (EFS) or the document may be printed and included in a paper filed application.</p>		

Filing By Reference:

<p>Only complete this section when filing an application by reference under 35 U.S.C. 111(c) and 37 CFR 1.57(a). Do not complete this section if application papers including a specification and any drawings are being filed. Any domestic benefit or foreign priority information must be provided in the appropriate section(s) below (i.e., "Domestic Benefit/National Stage Information" and "Foreign Priority Information").</p> <p>For the purposes of a filing date under 37 CFR 1.53(b), the description and any drawings of the present application are replaced by this reference to the previously filed application, subject to conditions and requirements of 37 CFR 1.57(a).</p>		
Application number of the previously filed application	Filing date (YYYY-MM-DD)	Intellectual Property Authority or Country Publication

Publication Information:

☐ Request Early Publication (Fee required at time of Request 37 CFR 1.219)
☐ Request Not to Publish. I hereby request that the attached application not be published under 35 U.S.C. 122(b) and certify that the invention disclosed in the attached application has not and will not be the subject of an application filed in another country, or under a multilateral international agreement, that requires publication at eighteen months after filing.

Representative Information:

<p>Representative information should be provided for all practitioners having a power of attorney in the application. Providing this information in the Application Data Sheet does not constitute a power of attorney in the application (see 37 CFR 1.32). Enter either Customer Number or complete the Representative Name section below. If both sections are completed the Customer Number will be used for the Representative Information during processing.</p>			
Please Select One:	☒ Customer	☐ US Patent Practitioner	☐ Limited Recognition (37 CFR 11.9)
Customer Number	21186		

Application Data Sheet 37 CFR 1.76	Attorney Docket Number	4820.001US10
	Application Number	Unknown
Title of Invention	SORBENTS FOR THE OXIDATION AND REMOVAL OF MERCURY	

The application data sheet is part of the provisional or nonprovisional application for which it is being submitted. The following form contains the bibliographic data arranged in a format specified by the United States Patent and Trademark Office as outlined in 37 CFR 1.76.

This document may be completed electronically and submitted to the Office in electronic format using the Electronic Filing System (EFS) or the document may be printed and included in a paper filed application.

Domestic Benefit/National Stage Information:

This section allows for the applicant to either claim benefit under 35 U.S.C. 119(e), 120, 121, or 365(c) or indicate National Stage entry from a PCT application. Providing this information in the application data sheet constitutes the specific reference required by 35 U.S.C. 119(e) or 120, and 37 CFR 1.78(a)(2) or CFR 1.78(a)(4), and need not otherwise be made part of the specification.

Prior Application Status	Pending		
Application Number	Continuity Type	Prior Application Number	Filing or 371(c) Date (YYYY-MM-DD)
This application	continuation of	15/974,343	2018-05-08
Prior Application Status	Pending		
Application Number	Continuity Type	Prior Application Number	Filing or 371(c) Date (YYYY-MM-DD)
15/974,343	continuation of	15/951,970	2018-04-12
Prior Application Status	Pending		
Application Number	Continuity Type	Prior Application Number	Filing or 371(c) Date (YYYY-MM-DD)
15/951,970	continuation of	14/712,558	2015-05-14
Prior Application Status	Patented		
Application Number	Continuity Type	Prior Application Number	Filing or 371(c) Date (YYYY-MM-DD)
14/712,558	continuation of	14/318,270	2014-06-27
Prior Application Status	Patented		
Application Number	Continuity Type	Prior Application Number	Filing or 371(c) Date (YYYY-MM-DD)
14/318,270	continuation of	13/966,768	2013-08-14
Prior Application Status	Patented		
Application Number	Continuity Type	Prior Application Number	Filing or 371(c) Date (YYYY-MM-DD)
13/966,768	continuation of	13/427,665	2012-03-22
Prior Application Status	Patented		
Application Number	Continuity Type	Prior Application Number	Filing or 371(c) Date (YYYY-MM-DD)
13/427,665	continuation of	12/419,219	2009-04-06

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

Application Data Sheet 37 CFR 1.76	Attorney Docket Number	4820.001US10
	Application Number	Unknown
Title of Invention	SORBENTS FOR THE OXIDATION AND REMOVAL OF MERCURY	
<p>The application data sheet is part of the provisional or nonprovisional application for which it is being submitted. The following form contains the bibliographic data arranged in a format specified by the United States Patent and Trademark Office as outlined in 37 CFR 1.76.</p> <p>This document may be completed electronically and submitted to the Office in electronic format using the Electronic Filing System (EFS) or the document may be printed and included in a paper filed application.</p>		

Prior Application Status	Abandoned		
Application Number	Continuity Type	Prior Application Number	Filing or 371(c) Date (YYYY-MM-DD)
12/419,219	continuation of	12/201,595	2008-08-29
Prior Application Status	Patented		
Application Number	Continuity Type	Prior Application Number	Filing or 371(c) Date (YYYY-MM-DD)
12/201,595	division of	11/209,163	2005-08-22
Prior Application Status	Expired		
Application Number	Continuity Type	Prior Application Number	Filing or 371(c) Date (YYYY-MM-DD)
11/209,163	Claims benefit of provisional	60/605,640	2004-08-30

Foreign Priority Information:

<p>This section allows for the applicant to claim priority to a foreign application. Providing this information in the application data sheet constitutes the claim for priority as required by 35 U.S.C. 119(b) and 37 CFR 1.55(d). When priority is claimed to a foreign application that is eligible for retrieval under the priority document exchange program (PDX) the information will be used by the Office to automatically attempt retrieval pursuant to 37 CFR 1.55(h)(1) and (2). Under the POX program, applicant bears the ultimate responsibility for ensuring that a copy of the foreign application is received by the Office from the participating foreign intellectual property office, or a certified copy of the foreign priority application is filed, within the time period specified in 37 CFR 1.55(g)(1).</p>			
Application Number	Country	Parent Filing Date (YYYY-MM-DD)	Access Code (if applicable)

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

Application Data Sheet 37 CFR 1.76	Attorney Docket Number	4820.001US10
	Application Number	Unknown
Title of Invention	SORBENTS FOR THE OXIDATION AND REMOVAL OF MERCURY	
<p>The application data sheet is part of the provisional or nonprovisional application for which it is being submitted. The following form contains the bibliographic data arranged in a format specified by the United States Patent and Trademark Office as outlined in 37 CFR 1.76.</p> <p>This document may be completed electronically and submitted to the Office in electronic format using the Electronic Filing System (EFS) or the document may be printed and included in a paper filed application.</p>		

Authorization or Opt-Out of Authorization to Permit Access:

When this Application Data Sheet is properly signed and filed with the application, applicant has provided written authority to permit a participating foreign intellectual property (IP) office access to the instant application-as-filed (see paragraph A in subsection 1 below) and the European Patent Office (EPO) access to any search results from the instant application (see paragraph B in subsection 1 below).

Should applicant choose not to provide an authorization identified in subsection 1 below, applicant must opt-out of the authorization by checking the corresponding box A or B or both in subsection 2 below.

NOTE: This section of the Application Data Sheet is ONLY reviewed and processed with the INITIAL filing of an application. After the initial filing of an application, an Application Data Sheet cannot be used to provide or rescind authorization for access by a foreign IP office(s). Instead, Form PTO/SB/39 or PTO/SB/69 must be used as appropriate.

1. Authorization to Permit Access by a Foreign Intellectual Property Office(s)

A. Priority Document Exchange (PDX) - Unless box A in subsection 2 (opt-out of authorization) is checked, the undersigned hereby grants the USPTO authority to provide the European Patent Office (EPO), the Japan Patent Office (JPO), the Korean Intellectual Property Office (KIPO), the State Intellectual Property Office of the People's Republic of China (SIPO), the World Intellectual Property Organization (WIPO), and any other foreign intellectual property office participating with the USPTO in a bilateral or multilateral priority document exchange agreement in which a foreign application claiming priority to the instant patent application is filed, access to: (1) the instant patent application-as-filed and its related bibliographic data, (2) any foreign or domestic application to which priority or benefit is claimed by the instant application and its related bibliographic data, and (3) the date of filing of this Authorization. See 37 CFR 1.14(h) (1).

B. Search Results from U.S. Application to EPO - Unless box B in subsection 2 (opt-out of authorization) is checked, the undersigned hereby grants the USPTO authority to provide the EPO access to the bibliographic data and search results from the instant patent application when a European patent application claiming priority to the instant patent application is filed. See 37 CFR 1.14(h)(2).

The applicant is reminded that the EPO's Rule 141(1) EPC (European Patent Convention) requires applicants to submit a copy of search results from the instant application without delay in a European patent application that claims priority to the instant application.

2. Opt-Out of Authorizations to Permit Access by a Foreign Intellectual Property Office(s)

- A. Applicant DOES NOT authorize the USPTO to permit a participating foreign IP office access to the instant ☐ application-as-filed. If this box is checked, the USPTO will not be providing a participating foreign IP office with any documents and information identified in subsection 1A above.
- ☐ B. Applicant DOES NOT authorize the USPTO to transmit to the EPO any search results from the instant patent application. If this box is checked, the USPTO will not be providing the EPO with search results from the instant application.

NOTE: Once the application has published or is otherwise publicly available, the USPTO may provide access to the application in accordance with 37 CFR 1.14.

Application Data Sheet 37 CFR 1.76	Attorney Docket Number	4820.001US10
	Application Number	Unknown
Title of Invention	SORBENTS FOR THE OXIDATION AND REMOVAL OF MERCURY	
<p>The application data sheet is part of the provisional or nonprovisional application for which it is being submitted. The following form contains the bibliographic data arranged in a format specified by the United States Patent and Trademark Office as outlined in 37 CFR 1.76.</p> <p>This document may be completed electronically and submitted to the Office in electronic format using the Electronic Filing System (EFS) or the document may be printed and included in a paper filed application.</p>		

Applicant Information:

<p>Providing assignment information in this section does not substitute for compliance with any requirement of part 3 of Title 37 of CFR to have an assignment recorded by the Office.</p>				
<p>Applicant: Midwest Energy Emissions Corp</p>				
<p><u>If the applicant is the inventor (or the remaining joint inventor or inventors under 37 CFR 1.45), this section should not be completed.</u> The information to be provided in this section is the name and address of the legal representative who is the applicant under 37 CFR 1.43; or the name and address of the assignee, person to whom the inventor is under an obligation to assign the invention, or person who otherwise shows sufficient proprietary interest in the matter who is the applicant under 37 CFR 1.46. If the applicant is an applicant under 37 CFR 1.46 (assignee, person to whom the inventor is obligated to assign, or person who otherwise shows sufficient proprietary interest) together with one or more joint inventors, then the joint inventor or inventors who are also the applicant should be identified in this section.</p>				
☒ Assignee		☐ Legal Representative under 35 U.S.C. 117		☐ Joint Inventor
☐ Person to whom the inventor is obligated to assign		☐ Person who shows sufficient proprietary interest		
<p>If applicant is the legal representative, indicate the authority to file the patent application, the inventor is:</p>				
☐ Deceased		☐ Legally incapacitated		
<p>Name of the Deceased or Legally Incapacitated Inventor :</p>				
<p>If the Applicant is an Organization check here: ☒</p>				
<p>Organization Name: Midwest Energy Emissions Corp</p>				
Prefix	Given Name	Middle Name	Family Name	Suffix
<p>Mailing Address Information:</p>				
Address 1	670 D Enterprise Dr			
Address 2				
City	Lewis Center	State/Province	OH	
Country	United States of America	Postal Code	43035	
Phone Number				
Email Address				


Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

Application Data Sheet 37 CFR 1.76	Attorney Docket Number	4820.001US10
	Application Number	Unknown
Title of Invention	SORBENTS FOR THE OXIDATION AND REMOVAL OF MERCURY	
<p>The application data sheet is part of the provisional or nonprovisional application for which it is being submitted. The following form contains the bibliographic data arranged in a format specified by the United States Patent and Trademark Office as outlined in 37 CFR 1.76.</p> <p>This document may be completed electronically and submitted to the Office in electronic format using the Electronic Filing System (EFS) or the document may be printed and included in a paper filed application.</p>		

Assignee Information including Non-Applicant Assignee Information:

<p>Providing assignment information in this section does not substitute for compliance with any requirement of part 3 of Title 37 of CFR to have an assignment recorded by the Office.</p>				
<p>Complete this section if assignee information, including non-applicant assignee information, is desired to be included on the patent application publication. An assignee-applicant identified in the "Applicant Information" section will appear on the patent application publication as an applicant. For an assignee-applicant, complete this section only if identification as an assignee is also desired on the patent application publication.</p>				
<p>If the Assignee or Non-Applicant Assignee is an Organization check here. ☐</p>				
Prefix	Given Name	Middle Name	Family Name	Suffix
Mailing Address Information For Assignee including Non-Applicant Assignee:				
Address 1				
Address 2				
City		State/Province		
Country		Postal Code		
Phone Number		Fax Number		
Email Address				

Signature:

<p>NOTE: This Application Data Sheet must be signed in accordance with 37 CFR 1.33(b). However, if this Application Data Sheet is submitted with the <u>INITIAL</u> filing of the application and either box A or B is <u>not</u> checked in subsection 2 of the "Authorization or Opt-Out of Authorization to Permit Access" section, then this form must also be signed in accordance with 37 CFR 1.14(c).</p> <p>This Application Data Sheet must be signed by a patent practitioner if one or more of the applicants is a juristic entity (e.g., corporation or association). If the applicant is two or more joint inventors, this form must be signed by a patent practitioner, <u>all</u> joint inventors who are the applicant, or one or more joint inventor-applicants who have been given power of attorney (e.g., see USPTO Form PTO/AIA/81) on behalf of <u>all</u> joint inventor-applicants.</p> <p>See 37 CFR 1.4(d) for the manner of making signatures and certifications.</p>					
Signature			Date (YYYY-MM-DD)	2018-06-04	
First Name	Nicholas	Last Name	Lanzatella	Registration Number	63,803

This collection of information is required by 37 CFR 1.76. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 23 minutes to complete, including gathering, preparing, and submitting the completed application data sheet form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-14**

**DECLARATION (37 CFR 1.63) FOR UTILITY OR DESIGN APPLICATION USING AN
APPLICATION DATA SHEET (37 CFR 1.76)**

Title of Invention	SORBENTS FOR THE OXIDATION AND REMOVAL OF MERCURY
As the below named inventor, I hereby declare that: This declaration is directed to: ☐ The attached application, or ☒ United States application or PCT international application number <u>13/966,768</u> , filed on <u>August 14, 2013</u> . The above-identified application was made or authorized to be made by me. I believe that I am the original inventor or an original joint inventor of a claimed invention in the application. I hereby acknowledge that any willful false statement made in this declaration is punishable under 18 U.S.C. 1001 by fine or imprisonment of not more than (5) years, or both. WARNING: Petitioner/applicant is cautioned to avoid submitting personal information in documents filed in a patent application that may contribute to identity theft. Personal information such as social security numbers, bank account numbers, or credit card numbers (other than a check or credit card authorization form PTO-2038 submitted for payment purposes) is never required by the USPTO to support a petition or an application. If this type of personal information is included in documents submitted to the USPTO, petitioners/applicants should consider redacting such personal information from the documents before submitting them to the USPTO. Petitioner/applicant is advised that the record of a patent application is available to the public after publication of the application (unless a non-publication request in compliance with 37 CFR 1.213(a) is made in the application) or issuance of a patent. Furthermore, the record from an abandoned application may also be available to the public if the application is referenced in a published application or an issued patent (see 37 CFR 1.14). Checks and credit card authorization forms PTO-2038 submitted for payment purposes are not retained in the application file and therefore are not publicly available. LEGAL NAME OF INVENTOR Inventor: <u>Edwin S. Olson</u> Date (Optional): _____ Signature: <u></u> Note: An application data sheet (PTO/SB/14 or equivalent), including naming the entire inventive entity, must accompany this form. Use an additional PTO/AIA/01 form for each additional inventor.	

This collection of information is required by 35 U.S.C. 111 and 37 CFR 1.63. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.11 and 1.14. This collection is estimated to take 1 minute to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 5470, Alexandria, VA 22315-1450. DO NOT SEND FILLS OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22312-1450.

If you need assistance in completing this form, call 1-800-PTO-9199 and select option 2.

3332.005US55

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

DECLARATION (37 CFR 1.63) FOR UTILITY OR DESIGN APPLICATION USING AN APPLICATION DATA SHEET (37 CFR 1.76)

Title of Invention	SORBENTS FOR THE OXIDATION AND REMOVAL OF MERCURY
--------------------	---

As the below named inventor, I hereby declare that:

This declaration is directed to: ☐ The attached application, or

☒ United States application or PCT international application number 13/956,768, filed on August 14, 2013.

The above identified application was made or authorized to be made by me.

I believe that I am the original inventor or an original joint inventor of a claimed invention in the application.

I hereby acknowledge that any willful false statement made in this declaration is punishable under 18 U.S.C. 1071 by fine or imprisonment of not more than (5) years, or both.

WARNING:

Petitioner/applicant is cautioned to avoid submitting personal information in documents filed in a patent application that may contribute to identity theft. Personal information such as social security numbers, bank account numbers, or credit card numbers (other than a check or credit card authorization form PTO-2038 submitted for payment purposes) is never required by the USPTO to support a petition or an application. If this type of personal information is included in documents submitted to the USPTO, petitioners/applicants should consider redacting such personal information from the documents before submitting them to the USPTO. Petitioner/applicants are advised that the record of a patent application is available to the public after publication of the application (unless a non-publication request in compliance with 37 CFR 1.213(a) is made in the application) or issuance of a patent. Furthermore, the record from an abandoned application may also be available to the public if the application is referenced in a published application or an issued patent (see 37 CFR 1.14). Checks and credit card authorization forms PTO-2038 submitted for payment purposes are not retained in the application file and therefore are not publicly available.

LEGAL NAME OF INVENTOR

Inventor: Michael J. Holmes Date (Optional): Oct. 28, 2013

Signature: [Handwritten Signature]

Note: An application data sheet (PTO/SF/14 or equivalent) including naming the entire inventive entity, must accompany this form. Use an additional PTO/AIA/01 form for each additional inventor.

This collection of information is required by 35 U.S.C. 115 and 37 CFR 1.17. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is guaranteed by 35 U.S.C. 122 and 37 CFR 1.11 and 1.14. This collection is estimated to take 1 minute to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual's use. Any comments on the amount of time you require to complete this form or suggestions for reducing this burden should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND PREVIOUS COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

If you need assistance in completing this form, call 1-800-PTO-4177 and select option 2.

3399.005US3

**DECLARATION (37 CFR 1.63) FOR UTILITY OR DESIGN APPLICATION USING AN
APPLICATION DATA SHEET (37 CFR 1.76)**

Title of
Invention:

SORBENTS FOR THE OXIDATION AND REMOVAL OF MERCURY

As the below named inventor, I hereby declare that:

This declaration

is directed to:

☐ The attached application, or

☒ United States application or PCT International application number 13/366,768,
filed on August 14, 2013.

The above-identified application was made or authorized to be made by me.

I believe that I am the original inventor or an original joint inventor of a claimed invention in the application.

I hereby acknowledge that any willful false statement made in this declaration is punishable under 18 U.S.C. 1001
by fine or imprisonment of not more than (5) years, or both.

WARNING:

Petitioner/applicant is cautioned to avoid submitting personal information in documents filed in a patent application that may contribute to identity theft. Personal information such as social security numbers, bank account numbers, or credit card numbers (other than a check or credit card authorization form PTO-2038 submitted for payment purposes) is never required by the USPTO to support a petition or an application. If this type of personal information is included in documents submitted to the USPTO, petitioners/applicants should consider redacting such personal information from the documents before submitting them to the USPTO. Petitioner/applicant is advised that the record of a patent application is available to the public after publication of the application (unless a non-publication request in compliance with 37 CFR 1.213(a) is made in the application) or issuance of a patent. Furthermore, the record from an abandoned application may also be available to the public if the application is referenced in a published application or an issued patent (see 37 CFR 1.14). Checks and credit card authorization forms PTO-2038 submitted for payment purposes are not retained in the application file and therefore are not publicly available.

LEGAL NAME OF INVENTOR

Inventor: John Henry Pavlish

Date (Optional): _____

Signature: John Pavlish

Note: An application data sheet (PTO/58/1A or equivalent), including naming the entire inventive entity, must accompany this form. Use an additional PTO/AIA/01 form for each additional inventor.

This collection of information is required by 35 U.S.C. 115 and 37 CFR 1.60. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 132 and 37 CFR 1.11 and 1.14. This collection is estimated to take 1 minute to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FILES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

If you need assistance in completing this form, call 1-800-PTO-9199 and select option 2.


3338/00SLSS

CERTIFICATION AND REQUEST FOR PRIORITIZED EXAMINATION UNDER 37 CFR 1.102(e)
(Page 1 of 1)

First Named Inventor:	Edwin S. Olson	Nonprovisional Application Number (if known):	Unknown
Title of Invention:	SORBENTS FOR THE OXIDATION AND REMOVAL OF MERCURY	Docket No.:	4820.001US10

APPLICANT HEREBY CERTIFIES THE FOLLOWING AND REQUESTS PRIORITIZED EXAMINATION FOR THE ABOVE-IDENTIFIED APPLICATION.

1. The processing fee set forth in 37 CFR 1.17(i)(1) and the prioritized examination fee set forth in 37 CFR 1.17(c) have been filed with the request. The publication fee requirement is met because that fee, set forth in 37 CFR 1.18(d), is currently \$0. The basic filing fee, search fee, and examination fee are filed with the request or have been already been paid. I understand that any required excess claims fees or application size fee must be paid for the application.
2. I understand that the application may not contain, or be amended to contain, more than four independent claims, more than thirty total claims, or any multiple dependent claims, and that any request for an extension of time will cause an outstanding Track I request to be dismissed.
3. **Original Application(Track One) – Prioritized Examination under § 1.102(e)(1)**
 - i. (a) The application is an original nonprovisional utility application filed under 35 U.S.C. 111(a). This certification and request is being filed with the utility application via EFS-Web.
---OR---
(b) The application is an original nonprovisional plant application filed under 35 U.S.C. 111(a). This certification and request is being filed with the plant application in paper.
 - ii. An executed inventor's oath or declaration under 37 CFR 1.63 or 37 CFR 1.64 for each inventor, or the application data sheet meeting the conditions specified in 37 CFR 1.53(f)(3)(i) is filed with the application.

Signature: 	Date: June 4, 2018
Name: (Print/Typed) Nicholas P. Lanzatella	Practitioner: Registration Number: 63,803
Note: This form must be signed in accordance with 37 CFR 1.33. See 37 CFR 1.4(d) for signature requirements and certifications. Submit multiple forms if more than one signature is required, see below*.	
*Total of <u>1</u> forms are submitted.	

SORBENTS FOR THE OXIDATION AND REMOVAL OF MERCURY

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. Patent Application Serial No. 15/974,343, filed May 8, 2018, which is a continuation of U.S. Patent Application Serial No. 15/951,970, filed April 12, 2018, which is a continuation of U.S. Patent Application Serial No. 14/712,558, filed May 14, 2015, which is a continuation of U.S. Patent Application Serial No. 14/318,270, filed June 27, 2014, which is a continuation of U.S. Patent Application Serial No. 13/966,768, filed August 14, 2013, issued as U.S. Patent No. 8,821,819, which is a continuation of U.S. Patent Application Serial No. 13/427,665, filed March 22, 2012, issued as U.S. Patent No. 8,512,655, which is a continuation of U.S. Patent Application Serial No. 12/419,219, filed April 06, 2009, issued as U.S. Patent No. 8,168,147, which is a continuation of U.S. Patent Application Serial No. 12/201,595, filed August 29, 2008, which is a division of U.S. Patent Application Serial No. 11/209,163, filed August 22, 2005, issued as U.S. Patent No. 7,435,286, which application claims the benefit under 35 U.S.C. § 119 (e) of U.S. Provisional Patent Application No. 60/605,640 filed Aug. 30, 2004, the disclosure of which is hereby incorporated by reference in its entirety.

STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT

This invention was made with United States Government support under Grant Numbers R 827649-01 and CR 830929-01 awarded by the United States Environmental Protection Agency and under Contract Number DE-FC26-98FT40320 awarded by the United States Department of Energy. The United States Government has certain rights in this invention.

BACKGROUND OF THE INVENTION

1. Technical Field of the Invention

The present invention relates to methods and materials for the removal of pollutants from flue gas or product gas from a gasification system. In particular, mercury is removed from gas streams generated during the burning or gasification of fossil fuels by highly reactive regenerable sorbents.

2. Background of the Invention

The combustion and gasification of fossil fuel such as coal generates flue gas that contains mercury and other trace elements that originate from the fuel. The release of the mercury (and other pollutants) to the environment must be controlled by use of sorbents, scrubbers, filters, precipitators, and other removal technologies. Mercury is initially present in the elemental form during combustion and gasification. In downstream process sections, such as in the ducts and stack of a combustion system, some of the elemental mercury is oxidized. The amount that is oxidized depends on the amount of acid gases present in the flue gas and other factors. Amounts of mercury vary with the fuel, but concentrations of mercury in the stream of flue gas from coal combustion are typically less than 5 parts per billion (ppb). Large coal combustion facilities such as electric utilities may emit a pound of mercury, or more, per day. Mercury removal applications include, without limitation, flue gas from coal (or other fossil fuel) combustion, waste incineration, product gas from gasification, as well as off gases from mineral processing, metal refining, retorting, cement manufacturing, chloralkali plants, dental facilities, and crematories.

Mercury Sorbent Technologies

Several types of mercury control methods for flue gas have been investigated, including injection of fine sorbent particles into a flue gas duct and passing the flue gas through a sorbent bed. Fine-particle injection sorbents include activated carbon, metal oxide sorbent, sodium sulfide particles, and basic silicate or oxide sorbents. When particle injection is employed, the mercury captured on the sorbent particles is removed from the gas stream in a bag house or electrostatic precipitator (ESP) and collected along with ash particulate. The sulfide and basic

silicate and oxide particles are effective only for the oxidized mercury, and the metal oxide sorbents exhibit slower capture kinetics than the carbon particles. Additionally, injection of fine carbon particles into the flue gas stream has been only partially successful in removing mercury, especially elemental mercury, where
5 effective removal of only about 60% is attained for some applications with a FF (fabric filter) to collect carbon and ash. Even lower removal rates have been observed when using an ESP to collect the carbon because the contact time of the carbon with the gas is very short.

A major problem with existing carbon injection systems is that the sorbent is
10 initially unreactive, and only after extended exposure to the flue gas does the sorbent become effectively seasoned and provide increased reactivity with the mercury in the gas. Consequently, these sorbents must be used in large amounts, at high sorbent-to-mercury ratios, to effectively capture the mercury. These sorbents tend to be relatively expensive and cannot be easily separated from the ash for
15 regeneration and reuse. The collection of carbon in the ash also creates solid waste disposal problems, and the spent sorbent may contaminate the collected ash, preventing its use in various applications.

Accordingly, there remains a need for more economical and effective mercury removal technology. This invention provides for cost-effective removal of
20 pollutants including mercury, using sorbent enhancement additives and/or highly reactive sorbents, with contact times of seconds (or less), and that may be regenerated and reused.

SUMMARY OF THE INVENTION

25 It is thus an object of the present invention to overcome the deficiencies of the prior art and thereby to provide new and economical methods for the removal of mercury from the gases produced in the utilization of fossil fuels.

A halogen/halide promoted activated carbon sorbent is described that is highly effective for the removal of mercury from flue gas streams. The sorbent
30 comprises a new halide-modified carbon form containing a reactive compound produced by the reaction of bromine (or halide or other halogen) with the carbon.

Optional secondary components and alkali may be added to further increase reactivity and mercury capacity. Mercury removal efficiencies obtained exceed or match conventional methods with added benefits such as reduced costs. Optionally, the sorbent can be regenerated and reused. Sorbent treatment and/or preparation methods are also described. New methods for in-flight preparation, introduction, and control of the active sorbent into the mercury contaminated gas stream are described.

In some embodiments, a promoted carbon sorbent is provided comprising a base activated carbon that has reacted with a promoter selected from the group consisting of halides, halogens, and combinations thereof, such that the reaction product is effective for the removal of mercury from a gas stream.

In an embodiment, a promoted carbon sorbent is provided wherein the base activated carbon is selected from the group consisting of powdered activated carbon, granular activated carbon, carbon black, carbon fiber, aerogel carbon, pyrolysis char, activated carbon with an average particle size greater than that of flyash produced such that it is physically separable therefrom, and combinations thereof, and the promoter is selected from the group consisting of molecular halogens, Group V (CAS nomenclature is used throughout) halides, Group VI halides, hydrohalides, and combinations thereof. In an embodiment, the base activated carbon may have a mass mean particle diameter such that it can be substantially separated by physical means from entrained ash in the gas stream from which mercury is to be removed. In an embodiment, the base activated carbon may have a mass mean particle diameter greater than about 40 micrometers.

In another embodiment, the sorbent comprises from about 1 to about 30 grams promoter per 100 grams of base activated carbon. Another embodiment further comprises an optional secondary component comprising a halogen or a hydrohalide such that the reactivity and mercury capacity of the sorbent are enhanced.

In another embodiment, the concentration of the optional secondary component on the finished sorbent is within the range of from about 1 to about 15 wt-% of the concentration of the promoter on the finished sorbent.

In another embodiment, an optional alkali component may preferably be added to provide a synergistic effect through combination of this alkali with the primary sorbent.

5 In another embodiment, the optional secondary component is selected from the group consisting of Group V halides, Group VI halides, HI, HBr, HCl, and combinations thereof. In another embodiment, the promoter is substantially in vapor form when combined with the base activated carbon. In another embodiment, the promoter is combined with an organic solvent prior to reaction with the base activated carbon. In another embodiment, the promoter and optional secondary
10 component are combined with the base activated carbon substantially simultaneously. Another embodiment further comprises adding a mercury-stabilizing reagent selected from the group consisting of S, Se, H₂S, SO₂, H₂Se, SeO₂, CS₂, P₂S₅, and combinations thereof. Another embodiment further comprises adding an optional alkali component.

15 In an embodiment, a method is provided comprising providing a granular activated carbon; reacting the activated carbon with a promoter selected from the group consisting of halogens, halides, and combinations thereof, such that the reaction product comprises a promoted carbon sorbent effective for removal of mercury from a gas stream. In a further embodiment, the reaction product comprises
20 from about 1 to about 30 grams promoter per 100 grams activated carbon. In another embodiment the reaction product has an average particle size distribution greater than the average size of entrained ash particles in the gas stream from which mercury is to be removed, such that the reaction product can be substantially removed from the entrained ash particles by physical means. In another embodiment
25 the reaction product has a mass mean particle diameter greater than about 40 micrometers.

In another embodiment, the promoter is selected from the group consisting of molecular halogens, hydrohalides, Group V halides, Group VI halides, and combinations thereof. In another embodiment the promoter is in the gas phase when
30 contacting the activated carbon. In another embodiment, the promoter is in an organic solvent when contacting the activated carbon.

In another embodiment, the promoter is selected from the group consisting of Br₂, a Group V bromide, a Group VI bromide, and combinations thereof.

In another embodiment, the method further comprises reacting the granular activated carbon with an optional secondary component comprising a halogen or a hydrohalide such that the reactivity and mercury capacity of the sorbent are enhanced. In another embodiment, the promoter and optional secondary component are contacted simultaneously with the activated carbon. In another embodiment the method further comprises adding a mercury-stabilizing reagent selected from the group consisting of S, Se, H₂S, SO₂, H₂Se, SeO₂, CS₂, P₂S₅, and combinations thereof. In an embodiment, a method is provided for control of mercury in a flue gas with substantially lower sorbent requirements. Through enhanced sorbent reactivity, mercury removal per gram of sorbent is increase, thereby decreasing the capital and operating costs by decreasing sorbent requirements.

In an embodiment, a method is provided for reducing mercury in flue gas comprising providing a sorbent, injecting the sorbent into a mercury-containing flue gas stream, collecting greater than 70 wt-% of the mercury in the flue gas on the sorbent to produce a cleaned flue gas, and substantially recovering the sorbent from the cleaned flue gas. In embodiments where less than 70 wt-% mercury removal is desired, the required removal may preferably be attained using less than half as much carbon as would be required with standard (non-enhanced) carbon. In a further embodiment, the method further comprises monitoring the mercury content of the clean flue gas, regenerating the recovered sorbent, and using the monitored mercury content of the cleaned flue gas to control the rate of injection of the sorbent. In another embodiment the injected sorbent is prepared in-flight by reacting an activated carbon and a promoter within a pneumatic transport line from which the reaction product is injected to the mercury-containing flue gas stream.

In another embodiment, the promoter is selected from the group consisting of molecular halogens, halides, and combinations thereof. In another embodiment, the promoter is reacted in the gas phase or as a vapor. In another embodiment, the promoter is added at from about 1 to about 30 grams per 100 grams of activated carbon.

In another embodiment, the injected sorbent is prepared in-flight by reacting an activated carbon, a promoter, and an optional secondary component to enhance the reactivity and capacity of the sorbent within a pneumatic transport line from which the reaction product is injected to the mercury-containing flue gas stream.

5 In another embodiment, the optional secondary component is selected from the group consisting of iodine, hydrohalides, Group V halides, Group VI halides, and combinations thereof. In another embodiment, the optional secondary component is added at from about 1 to about 15 wt% of the promoter content. In another embodiment, the method further comprises adding to the sorbent a mercury-
10 stabilizing reagent selected from the group consisting of S, Se, H₂S, SO₂, H₂Se, SeO₂, CS₂, P₂S₅, and combinations thereof.

In an embodiment, the method further comprises co-injecting an optional alkaline material, including without limitation alkaline and alkaline earth components, to improve the efficiency of mercury capture by capturing oxidized
15 mercury and/or capturing gaseous components that might otherwise reduce sorbent capacity. In another embodiment, the optional alkaline material may preferably comprise calcium oxide, sodium carbonate, and the like, as are known in the art.

In another embodiment, the method further comprises using the monitored mercury content of the cleaned flue gas to control the composition of the sorbent. In
20 another embodiment, the injected sorbent is prepared in-flight by reacting an activated carbon and a promoter within a pneumatic transport line from which the reaction product is injected to the mercury-containing flue gas stream, wherein the promoter is selected from the group consisting of molecular halogens, halides, and combinations thereof, wherein the promoter is reacted in the gas phase or as a vapor,
25 wherein the promoter is added at from about 1 to about 30 grams per 100 grams of activated carbon, wherein the rate at which the promoter is added and the rate of sorbent injection are determined by a digital computer based at least in part on the monitored mercury content of the cleaned flue gas.

In an embodiment, a method for reducing the mercury content of a mercury
30 and ash containing gas stream is provided wherein particulate activated carbon sorbent with a mass mean size greater than 40 μm is injected into the gas stream,

mercury is removed from the gas by the sorbent particles, the sorbent particles are separated from the ash particles on the basis of size, and the sorbent particles are re-injected to the gas stream. In another embodiment, the mercury-containing sorbent particles are regenerated to remove some or substantially all of the mercury. In
5 another embodiment, an alkaline component is co-injected into the gas stream. In another embodiment, the sorbent may further comprise a promoter. The promoter may preferably comprise a halide, a halogen, or both.

As will be described in more detail below, the present invention thus provides several advantages over previously known techniques, including
10 significantly more effective and economical mercury sorbents for effluent gases, advantageously applicable to treating gas streams from fired equipment and gasification systems.

The foregoing has outlined rather broadly the features and technical advantages of the present invention in order that the detailed description of the
15 invention that follows may be better understood. Additional features and advantages of the invention will be described hereinafter that form the subject of the claims of the invention. It should be appreciated by those skilled in the art that the conception and specific embodiments disclosed may be readily utilized as a basis for modifying or designing other structures for carrying out the same purposes of the present
20 invention. It should also be realized by those skilled in the art that such equivalent constructions do not depart from the spirit and scope of the invention as set forth in the appended claims.

BRIEF DESCRIPTION OF THE DRAWINGS

25 For a more detailed description of the preferred embodiments of the present invention, reference will now be made to the accompanying drawings.

FIG. 1 schematically illustrates methods for preparation of promoted carbon sorbents in accordance with the present invention.

FIG. 2 illustrates a proposed mechanistic model of the chemical reactions
30 resulting in the oxidation and capture of mercury.

FIG. 3 schematically illustrates preparation of promoted carbon sorbents and processes for flue gas mercury reduction in flue gases and/or product gases from a gasification system in accordance with the present invention, including in-flight preparation of promoted carbon sorbent.

5 FIG. 4 is a diagram illustrating breakthrough curves for 5 wt/wt % brominated NORIT Darco FGD sorbent (37 mg+113 mg sand) in low-HCl (1 ppm) synthetic flue gas.

10 FIG. 5 is a diagram illustrating breakthrough curves for non-halogenated NORIT Darco FGD sorbent (37 mg+113 mg sand) in low-HCl (1 ppm) synthetic flue gas.

FIG. 6 is a bar chart illustrating pilot-scale mercury removal results, including large-size sorbent results.

FIG. 7 is a diagram illustrating the effects of sorbent size and injection rate on mercury removal for ESPs and fabric filters.

15 FIG. 8 is a diagram illustrating the breakthrough curves for a brominated NORIT Darco FGD sorbent with inert sand.

FIG. 9 is a diagram illustrating the breakthrough curves for brominated NORIT Darco FGD sorbent with a co-injected alkali material.

20 FIG. 10 is a plot of mercury removal vs. carbon injection rate with and without co-injection of alkali material.

FIG. 11 is a block diagram illustrating the use of the invention in a coal fueled facility.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

25 Herein will be described in detail specific preferred embodiments of the present invention, with the understanding that the present disclosure is to be considered an exemplification of the principles of the invention, and is not intended to limit the invention to that illustrated and described herein. The present invention is susceptible to preferred embodiments of different forms or order and should not
30 be interpreted to be limited to the specifically expressed methods or compositions contained herein. In particular, various preferred embodiments of the present

invention provide a number of different configurations and applications of the inventive method, compositions, and their uses.

The present invention provides a cost-effective way to capture pollutants by utilizing exceptionally reactive halogen/halide promoted carbon sorbents using a bromide (or other halogen/halide) treatment of the carbon, that capture mercury via mercury-sorbent surface reactions, at very short contact times of seconds or less. The sorbent does not require in situ activation (no induction period) in the gas stream to achieve high reactivity, as do conventional activated carbon sorbents. The reactivity of the sorbent toward the pollutants is greatly enhanced and the sorption capacity can be regenerated, the promoted sorbent may be regenerated, recycled and/or reused.

The treated carbons, treatment techniques, and optional additives discussed herein have applicability to mercury control from the product or effluent gas or gases from gasification systems, syngas generators, and other mercury-containing gas streams, in addition to the flue gas from combustion systems. Thus, it should be understood that the terms combustion system and flue gas as used throughout this description may apply equally to gasification systems and syngas or fuel gas, as will be understood by those skilled in the art.

Referring now to FIG. 1, there is shown a block flow diagram illustrating some preferred embodiments of the process of the present invention to prepare promoted sorbents useful for mercury capture from flue gas and/or product gas from a gasification system streams. In a preferred embodiment illustrated by path 10-20, block 10 illustrates providing a base activated carbon, and adding a halogen or halide promoter that reacts with the carbon, illustrated at block 20, to produce a product promoted carbon sorbent. In embodiments where the halogen or halide is added, for example, as a vapor, no further steps may be necessary. In embodiments where the halogen or halide is added in, for example, a solvent, it may be desirable to employ solvent removal as illustrated by block 20A.

Referring still to FIG. 1, another preferred embodiment of the process of the present invention is illustrated by path 10-20-30, comprising providing a base activated carbon as shown by block 10, adding a halogen or halide promoter that

reacts with the carbon, illustrated at block 20, and adding a secondary component illustrated at block 30 that reacts with the result of block 20 to produce a product promoted carbon sorbent. In embodiments where both the halogen or halide promoter and the secondary component are added, for example, as a vapor, no further steps may be necessary. In embodiments where the halogen or halide promoter and/or secondary component are added in, for example, a solvent, it may be desirable to employ solvent removal as illustrated by block 30A.

Referring still to FIG. 1, another preferred embodiment of the process of the present invention is illustrated by path 10-40, comprising providing a base activated carbon as illustrated at block 10, and adding a halogen or halide promoter and a secondary component to the activated carbon together, with which they react as illustrated by block 40, producing a product promoted carbon sorbent. As above, in embodiments where vapor additions are made to the activated carbon no further steps may be desired. In embodiments where one or more components are added in solvent, a solvent removal step may be provided as illustrated by block 40A.

Referring still to FIG. 1, also illustrated are preferred embodiments in which, as illustrated by block 50, a flue gas stream is treated with product promoted carbon sorbent prepared as described above.

In some preferred embodiments the activated carbon provided may preferably be any of several types, as understood by those skilled in the art. For example, the activated carbon may include powdered activated carbon, granular activated carbon, carbon black, carbon fiber, carbon honeycomb or plate structure, aerogel carbon film, pyrolysis char, regenerated activated carbon from product promoted carbon sorbent, or other types as known in the art.

In some preferred embodiments the activated carbon provided may preferably be any of several types, as understood by those skilled in the art. For example, the activated carbon may include powdered activated carbon, granular activated carbon, carbon black, carbon fiber, carbon honeycomb or plate structure, aerogel carbon film, pyrolysis char, an activated carbon or regenerated activated carbon with a mass mean particle size greater than fly ash in a flue gas stream to be treated.

In some preferred embodiments the activated carbon provided may preferably be any of several types, as understood by those skilled in the art. For example, the activated carbon may include powdered activated carbon, granular activated carbon, carbon black, carbon fiber, carbon honeycomb or plate structure, aerogel carbon film, pyrolysis char, an activated carbon or regenerated activated carbon with a mass mean particle diameter preferably greater than 40 micrometers, more preferably greater than 60 micrometers, or a particle size distribution greater than that of the fly ash or entrained ash in a flue gas stream to be treated, such that the activated carbon and ash can be separated by physical means.

In some preferred embodiments, the halogen or halide promoter that is added to, and reacts with, the base activated carbon may preferably comprise, by way of illustration and not limitation, a molecular halogen in vapor or gaseous form, a molecular halogen in an organic solvent, a Group V or Group VI halide, such as PBr_3 or SCl_2 , respectively, in vapor, liquid, or solution form (though not in an aqueous solvent).

Embodiments are also provided in which the organic solvent may preferably comprise a chlorinated hydrocarbon, such as dichloromethane, a hydrocarbon solvent, including for example, petroleum ether, ligroin, pentane, hexane, toluene, and benzene, carbon disulfide, a waste solvent, an ether, a recycled solvent, a supercritical solvent, such as supercritical CO_2 , water (though not in the case of a Group V or Group VI halide), and others as will be apparent to those of skill in the art.

Referring now to FIG. 2, there is illustrated a theory developed from scientific evidence to explain the nature of the promoting compounds. For example, as illustrated in FIG. 2, hydrogen bromide reacts with the unsaturated structure of the activated carbon. This may be, by way of illustration only, a carbene species on the edge of the graphene sheet structures of the carbon. Molecular bromine or a bromine compound reacts to form a similar structure, with a positive carbon that is active for oxidizing the mercury with subsequent capture by the sorbent.

It has now been found that the formation of the new bromide compound with carbon increases their reactivity toward mercury and other pollutants. Additionally,

the resulting bromide compound is uniquely suited to facilitate oxidation of the mercury. The effectiveness of the oxidation apparently results from the promotion effect of the halide, exerted on the developing positive charge on the mercury during the oxidation, known in the chemical art as a specific catalytic effect. Thus, as the mercury electrons are drawn toward the positive carbon, the halide anion electrons are pushing in from the other side, stabilizing the positive charge developing on the mercury and lowering the energy requirement for the oxidation process. Bromide is especially reactive, owing to the highly polarizable electrons in the outer 4p orbitals of the ion. Thus, adding HBr or Br₂ to the carbon forms a similar carbon bromide, in which the positive carbon oxidizes the mercury with the assistance of the bromide ion.

Referring now to FIG. 3, a schematic flow diagram is provided of mercury control system 100 comprising preparation of promoted carbon sorbents, and flue gas mercury reduction, in accordance with preferred embodiments of the present invention. There is provided base activated carbon reservoir 110, an optional halogen/halide promoter reservoir 120, an optional secondary component reservoir 130, and an optional alkali component reservoir 180, each of which with corresponding flow control device(s) 201, 202, 203, and 208/209, respectively. In conjunction with the optional alkali component reservoir 180, optional flow control devices 208 and 209 can be used independently, together, or not at all.

Reservoirs 110, 120, 130, and 180 connect through their respective flow control devices and via associated piping, to transport line 115. Optional alkali component reservoir 180 may also connect, through respective flow control devices and via associated piping, to transport line 118. A source of air, nitrogen, or other transport gas(es) is provided by gas source 170 to transport line 115 for the purpose of entraining materials discharged from reservoirs 110, 120, 130, and 180 and injecting such materials, via injection point 116, into contaminated flue gas stream 15. A source of air, nitrogen, or other transport gas(es) may be provided by gas source 171 to transport line 118 for the purpose of entraining materials discharged from reservoirs 180 and injecting such materials, via injection point 119, into flue gas stream 15. Gas sources 170 and 171 may be the same or different, as desired.

Alternatively, transport gas(es) may be provided to both transport lines 115 and 118 by gas source 170 (connection from source 170 to line 118 not shown). Although gas sources 170 and 171 are shown in FIG. 3 as compressors or blowers, any source of transport energy known in the art may be acceptable, as will be appreciated by those of skill in the art.

For clarity, single injection points 116 or 119 are shown in FIG. 3, although one skilled in the art will understand that multiple injection points are within the scope of the present invention. Optical density measuring device(s) 204 is connected to transport line 115 and/or 118 to provide signals representative of the optical density inside transport line 115 and/or 118 as a function of time.

Downstream from injection point 116 and 119 is provided particulate separator 140. By way of illustration and not limitation, particulate separator 140 may comprise one or more fabric filters, one or more electrostatic precipitators (hereinafter "ESP"), or other particulate removal devices as are known in the art. It should be further noted that more than one particulate separator 140 may exist, sequentially or in parallel, and that injection point 116 and 119 may be at a location upstream and/or downstream of 140 when parallel, sequential, or combinations thereof exist. Particulate separator 140 produces at least a predominantly gaseous ("clean") stream 142, and a stream 141 comprising separated solid materials. A sorbent/ash separator 150 separates stream 141 into a largely ash stream 152, and a largely sorbent stream 151. Stream 151 may then preferably be passed to an optional sorbent regenerator 160, which yields a regenerated sorbent stream 161 and a waste stream 162.

An optional Continuous Emission Monitor (hereinafter "CEM") 205 for mercury is provided in exhaust gas stream 35, to provide electrical signals representative of the mercury concentration in exhaust stream 35 as a function of time. The optional mercury CEM 205 and flow controllers 201, 202, 203, 208, and 209 are electrically connected via optional lines 207 (or wirelessly) to an optional digital computer (or controller) 206, which receives and processes signals and preferably controls the preparation and injection of promoted carbon sorbent into contaminated flue gas stream 15.

In operation, promoted carbon sorbent and/or an optional alkali component is injected into contaminated flue gas stream 15. After contacting the injected material with the contaminated flue gas stream 15, the injected material reduces the mercury concentration, transforming contaminated flue gas into reduced mercury flue gas, 25. The injected material is removed from the flue gas 25, by separator 140, disposed of or further separated by optional separator 150, and disposed of or regenerated by an optional regenerator 160, respectively. The reduced mercury “clean” flue gas stream 142 is then monitored for mercury content by an optional CEM 205, which provides corresponding signals to an optional computer/controller 206. Logic and optimization signals from 206 then adjust flow controllers 201, 202, 203, 208, 209 to maintain the mercury concentration in exhaust stream 35 within desired limits, according to control algorithms well known in the art. Flow controllers 201, 202, 203, 208, 209 can also be adjusted manually or be some other automated means to maintain the mercury concentration in exhaust stream 35 within desired limits, according to control algorithms well known in the art.

Referring still to FIG. 3, there are illustrated several preferred embodiments for preparation and injection of promoted carbon sorbents and/or alkali components in accordance with the present invention. Stream 111 provides for introduction of base activated carbon from reservoir 110, as metered by flow controller 201 manually or under the direction of computer 206. The halogen/halide may be combined and react with the base activated carbon according to any of several provided methods. The halogen/halide may preferably be combined via line 121 directly into transport line 115, within which it contacts and reacts with the base activated carbon prior to injection point 116. This option is one form of what is referred to herein as “in-flight” preparation of a promoted carbon sorbent in accordance with the invention. Further, the halogen/halide may be combined via line 121b with base activated carbon prior to entering transport line 115. Still further, the halogen/halide may be contacted and react with the base activated carbon by introduction via line 121c into reservoir 110. This option is preferably employed when, for example, reservoir 110 comprises an ebullated or fluidized bed of base activated carbon, through which halogen/halide flows in gaseous form or as

a vapor. Of course, the halogen/halide may also preferably be contacted with the base activated carbon in liquid form or in a solvent, as discussed previously, and solvent removal (not shown in FIG. 3) may then be provided if necessary as mentioned with respect to embodiments discussed with reference to FIG. 1.

5 Similarly, the optional secondary component may be contacted and react directly in transport line 115 via line 131, or optionally as described above with respect to the halogen/halide, via lines 131*b* and 131*c*.

Similarly, the optional alkali component from 180 may either be added in transport line 115 directly, or may be injected separately by transport line 118,
10 combining downstream in flue gas 15 for synergistic effects with base activated carbon, promoted carbon, or optional secondary components. Being able to vary onsite the amount of the optional alkali component relative to base activated carbon, promoted carbon, or optional secondary components is a key feature to overcome and optimize for site-specific operating and flue gas conditions.

15 In some preferred embodiments wherein contacting between components and reaction is performed in a liquid or solvent phase, stirring of such liquid and/or slurry mixtures may be provided. In other embodiments, the halogen/halide promoter and optional secondary component(s) may preferably be sprayed in solution form into or on the base activated carbon. In some such embodiments,
20 drying, filtering, centrifugation, settling, decantation, or other solvent removal methods as are known in the art may then be provided.

In embodiments wherein the halogen/halide promoter is in gaseous or vapor form, it may be diluted in air, nitrogen, or other gas as appropriate. The halide/halogen gas, for example, gaseous HBr or Br₂, may be passed through an
25 ebullated or fluidized bed of granular or fibrous activated carbon, with the promoted carbon sorbent so produced removed from the top of the bed via gas entrainment for injection.

In some embodiments, the secondary component(s) may preferably comprise iodine or other halogens, hydrohalides, including without limitation HI, HBr, HCl, a
30 Group V or Group VI element with a molecular halogen, such as SCl₂ and others. In some preferred embodiments, the promoted carbon sorbent may comprise from

about 1 to about 30 g halogen/halide per 100 g base activated carbon. In some preferred embodiments, the promoted carbon sorbent may comprise a secondary component in concentration of from about 1 to about 15 wt-% of the concentration of the halogen/halide component.

5 In still other embodiments, the product promoted carbon sorbent may be applied to a substrate. In other embodiments, such prepared substrate(s) may be caused to contact a contaminated flue gas or gasification system product gas stream for mercury reduction purposes. Such substrates may be monolithic, rotating, or exposed to the gas stream in any number of ways known to those skilled in the art.

10 In some embodiments, a method is provided whereby a mercury stabilizing reagent is added to a promoted carbon sorbent to produce a bifunctional sorbent. Such stabilizing reagent(s) may be sequentially added, either before or after the addition and reaction of the halogen/halide. In some preferred embodiments, the halogen/halide preferably comprises Br or HBr, and the mercury-stabilizing reagent
15 may comprise S, Se, H₂S, SO₂, H₂Se, SeO₂, CS₂, P₂S₅, and combinations thereof.

Halogens in Mercury Capture

Methodologies for using halogens for the treatment of flue gas have been problematic, owing to their reactivity with other gases and metals, resulting in corrosion and health issues. A “halogen” is defined as a member of the very active
20 elements comprising Group VIIA (CAS nomenclature is used throughout; Group VIIA (CAS) corresponds to Group VIIB (IUPAC)) of the periodic table. In the molecular elemental form of the halogens, including F₂, Cl₂, Br₂, and I₂, the reaction with a hot flue gas components leave little to react with elemental mercury. The atomic elemental halogen form, which includes the fluorine, chlorine, bromine, and
25 iodine atoms, is about a million times more reactive to mercury but the concentration of the atomic forms is typically extremely low. In a large portion of electric utility coal combustion facilities, the concentrations are generally not sufficient to oxidize a significant amount of mercury.

30 The term “halide” as used herein is defined as a compound formed from the reaction of a halogen with another element or radical. In general, halide compounds are much less reactive than the molecular halogens, having a low chemical potential.

Halides are considered reduced forms that do not, alone, oxidize other compounds. In the conventional view therefore, a halide-salt-treated activated carbon will not effectively oxidize elemental mercury and capture elemental mercury.

Halogen Promoted Sorbent Characteristics

5 The sorbent described here has a very high initial reactivity for oxidizing mercury and therefore can be used in very small amounts to achieve very high capture efficiencies, thus lowering operation costs and lessening waste disposal problems. In addition, further disposal reductions are obtainable by regenerating and reusing the sorbents produced using the inventive technology. The time interval
10 required for the mercury and the promoted carbon sorbents of the present invention to successfully interact in a flue gas duct, with the subsequent collection of the mercury on the sorbent and ash is very short—less than seconds. Clearly, such collection times require the sorbent to have both high capacity and high reactivity toward mercury. The promoted carbon sorbent can be utilized in a very finely
15 powdered form to minimize mass transfer limitations. However, again, the reactivity should be very high to capture all of the mercury encountered by the fine particles. Additionally, use of these enhancement technologies allows capture to be effective for larger sorbent particles which also allows separation of the sorbent from the ash to enable subsequent regeneration as well as ash utilization. One feature of this
20 invention is the process to prepare a sorbent containing a halide compound formed on the carbon structure that provides a sorbent that is highly active on initial contact with the mercury contaminated gas stream, which allows for very effective capture of the mercury.

 It appears that the inventive sorbents chemically combine molecular
25 bromine, for example, from solution, with activated carbon (edge sites). X-ray photoelectron spectroscopy has established that the addition of bromine, chlorine, HBr, or HCl formed a chemical compound in the carbon structure. Thus, the sorbent produced from halogen and activated carbon does not represent a molecular halogen form, but rather a new chemically modified carbon (or halocarbon) structure. This
30 phenomenon may not occur with the less reactive iodine, where an I₂ molecular complex can exist on the carbon basal plane. In the case of bromine, modified

cationic carbon has a high chemical potential for oxidation of mercury. Thus, an entirely new model is presented for the reactivity of the bromine-treated carbon with mercury. The reactive carbon form can preferably be generated by the addition of bromine, hydrogen bromide, or combinations of bromine and other elements, as described herein. Halogen treatment resulted in higher-activity carbons because the halide anions (especially bromide and iodide) were effective in promoting the oxidation by stabilizing the developing positive charge on the mercury in the transition state for oxidation. Based on this model, several innovative, inexpensive, activity-enhancing features have been developed.

Optional Second Component

It has been demonstrated that addition of an optional second component, in addition to the bromine, results in improved reactivity and capacity for the sorbent, typically exceeding that of both the untreated carbon and the brominated carbon.

The second compound comprises either a second halogen or a compound derived from a second halogen, such as HI. Thus, in addition to having a reactive carbon form present, the second component generates a Lewis base with greater ability to stabilize the developing positive charge on the mercury. Thus, the second component is an element with more polarized electrons (4p and 5p).

Optional Alkali Component

It has been demonstrated that addition of an optional alkali component with a base or promoted activated carbon results in improved mercury capture, typically exceeding that of both the untreated carbon and the promoted carbon. Test data indicate that flue gas contaminants, flue gas constituents (SO_2 , NO_x , HCl , etc), operating temperature, mercury form, and mercury concentration may impact the effectiveness of the alkali addition. This suggests the need to be able to adjust and tailor the alkali-to-activated-carbon ratio onsite in order to overcome and optimize for a given set of site conditions.

The synergy that can be gained when co-injecting the two materials can be explained as follows. First, testing shows that binding sites on activated carbon (hereinafter "AC") can be consumed by chlorine species, sulfur species (i.e. sulfates), and other flue gas contaminants (arsenates, selenates, etc). The addition of

optional alkali material will interact and react with these species/contaminants thus minimizing their consumption of AC mercury binding sites. Second, testing also shows that standard AC will continue to oxidize mercury, even though the binding sites are fully consumed. This oxidized mercury can then react with alkali material and subsequently be captured by particulate control devices. Consequently, the addition of the optional alkali component acts to protect mercury binding sites and capture oxidized mercury, thereby resulting in improved mercury reduction at lower cost. Alkali is generally much lower in cost (~an order of magnitude less) than activated carbon, thus more of it can be used still resulting in overall lower costs.

10 “In-Flight” Sorbent Preparation

Furthermore, we have demonstrated that the halogen promoted carbon sorbent can be readily produced “in-flight”. This is accomplished by, for example, contacting the vapors of any combination of halogens and optionally a second component, in-flight, with very fine carbon particles. The particles may be dispersed in a stream of transport air (or other gas), which also conveys the halogen/halide promoted carbon sorbent particles to the flue gas duct, or other contaminated gas stream, from which mercury is to then be removed. There is no particular temperature requirement for this contact. This technology is obviously very simple to implement, and results in a great cost savings to facilities using this technology for mercury capture.

Advantages of On-Site Preparation

In-flight preparation of the halogen/halide promoted carbon sorbent on location produces certain advantages. For example, the treatment system can be combined with the carbon injection system at the end-use site. With this technique, the halogen/halide is introduced to the carbon-air (or other gas) mixture in a transport line (or other part of the sorbent storage and injection system). This provides the following benefits over current conventional concepts for treating sorbents off-site:

- Capital equipment costs at a treatment facility are eliminated.
- Costs to operate the treatment facility are eliminated.

There are no costs for transporting carbon and additive to a treatment facility.

The inventive process uses existing hardware and operation procedures.

5 The inventive technology ensures that the sorbent is always fresh, and thus, more reactive.

No new handling concerns are introduced.

There are no costs for removing carbon from treatment system.

10 The inventive process allows rapid on-site tailoring of additive-sorbent ratios in order to match the requirements of flue gas changes, such as may be needed when changing fuels or reducing loads, thus further optimizing the economics.

The inventive technology reduces the amount of spent sorbents that are disposed.

15 With the foregoing and other features in view, there is provided, in accordance with the present invention, embodiments including a process for preparing and regenerating halogen/halide promoted carbon sorbents, whose activity for mercury capture is enhanced by the addition of halogen (e.g. bromine) to the carbon structure.

Sorbent Injection Location

20 Some of the preferred embodiments contemplate the use of a halogen promoted sorbent in a powdered form that has been injected into a flue gas stream before or after ash particulates have been removed. Other embodiments of the inventive composition of the halogen promoted carbon sorbent comprise a powdered modified activated carbon prepared by adding Br₂ or HBr plus a second
25 optional component. Other embodiments allow the addition of the optional alkali component in conjunction with a base activated carbon and/or with the use of a halogen based sorbent and any other combinations of the sorbent technologies provided in this patent. Alternatively, embodiments include methods wherein the sorbent is on a moving contactor consisting of particles or fibers containing one or
30 more of the compositions listed above.

Sorbent Regeneration

Any of the above embodiments of the halogen/halide promoted carbon sorbent can be easily regenerated; the poisoning contaminants from the flue gas are preferably removed and an inexpensive promoting agent added, to restore mercury sorption activity. This process of promoting the activity of the carbon itself contrasts with the earlier, more expensive, conventional methods of adding a reagent (such as peroxide, gold, triiodide, etc.) to a sorbent. The halogen/halide promoted carbon sorbent of the present invention, treated with bromine and/or optional components, is noncorrosive. Detailed examples of sorbent regeneration techniques are described in co-pending, commonly owned PCT patent application No. PCT/US04/12828, titled "PROCESS FOR REGENERATING A SPENT SORBENT", which is hereby incorporated by reference in its entirety.

Sorbent Injection Control Schemes

Another advantage of the present invention relates to the use of a feedback system to more efficiently utilize certain aspects of the invention. Where possible and desirable, the mercury control technology of the present invention may preferably utilize continuous measurement of mercury emissions as feedback to assist in control of the sorbent injection rate. Tighter control on the sorbent and optional component(s) levels can be achieved in this way, which will ensure mercury removal requirements are met with minimal material requirements, thus minimizing the associated costs. In an embodiment, the mercury emissions are continuously measured downstream of the injection location, preferably in the exhaust gas at the stack.

Promoted Carbon Sorbents

Reactions of halogens and acidic species with the basic binding sites on the activated carbon sorbent create sites for oxidizing mercury. Other metal ions, such as boron, tin, arsenic, gallium, Sb, Pb, Bi, Cd, Ag, Cu, Zn, or other contaminants, will also react with the oxidation sites generated on the carbon.

According to our model, adding the bromine from the bromine reagent or a proton from a hydrogen halide acid to a basic carbene site on the carbon edge structure forms a carbocation that accepts electrons from the neutral mercury atom forming the oxidized mercury species that is bound to the sorbent surface. The

reactive site may also generate reactive bromine radicals or carbon radicals at the active sites on the carbon. Thus, the activated carbon serves to stabilize the bromine, yet provides a highly reactive bromine-containing reagent that can oxidize the mercury and promote its capture on the activated carbon. The sorbent that contains
5 bromine is expected to be more reactive than the corresponding sorbent containing chlorine and much less expensive than the sorbent containing iodine.

EXAMPLES

To more clearly illustrate the present invention, several examples are
10 presented below. These examples are intended to be illustrative and no limitations to the present invention should be drawn or inferred from the examples presented herein.

Example 1

15 Preparation and Testing of Halogenated Carbon (& Comparative Example) Gas Phase Halogenation

Finely powdered activated carbon (such as NORIT Darco FGD, NORIT Americas, Inc., Marshall, Tex. (USA), although others are suitable, as will be recognized by those skilled in the art), was placed in a rotating plastic barrel with
20 side blades (a 5 ft³ (0.14 m³) cement mixer) fitted with a tight plastic lid to prevent loss of the fine powder during the preparation. In a separate vessel, gas phase bromine was generated by passing a nitrogen stream over a weighed amount of liquid bromine that is warmed to about 40°-50° C. The vapor pressure of the bromine was such that a dark red gas is generated and passed out of the generator.
25 The outlet from the gaseous bromine generator is connected via a 1/4 inch (0.64 cm) plastic hose to a stationary metal tube inserted through a flange in the center of the plastic lid and passing into the center of the barrel. The flange is not air tight so that the excess of nitrogen is released after the bromine is transferred to the tumbling carbon. Thus, the bromine gas stream continuously passed into the rotating barrel
30 where it contacted the tumbling carbon. The unit is then operated until the desired amount of bromine has combined with the carbon. Typically, this is 0.4 to 1 kg of

bromine to 20 kg of carbon (2-5 wt. %). When the reaction is completed, the carbon is weighed. The treated carbon is odorless and does not cause skin irritation since the bromine has completely reacted with the carbon to produce the brominated carbon.

5 XPS spectra demonstrate that the brominated carbon contains both covalent carbon-bound (organic) bromide as well as anionic bromide. The product contains the same moisture originally present in the activated carbon (5-17 wt %), but does not require further drying for use. The moisture is driven out at higher temperatures (>150° C.), and the bromine was not released until very high temperatures

10 Bench-Scale Testing of Mercury Oxidation and Capture Efficiency

A bench-scale apparatus and procedure based on the above description was used to test the initial activities and capacities of several promoted activated carbon sorbents using powdered carbon, including bromine-containing activated carbons prepared from a variety of carbons, including commercially available sorbents, 15 aerogel film sorbents, and the original precursor carbons for comparison.

A detailed description of the apparatus and its operation is provided in Dunham, G.E.; Miller, S. J. Chang, R.; Bergman, P. *Environmental Progress* 1998, 17, 203, which is incorporated herein by reference in its entirety. The bench scale mercury sorbent tests in the flue gas compositions were performed with finely 20 (---400 mesh) powdered sorbents (37 mg) mixed with 113 mg sand and loaded on a quartz filter (2.5 inch (6.35 cm)). The loaded filter and holder were heated in an oven (125° C.) in the simulated flue gas stream (30 SCFH (standard cubic feet/hr) or 0.79 NCMH (normal cubic meters per hour)) containing the following: O₂ (6%), CO₂ (12%), SO₂ (600 ppm), NO (120 ppm) NO₂ (6 ppm), HCl (1 ppm), Hg⁰ (11 25 µg/m³), H₂O (15%), and N₂ (balance). Elemental mercury was provided by a standard permeation tube source placed in a double jacketed glass condenser, and heated to the desired temperature. Mercury concentrations in the gas streams were determined with a continuous mercury emission monitor (Sir Galahad mercury CEM mfr. P.S. Analytical Deerfield Beach Fla. USA), and a SnCl₂ cell was used to 30 convert oxidized species to elemental, so that both elemental and oxidized mercury concentration data could be obtained for both the influent and the effluent

concentrations from the sorbent bed. Mercury concentrations were calibrated for the flow rates used. Spent sorbents were analyzed for mercury to determine the mass balance.

Referring now to FIG. 4, the effluent mercury concentration data are plotted as a percent of the influent mercury versus time. The resulting curve (breakthrough curve) for the halogenated sorbents typically showed 0%-1% Hg in the effluent (99+0% capture) at the beginning, and increasing only after 30-60 minutes (breakthrough point), depending on the sorbent. FIG. 4 illustrates the breakthrough curves for 5 wt/wt % brominated NORIT Darco FGD sorbent (37 mg+113 mg sand) with synthetic flue gas containing 1 ppm HCl. Total Hg (solid circles) and elemental Hg (solid squares) in the effluent are presented as a per cent of the inlet Hg. "EOT" indicates the end of test (the later data points shown are for calibration checks).

FIG. 5 presents the comparative breakthrough curves for the corresponding nonhalogenated sorbents typically initiated at 5%-50% of inlet mercury, depending on the HCl concentration in the synthetic flue gas, thus indicating considerably lower reactivity for oxidation and capture of the mercury for the nonhalogenated sorbents. After breakthrough of either halogenated or nonhalogenated sorbent, most of the mercury in the effluent was oxidized mercury.

Example 2

Gas Phase Halogenation of Fluidized Carbon

A bed of activated carbon supported in a vertical tube by a plug of glass wool was fluidized by a nitrogen stream. The top of the fluidized bed tube was connected to a catching trap for carbon fines that blow out the top of the tube. The bromine gas generator as described in Example 1 was attached to the fluidized carbon bed and the desired amount of gaseous bromine was passed into the bed. The contents of the trap were then mixed with the material in the bed and weighed. The resulting brominated carbon exhibited properties similar to the brominated carbon of Example 1.

30

Example 3

Liquid Phase (Water) Halogenation

A 5% solution of bromine in water was prepared by carefully adding 50 g of bromine to 1 liter of cold water. One kg of activated carbon was added to the bromine solution in a large metal can. The resulting slurry was stirred with a large
5 paddle during the addition and for a short time afterwards until all the bromine had reacted with the carbon, as indicated by the disappearance of the red color. The slurry was then filtered using a Buchner funnel under vacuum. The moist carbon that was collected on the filter was dried in an oven at 110° C. for several hours to constant weight. As in Example 1, some moisture remains in the carbon, however.
10 The dried carbon was then tumbled in the rotating barrel with metal pieces to break up and fluff the carbon.

Example 4

Addition of the Optional Second Halide Component

15 Brominated carbon was produced by solution phase bromination similar to that described with reference to Example 3. However, before filtration, a solution of hydriodic acid (HI) was added to the slurry in an amount equal to 10% of the bromine amount. The slurry was stirred to complete the reaction and then filtered and dried as described in Example 3.

20

Example 5

Liquid Phase Phosphohalogenation

A solution of phosphorus tribromide (500 g) in ligroin (10 liters) was stirred in a large metal can and 10 kg of activated carbon was added. The resulting slurry
25 was stirred with a large paddle at ambient temperature to complete the reaction. The slurry was filtered under vacuum on a large Buchner funnel in several batches. The wet filter cake was dried at 110° C. in an oven to constant weight. The dried product was fluffed in the rotating barrel as described in Example 3.

30

Example 6

Preparation and Sorption on Larger-Particle Carbon

Tests were conducted on a pilot-scale combustor while firing a subbituminous coal, to evaluate mercury control by injecting larger-than-normal sized treated activated carbon. Standard AC sorbents generally are of fine size with a mean particle diameter of less than 20 micrometers, which is also typical of the flyash that is generated from pulverized coal combustion. Consequently, because the sizes of standard AC and flyash are similar, separation of the two is difficult. Injection of larger sized AC is generally not considered because the sorbent effectiveness decreases with size. In a scheme to recycle the injected carbon, the carbon is separated from the flyash. A separation based on size fractionation requires a treated larger particle sorbent. To test this concept, a treated larger sized (>60 µm) sorbent was developed, prepared, and tested.

Treatment—Gas Phase Halogenation

Granular activated carbon (Calgon F400) was ground and sieved through conventional mesh screens. The mesh size fraction -170 to +240 (corresponding to about 60 to about 88 micrometers) was collected and placed in a rotating vessel as described in Example 1 above. In a separate vessel, gas phase bromine was generated by passing a nitrogen stream over a weighed amount of liquid bromine that was warmed to about 40°-50° C., and the outlet from this gaseous bromine generator was connected via a ¼ inch (6.35 mm) plastic hose to a stationary metal tube inserted through a flange in the center of the lid and passing into the center of the rotating vessel, also as described in Example 1. The unit was operated until the desired amount of bromine had combined with the carbon, in this case 0.05 kg of bromine to 1 kg of carbon (5 wt. %). When the reaction was completed, the carbon was weighed. The treated carbon was odorless as has been described above.

PTC Apparatus

The pilot-scale combustor, known as the “Particulate Test Combustor” (hereinafter “PTC”), is a 550,000-Btu/hr (about 161 kW) pulverized coal (“PC”)-fired unit, designed to generate combustion flue gas properties and fly ash that are representative of those produced in a full-scale utility boiler. The combustor is oriented vertically to minimize wall deposits. A refractory lining helps to ensure adequate flame temperature for complete combustion and prevents rapid quenching

of the coalescing or condensing fly ash. Based on the superficial gas velocity, the mean residence time of a particle in the combustor is approximately 3 seconds. The coal nozzle of the PTC fires axially upward from the bottom of the combustor, and secondary air is introduced concentrically to the primary air with turbulent mixing.

5 Coal is introduced to the primary air stream via a screw feeder and eductor. An electric air preheater is used for precise control of the combustion air temperature. Originally, the PTC used cold-water annular heat exchangers to provide flue gas temperature control to the baghouse (also referred to as a "fabric filter") or electrostatic precipitator (ESP). However, analysis of ash deposits collected from
10 the heat exchangers indicated that some mercury was collected on the duct walls. To minimize this effect, the heat exchangers were modified to provide for higher duct wall temperatures.

The PTC instrumentation permits system temperatures, pressures, flow rates, flue gas constituent concentrations, and particulate control device (baghouse,
15 Advanced Hybrid Particle Collector/AHPC™, and/or electrostatic precipitator/ESP) operating data to be monitored continuously and recorded on a data logger.

PTC Procedure

Flue gas samples were taken at combinations of two of the three available system sample points: the furnace exit, the particulate control device inlet, and the
20 particulate control device outlet. After passing through sample conditioners to remove moisture, the flue gas was typically analyzed for O₂, CO, CO₂, SO₂, and NO_x. Each constituent was normally analyzed at both the furnace exit and the outlet of the particulate control device simultaneously, using two analyzers. The concentration values from all of the instruments were recorded continuously. In
25 addition, data were manually recorded at set time intervals. NO_x was determined using a pair of Rosemount Analytical NO_x chemiluminescent analyzers. SO₂ was measured using a pair of Ametek Instruments photometric gas analyzers. The remaining gases were measured by a pair of Rosemount Analytical multi-gas continuous emissions monitors. Each of these analyzers was regularly calibrated and
30 maintained to provide accurate flue gas concentration measurements.

The baghouse vessel was a 20 inch (50.8 cm) (ID) chamber that is heat-traced and insulated, with the flue gas introduced near the bottom. The combustor produced about 200 ACFM (actual cubic feet per minute; about 5.7 actual m³/min) of flue gas at 300° F. (about 150° C.), therefore three 13-ft by 5-inch (3.96 m by 12.7 cm) bags provided an air-to-cloth ratio of 4 ft/min (1.22 m/min). Each bag was cleaned separately in operation with its own diaphragm pulse valve. In order to quantify differences in pressure drop for different test conditions, the bags were cleaned on a time basis, rather than with the cleaning cycle initiated by pressure drop. Once bag cleaning was initiated, all three bags were pulsed in rapid succession on-line.

Tests were also conducted with a single-wire, tubular ESP replacing the fabric filter. The ESP unit was designed to provide a specific collection area of 125 at 300° F. (150° C.). Since the flue gas flow rate for the PTC is 130 SCFM (standard cubic feet per minute; about 3.7 NCMM (normal m³/min)), the gas velocity through the ESP is 5 ft/min (about 1.52 m/min). The plate spacing for the ESP unit is 11 in (27.9 cm). The ESP was designed to facilitate thorough cleaning between tests so that all tests can begin on the same basis.

PTC Results

Results are illustrated in FIG. 6. As can be observed in FIG. 6, even though the tested sorbent particle size is significantly larger than normal sorbent particles, the treated larger-than-normal sized (that is, >60 micrometers) activated carbon sorbent was quite effective at capturing mercury. Approximately 75% of the mercury was captured when the larger-sized treated AC was injected ahead of the pilot-scale ESP, while approximately 85% of the mercury was captured when injected ahead of the pilot-scale fabric filter ("FF"). Note that in FIG. 6 (and throughout) "Macf" (and "MACF") indicates million actual cubic feet (1 MACF is about 0.028 million actual cubic meters or "MACM").

Referring now to FIG. 7, it can be observed that the larger-sized treated AC when injected ahead of the pilot-scale ESP (diamond symbol(s)) performed better than the finer standard AC (triangles) under the same arrangement. In comparison, when injected ahead of the fabric filter (FF), the larger-sized treated AC (square)

performed similarly to slightly worse. However, for this application, the larger-sized treated AC can be physically separated from the smaller flyash particles, and the sorbent can then be regenerated, recycled, and reused. This will substantially improve overall utilization and economics. These data thus show that a larger-than-normal sized sorbent can provide effective mercury control and ease flyash and AC separation, thereby also preserving the characteristics of the flyash for sale and beneficial use. Accordingly, because >60 µm sorbent particles have been successfully demonstrated, superior mercury control can be obtained with >40 µm particles, which may be preferred in some applications, depending on the sorbent particle/ash separation system used. Note that in FIG. 7 (and throughout) “Macf” (and “MACF”) indicates million actual cubic feet.

Example 7

Liquid Phase (Organic Solvent) Halogenation

A 5% solution of bromine in ligroin was prepared by carefully adding 50 g of bromine to 1 liter of cold ligroin. One kg of activated carbon was added to the bromine solution in a large metal can. The slurry was stirred with a large paddle during the addition and for a short time afterwards until all the bromine had reacted with the carbon as indicated by the disappearance of the red color. The slurry was filtered using a Buchner funnel under vacuum. The carbon cake that was collected on the filter was dried in an oven at 110° C. for several hours until it appeared dry and a constant weight was obtained. As in Example 1, some moisture was left in the carbon, however. The dried carbon was then tumbled in the rotating barrel with metal pieces to break up and fluff the carbon.

Example 8

Promoted Activated Carbon Sorbents

A bench-scale procedure based on the above description was used to test the initial activities and capacities of several promoted activated carbon sorbents using powdered carbon, including the bromine-containing activated carbons prepared from a commercially available sorbent and an aerogel carbon film sorbent, as well

as the original precursor carbons for comparison. Bromine-treated carbons were prepared by impregnation of the powdered activated carbon precursors in a stirred solution of bromine in carbon tetrachloride or methylene chloride, or alternatively, in an aqueous solution of HBr, followed by drying in air at ambient temperature and
5 drying in an oven at 100° C. in air or nitrogen. Bromine-treated carbons were also prepared by impregnating bromine from the gas phase by passing the gas through a rotating dry bed of the activated carbon precursor. The results indicated that adding a second component to the solution improved the capacity of the sorbent.

The carbons were initially tested in a heated bed, where a synthetic flue gas
10 stream containing elemental mercury ($11 \mu\text{g}/\text{m}^3$) was passed through the bed. Concentrations of total and elemental Hg in the effluent gas were determined using a Sir Galahad mercury CEM ("continuous emission monitor") (mfr. P S Analytical, Deerfield Beach, Fla., USA). The powdered sorbent was supported on a quartz filter during the test, and the other sorbents were tested as a triple layer. A comparison of
15 the original commercial-grade powdered carbon sorbent with the sorbent after it was treated with 0.1 N HBr, and the powder was collected by centrifugation and drying, revealed that the mercury capture activity increased from an initial capture efficiency of about 50% of the Hg in the inlet to 100% capture. A comparison of the sorbent after subsequent regeneration with HBr indicated that it not only captured
20 mercury at the same level as before (100% capture) but its capacity was prolonged by several minutes, and thus enhanced. Similar results were obtained with the carbon film and carbon fiber sorbents by treatment with molecular bromine in solution or in dry beds as described above.

25 Example 9

Fluidized/Ebullated Bed Preparation

An activated carbon sorbent was prepared by treating the carbon by impregnating molecular bromine from a gas composition containing molecular bromine by flowing the gas through a liquid bromine reservoir in series with a
30 fluidized bed or ebullated bed of the carbon. The amount of bromine taken up by the

carbon ranges (in one example) from <1 to about 30 g per 100 g of activated carbon, depending on the proportions used.

Example 10

Full-Scale Testing

5 In this example, a baghouse (fabric filter) or ESP was used to collect particulates in the exhaust of a full-scale commercial pulverized coal-burning facility. A scrubber and sorbent bed were also used to remove undesired constituents from the flue gas stream, before being fed to the stack. In this example, 10 the halogen/halide promoted carbon sorbent was injected into the flue gas after the boiler. In general however, the inventive sorbent can be injected where desired (e.g., before, after, or within the boiler).

In one exemplary test conducted at a facility fired with lignite coal, the flue gas phase mercury (elemental) concentration was between 10 and 11 $\mu\text{g}/\text{m}^3$. The ash 15 and injected carbon were collected in the baghouse at 350° F. to 375° F. (about 175-190° C.). Injection of commercial-grade activated carbon powder (untreated) at a rate of 1.0 lb/MACF ("MACF" and "Macf" represent one million actual cubic feet; 1.0 lb/MACF is about 16 kg/MACM (million actual cubic meters)) resulted in mercury effluent concentrations of 3.8-4.2 $\mu\text{g}/\text{m}^3$ (representing 62%-58% removal 20 of the mercury from the gas, respectively), and at 2.0 lb/MACF (about 32 kg/MACM), gave 74%-71% removal. Injection of the bromine-treated carbon at 1.0 lb/MACF resulted in 73%-69% removal and at 2.0 lb/MACF gave 86%-84% removal. Thus, a significant increase in the mercury capture was exhibited during use of the bromine promoted carbon sorbent of the present invention.

25

Example 11A

Addition of Optional Alkaline Component—Bench-Scale

The efficiency of the activated carbons for mercury capture can be improved considerably by employing a basic material co-injected with the activated carbon, in 30 order to capture any oxidized mercury that may be released from the sorbent, or to

capture some of the sulfur or selenium oxides in the flue gas that can have a detrimental effect on the sorbent capacity.

Bench-scale testing was conducted by preparing a filter composed of 37 mg of brominated activated carbon mixed with 113 mg of calcium oxide. The test was conducted as described in Example 1 and compared with the same carbon sorbent but with an inert diluent. The breakthrough curve for the mixture of brominated (2%) NORIT Darco FGD sorbent with inert sand is shown in FIG. 8, and the breakthrough curve for the mixture with CaO is shown in FIG. 9. It can be seen that the point of 50% breakthrough improves to 65 minutes with the mixture with CaO from only 48 min with the sand mixture.

Example 11B

Addition of Optional Alkaline Component—Pilot-Scale

Tests were conducted on the pilot-scale PTC combustor described above with reference to Example 6 while firing a Texas lignite to evaluate mercury control by co-injecting a standard activated carbon (also referred to herein as “AC”) and an alkali material upstream of a fabric filter. Typical results are illustrated in FIG. 10. As shown in FIG. 10, co-injecting lime with activated carbon vastly improved mercury removal. Mercury removals of approximately 90% were achieved with the co-injected sorbents, whereas less than 60% removal was achieved with the use of standard AC alone, even at much higher injection rates. Data from similar tests show that injecting similar quantities of sodium carbonate and AC, and lime and AC, resulted in mercury removals of approximately 80%, and 87%, respectively. These data suggest that other alkali can also be co-injected with AC to improve mercury removal. Other data show that flue gas temperature may impact the effectiveness of the alkali addition. Further test data indicate that flue gas contaminants, flue gas constituents (SO₂, NO_x, HCl, etc.), operating temperature, mercury form, and mercury concentration may impact the effectiveness of the alkali addition. This indicates that it may be desirable to be able to adjust and tailor, onsite, the alkali-to-AC ratio in order to optimize removal for a given set of site conditions.

Without wishing to be bound by any particular theory, the synergy observed in the improved performance when co-injecting the two materials can be explained as follows. First, tests indicate that binding sites on AC can be consumed by sulfur species and other contaminants. The alkali material interacts and reacts with these species thus minimizing their consumption of AC mercury binding sites. Second, other work has shown that standard AC will continue to oxidize mercury even though the binding sites are fully consumed. This oxidized mercury can then react with alkali material and subsequently be captured by the particulate control device. Thus, combining alkali with treated and/or non-treated AC synergistically takes advantage of these two mechanisms, resulting in improved mercury capture at reduced costs.

Example 12

Brominated Carbon Sorbent for Gasification Fuel Gas

Preparation of 5% Br₂W-AC

Using a procedure similar to Example 3, a 2.5 wt/vol % solution of bromine in water was prepared. Granular Calgon F400 was added to the bromine solution to give a 5 wt/wt % brominated carbon product. The bromine solution was stirred with a large paddle during and after the addition until the red color in the water disappeared. The suspension was filtered by vacuum on a large Buchner funnel. The filter cake was dried in air, and then in an oven at 110° C. until a stable weight was obtained. The moisture was reduced to 15%.

Preparation of 5% Br₂D-AC

A brominated sorbent was prepared from Br₂ addition in solvent as described in Example 7, except that dichloromethane was used as the solvent instead of ligroin, and granular Calgon F400 was used.

Preparation of 5% PBr₃-AC

A phosphohalogenated sorbent was prepared from PBr₃ using the method described in Example 5, except granular Calgon F400 was used.

Testing in Hydrogen Atmosphere—Procedure

To simulate the capture of mercury from a heated fuel gas or syngas from coal gasification, tests were conducted employing a stream comprising 10% vol/vol hydrogen in nitrogen passing through the sorbent at 500 cc/min. The stream contained 26.9 micrograms/m³ of elemental mercury from a commercial mercury permeation source.

In the tests, the sorbent (0.5 g) was placed in a 0.39 inch (1 cm, inside diameter) glass tube fitted with a medium frit sintered glass filter disc to hold the sorbent in the gas stream. The tube containing the sorbent bed was connected to a gas inlet tube for introducing the gas stream containing the mercury vapor and at the outlet to a tube connection to the detector. The detector was a Semtech 2000 continuous mercury emission monitor. The tube was equilibrated in a nitrogen flow (450 cc/min) for 5 minutes at ambient temperature to stabilize the system. The detector showed 0 concentration of mercury in the effluent from the sorbent bed. (The blank run with no sorbent read 26.9 micrograms/m³). The tube was then placed in an oven at the selected temperature for the test (from 250° to 400° C.). Effluent mercury concentration data from the detector were collected until the detector showed a constant reading for 5 minutes. Hydrogen (50 cc/min) was then added to the gas stream and detector readings were taken every 5 min. Tests were conducted at several oven temperatures for various periods of time up to 3 hours, depending on the temperature and sorbent. The elemental mercury concentration data were plotted as a percent of inlet mercury concentration versus time as in Example 1. All the mercury in the effluent was elemental, so a single detector was sufficient, and no SnCl₂ trap was needed to convert to elemental mercury (as in Example 1). The time for 50% breakthrough (time to reach 50% capture) was then determined from the breakthrough curves.

Results

The results are shown in Table 1 (below) for the unbrominated sorbent (Calgon F-400), the brominated sorbents (5% Br₂W-AC and 5% BrD-AC), and the phosphobrominated sorbent (5% PBr₃-AC). The maximum mercury concentration obtained in the effluent in each run is also reported in Table 1 for the time period indicated in the last column.

Under the reducing hydrogen conditions, the unbrominated sorbent broke through immediately and was exhausted after only 6.5 min. This complete failure occurred because the hydrogen reduces the captured mercury in the unbrominated sorbent at any temperature above 100° C. Both of the brominated sorbents exhibited excellent reactivity and good capacity at all temperatures, up to at least 400° C. The phosphobrominated sorbent exhibited superior reactivity and capacity at all temperatures, up to at least 400° C.

Times for 50% Breakthrough Maximum Observed Hg Concentrations for Sorbents (10% Hydrogen Streams)				
Sorbent	Temp (° C.)	50% breakthrough (min)	Maximum [Hg] (µg/m ³)	Time (min)
F-400	250	6	20.3	6.5
5% Br2W-AC	250	>150	1.4	150
5% Br2W-AC	300	>180	4.3	180
5% Br2W-AC	350	160	15.1	180
5% Br2W-AC	400	60	13.9	65
5% PBr3-AC	250	>140	0.4	140
5% PBr3-AC	300	>150	0.5	150
5% PBr3-AC	350	>150	1.4	150
5% Br2D-AC	350	>180	2.1	180
5% Br2D-AC	400	>180	10.9	180

While the preferred embodiments of the invention have been shown and described, modifications thereof can be made by one skilled in the art without departing from the spirit and teachings of the invention. The embodiments described herein are exemplary only, and are not intended to be limiting. Many variations and modifications of the invention disclosed herein are possible and are within the scope of the invention. Accordingly, the scope of protection is not limited by the description set out above, but is only limited by the claims which follow, that scope including all equivalents of the subject matter of the claims.

The examples provided in the disclosure are presented for illustration and explanation purposes only and are not intended to limit the claims or embodiment of this invention. While the preferred embodiments of the invention have been shown and described, modifications thereof can be made by one skilled in the art without

departing from the spirit and teachings of the invention. Process criteria, equipment, and the like for any given implementation of the invention will be readily ascertainable to one of skill in the art based upon the disclosure herein. The embodiments described herein are exemplary only, and are not intended to be limiting. Many variations and modifications of the invention disclosed herein are possible and are within the scope of the invention. Use of the term “optionally” with respect to any element of the invention is intended to mean that the subject element is required, or alternatively, is not required. Both alternatives are intended to be within the scope of the invention.

The discussion of a reference in the Background is not an admission that it is prior art to the present invention, especially any reference that may have a publication date after the priority date of this application. The disclosures of all patents, patent applications, and publications cited herein are hereby incorporated herein by reference in their entirety, to the extent that they provide exemplary, procedural, or other details supplementary to those set forth herein.

Although the invention is described herein as a sorbent material and associated processes for its preparation and use, it is nevertheless not intended to be limited to the details described, since various modifications and structural changes may be made therein without departing from the spirit of the invention and within the scope and range of equivalents of the claims.

PROVISIONAL APPLICATION

A reactive sorbent material is described for capture of mercury in a vapor stream. The vapor stream includes flue gas from coal combustion or incineration, synthesis gas from gasification, as well as offgases from mineral processing, metal refining, retorting, cement manufacturing, chloralkali plants, dental facilities, and crematories. The sorbent is especially suited to, but not limited to, use in low-chlorine flue or exhaust gases where the mercury is mainly elemental. The sorbent comprises a bromide-modified carbon form containing a reactive compound produced by the reaction of bromine with the carbon. Other additional promoting substances can be added in smaller amounts to increase the reactivity with and

sorption of elemental mercury. This combination results in a carbon bromide structure in the carbon lattice that can oxidize the mercury to a species that is strongly bonded to the carbon structure and, therefore, easily retained on the sorbent at higher temperatures in the presence of flue gas constituents. In some examples, the sorbent consists of a fine or coarse powdered material for injection into the gas stream or a granular or fibrous material for use in a fixed or moving bed. In some examples, the sorbent does not require in situ activation (an induction period) in a flue gas stream as do conventional activated carbon sorbents. Other additives of base chemistry (Ca, Na, and others) may be added to flue gas as a sorbent mixture, or co-injected to selectively sorb acid gases or other flue gas constituents to keep available reactive sites for mercury oxidation and subsequent capture. The sorbent can be regenerated by washing off contaminating components derived from flue gas that poison the spent sorbent. Novel methods for introduction of the sorbent dispersion into the mercury contaminated gas stream are described.

Following is an outline of examples of the invention. The invention may also take on various other examples or embodiments, as a person skilled in the art would understand.

1. A modified carbon sorbent was prepared by reacting the carbon with molecular bromine by applying a solution of molecular bromine in an organic solvent to the carbon, followed by removal of the modified carbon from the bulk of solvent and further removal of solvent from the pores by drying the carbon in air or nitrogen. The solution may also contain an additional promoting substance in small amounts. In one example, the amount of bromine taken up by the carbon ranges from <1 to about 30g per 100g of activated carbon, depending on the proportions used.

1A. (Dependent)

Same as 1, carbon is powdered activated carbon.

Carbon is granular activated carbon.

Carbon is very fine carbon black.

Carbon is very fine carbon fiber.

Carbon is aerogel carbon film.

Carbon is char recovered from pyrolysis process.

Carbon is powdered activated carbon of size distribution larger than fly ash size distribution, so that it can be physically separated from the ash and regenerated
5 for reuse.

Carbon is regenerated from previous usage cycle and recycled.

Other desired types of carbon may also be used.

1B. (Dependent)

10 Same as 1, Solvent is chlorinated hydrocarbon such as dichloromethane.

Same as 1, Solvent is hydrocarbon solvent such as petroleum ether or ligroin or pentane or hexane or toluene or benzene.

Same as 1, Solvent is water.

Same as 1, Solvent is carbon disulfide.

15 Same as 1, Solvent is a waste solvent.

Same as 1, Solvent is an ether.

Same as 1, Solvent is recycled from previous batch.

Same as 1, Solvent is supercritical solvent such as CO₂.

Other desired types of Solvents may also be used.

20

1C. (Dependent)

Same as 1, solution of bromine is applied by stirring the carbon in the bromine solution.

25 Same as 1, solution of bromine is applied by spraying a solution of molecular bromine in an organic solvent, followed by removal of solvent from the pores by drying the carbon in air or nitrogen.

The bromine may also be applied using other desired techniques.

1D. (Dependent)

30 Same as 1, removal of solvent is by filtration, centrifugation, settling, and decantation and drying in vacuum, air, or other gas.

Same as 1, when sprayed or minimal volume, removal of solvent is by drying in air, vacuum, or other gas.

The solvent may also be removed using other desired techniques.

5 1E. (Dependent)

Same as 1, additional substance is iodine, at 1%-10% of the bromine concentration added.

Same as 1, additional substance is hydrohalide (HI, HBr, HCl), etc., 1%-10 % of bromine.

10 Same as 1, additional substance is a compound comprised of a Group V or VI element or combination of Group V or VI with Group VII element, such as SCl_2 , 1-10 wt % of bromine.

2. A modified carbon sorbent was prepared by reacting the carbon with
15 molecular bromine by contacting the carbon with a gas containing molecular bromine. In one example, the amount of bromine taken up by the carbon ranges from <1 to about 30 g per 100g of activated carbon, depending on the proportions used.

Contacting is by passing the Br_2 gas through a bed of the carbon.

20 Bed is ebullated or fluidized.

Bed is moving bed of granules or fibers.

Contacting is by admitting Br_2 gas to a duct through which the carbon is transported from a reservoir to the flue gas duct via an air-driven entrainment method, thus promoting the activity of the carbon in-flight.

25 Same additives as 1E, except these are added in the gas phase, and added in-flight as in 2 above.

3. A modified activated carbon sorbent was prepared by reacting the carbon
with hydrogen bromide (HBr) by stirring the carbon in a solution of HBr in an
30 organic solvent or in water, followed by removal of the modified carbon from the bulk of solvent and further removal of solvent from the pores by drying the carbon

in air or nitrogen. In one example, the amount of bromine taken up by the carbon ranges from <1 to about 30 g per 100g of activated carbon, depending on the proportions used.

5 Same dependent clauses as in 1A with regard to carbon forms. Same solutions and treatment as 1B, 1C, 1D.

Same additives as 1E, added into the solution phase or later in the gas phase, and added in-flight as in 2 above.

4. An activated carbon sorbent was prepared by impregnating hydrogen
10 bromide by passing a gas composition containing hydrogen bromide diluted with nitrogen or air through a fluidized bed or ebullated bed of the carbon. In one example, the amount of bromine taken up by the carbon ranges from <1 to about 30 g per 100g of activated carbon, depending on the proportions used.

15 Same dependent clauses as in 1A with regard to carbon forms. Contacting options are similar to 2.

5. Sequential treatment of activated carbon with bromine or HBr, followed by another mercury stabilizing reagent to generate a highly reactive bifunctional sorbent, the reagent to include sulfur and selenium species, such as H₂S, SO₂, H₂Se,
20 Se, SeO₂, CS₂, P₂S₅.

6. Sequential treatment of activated carbon with mercury stabilizing reagent, followed by bromine or HBr to generate a highly reactive bifunctional sorbent, the reagent to include sulfur and selenium species, such as H₂S, SO₂, H₂Se, Se, SeO₂,
25 CS₂, P₂S₅.

7. Treatment of a carbon with a Group V or VI element combined with Group VII element, such as PBr₃ or SCl₂. In one example, the amount of Group V or VI halide is 1-30 wt % of the carbon. The compound is added in vapor phase or in
30 solution (solvent is hydrocarbon, chlorinated hydrocarbon, or other solvent as described in 1B, but not water, since the compound is destroyed in water solution).

8. The process for preparing the bromine-containing activated carbon sorbent as described in Examples 1-6 and coupled with the injection of the bromine-containing fine-particle sorbent into the contaminated gas stream and subsequent
5 removal of the fine particles of sorbent from the gas stream in a collection device, such as bag filtration or electrostatic precipitator (ESP).
9. The process of using additives (1-8) in conjunction with sorbents to capture acid gases and other flue gas constituents that block oxidation reactions or consume
10 sorbent sites that would otherwise capture mercury. The additive is a compound comprised of Group I or II elements, such as Ca, Na, and others. These additives of base chemistry may be added to flue gas as a sorbent mixture or co-injected to selectively sorb acid gases or other gas constituents that compete for mercury reactive/sorption sites, thereby improving the effectiveness of activated carbon to
15 capture mercury. In addition, the base additives can augment the treated activated carbon by helping to capture oxidized mercury forms in the flue gas, such as mercuric chloride, or that are produced on the carbon sorbent, such as mercuric bromide, but are released to the gas phase as the sorbent becomes saturated or capacity limited.
- 20 10. The process of preparing a larger-than-normal ($>40\ \mu\text{m}$) sorbent particle size, promoting with the halogen treatment as described in 1-8, using the treated sorbent for capture of mercury by injecting in the flue gas, and finally separating and recovering the sorbent from the ash particles. The larger sorbent size thus will
25 allow easy mechanical/physical separation so that sorbent can be regenerated, recycled, and reused, and the ash can be sold as a low-carbon cementitious byproduct for concrete. The separation can be effected by various methods, such as density (gravity), floatation, or sieving methods.
- 30 11. The process for preparing the bromine-containing activated carbon sorbent as described in Example 1-10, coupled with the direct injection of the slurry of the

prepared fine-particle sorbent in the solvent or aqueous phase, so that the aerosol particles of the slurry achieve a high degree of dispersion in the gas stream and evaporation of the solvent in the hot gas occurs rapidly. The amount of slurry added is flow-controlled, and the concentration of particles in the slurry is monitored by
5 optical density measurements prior to injection. Collection of particles is performed.

12. The process for preparing the bromine-containing activated carbon sorbent, as described in Examples 2 and 4, coupled where the fine-particle dispersion of brominated sorbent in the gas stream at the top of the ebullated bed is led to the flue
10 gas or offgas duct where the said dispersion is contacted with mercury-contaminated flue gas or offgas stream. The amount of aerosol dispersion added is controlled by the gas flow to the ebullated bed, and the concentration of particles in the dispersion can be monitored by optical density measurements prior to injection. Collection of particles is performed by the existing particulate-collection equipment.

15

13. The process for preparing the bromine-containing activated carbon sorbent bed, coupled with contacting the bed with the mercury-contaminated flue gas or offgas.

20 14. The process for preparing the bromine-containing activated carbonB sorbent, as described in Examples 2 and 4, or untreated activated carbon, coated on a substrate or as activated carbon material. This material is placed in a moving system that geometrically allows for control of rate of exposure, sorption, and exchange of material in a continuous or semicontinuous manner.

25

15. In the sorbent and mercury removal process outlined in paragraphs above, the bromine reagents promote metal oxidation activity by creating cationic or radical character on the carbon edge structure that attracts mercury atoms and extracts electrons from said mercury atoms, resulting in oxidized mercury, which is
30 more easily captured on a sorbent. A similar mechanism applies to oxidation and capture of reduced arsenic and other pollutant species.

The invention relates to the process for the removal of mercury and other pollutant species from gas streams generated during the burning of fossil fuels, such as in a coal-fired utility or synthesis gas from gasification facilities. This removal process would utilize a sorbent and/or a combination of additives to remove pollutants from the gas stream, which are at the same time interacting with other gas components that result in poisoning or deactivating the sorbent and reducing its capacity or reaction rates with the targeted pollutant species. The present invention provides a cost-effective way to capture the pollutants by utilizing exceptionally active carbon sorbents and promoting mercury sorbent surface reactions, containing a bromide form of the carbon, that capture mercury with high kinetic chemisorption (oxidation) activity, so that capture can occur during contact times of seconds or less. The sorbent does not require in situ activation (induction period) in the gas stream to achieve high activity as do conventional activated carbon sorbents. The reactivity of the sorbent toward the pollutants and the sorption capacity can be regenerated, recycled, and reused.

Burning fossil fuels generates a flue gas that contains mercury (and other trace elements) that was in the coal, plus oxides of sulfur and nitrogen (acid gas emissions) and particulates whose release to the environment must be controlled by use of sorbents, scrubbers, filters, precipitators, and other removal technologies. While control of other elements and/or flue gas pollutants may apply, the discussion provided is focused on mercury. Initially, mercury is released in the elemental form during combustion/gasification, but downstream of the boiler, in the ducts and stack of the combustion system, part of the elemental mercury is oxidized. The amount oxidized depends on the amount of acid gases present in the flue gas and other factors. Amounts of mercury vary with the coal, but a typical concentration of mercury in the stream of combustion gas is about 5 parts per billion (ppb). A pound of mercury or more per day may be emitted in some utilities.

Discussion of Sorbent Technologies

Several types of mercury control methods for flue gas have been investigated, including injection of fine sorbent particles into a flue gas duct and passing the flue gas through a sorbent bed. Fine-particle injection sorbents include activated carbon, metal oxide sorbent, sodium sulfide particles (for example, see 5 U.S. Patent 6,214,304), and basic silicate or oxide sorbents (for example, see the Ghorishi reference (Ghorishi, B.; Gullet, B.K. Waste Manage Res. 1993, 16, 582). and Lancia references). When particle injection is employed, the mercury chemisorbed to the sorbent particle is removed from the gas stream in a bag house or ESP and collected along with ash particulates (for example, see U.S. Patents 10 4,889,698, 4,956,162, 5,672,323, 5,827,352, 6,027,551, and 5,505,766). The sulfide and basic silicate and oxide particles are effective only for the oxidized mercury, and the metal oxide sorbents exhibit slower capture kinetics than the carbon particles. Additionally, injection of fine carbon particles into the flue gas stream has been only partially successful in removing mercury, especially elemental mercury, 15 where effective removal of approximately 60% was attained with a baghouse to collect carbon and ash. Even lower removal rates have been observed when using an ESP to collect the carbon, since the contact time of the carbon with the gas is very short.

A major problem with existing carbon injection systems is that the sorbent is 20 initially unreactive, and only after exposure to the flue gas for about 20 minutes does the seasoned sorbent become effective and provide capture of 60% of the mercury in the gas. Consequently, these sorbents must be used in large amounts (high sorbent-to-mercury ratios) to effectively capture the mercury. These sorbents can be relatively expensive and cannot be easily separated from the ash, regenerated 25 and reused. The collection of carbon in the ash also creates solid waste disposal problems, and the spent sorbent may contaminate the collected ash for use in various applications.

Use of Halogens in Mercury Capture

30 Methodologies for using halogens for the treatment of flue gas have not previously been effective. Halogen is defined as a member of the very active

elements comprising Group VII-A of the periodic table. In the molecular elemental halogen form, including F₂, Cl₂, Br₂, and I₂, the reaction with elemental mercury is not fast enough to result in the formation of oxidized mercury in a coal combustion flue gas with conventional ash control technology. The atomic elemental halogen form, which includes F atom, Cl atom, Br atom, and I atom, is about a million times more reactive to mercury, but the concentrations of these forms are extremely low, and also, therefore, cannot result in oxidation of mercury in a utility flue gas.

A halide is a compound formed from reaction of a halogen with another element or radical. In general, the halide compounds are normally very much less reactive than the molecular halogens, having expended their high chemical potential in forming the low energy halide. The halide is considered a reduced form and cannot therefore oxidize anything by itself. It is for this reason that it is not obvious that a halide-halogen treated activated carbon would be effective at oxidizing elemental mercury and provide effective capture of elemental mercury. In fact, for tests with salts, analytical data show the addition of bromine to an activated carbon or carbon black or soot does form a compound by reacting with the unsaturated groups on the carbon. By applying x-ray photoelectron spectroscopy, it has been determined that bromine or HBr added to carbon black forms chemical compounds within a carbon structure.

A body of theory has been developed from scientific evidence to explain the nature of the promotion effect of the bromine compounds. This principle is illustrated in FIG. 2, which in step 1 shows the reaction of the hydrogen bromide with the unsaturated structure of the activated carbon. This may be a carbene species on the edge of the graphene sheets structures of the carbon. Molecular bromine or a bromine compound reacts to form a similar structure, with a positive carbon that is active for oxidizing the mercury.

We now teach that the formation of the new bromide compound with carbon increases the reactivity of the carbon forms toward mercury and other pollutants. The resulting bromide compound is uniquely suited to facilitate oxidation of the mercury. The effectiveness of the oxidation results from the promotion effect of the halide exerted on the developing positive charge on the mercury during the

oxidation, known in the chemical art as a specific catalytic effect. Thus, as the mercury electrons are drawn toward the positive carbon, the halide anion electrons are pushing in from the other side, which stabilizes the positive charge developing on the mercury and lowers the energy requirement for the oxidation process.

- 5 Bromide is especially reactive, owing to the highly polarizable electrons in the outer 4p orbitals of the ion. Thus, adding HBr or Br₂ to the carbon forms a similar carbon bromide, in which the positive carbon oxidizes the mercury with the assistance of the bromide ion.

10 Prior Art Publications

The earliest patents that relate to mercury capture on a sorbent are actually not for flue gas mercury control but for capture of mercury from air or other gas mixtures on a carbon or other sorbent. These patents were based on a model that recognized the affinity of halogens for mercury, rather than the formation of a
15 reactive carbon. These patents are discussed below according to the type of halogen used for impregnation.

One patent that teaches a halogen impregnation (Stock, U.S. Patent 1,984,164, issued in 1934) describes the use of activated carbon or other solid impregnated with a halogen for removing Hg from air. The impregnation method is
20 not specified. This seems to be the most general claim with respect to halogen impregnation. All the statements and claims appear to refer to halogen or iodine, but the patent does not appear to address bromides or other halides or bromide compounds or even specifically iodide or an iodine compound. The only example in the description is iodine impregnation. The patent also is restricted to air systems
25 and did not pertain to flue gas systems with reactive acid gases. The description did not assume that the iodine formed a reactive carbon species.

Japanese Patent JP 49-43197 describes the treatment of Hg-contaminated electrolysis cell gas using a metal iodide salt on a support. A similar treatment using a resin impregnated with a metal iodide is described in JP 50-6438. These patents do
30 not appear to represent a carbon bromide compound as specified in this patent application.

Another early patent (Hilgen, U.S. Patent 3,849,267, issued in 1974) describes a method for Hg removal from a gas which claims mixing molecular chlorine (Cl_2) with the gas to be cleaned and passing it through a nonporous sorbent such as glass wool and NaCl (not carbon). This was evidently not an obvious
5 extension of the Stock patent, since a halogen was introduced as part of the gas phase being cleaned.

A later patent (deJong, et al., U.S. Patent 4,196,173, issued in 1980) describes a method for Hg removal in air which claims using a bed of activated carbon impregnated with halogen-only Cl_2 is specified in the other claims and
10 examples, and it is prepared by flowing the Cl_2 stream through a carbon bed.

An improved sorbent for mercury in air was patented by Revoir and Jones (U.S. Patent 3662523, issued in 1972), in which ICl and ICl_3 vapors were impregnated into the activated carbon. No explanation of the increased activity was provided. Since these compounds are interhalogen compounds, the patent did not
15 infringe Stock.

U.S. Patent 5,891,324 describes an activated carbon containing an acid (HCl , H_2SO_4 , or H_3PO_4) for the removal of mercury contained in a liquid phase, such as would occur in a process steam in the oil industry. In this case, the model presented was that mercury is adsorbed from the liquid into the solid carbon phase at relatively
20 low temperatures.

In U.S. Patent Application 2004/0003716, a method is described for removing mercury from a combustion gas. This method employs an exposure of a finely powdered activated carbon to a molecular bromine gas at an elevated temperature or to HBr to produce a sorbent with good mercury removal ability when
25 injected into the flue gas duct. The model for the efficacy of the Nelson sorbent is not clearly stated, so it can be presumed that the reasoning for using bromine is the simple premise that some bromine form will help capture the mercury, as does iodine and chlorine. The methods for incorporation of the bromine in the Nelson application are not the same as with the present invention, and the Nelson method
30 will not produce the identical carbon bromide species that are obtained in the art described in this application. The Nelson method lacks many of the features

described in this application that impart exceptional activity to the sorbent in a convenient way, for example, the addition of smaller amount of a second more powerful promoting agent, the use of facile solvent systems, including aqueous bromine, and the use of in-flight bromine treatment. Additionally, the patent
5 application does not mention regeneration, recycling, or reuse, or the use of moving contactors or larger particle size to facilitate sorbent-ash separation.

Embodiments of the Invention.

A sorbent that is initially very reactive in oxidizing mercury can be used in
10 very small amounts to achieve high capture efficiencies, thus lowering operation costs and lessening the disposal problem. In addition, further disposal reduction is made possible by recycling and reusing the sorbent that is produced using this technology. The time interval for the mercury and sorbent to interact in a flue gas duct and the subsequent collection of the mercury on the sorbent and ash may be
15 very short- only seconds. This requires the sorbent to have high capacity and be very reactive toward mercury. A sorbent can be utilized in a very finely powdered form (e.g., 1-10 μm) to minimize mass transfer limitations. But, again, the reactivity should be very high to capture all of the mercury encountered by the fine particles. One feature of this invention is the process to prepare a sorbent containing a
20 bromide compound formed on the carbon structure that provides a sorbent that is highly active on initial contact with the mercury contaminated gas stream, which allows for effective capture of the mercury.

One possible way to do this is to chemically combine molecular bromine from solution with activated carbon (edge sites). X-ray photoelectron spectroscopy
25 established that the addition of bromine formed a chemical compound in the carbon structure. Thus, the sorbent does not represent a molecular bromine halogen form but a new chemically modified carbon structure. This may not occur with the less reactive iodine, where an I_2 - molecular complex can exist on the carbon basal plane. In the bromine case, it is actually the carbon that oxidizes the mercury. Thus, an
30 entirely new model is presented for the reactivity of the bromine-treated carbon with mercury. The reactive carbon form can be generated by the addition of bromine,

hydrogen bromide, or combinations of bromine and other elements as described herein. Chlorine treatment resulted in lower-activity carbons because the chloride anion was less effective in promoting the oxidation by stabilizing the developing positive charge on the mercury in the transition state for oxidation. Based on this model, several innovative, inexpensive, activity-enhancing features have been developed.

It has been demonstrated that addition of an optional second component, in addition to the bromine, results in improved reactivity and capacity for the sorbent, exceeding that of both the untreated carbon and the brominated carbon. The second compound comprises either a second halogen or a compound from a second halogen, such as HBr. Thus, in addition to having a reactive carbon form present, the second component generates a Lewis base with greater ability to stabilize the developing positive charge on the mercury. Thus the second component is an element with more polarized electrons (4p and 5p).

Furthermore, we demonstrated that the sorbent can be readily treated with any combination of bromine and the second component in-flight using vapors of these components contacting the very fine carbon particles dispersed in air or other gas stream that conveys the particles to the flue gas duct. There is no particular temperature requirement for this contact. This technology is very simple to implement, so it will result in a great cost savings to the utility using this technology for mercury capture.

A unique, nonobvious technique for preparation of the treated carbon is through combining the treatment system with the carbon injection system at the end-use site. With this technique, the halogen is introduced to the carbon-air mixture in the transport line (or other part of the sorbent storage and injection system). Benefits over current concepts to treat sorbents off-site include the following:

- Capital equipment costs at a treatment facility are eliminated.
- Costs to operate the treatment facility are eliminated.
- There are no costs for transporting carbon and additive to a treatment facility.
- This process uses existing hardware and operation procedures.

- This technology ensures that the sorbent is always fresh, and thus, more reactive.
- No new handling concerns are introduced.
- There are no costs for removing carbon from treatment system.
- This process allows rapid on-site tailoring of additive-sorbent ratios in order to match the requirements of flue gas changes, such as needed when changing fuels or reducing loads, thus further optimizing the economics.
- This technology reduces the amount of spent sorbents that are disposed.

With the foregoing and other features in view, there is provided, in accordance with the invention, a process for preparing and regenerating carbon sorbents whose activity for mercury capture is promoted by the addition of bromine to the carbon structure.

The invention applies to use of a sorbent in a powdered form that has been injected into a flue gas stream before or after ash particulates have been removed. Examples of the composition of the sorbent are a powdered modified activated carbon prepared by adding Br₂ or HBr plus a second optional component. Alternatively, the sorbent is on a moving contactor consisting of particles or fibers containing the compositions listed in the previous sentence. Either type can be regenerated; the poisoning contaminants from the flue gas are removed and an inexpensive promoting agent added to restore mercury sorption activity. This process of promoting the activity of the carbon itself contrasts with the earlier, more expensive art of adding a reagent (such as peroxide, gold, triiodide, etc.) to the sorbent. The activated carbon sorbent treated with bromine and/or the other components is noncorrosive.

Detailed examples of sorbent regeneration techniques are described in co-pending, commonly-owned PCT patent application No. PCT/US04/12828, titled "PROCESS FOR REGENERATING A SPENT SORBENT", which is incorporated by reference herein.

Although the invention is described herein as a sorbent material, it is nevertheless not intended to be limited to the details described, since various modifications and structural changes may be made therein without departing from

the spirit of the invention and within the scope and range of equivalents of the claims.

The construction and method of operation of the invention, however, together with additional objects and advantages thereof will be best understood from the following description of specific exemplary embodiments.

FIG. 11 is a block diagram illustrating the use of the invention in a coal fueled facility. Of course, the invention can also be used in any other desired type of facility. FIG. 11 shows a boiler for burning pulverized coal. The facility utilizes various devices to clean the exhaust of the boiler. In this example, a baghouse or ESP is used to collect particulates in the exhaust. A scrubber and sorbent bed are also used to remove undesired constituents from the flue gas stream, before being fed to the stack. In the example shown, the sorbent is injected into the flue gas after the boiler. The additive can be injected where desired (e.g., before, after, or within the boiler).

Another advantage of the present invention relates to the use of a feedback system to more efficiently utilize the invention. Where possible, the mercury control technology of the present invention will utilize measurement of mercury emissions as feedback to assist in control of the sorbent injection rate. Tighter control on the sorbent levels in this way will ensure mercury removal requirements are met with the minimal sorbent requirements and therefore the associated costs will be minimized. In one example, the emissions are measured at the stack.

Carbon Sorbent

Reactions of halogens and acidic species with the basic binding sites on the activated carbon sorbent create sites for oxidizing mercury. Other metal ions, such as boron, tin, arsenic, gallium, Sb, Pb, Bi, Cd, Ag, Cu, Zn, or other contaminants, will also react with the oxidation sites generated on the carbon.

According to our model, adding the bromine from the bromine reagent or a proton from a hydrogen halide acid to a basic carbene site on the carbon edge structure forms a carbocation that accept electrons from the neutral mercury atom forming the oxidized mercury species that is bound to the sorbent surface. The

reactive site may also generate reactive bromine radicals or carbon radicals at the active sites on the carbon. Thus, the activated carbon serves to stabilize the bromine, yet provides a highly reactive bromine- containing reagent that can oxidize the mercury and promote its capture on the activated carbon. The sorbent that contains
5 bromine is expected to be more reactive than the corresponding sorbent containing chlorine and much less expensive than the sorbent containing iodine.

A bench-scale procedure based on the above description was used to test the initial activities and capacities of several powdered carbon sorbents, including the bromine-containing activated carbons prepared from a commercially available
10 sorbent and an aerogel carbon film sorbent, as well as the original precursor carbons for comparison. Bromine-treated carbons were prepared by impregnation of the powdered activated carbon precursors in a stirred solution of bromine in carbon tetrachloride or methylene chloride, or alternatively, in an aqueous solution of HBr, followed by drying in air at ambient temperature and drying in an oven at 100°C in
15 air or nitrogen. Bromine-treated carbons were also prepared by impregnating bromine from the gas phase by passing the gas through a rotating dry bed of the activated carbon precursor. Adding a second component to the solution was demonstrated to improve the capacity of the sorbent.

The carbons were initially tested in a heated bed, where a synthetic flue gas
20 stream containing elemental mercury ($11 \mu\text{g}/\text{m}^3$) was passed through the bed. Concentrations of total and elemental Hg in the effluent gas were determined using a Sir Galahad mercury CEM. The powdered sorbent was supported on a quartz filter during the test, and the other sorbents were tested as a triple layer.

A comparison of the original commercial-grade powdered carbon sorbent
25 with the sorbent after it has been treated with 0.1 N HBr, collecting the powder by centrifugation and drying, revealed that the mercury capture activity is increased from an initial capture efficiency of about 50% of the Hg in the inlet to 100% capture. A comparison of the sorbent after subsequent regeneration with HBr indicates that it not only captures mercury at the same level as before (100%
30 capture) but is enhanced such that its capacity is prolonged by several minutes.

Similar results were obtained with the carbon film and carbon fiber sorbents by treatment with molecular bromine in solution or in dry beds as described above.

An activated carbon sorbent was prepared by treating the carbon by impregnating molecular bromine from a gas composition containing molecular bromine by flowing the gas through a liquid bromine reservoir in series with a fluidized bed of ebullated bed of the carbon. The amount of bromine taken up by the carbon ranges (in one example) from <1 to about 30 g per 100 g of activated carbon, depending on the proportions used.

In one exemplary test conducted at a facility fired with lignite coal, the flue gas phase mercury (elemental) concentration was between 10 and 11 $\mu\text{g}/\text{m}^3$. The ash and injected carbons were collected in the baghouse at 350E to 375EF. Injection of commercial-grade activated carbon powder (untreated) at a rate of 1.0 lb/Macf resulted in mercury effluent concentrations of 3.8-4.2 $\mu\text{g}/\text{m}^3$ (representing 62%-58% removal of the mercury from the gas), and at 2.0 lb/Macf, gave 74%-71% removal. Injection of the bromine-treated carbon at 1.0 lb/Macf resulted in 73%-69% removal and at 2.0 lb/Macf gave 86%-84% removal. Thus, a significant increase in the mercury capture was exhibited during use of the bromine-treated carbon.

Addendum: Other References to Hg Sorption

20 *Sorbent Beds with Particulate Removal*

Carbon beds have also been utilized for mercury capture in flue gas. The German Patent 34 26 059 describes the use of a very thick carbon bed for treatment of flue gases containing polyhalogenated compounds. Although the system employed at Dusseldorf would also have the potential for Hg removal (for example, see the Streng reference), it is not very practical to use such a thick bed. Spent sorbent is burned and not regenerated. The carbons are not pretreated.

The GE-Mitsui-BF system (Tsuji, K.; Shiraishi, I.; Dague, R.F. Proceedings, Sixth International Symposium, Air & Water Management Assoc., New Orleans, LA, March 10-12, 1993) employs a recirculating carbon bed, where mercury is removed along with acid gases (as ammonium salts) and the carbon is regenerated at high temperatures where ammonium sulfate is decomposed to SO_2 and N_2 and

mercury is converted to the elemental form, which desorbs from the sorbent. Attrition of the sorbent results in a significant sorbent cost. The carbons are not pretreated.

5 *Sorbent Injection After Particulate Removal*

A process of injecting manganese oxide sorbent particles is described in U.S. Patent Application 2002/0150516. Regeneration is claimed by removal of spent oxide particles from the reaction zone and rinsing with dilute aqueous acid.

10 *Sorbent Beds After Particulate Removal*

Of particular interest in designing a mercury control process is to use the sorbent downstream of a particulate control device so the sorbent is not highly diluted with the ash particles. The sorbent could then be more easily regenerated and recycled. The prior art teaches several examples of this type of configuration and sorbent processing.

15 U.S. Patent 5,607,496 teaches the oxidation of mercury on a metal oxide sorbent bed and subsequent absorption to sorbent. The sorbent bed follows the particulate-removal equipment and, thus, the gas still contains the SO_x and NO_x, which react with the metal oxide sorbent to form the metal sulfates, which poison the bed. High temperatures are proposed to regenerate the bed. However, Hg is only partially removed from the sorbent at temperatures up to 500°C. The sorbents do not work effectively after regeneration using this technique; the problem may be that manganese sulfate formed during the sorption cycle does not completely decompose back to an active manganese oxide form.

20 U.S. Patent 6,383,981 describes a fixed MnO₂ or Fe₂O₃ bed for removal of Hg from a hydrocarbon stream. No regeneration method appears to be included.

A recent U.S. Patent application (2001/0003116) describes the regeneration of a plate or honeycomb material composed of transition metal oxides that was used for sorption of mercury in flue gas. The claimed process involves heating the sorbent in a reducing gas stream to remove poisons, followed by impregnation with a polyfunctional complex-forming reagent containing the catalyst active component

30

to restore mercury capture capacity. The first of these steps can remove the mercury, but it is unclear whether it actually removes the sulfate poison. The second of these steps is rather expensive, because one is actually reconstituting the reagent on the sorbent

5 Porous beds containing a mercury oxidizing reagent on a solid support are described in several patents for removal of mercury from gas streams. These include peroxomonosulfate (for example, see U.S. Patent 4,786,483), triiodide or other mixed halogens (for example, see U.S. Patents 3,194,629; 3,662,523), or sulfur (for example, see U.S. Patents 3,194,629, 4,101,631, 4,708,853, 6,258,334). The reagent
10 material is destroyed either by reaction with the flue gas during sorption or by attempts to regenerate the sorbent; there is no way to regenerate these sorbents, except by reimpregnation of the expensive reagent.

Amalgamating noble metals (gold, silver) on a suitable support can be regenerated by microwave heating (for example, see U.S. Patent 6,136,072), but
15 they are expensive and not especially active for sorption in flue gas.

Hg Sorbents for Air or Natural Gas Treatment

Melkersson (U.S. Patent 3786619) described a Hg sorbent comprising SeO_2 or SeS_2 for air treatment. This method did not appear to employ a carbon support or
20 halide.

Yan (U.S. Patent 4814152) described a Hg sorbent comprising elemental sulfur and a metal catalyst on a carbon support. This method did not appear to employ a halide.

Attia (U.S. Patent 65080281) described a sorbent for mercury and a variety
25 of other contaminants comprising an inorganic aerogel composition. This method did not appear to employ a carbon support or halide.

Following is a List of Various Background References:

Lancia, A.; Musmarra, D.; Pepe, F.; Volpicelli, G. *Combust. Sci. & Technol.*
30 1993, 93, 277.

Streng, S.; Kassebohm, B. *Fuel Proc. Technol.* 1994, 39, 431.

U.S. Patent 6,214,304 Rosenthal
 U.S. Patent 4,889,698 Moller
 U.S. Patent 4,956,162 Smith
 U.S. Patent 5,672,323 Bhat.
 5 U.S. Patent 5,827,352 Altman
 U.S. Patent 6,027,551 Hwang
 U.S. Patent 5,505,766 Chang
 U.S. Patent 5,607,496 Brooks
 U.S. Patent 6,383,981 Blankenship
 10 U.S. Patent 4,786,483 Audeh
 U.S. Patent 3,194,629 Dreibelbis, et al
 U.S. Patent 4,101,631 Ambrosini, et al
 U.S. Patent 3,662,523 Revoir
 U.S. Patent 4,708,853 Matviya
 15 U.S. Patent 6,258,334 Gadkaree
 U.S. Patent 6,136,072 Sjostrom
 U.S. Patent Application 2002/0150516
 U.S. Patent Application 2001/0003116 Neufert

CLAIMS

1. A method for reducing mercury in a mercury-containing gas, the method comprising:
 - 5 injecting a sorbent into the mercury-containing gas;
 - collecting mercury in the mercury-containing gas on the sorbent to produce a cleaned gas, wherein the sorbent is a promoted activated carbon that is promoted in-flight with at least one promoter that is Br_2 , HBr , Br^- , or a combination thereof, wherein the mercury-containing gas is a coal-combustion gas.
- 10 2. The method of claim 1, wherein the coal that is combusted comprises the promoter or a precursor thereof.
3. The method of claim 2, further comprising combusting the coal that
- 15 comprises the promoter or the precursor thereof.
4. The method of claim 1, wherein the promoted activated carbon is promoted with the promoter while the promoter is in the gas phase or is a vapor.
- 20 5. The method of claim 1, further comprising promoting the activated carbon in-flight.
6. The method of claim 1, wherein the promoted activated carbon comprises active sites, comprising halide anions bound to the activated carbon.
- 25 7. The method of claim 1, wherein the promoted activated carbon comprises active sites comprising carbocations bound to halide anions.
8. The method of claim 1, wherein collecting the mercury comprises
- 30 chemically reacting carbene species edge sites in the activated carbon with the mercury.

9. The method of claim 1, further comprising injecting an alkaline sorbent into the mercury-containing gas stream.
10. The method of claim 9, wherein the alkaline sorbent is selected from the group consisting of alkali elements, alkaline earth elements, alkali salts, alkaline earth salts, and combinations thereof.
11. The method of claim 9, wherein the alkaline sorbent is selected from the group consisting of sodium carbonate, calcium oxide, lime, and combinations thereof.
12. The method of claim 1, wherein the activated carbon is chosen from powdered activated carbon, granular activated carbon, carbon black, carbon fiber, aerogel carbon, pyrolysis char, and combinations thereof.
13. The method of claim 1, wherein the promoter is HBr or Br⁻.
14. The method of claim 1, wherein the mercury-containing gas is a flue gas stream downstream of a boiler furnace.
15. The method of claim 1, wherein monitoring the mercury content of the cleaned gas is performed substantially continuously.
16. The method of claim 1, wherein the sorbent has a composition comprising from about 1 to about 30 grams of promoter per 100 grains of activated carbon.
17. The method of claim 1, further comprising injecting sorbent into the mercury-containing gas stream to form the promoted activated carbon.
18. The method of claim 1, comprising collecting greater than 70 wt% of the mercury in the mercury-containing gas.

19. The method of claim 1, comprising collecting greater than 70 wt% of the mercury in the mercury-containing gas on the sorbent.
- 5 20. The method of claim 1, wherein the method is a method for reducing mercury in the mercury-containing gas to a desired level, the method further comprising:
- monitoring the mercury content of the cleaned gas; and
 - controlling, in response to the monitored mercury content of the cleaned gas,
- 10 an injection rate of injecting the sorbent into the mercury-containing gas, the sorbent composition, or a combination thereof, so that the mercury content of the cleaned gas is maintained at or below the desired level.

Abstract

A promoted activated carbon sorbent is described that is highly effective for the removal of mercury from flue gas streams. The sorbent comprises a new
5 modified carbon form containing reactive forms of halogen and halides. Optional components may be added to increase reactivity and mercury capacity. These may be added directly with the sorbent, or to the flue gas to enhance sorbent performance and/or mercury capture. Mercury removal efficiencies obtained exceed conventional methods. The sorbent can be regenerated and reused. Sorbent treatment and
10 preparation methods are also described. New methods for in-flight preparation, introduction, and control of the active sorbent into the mercury contaminated gas stream are described.

1/11




FIG. 1

2/11




FIG. 2

3/11




FIG. 3

4/11




FIG. 4

5/11




FIG. 5

6/11




FIG. 6

7/11




FIG. 7

8/11




FIG. 8

9/11




FIG. 9

10/11




FIG. 10

11/11




FIG. 11

Electronic Patent Application Fee Transmittal				
Application Number:				
Filing Date:				
Title of Invention:		SORBENTS FOR THE OXIDATION AND REMOVAL OF MERCURY		
First Named Inventor/Applicant Name:		Edwin S. Olson		
Filer:		John I. Fischer/Allison Johnson		
Attorney Docket Number:		4820.001US10		
Filed as Large Entity				
Filing Fees for Track I Prioritized Examination - Nonprovisional Application under 35 USC 111(a)				
Description	Fee Code	Quantity	Amount	Sub-Total in USD(\$)
Basic Filing:				
UTILITY APPLICATION FILING	1011	1	300	300
UTILITY SEARCH FEE	1111	1	660	660
UTILITY EXAMINATION FEE	1311	1	760	760
REQUEST FOR PRIORITIZED EXAMINATION	1817	1	4000	4000
Pages:				
Claims:				
Miscellaneous-Filing:				
PROCESSING FEE, EXCEPT PROV. APPLS.	1830	1	140	140

Description	Fee Code	Quantity	Amount	Sub-Total in USD(\$)
Petition:				
Patent-Appeals-and-Interference:				
Post-Allowance-and-Post-Issuance:				
Extension-of-Time:				
Miscellaneous:				
Total in USD (\$)				5860

Electronic Acknowledgement Receipt

EFS ID:	32797267
Application Number:	15997091
International Application Number:	
Confirmation Number:	5161
Title of Invention:	SORBENTS FOR THE OXIDATION AND REMOVAL OF MERCURY
First Named Inventor/Applicant Name:	Edwin S. Olson
Customer Number:	21186
Filer:	John I. Fischer/Allison Johnson
Filer Authorized By:	John I. Fischer
Attorney Docket Number:	4820.001US10
Receipt Date:	04-JUN-2018
Filing Date:	
Time Stamp:	15:40:52
Application Type:	Utility under 35 USC 111(a)

Payment information:

Submitted with Payment	yes
Payment Type	DA
Payment was successfully received in RAM	\$5860
RAM confirmation Number	060518INTEFSW00002452190743
Deposit Account	
Authorized User	
The Director of the USPTO is hereby authorized to charge indicated fees and credit any overpayment as follows:	

File Listing:					
Document Number	Document Description	File Name	File Size(Bytes)/ Message Digest	Multi Part /.zip	Pages (if appl.)
1		4820_001US10_Application_Track1-signed.pdf	4840628	yes	85
			dc5330a44c857339508a49b91d79509354c4a246		
	Multipart Description/PDF files in .zip description				
	Document Description		Start	End	
	Transmittal of New Application		1	1	
	Application Data Sheet		2	9	
	Oath or Declaration filed		10	12	
	TrackOne Request		13	13	
	Specification		14	70	
	Claims		71	73	
	Abstract		74	74	
	Drawings-only black and white line drawings		75	85	
Warnings:					
Information:					
2	Fee Worksheet (SB06)	fee-info.pdf	38374	no	2
			efe4816605019ac6e17f22a328c9d91acf875c27		
Warnings:					
Information:					
Total Files Size (in bytes):			4879002		

This Acknowledgement Receipt evidences receipt on the noted date by the USPTO of the indicated documents, characterized by the applicant, and including page counts, where applicable. It serves as evidence of receipt similar to a Post Card, as described in MPEP 503.

New Applications Under 35 U.S.C. 111

If a new application is being filed and the application includes the necessary components for a filing date (see 37 CFR 1.53(b)-(d) and MPEP 506), a Filing Receipt (37 CFR 1.54) will be issued in due course and the date shown on this Acknowledgement Receipt will establish the filing date of the application.

National Stage of an International Application under 35 U.S.C. 371

If a timely submission to enter the national stage of an international application is compliant with the conditions of 35 U.S.C. 371 and other applicable requirements a Form PCT/DO/EO/903 indicating acceptance of the application as a national stage submission under 35 U.S.C. 371 will be issued in addition to the Filing Receipt, in due course.

New International Application Filed with the USPTO as a Receiving Office

If a new international application is being filed and the international application includes the necessary components for an international filing date (see PCT Article 11 and MPEP 1810), a Notification of the International Application Number and of the International Filing Date (Form PCT/RO/105) will be issued in due course, subject to prescriptions concerning national security, and the date shown on this Acknowledgement Receipt will establish the international filing date of the application.



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NUMBER	FILING or 371(c) DATE	GRP ART UNIT	FIL FEE REC'D	ATTY. DOCKET NO	TOT CLAIMS	IND CLAIMS
15/997,091	06/04/2018	1736	1720	4820.001US10	20	1

CONFIRMATION NO. 5161

FILING RECEIPT



0000000100490378

21186

SCHWEGMAN LUNDBERG & WOESSNER, P.A.

P.O. BOX 2938

MINNEAPOLIS, MN 55402

Date Mailed: 06/26/2018

Receipt is acknowledged of this non-provisional patent application. The application will be taken up for examination in due course. Applicant will be notified as to the results of the examination. Any correspondence concerning the application must include the following identification information: the U.S. APPLICATION NUMBER, FILING DATE, NAME OF APPLICANT, and TITLE OF INVENTION. Fees transmitted by check or draft are subject to collection. Please verify the accuracy of the data presented on this receipt. **If an error is noted on this Filing Receipt, please submit a written request for a Filing Receipt Correction. Please provide a copy of this Filing Receipt with the changes noted thereon. If you received a "Notice to File Missing Parts" for this application, please submit any corrections to this Filing Receipt with your reply to the Notice. When the USPTO processes the reply to the Notice, the USPTO will generate another Filing Receipt incorporating the requested corrections**

Inventor(s)

Edwin S. Olson, Grand Forks, ND;
Michael J. Holmes, Thompson, ND;
John H. Pavlish, East Grand Forks, MN;

Applicant(s)

Midwest Energy Emissions Corp, Lewis Center, OH;

Power of Attorney: None

Domestic Priority data as claimed by applicant

This application is a CON of 15/974,343 05/08/2018
which is a CON of 15/951,970 04/12/2018
which is a CON of 14/712,558 05/14/2015
which is a CON of 14/318,270 06/27/2014 PAT 9757689
which is a CON of 13/966,768 08/14/2013 PAT 8821819
which is a CON of 13/427,665 03/22/2012 PAT 8512655
which is a CON of 12/419,219 04/06/2009 PAT 8168147
which is a CON of 12/201,595 08/29/2008 ABN
which is a CON of 11/209,163 08/22/2005 PAT 7435286
which claims benefit of 60/605,640 08/30/2004

Foreign Applications for which priority is claimed (You may be eligible to benefit from the **Patent Prosecution Highway** program at the USPTO. Please see <http://www.uspto.gov> for more information.) - None.

Foreign application information must be provided in an Application Data Sheet in order to constitute a claim to foreign priority. See 37 CFR 1.55 and 1.76.

Permission to Access Application via Priority Document Exchange: Yes

Permission to Access Search Results: Yes

Applicant may provide or rescind an authorization for access using Form PTO/SB/39 or Form PTO/SB/69 as appropriate.

If Required, Foreign Filing License Granted: 06/21/2018

The country code and number of your priority application, to be used for filing abroad under the Paris Convention, is **US 15/997,091**

Projected Publication Date: 10/04/2018

Non-Publication Request: No

Early Publication Request: No
Title

SORBENTS FOR THE OXIDATION AND REMOVAL OF MERCURY

Preliminary Class

423

Statement under 37 CFR 1.55 or 1.78 for AIA (First Inventor to File) Transition Applications: No

PROTECTING YOUR INVENTION OUTSIDE THE UNITED STATES

Since the rights granted by a U.S. patent extend only throughout the territory of the United States and have no effect in a foreign country, an inventor who wishes patent protection in another country must apply for a patent in a specific country or in regional patent offices. Applicants may wish to consider the filing of an international application under the Patent Cooperation Treaty (PCT). An international (PCT) application generally has the same effect as a regular national patent application in each PCT-member country. The PCT process **simplifies** the filing of patent applications on the same invention in member countries, but **does not result** in a grant of "an international patent" and does not eliminate the need of applicants to file additional documents and fees in countries where patent protection is desired.

Almost every country has its own patent law, and a person desiring a patent in a particular country must make an application for patent in that country in accordance with its particular laws. Since the laws of many countries differ in various respects from the patent law of the United States, applicants are advised to seek guidance from specific foreign countries to ensure that patent rights are not lost prematurely.

Applicants also are advised that in the case of inventions made in the United States, the Director of the USPTO must issue a license before applicants can apply for a patent in a foreign country. The filing of a U.S. patent application serves as a request for a foreign filing license. The application's filing receipt contains further information and guidance as to the status of applicant's license for foreign filing.

Applicants may wish to consult the USPTO booklet, "General Information Concerning Patents" (specifically, the section entitled "Treaties and Foreign Patents") for more information on timeframes and deadlines for filing foreign patent applications. The guide is available either by contacting the USPTO Contact Center at 800-786-9199, or it can be viewed on the USPTO website at <http://www.uspto.gov/web/offices/pac/doc/general/index.html>.

For information on preventing theft of your intellectual property (patents, trademarks and copyrights), you may wish to consult the U.S. Government website, <http://www.stopfakes.gov>. Part of a Department of Commerce initiative, this website includes self-help "toolkits" giving innovators guidance on how to protect intellectual property in specific countries such as China, Korea and Mexico. For questions regarding patent enforcement issues, applicants may call the U.S. Government hotline at 1-866-999-HALT (1-866-999-4258).

LICENSE FOR FOREIGN FILING UNDER
Title 35, United States Code, Section 184
Title 37, Code of Federal Regulations, 5.11 & 5.15

GRANTED

The applicant has been granted a license under 35 U.S.C. 184, if the phrase "IF REQUIRED, FOREIGN FILING LICENSE GRANTED" followed by a date appears on this form. Such licenses are issued in all applications where the conditions for issuance of a license have been met, regardless of whether or not a license may be required as set forth in 37 CFR 5.15. The scope and limitations of this license are set forth in 37 CFR 5.15(a) unless an earlier license has been issued under 37 CFR 5.15(b). The license is subject to revocation upon written notification. The date indicated is the effective date of the license, unless an earlier license of similar scope has been granted under 37 CFR 5.13 or 5.14.

This license is to be retained by the licensee and may be used at any time on or after the effective date thereof unless it is revoked. This license is automatically transferred to any related applications(s) filed under 37 CFR 1.53(d). This license is not retroactive.

The grant of a license does not in any way lessen the responsibility of a licensee for the security of the subject matter as imposed by any Government contract or the provisions of existing laws relating to espionage and the national security or the export of technical data. Licensees should apprise themselves of current regulations especially with respect to certain countries, of other agencies, particularly the Office of Defense Trade Controls, Department of State (with respect to Arms, Munitions and Implements of War (22 CFR 121-128)); the Bureau of Industry and Security, Department of Commerce (15 CFR parts 730-774); the Office of Foreign Assets Control, Department of Treasury (31 CFR Parts 500+) and the Department of Energy.

NOT GRANTED

No license under 35 U.S.C. 184 has been granted at this time, if the phrase "IF REQUIRED, FOREIGN FILING LICENSE GRANTED" DOES NOT appear on this form. Applicant may still petition for a license under 37 CFR 5.12, if a license is desired before the expiration of 6 months from the filing date of the application. If 6 months has lapsed from the filing date of this application and the licensee has not received any indication of a secrecy order under 35 U.S.C. 181, the licensee may foreign file the application pursuant to 37 CFR 5.15(b).

SelectUSA

The United States represents the largest, most dynamic marketplace in the world and is an unparalleled location for business investment, innovation, and commercialization of new technologies. The U.S. offers tremendous resources and advantages for those who invest and manufacture goods here. Through SelectUSA, our nation works to promote and facilitate business investment. SelectUSA provides information assistance to the international investor

community; serves as an ombudsman for existing and potential investors; advocates on behalf of U.S. cities, states, and regions competing for global investment; and counsels U.S. economic development organizations on investment attraction best practices. To learn more about why the United States is the best country in the world to develop technology, manufacture products, deliver services, and grow your business, visit <http://www.SelectUSA.gov> or call +1-202-482-6800.

PATENT APPLICATION FEE DETERMINATION RECORD Substitute for Form PTO-875						Application or Docket Number 15/997,091	
APPLICATION AS FILED - PART I							
(Column 1)		(Column 2)		SMALL ENTITY		OTHER THAN SMALL ENTITY	
FOR	NUMBER FILED	NUMBER EXTRA	RATE(\$)	FEE(\$)		RATE(\$)	FEE(\$)
BASIC FEE (37 CFR 1.16(a), (b), or (c))	N/A	N/A	N/A			N/A	300
SEARCH FEE (37 CFR 1.16(k), (l), or (m))	N/A	N/A	N/A			N/A	660
EXAMINATION FEE (37 CFR 1.16(o), (p), or (q))	N/A	N/A	N/A			N/A	760
TOTAL CLAIMS (37 CFR 1.16(i))	20	minus 20 = *			OR	x 100 =	0.00
INDEPENDENT CLAIMS (37 CFR 1.16(h))	1	minus 3 = *				x 460 =	0.00
APPLICATION SIZE FEE (37 CFR 1.16(s))	If the specification and drawings exceed 100 sheets of paper, the application size fee due is \$310 (\$155 for small entity) for each additional 50 sheets or fraction thereof. See 35 U.S.C. 41(a)(1)(G) and 37 CFR 1.16(s).						0.00
MULTIPLE DEPENDENT CLAIM PRESENT (37 CFR 1.16(j))							0.00
* If the difference in column 1 is less than zero, enter "0" in column 2.			TOTAL			TOTAL	1720
APPLICATION AS AMENDED - PART II							
(Column 1)		(Column 2)		(Column 3)		SMALL ENTITY	
AMENDMENT A	CLAIMS REMAINING AFTER AMENDMENT	HIGHEST NUMBER PREVIOUSLY PAID FOR	PRESENT EXTRA	RATE(\$)	ADDITIONAL FEE(\$)	OTHER THAN SMALL ENTITY	
	Total (37 CFR 1.16(i))	*	Minus **	=		RATE(\$)	ADDITIONAL FEE(\$)
	Independent (37 CFR 1.16(h))	*	Minus ***	=		RATE(\$)	ADDITIONAL FEE(\$)
	Application Size Fee (37 CFR 1.16(s))					OR	
	FIRST PRESENTATION OF MULTIPLE DEPENDENT CLAIM (37 CFR 1.16(j))					OR	
TOTAL ADD'L FEE						OR	TOTAL ADD'L FEE
(Column 1)		(Column 2)		(Column 3)		SMALL ENTITY	
AMENDMENT B	CLAIMS REMAINING AFTER AMENDMENT	HIGHEST NUMBER PREVIOUSLY PAID FOR	PRESENT EXTRA	RATE(\$)	ADDITIONAL FEE(\$)	OTHER THAN SMALL ENTITY	
	Total (37 CFR 1.16(i))	*	Minus **	=		RATE(\$)	ADDITIONAL FEE(\$)
	Independent (37 CFR 1.16(h))	*	Minus ***	=		RATE(\$)	ADDITIONAL FEE(\$)
	Application Size Fee (37 CFR 1.16(s))					OR	
	FIRST PRESENTATION OF MULTIPLE DEPENDENT CLAIM (37 CFR 1.16(j))					OR	
TOTAL ADD'L FEE						OR	TOTAL ADD'L FEE
<div style="font-size: x-small;"> * If the entry in column 1 is less than the entry in column 2, write "0" in column 3. ** If the "Highest Number Previously Paid For" IN THIS SPACE is less than 20, enter "20". *** If the "Highest Number Previously Paid For" IN THIS SPACE is less than 3, enter "3". The "Highest Number Previously Paid For" (Total or Independent) is the highest found in the appropriate box in column 1. </div>							



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
15/997,091	06/04/2018	Edwin S. Olson	4820.001US 10	5161
21186 7590 07/12/2018 SCHWEGMAN LUNDBERG & WOESSNER, P.A. P.O. BOX 2938 MINNEAPOLIS, MN 55402 UNITED STATES OF AMERICA			EXAMINER ORLANDO, AMBER ROSE	
			ART UNIT 1776	PAPER NUMBER
			NOTIFICATION DATE 07/12/2018	DELIVERY MODE ELECTRONIC

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Notice of the Office communication was sent electronically on above-indicated "Notification Date" to the following e-mail address(es):

uspto@slwip.com
SLW@blackhillsip.com



UNITED STATES PATENT AND TRADEMARK OFFICE

Commissioner for Patents
United States Patent and Trademark Office
P.O. Box 1450
Alexandria, VA 22313-1450
www.uspto.gov

Doc Code:
TRACK1.GRANT

<i>Decision Granting Request for Prioritized Examination (Track I or After RCE)</i>	Application No.:15/997,091
<p>1. THE REQUEST FILED <u>June 4, 2018</u> IS <u>GRANTED</u>.</p> <p>The above-identified application has met the requirements for prioritized examination</p> <p>A. ☒ for an original nonprovisional application (Track I).</p> <p>B. ☐ for an application undergoing continued examination (RCE).</p> <p>2. The above-identified application will undergo prioritized examination. The application will be accorded special status throughout its entire course of prosecution until one of the following occurs:</p> <p>A. filing a <u>petition for extension of time</u> to extend the time period for filing a reply;</p> <p>B. filing an <u>amendment to amend the application to contain more than four independent claims, more than thirty total claims</u>, or a multiple dependent claim;</p> <p>C. filing a <u>request for continued examination</u>;</p> <p>D. filing a notice of appeal;</p> <p>E. filing a request for suspension of action;</p> <p>F. mailing of a notice of allowance;</p> <p>G. mailing of a final Office action;</p> <p>H. completion of examination as defined in 37 CFR 41.102; or</p> <p>I. abandonment of the application.</p> <p>Telephone inquiries with regard to this decision should be directed to Kimberly Inabinet at 571-272-4618.</p> <p><i>/Kimberly Inabinet/</i> Paralegal Specialist, Office of Petitions</p>	

Office of Petitions: Routing Sheet



Application No.

This application is being forwarded to your office for further processing. A decision has been rendered on a petition filed in this application, as indicated below. For details of this decision, please see the document PET.OP.DEC filed on the same date as this document.

☒ **GRANTED**

☐ **DISMISSED**

☐ **DENIED**

Office of Petitions: Decision Count Sheet

Mailing Month

7

Application No.

15997091



For US serial numbers: enter number only, no slashes or commas. Ex: 10123456

For PCT: enter "51+single digit of year of filing+last 5 numbers", Ex. for PCT/US05/12345, enter 51512345

Deciding Official:

Kimberly Inabinet

Count (1) - Palm Credit

15997091

Decision:

GRANT

FINANCE WORK NEEDED

☐ Select Check Box for YES

Decision Type:

643 - Track One request



Notes:

Count (2)

Decision:

n/a

FINANCE WORK NEEDED

☐ Select Check Box for YES

Decision Type:

NONE

Notes:

Count (3)

Decision:

n/a

FINANCE WORK NEEDED

☐ Select Check Box for YES

Decision Type:

NONE

Notes:

Initials of Approving Official (if required)

If more than 3 decisions, attach
2nd count sheet & mark this box

Printed on: 7/9/2018

Office of Petitions Internal Document - Ver. 5.0



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
15/997,091	06/04/2018	Edwin S. Olson	4820.001US10	5161
21186 7590 07/27/2018 SCHWEGMAN LUNDBERG & WOESSNER, P.A. P.O. BOX 2938 MINNEAPOLIS, MINNESOTA 55402 UNITED STATES OF AMERICA			EXAMINER ORLANDO, AMBER ROSE	
			ART UNIT 1776	PAPER NUMBER
			NOTIFICATION DATE 07/27/2018	DELIVERY MODE ELECTRONIC

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Notice of the Office communication was sent electronically on above-indicated "Notification Date" to the following e-mail address(es):

SLW@blackhillsip.com
uspto@slwip.com

DETAILED ACTION

Notice of Pre-AIA or AIA Status

The present application is being examined under the pre-AIA first to invent provisions.

Claim Rejections - 35 USC § 102

In the event the determination of the status of the application as subject to AIA 35 U.S.C. 102 and 103 (or as subject to pre-AIA 35 U.S.C. 102 and 103) is incorrect, any correction of the statutory basis for the rejection will not be considered a new ground of rejection if the prior art relied upon, and the rationale supporting the rejection, would be the same under either status.

The following is a quotation of the appropriate paragraphs of pre-AIA 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless –

(e) the invention was described in (1) an application for patent, published under section 122(b), by another filed in the United States before the invention by the applicant for patent or (2) a patent granted on an application for patent by another filed in the United States before the invention by the applicant for patent, except that an international application filed under the treaty defined in section 351(a) shall have the effects for purposes of this subsection of an application filed in the United States only if the international application designated the United States and was published under Article 21(2) of such treaty in the English language.

Claim(s) 1, 4-14 and 16-19 is/are rejected under pre-AIA 35 U.S.C. 102(e) as being anticipated by Nelson US 2004/0003716.

For claim 1, the Nelson reference discloses a method for reducing mercury in a mercury-containing gas, the method comprising: injecting a sorbent into the mercury-containing gas (paragraph [0060]); collecting mercury in the mercury-containing gas on the sorbent to produce a cleaned gas (paragraph [0060]), wherein the sorbent is a promoted activated carbon that is promoted in flight with at least one promoter that is Br₂, HBr, Br⁻, or a combination thereof, wherein the mercury-containing gas is a coal-combustion gas (paragraphs [0048]-[0051]).

For claim 4, the Nelson reference discloses the promoted activated carbon is promoted with the promoter while the promoter is in the gas phase or is a vapor (paragraphs [0050] and [0051]).

For claim 5, the Nelson reference discloses promoting the activated carbon in-flight (paragraphs [0048]-[0051]).

For claim 6, the promoted sorbent as disclosed by Nelson above would include active sites, comprising halide anions bound to the activated carbon.

For claim 7, the promoted sorbent as disclosed by Nelson above would include active sites comprising carbocations bound to halide anions.

For claim 8, the sorbent being promoted and then contacted with the mercury containing gas and removed thereafter as disclosed by Nelson above is chemically and physically equivalent to the claimed collecting the mercury comprises chemically reacting carbene species edge sites in the activated carbon with the mercury.

For claim 9, the Nelson reference injecting an alkaline sorbent into the mercury-containing gas stream (paragraph [0064]).

For claim 10, the Nelson reference discloses alkaline sorbent is selected from the group consisting of alkali elements, alkaline earth elements, alkali salts, alkaline earth salts, and combinations thereof (paragraph [0064]).

For claim 11, the Nelson reference discloses the alkaline sorbent is selected from the group consisting of sodium carbonate, calcium oxide, lime, and combinations thereof (paragraph [0064]).

For claim 12, the Nelson reference discloses the activated carbon is chosen from powdered activated carbon, granular activated carbon, carbon black, carbon fiber, aerogel carbon, pyrolysis char, and combinations thereof (paragraph [0040]).

For claim 13, the Nelson reference discloses the promoter is HBr or Br (paragraphs [0048]-[0051]).

For claim 14, the Nelson reference discloses the mercury-containing gas is a flue gas stream downstream of a boiler furnace (fig. 2-6 and paragraph [0060]).

For claim 16, the Nelson reference discloses the sorbent material has a composition comprising from about 1 to about 30 grams of additive per 100 grams of activated carbon (paragraph [0054]).

For claim 17, the Nelson reference discloses injecting sorbent into the mercury-containing gas stream to form the promoted activated carbon (paragraphs [0048]-[0051]).

For claims 18 and 19, the Nelson reference discloses collecting greater than 70 wt% of the mercury in the mercury-containing gas (paragraph [0084]).

Claim Rejections - 35 USC § 103

In the event the determination of the status of the application as subject to AIA 35 U.S.C. 102 and 103 (or as subject to pre-AIA 35 U.S.C. 102 and 103) is incorrect, any correction of the statutory basis for the rejection will not be considered a new ground of rejection if the prior art relied upon, and the rationale supporting the rejection, would be the same under either status.

The following is a quotation of pre-AIA 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

The factual inquiries set forth in *Graham v. John Deere Co.*, 383 U.S. 1, 148 USPQ 459 (1966), that are applied for establishing a background for determining obviousness under pre-AIA 35 U.S.C. 103(a) are summarized as follows:

1. Determining the scope and contents of the prior art.
2. Ascertaining the differences between the prior art and the claims at issue.

3. Resolving the level of ordinary skill in the pertinent art.

4. Considering objective evidence present in the application indicating obviousness or nonobviousness.

This application currently names joint inventors. In considering patentability of the claims under pre-AIA 35 U.S.C. 103(a), the examiner presumes that the subject matter of the various claims was commonly owned at the time any inventions covered therein were made absent any evidence to the contrary. Applicant is advised of the obligation under 37 CFR 1.56 to point out the inventor and invention dates of each claim that was not commonly owned at the time a later invention was made in order for the examiner to consider the applicability of pre-AIA 35 U.S.C. 103(c) and potential pre-AIA 35 U.S.C. 102(e), (f) or (g) prior art under pre-AIA 35 U.S.C. 103(a).

Claim 2-3 is/are rejected under pre-AIA 35 U.S.C. 103(a) as being unpatentable over Nelson US 2004/0003716 as applied in claim 1 and further in view of Comrie US 2007/0168213.

For claim 2 the Nelson reference does not disclose the coal that is combusted comprises the promoter or a precursor thereof.

The Comrie reference discloses that the sorbent compositions can be added anywhere within the coal burning process, before, during or after (paragraph [0006]). This would include the promoter or a precursor thereof.

It would have been obvious to one having ordinary skill in the art before the invention was made to have modified the Nelson reference to include either rearranging steps, or repeat steps to have the combusting coal in the presence of the additive and activated carbon and comprising mixing the additive and the coal before combusting the coal so as to entrap the contaminants in the mercury containing gas rather than release them to the atmosphere which would include the promoter or a precursor thereof Nelson (Comrie paragraph [0006]). Further the courts have held that selection of any order of

performing process steps is prima facie obvious in the absence of new or unexpected results); In re Gibson, 39 F.2d 975, 5 USPQ 230.

For claim 3, the combination of Nelson and Comrie would include combusting the coal that comprises the promoter or the precursor thereof as both Nelson and Comrie disclose combusting the coal.

Claims 15 and 20 is/are rejected under pre-AIA 35 U.S.C. 103(a) as being unpatentable over Nelson US 2004/0003716 as applied in claim 1 and further in view of Vosteen et al. US 6,878,358.

For claim 15, the Nelson reference does not disclose monitoring the mercury content of the cleaned gas is performed substantially continuously.

The Vosteen reference discloses monitoring the mercury content of the cleaned gas is performed substantially continuously (column 5, lines 47-63).

It would have been obvious to one having ordinary skill in the art before the invention was made to have modified the Nelson reference to include monitoring the mercury content of the cleaned gas is performed substantially continuously (Vosteen column 5, lines 47-63) so as to allow for the maximum amount of mercury to be removed from the waste gas stream.

For claim 20, the Nelson reference discloses the method is a method for reducing mercury in the mercury-containing gas to a desired level (as shown above).

The Nelson reference does not disclose monitoring the mercury content of the cleaned gas; and controlling, in response to the monitored mercury content of the cleaned gas, an injection rate of injecting the sorbent into the mercury-containing gas, the sorbent composition, or a combination thereof, so that the mercury content of the cleaned gas is maintained at or below the desired level.

The Vosteen reference discloses monitoring the mercury content of the cleaned gas; and controlling, in response to the monitored mercury content of the cleaned gas, an injection rate of

injecting the sorbent into the mercury-containing gas, the sorbent composition, or a combination thereof, so that the mercury content of the cleaned gas is maintained at or below the desired level (column 5, lines 47-63).

It would have been obvious to one having ordinary skill in the art before the invention was made to have modified the Nelson reference to include monitoring the mercury content of the cleaned gas; and controlling, in response to the monitored mercury content of the cleaned gas, an injection rate of injecting the sorbent into the mercury-containing gas, the sorbent composition, or a combination thereof, so that the mercury content of the cleaned gas is maintained at or below the desired level (Vosteen column 5, lines 47-63) so as to allow for the maximum amount of mercury to be removed from the waste gas stream.

Double Patenting

The nonstatutory double patenting rejection is based on a judicially created doctrine grounded in public policy (a policy reflected in the statute) so as to prevent the unjustified or improper timewise extension of the “right to exclude” granted by a patent and to prevent possible harassment by multiple assignees. A nonstatutory double patenting rejection is appropriate where the conflicting claims are not identical, but at least one examined application claim is not patentably distinct from the reference claim(s) because the examined application claim is either anticipated by, or would have been obvious over, the reference claim(s). See, e.g., *In re Berg*, 140 F.3d 1428, 46 USPQ2d 1226 (Fed. Cir. 1998); *In re Goodman*, 11 F.3d 1046, 29 USPQ2d 2010 (Fed. Cir. 1993); *In re Longi*, 759 F.2d 887, 225 USPQ 645 (Fed. Cir. 1985); *In re Van Ornum*, 686 F.2d 937, 214 USPQ 761 (CCPA 1982); *In re Vogel*, 422 F.2d 438, 164 USPQ 619 (CCPA 1970); *In re Thorington*, 418 F.2d 528, 163 USPQ 644 (CCPA 1969).

A timely filed terminal disclaimer in compliance with 37 CFR 1.321(c) or 1.321(d) may be used to overcome an actual or provisional rejection based on nonstatutory double patenting provided the reference application or patent either is shown to be commonly owned with the examined application,

or claims an invention made as a result of activities undertaken within the scope of a joint research agreement. See MPEP § 717.02 for applications subject to examination under the first inventor to file provisions of the AIA as explained in MPEP § 2159. See MPEP §§ 706.02(I)(1) - 706.02(I)(3) for applications not subject to examination under the first inventor to file provisions of the AIA. A terminal disclaimer must be signed in compliance with 37 CFR 1.321(b).

The USPTO Internet website contains terminal disclaimer forms which may be used. Please visit www.uspto.gov/patent/patents-forms. The filing date of the application in which the form is filed determines what form (e.g., PTO/SB/25, PTO/SB/26, PTO/AIA/25, or PTO/AIA/26) should be used. A web-based eTerminal Disclaimer may be filled out completely online using web-screens. An eTerminal Disclaimer that meets all requirements is auto-processed and approved immediately upon submission. For more information about eTerminal Disclaimers, refer to www.uspto.gov/patents/process/file/efs/guidance/eTD-info-I.jsp.

Claims 1- rejected on the ground of nonstatutory double patenting as being unpatentable over claims 1-3, 13, 22 and 26 of U.S. Patent No. 7,435,286 ('286).

Claim 1 of the current application corresponds to claim claims 1 of '286.

Claim 4 of the current application corresponds to claim claims 1 and 13 of '286.

Claim 5 of the current application corresponds to claim claims 1 and 13 of '286.

Claims 6-8 of the current application corresponds to claim claims 1 of '286.

Claim 9-11 of the current application corresponds to claim claims 1-3 of '286.

Claim 13 of the current application corresponds to claim claims 1 and 23 of '286.

Claim 14 of the current application corresponds to claim claims 1 of '286.

Claim 15 of the current application corresponds to claim claims 1 and 22 of '286.

Claim 16 of the current application corresponds to claim claims 1 and 26 of '286.

Claim 17 of the current application corresponds to claim claims 1 of '286.

Claims 18 and 19 of the current application corresponds to claim claims 1 of '286.

Claim 20 of the current application corresponds to claim claims 1 and 22 of '286.

Claims 2 and 3 are rejected on the ground of nonstatutory double patenting as being unpatentable over claims 1 of U.S. Patent No. 7,435,286 ('286) in view of Comrie US 2007/0168213.

The Comrie reference discloses that the sorbent compositions can be added anywhere within the coal burning process, before, during or after (paragraph [0006]). This would include the promoter or a precursor there of.

It would have been obvious to one having ordinary skill in the art before the invention was made to have modified the '286 reference to include either rearranging steps, or repeat steps to have the combusting coal in the presence of the additive and activated carbon and comprising mixing the additive and the coal before combusting the coal so as to entrap the contaminants in the mercury containing gas rather than release them to the atmosphere which would include the promoter or a precursor there of Nelson (Comrie paragraph [0006]). Further the courts have held that selection of any order of performing process steps is prima facie obvious in the absence of new or unexpected results); In re Gibson, 39 F.2d 975, 5 USPQ 230.

Claims 12 are rejected on the ground of nonstatutory double patenting as being unpatentable over claims 1 of U.S. Patent No. 7,435,286 ('286) in view of Nelson US 2004/0003716.

Claim 12 of the current application correspond to claim 1 of '286 except for '286 does not disclose the activated carbon is chosen from powdered activated carbon, granular activated carbon black, carbon fiber, aerogel carbon, pyrolysis char and combinations thereof.

The Nelson reference discloses the activated carbon is chosen from powdered activated carbon, granular activated carbon black, carbon fiber, aerogel carbon, pyrolysis char and combinations thereof (paragraph [0040]).

It would have been obvious to one having ordinary skill in the art before the claimed invention to have modified the '286 reference to include the activated carbon is chosen from powdered activated carbon, granular activated carbon black, carbon fiber, aerogel carbon, pyrolysis char and combinations thereof (Nelson paragraph [0040]) as the courts have held that since it has been held to be within the general skill of a worker in the art to select a known material on the basis of its suitability for the intended use as a matter of obvious design choice. *In re Leshin*, 125 USPQ 416.

Conclusion

Any inquiry concerning this communication or earlier communications from the examiner should be directed to AMBER ROSE ORLANDO whose telephone number is (571)270-3149. The examiner can normally be reached on Monday-Thursday 7:00-5:30.

Examiner interviews are available via telephone, in-person, and video conferencing using a USPTO supplied web-based collaboration tool. To schedule an interview, applicant is encouraged to use the USPTO Automated Interview Request (AIR) at <http://www.uspto.gov/interviewpractice>.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Duane Smith can be reached on (571)272-1166. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer

Application/Control Number: 15/997,091
Art Unit: 1776

Page 11

Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

AMBER ROSE. ORLANDO
Primary Examiner
Art Unit 1776

/AMBER R ORLANDO/
Primary Examiner, Art Unit 1776

Notice of References Cited	Application/Control No. 15/997,091		Applicant(s)/Patent Under Reexamination Olson et al.	
	Examiner AMBER R ORLANDO		Art Unit 1776	Page 1 of 1

U.S. PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date MM-YYYY	Name	CPC Classification	US Classification
*	A	US-5569436-A	10-1996	Lerner; Bernard J.	B01D53/64	110/235
*	B	US-6136749-A	10-2000	Gadkaree; Kishor P.	B01D53/8665	502/180
*	C	US-20040003716-A1	01-2004	Nelson, Sidney G. JR.	B01D53/02	95/134
*	D	US-6818043-B1	11-2004	Chang; Ramsay	B01D53/64	423/213.2
*	E	US-6848374-B2	02-2005	Srinivasachar; Srivats	B01D53/10	110/165R
*	F	US-7435286-B2	10-2008	Olson; Edwin S.	B01D53/10	95/142
*	G	US-7514052-B2	04-2009	Lissianski; Vitali Victor	B01D53/56	423/210
*	H	US-20090320678-A1	12-2009	Chang; Ramsay	B01D46/002	95/92
*	I	US-7780765-B2	08-2010	Srinivasachar; Srivats	B01D53/10	110/203
	J					
	K					
	L					
	M					

FOREIGN PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date MM-YYYY	Country	Name	CPC Classification
	N					
	O					
	P					
	Q					
	R					
	S					
	T					

NON-PATENT DOCUMENTS

*		Include as applicable: Author, Title Date, Publisher, Edition or Volume, Pertinent Pages)
	U	
	V	
	W	
	X	

*A copy of this reference is not being furnished with this Office action. (See MPEP § 707.05(a).)
Dates in MM-YYYY format are publication dates. Classifications may be US or foreign.

Search Notes 	Application/Control No. 15/997,091	Applicant(s)/Patent Under Reexamination Olson et al.
	Examiner AMBER R ORLANDO	Art Unit 1776

CPC - Searched*		
Symbol	Date	Examiner

CPC Combination Sets - Searched*		
Symbol	Date	Examiner

US Classification - Searched*			
Class	Subclass	Date	Examiner

* See search history printout included with this form or the SEARCH NOTES box below to determine the scope of the search.

Search Notes		
Search Notes	Date	Examiner
Text Search (See east search history)	07/23/2018	AO
Inventor Search (DAV)	07/23/2018	AO

Interference Search			
US Class/CPC Symbol	US Subclass/CPC Group	Date	Examiner

/AMBER R ORLANDO/ Primary Examiner, Art Unit 1776	
--	--

EAST Search History

EAST Search History (Prior Art)

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L3	70	"7435286"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/07/23 14:41
S1	45	(95/134.ccls. or 95/142.ccls. or 110/345.ccls. or 423/210.ccls.) and activated carbon and promoter	US-PGPUB; USPAT	ADJ	ON	2013/09/09 09:19
S2	0	(95/134.ccls. or 95/142.ccls. or 110/345.ccls. or 423/210.ccls.) and sorben and promoter and activated carbond and mercury	US-PGPUB; USPAT	ADJ	ON	2013/09/09 09:19
S3	0	(95/134.ccls. or 95/142.ccls. or 110/345.ccls. or 423/210.ccls.) and sorbent and promoter and activated carbond and mercury	US-PGPUB; USPAT	ADJ	ON	2013/09/09 09:20
S7	73	("20020150516" "4786483" "5409522" "5505766" "6383981" "6878358" "20020033097" "4530765" "5346674" "6080281" "4708853" "6027551" "6136072" "6258334" "6818043" "20060057044" "20080207443" "20010002387" "3826618" "4814152" "4820318" "4889698" "5891324" "6528030" "20050227146" "5419834" "7942566" "20080134888" "3662523" "3849267" "4196173" "4500327" "6942840" "20020134242" "20030136509" "20050147549" "20060112823" "20080134888" "6471936" "20010003116" "20050019240" "20060048646" "4956162" "5575982" "6372187" "6375909" "7435286" "7514052" "20050074380" "20090081092" "5288306" "1984164" "4101631" "5695726" "6080281" "6848374" "20050000197" "5300137" "5607496" "5672323" "6214304" "6953494" "5245120" "20070168213" "7938571" "20040003716" "20040013589" "3194629" "3786619" "5827352" "20040109800" "20070295347" "5435980" "6136749" "20030206846").PN.	US-PGPUB; USPAT	ADJ	ON	2015/03/17 12:25
S8	13	"11209163"	US-PGPUB; USPAT	ADJ	ON	2015/03/17 12:28
S9	3	"11209163" and non carbon	US-PGPUB; USPAT	ADJ	ON	2015/03/17 12:28
S10	161	(B01D53/64, B01D2257/602,	US-PGPUB;	ADJ	ON	2015/03/17

		B01D2253/104, B01D2253/10, B01D53/10).cpc. and (halogen or halide of HBr) with sorbent	USPAT			13:49
S11	0	(95/134.ccls. or 95/142.ccls. or 110/345.ccls. or 423/210.ccls.) and sorbent and promoter and activated carbond and mercury	US-PGPUB; USPAT	ADJ	ON	2015/03/17 13:50
S12	116	(95/134.ccls. or 95/142.ccls. or 110/345.ccls. or 423/210.ccls.) and (halogen or halide of HBr) with sorbent	US-PGPUB; USPAT	ADJ	ON	2015/03/17 13:50
S13	172	(B01D53/64, B01D2257/602, B01D2253/104, B01D2253/10, B01D53/10).cpc. and (halogen or halide of HBr) with sorbent	US-PGPUB; USPAT	ADJ	ON	2015/08/20 22:04
S14	67	(95/134.ccls. or 95/142.ccls. or 110/345.ccls. or 423/210.ccls.) and activated carbon and promoter	US-PGPUB; USPAT	ADJ	ON	2015/08/20 22:04
S15	67	"6136749"	US-PGPUB; USPAT	ADJ	ON	2016/05/27 09:11
S16	20	"684374"	US-PGPUB; USPAT	ADJ	ON	2016/05/27 09:12
S17	1	"20040003716"	US-PGPUB; USPAT	ADJ	ON	2016/05/27 09:12
S18	68	"6848374"	US-PGPUB; USPAT	ADJ	ON	2016/05/27 09:12
S19	41	"7435286"	US-PGPUB; USPAT	ADJ	ON	2016/05/27 09:13
S20	13	"8168147"	US-PGPUB; USPAT	ADJ	ON	2016/05/27 09:13
S21	69	(95/134.ccls. or 95/142.ccls. or 110/345.ccls. or 423/210.ccls.) and activated carbon and promoter	US-PGPUB; USPAT	ADJ	ON	2016/06/07 09:06
S22	181	(B01D53/64, B01D2257/602, B01D2253/104, B01D2253/10, B01D53/10).cpc. and (halogen or halide of HBr) with sorbent	US-PGPUB; USPAT	ADJ	ON	2016/06/07 09:06
S25	28	"5266280"	US-PGPUB; USPAT	ADJ	ON	2016/06/07 13:41
S26	281	sorbent with mercury and (diameter or size) with ("30" or "40" or "50" or "60" or "70") with (sorbent or carbon)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	ADJ	ON	2016/09/29 15:01
S27	148	sorbent with mercury and (diameter or size) with ("30" or "40" or "50" or "60" or "70") with (sorbent or carbon) and halogen	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	ADJ	ON	2016/09/29 15:02
S28	159	sorbent with mercury and (diameter or size) with ("30" or "40" or "50" or "60" or "70") with (sorbent or carbon) and halogen\$4	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT;	ADJ	ON	2016/09/29 16:18

			IBM_TDB			
S29	206	(sorbent or activated carbon) with mercury and (diameter or size) with ("30" or "40" or "50" or "60" or "70") with (sorbent or carbon) and halogen\$4 and activated carbon	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	ADJ	ON	2016/09/29 16:22
S30	195	(B01D53/64, B01D2257/602, B01D2253/104, B01D2253/10, B01D53/10).cpc. and (halogen or halide of HBr) with sorbent	US-PGPUB; USPAT	ADJ	ON	2016/09/30 13:48
S33	6	"20040003719"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	ADJ	ON	2016/11/16 10:56
S34	49	"2004003716"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	ADJ	ON	2016/11/16 10:57
S35	81	"6848374"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	ADJ	ON	2016/11/16 10:58
S36	56	"7435286"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	ADJ	ON	2016/11/16 11:02
S37	7	olson.in. and ("40" microns).clm.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	ADJ	ON	2016/11/16 11:04
S38	0	("40" microns and halocarbon sorbent).clm.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	ADJ	ON	2016/11/16 11:05
S39	0	(halocarbon sorbent).clm. and "40" microns and olson.in.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	ADJ	ON	2016/11/16 11:05

S40	65	"40" microns and olson.in.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	ADJ	ON	2016/11/16 11:06
S41	3907	("40" microns).clm.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	ADJ	ON	2016/11/16 11:06
S42	29	("40" microns and sorbent).clm.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	ADJ	ON	2016/11/16 11:06
S43	1	(halocarbon sorbent).clm. and olson.in.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	ADJ	ON	2016/11/16 11:08
S44	36	(sorbent).clm. and olson.in.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	ADJ	ON	2016/11/16 11:08
S45	0	(sorbent).clm. and olson.in. and "40" micron	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	ADJ	ON	2016/11/16 11:08
S46	17	"11209163"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	ADJ	ON	2016/11/16 11:09
S47	2	"20110233133"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	ADJ	ON	2016/11/16 11:27
S48	7	"20110023427"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO;	ADJ	ON	2016/11/16 11:28

			DERWENT; IBM_TDB			
S49	15	"2004025274"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	ADJ	ON	2016/11/16 11:32
S50	11	"20040025274"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	ADJ	ON	2016/11/16 11:32
S51	15	"2004025274"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	ADJ	ON	2016/11/16 11:33
S52	40	"6312489"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	ADJ	ON	2016/11/16 11:33
S53	30	("20030024872" "20050045553" "20050144916" "4008060" "4640779" "4655921" "4673503" "4738778" "4746432" "4799944" "5043000" "5051118" "5120296" "5174896" "5320657" "5512075" "5674302" "6152979" "6312489" "6315130" "6336946" "6398836" "6585793" "6598749" "7648546").PN. OR ("7931723").URPN.	US-PGPUB; USPAT; USOCR	ADJ	ON	2016/11/16 11:36
S54	33	("4200444" "4640779" "5968215" "6059851").PN. OR ("6312489").URPN.	US-PGPUB; USPAT; USOCR	ADJ	ON	2016/11/16 11:40
S55	5	"8518142"	US-PGPUB; USPAT; USOCR	ADJ	ON	2016/11/16 11:54
S56	4	"8747505"	US-PGPUB; USPAT; USOCR	ADJ	ON	2016/11/16 11:57
S57	2	"14318270"	US-PGPUB; USPAT; USOCR	ADJ	ON	2016/11/16 12:06
S58	13	pac with size with sorbent	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	ADJ	ON	2016/11/16 12:13
S59	197	(B01D53/64, B01D2257/602,	US-PGPUB;	ADJ	ON	2016/11/16

		B01D2253/104, B01D2253/10, B01D53/10).cpc. and (halogen or halide of HBr) with sorbent	USPAT			15:23
S60	0	(B01D53/64, B01D2257/602, B01D2253/104, B01D2253/10, B01D53/10).cpc. and (halogen or halide of HBr) with sorbent "4198388"	US-PGPUB; USPAT	ADJ	ON	2016/11/17 12:39
S61	10	"4198388"	US-PGPUB; USPAT	ADJ	ON	2016/11/17 12:39
S62	0	"2010083696"	US-PGPUB; USPAT	ADJ	ON	2016/11/17 13:32
S63	2	"20100083696"	US-PGPUB; USPAT	ADJ	ON	2016/11/17 13:32
S64	2	absorp\$5 with mea with methanol with acid	US-PGPUB; USPAT	ADJ	ON	2016/11/17 13:36
S65	2	"20070283813"	US-PGPUB; USPAT	ADJ	ON	2016/11/17 13:39
S66	21	"4469596"	US-PGPUB; USPAT	ADJ	ON	2016/11/21 08:29
S67	4	"2003229245"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	ADJ	ON	2017/05/10 10:36
S68	2	"20030229245"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	ADJ	ON	2017/05/10 10:36
S69	45	"5,338,458"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	ADJ	ON	2017/05/10 10:38
S70	45	"5338458"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	ADJ	ON	2017/05/10 10:38
S71	213	(B01D53/64, B01D2257/602, B01D2253/104, B01D2253/10, B01D53/10).cpc. and (halogen or halide of HBr) with sorbent	US-PGPUB; USPAT	ADJ	ON	2017/05/10 11:02
S72	64	("1786483" "1984164" "2317857" "20010002387" "20010003116" "20020134242" "20020150516" "20030136509" "20040003716" "20040013589" "20050019240" "20060048646" "20060191835" "20090062119" "20100047146" "20120183458" "20140056787"	US-PGPUB; USPAT	ADJ	ON	2017/05/10 11:20

		"3194629" "3662523" "3786619" "3826618" "3849267" "4196173" "4500327" "4814152" "4820318" "4889698" "4959162" "5300137" "5409522" "5462908" "5505766" "5575982" "5607496" "5672323" "5695726" "5827352" "5891324" "6027551" "6080281" "6136072" "6136749" "6214304" "6258334" "6372187" "6375909" "6383981" "6471936" "6528030" "6818043" "6848374" "6878358" "6942840" "6953494" "7101631" "7435286" "7479263" "7514052" "7563311" "7611564" "8007749" "8168147" "8168149" "8512655").PN.				
S73	3	("20090235848" "20110076210" "20150246315").PN.	US-PGPUB; USPAT	ADJ	ON	2017/05/10 11:31
S79	3	("20090235848" "20110076210" "20140224121").PN.	US-PGPUB; USPAT	ADJ	ON	2017/06/27 09:36
S80	96	("1984164" "2317857" "20010002387" "20010003116" "20020043496" "20020134242" "20020150516" "20030104937" "20030136509" "20040003716" "20040013589" "20040076570" "20050019240" "20060048646" "20060191835" "20080182747" "20080292512" "20090062119" "20090136401" "20090320678" "20100047146" "20110168018" "20120183458" "20130280156" "20140056787" "20140255279" "20140308188" "20150098878" "3194629" "3662523" "3786619" "3826618" "3849267" "3876393" "4094777" "4101631" "4196173" "4338896" "4500327" "4708853" "4786483" "4814152" "4820318" "4889698" "4956162" "5300137" "5336835" "5409522" "5462908" "5505766" "5575982" "5607496" "5672323" "5695726" "5827352" "5891324" "6027551" "6080281" "6136072" "6136749" "6214304" "6258334" "6372187" "6375909" "6383981" "6471936" "6528030" "6638485" "6808692" "6818043" "6848374" "6878358" "6942840" "6953494" "6960329" "7081434" "7211707" "7435286" "7479263" "7514052" "7521032" "7544338" "7563311" "7611564" "7622092" "7722843" "7767174" "7780765" "8007749" "8168147" "8168149" "8216535" "8512655" "8652235" "8821819" "9011805").PN.	US-PGPUB; USPAT	ADJ	ON	2017/06/27 09:41
S81	593	honeycomb with plug\$4 and plug\$4 with length	US-PGPUB; USPAT	ADJ	ON	2017/06/27 14:45
S82	0	honeycomb with plug\$4 and plug\$4 with length with less than with "5"	US-PGPUB; USPAT	ADJ	ON	2017/06/27 14:45
S83	0	honeycomb with plug\$4 and plug\$4 with length with less than	US-PGPUB; USPAT	ADJ	ON	2017/06/27 14:45

S84	127	honeycomb with plug\$4 and plug\$4 with length with "5"	US-PGPUB; USPAT	ADJ	ON	2017/06/27 14:46
S85	241	honeycomb with plug\$4 and plug\$4 with length with mm	US-PGPUB; USPAT	ADJ	ON	2017/06/27 14:47
S86	41	honeycomb with plug\$4 and plug\$4 with length with "3 mm "	US-PGPUB; USPAT	ADJ	ON	2017/06/27 14:49
S87	28	honeycomb with plug\$4 and plug\$4 with length with "3 mm " and plug\$4 with porosity	US-PGPUB; USPAT	ADJ	ON	2017/06/27 14:52
S88	28	honeycomb and plug\$4 with length with "3 mm " and plug\$4 with porosity	US-PGPUB; USPAT	ADJ	ON	2017/06/27 14:53
S89	43	honeycomb and plug\$4 with porosity with "100"	US-PGPUB; USPAT	ADJ	ON	2017/06/27 15:06
S90	20	honeycomb and plug\$4 with pore (size or diameter) with "100"	US-PGPUB; USPAT	ADJ	ON	2017/06/27 15:07
S91	8	saw with honeycomb with filter	US-PGPUB; USPAT	ADJ	ON	2017/06/29 13:31
S92	230	(B01D53/64, B01D2257/602, B01D2253/104, B01D2253/10, B01D53/10).cpc. and (halogen or halide of HBr) with sorbent	US-PGPUB; USPAT	ADJ	ON	2017/12/01 14:36
S93	2	"20060260468"	US-PGPUB; USPAT	ADJ	ON	2018/07/03 10:34
S94	19	engine with air with inlet with filter\$4 with cone	US-PGPUB; USPAT	ADJ	ON	2018/07/03 15:26
S95	36	engine with air with inlet with filter\$4 with (cone or conical or (diameter with (increas\$4 or decreas\$4)))	US-PGPUB; USPAT	ADJ	ON	2018/07/03 15:27
S96	24	("3771638" "3870495" "3872012" "4157902" "4702754" "5125940" "5522909" "5549724" "5632793").PN. OR ("5888260").URPN.	US-PGPUB; USPAT; USOCR	ADJ	ON	2018/07/03 15:31
S97	41	("0153535" "0439091" "1398685" "1530163" "1887052" "2087688" "4003836" "4018580" "4032455" "4039308" "4065276" "4261710" "4410341" "4414110" "4699715" "5106397" "5178656" "5522909" "5549722" "5549724" "5888260" "6397842" "6508052" "D401597" "D401942" "D403414" "D403416").PN. OR ("6808552").URPN.	US-PGPUB; USPAT; USOCR	ADJ	ON	2018/07/03 15:31
S98	15	("D403416").URPN.	USPAT	ADJ	ON	2018/07/03 15:33
S99	0	"20030089233"	USPAT	ADJ	ON	2018/07/04 12:29
S100	3	"20030089233"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/07/04 12:29
S101	26	"6833023"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/07/04 12:29
S102	2	"20070168213"	US-PGPUB;	ADJ	ON	2018/07/09

			USPAT; USOCR; FPRS; EPO; JPO			13:08
S103	14	carbocations with sorbent with bromine	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/07/09 13:14
S104	0	a side forming a cross sectional shape of each of the first	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/07/09 13:47
S105	0	non of side forming	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/07/09 13:56
S106	0	none of side forming	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/07/09 13:56
S107	0	none of sides forming	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/07/09 13:56
S109	13	olson.in. and (alkali and promoter and earth).clm.	US-PGPUB; USPAT	ADJ	ON	2018/07/17 16:22
S110	0	olson.in. and (alkali and promoter and earth with vapor).clm.	US-PGPUB; USPAT	ADJ	ON	2018/07/17 16:22
S111	10	olson.in. and (alkali and promoter with vapor).clm.	US-PGPUB; USPAT	ADJ	ON	2018/07/17 16:22
S112	0	"2015008283"	US-PGPUB; USPAT	ADJ	ON	2018/07/23 06:26
S113	2	"20150082833"	US-PGPUB; USPAT	ADJ	ON	2018/07/23 06:26
S114	24	olson.in. and liquid.clm. and promoted	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/07/23 07:50
S115	75	remov\$4 with mercury and (br or bromine) with liquid with carbon	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/07/23 07:54
S116	0	separating greater than "70" wt% of the mercury	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/07/23 09:17
S117	0	((separating greater) with (of the mercury)).clm.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/07/23 09:17

EAST Search History

S118	20	"11209163"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/07/23 09:43
------	----	------------	--	-----	----	---------------------

7/ 23/ 2018 2:56:48 PM

C:\ Users\ amillerharris\ Documents\ EAST\ Workspaces\ 12429058.wsp

Bibliographic Data

Application No: 15/997,091

Foreign Priority claimed: ☐ Yes ☒ No

35 USC 119 (a-d) conditions met: ☐ Yes ☒ No ☐ Met After Allowance

Verified and Acknowledged: /AMBER R ORLANDO/

Examiner's Signature

Initials

Title:

SORBENTS FOR THE OXIDATION AND REMOVAL OF MERCURY

FILING or 371(c) DATE	CLASS	GROUP ART UNIT	ATTORNEY DOCKET NO.
06/04/2018	423	1776	
RULE			

APPLICANTS

Midwest Energy Emissions Corp, Lewis Center, OH,

INVENTORS

Edwin S. Olson Grand Forks, ND, UNITED STATES

Michael J. Holmes Thompson, ND, UNITED STATES

John H. Pavlish East Grand Forks, MN, UNITED STATES

CONTINUING DATA

This application is a CON of 15974343 05/08/2018

15974343 is a CON of 15951970 04/12/2018

15951970 is a CON of 14712558 05/14/2015

14712558 is a CON of 14318270 06/27/2014 PAT 9757689

14318270 is a CON of 13966768 08/14/2013 PAT 8821819

13966768 is a CON of 13427665 03/22/2012 PAT 8512655

13427665 is a CON of 12419219 04/06/2009 PAT 8168147

12419219 is a CON of 12201595 08/29/2008

12201595 is a CON of 11209163 08/22/2005 PAT 7435286

11209163 has PRO of 60605640 08/30/2004

FOREIGN APPLICATIONS

IF REQUIRED, FOREIGN LICENSE GRANTED**

06/21/2018

STATE OR COUNTRY

UNITED STATES

ADDRESS

FILING FEE RECEIVED

\$5,860

REMARKS

This responds to the Non-Final Office Action dated July 27, 2018.

No claims are presently amended. No claims are presently canceled, and no claims were canceled previously. No new claims are presently added. As a result, claims 1-20 are now pending in this application.

The Rejection of Claims Under §102

I. The Office Action rejected claims 1, 4-14, and 16-19 under 35 U.S.C. § 102(e) over U.S. patent publication no. 2004/0003716 (“Nelson”).

This rejection is respectfully traversed.

Independent claim 1 recites in-flight promotion with a promoter that is Br₂, HBr, Br⁻, or a combination thereof.

The Office Action states at page 2 that Nelson describes a promoted activated carbon that is promoted in-flight with at least one promoter that is Br₂, HBr, Br⁻, or a combination thereof, citing to paragraphs [0048]-[0051] of Nelson. Paragraphs [0049]-[0051] describe treating activated carbon with bromine in a gaseous state or with a bromine-containing gas.

As explained in the present application, such as at page 20 at lines 11-17 and 22-28, “in-flight” promotion means that at the time of promotion the sorbent particles are dispersed in a stream of transport air or other gas that conveys the sorbent particles from one location to another in a mercury-removal system. The term “in-flight” promotion refers to the sorbent being promoted in-flight while being conveyed from one location to another in the mercury-removal system. However, the Office Action fails to show in Nelson, and Applicant cannot find in Nelson, a description or suggestion of the claimed feature of in-flight promotion of activated carbon sorbent, wherein at the time of promotion the sorbent is dispersed in a stream of transport air or other gas that conveys the sorbent particles from one location to another in a mercury-removal system. Accordingly, claim 1 is patentable over Nelson.

Dependent claims 4-14 and 16-19 are directly or indirectly dependent on independent claim 1. As such, claims 4-14 and 16-19 incorporate all the features of claim 1. Accordingly, dependent claims 4-14 and 16-19 are patentable for at least the same reasons given herein for patentability of independent claim 1.

Applicant therefore respectfully requests reconsideration and withdrawal of the rejection of claims 1, 4-14, and 16-19 under 35 U.S.C. § 102(e) over Nelson.

The Rejection of Claims Under §103

II. The Office Action rejected claims 2-3 under 35 U.S.C. § 103(a) over U.S. patent publication no. 2004/0003716 (“Nelson”) in view of U.S. patent publication no. 2007/0168213 (“Comrie”).

This rejection is respectfully traversed.

Independent claim 1 recites in-flight promotion with a promoter that is Br₂, HBr, Br⁻, or a combination thereof. Claims 2 and 3 recite that the coal that is combusted comprises the promoter or a precursor thereof.

As explained herein at II(A), Comrie is not prior art. As explained herein at II(B), Nelson cannot be used to achieve the presently claimed invention. As explained herein at II(C), the presently claimed invention has advantages that could not be predicted by a person of ordinary skill in the art before the invention was made. Further, as explained herein at II(D), the next Office Action cannot be properly made final.

II(A). Comrie is not prior art.

Comrie was published July 19, 2007, and the earliest priority is to a provisional application filed January 19, 2006. In contrast, the present application is a continuation that derives priority from a provisional application filed August 30, 2004 and converted to a U.S. Utility application on August 22, 2005. The present application has priority that is one year and five months prior to Comrie’s earliest priority date; even if only the first U.S. Utility application is considered for support, Comrie’s earliest priority date is still about five months later. Comrie is not prior art and could not be considered by a person of ordinary skill in the art prior to the time the present invention was made and the present application filed.

II(B). Nelson cannot be used achieve the presently claimed invention.

Nelson mentions promoting activated carbon outside of flue gas, and then adding the activated carbon to flue gas.

No cited reference that is available as prior art to the present application describes or suggests combusting coal that includes Br₂, HBr, Br⁻ or a precursor thereof. Therefore, dependent claims 2-3 are patentable.

II(C). The presently claimed invention has advantages that could not be predicted by a person of ordinary skill in the art before the invention was made.

The inventors of the present application have discovered that by combusting coal that includes Br₂, HBr, Br⁻ or a precursor thereof, and by placing a sorbent in the mercury-containing gas, as presently claimed, the sorbent can be bromide-promoted in-flight in the mercury-containing gas. Promotion of the sorbent in the mercury-containing gas has certain advantages that would be impossible for a person of ordinary skill in the art hypothetically having the cited prior art references in-hand.

Applicant's continuation-in-part U.S. application no. 15/853,029, published as U.S. patent publication no. 2018/0133646, includes experimental data in Part II of the Examples that compares the performance of activated sorbents added to the flue gas and promoted in-flight in the mercury-containing gas by bromide promoters that are added to the combustor to the performance of activated sorbents that are promoted outside of the flue gas and then added to the flue gas. As shown in Table 1 and as explained in paragraphs [0116]-[0117], promotion of the activated carbon in-flight in the mercury containing gas yielded significantly improved mercury capture compared to the activated carbon that was promoted before adding to the mercury-containing gas.

The M.P.E.P. at the beginning of § 2143.02 states (emphasis added) “[a] rationale to support a conclusion that a claim would have been obvious is that all the claimed elements were known in the prior art and one skilled in the art could have combined the elements as claimed by known methods with no change in their respective functions, *and the combination would have yielded nothing more than predictable results to one of ordinary skill in the art.*” The only cited reference available as prior art is Nelson; there is no way to predict from Nelson the superior mercury capture discovered by the present inventors that occurs when activated carbon is promoted in-flight in the mercury-containing gas, as occurs when following claims 2-3. The presently claimed invention therefore has advantages that could not be predicted from the cited references by a person of

ordinary skill in the art before the invention was made; accordingly, independent claim 1 is patentable over the cited references.

Dependent claims 2-3 are directly or indirectly dependent on independent claim 1. As such, these claims incorporate all the features of claim 1. Accordingly, dependent claims 2-3 are patentable for at least the reasons given herein for patentability of independent claim 1.

Applicant therefore respectfully requests reconsideration and withdrawal of the rejection of claims 2-3 under 35 U.S.C. § 103(a) over Nelson in view of Comrie.

II(D). The next Office Action cannot be made final.

As explained herein in section II, claims 2-3 are patentable over the cited references. Applicant has not amended the claims and, as such, has not introduced any new features or limitations which would suffice under MPEP §706.07(a) to render any subsequent action on the merits final. If the PTO wishes to issue a further action in response to the remarks presented herein, Applicant respectfully submits that such action should be non-final.

III. The Office Action rejected claims 15 and 20 under 35 U.S.C. § 103(a) over U.S. patent publication no. 2004/0003716 ("Nelson") in view of U.S. patent no. 6,878,358 ("Vosteen").

This rejection is respectfully traversed.

As explained herein at II(A)-II(C), claim 1 is patentable over Nelson. Vosteen fails to remedy the defects of Nelson; therefore, claim 1 is patentable over this combination of references.

Dependent claims 15 and 20 are dependent on independent claim 1. As such, these claims incorporate all the features of claim 1. Accordingly, dependent claims 15 and 20 are patentable for at least the reasons given herein for patentability of independent claim 1.

Applicant therefore respectfully requests reconsideration and withdrawal of the rejection of claims 15 and 20 under 35 U.S.C. § 103(a) over Nelson in view of Vosteen.

Double Patenting Rejection

IV. The Office Action rejected claims 1, 4-11, and 13-20 for nonstatutory double patenting over claims 1-3, 13, 22, and 26 of U.S. patent no. 7,435,286 ('286).

Applicant does not admit that claims 1, 4-11, and 13-20 are obvious in view of claims 1-3, 13, 22, and 26 of the '286.

As the current pending claims stand rejected on other grounds and are still subject to amendment, Applicant takes note of these rejections but do not take further action at this time inasmuch as no pending claim has yet to be allowed. Applicant will re-evaluate this rejection, upon an indication of allowable claims.

V. The Office Action rejected claims 2 and 3 for nonstatutory double patenting over claim 1 of U.S. patent no. 7,435,286 ('286) in view of U.S. patent publication no. 2007/0168213 ("Comrie").

This rejection is respectfully traversed. Applicant does not admit that claims 2 and 3 are obvious in view of the '286 in view of Comrie.

In the rejection, the Office Action derives the feature of combusting coal in the presence of a promoter from Comrie. However, as explained herein at II(A), Comrie is not prior art, because the present application has priority that is one year and five months prior to Comrie's earliest priority date.

Applicant therefore respectfully requests reconsideration and withdrawal of the rejection of claims 2 and 3 for nonstatutory double patenting over claim 1 of the '286 in view of Comrie.

VI. The Office Action rejected claim 12 for nonstatutory double patenting over claim 1 of U.S. patent no. 7,435,286 ('286) in view of U.S. patent publication no. 2004/0003716 ("Nelson").

Applicant does not admit that claim 12 is obvious in view of the '286 in view of Nelson.

As the current pending claims stand rejected on other grounds and are still subject to amendment, Applicant takes note of these rejections but do not take further action at this time inasmuch as no pending claim has yet to be allowed. Applicant will re-evaluate this rejection, upon an indication of allowable claims.

CONCLUSION

It is respectfully submitted that the claims are in condition for allowance, and notification to that effect is earnestly requested. The Examiner is invited to telephone the undersigned at (612) 349-9580 to facilitate prosecution of this application.

If necessary, please charge any additional fees or deficiencies, or credit any overpayments to Deposit Account No. 19-0743.

Respectfully submitted,

SCHWEGMAN LUNDBERG & WOESSNER, P.A.
P.O. Box 2938
Minneapolis, MN 55402-0938
(612) 373-6900

Date August 14, 2018

By 

Nicholas P. Lanzatella
Reg. No. 63,803

IN THE CLAIMS

Please amend the claims as follows:

1. (Original) A method for reducing mercury in a mercury-containing gas, the method comprising:
injecting a sorbent into the mercury-containing gas;
collecting mercury in the mercury-containing gas on the sorbent to produce a cleaned gas, wherein the sorbent is a promoted activated carbon that is promoted in-flight with at least one promoter that is Br₂, HBr, Br⁻, or a combination thereof, wherein the mercury-containing gas is a coal-combustion gas.
2. (Original) The method of claim 1, wherein the coal that is combusted comprises the promoter or a precursor thereof.
3. (Original) The method of claim 2, further comprising combusting the coal that comprises the promoter or the precursor thereof.
4. (Original) The method of claim 1, wherein the promoted activated carbon is promoted with the promoter while the promoter is in the gas phase or is a vapor.
5. (Original) The method of claim 1, further comprising promoting the activated carbon in-flight.
6. (Original) The method of claim 1, wherein the promoted activated carbon comprises active sites, comprising halide anions bound to the activated carbon.
7. (Original) The method of claim 1, wherein the promoted activated carbon comprises active sites comprising carbocations bound to halide anions.
8. (Original) The method of claim 1, wherein collecting the mercury comprises chemically reacting carbene species edge sites in the activated carbon with the mercury.

9. (Original) The method of claim 1, further comprising injecting an alkaline sorbent into the mercury-containing gas stream.
10. (Original) The method of claim 9, wherein the alkaline sorbent is selected from the group consisting of alkali elements, alkaline earth elements, alkali salts, alkaline earth salts, and combinations thereof.
11. (Original) The method of claim 9, wherein the alkaline sorbent is selected from the group consisting of sodium carbonate, calcium oxide, lime, and combinations thereof.
12. (Original) The method of claim 1, wherein the activated carbon is chosen from powdered activated carbon, granular activated carbon, carbon black, carbon fiber, aerogel carbon, pyrolysis char, and combinations thereof.
13. (Original) The method of claim 1, wherein the promoter is HBr or Br⁻.
14. (Original) The method of claim 1, wherein the mercury-containing gas is a flue gas stream downstream of a boiler furnace.
15. (Original) The method of claim 1, wherein monitoring the mercury content of the cleaned gas is performed substantially continuously.
16. (Original) The method of claim 1, wherein the sorbent has a composition comprising from about 1 to about 30 grams of promoter per 100 grains of activated carbon.
17. (Original) The method of claim 1, further comprising injecting sorbent into the mercury-containing gas stream to form the promoted activated carbon.

18. (Original) The method of claim 1, comprising collecting greater than 70 wt% of the mercury in the mercury-containing gas.

19. (Original) The method of claim 1, comprising collecting greater than 70 wt% of the mercury in the mercury-containing gas on the sorbent.

20. (Original) The method of claim 1, wherein the method is a method for reducing mercury in the mercury-containing gas to a desired level, the method further comprising:

monitoring the mercury content of the cleaned gas; and

controlling, in response to the monitored mercury content of the cleaned gas, an injection rate of injecting the sorbent into the mercury-containing gas, the sorbent composition, or a combination thereof, so that the mercury content of the cleaned gas is maintained at or below the desired level.

S/N 15/997,091

PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Inventor(s): Edwin S. Olson et al.

Examiner: AMBER ROSE ORLANDO

Application No.: 15/997,091

Group Art Unit: 1776

Filed: June 4, 2018

Docket No.: 4820.001UI0

Confirmation No.: 5161

Title: **SORBENTS FOR THE OXIDATION AND REMOVAL OF MERCURY**

AMENDMENT & RESPONSE UNDER 37 C.F.R. § 1.111

Mail Stop Amendment

Commissioner for Patents

P.O. Box 1450

Alexandria, VA 22313-1450

Applicant has received the Non-Final Office Action dated July 27, 2018. Please enter the following.

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Inventor(s): Edwin S. Olson et al.

Title: SORBENTS FOR THE OXIDATION AND REMOVAL OF MERCURY

Docket No.: 4820.001U10

Serial No.: 15/997,091

Filed: June 4, 2018

Due Date: October 27, 2018

Examiner: Amber Orlando

Group Art Unit: 1776

Customer No.: 21186

Confirmation No.: 5161

Mail Stop Amendment
Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

We are transmitting herewith the following attached items (as indicated with an "X"):

X Amendment and Response under 37 C.F.R. § 1.111 (10 pgs.)

If not provided for in a separate paper filed herewith, please consider this a **PETITION FOR EXTENSION OF TIME** for sufficient number of months to enter these papers and please charge any additional fees or credit overpayment to Deposit Account No. 19-0743. If applicable, any papers or fees supplied herewith are considered to be timely filed pursuant to 37 C.F.R. § 1.7(a), the response period falling on a Federal Holiday, Saturday or Sunday being extended to the next succeeding business day.

SCHWEGMAN LUNDBERG & WOESSNER, P.A.

Customer No.: 21186

By: 

Nicholas P. Lanzatella

Reg. No. 63,803

Electronic Acknowledgement Receipt

EFS ID:	33467290
Application Number:	15997091
International Application Number:	
Confirmation Number:	5161
Title of Invention:	SORBENTS FOR THE OXIDATION AND REMOVAL OF MERCURY
First Named Inventor/Applicant Name:	Edwin S. Olson
Customer Number:	21186
Filer:	Steven M. Reid/Megan Reed
Filer Authorized By:	Steven M. Reid
Attorney Docket Number:	4820.001US10
Receipt Date:	14-AUG-2018
Filing Date:	04-JUN-2018
Time Stamp:	17:36:15
Application Type:	Utility under 35 USC 111(a)

Payment information:

Submitted with Payment		no			
File Listing:					
Document Number	Document Description	File Name	File Size(Bytes)/ Message Digest	Multi Part /.zip	Pages (if appl.)
1		SIGNED_4820_001U10_NFOAR esponse.pdf	148579	yes	11
			46c87bb32d795307587c7d86ab33c311c6832945		

	Multipart Description/PDF files in .zip description		
	Document Description	Start	End
	Amendment/Req. Reconsideration-After Non-Final Reject	6	11
	Claims	3	5
	Amendment/Req. Reconsideration-After Non-Final Reject	2	2
	Transmittal Letter	1	1
Warnings:			
Information:			
Total Files Size (in bytes):		148579	
<p>This Acknowledgement Receipt evidences receipt on the noted date by the USPTO of the indicated documents, characterized by the applicant, and including page counts, where applicable. It serves as evidence of receipt similar to a Post Card, as described in MPEP 503.</p> <p><u>New Applications Under 35 U.S.C. 111</u> If a new application is being filed and the application includes the necessary components for a filing date (see 37 CFR 1.53(b)-(d) and MPEP 506), a Filing Receipt (37 CFR 1.54) will be issued in due course and the date shown on this Acknowledgement Receipt will establish the filing date of the application.</p> <p><u>National Stage of an International Application under 35 U.S.C. 371</u> If a timely submission to enter the national stage of an international application is compliant with the conditions of 35 U.S.C. 371 and other applicable requirements a Form PCT/DO/EO/903 indicating acceptance of the application as a national stage submission under 35 U.S.C. 371 will be issued in addition to the Filing Receipt, in due course.</p> <p><u>New International Application Filed with the USPTO as a Receiving Office</u> If a new international application is being filed and the international application includes the necessary components for an international filing date (see PCT Article 11 and MPEP 1810), a Notification of the International Application Number and of the International Filing Date (Form PCT/RO/105) will be issued in due course, subject to prescriptions concerning national security, and the date shown on this Acknowledgement Receipt will establish the international filing date of the application.</p>			

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

PATENT APPLICATION FEE DETERMINATION RECORD Substitute for Form PTO-875				Application or Docket Number 15/997,091		Filing Date 06/04/2018		☐ To be Mailed	
ENTITY: ☒ LARGE ☐ SMALL ☐ MICRO									
APPLICATION AS FILED - PART I									
		(Column 1)		(Column 2)					
FOR		NUMBER FILED		NUMBER EXTRA		RATE (\$)		FEE (\$)	
☐ BASIC FEE (37 CFR 1.16(a), (b), or (c))		N/A		N/A		N/A			
☐ SEARCH FEE (37 CFR 1.16(k), (l), or (m))		N/A		N/A		N/A			
☐ EXAMINATION FEE (37 CFR 1.16(o), (p), or (q))		N/A		N/A		N/A			
TOTAL CLAIMS (37 CFR 1.16(i))		minus 20 =	*			x \$100 =			
INDEPENDENT CLAIMS (37 CFR 1.16(h))		minus 3 =	*			x \$460 =			
☐ APPLICATION SIZE FEE (37 CFR 1.16(s))		If the specification and drawings exceed 100 sheets of paper, the application size fee due is \$310 (\$155 for small entity) for each additional 50 sheets or fraction thereof. See 35 U.S.C. 41(a)(1)(G) and 37 CFR 1.16(s).							
☐ MULTIPLE DEPENDENT CLAIM PRESENT (37 CFR 1.16(j))									
* If the difference in column 1 is less than zero, enter "0" in column 2.						TOTAL			
APPLICATION AS AMENDED - PART II									
		(Column 1)		(Column 2)	(Column 3)				
AMENDMENT	08/14/2018	CLAIMS REMAINING AFTER AMENDMENT		HIGHEST NUMBER PREVIOUSLY PAID FOR	PRESENT EXTRA		RATE (\$)		ADDITIONAL FEE (\$)
	Total (37 CFR 1.16(i))	* 20	Minus	** 20	= 0		x \$100 =		0
	Independent (37 CFR 1.16(h))	* 1	Minus	*** 3	= 0		x \$460 =		0
	☐ Application Size Fee (37 CFR 1.16(s))								
	☐ FIRST PRESENTATION OF MULTIPLE DEPENDENT CLAIM (37 CFR 1.16(j))								
							TOTAL ADD'L FEE		0
AMENDMENT		(Column 1)		(Column 2)	(Column 3)				
		CLAIMS REMAINING AFTER AMENDMENT		HIGHEST NUMBER PREVIOUSLY PAID FOR	PRESENT EXTRA		RATE (\$)		ADDITIONAL FEE (\$)
	Total (37 CFR 1.16(i))	*	Minus	**	=		x \$0 =		
	Independent (37 CFR 1.16(h))	*	Minus	***	=		x \$0 =		
	☐ Application Size Fee (37 CFR 1.16(s))								
☐ FIRST PRESENTATION OF MULTIPLE DEPENDENT CLAIM (37 CFR 1.16(j))									
							TOTAL ADD'L FEE		
* If the entry in column 1 is less than the entry in column 2, write "0" in column 3.							LIE		
** If the "Highest Number Previously Paid For" IN THIS SPACE is less than 20, enter "20".							brenda murphy		
*** If the "Highest Number Previously Paid For" IN THIS SPACE is less than 3, enter "3".									
The "Highest Number Previously Paid For" (Total or Independent) is the highest number found in the appropriate box in column 1.									

This collection of information is required by 37 CFR 1.16. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 12 minutes to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.**

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NUMBER	FILING OR 371(C) DATE	FIRST NAMED APPLICANT	ATTY. DOCKET NO./TITLE
15/997,091	06/04/2018	Edwin S. Olson	4820.001US10

CONFIRMATION NO. 5161

21186

SCHWEGMAN LUNDBERG & WOESSNER, P.A.
P.O. BOX 2938
MINNEAPOLIS, MN 55402

PUBLICATION NOTICE



Title:SORBENTS FOR THE OXIDATION AND REMOVAL OF MERCURY

Publication No.US-2018-0280870-A1

Publication Date:10/04/2018

NOTICE OF PUBLICATION OF APPLICATION

The above-identified application will be electronically published as a patent application publication pursuant to 37 CFR 1.211, et seq. The patent application publication number and publication date are set forth above.

The publication may be accessed through the USPTO's publicly available Searchable Databases via the Internet at www.uspto.gov. The direct link to access the publication is currently <http://www.uspto.gov/patft/>.

The publication process established by the Office does not provide for mailing a copy of the publication to applicant. A copy of the publication may be obtained from the Office upon payment of the appropriate fee set forth in 37 CFR 1.19(a)(1). Orders for copies of patent application publications are handled by the USPTO's Public Records Division. The Public Records Division can be reached by telephone at (571) 272-3150 or (800) 972-6382, by facsimile at (571) 273-3250, by mail addressed to the United States Patent and Trademark Office, Public Records Division, Alexandria, VA 22313-1450 or via the Internet.

In addition, information on the status of the application, including the mailing date of Office actions and the dates of receipt of correspondence filed in the Office, may also be accessed via the Internet through the Patent Electronic Business Center at www.uspto.gov using the public side of the Patent Application Information and Retrieval (PAIR) system. The direct link to access this status information is currently <https://portal.uspto.gov/pair/PublicPair>. Prior to publication, such status information is confidential and may only be obtained by applicant using the private side of PAIR.

Further assistance in electronically accessing the publication, or about PAIR, is available by calling the Patent Electronic Business Center at 1-866-217-9197.

Office of Data Management, Application Assistance Unit (571) 272-4000, or (571) 272-4200, or 1-888-786-0101



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
15/997,091	06/04/2018	Edwin S. Olson	4820.001US10	5161
21186 7590 11/02/2018 SCHWEGMAN LUNDBERG & WOESSNER, P.A. P.O. BOX 2938 MINNEAPOLIS, MN 55402			EXAMINER ORLANDO, AMBER ROSE	
			ART UNIT 1776	PAPER NUMBER
			NOTIFICATION DATE 11/02/2018	DELIVERY MODE ELECTRONIC

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Notice of the Office communication was sent electronically on above-indicated "Notification Date" to the following e-mail address(es):

SLW@blackhillsip.com
uspto@slwip.com

DETAILED ACTION

Notice of Pre-AIA or AIA Status

The present application is being examined under the pre-AIA first to invent provisions.

Claim Rejections - 35 USC § 112

The following is a quotation of 35 U.S.C. 112(b):

(b) **CONCLUSION.**—The specification shall conclude with one or more claims particularly pointing out and distinctly claiming the subject matter which the inventor or a joint inventor regards as the invention.

The following is a quotation of 35 U.S.C. 112 (pre-AIA), second paragraph:

The specification shall conclude with one or more claims particularly pointing out and distinctly claiming the subject matter which the applicant regards as his invention.

Claims 2-6, 12, 15 and 20 are rejected under 35 U.S.C. 112(b) or 35 U.S.C. 112 (pre-AIA), second paragraph, as being indefinite for failing to particularly point out and distinctly claim the subject matter which the inventor or a joint inventor, or for pre-AIA the applicant regards as the invention.

Claim 2 recites the limitation "the coal" in line 1. There is insufficient antecedent basis for this limitation in the claim.

Claim 3 recites the limitation "the coal" in line 1. There is insufficient antecedent basis for this limitation in the claim.

Claim 3 recites the limitation "the precursor" in line 2. There is insufficient antecedent basis for this limitation in the claim.

Claim 4 recites the limitation "the gas phase" in line 2. There is insufficient antecedent basis for this limitation in the claim.

Claim 5 recites the limitation "the activated carbon" in line 1. There is insufficient antecedent basis for this limitation in the claim.

Claim 6 recites the limitation "the activated carbon" in line 2. There is insufficient antecedent basis for this limitation in the claim.

Claim 12 recites the limitation "the activated carbon" in line 1. There is insufficient antecedent basis for this limitation in the claim.

Claim 15 recites the limitation "the mercury content" in line 1. There is insufficient antecedent basis for this limitation in the claim.

Claim 15 recites the limitation "the cleaned gas" in lines 1-2. There is insufficient antecedent basis for this limitation in the claim.

Claim 20 recites the limitation "the mercury content" in lines 3 and 6. There is insufficient antecedent basis for this limitation in the claim.

Claim 20 recites the limitation "the cleaned gas" in lines 3, 4 and 6. There is insufficient antecedent basis for this limitation in the claim.

Claim 20 recites the limitation "the sorbent composition" in line 5. There is insufficient antecedent basis for this limitation in the claim.

Claim Rejections - 35 USC § 102

In the event the determination of the status of the application as subject to AIA 35 U.S.C. 102 and 103 (or as subject to pre-AIA 35 U.S.C. 102 and 103) is incorrect, any correction of the statutory basis for the rejection will not be considered a new ground of rejection if the prior art relied upon, and the rationale supporting the rejection, would be the same under either status.

The following is a quotation of the appropriate paragraphs of pre-AIA 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless –

(e) the invention was described in (1) an application for patent, published under section 122(b), by another filed in the United States before the invention by the applicant for patent or (2) a patent granted on an application for patent by another filed in the United States before the invention by the applicant for patent, except that an international application filed under the treaty defined in section 351(a) shall have the effects for purposes of this subsection of an application filed in the United States only if the international application designated the United States and was published under Article 21(2) of such treaty in the English language.

Claim(s) 1, 4-14 and 16-19 is/are rejected under pre-AIA 35 U.S.C. 102(e) as being anticipated by Nelson US 2004/0003716.

For claim 1, the Nelson reference discloses a method for reducing mercury in a mercury-containing gas, the method comprising: injecting a sorbent into the mercury-containing gas (paragraph [0060]); collecting mercury in the mercury-containing gas on the sorbent to produce a cleaned gas (paragraph [0060]), wherein the sorbent is a promoted activated carbon that is promoted in-flight with at least one promoter that is Br_2 , HBr , Br^- , or a combination thereof, wherein the mercury-containing gas is a coal-combustion gas (paragraphs [0048]-[0051]).

For claim 4, the Nelson reference discloses the promoted activated carbon is promoted with the promoter while the promoter is in the gas phase or is a vapor (paragraphs [0050] and [0051]).

For claim 5, the Nelson reference discloses promoting the activated carbon in-flight (paragraphs [0048]-[0051]). The examiner interprets the (rotating drum, vertically-moving bed, fluidized-bed and transport reaction of Nelson providing the conditions of “in-flight” reactions of activated carbon and the promoter.

For claim 6, the promoted sorbent as disclosed by Nelson above would include active sites, comprising halide anions bound to the activated carbon.

For claim 7, the promoted sorbent as disclosed by Nelson above would include active sites comprising carbocations bound to halide anions.

For claim 8, the sorbent being promoted and then contacted with the mercury containing gas and removed thereafter as disclosed by Nelson above is chemically and physically equivalent to the claimed collecting the mercury comprises chemically reacting carbene species edge sites in the activated carbon with the mercury.

For claim 9, the Nelson reference injecting an alkaline sorbent into the mercury-containing gas stream (paragraph [0064]).

For claim 10, the Nelson reference discloses alkaline sorbent is selected from the group consisting of alkali elements, alkaline earth elements, alkali salts, alkaline earth salts, and combinations thereof (paragraph [0064]).

For claim 11, the Nelson reference discloses the alkaline sorbent is selected from the group consisting of sodium carbonate, calcium oxide, lime, and combinations thereof (paragraph [0064]).

For claim 12, the Nelson reference discloses the activated carbon is chosen from powdered activated carbon, granular activated carbon, carbon black, carbon fiber, aerogel carbon, pyrolysis char, and combinations thereof (paragraph [0040]).

For claim 13, the Nelson reference discloses the promoter is HBr or Br⁻ (paragraphs [0048]-[0051]).

For claim 14, the Nelson reference discloses the mercury-containing gas is a flue gas stream downstream of a boiler furnace (fig. 2-6 and paragraph [0060]).

For claim 16, the Nelson reference discloses the sorbent material has a composition comprising from about 1 to about 30 grams of additive per 100 grams of activated carbon (paragraph [0054]).

For claim 17, the Nelson reference discloses injecting sorbent into the mercury-containing gas stream to form the promoted activated carbon (paragraphs [0048]-[0051]).

For claims 18 and 19, the Nelson reference discloses collecting greater than 70 wt% of the mercury in the mercury-containing gas (paragraph [0084]).

Claim Rejections - 35 USC § 103

In the event the determination of the status of the application as subject to AIA 35 U.S.C. 102 and 103 (or as subject to pre-AIA 35 U.S.C. 102 and 103) is incorrect, any correction of the statutory basis for the rejection will not be considered a new ground of rejection if the prior art relied upon, and the rationale supporting the rejection, would be the same under either status.

The following is a quotation of pre-AIA 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

The factual inquiries set forth in *Graham v. John Deere Co.*, 383 U.S. 1, 148 USPQ 459 (1966), that are applied for establishing a background for determining obviousness under pre-AIA 35 U.S.C. 103(a) are summarized as follows:

1. Determining the scope and contents of the prior art.
2. Ascertaining the differences between the prior art and the claims at issue.
3. Resolving the level of ordinary skill in the pertinent art.
4. Considering objective evidence present in the application indicating obviousness or nonobviousness.

This application currently names joint inventors. In considering patentability of the claims under pre-AIA 35 U.S.C. 103(a), the examiner presumes that the subject matter of the various claims was commonly owned at the time any inventions covered therein were made absent any evidence to the contrary. Applicant is advised of the obligation under 37 CFR 1.56 to point out the inventor and invention dates of each claim that was not commonly owned at the time a later invention was made in order for the examiner to consider the applicability of pre-AIA 35 U.S.C. 103(c) and potential pre-AIA 35 U.S.C. 102(e), (f) or (g) prior art under pre-AIA 35 U.S.C. 103(a).

Claim 2-3, 5, 15 and 20 is/are rejected under pre-AIA 35 U.S.C. 103(a) as being unpatentable over Nelson US 2004/0003716 as applied in claim 1 and further in view of Felsvang et al. US 5,435,980.

For claim 2 the Nelson reference does not disclose the coal that is combusted comprises the promoter or a precursor thereof.

The Felsvang et al. reference discloses the coal that is combusted comprises the promoter or a precursor thereof (column 4, lines 39-46).

It would have been obvious to one having ordinary skill in the art before the invention was made to have modified the Nelson reference to include either rearranging steps, or repeat steps to have the coal that is combusted comprises the promoter or a precursor thereof (Felsvang et al. column 4, lines 39-46) so as to increase the removal of mercury in the mercury containing gas rather than release mercury to the atmosphere. Further the courts have held that selection of any order of performing process steps is prima facie obvious in the absence of new or unexpected results; In re Gibson, 39 F.2d 975, 5 USPQ 230.

For claim 3, the combination of Nelson and Felsvang et al. would include combusting the coal that comprises the promoter or the precursor thereof as both Nelson and Felsvang et al. disclose combusting the coal.

For claim 5, even if the Nelson reference does not disclose promoting the activated carbon in-flight, the Felsvang et al. reference does disclose this limitation (column 4, lines 39-46 and column 6, lines 6-21)

It would have been obvious to one having ordinary skill in the art before the invention was made to have modified the Nelson reference to include either rearranging steps, or repeat steps to have promoting the activated carbon in-flight (Felsvang et al. column 4, lines 39-46) so as to increase the removal of mercury in the mercury containing gas rather than release mercury to the atmosphere. Further the courts have held that selection of any order of performing process steps is prima facie obvious in the absence of new or unexpected results; In re Gibson, 39 F.2d 975, 5 USPQ 230.

For claim 15, the Nelson reference does not disclose monitoring the mercury content of the cleaned gas is performed substantially continuously.

The Felsvang reference discloses monitoring the mercury content of the cleaned gas is performed substantially continuously (column 6 lines 43-46).

It would have been obvious to one having ordinary skill in the art before the invention was made to have modified the Nelson reference to include monitoring the mercury content of the cleaned gas is performed substantially continuously (Felsvang et al. **promoting the activated carbon in-flight**) so as to allow for the maximum amount of mercury to be removed from the waste gas stream.

For claim 20, the Nelson reference discloses the method is a method for reducing mercury in the mercury-containing gas to a desired level (as shown above).

The Nelson reference does not disclose monitoring the mercury content of the cleaned gas; and controlling, in response to the monitored mercury content of the cleaned gas, an injection rate of injecting the sorbent into the mercury-containing gas, the sorbent composition, or a combination thereof, so that the mercury content of the cleaned gas is maintained at or below the desired level.

The Felsvang et al. reference discloses monitoring the mercury content of the cleaned gas; and controlling, in response to the monitored mercury content of the cleaned gas, an injection rate of injecting the sorbent into the mercury-containing gas, the sorbent composition, or a combination thereof, so that the mercury content of the cleaned gas is maintained at or below the desired level (**promoting the activated carbon in-flight**).

It would have been obvious to one having ordinary skill in the art before the invention was made to have modified the Nelson reference to include monitoring the mercury content of the cleaned gas; and controlling, in response to the monitored mercury content of the cleaned gas, an injection rate of injecting the sorbent into the mercury-containing gas, the sorbent composition, or a combination thereof, so that the mercury content of the cleaned gas is maintained at or below the desired level (Felsvang et al. **promoting the activated carbon in-flight**) so as to allow for the maximum amount of mercury to be removed from the waste gas stream.

Claim 1-20 is/are rejected under pre-AIA 35 U.S.C. 103(a) as being unpatentable over Felsvang et al. US 5,435,980 in view of Nelson US 2004/0003716.

For claim 1, the Felsvang et al. reference discloses a method for reducing mercury in a mercury-containing gas, the method comprising: injecting a sorbent into the mercury-containing gas (figure, objects 14 and 4, and column 4, lines 5-11); collecting mercury in the mercury-containing gas on the sorbent to produce a cleaned gas (column 5, lines 41-65), wherein the sorbent is a promoted activated carbon that is promoted in-flight with at least one promoter (column 4, line 63 – column 5, line 2 and column 6, lines 29-42) wherein the mercury-containing gas is a coal-combustion gas (abstract). The reference does not disclose the promoter is Br₂, HBr, Br⁻ or a combination thereof.

The Nelson reference discloses the promoter is Br₂, HBr, Br⁻ or a combination thereof (paragraphs [0017] and [0041]).

It would have been obvious to one having ordinary skill in the art at the time the invention was made to have modified the Felsvang et al. reference to either replace the Cl with or include in addition to the Cl, Br₂, HBr, Br⁻ or a combination thereof (Nelson paragraphs [0017] and [0041]) so as to provide an effective carbon sorbent for mercury.

For claim 2, the Felsvang et al. reference discloses the coal that is combusted comprises the promoter or a precursor thereof (column 4, lines 39-46).

For claim 3, the Felsvang et al. reference discloses combusting the coal that comprises the promoter or the precursor thereof (column 4, lines 39-46).

For claim 4, the Felsvang et al. reference discloses the promoted activated carbon is promoted with the promoter while the promoter is in the gas phase or is a vapor (column 4, lines 39-50).

For claim 5, the Felsvang et al. reference discloses promoting the activated carbon in flight (column 4, lines 39-50, 5-15 and column 6, lines 12-31).

For claims 6 and 7 as detailed above each of the claimed steps are disclosed by the combination of Felsvang and Nelson reference and therefore the result of performing the steps would inherently be the same and would result in the promoted activated carbon comprises active sites, comprising halide anions bound to the activated carbon and the promoted activated carbon comprises active sites comprising carbocations bound to halide anions.

For claim 8 the promoted sorbent is disclosed by the combination of Felsvang and Nelson. Further each of the steps as claimed above are also shown by Felsvang and Nelson and would inherently have the same results when the method is performed and would result in collecting the mercury comprises chemically reacting carbene species edge sites in the activated carbon with the mercury.

For claims 9 and 10, the Felsvang et al. reference discloses injecting an alkaline sorbent into the mercury-containing gas stream, wherein the alkaline sorbent is selected from the group consisting of alkali elements, alkaline earth elements, alkali salts, alkaline earth salts, and combinations thereof (column 4, lines 23-28, column 5, lines 26-40 and claim 3).

For claim 11, the Felsvang et al. reference discloses the alkaline sorbent is selected from the group consisting of sodium carbonate, calcium oxide, lime, and combinations thereof (column 4, lines 27-32).

For claim 12, the Felsvang et al. reference discloses the activated carbon is chosen from powdered activated carbon, granular activated carbon, carbon black, carbon fiber, aerogel carbon, pyrolysis char, and combinations thereof (column 3, lines 5-17).

For claim 13, the Nelson reference discloses the promoter is HBr or Br⁻ (paragraphs [0017] and [0041]).

For claim 14, the Felsvang et al. reference discloses the mercury-containing gas is a flue gas stream downstream of a boiler furnace (column 5, lines 23-26, abstract and column 3, lines 4-55).

For claim 15, the Felsvang et al. reference discloses monitoring the mercury content of the cleaned gas is performed substantially continuously (column 6, lines 42-47).

For claim 16, the Felsvang et al. reference does not explicitly state the sorbent has a composition comprising from about 1 to about 30 grams of promoter per 100 grains of activated carbon. The reference does disclose optimizing the amount of Cl and activated carbon introduced (column 6, lines 42-47).

Further the Nelson reference also discloses optimizing of the promoter so as to obtain a desired mercury reactivity (paragraph [0054]).

It would have been obvious to one having ordinary skill in the art before the invention was made to have modified the Felsvang et al. reference to include the sorbent has a composition comprising from about 1 to about 30 grams of promoter per 100 grains of activated carbon (Felsvang et al. column 6, lines 42-46 and Nelson paragraph [0054]) so as to adjust the amount of halogen introduced based on the Hg content and to ensure optimum reaction between the halogen and the activated carbon. Further the courts have held that where the general conditions of a claim are disclosed in the prior art, discovering the optimum or workable ranges involves only routine skill in the art. *In re Aller*, 105 USPQ 233.

For claim 17, the Felsvang et al. reference discloses injecting sorbent into the mercury-containing gas stream to form the promoted activated carbon (column 4, lines 39-46 and column 6, lines 6-11).

For claims 18 and 19, the Felsvang et al. reference discloses collecting greater than 70 wt% of the mercury in the mercury-containing gas and collecting greater than 70 wt% of the mercury in the mercury-containing gas on the sorbent (examples 1, 3 and 4). Further the examiner asserts that these limitations are the results of the method. As the method is disclosed by Felsvang et al. and Nelson as shown above, the result of such a combination would occur, i.e. the degree of separation of mercury.

For claim 20, the Felsvang et al. reference discloses the method is a method for reducing mercury in the mercury-containing gas to a desired level, the method further comprising: monitoring the mercury content of the cleaned gas; and controlling, in response to the monitored mercury content of the cleaned gas, an injection rate of injecting the sorbent into the mercury-containing gas, the sorbent composition, or a combination thereof, so that the mercury content of the cleaned gas is maintained at or below the desired level (column 6, lines 42-47).

Double Patenting

The nonstatutory double patenting rejection is based on a judicially created doctrine grounded in public policy (a policy reflected in the statute) so as to prevent the unjustified or improper timewise extension of the “right to exclude” granted by a patent and to prevent possible harassment by multiple assignees. A nonstatutory double patenting rejection is appropriate where the conflicting claims are not identical, but at least one examined application claim is not patentably distinct from the reference claim(s) because the examined application claim is either anticipated by, or would have been obvious over, the reference claim(s). See, e.g., *In re Berg*, 140 F.3d 1428, 46 USPQ2d 1226 (Fed. Cir. 1998); *In re Goodman*, 11 F.3d 1046, 29 USPQ2d 2010 (Fed. Cir. 1993); *In re Longi*, 759 F.2d 887, 225 USPQ 645 (Fed. Cir. 1985); *In re Van Ornum*, 686 F.2d 937, 214 USPQ 761 (CCPA 1982); *In re Vogel*, 422 F.2d 438, 164 USPQ 619 (CCPA 1970); *In re Thorington*, 418 F.2d 528, 163 USPQ 644 (CCPA 1969).

A timely filed terminal disclaimer in compliance with 37 CFR 1.321(c) or 1.321(d) may be used to overcome an actual or provisional rejection based on nonstatutory double patenting provided the reference application or patent either is shown to be commonly owned with the examined application, or claims an invention made as a result of activities undertaken within the scope of a joint research agreement. See MPEP § 717.02 for applications subject to examination under the first inventor to file

Art Unit: 1776

provisions of the AIA as explained in MPEP § 2159. See MPEP §§ 706.02(I)(1) - 706.02(I)(3) for applications not subject to examination under the first inventor to file provisions of the AIA. A terminal disclaimer must be signed in compliance with 37 CFR 1.321(b).

The USPTO Internet website contains terminal disclaimer forms which may be used. Please visit www.uspto.gov/patent/patents-forms. The filing date of the application in which the form is filed determines what form (e.g., PTO/SB/25, PTO/SB/26, PTO/AIA/25, or PTO/AIA/26) should be used. A web-based eTerminal Disclaimer may be filled out completely online using web-screens. An eTerminal Disclaimer that meets all requirements is auto-processed and approved immediately upon submission. For more information about eTerminal Disclaimers, refer to www.uspto.gov/patents/process/file/efs/guidance/eTD-info-I.jsp.

Claims 1 and 4-20 are rejected on the ground of nonstatutory double patenting as being unpatentable over claims 1-30 of U.S. Patent No. US 7,435,286 ('286)

Although the claims at issue are not identical, they are not patentably distinct from each other because while the current claim set includes different wording, the limitations correspond to '286.

This is a provisional nonstatutory double patenting rejection because the patentably indistinct claims have not in fact been patented.

Claims 2 and 3 are rejected on the ground of nonstatutory double patenting as being unpatentable over claims 1-30 of U.S. Patent No. US 7,435,286 ('286) in view of Felsvang et al. US 5,435,980.

'286 discloses the claimed invention except for the limitations of claims 2 and 3

Felsvang et al. and disclose this limitation as shown above.

It would have been obvious to one having ordinary skill in the art to have modified the '286 reference to include the limitations of claims 2 and 3 (Felsvang et al. column 5, 60-65 and column 4,

Art Unit: 1776

lines 42-45) so as to supplement the halogen content of the system so as to increase the mercury sorption capability.

This is a provisional nonstatutory double patenting rejection because the patentably indistinct claims have not in fact been patented.

Claims 1 and 4-20 are rejected on the ground of nonstatutory double patenting as being unpatentable over claims 1-25 of U.S. Patent No. US 8,168,147 ('147).

Although the claims at issue are not identical, they are not patentably distinct from each other because while the current claim set includes different wording, the limitations correspond to '147.

This is a provisional nonstatutory double patenting rejection because the patentably indistinct claims have not in fact been patented.

Claims 2 and 3 are rejected on the ground of nonstatutory double patenting as being unpatentable over claims 1-25 of U.S. Patent No. US 8,168,147 ('147) in view of Felsvang et al. US 5,435,980.

'286 discloses the claimed invention except for the limitations of claims 2 and 3

Felsvang et al. and disclose this limitation as shown above.

It would have been obvious to one having ordinary skill in the art to have modified the '147 reference to include the limitations of claims 2 and 3 (Felsvang et al. column 5, 60-65 and column 4, lines 42-45) so as to supplement the halogen content of the system so as to increase the mercury sorption capability.

This is a provisional nonstatutory double patenting rejection because the patentably indistinct claims have not in fact been patented.

Claims 1 and 4-20 are rejected on the ground of nonstatutory double patenting as being unpatentable over claims 1-60 of U.S. Patent No. US 8,512,655 ('655) in view of Felsvang et al. US 5,435,980.

Although the claims at issue are not identical, they are not patentably distinct from each other because while the current claim set includes different wording, the limitations correspond to '655.

This is a provisional nonstatutory double patenting rejection because the patentably indistinct claims have not in fact been patented.

Claims 2 and 3 are rejected on the ground of nonstatutory double patenting as being unpatentable over claims 1-30 of U.S. Patent No. US 8,512,655 ('655) in view of Felsvang et al. US 5,435,980.

'655 discloses the claimed invention except for the limitations of claims 2 and 3

Felsvang et al. and disclose this limitation as shown above.

It would have been obvious to one having ordinary skill in the art to have modified the '655 reference to include the limitations of claims 2 and 3 (Felsvang et al. column 5, 60-65 and column 4, lines 42-45) so as to supplement the halogen content of the system so as to increase the mercury sorption capability.

This is a provisional nonstatutory double patenting rejection because the patentably indistinct claims have not in fact been patented.

Claims 1 and 4-20 are rejected on the ground of nonstatutory double patenting as being unpatentable over claims 1-60 of U.S. Patent No. US 8,821,819 ('819).

Although the claims at issue are not identical, they are not patentably distinct from each other because while the current claim set includes different wording, the limitations correspond to '819.

This is a provisional nonstatutory double patenting rejection because the patentably indistinct claims have not in fact been patented.

Claims 2 and 3 are rejected on the ground of nonstatutory double patenting as being unpatentable over claims 1-30 of U.S. Patent No. US 8,521,819 ('819) in view of Felsvang et al. US 5,435,980.

'819 discloses the claimed invention except for the limitations of claims 2 and 3

Felsvang et al. and disclose this limitation as shown above.

It would have been obvious to one having ordinary skill in the art to have modified the '819 reference to include the limitations of claims 2 and 3 (Felsvang et al. column 5, 60-65 and column 4, lines 42-45) so as to supplement the halogen content of the system so as to increase the mercury sorption capability.

This is a provisional nonstatutory double patenting rejection because the patentably indistinct claims have not in fact been patented.

Claims 1 and 4-20 are rejected on the ground of nonstatutory double patenting as being unpatentable over claims 1-33 of U.S. Patent No. US 9,757,689 ('689).

Although the claims at issue are not identical, they are not patentably distinct from each other because while the current claim set includes different wording, the limitations correspond to '689.

This is a provisional nonstatutory double patenting rejection because the patentably indistinct claims have not in fact been patented.

Claims 2 and 3 are rejected on the ground of nonstatutory double patenting as being unpatentable over claims 1-30 of U.S. Patent No. US 9,757,689 ('689) in view of Felsvang et al. US 5,435,980.

'689 discloses the claimed invention except for the limitations of claims 2 and 3

Felsvang et al. and disclose this limitation as shown above.

It would have been obvious to one having ordinary skill in the art to have modified the '689 reference to include the limitations of claims 2 and 3 (Felsvang et al. column 5, 60-65 and column 4, lines 42-45) so as to supplement the halogen content of the system so as to increase the mercury sorption capability.

This is a provisional nonstatutory double patenting rejection because the patentably indistinct claims have not in fact been patented.

Claims 1 and 4-20 are rejected on the ground of nonstatutory double patenting as being unpatentable over claims 1-20 of U.S. Patent No. US 9,468,886 ('886).

Although the claims at issue are not identical, they are not patentably distinct from each other because while the current claim set includes different wording, the limitations correspond to '886.

This is a provisional nonstatutory double patenting rejection because the patentably indistinct claims have not in fact been patented.

Claims 2 and 3 are rejected on the ground of nonstatutory double patenting as being unpatentable over claims 1-30 of U.S. Patent No. US 9,468,886 ('886) in view of Felsvang et al. US 5,435,980.

'886 discloses the claimed invention except for the limitations of claims 2 and 3

Felsvang et al. and disclose this limitation as shown above.

It would have been obvious to one having ordinary skill in the art to have modified the '886 reference to include the limitations of claims 2 and 3 (Felsvang et al. column 5, 60-65 and column 4, lines 42-45) so as to supplement the halogen content of the system so as to increase the mercury sorption capability.

This is a provisional nonstatutory double patenting rejection because the patentably indistinct claims have not in fact been patented.

Claims 1 and 4-20 are rejected on the ground of nonstatutory double patenting as being unpatentable over claims 1-30 of U.S. Patent No. 8,652,235 ('235).

Although the claims at issue are not identical, they are not patentably distinct from each other because while the current claim set includes different wording, the limitations correspond to '235.

This is a provisional nonstatutory double patenting rejection because the patentably indistinct claims have not in fact been patented.

Claims 2 and 3 are rejected on the ground of nonstatutory double patenting as being unpatentable over claims 1-30 of U.S. Patent No. US 8,652,235 ('235) in view of Felsvang et al. US 5,435,980.

'235 discloses the claimed invention except for the limitations of claims 2 and 3

Felsvang et al. and disclose this limitation as shown above.

It would have been obvious to one having ordinary skill in the art to have modified the '235 reference to include the limitations of claims 2 and 3 (Felsvang et al. column 5, 60-65 and column 4, lines 42-45) so as to supplement the halogen content of the system so as to increase the mercury sorption capability.

This is a provisional nonstatutory double patenting rejection because the patentably indistinct claims have not in fact been patented.

Claims 1 and 4-20 are provisionally rejected on the ground of nonstatutory double patenting as being unpatentable over claims 1-16 of copending Application No. 15/295594 ('594).

Although the claims at issue are not identical, they are not patentably distinct from each other because while the current claim set includes different wording, the limitations correspond to '594.

This is a provisional nonstatutory double patenting rejection because the patentably indistinct claims have not in fact been patented.

Claims 2 and 3 are provisionally rejected on the ground of nonstatutory double patenting as being unpatentable over claims 1-16 of copending Application No. 15/295594 ('594) in view of Felsvang et al. US 5,435,980.

'594 discloses the claimed invention except for the limitations of claims 2 and 3

Felsvang et al. and disclose this limitation as shown above.

It would have been obvious to one having ordinary skill in the art to have modified the '594 reference to include the limitations of claims 2 and 3 (Felsvang et al. column 5, 60-65 and column 4, lines 42-45) so as to supplement the halogen content of the system so as to increase the mercury sorption capability.

This is a provisional nonstatutory double patenting rejection because the patentably indistinct claims have not in fact been patented.

Claims 1-20 are provisionally rejected on the ground of nonstatutory double patenting as being unpatentable over claims 8-20 of copending Application No. 15/589359 ('359).

Although the claims at issue are not identical, they are not patentably distinct from each other because while the current claimset includes different wording the limitations correspond to '359.

This is a provisional nonstatutory double patenting rejection because the patentably indistinct claims have not in fact been patented.

Claims 1 and 4-20 are provisionally rejected on the ground of nonstatutory double patenting as being unpatentable over claims 1-20 of copending Application No. 15/853029 ('029) in view of Felsvang et al. US 5,435,980.

Although the claims at issue are not identical, they are not patentably distinct from each other because while the current claimset includes different wording, the limitations correspond to '029.

This is a provisional nonstatutory double patenting rejection because the patentably indistinct claims have not in fact been patented.

Claims 2 and 3 are provisionally rejected on the ground of nonstatutory double patenting as being unpatentable over claims 1-16 of copending Application No. 15/853029 ('029) in view of Felsvang et al. US 5,435,980.

'029 discloses the claimed invention except for the limitations of claims 2 and 3

Felsvang et al. and disclose this limitation as shown above.

It would have been obvious to one having ordinary skill in the art to have modified the '029 reference to include the limitations of claims 2 and 3 (Felsvang et al. column 5, 60-65 and column 4, lines 42-45) so as to supplement the halogen content of the system so as to increase the mercury sorption capability.

This is a provisional nonstatutory double patenting rejection because the patentably indistinct claims have not in fact been patented.

Claims 1-20 are provisionally rejected on the ground of nonstatutory double patenting as being unpatentable over claims 1-20 of copending Application No. 14/712558 ('558). Although the claims at issue are not identical, they are not patentably distinct from each other because while the current claim set includes different wording it the limitations correspond to '558.

This is a provisional nonstatutory double patenting rejection because the patentably indistinct claims have not in fact been patented.

Claims 1-20 are provisionally rejected on the ground of nonstatutory double patenting as being unpatentable over claims 1-20 of copending Application No. 15/951970 ('970). Although the claims at issue are not identical, they are not patentably distinct from each other because while the current claim set includes different wording, the limitations correspond to '970.

This is a provisional nonstatutory double patenting rejection because the patentably indistinct claims have not in fact been patented.

Claims 1-20 are provisionally rejected on the ground of nonstatutory double patenting as being unpatentable over 1-20 of copending Application No. 15/382114 ('114).

Although the claims at issue are not identical, they are not patentably distinct from each other because while the current claim set includes different wording, the limitations correspond to '114.

This is a provisional nonstatutory double patenting rejection because the patentably indistinct claims have not in fact been patented.

Claims 2 and 3 are provisionally rejected on the ground of nonstatutory double patenting as being unpatentable over claims 1-16 of copending Application No. 15/382114 ('114) in view of Felsvang et al. US 5,435,980.

'114 discloses the claimed invention except for the limitations of claims 2 and 3

Felsvang et al. and disclose this limitation as shown above.

It would have been obvious to one having ordinary skill in the art to have modified the '114 reference to include the limitations of claims 2 and 3 (Felsvang et al. column 5, 60-65 and column 4, lines 42-45) so as to supplement the halogen content of the system so as to increase the mercury sorption capability.

This is a provisional nonstatutory double patenting rejection because the patentably indistinct claims have not in fact been patented.

Claims 1 and 4-20 are provisionally rejected on the ground of nonstatutory double patenting as being unpatentable over 1-20 of copending Application No. 15/853029 ('029).

Although the claims at issue are not identical, they are not patentably distinct from each other because while the current claim set includes different wording, the limitations correspond to '029.

This is a provisional nonstatutory double patenting rejection because the patentably indistinct claims have not in fact been patented.

Claims 2 and 3 are provisionally rejected on the ground of nonstatutory double patenting as being unpatentable over claims 1-16 of copending Application No. 15/853029 ('029) in view of Felsvang et al. US 5,435,980.

'029 discloses the claimed invention except for the limitations of claims 2 and 3

Felsvang et al. and disclose this limitation as shown above.

It would have been obvious to one having ordinary skill in the art to have modified the '029 reference to include the limitations of claims 2 and 3 (Felsvang et al. column 5, 60-65 and column 4,

Art Unit: 1776

lines 42-45) so as to supplement the halogen content of the system so as to increase the mercury sorption capability.

This is a provisional nonstatutory double patenting rejection because the patentably indistinct claims have not in fact been patented.

Claims 1 and 4-20 are provisionally rejected on the ground of nonstatutory double patenting as being unpatentable over 1-20 of copending Application No. 15/978,760 ('760).

Although the claims at issue are not identical, they are not patentably distinct from each other because while the current claim set includes different wording, the limitations correspond to '760.

This is a provisional nonstatutory double patenting rejection because the patentably indistinct claims have not in fact been patented.

Claims 2 and 3 are provisionally rejected on the ground of nonstatutory double patenting as being unpatentable over claims 1-16 of copending Application No. 15/978,760 ('594) in view of Felsvang et al. US 5,435,980.

'760 discloses the claimed invention except for the limitations of claims 2 and 3

Felsvang et al. and disclose this limitation as shown above.

It would have been obvious to one having ordinary skill in the art to have modified the '760 reference to include the limitations of claims 2 and 3 (Felsvang et al. column 5, 60-65 and column 4, lines 42-45) so as to supplement the halogen content of the system so as to increase the mercury sorption capability.

This is a provisional nonstatutory double patenting rejection because the patentably indistinct claims have not in fact been patented.

Claims 1-20 are provisionally rejected on the ground of nonstatutory double patenting as being unpatentable over 1-10, 14 and 21-25 of copending Application No. 15/974,343 ('343).

Although the claims at issue are not identical, they are not patentably distinct from each other because while the current claim set includes different wording, the limitations correspond to '760.

This is a provisional nonstatutory double patenting rejection because the patentably indistinct claims have not in fact been patented.

Response to Arguments

Applicant's arguments with respect to claims 1-20 have been considered but are moot because the arguments do not apply to any of the references being used in the current rejection.

Conclusion

Any inquiry concerning this communication or earlier communications from the examiner should be directed to AMBER ROSE ORLANDO whose telephone number is (571)270-3149. The examiner can normally be reached on Monday-Thursday 7:00-5:30.

Examiner interviews are available via telephone, in-person, and video conferencing using a USPTO supplied web-based collaboration tool. To schedule an interview, applicant is encouraged to use the USPTO Automated Interview Request (AIR) at <http://www.uspto.gov/interviewpractice>.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Duane Smith can be reached on (571)272-1166. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer

Application/Control Number: 15/997,091
Art Unit: 1776

Page 24

Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

AMBER ROSE. ORLANDO
Primary Examiner
Art Unit 1776

/AMBER R ORLANDO/
Primary Examiner, Art Unit 1776

Notice of References Cited	Application/Control No. 15/997,091		Applicant(s)/Patent Under Reexamination	
	Examiner AMBER R ORLANDO		Art Unit 1776	Page 1 of 2

U.S. PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date MM-YYYY	Name	CPC Classification	US Classification
*	A	US-5435980-A	07-1995	Felsvang; Karsten S.	B01D53/10	423/210
*	B	US-5569436-A	10-1996	Lerner; Bernard J.	B01D53/64	110/235
*	C	US-6136749-A	10-2000	Gadkaree; Kishor P.	B01D53/8665	502/180
*	D	US-6372187-B1	04-2002	Madden; Deborah A.	B01D53/508	110/345
*	E	US-6558454-B1	05-2003	Chang; Ramsay	B01D53/10	110/342
*	F	US-20040003716-A1	01-2004	Nelson, Sidney G. JR.	B01D53/02	95/134
*	G	US-6719828-B1	04-2004	Lovell; John S.	B01D53/02	423/210
*	H	US-20040086439-A1	05-2004	Vosteen, Bernhard	B01D53/64	423/210
*	I	US-6818043-B1	11-2004	Chang; Ramsay	B01D53/64	423/213.2
*	J	US-6848374-B2	02-2005	Srinivasachar; Srivats	B01D53/10	110/165R
*	K	US-20060048646-A1	03-2006	Olson; Edwin S.	B01D53/10	95/134
*	L	US-20070180990-A1	08-2007	Downs; William	B01D53/10	95/134
*	M	US-7514052-B2	04-2009	Lissianski; Vitali Victor	B01D53/56	423/210

FOREIGN PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date MM-YYYY	Country	Name	CPC Classification
	N					
	O					
	P					
	Q					
	R					
	S					
	T					

NON-PATENT DOCUMENTS

*		Include as applicable: Author, Title Date, Publisher, Edition or Volume, Pertinent Pages)
	U	
	V	
	W	
	X	

*A copy of this reference is not being furnished with this Office action. (See MPEP § 707.05(a).)
Dates in MM-YYYY format are publication dates. Classifications may be US or foreign.

Notice of References Cited	Application/Control No. 15/997,091		Applicant(s)/Patent Under Reexamination	
	Examiner AMBER R ORLANDO		Art Unit 1776	Page 2 of 2

U.S. PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date MM-YYYY	Name	CPC Classification	US Classification
*	A	US-20090297413-A1	12-2009	Olson; Edwin S.	B01D53/10	423/215.5
*	B	US-20090320678-A1	12-2009	Chang; Ramsay	B01D46/002	95/92
*	C	US-7780765-B2	08-2010	Srinivasachar; Srivats	B01D53/10	110/203
*	D	US-20150098878-A1	04-2015	Olson; Edwin S.	B01J20/12	423/210
*	E	US-20170100692-A1	04-2017	Olson; Edwin S.	B01D53/08	1/1
*	F	US-20170239644-A1	08-2017	Olson; Edwin S.	B01D53/02	1/1
*	G	US-20180133646-A1	05-2018	Pavlish; John H.	B01J20/3416	1/1
*	H	US-20180257031-A1	09-2018	Olson; Edwin S.	B01J20/3416	1/1
*	I	US-4013516-A	03-1977	Greenfield; Charles	C10B47/30	159/905
*	J	US-4699896-A	10-1987	Sing; Kenneth S. W.	B01J21/18	264/29.2
*	K	US-6103205-A	08-2000	Wojtowicz; Marek A.	B01D53/04	423/210
	L					
	M					

FOREIGN PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date MM-YYYY	Country	Name	CPC Classification
	N					
	O					
	P					
	Q					
	R					
	S					
	T					

NON-PATENT DOCUMENTS

*		Include as applicable: Author, Title Date, Publisher, Edition or Volume, Pertinent Pages)
	U	
	V	
	W	
	X	

*A copy of this reference is not being furnished with this Office action. (See MPEP § 707.05(a).)
Dates in MM-YYYY format are publication dates. Classifications may be US or foreign.

<i>Search Notes</i> 	Application/Control No. 15/997,091	Applicant(s)/Patent Under Reexamination Olson et al.
	Examiner AMBER R ORLANDO	Art Unit 1776

CPC - Searched*		
Symbol	Date	Examiner

CPC Combination Sets - Searched*		
Symbol	Date	Examiner

US Classification - Searched*			
Class	Subclass	Date	Examiner

* See search history printout included with this form or the SEARCH NOTES box below to determine the scope of the search.

Search Notes		
Search Notes	Date	Examiner
Text Search (See east search history)	07/23/2018	AO
Inventor Search (DAV)	07/23/2018	AO
Text Search (See east search history)	10/29/2018	AO

Interference Search			
US Class/CPC Symbol	US Subclass/CPC Group	Date	Examiner

/AMBER R ORLANDO/ Primary Examiner, Art Unit 1776	
--	--

EAST Search History

EAST Search History (Prior Art)

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L5	6	"9468886"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/10/29 14:12
S1	45	(95/134.ccls. or 95/142.ccls. or 110/345.ccls. or 423/210.ccls.) and activated carbon and promoter	US-PGPUB; USPAT	ADJ	ON	2013/09/09 09:19
S2	0	(95/134.ccls. or 95/142.ccls. or 110/345.ccls. or 423/210.ccls.) and sorben and promoter and activated carbond and mercury	US-PGPUB; USPAT	ADJ	ON	2013/09/09 09:19
S3	0	(95/134.ccls. or 95/142.ccls. or 110/345.ccls. or 423/210.ccls.) and sorbent and promoter and activated carbond and mercury	US-PGPUB; USPAT	ADJ	ON	2013/09/09 09:20
S7	73	("20020150516" "4786483" "5409522" "5505766" "6383981" "6878358" "20020033097" "4530765" "5346674" "6080281" "4708853" "6027551" "6136072" "6258334" "6818043" "20060057044" "20080207443" "20010002387" "3826618" "4814152" "4820318" "4889698" "5891324" "6528030" "20050227146" "5419834" "7942566" "20080134888" "3662523" "3849267" "4196173" "4500327" "6942840" "20020134242" "20030136509" "20050147549" "20060112823" "20080134888" "6471936" "20010003116" "20050019240" "20060048646" "4956162" "5575982" "6372187" "6375909" "7435286" "7514052" "20050074380" "20090081092" "5288306" "1984164" "4101631" "5695726" "6080281" "6848374" "20050000197" "5300137" "5607496" "5672323" "6214304" "6953494" "5245120" "20070168213" "7938571" "20040003716" "20040013589" "3194629" "3786619" "5827352" "20040109800" "20070295347" "5435980" "6136749" "20030206846").PN.	US-PGPUB; USPAT	ADJ	ON	2015/03/17 12:25
S8	13	"11209163"	US-PGPUB; USPAT	ADJ	ON	2015/03/17 12:28
S9	3	"11209163" and non carbon	US-PGPUB; USPAT	ADJ	ON	2015/03/17 12:28
S10	161	(B01D53/64, B01D2257/602,	US-PGPUB;	ADJ	ON	2015/03/17

		B01D2253/104, B01D2253/10, B01D53/10).cpc. and (halogen or halide of HBr) with sorbent	USPAT			13:49
S11	0	(95/134.ccls. or 95/142.ccls. or 110/345.ccls. or 423/210.ccls.) and sorbent and promoter and activated carbond and mercury	US-PGPUB; USPAT	ADJ	ON	2015/03/17 13:50
S12	116	(95/134.ccls. or 95/142.ccls. or 110/345.ccls. or 423/210.ccls.) and (halogen or halide of HBr) with sorbent	US-PGPUB; USPAT	ADJ	ON	2015/03/17 13:50
S13	172	(B01D53/64, B01D2257/602, B01D2253/104, B01D2253/10, B01D53/10).cpc. and (halogen or halide of HBr) with sorbent	US-PGPUB; USPAT	ADJ	ON	2015/08/20 22:04
S14	67	(95/134.ccls. or 95/142.ccls. or 110/345.ccls. or 423/210.ccls.) and activated carbon and promoter	US-PGPUB; USPAT	ADJ	ON	2015/08/20 22:04
S15	67	"6136749"	US-PGPUB; USPAT	ADJ	ON	2016/05/27 09:11
S16	20	"684374"	US-PGPUB; USPAT	ADJ	ON	2016/05/27 09:12
S17	1	"20040003716"	US-PGPUB; USPAT	ADJ	ON	2016/05/27 09:12
S18	68	"6848374"	US-PGPUB; USPAT	ADJ	ON	2016/05/27 09:12
S19	41	"7435286"	US-PGPUB; USPAT	ADJ	ON	2016/05/27 09:13
S20	13	"8168147"	US-PGPUB; USPAT	ADJ	ON	2016/05/27 09:13
S21	69	(95/134.ccls. or 95/142.ccls. or 110/345.ccls. or 423/210.ccls.) and activated carbon and promoter	US-PGPUB; USPAT	ADJ	ON	2016/06/07 09:06
S22	181	(B01D53/64, B01D2257/602, B01D2253/104, B01D2253/10, B01D53/10).cpc. and (halogen or halide of HBr) with sorbent	US-PGPUB; USPAT	ADJ	ON	2016/06/07 09:06
S25	28	"5266280"	US-PGPUB; USPAT	ADJ	ON	2016/06/07 13:41
S26	281	sorbent with mercury and (diameter or size) with ("30" or "40" or "50" or "60" or "70") with (sorbent or carbon)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	ADJ	ON	2016/09/29 15:01
S27	148	sorbent with mercury and (diameter or size) with ("30" or "40" or "50" or "60" or "70") with (sorbent or carbon) and halogen	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	ADJ	ON	2016/09/29 15:02
S28	159	sorbent with mercury and (diameter or size) with ("30" or "40" or "50" or "60" or "70") with (sorbent or carbon) and halogen\$4	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT;	ADJ	ON	2016/09/29 16:18

			IBM_TDB			
S29	206	(sorbent or activated carbon) with mercury and (diameter or size) with ("30" or "40" or "50" or "60" or "70") with (sorbent or carbon) and halogen\$4 and activated carbon	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	ADJ	ON	2016/09/29 16:22
S30	195	(B01D53/64, B01D2257/602, B01D2253/104, B01D2253/10, B01D53/10).cpc. and (halogen or halide of HBr) with sorbent	US-PGPUB; USPAT	ADJ	ON	2016/09/30 13:48
S33	6	"20040003719"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	ADJ	ON	2016/11/16 10:56
S34	49	"2004003716"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	ADJ	ON	2016/11/16 10:57
S35	81	"6848374"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	ADJ	ON	2016/11/16 10:58
S36	56	"7435286"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	ADJ	ON	2016/11/16 11:02
S37	7	olson.in. and ("40" microns).clm.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	ADJ	ON	2016/11/16 11:04
S38	0	("40" microns and halocarbon sorbent).clm.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	ADJ	ON	2016/11/16 11:05
S39	0	(halocarbon sorbent).clm. and "40" microns and olson.in.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	ADJ	ON	2016/11/16 11:05

S40	65	"40" microns and olson.in.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	ADJ	ON	2016/11/16 11:06
S41	3907	("40" microns).clm.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	ADJ	ON	2016/11/16 11:06
S42	29	("40" microns and sorbent).clm.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	ADJ	ON	2016/11/16 11:06
S43	1	(halocarbon sorbent).clm. and olson.in.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	ADJ	ON	2016/11/16 11:08
S44	36	(sorbent).clm. and olson.in.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	ADJ	ON	2016/11/16 11:08
S45	0	(sorbent).clm. and olson.in. and "40" micron	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	ADJ	ON	2016/11/16 11:08
S46	17	"11209163"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	ADJ	ON	2016/11/16 11:09
S47	2	"20110233133"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	ADJ	ON	2016/11/16 11:27
S48	7	"20110023427"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO;	ADJ	ON	2016/11/16 11:28

			DERWENT; IBM_TDB			
S49	15	"2004025274"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	ADJ	ON	2016/11/16 11:32
S50	11	"20040025274"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	ADJ	ON	2016/11/16 11:32
S51	15	"2004025274"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	ADJ	ON	2016/11/16 11:33
S52	40	"6312489"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	ADJ	ON	2016/11/16 11:33
S53	30	("20030024872" "20050045553" "20050144916" "4008060" "4640779" "4655921" "4673503" "4738778" "4746432" "4799944" "5043000" "5051118" "5120296" "5174896" "5320657" "5512075" "5674302" "6152979" "6312489" "6315130" "6336946" "6398836" "6585793" "6598749" "7648546").PN. OR ("7931723").URPN.	US-PGPUB; USPAT; USOCR	ADJ	ON	2016/11/16 11:36
S54	33	("4200444" "4640779" "5968215" "6059851").PN. OR ("6312489").URPN.	US-PGPUB; USPAT; USOCR	ADJ	ON	2016/11/16 11:40
S55	5	"8518142"	US-PGPUB; USPAT; USOCR	ADJ	ON	2016/11/16 11:54
S56	4	"8747505"	US-PGPUB; USPAT; USOCR	ADJ	ON	2016/11/16 11:57
S57	2	"14318270"	US-PGPUB; USPAT; USOCR	ADJ	ON	2016/11/16 12:06
S58	13	pac with size with sorbent	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	ADJ	ON	2016/11/16 12:13
S59	197	(B01D53/64, B01D2257/602,	US-PGPUB;	ADJ	ON	2016/11/16

		B01D2253/104, B01D2253/10, B01D53/10).cpc. and (halogen or halide of HBr) with sorbent	USPAT			15:23
S60	0	(B01D53/64, B01D2257/602, B01D2253/104, B01D2253/10, B01D53/10).cpc. and (halogen or halide of HBr) with sorbent "4198388"	US-PGPUB; USPAT	ADJ	ON	2016/11/17 12:39
S61	10	"4198388"	US-PGPUB; USPAT	ADJ	ON	2016/11/17 12:39
S62	0	"2010083696"	US-PGPUB; USPAT	ADJ	ON	2016/11/17 13:32
S63	2	"20100083696"	US-PGPUB; USPAT	ADJ	ON	2016/11/17 13:32
S64	2	absorp\$5 with mea with methanol with acid	US-PGPUB; USPAT	ADJ	ON	2016/11/17 13:36
S65	2	"20070283813"	US-PGPUB; USPAT	ADJ	ON	2016/11/17 13:39
S66	21	"4469596"	US-PGPUB; USPAT	ADJ	ON	2016/11/21 08:29
S67	4	"2003229245"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	ADJ	ON	2017/05/10 10:36
S68	2	"20030229245"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	ADJ	ON	2017/05/10 10:36
S69	45	"5,338,458"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	ADJ	ON	2017/05/10 10:38
S70	45	"5338458"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	ADJ	ON	2017/05/10 10:38
S71	213	(B01D53/64, B01D2257/602, B01D2253/104, B01D2253/10, B01D53/10).cpc. and (halogen or halide of HBr) with sorbent	US-PGPUB; USPAT	ADJ	ON	2017/05/10 11:02
S72	64	("1786483" "1984164" "2317857" "20010002387" "20010003116" "20020134242" "20020150516" "20030136509" "20040003716" "20040013589" "20050019240" "20060048646" "20060191835" "20090062119" "20100047146" "20120183458" "20140056787"	US-PGPUB; USPAT	ADJ	ON	2017/05/10 11:20

		"3194629" "3662523" "3786619" "3826618" "3849267" "4196173" "4500327" "4814152" "4820318" "4889698" "4959162" "5300137" "5409522" "5462908" "5505766" "5575982" "5607496" "5672323" "5695726" "5827352" "5891324" "6027551" "6080281" "6136072" "6136749" "6214304" "6258334" "6372187" "6375909" "6383981" "6471936" "6528030" "6818043" "6848374" "6878358" "6942840" "6953494" "7101631" "7435286" "7479263" "7514052" "7563311" "7611564" "8007749" "8168147" "8168149" "8512655").PN.				
S73	3	("20090235848" "20110076210" "20150246315").PN.	US-PGPUB; USPAT	ADJ	ON	2017/05/10 11:31
S79	3	("20090235848" "20110076210" "20140224121").PN.	US-PGPUB; USPAT	ADJ	ON	2017/06/27 09:36
S80	96	("1984164" "2317857" "20010002387" "20010003116" "20020043496" "20020134242" "20020150516" "20030104937" "20030136509" "20040003716" "20040013589" "20040076570" "20050019240" "20060048646" "20060191835" "20080182747" "20080292512" "20090062119" "20090136401" "20090320678" "20100047146" "20110168018" "20120183458" "20130280156" "20140056787" "20140255279" "20140308188" "20150098878" "3194629" "3662523" "3786619" "3826618" "3849267" "3876393" "4094777" "4101631" "4196173" "4338896" "4500327" "4708853" "4786483" "4814152" "4820318" "4889698" "4956162" "5300137" "5336835" "5409522" "5462908" "5505766" "5575982" "5607496" "5672323" "5695726" "5827352" "5891324" "6027551" "6080281" "6136072" "6136749" "6214304" "6258334" "6372187" "6375909" "6383981" "6471936" "6528030" "6638485" "6808692" "6818043" "6848374" "6878358" "6942840" "6953494" "6960329" "7081434" "7211707" "7435286" "7479263" "7514052" "7521032" "7544338" "7563311" "7611564" "7622092" "7722843" "7767174" "7780765" "8007749" "8168147" "8168149" "8216535" "8512655" "8652235" "8821819" "9011805").PN.	US-PGPUB; USPAT	ADJ	ON	2017/06/27 09:41
S81	593	honeycomb with plug\$4 and plug\$4 with length	US-PGPUB; USPAT	ADJ	ON	2017/06/27 14:45
S82	0	honeycomb with plug\$4 and plug\$4 with length with less than with "5"	US-PGPUB; USPAT	ADJ	ON	2017/06/27 14:45
S83	0	honeycomb with plug\$4 and plug\$4 with length with less than	US-PGPUB; USPAT	ADJ	ON	2017/06/27 14:45

S84	127	honeycomb with plug\$4 and plug\$4 with length with "5"	US-PGPUB; USPAT	ADJ	ON	2017/06/27 14:46
S85	241	honeycomb with plug\$4 and plug\$4 with length with mm	US-PGPUB; USPAT	ADJ	ON	2017/06/27 14:47
S86	41	honeycomb with plug\$4 and plug\$4 with length with "3 mm "	US-PGPUB; USPAT	ADJ	ON	2017/06/27 14:49
S87	28	honeycomb with plug\$4 and plug\$4 with length with "3 mm " and plug\$4 with porosity	US-PGPUB; USPAT	ADJ	ON	2017/06/27 14:52
S88	28	honeycomb and plug\$4 with length with "3 mm " and plug\$4 with porosity	US-PGPUB; USPAT	ADJ	ON	2017/06/27 14:53
S89	43	honeycomb and plug\$4 with porosity with "100"	US-PGPUB; USPAT	ADJ	ON	2017/06/27 15:06
S90	20	honeycomb and plug\$4 with pore (size or diameter) with "100"	US-PGPUB; USPAT	ADJ	ON	2017/06/27 15:07
S91	8	saw with honeycomb with filter	US-PGPUB; USPAT	ADJ	ON	2017/06/29 13:31
S92	230	(B01D53/64, B01D2257/602, B01D2253/104, B01D2253/10, B01D53/10).cpc. and (halogen or halide of HBr) with sorbent	US-PGPUB; USPAT	ADJ	ON	2017/12/01 14:36
S93	2	"20060260468"	US-PGPUB; USPAT	ADJ	ON	2018/07/03 10:34
S94	19	engine with air with inlet with filter\$4 with cone	US-PGPUB; USPAT	ADJ	ON	2018/07/03 15:26
S95	36	engine with air with inlet with filter\$4 with (cone or conical or (diameter with (increas\$4 or decreas\$4)))	US-PGPUB; USPAT	ADJ	ON	2018/07/03 15:27
S96	24	("3771638" "3870495" "3872012" "4157902" "4702754" "5125940" "5522909" "5549724" "5632793").PN. OR ("5888260").URPN.	US-PGPUB; USPAT; USOCR	ADJ	ON	2018/07/03 15:31
S97	41	("0153535" "0439091" "1398685" "1530163" "1887052" "2087688" "4003836" "4018580" "4032455" "4039308" "4065276" "4261710" "4410341" "4414110" "4699715" "5106397" "5178656" "5522909" "5549722" "5549724" "5888260" "6397842" "6508052" "D401597" "D401942" "D403414" "D403416").PN. OR ("6808552").URPN.	US-PGPUB; USPAT; USOCR	ADJ	ON	2018/07/03 15:31
S98	15	("D403416").URPN.	USPAT	ADJ	ON	2018/07/03 15:33
S99	0	"20030089233"	USPAT	ADJ	ON	2018/07/04 12:29
S100	3	"20030089233"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/07/04 12:29
S101	26	"6833023"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/07/04 12:29
S102	2	"20070168213"	US-PGPUB;	ADJ	ON	2018/07/09

			USPAT; USOCR; FPRS; EPO; JPO			13:08
S103	14	carbocations with sorbent with bromine	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/07/09 13:14
S104	0	a side forming a cross sectional shape of each of the first	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/07/09 13:47
S105	0	non of side forming	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/07/09 13:56
S106	0	none of side forming	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/07/09 13:56
S107	0	none of sides forming	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/07/09 13:56
S109	13	olson.in. and (alkali and promoter and earth).clm.	US-PGPUB; USPAT	ADJ	ON	2018/07/17 16:22
S110	0	olson.in. and (alkali and promoter and earth with vapor).clm.	US-PGPUB; USPAT	ADJ	ON	2018/07/17 16:22
S111	10	olson.in. and (alkali and promoter with vapor).clm.	US-PGPUB; USPAT	ADJ	ON	2018/07/17 16:22
S112	0	"2015008283"	US-PGPUB; USPAT	ADJ	ON	2018/07/23 06:26
S113	2	"20150082833"	US-PGPUB; USPAT	ADJ	ON	2018/07/23 06:26
S114	24	olson.in. and liquid.clm. and promoted	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/07/23 07:50
S115	75	remov\$4 with mercury and (br or bromine) with liquid with carbon	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/07/23 07:54
S116	0	separating greater than "70" wt% of the mercury	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/07/23 09:17
S117	0	((separating greater) with (of the mercury)).clm.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/07/23 09:17

S118	20	"11209163"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/07/23 09:43
S119	40	(during with after with mercury with sorbent)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/10/01 17:38
S120	304	sorbent with mercury and sorbent with boiler	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/10/01 17:39
S121	2	"20070168213"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/10/01 17:41
S122	18	before with burn\$4 with coal with sorbent	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/10/01 17:42
S123	204	("0174348" "0202092" "0208011" "0224649" "0229159" "0298727" "0346765" "0347078" "0367014" "0537926" "0537998" "0541025" "0625754" "0647622" "0685719" "0688782" "0700888" "0744908" "0846338" "0894110" "0896876" "0911960" "0945331" "0945846" "1112547" "1167471" "1167472" "1183445" "1788466" "1984164" "20020065581" "20020114749" "20020184817" "20030088370" "20030103882" "20040003716" "20040013589" "20040086439" "20040219083" "20050039598" "20060047526" "20060210463" "2016821" "2059388" "2089599" "2511288" "3194629" "3288576" "3437476" "3599610" "3662523" "3725530" "3764496" "3823676" "3838190" "3849267" "3849537" "3956458" "3961020" "3974254" "4040802" "4075282" "4094777" "4101631" "4115518" "4148613" "4174373" "4196173" "4226601" "4233274" "4272250" "4280817" "4305726" "4322218" "4377599" "4387653" "4394354" "4440100" "4472278" "4474896" "4519807" "4519995" "4555392" "4582936" "4602918" "4629721" "4693731" "4716137" "4741278" "4758418" "4764219" "4786483" "4804521" "4807542" "4824441" "4830829" "4873930" "4886519" "4892567" "4915818" "4933158" "4936047" "4964889" "5013358" "5024171"	US-PGPUB; USPAT; USOCR	ADJ	ON	2018/10/01 17:42

		"5049163" "5116793" "5126300" "5137854" "5162598" "5190566" "5238488" "5350728" "5368617" "5409522" "5435980" "5447703" "5460643" "5505746" "5505766" "5571490").PN. OR ("5587003" "5618508" "5635150" "5659100" "5670122" "5733516" "5738834" "5787823" "5810910" "5897688" "5910292" "5989506" "6024931" "6083289" "6240859" "6258334" "6372187" "6375909" "6475451" "6521021" "6528030" "6533842" "6558454" "6610263" "6613110" "6719828" "6732055" "6737031" "6746531" "6790420" "6808692" "6848374" "6878358" "6942840" "6953494" "6962617" "6974564" "6975975" "7468170" "7507083" "7674442" "7758827" "7776301").PN.				
S124	1	"15573128"	US-PGPUB; USPAT; USOCR	ADJ	ON	2018/10/02 12:07
S125	2	"20110207597"	US-PGPUB; USPAT; USOCR	ADJ	ON	2018/10/02 12:08
S126	2	"20070168213"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/10/02 17:30
S127	71	sorbent with before with coal and remov\$4 with mercury	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/10/02 17:30
S128	234	"6953494"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/10/02 17:38
S129	121	"5435980"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/10/02 17:40
S130	35	promoter with sorbent and "30" g	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/10/02 22:19
S131	28	promoter with sorbent with mercury and "30" g	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/10/02 22:19
S132	4	promoter with sorbent with mercury and ("30" g).clm.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/10/02 22:20

S133	4	promot\$4 with sorbent with mercury and ("30" g).clm.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/10/02 22:23
S134	4	promot\$4 with sorbent with mercury and pre.clm.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/10/02 22:41
S135	2	promot\$4 with sorbent with mercury and pre-heater	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/10/02 22:42
S136	2	promot\$4 with sorbent with mercury and pre heater	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/10/03 08:36
S137	57	promot\$4 with sorbent with mercury and pre	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/10/03 08:36
S138	24	sorbent with preheat\$4 with coal	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/10/03 08:39
S139	121	"5435980"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/10/03 08:47
S140	23	"11209163"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/10/03 11:28
S141	5	"14102896"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/10/03 11:48
S142	7	"12429058"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/10/03 12:09
S143	4	"12202595"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/10/03 12:23
S144	20	"12201595"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/10/03 12:24

S145	3	"14564860"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/10/03 12:27
S146	1	"15978760"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/10/03 12:28
S147	1	"15589359"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/10/03 12:32
S148	1	"15853029"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/10/03 12:37
S149	8	"15997091"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/10/03 12:42
S150	6	"14712558"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/10/03 12:42
S151	2	"15951970"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/10/03 15:18
S152	4	"15382114"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/10/03 15:47
S153	1	"15853029"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/10/03 15:51
S154	2	"20070168213"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/10/03 18:18
S155	69	"4279873"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/10/03 18:42
S156	75	"7435286"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/10/04 07:59

S157	4	"15295594"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/10/04 08:08
S158	1	("20180257030").PN.	US-PGPUB; USPAT	ADJ	ON	2018/10/04 09:31
S159	86	"5569436"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/10/04 09:32
S160	6	"5785935"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/10/04 09:33
S161	8	"6475471"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/10/04 09:33
S162	53	"6103205"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/10/04 11:46
S163	0	pyrolysis with char with mercury with activated	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/10/04 11:49
S164	17	pyrolysis with char with mercury	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/10/04 11:49
S165	121	pyrolysis with char with activated carbon	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/10/04 11:50
S166	0	pyrolysis with char with activated carbon with mercury with sorbent	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/10/04 11:50
S167	43	pyrolysis with char with activated carbon and mercury with sorbent	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/10/04 11:50
S168	118	pyrolysis with char with tire	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/10/04 12:04
S169	58	pyrolysis with char with activated carbon and mercury	US-PGPUB; USPAT; USOCR;	ADJ	ON	2018/10/04 12:04

			FPRS; EPO; JPO			
S170	8	"20040081724"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	AD J	ON	2018/10/04 15:07
S171	4	"14128179"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ J	ON	2018/10/04 15:10
S172	84	activat\$4 carbon with boiler with coal and remov\$4 with mercury	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ J	ON	2018/10/15 13:27
S173	88	activat\$4 carbon with boiler with coal and (remov\$4 or filter\$4 or absorb\$4 or adsorb\$4) with mercury	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ J	ON	2018/10/15 13:27
S174	0	mercury with stabiliz\$4 with sulfur dioxide	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ J	ON	2018/10/15 14:23
S175	75	"7435286"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ J	ON	2018/10/15 15:07
S176	6	"9468886"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ J	ON	2018/10/16 06:48
S177	17	"8821819"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ J	ON	2018/10/16 06:51
S178	15	"8652235"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ J	ON	2018/10/16 06:55
S179	93	"6136749"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ J	ON	2018/10/24 09:08
S180	4	"9757689"	US-PGPUB; USPAT	ADJ J	ON	2018/10/24 12:37
S181	9	"8939388"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ J	ON	2018/10/29 09:59

EAST Search History

S182	669	urea with inject\$4 with filter\$4 with exhaust	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/10/29 10:15
S183	2	urea with inject\$4 with filter\$4 with exhaust and urea with quench\$4	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/10/29 10:16
S184	13	"3615165"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/10/29 10:35
S185	136	urea with quench\$4 with remov\$4	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/10/29 10:39
S186	48	urea dust with scrub\$4	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/10/29 11:25
S187	38	"6221155"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO	ADJ	ON	2018/10/29 12:04

10/29/2018 2:26:05 PM

C:\Users\amillerharris\Documents\EAST\Workspaces\12429058.wsp

A/N 15/997,091

PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Inventor(s): Edwin S. Olson et al.

Examiner: AMBER ROSE ORLANDO

Application No.: 15/997,091

Group Art Unit: 1776

Filed: June 4, 2018

Docket No.: 4820.001U10

Confirmation No.: 5161

Title: SORBENTS FOR THE OXIDATION AND REMOVAL OF MERCURY

AMENDMENT & RESPONSE UNDER 37 C.F.R. § 1.111

Mail Stop Amendment

Commissioner for Patents

P.O. Box 1450

Alexandria, VA 22313-1450

Applicant has received the Non-Final Office Action dated November 2, 2018. Please enter the following.

IN THE CLAIMS

Please amend the claims as follows:

1. (Currently Amended) A method for reducing mercury in a mercury-containing gas, the method comprising:
~~injecting a sorbent into the mercury-containing gas;~~
combusting coal that comprises an additive comprising Br₂, HBr, Br⁻, or a combination thereof, to form the mercury-containing gas, wherein the combusting of the coal is performed at a coal combustion facility site;
collecting mercury in the mercury-containing gas on [[the]]a sorbent to produce a cleaned gas, wherein the sorbent [[is]]comprises a promoted activated carbon that is promoted in-flight in a gas stream at the coal combustion facility site comprising contacting activated carbon dispersed in the gas stream with at least one promoter that is comprising [[Br₂,]HBr, Br⁻, or a combination thereof, wherein the mercury-containing gas is a coal combustion gas.
- 2-3. (Canceled)
4. (Currently Amended) The method of claim 1, wherein ~~the promoted an~~ activated carbon is promoted with the promoter while the promoter is in [[the]]a gas phase or is a vapor.
5. (Canceled)
6. (Original) The method of claim 1, wherein the promoted activated carbon comprises active sites, comprising halide anions bound to the activated carbon.
7. (Original) The method of claim 1, wherein the promoted activated carbon comprises active sites comprising carbocations bound to halide anions.
8. (Currently Amended) The method of claim 1, wherein collecting the mercury comprises ~~chemically~~ reacting carbene species edge sites in the activated carbon with the mercury.

9. (Original) The method of claim 1, further comprising injecting an alkaline sorbent into the mercury-containing gas stream.
10. (Original) The method of claim 9, wherein the alkaline sorbent is selected from the group consisting of alkali elements, alkaline earth elements, alkali salts, alkaline earth salts, and combinations thereof.
11. (Original) The method of claim 9, wherein the alkaline sorbent is selected from the group consisting of sodium carbonate, calcium oxide, lime, and combinations thereof.
12. (Original) The method of claim 1, wherein the activated carbon is chosen from powdered activated carbon, granular activated carbon, carbon black, carbon fiber, aerogel carbon, pyrolysis char, and combinations thereof.
13. (Original) The method of claim 1, wherein the promoter is HBr or Br⁻.
14. (Original) The method of claim 1, wherein the mercury-containing gas is a flue gas stream downstream of a boiler furnace.
15. (Currently Amended) The method of claim 1, wherein monitoring [[the]]mercury content of the cleaned gas is performed substantially continuously.
16. (Currently Amended) The method of claim 1, wherein the sorbent has a composition comprising from about 1 to about 30 grams of promoter per 100 grainsgrams of activated carbon.
17. (Currently Amended) The method of claim 1, further comprising injecting a sorbent comprising activated carbon into the mercury-containing gas stream to form the promoted activated carbon.

18. (Original) The method of claim 1, comprising collecting greater than 70 wt% of the mercury in the mercury-containing gas.
19. (Original) The method of claim 1, comprising collecting greater than 70 wt% of the mercury in the mercury-containing gas on the sorbent.
20. (Currently Amended) The method of claim 1, wherein the method is a method for reducing mercury in the mercury-containing gas to a desired level, the method further comprising:
monitoring ~~[[the]]~~mercury content of the cleaned gas; and
controlling, in response to the monitored mercury content of the cleaned gas, an injection rate of injecting a ~~[[the]]~~sorbent comprising activated carbon into the mercury-containing gas, a rate at which the promoter is added to the sorbent comprising activated carbon~~the sorbent composition~~, or a combination thereof, so that the mercury content of the cleaned gas is maintained at or below the desired level.

REMARKS

This responds to the Non-Final Office Action dated November 2, 2018.

Claims 1, 4, 8, 15, 16, 17, and 20 are presently amended. Claims 2-3 and 5 are presently canceled, and no claims were canceled previously. No new claims are presently added. As a result, claims 1, 4, and 6-20 are now pending in this application.

Independent claim 1 is amended to recite “...combusting coal that comprises an additive comprising Br₂, HBr, Br⁻, or a combination thereof, to form the mercury-containing gas, wherein the combusting of the coal is performed at a coal combustion facility site...” Support can be found in the present published application at paragraphs [0042] (promoter can be bromide, Br⁻), [0054] and [0072] (bromine, bromide, or HBr can be promoter), paragraphs [0077]-[0086] (“additive” can mean promoter), and FIG. 11 (the additive can be added to the coal).

Independent claim 1 is amended to recite “...wherein the sorbent [[is]]comprises a promoted activated carbon that is promoted in-flight in a gas stream at the coal combustion facility site comprising contacting activated carbon dispersed in the gas stream with at least one promoter ~~that is comprising~~ [[Br₂,]HBr, Br⁻, or a combination thereof, wherein the mercury-containing gas is a coal combustion gas...” Support can be found in the present published application at paragraph [0076]-[0086].

Claim 20 is amended to recite “...controlling, in response to the monitored mercury content of the cleaned gas, an injection rate of injecting a [[the]]sorbent comprising activated carbon into the mercury-containing gas, a rate at which the promoter is added to the sorbent comprising activated carbon~~the sorbent composition~~, or a combination thereof, so that the mercury content of the cleaned gas is maintained at or below the desired level.” Support can be found in the present published application at paragraph [0025].

No new matter is added via the amendments herein.

The Rejection of Claims Under §112

I. The Office Action rejected claims 2-6, 12, 15 and 20 under 35 U.S.C. § 112(b) or 35 U.S.C. § 112 (pre-AIA), second paragraph, as allegedly being indefinite.

This rejection is respectfully traversed.

The Office Action states that claim 2 recites “the coal” in line 1, which is lacking sufficient antecedent basis.

Claim 2 is presently canceled.

The Office Action states that claim 3 recites the limitation “the coal” in line 1, which is lacking sufficient antecedent basis.

Claim 3 is presently canceled.

The Office Action states that claim 3 recites the limitation “the precursor” in line 2, which is lacking sufficient antecedent basis.

Claim 3 is presently canceled.

The Office Action states that claim 4 recites the limitation “the gas phase” in line 2, which is lacking sufficient antecedent basis.

Claim 4 is presently amended to recite “...wherein ~~the promoted~~ an activated carbon is promoted with the promoter while the promoter is in ~~[[the]]~~ a gas phase or is a vapor.”

The Office Action states that claim 5 recites the limitation “the activated carbon” in line 1, which is lacking sufficient antecedent basis.

Claim 1 is presently amended to recite “...wherein the sorbent ~~[[is]]~~ comprises a promoted activated carbon that is promoted in-flight in a gas stream at the coal combustion facility site comprising contacting activated carbon dispersed in the gas stream with at least one promoter...”

In view of the amendments to claim 1, claim 5’s recitation of “the activated carbon” has antecedent basis in claim 1 from which it depends.

The Office Action states that claim 6 recites the limitation “the activated carbon” in line 2, which is lacking sufficient antecedent basis.

In view of the amendments to claim 1, claim 6’s recitation of “the activated carbon” has antecedent basis in claim 1 from which it depends.

The Office Action states that claim 12 recites the limitation “the activated carbon” in line 1, which is lacking sufficient antecedent basis.

In view of the amendments to claim 1, claim 12’s recitation of “the activated carbon” has antecedent basis in claim 1 from which it depends.

The Office Action states that claim 15 recites the limitation “the mercury content” in line 1, which is lacking sufficient antecedent basis.

Claim 15 is presently amended to recite “...wherein monitoring [[the]]mercury content of the cleaned gas is performed substantially continuously.”

The Office Action states that claim 15 recites the limitation “the cleaned gas” in lines 1-2, which is lacking sufficient antecedent basis.

Claim 1 recites “...collecting mercury in the mercury-containing gas on [[the]]a sorbent to produce a cleaned gas...” Claim 15’s recitation of “the cleaned gas” has antecedent basis in claim 1 from which it depends.

The Office Action states that claim 20 recites the limitation “the mercury content” in lines 3 and 6, which is lacking sufficient antecedent basis.

Claim 20 is presently amended to recite “...monitoring [[the]]mercury content of the cleaned gas...”

The Office Action states that claim 20 recites the limitation “the cleaned gas” in lines 3, 4 and 6, which is lacking sufficient antecedent basis.

Claim 15’s recitation of “the cleaned gas” has antecedent basis in claim 1 from which it depends.

The Office Action states that claim 20 recites the limitation “the sorbent composition” in line 5, which is lacking sufficient antecedent basis.

Claim 20 is presently amended to recite “...a rate at which the promoter is added to the sorbent comprising activated carbon~~the sorbent composition~~...”

Applicant therefore respectfully requests reconsideration and withdrawal of the rejection of claims 2-6, 12, 15 and 20 under 35 U.S.C. § 112(b) or 35 U.S.C. § 112 (pre-AIA), second paragraph.

The Rejection of Claims Under §102

II. The Office Action rejected claims 1, 4-14, and 16-19 under 35 U.S.C. § 102(e) over U.S. patent publication no. 2004/0003716 (“Nelson”).

This rejection is respectfully traversed.

Independent claim 1 is amended to recite “...combusting coal that comprises an additive comprising Br₂, HBr, Br⁻, or a combination thereof, to form the mercury-containing gas, wherein the combusting of the coal is performed at a coal combustion facility site....”

Nelson fails to describe or suggest combusting coal that includes an additive that includes Br₂, HBr, Br⁻, or a combination thereof. Nelson fails to describe or suggest all the features of independent claim 1; therefore, this claim cannot be anticipated by Nelson.

Dependent claims 4-14 and 16-19 are directly or indirectly dependent on independent claim 1. As such, these dependent claims incorporate all the features of claim 1. Accordingly, dependent claims 4-14 and 16-19 are patentable for at least the reasons given herein for patentability of independent claim 1.

Applicant therefore respectfully requests reconsideration and withdrawal of the rejection of claims 1, 4-14, and 16-19 under 35 U.S.C. § 102(e) over Nelson.

The Rejection of Claims Under §103

III. The Office Action rejected claims 2-3, 5, 15, and 20 under 35 U.S.C. § 103(a) over U.S. patent publication no. 2004/0003716 (“Nelson”) in view of U.S. patent no. 5,435,980 (“Felsvang”).

This rejection is respectfully traversed.

As explained herein at **IV**, independent claim 1 is patentable over Nelson in view of Felsvang.

Dependent claims 2-3, 5, 15, and 20 are dependent on independent claim 1. As such, these dependent claims incorporate all the features of claim 1. Accordingly, dependent claims 2-3, 5, 15, and 20 are patentable for at least the reasons given herein for patentability of independent claim 1.

Applicant therefore respectfully requests reconsideration and withdrawal of the rejection of claims 2-3, 5, 15, and 20 under 35 U.S.C. § 103(a) over Nelson in view of Felsvang.

IV. The Office Action rejected claims 1-20 under 35 U.S.C. § 103(a) over U.S. patent publication no. 2004/0003716 (“Nelson”) in view of U.S. patent no. 5,435,980 (“Felsvang”).

This rejection is respectfully traversed.

Independent claim 1 is amended to recite “...combusting coal that comprises an additive comprising Br₂, HBr, Br⁻, or a combination thereof, to form the mercury-containing gas, wherein the combusting of the coal is performed at a coal combustion facility site; collecting mercury in the mercury-containing gas on [[the]]a sorbent to produce a cleaned gas, wherein the sorbent [[is]]comprises a promoted activated carbon that is promoted in-flight in a gas stream at the coal combustion facility site comprising contacting activated carbon dispersed in the gas stream with at least one promoter ~~that is comprising~~ [[Br₂, HBr, Br⁻, or a combination thereof, wherein the mercury-containing gas is a coal combustion gas.”

As amended, any process encompassed by independent claim 1 includes in-flight promotion of activated carbon in the flue gas. Whether the activated carbon is untreated at the time of addition to the mercury-containing gas or the activated carbon is treated with an additive prior to addition to the mercury containing gas, the injected activated carbon encounters promoters in the flue gas formed from the combustion of the coal comprising the additive including Br₂, HBr, Br⁻, or a combination thereof, and is thereby promoted in-flight in the flue gas.

As explained herein at **IV(A)**, there would be no motivation for a person of ordinary skill in the art to use Nelson’s bromide additives in Felsvang’s process. As explained herein at **IV(B)(1)**, in-flight promotion with bromide promoters is more effective for mercury removal than treating the sorbent with bromide or bromine additives outside the mercury-containing gas, and as explained herein at **IV(B)(2)**, there would be no way for a person of ordinary skill in the art to predict this advantage from the cited references. As explained herein at **IV(C)(1)**, in-flight promotion with bromide promoters is more effective for mercury removal than in-flight promotion with chloride-

promoters, and as explained herein at **IV(C)(2)**, there would be no way for a person of ordinary skill in the art to predict this advantage from the cited references. As explained herein at **IV(D)**, even if a person of ordinary skill in the art compared the mercury removal of Felsvang's activated carbons promoted with chloride in the flue gas to activated carbons treated with HCl outside of the flue gas, they would not determine that in-flight promotion provides the same or better mercury removal properties. As explained herein at **IV(E)(1)**, activated carbon treated with bromide additives outside the flue gas and subsequently injected into the flue gas containing bromide promoters for in-flight promotion results in greater mercury removal than using activated carbon only treated with bromide additives outside the flue gas or activated carbon only treated with bromide promoters in-flight in the flue gas, and as explained herein at **IV(E)(2)**, there would be no way for a person of ordinary skill in the art to predict this advantage from the cited references.

IV(A). There would be no motivation for a person of ordinary skill in the art to use Nelson's bromide additives in Felsvang's process.

Independent claim 1 is amended to recite "...combusting coal that comprises an additive comprising Br₂, HBr, Br⁻, or a combination thereof, to form the mercury-containing gas, wherein the combusting of the coal is performed at a coal combustion facility site; collecting mercury in the mercury-containing gas on [[the]]a sorbent to produce a cleaned gas, wherein the sorbent [[is]]comprises a promoted activated carbon that is promoted in-flight in a gas stream at the coal combustion facility site comprising contacting activated carbon dispersed in the gas stream with at least one promoter that is comprising [[Br₂,]HBr, Br⁻, or a combination thereof, wherein the mercury-containing gas is a coal combustion gas."

The Office Action admits that Felsvang fails to describe or suggest a halogen or halide promoter that is Br₂, HBr, or Br⁻. Nelson fails to describe or suggest in-flight promotion of activated carbon with a halide in the flue gas. The Office Action alleges that one of ordinary skill in the art would combine Nelson's additive with Felsvang's method to accomplish the presently claimed method, stating that such a modification of Felsvang would be made "...to promote activated carbon (Nelson paragraphs [0017] and [0041]) so as to provide an effective carbon sorbent for mercury." (Office Action, page 9, last sentence of fourth full paragraph). Applicant respectfully

disagrees. As explained below, a person of ordinary skill in the art would not be motivated to use Nelson's bromide additives in Felsvang's process.

Felsvang is directed to adding chlorine (Cl_2) or chloride (Cl^-) materials to the coal or combustion products. Felsvang makes clear that addition of chlorine or chloride material increases the amount of chloride supplied to the flue gas, or to the drying-absorption zone, see, Abstract and col. 3, lines 40-44. When Felsvang mentions activated carbon, the interaction between activated carbon and chloride is the focus: "[i]t has been experienced that the increase of the Hg-removing effect of chloride addition to the drying-absorption zone in a process treating flue gases of low chloride content is especially remarkable when activated carbon is present...." Col. 3, line 67 bridging to col. 4, line 4. For a person of ordinary skill in the art to be motivated to replace Felsvang's chloride-treatment with treatment by another material to provide an effective carbon sorbent for mercury, that person would need to think that the material they are using to replace the chloride would result in the same or better mercury-removal efficiency. However, not only does Felsvang fail to describe or suggest that in-flight promotion of activated carbon with chloride provides better mercury removal than treatment of activated carbon outside the flue gas with chloride; further, as shown herein at **IV(D)**, treatment of activated carbon outside the flue gas with chloride actually provides better mercury removal than in-flight promotion of activated carbon with chloride, which would lead one of ordinary skill in the art away from using in-flight promotion.

Nelson's Background paragraph [0017] states that "[t]he particular advantages of using bromine rather than iodine or iodides, or chlorine or chlorides, with activated carbons for mercury control have not been previously appreciated." The paragraph then goes on to describe various accomplishments in the prior art, stating that prior art processes fail to use bromine as a sequestration agent on carbon, and concludes with "[r]ather, it serves as a catalyst, taking part in a repeated series of desired chemical reactions, but not becoming permanently consumed by any of them. Perhaps it is understandable that the tenacity of carbon-bromine-mercury complexes could be overlooked." Importantly, paragraph [0017] states that bromine (Br_2) is superior to I_2 or I^- , or Cl_2 or Cl^- , with activated carbons for sequestration, and never states that the claimed promoters HBr or Br^- are more effective with activated carbons than chlorides.

Nelson's paragraph [0041] states:

[0041] I have discovered that the simple act of exposing a carbonaceous material, preferably powdered activated carbon (PAC), to gaseous bromine, $\text{Br}_2(\text{g})$, or to gaseous hydrogen bromide, $\text{HBr}(\text{g})$, significantly increases the carbonaceous material's ability to remove mercury species when injected into high-temperature coal-fired flue-gas compositions. Surprisingly, gaseous bromine produces a much more effective and appropriate carbon sorbent for mercury in hot combustion gases than do iodine or iodide species, or chlorine or chloride species, in contrast to what has been taught in the prior art.

Paragraph [0041] begins by stating that bromine, defined as Br_2 , or hydrogen bromide, defined as HBr , increases the mercury absorption capacity of activated carbon. Then, paragraph [0041] states specifically that bromine (Br_2) produces a more effective mercury-absorbing carbon sorbent than iodine (I_2), or iodide (I^-), or chlorine (Cl_2), or chloride (Cl^-). With the precise definitions given for bromine and hydrogen bromide, and then reference only to bromine, Nelson makes clear that the comparison of efficacy is only with respect to bromine and not hydrogen bromide. Like paragraph [0017], paragraph [0041] also fails to state that HBr or Br^- are more effective with activated carbons than chlorides.

The majority of Nelson's Examples (1-4 and 8) focus only on Br_2 . Nelson's Examples 5-7 demonstrate the use of HBr -treated sorbent; however, none of these Examples or any other parts of Nelson compare the mercury-absorption performance of HBr -treated activated carbon to chloride-treated activated carbon such as HCl -treated activated carbon. Although figures 14 and 15 illustrate HBr -treated activated carbon and Cl_2 -treated activated carbon, Cl_2 -treated activated carbon is not chloride-treated carbon and these figures fail to show any examples of chloride-treated activated carbon.

Nelson's paragraph [0049] states:

[0049] A critical element in the process is that a bromine-containing gas 3 is used to treat the carbonaceous substrate. Preferably this gas comprises elemental bromine, $\text{Br}_2(\text{g})$, although other bromine-containing gases, such as hydrogen bromide, HBr , will also have the advantageous effect of the invention.

Paragraph [0049] says that using Br_2 is a critical element of the process. It states that HBr can also have the "advantageous effect of the invention"; however, it is not clear what advantage this is

referring to. The very next paragraph, [0050], states “[i]n the liquid form at ambient temperatures, elemental bromine is dense and compact, with advantages in transport and storage.” These statements also hold true for HBr in the form of a gas. No Example is given in Nelson comparing the mercury-absorption performance of activated carbons treated with bromides such as HBr to the mercury-absorption performance of chlorides such as HCl. In every statement comparing to other halogens or halides, Nelson states with great particularity, even giving the chemical formula, that bromine (Br₂) has advantageous effects over other halogens and halides but fails to mention bromides in these statements. One of ordinary skill in the art would not interpret paragraph [0049] or any other part of Nelson as describing or suggesting that bromides even have the same effectiveness for mercury sequestration when used to treat activated carbons as chlorides, let alone that bromides are more effective for mercury sequestration when used to treat activated carbons than chlorides or chlorine.


Nelson fails to describe or suggest that treatment of activated carbon with bromides such as HBr could provide any mercury-removal improvement, or even the same mercury-removal activity, compared to activated carbons treated with chlorides. Not only does Felsvang fail to describe or suggest that in-flight promotion of activated carbon with chloride provides better mercury removal than treatment of activated carbon outside the flue gas with chloride; further, as shown herein at **IV(D)**, treatment of activated carbon outside the flue gas with chloride actually provides better mercury removal than in-flight promotion of activated carbon with chloride, which would lead one of ordinary skill in the art away from using in-flight promotion. A person of ordinary skill in the art would have no reason to modify Felsvang’s chloride process with a different promoter to form an effective carbon sorbent for mercury if the resulting mercury-removal efficiency could not be reasonably predicted to be the same or greater as that of Felsvang’s original process. Therefore, a person of ordinary skill in the art would not be motivated to combine Nelson’s bromide additive with Felsvang’s chloride method. Independent claim 1 is patentable for at least this reason.

IV(B)(1). In-flight promotion with bromide promoters is more effective for mercury removal than treating the sorbent with bromide or bromine additives outside the mercury-containing gas.

The inventors of the present application have discovered that by combusting coal in the presence of a bromide promoter, and by placing an activated carbon sorbent in the mercury-


containing gas, as presently claimed, the activated carbon can be promoted by the promoter in-flight in the mercury-containing gas, and further, that in-flight bromide promotion of the activated carbon is more effective for mercury removal than use of an activated carbon that is treated with bromides or bromine outside the flue gas.

As explained in the 37 CFR § 1.132 declaration by John Pavlish filed with the Non-Final Office Action Response for Application No. 15/978,760 on December 3, 2018 (“first 132 Declaration”), pilot-scale testing was performed with activated carbon alone (untreated) injected into the flue gas, the activated carbon treated with Br₂ outside the flue gas as per the Nelson procedure (see, first 132 Declaration at item 6), and with NaBr added to coal prior to introduction to the furnace with injection of untreated activated carbon into the flue gas. The same activated carbon was used for each sample. See, the first 132 Declaration at items 8-11. The plot given in the first 132 Declaration at item 11 is reproduced below.



The data in the plot above from item 11 of the first 132 Declaration show that the NaBr added to coal prior to introduction to the furnace with injection of untreated activated carbon into the flue gas (in-flight promotion with Br⁻) provided a higher percent of mercury removal at all tested sorbent injection rates as compared to the activated carbon alone (untreated) and compared to the activated carbon treated with Br₂ outside the flue gas described herein at item 6 as per the Nelson procedure. With NaBr added to the coal and activated carbon injected into the flue gas, there was a significant reduction in the amount of sorbent required to achieve similar mercury removal compared to the activated carbon treated with Br₂ outside the flue gas. For example, to achieve 70% mercury removal, 2.5 lb/MMacf of Br₂-treated carbon was required, as compared to 1.6 lb/MMacf with NaBr added to the coal and activated carbon injected into the flue gas; an additional $(2.5-1.6/1.6)*100\%$ or 56% treated sorbent was required to achieve the same level of mercury removal. See, first 132 Declaration at items 2-5 and 12.

The percent mercury removal per 1 wt% HBr versus the sorbent injection rate was compared with NaBr added to coal prior to introduction to the furnace with injection of untreated activated carbon into the flue gas using the pilot-scale plant, and with Nelson's activated carbon treated with HBr outside the flue gas. The data for Nelson's activated carbon treated with HBr outside the flue gas was taken directly from Nelson. The first plot given in the first 132 Declaration at item 13 is reproduced below, but only showing the bromide data.



The data in the plot above, derived from the first plot at item 13 of the first 132 Declaration, show that the NaBr added to coal prior to introduction to the furnace with injection of untreated activated carbon into the flue gas provided a significantly higher (about 2x) percent mercury removal per 1 wt% HBr at all tested sorbent injection rates as compared to Nelson's activated carbon treated with HBr outside the flue gas. See, first 132 Declaration at item 14.

The data from the pilot-scale plant was also plotted to show the milligrams of HBr/MMacf per 1% mercury removal versus the sorbent injection rate with NaBr added to coal prior to introduction to the furnace with injection of untreated activated carbon into the flue gas, and for Nelson's activated carbon treated with HBr outside the flue gas. The second plot given in the first 132 Declaration at item 13 is reproduced below.