



(12) **United States Patent**
Mora et al.

(10) **Patent No.:** **US 11,864,641 B2**
(45) **Date of Patent:** **Jan. 9, 2024**

(54) **MAGNETICALLY COUPLED WALLET
ACCESSORY FOR MOBILE DEVICE**

(71) Applicant: **1Lss, Inc.**, Los Angeles, CA (US)

(72) Inventors: **Fernando Mora**, Reseda, CA (US);
Alejandro Baca, North Hollywood, CA
(US); **Mydul R. Islam**, Los Angeles,
CA (US)

(73) Assignee: **1LSS, INC.**, Los Angeles, CA (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 122 days.

(21) Appl. No.: **17/331,280**

(22) Filed: **May 26, 2021**

(65) **Prior Publication Data**

US 2021/0282513 A1 Sep. 16, 2021

Related U.S. Application Data

(63) Continuation of application No. 16/583,168, filed on
Sep. 25, 2019, now Pat. No. 11,058,194.

(Continued)

(51) **Int. Cl.**

A45F 5/00 (2006.01)

A45C 1/06 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **A45C 1/06** (2013.01); **A45F 5/00**
(2013.01); **B60R 11/0241** (2013.01);

(Continued)

(58) **Field of Classification Search**

CPC **A45F 2200/0516**; **A45F 2005/008**; **A45F**
5/021; **A45C 13/1069**; **A45C 2011/002**;

(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

525,097 A 8/1894 Flint
5,718,329 A * 2/1998 Ippolito A45C 11/182
150/147

(Continued)

FOREIGN PATENT DOCUMENTS

AU 2019100586 A4 7/2019
CN 202395233 U 8/2012

(Continued)

OTHER PUBLICATIONS

Amovo webpage offering folio wallet Oct. 16, 2016.

(Continued)

Primary Examiner — Adam J Waggenpack


(74) *Attorney, Agent, or Firm* — Thomas Coester
Intellectual Property

(57)


ABSTRACT

A wallet for attachment to a mobile device. The wallet has a body defining a compartment and a device side surface. The wallet has a first arrangement of magnetic material with a first region exposing a first polarity magnetic field at the device side surface and a second adjacent region exposing an opposite polarity magnetic field at the device side surface. The wallet also has a second arrangement of magnetic material with a first region exposing a first polarity magnetic field at the device side surface and a second adjacent region exposing an opposite polarity magnetic field at the device side surface. Collectively, the first and second arrangements, in use, magnetically couple the accessory to a mobile device and cause the accessory to adopt a specific orientation on the mobile device.

11 Claims, 61 Drawing Sheets



Related U.S. Application Data				2014/0217135	A1 *	8/2014	Murphy	F16M 13/04
(60)	Provisional application No. 62/736,379, filed on Sep. 25, 2018.			2015/0122852	A1 *	5/2015	Feng	224/218 A45F 5/00 224/191
				2016/0045019	A1	2/2016	Srey	
(51)	Int. Cl. F16M 13/00 (2006.01) B60R 11/02 (2006.01) H01F 7/02 (2006.01) H04M 1/04 (2006.01) B60R 11/00 (2006.01)			2016/0260532	A1 *	9/2016	Baca	H01F 7/0252
				2016/0286944	A1	10/2016	Snyder	
				2016/0352380	A1	12/2016	Kovacs	
				2017/0354229	A1 *	12/2017	Berkley	A45C 13/005
				2018/0116383	A1	5/2018	McGahey	
(52)	U.S. Cl. CPC F16M 13/005 (2013.01); H01F 7/0252 (2013.01); H04M 1/04 (2013.01); A45C 2001/067 (2013.01); A45F 2200/0516 (2013.01); B60R 2011/007 (2013.01)			2018/0153287	A1	6/2018	William	
				2018/0234126	A1 *	8/2018	Yeo	H04B 1/3888
				2019/0111855	A1	4/2019	Aloe et al.	
				2019/0198212	A1 *	6/2019	Levy	H01F 7/02
				2020/0127694	A1	4/2020	Lim	
				2020/0329133	A1	10/2020	Surani et al.	
				FOREIGN PATENT DOCUMENTS				
(58)	Field of Classification Search CPC A45C 2011/003; A45C 2200/15; F16B 2001/0035 USPC 224/217 See application file for complete search history.			CN	103763411	A	4/2014	
				CN	204498177	U	7/2015	
(56)	References Cited U.S. PATENT DOCUMENTS 7,698,789 B2 * 4/2010 Cserpes A63B 57/60 24/303 8,817,457 B1 * 8/2014 Colby G06F 1/1626 361/679.55 9,033,384 B2 5/2015 Potter et al. 9,300,346 B2 3/2016 Hirsch 9,397,719 B1 7/2016 Schmidt 9,531,424 B1 12/2016 Tucker 9,568,950 B2 2/2017 Christie, II 9,574,355 B2 * 2/2017 Meyer A47G 1/00 9,692,863 B2 6/2017 Xie et al. 9,706,829 B2 7/2017 Tilney 9,800,283 B2 * 10/2017 Schmidt F16M 13/00 10,117,505 B1 11/2018 Alvarez 10,134,517 B2 * 11/2018 Baca H01F 7/0252 10,743,628 B2 * 8/2020 Leimer A45C 13/1092 11,058,194 B2 * 7/2021 Mora A45C 1/06 2012/0031937 A1 * 2/2012 Baker A45F 5/00 224/217 2014/0043748 A1 * 2/2014 Sartee G06F 1/1675 361/679.27 2014/0128132 A1 5/2014 Cox, III			CN	105959437	A	9/2016	
				CN	207010743	U	2/2018	
				CN	209030273	U	6/2019	
				CN	209119859	U	7/2019	
				DE	202013007919	U1	1/2014	
				KR	19970013879	A	3/1997	
				KR	200255276	Y1	11/2001	
				KR	20130004713	U	8/2013	
				KR	101516366	B1	4/2015	
				KR	20150146304	A	12/2015	
				KR	20170132511	A	12/2017	
				KR	20170141156	A	12/2017	
				KR	20180002587	U	8/2018	
				KR	200489984	Y1	9/2019	
				KR	200491657	Y1	5/2020	
				TW	105202088	U	7/2016	
		OTHER PUBLICATIONS						
		Burkley webpage of youtube video of magnetic folio wallet May 17, 2017.						
		Mos Stash webpage of youtube video of magnetic folio wallet Jul. 26, 2016.						
		Media Bridge webpage offering folio wallet Feb. 19, 2017.						
		Zover webpage offering folio wallet Nov. 26, 2017.						
		Mous Web archive page featuring Mous magnetic wallet Aug. 9, 2018.						
		* cited by examiner						






FIG. 2





FIG 3.






FIG. 5





FIG. 6



100




FIG. 8A




FIG. 8B




FIG. 9




FIG. 10




FIG. 11








FIG. 12






FIG. 14A




FIG. 14B

FIG. 15B




FIG. 16A




FIG. 16B




FIG. 17A




FIG. 17B




FIG. 18




FIG. 19




FIG. 20





FIG. 21






FIG. 23





FIG. 24






FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31




FIG. 32




FIG. 33




FIG. 34




FIG. 35




FIG. 36




FIG. 37




FIG. 38




FIG. 39




FIG. 40A




FIG. 40B




FIG. 40C




FIG. 40D




FIG. 40E




FIG. 40F




FIG. 41A




FIG. 41B




FIG. 41C




FIG. 41D




FIG. 42A




FIG. 42B




FIG. 42C




FIG. 42D




FIG. 42E




FIG. 42F




FIG. 42G

FIG 43A

N	S	N	S	N
N	S	N	S	N

FIG 43B

N	S	N	S	N
S	N	S	N	S

FIG 43C

N	N	S	N	N
S	S	N	S	S

FIG 43D

S	N	S	N	S
S	S	N	S	S

FIG 43E

S	N	S	N
---	---	---	---

FIG 43F

S	N	N	S
---	---	---	---

FIG 43G

S	N	S	N
---	---	---	---

FIG 43H

S	N	S
---	---	---

FIG 43I

S	N
---	---

FIG 43J

N	S	Fe	N	S
---	---	----	---	---

FIG 43K

Fe	N	S	Fe
----	---	---	----

FIG 43L

S	Fe	N
---	----	---




FIG 44A




FIG 44B




FIG 44C




FIG. 45




FIG 46




FIG 47




FIG 48

1

**MAGNETICALLY COUPLED WALLET
ACCESSORY FOR MOBILE DEVICE****CROSS-REFERENCE TO RELATED
APPLICATIONS**

This application is a continuation of U.S. application Ser. No. 16/583,168 filed Sep. 25, 2019 entitled INTERPOSABLE MAGNETICALLY COUPLED DEVICES, which claims the benefit of priority under 35 U.S.C. § 119(e) of U.S. Provisional Patent Application No. 62/736,379, entitled INTERPOSABLE MAGNETICALLY COUPLED DEVICES, filed on Sep. 25, 2018, the content of which is incorporated herein by reference in its entirety for all purposes. This application is related to U.S. patent application Ser. No. 14/288,243, entitled “LOW PROFILE MAGNETIC MOUNT FOR ELECTRONIC DISPLAY DEVICES,” filed May 27, 2014, and to U.S. patent application Ser. No. 15/059,163, entitled “SELF-ALIGNING, MULTI-SURFACE MAGNETIC MOUNT FOR ELECTRONIC DISPLAY DEVICES,” filed Mar. 2, 2016 the disclosures of each which are incorporated herein by reference in its entirety for all purposes.

BACKGROUND

Cell phones are an essential part of many people's lives and frequently carried by people throughout the day. Cell phones can provide navigation, entertainment, and function as a camera in addition to their primary purpose as a telecommunications device. Like cell phones, wallets are an integral part of daily life. Wallets come in a variety of sizes and configurations for organizing and securing credit cards, cash, checks, identification, photos, and other possessions.

A cell phone and wallet are the two important items that people carry with them throughout their day. These items can get buried in one's purse, fall between the seats of a vehicle, and otherwise become displaced. When driving, it is important to have a cell phone at the ready in case navigation is required without having to search for it. Also it is sometimes necessary to have one's wallet close by to pay tolls or swipe a badge to enter a parking garage. In addition, a battery pack or wireless charger may be needed for recharging of the cell phone and plug-in charging is unavailable. Thus, a need exists to better arrange one's cell phone, wallet and other related accessories.

SUMMARY

The embodiments described herein relate generally to mobile electronic display device accessories and mounts and, more specifically, to a mounting system that can be used to easily mount and unmount mobile electronic display devices and related accessories to each other and to various surfaces in various stacked and other configurations and in various orientations (e.g., landscape and portrait). Such accessories may include, for example, wallets, battery packs, wireless chargers, kickstands, finger loops and combinations thereof. In particular, the embodiments described herein utilize magnetic coupling to facilitate rapid mounting and unmounting of such accessories to and from mobile electronic display devices.

In one aspect the disclosure relates to a mobile device accessory including an accessory device having a surface. An arrangement of magnets of alternating polarity are included within the accessory device or attached to the surface. The arrangement of magnets are magnetically

2

coupleable to a device-side attachment including a plurality of magnets. The device-side attachment may be attached to a mobile device or part of a protective case for the mobile device. The plurality of magnets may include a first plurality of magnets arranged in a first direction and a second plurality of magnets arranged in a second direction, thereby enabling the accessory device to be disposed in different orientations when magnetically coupled to the device-side attachment. When the device-side attachment is part of a protective case for a mobile device, the different orientations may include a portrait orientation and a landscape orientation relative to the mobile device.

The disclosure is also directed to a mobile device accessory system including a first accessory device having a first front side and a first back side. The first accessory device includes a first plurality of alternating polarity magnets on the first front side and a second plurality of alternating polarity magnets on the first back side. A second accessory device has a second front side and a second back side, the second accessory device having a third plurality of alternating polarity magnets on the second front side and a fourth plurality of alternating polarity magnets on the second back side. The first accessory device is magnetically coupled to a device-side attachment associated with a mobile device and is interposed between the device-side attachment and the second accessory device. The second plurality of alternating polarity magnets may be aligned with and magnetically coupled to the third plurality of alternating polarity magnets.

In addition, the second accessory device may be interposed between the first accessory device and a surface-side attachment including a fifth plurality of alternating polarity magnets. In this case the fourth plurality of alternating polarity magnets are magnetically coupled to the fifth plurality of alternating polarity magnets.

In another aspect the disclosure pertains to a system including a first plurality of alternating polarity magnets attached to a protective case for a mobile device. A first accessory device has a first front side and a first back side, the first accessory device having a second plurality of alternating polarity magnets on the first front side and a third plurality of alternating polarity magnets on the first back side. The second plurality of alternating polarity magnets are magnetically coupled to the first plurality of alternating polarity magnets. A second accessory device has a second front side and a second back side, the second accessory device having a fourth plurality of alternating polarity magnets on the second front side and a fifth plurality of alternating polarity magnets on the second back side. The fourth plurality of alternating polarity magnets are magnetically coupled to the third plurality of alternating polarity magnets.

The system may further include a third accessory device having a third front side and a third back side. The third accessory device includes a sixth plurality of alternating polarity magnets on the third front side and a seventh plurality of alternating polarity magnets on the third back side. The sixth plurality of alternating polarity magnets are magnetically coupled to the fifth plurality of alternating polarity magnets. In one implementation the first accessory device, the second accessory device and the third accessory device are configured in a stack. In addition, the first accessory device, the second accessory device and the third accessory device are configured to be able to be moved to different positions in the stack.

In another aspect the disclosure relates to an accessory wallet for use with a mobile electronic device. The wallet includes a layered front section including a plurality of front

3

layers. The wallet further includes a layered back section including a plurality of back layers wherein the layered front side and the layered back side are arranged to form a compartment. A plurality of magnets are disposed on at least one of the plurality of front layers and one of the plurality of back layers. This arrangement of magnets renders the wallet magnetically coupleable to at least one of an external object and an external surface.

The plurality of front layers of the wallet may include a front portion and a front support and the plurality of back layers may include a back portion and a back support. The plurality of front layers may further include a metallic front shield and the plurality of back layers may further include a metallic back shield. In this case the metallic front shield and the metallic back shield form opposing surfaces of the compartment.

The disclosure is further directed to a mounting system including a device-side attachment having a first plurality of magnets disposed in a protective cover for an electronic device. The mounting system further includes a wallet including a second plurality of magnets and a third plurality of magnets wherein at least one of the first plurality of magnets is arranged to attractively couple with at least one of the second plurality of magnets. A surface-side attachment includes a fourth plurality of magnets arranged to attractively couple to the third plurality of magnets.

The wallet may be configured with a layered front section and a layered back section arranged to form a compartment. The second plurality of magnets may be disposed within the layered front section and the third plurality of magnets may be disposed within the layered back section.

The disclosure further pertains to a system including a device-side attachment having a first plurality of magnets disposed in a protective cover for an electronic device. The system also includes a wallet having a layered front section, a layered back section and a second plurality of magnets where the layered front section and the layered back section form a compartment. The first plurality of magnets are arranged to attractively couple with the second plurality of magnets.

The mounting systems disclosed herein may include a surface-side attachment affixed to a surface including a nonmagnetic surface and device-side attachment coupled to the electronic display device as described in the above-referenced U.S. patent application Ser. No. 15/059,163. While it is recognized that the surface-side attachment can be affixed to a ferromagnetic surface, the present mounting system is especially suitable for nonmagnetic surfaces. In one implementation, a plurality of magnets is embedded within the surface-side attachment. Alternatively, a plurality of magnets may be directly attached to the nonmagnetic surface that is covered by a protective housing. In another implementation, the surface-side attachment is integrated into the nonmagnetic surface during its manufacture.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of a wallet with extended loop, according to an embodiment.

FIG. 2 is a perspective view of a wallet with retracted loop, according to an embodiment.

FIG. 3 is a perspective, exploded view of a wallet, according to an embodiment.

FIG. 4 is an exploded, perspective view of a wallet including exemplary materials of construction, according to an embodiment.

4

FIG. 5 is a perspective view of a partially assembled wallet including a detail of exemplary materials of construction, according to an embodiment.

FIGS. 6 and 7 are perspective, hidden views of a wallet including placement of magnets therein, according to embodiments.

FIGS. 8A and 8B are views of a back portion and front portion of wallet, according to an embodiment.

FIG. 9 is a view of a user holding a wallet, according to an embodiment.

FIG. 10 is a perspective view of a wallet attached to an electronic display device case, according to an embodiment.

FIG. 11 is an exploded view of an electronic display device case, a wallet, and a magnetic surface-side attachment, according to an embodiment.

FIG. 12 is a view of a wallet interposed between an electronic display device case and a magnetic surface-side attachment, according to an embodiment.

FIG. 13A is a front view of an electronic display device case.

FIGS. 13B-13D are cross-sectional views of the electronic display device case of FIG. 13A, a wallet, and a magnetic surface-side attachment, respectively.

FIGS. 14A and 14B are views of a back portion of wallet attached to an electronic display device case, according to an embodiment.

FIGS. 15A and 15B are views of a front portion an electronic display device case including electronic display device case magnets, according to an embodiment.

FIGS. 16A and 16B are hidden views of a back portion of wallet attached to an electronic display device case showing exemplary positions of electronic display device case magnets, according to an embodiment.

FIGS. 17A and 17B are views of a back portion of wallet attached to an electronic display device case, according to an embodiment.

FIG. 18 is a perspective view of a wallet interposed between an electronic display device case and a magnetic surface-side attachment, according to an embodiment.

FIG. 19 is a perspective view of a charging device, according to an embodiment.

FIG. 20 is a side view of a charging device with extended loop, according to an embodiment.

FIG. 21 is a perspective view of a charging device including power port, according to an embodiment.

FIG. 22 is an exploded, perspective view of an electronic display device case, a charging device, and a magnetic surface-side attachment attached to a vehicle dash, according to an embodiment.

FIG. 23 is a perspective view of an electronic display device case, a charging device, and a magnetic surface-side attachment attached to a vehicle dash, according to an embodiment.

FIG. 24 is a view of a user holding a wallet using the loop, according to an embodiment.

FIGS. 25-28 are perspective views of a wallet functioning as a kickstand, according to embodiments.

FIGS. 29-32 are perspective views of a wallet functioning as an adjustable kickstand, according to embodiments.

FIGS. 33 and 34 are partially transparent rear views of a battery pack with wireless charging and a protective cover for an electronic device.

FIGS. 35 and 36 are partially transparent rear views of a battery pack with wireless charging and a protective cover for an electronic device.

5

FIGS. 37 and 38 are perspective views of a charging device interposed between a protective case for a mobile device and a surface-side attachment, according to an embodiment.

FIG. 39 is a side view of a stacked arrangement of magnetically-coupled accessories for a mobile device, according to an embodiment.

FIGS. 40A, 40C, and 40E are perspective views of a surface with a surface-side attachment, according to an embodiment.

FIGS. 40B, 40D, and 40F show front views of a surface-side attachment.

FIGS. 41A to 41D are front views of multiple device-side attachments embedded in the interior of a protective case for an electronic display device, according to an embodiment.

FIGS. 42A to 42D show multiple views of an embodiment of a protective case mounted in a landscape orientation.

FIGS. 42E to 42F show multiple views of an embodiment of an electronic display device mounted in a landscape orientation.

FIG. 42G is another prospective view of electronic display device within a protective case that is mounted to a surface.

FIGS. 43A to 43I depict examples of self-aligning arrangements of outwardly-facing magnet poles for use in device-side attachments and in surface-side attachments.

FIGS. 43J to 43L depict examples of self-aligning arrangements of magnets for device-side attachments and for surface-side attachments including ferrous inserts "Fe"

FIG. 44A is a prospective view of three surface-side attachments.

FIG. 44B is a prospective view of a surface-side attachment including three magnets within a surface-side attachment housing.

FIG. 44C is a front view of a surface-side attachment including three magnets within a surface-side attachment housing.

FIG. 45 is a prospective view of three surface-side attachments.

FIG. 46 is a prospective view of a surface-side attachment including five magnets and a surface-side attachment housing further including an angled face.

FIG. 47 is a prospective view of a surface-side attachment including seven magnets within a surface-side attachment housing.

FIG. 48 is a prospective view of a surface-side attachment including seven magnets within a surface-side attachment housing.

DETAILED DESCRIPTION

All definitions, as defined and used herein, should be understood to control over dictionary definitions, definitions in documents incorporated by reference, and/or ordinary meanings of the defined terms.

The indefinite articles "a" and "an," as used herein in the specification and in the claims, unless clearly indicated to the contrary, should be understood to mean "at least one."

The phrase "and/or," as used herein in the specification and in the claims, should be understood to mean "either or both" of the elements so conjoined, i.e., elements that are conjunctively present in some cases and disjunctively present in other cases. Multiple elements listed with "and/or" should be construed in the same fashion, i.e., "one or more" of the elements so conjoined. Other elements may optionally be present other than the elements specifically identified by the "and/or" clause, whether related or unrelated to those

6

elements specifically identified. Thus, as a non-limiting example, a reference to "A and/or B", when used in conjunction with open-ended language such as "comprising" can refer, in one embodiment, to A only (optionally including elements other than B); in another embodiment, to B only (optionally including elements other than A); in yet another embodiment, to both A and B (optionally including other elements); etc.

As used herein in the specification and in the claims, "or" should be understood to have the same meaning as "and/or" as defined above. For example, when separating items in a list, "or" or "and/or" shall be interpreted as being inclusive, i.e., the inclusion of at least one, but also including more than one, of a number or list of elements, and, optionally, additional unlisted items. Only terms clearly indicated to the contrary, such as "only one of" or "exactly one of," or, when used in the claims, "consisting of," will refer to the inclusion of exactly one element of a number or list of elements. In general, the term "or" as used herein shall only be interpreted as indicating exclusive alternatives (i.e. "one or the other but not both") when preceded by terms of exclusivity, such as "either," "one of," "only one of," or "exactly one of." "Consisting essentially of," when used in the claims, shall have its ordinary meaning as used in the field of patent law.

As used herein in the specification and in the claims, the phrase "at least one," in reference to a list of one or more elements, should be understood to mean at least one element selected from any one or more of the elements in the list of elements, but not necessarily including at least one of each and every element specifically listed within the list of elements and not excluding any combinations of elements in the list of elements. This definition also allows that elements may optionally be present other than the elements specifically identified within the list of elements to which the phrase "at least one" refers, whether related or unrelated to those elements specifically identified. Thus, as a non-limiting example, "at least one of A and B" (or, equivalently, "at least one of A or B," or, equivalently "at least one of A and/or B") can refer, in one embodiment, to at least one, optionally including more than one, A, with no B present (and optionally including elements other than B); in another embodiment, to at least one, optionally including more than one, B, with no A present (and optionally including elements other than A); in yet another embodiment, to at least one, optionally including more than one, A, and at least one, optionally including more than one, B (and optionally including other elements); etc.

In the claims, as well as in the specification above, all transitional phrases such as "comprising," "including," "carrying," "having," "containing," "involving," "holding," "composed of," and the like are to be understood to be open-ended, i.e., to mean including but not limited to. Only the transitional phrases "consisting of" and "consisting essentially of" shall be closed or semi-closed transitional phrases, respectively, as set forth in the United States Patent Office Manual of Patent Examining Procedures, Section 2111.03.

As used herein in the specification and in the claims, an "electronic display device" should be understood to mean any electronic device or any display device including cell phones, computer tablets, phablets, electronic organizers, personal digital assistant, navigation devices (GPS), radar detectors, garage door openers, remote controls, wireless microphones and/or speakers, cameras, video recorders, music players, controllers and microcomputers. While the mounting system described herein is intended for electronic display devices, it should be understood that the mounting

system is suitable for any object of similar size and dimensions as an electronic display device.

As used herein in the specification and in the claims, a “wallet” should be understood to mean any apparatus for holding at least one of a credit card, cash, identification, a check, a badge, a picture, a key, a piece of paper, a coupon, business cards, and combinations thereof. While the wallet described herein is intended for containing the aforementioned items, it should be understood that a wallet is also suitable for containing any objects of similar size and dimensions as these items. While the wallet’s contents are generally described as credit cards, it should be understood that a wallet can carry any number of the items identified above.

As used herein in the specification and in the claims, “outward” or “outwardly,” should be understood to mean facing away from of an object or surface, rather than facing toward an object or surface to which it is affixed. The outward faces of the attachments are designed to couple to each other and can have complementary physical features which interact with each other. When the device-side attachment is mounted to the surface-side attachment, the outward face of the surface-side attachment is coupled to the outward face of device-side attachment.

As used herein in the specification and in the claims, “front” and “back,” should be understood to mean facing away toward or away from a user during interaction with the object. For example, the wallet may be held in a person’s hand with a finger extended through the loop or finger strap, which is on the back side of the wallet, and the front side of the wallet faces the user.

Each embodiment in this specification is to be applied mutatis mutandis to every other embodiment unless expressly stated otherwise.

In some embodiments, a wallet is magnetically coupleable to a case configured to contain an electronic display device is described herein. In some embodiments, a wallet is magnetically coupleable to a magnetic mount configured to attach to a surface is described herein. In some embodiments, a wallet is interposable between electronic display device and a magnetic surface mount is described herein.

FIG. 1 is a perspective view of a wallet 100 with loop (finger strap) 115 in an extended position, according to an embodiment. Wallet 100 includes a back portion 110, left portion 130, top portion 150, and a bottom portion 160. Loop 115, also referred to as a finger strap, is shown in an extended position with a portion of a plurality of credit cards 10 visible through loop slot 116. Loop 115 provides a user with a secure grip on wallet 100.

In some embodiments, a Wallet 100 holds a plurality of credit cards 10 in an amount from 1 to 8 credit cards, in an amount of at least 2 credit cards, in an amount of at least 5 credit cards, in an amount from 3 to 10 credit cards, in an amount from 2 to 8 credit cards, in an amount from 3 to 8 credit cards, in an amount from 4 to 8 credit cards, and/or in an amount from 3 to 8 credit cards.

In some embodiments, a Wallet 100 has overall dimensions of 70 mm wide×90 mm tall, and 4 mm to 10 mm thick depending on credit cards 10 contained therein.

FIG. 2 is a perspective view of a wallet 100 with loop 115 in a retracted position, according to an embodiment. Loop 115 flattens to fit within loop slot 116. In some embodiments, loop slot 116 allows the loop 115 to flatten within loop slot 116 such that loop 115 is substantially flush with back portion 110 forming a substantially planer configuration. In some embodiments, loop slot 116 allows only a first portion

of loop 115 to flatten within loop slot 116 such that a second portion of loop 115 protrudes from a plane defined by the back portion 110.

FIG. 3 is an perspective, exploded view of a wallet 100, according to an embodiment. Wallet 100 includes a back support 112 and a front support 122. Back support 112 and front support 122 can provide stiffness and rigidity to wallet 100. Back support 112 and front support 122 can also provide a substrate for attaching back-side magnets 119, and front-side bottom magnets 128 and front-side top magnets 129. Back shield 113 and front shield 123 protect magnetically sensitive credit cards from exposure to the magnetic fields created by back-side magnets 119, front-side bottom magnets 128, and front-side top magnets 129. Exemplary configurations of back-side magnets 119, front-side bottom magnets 128, and front-side top magnets 129 are disclosed in U.S. Publication No. 2016-0260532, and in particular the disclosure of the device-side attachments that provide self-alignment with surface-side attachments. To assemble wallet 100, back portion 110 and front portion 120 are folded about an axis to form a compartment for storing credit cards 10. An optional divider 125 separates a one compartment into two compartments. In some embodiments, wallet 100 includes one or more dividers. A divider is a useful means to separate the credit cards from the cash bills and other contents of the wallet 100.

FIG. 4 is an exploded, perspective view of a wallet 100 including exemplary materials of construction, according to an embodiment. Divider 125 can be made from materials such as plastic, cardboard, paper, metal, composites, laminations, and combinations thereof. Back shield 113 and front shield 123 can be made from magnetic field blocking materials including metal, foil coated plastic, foil coated cardboard, carbon filled composites, and combinations thereof. Back support 112 and front support 122 can be made from materials such as plastic, cardboard, paper, metal, composites, laminations, and combinations thereof. Back portion 110 and front portion 120 can be made from a single substrate and folded together, or in other embodiments, back portion 110 and front portion 120 can be made from two or more pieces and joined together. Back portion 110 and front portion 120 can be made from materials such as plastic, leather, composites, laminations, fabric, synthetic material, and combinations thereof.

FIG. 5 is a perspective view of a partially assembled wallet 100 including a detail of exemplary materials of construction, according to an embodiment. Components can be bonded together with adhesive.

FIGS. 6 and 7 are perspective, hidden views of a wallet 100 including placement of magnets therein, according to embodiments. In FIG. 6, the back portion 110 is facing upwards, while in FIG. 7, the front portion 120 is facing upwards. In these embodiments, only the front side includes magnets. In other embodiments, both the front side and the back side include magnets.

FIGS. 8A and 8B are views of a back portion and front portion of wallet-, according to an embodiments. Wallet 100 includes a content removal slot 126 that facilitates the removal of credit cards 10. A user can place their finger through the content removal slot 126 and slide credit cards 10 through the top portion 150 of wallet 100. Content removal slot 126 also provides a window into the compartment of wallet 100 for visually inspecting its contents. Additionally, in one embodiment, front portion 120 and back portion 110 taper near the opening of the compartment. This tapering allows the edges of credit cards within the com-

9

partment to be exposed near the opening further facilitating removal of the individual cards.

FIG. 9 is a view of a user holding a wallet 100, according to an embodiment. Wallet 100 can hold a plurality of credit cards 10 in a compartment formed between front portion 120, back portion 110, bottom portion 160, top portion 150, left portion 130 and right portion 140.

FIG. 10 is a perspective view of the wallet 100 as attached to an electronic display device case 200, according to an embodiment. The front portion 120 of wallet 100 is temporarily affixed to the back side of electronic display device case 200 by magnetic attraction between the magnets embedded in the wallet 100 and magnets embedded in the electronic display device case 200. Loop 115 allows a user to securely grip the wallet 100, which in turn also provides a secure grip on the electronic display device case 200. In this manner, loop 115 is removable from the back side of the electronic display device case 200 when wallet 100 is detached from the electronic display device case 200. Wallet 100 provides the added functionality of a convenient, removable grip that allows a user to easily use electronic display device 250. Loop 115 (along with wallet 100), are quickly and easily removed for wirelessly charging electronic display device 250. After wirelessly charging, Loop 115 (along with wallet 100), are quickly and easily attached to the electronic display device case 200.

In these embodiments, wallet 100 is configured and designed so that it can be used while attached to the electronic display device case 200.

FIG. 11 is an exploded view of an electronic display device case 200, a wallet 100, and a magnetic surface-side attachment 300, according to an embodiment. The back side magnets 119 are configured to magnetically align and attach to surface-side attachment 300. The front-side top magnets 129 and front-side bottom magnets 128, in turn, are configured to magnetically align and attach to electronic display device case 200.

FIG. 12 is a view of a wallet 100 interposed between an electronic display device case 200 and a magnetic surface-side attachment 300, according to an embodiment. In this manner, a single surface-side attachment 300 is able to securely hold both a wallet and an electronic display device case 200 (with electronic display device therein) at the same time.

FIG. 13A is a front view of an electronic display device case 200. FIGS. 13B-13D are cross-sectional views of the electronic display device case 200, a wallet 100, and a magnetic surface-side attachment 300, respectively. In FIG. 13A, electronic display device case 200 is bisected by line AA, and the relative positions of electronic display device case magnets (device-side attachments) 210 that are embedded within the electronic display device case 200 can be seen in the cross-sectional view of FIG. 13B. The cross-sectional view of wallet 100 also shows back-side magnets 119, front-side bottom magnets 128, and front-side top magnets 129 embedded within the back portion 110 and front portion 120, respectively.

FIGS. 14A and 14B are views of a back portion 110 of wallet 100 attached to an electronic display device case 200, according to an embodiment.

FIGS. 15A and 15B are views of a front portion 120 of an electronic display device case 200 including electronic display device case magnets (device-side attachments) 210, according to an embodiment.

FIGS. 16A and 16B are hidden views of a back portion 110 of wallet 100 attached to an electronic display device

10

case 200 showing exemplary positions of electronic display device case magnets (device-side attachments) 210, according to an embodiment.

FIGS. 17A and 17B are views of a back portion 110 of wallet 100 attached to an electronic display device case 200, according to an embodiment.

FIG. 18 is a perspective view of a wallet 100 interposed between an electronic display device case 200 and a magnetic surface-side attachment 300, according to an embodiment. In this embodiment, the surface-side attachment 300 is affixed to a vehicle dash or dashboard 400. In this manner, an electronic display device 250 and wallet 100 are at an arm's reach for a driver of the vehicle. Another advantage is that a single surface-side attachment 300 can be used to mount two items (i.e. a cell phone and wallet). In some embodiments, the electronic display device 250 mounted to wallet 100 is in a portrait orientation. In some embodiments, the electronic display device 250 mounted to wallet 100 is in a landscape orientation.

FIG. 19 is a perspective view of a charging device 500, according to an embodiment. Charging device 500 can have a configuration similar to wallet 100 meaning that it can have similar physical dimensions as well as the placement of the front-side bottom magnets 528, front-side top magnets 529, and back-side magnets 519. Charging device 500 can be a wireless charging device that transmits energy through an electronic display device case 200 and into electronic display device 250 to recharge its battery. Charging device 500 can be a battery pack that wirelessly transmits energy through an electronic display device case 200 and into electronic display device 250 to recharge its battery. In some embodiments, charging device 500 is a battery pack only. In some embodiments, charging device 500 is wireless charging device only. In some embodiments, charging device 500 is both a battery pack and a wireless charging device together.

FIG. 20 is a side view of a charging device 500 with loop 515 shown in an extended position, according to an embodiment.

FIG. 21 is a perspective view of a charging device 500 including power port 511, according to an embodiment. Charging device 500 can be externally powered through power port 511. For example, power port 511 can be a USB connector that receive a cable that electrically couples charging device 500 to a power supply such as a vehicle battery or power outlet.

In other embodiments, charging device 500 can be a battery pack that transfers an electrical charge to an electronic display device 250 through a cable connected to power port 511. In this manner, the charging device 500 has a wired connection to electrically charge the electronic display device 250.

FIG. 22 is an exploded, perspective view of an electronic display device case 200, a charging device 500, and a magnetic surface-side attachment 300 attached to a vehicle dashboard 400, according to an embodiment. Charging device 500 is magnetically coupled to the back side of electronic display device case 200 and wirelessly charges electronic display device 250. Power cable 512 is attached to power port 511. In embodiments, power cable 512 electrically couples charging device 500 to a power source. In embodiments, power cable 512 electrically couples charging device 500 to an electronic display device 250. The concentric circles shown on charging device 500 represents a wireless charging pad, according to some embodiments.

FIG. 23 is a perspective view of a charging device 500 interposed between an electronic display device case 200

11

and a magnetic surface-side attachment **300** that is affixed to a vehicle dashboard **400**, according to an embodiment. It should be noted and appreciated that one or more charging devices **500** and/or wallets can be interposed between an electronic display device case **200** and a magnetic surface-side attachment **300**. In this manner, multiple devices can be stacked one on top of each other.

FIG. **24** is a view of a user holding a wallet **100** using the loop **115**, according to an embodiment. Wallet **100** contains a plurality of credit cards **10** and is magnetically attracted to one or more device-side attachments directly adhered to an electronic display device **250**. In this embodiment, no electronic display case is used.

FIGS. **25-28** are perspective views of a wallet **100** functioning as a kickstand to prop up electronic display device case **200**, according to embodiments. The front-side top magnets **129** are attracted and coupled to electronic display device case magnets **210**, however, front-side bottom magnets **128** are positioned a distance apart from the electronic display device case **200**. In this manner, the wallet **100** form an upside down "V" shape with the electronic display device case **200** and functions as a kickstand. The friction between the bottom of electronic display device case **200** and a horizontal surface, and the bottom portion **160** of wallet **100** and a horizontal surface help retain the kickstand configuration. Charging device **500** has similar functionality to wallet **100** and can function as a kickstand. In some embodiments, charging device **500** is a battery pack and functions as a kickstand.

In FIG. **25**, an electronic display device case **200** is in a portrait configuration. In FIGS. **26** and **27**, an electronic display device case **200** is in a landscape configuration. FIG. **28** is a picture of an electronic display device case **200** is in a portrait configuration on a horizontal surface **600**.

FIGS. **29-32** are perspective views of a wallet **100** functioning as an adjustable kickstand to prop up electronic display device case **200**, according to embodiments, according to embodiments. In these embodiments, the wallet **100** is inverted such that a bottom portion **160** of wallet **100** is attracted and coupled to electronic display device case magnets (device-side attachments) **210**. A plurality of credit cards **10** can be extended through a top portion **150** of wallet **100** to adjust an angle Θ to position electronic display device case **200** in closer to a vertical orientation. The top portion **150** of wallet **100** has sufficient friction to grip a plurality of credit cards **10** and hold them in a partially extended position.

An electronic display device **250** can include a plurality of electric display case magnets (device-side attachments) **210** coupled to the electronic display device case **200** or directly to the electronic display device without using a protective case. The electronic display device **250** can be, for example, cellphone, a tablet computer, a smartphone, a television, or an LCD display. In some embodiments, the electronic display device **400** can be an Apple iPad or iPhone, an Android smartphone, or eBook reader.

Magnets for the surface-side attachment **300**, wallet **100**, charging device **500**, electronic display device case magnets (device-side attachments) **210**, and any other accessory configured to attach to these devices are preferably made out of rare earth metals including alloys of neodymium or samarium-cobalt. Rare earth magnets are selected based on their strongly magnetic properties that include a higher maximum energy product (related to magnetic flux per unit volume) than other types of magnets including ferrite and alnico magnets. Neodymium magnets of grade N48 and

12

higher are preferred, and neodymium magnets of grade N52 and higher are more preferred.

Magnets can generally be uniform or different in shape, size, magnetic and/or other properties within surface-side attachment **300**, wallet **100**, charging device **500**, electronic display device case magnets (device-side attachments) **210**, and any other accessory configured to attach to these devices. While these magnets can be somewhat different in shape, size, magnetic and/or other properties, it is preferred that when mounted, each magnet is uniform in shape, size, magnetic and/or other properties to its complementary magnet.

The magnets for the surface-side attachment **300**, wallet **100**, charging device **500**, electronic display device case magnets (device-side attachments) **210**, and any other accessory configured to attach to these devices are arranged to be self-aligning during mounting. The magnets are arranged so that when the attachments are coupled together during mounting, at least one magnet with an outwardly-facing north pole is attracted to a corresponding magnet with an outwardly-facing south pole, and vice versa.

Attention is now directed to FIGS. **33** and **34**, which are partially transparent rear views of a battery pack with wireless charging **3300** and a protective cover **3310** for an electronic device. In FIG. **33**, the battery pack with wireless charging **3300** is separated from the protective cover **3310**. In FIG. **34**, the battery pack with wireless charging **3300** is magnetically-coupled to the protective cover **3310** in a portrait mode configuration. For purposes of clarity, only coils **3312** of an electronic device disposed within the protective cover **3310** are illustrated in FIG. **33**. The battery pack with wireless charging **3300** can have a configuration similar to wallet **100** meaning that it can have similar physical dimensions as well as similar placement of magnets.

As may be appreciated from FIG. **33**, the coils **3302** and magnets **3304** of the battery pack with wireless charging **3300** are preferably configured to mirror the arrangement of the coils **3312** of the electronic device and the magnets **3314** of the protective cover **3310**. Specifically, note that a distance D between the coils **3302** and the magnets **3304** of the battery pack with wireless charging **3300** is substantially identical to a distance D' between the coils **3312** of the electronic device and the magnets **3314a** of the protective cover **3310** (when the electronic device is disposed within the protective cover **3310**). As a consequence, when the battery pack with wireless charging **3300** becomes connected to the protective cover **3310** (FIG. **34**), its coils **3302** align with the coils **3312** of the electronic device so that energy may be transmitted through the protective cover **3310** and into the electronic device to recharge its battery.

Attention is now directed to FIGS. **35** and **36**, which are partially transparent rear views of a battery pack with wireless charging **3500** and a protective cover **3510** for an electronic device. In FIG. **35**, the battery pack with wireless charging **3500** is separated from the protective cover **3510**. In FIG. **36**, the battery pack with wireless charging **3500** is magnetically-coupled to the protective cover **3510** in a landscape mode configuration. For purposes of clarity, only coils **3512** of an electronic device disposed within the protective cover **3510** are illustrated in FIG. **35**.

As may be appreciated from FIG. **35**, the coils **3502** and magnets **3504** of the battery pack with wireless charging **3500** are preferably configured to mirror the arrangement of the coils **3512** of the electronic device and the magnets **3514** of the protective cover **3510**. Specifically, note that a distance L between the coils **3502** and the magnets **3504** of the

13

battery pack with wireless charging **3500** is substantially identical to a distance L' between the coils **3512** of the electronic device and the magnets **3514a** of the protective cover **3510** (when the electronic device is disposed within the protective cover **3510**). As a consequence, when the battery pack with wireless charging **3500** becomes connected to the protective cover **3510** (FIG. 36), its coils **3502** align with the coils **3512** of the electronic device so that energy may be transmitted through the protective cover **3510** and into the electronic device to recharge its battery.

In one embodiment the battery pack with wireless charging **3500** is implemented as a unitary device. In other embodiments a battery pack may be substituted for the battery pack with wireless charging **3500**. In this case the battery pack would be connected by a cable or the like to the electronic device. In still other embodiments the battery pack with wireless charging **3500** may be implemented as a battery pack mechanically or magnetically coupled to a wireless charger.

FIGS. 37 and 38 are perspective views of a charging device **3710** interposed between a protective case **3720** for a mobile device **3730** and a surface-side attachment **3740**, according to an embodiment. In the embodiment of FIGS. 37 and 38, the charging device is coupled magnetically to the protective case **3720** and to the surface-side attachment **3740** using arrangements of alternating polarity magnets of the type disclosed herein. As shown, in the embodiment of FIG. 37 the charging device **3710** is arranged in a landscape orientation relative to a direction of the surface-side attachment **3740**. In the embodiment of FIG. 38, the charging device **3710** is arranged in a portrait orientation relative to a direction of the surface-side attachment **3740**.

FIG. 39 is a side view of a stacked arrangement of magnetically-coupled accessories for a mobile device, according to an embodiment. In the embodiment of FIG. 39 a first accessory device **3910** includes first set of magnets of alternating polarity **3912** positioned proximate the top of a front surface of the device **3910** and a second set of magnets of alternating polarity **3914** positioned proximate the bottom of the front surface of the device **3910**. The first accessory device **3910** also includes third set of magnets of alternating polarity **3916** positioned proximate the top of a back surface of the device **3910** and a fourth set of magnets of alternating polarity **3918** positioned proximate the bottom of the back surface of the device **3910**. The first set of magnets of alternating polarity **3912** are magnetically coupled to a fifth set of magnets of alternating polarity **3922** positioned on or within a protective case **3920** for a mobile device. The second set of magnets of alternating polarity **3914** are magnetically coupled to a sixth set of magnets of alternating polarity **3924** positioned on or within the protective case **3920**. In other embodiments the fifth set of magnets of alternating polarity **3922** and the sixth set of magnets of alternating polarity **3924** are embedded within or attached to a mobile device. The first accessory device **3910** may comprise, for example, a battery pack with a wireless charger.

The third set of magnets of alternating polarity **3916** are magnetically coupled to a seventh set of magnets of alternating polarity **3932** positioned on or within a top front portion of a second accessory device **3930**. The fourth set of magnets of alternating polarity **3918** are magnetically coupled to an eighth set of magnets of alternating polarity **3934** positioned on or within a bottom front portion of the second accessory device **3930**. In one embodiment the second accessory device **3930** may further include a ninth set of magnets of alternating polarity **3938**, which may be

14

coupled to, for example, an additional accessory device or a surface-side attachment including an additional plurality of magnets of alternating polarity. In one embodiment the second accessory device **3930** may comprise, for example, a magnetically-coupleable wallet defining a compartment of the type described herein.

By utilizing arrangements of pluralities of magnets of alternating polarity as described herein, the protective cover **3920**, first accessory device **3910** and second accessory device **3930** may be automatically aligned upon being magnetically coupled to each other. In addition, the stack comprises of the protective cover **3920**, first accessory device **3910** and second accessory device **3930** may be secured to ferrous metal surfaces or to other surfaces via use of a surface-side attachment including an additional set of magnets.

It should be understood that in other embodiments the first accessory device **3910** and the second accessory device **3930** may comprise various different magnetically-coupleable accessories for a mobile device. These accessories include, for example, magnetically-coupleable wallets, wireless chargers, battery packs, wireless chargers in combination with battery packs, kickstands, finger loops, and combinations of any of these. In general, these accessories may be configured in a stacked arrangement such as is shown in FIG. 39. However, in certain embodiments (e.g., in embodiments including a magnetically-coupleable kickstand) not all of the accessories will be arranged in a stack.

The following discussion with reference to FIGS. 40-48, describes various magnet arrangements which may be utilized within the systems for facilitating the attachment of add-on devices to mobile devices described with reference to FIGS. 1-39. See also U.S. Pat. No. 10,134,517, the content of which is incorporated by reference herein.

FIGS. 40A, 40C, and 40E are perspective views of a surface **1000** with a surface-side attachment **1100** according to an embodiment, and FIGS. 40B, 40D, and 40F show front views of the surface-side attachment **1100**. Surface-side attachment **1100** can include a surface-side attachment housing **1300** containing a plurality of magnets **2000**. As shown in FIGS. 40A and 40B, the surface-side attachment **1100** can include two linear rows, with each linear row containing four individual magnets **2000**. As shown in FIGS. 40C and 40D, the surface-side attachment **1100** can include two linear rows, with each linear row containing five individual magnets **2000**. As shown in FIGS. 40E and 40F, the surface-side attachment **1100** can include a single linear row containing five individual magnets **2000**. It should be recognized that any number of magnets greater than two can be used in surface-side attachment **1100**, and that FIGS. 40A to 40F are merely exemplary embodiments.

Surface-side attachment housing **1300** is preferably made out of a metal such as aluminum, or alternately, it can be made out of polymer or a combination of metal and polymer. Magnets **2000** can be permanently bonded to the surface-side attachment housing **1300** using adhesive or mechanical fasteners. In one embodiment, the edges of surface-side attachment housing **1300** are crimped to retain magnets **2000**.

The surface-side attachment **1100** refers to a plurality of magnets **2000** coupleable to a surface. Surface-side attachment **1100** can be affixed to surface **1000** with adhesive or by using a mechanical fastener. For example, double-sided adhesive tape can be used to permanently or temporarily affix surface-side attachment **1100** to surface **1000**. Alternatively, adhesive glue can be selected based on the surface **1000** characteristics and desired bond characteristics to affix

15

surface-side attachment **1100** to surface **1000**. In one example, the surface-side attachment **1100** is affixed to the dash of an automobile using double-sided adhesive tape. In another example, the surface-side attachment **1100** is affixed to the bezel of a computer monitor using double-sided adhesive tape.

Surface **1000** can be any solid surface including nonmagnetic surfaces and nonferrous surfaces. For example, surface **1000** can be polymer, wood, glass, metal and combinations thereof. Generally, nonporous surfaces provide for greater adhesion of the surface-side attachment **1100**, though surface-side attachment **1100** can be bonded to porous surfaces by using a suitable adhesive or mechanical fastener.

FIGS. **41A** to **41D** are front views of multiple device-side attachments **4100** embedded in the interior of a protective case **4300** for an electronic display device, according to an embodiment. The device-side attachments **4100** are embedded in the perimeter of the protective case **4300** to allow the electronic display device to be hung in either a portrait orientation, as shown in FIG. **41A**, or a landscape orientation, as shown in FIG. **41B**. As shown in FIGS. **41A** and **41B**, the device-side attachments **4100** can include a single linear row containing five individual magnets **5000**. As shown in FIGS. **41C** and **41D**, the device-side attachment **4100** can include two linear rows, with each linear row containing five individual magnets **500**. It should be recognized that any number of magnets greater than two can be used in device-side attachment **4100**, and that FIGS. **41A** to **41D** are merely exemplary embodiments. The device-side attachment **4100** refers to a plurality of magnets **5000** coupleable to an electronic display device.

Protective case **4300** is preferably made out of a polymer, or alternately, it can be made out of metal, cellulosic material, and combinations thereof. Device-side attachment **4100** can be permanently embedded within protective case **4300** or bonded to the protective case **4300** using an adhesive. Mechanical fasteners can also be used to secure device-side attachment **4100** to the protective case **4300**, are especially suitable for applications with require a high strength connection.

FIGS. **42A** to **42D** show multiple views of an embodiment of a protective case **4300** mounted in a landscape orientation. FIG. **42A** is a front view of multiple device-side attachments **4100** attached to the interior of a protective case **4300** for an electronic display device that is mounted to a surface **1000**. FIG. **42B** is a profile view of multiple device-side attachments **4100** affixed to the interior of a protective case **4300** for an electronic display device that is mounted to a surface **100**. FIG. **42C** is a perspective view of multiple device-side attachments **4100** affixed to the interior of a protective case **4300** for an electronic display device that is mounted to a surface **100**. FIG. **42D** is another perspective view of multiple device-side attachments **4100** affixed to the interior of a protective case **4300** for an electronic display device that is mounted to a surface **1000**.

FIGS. **42E** to **42F** show multiple views of an embodiment of an electronic display device **4000** mounted in a landscape orientation. FIG. **42E** is a front view of electronic display device **4000** within a protective case **4300** that is mounted to a surface **1000**. FIG. **42F** is a prospective view of electronic display device **4000** within a protective case **4300** that is mounted to a surface **1000**. FIG. **42G** is another prospective view of electronic display device **4000** within a protective case **4300** that is mounted to a surface **1000**. The mounting system described herein can provide a temporary method of attaching an electronic display device to a surface while providing a low profile. In other words, when mounted to the

16

surface, the mounting system does not add significant thickness to the electronic display device. The device-side attachment **4100** can be coupled in such a way that it does not add significant thickness to the electronic display device **4000** (see, e.g., FIGS. **42B** and **42G**). The surface-side attachment **1100** can be affixed in such a way that it is integrated with the styling and design of surface **1000**. Surface-side attachment **1100** can be colored to match the surface **1000** and/or mimic the features already present on surface **1000**. For example, surface-side attachment **1100** can have a brushed aluminum finish and include magnets **2000** that resemble buttons on the dash of a vehicle.

An electronic display device **4000** can include a device-side attachment **4100** coupled to a back side of the electronic display device **4000** without using a protective case **4300** (not shown). In some embodiments, the magnets **5000** can be coupled to the electronic display device **4000** with, for example, a double-sided adhesive tape. Other attachment methods such as glues, mechanical latches, hinges, or elastic grip can alternatively be used. The device-side attachment **4100** can be used to mount the electronic display device **4000** to a surface **1000** by coupling with a surface-side attachment **1100**. The electronic display device **4000** can be, for example, a tablet computer, a smartphone, a television, or an LCD display. In some embodiments, the electronic display device **4000** can be an Apple iPad or iPhone, an Android smartphone, or eBook reader.

In some embodiments, the device-side attachment has a thickness from about 0.5 to about 6.5 mm, from about 0.5 to about 4 mm, from about 0.5 to about 2 mm, from about 0.5 to about 1.5 mm, or from about 1 to about 2 mm, and including all subranges therebetween each of the ranges. In some embodiments, the device-side attachment has a thickness of about 0.5 mm, about 1.0 mm, about 1.5 mm, about 2.0 mm, about 2.5 mm, about 3.0 mm, about 3.5 mm, about 4.0 mm, about 4.5 mm, about 5.0 mm, about 5.5 mm, about 6.0 mm, or about 6.5 mm. In some embodiments, the device-side attachment has a thickness of less than 0.5 mm, less than 1.0 mm, less than 1.5 mm, less than 2.0 mm, less than 2.5 mm, less than 3.0 mm, less than 3.5 mm, less than 4.0 mm, less than 4.5 mm, less than 5.0 mm, less than 5.5 mm, less than 6.0 mm, or less than 6.5 mm.

In some embodiments, the device-side attachment including the protective cover has a thickness from about 0.5 to about 6.5 mm, from about 0.5 to about 4 mm, from about 0.5 to about 2 mm, from about 0.5 to about 1.5 mm, or from about 1 to about 2 mm, and including all subranges therebetween each of the ranges. In some embodiments, the device-side attachment including the protective cover has a thickness of about 0.5 mm, about 1.0 mm, about 1.5 mm, about 2.0 mm, about 2.5 mm, about 3.0 mm, about 3.5 mm, about 4.0 mm, about 4.5 mm, about 5.0 mm, about 5.5 mm, about 6.0 mm, or about 6.5 mm. In some embodiments, the device-side attachment including the protective cover has a thickness of less than 0.5 mm, less than 1.0 mm, less than 1.5 mm, less than 2.0 mm, less than 2.5 mm, less than 3.0 mm, less than 3.5 mm, less than 4.0 mm, less than 4.5 mm, less than 5.0 mm, less than 5.5 mm, less than 6.0 mm, or less than 6.5 mm.

The magnets **5000** of the device-side attachment **4100** are attracted to the magnets **2000** of the surface-side attachment **1100**. When the device-side attachment **4100** is placed in close proximity to the surface-side attachment **1100**, the magnetic attractive forces draw the attachments together to mount electronic display device **400**. The magnetic attractive forces between magnets **5000** and magnets **2000** are great enough to overcome the force of gravity on the

electronic display device **4000** within the protective case **4300** when mounted to the surface-side attachment **1100**. This force of friction between magnets **5000** and magnets **2000** can be proportional to the normal force and friction coefficient of the materials. The normal force is the magnetic attractive pull force between the magnets **5000** and magnets **2000**. This normal force, in addition to the friction coefficient between the faces of the magnets, produce an overall force of friction high enough to hold the electronic display device **4000** in place when mounted to the surface **1000**.

Magnets **2000** and magnets **5000** are preferably made out of rare earth metals including alloys of neodymium or samarium-cobalt. Rare earth magnets are selected based on their strongly magnetic properties that include a higher maximum energy product (related to magnetic flux per unit volume) than other types of magnets including ferrite and alnico magnets. Neodymium magnets of grade N48 and higher are preferred, and neodymium magnets of grade N52 and higher are more preferred.

The magnets **2000** and the magnets **5000** are permanent magnets that retain their magnetic properties once magnetized. Every magnet has a south pole and a north pole axially situated across opposite faces of the magnet. The north pole of a first magnet is attracted to the south pole of a second magnet, and vice versa. The north pole of a first magnet is repulsed by the north pole of a second magnet, and vice versa. The device-side attachment **4100** and the surface-side attachment **1100** each include at least one magnet with an outwardly-facing north pole, and at least one magnet with an outwardly-facing south pole.

Magnets can generally be uniform or different in shape, size, magnetic and/or other properties within the device-side attachment **4100** or within the surface-side attachment **1100**. While the device-side attachment **4100** and the surface-side attachment **1100** can be somewhat different in shape, size, magnetic and/or other properties, it is preferred that when mounted, each magnet **5000** in device-side attachment **4100** is uniform in shape, size, magnetic and/or other properties to its complementary magnet **2000** in surface-side attachment **1100**. However, the magnets **5000** of the device-side attachment **4100** can be smaller than the magnets **2000** of the surface-side attachment **1100**. It is also preferred that the relative positions (centerlines) of each magnet **5000** within a device-side attachment **4100** are the same as the relative positions of each complementary magnet **2000** within the surface-side attachment **1100** when the attachments are coupled during mounting.

The magnets **5000** and the magnets **2000** within the device-side attachment **4100** and the surface-side attachment **1100** are arranged to be self-aligning during mounting. The magnets **5000** and the magnets **2000** are arranged so that when the attachments are coupled together during mounting, at least one magnet with an outwardly-facing north pole of the device-side attachment **4100** is attracted to a corresponding magnet with an outwardly-facing south pole of the surface-side attachment **1100**, and vice versa. If during mounting the magnet with an outwardly-facing north pole of the device-side attachment **4100** lines up with a magnet with an outwardly-facing north pole of the surface-side attachment **1100**, the like poles repulse each other. If during mounting the magnet with an outwardly-facing north pole of the device-side attachment **4100** lines up with a magnet with an outwardly-facing south pole of the surface-side attachment **1100**, the opposite poles attract each other. The magnetic forces of attraction and repulsion, along with the predetermined arrangement of the outwardly-facing poles of

the magnets within each attachment, provide for self-alignment of the coupled attachments.

FIGS. **43A** to **43I** depict examples of self-aligning arrangements of outwardly-facing magnet poles for use in device-side attachments **4100** and in surface-side attachments **1100**. For each magnet having an outwardly-facing north pole "N" on a given attachment, the complementary attachment will have a magnet with outwardly-facing south pole "S" positioned to align when the attachments are coupled. FIGS. **43A**, **43F**, and **43H** are examples of symmetrical self-aligning magnet pole arrangements whereby the electronic display device can be mounted in either of two positions that are 180 degrees of each other. FIGS. **43B** to **43E**, **43G** and **43I** are examples of asymmetrical self-aligning magnet pole arrangements whereby the electronic display device can be mounted in only one position.

FIGS. **43J** to **43L** depict examples of self-aligning arrangements of magnets for device-side attachments **4100** and for surface-side attachments **1100** including ferrous inserts "Fe". Ferrous inserts can be used in device-side attachments **4100** in situations when the positioning of a magnet **5000** would interfere with the operation of the electronic display device **4000**. For example, positioning a magnet over the location of an internal antenna of an electronic display device may interfere with the reception. By placing a ferrous insert within the device-side attachment **4100**, problems associated with reception can be avoided while allowing the magnets **2000** of the surface-side attachment **1100** a ferrous surface to attractively couple to.

Ferrous inserts can also be used in surface-side attachments **1100** to reduce product costs. Rare earth magnets **2000** tend to be expensive. A surface-side attachment **1100** that includes at least one magnet with an outwardly-facing north pole and at least one magnet with an outwardly-facing south pole can still provide for self-alignment, while other magnets **2000** in the surface-side attachment **1100** can be replaced with ferrous inserts that allow the magnets **5000** in the device-side attachment **4100** a ferrous surface to attractively couple to. The device-side attachment **4100** within the mounting system still retains all of the magnets **5000** and the ability to attractively couple to any ferrous surface. By incorporating the ferrous inserts into the surface-side attachment **1100**, the overall cost of the mounting system can be reduced while affording the same level of functionality.

FIG. **44A** is a prospective view of three surface-side attachments **1100**. In this example, the plurality of magnets is permanently affixed to an aluminum housing.

FIG. **44B** is a prospective view of a surface-side attachment **1100** including three magnets **2000** within a surface-side attachment housing **1300**. In this example, the plurality of magnets is permanently affixed to an aluminum housing.

FIG. **44C** is a front view of a surface-side attachment **1100** including three magnets **2000** within a surface-side attachment housing **1300**. In this example, the plurality of magnets is permanently affixed to an aluminum housing.

FIG. **45** is a prospective view of three surface-side attachments **1100**.

In some embodiments, the surface-side attachment has a thickness from about 0.5 to about 6.5 mm, from about 0.5 to about 4 mm, from about 0.5 to about 2 mm, from about 0.5 to about 1.5 mm, or from about 1 to about 2 mm, and including all subranges therebetween each of the ranges. In some embodiments, the surface-side attachment has a thickness of about 0.5 mm, about 1.0 mm, about 1.5 mm, about 2.0 mm, about 2.5 mm, about 3.0 mm, about 3.5 mm, about 4.0 mm, about 4.5 mm, about 5.0 mm, about 5.5 mm, about 6.0 mm, or about 6.5 mm. In some embodiments, the

19

surface-side attachment has a thickness of less than 0.5 mm, less than 1.0 mm, less than 1.5 mm, less than 2.0 mm, less than 2.5 mm, less than 3.0 mm, less than 3.5 mm, less than 4.0 mm, less than 4.5 mm, less than 5.0 mm, less than 5.5 mm, less than 6.0 mm, or less than 6.5 mm.

FIG. 46 is a prospective view of a surface-side attachment 1100 including five magnets 2000 and a surface-side attachment housing 1300 further including an angled face. The angled face of surface-side attachment 1100 can provide increased coupling strength by the angled face supporting a portion of the weight of the electronic display device 400. The angled face can also improve the coupling strength of the mounting system by positioning the lower end of the electronic display device 4000 against the surface 1000 which reduces the tendency of the electronic display device 4000 to rotate about the bottom edge of surface-side attachment 1100 and separate from the top edge of surface-side attachment 1100.

FIG. 47 is a prospective view of a surface-side attachment 1100 including seven magnets 2000 within a surface-side attachment housing 1300.

FIG. 48 is a prospective view of a surface-side attachment 1100 including seven magnets 2000 within a surface-side attachment housing 1300.

As may be appreciated from FIGS. 40-48, a self-aligning mounting system for mounting an electronic display device to a surface or attached the electronic display device to an object (e.g., a magnetically-coupleable wallet) may include a device-side attachment containing a first plurality of magnets disposed in a protective cover for the electronic display device. The first plurality of magnets includes at least one magnet with an outwardly-facing north pole of a magnet and at least one magnet with an outwardly-facing south pole. The protective cover can include a high friction surface covering the first plurality of magnets. The mounting system also includes a surface-side attachment that includes a second plurality of magnets disposed in a housing and configured to attach to the surface; alternatively, the second plurality of magnets are disposed within or upon an object to which the electronic display device is to be attached. The second plurality of magnets includes at least one magnet with an outwardly-facing north pole and at least one magnet with an outwardly-facing south pole. The at least one outwardly-facing north pole of the first plurality of magnets is arranged to attractively couple with the at least one outwardly-facing south pole of the second plurality of magnets. The at least one outwardly-facing south pole of the first plurality of magnets is arranged to couple with the at least one outwardly-facing north pole of the second plurality of magnets. The high friction surface covering the first plurality of magnets is configured to be disposed between the first plurality of magnets when coupled to the second plurality of magnets.

In one implementation, a mounting system for mounting an electronic display device to a surface or attaching the electronic display to an object includes a protective case defining an interior surface conforming to an exterior surface of an electronic display device. A first plurality of magnets contacts the protective case and configured to couple to the electronic display device. The first plurality of magnets including at least one magnet with an outwardly-facing north pole and at least one magnet with an outwardly-facing south pole. The at least one magnet with an outwardly-facing north pole of the first plurality of magnets is arranged to couple with at least one magnet with an outwardly-facing south pole of a second plurality of magnets included within a surface-side attachment attached to the

20

surface or included within or upon the object. The at least one magnet with an outwardly-facing south pole of the first plurality of magnets is arranged to couple with at least one magnet with an outwardly-facing north pole of the second plurality of magnets.

The first plurality of magnets and the second plurality of magnets may be made from rare earth metals. The rare earth metals may include alloys of neodymium or samarium-cobalt. The first plurality of magnets and the second plurality of magnets can be grade N48 or higher. The first plurality of magnets and the second plurality of magnets may each comprise two linear rows of magnets.

The first plurality of magnets may be affixed to the interior of the protective cover. The first plurality of magnets may be embedded in the protective cover or the protective case. The first plurality of magnets is affixed to an exterior surface of the protective cover or the protective case. The protective cover may include a high friction surface covering the first plurality of magnets.

The shear force between the surface-side attachment and the device-side attachment may be in a direction substantially parallel to the first outward face and parallel to the second outward face. The shear force may be a direction perpendicular to an attractive force between the first plurality of magnets and the second plurality of magnets.

While various embodiments have been described above, it should be understood that they have been presented by way of example only, and not limitation. For example, wallet 100 and charging device 500 could be any accessory including a combination of a wallet and a battery pack. Also, for example, the surface-side attachment 300 can be attached to any surface such as a wall, computer monitor, inside a backpack, vehicle headrest, refrigerator, etc., not just a vehicle dashboard 400. Where methods described above indicate certain events occurring in certain order, the ordering of certain events may be modified. Additionally, certain of the events may be performed concurrently in a parallel process when possible, as well as performed sequentially as described above.

Where schematics and/or embodiments described above indicate certain components arranged in certain orientations or positions, the arrangement of components may be modified. While the embodiments have been particularly shown and described, it will be understood that various changes in form and details may be made. Any portion of the apparatus and/or methods described herein may be combined in any combination, except mutually exclusive combinations. The embodiments described herein can include various combinations and/or sub-combinations of the functions, components, and/or features of the different embodiments described.

What is claimed is:

1. A wallet for attachment to a mobile device comprising:
 - a body defining a compartment and having a device side surface;
 - a first arrangement of magnetic material having a first region exposing a first polarity magnetic field at the device side surface and a second adjacent region exposing an opposite polarity magnetic field at the device side surface;
 - a second arrangement of magnetic material having a first region exposing a first polarity magnetic field at the device side surface and a second adjacent region exposing an opposite polarity magnetic field at the device side surface; and
 - a ferromagnetic shield between the first and second arrangements and the compartment;

21

wherein the first arrangement and the second arrangement are physically separated on the wallet by a region of nonmagnetic material, the region of nonmagnetic material having a maximum cross dimension greater than a distance between any two immediately adjacent first polarity and opposite polarity regions in the first or second arrangement; and

wherein the first and second arrangements, in use, concurrently magnetically couple the wallet to a mobile device and wherein the first and second arrangements cause the wallet to adopt a specific orientation on the mobile device.

2. The wallet of claim 1 wherein the body defines at least one content removal slot.

3. The wallet of claim 1 wherein an attractive force between the first arrangement, the second arrangement and complementary arrangement of magnets associated with the mobile device are sufficient to support a weight of the mobile device.

4. The wallet of claim 1 wherein a spacing between the first region and the second region in the first arrangement is less than 2 mm.

5. A wallet for attachment to a mobile device comprising:
a body defining a compartment and having a device side surface;

a first arrangement of magnetic material having a first region exposing a first polarity magnetic field at the device side surface and a second adjacent region exposing an opposite polarity magnetic field at the device side surface;

a second arrangement of magnetic material having a first region exposing a first polarity magnetic field at the device side surface and a second adjacent region exposing an opposite polarity magnetic field at the device side surface; and

a metallic plate between the first arrangement and the compartment;

wherein the first arrangement and the second arrangement are physically separated on the wallet by a region of nonmagnetic material, the region of nonmagnetic material having a maximum cross dimension greater than a distance between any two immediately adjacent first polarity and opposite polarity regions in the first or second arrangement; and

22

wherein the first and second arrangements, in use, concurrently magnetically couple the wallet to a mobile device and wherein the first and second arrangements cause the wallet to adopt a specific orientation on the mobile device.

6. The wallet of claim 1 wherein the device side surface is substantially planar and an attachment surface of the mobile device is also substantially planar.

7. The wallet of claim 1 wherein the first and second arrangement permit coupling to the mobile device in exactly one orientation.

8. The wallet of claim 1 wherein the first and second arrangement permit coupling to the mobile device in exactly two orientations.

9. The wallet of claim 1 further comprising:

a finger loop on a surface opposite the device side surface.

10. The wallet of claim 1 wherein the body defines an opening into the compartment and

wherein a material defining the opening tapers towards a long axis of the body at the opening to expose a content of the compartment at the opening.

11. A wallet for attachment to a mobile device comprising:
a body defining a compartment and having a device side surface;

a first arrangement of magnetic material having a first region exposing a first polarity magnetic field at the device side surface and a second adjacent region exposing an opposite polarity magnetic field at the device side surface;

a second arrangement of magnetic material having a first region exposing a first polarity magnetic field at the device side surface and a second adjacent region exposing an opposite polarity magnetic field at the device side surface; and

wherein the first magnetic arrangement has at least one of a different orientation or a different geometric pattern than the second arrangement; and

wherein the first and second arrangements, in use, concurrently magnetically couple the wallet to a mobile device and wherein the first and second arrangements cause the wallet to adopt a specific orientation on the mobile device.

* * * * *