

Exhibit G

US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

U.S. Patent No. 12,015,933 issued on June 18, 2024. Claim 1 recites a method for improving the performance of circuitry that is adapted to be used in a wireless networking device (*e.g.*, a smartphone, laptop, tablet, or access point) having software and/or hardware that enables a “puncturing” feature. Puncturing occurs when a wireless networking device (WND) is using, for example, a 160 MHz channel and punctures out of it one or more sub-channels with interference.

Samsung has infringed at least claims 1-8, 10-11, and 14-30 of the '933 patent in the manner charted herein in manufacturing and/or testing in the United States all Samsung products (*e.g.*, smartphones, TVs, laptops, and tablets) that share the features detailed below with reference to the Galaxy S24 Ultra smartphone. Specifically, the methods Samsung has used to manufacture and/or test all Samsung products that implement Multi-Link Operation (“MLO”) as specified in IEEE 802.11be Draft Standard for Information Technology—Telecommunications and Information Exchange Between Systems Local and Metropolitan Area Networks—Specific Requirements (D7.0 Aug. 2024) (“Wi-Fi 7 Draft Standard”) using two or more transceivers infringe as set forth below. Additionally or alternatively, Samsung has infringed at least claims 1-8, 10-11, and 14-30 of the '933 patent by importing into the United States, offering to sell, selling, and/or using in the United States all Samsung products made by the processes charted herein.

The Samsung Galaxy S24 Ultra has Wi-Fi 7 enabled, using a Qualcomm Snapdragon 8 Gen 3 processor,¹ including Qualcomm's FastConnect 7800 Mobile Connectivity System.² Qualcomm's FastConnect 7800 is Wi-Fi CERTIFIED™ having at least Certification ID WFA127693 that includes connectivity, optimization, security, and spectrum & regulatory features.³ Furthermore, Samsung's Galaxy S24 Ultra is Wi-Fi CERTIFIED™ having at least Certification ID WFA127969 that includes applications & services, connectivity, optimization, security, and spectrum & regulatory features.⁴ Optimization certifications include Wi-Fi Agile Multiband™.⁵

Pursuant to the Wi-Fi 7 Draft Standard, a WND comprises at least a multi-link device (MLD), which may be an access point (AP) MLD or a non-AP MLD. The Galaxy S24 Ultra is configured to operate both as an AP MLD and as a non-AP MLD. As

¹ [Samsung Galaxy S24 Ultra Specs](https://www.gsmarena.com/samsung_galaxy_s24_ultra-12771.php); https://www.gsmarena.com/samsung_galaxy_s24_ultra-12771.php.

² FastConnect 7800 Mobile Connectivity System described here: <https://www.qualcomm.com/products/technology/wi-fi/fastconnect/fastconnect-7800>. See also <https://www.qualcomm.com/snapdragon/news/wi-fi-7-unleashed-with-samsung-galaxy-s24-ultra>.

³ <https://api.cert.wi-fi.org/api/certificate/download/public?variantId=137093>.

⁴ <https://api.cert.wi-fi.org/api/certificate/download/public?variantId=129396>.

⁵ WiFi Alliance, Wi-Fi Agile Multiband Technical Specification, v1.5 (2020) (“Wi-Fi Agile Multiband Specification”).

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

described in more detail in the following claim chart, the Galaxy S24 Ultra is enabled to perform the claimed puncturing operations when operating as an AP MLD and when operating as a non-AP MLD.

The accused instrumentalities include all Samsung electronics devices (including smartphones, TVs, laptops, tablets, and wearable devices) that implement MLO as specified in IEEE 802.11be Draft Standard for Information Technology—Telecommunications and Information Exchange Between Systems Local and Metropolitan Area Networks—Specific Requirements (D7.0, Aug. 2024) using two or more transceivers. The accused instrumentalities include Samsung products released with MLO capabilities as well as Samsung products made MLO-capable through, for example, Samsung firmware updates. Claim 2 of the '933 patent is only asserted with respect to accused Samsung smartphones.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
1. A method of improving the performance of circuitry, comprising the steps of:	Samsung has practiced the claimed method of improving performance of circuitry in the manner charted herein by manufacturing and/or testing the Samsung Galaxy S24 Ultra mobile phone (“Galaxy S24 Ultra”).⁶ The Galaxy S24 Ultra is a wireless networking device (WND), which comprises circuitry. A WND comprises at least a multi-link device (MLD) as specified by IEEE 802.11be/D5.0 Draft Standard for Information Technology—Telecommunications and Information Exchange Between Systems Local and Metropolitan Area Networks—Specific Requirements (Aug. 2024) (“Wi-Fi 7 Draft Standard”).⁷ An MLD may be an access point (AP) MLD or a non-AP MLD. multi-link device: [MLD] A logical entity that is capable of supporting more than one affiliated station (STA) and can operate using one or more affiliated STAs, and that presents one medium access control (MAC) data service and a single MAC service access point (MAC SAP) to the logical link control (LLC) sublayer. access point (AP) multi-link device (MLD): [AP MLD] An MLD, where each station (STA) affiliated with the MLD is an AP. non-access point (non-AP) multi-link device (MLD): [non-AP MLD] An MLD, where each station (STA) affiliated with the MLD is a non-access point (non-AP) station (non-AP STA). Wi-Fi 7 Draft Standard at 61, 62, 63.

⁶ Additionally or alternatively, Samsung has imported into the United States, offered to sell, sold, or used within the United States the Galaxy S24 Ultra mobile phone, which is made by the claimed method. *See* 35 U.S.C. § 271(g).

⁷ *See also* all previous versions of the Wi-Fi 7 Draft Standard, including each of 802.11be/D1.0 (2021) through 802.11be/D6.0 (2024).

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	In this context, for example, a wireless terminal device or a network access device may comprise one or more MLDs. A wireless networking device may be, for example, a wireless station in a Wi-Fi 7 system, such as a stationary wireless AP or a mobile wireless AP, such as the Galaxy S24 Ultra, comprising an AP MLD. A WND may also be, for example, a mobile or fixed device comprising a non-AP MLD. Such devices may be, for example, mobile telephones or smartphones, such as the Galaxy S24 Ultra. In this regard, the Galaxy S24 Ultra is operable both as an AP MLD and as a non-AP MLD. For example, the Galaxy S24 Ultra is capable of operating as a mobile hotspot, thereby sharing its data connection with other devices.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung’s Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	Mobile hotspot Mobile hotspot uses your data plan to create a Wi-Fi network that can be used by multiple devices. 1. From Settings, tap  Connections > Mobile hotspot and tethering > Mobile hotspot. 2. Tap  to turn on Mobile hotspot. 3. On the devices you want to connect, activate Wi-Fi, and select your device's Mobile hotspot. Enter the Mobile hotspot password to connect.  TIP Tap  QR code to connect another device to your Mobile hotspot by scanning a QR code instead of entering a password. Configure mobile hotspot settings You can customize your mobile hotspot's security and connection settings. 1. From Settings, tap  Connections > Mobile hotspot and tethering > Mobile hotspot. 2. Tap  to turn on Mobile hotspot, and then tap the following settings to change them: <i>Samsung Galaxy S24, S24+, S24 Ultra User Guide, Ver. U 14.1 (English(North America)) (Sept. 6, 2024) at 120.</i> When operating as a mobile hotspot, the Galaxy S24 Ultra behaves as an AP for other devices. Otherwise, the Galaxy S24 Ultra operates as a non-AP MLD in communications with other devices. The Galaxy S24 Ultra comprises circuitry, including circuitry for wireless communication.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	The Samsung Galaxy S24 Ultra has Wi-Fi 7 enabled, using a Qualcomm Snapdragon 8 Gen 3 processor, including Qualcomm's FastConnect 7800 Mobile Connectivity System, which forms at least a portion of the claimed circuitry. Wi-Fi Connectivity 802.11a/b/g/n/ac/ax/be 2.4GHz+5GHz+6GHz, EHT320, MIMO, 4096-QAM Samsung Galaxy S24 Ultra Specs. Samsung Galaxy S24 Ultra Featuring Snapdragon 8 Gen 3 for Galaxy. Introducing Samsung Galaxy S24 Ultra, now with many next-gen AI features and capabilities enabled by Snapdragon 8 Gen 3 for Galaxy. Powered with Galaxy AI, Galaxy S24 Ultra adapts to your passions and behaviors to make a new level of achievement possible. And, with Qualcomm FastConnect 7800 Mobile Connectivity System, you'll get the best possible connection and premium WiFi 7 connectivity. https://www.qualcomm.com/snapdragon/device-finder/samsung-galaxy-s24-ultra.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
[1.a] providing a processing interface that is adapted to be connected to an application interface of a wireless networking device, the application interface being associated with a first application, the first application providing, after the circuitry has been connected to the application interface and when the wireless networking device is being used, a first data stream and having a first wireless bandwidth requirement;	In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has provided a processing interface that is adapted to be connected to an application interface of a wireless networking device, the application interface being associated with a first application, the first application providing, after the circuitry has been connected to the application interface and when the wireless networking device is being used, a first data stream and having a first wireless bandwidth requirement. As described with respect to the preamble of claim 1, the Galaxy S24 Ultra is a WND comprising circuitry, including but not limited to, the Qualcomm Snapdragon 8 Gen 3 processor. Wi-Fi Connectivity 802.11a/b/g/n/ac/ax/be 2.4GHz+5GHz+6GHz, EHT320, MIMO, 4096-QAM Samsung Galaxy S24 Ultra Specs. Samsung Galaxy S24 Ultra Featuring Snapdragon 8 Gen 3 for Galaxy. Introducing Samsung Galaxy S24 Ultra, now with many next-gen AI features and capabilities enabled by Snapdragon 8 Gen 3 for Galaxy. Powered with Galaxy AI, Galaxy S24 Ultra adapts to your passions and behaviors to make a new level of achievement possible. And, with Qualcomm FastConnect 7800 Mobile Connectivity System, you'll get the best possible connection and premium WiFi 7 connectivity.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	https://www.qualcomm.com/snapdragon/device-finder/samsung-galaxy-s24-ultra. The Galaxy S24 Ultra includes an application interface that allows the Wi-Fi module of the Galaxy S24 Ultra to interact with one or more applications having bandwidth requirements. The application interface comprises hardware and/or software engaging with software applications, such as internet browsers or video playback apps, having data streams when the wireless networking device is used. Each application data stream has a wireless bandwidth requirement. Additionally, the Galaxy S24 Ultra has a processing interface adapted to be connected to the application interface. The processing interface is provided by the Qualcomm Snapdragon 8 Gen 3 processor contained within the Galaxy S24 Ultra. The Wi-Fi 7 Draft Standard includes the reference model for an MLD shown below.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung’s Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	Figure 4-33b—Reference model for an MLD for two links Figure 4-33b, Wi-Fi 7 Draft Standard at 78. As shown in Figure 4-33b above, an MLD, such as in the Galaxy S24 Ultra, has a Station Management Entity (SME). The SME is in communication with a MAC Sublayer Management Entity (MLME), through an MLME SAP, and a PHY Management Entity (PLME), through a PLME SAP. Further, the MLME is in communication with the Upper MAC Sublayer (UMAC) and with each Lower MAC entity (LMAC). The SME is responsible for coordinating the MLD and each of the affiliated STAs used to establish links between devices. It operates at least by communicating with the

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	MLME SAP and the PLME SAP to manage the MAC and PHY interfaces affiliated with each link. The communicating may include, for example, messaging, signaling, or shared memory access. An MLD supports multiple MAC functions, with synchronization across the MAC functions as needed via the MLD synchronization service (see 35.3.25 (MLD synchronization service)) and otherwise coordinated by the SME. Each affiliated STA is enumerated with a Link ID (for example, as Link 1 and Link 2 in Figure 4-33b (Reference model for an MLD for two links)) and MLME primitives are invoked through an MLME SAP. The SME maintains the authentication and association states. The Authenticator and the MAC-SAP of the AP MLD are identified by the same AP MLD MAC address. The Supplicant and the MAC-SAP of the non-AP MLD are identified by the same non-AP MLD MAC address. The SME is responsible for coordinating the MLD and each of the affiliated STAs through the MLME, and to maintain an RSNA key management entity and IEEE 802.1X Authenticator or Supplicant, for MLO. Wi-Fi 7 Draft Standard at 78. 36.1.3.2 PHY management entity (PLME) The PLME performs management of the local PHY functions in conjunction with the MLME. Wi-Fi 7 Draft Standard at 707. Accordingly, the processing interface comprises at least a portion of the SME and MLME. The processing interface may also include at least a portion of the MLME SAP and PLME SAP by which the SME communicates with other management layers. Additionally, the processing interface may include at least some functionality of the UMAC. As shown above in Figure 4-33b, the MLD has a MAC layer that is divided into an LMAC corresponding to each STA, and a single UMAC managing common operations for all STAs.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	The LMACs perform certain link-specific MAC functions while the UMAC is responsible for MAC functions common to the multiple links. 5.1.5.1a MLD MAC sublayer functions The MLD upper MAC sublayer functions include: — Authentication, association, and reassociation (between an AP MLD and a non-AP MLD) — Security association (e.g., PMKSA, PTKSA) and distribution of GTK/IGTK/BIGTK — SN/PN assignment for frames to be encrypted by PTK for individually addressed frames — SN assignment for group addressed MSDUs — Power save buffering of individually addressed frames (only on AP MLD) — Encryption/decryption using PTK for individually addressed frames — Selection of the MLD lower MAC entity for transmission (TID-to-link mapping (see 35.3.7.2 (TID-To-Link Mapping (TTLM)))) — Merging reception of MPDUs from two or more links — Reordering of packets to ensure in-order delivery per each Block Ack session — Block Ack scoreboarding for individually addressed frames (in collaboration with the MLD lower MAC entities). Optionally, the MLD upper MAC sublayer delivers successful status records of MPDUs and/or scoreboard context control information on Block Ack scoreboarding at one of the setup links to other setup links (see 35.3.8 (Block ack procedures in MLO)) — MLD level management information exchange/indication via the MLD lower MAC entity — Each affiliated STA selects its own EDCA parameters (for a non-AP STA it comes from the peer AP on that link). Wi-Fi 7 Draft Standard at 84.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	The MLD lower MAC entity functions include: — Link specific control information exchange/indication (e.g., RTS/CTS, acknowledgements, NDP, etc.) — Power save state and mode — MAC address filtering for frame reception — Block Ack scoreboarding for individually addressed frames (in collaboration with the MLD upper MAC sublayer). Optionally, the MLD lower MAC entity receives the successful status records of the MPDUs and/or scoreboard context control information of the Block Ack agreement from the MLD upper MAC sublayer) (see 35.3.8 (Block ack procedures in MLO)) Wi-Fi 7 Draft Standard at 84-85. Operations performed by the UMAC include, for example, TID-to-Link Mapping and authentication, association, and reassociation between an AP MLD and a non-AP MLD. The processing interface may therefore include at least some functionality of the UMAC. The processing interface is located below other layers of the MLD, such as the data link layer. The processing interface is adapted to be connected to the application interface. The processing interface is responsible for AP MLD and non-AP MLD multi-link operation (MLO) processes that allow the Galaxy S24 Ultra to discover, authenticate, associate, and set up links with other MLDs for meeting bandwidth requirements. Bandwidth information is exchanged between the application interface and the processing interface. For example, in order to perform TID-to-Link Mapping and other MLO operations for exchanging frames across links, the processing interface is connected to the application interface. MLO is defined for an EHT STA in 35.3 (Multi-link operation (MLO)). MLO allows an AP MLD and a non-AP MLD to set up multiple links between them. A reference model for MLO is described in 4.9.6 (Reference model for multi-link operation (MLO)). Wi-Fi 7 Draft Standard at 523.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	4.9.6 Reference model for multi-link operation (MLO) MLO defines a set of procedures allowing communication over one or more links between MLDs. An MLD manages such communication over one or more links. Communication over links using different channels on different frequency bands or the same frequency band can occur simultaneously or not depending on the capabilities of both the AP MLD and the non-AP MLD (see 35.3.16.3 (Simultaneous transmit and receive (STR) operation) and 35.3.16.4 (Nonsimultaneous transmit and receive (NSTR) operation)). The MLO procedures (see 35.3 (Multi-link operation (MLO))) allow a pair of MLDs to discover, synchronize, (de)authenticate, (re)associate, disassociate, and manage links and other resources with each other on any common bands or channels that are supported by both MLDs. Wi-Fi 7 Draft Standard at 76. For example, the processing interface performs TID-to-Link mapping procedures to determine how data frames will be assigned for transmission. 35.3.7.2 TID-To-Link Mapping (TTLM) 35.3.7.2.1 General The TTLM mechanism allows an AP MLD and a non-AP MLD that performed or are performing ML setup to determine how Data frames belonging to TIDs 0–7 and Management frames will be assigned for transmission, on the setup links between the two MLDs in DL and UL. Wi-Fi 7 Draft Standard at 565. The SME is responsible for coordinating the MLD and each of the affiliated STAs through the MLME, and to maintain an RSNA key management entity and IEEE 802.1X Authenticator or Supplicant, for MLO. Wi-Fi 7 Draft Standard at 78.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	As shown above in Figure 4-33b, the processing interface engages with other layers within the Galaxy S24 Ultra through a MAC SAP. Information regarding data streams from the application interface may be communicated to the processing interface through the MAC SAP. Thus, the processing interface of the Galaxy S24 Ultra, when operating as an AP MLD or a non-AP MLD, comprises at least portions of the MAC SAP, UMAC, MLME, and SME in providing data streams and meeting bandwidth requirements. Where the application that needs to transmit and/or receive data interacts with the UMAC through the MAC SAP, the UMAC passes data to the MLME, which is responsible for managing the MAC layer functions. The MLME communicates with the SME to request channel allocation, link selection, and other resources necessary for data transmission given the bandwidth requirements. The SME coordinates with the UMAC to determine the optimal links and channels for data transmission. Once the resources are allocated, the SME instructs the MLME to transmit/receive the data over the selected links.
[1.b] connecting first and second actual MAC interfaces to the processing interface;	In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has connected first and second actual MAC interfaces to the processing interface. As shown below, the Wi-Fi 7 Draft Standard explains that an AP MLD or a non-AP MLD has multiple STAs that can each establish a link. Each link is associated with a frequency band (<i>e.g.</i>, 2.4 GHz, 5 GHz, or 6 GHz). The reference diagram below illustrates two STAs and associated links for simplicity; a Wi-Fi 7 MLD provides three STAs and thus may form three links—one for each of the 2.4 GHz, 5 GHz, and 6 GHz frequency bands.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	Figure 4-33b—Reference model for an MLD for two links Figure 4-33b, Wi-Fi 7 Draft Standard at 78. Each STA of the AP MLD or non-AP MLD has a PHY unique to that STA and associated with an affiliated link. Additionally, the MLD has a MAC layer that is divided into an LMAC corresponding to each STA and affiliated link, and a single UMAC managing common operations for all STAs and affiliated links. The LMACs perform certain link-specific MAC functions while the UMAC is responsible for MAC functions common to the multiple links.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	5.1.5.1a MLD MAC sublayer functions The MLD upper MAC sublayer functions include: — Authentication, association, and reassociation (between an AP MLD and a non-AP MLD) — Security association (e.g., PMKSA, PTKSA) and distribution of GTK/IGTK/BIGTK — SN/PN assignment for frames to be encrypted by PTK for individually addressed frames — SN assignment for group addressed MSDUs — Power save buffering of individually addressed frames (only on AP MLD) — Encryption/decryption using PTK for individually addressed frames — Selection of the MLD lower MAC entity for transmission (TID-to-link mapping (see 35.3.7.2 (TID-To-Link Mapping (TTLM)))) — Merging reception of MPDUs from two or more links — Reordering of packets to ensure in-order delivery per each Block Ack session — Block Ack scoreboarding for individually addressed frames (in collaboration with the MLD lower MAC entities). Optionally, the MLD upper MAC sublayer delivers successful status records of MPDUs and/or scoreboard context control information on Block Ack scoreboarding at one of the setup links to other setup links (see 35.3.8 (Block ack procedures in MLO)) — MLD level management information exchange/indication via the MLD lower MAC entity — Each affiliated STA selects its own EDCA parameters (for a non-AP STA it comes from the peer AP on that link). Wi-Fi 7 Draft Standard at 84.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	The MLD lower MAC entity functions include: — Link specific control information exchange/indication (e.g., RTS/CTS, acknowledgements, NDP, etc.) — Power save state and mode — MAC address filtering for frame reception — Block Ack scoreboarding for individually addressed frames (in collaboration with the MLD upper MAC sublayer). Optionally, the MLD lower MAC entity receives the successful status records of the MPDUs and/or scoreboard context control information of the Block Ack agreement from the MLD upper MAC sublayer) (see 35.3.8 (Block ack procedures in MLO)) Wi-Fi 7 Draft Standard at 84-85. The Galaxy S24 Ultra, when operating as an AP MLD or a non-AP MLD, has three wireless transceivers (or STAs) that communicate in the 2.4 GHz, 5 GHz, and 6 GHz bands. Accordingly, and as discussed with respect to element 1.d, the Galaxy S24 has at least first and second wireless transceivers. Wi-Fi Connectivity 802.11a/b/g/n/ac/ax/be 2.4GHz+5GHz+6GHz, EHT320, MIMO, 4096-QAM Samsung Galaxy S24 Ultra Specs. In accordance with the Wi-Fi 7 Draft Standard, the Galaxy S24 Ultra has first and second actual MAC interfaces corresponding to its first and second STAs. Each MAC interface comprises, for each of the first and second transceivers, a corresponding LMAC. The first and second actual MAC interfaces are connected to the processing interface. As described above, the processing interface comprises at least a portion of the SME,

US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	MLME, MAC SAP, MLME SAP, and PLME SAP in combination with at least some functionality of the UMAC. As shown in Figure 4-33b of the Wi-Fi 7 Draft Standard, the LMACs and the UMAC are in communication with the MLME. The MLME is further in communication with the SME via the MLME SAP. Figure 4-33b—Reference model for an MLD for two links
[1.c] connecting first and second actual PHY interfaces respectively	In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has connected first and second actual PHY interfaces respectively to the first and second actual MAC interfaces.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
to the first and second actual MAC interfaces;	As discussed with respect to element 1.b of claim 1, the Galaxy S24 Ultra, when operating as an AP MLD or a non-AP MLD, has three transceivers that communicate in the 2.4 GHz, 5 GHz, and 6 GHz frequency bands. In addition to an associated MAC interface, each of these transceivers has an associated PHY interface. As shown in Figure 4-33b below, the PHY for each STA is connected to the corresponding actual MAC interface for that STA via a PHY SAP. The PHYs corresponding to the first and second wireless transceivers of the Galaxy S24 Ultra comprise the first and second actual PHY interfaces. Figure 4-33b—Reference model for an MLD for two links Figure 4-33b, Wi-Fi 7 Draft Standard at 78 (emphasis added).

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	Each PHY communicates with its corresponding MAC through the PHY SAP using certain vectors. 36.2 EHT PHY service interface 36.2.1 Introduction The EHT PHY provides an interface to the EHT MAC through an extension of the generic PHY service interface defined in 8.3.4 (Basic service and options). The interface includes TXVECTOR, RXVECTOR, PHYCONFIG_VECTOR, and TRIGVECTOR. The EHT MAC uses the TXVECTOR to supply the EHT PHY with per-PPDU transmit parameters. The EHT PHY uses the RXVECTOR to inform the EHT MAC of the received PPDU parameters. The EHT MAC uses the PHYCONFIG_VECTOR to configure the EHT PHY for operation that is independent of PPDU transmission or reception. The EHT MAC uses the TRIGVECTOR to configure the EHT PHY to receive EHT TB PPDU's over each assigned RU or MRU. Wi-Fi 7 Draft Standard at 708.
[1.d] respectively associating first and second wireless transceivers with the first and second actual PHY interfaces, wherein each of the first and second wireless transceivers is suitable for use in a wireless local area network, and the first and second wireless transceivers, respectively, (i) have a first and second bandwidth availability up to first and second actual bandwidths, and (ii) are	In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has respectively associated first and second wireless transceivers with the first and second actual PHY interfaces, wherein each of the first and second wireless transceivers is suitable for use in a wireless local area network, and the first and second wireless transceivers, respectively, (i) have a first and second bandwidth availability up to first and second actual bandwidths, and (ii) are adapted to emit radio signals in first and second different bands of frequencies. The Galaxy S24 Ultra, when operating as an AP MLD or a non-AP MLD, has three wireless transceivers having three different frequency bands, including at least first and second wireless transceivers. Each transceiver is associated with an actual MAC interface and an actual PHY interface. Each of the three transceivers is suitable for use in a wireless local area network, such as a Wi-Fi network, shown below.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
adapted to emit radio signals in first and second different bands of frequencies;	Wi-Fi Connectivity 802.11a/b/g/n/ac/ax/be 2.4GHz+5GHz+6GHz, EHT320, MIMO, 4096-QAM Samsung Galaxy S24 Ultra Specs. The Wi-Fi 7 Draft Standard references that the transceivers are used in wireless local area networks that emit radio waves in frequency bands “ensuring backward compatibility and coexistence with legacy IEEE Std 802.11 compliant devices operating in the 2.4 GHz, 5 GHz, and 6 GHz bands.” Wi-Fi 7 Draft Standard at 2. Additionally, the first and second transceivers of the Galaxy S24 Ultra have first and second bandwidth availability up to first and second actual bandwidths. At any given time, each of the three transceivers associated with the 2.4, 5, and 6 GHz bands has a bandwidth availability representing a portion of an actual and/or total bandwidth for that band. As described in further detail below, the UMAC, in combination with the SME (both of the processing interface), uses the bandwidth availability of each transceiver to make resource allocation decisions. The first and second transceivers of the Galaxy S24 Ultra are adapted to emit radio signals in first and second different bands of frequencies. The first and second transceivers can be any two of the 2.4 GHz, 5 GHz, and 6 GHz transceivers of the Galaxy S24 Ultra.
[1.e] forming in the processing interface (i) at least one virtual MAC interface and	In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has formed in the processing interface at least one virtual MAC interface. As described with respect to elements 1.a and 1.b, the processing interface of the Galaxy S24 Ultra, when operating as an AP MLD or a non-AP MLD, comprises at least a

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	portion of the SME, MLME, MAC SAP, MLME SAP, and PLME SAP in combination with certain functionality of the UMAC. The processing interface performs certain functions that correspond to and comprise a virtual MAC interface. When operating as an AP MLD or a non-AP MLD, the processing interface of the Galaxy S24 Ultra performs certain functions that correspond to and comprise a virtual MAC interface. For example, the processing interface, and particularly the SME, makes strategic decisions about resource allocation and/or link recommendations based on traffic demands and network conditions. Network condition information necessarily includes bandwidth availability information resulting from channel assessments directly or indirectly by way of, for example, at least trigger frames, management frames, and feedback messages. The Galaxy S24 Ultra complies with the Wi-Fi Agile Multiband Specification, which “is built on the fundamental premise that the APs and STAs each have information which can aid in making the most effective selection of the spectrum band in which the STA and AP should be communicating. By exchanging this information with each other, APs and STAs enable each other to make decisions that collectively drive the network towards more efficient use of the available spectrum.” Wi-Fi Agile Multiband Specification at § 3.1. 3 Wi-Fi Agile Multiband protocol 3.1 Introduction The goal of the Wi-Fi Agile Multiband certification program is to certify features that facilitate efficient use of multiple frequency bands/channels available to APs and the STAs. The program is built on the fundamental premise that the APs and STAs each have information which can aid in making the most effective selection of the spectrum band in which the STA and AP should be communicating. By exchanging this information with each other, APs and STAs enable each other to make decisions that collectively drive the network towards more efficient use of the available spectrum. The following sections describe the information exchanged and the mechanisms by which APs and STAs exchange the desired information. Where applicable, references to existing IEEE standards are provided. In instances where there is a need to go beyond what the IEEE standards specify, the corresponding functionality, protocols and constraints are defined.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	Wi-Fi Agile Multiband Specification at § 3.1. As a particular example, in accordance with the Wi-Fi 7 Draft Standard, the SME's understanding of traffic priorities, queue lengths, and real-time network status enables intelligent TID-to-link mapping in the Galaxy S24 Ultra. This mapping determines which traffic (identified by TID) should be directed to which links (<i>i.e.</i>, associated bandwidth resources). The SME, in combination with the UMAC, allocates appropriate RUs/MRUs (resource units / multiple resource units) based on the data requirements of the specific traffic type mapped to a link. The SME considers factors like the amount of data to be transmitted for a particular TID and the channel bandwidth available on the chosen link. It can choose to allocate a single RU for smaller data packets or low-priority traffic, or allocate multiple RUs combined into an MRU for larger data transfers or high-priority traffic requiring more bandwidth. Accordingly, the processing interface comprises at least one virtual MAC interface. The virtual MAC interface comprises the portions of the SME and MLME, in combination with functionality of the UMAC, that perform RU/MRU allocation and TID-to-Link mapping. The virtual MAC interface may additionally include a portion of the MLME SAP by which the SME communicates with the MLME.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	An MLD supports multiple MAC functions, with synchronization across the MAC functions as needed via the MLD synchronization service (see 35.3.25 (MLD synchronization service)) and otherwise coordinated by the SME. Each affiliated STA is enumerated with a Link ID (for example, as Link 1 and Link 2 in Figure 4-33b (Reference model for an MLD for two links)) and MLME primitives are invoked through an MLME SAP. The SME maintains the authentication and association states. The Authenticator and the MAC-SAP of the AP MLD are identified by the same AP MLD MAC address. The Supplicant and the MAC-SAP of the non-AP MLD are identified by the same non-AP MLD MAC address. The SME is responsible for coordinating the MLD and each of the affiliated STAs through the MLME, and to maintain an RSNA key management entity and IEEE 802.1X Authenticator or Supplicant, for MLO. Wi-Fi 7 Draft Standard at 78.
[1.f] (ii) first and second virtual PHY interfaces that, after the circuitry has been connected to the application interface and during operation of the wireless networking device, feed information regarding the bandwidth availabilities of the first and second wireless transceivers back to the at least one virtual MAC interface;	In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has formed in the processing interface first and second virtual PHY interfaces that, after the circuitry has been connected to the application interface and during operation of the wireless networking device, feed information regarding the bandwidth availabilities of the first and second wireless transceivers back to the at least one virtual MAC interface. As described with respect to element 1.e, when operating as an AP MLD or a non-AP MLD, at least a first portion of the processing interface of the Galaxy S24 Ultra comprises a virtual MAC interface. The virtual MAC interface comprises portions of the SME and MLME, in combination with functionality of the UMAC, and makes strategic decisions about resource allocation and/or link recommendations. For example, the virtual MAC interface comprises the portions of the SME and MLME, in combination with functionality of the UMAC, that perform RU/MRU allocation and TID-to-Link mapping. The virtual MAC interface may additionally include a portion of the MLME SAP by which the SME communicates with the MLME.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	Additionally, in order for the processing interface to make strategic decisions about resource allocation and/or link recommendations, the SME must receive information regarding bandwidth availabilities of the transceivers. For example, to allocate RUs/MRUs to achieve the increased bandwidth utilization and efficiency objectives of the IEEE 802.11be standard and for multi-users, the SME must receive information regarding the bandwidth availabilities of the transceivers from which the RUs/MRUs may be assigned based at least on channel utilization and/or congestion. <i>See, e.g.</i>, Wi-Fi 7 Draft Standard at 629-637. Information regarding bandwidth availabilities of the transceivers may be or include information about the actual PHY itself. Information regarding bandwidth availabilities of the transceivers may additionally or alternatively include information received at the actual PHY from another device, such as an AP MLD device. In each case, information regarding bandwidth availabilities is communicated to the virtual MAC interface. As described in more detail below, the virtual PHY interfaces of the Galaxy S24 Ultra, when operating as an AP MLD or a non-AP MLD, comprise those portions of the SME that report information regarding bandwidth availabilities to the virtual MAC. Each virtual PHY interface may additionally include a portion of the MLME, where logic or pathways within the MLME are used in reporting information about bandwidth availabilities to the virtual MAC. Additionally, the path of communication by which information regarding bandwidth availabilities is fed to the virtual MAC may be or include portions of the MLME SAP and/or PLME SAP. Each virtual PHY interface may therefore additionally include a portion of the MLME SAP and/or the PLME SAP through which bandwidth information is directed to the virtual MAC. The Galaxy S24 Ultra has three STAs for its three transceivers, each with a corresponding actual PHY interface. In connection with each actual PHY interface, the Galaxy S24 Ultra has a virtual PHY interface responsible for feeding information regarding bandwidth availabilities about the corresponding actual PHY interface to the virtual MAC.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	The Galaxy S24 Ultra therefore has first and second virtual PHY interfaces corresponding to its first and second transceivers. The Wi-Fi Agile Multiband Specification provides examples of information regarding bandwidth availabilities that may be communicated by the virtual PHY interfaces. In accordance with the Wi-Fi Agile Multiband Specification, when operating as a non-AP MLD, for example, the Galaxy S24 Ultra provides “to a Wi-Fi Agile Multiband AP a list of channels and bands on which it prefers not to be associated,” including in each list entry: channel and band, preference value, and reason code. Wi-Fi Agile Multiband Specification at § 2.3.2. A Wi-Fi Agile Multiband STA shall support the following features: • Indicates whether or not it has a cellular data connection available (refer to section 4.2.3) • Provides to a Wi-Fi Agile Multiband AP a list of channels and bands on which it prefers not to be associated, including in each list entry: ▪ Channel and band ▪ Preference value ▪ Reason code Wi-Fi Agile Multiband Specification at § 2.3.2. Reason codes may include, for example, co-located interference, where an “unacceptable level of interference is being experienced by the Wi-Fi Agile Multiband STA in this channel,” and in-device interferer, where the “Agile Multiband STA has another active connection in this channel, or near enough to this channel to cause operating interference.” Wi-Fi Agile Multiband Specification at Table 10. “This information is communicated to the Wi-Fi Agile Multiband AP when the Wi-Fi Agile Multiband STA associates or reassociates, and when the information changes while the Wi-Fi Agile Multiband STA is associated.” Wi-Fi Agile Multiband Specification at §3.2. For a Wi-Fi Agile Multiband AP that supports MLO as defined in the Wi-Fi 7 Draft Standard, “this list of non-preferred channels” is indicated across all affiliated non-AP STAs. <i>Id.</i>

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	In addition to the non-AP MLD communicating such channel and band information to an AP MLD, such channel and band information, including interference information, may be communicated from the Galaxy S24 Ultra's virtual PHY interfaces to the virtual MAC. Information regarding bandwidth availabilities may be communicated by the virtual PHY interfaces to the virtual MAC through multiple operations. For example: <u>Multi-Link Beacon or Probe Response</u> In accordance with the Wi-Fi Agile Multiband Specification, the Galaxy S24 Ultra "include[s] the MBO [Multiband Operation] Capability Indication attribute in Beacon and Probe Response frames on all links." Wi-Fi Agile Multiband Specification at §3.8. 3.8 MBO Capability Indication attribute Wi-Fi Agile Multiband APs shall include the MBO Capability Indication attribute in Beacon frames, Probe Response frames and (Re)Association Response frames. This attribute indicates that the AP is a Wi-Fi Agile Multiband AP, and whether it is cellular data aware or not. A Wi-Fi Agile Multiband AP which supports MLO as defined in [2], shall include the MBO Capability Indication attribute in Beacon and Probe Response frames on all links. Wi-Fi Agile Multiband Specification at §3.8. Support for MBO attribute AP Beacon, Probe Response, and (Re)Association Response management frames is mandatory, as is support for non-preferred channel reports for the STA (Re)Association Request. Wi-Fi Agile Multiband Specification at Table 5. A non-AP MLD, such as the Galaxy S24 Ultra, obtains information regarding bandwidths from AP MLDs. Such information may be obtained, for example, during MLO discovery. For example, during MLO discovery and ML setup, a non-AP MLD discovers an AP MLD using either (1) passive or active scanning, or (2) transmission of a multi-link probe

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	request. The non-AP MLD receives from the AP MLD either a beacon frame or a multi-link probe response frame. 35.3.4.6 Frame exchange sequences during MLO discovery and ML setup A non-AP MLD is expected to discover an AP MLD and affiliated AP(s) of interest before initiating an ML setup with the AP MLD. The non-AP MLD can use one or a combination of the following methods for discovering the AP MLD and affiliated AP(s) of interest: — Through each of its affiliated STAs, perform passive scanning by following the procedure defined in 11.1.4.2 (Passive scanning) or active scanning by following the procedure defined in 11.1.4.3 (Active scanning and probing procedures). — Through one of its affiliated STAs, transmit a multi-link probe request on any link that the AP MLD is operating on, with the frame addressed to the affiliated AP operating on that link, to obtain information about the AP MLD and its affiliated AP(s) by following the procedure defined in 35.3.4.2 (Use of multi-link probe request and response). Wi-Fi 7 Draft Standard at 544.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra




Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	Fig. 35-5, Wi-Fi 7 Draft Standard at 545. The beacon frame and the multi-link probe response frame received by the non-AP MLD include information regarding bandwidth availabilities. In particular, both the beacon frame and the multi-link probe response frame include a multi-link traffic indication element, an EHT capabilities element, an EHT operation element, a TID-to-Link mapping element, and a channel usage element. Wi-Fi 7 Draft Standard at 183-84 (beacon frame), 190-91 (probe response frame). These elements include information regarding bandwidth availability, such as a per-link traffic indication list contained in the multi-link traffic indication element and PHY capabilities information contained in the EHT capabilities element. Wi-Fi 7 Draft Standard at 295-97 (Multi-Link Traffic Indication), 269-93 (EHT Capabilities).

US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

The beacon or multi-link probe response frame may additionally or alternatively include a Basic Multi-Link element, which includes a Per-STA Profile sub-element. Wi-Fi 7 Draft Standard at 248-61.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung’s Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra												
	The format of the Per-STA Profile subelement is defined in Figure 9-1074u (Per-STA Profile subelement format of the Basic Multi-Link element). <table><tr><td></td><td>Subelement ID</td><td>Length</td><td>STA Control</td><td>STA Info</td><td>STA Profile</td></tr><tr><td>Octets:</td><td>1</td><td>1</td><td>2</td><td>variable</td><td>variable</td></tr></table> Figure 9-1074u—Per-STA Profile subelement format of the Basic Multi-Link element Wi-Fi 7 Draft Standard at 259. Additionally, or alternatively, devices may transmit beacon frames on multiple channels simultaneously. By analyzing overlapping beacon frames from neighboring APs, the MLD can infer channel occupancy and recommend and/or allocate potential resources for its own transmissions. <u>Punctured Subchannels</u> Additionally, the Galaxy S24 Ultra, with Wi-Fi 7 enabled, is configured for preamble puncturing. The puncturing pattern, required of the standard, provides information regarding the first and second bandwidth availabilities to the virtual MAC interface. Preamble puncturing allows WNDs, such as the Galaxy S24 Ultra, to recognize and exclude unavailable subchannels from a transmission. For example, the Wi-Fi 7 Draft Standard describes the U-SIG field that carries the information necessary to interpret EHT PPDU's, and that shows a puncturing pattern wherein RUs and MRUs are punctured. The puncturing pattern indicates what sub-portions of RUs or MRUs are not to be used for transmission or reception purposes. Unavailable subchannels may be indicated, for example, in a Disabled Subchannel Bitmap.		Subelement ID	Length	STA Control	STA Info	STA Profile	Octets:	1	1	2	variable	variable
	Subelement ID	Length	STA Control	STA Info	STA Profile								
Octets:	1	1	2	variable	variable								

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	36.3.12.11 EHT preamble of preamble punctured EHT MU PPDU 36.3.12.11.1 General Preamble puncturing refers to the transmission of a PPDU in which no signal is present in at least one of the 20 MHz subchannels within the PPDU bandwidth. Preamble puncturing might be the result of the unavailability of 20 MHz subchannel(s) within the PPDU bandwidth, such as a busy channel indicated by the CCA or the setting of the Disabled Subchannel Bitmap subfield in the EHT Operations element (see 9.4.2.321 (EHT Operation element)). Wi-Fi 7 Draft Standard at 867. Otherwise, an EHT STA may puncture other subchannels in addition to those indicated in the Disabled Subchannel Bitmap subfield in the EHT Operation element in an EHT MU PPDU or a non-HT duplicate PPDU. If an EHT AP punctures other subchannels in an EHT MU PPDU or a non-HT duplicate PPDU in addition to those indicated in the Disabled Subchannel Bitmap subfield and solicits a response to the PPDU, the EHT AP shall use a triggering frame to solicit the response in a TB PPDU and assign an RU or MRU within the nonpunctured subchannel set to a responding EHT STA. Wi-Fi 7 Draft Standard at 686. Regardless of the inclusion of the Disabled Subchannel Bitmap subfield in the EHT Operation element, an EHT STA may use EHT MU PPDU preamble puncturing modes as defined in 36.3.12.11 (EHT preamble of preamble punctured EHT MU PPDU) or EHT TB PPDU in which not all the 20 MHz subchannels are assigned. Wi-Fi 7 Draft Standard at 686. Unavailable subchannels (<i>i.e.</i>, punctured subchannels) may also be identified using TXVector parameters, as shown below.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	35.11.5 INACTIVE_SUBCHANNELS An EHT STA shall not transmit on any 20 MHz subchannel that is punctured as indicated in the TXVECTOR parameter INACTIVE_SUBCHANNELS (see Table 36-1 (TXVECTOR and RXVECTOR parameters)). The indication of which subchannels are punctured in a non-HT duplicate PPDU or EHT PPDU is conveyed from the MAC to the PHY through the TXVECTOR parameter INACTIVE_SUBCHANNELS (see Table 36-1 (TXVECTOR and RXVECTOR parameters)). The parameter INACTIVE_SUBCHANNELS is present in the TXVECTOR of a non-HT duplicate PPDU or EHT PPDU when the conditions defined in 35.15.2 (Preamble puncturing operation) are satisfied. Wi-Fi 7 Draft Standard at 671. If a 20 MHz subchannel is indicated as a punctured subchannel in the most recently exchanged Disabled Subchannel Bitmap subfield in the EHT Operation element, the corresponding bit in the TXVECTOR parameter INACTIVE_SUBCHANNELS shall be set to 1 and the punctured 20 MHz subchannel shall not be used by the non-TB PPDU(s) that is transmitted during the time allocated by the associated AP. Wi-Fi 7 Draft Standard at 527. When operating as an AP MLD or a non-AP MLD, the virtual MAC interface of the Galaxy S24 Ultra evaluates the channel information, such as the puncturing pattern, to determine what portions of channels are unavailable, and therefore not to be recommended and/or used for transmission or reception purposes. <u>Bandwidth Signaling TA</u> As another example of information regarding bandwidth availabilities, a bandwidth signaling transmitter address (TA) indicates the presence of additional signaling related to the bandwidth to be used in a subsequent transmission. A bandwidth signaling TA may be

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	communicated in connection with control frames such as an RTS frame, a PS-Poll frame, or a BlockAckReq frame. 35.2 EHT channel access 35.2.1 TXOP 35.2.1.1 Bandwidth signaling An EHT STA that is a STA 6G and is transmitting a Control frame in non-HT duplicate format with a bandwidth signaling TA addressed to an EHT STA shall set the TXVECTOR parameter CH_BANDWIDTH_IN_NON_HT signaled via the scrambling sequence and SERVICE field according to Table 36-1 (TXVECTOR and RXVECTOR parameters). An EHT STA that is a STA 6G and is transmitting a CTS frame in non-HT duplicate format in response to an RTS frame in non-HT duplicate format with a bandwidth signaling TA addressed to the EHT STA shall set the TXVECTOR parameter CH_BANDWIDTH_IN_NON_HT signaled via the scrambling sequence and SERVICE field according to Table 36-1 (TXVECTOR and RXVECTOR parameters). Wi-Fi 7 Draft Standard at 523. Additionally, multi-link enhancements in the use of management primitives, clear channel assessments, link monitoring, bandwidth query or link quality reports, and/or channel availability mechanisms may be used for communicating information about bandwidth availabilities to the virtual MAC interface. Thus, when operating as an AP MLD or a non-AP MLD, the SME of the Galaxy S24 Ultra makes decisions and/or recommendations about which channels to use for data transmission by collecting information about channel conditions, including noise levels, and selecting the channels that offer the best performance. To accomplish this, the MLME provides the SME with information about the available channels and their characteristics, such as channel utilization and interference levels. The PLME provides feedback to the MLME about channel conditions, which the MLME may then relay to the SME.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
[1.g] wherein the processing interface is configured to, after the circuitry has been connected to the application interface and when the wireless networking device is being used, and in a manner transparent to any layer of the wireless networking device above the processing interface,	In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has configured the processing interface such that after the circuitry has been connected to the application interface and when the wireless networking device is being used, the processing interface operates in a manner transparent to any layer of the wireless networking device above the processing interface. Layers between the processing interface and the application interface include, for example, a data link interface. As described with respect to elements 1.a and 1.b, when operating as an AP MLD or a non-AP MLD, the processing interface of the Galaxy S24 Ultra comprises at least a portion of the SME, MLME, MAC SAP, MLME SAP, and PLME SAP in combination with at least some functionality of the UMAC. The SME, MLME, PLME, MAC SAP, and UMAC exchange information and operate to make bandwidth allocation decisions and/or recommendations in a manner transparent to all layers of the wireless networking device above the processing interface such as the data link layer. 4.2.5 Interaction with other IEEE 802[®] layers IEEE Std 802.11 is required to appear to higher layers [logical link control (LLC) sublayer] as a general-purpose IEEE 802 LAN. This requires that the IEEE 802.11 network handle STA mobility within the MAC sublayer. To meet reliability assumptions (that LLC makes about lower layers), it is necessary for IEEE Std 802.11 to incorporate functionality that is untraditional for MAC sublayers. IEEE 802.11-2020 Standard for Information Technology—Telecommunications and Information Exchange Between Systems Local and Metropolitan Area Networks—Specific Requirements (2020) at 219.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	An MLD supports multiple MAC functions, with synchronization across the MAC functions as needed via the MLD synchronization service (see 35.3.25 (MLD synchronization service)) and otherwise coordinated by the SME. Each affiliated STA is enumerated with a Link ID (for example, as Link 1 and Link 2 in Figure 4-33b (Reference model for an MLD for two links)) and MLME primitives are invoked through an MLME SAP. The SME maintains the authentication and association states. The Authenticator and the MAC-SAP of the AP MLD are identified by the same AP MLD MAC address. The Supplicant and the MAC-SAP of the non-AP MLD are identified by the same non-AP MLD MAC address. The SME is responsible for coordinating the MLD and each of the affiliated STAs through the MLME, and to maintain an RSNA key management entity and IEEE 802.1X Authenticator or Supplicant, for MLO. Wi-Fi 7 Draft Standard at 78. The SME maintains the authentication and association states. The same AP MLD MAC address and same non-AP MLD MAC address are used. Thus, when the Galaxy S24 Ultra is being used, operating as an AP MLD or a non-AP MLD, its processing interface operates in a manner transparent to any layer of the Galaxy S24 Ultra above the processing interface. Further, testing of the Galaxy S24 Ultra indicates that, when the Galaxy S24 Ultra is in use, its processing interface, including its virtual MAC interface, operates to make bandwidth allocation decisions and/or recommendations in a manner transparent to all layers of the wireless networking device above the processing interface such as the data link layer. For example, the screenshots below demonstrate that, in use, the processing interface of the Galaxy S24 Ultra operates to make, for example, bandwidth allocation decisions using each of the 2.4 GHz, 5 GHz, and 6 GHz bands.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra


USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra								
	 The screenshot displays the Wi-Fi settings for the network 'ASUSZENWIFI2'. It shows three frequency bands: 2.4 GHz, 5 GHz, and 6 GHz, all of which are 'CONNECTED'. The signal strength for each band is indicated by a green bar and a dBm value. The 2.4 GHz band shows -47 dBm, the 5 GHz band shows -66 dBm, and the 6 GHz band shows -77 dBm. A red box highlights the 2.4 GHz, 5 GHz, and 6 GHz sections. Below these, there are two more sections for 'Access Point' settings, each showing a 2.4 GHz band with signal strength values of -69 dBm and -80 dBm, and a 6 GHz band with a signal strength value of -86 dBm. The bottom section shows a 5 GHz band with a signal strength value of -79 dBm. The status bar at the top shows the time as 5:56, signal strength, and 100% battery. <table border="1"><thead><tr><th>Frequency Band</th><th>Signal Strength (dBm)</th></tr></thead><tbody><tr><td>2.4 GHz</td><td>-47</td></tr><tr><td>5 GHz</td><td>-66</td></tr><tr><td>6 GHz</td><td>-77</td></tr></tbody></table>	Frequency Band	Signal Strength (dBm)	2.4 GHz	-47	5 GHz	-66	6 GHz	-77
Frequency Band	Signal Strength (dBm)								
2.4 GHz	-47								
5 GHz	-66								
6 GHz	-77								

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	WiFiman application screenshot taken on Galaxy S24 Ultra demonstrating connection with local access point (emphasis added).

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	5:58 GG 99% < Connection information Link statusL2 statusL3 status ASUSZENWIFI2 06:28:aa:6c:c2:40 [MLD] RSSI [2.4GHz] Not in use [6GHz] Not in use [5GHz] -75 dBm  Channel utilization [2.4GHz] Not in use [5GHz] 9% (23/255)  Link speed [2.4GHz] Tx=68 Mbps / Rx=17 Mbps [6GHz] Tx=0 Mbps / Rx=0 Mbps [5GHz] Tx=432 Mbps / Rx=288 Mbps

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra


USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra																					
	WiFiman application screenshot taken on Galaxy S24 Ultra demonstrating connection with local access point. As shown above, the processing interface’s utilization of the available channels changes over time. Despite this, as shown below, in use, the Galaxy S24 Ultra is associated with only a single IP address and a single MAC address used to route Internet traffic to the Galaxy S24 Ultra. <table><tr><th>Nombre del host</th><th>Dirección MAC</th><th>Tipo de conexión</th></tr><tr><td>decoMeshXE5300</td><td>98:25:4A:FC:22:27</td><td>Ethernet</td></tr><tr><td>834-v6-9EE0</td><td>AC:13:9C:F1:9E:E0</td><td>Ethernet</td></tr><tr><td>ac:b9:2f:1a:05:a3</td><td>AC:B9:2F:1A:05:A3</td><td>Ethernet</td></tr><tr><td>Joses-MBP</td><td>6C:7E:67:DB:31:0C</td><td>Ethernet</td></tr><tr><td>cc:28:aa:6c:c2:40</td><td>CC:28:AA:6C:C2:40</td><td>Ethernet</td></tr><tr><td>Jose-S24-Ultra</td><td>00:32:3A:06:B3:7D</td><td>Ethernet</td></tr></table>	Nombre del host	Dirección MAC	Tipo de conexión	decoMeshXE5300	98:25:4A:FC:22:27	Ethernet	834-v6-9EE0	AC:13:9C:F1:9E:E0	Ethernet	ac:b9:2f:1a:05:a3	AC:B9:2F:1A:05:A3	Ethernet	Joses-MBP	6C:7E:67:DB:31:0C	Ethernet	cc:28:aa:6c:c2:40	CC:28:AA:6C:C2:40	Ethernet	Jose-S24-Ultra	00:32:3A:06:B3:7D	Ethernet
Nombre del host	Dirección MAC	Tipo de conexión																				
decoMeshXE5300	98:25:4A:FC:22:27	Ethernet																				
834-v6-9EE0	AC:13:9C:F1:9E:E0	Ethernet																				
ac:b9:2f:1a:05:a3	AC:B9:2F:1A:05:A3	Ethernet																				
Joses-MBP	6C:7E:67:DB:31:0C	Ethernet																				
cc:28:aa:6c:c2:40	CC:28:AA:6C:C2:40	Ethernet																				
Jose-S24-Ultra	00:32:3A:06:B3:7D	Ethernet																				

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	Internet browser screenshot indicating connection between Sagemcom Internet Gateway router and Galaxy S24 Ultra (emphasis added).
[1.h] (a) request or create (i) a first association between a recipient and the first actual MAC and PHY interfaces and (ii) a second association between the recipient and the second actual MAC and PHY interfaces,	In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has configured the processing interface to request or create (i) a first association between a recipient and the first actual MAC and PHY interfaces and (ii) a second association between the recipient and the second actual MAC and PHY interfaces. MLO allows a non-AP MLD and an AP MLD to establish multiple links between their corresponding STAs. The Galaxy S24 Ultra, when operating as an AP MLD or a non-AP MLD, is configured to request or create associations between its STAs and those of another device. As described above, the Galaxy S24 Ultra has multiple STAs, each having a corresponding actual PHY interface and a corresponding actual MAC interface. Each station is associated with a frequency band, such as 2.4 GHz, 5 GHz, or 6 GHz. MLO is defined for an EHT STA in 35.3 (Multi-link operation (MLO)). MLO allows an AP MLD and a non-AP MLD to set up multiple links between them. A reference model for MLO is described in 4.9.6 (Reference model for multi-link operation (MLO)). Wi-Fi 7 Draft Standard at 523.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	4.9.6 Reference model for multi-link operation (MLO) MLO defines a set of procedures allowing communication over one or more links between MLDs. An MLD manages such communication over one or more links. Communication over links using different channels on different frequency bands or the same frequency band can occur simultaneously or not depending on the capabilities of both the AP MLD and the non-AP MLD (see 35.3.16.3 (Simultaneous transmit and receive (STR) operation) and 35.3.16.4 (Nonsimultaneous transmit and receive (NSTR) operation)). The MLO procedures (see 35.3 (Multi-link operation (MLO))) allow a pair of MLDs to discover, synchronize, (de)authenticate, (re)associate, disassociate, and manage links and other resources with each other on any common bands or channels that are supported by both MLDs. Each MLD has a single MAC-SAP. Each STA affiliated with an MLD has a MAC address different from any other STA affiliated with the same MLD. Wi-Fi 7 Draft Standard at 76. When a link is established between a non-AP MLD and an AP MLD, an association is requested or created between the actual MAC and actual PHY interfaces of the non-AP MLD and the AP MLD.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	Figure 4-33a—Example communication system between two MLDs via their affiliated STAs (for individually addressed MSDUs)

Fig. 4-33a, Wi-Fi 7 Draft Standard at 77.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	During MLO discovery and ML setup, a non-AP MLD may discover an AP MLD using either (1) passive or active scanning, or (2) transmission of a multi-link probe request. The non-AP MLD receives from the AP MLD either a beacon frame or a multi-link probe response frame. These exchanges of frames allow the non-AP MLD and the AP MLD (here, the recipient) to request or create an association between their STAs. Operating as an AP MLD, the Galaxy S24 Ultra may request or create associations between its actual MAC and PHY interfaces and a recipient, such as a non-AP MLD device. Additionally, when operating as a non-AP MLD, the Galaxy S24 Ultra may request or create associations between its actual MAC and PHY interfaces and a recipient, such as an AP MLD device. 35.3.4.6 Frame exchange sequences during MLO discovery and ML setup A non-AP MLD is expected to discover an AP MLD and affiliated AP(s) of interest before initiating an ML setup with the AP MLD. The non-AP MLD can use one or a combination of the following methods for discovering the AP MLD and affiliated AP(s) of interest: — Through each of its affiliated STAs, perform passive scanning by following the procedure defined in 11.1.4.2 (Passive scanning) or active scanning by following the procedure defined in 11.1.4.3 (Active scanning and probing procedures). — Through one of its affiliated STAs, transmit a multi-link probe request on any link that the AP MLD is operating on, with the frame addressed to the affiliated AP operating on that link, to obtain information about the AP MLD and its affiliated AP(s) by following the procedure defined in 35.3.4.2 (Use of multi-link probe request and response). Wi-Fi 7 Draft Standard at 544.

Exhibit G

US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	Figure 35-5 (Possible frame exchange sequences during MLO discovery and ML setup when the AP operating on the channel does not correspond to a nontransmitted BSSID) shows a possible frame exchange sequence performed, during discovery, between a non-AP STA affiliated with a non-AP MLD and an AP that does not correspond to a nontransmitted BSSID and is affiliated with an AP MLD. ← = Alternate sequence ^aThis example assumes that APs on 2.4 GHz and 5 GHz do not correspond to a nonTxBSSID [I] = Individually addressed [IB] = Individual or broadcast address (i.e., A1 is set to BSSID or broadcast address) [B] = Broadcast (A1 is set to broadcast address) [cB] = Conditionally broadcast (i.e., A1 set to broadcast address in 6 GHz or if dot11FILSOmitReplicateProbeResponses equal to true); otherwise, individually addressed (i.e., A1 set to the MAC address of the non-AP STA operating on the link) Figure 35-5—Possible frame exchange sequences during MLO discovery and ML setup when the AP operating on the channel does not correspond to a nontransmitted BSSID

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	Fig. 35-5, Wi-Fi 7 Draft Standard at 545. As indicated above, the Galaxy S24 Ultra has three wireless transceivers, including at least first and second wireless transceivers. Each transceiver is associated with an actual MAC interface and an actual PHY interface. Thus, when operating as an AP MLD or a non-AP MLD, the Galaxy S24 Ultra may request or create an association between each of its actual PHY and MAC interfaces and a recipient. Further, testing of the Galaxy S24 Ultra indicates that, when the Galaxy S24 Ultra is in use, its processing interface operates to request or create associations between the Galaxy S24 Ultra and a recipient, such as an AP MLD, over multiple bands. For example, the screenshot below demonstrates that, in use, the Galaxy S24 Ultra may have an association between a recipient and each of its three transceivers.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra


USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra								
	 The screenshot displays the Wi-Fi settings for the network 'ASUSZENWIFI2'. It shows three frequency bands: 2.4 GHz, 5 GHz, and 6 GHz, all marked as 'CONNECTED'. The signal strength for each band is indicated by a green bar and a dBm value. The 2.4 GHz band shows -47 dBm, the 5 GHz band shows -66 dBm, and the 6 GHz band shows -77 dBm. A red box highlights the 2.4 GHz, 5 GHz, and 6 GHz sections. Below these, there are two more sections for 'Access Point' settings, each showing a 2.4 GHz band with signal strength values of -69 dBm and -80 dBm, and a 6 GHz band with a signal strength value of -86 dBm. The bottom section shows a 5 GHz band with a signal strength value of -79 dBm. The status bar at the top shows the time as 5:56, signal strength, and 100% battery. <table border="1"><thead><tr><th>Frequency Band</th><th>Signal Strength (dBm)</th></tr></thead><tbody><tr><td>2.4 GHz</td><td>-47</td></tr><tr><td>5 GHz</td><td>-66</td></tr><tr><td>6 GHz</td><td>-77</td></tr></tbody></table>	Frequency Band	Signal Strength (dBm)	2.4 GHz	-47	5 GHz	-66	6 GHz	-77
Frequency Band	Signal Strength (dBm)								
2.4 GHz	-47								
5 GHz	-66								
6 GHz	-77								

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	WiFiman application screenshot taken on Galaxy S24 Ultra demonstrating connection with local access point (emphasis added).
[1.i] (b) identify at least one first portion of the first actual bandwidth of the first wireless transceiver, the identified at least one first portion comprising a set of given resources,	In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has configured the processing interface to identify at least one first portion of the first actual bandwidth of the first wireless transceiver, the identified at least one first portion comprising a set of given resources. To achieve the increased bandwidth utilization and efficiency objectives of the Wi-Fi 7 Draft Standard and for MLO, when operating as an AP MLD or a non-AP MLD, the processing interface of the Galaxy S24 Ultra monitors and identifies portions of bandwidths for each of the device's three transceivers that are available for communication so that the processing interface can make resource allocations and/or recommendations based at least on channel utilization and/or congestion. <i>See, e.g.</i>, Wi-Fi 7 Draft Standard at 629-637. As described with respect to element 1.f, information regarding bandwidth availabilities is communicated to the virtual MAC using a variety of operations. Once received, the information regarding bandwidth availabilities allows the processing interface to identify at least one portion of the first actual bandwidth of the first wireless transceiver. A portion of actual bandwidth may comprise a single RU, a group of RUs or an MRU. Further, a portion of actual bandwidth comprises a set of resources that include, for example, bandwidth channels or subchannels associated with a particular frequency band. As a particular example, a set of given resources may comprise a plurality of 20MHz subchannels for a particular frequency band.
[1.j] (c) evaluate whether any of the given resources of the first identified actual bandwidth portion	In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has configured the processing interface to evaluate whether any of the given resources of the first identified actual bandwidth portion are unavailable for communication.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
are unavailable for communication, and	As described with respect to element 1.f, the Galaxy S24 Ultra, when operating as an AP MLD or a non-AP MLD, obtains information about bandwidth availabilities from other devices through, for example, beacon frames and multi-link response frames. For example, both the beacon frame and the multi-link probe response frame include a multi-link traffic indication element, an EHT capabilities element, an EHT operation element, a TID-to-Link mapping element, and a channel usage element. Wi-Fi 7 Draft Standard at 183-84 (beacon frame), 190-91 (probe response frame). These elements include information regarding bandwidth availability, such as a per-link traffic indication list contained in the multi-link traffic indication element and PHY capabilities information contained in the EHT capabilities element. Wi-Fi 7 Draft Standard at 295-97 (Multi-Link Traffic Indication), 269-96 (EHT Capabilities). From such information, the processing interface can identify bandwidth portions that are unavailable for communication. The Wi-Fi Agile Multiband Specification provides examples of information regarding bandwidth availabilities that may be communicated by the virtual PHY interfaces. In accordance with the Wi-Fi Agile Multiband Specification, when operating as a non-AP MLD, for example, the Galaxy S24 Ultra provides “to a Wi-Fi Agile Multiband AP a list of channels and bands on which it prefers not to be associated,” including in each list entry: channel and band, preference value, and reason code. Wi-Fi Agile Multiband Specification at § 2.3.2. A Wi-Fi Agile Multiband STA shall support the following features: • Indicates whether or not it has a cellular data connection available (refer to section 4.2.3) • Provides to a Wi-Fi Agile Multiband AP a list of channels and bands on which it prefers not to be associated, including in each list entry: ▪ Channel and band ▪ Preference value ▪ Reason code Wi-Fi Agile Multiband Specification at § 2.3.2.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	Reason codes may include, for example, co-located interference, where an “unacceptable level of interference is being experienced by the Wi-Fi Agile Multiband STA in this channel,” and in-device interferer, where the “Agile Multiband STA has another active connection in this channel, or near enough to this channel to cause operating interference.” Wi-Fi Agile Multiband Specification at Table 10. “This information is communicated to the Wi-Fi Agile Multiband AP when the Wi-Fi Agile Multiband STA associates or reassociates, and when the information changes while the Wi-Fi Agile Multiband STA is associated.” Wi-Fi Agile Multiband Specification at §3.2. For a Wi-Fi Agile Multiband AP that supports MLO as defined in the Wi-Fi 7 Draft Standard, “this list of non-preferred channels” is indicated across all affiliated non-AP STAs. <i>Id.</i> Additionally, the Galaxy S24 Ultra, with Wi-Fi 7 enabled, is configured for preamble puncturing. Preamble puncturing allows WNDs, such as the Galaxy S24 Ultra, to recognize and exclude unavailable subchannels from a transmission. For example, the Wi-Fi 7 Draft Standard describes the U-SIG field that carries the information necessary to interpret EHT PPDU, and that shows a puncturing pattern wherein RUs and MRUs are punctured. The puncturing pattern indicates what sub-portions of RUs or MRUs are not to be used for transmission or reception purposes. Unavailable subchannels may be indicated, for example, in a Disabled Subchannel Bitmap. 36.3.12.11 EHT preamble of preamble punctured EHT MU PPDU 36.3.12.11.1 General Preamble puncturing refers to the transmission of a PPDU in which no signal is present in at least one of the 20 MHz subchannels within the PPDU bandwidth. Preamble puncturing might be the result of the unavailability of 20 MHz subchannel(s) within the PPDU bandwidth, such as a busy channel indicated by the CCA or the setting of the Disabled Subchannel Bitmap subfield in the EHT Operations element (see 9.4.2.321 (EHT Operation element)). Wi-Fi 7 Draft Standard at 867.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	Otherwise, an EHT STA may puncture other subchannels in addition to those indicated in the Disabled Subchannel Bitmap subfield in the EHT Operation element in an EHT MU PPDU or a non-HT duplicate PPDU. If an EHT AP punctures other subchannels in an EHT MU PPDU or a non-HT duplicate PPDU in addition to those indicated in the Disabled Subchannel Bitmap subfield and solicits a response to the PPDU, the EHT AP shall use a triggering frame to solicit the response in a TB PPDU and assign an RU or MRU within the nonpunctured subchannel set to a responding EHT STA. Wi-Fi 7 Draft Standard at 686. Regardless of the inclusion of the Disabled Subchannel Bitmap subfield in the EHT Operation element, an EHT STA may use EHT MU PPDU preamble puncturing modes as defined in 36.3.12.11 (EHT preamble of preamble punctured EHT MU PPDU) or EHT TB PPDU in which not all the 20 MHz subchannels are assigned. Wi-Fi 7 Draft Standard at 686. Unavailable subchannels (<i>i.e.</i>, punctured subchannels) may also be identified using TXVector parameters, as shown below. 35.11.5 INACTIVE_SUBCHANNELS An EHT STA shall not transmit on any 20 MHz subchannel that is punctured as indicated in the TXVECTOR parameter INACTIVE_SUBCHANNELS (see Table 36-1 (TXVECTOR and RXVECTOR parameters)). The indication of which subchannels are punctured in a non-HT duplicate PPDU or EHT PPDU is conveyed from the MAC to the PHY through the TXVECTOR parameter INACTIVE_SUBCHANNELS (see Table 36-1 (TXVECTOR and RXVECTOR parameters)). The parameter INACTIVE_SUBCHANNELS is present in the TXVECTOR of a non-HT duplicate PPDU or EHT PPDU when the conditions defined in 35.15.2 (Preamble puncturing operation) are satisfied. Wi-Fi 7 Draft Standard at 671.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	If a 20 MHz subchannel is indicated as a punctured subchannel in the most recently exchanged Disabled Subchannel Bitmap subfield in the EHT Operation element, the corresponding bit in the TXVECTOR parameter INACTIVE_SUBCHANNELS shall be set to 1 and the punctured 20 MHz subchannel shall not be used by the non-TB PPDU(s) that is transmitted during the time allocated by the associated AP. Wi-Fi 7 Draft Standard at 527. When operating as an AP MLD or a non-AP MLD, the processing interface of the Galaxy S24 Ultra evaluates the channel information, such as the puncturing pattern, to determine what portions of channels are unavailable, and therefore not to be recommended and/or used for transmission or reception purposes. Thus, based on the information provided to the SME portions of the processing interface, the processing interface may evaluate whether any of the given resources of the first identified actual bandwidth portion are unavailable. For example, quality of the possible communications channels may be assessed to identify interference making channels unavailable for communication. Based on such evaluation, the unavailable channels may be avoided in channel selection.
[1.k] (d) use the first wireless transceiver to transmit the first data stream to the recipient, without requiring disassociation of the recipient from either or both of the first and second actual MAC and PHY interfaces, using a subset of frequencies corresponding to only the given resources of the first bandwidth portion that are not unavailable for communication to	In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has configured the processing interface to use the first wireless transceiver to transmit the first data stream to the recipient, without requiring disassociation of the recipient from either or both of the first and second actual MAC and PHY interfaces, using a subset of frequencies corresponding to only the given resources of the first bandwidth portion that are not unavailable for communication to thereby at least partially satisfy the first wireless bandwidth requirement of the first application. The Galaxy S24 Ultra, when operating as an AP MLD or a non-AP MLD, enables the use of TID-to-link mapping in accordance with the Wi-Fi 7 Draft Standard. For example, when operating as an AP MLD, the SME and UMAC (through a Resource Allocation

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
thereby at least partially satisfy the first wireless bandwidth requirement of the first application; and	Manager) determine TID-to-link mapping and assign RUs/MRUs based on traffic needs and available resources on each link. Likewise, when operating as a non-AP MLD, the SME and UMAC may monitor and evaluate traffic needs and available resources to provide recommendation information to an AP MLD device assigning RUs/MRUs. Further, when operating as a non-AP MLD, the Galaxy S24 Ultra follows the TID-to-link mapping determined by the AP. Thus, the system architecture solves limitations of multi-band to enable MLO in IEEE 802.11be to be based on the processing interface's unique understanding of traffic priorities, queue lengths, and real-time network status enabling intelligent TID-to-link mapping. This mapping determines which traffic (<i>e.g.</i>, identified by TID) should be directed to which links (<i>i.e.</i>, associated bandwidth resources). As a particular example, when operating as an AP MLD, the SME and UMAC allocate appropriate RU(s)/MRU(s) based on the data requirements of the specific traffic type mapped to a link. The UMAC considers factors like the amount of data to be transmitted for a particular TID and the channel bandwidth available on the chosen link. It can choose to allocate a single RU for smaller data packets or low-priority traffic, or allocate multiple RUs combined into an MRU for larger data transfers or high-priority traffic requiring more bandwidth. Assigning RUs or MRUs is an integral part of TID-to-link mapping. Likewise, when operating as a non-AP MLD, the SME and UMAC direct packets to links based on the TID-to-link mapping identified by an AP. In a survey paper published in IEEE Access and discussing MLO operations as presented in the Wi-Fi 7 Draft Standard, the authors describe that the processing interface of an MLD assigns traffic flows to channels based on channel availability and traffic needs.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	The motivation for MLO stems from its projected benefits across various dimensions [20]. Firstly, the introduction of the multi-link framework enables significantly improved coordinated operations across multiple links [34], [35]. Through unified and cooperative link management, Wi-Fi 7 can more easily accomplish additional throughput for data flows separated across links than earlier Wi-Fi technologies with separate and independent operations across multiple bands. Secondly, using several lines concurrently enhances the likelihood that a channel will be accessed, considerably reducing latency [36]. Thirdly, MLO permits duplication across numerous connections³ to guarantee the successful transmission of crucial data that demands extremely high reliability. Finally, depending on the application's requirements, MLO can be used to assign data flows to specific links to accomplish traffic separation [37]. Abdalfahid, Alsadg A., <i>et al.</i>, <i>Multi-Link Operation in IEEE802.11be Extremely High Throughput: A Survey</i>, 12 IEEE Access 46891, 46892 (2024) (emphasis added).

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	B. TID-TO-LINK MAPPING The IEEE 802.11 standard defines a Traffic Identifier (TID) as a four-bit value (ranging from 0 to 7) used to differentiate packets for QoS purposes [37]. There are $(2^4) = 16$ possible TID values; 8 identify Traffic Categories (TCs), and the other 8 identify parameterized Traffic Streams (TSs). The TID is assigned to an MSDU in the layers above the MAC () [76]. In MLO, TID is crucial in directing traffic with specific QoS requirements to the appropriate connections or channels. TID-to-link mapping associates each TID with a connection set, allowing any link within that set to transmit data frames associated with that TID. All established connections are initially linked to each TID, though this mapping can later be adjusted through negotiation processes [20], [77]. Abdalfahid, Alsadg A., <i>et al.</i>, <i>Multi-Link Operation in IEEE802.11be Extremely High Throughput: A Survey</i>, 12 IEEE Access 46891, 46895 (2024) (emphasis added). When the Galaxy S24 Ultra operates as an AP MLD or a non-AP MLD, its processing interface instructs the actual MAC and actual PHY to transmit data packets using primitives. These instructions specify the chosen link and may specify the allocated RU/MRU configuration. Based on the instructions, the actual PHY layer segments data packets into units, modulates the data units using appropriate techniques for transmission over the designated link, and transmits the modulated data units using the allocated radio frequencies on the chosen transceiver. For example, the processing interface uses certain vectors, including TXVECTOR, RXVECTOR, PHYCONFIG_VECTOR, and TRIG_VECTOR to instruct the PHY.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	36.2 EHT PHY service interface 36.2.1 Introduction The EHT PHY provides an interface to the EHT MAC through an extension of the generic PHY service interface defined in 8.3.4 (Basic service and options). The interface includes TXVECTOR, RXVECTOR, PHYCONFIG_VECTOR, and TRIGVECTOR. The EHT MAC uses the TXVECTOR to supply the EHT PHY with per-PPDU transmit parameters. The EHT PHY uses the RXVECTOR to inform the EHT MAC of the received PPDU parameters. The EHT MAC uses the PHYCONFIG_VECTOR to configure the EHT PHY for operation that is independent of PPDU transmission or reception. The EHT MAC uses the TRIGVECTOR to configure the EHT PHY to receive EHT TB PPDU's over each assigned RU or MRU. Wi-Fi 7 Draft Standard at 708, 709-23 (listing TXVECTOR and RXVECTOR parameters). In all options, in order to transmit data, the MAC generates a PHY-TXSTART.request primitive, which causes the PHY entity to respond with a PHY-TXSTART.confirm primitive and enter the transmit state. Further, the PHY is set to operate at the appropriate frequency through station management via the PLME, as specified in 36.4 (EHT PLME). Other transmit parameters, such as EHT-MCS, coding types, and transmit power, are set via the PHY-SAP using the PHY-TXSTART.request primitive (containing TXVECTOR), as described in 36.2.2 (TXVECTOR and RXVECTOR parameters). After transmitting a PPDU that carries a Trigger frame, the MAC sublayer issues a PHY-TRIGGER.request with a TRIGVECTOR parameter that provides the PHY entity with the information needed to demodulate the expected EHT TB PPDU response. The remainder of the subclause applies to the first two paths. Wi-Fi 7 Draft Standard at 940. As described above with respect to element 1.j, the processing interface of the Galaxy S24 Ultra evaluates channel information, such as a puncturing pattern to determine what portions of channels are unavailable for transmission or reception purposes. The processing interface may then transmit a data stream using only portions of bandwidth that are not unavailable.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	Accordingly, when operating as AP MLD or as a non-AP MLD, the processing interface is configured to transmit the first data stream using a subset of frequencies corresponding to only the given resources of the first bandwidth portion that are not unavailable for communication. Additionally, the processing interface may transmit a data stream using the first wireless transceiver without requiring disassociation of the recipient from either or both of the first and second actual MAC and PHY interfaces. As described with respect to element 1.h, MLO allows a non-AP MLD and an AP MLD to establish multiple links between their corresponding STAs. Data may be transmitted or received on one of the established links without requiring disassociation of the other established links. 35.3.16 ML channel access 35.3.16.1 General A STA that is affiliated with an MLD shall contend for the WM on its link independently from the other STA(s) affiliated with the same MLD, unless explicitly stated otherwise in the subclauses below. Wi-Fi 7 Draft Standard at 598.
[1.1] wherein, after the circuitry has been connected to the application interface and when the wireless networking is being used, the wireless networking device's utilization of the first available bandwidth portion of the first wireless transceiver does not prevent any wireless networking device devices [sic] from utilizing a	In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has configured it such that, after the circuitry has been connected to the application interface and when the wireless networking device is being used, the wireless networking device's utilization of the first available bandwidth portion of the first wireless transceiver does not prevent any wireless networking device from utilizing a range of frequencies corresponding to the remaining portion of the bandwidth availability of the first wireless transceiver for data transmission or reception purposes at the same time that the first bandwidth portion is being used for data transmission purposes.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
range of frequencies corresponding to the remaining portion of the bandwidth availability of the first wireless transceiver for data transmission or reception purposes at the same time that the first bandwidth portion is being used for data transmission purposes.	As described in the Wi-Fi 7 Draft Standard, an AP or non-AP MLD like the Galaxy S24 Ultra will use each of the first and second wireless transceivers to communicate via the RUs or MRUs that have been respectively assigned. The Galaxy S24 Ultra is configured for Multi-user Multiple Input Multiple Output (MU-MIMO) procedures, as well as Orthogonal Frequency Division Multiple Access (OFDMA) procedures. The EHT PHY provides support for DL OFDMA, UL OFDMA, DL MU-MIMO, and UL MU-MIMO. Both DL MU-MIMO and UL MU-MIMO transmissions are supported on both the entire PPDU bandwidth and portions of the PPDU bandwidth, with the assigned resource unit of size greater than or equal to 242 tones. On a resource unit utilizing MU-MIMO transmission, there is support for up to 8 users with up to 4 spatial streams per user with the total number of spatial streams across all users not exceeding 8. The EHT PHY also supports preamble puncturing of an EHT MU PPDU for both OFDMA and non-OFDMA. Wi-Fi 7 Draft Standard at 701.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	Wi-Fi CERTIFIED 7™ (continued) MCS 8-9 Rx MCS 8-9 Tx MCS 10-11 Rx MCS 10-11 Tx MCS 12-13 Rx MCS 12-13 Tx Multi-link reconfiguration – AP removal Multi-link reconfiguration – AP restart Multi-RU Operating mode indication Operating mode indication for 320 MHz Static puncturing STR (Simultaneous Transmit and Receive) SU-MIMO Triggered uplink access optimization UL MU-MIMO UL OFDMA Wi-Fi CERTIFIED Certificate for Qualcomm FastConnect 7800 Mobile Connectivity System, Cert. I.D. WFA127693 (2024) (emphasis added). Further, testing of the Galaxy S24 Ultra indicates that the wireless networking device's utilization of identified bandwidth portions does not prevent any wireless networking device from utilizing a range of frequencies corresponding to remaining portions of bandwidth availability. For example, when one MLD, a Galaxy S25 Ultra, was used to transmit video data to another MLD, a Galaxy S24 Ultra, via an AP using portions of available bandwidth, other bandwidth portions remained available for use by the S24 Ultra, the S25 Ultra, and other devices.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	The screenshots below taken from the Galaxy S24 Ultra and Galaxy S25 Ultra devices show connections to the AP using the same three channels: a 20 MHz channel (“Ch 9”) of the 2.4 GHz frequency band, a 160 MHz channel (“Ch 104”) of the 5 GHz frequency band, and a 320 MHz channel (“Ch 85”) of the 6 GHz frequency band.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra


USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	 The screenshot shows the WiFiman application interface on a Galaxy S24 Ultra. At the top, the title is 'ASUSZENWIFI2'. Below it, the channel is '9, 85, 104' and security is 'WPA2-PSK / WPA3-SAE / WPS'. There are three tabs: 'All (3)', '2.4 GHz (1)', and '5 GHz (1)'. The 'All (3)' tab is selected. The interface lists three access points: 2.4 GHz (CONNECTED, -44 dBm, Ch: 9 (20 MHz)), 5 GHz (CONNECTED, -60 dBm, Ch: 104 (160 MHz)), and 6 GHz (CONNECTED, -64 dBm, Ch: 85 (320 MHz)). Each entry has a green bar representing signal strength and a right arrow.  The screenshot shows the WiFiman application interface on a Galaxy S25 Ultra. At the top, the title is 'ASUSZENWIFI2'. Below it, the channel is '9, 85, 104' and security is 'WPA2-PSK / WPA3-SAE / WPS'. There are three tabs: 'All (3)', '2.4 GHz (1)', and '5 GHz (1)'. The 'All (3)' tab is selected. The interface lists three access points: 2.4 GHz (CONNECTED, -59 dBm, Ch: 9 (20 MHz)), 5 GHz (CONNECTED, -61 dBm, Ch: 104 (160 MHz)), and 6 GHz (CONNECTED, -68 dBm, Ch: 85 (320 MHz)). Each entry has a green bar representing signal strength and a right arrow. WiFiman application screenshot taken on Galaxy S24 Ultra showing associations on three frequency bands (Left); WiFiman application screenshot taken on Galaxy S25 Ultra showing associations on three frequency bands (Right).

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	As shown below, the Galaxy S24 Ultra and Galaxy S25 Ultra used only a portion of available bandwidth to communicate the video stream, such that other devices were not impeded from using available bandwidth of the 2.4 GHz, 5 GHz, or 6 GHz transceivers.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra



USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	  WiFiman application screenshot taken on Galaxy S24 Ultra during data reception (Left); WiFiman application screenshot taken on Galaxy S25 Ultra during data transmission (Right).

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	Thus, when operating as an AP MLD or a non-AP MLD, the Galaxy S24 Ultra is configured such that after the circuitry has been connected to the application interface and when the wireless networking device is being used, the wireless networking device's utilization of the first available bandwidth portion of the first wireless transceiver does not prevent other wireless networking devices from utilizing a range of frequencies corresponding to the remaining portion of the bandwidth availability of the first wireless transceiver for data transmission or reception purposes at the same time that the first bandwidth portion is being used for data transmission purposes.
2. The method of claim 1, wherein the wireless networking device comprises a wireless access point.	<i>See claim 1, above.</i> In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has performed the method of claim 1, wherein the Galaxy S24 Ultra comprises a wireless access point. An MLD may be an AP MLD or a non-AP MLD. multi-link device: [MLD] A logical entity that is capable of supporting more than one affiliated station (STA) and can operate using one or more affiliated STAs, and that presents one medium access control (MAC) data service and a single MAC service access point (MAC SAP) to the logical link control (LLC) sublayer. access point (AP) multi-link device (MLD): [AP MLD] An MLD, where each station (STA) affiliated with the MLD is an AP. non-access point (non-AP) multi-link device (MLD): [non-AP MLD] An MLD, where each station (STA) affiliated with the MLD is a non-access point (non-AP) station (non-AP STA). Wi-Fi 7 Draft Standard at 61, 62, 63.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	A wireless terminal device or a network access point may comprise one or more MLDs. A wireless networking device may be, for example, a wireless station in a Wi-Fi 7 system, such as a stationary wireless AP or a mobile wireless AP, such as the Galaxy S24 Ultra, comprising an AP MLD. In this regard, the Galaxy S24 Ultra is operable both as an AP MLD and as a non-AP MLD. For example, the Galaxy S24 Ultra is capable of operating as a mobile hotspot wireless access point, thereby sharing its data connection with other devices using Wi-Fi 7. Mobile hotspot Mobile hotspot uses your data plan to create a Wi-Fi network that can be used by multiple devices. 1. From Settings, tap  Connections > Mobile hotspot and tethering > Mobile hotspot. 2. Tap  to turn on Mobile hotspot. 3. On the devices you want to connect, activate Wi-Fi, and select your device's Mobile hotspot. Enter the Mobile hotspot password to connect.  TIP Tap  QR code to connect another device to your Mobile hotspot by scanning a QR code instead of entering a password. Configure mobile hotspot settings You can customize your mobile hotspot's security and connection settings. 1. From Settings, tap  Connections > Mobile hotspot and tethering > Mobile hotspot. 2. Tap  to turn on Mobile hotspot, and then tap the following settings to change them:

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	<i>Samsung Galaxy S24, S24+, S24 Ultra User Guide</i>, Ver. U 14.1 (English(North America)) (Sept. 6, 2024) at 120. When operating as a mobile hotspot, the Galaxy S24 Ultra behaves as a wireless access point for other devices.
3. The method of claim 1, wherein the first and second frequency bands are specified in at least one member of the family of IEEE 802.11 standards that was in existence as of Oct. 30, 2013.	<i>See claim 1, above.</i> In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has performed the method of claim 1, wherein the first and second frequency bands are specified in at least one member of the family of IEEE 802.11 standards that was in existence as of Oct. 30, 2013. As described with respect to claim 1, the Galaxy S24 Ultra has three frequency bands: 2.4 GHz, 5 GHz, and 6 GHz. The first and second frequency bands are each one of the 2.4 GHz and 5 GHz bands. These bands had been specified, for example, in the IEEE 802.11n standard that is one of the IEEE 802.11 standards that was in existence as of October 30, 2013, and in particular since 2009. 36.3.24.1 General The STA may operate in the 2.4 GHz band, 5 GHz band, or 6 GHz band. The set of valid operating channel numbers by regulatory domain is defined in Annex E. Channel allocation for each band is defined as follows: — In 19.3.15.2 (Channel allocation in the 2.4 GHz band) for the 2.4 GHz band — In 19.3.15.3 (Channel allocation in the 5 GHz band) for the 5 GHz band — In 27.3.23.2 (Channel allocation in the 6 GHz band) for the 6 GHz band Wi-Fi 7 Draft Standard at 909 (referencing Sections 19.3.15.2-3 of Base Standard).

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra						
	19.3.15.1 General The STA may operate in the 5 GHz band and/or 2.4 GHz band. When using 20 MHz channels, it uses channels defined in 17.3.8.4 (5 GHz band) or 16.3.6 (2.4 GHz band). When using 40 MHz channels, it can operate in the channels defined in 19.3.15.2 and 19.3.15.3. IEEE 802.11-2020 Base Standard Section 19.3.15.1 at 2928. 20.3.15 Channel numbering and channelization The STA may operate in the 5 GHz band and/or 2.4 GHz band. When using 20 MHz channels it uses channels defined in 17.3.8.3 (5 GHz band) or 18.4.6 (2.4 GHz band). When using 40 MHz channels, it can operate in the channels defined in 20.3.15.1 and 20.3.15.2. IEEE 802.11n Standard Section 20.3.15 (2009). The Qualcomm FastConnect 7800 Mobile Connectivity System of the Galaxy S24 Ultra supports the corresponding 802.11 predecessor 2.4 GHz and 5 GHz bands, as confirmed from the certification excerpt shown below. <table> <tr> <th colspan="2">Summary of Certifications</th></tr> <tr> <th>CLASSIFICATION</th><th>CERTIFICATION</th></tr> <tr> <td>Connectivity</td><td>2.4 GHz Spectrum Capabilities 5 GHz Spectrum Capabilities</td></tr> </table> Wi-Fi CERTIFIED Certificate for Qualcomm FastConnect 7800 Mobile Connectivity System, Cert. I.D. WFA127693 (2024).	Summary of Certifications		CLASSIFICATION	CERTIFICATION	Connectivity	2.4 GHz Spectrum Capabilities 5 GHz Spectrum Capabilities
Summary of Certifications							
CLASSIFICATION	CERTIFICATION						
Connectivity	2.4 GHz Spectrum Capabilities 5 GHz Spectrum Capabilities						
4. The method of claim 1, wherein the at least one virtual MAC interface includes a decision block.	<i>See claim 1, above.</i>						

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has provided at least one virtual MAC interface that includes a decision block. The Galaxy S24 Ultra may use a TID-to-link mapping element to identify the link(s) on which a corresponding MAC Protocol Data Unit (MPDU) is intended to be transmitted in its proper format at least based upon a unique traffic identifier (TID). The TID represents quality of service (QoS) characteristics such as the type of data stream and its size. TIDs are used to classify traffic based on such QoS characteristics including their bandwidth requirements. For example, the processing interface performs TID-to-Link mapping procedures to determine how data frames should be assigned for transmission. <i>See</i> elements 1.a and 1.k of claim 1. Accordingly, the decision block of the Galaxy S24 Ultra comprises at least those portions of the UMAC and SME that determine the size and type of data to be transmitted for purposes of TID-to-link mapping.
5. The method of claim 1, wherein the at least one virtual MAC interface includes a processing block.	<i>See</i> claim 1, above. In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has provided at least one virtual MAC interface that includes a processing block. The Galaxy S24 Ultra may use a TID-to-link mapping element to identify the link(s) on which a corresponding MAC Protocol Data Unit (MPDU) is intended to be transmitted in its proper format at least based upon a unique traffic identifier (TID). The TID represents quality of service (QoS) characteristics such as the type of data stream and its size. TIDs are used to classify traffic based on such QoS characteristics including their bandwidth requirements.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	For example, the processing interface performs TID-to-Link mapping procedures to determine how data frames should be assigned for transmission including processing data streams accordingly. <i>See</i> elements 1.a and 1.k of claim 1. Accordingly, the processing block of the Galaxy S24 Ultra comprises at least those portions of the UMAC and SME that prepare the data stream to be packetized for purposes of TID-to-link mapping.
6. The method of claim 1, wherein the at least one virtual MAC interface includes an ultra-streaming block.	<i>See</i> claim 1, above. In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has provided at least one virtual MAC interface that includes an ultra-streaming block. The Galaxy S24 Ultra may use a TID-to-link mapping element to identify the link(s) on which a corresponding MAC Protocol Data Unit (MPDU) is intended to be transmitted in its proper format at least based upon a unique traffic identifier (TID). The TID represents quality of service (QoS) characteristics such as the type of data stream and its size. TIDs are used to classify traffic based on such QoS characteristics including their bandwidth requirements. For example, the processing interface performs TID-to-Link mapping procedures to determine how data frames should be assigned for transmission including processing data streams accordingly. <i>See</i> elements 1.a and 1.k of claim 1. Accordingly, the ultra-streaming block of the Galaxy S24 Ultra comprises at least those portions of the UMAC and SME that packetize the prepared data stream for purposes of TID-to-link mapping.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
7. The method of claim 1, wherein the first virtual PHY interface includes an RF block.	<i>See</i> claim 1, above. In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has provided a first virtual PHY interface that includes an RF block. As described with respect to element 1.e of claim 1, in order for the processing interface to make strategic decisions about resource allocation and/or link recommendations, the SME must receive information regarding bandwidth availabilities of the transceivers. For example, to allocate RUs/MRUs to achieve the increased bandwidth utilization and efficiency objectives of the IEEE 802.11be standard and for multi-users, the SME must receive information regarding the bandwidth availabilities of the transceivers from which the RUs/MRUs may be assigned based at least on channel utilization and/or congestion. <i>See, e.g.,</i> Wi-Fi 7 Draft Standard at 629-637. Information regarding bandwidth availabilities of the transceivers may be or include information about the actual PHY itself. Information regarding bandwidth availabilities of the transceivers may additionally or alternatively include information received at the actual PHY from another device, such as an AP MLD device. In each case, information regarding bandwidth availabilities is communicated to the virtual MAC interface. The first virtual PHY interface of the Galaxy S24 Ultra includes at least one RF block comprising those portions of the SME that report information regarding bandwidth availabilities to the virtual MAC. The RF block(s) may be used to determine whether any of the given resources of a bandwidth portion in one of the Wi-Fi bands are unavailable. Each RF block may additionally include a portion of the MLME, where logic or pathways within the MLME are used in reporting information about bandwidth availabilities to the virtual MAC. Additionally, the path of communication by which information regarding bandwidth availabilities is fed to the virtual MAC may be or include portions of the MLME SAP and/or PLME SAP. Each RF block may therefore additionally include a portion of the

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	MLME SAP and/or the PLME SAP through which bandwidth information is directed to the virtual MAC.
8. The method of claim 1, wherein the second virtual PHY interface includes an RF block.	<i>See</i> claim 1, above. In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has provided a second virtual PHY interface that includes an RF block. As described with respect to element 1.e of claim 1, in order for the processing interface to make strategic decisions about resource allocation and/or link recommendations, the SME must receive information regarding bandwidth availabilities of the transceivers. For example, to allocate RUs/MRUs to achieve the increased bandwidth utilization and efficiency objectives of the IEEE 802.11be standard and for multi-users, the SME must receive information regarding the bandwidth availabilities of the transceivers from which the RUs/MRUs may be assigned based at least on channel utilization and/or congestion. <i>See, e.g.,</i> Wi-Fi 7 Draft Standard at 629-637. Information regarding bandwidth availabilities of the transceivers may be or include information about the actual PHY itself. Information regarding bandwidth availabilities of the transceivers may additionally or alternatively include information received at the actual PHY from another device, such as an AP MLD device. In each case, information regarding bandwidth availabilities is communicated to the virtual MAC interface. The second virtual PHY interface of the Galaxy S24 Ultra includes at least one RF block comprising those portions of the SME that report information regarding bandwidth availabilities to the virtual MAC. The RF block(s) may be used to determine whether any of the given resources of a bandwidth portion in one of the Wi-Fi bands are unavailable. Each RF block may additionally include a portion of the MLME, where logic or pathways within the MLME are used in reporting information about bandwidth availabilities

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	to the virtual MAC. Additionally, the path of communication by which information regarding bandwidth availabilities is fed to the virtual MAC may be or include portions of the MLME SAP and/or PLME SAP. Each RF block may therefore additionally include a portion of the MLME SAP and/or the PLME SAP through which bandwidth information is directed to the virtual MAC.
10. The method of claim 1, wherein the processing interface includes a bandwidth allocator.	<i>See claim 1, above.</i> In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has provided a processing interface that includes at bandwidth allocator. The Galaxy S24 Ultra complies with the Wi-Fi Agile Multiband Specification, which “is built on the fundamental premise that the APs and STAs each have information which can aid in making the most effective selection of the spectrum band in which the STA and AP should be communicating. By exchanging this information with each other, APs and STAs enable each other to make decisions that collectively drive the network towards more efficient use of the available spectrum.” Wi-Fi Agile Multiband Specification at § 3.1. 3 Wi-Fi Agile Multiband protocol 3.1 Introduction The goal of the Wi-Fi Agile Multiband certification program is to certify features that facilitate efficient use of multiple frequency bands/channels available to APs and the STAs. The program is built on the fundamental premise that the APs and STAs each have information which can aid in making the most effective selection of the spectrum band in which the STA and AP should be communicating. By exchanging this information with each other, APs and STAs enable each other to make decisions that collectively drive the network towards more efficient use of the available spectrum. The following sections describe the information exchanged and the mechanisms by which APs and STAs exchange the desired information. Where applicable, references to existing IEEE standards are provided. In instances where there is a need to go beyond what the IEEE standards specify, the corresponding functionality, protocols and constraints are defined. Wi-Fi Agile Multiband at §3.1.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	As described with respect to element 1.a of claim 1, the processing interface of the Galaxy S24 Ultra comprises at least a portion of the SME, MLME, MAC SAP, MLME SAP, and PLME SAP in combination with certain functionality of the UMAC. When operating as an AP MLD or a non-AP MLD, the processing interface of the Galaxy S24 Ultra performs certain functions that correspond to and comprise a bandwidth allocator. For example, the processing interface, and particularly the SME, makes strategic decisions about resource allocation and/or link recommendations based on traffic demands and network conditions. Network condition information necessarily includes bandwidth availability information resulting from channel assessments directly or indirectly by way of at least trigger frames and feedback messages. As a particular example, in accordance with the Wi-Fi 7 Draft Standard, the SME's understanding of traffic priorities, queue lengths, and real-time network status enables intelligent TID-to-link mapping in the Galaxy S24 Ultra. This mapping determines which traffic (identified by TID) should be directed to which links (<i>i.e.</i>, associated bandwidth resources). The SME, in combination with the UMAC, allocates appropriate RUs/MRUs (resource units / multiple resource units) based on the data requirements of the specific traffic type mapped to a link. The SME considers factors like the amount of data to be transmitted for a particular TID and the channel bandwidth available on the chosen link. It can choose to allocate a single RU for smaller data packets or low-priority traffic, or allocate multiple RUs combined into an MRU for larger data transfers or high-priority traffic requiring more bandwidth. Accordingly, the processing interface comprises at least one bandwidth allocator. The bandwidth allocator comprises the portions of the SME and MLME, in combination with functionality of the UMAC, that perform RU/MRU allocation and TID-to-Link mapping. The bandwidth allocator may additionally include a portion of the MLME SAP by which the SME communicates with the MLME.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	An MLD supports multiple MAC functions, with synchronization across the MAC functions as needed via the MLD synchronization service (see 35.3.25 (MLD synchronization service)) and otherwise coordinated by the SME. Each affiliated STA is enumerated with a Link ID (for example, as Link 1 and Link 2 in Figure 4-33b (Reference model for an MLD for two links)) and MLME primitives are invoked through an MLME SAP. The SME maintains the authentication and association states. The Authenticator and the MAC-SAP of the AP MLD are identified by the same AP MLD MAC address. The Supplicant and the MAC-SAP of the non-AP MLD are identified by the same non-AP MLD MAC address. The SME is responsible for coordinating the MLD and each of the affiliated STAs through the MLME, and to maintain an RSNA key management entity and IEEE 802.1X Authenticator or Supplicant, for MLO. Wi-Fi 7 Draft Standard at 78.
11. The method of claim 1, wherein the first identified actual bandwidth portion is contiguous.	<i>See claim 1, above.</i> In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has performed the method of claim 1 wherein the first identified actual bandwidth portion is contiguous. In contrast to a non-contiguous bandwidth portion, a contiguous bandwidth portion may be, for example, an RU, a portion of a punctured RU, or an MRU. contiguous transmission: A transmission that uses only one frequency segment. IEEE 802.11-2020 Standard for Information Technology— Telecommunications and Information Exchange Between Systems Local and Metropolitan Area Networks—Specific Requirements (2020) at 160. noncontiguous transmission: A transmission that uses nonadjacent frequency segments.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	IEEE 802.11-2020 Standard for Information Technology—Telecommunications and Information Exchange Between Systems Local and Metropolitan Area Networks—Specific Requirements (2020) at 166. For example, the image below shows two available bandwidth portions separated by a punctured subchannel. Each available bandwidth portion is a contiguous bandwidth portion. Fig. 3 – Preamble puncturing allows wider channels even with interfering users. https://www.qualcomm.com/news/onq/2022/02/pushing-limits-wi-fi-performance-wi-fi-7.
14. The method of claim 1, wherein the processing interface is configured to, after the circuitry has been connected to the application interface and when the wireless networking device is being used, and in a manner transparent to any layer of the wireless networking device above the processing interface,	<i>See claim 1, above.</i> In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has configured the processing interface such that, after the circuitry has been connected to the application interface and when the wireless networking device is being used, the processing interface operates in a manner transparent to any layer of the wireless networking device above the processing interface. Layers between the processing interface and the application interface include, for example, a data link interface.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	As described with respect to elements 1.a and 1.b of claim 1, when operating as an AP MLD or a non-AP MLD, the processing interface of the Galaxy S24 Ultra comprises at least a portion of the SME, MLME, MAC SAP, MLME SAP, and PLME SAP in combination with at least some functionality of the UMAC. The SME, MLME, PLME, MAC SAP, and UMAC exchange information and operate to make bandwidth allocation decisions and/or recommendations in a manner transparent to all layers of the wireless networking device above the processing interface such as the data link layer. 4.2.5 Interaction with other IEEE 802® layers IEEE Std 802.11 is required to appear to higher layers [logical link control (LLC) sublayer] as a general-purpose IEEE 802 LAN. This requires that the IEEE 802.11 network handle STA mobility within the MAC sublayer. To meet reliability assumptions (that LLC makes about lower layers), it is necessary for IEEE Std 802.11 to incorporate functionality that is untraditional for MAC sublayers. IEEE 802.11-2020 Standard for Information Technology— Telecommunications and Information Exchange Between Systems Local and Metropolitan Area Networks—Specific Requirements (2020) at 219.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	An MLD supports multiple MAC functions, with synchronization across the MAC functions as needed via the MLD synchronization service (see 35.3.25 (MLD synchronization service)) and otherwise coordinated by the SME. Each affiliated STA is enumerated with a Link ID (for example, as Link 1 and Link 2 in Figure 4-33b (Reference model for an MLD for two links)) and MLME primitives are invoked through an MLME SAP. The SME maintains the authentication and association states. The Authenticator and the MAC-SAP of the AP MLD are identified by the same AP MLD MAC address. The Supplicant and the MAC-SAP of the non-AP MLD are identified by the same non-AP MLD MAC address. The SME is responsible for coordinating the MLD and each of the affiliated STAs through the MLME, and to maintain an RSNA key management entity and IEEE 802.1X Authenticator or Supplicant, for MLO. Wi-Fi 7 Draft Standard at 78. The SME maintains the authentication and association states. The same AP MLD MAC address and the same non-AP MLD MAC address are used. Thus, when the Galaxy S24 Ultra is being used, either operating as an AP MLD or a non-AP MLD, its processing interface operates in a manner transparent to any layer of the Galaxy S24 Ultra above the processing interface. Further, testing of the Galaxy S24 Ultra indicates that, when the Galaxy S24 Ultra is in use, its processing interface operates to make bandwidth allocation decisions and/or recommendations in a manner transparent to all layers of the wireless networking device above the processing interface such as the data link layer. For example, the screenshots below demonstrate that, in use, the processing interface of the Galaxy S24 Ultra operates to make, for example, bandwidth allocation decisions using each of the 2.4 GHz, 5 GHz, and 6 GHz bands.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra


USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra								
	 The screenshot displays the Wi-Fi settings for the network 'ASUSZENWIFI2'. It shows three frequency bands: 2.4 GHz, 5 GHz, and 6 GHz, all of which are 'CONNECTED'. The signal strength for each band is indicated by a green bar and a dBm value. The 2.4 GHz band shows -47 dBm, the 5 GHz band shows -66 dBm, and the 6 GHz band shows -77 dBm. A red box highlights the 2.4 GHz, 5 GHz, and 6 GHz sections. Below these, there are two more sections for 'Access Point' settings, each showing a 2.4 GHz band with signal strength values of -69 dBm and -86 dBm, and a 5 GHz band with a signal strength of -79 dBm. <table border="1"><thead><tr><th>Frequency Band</th><th>Signal Strength (dBm)</th></tr></thead><tbody><tr><td>2.4 GHz</td><td>-47</td></tr><tr><td>5 GHz</td><td>-66</td></tr><tr><td>6 GHz</td><td>-77</td></tr></tbody></table>	Frequency Band	Signal Strength (dBm)	2.4 GHz	-47	5 GHz	-66	6 GHz	-77
Frequency Band	Signal Strength (dBm)								
2.4 GHz	-47								
5 GHz	-66								
6 GHz	-77								

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	WiFiman application screenshot taken on Galaxy S24 Ultra demonstrating connection with local access point (emphasis added).

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung’s Galaxy S24 Ultra


USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	 The screenshot displays the 'Connection information' screen for a Samsung device. At the top, the status bar shows the time as 5:58, signal strength, and a 99% battery level. The screen title is 'Connection information' with a back arrow. Below the title are three tabs: 'Link status' (selected), 'L2 status', and 'L3 status'. The main content area shows the network name 'ASUSZENWIFI2' and its MAC address '06:28:aa:6c:c2:40 [MLD]'. Under the 'RSSI' section, it indicates '[2.4GHz] Not in use', '[6GHz] Not in use', and '[5GHz] -75 dBm'. A line graph below this shows signal strength across frequencies, with a peak in the 5GHz band. The 'Channel utilization' section shows '[2.4GHz] Not in use' and '[5GHz] 9% (23/255)'. Another line graph shows utilization across frequencies, with a significant peak in the 5GHz band. The 'Link speed' section shows '[2.4GHz] Tx=68 Mbps / Rx=17 Mbps', '[6GHz] Tx=0 Mbps / Rx=0 Mbps', and '[5GHz] Tx=432 Mbps / Rx=288 Mbps'. A third line graph shows link speed across frequencies, with a peak in the 5GHz band. The bottom of the screen shows the standard Android navigation bar.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra


USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	WiFiman application screenshot taken on Galaxy S24 Ultra demonstrating connection with local access point. As shown above, the processing interface's utilization of the available channels changes over time. Despite this, as shown below, in use, the Galaxy S24 Ultra is associated with only a single IP address and a single MAC address used to route Internet traffic to the Galaxy S24 Ultra. 

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	Internet browser screenshot indicating connection between Sagemcom Internet Gateway router and Galaxy S24 Ultra (emphasis added).
[14.a] (a) identify at least one second portion of the first actual bandwidth of the first wireless transceiver, the identified second bandwidth portion comprising a set of given resources, the first and second identified actual bandwidth portions not being contiguous with each other,	In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has configured the processing interface to identify at least one second portion of the first actual bandwidth of the first wireless transceiver, the identified second bandwidth portion comprising a set of given resources, the first and second identified actual bandwidth portions not being contiguous with each other. As described with respect to element 1.i of claim 1, above, the processing interface may identify at least one first portion of the first actual bandwidth of the first wireless transceiver, the identified at least one first portion comprising a set of given resources. The processing interface may do so using, for example, information regarding bandwidth availabilities that is communicated to the virtual MAC and a puncturing pattern. <i>See</i> element 1.i of claim 1, above. Using the same mechanism, the processing interface may identify at least one second portion of the first actual bandwidth of the first wireless transceiver. Additionally, the first and second actual bandwidth portions may be non-contiguous portions. Non-contiguous bandwidth portions are nonadjacent. noncontiguous transmission: A transmission that uses nonadjacent frequency segments. IEEE 802.11-2020 Standard for Information Technology— Telecommunications and Information Exchange Between Systems Local and Metropolitan Area Networks—Specific Requirements (2020) at 166.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra


USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	For example, the image below shows two available bandwidth portions separated by a punctured subchannel. The two available bandwidth portions are not adjacent, due to the interference, and therefore are not contiguous.  https://www.qualcomm.com/news/onq/2022/02/pushing-limits-wi-fi-performance-wi-fi-7. The Galaxy S24 Ultra, with Wi-Fi 7 enabled, is configured for preamble puncturing in all frequency bands and associated transceivers. Preamble puncturing allows WNDs, such as the Galaxy S24 Ultra, to recognize and exclude unavailable subchannels from a transmission. These channel(s) may be bounded in some cases by two portions of the first identified bandwidth portion, thus resulting in at least two non-contiguous portions. <i>See</i> elements 1.f and 1.j of claim 1, above. The Wi-Fi 7 Draft Standard describes the U-SIG field that carries the information necessary to interpret EHT PPDU, and that shows a puncturing pattern wherein RUs and MRUs are punctured. The puncturing pattern indicates what sub-portions of RUs or MRUs are not to be used for transmission or reception purposes. Unavailable subchannels may be indicated, for example, in a Disabled Subchannel Bitmap, where such subchannels may separate two non-contiguous portions of the first identified bandwidth portion of the first wireless transceiver.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	During use, the processing interface evaluates the puncturing pattern to determine what portions of RUs or MRUs are unavailable (that may separate two available portions), and therefore not to be used for transmission purposes. Additionally, an MRU by itself, when not punctured, involves the use of at least two different non-contiguous bandwidth portions.
[14.b] (b) evaluate whether any of the given resources of the second identified actual bandwidth portion are unavailable for communication, and	In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has configured the processing interface to evaluate whether any of the given resources of the second identified actual bandwidth portion are unavailable for communication. As described with respect to element 1.j of claim 1, above, the processing interface may evaluate whether any of the given resources of the first identified actual bandwidth portion are unavailable for communication. The processing interface may do so using, for example, information regarding bandwidth availabilities that is communicated to the virtual MAC and a puncturing pattern. <i>See</i> element 1.j of claim 1, above. Using the same mechanism, the processing interface may evaluate whether any of the given resources of the second identified actual bandwidth portion are unavailable for communication.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
[14.c] (c) use the first wireless transceiver to transmit the first data stream to the recipient, without requiring disassociation of the recipient from either or both of the first and second actual MAC and PHY interfaces, using a subset of frequencies corresponding to only the given resources of the first and second bandwidth portions that are not unavailable for communication to thereby at least partially satisfy the first wireless bandwidth requirement of the first application.	In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has configured the processing interface to use the first wireless transceiver to transmit the first data stream to the recipient, without requiring disassociation of the recipient from either or both of the first and second actual MAC and PHY interfaces, using a subset of frequencies corresponding to only the given resources of the first and second bandwidth portions that are not unavailable for communication to thereby at least partially satisfy the first wireless bandwidth requirement of the first application. When the Galaxy S24 Ultra operates as an AP MLD or a non-AP MLD, its processing interface instructs the actual MAC and actual PHY to transmit data packets using primitives. These instructions specify the chosen link and the allocated RU/MRU configuration. Based on the instructions, the actual PHY layer segments data packets into units, modulates the data units using appropriate techniques for transmission over the designated link, and transmits the modulated data units using the allocated radio frequencies on the chosen transceiver. For example, the processing interface may use certain vectors, including TXVECTOR, RXVECTOR, PHYCONFIG_VECTOR, and TRIG_VECTOR to instruct the PHY. 36.2 EHT PHY service interface 36.2.1 Introduction The EHT PHY provides an interface to the EHT MAC through an extension of the generic PHY service interface defined in 8.3.4 (Basic service and options). The interface includes TXVECTOR, RXVECTOR, PHYCONFIG_VECTOR, and TRIGVECTOR. The EHT MAC uses the TXVECTOR to supply the EHT PHY with per-PPDU transmit parameters. The EHT PHY uses the RXVECTOR to inform the EHT MAC of the received PPDU parameters. The EHT MAC uses the PHYCONFIG_VECTOR to configure the EHT PHY for operation that is independent of PPDU transmission or reception. The EHT MAC uses the TRIGVECTOR to configure the EHT PHY to receive EHT TB PPDU's over each assigned RU or MRU.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	Wi-Fi 7 Draft Standard at 708, 709-23 (listing TXVECTOR and RXVECTOR parameters). In all options, in order to transmit data, the MAC generates a PHY-TXSTART.request primitive, which causes the PHY entity to respond with a PHY-TXSTART.confirm primitive and enter the transmit state. Further, the PHY is set to operate at the appropriate frequency through station management via the PLME, as specified in 36.4 (EHT PLME). Other transmit parameters, such as EHT-MCS, coding types, and transmit power, are set via the PHY-SAP using the PHY-TXSTART.request primitive (containing TXVECTOR), as described in 36.2.2 (TXVECTOR and RXVECTOR parameters). After transmitting a PPDU that carries a Trigger frame, the MAC sublayer issues a PHY-TRIGGER.request with a TRIGVECTOR parameter that provides the PHY entity with the information needed to demodulate the expected EHT TB PPDU response. The remainder of the subclause applies to the first two paths. Wi-Fi 7 Draft Standard at 940. The processing interface of the Galaxy S24 Ultra evaluates channel information, such as a puncturing pattern, to determine what portions of channels are unavailable for transmission or reception purposes. Additionally, the Galaxy S24 Ultra, when operating as an AP MLD or a non-AP MLD, enables the use of TID-to-link mapping in accordance with the Wi-Fi 7 Draft Standard. For example, when operating as an AP MLD, the SME and UMAC (through a Resource Allocation Manager) may determine TID-to-link mapping and assign RUs/MRUs based on traffic needs and available resources on each link. Likewise, when operating as a non-AP MLD, the SME and UMAC may monitor and evaluate traffic needs and available resources to provide recommendation information to an AP MLD device assigning RUs/MRUs. Further, when operating as a non-AP MLD, the Galaxy S24 Ultra follows the TID-to-link mapping determined by the AP. Thus, the system architecture solves limitations of multi-band to enable MLO in IEEE 802.11be to be based on the processing interface's unique understanding of traffic priorities, queue lengths, and real-time network status enabling intelligent TID-to-link mapping. This mapping determines which traffic (<i>e.g.</i>, identified by TID) should be directed to which links (<i>i.e.</i>, associated bandwidth resources).

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	As a particular example, when operating as an AP MLD, the SME and UMAC allocate appropriate RU(s)/MRU(s) based on the data requirements of the specific traffic type mapped to a link. The UMAC considers factors like the amount of data to be transmitted for a particular TID and the channel bandwidth available on the chosen link. It can choose to allocate a single RU for smaller data packets or low-priority traffic, or allocate multiple RUs combined into an MRU for larger data transfers or high-priority traffic requiring more bandwidth. Assigning RUs or MRUs is an integral part of TID-to-link mapping. Likewise, when operating as a non-AP MLD, the SME and UMAC direct packets to links based on the TID-to-link mapping identified by an AP. Multiple RUs can be combined for simultaneous transmission to satisfy a bandwidth requirement. 36.3.2.2 Subcarriers and resource allocation for multiple RUs 36.3.2.2.1 General The EHT PHY supports the use of MRU in an EHT PPDU. An MRU consists of selected combinations of multiple RUs of 26-tone RU, 52-tone RU, 106-tone RU, 242-tone RU, 484-tone RU, 996-tone RU, and 2×996-tone RU. The tone indices of the various RUs for different EHT PPDU bandwidths are defined in 36.3.2.1 (Subcarriers and resource allocation in EHT PPDU). RUs that are the same size as or larger than 242-tone RUs are defined as large size RUs and RUs that are smaller than 242-tone RUs are defined as small size RUs. Small size RUs can only be combined with small size RUs to form small size MRUs. The supported small size MRUs are defined in 36.3.2.2.2 (Small size MRUs). Large size RUs can only be combined with large size RUs to form large size MRUs. The supported large size MRUs are defined in 36.3.2.2.3 (Large size MRUs).

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	Wi-Fi 7 Draft Standard at 740. The Galaxy S24 Ultra is configured for multi-RU operation, thus allowing for the aggregation of multiple bandwidth portions for simultaneous transmission or reception. Wi-Fi CERTIFIED 7™ (continued) - MCS 8-9 Rx - MCS 8-9 Tx - MCS 10-11 Rx - MCS 10-11 Tx - MCS 12-13 Rx - MCS 12-13 Tx - Multi-link reconfiguration – AP removal - Multi-link reconfiguration – AP restart Multi-RU - Operating mode indication - Operating mode indication for 320 MHz - Static puncturing - STR (Simultaneous Transmit and Receive) - SU-MIMO - Triggered uplink access optimization - UL MU-MIMO - UL OFDMA Wi-Fi CERTIFIED Certificate for Qualcomm FastConnect 7800 Mobile Connectivity System, Cert. I.D. WFA127693 (2024) (emphasis added). As described with respect to element 1.a of claim 1, the Galaxy S24 Ultra's processing interface is provided by the Qualcomm Snapdragon 8 Gen 3 System on a Chip processor that

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	includes the FastConnect 7800 connectivity system contained within the Galaxy S24 Ultra. The Qualcomm FastConnect 7800 connectivity system is compliant with Wi-Fi 7 standards. Leading Wi-Fi 7, premium Wi-Fi 6/6E, and advanced Bluetooth audio come together in this powerful and versatile connectivity system to unlock extreme performance for mobile, compute, and XR experiences. The Qualcomm® FastConnect™ 7800 Mobile Connectivity System is an advanced 14nm Wi-Fi and Bluetooth® Connectivity system delivering ultra-high speeds (up to 5.8 Gbps*), sustained low latency (2 ms), and premium Bluetooth audio. While maintaining compliance with the latest Wi-Fi 6/6E and Wi-Fi 7 standards, FastConnect 7800 is packed with sophisticated innovation that goes beyond standard benchmarks. High Band Simultaneous Multi-Link Wi-Fi technology uniquely harnesses the potential of 5 and 6GHz bands for multiple links of high band performance for throughput hungry and latency sensitive applications, eliminating dependence on comparatively narrow and congested 2.4GHz band. https://www.qualcomm.com/products/technology/wi-fi/fastconnect/fastconnect-7800. As demonstrated below, the Qualcomm FastConnect 7800 connectivity system allows the Galaxy S24 Ultra to aggregate resources within, for example, the 5 GHz band.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra


USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	In regions and environments where 6GHz is not available  FastConnect 7800 can harness up to 240MHz of the global 5GHz band *Speed claims refer to maximum physical layer (PHY) rate https://www.qualcomm.com/products/technology/wi-fi/fastconnect/fastconnect-7800. This evidences that devices, such as the Galaxy S24 Ultra, for example, can aggregate a 160 MHz channel in the 5 GHz band with an 80 MHz channel in the 5 GHz band. Additionally, the processing interface may transmit a data stream using the first wireless transceiver without requiring disassociation of the recipient from any of the first and second actual MAC and PHY interfaces. As described with respect to element 1.h, MLO allows a non-AP MLD and an AP MLD to establish multiple links between their corresponding STAs. Data may be transmitted or received on one of the established links without requiring disassociation of the other established links.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	35.3.16 ML channel access 35.3.16.1 General A STA that is affiliated with an MLD shall contend for the WM on its link independently from the other STA(s) affiliated with the same MLD, unless explicitly stated otherwise in the subclauses below. Wi-Fi 7 Draft Standard at 598.
15. The method of claim 14, wherein the second identified actual bandwidth portion is contiguous.	<i>See claim 14, above.</i> In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has performed the method of claim 14 wherein the second identified actual bandwidth portion is contiguous. In contrast to a non-contiguous bandwidth portion, a contiguous bandwidth portion may be, for example, an RU, a portion of a punctured RU, or an MRU. contiguous transmission: A transmission that uses only one frequency segment. IEEE 802.11-2020 Standard for Information Technology— Telecommunications and Information Exchange Between Systems Local and Metropolitan Area Networks—Specific Requirements (2020) at 160. noncontiguous transmission: A transmission that uses nonadjacent frequency segments. IEEE 802.11-2020 Standard for Information Technology— Telecommunications and Information Exchange Between Systems Local and Metropolitan Area Networks—Specific Requirements (2020) at 166. For example, the image below shows two available bandwidth portions separated by a punctured subchannel. Each available bandwidth portion is a contiguous bandwidth portion.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra


USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	 Fig. 3 – Preamble puncturing allows wider channels even with interfering users. https://www.qualcomm.com/news/onq/2022/02/pushing-limits-wi-fi-performance-wi-fi-7.
16. The method of claim 14, wherein the processing interface is configured to, after the circuitry has been connected to the application interface and when the wireless networking device is being used, and in a manner transparent to any layer of the wireless networking device above the processing interface,	<i>See claim 14, above.</i> In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has configured the processing interface such that, after the circuitry has been connected to the application interface and when the wireless networking device is being used, the processing interface operates in a manner transparent to any layer of the wireless networking device above the processing interface. <i>See claim 14, above.</i>
[16.a] (a) if all of the given resources of the first identified bandwidth portions are unavailable, identify at least one third portion of the first actual bandwidth of the first wireless transceiver, the third identified bandwidth portion comprising a set of given resources,	In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has configured the processing interface to, if all of the given resources of the first identified bandwidth portions are unavailable, identify at least one third portion of the first actual bandwidth of the first wireless transceiver, the third identified bandwidth portion comprising a set of given resources. As described with respect to element 1.j of claim 1, above, the processing interface may evaluate whether any of the given resources of the first identified actual bandwidth

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	portion are unavailable for communication. The processing interface may do so using, for example, information regarding bandwidth availabilities that is communicated to the virtual MAC and a puncturing pattern. <i>See</i> element 1.j of claim 1, above. Using the same mechanism, the processing interface may determine that all of the given resources of the first identified bandwidth portions are unavailable. As described with respect to element 1.i of claim 1, above, the processing interface may identify at least one first portion of the first actual bandwidth of the first wireless transceiver, the identified at least one first portion comprising a set of given resources. The processing interface may do so using, for example, information regarding bandwidth availabilities that is communicated to the virtual MAC and a puncturing pattern. <i>See</i> element 1.i of claim 1, above. Using the same mechanism, the processing interface may identify at least one third portion of the first actual bandwidth of the first wireless transceiver.
[16.b] (b) evaluate whether any of the given resources of the third identified bandwidth portion are unavailable for communication, and	In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has configured the processing interface to evaluate whether any of the given resources of the third identified bandwidth portion are unavailable for communication. As described with respect to element 1.j of claim 1, above, the processing interface may evaluate whether any of the given resources of the first identified actual bandwidth portion are unavailable for communication. The processing interface may do so using, for example, information regarding bandwidth availabilities that is communicated to the virtual MAC and a puncturing pattern. <i>See</i> element 1.j of claim 1, above. Using the same mechanism, the processing interface may evaluate whether any of the given resources of the third identified bandwidth portion are unavailable for communication.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
[16.c] (c) use the first wireless transceiver to transmit the first data stream to the recipient, without requiring disassociation of the recipient from either or both of the first and second actual MAC and PHY interfaces, using a subset of frequencies corresponding to only the given resources of the third identified bandwidth portion that are not unavailable for communication to thereby at least partially satisfy the first wireless bandwidth requirement of the first application.	In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has configured the processing interface to use the first wireless transceiver to transmit the first data stream to the recipient, without requiring disassociation of the recipient from either or both of the first and second actual MAC and PHY interfaces, using a subset of frequencies corresponding to only the given resources of the third identified bandwidth portion that are not unavailable for communication to thereby at least partially satisfy the first wireless bandwidth requirement of the first application When the Galaxy S24 Ultra operates as an AP MLD or a non-AP MLD, its processing interface instructs the actual MAC and actual PHY to transmit data packets using primitives. These instructions specify the chosen link and the allocated RU/MRU configuration. Based on the instructions, the actual PHY layer segments data packets into units, modulates the data units using appropriate techniques for transmission over the designated link, and transmits the modulated data units using the allocated radio frequencies on the chosen transceiver. For example, the processing interface may use certain vectors, including TXVECTOR, RXVECTOR, PHYCONFIG_VECTOR, and TRIG_VECTOR to instruct the PHY. 36.2 EHT PHY service interface 36.2.1 Introduction The EHT PHY provides an interface to the EHT MAC through an extension of the generic PHY service interface defined in 8.3.4 (Basic service and options). The interface includes TXVECTOR, RXVECTOR, PHYCONFIG_VECTOR, and TRIGVECTOR. The EHT MAC uses the TXVECTOR to supply the EHT PHY with per-PPDU transmit parameters. The EHT PHY uses the RXVECTOR to inform the EHT MAC of the received PPDU parameters. The EHT MAC uses the PHYCONFIG_VECTOR to configure the EHT PHY for operation that is independent of PPDU transmission or reception. The EHT MAC uses the TRIGVECTOR to configure the EHT PHY to receive EHT TB PPDU's over each assigned RU or MRU.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	Wi-Fi 7 Draft Standard at 708, 709-23 (listing TXVECTOR and RXVECTOR parameters). In all options, in order to transmit data, the MAC generates a PHY-TXSTART.request primitive, which causes the PHY entity to respond with a PHY-TXSTART.confirm primitive and enter the transmit state. Further, the PHY is set to operate at the appropriate frequency through station management via the PLME, as specified in 36.4 (EHT PLME). Other transmit parameters, such as EHT-MCS, coding types, and transmit power, are set via the PHY-SAP using the PHY-TXSTART.request primitive (containing TXVECTOR), as described in 36.2.2 (TXVECTOR and RXVECTOR parameters). After transmitting a PPDU that carries a Trigger frame, the MAC sublayer issues a PHY-TRIGGER.request with a TRIGVECTOR parameter that provides the PHY entity with the information needed to demodulate the expected EHT TB PPDU response. The remainder of the subclause applies to the first two paths. Wi-Fi 7 Draft Standard at 940. The processing interface of the Galaxy S24 Ultra evaluates channel information, such as a puncturing pattern, to determine what portions of channels are unavailable for transmission or reception purposes. Additionally, the Galaxy S24 Ultra, when operating as an AP MLD or a non-AP MLD, enables the use of TID-to-link mapping in accordance with the Wi-Fi 7 Draft Standard. For example, when operating as an AP MLD, the SME and UMAC (through a Resource Allocation Manager) may determine TID-to-link mapping and assign RUs/MRUs based on traffic needs and available resources on each link. Likewise, when operating as a non-AP MLD, the SME and UMAC may monitor and evaluate traffic needs and available resources to provide recommendation information to an AP MLD device assigning RUs/MRUs. Further, when operating as a non-AP MLD, the Galaxy S24 Ultra follows the TID-to-link mapping determined by the AP. Thus, the system architecture solves limitations of multi-band to enable MLO in IEEE 802.11be to be based on the processing interface's unique understanding of traffic priorities, queue lengths, and real-time network status enabling intelligent TID-to-link mapping. This mapping determines which traffic (<i>e.g.</i>, identified by TID) should be directed to which links (<i>i.e.</i>, associated bandwidth resources).

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	As a particular example, when operating as an AP MLD, the SME and UMAC allocate appropriate RU(s)/MRU(s) based on the data requirements of the specific traffic type mapped to a link. The UMAC considers factors like the amount of data to be transmitted for a particular TID and the channel bandwidth available on the chosen link. It can choose to allocate a single RU for smaller data packets or low-priority traffic, or allocate multiple RUs combined into an MRU for larger data transfers or high-priority traffic requiring more bandwidth. Assigning RUs or MRUs is an integral part of TID-to-link mapping. Likewise, when operating as a non-AP MLD, the SME and UMAC direct packets to links based on the TID-to-link mapping identified by an AP. Additionally, the processing interface may transmit a data stream using the first wireless transceiver without requiring disassociation of the recipient from any of the first and second actual MAC and PHY interfaces. As described with respect to element 1.h, MLO allows a non-AP MLD and an AP MLD to establish multiple links between their corresponding STAs. Data may be transmitted or received on one of the established links without requiring disassociation of the other established links. 35.3.16 ML channel access 35.3.16.1 General A STA that is affiliated with an MLD shall contend for the WM on its link independently from the other STA(s) affiliated with the same MLD, unless explicitly stated otherwise in the subclauses below. Wi-Fi 7 Draft Standard at 598.
17. The method of claim 14, wherein the processing interface is configured to, after the circuitry has been connected to the application	<i>See claim 14, above.</i> In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has configured the processing interface such that, after the circuitry has been connected to the application

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
interface and when the wireless networking device is being used, and in a manner transparent to any layer of the wireless networking device above the processing interface,	interface and when the wireless networking device is being used, the processing interface operates in a manner transparent to any layer of the wireless networking device above the processing interface. <i>See</i> claim 14, above.
[17.a] (a) if all of the given resources of the second actual bandwidth portion are unavailable, identify at least one fourth portion of the actual bandwidth of the first wireless transceiver, the fourth identified bandwidth portion comprising a set of given resources,	In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has configured the processing interface to, if all of the given resources of the second actual bandwidth portion are unavailable, identify at least one fourth portion of the actual bandwidth of the first wireless transceiver, the fourth identified bandwidth portion comprising a set of given resources. As described with respect to element 1.j of claim 1, above, the processing interface may evaluate whether any of the given resources of the first identified actual bandwidth portion are unavailable for communication. The processing interface may do so using, for example, information regarding bandwidth availabilities that is communicated to the virtual MAC and a puncturing pattern. <i>See</i> element 1.j of claim 1, above. Using the same mechanism, the processing interface may determine that all of the given resources of the second actual bandwidth portion are unavailable. As described with respect to element 1.i of claim 1, above, the processing interface may identify at least one first portion of the first actual bandwidth of the first wireless transceiver, the identified at least one first portion comprising a set of given resources. The processing interface may do so using, for example, information regarding bandwidth availabilities that is communicated to the virtual MAC and a puncturing pattern. <i>See</i> element 1.i of claim 1, above. Using the same mechanism, the processing interface may identify at least one fourth portion of the actual bandwidth of the first wireless transceiver.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
[17.b] (b) evaluate whether any of the given resources of the fourth identified bandwidth portion are unavailable for communication, and	In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has configured the processing interface to evaluate whether any of the given resources of the fourth identified bandwidth portion are unavailable for communication. As described with respect to element 1.j of claim 1, above, the processing interface may evaluate whether any of the given resources of the first identified actual bandwidth portion are unavailable for communication. The processing interface may do so using, for example, information regarding bandwidth availabilities that is communicated to the virtual MAC and a puncturing pattern. <i>See</i> element 1.j of claim 1, above. Using the same mechanism, the processing interface may evaluate whether any of the given resources of the fourth identified bandwidth portion are unavailable for communication.
[17.c] (c) use the first wireless transceiver to transmit the first data stream to the recipient, without requiring disassociation of the recipient from either or both of the first and second actual MAC and PHY interfaces, using a subset of frequencies corresponding to only the given resources of the fourth identified bandwidth portion that are not unavailable for communication to thereby at least partially satisfy the first wireless bandwidth requirement of the first application.	In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has configured the processing interface to use the first wireless transceiver to transmit the first data stream to the recipient, without requiring disassociation of the recipient from either or both of the first and second actual MAC and PHY interfaces, using a subset of frequencies corresponding to only the given resources of the fourth identified bandwidth portion that are not unavailable for communication to thereby at least partially satisfy the first wireless bandwidth requirement of the first application. When the Galaxy S24 Ultra operates as an AP MLD or a non-AP MLD, its processing interface instructs the actual MAC and actual PHY to transmit data packets using primitives. These instructions specify the chosen link and the allocated RU/MRU configuration. Based on the instructions, the actual PHY layer segments data packets into units, modulates the data units using appropriate techniques for transmission over the designated link, and transmits the modulated data units using the allocated radio frequencies on the chosen transceiver. For example, the processing interface may use certain vectors, including TXVECTOR, RXVECTOR, PHYCONFIG_VECTOR, and TRIG_VECTOR to instruct the PHY.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	36.2 EHT PHY service interface 36.2.1 Introduction The EHT PHY provides an interface to the EHT MAC through an extension of the generic PHY service interface defined in 8.3.4 (Basic service and options). The interface includes TXVECTOR, RXVECTOR, PHYCONFIG_VECTOR, and TRIGVECTOR. The EHT MAC uses the TXVECTOR to supply the EHT PHY with per-PPDU transmit parameters. The EHT PHY uses the RXVECTOR to inform the EHT MAC of the received PPDU parameters. The EHT MAC uses the PHYCONFIG_VECTOR to configure the EHT PHY for operation that is independent of PPDU transmission or reception. The EHT MAC uses the TRIGVECTOR to configure the EHT PHY to receive EHT TB PPDU's over each assigned RU or MRU. Wi-Fi 7 Draft Standard at 708, 709-23 (listing TXVECTOR and RXVECTOR parameters). In all options, in order to transmit data, the MAC generates a PHY-TXSTART.request primitive, which causes the PHY entity to respond with a PHY-TXSTART.confirm primitive and enter the transmit state. Further, the PHY is set to operate at the appropriate frequency through station management via the PLME, as specified in 36.4 (EHT PLME). Other transmit parameters, such as EHT-MCS, coding types, and transmit power, are set via the PHY-SAP using the PHY-TXSTART.request primitive (containing TXVECTOR), as described in 36.2.2 (TXVECTOR and RXVECTOR parameters). After transmitting a PPDU that carries a Trigger frame, the MAC sublayer issues a PHY-TRIGGER.request with a TRIGVECTOR parameter that provides the PHY entity with the information needed to demodulate the expected EHT TB PPDU response. The remainder of the subclause applies to the first two paths. Wi-Fi 7 Draft Standard at 940. The processing interface of the Galaxy S24 Ultra evaluates channel information, such as a puncturing pattern, to determine what portions of channels are unavailable for transmission or reception purposes. Additionally, the Galaxy S24 Ultra, when operating as an AP MLD or a non-AP MLD, enables the use of TID-to-link mapping in accordance with the Wi-Fi 7 Draft Standard. For example, when operating as an AP MLD, the SME and UMAC

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	(through a Resource Allocation Manager) may determine TID-to-link mapping and assign RUs/MRUs based on traffic needs and available resources on each link. Likewise, when operating as a non-AP MLD, the SME and UMAC may monitor and evaluate traffic needs and available resources to provide recommendation information to an AP MLD device assigning RUs/MRUs. Further, when operating as a non-AP MLD, the Galaxy S24 Ultra follows the TID-to-link mapping determined by the AP. Thus, the system architecture solves limitations of multi-band to enable MLO in IEEE 802.11be to be based on the processing interface's unique understanding of traffic priorities, queue lengths, and real-time network status enabling intelligent TID-to-link mapping. This mapping determines which traffic (<i>e.g.</i>, identified by TID) should be directed to which links (<i>i.e.</i>, associated bandwidth resources). As a particular example, when operating as an AP MLD, the SME and UMAC allocate appropriate RU(s)/MRU(s) based on the data requirements of the specific traffic type mapped to a link. The UMAC considers factors like the amount of data to be transmitted for a particular TID and the channel bandwidth available on the chosen link. It can choose to allocate a single RU for smaller data packets or low-priority traffic, or allocate multiple RUs combined into an MRU for larger data transfers or high-priority traffic requiring more bandwidth. Assigning RUs or MRUs is an integral part of TID-to-link mapping. Likewise, when operating as a non-AP MLD, the SME and UMAC direct packets to links based on the TID-to-link mapping identified by an AP. Additionally, the processing interface may transmit a data stream using the first wireless transceiver without requiring disassociation of the recipient from any of the first and second actual MAC and PHY interfaces. As described with respect to element 1.h, MLO allows a non-AP MLD and an AP MLD to establish multiple links between their corresponding STAs. Data may be transmitted or received on one of the established links without requiring disassociation of the other established links.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	35.3.16 ML channel access 35.3.16.1 General A STA that is affiliated with an MLD shall contend for the WM on its link independently from the other STA(s) affiliated with the same MLD, unless explicitly stated otherwise in the subclauses below. Wi-Fi 7 Draft Standard at 598.
18. The method of claim 1, wherein the processing interface is configured to, after the circuitry has been connected to the application interface and when the wireless networking device is being used, and in a manner transparent to any layer of the wireless networking device above the processing interface,	<i>See claim 1, above.</i> In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has configured the processing interface such that, after the circuitry has been connected to the application interface and when the wireless networking device is being used, the processing interface operates in a manner transparent to any layer of the wireless networking device above the processing interface. <i>See</i> element 1.g of claim 1, above.
[18.a] (a) identify at least one first portion of the second actual bandwidth of the second wireless transceiver, the first identified portion of the second wireless transceiver comprising a set of given resources,	In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has configured the processing interface to identify at least one first portion of the second actual bandwidth of the second wireless transceiver, the first identified bandwidth portion of the second wireless transceiver comprising a set of given resources. As described with respect to element 1.i of claim 1, above, the processing interface may identify at least one first portion of the first actual bandwidth of the first wireless transceiver, the identified at least one first portion comprising a set of given resources. The processing interface may do so using, for example, information regarding bandwidth availabilities that is communicated to the virtual MAC and a puncturing pattern. <i>See</i> element 1.i of claim 1, above. Using the same mechanism, the processing interface may identify at least one first portion of the second actual bandwidth of the second wireless transceiver.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
[18.b] (b) evaluate whether any of the given resources of the first identified actual bandwidth portion of the second wireless transceiver are unavailable for communication, and	In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has configured the processing interface to evaluate whether any of the given resources of the first identified actual bandwidth portion of the second wireless transceiver are unavailable for communication. As described with respect to element 1.j of claim 1, above, the processing interface may evaluate whether any of the given resources of the first identified actual bandwidth portion are unavailable for communication. The processing interface may do so using, for example, information regarding bandwidth availabilities that is communicated to the virtual MAC and a puncturing pattern. <i>See</i> element 1.j of claim 1, above. Using the same mechanism, the processing interface may evaluate whether any of the given resources of the first identified actual bandwidth portion of the second wireless transceiver are unavailable for communication.
[18.c] (c) if none of the given resources of the first identified bandwidth portion of the first wireless transceiver are available for communication and if the first identified bandwidth portion of the second wireless transceiver is available for communication, use the second wireless transceiver to transmit the first data stream to the recipient, without requiring disassociation of the recipient from either or both of the first and second actual MAC and PHY interfaces, using a subset of frequencies corresponding only to the given	In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has configured the processing interface to, if none of the given resources of the first identified bandwidth portion of the first wireless transceiver are available for communication and if the first identified bandwidth portion of the second wireless transceiver is available for communication, use the second wireless transceiver to transmit the first data stream to the recipient, without requiring disassociation of the recipient from either or both of the first and second actual MAC and PHY interfaces, using a subset of frequencies corresponding only to the given resources of the first identified actual bandwidth portion of the second wireless transceiver that are not unavailable for communication to thereby at least partially satisfy the first wireless bandwidth requirement of the first application. As described with respect to element 1.j of claim 1, above, the processing interface may evaluate whether any of the given resources of the first identified actual bandwidth portion are unavailable for communication. The processing interface may do so using, for example, information regarding bandwidth availabilities that is communicated to the virtual MAC and a puncturing pattern. <i>See</i> element 1.j of claim 1, above. Using the same

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
resources of the first identified actual bandwidth portion of the second wireless transceiver that are not unavailable for communication to thereby at least partially satisfy the first wireless bandwidth requirement of the first application; and	mechanism, the processing interface may determine that none of the given resources of the first identified bandwidth portion of the first wireless transceiver are available and that the first identified bandwidth portion of the second wireless transceiver is available. When the Galaxy S24 Ultra operates as an AP MLD or a non-AP MLD, its processing interface instructs the actual MAC and actual PHY to transmit data packets using primitives. These instructions specify the chosen link and the allocated RU/MRU configuration. Based on the instructions, the actual PHY layer segments data packets into units, modulates the data units using appropriate techniques for transmission over the designated link, and transmits the modulated data units using the allocated radio frequencies on the chosen transceiver. For example, the processing interface may use certain vectors, including TXVECTOR, RXVECTOR, PHYCONFIG_VECTOR, and TRIG_VECTOR to instruct the PHY. 36.2 EHT PHY service interface 36.2.1 Introduction The EHT PHY provides an interface to the EHT MAC through an extension of the generic PHY service interface defined in 8.3.4 (Basic service and options). The interface includes TXVECTOR, RXVECTOR, PHYCONFIG_VECTOR, and TRIGVECTOR. The EHT MAC uses the TXVECTOR to supply the EHT PHY with per-PPDU transmit parameters. The EHT PHY uses the RXVECTOR to inform the EHT MAC of the received PPDU parameters. The EHT MAC uses the PHYCONFIG_VECTOR to configure the EHT PHY for operation that is independent of PPDU transmission or reception. The EHT MAC uses the TRIGVECTOR to configure the EHT PHY to receive EHT TB PPDU's over each assigned RU or MRU. Wi-Fi 7 Draft Standard at 708, 709-23 (listing TXVECTOR and RXVECTOR parameters).

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	In all options, in order to transmit data, the MAC generates a PHY-TXSTART.request primitive, which causes the PHY entity to respond with a PHY-TXSTART.confirm primitive and enter the transmit state. Further, the PHY is set to operate at the appropriate frequency through station management via the PLME, as specified in 36.4 (EHT PLME). Other transmit parameters, such as EHT-MCS, coding types, and transmit power, are set via the PHY-SAP using the PHY-TXSTART.request primitive (containing TXVECTOR), as described in 36.2.2 (TXVECTOR and RXVECTOR parameters). After transmitting a PPDU that carries a Trigger frame, the MAC sublayer issues a PHY-TRIGGER.request with a TRIGVECTOR parameter that provides the PHY entity with the information needed to demodulate the expected EHT TB PPDU response. The remainder of the subclause applies to the first two paths. Wi-Fi 7 Draft Standard at 940. The processing interface of the Galaxy S24 Ultra evaluates channel information, such as a puncturing pattern, to determine what portions of channels are unavailable for transmission or reception purposes. Additionally, the Galaxy S24 Ultra, when operating as an AP MLD or a non-AP MLD, enables the use of TID-to-link mapping in accordance with the Wi-Fi 7 Draft Standard. For example, when operating as an AP MLD, the SME and UMAC (through a Resource Allocation Manager) may determine TID-to-link mapping and assign RUs/MRUs based on traffic needs and available resources on each link. Likewise, when operating as a non-AP MLD, the SME and UMAC may monitor and evaluate traffic needs and available resources to provide recommendation information to an AP MLD device assigning RUs/MRUs. Further, when operating as a non-AP MLD, the Galaxy S24 Ultra follows the TID-to-link mapping determined by the AP. Thus, the system architecture solves limitations of multi-band to enable MLO in IEEE 802.11be to be based on the processing interface's unique understanding of traffic priorities, queue lengths, and real-time network status enabling intelligent TID-to-link mapping. This mapping determines which traffic (<i>e.g.</i>, identified by TID) should be directed to which links (<i>i.e.</i>, associated bandwidth resources).

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	As a particular example, when operating as an AP MLD, the SME and UMAC allocate appropriate RU(s)/MRU(s) based on the data requirements of the specific traffic type mapped to a link. The UMAC considers factors like the amount of data to be transmitted for a particular TID and the channel bandwidth available on the chosen link. It can choose to allocate a single RU for smaller data packets or low-priority traffic, or allocate multiple RUs combined into an MRU for larger data transfers or high-priority traffic requiring more bandwidth. Assigning RUs or MRUs is an integral part of TID-to-link mapping. Likewise, when operating as a non-AP MLD, the SME and UMAC direct packets to links based on the TID-to-link mapping identified by an AP. Additionally, the processing interface may transmit a data stream using the first wireless transceiver without requiring disassociation of the recipient from any of the first and second actual MAC and PHY interfaces. As described with respect to element 1.h, MLO allows a non-AP MLD and an AP MLD to establish multiple links between their corresponding STAs. Data may be transmitted or received on one of the established links without requiring disassociation of the other established links. 35.3.16 ML channel access 35.3.16.1 General A STA that is affiliated with an MLD shall contend for the WM on its link independently from the other STA(s) affiliated with the same MLD, unless explicitly stated otherwise in the subclauses below. Wi-Fi 7 Draft Standard at 598.
[18.d] wherein, after the circuitry has been connected to the application interface and when the wireless networking device is being	In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has configured it such that after the circuitry has been connected to the application interface and when the wireless networking device is being used, the wireless networking device's utilization of the first identified actual bandwidth portion of the second wireless transceiver does not prevent any

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
used, the wireless networking device's utilization of the first identified actual bandwidth portion of the second wireless transceiver does not prevent any other wireless networking device from utilizing a range of frequencies corresponding to the remaining portion of the bandwidth availability of the second wireless transceiver for data transmission or reception purposes.	wireless networking device from utilizing a range of frequencies corresponding to the remaining portion of the bandwidth availability of the second wireless transceiver for data transmission or reception purposes. As described in the Wi-Fi 7 Draft Standard, an AP or non-AP MLD like the Galaxy S24 Ultra will use each of the first and second wireless transceivers to communicate via the RUs or MRUs that have been respectively assigned. The Galaxy S24 Ultra is configured for Multi-user Multiple Input Multiple Output (MU-MIMO) procedures, as well as Orthogonal Frequency Division Multiple Access (OFDMA) procedures. The EHT PHY provides support for DL OFDMA, UL OFDMA, DL MU-MIMO, and UL MU-MIMO. Both DL MU-MIMO and UL MU-MIMO transmissions are supported on both the entire PPDU bandwidth and portions of the PPDU bandwidth, with the assigned resource unit of size greater than or equal to 242 tones. On a resource unit utilizing MU-MIMO transmission, there is support for up to 8 users with up to 4 spatial streams per user with the total number of spatial streams across all users not exceeding 8. The EHT PHY also supports preamble puncturing of an EHT MU PPDU for both OFDMA and non-OFDMA. Wi-Fi 7 Draft Standard at 701.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung’s Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	Wi-Fi CERTIFIED 7™ (continued) MCS 8-9 Rx MCS 8-9 Tx MCS 10-11 Rx MCS 10-11 Tx MCS 12-13 Rx MCS 12-13 Tx Multi-link reconfiguration – AP removal Multi-link reconfiguration – AP restart Multi-RU Operating mode indication Operating mode indication for 320 MHz Static puncturing STR (Simultaneous Transmit and Receive) SU-MIMO Triggered uplink access optimization UL MU-MIMO UL OFDMA Wi-Fi CERTIFIED Certificate for Qualcomm FastConnect 7800 Mobile Connectivity System, Cert. I.D. WFA127693 (2024) (emphasis added). Further, testing of the Galaxy S24 Ultra indicates that the wireless networking device’s utilization of identified bandwidth portions does not prevent any wireless networking device from utilizing a range of frequencies corresponding to remaining portions of bandwidth availability. For example, when one MLD, a Galaxy S25 Ultra, was used to transmit video data to another MLD, a Galaxy S24 Ultra, via an AP using portions of available bandwidth, other bandwidth portions remained available for use by the S24 Ultra, the S25 Ultra, and other devices.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	The screenshots below taken from the Galaxy S24 Ultra and Galaxy S25 Ultra devices show connections to the AP using the same three channels: a 20 MHz channel (“Ch 9”) of the 2.4 GHz frequency band, a 160 MHz channel (“Ch 104”) of the 5 GHz frequency band, and a 320 MHz channel (“Ch 85”) of the 6 GHz frequency band.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra


USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	 The screenshot shows the WiFiman application interface on a Galaxy S24 Ultra. At the top, the title is 'ASUSZENWIFI2'. Below it, the channel is '9, 85, 104' and security is 'WPA2-PSK / WPA3-SAE / WPS'. There are three tabs: 'All (3)', '2.4 GHz (1)', and '5 GHz (1)'. The 'All (3)' tab is selected. The interface lists three access points, all connected: 2.4 GHz (CONNECTED) -44 dBm, Ch: 9 (20 MHz), CE:28:AA:5C:C2:40 5 GHz (CONNECTED) -60 dBm, Ch: 104 (160 MHz), CE:28:AA:5C:C2:41 6 GHz (CONNECTED) -64 dBm, Ch: 85 (320 MHz), CE:28:AA:5C:C2:42  The screenshot shows the WiFiman application interface on a Galaxy S25 Ultra. At the top, the title is 'ASUSZENWIFI2'. Below it, the channel is '9, 85, 104' and security is 'WPA2-PSK / WPA3-SAE / WPS'. There are three tabs: 'All (3)', '2.4 GHz (1)', and '5 GHz (1)'. The 'All (3)' tab is selected. The interface lists three access points, all connected: 2.4 GHz (CONNECTED) -59 dBm, Ch: 9 (20 MHz), CE:28:AA:5C:C2:40 5 GHz (CONNECTED) -61 dBm, Ch: 104 (160 MHz), CE:28:AA:5C:C2:41 6 GHz (CONNECTED) -68 dBm, Ch: 85 (320 MHz), CE:28:AA:5C:C2:42 WiFiman application screenshot taken on Galaxy S24 Ultra showing associations on three frequency bands (Left); WiFiman application screenshot taken on Galaxy S25 Ultra showing associations on three frequency bands (Right).

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	As shown below, the Galaxy S24 Ultra and Galaxy S25 Ultra used only a portion of available bandwidth to communicate the video stream, such that other devices were not impeded from using available bandwidth of the 2.4 GHz, 5 GHz, or 6 GHz transceivers.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra



USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	 2:22 98% < Connection information Link status L2 status L3 status ASUSZENWIFI2 06:28:aa:6c:c2:40 [MLD] RSSI [2.4GHz] Not in use [5GHz] -57 dBm [6GHz] Not in use Channel utilization [6GHz] Not in use [5GHz] 2% (6/255) Link speed [2.4GHz] Tx=154 Mbps / Rx=68 Mbps [5GHz] Tx=576 Mbps / Rx=1729 Mbps [6GHz] Tx=1297 Mbps / Rx=2882 Mbps  2:22 99% < Connection information Link status L2 status L3 status ASUSZENWIFI2 06:28:aa:6c:c2:40 [MLD] RSSI [2.4GHz] Not in use [5GHz] -66 dBm [6GHz] -65 dBm Channel utilization [6GHz] Not in use [5GHz] 2% (6/255) Link speed [2.4GHz] Tx=1729 Mbps / Rx=2882 Mbps [5GHz] Tx=1729 Mbps / Rx=1441 Mbps [6GHz] Tx=0 Mbps / Rx=0 Mbps WiFiman application screenshot taken on Galaxy S24 Ultra during data reception (Left); WiFiman application screenshot taken on Galaxy S25 Ultra during data transmission (Right).

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	Thus, when operating as an AP MLD or a non-AP MLD, the Galaxy S24 Ultra is configured such that the wireless networking device's utilization of the first available bandwidth portion of the first wireless transceiver does not prevent other wireless networking devices from utilizing a range of frequencies corresponding to the remaining portion of the bandwidth availability of the first wireless transceiver for data transmission purposes at the same time that the first bandwidth portion is being used for data transmission purposes.
19. The method of claim 18, wherein the processing interface is configured to, after the circuitry has been connected to the application interface and when the wireless networking device is being used, and in a manner transparent to any layer of the wireless networking device above the processing interface,	<i>See claim 18, above.</i> In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has configured the processing interface such that after the circuitry has been connected to the application interface and when the wireless networking device is being used, the processing interface operates in a manner transparent to any layer of the wireless networking device above the processing interface. <i>See element 1.g of claim 1, above.</i>
[19.a] (a) if both the first identified actual bandwidth portions of the first and second wireless transceivers are available for communication, evaluate the data transfer characteristics of both,	In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has configured the processing interface to, if both the first identified actual bandwidth portions of the first and second wireless transceivers are available for communication, evaluate the data transfer characteristics of both. As described with respect to element 1.f of claim 1, the Galaxy S24 Ultra, when operating as an AP MLD or a non-AP MLD, obtains information about bandwidth availabilities from other devices through, for example, beacon frames and multi-link response frames. For example, both the beacon frame and the multi-link probe response frame include a multi-link traffic indication element, an EHT capabilities element, an EHT operation element, a TID-to-Link mapping element, and a channel usage element. Wi-Fi 7 Draft Standard at 180-81 (beacon frame), 188-89 (probe response frame). These elements include information regarding bandwidth availability, such as a per-link traffic indication list

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	contained in the multi-link traffic indication element and PHY capabilities information contained in the EHT capabilities element. Wi-Fi 7 Draft Standard at 291-93 (Multi-Link Traffic Indication), 265-81 (EHT Capabilities). From this information, the processing interface can identify bandwidth portions that are unavailable or not preferred for communication. The Wi-Fi Agile Multiband Specification provides examples of information regarding bandwidth availabilities that may be communicated by the virtual PHY interface. In accordance with the Wi-Fi Agile Multiband Specification, when operating as a non-AP MLD, for example, the Galaxy S24 Ultra provides “to a Wi-Fi Agile Multiband AP a list of channels and bands on which it prefers not to be associated,” including in each list entry: channel and band, preference value, and reason code. Wi-Fi Agile Multiband Specification at § 2.3.2. A Wi-Fi Agile Multiband STA shall support the following features: • Indicates whether or not it has a cellular data connection available (refer to section 4.2.3) • Provides to a Wi-Fi Agile Multiband AP a list of channels and bands on which it prefers not to be associated, including in each list entry: ▪ Channel and band ▪ Preference value ▪ Reason code Wi-Fi Agile Multiband Specification at § 2.3.2. Reason codes may include, for example, co-located interference, where an “unacceptable level of interference is being experienced by the Wi-Fi Agile Multiband STA in this channel,” and in-device interferer, where the “Agile Multiband STA has another active connection in this channel, or near enough to this channel to cause operating interference.” Wi-Fi Agile Multiband Specification at Table 10. “This information is communicated to the Wi-Fi Agile Multiband AP when the Wi-Fi Agile Multiband STA associates or reassociates, and when the information changes while the Wi-Fi Agile

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	Multiband STA is associated.” Wi-Fi Agile Multiband Specification at §3.2. For a Wi-Fi Agile Multiband AP that supports MLO as defined in the Wi-Fi 7 Draft Standard, “this list of non-preferred channels” is indicated across all affiliated non-AP STAs. <i>Id.</i> Additionally, the Galaxy S24 Ultra, with Wi-Fi 7 enabled, is configured for preamble puncturing. Preamble puncturing allows WNDs, such as the Galaxy S24 Ultra, to recognize and exclude unavailable subchannels from a transmission. <i>See</i> elements 1.f and 1.j of claim 1, above. During use, the processing interface evaluates the puncturing pattern to determine what portions of RUs or MRUs are unavailable or not preferred (and thus not subsequently assigned), and therefore not to be used for transmission purposes. Where bandwidth portions are identified as being available, the data transfer characteristics and quality of identified bandwidth portions may be assessed to identify interference making channels unavailable for communication as well as preferred channels. Testing of the Galaxy S24 Ultra indicates that, when the Galaxy S24 Ultra is in use, the processing interface evaluates data transfer characteristics, such as bandwidth utilization and RSSI data, as shown below.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra


USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	 The screenshot displays the 'Connection information' screen for a Wi-Fi network named 'ASUSZENWIFI2'. It includes tabs for 'Link status', 'L2 status', and 'L3 status'. The 'Link status' tab is active, showing the MAC address '06:28:aa:6c:c2:40 [MLD]'. Below this, the 'RSSI' section shows signal strength for 2.4GHz (Not in use), 6GHz (Not in use), and 5GHz (-75 dBm), accompanied by a spectral graph. The 'Channel utilization' section shows utilization for 2.4GHz (Not in use) and 5GHz (9% (23/255)), also with a spectral graph. The 'Link speed' section shows speeds for 2.4GHz (Tx=68 Mbps / Rx=17 Mbps), 6GHz (Tx=0 Mbps / Rx=0 Mbps), and 5GHz (Tx=432 Mbps / Rx=288 Mbps). The phone's status bar at the top shows the time as 5:58 and battery at 99%.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	WiFiman application screenshot taken on Galaxy S24 Ultra demonstrating connection with local access point.
[19.b] (b) if the data transfer characteristics of the first identified bandwidth portion of the first wireless transceiver are better than those of the first identified bandwidth portion of the second wireless transceiver, use the first wireless transceiver to transmit the first data stream to the recipient, without requiring disassociation of the recipient from either or both of the first and second actual MAC and PHY interfaces, using a subset of frequencies corresponding to only the given resources of the first identified bandwidth portion of the first wireless transceiver that are not unavailable for communication to thereby at least partially satisfy the first wireless bandwidth requirement of the first application, and	In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has configured the processing interface to, if the data transfer characteristics of the first identified bandwidth portion of the first wireless transceiver are better than those of the first identified bandwidth portion of the second wireless transceiver, use the first wireless transceiver to transmit the first data stream to the recipient, without requiring disassociation of the recipient from either or both of the first and second actual MAC and PHY interfaces, using a subset of frequencies corresponding to only the given resources of the first identified bandwidth portion of the first wireless transceiver that are not unavailable for communication to thereby at least partially satisfy the first wireless bandwidth requirement of the first application. For example, the SME and UMAC (through a Resource Allocation Manager) determine TID-to-link mapping and assign RUs/MRUs based on traffic needs and comparison of evaluated data transfer characteristics on each link. The system architecture solves limitations of multi-band to enable MLO in IEEE 802.11be to be based on at least the processing interface's unique understanding of traffic priorities, queue lengths, and real-time network status enabling intelligent TID-to-link mapping. This mapping determines which traffic (<i>e.g.</i>, identified by TID) should be directed to which links (<i>i.e.</i>, associated bandwidth resources). The SME and UMAC allocate appropriate RU(s)/MRU(s) based on the data requirements of the specific traffic type mapped to a link in light of its transfer characteristics. The UMAC considers factors like the amount of data to be transmitted for a particular TID and the data transfer characteristics including the channel bandwidth available on the chosen link. It can choose to allocate a single RU (Resource Unit) for smaller data packets or low-priority traffic, or allocate multiple RUs combined into an MRU (Multiple Resource Unit) for larger data transfers or high-priority traffic requiring more bandwidth. Assigning RUs or MRUs (Multiple Resource Units) is an integral part of TID-to-link mapping.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	Accordingly, the processing interface may be configured to select for transmission a first identified bandwidth portion of either a first or second transceiver based upon a comparison of the evaluated data transfer characteristics of the transceivers, and transmit the data stream. In a survey paper published in IEEE Access and discussing MLO operations as presented in the Wi-Fi 7 Draft Standard, the authors describe that the processing interface of an MLD assigns traffic flows to channels based on channel availability and traffic needs. The motivation for MLO stems from its projected benefits across various dimensions [20]. Firstly, the introduction of the multi-link framework enables significantly improved coordinated operations across multiple links [34], [35]. Through unified and cooperative link management, Wi-Fi 7 can more easily accomplish additional throughput for data flows separated across links than earlier Wi-Fi technologies with separate and independent operations across multiple bands. Secondly, using several lines concurrently enhances the likelihood that a channel will be accessed, considerably reducing latency [36]. Thirdly, MLO permits duplication across numerous connections³ to guarantee the successful transmission of crucial data that demands extremely high reliability. Finally, depending on the application's requirements, MLO can be used to assign data flows to specific links to accomplish traffic separation [37]. Abdalfahid, Alsadg A., <i>et al.</i>, <i>Multi-Link Operation in IEEE802.11be Extremely High Throughput: A Survey</i>, 12 IEEE Access 46891, 46892 (2024) (emphasis added).

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	B. TID-TO-LINK MAPPING The IEEE 802.11 standard defines a Traffic Identifier (TID) as a four-bit value (ranging from 0 to 7) used to differentiate packets for QoS purposes [37]. There are $(2^4) = 16$ possible TID values; 8 identify Traffic Categories (TCs), and the other 8 identify parameterized Traffic Streams (TSs). The TID is assigned to an MSDU in the layers above the MAC () [76]. In MLO, TID is crucial in directing traffic with specific QoS requirements to the appropriate connections or channels. TID-to-link mapping associates each TID with a connection set, allowing any link within that set to transmit data frames associated with that TID. All established connections are initially linked to each TID, though this mapping can later be adjusted through negotiation processes [20], [77]. Abdalfahid, Alsadg A., <i>et al.</i>, <i>Multi-Link Operation in IEEE802.11be Extremely High Throughput: A Survey</i>, 12 IEEE Access 46891, 46895 (2024) (emphasis added). Based on the TID-to-Link mapping, at least the processing interface instructs the actual MAC and actual PHY to transmit the data packets using primitives. These instructions specify the chosen link and the allocated RU/MRU configuration. Based on the instructions, the actual PHY layer segments data packets into units according to the allocated RU/MRU configuration, modulates the data units using appropriate techniques for transmission over the designated link, and transmits the modulated data units using the allocated radio frequencies on the chosen transceiver. For example, the processing interface uses certain vectors, including TXVECTOR, RXVECTOR, PHYCONFIG_VECTOR, and TRIG_VECTOR to instruct the PHY.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	36.2 EHT PHY service interface 36.2.1 Introduction The EHT PHY provides an interface to the EHT MAC through an extension of the generic PHY service interface defined in 8.3.4 (Basic service and options). The interface includes TXVECTOR, RXVECTOR, PHYCONFIG_VECTOR, and TRIG_VECTOR. The EHT MAC uses the TXVECTOR to supply the EHT PHY with per-PPDU transmit parameters. The EHT PHY uses the RXVECTOR to inform the EHT MAC of the received PPDU parameters. The EHT MAC uses the PHYCONFIG_VECTOR to configure the EHT PHY for operation that is independent of PPDU transmission or reception. The EHT MAC uses the TRIG_VECTOR to configure the EHT PHY to receive EHT TB PPDU's over each assigned RU or MRU. Wi-Fi 7 Draft Standard at 670, 671-85 (listing TXVECTOR and RXVECTOR parameters). In all options, in order to transmit data, the MAC generates a PHY-TXSTART.request primitive, which causes the PHY entity to respond with a PHY-TXSTART.confirm primitive and enter the transmit state. Further, the PHY is set to operate at the appropriate frequency through station management via the PLME, as specified in 36.4 (EHT PLME). Other transmit parameters, such as EHT-MCS, coding types, and transmit power, are set via the PHY-SAP using the PHY-TXSTART.request(TXVECTOR) primitive, as described in 36.2.2 (TXVECTOR and RXVECTOR parameters). After transmitting a PPDU that carries a Trigger frame, the MAC sublayer issues a PHY-TRIGGER.request with a TRIGVECTOR parameter that provides the PHY entity with the information needed to demodulate the expected EHT TB PPDU response. The remainder of the subclause applies to the first two paths. Wi-Fi 7 Draft Standard at 902. At least the processing interface evaluates the puncturing pattern to determine what portions of RUs or MRUs are unavailable or not preferred (and thus not subsequently assigned), and therefore not to be used for transmission purposes given the comparison of data transfer characteristics.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	Additionally, the Galaxy S24 Ultra uses enhanced multi-link single-radio (EMLSR) mode. • Android - Android 13 first support, but Android 14 is better (link reconfiguration, use MLD in roaming algorithm) - Pixel 9 - STR MLMR (2.4/5/6) and EMLSR Wi-Fi 7 (802.11be) with 2.4GHz+5GHz+6GHz, 2x2+2x2 MIMO - Pixel 8 - STR MLMR (2.4 + 5/6) and EMLSR (- Samsung S24 Ultra - STR MLMR (2.4 + 5/6) and EMLSR - One Plus 11 - STR MLMR (2.4 + 5/6) and EMLSR https://www.redimadrid.es/files/2024-7-WiFi7-AIOps.pdf at 16 (emphasis added). Wi-Fi CERTIFIED 7™ - Advertised TID-to-link mapping - A-MPDU with A-MSDU - Beamforming sounding - BSS critical update - Compressed Block Ack Rx (buffer size 256) - Compressed Block Ack Tx (buffer size 256) - Compressed Block Ack Rx (buffer size 512) - Compressed Block Ack Tx (buffer size 512) - DL MU-MIMO EMLSR (Enhanced Multilink Single-Radio) - EPCS (Emergency Preparedness Communications Services) priority access - LDPC Rx - LDPC Tx - Load Balancing in MLO

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung’s Galaxy S24 Ultra


USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	Wi-Fi CERTIFIED Certificate for Qualcomm FastConnect 7800 Mobile Connectivity System, Cert. I.D. WFA127693 (2024) (emphasis added). A device operating in EMLSR mode can listen over multiple links simultaneously. Link Switching Multi-link single radio (MLSR): Lower Latency - MLO, but TX/RX over one link at a time by switching links (bands) - Requires one radio on client Enhanced multi-link single radio (EMLSR): Lowest Latency - Same as MLSR, but can listen over multiple links simultaneously - Requires one radio on client Enhanced Multi-link Single Radio (EMLSR) Operation  The diagram illustrates the EMLSR operation. On the left, a laptop icon is connected by a line to a switch. The switch has two output paths: one labeled '5 GHz Channel' and another labeled '6 GHz Channel'. Both channels lead to a server icon on the right. Below the switch, the text 'Dynamic switching' is present. https://www.redimadrid.es/files/2024-7-WiFi7-AIOps.pdf at 14.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	A device operating in EMLSR mode exchanges frames on the first selected transceiver which has the most bandwidth available for load balancing or congestion avoidance purposes. Operation (MLO). Within MLO, the enhanced Multi-Link Single Radio (eMLSR) mode stands out prominently. This technique empowers Wi-Fi access points (APs) and user devices (STAs) to utilize multiple antennas for establishing simultaneous connections across different channels. Via enabling fast channel switching, it allows Wi-Fi APs and STAs to adapt swiftly to changing environmental conditions, enhancing transmission throughput and dependability. Chen, Yun-Tai, <i>et al.</i>, <i>Dynamic Channel Switching and Transition Frequency Scheme for 802.11be eMLSR-Enabled Devices</i>, 2024 IEEE Wireless Communications and Networking Conference at 1 (2024). The eMLSR mode allows Wi-Fi access points (APs) and user devices (STAs) to dynamically transition to the optimal channel to achieve enhanced data throughput. It is essential Chen, Yun-Tai, <i>et al.</i>, <i>Dynamic Channel Switching and Transition Frequency Scheme for 802.11be eMLSR-Enabled Devices</i>, 2024 IEEE Wireless Communications and Networking Conference at 1 (2024). Samsung also described EMLSR operations in U.S. Patent Application No. 17/935,040, which published on April 13, 2023, with Publication No. US2023/0109759. Links with higher bandwidth availability have lower channel contention and hence higher probability of winning channel access. As the Samsung application states, “by opportunistically selecting a link for data communication where it wins the channel contention, EMLSR can improve system spectral efficiency.”

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	[0010] The non-AP MLDs in 802.11be can have different capabilities in terms of multi-link operation. Many 802.11be non-AP MLDs may only have a single radio. Enhanced Multi-Link Single Radio (EMLSR) enables a multi-link operation with a single radio. With EMLSR operation, such a non-AP MLD can achieve throughput enhancement with reduced latency—a performance close to concurrent dual radio non-AP MLDs. [0011] In EMLSR mode, a non-AP device behaves like a single radio device that can perform channel sensing and reception of elementary packets on multiple bands/links simultaneously but can perform reliable data communication on only one link at a time. Thus, by opportunistically selecting a link for data communication where it wins the channel contention, EMLSR can improve system spectral efficiency. U.S. Publ. No. US2023/0109759 at ¶¶ [0010]-[0011]. As a particular example, when operating as a non-AP MLD in EMLSR mode, the Galaxy S24 Ultra may listen to two (or more) pre-configured channels simultaneously for incoming packets. Such listening operations may be based on CCA (Clear Channel Assessment) and/or receiving an initial control frame (either a multi-user request-to-send (MU-RTS) or a buffer status report poll (BSRP)) of frame exchanges initiated by an AP with which the Galaxy S24 Ultra is associated. Upon receipt of a control frame, the Galaxy S24 Ultra may respond with a control frame (<i>e.g.</i>, clear-to-send (CTS)).

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	When a non-AP MLD is operating in the EMLSR mode with an AP MLD supporting the EMLSR mode, the following applies: a) The non-AP MLD shall be able to listen on the EMLSR link(s), by having its affiliated non-AP STA(s) corresponding to those links in the awake state. The listening operation includes CCA and receiving the initial Control frame of frame exchanges that are initiated by the AP MLD. Wi-Fi 7 Draft Standard at 610. As another example, the Galaxy S24 Ultra, when operating as an AP MLD or a non-AP MLD, may monitor channel conditions, including traffic volume, signal strength, and interference levels. This information may be gathered through Channel Load Reports (CLRs) exchanged between devices. For example, the AP MLD intelligently distributes traffic across available transceivers based on channel load information directing devices to less congested links. Load balancing algorithms may dynamically distribute traffic across MLO links for optimal utilization. Load balancing mechanisms may adapt to changing network conditions by adjusting link usage. Load balancing may result in more efficient use of available channels and links by minimizing congestion. The non-AP MLD may implement load balancing decisions made by the AP MLD. As shown below, the Galaxy S24 Ultra uses load balancing in MLO.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	Wi-Fi CERTIFIED 7™ Advertised TID-to-link mapping A-MPDU with A-MSDU Beamforming sounding BSS critical update Compressed Block Ack Rx (buffer size 256) Compressed Block Ack Tx (buffer size 256) Compressed Block Ack Rx (buffer size 512) Compressed Block Ack Tx (buffer size 512) DL MU-MIMO EMLSR (Enhanced Multilink Single-Radio) EPCS (Emergency Preparedness Communications Services) priority access LDPC Rx LDPC Tx Load Balancing in MLO Wi-Fi CERTIFIED Certificate for Qualcomm FastConnect 7800 Mobile Connectivity System, Cert. I.D. WFA127693 (2024) (emphasis added). Accordingly, when operating as AP MLD or as a non-AP MLD, the processing interface of the Galaxy S24 Ultra is configured to transmit the data stream to the recipient using the first identified bandwidth portion of either the first or second wireless transceiver based upon a comparison of the evaluated data transfer characteristics. Additionally, the processing interface may transmit a data stream using the first wireless transceiver without requiring disassociation of the recipient from either or both of the first and second actual MAC and PHY interfaces. MLO allows a non-AP MLD and an

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	AP MLD to establish multiple links between their corresponding STAs. Data may be transmitted or received on one of the established links without requiring disassociation of the other established links. 35.3.16 ML channel access 35.3.16.1 General A STA that is affiliated with an MLD shall contend for the WM on its link independently from the other STA(s) affiliated with the same MLD, unless explicitly stated otherwise in the subclauses below. Wi-Fi 7 Draft Standard at 598.
[19.c] (c) if the data transfer characteristics of the first identified portion of the second wireless transceiver are better than those of the first identified bandwidth portion of the first wireless transceiver, use the second wireless transceiver to transmit the first data stream to the recipient, without requiring disassociation of the recipient from either or both of the first and second actual MAC and PHY interfaces, using a subset of frequencies corresponding to only the given resources of the first identified bandwidth portion of the second wireless transceiver that are not unavailable for communication	In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has configured the processing interface to, if the data transfer characteristics of the first identified portion of the second wireless transceiver are better than those of the first identified bandwidth portion of the first wireless transceiver, use the second wireless transceiver to transmit the first data stream to the recipient, without requiring disassociation of the recipient from either or both of the first and second actual MAC and PHY interfaces, using a subset of frequencies corresponding to only the given resources of the first identified bandwidth portion of the second wireless transceiver that are not unavailable for communication to thereby at least partially satisfy the first wireless bandwidth requirement of the first application. For example, the SME and UMAC (through a Resource Allocation Manager) determine TID-to-link mapping and assign RUs/MRUs based on traffic needs and comparison of evaluated data transfer characteristics on each link. The system architecture solves limitations of multi-band to enable MLO in IEEE 802.11be to be based on at least the processing interface's unique understanding of traffic priorities, queue lengths, and real-time network status enabling intelligent TID-to-link mapping. This mapping determines which traffic (<i>e.g.</i>, identified by TID) should be directed to which links (<i>i.e.</i>, associated bandwidth resources). The SME and UMAC allocate appropriate RU(s)/MRU(s) based on the data

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
to thereby at least partially satisfy the first wireless bandwidth requirement of the first application.	requirements of the specific traffic type mapped to a link in light of its transfer characteristics. The UMAC considers factors like the amount of data to be transmitted for a particular TID and the data transfer characteristics including the channel bandwidth available on the chosen link. It can choose to allocate a single RU (Resource Unit) for smaller data packets or low-priority traffic, or allocate multiple RUs combined into an MRU (Multiple Resource Unit) for larger data transfers or high-priority traffic requiring more bandwidth. Assigning RUs or MRUs (Multiple Resource Units) is an integral part of TID-to-link mapping. Accordingly, the processing interface may be configured to select for transmission a first identified bandwidth portion of either a first or second transceiver based upon a comparison of the evaluated data transfer characteristics of the transceivers, and transmit the data stream. At least the processing interface evaluates the puncturing pattern to determine what portions of RUs or MRUs are unavailable or not preferred (and thus not subsequently assigned), and therefore not to be used for transmission purposes given the comparison of data transfer characteristics. Additionally, the Galaxy S24 Ultra uses enhanced multi-link single-radio (EMLSR) mode. Accordingly, when operating as AP MLD or as a non-AP MLD, the processing interface of the Galaxy S24 Ultra is configured to transmit the data stream to the recipient using the first identified bandwidth portion of either the first or second wireless transceiver based upon a comparison of the evaluated data transfer characteristics. <i>See</i> element 19.b, above.
20. The method of claim 19, wherein the data transfer characteristics are representative of one or more environmental conditions where the wireless networking device is used.	<i>See</i> claim 19, above. In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has performed the method of claim 19, wherein the data transfer characteristics are representative of one or more environmental conditions where the wireless networking device is being used. Environmental conditions where the wireless networking device is used may include, for example, bandwidth unavailability and received signal strength.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	The Galaxy S24 Ultra complies with the Wi-Fi Agile Multiband Specification where, “[t]he goal of the Wi-Fi Agile Multiband certification program is to certify features that facilitate efficient use of multiple frequency bands/channels available to APs and the STAs. The program is built on the fundamental premise that the APs and STAs each have information which can aid in making the most effective selection of the spectrum band in which the STA and AP should be communicating.” Wi-Fi Agile Multiband Specification at §3.1. As described with respect to element 1.f of claim 1, the Galaxy S24 Ultra, when operating as an AP MLD or a non-AP MLD, obtains information about bandwidth availabilities from other devices through, for example, beacon frames and multi-link response frames. For example, both the beacon frame and the multi-link probe response frame include a multi-link traffic indication element, an EHT capabilities element, an EHT operation element, a TID-to-Link mapping element, and a channel usage element. Wi-Fi 7 Draft Standard at 180-81 (beacon frame), 188-89 (probe response frame). These elements include information regarding bandwidth availability, such as a per-link traffic indication list contained in the multi-link traffic indication element and PHY capabilities information contained in the EHT capabilities element. Wi-Fi 7 Draft Standard at 291-93 (Multi-Link Traffic Indication), 265-81 (EHT Capabilities). From this information, the processing interface can identify bandwidth portions that are unavailable. Additionally, the Galaxy S24 Ultra, with Wi-Fi 7 enabled, is configured for preamble puncturing. Preamble puncturing allows WNDs, such as the Galaxy S24 Ultra, to recognize and exclude unavailable subchannels from a transmission. <i>See</i> elements 1.f and 1.j of claim 1, above. During use, the processing interface evaluates the puncturing pattern to determine what portions of RUs or MRUs are unavailable (and thus not subsequently assigned), and therefore not to be used for transmission purposes.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	The Galaxy S24 Ultra also evaluates at least one data transfer characteristic comprising evaluation of received signal strength through radio measurements (“RM”) and received signal strength indicator (“RSSI”). For example, “[a] Wi-Fi Agile Multiband AP shall include an RM Enabled Capabilities element in all Beacon and Probe Response frames,” and “[a] Wi-Fi Agile Multiband STA shall include an RM Enabled Capabilities element with bit 6 set to one into an Association Request frame sent to a Wi-Fi Agile Multiband AP.” Wi-Fi Agile Multiband Specification at §2.3.4. “The AP shall only send the Beacon request to the STA if the STA indicates that it supports the associated RM capability.” Wi-Fi Agile Multiband Specification at §3.4. For example, association related attributes include an “Insufficient RSSI” reason code, and transition related attributes include low RSSI reason codes. Wi-Fi Agile Multiband Specification at Tables 14, 18, and 20. Testing of the Galaxy S24 Ultra indicates that, when the Galaxy S24 Ultra is in use, the processing interface evaluates data transfer characteristics, such as bandwidth utilization and RSSI data, as shown below.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra


USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	 The screenshot displays the 'Connection information' screen on a Samsung Galaxy S24 Ultra. At the top, the status bar shows the time as 5:58, signal strength, and a 99% battery level. The screen title is 'Connection information' with a back arrow. Below the title are three tabs: 'Link status' (selected), 'L2 status', and 'L3 status'. The main content area shows the network name 'ASUSZENWIFI2' with its MAC address '06:28:aa:6c:c2:40 [MLD]'. Under the 'RSSI' section, it indicates '[2.4GHz] Not in use', '[6GHz] Not in use', and '[5GHz] -75 dBm'. A line graph below this shows signal strength across frequencies, with a peak in the 5GHz band. The 'Channel utilization' section shows '[2.4GHz] Not in use' and '[5GHz] 9% (23/255)'. Another line graph shows utilization across frequencies, with a significant peak in the 5GHz band. The 'Link speed' section shows '[2.4GHz] Tx=68 Mbps / Rx=17 Mbps', '[6GHz] Tx=0 Mbps / Rx=0 Mbps', and '[5GHz] Tx=432 Mbps / Rx=288 Mbps'. The bottom of the screen shows the standard Android navigation bar.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	WiFiman application screenshot taken on Galaxy S24 Ultra demonstrating connection with local access point.
21. The method of claim 1, wherein the processing interface is configured to, after the circuitry has been connected to the application interface and when the wireless networking device is being used, and in a manner transparent to any layer of the wireless networking device above the processing interface,	<i>See claim 1, above.</i> In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has configured the processing interface such that after the circuitry has been connected to the application interface and when the wireless networking device is being used, the processing interface operates in a manner transparent to any layer of the wireless networking device above the processing interface. <i>See element 1.g of claim 1, above.</i>
[21.a] aggregate the first identified actual bandwidth portion of the first wireless transceiver with an identified first portion of an available bandwidth of the second wireless transceiver to at least partially simultaneously transmit the first data stream to the first recipient from both of the first and second wireless transceivers.	In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has configured the processing interface to aggregate the first identified actual bandwidth portion of the first wireless transceiver with an identified first portion of an available bandwidth of the second wireless transceiver to at least partially simultaneously transmit the first data stream to the first recipient from both of the first and second wireless transceivers. The processing interface of the Galaxy S24 Ultra receives a data stream from the application interface and prepares the data stream for transmission by first packetizing it. Packets are then assigned to links for transmission in accordance with, for example, TID-to-Link mapping that is negotiated between an AP MLD and a non-AP MLD. <i>See elements 1.a and 1.k of claim 1.</i>

Exhibit G

US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra




Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	Fig. 5-2a, Wi-Fi 7 Draft Standard at 82 (emphasis added). Additionally, MLO allows a non-AP MLD to transmit data over multiple links with different frequencies simultaneously. The processing interface may prepare the data stream for simultaneous transmission to the recipient from two selected transceivers using a subset of frequencies corresponding to their available bandwidths. With MLO procedures, the processing interface may assign some data packets to a first link and other data packets to a second link for simultaneous transmission including different frequency bands. 4.9.6 Reference model for multi-link operation (MLO) MLO defines a set of procedures allowing communication over one or more links between MLDs. An MLD manages such communication over one or more links. Communication over links using different channels on different frequency bands or the same frequency band can occur simultaneously or not depending on the capabilities of both the AP MLD and the non-AP MLD (see 35.3.16.3 (Simultaneous transmit and receive (STR) operation) and 35.3.16.4 (Nonsimultaneous transmit and receive (NSTR) operation)). The MLO procedures (see 35.3 (Multi-link operation (MLO))) allow a pair of MLDs to discover, synchronize, (de)authenticate, (re)associate, disassociate, and manage links and other resources with each other on any common bands or channels that are supported by both MLDs. Each MLD has a single MAC-SAP. Each STA affiliated with an MLD has a MAC address different from any other STA affiliated with the same MLD. Wi-Fi 7 Draft Standard at 76. As shown below, Abdalhafid <i>et al.</i> describe the processing interface's ability to satisfy the requirements of a traffic flow using multiple links with simultaneous transmission.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	C. MULTI-LINK CHANNEL ACCESS MLO offers a distinct advantage over a single wide channel by facilitating asynchronous channel access and data transmission across multiple links. This enables simultaneous transmission and reception in separate frequency bands [40], Abdalfahid, Alsadg A., <i>et al.</i>, <i>Multi-Link Operation in IEEE802.11be Extremely High Throughput: A Survey</i>, 12 IEEE Access 46891, 46896 (2024) (emphasis added). The motivation for MLO stems from its projected benefits across various dimensions [20]. Firstly, the introduction of the multi-link framework enables significantly improved coordinated operations across multiple links [34], [35]. Through unified and cooperative link management, Wi-Fi 7 can more easily accomplish additional throughput for data flows separated across links than earlier Wi-Fi technologies with separate and independent operations across multiple bands. Secondly, using several lines concurrently enhances the likelihood that a channel will be accessed, considerably reducing latency [36]. Thirdly, MLO permits duplication across numerous connections³ to guarantee the successful transmission of crucial data that demands extremely high reliability. Finally, depending on the application's requirements, MLO can be used to assign data flows to specific links to accomplish traffic separation [37]. Abdalfahid, Alsadg A., <i>et al.</i>, <i>Multi-Link Operation in IEEE802.11be Extremely High Throughput: A Survey</i>, 12 IEEE Access 46891, 46892 (2024) (emphasis added).

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	2) 1-TO-M TID-TO-LINK MAPPING, WHICH COMES IN AT NUMBER (PACKET-LEVEL AGGREGATION) This mapping enables traffic associated with a particular TID to travel via any link within a designated set. This strategy accelerates the resolution of congested TID queues, enhancing traffic handling capacity. UMAC manages TID-specific packet routing on the transmitter's end. However, this approach introduces packet reordering, requiring the receiver's UMAC to temporarily store data and orderly transmit packets to the LLC layer [20]. In other words UMAC serves as a shared component within the MAC sub-layer across all interfaces. Within the UMAC, operations that re independent of specific links are carried out. Examples include the assignment of sequence numbers and the aggregation/de-aggregation of MAC service data units (MSDUs). It is crucial to note that the assignment of sequence numbers is specifically conducted at the UMAC, as packets from the same traffic flow may undergo fragmentation and transmission across different links. This approach facilitates the reordering of packets at the receiver's end. Furthermore, this layer is responsible for executing common management functions applicable to all links, such as setup, association, and authentication [71]. Abdalfahid, Alsadg A., <i>et al.</i>, <i>Multi-Link Operation in IEEE802.11be Extremely High Throughput: A Survey</i>, 12 IEEE Access 46891, 46895-6 (2024) (emphasis added). As a particular example, when operating as a non-AP MLD, the Galaxy S24 Ultra may operate in EMLMR mode. The Wi-Fi 7 Draft Standard states that EMLMR mode is an operating mode wherein a non-AP MLD like the Galaxy S24 Ultra aggregates some physical resources of its different radios used on different links (so-called EMLMR links) in order to

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	transmit or receive data up to a pre-defined number of supported Rx/Tx spatial streams, which number may be greater than the number of supported Rx/Tx spatial streams of each radio. To operate in EMLMR mode, the Galaxy S24 Ultra makes allocation decisions that involve use of at least some of the first and second bandwidth availabilities. 35.3.18 Enhanced multi-link multi-radio (EMLMR) operation The enhanced multi-link multi-radio (EMLMR) operation defined in this subclause allows a non-AP MLD with multiple radios on multiple links to listen a set of links as defined below for an initial frame sent by an AP affiliated with an AP MLD, followed by frame exchanges that satisfy the MCS and number of spatial streams (N_{SS}) capabilities in the EMLMR mode on the link on which the initial frame was received. Here initial frame is transmitted in a PPDU whose N_{SS} satisfies the receiving STA's capabilities. A non-AP MLD may operate in the EMLMR mode on a specified set of the enabled links as defined in 9.4.1.76 (EML Control field) between the non-AP MLD and its associated AP MLD. The specified set of the enabled links in which the EMLMR mode is applied is called EMLMR links. A non-AP STA affiliated with the non-AP MLD that is on an EMLMR link is an EMLMR STA. The EMLMR links shall be indicated in the EMLMR Link Bitmap subfield of the EML Control field of the EML Operating Mode Notification frame (see 9.6.38.8 (EML Operating Mode Notification frame details)) by setting the bit positions corresponding to the link IDs of these links in the EMLMR Link Bitmap subfield to 1. Wi-Fi 7 Draft Standard at 613. As described with respect to element 1.a of claim 1, the Galaxy S24 Ultra's processing interface is provided by the Qualcomm Snapdragon 8 Gen 3 System on a Chip processor that includes the FastConnect 7800 connectivity system contained within the Galaxy S24 Ultra. The Qualcomm FastConnect 7800 connectivity system is compliant with Wi-Fi 7 standards.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	Leading Wi-Fi 7, premium Wi-Fi 6/6E, and advanced Bluetooth audio come together in this powerful and versatile connectivity system to unlock extreme performance for mobile, compute, and XR experiences. The Qualcomm® FastConnect™ 7800 Mobile Connectivity System is an advanced 14nm Wi-Fi and Bluetooth® Connectivity system delivering ultra-high speeds (up to 5.8 Gbps*), sustained low latency (2 ms), and premium Bluetooth audio. While maintaining compliance with the latest Wi-Fi 6/6E and Wi-Fi 7 standards, FastConnect 7800 is packed with sophisticated innovation that goes beyond standard benchmarks. High Band Simultaneous Multi-Link Wi-Fi technology uniquely harnesses the potential of 5 and 6GHz bands for multiple links of high band performance for throughput hungry and latency sensitive applications, eliminating dependence on comparatively narrow and congested 2.4GHz band. https://www.qualcomm.com/products/technology/wi-fi/fastconnect/fastconnect-7800. As demonstrated below, the Qualcomm FastConnect 7800 connectivity system allows the Galaxy S24 Ultra to aggregate resources from multiple links.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra


USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	With Wi-Fi 7 HBS Multi-Link 320MHz becomes even more achievable  delivering the fastest and lowest-latency Wi-Fi 7 performance * Speed claims refer to maximum physical layer (PHY) rate https://www.qualcomm.com/products/technology/wi-fi/fastconnect/fastconnect-7800. This evidences that devices, such as the Galaxy S24 Ultra phone, for example, can aggregate a 160 MHz channel in the 5 GHz band with a 160 MHz channel in the 6 GHz band. Testing of the Galaxy S24 Ultra indicates that, when the Galaxy S24 Ultra is in use, it operates in EMLMR mode to aggregate resources from multiple links. For example, the screenshot below illustrates the Galaxy S24 Ultra's aggregation of the 2.4 GHz and the 5 GHz bands.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung’s Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	5:58 GG 99% < Connection information Link statusL2 statusL3 status ASUSZENWIFI2 06:28:aa:6c:c2:40 [MLD] RSSI [2.4GHz] Not in use [6GHz] Not in use [5GHz] -75 dBm  Channel utilization [2.4GHz] Not in use [5GHz] 9% (23/255)  Link speed [2.4GHz] Tx=68 Mbps / Rx=17 Mbps [6GHz] Tx=0 Mbps / Rx=0 Mbps [5GHz] Tx=432 Mbps / Rx=288 Mbps

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	WiFiman application screenshot taken on Galaxy S24 Ultra demonstrating connection with local access point.
22. The method of claim 21, wherein the first data stream is substantially simultaneously transmitted to the recipient from both of the first and second wireless transceivers.	<i>See claim 21, above.</i> In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has performed the method of claim 21, wherein the first data stream is substantially simultaneously transmitted to the recipient from both of the first and second wireless transceivers. As described with respect to claim 21, MLO allows a non-AP MLD to transmit data over multiple links with different frequencies simultaneously. With MLO procedures, some data packets may be transmitted using a first link and other data packets may be transmitted using a second link for simultaneous transmission including over different frequency bands. For example, the Galaxy S24 Ultra may operate in EMLMR mode. The transmission of data over two transceivers may be performed substantially simultaneously. 4.9.6 Reference model for multi-link operation (MLO) MLO defines a set of procedures allowing communication over one or more links between MLDs. An MLD manages such communication over one or more links. Communication over links using different channels on different frequency bands or the same frequency band can occur simultaneously or not depending on the capabilities of both the AP MLD and the non-AP MLD (see 35.3.16.3 (Simultaneous transmit and receive (STR) operation) and 35.3.16.4 (Nonsimultaneous transmit and receive (NSTR) operation)). The MLO procedures (see 35.3 (Multi-link operation (MLO))) allow a pair of MLDs to discover, synchronize, (de)authenticate, (re)associate, disassociate, and manage links and other resources with each other on any common bands or channels that are supported by both MLDs. Each MLD has a single MAC-SAP. Each STA affiliated with an MLD has a MAC address different from any other STA affiliated with the same MLD. Wi-Fi 7 Draft Standard at 76.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	As a particular example, when operating as a non-AP MLD, the Galaxy S24 Ultra may operate in EMLMR mode. The Wi-Fi 7 Draft Standard states that EMLMR mode is an operating mode wherein a non-AP MLD like the Galaxy S24 Ultra aggregates some physical resources of its different radios used on different links (so-called EMLMR links) in order to transmit or receive data up to a pre-defined number of supported Rx/Tx spatial streams, which number may be greater than the number of supported Rx/Tx spatial streams of each radio. 35.3.18 Enhanced multi-link multi-radio (EMLMR) operation The enhanced multi-link multi-radio (EMLMR) operation defined in this subclause allows a non-AP MLD with multiple radios on multiple links to listen a set of links as defined below for an initial frame sent by an AP affiliated with an AP MLD, followed by frame exchanges that satisfy the MCS and number of spatial streams (N_{SS}) capabilities in the EMLMR mode on the link on which the initial frame was received. Here initial frame is transmitted in a PPDU whose N_{SS} satisfies the receiving STA's capabilities. A non-AP MLD may operate in the EMLMR mode on a specified set of the enabled links as defined in 9.4.1.76 (EML Control field) between the non-AP MLD and its associated AP MLD. The specified set of the enabled links in which the EMLMR mode is applied is called EMLMR links. A non-AP STA affiliated with the non-AP MLD that is on an EMLMR link is an EMLMR STA. The EMLMR links shall be indicated in the EMLMR Link Bitmap subfield of the EML Control field of the EML Operating Mode Notification frame (see 9.6.38.8 (EML Operating Mode Notification frame details)) by setting the bit positions corresponding to the link IDs of these links in the EMLMR Link Bitmap subfield to 1. Wi-Fi 7 Draft Standard at 613.
23. The method of claim 21, wherein the processing interface is configured to, after the circuitry has been connected to the application interface and when the wireless networking device is being used,	<i>See claim 21, above.</i> In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has configured the processing interface such that after the circuitry has been connected to the application interface and when the wireless networking device is being used, the processing interface

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
and in a manner transparent to any layer of the wireless networking device above the processing interface,	operates in a manner transparent to any layer of the wireless networking device above the processing interface. <i>See</i> element 1.g of claim 1, above.
[23.a] aggregate the first identified actual bandwidth portion of the first wireless transceiver with an identified first portion of an available bandwidth of the second wireless transceiver to cause the first and second wireless transceivers to at least partially simultaneously receive a second data stream from the recipient.	In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has configured the processing interface to aggregate the first identified actual bandwidth portion of the first wireless transceiver with an identified first portion of an available bandwidth of the second wireless transceiver to cause the first and second wireless transceivers to at least partially simultaneously receive a second data stream from the recipient. As discussed with respect to claim 1, the Galaxy S24 Ultra, when operating as an AP MLD or a non-AP MLD, has three transceivers. The Galaxy S24 Ultra, when operating as an AP MLD or a non-AP MLD, receives data in accordance with negotiated TID-to-Link mapping procedures. <i>See</i> elements 1.a and 1.k of claim 1. For example, two peer MLDs may negotiate a TID-to-Link Mapping (TTLM). The two MLDs perform uplink and downlink operations in accordance with the negotiated TTLM. Once an MLD has successfully negotiated a TTLM with a peer MLD, both the MLD and the peer MLD shall update UL and/or DL TTLM information according to the negotiated TTLM. In case TTLM of a specific TID is missing in the negotiation, the most recent TTLM of this TID shall remain unchanged and valid unless it is successfully updated according to the procedure defined in 35.3.7.1 (General). If an MLD has failed to negotiate a TTLM with a peer MLD, the most recent TTLM of each of the TIDs shall remain unchanged and valid unless it is successfully updated according to the procedure defined in 35.3.7.2.1 (General). Wi-Fi 7 Draft Standard at 569.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	When an MLD has successfully negotiated with a peer MLD an UL and/or DL TTLM in which the bit position i of the Link Mapping Of TID n field in the TID-To-Link Mapping element in the (Re)Association Request frame or TID-To-Link Mapping Request frame is set to 0, TID n shall not be mapped to the link associated with the link ID i and therefore an MPDU corresponding to TID n, with exceptions for QoS Null frame as specified in 35.3.7.2.1 (General), shall not be scheduled for transmission on the link associated with link ID i in the UL and/or DL based on the Direction subfield in the TID-To-Link Mapping element. Wi-Fi 7 Draft Standard at 570. Additionally, the data stream is received by the processing interface. As shown below, data transmitted to an MLD, such as the Galaxy S24 Ultra, is transmitted through the LMAC, the UMAC, and to the LLC sublayer via the MAC SAP. During reception, MPDUs originating from different PHY SAPs first go through an MLD lower MAC entity, followed by a merging process (first-in first-out), and then go through the rest of the processes in the right-hand side of Figure 5-2a (MAC data plane architecture for an MLD exchanging individually addressed Data frames with a peer MLD). Then, one or more MSDUs are delivered to the LLC sublayer via the MAC SAP or to the DS via the DSAF. If an MSDU arrives at a disabled IEEE 802.1X Controlled/Uncontrolled Port and the MSDU does not represent an IEEE 802.1X frame, then the MSDU is discarded. Wi-Fi 7 Draft Standard at 81.

Exhibit G

US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra




Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	Fig. 5-2a, Wi-Fi 7 Draft Standard at 82 (emphasis added). As a particular example, when operating as a non-AP MLD, the Galaxy S24 Ultra may operate in EMLMR mode. The Wi-Fi 7 Draft Standard states that EMLMR mode is an operating mode wherein a non-AP MLD like the Galaxy S24 Ultra aggregates some physical resources of its different radios used on different links (so-called EMLMR links) in order to transmit or receive data up to a pre-defined number of supported Rx/Tx spatial streams, which number may be greater than the number of supported Rx/Tx spatial streams of each radio. 35.3.18 Enhanced multi-link multi-radio (EMLMR) operation The enhanced multi-link multi-radio (EMLMR) operation defined in this subclause allows a non-AP MLD with multiple radios on multiple links to listen a set of links as defined below for an initial frame sent by an AP affiliated with an AP MLD, followed by frame exchanges that satisfy the MCS and number of spatial streams (N_{SS}) capabilities in the EMLMR mode on the link on which the initial frame was received. Here initial frame is transmitted in a PPDU whose N_{SS} satisfies the receiving STA's capabilities. A non-AP MLD may operate in the EMLMR mode on a specified set of the enabled links as defined in 9.4.1.76 (EML Control field) between the non-AP MLD and its associated AP MLD. The specified set of the enabled links in which the EMLMR mode is applied is called EMLMR links. A non-AP STA affiliated with the non-AP MLD that is on an EMLMR link is an EMLMR STA. The EMLMR links shall be indicated in the EMLMR Link Bitmap subfield of the EML Control field of the EML Operating Mode Notification frame (see 9.6.38.8 (EML Operating Mode Notification frame details)) by setting the bit positions corresponding to the link IDs of these links in the EMLMR Link Bitmap subfield to 1. Wi-Fi 7 Draft Standard at 613. As described with respect to element 1.a of claim 1, the Galaxy S24 Ultra's processing interface is provided by the Qualcomm Snapdragon 8 Gen 3 System on a Chip processor that includes the FastConnect 7800 connectivity system contained within the Galaxy S24 Ultra. The Qualcomm FastConnect 7800 connectivity system is compliant with Wi-Fi 7 standards.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	Leading Wi-Fi 7, premium Wi-Fi 6/6E, and advanced Bluetooth audio come together in this powerful and versatile connectivity system to unlock extreme performance for mobile, compute, and XR experiences. The Qualcomm® FastConnect™ 7800 Mobile Connectivity System is an advanced 14nm Wi-Fi and Bluetooth® Connectivity system delivering ultra-high speeds (up to 5.8 Gbps*), sustained low latency (2 ms), and premium Bluetooth audio. While maintaining compliance with the latest Wi-Fi 6/6E and Wi-Fi 7 standards, FastConnect 7800 is packed with sophisticated innovation that goes beyond standard benchmarks. High Band Simultaneous Multi-Link Wi-Fi technology uniquely harnesses the potential of 5 and 6GHz bands for multiple links of high band performance for throughput hungry and latency sensitive applications, eliminating dependence on comparatively narrow and congested 2.4GHz band. https://www.qualcomm.com/products/technology/wi-fi/fastconnect/fastconnect-7800. As demonstrated below, the Qualcomm FastConnect 7800 connectivity system allows the Galaxy S24 Ultra to aggregate resources from multiple links.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra


USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	With Wi-Fi 7 HBS Multi-Link 320MHz becomes even more achievable  delivering the fastest and lowest-latency Wi-Fi 7 performance * Speed claims refer to maximum physical layer (PHY) rate https://www.qualcomm.com/products/technology/wi-fi/fastconnect/fastconnect-7800. This evidences that devices, such as the Galaxy S24 Ultra phone, for example, can aggregate a 160 MHz channel in the 5 GHz band with a 160 MHz channel in the 6 GHz band. Testing of the Galaxy S24 Ultra indicates that, when the Galaxy S24 Ultra is in use, it operates in EMLMR mode to aggregate resources from multiple links. For example, the screenshot below illustrates the Galaxy S24 Ultra's aggregation of the 2.4 GHz and the 5 GHz bands.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra


USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	 The screenshot displays the 'Connection information' screen for a Wi-Fi network named 'ASUSZENWIFI2' with MAC address '06:28:aa:6c:c2:40 [MLD]'. The 'Link status' tab is selected. The RSSI section shows: [2.4GHz] Not in use, [6GHz] Not in use, and [5GHz] -75 dBm. The Channel utilization section shows: [2.4GHz] Not in use and [5GHz] 9% (23/255). The Link speed section shows: [2.4GHz] Tx=68 Mbps / Rx=17 Mbps, [6GHz] Tx=0 Mbps / Rx=0 Mbps, and [5GHz] Tx=432 Mbps / Rx=288 Mbps. The background of the screen is white with blue and green accents for the graphs.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	WiFiman application screenshot taken on Galaxy S24 Ultra demonstrating connection with local access point.
24. The method of claim 23, wherein the second data stream is substantially simultaneously received by both of the first and second wireless transceivers.	<i>See claim 23, above.</i> In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has performed the method of claim 23, wherein the second data stream is substantially simultaneously received by both of the first and second wireless transceivers. As described with respect to claim 23, MLO allows a non-AP MLD to receive data over multiple links with different frequencies simultaneously. With MLO procedures, some data packets may be received using a first link and other data packets may be received using a second link for simultaneous reception including across different frequency bands. For example, the Galaxy S24 Ultra may operate in EMLMR mode. The reception of data over two transceivers may be performed substantially simultaneously. 4.9.6 Reference model for multi-link operation (MLO) MLO defines a set of procedures allowing communication over one or more links between MLDs. An MLD manages such communication over one or more links. Communication over links using different channels on different frequency bands or the same frequency band can occur simultaneously or not depending on the capabilities of both the AP MLD and the non-AP MLD (see 35.3.16.3 (Simultaneous transmit and receive (STR) operation) and 35.3.16.4 (Nonsimultaneous transmit and receive (NSTR) operation)). The MLO procedures (see 35.3 (Multi-link operation (MLO))) allow a pair of MLDs to discover, synchronize, (de)authenticate, (re)associate, disassociate, and manage links and other resources with each other on any common bands or channels that are supported by both MLDs. Each MLD has a single MAC-SAP. Each STA affiliated with an MLD has a MAC address different from any other STA affiliated with the same MLD. Wi-Fi 7 Draft Standard at 76.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	As a particular example, when operating as a non-AP MLD, the Galaxy S24 Ultra may operate in EMLMR mode. The Wi-Fi 7 Draft Standard states that EMLMR mode is an operating mode wherein a non-AP MLD like the Galaxy S24 Ultra aggregates some physical resources of its different radios used on different links (so-called EMLMR links) in order to transmit or receive data up to a pre-defined number of supported Rx/Tx spatial streams, which number may be greater than the number of supported Rx/Tx spatial streams of each radio. 35.3.18 Enhanced multi-link multi-radio (EMLMR) operation The enhanced multi-link multi-radio (EMLMR) operation defined in this subclause allows a non-AP MLD with multiple radios on multiple links to listen a set of links as defined below for an initial frame sent by an AP affiliated with an AP MLD, followed by frame exchanges that satisfy the MCS and number of spatial streams (N_{SS}) capabilities in the EMLMR mode on the link on which the initial frame was received. Here initial frame is transmitted in a PPDU whose N_{SS} satisfies the receiving STA's capabilities. A non-AP MLD may operate in the EMLMR mode on a specified set of the enabled links as defined in 9.4.1.76 (EML Control field) between the non-AP MLD and its associated AP MLD. The specified set of the enabled links in which the EMLMR mode is applied is called EMLMR links. A non-AP STA affiliated with the non-AP MLD that is on an EMLMR link is an EMLMR STA. The EMLMR links shall be indicated in the EMLMR Link Bitmap subfield of the EML Control field of the EML Operating Mode Notification frame (see 9.6.38.8 (EML Operating Mode Notification frame details)) by setting the bit positions corresponding to the link IDs of these links in the EMLMR Link Bitmap subfield to 1. Wi-Fi 7 Draft Standard at 613.
25. The method of claim 1, wherein the processing interface is configured to, after the circuitry has been connected to the application interface and when the wireless networking device is being used, in	<i>See claim 1, above.</i> In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has configured the processing interface to, after the circuitry has been connected to the application interface and when the wireless networking device is being used, operate in a manner transparent to any

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
a manner transparent to any layer of the wireless networking device above the processing interface,	layer of the wireless networking device above the processing interface. <i>See</i> element 1.g of claim 1, above.
[25.a] (a) identify at least one first portion of bandwidth available for communication of the second wireless transceiver, the identified at least one first portion of the second wireless transceiver comprising a set of given resources,	In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has configured the processing interface to identify at least one first portion of bandwidth available for communication of the second wireless transceiver, the identified at least one first portion of the second wireless transceiver comprising a set of given resources. As described with respect to element 1.i of claim 1, Samsung has configured the processing interface to identify at least one first portion of the first actual bandwidth of the first wireless transceiver, the identified at least one first portion comprising a set of given resources. The processing interface may do so using, for example, information regarding bandwidth availabilities that is communicated to the virtual MAC and a puncturing pattern. <i>See</i> element 1.i of claim 1, above. Using the same mechanism, the processing interface may identify at least one first portion of bandwidth available for communication of the second wireless transceiver.
[25.b] (b) evaluate whether any of the given resources of the at least one first identified portions of the first and second wireless transceivers are not unavailable for communication,	In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has configured the processing interface to evaluate whether any of the given resources of the at least one first identified portions of the first and second wireless transceivers are not unavailable for communication. As described with respect to element 1.j of claim 1, above, the processing interface may evaluate whether any of the given resources of the first identified actual bandwidth portion are unavailable for communication. The processing interface may do so using, for example, information regarding bandwidth availabilities that is communicated to the virtual MAC and a puncturing pattern. <i>See</i> element 1.j of claim 1, above. Using the same mechanism, the processing interface may evaluate whether any of the given resources of the at least one first identified portions of the first and second wireless transceivers are not unavailable for communication.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
[25.c] (c) use the first wireless transceiver to transmit the first data stream to the recipient, without requiring disassociation of either or both of the first and second associations, using a specific subset of frequencies corresponding to the given resources of the identified at least one first bandwidth portion of the first wireless transceiver that are not unavailable for communication to thereby at least partially satisfy the first wireless bandwidth requirement of the first application, and	In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has configured the processing interface to use the first wireless transceiver to transmit the first data stream to the recipient, without requiring disassociation of either or both of the first and second associations, using a specific subset of frequencies corresponding to the given resources of the identified at least one first bandwidth portion of the first wireless transceiver that are not unavailable for communication to thereby at least partially satisfy the first wireless bandwidth requirement of the first application. <i>See element 1.k of claim 1, above.</i>
[25.d] (d) use the second wireless transceiver to receive a second data stream from the recipient at least partially simultaneously with the first data stream being transmitted to the recipient from the first wireless transceiver, without requiring disassociation of either or both of the first and second associations, using a specific subset of frequencies corresponding to only the given resources of the identified at least one first bandwidth portion of the second wireless transceiver that are not	In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has configured the processing interface to use the second wireless transceiver to receive a second data stream from the recipient at least partially simultaneously with the first data stream being transmitted to the recipient from the first wireless transceiver, without requiring disassociation of either or both of the first and second associations, using a specific subset of frequencies corresponding to only the given resources of the identified at least one first bandwidth portion of the second wireless transceiver that are not unavailable for communication to thereby at least partially satisfy a second wireless bandwidth requirement associated with the second data stream. The Galaxy S24 Ultra, when operating as an AP MLD or a non-AP MLD, receives data in accordance with negotiated TID-to-Link mapping procedures. <i>See elements 1.a, 1.k, and 1.l of claim 1.</i>

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
unavailable for communication to thereby at least partially satisfy a second wireless bandwidth requirement associated with the second data stream; and	For example, two peer MLDs may negotiate a TID-to-Link Mapping (TTLM). The two MLDs perform uplink and downlink operations in accordance with the negotiated TTLM. Once an MLD has successfully negotiated a TTLM with a peer MLD, both the MLD and the peer MLD shall update UL and/or DL TTLM information according to the negotiated TTLM. In case TTLM of a specific TID is missing in the negotiation, the most recent TTLM of this TID shall remain unchanged and valid unless it is successfully updated according to the procedure defined in 35.3.7.1 (General). If an MLD has failed to negotiate a TTLM with a peer MLD, the most recent TTLM of each of the TIDs shall remain unchanged and valid unless it is successfully updated according to the procedure defined in 35.3.7.2.1 (General). Wi-Fi 7 Draft Standard at 569. When an MLD has successfully negotiated with a peer MLD an UL and/or DL TTLM in which the bit position i of the Link Mapping Of TID n field in the TID-To-Link Mapping element in the (Re)Association Request frame or TID-To-Link Mapping Request frame is set to 0, TID n shall not be mapped to the link associated with the link ID i and therefore an MPDU corresponding to TID n, with exceptions for QoS Null frame as specified in 35.3.7.2.1 (General), shall not be scheduled for transmission on the link associated with link ID i in the UL and/or DL based on the Direction subfield in the TID-To-Link Mapping element. Wi-Fi 7 Draft Standard at 570. Additionally, the data stream is received by the processing interface. As shown below, data transmitted to an MLD, such as the Galaxy S24 Ultra, is transmitted through the LMAC, the UMAC, and to the LLC sublayer via the MAC SAP. During reception, MPDUs originating from different PHY SAPs first go through an MLD lower MAC entity, followed by a merging process (first-in first-out), and then go through the rest of the processes in the right-hand side of Figure 5-2a (MAC data plane architecture for an MLD exchanging individually addressed Data frames with a peer MLD). Then, one or more MSDUs are delivered to the LLC sublayer via the MAC SAP or to the DS via the DSAF. If an MSDU arrives at a disabled IEEE 802.1X Controlled/Uncontrolled Port and the MSDU does not represent an IEEE 802.1X frame, then the MSDU is discarded. Wi-Fi 7 Draft Standard at 81.

Exhibit G

US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra




Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	Fig. 5-2a, Wi-Fi 7 Draft Standard at 82 (emphasis added). As a particular example, the Galaxy S24 Ultra can operate using a simultaneous transmit and receive (STR) mode. • Android - Android 13 first support, but Android 14 is better (link reconfiguration, use MLD in roaming algorithm) - Pixel 9 - STR MLMR (2.4/5/6) and EMLSR Wi-Fi 7 (802.11be) with 2.4GHz+5GHz+6GHz, 2x2+2x2 MIMO - Pixel 8 - STR MLMR (2.4 + 5/6) and EMLSR (- Samsung S24 Ultra - STR MLMR (2.4 + 5/6) and EMLSR - One Plus 11 - STR MLMR (2.4 + 5/6) and EMLSR https://www.redimadrid.es/files/2024-7-WiFi7-AIOps.pdf at 16 (emphasis added).

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung’s Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	Wi-Fi CERTIFIED 7™ (continued) MCS 8-9 Rx MCS 8-9 Tx MCS 10-11 Rx MCS 10-11 Tx MCS 12-13 Rx MCS 12-13 Tx Multi-link reconfiguration – AP removal Multi-link reconfiguration – AP restart Multi-RU Operating mode indication Operating mode indication for 320 MHz Static puncturing STR (Simultaneous Transmit and Receive) SU-MIMO Triggered uplink access optimization UL MU-MIMO UL OFDMA Wi-Fi CERTIFIED Certificate for Qualcomm FastConnect 7800 Mobile Connectivity System, Cert. I.D. WFA127693 (2024) (emphasis added). In STR mode, the Galaxy S24 Ultra can, for example, use one of its wireless transceivers for transmitting data over a first link and simultaneously use another of its wireless transceivers for receiving data over a second link. The two links used simultaneously constitute an STR link pair.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	35.3.16.3 Simultaneous transmit and receive (STR) operation When a pair of links on which an MLD operates is an STR link pair, a STA that is affiliated with the MLD and that is operating on a link in that STR link pair shall access the WM on that link by following the rules defined in 10.3 (DCF) and 10.23.2 (HCF contention based channel access (EDCA)) regardless of any activity occurring on the other link within that STR link pair, unless explicitly stated otherwise. All pairs of links for an AP MLD that is not an NSTR mobile AP MLD and that operates on more than one link shall be STR link pairs. NOTE—If an AP MLD that is not an NSTR mobile AP MLD operates on only one link, any STR requirements and capabilities that correspond to a link pair no longer apply. An example of an AP MLD and a non-AP MLD operating over an STR link pair is shown in AH.14.1 (Example of MLD operation over an STR link pair). Wi-Fi 7 Draft Standard at 600. As shown in Figure AH-48 below, the Galaxy S24 Ultra may use an STR link pair to transmit data with one transceiver and simultaneously receive data with another transceiver. AH.14.1 Example of MLD operation over an STR link pair Figure AH-48 (Channel access of two MLDs over an STR link pair) shows an example of an AP MLD and a non-AP MLD that are operating over an STR link pair and that are contending for access to the WM and subsequent frame exchanges between two MLDs on those links. After the AP MLD has performed an ML setup with the non-AP MLD to set up link 1 and link 2 successfully and the links are enabled, then AP 2 can receive data frames from non-AP STA 2 on link 2, while AP 1 contends for the WM and then transmits data frames to non-AP STA 1 on link 1 after it obtains a TXOP. Wi-Fi 7 Draft Standard at 1080-81.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung’s Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra Figure AH-48—Channel access of two MLDs over an STR link pair Wi-Fi 7 Draft Standard at 1081. The STR mode specified in the standards delineates two types of STR modes – asynchronous and synchronous. When the Galaxy S24 Ultra uses asynchronous STR, there is at least some partial overlap between the reception and transmission of data streams. When the Galaxy S24 Ultra uses synchronous STR, then there is full overlap between the reception and transmission of data streams. This is illustrated in the example below.
----------------	---

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung’s Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	Asynchronous Multi-Link The diagram illustrates asynchronous multi-link operation between two links, Link 1 and Link 2. Link 1 starts with a hatched preamble, followed by Downlink DATA (yellow), MU ACK (grey), a second hatched preamble, a Trigger Frame (TF, grey), Uplink DATA (yellow), and BA (grey). Link 2 starts with a hatched preamble, followed by Downlink DATA (yellow and red), MU ACK (grey). A 'Preamble' label points to the start of Link 2's transmission. A 'Trigger Frame' label points to the TF in Link 1's transmission. Synchronous Multi-Link The diagram illustrates synchronous multi-link operation between two links, Link 1 and Link 2. Both links start with a hatched preamble, followed by Downlink DATA (yellow), MU ACK (grey), a second hatched preamble, a Trigger Frame (TF, grey), Uplink DATA (yellow), and BA (grey). The transmissions on both links are aligned in time. FIGURE 8. Asynchronous vs. synchronous multi-link operation [40]. Abdalfahid, Alsadg A., et al., <i>Multi-Link Operation in IEEE802.11be Extremely High Throughput: A Survey</i>, 12 IEEE Access 46891, 46898 (2024).

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
[25.e] wherein, after the circuitry has been connected to the application interface and when the wireless networking device is being used, the wireless networking device's utilization of the at least one first bandwidth portions of the first and second wireless transceivers does not prevent any wireless networking device from utilizing a range of frequencies corresponding to the remaining portion of the bandwidth availabilities of the first and second wireless transceivers for data transmission or reception purposes at the same time that data is being transmitted from or received by the first and second wireless transceivers.	In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has configured the processing interface such that, after the circuitry has been connected to the application interface and when the wireless networking device is being used, the wireless networking device's utilization of the at least one first bandwidth portions of the first and second wireless transceivers does not prevent any wireless networking device from utilizing a range of frequencies corresponding to the remaining portion of the bandwidth availabilities of the first and second wireless transceivers for data transmission or reception purposes at the same time that data is being transmitted from or received by the first and second wireless transceivers. As described in the Wi-Fi 7 Draft Standard, an AP or non-AP MLD like the Galaxy S24 Ultra will use each of the first and second wireless transceivers to communicate via the RUs or MRUs that have been respectively assigned. The Galaxy S24 Ultra is configured for Multi-user Multiple Input Multiple Output (MU-MIMO) procedures, as well as Orthogonal Frequency Division Multiple Access (OFDMA) procedures. The EHT PHY provides support for DL OFDMA, UL OFDMA, DL MU-MIMO, and UL MU-MIMO. Both DL MU-MIMO and UL MU-MIMO transmissions are supported on both the entire PPDU bandwidth and portions of the PPDU bandwidth, with the assigned resource unit of size greater than or equal to 242 tones. On a resource unit utilizing MU-MIMO transmission, there is support for up to 8 users with up to 4 spatial streams per user with the total number of spatial streams across all users not exceeding 8. The EHT PHY also supports preamble puncturing of an EHT MU PPDU for both OFDMA and non-OFDMA. Wi-Fi 7 Draft Standard at 701.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	Wi-Fi CERTIFIED 7™ (continued) MCS 8-9 Rx MCS 8-9 Tx MCS 10-11 Rx MCS 10-11 Tx MCS 12-13 Rx MCS 12-13 Tx Multi-link reconfiguration – AP removal Multi-link reconfiguration – AP restart Multi-RU Operating mode indication Operating mode indication for 320 MHz Static puncturing STR (Simultaneous Transmit and Receive) SU-MIMO Triggered uplink access optimization UL MU-MIMO UL OFDMA Wi-Fi CERTIFIED Certificate for Qualcomm FastConnect 7800 Mobile Connectivity System, Cert. I.D. WFA127693 (2024) (emphasis added). Further, testing of the Galaxy S24 Ultra indicates that the wireless networking device's utilization of identified bandwidth portions does not prevent any wireless networking device from utilizing a range of frequencies corresponding to remaining portions of bandwidth availability. For example, when one MLD, a Galaxy S25 Ultra, was used to transmit video data to another MLD, a Galaxy S24 Ultra, via an AP using portions of available bandwidth, other bandwidth portions remained available for use by the S24 Ultra, the S25 Ultra, and other devices.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	The screenshots below taken from the Galaxy S24 Ultra and Galaxy S25 Ultra devices show connections to the AP using the same three channels: a 20 MHz channel (“Ch 9”) of the 2.4 GHz frequency band, a 160 MHz channel (“Ch 104”) of the 5 GHz frequency band, and a 320 MHz channel (“Ch 85”) of the 6 GHz frequency band.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra


USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	 The image displays two side-by-side screenshots of the WiFiman application interface on Samsung Galaxy smartphones. Both screens show the configuration for the 'ASUSZENWIFI2' network, which is set to Channel 9 (85, 104) and uses WPA2-PSK / WPA3-SAE / WPS security. The interface lists three frequency bands: 2.4 GHz, 5 GHz, and 6 GHz, each with a 'CONNECTED' status and a signal strength indicator. The left screenshot (Galaxy S24 Ultra) shows signal strengths of -44 dBm for 2.4 GHz (Ch: 9, 20 MHz), -60 dBm for 5 GHz (Ch: 104, 160 MHz), and -64 dBm for 6 GHz (Ch: 85, 320 MHz). The right screenshot (Galaxy S25 Ultra) shows signal strengths of -59 dBm for 2.4 GHz (Ch: 9, 20 MHz), -61 dBm for 5 GHz (Ch: 104, 160 MHz), and -68 dBm for 6 GHz (Ch: 85, 320 MHz). Both screens also show a battery level of 99% and the time 2:16. WiFiman application screenshot taken on Galaxy S24 Ultra showing associations on three frequency bands (Left); WiFiman application screenshot taken on Galaxy S25 Ultra showing associations on three frequency bands (Right).

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	As shown below, the Galaxy S24 Ultra and Galaxy S25 Ultra used only a portion of available bandwidth to communicate the video stream, such that other devices were not impeded from using available bandwidth of the 2.4 GHz, 5 GHz, or 6 GHz transceivers.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra



USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	 2:22 98% < Connection information Link status L2 status L3 status ASUSZENWIFI2 06:28:aa:6c:c2:40 [MLD] RSSI [2.4GHz] Not in use [5GHz] -57 dBm [6GHz] Not in use Channel utilization [6GHz] Not in use [5GHz] 2% (6/255) Link speed [2.4GHz] Tx=154 Mbps / Rx=68 Mbps [5GHz] Tx=576 Mbps / Rx=1729 Mbps [6GHz] Tx=1297 Mbps / Rx=2882 Mbps  2:22 99 < Connection information Link status L2 status L3 status ASUSZENWIFI2 06:28:aa:6c:c2:40 [MLD] RSSI [2.4GHz] Not in use [5GHz] -66 dBm [6GHz] -65 dBm Channel utilization [6GHz] Not in use [5GHz] 2% (6/255) Link speed [2.4GHz] Tx=1729 Mbps / Rx=2882 Mbps [5GHz] Tx=1729 Mbps / Rx=1441 Mbps [6GHz] Tx=0 Mbps / Rx=0 Mbps WiFiman application screenshot taken on Galaxy S24 Ultra during data reception (Left); WiFiman application screenshot taken on Galaxy S25 Ultra during data transmission (Right).

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	Thus, when operating as an AP MLD or a non-AP MLD, the Galaxy S24 Ultra is configured such that the wireless networking device's utilization of the first available bandwidth portion of the first wireless transceiver does not prevent other wireless networking devices from utilizing a range of frequencies corresponding to the remaining portion of the bandwidth availability of the first wireless transceiver for data transmission purposes at the same time that the first bandwidth portion is being used for data transmission purposes.
26. The method of claim 25, wherein the second data stream is received by the second wireless transceiver substantially simultaneously with the transmission of the first data stream from the first wireless transceiver.	<i>See claim 25, above.</i> In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has performed the method of claim 25, wherein the second data stream is received by the second wireless transceiver substantially simultaneously with the transmission of the first data stream from the first wireless transceiver. The Galaxy S24 Ultra can operate using a simultaneous transmit and receive (STR) mode. <i>See claim 25, above.</i> In the STR mode, the processing interface may operate its links synchronously or asynchronously. When the Galaxy S24 Ultra uses asynchronous STR, there is at least some partial overlap in the communication of data on separate links. When the Galaxy S24 Ultra uses synchronous STR, then there is full overlap in the communication of data on separate links. This is illustrated in the example below.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung’s Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	MLO-STR involves two schemes, asynchronous and synchronous transmission as illustrated in Fig 8. In asynchronous transmission, each station (STA) in a MLD accesses its link independently, allowing simultaneous uplink and downlink frames across networks [20], [26]. This suits Synchronous Transmit-Receive (STR) MLDs but impedes non-STR MLDs due to interference [81]. Synchronous multi-link operation avoids the problem of power leakage from a transmitting affiliated device to the others at the cost of reduced throughput caused by more rare channel access. While initially designed for non-STR MLDs, this approach accommodates both STR and non-STR setups, reducing RF power leakage between links. However, considering idle channel requirements, asynchronous transmission might be more efficient for multi-channel utilization [20], [40]. Abdalfahid, Alsadg A., <i>et al.</i>, <i>Multi-Link Operation in IEEE802.11be Extremely High Throughput: A Survey</i>, 12 IEEE Access 46891, 46897 (2024).

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	Asynchronous Multi-Link Trigger Frame Link 1: Preamble, Downlink DATA, MU ACK, TF, Uplink DATA, BA Link 2: Preamble, Downlink DATA, MU ACK Synchronous Multi-Link Link 1: Preamble, Downlink DATA, MU ACK, TF, Uplink DATA, BA Link 2: Preamble, Downlink DATA, MU ACK, TF, Uplink DATA, BA FIGURE 8. Asynchronous vs. synchronous multi-link operation [40]. Abdalfahid, Alsadg A., et al., <i>Multi-Link Operation in IEEE802.11be Extremely High Throughput: A Survey</i>, 12 IEEE Access 46891, 46898 (2024).
27. The method of claim 25, wherein the start of the reception of the second data stream by the second wireless transceiver is substantially simultaneous with the start of the transmission of the first data stream from the first wireless transceiver.	<i>See claim 25, above.</i> In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has performed the method of claim 25, wherein the start of the reception of the second data stream by the second wireless transceiver is substantially simultaneous with the start of the transmission of the first data stream from the first wireless transceiver. The Galaxy S24 Ultra can operate using a simultaneous transmit and receive (STR) mode. <i>See claim 25, above.</i> In the STR mode, the processing interface may operate its links synchronously or asynchronously. When the Galaxy S24 Ultra uses asynchronous STR, there is at least some

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	partial overlap in the communication of data on separate links. When the Galaxy S24 Ultra uses synchronous STR, then there is full overlap in the communication of data on separate links. This is illustrated in the example below. MLO-STR involves two schemes, asynchronous and synchronous transmission as illustrated in Fig 8. In asynchronous transmission, each station (STA) in a MLD accesses its link independently, allowing simultaneous uplink and downlink frames across networks [20], [26]. This suits Synchronous Transmit-Receive (STR) MLDs but impedes non-STR MLDs due to interference [81]. Synchronous multi-link operation avoids the problem of power leakage from a transmitting affiliated device to the others at the cost of reduced throughput caused by more rare channel access. While initially designed for non-STR MLDs, this approach accommodates both STR and non-STR setups, reducing RF power leakage between links. However, considering idle channel requirements, asynchronous transmission might be more efficient for multi-channel utilization [20], [40]. Abdalfahid, Alsadg A., <i>et al.</i>, <i>Multi-Link Operation in IEEE802.11be Extremely High Throughput: A Survey</i>, 12 IEEE Access 46891, 46897 (2024).

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	Asynchronous Multi-Link Trigger Frame Link 1: Preamble, Downlink DATA, MU ACK, TF, Uplink DATA, BA Link 2: Preamble, Downlink DATA, MU ACK Synchronous Multi-Link Link 1: Preamble, Downlink DATA, MU ACK, TF, Uplink DATA, BA Link 2: Preamble, Downlink DATA, MU ACK, TF, Uplink DATA, BA FIGURE 8. Asynchronous vs. synchronous multi-link operation [40]. Abdalfahid, Alsadg A., <i>et al.</i>, <i>Multi-Link Operation in IEEE802.11be Extremely High Throughput: A Survey</i>, 12 IEEE Access 46891, 46898 (2024). As shown in the synchronous multi-link example above, for example, the start of transmission over each link is substantially simultaneous.
28. The method of claim 25, wherein the end of the reception of the second data stream by the second wireless transceiver is substantially simultaneous with the end of the transmission of the first data stream from the first wireless transceiver.	<i>See claim 25, above.</i> In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has performed the method of claim 25, wherein the end of the reception of the second data stream by the second wireless transceiver is substantially simultaneous with the end of the transmission of the first data stream from the first wireless transceiver. The Galaxy S24 Ultra can operate using a simultaneous transmit and receive (STR) mode. <i>See claim 25, above.</i>

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	In the STR mode, the processing interface may operate its links synchronously or asynchronously. When the Galaxy S24 Ultra uses asynchronous STR, there is at least some partial overlap in the communication of data on separate links. When the Galaxy S24 Ultra uses synchronous STR, then there is full overlap in the communication of data on separate links. This is illustrated in the example below. MLO-STR involves two schemes, asynchronous and synchronous transmission as illustrated in Fig 8. In asynchronous transmission, each station (STA) in a MLD accesses its link independently, allowing simultaneous uplink and downlink frames across networks [20], [26]. This suits Synchronous Transmit-Receive (STR) MLDs but impedes non-STR MLDs due to interference [81]. Synchronous multi-link operation avoids the problem of power leakage from a transmitting affiliated device to the others at the cost of reduced throughput caused by more rare channel access. While initially designed for non-STR MLDs, this approach accommodates both STR and non-STR setups, reducing RF power leakage between links. However, considering idle channel requirements, asynchronous transmission might be more efficient for multi-channel utilization [20], [40]. Abdalhafid, Alsadg A., <i>et al.</i>, <i>Multi-Link Operation in IEEE802.11be Extremely High Throughput: A Survey</i>, 12 IEEE Access 46891, 46897 (2024).

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	Asynchronous Multi-Link Synchronous Multi-Link FIGURE 8. Asynchronous vs. synchronous multi-link operation [40]. Abdalfahid, Alsadg A., <i>et al.</i>, <i>Multi-Link Operation in IEEE802.11be Extremely High Throughput: A Survey</i>, 12 IEEE Access 46891, 46898 (2024). As shown in the synchronous multi-link example above, for example, the start of transmission over each link is substantially simultaneous.
29. The method of claim 25, wherein the processing interface is configured to, after the circuitry has been connected to the application interface and when the wireless networking device is being used, in a manner transparent to any layer of the wireless networking device above the processing interface,	<i>See claim 25, above.</i> In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has configured the processing interface such that, after the circuitry has been connected to the application interface and when the wireless networking device is being used, the processing interface operates in a manner transparent to any layer of the wireless networking device above the processing interface. <i>See element 1.g of claim 1, above.</i>

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
[29.a] (a) identify at least one second portion of bandwidth available for communication of the first wireless transceiver, the identified at least one second portion of the first second wireless transceiver comprising a set of given resources,	In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has configured the processing interface to identify at least one second portion of bandwidth available for communication of the first wireless transceiver, the identified at least one second portion of the first second wireless transceiver comprising a set of given resources. As described with respect to element 1.i of claim 1, above, the processing interface may identify at least one first portion of the first actual bandwidth of the first wireless transceiver, the identified at least one first portion comprising a set of given resources. The processing interface may do so using, for example, information regarding bandwidth availabilities that is communicated to the virtual MAC and a puncturing pattern. <i>See</i> element 1.i of claim 1, above. Using the same mechanism, the processing interface may identify at least one second portion of bandwidth available for communication of the first wireless transceiver.
[29.b] (b) evaluate whether any of the given resources of the at least one first and identified portions of the first wireless transceiver are not unavailable for communication, and	In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has configured the processing interface to evaluate whether any of the given resources of the at least one first and identified portions of the first wireless transceiver are not unavailable for communication. As described with respect to element 1.j of claim 1, above, the processing interface may evaluate whether any of the given resources of the first identified actual bandwidth portion are unavailable for communication. The processing interface may do so using, for example, information regarding bandwidth availabilities that is communicated to the virtual MAC and a puncturing pattern. <i>See</i> element 1.j of claim 1, above. Using the same mechanism, the processing interface may evaluate whether any of the given resources of the at least one first and identified portions of the first wireless transceiver are not unavailable for communication.
[29.c] (c) use the first wireless transceiver to transmit the first data	In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has configured the processing interface to use the first wireless transceiver to transmit the first data stream to the

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
stream to the recipient, without requiring disassociation of either or both of the first and second associations, using a specific subset of frequencies corresponding to the given resources of the identified at least one first and second bandwidth portion of the first wireless transceiver that are not unavailable for communication to thereby at least partially satisfy the first wireless bandwidth requirement of the first application.	recipient, without requiring disassociation of either or both of the first and second associations, using a specific subset of frequencies corresponding to the given resources of the identified at least one first and second bandwidth portion of the first wireless transceiver that are not unavailable for communication to thereby at least partially satisfy the first wireless bandwidth requirement of the first application. When the Galaxy S24 Ultra operates as an AP MLD or a non-AP MLD, its processing interface instructs the actual MAC and actual PHY to transmit data packets using primitives. These instructions specify the chosen link and the allocated RU/MRU configuration. Based on the instructions, the actual PHY layer segments data packets into units, modulates the data units using appropriate techniques for transmission over the designated link, and transmits the modulated data units using the allocated radio frequencies on the chosen transceiver. For example, the processing interface may use certain vectors, including TXVECTOR, RXVECTOR, PHYCONFIG_VECTOR, and TRIG_VECTOR to instruct the PHY. 36.2 EHT PHY service interface 36.2.1 Introduction The EHT PHY provides an interface to the EHT MAC through an extension of the generic PHY service interface defined in 8.3.4 (Basic service and options). The interface includes TXVECTOR, RXVECTOR, PHYCONFIG_VECTOR, and TRIGVECTOR. The EHT MAC uses the TXVECTOR to supply the EHT PHY with per-PPDU transmit parameters. The EHT PHY uses the RXVECTOR to inform the EHT MAC of the received PPDU parameters. The EHT MAC uses the PHYCONFIG_VECTOR to configure the EHT PHY for operation that is independent of PPDU transmission or reception. The EHT MAC uses the TRIGVECTOR to configure the EHT PHY to receive EHT TB PPDU's over each assigned RU or MRU. Wi-Fi 7 Draft Standard at 708, 709-23 (listing TXVECTOR and RXVECTOR parameters).

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	In all options, in order to transmit data, the MAC generates a PHY-TXSTART.request primitive, which causes the PHY entity to respond with a PHY-TXSTART.confirm primitive and enter the transmit state. Further, the PHY is set to operate at the appropriate frequency through station management via the PLME, as specified in 36.4 (EHT PLME). Other transmit parameters, such as EHT-MCS, coding types, and transmit power, are set via the PHY-SAP using the PHY-TXSTART.request primitive (containing TXVECTOR), as described in 36.2.2 (TXVECTOR and RXVECTOR parameters). After transmitting a PPDU that carries a Trigger frame, the MAC sublayer issues a PHY-TRIGGER.request with a TRIGVECTOR parameter that provides the PHY entity with the information needed to demodulate the expected EHT TB PPDU response. The remainder of the subclause applies to the first two paths. Wi-Fi 7 Draft Standard at 940. The processing interface of the Galaxy S24 Ultra evaluates channel information, such as a puncturing pattern, to determine what portions of channels are unavailable for transmission or reception purposes. Additionally, the Galaxy S24 Ultra, when operating as an AP MLD or a non-AP MLD, enables the use of TID-to-link mapping in accordance with the Wi-Fi 7 Draft Standard. For example, when operating as an AP MLD, the SME and UMAC (through a Resource Allocation Manager) may determine TID-to-link mapping and assign RUs/MRUs based on traffic needs and available resources on each link. Likewise, when operating as a non-AP MLD, the SME and UMAC may monitor and evaluate traffic needs and available resources to provide recommendation information to an AP MLD device assigning RUs/MRUs. Further, when operating as a non-AP MLD, the Galaxy S24 Ultra follows the TID-to-link mapping determined by the AP. Thus, the system architecture solves limitations of multi-band to enable MLO in IEEE 802.11be to be based on the processing interface's unique understanding of traffic priorities, queue lengths, and real-time network status enabling intelligent TID-to-link mapping. This mapping determines which traffic (<i>e.g.</i>, identified by TID) should be directed to which links (<i>i.e.</i>, associated bandwidth resources).

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	As a particular example, when operating as an AP MLD, the SME and UMAC allocate appropriate RU(s)/MRU(s) based on the data requirements of the specific traffic type mapped to a link. The UMAC considers factors like the amount of data to be transmitted for a particular TID and the channel bandwidth available on the chosen link. It can choose to allocate a single RU for smaller data packets or low-priority traffic, or allocate multiple RUs combined into an MRU for larger data transfers or high-priority traffic requiring more bandwidth. Assigning RUs or MRUs is an integral part of TID-to-link mapping. Likewise, when operating as a non-AP MLD, the SME and UMAC direct packets to links based on the TID-to-link mapping identified by an AP. Multiple RUs can be combined for simultaneous transmission to satisfy a bandwidth requirement. 36.3.2.2 Subcarriers and resource allocation for multiple RUs 36.3.2.2.1 General The EHT PHY supports the use of MRU in an EHT PPDU. An MRU consists of selected combinations of multiple RUs of 26-tone RU, 52-tone RU, 106-tone RU, 242-tone RU, 484-tone RU, 996-tone RU, and 2×996-tone RU. The tone indices of the various RUs for different EHT PPDU bandwidths are defined in 36.3.2.1 (Subcarriers and resource allocation in EHT PPDUs). RUs that are the same size as or larger than 242-tone RUs are defined as large size RUs and RUs that are smaller than 242-tone RUs are defined as small size RUs. Small size RUs can only be combined with small size RUs to form small size MRUs. The supported small size MRUs are defined in 36.3.2.2.2 (Small size MRUs). Large size RUs can only be combined with large size RUs to form large size MRUs. The supported large size MRUs are defined in 36.3.2.2.3 (Large size MRUs).

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung’s Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	Wi-Fi 7 Draft Standard at 740. The Galaxy S24 Ultra is configured for multi-RU operation, thus allowing for the aggregation of multiple bandwidth portions for simultaneous transmission or reception. Wi-Fi CERTIFIED 7™ (continued) - MCS 8-9 Rx - MCS 8-9 Tx - MCS 10-11 Rx - MCS 10-11 Tx - MCS 12-13 Rx - MCS 12-13 Tx - Multi-link reconfiguration – AP removal - Multi-link reconfiguration – AP restart Multi-RU - Operating mode indication - Operating mode indication for 320 MHz - Static puncturing - STR (Simultaneous Transmit and Receive) - SU-MIMO - Triggered uplink access optimization - UL MU-MIMO - UL OFDMA Wi-Fi CERTIFIED Certificate for Qualcomm FastConnect 7800 Mobile Connectivity System, Cert. I.D. WFA127693 (2024) (emphasis added). As described with respect to element 1.a of claim 1, the Galaxy S24 Ultra’s processing interface is provided by the Qualcomm Snapdragon 8 Gen 3 System on a Chip processor that

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	includes the FastConnect 7800 connectivity system contained within the Galaxy S24 Ultra. The Qualcomm FastConnect 7800 connectivity system is compliant with Wi-Fi 7 standards. Leading Wi-Fi 7, premium Wi-Fi 6/6E, and advanced Bluetooth audio come together in this powerful and versatile connectivity system to unlock extreme performance for mobile, compute, and XR experiences. The Qualcomm® FastConnect™ 7800 Mobile Connectivity System is an advanced 14nm Wi-Fi and Bluetooth® Connectivity system delivering ultra-high speeds (up to 5.8 Gbps*), sustained low latency (2 ms), and premium Bluetooth audio. While maintaining compliance with the latest Wi-Fi 6/6E and Wi-Fi 7 standards, FastConnect 7800 is packed with sophisticated innovation that goes beyond standard benchmarks. High Band Simultaneous Multi-Link Wi-Fi technology uniquely harnesses the potential of 5 and 6GHz bands for multiple links of high band performance for throughput hungry and latency sensitive applications, eliminating dependence on comparatively narrow and congested 2.4GHz band. https://www.qualcomm.com/products/technology/wi-fi/fastconnect/fastconnect-7800. As demonstrated below, the Qualcomm FastConnect 7800 connectivity system allows the Galaxy S24 Ultra to aggregate resources within, for example, the 5 GHz band.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung’s Galaxy S24 Ultra


USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	In regions and environments where 6GHz is not available  https://www.qualcomm.com/products/technology/wi-fi/fastconnect/fastconnect-7800. This evidences that devices, such as the Galaxy S24 Ultra phone, for example, can aggregate a 160 MHz channel in the 5 GHz band with an 80 MHz channel in the 5 GHz band. Additionally, the processing interface may transmit a data stream using the first wireless transceiver without requiring disassociation of the recipient from any of the first and second actual MAC and PHY interfaces. As described with respect to element 1.h, MLO allows a non-AP MLD and an AP MLD to establish multiple links between their

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	corresponding STAs. Data may be transmitted or received on one of the established links without requiring disassociation of the other established links. 35.3.16 ML channel access 35.3.16.1 General A STA that is affiliated with an MLD shall contend for the WM on its link independently from the other STA(s) affiliated with the same MLD, unless explicitly stated otherwise in the subclauses below. Wi-Fi 7 Draft Standard at 598. Additionally, the processing interface may use the first wireless transceiver to transmit the first data stream to the recipient, without requiring disassociation of either or both of the first and second associations, using a specific subset of frequencies corresponding to the given resources of the identified at least one first and second bandwidth portion of the first wireless transceiver that are not unavailable for communication while using the second wireless transceiver to receive a second data stream from the recipient at least partially simultaneously with the first data stream being transmitted to the recipient from the first wireless transceiver, as discussed in claim 25.
30. The method of claim 29, wherein the processing interface is configured to, after the circuitry has been connected to the application interface and when the wireless networking device is being used, in a manner transparent to any layer of the wireless networking device above the processing interface,	<i>See claim 29, above.</i> In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has configured the processing interface such that, after the circuitry has been connected to the application interface and when the wireless networking device is being used, the processing interface operates in a manner transparent to any layer of the wireless networking device above the processing interface. <i>See element 1.g of claim 1, above.</i>

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
[30.a] (a) identify at least one second portion of bandwidth available for communication of the second wireless transceiver, the identified at least one second portion of the second wireless transceiver comprising a set of given resources,	In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has configured the processing interface to identify at least one second portion of bandwidth available for communication of the second wireless transceiver, the identified at least one second portion of the second wireless transceiver comprising a set of given resources. As described with respect to element 25.a of claim 25, above, the processing interface may identify at least one first portion of the second actual bandwidth of the second wireless transceiver, the identified at least one first portion comprising a set of given resources. The processing interface may do so using, for example, information regarding bandwidth availabilities that is communicated to the virtual MAC and a puncturing pattern. <i>See</i> element 25.a of claim 25, above. Using the same mechanism, the processing interface may identify at least one second portion of bandwidth of the second wireless transceiver.
[30.b] (b) evaluate whether any of the given resources of the at least one first and identified portions of the second wireless transceiver are not unavailable for communication, and	In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has configured the processing interface to evaluate whether any of the given resources of the at least one first and identified portions of the second wireless transceiver are not unavailable for communication. As described with respect to element 25.b of claim 25, above, the processing interface may evaluate whether any of the given resources of the first identified actual bandwidth portion are unavailable for communication. The processing interface may do so using, for example, information regarding bandwidth availabilities that is communicated to the virtual MAC and a puncturing pattern. <i>See</i> element 25.b of claim 25, above. Using the same mechanism, the processing interface may evaluate whether any of the given resources of the at least one first and identified portions of the second wireless transceiver are not unavailable for communication.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
[30.c] (c) use the second wireless transceiver to receive the second data stream from the recipient, without requiring disassociation of either or both of the first and second associations, using a specific subset of frequencies corresponding to the given resources of the identified at least one first and second bandwidth portion of the second wireless transceiver that are not unavailable for communication to thereby at least partially satisfy the first wireless bandwidth requirement of the second application.	In manufacturing and/or testing the Galaxy S24 Ultra, Samsung has configured the processing interface to use the second wireless transceiver to receive the second data stream from the recipient, without requiring disassociation of either or both of the first and second associations, using a specific subset of frequencies corresponding to the given resources of the identified at least one first and second bandwidth portion of the second wireless transceiver that are not unavailable for communication to thereby at least partially satisfy the first wireless bandwidth requirement of the second application. When the Galaxy S24 Ultra operates as an AP MLD or a non-AP MLD, its processing interface instructs the actual MAC and actual PHY to transmit data packets using primitives. These instructions specify the chosen link and the allocated RU/MRU configuration. Based on the instructions, the actual PHY layer segments data packets into units, modulates the data units using appropriate techniques for transmission over the designated link, and transmits the modulated data units using the allocated radio frequencies on the chosen transceiver. For example, the processing interface may use certain vectors, including TXVECTOR, RXVECTOR, PHYCONFIG_VECTOR, and TRIG_VECTOR to instruct the PHY. 36.2 EHT PHY service interface 36.2.1 Introduction The EHT PHY provides an interface to the EHT MAC through an extension of the generic PHY service interface defined in 8.3.4 (Basic service and options). The interface includes TXVECTOR, RXVECTOR, PHYCONFIG_VECTOR, and TRIGVECTOR. The EHT MAC uses the TXVECTOR to supply the EHT PHY with per-PPDU transmit parameters. The EHT PHY uses the RXVECTOR to inform the EHT MAC of the received PPDU parameters. The EHT MAC uses the PHYCONFIG_VECTOR to configure the EHT PHY for operation that is independent of PPDU transmission or reception. The EHT MAC uses the TRIGVECTOR to configure the EHT PHY to receive EHT TB PPDU's over each assigned RU or MRU.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	Wi-Fi 7 Draft Standard at 708, 709-23 (listing TXVECTOR and RXVECTOR parameters). In all options, in order to transmit data, the MAC generates a PHY-TXSTART.request primitive, which causes the PHY entity to respond with a PHY-TXSTART.confirm primitive and enter the transmit state. Further, the PHY is set to operate at the appropriate frequency through station management via the PLME, as specified in 36.4 (EHT PLME). Other transmit parameters, such as EHT-MCS, coding types, and transmit power, are set via the PHY-SAP using the PHY-TXSTART.request primitive (containing TXVECTOR), as described in 36.2.2 (TXVECTOR and RXVECTOR parameters). After transmitting a PPDU that carries a Trigger frame, the MAC sublayer issues a PHY-TRIGGER.request with a TRIGVECTOR parameter that provides the PHY entity with the information needed to demodulate the expected EHT TB PPDU response. The remainder of the subclause applies to the first two paths. Wi-Fi 7 Draft Standard at 940. The processing interface of the Galaxy S24 Ultra evaluates channel information, such as a puncturing pattern, to determine what portions of channels are unavailable for transmission or reception purposes. Additionally, the Galaxy S24 Ultra, when operating as an AP MLD or a non-AP MLD, enables the use of TID-to-link mapping in accordance with the Wi-Fi 7 Draft Standard. For example, when operating as an AP MLD, the SME and UMAC (through a Resource Allocation Manager) may determine TID-to-link mapping and assign RUs/MRUs based on traffic needs and available resources on each link. Likewise, when operating as a non-AP MLD, the SME and UMAC may monitor and evaluate traffic needs and available resources to provide recommendation information to an AP MLD device assigning RUs/MRUs. Further, when operating as a non-AP MLD, the Galaxy S24 Ultra follows the TID-to-link mapping determined by the AP. Thus, the system architecture solves limitations of multi-band to enable MLO in IEEE 802.11be to be based on the processing interface's unique understanding of traffic priorities, queue lengths, and real-time network status enabling intelligent TID-to-link mapping. This mapping determines which traffic (<i>e.g.</i>, identified by TID) should be directed to which links (<i>i.e.</i>, associated bandwidth resources).

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	As a particular example, when operating as an AP MLD, the SME and UMAC allocate appropriate RU(s)/MRU(s) based on the data requirements of the specific traffic type mapped to a link. The UMAC considers factors like the amount of data to be transmitted for a particular TID and the channel bandwidth available on the chosen link. It can choose to allocate a single RU for smaller data packets or low-priority traffic, or allocate multiple RUs combined into an MRU for larger data transfers or high-priority traffic requiring more bandwidth. Assigning RUs or MRUs is an integral part of TID-to-link mapping. Likewise, when operating as a non-AP MLD, the SME and UMAC direct packets to links based on the TID-to-link mapping identified by an AP. Multiple RUs can be combined for simultaneous reception to satisfy a bandwidth requirement. 36.3.2.2 Subcarriers and resource allocation for multiple RUs 36.3.2.2.1 General The EHT PHY supports the use of MRU in an EHT PPDU. An MRU consists of selected combinations of multiple RUs of 26-tone RU, 52-tone RU, 106-tone RU, 242-tone RU, 484-tone RU, 996-tone RU, and 2×996-tone RU. The tone indices of the various RUs for different EHT PPDU bandwidths are defined in 36.3.2.1 (Subcarriers and resource allocation in EHT PPDU). RUs that are the same size as or larger than 242-tone RUs are defined as large size RUs and RUs that are smaller than 242-tone RUs are defined as small size RUs. Small size RUs can only be combined with small size RUs to form small size MRUs. The supported small size MRUs are defined in 36.3.2.2.2 (Small size MRUs). Large size RUs can only be combined with large size RUs to form large size MRUs. The supported large size MRUs are defined in 36.3.2.2.3 (Large size MRUs).

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	Wi-Fi 7 Draft Standard at 740. The Galaxy S24 Ultra is configured for multi-RU operation, thus allowing for the aggregation of multiple bandwidth portions for simultaneous transmission or reception. Wi-Fi CERTIFIED 7™ (continued) - MCS 8-9 Rx - MCS 8-9 Tx - MCS 10-11 Rx - MCS 10-11 Tx - MCS 12-13 Rx - MCS 12-13 Tx - Multi-link reconfiguration – AP removal - Multi-link reconfiguration – AP restart Multi-RU - Operating mode indication - Operating mode indication for 320 MHz - Static puncturing - STR (Simultaneous Transmit and Receive) - SU-MIMO - Triggered uplink access optimization - UL MU-MIMO - UL OFDMA Wi-Fi CERTIFIED Certificate for Qualcomm FastConnect 7800 Mobile Connectivity System, Cert. I.D. WFA127693 (2024) (emphasis added). As described with respect to element 1.a of claim 1, the Galaxy S24 Ultra's processing interface is provided by the Qualcomm Snapdragon 8 Gen 3 System on a Chip processor that

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	includes the FastConnect 7800 connectivity system contained within the Galaxy S24 Ultra. The Qualcomm FastConnect 7800 connectivity system is compliant with Wi-Fi 7 standards. Leading Wi-Fi 7, premium Wi-Fi 6/6E, and advanced Bluetooth audio come together in this powerful and versatile connectivity system to unlock extreme performance for mobile, compute, and XR experiences. The Qualcomm® FastConnect™ 7800 Mobile Connectivity System is an advanced 14nm Wi-Fi and Bluetooth® Connectivity system delivering ultra-high speeds (up to 5.8 Gbps*), sustained low latency (2 ms), and premium Bluetooth audio. While maintaining compliance with the latest Wi-Fi 6/6E and Wi-Fi 7 standards, FastConnect 7800 is packed with sophisticated innovation that goes beyond standard benchmarks. High Band Simultaneous Multi-Link Wi-Fi technology uniquely harnesses the potential of 5 and 6GHz bands for multiple links of high band performance for throughput hungry and latency sensitive applications, eliminating dependence on comparatively narrow and congested 2.4GHz band. https://www.qualcomm.com/products/technology/wi-fi/fastconnect/fastconnect-7800. As demonstrated below, the Qualcomm FastConnect 7800 connectivity system allows the Galaxy S24 Ultra to aggregate resources within, for example, the 5 GHz band.

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra


USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	In regions and environments where 6GHz is not available  FastConnect 7800 can harness up to 240MHz of the global 5GHz band *Speed claims refer to maximum physical layer (PHY) rate https://www.qualcomm.com/products/technology/wi-fi/fastconnect/fastconnect-7800. This evidences that devices, such as the Galaxy S24 Ultra phone, for example, can aggregate a 160 MHz channel in the 5 GHz band with an 80 MHz channel in the 5 GHz band. Additionally, the processing interface may transmit a data stream using the first wireless transceiver without requiring disassociation of the recipient from any of the first and second actual MAC and PHY interfaces. As described with respect to element 1.h, MLO allows a non-AP MLD and an AP MLD to establish multiple links between their

Exhibit G
US Patent No. 12,015,933, Claims 1-8, 10-11, and 14-30 on Samsung's Galaxy S24 Ultra

USP 12,015,933	Evidence of Use in the Galaxy S24 Ultra
	corresponding STAs. Data may be transmitted or received on one of the established links without requiring disassociation of the other established links. 35.3.16 ML channel access 35.3.16.1 General A STA that is affiliated with an MLD shall contend for the WM on its link independently from the other STA(s) affiliated with the same MLD, unless explicitly stated otherwise in the subclauses below. Wi-Fi 7 Draft Standard at 598. Additionally, the processing interface may use the second wireless transceiver to receive the second data stream from the recipient, without requiring disassociation of either or both of the first and second associations, using a specific subset of frequencies corresponding to the given resources of the identified at least one first and second bandwidth portions of the second wireless transceiver that are not unavailable for communication while using the first wireless transceiver to transmit a first data stream to the recipient at least partially simultaneously with the second data stream being received from the recipient, as discussed in claim 25.