

(10) **Patent No.:** US 7,764,982 B2
(45) **Date of Patent:** Jul. 27, 2010

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,910,701	A *	10/1975	Henderson et al.	356/39
3,998,550	A	12/1976	Konishi et al.	
4,157,708	A	6/1979	Imura	
4,167,331	A	9/1979	Nielsen	
4,266,554	A	5/1981	Hamaguri	
4,446,871	A	5/1984	Imura	
4,586,513	A	5/1986	Hamaguri	
4,621,643	A	11/1986	New et al.	
4,653,498	A	3/1987	New et al.	
4,685,464	A	8/1987	Goldberger	
4,694,833	A	9/1987	Hamaguri	

(Continued)

FOREIGN PATENT DOCUMENTS

WO WO 98/43071 10/1998

(Continued)

(21) Appl. No.: 11/367,013

(22) Filed: **Mar. 1, 2006**

(65) **Prior Publication Data**

US 2006/0211924 A1 Sep. 21, 2006

Related U.S. Application Data

(60) Provisional application No. 60/657,596, filed on Mar. 1, 2005, provisional application No. 60/657,281, filed on Mar. 1, 2005, provisional application No. 60/657,268, filed on Mar. 1, 2005, provisional application No. 60/657,759, filed on Mar. 1, 2005.

(51) **Int. Cl.**
A61B 5/1455 (2006.01)

(52) **U.S. Cl.** 600/310; 600/322

(58) **Field of Classification Search** 600/310,
600/316; 356/39, 40, 41, 42, 451
See application file for complete search history.

OTHER PUBLICATIONS

Schmitt, Joseph M.; Zhou, Guan-Xiong; Miller, Justin *Measurement of Blood Hematocrit by Dual-wavelength Near-IR Photoplethysmography*, published May 1992, Proc. SPIE vol. 1641, p. 150-161, Physiological Monitoring and Early Detection Diagnostic Methods, Thomas S. Mang; Ed. (SPIE homepage), in 12 pages.

Primary Examiner—Eric F Winakur


Assistant Examiner—Etsub D Berhanu

(74) *Attorney, Agent, or Firm*—Knobbe, Martens, Olson & Bear, LLP

(57) **ABSTRACT**

A physiological sensor has light emitting sources, each activated by addressing at least one row and at least one column of an electrical grid. The light emitting sources are capable of transmitting light of multiple wavelengths and a detector is responsive to the transmitted light after attenuation by body tissue.

22 Claims, 48 Drawing Sheets



U.S. PATENT DOCUMENTS					
4,700,708 A	10/1987	New et al.	5,520,177 A	5/1996	Ogawa
4,714,341 A	12/1987	Hamaguri et al.	5,533,507 A	7/1996	Potratz
4,770,179 A	9/1988	New et al.	5,533,511 A	7/1996	Kaspari et al.
4,773,422 A	9/1988	Isaacson et al.	5,551,423 A	9/1996	Sugiura
4,781,195 A	11/1988	Martin	5,553,615 A	9/1996	Carim et al.
4,800,885 A	1/1989	Johnson	5,555,882 A	9/1996	Richardson et al.
4,832,484 A	5/1989	Aoyagi et al.	5,562,002 A	10/1996	Lalin
4,846,183 A	7/1989	Martin	5,577,500 A	11/1996	Potratz
4,863,265 A	9/1989	Flower et al.	5,584,299 A	12/1996	Sakai et al.
4,867,571 A	9/1989	Frick et al.	5,588,427 A	12/1996	Tien
4,869,254 A	9/1989	Stone et al.	5,590,649 A	1/1997	Caro et al.
4,907,876 A	3/1990	Suzuki et al.	5,590,652 A	1/1997	Inai
4,911,167 A	3/1990	Corenman et al.	5,595,176 A	1/1997	Yamaura
4,934,372 A	6/1990	Corenman et al.	5,596,992 A	1/1997	Haaland et al.
4,942,877 A	7/1990	Sakai et al.	5,602,924 A	2/1997	Durand et al.
4,955,379 A	9/1990	Hall	5,603,623 A	2/1997	Nishikawa et al.
4,960,126 A	10/1990	Conlon et al.	5,630,413 A	5/1997	Thomas et al.
4,960,128 A	10/1990	Gordon et al.	5,632,272 A	5/1997	Diab et al.
4,964,010 A	10/1990	Miyasaka et al.	5,638,816 A	6/1997	Kiani-Azarbayjany et al.
4,964,408 A	10/1990	Hink et al.	5,638,818 A	6/1997	Diab et al.
4,967,571 A	11/1990	Sporri	5,645,059 A	7/1997	Fein et al.
4,975,581 A	12/1990	Robinson et al.	5,645,060 A	7/1997	Yorkey
4,986,665 A	1/1991	Yamanishi et al.	5,645,440 A	7/1997	Tobler et al.
4,997,769 A	3/1991	Lundsgaard	5,660,567 A	8/1997	Nierlich et al.
RE33,643 E	7/1991	Isaacson et al.	5,662,106 A	9/1997	Swedlow et al.
5,033,472 A	7/1991	Sato et al.	5,676,139 A	10/1997	Goldberger et al.
5,041,187 A	8/1991	Hink et al.	5,676,141 A	10/1997	Hollub
5,054,495 A	10/1991	Uemura et al.	5,678,544 A	10/1997	DeLonzor et al.
5,058,588 A	10/1991	Kaestle et al.	5,685,299 A	11/1997	Diab et al.
5,069,213 A	12/1991	Polczynski	5,685,301 A	11/1997	Klomhaus
5,078,136 A	1/1992	Stone et al.	5,687,719 A	11/1997	Sato et al.
5,163,438 A	11/1992	Gordon et al.	5,687,722 A	11/1997	Tien et al.
5,190,040 A	3/1993	Aoyagi	5,690,104 A	11/1997	Kanemoto et al.
5,209,230 A	5/1993	Swedlow et al.	5,692,503 A	12/1997	Kuentstner
5,259,381 A	11/1993	Cheung et al.	5,697,371 A	12/1997	Aoyagi
5,267,562 A	12/1993	Ukawa et al.	5,713,355 A	2/1998	Richardson et al.
5,267,563 A	12/1993	Swedlow et al.	D393,830 S	4/1998	Tobler et al.
5,278,627 A	1/1994	Aoyagi	5,743,262 A	4/1998	Lepper, Jr. et al.
5,297,548 A	3/1994	Pologe	5,743,263 A	4/1998	Baker, Jr.
5,313,940 A	5/1994	Fuse et al.	5,746,206 A	5/1998	Mannheimer
5,331,549 A	7/1994	Crawford, Jr.	5,746,697 A	5/1998	Swedlow et al.
5,335,659 A	8/1994	Pologe et al.	5,752,914 A	5/1998	Delonzor et al.
5,337,744 A	8/1994	Branigan	5,755,226 A	5/1998	Carim et al.
5,348,004 A	9/1994	Hollub	5,758,644 A	6/1998	Diab et al.
5,351,685 A	10/1994	Potratz	5,760,910 A	6/1998	Lepper, Jr. et al.
5,355,880 A	10/1994	Thomas et al.	5,769,785 A	6/1998	Diab et al.
5,355,882 A	10/1994	Ukawa et al.	5,772,587 A	6/1998	Gratton et al.
5,361,758 A	11/1994	Hall et al.	5,779,630 A	7/1998	Fein et al.
5,368,224 A	11/1994	Richardson et al.	5,782,237 A	7/1998	Casciani et al.
D353,195 S	12/1994	Savage et al.	5,782,756 A	7/1998	Mannheimer
D353,196 S	12/1994	Savage et al.	5,782,757 A	7/1998	Diab et al.
5,385,143 A	1/1995	Aoyagi	5,785,659 A	7/1998	Caro et al.
5,387,122 A	2/1995	Goldberger et al.	5,790,729 A	8/1998	Pologe et al.
5,392,777 A	2/1995	Swedlow et al.	5,791,347 A	8/1998	Flaherty et al.
5,413,101 A	5/1995	Sugiura	5,792,052 A	8/1998	Isaacson et al.
5,421,329 A	6/1995	Casciani et al.	5,793,485 A	8/1998	Gourley
5,427,093 A	6/1995	Ogawa et al.	5,800,348 A	9/1998	Kaestle et al.
5,429,128 A	7/1995	Cadell et al.	5,800,349 A	9/1998	Isaacson et al.
5,431,170 A	7/1995	Mathews	5,803,910 A	9/1998	Potratz
5,435,309 A	7/1995	Thomas et al.	5,807,246 A	9/1998	Sakaguchi et al.
D361,840 S	8/1995	Savage et al.	5,807,247 A	9/1998	Merchant et al.
D362,063 S	9/1995	Savage et al.	5,810,723 A	9/1998	Aldrich
5,452,717 A	9/1995	Branigan et al.	5,810,724 A	9/1998	Gronvall
D363,120 S	10/1995	Savage et al.	5,810,734 A	9/1998	Caro et al.
RE35,122 E	12/1995	Corenman et al.	5,817,010 A	10/1998	Hibl
5,482,036 A	1/1996	Diab et al.	5,818,985 A	10/1998	Merchant et al.
5,490,505 A	2/1996	Diab et al.	5,823,950 A	10/1998	Diab et al.
5,490,523 A	2/1996	Isaacson et al.	5,823,952 A	10/1998	Levinson et al.
5,494,032 A	2/1996	Robinson et al.	5,827,182 A	10/1998	Raley
5,494,043 A	2/1996	O'Sullivan et al.	5,830,131 A	11/1998	Caro et al.
5,503,148 A	4/1996	Pologe et al.	5,830,137 A	11/1998	Scharf
			5,833,618 A	11/1998	Caro et al.
			5,839,439 A	11/1998	Nierlich et al.

RE36,000 E	12/1998	Swedlow et al.	6,285,895 B1	9/2001	Ristolainen et al.
5,842,979 A	12/1998	Jarman	6,285,896 B1	9/2001	Tobler et al.
5,851,178 A	12/1998	Aronow	6,298,252 B1	10/2001	Kovach et al.
5,851,179 A	12/1998	Ritson et al.	6,304,675 B1	10/2001	Osbourne et al.
5,853,364 A	12/1998	Baker, Jr. et al.	6,304,767 B1	10/2001	Soller et al.
5,857,462 A	1/1999	Thomas et al.	6,321,100 B1	11/2001	Parker
5,860,919 A	1/1999	Kiani-Azarbayjany et al.	6,330,468 B1	12/2001	Scharf
5,865,736 A	2/1999	Baker, Jr. et al.	6,334,065 B1	12/2001	Al-Ali et al.
5,876,348 A	3/1999	Sugo	6,341,257 B1	1/2002	Haaland
5,885,213 A	3/1999	Richardson et al.	6,343,224 B1	1/2002	Parker
5,890,929 A	4/1999	Mills et al.	6,349,228 B1	2/2002	Kiani et al.
5,891,024 A	4/1999	Jarman et al.	6,351,658 B1	2/2002	Middleman et al.
5,904,654 A	5/1999	Wohlmann et al.	6,356,774 B1	3/2002	Bernstein et al.
5,910,108 A	6/1999	Solenberger	6,360,114 B1	3/2002	Diab et al.
5,916,154 A	6/1999	Hobbs et al.	6,363,269 B1	3/2002	Hanna et al.
5,919,133 A	7/1999	Taylor	6,371,921 B1	4/2002	Caro et al.
5,919,134 A	7/1999	Diab	6,374,129 B1	4/2002	Chin et al.
5,921,921 A	7/1999	Potratz et al.	6,377,828 B1	4/2002	Chaiken et al.
5,934,277 A	8/1999	Mortz	6,377,829 B1	4/2002	Al-Ali
5,934,925 A	8/1999	Tobler et al.	6,388,240 B2	5/2002	Schulz et al.
5,940,182 A	8/1999	Lepper, Jr. et al.	6,393,310 B1	5/2002	Kuenstner
5,954,644 A	9/1999	Dettling	6,397,091 B2	5/2002	Diab et al.
5,978,691 A	11/1999	Mills	6,397,092 B1	5/2002	Norris et al.
5,983,122 A	11/1999	Jarman et al.	6,397,093 B1	5/2002	Aldrich
5,995,855 A	11/1999	Kiani et al.	6,408,198 B1	6/2002	Hanna et al.
5,995,856 A	11/1999	Mannheimer et al.	6,411,833 B1	6/2002	Baker, Jr. et al.
5,995,859 A	11/1999	Takahashi	6,415,166 B1	7/2002	Van Hoy et al.
5,997,343 A	12/1999	Mills et al.	6,415,233 B1	7/2002	Haaland
5,999,841 A	12/1999	Aoyagi et al.	6,415,236 B2	7/2002	Kobayashi et al.
6,002,952 A	12/1999	Diab et al.	6,430,525 B1	8/2002	Weber et al.
6,006,119 A	12/1999	Soller et al.	6,434,408 B1	8/2002	Heckel
6,011,986 A	1/2000	Diab et al.	6,441,388 B1	8/2002	Thomas et al.
6,014,576 A	1/2000	Raley	6,453,184 B1	9/2002	Hyogo et al.
6,018,673 A	1/2000	Chin et al.	6,463,310 B1	10/2002	Swedlow et al.
6,018,674 A	1/2000	Aronow	6,463,311 B1	10/2002	Diab
6,023,541 A	2/2000	Merchant et al.	6,470,199 B1	10/2002	Kopotic et al.
6,027,452 A	2/2000	Flaherty et al.	6,480,729 B2	11/2002	Stone
6,036,642 A	3/2000	Diab et al.	6,490,466 B1	12/2002	Fein et al.
6,045,509 A	4/2000	Caro et al.	6,497,659 B1	12/2002	Rafert
6,064,898 A	5/2000	Aldrich	6,501,974 B2	12/2002	Huiku
6,067,462 A	5/2000	Diab et al.	6,501,975 B2	12/2002	Diab et al.
6,068,594 A	5/2000	Schloemer et al.	6,504,943 B1	1/2003	Sweatt et al.
6,073,037 A	6/2000	Alam et al.	6,505,060 B1	1/2003	Norris
6,081,735 A	6/2000	Diab et al.	6,505,061 B2	1/2003	Larson
6,083,172 A	7/2000	Baker, Jr. et al.	6,505,133 B1	1/2003	Hanna
6,088,607 A	7/2000	Diab et al.	6,510,329 B2	1/2003	Heckel
6,094,592 A	7/2000	Yorkey et al.	6,515,273 B2	2/2003	Al-Ali
6,104,938 A	8/2000	Huiku	6,519,486 B1	2/2003	Edgar, Jr. et al.
6,110,522 A	8/2000	Lepper, Jr. et al.	6,519,487 B1	2/2003	Parker
6,112,107 A	8/2000	Hannula	6,522,398 B2	2/2003	Cadell et al.
6,122,042 A	9/2000	Wunderman et al.	6,525,386 B1	2/2003	Mills et al.
6,144,868 A	11/2000	Parker	6,526,300 B1	2/2003	Kiani et al.
6,151,516 A	11/2000	Kiani-Azarbayjany et al.	6,526,301 B2	2/2003	Larsen et al.
6,151,518 A	11/2000	Hayashi	6,528,809 B1	3/2003	Thomas et al.
6,152,754 A	11/2000	Gerhardt et al.	6,537,225 B1	3/2003	Mills
6,154,667 A	11/2000	Miura et al.	6,541,756 B2	4/2003	Schulz et al.
6,157,041 A	12/2000	Thomas et al.	6,542,764 B1	4/2003	Al-Ali et al.
6,157,850 A	12/2000	Diab et al.	6,545,652 B1 *	4/2003	Tsuji 345/82
6,165,005 A	12/2000	Mills et al.	6,546,267 B1	4/2003	Sugiura
6,184,521 B1	2/2001	Coffin, IV et al.	6,553,241 B2	4/2003	Mannheimer et al.
6,192,261 B1	2/2001	Gratton et al.	6,564,077 B2	5/2003	Mortara
6,206,830 B1	3/2001	Diab et al.	6,571,113 B1	5/2003	Fein et al.
6,226,539 B1	5/2001	Potratz	6,580,086 B1	6/2003	Schulz et al.
6,229,856 B1	5/2001	Diab et al.	6,582,964 B1	6/2003	Samsoondar et al.
6,230,035 B1	5/2001	Aoyagi et al.	6,584,336 B1	6/2003	Ali et al.
6,236,872 B1	5/2001	Diab et al.	6,584,413 B1	6/2003	Keenan et al.
6,253,097 B1	6/2001	Aronow et al.	6,591,123 B2	7/2003	Fein et al.
6,256,523 B1	7/2001	Diab et al.	6,594,511 B2	7/2003	Stone et al.
6,262,698 B1 *	7/2001	Blum 345/55	6,595,316 B2	7/2003	Cybulski et al.
6,263,222 B1	7/2001	Diab et al.	6,597,933 B2	7/2003	Kiani et al.
6,272,363 B1	8/2001	Casciani et al.	6,600,940 B1	7/2003	Fein et al.
6,278,522 B1	8/2001	Lepper, Jr. et al.	6,606,509 B2	8/2003	Schmitt
6,280,213 B1	8/2001	Tobler et al.	6,606,510 B2	8/2003	Swedlow et al.

6,606,511	B1	8/2003	Ali et al.	6,813,511	B2	11/2004	Diab et al.
6,611,698	B1	8/2003	Yamashita et al.	6,816,741	B2	11/2004	Diab
6,614,521	B2	9/2003	Samsoondar et al.	6,819,950	B2	11/2004	Mills
6,615,064	B1	9/2003	Aldrich	6,822,564	B2	11/2004	Al-Ali
6,615,151	B1	9/2003	Scecina et al.	6,825,619	B2	11/2004	Norris
6,618,602	B2	9/2003	Levin	6,826,419	B2	11/2004	Diab et al.
6,622,095	B2	9/2003	Kobayashi et al.	6,829,496	B2	12/2004	Nagai et al.
6,628,975	B1	9/2003	Fein et al.	6,830,711	B2	12/2004	Mills et al.
6,631,281	B1	10/2003	Kastle	6,836,679	B2	12/2004	Baker, Jr. et al.
6,632,181	B2	10/2003	Flaherty et al.	6,839,579	B1	1/2005	Chin
6,640,116	B2	10/2003	Diab	6,839,580	B2	1/2005	Zonios et al.
6,643,530	B2	11/2003	Diab et al.	6,839,582	B2	1/2005	Heckel
6,650,917	B2	11/2003	Diab et al.	6,842,702	B2	1/2005	Haaland et al.
6,654,623	B1	11/2003	Kastle	6,845,256	B2	1/2005	Chin et al.
6,654,624	B2	11/2003	Diab et al.	6,847,835	B1	1/2005	Yamanishi
6,657,717	B2	12/2003	Cadell et al.	6,850,787	B2	2/2005	Weber et al.
6,658,276	B2	12/2003	Kianl et al.	6,850,788	B2	2/2005	Al-Ali
6,658,277	B2	12/2003	Wasserman	6,852,083	B2	2/2005	Caro et al.
6,661,161	B1	12/2003	Lanzo et al.	6,861,639	B2	3/2005	Al-Ali
6,662,033	B2	12/2003	Casciani et al.	6,869,402	B2	3/2005	Arnold
6,665,551	B1	12/2003	Suzuki	6,882,874	B2	4/2005	Huiku
6,668,183	B2	12/2003	Hicks et al.	6,898,452	B2	5/2005	Al-Ali et al.
6,671,526	B1	12/2003	Aoyagi et al.	6,912,049	B2	6/2005	Pawluczyk et al.
6,671,531	B2	12/2003	Al-Ali et al.	6,917,422	B2	7/2005	Samsoondar et al.
6,675,031	B1	1/2004	Porges et al.	6,919,566	B1	7/2005	Cadell
6,675,106	B1	1/2004	Keenan et al.	6,920,345	B2	7/2005	Al-Ali et al.
6,678,543	B2	1/2004	Diab et al.	6,921,367	B2	7/2005	Mills
6,681,126	B2	1/2004	Solenberger	6,922,645	B2	7/2005	Haaland et al.
6,684,090	B2	1/2004	Ali et al.	6,928,311	B1	8/2005	Pawluczyk et al.
6,684,091	B2	1/2004	Parker	6,931,268	B1	8/2005	Kiani-Azarbayjany et al.
6,687,620	B1	2/2004	Haaland et al.	6,931,269	B2	8/2005	Terry
6,694,157	B1	2/2004	Stone et al.	6,934,570	B2	8/2005	Kiani et al.
6,697,655	B2	2/2004	Sueppel et al.	6,939,305	B2	9/2005	Flaherty et al.
6,697,656	B1	2/2004	Al-Ali	6,943,348	B1	9/2005	Coffin, IV
6,697,658	B2	2/2004	Al-Ali	6,944,487	B2	9/2005	Maynard et al.
RE38,476	E	3/2004	Diab et al.	6,950,687	B2	9/2005	Al-Ali
6,699,194	B1	3/2004	Diab et al.	6,961,598	B2	11/2005	Diab
6,701,170	B2	3/2004	Stetson	6,970,792	B1	11/2005	Diab
6,708,049	B1	3/2004	Berson et al.	6,975,891	B2	12/2005	Pawluczyk
6,711,503	B2	3/2004	Haaland	6,979,812	B2	12/2005	Al-Ali
6,714,803	B1	3/2004	Mortz	6,985,764	B2	1/2006	Mason et al.
6,714,804	B2	3/2004	Al-Ali et al.	6,987,994	B1	1/2006	Mortz
6,714,805	B2	3/2004	Jeon et al.	6,993,371	B2	1/2006	Kiani et al.
RE38,492	E	4/2004	Diab et al.	6,996,427	B2	2/2006	Ali et al.
6,719,705	B2	4/2004	Mills	6,999,904	B2	2/2006	Weber et al.
6,720,734	B2	4/2004	Norris	7,001,337	B2	2/2006	Dekker
6,721,584	B2	4/2004	Baker, Jr. et al.	7,003,338	B2	2/2006	Weber et al.
6,721,585	B1	4/2004	Parker	7,003,339	B2	2/2006	Diab et al.
6,725,074	B1	4/2004	Kastle	7,006,856	B2	2/2006	Baker, Jr. et al.
6,725,075	B2	4/2004	Al-Ali	7,015,451	B2	3/2006	Dalke et al.
6,726,634	B2	4/2004	Freeman	7,024,233	B2	4/2006	Al et al.
6,735,459	B2	5/2004	Parker	7,027,849	B2	4/2006	Al-Ali
6,741,875	B1	5/2004	Pawluczyk et al.	7,030,749	B2	4/2006	Al-Ali
6,741,876	B1	5/2004	Scecina et al.	7,039,449	B2	5/2006	Al-Ali
6,743,172	B1	6/2004	Blike	7,041,060	B2	5/2006	Flaherty et al.
6,745,060	B2	6/2004	Diab et al.	7,044,918	B2	5/2006	Diab
6,745,061	B1	6/2004	Hicks et al.	7,245,953	B1	7/2007	Parker
6,748,253	B2	6/2004	Norris et al.	7,377,794	B2	5/2008	Al-Ali et al.
6,748,254	B2	6/2004	O'Neil et al.	2001/0044700	A1	11/2001	Koboyashi et al.
6,754,515	B1	6/2004	Pologe	2001/0045532	A1	11/2001	Schulz et al.
6,754,516	B2	6/2004	Mannheimer	2002/0021269	A1	2/2002	Rast
6,760,607	B2	7/2004	Al-Ali	2002/0035318	A1 *	3/2002	Mannheimer et al. 600/323
6,760,609	B2	7/2004	Jacques	2002/0038078	A1	3/2002	Ito
6,770,028	B1	8/2004	Ali et al.	2002/0038081	A1	3/2002	Fein et al.
6,771,994	B2	8/2004	Kiani et al.	2002/0059047	A1	5/2002	Haaland
6,773,397	B2	8/2004	Kelly	2002/0111748	A1	8/2002	Kobayashi et al.
6,778,923	B2	8/2004	Norris et al.	2002/0115919	A1	8/2002	Al-Ali
6,780,158	B2	8/2004	Yarita	2002/0156353	A1	10/2002	Larson
6,788,849	B1	9/2004	Pawluczyk	2002/0159002	A1 *	10/2002	Chang 349/61
6,792,300	B1	9/2004	Diab et al.	2002/0161291	A1	10/2002	Kiani et al.
6,801,797	B2	10/2004	Mannheimer et al.	2002/0165440	A1	11/2002	Mason et al.
6,801,799	B2	10/2004	Mendelson	2002/0183819	A1	12/2002	Struble
6,810,277	B2	10/2004	Edgar, Jr. et al.	2003/0045784	A1	3/2003	Palatnik et al.

US 7,764,982 B2

Page 5

2003/0045785 A1 *	3/2003	Diab et al.	600/323	2005/0070773 A1	3/2005	Chin et al.
2003/0109775 A1	6/2003	O'Neil et al.		2005/0070775 A1	3/2005	Chin et al.
2003/0120160 A1	6/2003	Yarita		2005/0075546 A1	4/2005	Samsoondar et al.
2003/0139657 A1	7/2003	Solenberger		2005/0085735 A1	4/2005	Baker, Jr. et al.
2003/0195402 A1	10/2003	Fein et al.		2005/0101848 A1	5/2005	Al Ali et al.
2004/0006261 A1	1/2004	Swedlow et al.		2005/0124871 A1	6/2005	Baker, Jr. et al.
2004/0033618 A1	2/2004	Haass et al.		2005/0143634 A1	6/2005	Baker, Jr. et al.
2004/0059209 A1	3/2004	Al Ali et al.		2005/0143943 A1	6/2005	Brown
2004/0064259 A1	4/2004	Haaland et al.		2005/0148834 A1	7/2005	Hull et al.
2004/0081621 A1 *	4/2004	Arndt et al.	424/9.6	2005/0184895 A1	8/2005	Petersen et al.
2004/0092805 A1	5/2004	Yarita		2005/0187447 A1	8/2005	Chew et al.
2004/0133087 A1	7/2004	Al Ali et al.		2005/0187448 A1	8/2005	Petersen et al.
2004/0138538 A1	7/2004	Stetson		2005/0187449 A1	8/2005	Chew et al.
2004/0138540 A1	7/2004	Baker, Jr. et al.		2005/0187450 A1	8/2005	Chew et al.
2004/0147823 A1	7/2004	Kiani et al.		2005/0187452 A1	8/2005	Petersen et al.
2004/0158134 A1	8/2004	Diab et al.		2005/0187453 A1	8/2005	Petersen et al.
2004/0158135 A1	8/2004	Baker, Jr. et al.		2005/0197549 A1	9/2005	Baker, Jr.
2004/0162472 A1	8/2004	Berson et al.		2005/0197579 A1	9/2005	Baker, Jr.
2004/0167382 A1	8/2004	Gardner et al.		2005/0197793 A1	9/2005	Baker, Jr.
2004/0176670 A1	9/2004	Takamura et al.		2005/0203357 A1	9/2005	Debreczeny et al.
2004/0181134 A1	9/2004	Baker, Jr. et al.		2005/0228253 A1	10/2005	Debreczeny
2004/0199063 A1	10/2004	O'Neil et al.		2005/0250997 A1	11/2005	Takeda et al.
2004/0204639 A1	10/2004	Casciani et al.		2006/0030764 A1	2/2006	Porges et al.
2004/0204868 A1	10/2004	Maynard et al.				
2004/0262046 A1	12/2004	Simon et al.				
2004/0267103 A1	12/2004	Li et al.				
2004/0267140 A1	12/2004	Ito et al.				
2005/0033128 A1	2/2005	Al Ali et al.				
2005/0043902 A1	2/2005	Haaland et al.				
2005/0049469 A1	3/2005	Aoyagi et al.				
2005/0054908 A1 *	3/2005	Blank et al.	600/316			

FOREIGN PATENT DOCUMENTS

WO	WO 00/59374	10/2000
WO	WO 02/26123	4/2002
WO	WO 03/068060	8/2003

* cited by examiner




FIG. 1




FIG. 2A




FIG. 2B




FIG. 2C




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10A




FIG. 10B




FIG. 10C




FIG. 10D




FIG. 11A




FIG. 11B




FIG. 11C






FIG. 12






FIG. 15





FIG. 16



1402






FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29A




FIG. 29B




FIG. 30A




FIG. 30B




FIG. 30C




FIG. 30F




FIG. 30D




FIG. 30G




FIG. 30E




FIG. 30H




FIG. 31A




FIG. 31B





FIG. 31C



SECTION A-A

FIG. 31F




FIG. 31D




FIG. 31G





FIG. 31E



SECTION B-B

FIG. 31H




FIG. 32A




FIG. 32B





FIG. 32C



SECTION A-A

FIG. 32F




FIG. 32D




FIG. 32G





FIG. 32E



SECTION B-B

FIG. 32H




FIG. 33A




FIG. 33B




FIG. 33C




FIG. 33F




FIG. 33D




FIG. 33G




FIG. 33E




FIG. 33H




FIG. 34A




FIG. 34B





FIG. 34C



SECTION A-A

FIG. 34F




FIG. 34D




FIG. 34G





FIG. 34E



SECTION B-B

FIG. 34H




FIG. 35A




FIG. 35B




FIG. 36A




FIG. 36B




FIG. 36C




FIG. 37A




FIG. 37B




FIG. 37D





FIG. 37C



SECTION B-B

FIG. 38A




FIG. 38B





FIG. 38C



SECTION A-A

FIG. 38D




FIG. 39A




FIG. 39B





FIG. 39C



SECTION A-A
FIG. 39D




FIG. 40




FIG. 41A




FIG. 41B








FIG. 41C






FIG. 44A




FIG. 44B




FIG. 45




FIG. 46

1

MULTIPLE WAVELENGTH SENSOR EMITTERS

PRIORITY CLAIM TO RELATED PROVISIONAL APPLICATIONS

The present application claims priority benefit under 35 U.S.C. §119(e) to U.S. Provisional Patent Application Ser. No. 60/657,596, filed Mar. 1, 2005, entitled "Multiple Wavelength Sensor," No. 60/657,281, filed Mar. 1, 2005, entitled "Physiological Parameter Confidence Measure," No. 60/657,268, filed Mar. 1, 2005, entitled "Configurable Physiological Measurement System," and No. 60/657,759, filed Mar. 1, 2005, entitled "Noninvasive Multi-Parameter Patient Monitor." The present application incorporates the foregoing disclosures herein by reference.

INCORPORATION BY REFERENCE OF COPENDING RELATED APPLICATIONS

The present application is related to the following copen-
ing U.S. utility applications:

	App. Sr. No.	Filing Date	Title	Atty Dock.
1	11/366,995	Mar. 1, 2006	Multiple Wavelength Sensor Equalization	MLR.003A
2	11/366,209	Mar. 1, 2006	Multiple Wavelength Sensor Substrate	MLR.004A
3	11/366,210	Mar. 1, 2006	Multiple Wavelength Sensor Interconnect	MLR.005A
4	11/366,833	Mar. 1, 2006	Multiple Wavelength Sensor Attachment	MLR.006A
5	11/366,997	Mar. 1, 2006	Multiple Wavelength Sensor Drivers	MLR.009A
6	11/367,034	Mar. 1, 2006	Physiological Parameter Confidence Measure	MLR.010A
7	11/367,036	Mar. 1, 2006	Configurable Physiological Measurement System	MLR.011A
8	11/367,033	Mar. 1, 2006	Noninvasive Multi- Parameter Patient Monitor	MLR.012A
9	11/367,014	Mar. 1, 2006	Noninvasive Multi- Parameter Patient Monitor	MLR.013A
10	11/366,208	Mar. 1, 2006	Noninvasive Multi- Parameter Patient Monitor	MLR.014A

The present application incorporates the foregoing disclo-
sures herein by reference.

BACKGROUND OF THE INVENTION

Spectroscopy is a common technique for measuring the concentration of organic and some inorganic constituents of a solution. The theoretical basis of this technique is the Beer-Lambert law, which states that the concentration c_i of an absorbent in solution can be determined by the intensity of light transmitted through the solution, knowing the path-length d_λ , the intensity of the incident light $I_{0,\lambda}$, and the extinction coefficient $\epsilon_{i,\lambda}$ at a particular wavelength λ . In generalized form, the Beer-Lambert law is expressed as:

$$I_\lambda = I_{0,\lambda} e^{-d_\lambda \mu_{a,\lambda}} \quad (1)$$

$$\mu_{a,\lambda} = \sum_{i=1}^n \epsilon_{i,\lambda} \cdot c_i \quad (2)$$

where $\mu_{a,\lambda}$ is the bulk absorption coefficient and represents the probability of absorption per unit length. The minimum

2

number of discrete wavelengths that are required to solve EQS. 1-2 are the number of significant absorbers that are present in the solution.

A practical application of this technique is pulse oximetry, which utilizes a noninvasive sensor to measure oxygen saturation (SpO_2) and pulse rate. In general, the sensor has light emitting diodes (LEDs) that transmit optical radiation of red and infrared wavelengths into a tissue site and a detector that responds to the intensity of the optical radiation after absorption (e.g., by transmission or transreflectance) by pulsatile arterial blood flowing within the tissue site. Based on this response, a processor determines measurements for SpO_2 , pulse rate, and can output representative plethysmographic waveforms. Thus, "pulse oximetry" as used herein encompasses its broad ordinary meaning known to one of skill in the art, which includes at least those noninvasive procedures for measuring parameters of circulating blood through spectroscopy. Moreover, "plethysmograph" as used herein (commonly referred to as "photoplethysmograph"), encompasses its broad ordinary meaning known to one of skill in the art, which includes at least data representative of a change in the absorption of particular wavelengths of light as a function of the changes in body tissue resulting from pulsing blood. Pulse oximeters capable of reading through motion induced noise are available from Masimo Corporation ("Masimo") of Irvine, Calif. Moreover, portable and other oximeters capable of reading through motion induced noise are disclosed in at least U.S. Pat. Nos. 6,770,028, 6,658,276, 6,157,850, 6,002,952, 5,769,785, and 5,758,644, which are owned by Masimo and are incorporated by reference herein. Such reading through motion oximeters have gained rapid acceptance in a wide variety of medical applications, including surgical wards, intensive care and neonatal units, general wards, home care, physical training, and virtually all types of monitoring scenarios.

SUMMARY OF THE INVENTION

There is a need to noninvasively measure multiple physiological parameters, other than, or in addition to, oxygen saturation and pulse rate. For example, hemoglobin species that are also significant under certain circumstances are carboxyhemoglobin and methemoglobin. Other blood parameters that may be measured to provide important clinical information are fractional oxygen saturation, total hemoglobin (Hbt), bilirubin and blood glucose, to name a few.

One aspect of a physiological sensor is light emitting sources, each activated by addressing at least one row and at least one column of an electrical grid. The light emitting sources transmit light having multiple wavelengths and a detector is responsive to the transmitted light after attenuation by body tissue.

Another aspect of a physiological sensor is light emitting sources capable of transmitting light having multiple wavelengths. Each of the light emitting sources includes a first contact and a second contact. The first contacts of a first set of the light emitting sources are in communication with a first conductor and the second contacts of a second set of the light emitting sources are in communication with a second conductor. A detector is capable of detecting the transmitted light attenuated by body tissue and outputting a signal indicative of at least one physiological parameter of the body tissue. At least one light emitting source of the first set and at least one light emitting source of the second set are not common to the first and second sets. Further, each of the first set and the second set comprises at least two of the light emitting sources.

A further aspect of a physiological sensor sequentially addresses light emitting sources using conductors of an electrical grid so as to emit light having multiple wavelengths that when attenuated by body tissue is indicative of at least one physiological characteristic. The emitted light is detected after attenuation by body tissue.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of a physiological measurement system utilizing a multiple wavelength sensor;

FIGS. 2A-C are perspective views of multiple wavelength sensor embodiments;

FIG. 3 is a general block diagram of a multiple wavelength sensor and sensor controller;

FIG. 4 is an exploded perspective view of a multiple wavelength sensor embodiment;

FIG. 5 is a general block diagram of an emitter assembly;

FIG. 6 is a perspective view of an emitter assembly embodiment;

FIG. 7 is a general block diagram of an emitter array;

FIG. 8 is a schematic diagram of an emitter array embodiment;

FIG. 9 is a general block diagram of equalization;

FIGS. 10A-D are block diagrams of various equalization embodiments;

FIGS. 11A-C are perspective views of an emitter assembly incorporating various equalization embodiments;

FIG. 12 is a general block diagram of an emitter substrate;

FIGS. 13-14 are top and detailed side views of an emitter substrate embodiment;

FIG. 15-16 are top and bottom component layout views of an emitter substrate embodiment;

FIG. 17 is a schematic diagram of an emitter substrate embodiment;

FIG. 18 is a plan view of an inner layer of an emitter substrate embodiment;

FIG. 19 is a general block diagram of an interconnect assembly in relationship to other sensor assemblies;

FIG. 20 is a block diagram of an interconnect assembly embodiment;

FIG. 21 is a partially-exploded perspective view of a flex circuit assembly embodiment of an interconnect assembly;

FIG. 22 is a top plan view of a flex circuit;

FIG. 23 is an exploded perspective view of an emitter portion of a flex circuit assembly;

FIG. 24 is an exploded perspective view of a detector assembly embodiment;

FIGS. 25-26 are block diagrams of adjacent detector and stacked detector embodiments;

FIG. 27 is a block diagram of a finger clip embodiment of an attachment assembly;

FIG. 28 is a general block diagram of a detector pad;

FIGS. 29A-B are perspective views of detector pad embodiments;

FIGS. 30A-H are perspective bottom, perspective top, bottom, back, top, side cross sectional, side, and front cross sectional views of an emitter pad embodiment;

FIGS. 31A-H are perspective bottom, perspective top, top, back, bottom, side cross sectional, side, and front cross sectional views of a detector pad embodiment;

FIGS. 32A-H are perspective bottom, perspective top, top, back, bottom, side cross sectional, side, and front cross sectional views of a shoe box;

FIGS. 33A-H are perspective bottom, perspective top, top, back, bottom, side cross sectional, side, and front cross sectional views of a slim-finger emitter pad embodiment;

FIGS. 34A-H are perspective bottom, perspective top, top, back, bottom, side cross sectional, side, and front cross sectional views of a slim-finger detector pad embodiment;

FIGS. 35A-B are plan and cross sectional views, respectively, of a spring assembly embodiment;

FIGS. 36A-C are top, perspective and side views of a finger clip spring;

FIGS. 37A-D are top, back, bottom, and side views of a spring plate;

FIGS. 38A-D are front cross sectional, bottom, front and side cross sectional views of an emitter-pad shell;

FIGS. 39A-D are back, top, front and side cross sectional views of a detector-pad shell;

FIG. 40 is a general block diagram of a monitor and a sensor;

FIGS. 41A-C are schematic diagrams of grid drive embodiments for a sensor having back-to-back diodes and an information element;

FIG. 42 is a schematic diagram of a grid drive embodiment for an information element;

FIGS. 43A-C are schematic diagrams for grid drive readable information elements;

FIGS. 44A-B are cross sectional and side cut away views of a sensor cable;

FIG. 45 is a block diagram of a sensor controller embodiment; and

FIG. 46 is a detailed exploded perspective view of a multiple wavelength sensor embodiment.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Overview

In this application, reference is made to many blood parameters. Some references that have common shorthand designations are referenced through such shorthand designations. For example, as used herein, HbCO designates carboxyhemoglobin, HbMet designates methemoglobin, and Hbt designates total hemoglobin. Other shorthand designations such as COHb, MetHb, and tHb are also common in the art for these same constituents. These constituents are generally reported in terms of a percentage, often referred to as saturation, relative concentration or fractional saturation. Total hemoglobin is generally reported as a concentration in g/dL. The use of the particular shorthand designators presented in this application does not restrict the term to any particular manner in which the designated constituent is reported.

FIG. 1 illustrates a physiological measurement system 10 having a monitor 100 and a multiple wavelength sensor assembly 200 with enhanced measurement capabilities as compared with conventional pulse oximetry. The physiological measurement system 10 allows the monitoring of a person, including a patient. In particular, the multiple wavelength sensor assembly 200 allows the measurement of blood constituent and related parameters in addition to oxygen saturation and pulse rate. Alternatively, the multiple wavelength sensor assembly 200 allows the measurement of oxygen saturation and pulse rate with increased accuracy or robustness as compared with conventional pulse oximetry.

In one embodiment, the sensor assembly 200 is configured to plug into a monitor sensor port 110. Monitor keys 160 provide control over operating modes and alarms, to name a few. A display 170 provides readouts of measured parameters, such as oxygen saturation, pulse rate, HbCO and HbMet to name a few.

5

FIGS. 2A illustrates a multiple wavelength sensor assembly 200 having a sensor 400 adapted to attach to a tissue site, a sensor cable 4400 and a monitor connector 210. In one embodiment, the sensor 400 is incorporated into a reusable finger clip adapted to removably attach to, and transmit light through, a fingertip. The sensor cable 4400 and monitor connector 210 are integral to the sensor 400, as shown. In alternative embodiments, the sensor 400 may be configured separately from the cable 4400 and connector 210.

FIGS. 2B-C illustrate alternative sensor embodiments, including a sensor 401 (FIG. 2B) partially disposable and partially reusable (resposable) and utilizing an adhesive attachment mechanism. Also shown is a sensor 402 (FIG. 2C) being disposable and utilizing an adhesive attachment mechanism. In other embodiments, a sensor may be configured to attach to various tissue sites other than a finger, such as a foot or an ear. Also a sensor may be configured as a reflectance or transreflectance device that attaches to a forehead or other tissue surface.

FIG. 3 illustrates a sensor assembly 400 having an emitter assembly 500, a detector assembly 2400, an interconnect assembly 1900 and an attachment assembly 2700. The emitter assembly 500 responds to drive signals received from a sensor controller 4500 in the monitor 100 via the cable 4400 so as to transmit optical radiation having a plurality of wavelengths into a tissue site. The detector assembly 2400 provides a sensor signal to the monitor 100 via the cable 4400 in response to optical radiation received after attenuation by the tissue site. The interconnect assembly 1900 provides electrical communication between the cable 4400 and both the emitter assembly 500 and the detector assembly 2400. The attachment assembly 2700 attaches the emitter assembly 500 and detector assembly 2400 to a tissue site, as described above. The emitter assembly 500 is described in further detail with respect to FIG. 5, below. The interconnect assembly 1900 is described in further detail with respect to FIG. 19, below. The detector assembly 2400 is described in further detail with respect to FIG. 24, below. The attachment assembly 2700 is described in further detail with respect to FIG. 27, below.

FIG. 4 illustrates a sensor 400 embodiment that removably attaches to a fingertip. The sensor 400 houses a multiple wavelength emitter assembly 500 and corresponding detector assembly 2400. A flex circuit assembly 1900 mounts the emitter and detector assemblies 500, 2400 and interconnects them to a multi-wire sensor cable 4400. Advantageously, the sensor 400 is configured in several respects for both wearer comfort and parameter measurement performance. The flex circuit assembly 1900 is configured to mechanically decouple the cable 4400 wires from the emitter and detector assemblies 500, 2400 to reduce pad stiffness and wearer discomfort. The pads 3000, 3100 are mechanically decoupled from shells 3800, 3900 to increase flexibility and wearer comfort. A spring 3600 is configured in hinged shells 3800, 3900 so that the pivot point of the finger clip is well behind the fingertip, improving finger attachment and more evenly distributing the clip pressure along the finger.

As shown in FIG. 4, the detector pad 3100 is structured to properly position a fingertip in relationship to the detector assembly 2400. The pads have flaps that block ambient light. The detector assembly 2400 is housed in an enclosure so as to reduce light piping from the emitter assembly to the detector assembly without passing through fingertip tissue. These and other features are described in detail below. Specifically, emitter assembly embodiments are described with respect to FIGS. 5-18. Interconnect assembly embodiments, including the flexible circuit assembly 1900, are described with respect

6

to FIGS. 19-23. Detector assembly embodiments are described with respect to FIGS. 24-26. Attachment assembly embodiments are described with respect to FIGS. 27-39.

Emitter Assembly

FIG. 5 illustrates an emitter assembly 500 having an emitter array 700, a substrate 1200 and equalization 900. The emitter array 700 has multiple light emitting sources, each activated by addressing at least one row and at least one column of an electrical grid. The light emitting sources are capable of transmitting optical radiation having multiple wavelengths. The equalization 900 accounts for differences in tissue attenuation of the optical radiation across the multiple wavelengths so as to at least reduce wavelength-dependent variations in detected intensity. The substrate 1200 provides a physical mount for the emitter array and emitter-related equalization and a connection between the emitter array and the interconnection assembly. Advantageously, the substrate 1200 also provides a bulk temperature measurement so as to calculate the operating wavelengths for the light emitting sources. The emitter array 700 is described in further detail with respect to FIG. 7, below. Equalization is described in further detail with respect to FIG. 9, below. The substrate 1200 is described in further detail with respect to FIG. 12, below.

FIG. 6 illustrates an emitter assembly 500 embodiment having an emitter array 700, an encapsulant 600, an optical filter 1100 and a substrate 1200. Various aspects of the emitter assembly 500 are described with respect to FIGS. 7-18, below. The emitter array 700 emits optical radiation having multiple wavelengths of predetermined nominal values, advantageously allowing multiple parameter measurements. In particular, the emitter array 700 has multiple light emitting diodes (LEDs) 710 that are physically arranged and electrically connected in an electrical grid to facilitate drive control, equalization, and minimization of optical pathlength differences at particular wavelengths. The optical filter 1100 is advantageously configured to provide intensity equalization across a specific LED subset. The substrate 1200 is configured to provide a bulk temperature of the emitter array 700 so as to better determine LED operating wavelengths.

Emitter Array

FIG. 7 illustrates an emitter array 700 having multiple light emitters (LE) 710 capable of emitting light 702 having multiple wavelengths into a tissue site 1. Row drivers 4530 and column drivers 4560 are electrically connected to the light emitters 710 and activate one or more light emitters 710 by addressing at least one row 720 and at least one column 740 of an electrical grid. In one embodiment, the light emitters 710 each include a first contact 712 and a second contact 714. The first contact 712 of a first subset 730 of light emitters is in communication with a first conductor 720 of the electrical grid. The second contact 714 of a second subset 750 of light emitters is in communication with a second conductor 740. Each subset comprises at least two light emitters, and at least one of the light emitters of the first and second subsets 730, 750 are not in common. A detector 2400 is capable of detecting the emitted light 702 and outputting a sensor signal 2500 responsive to the emitted light 702 after attenuation by the tissue site 1. As such, the sensor signal 2500 is indicative of at least one physiological parameter corresponding to the tissue site 1, as described above.

FIG. 8 illustrates an emitter array 700 having LEDs 801 connected within an electrical grid of n rows and m columns totaling n+m drive lines 4501, 4502, where n and m integers greater than one. The electrical grid advantageously minimizes the number of drive lines required to activate the LEDs

801 while preserving flexibility to selectively activate individual LEDs **801** in any sequence and multiple LEDs **801** simultaneously. The electrical grid also facilitates setting LED currents so as to control intensity at each wavelength, determining operating wavelengths and monitoring total grid current so as to limit power dissipation. The emitter array **700** is also physically configured in rows **810**. This physical organization facilitates clustering LEDs **801** according to wavelength so as to minimize pathlength variations and facilitates equalization of LED intensities.

As shown in FIG. 8, one embodiment of an emitter array **700** comprises up to sixteen LEDs **801** configured in an electrical grid of four rows **810** and four columns **820**. Each of the four row drive lines **4501** provide a common anode connection to four LEDs **801**, and each of the four column drive lines **4502** provide a common cathode connection to four LEDs **801**. Thus, the sixteen LEDs **801** are advantageously driven with only eight wires, including four anode drive lines **812** and four cathode drive lines **822**. This compares favorably to conventional common anode or cathode LED configurations, which require more drive lines. In a particular embodiment, the emitter array **700** is partially populated with eight LEDs having nominal wavelengths as shown in TABLE 1. Further, LEDs having wavelengths in the range of 610-630 nm are grouped together in the same row. The emitter array **700** is adapted to a physiological measurement system **10** (FIG. 1) for measuring H_bCO and/or METHb in addition to S_pO_2 and pulse rate.

TABLE 1

LED	Nominal LED Wavelengths		
	λ	Row	Col
D1	630	1	1
D2	620	1	2
D3	610	1	3
D4		1	4
D5	700	2	1
D6	730	2	2
D7	660	2	3
D8	805	2	4
D9		3	1
D10		3	2
D11		3	3
D12	905	3	4
D13		4	1
D14		4	2
D15		4	3
D16		4	4

Also shown in FIG. 8, row drivers **4530** and column drivers **4560** located in the monitor **100** selectively activate the LEDs **801**. In particular, row and column drivers **4530**, **4560** function together as switches to Vcc and current sinks, respectively, to activate LEDs and as switches to ground and Vcc, respectively, to deactivate LEDs. This push-pull drive configuration advantageously prevents parasitic current flow in deactivated LEDs. In a particular embodiment, only one row drive line **4501** is switched to Vcc at a time. One to four column drive lines **4502**, however, can be simultaneously switched to a current sink so as to simultaneously activate multiple LEDs within a particular row. Activation of two or more LEDs of the same wavelength facilitates intensity equalization, as described with respect to FIGS. 9-11, below. LED drivers are described in further detail with respect to FIG. 45, below.

Although an emitter assembly is described above with respect to an array of light emitters each configured to trans-

mit optical radiation centered around a nominal wavelength, in another embodiment, an emitter assembly advantageously utilizes one or more tunable broadband light sources, including the use of filters to select the wavelength, so as to minimize wavelength-dependent pathlength differences from emitter to detector. In yet another emitter assembly embodiment, optical radiation from multiple emitters each configured to transmit optical radiation centered around a nominal wavelength is funneled to a tissue site point so as to minimize wavelength-dependent pathlength differences. This funneling may be accomplished with fiberoptics or mirrors, for example. In further embodiments, the LEDs **801** can be configured with alternative orientations with correspondingly different drivers among various other configurations of LEDs, drivers and interconnecting conductors.

Equalization

FIG. 9 illustrate a physiological parameter measurement system **10** having a controller **4500**, an emitter assembly **500**, a detector assembly **2400** and a front-end **4030**. The emitter assembly **500** is configured to transmit optical radiation having multiple wavelengths into the tissue site **1**. The detector assembly **2400** is configured to generate a sensor signal **2500** responsive to the optical radiation after tissue attenuation. The front-end **4030** conditions the sensor signal **2500** prior to analog-to-digital conversion (ADC).

FIG. 9 also generally illustrates equalization **900** in a physiological measurement system **10** operating on a tissue site **1**. Equalization encompasses features incorporated into the system **10** in order to provide a sensor signal **2500** that falls well within the dynamic range of the ADC across the entire spectrum of emitter wavelengths. In particular, equalization compensates for the imbalance in tissue light absorption due to Hb and HbO_2 **910**. Specifically, these blood constituents attenuate red wavelengths greater than IR wavelengths. Ideally, equalization **900** balances this unequal attenuation. Equalization **900** can be introduced anywhere in the system **10** from the controller **4500** to front-end **4000** and can include compensatory attenuation versus wavelength, as shown, or compensatory amplification versus or both.

Equalization can be achieved to a limited extent by adjusting drive currents from the controller **4500** and front-end **4030** amplification accordingly to wavelength so as to compensate for tissue absorption characteristics. Signal demodulation constraints, however, limit the magnitude of these adjustments. Advantageously, equalization **900** is also provided along the optical path from emitters **500** to detector **2400**. Equalization embodiments are described in further detail with respect to FIGS. 10-11, below.

FIGS. 10A-D illustrate various equalization embodiments having an emitter array **700** adapted to transmit optical radiation into a tissue site **1** and a detector assembly **2400** adapted to generate a sensor signal **2500** responsive to the optical radiation after tissue attenuation. FIG. 10A illustrates an optical filter **1100** that attenuates at least a portion of the optical radiation before it is transmitted into a tissue site **1**. In particular, the optical filter **1100** attenuates at least a portion of the IR wavelength spectrum of the optical radiation so as to approximate an equalization curve **900** (FIG. 9). FIG. 10B illustrates an optical filter **1100** that attenuates at least a portion of the optical radiation after it is attenuated by a tissue site **1**, where the optical filter **1100** approximates an equalization curve **900** (FIG. 9).

FIG. 10C illustrates an emitter array **700** where at least a portion of the emitter array generates one or more wavelengths from multiple light emitters **710** of the same wavelength. In particular, the same-wavelength light emitters **710** boost at least a portion of the red wavelength spectrum so as

9

to approximately equalize the attenuation curves **910** (FIG. **9**). FIG. **10D** illustrates a detector assembly **2400** having multiple detectors **2610**, **2620** selected so as to equalize the attenuation curves **910** (FIG. **9**). To a limited extent, optical equalization can also be achieved by selection of particular emitter array **700** and detector **2400** components, e.g. LEDs having higher output intensities or detectors having higher sensitivities at red wavelengths. Although equalization embodiments are described above with respect to red and IR wavelengths, these equalization embodiments can be applied to equalize tissue characteristics across any portion of the optical spectrum.

FIGS. **11A-C** illustrates an optical filter **1100** for an emitter assembly **500** that advantageously provides optical equalization, as described above. LEDs within the emitter array **700** may be grouped according to output intensity or wavelength or both. Such a grouping facilitates equalization of LED intensity across the array. In particular, relatively low tissue absorption and/or relatively high output intensity LEDs can be grouped together under a relatively high attenuation optical filter. Likewise, relatively low tissue absorption and/or relatively low output intensity LEDs can be grouped together without an optical filter or under a relatively low or negligible attenuation optical filter. Further, high tissue absorption and/or low intensity LEDs can be grouped within the same row with one or more LEDs of the same wavelength being simultaneously activated, as described with respect to FIG. **10C**, above. In general, there can be any number of LED groups and any number of LEDs within a group. There can also be any number of optical filters corresponding to the groups having a range of attenuation, including no optical filter and/or a "clear" filter having negligible attenuation.

As shown in FIGS. **11A-C**, a filtering media may be advantageously added to an encapsulant that functions both as a cover to protect LEDs and bonding wires and as an optical filter **1100**. In one embodiment, a filtering media **1100** encapsulates a select group of LEDs and a clear media **600** (FIG. **6**) encapsulates the entire array **700** and the filtering media **1000** (FIG. **6**). In a particular embodiment, corresponding to TABLE 1, above, five LEDs nominally emitting at 660-905 nm are encapsulated with both a filtering media **1100** and an overlying clear media **600** (FIG. **6**), i.e. attenuated. In a particular embodiment, the filtering media **1100** is a 40:1 mixture of a clear encapsulant (EPO-TEK OG147-7) and an opaque encapsulate (EPO-TEK OG147) both available from Epoxy Technology, Inc., Billerica, Mass. Three LEDs nominally emitting at 610-630 nm are only encapsulated with the clear media **600** (FIG. **6**), i.e. unattenuated. In alternative embodiments, individual LEDs may be singly or multiply encapsulated according to tissue absorption and/or output intensity. In other alternative embodiments, filtering media may be separately attachable optical filters or a combination of encapsulants and separately attachable optical filters. In a particular embodiment, the emitter assembly **500** has one or more notches along each side proximate the component end **1305** (FIG. **13**) for retaining one or more clip-on optical filters.

Substrate

FIG. **12** illustrates light emitters **710** configured to transmit optical radiation **1201** having multiple wavelengths in response to corresponding drive currents **1210**. A thermal mass **1220** is disposed proximate the emitters **710** so as to stabilize a bulk temperature **1202** for the emitters. A temperature sensor **1230** is thermally coupled to the thermal mass **1220**, wherein the temperature sensor **1230** provides a temperature sensor output **1232** responsive to the bulk temperature **1202** so that the wavelengths are determinable as a function of the drive currents **1210** and the bulk temperature **1202**.

10

In one embodiment, an operating wavelength λ_a of each light emitter **710** is determined according to EQ. 3

$$\lambda_a = f(T_b, I_{drive}, \sum I_{drive}) \quad (3)$$

where T_b is the bulk temperature, I_{drive} is the drive current for a particular light emitter, as determined by the sensor controller **4500** (FIG. **45**), described below, and $\sum I_{drive}$ is the total drive current for all light emitters. In another embodiment, temperature sensors are configured to measure the temperature of each light emitter **710** and an operating wavelength λ_a of each light emitter **710** is determined according to EQ. 4

$$\lambda_a = f(T_a, I_{drive}, \sum I_{drive}) \quad (4)$$

where T_a is the temperature of a particular light emitter, I_{drive} is the drive current for that light emitter and $\sum I_{drive}$ is the total drive current for all light emitters.

In yet another embodiment, an operating wavelength for each light emitter is determined by measuring the junction voltage for each light emitter **710**. In a further embodiment, the temperature of each light emitter **710** is controlled, such as by one or more Peltier cells coupled to each light emitter **710**, and an operating wavelength for each light emitter **710** is determined as a function of the resulting controlled temperature or temperatures. In other embodiments, the operating wavelength for each light emitter **710** is determined directly, for example by attaching a charge coupled device (CCD) to each light emitter or by attaching a fiberoptic to each light emitter and coupling the fiberoptics to a wavelength measuring device, to name a few.

FIGS. **13-18** illustrate one embodiment of a substrate **1200** configured to provide thermal conductivity between an emitter array **700** (FIG. **8**) and a thermistor **1540** (FIG. **16**). In this manner, the resistance of the thermistor **1540** (FIG. **16**) can be measured in order to determine the bulk temperature of LEDs **801** (FIG. **8**) mounted on the substrate **1200**. The substrate **1200** is also configured with a relatively significant thermal mass, which stabilizes and normalizes the bulk temperature so that the thermistor measurement of bulk temperature is meaningful.

FIGS. **13-14** illustrate a substrate **1200** having a component side **1301**, a solder side **1302**, a component end **1305** and a connector end **1306**. Alignment notches **1310** are disposed between the ends **1305**, **1306**. The substrate **1200** further has a component layer **1401**, inner layers **1402-1405** and a solder layer **1406**. The inner layers **1402-1405**, e.g. inner layer **1402** (FIG. **18**), have substantial metallized areas **1411** that provide a thermal mass **1220** (FIG. **12**) to stabilize a bulk temperature for the emitter array **700** (FIG. **12**). The metallized areas **1411** also function to interconnect component pads **1510** and wire bond pads **1520** (FIG. **15**) to the connector **1530**.

FIGS. **15-16** illustrate a substrate **1200** having component pads **1510** and wire bond pads **1520** at a component end **1305**. The component pads **1510** mount and electrically connect a first side (anode or cathode) of the LEDs **801** (FIG. **8**) to the substrate **1200**. Wire bond pads **1520** electrically connect a second side (cathode or anode) of the LEDs **801** (FIG. **8**) to the substrate **1200**. The connector end **1306** has a connector **1530** with connector pads **1532**, **1534** that mount and electrically connect the emitter assembly **500** (FIG. **23**), including the substrate **1200**, to the flex circuit **2200** (FIG. **22**). Sub-

11

strate layers **1401-1406** (FIG. **14**) have traces that electrically connect the component pads **1510** and wire bond pads **1520** to the connector **1532-1534**. A thermistor **1540** is mounted to thermistor pads **1550** at the component end **1305**, which are also electrically connected with traces to the connector **1530**. Plated thru holes electrically connect the connector pads **1532, 1534** on the component and solder sides **1301, 1302**, respectively.

FIG. **17** illustrates the electrical layout of a substrate **1200**. A portion of the LEDs **801**, including **D1-D4** and **D13-D16** have cathodes physically and electrically connected to component pads **1510** (FIG. **15**) and corresponding anodes wire bonded to wire bond pads **1520**. Another portion of the LEDs **801**, including **D5-D8** and **D9-D12**, have anodes physically and electrically connected to component pads **1510** (FIG. **15**) and corresponding cathodes wire bonded to wire bond pads **1520**. The connector **1530** has row pinouts **J21-J24**, column pinouts **J31-J34** and thermistor pinouts **J40-J41** for the LEDs **801** and thermistor **1540**.

Interconnect Assembly

FIG. **19** illustrates an interconnect assembly **1900** that mounts the emitter assembly **500** and detector assembly **2400**, connects to the sensor cable **4400** and provides electrical communications between the cable and each of the emitter assembly **500** and detector assembly **2400**. In one embodiment, the interconnect assembly **1900** is incorporated with the attachment assembly **2700**, which holds the emitter and detector assemblies to a tissue site. An interconnect assembly embodiment utilizing a flexible (flex) circuit is described with respect to FIGS. **20-24**, below.

FIG. **20** illustrates an interconnect assembly **1900** embodiment having a circuit substrate **2200**, an emitter mount **2210**, a detector mount **2220** and a cable connector **2230**. The emitter mount **2210**, detector mount **2220** and cable connector **2230** are disposed on the circuit substrate **2200**. The emitter mount **2210** is adapted to mount an emitter assembly **500** having multiple emitters. The detector mount **2220** is adapted to mount a detector assembly **2400** having a detector. The cable connector **2230** is adapted to attach a sensor cable **4400**. A first plurality of conductors **2040** disposed on the circuit substrate **2200** electrically interconnects the emitter mount **2210** and the cable connector **2230**. A second plurality of conductors **2050** disposed on the circuit substrate **2200** electrically interconnects the detector mount **2220** and the cable connector **2230**. A decoupling **2060** disposed proximate the cable connector **2230** substantially mechanically isolates the cable connector **2230** from both the emitter mount **2210** and the detector mount **2220** so that sensor cable stiffness is not translated to the emitter assembly **500** or the detector assembly **2400**. A shield **2070** is adapted to fold over and shield one or more wires or pairs of wires of the sensor cable **4400**.

FIG. **21** illustrates a flex circuit assembly **1900** having a flex circuit **2200**, an emitter assembly **500** and a detector assembly **2400**, which is configured to terminate the sensor end of a sensor cable **4400**. The flex circuit assembly **1900** advantageously provides a structure that electrically connects yet mechanically isolates the sensor cable **4400**, the emitter assembly **500** and the detector assembly **2400**. As a result, the mechanical stiffness of the sensor cable **4400** is not translated to the sensor pads **3000, 3100** (FIGS. **30-31**), allowing a comfortable finger attachment for the sensor **200** (FIG. **1**). In particular, the emitter assembly **500** and detector assembly **2400** are mounted to opposite ends **2201, 2202** (FIG. **22**) of an elongated flex circuit **2200**. The sensor cable **4400** is mounted to a cable connector **2230** extending from a middle portion of the flex circuit **2200**. Detector wires **4470** are shielded at the

12

flex circuit junction by a fold-over conductive ink flap **2240**, which is connected to a cable inner shield **4450**. The flex circuit **2200** is described in further detail with respect to FIG. **22**. The emitter portion of the flex circuit assembly **1900** is described in further detail with respect to FIG. **23**. The detector assembly **2400** is described with respect to FIG. **24**. The sensor cable **4400** is described with respect to FIGS. **44A-B**, below.

FIG. **22** illustrates a sensor flex circuit **2200** having an emitter end **2201**, a detector end **2202**, an elongated interconnect **2204, 2206** between the ends **2201, 2202** and a cable connector **2230** extending from the interconnect **2204, 2206**. The emitter end **2201** forms a "head" having emitter solder pads **2210** for attaching the emitter assembly **500** (FIG. **6**) and mounting ears **2214** for attaching to the emitter pad **3000** (FIG. **30B**), as described below. The detector end **2202** has detector solder pads for attaching the detector **2410** (FIG. **24**). The interconnect **2204** between the emitter end **2201** and the cable connector **2230** forms a "neck," and the interconnect **2206** between the detector end **2202** and the cable connector **2230** forms a "tail." The cable connector **2230** forms "wings" that extend from the interconnect **2204, 2206** between the neck **2204** and tail **2206**. A conductive ink flap **2240** connects to the cable inner shield **4450** (FIGS. **44A-B**) and folds over to shield the detector wires **4470** (FIGS. **44A-B**) soldered to the detector wire pads **2236**. The outer wire pads **2238** connect to the remaining cable wires **4430** (FIGS. **44A-B**). The flex circuit **2200** has top coverlay, top ink, inner coverlay, trace, trace base, bottom ink and bottom coverlay layers.

The flex circuit **2200** advantageously provides a connection between a multiple wire sensor cable **4400** (FIGS. **44A-B**), a multiple wavelength emitter assembly **500** (FIG. **6**) and a detector assembly **2400** (FIG. **24**) without rendering the emitter and detector assemblies unwieldy and stiff. In particular, the wings **2230** provide a relatively large solder pad area **2232** that is narrowed at the neck **2204** and tail **2206** to mechanically isolate the cable **4400** (FIGS. **44A-B**) from the remainder of the flex circuit **2200**. Further, the neck **2206** is folded (see FIG. **4**) for installation in the emitter pad **3000** (FIGS. **30A-H**) and acts as a flexible spring to further mechanically isolate the cable **4400** (FIGS. **44A-B**) from the emitter assembly **500** (FIG. **4**). The tail **2206** provides an integrated connectivity path between the detector assembly **2400** (FIG. **24**) mounted in the detector pad **3100** (FIGS. **31A-H**) and the cable connector **2230** mounted in the opposite emitter pad **3000** (FIGS. **30A-H**).

FIG. **23** illustrates the emitter portion of the flex circuit assembly **1900** (FIG. **21**) having the emitter assembly **500**. The emitter assembly connector **1530** is attached to the emitter end **2210** of the flex circuit **2200** (FIG. **22**). In particular, reflow solder **2330** connects thru hole pads **1532, 1534** of the emitter assembly **500** to corresponding emitter pads **2310** of the flex circuit **2200** (FIG. **22**).

FIG. **24** illustrates a detector assembly **2400** including a detector **2410**, solder pads **2420**, copper mesh tape **2430**, an EMI shield **2440** and foil **2450**. The detector **2410** is soldered **2460** chip side down to detector solder pads **2420** of the flex circuit **2200**. The detector solder joint and detector ground pads **2420** are wrapped with the Kapton tape **2470**. EMI shield tabs **2442** are folded onto the detector pads **2420** and soldered. The EMI shield walls are folded around the detector **2410** and the remaining tabs **2442** are soldered to the back of the EMI shield **2440**. The copper mesh tape **2430** is cut to size and the shielded detector and flex circuit solder joint are wrapped with the copper mesh tape **2430**. The foil **2450** is cut to size with a predetermined aperture **2452**. The foil **2450** is

13

wrapped around shielded detector with the foil side in and the aperture 2452 is aligned with the EMI shield grid 2444.

Detector Assembly

FIG. 25 illustrates an alternative detector assembly 2400 embodiment having adjacent detectors. Optical radiation having multiple wavelengths generated by emitters 700 is transmitted into a tissue site 1. Optical radiation at a first set of wavelengths is detected by a first detector 2510, such as, for example, a Si detector. Optical radiation at a second set of wavelengths is detected by a second detector 2520, such as, for example, a GaAs detector.

FIG. 26 illustrates another alternative detector assembly 2400 embodiment having stacked detectors coaxial along a light path. Optical radiation having multiple wavelengths generated by emitters 700 is transmitted into a tissue site 1. Optical radiation at a first set of wavelengths is detected by a first detector 2610. Optical radiation at a second set of wavelengths passes through the first detector 2610 and is detected by a second detector 2620. In a particular embodiment, a silicon (Si) detector and a gallium arsenide (GaAs) detector are used. The Si detector is placed on top of the GaAs detector so that light must pass through the Si detector before reaching the GaAs detector. The Si detector can be placed directly on top of the GaAs detector or the Si and GaAs detector can be separated by some other medium, such as a transparent medium or air. In another particular embodiment, a germanium detector is used instead of the GaAs detector. Advantageously, the stacked detector arrangement minimizes error caused by pathlength differences as compared with the adjacent detector embodiment.

Finger Clip

FIG. 27 illustrates a finger clip embodiment 2700 of a physiological sensor attachment assembly. The finger clip 2700 is configured to removably attach an emitter assembly 500 (FIG. 6) and detector assembly 2400 (FIG. 24), interconnected by a flex circuit assembly 1900, to a fingertip. The finger clip 2700 has an emitter shell 3800, an emitter pad 3000, a detector pad 2800 and a detector shell 3900. The emitter shell 3800 and the detector shell 3900 are rotatably connected and urged together by the spring assembly 3500. The emitter pad 3000 is fixedly retained by the emitter shell. The emitter assembly 500 (FIG. 6) is mounted proximate the emitter pad 3000 and adapted to transmit optical radiation having a plurality of wavelengths into fingertip tissue. The detector pad 2800 is fixedly retained by the detector shell 3900. The detector assembly 3500 is mounted proximate the detector pad 2800 and adapted to receive the optical radiation after attenuation by fingertip tissue.

FIG. 28 illustrates a detector pad 2800 advantageously configured to position and comfortably maintain a fingertip relative to a detector assembly for accurate sensor measurements. In particular, the detector pad has fingertip positioning features including a guide 2810, a contour 2820 and a stop 2830. The guide 2810 is raised from the pad surface 2803 and narrows as the guide 2810 extends from a first end 2801 to a second end 2802 so as to increasingly conform to a fingertip as a fingertip is inserted along the pad surface 2803 from the first end 2801. The contour 2820 has an indentation defined along the pad surface 2803 generally shaped to conform to a fingertip positioned over a detector aperture 2840 located within the contour 2820. The stop 2830 is raised from the pad surface 2803 so as to block the end of a finger from inserting beyond the second end 2802. FIGS. 29A-B illustrate detector pad embodiments 3100, 3400 each having a guide 2810, a contour 2820 and a stop 2830, described in further detail with respect to FIGS. 31 and 34, respectively.

14

FIGS. 30A-H illustrate an emitter pad 3000 having emitter pad flaps 3010, an emitter window 3020, mounting pins 3030, an emitter assembly cavity 3040, isolation notches 3050, a flex circuit notch 3070 and a cable notch 3080. The emitter pad flaps 3010 overlap with detector pad flaps 3110 (FIGS. 31A-H) to block ambient light. The emitter window 3020 provides an optical path from the emitter array 700 (FIG. 8) to a tissue site. The mounting pins 3030 accommodate apertures in the flex circuit mounting ears 2214 (FIG. 22), and the cavity 3040 accommodates the emitter assembly 500 (FIG. 21). Isolation notches 3050 mechanically decouple the shell attachment 3060 from the remainder of the emitter pad 3000. The flex circuit notch 3070 accommodates the flex circuit tail 2206 (FIG. 22) routed to the detector pad 3100 (FIGS. 31A-H). The cable notch 3080 accommodates the sensor cable 4400 (FIGS. 44A-B). FIGS. 33A-H illustrate an alternative slim finger emitter pad 3300 embodiment.

FIGS. 31A-H illustrate a detector pad 3100 having detector pad flaps 3110, a shoe box cavity 3120 and isolation notches 3150. The detector pad flaps 3110 overlap with emitter pad flaps 3010 (FIGS. 30A-H), interleaving to block ambient light. The shoe box cavity 3120 accommodates a shoe box 3200 (FIG. 32A-H) described below. Isolation notches 3150 mechanically decouple the attachment points 3160 from the remainder of the detector pad 3100. FIGS. 34A-H illustrate an alternative slim finger detector pad 3400 embodiment.

FIGS. 32A-H illustrate a shoe box 3200 that accommodates the detector assembly 2400 (FIG. 24). A detector window 3210 provides an optical path from a tissue site to the detector 2410 (FIG. 24). A flex circuit notch 3220 accommodates the flex circuit tail 2206 (FIG. 22) routed from the emitter pad 3000 (FIGS. 30A-H). In one embodiment, the shoe box 3200 is colored black or other substantially light absorbing color and the emitter pad 3000 and detector pad 3100 are each colored white or other substantially light reflecting color.

FIGS. 35-37 illustrate a spring assembly 3500 having a spring 3600 configured to urge together an emitter shell 3800 (FIG. 46) and a detector shell 3900. The detector shell is rotatably connected to the emitter shell. The spring is disposed between the shells 3800, 3900 and adapted to create a pivot point along a finger gripped between the shells that is substantially behind the fingertip. This advantageously allows the shell hinge 3810, 3910 (FIGS. 38-39) to expand so as to distribute finger clip force along the inserted finger, comfortably keeping the fingertip in position over the detector without excessive force.

As shown in FIGS. 36A-C, the spring 3600 has coils 3610, an emitter shell leg 3620 and a detector shell leg 3630. The emitter shell leg 3620 presses against the emitter shell 3800 (FIGS. 38A-D) proximate a grip 3820 (FIGS. 38A-D). The detector shell legs 3630 extend along the detector shell 3900 (FIGS. 39A-D) to a spring plate 3700 (FIGS. 37A-D) attachment point. The coil 3610 is secured by hinge pins 410 (FIG. 46) and is configured to wind as the finger clip is opened, reducing its diameter and stress accordingly.

As shown in FIGS. 37A-D the spring plate 3700 has attachment apertures 3710, spring leg slots 3720, and a shelf 3730. The attachment apertures 3710 accept corresponding shell posts 3930 (FIGS. 39A-D) so as to secure the spring plate 3700 to the detector shell 3900 (FIG. 39A-D). Spring legs 3630 (FIG. 36A-C) are slidably anchored to the detector shell 3900 (FIG. 39A-D) by the shelf 3730, advantageously allowing the combination of spring 3600, shells 3800, 3900 and hinges 3810, 3910 to adjust to various finger sizes and shapes.

FIGS. 38-39 illustrate the emitter and detector shells 3800, 3900, respectively, having hinges 3810, 3910 and grips 3820,

15

3920. Hinge apertures 3812, 3912 accept hinge pins 410 (FIG. 46) so as to create a finger clip. The detector shell hinge aperture 3912 is elongated, allowing the hinge to expand to accommodate a finger.

Monitor and Sensor

FIG. 40 illustrates a monitor 100 and a corresponding sensor assembly 200, as described generally with respect to FIGS. 1-3, above. The sensor assembly 200 has a sensor 400 and a sensor cable 4400. The sensor 400 houses an emitter assembly 500 having emitters responsive to drivers within a sensor controller 4500 so as to transmit optical radiation into a tissue site. The sensor 400 also houses a detector assembly 2400 that provides a sensor signal 2500 responsive to the optical radiation after tissue attenuation. The sensor signal 2500 is filtered, amplified, sampled and digitized by the front-end 4030 and input to a DSP (digital signal processor) 4040, which also commands the sensor controller 4500. The sensor cable 4400 electrically communicates drive signals from the sensor controller 4500 to the emitter assembly 500 and a sensor signal 2500 from the detector assembly 2400 to the front-end 4030. The sensor cable 4400 has a monitor connector 210 that plugs into a monitor sensor port 110.

In one embodiment, the monitor 100 also has a reader 4020 capable of obtaining information from an information element (IE) in the sensor assembly 200 and transferring that information to the DSP 4040, to another processor or component within the monitor 100, or to an external component or device that is at least temporarily in communication with the monitor 100. In an alternative embodiment, the reader function is incorporated within the DSP 4040, utilizing one or more of DSP I/O, ADC, DAC features and corresponding processing routines, as examples.

In one embodiment, the monitor connector 210 houses the information element 4000, which may be a memory device or other active or passive electrical component. In a particular embodiment, the information element 4000 is an EPROM, or other programmable memory, or an EEPROM, or other reprogrammable memory, or both. In an alternative embodiment, the information element 4000 is housed within the sensor 400, or an information element 4000 is housed within both the monitor connector 4000 and the sensor 400. In yet another embodiment, the emitter assembly 500 has an information element 4000, which is read in response to one or more drive signals from the sensor controller 4500, as described with respect to FIGS. 41-43, below. In a further embodiment, a memory information element is incorporated into the emitter array 700 (FIG. 8) and has characterization information relating to the LEDs 801 (FIG. 8). In one advantageous embodiment, trend data relating to slowly varying parameters, such as perfusion index, HbCO or METHb, to name a few, are stored in an IE memory device, such as EEPROM.

Back-To-Back LEDs

FIGS. 41-43 illustrate alternative sensor embodiments. A sensor controller 4500 configured to activate an emitter array 700 (FIG. 7) arranged in an electrical grid, is described with respect to FIG. 7, above. Advantageously, a sensor controller 4500 so configured is also capable of driving a conventional two-wavelength (red and IR) sensor 4100 having back-to-back LEDs 4110, 4120 or an information element 4300 or both.

FIG. 41A illustrates a sensor 4100 having an electrical grid 4130 configured to activate light emitting sources by addressing at least one row conductor and at least one column conductor. A first LED 4110 and a second LED 4120 are configured in a back-to-back arrangement so that a first contact 4152 is connected to a first LED 4110 cathode and a second LED

16

4120 anode and a second contact 4154 is connected to a first LED 4110 anode and a second LED 4120 cathode. The first contact 4152 is in communications with a first row conductor 4132 and a first column conductor 4134. The second contact 4154 is in communications with a second row conductor 4136 and a second column conductor 4138. The first LED 4110 is activated by addressing the first row conductor 4132 and the second column conductor 4138. The second LED 4120 is activated by addressing the second row conductor 4136 and the first column conductor 4134.

FIG. 41B illustrates a sensor cable 4400 embodiment capable of communicating signals between a monitor 100 and a sensor 4100. The cable 4400 has a first row input 4132, a first column input 4134, a second row input 4136 and a second column input 4138. A first output 4152 combines the first row input 4132 and the first column input 4134. A second output 4154 combines a second row input 4136 and second column input 4138.

FIG. 41C illustrates a monitor 100 capable of communicating drive signals to a sensor 4100. The monitor 4400 has a first row signal 4132, a first column signal 4134, a second row signal 4136 and a second column signal 4138. A first output signal 4152 combines the first row signal 4132 and the first column signal 4134. A second output signal 4154 combines a second row signal 4136 and second column signal 4138.

Information Elements

FIGS. 42-43 illustrate information element 4200-4300 embodiments in communications with emitter array drivers configured to activate light emitters connected in an electrical grid. The information elements are configured to provide information as DC values, AC values or a combination of DC and AC values in response corresponding DC, AC or combination DC and AC electrical grid drive signals. FIG. 42 illustrates information element embodiment 4200 advantageously driven directly by an electrical grid having rows 710 and columns 720. In particular, the information element 4200 has a series connected resistor R_2 4210 and diode 4220 connected between a row line 710 and a column line 720 of an electrical grid. In this manner, the resistor R_2 value can be read in a similar manner that LEDs 810 (FIG. 8) are activated. The diode 4220 is oriented, e.g. anode to row and cathode to column as the LEDs so as to prevent parasitic currents from unwanted activation of LEDs 810 (FIG. 8).

FIGS. 43A-C illustrate other embodiments where the value of R_1 is read with a DC grid drive current and a corresponding grid output voltage level. In other particular embodiments, the combined values of R_1 , R_2 and C or, alternatively, R_1 , R_2 and L are read with a varying (AC) grid drive currents and a corresponding grid output voltage waveform. As one example, a step in grid drive current is used to determine component values from the time constant of a corresponding rise in grid voltage. As another example, a sinusoidal grid drive current is used to determine component values from the magnitude or phase or both of a corresponding sinusoidal grid voltage. The component values determined by DC or AC electrical grid drive currents can represent sensor types, authorized suppliers or manufacturers, emitter wavelengths among others. Further, a diode D (FIG. 43C) can be used to provide one information element reading R_1 at one drive level or polarity and another information element reading, combining R_1 and R_2 , at a second drive level or polarity, i.e. when the diode is forward biased.

Passive information element 4300 embodiments may include any of various combinations of resistors, capacitors or inductors connected in series and parallel, for example. Other information element 4300 embodiments connected to an electrical grid and read utilizing emitter array drivers

17

incorporate other passive components, active components or memory components, alone or in combination, including transistor networks, PROMs, ROMs, EPROMs, EEPROMs, gate arrays and PLAs to name a few.

Sensor Cable

FIGS. 44A-B illustrate a sensor cable 4400 having an outer jacket 4410, an outer shield 4420, multiple outer wires 4430, an inner jacket 4440, an inner shield 4450, a conductive polymer 4460 and an inner twisted wire pair 4470. The outer wires 4430 are advantageously configured to compactly carry multiple drive signals to the emitter array 700 (FIG. 7). In one embodiment, there are twelve outer wires 4430 corresponding to four anode drive signals 4501 (FIG. 45), four cathode drive signals 4502 (FIG. 45), two thermistor pinouts 1450 (FIG. 15) and two spares. The inner twisted wire pair 4470 corresponds to the sensor signal 2500 (FIG. 25) and is extruded within the conductive polymer 4460 so as to reduce triboelectric noise. The shields 4420, 4450 and the twisted pair 4470 boost EMI and crosstalk immunity for the sensor signal 2500 (FIG. 25).

Controller

FIG. 45 illustrates a sensor controller 4500 located in the monitor 100 (FIG. 1) and configured to provide anode drive signals 4501 and cathode drive signals 4502 to the emitter array 700 (FIG. 7). The DSP (digital signal processor) 4040, which performs signal processing functions for the monitor, also provides commands 4042 to the sensor controller 4500. These commands determine drive signal 4501, 4502 levels and timing. The sensor controller 4500 has a command register 4510, an anode selector 4520, anode drivers 4530, current DACs (digital-to-analog converters) 4540, a current multiplexer 4550, cathode drivers 4560, a current meter 4570 and a current limiter 4580. The command register 4510 provides control signals responsive to the DSP commands 4042. In one embodiment, the command register 4510 is a shift register that loads serial command data 4042 from the DSP 4040 and synchronously sets output bits that select or enable various functions within the sensor controller 4500, as described below.

As shown in FIG. 45, the anode selector 4520 is responsive to anode select 4516 inputs from the command register 4510 that determine which emitter array row 810 (FIG. 8) is active. Accordingly, the anode selector 4520 sets one of the anode on 4522 outputs to the anode drivers 4530, which pulls up to Vcc one of the anode outputs 4501 to the emitter array 700 (FIG. 8).

Also shown in FIG. 45, the current DACs 4540 are responsive to command register data 4519 that determines the currents through each emitter array column 820 (FIG. 8). In one embodiment, there are four, 12-bit DACs associated with each emitter array column 820 (FIG. 8), sixteen DACs in total. That is, there are four DAC outputs 4542 associated with each emitter array column 820 (FIG. 8) corresponding to the currents associated with each row 810 (FIG. 8) along that column 820 (FIG. 8). In a particular embodiment, all sixteen DACs 4540 are organized as a single shift register, and the command register 4510 serially clocks DAC data 4519 into the DACs 4540. A current multiplexer 4550 is responsive to cathode on 4518 inputs from the command register 4510 and anode on 4522 inputs from the anode selector 4520 so as to convert the appropriate DAC outputs 4542 to current set 4552 inputs to the cathode drivers 4560. The cathode drivers 4560 are responsive to the current set 4552 inputs to pull down to ground one to four of the cathode outputs 4502 to the emitter array 700 (FIG. 8).

18

The current meter 4570 outputs a current measure 4572 that indicates the total LED current driving the emitter array 700 (FIG. 8). The current limiter 4580 is responsive to the current measure 4572 and limits specified by the command register 4510 so as to prevent excessive power dissipation by the emitter array 700 (FIG. 8). The current limiter 4580 provides an enable 4582 output to the anode selector 4520. A Hi Limit 4512 input specifies the higher of two preset current limits. The current limiter 4580 latches the enable 4582 output in an off condition when the current limit is exceeded, disabling the anode selector 4520. A trip reset 4514 input resets the enable 4582 output to re-enable the anode selector 4520.

Sensor Assembly

As shown in FIG. 46, the sensor 400 has an emitter shell 3800, an emitter pad 3000, a flex circuit assembly 2200, a detector pad 3100 and a detector shell 3900. A sensor cable 4400 attaches to the flex circuit assembly 2200, which includes a flex circuit 2100, an emitter assembly 500 and a detector assembly 2400. The portion of the flex circuit assembly 2200 having the sensor cable 4400 attachment and emitter assembly 500 is housed by the emitter shell 3800 and emitter pad 3000. The portion of the flex circuit assembly 2200 having the detector assembly 2400 is housed by the detector shell 3900 and detector pad 3100. In particular, the detector assembly 2400 inserts into a shoe 3200, and the shoe 3200 inserts into the detector pad 3100. The emitter shell 3800 and detector shell 3900 are fastened by and rotate about hinge pins 410, which insert through coils of a spring 3600. The spring 3600 is held to the detector shell 3900 with a spring plate 3700. A finger stop 450 attaches to the detector shell. In one embodiment, a silicon adhesive 420 is used to attach the pads 3000, 3100 to the shells 3800, 3900, a silicon potting compound 430 is used to secure the emitter and detector assemblies 500, 2400 within the pads 3000, 3100, and a cyanoacrylic adhesive 440 secures the sensor cable 4400 to the emitter shell 3800.

A multiple wavelength sensor has been disclosed in detail in connection with various embodiments. These embodiments are disclosed by way of examples only and are not to limit the scope of the claims that follow. One of ordinary skill in art will appreciate many variations and modifications.

What is claimed is:

1. A physiological sensor configured to measure an indication of a physiological characteristic of a living patient, the physiological sensor comprising:

a plurality of light emitting sources arranged to impinge light on body tissue of a living patient, each light emitting source activated by addressing at least one of a plurality of rows and at least one of a plurality of columns of an electrical grid, the light emitting sources capable of transmitting light of a plurality of wavelengths, wherein there are fewer light emitting sources than intersections of the rows and columns;

a detector responsive to the transmitted light after attenuation by body tissue of the living patient, the body tissue including pulsating blood, wherein the detector is configured to generate a signal indicative of a physiological characteristic of the living patient; and

a sensor housing configured to position the plurality of light emitting sources and the detector with respect to the body tissue of the living patient.

2. The physiological sensor according to claim 1 wherein multiple ones of the light emitting sources are capable of transmitting light of the same wavelength, the multiple ones simultaneously activated by addressing one of the rows.

19

3. The physiological sensor according to claim 2 wherein: the light emitting sources are LEDs, and each of the LEDs have an anode in common with one of the rows and a cathode in common with one of the columns so that driving one of the rows and one of the columns activates a unique one of the LEDs.
4. The physiological sensor according to claim 3 further comprising:
a plurality of row drivers in communication with the rows; and
a plurality of column drivers in communication with the columns,
wherein a selected row driver sources current to a corresponding row and selected column driver sinks current from a corresponding column so as to activate an addressed one of the LEDs.
5. The physiological sensor according to claim 4 wherein deselected ones of the row drivers pull corresponding rows to a low voltage via a functional switch configured to operably connect deselected rows to a low voltage source and deselected ones of the column drivers pull corresponding columns to a high voltage via a functional switch configured to operably connect deselected columns to a high voltage source so as to substantially block parasitic current from unaddressed ones of the LEDs.
6. The physiological sensor according to claim 5 wherein the electrical grid comprises at least three rows or at least three columns.
7. The physiological sensor according to claim 5 wherein the electrical grid communicates with at least eight LEDs.
8. The physiological sensor of claim 1, wherein the plurality of light emitting sources and the detector are coupled to a flex circuit.
9. The physiological sensor of claim 1, wherein the plurality of light emitting sources are arranged to minimize optical pathlength differences.
10. The physiological sensor of claim 1, wherein the plurality of light emitting sources are arranged to facilitate equalization.
11. The physiological sensor of claim 1, wherein the electrical grid is arranged so as to prevent parasitic currents from unwanted activation of the light emitting sources.
12. The physiological sensor of claim 1, wherein the light emitting sources correspond to multiple different wavelengths of light, the light sources being arranged in clusters corresponding to said wavelengths.
13. The physiological sensor of claim 12, wherein the light sources are arranged in clusters corresponding to said wavelengths so as to minimize pathlength variations.

20

14. The physiological sensor of claim 12, wherein the light sources are arranged in clusters corresponding to said wavelengths so as to facilitate equalization of intensities.
15. The physiological sensor of claim 12, wherein the light emitting sources are further configured to comprise wavelengths usable to measure two or more of HbCO, METHb, and SpO₂.
16. A method for measuring a physiological characteristic of a living patient, the method comprising:
positioning a sensor with respect to body tissue of a living patient, the sensor comprising a plurality of light emitting sources arranged to impinge light on the body tissue and a detector, the light emitting sources being arranged in an electrical grid comprising rows and columns, wherein there are fewer light emitting sources than intersections of the rows and columns;
activating the plurality of light emitting sources, said activating each light emitting source comprising addressing at least one of the rows and at least one of the columns of the electrical grid, such that a plurality of wavelengths of light are emitted from the plurality of light emitting sources;
detecting the light with the detector after attenuation by the body tissue of the living patient, the body tissue comprising pulsating blood; and
generating a signal reflecting a physiological characteristic of the living patient responsive to the detected light.
17. The method of claim 16, wherein the electrical grid is arranged so as to prevent parasitic currents from unwanted activation of the light emitting sources.
18. The method of claim 16, further comprising connecting deselected columns to a voltage source to substantially block parasitic current from unaddressed ones of the light emitting sources.
19. The method of claim 16, wherein the light emitting sources correspond to multiple different wavelengths of light, the light sources being arranged in clusters corresponding to said wavelengths.
20. The method of claim 19, wherein the light sources are arranged in said clusters corresponding to said wavelengths so as to minimize pathlength variations.
21. The method of claim 19, wherein the light sources are arranged in said clusters corresponding to said wavelengths so as to facilitate equalization of intensities.
22. The method of claim 16, wherein the light emitting sources are further configured to emit wavelengths adapted to measure two or more of HbCO, METHb, and SpO₂.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 7,764,982 B2
APPLICATION NO. : 11/367013
DATED : July 27, 2010
INVENTOR(S) : Smith et al.


Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

On the Title Page, Item (12) "Dalke et al." should read --Smith et al.--

On the Title Page, Item (75) Inventors: should read --Robert Smith, Lake Forest, CA (US);
David Dalke, Irvine, CA (US); Ammar Al-Ali, Tustin, CA (US); Mohamed Diab, Mission Viejo, CA
(US); Marcelo Lamago, Rancho Santa Margarita, CA (US)--

Signed and Sealed this
Twenty-eighth Day of February, 2012

A handwritten signature in black ink, reading "David J. Kappos". The signature is written in a cursive, flowing style with a large initial "D".

David J. Kappos
Director of the United States Patent and Trademark Office