



US 20060198189A1

(19) **United States**(12) **Patent Application Publication****Lue et al.**(10) **Pub. No.: US 2006/0198189 A1**(43) **Pub. Date: Sep. 7, 2006**

(54) **NON-VOLATILE MEMORY CELLS,
MEMORY ARRAYS INCLUDING THE SAME
AND METHODS OF OPERATING CELLS
AND ARRAYS**

on Jan. 27, 2005. Provisional application No. 60/689,231, filed on Jun. 10, 2005. Provisional application No. 60/689,314, filed on Jun. 10, 2005.

(75) Inventors: **Hang-Ting Lue**, Hsinchu City (TW);
Sheng-Chih Lai, Taichung City (TW)

Correspondence Address:
**AKIN GUMP STRAUSS HAUSER & FELD
L.L.P.
ONE COMMERCE SQUARE
2005 MARKET STREET, SUITE 2200
PHILADELPHIA, PA 19103 (US)**

(73) Assignee: **Macronix International Co., Ltd.**

(21) Appl. No.: **11/324,495**

(22) Filed: **Jan. 3, 2006**

Related U.S. Application Data

(60) Provisional application No. 60/640,229, filed on Jan. 3, 2005. Provisional application No. 60/647,012, filed


Publication Classification

(51) **Int. Cl.**
G11C 16/04 (2006.01)

(52) **U.S. Cl.** **365/185.12**

(57) **ABSTRACT**

Memory cells comprising: a semiconductor substrate having a source region and a drain region disposed below a surface of the substrate and separated by a channel region; a tunnel dielectric structure disposed above the channel region, the tunnel dielectric structure comprising at least one layer having a small hole-tunneling-barrier height; a charge storage layer disposed above the tunnel dielectric structure; an insulating layer disposed above the charge storage layer; and a gate electrode disposed above the insulating layer are described along with arrays thereof and methods of operation.






Fig. 1b

Fig. 1a




Fig. 2




Fig. 3




Fig. 4




Fig. 5b




Fig. 5a




Fig. 5d




Fig. 5c




Fig. 5e




Fig. 6




Fig. 7a




Fig. 7b

CV DURING -FN ERASE (ONONO=15/20/18/70/90), WITH Pt GATE




Fig. 7c

CV DURING RETENTION (ONONO=15/20/18/70/90), WITH Pt GATE




Fig. 7d




Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12b
LAYOUT EXAMPLE OF THIS
VIRTUAL GROUND ARRAY.

Fig. 12a
EQUIVALENT CIRCUIT OF THE
VIRTUAL GROUND ARRAY.




Fig. 13




Fig. 14a




Fig. 14b




Fig. 15b




Fig. 15a




Fig. 16a




Fig. 16b




Fig. 17




Fig. 18




Fig. 19a




Fig. 19b




Fig. 20




Fig. 21b




Fig. 21a




Fig. 22b






Fig. 22a






Fig. 24a




Fig. 24b




Fig. 25




Fig. 26




Fig. 27




Fig. 28




Fig. 29a




Fig. 29b




Fig. 30





Fig. 31



NON-VOLATILE MEMORY CELLS, MEMORY ARRAYS INCLUDING THE SAME AND METHODS OF OPERATING CELLS AND ARRAYS

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application is based upon, and claims priority under 35 U.S.C. § 119(e) of: provisional U.S. Patent Application No. 60/640,229, filed on Jan. 3, 2005; provisional U.S. Patent Application No. 60/647,012, filed on Jan. 27, 2005; provisional U.S. Patent Application No. 60/689,231, filed on Jun. 10, 2005; and provisional U.S. Patent Application No. 60/689,314, filed on Jun. 10, 2005; the entire contents of each of which are incorporated herein by reference.

BACKGROUND OF THE INVENTION

[0002] Non-volatile memory ("NVM") refers to semiconductor memory which is able to continually store information even when the supply of electricity is removed from the device containing the NVM cell. NVM includes Mask Read-Only Memory (Mask ROM), Programmable Read-Only Memory (PROM), Erasable Programmable Read-Only Memory (EPROM), Electrically Erasable Programmable Read-Only Memory (EEPROM), and Flash Memory. Non-volatile memory is extensively used in the semiconductor industry and is a class of memory developed to prevent loss of programmed data. Typically, non-volatile memory can be programmed, read and/or erased based on the device's end-use requirements, and the programmed data can be stored for a long period of time.

[0003] Generally, non-volatile memory devices may have various designs. One example of an NVM cell design is the so-called SONOS (silicon-oxide-nitride-oxide-silicon) device, which may use a thin tunnel oxide layer, to allow hole direct tunneling erase operations. Although such designs may have good erase speed, the data retention is usually poor, in part because direct tunneling may occur even at a low electrical field strengths that may exist during a retention state of a memory device.

[0004] Another NVM design is NROM (nitrided read-only memory), which uses a thicker tunnel oxide layer to prevent charge loss during retention states. However, a thick tunnel oxide layer may impact channel erase speed. As a result, band-to-band tunneling hot-hole (BTBTHH) erase methods can be used to inject hole traps to compensate the electrons. However, the BTBTHH erase methods may cause some reliability issues. For example, the characteristics of NROM devices employing BTBTHH erase methods may degrade after numerous P/E (program/erase) cycles.

[0005] Thus, a need in the art exists for non-volatile memory cell designs and arrays which can be operated (programmed/erased/read) numerous times with improved data retention performance and increased operation speeds.

BRIEF SUMMARY OF THE INVENTION

[0006] The present invention relates to non-volatile memory devices, and more specifically, to non-volatile memory devices including a tunnel dielectric structure that facilitates self-converging erase operations while also maintaining charge retention in a charge storage layer of the memory device during retention states.

[0007] One embodiment of the present invention includes memory cells comprising: a semiconductor substrate having a source region and a drain region disposed below a surface of the substrate and separated by a channel region; a tunnel dielectric structure disposed above the channel region, the tunnel dielectric structure comprising at least one layer having a small hole-tunneling-barrier height; a charge storage layer disposed above the tunnel dielectric structure; an insulating layer disposed above the charge storage layer; and a gate electrode disposed above the insulating layer.

[0008] Another embodiment of the present invention includes memory cells comprising: a semiconductor substrate having a source region and a drain region disposed below a surface of the substrate and separated by a channel region; a multi-layer tunnel dielectric structure disposed above the channel region, the multi-layer tunnel dielectric structure comprising at least one layer having a small hole-tunneling-barrier height; a charge storage layer disposed above the multi-layer tunnel dielectric structure; an insulating layer disposed above the charge storage layer; and a gate electrode disposed above the insulating layer.

[0009] In certain preferred embodiments, the layer providing a small hole-tunneling-barrier height may contain materials such as silicon nitride (Si_3N_4) or hafnium oxide (HfO_2). In certain preferred embodiments of the present invention memory cells include a tunnel dielectric structure having multiple layers, such as a stacked dielectric tri-layer structure of silicon oxide, silicon nitride, and silicon oxide (ONO). Such tunnel dielectric structures provide a SONOS (silicon-oxide-nitride-oxide-nitride-oxide-silicon) or a super-lattice SONOS design.

[0010] In certain preferred embodiments of the present invention the tunnel dielectric structure can comprise at least two dielectric layers each having a thickness of up to about 4 nm. Additionally, in certain preferred embodiments of the present invention, the gate electrode comprises a material having a work function value greater than that of N^+ polysilicon.

[0011] In certain preferred embodiments, the tunnel dielectric structure can include a layer comprising a material having a small hole tunneling barrier height, wherein the material is present in the layer at a concentration gradient such that the concentration of the material is at a maximum at a depth point within the layer.

[0012] The present invention also includes non-volatile memory devices which comprise a plurality of memory cells (i.e., an array) in accordance with one or more of the embodiments described herein. As used herein, a "plurality" refers to two or more. Memory devices in accordance with the present invention exhibit significantly improved operational properties including increased erase speeds, improved charge retention and larger windows of operation.

[0013] The present invention also includes methods of operating non-volatile memory cells and arrays. Methods of operation in accordance with the present invention include resetting the memory devices by applying a self-converging method to tighten V_t distribution of the memory devices; programming at least one of the memory devices by channel +FN injection; and reading at least one of the memory devices by applying a voltage between an erased state level and a programmed state level of at least one of the memory

devices. As used herein, the term “tighten” refers to the narrowing of the threshold voltage distribution among the many memory cells of an array. In general, threshold voltage distribution is “tightened” where the threshold voltages of several cells are within a narrow range of one another such that operation of the array is improved over conventional designs. For example, in some preferred embodiments, such as in a NAND array comprising memory cells in accordance with one or more embodiments of the present invention, a “tightened” threshold voltage distribution indicates that the threshold voltages of the various memory cells are within a 0.5V range of one another. In other array architectures employing memory cells in accordance with the present invention, the “tightened” threshold voltage distribution may have a range of about 1.0V from the upper limit to the lower limit.

[0014] One embodiment of a method of operation in accordance with the present invention includes operating an array in accordance with the present invention by applying self-converging reset/erase voltages to the substrate and the gate electrode in each memory cell to be reset/erased; programming at least one of the plurality of memory cells; and reading at least one of the plurality of memory cells by applying a voltage between an erased state level and a programmed state level of at least one of the memory devices.

[0015] The present invention also includes methods of forming a memory cell, comprising: providing a semiconductor substrate having a source region and a drain region formed therein below a surface of the substrate and separated by a channel region; forming a tunnel dielectric structure above the channel region, wherein forming the tunnel dielectric structure comprises forming at least two dielectric layers, wherein one of the at least two dielectric layers has a smaller hole tunneling barrier height than the other of the at least two dielectric layers; forming a charge storage layer above the tunnel dielectric structure; forming an insulating layer above the charge storage layer; and forming a gate electrode above the insulating layer.

[0016] As used herein, the phrase “small hole tunneling barrier height” refers generally to values which are less than or equal to the approximate hole tunneling barrier height of silicon dioxide. In particular, a small hole tunneling barrier height is preferably less than or equal to about 4.5 eV. More preferably, a small hole tunneling barrier height is less than or equal to about 1.9 eV.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

[0017] The foregoing summary, as well as the following detailed description of the invention, will be better understood when read in conjunction with the appended drawings. For the purpose of illustrating the invention, there are shown in the drawings embodiments which are presently preferred. It should be understood, however, that the invention is not limited to the precise arrangements and instrumentalities shown.

[0018] In the drawings:

[0019] FIGS. 1a and 1b are cross-sectional schematic representations of an N-channel memory cell in accordance with one embodiment of the present invention and a P-channel

memory cell in accordance with one embodiment of the present invention, respectively;

[0020] FIG. 2 is a graphical representation of the threshold voltage (charge trapping capacity) of a tunnel dielectric structure in accordance with one embodiment of the present invention under various programming methods;

[0021] FIG. 3 is a graphical representation of the threshold voltage of a SONOS memory cell in accordance with one embodiment of the present invention over time during erase;

[0022] FIG. 4 is a graphical representation of the threshold voltage of a SONOS memory cell in accordance with one embodiment of the present invention over time during retention;

[0023] FIGS. 5a-5e are band energy diagrams of ONO tunnel dielectric structures in accordance with various embodiments of the present invention;

[0024] FIG. 6 is a graphical representation of hole-tunneling current versus electrical field strength for three different tunnel dielectric structures;

[0025] FIG. 7a is a graphical representation of the threshold voltage over time of a memory cell in accordance with one embodiment of the present invention during erase after various types of programming;

[0026] FIG. 7b is a graphical representation of the threshold voltage over time of a memory cell having a platinum gate in accordance with one embodiment of the present invention during erase;

[0027] FIGS. 7c and 7d are graphical representations of capacitance versus voltage for the memory cell referred to in FIG. 7b;

[0028] FIG. 8 is a graphical representation of the threshold voltage of a memory cell in accordance with one embodiment of the present invention over the course of numerous programs/erase cycles under various operating conditions;

[0029] FIG. 9 is a graphical representation of the current-voltage (IV) relationship for a memory cell in accordance with one embodiment of the invention after one cycle and 10 cycles;

[0030] FIG. 10 is a graphical representation of the threshold voltage of a memory cell in accordance with one embodiment of the present invention over the course of numerous programs/erase cycles under one set of programming and erasing conditions;

[0031] FIG. 11 is a graphical representation of the change in threshold voltage over time in a memory cell according to one embodiment of the present invention under VG-accelerated retention testing;

[0032] FIGS. 12a and 12b are an equivalent circuit diagram and layout view, respectively, of a virtual ground array of memory cells in accordance with one embodiment of the present invention;

[0033] FIG. 13 is a cross-section schematic representation of a virtual ground array of memory cells in accordance with one embodiment of the present invention taken along line 12B-12B as shown in FIG. 12b;

[0034] **FIGS. 14a and 14b** are equivalent circuit diagrams of memory arrays comprising memory cells in accordance with one embodiment of the present invention and depicting suitable reset/erase voltages in accordance with two embodiments of operation in accordance with the present invention;

[0035] **FIGS. 15a and 15b** are equivalent circuit diagrams of memory arrays comprising memory cells in accordance with one embodiment of the present invention depicting one method of programming in accordance with the present invention;

[0036] **FIGS. 16a and 16b** are equivalent circuit diagrams of memory arrays comprising memory cells in accordance with one embodiment of the present invention depicting one method of reading a bit in accordance with the present invention;

[0037] **FIG. 17** is a graphical representation of the threshold voltage of a memory cell in accordance with one embodiment of the present invention over time under various erasing conditions;

[0038] **FIG. 18** is a graphical representation of the threshold voltage of a memory cell in accordance with one embodiment of the present invention over the course of numerous programs/erase cycles;

[0039] **FIGS. 19a and 19b** are graphical representations of the current at the drain of a memory cell in accordance with one embodiment under various gate voltages depicted in a logarithmic scale and a linear scale, respectively;

[0040] **FIG. 20** is an equivalent circuit diagram of an array including memory cells in accordance with one embodiment of the present invention depicting one method of programming a bit in accordance with the present invention;

[0041] **FIGS. 21a and 21b** are a layout view and equivalent circuit diagram of a virtual ground array in accordance with one embodiment of the present invention;

[0042] **FIGS. 22a and 22b** are an equivalent circuit diagram and layout view, respectively, of a NAND array of memory cells in accordance with one embodiment of the present invention;

[0043] **FIGS. 23a and 23b** are cross-sectional schematic representations of a NAND array of memory cells in accordance with one embodiment of the present invention taken along lines 22A-22A and 22B-22B, respectively, as shown in **FIG. 22b**;

[0044] **FIG. 24a** is an equivalent circuit diagram of a NAND array in accordance with one embodiment of the present invention depicting one method of operation in accordance with the present invention;

[0045] **FIG. 24b** is a graphical representation of threshold voltages over time during a reset operation in accordance with one embodiment of the present invention for two memory cells having different initial threshold voltages;

[0046] **FIG. 25** is an equivalent circuit diagram depicting a method of operation in accordance with one embodiment of the present invention;

[0047] **FIG. 26** is a graphical representation of the threshold voltage of a memory cell in accordance with one embodiment of the present invention over time under various erasing conditions;

[0048] **FIG. 27** is an equivalent circuit diagram depicting a method of operation in accordance with one embodiment of the present invention;

[0049] **FIG. 28** is a graphical representation of the threshold voltage of a memory cell in accordance with one embodiment of the present invention over the course of numerous programs/erase cycles under one set of programming and erasing conditions

[0050] **FIGS. 29a and 29b** are graphical representations of the current at the drain of a memory cell in accordance with one embodiment under various gate voltages at three different cycle numbers depicted in a logarithmic scale and a linear scale, respectively

[0051] **FIG. 30** is a graphical representation of the threshold voltage of memory cells in accordance with one embodiment of the present invention over time during retention at three different temperature and cycle conditions;

[0052] **FIG. 31** is a cross-sectional schematic representation of a NAND array wordline in accordance with one embodiment of the present invention; and

[0053] **FIG. 32** is a cross-sectional schematic representation of a NAND array wordline formation technique in accordance with one embodiment of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

[0054] Reference will now be made in detail to the invention and the presently preferred embodiments thereof, examples of which are illustrated in the accompanying drawings. Wherever possible, the same or similar reference numbers are used in the drawings and the description to refer to the same or like parts. It should be noted that the non-graph drawings are in greatly simplified form and are not to precise scale. In reference to the disclosure herein, for purposes of convenience and clarity only, directional terms, such as top, bottom, left, right, up, down, above, below, beneath, rear, and front, are used with respect to the accompanying drawings. Such directional terms used in conjunction with the following description of the drawings should not be construed to limit the scope of the invention in any manner not explicitly set forth in the appended claims. Although the disclosure herein refers to certain illustrated embodiments, it is to be understood that these embodiments are presented by way of example and not by way of limitation. It is to be understood and appreciated that the process steps and structures described herein do not cover a complete process flow for the manufacture of entire integrated circuits. The present invention may be practiced in conjunction with various integrated circuit fabrication techniques that are known in the art or to be developed.

[0055] Memory cells in accordance with the present invention can overcome some of the reliability issues in SONOS and NROM devices. For example, memory cell structures in accordance with the present invention may allow fast FN channel erase methods, while at the same time, maintaining good charge retention characteristics. Various embodiments of the memory cells according to the present invention can also alleviate reliance on the BTBTHH erase method, thereby avoiding device degradation after numerous P/E cycles.

[0056] One example may employ an ultra-thin tunnel dielectric or ultra-thin oxide layer in conjunction with the small hole tunneling barrier height layer in embodiments where the tunnel dielectric structure is a multilayer structure. This may provide better stress immunity. Non-volatile memory cells according to the present invention also show little degradation after numerous P/E cycles.

[0057] Memory cells according to the present invention may employ either an n-channel or a p-channel design, such as shown in FIGS. 1a and 1b. FIG. 1a depicts a cross-sectional view of an n-channel memory cell 100 in accordance with one embodiment of the present invention. The memory cell includes a p-type substrate 101 containing at least two n-doped regions 102 & 104, wherein each of the doped regions 102 & 104 may function as either a source or drain depending upon voltages applied. As shown in FIG. 1a, for reference purposes, doped region 102 can serve as the source and doped region 104 can serve as the drain. The substrate 101 further includes a channel region 106 between the two n-doped regions. Above the channel region 106, on the surface of the substrate 101, is a tunnel dielectric structure 120. In certain preferred embodiments, the tunnel dielectric structure 120 can comprise a tri-layer thin ONO structure wherein a small hole-tunneling-barrier height nitride layer 124 is sandwiched between a thin lower oxide layer 122 and an upper thin oxide layer 126. The memory cell 100 further includes a charge-trapping (or charge storage) layer 130, preferably a nitride, above the tunnel dielectric structure 120, and an insulating layer 140, preferably comprising a blocking oxide, disposed above the charge-trapping layer 130. A gate 150 is disposed on the insulating layer 140.

[0058] FIG. 1b, depicts a cross-sectional view of an p-channel memory cell 200 in accordance with one embodiment of the present invention. The memory cell includes an n-type substrate 201 containing at least two p-doped regions 202 & 204, wherein each of the doped regions 202 & 204 may function as either a source or drain. The substrate 201 further includes a channel region 206 between the two p-doped regions. The p-channel memory cell 200 similarly includes a tunnel dielectric structure 220, comprising a tri-layer thin ONO structure wherein a small hole-tunneling-barrier height nitride layer 224 is sandwiched between a thin lower oxide layer 222 and an upper thin oxide layer 226, a charge-trapping (or charge storage) layer 230, an insulating layer 240, and a gate 250.

[0059] Thus, for example, as depicted in FIGS. 1a and 1b, memory cells in accordance with the present invention may include: a multi-layer thin film tunnel dielectric structure, including a first silicon oxide layer O1, a first silicon nitride layer N1, and a second silicon oxide layer O2; a charge-storage layer, such as a second silicon nitride layer N2; and an insulating layer such as a third silicon oxide layer O3, on or over ("above") a substrate, such as a semiconductor substrate (e.g., a silicon substrate). The tunneling dielectric structure allows hole tunneling from the substrate to the charge-storage layer during an erase/reset operation of the memory device. Preferably, the tunnel dielectric structure in a non-volatile memory cell of the present invention has a negligible charge-trapping efficiency, and more preferably, does not trap charge at all during memory operations.

[0060] Charge storage materials such as a silicon nitride layer, HfO_2 , and Al_2O_3 may be used as the small hole

tunneling barrier height layer in a tunnel dielectric structure. In certain preferred embodiments of the present invention, an efficient charge storage material, such as a silicon nitride can be used as a charge storage layer in the memory device. A blocking oxide that prevents charge loss may serve as an insulating layer, such as a third silicon oxide layer O3. The memory cells according to the present invention also include a gate or gate electrode, such as a polysilicon gate, above the insulating layer. The tunnel dielectric structure, charge storage layer, insulating layer and gate can be formed above the substrate above at least a portion of a channel region, which is defined by and is disposed between a source region and a drain region.

[0061] Memory cells according to various embodiments of the present invention comprise a tunnel dielectric structure which can provide fast FN erase speeds of around 10 msec under a negative gate voltage (V_g), such as a V_g of about -10 to about -20 V. On the other hand, the charge retention can still be maintained, and, in some examples, may be better than many conventional SONOS devices. Memory cells according to the present invention can also avoid the use of band-to-band hot hole erase operations, which, are commonly used in NROM devices. Avoidance of such band-to-band hot hole erase operations may greatly eliminate hot-hole introduced damages and such avoidance is therefore desirable.

[0062] Referring to FIG. 2, experimental measurements of threshold voltage for a tunnel dielectric structure in accordance with one embodiment of the present invention shows that an ultra-thin O1/N1/O2 structure can have a negligible trapping efficiency, as evidenced by the unchanged threshold voltage level under successive programming pulses. In the example tested for FIG. 2, the O1/N1/O2 layers had thicknesses of 30, 30 and 35 angstroms (Å), respectively. As shown in FIG. 2, the threshold voltage V_t remains steady at approximately 1.9 volts over the course of several program shots using various methods of programming, namely -FN programming, +FN programming and CHE (channel hot electron) programming. Thus, such an ultra thin O1/N1/O2 film may serve as a modulated tunnel dielectric structure. The results under various charge injection methods including CHE, +FN and -FN all suggest negligible charge trapping. Manufacturing processes or device structures may be designed to minimize interfacial traps, so that neither O1/N1 nor N1/O2 interface is active.

[0063] FIG. 3 illustrates the erase characteristics of a memory cell having a SONONOS design in accordance with one embodiment of the present invention. The memory cell in the embodiment described in FIG. 3 comprises an n-MOS-FET design with an ONO tunnel dielectric structure having thicknesses of 15 Å, 20 Å and 18 Å, respectively. The memory cell of this embodiment comprises a silicon nitride charge storage layer having a thickness of about 70 Å, an insulating silicon oxide layer with a thickness of about 90 Å, and a gate comprising any suitable conductive material, for example, n-doped polycrystalline silicon. Referring to FIG. 3, fast FN erase may be achieved, such as within 10 msec, and an excellent self-convergent erase properties may also be obtained.

[0064] FIG. 4 illustrates the charge retention characteristics of a SONONOS device in accordance with an embodiment of a memory cell according to the present invention as

described with reference to **FIG. 3**. As shown, the retention characteristics can be better than those of conventional SONOS devices, and in terms of magnitude, may be many orders better.

[0065] **FIGS. 5a** and **5b** are band diagrams which illustrate possible effects of using a tunnel dielectric structure containing at least one layer having a small hole-tunneling-barrier height. The band diagram of the tunnel dielectric structure, an O1/N1/O2 trilayer in this example, under a low electrical field, which may exist during memory data retention, is shown in **FIG. 5a**. Direct tunneling as represented by the dotted arrow may be eliminated under low electrical fields, thereby providing good charge retention during retention states. On the other hand, band diagram offset under a high electrical field, as shown in **FIG. 5b**, can reduce the barrier effect of N1 and O2 such that the direct tunneling through O1 may occur. A tunnel dielectric structure having at least one small hole-tunneling-barrier height layer may allow efficient FN erase operation.

[0066] **FIGS. 5c** and **5d** illustrate another set of band diagrams in one example. For a better band offset condition in one example, the thickness of N1 may be larger than that of O1. The band diagram of valence band is plotted at the same electrical field $E_{01}=14$ MV/cm. The tunneling probability according to WKB approximation is correlated to the shadow area. In this example, for $N1=O1$ in thickness, the band offset does not completely screen out the barrier of O2. On the other hand, for $N1>O1$, the band offset can more easily screen out O1. Therefore, for $N1>O1$ in thickness, the hole tunneling current may be larger under the same electrical field in O1.

[0067] An experiment with measured and simulated hole tunneling currents, as shown in **FIG. 6**, further describes hole tunneling through a tunnel dielectric structure according to certain embodiments of the present invention. For example, hole tunneling current through the O1/N1/O2 dielectric may fall between that of an ultra-thin oxide and a thick oxide. In one example, under a high electrical field, the hole tunneling current may approximate that of an ultra-thin oxide. However, under a low electrical field, the direct tunneling can be suppressed. As shown in **FIG. 6**, hole tunneling current is detected through a thin oxide layer even at low electrical field strengths of only 1 MV/cm. Hole tunneling current is negligible through a thick oxide even at relatively high field strengths such as, for example, 11-13 mV/cm. However, hole tunneling current through an ONO tunnel dielectric structure approaches that of a thin oxide layer when high electric field strengths are present. In **FIG. 6**, the large current leakage due to hole tunneling through an ultra-thin oxide at low electrical fields can be seen at area A of the graph. In **FIG. 6**, hole tunneling current through an O1/N1/O2 tunnel dielectric structure at high electric field strengths can be seen at area B of the graph. In **FIG. 6**, the virtually non-existent tunneling current through an O1/N1/O2 tunnel dielectric structure and a thick oxide at low electrical fields can be seen at area C of the graph.

[0068] Memory cell designs in accordance with the present invention may be applied to various memory types, including but not limited to, NOR and/or NAND-type flash memories.

[0069] As noted above, a tunnel dielectric layer may include two or more layers, including one layer that may

provide a small hole-tunneling-barrier height. In one example, the layer providing a small hole-tunneling-barrier height may contain silicon nitride. The layer may be sandwiched between two silicon oxide layers, thereby forming an O/N/O tunnel dielectric if silicon nitride is used as the intermediate layer. In certain preferred embodiments of the present invention, each layer in a tunnel dielectric structure is up to about 4 nm thick. In some preferred embodiments, each of the layers in the tunnel dielectric structure can have a thickness of about 1 nm to 3 nm. In one exemplary device, a tri-layer structure may have a bottom layer, such as a silicon oxide layer, of about 10 Å to 30 Å, an intermediate layer, such as a silicon nitride layer, of about 10 Å to 30 Å, and a top layer, such as another silicon oxide layer, of about 10 Å to 30 Å. In one particular example, an O/N/O tri-layer structure having a 15 Å bottom silicon oxide layer, a 20 Å intermediate silicon nitride layer, and an 18 Å top silicon oxide layer may be used.

[0070] In one example, a thin O/N/O tri-layer structure shows negligible charge trapping. Theoretical band diagram and tunneling current analysis, such as described with reference to **FIGS. 5a, 5b** and **6**, may suggest that a tunnel dielectric structure, such as an O1/N1/O2 structure having thicknesses of 3 nm or less for each of the layers, can suppress the hole direct-tunneling at low electric field during retention. At the same time, it still may allow efficient hole tunneling at high electric field. This may be because the band offset can effectively screen out the tunneling barrier of N1 and O2. Therefore, this proposed device may offer fast hole tunneling erase, while it is immune from the retention problem of the conventional SONOS devices. Experimental analysis shows excellent endurance and retention properties of memory cells in accordance with various embodiments of the present invention.

[0071] In certain preferred embodiments, the tunnel dielectric structure includes at least a middle layer and two adjacent layers on opposing sides of the middle layer, wherein each of the middle layer and two adjacent layers comprises a first material and a second material, wherein the second material has a valence band energy level greater than the valence band energy level of the first material and the second material has a conduction band energy level less than the conduction band energy level of the first material; and wherein the concentration of the second material is higher in the middle layer than in the two adjacent layers and the concentration of the first material is higher in the two adjacent layers than in the middle layer. Preferably, in a tunnel dielectric structure in accordance with this embodiment of the present invention, the first material comprises oxygen and/or an oxygen-containing compound and the second material comprises nitrogen and/or a nitrogen-containing compound. For example, the first material can comprise an oxide, such as silicon oxide, and the second material can comprise a nitride, such as Si_3N_4 or $Si_xO_yN_z$.

[0072] Tunnel dielectrics in accordance with this aspect of the invention may be comprised of three or more layers, all of which can contain similar elements (such as Si, N and O), so long as the concentration of the material having the smallest hole tunneling barrier height is higher within the middle layer than in the two adjacent layers.

[0073] In certain tunnel dielectric structures according to the preceding embodiment of the present invention, the

second material can be present in the middle layer in a gradient concentration such that the concentration of the second material in the middle layer increases from one adjacent layer/middle layer interface to a maximum concentration at a depth point within the middle layer, and decreases from the maximum concentration depth point to a lower concentration at the other adjacent layer/middle layer interface. The increase and decrease in concentration is preferably gradual.

[0074] In still other embodiments of the present invention, the tunnel dielectric structure includes at least a middle layer and two adjacent layers on opposing sides of the middle layer, wherein the two adjacent layers comprise a first material and the middle layer comprises a second material, wherein the second material has a valence band energy level greater than the valence band energy level of the first material and the second material has a conduction band energy level less than the conduction band energy level of the first material; and wherein the second material is present in the middle layer in a gradient concentration such that the concentration of the second material in the middle layer increases from one adjacent layer/middle layer interface to a maximum concentration at a depth point within the middle layer, and decreases from the maximum concentration depth point to a lower concentration at the other adjacent layer/middle layer interface. The increase and decrease in concentration is preferably gradual. Preferably, in a tunnel dielectric structure in accordance with this embodiment of the present invention, the first material comprises oxygen and/or an oxygen-containing compound and the second material comprises nitrogen and/or a nitrogen-containing compound. For example, the first material can comprise an oxide, such as silicon oxide, and the second material can comprise a nitride, such as Si_3N_4 or $\text{Si}_x\text{O}_y\text{N}_z$.

[0075] For example, in embodiments of the present invention where the tunnel dielectric layer comprises a tri-layer ONO structure, the bottom oxide and top oxide layers can comprise silicon dioxide and the middle nitride layer can be comprised of, for example, silicon oxynitride and silicon nitride wherein the concentration of silicon nitride (i.e., the material having the smaller hole tunneling barrier height of the two) is not constant within the layer, but rather reaches a maximum at some depth point within the layer between the two interfaces with the sandwiching oxide layers.

[0076] The precise point within the middle layer where the material with the smallest hole tunneling barrier height reaches its maximum concentration is not critical, so long as it is present in a gradient and reaches its maximum concentration in the tunnel dielectric layer at some point within the middle layer.

[0077] The gradient concentration of the material having the smallest hole tunneling barrier height can be advantageous in improving various properties of non-volatile memory devices, particularly those having a SONOS, or SONOS-like structure. For example, retention state charge loss can be diminished, hole tunneling under high electric fields can be improved and, to the extent it may occur, charge-trapping in the tunnel dielectric can be avoided.

[0078] The band diagram of a tunnel dielectric layer can be advantageously modified in accordance with this aspect of the present invention such that the valence band energy

level and the conduction band energy level of the middle layer do not have a constant value, but rather vary across the thickness of the layer with the concentration of the material having the smallest hole tunneling barrier height. Referring to FIG. 5e, modification of an ONO tri-layer tunnel dielectric in accordance with this aspect of the invention is shown via a band diagram. The middle layer (Layer-2) is comprised of silicon nitride. The outer layers (Layer-1 and Layer-3) are comprised of silicon dioxide. The concentration of silicon nitride in Layer-2 is varied such that the valence band energy level and the conduction band energy level reach a maximum and minimum value, respectively, at the depth in Layer-2 where the concentration of silicon nitride is highest. Three possible silicon nitride concentration gradients are shown in FIG. 5e, depicted by dashed lines representing the variable valence band energy conduction band energy levels that result from the concentration gradients. As shown in FIG. 5e, by the circles on the dashed lines representing three alternative silicon nitride concentration maximums within Layer-2, the lowest valence band energy level and the highest conduction band energy level coincide with the silicon nitride concentration maximum.

[0079] Multi-layer tunnel dielectric structures in accordance with such embodiments of the present invention, can be prepared in a variety of ways. For example, a first silicon dioxide or silicon oxynitride layer can be formed using any number of conventional oxidation approaches including, but not limited to thermal oxidation, radical (ISSG) oxidation, and plasma oxidation/nitridation, as well as chemical vapor deposition processes. A middle layer with a gradient concentration of SiN can then be formed, for example, via chemical vapor deposition processes, or alternatively, by plasma nitridation of excess oxide or oxynitride formed on top of the first layer. A third layer, the upper oxide layer, can then be formed, for example, by oxidation or chemical vapor deposition.

[0080] A charge storage layer can then be formed over the tunnel dielectric structure. In one example, a charge storage layer of about 5 nm to 10 nm may be formed over the tunnel dielectric structure. In one particular example, a silicon nitride layer of about 7 nm or thicker may be used. The insulating layer above the charge storage layer may be about 5 nm to 12 nm. For example, a silicon oxide layer of about 9 nm or thicker may be used. And the silicon oxide layer may be formed by a thermal process converting at least a portion of a nitride layer to form the silicon oxide layer. Any method, known or to be developed, for forming layers of suitable materials described herein can be used to deposit or form tunnel dielectric layers, charge-storage layers and/or insulating layers. Suitable methods include, for example, thermal growth methods and chemical vapor deposition methods.

[0081] In one example, a thermal conversion process may provide a high density or concentration of interfacial traps that can enhance the trapping efficiency of a memory device. For example, thermal conversion of nitride can be carried out at 1000° C., while the gate flow ratio is $\text{H}_2:\text{O}_2=1000:4000$ sccm.

[0082] In addition, because silicon nitride generally has very low (about 1.9 eV) hole barrier, it may become transparent to hole tunneling under high field. Meanwhile, the total thickness of a tunnel dielectric, such as an ONO

structure, may prevent direct tunneling of electrons under a low electric field. In one example, this asymmetrical behavior may provide a memory device offering not only fast hole-tunneling erase, but also reduction or elimination of charge leakage during retention.

[0083] An exemplary device may be fabricated by 0.12 μm NROM/NBit technologies. Table 1 shows the device structure and parameters in one example. The proposed tunnel dielectric with an ultra-thin O/N/O may alter the hole tunneling current. A thicker (7 nm) N2 layer may serve as a charge-trapping layer and an O3 (9 nm) layer may serve as the blocking layer in one example. Both N2 and O3 may be fabricated using NROM/NBit technologies.

TABLE 1

Layer	Approximate Thickness (Angstroms)
Bottom Oxide (O1)	15
Inter Nitride (N1)	20
Inter Oxide (O2)	18
Trapping Nitride (N2)	70
Blocking Oxide (O3)	90
Gate: N ⁺ -polysilicon	
Channel length: 0.22 μm	
Channel width: 0.16 μm	

[0084] In certain embodiments of the present invention, a gate can comprise a material having a work function greater than that of N⁺ polysilicon. In certain preferred embodiments of the present invention, such a high work function gate material can comprise a metal such as, for example, platinum, iridium, tungsten, and other noble metals. Preferably, the gate material in such embodiments has a work function greater than or equal to about 4.5 eV. In particularly preferred embodiments, the gate material comprises a high work function metal such as, for example, platinum or iridium. Additionally, preferred high work function materials include, but are not limited to P⁺ polysilicon, and metal nitrides such as, for example, titanium nitride and tantalum nitride. In particularly preferred embodiments of the present invention, the gate material comprises platinum.

[0085] An exemplary device in accordance with an embodiment of the present invention having a high work function gate material may also be fabricated by 0.12 μm NROM/NBit technologies. Table 2 shows the device structure and parameters in one example. The proposed tunnel dielectric with an ultra-thin O/N/O may alter the hole tunneling current. A thicker (7 nm) N2 layer may serve as a charge-trapping layer and an O3 (9 nm) layer may serve as the blocking layer in one example. Both N2 and O3 may be fabricated using NROM/NBit technologies.

TABLE 2

Layer	Approximate Thickness (Angstroms)
Bottom Oxide	15
Inter Nitride	20
Inter Oxide	18
Trapping Nitride (N2)	70
Blocking Oxide	90
Gate: Platinum	
Channel length: 0.22 μm	
Channel width: 0.16 μm	

[0086] Memory cells in accordance with high work function gate material embodiments of the present invention exhibit erase properties which are even more improved over other embodiments. High work function gate materials suppress gate electron injection into the trapping layer. In certain embodiments of the present invention wherein the memory cells comprise an N⁺ polysilicon gate, hole tunneling into the charge-trapping layer during erase occurs simultaneously with gate electron injection. This self-converging erase effect results in higher threshold voltage levels in the erased state, which can be undesirable in NAND applications. Memory cells in accordance with high work function gate material embodiments of the present invention can be used in various type of memory applications including, for example, NOR- and NAND-type memories. However, the memory cells according to high work function gate material embodiments of the present invention are particularly suitable for use in NAND applications where elevated threshold voltages in the erased/reset state can be undesirable. Memory cells in accordance with high work function gate material embodiments of the present invention can be erased via hole tunneling methods and preferably via -FN erasing operations.

[0087] An exemplary device having an ONO tunneling dielectric and an N⁺ polysilicon gate may be programmed by conventional SONOS or NROM method and erased by channel FN hole tunneling. FIG. 7a shows the erase characteristics of an exemplary SONOS device having an ONO tunneling dielectric in one example. Referring to FIG. 7a, a higher gate voltage results in a faster erase speed. It also has a higher saturation V_t, because gate injection is also stronger and the resulting dynamic balance point (which determines the V_t) is higher. This is shown on the right-hand side of the graph as the threshold voltage reaches a minimum at values of from about 3 to about 5 volts depending upon the erase gate voltage. The hole tunneling current can be extracted by a transient analysis method by differentiating the curves in FIG. 7a. The extracted hole current from the measurement in FIG. 7a is illustrated in FIG. 6 as discussed above. For comparison, there is also plotted simulated hole tunneling current using WKB approximation. The experimental results are in reasonable agreement with our prediction. The tunneling current through the O1/N1/O2 stack approaches that of the ultra-thin O1 under a high electric field, while it is turned-off under a low electric field.

[0088] In accordance with certain embodiments of memory cells of the present invention having high work function gate materials, wherein the high work function gate suppresses gate electron injection, the threshold voltage of the device in an erased or reset state can be much lower, and even negative, depending upon erase time. The threshold voltage values of a memory device in accordance with one embodiment of the present invention wherein the gate is comprised of platinum and the tunnel dielectric layer comprises a 15/20/18 angstrom ONO structure are shown in FIG. 7b. As shown in FIG. 7b, at a similar gate voltage (-18 V) during a -FN erase operation, the threshold voltage of the device can be set below -3V. The corresponding capacitance versus gate voltage values for the device are shown in FIG. 7c.

[0089] Moreover, retention properties of memory devices in accordance with high work function gate material embodiments the present invention are improved. The reten-

tion properties of a memory device having a platinum gate are shown in **FIG. 7d** wherein the capacitance is graphed as a function of gate voltage following erase and program, and then 30 minutes after each operation and two hours after each operation. Minimal deviation is observed.

[0090] Memory cells in accordance with various embodiments of the present invention may be operated with at least two separate schemes. For example, CHE programming with reverse read (mode 1) may be used to perform a 2-bits/cell operation. Additionally, low-power +FN programming (mode 2) may also be used for a 2-bits/cell operation. Both modes can use the same hole tunneling erase method. Mode 1 may preferably be used for a virtual ground array architecture for NOR-type flash memories. Mode 2 may preferably be used for NAND-type flash memories.

[0091] As an example, **FIG. 8** shows the excellent endurance properties of a virtual ground array architecture NOR-type flash memory in accordance with one embodiment of the present invention under mode 1 operation. Erase degradation of such memory devices having a tunnel dielectric structure does not occur, because hole tunneling erase ($V_g = -15$ V) is a uniform channel erase method. The corresponding IV curves are also shown in **FIG. 9**, which suggest little degradation of the device after numerous P/E cycles. In one example, this may be because ultra-thin oxide/nitride layers possess good stress immunity properties. Additionally, the memory device is free of hot-hole introduced damages. The endurance properties of a NAND-type flash memory in accordance with one embodiment of the present invention under Mode 2 operation are shown in **FIG. 10**. For a faster convergent erasing time, one may use a larger bias ($V_g = -16$ V). Excellent endurance may also be obtained in this example.

[0092] The charge retention of an exemplary SONOS device in accordance with one embodiment of the present invention is shown in **FIG. 4**, where only a 60 mV charge loss is observed after 100 hours. The improvement of retention is many orders of magnitude better than conventional SONOS devices. VG-accelerated retention test also shows that direct tunneling can be suppressed at the low electrical field. **FIG. 11** illustrates an example of a VG-accelerated retention test for a 10K P/E cycled device. The charge loss is small at $-V_g$ stress after a 1000 sec stress, indicating that the hole direct tunneling at small electrical field can be suppressed.

[0093] Accordingly, the SONOS design identified in the above examples may provide a fast hole tunneling erase with excellent endurance properties. As noted above, the design may be implemented in both NOR and NAND-type nitride-storage flash memories. Additionally, a memory array in accordance with the present invention may include multiple memory devices with similar or different configurations.

[0094] In various embodiments of arrays according to the present invention, memory cells according to the present invention may be used in place of conventional NROM or SONOS devices in a virtual ground array architecture. The reliability problems and erase degradations may be solved or mitigated by using FN hole tunneling instead of hot-hole injection. Without limiting the scope of the invention to the specific structures described below, various operation meth-

ods in accordance with memory arrays of the present invention are described below for exemplary NOR virtual ground array architectures.

[0095] CHE or CHISEL (channel initiated secondary electron) programming and reverse read may be used for 2-bit/cell memory array. And the erase method may be a uniform channel FN hole tunneling erase. In one example, the array architecture may be a virtual ground array or a JTOX array. With reference to **FIGS. 12a-20**, an O1/N1/O2 tri-layer structure may be used as the tunnel dielectric, each layer having about 3 nm or less in thickness to provide hole direct tunneling. With reference to **FIGS. 12a-20**, N2 may be thicker than 5 nm to provide a high trapping efficiency. An insulating layer, O3, may be a silicon oxide layer formed by wet oxidation, such as a wet converted top oxide (silicon oxide), to provide a large density of traps at the interface between O3 and N2. O3 may be about 6 nm or thicker to prevent charge loss from this silicon oxide layer.

[0096] **FIGS. 12a** and **12b** illustrate an example of a virtual ground array architecture incorporating the memory cells discussed above, such as memory cells having a tri-layer ONO tunnel dielectric. In particular, **FIG. 12a** illustrates an equivalent circuit of a portion of a memory array, and **FIG. 12b** illustrates an exemplary layout of a portion of the memory array.

[0097] In addition, **FIG. 13** illustrates a schematic diagram of the cross-sectional view of several memory cells incorporated in the array. In one example, the buried diffusion (BD) areas may be N⁺-doped junctions for the source or drain regions of the memory cells. The substrate may be a p-type substrate. In order to avoid possible breakdown of the BDOX areas (oxide above BD) during $-FN$ erase, a thick BDOX (>50 nm) may be used in one example.

[0098] **FIGS. 14a** and **14b** illustrate possible electrical RESET schemes for an exemplary virtual ground array incorporating 2 bits/cell memory cells having a tunnel dielectric design discussed above. Before performing further P/E cycles, all the devices may first undergo an electrical "RESET". A RESET process may ensure the V_t uniformity of memory cells in the same array and raise the device V_t to the convergent erased state. For example, applying $V_g = -15$ V for 1 sec, as shown in **FIG. 14a**, may have the effect of injecting some charge into a charge trapping layer of silicon nitride to reach a dynamic balancing condition. With the RESET, even memory cells that are non-uniformly charged due, for example, to the plasma charging effect during their fabrication processes may have their V_t converged. An alternative way for creating a self-converging bias condition is to provide bias for both gate and substrate voltages. For example, referring to **FIG. 14b**, $V_g = -8$ V and P-well = +7 V may be applied.

[0099] **FIGS. 15a** and **15b** illustrate programming schemes for an exemplary virtual ground array incorporating 2 bits/cell memory cells having a tunnel dielectric design discussed above. Channel hot-electron (CHE) programming may be used to program the device. For Bit-1 programming illustrated in **FIG. 15a**, the electrons are locally injected into the junction edge above BLN (bit line N). For Bit-2 programming shown in **FIG. 15b**, the electrons are stored above BLN-I. Typical programming voltage for WL (word line) is around 6 V to 12 V. Typical programming voltage for BL (bit line) is about 3 to 7 V, and the p-well may be kept grounded.

[0100] **FIGS. 16a** and **16b** illustrate reading schemes for an exemplary virtual ground array incorporating 2 bits/cell memory cells having a tunnel dielectric design discussed above. In one example, reverse read is used to read the device to perform a 2 bits/cell operation. Referring to **FIG. 16a**, for reading Bit-1, BLN-I is applied with a suitable read voltage, such as 1.6 V. Referring to **FIG. 16b**, for reading bit-2, BLN is applied with a suitable read voltage, such as 1.6V. In one example, the reading voltage may be in the range of about 1 to 2 V. The word lines and the P-well may be 13 kept grounded. However, other modified read schemes, such as a raised-Vs reverse read method can be performed. For example, a raised-Vs reverse read method may use $V_d/V_s=1.8/0.2$ V for reading Bit-2, and $V_d/V_s=0.2/0.8$ for reading Bit-1.

[0101] **FIGS. 14a** and **14b** also illustrate sector erase schemes for an exemplary virtual ground array incorporating 2 bits/cell memory cells having a tunnel dielectric design discussed above. In one example, sector erase with channel hole tunneling erase may applied to erase the memory cells simultaneously. An ONO tunnel dielectric in a memory cell having the SONONOS structure may offer a fast erase, which may occur in about 10 to 50 msec and a self-convergent channel erase speed. In one example, a sector erase operation condition may be similar to a RESET process. For example, referring to **FIG. 14a**, applying V_G =about -15 V at the WL's simultaneously and leaving all the BL's floating may achieve a sector erase. And the p-well may be kept grounded.

[0102] Alternatively, referring to **FIG. 14b**, applying about -8 V to the WL's and about +7 V to the p-well may also achieve a sector erase. In some examples, a complete sector erase operation may be carried out within 100 msec or less without having any over-erase or hard-to-erase cells. The device design discussed above may facilitate a channel erase providing excellent self-convergent properties.

[0103] **FIG. 17** illustrates the erase characteristics in one example of using an SONONOS device. An example of an SONONOS device may have the thickness of O1/N1/O2/N2/O3 respectively as about 15/20/18/70/90 Angstroms, with an N+-polysilicon gate and thermally converted top oxide as O3. The erase speeds for various gate voltages are shown. A higher gate voltage results in a faster erase speed.

[0104] However, the convergent V_t is also higher. This is because gate injection is more active under higher gate voltages. To reduce gate injection, P+-polysilicon gate or other metal gate with a high work function may be used alternatively as the gate material to reduce the gate-injected electrons during the erase.

[0105] **FIG. 18** illustrates the endurance properties of using SONONOS devices in a virtual ground array architecture. The endurance properties of in some examples are excellent. The programming condition is $V_g/V_d=8.5/4.4$ V, 0.1 μ sec for Bit-1 and $V_g/V_s=8.5/4.6$ V, 0.1 μ sec for Bit-2. The FN erase may use $V_g=-15$ V for about 50 msec to erase the two bits simultaneously. Because the FN erase is self-convergent uniform channel erase, hard-to-erase or over-erase cells usually do not present. In some examples, the devices proposed above show excellent endurance properties even without using a Program/Erase verifying or stepping algorithm.

[0106] **FIGS. 19a** and **19b** illustrate I-V characteristics during P/E cycles in one example. The corresponding I-V

curves in both log scale (**FIG. 19a**) and linear scale (**FIG. 19b**) are shown. In one example, an SONONOS device possesses little degradations after numerous P/E cycles, such that both the sub-threshold swing (S.S.) and trans-conductance (gm) are almost the same after numerous cycles. This SONONOS device possesses superior endurance properties than NROM device. One reason may be that hot-hole injection is not used. Additionally, an ultra-thin oxide as noted above may possess better stress immunity properties than a thick tunnel oxide.

[0107] **FIG. 20** illustrates a CHISEL programming scheme in one example. An alternative way to program the device is to use CHISEL programming scheme, which uses negative substrate bias enhanced impact ionization to increase the hot carrier efficiency. The programming current can be also reduced due to the body effect. Typical condition is illustrated in this figure, where substrate is applied with a negative voltage (-2 V), and the junction voltage is reduced to about 3.5 V. For conventional NROM devices and technologies, CHISEL programming is not applicable because it may inject more electrons near the channel center region. And hot-hole erase is inefficient to remove the electrons near the channel center region in the conventional NROM devices.

[0108] **FIGS. 21a** and **21b** illustrate the design of a JTOX virtual ground array in one example. The JTOX virtual ground array provides an alternative implementation of using SONONOS memory cells in a memory array. In one example, one difference between the JTOX structure and a virtual ground array is that the devices in the JTOX structure that are isolated by STI processes. A typical layout example is illustrated in **FIG. 21a**. **FIG. 21b** illustrates a corresponding equivalent circuit, which is the same as that of a virtual ground array.

[0109] As noted above, memory cell structures in accordance with the present invention are suitable for both NOR- and NAND-type flash memories. The following will describe additional examples of memory array designs and their operation methods. Without limiting the scope of the invention to the specific structures described below, various operation methods in accordance with memory arrays of the present invention are described below for exemplary NAND architectures.

[0110] As noted above, n-channel SONONOS memory devices having an ONO tunneling dielectric may be used in a memory device. **FIGS. 22a** and **22b** illustrate an example of a NAND array architecture. **FIGS. 23a** and **23b** illustrate the cross-sectional views of an exemplary memory array design from two different directions. In some examples, the operation methods of a memory array may include +FN programming, self-convergent reset/erase, and reading methods. Additionally, circuit operation methods may be included to avoid program disturb in some examples.

[0111] In addition to the single-block gate structure design, a split-gate array, such as a NAND array using SONONOS devices positioned between two transistor gates which are located next to the source/drain regions, may also be used. In some examples, a split-gate design may scale down device dimension to $F=30$ nm or below. Furthermore, the devices may be designed to obtain good reliability, to reduce or eliminate the inter-floating-gate coupling effect, or to achieve both. As discussed above, an SONONOS memory

device may provide excellent self-converging erase, which may help sector-erase operations and V_t distribution control. Furthermore, a tightened erased state distribution may facilitate multi-level applications (MLC).

[0112] By using certain designs for a memory array structure, the effective channel length (L_{eff}) may be enlarged to reduce or eliminate short-channel effects. Some examples may be designed to use no diffusion junctions, thereby avoiding the challenges in providing shallow junctions or using pocket implantations during the manufacturing processes of memory devices.

[0113] FIG. 1 illustrates an example of a memory device having an SONOS design. In addition, Table 1 noted above illustrates an example of materials used for different layers and their thicknesses. In some examples, P+-polysilicon gate may be used to provide a lower saturated Reset/Erase V_t , which may be achieved by reducing gate injection.

[0114] FIGS. 22a and 22b illustrate an example of a memory array, such as an SONOS-NAND array having memory cells in accordance with embodiment described in Table 1, with diffusion junctions. In one example, separate devices may be isolated from each other by various isolation techniques, such as by using shallow-trench isolation (STI) or the isolation technique of silicon-on-insulator (SOI). Referring to FIG. 22a, a memory array may include multiple bit lines, such as BL1 and BL2, and multiple word lines, such as WL1, WLN-1, and WLN. Additionally, the array may include source line transistor(s) (or source-line-selecting transistor(s) or SLTs) and bit line transistor(s) (or bit-line-selecting transistor(s) or BLTs). As illustrated, the memory cells in the array may use an SONOS design, and the SLT and BLT may include n-type metal-oxide-semiconductor field-effect transistors (NMOSFETs).

[0115] FIG. 22b illustrates an exemplary layout of a memory array, such as a NAND array. Referring to FIG. 22b, L_g is the channel length of memory cells, and L_s is the space between each separate lines of memory devices. Additionally, W is the channel width of memory cells, and W_s is the width of isolation areas between separate bit lines or source/drain areas, which may be the STI width in one example.

[0116] Referring again to FIGS. 22a and 22b, the memory devices may be connected in series and form a NAND array. For example, a string of memory devices may include 16 or 32 memory devices, providing a string number of 16 or 32. The BLTs and SLTs may be used as selecting transistors to control the corresponding NAND strings. In one example, the gate dielectric for BLTs and SLTs may be a silicon oxide layer that does not include a silicon nitride trapping layer. Such configuration, although not necessarily required in every case, may avoid possible V_t shift of BLTs and SLTs during the operations of the memory array in some examples. Alternatively, the BLTs and SLTs may use the combination of ONONO layers as their gate dielectric layers.

[0117] In some examples, the gate voltages applied to BLTs and SLTs may be less than 10 V, which may cause less gate disturb. In cases where the gate dielectric layer of BLTs and SLTs may be charged or trapped with charges, additional $-V_g$ erase can be applied to the gates of BLT or SLT to discharge their gate dielectric layers.

[0118] Referring again to FIG. 22a, each BLT may be coupled to a bit-line (BL). In one example, a BL may be a metal line having the same or approximately the same pitch to that of STI. Also, each SLT is connected to a source line (SL). The source line is parallel to the WL and connected to the sense amplifier for read sensing. The source line may be a metal, such as tungsten, or polysilicon line, or a diffusion N+-doped line.

[0119] FIG. 23a illustrates a cross-sectional view of an exemplary memory array, such as an SONOS-NAND memory array, along the channel-length direction. Typically, L_g and L_s is approximately equal to F , which generally represents the critical dimension of a device (or node). The critical dimension may vary with the technologies used for fabrication. For example, $F=50$ nm stands for using a 50 nm node. FIG. 23b illustrates a cross-sectional view of an exemplary memory array, such as an SONOS-NAND memory array, along the channel-width direction. Referring to FIG. 23b, the pitch in the channel-width direction is approximately equal or slightly larger than that in the channel length direction. Therefore, the size of a memory cell is approximately $4F^2/\text{cell}$.

[0120] In examples of manufacturing a memory array, such as the arrays noted above, the processes may involve using only two primary masks or lithography processes, such as one for the polysilicon (word line) and another for STI (bit lines). In contrast, the manufacturing of NAND-type floating gate devices may require at least two-poly processing and another inter-poly ONO processing. Accordingly, the structure and manufacturing processes of the proposed devices may be simpler than those of NAND-type floating gate memories.

[0121] Referring to FIG. 23a, in one example, the spaces (L_s) between word lines (WLs) may be formed with shallow junctions, such as shallow junctions of N+-doped regions, which may serve as source or drain regions of the memory devices. As illustrated in FIG. 23A, additional implantation and/or diffusion process, such as a tilt-angle pocket implantation, may be carried out to provide one or more "pocket" regions or pocket extensions of junctions that neighbor one or more of the shallow junction regions. In some examples, such configuration may provide better device characteristics.

[0122] In examples where STI is used of isolating separate memory devices, the trench depth of STI regions may be larger than the depletion width in p-well, especially when the junction bias used is raised higher. For example, the junction bias may be as high as about 7V for program inhibited bit line(s) (unselected bit line(s) during programming). In one example, the depth of STI regions may be in the range of about 200 to 400 nm.

[0123] After a memory array is manufactured, a reset operation may be performed to tighten the V_t distribution first before other operations of the memory array. FIG. 24a illustrates an examples of such operation. In one example, before other operations start, one may first apply V_G =about -7 V and $V_{P\text{-well}}$ = $+8$ V to reset the array (The voltage drop of V_G and $V_{P\text{-Well}}$ can be partitioned into the gate voltage into each WL and p-well). During RESET, the BL's can be floating, or raised to the same voltage as the P-Well. As illustrated in FIG. 24b, the reset operation may provide excellent self-convergent properties. In one example, even SONOS devices are initially charged to various V_t s, the

reset operation can “tighten” them to a Reset/Erase state. In one example, the reset time is about 100 msec. In that example, the memory array may use n-channel SONOS devices with $\text{ONONO}=15/20/18/70/90$ angstroms having an N+-polysilicon gate with $L_g/W=0.22/0.16$ μm .

[0124] Generally, traditionally floating-gate devices are not capable of providing self-converging erase. In contrast, SONOS devices may be operated with converging Reset/Erase methods. In some examples, this operation may become essential because the initial V_t distribution is often in a wide range due to certain process issues, such as process non-uniformity or plasma charging effects. The exemplary self-converging “Reset” may help to tighten, or narrow the range of, the initial V_t distribution of memory devices.

[0125] In one example of programming operations, the selected WL may be applied with a high voltage, such as a voltage of about +16 V to +20 V, to induce channel +FN injection. Other PASS gates (other unselected WL's) may be turned on to induce the inversion layer in a NAND string. +FN programming may be a low-power method in some examples. In one example, parallel programming methods such as page programming with 4 K Bytes cells in parallel can burst the programming throughput to more than 10 MB/sec, while the total current consumption can be controlled within 1 mA. In some examples, to avoid program disturb in other BLs, a high voltage, such as a voltage of about 7 V may be applied to other BLs so that the inversion layer potential is raised higher to suppress the voltage drop in the unselected BLs (such as cell B in FIG. 25).

[0126] In examples of read operations, the selected WL may be raised to a voltage that is between an erased state level (EV) and a programmed state level (PV). Other WLs may serve as the “PASS gates” so that their gate voltages may be raised a voltage higher than PV. In some examples, erase operations may be similar to the reset operation noted above, which may allow self-convergence to the same or similar reset V_t .

[0127] FIG. 25 illustrates an example of operating a memory array. Programming may include channel +FN injection of electrons into an SONOS nitride trapping layer. Some examples may include applying V_g =about +18 V to the selected WLN-1, and applying V_g =about +10 V to other WLs, as well as the BLT. The SLT can be turned off to avoid channel hot electron injection in cell B. In this example, because all the transistors in the NAND string are turned-on, the inversion layer passes through the strings. Furthermore, because BL1 is grounded, the inversion layer in BL1 has zero potential. On the other hand, other BLs are raised to a high potential, such as a voltage of about +7 V, so that the inversion layer of other BLs are higher.

[0128] In particular, for cell A, which is the cell selected for programming, the voltage drop is about +18 V, which causes +FN injection. And the V_t may be raised to PV. For cell B, the voltage drop is +11 V, causing much less +FN injection, as FN injection is sensitive to V_g . For cell C, only +10 V is applied, causing no or negligible +FN injection. In some examples, a programming operation is not limited to the technique illustrated. In other words, other adequate program inhibit techniques may be applied.

[0129] FIGS. 24a, 26, and 27 further illustrate some examples of array operations and illustrate the endurance

and retention properties of some examples. As illustrated, the device degradation after a number of operation cycles may remain very small. FIG. 24A illustrates an exemplary erase operation, which may be similar to a reset operation. In one example, the erase is performed by sector or block. As noted above, the memory devices may have good self-converging erase property. In some examples, the erase saturation V_t may be dependent on V_g . For example, a higher V_g may cause a higher saturated V_t . As illustrated in FIG. 26B, the convergent time may be around 10 to 100 msec.

[0130] FIG. 27 illustrates an exemplary reading operation. In one example, reading may be performed by applying a gate voltage that is between an erased state V_t (EV) and a programmed state V_t (PV). For example, the gate voltage may be about 5 V. On the other hand, other WLs and BLT and SLT are applied with a higher gate voltage, such as a voltage of about +9 V, to turn-on all the other memory cells. In one example, if V_t of cell A is higher than 5 V, the read current may be very small (<0.1 μA). If V_t of cell A is lower than 5 V, the read current may be higher (>0.1 μA). As a result, the memory state, i.e. the stored information, can be identified.

[0131] In some examples, the pass gate voltage for other WLs should be higher than the high- V_t state or the programmed state V_t , but not too high to trigger gate disturb. In one example, the PASS voltage is in the range of about 7 to 10 V. The applied voltage at the BL may be about 1 V. Although a larger read voltage may induce more current, the read disturb may become more apparent in some examples. In some examples, the sensing amplifier can be either placed on a source line (source sensing) or on a bit line (drain sensing).

[0132] Some examples of NAND strings may have 8, 16, or 32 memory devices per string. A larger NAND string may save more overhead and increase array efficiency. However, in some examples, the read current may be smaller and disturb may become more apparent. Therefore, adequate numbers of NAND string should be chosen based on various design, manufacture, and operation factors.

[0133] FIG. 28 illustrates the cycle endurance of certain exemplary devices. Referring to FIG. 28, P/E cycles with +FN program and -FN erase may be carried out, and the results suggest good endurance characteristics. In this example, the erase condition is V_g =about -16 V for 10 msec. In some examples, only single shot of erase is needed and verification of status is not necessary. The memory V_t window is good without degradation.

[0134] FIGS. 29a and 29b illustrate the IV characteristics of exemplary memory devices using different scales. In particular, FIG. 29a illustrates a small swing degradation of the device, and FIG. 29b illustrates a small gm degradation of the device. FIG. 30 illustrates the retention characteristics of an exemplary SONOS device. Referring to FIG. 30, a good retention is provided by having less than 100 mV charge loss for device operated after 10K cycles and after leaving for 200 hours at room temperature. FIG. 30 also illustrates an acceptable charge loss at high temperatures.

[0135] In some examples, a split-gate design, such as a split-gate SONOS-NAND design, may be used to achieve a more aggressive down-scaling of a memory array.

FIG. 31 illustrates an example of using such design. Referring to **FIG. 31**, the spaces (Ls) between each word line, or between two neighboring memory devices sharing the same bit line, may be reduced. In one example, Ls may be shrunk to about or less than 30 nm. As illustrated, the memory devices using a split-gate design along the same bit line may share only one source region and one drain region. In other words, a split-gate SONOS-NAND array may use no diffusion regions or junctions, such as N⁺-doped regions, for some of the memory devices. In one example, the design may also reduce or eliminate the need for shallow junctions and neighboring “pockets”, which in some examples may involve a more complicated manufacturing process. Furthermore, in some examples, the design is less affected by short-channel effects, because the channel length has been increased, such as increased to $L_g = 2F - L_s$ in one example.

[0136] **FIG. 32** illustrates an exemplary manufacturing process of a memory array using a split-gate design. The schematic diagram is merely an illustrative example, and the memory array may be designed and manufactured in various different ways. Referring to **FIG. 32**, after multiple layers of materials for providing the memory devices are formed, those layers may be patterned using a silicon oxide structure as a hard mask formed over those layers. For example, the silicon oxide regions may be defined by lithography and etching processes. In one example, the pattern used for defining the initial silicon oxide regions may have a width of about F and the space between the silicon oxide regions of about F, resulting a pitch of about 2F. After the initial silicon oxide regions are patterned, silicon oxide spacers may then be formed surrounding the patterned regions to enlarge each silicon oxide region and narrow their spacing.

[0137] Referring again to **FIG. 32**, after the silicon oxide regions are formed, they are used as a hard mask to define or pattern their underlying layers to provide one or more memory devices, such as multiple NAND strings. In addition, insulating materials, such as silicon oxide, may be used to fill in the spaces, such as Ls spaces shown in **FIG. 32**, between the neighboring memory devices.

[0138] In one example, the space Ls between neighboring memory devices along the same bit line may be in the range of about 15 nm to about 30 nm. As noted above, the effective channel length may be enlarged to $2F - L_s$ in this example. In one example, if F is about 30 nm and Ls is about 15 nm, L_{eff} is about 45 nm. For the operation of those exemplary memory devices, the gate voltage may be reduced to below 15 V. In addition, the inter-polysilicon voltage drop between word lines may be designed to be no larger than 7V to avoid breakdown of the spacers in the Ls spaces. In one example, this may be achieved by having an electric field of less than 5 MV/cm between neighboring word lines.

[0139] The L_{eff} with diffusion junctions for conventional NAND floating-gate devices is about half of the their gate length. In contrast, if F is about 50 nm and L_{eff} is about 30 nm, L_{eff} is about 80 nm for the proposed design (the split-gate NAND) in one example. The longer L_{eff} can provide better device characteristics by reducing or eliminating the impact of short-channel effects.

[0140] As illustrated above, a split-gate NAND design may further shrink the space (Ls) between neighboring memory cells of the same bit line. In contrast, traditional NAND-type floating-gate devices may not provide a small

spacing, because inter-floating-gate coupling effect may lose the memory window. The inter-floating gate coupling is the interference between adjacent memory cells when the coupling capacitance between adjacent floating gate is high (the space between the floating gates is small so that the coupling capacitance between the adjacent floating gates becomes very high such that read disturb happens). As noted above, the design may eliminate the need to fabricate certain diffusion junctions, and the inversion layer can be directly connected if all the word lines are turned on. Therefore, the design may simplify the manufacturing process of memory devices.

[0141] As illustrated, some examples noted above, including the structural design, array design, and operation of memory devices, may provide desirable array dimension, good reliability, good performance, or the combination of any of them. Some examples noted may be applicable for down-scaling the dimensions of non-volatile flash memories, such as NAND flash memories and flash memory for data applications. Some examples may provide SONOS devices with uniform and self-converging channel hole-tunneling erase. Some examples also may provide good endurance of memory devices and reduce certain no hard-to-erase or over-erase issues. Also, good device characteristics, such as small degradations after P/E cycles and good charge retention, may be provided. Device uniformity within a memory array may be provided without having erratic bits or cells. Furthermore, some examples may provide good short-channel device characteristics via a split-gate NAND design, which may offer a better sense margin during the operations of the memory devices.

[0142] The foregoing disclosure of the preferred embodiments of the present invention has been presented for purposes of illustration and description. It is not intended to be exhaustive or to limit the invention to the precise forms disclosed. It will be appreciated by those skilled in the art that changes could be made to the embodiments described above without departing from the broad inventive concept thereof. It is understood, therefore, that this invention is not limited to the particular embodiments disclosed, but it is intended to cover modifications within the spirit and scope of the present invention as defined by the appended claims.

What is claimed is:

1. A memory cell comprising:

- a semiconductor substrate having a source region and a drain region disposed below a surface of the substrate and separated by a channel region;
- a tunnel dielectric structure disposed above the channel region, the tunnel dielectric structure comprising at least one layer having a small hole-tunneling-barrier height;
- a charge storage layer disposed above the tunnel dielectric structure;
- an insulating layer disposed above the charge storage layer; and
- a gate electrode disposed above the insulating layer, wherein the gate electrode comprises a material having a work function value greater than that of N⁺ polysilicon.

2. The memory cell according to claim 1, wherein the gate electrode comprises platinum.

3. The memory cell according to claim 1, wherein the tunnel dielectric structure comprises at least two dielectric layers each having a thickness of up to about 4 nm.

4. The memory cell according to claim 1, wherein the tunnel dielectric structure comprises a first silicon oxide layer, a first silicon nitride layer above the first silicon oxide layer, and a second silicon oxide layer above the first silicon nitride layer.

5. The memory cell according to claim 1, wherein the charge storage layer comprises at least one material selected from the group consisting of silicon nitride, Al_2O_3 , and HfO_2 .

6. The memory cell according to claim 1, wherein the insulating layer comprises silicon oxide.

7. The memory cell according to claim 1, wherein the tunnel dielectric structure has a negligible trapping efficiency.

8. A memory array comprising a plurality of memory cells according to claim 1.

9. The memory array according to claim 8, wherein at least two of the plurality of memory cells are separated from each other by at least one of a shallow-trench isolation and a silicon-on-insulator isolation.

10. The memory array according to claim 8, wherein the memory array comprises at least two word lines, at least two bit lines, and at least one source line.

11. The memory array according to claim 8, wherein the memory array comprises at least one bit line selecting transistor coupled to a corresponding bit line.

12. The memory array according to claim 8, wherein the memory array comprises at least one source line selecting transistor coupled to a corresponding source line.

13. The memory array according to claim 8, wherein the substrate comprises at least a pair of shallow junctions for the memory device.

* * * * *