US009020697B2

(12) **United States Patent**
Ricci et al.

(10) **Patent No.: US 9,020,697 B2**
(45) **Date of Patent: Apr. 28, 2015**

(54) **VEHICLE-BASED MULTIMODE DISCOVERY**

(71) Applicant: **Flextronics AP, LLC**, San Jose, CA (US)

(72) Inventors: **Christopher P. Ricci**, Saratoga, CA (US); **Octavian Chincisan**, Richmond Hill (CA); **Alisher I. Yusupov**, Richmond Hill (CA)

(73) Assignee: **Flextronics AP, LLC**, San Jose, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/253,312**

(22) Filed: **Apr. 15, 2014**

(65) **Prior Publication Data**

US 2014/0309870 A1 Oct. 16, 2014

Related U.S. Application Data

(60) Provisional application No. 61/811,981, filed on Apr. 15, 2013, provisional application No. 61/865,954, filed on Aug. 14, 2013, provisional application No. 61/870,698, filed on Aug. 27, 2013, provisional application No. 61/891,217, filed on Oct. 15, 2013, provisional application No. 61/904,205, filed on Nov. 14, 2013, provisional application No. 61/924,572, filed on Jan. 7, 2014, provisional application No. 61/926,749, filed on Jan. 13, 2014.

(51) **Int. Cl.**
G06F 21/00 (2013.01)
G07C 9/00 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC ***G07C 9/00158*** (2013.01); ***G07C 9/00126*** (2013.01); ***G08B 21/0205*** (2013.01); ***B60Q 1/00*** (2013.01); ***G08B 25/016*** (2013.01); ***G08G 1/0965*** (2013.01); ***H04W 76/021*** (2013.01); ***H04W 48/02*** (2013.01); ***H04W 4/12*** (2013.01); *H04W 4/206* (2013.01); *H04W 84/005* (2013.01); ***G05D 23/1917*** (2013.01); ***B60R 16/037*** (2013.01); ***G07C 5/00*** (2013.01); ***G07C 5/008*** (2013.01); ***G05D 1/0027*** (2013.01); ***G01C 21/00*** (2013.01); ***G06F 17/30864*** (2013.01); ***G01C 21/34*** (2013.01); ***G05D 1/0212*** (2013.01); ***B60W 40/09*** (2013.01); ***G07C 5/085*** (2013.01); ***G07C 5/0808*** (2013.01); ***G06F 17/30247*** (2013.01); ***G06K 9/00268*** (2013.01); ***B60W 50/08*** (2013.01); ***G06F 21/00*** (2013.01); ***G06F 3/017*** (2013.01); ***B60R 16/0373*** (2013.01); ***H04W 4/046*** (2013.01); ***G06K 9/00255*** (2013.01); ***H04W 36/32*** (2013.01); ***G08G 1/166*** (2013.01);
(Continued)

(58) **Field of Classification Search**
USPC 701/36
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,754,255 A 6/1988 Sanders et al.
5,204,817 A 4/1993 Yoshida
(Continued)

FOREIGN PATENT DOCUMENTS

EP 1909069 12/2010
KR 2006-0128484 12/2006
WO WO 2012/102879 8/2012

OTHER PUBLICATIONS

U.S. Appl. No. 14/543,535, filed Nov. 17, 2014, Ricci.
(Continued)

Primary Examiner — Thomas Tarcza
Assistant Examiner — Alex C Dunn
(74) *Attorney, Agent, or Firm* — Sheridan Ross P.C.

(57) **ABSTRACT**

Methods and systems for a device discovery daemon that bases access of a communication device to an on board vehicle network on device location are provided.

21 Claims, 51 Drawing Sheets



(51) **Int. Cl.**

G08B 21/02	(2006.01)
B60Q 1/00	(2006.01)
G08B 25/01	(2006.01)
G08G 1/0965	(2006.01)
H04W 76/02	(2009.01)
H04W 48/02	(2009.01)
H04W 4/12	(2009.01)
G05D 23/19	(2006.01)
B60R 16/037	(2006.01)
G07C 5/00	(2006.01)
G05D 1/00	(2006.01)
G01C 21/00	(2006.01)
G06F 17/30	(2006.01)
G01C 21/34	(2006.01)
G05D 1/02	(2006.01)
B60W 40/09	(2012.01)
G07C 5/08	(2006.01)
G06K 9/00	(2006.01)
B60W 50/08	(2012.01)
G06F 3/01	(2006.01)
H04W 4/04	(2009.01)
H04W 36/32	(2009.01)
G08G 1/16	(2006.01)
G01C 21/36	(2006.01)
G06Q 30/06	(2012.01)
G01C 21/26	(2006.01)
G06F 17/28	(2006.01)
G06Q 10/02	(2012.01)
G06Q 20/14	(2012.01)
G06Q 50/30	(2012.01)
G06Q 30/02	(2012.01)
G06Q 10/00	(2012.01)
G06Q 30/00	(2012.01)
H04L 29/08	(2006.01)
G06F 3/0481	(2013.01)
G06F 3/0484	(2013.01)
G06F 9/445	(2006.01)
H04N 21/214	(2011.01)
H04N 21/218	(2011.01)
H04N 21/258	(2011.01)
H04N 21/414	(2011.01)
H04N 21/454	(2011.01)
H04N 21/475	(2011.01)
H04L 29/06	(2006.01)
H04W 4/20	(2009.01)
H04W 84/00	(2009.01)
G08G 1/0967	(2006.01)
H04N 7/18	(2006.01)
H04W 12/06	(2009.01)
H04W 12/08	(2009.01)

(52) **U.S. Cl.**

CPC ***G01C 21/36*** (2013.01); ***G06Q 30/0633*** (2013.01); ***G06Q 30/0639*** (2013.01); ***G01C 21/3647*** (2013.01); ***G01C 21/26*** (2013.01); ***G06F 17/28*** (2013.01); ***G06Q 10/02*** (2013.01); ***G06Q 30/0645*** (2013.01); ***G06Q 20/145*** (2013.01); ***G06Q 50/30*** (2013.01); ***G06Q 30/0265*** (2013.01); ***G06Q 10/20*** (2013.01); ***G06Q 30/012*** (2013.01); ***G06F 17/30557*** (2013.01); ***H04L 67/12*** (2013.01); ***G06F 3/016*** (2013.01); ***G06F 3/0481*** (2013.01); ***G06F 3/04842*** (2013.01); ***G06F 8/65*** (2013.01); ***H04N 21/214*** (2013.01); ***H04N 21/2181*** (2013.01); ***H04N 21/25841*** (2013.01); ***H04N 21/41422*** (2013.01); ***H04N 21/4542*** (2013.01); ***H04N 21/4751*** (2013.01); ***H04L 63/08*** (2013.01); *G08G 1/096725* (2013.01); *G08G 1/096741* (2013.01); *G08G 1/096775* (2013.01); *H04N 7/181* (2013.01); *H04W 12/06* (2013.01); *H04W 12/08* (2013.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,296,840	A	3/1994	Gieffers	
5,529,138	A	6/1996	Shaw et al.	
5,572,450	A	11/1996	Worthy	
5,825,283	A	10/1998	Camhi	
5,986,575	A	11/1999	Jones et al.	
6,148,261	A	11/2000	Obradovich et al.	
6,356,838	B1	3/2002	Paul	
6,557,752	B1	5/2003	Yacoob	
6,563,910	B2	5/2003	Menard et al.	
6,617,981	B2	9/2003	Basinger	
6,675,081	B2	1/2004	Shuman et al.	
6,892,131	B2	5/2005	Coffee et al.	
6,944,533	B2	9/2005	Obradovich et al.	
7,047,129	B2	5/2006	Uotani	
7,058,898	B2	6/2006	McWalter et al.	
7,142,696	B1	11/2006	Engelsberg et al.	
7,233,861	B2	6/2007	Van Buaer et al.	
7,239,960	B2	7/2007	Yokota et al.	
7,295,904	B2	11/2007	Kanevsky et al.	
7,313,547	B2	12/2007	Mocek et al.	
7,526,539	B1	4/2009	Hsu	
7,667,618	B2	2/2010	Chitor et al.	
7,748,021	B2	6/2010	Obradovich et al.	
7,864,073	B2	1/2011	Lee et al.	
7,873,471	B2	1/2011	Gieseke	
7,969,324	B2	6/2011	Chevion et al.	
8,233,919	B2	7/2012	Haag et al.	
8,245,609	B1	8/2012	Greenwald et al.	
8,350,721	B2 *	1/2013	Carr	340/903
8,417,449	B1	4/2013	Denise	
8,442,758	B1	5/2013	Rovik et al.	
8,509,982	B2	8/2013	Montemerlo et al.	
8,521,410	B2	8/2013	Mizuno et al.	
8,543,330	B2	9/2013	Taylor et al.	
8,552,886	B2	10/2013	Bensoussan	
8,578,279	B2	11/2013	Chen et al.	
8,613,385	B1	12/2013	Hulet et al.	
8,634,984	B2	1/2014	Sumizawa	
8,660,735	B2 *	2/2014	Tengler et al.	701/24
8,718,797	B1	5/2014	Addepalli et al.	
8,730,033	B2 *	5/2014	Yarnold et al.	340/539.13
8,788,220	B2	7/2014	Soles et al.	
8,793,034	B2 *	7/2014	Ricci	701/1
8,793,065	B2	7/2014	Seltzer et al.	
8,798,918	B2	8/2014	Onishi et al.	
8,818,725	B2	8/2014	Ricci	
8,825,277	B2	9/2014	McClellan et al.	
8,825,362	B2	9/2014	Kirsch	
8,825,382	B2	9/2014	Liu	
8,831,826	B2	9/2014	Ricci	
8,838,095	B2	9/2014	Jouin	
8,862,299	B2	10/2014	Ricci	
2002/0009978	A1 *	1/2002	Dukach et al.	455/99
2002/0026278	A1	2/2002	Feldman et al.	
2002/0065046	A1 *	5/2002	Mankins et al.	455/59
2002/0077985	A1	6/2002	Kobata et al.	
2002/0103622	A1	8/2002	Burge	
2002/0128774	A1	9/2002	Takezaki et al.	
2002/0143461	A1	10/2002	Burns et al.	
2002/0174021	A1	11/2002	Chu et al.	
2003/0004624	A1	1/2003	Wilson et al.	
2003/0060937	A1	3/2003	Shinada et al.	
2003/0065432	A1	4/2003	Shuman et al.	
2003/0101451	A1	5/2003	Bentolila et al.	
2003/0204290	A1	10/2003	Sadler et al.	
2004/0036622	A1 *	2/2004	Dukach et al.	340/691.6
2004/0039504	A1	2/2004	Coffee et al.	

(56) **References Cited**

U.S. PATENT DOCUMENTS

2004/0093155 A1 5/2004 Simonds et al.
2004/0153356 A1 8/2004 Lockwood et al.
2004/0204837 A1 10/2004 Singleton
2004/0217850 A1 11/2004 Perttunen et al.
2004/0225557 A1 11/2004 Phelan et al.
2004/0260470 A1 12/2004 Rast
2005/0038598 A1 2/2005 Oesterling et al.
2005/0065716 A1 3/2005 Timko et al.
2005/0097541 A1 5/2005 Holland
2005/0122235 A1 6/2005 Teffer et al.
2005/0159853 A1 7/2005 Takahashi et al.
2005/0197748 A1 9/2005 Holst et al.
2005/0261815 A1 11/2005 Cowelchuk et al.
2005/0283284 A1 12/2005 Grenier et al.
2006/0036358 A1 2/2006 Hale et al.
2006/0058948 A1 3/2006 Blass et al.
2006/0130033 A1 6/2006 Stoffels et al.
2006/0173841 A1 8/2006 Bill
2006/0287807 A1 12/2006 Teffer
2007/0061057 A1 3/2007 Huang et al.
2007/0135995 A1 6/2007 Kikuchi et al.
2007/0182625 A1 8/2007 Kerai et al.
2007/0192486 A1 8/2007 Wilson et al.
2007/0194944 A1 8/2007 Galera et al.
2008/0033635 A1 2/2008 Obradovich et al.
2008/0086455 A1 4/2008 Meisels et al.
2008/0104227 A1 5/2008 Birnie et al.
2008/0129475 A1 6/2008 Breed et al.
2008/0161986 A1 7/2008 Breed
2008/0169940 A1 7/2008 Lee et al.
2008/0255721 A1 10/2008 Yamada
2008/0300778 A1 12/2008 Kuznetsov
2009/0006525 A1 1/2009 Moore
2009/0119657 A1 5/2009 Link, II
2009/0125174 A1 5/2009 Delean
2009/0138336 A1* 5/2009 Ashley et al. 705/10
2009/0157312 A1 6/2009 Black et al.
2009/0222200 A1 9/2009 Link et al.
2009/0234578 A1 9/2009 Newby et al.
2009/0284359 A1 11/2009 Huang et al.
2009/0287405 A1 11/2009 Liu et al.
2009/0299572 A1 12/2009 Fujikawa et al.
2010/0023204 A1 1/2010 Basir et al.
2010/0036560 A1 2/2010 Wright et al.
2010/0057337 A1 3/2010 Fuchs
2010/0087984 A1 4/2010 Joseph
2010/0087987 A1 4/2010 Huang et al.
2010/0106344 A1 4/2010 Edwards et al.
2010/0106418 A1 4/2010 Kindo et al.
2010/0125387 A1 5/2010 Sehyun et al.
2010/0125405 A1 5/2010 Chae et al.
2010/0125811 A1 5/2010 Moore et al.
2010/0136944 A1 6/2010 Taylor et al.
2010/0137037 A1 6/2010 Basir
2010/0145700 A1 6/2010 Kennewick et al.
2010/0145987 A1 6/2010 Harper et al.
2010/0152976 A1 6/2010 White et al.
2010/0169432 A1* 7/2010 Santori et al. 709/206
2010/0174474 A1 7/2010 Nagase
2010/0211300 A1 8/2010 Jaffe et al.
2010/0211304 A1 8/2010 Hwang et al.
2010/0211441 A1 8/2010 Sprigg et al.
2010/0222939 A1 9/2010 Namburu et al.
2010/0235891 A1* 9/2010 Oglesbee et al. 726/5
2010/0274410 A1 10/2010 Tsien et al.
2010/0289643 A1 11/2010 Trundle et al.
2010/0304640 A1 12/2010 Sofman et al.
2010/0305807 A1* 12/2010 Basir et al. 701/33
2010/0306309 A1 12/2010 Santori et al.
2010/0321151 A1 12/2010 Matsuura et al.
2010/0332130 A1 12/2010 Shimizu et al.
2011/0040438 A1 2/2011 Kluge et al.
2011/0077808 A1 3/2011 Hyde et al.
2011/0078024 A1 3/2011 Messier et al.
2011/0090078 A1 4/2011 Kim et al.
2011/0093438 A1 4/2011 Poulsen
2011/0112717 A1 5/2011 Resner
2011/0137520 A1 6/2011 Rector et al.
2011/0184642 A1 7/2011 Rotz et al.
2011/0197187 A1 8/2011 Roh
2011/0210867 A1 9/2011 Benedikt
2011/0246210 A1 10/2011 Matsur
2011/0247013 A1 10/2011 Feller et al.
2011/0257973 A1 10/2011 Chutorash et al.
2011/0291926 A1 12/2011 Gokturk et al.
2011/0301844 A1 12/2011 Aono
2011/0309926 A1 12/2011 Eikelenberg et al.
2011/0309953 A1 12/2011 Petite et al.
2011/0313653 A1 12/2011 Lindner
2011/0320089 A1 12/2011 Lewis
2012/0010807 A1 1/2012 Zhou
2012/0030512 A1 2/2012 Wadhwa et al.
2012/0046822 A1 2/2012 Anderson
2012/0047530 A1 2/2012 Shkedi
2012/0053793 A1 3/2012 Sala et al.
2012/0053888 A1 3/2012 Stahlin et al.
2012/0059789 A1 3/2012 Sakai et al.
2012/0065815 A1 3/2012 Hess
2012/0105613 A1 5/2012 Weng et al.
2012/0188876 A1 7/2012 Chow et al.
2012/0197523 A1 8/2012 Kirsch
2012/0204166 A1 8/2012 Ichihara
2012/0254763 A1 10/2012 Protopapas et al.
2012/0254804 A1 10/2012 Shema et al.
2012/0289253 A1 11/2012 Haag et al.
2012/0316720 A1 12/2012 Hyde et al.
2012/0323413 A1 12/2012 Kedar-Dongarkar et al.
2012/0327231 A1 12/2012 Cochran et al.
2013/0019252 A1 1/2013 Haase et al.
2013/0024060 A1 1/2013 Sukkari et al.
2013/0030645 A1 1/2013 Divine et al.
2013/0031540 A1 1/2013 Throop et al.
2013/0055096 A1 2/2013 Kim et al.
2013/0059607 A1 3/2013 Herz et al.
2013/0066512 A1 3/2013 Willard et al.
2013/0079964 A1 3/2013 Sukkarie et al.
2013/0083805 A1 4/2013 Lu et al.
2013/0099915 A1 4/2013 Prasad et al.
2013/0116882 A1 5/2013 Link et al.
2013/0116915 A1 5/2013 Ferreira et al.
2013/0134730 A1 5/2013 Ricci
2013/0135118 A1 5/2013 Ricci
2013/0138591 A1 5/2013 Ricci
2013/0138714 A1 5/2013 Ricci
2013/0139140 A1 5/2013 Rao et al.
2013/0141247 A1 6/2013 Ricci
2013/0141252 A1 6/2013 Ricci
2013/0143495 A1 6/2013 Ricci
2013/0143546 A1 6/2013 Ricci
2013/0143601 A1 6/2013 Ricci
2013/0144459 A1 6/2013 Ricci
2013/0144460 A1 6/2013 Ricci
2013/0144461 A1 6/2013 Ricci
2013/0144463 A1 6/2013 Ricci et al.
2013/0144470 A1 6/2013 Ricci
2013/0144486 A1 6/2013 Ricci
2013/0144520 A1 6/2013 Ricci
2013/0144657 A1 6/2013 Ricci
2013/0145065 A1 6/2013 Ricci
2013/0145279 A1 6/2013 Ricci
2013/0145297 A1 6/2013 Ricci et al.
2013/0145360 A1 6/2013 Ricci
2013/0145401 A1 6/2013 Ricci
2013/0145482 A1 6/2013 Ricci et al.
2013/0147638 A1 6/2013 Ricci
2013/0151065 A1 6/2013 Ricci
2013/0151088 A1 6/2013 Ricci
2013/0152003 A1 6/2013 Ricci et al.
2013/0154298 A1 6/2013 Ricci
2013/0158821 A1 6/2013 Ricci
2013/0166096 A1 6/2013 Jotanovic
2013/0166097 A1 6/2013 Ricci
2013/0166208 A1 6/2013 Forstall et al.
2013/0167159 A1 6/2013 Ricci et al.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2013/0197796 A1 8/2013 Obradovich et al.
2013/0198031 A1 8/2013 Mitchell et al.
2013/0204455 A1 8/2013 Chia et al.
2013/0207794 A1 8/2013 Patel et al.
2013/0212065 A1 8/2013 Rahnama
2013/0218445 A1 8/2013 Basir
2013/0219039 A1 8/2013 Ricci
2013/0226365 A1 8/2013 Brozovich
2013/0231784 A1 9/2013 Rovik et al.
2013/0241720 A1 9/2013 Ricci et al.
2013/0245882 A1 9/2013 Ricci
2013/0261966 A1 10/2013 Wang et al.
2013/0282946 A1 10/2013 Ricci
2013/0293364 A1 11/2013 Ricci et al.
2013/0293452 A1 11/2013 Ricci et al.
2013/0295913 A1 11/2013 Matthews et al.
2013/0300554 A1 11/2013 Braden
2013/0304371 A1 11/2013 Kitatani et al.
2013/0338914 A1 12/2013 Weiss
2013/0345929 A1 12/2013 Bowden et al.
2014/0028542 A1 1/2014 Lovitt et al.
2014/0058672 A1 2/2014 Wansley et al.
2014/0067201 A1 3/2014 Visintainer et al.
2014/0067564 A1 3/2014 Yuan
2014/0109075 A1 4/2014 Hoffman et al.
2014/0169621 A1 6/2014 Burr
2014/0220966 A1 8/2014 Muetzel et al.
2014/0244111 A1 8/2014 Gross et al.
2014/0244156 A1 8/2014 Magnusson et al.
2014/0245278 A1 8/2014 Zellen
2014/0245284 A1 8/2014 Alrabady et al.
2014/0278070 A1 9/2014 McGavran et al.
2014/0278071 A1 9/2014 San Filippo et al.
2014/0282470 A1 9/2014 Buga et al.
2014/0292545 A1 10/2014 Nemoto
2014/0306799 A1 10/2014 Ricci
2014/0306814 A1 10/2014 Ricci
2014/0306817 A1 10/2014 Ricci
2014/0306826 A1 10/2014 Ricci
2014/0306833 A1 10/2014 Ricci
2014/0306834 A1 10/2014 Ricci
2014/0306835 A1 10/2014 Ricci
2014/0307655 A1 10/2014 Ricci
2014/0307724 A1 10/2014 Ricci
2014/0308902 A1 10/2014 Ricci
2014/0309789 A1 10/2014 Ricci
2014/0309790 A1 10/2014 Ricci
2014/0309804 A1 10/2014 Ricci
2014/0309805 A1 10/2014 Ricci
2014/0309806 A1 10/2014 Ricci
2014/0309813 A1 10/2014 Ricci
2014/0309814 A1 10/2014 Ricci et al.
2014/0309815 A1 10/2014 Ricci et al.
2014/0309838 A1 10/2014 Ricci
2014/0309839 A1 10/2014 Ricci et al.
2014/0309847 A1 10/2014 Ricci
2014/0309849 A1 10/2014 Ricci
2014/0309852 A1 10/2014 Ricci
2014/0309853 A1 10/2014 Ricci
2014/0309862 A1 10/2014 Ricci
2014/0309863 A1 10/2014 Ricci
2014/0309864 A1 10/2014 Ricci
2014/0309865 A1 10/2014 Ricci
2014/0309866 A1 10/2014 Ricci
2014/0309867 A1 10/2014 Ricci
2014/0309868 A1 10/2014 Ricci
2014/0309869 A1 10/2014 Ricci
2014/0309871 A1 10/2014 Ricci
2014/0309872 A1 10/2014 Ricci
2014/0309873 A1 10/2014 Ricci
2014/0309874 A1 10/2014 Ricci
2014/0309875 A1 10/2014 Ricci
2014/0309876 A1 10/2014 Ricci
2014/0309877 A1 10/2014 Ricci
2014/0309878 A1 10/2014 Ricci
2014/0309879 A1 10/2014 Ricci
2014/0309880 A1 10/2014 Ricci
2014/0309885 A1 10/2014 Ricci
2014/0309886 A1 10/2014 Ricci
2014/0309891 A1 10/2014 Ricci
2014/0309892 A1 10/2014 Ricci
2014/0309893 A1 10/2014 Ricci
2014/0309913 A1 10/2014 Ricci et al.
2014/0309919 A1 10/2014 Ricci
2014/0309920 A1 10/2014 Ricci
2014/0309921 A1 10/2014 Ricci et al.
2014/0309922 A1 10/2014 Ricci
2014/0309923 A1 10/2014 Ricci
2014/0309927 A1 10/2014 Ricci
2014/0309929 A1 10/2014 Ricci
2014/0309930 A1 10/2014 Ricci
2014/0309934 A1 10/2014 Ricci
2014/0309935 A1 10/2014 Ricci
2014/0309982 A1 10/2014 Ricci
2014/0310031 A1 10/2014 Ricci
2014/0310075 A1 10/2014 Ricci
2014/0310103 A1 10/2014 Ricci
2014/0310186 A1 10/2014 Ricci
2014/0310277 A1 10/2014 Ricci
2014/0310379 A1 10/2014 Ricci et al.
2014/0310594 A1 10/2014 Ricci et al.
2014/0310610 A1 10/2014 Ricci
2014/0310702 A1 10/2014 Ricci et al.
2014/0310739 A1 10/2014 Ricci et al.
2014/0310788 A1 10/2014 Ricci
2015/0007155 A1 1/2015 Hoffman et al.

OTHER PUBLICATIONS

"Accessibility A guide for Businesses and Organizations," Microsoft, 2011, 53 pages.
"Accessibility Guide for Educators," Microsoft, 2014, 1 page [retrieved from www.microsoft.com/enable/education/].
"Guide for Individuals with Language and Communication Impairments," Microsoft, 2014, 9 pages [retrieved from www.microsoft.com/enable/guides/language.aspx].
"Guide for Individuals with Vision Impairments," Microsoft, 2014, 8 pages [retrieved from www.microsoft/com/enable/guides/vision.aspx].
"Guide for Individuals with Age-related Impairments," Microsoft, 2014, 1 page [retrieved from www.icrosoft.com/enable/aging].
"Guide for Individuals with Learning Impairments," Microsoft, 2014, 1 page [retrieved from www.microsoft.com/enable/guides/learning.aspx].
"Guide for Individuals with Dexterity and Mobility Impairments," Microsoft, 2014, 6 pages [retrieved from www.microsoft.com/enable/guides/dexterity.aspx].
"Guide for Individuals with Hearing Impairments," Microsoft, 2014, 5 pages [retrieved from www.microsoft.com/enable/guides/hearing.aspx].
Bennett "Meet Samsung's Version of Apple AirPlay," CNET.com, Oct. 10, 2012, 11 pages [retrieved from the internet on Aug. 14, 2014 from www.cnet.com/products/samsung-allshare-cast-hub-eadt10jdegsta/].
International Search Report and Written Opinion for International (PCT) Patent Application No. PCT/US2014/034092, mailed Aug. 22, 2014 8 pages.
International Search Report and Written Opinion for International (PCT) Patent Application No. PCT/US2014/034099, mailed Aug. 25, 2014 8 pages.
International Search Report and Written Opinion for International (PCT) Patent Application No. PCT/US2014/034087, mailed Aug. 22, 2014 7 pages.
International Search Report and Written Opinion for International (PCT) Patent Application No. PCT/US14/34232, mailed Sep. 15, 2014 8 pages.
International Search Report and Written Opinion for International (PCT) Patent Application No. PCT/US14/34098, mailed Sep. 15, 2014 10 pages.

(56) **References Cited**

OTHER PUBLICATIONS

International Search Report and Written Opinion for International (PCT) Patent Application No. PCT/US14/34108, mailed Sep. 15, 2014 7 pages.
International Search Report and Written Opinion for International (PCT) Patent Application No. PCT/US2014/034101, mailed Aug. 22, 2014 7 pages.
International Search Report and Written Opinion for International (PCT) Patent Application No. PCT/US2014/034103, mailed Sep. 3, 2014 7 pages.
International Search Report and Written Opinion for International (PCT) Patent Application No. PCT/US14/34114, mailed Sep. 15, 2014 9 pages.
International Search Report and Written Opinion for International (PCT) Patent Application No. PCT/US14/34125, mailed Sep. 15, 2014 8 pages.
International Search Report and Written Opinion for International (PCT) Patent Application No. PCT/US14/34254, mailed Sep. 15, 2014 10 pages.
Official Action for U.S. Appl. No. 14/253,729, mailed Nov. 19, 2014 8 pages.
Official Action for U.S. Appl. No. 14,253,405, mailed Nov. 18, 2014 6 pages.
Official Action for U.S. Appl. No. 14/253,838, mailed Nov. 20, 2014 31 pages.
Official Action for U.S. Appl. No. 14/253,506, mailed Nov. 14, 2014 9 pages.
International Search Report and Written Opinion for International (PCT) Patent Application No. PCT/US2014/034088, mailed Dec. 24, 2014, 9 pages.
Official Action for U.S. Appl. No. 14/253,836, mailed Feb. 24, 2015, 12 pages.
Official Action for U.S. Appl. No. 14/253,706, mailed Jan. 29, 2015, 8 pages.
Official Action for U.S. Appl. No. 14/253,729, mailed Mar. 6, 2015, 7 pages.
Official Action for U.S. Appl. No. 14/253,2014, mailed Jan. 26, 2015, 6 pages.
Official Action for U.S. Appl. No. 14/252,858, mailed Jan. 26, 2015, 8 pages.
Official Action for U.S. Appl. No. 14/253,034, mailed Jan. 26, 2015, 12 pages.
Notice of Allowance for U.S. Appl. No. 14/253,405, mailed Mar. 5, 2015, 5 pages.
Official Action for U.S. Appl. No. 14/252,876, mailed Jan. 30, 2015, 9 pages.
Official Action for U.S. Appl. No. 14/253,334, mailed Jan. 27, 2015, 13 pages.
Notice of Allowance for U.S. Appl. No. 14/253,058, mailed Jan. 28, 2015, 9 pages.
Official Action for U.S. Appl. No. 14/253,022, mailed Feb. 20, 2015, 13 pages.
Official Action for U.S. Appl. No. 14/253,251, mailed Dec. 29, 2014, 8 pages.
Official Action for U.S. Appl. No. 14/253,388, mailed Jan. 30, 2015, 8 pages.
Official Action for U.S. Appl. No. 14/253,727, mailed Jan. 6, 2015, 8 pages.
Official Action for U.S. Appl. No. 14/253,743, mailed Feb. 12, 2015, 8 pages.
Official Action for U.S. Appl. No. 14/253,766, mailed Dec. 12, 2014, 7 pages.
Notice of Allowance for U.S. Appl. No. 14/253,506, mailed Mar. 6, 2015, 5 pages.
International Search Report and Written Opinion for International (PCT) Patent Application No. PCT/US14/034194, mailed Dec. 31, 2014, 11 pages.

* cited by examiner



Fig. 1


248N
248A
248
242
242A
242B
242N
244
Vehicle Sensors
Sensor 1
Sensor 2
Sensor N
Sensor Memory
Wired/Wireless Transceiver/ Communications Port(s)
260
252
Profile Data
228
Server
Communication Network
Non-Vehicle Sensor(s)
236
Vehicle Control System
204
Stored Data
Profile Data
232
252
224
Diagnostic Communications Module
256
System Data
208
User
212
216
200
Device Data
Profile Data
220
252

Fig. 2


300
204
Vehicle Control System
304
Processor
308
Memory
312
I/O Module
316
Power Source and Power Control Module
208
System Data
320
Data Storage
252
Profile Data
356
324
User Interface(s)/ Input Interface(s)
328
Vehicle Subsystems
332
User Interaction Subsystem
336
Navigation Subsystems
340
Sensor(s)/Sensor Subsystems
344
Communication Subsystems
348
Media Subsystems
352
Device Interaction Subsystem

Fig. 3


400
420
404
IP Router
WiMax, 4G LGE Etc.
Operator Cluster
424
Storage
428
Master Blade
432
Comp Blade 1
436
Comp Blade N
440
Remote Display 1
444
Remote Display N
448
Console Display
452
I/O Network / Bus
408
412
416
409
413
417
Communication Channel(s)/ Ethernet Zones/ Optionally connected with 224
Access Point, e.g., WiFi
802.11x
456
Bluetooth® Access Point / USB
Bluetooth®
460
FemtoCell
3G/LTE
464
Storage Controller
468
Firewall
484
GPS
488
Media Controller
492
Media I/O
Media
496
Subsystem Switch 1
498A
Subsystem Switch N
498B
USB
472
DVD
476
Other
480

Fig. 4


500
104
Vehicle
508A
Area 1
Zone B
Zone A
512B
512A
508B
Area 2
Zone E
Zone D
Zone C
512E
512D
512C
508N
Area N
Zone N
512N
516
520

Fig. 5A


500
104
456
Access Point
Vehicle Communications
508A
508B
508N
512A
512B
512C
512D
512E
512N
Area 1
Area 2
Area N
Zone A
Zone B
Zone C
Zone D
Zone E
Zone N
Internal Vehicle Communications between Vehicle and one or more devices, or between devices
One or more of: Bluetooth®, NFC, WiFi, Mobile Hotspot, Point-to-Point, Point-to-Multiple Other Points, etc.

Fig. 5B


500
104
Vehicle Communications
248A
248N
248
Internal Vehicle Communications Access Point
456
484
Optional Firewall
Communication Network (s) / Bus(es)
224
260
Transceiver (e.g., FemtoCell, WiMax, 4G, LTE, Wireless Communications Module)
Internal Vehicle Communications between Vehicle and one or more devices, or between devices
One or more of: Bluetooth®, NFC, WiFi, Mobile Hotspot, Ethernet, 802.11(x), Point-to-Point, Point-to-Multiple Other Points, etc.

Fig. 5C


104
204
676
660
607
224
657
648
678
224
653
224
648
678
690
692
212
248
668
672
616
640
644
676
607
620
660
674
612
636
670
609
664
600

Fig. 6A


692B
216
648
679
108
624B
692A
624A
622B
642
622A
204
694
248
677
224

Fig. 6B


340
104
716
768
772
776
780
Safety
Force Sensor(s)
Mechanical Motion Sensor(s)
Orientation Sensor(s)
Restraint Sensor(s)
Vehicle - Interior Sensors
User Interface
756
760
764
Biometric Sensor(s)
Camera Sensor(s)
Audio Sensor(s)
Infrared Sensor(s)
Motion Sensor(s)
Weight Sensor(s)
Wireless Network Sensor(s)
712
740
744
748
752
720
Associated Device(s) Sensors
356
Environmental
Oxygen/Air Sensor(s)
Temperature Sensor(s)
Humidity Sensor(s)
Light/Photo Sensor(s)
708
724
728
732
736

Fig. 7A


340
716E
104
768
772
776
782
Safety
Force Sensor(s)
Mechanical Motion Sensor(s)
Orientation Sensor(s)
Vehicle Body Sensor(s)
Vehicle - Exterior Sensors
750
754
758
Vehicle Sensor(s)
Biological Sensor(s)
Wireless Signal Sensor(s)
Environmental
740
744
760
764
Infrared Sensor(s)
Motion Sensor(s)
Camera Sensor(s)
Audio Sensor(s)
724
728
732
736
Oxygen/Air Sensor(s)
Temperature Sensor(s)
Humidity Sensor(s)
Light/Photo Sensor(s)
708E
356

Fig. 7B


800
878
882
886
880
860
Network Transceiver
864
Video I/O Interface
870
Infotainment System
874
Audio I/O Interface
Video Controller
Audio Controller
Profile Identification Module
Data Storage
Profile Database
840
844
848
852
856
824
828
832
836
Network Transceiver
Signal Processing
Memory
Language Database
Media Controller
348
Media Processor
Match Engine
Audio Processor
Speech Synthesis
804
808
812
816
820
356

Fig. 8A


800
Profile Data
252
817
User/Device Interaction Subsystem
User Identification Module
822
Vehicle Control Module
826
Environmental Control Module
830
Gesture Control Module
834
Video I/O Interface
864
Audio I/O Interface
874
Sensor Module
814
Device Interaction Module
818
888
806
User
216
802
810
356

Fig. 8B


Navigation Subsystems
Vehicle-to-Vehicle Transceiver
8120
Network Traffic Control Transceiver
8116
Traffic Controller
8112
8124
Traffic Information Database
8108
Automobile Controller
8104
Vehicle Systems Transceiver
Vehicle Control Subsystem
328
Maps Database
8100
Location Module
896
Sensor(s)
242
GPS Antenna/ Receiver
892
336

Fig. 8C


912
916
920
924
Other Device 1
Other Device 2
Other Device 3
Other Device N
Network / Communications Bus(es)
Communication Network
224/404
224
904
908
Other Device / Co-Host
Host Device (Routing Profile / Permission Module and Rules)

Fig. 9


Memory
Communication Subsystem Interface 1008
Operating System 1004
Firewall 1044
Desktop Manger 1012
Windows Manager 1032
Application Manager 1036
Panel Launcher 1040
File System 1016
Device Discovery Daemon 1020
Desktop Plugin 1024
Kernel 1028
IP 1048
Comm. 1052
Driver(s) 1056
356
308
304
Processor
Storage
208

Fig. 10

Tap



FIG. 11A

Long Press



FIG. 11B

Drag



FIG. 11C

Flick



FIG. 11D

Pinch



FIG. 11E

Spread



FIG. 11F



FIG. 11G



FIG. 11H



FIG. 11I



FIG. 11J



FIG. 11K


1200
1244
1242
1238
1236
1232
1228
1224
1220
1216
1212
1208
1204
1240A
1240B
1248
User
ID
Area
Zone
Settings
Health Data
Gestures
Safety Parameters
Profile Information
Linked Data
User 1
Features 1
1
1
1, 2, 3, 4
X, Y
1, 2, 3
X,Y
X, Y
A, B, C
Features 1
1
2
1, 2
X, Y
3, 4, 5
X,Y
X, Y
A, B, C, D
Features 1
2
3
1, 2
X, Y
3, 4, 5
X,Y
X, Y
A, B, C
User 2
Features 2
2
3
1, 2, 3, 4, 5
Z
1, 2, 3
X,Y
X, Y, Z
A, B, C
Features 2
2
4
Z
8,9,7
X,Y
X, Y, Z
A, B
Features 2
3
7
5, 7, 9
Z
8,9,7
X,Y
X, Y, Z
A, B

Fig. 12A


1200
1244
1242
1238
1262
1260
1258
1224
1220
1216
1256
1254
1252
1250
1250A
1250B
1248
Device
User ID
Device ID
Area
Zone
Settings
Capabilities
Priority
Registration Data
Profile Information
Linked Data
Device 1
User 1
XYZ123
1
1
1, 2, 3
X, Y
A1
X11
X, Y
A, B, C
User 2
XYZ123
1
2
1, 2, 3, 4
X, Y, Z
A2
X12
X, Y
A, C, D
User 3
XYZ123
2
3
1, 2
X, Y, Z
B2
X13
X, Y
A, B, C
Device 2
User 1
ABC456
2
3
1, 2, 3, 4, 5
Z
A1
X21
X, Y, Z
A, B
User 4
ABC456
2
4
Z
X, Y, Z
A, B
User 6
ABC456
3
7
5, 7, 9
Z
C3
X22
X, Y, Z
A, B, C

Fig. 12B



Vehicle System	Component ID	Priority Type	Area	Zone	Settings	Health Status	Communication Type(s)	Profile Information	Linked Data
System 1	Component 1	C	1	1	1, 2	X, Y	W1, W2, W3	Y	A, B
	Component 2	NC	1	2	1	X, Y	W2, W3	X, Y	A, B, D
	Component 5	C	2	3	1, 2, 3	X	W1, W2		A, C
System 2	Component 3	C	2	3	1, 2, 3, 4	X, Y	W1	X, Y, Z	A, B
System 3	Component 7	NC	2	8	1, 3	X, Y, Z	W1, W2, W3, W4	X, Y, Z	A, B, C
	Component 8	NC	3	9	5, 8		W1, W2, W3	X	A, B

Fig. 12C


1200
1244
1242
1238
1286
1278
1224
1220
1216
1284
1282
1280
1280A
1280B
1248
Vehicle
ID
Area
Zone
Settings
Health Status
Warnings
Profile Information
Linked Data
Vehicle 1
S1-1
1
1
1, 2, 3
X
T1
Y, Z
A, B, C
S1-2
1
2
1, 2
X, Y, Z
X, Y
A, B, D
SS-1
2
3
1, 2, 3, 4
T2
X
A, C, E
Vehicle 2
S2-1
2
3
1, 3, 4
X, Y
T1, T2, T3
X, Y, Z
A, B
S2-2
2
6
1, 3, 5
X, Z
X, Y, Z
A, B, C
S2-3
3
4
5, 8, 9
X
X, Y
A, B, D

Fig. 12D


1300
1304
START
1308
Determine person in zone/area
1312
Determine if person can be identified?
YES
NO
1316
Identify person
1320
Characterize person
1324
Determine settings are to be stored
1328
Store settings for person
1332
Store settings in cloud storage
1336
END

Fig. 13


1400
1404
START
1408
Determine person in zone/area
1412
Identify person
1416
Determine settings associated with person
1420
Retrieve settings
1424
Configure/react to settings
1428
END

Fig. 14


1500
1504
START
1508
Determine person in zone/area
1512
Determine characteristics
1516
Determine if person can be identified?
YES
NO
1520
Identify person
1524
Characterize person
1528
Determine if settings are to be stored?
NO
1532
Retrieve settings
YES
1536
Store settings in cloud storage
1540
END

Fig. 15


1600
1604
START
1608
Determine person in zone/area
1612
Determine characteristics
1616
Determine if person can be identified?
YES
NO
1620
Identify person
1624
Characterize person
1628
Determine if gesture(s) are to be stored?
NO
1632
Retrieve gesture(s)
YES
1636
Store gesture(s) in cloud storage
1640
END

Fig. 16


1700
1704
START
1708
Determine person in zone/area
1712
Identify person
1716
Receive gesture from person
1720
Identify gesture
1724
Configure vehicle or react to gesture
1728
END

Fig. 17


1804
START
1800
1808
Determine person in zone/area
1812
Determine characteristics of person
1816
Determine if person can be identified?
YES
NO
1824
Characterize person
1820
Identify person
1828
Determine health/safety data is to be stored
1832
Store health/safety data for person
1836
Wait a period of time
1840
Store gesture(s) in cloud storage
1844
END

Fig. 18


1900
1904
START
1908
Receive health data from person
1912
Compare health data to stored data
1916
Determine if health data is within acceptable parameters?
YES
NO
1924
React to health data
1928
END

Fig. 19


DETECT COMPUTATIONAL DEVICE CONNECTABLE WITH VEHICLE NETWORK
2000
ACCESS CONFIGURATION AND OTHER INFORMATION OF CONNECTED COMPUTATIONAL DEVICE
2004
RECOGNIZE AND/OR AUTHENTICATE COMPUTATIONAL DEVICE?
2008
Yes
No
COMPUTATIONAL DEVICE IN VEHICLE?
2012
Yes
No
DETERMINE SPATIAL LOCATION/SEAT POSITION OF COMPUTATIONAL DEVICE
2016
ENABLE ACCESS TO DEFINED SET OF FUNCTIONS BASED ON LOCATION OF DEVICE WITHIN VEHICLE OR AUTHENTICATION CREDENTIALS
2020
DENY ACCESS OF COMPUTATIONAL DEVICE
2024

Fig. 20


2100
MEDIA CONTENT
348
2108
NETWORK CONTROL SERVER
2104
2112
MEDIA SERVER
2116
VNC SOFTWARE
2120
USER COMPUTATIONAL DEVICE

FIG. 21


RECEIVE BY VNC SOFTWARE COMMAND FOR CONTENT FROM USER OF PREVIOUSLY CONNECTED COMPUTATIONAL DEVICE
2200
DETERMINE BY MEDIA SERVER IDENTITY OF DEVICE AND/OR USER OF DEVICE AND/OR SPATIAL LOCATION OF DEVICE
2204
APPLY BY MEDIA SERVER APPROPRIATE FILTERS AND RESTRICTIONS (E.G., BLACKLIST AND/OR WHITELIST OF WEBSITES AND USER ACCOUNT RESTRICTIONS)
2208
RETRIEVE PERMISSIBLE CONTENT VIA NETWORK CONTROL SERVER
2212
APPLY BY MEDIA SERVER APPROPRIATE FILTERS AND RESTRICTIONS (E.G., FILTER OUT INAPPROPRIATE CONTENT)
2216
CONFIGURE BY MEDIA SERVER FILTERED MEDIA FOR CAPABILITIES OF USER DEVICE AND IN ACCORDANCE WITH USER PREFERENCES
2220
DELIVER CONFIGURED MEDIA TO USER DEVICE
2224

FIG. 22


2300
2304
2308
2312
FIRST VIRTUAL MACHINE HAVING FIRST OPERATION SYSTEM
SECOND VIRTUAL MACHINE HAVING SECOND OPERATING SYSTEM
2316
HYPERVISOR MODULE
2320
MICROPROCESSOR

FIG. 23


2400
1004a
1004b
2412
2420
2420
APPLICATION LAYER
APPLICATION LAYER
2416
2416
FRAMEWORK LAYER
FRAMEWORK LAYER
2408
2408
LIBRARIES LAYER
LIBRARIES LAYER
1028
KERNEL
2320
MICROPROCESSOR

FIG. 24


2500
DETECT STIMULUS
2504
COLLECT METRICS REGARDING OPERATIONS OF COMPUTER
2508
NORMAL OR ABNORMAL?
Yes
No
2512
SHUT DOWN SELECTED OPERATING SYSTEM
2516
RECORD METRICS AND FINDINGS

FIG. 25


2600
DETECT STIMULUS
2604
SELECTED USER INTERFACE ASSOCIATED WITH DRIVER?
No
Yes
2608
RECONFIGURE USER INTERFACE
DO NOT RECONFIGURE USER INTERFACE
2612
SELECT NEXT USER INTERFACE
2616

FIG. 26


2700
DETECT STIMULUS
2704
USER AUTHENTICATED SUCCESSFULLY?
Yes
No
2708
RETRIEVE USER ACCOUNT
2712
DETERMINE SEAT POSITION OF USER
2716
ENABLE ELIGIBLE RIGHTS AND PRIVILEGES AND SETTINGS AND DISABLE INELIGIBLE RIGHTS AND PRIVILEGES AND SETTINGS BASED ON SEAT POSITION
2720
CREATE ACCOUNT FOR UNAUTHENTICATED USER

FIG. 27


Home Screen
2820
2832
2812
2828
Continue as Guest
Settings application progress modal
Manual sign-in
Retry
4
2816
Recognition progress indicator modal
Recognition successful
Success
Sign in using ID
Face Detection screen
Face recognition failure dialog
Continue as Guest
Recognition not successful
2804
Detection successful
100
Cancel
To manual sign-in
Retry
2803
Face Detection screen
2
Detection not successful
3
2800
Trigger
1

FIG. 28


C
2912
A
Please put your face in the circle
2900
2904
B
2908a
2908b

FIG. 29


3000
3028
3030
3032
3020
3034
3036
3038
3040
3016
3018
3004
3022
3024
3026
3046
3042
3048
3050
3052
3054
3044
3008
No route selected
3056
3058
3068
3060
3062
3064
3012
3066
3070

FIG. 30


3100
DETECT STIMULUS
3104
SELECTED OCCUPANT HAVE IMPAIRMENT?
Yes
No
3108
DETERMINE OCCUPANT SEATING AND/OR INTERFACE LOCATION
3112
CONFIGURE VEHICLE COMMUNICATION INTERFACE BASED ON OCCUPANT IMPAIRMENT
3116
SELECT NEXT OCCUPANT

FIG. 31


3200
DETECT STIMULUS
3204
RETRIEVE FOR IDENTIFIED OCCUPANT SELECTED USER ACCOUNT AND/OR SYSTEM DATA
3208
DOES SELECTED OCCUPANT HAVE ABILITY THAT DEVIATES SUFFICIENTLY FROM NORMAL RANGE?
YES
No
3212
RETRIEVE AND APPLY RULE SETS FOR TYPE OF DEVIATION
3216
CONFIGURE VEHICLE COMMUNICATION INTERFACE AND/OR AUTOMATED VEHICLE RESPONSE SYSTEM

FIG. 32


3304a
3304b
3304c
3304h
3304i
3304g
3304j
3304d
3304e
3304f
3304o
3304n
3304zz
3304k
3304l
3304m
3304p
3304q
3304r
3304s
3304t
3304yy
3304v
3304w
3304x
3304z
3304y
3304aa
3304bb
3304cc
3304jj
3304dd
3304ee
3304ff
3304kk
3304ll
3304mm
3304gg
3304hh
3304nn
3304ii
3304oo
3304pp
3304qq
3304rr
3304ss
3304tt
3304uu
3304vv
3304ww
3304xx
3304aaa
3304bbb
3304eee
3304ccc
3304ddd
3300

FIG. 33


3000
3028
3030
3032
3020
3034
3036
3038
3040
3016
3018
3084
3004
3080
3022
3024
3026
3088
3046
3042
3048
3050
3052
3044
3054
3008
No route selected
3092
3056
3096
3058
3068
3064
3060
3062
3012
3098
3066
3070

FIG. 34


3500
DETECT STIMULUS
3504
MAP CURRENT DISPLAY TO SELECTED CONTROL SURFACE
3508
DETECT MOVEMENT OF USER'S DIGIT ON MAPPED CONTROL SURFACE?
YES
No
3512
DETECT POSITION OF USER'S DIGIT
3516
MAP DETECTED POSITION TO CURRENT DISPLAY
3520
PERFORM ACTION BASED ON DETECTED POSITION

FIG. 35


DETECT STIMULUS
3600
3604
SELECT CURRENT VEHICLE OCCUPANT
3608
DETERMINE SEATING POSITION OF OCCUPANT
3612
DETERMINE TYPES OF INFORMATION TO COLLECT FOR PERSONA OF SELECTED OCCUPANT
3616
COLLECT SELECTED TYPES OF INFORMATION
3620
UPDATE PERSONA OF SELECTED OCCUPANT
3624
NEXT OCCUPANT?
NO
YES

FIG. 36


DETECT STIMULUS
3700
SELECT CURRENT VEHICLE OCCUPANT
3704
DETERMINE SEATING POSITION OF OCCUPANT
3708
ACCESS PERSONA OF SELECTED OCCUPANT
3712
DETERMINE VEHICLE RELATED INFORMATION
3716
DETERMINE OTHER RELEVANT TYPES OF INFORMATION
3720
PERFORM ACTION?
3724
NO
YES
A
B

FIG. 37A


A
B
3728
NEXT OCCUPANT?
NO
YES
STEP 3700
STEP 3704
3732
PROMPT OCCUPANT
3736
PERFORM ACTION IF REQUESTED
NO
YES
3740
UPDATE PERSONA TO REFLECT PERFORMANCE OF ACTION
3744
NEXT OCCUPANT?

FIG. 37B


DETECT STIMULUS
3800
IDENTIFY AND INVENTORY ENABLED ON BOARD COMPUTATIONAL RESOURCES AND CAPABILITIES THEREOF
3804
IDENTIFY AND INVENTORY ENABLED WIRELESS CONNECTED COMPUTATIONAL RESOURCES AND CAPABILITIES THEREOF
3808
ASSIGN NETWORK ADDRESSES TO EACH ENABLED RESOURCE
3812
MAINTAIN AND STORE NETWORK TOPOLOGY
3816

FIG. 38


DETECT STIMULUS
3900
DETERMINE REQUIREMENTS FOR EXECUTION OF SELECTED COMPONENT OR MODULE
3904
IS BLADE PROCESSOR AVAILABLE TO EXECUTE SELECTED COMPONENT AND/ OR MODULE?
3908
YES
NO
ASSIGN SELECTED COMPONENT AND/OR MODULE TO SELECTED BLADE PROCESSOR
3912
UPDATE NETWORK TOPOLOGY
3916
DENY SELECTED COMPONENT AND/OR MODULE PERMISSION TO EXECUTE
3920

FIG. 39

VEHICLE-BASED MULTIMODE DISCOVERY

CROSS REFERENCE TO RELATED APPLICATIONS

The present application claims the benefits of and priority, under 35 U.S.C. §119(e), to U.S. Provisional Application Ser. Nos. 61/811,981, filed on Apr. 15, 2013, entitled "Functional Specification for a Next Generation Automobile"; 61/865,954, filed on Aug. 14, 2013, entitled "Gesture Control of Vehicle Features"; 61/870,698, filed on Aug. 27, 2013, entitled "Gesture Control and User Profiles Associated with Vehicle Features"; 61/891,217, filed on Oct. 15, 2013, entitled "Gesture Control and User Profiles Associated with Vehicle Features"; 61/904,205, filed on Nov. 14, 2013, entitled "Gesture Control and User Profiles Associated with Vehicle Features"; 61/924,572, filed on Jan. 7, 2014, entitled "Gesture Control and User Profiles Associated with Vehicle Features"; and 61/926,749, filed on Jan. 13, 2014, entitled "Method and System for Providing Infotainment in a Vehicle." The entire disclosures of the applications listed above are hereby incorporated by reference, in their entirety, for all that they teach and for all purposes.

This application is also related to U.S. patent application Ser. No. 13/420,236, filed on Mar. 14, 2012, entitled, "Configurable Vehicle Console"; Ser. No. 13/420,240, filed on Mar. 14, 2012, entitled "Removable, Configurable Vehicle Console"; Ser. No. 13/462,593, filed on May 2, 2012, entitled "Configurable Dash Display"; Ser. No. 13/462,596, filed on May 2, 2012, entitled "Configurable Heads-Up Dash Display"; Ser. No. 13/679,459, filed on Nov. 16, 2012, entitled "Vehicle Comprising Multi-Operating System"; Ser. No. 13/679,234, filed on Nov. 16, 2012, entitled "Gesture Recognition for On-Board Display"; Ser. No. 13/679,412, filed on Nov. 16, 2012, entitled "Vehicle Application Store for Console"; Ser. No. 13/679,857, filed on Nov. 16, 2012, entitled "Sharing Applications/Media Between Car and Phone (Hydroid)"; Ser. No. 13/679,878, filed on Nov. 16, 2012, entitled "In-Cloud Connection for Car Multimedia"; Ser. No. 13/679,875, filed on Nov. 16, 2012, entitled "Music Streaming"; Ser. No. 13/679,676, filed on Nov. 16, 2012, entitled "Control of Device Features Based on Vehicle State"; Ser. No. 13/678,673, filed on Nov. 16, 2012, entitled "Insurance Tracking"; Ser. No. 13/678,691, filed on Nov. 16, 2012, entitled "Law Breaking/Behavior Sensor"; Ser. No. 13/678,699, filed on Nov. 16, 2012, entitled "Etiquette Suggestion"; Ser. No. 13/678,710, filed on Nov. 16, 2012, entitled "Parking Space Finder Based on Parking Meter Data"; Ser. No. 13/678,722, filed on Nov. 16, 2012, entitled "Parking Meter Expired Alert"; Ser. No. 13/678,726, filed on Nov. 16, 2012, entitled "Object Sensing (Pedestrian Avoidance/Accident Avoidance)"; Ser. No. 13/678,735, filed on Nov. 16, 2012, entitled "Proximity Warning Relative to Other Cars"; Ser. No. 13/678,745, filed on Nov. 16, 2012, entitled "Street Side Sensors"; Ser. No. 13/678,753, filed on Nov. 16, 2012, entitled "Car Location"; Ser. No. 13/679,441, filed on Nov. 16, 2012, entitled "Universal Bus in the Car"; Ser. No. 13/679,864, filed on Nov. 16, 2012, entitled "Mobile Hot Spot/Router/Application Share Site or Network"; Ser. No. 13/679,815, filed on Nov. 16, 2012, entitled "Universal Console Chassis for the Car"; Ser. No. 13/679,476, filed on Nov. 16, 2012, entitled "Vehicle Middleware"; Ser. No. 13/679,306, filed on Nov. 16, 2012, entitled "Method and System for Vehicle Data Collection Regarding Traffic"; Ser. No. 13/679,369, filed on Nov. 16, 2012, entitled "Method and System for Vehicle Data Collection"; Ser. No. 13/679,680, filed on Nov. 16, 2012, entitled "Communications Based on Vehicle Diagnostics and Indications"; Ser. No. 13/679,443, filed on Nov. 16, 2012, entitled "Method and System for Maintaining and Reporting Vehicle Occupant Information"; Ser. No. 13/678,762, filed on Nov. 16, 2012, entitled "Behavioral Tracking and Vehicle Applications"; Ser. No. 13/679,292, filed Nov. 16, 2012, entitled "Branding of Electrically Propelled Vehicles Via the Generation of Specific Operating Output"; Ser. No. 13/679,400, filed Nov. 16, 2012, entitled "Vehicle Climate Control"; Ser. No. 13/840,240, filed on Mar. 15, 2013, entitled "Improvements to Controller Area Network Bus"; Ser. No. 13/678,773, filed on Nov. 16, 2012, entitled "Location Information Exchange Between Vehicle and Device"; Ser. No. 13/679,887, filed on Nov. 16, 2012, entitled "In Car Communication Between Devices"; Ser. No. 13/679,842, filed on Nov. 16, 2012, entitled "Configurable Hardware Unit for Car Systems"; Ser. No. 13/679,204, filed on Nov. 16, 2012, entitled "Feature Recognition for Configuring a Vehicle Console and Associated Devices"; Ser. No. 13/679,350, filed on Nov. 16, 2012, entitled "Configurable Vehicle Console"; Ser. No. 13/679,358, filed on Nov. 16, 2012, entitled "Configurable Dash Display"; Ser. No. 13/679,363, filed on Nov. 16, 2012, entitled "Configurable Heads-Up Dash Display"; and Ser. No. 13/679,368, filed on Nov. 16, 2012, entitled "Removable, Configurable Vehicle Console". The entire disclosures of the applications listed above are hereby incorporated by reference, in their entirety, for all that they teach and for all purposes.

BACKGROUND

Whether using private, commercial, or public transport, the movement of people and/or cargo has become a major industry. In today's interconnected world, daily travel is essential to engaging in commerce. Commuting to and from work can account for a significant portion of a traveler's day. As a result, vehicle manufacturers have begun to focus on making this commute, and other journeys, more enjoyable.

Currently, vehicle manufacturers attempt to entice travelers to use a specific conveyance based on any number of features. Most of these features focus on vehicle safety or efficiency. From the addition of safety-restraints, air-bags, and warning systems to more efficient engines, motors, and designs, the vehicle industry has worked to appease the supposed needs of the traveler. Recently, however, vehicle manufactures have shifted their focus to user and passenger comfort as a primary concern. Making an individual more comfortable while traveling instills confidence and pleasure in using a given vehicle, increasing an individual's preference for a given manufacturer and/or vehicle type.

One way to instill comfort in a vehicle is to create an environment within the vehicle similar to that of an individual's home. Integrating features in a vehicle that are associated with comfort found in an individual's home can ease a traveler's transition from home to vehicle. Several manufacturers have added comfort features in vehicles such as the following: leather seats, adaptive and/or personal climate control systems, music and media players, ergonomic controls, and, in some cases, Internet connectivity. However, because these manufacturers have added features to a conveyance, they have built comfort around a vehicle and failed to build a vehicle around comfort.

SUMMARY

There is a need for a vehicle ecosystem, which can integrate both physical and mental comforts, while seamlessly communicating with current electronic devices to result in a

totally intuitive and immersive user experience. These and other needs are addressed by the various aspects, embodiments, and/or configurations of the present disclosure. Also, while the disclosure is presented in terms of exemplary and optional embodiments, it should be appreciated that individual aspects of the disclosure can be separately claimed.

A method can be provided by the present disclosure that includes the steps of:

providing, in a vehicle, first and second operating systems executing on a common microprocessor, wherein the first operating system comprises one or more applications performing a critical vehicle task, function, and/or operation and the second operating system comprises one or more applications performing an infotainment task, function, and/or operation;

collecting, by a computer control module, one or more metrics regarding an operation of the first and/or second operating system and/or computer and/or a network in communication with the computer;

determining, by the computer control module, whether the collected one or metrics are normal and/or abnormal; and

when the collected one or metrics is not normal or abnormal, shutting down the second operating system but not the first operating system.

In a vehicle, first and second operating systems can execute on a common microprocessor, the first operating system can comprise one or more applications performing a critical vehicle task, function, and/or operation and the second operating system can comprise one or more applications performing an infotainment task, function, and/or operation, and a tangible and non-transient computer readable medium in the vehicle can include microprocessor executable and readable instructions that, when executed by the microprocessor, can perform operations including:

collecting, by a computer control module, one or more metrics regarding an operation of the first and/or second operating system and/or a network in communication with the computer;

determining, by the computer control module, whether the collected one or metrics of one or more of the first and/or second operating system and/or a network in communication with the computer are normal and/or abnormal; and

applying one or more of the following rules:

when the collected one or metrics associated with the first operating system is not normal or abnormal, shutting down the first and second operating systems;

when the collected one or metrics associated with the second operating system is not normal or abnormal, shutting down the second, but not the first, operating system; and

when the collected one or metrics associated with the network is not normal or abnormal, shutting down the second, but not the first, operating system.

A vehicle can include:

a first computer having a first operating system executing one or more applications performing a critical vehicle task, function, and/or operation; and

a second computer having a different second operating system executing one or more applications performing at least one of an infotainment task, function, and/or operation and less critical task, function, and/or operation, wherein at least one of the following can be true:

(a) a computer control module collects one or more metrics regarding an operation of the first and/or second computers and/or a network in communication with the first and/or second computer, determines whether the collected one or metrics regarding an operation of the first and/or second computers and/or network are normal and/or abnormal, and apply one or more of the following rules:

when the collected one or metrics associated with the first operating system is not normal or abnormal, shutting down the first and second operating systems;

when the collected one or metrics associated with the second operating system is not normal or abnormal, shutting down the second, but not the first, operating system; and

when the collected one or metrics associated with the network is not normal or abnormal, shutting down the second, but not the first, operating system; and

(b) the first and second computers are configured to be incapable of communicating with each other.

Each member of the set of critical vehicle tasks, functions, and/or operations can be different from each member of the set of infotainment tasks, functions, and/or operations, whereby the union of the two sets is null.

The critical task, function or operation can be one or more of monitoring, controlling, and/or operating the ECU, TCU, door settings, window settings, and/or blind spot monitor, monitoring, controlling, and/or operating the safety equipment, monitoring and/or controlling certain critical sensors such as the power source controller and energy output sensor, engine temperature, oil pressure sensing, hydraulic pressure sensors, sensors for headlight and other lights, vehicle control system sensors, and/or steering/torque sensor, controlling the operation of the engine, head light control unit, power steering, display panel, switch state control unit, power control unit, and/or brake control unit, and/or issuing alerts to a user and/or remote monitoring entity of potential problems with a vehicle operation.

The infotainment task, function or operation can be one or more of receiving, processing, and/or providing media and/or multimedia content.

The first operating system can be simulated by a first virtual machine and the second operating system by a second virtual machine and the computer control module can be in or configured as a hypervisor module.

The first and second operating systems can concurrently and independently run on a common kernel.

A first requirement applied to the first operating system to determine abnormal operation can be different from a second requirement applied to the second operating system to determine abnormal operation.

The present disclosure can include a method, vehicle, and/or tangible and non-transient computer readable medium comprising the steps, operations, and/or functions of:

(a) determining, by a microprocessor executable device discovery daemon, that a computational device is connected to or attempting to connect to a network and/or communication subsystem of a vehicle;

(b) in response, determining, by the device discovery daemon, whether the computational device is located within a predetermined area and/or zone of the vehicle; and

(c) applying, by the device discovery daemon, at least the following rules:

(C1) when the computational device is located within the predetermined area and/or zone of the vehicle, permitting the computational device to access or attempt to access the vehicle network and/or communication subsystem; and

(C2) when the computational device is not located within the predetermined area and/or zone of the vehicle, not permitting the computational device to access or attempt to access the vehicle network and/or communication subsystem.

A type of the computational device can determine a specific predetermined area and/or zone of the vehicle, from among a plurality of predetermined areas and/or zones, to be used in applying the rules.

The computational device can be one or more of a tablet computer, laptop, smart phone, and personal digital assistant.

The specific predetermined area and/or zone of the vehicle can be at least part of the passenger compartment.

The device discovery daemon can perform sub-steps of step (a) including:

receiving, by the device discovery daemon, information from an on board vehicle sensor that a new occupant has entered the vehicle;

in response to the receipt of the information, emitting, by the device discovery daemon, a ping to discover the computational device; and

when a responsive signal is received from the computational device, determining, by the device discovery daemon, that the computational device is attempting to connect to a network and/or communication subsystem of a vehicle.

The determining step/operation/function (b) can base the determination on whether the computational device is located within the predetermined area and/or zone of the vehicle on one or more of signal strength of a signal from the computational device as received by an access point of the vehicle, a received satellite-based position of the computational device, triangulation based on relative received signal strengths of a signal from the computational device as received by multiple access points of the vehicle, image processing of images of the predetermined area and/or zone, occupant presence and/or location information received by an on board vehicle sensor, whether the computational device is attempting to connect to the network and/or communication subsystem wirelessly or by hard wire connection, whether the computational device has moved relative to a selected access point during a defined time interval, whether the received signal strength of signaling from the computational device at a selected access point varies temporally, a type or service of the computational device, and input received from a user of the computational device.

When the computational device is determined to be located within the predetermined area and/or zone of the vehicle and is permitted to access or attempt to access the vehicle network and/or communication subsystem and wherein the device discovery daemon can determine a set of tasks, functions, and/or operations that can be performed and a set of tasks, functions, and/or operations that cannot be performed based on the determined location of the computational device.

The device discovery daemon can determine a level of confidence that the computational device is located within the predetermined area and/or zone and wherein the device discovery daemon determines that the computational device is located within the predetermined area and/or zone when the level of confidence has at least a threshold value.

A method, vehicle, and/or computer executable instructions can be provided that perform at least the following steps, operations, and functions:

(a) determining, by a microprocessor executable media controller subsystem, that a user is driving a vehicle; and

(b) in response, the microprocessor executable media controller subsystem performing one or more of the following steps:

(i) removing a video channel but not an audio channel from media content to be displayed on a screen associated with the user;

(ii) applying screen magnification to content displayed on the screen associated with the user;

(iii) reconfiguring the screen and/or content to provide a large font and/or icon size for the displayed content compared to the displayed content when the user is not driving the vehicle;

(iv) removing unnecessary animations from the content to be displayed on the screen;

(v) removing background images from, while leaving at least one foreground image in, the content to be displayed on the screen;

(vi) compared to the displayed content when the user is not driving the vehicle, reconfiguring the screen and/or content to provide higher contrast to make the displayed content more visible to the user;

(vii) initiating a screen reader to audibly describe currently displayed content to the user;

(viii) compared to the period for notification dialog boxes to remain open on the screen when the user is not driving the vehicle, enabling a longer period for notification dialog boxes to remain open on the screen;

(ix) changing the color and/or transparency of window borders on the displayed content;

(x) changing the thickness of a focus rectangle around a currently selected object in a dialog box displayed on the screen;

(xi) changing the color, size and/or thickness of an on-screen mouse pointer displayed on the screen;

(xii) changing a keyboard setting of a keyboard displayed on the screen;

(xiii) formatting a web page, in the content to be displayed, differently from the web page format received from a web server;

(xiv) compared to the size of a mouse-selectable screen object when the user is not driving the vehicle, increasing a size of a mouse-selectable screen object to provide a larger target;

(xv) enabling mouse keys to move the mouse cursor on the screen;

(xvi) enabling one or more of sticky keys, toggle keys, and filter keys; and

(xvii) enabling the screen to receive input written by the user's finger as an inputted command or request.

The user can be determined to be driving the vehicle when the user is determined to be in a driver's seat of the vehicle.

The user can be determined to be driving the vehicle when the vehicle is at least one of in gear and in motion.

The method/vehicle/instructions can further perform the following steps, operations, and functions:

(c) determining, by the media controller subsystem, that the user is no longer driving the vehicle; and

(d) in response to step (c), the media controller subsystem performing one or more of the following steps:

(i) no longer removing a video channel from media content to be displayed;

(ii) no longer applying screen magnification to content to be displayed;

(iii) reconfiguring the display to provide a smaller font and/or icon size for the content to be displayed compared to the font and/or icon size used when the user is driving the vehicle;

(iv) no longer removing unnecessary animations from the content to be displayed;

(v) no longer removing background images from the content to be displayed;

(vi) reconfiguring the screen to provide lower contrast compared to the contrast used when the user is driving the vehicle;

(vii) disabling the screen reader;

(viii) compared to the period for notification dialog boxes to remain open on the screen when the user is driving the vehicle, enabling a shorter period for notification dialog boxes to remain open on the screen;

(ix) compared to the color and/or transparency of window borders on the displayed content when the user is driving the vehicle changing the color and/or transparency of window borders on the displayed content;

(x) compared to the thickness of a focus rectangle around a currently selected object in a dialog box displayed on the screen color and/or transparency of window borders on the displayed content when the user is driving the vehicle, changing the thickness of a focus rectangle around a currently selected object in a dialog box displayed on the screen;

(xi) compared to the color, size and/or thickness of an on-screen mouse pointer displayed on the screen when the user is driving the vehicle, changing the color, size and/or thickness of an on-screen mouse pointer displayed on the screen;

(xii) compared to the keyboard setting of a keyboard displayed on the screen when the user is driving the vehicle, changing a keyboard setting of a keyboard displayed on the screen;

(xiii) no longer formatting a web page, in the content to be displayed, differently from the web page format received from a web server;

(xiv) compared to the size of a mouse-selectable screen object when the user is driving the vehicle, decreasing a size of a mouse-selectable screen object to provide a larger target;

(xv) disabling mouse keys to move the mouse cursor on the screen;

(xvi) disabling the one or more of sticky keys, toggle keys, and filter keys; and

(xvii) disabling the screen to receive input written by the user's finger as an inputted command or request.

The user can be determined not to be driving the vehicle when the vehicle is at least one of not in gear, parked, and not in motion.

The user can be determined to be in a driver's seat of the vehicle when the user is located within a predetermined area and/or zone.

The determining step (a) can base the determination on whether the user is located within the predetermined area and/or zone of the vehicle on one or more of signal strength of a signal from a computational device associated with the user as received by an access point of the vehicle, a received satellite-based position of the computational device, triangulation based on relative received signal strengths of a signal from the computational device as received by multiple access points of the vehicle, image processing of images of the predetermined area and/or zone, user presence and/or location information received by an on board vehicle sensor, and input received from a user of the computational device.

A media controller subsystem can include:

a microprocessor executable distributed network control server operable to access selected content on a public network external to a vehicle comprising the media controller subsystem, the distributed network control server having at least one of an assigned Internet Protocol address and global unicast address;

a microprocessor executable media server operable to receive requests for content from a vehicle occupant and provide requested content to a portable computational device associated with the vehicle occupant, the media server having a contactable electronic address on a local area network maintained by the vehicle;

a microprocessor readable memory to store content; and

a microprocessor executable virtual network console operable to provide the computational device with remote access to the media server.

The distributed network control server, media server, and virtual network console can be on a common media processing board mounted on the vehicle.

The portable computational device can be discrete from, remote from, and in wireless communication with the media processing board.

The virtual network console can operate in accordance with the Remote Frame Buffer protocol on top of the TCP/IP suite of protocols, thereby causing the remote computational device to appear to a computer mounted in the vehicle as if the remote computational device is part of the on board vehicle control system comprising the computer.

The vehicle occupant, through the remote computational device, can control one or more of the following media presentation features of a screen and sound system mounted on the vehicle: volume, contrast, resolution, and channel selection.

A method, vehicle, and instructions can perform at least the following steps, operations, and functions:

(a) determining, by a microprocessor executable media server, at least one of an identity of a vehicle occupant requesting media content, an identity of a portable computational device associated with the vehicle occupant, and a spatial location of the vehicle occupant and/or remote computational device;

(b) based on the at least one of the identity of the vehicle occupant requesting media content, the identity of a portable computational device associated with the vehicle occupant, and the spatial location of the vehicle occupant and/or remote computational device, applying, by the microprocessor executable media server, at least one of a filter and restriction to the requested media content to form filtered and/or permitted media content to be provided to the portable computational device; and

(c) providing, by a microprocessor executable media server, the filtered and/or permitted media content to the portable computational device.

The portable computational device can be discrete from, remote from, and in wireless communication with the media processing board.

The filter and/or restriction can be applied to a media request of the vehicle occupant before and/or after the requested media content is accessed.

The filter and/or restriction can be one or more of an age-related content filter and/or restriction, a vehicle occupant seating location filter and/or restriction, and a privacy filter and/or restriction.

A method, vehicle, and tangible and non-transient computer readable medium can be provided to perform steps, operations, and functions, including:

(a) receiving a request from a vehicle occupant to perform a vehicle task, function and/or operation;

(b) determining that the vehicle occupant has been authenticated successfully;

(c) accessing an account for the vehicle occupant, the account defining rights and privileges of the user with respect to controlling a vehicle task, function and/or operation;

(d) determining at least one of an area and/or zone occupied by the vehicle occupant and an operating state of the vehicle; and

(e) based upon the account corresponding to the vehicle occupant and the at least one of an area and/or zone occupied by the vehicle occupant and an operating state of the vehicle, applying the following rules:

(i) when the account permits the vehicle occupant to perform the requested vehicle task, function and/or operation, performing or causing to be performed the vehicle task, function, and/or operation; and

(ii) when the account does not permit the vehicle occupant to perform the requested vehicle task, function and/or operation, not performing or causing to be performed the vehicle task, function, and/or operation.

In step, operation, or function (e), a microprocessor executable vehicle control system can apply the rules based on the account corresponding to the vehicle occupant and the area and/or zone occupied by the vehicle occupant. Then vehicle occupant can perform a first set of vehicle tasks, functions and operations when in a first area and/or zone and a different set of vehicle tasks, functions, and operations when in a different second area and/or zone.

In step, operation, or function (e), the microprocessor executable vehicle control system can apply the rules based on the account corresponding to the vehicle occupant and the operating state of the vehicle. The vehicle occupant can perform a first set of vehicle tasks, functions and operations when the vehicle is in a first operating state and a different set of vehicle tasks, functions, and operations when the vehicle is in a second operating state.

When rule (i) applies, the vehicle occupant can control the requested vehicle task, function and/or operation using one or more of a cell phone, laptop, tablet computer, and personal digital assistant.

A different authentication procedure can be used for the vehicle occupant when requesting a first set of vehicle tasks, operations, and functions than when requesting a second set of vehicle tasks, operations, and functions.

The account can include rights and privileges for the vehicle occupant with respect to a vehicle task, function or operation, security and/or authentication requirements and/or credentials for the vehicle occupant, and personal settings of the vehicle occupant.

The personal settings of the vehicle occupant can include a plurality of a seat setting, climate control setting, lighting setting, configuration of an instrument cluster on a screen, rear view mirror setting, driving mode, media channel setting or preset, media delivery preference, music genre preference, scheduled program, playlist, synchronization with cloud-based data associated with the vehicle occupant, application-specific personalization and selections, and a display setting and configuration.

A method/vehicle/computer readable instructions can perform at least the following steps/operations/functions:

(a) detecting, by a microprocessor executable media controller subsystem, a change in state of a vehicle, a driver of the vehicle having a graphical user interface on board and/or in communication with a computer network controlled by computer on board the vehicle;

(b) in response, reconfiguring, by the media controller subsystem, the graphical user interface by at least one of the following actions to reduce driver distraction and/or make content displayed by the graphical user interface more visible to the driver:

apply screen magnification to at least part of the content displayed on the graphical user interface;

render at least part of the displayed content in a larger font and/or icon size;

initiate a screen reader to audibly provide and/or describe at least part of the displayed content to the driver;

initiate haptic feedback to provide and/or describe at least part of the displayed content to the driver;

disable unnecessary animation effects from at least a part of the displayed content;

remove a background image from while leaving a foreground image in at least part of the displayed content;

enable a longer period for notification dialog boxes to remain open in the displayed content;

enable a longer contact period of a digit of the driver to select a selectable object in the displayed content;

disable automatic arrangement of windows when a mouse cursor is moved to an edge of the displayed content;

enable activate a window in at least part of the displayed content by hovering over the window with a mouse cursor;

enable keyboard web page navigation in the displayed content;

enable a high contrast between text and a background color in at least part of the displayed content;

change a color and transparency of a border of a window in at least part of the displayed content;

change a thickness of a focus rectangle around a currently selected item in a dialog box in the displayed content;

change a color, size, and/or thickness of an on-screen mouse pointer in the displayed content;

change a keyboard setting displayed in the displayed content and/or in communication with the displayed content;

ignore a color, font style, font size, and/or format of a web page of the displayed content in accordance with a predetermined style sheet;

increase a size of a selectable object in at least part of the displayed content;

enable blind typing on the graphical user interface; and

remove one or more selectable objects from the displayed content.

A method/vehicle/computer readable instructions can perform at least the following steps/operations/functions:

(a) mapping, by a microprocessor executable media controller subsystem, a graphical user interface on board and/or in communication with a computer network controlled by computer on board the vehicle with a segmented control surface, whereby each segment corresponds to an item of content displayed on the graphical user interface;

(b) tracking, by a microprocessor executable media controller subsystem, a position of a body part of a user on the control surface relative to the control surface segments;

(c) determining, by a microprocessor executable media controller subsystem, that the body part of the user is located on a first segment; and

(d) in response, at least one of providing displayed content corresponding to the first segment and selecting a selectable object corresponding to the first segment.

The control surface can be electrically, magnetically, and electromagnetically nonresponsive to contact of the user's body part.

The control surface can be optically nonresponsive to contact of the user's body part.

The control surface can be part of an arm rest and/or dashboard and wherein the graphical user interface is virtual and not displayed to the user.

The control surface can be part of an arm rest and/or dashboard and wherein the graphical user interface is displayed to the user on a screen on board the vehicle.

A method/vehicle/computer readable instructions can perform at least the following steps/operations/functions:

(a) determining, by a vehicle control system, that a vehicle occupant has an impairment; and

(b) in response, altering a communication interface of the vehicle to accommodate the impairment.

The impairment can be one or more of a vision impairment, hearing impairment, dexterity impairment, mobility impairment, language impairment, and communication impairment.

The communication interface can be a screen on board the vehicle.

The location of the vehicle occupant and the screen corresponding to the determined occupant location can be determined.

The alteration can be one or more of:

apply screen magnification to at least part of the content displayed on the screen;

render at least part of the displayed content in a larger font and/or icon size;

initiate a screen reader to audibly provide and/or describe at least part of the displayed content to the occupant;

initiate haptic feedback to provide and/or describe at least part of the displayed content to the occupant;

disable unnecessary animation effects from at least a part of the displayed content;

remove a background image from while leaving a foreground image in at least part of the displayed content;

enable a longer period for notification dialog boxes to remain open in the displayed content;

enable a longer contact period of a digit of the occupant to select a selectable object in the displayed content;

disable automatic arrangement of windows when a mouse cursor is moved to an edge of the displayed content;

enable activate a window in at least part of the displayed content by hovering over the window with a mouse cursor;

enable keyboard web page navigation in the displayed content;

enable a high contrast between text and a background color in at least part of the displayed content;

change a color and transparency of a border of a window in at least part of the displayed content;

change a thickness of a focus rectangle around a currently selected item in a dialog box in the displayed content;

change a color, size, and/or thickness of an on-screen mouse pointer in the displayed content;

change a keyboard setting displayed in the displayed content and/or in communication with the displayed content;

ignore a color, font style, font size, and/or format of a web page of the displayed content in accordance with a predetermined style sheet;

increase a size of a selectable object in at least part of the displayed content;

enable blind typing on the graphical user interface;

enable text and/or a visual alternative to an audio channel associated with the displayed content;

increase a volume setting of the audio channel;

change a sound provided by the audio channel;

enable sign language interpretation;

enable a text phone application;

change a setting of a mouse associated with the displayed content; and

remove one or more selectable objects from the displayed content.

A method/vehicle/computer readable instructions can perform at least the following steps/operations/functions:

(a) sensing, by a vehicle control system, a sound from a source external to a vehicle;

(b) identifying, by the vehicle control system, a type and/or source of the sound;

(c) based on the identifying step, notifying a driver of the vehicle of the type and/or source of the sound.

The notification can be one or more of a visual notification, an audible notification, and a haptic notification.

The notification can be an audible notification.

The audible notification can be one or more of a portion of the frequency range of the received sound, a frequency shifted portion of the received sound, and a phase shifted portion of the sound.

A method/vehicle/computer readable instructions can perform at least the following step/operation/function:

altering, by a vehicle control system, an interface of a vehicle based on one or more of a user impairment, user medical condition, user age, user physical condition, user driving characteristic and driving history.

The interface can be one or more of a steering wheel, pedal, a graphical user interface, and a setting and/or configuration of an automated vehicle response system.

The automated vehicle response system can be a collision avoidance system.

A method/vehicle/computer readable instructions can perform at least the following step/operation/function:

maintaining a persona of a vehicle occupant; and

based on the persona of the vehicle occupant and vehicle-related information, perform an action assisting the vehicle occupant.

the vehicle-related information comprises at least one of a current and/or future vehicle location and path of vehicle travel.

The action performed can depend on a seating position of the vehicle occupant.

The persona can include one or more of bioinformatics, medical information, driving history, personal information, private information, travel information, and Internet browsing history and/or browsed content.

The vehicle related information can include one or more of vehicle context, state, external surroundings, location, past, current, and/or intended path of travel, waypoint, and destination.

The action can be one or more of making an appointment, making a reservation, purchasing an item on line, adding a waypoint or destination to path of travel on a navigation system of the vehicle, adding an entry into the occupant's electronic calendar, changing a destination or path of travel on the navigation system, warning the occupant, notifying the occupant, and sending a message to a person at a waypoint or destination of the vehicle regarding an arrival time.

The steps/functions/operations can determine relevant information other than the persona of the vehicle occupant and the vehicle-related information.

The relevant information can include one or more of a persona of a selected person not currently in the vehicle, a message from a friend or family member of the vehicle occupant, a current activity of the friend and/or family member, a location, hours of operation, and/or descriptive information about a point and/or location of interest near the vehicle and/or the vehicle's path of travel, a location, hours of operation, and/or descriptive information about a vehicle service facility near the vehicle and/or the vehicle's path of travel, a location, hours of operation, and/or descriptive information about a hotel and/or motel near the vehicle and/or the vehicle's path of travel, a current location of the friend or family member near the vehicle and/or the vehicle's path of travel, and a road condition along a path of travel of the vehicle.

The vehicle can obtain the persona from one or more of a different vehicle driven by the occupant and a home computer.

The vehicle can synchronize with the different vehicle and/or home computer when the vehicle is parked in proximity thereto and an ignition of the vehicle is turned off

The maintaining of the persona can include collecting information from one or more vehicle sensors and/or from a remote information source.

A type of information collected can depend on a seating position of the occupant.

The type of information collected can depend on one or more of an identity of the occupant, an age of the occupant, and an association of the occupant with the vehicle.

The persona can be defined in a format (e.g., grammar, syntax, and/or semantics) that can be processed by vehicles of different manufacturers.

A vehicle backplane assembly can include at least the following components:

A plurality of blade processors in a vehicle that includes a first set of blade processors installed prior to vehicle sale and not modifiable and/or replaceable by the vehicle owner and a second set of blade processors installable after vehicle sale and is modifiable and/or replaceable by the vehicle owner. Each blade processor includes a microprocessor, a memory, and a network interface and each of the blade processors performing a different set of functions.

The restricted access by the customer to the first set of blade processors can be done through restrictions on software rights and privileges (e.g., read only rights and privileges to machine code with no right or privilege to modify same) and physical access to the first set of blade processors (e.g., through a locked housing containing one or more components of the blade processors).

The assembly can include a third set of blade processors that interfaces with the first and second set of blade processors to provide input to and/or receive output from a corresponding one of the first and second blade processors.

A satellite receiving system can be a member of the third set of blade processors and a navigation system a member of one of the first and second set of blade processors.

Each of the first and second sets of blade processors can include a corresponding Universal Serial Bus ("USB") hub, the USB hub comprising a plurality of ports to permit devices to connect to the USB hub.

The first set of blades can include a master blade processor operable to inventory hardware and/or software in communication with the backplane assembly, assign blade processors to applications attempting to execute, and/or determine a health state of a selected the blade processor.

A vehicle can include a plurality of blade processors, each blade processor performing a function that is at least one of a vehicle task, function, or operation and an infotainment task, function, or operation.

The blade processors can have a backplane.

The backplane can have a first communication zone defining a trusted network within the vehicle to connect with trusted computational devices and/or module provided or certified by the vehicle manufacturer but not untrusted computational devices and/or modules provided by vehicle occupants. Whether or not a computational device and/or module is certified by a manufacturer can be determined using known license check procedures, such as a unique identifier, a unique credential (e.g., password or encrypted or unencrypted key), and the like. When the check is completed satisfactorily (e.g., the unique identifier or a unique credential (e.g., password or encrypted or unencrypted key) provided by the device and/or module matches a stored identifier in the memory of the vehicle control system (or master blade processor)), the computational device and/or module is deemed to be certified by the manufacturer. When the check is not completed satisfactorily, the computational device and/or module is not deemed to be certified by the manufacturer.

The backplane can have a second communication zone defining an untrusted network to connect with the untrusted computational devices.

The backplane can have a third communication zone providing power and data transmission to the plurality of blade processors.

The first and second communication zones can be connected logically on opposing sides of a firewall blade processor.

A master blade processor can enable a connection to a computational device connected to the first communication zone upon verification that the connected computational device is certified by a vehicle manufacturer.

The first and second communication zones can be configured as separate Ethernet switches. The first and second communication zones are typically not in signal communication with one another.

A firewall can have a dedicated slot that bridges the first and second communication zones and uses the third communication zone for power connections.

An output of each of the plurality of blade processors can be an IP message framed into an Ethernet packet.

A sensor and/or controller of the vehicle can communicate by a Car Area Network ("CAN") protocol. An Ethernet bus controller can terminate a CAN bus to the sensor and/or controller and a CAN Ethernet controller subsystem can translate an Ethernet message from a blade processor to a CAN protocol-based message.

The plurality of blade processors can be configured as a crate having the backplane connector and on-backplane Ethernet interfaces enabling the blade processors to communicate with one another using Ethernet messages.

A vehicle can include a plurality of blade processors, each blade processor performing a function that is at least one of a vehicle task, function, or operation and an infotainment task, function, or operation. The plurality of blade processors can include a master blade processor operable to assign a component and/or module requiring a blade processor for execution to a selected blade processor.

The master blade processor can inventory hardware and software capabilities of components and/or modules in communication with the master blade processor to provide an application resource table comprising component and/or module identity, functional description, and/or computational resource requirements and/or capabilities needed for execution of the component and/or module.

A blade processor can be assigned to execute the component and/or module when the blade processor satisfies the corresponding computational resource requirements and/or capabilities.

The master blade processor can assign a network address to each blade processor and communication device in communication with the master blade processor.

The master blade processor can assign a component and/or module to a selected blade processor when the selected blade processor is available or, though unavailable, is executing a component and/or module having a lower priority than the component and/or module to be assigned to the selected blade processor.

The present disclosure can provide a number of advantages depending on the particular aspect, embodiment, and/or configuration. For example, operating multiple operating systems on a common on board computer platform for vehicle control and infotainment tasks, functions and operations can provide a high level of vehicle security and block successfully intrusive attacks. The network security configurations can enable both infotainment and critical vehicle tasks, functions,

and operations to performed automatically and concurrently in a vehicle without increasing driver danger from computer-targeted attacks by an outside source. Using a common computer to run safely both the first and second operating systems can not only reduce vehicle manufacturing costs but also provide a simpler computational architecture. The device discovery daemon, by locating the portable device seeking access to the vehicle network, can not only provide higher levels of security from intrusive attacks via a computational device external to the vehicle but also protect the privacy and resources of the vehicle network. The application of accessibility technologies to the driver's screen can successfully reduce driver distractions while enabling the driver to perform permissible computational tasks. The availability of accessibility technologies in the vehicle can not only comply with prevailing legal requirements but also enhance passenger enjoyment. The use of network control and media servers and virtual network console functionality on a common processing board can provide a simple yet effective way to stream media to devices within the vehicle network. The use of media filters and restrictions based on one or more of the identity of the vehicle occupant requesting media content, the identity of a portable computational device associated with the vehicle occupant, and the spatial location of the vehicle occupant and/or remote computational device can enable compliance with prevailing laws regarding driver distractions while providing the vehicle owner with the ability to control media access by one or more selected vehicle occupants. The use of user accounts to control passenger access to vehicle tasks, functions, and operations can prevent a non-driving passenger, for instance, from controlling a critical vehicle task, function or operation and confusing or frustrating the driver. The inactive control surface can enable a vehicle occupant to perform tasks, functions and operations without viewing his or her screen. This provides yet another convenient method for driver control of vehicle and non-vehicle tasks, functions, and operations without distraction while driving the vehicle. The blade processor architecture can take advantage of the pervasiveness of TCP/IP and the large volume of components and/or modules made for IP-based distributed systems, such as the Ethernet. The architecture can be a modular distributed system that can be upgraded and/or extended over time, without changing the basic processing architecture. Because the various subsystems can communicate with one another by protocol-based messages, there is not requirement that all software be written in any specific language or execute on any specific operating system. This can allow developers to use the most appropriate run time environment for the subsystem being developed. For instance, when a real time operating system ("RTOS") is required because of the timing constraints of the run time environment (i.e., real time control of a function), a subsystem can be developed using RTOS, without constraining the runtime environment of less demanding systems (e.g., a console subsystem).

These and other advantages will be apparent from the disclosure.

The phrases "at least one," "one or more," and "and/or" are open-ended expressions that are both conjunctive and disjunctive in operation. For example, each of the expressions "at least one of A, B and C," "at least one of A, B, or C," "one or more of A, B, and C," "one or more of A, B, or C" and "A, B, and/or C" means A alone, B alone, C alone, A and B together, A and C together, B and C together, or A, B and C together.

The term "a" or "an" entity refers to one or more of that entity. As such, the terms "a" (or "an"), "one or more," and "at least one" can be used interchangeably herein. It is also to be noted that the terms "comprising," "including," and "having" can be used interchangeably.

"Accessible technology" refers to any computer technology that users can adjust and/or employ to accommodate his or her vision, dexterity, hearing, cognitive, language, learning, and/or speech needs. Accessibility technology can be in the form of accessibility features or settings built into software programs and specialty hardware devices or software programs.

"Assistive technology" refers to any technology that users can adjust and/or employ to accommodate his or her vision, dexterity, hearing, cognitive, language, learning, and/or speech needs. Examples of assistive technology include accessible technology, adjuncts, peripherals, plug-ins, and add-ins.

The term "disability" refers to the consequence of an impairment that may be physical, cognitive, intellectual, mental, sensory, emotional, developmental, or some combination of these. By way of illustration, Section 503 defines "disability" as an impairment that substantially limits a major life activity, even if it were not to limit any other major life activity, or an impairment that is episodically active or in remission and would substantially limit a major life activity when active.

The term "automatic" and variations thereof, as used herein, refer to any process or operation done without material human input when the process or operation is performed. However, a process or operation can be automatic, even though performance of the process or operation uses material or immaterial human input, if the input is received before the performance of the process or operation. Human input is deemed to be material if such input influences how the process or operation will be performed. Human input that consents to the performance of the process or operation is not deemed to be "material."

The term "automotive navigation system" can refer to a satellite navigation system designed for use in vehicles. It typically uses a GPS navigation device to acquire position data to locate the user on a road in the unit's map database. Using the road database, the unit can give directions to other locations along roads also in its database. Dead reckoning using distance data from sensors attached to the drivetrain, a gyroscope and an accelerometer can be used for greater reliability, as GPS signal loss and/or multipath can occur due to urban canyons or tunnels.

The term "bus" and variations thereof, as used herein, can refer to a subsystem that transfers information and/or data between various components. A bus generally refers to the collection communication hardware interface, interconnects, bus architecture, standard, and/or protocol defining the communication scheme for a communication system and/or communication network. A bus may also refer to a part of a communication hardware that interfaces the communication hardware with the interconnects that connect to other components of the corresponding communication network. The bus may be for a wired network, such as a physical bus, or wireless network, such as part of an antenna or hardware that couples the communication hardware with the antenna. A bus architecture supports a defined format in which information and/or data is arranged when sent and received through a communication network. A protocol may define the format and rules of communication of a bus architecture.

The terms "communication device," "smartphone," and "mobile device," and variations thereof, as used herein, can be used interchangeably and may include any type of device capable of communicating with one or more of another device

and/or across a communications network, via a communications protocol, and the like. Exemplary communication devices may include but are not limited to smartphones, handheld computers, laptops, netbooks, notebook computers, subnotebooks, tablet computers, scanners, portable gaming devices, phones, pagers, GPS modules, portable music players, and other Internet-enabled and/or network-connected devices.

A "communication modality" can refer to any protocol- or standard defined or specific communication session or interaction, such as Voice-Over-Internet-Protocol ("VoIP"), cellular communications (e.g., IS-95, 1G, 2G, 3G, 3.5G, 4G, 4G/IMT-Advanced standards, 3GPP, WIMAX™, GSM, CDMA, CDMA2000, EDGE, 1xEVDO, iDEN, GPRS, HSPDA, TDMA, UMA, UMTS, ITU-R, and 5G), Bluetooth™, text or instant messaging (e.g., AIM, Blauk, eBuddy, Gadu-Gadu, IBM Lotus Sametime, ICQ, iMessage, IMVU, Lync, MXit, Paltalk, Skype, Tencent QQ, Windows Live Messenger™ or MSN Messenger™, Wireclub, Xfire, and Yahoo! Messenger™), email, Twitter (e.g., tweeting), Digital Service Protocol (DSP), and the like.

The term "communication system" or "communication network" and variations thereof, as used herein, can refer to a collection of communication components capable of one or more of transmission, relay, interconnect, control, or otherwise manipulate information or data from at least one transmitter to at least one receiver. As such, the communication may include a range of systems supporting point-to-point or broadcasting of the information or data. A communication system may refer to the collection individual communication hardware as well as the interconnects associated with and connecting the individual communication hardware. Communication hardware may refer to dedicated communication hardware or may refer a processor coupled with a communication means (i.e., an antenna) and running software capable of using the communication means to send and/or receive a signal within the communication system. Interconnect refers some type of wired or wireless communication link that connects various components, such as communication hardware, within a communication system. A communication network may refer to a specific setup of a communication system with the collection of individual communication hardware and interconnects having some definable network topography. A communication network may include wired and/or wireless network having a pre-set to an ad hoc network structure.

The term "computer-readable medium," as used herein refers to any tangible storage and/or transmission medium that participates in providing instructions to a processor for execution. Such a medium may take many forms, including but not limited to, non-volatile media, volatile media, and transmission media. Non-volatile media includes, for example, non-volatile random access memory (NVRAM), or magnetic or optical disks. Volatile media includes dynamic memory, such as main memory. Common forms of computer-readable media include, for example, a floppy disk, a flexible disk, hard disk, magnetic tape, or any other magnetic medium, magneto-optical medium, a compact disc read only memory (CD-ROM), any other optical medium, punch cards, paper tape, any other physical medium with patterns of holes, a random access memory (RAM), a programmable read only memory (PROM), and erasable programmable read only memory EPROM, a FLASH-EPROM, a solid state medium like a memory card, any other memory chip or cartridge, a carrier wave as described hereinafter, or any other medium from which a computer can read. A digital file attachment to an e-mail or other self-contained information archive or set of archives is considered a distribution medium equivalent to a tangible storage medium. When the computer-readable media is configured as a database, it is to be understood that the database may be any type of database, such as relational, hierarchical, object-oriented, and/or the like. Accordingly, the disclosure is considered to include a tangible storage medium or distribution medium and prior art-recognized equivalents and successor media, in which the software implementations of the present disclosure are stored. It should be noted that any computer readable medium that is not a signal transmission may be considered non-transitory.

The terms dash and dashboard and variations thereof, as used herein, may be used interchangeably and can be any panel and/or area of a vehicle disposed adjacent to an operator, user, and/or passenger. Dashboards may include, but are not limited to, one or more control panel(s), instrument housing(s), head unit(s), indicator(s), gauge(s), meter(s), light(s), audio equipment, computer(s), screen(s), display(s), HUD unit(s), and graphical user interface(s).

The term "module" as used herein refers to any known or later developed hardware, software, firmware, artificial intelligence, fuzzy logic, or combination of hardware and software that is capable of performing the functionality associated with that element.

The term "desktop" refers to a metaphor used to portray systems. A desktop is generally considered a "surface" that may include pictures, called icons, widgets, folders, etc. that can activate and/or show applications, windows, cabinets, files, folders, documents, and other graphical items. The icons are generally selectable to initiate a task through user interface interaction to allow a user to execute applications and/or conduct other operations.

The term "display" refers to a portion of a physical screen used to display the output of a computer to a user.

The term "displayed image" refers to an image produced on the display. A typical displayed image is a window or desktop. The displayed image may occupy all or a portion of the display.

The term "display orientation" refers to the way in which a rectangular display is oriented for viewing. The two most common types of display orientations are portrait and landscape. In landscape mode, the display is oriented such that the width of the display is greater than the height of the display (such as a 4:3 ratio, which is 4 units wide and 3 units tall, or a 16:9 ratio, which is 16 units wide and 9 units tall). Stated differently, the longer dimension of the display is oriented substantially horizontal in landscape mode while the shorter dimension of the display is oriented substantially vertical. In the portrait mode, by contrast, the display is oriented such that the width of the display is less than the height of the display. Stated differently, the shorter dimension of the display is oriented substantially horizontal in the portrait mode while the longer dimension of the display is oriented substantially vertical. A multi-screen display can have one composite display that encompasses all the screens. The composite display can have different display characteristics based on the various orientations of the device.

The term "electronic address" can refer to any contactable address, including a telephone number, instant message handle, e-mail address, Uniform Resource Locator ("URL"), Global Universal Identifier ("GUID"), Universal Resource Identifier ("URI"), Address of Record ("AOR"), electronic alias in a database, etc., combinations thereof

The term "gesture" refers to a user action that expresses an intended idea, action, meaning, result, and/or outcome. The user action can include manipulating a device (e.g., opening or closing a device, changing a device orientation, moving a trackball or wheel, etc.), movement of a body part in relation

to the device, movement of an implement or tool in relation to the device, audio inputs, etc. A gesture may be made on a device (such as on the screen) or with the device to interact with the device.

The term "gesture capture" refers to a sense or otherwise a detection of an instance and/or type of user gesture. The gesture capture can be received by sensors in three-dimensional space. Further, the gesture capture can occur in one or more areas of a screen, for example, on a touch-sensitive display or a gesture capture region. A gesture region can be on the display, where it may be referred to as a touch sensitive display, or off the display, where it may be referred to as a gesture capture area.

The terms "infotainment" and "infotainment system" may be used interchangeably and can refer to the hardware/software products, data, content, information, and/or systems, which can be built into or added to vehicles to enhance driver and/or passenger experience. Infotainment may provide media and/or multimedia content. An example is information-based media content or programming that also includes entertainment content.

A "multi-screen application" refers to an application that is capable of producing one or more windows that may simultaneously occupy one or more screens. A multi-screen application commonly can operate in single-screen mode in which one or more windows of the application are displayed only on one screen or in multi-screen mode in which one or more windows are displayed simultaneously on multiple screens.

A "single-screen application" refers to an application that is capable of producing one or more windows that may occupy only a single screen at a time.

The terms "online community," "e-community," or "virtual community" can mean a group of people that interact via a computer network, for social, professional, educational, and/or other purposes. The interaction can use a variety of media formats, including wikis, blogs, chat rooms, Internet forums, instant messaging, email, and other forms of electronic media. Many media formats may be used in social software separately and/or in combination, including text-based chat rooms and forums that use voice, video text or avatars.

The term "satellite positioning system receiver" can refer to a wireless receiver or transceiver to receive and/or send location signals from and/or to a satellite positioning system (SPS), such as the Global Positioning System ("GPS") (US), GLONASS (Russia), Galileo positioning system (EU), Compass navigation system (China), and Regional Navigational Satellite System (India).

The term "social network service" may include a service provider that builds online communities of people, who share interests and/or activities, or who are interested in exploring the interests and/or activities of others. Social network services can be network-based and may provide a variety of ways for users to interact, such as e-mail and instant messaging services.

The term "social network" can refer to a network-based social network.

The term "screen," "touch screen," "touchscreen," or "touch-sensitive display" refers to a physical structure that enables the user to interact with the computer by touching areas on the screen and provides information to a user through a display. The touch screen may sense user contact in a number of different ways, such as by a change in an electrical parameter (e.g., resistance or capacitance), acoustic wave variations, infrared radiation proximity detection, light variation detection, and the like. In a resistive touch screen, for example, normally separated conductive and resistive metallic layers in the screen pass an electrical current. When a user touches the screen, the two layers make contact in the contacted location, whereby a change in electrical field is noted and the coordinates of the contacted location calculated. In a capacitive touch screen, a capacitive layer stores electrical charge, which is discharged to the user upon contact with the touch screen, causing a decrease in the charge of the capacitive layer. The decrease is measured, and the contacted location coordinates determined. In a surface acoustic wave touch screen, an acoustic wave is transmitted through the screen, and the acoustic wave is disturbed by user contact. A receiving transducer detects the user contact instance and determines the contacted location coordinates.

The term "window" refers to a, typically rectangular, displayed image on at least part of a display that contains or provides content different from the rest of the screen. The window may obscure the desktop. The dimensions and orientation of the window may be configurable either by another module or by a user. When the window is expanded, the window can occupy substantially all of the display space on a screen or screens.

The terms "determine," "calculate," and "compute," and variations thereof, as used herein, are used interchangeably and include any type of methodology, process, mathematical operation, or technique.

It shall be understood that the term "means," as used herein, shall be given its broadest possible interpretation in accordance with 35 U.S.C., Section 112, Paragraph 6 or other applicable law. Accordingly, a claim incorporating the term "means" shall cover all structures, materials, or acts set forth herein, and all of the equivalents thereof. Further, the structures, materials or acts and the equivalents thereof shall include all those described in the summary of the invention, brief description of the drawings, detailed description, abstract, and claims themselves.

The terms "vehicle," "car," "automobile," and variations thereof may be used interchangeably herein and can refer to a device or structure for transporting animate and/or inanimate or tangible objects (e.g., persons and/or things), such as a self-propelled conveyance. A vehicle as used herein can include any conveyance or model of a conveyance, where the conveyance was originally designed for the purpose of moving one or more tangible objects, such as people, animals, cargo, and the like. The term "vehicle" does not require that a conveyance moves or is capable of movement. Typical vehicles may include but are in no way limited to cars, trucks, motorcycles, busses, automobiles, trains, railed conveyances, boats, ships, marine conveyances, submarine conveyances, airplanes, space craft, flying machines, human-powered conveyances, and the like.

The term "profile," as used herein, can refer to any data structure, data store, and/or database that includes one or more items of information associated with a vehicle, a vehicle system, a device (e.g., a mobile device, laptop, mobile phone, etc.), or a person.

The term "in communication with," as used herein, refers to any coupling, connection, or interaction using electrical signals to exchange information or data, using any system, hardware, software, protocol, or format, regardless of whether the exchange occurs wirelessly or over a wired connection.

The preceding is a simplified summary of the disclosure to provide an understanding of some aspects of the disclosure. This summary is neither an extensive nor exhaustive overview of the disclosure and its various aspects, embodiments, and/or configurations. It is intended neither to identify key or critical elements of the disclosure nor to delineate the scope of the disclosure but to present selected concepts of the disclo-

sure in a simplified form as an introduction to the more detailed description presented below. As will be appreciated, other aspects, embodiments, and/or configurations of the disclosure are possible utilizing, alone or in combination, one or more of the features set forth above or described in detail below.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. **1** depicts an embodiment of a vehicle operating environment;

FIG. **2** is a block diagram of an embodiment of a vehicle system;

FIG. **3** is a block diagram of an embodiment of a vehicle control system environment;

FIG. **4** is a block diagram of an embodiment of a vehicle communications subsystem;

FIG. **5**A is a first block diagram of an embodiment of a vehicle interior environment separated into areas and/or zones;

FIG. **5**B is a second block diagram of an embodiment of a vehicle interior environment separated into areas and/or zones;

FIG. **5**C is a third block diagram of an embodiment of a vehicle interior environment separated into areas and/or zones;

FIG. **6**A depicts an embodiment of a sensor configuration for a vehicle;

FIG. **6**B depicts an embodiment of a sensor configuration for a zone of a vehicle;

FIG. **7**A is a block diagram of an embodiment of interior sensors for a vehicle;

FIG. **7**B is a block diagram of an embodiment of exterior sensors for a vehicle;

FIG. **8**A is a block diagram of an embodiment of a media subsystem for a vehicle;

FIG. **8**B is a block diagram of an embodiment of a user and device interaction subsystem for a vehicle;

FIG. **8**C is a block diagram of an embodiment of a Navigation subsystem for a vehicle;

FIG. **9** is a block diagram of an embodiment of a communications subsystem for a vehicle;

FIG. **10** is a block diagram of an embodiment of a software architecture for the vehicle control system;

FIG. **11**A is a graphical representation of an embodiment of a gesture that a user may perform to provide input to a vehicle control system;

FIG. **11**B is a graphical representation of an embodiment of a gesture that a user may perform to provide input to a vehicle control system;

FIG. **11**C is a graphical representation of an embodiment of a gesture that a user may perform to provide input to a vehicle control system;

FIG. **11**D is a graphical representation of an embodiment of a gesture that a user may perform to provide input to a vehicle control system;

FIG. **11**E is a graphical representation of an embodiment of a gesture that a user may perform to provide input to a vehicle control system;

FIG. **11**F is a graphical representation of an embodiment of a gesture that a user may perform to provide input to a vehicle control system;

FIG. **11**G is a graphical representation of an embodiment of a gesture that a user may perform to provide input to a vehicle control system;

FIG. **11**H is a graphical representation of an embodiment of a gesture that a user may perform to provide input to a vehicle control system;

FIG. **11**I is a graphical representation of an embodiment of a gesture that a user may perform to provide input to a vehicle control system;

FIG. **11**J is a graphical representation of an embodiment of a gesture that a user may perform to provide input to a vehicle control system;

FIG. **11**K is a graphical representation of an embodiment of a gesture that a user may perform to provide input to a vehicle control system;

FIG. **12**A is a diagram of an embodiment of a data structure for storing information about a user of a vehicle;

FIG. **12**B is a diagram of an embodiment of a data structure for storing information about a device associated with or in a vehicle;

FIG. **12**C is a diagram of an embodiment of a data structure for storing information about a system of a vehicle;

FIG. **12**D is a diagram of an embodiment of a data structure for storing information about a vehicle;

FIG. **13** is a flow or process diagram of a method for storing one or more settings associated with a user;

FIG. **14** is a flow or process diagram of a method for establishing one or more settings associated with a user;

FIG. **15** is a flow or process diagram of a method for storing one or more settings associated with a user;

FIG. **16** is a flow or process diagram of a method for storing one or more gestures associated with a user;

FIG. **17** is a flow or process diagram of a method for reacting to a gesture performed by a user;

FIG. **18** is a flow or process diagram of a method for storing health data associated with a user;

FIG. **19** is a flow or process diagram of a method for reacting to a gesture performed by a user;

FIG. **20** depicts a flow diagram according to an embodiment;

FIG. **21** depicts an on board media system according to an embodiment;

FIG. **22** depicts a flow diagram according to an embodiment;

FIG. **23** depicts a flow diagram according to an embodiment;

FIG. **24** depicts a computational system according to an embodiment;

FIG. **25** depicts a computational system according to an embodiment;

FIG. **26** depicts a flow diagram according to an embodiment;

FIG. **27** depicts a flow diagram according to an embodiment;

FIG. **28** depicts a screen shot according to an embodiment; and

FIG. **29** depicts a screen shot according to an embodiment;

FIG. **30** depicts a screen shot according to an embodiment;

FIG. **31** depicts a flow diagram according to an embodiment;

FIG. **32** depicts a flow diagram according to an embodiment;

FIG. **33** depicts a segmented control surface according to an embodiment;

FIG. **34** depicts a mapped display according to an embodiment;

FIG. **35** depicts a flow diagram according to an embodiment;

FIG. **36** depicts a flow diagram according to an embodiment;

FIGS. **37**A-B depict a flow diagram according to an embodiment;

FIG. **38** depicts a flow diagram according to an embodiment; and

FIG. **39** depicts a flow diagram according to an embodiment.

In the appended figures, similar components and/or features may have the same reference label. Further, various components of the same type may be distinguished by following the reference label by a letter that distinguishes among the similar components. If only the first reference label is used in the specification, the description is applicable to any one of the similar components having the same first reference label irrespective of the second reference letter or label.

DETAILED DESCRIPTION

Presented herein are embodiments of systems, devices, processes, data structures, user interfaces, etc. The embodiments may relate to an automobile and/or an automobile environment. The automobile environment can include systems associated with the automobile and devices or other systems in communication with the automobile and/or automobile systems. Furthermore, the systems can relate to communications systems and/or devices and may be capable of communicating with other devices and/or to an individual or group of individuals. Further, the systems can receive user input in unique ways. The overall design and functionality of the systems provide for an enhanced user experience making the automobile more useful and more efficient. As described herein, the automobile systems may be electrical, mechanical, electro-mechanical, software-based, and/or combinations thereof

A vehicle environment **100** that may contain a vehicle ecosystem is shown in FIG. **1**. The vehicle environment **100** can contain areas associated with a vehicle or conveyance **104**. The vehicle **104** is shown as a car but can be any type of conveyance. The environment **100** can include at least three zones. A first zone **108** may be inside a vehicle **104**. The zone **108** includes any interior space, trunk space, engine compartment, or other associated space within or associated with the vehicle **104**. The interior zone **108** can be defined by one or more techniques, for example, geo-fencing.

A second zone **112** may be delineated by line **120**. The zone **112** is created by a range of one or more sensors associated with the vehicle **104**. Thus, the area **112** is exemplary of the range of those sensors and what can be detected by those sensors associated with the vehicle **104**. Although sensor range is shown as a fixed and continuous oval, the sensor range may be dynamic and/or discontinuous. For example, a ranging sensor (e.g., radar, lidar, ladar, etc.) may provide a variable range depending on output power, signal characteristics, or environmental conditions (e.g., rain, fog, clear, etc.). The rest of the environment includes all space beyond the range of the sensors and is represented by space **116**. Thus, the environment **100** may have an area **116** that includes all areas beyond the sensor range **112**. The area **116** may include locations of travel that the vehicle **104** may proceed to in the future.

An embodiment of a vehicle system **200** is shown in FIG. **2**. The vehicle system **200** may comprise hardware and/or software that conduct various operations for or with the vehicle **104**. The operations can include, but are not limited to, providing information to the user **216**, receiving input from the user **216**, and controlling the functions or operation of the vehicle **104**, etc. The vehicle system **200** can include a vehicle control system **204**. The vehicle control system **204** can be any type of computing system operable to conduct the operations as described herein. An example of a vehicle control system may be as described in conjunction with FIG. **3**.

The vehicle control system **204** may interact with a memory or storage system **208** that stores system data. System data **208** may be any type of data needed for the vehicle control system **204** to control effectively the vehicle **104**. The system data **208** can represent any type of database or other storage system. Thus, the system data **208** can be a flat file data system, an object-oriented data system, or some other data system that may interface with the vehicle control system **204**.

The vehicle control system **204** may communicate with a device or user interface **212**, **248**. The user interface **212**, **248** may be operable to receive user input either through touch input, on one or more user interface buttons, via voice command, via one or more image sensors, or through a graphical user interface that may include a gesture capture region, as described in conjunction with the other figures provided herein. Further, the symbol **212**, **248** can represent a device that is located or associated with the vehicle **104**. The device **212**, **248** can be a mobile device, including, but not limited to, a mobile telephone, a mobile computer, or other type of computing system or device that is either permanently located in or temporarily associated with, but not necessarily connected to, the vehicle **104**. Thus, the vehicle control system **204** can interface with the device **212**, **248** and leverage the device's computing capability to provide one or more of the features or functions as described herein.

The device or user interface **212**, **248** can receive input or provide information to a user **216**. The user **216** may thus interact with the vehicle control system **204** through the interface or device **212**, **248**. Further, the device **212**, **248** may include or have access to device data **220** and/or profile data **252**. The device data **220** can be any type of data that is used in conjunction with the device **212**, **248** including, but not limited to, multimedia data, preferences data, device identification information, or other types of data. The profile data **252** can be any type of data associated with at least one user **216** including, but in no way limited to, bioinformatics, medical information, driving history, personal information (e.g., home physical address, business physical address, contact addresses, likes, dislikes, hobbies, size, weight, occupation, business contacts—including physical and/or electronic addresses, personal contacts—including physical and/or electronic addresses, family members, and personal information related thereto, etc.), other user characteristics, advertising information, user settings and feature preferences, travel information, associated vehicle preferences, communication preferences, historical information (e.g., including historical, current, and/or future travel destinations), Internet browsing history, or other types of data. In any event, the data may be stored as device data **220** and/or profile data **252** in a storage system similar to that described in conjunction with FIGS. **12**A through **12**D.

As an example, the profile data **252** may include one or more user profiles. User profiles may be generated based on data gathered from one or more of vehicle preferences (e.g., seat settings, HVAC settings, dash configurations, and the like), recorded settings, geographic location information (e.g., provided by a satellite positioning system (e.g., GPS), Wi-Fi hotspot, cell tower data, etc.), mobile device information (such as mobile device electronic addresses, Internet browsing history and content, application store selections, user settings and enabled and disabled features, and the like), private information (such as user information from a social network, user presence information, user business account,

and the like), secure data, biometric information, audio information from on board microphones, video information from on board cameras, Internet browsing history and browsed content using an on board computer and/or the local area network enabled by the vehicle **104**, geographic location information (e.g., a vendor storefront, roadway name, city name, etc.), and the like.

The profile data **252** may include one or more user accounts. User accounts may include access and permissions to one or more settings and/or feature preferences associated with the vehicle **104**, communications, infotainment, content, etc. In one example, a user account may allow access to certain settings for a particular user, while another user account may deny access to the settings for another user, and vice versa. The access controlled by the user account may be based on at least one of a user account priority, role, permission, age, family status, a group priority (e.g., the user account priority of one or more users, etc.), a group age (e.g., the average age of users in the group, a minimum age of the users in the group, a maximum age of the users in the group, and/or combinations thereof, etc.).

For example, a user **216** may be allowed to purchase applications (e.g., software, etc.) for the vehicle **104** and/or a device associated with the vehicle **104** based on information associated with the user account. This user account information may include a preferred payment method, permissions, and/or other account information. As provided herein, the user account information may be part of the user profile and/or other data stored in the profile data **252**.

As another example, an adult user (e.g., a user with an age of 18 years old and/or over, etc.) may be located in an area of a vehicle **104**, such as a rear passenger area. Continuing this example a child user (e.g., a user with an age of 17 years old and/or less, etc.) may be located in the same, or close, area. In this example, the user account information in the profile data **252** associated with both the adult user and the child user may be used by the vehicle **104** in determining whether content is appropriate for the area given the age of the child user. For instance, a graphic movie containing violence (e.g., a movie associated with a mature rating, such as a Motion Picture Association of America (MPAA) rating of "R," "NC-17," etc.) may be suitable to present to a display device associated with the adult user but may not be acceptable to present to the display device if a 12-year old child user may see and/or hear the content of the movie.

The vehicle control system **204** may also communicate with or through a communication network **224**. The communication network **224** can represent any type of wireless and/or wired communication system that may be included within the vehicle **104** or operable to communicate outside the vehicle **104**. Thus, the communication network **224** can include a local area communication capability and a wide area communication capability. For example, the communication network **224** can include a Bluetooth® wireless system, an 802.11x (e.g., 802.11G/802.11N/802.11AC, or the like, wireless system), a CAN bus, an Ethernet network within the vehicle **104**, or other types of communication networks that may function with or be associated with the vehicle **104**. Further, the communication network **224** can also include wide area communication capabilities, including one or more of, but not limited to, a cellular communication capability, satellite telephone communication capability, a wireless wide area network communication capability, or other types of communication capabilities that allow for the vehicle control system **204** to communicate outside the vehicle **104**.

The vehicle control system **204** may communicate through the communication network **224** to a server **228** that may be located in a facility that is not within physical proximity to the vehicle **104**. Thus, the server **228** may represent a cloud computing system or cloud storage that allows the vehicle control system **204** to either gain access to further computing capabilities or to storage at a location outside of the vehicle **104**. The server **228** can include a computer processor and memory and be similar to any computing system as understood to one skilled in the art.

Further, the server **228** may be associated with stored data **232**. The stored data **232** may be stored in any system or by any method, as described in conjunction with system data **208**, device data **220**, and/or profile data **252**. The stored data **232** can include information that may be associated with one or more users **216** or associated with one or more vehicles **104**. The stored data **232**, being stored in a cloud or in a distant facility, may be exchanged among vehicles **104** or may be used by a user **216** in different locations or with different vehicles **104**. Additionally or alternatively, the server may be associated with profile data **252** as provided herein. It is anticipated that the profile data **252** may be accessed across the communication network **224** by one or more components of the system **200**. Similar to the stored data **232**, the profile data **252**, being stored in a cloud or in a distant facility, may be exchanged among vehicles **104** or may be used by a user **216** in different locations or with different vehicles **104**.

The vehicle control system **204** may also communicate with one or more sensors **236**, **242**, which are either associated with the vehicle **104** or communicate with the vehicle **104**. Vehicle sensors **242** may include one or more sensors for providing information to the vehicle control system **204** that determine or provide information about the environment **100** in which the vehicle **104** is operating. Embodiments of these sensors may be as described in conjunction with FIGS. **6**A-**7**B. Non-vehicle sensor **236** can be any type of sensor that is not currently associated with the vehicle **104**. For example, non-vehicle sensor **236** can be sensors in a traffic system operated by a third party that provides data to the vehicle control system **204**. Further, the non-vehicle sensor(s) **236** can be other types of sensors which provide information about the distant environment **116** or other information about the vehicle **104** or the environment **100**. These non-vehicle sensors **236** may be operated by third parties but provide information to the vehicle control system **204**. Examples of information provided by the sensors **236** and that may be used by the vehicle control system **204** may include weather tracking data, traffic data, user health tracking data, vehicle maintenance data, or other types of data, which may provide environmental or other data to the vehicle control system **204**. The vehicle control system **204** may also perform signal processing of signals received from one or more sensors **236**, **242**. Such signal processing may include estimation of a measured parameter from a single sensor, such as multiple measurements of a range state parameter from the vehicle **104** to an obstacle, and/or the estimation, blending, or fusion of a measured state parameter from multiple sensors such as multiple radar sensors or a combination of a ladar/lidar range sensor and a radar sensor. Signal processing of such sensor signal measurements may comprise stochastic signal processing, adaptive signal processing, and/or other signal processing techniques known to those skilled in the art.

The various sensors **236**, **242** may include one or more sensor memory **244**. Embodiments of the sensor memory **244** may be configured to store data collected by the sensors **236**, **242**. For example, a temperature sensor may collect temperature data associated with a vehicle **104**, user **216**, and/or

environment, over time. The temperature data may be collected incrementally, in response to a condition, or at specific time periods. In this example, as the temperature data is collected, it may be stored in the sensor memory **244**. In some cases, the data may be stored along with an identification of the sensor and a collection time associated with the data. Among other things, this stored data may include multiple data points and may be used to track changes in sensor measurements over time. As can be appreciated, the sensor memory **244** can represent any type of database or other storage system.

The diagnostic communications module **256** may be configured to receive and transmit diagnostic signals and information associated with the vehicle **104**. Examples of diagnostics signals and information may include, but is in no way limited to, vehicle system warnings, sensor data, vehicle component status, service information, component health, maintenance alerts, recall notifications, predictive analysis, and the like. Embodiments of the diagnostic communications module **256** may handle warning/error signals in a predetermined manner. The signals, for instance, can be presented to one or more of a third party, occupant, vehicle control system **204**, and a service provider (e.g., manufacturer, repair facility, etc.).

Optionally, the diagnostic communications module **256** may be utilized by a third party (i.e., a party other than the user **216**, etc.) in communicating vehicle diagnostic information. For instance, a manufacturer may send a signal to a vehicle **104** to determine a status associated with one or more components associated with the vehicle **104**. In response to receiving the signal, the diagnostic communications module **256** may communicate with the vehicle control system **204** to initiate a diagnostic status check. Once the diagnostic status check is performed, the information may be sent via the diagnostic communications module **256** to the manufacturer. This example may be especially useful in determining whether a component recall should be issued based on the status check responses returned from a certain number of vehicles.

Wired/wireless transceiver/communications ports **260** may be included. The wired/wireless transceiver/communications ports **260** may be included to support communications over wired networks or links, for example with other communication devices, server devices, and/or peripheral devices. Examples of wired/wireless transceiver/communications ports **260** include Ethernet ports, Universal Serial Bus (USB) ports, Institute of Electrical and Electronics Engineers (IEEE) 1594, or other interface ports.

An embodiment of a vehicle control environment **300** including a vehicle control system **204** may be as shown in FIG. **3**. Beyond the vehicle control system **204**, the vehicle control environment **300** can include one or more of, but is not limited to, a power source and/or power control module **316**, a data storage module **320**, user interface(s)/input interface(s) **324**, vehicle subsystems **328**, user interaction subsystems **332**, Global Positioning System (GPS)/Navigation subsystems **336**, sensor(s) and/or sensor subsystems **340**, communication subsystems **344**, media subsystems **348**, and/or device interaction subsystems **352**. The subsystems, modules, components, etc. **316-352** may include hardware, software, firmware, computer readable media, displays, input devices, output devices, etc. or combinations thereof. The system, subsystems, modules, components, etc. **204**, **316-352** may communicate over a network or bus **356**. This communication bus **356** may be bidirectional and perform data communications using any known or future-developed standard or protocol. An example of the communication bus **356** may be as described in conjunction with FIG. **4**.

The vehicle control system **204** can include a processor **304**, memory **308**, and/or an input/output (I/O) module **312**. Thus, the vehicle control system **204** may be a computer system, which can comprise hardware elements that may be electrically coupled. The hardware elements may include one or more central processing units (CPUs) **304**; one or more components of the I/O module **312** including input devices (e.g., a mouse, a keyboard, etc.) and/or one or more output devices (e.g., a display device, a printer, etc.).

The processor **304** may comprise a general purpose programmable processor or controller for executing application programming or instructions. The processor **304** may, optionally, include multiple processor cores, and/or implement multiple virtual processors. Additionally or alternatively, the processor **304** may include multiple physical processors. As a particular example, the processor **304** may comprise a specially configured application specific integrated circuit (ASIC) or other integrated circuit, a digital signal processor, a controller, a hardwired electronic or logic circuit, a programmable logic device or gate array, a special purpose computer, or the like. The processor **304** generally functions to run programming code or instructions implementing various functions of the vehicle control system **204**.

The input/output module **312** and associated ports may be included to support communications over wired or wireless networks or links, for example with other communication devices, server devices, and/or peripheral devices. Examples of an input/output module **312** include an Ethernet port, a Universal Serial Bus (USB) port, Institute of Electrical and Electronics Engineers (IEEE) 1594, or other interface.

The vehicle control system **204** may also include one or more storage devices **308**. By way of example, storage devices **308** may be disk drives, optical storage devices, solid-state storage devices such as a random access memory ("RAM") and/or a read-only memory ("ROM"), which can be programmable, flash-updateable and/or the like. The vehicle control system **204** may additionally include a computer-readable storage media reader; a communications system (e.g., a modem, a network card (wireless or wired), an infra-red communication device, etc.); and working memory **308**, which may include RAM and ROM devices as described above. The vehicle control system **204** may also include a processing acceleration unit, which can include a digital signal processor (DSP), a special-purpose processor, and/or the like.

The computer-readable storage media reader can further be connected to a computer-readable storage medium, together (and, optionally, in combination with storage device(s)) comprehensively representing remote, local, fixed, and/or removable storage devices plus storage media for temporarily and/or more permanently containing computer-readable information. The communications system may permit data to be exchanged with an external or internal network and/or any other computer or device described herein. Moreover, as disclosed herein, the term "storage medium" may represent one or more devices for storing data, including read only memory (ROM), random access memory (RAM), magnetic RAM, core memory, magnetic disk storage mediums, optical storage mediums, flash memory devices, and/or other machine readable mediums for storing information.

The vehicle control system **204** may also comprise software elements including an operating system and/or other code, as described in conjunction with FIG. **10**. It should be appreciated that alternates to the vehicle control system **204** may have numerous variations from that described herein.

For example, customized hardware might also be used and/or particular elements might be implemented in hardware, software (including portable software, such as applets), or both. Further, connection to other computing devices such as network input/output devices may be employed.

The power source and/or power control module **316** can include any type of power source, including, but not limited to, batteries, alternating current sources (from connections to a building power system or power line), solar cell arrays, etc. One or more components or modules may also be included to control the power source or change the characteristics of the provided power signal. Such modules can include one or more of, but is not limited to, power regulators, power filters, alternating current (AC) to direct current (DC) converters, DC to AC converters, receptacles, wiring, other converters, etc. The power source and/or power control module **316** functions to provide the vehicle control system **204** and any other system with power.

The data storage **320** can include any module for storing, retrieving, and/or managing data in one or more data stores and/or databases. The database or data stores may reside on a storage medium local to (and/or resident in) the vehicle control system **204** or in the vehicle **104**. Alternatively, some of the data storage capability may be remote from the vehicle control system **204** or automobile, and in communication (e.g., via a network) to the vehicle control system **204**. The database or data stores may reside in a storage-area network ("SAN") familiar to those skilled in the art. Similarly, any necessary files for performing the functions attributed to the vehicle control system **204** may be stored locally on the respective vehicle control system **204** and/or remotely, as appropriate. The databases or data stores may be a relational database, and the data storage module **320** may be adapted to store, update, and retrieve data in response to specifically-formatted commands. The data storage module **320** may also perform data management functions for any flat file, object oriented, or other type of database or data store.

A first data store that may be part of the vehicle control environment **300** is a profile data store **252** for storing data about user profiles and data associated with the users. A system data store **208** can include data used by the vehicle control system **204** and/or one or more of the components **324-352** to facilitate the functionality described herein. The data stores **208** and/or **252** may be as described in conjunction with FIGS. **1** and/or **12**A-**12**D.

The user interface/input interfaces **324** may be as described herein for providing information or data and/or for receiving input or data from a user. Vehicle systems **328** can include any of the mechanical, electrical, electromechanical, computer, or other systems associated with the function of the vehicle **100**. For example, vehicle systems **328** can include one or more of, but is not limited to, the steering system, the braking system, the engine and engine control systems, the electrical system, the suspension, the drive train, the cruise control system, the radio, the heating, ventilation, air conditioning (HVAC) system, the windows and/or doors, etc. These systems are well known in the art and will not be described further.

Examples of the other systems and subsystems **324-352** may be as described further herein. For example, the user interface(s)/input interface(s) **324** may be as described in FIGS. **2** and **8**B; the vehicle subsystems **328** may be as described in FIG. **6***a* et. seq.; the user interaction subsystem **332** may be as described in conjunction with the user/device interaction subsystem **817** of FIG. **8**B; the Navigation subsystem **336** may be as described in FIGS. **6**A and **8**C; the sensor(s)/sensor subsystem **340** may be as described in FIGS. **7**A and **7**B; the communication subsystem **344** may be as described in FIGS. **2**, **4**, **5**B, **5**C, and **9**; the media subsystem **348** may be as described in FIG. **8**A; and, the device interaction subsystem **352** may be as described in FIG. **2** and in conjunction with the user/device interaction subsystem **817** of FIG. **8**B.

FIG. **4** illustrates an optional communications channel architecture **400** and associated communications components. FIG. **4** illustrates some of the optional components that can be interconnected via the communication channels/zones **404**. Communication channels/zones **404** can carry information on one or more of a wired and/or wireless communications link with, in the illustrated example, there being three communications channels/zones, **408**, **412**, and **416**.

This optional environment **400** can also include an IP router **420**, an operator cluster **424**, one or more storage devices **428**, one or more blades, such as master blade **432**, and computational blades **436** and **440**. Additionally, the communications channels/zones **404** can interconnect one or more displays, such as, remote display 1 **444**, remote display N **448**, and console display **452**. The communications channels/zones **404** also interconnect an access point **456**, a Bluetooth® access point/USB hub **460**, a Femtocell **464**, a storage controller **468**, that is connected to one or more of USB devices **472**, DVDs **476**, or other storage devices **480**. To assist with managing communications within the communication channel, the environment **400** optionally includes a firewall **484** which will be discussed hereinafter in greater detail. Other components that could also share the communications channel/zones **404** include GPS **488**, media controller **492**, which is connected to one or more media sources **496**, and one or more subsystems, such as subsystem switches **498**.

Optionally, the communications channels/zones **404** can be viewed as an I/O network or bus where the communications channels are carried on the same physical media. Optionally, the communication channels **404** can be split amongst one or more physical media and/or combined with one or more wireless communications protocols. Optionally, the communications channels **404** can be based on wireless protocols with no physical media interconnecting the various elements described herein.

The environment **400** shown in FIG. **4** can include a collection of blade processors that are housed in a "crate." The crate can have a PC-style backplane connector **408** and a backplane Ethernet **408** that allows the various blades to communicate with one another using, for example, an Ethernet.

Various other functional elements illustrated in FIG. **4** can be integrated into this crate architecture with, as discussed hereinafter, various zones utilized for security. Optionally, as illustrated in FIG. **4**, the backplane **404**/**408** can have two separate Ethernet zones that may or may not be on the same communications channel. Optionally, the zones exist on a single communications channel on the I/O network/bus **408**. Optionally, the zones are actually on different communications channels, e.g., **412**, **416**; however, the implementation is not restricted to any particular type of configuration. Rather, as illustrated in FIG. **4**, there can be a red zone **417** and a green zone **413**, and the I/O backplane on the network/bus **408** that enables standard I/O operations. This backplane or I/O network/bus **408** also optionally can provide power distribution to the various modules and blades illustrated in FIG. **4**. The red and green Ethernet zones, **417** and **413** respectively, can be implemented as Ethernet switches, with one on each side of the firewall **484**. Two Ethernets (untrusted and trusted) are not connected in accordance with an optional embodiment.

Optionally, the connector geometry for the firewall can be different for the Ethernet zones than for the blades that are a part of the system.

The red zone **417** only needs to go from the modular connector to the input side of the backplane connector of the firewall **484**. While FIG. **4** indicates that there are five external red zone connectors to the firewall **484**, provisions can be made for any number of ports with the connections being made at the access point **456**, the Bluetooth® access point (combo controller) **460**, Femtocell **464**, storage controller **468**, and/or firewall **484**. Optionally, the external port connections can be made through a manufacturer configurable modular connector panel, and one or more of the red zone Ethernet ports could be available through a customer supplied crate which allows, for example, wired Ethernet connections from a bring-your-own-device (BYOD) to the firewall **484**.

The green zone **413** goes from the output side of the firewall **484** and generally defines the trusted Ethernet. The Ethernet on the backplane **408** essentially implements an Ethernet switch for the entire system, defining the Ethernet backbone of the vehicle **104**. All other modules, e.g., blades, etc., can connect to a standard backplane bus and the trusted Ethernet. Some number of switch ports can be reserved to connect to an output modular connector panel to distribute the Ethernet throughout the vehicle **104**, e.g., connecting such elements as the console display **452**, remote displays **444**, **448**, GPS **488**, etc. Optionally, only trusted components, either provided or approved by the manufacturer after testing, can be attached to the green zone **413**, which is by definition in the trusted Ethernet environment.

Optionally, the environment **400**, shown in FIG. **4**, utilizes IPv6 over Ethernet connections wherever possible. Using, for example, the Broadcom single-twisted pair Ethernet technology, wiring harnesses are simplified and data transmission speeds are maximized. However, while the Broadcom single-twisted pair Ethernet technology can be used, in general, systems and methods can work comparably well with any type of well-known Ethernet technology or other comparable communications technology.

As illustrated in FIG. **4** the I/O network/bus **408** is a split-bus concept that contains three independent bus structures:

The red zone **417**—the untrusted Ethernet environment. This zone **417** may be used to connect network devices and customer provided devices to the vehicle information system with these devices being on the untrusted side of the firewall **484**.

The green zone **413**—the trusted Ethernet environment, this zone **413** can be used to connect manufacturer certified devices such as GPS units, remote displays, subsystem switches, and the like, to the vehicle network **404**. Manufacturer certified devices can be implemented by vendors that allow the vehicle software system to validate whether or not a device is certified to operate with the vehicle **100**. Optionally, only certified devices are allowed to connect to the trusted side of the network.

The I/O bus **409**—the I/O bus may be used to provide power and data transmission to bus-based devices such as the vehicle solid state drive, the media controller blade **492**, the computational blades **436**, **440**, and the like.

As an example, the split-bus structure can have the following minimum configuration:

Two slots for the red zone Ethernet;

One slot for built-in LTE/WiMax access **420** from the car to other network resources such as the cloud/Internet;

One slot for user devices or bring-your-own device access, this slot can implement, for example, WiFi, Bluetooth®, and/or USB connectivity **456**, which can be provided in, for example, the customer crate;

One slot for combined red zone and green zone Ethernet, this slot can be reserved for the firewall controller;

Two slots for computational blades. Here the two computation blades are illustratively as shown the optional master blade and the multimedia blade or controller **492** which can be provided as standard equipment; and

The expansion controller that allows the I/O bus to be extended and provides additional Ethernet switch ports for one or more of the red or green zones, which may require that the basic green zone Ethernet switch implementation will support additional ports beyond the initial three that are needed for the basic exemplary system.

It should be possible to build 8 or 16 or more Ethernet switches that allow for the expansion with existing component(s) in a straight-forward manner.

The red zone **417** can be implemented as an 8-port Ethernet switch that has three actual bus ports within the crate with the remaining five ports being available on the customer crate. The crate implements red zone slots for the firewall controller **484**, the combo controller which includes WiFi, Bluetooth®, USB hub (**456**, **460**) and the IP router **420**.

The firewall controller **484** can have a dedicated slot that bridges the red zone **417**, green zone **413**, and uses the I/O bus for power connections. In accordance with an optional low cost implementation, the firewall **484** can be implemented by a dummy module that simply bridges the red zone **417** and the green zone **413** without necessarily providing any firewall functionality. The combo controller **460** that includes the WiFi, Bluetooth®, and USB hub can be provided for consumer device connections. This controller can also implement the IPv6 (un-routable) protocol to insure that all information is packetized for transmission via IP over the Ethernet in the I/O network/bus **408**.

The combo controller **460** with the USB hub can have ports in the customer crate. The combo controller **460** can implement USB discovery functions and packetizes the information for transmission via IP over Ethernet. The combo controller **460** can also facilitate installation of the correct USB driver for the discovered device, such as a BYOD from the user. The combo controller **460** and USB hub can then map the USB address to a "local" IPv6 address for interaction with one or more of the computational blades which is generally going to be the media controller **492**.

The IP router **420** can implement Internet access through a manufacturer provided service. This service can allow, for example, a manufacturer to offer value-added services to be integrated into the vehicle information systems. The existence of the manufacturer provided Internet access can also allow the "e-Call" function and other vehicle data recorder functions to be implemented. IP router **420** also allows, for example, WiMax, 4G LTE, and other connections to the Internet through a service provider that can be, for example, contracted by the manufacturer. Internally, the IP router **420** can allow cellular handset connections to the Internet through a Femtocell **464** that is part of the IP router implementation. The IP router **420**, with the Femtocell **464**, can also allow a cone of silence functionality to be implemented. The IP router **420** can be an optional component for a vehicle provided by, for example, the manufacturer, a dealer, or installed by a user. In the absence of the IP router **420**, it is possible to connect a consumer handheld device to the I/O network/bus **408** using, for example, either WiFi or Bluetooth® **456**, **460**. While functionality may be somewhat reduced when using a hand-

held device instead of a built-in Ethernet connection, systems and methods of this invention can also work utilizing this consumer handheld device which then connects to the Internet via, for example, WiMax, 4G, 4G LTE, or the like.

FIGS. **5**A-**5**C show configurations of a vehicle **104**. In general, a vehicle **104** may provide functionality based at least partially on one or more areas, zones, and distances, associated with the vehicle **104**. Non-limiting examples of this functionality are provided herein below.

An arrangement or configuration for sensors within a vehicle **104** is as shown in FIG. **5**A. The sensor arrangement **500** can include one or more areas **508** within the vehicle. An area can be a larger part of the environment inside or outside of the vehicle **104**. Thus, area one **508**A may include the area within the trunk space or engine space of the vehicle **104** and/or the front passenger compartment. Area two **508**B may include a portion of the interior space **108** (e.g., a passenger compartment, etc.) of the vehicle **104**. The area N, **508**N, may include the trunk space or rear compartment area, when included within the vehicle **104**. The interior space **108** may also be divided into other areas. Thus, one area may be associated with the front passenger's and driver's seats, a second area may be associated with the middle passengers' seats, and a third area may be associated with a rear passenger's seat. Each area **508** may include one or more sensors that are positioned or operate to provide environmental information about that area **508**.

Each area **508** may be further separated into one or more zones **512** within the area **508**. For example, area 1 **508**A may be separated into zone A **512**A, and zone B **512**B. Each zone **512** may be associated with a particular portion of the interior occupied by a passenger. For example, zone A **512**A may be associated with a driver. Zone B **512**B, may be associated with a front passenger. Each zone **512** may include one or more sensors that are positioned or configured to collect information about the environment or ecosystem associated with that zone or person.

A passenger area **508**B may include more than two zones as described in conjunction with area **508**A. For example, area **508**B may include three zones, **512**C, **512**D, and **512**E. These three separate zones **512**C, **512**D, and **512**E may be associated with three passenger seats typically found in the rear passenger area of a vehicle **104**. An area **508**N and may include a single zone **512**N as there may be no separate passenger areas but may include a single trunk area within the vehicle **104**. The number of zones **512** is unlimited within the areas as the areas are also unlimited inside the vehicle **104**. Further, it should be noted that there may be one or areas **508** or zones **512** that may be located outside the vehicle **104** that may have a specific set of sensors associated therewith.

Optionally, each area/access point **508**, **456**, **516**, **520**, and/or zone **512**, associated with a vehicle **104**, may comprise one or more sensors to determine a presence of a user **216** and/or device **212**, **248** in and/or adjacent to each area **508**, **456**, **516**, **520**, and/or zone **512**. The sensors may include vehicle sensors **242** and/or non-vehicle sensors **236** as described herein. It is anticipated that the sensors may be configured to communicate with a vehicle control system **204** and/or the diagnostic communications module **256**. Additionally or alternatively, the sensors may communicate with a device **212**, **248**. The communication of sensors with the vehicle **104** may initiate and/or terminate the control of device **212**, **248** features. For example, a vehicle operator may be located in a second outside area **520** associated with a vehicle **104**. As the operator approaches the first outside area **516**, associated with the vehicle **104**, the vehicle control system **204** may determine to control features associated with one or more device **212**, **248** and diagnostic communications module **256**.

Optionally, the location of the device **212**, **248** relative to the vehicle **104** may determine vehicle functionality and/or features to be provided and/or restricted to a user **216**. By way of example, a device **212**, **248** associated with a user **216** may be located at a second outside area **520** from the vehicle **104**. In this case, and based at least partially on the distance of the device **212**, **248** from the vehicle **104** (e.g., provided by detecting the device **212**, **248** at or beyond the second outside area **520**) the vehicle **104** may lock one or more features (e.g., ignition access, vehicle access, communications ability, etc.) associated with the vehicle **104**. Optionally, the vehicle **104** may provide an alert based on the distance of the device **212**, **248** from the vehicle **104**. Continuing the example above, once the device **212**, **248** reaches the first outside area **516** of the vehicle **104** at least one of the vehicle features may be unlocked. For instance, by reaching the first outside area **516**, the vehicle **104** may unlock a door of the vehicle **104**. In some cases, when the device is detected to be inside the vehicle **104**, the various sensors **236**, **242** may determine that the user **216** is in an area **508** and/or zone **512**. As is further described herein, features of the vehicle **104**, device **212**, **248**, and/or other components may be controlled based on rules stored in a memory.

FIG. **5**B illustrates optional internal vehicle communications between one or more of the vehicle and one or more devices or between devices. Various communications can occur utilizing one or more Bluetooth®, NFC, WiFi, mobile hot spot, point-to-point communications, point-to-multipoint other point communications, an ad hoc network, or in general any known communications protocol over any known communications media or media-types.

Optionally, various types of internal vehicle communications can be facilitated using an access point **456** that utilizes one or more of Bluetooth®, NFC, WiFi, wireless Ethernet, mobile hot spot technology, or the like. Upon being connected with, and optionally authenticated to the access point **456**, the connected device is able to communicate with one or more of the vehicle and one or more other devices that are connected to the access point **456**. The type of connection to the access point **456** can be based on, for example, the zone **512**, in which the device is located.

The user may identify their zone **512** in conjunction with an authentication procedure to the access point **456**. For example, a driver in zone A **512**A, upon authenticating to the access point **456**, can cause the access point **456** to send a query to the device asking the device user in which zone **512** they are located. As discussed hereinafter, the zone **512** the user device is located in may have an impact on the type of communications, available bandwidth, the types of other devices or vehicle systems or subsystems the device could communicate with, and the like. As a brief introduction, internal communications with zone A **512**A may be given preferential treatment over those communications originating from area 2 **508**B, which could have in itself, preferential treatment over communications originating within area N **508**N.

Moreover, the device in zone A **512**A can include profile information that governs the other devices that are allowed to connect to the access point **456** and what those devices have access to, how they can communicate, how much bandwidth they are allocated, and the like. While, optionally, the device associated with zone A **512**A will be considered the "master" controller of the profile that governs the internal vehicle communications, it should be appreciated that this was arbitrarily chosen since it is assumed that there will always be a driver in a car that is present in zone A **512**A. However, it should be

appreciated the driver in zone A **512**A, for example, may not have a communications device in which case a device associated with one of the other areas or zones, such as zone B **512**B, area 2 **508**B, or area N **508**N could also be associated with or control this master profile.

Optionally, various devices located within the various zones **512** can connect using, for example, ports provided by access point **456** or Bluetooth® access point/USB hub **460** as illustrated in FIG. **4**. Similarly, the device(s) could connect utilizing the Femtocell **464** and optionally be directly connected via, for example, a standard Ethernet port.

As discussed, each one of the areas, area 1 **508**A, area 2 **508**B, and area N **508**N, can each have associated therewith a profile that governs, for example, how many and what types of devices can connect from that area **508**, bandwidth allocated to that area **508**, the types of media or content available to device(s) within that area **508**, the interconnection of devices within that area **508** or between areas **508**, or, in general, can control any aspect of communication of an associated device with any one or more other associated devices/vehicle systems within the vehicle **104**.

Optionally, area 2 **508**B devices can be provided with full access to multimedia and infotainment available within the vehicle **104**, however, devices in area 2 **508**B may be restricted from any access to vehicle functions. Only devices in area 1 **508**A may be able to access vehicle control functions such as when "parents" are located in area 1 **508**A and the children are located in area 2 **508**B. Optionally, devices found in zone E **512**E of area 2 **508**B may be able to access limited vehicle control functionality such as climate control within area 2. Similarly, devices in area N **508**N may be able to control climate features within zone N **512**N.

As will be appreciated, profiles can be established that allow management of communications within each of the areas **508**, and further optionally within each of the zones **512**. The profile can be granular in nature controlling not only what type of devices can connect within each zone **512**, but how those devices can communicate with other devices and/or the vehicle and types of information that can be communicated.

To assist with identifying a location of a device within a zone **512**, a number of different techniques can be utilized. One optional technique involves one or more of the vehicle sensors detecting the presence of an individual within one of the zones **512**. Upon detection of an individual in a zone **512**, communications subsystems **344** and the access point **456** can cooperate to not only associate the device within the zone **512** with the access point **456** but to also determine the location of the device within an area, and optionally within a zone **512**. Once the device is established within a zone **512**, a profile associated with the vehicle **104** can store information identifying that device and/or a person and optionally associating it with a particular zone **512** as a default. As discussed, there can be a master profile optionally associated with the device in zone A **512**A, this master profile can govern communications with the communications subsystems **340** and where communications within vehicle **104** are to occur.

Some optional profiles are illustrated below where the Master Profile governs other device connectivity:

Master Profile:

Area 1 508A	Area 2 508B	Area N 508N	Other
All Communications	Allow Access to Infotainment	No Access	Master Profile acts as Firewall and Router
All Vehicle Controls	Allow Area 2 Climate Control		

Secondary Profile (e.g., Device in Zone B **512**B, Area 1 **508**A)

Area 1 508A	Area 2 508B	Area N 508N	Other
All Communications	Allow Access to Infotainment	Allow Access to Infotainment	Master Profile acts as Firewall and Router
All Vehicle Controls	Allow Area 2 Climate Control	Allow Area 2 Climate Control	

Secondary Profile, Option 2

Area 1 508A	Area 2 508B	Area N 508N	Other
All Communications	Allow Access to Infotainment, Internet	Allow Access to Infotainment	
All Vehicle Controls Except Driver-centric Controls	Allow Area 2 Climate Control	Allow Area 2 Climate Control	

Some optional profiles are illustrated below where the Area/Zone governs device connectivity:

Area 2 **508**B Profile:

Area 1 508A	Area 2 508B	Area N 508N	Other
No Communications with Area 1 Devices	Allow Access to Infotainment, Allow Access to Other Area 2 or Zone N Devices, Internet		
No Vehicle Controls	Allow Area 2 Climate Control		

Area N **508**N Profile:

Area 1 508A	Area 2 508B	Area N 508N	Other
Communications with Area 1, Zone B Device		Allow Access to Infotainment, Allow Access to Other Area N or Zone N Devices	
No Vehicle Controls		Allow Area N Climate Control	

Area 2 **508**B Profile:

Area 1 508A	Area 2 508B	Area N 508N	Other
Media Sharing with Area 1, Zone B and Vehicle	Allow Access to Infotainment, Allow Access to Other Area 2 or Zone N Devices, Internet and Femtocell		
No Vehicle Controls			

Optionally, a user's device, such as a SmartPhone, can store in, for example a profile, with which zone **512** the user's device is associated. Then, assuming the user sits in the same zone **512** and area **508** as previously, the user's device can re-establish the same communications protocols with the access point **456** as were previously established.

In addition or in the alternative, the areas **508** and zones **512** can have associated therewith restrictions as to which one or more other user's devices with which users' devices can connect. For example, a first user's device can connect with any other user device in area 2 **508**B or area N **508**N, however is restricted from connecting with a user device in area 1 **508**A, zone A **512**A. However, the first user device may be able to communicate with another user's device that is located in area 1 **508**A, zone B **512**B. These communications can include any type of standard communications such as sharing content, exchanging messages, forwarding or sharing multimedia or infotainment, or in general can include any communications that would ordinarily be available between two devices and/or the vehicle and vehicle systems. As discussed, there may be restrictions on the type of communications that can be sent to the device in area 1 **508**A, zone A **512**A. For example, the user's device in area 1 **508**A, zone A **512**A may be restricted from receiving one or more of text messages, multimedia, infotainment, or in general anything that can be envisioned as a potential distraction to the driver. Moreover, it should be appreciated that the communications between the various devices and the various zones **512** need not necessarily occur with the assistance of access point **456**, but the communications could also occur directly between the device(s).

FIG. **5**C outlines optional internal vehicle communications between one or more of the vehicle and one or more devices. More specifically, FIG. **5**C illustrates an example of vehicle communications where the vehicle **104** is equipped with the necessary transceivers to provide a mobile hot spot functionality to any user device(s) therein, such as user devices **248**A and **248**N.

Optionally, and as discussed above, one or more user devices can connect to the access point **456**. This access point **456** is equipped to handle communications routing to not only the communication network/buses **224** for intra-vehicle communications, but optionally can also communicate with, for example, the Internet or the cloud, in cooperation with transceiver **260**. Optionally included is a firewall **484** that has the capability of not only blocking certain types of content, such as a malicious content, but can also operate to exclude certain type of communications from emanating from the vehicle **104** and transceiver **260**. As will be appreciated, various profiles could be established in the firewall **484** that controls not only the type of communications that can be received at the vehicle **104**, but the type of communications that can be sent from the vehicle **104**.

The transceiver **260** can be any type of well-known wireless transceiver that communicates using a known communications protocol such as WiMax, 4G, 4G LTE, 3G, or the like. The user devices can communicate via, for example, WiFi link **248** with the access point **456**, with the transceiver **260** providing Internet connectivity to the various user devices. As will be appreciated, there may need to be an account associated with transceiver **260** with a wireless carrier to provide data and/or voice connectivity to enable the user devices to communicate with the Internet. Typically, the account is established on a month-to-month basis with an associated fee but could also be performed based on the amount of data to be transmitted, received, or in any other manner.

Moreover, one or more of the user's devices and access point **456** can maintain profile information that governs how the user's devices are able to communicate with other devices, and optionally the Internet. Optionally, a profile can exist that only allows the user's devices to communicate with other user's devices and/or the vehicle, multimedia and/or the vehicle infotainment system, and may not be allowed access to the Internet via transceiver **260**. The profile can stipulate that the user's device could connect to the Internet via transceiver **260** for a specified period of time and/or up to a certain amount of data usage. The user's device can have full access to the Internet via transceiver **260** with no limit on time or data usage which would reduce the data usage of the user's device since it is connected via WiFi to the access point **456**, but however, would increase the data usage by transceiver **260**, and therefore, shift the billing for that data usage to the transceiver **260** instead of the user's device. Still further, and as previously discussed, the various profiles may stipulate which user's device has priority for use of the bandwidth provided by the transceiver **260**. For example, a user's device located area 1 **508**A, zone A **512**A may be given preferential routing treatment of data above that of a user's device in zone N **512**N. In this manner, for example, a driver would be given priority for Internet access above that of the passengers. This could become important, for example, when the driver is trying to obtain traffic or direction information or, for example, when the vehicle is performing a download to update various software features.

As will be appreciated, the optional firewall **484** can cooperate with the access point **456** and the various profiles that area **508** associated with the various devices within the vehicle **104** and can fully implement communications restrictions, control bandwidth limits, Internet accessibility, malicious software blocking, and the like. Moreover, the optional firewall **484** can be accessed by an administrator with one or more of these configuration settings edited through an administrator's control panel. For example, in a scenario where parents are always in area 1 **508**A, it may be appropriate to give all of the user's devices in area 1 **508**A full access to the Internet utilizing transceiver **260**, however, while restricting access and/or bandwidth to any other user devices within the vehicle **104**. As the user's device and profile would be known by the firewall **484**, upon the user's device being associated with the access point **456**, the firewall **484** and transceiver **260** can be configured to allow communications in accordance with the stored profile.

A set of sensors or vehicle components **600** associated with the vehicle **104** may be as shown in FIG. **6**A. The vehicle **104** can include, among many other components common to vehicles, wheels **607**, a power source **609** (such as an engine, motor, or energy storage system (e.g., battery or capacitive energy storage system)), a manual or automatic transmission **612**, a manual or automatic transmission gear controller **616**, a power controller **620** (such as a throttle), a vehicle control system **204**, the display device **212**, a braking system **636**, a steering wheel **640**, a power source activation/deactivation switch **644** (e.g., an ignition), an occupant seating system **648**, a wireless signal receiver **653** to receive wireless signals from signal sources such as roadside beacons and other electronic roadside devices, and a satellite positioning system receiver **657** (e.g., a Global Positioning System ("GPS") (US), GLONASS (Russia), Galileo positioning system (EU), Compass navigation system (China), and Regional Navigational Satellite System (India) receiver), driverless systems (e.g., cruise control systems, automatic steering systems, automatic braking systems, etc.).

The vehicle **104** can include a number of sensors in wireless or wired communication with the vehicle control system **204** and/or display device **212**, **248** to collect sensed information regarding the vehicle state, configuration, and/or operation. Exemplary sensors may include one or more of, but are not limited to, wheel state sensor **660** to sense one or more of vehicle speed, acceleration, deceleration, wheel rotation, wheel speed (e.g., wheel revolutions-per-minute), wheel slip, and the like, a power source energy output sensor **664** to sense a power output of the power source **609** by measuring one or more of current engine speed (e.g., revolutions-per-minute), energy input and/or output (e.g., voltage, current, fuel consumption, and torque) (e.g., turbine speed sensor, input speed sensor, crankshaft position sensor, manifold absolute pressure sensor, mass flow sensor, and the like), and the like, a switch state sensor **668** to determine a current activation or deactivation state of the power source activation/deactivation switch **644**, a transmission setting sensor **670** to determine a current setting of the transmission (e.g., gear selection or setting), a gear controller sensor **672** to determine a current setting of the gear controller **616**, a power controller sensor **674** to determine a current setting of the power controller **620**, a brake sensor **676** to determine a current state (braking or non-braking) of the braking system **636**, a seating system sensor **678** to determine a seat setting and current weight of seated occupant, if any) in a selected seat of the seating system **648**, exterior and interior sound receivers **690** and **692** (e.g., a microphone, sonar, and other type of acoustic-to-electric transducer or sensor) to receive and convert sound waves into an equivalent analog or digital signal. Examples of other sensors (not shown) that may be employed include safety system state sensors to determine a current state of a vehicular safety system (e.g., air bag setting (deployed or undeployed) and/or seat belt setting (engaged or not engaged)), light setting sensor (e.g., current headlight, emergency light, brake light, parking light, fog light, interior or passenger compartment light, and/or tail light state (on or off)), brake control (e.g., pedal) setting sensor, accelerator pedal setting or angle sensor, clutch pedal setting sensor, emergency brake pedal setting sensor, door setting (e.g., open, closed, locked or unlocked) sensor, engine temperature sensor, passenger compartment or cabin temperature sensor, window setting (open or closed) sensor, one or more interior-facing or exterior-facing cameras or other imaging sensors (which commonly convert an optical image into an electronic signal but may include other devices for detection objects such as an electromagnetic radiation emitter/receiver that emits electromagnetic radiation and receives electromagnetic waves reflected by the object) to sense objects, such as other vehicles and pedestrians and optionally determine the distance, trajectory and speed of such objects, in the vicinity or path of the vehicle, odometer reading sensor, trip mileage reading sensor, wind speed sensor, radar transmitter/receiver output, brake wear sensor, steering/torque sensor, oxygen sensor, ambient lighting sensor, vision system sensor, ranging sensor, parking sensor, heating, venting, and air conditioning (HVAC) sensor, water sensor, air-fuel ratio meter, blind spot monitor, hall effect sensor, microphone, radio frequency (RF) sensor, infrared (IR) sensor, vehicle control system sensors, wireless network sensor (e.g., Wi-Fi and/or Bluetooth® sensor), cellular data sensor, and other sensors either future-developed or known to those of skill in the vehicle art.

In the depicted vehicle embodiment, the various sensors can be in communication with the display device **212**, **248** and vehicle control system **204** via signal carrier network **224**. As noted, the signal carrier network **224** can be a network of signal conductors, a wireless network (e.g., a radio frequency, microwave, or infrared communication system using a communications protocol, such as Wi-Fi), or a combination thereof. The vehicle control system **204** may also provide signal processing of one or more sensors, sensor fusion of similar and/or dissimilar sensors, signal smoothing in the case of erroneous "wild point" signals, and/or sensor fault detection. For example, ranging measurements provided by one or more RF sensors may be combined with ranging measurements from one or more IR sensors to determine one fused estimate of vehicle range to an obstacle target.

The control system **204** may receive and read sensor signals, such as wheel and engine speed signals, as a digital input comprising, for example, a pulse width modulated (PWM) signal. The processor **304** can be configured, for example, to read each of the signals into a port configured as a counter or configured to generate an interrupt on receipt of a pulse, such that the processor **304** can determine, for example, the engine speed in revolutions per minute (RPM) and the speed of the vehicle in miles per hour (MPH) and/or kilometers per hour (KPH). One skilled in the art will recognize that the two signals can be received from existing sensors in a vehicle comprising a tachometer and a speedometer, respectively. Alternatively, the current engine speed and vehicle speed can be received in a communication packet as numeric values from a conventional dashboard subsystem comprising a tachometer and a speedometer. The transmission speed sensor signal can be similarly received as a digital input comprising a signal coupled to a counter or interrupt signal of the processor **304** or received as a value in a communication packet on a network or port interface from an existing subsystem of the vehicle **104**. The ignition sensor signal can be configured as a digital input, wherein a HIGH value represents that the ignition is on and a LOW value represents that the ignition is OFF. Three bits of the port interface can be configured as a digital input to receive the gear shift position signal, representing eight possible gear shift positions. Alternatively, the gear shift position signal can be received in a communication packet as a numeric value on the port interface. The throttle position signal can be received as an analog input value, typically in the range 0-5 volts. Alternatively, the throttle position signal can be received in a communication packet as a numeric value on the port interface. The output of other sensors can be processed in a similar fashion.

Other sensors may be included and positioned in the interior space **108** of the vehicle **104**. Generally, these interior sensors obtain data about the health of the driver and/or passenger(s), data about the safety of the driver and/or passenger(s), and/or data about the comfort of the driver and/or passenger(s). The health data sensors can include sensors in the steering wheel that can measure various health telemetry for the person (e.g., heart rate, temperature, blood pressure, blood presence, blood composition, etc.). Sensors in the seats may also provide for health telemetry (e.g., presence of liquid, weight, weight shifts, etc.). Infrared sensors could detect a person's temperature; optical sensors can determine a person's position and whether the person has become unconscious. Other health sensors are possible and included herein.

Safety sensors can measure whether the person is acting safely. Optical sensors can determine a person's position and focus. If the person stops looking at the road ahead, the optical sensor can detect the lack of focus. Sensors in the seats may detect if a person is leaning forward or may be injured by a seat belt in a collision. Other sensors can detect that the driver has at least one hand on a steering wheel. Other safety sensors are possible and contemplated as if included herein.

Comfort sensors can collect information about a person's comfort. Temperature sensors may detect a temperature of the

interior cabin. Moisture sensors can determine a relative humidity. Audio sensors can detect loud sounds or other distractions. Audio sensors may also receive input from a person through voice data. Other comfort sensors are possible and contemplated as if included herein.

FIG. **6**B shows an interior sensor configuration for one or more zones **512** of a vehicle **104** optionally. Optionally, the areas **508** and/or zones **512** of a vehicle **104** may include sensors that are configured to collect information associated with the interior **108** of a vehicle **104**. In particular, the various sensors may collect environmental information, user information, and safety information, to name a few. Embodiments of these sensors may be as described in conjunction with FIGS. **7**A-**8**B.

Optionally, the sensors may include one or more of optical, or image, sensors **622**A-B (e.g., cameras, etc.), motion sensors **624**A-B (e.g., utilizing RF, IR, and/or other sound/image sensing, etc.), steering wheel user sensors **642** (e.g., heart rate, temperature, blood pressure, sweat, health, etc.), seat sensors **677** (e.g., weight, load cell, moisture, electrical, force transducer, etc.), safety restraint sensors **679** (e.g., seatbelt, airbag, load cell, force transducer, etc.), interior sound receivers **692**A-B, environmental sensors **694** (e.g., temperature, humidity, air, oxygen, etc.), and the like.

The image sensors **622**A-B may be used alone or in combination to identify objects, users **216**, and/or other features, inside the vehicle **104**. Optionally, a first image sensor **622**A may be located in a different position within a vehicle **104** from a second image sensor **622**B. When used in combination, the image sensors **622**A-B may combine captured images to form, among other things, stereo and/or three-dimensional (3D) images. The stereo images can be recorded and/or used to determine depth associated with objects and/or users **216** in a vehicle **104**. Optionally, the image sensors **622**A-B used in combination may determine the complex geometry associated with identifying characteristics of a user **216**. For instance, the image sensors **622**A-B may be used to determine dimensions between various features of a user's face (e.g., the depth/distance from a user's nose to a user's cheeks, a linear distance between the center of a user's eyes, and more). These dimensions may be used to verify, record, and even modify characteristics that serve to identify a user **216**. As can be appreciated, utilizing stereo images can allow for a user **216** to provide complex gestures in a 3D space of the vehicle **104**. These gestures may be interpreted via one or more of the subsystems as disclosed herein. Optionally, the image sensors **622**A-B may be used to determine movement associated with objects and/or users **216** within the vehicle **104**. It should be appreciated that the number of image sensors used in a vehicle **104** may be increased to provide greater dimensional accuracy and/or views of a detected image in the vehicle **104**.

The vehicle **104** may include one or more motion sensors **624**A-B. These motion sensors **624**A-B may detect motion and/or movement of objects inside the vehicle **104**. Optionally, the motion sensors **624**A-B may be used alone or in combination to detect movement. For example, a user **216** may be operating a vehicle **104** (e.g., while driving, etc.) when a passenger in the rear of the vehicle **104** unbuckles a safety belt and proceeds to move about the vehicle **104**. In this example, the movement of the passenger could be detected by the motion sensors **624**A-B. Optionally, the user **216** could be alerted of this movement by one or more of the devices **212**, **248** in the vehicle **104**. In another example, a passenger may attempt to reach for one of the vehicle control features (e.g., the steering wheel **640**, the console, icons displayed on the head unit and/or device **212**, **248**, etc.). In this case, the movement (i.e., reaching) of the passenger may be detected by the motion sensors **624**A-B. Optionally, the path, trajectory, anticipated path, and/or some other direction of movement/motion may be determined using the motion sensors **624**A-B. In response to detecting the movement and/or the direction associated with the movement, the passenger may be prevented from interfacing with and/or accessing at least some of the vehicle control features (e.g., the features represented by icons may be hidden from a user interface, the features may be locked from use by the passenger, combinations thereof, etc.). As can be appreciated, the user **216** may be alerted of the movement/motion such that the user **216** can act to prevent the passenger from interfering with the vehicle **104** controls. Optionally, the number of motion sensors in a vehicle **104**, or areas of a vehicle **104**, may be increased to increase an accuracy associated with motion detected in the vehicle **104**.

The interior sound receivers **692**A-B may include, but are not limited to, microphones and other types of acoustic-to-electric transducers or sensors. Optionally, the interior sound receivers **692**A-B may be configured to receive and convert sound waves into an equivalent analog or digital signal. The interior sound receivers **692**A-B may serve to determine one or more locations associated with various sounds in the vehicle **104**. The location of the sounds may be determined based on a comparison of volume levels, intensity, and the like, between sounds detected by two or more interior sound receivers **692**A-B. For instance, a first interior sound receiver **692**A may be located in a first area of the vehicle **104** and a second interior sound receiver **692**B may be located in a second area of the vehicle **104**. If a sound is detected at a first volume level by the first interior sound receiver **692**A and a second, higher, volume level by the second interior sound receiver **692**B in the second area of the vehicle **104**, the sound may be determined to be closer to the second area of the vehicle **104**. As can be appreciated, the number of sound receivers used in a vehicle **104** may be increased (e.g., more than two, etc.) to increase measurement accuracy surrounding sound detection and location, or source, of the sound (e.g., via triangulation, etc.).

Seat sensors **677** may be included in the vehicle **104**. The seat sensors **677** may be associated with each seat and/or zone **512** in the vehicle **104**. Optionally, the seat sensors **677** may provide health telemetry and/or identification via one or more of load cells, force transducers, weight sensors, moisture detection sensor, electrical conductivity/resistance sensor, and the like. For example, the seat sensors **677** may determine that a user **216** weighs 180 lbs. This value may be compared to user data stored in memory to determine whether a match exists between the detected weight and a user **216** associated with the vehicle **104**. In another example, if the seat sensors **677** detect that a user **216** is fidgeting, or moving, in a seemingly uncontrollable manner, the system may determine that the user **216** has suffered a nervous and/or muscular system issue (e.g., seizure, etc.). The vehicle control system **204** may then cause the vehicle **104** to slow down and in addition or alternatively the automobile controller **8104** (described below) can safely take control of the vehicle **104** and bring the vehicle **104** to a stop in a safe location (e.g., out of traffic, off a freeway, etc).

Health telemetry and other data may be collected via the steering wheel user sensors **642**. Optionally, the steering wheel user sensors **642** may collect heart rate, temperature, blood pressure, and the like, associated with a user **216** via at least one contact disposed on or about the steering wheel **640**.

The safety restraint sensors **679** may be employed to determine a state associated with one or more safety restraint

devices in a vehicle **104**. The state associated with one or more safety restraint devices may serve to indicate a force observed at the safety restraint device, a state of activity (e.g., retracted, extended, various ranges of extension and/or retraction, deployment, buckled, unbuckled, etc.), damage to the safety restraint device, and more.

Environmental sensors **694**, including one or more of temperature, humidity, air, oxygen, carbon monoxide, smoke, and other environmental condition sensors may be used in a vehicle **104**. These environmental sensors **694** may be used to collect data relating to the safety, comfort, and/or condition of the interior space **108** of the vehicle **104**. Among other things, the data collected by the environmental sensors **694** may be used by the vehicle control system **204** to alter functions of a vehicle. The environment may correspond to an interior space **108** of a vehicle **104** and/or specific areas **508** and/or zones **512** of the vehicle **104**. It should be appreciate that an environment may correspond to a user **216**. For example, a low oxygen environment may be detected by the environmental sensors **694** and associated with a user **216** who is operating the vehicle **104** in a particular zone **512**. In response to detecting the low oxygen environment, at least one of the subsystems of the vehicle **104**, as provided herein, may alter the environment, especially in the particular zone **512**, to increase the amount of oxygen in the zone **512**. Additionally or alternatively, the environmental sensors **694** may be used to report conditions associated with a vehicle (e.g., fire detected, low oxygen, low humidity, high carbon monoxide, etc.). The conditions may be reported to a user **216** and/or a third party via at least one communications module as provided herein.

Among other things, the sensors as disclosed herein may communicate with each other, with devices **212**, **248**, and/or with the vehicle control system **204** via the signal carrier network **224**. Additionally or alternatively, the sensors disclosed herein may serve to provide data relevant to more than one category of sensor information including, but not limited to, combinations of environmental information, user information, and safety information to name a few.

FIGS. **7**A-**7**B show block diagrams of various sensors that may be associated with a vehicle **104**. Although depicted as interior and exterior sensors, it should be appreciated that any of the one or more of the sensors shown may be used in both the interior space **108** and the exterior space of the vehicle **104**. Moreover, sensors having the same symbol or name may include the same, or substantially the same, functionality as those sensors described elsewhere in the present disclosure. Further, although the various sensors are depicted in conjunction with specific groups (e.g., environmental **708**, **708**E, user interface **712**, safety **716**, **716**E, etc.) the sensors should not be limited to the groups in which they appear. In other words, the sensors may be associated with other groups or combinations of groups and/or disassociated from one or more of the groups shown. The sensors as disclosed herein may communicate with each other, the devices **212**, **248**, and/or the vehicle control system **204** via one or more communications channel(s) **356**.

FIG. **7**A is a block diagram of an embodiment of interior sensors **340** for a vehicle **104** is provided. The interior sensors **340** may be arranged into one or more groups, based at least partially on the function of the interior sensors **340**. The interior space **108** of a vehicle **104** may include an environmental group **708**, a user interface group **712**, and a safety group **716**. Additionally or alternatively, there may be sensors associated with various devices inside the vehicle (e.g., devices **212**, **248**, smart phones, tablets, mobile computers, etc.)

The environmental group **708** may comprise sensors configured to collect data relating to the internal environment of a vehicle **104**. It is anticipated that the environment of the vehicle **104** may be subdivided into areas **508** and zones **512** in an interior space **108** of a vehicle **104**. In this case, each area **508** and/or zone **512** may include one or more of the environmental sensors. Examples of environmental sensors associated with the environmental group **708** may include, but are not limited to, oxygen/air sensors **724**, temperature sensors **728**, humidity sensors **732**, light/photo sensors **736**, and more. The oxygen/air sensors **724** may be configured to detect a quality of the air in the interior space **108** of the vehicle **104** (e.g., ratios and/or types of gasses comprising the air inside the vehicle **104**, dangerous gas levels, safe gas levels, etc.). Temperature sensors **728** may be configured to detect temperature readings of one or more objects, users **216**, and/or areas **508** of a vehicle **104**. Humidity sensors **732** may detect an amount of water vapor present in the air inside the vehicle **104**. The light/photo sensors **736** can detect an amount of light present in the vehicle **104**. Further, the light/photo sensors **736** may be configured to detect various levels of light intensity associated with light in the vehicle **104**.

The user interface group **712** may comprise sensors configured to collect data relating to one or more users **216** in a vehicle **104**. As can be appreciated, the user interface group **712** may include sensors that are configured to collect data from users **216** in one or more areas **508** and zones **512** of the vehicle **104**. For example, each area **508** and/or zone **512** of the vehicle **104** may include one or more of the sensors in the user interface group **712**. Examples of user interface sensors associated with the user interface group **712** may include, but are not limited to, infrared sensors **740**, motion sensors **744**, weight sensors **748**, wireless network sensors **752**, biometric sensors **756**, camera (or image) sensors **760**, audio sensors **764**, and more.

Infrared sensors **740** may be used to measure IR light irradiating from at least one surface, user **216**, or other object in the vehicle **104**. Among other things, the Infrared sensors **740** may be used to measure temperatures, form images (especially in low light conditions), identify users **216**, and even detect motion in the vehicle **104**.

The motion sensors **744** may be similar to the motion detectors **624**A-B, as described in conjunction with FIG. **6**B. Weight sensors **748** may be employed to collect data relating to objects and/or users **216** in various areas **508** of the vehicle **104**. In some cases, the weight sensors **748** may be included in the seats and/or floor of a vehicle **104**.

Optionally, the vehicle **104** may include a wireless network sensor **752**. This sensor **752** may be configured to detect one or more wireless network(s) inside the vehicle **104**. Examples of wireless networks may include, but are not limited to, wireless communications utilizing Bluetooth®, Wi-Fi™, ZigBee, IEEE 802.11, and other wireless technology standards. For example, a mobile hotspot may be detected inside the vehicle **104** via the wireless network sensor **752**. In this case, the vehicle **104** may determine to utilize and/or share the mobile hotspot detected via/with one or more other devices **212**, **248** and/or components associated with the vehicle **104**.

Biometric sensors **756** may be employed to identify and/or record characteristics associated with a user **216**. It is anticipated that biometric sensors **756** can include at least one of image sensors, IR sensors, fingerprint readers, weight sensors, load cells, force transducers, heart rate monitors, blood pressure monitors, and the like as provided herein.

The camera sensors **760** may be similar to image sensors **622**A-B, as described in conjunction with FIG. **6**B. Optionally, the camera sensors may record still images, video, and/or

combinations thereof. The audio sensors **764** may be similar to the interior sound receivers **692**A-B, as described in conjunction with FIGS. **6**A-**6**B. The audio sensors may be configured to receive audio input from a user **216** of the vehicle **104**. The audio input from a user **216** may correspond to voice commands, conversations detected in the vehicle **104**, phone calls made in the vehicle **104**, and/or other audible expressions made in the vehicle **104**.

The safety group **716** may comprise sensors configured to collect data relating to the safety of a user **216** and/or one or more components of a vehicle **104**. The vehicle **104** may be subdivided into areas **508** and/or zones **512** in an interior space **108** of a vehicle **104** where each area **508** and/or zone **512** may include one or more of the safety sensors provided herein. Examples of safety sensors associated with the safety group **716** may include, but are not limited to, force sensors **768**, mechanical motion sensors **772**, orientation sensors **776**, restraint sensors **780**, and more.

The force sensors **768** may include one or more sensors inside the vehicle **104** configured to detect a force observed in the vehicle **104**. One example of a force sensor **768** may include a force transducer that converts measured forces (e.g., force, weight, pressure, etc.) into output signals.

Mechanical motion sensors **772** may correspond to encoders, accelerometers, damped masses, and the like. Optionally, the mechanical motion sensors **772** may be adapted to measure the force of gravity (i.e., G-force) as observed inside the vehicle **104**. Measuring the G-force observed inside a vehicle **104** can provide valuable information related to a vehicle's acceleration, deceleration, collisions, and/or forces that may have been suffered by one or more users **216** in the vehicle **104**. As can be appreciated, the mechanical motion sensors **772** can be located in an interior space **108** or an exterior of the vehicle **104**.

Orientation sensors **776** can include accelerometers, gyroscopes, magnetic sensors, and the like that are configured to detect an orientation associated with the vehicle **104**. Similar to the mechanical motion sensors **772**, the orientation sensors **776** can be located in an interior space **108** or an exterior of the vehicle **104**.

The restraint sensors **780** may be similar to the safety restraint sensors **679** as described in conjunction with FIGS. **6**A-**6**B. These sensors **780** may correspond to sensors associated with one or more restraint devices and/or systems in a vehicle **104**. Seatbelts and airbags are examples of restraint devices and/or systems. As can be appreciated, the restraint devices and/or systems may be associated with one or more sensors that are configured to detect a state of the device/system. The state may include extension, engagement, retraction, disengagement, deployment, and/or other electrical or mechanical conditions associated with the device/system.

The associated device sensors **720** can include any sensors that are associated with a device **212**, **248** in the vehicle **104**. As previously stated, typical devices **212**, **248** may include smart phones, tablets, laptops, mobile computers, and the like. It is anticipated that the various sensors associated with these devices **212**, **248** can be employed by the vehicle control system **204**. For example, a typical smart phone can include, an image sensor, an IR sensor, audio sensor, gyroscope, accelerometer, wireless network sensor, fingerprint reader, and more. It is an aspect of the present disclosure that one or more of these associated device sensors **720** may be used by one or more subsystems of the vehicle system **200**.

In FIG. **7**B, a block diagram of an embodiment of exterior sensors **340** for a vehicle **104** is shown. The exterior sensors may include sensors that are identical, or substantially similar, to those previously disclosed in conjunction with the interior sensors of FIG. **7**A. Optionally, the exterior sensors **340** may be configured to collect data relating to one or more conditions, objects, users **216**, and other events that are external to the interior space **108** of the vehicle **104**. For instance, the oxygen/air sensors **724** may measure a quality and/or composition of the air outside of a vehicle **104**. As another example, the motion sensors **744** may detect motion outside of a vehicle **104**.

The external environmental group **708**E may comprise sensors configured to collect data relating to the external environment of a vehicle **104**. In addition to including one or more of the sensors previously described, the external environmental group **708**E may include additional sensors, such as, vehicle sensors **750**, biological sensors, and wireless signal sensors **758**. Vehicle sensors **750** can detect vehicles that are in an environment surrounding the vehicle **104**. For example, the vehicle sensors **750** may detect vehicles in a first outside area **516**, a second outside area **520**, and/or combinations of the first and second outside areas **516**, **520**. Optionally, the vehicle sensors **750** may include one or more of RF sensors, IR sensors, image sensors, and the like to detect vehicles, people, hazards, etc. that are in an environment exterior to the vehicle **104**. Additionally or alternatively, the vehicle sensors **750** can provide distance/directional information relating to a distance (e.g., distance from the vehicle **104** to the detected object) and/or a direction (e.g., direction of travel, etc.) associated with the detected object.

The biological sensors **754** may determine whether one or more biological entities (e.g., an animal, a person, a user **216**, etc.) is in an external environment of the vehicle **104**. Additionally or alternatively, the biological sensors **754** may provide distance information relating to a distance of the biological entity from the vehicle **104**. Biological sensors **754** may include at least one of RF sensors, IR sensors, image sensors and the like that are configured to detect biological entities. For example, an IR sensor may be used to determine that an object, or biological entity, has a specific temperature, temperature pattern, or heat signature. Continuing this example, a comparison of the determined heat signature may be compared to known heat signatures associated with recognized biological entities (e.g., based on shape, locations of temperature, and combinations thereof, etc.) to determine whether the heat signature is associated with a biological entity or an inanimate, or non-biological, object.

The wireless signal sensors **758** may include one or more sensors configured to receive wireless signals from signal sources such as Wi-Fi™ hotspots, cell towers, roadside beacons, other electronic roadside devices, and satellite positioning systems. Optionally, the wireless signal sensors **758** may detect wireless signals from one or more of a mobile phone, mobile computer, keyless entry device, RFID device, near field communications (NFC) device, and the like.

The external safety group **716**E may comprise sensors configured to collect data relating to the safety of a user **216** and/or one or more components of a vehicle **104**. Examples of safety sensors associated with the external safety group **716**E may include, but are not limited to, force sensors **768**, mechanical motion sensors **772**, orientation sensors **776**, vehicle body sensors **782**, and more. Optionally, the exterior safety sensors **716**E may be configured to collect data relating to one or more conditions, objects, vehicle components, and other events that are external to the vehicle **104**. For instance, the force sensors **768** in the external safety group **716**E may detect and/or record force information associated with the outside of a vehicle **104**. For instance, if an object strikes the exterior of the vehicle **104**, the force sensors **768** from the

exterior safety group **716**E may determine a magnitude, location, and/or time associated with the strike.

The vehicle **104** may include a number of vehicle body sensors **782**. The vehicle body sensors **782** may be configured to measure characteristics associated with the body (e.g., body panels, components, chassis, windows, etc.) of a vehicle **104**. For example, two vehicle body sensors **782**, including a first body sensor and a second body sensor, may be located at some distance apart. Continuing this example, the first body sensor may be configured to send an electrical signal across the body of the vehicle **104** to the second body sensor, or vice versa. Upon receiving the electrical signal from the first body sensor, the second body sensor may record a detected current, voltage, resistance, and/or combinations thereof associated with the received electrical signal. Values (e.g., current, voltage, resistance, etc.) for the sent and received electrical signal may be stored in a memory. These values can be compared to determine whether subsequent electrical signals sent and received between vehicle body sensors **782** deviate from the stored values. When the subsequent signal values deviate from the stored values, the difference may serve to indicate damage and/or loss of a body component. Additionally or alternatively, the deviation may indicate a problem with the vehicle body sensors **782**. The vehicle body sensors **782** may communicate with each other, a vehicle control system **204**, and/or systems of the vehicle system **200** via a communications channel **356**. Although described using electrical signals, it should be appreciated that alternative embodiments of the vehicle body sensors **782** may use sound waves and/or light to perform a similar function.

FIG. **8**A is a block diagram of an embodiment of a media controller subsystem **348** for a vehicle **104**. The media controller subsystem **348** may include, but is not limited to, a media controller **804**, a media processor **808**, a match engine **812**, an audio processor **816**, a speech synthesis module **820**, a network transceiver **824**, a signal processing module **828**, memory **832**, and a language database **836**. Optionally, the media controller subsystem **348** may be configured as a dedicated blade that implements the media-related functionality of the system **200**. Additionally or alternatively, the media controller subsystem **348** can provide voice input, voice output, library functions for multimedia, and display control for various areas **508** and/or zones **512** of the vehicle **104**.

Optionally, the media controller subsystem **348** may include a local IP address (e.g., IPv4, IPv6, combinations thereof, etc.) and even a routable, global unicast address. The routable, global unicast address may allow for direct addressing of the media controller subsystem **348** for streaming data from Internet resources (e.g., cloud storage, user accounts, etc.). It is anticipated, that the media controller subsystem **348** can provide multimedia via at least one Internet connection, or wireless network communications module, associated with the vehicle **104**. Moreover, the media controller subsystem **348** may be configured to service multiple independent clients simultaneously.

The media processor **808** may comprise a general purpose programmable processor or controller for executing application programming or instructions related to the media subsystem **348**. The media processor **808** may include multiple processor cores, and/or implement multiple virtual processors. Optionally, the media processor **808** may include multiple physical processors. By way of example, the media processor **808** may comprise a specially configured application specific integrated circuit (ASIC) or other integrated circuit, a digital signal processor, a controller, a hardwired electronic or logic circuit, a programmable logic device or gate array, a special purpose computer, or the like. The media processor **808** generally functions to run programming code or instructions implementing various functions of the media controller **804**.

The match engine **812** can receive input from one or more components of the vehicle system **800** and perform matching functions. Optionally, the match engine **812** may receive audio input provided via a microphone **886** of the system **800**. The audio input may be provided to the media controller subsystem **348** where the audio input can be decoded and matched, via the match engine **812**, to one or more functions available to the vehicle **104**. Similar matching operations may be performed by the match engine **812** relating to video input received via one or more image sensors, cameras **878**, and the like.

The media controller subsystem **348** may include a speech synthesis module **820** configured to provide audio output to one or more speakers **880**, or audio output devices, associated with the vehicle **104**. Optionally, the speech synthesis module **820** may be configured to provide audio output based at least partially on the matching functions performed by the match engine **812**.

As can be appreciated, the coding/decoding, the analysis of audio input/output, and/or other operations associated with the match engine **812** and speech synthesis module **820**, may be performed by the media processor **808** and/or a dedicated audio processor **816**. The audio processor **816** may comprise a general purpose programmable processor or controller for executing application programming or instructions related to audio processing. Further, the audio processor **816** may be similar to the media processor **808** described herein.

The network transceiver **824** can include any device configured to transmit and receive analog and/or digital signals. Optionally, the media controller subsystem **348** may utilize a network transceiver **824** in one or more communication networks associated with the vehicle **104** to receive and transmit signals via the communications channel **356**. Additionally or alternatively, the network transceiver **824** may accept requests from one or more devices **212**, **248** to access the media controller subsystem **348**. One example of the communication network is a local-area network (LAN). As can be appreciated, the functionality associated with the network transceiver **824** may be built into at least one other component of the vehicle **104** (e.g., a network interface card, communications module, etc.).

The signal processing module **828** may be configured to alter audio/multimedia signals received from one or more input sources (e.g., microphones **886**, etc.) via the communications channel **356**. Among other things, the signal processing module **828** may alter the signals received electrically, mathematically, combinations thereof, and the like.

The media controller **804** may also include memory **832** for use in connection with the execution of application programming or instructions by the media processor **808**, and for the temporary or long term storage of program instructions and/or data. As examples, the memory **832** may comprise RAM, DRAM, SDRAM, or other solid state memory.

The language database **836** may include the data and/or libraries for one or more languages, as are used to provide the language functionality as provided herein. In one case, the language database **836** may be loaded on the media controller **804** at the point of manufacture. Optionally, the language database **836** can be modified, updated, and/or otherwise changed to alter the data stored therein. For instance, additional languages may be supported by adding the language data to the language database **836**. In some cases, this addition of languages can be performed via accessing administrative functions on the media controller **804** and loading the new

language modules via wired (e.g., USB, etc.) or wireless communication. In some cases, the administrative functions may be available via a vehicle console device **248**, a user device **212**, **248**, and/or other mobile computing device that is authorized to access administrative functions (e.g., based at least partially on the device's address, identification, etc.).

One or more video controllers **840** may be provided for controlling the video operation of the devices **212**, **248**, **882** associated with the vehicle. Optionally, the video controller **840** may include a display controller for controlling the operation of touch sensitive screens, including input (touch sensing) and output (display) functions. Video data may include data received in a stream and unpacked by a processor and loaded into a display buffer. In this example, the processor and video controller **840** can optimize the display based on the characteristics of a screen of a display device **212**, **248**, **882**. The functions of a touch screen controller may be incorporated into other components, such as a media processor **808** or display subsystem.

The audio controller **844** can provide control of the audio entertainment system (e.g., radio, subscription music service, multimedia entertainment, etc.), and other audio associated with the vehicle **104** (e.g., navigation systems, vehicle comfort systems, convenience systems, etc.). Optionally, the audio controller **844** may be configured to translate digital signals to analog signals and vice versa. As can be appreciated, the audio controller **844** may include device drivers that allow the audio controller **844** to communicate with other components of the system **800** (e.g., processors **816**, **808**, audio I/O **874**, and the like).

The system **800** may include a profile identification module **848** to determine whether a user profile is associated with the vehicle **104**. Among other things, the profile identification module **848** may receive requests from a user **216**, or device **212**, **228**, **248**, to access a profile stored in a profile database **856** or profile data **252**. Additionally or alternatively, the profile identification module **848** may request profile information from a user **216** and/or a device **212**, **228**, **248**, to access a profile stored in a profile database **856** or profile data **252**. In any event, the profile identification module **848** may be configured to create, modify, retrieve, and/or store user profiles in the profile database **856** and/or profile data **252**. The profile identification module **848** may include rules for profile identification, profile information retrieval, creation, modification, and/or control of components in the system **800**.

By way of example, a user **216** may enter the vehicle **104** with a smart phone or other device **212**. In response to determining that a user **216** is inside the vehicle **104**, the profile identification module **848** may determine that a user profile is associated with the user's smart phone **212**. As another example, the system **800** may receive information about a user **216** (e.g., from a camera **878**, microphone **886**, etc.), and, in response to receiving the user information, the profile identification module **848** may refer to the profile database **856** to determine whether the user information matches a user profile stored in the database **856**. It is anticipated that the profile identification module **848** may communicate with the other components of the system to load one or more preferences, settings, and/or conditions based on the user profile. Further, the profile identification module **848** may be configured to control components of the system **800** based on user profile information.

Optionally, data storage **852** may be provided. Like the memory **832**, the data storage **852** may comprise a solid state memory device or devices. Alternatively or in addition, the data storage **852** may comprise a hard disk drive or other random access memory. Similar to the data storage **852**, the profile database **856** may comprise a solid state memory device or devices.

An input/output module **860** and associated ports may be included to support communications over wired networks or links, for example with other communication devices, server devices, and/or peripheral devices. Examples of an input/output module **860** include an Ethernet port, a Universal Serial Bus (USB) port, CAN Bus, Institute of Electrical and Electronics Engineers (IEEE) 1594, or other interface. Users may bring their own devices (e.g., Bring Your Own Device (BYOD), device **212**, etc.) into the vehicle **104** for use with the various systems disclosed. Although most BYOD devices can connect to the vehicle systems (e.g., the media controller subsystem **348**, etc.) via wireless communications protocols (e.g., Wi-Fi™, Bluetooth®, etc.) many devices may require a direct connection via USB, or similar. In any event, the input/output module **860** can provide the necessary connection of one or more devices to the vehicle systems described herein.

A video input/output interface **864** can be included to receive and transmit video signals between the various components in the system **800**. Optionally, the video input/output interface **864** can operate with compressed and uncompressed video signals. The video input/output interface **864** can support high data rates associated with image capture devices. Additionally or alternatively, the video input/output interface **864** may convert analog video signals to digital signals.

The infotainment system **870** may include information media content and/or entertainment content, informational devices, entertainment devices, and the associated programming therefor. Optionally, the infotainment system **870** may be configured to handle the control of one or more components of the system **800** including, but in no way limited to, radio, streaming audio/video devices, audio devices **880**, **882**, **886**, video devices **878**, **882**, travel devices (e.g., GPS, navigational systems, etc.), wireless communication devices, network devices, and the like. Further, the infotainment system **870** can provide the functionality associated with other infotainment features as provided herein.

An audio input/output interface **874** can be included to provide analog audio to an interconnected speaker **880** or other device, and to receive analog audio input from a connected microphone **886** or other device. As an example, the audio input/output interface **874** may comprise an associated amplifier and analog to digital converter. Alternatively or in addition, the devices **212**, **248** can include integrated audio input/output devices **880**, **886** and/or an audio jack for interconnecting an external speaker **880** or microphone **886**. For example, an integrated speaker **880** and an integrated microphone **886** can be provided, to support near talk, voice commands, spoken information exchange, and/or speaker phone operations.

Among other things, the system **800** may include devices that are part of the vehicle **104** and/or part of a device **212**, **248** that is associated with the vehicle **104**. For instance, these devices may be configured to capture images, display images, capture sound, and present sound. Optionally, the system **800** may include at least one of image sensors/cameras **878**, display devices **882**, audio input devices/microphones **886**, and audio output devices/speakers **880**. The cameras **878** can be included for capturing still and/or video images. Alternatively or in addition, image sensors **878** can include a scanner or code reader. An image sensor/camera **878** can include or be associated with additional elements, such as a flash or other light source. In some cases, the display device **882** may include an audio input device and/or an audio output device in

addition to providing video functions. For instance, the display device **882** may be a console, monitor, a tablet computing device, and/or some other mobile computing device.

FIG. **8**B is a block diagram of an embodiment of a user/device interaction subsystem **817** in a vehicle system **800**. The user/device interaction subsystem **817** may comprise hardware and/or software that conduct various operations for or with the vehicle **104**. For instance, the user/device interaction subsystem **817** may include at least one user interaction subsystem **332** and device interaction subsystem **352** as previously described. These operations may include, but are not limited to, providing information to the user **216**, receiving input from the user **216**, and controlling the functions or operation of the vehicle **104**, etc. Among other things, the user/device interaction subsystem **817** may include a computing system operable to conduct the operations as described herein.

Optionally, the user/device interaction subsystem **817** can include one or more of the components and modules provided herein. For instance, the user/device interaction subsystem **817** can include one or more of a video input/output interface **864**, an audio input/output interface **874**, a sensor module **814**, a device interaction module **818**, a user identification module **822**, a vehicle control module **826**, an environmental control module **830**, and a gesture control module **834**. The user/device interaction subsystem **817** may be in communication with other devices, modules, and components of the system **800** via the communications channel **356**.

The user/device interaction subsystem **817** may be configured to receive input from a user **216** and/or device via one or more components of the system. By way of example, a user **216** may provide input to the user/device interaction subsystem **817** via wearable devices **802**, **806**, **810**, video input (e.g., via at least one image sensor/camera **878**, etc.) audio input (e.g., via the microphone, audio input source, etc.), gestures (e.g., via at least one image sensor **878**, motion sensor **888**, etc.), device input (e.g., via a device **212**, **248** associated with the user, etc.), combinations thereof, and the like.

The wearable devices **802**, **806**, **810** can include heart rate monitors, blood pressure monitors, glucose monitors, pedometers, movement sensors, wearable computers, and the like. Examples of wearable computers may be worn by a user **216** and configured to measure user activity, determine energy spent based on the measured activity, track user sleep habits, determine user oxygen levels, monitor heart rate, provide alarm functions, and more. It is anticipated that the wearable devices **802**, **806**, **810** can communicate with the user/device interaction subsystem **817** via wireless communications channels or direct connection (e.g., where the device docks, or connects, with a USB port or similar interface of the vehicle **104**).

A sensor module **814** may be configured to receive and/or interpret input provided by one or more sensors in the vehicle **104**. In some cases, the sensors may be associated with one or more user devices (e.g., wearable devices **802**, **806**, **810**, smart phones **212**, mobile computing devices **212**, **248**, and the like). Optionally, the sensors may be associated with the vehicle **104**, as described in conjunction with FIGS. **6**A-**7**B.

The device interaction module **818** may communicate with the various devices as provided herein. Optionally, the device interaction module **818** can provide content, information, data, and/or media associated with the various subsystems of the vehicle system **800** to one or more devices **212**, **248**, **802**, **806**, **810**, **882**, etc. Additionally or alternatively, the device interaction module **818** may receive content, information, data, and/or media associated with the various devices provided herein.

The user identification module **822** may be configured to identify a user **216** associated with the vehicle **104**. The identification may be based on user profile information that is stored in profile data **252**. For instance, the user identification module **822** may receive characteristic information about a user **216** via a device, a camera, and/or some other input. The received characteristics may be compared to data stored in the profile data **252**. Where the characteristics match, the user **216** is identified. As can be appreciated, where the characteristics do not match a user profile, the user identification module **822** may communicate with other subsystems in the vehicle **104** to obtain and/or record profile information about the user **216**. This information may be stored in a memory and/or the profile data storage **252**.

The vehicle control module **826** may be configured to control settings, features, and/or the functionality of a vehicle **104**. In some cases, the vehicle control module **826** can communicate with the vehicle control system **204** to control critical functions (e.g., driving system controls, braking, accelerating, etc.) and/or noncritical functions (e.g., driving signals, indicator/hazard lights, mirror controls, window actuation, etc.) based at least partially on user/device input received by the user/device interaction subsystem **817**.

The environmental control module **830** may be configured to control settings, features, and/or other conditions associated with the environment, especially the interior environment, of a vehicle **104**. Optionally, the environmental control module **830** may communicate with the climate control system (e.g. changing cabin temperatures, fan speeds, air direction, etc.), oxygen and/or air quality control system (e.g., increase/decrease oxygen in the environment, etc.), interior lighting (e.g., changing intensity of lighting, color of lighting, etc.), an occupant seating system **648** (e.g., adjusting seat position, firmness, height, etc.), steering wheel **640** (e.g., position adjustment, etc.), infotainment/entertainment system (e.g., adjust volume levels, display intensity adjustment, change content, etc.), and/or other systems associated with the vehicle environment. Additionally or alternatively, these systems can provide input, set-points, and/or responses, to the environmental control module **830**. As can be appreciated, the environmental control module **830** may control the environment based at least partially on user/device input received by the user/device interaction subsystem **817**.

The gesture control module **834** is configured to interpret gestures provided by a user **216** in the vehicle **104**. Optionally, the gesture control module **834** may provide control signals to one or more of the vehicle systems **300** disclosed herein. For example, a user **216** may provide gestures to control the environment, critical and/or noncritical vehicle functions, the infotainment system, communications, networking, and more. Optionally, gestures may be provided by a user **216** and detected via one or more of the sensors as described in conjunction with FIGS. **6**B-**7**A. As another example, one or more motion sensors **888** may receive gesture input from a user **216** and provide the gesture input to the gesture control module **834**. Continuing this example, the gesture input is interpreted by the gesture control module **834**. This interpretation may include comparing the gesture input to gestures stored in a memory. The gestures stored in memory may include one or more functions and/or controls mapped to specific gestures. When a match is determined between the detected gesture input and the stored gesture

information, the gesture control module **834** can provide a control signal to any of the systems/subsystems as disclosed herein.

FIG. **8**C illustrates a GPS/Navigation subsystem(s) **336**. The Navigation subsystem(s) **336** can be any present or future-built navigation system that may use location data, for example, from the Global Positioning System (GPS), to provide navigation information or control the vehicle **104**. The Navigation subsystem(s) **336** can include several components or modules, such as, one or more of, but not limited to, a GPS Antenna/receiver **892**, a location module **896**, a maps database **8100**, an automobile controller **8104**, a vehicle systems transceiver **8108**, a traffic controller **8112**, a network traffic transceiver **8116**, a vehicle-to-vehicle transceiver **8120**, a traffic information database **8124**, etc. Generally, the several components or modules **892-8124** may be hardware, software, firmware, computer readable media, or combinations thereof

A GPS Antenna/receiver **892** can be any antenna, GPS puck, and/or receiver capable of receiving signals from a GPS satellite or other navigation system, as mentioned hereinbefore. The signals may be demodulated, converted, interpreted, etc. by the GPS Antenna/receiver **892** and provided to the location module **896**. Thus, the GPS Antenna/receiver **892** may convert the time signals from the GPS system and provide a location (e.g., coordinates on a map) to the location module **896**. Alternatively, the location module **896** can interpret the time signals into coordinates or other location information.

The location module **896** can be the controller of the satellite navigation system designed for use in automobiles. The location module **896** can acquire position data, as from the GPS Antenna/receiver **892**, to locate the user or vehicle **104** on a road in the unit's map database **8100**. Using the road database **8100**, the location module **896** can give directions to other locations along roads also in the database **8100**. When a GPS signal is not available, the location module **896** may apply dead reckoning to estimate distance data from sensors **242** including one or more of, but not limited to, a speed sensor attached to the drive train of the vehicle **104**, a gyroscope, an accelerometer, etc. GPS signal loss and/or multipath can occur due to urban canyons, tunnels, and other obstructions. Additionally or alternatively, the location module **896** may use known locations of Wi-Fi hotspots, cell tower data, etc. to determine the position of the vehicle **104**, such as by using time difference of arrival (TDOA) and/or frequency difference of arrival (FDOA) techniques.

The maps database **8100** can include any hardware and/or software to store information about maps, geographical information system information, location information, etc. The maps database **8100** can include any data definition or other structure to store the information. Generally, the maps database **8100** can include a road database that may include one or more vector maps of areas of interest. Street names, street numbers, house numbers, and other information can be encoded as geographic coordinates so that the user can find some desired destination by street address. Points of interest (waypoints) can also be stored with their geographic coordinates. For example, a point of interest may include speed cameras, fuel stations, public parking, and "parked here" (or "you parked here") information. The map database contents can be produced or updated by a server connected through a wireless system in communication with the Internet, even as the vehicle **104** is driven along existing streets, yielding an up-to-date map.

An automobile controller **8104** can be any hardware and/or software that can receive instructions from the location module **896** or the traffic controller **8112** and operate the vehicle **104**. The automobile controller **8104** receives this information and data from the sensors **242** to operate the vehicle **104** without driver input. Thus, the automobile controller **8104** can drive the vehicle **104** along a route provided by the location module **896**. The route may be adjusted by information sent from the traffic controller **8112**. Discrete and real-time driving can occur with data from the sensors **242**. To operate the vehicle **104**, the automobile controller **8104** can communicate with a vehicle systems transceiver **8108**.

The vehicle systems transceiver **8108** can be any present or future-developed device that can comprise a transmitter and/or a receiver, which may be combined and can share common circuitry or a single housing. The vehicle systems transceiver **8108** may communicate or instruct one or more of the vehicle control subsystems **328**. For example, the vehicle systems transceiver **8108** may send steering commands, as received from the automobile controller **8104**, to an electronic steering system, to adjust the steering of the vehicle **100** in real time. The automobile controller **8104** can determine the effect of the commands based on received sensor data **242** and can adjust the commands as need be. The vehicle systems transceiver **8108** can also communicate with the braking system, the engine and drive train to speed or slow the car, the signals (e.g., turn signals and brake lights), the headlights, the windshield wipers, etc. Any of these communications may occur over the components or function as described in conjunction with FIG. **4**.

A traffic controller **8112** can be any hardware and/or software that can communicate with an automated traffic system and adjust the function of the vehicle **104** based on instructions from the automated traffic system. An automated traffic system is a system that manages the traffic in a given area. This automated traffic system can instruct cars to drive in certain lanes, instruct cars to raise or lower their speed, instruct a car to change their route of travel, instruct cars to communicate with other cars, etc. To perform these functions, the traffic controller **8112** may register the vehicle **104** with the automated traffic system and then provide other information including the route of travel. The automated traffic system can return registration information and any required instructions. The communications between the automated traffic system and the traffic controller **8112** may be received and sent through a network traffic transceiver **8116**.

The network traffic transceiver **8116** can be any present or future-developed device that can comprise a transmitter and/or a receiver, which may be combined and can share common circuitry or a single housing. The network traffic transceiver **8116** may communicate with the automated traffic system using any known or future-developed, protocol, standard, frequency, bandwidth range, etc. The network traffic transceiver **8116** enables the sending of information between the traffic controller **8112** and the automated traffic system.

The traffic controller **8112** can also communicate with another vehicle, which may be in physical proximity (i.e., within range of a wireless signal), using the vehicle-to-vehicle transceiver **8120**. As with the network traffic transceiver **8116**, the vehicle-to-vehicle transceiver **8120** can be any present or future-developed device that can comprise a transmitter and/or a receiver, which may be combined and can share common circuitry or a single housing. Generally, the vehicle-to-vehicle transceiver **8120** enables communication between the vehicle **104** and any other vehicle. These communications allow the vehicle **104** to receive traffic or safety information, control or be controlled by another vehicle, establish an alternative communication path to communicate with the automated traffic system, establish a node including

two or more vehicle that can function as a unit, etc. The vehicle-to-vehicle transceiver **8120** may communicate with the other vehicles using any known or future-developed, protocol standard, frequency, bandwidth range, etc.

The traffic controller **8112** can control functions of the automobile controller **8104** and communicate with the location module **896**. The location module **896** can provide current location information and route information that the traffic controller **8112** may then provide to the automated traffic system. The traffic controller **8112** may receive route adjustments from the automated traffic system that are then sent to the location module **896** to change the route. Further, the traffic controller **8112** can also send driving instructions to the automobile controller **8104** to change the driving characteristics of the vehicle **104**. For example, the traffic controller **8112** can instruct the automobile controller **8104** to accelerate or decelerate to a different speed, change lanes, or perform another driving maneuver. The traffic controller **8112** can also manage vehicle-to-vehicle communications and store information about the communications or other information in the traffic information database **8124**.

The traffic information database **8124** can be any type of database, such as relational, hierarchical, object-oriented, and/or the like. The traffic information database **8124** may reside on a storage medium local to (and/or resident in) the vehicle control system **204** or in the vehicle **104**. The traffic information database **8124** may be adapted to store, update, and retrieve information about communications with other vehicles or any active instructions from the automated traffic system. This information may be used by the traffic controller **8112** to instruct or adjust the performance of driving maneuvers.

FIG. **9** illustrates an optional communications architecture where, the host device **908** may include one more routing profiles, permission modules, and rules that control how communications within the vehicle **104** are to occur. This communications architecture can be used in conjunction with the routing tables, rules and permissions associated with access point **456** and optional firewall **484**, or can be in lieu thereof. For example, the host device **908** acts as a mobile hot spot to one or more other devices within vehicle **104**, such as, other device 1 **912**, other device 2 **916**, other device 3 **920**, and other device N **924**. Optionally, one or more of the other devices **912** can communicate directly with the host device **908** which then provides Internet access to those devices **912** via the device **908**. The host device **908** can act as a mobile hot spot for any one or more of the other devices **912**, which may not need to communicate over the network/communications buses **224**/**404**, but could instead connect directly to the host device **908** via, for example, NFC, Bluetooth®, WiFi, or the like. When the device **908** is acting as the host device, the device **908** can include one or more routing profiles, permissions, rules modules, and can also act as a firewall for the various inter and intra vehicle communications.

As will be appreciated, there could be alternative host devices, such as, host **904** which could also act as, for example, a co-host in association with device **908**. Optionally, one or more of the routing profile, permission information, and rules could be shared between the co-host devices **904**, **908**, both of those devices being usable for Internet access for one or more of the other devices, **912**-**924**. As will be appreciated, the other devices **912**-**924** need not necessarily connect to one or more of host device **908** and the other device **904** via a direct communications link, but could also interface with those devices **904**, **908** utilizing the network/communications buses **224**/**404** associated with the vehicle **100**. As previously discussed, one or more of the other devices can connect to the network/communications buses **224**/**404** utilizing the various networks and/or buses discussed herein which would therefore enable, for example, regulation of the various communications based on the Ethernet zone that the other device **912** is associated with.

An embodiment of one or more modules that may be associated with the vehicle control system **204** may be as shown in FIG. **10**. The modules can include a communication subsystem interface **1008** in communication with an operating system **1004**. The communications may pass through a firewall **1044**. The firewall **1044** can be any software that can control the incoming and outgoing communications by analyzing the data packets and determining whether the packets should be allowed through the firewall, based on applied rule set. A firewall **1044** can establish a "barrier" between a trusted, secure internal network and another network (e.g., the Internet) that is not assumed to be secure and trusted.

In some situations, the firewall **1044** may establish security zones that are implemented by running system services and/or applications in restricted user groups and accounts. A set of configuration files and callbacks may then be linked to an IP table firewall. The IP table firewall can be configured to notify a custom filter application at any of the layers of the Ethernet packet. The different users/group rights to access the system may include: system users, which may have exclusive right over all device firewall rules and running software; a big-brother user, which may have access to on board device (OBD) control data and may be able to communicate with the vehicle subsystem **328** and may be able to alter the parameters in the vehicle control system **204**; a dealer user, which can have rights to read OBD data for diagnostics and repairs; a dashboard user, which can have rights to launch dashboard applications and/or authenticate guest users and change their permissions to trusted/friend/family, and can read but cannot write into OBD diagnostic data; a world wide web (WWW) data user, which can have HTTP rights to respond to HTTP requests (the HTTP requests also can target different user data, but may be filtered by default user accounts); a guest user, which may have no rights; a family/friend user, which may have rights to play media from the media subsystem **348** and/or to stream media to the media subsystem **348**.

The operating system **1004** can be a collection of software that manages computer hardware resources and provides common services for applications and other programs. The operating system **1004** may schedule time-sharing for efficient use of the system. For hardware functions, such as input, output, and memory allocation, the operating system **1004** can act as an intermediary between applications or programs and the computer hardware. Examples of operating systems that may be deployed as operating system **1004** include Android, BSD, iOS, Linux, OS X, QNX, Microsoft Windows, Windows Phone, IBM z/OS, etc.

The operating system **1004** can include one or more submodules. For example, a desktop manager **1012** can manage one or more graphical user interfaces (GUI) in a desktop environment. Desktop GUIs can help the user to easily access and edit files. A command-line interface (CLI) may be used if full control over the operating system (OS) **1004** is required. The desktop manager **1012** is described further hereinafter.

A kernel **1028** can be a computer program that manages input/output requests from software and translates them into data processing instructions for the processor **304** and other components of the vehicle control system **204**. The kernel **1028** is the fundamental component of the operating system **1004** that can execute many of the functions associated with the OS **1004**.

The kernel **1028** can include other software functions, including, but not limited to, driver(s) **1056**, communication software **1052**, and/or Internet Protocol software **1048**. A driver **1056** can be any computer program that operates or controls a particular type of device that is attached to a vehicle control system **204**. A driver **1056** can communicate with the device through the bus **356** or communications subsystem **1008** to which the hardware connects. When a calling program invokes a routine in the driver **1056**, the driver **1056** may issue one or more commands to the device. Once the device sends data back to the driver **1056**, the driver **1056** may invoke routines in the original calling program. Drivers can be hardware-dependent and operating-system-specific. Driver(s) **1056** can provide the interrupt handling required for any necessary asynchronous time-dependent hardware interface.

The IP module **1048** can conduct any IP addressing, which may include the assignment of IP addresses and associated parameters to host interfaces. The address space may include networks and sub-networks. The IP module **1048** can perform the designation of network or routing prefixes and may conduct IP routing, which transports packets across network boundaries. Thus, the IP module **1048** may perform all functions required for IP multicast operations.

The communications module **1052** may conduct all functions for communicating over other systems or using other protocols not serviced by the IP module **1048**. Thus, the communications module **1052** can manage multicast operations over other busses or networks not serviced by the IP module **1048**. Further, the communications module **1052** may perform or manage communications to one or more devices, systems, data stores, services, etc. that are in communication with the vehicle control system **204** or other subsystems through the firewall **1044**. Thus, the communications module **1052** can conduct communications through the communication subsystem interface **1008**.

A file system **1016** may be any data handling software that can control how data is stored and retrieved. The file system **1016** can separate the stored data into individual pieces, and giving each piece a name, can easily separate and identify the pieces of data. Each piece of data may be considered a "file". The file system **1016** can construct data structure and logic rules used to manage the information and the identifiers for the information. The structure and logic rules can be considered a "file system."

A device discovery daemon **1020** may be a computer program that runs as a background process that can discover new devices that connect with the network **356** or communication subsystem **1008** or devices that disconnect from the network **356** or communication subsystem **1008**. The device discovery daemon **1020** can ping the network **356** (the local subnet) when the vehicle **104** starts, when a vehicle door opens or closes, or upon the occurrence of other events. Additionally or alternatively, the device discovery daemon **1020** may force Bluetooth®, USB, and/or wireless detection. For each device that responds to the ping, the device discovery daemon **1020** can populate the system data **208** with device information and capabilities, using any of one or more protocols, including one or more of, but not limited to, IPv6 Hop-by-Hop Option (HOPOPT), Internet Control Message Protocol (ICMP), Internet Group Management Protocol (IGMP), Gateway-to-Gateway Protocol (GGP), Internet Protocol (IP), Internet Stream Protocol (ST), Transmission Control Protocol (TCP), Exterior Gateway Protocol (EGP), CHAOS, User Datagram Protocol (UDP), etc.

For example, the device discovery daemon **1020** can determine device capabilities based on the opened ports the device exposes. If a camera exposes port **80**, then the device discovery daemon **1020** can determine that the camera is using a Hypertext Transfer Protocol (HTTP). Alternatively, if a device is supporting Universal Plug and Play (UPnP), the system data **208** can include more information, for example, a camera control universal resource locator (URL), a camera zoom URL, etc. When a scan stops, the device discovery daemon **1020** can trigger a dashboard refresh to ensure the user interface reflects the new devices on the desktop.

A desktop manager **1012** may be a computer program that manages the user interface of the vehicle control system **204**. The desktop environment may be designed to be customizable and allow the definition of the desktop configuration look-and-feel for a wide range of appliances or devices from computer desktops, mobile devices, computer tablets, etc. Launcher(s), panels, desktop areas, the desktop background, notifications, panes, etc., can be configured from a dashboard configuration file managed by the desktop manager **1012**. The graphical elements in which the desktop manager **1012** controls can include launchers, the desktop, notification bars, etc.

The desktop may be an area of the display where the applications are running. The desktop can have a custom background. Further, the desktop may be divided into two or more areas. For example, the desktop may be divided into an upper half of a display and a lower half of the display. Each application can be configured to run in a portion of the desktop. Extended settings can be added to the desktop configuration file, such that, some objects may be displayed over the whole desktop or in custom size out of the context of the divided areas.

The notification bar may be a part of a bar display system, which may provide notifications by displaying, for example, icons and/or pop-up windows that may be associated with sound notifications. The notification mechanism can be designed for separate plug-ins, which run in separate processes and may subscribe to a system Intelligent Input Bus (IBUS)/D-BUS event service. The icons on the notifications bar can be accompanied with application short-cuts to associated applications, for example, a Bluetooth® manager, a USB manager, radio volume and or tone control, a security firewall, etc.

The desktop manager **1012** may include a windows manager **1032**, an application launcher **1036**, and/or a panel launcher **1040**. Each of these components can control a different aspect of the user interface. The desktop manager **1012** can use a root window to create panels that can include functionality for one or more of, but not limited to: launching applications, managing applications, providing notifications, etc.

The windows manager **1032** may be software that controls the placement and appearance of windows within a graphical user interface presented to the user. Generally, the windows manager **1032** can provide the desktop environment used by the vehicle control system **204**. The windows manager **1032** can communicate with the kernel **1028** to interface with the graphical system that provides the user interface(s) and supports the graphics hardware, pointing devices, keyboard, touch-sensitive screens, etc. The windows manager **1032** may be a tiling window manager (i.e., a window manager with an organization of the screen into mutually non-overlapping frames, as opposed to a coordinate-based stacking of overlapping objects (windows) that attempts to fully emulate the desktop metaphor). The windows manager **1032** may read and store configuration files, in the system data **208**, which can control the position of the application windows at precise positions.

An application manager **1036** can control the function of any application over the lifetime of the process. The process

or application can be launched from a panel launcher **1040** or from a remote console. The application manager **1036** can intercept the process name and may take appropriate action to manage that process. If the process is not running, the application manager **1036** can load the process and may bring the process to a foreground in a display. The application manager **1036** may also notify the windows manager **1032** to bring the associated window(s) to a top of a window stack for the display. When a process starts from a shell or a notification out of the context of the desktop, the application manager **1036** can scan files to match the process name with the entry name provided. When a match is found, the application manager **1036** can configure the process according to a settings file.

In some situations, the application manager **1036** may restrict an application as singleton (i.e., restricts the instantiation of a class to one object). If an application is already running and the application manager **1036** is asked to run the application again, the application manager **1036** can bring the running process to a foreground on a display. There can be a notification event exchange between the windows manager **1032** and the application manager **1036** for activating the appropriate window for the foreground process. Once an application is launched, the application may not be terminated or killed. The application can be sent to the background, except, possibly, for some applications (e.g., media player, Bluetooth®, notifications, etc.), which may be given a lowest process priority.

The panel launcher **1040** can be a widget configured to be placed along a portion of the display. The panel launcher **1040** may be built from desktop files from a desktop folder. The desktop folder location can be configured by a configuration file stored in system data **208**. The panel launcher **1040** can allow for the launching or executing of applications or processes by receiving inputs from a user interface to launch programs.

A desktop plugin **1024** may be a software component that allows for customization of the desktop or software interface through the initiation of plug-in applications.

One or more gestures used to interface with the vehicle control system **204** may be as described in conjunction with FIG. **11**A through **11**K. FIGS. **11**A through **11**H depict various graphical representations of gesture inputs that may be recognized by the devices **212**, **248**. The gestures may be performed not only by a user's body part, such as a digit, but also by other devices, such as a stylus, that may be sensed by the contact sensing portion(s) of a screen associated with the device **212**, **248**. In general, gestures are interpreted differently, based on where the gestures are performed (either directly on a display or in a gesture capture region). For example, gestures in a display may be directed to a desktop or application, and gestures in a gesture capture region may be interpreted as for the system.

With reference to FIGS. **11**A-**11**H, a first type of gesture, a touch gesture **1120**, is substantially stationary on a portion (e.g., a screen, a display, etc.) of a device **212**, **248** for a selected length of time. A circle **1128** represents a touch or other contact type received at particular location of a contact sensing portion of the screen. The circle **1128** may include a border **1132**, the thickness of which indicates a length of time that the contact is held substantially stationary at the contact location. For instance, a tap **1120** (or short press) has a thinner border **1132**A than the border **1132**B for a long press **1124** (or for a normal press). The long press **1124** may involve a contact that remains substantially stationary on the screen for longer time period than that of a tap **1120**. As will be appreciated, differently defined gestures may be registered depending upon the length of time that the touch remains stationary prior to contact cessation or movement on the screen.

With reference to FIG. **11**C, a drag gesture **1100** on the screen is an initial contact (represented by circle **1128**) with contact movement **1136** in a selected direction. The initial contact **1128** may remain stationary on the screen for a certain amount of time represented by the border **1132**. The drag gesture typically requires the user to contact an icon, window, or other displayed image at a first location followed by movement of the contact in a drag direction to a new second location desired for the selected displayed image. The contact movement need not be in a straight line but have any path of movement so long as the contact is substantially continuous from the first to the second locations.

With reference to FIG. **11**D, a flick gesture **1104** on the screen is an initial contact (represented by circle **1128**) with truncated contact movement **1136** (relative to a drag gesture) in a selected direction. A flick may have a higher exit velocity for the last movement in the gesture compared to the drag gesture. The flick gesture can, for instance, be a finger snap following initial contact. Compared to a drag gesture, a flick gesture generally does not require continual contact with the screen from the first location of a displayed image to a predetermined second location. The contacted displayed image is moved by the flick gesture in the direction of the flick gesture to the predetermined second location. Although both gestures commonly can move a displayed image from a first location to a second location, the temporal duration and distance of travel of the contact on the screen is generally less for a flick than for a drag gesture.

With reference to FIG. **11**E, a pinch gesture **1108** on the screen is depicted. The pinch gesture **1108** may be initiated by a first contact **1128**A to the screen by, for example, a first digit and a second contact **1128**B to the screen by, for example, a second digit. The first and second contacts **1128**A,B may be detected by a common contact sensing portion of a common screen, by different contact sensing portions of a common screen, or by different contact sensing portions of different screens. The first contact **1128**A is held for a first amount of time, as represented by the border **1132**A, and the second contact **1128**B is held for a second amount of time, as represented by the border **1132**B. The first and second amounts of time are generally substantially the same, and the first and second contacts **1128**A,B generally occur substantially simultaneously. The first and second contacts **1128**A,B generally also include corresponding first and second contact movements **1136**A,B, respectively. The first and second contact movements **1136**A,B are generally in opposing directions. Stated another way, the first contact movement **1136**A is towards the second contact **1136**B, and the second contact movement **1136**B is towards the first contact **1136**A. More simply stated, the pinch gesture **1108** may be accomplished by a user's digits touching the screen in a pinching motion.

With reference to FIG. **11**F, a spread gesture **1110** on the screen is depicted. The spread gesture **1110** may be initiated by a first contact **1128**A to the screen by, for example, a first digit, and a second contact **1128**B to the screen by, for example, a second digit. The first and second contacts **1128**A,B may be detected by a common contact sensing portion of a common screen, by different contact sensing portions of a common screen, or by different contact sensing portions of different screens. The first contact **1128**A is held for a first amount of time, as represented by the border **1132**A, and the second contact **1128**B is held for a second amount of time, as represented by the border **1132**B. The first and second amounts of time are generally substantially the same, and the first and second contacts **1128**A,B generally occur sub-

stantially simultaneously. The first and second contacts **1128**A,B generally also include corresponding first and second contact movements **1136**A,B, respectively. The first and second contact movements **1136**A,B are generally in an opposing direction. Stated another way, the first and second contact movements **1136**A,B are away from the first and second contacts **1128**A,B. More simply stated, the spread gesture **1110** may be accomplished by a user's digits touching the screen in a spreading motion.

The above gestures may be combined in any manner, such as those shown by FIGS. **11**G and **11**H, to produce a determined functional result. For example, in FIG. **11**G a tap gesture **1120** is combined with a drag or flick gesture **1112** in a direction away from the tap gesture **1120**. In FIG. **11**H, a tap gesture **1120** is combined with a drag or flick gesture **1116** in a direction towards the tap gesture **1120**.

The functional result of receiving a gesture can vary depending on a number of factors, including a state of the vehicle **104**, display, or screen of a device, a context associated with the gesture, or sensed location of the gesture, etc. The state of the vehicle **104** commonly refers to one or more of a configuration of the vehicle **104**, a display orientation, and user and other inputs received by the vehicle **104**. Context commonly refers to one or more of the particular application (s) selected by the gesture and the portion(s) of the application currently executing, whether the application is a single- or multi-screen application, and whether the application is a multi-screen application displaying one or more windows. A sensed location of the gesture commonly refers to whether the sensed set(s) of gesture location coordinates are on a touch sensitive display or a gesture capture region of a device **212**, **248**, whether the sensed set(s) of gesture location coordinates are associated with a common or different display, or screen, or device **212**, **248**, and/or what portion of the gesture capture region contains the sensed set(s) of gesture location coordinates.

A tap, when received by a touch sensitive display of a device **212**, **248**, can be used, for instance, to select an icon to initiate or terminate execution of a corresponding application, to maximize or minimize a window, to reorder windows in a stack, and/or to provide user input such as by keyboard display or other displayed image. A drag, when received by a touch sensitive display of a device **212**, **248**, can be used, for instance, to relocate an icon or window to a desired location within a display, to reorder a stack on a display, or to span both displays (such that the selected window occupies a portion of each display simultaneously). A flick, when received by a touch sensitive display of a device **212**, **248** or a gesture capture region, can be used to relocate a window from a first display to a second display or to span both displays (such that the selected window occupies a portion of each display simultaneously). Unlike the drag gesture, however, the flick gesture is generally not used to move the displayed image to a specific user-selected location but to a default location that is not configurable by the user.

The pinch gesture, when received by a touch sensitive display or a gesture capture region of a device **212**, **248**, can be used to minimize or otherwise increase the displayed area or size of a window (typically when received entirely by a common display), to switch windows displayed at the top of the stack on each display to the top of the stack of the other display (typically when received by different displays or screens), or to display an application manager (a "pop-up window" that displays the windows in the stack). The spread gesture, when received by a touch sensitive display or a gesture capture region of a device **212**, **248**, can be used to maximize or otherwise decrease the displayed area or size of a window, to switch windows displayed at the top of the stack on each display to the top of the stack of the other display (typically when received by different displays or screens), or to display an application manager (typically when received by an off-screen gesture capture region on the same or different screens).

The combined gestures of FIG. **11**G, when received by a common display capture region in a common display or screen of a device **212**, **248**, can be used to hold a first window location constant for a display receiving the gesture while reordering a second window location to include a window in the display receiving the gesture. The combined gestures of FIG. **11**H, when received by different display capture regions in a common display or screen of a device **212**, **248** or in different displays or screens of one more devices **212**, **248**, can be used to hold a first window location for a display receiving the tap part of the gesture while reordering a second window location to include a window in the display receiving the flick or drag gesture. Although specific gestures and gesture capture regions in the preceding examples have been associated with corresponding sets of functional results, it is to be appreciated that these associations can be redefined in any manner to produce differing associations between gestures and/or gesture capture regions and/or functional results.

Gestures that may be completed in three-dimensional space and not on a touch sensitive screen or gesture capture region of a device **212**, **248** may be as shown in FIGS. **11**I-**11**K. The gestures may be completed in an area where a sensor, such as an optical sensor, infrared sensor, or other type of sensor, may detect the gesture. For example, the gesture **1140** in FIG. **11**I may be executed by a person when the person opens their hand **1164** and moves their hand in a back and forth direction **1148** as a gesture **1140** to complete some function with the vehicle **104**. For example gesture **1140** may change the station of the radio in the vehicle **104**. The sensors **242** may both determine the configuration of the hand **1164** and the vector of the movement. The vector and hand configuration can be interpreted to mean certain things to the vehicle control system **204** and produce different results.

In another example of a gesture **1152** in FIG. **11**J, a user may configure their hand **1164** to extend two fingers and move the hand **1164** in an up and down operation **1156**. This gesture **1152** may control the volume of the radio or some other function. For instance, this gesture **1152** may be configured to place the vehicle in a "valet" mode to, among other things, restrict access to certain features associated with the vehicle. Again, the sensors **242** may determine how the person has configured their hand **1164**, and the vector of the movement. In another example of a gesture **1160** shown in FIG. **11**K, a user may extend their middle three fingers at an angle that is substantially 45° for vertical from straight vertical and circle the hand in a counter-clockwise motion **1166**. This gesture **1160** may cause the automobile to change the heat setting or do some other function. As can be understood by one skilled in the art, the configurations of the hand and the types of movement are variable. Thus, the user may configure the hand **1164** in any way imaginable and may also move that hand **1164** in any direction with any vector in three-dimensional space.

The gestures **1140**, **1152**, **1160**, as shown in FIGS. **11**I-**11**K, may occur in a predetermined volume of space within the vehicle **104**. For example, a sensor may be configured to identify such gestures **1140**, **1152**, **1160** between the front passenger's and front driver's seats over a console area within the passenger compartment of the vehicle **104**. The gestures **1140**, **1152**, **1160** may be made within area 1 **508**A between zones A **512**A and B **512**B. However, there may be other areas

508 where a user may use certain gestures, where sensors 242 may be able to determine a certain function is desired. Gestures that may be similar but used in different areas within the vehicle 104 may cause different functions to be performed. For example, the gesture 1140 in FIG. 11I, if used in zone E 512E, may change the heat provided in zone E 512E, but may change the station of a radio if used in zone A 512A and/or zone B 512B. Further, the gestures may be made with other body parts or, for example, different expressions of a person's face and may be used to control functions in the vehicle 104. Also, the user may use two hands in some circumstances or do other types of physical movements that can cause different reactions in the vehicle 104.

FIGS. 12A-12D show various embodiments of a data structure 1200 to store different settings. The data structure 1200 may include one or more of data files or data objects 1204, 1250, 1270, 1280. Thus, the data structure 1200 may represent different types of databases or data storage, for example, object-oriented data bases, flat file data structures, relational database, or other types of data storage arrangements. Embodiments of the data structure 1200 disclosed herein may be separate, combined, and/or distributed. As indicated in FIGS. 12A-12D, there may be more or fewer portions in the data structure 1200, as represented by ellipses 1244. Further, there may be more or fewer files in the data structure 1200, as represented by ellipses 1248.

Referring to FIG. 12A, a first data structure is shown. The data file 1204 may include several portions 1208-1242 representing different types of data. Each of these types of data may be associated with a user, as shown in portion 1208.

There may be one or more user records 1240 and associated data stored within the data file 1204. As provided herein, the user can be any person that uses or rides within the vehicle or conveyance 104. The user may be identified in portion 1212. For the vehicle 104, the user may include a set of one or more features that may identify the user. These features may be the physical characteristics of the person that may be identified by facial recognition or some other type of system. In other situations, the user may provide a unique code to the vehicle control system 204 or provide some other type of data that allows the vehicle control system 204 to identify the user. The features or characteristics of the user are then stored in portion 1212.

Each user, identified in portion 1208, may have a different set of settings for each area 508 and/or each zone 512 within the vehicle 104. Thus, each set of settings may also be associated with a predetermined zone 512 or area 508. The zone 512 is stored in portion 1220, and the area 508 is stored in portion 1216.

One or more settings may be stored in portion 1224. These settings 1224 may be the configurations of different functions within the vehicle 104 that are specified by or for that user. For example, the settings 1224 may be the position of a seat, the position of a steering wheel, the position of accelerator and/or brake pedals, positions of mirrors, a heating/cooling setting, a radio setting, a cruise control setting, or some other type of setting associated with the vehicle 104. Further, in vehicles adapted to have a configurable console or a configurable dash or heads-up display, the settings 1224 may also provide for how that heads-up display, dash, or console are configured for this particular user.

Each setting 1224 may be associated with a different area 508 or zone 512. Thus, there may be more settings 1224 for when the user is the driver and in zone A 512A, 512A, of area 1, 508A. However, there may be similar settings 1224 among the different zones 512 or areas 508 as shown in portion 1224. For example, the heating or radio settings for the user may be similar in every zone 512.

The sensors 242 within the vehicle 104 may be able to either obtain or track health data in portion 1228. Health data 1228 may include any type of physical characteristic associated with the user. For example, a heart rate, a blood pressure, a temperature, or other types of heath data may be obtained and stored in portion 1228. The user may have this health data tracked over a period of time to allow for statistical analysis of the user's health while operating the vehicle 104. In this way, if some function of the user's health deviates from a norm (e.g., a baseline measurement, average measurements taken over time, and the like), the vehicle 104 may be able to determine there is a problem with the person and react to that data.

One or more gestures may be stored in portion 1232. Thus, the gestures used and described in conjunction FIG. 11A through 11K may be configurable. These gestures may be determined or created by the user and stored in portion 1132. A user may have different gestures for each zone 512 or area 508 within the vehicle. The gestures that do certain things while driving may do other things while in a different area 508 of the vehicle 104. Thus, the user may use a first set of gestures while driving and a second set while a passenger. Further, one or more users may share gestures as shown in portion 1232. Each driver may have a common set of gestures that they use in zone A 512A, 512A. Each of these gestures may be determined or captured and then stored with their characteristics (e.g., vector, position of gesture, etc.) in portion 1232.

One or more sets of safety parameters may be stored in portion 1236. Safety parameters 1236 may be common operating characteristics for this driver/passenger or for all drivers/passengers that if deviated from may determine there is a problem with the driver/passenger or the vehicle 104. For example, a certain route may be taken repeatedly and an average speed or mean speed may be determined. If the mean speed deviates by some number of standard deviations, a problem with the vehicle 104 or the user may be determined. In another example, the health characteristics or driving experience of the user may be determined. If the user drives in a certain position where their head occupies a certain portion of three-dimensional space within the vehicle 104, the vehicle control system 204 may determine that the safety parameter includes the users face or head being within this certain portion of the vehicle interior space. If the user's head deviates from that interior space for some amount of time, the vehicle control system 204 can determine that something is wrong with the driver and change the function or operation of the vehicle 104 to assist the driver. This may happen, for example, when a user falls asleep at the wheel. If the user's head droops and no longer occupies a certain three dimensional space, the vehicle control system 204 can determine that the driver has fallen asleep and may take control of the operation of the vehicle 204 and the automobile controller 8104 may steer the vehicle 204 to the side of the road. In other examples, if the user's reaction time is too slow or some other safety parameter is not nominal, the vehicle control system 204 may determine that the user is inebriated or having some other medical problem. The vehicle control system 204 may then assume control of the vehicle to ensure that the driver is safe.

Information corresponding to a user and/or a user profile may be stored in the profile information portion 1238. For example, the profile information 1238 may include data relating to at least one of current data, historical data, a user preference, user habit, user routine, observation, location data

(e.g., programmed and/or requested destinations, locations of parking, routes traveled, average driving time, etc.), social media connections, contacts, brand recognition (e.g., determined via one or more sensors associated with the vehicle **104**, a device **212**, **248**, etc.), audible recording data, text data, email data, political affiliation, preferred retail locations/sites (e.g., physical locations, web-based locations, etc.), recent purchases, behavior associated with the aforementioned data, and the like. The data in the profile information portion **1238** may be stored in one or more of the data structures **1200** provided herein. As can be appreciated, these one or more data structures may be stored in one or more memory locations. Examples of various memory locations are described in conjunction with FIG. **2**.

One or more additional data fields may be stored in the linked data portion **1242** as data and/or locations of data. The linked data **1242** may include at least one of pointers, addresses, location identification, data source information, and other information corresponding to additional data associated with the data structure **1200**. Optionally, the linked data portion **1242** may refer to data stored outside of a particular data structure **1200**. For example, the linked data portion **1242** may include a link/locator to the external data. Continuing this example, the link/locator may be resolved (e.g., via one or more of the methods and/or systems provided herein, etc.) to access the data stored outside of the data structure **1200**. Additionally or alternatively, the linked data portion **1242** may include information configured to link the data objects **1204** to other data files or data objects **1250**, **1270**, **1280**. For instance, the data object **1204** relating to a user may be linked to at least one of a device data object **1250**, a vehicle system data object **1270**, and a vehicle data object **1280**, to name a few.

An embodiment of a data structure **1200** to store information associated with one or more devices is shown in FIG. **12**B. The data file **1250** may include several portions **1216**-**1262** representing different types of data. Each of these types of data may be associated with a device, as shown in portion **1252**.

There may be one or more device records **1250** and associated data stored within the data file **1250**. As provided herein, the device may be any device that is associated with the vehicle **104**. For example, a device may be associated with a vehicle **104** when that device is physically located within the interior space **108** of the vehicle **104**. As another example, a device may be associated with a vehicle **104** when the device registers with the vehicle **104**. Registration may include pairing the device with the vehicle **104** and/or one or more of the vehicle systems (e.g., as provided in FIG. **3**). In some cases, the registration of a device with a vehicle **104** may be performed manually and/or automatically. An example of automatic registration may include detecting, via one or more of the vehicle systems, that a device is inside the vehicle **104**. Upon detecting that the device is inside the vehicle **104**, the vehicle system may identify the device and determine whether the device is or should be registered. Registration may be performed outside of a vehicle **104** via providing a unique code to the vehicle **104** and/or at least one of the vehicle systems.

The device may be identified in portion **1256**. Among other things, the device identification may be based on the hardware associated with the device (e.g., Media Access Control (MAC) address, Burned-In Address (BIA), Ethernet Hardware Address (EHA), physical address, hardware address, and the like).

Optionally, a device may be associated with one or more users. For example, a tablet and/or graphical user interface (GUI) associated with the vehicle **104** may be used by multiple members of a family. For instance, the GUI may be located in a particular area **508** and/or zone **512** of the vehicle **104**. Continuing this example, when a family member is located in the particular area **508** and/or zone **512**, the device may include various settings, features, priorities, capabilities, and the like, based on an identification of the family member. The user may be identified in portion **1254**. For the device, the user identification portion **1254** may include a set of one or more features that may identify a particular user. These features may be the physical characteristics of the person that may be identified by facial recognition, or some other type of system, associated with the device and/or the vehicle **104**. Optionally, the user may provide a unique code to the device, or provide some other type of data, that allows the device to identify the user. The features or characteristics of the user are then stored in portion **1254**.

Each device identified in the device identification portion **1256** may have a different set of settings for each area **508** and/or each zone **512**, and/or each user of the device. Thus, each set of settings may also be associated with a predetermined zone **512**, area **508**, and/or user. The zone **512** is stored in portion **1220** and the area **508** is stored in portion **1216**.

One or more settings may be stored in portion **1224**. These settings **1224** may be similar and/or identical to those previously described. Further, the settings **1224** may also provide for how a device is configured for a particular user. Each setting **1224** may be associated with a different area **508** or zone **512**. Thus, there may be more restrictive settings **1224** (e.g., restricted multimedia, texting, limited access to device functions, and the like) for the device when the user is the driver and in zone A **512**A, **512**A, of area 1, **508**A. However, when the user is in another zone **512** or area **508**, for example, where the user is not operating a vehicle **104**, the settings **1224** may provide unrestricted access to one or more features of the device (e.g., allowing texting, multimedia, etc.).

Optionally, the capabilities of a device may be stored in portion **1258**. Examples of device capabilities may include, but are not limited to, a communications ability (e.g., via wireless network, EDGE, 3G, 4G, LTE, wired, Bluetooth®, Near Field Communications (NFC), Infrared (IR), etc.), hardware associated with the device (e.g., cameras, gyroscopes, accelerometers, touch interface, processor, memory, display, etc.), software (e.g., installed, available, revision, release date, etc.), firmware (e.g., type, revision, etc.), operating system, system status, and the like. Optionally, the various capabilities associated with a device may be controlled by one or more of the vehicle systems provided herein. Among other things, this control allows the vehicle **104** to leverage the power and features of various devices to collect, transmit, and/or receive data.

One or more priorities may be stored in portion **1260**. The priority may correspond to a value, or combination of values, configured to determine how a device interacts with the vehicle **104** and/or its various systems. The priority may be based on a location of the device (e.g., as stored in portions **1216**, **1220**). A default priority can be associated with each area **508** and/or zone **512** of a vehicle **104**. For example, the default priority associated with a device found in zone 1 **512**A of area 1 **508**A (e.g., a vehicle operator position) may be set higher than an (or the highest of any) alternative zone **512** or area **508** of the vehicle **104**. Continuing this example, the vehicle **104** may determine that, although other devices are found in the vehicle, the device, having the highest priority, controls features associated with the vehicle **104**. These features may include vehicle control features, critical and/or non-critical systems, communications, and the like. Addi-

tionally or alternatively, the priority may be based on a particular user associated with the device. Optionally, the priority may be used to determine which device will control a particular signal in the event of a conflict.

Registration data may be stored in portion **1262**. As described above, when a particular device registers with a vehicle **104**, data related to the registration may be stored in the registration data portion **1262**. Such data may include, but is not limited to, registration information, registration codes, initial registration time, expiration of registration, registration timers, and the like. Optionally, one or more systems of the vehicle **104** may refer to the registration data portion **1262** to determine whether a device has been previously registered with the vehicle **104**. As shown in FIG. **12**B, User 4 of Device 2 has not been registered. In this case, the registration data field **1262**, for this user, may be empty, contain a null value, or other information/indication that there is no current registration information associated with the user.

Additionally or alternatively, the data structure **1200** may include a profile information portion **1238** and/or a linked data portion **1242**. Although the profile information portion **1238** and/or the linked data portion **1242** may include different information from that described above, it should be appreciated that the portions **1238**, **1242** may be similar, or identical, to those as previously disclosed.

An embodiment of a data structure **1200** to store information associated with one or more vehicle systems is shown in FIG. **12**C. The data file **1270** may include several portions **1216-1279** representing different types of data. Each of these types of data may be associated with a vehicle system, as shown in portion **1272**.

There may be one or more system records **1270** and associated data stored within the data file **1270**. As provided herein, the vehicle systems may be any system and/or subsystem that is associated with the vehicle **104**. Examples of various systems are described in conjunction with FIG. **3** and other related figures (e.g., systems **324-352**, etc.). One example of a system associated with the vehicle **104** is the vehicle control system **204**. Other systems may include communications subsystems **344**, vehicle subsystems **328**, and media subsystems **348**, to name a few. It should be appreciated that the various systems may be associated with the interior space **108** and/or the exterior of the vehicle **104**.

Each system may include one or more components. The components may be identified in portion **1274**. Identification of the one or more components may be based on hardware associated with the component. This identification may include hardware addresses similar to those described in conjunction with the devices of FIG. **12**B. Additionally or alternatively, a component can be identified by one or more signals sent via the component. Such signals may include an Internet Protocol (IP), or similar, address as part of the signal. Optionally, the signal may identify the component sending the signal via one or more of a header, a footer, a payload, and/or an identifier associated with the signal (e.g., a packet of a signal, etc.).

Each system and/or component may include priority type information in portion **1276**. Among other things, the priority type information stored in portion **1276** may be used by the various methods and systems provided herein to differentiate between critical and non-critical systems. Non-limiting examples of critical systems may correspond to those systems used to control the vehicle **104**, such as, steering control, engine control, throttle control, braking control, and/or navigation informational control (e.g., speed measurement, fuel measurement, etc.) Non-critical systems may include other systems that are not directly related to the control of the vehicle **104**. By way of example, non-critical systems may include media presentation, wireless communications, comfort settings systems (e.g., climate control, seat position, seat warmers, etc.), and the like. Although examples of critical and/or non-critical systems are provided above, it should be appreciated that the priority type of a system may change (e.g., from critical to non-critical, from non-critical to critical, etc.) depending on the scenario. For instance, although the interior climate control system may be classified as a non-critical system at a first point in time, it may be subsequently classified as a critical system when a temperature inside/outside of the vehicle **104** is measured at a dangerous level (e.g., sub-zero Fahrenheit, greater than 90-degrees Fahrenheit, etc.). As such, the priority type may be associated with temperature conditions, air quality, times of the day, condition of the vehicle **104**, and the like.

Each system may be associated with a particular area **508** and/or zone **512** of a vehicle **104**. Among other things, the location of a system may be used to assess a state of the system and/or provide how the system interacts with one or more users of the vehicle **104**. As can be appreciated each system may have a different set of settings for each area **508** and/or each zone **512**, and/or each user of the system. Thus, each set of settings may also be associated with a predetermined zone **512**, area **508**, system, and/or user. The zone **512** is stored in portion **1220** and the area **508** is stored in portion **1216**.

One or more settings may be stored in portion **1224**. These settings **1224** may be similar and/or identical to those previously described. Further, the settings **1224** may also provide for how a system is configured for a particular user. Each setting **1224** may be associated with a different area **508** or zone **512**. For instance, a climate control system may be associated with more than one area **508** and/or zone **512**. As such, a first user seated in zone 1 **512**A of area 1 **508**A may store settings related to the climate control of that zone **512**A that are different from other users and/or zones **512** of the vehicle **104**. Optionally, the settings may not be dependent on a user. For instance, specific areas **508** and/or zones **512** of a vehicle **104** may include different, default, or the same settings based on the information stored in portion **1224**.

The various systems and/or components may be able to obtain or track health status data of the systems and/or components in portion **1278**. The health status **1278** may include any type of information related to a state of the systems. For instance, an operational condition, manufacturing date, update status, revision information, time in operation, fault status, state of damage detected, inaccurate data reporting, and other types of component/system health status data may be obtained and stored in portion **1278**.

Each component and/or system may be configured to communicate with users, systems, servers, vehicles, third parties, and/or other endpoints via one or more communication type. At least one communication ability and/or type associated with a system may be stored in the communication type portion **1279**. Optionally, the communication types contained in this portion **1279** may be ordered in a preferential order of communication types. For instance, a system may be configured to preferably communicate via a wired communication protocol over one or more wired communication channels (e.g., due to information transfer speeds, reliability, and the like). However, in this instance, if the one or more wired communication channels fail, the system may transfer information via an alternative communication protocol and channel (e.g., a wireless communication protocol and wireless communication channel, etc.). Among other things, the methods and systems provided herein may take advantage of the

information stored in the communication type portion **1279** to open available communication channels in the event of a communication channel failure, listen on other ports for information transmitted from the systems, provide a reliability rating based on the number of redundant communication types for each component, and more. Optionally, a component or system may be restricted from communicating via a particular communication type (e.g., based on rules, traffic, critical/non-critical priority type, and the like). In this example, the component or system may be forced by the vehicle control system **204** to use an alternate communication type where available, cease communications, or store communications for later transfer.

Additionally or alternatively, the data structure **1200** may include a profile information portion **1238** and/or a linked data portion **1242**. Although the profile information portion **1238** and/or the linked data portion **1242** may include different information from that described above, it should be appreciated that the portions **1238**, **1242** may be similar, or identical, to those as previously disclosed.

Referring now to FIG. **12**D, a data structure **1200** is shown optionally. The data file **1280** may include several portions **1216**-**1286** representing different types of data. Each of these types of data may be associated with a vehicle, as shown in portion **1282**.

There may be one or more vehicle records **1280** and associated data stored within the data file **1282**. As provided herein, the vehicle **104** can be any vehicle or conveyance **104** as provided herein. The vehicle **104** may be identified in portion **1282**. Additionally or alternatively, the vehicle **104** may be identified by one or more systems and/or subsystems. The various systems of a vehicle **104** may be identified in portion **1284**. For example, various features or characteristics of the vehicle **104** and/or its systems may be stored in portion **1284**. Optionally, the vehicle **104** may be identified via a unique code or some other type of data that allows the vehicle **104** to be identified.

Each system may be associated with a particular area **508** and/or zone **512** of a vehicle **104**. Among other things, the location of a system may be used to assess a state of the system and/or provide how the system interacts with one or more users of the vehicle **104**. As can be appreciated each system may have a different set of settings for each area **508** and/or each zone **512**, and/or each user of the system. Thus, each set of settings may also be associated with a predetermined zone **512**, area **508**, system, and/or user. The zone **512** is stored in portion **1220** and the area **508** is stored in portion **1216**.

One or more settings may be stored in portion **1224**. These settings **1224** may be similar and/or identical to those previously described. Further, the settings **1224** may also provide for how a vehicle and/or its systems are configured for one or more users. Each setting **1224** may be associated with a different area **508** or zone **512**. Optionally, the settings may not be dependent on a particular user. For instance, specific areas **508** and/or zones **512** of a vehicle **104** may include different, default, or the same settings based on the information stored in portion **1224**.

The various systems and/or components may be able to obtain or track health status data of the systems and/or components in portion **1278**. The health status **1278** may include any type of information related to a state of the systems. For instance, an operational condition, manufacturing date, update status, revision information, time in operation, fault status, state of damage detected, inaccurate data reporting, and other types of component/system health status data may be obtained and stored in portion **1278**.

One or more warnings may be stored in portion **1286**. The warnings data **1286** may include warning generated by the vehicle **104**, systems of the vehicle **104**, manufacturer of the vehicle, federal agency, third party, and/or a user associated with the vehicle. For example, several components of the vehicle may provide health status information (e.g., stored in portion **1278**) that, when considered together, may suggest that the vehicle **104** has suffered some type of damage and/or failure. Recognition of this damage and/or failure may be stored in the warnings data portion **1286**. The data in portion **1286** may be communicated to one or more parties (e.g., a manufacturer, maintenance facility, user, etc.). In another example, a manufacturer may issue a recall notification for a specific vehicle **104**, system of a vehicle **104**, and/or a component of a vehicle **104**. It is anticipated that the recall notification may be stored in the warning data field **1286**. Continuing this example, the recall notification may then be communicated to the user of the vehicle **104** notifying the user of the recall issued by the manufacturer.

Additionally or alternatively, the data structure **1200** may include a profile information portion **1238** and/or a linked data portion **1242**. Although the profile information portion **1238** and/or the linked data portion **1242** may include different information from that described above, it should be appreciated that the portions **1238**, **1242** may be similar, or identical, to those as previously disclosed.

An embodiment of a method **1300** for storing settings for a user **216** associated with vehicle **104** is shown in FIG. **13**. While a general order for the steps of the method **1300** is shown in FIG. **13**, the method **1300** can include more or fewer steps or can arrange the order of the steps differently than those shown in FIG. **13**. Generally, the method **1300** starts with a start operation **1304** and ends with an end operation **1336**. The method **1300** can be executed as a set of computer-executable instructions executed by a computer system and encoded or stored on a computer readable medium. Hereinafter, the method **1300** shall be explained with reference to the systems, components, modules, software, data structures, user interfaces, etc. described in conjunction with FIGS. **1**-**12**.

A person may enter the vehicle space **108**. One or more sensors **242** may then identify that a person is sitting within the vehicle **104**, in step **1308**. For example, sensors **242** in a seat, may determine that some new amount of weight has been registered. The amount of weight may fall within predetermined parameters (e.g., over a threshold, in a specific range, etc.). This weight may then be determined to be a person by one or more optical or other sensors **242**. The vehicle control system **204** may then determine that a person is in a certain zone **512** or area **508**. For example, the sensors **242** may send signals to the vehicle controls system **204** that an event has occurred. This information may be sent to the vehicle control system processor **304** to determine the zone **512** and area **508** where the event occurred. Further, the vehicle control system **204** may then identify the person, in step **1312**.

The vehicle control system **204** can receive the information from the sensors **242** and use that information to search the database **1200** that may be stored within the system data **208**. The sensor data may be compared to ID characteristics **1212** to determine if the person has already been identified. The vehicle control system **204** may also send the characteristic data from the sensors to the communication network **224** to a server **228** to compare the sensor data to stored data **232** that may be stored in a cloud system. The person's features can be compared to stored features **1212** to determine if the person in the vehicle **104** can be identified.

If the person has been identified previously and their characteristics stored in portion **1212**, the method **1300** proceeds YES to step **1316** where that person may be identified. In identifying a person, the information associated with that person **1240** may be retrieved and provided to the vehicle control system **204** for further action. If a person cannot be identified by finding their sensor characteristics in portion **1212**, the method **1300** proceeds NO to step **1320**. In step **1320**, the vehicle control system **204**, using an application, may create a new record in table **1200** for the user. This new record may store a user identifier and their characteristics **1212**. It may also store the area **508** and zone **512** in data portions **1216** and **1220**. The new record may then be capable of receiving new settings data for this particular user. In this way, the vehicle **104** can automatically identify or characterize a person so that settings may be established for the person in the vehicle **104**.

The input module **312** may then determine if settings are to be stored, in step **1324**. Settings might be any configuration of the vehicle **104** that may be associated with the user. The determination may be made after receiving a user input from the user. For example, the user may make a selection on a touch sensitive display indicating that settings currently made are to be stored. In other situations, a period of time may elapse after the user has made a configuration. After determining that the user is finished making changes to the settings, based on the length of the period of time since the setting was established, the vehicle control system **204** can save the setting. Thus, the vehicle control system **204** can make settings automatically based on reaching a steady state for settings for user.

The vehicle control system **204** may then store the settings for the person, in step **1328**. The user interaction subsystem **332** can make a new entry for the user **1208** in data structure **1204**. The new entry may be either a new user or a new settings listed in **1224**. The settings may be stored based on the area **508** and zone **512**. As explained previously, the settings can be any kind of configuration of the vehicle **104** that may be associated with the user in that area **508** and the zone **512**.

The settings may also be stored in cloud storage, in step **1332**. Thus, the vehicle control system **204** can send the new settings to the server **228** to be stored in storage **232**. In this way, these new settings may be ported to other vehicles for the user. Further, the settings in storage system **232** may be retrieved, if local storage does not include the settings in storage system **208**.

Additionally or alternatively, the settings may be stored in profile data **252**. As provided herein, the profile data **252** may be associated with one or more devices **212**, **248**, servers **228**, vehicle control systems **204**, and the like. Optionally, the settings in profile data **252** may be retrieved in response to conditions. For instance, the settings may be retrieved from at least one source having the profile data if local storage does not include the settings in storage system **208**. As another example, a user **216** may wish to transfer settings stored in profile data **252** to the system data **208**. In any event, the retrieval and transfer of settings may be performed automatically via one or more devices **204**, **212**, **248**, associated with the vehicle **104**.

An embodiment of a method **1400** to configure the vehicle **104** based on stored settings is shown in FIG. **14**. A general order for the steps of the method **1400** is shown in FIG. **14**. Generally, the method **1400** starts with a start operation **1404** and ends with an end operation **1428**. The method **1400** can include more or fewer steps or can arrange the order of the steps differently than those shown in FIG. **14**. The method **1400** can be executed as a set of computer-executable instructions executed by a computer system and encoded or stored on a computer readable medium. Hereinafter, the method **1400** shall be explained with reference to the systems, components, modules, software, data structures, user interfaces, etc. described in conjunction with FIGS. **1-13**.

The vehicle control system **204** can determine if a person is in a zone **512** or area **508**, in step **1408**. This determination may be made by receiving data from one or more sensors **242**. The vehicle **104** can use facial recognition, weight sensors, heat sensors, or other sensors to determine whether a person is occupying a certain zone **512**.

Using the information from the sensors **242**, the vehicle control system **204** can identify the person, in step **1412**. The vehicle control system **204** can obtain characteristics for the user currently occupying the zone **512** and compare those characteristics to the identifying features in portion **1212** of data structure **1204**. Thus, the settings in portion **1224** may be retrieved by identifying the correct zone **512**, area **508**, and characteristics for the user.

The vehicle control system **204** can first determine if there are settings associated with the identified person for that zone **512** and/or area **508**, in step **1416**. After identifying the user by matching characteristics with the features in portion **1212**, the vehicle control system **204** can determine if there are settings for the user for the area **1216** and zone **1220** the user currently occupies. If there are settings, then the vehicle control system **204** can make the determination that there are settings in portion **1224**, and the vehicle control system **204** may then read and retrieve those settings, in step **1420**. The settings may be then used to configure or react to the presence of the user, in step **1424**. Thus, these settings may be obtained to change the configuration of the vehicle **104**, for example, how the position of the seats or mirrors are set, how the dash, console, or heads up display is configured, how the heat or cooling is configured, how the radio is configured, or how other different configurations are made.

Embodiments of a method **1500** for storing settings in cloud storage are shown in FIG. **15**. A general order for the steps of the method **1500** is shown in FIG. **15**. Generally, the method **1500** starts with a start operation **1504** and ends with an end operation **1540**. The method **1500** can include more or fewer steps or can arrange the order of the steps differently than those shown in FIG. **15**. The method **1500** can be executed as a set of computer-executable instructions executed by a computer system and encoded or stored on a computer readable medium. Hereinafter, the method **1500** shall be explained with reference to the systems, components, modules, software, data structures, user interfaces, etc. described in conjunction with FIGS. **1-14**.

The vehicle control system **204** can determine if a person is in a zone **512** or area **508**, in step **1508**. As explained previously, the vehicle control system **204** can receive vehicle sensor data from vehicle sensors **242** that show a person has occupied a zone **512** or an area **508** of the vehicle **104**. Using the vehicle sensor data, the vehicle control system **204** can determine characteristics of the person, in step **1512**. These characteristics are compared to the features in portion **1212** of the data structure **1204**. From this comparison, the vehicle control system **204** can determine if the person is identified within the data structure **1204**, in step **1516**. If there is a comparison and the person can be identified, the method **1500** proceeds YES to step **1520**. However, if the person cannot be identified, the method **1500** proceeds NO, to step **1524**.

In step **1520**, the person is identified in portion **1208** by the successful comparison of the characteristics and the features. It should be noted that there may be a degree of variability

between the characteristics and the features in portion **1212**. Thus, the comparison may not be an exact comparison but may use methods known in the art to make a statistically significant comparison between the characteristics received from the sensors **242** and the features stored in portion **1212**. In step **1524**, the characteristics received from sensors **242** are used to characterize the person. In this way, the received characteristics may be used as an ID, in portion **1212**, for a new entry for a new user in portion **1208**.

The user may make one or more settings for the vehicle **104**. The vehicle control system **204** may determine if the settings are to be stored, in step **1528**. If the settings are to be stored, the method **1500** proceeds YES to step **1536**. If the settings are not to be stored or if there are no settings to be stored, the method **1500** proceeds NO to step **1532**. In step **1532**, the vehicle control system **204** can retrieve the settings in the portion **1224** of the data structure **1204**. Retrieval of the settings may be as described in conjunction with FIG. **14**. If settings are to be stored, the vehicle control system **204** can send those settings to server **228** to be stored in data storage **232**, in step **1536**. Data storage **232** acts as cloud storage that can be used to retrieve information on the settings from other vehicles or from other sources. Thus, the cloud storage **232** allows for permanent and more robust storage of user preferences for the settings of the vehicle **104**.

An embodiment of a method **1600** for storing gestures associated with the user is shown in FIG. **16**. A general order for the steps of the method **1600** is shown in FIG. **16**. Generally, the method **1600** starts with a start operation **1604** and ends with an end operation **1640**. The method **1600** can include more or fewer steps or can arrange the order of the steps differently than those shown in FIG. **16**. The method **1600** can be executed as a set of computer-executable instructions executed by a computer system and encoded or stored on a computer readable medium. Hereinafter, the method **1600** shall be explained with reference to the systems, components, modules, software, data structures, user interfaces, etc. described in conjunction with FIGS. **1-15**.

Vehicle control system **204** may receive sensor data from sensors **242** to determine a person is occupying a zone **512** in an area **508** of the vehicle **104**, in step **1608**. The sensor data may provide characteristics for the person, in step **1612**. The vehicle control system **204** may then use the characteristics to determine if the person can be identified, in step **1616**. The vehicle control system **204** may compare the characteristics to the features in portion **1212** for the people having been recognized and having data associated therewith. If a comparison is made between the characteristics and the features in portion **1212**, the person can be identified, and the method **1600** proceeds YES to step **1620**. If there is no comparison, the method **1600** may proceed NO to step **1624**. In step **1620**, the person may be identified by the vehicle control system **204**. Thus, the person's features and associated data record **1240** may be determined and the user identified in portion **1208**. If the person is not identified, the vehicle control system **204** can characterize the person in step **1624** by establishing a new record in data structure **1204** using the characteristics, received from the sensors **242**, for the features in portion **1212**.

Thereinafter, the vehicle control system **204** may determine if gestures are to be stored and associated with the user, in step **1628**. The vehicle control system **204** may receive user input on a touch sensitive display or some other type of gesture capture region which acknowledges that the user wishes to store one or more gestures. Thus, the user may create their own gestures such as those described in conjunction with FIGS. **11A-11K**. These gestures may then be characterized and stored in data structure **1204**. If there are gestures to be stored, the method **1600** proceeds YES to step **1636**. If gestures are not to be stored the method **1600** may proceed NO to step **1632**.

In step **1632**, the vehicle control system **204** can retrieve current gestures from portion **1232**, which are associated with user **1240**. These gestures may be used then to configure how the vehicle **104** will react if a gesture is received. If gestures are to be stored, the vehicle control system **204** may store characteristics, in step **1636**, as received from sensor **242** or from one more user interface inputs. These characteristics may then be used to create the stored gestures **1232**, in data structure **1204**. The characteristics may include what the gesture looks like or appears and also what affect the gesture should have. This information may then be used to change the configuration or operation of the vehicle **104** based on the gesture if it is received at a later time.

An embodiment of a method **1700** for receiving a gesture and configuring the vehicle **104** based on the gesture may be as provided in FIG. **17**. A general order for the steps of the method **1700** is shown in FIG. **17**. Generally, the method **1700** starts with a start operation **1704** and ends with an end operation **1728**. The method **1700** can include more or fewer steps or can arrange the order of the steps differently than those shown in FIG. **17**. The method **1700** can be executed as a set of computer-executable instructions executed by a computer system and encoded or stored on a computer readable medium. Hereinafter, the method **1700** shall be explained with reference to the systems, components, modules, software, data structures, user interfaces, etc. described in conjunction with FIGS. **1-16**.

A vehicle control system **204** can receive sensor data from vehicle sensors **242**. The vehicle sensor data can be used by the vehicle control system **204** to determine that a person is in a zone **512** or area **508**, in step **1708**. The vehicle sensor data may then be used to compare against feature characteristics **1212** to identify a person, in step **1712**. The vehicle control system **204** thereinafter may receive a gesture, in step **1716**. The gesture may be perceived by vehicle sensors **242** or received in a gesture capture region. The gesture may be as described in conjunction with FIGS. **11A-11K**. Upon receiving the gesture, the vehicle control system **204** can compare the gesture to gesture characteristics in portion **1232**, in step **1720**. The comparison may be made so that a statistically significant correlation between the sensor data or gesture data and the gesture characteristic **1232** is made. Upon identifying the gesture, the vehicle control system **204** can configure the vehicle **104** and/or react to the gesture, in step **1724**. The configuration or reaction to the gesture may be as prescribed in the gesture characteristic **1232**.

An embodiment of a method **1800** for storing health data may be as shown in FIG. **18**. A general order for the steps of the method **1800** is shown in FIG. **18**. Generally, the method **1800** starts with a start operation **1804** and ends with an end operation **1844**. The method **1800** can include more or fewer steps or can arrange the order of the steps differently than those shown in FIG. **18**. The method **1800** can be executed as a set of computer-executable instructions executed by a computer system and encoded or stored on a computer readable medium. Hereinafter, the method **1800** shall be explained with reference to the systems, components, modules, software, data structures, user interfaces, etc. described in conjunction with FIGS. **1-17**.

Vehicle control system **204** can receive sensor data from sensors **242**. The sensor data may be used to determine that a person is in a zone **512** or area **508**, in step **1808**. The sensor data may then be used to determine characteristics of the

person, in step **1812**. From the characteristics, the vehicle control system **204** can determine if a person may be identified in data structure **1204**, in step **1816**. If it is determined that the person can be identified in step **1816**, the method **1800** proceeds YES to step **1820**. If the person cannot be identified, the method **1800** proceeds NO to step **1824**. A person may be identified by matching the characteristics of a person from the sensor data to the features shown in portion **1212**. If these comparisons are statistically significant, the person may be identified in portion **1208**, in step **1820**. However, if the person is not identified in portion **1208**, the vehicle control system **204** can characterize the person using the vehicle sensor data, in step **1824**. In this way, the vehicle control system **204** can create a new record for a new user in data structure **1204**.

Thereinafter, the vehicle control system **204** may receive health and/or safety data from the vehicle sensors **242**, in step **1828**. The vehicle control system **204** can determine if the health or safety data is to be stored, in step **1832**. The determination is made as to whether or not there is sufficient health data or safety parameters, in portion **1228** and **1236**, to provide a reasonable baseline data pattern for the user **1240**. If there is data to be received and stored, the vehicle control system **204** can store the data for the person in portions **1228** and **1236** of the data structure **1204**, in step **1832**.

The vehicle control system **204** may then wait a period of time, in step **1836**. The period of time may be any amount of time from seconds to minutes to days. Thereinafter, the vehicle control system **204** can receive new data from vehicle sensors **242**, in step **1828**. Thus, the vehicle control system **204** can receive data periodically and update or continue to refine the health data and safety parameters in data structure **1204**. Thereinafter, the vehicle control system **204** may optionally store the health and safety data in cloud storage **232** by sending it through the communication network **224** to the server **228**, in step **1840**.

An embodiment of a method **1900** for monitoring the health of a user may be as shown in FIG. **19**. A general order for the steps of the method **1900** is shown in FIG. **19**. Generally, the method **1900** starts with a start operation **1904** and ends with an end operation **1928**. The method **1900** can include more or fewer steps or can arrange the order of the steps differently than those shown in FIG. **19**. The method **1900** can be executed as a set of computer-executable instructions executed by a computer system and encoded or stored on a computer readable medium. Hereinafter, the method **1900** shall be explained with reference to the systems, components, modules, software, data structures, user interfaces, etc. described in conjunction with FIGS. **1-18**.

The vehicle control system **204** can receive health data from sensors **242**. The health data may be received in step **1908**. The vehicle control system **204** may then compare the received health data to stored health parameters in portion **1228** or portion **1236**, in step **1912**. The comparison may check if there is statistically significant separation or disagreement between the received health data and the stored health data. Thus, the vehicle control system **204** can make a health comparison of the user based on a baseline of health data previously stored. A statistically significant comparison may include determining if there are any parameters more than three standard deviations from the average or norm, any parameter that is increasing or decreasing over a period of eight different measurements, a measurement that is more than two standard deviations from the norm more than three measurements consecutively, or other types of statistical comparisons.

If the vehicle control system **204** determines that measured health parameter does deviate from the norm, the vehicle control system **204** can determine whether the health data is within acceptable limits, in step **1916**. If the health data is within acceptable limits, the method **1900** proceeds YES back to receiving new health data, in step **1908**. In this way, the health data is periodically or continually monitored to ensure that the driver is in a healthy state and able to operate the vehicle. If the health data is not within acceptable parameters, the method **1900** may proceed NO to step **1924** where the vehicle control system **204** may react to the change in the health data. The reaction may include any measure to provide for the safety of the user, such as stopping the vehicle, beginning to drive the vehicle, driving the vehicle to a new location, such as a hospital, waking the driver with an alarm or other noise, or performing some other function that may help maintain the health or safety of the user.

The health data received may be a reaction from the driver. For example, the driver may call for help or ask the vehicle for assistance. For example, the driver or passenger may say that they are having a medical emergency and ask the car to perform some function to help. The function to help may include driving the person to a hospital or stopping the car and calling for emergency assistance.

Vehicle Network Security

Vehicle network security is a major obstacle to be overcome in making vehicles Internet capable. Firewall **484** can provide security but, due to the seriousness of the consequences to public safety of a security breach, additional security measures are desirable.

Network security can use a common computer to run simultaneously first and second operating systems, respectively, for critical and non-critical tasks, functions, and operations of each processing module of the vehicle control system **204**, whereby, in the event of a security breach event, the second operating system is disabled or its execution discontinued.

Other vehicle network security algorithms will be discussed with reference to FIGS. **23-25**. An effective approach to protecting the critical tasks, functions, and operations from attack is to have one computer that handles vehicle tasks, functions, and operations and a different computer that handles infotainment tasks, functions, and operations. The first and second computers (and the distributed processing networks of which each of the first and second computers are a part) are disconnected from one another and unable to communicate with one another either wirelessly or non-wirelessly (e.g., by a signal transmission line such as a bus). The first computer (and/or any component in the distributed processing component of which it is a part) is not discoverable by the vehicle wireless network access points **456** and/or the second computer and does not appear on any network topology (or management information base or MIB) stored in the second computer. The converse may or may not be true with respect to the second computer being discoverable by the first computer; that is, a network topology (or MIB) of a component in the network controlled by the first computer, including the first computer itself, may describe or include information regarding one or more components of the network controlled by the second computer or the second computer itself. Stated another way, the infotainment network (or the distributed processing network containing any component (such as one or more of the IP router **420**, IP module **1048**, communications module **1052**, device discovery daemon **1020**, media controller **492**, media processor **808**, access point **456**, match engine **812**, video controller **840**, audio controller **844**, speech synthesis module **820**, network transceiver **824**, signal

processing module **828**, device interaction module **818**, and combo controller **460**) participating in, providing, or handling infotainment content) can be prohibited from communicating with a vehicle non-infotainment control network containing any component participating in, providing, or handling signaling for controlling non-infotainment vehicle control tasks, functions, or operations, such as critical tasks, functions or operations (such as one or more of the vehicle control module **826**, location module **896**, automobile controller **8104**, vehicle systems transceiver **8108**, traffic controller **8112**, network traffic transceiver **8116**, and environmental control module **830**). The first computer can have no contactable address (such as a local IP address or global unicast address) on any wireless or non-wireless network, including the infotainment network, and is not addressable, contactable, or otherwise able to communicate with the second computer, a component in the network controlled by the second computer, or any portable computational device (such as the device or user interface **212**, **248**, user interface (s)/input interface(s) **324** and/or I/O module **312**).

Critical tasks, functions or operations can include one or more of (depending on the particular vehicle) monitoring, controlling, and/or operating the ECU, TCU, door settings, window settings, and/or blind spot monitor, monitoring, controlling, and/or operating the safety equipment (e.g., airbag deployment control unit, collision sensor, nearby object sensing system, seat belt control unit, sensors for setting the seat belt, etc.), monitoring and/or controlling certain critical sensors such as the power source controller and energy output sensor, engine temperature, oil pressure sensing, hydraulic pressure sensors, sensors for headlight and other lights (e.g., emergency light, brake light, parking light, fog light, interior or passenger compartment light, and/or tail light state (on or off)), vehicle control system sensors, and/or steering/torque sensor, controlling the operation of the engine (e.g., ignition), head light control unit, power steering, display panel, switch state control unit, power control unit, and/or brake control unit, and/or issuing alerts to a user and/or remote monitoring entity of potential problems with a vehicle operation.

Less critical tasks, functions or operations to vehicle operation (which are unrelated to infotainment) can, depending on the application, further include one or more of (depending on the particular vehicle) monitoring, controlling, and/or operating a wireless network sensor (e.g., Wi-Fi and/or Bluetooth sensor), cellular data sensor, emissions control, seating system controller and sensor, monitoring certain non-critical sensors such as ambient (outdoor) weather readings (e.g., temperature, precipitation, wind speed, and the like), odometer reading sensor, trip mileage reading sensor, road condition sensors (e.g., wet, icy, etc.), radar transmitter/receiver output, brake wear sensor, oxygen sensor, ambient lighting sensor, vision system sensor, ranging sensor, parking sensor, heating, venting, and air conditioning (HVAC) system and sensor, water sensor, air-fuel ratio meter, hall effect sensor, microphone, radio frequency (RF) sensor, and/or infrared (IR) sensor.

Infotainment tasks, functions, or operations can include one or more of monitoring, controlling, and/or operating a wireless network sensor (e.g., Wi-Fi and/or Bluetooth sensor), cellular data sensor, emissions control, entertainment system, receiving, processing, and/or providing media and/or multimedia content. Infotainment tasks, functions, or operations are typically performed by one or more of the IP router **420**, IP module **1048**, communications module **1052**, device discovery daemon **1020**, media controller **492**, media processor **808**, access point **456**, match engine **812**, video controller **840**, audio controller **844**, speech synthesis module **820**, network transceiver **824**, signal processing module **828**, device interaction module **818**, desktop manager **1012**, windows manager **1032**, application manager **1036**, panel launcher **1040**, desktop plugin **1024**, and combo controller **460**.

Another approach is depicted in FIG. **23**, which shows a common computer **2300** having a microprocessor **2320** executing first and second virtual machines **2308** and **2312**. In common memory **2304**, each of the first and second virtual machines is an isolated software container with its own operating system **1004** and executing one or more applications. By way of example and with reference to the first and second computers discussed above, the first virtual machine can simulate the first computer while the second virtual machine can simulate the second computer. Applications stored in each virtual machine would be those applications responsible for critical tasks, functions, and operations in the first virtual machine **2308** and non-critical tasks, functions, and operations in the second virtual machine **2312**. Alternatively, the applications stored in the first virtual machine **2308** can be those controlling vehicle tasks, functions, and operations while those stored in the second virtual machine **2312** can be those controlling infotainment tasks, functions, and operations. For example, the first virtual machine **2308** can include one or more of vehicle control module **826**, location module **896**, automobile controller **8104**, vehicle systems transceiver **8108**, traffic controller **8112**, network traffic transceiver **8116**, and environmental control module **830** while the second virtual machine **2312** can include one or more of the IP module **1048**, communications module **1052**, device discovery daemon **1020**, media controller **492**, media processor **808**, access point **456**, match engine **812**, video controller **840**, audio controller **844**, speech synthesis module **820**, network transceiver **824**, signal processing module **828**, device interaction module **818**, and combo controller **460**. Because each of the first and second virtual machines is completely separate and independent, multiple virtual machines can run simultaneously on a common computer. A hypervisor module **2316** decouples the first and second virtual machines **2308** and **2312** from the host and dynamically allocates computing resources to each of the first and second virtual machine as needed. Computing resources includes, for example, interrupt requests, input/output memory locations, direct memory access, memory capacity allocated for each operating system, scheduling of central processing units, and the like.

Yet another approach is shown in FIG. **24**. As illustrated in FIG. **24**, a common computer **2400** includes first and second operating systems **1004***a* and **1004***b* stored in common memory **2412**. Each of the first and second operating systems **1004***a* and **1004***b* executing by the microprocessor **2320**, can have one or more of a libraries layer **2408**, application framework layer **2416**, and application layer **2420**. Applications are executed in application layer supported by application framework layer of the respective operating system. For example in the case of infotainment, the application framework layer may include a window manager, activity manager, package manager, resource manager, telephony manager, gesture controller, and/or other managers and services. Each operating system can rely on a common kernel **1028** for process isolation, memory management, and threading support. Libraries layer includes user libraries that implement common functions with input/output and string manipulation, graphics libraries, database libraries, communication libraries, and/or other libraries.

By way of example and with reference to the prior paragraph, the first operating system and environment can simulate the first computer while the second operating system and environment can simulate the second computer. Applications

executing in each operating system and environment would be those applications responsible for critical and non-critical tasks, functions, and operations. More specifically, the applications stored in the application framework layer of the first operating system **1004***a* can be those controlling vehicle tasks, functions, and operations while those stored in the second operating system **1004***b* can be those controlling infotainment tasks, functions, and operations. For example, the first operating system **1004***a* can include one or more of vehicle control module **826**, location module **896**, automobile controller **8104**, vehicle systems transceiver **8108**, traffic controller **8112**, network traffic transceiver **8116**, and environmental control module **830** while the second operating system **1004***b* can include one or more of the IP module **1048**, communications module **1052**, device discovery daemon **1020**, media controller **492**, media processor **808**, access point **456**, match engine **812**, video controller **840**, audio controller **844**, speech synthesis module **820**, network transceiver **824**, signal processing module **828**, device interaction module **818**, and combo controller **460**.

The first operating system **1004***a* can run in a separate execution environment from the second operating system **1004***b*. For example, one operating system (typically the first operating system **1004***a*) can run in a root execution environment while the other operating system (typically the first operating system **1004***b*) runs in a secondary execution environment established under the root execution environment. Processes and applications running on the second operating system, for instance, can access user libraries, manager(s), and service(s) in the secondary execution environment. Generally applications for one operating system do not run on the other operating system.

The kernel **1028** is shared such that the first and second operating systems run concurrently and independently on the shared kernel **1028**. Specifically, both operating systems **1004***a,b* interface to the shared kernel **1028** through the same kernel interface, such as by making system calls to the shared kernel **1028**. The shared kernel **1028** manages task scheduling for processes of both operating systems and resource management, such as CPU scheduling, memory access and input/output.

Other techniques exist for running multiple operating systems, including dual-boot, multiple operating systems loaded on a computing device one-at-a-time, hosted virtual machines, and operating system level virtualization.

FIG. **25** depicts an operation of the hypervisor module **2316** or common kernel **1028** (collectively "computer control module").

In step **2500**, the computer control module detects a stimulus, such as a potential security breach, attack, or other intrusion or attempted intrusion notification, a clock signal, an interrupt and the like. Examples of breaches, attacks, and other intrusions include denial-of-service attacks, spoofing, man in the middle, ARP spoofing, smurf attack, buffer overflow, heap overflow, format string attack, SQL injection, and cyber attack.

In step **2504**, the computer control module collects metrics regarding operations of the first and/or second operating system (e.g., of first or second virtual machine) and/or of the computer or associated therewith (e.g., of the network controlled by the first or second operating system). Metrics include network metrics, computational device metrics, and the like. Examples of network metrics include measuring link utilization, number of hops, speed of the path, packet loss, latency, path reliability, path bandwidth, network overhead, maximum transmission unit or MTU, throughput and the like and of computer metrics include load, transaction times, database access times, available memory, central processing unit ("CPU") usage, memory usage, and the like.

In decision diamond **2508**, the computer control module determines whether or not the collected metrics indicate a normal or abnormal operating state of the computer and/or of the first or second operating system and/or associated therewith. A normal operating state is deemed to occur when the collected metrics are within normal operational ranges. An abnormal operating state is deemed to occur when one or more of the collected metrics are outside of normal operational ranges. The ranges are predetermined or preconfigured by the manufacturer. Where some metrics are normal and others abnormal, the metrics may be ranked or scored, with the cumulative score being the basis for the normal or abnormal operating state determination.

In one application, the computer control module acts differently depending on whether the abnormality impacts the first or second operating system. When the first operating system responsible for critical vehicle functions, tasks, or operations is behaving abnormally, the driver can be warned of the potential problem and asked to terminate operation of the vehicle. Execution of certain critical vehicle tasks, functions or operations can be discontinued in favor of manual control of the vehicle tasks, functions, or operations. Execution of certain critical vehicle tasks, functions, or operations can be discontinued while other more critical tasks, functions, or operations continue to be executed. For example, steering, brakes, headlights, wipers, and vehicle acceleration can continue to be executed while environmental or climate control operations are discontinued. When the second operating system responsible for infotainment functions, tasks, or operations behaves abnormally, the driver can be warned of the potential problem and execution of the second operating system terminated automatically.

The determination as to whether the first or second operating system is behaving abnormally can be different. The first operating system can require more metrics to be abnormal than the second operating system or vice versa. Because the second operating system is more likely to be subject to an attack from the Internet or a portable device, a lesser deviation from normal operational ranges can be considered to be abnormal operation of the second operating system compared to the deviation required for the first operating system to be considered to be operating abnormally. Stated another way, a lower threshold is required to find abnormal operation of the second operating system when compared to the first operating system.

When the operating state is abnormal, the computer control module, in step **2512**, shuts down or disables the second virtual machine, operating system, or computer so that the first virtual machine, operating system, or computer continues to perform critical and/or automotive tasks, functions or operations while shutting down, terminating, or discontinuing execution of infotainment tasks, functions, or operations.

When the operating state of a network in communication with the computer control module is abnormal as determined by comparison of a network metric with one or more threshold values, the second, but not the first, operating system can be shut down, particularly when the second operating system (but not the first operating system) is controlling and/or receiving input from the network.

After step **2512** or when the operating state is normal, the computer control module, in step **2516**, records the metrics and findings and returns to step **2500**.

The above discussion can be applied to a vehicle having separate computers running the first and second operating systems, respectively. In other words, the computer controller

would monitor the operations of each of the first and second computers and a corresponding network providing input to each and perform the steps of FIG. **25** with respect to each of the first and second operating systems in each of the first and second computers and their respective networks.

Critical tasks, functions, and operations can be performed by an application executing in the first operating system and less critical tasks, functions, and operations (and infotainment tasks, functions, and operations) can be performed by an application executing in the second operating system. For instance, vehicle controls (e.g., steering, braking, indicating, etc.) can be considered mission critical and performed in the first operating system environment, whereas environmental controls and radio stations and entertainment presentations can be considered as non-critical and performed in the second operating system environment. Among other things, the critical tasks, functions, and operations can be performed not only by the first operating system but also alternatively by a redundant operating system. The redundant operating system may be configured to run in tandem with the first operating system performing critical tasks, functions, and operations and replace, or receive a "hot" handoff from, the first operating system in the event of a failure or malfunction of the first operating system or an application executing in the first operating system. In a "hot" handoff, the redundant operating system may replace the mission critical operating system without interruption of operation. Additionally or alternatively, the first operating system may utilize one or more of error checking communication protocols, secure communication standards, encrypted communications, high speed communications protocols, and the like.

The Vehicle as an Artificially Intelligent Assistant

The vehicle control system **204** can act as an artificially intelligent assistant that, based on an awareness of a selected vehicle occupant's persona (e.g., his or her physical, psychological, mental and other characteristics, needs, desires, behavior, personality, goals, habits, biometric information, likes or interests, dislikes, preferences, and the like) and/or the persona of family and friends of the selected vehicle occupant, proactively (without a preceding request of the selected vehicle occupant) provides feedback, suggestions, reminders, recommendations, and/or other types of assistance to the selected vehicle occupant. For example, the vehicle control system **204** can characterize, define, and/or analyze a person's persona based on profile data **252** of the person, device data **220** associated with the person, stored data **232**, system data **208**, and information related to the person as collected by vehicle interior and exterior sensors. In other words, a vehicle occupant's persona can include the information in one or more of the profile data **252** of the person, device data **220** associated with the person, stored data **232**, system data **208**, and information related to the person as collected by vehicle interior and exterior sensors. Based on the persona of selected persona and vehicle-related information (such as vehicle context, state, external surroundings, location, past, current, and/or intended path of travel, waypoints, and destination of the vehicle) can proactively provide suggestions, reminders, recommendations and/or other types of assistance to the selected vehicle occupant.

The persona can include a user selected and/or configured avatar, which is provided to the user via any graphical user interface by which the vehicle control system provides suggestions, reminders, recommendations and/or other types of assistance to the selected user as a vehicle occupant. As will be appreciated, an "avatar" is the graphical and/or voice representation of an object that can be the user or the user's alter ego or character or of a person selected by the user. It may take either a three-dimensional form, as in games or virtual worlds, or a two-dimensional form as an icon in Internet forums and other online communities. It can have not only a visual image but also distinct voice, mannerisms, and/or other behavior. It is commonly an object selected and/or configured by the user. Avatars can be used as virtual embodiments of embodied agents, which are driven more or less by artificial intelligence rather than real people.

Each occupant of a vehicle can have a differently configured and/or appearing avatar at his or her display interacting with him or her. As set forth below, the avatar may accompany the user from vehicle-to-vehicle as part of the user's persona, which can be shared from vehicle to vehicle.

For example, the vehicle control system, based on an awareness of a selected person's persona and the vehicle-related information, can note vehicle related alarms, bring to a selected person's attention instant messages, emails, voice mails from, missed phone calls from, current activities of and/or locations of friends, and points of interest near the vehicle or its path of travel.

In a further illustration, the vehicle control system notes that a vehicle driver's anniversary is next week, that the driver's spouse has pinned a bracelet that she likes, that the bracelet is on sale at a specific store, and that the driver has an appointment near the store and, in response, alerts the driver to the sale and spousal interest in the bracelet and asks the driver, via any one of the user interfaces **212**, **248**, input/output module **312**, and user interface/input interfaces **324**, whether the vehicle control system can (i) add a stop to the driver's calendar and/or waypoint for the store to the driver's path of travel and/or (ii) make the purchase of the bracelet online for the driver.

In yet a further illustration, the vehicle control system notes that a vehicle warning has been triggered, such as an actual or potential engine or other vehicle malfunction (e.g., low battery charge voltage, low oil pressure, high engine pressure, low fuel level, low tire pressure, air bag initiator malfunction, etc.), identifies vehicle service facilities in proximity to the current vehicle position or path of travel that is capable of repairing or addressing the source of the warning (e.g., a service garage, fuel station, dealership, etc.), contacts the facility to provide details on the malfunction to determine service cost, determine possible appointment times, notifies the driver of the possible appointment times, service cost, and corresponding facility location, and, at the option of the driver, schedules an appointment at the facility and adds a stop to the driver's calendar and/or waypoint for the facility to the driver's path of travel.

In yet a further illustration, the vehicle control system notes that a friend or family member of a vehicle occupant is in spatial proximity to the current vehicle position or path of travel, notifies the vehicle occupant of the identity and current location of the friend or family member, and, at the option of the occupant, contacts the friend or family member to notify them of the vehicle occupant's current position and arrange a meeting at a specified location nearby the current vehicle location or path of travel and adds a stop to the driver's calendar and/or waypoint for the meeting location to the driver's path of travel. This is particularly useful where the friend of family member is mobile too, such as in a vehicle or on a bike.

In yet a further illustration, the vehicle control system notes that the vehicle is on a long distance trip (based on the driver's or other occupant's electronic calendar and/or current location relative to the driver's or other occupant's home location), identifies hotels or motels in proximity to the current vehicle position or path of travel, contacts the hotel or motel

to determine possible room types (e.g., one or two beds, bed size, etc.), cost, and availabilities, notifies the driver of the accommodations available and cost, and, at the option of the driver, books an accommodation at a selected hotel or motel and adds a stop to the driver's calendar and/or waypoint for the hotel or motel to the driver's path of travel.

In yet a further illustration, the vehicle control system notes that the vehicle is on a long distance trip, identifies a point or location of interest based on a persona of a vehicle occupant in proximity to the current vehicle position or path of travel, collects and provides information about the point or location of interest to the vehicle occupant, optionally contacts the point or location of interest to determine business hours and costs to visit the point or location of interest, notifies the occupant of the business hours and cost, and, at the option of the driver, books an accommodation at the point or location of interest and adds a stop to the occupant's calendar and/or waypoint for the point or location of interest to the driver's path of travel. The point or location of interest can be a historical landmark, museum, library, church, store, restaurant, coffee shop, mall, healthcare facility, and the like.

In yet a further illustration, the vehicle control system notes, from the electronic calendar of the driver and/or historic driver behavior, that the destination of the vehicle is a meeting, place of employment, or other point of interest and the location thereof, determines that the path of travel of the vehicle will not arrive at the destination timely such as due to traffic, road construction, or other delays, determines a different route that will arrive timely at the destination, proposes the alternate route to the driver, and, at the driver's option, changes the on board navigation to redirect the driver along the alternate route. The vehicle control system can also send a message, such as an email or instant message, to one or more meeting participants or his or her place of employment to let them know that he or she will or may be late.

In a further illustration, an interior or exterior vehicle sensor **340** senses a condition or activity, such as of a vehicle passenger (e.g., a child passenger unbuckling a seat belt, children fighting in the back seat, an in appropriate gesture of a vehicle occupant, and the like) and notifies a selected vehicle occupant, such as the driver of the condition or activity.

In a further illustration, a vehicle control system based on information received from a sensor, such as a camera sensor **760**, can identify and/or distinguish an occupant's actions, clothing, held objects or objects in the possession of the user, and the like and perform an action. For instance, the vehicle control system can direct the occupant to a current sale of an identified object worn by or in the possession of the occupant that is in spatial proximity to the current vehicle location. Information regarding objects associated with the user can also be identified by radio frequency identification readers and tags, barcode readers, quick response code readers and the like.

In a further illustration, the vehicle control system determines that the occupant is driving the vehicle to a specific store and provides an alternate store site based on a busyness of one or more store locations. Parking information (e.g., how many spaces are occupied or free based on parking sensors, metered parking information, etc.) may be used to help determine an optimal store or destination location. A user, for instance, may be driving down a street and pull into a Starbucks™ parking lot at where the user and five other vehicles cannot find a parking spot. In this case, the user may spend five minutes waiting for the five other vehicles to clear the lot so the user can travel to another location. However, the vehicle control system, knowing that the parking lot associated with that particular Starbucks™ was fully occupied, may cause the vehicle to alter the route (or suggest an alternate route) to go to another Starbucks™ location based on the traffic and/or lack of parking.

In a further illustration, the vehicle control system may use image sensors to translate signs (e.g., road signs, store signs, advertisements, billboards, etc.). The translation process may be provided via the processing power of the mobile device, via processing on the cloud, combinations thereof, etc., and provide the translated signage message to the occupant.

In a further illustration, the vehicle control system may present a translated availability and/or assistance to guide a user in finding products traditionally purchased on trips. This guidance may be based upon the past behavior associated with the user persona. For instance, when a user travels to a new place the user may always (or mostly) shop for toothpaste, water, and ibuprofen. As can be appreciated, some foreign countries may not offer all of the products at a single store, like North American supermarkets. Continuing this example, the vehicle may provide a translation for the purchasing behavior by at least providing one or more shopping outlets where a user can procure toothpaste, water, and ibuprofen. In this example, the vehicle control system may state in the user's own language "You can find toothpaste and ibuprofen at the Apotheke on Dipplestrasse in downtown Munich. For water you may wish to visit the Marktkauf on Maybach Gaenge two blocks south of Dipplestrasse."

In a further illustration, the user may query for translation and visual assistance, such as "What does Aspirin look like in Germany". In response, the system may provide a picture or image and a translation text, voice, etc. via the mobile device and/or the vehicle.

In a further illustration, the vehicle control system and/or the mobile device, based on vehicle location and/or path of travel, may present travel and tourism options based on popular sites and/or destinations and, if selected, add the selected option as a waypoint or destination. For instance, the vehicle control system may provide the popular sites and/or destinations with a message, such as "75% of travelers visit the following destinations." The vehicle control system may develop a "perfect itinerary" based on the destinations desired and the timeframe. In some cases the itinerary may be based on desired locations and/or locations to be avoided. For instance a user may not wish to visit an industrial neighborhood, and as such the itinerary may provide routes that avoid industrialization.

In a further illustration, the vehicle control system can use a vehicle location-based trigger to activate and/or deactivate features and/or settings at a waypoint or destination, such as a home, a garage, and the like. For instance, the user may be returning home from work (this determination may be predicted based on prior trips made at the same or similar time of day by the same user), at a certain distance from the home, the vehicle may send a signal to a home automation system to set appropriate levels of lighting, thermostat, and/or initiate/deactivate other devices and/or open a garage door or entrance gate. A user may be traveling home from work and the vehicle control system may send a message, such as a text message, phone call, email, etc. to a third party to indicate the user is coming home. In some cases, the message may be identified as being sent from the vehicle (e.g., a vehicle icon with the message). The third party may respond to the message, which is then relayed, visually and or audibly, to the user via the components of the vehicle (e.g., dashboard, head unit, speakers, combinations thereof, etc.). By way of example, a third party may state "Please pick up some eggs and fabric softener before you come home, thanks."

In a further illustration, the vehicle control system can learn which routes one or more users travels at any given time period (hours, days, weeks, months, etc.). This information may be used to adjust routes based on traffic, weather, mood, etc. For instance, a user may plan to travel (or is traveling) to work on a Monday morning where heavy traffic is detected ahead in the user's "usual" Monday morning route. Upon detecting the traffic along the usual route, the vehicle may present the user with alternate route selections, or automatically adjust a route presented to the user. Routes may be altered by the vehicle control system based on past purchases, patterns, preferences and the like associated with a user profile. For instance, if a user visits McDonalds every morning for a cup of coffee and an egg McMuffin, the route guidance may alter the route of the individual to pass along several McDonalds. The route alteration may be terminated once the user stops to purchase products at the McDonalds. As can be appreciated, businesses may pay for route alteration and suggestion as a form of advertising.

In a further illustration, the vehicle control system centers around interactions and learns from user preferences. For instance, the vehicle control system learns that the user tends to like it warmer in the morning than in the afternoon, and adjust temperature settings in the vehicle accordingly. Further, since there are cameras and facial recognition, it can know my preferences and put them in, no matter what seat the user is in. IN another instance, the user has been surfing the Internet looking for new bikes, and the vehicle control system informs the user that there is a bike shop around the corner and adds the bike shop as a waypoint or destination.

In a further illustration, the vehicle control system synchronizes with an electronic calendar of the user to create (i) smarter alarms and (ii) updates. Smart alarms mean that instead of a standard 15 minute warning before a meeting, if it is an offsite meeting with an address entered, the system can determine how much time it will take based upon traffic, previous driving habits, the amount of time it generally takes to exit the office and get to the car, etc., and change the warning accordingly. The updates can be triggered based upon the time of arrival determination from the GPS or as calculated above and send SMS notices to other attendees or prompt to call the meeting leader. Similarly, if the car determines the user is stopping into Starbucks, it could remotely ask the other meeting attendees if they want anything.

In a further illustration, The vehicle control system knows a child's curfew and also the distance from home. Given that information, it could inform the child driver that he or she must leave to make it home in time to avoid a curfew violation. Further, since it knows the occupants, it could potentially include time to deliver them home too.

In a further illustration, the user is training for a marathon. He has a wearable device attached to his clothing that uses his biometric data (e.g., heart rate, body temperature, energy levels, sleeping habits, etc.) throughout the day. It also has a GPS that tracks location and terrain and an MP3 player. On his way to work, the wearable device has synchronized with the vehicle control system. The user verbally checks off his breakfast from his marathon widget on the home page displayed on the on board console and confirms his goals to be realized that day as well as his calendar appointments. On his way to a meeting later that day, the vehicle control system notes that it is near lunch time, reviews the restaurants in spatial proximity to the vehicle, determines which restaurants have menu items consistent with the user's dietary goals that day, and recommends a nearby restaurant. The user accepts the recommendation, and the vehicle control system books an advanced reservation and adds the restaurant as a waypoint. On his way back to the office, the vehicle control system notes that the user's heart rate is too low, notifies the user, and, upon the user's confirmation, adjusts the oxygen levels in the vehicle, seat and lumbar settings, and temperature levels to inhibit drowsiness.

In a further illustration, a user and his child enter the vehicle while the child is watching programming (such as a movie on Netflix™) on a tablet computer. The vehicle control system recognizes the user, determines his role in the car or seating position (driver), and applies the user's personal settings. The user's phone is automatically paired with the multimedia controller via the local or on board wireless access point. The vehicle control system determines that the child is in the back seat and recognizes his identity. The vehicle control system asks the user if the programming is to be continued to be provided to the child on the child's rear seat display subsystem. After dropping the child off at school, the vehicle control system determines, based on the user's electronic calendar, that the user is behind schedule for a next appointment due to an accident on the current path of travel, recommends an alternate path of travel and sends a message to the meeting participants that the user will be late and providing an estimated arrival time and reason for the late arrival. The message may be automatically generated or dictated by the user via the vehicle infotainment system. After work is over, the user drives home during a baseball game. The persona of the user informs the vehicle control system that the user is a baseball fan and recommends to the user that he tune into the game on radio. At the user's request, the infotainment system tunes automatically into the game broadcast on the radio.

The occupant persona is not limited to information obtained and stored directly by the vehicle. It can include information obtained by the vehicle from other sources, such as from a server **228** over a communication network **228** such as the Internet and IP router **420**. An example would be from a social network profile or page of a selected vehicle occupant, a web or home page of the selected vehicle occupant, a telecommunications presence server associated with the selected vehicle occupant, and the like. Another example would be from another vehicle driven or occupied by the selected vehicle occupant. Another example would be from a home computer network of the selected vehicle occupant. In the latter examples, the information can be obtained not only via the Internet but also directly via synchronization when the vehicles are parked in a common garage of the occupant's home even when the ignition of the vehicle(s) is/are turned off Another example would be from a portable communication or computational device of an occupant, such as from a device or user interface **212**, **248**. As noted, a transceiver of the vehicle can provide a mobile hot spot functionality not only to any user device(s) therein but also to a computer of another vehicle located in proximity to the selected vehicle. Synchronization with another vehicle's computer or with a home computer can be done, for example, by the http server capabilities of the vehicles.

The persona can be stored as part of a template locally, remotely, or combinations thereof. The persona can be stored in the cloud, on a personal communication device (such as a phone or tablet computer), in a memory of the vehicle, on a local storage memory, key fob, and the like. It may be encrypted and accessed and/or modified by the user via authorization through a verification system, which may rely on credentials and/or biometric information. The template may be universally applied by all vehicle manufacturers to enable the persona to be portable among vehicles so that the intelligent capability of the vehicle appears to follow the

associated user from vehicle to vehicle even when manufactured by different companies. The template can even follow the user from seat position to seat position within a vehicle, automatically populating vehicle settings, such as seat and console settings and features associated with a new seating position, when the user is identified as having moved to the new seat.

A console may not support multimedia entertainment, particularly video. Multimedia content is typically displayed on remote display subsystems dedicated to a specific seating position.

By way of illustration, user personas may be presented (or uploaded) to a vehicle in advance of a user reaching a vehicle (rental cars, etc.). For example, Hertz® car rental agency can maintain a persona for each customer and upload the persona onto the car rented to the customer at the time the leasing is consummated. While the user is walking from the rental desk to the car, the car is automatically adjusting all of the vehicle settings as set forth in the user persona. In this way, the user need not manually select any settings when he or she begins driving the car.

By way of further illustration, as part of a travel package, a rental car system may determine where a user is staying (e.g., hotel, motel, building, etc.), a mobile device number associated with the user, and the like. The system may send a text message, email, phone call, or other signal to the mobile device number to request access to the user's persona template. The template can be incorporated with the vehicle and settings associated with the vehicle may be updated prior to the user reaching the vehicle. Using this method, administrative assistants can reserve a vehicle on behalf of another individual and link the user template to the reservation based on the user's mobile device phone number. The mobile device can act as the key. For instance, a phone number may be embedded in the private key of the mobile device. The public key may be presented to the rental car. In some cases a combination of phone number and device ID (e.g., EIN, MAC address, etc.) may be used as part of the authentication.

The vehicle control system can apply rule sets or templates to trigger notifications and other actions of the vehicle control system and/or display artificial or computational intelligence based on observing the behavior of a selected person over time. In any of the embodiments disclosed herein, the vehicle control system and/or mobile device may determine patterns, such as, destinations, purchases, etc. to categorize data, advertising, and the like. The artificial or computational intelligence can, for example, have symbolic, sub-symbolic, or hybrid components and/or modules. Examples include neural networks (e.g., acyclic or feedforward neural networks and recurrent neural networks), fuzzy systems, and evolutionary computation.

An example of a home page **3000** displayed by a device or user interface **212**, **248**, user interface (s)/input interface(s) **324** and/or I/O module **312** is shown in FIG. **30**. The layout of the home page **3000** is defined by the user profile. When the user is signed as a guest user, a default layout is provided. The various objects in the layout can be configured as widgets or a lightweight version of an application or item of functionality.

The home page **3000***t* includes, in an upper area **3004** of the screen, user selectable icons for various applications (which if selected open or initiate or recall the application), such as navigation ("Nav" icon) **3016**, media ("Media" icon) **3018**, phone ("Phone" icon) **3020**, rear view (to provide the driver with a video stream from a backup camera) ("Rear View" icon) **3022**, other applications **3024**, and "my dash" (to provide the user with a display having typical dash indicators, such as speedometer, tacometer, oil pressure, warning lights, battery charge indicator, fuel level, and the like) **3026**; an upper information bar **3028** including a greeting to the identified driver **3030**, satellite reception indicator **3032**, WiFi connectivity indicator **3034**, cellular connectivity indicator **3036**, weather information **3038**, and date **3040**; in a central area **3008** of the screen, various types of information, such as navigation input fields **3042** (e.g., "set destination" field (which is a drop target into which location-enabled objects can be dragged and dropped) to provide guidance from the user's current user inputted or satellite-based location to the inputted destination), "set waypoints" field **3044** ((which is a drop target field into which any location-enabled object can be dragged and dropped) to set an ordering of waypoints along a selected or inputted route), suggested locations **3046** (based on upcoming events in the electronic calendar of the user and/or based on the user's preferences, likes, schedule, and observed habits and other persona information) (and therefore have location information, such as address information, inputted into the calendar entry and/or satellite-based coordinates based on prior driving history)) to be dragged and dropped into the "set destination" and/or "set waypoints" field, favorite locations **3048** (which is a list of user-defined favorite locations and which can also be dragged and dropped into the "set destination" and/or "set waypoints" field (and therefore have corresponding location information, such as satellite-based geographic coordinates or addresses entered in field(s) associated with the respective favorite locations (a home or work address is an example of a user selected favorite location))), recent locations **3050** (which refer to locations visited within a user-defined time interval of the present time and/or at least a predetermined number of times over a user-defined time interval and which can also be dragged and dropped into the "set destination" and/or "set waypoints" field (and therefore have corresponding location information, such as satellite-based geographic coordinates or addresses entered in field(s) associated with the respective recent locations)), "people" **3052** (which can be the contacts of the user or other list of friends and which provide names, contact information, and addresses for people having a corresponding contact profile, which profile can also be dragged and dropped into either the "set destination" or "set waypoints" field), points of interest **3054** (which are points of interest or potential interest to the operator such as food serving locations, fuel stations, lodging facilities, parking, attractions, health care facilities, historical landmarks, and the like and which can also be dragged and dropped into either the set destination or set waypoints field (and therefore have corresponding location information, such as satellite-based geographic coordinates or addresses entered in field(s) associated with the corresponding point of interest)), display of calendar appointments for a selected day **3056**, weather information for a selected day (e.g., temperatures, precipitation, wind speed and direction, atmospheric condition (e g, sunny, partially sunny, cloudy, partly cloudy, etc.), **3058** and received and/or sent messages (e.g., emails, voice mails, and/or texts) **3068** from friends (which dropdown menu can include family, business contacts, and other user defined category of contacts); and in a lower area **3012** of the screen, a climate control icon ("Climate" icon) for a climate control application **3060**, controls icon ("Control" icon) to control vehicle tasks, functions or operations **3062**, and speaker volume settings (shown by the speaker and triangle images) **3064** and controls to the left and right of the speaker image **3066** and **3070**.

When a suggested, favorite, recent location, people, or points of interest object or object identifier is dragged and

dropped by a sensed gesture or stylus or mouse into the "set destination" or "set waypoint" fields, the navigation subsystem **336**, based on the current satellite-based location of the vehicle, automatically determines a route from the vehicle's current location to the stored location associated with the dragged and dropped object. As more objects are dragged and dropped into either the "set destination" or "set waypoint" fields, the route is altered to accommodate the various associated locations. A traceroute on a map and/or directions can be provided to the vehicle operator. The traceroute or directions can be updated to show the vehicle's current location. The traceroute or directions can be altered to reflect traffic and/or road conditions (when the user selects "quickest" route), surface street or highway preferences, roadside aesthetics (when the user selects "most scenic" route), and the like. This information can be displayed by the user selection of the "Nav" icon **3016**.

The screen can provide a map on the background to assist navigation configuration. As the user configures the "set destination" and "set waypoint" fields, the traceroute can be updated on the background map. In other words, the various location-enabled objects and the "set destination" and "set waypoint" fields are overlays of the map.

As noted, the screen configuration and content, such as the arrangement of the various icons and displayed information, can be rearranged or reconfigured by the user to reflect his or her needs or desires.

Because the screen content is complex and/or content-heavy and can distract the operator when driving, the screen may be altered when the vehicle is in a driving mode relative to a parked mode. In a driving mode, the wheels are in motion and the gear shift is out of the "parked" position. In the parked mode, the wheels are not in motion and the gear shift is in the "parked" position. The home screen of FIG. **30** therefore can be closed automatically on the driver's console display and disabled when the vehicle is in the driving mode and opened automatically and enabled when the vehicle is in the parked mode.

Certain applications can be launched automatically when the vehicle is in the driving mode. An example would be the navigation application so that the console display shows the display for the navigation application instead of the home screen of FIG. **30**. One or more other applications can be selected by the user as the display in driving mode.

Alternatively or additionally, when the vehicle is placed in reverse gear with the home screen active, the rear-view application can be launched automatically to display, in the rear view application display, live video from one or more rear cameras on the back of the vehicle. When the vehicle is placed in forward gear, the rear view application can be automatically closed to terminate the rear view application display and the navigation application automatically opened to provide the navigation display.

The operation of the profile identification module **848** will be discussed with reference to FIG. **36**.

In step **3600**, the, the profile identification module **848** detects a stimulus, such as the vehicle changing operational state, expiration of a selected time period, a door opening or closing, and the like.

In step **3604**, the profile identification module **848** selects a current vehicle occupant, which can be the driver or a passenger.

In step **3608**, the profile identification module **848** determines a seating position of the selected vehicle occupant; that is, the module **848** determines which of the driver's seat, front passenger seat, driver's side rear passenger seat, middle rear passenger seat, and passenger's side rear passenger seat the selected vehicle occupant is occupying. This can be done by the user identification module **822**.

In step **3612**, the profile identification module **848** determines the types of information to collect for the persona of the selected occupant. The type of information to be collected can vary by occupant identity, age of occupant, an association of the occupant with the vehicle, and/or occupant seating position. For example, the driving history during the recent vehicle use may be collected for a driver but not a passenger. The driving history during the recent vehicle use may be collected for an adult passenger but not for a child passenger. The driving history during the recent vehicle use may be collected for a vehicle owner but not for a guest driver or driver having a default profile.

In step **3616**, the profile identification module **848** collects the selected types of information.

In step **3620**, the profile identification module **848** determines whether there is a next occupant to be selected. If so, the profile identification module **848** returns to step **3604**. If not, the profile identification module **848** returns to step **3600** and awaits the next stimulus instance.

An operation of the vehicle control system **204** will be discussed with reference to FIGS. **37**A-B.

In step **3700**, the vehicle control system **204** detects a stimulus, such as the vehicle changing operational state, expiration of a selected time period, a door opening or closing, and the like.

In step **3704**, the vehicle control system **204** selects a current vehicle occupant.

In step **3708**, the vehicle control system **204** determines a seating position of the selected occupant.

In step **3712**, the profile identification module **848** accesses, at the request of the vehicle control system **204**, the persona of the selected occupant.

In step **3716**, the vehicle control system **204** determines vehicle related information. This information includes typically any information collected by an interior or exterior vehicle sensor **104**, **242**, including a satellite navigation system, such as GPS **488**.

In step **3720**, the vehicle control system **204** determines other relevant types of information, such as the information referenced above in the examples and illustrations. The other relevant types of information can include, for instance, a persona of a selected person not currently in the vehicle, an instant message, email, voice mail from, missed phone call from, current activity of and/or current location of a friend and/or family member of the selected vehicle occupant, a location, hours of operation, and/or descriptive information about a point and/or location of interest near the vehicle and/or its path of travel, a location, hours of operation, and/or descriptive information about a vehicle service facility near the vehicle and/or its path of travel, a location, hours of operation, and descriptive information about a hotel and/or motel near the vehicle and/or its path of travel, a current location of the friend or family member near the vehicle and/or its path of travel, a road condition such as traffic, road construction, or other delay near the vehicle and/or its path of travel, and the like. This information can be collected from the server **228** via the communication network **224**.

In decision diamond **3724**, the vehicle control system **204** determines whether or not to perform an action. This determination can be based on a rule-based or template-based analysis of the persona of the selected occupant, vehicle related information, and other relevant types of information. The particular rules selected to apply to the collected information to determine whether or not to perform an action and what action to perform can depend on the identification of the

selected vehicle occupant and/or seating position of the selected vehicle occupant. Actions that can be performed include those referenced above, including making an appointment or reservation, purchasing an item on line, adding a waypoint to a path of travel on a navigation system, adding an entry into the selected occupant's calendar, changing a destination or path of travel on a navigation system, warning or notifying the occupant, and sending a message to a person regarding an arrival time at a waypoint or destination.

When the vehicle control system **204** determines not to perform an action, the vehicle control system **204**, in decision diamond **3728**, determines if there is a next occupant to be selected in the vehicle. If not, the vehicle control system returns to step **3700** and, if so, to step **3704**.

When an action is to be performed, the vehicle control system **204** in step **3732** optionally prompts the occupant whether or not the action is to be performed.

When instructed, the action is performed in step **3736**.

In step **3740**, the profile identification module **848** updates the persona of the selected vehicle occupant to reflect the action performed and the surrounding context. This can be important for the vehicle control system **204** creating new rules describing the likely behavior of the selected vehicle occupant.

In decision diamond **3728**, the vehicle control system **204** determines if there is a next occupant to be selected in the vehicle. If not, the vehicle control system returns to step **3700** and, if so, to step **3704**.

Operation of the Device Discovery Module **2080**

The device discovery daemon **1020** can discover automatically computational devices within the vehicle that connect or attempt to connect to network **356** or communication subsystem **1008** or that disconnect or attempt to disconnect from the network **356** or communication subsystem **1008**. The device discovery daemon **1020** discovers automatically computational devices, such as portable user communication devices, located within the vehicle and connects, wirelessly, the portable user communication device with the network **356** or communication subsystem **1008**.

The device discovery daemon **1020** may intercept emitted signals from one or more devices in or about the vehicle to pair a device with the network **356** or communication subsystem **1008**. Rather than requiring an active pair handshake, the network **356** or communication subsystem **1008** may utilize certain receivers to "listen" for cell tower registration signals, sent messages, sent packets (packet sniffing), etc. From this information, the device discovery daemon **1020** may isolate a MAC address, or other identifier, associated with a device and register the device with the vehicle, a vehicle zone, a user, etc. In some cases, and upon detecting a device signal, the device discovery daemon **1020** may request permission from a user before pairing the device. In one example, the pairing may be initiated by the device discovery daemon **1020** (upon a first registration) to a user's device. Subsequent pairings may be initiated by a user's device to the network **356** or communication subsystem **1008**. One or more of Bluetooth, Near Field Communications (NFC), and other protocols may be used to pair a device with the network **356** or communication subsystem **1008**.

FIG. **20** depicts an operation of the device discovery daemon **1020**.

In this operation, the device discovery daemon **1020** detects a computational device attempting to connect to or otherwise connectable with the vehicle network **356** or communication subsystem **1008** and, applying rules, determines when it is appropriate to connect with the computational device. The computational device may be a module installed on a backplane, a vehicle component and/or module that is attempting to be installed, a portable user communication device, and the like. The daemon can ping the local communication network each time the vehicle starts or each time a vehicle door opens or closes. The daemon can perform a Bluetooth™ and WiFi™ device discovery too. For each communication device that responds to the ping, the daemon can use plural protocols, such as HPPOPT, ICMP, IGMP, GGP, IP, ST, TCP, EGP, CHAOS, and UDP to populate a device's folder in the device data with device capabilities. Device capabilities are determined by the opened port(s) the device exposes.

The device discovery daemon **1020**, in conjunction with the combo controller can determine a spatial location of the computational device as a prerequisite to permitting the computational device, even if properly authenticated, to connect to the vehicle network **356** or communication subsystem **1008**. The spatial location can be required to be in an area **508** or set of areas **508** and/or zone or set of zones. Depending on the type of computational device, the computational device, for example, may be required to be in the area two **508**B for connection to be accepted. This can be the case for a portable personal communication device, such as a wireless or cellular phone, tablet computer, personal digital assistant, laptop, and the like. For other types of computational devices, the computational device, for example, may be required to be in area one **508**A (such as the engine space) and/or area N **508***n* (such as the trunk). Thus, different types of computational devices can have different location requirements as a prerequisite for connectivity to be enabled or accepted. This can be the case for an engine control module, vehicle sensor, or other device that controls or senses a vehicle task, function or operation that, for instance, either connects wirelessly or by a wire-line connection, to the red zone **417**, green zone **413**, or I/O backplane on the network/bus **408**.

In step **2000**, the device discovery daemon **1020** detects a computational device connectable with the vehicle network **356** or communication subsystem **1008**. "Connectable" can refer to the computational device being physically within the vehicle, the computational device having a threshold signal strength or connection quality with the vehicle network, the computational device being configured properly to connect with the vehicle network, and the like. "Connection" can be done either wirelessly or by wired connection.

Detection can be done by pinging the computational device and/or receiving a ping from the computational device. As an example, to connect to a Wi-Fi LAN a computational device must be equipped with a wireless network interface controller. The combination of a computer, such as the computer in the computational device, and interface controller is called a station. All stations share a single radio frequency communication channel. Transmissions on this channel are received by all stations within range. The hardware does not signal the user that the transmission was delivered and is therefore called a best-effort delivery mechanism. A carrier wave is used to transmit the data in packets, referred to as "Ethernet frames". Each station is constantly tuned in on the radio frequency communication channel to pick up available transmissions.

Device detection can be in response to or triggered by a sensed event other than receipt of a ping from the computational device. As noted, device detection can be receipt of information from one or more on board sensors that a new occupant has entered the vehicle. Exemplary information includes a door opening or closing, a successful authentication of an occupant or computational device, a sensed load in a seat, detection of movement within the vehicle, and detec-

tion of initiation of a vehicle task, function or operation, such as a key inserted in an ignition, engine start up, and the like.

In step **2004** and as noted above, the device discovery daemon **1020** accesses computational device accesses configuration and other information and capabilities of the connected computational device. This information can include device type and/or class, manufacturer name, product and/or device identifier or name, firmware identification, services running, device operating system, network address(es), capabilities, user credentials, and the like. The device discovery daemon **1020** can determine presence of the computational device on any input channel, such as Ethernet, USB, WiFi, Bluetooth, and the like.

In decision diamond **2008**, the device discovery daemon **1020** determines whether or not the computational device is recognized and/or authenticated properly. Recognition can be based on any of the configuration and other information and is deemed to occur when selected fields of the information map to and are the same as similar fields previously encountered and/or recorded in system data **208** by the device discovery daemon **1020**. Authentication is deemed to occur when the credentials match stored credentials for the recognized computational device.

When the computational device is not recognized and/or authenticated successfully, the device discovery daemon **1020**, in decision diamond **2012**, determines whether the computational device is in a predetermined area or zone of the vehicle for the type of computational device corresponding to the computational device. As will be appreciated, some wireless protocols, particularly WiFi™, use an access point (or hotspot) having a defined range, which can be commensurate with the area of the vehicle passenger cabin. The passenger cabin can be surrounded by walls that substantially block radio waves to prevent computational devices external to the passenger cabin from connecting to the network. Multiple overlapping access points can be used to cover larger passenger cabins, such as buses, trains, planes and the like. This determination can be based on received signal strength from the computational device, a satellite-based position of the computational device compared to a satellite-based position of the vehicle or sub-area of the passenger cabin, triangulation based on the relative received signal strengths of multiple access points, camera feedback or image processing of camera or video feed of the passenger compartment, occupant information received from other sensors such as occupant location or presence information received from an infrared sensor **740**, motion sensor **744**, weight sensor **748**, biometric sensor **756**, camera sensor **760**, audio sensor **764**, and associated device sensor **720**, user input and the like. User input can be received by a screen pop-up on the computational device requesting the user to designate whether or not and what vehicle the user is currently in and/or what seat position the user has in that vehicle.

A level of confidence can be assigned by the device discovery daemon **1020** to the computational device indicating a likelihood or probability that the computational device is located within the passenger compartment. This level of confidence can be based on consideration and analysis of multiple of the factors identified above. When multiple factors indicate that the user is within the passenger compartment, a higher likelihood is assigned to that determination; likewise, when multiple factors indicate that the user is outside of the passenger compartment, a lower likelihood is assigned to the determination. When no or an unsatisfactory response is received from the user in response to a request for user input and/or the level of confidence is below a selected threshold, the user is deemed to be located outside of the predetermined area and/or zone.

A further spatial determination can be made by the device discovery daemon **1020** based on how the computational device connected to the automotive network. If the computational device is hard wire connected, or plugged in, to the automotive network (which can be determined by known techniques), the spatial location of the computational device can be assumed to be within the vehicle regardless of other location mechanisms employed by the device discovery module.

A further spatial determination can be made by the device discovery daemon **1020** based on whether or not the computational device has moved within a defined time interval. This indicates that the computational device may not be within the vehicle as movement of a computational device within the vehicle is less likely than a computational device located outside of the vehicle, where the person corresponding to the computational device is often moving relative to the position of the vehicle.

A further spatial determination can be made by the device discovery daemon **1020** based on whether the signal strength or signal-to-noise ratio associated with a ping or other signal from the computational device varies significantly over a selected time interval. The signal-to-noise ratio associated with signaling from a computational device located within the vehicle would remain relatively constant while the signal-to-noise ratio associated with signaling from a computational device located outside of the vehicle would likely vary significantly as the person associated with the computational device moves relative to the vehicle and/or network **356** or communication subsystem **1008**.

A further spatial determination can be made by the device discovery daemon **1020** based on an analysis of signal characteristics. Signal characteristics can include one or more of, but is not limited to analyzing signal attenuation, where a signal with a shrinking strength or increasing strength may be determined to be moving in relative proximity or position to the vehicle, analyzing any Doppler shift in the frequency, which may indicate movement in reference to the vehicle and/or network **356** or communication subsystem **1008**, analyzing any kind of delay between receiving the same signal at the various transceivers **260** and/or sensors **242**A-N. A difference in the time of receipt can be used to triangulate where the location of the signal originated and if that location is outside the vehicle or inside the vehicle.

A further spatial determination can be made by the device discovery daemon **1020** based on an analysis of location information. Beyond the signal characteristics, the device discovery daemon **1020** may receive information from one or more sensors **242**A-N to determine a location of the vehicle. If the location of the vehicle is in an area where there is not a likelihood of signal congestion, for example, in the driveway of someone's home, then all received signals may be determined to have been with inside the vehicle. Thus, as signals are received and if the location has changed, the device discovery daemon **1020** may determine whether the current location is an area where there may be more signals received that would be outside the vehicle or whether the signals received has changed.

Analysis of the person sending the signal may also be used by the device discovery daemon **1020**. Thus, the device discovery daemon **1020** may access historical signal data (which is a record of devices that have previously been granted access to the vehicle communications network) to determine if the signals have been received from this device or from this

person before. Thus, the signal may identify a person documented in the signal data, and the device discovery daemon **1020** may determine if that person has used or connected with the device discovery daemon **1020** previously. Further, the device discovery daemon **1020** can determine if there is movement of the vehicle. If a signal remains within the car after the vehicle moves, then that signal can be determined to be inside the vehicle. For example, if the signal is received at the beginning of a route and then at some time thereinafter the signal continues to be received, then it is determined that signal may be inside the vehicle.

Further, sensor data may be analyzed by the device discovery daemon **1020**. Sensor data may include such things as determining if there are people and the number of people within a car. Thus, if there are three people in the vehicle and three signals are received, all three signals may be determined to be inside the vehicle. Further, it may be possible for the sensors **242** to determine if a device is currently being used inside the vehicle. For example, if an optical sensor can view a device within its field of vision and/or if an electromagnetic field sensor determines that there is EMF radiation emanating from a location in the vehicle, then the device discovery daemon **1020** can determine that that signal is originating inside a vehicle.

A further spatial determination can be made based on the type (or service) of computational device attempting to interact with the automotive network. If the computational device is not the type (or service) of device expected to be positioned within the passenger compartment, its attempt to connect to the automotive network can be disregarded completely. If the computational device is the type (or service) of device that can be connected to the vehicle network but is not the type (or service) of device expected to be associated with an occupant (such as a non-infotainment vehicle task, function, or operation control module, sensor module, a module plugged into a backplane (such as an XM radio module), or other type of device not permitted or expected to be associated with an occupant), the spatial determination may be deemed to be satisfied by the computational device being located somewhere within the vehicle even if outside of the passenger compartment. Conversely, if the computational device is the type (or service) of device that would normally be carried by a vehicle occupant, the spatial location query would be satisfied only when the computational device location were within the passenger compartment. This would prevent an unauthorized computational device, such as a cell phone or tablet computer, from connecting to the automotive network simply by being held above, beside, or beneath the vehicle. The mapping of type of computational device to permissible location (e.g., area and/or zone) within the vehicle can be effected in a look up table or other set of rules.

The device discovery daemon **1020** may receive one or more of these analyses and resolve the information. Thus, device discovery daemon **1020** can cross-correlate information from different analyses to determine if the signal is within the vehicle. Different weight may be given to different analyzes to make a determination about where the signal originates. In this way, a more robust decision is made as to whether or not the signal originates in the vehicle and should be allowed to connect to the universal bus or the routing system of the vehicle.

While this logic is described with respect to the location of the computational device, it is to be understood that this determination is optional. Whether or not a communication device is enabled to connect to the vehicle network **356** or communication subsystem **1008** can be based solely on successful authentication. In this way, the vehicle on board computer can connect automatically to the owner's home virtual private network to upload and/or download information, settings, and other information (such as user input into the vehicle computer, vehicle driving history (e.g., miles traveled, travel traceroutes, speeds traveled, and locations visited), vehicle service information (such as gas and fluid levels, engine problems, alarms or warnings activated, and the like), input received by on board applications from the user (such as scheduled appointments, notes, documents, and the like), applications downloaded, and the like. Synchronization of the on board vehicle and home computer can occur automatically whether the vehicle is turned on or off. This can be highly beneficial when the vehicle is parked in the garage.

When the computational device is recognized and/or authenticated and/or when the computational device is determined to be within a proper area and/or zone of the vehicle for the device type of the computational device, the device discovery daemon **1020**, in optional step **2016** determines a spatial location and/or seat position of the computational device to determine appropriate rights and/or privileges and/or restrictions of the user of the computational device as defined by user account or profile associated with the user, the device type of the computational device, the seat position of the user, or area or zone in which the user and/or computational device is located.

In step **2020**, the device discovery daemon **1020** permits or enables connection of the computational device with the vehicle network **356** or communication subsystem **1008** and optionally stipulates or defines what set of tasks, functions, and/or operations the user of the computational device can perform using the computational device, such as based on the location of the computational device within the vehicle and/or based on the authentication credentials (e.g., the identity of the computational device user).

When the computational device is determined to be outside of a defined area and/or zone of the vehicle (e.g., outside the passenger compartment or cabin) and the device discovery daemon **1020** does not recognize and/or authenticate the computational device successfully, the device discovery daemon **1020**, in step **2024**, denies access of the computational device to connect to or access the vehicle network **356** or communication subsystem **1008**.

An example of the device discovery daemon **1020** operation will now be discussed. Assume that a vehicle owner purchases an XM radio module off the shelf from a vendor. The user then plugs in the module to the vehicle network. In attempting to enable the functionality of the XM radio, the device discovery daemon **1020** first attempts to recognize and/or authenticate the module. During the process, the XM radio module can be permitted to communicate through the vehicle network or an antenna internal to the module with a remote website to confirm that the XM radio was purchased by the vehicle owner and/or perform licensing validation checks. The vehicle owner's XM radio account is likely already associated with the XM radio module when purchased.

When the XM radio module is plugged into a backplane (FIG. **4**) in the vehicle network **356** or communication subsystem **1008**, the trigger event occurs, and the device discovery daemon **1020** and combo controller commence operation. After device discovery is completed successfully by the device discovery daemon **1020**, the combo controller downloads, from the user's XM account, the user's XM preferences (e.g., favorites) and causes the XM functionality in the vehicle to be configured accordingly. During installation, the combo controller can provide an installation in process dialog the user and, upon successful completion, an installation

complete dialog. After acknowledging that the installation is complete, a new application icon for the XM radio appears in the upper area of the screen of FIG. **30**. The new application icon can have a different appearance than other previously installed application icons to inform the user that the new application is available. When the user launches the new application, the application screen is shown. The application screen of any application depends on the application and user preferences.

The environment **400** of FIG. **4** can interface with three different types of blade processors. A first type of blade processors is installed prior to sale by a manufacturer or vendor. These blade processors are in a manufacturer "crate" and not replaceable or upgradeable by the customer but only by a certified service facility. A second type of blade processors can be installed post-sale by or on behalf of the customer. These blade processors are in a customer "crate". A third type of blade processors interfaces with the first and second type of blade processors. These blade processors are in an accessory "crate". The blade processors generally refer to executable instructions executing on a microprocessor. Each blade typically includes a corresponding set of functions (such as 802.11 WiFi™ interface, Bluetooth™ radio, cellphone radio, storage unit, or satellite position system (such as GPS)), a flash memory, a microprocessor, and a network interface. Typically, the function is software or a combination of hardware and software. Examples include a media controller blade, video controller blade, audio controller blade, profile identification module blade, and the like. This configuration may also be used for a wide variety of other software, such as applications, drivers, and the like, and devices, such as an infotainment system, satellite receiving system, and the like and combinations thereof. For example, an aftermarket infotainment system upgrade or component and/or module can be installed by the customer. The infotainment system upgrade or component and/or module searches for, locates, and connects to a suitable antenna installed prior to sale. The output of the blade processor is an IP message framed into an Ethernet packet. The blade processor can be compatible with the Car Area Network ("CAN") protocol. The CAN control system, which was intended for sensor feedback and controller control signaling through a relatively slow, serial bus, can be integrated into the blade processor architecture by terminating CAN buses in one or more Ethernet bus controllers. The output is configured for a discrete Ethernet-based sensor or controller, with the translation to the CAN protocol being made at a CAN Ethernet controller subsystem.

A "crate" commonly has a backplane connector and on-backplane Ethernet interfaces that enable blade processors to communicate with one another using Ethernet messages. The crate can be a USB hub have a series of ports to permit devices to connect to the USB hub; therefore, each "crate" generally has a corresponding USB hub and ports connected thereto.

A master blade processor can be provided. The master blade processor can be substantially the same as the other blade processors except for scheduling and control functionality. The master blade processor can include a service manager that inventories hardware and software capabilities of components and/or modules available (or connected) through hard wire connections within the vehicle and/or computational devices connected wirelessly to the vehicle local area network (e.g., through a wireless access point or local hot spot maintained by the vehicle control system). The output of the inventory step is a network topology comprising assigned network addresses, component and/or module description and capabilities, operational status, and "next hop" addresses to demonstrate positions of components and/or modules next to one another. An application resource table can be maintained that maps application identity, functional description, and/or application type against computational resource requirements and/or capabilities. Requests to the master blade processor allow various applications to access distributed services or automatically disable features not supported by the vehicle's computer system.

The master blade processor can coordinate a health check for the various components and/or modules in or connected wirelessly to the vehicle's computer system and be responsible for sending a keep alive messages (or status queries or interrogation messages sent at periodic intervals) to the various components and/or modules to evaluate health or identify malfunctions. If no response is received within a predetermined time period after keep alive message transmission, a malfunction is assumed to exist.

For components and/or modules requiring high availability, the master blade processor can create a high availability set with a required number of blade processors. This table controls the priority of which blades are capable of becoming master blade processors in the event of a malfunction of the current master blade processor. Shadow copies of each high availability component (e.g., device) and/or module (e.g., application) are created and maintained for backup purposes in the event of a malfunction of the corresponding active blade processor. High availability applications write all variables to a file created at application initiation residing in vehicle memory. In the event of a malfunction of a high availability application, the master blade processor reassigns the high availability application to a new blade processor. The application can be reinitiated or refreshed or synchronized (using the shadow file) on the newly assigned blade processor. In this manner, the master blade processor is able to redistribute applications to blade processors and/or stopping execution of applications to realize a selected level of performance for the entire vehicle computer system.

A table can be maintained mapping a network address (e.g., a MAC and/or IPv6 address) of each component and/or module against information about the corresponding component and/or module and/or a pointer to a variable file for the component and/or module in memory. Entries on the table may have a corresponding state of health or be added when the corresponding component and/or module passes a health check or removed when the corresponding component and/or module fails to pass a health check.

Upon start up, the master blade processor checks the application resource requirement entries in an application resource table and assigns each application to a blade processor having the most applicable and/or available resources. If an application has specific requirements for execution (e.g., a multimedia infotainment application), the application is assigned to and locked to a specific blade processor (such as a multimedia controller).

An operation of the master blade processor will be discussed with reference to FIG. **38**.

In step **3800**, the blade processor detects a stimulus. The stimulus can be system boot sequence.

In step **3804**, the master blade processor identifies and inventories enabled on board computational resources (such as each blade processor, IP router, vehicle sensors, database management systems, and the like, and the capabilities thereof. On board components and/or modules are typically physically connected to a network bus.

In step **3808**, the master blade processor identifies and inventories enabled portable computational resources and the capabilities thereof. Portable components, such as tablet

computers and smart phones, are typically wirelessly connected, via a wireless access point, to a network bus.

In step **3812**, the master blade processor assigns a network address to each enabled resource.

In step **3816**, the master blade processor maintains and stores the resulting network topology in system data **208**.

In one configuration, a blade processor is not identified as the "master" blade processor prior to system booting. An application executes on a designated blade processor (such as a blade processor handling multimedia system or media subsystem functions) at boot time to detect the presence of a blade processor having specific capabilities. When the blade processor having the specific capabilities is identified, a variable associated with the designated blade processor is changed from "master" to "slave" and the system reboots, thereby transferring system control to the identified master blade processor. A table can be created controlling a priority of which blade processors are capable of becoming master blade processors in the event of master blade processor malfunction. When a master blade processor malfunctions, a next in priority blade processor is selected as the new master blade processor.

An operation of the master blade processor will be discussed with reference to FIG. **39**.

In step **3900**, the master blade processor detects a stimulus. Exemplary stimuli include determining that a component and/or module has failed a health check, receipt of a request for a component and/or module for blade processor resources to execute, and the like.

In step **3904**, the master blade processor determines the requirements for execution of a selected component and/or module, such as set forth in the application resource requirement table. The selected component and/or module can, for example, be a blade processor, software, such as an application, a component, such as a sensor, a satellite receiving system, and the like, and/or a combination thereof

In decision diamond **3908**, the master blade processor, based on the resource inventory output in step **3808**, determines whether a blade processor is available to execute the selected component and/or module. This determination can be done by any number of techniques. It can be based on one or more of a degree of compatibility of the selected component and/or module with each of the blade processor, a current availability of a blade processor to execute the selected component and/or module (e.g., whether the blade processor is currently executing another component and/or module), a relative importance or priority of the selected component and/or module relative to a relative importance of a currently executing component and/or module on a blade processor, whether the blade processor can satisfy the requirements of the selected component and/or module, a current available bandwidth of a blade processor which may be executing another component and/or module, and the like.

In step **3912**, which is performed when a blade processor is available to execute the selected component and/or module, the master blade processor assigns the selected component and/or module to a blade processor for execution. The assignment is recorded in a resource allocation table which maps application identity and/or description against an identifier of the assigned blade processor. If an application has specific requirements for execution (e.g., a multimedia infotainment application or firewall application), the master blade processor may permanently assign the application (or lock the assignment) to a specific blade processor. The master blade processor can, for unlocked assignments, redistribute or reassign components or modules to blade processors or stop components or modules from executing to realize a maximum performance level for the system and/or ensure that critical vehicle, less critical vehicle, or infotainment tasks, functions, or operations are performed.

By way of example, the master blade processor can stop a lower importance or priority component and/or module from executing in favor of a higher importance or priority component and/or module requiring a blade processor to execute. For example, a critical task, function or operation has a higher level of importance or priority than a less critical vehicle task, function or operation. A less critical vehicle task, function or operation can have a higher level of importance or priority than an infotainment task, function or operation or vice versa.

The master blade processor, in next step **3916**, updates the network topology.

In step **3920**, which is performed when a blade processor is unavailable to execute the selected component and/or module, the master blade processor denies the selected component and/or module permission to execute.

When the master blade processor determines that a minimum set of blade processor resources and/or capabilities is not operational, it will send a system reset message to clear operator warning circuitry within an allocated timeframe.

Streaming of Media

An integrated circuit board configuration can be provided to enable media streaming to computational devices wirelessly connected to the vehicle network via an access point **456** of the vehicle. In this manner, different media can be provided simultaneously to different user interfaces (e.g., on board display subsystems) of different vehicle occupants.

FIG. **21** depicts a configuration of the media controller subsystem **348** for simultaneously streaming multiple channels of media (e.g., multimedia or infotainment content). Media content **2100**, such as audio, video, picture, and/or text media, is received by the network transceiver **824** and provided to a common media processing board **2104**. The processing board **2104** comprises a network control server **2108**, such as a distributed network control ("DNC") server, a media server **2112**, such as a digital living network alliance ("DLNA") server, and virtual network console ("VNC") software **2116**. The network control server **2108** has an IP address and/or a routable, global unicast address while the media server has a contactable electronic address (such as a media access control or MAC address) on the vehicle network **356** or communication subsystem **1008**.

As will be appreciated, each of the network control and media servers **2108** and **2112** comprise a microprocessor and memory to buffer media content, execution of application programming, long term storage of program instructions and/or data, and the like, In one application, the media server **2112** comprises functionality of the media controller **804**, media processor **808**, and signal processing module **828**.

A user portable (remote) or Bring Your Own Device (BYOD) computational device **2120** is in wireless or wired communication with the board **2104**, such as via a wireless protocol (e.g., Bluetooth™, WiFi™ and the like). The VNC software **2116** effectively provides the remote computational device **2120** (e.g., portable communication device) with remote access to the board **2104**, which is typically part of the vehicle on board computer (e.g., the console computer). As will be appreciated, the VNC software can operate in accordance with the RFB (Remote Frame Buffer) protocol on top of the TCP/IP suite of protocols. The result is that the remote computational device appears to the on board computer as if it were part of the on board vehicle computer or vehicle control system **204**. This enables the remote computational device to provide commands to the media controller subsystem **348** for desired multimedia content and media pre-

sentation features and settings (such as volume, contrast, resolution, channel selection, and the like). In some applications, the remote computational device must download an application from the vehicle to enable multimedia requests from the remote computational device to pull information from the multimedia controller, where the media can be streamed to its final destination. The commands are provided, by the VNC software **2116** indirectly to the media server **2112** for delivery to the network control server **2108** or directly to the network control server **2108**, which retrieves the requested content from an external network (e.g., an Internet or radio network) accessible source. The media may then be provided to a display at the seat position of the user and/or to the BYOD computational device **2120** (via the wireless access point). When the requested media content is available locally (already stored in vehicle memory), the media content is provided from local storage in preference to accessing the media content via the Internet. When the requested media is not available locally, it is obtained via the Internet and is cached in local storage in parallel with streaming to the user's display and/or BYOD computational device **2120**. Each display at each seat position can independently provide a corresponding user with a playlist of audio or video from independent sources.

With reference to FIG. **22**, the operation of the media controller subsystem **348** will be discussed. In step **2200**, the VNC software **2116** receives a command or request for content from the user of the BYOD computational device. The device has been previously connected successfully by the device discovery daemon or combo controller to the vehicle network **356** or communication subsystem **1008**.

Typically, the combo controller has ports in the crate, implements certain device discovery functions, and packetizes information for transmission via IP over Ethernet. The combo controller commonly installs the correct driver for the discovered device. It then maps the device (e.g., USB) address to a local TCP/IP address for interaction with one of the blade processors.

In step **2204**, the media server determines, from the system data **208**, portable computational device information and capabilities, the identity of the user of the device, an identity of the portable computational device associated with the user, and/or the spatial location of the device (e.g., area and/or zone in which the device is located). This information has been previously determined by the device discovery daemon or combo controller but may be updated by the media server using the location techniques discussed above.

In step **2208**, the media server applies appropriate filters and restrictions based on the identity of the user (e.g., user account) and/or spatial location of the device (e.g., user context). The filters or restrictions can include, for example, age-related content filters and/or restrictions, seating location filters and/or restrictions, and privacy filters and/or restrictions. The filters and/or restrictions can ban the type of content requested or the source of the content (e.g., a blacklist of web sites), redirect the request to a different source of the content, and/or limit the user to content from approved sources, such as permitted by a whitelist. Other user account restrictions can be applied by the media server before the content request is passed to the network control server **2108**.

The owner of the vehicle can configure the multimedia controller menus. Initially, the menu allows for all seat positions to access any media that is available through the multimedia controller. The owner can create profiles for different potential vehicle occupants. By creating the profiles, the owner is able to allow or disallow access to media from selected seat positions, including access to media menus (e.g., audio or video playlists, software applications (such as Internet browsers, applications to control passenger compartment climate control functions, games, and the like). The owner can also limit media and/or media menu access based on a MAC address of a computational device **2120** of an occupant. Only devices having a permitted MAC address can access media and/or menus while those not having a permitted MAC address cannot. This can ensure that control is not only position-based but also device-based.

In step **2212** and if permitted by the media server, the network control server **2108** accesses the filtered content request (which may be altered to reflect user account restrictions) and retrieves the permissible content via the public network. The network control server **2108**, for example, can access the media content **2100** from a media source accessed through an external network, such as a radio network or other type of untrusted public network (such as the Internet). The filtered content request may, for example, be for different content than that originally requested, differently formatted content than that originally requested, differently sourced content (e.g., from a different web server or site) than that originally requested, and the like.

In step **2216**, the network control server **2108** receives the permissible content from a publicly networked source (e.g., web server or site) and passes the retrieved content to the media server **2112**. Based on user account restrictions and/or user context, the media server applies appropriate filters and restrictions to remove or filter out inappropriate content. The filters or restrictions can include, for example, age-related content filters and/or restrictions, seating location filters and/or restrictions, and privacy filters and/or restrictions.

In one application, the combo controller connects via IP over Ethernet and assigns a local IP address to the BYOD device connected to a port in the consumer crate. The USB layer of the combo controller packetizes information from the BYOD device and communicates with a USB access program that executes on a multimedia blade processor. The USB access program de-packetizes the information and connects to the USB I/O subsystem of the multimedia blade processor to transfer the information to either local storage or directly to one of the output devices associated with the appropriate seating position.

Other user account restrictions can be applied by the media server before the content is passed by the media server to the user. For example, when the user is driving the vehicle video can be removed automatically from the content to avoid distracting the driver so that only the audio channel accompanying the video channel is provided to the user. In another example and in response to determining that the requesting user or user is driving the vehicle rather than being a (non-driving) passenger, screen magnification can be applied automatically to the visual content to assist the driver of the vehicle; that is, the user is the driver and larger font is easier to see than smaller font. In other examples, the visual content, in response to determining that the requesting user or user is driving the vehicle rather than being a (non-driving) passenger, is presented or rendered automatically in a large font and/or icon size (e.g., without changing screen resolution) compared to the font and/or icon size for the content displayed to a (non-driving) passenger to reduce driver distraction. In yet another example, the media server **2112** determines that the user is driving the car rather than being a (non-driving) passenger and enables or disables automatically removal of all unnecessary animations from the content to be displayed. In yet another example, the media server **2112** determines that the user is driving the car rather than being a (non-driving) passenger and enables automatic

removal of background images from, while leaving one or more displayed foreground images in, the content to be displayed. In yet another example, the media server **2112** determines that the user is driving the car rather than being a (non-driving) passenger and automatically enables or renders high contrast (e.g., between text and background colors) to make the displayed content more visible to the user. The feature and/or setting and/or filters could be applied to the displayed content only when the vehicle is in motion or in forward or reverse gear and not parked even when the user is the driver.

Rather than automatic detection, any of the above features and/or settings and/or filters can be a standard feature and/or setting and/or filter and can be applied to the on board vehicle display for the driver but not to the on board vehicle displays of other (non-driving) passengers. In other words, the feature or setting or filter would not be applied to the on board vehicle display of a (non-driving) passenger. Alternatively, the feature and/or setting and/or filter would be applied to the on board vehicle display for the driver only when the vehicle is in motion or in forward or reverse gear but not when the vehicle is parked.

In step **2220**, the media server **2112** configures the filtered media for the capabilities of the user device and/or on board vehicle display and in accordance with user preferences. The media server **2112** directly provides, or streams, the media stream or indirectly provides, or streams, the media stream via the VNC software **2116** to the user computational device **2120** and/or on board vehicle display for presentation to the user. Stated another way, the network control server **2108** provides the media content **2100** while the media server **2112** provides the channel for the media content **2100** to be provided to the user computational device **2120**.

The media controller subsystem **348** can handle multiple (e.g., eight or more) media and/or multimedia streams simultaneously by differing channels. The streams of information may be separated and served on different channels via one or more of WiFi, Bluetooth, NFC, and other communications protocols. Multiple BYOD computational devices can be served simultaneously and can mix and match or otherwise control what is streamed and where it is streamed.

Assisted Driver Display

The device or user interface **212**, **248**, user interface (s)/input interface(s) **324** and/or I/O module **312** (such as the on board display for the driver) can be reconfigured when the vehicle changes state from parked or substantially motionless to be in motion or in forward or reverse gear to facilitate the driver's ability to view visual content and avoid driver distractions. Other devices or user interfaces **212**, **248**, user interface (s)/input interface(s) **324** and/or I/O modules **312** of other vehicle occupants or passengers typically are not reconfigured even when the vehicle is in gear or motion. When the state of the vehicle changes to parked (or not in motion), the device or user interface **212**, **248**, user interface (s)/input interface(s) **324** and/or I/O module **312** of the driver returns to a different configuration, which is typically the same configuration as the devices or user interfaces **212**, **248**, user interface (s)/input interface(s) **324** and/or I/O modules **312** of other vehicle occupants or passengers.

There are a number of reconfigurations that may be implemented for the unimpaired driver's device or user interface **212**, **248**, user interface (s)/input interface(s) **324** and/or I/O module **312** in response to a change of state of the vehicle, particularly from parked or stationary to be in motion or in forward or reverse gear.

For example, the media controller subsystem **348** can remove video automatically from the content to be displayed by the device or user interface **212**, **248**, user interface (s)/input interface(s) **324** and/or I/O module **312** of the driver to avoid distracting the driver so that only the audio channel accompanying the video channel is provided to the user. A still image derived from one or more frames of the video content can replace the video component in the displayed content.

In another example, the media controller subsystem **348** applies screen magnification automatically to the visual content to assist the driver of the vehicle; that is, the user is the driver and larger font is easier to see than smaller font. The screen magnifier is software that interfaces with a computer's graphical output to present enlarged screen content. The simplest form of magnification presents an enlarged portion of the original screen content, the focus, so that it covers some or all of the full screen. This enlarged portion should include the content of interest to the user and the pointer or cursor, also suitably enlarged. As the user moves the pointer or cursor the screen magnifier should track with it and show the new enlarged portion.

In another example, the media controller subsystem **348** presents or renders the automatically in a large font and/or icon size (e.g., without changing screen resolution) to reduce driver distraction. The large font and/or icon size, unlike screen magnification, applies to all, and not simply a portion of, displayed content.

In yet another example, the media controller subsystem **348** initiates automatically a screen reader (or other text-to-speech program) to audibly provide the visual content to the user. A screen reader is a software application that attempts to identify and interpret what is being displayed on the screen (or, more accurately, sent to standard output, whether a video monitor is present or not). This interpretation is then represented to the user with text-to-speech and/or sound icons. Screen readers can be used in combination with the screen magnifier to read the content within the enlarged portion of the screen content.

More specifically, screen narration in vehicle can describe the layout of a current display, including a current position, page, functionality, etc., of displayed content and the position of a digit of the user and/or cursor relative to displayed objects. The names of the displayed objects in proximity to the current digit and/or cursor location can be audibly identified. In another example, a user can identify a displayed object to be located and the media controller subsystem **348** can use "hotter", "hot", "colder", and cold" game to inform the user where his or her digit and digit movement is relative to the identified object. For example, the media controller subsystem **348** can tell the user that "you're getting warmer" as the user's digit moves closer to the identified object.

In yet another example, the media controller subsystem **348** determines that the user is driving the car rather than being a (non-driving) passenger and enables or disables automatically remove all unnecessary animation effects such as fading effects (e.g., fade windows), from the displayed content.

In yet another example, the media controller subsystem **348** automatically removes background images from the displayed content while leaving one or more displayed foreground images. The removed background image can be replaced with a uniform background, such as a commonly colored or white background.

In yet another example, the media controller subsystem **348** enables automatically a longer (than normal) period for notification dialog boxes to stay open on the display.

In yet another example, the media controller subsystem **348** automatically disables automatic arrangement of windows when the mouse cursor is moved to the edge of the screen.

In yet another example, the media controller subsystem **348** automatically enables activate a window by hovering over it with the mouse cursor.

In yet another example, the media controller subsystem **348** automatically enables keyboard web page navigation.

In yet another example, the media controller subsystem **348** automatically enables or renders high contrast (e.g., between text and background colors) to make the displayed content more visible to the user.

In yet another example, the media controller subsystem **348** automatically changes the color and transparency of window borders (making the borders easier to see).

In yet another example, the media controller subsystem **348** automatically changes the thickness of focus rectangle (around the currently selected item in a dialog box).

In yet another example, the media controller subsystem **348** automatically changes the color, size, and/or thickness of the on-screen mouse pointer.

In yet another example, the media controller subsystem **348** automatically changes the keyboard settings (e.g., select how long you need to press a key before the keyboard character starts repeating, the speed at which keyboard characters repeat, and the rate at which the cursor blinks, etc.).

In yet another example, the media controller subsystem **348** automatically ignores colors, font styles and font sizes used on web pages, or formats web pages using a user specified or default style sheet.

In yet another example, the media controller subsystem **348** automatically enables or renders in the content an increased size of a mouse-selectable screen element or object to provide a larger target.

In yet another example, the media controller subsystem **348** automatically enables mouse keys to move the mouse pointer or cursor.

In yet another example, the media controller subsystem **348** automatically enables one or more of sticky keys (which allow the user to enter a combination of multiple keys without having to hold a first key down when he or she depresses a second key), toggle keys (which play an alert each time the user presses Caps Lock, Num Lock, or Scroll Lock keys), and filter keys (which causes the computer to ignore keystrokes that occur in rapid succession or keystrokes held down for several seconds unintentionally).

In yet another example, the media controller subsystem **348** automatically causes the driver's device or user interface **212**, **248**, user interface (s)/input interface(s) **324** and/or I/O module **312** to be configured to enable blind typing. In blind typing, the driver can write naturally with a finger on the interface and the interface can determine, from the natural written script, a command or request of the driver. This configuration typically requires the interface to be configured as a touchpad. While other systems require the driver to focus away from the road—either by selecting letters from menus or on a displayed keyboard—blind typing permits the driver to input commands or requests to the vehicle control system without having to visually focus on any screen.

Although many of the above display changes or reconfigurations have been used to enable impaired users to access a computer, the driver is typically not disabled or impaired (e.g., not visually impaired or disabled). These changes or reconfigurations can however be highly beneficial in enabling a driver to interact with the computer in a manner that substantially avoids or inhibits driver distraction.

Rather than automatic detection, any of the above features and/or settings and/or filters can be a standard feature and/or setting and/or filter and can be applied to the on board vehicle display for the driver but not to the on board vehicle displays of other (non-driving) passengers. In other words, the feature or setting or filter would not be applied to the on board vehicle display of a (non-driving) passenger. Alternatively, the feature and/or setting and/or filter would be applied to the on board vehicle display for the driver only when the vehicle is in motion or in forward or reverse gear and not when the vehicle is parked.

A user interface (UI), such as the driver's device or user interface **212**, **248**, user interface (s)/input interface(s) **324** and/or I/O module **312**, may be provided that includes an area for navigation by a user. As a user navigates the UI area, the user may be provided with one or more of sounds, audio narration, haptic/tactile feedback, visual indicator (e.g., not associated with the UI), and the like. For example, a location in the UI area may represent a button and/or other icon. When the user makes contact with the location having the button, a sound and/or tactile feedback may be presented to the user to indicate where the user's pointer (e.g., one or more finger, hand, etc.) is located. As one example, as a user reaches a location in the UI area associated with a "call" button, the sound presented may be a ring (e.g., a bell), and a vibration may be provided to the UI. Alternatively, screen narration by a screen reader can be provided, which informs conversationally the user where his or her digit is located. For example, the narration can be to recite the name corresponding to the button. In another example, as a user moves a pointer about the UI area, a frequency of sound may change to indicate a position in the UI area (e.g., the low left portion of the UI area may provide a low pitch and/or frequency sound, while a position in the upper right portion of the UI area may have a higher pitch and/or frequency sound, and portions in between can have different pitches and/or frequencies, etc.—similar to the Theremin musical instrument).

By way of example, a graphical UI or GUI may allow a user to interact with certain displayed buttons, features, and/or menus while a vehicle is stationary, but may restrict access and/or interaction when the vehicle is moving. One example of this restricted interaction involves greying-out buttons associated with an associated phone feature when the vehicle moves. In the embodiments provided herein, the display can be completely turned off or blanked out when moving and a user may still be able to interact with features. Because the user will not be distracted by the visual presentation of elements the user is free to drive while interacting.

In some embodiments a GUI may be used where a display of the GUI is turned off to provide the above described functionality.

A display navigation mode can be selectively triggered by the user to implement any of the above configurations and/or features. When the user wishes to enter display navigation mode, the user can provide a command, such as by voice or gesture, to enter that mode. In that mode, any of the above assistive configurations or features can be implemented. For example, voice navigation is activated and the residence time of the user's touch on the touch screen required to select a contacted icon is lengthened to avoid incidental or accidental icon selection as the user moves his or her hand/digit around the touch screen. When the user arrives at a desired location, the icon will be activated after touch contact for the longer residence time. When the icon is selected, the touch screen can return to normal operating mode with a shorter residence time for icon activation.

The user can alternatively use a roller or track ball and selector to effect narrated screen navigation.

In another embodiment, the user contacts an arbitrary and substantially planar or flat control surface, such as an arm rest, dash, steering wheel, glove box door, center or rear center console, window (e.g., windshield), passenger compartment roof, seat surface, door panel, or other electrically, magnetically, electromagnetically, and optically nonreactive surface to activate icons on the activated or deactivated vehicle computer center or rear center display. The control surface can be any arbitrary surface selected by the user. This can be done by optically or visually separating the surface into segments, each segment corresponding to a segment on the display. The movement of the user's hand or digit is tracked optically over the surface with reference to the segments. As the user moves his or her hand, the user can be audibly told where his or her hand is relative to the display. When the user's hand/digit is at a selected location, the user can leave his or her hand/digit at that location for a selected residence time to cause the icon in the corresponding segment of the display to be activated.

The activated or deactivated vehicle computer center or rear center display can be any of the driver's device or user interface **212**, **248**, user interface (s)/input interface(s) **324** and/or I/O module **312**, may be provided that includes an area for navigation by a user.

An example is described with reference to FIGS. **33-34**. FIG. **34** depicts the display of FIG. **30** with defined segments overlaid on the display. This is done to show the process of mapping the control surface to the displayed objects. FIG. **33** shows the same defined segments positioned on the control surface **3300**. Each segment of the control surface **3300** corresponds to an information-containing and/or activatable or selectable object of the current display. As the display changes in response to user input or otherwise, the type, identity, and/or arrangement of displayed information and objects changes requiring the display to be remapped to the control surface **3300**. Remapping typically requires the defined segments to be redefined and reconfigured to reflect the new display configuration.

As shown by FIG. **33**, the dividing lines define various cells, each of which corresponds to displayed content on the display of FIG. **34**. Specifically, cell **3304***a* corresponds to display field comprising driver name **3028**, cell **3304***b* to satellite reception indicator **3032**, cell **3304***c* to WiFi connectivity indicator **3034**, cell **3304***d* to cellular connectivity indicator **3036**, cell **3304***e* to display field comprising weather information **3038**, cell **3304***f* to display field comprising date **3040**, cell **3034***g* to icon **3380**, cell **3034***h* to navigation ("Nav" icon) **3016**, cell **3034***i* to media ("Media" icon) **3018**, cell **3034***j* to phone ("Phone" icon) **3020**, cell **3034***k* to rear view ("Rear View" icon) **3022**, cell **30341** to other applications icon **3024**, cell **3034***m* to icon **3384**, cell **3034***n* to "my dash" icon **3026**, cell **3034***o* to navigation display field **3088**, cell **3034***zz* to suggested icon, cell **3034***p* to set destination icon, cell **3034***q* to display field containing destination, cell **3034***r* to display field containing suggested waypoint, cell **3034***s* to display field containing suggested waypoint, cell **3034***t* to set destination icon, cell **3034***u* to set destination box, cell **3034***v* to favorites icon, cell **3034***w* to recent locations, cell **3034***x* to people icon, cell **3034***y* to points of interest icon, cell **3034***yy* to set waypoints, cell **3034***z* to set waypoints box, cell **3034***aa* to go icon, cell **3034***bb* to calendar icon **3092**, cell **3034***cc* to weather icon **3096**, cell **3034***dd* to display field containing appointment, cell **3034***ee* to display field containing appointment, cell **3034***ff* to display field containing appointment, cell **3034***gg* to display field containing appointment, cell **3034***hh* to display field containing appointment, cell **3034***ii* to display field containing appointment, cell **3034***jj* to display field containing weather information, cell **3034***kk* to display field containing weather information, cell **3034***ll* to display field containing weather information, cell **3034***mm* to display field containing weather information, cell **3034***nn* to display field containing weather information, cell **303400** to display field containing weather information, cell **3304***pp* to friends icon, cell **3304***qq* to received and/or sent messages **3068**, cell **3304***rr* to received and/or sent messages **3068**, cell **3304***ss* to received and/or sent messages **3068**, cell **3304***tt* to received and/or sent messages **3068**, cell **3304***uu* to received and/or sent messages **3068**, cell **3304***vv* to received and/or sent messages **3068**, cell **3304***ww* to icon **3098**, cell **3304***xx* to a climate control icon ("Climate" icon), cell **3304***aaa* to a controls icon ("Control" icon) to control vehicle tasks, functions or operations **3062**, cell **3304***bbb* to speaker volume setting **3064**, cells **3304***ccc* and *ddd* to controls to the left and right of the speaker image **3066** and **3070**, respectively, and cell **3304***eee* to speaker icon.

By way of example, the user's digit points at **3304***h*, which corresponds to the navigation icon **3016** of the home page **3000** of FIG. **30**. By leaving the user's digit stationary in that location for a selected period of time, the media controller subsystem **348** determines that the user desires to activate the navigation icon **3016**, which causes a different display to be rendered. The new display is remapped to the control surface so that the dividing lines on the control surface mirror the dividing lines overlain on the new display. By way of further example, the user's digit points at **3304***f*, which corresponds to the display field for date and time of the home page **3000** of FIG. **30**. A screen reader reads the date and time to the user. By way of further example, the user's digit points at **3304***dd*, which corresponds to the display field for appointment of the home page **3000** of FIG. **30**. A screen reader reads the displayed appointment information to the user.

Optical tracking of the user's digit enables the location of the digit. Optical tracking typically determines in real-time the position of the digit by tracking the positions of either active or passive infrared markers attached to the object. The position of the point of reflection is determined using the camera sensors **760**, motion sensors **744**, and/or infrared sensors **740**. In one configuration, the user's digit is equipped with markers. Markers can be light reflectors ("passive markers", e.g. retroreflectors) or light emitters ("active markers", e.g. LEDs). To also measure the orientation of a body, several (greater than or equal to 3) of these markers have to be arranged at a known geometry. The camera sensors **760** scan a certain volume and detect the light that comes from the markers. These images are processed to identify and calculate potential marker positions (in image coordinates). The result of each measurement are coordinates that describe the position of the markers, and hence the position and orientation of the body carrying the markers.

Other techniques can be employed. The cell dividing lines can be projected onto the control surface by the camera sensors **760**. The position of a selected digit of the user can be tracked using image processing of images of the control surface with the cell boundary or dividing lines in the images. Examples of other techniques include video tracking, such as blob tracking, kernel-based tracking, contour tracking, visual feature matching, match moving, motion capture, motion estimation, Swistrack, and single particle tracking.

The operation of the control surface will be discussed with reference to FIG. **35**.

In step **3500**, the media controller subsystem **348** detects a stimulus, such as ignition of the engine, motion of the vehicle,

the vehicle being placed in gear, a gesture or other activation command from the user, and the like.

In response, the media controller subsystem **348**, in step **3504**, maps the current display of a selected one of the driver's device or user interface **212**, **248**, user interface (s)/input interface(s) **324** and/or I/O module **312** to a selected control surface. This can include proportional sizing the control surface to the display and determining cell and cell boundary locations. The sizes of the cells are commonly proportional to the corresponding displayed content.

In step **3508**, the media controller subsystem **348** determines, by one or more of the motion sensors **744**, infrared sensors **740**, and camera sensors **760**, whether a user's digit has moved relative to the stationary cell boundaries and cells on the mapped control surface.

When movement is detected, the media controller subsystem **348**, in step **3512**, detects or determines, by one or more of the motion sensors **744**, infrared sensors **740**, and camera sensors **760**, the position of the digit on the control surface relative to the cells and cell boundaries.

In step **3516**, the detected position of the digit is mapped to the currently displayed content. This is done by mapping the cell where the tip of the digit is positioned to the corresponding displayed content on the display.

In step **3520**, the media controller subsystem **348** performs an action based on the detected digit position. The action depends on the type of displayed content corresponding to the digit position. When the displayed content is activatable or selectable, the media controller subsystem **348** activates the corresponding task, function or operation. When the displayed content is not activatable or selectable, a screen reader in the media controller subsystem **348** reads the displayed content to the user. Some operations are drag-and-drop operations where content is moved by the user's digit from one location to another, such as a destination or waypoint being dragged from one location and dropped into a set destination or wet waypoint box. This can be done by detecting the user's digit in a first location, determining that the displayed content can be dragged and dropped to another location, waiting for the digit to move to a second location, and, when in the second location, dropping the content into displayed content corresponding to the second location when the displayed content permits this operation to be performed.

As noted, when the task, function or operation causes the display to change the control surface is remapped to the display.

In another embodiment, the UI may not include any display at all. Because any surface can receive input, as provided herein, a display is not needed. Examples of this type of display-less UI can be implemented on any surface that has a substantially flat or planar area or surface. In one embodiment, the UI area may include a capacitive and/or resistive touch interface region. In another embodiment, the UI area may be a surface that includes an area visible from at least one image sensor (e.g., camera, etc.). Other examples of a display-less UI may include a volume of space in which a user can move a pointer.

In the examples provided above, a user may navigate the non-displayed UI elements (e.g., icons, buttons, etc.) using sound, haptic feedback, etc.

An operation of the media controller subsystem **348** will now be described with reference to FIG. **26**.

In step **2600**, a stimulus is detected by the media controller subsystem **348** based on input from one or more vehicle sensors. An exemplary stimulus includes a change in vehicle operating state. Common changes in vehicle operating state include a change from "parked" to "forward gear" and vice versa, from "parked" to "reverse gear" and vice versa, from "forward gear" to "reverse gear" and vice versa, and from stationary to in motion and vice versa.

In decision diamond **2604**, the media controller subsystem **348** selects a device or user interface **212**, **248**, user interface (s)/input interface(s) **324** and/or I/O module **312** and determines whether or not it is associated with the driver. This is typically determined by determining whether or not the selected device or user interface **212**, **248**, user interface (s)/input interface(s) **324** and/or I/O module **312** is located in an area and/or zone occupied by the driver. Location of the device or user interface **212**, **248**, user interface (s)/input interface(s) **324** and/or I/O module **312** can be determined using the techniques noted above.

When the device or user interface **212**, **248**, user interface (s)/input interface(s) **324** and/or I/O module **312** is located in the area and/or zone of the driver, the media controller subsystem **348**, in step **2608**, reconfigures the user interface to enable or disable (depending on the initial and final states) one of the features, settings, or filters discussed above.

When the device or user interface **212**, **248**, user interface (s)/input interface(s) **324** and/or I/O module **312** is not located in the area and/or zone of the driver, the media controller subsystem **348**, in step **2608**, does not reconfigure the user interface to enable or disable (depending on the initial and final states) one of the features, settings, or filters discussed above.

After performing either of steps **2608** or **2612**, the media controller subsystem **348** selects a next device or user interface **212**, **248**, user interface (s)/input interface(s) **324** and/or I/O module **312** and returns to decision diamond **2604**.

This process is continued until all devices or user interfaces **212**, **248**, user interface (s)/input interface(s) **324** and/or I/O modules **312** have been considered.

In other embodiments, the media controller subsystem **348** can audibly warn of or describe an image detected via an infrared sensor, motion sensor or camera sensor that is in the path of the vehicle. Known image processing and image recognition techniques can be used to identify the object image and compare the image to a projected path of the vehicle. An exemplary technique acquires the image, preprocesses the acquired image, performs feature extraction from the pre-processed image, performs detection and/or segmentation using the extracted features, and performs high level processing and decision making. The path of the vehicle, as determined by a steering wheel setting and a projected path of the center line of the vehicle for that setting along with a width of the vehicle can be compared against the position of the object. When the projected path causes any portion of the vehicle to contact the object or be within an unsafe distance of the object, appropriate instructions or warnings can be issued. Thus, not only can a warning containing the object description be provided to the driver but also directions can be audibly provided to enable the driver to miss the object. For example, the driver can be instructed by one or more of the following: "Watch Out!"; "Turn the wheel left, a little more, a little more, perfect, straighten out"; "Turn the wheel right, a little more, a little more, perfect, straighten out"; and the like. This can provide invaluable assistance to driver's who struggle, for example, with backing up the vehicle due to depth perception and/or orientation issues.

User Account Management and Occupant Control of Vehicle Tasks, Functions and Operations

The vehicle control system **204** can manage user accounts that stipulate, control, and define rights and privileges of each user of the vehicle and vehicle network. Different users and/

or devices may include different accounts. In some cases these accounts may include user and/or device-specific privileges.

For example, a system user has exclusive rights and privileges over all communication device firewall rules and running software. The system user can control selected vehicle tasks, functions and operations and infotainment via predetermined or preconfigured gestures. A manufacturer or vendor user can have local or remote access to on board control system data and alter the parameters and settings in the vehicle control system and to perform diagnosis and repair. A dashboard user can have rights to launch a dashboard application and authenticate guest or default users and change permissions to trusted friends or family members. Dashboard users can read on board diagnostic system data but cannot overwrite or change it. A user can be both a system and dashboard user. An Internet source interacting with the vehicle has only http rights to respond to http requests received from the vehicle. The requests can target different user data but these are filtered by default user accounts. Guest users have no rights. Family and friend users have rights to play media from the media controller and to stream its media to the controller. They may or may not have rights to control vehicle tasks, functions and operations, whether or not by gesture. The back seat displays are part of this group of users. The back seat displays can be smart WiFi removable communication devices that can be removed from the vehicle in WiFi range of the communication network.

In one example, a child user may wish to change the temperature in his zone of the vehicle. Continuing the example, the child may have an account that allows access to this feature (but not other more critical features). As such the child may change the temperature via the device or other control. The child, however, may not be entitled to change the feature for an area or zone other than that in which he or she is currently located. Additionally or alternatively, a driver may have a broader account and privileges. In this case, the driver may control critical features, and even tasks, operations, and functions, of a vehicle. Remote control of a vehicle or infotainment task, operation, or function through the on board vehicle computer and by a portable or handheld computational device, such as a cellular phone or tablet computer, interconnected with the vehicle computer, can be permitted for some users but not others. For example, a privileged user can control an infotainment or climate control function on the dashboard from the back seat of the vehicle. The control of the vehicle or infotainment task, function, or operation may be made via a device or user interface **212**, **248**, user interface (s)/input interface(s) **324** and/or I/O module **312**. Accordingly, occupant control of a (typically non- or less critical) vehicle task, function, or operation (such as an infotainment task, function or operation) can be done using an on board (or vehicle mounted) computational device or a portable computational device discrete from and not mounted on the vehicle.

In another example, a user in the rear passenger seat of a vehicle may wish to take control of specific features that are allowed in that zone. Such features may include controlling the climate, changing a radio station or infotainment presentation, opening a window, setting a volume level, setting a screen contrast and/or resolution, and/or adjusting a seat position. The control of these features may be provided to the user in the rear passenger seat via a display, gesture control region, or other device associated with the zone in which the rear passenger is seated. Associated devices may include the user's smart-phone, tablet, computer, and/or other device.

In yet another example, a vehicle occupant can perform a first set of vehicle tasks, functions and operations when in a first area and/or zone and a different set of vehicle tasks, functions, and operations when in a different second area and/or zone. For instance, a vehicle occupant can drive the car or perform another critical vehicle task, function or operation when seated in the driver's seat but not when seated in a different seat. When the vehicle occupant is in the back seat, he is unable to be a back seat driver of the vehicle or perform another critical vehicle task, function or operation.

In yet another example, a vehicle occupant can perform a first set of vehicle tasks, functions and operations when the vehicle is in a first operating state and a different set of vehicle tasks, functions, and operations when the vehicle is in a second operating state. The vehicle occupant, for instance, can watch a video on the driver's center console or display subsystem when parked and/or the vehicle is stationary (not in motion) but cannot watch the video on the driver's center console or display subsystem when the vehicle is in gear and/or motion.

In yet another example, a different authentication procedure is used for the vehicle occupant when requesting a first set of vehicle tasks, operations, and functions than when requesting a second set of vehicle tasks, operations, and functions. When the vehicle occupant is entitled to drive the vehicle or perform another critical vehicle task, function or operation, a different and higher or more stringent set of authentication requirements can be required than when the vehicle occupant is not entitled to drive the vehicle. For instance, multiple authentication techniques may be used in the former case but only one in the latter case.

As noted, the vehicle control system **204** manages user accounts, which contain user credentials, such as user identifiers, passwords, user biometric data (e.g., fingerprints, retina images, facial characteristics, user weight, and other physical characteristics), and rights and privileges of the user in performing vehicle tasks, functions, and operations, both critical and non-critical. In addition to the rights and privileges defined in the user account, the vehicle control system **204** can consider additional gating or filtering factors, such as current user position (e.g., what area and/or zone the user is located or seated in), in determining what rights and privileges apply currently to the user.

The vehicle control system **204** can manage and enforce accounts for authenticated and non-authenticated users. Each account specifies rights and privileges for the corresponding user and/or security/authentication requirements and/or personal settings of the user (such as seat and lumbar settings, climate control settings, lighting settings, configuration of instrument cluster, rear view mirror settings, driving modes (such as fuel economy, sport, city, and the like), media channel settings or presets, media delivery preferences, music genre preferences, scheduled programs, playlists, synchronization with cloud-based data associated with the user (such as iCloud™ of Apple™, Outlook™, and the like with examples of cloud-based data being electronic calendar, email, contacts, media content, texts, voice mail messages, and the like), application-specific personalization and selections, display settings and configurations, and the like) and other information noted above with respect to the profile data **252** and device data **220**. These will be henceforth encompassed by any reference to a user's account.

For example, an owner of the vehicle would have the right and privilege not only to access infotainment media but also to access and control critical and non- or less critical vehicle tasks, functions, and operations. Because he is entitled to the highest level of rights and privileges, his or her authentication

requirements may be more demanding than another vehicle occupant not having such rights and privileges. A child of the vehicle owner on the other hand would have a very restricted or no right to access and control vehicle tasks, functions, and operations (except for climate control, seat, and/or window settings) and restricted rights to access infotainment media. As noted above, a child filter could be configured by the vehicle owner to prevent the child from accessing age-restricted media.

A guest of the vehicle owner having no corresponding account would be provided with a default account having default and restricted rights and privileges to access vehicle and infotainment tasks, functions, and operations, and settings and configurations, which could be expanded based on input from the owner. This could be done in response to a query by the vehicle control system **204** that the vehicle occupant is not recognized (or authenticated). The vehicle control system **204** could provide the owner with multiple default accounts, one for an adult with driving privileges, one for an adult without driving privileges, and one for a child, and request the owner select the appropriate default account for the occupant. An identifier of the occupant and optionally authentication credentials would be inputted by the owner, and the vehicle control system **204** could store image processing information of the occupant's facial or other image, biometric information, and/or occupant weight for purposes of authentication. The owner could define, in an account created or modified by the owner, the rights and privileges of the person associated with the account.

An operation of the vehicle control system **204** is shown in FIG. **27**.

In step **2700**, the vehicle control system **204** detects a stimulus, such as a driver prompt, presence of an occupant, and the like. As noted above, the presence of an occupant can be sensed by seat weight sensors, image processing analysis, motion detection, proximity of a key fob, and/or biometric information.

In decision diamond **2704**, the vehicle control system **204** determines whether or not each of the vehicle occupants has been authenticated successfully. Authentication can be performed by any suitable technique and using any suitable input, such as by one or more of receiving and validating user credentials, sensing an occupant's weight in a seat (with the weight being different from weight ranges predefined for each known occupant), image processing performed on the facial characteristics of the various vehicle occupants (and comparing the sensed facial characteristics against those for known occupants), biometrics (such as a fingerprint image of the occupant sensed by the occupant touching a touchscreen display, retinal scan, heart rhythm as received by conductive elements on a vehicle component such as the steering wheel or gear shift) (which are compared against corresponding stored biometrics for known occupants), and the like. An unauthenticated occupant could be recognized by sensing an occupant's weight in a seat (with the weight being different from weight ranges predefined for each known occupant), image processing performed on the facial characteristics of the various vehicle occupants (with the sensed facial characteristics failing to match stored facial characteristics for known occupants), unrecognized biometrics (which do not correspond to biometrics for known occupants), and the like.

Authentication using image processing applied to video images of occupants in the vehicle can be performed by any suitable technique. In one technique, facial recognition occurs in two stages, namely face detection and recognition. The face detection stage attempts to obtain an acceptable image from the video stream of the vehicle occupants to use in the face recognition stage. The face recognition process uses the image obtained from the detection stage and compares it with a database of known faces. When the facial image obtained from the detection stage matches a known stored facial image, authentication is successful. When the facial image obtained from the detection stage fails to match a known stored facial image, authentication is unsuccessful. As noted, image processing can be augmented by other security mechanisms for higher level privileges, such as authentication by user credentials (e.g., pattern lock, PIN, or other password).

When the user is authenticated successfully, the vehicle control system **204**, in step **2708**, retrieves the corresponding account for the successfully authenticated user.

In step **2712**, the vehicle control system **204** next determines the area and/or zone (e.g., seat position) occupied by the authenticated user, such as by using any of the techniques discussed herein, including without limitation image processing information of the various occupants, sensed seat weight, user input, location coordinates received from a portable computational device, such as a cell phone, tablet computer, or personal digital assistant associated with the user, and the like. The vehicle control system **204** may also determine an operating state of the vehicle, e.g., in motion, parked, in gear, in neutral, and the like.

In step **2716**, based on location (e.g., seat position) of the corresponding authenticated user and/or the operating state of the vehicle, the vehicle control system **204** enables eligible rights, privileges, settings and configurations set forth in the corresponding account and disables ineligible right or privileges or alters settings and configurations.

When the user is not authenticated successfully, the vehicle control system **204**, in step **2720**, creates an account for the unauthenticated user as set forth above. As noted, the account can be a default account.

Another application of the vehicle control system **204** for authentication by facial recognition is shown in FIGS. **28-29**.

In step **2800**, the vehicle control system **204** detects a stimulus or trigger event.

In step **2804**, the vehicle control system **204** provides, via the device or user interface **212**, **248**, user interface (s)/input interface(s) **324** and/or I/O module **312**, the user with a face detection screen, such as that shown in FIG. **29**. As shown in FIG. **29**, the face detection screen **2900** is a dashed outline **2904** of a human face having eye holes **2908***a* and *b* to enable the user to align his or her face with the screen for a higher quality video image of the user's face. This screen **2900** prompts the user to align his or her face such that the facial recognition camera can obtain a good image. The screen can show the video feed from the facial recognition camera with the dashed outline as an overlay. The dashed outline is intended to assist users situate his or her image properly in the camera's field of view. An instruction line **2912** can appear at the top of the screen **2900**.

When an acceptable facial image is not obtained so that facial recognition cannot be performed, the vehicle control system **204** proceeds **2803** to a manual sign-in step (discussed below) and provides the user with a face recognition failure notification dialog over the screen **2900** of the device or user interface **212**, **248**, user interface (s)/input interface(s) **324** and/or I/O module **312** in step **2812**. If a proper facial image is obtained, the vehicle control system **204**, in step **2816**, searches through a repository of stored facial images to find a match and, during the mapping, provides the user with a recognition progress indicator modal on the screen **2900**.

When recognition is not successful or no match is found, the vehicle control system **204** proceeds to step **2812** and the manual sign-in step discussed below.

When recognition is successful and a match is found, the vehicle control system **204** proceeds to step **2820** and applies the personal settings of the user, such as any or all of the settings referenced above. A settings application progress modal can be displayed over the displayed screen.

In step **2812**, the vehicle control system **204** provides the user with a manual sign-in screen (not shown) requesting input of the user's credentials. The manual sign-in screen, for example, can include fields for user identifier and password and options to sign in or continue as a guest.

When the credentials are not received within a time out period or are incorrect or at the request of the user in step **2812**, the vehicle control system **204** can create **2828** a guest or default account for the user as discussed above and applies default settings.

When the credentials are received and successfully authenticated, the vehicle control system **204** in step **2820** applies the personal settings of the user.

The vehicle control system **204**, after steps **2820**, **2824**, or **2828** proceeds to step **2832** and provides a home screen page, such as home page **3000**, configured in accordance with the applicable settings.

Configuration of Haptic Feedback and Visual Preferences in Vehicle User Interfaces

The profile data **252** can include, for each occupant in a corresponding user profile, physical impairment information, such as information regarding a disability. The physical impairments include vision impairments (e.g., low vision, blindness, night and color blindness, and light sensitivity), hearing impairments (such as hearing loss, hard-of-hearing, and deafness), dexterity and mobility impairments (such as caused by arthritis, cerebral palsy, multiple sclerosis, loss of limb or digit, spinal cord injury, and repetitive stress injury), and language and/or communication impairments (such as aphasia, delayed speech, dyslexia, and other conditions resulting in difficulties remembering, solving problems, and/or perceiving sensory information).

System data **208** can include rules to implement by the vehicle control system **204** an accessibility or assistive technology. This can include reconfiguring, for example, the driver's device or user interface **212**, **248**, user interface (s)/input interface(s) **324** and/or I/O module **312**. Once the user having the impairment is located in the vehicle or correlated with a particular seat position and/or device or user interface **212**, **248**, user interface (s)/input interface(s) **324** and/or I/O module **312**, the accessibility or assistive technology can be applied to the corresponding device or user interface **212**, **248**, user interface (s)/input interface(s) **324** and/or I/O module **312**. The type of accessibility or assistive technology employed can depend not only on the type and capabilities of the device or user interface **212**, **248**, user interface (s)/input interface(s) **324** and/or I/O module **312** but also on the seat position of the impaired user. Specifically, when the impaired user is a driver of the vehicle, he or she may receive different accessibility or assistive technology compared to when he or she is a non-driving vehicle occupant or passenger.

The type of assistance provided by the vehicle control system **204** depends on the particular impairment and/or disability involved. For example, if the vehicle control system **204** were to determine that the user has a particular impairment and/or disability, the vehicle control system **204** can recommend and/or implement automatically other feature or device settings and/or accessible technology that may provide improved access for the user. By way of illustration, information, commands, warnings, and requests provided by way of the driver's device or user interface **212**, **248**, user interface (s)/input interface(s) **324** and/or I/O module **312** to users with vision impairments can be one or more of the use of screen magnification, high contrast (e.g., between text and background colors such as white text on a black background, large font size and/or icon size (e.g., without changing screen resolution), color changes on the screen, a screen reader (or other text-to-speech program), speech recognition software (such as to operate the computer and/or software), enablement of a read mode, keyboard web page navigation, and the like. Information, commands, warnings, and requests provided by way of the driver's device or user interface **212**, **248**, user interface (s)/input interface(s) **324** and/or I/O module **312** to users with a hearing impairment can be one or more of the use of text or visual alternatives for sounds, high volume levels, changed computer sounds, sign language interpretation or translation (e.g., by image processing and acquisition based on visual images captured by one or more camera sensors), a text phone application, and the like. Information, commands, warnings, and requests provided by way of the driver's device or user interface **212**, **248**, user interface (s)/input interface(s) **324** and/or I/O module **312** to users with a dexterity and/or mobility impairment can be one or more of the use of particular mouse settings (e.g., mouse button configuration and timing (such as double-click speed), to make the mouse pointer more visible, and to alter the scroll speed of the mouse wheel or how quickly the mouse pointer responds to movements of the mouse), an increased size of a mouse-selectable screen element to provide a larger target, mouse keys to move the mouse pointer, sticky keys, toggle keys, filter keys, keyboard shortcuts, access keys, keyboard settings, an on-screen keyboard, speech recognition software (such as to dictate into almost any application (e.g., the user can dictate documents and email, surf the web, and control selected vehicle tasks, functions, and operations by voice command)), disablement of the automatic arrangement of windows when the mouse cursor is moved to the edge of the screen, enablement of activate a window by hovering over it with the mouse cursor, keyboard web page navigation, a disability assistive keyboard (such as an alternative keyboard) displayed on the screen, a keyboard filter, and the like. Information, commands, warnings, and requests provided by way of the driver's device or user interface **212**, **248**, user interface (s)/input interface(s) **324** and/or I/O module **312** to users with a language and/or communication impairment can be one or more of the use of sticky keys, toggle keys, filter keys, enablement of remove background images, disablement of all unnecessary animations, long period for notification dialog boxes to stay open, a keyboard filter, speech recognition software, enablement of a read mode, a screen reader, keyboard web page navigation, and a speech synthesizer, and the like. Information, commands, warnings, and requests provided by way of the driver's device or user interface **212**, **248**, user interface (s)/input interface(s) **324** and/or I/O module **312** to users with a learning impairment can be one or more of the use of a word prediction program, a reading tool, a learning disability program, a speech synthesizer, and speech recognition programs.

For users with an impairment, an assistive technology can use haptic feedback to provide information to a user. Haptic technology, or haptics, is a tactile feedback technology which takes advantage of the sense of touch by applying forces, vibrations, or motions to the user. Haptic feedback commonly uses the sense of touch in a user interface to provide information to an end user. The user interface can be any device with which a body part of the user is in contact and through which

haptic feedback can be transmitted. Examples include a steering wheel, tactile electronic display, seat, seat belt, foot pedal, gear shift, center or rear center console, arm rest, other contact surface, and the like. In one configuration, the assistive technology is a system where at least two actuators are positioned beneath a user interface to provide vibratory feedback when a user makes contact with the unit. One actuator can induce a feedback vibration while one or more other actuator creates a second vibration to suppress the first from propagating to unwanted regions of the interface, thereby "localizing" the haptic experience. To minimize driver's attention away from the road or for a visually impaired occupant, tactile (or haptic or aural) feedback can be used to help a user identify which button/icon they are touching or pressing, without drawing their visual attention away from the road. It can also be used, for the hearing impaired, haptic feedback can be used to identify external sounds, such as sirens of an emergency vehicle, and/or a vehicle horn and/or information about a vehicle task, function or operation, such as an engine-related warning being activated, vehicle speed, vehicle gear currently engaged, and the like. Each type of information to be provided by haptic feedback to the user can have a correspondingly different haptic feedback response to enable the user to distinguish between types of information. For example, a police siren can have a different haptic feedback than an ambulance siren, both of which can have a different haptic feedback from an engine-related warning.

The external sound can be detected by one or more sound sensors positioned interiorly and/or exteriorly to the vehicle. Each sensor generates an analog or digital representation of the sound detected over a selected frequency range. The vehicle control system uses template matching to associate the profile of the sound detected with a corresponding matching profile of type of sound. In other words, the sound profile is the template and the sensed sound profile of a police siren is matched to the template sound profile.

Sensed sound template matching can be used to generate an alert or sound in a different frequency range to a user. All or part of the sensed sound profile can be frequency shifted to provide a corresponding output sound profile covering a different frequency range. The matching type of sound can have a unique corresponding output sound profile. The output sound profile can be played to the vehicle occupants over the sound system of the vehicle. The output sound profile may be suited to a user's particular frequency and/or hearing disability such that the output sound profile contains a set of frequencies that the user can hear. The sound may even adjust an audible signal presented to a user (e.g., statically, dynamically, and/or combinations thereof) to provide a differently shaped or phase-shifted sound profile. The sound profile over certain frequency ranges can be exaggerated in magnitude and/or the sound profile over certain frequency ranges can be decreased in magnitude or eliminated altogether. The output sound profile is played over the vehicle's sound system in temporal proximity to the detection of the corresponding external sound profile to alarm the occupant. In one configuration, the output sound profile is played over the spatially dispersed speakers in the passenger compartment with sound delays (or phase shifts) and/or magnitude levels at each speaker simulating the sound delays and/or magnitude levels of the various portions of the sound sensed by the various sound detectors positioned inside and/or outside of the vehicle. This can indicate to the user spatially where the origin or source of the sound is located relative to the vehicle.

Alternative to or in addition to playing the output sound profile, visual signals and/or alerts to a user (e.g., flashing lights, increasing intensity associated with a visual signal, animated icons, etc.) can be provided visually to the user. The color, brightness, duration, and/or intensity of the light emitted and/or appearance of the animated icon can vary by the matching type of sound profile such that each type of sound profile has a unique set of visual signals and/or alerts to the user.

The general interfaces of a vehicle, including but not limited to, at least one of the infotainment system, interfaces, graphical user interfaces, and the like, can be configured to display color-blind friendly colors so that the interface is meaningful and usable for a color-blind user. Colors, contrast, brightness, etc. may be configured to provide an optimum user experience based on the type of color-blindness.

The vehicle control system can adjust or modify settings on manual controls to account for a user impairment or medical condition, age, physical condition or characteristics, and/or driving history. This information can be recorded in a corresponding user profile, obtained over the Internet from a remote source (such as driving history from a law enforcement agency), and/or sensed by observing the user's behavior over time. For instance, the user may not respond quickly to a vehicle sensed obstacle in the path of the vehicle, may move, shake or jitter the steering wheel slightly during vehicle operation. The user response time, pedal displacement of the user, force applied to a pedal by the user, steering wheel displacement during straight-line driving, and the like can be monitored by the vehicle control system and the monitored behavior analyzed and stored in the corresponding user profile. Analysis can by matching the observed behavior against various templates. The closest template is associated with a corresponding set of configuration rules regarding what settings to use for manual controls of the vehicle, The abilities can be based on driving or responsiveness tests and/or driver profiles maintained by a law enforcement or driver regulating agency.

Based on impairment, medical condition, age, and/or abilities, for example, the steering wheel, pedals, and/or other systems can be adjusted for play and/or responsiveness. For example, an individual who suffers from one or more of Parkinsons, old age, shaking, etc. may require more "play" in the steering wheel such that any shaking and/or small movements of the individual do not adversely affect the steering sensitivity of the vehicle. Upon detecting the user impairment, the vehicle control system may alter the characteristics of the steering wheel, for example, by reducing the sensitivity associated with movement. In one case, the sensitivity may be changed by modifying the electrical output in response to receiving a certain mechanical angular movement of the steering wheel. For instance, an angular movement of 10 degrees at the steering wheel may be the minimum default angular movement to cause the wheels on a vehicle to begin to turn. Upon detecting a user's disability, this minimum default angular movement may be increased to 30 degrees, as an example. Therefore, small movements (e.g., under 30 degrees) will not affect the steering. The changes to be implemented are typically based on rule sets in the system data **208** which map a set of user-related descriptors to recommended or required changes. The descriptors typically describe one or more of user impairment, medical condition, age, and/or abilities.

As can be appreciated, the sensitivity associated with a steering wheel and/or other manual vehicle control systems may be increased based on a user's abilities. Using the example provided above, an angular movement of 10 degrees at the steering wheel may be the minimum default angular movement to cause the wheels on a vehicle to begin to turn. Upon detecting a user's ability (e.g., quick reactions, steady

hands, past driving history, past vehicle history, etc.) this minimum default angular movement may be decreased to 5 degrees, as an example. Therefore, smaller movements (e.g., of 5 degrees applied at the wheel) will cause the vehicle to begin turning (similar to racing vehicles and/or high-end cars, etc.).

In other examples, (brake, emergency brake, accelerator and/or clutch) pedal movement range can be adjusted; that is, the vehicle control system can automatically adjust one or more of pedal stroke length, sensitivity, etc., based at least partially on user profile data and abilities.

The adjustment based on user profile and abilities can be extended to adjust settings and configurations of automated vehicle response systems. A collision avoidance system is an automobile safety system designed to reduce the severity of an accident. Also known as precrash system, forward collision warning system or collision mitigating system, it uses radar and sometimes laser and camera sensors to detect an imminent crash. Once the detection is done, these systems either provide a warning to the driver when there is an imminent collision or take action autonomously without any driver input (by braking or steering or both). In one approach, the collision avoidance system works in multiple phases. In a first phase, the collision avoidance system provides warning of an impending accident, while the hazard warning lights are activated, the side windows and sunroof are closed and the front seat belts are tensioned. In a second phase, the warning is followed by light braking, strong enough to win the driver's attention. In a third phase, the collision avoidance system initiates autonomous partial braking. In a fourth phase, the collision avoidance system decelerates the car followed by automatic deceleration at full braking power, roughly half a second before projected impact. In another approach, the collision avoidance system provides a warning to the driver through a Heads Up Display that visually resembles brake lamps. If the driver does not react, the system pre-charges the brakes and increases the brake assist sensitivity to maximize driver braking performance. In another approach, the collision avoidance system comprises radar and camera-based crash imminent braking in which radar technology detects a possible crash threat and alerts the driver. If the driver does not appear to react quickly enough or does not react at all, the system intervenes to apply the brakes in an effort to avoid the crash. In another approach, the collision avoidance system has three warning stages. In the first warning stage, the collision avoidance system includes audible and visual warnings to brake. If ignored, the collision avoidance system in the second stage tugs on the shoulder portion of the seat belt two to three times as an additional tactile warning to the driver to take action. In a third stage, the collision avoidance system predicts that a collision is unavoidable and includes full seat belt slack takeup for more effective seat belt protection and automatic application of the brakes to lessen the severity of the predicted crash. In another approach, the collision avoidance system highlights pedestrians in front of the vehicle at night by alerting the driver with an audible chime and visually displaying them via a Heads Up Display. In another approach, the collision avoidance system uses electronic stability control sensors to measure steering angle, vehicle yaw and lateral acceleration of the vehicle and brake assist (BAS) sensors to detect emergency braking, The collision avoidance system can tighten the seat belts, adjust seat positions including rear seats (if installed), raise folded rear headrests (if installed) and close the sunroof and windows if it detects a possible collision (including rollover). The collision avoidance system can use radar to monitor the traffic situation ahead and provide automatic partial braking if the driver does not react to the warnings and the system detects a severe danger of an accident. The disclosure can be applied to other automated response systems besides collision avoidance systems.

The vehicle can adjust the settings of the automotive response systems, such as a collision avoidance system, to reflect a driver's unique abilities and/or impairments. The settings for instance can be for instance the time at which a warning of a potential collision is provided to the driver, the duration of the driver response or reaction time interval from a warning of a collision is provided to the driver and the initiation of automated braking, the braking force or deceleration of automated braking, and the time over which automated braking occurs. For example, a driver with particularly quick responses can have less fault tolerant triggers than a driver with slow responses; that is, the collision avoidance system for the former driver will trigger automated braking later than the collision avoidance system for the latter driver.

An operation of the vehicle control system will be discussed with reference to FIG. **31**.

In step **3100**, the vehicle control system senses a stimulus, such as ignition of the vehicle, the vehicle being placed in gear, a door opening or closing to permit a person to enter or exit the vehicle, activation of a graphical user interface, and the like.

In step **3104**, the vehicle control system determines an identity of each occupant and, based on the occupant's user profile, whether or not the occupant has an impairment. The occupant may be identified by any suitable technique, including authentication, electronic address information of a portable communication device associated with the user, image recognition, seat sensor feedback (e.g., weight of occupant), seat and lumbar settings selected by the occupant, and the like.

When the occupant has an impairment, the vehicle control system determines, in step **3108**, occupant seating and/or interface location. The interface can be, for example, a graphical user interface, steering wheel, brake, clutch, or accelerator pedal, gear shift, or other communication interface by which the occupant is provided or provides information to the vehicle control system.

In step **3112**, the vehicle control system configures the vehicle communication interface based on the type and/or severity of the occupant impairment(s), seating position of the occupant, and/or type of interface.

In step **3116**, the vehicle control system selects a next occupant of the vehicle and returns to decision diamond **3104**.

An operation of the vehicle control system will be discussed with reference to FIG. **32**.

In step **3200**, the vehicle control system senses a stimulus, such as ignition of the vehicle, the vehicle being placed in gear, a door opening or closing to permit a person to enter or exit the vehicle, activation of a graphical user interface, and the like.

In step **3204**, the vehicle control system determines an identity of each occupant, retrieves the corresponding user profile and relevant system data. The occupant may be identified by any suitable technique, including authentication, electronic address information of a portable communication device associated with the user, image recognition, seat sensor feedback (e.g., weight of occupant), seat and lumbar settings selected by the occupant, and the like.

In decision diamond **3208**, the vehicle control system, based on the occupant's user profile and/or relevant system data, determines whether or not the occupant has an ability that deviates sufficiently from a normal range for the subject vehicle communication interface and/or automated vehicle response system. The normal range is defined for each type of

activity and for each type of interface and/or automated control system. As will be appreciated, different types of activities, different types of interfaces, and/or different types of automated control systems have differing normal ranges.

When the occupant has an activity that deviates sufficiently from a normal range, the vehicle control system retrieves and applies rule sets, in step **3212**, to determine what settings of the vehicle communication interface and/or automated vehicle response system require alteration.

In step **3216**, the vehicle control system configures the vehicle communication interface and/or automated vehicle response system based on the rule set application.

The vehicle control system then returns to step **3200**.

The exemplary systems and methods of this disclosure have been described in relation to configurable vehicle center or rear center consoles and associated devices. However, to avoid unnecessarily obscuring the present disclosure, the preceding description omits a number of known structures and devices. This omission is not to be construed as a limitation of the scopes of the claims. Specific details are set forth to provide an understanding of the present disclosure. It should however be appreciated that the present disclosure may be practiced in a variety of ways beyond the specific detail set forth herein.

Furthermore, while the exemplary aspects, embodiments, options, and/or configurations illustrated herein show the various components of the system collocated, certain components of the system can be located remotely, at distant portions of a distributed network, such as a LAN and/or the Internet, or within a dedicated system. Thus, it should be appreciated, that the components of the system can be combined in to one or more devices, such as a Personal Computer (PC), laptop, netbook, smart phone, Personal Digital Assistant (PDA), tablet, etc., or collocated on a particular node of a distributed network, such as an analog and/or digital telecommunications network, a packet-switch network, or a circuit-switched network. It will be appreciated from the preceding description, and for reasons of computational efficiency, that the components of the system can be arranged at any location within a distributed network of components without affecting the operation of the system. For example, the various components can be located in a switch such as a PBX and media server, gateway, in one or more communications devices, at one or more users' premises, or some combination thereof. Similarly, one or more functional portions of the system could be distributed between a telecommunications device(s) and an associated computing device.

Furthermore, it should be appreciated that the various links connecting the elements can be wired or wireless links, or any combination thereof, or any other known or later developed element(s) that is capable of supplying and/or communicating data to and from the connected elements. These wired or wireless links can also be secure links and may be capable of communicating encrypted information. Transmission media used as links, for example, can be any suitable carrier for electrical signals, including coaxial cables, copper wire and fiber optics, and may take the form of acoustic or light waves, such as those generated during radio-wave and infra-red data communications.

Also, while the flowcharts have been discussed and illustrated in relation to a particular sequence of events, it should be appreciated that changes, additions, and omissions to this sequence can occur without materially affecting the operation of the disclosed embodiments, configuration, and aspects.

A number of variations and modifications of the disclosure can be used. It would be possible to provide for some features of the disclosure without providing others.

It should be appreciated that the various processing modules (e.g., processors, vehicle systems, vehicle subsystems, modules, etc.), for example, can perform, monitor, and/or control critical and non-critical tasks, functions, and operations, such as interaction with and/or monitoring and/or control of critical and non-critical on board sensors and vehicle operations (e.g., engine, transmission, throttle, brake power assist/brake lock-up, electronic suspension, traction and stability control, parallel parking assistance, occupant protection systems, power steering assistance, self-diagnostics, event data recorders, steer-by-wire and/or brake-by-wire operations, vehicle-to-vehicle interactions, vehicle-to-infrastructure interactions, partial and/or full automation, telematics, navigation/SPS, multimedia systems, audio systems, rear seat entertainment systems, game center or rear center consoles, tuners (SDR), heads-up display, night vision, lane departure warning, adaptive cruise control, adaptive headlights, collision warning, blind spot sensors, park/reverse assistance, tire pressure monitoring, traffic signal recognition, vehicle tracking (e.g., LoJack™), dashboard/instrument cluster, lights, seats, climate control, voice recognition, remote keyless entry, security alarm systems, and wiper/window control). Processing modules can be enclosed in an advanced EMI-shielded enclosure containing multiple expansion modules. Processing modules can have a "black box" or flight data recorder technology, containing an event (or driving history) recorder (containing operational information collected from vehicle on board sensors and provided by nearby or roadside signal transmitters), a crash survivable memory unit, an integrated controller and circuitry board, and network interfaces.

Critical system controller(s) can control, monitor, and/or operate critical systems. Critical systems may include one or more of (depending on the particular vehicle) monitoring, controlling, operating the ECU, TCU, door settings, window settings, blind spot monitor, monitoring, controlling, operating the safety equipment (e.g., airbag deployment control unit, collision sensor, nearby object sensing system, seat belt control unit, sensors for setting the seat belt, etc.), monitoring and/or controlling certain critical sensors such as the power source controller and energy output sensor, engine temperature, oil pressure sensing, hydraulic pressure sensors, sensors for headlight and other lights (e.g., emergency light, brake light, parking light, fog light, interior or passenger compartment light, and/or tail light state (on or off)), vehicle control system sensors, wireless network sensor (e.g., Wi-Fi and/or Bluetooth sensors, etc.), cellular data sensor, and/or steering/torque sensor, controlling the operation of the engine (e.g., ignition, etc.), head light control unit, power steering, display panel, switch state control unit, power control unit, and/or brake control unit, and/or issuing alerts to a user and/or remote monitoring entity of potential problems with a vehicle operation.

Non-critical system controller(s) can control, monitor, and/or operate non-critical systems. Non-critical systems may include one or more of (depending on the particular vehicle) monitoring, controlling, operating a non-critical system, emissions control, seating system controller and sensor, infotainment/entertainment system, monitoring certain non-critical sensors such as ambient (outdoor) weather readings (e.g., temperature, precipitation, wind speed, and the like), odometer reading sensor, trip mileage reading sensor, road condition sensors (e.g., wet, icy, etc.), radar transmitter/receiver output, brake wear sensor, oxygen sensor, ambient lighting sensor, vision system sensor, ranging sensor, parking sensor, heating, venting, and air conditioning (HVAC) system

and sensor, water sensor, air-fuel ratio meter, hall effect sensor, microphone, radio frequency (RF) sensor, and/or infrared (IR) sensor.

It is an aspect of the present disclosure that one or more of the non-critical components and/or systems provided herein may become critical components and/or systems, and/or vice versa, depending on a context associated with the vehicle.

Optionally, the systems and methods of this disclosure can be implemented in conjunction with a special purpose computer, a programmed microprocessor or microcontroller and peripheral integrated circuit element(s), an ASIC or other integrated circuit, a digital signal processor, a hard-wired electronic or logic circuit such as discrete element circuit, a programmable logic device or gate array such as PLD, PLA, FPGA, PAL, special purpose computer, any comparable means, or the like. In general, any device(s) or means capable of implementing the methodology illustrated herein can be used to implement the various aspects of this disclosure. Exemplary hardware that can be used for the disclosed embodiments, configurations and aspects includes computers, handheld devices, telephones (e.g., cellular, Internet enabled, digital, analog, hybrids, and others), and other hardware known in the art. Some of these devices include processors (e.g., a single or multiple microprocessors), memory, nonvolatile storage, input devices, and output devices. Furthermore, alternative software implementations including, but not limited to, distributed processing or component/object distributed processing, parallel processing, or virtual machine processing can also be constructed to implement the methods described herein.

In yet another embodiment, the disclosed methods may be readily implemented in conjunction with software using object or object-oriented software development environments that provide portable source code that can be used on a variety of computer or workstation platforms. Alternatively, the disclosed system may be implemented partially or fully in hardware using standard logic circuits or VLSI design. Whether software or hardware is used to implement the systems in accordance with this disclosure is dependent on the speed and/or efficiency requirements of the system, the particular function, and the particular software or hardware systems or microprocessor or microcomputer systems being utilized.

In yet another embodiment, the disclosed methods may be partially implemented in software that can be stored on a storage medium, executed on programmed general-purpose computer with the cooperation of a controller and memory, a special purpose computer, a microprocessor, or the like. In these instances, the systems and methods of this disclosure can be implemented as program embedded on personal computer such as an applet, JAVA® or CGI script, as a resource residing on a server or computer workstation, as a routine embedded in a dedicated measurement system, system component, or the like. The system can also be implemented by physically incorporating the system and/or method into a software and/or hardware system.

Although the present disclosure describes components and functions implemented in the aspects, embodiments, and/or configurations with reference to particular standards and protocols, the aspects, embodiments, and/or configurations are not limited to such standards and protocols. Other similar standards and protocols not mentioned herein are in existence and are considered to be included in the present disclosure. Moreover, the standards and protocols mentioned herein and other similar standards and protocols not mentioned herein are periodically superseded by faster or more effective equivalents having essentially the same functions. Such replacement standards and protocols having the same functions are considered equivalents included in the present disclosure.

The present disclosure, in various aspects, embodiments, and/or configurations, includes components, methods, processes, systems and/or apparatus substantially as depicted and described herein, including various aspects, embodiments, configurations embodiments, subcombinations, and/or subsets thereof. Those of skill in the art will understand how to make and use the disclosed aspects, embodiments, and/or configurations after understanding the present disclosure. The present disclosure, in various aspects, embodiments, and/or configurations, includes providing devices and processes in the absence of items not depicted and/or described herein or in various aspects, embodiments, and/or configurations hereof, including in the absence of such items as may have been used in previous devices or processes, e.g., for improving performance, achieving ease and\or reducing cost of implementation.

The foregoing discussion has been presented for purposes of illustration and description. The foregoing is not intended to limit the disclosure to the form or forms disclosed herein. In the foregoing Detailed Description for example, various features of the disclosure are grouped together in one or more aspects, embodiments, and/or configurations for the purpose of streamlining the disclosure. The features of the aspects, embodiments, and/or configurations of the disclosure may be combined in alternate aspects, embodiments, and/or configurations other than those discussed above. This method of disclosure is not to be interpreted as reflecting an intention that the claims require more features than are expressly recited in each claim. Rather, as the following claims reflect, inventive aspects lie in less than all features of a single foregoing disclosed aspect, embodiment, and/or configuration. Thus, the following claims are hereby incorporated into this Detailed Description, with each claim standing on its own as a separate preferred embodiment of the disclosure.

Moreover, though the description has included description of one or more aspects, embodiments, and/or configurations and certain variations and modifications, other variations, combinations, and modifications are within the scope of the disclosure, e.g., as may be within the skill and knowledge of those in the art, after understanding the present disclosure. It is intended to obtain rights which include alternative aspects, embodiments, and/or configurations to the extent permitted, including alternate, interchangeable and/or equivalent structures, functions, ranges or steps to those claimed, whether or not such alternate, interchangeable and/or equivalent structures, functions, ranges or steps are disclosed herein, and without intending to publicly dedicate any patentable subject matter.

What is claimed is:

1. A method, comprising:

(a) determining, by a microprocessor executable device discovery daemon, that a computational device is connected to or attempting to connect to a network and/or communication subsystem of a vehicle;

(b) in response, determining, by the device discovery daemon, whether the computational device is located within a predetermined area and/or zone of the vehicle; and

(c) applying, by the device discovery daemon, at least the following rules:

(C1) when the computational device is located within the predetermined area and/or zone of the vehicle, permitting the computational device to access or attempt to access the vehicle network and/or communication subsystem; and

(C2) when the computational device is not located within the predetermined area and/or zone of the vehicle, not permitting the computational device to access or attempt to access the vehicle network and/or communication subsystem.

2. The method of claim **1**, wherein a type of the computational device determines a specific predetermined area and/or zone of the vehicle, from among a plurality of predetermined areas and/or zones, to be used in applying the rules, wherein the computational device is one or more of a tablet computer, laptop, smart phone, and personal digital assistant, and wherein the specific predetermined area and/or zone of the vehicle is at least part of the passenger compartment.

3. The method of claim **1**, wherein step (a) comprises the substeps:

receiving, by the device discovery daemon, information from an on board vehicle sensor that a new occupant has entered the vehicle;

in response to the receipt of the information, emitting, by the device discovery daemon, a ping to discover the computational device; and

when a responsive signal is received from the computational device, determining, by the device discovery daemon, that the computational device is attempting to connect to a network and/or communication subsystem of a vehicle.

4. The method of claim **1**, wherein the determining step (b) bases the determination on whether the computational device is located within the predetermined area and/or zone of the vehicle on one or more of signal strength of a signal from the computational device as received by an access point of the vehicle, a received satellite-based position of the computational device, triangulation based on relative received signal strengths of a signal from the computational device as received by multiple access points of the vehicle, image processing of images of the predetermined area and/or zone, occupant presence and/or location information received by an on board vehicle sensor, whether the computational device is attempting to connect to the network and/or communication subsystem wirelessly or by hard wire connection, whether the computational device has moved relative to a selected access point during a defined time interval, whether the received signal strength of signaling from the computational device at a selected access point varies temporally, a type or service of the computational device, and input received from a user of the computational device.

5. The method of claim **4**, wherein the wherein the computational device determined to be located within the predetermined area and/or zone of the vehicle and is permitted to access or attempt to access the vehicle network and/or communication subsystem and wherein the device discovery daemon determines a set of tasks, functions, and/or operations that can be performed and a set of tasks, functions, and/or operations that cannot be performed based on the determined location of the computational device.

6. The method of claim **4**, wherein the device discovery daemon uses multiple of the one or more of signal strength of a signal from the computational device as received by an access point of the vehicle, a received satellite-based position of the computational device, triangulation based on relative received signal strengths of a signal from the computational device as received by multiple access points of the vehicle, image processing of images of the predetermined area and/or zone, occupant presence and/or location information received by an on board vehicle sensor, whether the computational device is attempting to connect to the network and/or communication subsystem wirelessly or by hard wire connection, whether the computational device has moved relative to a selected access point during a defined time interval, whether the received signal strength of signaling from the computational device at a selected access point varies temporally, a type or service of the computational device, and input received from a user of the computational device.

7. The method of claim **6**, wherein the device discovery daemon determines a level of confidence that the computational device is located within the predetermined area and/or zone and wherein the device discovery daemon determines that the computational device is located within the predetermined area and/or zone when the level of confidence has at least a threshold value.

8. A vehicle, comprising:

a microprocessor executable device discovery daemon operable to:

(a) determine that a computational device is connected to or attempting to connect to a network and/or communication subsystem of a vehicle;

(b) in response, determining whether the computational device is located within a predetermined area and/or zone of the vehicle; and

(c) applying at least the following rules:

(C1) when the computational device is located within the predetermined area and/or zone of the vehicle, permitting the computational device to access or attempt to access the vehicle network and/or communication subsystem; and

(C2) when the computational device is not located within the predetermined area and/or zone of the vehicle, not permitting the computational device to access or attempt to access the vehicle network and/or communication subsystem.

9. The vehicle of claim **8**, wherein a type of the computational device determines a specific predetermined area and/or zone of the vehicle, from among a plurality of predetermined areas and/or zones, to be used in applying the rules, wherein the computational device is one or more of a tablet computer, laptop, smart phone, and personal digital assistant, and wherein the specific predetermined area and/or zone of the vehicle is at least part of the passenger compartment.

10. The vehicle of claim **8**, wherein operation (a) comprises the suboperations:

receiving, by the device discovery daemon, information from an on board vehicle sensor that a new occupant has entered the vehicle;

in response to the receipt of the information, emitting, by the device discovery daemon, a ping to discover the computational device; and

when a responsive signal is received from the computational device, determining, by the device discovery daemon, that the computational device is attempting to connect to a network and/or communication subsystem of a vehicle.

11. The vehicle of claim **8**, wherein the determining operation (b) bases the determination on whether the computational device is located within the predetermined area and/or zone of the vehicle on one or more of signal strength of a signal from the computational device as received by an access point of the vehicle, a received satellite-based position of the computational device, triangulation based on relative received signal strengths of a signal from the computational device as received by multiple access points of the vehicle, image processing of images of the predetermined area and/or zone, occupant presence and/or location information received by an on board vehicle sensor, whether the computational device is attempting to connect to the network and/or com-

munication subsystem wirelessly or by hard wire connection, whether the computational device has moved relative to a selected access point during a defined time interval, whether the received signal strength of signaling from the computational device at a selected access point varies temporally, a type or service of the computational device, and input received from a user of the computational device.

12. The vehicle of claim **11**, wherein the wherein the computational device determined to be located within the predetermined area and/or zone of the vehicle and is permitted to access or attempt to access the vehicle network and/or communication subsystem and wherein the device discovery daemon determines a set of tasks, functions, and/or operations that can be performed and a set of tasks, functions, and/or operations that cannot be performed based on the determined location of the computational device.

13. The vehicle of claim **11**, wherein the device discovery daemon uses multiple of the one or more of signal strength of a signal from the computational device as received by an access point of the vehicle, a received satellite-based position of the computational device, triangulation based on relative received signal strengths of a signal from the computational device as received by multiple access points of the vehicle, image processing of images of the predetermined area and/or zone, occupant presence and/or location information received by an on board vehicle sensor, whether the computational device is attempting to connect to the network and/or communication subsystem wirelessly or by hard wire connection, whether the computational device has moved relative to a selected access point during a defined time interval, whether the received signal strength of signaling from the computational device at a selected access point varies temporally, a type or service of the computational device, and input received from a user of the computational device.

14. The vehicle of claim **13**, wherein the device discovery daemon determines a level of confidence that the computational device is located within the predetermined area and/or zone and wherein the device discovery daemon determines that the computational device is located within the predetermined area and/or zone when the level of confidence has at least a threshold value.

15. A tangible and non-transient computer readable medium including microprocessor executable instructions that, when executed, perform at least the following functions:

(a) determining that a computational device is connected to or attempting to connect to a network and/or communication subsystem of a vehicle;

(b) in response, determining whether the computational device is located within a predetermined area and/or zone of the vehicle; and

(c) applying, by the device discovery daemon, at least the following rules:

(C1) when the computational device is located within the predetermined area and/or zone of the vehicle, permitting the computational device to access or attempt to access the vehicle network and/or communication subsystem; and

(C2) when the computational device is not located within the predetermined area and/or zone of the vehicle, not permitting the computational device to access or attempt to access the vehicle network and/or communication subsystem.

16. The computer readable medium of claim **15**, wherein a type of the computational device determines a specific predetermined area and/or zone of the vehicle, from among a plurality of predetermined areas and/or zones, to be used in applying the rules, wherein the computational device is one or more of a tablet computer, laptop, smart phone, and personal digital assistant, and wherein the specific predetermined area and/or zone of the vehicle is at least part of the passenger compartment.

17. The computer readable medium of claim **15**, wherein function (a) comprises the subfunctions:

receiving, by the device discovery daemon, information from an on board vehicle sensor that a new occupant has entered the vehicle;

in response to the receipt of the information, emitting, by the device discovery daemon, a ping to discover the computational device; and

when a responsive signal is received from the computational device, determining, by the device discovery daemon, that the computational device is attempting to connect to a network and/or communication subsystem of a vehicle.

18. The computer readable medium of claim **15**, wherein the determining function (b) bases the determination on whether the computational device is located within the predetermined area and/or zone of the vehicle on one or more of signal strength of a signal from the computational device as received by an access point of the vehicle, a received satellite-based position of the computational device, triangulation based on relative received signal strengths of a signal from the computational device as received by multiple access points of the vehicle, image processing of images of the predetermined area and/or zone, occupant presence and/or location information received by an on board vehicle sensor, whether the computational device is attempting to connect to the network and/or communication subsystem wirelessly or by hard wire connection, whether the computational device has moved relative to a selected access point during a defined time interval, whether the received signal strength of signaling from the computational device at a selected access point varies temporally, a type or service of the computational device, and input received from a user of the computational device.

19. The computer readable medium of claim **18**, wherein the wherein the computational device determined to be located within the predetermined area and/or zone of the vehicle and is permitted to access or attempt to access the vehicle network and/or communication subsystem and wherein the device discovery daemon determines a set of tasks, functions, and/or operations that can be performed and a set of tasks, functions, and/or operations that cannot be performed based on the determined location of the computational device.

20. The computer readable medium of claim **18**, wherein the device discovery daemon uses multiple of the one or more of signal strength of a signal from the computational device as received by an access point of the vehicle, a received satellite-based position of the computational device, triangulation based on relative received signal strengths of a signal from the computational device as received by multiple access points of the vehicle, image processing of images of the predetermined area and/or zone, occupant presence and/or location information received by an on board vehicle sensor, whether the computational device is attempting to connect to the network and/or communication subsystem wirelessly or by hard wire connection, whether the computational device has moved relative to a selected access point during a defined time interval, whether the received signal strength of signaling from the computational device at a selected access point varies temporally, a type or service of the computational device, and input received from a user of the computational device.

21. The computer readable medium of claim 20, wherein the device discovery daemon determines a level of confidence that the computational device is located within the predetermined area and/or zone and wherein the device discovery daemon determines that the computational device is located within the predetermined area and/or zone when the level of confidence has at least a threshold value.

* * * * *