



US012038247B2

(12) **United States Patent**
Blakley

(10) **Patent No.:** **US 12,038,247 B2**

(45) **Date of Patent:** **Jul. 16, 2024**

(54) **FIREARM TRIGGER MECHANISM**

FOREIGN PATENT DOCUMENTS

(71) Applicant: **ABC IP, LLC**, Dover, DE (US)

DE 582963 C 8/1933
DE 4008351 A1 9/1991

(72) Inventor: **Brian A. Blakley**, Pinellas Park, FL (US)

(Continued)

(73) Assignee: **ABC IP, LLC**, Dover, DE (US)

OTHER PUBLICATIONS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

Statutory Invention Registration No. H107, Inventor: Bauer, Published Aug. 5, 1986 (8 pages).

Primary Examiner — Reginald S Tillman, Jr.

(21) Appl. No.: **18/325,225**

(74) *Attorney, Agent, or Firm* — Wood Herron & Evans LLP

(22) Filed: **May 30, 2023**

(65) **Prior Publication Data**

US 2024/0085136 A1 Mar. 14, 2024

Related U.S. Application Data

(60) Provisional application No. 63/374,941, filed on Sep. 8, 2022.

(51) **Int. Cl.**
F41A 19/45 (2006.01)
F41A 17/46 (2006.01)

(Continued)

(52) **U.S. Cl.**
CPC **F41A 19/45** (2013.01); **F41A 17/46** (2013.01); **F41A 19/10** (2013.01); **F41A 19/16** (2013.01); **F41A 19/15** (2013.01)

(58) **Field of Classification Search**
CPC F41A 19/10; F41A 19/45; F41A 19/15; F41A 17/46

(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS


2,765,562 A 10/1956 Roper et al.
3,045,555 A 7/1962 Stoner

(Continued)

(57) **ABSTRACT**

A trigger mechanism that can be used in AR-pattern firearms has a hammer, a trigger member, a disconnecter, a cam, and a “three position” safety selector having safe, standard semi-automatic, and forced reset semi-automatic positions. In the standard semi-automatic position, rearward movement of the bolt carrier causes rearward pivoting of the hammer and pivoting of the cam from a first position to a second position such that a cam lobe forces the trigger member towards the set position, but prior to reaching the set position the disconnecter hook catches the hammer hook, at which time a user must manually release the trigger member to free the hammer from the disconnecter to permit the hammer and trigger member to pivot to their set positions so that the user can pull the trigger member to fire the firearm. In the forced reset semi-automatic position, rearward movement of the bolt carrier causes rearward pivoting of the hammer and pivoting of the cam from the first position to the second position such that the cam lobe forces the trigger member to the set position, the safety selector preventing the disconnecter hook from catching the hammer hook, at which time the user can pull the trigger member to fire the firearm without manually releasing the trigger member.

23 Claims, 18 Drawing Sheets



- (56) **References Cited**
- U.S. PATENT DOCUMENTS

- | | | | |
|--------------|----|---------|--------------------|
| 9,121,661 | B2 | 9/2015 | Calvete |
| 9,146,066 | B1 | 9/2015 | Cason |
| 9,146,067 | B2 | 9/2015 | Stakes |
| 9,182,189 | B2 | 11/2015 | Seigler |
| 9,228,786 | B2 | 1/2016 | Sullivan et al. |
| 9,310,150 | B1 | 4/2016 | Geissele |
| 9,347,726 | B1 | 5/2016 | Thomas |
| 9,448,023 | B2 | 9/2016 | Sheets, Jr. et al. |
| 9,476,660 | B2 | 10/2016 | Potter et al. |
| 9,513,076 | B2 | 12/2016 | Kolev et al. |
| 9,568,264 | B2 | 2/2017 | Graves |
| 9,618,288 | B2 | 4/2017 | Wilson |
| 9,618,289 | B1 | 4/2017 | Geissele |
| 9,625,231 | B1 | 4/2017 | Hass |
| 9,631,886 | B2 | 4/2017 | Findlay |
| 9,651,329 | B2 | 5/2017 | Hittmann |
| 9,658,007 | B2 | 5/2017 | Withey |
| 9,683,800 | B2 | 6/2017 | Sewell, Jr. et al. |
| 9,733,031 | B1 | 8/2017 | Sylvester et al. |
| 9,759,504 | B2 | 9/2017 | Geissele |
| 9,777,980 | B2 | 10/2017 | Heizer |
| 9,810,493 | B2 | 11/2017 | Fluhr et al. |
| 9,810,496 | B2 | 11/2017 | Kolev et al. |
| 9,816,772 | B2 | 11/2017 | Graves |
| 9,829,263 | B2 | 11/2017 | Bonner |
| 9,835,398 | B2 | 12/2017 | Biegel |
| 9,863,730 | B2 | 1/2018 | Elftmann |
| 9,869,522 | B2 | 1/2018 | Larson, Jr. et al. |
| 9,874,417 | B2 | 1/2018 | Zajk et al. |
| 9,927,197 | B1 | 3/2018 | Geissele |
| 9,939,221 | B2 | 4/2018 | Graves |
| 10,002,500 | B2 | 6/2018 | Hall et al. |
| 10,006,734 | B1 | 6/2018 | Findlay |
| 10,030,924 | B1 | 7/2018 | Smith |
| 10,077,960 | B2 | 9/2018 | Geissele |
| 10,107,580 | B2 | 10/2018 | Fellows et al. |
| 10,254,067 | B2 | 4/2019 | Foster |
| 10,267,584 | B2 | 4/2019 | Kasanjian-King |
| 10,330,413 | B2 | 6/2019 | Williams et al. |
| 10,488,136 | B2 | 11/2019 | Sullivan et al. |
| 10,502,511 | B2 | 12/2019 | Graves |
| 10,514,223 | B1 | 12/2019 | Rounds |
| 10,584,932 | B2 | 3/2020 | Foster |
| 11,287,205 | B2 | 3/2022 | Biegel |
| 11,293,715 | B1 | 4/2022 | Newsome et al. |
| 11,346,627 | B1 | 5/2022 | DeMonico |
| 11,724,003 | B2 | 8/2023 | Strbac |
| 2006/0048426 | A1 | 3/2006 | Crandall |
| 2006/0101695 | A1 | 5/2006 | Longueira |
| 2007/0051236 | A1 | 3/2007 | Graves et al. |
| 2007/0199435 | A1 | 8/2007 | Hochstrate et al. |
| 2009/0151213 | A1 | 6/2009 | Bell |
| 2009/0188145 | A1 | 7/2009 | Fluhr et al. |
| 2011/0209607 | A1 | 9/2011 | St. George |
| 2013/0118343 | A1 | 5/2013 | Hirt |
| 2014/0311004 | A1 | 10/2014 | Barrett |
| 2016/0010933 | A1 | 1/2016 | Bonner |
| 2016/0102933 | A1 | 4/2016 | Graves |
| 2016/0161202 | A1 | 6/2016 | Larue |
| 2017/0176124 | A1 | 6/2017 | Wilson |
| 2017/0219307 | A1 | 8/2017 | Foster |
| 2017/0276447 | A1 | 9/2017 | Foster |
| 2017/0284761 | A1 | 10/2017 | Lewis et al. |
| 2017/0299309 | A1 | 10/2017 | Fellows et al. |
| 2017/0328663 | A1 | 11/2017 | Fellows et al. |
| 2018/0066911 | A1 | 3/2018 | Graves |
| 2018/0087860 | A1 | 3/2018 | Sullivan et al. |
| 2018/0112944 | A1 | 4/2018 | Underwood et al. |
| 2018/0195823 | A1 | 7/2018 | Schafer et al. |
| 2018/0202740 | A1 | 7/2018 | Elftmann, Jr. |
| 2018/0231342 | A1 | 8/2018 | Martinez |
| 2021/0222974 | A1 | 7/2021 | Graves |

EP	1678458	B1	2/2012
EP	2950033	B1	11/2016

(56)

References Cited

FOREIGN PATENT DOCUMENTS

TW	409847 U	10/2000
WO	2016/028337 A1	2/2016
WO	2018/058174 A1	4/2018




FIG. 1




FIG. 2




FIG. 3




FIG. 4A




FIG. 4B





FIG. 5A







FIG. 6A






FIG. 7




FIG. 8A




FIG. 8B




FIG. 8C




FIG. 8D




FIG. 9A




FIG. 9B




FIG. 9C




FIG. 9D

1

FIREARM TRIGGER MECHANISM**RELATED APPLICATIONS**

This application claims the priority benefit of U.S. Provisional Patent Application No. 63/374,941 filed Sep. 8, 2022, which is hereby incorporated by reference herein as if fully set forth in its entirety.

FIELD OF THE INVENTION

The present invention relates generally to a firearm trigger mechanism, and more particularly to a semiautomatic trigger that is selectively mechanically reset by movement of the bolt carrier.

BACKGROUND OF THE INVENTION

In a standard semiautomatic firearm, actuation of the trigger releases a sear, allowing a hammer or striker to fire a chambered ammunition cartridge. Part of the ammunition's propellant force is used to cycle the action, extracting and ejecting a spent cartridge and replacing it with a loaded cartridge. The cycle includes longitudinal reciprocation of a bolt and/or carrier, which also resets the hammer or striker.

A standard semiautomatic trigger mechanism includes a disconnecter, which holds the hammer or striker in a cocked position until the trigger member is reset to engage the sear. This allows the firearm to be fired only a single time when the trigger is pulled and held, because the user is not typically able to release the trigger rapidly enough so that the sear engages before the bolt or bolt carrier returns to its in-battery position. The disconnecter prevents the firearm from either firing multiple rounds on a single pull of the trigger, or from allowing the hammer or striker to simply "follow" the bolt as it returns to battery without firing a second round, but leaving the hammer or striker uncocked.

For various reasons, shooters desire to increase the rate of semiautomatic fire. Sometimes this is simply for entertainment and the feeling of shooting a machine gun. In the past, users have been known to employ "bump firing" to achieve rapid semiautomatic fire. Bump firing uses the recoil of the semiautomatic firearm to fire shots in rapid succession. The process involves bracing the rifle with the non-trigger hand, loosening the grip of the trigger hand (but leaving the trigger finger in its normal position in front of the trigger), and pushing the rifle forward in order to apply pressure on the trigger from the finger while keeping the trigger finger stationary. When fired with the trigger finger held stationary, the firearm will recoil to the rear and allow the trigger to reset as it normally does. When the non-trigger hand pulls the firearm away from the body and back forward toward the original position, it causes the trigger to be pressed against the stationary finger again, firing another round as the trigger is pushed back.

Devices for increasing the rate of semiautomatic fire are shown in U.S. Pat. Nos. 9,568,264, 9,816,772, and 9,939,221, issued to Thomas Allen Graves. The devices shown in these patents forcefully reset the trigger with rigid mechanical contact between the trigger member and the bolt as the action cycles. To adapt this invention to an AR-pattern firearm, for example, would require not only a modified fire control mechanism, but also a modified bolt carrier.

Other devices for increasing the rate of semiautomatic fire are shown in the assignee's U.S. Pat. Nos. 10,514,223 and 11,346,627 and U.S. patent application Ser. No. 18/048,572 filed Oct. 21, 2022, all of which are hereby incorporated by

2

reference as if fully set forth in their entirety. In these devices the hammer forces the trigger to the set position, and a locking bar prevents early hammer release.

Another device for increasing the rate of semiautomatic fire is shown in U.S. Pat. No. 7,398,723, issued on Jul. 15, 2008, to Brian A. Blakley, and is hereby incorporated by reference herein as if fully set forth in its entirety. The device shown in this patent has a pivoting cam which is contacted by the rearwardly traveling bolt carrier, pivoting the cam rearwardly such that the bottom surface of the cam presses downward on the trigger-extension, forcing the rear of the trigger down, and thereby moving forward the surface of the trigger that an operator's finger engages.

Further improvement in forced reset triggers is desired.

SUMMARY OF INVENTION

The present invention provides a semiautomatic trigger mechanism for increasing rate of fire that can be retrofitted into popular existing firearm platforms. In particular, this invention provides a trigger mechanism that can be used in AR-pattern firearms with an otherwise standard M16-pattern bolt carrier assembly. Embodiments of the present invention are particularly adaptable for construction as a "drop-in" replacement trigger module that only requires insertion of two assembly pins and the safety selector. Advantageously, the present invention provides a "three position" trigger mechanism having safe, standard semi-automatic, and forced reset semi-automatic positions.

In one aspect, a firearm trigger mechanism comprises a housing adapted to be installed in a fire control mechanism pocket of a receiver and having a first pair of transversely aligned openings for receiving a hammer pin, a second pair of transversely aligned openings for receiving a trigger pin, and a third pair of transversely aligned openings for receiving a cam pin, a hammer having a sear catch and a hook for engaging a disconnecter and mounted in the housing to pivot on the hammer pin between set and released positions, the hammer adapted to be pivoted rearward by rearward movement of a bolt carrier, a trigger member having a sear and mounted in the housing to pivot on the trigger member pin between set and released positions, wherein the sear and sear catch are in engagement in the set positions of the hammer and trigger member and are out of engagement in the released positions of the hammer and trigger member, a disconnecter having a hook for engaging the hammer and mounted in the housing to pivot on the trigger member pin, a cam having a cam lobe and mounted in the housing to pivot on the cam pin, the cam being pivotable between a first position at which the cam lobe does not force the trigger member towards the set position and a second position at which the cam lobe does force the trigger member towards the set position, and a safety selector adapted to be mounted in the fire control mechanism pocket to pivot between safe, standard semi-automatic, and forced reset semi-automatic positions. In the standard semi-automatic position, rearward movement of the bolt carrier causes rearward pivoting of the hammer and pivoting of the cam from the first position to the second position such that the cam lobe forces the trigger member towards the set position but prior to reaching the set position the disconnecter hook catches the hammer hook, and thereafter forward movement of the bolt carrier causes the cam to pivot to the first position, at which time a user must manually release the trigger member to free the hammer from the disconnecter to permit the hammer and trigger member to pivot to the set positions so that the user can pull the trigger member to fire the firearm. In the forced reset

3

semi-automatic position, rearward movement of the bolt carrier causes rearward pivoting of the hammer and pivoting of the cam from the first position to the second position such that the cam lobe forces the trigger member to the set position, the safety selector preventing the disconnecter hook from catching the hammer hook, and thereafter forward movement of the bolt carrier causes the cam to pivot to the first position, at which time the user can pull the trigger member to fire the firearm without manually releasing the trigger member.

The safety selector can have a protuberance thereon which, when the safety selector is in the forced reset semi-automatic position, contacts the disconnecter preventing the disconnecter hook from catching the hammer hook. The trigger mechanism can further include a spring which biases the trigger member towards the set position.

In another aspect, a firearm trigger mechanism comprises a housing adapted to be installed in a fire control mechanism pocket of a receiver and having a first pair of transversely aligned openings for receiving a hammer pin, a second pair of transversely aligned openings for receiving a trigger pin, and a third pair of transversely aligned openings for receiving a cam pin, a hammer having a sear catch and a hook for engaging a disconnecter and mounted in the housing to pivot on the hammer pin between set and released positions, the hammer adapted to be pivoted rearward by rearward movement of a bolt carrier, a trigger member having a sear and mounted in the housing to pivot on the trigger member pin between set and released positions, wherein the sear and sear catch are in engagement in the set positions of the hammer and trigger member and are out of engagement in the released positions of the hammer and trigger member, a disconnecter having a hook for engaging the hammer and mounted in the housing to pivot on the trigger member pin, a cam having a cam lobe and mounted in the housing to pivot on the cam pin, the cam being pivotable between a first position at which the cam lobe does not force the trigger member towards the set position and a second position at which the cam lobe does force the trigger member towards the set position, and a safety selector adapted to be mounted in the fire control mechanism pocket to pivot between safe, standard semi-automatic, and forced reset semi-automatic positions. In the standard semi-automatic position, rearward movement of the bolt carrier causes rearward pivoting of the hammer and pivoting of the cam from the first position to the second position such that the cam lobe forces the trigger member towards the set position but prior to reaching the set position the disconnecter hook catches the hammer hook, and thereafter forward movement of the bolt carrier causes the cam to pivot to the first position, at which time a user must manually release the trigger member to free the hammer from the disconnecter to permit the hammer and trigger member to pivot to the set positions so that the user can pull the trigger member to fire the firearm. In the forced reset semi-automatic position, rearward movement of the bolt carrier causes rearward pivoting of the hammer and pivoting of the cam from the first position to the second position such that the cam lobe forces the trigger member to the set position, the safety selector preventing the disconnecter hook from catching the hammer hook, and thereafter forward movement of the bolt carrier causes the cam to pivot to the first position, at which time the user can pull the trigger member to fire the firearm without manually releasing the trigger member.

The safety selector can have a protuberance thereon which, when the safety selector is in the forced reset semi-automatic position, contacts the disconnecter prevent-

4

ing the disconnecter hook from catching the hammer hook. The first and second pairs of transversely aligned openings in the housing can be adapted to be aligned with first and second pairs of transversely aligned assembly pin openings in the fire control mechanism pocket. The trigger mechanism can include a spring which biases the trigger member towards the set position. The spring can be a torsion spring.

In another aspect, a firearm comprises a receiver having a fire control mechanism pocket therein, a reciprocating bolt carrier, a hammer having a sear catch and a hook for engaging a disconnecter and mounted in the fire control mechanism pocket to pivot on a transverse hammer pivot axis between set and released positions, the hammer adapted to be pivoted rearward by rearward movement of the bolt carrier, a trigger member having a sear and mounted in the fire control mechanism pocket to pivot on a transverse trigger member pivot axis between set and released positions, wherein the sear and sear catch are in engagement in the set positions of the hammer and trigger member and are out of engagement in the released positions of the hammer and trigger member, a disconnecter having a hook for engaging the hammer and mounted in the fire control mechanism pocket to pivot on the transverse trigger member pivot axis, a cam having a cam lobe and mounted in the fire control mechanism pocket to pivot on a transverse cam pivot axis, the cam being pivotable between a first position at which the cam lobe does not force the trigger member towards the set position and a second position at which the cam lobe does force the trigger member towards the set position, and a safety selector mounted in the fire control mechanism pocket to pivot between safe, standard semi-automatic, and forced reset semi-automatic positions. In the standard semi-automatic position, rearward movement of the bolt carrier causes rearward pivoting of the hammer and pivoting of the cam from the first position to the second position such that the cam lobe forces the trigger member towards the set position but prior to reaching the set position the disconnecter hook catches the hammer hook, and thereafter forward movement of the bolt carrier causes the cam to pivot to the first position, at which time a user must manually release the trigger member to free the hammer from the disconnecter to permit the hammer and trigger member to pivot to the set positions so that the user can pull the trigger member to fire the firearm. In the forced reset semi-automatic position, rearward movement of the bolt carrier causes rearward pivoting of the hammer and pivoting of the cam from the first position to the second position such that the cam lobe forces the trigger member to the set position, the safety selector preventing the disconnecter hook from catching the hammer hook, and thereafter forward movement of the bolt carrier causes the cam to pivot to the first position, at which time the user can pull the trigger member to fire the firearm without manually releasing the trigger member.

The firearm can further comprise a housing having a first pair of transversely aligned openings with a hammer pin therethrough and a second pair of transversely aligned openings with a trigger member pin therethrough, the hammer mounted on the hammer pin, the trigger member and disconnecter mounted on the trigger member pin. The receiver can have a first pair of transversely aligned assembly pin openings and a second pair of transversely aligned assembly pin openings, the housing first pair of openings coaxial with the receiver first pair of openings and the housing second pair of openings coaxial with the receiver second pair of openings, a first assembly pin passing through the receiver first pair of openings and through the housing first pair of openings, and a second assembly pin passing

5

through the receiver second pair of openings and through the housing second pair of openings. The firearm can further comprise a spring which biases the trigger member towards the set position. The spring can be a torsion spring.

In another aspect, a firearm trigger mechanism comprises a hammer having a sear catch and a hook for engaging a disconnecter and adapted to be mounted in a fire control mechanism pocket of a receiver to pivot on a transverse hammer pivot axis between set and released positions, the hammer adapted to be pivoted rearward by rearward movement of a bolt carrier, a trigger member having a sear and adapted to be mounted in the fire control mechanism pocket to pivot on a transverse trigger member pivot axis between set and released positions, wherein the sear and sear catch are in engagement in the set positions of the hammer and trigger member and are out of engagement in the released positions of the hammer and trigger member, a disconnecter having a hook for engaging the hammer and adapted to be mounted in the fire control mechanism pocket to pivot on the transverse trigger member pivot axis, a cam having a cam lobe and adapted to be movably mounted in the fire control mechanism pocket, the cam being movable between a first position at which the cam lobe does not force the trigger member towards the set position and a second position at which the cam lobe does force the trigger member towards the set position, and a safety selector adapted to be mounted in the fire control mechanism pocket to pivot between safe, standard semi-automatic, and forced reset semi-automatic positions. In the standard semi-automatic position, rearward movement of the bolt carrier causes rearward pivoting of the hammer and movement of the cam from the first position to the second position such that the cam lobe forces the trigger member towards the set position but prior to reaching the set position the disconnecter hook catches the hammer hook, and thereafter forward movement of the bolt carrier causes the cam to move to the first position, at which time a user must manually release the trigger member to free the hammer from the disconnecter to permit the hammer and trigger member to pivot to the set positions so that the user can pull the trigger member to fire the firearm. In the forced reset semi-automatic position, rearward movement of the bolt carrier causes rearward pivoting of the hammer and movement of the cam from the first position to the second position such that the cam lobe forces the trigger member to the set position, the safety selector preventing the disconnecter hook from catching the hammer hook, and thereafter forward movement of the bolt carrier causes the cam to move to the first position, at which time the user can pull the trigger member to fire the firearm without manually releasing the trigger member.

Other aspects, features, benefits, and advantages of the present invention will become apparent to a person of skill in the art from the detailed description of various embodiments with reference to the accompanying drawing figures, all of which comprise part of the disclosure.

BRIEF DESCRIPTION OF THE DRAWINGS

Like reference numerals are used to indicate like parts throughout the various drawing figures, wherein:

FIG. 1 is a top front right perspective view of a drop-in trigger module for an AR-pattern firearm according to one embodiment of the invention.

FIG. 2 is a top rear right perspective view thereof.

FIG. 3 is a top rear right exploded perspective view thereof.

6

FIG. 4A is a top rear right cross-sectional view thereof with the safety selector in the safe position and with the hammer and trigger member in their set positions.

FIG. 4B is a bottom rear right cross-sectional view thereof with the safety selector in the safe position and with the hammer and trigger member in their set positions.

FIG. 5A is a top rear right cross-sectional view thereof with the safety selector in the standard semi-automatic position and with the hammer and trigger member in their set positions.

FIG. 5B is a bottom rear right cross-sectional view thereof with the safety selector in the standard semi-automatic position and with the hammer and trigger member in their set positions.

FIG. 6A is a top rear right cross-sectional view thereof with the safety selector in the forced reset semi-automatic position and with the hammer and trigger member in their set positions.

FIG. 6B is a bottom rear right cross-sectional view thereof with the safety selector in the forced reset semi-automatic position and with the hammer and trigger member in their set positions.

FIG. 7 is a cross-sectional view showing the trigger module installed in a typical AR15-pattern lower receiver, with the hammer and trigger member in their set positions and with the bolt carrier in an in-battery position, and with the safety selector in the safe position.

FIG. 8A is a view similar to FIG. 7 but with the safety selector in the standard semi-automatic position.

FIG. 8B is a view similar to FIG. 8A but after the trigger has been pulled to drop the hammer.

FIG. 8C is a view similar to FIG. 8B but with the bolt carrier cycling to the rear to pivot the hammer and cam.

FIG. 8D is a view similar to FIG. 8C but with the bolt carrier having returned to battery and the disconnecter having caught the hammer.

FIG. 9A is a view similar to FIG. 7 but with the safety selector in the forced reset semi-automatic position.

FIG. 9B is a view similar to FIG. 9A but after the trigger has been pulled to drop the hammer.

FIG. 9C is a view similar to FIG. 9B but with the bolt carrier cycling to the rear to pivot the hammer and cam.

FIG. 9D is a view similar to FIG. 9C but with the bolt carrier having returned to battery and the hammer and trigger having returned to their set positions.

DETAILED DESCRIPTION OF THE DRAWINGS

With reference to the drawing figures, this section describes particular embodiments and their detailed construction and operation. Throughout the specification, reference to “one embodiment,” “an embodiment,” or “some embodiments” means that a particular described feature, structure, or characteristic may be included in at least one embodiment. Thus, appearances of the phrases “in one embodiment,” “in an embodiment,” or “in some embodiments” in various places throughout this specification are not necessarily all referring to the same embodiment. Furthermore, the described features, structures, and characteristics may be combined in any suitable manner in one or more embodiments. In view of the disclosure herein, those skilled in the art will recognize that the various embodiments can be practiced without one or more of the specific details or with other methods, components, materials, or the like. In some instances, well-known structures, materials, or operations are not shown or not described in detail to avoid obscuring aspects of the embodiments. “Forward” will indi-

cate the direction of the muzzle and the direction in which projectiles are fired, while “rearward” will indicate the opposite direction. “Lateral” or “transverse” indicates a side-to-side direction generally perpendicular to the axis of the barrel. Although firearms may be used in any orientation, “left” and “right” will generally indicate the sides according to the user’s orientation, “top” or “up” will be the upward direction when the firearm is gripped in the ordinary manner. QAs used herein, “transverse” means a side-to-side direction generally perpendicular to the longitudinal axis of the barrel.

Referring first to FIGS. 1-6B, there is illustrated a “drop-in” trigger module 10 adapted for use in an AR-pattern firearm according to a first embodiment of the present invention. As used herein, “AR-pattern” firearm includes the semiautomatic versions of the AR10 and AR15 firearms and variants thereof of any caliber, including pistol caliber carbines or pistols using a blow-back bolt. While select fire (fully automatic capable) versions of this platform, such as the M16 and M4, are also AR-pattern firearms, this invention only relates to semiautomatic firearm actions. The concepts of this invention may be adaptable to other popular semiautomatic firearm platforms, such as the Ruger 10/22™, AK-pattern firearms, and HK-pattern firearms.

The module 10 includes a frame or housing 12 sized and shaped to fit within the internal fire control pocket of an AR-pattern lower receiver 14. Lower receiver parts not important to the present invention are well-known in the art and are omitted from the figures for clarity. The housing 12 includes left and right sidewalls 16, 18 which extend substantially vertically and parallel to one another in a laterally spaced-apart relationship. The sidewalls 16, 18 may be interconnected by front and rear sidewalls 20, 22. The sidewalls 16, 18 include first and second pairs of aligned openings 24, 26 for receiving hollow transverse pins 30, 32 upon which a hammer 36 and trigger member 38 pivot. The openings 24, 26 are located coaxially with openings 42, 44 in the lower receiver 14. Standard AR-pattern hammer and trigger pins 46, 48 pass through the openings 42, 44 in the lower receiver 14 and through the hollow transverse pins 30, 32 to assemble the housing 12 into the lower receiver 14. Thus, the pins 30, 32 retain the hammer 36 and trigger member 38 in the housing 12 in modular fashion, whereas the pins 46, 48 retain the trigger module 10 in the lower receiver 14.

The hammer 36 has a hammer head 50, a sear catch 52, and a hammer hook 53. The hammer 36 is spring biased towards a forward position by a standard AR-pattern hammer torsion spring (not shown).

The trigger member 38 has a trigger blade 54 that extends downwardly. The trigger blade 54 is the part of the trigger member 38 contacted by a user’s finger to actuate the trigger mechanism. The trigger blade 54 may be curved (as shown) or straight, as desired. The trigger member 38 has a sear 56. When the sear 56 and the sear catch 52 are engaged, the hammer 36 and trigger member 38 are in their set positions. When the sear 56 and sear catch 52 are not engaged, the hammer 36 and trigger member 38 are in their released positions. The trigger member 38 also has a cam follower 58. The trigger member 38 is spring biased by a standard AR-pattern trigger member torsion spring (not shown) so that the trigger blade 54 is spring biased towards a forward position.

A disconnecter 60 is pivoted on the hollow transverse pin 32 upon which the trigger member 38 pivots. The disconnecter 60 has a disconnecter hook 64 and a tail 66. The tail 66 of the disconnecter 60 is spring biased upwardly away

from a tail 68 of the trigger member 38 by a standard AR-pattern disconnecter compression spring 67.

A cam 72 is movably mounted to the housing 12. For example, the cam 72 can be pivoted on a cam pin 74 that is installed in aligned openings 76 in the sidewalls 16, 18 of the housing 12. The cam 72 has a cam lobe 78 that interacts with the cam follower 58, in a manner to be described below. The cam 72 has a first contact surface 82 on an upper forward portion thereof and a second contact surface 84 on an upper rearward portion thereof. The cam 72 has a notch 86 below the second contact surface 84 to provide clearance for the rear wall 22 of the housing 12. Alternatively, the cam 72 can be slidably mounted to the housing 12 with or without spring bias.

An upper receiver 90 houses a bolt carrier assembly 92. As is well-known in the art, the bolt carrier assembly 92 (or blow-back bolt) slidably reciprocates in the upper receiver 90 and engages the breach of a barrel or barrel extension. As used herein, “bolt carrier” and “bolt carrier assembly” may be used interchangeably and include a blow-back type bolt used in pistol caliber carbine configurations of the AR-platform. The bolt carrier assembly 92 used with the embodiments of this invention can have either a standard mil-spec M16-pattern bolt carrier, a standard AR15-pattern bolt carrier, or some variation of the two, depending on the design of the cam 72, and whether operated by a gas direct impingement system or a gas piston system. The bolt carrier assembly 92 has an engagement surface 94 in a rear portion 96 of the bolt carrier body 98. As in an ordinary AR15-pattern configuration, during rearward travel of the bolt carrier assembly 92 a lower surface 102 in a forward portion 104 of the bolt carrier body 98 contacts the face of the hammer head 50 causing the hammer 36 to pivot rearward. During further rearward travel of bolt carrier assembly 92 the lower surface 102 of the bolt carrier body 98 contacts the surface 82 of the cam 72 to the pivot cam 72 in a first direction from a first position to a second position. During forward travel of the bolt carrier assembly 92 the engagement surface 94 of the bolt carrier body 98 contacts the surface 84 of the cam 72 to pivot the cam 72 in a second opposite direction from the second position to the first position.

A three position safety selector 110 has safe, standard semi-automatic, and forced reset semi-automatic positions. When in the safe position (safety selector indicator 111 pointing forward), a wide semi-circular portion 112 of the safety selector 110 prevents the trigger blade 54 from being pulled (FIGS. 4A, 4B, and 7). When in the standard semi-automatic position (safety selector indicator 111 pointing upward), a flat portion 114 of the safety selector 110 permits the trigger blade 54 to be pulled. The disconnecter 60 can pivot with the trigger member 38 and the disconnecter hook 64 can catch the hammer hook 53 during rearward pivoting travel of the hammer head 50. (FIGS. 5A and 5B). When in the forced reset semi-automatic position (safety selector indicator 111 pointing rearward), a narrow semi-circular portion 116 permits the trigger blade 54 to be pulled but prevents the disconnecter 60 from pivoting with the trigger member 38 thus preventing the disconnecter hook 64 from catching the hammer hook 53 during rearward pivoting travel of the hammer head 50. (FIGS. 6A and 6B). In other words, in the forced reset semi-automatic position, the disconnecter 60 is “disabled” in that the disconnecter hook 64 is unable to catch the hammer hook 53 during cycling of the bolt carrier assembly 92.

Referring now to FIGS. 8A-8D, with the safety selector 110 set in the standard semi-automatic position, rearward

finger pressure on the trigger blade 54 causes the trigger member 38 to rotate clockwise. Depending on the position of the cam 72, the cam follower 58 may or may not act upon the cam lobe 78 to pivot the cam 72 clockwise. Rotation of the trigger member 38 causes the sear 56 to disengage from the sear catch 52 of the hammer 36. This allows the hammer 36 to drop by spring force onto the firing pin 99 of the bolt carrier assembly 92, discharging an ammunition cartridge (not shown), and causing the action to cycle by moving the bolt carrier assembly 92 rearward. Rearward travel of the bolt carrier assembly 92 causes the lower surface 102 to contact the face of the hammer head 50 and pivot the hammer 36 counter-clockwise. During pivoting travel of the hammer 36 the disconnecter hook 64 catches the hammer hook 53. During further rearward travel of the bolt carrier assembly 92 the lower surface 102 contacts the surface 82 of the cam 72 to pivot the cam 72 counter-clockwise. As the cam 72 pivots counter-clockwise, the cam lobe 78 may act upon the cam follower 58 to pivot the trigger member 38 counter-clockwise. Forward travel of the bolt carrier assembly 92 returning to battery causes the surface 94 to contact the surface 84 of the cam 72 to pivot the cam 72 clockwise. At this point rearward finger pressure on the trigger blade 54 must be released to allow the sear 56 to engage the sear catch 52, returning the hammer 36 and trigger member 38 to their set positions. Thereafter the user can reapply rearward finger pressure on the trigger blade 54 to fire another round.

Referring now to FIGS. 9A-9D, with the safety selector 110 set in the forced reset semi-automatic position, rearward finger pressure on the trigger blade 54 causes the trigger member 38 to rotate clockwise. The narrow semi-circular portion 116 of the safety selector 110 prevents the disconnecter 60 from rotating with the trigger member 38, thus "disabling" the disconnecter 60, preventing the disconnecter hook 64 from catching the hammer hook 53. Depending on the position of the cam 72, the cam follower 58 may or may not act upon the cam lobe 78 to pivot the cam 72 clockwise. Rotation of the trigger member 38 causes the sear 56 to disengage from the sear catch 52 of the hammer 36. This allows the hammer 36 to drop by spring force onto the firing pin 99 of the bolt carrier assembly 92, discharging an ammunition cartridge, and causing the action to cycle by moving the bolt carrier assembly 92 rearward. Rearward travel of the bolt carrier assembly 92 causes the lower surface 102 to contact the face of the hammer head 50 and pivot the hammer 36 counter-clockwise. During further rearward travel of the bolt carrier assembly 92 the lower surface 102 contacts the surface 82 of the cam 72 to pivot the cam 72 counter-clockwise. As the cam 72 pivots counter-clockwise, the cam lobe 78 acts upon the cam follower 58 to pivot the trigger member 38 counter-clockwise. The bolt carrier assembly 92 thereby forces the hammer 36 and trigger member 38 to their set positions wherein the sear 56 engages the sear catch 52. Forward travel of the bolt carrier assembly 92 returning to battery causes the surface 94 to contact the surface 84 of the cam 72 to pivot the cam 72 clockwise. At this point the user can reapply rearward finger pressure on the trigger blade 54 to fire another round, without first manually releasing rear finger pressure on the trigger blade 54.

Thus, as the bolt carrier assembly 92 returns forward, the trigger member 38 is held in its set position by cam 72. The trigger member 38 cannot be pulled to release the sear/sear catch engagement, thus precluding early hammer release or "hammer follow" against the bolt carrier assembly 92 and firing pin 99 as the bolt carrier assembly 92 is returning to battery. When the bolt carrier assembly 92 has reached (or

nearly reached) its closed, in-battery position, the engagement surface 94 contacts and forwardly displaces the contact surface 84 of cam 72, disengaging the cam lobe 78 from the cam follower 58, allowing the trigger blade 54 to be pulled. Again, this prevents early hammer release and contact of the hammer against the firing pin before the bolt is completely locked and in-battery.

While various embodiments of the present invention have been described in detail, it should be apparent that modifications and variations thereto are possible, all of which fall within the true spirit and scope of the invention. Therefore, the foregoing is intended only to be illustrative of the principles of the invention. The invention resides in each individual feature described herein, alone, and in any and all combinations and subcombinations of any and all of those features. Further, since numerous modifications and changes will readily occur to those skilled in the art, it is not intended to limit the invention to the exact construction and operation shown and described. Accordingly, all suitable modifications and equivalents may be included and considered to fall within the scope of the invention, defined by the following claim or claims.

What is claimed is:

1. A firearm trigger mechanism comprising:

a hammer having a sear catch and a hook for engaging a disconnecter and adapted to be mounted in a fire control mechanism pocket of a receiver to pivot on a transverse hammer pivot axis between set and released positions, said hammer adapted to be pivoted rearward by rearward movement of a bolt carrier,

a trigger member having a sear and adapted to be mounted in the fire control mechanism pocket to pivot on a transverse trigger member pivot axis between set and released positions,

wherein said sear and sear catch are in engagement in said set positions of said hammer and trigger member and are out of engagement in said released positions of said hammer and trigger member,

a disconnecter having a hook for engaging said hammer and adapted to be mounted in the fire control mechanism pocket to pivot on said transverse trigger member pivot axis,

a cam having a cam lobe and adapted to be mounted in the fire control mechanism pocket to pivot on a transverse cam pivot axis, said cam being pivotable between a first position at which said cam lobe does not force said trigger member towards said set position and a second position at which said cam lobe does force said trigger member towards said set position, and

a safety selector adapted to be mounted in the fire control mechanism pocket to pivot between safe, standard semi-automatic, and forced reset semi-automatic positions,

whereupon in said standard semi-automatic position, rearward movement of the bolt carrier causes rearward pivoting of said hammer and pivoting of said cam from said first position to said second position such that said cam lobe forces said trigger member towards said set position but prior to reaching said set position said disconnecter hook catches said hammer hook, and thereafter forward movement of the bolt carrier causes said cam to pivot to said first position, at which time a user must manually release said trigger member to free said hammer from said disconnecter to permit said hammer and trigger member to pivot to said set positions so that the user can pull said trigger member to fire the firearm, and

11

whereupon in said forced reset semi-automatic position, rearward movement of the bolt carrier causes rearward pivoting of said hammer and pivoting of said cam from said first position to said second position such that said cam lobe forces said trigger member to said set position, said safety selector preventing said disconnecter hook from catching said hammer hook, and thereafter forward movement of the bolt carrier causes said cam to pivot to said first position, at which time the user can pull said trigger member to fire the firearm without manually releasing said trigger member.

2. The trigger mechanism of claim 1, wherein said safety selector has a protuberance thereon which, when said safety selector is in said forced reset semi-automatic position, contacts said disconnecter preventing said disconnecter hook from catching said hammer hook.

3. The trigger mechanism of claim 1 further including a spring which biases said trigger member towards said set position.

4. A firearm trigger mechanism comprising:

a housing adapted to be installed in a fire control mechanism pocket of a receiver and having a first pair of transversely aligned openings for receiving a hammer pin, a second pair of transversely aligned openings for receiving a trigger pin, and a third pair of transversely aligned openings for receiving a cam pin,

a hammer having a sear catch and a hook for engaging a disconnecter and mounted in said housing to pivot on said hammer pin between set and released positions, said hammer adapted to be pivoted rearward by rearward movement of a bolt carrier,

a trigger member having a sear and mounted in said housing to pivot on said trigger member pin between set and released positions,

wherein said sear and sear catch are in engagement in said set positions of said hammer and trigger member and are out of engagement in said released positions of said hammer and trigger member,

a disconnecter having a hook for engaging said hammer and mounted in said housing to pivot on said trigger member pin,

a cam having a cam lobe and mounted in said housing to pivot on said cam pin, said cam being pivotable between a first position at which said cam lobe does not force said trigger member towards said set position and a second position at which said cam lobe does force said trigger member towards said set position, and

a safety selector adapted to be mounted in the fire control mechanism pocket to pivot between safe, standard semi-automatic, and forced reset semi-automatic positions,

whereupon in said standard semi-automatic position, rearward movement of the bolt carrier causes rearward pivoting of said hammer and pivoting of said cam from said first position to said second position such that said cam lobe forces said trigger member towards said set position but prior to reaching said set position said disconnecter hook catches said hammer hook, and thereafter forward movement of the bolt carrier causes said cam to pivot to said first position, at which time a user must manually release said trigger member to free said hammer from said disconnecter to permit said hammer and trigger member to pivot to said set positions so that the user can pull said trigger member to fire the firearm, and

whereupon in said forced reset semi-automatic position, rearward movement of the bolt carrier causes rearward

12

pivoting of said hammer and pivoting of said cam from said first position to said second position such that said cam lobe forces said trigger member to said set position, said safety selector preventing said disconnecter hook from catching said hammer hook, and thereafter forward movement of the bolt carrier causes said cam to pivot to said first position, at which time the user can pull said trigger member to fire the firearm without manually releasing said trigger member.

5. The trigger mechanism of claim 4, wherein said safety selector has a protuberance thereon which, when said safety selector is in said forced reset semi-automatic position, contacts said disconnecter preventing said disconnecter hook from catching said hammer hook.

6. The trigger mechanism of claim 4, wherein said first and second pairs of transversely aligned openings in said housing are adapted to be aligned with first and second pairs of transversely aligned assembly pin openings in the fire control mechanism pocket.

7. The trigger mechanism of claim 4 further including a spring which biases said trigger member towards said set position.

8. The trigger mechanism of claim 7 wherein said spring is a torsion spring.

9. A firearm comprising:

a receiver having a fire control mechanism pocket therein, a reciprocating bolt carrier,

a hammer having a sear catch and a hook for engaging a disconnecter and mounted in said fire control mechanism pocket to pivot on a transverse hammer pivot axis between set and released positions, said hammer adapted to be pivoted rearward by rearward movement of said bolt carrier,

a trigger member having a sear and mounted in said fire control mechanism pocket to pivot on a transverse trigger member pivot axis between set and released positions,

wherein said sear and sear catch are in engagement in said set positions of said hammer and trigger member and are out of engagement in said released positions of said hammer and trigger member,

a disconnecter having a hook for engaging said hammer and mounted in said fire control mechanism pocket to pivot on said transverse trigger member pivot axis,

a cam having a cam lobe and mounted in said fire control mechanism pocket to pivot on a transverse cam pivot axis, said cam being pivotable between a first position at which said cam lobe does not force said trigger member towards said set position and a second position at which said cam lobe does force said trigger member towards said set position, and

a safety selector mounted in said fire control mechanism pocket to pivot between safe, standard semi-automatic, and forced reset semi-automatic positions,

whereupon in said standard semi-automatic position, rearward movement of said bolt carrier causes rearward pivoting of said hammer and pivoting of said cam from said first position to said second position such that said cam lobe forces said trigger member towards said set position but prior to reaching said set position said disconnecter hook catches said hammer hook, and thereafter forward movement of said bolt carrier causes said cam to pivot to said first position, at which time a user must manually release said trigger member to free said hammer from said disconnecter to permit said

13

hammer and trigger member to pivot to said set positions so that the user can pull said trigger member to fire said firearm, and
 whereupon in said forced reset semi-automatic position, rearward movement of said bolt carrier causes rearward pivoting of said hammer and pivoting of said cam from said first position to said second position such that said cam lobe forces said trigger member to said set position, said safety selector preventing said disconnecter hook from catching said hammer hook, and thereafter forward movement of said bolt carrier causes said cam to pivot to said first position, at which time the user can pull said trigger member to fire said firearm without manually releasing said trigger member.

10. The firearm of claim 9 further comprising:
 a housing having a first pair of transversely aligned openings with a hammer pin therethrough and a second pair of transversely aligned openings with a trigger member pin therethrough,
 said hammer mounted on said hammer pin, said trigger member and disconnecter mounted on said trigger member pin.

11. The firearm of claim 10 further comprising:
 said receiver having a first pair of transversely aligned assembly pin openings and a second pair of transversely aligned assembly pin openings,
 said housing first pair of openings coaxial with said receiver first pair of openings and said housing second pair of openings coaxial with said receiver second pair of openings,
 a first assembly pin passing through said receiver first pair of openings and through said housing first pair of openings, and
 a second assembly pin passing through said receiver second pair of openings and through said housing second pair of openings.

12. The firearm of claim 10 further comprising a spring which biases said trigger member towards said set position.

13. The firearm of claim 12 wherein said spring is a torsion spring.

14. A firearm trigger mechanism comprising:
 a hammer having a sear catch and a hook for engaging a disconnecter and adapted to be mounted in a fire control mechanism pocket of a receiver to pivot on a transverse hammer pivot axis between set and released positions, said hammer adapted to be pivoted rearward by rearward movement of a bolt carrier,
 a trigger member having a sear and adapted to be mounted in the fire control mechanism pocket to pivot on a transverse trigger member pivot axis between set and released positions,
 wherein said sear and sear catch are in engagement in said set positions of said hammer and trigger member and are out of engagement in said released positions of said hammer and trigger member,
 a disconnecter having a hook for engaging said hammer and adapted to be mounted in the fire control mechanism pocket to pivot on said transverse trigger member pivot axis,
 a cam having a cam lobe and adapted to be movably mounted in the fire control mechanism pocket, said cam being movable between a first position at which said cam lobe does not force said trigger member towards said set position and a second position at which said cam lobe does force said trigger member towards said set position, and

14

a safety selector adapted to be mounted in the fire control mechanism pocket to pivot between safe, standard semi-automatic, and forced reset semi-automatic positions,
 whereupon in said standard semi-automatic position, rearward movement of the bolt carrier causes rearward pivoting of said hammer and movement of said cam from said first position to said second position such that said cam lobe forces said trigger member towards said set position but prior to reaching said set position said disconnecter hook catches said hammer hook, and thereafter forward movement of the bolt carrier causes said cam to move to said first position, at which time a user must manually release said trigger member to free said hammer from said disconnecter to permit said hammer and trigger member to pivot to said set positions so that the user can pull said trigger member to fire the firearm, and
 whereupon in said forced reset semi-automatic position, rearward movement of the bolt carrier causes rearward pivoting of said hammer and movement of said cam from said first position to said second position such that said cam lobe forces said trigger member to said set position, said safety selector preventing said disconnecter hook from catching said hammer hook, and thereafter forward movement of the bolt carrier causes said cam to move to said first position, at which time the user can pull said trigger member to fire the firearm without manually releasing said trigger member.

15. A firearm trigger mechanism comprising:
 a hammer having a sear catch and a hook for engaging a disconnecter and adapted to be mounted in a fire control mechanism pocket of a receiver to pivot on a transverse hammer pivot axis between set and released positions, said hammer adapted to be pivoted rearward by rearward movement of a bolt carrier,
 a trigger member having a sear and adapted to be mounted in the fire control mechanism pocket to pivot on a transverse trigger member pivot axis between set and released positions,
 wherein said sear and sear catch are in engagement in said set positions of said hammer and trigger member and are out of engagement in said released positions of said hammer and trigger member,
 said disconnecter having a hook for engaging said hammer and adapted to be mounted in the fire control mechanism pocket to pivot on a transverse disconnecter pivot axis, and
 a cam having a cam lobe and adapted to be movably mounted in the fire control mechanism pocket, said cam being movable between a first position and a second position, in said second position said cam lobe forces said trigger member towards said set position,
 whereupon in a standard semi-automatic mode, said cam is in said first position, rearward movement of the bolt carrier causes rearward pivoting of said hammer such that said disconnecter hook catches said hammer hook, and thereafter the bolt carrier moves forward into battery, at which time a user must manually release said trigger member to free said hammer from said disconnecter to permit said hammer and trigger member to pivot to said set positions so that the user can pull said trigger member to fire the firearm, and
 whereupon in a forced reset semi-automatic mode, said cam is in said second position, rearward movement of the bolt carrier causes rearward pivoting of said hammer such that said disconnecter hook is prevented from

15

catching said hammer hook, and thereafter the bolt carrier moves forward into battery, at which time the user can pull said trigger member to fire the firearm.

16. The trigger mechanism of claim 15, further comprising:

a housing having a first pair of transversely aligned openings with a hammer pin therethrough and a second pair of transversely aligned openings with a trigger member pin therethrough,

said hammer mounted on said hammer pin, said trigger member and disconnector mounted on said trigger member pin.

17. The trigger mechanism of claim 15, further comprising a spring which biases said trigger member towards said set position.

18. The trigger mechanism of claim 17, wherein said spring is a torsion spring.

19. The trigger mechanism of claim 15, wherein the trigger member pivot axis and disconnector pivot axis are coaxial.

20. A firearm trigger mechanism comprising:

a hammer having a sear catch and a hook for engaging a disconnector and adapted to be mounted in a fire control mechanism pocket of a receiver to pivot on a transverse hammer pivot axis between set and released positions, said hammer adapted to be pivoted rearward by rearward movement of a bolt carrier,

a trigger member having a sear and adapted to be mounted in the fire control mechanism pocket to pivot on a transverse trigger member pivot axis between set and released positions,

wherein said sear and sear catch are in engagement in said set positions of said hammer and trigger member and are out of engagement in said released positions of said hammer and trigger member,

a disconnector having a hook for engaging said hammer and adapted to be mounted in the fire control mechanism pocket to pivot on said transverse disconnector pivot axis,

16

a cam having a cam lobe and adapted to be movably mounted in the fire control mechanism pocket, said cam being movable between a first position at which said cam lobe does not force said trigger member into said set position and a second position at which said cam lobe does force said trigger member into said set position, and

a safety selector adapted to be movably mounted in the fire control mechanism pocket to move between safe, standard semi-automatic, and forced reset semi-automatic positions,

whereupon in said standard semi-automatic position, said cam is in said first position, rearward movement of the bolt carrier causes rearward pivoting of said hammer such that said disconnector hook catches said hammer hook, and thereafter the bolt carrier moves forward into battery, at which time a user must manually release said trigger member to free said hammer from said disconnector to permit said hammer and trigger member to pivot to said set positions so that the user can pull said trigger member to fire the firearm, and

whereupon in said forced reset semi-automatic position, said cam is in said second position, rearward movement of the bolt carrier causes rearward pivoting of said hammer such that said disconnector hook is prevented from catching said hammer hook, and thereafter the bolt carrier moves forward into battery, at which time the user can pull said trigger member to fire the firearm.

21. The trigger mechanism of claim 20, wherein said cam is not a part of said safety selector.

22. The trigger mechanism of claim 20, wherein said safety selector moves between safe, standard semi-automatic, and forced reset semi-automatic positions by rotation.

23. The trigger mechanism of claim 20, wherein the trigger member pivot axis and disconnector pivot axis are coaxial.

* * * * *