


(19) **United States**(12) **Patent Application Publication**
Dorenbosch et al.(10) **Pub. No.: US 2002/0173308 A1**(43) **Pub. Date: Nov. 21, 2002**(54) **INSTANT MESSAGE PROXY FOR CIRCUIT
SWITCHED MOBILE ENVIRONMENT**(52) **U.S. Cl. 455/435; 455/432; 455/421**(75) **Inventors: Jheroen P. Dorenbosch, Paradis, TX
(US); Kevin C. Mowry, Irving, TX
(US)**(57) **ABSTRACT**

Correspondence Address:

**MOTOROLA INC
5401 NORTH BEACH STREET
MAILSTOP E230
FORT WORTH, TX 76137**(73) **Assignee: MOTOROLA, INC.**(21) **Appl. No.: 09/855,385**(22) **Filed: May 15, 2001****Publication Classification**(51) **Int. Cl.⁷ H04Q 7/20**

An instant message (IM) proxy according to the present invention is capable of maintaining the availability status of a mobile subscriber even when the mobile subscriber is roaming or temporarily out of a mobile network coverage area, and even after the IM proxy unsuccessfully attempts to send an instant message to the mobile subscriber. Messages will continue to be re-sent to the mobile subscriber in the near-real time manner characteristic of a typical instant message system until IM parameters programmed into a retry counter and/or the timer located at the proxy are exceeded and the IM proxy drops the message. In addition, the IM proxy of the present invention is capable of bundling instant messages intended for the mobile subscriber to minimize mobile system overhead connection costs while at the same time minimizing IM system latency

10




FIG. 1




FIG. 2





FIG. 3

FIG. 4






FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9

INSTANT MESSAGE PROXY FOR CIRCUIT SWITCHED MOBILE ENVIRONMENT

BACKGROUND OF THE INVENTION

[0001] 1. Field of the Invention

[0002] The present invention relates generally to instant message systems, and more particularly to an instant message proxy that is capable of maintaining the availability status of a mobile subscriber when the communicating to the subscriber is temporarily broken.

[0003] 2. Background of the Invention

[0004] Conventional instant message (IM) systems use a variety of system architectures. However, such systems typically require that potential IM participants, often referred to as buddies, must register and establish a connection with an IM login server. Participant-specific information, such as presence contact information, is generated through this registration and is stored in a database associated with the IM login server for the duration of the IM session. Additionally, the IM login server uses the connection to determine the presence status of the buddy; if the connection is broken, the buddy is unavailable. Once IM participants are registered with the IM login server, messages sent between registered participants are typically routed through an IM message server or servers to the respective designated target buddy or buddies.

[0005] The above-described conventional IM systems have certain associated limitations when one or more of the participants in an IM session communicate via an IM-enabled mobile station such as a mobile handset. Specifically, IM systems typically rely on a best-effort delivery mechanism in which a message intended for a target buddy is delivered if the IM login server determines that the target buddy is available. If the IM login server determines that the target buddy is not available, the message is dropped. Because a mobile station participant may move in and out of service during an IM session, it may not be possible for the mobile station to maintain a reliable connection with the login server. If the connection is lost, messages targeted at the mobile station will be inadvertently dropped.

[0006] In addition, a circuit-switched mobile network has both a considerable delay associated with an IM connection set-up and a high cost associated with maintaining an open connection during an IM session. Therefore, it is not economically practical to implement an IM system with mobile network subscribers by establishing and then maintaining open connections for the duration of IM sessions.

BRIEF DESCRIPTION OF THE DRAWINGS

[0007] Additional objects and advantages of the present invention will be more readily apparent from the following detailed description of preferred embodiments thereof when taken together with the accompanying drawings in which:

[0008] **FIG. 1** is a system diagram of an IM system of a preferred embodiment in accordance with the present invention;

[0009] **FIG. 2** is a more detailed block diagram of the IM proxy shown in **FIG. 1**;

[0010] **FIG. 3** is a block diagram of the components of an IM message packet of the type sent over the system shown in **FIG. 1**;

[0011] **FIG. 4** is a timing diagram illustrating an IM session setup between a source buddy and a target buddy in the system shown in **FIG. 1**;

[0012] **FIG. 5** is a timing diagram illustrating message transmission protocol between the source and target buddies shown in **FIG. 4**;

[0013] **FIG. 6** is a timing diagram illustrating further message transmission protocol between the source and target buddies shown in **FIG. 4**;

[0014] **FIG. 7** is a timing diagram illustrating message transmission protocol between the source and target buddies shown in **FIG. 4** over an IM system of another preferred embodiment in accordance with the present invention;

[0015] **FIG. 8** is a timing diagram illustrating IM proxy message buffering protocol; and

[0016] **FIG. 9** is a timing diagram further illustrating message transmission protocol between multiple source buddies and the target buddy of **FIG. 4** over the IM system discussed in connection with **FIGS. 7 and 8**.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0017] Referring now to the drawings in which like numerals reference like parts, **FIG. 1** shows an architecture of an IM system **10** that accommodates both a mobile subscriber, represented generally by the wireless handset, **12**, and a conventional subscriber, represented generally by a personal computer **14**. While it should be understood that the system architecture is capable of supporting plural IM sessions among numerous mobile and/or conventional subscribers, only the single mobile subscriber **12** and the single conventional subscriber **14** are shown for discussion purposes.

[0018] The IM system **10** includes an IM login server **16**. All IM system subscribers must register with the IM login server **16** to become available for and participate in an IM session. The IM login server **16** includes a login database **18** for storing subscriber information, such as presence information for informing subscriber buddies of the login presence of the subscriber, contact information indicating that a subscriber is available for receiving instant messages, and/or other similar subscriber-specific information and parameters that the IM login server **16** detects and receives based on subscriber registration. The IM system **10** may also include one or more IM message servers, such as the IM servers **20, 22**, for facilitating passage of instant messages between subscribers who have registered with the IM login server **16** in a manner known to those skilled in the art.

[0019] In addition to the above components, the IM system **10** also includes an IM proxy **24** according to the present invention that is located in a message pathway between the mobile subscriber **12** and both the IM login server **16** and the IM message servers **20, 22**. The IM proxy **24** functions to set up a connection, such as an IP connection, with the IM login server **16** for the mobile subscriber **12** and for facilitating information flow between the IM login server **16** and the mobile subscriber **12** once the connection is established. The IM proxy **24** is preferably a UNIX or NT server, and is preferably associated with a wireless circuit switched mobile network represented generally at **26**. More specifically, the

IM proxy 24 is preferably housed within a mobile services switching center (MSC) 28. Alternatively, the IM proxy 24 may be located in proximity to the MSC 28, or housed in, or located in proximity to, a base station, a base station controller, a GSN regional network controller, a packet data system controller (GSM SGSN), or a packet data gateway (GSM GGSN or CDMA 2000 PDSN), all of which are known mobile network entities.

[0020] FIG. 2 shows the IM proxy 24 in more detail. The IM proxy 24 includes multiple ports, such as ports 32a-32c, for establishing an IP connection 34a with the mobile subscriber 12 and IP (TCP or UDP) connections 34b, 34c with the IM login server 16 and the IM servers 20, 22. A message buffer 36 stores instant messages intended for the mobile subscriber 12 based on IM system parameters discussed below. A retry counter 38 and a timer 40 enable the IM proxy 24 to maintain its IP connection with the IM login server 16, and therefore maintain the mobile subscriber's registered status with the IM login server 16, when the mobile subscriber 12 becomes temporarily unavailable due to roaming or the like, by causing the IM proxy 24 to re-send a message intended for the mobile subscriber 12 a predetermined number of times within a predetermined time period before the IM proxy 24 drops the message from the message buffer 36. The number of times that a message is re-sent and the time period within which the message is resent are parameters that may be programmed into the IM proxy 24 based on system or subscriber requirements. Through utilization of the retry counter 38 and/or the timer 40, the IM proxy 24 minimizes the number of times that instant messages intended for the mobile subscriber 12 are dropped when the mobile subscriber 12 temporarily roams outside a designated mobile coverage area or otherwise temporarily becomes unavailable from the standpoint of the IM login server 16. The reader will note that the word "connection" as used in TCP Systems does not have the same meaning in UDP system. As used here 'connections' mean some way for two entities to exchange messages.

[0021] FIG. 3 illustrates the basic structure of an instant message 42 of the type that is transmitted across the IM system 10. The instant message structure is similar to that of an email message and includes both a message header 44 and a message body 46. The header 44 includes both target buddy "To" and source buddy "From" subheaders 48, 50. The target buddy subheader 48 contains information that identifies a subscriber who is intended to receive the instant message 48, while the source buddy subheader 50 contains information that identifies an IM subscriber who is sending the instant message. The header 44 may also contain other information such as timestamp and subject information. The message body 46 contains the actual message that is to be communicated to the target buddy. As will now be described, the IM proxy 24 efficiently utilizes the information in the target buddy and source buddy subheaders 48, 50 to manage IM sessions between a mobile subscriber, such as the mobile subscriber 12, and buddies of the mobile subscriber, and in a manner that minimizes the occurrence of instant messages intended for the mobile subscriber being dropped.

[0022] Referring now to the timing diagrams shown in FIGS. 4-6, operation of the IM proxy 24 within the IM system 10 will now be discussed. Although only the mobile subscriber (target buddy) 12 and the conventional subscriber (source buddy) 14 are shown as being registered with the IM

login server 16 (FIG. 1) and as communicating with the IM proxy 24, it should be understood that multiple source buddies (either mobile or conventional subscribers) are capable of communicating with multiple target buddies (either mobile or conventional subscribers) via the functionality implemented at the IM proxy 24.

[0023] Specifically, FIG. 4 illustrates a situation in which the mobile subscriber 12 is available for receiving instant messages from the conventional subscriber 14. Initially, at 52 the conventional subscriber 14 transmits an instant message intended for the mobile subscriber 12 after receiving an indication from the IM proxy 24 that the mobile subscriber 12 is logged on to the IM system 10 and is therefore available to participate in an IM session. The target buddy subheader 48 of the instant message identifies the mobile subscriber 12 as the target buddy, while the source buddy subheader 50 identifies the conventional subscriber 14 as the source buddy. The instant message is first delivered 52 to the IM proxy 24 and then at 54 is forwarded to the mobile subscriber 12. Because the mobile subscriber 12 is registered and online when the instant message is forwarded from the IM proxy 24, the mobile subscriber 12 receives the message in real time and at 56 acknowledges receipt of the message by sending an Ack message back to the conventional subscriber 14. The IM proxy 24 receives the Ack message and then forwards it at 58 to the conventional subscriber 14 as confirmation that the mobile subscriber 12 received the message sent at 52.

[0024] FIG. 5 illustrates a situation in which the mobile subscriber 12 temporarily travels outside the coverage area of the mobile network 26. At 60, the conventional subscriber 14 transmits an instant message to the mobile subscriber 12 after learning via the IM proxy 24 that the mobile subscriber 12 is logged on to the IM system 10 and therefore available to participate in an IM session. The instant message is first delivered to the IM proxy 24 and then at 62 the IM proxy 24 attempts to deliver the message to the mobile subscriber 12. However, if the mobile subscriber 12 temporarily loses coverage and is therefore unavailable to receive the message sent at 60, it does not receive the message and therefore, as indicated at 64, does not reply with an Ack message. Subsequently, the IM proxy 24 increments the retry counter 38 and starts the timer 40 before again attempting to send the message, as indicated at 66 and 68, as long as the number of retries has not exceeded a predetermined limit tracked by and programmed into the retry counter 38 and as long as the predetermined time period tracked by the timer 40 has not expired. The number of retries, the delay between delivery attempts, and the predetermined time period are parameters that are preferably based on system latency characteristics, such as network reliability, network location, the load on the proxy, the time of day, and the identity of the source or target buddy. However, these parameters may also be determined based on individual service options paid for by each subscriber, subscriber classes, subscriber usage habits, and the like.

[0025] Once the retry counter 38 and the timer 40 are enabled, the IM proxy 24 periodically informs the conventional subscriber 14 that, as indicated at 70, it is in the process of trying to deliver the message. However, the mobile subscriber will continue to fail to reply with an Ack

message, as indicated at **72** and **74**, as long as the mobile subscriber **12** remains outside of the mobile network coverage area.

[0026] If the mobile subscriber re-enters the mobile network coverage area before the number of retries exceeds the predetermined limit tracked by and programmed into the retry counter **38** and before the predetermined time period tracked by the timer **40** expires, the IM proxy **24** stops and resets the retry counter **38** and the timer **40**. Upon finally receiving the instant message at **76**, the mobile subscriber **12** responds by sending an Ack message at **78** back to the conventional subscriber **14**. The IM proxy **24** receives the Ack message from the mobile subscriber **12** and at **80** forwards it to the conventional subscriber **14** as confirmation that the mobile subscriber **12** received the instant message. The IM proxy **24** then stops and resets the retry counter **38** and the timer **40**.

[0027] While the above operation of the IM proxy **24** has been described with respect to an IM session between a mobile subscriber and a conventional subscriber, it should be appreciated that the message protocol of the IM proxy is capable of being implemented for IM sessions between two or more mobile subscribers as well as IM sessions between two or more mobile subscribers and two or more conventional subscribers. For IM sessions in which there are three or more participants, the retry counter **38** and the timer **40** are capable of tracking multiple attempted message deliveries to multiple mobile subscribers. Alternatively, there may be multiple instantiations of the IM proxy within the IM system; namely, one IM proxy per mobile station. Also, it should be appreciated that the proxy **24** can be implemented with only a counter when the number of retries is limited, or with only a timer when the proxy is designed to retry an unlimited number of times until the timer expires.

[0028] FIG. 6 illustrates a situation in which the mobile subscriber **12** becomes unavailable for receiving instant messages for a period of time that exceeds the number of retries allotted by and programmed into the retry counter and/or the predetermined time period allotted by the timer **40**. The sequence of messaging events **60-74** are identical to those discussed in connection with FIG. 5. However, the message events **82, 84** differ from the message events **76, 78**. Specifically, if the mobile subscriber **12** fails to re-enter the mobile network coverage area and therefore remains incapable of receiving the instant message from the conventional subscriber **14**, the IM proxy **24** again unsuccessfully re-tries at **82** to forward the message to the mobile subscriber **12**. The mobile subscriber **12** does not receive the message and, as indicated at **84**, therefore does not send an Ack message back to the conventional subscriber **14**.

[0029] Subsequent to the IM proxy **24** re-trying to send the message at **82**, the number of times that the IM proxy tries to send the message exceeds the predetermined limit allotted by and programmed into the retry counter **38** and/or the predetermined time period allotted by the timer **40** expires. As a result, the IM proxy **24** discontinues its attempts to forward the message to the mobile subscriber **12** and drops the message. At **86** it sends a delivery failure indication to the conventional subscriber **14**. Preferably the delivery failure indication will be formatted to appear as though it is sent from the mobile subscriber **12** and to explain that the mobile subscriber **12** is connected via the wireless network **28**. Once

the delivery failure indication is delivered at **86**, the IM proxy **24** then drops the connection between it and the conventional subscriber **14**. In addition, at **88** the IM proxy **24** also drops its connection with the IM login server **16** after indicating to the IM server **16** that the mobile subscriber **12** is unavailable. Dropping this connection can take numerous forms depending on the underlying transport system. In a TCP system the handshake is discontinued. In UDP systems, a message explicitly indicating unavailability, explicit de-registration, or perhaps allowing the expiration of a registration timer can be used.

[0030] In view of the above, it should now be appreciated that the IM proxy **24** of the instant message system of the present invention is capable of maintaining a mobile subscriber's availability status. Therefore, the mobile subscriber continues to appear available to IM buddies when the mobile subscriber is roaming or temporarily out of service even after the IM proxy unsuccessfully attempts to send an instant message to the mobile subscriber. Messages will continue to be re-sent to the mobile subscriber in the near-real time manner characteristic of a typical instant message system until IM parameters programmed into the retry counter **38** and/or the timer **40** are exceeded and the IM proxy drops the message.

[0031] Turning now to FIGS. 7 and 8, the functionality of the IM proxy **24** will now be described according to another embodiment of the present invention. It should be understood that the underlying IM system of the embodiment discussed in connection with FIGS. 7 and 8 is substantially identical to that shown in FIGS. 1-3 except for those components labeled with different reference numerals.

[0032] Specifically, FIG. 7 illustrates an IM session between the mobile subscriber **12** and the conventional subscriber **14** in which the IM proxy **24'** bundles instant messages sent to the mobile subscriber **12** based on certain predetermined parameters discussed below. After both the mobile subscriber **12** and the conventional subscriber **14** come online and register with the IM server **16** (FIG. 1), the mobile subscriber **12** sends a message via the IM proxy at **90** to the conventional subscriber **14**. The IM server **20** receives the message and then forwards the message at **92** to the conventional subscriber **14** based on information contained in the target buddy subheader **48** (FIG. 3).

[0033] After receiving the message, the conventional subscriber **14** responds by sending a message at **94** back to the mobile subscriber **12** through the IM server **20** and the IM proxy **24'**. However, the IM proxy **24'** recognizes, via information contained in the target buddy subheader **48** (FIG. 3), that the message is intended for the mobile subscriber **12**. To minimize connection overhead in the circuit switched mobile network **28**, the IM proxy **24'** does not maintain an open connection with the mobile subscriber **12**. Specifically, the IM proxy **24'** registers with the IM server **16** (FIG. 1) on behalf of the mobile subscriber **12** and provides availability information to mobile subscriber buddies such as the conventional subscriber **14**. However, it does not maintain a constant connection with the mobile subscriber **12**, but instead bundles instant messages for the mobile subscriber **12** and notifies the mobile subscriber **12** that instant messages are available for download from the message buffer **36** (FIG. 2) only when the mobile subscriber **12** has multiple messages stored in the message buffer **36** or,

alternatively, only after at least one instant message has been stored in the message buffer 36 for a certain amount of time. Alternatively, the proxy 24' may notify the mobile subscriber 12 by sending the instant messages from the message buffer 36 to the mobile subscriber 12. Therefore, in the current example, the IM proxy 24' stores the instant message forwarded at 96 from the IM server 20 until the above discussed, or other system-specific, downlink parameters are met.

[0034] In the meantime, the mobile subscriber 12 may send an additional message at 98 to the conventional subscriber 14 asking whether the conventional subscriber 14 received the message sent at 90. After receiving the message, the conventional subscriber 14 again responds by sending a message at 102 back to the mobile subscriber 12 through the IM server 20. However, the IM proxy 24' again recognizes, via information contained in the target buddy subheader 48 (FIG. 3), that the message is intended for the mobile subscriber 12, and therefore stores the instant message in the message buffer 36 until a downlink is established with the mobile subscriber 12.

[0035] As indicated by the message sequences shown at 106-112, this cycle may be repeated until the IM proxy 24' determines that it is time to forward all stored instant messages to the mobile subscriber 12. If, for example, the IM proxy 24' is programmed to forward instant messages to the mobile subscriber 12 when the number of stored instant messages reaches 3, the IM proxy 14 will establish a downlink connection with the mobile subscriber 12 and, as indicated at 114, will forward the three stored messages to the mobile subscriber 12. Therefore, even though some latency is introduced into the IM system, overall system connection overhead is reduced.

[0036] FIG. 8 illustrates an IM session involving the mobile subscriber 12 and multiple buddies, such as conventional subscribers 14, 14' and 14", in which the IM proxy 24' stores and bundles instant messages in its buffer 36 from the conventional subscribers 14, 14' and 14" based on predetermined participant parameters to minimize system connection overhead in a manner that also minimizes the amount of latency introduced into the system due to the message bundling.

[0037] For example, after the conventional subscribers 14, 14' and 14" come online and register with the IM login server 16 (FIG. 1), each of the conventional subscribers 14, 14' and 14" sends a message to the mobile subscriber 12 through the IM server 20 and the IM proxy 24'. The IM proxy 24' recognizes, via information contained in the target buddy subheader 48 (FIG. 3) of each of the messages, that the messages sent at 116-120 are intended for the mobile subscriber 12. The IM proxy 24' then stores and bundles these messages in its message buffer 36 until the IM proxy 24' determines, in a manner that will be discussed in connection with FIG. 9, that the messages should be downloaded to the mobile subscriber 12. When the IM proxy 24' determines that download parameters have been met, the IM proxy 24' establishes a connection with the mobile subscriber 12 and at 122 downloads the stored and bundled messages to the mobile subscriber 12.

[0038] FIG. 9 illustrates an exemplary IM session between the mobile subscriber 12 and multiple buddies, such as conventional subscribers 14, 14' and 14", in which

the IM proxy 24' monitors the number of participants in an IM session, the message rate and the number of stored messages in its buffer from each participant, and bundles instant messages sent to the mobile subscriber 12 based on certain predetermined participant parameters discussed below to minimize system connection overhead in a manner that also minimizes the amount of latency introduced into the system due to the message bundling.

[0039] After both the mobile subscriber 12 and the conventional subscribers 14, 14' and 14" come online and register with the IM server 16 (FIG. 1) through respective connections, the mobile subscriber sends a message at 124 through the IM proxy 24' and the IM server 20 as discussed above to the conventional subscriber 14. After receiving the message, the conventional subscriber 14 responds by sending a message at 126 back to the mobile subscriber 12. The IM proxy 24' recognizes, via information contained in the target buddy subheader 48 (FIG. 3), that the message sent at 126 is intended for the mobile subscriber 12. However, the IM proxy 24' recognizes that the message sent at 126 is from the source buddy from which it had recently received the message sent at 124. The IM session between the mobile subscriber 12 and the conventional subscriber 14 continues in this manner, as exemplified by subsequent messages sent at 128, 130, until the IM proxy 24' is notified by the IM server 20 that additional buddies, such as conventional subscribers 14', 14", have registered with the IM server 20 as indicated generally at 132, 134. As indicated at 136, the IM proxy 24' continues to forward messages to the mobile subscriber 12 as long as the IM proxy 24' continues to detect only messages from a single IM session participant. The IM proxy 24' begins to bundle instant messages intended for the mobile subscriber in the buffer 36 when the IM proxy 24' detects that multiple participants are sending messages, such as those shown at 138-142, to the mobile subscriber 12. The IM proxy 24' then establishes a connection with the mobile subscriber 12 and flushes the IM proxy buffer 36 when a predetermined bundling parameter is met, such as when one of the IM session participants, such as the conventional subscriber 14", sends a second message, such as the message at 144, while a previous message sent from that participant at 138 is being stored in the buffer 36.

[0040] In the present example, the IM proxy 24' forwards the stored instant messages at 146 after it receives the second message at 144 from the conventional subscriber 14". However, the IM proxy 24' can be programmed to cease instant message bundling based on: a predetermined number of IM session participants sending messages to the target buddy within a predetermined time period; more than a predetermined number of IM session participants sending more than a predetermined number of messages to the target buddy within a predetermined time period; an IM session participant sending a second message to the mobile subscriber during message bundling while a previous message sent by the participant is being stored at the IM proxy; more than a predetermined number of messages are stored; a predetermined storage time is exceeded; a predetermined buffer memory threshold is exceeded; the number of IM session participants; call traffic on the wireless system; mobile subscriber subscription parameters; a request or instructions from the mobile subscriber to initiate message bundling; and/or a subsequent connection made by the mobile subscriber for purposes other than the particular IM session.

[0041] Of course, the IM proxy 24' can also be programmed to initiate message bundling operations when one or more of the above parameters is/are no longer met, or when, for example, the mobile subscriber 12 informs the IM proxy 24' that the mobile subscriber no longer wants message bundling.

[0042] It should therefore be understood based on the above discussion in connection with FIGS. 8 and 9 that the IM proxy 24' of the present invention can be programmed to provide message bundling to minimize mobile system overhead connection costs and at the same time minimize IM system latency.

[0043] While the above description is of the preferred embodiment of the present invention, it should be appreciated that the invention may be modified, altered, or varied without deviating from the scope and fair meaning of the following claims.

What is claimed is:

1. A method of compensating for temporary subscriber unavailability in a mobile instant message session environment, comprising:

causing a mobile subscriber to register with an instant message system prior to participating in an instant message session;

indicating availability of the mobile subscriber to buddies of the mobile subscriber;

receiving an instant message intended for the mobile subscriber from one of the buddies; and

dropping the instant message intended for the mobile subscriber from the one of the buddies if the mobile subscriber does not receive the instant message after the instant message is resent a predetermined number of times.

2. The method of claim 1, further comprising automatically unregistering the mobile subscriber after the resending of an instant message intended for the mobile subscriber from one of the buddies for one of a predetermined number of times and a predetermined time period.

3. A mobile subscriber instant message system, comprising:

an instant message proxy for receiving registration information from a mobile subscriber and for subsequently indicating to registered system subscribers participating in an instant message session that the mobile subscriber is available for receiving instant messages;

the instant message proxy further for resending an instant message intended for the mobile subscriber and not received by the mobile subscriber to compensate for mobile network latencies; and

the instant message proxy further for dropping the instant message if the mobile subscriber does not receive the instant message after the instant message is resent a predetermined number of times.

4. The mobile subscriber instant message system of claim 3, wherein the instant message proxy is located in one of a mobile services switching center, a mobile system gateway, and an instant message server.

5. The mobile subscriber instant message system of claim 3, wherein the instant message proxy is located in proximity

to one of a mobile services switching center, a mobile system gateway, and an instant message server.

6. The mobile subscriber instant message system of claim 3, wherein the instant message proxy includes at least one of a timer and a counter programmed to limit the instant message from being sent to the mobile subscriber for at least one of only the predetermined number of times and within a predetermined time period.

7. The mobile subscriber instant message system of claim 3, further comprising a login server with which the mobile subscriber must register prior to participating in an instant message session, the login server for indicating to the registered system subscribers participating in the instant message session that the mobile subscriber is available for receiving instant messages.

8. A method of bundling messages for a mobile subscriber in an instant message system to minimize mobile system connection overhead, comprising:

queuing instant messages intended for the mobile subscriber while the mobile subscriber is not registered with the instant message system;

notifying the mobile subscriber when queued instant message parameters reach a predetermined limit; and

facilitating connection of the mobile subscriber to the instant message system to enable the mobile subscriber to retrieve the queued instant messages.

9. The method of claim 8, wherein the notifying the mobile subscriber when queued instant message parameters reach a predetermined limit comprises notifying the mobile subscriber when the number of queued instant messages intended for the mobile subscriber reaches a predetermined number.

10. The method of claim 8, wherein the notifying the mobile subscriber when queued instant message parameters reach a predetermined limit comprises notifying the mobile subscriber when at least one queued instant message intended for the mobile subscriber has been queued for a predetermined amount of time.

11. The method of claim 10, wherein the notifying the mobile subscriber when queued instant message parameters reach a predetermined limit comprises notifying the mobile subscriber when a predetermined number of buddies send messages intended for the mobile subscriber within a predetermined amount of time.

12. The method of claim 8, wherein the notifying the mobile subscriber when queued instant message parameters reach a predetermined limit comprises notifying the mobile subscriber when a predetermined number of buddies send a predetermined number of messages intended for the mobile subscriber within a predetermined amount of time.

13. The method of claim 8, wherein the notifying the mobile subscriber when queued instant message parameters reach a predetermined limit comprises notifying the mobile subscriber when a buddy sends a second message intended for the mobile subscriber subsequent to sending a first unanswered message.

14. The method of claim 8, wherein the notifying the mobile subscriber when queued instant message parameters reach a predetermined limit is based at least in part on a number of instant message session participants.

15. The method of claim 8, wherein the notifying the mobile subscriber when queued instant message parameters

reach a predetermined limit is based at least in part on one of mobile network traffic parameters and mobile subscriber subscription parameters.

16. The method of claim 8, wherein the predetermined limit in the notifying the mobile subscriber when queued instant message parameters reach a predetermined limit is based at least in part on mobile subscriber-based instructions.

17. The method of claim 8, further comprising:

causing the mobile subscriber to register with the instant message system when the mobile subscriber wants to participate in an instant message session; and

indicating to buddies of the mobile subscriber that the mobile subscriber is available for receiving instant messages.

18. The method of claim 8, further comprising downloading the queued instant messages intended for the mobile subscriber when one of a high priority instant message is received and the mobile subscriber sends an outgoing message.

19. The method of claim 8, further comprising notifying buddies of the mobile subscriber that the mobile subscriber

is connected through a wireless system upon initiation of the queuing of instant messages intended for the mobile subscriber while the mobile subscriber is not registered with the instant message system.

20. A mobile subscriber instant message system, comprising:

an instant message proxy located between a mobile subscriber and at least one instant message buddy of the mobile subscriber for queuing instant messages intended for the mobile subscriber while the mobile subscriber is not registered;

the instant message proxy further for notifying the mobile subscriber when queued instant message parameters reach a predetermined limit; and

the instant message proxy further for enabling the mobile subscriber to retrieve the queued instant messages when the queued instant message parameters reach the predetermined limit.

* * * * *