Doc Code: PA..
Document Description: Power of Attorney

PTO/AIA/82A (07-13)
Approved for use through 01/31/2018. OMB 0651-0035
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

TRANSMITTAL FOR POWER OF ATTORNEY TO ONE OR MORE REGISTERED PRACTITIONERS

NOTE: This form is to be submitted with the Power of Attorney by Applicant form (PTO/AIA/82B) to identify the application to which the Power of Attorney is directed, in accordance with 37 CFR 1.5, unless the application number and filing date are identified in the Power of Attorney by Applicant form. If neither form PTO/AIA/82A nor form PTO/AIA82B identifies the application to which the Power of Attorney is directed, the Power of Attorney will not be recognized in the application.

Application Number	Not Yet Known
Filing Date	Herewith
First Named Inventor	John A. Nix
Title	Key Derivation for a Module Using an Embedded Universal Integrated Circuit Card
Art Unit	
Examiner Name	
Attorney Docket Number	63121/0224

SIGNATURE of Applicant or Patent Practitioner

Signature	/Keith J. Barkaus/	Date (Optional)	2023-08-03
Name	Keith J. Barkaus	Registration Number	51,431
Title (if Applicant is a juristic entity)			
Applicant Name (if Applicant is a juristic entity)			

NOTE: This form must be signed in accordance with 37 CFR 1.33. See 37 CFR 1.4(d) for signature requirements and certifications. If more than one applicant, use multiple forms.

☑ *Total of 1 forms are submitted.

This collection of information is required by 37 CFR 1.131, 1.32, and 1.33. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.11 and 1.14. This collection is estimated to take 3 minutes to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.**

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

Doc Code: PA..
Document Description: Power of Attorney

PTO/AIA/82B (07-13)
Approved for use through 11/30/2014. OMB 0651-0051
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number

POWER OF ATTORNEY BY APPLICANT

I hereby revoke all previous powers of attorney given in the application identified in either the attached transmittal letter or the boxes below.

Application Number	Filing Date

(Note: The boxes above may be left blank if information is provided on form PTO/AIA/82A.)

☑ I hereby appoint the Patent Practitioner(s) associated with the following Customer Number as my/our attorney(s) or agent(s), and to transact all business in the United States Patent and Trademark Office connected therewith for the application referenced in the attached transmittal letter (form PTO/AIA/82A) or identified above: 01912

OR

☐ I hereby appoint Practitioner(s) named in the attached list (form PTO/AIA/82C) as my/our attorney(s) or agent(s), and to transact all business in the United States Patent and Trademark Office connected therewith for the patent application referenced in the attached transmittal letter (form PTO/AIA/82A) or identified above. (Note: Complete form PTO/AIA/82C.)

Please recognize or change the correspondence address for the application identified in the attached transmittal letter to:

☑ The address associated with the above-mentioned Customer Number

OR

☐ The address associated with Customer Number:

OR

Firm or Individual Name					
Address					
City		State		Zip	
Country					
Telephone		Email			

I am the Applicant (if the Applicant is a juristic entity, list the Applicant name in the box):

NETWORK-1 TECHNOLOGIES, INC.

☐ Inventor or Joint Inventor (title not required below)

☐ Legal Representative of a Deceased or Legally Incapacitated Inventor (title not required below)

☑ Assignee or Person to Whom the Inventor is Under an Obligation to Assign (provide signer's title if applicant is a juristic entity)

☐ Person Who Otherwise Shows Sufficient Proprietary Interest (e.g., a petition under 37 CFR 1.46(b)(2) was granted in the application or is concurrently being filed with this document) (provide signer's title if applicant is a juristic entity)

SIGNATURE of Applicant for Patent

The undersigned (whose title is supplied below) is authorized to act on behalf of the applicant (e.g., where the applicant is a juristic entity).

Signature		Date (Optional)	
Name	Corey M. Horowitz		
Title	Chairman and CEO		

NOTE: Signature - This form must be signed by the applicant in accordance with 37 CFR 1.33. See 37 CFR 1.4 for signature requirements and certifications. If more than one applicant, use multiple forms.

☑ Total of 1 forms are submitted.

This collection of information is required by 37 CFR 1.131, 1.32, and 1.33. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.11 and 1.14. This collection is estimated to take 3 minutes to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.**

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

PTO/AIA/01 (06-12)
Approved for use through 01/31/2014. OMB 0651-0032
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

DECLARATION (37 CFR 1.63) FOR UTILITY OR DESIGN APPLICATION USING AN APPLICATION DATA SHEET (37 CFR 1.76)

Title of Invention	Key Derivation for a Module using an Embedded Universal Integrated Circuit Card

As the below named inventor, I hereby declare that:

This declaration is directed to:

- [■] The attached application, or
- [ ] United States application or PCT international application number _____

  filed on _____.

The above-identified application was made or authorized to be made by me.

I believe that I am the original inventor or an original joint inventor of a claimed invention in the application.


I hereby acknowledge that any willful false statement made in this declaration is punishable under 18 U.S.C. 1001 by fine or imprisonment of not more than five (5) years, or both.

WARNING:

Petitioner/applicant is cautioned to avoid submitting personal information in documents filed in a patent application that may contribute to identity theft. Personal information such as social security numbers, bank account numbers, or credit card numbers (other than a check or credit card authorization form PTO-2038 submitted for payment purposes) is never required by the USPTO to support a petition or an application. If this type of personal information is included in documents submitted to the USPTO, petitioners/applicants should consider redacting such personal information from the documents before submitting them to the USPTO. Petitioner/applicant is advised that the record of a patent application is available to the public after publication of the application (unless a non-publication request in compliance with 37 CFR 1.213(a) is made in the application) or issuance of a patent. Furthermore, the record from an abandoned application may also be available to the public if the application is referenced in a published application or an issued patent (see 37 CFR 1.14). Checks and credit card authorization forms PTO-2038 submitted for payment purposes are not retained in the application file and therefore are not publicly available.

LEGAL NAME OF INVENTOR

Inventor: John A. Nix Date (Optional): November 18, 2013

Signature: 

Note: An application data sheet (PTO/SB/14 or equivalent), including naming the entire inventive entity, must accompany this form or must have been previously filed. Use an additional PTO/AIA/01 form for each additional inventor.

This collection of information is required by 35 U.S.C. 115 and 37 CFR 1.63. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.11 and 1.14. This collection is estimated to take 1 minute to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.**

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICATION FOR UNITED STATES PATENT

Title: **Key Derivation for a Module using an Embedded Universal Integrated Circuit Card**

Inventor: John A. Nix
807 Davis St., Unit 2207
Evanston, IL 60201
Citizen of the United States of America

Petitioner Samsung Ex-1004, 0004

CROSS-REFERENCE TO RELATED APPLICATIONS

This is a continuation of U.S. Patent Application No. 17/304,922, filed June 28, 2021, which is a continuation of U.S. Patent Application No. 16/879,325, filed May 20, 2020, which is a continuation of U.S. Patent Application No. 16/201,401, filed November 27, 2018, and which issued as U.S. Patent No. 10,700,856, which is a continuation of U.S. Patent Application No. 15/680,758, filed August 18, 2017, and which issued as U.S. Patent No. 10,187,206, which is a continuation of U.S. Patent Application No. 15/130,146, filed April 15,2016, and which issued as U.S. Patent No. 9,742,562, which is a continuation of U.S. Patent Application No. 14/084,141, filed November 19, 2013, and which issued as U.S. Patent No. 9,319,223, each of which is fully incorporated by reference herein.

The subject matter of this application is related to the subject matter of U.S. Patent Application Serial No. 14/023,181, filed September 10, 2013 in the name of John Nix, entitled "Power Management and Security for Wireless Modules in 'Machine-to-Machine' Communications," which is hereby incorporated by reference in its entirety.

The subject matter of this application is also related to the subject matter of U.S. Patent Application Serial No. 14/039,401, filed September 27, 2013 in the name of John Nix, entitled "Secure PKI Communications for 'Machine-to-Machine' Modules, including Key Derivation by Modules and Authenticating Public Keys," which is hereby incorporated by reference in its entirety.

The subject matter of this application is also related to the subject matter of U.S. Patent Application Serial No. 14/055,606, filed October 16, 2013 in the name of John Nix, entitled "Systems and Methods for 'Machine-to-Machine' (M2M) Communications Between Modules, Servers, and an Application using Public Key Infrastructure (PKI)," which is hereby incorporated by reference in its entirety.

The subject matter of this application is also related to the subject matter of U.S. Patent Application Serial No. 14/064,618, filed October 28, 2013 in the name of John Nix, entitled "A Set of Servers for "Machine-to-Machine" Communications using Public Key Infrastructure," which is hereby incorporated by reference in its entirety.

BACKGROUND

Technical Field

The present methods and systems relate to communications for a module, and more particularly, to methods and systems for supporting an embedded universal integrated circuit card (eUICC) in a module,

Petitioner Samsung Ex-1004, 0005

where the module can securely and efficiently derive keys for communicating with a server and a wireless network, including shared secret keys and key pairs for use with public key infrastructure (PKI).

Description of Related Art

The combination of "machine-to-machine" (M2M) communications and using low-cost sensors, Internet connections, and processors is a promising and growing field. Among many potential benefits, M2M technologies allow the remote monitoring and/or control of people, assets, or a location where manual monitoring is not economic, or costs can be significantly reduced by using automated monitoring as opposed to manual techniques. Prominent examples today include vending machines, automobiles, alarm systems, and remote sensors. Fast growing markets for M2M applications today include tracking devices for shipping containers or pallets, health applications such as, but not limited to, the remote monitoring of a person's glucose levels or heartbeat, monitoring of industrial equipment deployed in the field, and security systems. Many M2M applications leverage either wired Internet connections or wireless connections, and both types of connections continue to grow rapidly. M2M applications may also be referred to as "the Internet of things".

M2M communications can provide remote control over actuators that may be connected to a M2M device, such as, but not limited to, turning on or off a power switch, locking or unlocking a door, adjusting a speed of a motor, or similar remote control. A decision to change or adjust an actuator associated with an M2M device can utilize one or a series of sensor measurements. An M2M device may also be referred to as a "wireless module" or also simply a module. As one example, if a building or room is too cold, then temperature can be reported to a central server by an M2M device and the server can instruct the M2M device to turn on a switch that activates heat or adjusts a thermostat. As the costs for computer and networking hardware continue to decline, together with the growing ease of obtaining either wired or wireless Internet access for small form-factor devices, the number of economically favorable applications for M2M communications grows.

Many M2M applications can leverage wireless networking technologies. Wireless technologies such as, but not limited to, wireless local area networks and wireless wide area networks have proliferated around the world over the past 15 years, and usage of these wireless networks is also expected to continue to grow. Wireless local area network (LAN) technologies include WiFi and wireless wide area network (WAN) technologies include 3rd Generation Partnership Project's (3GPP) 3rd Generation (3G) Universal Mobile Telecommunications System (UMTS) and 4th Generation (4G) Long-term Evolution (LTE), LTE Advanced, and the Institute of Electrical and Electronics Engineers' (IEEE) 802.16 standard, also known as WiMax. The use of wireless technologies with "machine-to-machine" communications creates new opportunities for

Petitioner Samsung Ex-1004, 0006

the deployment of M2M modules in locations less suitable for fixed-wire Internet access, but also creates a significant new class of problems that need to be solved.

One class of problems for using M2M modules with traditional wireless networks results from basic design considerations for the wireless networks, where many wireless wide-area networking standards were designed and optimized for mobile phones, including smart phones. A core element of traditional wireless WAN technologies such as 3GPP and ETSI standards over the past 20 years has included the use of a subscriber identity module (SIM) card within 2G networks and a related universal integrated circuit card (UICC) for 3G and 4G networks, including LTE networks. ETSI standards for a physical UICC as of 2013 include ETSI TR 102 216. Traditionally, these cards have been supplied by a mobile network operator (MNO) and contain a pre-shared secret key K in addition to a set of parameters for a mobile phone or user equipment to connect with the wireless network operated by the MNO. The parameters could include (i) an identity such as an IMSI, (ii) a set of frequencies for a mobile phone to scan in order to locate a beacon signal from the MNO, (iii) a preferred access list of other MNOs in order to support roaming in locations where the MNI associated with the IMSI is not available, and (iv) many other related parameters as well. The physical media and cards in the form of a UICC can be appropriate or suitable for a mobile phone or mobile handset, where an end user can readily replace or "swap out" the physical card as the mobile phone changes geographical locations or due to other preferences for the subscriber or end-user. Distributors of either mobile handsets or mobile phone service can physically insert or change an appropriate UICC for the mobile phones as well.

However, the rapid growth for "machine-to-machine" applications has created significant challenges to the traditional model of utilizing physical media such as a UICC in order to provide data and parameters for a module's connectivity to a MNO. Exemplary reasons for potential difficulties with physical media such as a UICC in M2M applications include (i) the modules may be installed in remote locations that are difficult or expensive to reach after installation, such as, but not limited to, tracking devices on shipping containers that can move globally, (ii) a manufacturer or service provider may prefer for the module to be hermetically sealed for business or technical reasons, including the physical UICC may not be easily tampered with, and (iii) a module (such as a tracking device on a 40 foot shipping container) may move between several different countries, and the lowest costs for Internet or data connectivity through the wireless WAN may be through utilizing different UICC cards from different operators, but the cost of swapping the UICC card could be prohibitive.

Other needs for changing a preferred network or network credentials without physically changing a UICC exist as well. These needs have been one motivation for the industry, including ETSI and 3GPP standards bodies, to consider an embedded UICC, also known as an "eUICC". With an eUICC, the

Petitioner Samsung Ex-1004, 0007

operation of an UICC can be essentially "virtualized", such that the data and algorithms within a UICC can be processed in software and distributed through electronic media (such as, but not limited to, a file transfer or file download). Exemplary benefits and technical considerations for using an eUICC in M2M applications as of November 2013 is outlined in ETSI TS 103 383 v12.1, entitled "Smart Cards; Embedded UICC; Requirements Specification," which is herein incorporated by reference in its entirety. Note that this published standard from September 2013, and the standard is primarily in the requirements definition phase, and many of the technical specifications for implementation and operation of an eUICC will be defined in the future.

Although the use of an embedded eUICC can solve many of the issues for distributing and managing physical media such as a UICC, many additional challenges remain. Many open and remaining challenges for a eUICC pertain to securely and electronically transferring a new set of MNO network access credentials (such as an IMSI and network key K) to a module in a secure and efficient manner. A need exists in the art for a module to securely obtain network access credentials. Another need exists in the art for the obtained credentials in a eUICC to be fully compatible with the significant installed and legacy base of networks that use a pre-shared secret key K, where the key K serves as the foundation for authentication and ciphering of data for a mobile phone or user equipment, including modules using conventional technology. A successful solution to these needs for M2M applications in the form of an eUICC can also provide a working solution of the needs for regular mobile phones as well, such that a consumer mobile phone could implement and utilize an eUICC in order to eliminate the costs and complexity of dealing with a physical UICC.

A need exists in the art for module and a mobile network operator to securely share a pre-shared secret key K without depending on physical distribution of the key K or electronic distribution of the key K through 3rd parties, even in an encrypted form. As currently contemplated in November of 2013 by eUICC standards discussed above, a pre-shared secret key K and related network access credentials are transmitted to a module in an encrypted form, including multiple potential layers of encryption and authentication. The pre-shared secret key K is also known as key K in 4G LTE and related networks and key Ki in 3G networks. The resulting security for the electronically transferred, pre-shared secret key K is no stronger than (i) the encryption on the channel used to transfer key K, and (ii) the security and chain of control for keys used to encrypt the communications channel transferring key K to a module or a mobile phone. The MNO using an electronically transferred key K for network access credentials is dependent on the communications channel for transferring key K, even though that communications channel may be outside the control of the MNO (such as at a time when key K is transferred using another MNO or a different network).

In addition, over an extended period of time such as several years, a mobile network operator could prefer for the key K to periodically rotate or change for an individual module or mobile phone in order to

Petitioner Samsung Ex-1004, 0008

increase security. The continued and extended use of a single key K for all communications with a module or mobile phone can be a security risk, especially with a large volume of data transferred that could be subject to analysis for cryptographic weaknesses by potential attackers. Additionally, in the future a standard key length for key K may increase from today's current 128 bits to a longer key length such as an exemplary 256 bits. With conventional technology where key K is recorded in physical media such as a UICC, the only feasible way to change key K for a module or mobile phone is to physically distribute a new UICC card, with resulting costs and business complexities. A need exists in the art for a module, including a mobile phone, and a MNO to securely and efficiently support a change in network access credentials, including a key K for the module connecting to the MNO, without requiring a physical replacement of a UICC or equivalent physical media recording a key K.

And other needs exist in the art as well, as the list recited above is not meant to be exhaustive but rather illustrative.

Petitioner Samsung Ex-1004, 0009

SUMMARY

Methods and systems are provided for secure and efficient communication using a module to communicate with a server and a mobile operator network. The module can support "Machine to Machine" (M2M) communications, also known as "the Internet of things". The methods and systems contemplated herein can also support other applications as well, including mobile phone handsets connecting to a wireless network, where the wireless network can be associated with or the radio access portion of a mobile operator network. A module in the present invention can comprise a mobile phone such as a smartphone. An objective of the invention is to address the challenges noted above for securing the deployment of modules that can utilize an embedded universal integrated circuit card (eUICC) and/or also PKI algorithms and keys. The methods and systems contemplated herein can reduce the need for manual intervention with a module in order to automatically and remotely change network access credentials in order for the module to utilize new or different keys in order to connect and authenticate with a wireless network. By using an eUICC, such as an eUICC supporting the derivation of keys for secure communication of data between a module and a server, the value and usefulness of modules can be increased for a user and a mobile operator network.

Exemplary embodiments may take the form of methods and systems for a module. The module and a server associated with a wireless network or a mobile network operator can include a set of cryptographic algorithms for use in sending and receiving data. The cryptographic algorithms can include asymmetric ciphering algorithms, symmetric ciphering algorithms, secure hash algorithms, digital signature algorithms, key pair generation algorithms, a key derivation function, and a random number generator. The module can utilize a set of cryptographic parameters with the set of cryptographic algorithms. In exemplary embodiments, the module and the server can also include a shared secret algorithm and a secret ciphering algorithm.

The module can utilize the set of cryptographic algorithms and the set of cryptographic parameters to securely generate or derive module private keys and module public keys. A module private key and module public key can be generated either (i) upon manufacturing, distribution, installation, or an initial use of the module, or (ii) at subsequent times after initial use such as when a new set of key pairs are required or are useful for continued operation of the module. A module private key that is loaded into a module by a manufacturer, distributor, technician, or end user can comprise an initial module private key, and a private key that is derived by a module after installation or distribution can comprise a derived module private key. After deriving the module public key and module private key, the module private key can be preferably recorded in a nonvolatile memory within the module.

Petitioner Samsung Ex-1004, 0010

In a first embodiment, the module can connect with a wireless network operated by a module network operator. The wireless network could comprise a network based upon wireless wide area networking (WAN) standards such as a wireless network that utilizes Long-Term Evolution (LTE) standards, LTE Advanced, or related networks where authentication and encryption of data utilizes conventional technology with a pre-shared secret key K as defined in the wireless network standards. With conventional technology and these exemplary standards-based networks, the pre-shared secret key K is normally recorded in a universal integrated circuit card (UICC) that is distributed to end users for insertion into modules and mobile phones. This physical distribution of a UICC can create challenges and costs for modules supporting M2M applications. For example, with conventional technology the replacement of the UICC in order to connect with a different wireless network can be difficult or incur higher costs than the electronic generation and/or distribution of a profile for an eUICC. The profile can include data for (i) appropriate network access credentials and also (ii) network parameters for connecting a module with a wireless network associated with a mobile operator network. The MNO can process or create data or values in the profile for initial network access credentials and the network paramters. A first exemplary embodiment supports a module using a network module identity to securely change a key K used for authentication without either (i) receiving a new physical UICC or (ii) receiving a new eUICC profile.

In a first exemplary embodiment, the module can store an initial key K in at least one of a physical UICC or a "virtual" UICC in the form of an eUICC. The eUICC can record a profile with the initial key K. The module could receive the physical UICC or the profile for the eUICC with the initial key K from either (i) a manufacturer, distributor, installer, or end user, or (ii) via a network. In the case where the profile for the eUICC is received via a network (which could comprise a different wireless network than the wireless network for the module to use the eUICC profile), the network could be a prior network the module connects with before applying and using the profile for the eUICC. The profile for an eUICC can include the equivalent data that is recorded in a physical UICC, such that the eUICC operating with an activated eUICC profile can provide functionality to a module that is equivalent to a physical UICC. After recording the initial key K and related network access credentials and network parameters, the module can connect and authenticate with the wireless network using the initial key K. The authentication could comprise steps established in standards including sending a network module identity (which could be an IMSI or related identity), receiving a RAND value, inputting the RAND into the UICC or eUICC, receiving a RES value from the UICC or eUICC, and sending the RES to the wireless network.

Either before or after authentication with the wireless network using the initial key K, the module can use the set of cryptographic parameters and the set of cryptographic algorithms to derive a module private key and a module public key, which can comprise a module PKI key pair. The module PKI key pair could

Petitioner Samsung Ex-1004, 0011

be processed according to a variety of cryptographic algorithms, including the use of RSA-based algorithms and elliptic curve cryptography (ECC) algorithms. In an exemplary embodiment, the module can derive the module PKI key pair with ECC algorithms in order to reduce the processing power and bandwith required, where a similar level of security can be achieved with shorter key lengths using ECC algorithms compared to RSA algorithms. In another embodiment, RSA algorithms can be used to derive the module PKI key pair in order to support legacy software and systems that utilize RSA algorithms for public and private keys, and related cryptographic operations including signatures with the digital signature algorithm (DSA). The module can also derive a key K module token using the derived module private key. For embodiments where ECC algorithms are used to derive the module PKI key pair, the key K module token can comprise the module public key, although different values for the key K module token can be utilized as well.

Continuing with the first exemplary embodiment, after authentication with the wireless network using the initial key K, the module can send the derived key K module token to the wireless network. The module can send the key K module token to a server associated with or operated by the mobile network operator. The mobile network operator can record that the key K module token is associated with the network module identity, in order to track a plurality of modules and key K module tokens. The module can derive a secret shared network key K using a key derivation function. The key derivation function can use as input the derived module private key, the set of cryptographic parameters, and a key K network token. The key K network token and the set of cryptographic parameters for the key derivation function could be (i) recorded in the UICC or eUICC profile, or (ii) received by the module from the wireless network after connecting with the initial key K. The secret shared network key K can comprise a second key K, different than the initial key K, for the module to authenticate with the wireless network, and also encrypt/decrypt data with the wireless network. A server operated by a mobile network operator and associated with the wireless network can use the key K module token received from the module to also derive the secret shared network key K.

Continuing with the first exemplary embodiment, after both the module and the server have derived the secret shared network key K, the module can subsequently authenticate with the wireless network using the mutually derived secret shared network key K. The authentication could comprise steps established in standards, including sending the network module identity (including using the same network module identity as with initial key K, although the module could also change the network module identity), receiving a RAND value, inputting the RAND and the derived secret shared network key K into a set of cryptographic algorithms, calculating a RES value using the set of cryptographic algorithms, and sending the RES to the wireless network. Additional keys such as cipher keys, integrity keys, and symmetric ciphering keys can further be derived by both the module and the wireless network using the secret shared network key K and

Petitioner Samsung Ex-1004, 0012

the RAND value. In this manner, a module and a mobile network operator can mutually derive a secret shared network key K instead of requiring the physical or electronic distribution of key K, thereby increasing security and flexibility for communications between a module and a wireless network.

A second exemplary embodiment can support a module changing a key K used to (i) authenticate with a wireless network and (i) cipher/decipher data with a wireless network. The module can change key K without requiring the manual exchange of a UICC or other physical intervention. The module can use an eUICC profile and change key K while using the same eUICC profile. The module, could also comprise a mobile phone such as, but not limited to, a smart phone. The module can include a module identity which is recorded into a read-only or protected address upon manufacturing or distribution of the module. The module can receive eUICC profiles from an eUICC subscription manager. The module can use the module identity to identify the module with the eUICC subscription manager and also an initial private key to authenticate and/or cipher data with the eUICC subscription manager. The eUICC subscription manager can use a server in order to communicate with the module. After connecting with a first network, which could comprise a first wireless WAN, wireless LAN, or wired connection, the module can receive a eUICC profile for an eUICC in the module, where the eUICC profile includes a network module identity and a first key K. The first key K can be a standards-based key K used with wireless networks, and be equivalent to a pre-shared secret key K recorded in physical UICC, and may also be similar or equivalent to an initial key K from the first exemplary embodiment outlined above.

Continuing with this second exemplary embodiment, the module can use the eUICC, the network module identity, and the first key K to authenticate with the wireless network. The authentication could comprise steps established in wireless networking standards including sending a network module identity (which could be an IMSI or related identity), receiving a RAND value, inputting the RAND into the eUICC, receiving a RES value from the eUICC (where the eUICC uses the first key K to calculate the RES), and sending the RES to the wireless network. After authenticating with the wireless network using the first key K, the module can send a key K module token to the wireless network. The key K module token can comprise a number or a string for a module network operator associated with the wireless network to utilize in a key derivation function. Data for the authentication and related steps in this second embodiment can be communicated between a module and a set of servers, where the set of servers are associated with the wireless network and mobile network operator. The wireless network can comprise the radio access portion or segment for the mobile network operator.

Continuing with this second embodiment, after authenticating with the wireless network using the first key K, the module can receive a set of cryptographic parameters. The module can use the received set of cryptographic parameters and a key derivation function in order to derive a second key K. A server

Petitioner Samsung Ex-1004, 0013

associated with the mobile network operator can use the received key K module token, the set of cryptographic parameters, and the key derivation function in order to derive the same second key K. The second key K derived by the module can be recorded in the eUICC profile for the wireless network. The module can disconnect from the wireless network after attaching using the first key K, and then reconnect using the second key K which has now been mutually derived by both the module and the mobile network operator. The module can reconnect using the eUICC, the received eUICC profile, and either (i) the network module identity used with the first key K, or (ii) a second network module identity sent or received by the module after connecting with the first key K. In this manner, a module can change the key K used to authenticate and cipher/decipher data with a wireless network from a first key K to a second key K. This can increase flexibility of the system and reduce costs of physically distributing a new UICC to the module (or electronically sending new eUICC profiles) in order to change a key K. Also note that the second key K does not need to be transmitted, even in an encrypted form through third parties such as an eUICC subscription manager, and thus the security of a system using an eUICC can be increased as well.

A third exemplary embodiment can comprise a method for a module to securely and efficiently send sensor data to a server. The module can include a sensor for automatically collecting data regarding a monitored unit. The module can comprise a wireless module that connects to a wireless network, including a wireless WAN such as a public land mobile network (PLMN). The module and the network can use standards that include Internet Protocol (IP) at the network and transport layers of the open systems interconnection (OSI) stack. The module can record an initial module private key and a module identity in a non-volatile memory, and the initial module private key and module identity could be recorded by a module manufacturer, or the module identity could be recorded by a module manufacturer and a distributor or end user could record the initial module private key. An eUICC subscription manager could also provide the initial module private key. The module manufacturer, distributor, mobile network operator, and/or module provider could operate as an eUICC subscription manager. Upon connecting with a first network, the module can receive a set of cryptographic parameters and a profile for an eUICC from the eUICC subscription manager, and the module can decrypt the profile using the initial module private key.

Continuing with this third exemplary embodiment, the module can derive a module private key and a module public key using the set of cryptographic parameters and a set of cryptographic algorithms. The module can select the received eUICC profile, activate the profile, and authenticate and connect with a wireless network using the eUICC profile. The module can send a message with the derived module public key and the module identity to a server and the module can authenticate the message using the initial module private key. A server could record or have access to an initial module public key associated with the initial module private key, and the server can use the initial module public key to authenticate the message sent by

Petitioner Samsung Ex-1004, 0014

the module. In this manner of a module using the initial module private key and the server using the initial module public key, the module can authoritatively send the derived module public key, such that a fraudulent or otherwise unauthorized module could not feasibly submit a public key for the module with the module identity. After sending and authenticating the derived module public key, the module can send a sensor measurement with a module identity in a message to the server, and the message could contain a module encrypted data. The module can use the derived module private key to encrypt the module encrypted data. The server can use the received, authenticated module public key to decrypt the module encrypted data. The server can record or forward the sensor data, and the module can repeat the process of collecting sensor data and using the derived module private key to send the sensor data.

In another embodiment, the module may be deployed within a wireless network such as, but not limited to, a 4G LTE network, a LTE Advanced network, or a WiFi network, and the module may comprise a wireless module. After being installed next to a monitored unit, the wireless module can (i) wake from a sleep or dormant state, (ii) utilize a sensor to collect data associated with a monitored unit, (iii) connect to the wireless network using Internet Protocol standards, and (iv) send the sensor data to a server. During an active state, the module can use a UDP IP:port number to both send a message to the server and receive a response to the server. The message as a UDP datagram can be a UDP Lite datagram and with a checksum only applied to the packet header. A UDP Lite datagram with sensor data can include channel coding for the body of the datagram to mitigate the effect of bit errors. In this embodiment, the wireless network can preferably support the UDP Lite protocol.

In exemplary embodiments, a module can use a first module private key and a server can use a first module public key to establish communication between the two nodes. The server can belong to a mobile network operator and be associated with a wireless network. The server can securely send the module a set of cryptographic parameters, where the set of cryptographic parameters includes values to define an equation for an elliptic curve. The values could comprise constants and variables such that the module can calculate an elliptic curve, and the elliptic curve can be different than standard, published curves. The set of cryptographic parameters could be sent from the server to the module in a server encrypted data, where the server encrypted data is decrypted by the module using any of (i) the first module private key, (ii) a symmetric key, and (iii) a shared secret key. The module can use the set of cryptographic parameters, a random number generator, and a key pair generation algorithm within a set of cryptographic algorithms in order to generate a new, second module key pair, which could comprise a second module public key and a second module private key. The module can securely and/or authoritatively send the second module public key to the server, where the steps to implement security for sending the second module public key can include using of the first module public key and/or the shared secret key.

Petitioner Samsung Ex-1004, 0015

In another embodiment, a module with a module identity can derive its own public and private keys after distribution of the module using a first set of cryptographic parameters. A module can send a message that includes a module identity, where the module identity can be verified using at least one of a module digital signature and a shared secret key. A set of servers can send the module with the module identity a second set of cryptographic parameters, which can be different than the first set of cryptographic parameters. Over time, the module can use at least a subset of the second set of cryptographic parameters to derive multiple pairs of module public and private keys. Over time, the module can (i) send a series of module public keys with the module identity and (ii) use a previous module public key in the series to verify and/or authenticate a message with a module public key sent by the module to the server.

In exemplary embodiments, the module can use a shared secret algorithm in order to derive a shared secret key without sending or receiving the shared secret key. A set of component parameters and an algorithm token can also be input into the shared secret algorithm. A server could record the same component parameters, the same shared secret algorithm, and also receive the algorithm token from the module. The server can derive the same shared secret key as the module. The module and the server can then use the same shared secret key as a symmetric key for symmetric ciphering algorithms, for authentication where both the module and a server mutually authenticate using a message digest and the shared secret key.

These as well as other aspects and advantages will become apparent to those of ordinary skill in the art by reading the following detailed description, with reference where appropriate to the accompanying drawings.

Petitioner Samsung Ex-1004, 0016

BRIEF DESCRIPTION OF THE DRAWINGS

Various exemplary embodiments are described herein with reference to the following drawings, wherein like numerals denote like entities.

Figure 1a is a graphical illustration of an exemplary system, where a server and a module connect using a wireless network, in accordance with exemplary embodiments;

Figure 1b is a graphical illustration of hardware, firmware, and software components for a module, in accordance with exemplary embodiments;

Figure 1c is a graphical illustration of components within a module, in accordance with exemplary embodiments;

Figure 1d is a graphical illustration of components in a set of cryptographic algorithms, in accordance with exemplary embodiments;

Figure 1e is a graphical illustration of a set of components for a module and a set of component parameters, in accordance with exemplary embodiments;

Figure 1f is a graphical illustration for deriving a shared secret key using a shared secret algorithm, an algorithm token, and component parameters, in accordance with exemplary embodiments;

Figure 1g is a graphical illustration for ciphering and deciphering plaintext using a secret ciphering algorithm with input of ciphertext and a key, in accordance with exemplary embodiments;

Figure 1h is a graphical illustration for deriving a shared secret key and an encrypted module identity, in accordance with exemplary embodiments;

Figure 1i is a graphical illustration of an exemplary system, where a module and a server exchange a set of cryptographic parameters and a subset of the set of cryptographic parameters, in accordance with exemplary embodiments;

Figure 1j is an illustration of a certificate that includes a PKI public key, where the key comprises an elliptic curve cryptography (ECC) key, in accordance with exemplary embodiments;

Figure 1k is a graphical illustration of hardware, firmware, and software components for a server, in accordance with exemplary embodiments;

Figure 1m is a graphical illustration of components within a server, in accordance with exemplary embodiments;

Figure 2 is a graphical illustration of an exemplary system, where a module sends a message to a server, and where the module receives a response to the message, in accordance with exemplary embodiments;

Petitioner Samsung Ex-1004, 0017

Figure 3a is a flow chart illustrating exemplary steps for a module to send sensor data to a server, in accordance with exemplary embodiments;

Figure 3b is a graphical illustration of components within a received profile and an activated profile for an embedded universal integrated circuit card (eUICC), in accordance with exemplary embodiments;

Figure 4 a is a flow chart illustrating exemplary steps for a module to process a message, including encrypting sensor data and sending a digital signature, in accordance with exemplary embodiments;

Figure 5a a is a flow chart illustrating exemplary steps for a module to process a response from the server, including verifying a server's identity and decrypting instructions, in accordance with exemplary embodiments;

Figure 5b is a flow chart illustrating exemplary steps for a module to communicate with a server, including the module deriving public and private keys, in accordance with exemplary embodiments;

Figure 6 is a simplified message flow diagram illustrating an exemplary message sent by a module, and an exemplary response received by the module, in accordance with exemplary embodiments;

Figure 7 is a flow chart illustrating exemplary steps for a module to derive a series of public keys and private keys, including sending and authenticating the derived public keys, in accordance with exemplary embodiments;

Figure 8 is a simplified message flow diagram illustrating an exemplary message sent by a module, wherein the message includes a derived module public key, in accordance with exemplary embodiments;

Figure 9a is a flow chart illustrating exemplary steps for a module to use a shared secret key to authenticate with a server, in accordance with exemplary embodiments;

Figure 9b is a flow chart illustrating exemplary steps for a module to derive a shared secret key K using a derived module PKI key, in accordance with exemplary embodiments;

Figure 10 is a simplified message flow diagram illustrating an exemplary system with exemplary data transferred between a module and a set of servers, in accordance with exemplary embodiments;

Figure 11 is a graphical illustration for a module and a network to mutually derive a shared secret key K, in accordance with exemplary embodiments.

Petitioner Samsung Ex-1004, 0018

DETAILED DESCRIPTION OF EXEMPLARY EMBODIMENTS OF THE INVENTION

Figure 1a

Figure 1a is a graphical illustration of an exemplary system, where a server and a module connect over a wireless network, in accordance with exemplary embodiments. The system 100 includes a module 101 operating within a wireless network 102. System 100 can also include a module provider 109, an IP Network 107, and a mobile network operator 108, a certificate authority 118, and a monitored unit 119. Mobile network operator (MNO) 108 can include a server 105. For embodiments where the MNO 108 uses 4G LTE and LTE Advanced networks, server 105 could comprise a home subscriber server (HSS). Server 105 could be a server with related functionality for a MNO 108 that uses different wireless network standards than those based on 4G LTE. System 100 is illustrated without specific packet transmissions between module 101 and mobile network operator 108. Examples of the communications and messages pertaining to the present invention will be illustrated in later Figures. As contemplated herein, machine-to-machine communications may comprise communication between a module 101 and a server 105, such that data can be transferred between the two with minimal manual intervention, although manual intervention can be required to set up system 100 and any occasional manual maintenance required. As contemplated herein, machine-to-machine communications may also be referred to as "the Internet of things" (IoT). Also note that module 101 may comprise a wireless module, such that module 101 can communicate with wireless network 102 using a radio and an antenna. A wireless or a wired configuration for module 101 can be utilized in the present invention.

If module 101 operates as a wireless module, module 101 and wireless network 102 can communicate using a base station 103. Module 101 and wireless network 102 can utilize a variety of wireless technologies to communicate, including WiFi, WiMax, a 2nd generation wireless wide area network (WAN) technology such as, but not limited to, General Packet Radio Services (GPRS) or Enhanced Data rates for GSM Evolution (EDGE), 3rd Generation Partnership Project (3GPP) technology such as, but not limited to, 3G, 4G LTE, or 4G LTE Advanced, and other examples exist as well. A wired module 101 can connect to the IP Network 107 via a wired connection such as, but not limited to, an Ethernet, a fiber optic, or a Universal Serial Bus (USB) connection (not shown).

Generally, the communication techniques described herein can be independent of the network technologies utilized at the physical and data-link layers, so long as the underlying network provides access to the IP Network 107 and supports Internet Protocols (IP). The IP Network 107 can be an IPv4 or an IPv6 packet-switched based network that utilizes standards derived from the Internet Engineering Task Force, such as, but not limited to, RFC 786 (User Datagram Protocol), RFC 793 (Transmission Control Protocol),

Petitioner Samsung Ex-1004, 0019

and related protocols. The IP Network 107 can be the public Internet comprising globally routable IP addresses, or a private network that utilizes private IP addresses. IP Network 107 as illustrated in Figure 1a could comprise the globally routable public Internet, or IP Network 107 could also be a private Internet that is (i) not globally routable and (ii) only accessible to authorized modules and servers. As one example of a private IP Network 107, IP Network 107 could use private IP addresses for nodes on the network, and in this case IP Network 107 could be referred to as an intranet or private network. Alternatively, IP Network 107 could be a private network layered on top of the publicly routable Internet via secured and encrypted connections. The specific numbers for IP addresses and port numbers shown in Figure 1a and other figures are illustrative and any valid IP address or port number can be used, including an IPv4 and an IPv6 address. Server 105 within mobile network operator 108 can communicate with the module 101 using IP network 107, where IP network 107 can comprise a private network that utilizes Internet Protocol standards. Module 101 can access the public Internet after authenticating with the server 105 associated with the MNO 108.

When operating in a wireless network configuration, module 101 can access the IP Network 107 via the wireless network 102. In the wireless network configuration, module 101 can be a wireless handset, a cellular phone, a smartphone, a tablet computer, a laptop, a computer with a radio, a tracking device, or a circuit board with a radio that accesses wireless network 102. Examples of wireless modules that utilize a wireless WAN such as, but not limited to, 2G and 3G networking technologies include the Motorola® G24-l and Huawei® MC323. Example manufacturers of wireless modules in 2012 include Sierra Wireless® and Telit®. Example leading manufacturers of mobile phones in 2013 include Apple® and Samsung®. In a wired configuration (not shown), module 101 can be a computer, security camera, security monitoring device, networked controller, etc. A more detailed depiction of exemplary components of a module 101 is included in Figure 1b and Figure 1c below. Module 101 could also comprise a "point of presence" payment terminal, such that a sensor 101f associated with module 101 could collect payment information such as, but not limited to, an account number from a credit card or similar payment card. Module 101 could communicate with the payment card via a magnetic reader or near-field wireless communications, and in this case the magnetic reader or antenna for near-field communications can function as a sensor. Module 101 could also operate as a "smartcard" such that an end user presents module 101 to merchants for payments.

Wireless network 102 may comprise either a wireless local area network (LAN) or a wireless WAN such as a public land mobile network (PLMN). Examples for technologies used in wireless LANs include an 802.11 WLAN, Bluetooth, or Zigbee among other possibilities. Module 101 operating in wireless mode could communicate with a base station 103 of a wireless network 102 using a radio and an antenna. Wireless network 102 could operate as a Mode II device according to FCC Memorandum Opinion and Order (FC-12-36) and related white space regulation documents. If module 101 supports IEEE 802.15.4, then wireless

Petitioner Samsung Ex-1004, 0020

network 102 could be a Zigbee network, an ISA100.11a standards-based network, or a 6LoWPAN network as described by IETF RFC 4944. Other possibilities exist as well for the wireless technology utilized by a wireless network 102 and module 101, operating in a wireless mode, without departing from the scope of the present invention.

Module 101 can collect data regarding a monitored unit 119 and periodically report status to a mobile network operator 108 or a server 105. Examples of a monitored unit 119 can include a vending machine, an alarm system, an automobile or truck, a standard 40-foot or 20-foot shipping container, or industrial equipment such as, but not limited to, a transformer on an electrical grid or elevator in a building. Additional examples of a monitored unit 119 include can also include a pallet for shipping or receiving goods, an individual box of pharmaceuticals, a health monitoring device attached to a person such as, but not limited to, a pacemaker or glucose monitor, and a gate or door for opening and closing. Other examples exist as well without departing from the scope of the present invention. Module 101 can utilize a sensor to measure and collect data regarding a parameter of monitored unit 119 such as, but not limited to, temperature, physical location potentially including geographical coordinates from a Global Positioning System (GPS) receiver, radiation, humidity, surrounding light levels, surrounding RF signals, weight, vibration and/or shock, voltage, current, and/or similar measurements.

As illustrated in Figure 1a, wireless network 102 may include a wireless network firewall 104 and mobile network operator 108 may include a server network firewall 124. These firewalls may be used to secure communication at the data link, network, transport, and/or application layers of communications using the IP Network 107. Firewalls 104 and 124 could perform network address translation (NAT) routing or operate as symmetric firewalls, and/or selectively filter packets received through IP Network 107 in order to secure system 100. The firewall functionality of firewalls 104 and 124 could be of many possible types, including a symmetric firewall, a network-layer firewall that filters inbound packets according to pre-determined rules, an application-layer firewall, or a NAT router, as examples. Firewalls 104 and 124 could also implement an IPSec tunnel between the two firewalls. Although a single firewall 104 and 124 is illustrated in wireless network 102 (or a wired network 102 or simply "network 102") and with mobile network operator 108, respectively, firewall 104 and 124 may each comprise multiple firewalls that operate in conjunction and the combined operation may be considered a single firewall 104 and 124, respectively.

According to a preferred exemplary embodiment, module 101 may preferably record a module private key 112. As described in additional figures below, module 112 can generate a key pair comprising a module private key 112 and a module public key 111, where module private key 112 resides within module 101 and may not be shared or transmitted to other parties. Alternatively, the present invention also contemplates that module 101 does not derive its own module private key 112, and rather module private key

Petitioner Samsung Ex-1004, 0021

112 can be securely loaded or transmitted to module 101, and in this case the loaded module private key 112 can comprise an initial module private key 112b. Module 101 may also be associated with a module provider 109. Module provider 109 could be a manufacturer or distributor of module 101, or may also be the company that installs and services module 101 or associates module 101 with monitored unit 119. Module provider 109 can record a module public key 111 and a certificate 122 (illustrated below in Figure 1j) for module 101. Module public key 111 may be associated with a module public key identity 111a, which could be an identifier of module public key 111.

Either module provider 109 or mobile network operator 108 could function as a eUICC subscription manager 164, where an eUICC subscription manager 164 can manage the recording and secure distribution of eUICC profiles to a module 101. Other entities could operate as an eUICC subscription manager 164 as well. An eUICC subscription manager is described in ETSI TS 103 383 v12.1, entitled "Smart Cards; Embedded UICC; Requirements Specification," which is herein incorporated by reference in its entirety. An eUICC subscription manager 164 can also use a server 105 and record private keys and public keys for the server/subscription manager operation. In embodiments, eUICC subscription manager 164 can use a module public key 111 to cipher an eUICC profile (such as, but not limited to, a received eUICC profile 311 depicted and described in connection with Figure 3b below), such that only module 101 with module public key 111 could reasonably decipher the eUICC profile. In this manner, the eUICC profile 311 can remain reasonably secured. The eUICC subscription manager 164 can use either symmetric ciphering 141b or asymmetric ciphering 141a to encrypt the eUICC profile. The module public key 111 used by an eUICC subscription manager 164 can comprise an initial module public key 111b, where the initial module public key 111b can be derived outside module 101 and loaded into module 101. Or, the eUICC subscription manager 164 can use a module public key 111 derived by the module 101 (such that derived module public key 111 has been transferred to the eUICC subscription manager 164 in a secure and reliably manner).

In embodiments, a module 101 may utilize multiple module public keys 111 over the lifetime of module 101 (including multiple corresponding module private keys 112), and module public key identity 111a can be used to select and/or identify the correct module public key 111. Module public key identity 111a could be a string or sequence number uniquely associated with module public key 111 for a given module 101 (i.e. module public key identity 111a does not need to be globally unique). As illustrated in Figure 1a, module public key identity 111a may preferably not be included in the string or number comprising module public key 111, but rather associated with the string or number comprising module public key 111, and in this case the two together (module public key identity 111a and the string or number for module public key 111) can refer to module public key 111 as contemplated herein. In addition, module 101 can record an initial module private key 112b and an initial module public key 111b. These initial keys can

Petitioner Samsung Ex-1004, 0022

be different from a module private key 112 and a module public key 111 since the "initial" keys can be derived from an outside source and loaded into a module 101, and module private key 112 and module public key 111 can be derived by module 101.

The module public key 111 can optionally be signed by a certificate authority 118 in order to confirm the identity of module 101 and/or the identity of module provider 109. Module provider 109 can also function as a certificate authority 118 for module 101. Thus, the validity of module public key 111, possibly recorded in a certificate 122 (illustrated in Figure 1j) could be checked with module provider 109, and the wireless module provider's 109 provider public key 120 could be checked against certificate authority 118. Other configurations for signing public keys and using certificates with public keys are possible as well without departing from the scope of the present invention.

Public keys and private keys as contemplated in the present invention, including module public key 111 and module private key 112 and additional keys described herein, may leverage established standards for Public Key Infrastructure (PKI). Public keys may be formatted according to the X.509 series of standards, such as, but not limited to, X.509 v3 certificates, and subsequent or future versions, and these keys may be considered cryptographic keys. The keys can support standards such as, but not limited to, the International Organization for Standardization (ISO) ISO/IEC 9594 series of standards (herein incorporated by reference) and the Internet Engineering Task Force (IETF) RFC 5280 titled "Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile" (herein incorporated by reference), including future updates to these standards.

Module public key 111 and module private key 112, as well as the other private and public keys described within the present invention, could be generated using standard software tools such as, but not limited to, Openssl, and other tools to generate public and private keys exist as well. Public and private keys as contemplated herein could be recorded in a file such as, but not limited to, a *.pem file (Privacy-enhanced Electronic Mail), a file formatted according to Basic Encoding Rules (BER), Canonical Encoding Rules (CER), or Distinguished Encoding Rules (DER), or as text or binary file. Other formats for public and private keys may be utilized as well, including proprietary formats, without departing from the scope of the present invention. As contemplated herein, a key may also comprise a public key, a private key, or a shared key including a secret shared key. A public key as contemplated herein may also be considered a certificate or a public certificate. A private key as contemplated herein may also be considered a secret key.

Server 105 can include a module database 105k, and server 105 will also be described in additional detail below in Figure 1k and Figure 1m. Server 105 can operate as an HSS in 4G LTE networks, including recording network access credentials 314 (described in Figure 3b below) for a plurality of modules 101 in a module database 105k. Server 105 could be a plurality of individual computers operating in a coordinated

Petitioner Samsung Ex-1004, 0023

manner through a network in order to function as a server 105. Server 105 can include a server public key 114 and a server private key 105c. Mobile network operator 108 can also include a network private key 165a and a network public key 165b. Additional details regarding the various public and private keys illustrated in Figure 1a will be provided in Figures below.

Other configurations besides the one illustrated in Figure 1a are possible as well. Wireless network 102 could be included in mobile network operator 108. In many common commercial relationships for the operation of mobile phone service in the United States in 2013, wireless network 102 could represent a portion of the radio access network used by a mobile network operator 108. MNO 108 could outsource the operation and maintenance of a radio access network, such as a wireless network 102, to 3rd parties. In this configuration, wireless network 102 could represent a network operated by a first company specializing in the operation of radio towers and BTS equipment. This first company could be contracted with the mobile network operator 108 in order to support mobile phone service or data services to modules 101.

In addition, server 105 could reside within wireless network 102 in a data center managed by wireless network 102. Wireless network 102 could also operate as a module provider 109. Although a single module 101, server 105, wireless network 102, and mobile network operator 108 are illustrated in Figure 1a, system 100 could comprise a plurality of each of these elements. Module 101 could also record sensor data pertaining to a plurality of monitored units 119. Module 101 could be mobile, such as physically attached to a truck or a pallet, and module 101 could connect to a series of different wireless networks 102 or base stations 103 as module 101 moves geographically. Other configurations are possible as well for the elements illustrated in Figure 1a without departing from the scope of the present invention.

Figure 1b

Figure 1b is a graphical illustration of hardware, firmware, and software components for a module, in accordance with exemplary embodiments. Figure 1b is illustrated to include many components that can be common within a module 101, and module 101 may also operate in a wireless configuration in order to connect with a wireless network 102. Module 101 may consist of multiple components in order to collect sensor data or control an actuator associated with a monitored unit 119. In a wireless configuration, the physical interface 101a of module 101 may support radio-frequency (RF) communications with networks including a wireless network 102 via standards such as, but not limited to, GSM, UMTS, mobile WiMax, CDMA, LTE, LTE Advanced, and/or other mobile-network technologies. In a wireless configuration, the physical interface 101a may also provide connectivity to local networks such as, but not limited to, 802.11 WLAN, Bluetooth, or Zigbee among other possibilities. In a wireless configuration, module 101 could use a

Petitioner Samsung Ex-1004, 0024

physical interface 101a be connected with both a wireless WAN and wireless LAN simultaneously. In a wired configuration, the physical interface 101a can provide connectivity to a wired network such as, but not limited to, through an Ethernet connection or USB connection.

The physical interface 101a can include associated hardware to provide the connections such as, but not limited to, radio-frequency (RF) chipsets, a power amplifier, an antenna, cable connectors, etc., and additional exemplary details regarding these components are described below in Figure 1c. Device driver 101g can communicate with the physical interfaces 101a, providing hardware access to higher-level functions on module 101. Device drivers 101g may also be embedded into hardware or combined with the physical interfaces. Module 101 may preferably include an operating system 101h to manage device drivers 101g and hardware resources within module 101. The operating systems described herein can also manage other resources such as, but not limited to, memory and may support multiple software programs operating on module 101 or server 105, respectively, at the same time. The operating system 101h can include Internet protocol stacks such as, but not limited to, a User Datagram Protocol (UDP) stack, Transmission Control Protocol (TCP) stack, a domain name system (DNS) stack, etc., and the operating system 101h may include timers and schedulers for managing the access of software to hardware resources. The operating system shown of 101h can be appropriate for a low-power device with limited memory and CPU resources (compared to a server 105). An example operating system 101h for module 101 includes Linux, Android® from Google®, Windows® Mobile, or Open AT® from Sierra Wireless®. Additional example operating systems 101h for module 101 include eCos, uC/OS, LiteOs, and Contiki, and other possibilities exist as well without departing from the scope of the present invention.

A module program 101i may be an application programmed in a language such as, but not limited to, C, C++, Java, and/or Python, and could provide functionality to support M2M applications such as, but not limited to, remote monitoring of sensors and remote activation of actuators. Module program 101i could also be a software routine, subroutine, linked library, or software module, according to one preferred embodiment. As contemplated herein, a module program 101i may be an application operating within a smartphone, such as, but not limited to, an iPhone® or Android®-based smartphone, and in this case module 101 could comprise the smartphone. The application functioning as a module program 101i could be downloaded from an "app store" associated with the smartphone. Module program 101i can include data reporting steps 101x, which can provide the functionality or CPU 101b instructions for collecting sensor data, sending messages to server 105, and receiving responses from server 105, as described in the present invention.

Many of the logical steps for operation of module 101 can be performed in software and hardware by various combinations of sensor 101f, actuator 101y, physical interface 101a, device driver 101g, operating

Petitioner Samsung Ex-1004, 0025

system 101h, module program 101i, and data reporting steps 101x. When module 101 is described herein as performing various actions such as acquiring an IP address, connecting to the wireless network, monitoring a port, transmitting a packet, sending a message, receiving a response, or encrypting or signing data, specifying herein that module 101 performs an action can refer to software, hardware, and/or firmware operating within module 101 illustrated in Figure 1b or Figure 1c performing the action. Note that module 101 may also optionally include user interface 101j which may include one or more devices for receiving inputs and/or one or more devices for conveying outputs. User interfaces are known in the art and generally are simple for modules such as, but not limited to, a few LED lights or LCD display, and thus user interfaces are not described in detail here. User interface 101j could comprise a touch screen if module 101 operates as a smartphone or mobile phone. As illustrated in Figure 1b, module 101 can optionally omit a user interface 101j, since no user input may be required for many M2M applications, although a user interface 101j could be included with module 101.

Module 101 may be a computing device that includes computer components for the purposes of collecting data from a sensor 101f or triggering an action by an actuator 101y. Module 101 may include a central processing unit (CPU) 101b, a random access memory (RAM) 101e, and a system bus 101d that couples various system components including the random access memory 101e to the processing unit 101b. The system bus 101d may be any of several types of bus structures including a memory bus or memory controller, a peripheral bus, and a local bus using any of a variety of bus architectures including a data bus. Note that the computer components illustrated for the module 101 in Figure 1b may be selected in order to minimize power consumption and thereby maximize battery life, if module 101 includes a battery and is not attached to external power. In addition, the computer components illustrated for the module 101 in Figure 1b may also be selected in order to optimize the system for both long periods of sleep or idle states relative to active communications and also may be optimized for predominantly uplink (i.e. device to network) communications with small packets or messages. The computer components illustrated for the module 101 in Figure 1b may also be general-purpose computing components, and specialized components are not required in order to utilize many of the embodiments contemplated herein.

Module 101 may include a read-only memory (ROM) 101c which can contain a boot loader program. Although ROM 101c is illustrated as "read-only memory", ROM 101c could comprise long-term memory storage chipsets or physical units that are designed for writing once and reading many times. As contemplated within the present invention, a read-only address could comprise a ROM 101c memory address or another hardware address for read-only operations accessible via bus 101d. Changing data recorded in a ROM 101c can require a technician have physical access to module 101, such as, but not limited to, removing a cover or part of an enclosure, where the technician can subsequently connect equipment to a

Petitioner Samsung Ex-1004, 0026

circuit board in module 101, including replacing ROM 101c. ROM 101c could also comprise a nonvolatile memory, such that data is stored within ROM 101c even if no electrical power is provided to ROM 101c. Although not illustrated in Figure 1b, but illustrated in Figure 1c below, module 101 could also include a flash memory 101w. Module program 101i, data reporting steps 101x, operating system 101h, or device driver 101g could be stored in flash memory 101w within module 101 when the module is powered off. These components and/or instructions could be moved from a flash memory 101w (not shown in Figure 1b but shown in Figure 1c) into RAM 101e when the module is powered on. Note that ROM 101c could be optionally omitted or included in a memory unit within CPU 101b (not shown).

Although the exemplary environment described herein employs ROM 101c and RAM 101e, it should be appreciated by those skilled in the art that other types of computer readable media which can store data that is accessible by a module 101, such as, but not limited to, memory cards, subscriber identity module (SIM) cards, local miniaturized hard disks, and the like, may also be used in the exemplary operating environment without departing from the scope of the invention. The memory and associated hardware illustrated in Figure 1b provide nonvolatile storage of computer-executable instructions, data structures, program modules, module program 101i, and other data for computer or module 101. Note the module 101 may include a physical data connection at the physical interface 101a such as, but not limited to, a miniaturized universal serial bus adapter 101v (illustrated in Figure 1c), firewire, optical, or other another port. The computer executable instructions such as, but not limited to, module program 101i, data reporting steps 101x, operating system 101h, or device driver 101g can be initially loaded into memory such as, but not limited to, ROM 101c or RAM 101e through the physical interface 101a before module 101 is given to an end user, shipped by a manufacturer to a distribution channel, or installed by a technician. In addition, the computer executable instructions such as, but not limited to, module program 101i, data reporting steps 101x, operating system 101h or device driver 101g could be transferred wirelessly to module 101. In either case (wired or wireless transfer of computer executable instructions), the computer executable instructions such as module program 101i, data reporting steps 101x, operating system 101h, or device driver 101g could be stored remotely on a disk drive, solid state drive, or optical disk (external drives not shown).

A number of program modules may be stored in RAM 101e, ROM 101c, or possibly within CPU 101b, including an operating system 101h, device driver 101g, an http client (not shown), a DNS client, and related software. Further, the module program 101i and/or data reporting steps 101x can perform the various actions described in the present invention for the module 101 through instructions the module program 101i and/or data reporting steps 101x provide to the CPU 101b. A user may enter commands and information into module 101 through an optional user interface 101j, such as a keypad, keyboard (possibly miniaturized for a mobile phone form-factor), and a pointing device. Pointing devices may include a trackball, an electronic

Petitioner Samsung Ex-1004, 0027

pen, or a touch screen. A user interface 101j illustrated in Figure 1b can also comprise the description of a user interface 101j within U.S. Patent Application Serial No. 14/039,401, filed September 27, 2013 in the name of John Nix, which is herein incorporated in its entirety.

The module 101, comprising a computer, may operate in a networked environment using logical connections to one or more remote computers, such as the server 105 illustrated in Figure 1a. Server 105 can also function as a general purpose server to provide files, programs, disk storage, remote memory, and other resources to module 101 usually through a networked connection. Additional details regarding server 105 are provided in Figure 1k and Figure 1m below. Additional remote computers with which module 101 communicates may include another module 101 or mobile device, an M2M node within a capillary network, a personal computer, other servers, a client, a router, a network PC, a peer device, a base station 103, or other common network node. It will be appreciated that the network connections shown throughout the present invention are exemplary and other means of establishing a wireless or wired communications link may be used between mobile devices, computers, servers, corresponding nodes, and similar computers.

The module program 101i and data reporting steps 101x operating within module 101 illustrated in Figure 1b can provide computer executable instructions to hardware such as CPU 101b through a system bus 101d in order for a module 101 to (i) collect data from a sensor, (ii) change the state of an actuator 101y, and (iii) send or receive packets with a server 105, thus allowing server 105 to remotely monitor or control a monitored unit 119. The module program 101i and/or data reporting steps 101x can enable the module 101 to transmit or send data from sensor 101f or module 101 by recording data in memory such as RAM 101e, where the data can include sensor data, a destination IP:port number, a packet or packet header value, an encryption or ciphering algorithm and key, a digital signature algorithm and key, etc. The data recorded in RAM 101e can be subsequently read by the operating system 101h or the device driver 101g. The operating system 101h or the device driver 101g can write the data to a physical interface 101a using a system bus 101d in order to use a physical interface 101a to send data to a server 105 using the IP Network 107. Alternatively, the module program 101i and/or data reporting steps 101x can write the data directly to the physical interface 101a using the system bus 101d.

The module program 101i and/or data reporting steps 101x, or operating system 101h can include steps to process the data recorded in memory such as, but not limited to, encrypting data, selecting a destination address, or encoding sensor data acquired by (i) a sensor 101f or (ii) through a physical interface 101a such as, but not limited to, a thermocouple, shock or vibration sensor, light sensor, or global positioning system (GPS) receiver, etc. The module 101 can use the physical interface 101a such as, but not limited to, a radio to transmit or send the data from a sensor to a base station 103. For those skilled in the art, other steps

Petitioner Samsung Ex-1004, 0028

are possible as well for a module program 101i or operating system 101h to collect data from a sensor 101f and send the data in a packet without departing from the scope of the present invention.

Conversely, in order for module 101 to receive a packet or response from server 105, the physical interface 101a can use a radio to receive data from a base station 103. The received data can include information from a server 105 and may comprise a datagram, a source IP:port number, a packet or header value, an instruction for module 101, an acknowledgement to a packet that module 101 sent, a digital signature, and/or encrypted data. The operating system 101h or device driver 101g can use a system bus 101d and CPU 101b to record the received data in memory such as RAM 101e, and the module program 101i or operating system 101h may access the memory in order to process the received data and determine the next step for the module 101 after receiving the data. The steps within this paragraph may also describe the steps a module program 101i or data reporting steps 101x can perform in order to receive a packet or a response 209 below. For those skilled in the art, other steps are possible as well for a module program 101i, data reporting steps 101x, or module 101 to receive a packet or response from a server 105 within the scope of the present invention.

Moreover, those skilled in the art will appreciate that the present invention may be implemented in other computer system configurations, including hand-held devices, netbooks, portable computers, multiprocessor systems, microprocessor based or programmable consumer electronics, network personal computers, minicomputers, mainframe computers, and the like. The invention may also be practiced in distributed computing environments, where tasks are performed by remote processing devices that are linked through a communications network. In a distributed computing environment, program modules may be located in both local and remote memory storage devices. In addition, the terms “mobile node”, “mobile station”, “mobile device”, “M2M module”, “M2M device”, “networked sensor”, or “industrial controller” can be used to refer to module 101 or its functional capabilities of (i) collecting sensor data regarding a monitored unit 119, (ii) changing state of an actuator 101y associated with monitored unit 119, and/or (iii) communicating the data associated with a monitored unit 119 with a wireless network 102. The function of module 101 and sensor 101f could be integrated, and in this case module 101 could also be referred to as a “sensor”, “intelligent sensor”, or “networked sensor”. Further, the term “module” or “monitoring device” can be used to refer to the module program 101i when module program 101i provides functional capabilities such as reporting data from a sensor 101f to a server 105 or receiving instructions for an actuator 101y from a server 105. Other possibilities exist as well for the configuration or combination of components illustrated in Figure 1b without departing from the scope of the present invention.

Petitioner Samsung Ex-1004, 0029

Figure 1c

Figure 1c is a graphical illustration of components within a module, in accordance with exemplary embodiments. Figure 1c is illustrated to show a combination of components useful for leveraging the efficient and secure communication techniques described in the present invention. In addition to the components illustrated in Figure 1b above, module 101 can include a an eUICC 163, a battery 101k, a server public key 114, a wireless module private key 112, a connection to an actuator 101y, a USB interface 101v, a CPU wake controller 101u, a flash memory 101w, a symmetric key 127, a pre-shared secret key 129, a random number generator 128, cryptographic algorithms 141, a radio 101z, and other components illustrated in Figure 1c. Not all of the components illustrated in Figure 1c are required for many exemplary embodiments, and some of the components illustrated in Figure 1c may also be optionally omitted in some exemplary embodiments.

The CPU 101b can comprise a general purpose processor appropriate for the low power consumption requirements of a module 101, and may also function as a microcontroller. A CPU 101b and a CPU wake controller 101u are depicted and described in connection with Figure 1b of U.S. Patent Application Serial No. 14/055,606, filed October 16, 2013 in the name of John Nix, entitled "Systems and Methods for 'Machine-to-Machine' (M2M) Communications Between Modules, Servers, and an Application using Public Key Infrastructure (PKI)," which is hereby incorporated by reference in its entirety. Clock 160 can comprise a crystal oscillator generating sine or square wave outputs at a frequency to drive a system bus 101d, CPU 101b, and RAM 101e, in addition to other functionality. In exemplary embodiments, clock 160 can comprise a temperature-compensated crystal oscillator (TCXO), a voltage-controlled crystal oscillator (VCXO), or a voltage-controlled temperature-compensated crystal oscillator (VCTCXO), and other possibilities exist as well. Clock 160 could include circuits and logic to keep time while module 101 is both in an active state and a dormant state.

An eUICC 163 within module 101 can comprise an embedded universal integrated circuit card 163. An eUICC 163 can provide the equivalent functionality as physical UICC, where definitions for a physical UICC are included in ETSI TR 102 216 and ETSI TS 102 221 V11.0.0. An eUICC 163 in Figure 1c can support exemplary requirements for an eUICC outlined in ETSI TS 103 383 v12.2, entitled "Smart Cards; Embedded UICC; Requirements Specification," which is herein incorporated by reference in its entirety. An eUICC 163 as illustrated in Figure 1c can be implemented within module 101 in several different ways, including (i) as a module program 101i recorded in a nonvolatile memory, such as, but not limited to, either flash memory 101w or ROM 101c, (ii) firmware within CPU 101b or another specialized processing unit within module 101, (iii) a physical UICC within module 101 that contains the eUICC 163, or (iv) a specialized circuit within a surface mount package that is soldered directly onto a circuit board of the module

Petitioner Samsung Ex-1004, 0030

101, including an 8-lead small outline non-leaded (SON-8) package. For the embodiment where an eUICC 163 comprises a module program 101i, the eUICC 163 could be loaded and installed within nonvolatile memory 101w in module 101 using the steps and procedures described for a module program 101i in Figure 1b. Other possibilities exist as well for the physical implementation of an eUICC 163 within a module 101 without departing from the scope of the present invention. An eUICC 163 may also be referred to as an "electronic UICC", an "electronic SIM" (eSIM), or an "embedded SIM" (also eSIM).

For embodiments where an eUICC 163 can be loaded into a RAM 101e or flash 101w memory, a CPU 101b could designate the RAM 101e or flash 101w memory containing the instructions and data for an eUICC 163 to be a protected memory. When (i) loaded with appropriate data (such as, but not limited to an activated eUICC profile 313 described in Figure 3b below), and (ii) a profile for a MNO 108 is selected and activated, then an eUICC 163 can provide the equivalent functionality of a physical UICC. The eUICC 163, using an activated eUICC profile 313, can provide the module 101 with (i) network access credentials 314, and (ii) network parameters 310 in order to connect with wireless network 102. The eUICC 163, using an activated eUICC profile 313, can record a secret shared network key K (described in Figures 9b and 11 below and related Figures) and also a network module identity 110b (described in Figure 3b below and related Figures). The eUICC 163 can support standard steps by module 101 for network authentication contemplated in 3GPP TS 33.401 V12.9.0 and related standards, including inputting a RAND 912 (depicted and described in Figure 9b) and outputting an RES 913 (also depicted and described in Figure 9b).

According to an exemplary embodiment, an eUICC 163 can be recorded and operate within a "eUICC supporting" physical universal integrated circuit card (UICC) 166 within module 101. This "eUICC supporting", physical UICC 166 can include a processing unit, RAM memory, ROM memory, EEPROM memory, a bus, and a physical interface in order to support a profile activation 316 of multiple different received eUICC profiles 311 (where profile activation 316 and profile 311 are in Figure 3b below). The processing unit, RAM memory, ROM memory, EEPROM memory, and bus in an "eUICC supporting" UICC 166 could comprise smaller versions with similar or equivalent functionality of the CPU 101b, RAM 101e, ROM 101c, flash memory 101w, and bus 101d, respectively, depicted and described in Figure 1b below for a module 101. In other words, a module 101 could include a connection and slot for a physical UICC card, and (i) a manufacturer, distributor, or end user could load an "eUICC supporting" UICC 166 into the slot, and (ii) the eUICC 163 could operate on the physical UICC.

The physical form-factor for an "eUICC supporting" UICC 166 could be identical to a UICC, and a difference between the two may not even be apparent upon visual inspection without special markings on the card. The physical form-factor for an "eUICC supporting" UICC 166 could comprise a "micro-SIM" or a "nano-SIM" as defined in ETSI TS 102 221 V11.0.0, which is herein incorporated by reference. When the

Petitioner Samsung Ex-1004, 0031

module 101 detects a "eUICC supporting" UICC 166, the module 101 could send received eUICC profiles 311 to the "eUICC supporting" UICC 166, and also select, deselect, activate, and deactivate the different received eUICC proviles 311 recorded in the "eUICC supporting" UICC 166. When a module 101 detects that a regular UICC (i.e. not an "eUICC supporting " UICC 166) has been loaded into a slot for UICCs, the module 101 could access the UICC in a regular manner implemented by mobile phones and modules for connecting to existing wireless networks in 2013, such as LTE or 3G networks.

In addition to recording a received profile 311 and an activated profile 313, an eUICC 163 can record an initial module private key 112b and a network public key 165b. An eUICC 163 can also record a plurality of received eUICC profiles 311. As illustrated in Figure 3b below, the network public key 165b could be recorded in the received eUICC profile 311, where different profiles 311 and different network public keys 165b can be associated with different wireless networks 102. The initial module private key 112b can be associated with an initial module public key 111b, as illustrated in Figure 1a above. An eUICC subscription manager 164 could use the initial module public key 111b to encrypt the eUICC profile 311, and a module 101 could use the initial module private key 112b to decrypt the eUICC profile received from the subscription manager 164. The eUICC subscription manager 164, assuming the eUICC subscription manager 164 is associated with MNO 108, could sign the eUICC profile 311 using the network private key 165a (such as creating a server digital signature 506 as described in Figure 5a below), and module 101 could verify the server digital signature 506 with the network public key 165b. The network public key 165b could be recorded in either (i) the eUICC 163 directly, and/or (ii) within the profile 311. In either case, the initial module private key 112b, initial module public key 111b, an network PKI keys 165a and 165b (as illustrated in Figure 1a) can be useful for module 101 to authoritatively and securely receive eUICC profiles 311.

Sensor 101f could be a device to collect environmental data or data regarding a monitored unit 119. Sensor 101f could collect data such as, but not limited to, temperature, humidity, pressure, visible light levels, radiation, shock and/or vibration, voltage, current, weight, pH levels, orientation/motion, or the presence of specific chemicals. Sensor 101f could also be a microphone. Sensor 101f could be a magnetic strip reader for credit cards and similar cards, or an antenna for either near-field RF communications, such as, but not limited to, reading an RF identity tag. An antenna for a sensor 101f could also collect longer-range RF signals, such as, but not limited to, reading long-range radio frequency identity tags. Sensor 101f could also collect biometric data such as, but not limited to, heart rate, glucose levels, body temperature, or other health measurements and in this case monitored unit 119 could be a person. The sensor 101f can provide data to the CPU 101b in the form of analog or digital data, which can be communicated via a system bus 101d or physical interface 101a and other electrical interfaces are possible as well. A sensor measurement can comprise the analog or digital data collected by CPU 101b from sensor 101f. A sensor

Petitioner Samsung Ex-1004, 0032

measurement can include processing of the analog or digital data input CPU 101b by sensor 101f, such as, but not limited to, averaging over time, using mathematic formulas to convert the raw data from sensor 101f into a usable form. Module 101 may also collect sensor data or sensor values using a sensor 101f and CPU 101b, where the data or values are derived from electrical signals output by a sensor 101f. A sensor measurement can comprise the sensor data or sensor values. If module 101 comprises a "point of presence" payment terminal, then a sensor measurement could comprise data read from a payment card.

As contemplated herein, the terms "sensor measurement" and "sensor data" can be used interchangeably, and can also be considered functionally equivalent. Although a single sensor 101f is shown in Figure 1c, a module 101 could include multiple sensors. Each of the multiple sensors 101f could include a sensor identity 151, which could comprise a number or string to identify the sensor 101f. A sensor 101f could be external to module 101, and also a plurality of sensors 101f may be used and they also can connect to module 101 when module 101 uses radio 101z as a base station for a WiFi network. An exemplary embodiment where sensor 101f connects to module 101 using a radio 101z is also depicted and described in connection with Figure 1e of U.S. Patent Application Serial No. 14/055,606, filed October 16, 2013 in the name of John Nix, which is hereby incorporated by reference in its entirety.

Actuator 101y could be a device to control a parameter or state for a monitored unit 119, such as, but not limited to, changing a voltage or current, activating a switch or relay, turning on or off a microphone or speaker, activating or deactivating a light, and other examples are well known in the art. Actuator 101y could also be a speaker. Actuator 101y could be controlled by module 101 via a digital or analog output from CPU 101b, which could also be transmitted or sent via system bus 101d or a physical interface 101a. Although actuator 101y is illustrated as external to wireless module 101 in Figure 1c, actuator 101y could also be internal to module 101, and module 101 could include multiple actuators 101y. The use of multiple actuators 101y each with an actuator identity 152 is also depicted and described in connection with Figure 1e of U.S. Patent Application Serial No. 14/055,606, filed October 16, 2013 in the name of John Nix, which is hereby incorporated by reference in its entirety. Sensors and actuators are well known to those of ordinary skill in the art, and thus are not described in additional detail herein.

Module 101 can include a Universal Serial Bus (USB) interface 101v. In accordance with an exemplary embodiment, module 101 can comprise a wireless module and include a radio 101z. Note that the use of a radio 101z is not required for module 101, which could also obtain a connection to the IP Network 107 via a wired line such as Ethernet. Although not illustrated, radio 101z could include antennas for reception and transmission of RF signals, and even multiple antennas could be used. Although a single radio 101z is illustrated in module 101, module 101 could also contain multiple radios 101z. Radio 101z can support wireless LAN standards such as, but not limited to, WiFi, Bluetooth, and Zigbee, or similar wireless

Petitioner Samsung Ex-1004, 0033

LAN standards. Radio 101z illustrated in Figure 1c can comprise a radio 101z depicted and described in connection with Figure 1d of U.S. Patent Application Serial No. 14/039,401, filed September 27, 2013 in the name of John Nix, the contents of which are herein incorporated in their entirety.

Note that module 101 may also operate as a base station in a wireless LAN, such as, but not limited to, an 802.11 base station. When module 101 operates a wireless LAN, radio 101z can function as either a client/node and/or a base station 103 to support communication from other wireless nodes in physical proximity, such as, but not limited to, other nodes within an exemplary 50 meters. The other wireless nodes could comprise a sensor 101f and/or actuator 101y, and in this case a sensor could be referred to as a "networked sensor" and an actuator could be referred to as a "networked actuator". Radio 101z functioning as a base station is depicted and described as a base station 103 is depicted and described in connection with Figure 1d of U.S. Patent Application Serial No. 14/039,401, filed September 27, 2013 in the name of John Nix, the contents of which are herein incorporated in their entirety.

In accordance with exemplary embodiments, module 101 can store module private key 112, server public key 114, and module identity 110, and a symmetric key 127 in memory/RAM 101e during operation, such as when CPU 101b is active and the module 101 is connected to a network such as a wireless network 102 during data transmissions. Module private key 112 preferably is recorded in nonvolatile memory such as, but not limited to, flash memory 101w, so that module 101 has access to its private key 112 after the private key has been derived or loaded, including times when a battery 101k has been fully drained or removed from module 101 (if module 101 does not utilize a persistent power source such as land-line power).

Symmetric key 127 can be a secure, shared private key for use with symmetric encryption or symmetric ciphering algorithms 141b (in Figure 1g below). Symmetric key 127 can be derived by using module public key 111 and/or server public key 114, possibly through the use of a key derivation function 141f (described in Figure 1d below). Symmetric key 127 can be used for both encryption and decryption with symmetric cryptographic algorithms 141b described in Figure 1d below, where a shared secret key can be used to encrypt/cipher and/or decrypt/decipher. Symmetric key 127 may also include an expiration time 133, such that symmetric key 127 may only be used by module 101 and/or server 105 during a limited period of time, such symmetric key 127 remaining only valid for a day, or a week, or during a session (where the session comprises multiple messages and/or responses between a module 101 and a server 105), etc. Module 101 can also derive symmetric key 127 according the Elliptic Curve Integrated Encryption Scheme (ECIES) and/or ECDH 159, discussed in Figure 1d below, using module public key 111, server public key 114, and a random number 128a from random number generator 128. ECIES could be included in cryptographic algorithms 141. A summary of ECIES shared key derivation is described the Wikipedia article "Integrated

Petitioner Samsung Ex-1004, 0034

Encryption Scheme" from September 18, 2013 (herein incorporated by reference). Other possibilities for shared key derivation function using public keys are possible as well, including a Diffie–Hellman key exchange. Using a derived symmetric key from the exemplary key derivation function ECIES, module 101 and/or server 105 could derive a second symmetric key 127 after the expiration time 133 of the first symmetric key 127 had transpired. As contemplated herein, a symmetric key 127 can also comprise a session key, or the use of a "session key" with a symmetric ciphering algorithm 141b can comprise a symmetric key 127.

In an exemplary embodiment, a key derivation function 141f using public keys is not required to generate a shared symmetric key 127, and alternatively a shared symmetric key 127 could be generated by any of module 101, server 105, module provider 109, mobile network operator 108, or wireless network 102. If module 101 generates shared symmetric key 127 for symmetric ciphering 141b within a cryptographic algorithms 141, then module 101 can send shared symmetric key 127 to server 105 using an asymmetric ciphering depicted and described in connection with Figure 4 below. In accordance with a preferred exemplary embodiment, module 101 preferably uses a random number generator 128 to generate a random number 128a (illustrated in Figure 1d) for input into cryptographic algorithms 141, and the seed 128b in random number generator 128 could utilize data from a sensor 101f in order to generate a random number 128a with high entropy in the creation of symmetric key 127. Random number generator 128 and random number 128a are also depicted and described in connection with Figure 1d of U.S. Patent Application Serial No. 14/039,401, filed September 27, 2013 in the name of John Nix, the contents of which are herein incorporated in their entirety.

Module identity 110 is preferably a unique identifier of module 101, and could comprise a number or string such as, but not limited to, a serial number, an international mobile subscriber identity number (IMSI), international mobile equipment identity (IMEI), or an Ethernet media access control (MAC) address. According to an exemplary embodiment, module identity 110 can also comprise a serial number or string that is written into hardware of module 101 upon manufacturing or distribution of module 101 (also depicted and described in connection with a step 511 in Figure 5b below). In this case, module identity 110 could be recorded in a read only memory 101c, where read only memory 101c could not be easily erased or otherwise tampered with. Read only memory 101c could also comprise a protected memory and the address for accessing the module identity 101 within the ROM 101c could comprise a protected address. A protected address can comprise an address accessible to a CPU 101b and readable by CPU 101b where the data within the protected address is not modified, changed, or updated by a CPU 101b under normal operating conditions. Also note that the protected address can comprise one form of a nonvolatile memory, where a memory records data. Or, module 101 could read module identity 110, which could be written into hardware

Petitioner Samsung Ex-1004, 0035

by a manufacturer, distributor, or module provider 109, by using a device driver 101g that reads a hardware address containing the module identity 110 using the system bus 101d. In this case, the hardware address can comprise a protected address, as contemplated herein. Module 101 can read the module identity 110 by accessing a read-only address using the bus 101d. In either case, in many embodiments module identity 110 may preferably be permanently or persistently associated with the physical hardware of module 101, which can be helpful for the security procedures contemplated herein. Module identity 110 can function as a basic identifier for services from mobile network operator 108, wireless network 102, eUICC subscription manager 164, and/or server 105 in order to properly identify module 101 among a plurality of modules. Module private key 112 and module public key 111 could be unique to module 101 and uniquely associated with module identity 110, according to a preferred embodiment.

As contemplated herein, a module identity 110 can also have more than one use. A first module identity 110 could comprise a serial number for the physical hardware of module 101, as described in the paragraph above. A second module identity 110 could also comprise a session identifier, for data sessions between module 101 and server 105, where the session identifier can be uniquely associated by a server 105 to module 101. A third module identity 110 could comprise a network module identity 110b within a set of network access credential 314 described in Figure 3b below. A fourth module identity 110 can be associated with the eUICC 163. In embodiments where module identity 110 has more than one use, format, or representation, the module identity 110 associated with or written into hardware of module 101 (and potentially read from a read-only address in module 101) may preferably comprise the module identity 110 used in a certificate 122. Since a module 101 may utilize multiple module public keys 111 and module private keys 112 over its lifetime, a certificate 122 for module 101 can preferably include both (i) the module identity 110 (such as, but not limited to, a serial number for the physical hardware of module 101) and (ii) a module public key identity 111a in order to specify the particular module public key 111 associated with certificate 122. The use of a module public key identity 111a in a certificate 122 is also depicted and described in connection with Figure 1h of U.S. Patent Application Serial No. 14/055,606, filed October 16, 2013 in the name of John Nix. Since a module 101 may also have multiple public keys 111 for different purposes (such as, but not limited to, one for creating digital signatures, another for asymmetric ciphering, another for use with a second wireless network 102, etc.), then module 101 may also potentially have multiple valid certificates 122 concurrently each with different module public key identities 111a.

Further, as contemplated herein, a module identity 110 could also comprise more than one physical string or number, such as, but not limited to, a first string when module 101 connects with a first mobile network operator 108 or first wireless network 102, and module identity 110 could comprise a second string when module 101 connects with a second mobile network operator 108 or second wireless network 102. The

Petitioner Samsung Ex-1004, 0036

first mobile network operator 108 or first wireless network 102 may have a first requirement or specification for the format, length, structure, etc. of module identity 110, and the second mobile network operator 108 or second wireless network 102 may have a second requirement or specification for the format, length, structure, etc. of module identity 110. In this manner, even though more than one string or number is used to identify a module 101, the two different strings or numbers could comprise a module identity 110.

Server public key 114 in module 101 could be obtained from downloading the key over the IP Network 107, or optionally also written into nonvolatile memory of module 101 upon manufacture or distribution. Server public key 114 could be obtained using a domain name or Internet address that is recorded in nonvolatile memory upon the configuration of module 101, such as, but not limited to, during installation or distribution, and module 101 could fetch the server public key 114 upon connecting to a wireless network 102 or other connection to the IP Network 107. Additional elements besides those depicted in Figure 1c could also be recorded in volatile memory 101e, which could comprise a RAM 101e. For example, cryptographic algorithms 141, the shared secret keys 129, and the pre-shared secret key code 134 could also be recorded in RAM 101e as well. Note that values and related data can also be recorded in both RAM 101e and nonvolatile memory 101w at the same time, such that data in nonvolatile memory 101w allows module 101 to access the data after a shutdown state, but moving the same data into RAM 101e during an active state allows module 101 to more quickly perform operations using a CPU 101b. Other possibilities exist as well for the storage location of various values and data elements illustrated in Figure 1e without departing from the scope of the present invention.

Module 101 may also contain cryptographic algorithms 141, which may comprise a suite of algorithms or subroutines that can be utilized for (i) deriving a pair of keys comprising a public key and a private key, (ii) encrypting data using public keys, (iii) decrypting data using private keys, (iv) processing secure hash signatures using private keys, and (v) verifying secure hash signatures using public keys, and related software, firmware, or subroutines for implementing a cryptographic system, including symmetric ciphering algorithms. Cryptographic algorithms 141 (also described below in Figure 1d) could utilize publicly available software libraries within tools such as, but not limited to, OpenSSL maintained by The OpenSSL Project (http://www.openssl.org/), libgcrypt maintained by The Free Software Foundation (http://www.gnu.org/software/libgcrypt/), and similar libraries such as, but not limited to, libmcrypt and Crypto++. Note that cryptographic algorithms 141 could also use proprietary cryptographic libraries as well. In addition to implementing asymmetric encryption/ciphering, such as, but not limited to, used with RSA and ECC cryptography, cryptographic algorithms 141 can provide symmetric ciphering where a shared private key is utilized to both encrypt and decrypt, such as, but not limited to, with the Advanced Encryption Standard (AES) cipher suite.

Petitioner Samsung Ex-1004, 0037

As illustrated in Figure 1c, module 101 may also contain a random number generator 128. Random number generator 128 may contain a seed 128b. The creation of random numbers with a high degree of entropy may be important the use of cryptographic algorithms 141. A plurality of the data as a source for a random number seed 128b could be appended together into a "module random seed file" 139 (illustrated in Figure 1d) with a combined series or list of states (i.e. a plurality of sensor 101f measurements, radio 101z measurements, clock 160 times or values, memory 101e or memory 101w states, operating system 101h states, actuator 101y states, and/or hardware 101a or 101d states). Note that values or data for each of the elements listed in the previous sentence could be utilized in a "module random seed file" 139 instead of or in addition to a state. The "module random seed file" is also depicted and described in connection with Figure 1e of U.S. Patent Application Serial No. 14/055,606, filed October 16, 2013 in the name of John Nix, which is hereby incorporated by reference in its entirety

Note that the term "public key" as contemplated herein includes a key that may be shared with other elements, where the other elements may not be under the direct control of the same entity that holds the corresponding private key. However, the term "public key" as used herein does not require that the public key is made available to the general public or is publicly disclosed. An additional layer of security may be maintained in the present invention by preferably only sharing public keys on a confidential basis with other entities. For example, module public key 111 may be created by module 101 when generating module private key 112, and module 101 may share module public key 111 with mobile network operator 108 in order to record module public key 111 in server 105, but module 101 could choose to not (i) share module public key 111 with other entities, such as module provider 109 or (ii) provide a certificate 122 with module public key 111 publicly available on the IP Network 107. The benefits of confidentially sharing module public key 111 with server 105 are also further described below.

Although a single public key and private key for module 101 is illustrated in Figure 1c, both module 101 and server 105 may each utilize several different pairs of public keys and private keys. As one example, module 101 may record a first private key 112 used for creating a digital signature and a second private key 112 for decryption using asymmetric ciphering algorithms 141a. In this example, a server 105 could utilize a first module public key 111 to verify the digital signature, and a second module public key 111 could be utilized to encrypt messages sent to module 101. Similarly, either module 101 or server 105 may use private key 112 or 105c, respectively, to derive secondary shared keys such as, but not limited to, a derived shared key 129b below. Thus, one key pair could be used with digital signatures, a second key pair used for asymmetric ciphering, and a third key pair to derive shared secret keys. Each of the three illustrated pairs of keys could comprise a set of keys, and each of the illustrated pairs of keys could also use a different set of

Petitioner Samsung Ex-1004, 0038

cryptographic parameters 126 (illustrated in Figure 1g below), although the cryptographic parameters 126 for the various pairs of keys could also be the same.

In addition, module 101 could utilize a first set of keys to communicate with a first MNO 108 and a second set of keys to communicate with a second MNO 108. The first set of keys could use or be associated with a first set of cryptographic parameters 126 and the second set of keys could use or be associated with a second set of cryptographic parameters 126. According to exemplary embodiments, module 101 may also include a pre-shared secret key 129a. Pre-shared secret key 129a can comprise a secret key that is shared between module 101 and server 105 before module 101 begins (i) communicating with server 105 and/or a certificate authority 118, (ii) or utilizing PKI-based encryption and authentication to communicate with mobile network operator 108. As illustrated in Figure 1f below, server 105 could also record the pre-shared secret key 129a, and a pre-shared secret key 129a can be associated with each module 101 using a module identity 110. A pre-shared secret key 129a is also depicted and described in connection with U.S. Patent Application Serial No. 14/055,606, filed October 16, 2013 in the name of John Nix, which is hereby incorporated by reference in its entirety. In an exemplary embodiment, once the pre-shared secret key 129a has been utilized to authenticate or verify a module public key 111 with a server 105 (such as, but not limited to, using subsequent steps 517 in Figure 5b below), then that particular pre-shared secret key 129a may be "discarded" and not used again for security purposes contemplated herein.

Note that the use of a pre-shared secret key 129a and pre-shared secret key code 134 is also optional, such that a module program 101i could cipher of obfuscate the initial submission of a derived module public key 111 and module identity to a server 105, so that server 105 could be reasonably assured only a valid module 101 submitted the module public key 111. According to a preferred exemplary embodiment, module 101 can derive its own module private key 112 and module public key 111, and utilize pre-shared secret key 129a in order to securely and/or authoritatively communicate the derived module public key 111 with server 105 and/or a certificate authority 118. The use of pre-shared secret key 129a can be particularly useful if module 101 has already been deployed with a monitored unit 119 and connects to server 105 though the IP Network 107 for the very first time. Server 105 could preferably utilize pre-shared secret key 129a in order to confirm that a received module public key 111 and module identity 110 from module 101 authoritatively belong to module 101, as opposed to being an unauthorized or even fraudulent submission of module public key 111 and module identity 110.

Server 105 could utilize a pre-shared secret key 129a and the steps depicted and described in connection with Figure 4 below in order to securely receive module public key 111 and module identity 110 from module 101, including the first time module 101 sends module public key 111 to server 105. As one example, pre-shared secret key 129a could be utilized as a symmetric ciphering 141b key, described in

Petitioner Samsung Ex-1004, 0039

Figure 1d below. After the first submission of module public key 111 to server 105, any subsequent submissions of new module public keys 111 derived by module 101 could either (i) continue to use the pre-shared secret key 129a, or (ii) use a symmetric key 127 derived after the first module public key 111 has been received. Securing the submission of module public key 111 with server 105, including both the first submission and subsequent submissions, is also depicted and described in connection with Figure 5b below.

Figure 1d

Figure 1d is a graphical illustration of components in a set of cryptographic algorithms, in accordance with exemplary embodiments. As contemplated herein, communications with module 101 can be secured by using cryptographic algorithms 141. The cryptographic algorithms 141 used by module 101, server 105, or other servers can comprise a set of steps, procedures, or software routines for accomplishing steps to cipher, decipher, sign, and verify messages, including the generation of public keys, private keys, and derived shared keys, including symmetric keys. Cryptographic algorithms 141 can be implemented in software or firmware operating on (i) module 101 in the form of a module program 101i or an eUICC 163, (ii) server 105 in the form of a module controller 105x, or (iii) wireless network 102 or MNO 108 in the form of a server 105, where server 105 generates tokens for the authentication of a module 101 and mobile phones connecting with wireless network 102. Example software for a cryptographic algorithms 141 includes the libraries within the openssl, libmcrypt, and/or and Crypto++ discussed in Figure 1c. Other possibilities for the location of cryptographic algorithms 141 within a module 101, server 105, or wireless network 102 exist as well, including possibly module operating system 101h and a server operating system 105h (described in Figure 1k below).

In addition, cryptographic algorithms 141 may be implemented in hardware or firmware on any of module 101, server 105, or MNO 108. Note that module 101, server 105 and MNO 108 could each utilize a different set of cryptographic algorithms 141, although the sets of algorithms should preferably be fully interoperable (i.e. ciphering with a first symmetric ciphering algorithm 141b and a symmetric key 127 on module 101 could be deciphered by a second symmetric ciphering algorithm 141b on server 105 using the symmetric key 127, etc.). As illustrated in Figure 1d, cryptographic algorithms 141 may comprise an asymmetric ciphering algorithm 141a, a symmetric ciphering algorithm 141b, a secure hash algorithm 141c, a digital signature algorithm 141d, a key pair generation algorithm 141e, a key derivation function 141f, a random number generator 128, and the other algorithms depicted in Figure 1d.

Asymmetric ciphering algorithms 141a can comprise algorithms utilizing public key infrastructure (PKI) techniques for both (i) encrypting with a public key and (ii) decrypting with a private key. Example

Petitioner Samsung Ex-1004, 0040

algorithms within asymmetric algorithms 141a include the RSA algorithms 153 and the Elliptic Curve Cryptography (ECC) algorithms 154, and other asymmetric algorithms could be utilized as well. For example, either the ECC algorithms 154 or RSA algorithms 153 can be used for encryption and decryption, including (i) encryption step 402 discussed below in Figure 4, as well as (ii) decryption step 514 discussed below in Figure 5a. A set of cryptographic parameters 126 can include input into asymmetric ciphering algorithms 141a, such as, but not limited to, specifying key lengths, elliptic curves to utilize (if ECC), modulus (if RSA) or other parameters or settings required. As contemplated herein and described in additional detail below, the algorithms illustrated in Figure 1d can perform both ciphering and deciphering, using the appropriate keys. Although RSA algorithms 153 and ECC algorithms 154 are illustrated within an asymmetric ciphering algorithm 141a, a RSA algorithm 153 and ECC algorithm 154 could also be associated with a key pair generation algorithm 141e and other elements within a set of cryptographic algorithms 141, and thus not exclusively used within a set of cryptographic algorithms 141 by an asymmetric ciphering algorithm 141a.

The use and application of RSA algorithms and cryptography are described within IETF RFC 3447 titled "Public-Key Cryptography Standards (PKCS) #1: RSA Cryptography Specifications Version 2.1", herein incorporated by reference, among other published standards for the use of RSA algorithms 153. The use of an RSA algorithm 153 for encryption and decryption, including with cryptographic algorithms 141 and other description of encryption or decryption algorithms, can also be processed according to the description of the RSA algorithm according to the Wikipedia entry for "RSA (algorithm)" as of September 9, 2013, which is incorporated by reference herein.

The use and application of ECC algorithms 154 for asymmetric ciphering algorithms 141a within cryptographic algorithms 141 are described within IETF RFC 6090 titled "Fundamental Elliptic Curve Cryptography Algorithms" (herein incorporated by reference), among other published standards using ECC. ECC algorithms 154 can also utilize elliptic curve cryptography algorithms to the Wikipedia entry for "Elliptic curve cryptography" as of September 9, 2013, which is incorporated by reference herein. ECC algorithms 154 may utilized according to exemplary preferred embodiments in order to maintain high security with smaller key lengths, compared to RSA, thereby helping to comparably reduce the message lengths, radio frequency spectrum utilization, and processing power required by module 101. Thus, the use of ECC algorithms 154 within various steps requiring ciphering or digital signatures may help conserve battery life of module 101 while maintaining the objective of securing system 100 and other systems illustrated herein. Note that as contemplated herein, other algorithms besides with ECC algorithms 154 and RSA algorithms 153 may be also be used in asymmetric algorithms 141a and also a key pair generation algorithm 141e.

Petitioner Samsung Ex-1004, 0041

Cryptographic algorithms 141 may also include a set of symmetric ciphering algorithms 141b. Symmetric ciphering algorithms 141b can utilize a symmetric key 127 by one node such as a module 101 to encrypt or cipher data, and the encrypted data can be decrypted or deciphered by server 105 also using the symmetric key 127. Examples of symmetric ciphers include Advanced Encryption Standard 155 (AES), as specified in Federal Information Processing Standards (FIPS) Publication 197, and Triple Data Encryption Standard (Triple DES), as described in NIST Special Publication 800-67 Revision 1, "Recommendation for the Triple Data Encryption Algorithm (TDEA) Block Cipher (Revised January 2012)". Cryptographic parameters 126 input into symmetric ciphering algorithms 141b can include symmetric key 127 length, such as, but not limited to, the selection of 128, 192, or 256 bits with AES 155 symmetric ciphering, and cryptographic parameters 126 could also select a symmetric ciphering algorithm in a collection of symmetric ciphering algorithms 141b. Other examples of symmetric ciphering algorithms 141b may be utilized as well within cryptographic algorithms 141. Also note that as contemplated herein, the term "symmetric ciphering" contemplates the use of a symmetric key 127 in order to encrypt or cipher data with a symmetric ciphering algorithm 141b, and "asymmetric ciphering" contemplated the use of an asymmetric ciphering algorithm 141a to encrypt or cipher data with a public key, such as module public key 111 or server public key 114.

Cryptographic algorithms 141 may also include a set of secure hash algorithms 141c in order to compute and output a secure hash value or number based on a string or file input into the secure hash algorithms 141c. Example secure hash algorithms include SHA256 156 (also known as SHA-2) and SHA-3 157. SHA256 156 is specified in the National Institute of Standards and Technology (NIST) Federal Information Processing Standards Publication (FIPS PUB) 180-2 titled "Secure Hash Standard". SHA-3 157 is scheduled to be published in FIPS PUB 180-5. Cryptographic parameters 126 input into secure hash algorithms 141c can include the selection of the length of the secure hash, such as, but not limited to, using 224, 256, or 512 bits with either SHA-2 or SHA-3, and other possibilities exist as well.

Cryptographic algorithms 141 may also include a set of digital signature algorithms 141d, in order to sign and verify messages between (i) module 101 and server 105 or (ii) server 105 and wireless network 102. Digital signature algorithms 141d can also verify signatures such as, but not limited to, comparing that (i) a first secure hash value in the form of a digital signature in a certificate (not shown) using a certificate authority public key matches (ii) a second secure hash value in the certificate (not shown). Digital signature algorithms 141d can utilize algorithms in National Institute of Standards (NIST) "FIPS 186-4: Digital Signature Standard", or IETF RFC 6979 titled "Deterministic Usage of the Digital Signature Algorithm (DSA) and Elliptic Curve Digital Signature Algorithm (ECDSA)". The use of ECDSA algorithm 158 within a set of digital signature algorithms 141d may be preferred if keys such as, but not limited to, module public key 111 and server public key 114 are based on elliptic curve cryptography. The use of the Digital Signature

Petitioner Samsung Ex-1004, 0042

Standard can comprise a DSA algorithm 167. Other PKI standards or proprietary techniques for securely verifying digital signatures may be utilized as well in digital signature algorithms 141d. Cryptographic parameters 126 input into digital signature algorithms 141d can include the selection of a secure hash algorithms 141c to utilize with digital signature algorithms 141d, or the algorithm to utilize, such as, but not limited to, ECDSA 158 shown or an RSA-based alternative for digital signatures is possible as well. Cryptographic parameters 126 input into digital signature algorithms 141d can also include a padding scheme for use with a digital signature algorithms 141d. Digital signature algorithms 141d could also include an RSA digital signature algorithm for use with RSA-based public and private keys.

Cryptographic algorithms 141 may also include key pair generation algorithms 141e, a key derivation function 141f, and a random number generator 128. Key pair generation algorithms 141e can be utilized by module 101, server 105, or network 102 to securely generate private and public keys. The key pair generation algorithms 141e can also use input from a cryptographic parameters 126, such as, but not limited to, the desired key lengths, or a value for an ECC curve if the public key will support ECC algorithms 154. According to an exemplary preferred embodiment, module 101 can derive a pair of module public key 111 and module private key 112 using key pair generation algorithms 141e. Software tools such as, but not limited to, openssl and libcrypt include libraries for the generation key pairs, and these and similar libraries can be used in a key pair generation algorithm 141e.

Key derivation function 141f can be used by module 101, server 105, and/or wireless network 102 in order to determine a common derived shared secret key 129b, using at least two numbers as input. In exemplary embodiments, one of the two numbers as input can comprise one of (i) a private key, or (ii) a secret shared key 129. The other of the two numbers input into a key derivation function 141f could comprise at least one number from (i) a set of cryptographic algorithms 126 or (ii) a random number 128 that is commonly shared between two nodes utilizing a key derivation function 141f in order to process or obtain the same derived shared secret key 129b. A key exchange to share a common symmetric key 127 can be performed using a key derivation function 141f and cryptographic parameters 126, in addition to using public and/or private keys in some embodiments. In exemplary embodiments, three values comprising (i) a private key, (ii) a token such as a public key or a random number, and (iii) values from a set of cryptographic parameters 126 can be input into the key derivation function 141f in order to output a derived shared secret key 129b.

An exemplary algorithm within a key derivation function 141f can be the Diffie-Hellman key exchange, which is used by tools such as, but not limited to, secure socket layer (SSL) with RSA algorithms 153. When using ECC algorithms 154, module 101 and server 105 can utilize Elliptic Curve Diffie-Hellman (ECDH) algorithms 159, and a summary of ECDH is included in the Wikipedia article titled "Elliptic Curve

Petitioner Samsung Ex-1004, 0043

Diffie-Hellman" (http://en.wikipedia.org/wiki/Elliptic_curve_Diffie %E2%80%93Hellman from September 24, 2013, which is herein incorporated by reference. Other algorithms to derive a shared secret key 129b using public keys, private keys, and tokens may also be utilized in a key derivation function 141f, such as, but not limited to, the American National Standards Institute (ANSI) standard X-9.63 160. Cryptographic parameters 126 used with key derivation function 141f with elliptic curve cryptography can include a common base point G for two nodes using the key derivation function 141f and public keys. The base point G in a cryptographic parameters 126 can be transmitted or sent from a module 101 to a server 105 in a message 208, and the base point G can be sent from a server 105 to a module 101 in a response 209, and other possibilities exist as well, including recording the base point G within a received eUICC profile 311. Cryptographic parameters 126 can also include other or additional information for using a key derivation function 141f in order to derive either (i) a commonly shared symmetric key 127, or (ii) a commonly shared secret key 129b. The use of a key derivation function 141f with a Diffie Helmman key exchange is also depicted and described in connection with Figure 11 below. Other possibilities for a key derivation function 141f exist as well without departing from the scope of the present invention.

Cryptographic parameters 126 input into key pair generation algorithms 141e can include the type of asymmetric ciphering algorithms 141a used with the keys, the key length in bits, an elliptic curve utilized for ECC, a time-to-live for a public key that is derived, and similar settings. Additional cryptographic parameters 126 for a public key can include a supported point formats extension, where the supported point formats extension could comprise uncompressed, compressed prime, or "compressed char2" formats, as specified in ANSI X-9.62. In other words, an ECC public key can have several formats and a set of cryptographic parameters 126 can be useful to specify the format. Although a set of cryptographic parameters 126 is illustrated in Figure 1d as internal to cryptographic algorithms 141, parameters 126 could be recorded in other locations in a module 101 or a system 100. As one example, a set of cryptographic parameters 126 could be recorded in a server 105 and downloaded by module 101 using the IP Network 107. The various algorithms within cryptographic algorithms 141 may utilize a random number generator 128, which is also depicted and described in connection with Figure 1c above. As contemplated herein, the term "cryptographic parameters" 126 may be considered equivalent to a "set of cryptographic parameters" 126, and also use of the terms "parameters" 126 and "set of parameters" 126 can both refer to the cryptographic parameters 126 illustrated in Figure 1d and Figure 1i. Cryptographic parameters 126 are also further depicted and described in connection with Figure 1i below.

According to a preferred exemplary embodiment, cryptographic parameters 126 can include values to define an elliptic curve and/or use ECC algorithms 154. A set of ECC parameters 137 could comprise values or numbers for an elliptic curve defining equation. ECC parameters 137 are also depicted and described in

Petitioner Samsung Ex-1004, 0044

Figure 1g of U.S. Patent Application Serial No. 14/055,606, filed October 16, 2013 in the name of John Nix, which is hereby incorporated by reference in its entirety. Cryptographic parameters 126 could also include an ECC standard curve 138, which could comprise a name and/or values for a standardized curve, such as, but not limited to, the list of named curves included in section 5.1.1 of IETF RFC 4492 titled "Elliptic Curve Cryptography (ECC) Cipher Suites for Transport Layer Security (TLS)."

As contemplated herein, a set of cryptographic algorithms 141 may operate using either strings or numbers, and cryptographic parameters 126 could include either strings or numbers as well. As contemplated herein (i) a collection, sequence, and/or series of numbers could comprise a string, (ii) a string can include a mixture of numbers and characters, or (iii) a string can comprise a collection, sequence, and/or series of characters or bits. The processing of cryptographic algorithms 141 within a module 101 can take place within a CPU 101b, or module 101 could also process cryptographic algorithms in a cryptographic processing unit (not shown) connected to the system bus 101d. An eUICC 163 could also include a set of cryptographic algorithms 141, in addition to a separate set of cryptographic algorithms 141 being recorded in a flash memory 101w for module 101. According to an exemplary embodiment, a module 101 or a server 105 could include a cryptographic processing unit (not shown) separate from the CPU 101b or CPU 105b in order to increase efficiency or security for supporting the use of cryptography through a system 100. An eUICC 163 could comprise the separate cryptographic processing unit. Alternatively, in exemplary embodiments cryptographic algorithms 141 can be implemented entirely in software within a module 101 and/or server 105, and also utilized by a module controller 105x and network controller 101i.

A shared secret algorithm 141g is depicted and described in connection with Figure 1f below. In an exemplary embodiment, a shared secret algorithm 141g can comprise an algorithm to accept input from (i) a set of component parameters 101t and (ii) an algorithm token 190, which are both depicted and described in connection with Figure 1e and Figure 1f, and the shared secret algorithm 141g can output a shared secret key 129c. A secret ciphering algorithm 141h is depicted and described in connection with Figure 1g below. In an exemplary embodiment, a secret ciphering algorithm 141h can comprise an algorithm to accept input from (i) a module identity 110 and (ii) an algorithm token 190 as a key, which are both depicted and described in connection with Figure 1f, and the secret ciphering algorithm 141h can output an encrypted module identity 110a. A secret ciphering algorithm 141h can also be used as a symmetric ciphering algorithm 141b, where the logic and/or steps for using a key such as, but not limited to an algorithm token 190, remain secret and/or are not publicly shared. In an exemplary embodiment, a secret ciphering algorithm 141h can be similar to AES 155, but with a different and confidential series of steps for mixing and substituting data input in order to output encrypted data. A server 105 or other servers can use a secret ciphering algorithm 141h and input of a ciphertext and a key to derive or process plaintext. In an exemplary embodiment, a server 105 or other

Petitioner Samsung Ex-1004, 0045

servers can use a secret ciphering algorithm 141h and input of (i) ciphertext of an encrypted module identity 110a and (ii) an algorithm token 190 in order to output a module identity 110.

Figure 1e

Figure 1e is a graphical illustration of a set of components for a module and a set of component parameters, in accordance with exemplary embodiments. A module 101 can comprise a plurality of hardware and software components for operating in a system 100 and other exemplary systems illustrated herein. The hardware components can be manufactured and assembled into a housing or enclosure for distribution to module providers 109 and/or distributors or end users of a module 101. Hardware components illustrated in Figure 1e can include a RAM 101e, a flash memory 101w, a CPU 101b, a radio 101z, an eUICC 163, a sensor 101f, and an actuator 101y. Software and/or firmware components can include operating system 101h and also a module program 101i (not shown). Module 101 can also include a plurality of any of these components. Any of the components can include a set of component parameters 101t, including a model number, size or capacity, a serial number, a manufacturing date (or release date), a system bus 101d address, a speed or capacity, an operating frequency, a software or firmware version for the component, a file size, an associated battery size 101k, and/or a list of values, etc. The overall assembled and/or manufactured module 101 can include component parameters 101t as well, including a serial number, version number, list of supported sensors and/or actuators, etc. Component parameters 101t are depicted in Figure 1e as illustrative as opposed to being limiting, and other component parameters can be utilized as well for a set of component parameters 101t, in addition to the use of different components than those illustrated in Figure 1e.

In exemplary embodiments, component parameters 101t can include many values that remain persistent over the lifetime of a module 101, although in some embodiments a component for a module 101 could be changed after manufacturing. As one example, a technician could change a memory unit such as a RAM 101e for upgrade or other purposes, and the new RAM 101e could subsequently utilize different component parameters 101t. In exemplary embodiments other entities besides the module 101 could record or store a set of component parameters 101t for a module 101, including module provider 109, mobile network operator 108, and/or a server 105. A server 105 or the other entities could record a set of component parameters 101t in a database with a module identity 110, and the database that includes component parameters 101t for the module 101 could be updated if the component parameters 101t change after manufacturing. As contemplated herein, a set of component parameters 101t can comprise any of the component parameters 101t for each of the hardware and/or software elements within a module 101, including component parameters 101t for the overall module 101. A set of component parameters can

Petitioner Samsung Ex-1004, 0046

comprise either numbers or strings, including a mix of numbers and strings. As contemplated herein, the term "set of component parameters" 101t can also refer to component parameters 101t. Since each module 101 in a plurality of modules 101 can be different, such as using different serial numbers for individual components, a set of component parameters 101t for a module 101 can be unique in exemplary embodiments. Other possibilities exist as well for a set of component parameters 101t to be unique for a module 101 without departing from the scope of the present invention.

Figure 1f

Figure 1f is a graphical illustration for deriving a shared secret key using a shared secret algorithm, an algorithm token, and component parameters, in accordance with exemplary embodiments. A module 101 and/or server 105 can use a shared secret algorithm 141g to process or derive a shared secret key 129c using as input (i) a set of component parameters 101t and an algorithm token 190. A set of component parameters 101t for a module 101 are depicted and described in connection with Figure 1e above. The component parameters 101t for a module 101 can include a list of values input into the shared secret algorithm 141g such as one or more component or system serial numbers, system bus 101d addresses, component model numbers, component sizes, date or time values for component manufacturing or release dates, and/or other similar data. In an exemplary embodiment, the set of parameters 101t input into a shared secret algorithm 141g can be persistent or relatively long-lived, such that the list of values from a set of component parameters 101t do not frequently change. In another embodiment, the list or values for a module 101 comprising a set of component parameters 101t can change over time, and in this case, both module 101 and a server 105 (or other servers using the shared secret algorithm 141g) would also record any updated or changed values for a set of component parameters 101t in order to utilize the same input. In other words, a set of component parameters 101t used by a module 101 and a server 105 (or other servers associated with server 105) can keep the set of component parameters 101t for a module 101 synchronized.

An algorithm token 190 input into a shared secret algorithm 141g can comprise a temporary value or a number or a string that may preferably only be used once in exemplary embodiments. As illustrated in Figure 1f, an algorithm token 190 can comprise a timestamp and/or a random number 128a. The timestamp can be calculated using a clock 160 and the random number 128a may comprise a random number 128a processed with a random number generator 128. The random number generator 128 could use a "module random seed file" 139 in order to populate a seed 128b with a number or value that comprises a high level of "noise" or information entropy. As contemplated herein, a random number 128a can comprise a pseudo-random number such that the number output by a random number generator 128 may not completely mathematically random, but for the purposes contemplated herein a pseudo-random number can comprise a

Petitioner Samsung Ex-1004, 0047

random number 128a. In an exemplary embodiment, an algorithm token 190 can comprise a time value, a random number 128a alone, or a combination of a time value and a random number 128a. In an exemplary embodiment, the time value and/or random number 128 may preferably have a sufficient number of digits or resolution such that the probability of using the same random number 128a and/or time value as an algorithm token 190 input into a shared secret algorithm 141g would be sufficiently small or negligible. Note that other values besides a time value or a random number 128a could be used in an algorithm token 190, where the other values also have a low probability of being reused and/or also contain a high level of information entropy. As contemplated herein, an algorithm token 190 can also be used with other algorithms in a set of cryptographic algorithms 141 in addition to a shared secret algorithm 141g, including a secret ciphering algorithm 141h depicted and described in connection with Figure 1g below.

Shared secret algorithm 141g can use the algorithm token 190 and set of component parameters 101t as input and output a shared secret key 129c. Another element in a system 100 besides a module 101 can obtain or process the same shared secret key 129c using an equivalent value for an algorithm token 190 and set of component parameters 101t. Consequently in preferred embodiments module 101 and the other element such as, but not limited to server 105, could determine the same or equivalent value for an output shared secret key 129c without having to send or receive the shared secret key 129c output from the shared secret algorithm 141g. Shared secret algorithm 141g could use logic or a set of programmatic steps for taking the values input and generating the output of a shared secret key 129c. In an exemplary embodiment, shared secret algorithm 141g could select, mix, and append values from the series of component parameters 101t and the time value and/or random number 128a into a string or number. A shared secret algorithm 141g could also use data from the algorithm token 190 to determine or process data from the set of component parameters 101t in order to output at least one shared secret key 129c.

In an exemplary embodiment, a string or number resulting from processing the set of component parameters 101t and algorithm token 190 could be input into a secure hash algorithm 141c with a shared secret algorithm 141g, and the output of the secure hash algorithm 141c could be used for a shared secret key 129c. Other possibilities for the logic of a shared secret algorithm 141g, including using a set of component parameters 101t and an algorithm token 190 to create a shared secret key 129c, are possible as well without departing from the scope of the present invention. Although a single algorithm token 190 and single shared secret key 129c are illustrated in Figure 1f, a module 101 and server 105 could use a plurality of single algorithm tokens 190 with a shared secret algorithm 141g. In an exemplary embodiment, shared secret algorithm 141g could also output a plurality of shared secret keys 129c, and other logic could specify the use of one or several of the plurality of shared secret keys 129c output by a shared secret algorithm 141g.

Petitioner Samsung Ex-1004, 0048

In an exemplary embodiment, the values from the series of component parameters 101t and the algorithm token 190, such as, but not limited to a time value and/or random number 128a, both (i) input into a shared secret algorithm 141g and (ii) including possibility using a secure hash algorithm 141c with a shared secret algorithm 141g, can be longer (or comprise more bits) than the output of a shared secret algorithm 141g. The logic for processing the set of component parameters 101t and algorithm token 190 as input into the shared secret algorithm 141g can include rules, steps, and/or logic for selecting subsets of the input data, mixing the input data, and ordering the input data. In an exemplary embodiment, the rules, steps, and/or logic for processing the input data in a shared secret algorithm 141g may preferably remain confidential or not publicly shared, in order for the output of shared secret key 129c to reasonably remain "secret" and not reasonably obtainable by third parties who might also have the set of component parameters 101t and the algorithm token 190.

In exemplary embodiments where a secure hash algorithm 141c is used in or with a shared secret algorithm 141g, a processed subset of the output from the secure hash algorithm 141c could be used for the shared secret key 129c. For example, if (A) the secure hash algorithm 141c outputs 256 bits, but a smaller key is needed such as an exemplary 128 bits for a shared secret key 129c that comprises a symmetric key 127 for use with AES ciphering 155, then (B) shared secret algorithm 141g could also contain logic to select or derive the shared secret key 129c of the appropriate length from the output of a secure hash algorithm 141c, including truncating, parsing, or selecting a subset the output from a secure hash algorithm 141c. Multiple instances or rounds of one or many of a secure hash algorithm 141c could also be used with a shared secret algorithm 141g such that data input is processed in a shared secret algorithm 141g using a secure hash algorithm 141c more than once. In exemplary embodiments, as described below in Figure 1g, the algorithm token 190 for a shared secret algorithm 141g can be shared by module 101 with other parties or nodes, including a server 105, in order for the server 105 to calculate the same shared secret key 129c using the shared secret algorithm 141g and the same set of recorded component parameters 101t. In these embodiments mentioned in the previous sentence, the module 101 could send the algorithm token to a server 105 in a message 208, as illustrated in Figure 6 below.

As contemplated herein, a shared secret key 129c output from a shared secret algorithm 141g may have multiple different uses, where a first shared secret key 129c can be used in a module identity string ciphering algorithm 161 (Figure 1g below) and a second shared secret key 129c could be used as a symmetric key 127. Also, a shared secret algorithm 141g can comprise one embodiment of a key derivation function 141f, where the shared secret key 129c can also comprise a derived shared secret key 129b. Other possibilities exist as well without departing from the scope of the present invention.

Petitioner Samsung Ex-1004, 0049

Figure 1g

Figure 1g is a graphical illustration for ciphering and deciphering plaintext using a secret ciphering algorithm with input of ciphertext and a key, in accordance with exemplary embodiments. Figure 1g illustrates an exemplary secret ciphering algorithm ciphering 161 and an exemplary secret ciphering algorithm deciphering 162. In the exemplary secret ciphering algorithm ciphering 161, a secret ciphering algorithm 141h can process or derive output of ciphertext as encrypted module identity 110a using input of (i) an algorithm token 190 as a cipher key and (ii) plaintext in the form of a module identity 110. In the exemplary secret ciphering algorithm deciphering 162, a secret ciphering algorithm 141h can process or derive plaintext output of a module identity 110 using input of (i) an algorithm token 190 as a cipher key and (ii) ciphertext in the form of an encrypted module identity 110a. As contemplated herein, a secret ciphering algorithm 141h as one form of a symmetric ciphering algorithm 141b can also process other ciphertext and plaintext besides an encrypted module identity 110a and a module identity 110, respectively. In addition, a secret ciphering algorithm 141h can use a different key besides an algorithm token 190 as a cipher key, such as, but not limited to, a random number 128a as a cipher key.

The communication of a module identity 110 in a system 100 and other systems illustrated herein can include the transmission of an encrypted module identity 110a with the cipher key in the form of an algorithm token 190. The transmission of an encrypted module identity 110a with the cipher key in the form of an algorithm token 190 can remain reasonably secure, since the symmetric ciphering algorithm 141b used in a secret ciphering algorithm 141h to process ciphertext transmitted can remain secret or confidential. The secret symmetric ciphering algorithm 141b can comprise a secret ciphering algorithm 141h. A secret ciphering algorithm 141h is also depicted and described in connection with Figure 1d. In an exemplary embodiment, secret ciphering algorithm 141h, and other cryptographic algorithms 141, can be included in a module program 101i and a program, library, or subroutine in a server 105.

In an exemplary embodiment, in order for the secret ciphering algorithm 141h to remain reasonably secure and/or confidential, the secret ciphering algorithm 141h can either (i) not be transmitted across a network such as, but not limited to, the IP Network 107 and recorded in module 101 upon manufacturing and/or distribution, or (ii) transmitted across a network such as, but not limited to, the IP Network 107 in an encrypted or ciphered format. In exemplary embodiments, a cipher key used in a secret ciphering algorithm ciphering 161 and a secret ciphering algorithm deciphering 162 can also comprise any of a shared secret key 129c, a symmetric key 127, a derived shared key 129b, or a pre-shared secret key 129a. With the use of a cipher key such as a shared secret key 129c, a symmetric key 127, a derived shared key 129b, or a pre-shared secret key 129a, these keys may optionally not be transmitted with the ciphertext output of secret ciphering

Petitioner Samsung Ex-1004, 0050

algorithm 141h, when the other node also can derive or obtain the cipher key through secure means. Other possibilities exist as well, in order for a module 101 and a server 105 to use the same cipher key with a secret ciphering algorithm 141h to decrypt or resolve the ciphertext possibly in the form of an encrypted module identity 110a into plaintext possibly in the form of a module identity 110. A secret ciphering algorithm 141h could select, mix, and append values from the cipher key and the plaintext in a secret or confidential manner in a plurality of rounds, such that an observer with the cipher key and the ciphertext would not reasonably be able to read or determine the plaintext.

In exemplary embodiments, a module identity 110 can be sent or transmitted in the form of an encrypted module identity 110a in order to protect the identity of module 101 from third parties along the path of communications between a module 101 and a server 105. The algorithm token 190 sent with the encrypted module identity 110a can be a cipher key used by a secret ciphering algorithm 141h to decipher the encrypted module identity 110a into a module identity 110. A module 101 can use a secret ciphering algorithm ciphering 161 to convert a module identity 110 into an encrypted module identity string 110a with an algorithm token 190 as a cipher key. In a secret ciphering algorithm ciphering 161, the module identity 110 and the algorithm token 190 as a cipher key can be input in to a secret ciphering algorithm 141g in order to output a encrypted module identity 110a string or number. The algorithm token 190 can comprise or use a random number 128a. A module 101 sending a message with an encrypted module identity 110a and an algorithm token 190 is depicted and described in connection with Figure 6 below. In an exemplary embodiment, the plaintext can include a security token 401 in order to prevent replay or reuse of the encrypted module identity 110a, where a security token 401 is depicted and described in connection with Figure 4 below. Note that the use of a security token 401 is optional and may be omitted, and replay or reuse of an encrypted module identity 110a can also be implemented by changing the algorithm token 190 used as a cipher key.

A node such as a server 105 could use a secret ciphering algorithm deciphering 162 in order to read plaintext from a received ciphertext and also a received algorithm token 190. When used with an encrypted module identity 110a, a server 105 could process or input the encrypted module identity 110a into a secret ciphering algorithm 141h, along with inputting the algorithm token 190, in order to extract the plaintext. A secret ciphering algorithm deciphering 162 can comprise the reverse or inverse operation of secret ciphering algorithm ciphering 161. Note that the plaintext could include a security token 401 in order to prevent replay or reuse of the ciphertext, and a security token 401 is depicted and described in connection with Figure 4 below and could comprise a random number or string. In order to decrypt an encrypted module identity 110a, a server 105 would preferably use the same secret ciphering algorithm 141h implemented by the module 101 sending the encrypted module identity 110a. The module 101 can use a secret ciphering

Petitioner Samsung Ex-1004, 0051

algorithm ciphering 161 to cipher or encrypt the module identity 110 as the encrypted module identity 110a. The server 105 can also receive the algorithm token 190 along with a message that contains the encrypted module identity 110a. Although illustrated in Figure 6 below as both encrypted module identity 110a and algorithm token 190 being received by a server 105 in the same message, the two values could be sent in separate messages.

An algorithm token 190 as a cipher key input into a secret ciphering algorithm 141h can comprise a temporary value or a number or a string that may preferably only be used once in exemplary embodiments, and can include a random number 128a. As illustrated in Figure 1h, an algorithm token 190 for a secret ciphering algorithm 141h can comprise a timestamp and/or a random number 128a. The timestamp can be calculated using a clock 160 and the random number 128a may comprise a random number 128a processed with a random number generator 128. The random number generator 128 could use a "module random seed file" 139 in order to populate a seed 128b with a number or value that comprises a high level of "noise" or information entropy. In an exemplary embodiment, an algorithm token 190 can comprise a time value alone, a random number 128a alone, or a combination of a time value and a random number 128a. In an exemplary embodiment, the time value and/or random number 128 may preferably have a sufficient number of digits or resolution such that the probability of using the same random number 128a and/or time value as an algorithm token 190 input into a secret ciphering algorithm 141h would be sufficiently small or negligible. Note that other values besides a time value or a random number 128a could be used in an algorithm token 190, where the other values also have a low probability of being reused and also contain a high level of information entropy.

In an exemplary embodiment, for a system 100 with a plurality of modules 101, different modules 101 could utilize different secret ciphering algorithms 141h. Other identifying information besides a module identity 110 within a module encrypted data 110a could be used by a set of servers 105 in order to determine which secret ciphering algorithm 141h is used for any given module 101. A first set of modules 101 using a first secret ciphering algorithm 141h, possibly to encrypt a module identity 110, could send data to a first IP address or port number. The receipt of data at the port number or address by the server could signal or determine for the server 105 which secret ciphering algorithm 141h was used to encrypt the plaintext, thereby allowing the server 105 to select the appropriate secret ciphering algorithm 141h in order to decrypt the received ciphertext. Or, module 101 could send a value in a message that would specify which secret ciphering algorithm 141h is used with ciphertext sent by module 101, such as an encrypted module identity 110a. Other possibilities exist as well for the use of a plurality of secret ciphering algorithms 141h as well, without departing from the scope of the present invention.

Petitioner Samsung Ex-1004, 0052

In exemplary embodiments, where a module identity 110 may be obfuscated or encrypted in an encrypted module identity 110a sent to a server 105 in a message, the packet may also contain other encrypted data such as a module encrypted data 403 depicted and described below in Figure 4. The packet can also include the algorithm token 190. A module encrypted data 403 can be ciphered with a symmetric key 127 and a different symmetric ciphering algorithm 141b than secret ciphering algorithm 141h. A server 105 receiving a packet containing a module encrypted data 403 should preferably be able to select a symmetric key 127 using a module identity 110 in order to decrypt the module encrypted data 403. Since the module identity 110 may be transmitted as an encrypted module identity 110a, the server 105 can use the algorithm token 190 and a secret ciphering algorithm deciphering 162 in order to read the plaintext module identity 110. Upon reading the plaintext module identity 110, the server can select the symmetric key 127 from a module database 105k in order to decrypt the module encrypted data 403 into plaintext.

Figure 1h

Figure 1h is a graphical illustration for deriving a shared secret key and an encrypted module identity, in accordance with exemplary embodiments. As depicted and described in connection with Figure 1f, a shared secret key 129c can be calculated or derived by a shared secret algorithm 141g, where the shared secret algorithm 141g can use input from a set of component parameters 101t and an algorithm token 190. The set component parameters 101t depicted in Figure 1h are shown as illustrative as opposed to limiting, and other component parameters 101t could be utilized as well by a shared secret algorithm 141g. The values for a set of component parameters 101t could be encoded in different formats than plaintext as well. The algorithm token 190 can also comprise different data, such as a random number 128a in the form of binary or hexadecimal data and also with a longer set of digits than those shown in Figure 1h. A timestamp can be in other formats, such as, but not limited to, a number corresponding to unix epoch time. A module 101 and a server 105 could calculate the same or equivalent shared secret key 129c using the same or equivalent input from the algorithm token 190 and the set of component parameters 101t. The module 101 and server 105 could use the same share secret algorithm 141g to determine the same shared secret key 129c. The server 105 could record the set of component parameters 101t in a module database 105k, and the server 105 could select the set of component parameters 101t using a module identity 110 received in a message. A shared secret key 129c could also comprise a number longer than the number illustrated in Figure 1h, such as an exemplary 128 bits for use as a symmetric key 127 with a symmetric ciphering algorithm 141b that requires a key of 128 bits, and other possibilities exist as well.

In order to output shared secret key 129c, shared secret algorithm 141g can use the logic and/or steps for a shared secret algorithm 141g depicted and described in connection with Figure 1f to process the input

Petitioner Samsung Ex-1004, 0053

data from the set of component parameters 101t and the algorithm token 190 in order to calculate the shared secret key 129c. Different values for a shared secret key 129c could be calculated using different values for the set of component parameters 101t and the algorithm token 190. As illustrated in Figure 1h, a first module 101 associated with a first module identity 110 could use a first set of component parameters 101t and different values for an algorithm token 190 in order to obtain different shared secret keys 129c over time, and a server 105 could calculate the same shared secret keys 129c by receiving the algorithm token 190 in a message. As illustrated in Figure 1h, a second module 101 associated with a second module identity 110 could use a second set of component parameters 101t and different values for an algorithm token 190 in order to obtain different shared secret keys 129c associated with the second module 101 over time. A server 105 could calculate the corresponding shared secret keys 129c for the second module 101 by receiving the algorithm token 190 in a message, and use the second set of component parameters 101t.

Encrypted module identity 110a can be calculated by a module 101 using a secret ciphering algorithm ciphering 161 and a key in the form of an algorithm token 190. The algorithm token 190 can preferably include a random number 128a in an exemplary embodiment. As illustrated in Figure 1h, a set of component parameters 101t can also be used in a ciphering key in a secret ciphering algorithm ciphering 161, but the use of component parameters 101t with a secret ciphering algorithm ciphering 161 can optionally be omitted, and in this case the ciphering key for a secret ciphering algorithm ciphering 161 can comprise an algorithm token 190. The encrypted module identity 110a and algorithm token 190 could be sent to a server 105 in an exemplary message illustrated in Figure 6 below. A server 105 or set of servers 1010 (illustrated in Figure 10) could receive the encrypted module identity 110a and algorithm token 190, and the server 105 could use a secret ciphering algorithm deciphering 162 and the algorithm token 190 to decrypt the encrypted module identity 110a in order to read the plaintext module identity 110. By using different values for the algorithm token 190 with a secret ciphering algorithm ciphering 161, a module 101 can calculate different values for encrypted module identity 110a over time.

Figure 1i

Figure 1i is a graphical illustration of an exemplary system, where a module and a server exchange a set of cryptographic parameters and a subset of the set of cryptographic parameters, in accordance with exemplary embodiments. In exemplary embodiments, a first node can send a set of cryptographic parameters 126 to a second node, and the second node can send a subset of cryptographic parameters 126a to the first node. In an exemplary embodiment, a server 105 can send the set of cryptographic parameters 126 to a module 101, and the module 101 can send the subset of the cryptographic parameters 126a to the server 105. The module can select the subset of cryptographic parameters 126a according to the capabilities of a

Petitioner Samsung Ex-1004, 0054

module program 101i and/or a set of cryptographic parameters 141 recorded in the module 101. In another exemplary embodiment, a module 101 can send the set of cryptographic parameters 126 to a server 105 (or a set of servers 1010 illustrated in Figure 10), and the server 105 can send the subset of the cryptographic parameters 126a to the module 101.

In this manner, using the steps illustrated in Figure 1i, the two nodes can select and agree on a subset of cryptographic parameters 126a for use with a set of cryptographic algorithms 141. The exemplary values for a set of cryptographic parameters 126 are shown in Figure 1i to be illustrative as opposed to limiting, and other values or fields for a set of cryptographic parameters 126 are possible as well without departing from the scope of the present invention. As contemplated herein, a subset of cryptographic parameters 126a can also comprise a set of cryptographic parameters 126. Although not illustrated in Figure 1i, a node receiving a subset of cryptographic parameters 126a could send an acknowledgement upon receipt to signal the subset of cryptographic parameters 126a had been properly received in a valid or acceptable format and also implemented in communication with the other node.

In addition, both the set of cryptographic parameters 126 and the subset of cryptographic parameters 126a can be transmitted in a ciphertext form in order to increase security. In an exemplary embodiment, server 105 can send the set of cryptographic parameters 126 in a server encrypted data 504 (depicted and described in connection with Figure 5a below), and the module 101 can respond with a subset of cryptographic parameters 126a in a module encrypted data 403 (depicted and described in connection with Figure 4 below). The set of cryptographic parameters 126 or 126a could be encrypted with a symmetric key 127, where in an exemplary embodiment the symmetric key 127 could comprise a pre-shared secret key 129a depicted and described in connection with Figure 1d of U.S. Patent Application Serial No. 14/039,401, filed September 27, 2013 in the name of John Nix, which is incorporated by reference in its entirety. Or, the symmetric key 127 for encrypting a set of cryptographic parameters 126 or 126a could comprise a shared secret key 129c as described in Figure 1f and Figure 1h herein.

In exemplary embodiments, module 101 and server 105 could pre-agree to a base set of cryptographic parameters 126 different than the set of cryptographic parameters 126 illustrated in Figure 1i, and the pre-agreed base set of cryptographic parameters 126 could be used with a set of cryptographic algorithms 141 to establish a symmetric key 127 in order to encrypt the set of cryptographic parameters 126 or 126a. In addition, the set of cryptographic parameters 126 or 126a could be ciphered using an asymmetric ciphering algorithm 141a and a public key of the other node, and sent to the receiving node to decrypt using the private key of the receiving node. The algorithms used to cipher a set of cryptographic parameters 126 in an asymmetric ciphering algorithm 141a could be pre-agreed, and a different set of asymmetric ciphering algorithms 141a could be selected after processing the received set of cryptographic parameters 126. Other

Petitioner Samsung Ex-1004, 0055

possibilities for encrypting a set of cryptographic parameters 126 or 126a exist as well without departing from the scope of the present invention. Alternatively, the set of cryptographic parameters 126 and/or 126a could be sent between two nodes as plaintext within an IP packet.

The set of cryptographic parameters 126 can include a list of available options for a set of asymmetric ciphering algorithms 141a, symmetric ciphering algorithms 141b, secure hash algorithms 141c, digital signature algorithms 141d, a key pair generation algorithm 141e, and also general cryptographic parameters 126b. Although not illustrated in Figure 1i, a set of cryptographic parameters 126 could also include parameters for a key derivation function 141f, a shared secret algorithm 141g, and a secret ciphering algorithm 141h. In an exemplary embodiment, the list of available options for a set of asymmetric ciphering algorithms 141a could comprise a list of ECC standard curves 138 and also ECC parameters 137 which could comprise a list of numbers or values for an elliptic curve defining equation. A module 101 and a server 105 could utilize a custom or non-standard elliptic curve defining equation by sending and/or receiving a set of ECC parameters 137 in a set of cryptographic parameters 126. Or, as illustrated in Figure 1i, a node could select an ECC standard curve 138 from a list in a set of cryptographic parameters 126. A set of cryptographic parameters 126 could include a private key length 126e for deriving a module private key 112. A node could take similar steps for selecting an option from a list of available options for other fields as well in a set of cryptographic parameters 126 such as, but not limited to, symmetric ciphering algorithms 141b, secured hash algorithms 141c, etc. as illustrated in Figure 1i, in order to derive a subset of cryptographic parameters 126a.

General parameters 126b can include a list of values that can be utilized in a set of cryptographic algorithms 141. General parameters 126 could specify values for using and/or the format of (i) a security token 410, (ii) an algorithm for processing an encrypted module identity string 110a, (iii) a certificate 122, (iv) a public key identity 111a, (v) the authentication means of a derived public key 111 in a step 517 depicted and described below in connection with Figure 5b, (vi) a padding scheme 126c for the set of cryptographic algorithms 141, and/or (vii) key encoding rules 126d. Key encoding rules 126d can specify the format for sending and receiving a public key, such as the format of a derived module public key 111 sent to a server 105 in a step 516 depicted and described in connection with Figure 5b below. Numerals depicted in Figure 1i with a general parameters 126b include a " ' " so show an association with the fields shown, as opposed to comprising the elements themselves. For example, the value of "security token length: 8 bytes" in a general parameters 126b with a label of "401'" illustrates the value of "security token length: 8 bytes" is associated with a security token 401 as opposed to being an exemplary the value for a security token 401. Likewise, the value of "Public Key Identity: yes" with a label of 111a' illustrates that a general

Petitioner Samsung Ex-1004, 0056

parameters 126b can specify a value for using a public key identity 111a as opposed to a public key identity 111a comprising a value of "Public Key Identity: yes", etc.

Within a general parameters 126b in a set or subset of a cryptographic parameters 126, a field associated with module identity 110, illustrated as "110'", can specify an algorithm to use for ciphering or obfuscating a module identity 110. A general parameters 126b could specify the use of a secret ciphering algorithm ciphering 161 for encrypting a module identity 110. In an exemplary embodiment, the general parameters 126b can specify the method of authentication for a derived module public key 111, where the module 101 could use a step 517 below. Exemplary values in a general parameters 126b for the authentication of a derived module public key 111 include, but are not limited to, message digest with a secret key, ciphering with a symmetric key 127, authenticating with a pre-shared public key, and module 101 sending a module digital signature 405 depicted and described in connection with Figure 4 below. In accordance with preferred exemplary embodiments, a set of cryptographic parameters 126, possibly in a set of general parameters 126b, can include both (i) values for a module 101 to use with a set of cryptographic parameters 141 for deriving a new module public key 111 and new module private key 112, and (ii) steps or values for a module 101 to authenticate the new, derived module public key 111 with a server 105.

The set of cryptographic parameters 126 illustrated in Figure 1i for a module 101 and the subset of cryptographic parameters 126a may be different than conventional technology, since the module 101 can select appropriate parameters or values for deriving its own module public key 111 and module private key 112, as well as changing the parameters or values over time for the generation of subsequent or new module public keys 111 and module private keys 112. Although not illustrated in Figure 1i, general parameters 126b could also include a time value for module 101 to refresh the set of cryptographic parameters 126 with server 105, such as periodically checking for a change in a preferred set of cryptographic parameters 126. In order to minimize bandwidth and also power consumption for a module 101, an exemplary time value for module 101 to check with server 105 for a new set of cryptographic parameters 126 could be an exemplary every 30 days. In another embodiment, server 105 could simply send a new set of cryptographic parameters 126 to module 101 each time new values may applicable.

As contemplated herein, a module 101 may be deployed with a monitored unit 119 for an extended period such as several years or longer, and a module public key 111 with a limited validity date could expire. In this case, after an extended period such as years, a preferred set of cryptographic parameters 126 could change, such as movement to longer private key lengths 126e, or the use of a new set of ECC standard curves 138. In this case, when a new module public key 111 is required, possibly due to the expiration of a prior module public key 111, module 101 could receive a new set of cryptographic parameters 126 and send a subset of the cryptographic parameters 126a before deriving a new module private key 112 and a new

Petitioner Samsung Ex-1004, 0057

module public key 111 using the subset of cryptographic parameters 126a and a set of cryptographic algorithms 141. In exemplary embodiments, a set of cryptographic parameters 126 or subset of cryptographic parameters 126a used by a module 101 can change over time.

A set of cryptographic parameters 126 could specify additional information to the exemplary data shown in Figure 1i. Within a set of general parameters 126b, a name or address of a certificate authority 118 could be included, where module 101 could send a module public key 111 derived using a step 515 depicted and described in connection with Figure 5b. A set of cryptographic parameters 126 could include other names and addresses of servers, such as a first server 105 in a set of servers 1010 where module 101 would first authenticate module identity 110 and obtain a symmetric key 127, and module 101 could then communicate with a second server 105 using the symmetric key 127. A set of cryptographic parameters 126 could specify that the source of new module private key 112 and module public key 111 could be internally derived by module 101, as opposed to module 101 seeking a new module private key 112 from a local source, such as via a local network or a physical interface such as USB interface 101v. In addition, a set of cryptographic parameters 126 could include values for a random number generator 128, such as specifying the use of a seed 128b, or a module seed file 139, or the minimum length of a random number 128a. In addition, a plurality of different shared secret algorithms 141g and secret ciphering algorithms 141h could be used by a module 101 and a server 105, and specific shared secret algorithms 141g and secret ciphering algorithms 141h can be selected in a set of cryptographic parameters 126.

In exemplary embodiments, although not illustrated in Figure 1i, a set of cryptographic parameters 126 or 126a can specify the use of multiple module private keys 112 and module public keys 111 concurrently. In an exemplary embodiment, a module 101 could use a first module private key 111 with asymmetric ciphering algorithms 141a for receiving symmetric keys 127, and a second module private key 111 for deriving or calculating a module digital signature 405 (in Figure 4 below). Further, a module 101 could communicate with a plurality of servers 105, where a first server 105 could use a first set of cryptographic parameters 126 and a second server could use a second and different set of cryptographic parameters 126. In order to maintain compatibility with the different servers 105, a module 101 could use (i) a first module private key 112 and first module public key 111 that was derived using the first set of cryptographic parameters 126 for communicating with the first server 105, and (ii) a second module private key 112 and second module public key 111 that was derived using the second set of cryptographic parameters 126 for communicating with the second server 105. In order to keep track of potentially multiple sets of cryptographic parameters 126 and/or subsets of cryptographic parameters 126a, a module 101 and/or a server 105 could implement a set of cryptographic parameters token 126c. The token 126c, illustrated as an exemplary "Set A" in Figure 1i, can be a value to represent a collection of cryptographic parameters 126,

Petitioner Samsung Ex-1004, 0058

and subsequently either module 101 or server 105 could refer to the set of cryptographic parameters 126 using the set of cryptographic parameters token 126c instead of communicating the full set of cryptographic parameters 126.

As contemplated herein, a set of cryptographic parameters 126 could also include values for a module 101 to authenticate or communicate with one or multiple wireless networks 102. In an embodiment, a wireless network 102 could require a specific symmetric ciphering algorithm 141b, and also a specific key derivation function 141f for generating derived shared keys 129b, and the specific values needed for module 101 to communicate with a wireless network 102 could be sent in a set of cryptographic parameters 126. Other possibilities exist as well to those of ordinary skill in the art without departing from the scope of the present invention.

Figure 1j

Figure 1j is an illustration of a certificate that includes a PKI public key, where the key comprises an elliptic curve cryptography key, in accordance with exemplary embodiments. Public and private keys in system 100 and other systems contemplated herein can utilize PKI techniques other than RSA, such as the elliptic curve cryptography (ECC) public key 111 illustrated in Figure 1h. One benefit of using ECC is that an equivalent level of security can be obtained for a much smaller key length. Also, energy may be conserved using ECC algorithms 154 compared to RSA algorithms 153. An analysis of the energy conserved for ciphering, deciphering, signing, and verifying messages using ECC versus RSA is included in the paper titled "Energy Analysis of Public-Key Cryptography on Small Wireless Devices" by Wander et al (herein incorporated by reference). Smaller key lengths save bandwidth, memory, processing resources, and power, which are all valuable for a module 101 to conserve a battery 101k and usage of radio-frequency spectrum. For example, an ECC key length of 283 bits provides security similar to an RSA key length of approximately 2048 bits. Module public key 111 can comprise an ECC key in an X.509 certificate, as illustrated in Figure 1g.

Certificate 122 could include a signature 123, where signature 123 can be signed using ECC signature techniques, such as the Elliptic Curve Digital Signature Algorithm (ECDSA) 158 with a secure hash such as SHA256 156. A signature 123 in a certificate 122 containing an elliptic public key 111 could also be signed using a DSA algorithm 167. In order to generate signature 123, the private key associated with either CA 118 or module provider 109 may also be an ECC-based private key (for ECDSA 158). Note that the public key 111 in a certificate 122 could use a different asymmetric ciphering algorithm 141a than the algorithm used for signing, such that the public key 111 can be an ECC key, while the signature 123 could be generated with RSA algorithm 153 and/or key. Certificate 122 may also include a subset of

Petitioner Samsung Ex-1004, 0059

cryptographic parameters 126a (or "parameters 126a"), where parameters 126a can specify an elliptic curve utilized with the module public key 111. Parameters 126a could also include the start and end times for the validity of either public key 111 or certificate 122. Other parameters 126a can be utilized in a certificate 122 as well, including parameters 126a recording a modulus for an RSA algorithm 153.

Certificate 122 illustrated in Figure 1g also illustrates an exemplary embodiment of the present invention. Over the lifetime of a module 101, which could be a decade or longer, multiple module public keys 111 may be utilized. Exemplary reasons for the potential use of multiple different module public keys 111 include (i) the expiration of a certificate 122 (including expiration of a public key associated with a certificate authority 118 used in signature 123), (ii) a need to change an elliptic curve specified in a parameters 126, (iii) adding a new public/private key pair for connection with a different wireless network 102, (iv) as increasing a key length utilized in a public/private key pair, (v) the transfer of ownership or control of module 101, and/or (vi) module 101 connecting to a new server 105 that utilizes a different asymmetric ciphering algorithm (i.e. RSA instead of ECC). Other possibilities exist as well for reasons a module to derive a new module public key 111. Note that the multiple module public keys 111 may also be utilized concurrently, such that (i) a first module public key 111 in a first certificate 102 can be utilized with a first server 105, and (ii) a second module public key 111 (possibly derived using a different set of parameters 126 including using a different elliptic curve or asymmetric ciphering algorithm) can be utilized with a second server 105 and/or wireless network 102.

In either case of (i) module 101 using multiple module public keys 111 concurrently, or (ii) module 101 using different module public keys 111 in sequence, a certificate 122 can preferably include a module public key identity 111a to specify the module public key 111 utilized in a certificate 122. As illustrated in Figure 1j, the module public key identity 111a could be included in the CN field, and the module identity 110 can be included in the OU field. Alternatively, the module public key identity 111a and module identity 110 can be appended together and used in the CN field. In this manner and according to preferred exemplary embodiments, a module public key identity 111a is utilized with both a module identity 110 and a module public key 111 within a certificate 122. Also, as noted previously herein, the use of a certificate 122 may optionally be omitted, such that module 101 and server 105 share public keys without using certificates 122, or a server 105 could use a certificate 122 and module 101 may omit a certificate 122 and other possibilities exist as well.

Figure 1k

Figure 1k is a graphical illustration of hardware, firmware, and software components for a server, in accordance with exemplary embodiments. The illustrated components for the server 105 in Figure 1k

Petitioner Samsung Ex-1004, 0060

include a central processing unit (CPU) 105b, a random access memory (RAM) 105e, a system bus 105d, storage 105m, an operating system 105h, and a module controller 105x. These elements can provide functions equivalent to the central processing unit (CPU) 101b, RAM 101e, system bus 101d, flash memory 101w, and an operating system 101h described above in Figure 1b, respectively. In general, a server 105 can have higher-end components such as, but not limited to, a larger CPU 105b and greater RAM 105e in order to support communications with a plurality of modules 101. Server 105 can comprise a general purpose computer such as, but not limited to, a rack mounted server within a data center or rack, or could also comprise a desktop computer or laptop. Server 105 could also be a specialized computer, with hardware and software selected for supporting a plurality of modules 101 connecting and communicating simultaneously. Operating system 101h can comprise an operating system appropriate for a server such as, but not limited to, Linux, Solaris®, or Windows® Server. Server 105 can preferably include at least one wired Ethernet connection with high bandwidth that is persistently connected to the IP Network 107, while the IP Network 107 connection for module 101 may be transient as module 101 changes between sleep and active states. Module controller 105x can provide the server-side logic for managing communications and controlling module 101 using a module database 105k. Network controller 105i can provide functionality for communicating with external servers or nodes, such as, but not limited to, a wireless network 102 illustrated in Figure 1a.

A module controller 105x and network controller 105i may be applications programmed in a language such as, but not limited to, C, C++, Java, or Python and could provide functionality to support authentication and communication with modules 101, including M2M applications such as, but not limited to, remote monitoring of sensors and remote activation of actuators. Module controller 105x and network controller 105i could also be software routines, subroutines, linked libraries, or software modules, according to preferred embodiments. Many of the logical steps for operation of server 105, module controller 105x, and/or network controller 105i can be performed in software and hardware by various combinations of physical interface 105a, system bus 105d, device driver 105g, and operating system 105h. A module controller 105x and network controller 105i can also access a set of cryptographic algorithms 141 (in Figure 1d above) in order (i) to encrypt and decrypt data, and also (ii) process or generate a digital signature and verify received digital signatures, including message digest authentication. When server 105 is described herein as performing various actions such as, but not limited to, acquiring an IP address, monitoring a port, transmitting or sending a packet, receiving a message, or encrypting or signing a message, specifying herein that server 105 performs an action can refer to software, hardware, and/or firmware operating within server 105 performing the action. As contemplated herein, when a server 105 is described as performing an action such as, but not limited to, sending a response, receiving a message, verifying a digital signature, decrypting

Petitioner Samsung Ex-1004, 0061

data, etc., in some embodiments a set of servers 1010 (illustrated in Figure 10) can perform the actions for the server 105. In this case, a server 105 could be a member of the set of servers 1010.

The server 105 may store computer executable instructions such as, but not limited to, module controller 105x or network controller 105i on storage 105m. Storage 105m may comprise a disk drive, a solid-state drive, an optical drive, or a disk array. Module controller 105x (i) can manage communications with module 101 or a plurality of modules 101 and (ii) may be downloaded and installed on the server 105. As noted previously and elsewhere herein, module program 101i and module controller 105x can preferably interoperate with each other in order to collect sensor data and control an actuator associated with a monitored unit 119.

The network controller 105i and/or module controller 105x operating within server 105 illustrated in Figure 1k can provide computer executable instructions to hardware such as CPU 105b through a system bus 105d in order to (i) receive a message from the module 101 and (ii) send a response, wherein the message can include sensor 101f data and the response can include an acknowledgement of the message and/or an instruction to the module 101. The module controller 105x can enable the server 105 to send a response to a message from module 101 by recording data associated with module 101 in memory such as RAM 105e, where the data can include an instruction from module 101, a destination IP:port number, a packet or packet header value, and the data can be processed using an encryption or ciphering algorithm or key, a digital signature algorithm or key, etc. The operating system 105h or the device driver 105g can write the data from RAM 105e to a physical interface 105a using a system bus 105d and an Ethernet connection in order to send the data via the IP Network 107 illustrated in Figure 1a. Alternatively, the software program 105i and/or module controller 105x can write the data directly to the physical interface 105a using the system bus 105d.

The server 105 can utilize the physical interface 105a to receive data from a module 101 and/or wireless network 102 using a local area network such as Ethernet, although the physical interface 105a of server 105 could also utilize a wireless connection. The server 105 can listen or monitor for data from the IP Network 107 using port number and/or a TCP/UDP socket. The received data from a module 101 can be a message formatted according to an Internet packet or datagram or series of datagrams inside Ethernet packets and include information from a module 101 such as, but not limited to, a source IP address and port number, an identity of the module, sensor data that may be encrypted, and/or a digital signature of the module. The received data from wireless network 102 can comprise a series of datagrams formatted according to Internet Protocol and/or datagrams inside Ethernet packets. The received data or message from wireless network 102 can include information regarding wireless network 102 and/or server 105, such as a source IP address and port number associated with wireless network 102, an identity of the server, actuator instructions or

Petitioner Samsung Ex-1004, 0062

commands for a module 101 that may be encrypted, and a digital signature associated with the wireless network 102.

When server 105 receives messages or data, the operating system 105h or device driver 105g can record the received data from module 101 or wireless network 102 via physical interface 105a into memory such as RAM 105e. The network controller 105i or operating system 105h may subsequently access the memory in order to process the data received. The network controller 105i and/or module controller 105x, or operating system 105h can include steps to process the data recorded in memory and received from the module 101 or wireless network 102, such as, but not limited to, parsing the received packet, decrypting data, verifying a digital signature with a key, or decoding sensor data included in a message from the module.

The server 105 and/or network controller 105i may communicate with wireless network 102 by sending and receiving packets over a LAN or the IP Network 107, using a physical interface 105a and a wired connection such as Ethernet or possibly a wireless connection as well. The server 105 can use the physical interface 105a such as an Ethernet connection to send and receive the data from the IP Network 107. For those skilled in the art, other steps are possible as well for an network controller 105i or operating system 105h within a server 105 to (i) send/receive a packet or message to/from a module 101 and (ii) send/receive a packet or message to/from an wireless network 102 without departing from the scope of the present invention. Network controller 105i and module controller 105x may optionally be combined within a server 105, or alternatively distributed across different physical computers and function in a coordinated manner using a network.

The device drivers 105g, operating systems 105h, and/or module controller 105x could also optionally be combined into an integrated system for providing the server 105 functionality. Although a single physical interface 105a, device-driver set 105g, operating system 105h, module controller 105x, and network controller 105i are illustrated in Figure 1k for server 105, server 105 may contain multiple physical interfaces, device drivers, operating systems, software programs, module programs, and/or user interfaces. Server 105 may operate in a distributed environment, such that multiple computers operate in conjunction through a network to provide the functionality of server 105. Also, server 105 may operate in a "virtualized" environment, where server 105 shares physical resources such as a physical CPU 105b with other processes operating on the same computer. And other arrangements could be used as well, without departing from the invention.

Petitioner Samsung Ex-1004, 0063

Figure 1m

Figure 1m is a graphical illustration of components within a server, in accordance with exemplary embodiments. Server 105 can include a module database 105k, a sub-server 105w, and a message preprocessor 105y. Server 105 can also include one or many sets of cryptographic parameters 126, a secret ciphering algorithm ciphering 161, and a secret ciphering algorithm deciphering 162. In an exemplary embodiment, the elements illustrated within a server 105 in Figure 1m may be stored in volatile memory such as RAM 105e, and/or storage 105m, and may also be accessible to a processor CPU 105b via a system bus 105d. In another exemplary embodiment, the module database 105k, sub-server 105w, and message processor 105y can comprise separate computers. Module database 105k, sub-server 105w, and message preprocessor 105y could represent either different processes or threads operating on a server 105, or physically separate computers operating in conjunction over a network to perform the functions of a server 105. Since server 105 can preferably support communications with a plurality of modules 101, server 105 can utilize module database 105k to store and query data regarding a plurality of modules 101, monitored units 119, and the overall M2M service. The server 105 can store a plurality of module public keys 111 associated with each of a plurality of devices in the module database 105k. The server 105 can also store a plurality of shared secret network keys K 129d associated with each of a plurality of modules, where secret shared network key K 129d is also depicted and described in connection with Figures 9b and 11. The server 105 can use a module identity 110, possibly in the form of a network module identity 110b, for a module 101, received in a message to query the module database 105k and select the public key 111, secret shared network key K 129d, a symmetric key 127, and other data associated with the module 101.

Although not illustrated in Figure 1m, module database 105k can also record a pre-shared secret key code 134, a set of cryptographic parameters 126 or 126a, and a module identity 110 for each module 101, along with the pre-shared secret key 129a shown in Figure 1m. In embodiments where server 105 functions as a home subscriber server (HSS), module database 105 could record authentication triplets of a RAND 912, an RES 913 (both described in Figure 9b below), and also a network authentication token. Examples of module database 105k could include MySQL, Oracle®, SQLite, hash tables, distributed hash tables, text files, etc. Module database 105k could reside within RAM 105e or storage 105m. Server 105 may also record a symmetric key 127, where the symmetric key 127 can be associated with an expiration time 133. Symmetric key 127 can also be recorded in a module database 105k or a sub-server 105w.

Message preprocessor 105y can process incoming packets and route them to an appropriate sub-server 105w using information contained in an incoming message, such as, but not limited to, a module identity 110 or 110b, a server identity 206 illustrated in Figure 2 below, and/or a destination IP address. Sub-

Petitioner Samsung Ex-1004, 0064

server 105w can include a server private key 105c and cryptographic algorithms 141. A plurality of sub-servers 105w can be utilized by a server 105 in order to support communication with a plurality of modules 101. The server private key 105c and module public key 111 can be utilized by module 101 to secure communication with server 105, including the steps depicted and described in connection with Figures 4 and Figure 5a below. Cryptographic algorithms 141 may comprise a suite of algorithms or subroutines and are depicted and described in connection with Figure 1d.

Server 105 may also comprise a collection of individual computers, where the individual computers could be either centrally located or geographically dispersed, but the individual computers may function in a coordinated manner over a network to operate as a server 105. Server 105 may be a "virtualized" server, with computing resources shared with other processes operating on a computer. A server 105 as illustrated in Figure 1k and Figure 1m may also be operated by a wireless network 102. Wireless network 102 could belong to or be associated with a mobile network operator 108. The mobile network operator (MNO) could control and/or own a public land mobile network (PLMN), and exemplary large MNOs in the United States in 2013 include AT&T® and Verizon®. The wireless network 102 as illustrated in Figure 1a could comprise the radio access portion of a mobile network operator's network, and a server 105 as illustrated in Figure 1k and Figure 1m could reside within the network potion for a mobile network operator. In the embodiments where server 105 is located on a mobile network operator's 108 network, the firewall 104 could optionally be omitted, such that a server 105 can directly communicate with module 101 when module 101 is attached or connected to, or attempts to attach or connect to wireless network 102. Other possibilities exist as well for a server 105 to reside within a mobile network operator's 108 network without departing from the scope of the present invention.

Figure 2

Figure 2 is a graphical illustration of an exemplary system, where a module sends a message to a server, and where the module receives a response to the message, in accordance with exemplary embodiments. Module 101 as depicted and described in Figure 2 can operate as a wireless module 101, although a wired connection to the IP Network 107 could alternatively be utilized. System 100 as illustrated in Figure 2 includes RF signals 201, module IP address 202, port number 203, module IP:port 204, server port number 205, server ID 206, server IP:port number 207, message 208, response 209, wireless network firewall address 210, and firewall port binding packet 211. Many of the elements illustrated within system 100 in Figure 2 are also depicted and described in connection with Figure 2 of U.S. patent application Ser. No. 14/039,401 (the contents of which are hereby incorporated by reference in their entirety). As

Petitioner Samsung Ex-1004, 0065

contemplated herein, a wireless module 101 can comprise a module 101, or in other words a wireless module 101 may be a module 101 that is wireless. Functions described as being performed by a wireless module 101 may also be performed by a wired module 101 (where connection to a wired network would be used instead of connection to a wireless network 102). Also as contemplated herein and illustrated in Figure 2, the wording "module 101 sends a message 208" can also be considered equivalent to "server 105 receives a message 208". Likewise, the wording "server 105 sends a response 209" can be considered equivalent to "module 101 receives a response 209".

A wireless module 101 can wake from a dormant state in order perform (i) remote and automated monitoring and (ii) control functions such as, but not limited to, collecting a sensor 101f measurement, communicating with server 105, and controlling an actuator 101y. If module 101 is connected to land-line power or a long-lasting external power source such solar power, then module 101 may remain in an active state and bypass a dormant state, although transmitting RF signals 201 may preferably only be utilized when communicating with wireless network 102 or sending data to and receiving data from wireless network 102 and/or mobile network operator 108. The wireless module 101 can acquire an IP address 202 from the wireless network 102. IP address 202 is illustrated as being an IPv6 address, but IP address 202 could also be an IPv4 address.

In order to transmit or send data from wireless module 101 to server 105, a wireless module 101 can use module program 101i to collect data from a sensor 101f in order to update server 105. Module program 101i can request a port number 203 from operating system 101h in order to have a source IP:port for sending data using IP protocols such as, but not limited to, TCP and UDP. The terminology "IP:port" as described herein refers to combining an IP address with a port number. Wireless module IP address 202 and port number 203 can be combined to form IP:port number 204. IP:port number 204 can be utilized as a source IP:port number for packets transmitted from wireless module 101, as well as a destination IP:port number for packets received by wireless module 101, when communicating with server 105.

In order to utilize IP Network 107, module 101 may also need a destination IP address and port number in order to send packets to server 105. Before sending data to server 105, wireless module 101 preferably retrieves server IP address 106 and server port number 205 from RAM 101e. Server IP address 106 could be recorded in RAM 101e via (i) a DNS query using server name 206 or (ii) queries to mobile network operator 108 or wireless network 102. CPU 101b may copy server IP address 106 and server port number 205 from nonvolatile memory into volatile memory such as, but not limited to, a register for processing to send a packet to server 105. Server name 206 could also be a server identity. (A) Server IP address 106 or server name 206 and (B) server port number 205 could be recorded in a nonvolatile memory such as, but not limited to, flash memory 101w and/or an eUICC 163 so that wireless module 101 can store

Petitioner Samsung Ex-1004, 0066

the proper destination of packets transmitted or sent even when wireless module is dormant or shutdown. Server IP address 106 and server port number 205 can be combined into a server IP:port number 207.

After collecting data from a sensor, module 101 can send a packet from IP:port 204 to IP:port 207, and the packet could comprise a message 208 that may include the data from a sensor 101f. Note that message 208 does not need to include sensor data, and message could potentially be a periodic registration message or keep-alive message. As contemplated herein, the term "sensor measurement" can refer to data associated with or derived from a sensor 101f. A sensor measurement, can comprise a string containing data regarding a parameter of a monitored unit 119 and collected by a sensor 101f. The sensor measurement as sent in a message 208 can also represent a string (alphanumeric, binary, text, hexadecimal, etc.), where the string comprises a transformation or processing of sensor data collected by a CPU 101b, such including formatting, compressing, or encrypting, encoding, etc. of sensor data. A "sensor measurement" could comprise a plurality of data from a sensor 101f.

In order to minimize bandwidth and time required for RF signals 201 to be active, module 101 can send the message 208 as a single UDP datagram in accordance with a preferred exemplary embodiment. The single UDP datagram in this embodiment can preferably be the only packet sent from module 101 to server 105 or mobile network operator 108 during a wake state for the module 101 when the radio 101z is active and transmitting, such as, but not limited to, in a radio resource control (RRC) connected state. In other words, according to this preferred exemplary embodiment, the message 208 sent by module 101 can preferably be the only message or packet sent by the wireless module to the server 105 between dormant periods of module 101. By sending message 208 as a single UDP datagram, both a battery 101k is conserved and utilization of valuable RF spectrum is reduced. Message 208 could also comprise a series of associated UDP messages.

Also, as contemplated herein, message 208 could comprise a related series of packets, so that message 208 could comprise multiple datagrams. As one example, if TCP is utilized as the transport protocol for message 208, then the series of TCP messages including the initial handshake, one or more packets of payload data, and the closing of the connection could together comprise message 208. As another example, if UDP or UDP Lite is utilized for the transport protocol, and payload data exceeds a maximum transmission unit (MTU) size for the UDP packet and the payload data is spread across multiple packets, then the multiple packets would comprise a message 208. Further, a related series of packets comprising a message 208 could be identified by using the same source IP:port number as either (i) received by server 105 or (ii) sent by module 101. In addition, a related series of packets comprising a first message 208 could be identified as a series of packets sent by module 101 before receiving a response 209 from a server, and packets sent after receiving a response 209 could comprise a second message 208. Other possibilities for a

Petitioner Samsung Ex-1004, 0067

message 208 to comprise multiple packets or datagrams may exist without departing from the scope of the present invention.

The UDP datagram for message 208 could also be formatted according to the UDP Lite protocol, as specified in IETF RFC 3828, which is also incorporated by reference herein. The term "UDP Lite" described in the present invention may also refer to any connectionless protocol widely supported on IP Network 107 where checksums may be partially disabled, thereby supporting the transfer of bit errors within a datagram. The advantages of UDP over TCP is that UDP can be quickly sent, while TCP requires a "handshake" with the server which requires more time and bandwidth, which would utilize more energy from battery 101k. According to an exemplary embodiment, both message 208 and response 209 can be TCP messages. In this exemplary embodiment, message 208 and response 209 could each comprise a series of TCP messages that can include a TCP SYN, SYN ACK, ACK, ACK w/ data, FIN ACK, etc.

According to an exemplary embodiment, module 101 sends (and server 105 receives) the same sensor data in multiple copies of the same UDP packet. Each of the multiple copies of the same UDP packet can also optionally be formatted according to the UDP Lite protocol. As one example, wireless module sends three identical copies of the UDP or UDP Lite packet that include the same sensor data. The benefit of sending three copies of UDP Lite include (i) the RF signals 201 received by the base station 103 could include bit errors, which could result in a regular (RFC 768) UDP packet being dropped, since a bit error could result in a UDP checksum mismatch, as received and processed by wireless network 102. Note that the use of checksums is mandatory in IPv6, and thus checksums cannot be fully disabled in IPv6. With UDP Lite packets transmitted by wireless module 101, where the mandatory checksum for IPv6 can cover the packet header, wireless network 102 can forward all packets received, potentially including bit errors, to server 105 over the IP Network 107.

Server 105 can receive the multiple copies of the UDP or UDP Lite packets, which could include bit errors received, and server 105 could compare or combine the multiple copies or each individual UDP Lite packet in order to remove bit errors. Note that UDP Lite is not required, and wireless module 101 could send the message 208 using a single UDP packet, or multiple copies of a regular UDP (i.e. non UDP Lite) packet. However, using UDP Lite with multiple packets sent can provide benefits such as if the sensor data is encrypted in the packet, then a single bit error would normally break the receiver's ability to decipher the data using a cryptographic key, unless the encrypted data was channel coded and the channel coding could recover from the bit error in order to present an error-free input of the encrypted data to a deciphering algorithm.

Further, between periods of sleep when a wireless module 101 becomes active and transmits RF signals 201, module 101, which may also comprise a wireless module 101, could send the sensor data in a

Petitioner Samsung Ex-1004, 0068

single UDP Lite packet where the packet includes channel coding, which can also be referred to forward error correction. Forward error correction could also be implemented by sending multiple copies of the same UDP packet. Note that since large segments of message 208 could include encrypted or hashed data, those segments may not be appropriate for compression since the data is often similar to random strings which are not readily compressed. Channel coding techniques for the data in message 208 could include block codes and convolution codes. Block codes could include Reed-Solomon, Golay, BCH, Hamming, and turbo codes. According to a preferred exemplary embodiment, data within message 208 is sent as a UDP Lite packet using a turbo code to correct multiple bit errors within a packet or datagram sent by module 101 and received by server 105.

In system 100 illustrated in Figure 2, server 105 can use IP:port 207 to receive the packet from wireless module 101 and sent from source IP:port 204 to IP:port 207, and the packet could comprise a message 208 that may include the data from a sensor associated with module 101 or monitored unit 119. As contemplated herein, a message 208 illustrated in Figure 2 does not need to include sensor data and other data could be transmitted or sent, such as, but not limited to, a server instruction 414 (described in Figure 4 below), or other data pertaining to module 101 or a monitored unit 119. Note that server 105 can use IP:port 207 to receive a plurality of messages 208 from a plurality of wireless modules 101. Server 105 preferably listens for UDP packets on IP:port 207 or monitors IP:port 207, although TCP packets could be supported as well. If server 105 receives multiple copies of the same UDP packet from module 101, server 105 preferably includes a timer to drop duplicate packets received outside a timer window such as, but not limited to, an exemplary 5 seconds.

After receiving the message 208 and processing the message according to the techniques described below such as, but not limited to, in Figure 4, server 105 can send a response 209. Since module 101 may belong to a wireless network 102 which includes a firewall 104, the source IP:port of the message 208 received by server 105 could be different from the source IP:port 204 utilized by wireless module 101. The source IP:port in message 208 could be changed if firewall 104 performs network address translation (NAT), as one example. Server 105 may not readily know if a NAT translation has been performed on the message 208. Alternatively, firewall 104 may not perform NAT, but could still block data from the IP Network 107 which does not properly match the firewall rules. As one example, firewall 104 could be a symmetric firewall (but without NAT functionality), where only packets from IP:port 207 to IP:port 204 are allowed to pass the firewall after message 208 has been sent by module 101.

In either case, where firewall 104 may or may not perform NAT routing, server 105 preferably sends the response 209 from the server IP:port 207 to the source IP:port it receives in message 208. According to a preferred exemplary embodiment, response 209 is a UDP packet sent from server 105 with (i) a source

Petitioner Samsung Ex-1004, 0069

IP:port 207 and (ii) a destination IP:port equal to the source IP:port received in message 208, as illustrated in packet 209a. The example use of source and destination IP:ports in message 208 and response 209 are also illustrated in Figure 6a below. In this manner, the UDP packet can traverse a firewall 104, if firewall 104 is present. If firewall 104 is present and performs NAT routing, then firewall 104 can receive the response 209 and change the destination IP address and port within response 209 to equal IP:port 204.

According to exemplary preferred embodiments, module 101 may also obtain power from a land-line source, such as, but not limited to, a traditional 120 volt wall socket, or possibly power over Ethernet, and other non-transient power sources could be utilized as well. In this case, module 101 may remain persistently connected to the Internet through either a wireless network 102 or a wired connection such as, but not limited to, Ethernet. In other words, module 101 may omit entering periods of sleep or dormancy where inbound packets from the Internet would not be received due to the sleep state of module 101. Consequently in an exemplary embodiment, module 101, which does not sleep for periods longer than a minute, may preferably periodically send a firewall port binding packet 211 from IP:port 204 to IP:port 207 in order to keep ports and addresses within a firewall 104 and/or firewall 124 open to communications between module 101 and server 105. Firewall port binding packet 211 can comprise a packet that is sent periodically using a timer interval that is shorter than the port-binding timeout period 117 on a firewall 104 and firewall 124.

Continuing with this exemplary embodiment where module 101 does not sleep for periods longer than approximately one minute, if UDP is utilized for message 208 and response 209, then a small UDP packet comprising firewall port binding packet 211 can be sent periodically such as, but not limited to, every 45 seconds. If TCP is utilized for message 208 and response 209, then a small TCP packet comprising firewall port binding packet 211 can be sent periodically such as, but not limited to, every 4 minutes. Other possibilities for the timing of sending firewall port binding packet 211 are possible as well. By sending firewall port binding packet 211 periodically, server 105 can send module 101 a response 209, (i) which could include a module instruction 502 as explained in Figure 5a, at (ii) time intervals between message 208 and response 209 that are longer than the firewall port binding timeout values 117 of firewall 104 and/or firewall 124. Without firewall port binding packet 211, if (A) a response 209 sent from server 105 at an exemplary 180 seconds after receiving message 208, such as, but not limited to, after a firewall port binding timeout value 117 of firewall 104 of an exemplary 60 seconds transpired, then (B) response 209 would be dropped by firewall 104 and the response 209 would not be received by module 101.

Petitioner Samsung Ex-1004, 0070

Figure 3a

Figure 3a is a flow chart illustrating exemplary steps for a module to send sensor data to a server, in accordance with exemplary embodiments. As illustrated in Figure 3a, Figure 3a may include the data reporting steps 101x used by a module 101 in a module program 101i, where data reporting steps 101x and a module program 101i are depicted and described in connection with Figure 1b above. The processes and operations, including data reporting steps 101x, described below with respect to all of the logic flow diagrams may include the manipulation of signals by a processor and the maintenance of these signals within data structures resident in one or more memory storage devices. For the purposes of this discussion, a process can be generally conceived to be a sequence of computer-executed steps leading to a desired result.

These steps usually require physical manipulations of physical quantities. Usually, though not necessarily, these quantities take the form of electrical, magnetic, or optical signals capable of being stored, transferred, combined, compared, or otherwise manipulated. It is convention for those skilled in the art to refer to representations of these signals as bits, bytes, words, information, elements, symbols, characters, numbers, points, data, entries, objects, images, files, or the like. It should be kept in mind, however, that these and similar terms are associated with appropriate physical quantities for computer operations, and that these terms are merely conventional labels applied to physical quantities that exist within and during operation of the computer.

It should also be understood that manipulations within the computer are often referred to in terms such as listing, creating, adding, calculating, comparing, moving, receiving, determining, configuring, identifying, populating, loading, performing, executing, storing etc. that are often associated with manual operations performed by a human operator. The operations described herein can be machine operations performed in conjunction with various input provided by a human operator or user that interacts with the computer.

In addition, it should be understood that the programs, processes, methods, etc. described herein are not related or limited to any particular computer or apparatus. Rather, various types of general purpose machines may be used with the following process in accordance with the teachings described herein.

The present invention may comprise a computer program or hardware or a combination thereof which embodies the functions described herein and illustrated in the appended flow charts. However, it should be apparent that there could be many different ways of implementing the invention in computer programming or hardware design, and the invention should not be construed as limited to any one set of computer program instructions.

Further, a skilled programmer would be able to write such a computer program or identify the appropriate hardware circuits to implement the disclosed invention without difficulty based on the flow

Petitioner Samsung Ex-1004, 0071

charts and associated description in the application text, for example. Therefore, disclosure of a particular set of program code instructions or detailed hardware devices is not considered necessary for an adequate understanding of how to make and use the invention. The inventive functionality of the claimed computer implemented processes will be explained in more detail in the following description in conjunction with the remaining Figures illustrating other process flows.

Further, certain steps in the processes or process flow described in all of the logic flow diagrams below must naturally precede others for the present invention to function as described. However, the present invention is not limited to the order of the steps described if such order or sequence does not alter the functionality of the present invention. That is, it is recognized that some steps may be performed before, after, or in parallel other steps without departing from the scope and spirit of the present invention.

The processes, operations, and steps performed by the hardware and software described in this document usually include the manipulation of signals by a CPU or remote server and the maintenance of these signals within data structures resident in one or more of the local or remote memory storage devices. Such data structures impose a physical organization upon the collection of data stored within a memory storage device and represent specific electrical or magnetic elements. These symbolic representations are the means used by those skilled in the art of computer programming and computer construction to most effectively convey teachings and discoveries to others skilled in the art.

At step 301, before final distribution of the module to a sales channel, equipment distributors, or end users, a module private key 112 and module identity 110 could be recorded in non-volatile memory 101w of the module 101. The module private key 112 could be a private key formatted according to the X.500 series of standards published by the International Organization for Standardization (ISO) in ISO/IEC 9594 or similar and subsequent standards, or alternatively according to another format including a propriety format. The module private key 112 could be formatted using RSA encryption algorithms or ECC encryption algorithms, and other possibilities exist as well for the format of encryption and/or decryption keys without departing from the scope of the present invention. Note that step 301 contemplates an alternative to the case where a module 101 derives its own public and private keys using key pair generation algorithms 141e. Thus, the present invention also contemplates that a module private key 112 is derived outside module 101 and loaded into nonvolatile memory 101w. Note that in this case, where module private key 112 is loaded from an external source to module 101, that module 101 could still utilize other features contemplated herein, such as if module 101 needed to derive public and private keys in the future after the initial step 301.

Module identity 110 can be a unique identifier associated with module 101, and can represent a number or a string. The module private key 112 and module identity 110 could be recorded in non-volatile memory 101w by the manufacturer, or a service provider. Alternatively, the module private key 112 and

Petitioner Samsung Ex-1004, 0072

module identity 110 could be recorded in non-volatile memory 101c by the end users. At step 302, the module is distributed and installed in physical proximity to a monitored unit 119. Although step 301 is illustrated as occurring before step 302 according to an exemplary embodiment, step 301 can take place after step 302 or concurrently with step 302, and other possibilities exist as well without departing from the scope of the present invention.

After installation of the module 101, module 101 can wake from a dormant state in step 303. The dormant state can comprise a state of low power usage as described in Figure 1c, in order to conserve battery life and wired bandwidth or wireless spectrum resources. As noted in Figure 1c, module 101 can utilize a bootloader program 125 in order to initiate operations from a sleep or dormant state. At step 303, the module private key 112, module identity 110, server identity 206, and/or server address 106 could be moved from non-volatile memory 101w into RAM 101e. At step 304, the module 101 can read the module private key 112 and module identity 110 recorded in RAM 101e, and also record the server public key 114 and server IP:port 207. The server public key 114 and server IP:port 207 could also be either locally stored previous to step 304 in a non-volatile memory 101w, or obtained through the IP Network 107 via a query to mobile network operator 108. As one example, module 101 could obtain the server public key 114 by establishing an Internet connection through a network such as a wireless network 102 and downloading the server public key 114 from server 105.

If module 101 utilizes a sleep or dormant state (according to exemplary sleep or dormant states depicted and described in connection with Figure 1c of U.S. Patent Application Serial No. 14/023,181, which is herein incorporated by reference) in order to conserve power consumption or energy utilization, then according to a preferred exemplary embodiment at step 304, after waking, module 101 can preferably read from nonvolatile such as a flash memory 101w each of (i) module private key 112, (ii) module identity 110, (iii) the server public key 114, (iv) server IP:port 207, and (v) data reporting steps 101x. The location of server 105 could be obtained via a DNS query using the server identity 206. Although not illustrated in Figure 3a, server identity 206 and server IP:port 207 could also be recorded in non-volatile memory at step 301. Other means are possible as well for module 101 to obtain server public key 114 and server IP:port 207.

At step 305, the module 101 can read data from a sensor 101f. The data can comprise information regarding a monitored unit 119, as illustrated in Figure 1a. As referenced herein, the data collected at step 305 may comprise a sensor measurement 305 or sensor data 305. At step 306, the module can utilize cryptographic algorithms 141 to (i) encrypt the data from sensor 101f using the server public key 114 and (ii) sign the encrypted data using the module private key 112. Note that a symmetric ciphering algorithm 141b may be used at step 306, but since the symmetric key 127 may be derived using the server public key 114,

Petitioner Samsung Ex-1004, 0073

the sensor data 305 can be encrypted using the server public key (indirectly) at step 306. According to a preferred exemplary embodiment, the module can add channel coding to the data resulting from the steps taken in the previous sentence, although the channel coding can optionally be omitted. A more detailed description of the steps for encrypting and signing data from the sensor are included in Figure 4a below.

After encrypting and signing sensor data, the module can send the data to the server 105 in message 208, where message 208 is formatted and sent according to a either a TCP or UDP packet. An exemplary format of message 208 is also depicted and described in connection with Figure 6 below. Message 208 could be sent using the UDP Lite protocol, although the message could also be sent in a TCP datagram, after completing the initial TCP "handshakes" with server 105. Message 208 in the form of a UDP or TCP datagram can be sent from the module IP:port 204 to the server IP:port 207. Message 208 can also comprise sending the sensor data in multiple datagrams, including two or more copies of the same data. Although not illustrated in Figure 3a, upon the first communication with a server 105, according to an exemplary embodiment, module 101 can send a certificate 122 to server 105, where certificate 122 would normally include module public key 111. Server 105 could utilize a certificate 122 to verify a module identity 110.

As illustrated in Figure 3, the module 101 can then receive reply from server 105 to the message 208 in the form of a response 209. Response 209 can be encrypted with the module public key 111 and signed with the server private key 105c, as depicted and described in connection with Figure 5a below. An exemplary format of the response 209 is also depicted and described in connection with Figure 6 below. The module 101 can receive the encrypted response 209 to message 208 in a datagram 209a that is sent from server IP:port 207 and received at module IP:port 204.

At step 307a, the module 101 can process the response 209 by decrypting the response 209 using the module private key 112 and cryptographic algorithms 141. At step 307b, module 101 can verify a digital signature of response 209 using the server public key 114 and cryptographic algorithms 141. Additional details regarding step 307a and 307b are depicted and described in connection with Figure 5a below. Note that encryption of response 209 may be optionally omitted and a digital signature in response 209 may also be optionally omitted. Although not shown in Figure 3a, if the module 101 cannot decrypt the response 209 or verify the digital signature of response 209, then the module 101 can drop the response 209 and optionally send message 208 again.

After the module 101 successfully processes response 209 in steps 307a and 307b, as shown in step 308, the module 101 can sleep the CPU 101b and/or shutdown the radio 101z. Step 308 could comprise the module 101 entering the "radio off" state 505a as depicted and described in connection with Figure 6b of U.S. Patent Application Serial No. 14/023,181 (the contents of which are hereby incorporated by reference in their entirety), and/or entering the "CPU off" state 505b as described in Figure 6c of U.S. Patent Application

Petitioner Samsung Ex-1004, 0074

Serial No. 14/023,181. Step 308 could also comprise the module 101 sending a detach message to a wireless network 102 as depicted and described in connection with Figure 6a of U.S. Patent Application Serial No. 14/023,181. Thus, according to a preferred exemplary embodiment, module 101 can omit sending or receiving any further radio resource control messages after processing the encrypted and/or signed response 209, when completing step 308.

After entering the sleep state in step 308, the module can then periodically check a sleep timer at step 309, and wake from sleep if the timer has expired and report subsequent data from a sensor 101f to a server 105 by returning to step 305.

Figure 3b

Figure 3b is a graphical illustration of components within a received profile and an activated profile for an embedded universal integrated circuit card (eUICC), in accordance with exemplary embodiments. The need for supporting M2M applications, where swapping out a SIM card or UICC card may not be practical, supports the use of an alternative embedded universal integrated circuit card (eUICC). Note that the development of an eUICC for M2M applications could extend to mobile phones and smart phones generally in the future, such that a SIM card or UICC would not need to be distributed to end users for insertion into mobile phones or M2M devices, thereby reducing costs and increasing the flexibility of modules 101 to quickly and easily connect with different wireless networks 102. In September of 2013, ETSI published an outline of the requirements for an eUICC specification in ETSI TS 103 383 v12.2.0, while many of the implementation details remain under study and review as of November 2013. ETSI technical specification TS 103 383 v12.2.0 is herein incorporated by reference in its entirety.

A primary feature of an eUICC 163 can be the automated and remote handling of network access credentials. An eUICC 163 can support subscriber and user equipment access a wireless network 102 such as a PLMN that supports ETSI standards such as LTE and future mobile operator networks. The electronic distribution of network access credentials such as the traditional Ki or K pre-shared secret key in mobile networks faces significant security challenges in the form of a profile for an eUICC 163. Figure 3b illustrates an exemplary embodiment, where the internal derivation of a module private key 112 and a module public key 111 in the present invention can provide in a secure and flexible manner either (i) essential network access credentials directly (where network access credentials can use a module private key 112 and module public key 111), or (ii) the support of the derivation of a secret shared network key K 129d (thereby allowing network access credentials to remain both secure and fully compatible with deployed wireless networks reliant on key K).

Petitioner Samsung Ex-1004, 0075

A received eUICC profile 311 could provide information for connecting to a wireless network 102. A received eUICC profile 311 can include much or all of the same information available to a module 101 from a traditional physical SIM card or UICC. The received eUICC profile 311 can comprise a profile for the eUICC 163 that is received by module 101. The module 101 can receive the profile 311 via a radio 101z or a network interface 101a such as a usb interface 101v (in embodiments where a manufacturers, distributor, module provider 109, or end user load an initial received profile 311). An eUICC 163 can support multiple profiles in order for a module 101 to connect with multiple different wireless networks 102 that support ETSI and similar standards for wireless WANs. A received eUICC profile 311 could also comprise a file or a set of data that is encrypted using any of a symmetric ciphering algorithm 141b, an asymmetric ciphering algorithm 141a, or potentially a secret ciphering algorithm 141h. The file or set of data which includes network access credentials 312 for a wireless network 102 can comprise a received eUICC profile 311. The encryption of a received eUICC profile 311 is not illustrated in Figure 3b, and for clarity the received eUICC profile 311 is illustrated in Figure 3b in plaintext form. As contemplated herein, received eUICC profile 311 may be referred to as profile 311, and activated eUICC profile 311 may be referred to as profile 313. Profile 311 can be a file or set of data that is (i) received by module 101 and (ii) includes network access credentials 312. Profile 313 can be a file or set of data that is (i) selected and/or activated by module 101 in a profile activation step 316, and (ii) includes network access credentials 314.

In addition, according to a preferred exemplary embodiment, a received eUICC profile 311 is encrypted with a symmetric ciphering algorithm 141b and a derived shared secret key 129b as a symmetric key 127 for the symmetric ciphering algorithm 141b. The derived shared secret key 129b could be derived using a key derivation function 141f and input of at least an initial module private key 112b. The key derivation function 141f could comprise an ECDH 159 key exchange, such that the network public key 165b could also be input into the key derivation function, where the cryptographic parameters for an ECDH 159 comprise a base point G. Consequently, in an exemplary embodiment, module 101 can receive the profile 311 and decrypt the profile 311 using the initial module private key 112b. In other words, the initial module private key 112b can be input into an ECDH 159, and the resulting derived shared secret key 129b (which would be mutually derived by a server 105) could be used with a symmetric ciphering algorithm 141b for a module 101 to decrypt the received profile 311. In another embodiment, the initial module private key 112b could comprise a symmetric ciphering key 127, such that module 101 can decrypt the profile 311 directly using the initial module private key 112b and a symmetric ciphering algorithm 141b (and a server 105 associated with an eUICC subscription manager 164 could encrypt the profile 311 using the initial module private key 112b.

Petitioner Samsung Ex-1004, 0076

In exemplary embodiments, the received eUICC profile 311 can include a shared secret key 510, where the shared secret key 510 can be used to authenticate a derived module public key 111 in a set of activated mobile network operator (MNO) network access credentials 314 after a profile activation step 316. A shared secret key 510 is also depicted and described in further detail in connection with Figure 5b below. A shared secret key 510 within a received eUICC profile 311 may be optionally omitted, and an initial key K 325 could be used by module 101 to securely and/or authoritatively send a derived module public key 111 (and/or a key K module token 1103) to a wireless network 102, as depicted and described in Figures 5b, Figure 7, and Figure 9b below.

In exemplary embodiments, the received eUICC profile 311 can include an initial key K 325, which could comprise a standard shared secret key K for accessing wireless network 102 (such as a key K contemplated in 3GPP TS 33.401 V12.9.0 figure 6.2-1 and related standards). The initial key K 325 with network module identity 110b can be used by module 101 to initially connect with wireless network 102. Upon or after the initial connection from module 101, wireless network 102 can receive cryptographic data from module 101 such as, but not limited to, a derived module public key 111 and/or a key K module token 1103 (depicted and described in connection with Figure 11 below). After sending the cryptographic data using the initial key K 325, module 101 and mobile network operator 108 could mutually derive the new secret shared network key K 129d illustrated in Figure 3b (using steps depicted and described in connection with Figure 9b and Figure 11 below). Module 101 and mobile network operator 108 could subsequently (i) record the derived, secret shared network key K 129d recorded by a module 101 within an activated eUICC profile 313 in an eUICC 163, and (ii) use the derived, secret shared network key K 129d with the network module identity 110b as a set of activated mobile network operator network access credentials 314. Additional details for using a module private key 112, module public key 111, and a key K module token 1103 in order to derive a mutually shared secret shared network key K 129d is depicted and described in additional Figures below.

As contemplated herein, a received eUICC profile 311 and an activated eUICC profile 313 can comprise versions or subsets of profiles for an eUICC contemplated in ETSI specification TS 103 383 v12.2.0 and related standards. Also as contemplated herein, a received eUICC profile 311 can be referred to as a "received profile", and likewise an activated eUICC profile 313 below can be referred to as an "activated profile". A received eUICC profile 311 can include a set of cryptographic parameters 126, a set of network parameters 310, and a received mobile network operator (MNO) network access credentials 312. The received MNO network access credentials 312 could include a network module identity 110b, and the network module identity 110b could comprise an IMSI number or similar network identifier. In an exemplary preferred embodiment, the received MNO network access credentials 312 does not include a

Petitioner Samsung Ex-1004, 0077

module private key 112 and corresponding module public key 111, and these keys can be derived by a module 101 and subsequently included in an activated eUICC profile 313 below. The received MNO network access credentials 312 can include an initial key K 325 for initial communication with a wireless network 102 for a mobile network operator 108. A set of cryptographic parameters 126 are depicted and described in connection with Figure 1d and Figure 1i and other Figures herein.

The set of network parameters 310 could comprise a list of values and settings for a module 101 to utilize in connecting with a mobile network 101. The settings could include a list of numbers or strings for values such as (i) allowed frequencies or frequency bands to scan, (ii) preferred access lists for roaming onto other wireless networks, (iii) criteria for a module 101 to select base stations in idle mode, (iv) support for emergency services, (v) supported languages or character encoding, etc. While a received eUICC profile 311 is activated, the network module identity 110b can be uniquely associated with a module identity 110, and thus a network module identity 110b could comprise a module identity 110, in order to identify module 101 with a wireless network 102. A received eUICC profile 311 could also include a network public key 165b, which could provide functionality equivalent for a server public key 114, with additional differences between a network public key 165b and a server public key 114 could be (i) network public key 165b can be associated with entities such as MNO 108 or eUICC subscription manager 164, and (ii) network public key 165b can be associated with network private key 165a. Network public key 165b could also be associated with a plurality or collection of servers 105, such as the set of servers 1010 illustrated in Figure 10, while a server public key 114 could be associated with a particular server 105. As illustrated in Figure 1c, the network public key 165b can be recorded in the eUICC 163 directly instead of within a received eUICC profile 313, and other possibilities exist as well without departing from the scope of the present invention.

In exemplary embodiments, a received eUICC profile 311 could be stored or recorded in a nonvolatile memory of module 101 such as, but not limited to, a flash memory 101w. An initial, first received eUICC profile 311 could be loaded into an eUICC 163 of module 101 by a manufacturer during manufacturing of module 101, a distributor during distribution of module 101, or a technician or end-user upon installation or receipt of module 101. The initial, first received eUICC profile 311 could also be recorded in a nonvolatile memory such as a ROM 101c, and a manufacturer or module provider 109 could write the initial, first received eUICC profile into the ROM 101c before distribution, and other possibilities exist as well. Note that and additional, second received eUICC profile 311 (or a plurality of received eUICC profiles 311) could be received by a module 101 after connection to an initial wireless network 102 using the initial, first received eUICC profile 311. Other possibilities exist as well for a module 101 to receive and record a received eUICC profile 311 without departing from the scope of the present invention. The second,

Petitioner Samsung Ex-1004, 0078

received eUICC profile 311 could be received by a module 101 from an eUICC subscription manager 164 (such as in a response 209 from a server 105 operated by a subscription manager 164).

A module 101 could convert a received eUICC profile 311 into an activated eUICC profile 313, after waking from a dormant state in order to connect with an initial wireless network 102 using a profile activation 316 step. For a profile activation 316 step, a module 101 could populate or provide the received MNO network access credentials 312 with a derived module private key 112 and a derived module public key 111. In this manner, a profile activation step 316 can take a step to convert a received eUICC profile 311 into an activated eUICC profile 313, and other steps for activation of a received eUICC profile 311 may be required as well. Within a profile activation step 316, a module 101 could use the set of cryptographic parameters 126 within the received eUICC profile 311 and a set of cryptographic algorithms 141, including a key pair generation algorithm 141e and a random number generator 128 in order to derive the module private key 112 and a corresponding module public key 111. The processing, generation, and/or derivation by a module 101 of a module PKI key pair 315 in a profile activation step 316 is also depicted and described in further detail along with a step 515 in Figure 5b below.

The derived module private key 112 and derived module public key 111 could comprise a first derived module PKI key pair 315. By populating or associating the received MNO network access credentials 312 with a derived module private key 112 and a corresponding module public key 111 in a profile activation step 316, the module 101 can convert, transform, or process the received MNO network access credentials 312 into an activated MNO network access credentials 314 within an activated eUICC profile 313, whereby the activated eUICC profile 313 can include or be associated with the derived module private key 112 and a corresponding module public key 111. Within an activated eUICC profile 313, the derived module private key 112 and a corresponding module public key 111 could be recorded or associated with a set of activated MNO network access credentials 314. The activated eUICC profile 313 could be recorded in an eUICC 163. In another exemplary embodiment, the recording by a module 101 of a derived module private key 112 and a corresponding module public key 111 can occur at a separate time than a profile activation step 316, although the module PKI key pair 315 may preferably be recorded by a module 101 before module 101 completes a connection to a wireless network 102. For example, the module 101 could potentially "pre-populate" or "pre-associate" the received MNO network access credentials 312 with a derived module PKI key pair 315 before a profile activation step 316. Note that a derived module private key 112 and a corresponding module public key 111 may optionally not be recorded directly within an activated eUICC profile 313, but rather can be separately associated by a module 101 or an eUICC 163 with an activated eUICC profile 313.

Petitioner Samsung Ex-1004, 0079

In exemplary embodiments, the first activated eUICC profile 313 could be deactivated and continued to be recorded by a module 101, along with the first derived module PKI key pair 315, for potential later use. The module 101 could subsequently activate a second received eUICC profile 311, including populating or associating the second received eUICC profile 311 with a second, different, derived module PKI key pair 315 (i.e. different than the first derived module PKI key pair 315) in order to connect with a second wireless network 102 for a second mobile network operator 108 using a second activated MNO network access credentials 314 with the second, different, derived module PKI key pair 315. In other words, a module 101 could use a profile activation step 316 a second time with the second received eUICC profile 311, resulting a second activated eUICC profile 313 where the first activated eUICC profile 313 had been deactivated. Although not illustrated in Figure 3b, an activated eUICC profile 313 can optionally continue to record the initial key K 325 from the received eUICC profile 311 before a profile activation step 316.

Upon reactivation of the first activated eUICC profile 313 (which could be deactivated in order to use the second received eUICC profile 311 as described in the paragraph above) in order to connect with the initial wireless network 102 a second time, the module 101 could either (i) reuse the first derived module PKI key pair 315, or (ii) derive a new derived module PKI key pair 315. Thus, a profile activation step 316 could populate a received eUICC profile 311 with a derived module PKI key pair 315 if the received eUICC profile 311 does not already include a derived module PKI key pair 315, but a profile activation step 316 could reuse an existing derived module PKI key pair 315 for reactivating a previously used (but deactivated) activated eUICC profile 313. In another embodiment, a profile activation step 316 could repopulate a previously used (but deactivated) activated eUICC profile 313 with a new derived module PKI key pair 315.

In exemplary embodiments, a module 101 and a wireless network 102 could perform many additional steps in order for a module 101 to utilize a received eUICC profile 311 and an activated eUICC profile 313, including: populating an activated eUICC profile 313 with other data, encrypting and decrypting a received eUICC profile 311, providing access to a wireless network 102 to control or update an activated eUICC profile 313 or a received eUICC profile 311, implementing policies for the remote management of an eUICC 163, installing or loading an eUICC profile, deleting an eUICC profile. Profiles received and activated by a module 101 using an eUICC 163 could be provided and managed by an eUICC subscription manager 164, in addition to many other steps and procedures. These additional steps and procedures for the utilization of an eUICC 163, other than steps and elements described in Figure 3b including (i) the use of a derived module PKI key pair 315, (ii) deriving a secret shared network key K 129d, and (iii) using an initial key K 325 but then subsequently the secret shared network key K 129d, are known to those of ordinary skill in the art and thus are not described in additional detail herein. Additional steps related to a module 101 using a profile activation 316 step to derive and utilize a module PKI key pair 315 as a basis for (i) network

Petitioner Samsung Ex-1004, 0080

access credentials, (ii) the secure authentication and verification of a module identity 110 (possibly comprising a network module identity 110b), and (iii) encryption or ciphering of data transmitted from or received by a module 101, are depicted and described in additional Figures below.

Figure 4

Figure 4 a is a flow chart illustrating exemplary steps for a module to process a message, including encrypting sensor data and sending a digital signature, in accordance with exemplary embodiments. The steps illustrated in Figure 4 may comprise step 306 illustrated in Figure 3a above. Since message 208 and response 209 may traverse the wireless network 102 and IP Network 107, according to an exemplary preferred embodiment, a module 101 and a server 105 can take additional steps in order to maintain security of a system 100. Since module 101 could connect from a wide variety of networks, such as LAN, wireless LAN, wireless WAN, etc., server 105 may optionally support module 101 connecting from any valid IP address, including addresses outside of a mobile network operator's 108 wireless network 102. Module 101 can process a message 208 using the sequence of steps illustrated in Figure 4. For additional clarification, an exemplary format of a message 208, using the exemplary steps of Figure 4, is illustrated in Figure 6 below. Note that the security methods described herein are optional, and message 208 and response 208 can be sent without the additional security steps described herein, but the use of these security steps may be preferred. Figure 4 can contain the messages and steps shown within step 306 of Figure 3a, where a module 101 processes message 208 before sending it to server 105 through the wireless network 102 and IP Network 107.

As illustrated in Figure 4, in preparing a message 208 to send to server 105, module 101 can utilize a sensor measurement 305, where the sensor measurement 305 comprises sensor data acquired by a sensor 101f associated with module 101. A sensor measurement 305 is also depicted and described in connection with Figure 1c above, and may comprise a string or number containing data regarding a parameter of a monitored unit 119. Sensor measurement 305 can also comprise a plurality of measurements or processed sensor measurements 305 such as an average value over time, high and low values, etc. Sensor measurement 305 could be either raw or processed data collected by a sensor 101f. As illustrated in Figure 4, module 101 could also include a server instruction 414, which could be a command for server 105 such as an update, query, or notification. A server instruction 414 could also be used by module 101 as input into step 402 below, where the server instruction 414 can be encrypted.

Module 101 may optionally add a security token 401, which could also be a random number, or a randomly generated text, binary, or hexadecimal string. Security token 401 could be created using random

Petitioner Samsung Ex-1004, 0081

number generator 128 and included in message 208 in order to make each message 208 unique and thus avoid any replay attacks when message 208 traverses wireless network 102 and IP Network 107 in order to securely reach server 105. A random number in security token 401 could be processed by module 101 using a seed 128b in a random number generator 128, where the seed utilizes data from sensor 101f as input into the seed, as illustrated in Figure 1c above. Security token 401 could alternatively be a non-random number used to make message 208 unique, such as a timestamp with significant digits to milliseconds or microseconds, and other possibilities for security token 401 exist as well. In other words, the use of security token 401 can ensure to a high level of certainty that each message 208 will be different and thus the same data within message 208 would not be sent more than once (other than a short timeframe such as within a few seconds where the same UDP packet for a message 208 could be intentionally sent more than once in order to implement and support forward error correction).

At step 401a, if (i) module 101 is sending message 208 to server 105 for the first time, or (ii) expiration time 133 for a previous symmetric key 127 has transpired, then module 101 may preferably include a symmetric key 127 within message 208, where the symmetric key 127 would be encrypted using an asymmetric ciphering algorithm 141a with the module private key 112 at step 402. In this case of (i) or (ii) in the previous sentence, module 101 can securely send the symmetric key 127 to server 105, which could then utilize symmetric key 127 in a symmetric ciphering algorithms 141b at later steps. As noted in Figure 1d, symmetric key 127 could be derived using cryptographic algorithms 141 and a random number from random number generator 128. If (a) module 101 has already sent a message 208 to server 105, or (b) expiration time 133 for a symmetric key 127 has not transpired (and thus symmetric key 127 would remain valid), then module 101 can omit including symmetric key 127 at step 401a.

At step 402, module 101 could utilize the sensor data 305, security token 401, server public key 114, server instruction 414 (not shown) and the cryptographic algorithms 141 to encrypt the sensor data 305 and security token 401. A step 402 could utilize either a symmetric ciphering algorithm 141b with a symmetric key 127 or an asymmetric ciphering algorithm 141a with the server public key 114. Symmetric ciphering 141b may be used to encrypt sensor data 305, and asymmetric ciphering 141a may be used to encrypt a symmetric key 127. The output of step 402 can be module encrypted data 403. If a symmetric key 127 is included within message 208, then module 101 preferably utilizes asymmetric ciphering 141a with server public key 114 at step 402. The asymmetric ciphering 141a at step 402 may be processed according to RSA algorithms 153, elliptic curve cryptography (ECC) algorithms 154, or other asymmetric ciphering algorithms for either public key cryptography or proprietary methods.

Note that if (A) a symmetric key 127 is utilized for symmetric ciphering 141b between module 101 and server 105 at step 402, such utilizing as a symmetric key 127 which could be derived using ECDH 159,

Petitioner Samsung Ex-1004, 0082

then (B) AES 155, Triple DES, or other symmetric ciphering algorithms 141b can be used at step 402 to generate module encrypted data 403. If symmetric ciphering 141b is utilized in step 402, exemplary symmetric ciphers AES 155 and Triple DES are depicted and described in connection with Figure 1d above. If symmetric ciphering 141b with ECIES is utilized in step 402, then step 402 could utilize the steps outlined in Figure 2, titled "ECIES Encryption Functional Diagram" in "A Survey of the Elliptic Curve Integrated Encryption Scheme" by Martinez et al in the Journal of Computer Science and Engineering, Volume 2, August 2010, page 10, (herein incorporated by reference). The use of (i) symmetric ciphering algorithms 141b, such as with AES 155, Triple DES, and similar secure symmetric ciphers, with (ii) symmetric key 127 may be preferred at step 402, if symmetric key 127 is available.

After processing module encrypted data 403, module 101 can add or append a module identity 110. Module identity 110 is illustrated in Figure 4 as being added after the module 101 processes module encrypted data 403, although module identity 110 may optionally only be included in module encrypted data 403 if symmetric ciphering 141b with cryptographic algorithms 141 and symmetric key 127 is utilized, (i.e. module identity 110 could be included before step 402, where module identity could be included as an input into step 402 as opposed to being added after step 402). By including module identity 110, possibly in the form of an encrypted module identity 110a, as external to module encrypted data 403 as illustrated in Figure 4 at step 404, server 105 can use the module identity 110 to pre-process or route a message before decrypting module encrypted data 403. For example, server 105 could utilize a message preprocessor 105y and module identity 110 outside of module encrypted data 403 to select a sub-server 105w. By including module identity 110, possibly in the form of an encrypted module identity 110a, as external to module encrypted data 403, server 105 can use the module identity 110 to select either (i) a module public key 111 or (ii) a symmetric key 127 from a database 105k in order to decrypt module encrypted data 403 or verify a digital signature. The exemplary message 208 illustrated in Figure 6 below shows one example of a message 208 where module identity 110 in the form of an encrypted module identity 110a is included as external to module encrypted data 403, which is also illustrated in Figure 4.

Module identity 110 in a message 208 can represent the use of multiple unique strings or numbers over time that are uniquely associated with module 101, such as a first string for module identity 110 as recorded by module 101 and a second string for module identity 110 as recorded by a server 105. Module identity 110 could also comprise a session identifier, where the session identifier is uniquely associated with module identity 110 for a limited period of time, and a new session identifier is periodically generated by either module 101 or server 105. Thus, the use of a module identity 110 in a message 208 may comprise a different format or string than the module identity 110 preferably read from hardware, where the module

Petitioner Samsung Ex-1004, 0083

identity 110 read from hardware could be a serial number, Ethernet MAC address, IMEI, etc. However, both can be utilized to uniquely identify a module 101 and thus are referred to herein as a "module identity" 110.

For cases where module 101 either (i) uses asymmetric ciphering 141a in a step 402, such as sending a symmetric key 127, or (ii) sends data without symmetric ciphering 141b (i.e. sends plaintext) module 101 can generate a module digital signature 405 for the message 208 using the module private key 112. The module digital signature 405 can be processed according to public key infrastructure (PKI) standards such as the National Institute of Standards (NIST) "FIPS 186-4: Digital Signature Standard" (which is hereby incorporated herein by reference), or IETF RFC 6979 titled "Deterministic Usage of the Digital Signature Algorithm (DSA) and Elliptic Curve Digital Signature Algorithm (ECDSA)" (which is hereby incorporated herein by reference). The use of a module digital signature 405 can be processed according to the description of a digital signature according to the Wikipedia entry for "Digital Signature" as of September 9, 2013, which is incorporated by reference herein in its entirety. Module digital signature 405 may also comprise a Message Authentication Code (MAC) or tag. Also note that other uses of a digital signature as contemplated within the present invention may refer to the above three references and related standard techniques for processing and creating digital signatures.

Other PKI standards or proprietary methods for securely generating a module digital signature 405 may be utilized as well. According to a preferred exemplary embodiment, ECC algorithms for generating module digital signature 405 may be utilized in order to minimize the key length compared to RSA algorithms. Module digital signature 405 may comprise a secure hash signature using a secure hash algorithm 141c related to the secure hash algorithm 1 (SHA-1), or subsequent standards such as SHA-2 156 and SHA-3 157, and other possibilities exist as well. Module digital signature 405 is illustrated in Figure 4 as being processed after module encrypted data 403, but module digital signature 405 may also optionally be included in module encrypted data 403. However, since module digital signature 403 can represent a secured hash signature that can contain limited useful information to a potential eavesdropper, module processing resources and energy can be conserved by including module digital signature 405 after and external to module encrypted data 403 (i.e. the benefits of encrypting module digital signature 405 may be limited). Also note that module digital signature 405 and the other secure digital signatures contemplated herein may be calculated with input from either (i) the plaintext in an encrypted message such as module encrypted data 403 or (ii) the ciphered data before conversion to plaintext, such as module encrypted data 403 before decryption at step 413.

Module 101 can then continue processing message 208 by including channel coding 406. Channel coding techniques for channel coding 406 could include block codes and convolution codes. Block codes could include Reed-Solomon, Golay, BCH, Hamming, and turbo codes. According to a preferred exemplary

Petitioner Samsung Ex-1004, 0084

embodiment, channel coding 406 can utilize a turbo code, so that server 105 can correct bit errors received by server 105 in message 208. Alternatively, module 101 could implement channel coding by simply transmitting the same packet more than once and the use of block codes or convolution codes could be bypassed. Or, module 101 could implement channel coding by both transmitting the same packet more than once and also using a block code or convolution code in the body of the packet. The use of channel coding 406 can be preferred, since any bit errors received by server 105 within module encrypted data 403 or module digital signature 405 in message 208 could break a decryption or signature verification algorithm such as cryptographic algorithms 141 used by server 105. Thus, the use of channel coding 406 (with a transport protocol that supports the transmission of bit errors such as UDP with checksums disabled in IPv4 or UDP Lite) can ensure the decryption of message 208 is robust to bit errors. Bit errors may potentially generated by intermediate network links and nodes as message 208 traverses a wireless network 102 or IP Network 107. Channel coding 406 may optionally be omitted.

As illustrated in Figure 4, module 101 can then format message 208 according to a transport protocol such as UDP within UDP processing 407 to create message 208. Other options besides the UDP processing illustrated in Figure 4 are available as well, including TCP formatting, but UDP formatting may be preferred in order to minimize the number of packets transmitted as well as TCP overhead. Note that TCP overhead when using IPv6 can be significant, since the full series of TCP messages to establish a TCP session and transmit the message 208 may include about 4-6 packets, where each packet in the message includes a TCP header and a full 128 bit address for both the source IP address and the destination IP address. In contrast, UDP may preferably require only a single packet for message 208 and a single packet for response 209, thus significantly reducing the overhead and conserving either (i) a battery 101k life or (ii) energy usage by module 101 by reducing the data transmitted and received by module 101.

According to a preferred exemplary embodiment, UDP formatting 407 can be formatted according to the UDP Lite protocol (IETF RFC 3828) with IPv6, whereby UDP checksums can be partially disabled and channel coding 406 can be included in the UDP datagram to correct for bit errors. Note that the UDP and UDP Lite protocols may be updated in the future with subsequent standards, but the UDP formatting 407 may preferably continue to include both (i) partially or fully omitted packet checksums within the packet header and (ii) channel coding within the packet body. Also note that if IPv4 is utilized by module 101 and server 105, regular UDP (i.e. according to RFC 768) formatting may be utilized with channel coding 406 and checksums in the packet header may be disabled.

As illustrated in Figure 4, after adding UDP formatting 407, module 101 may record a fully formatted message 208. As illustrated in Figure 2, message 208 can be sent by module 101 using a physical interface 101a such as radio 101z and a wireless network 102 and the IP Network 107. Additional details

Petitioner Samsung Ex-1004, 0085

regarding the structure of message 208 after taking exemplary steps in Figure 4 are shown in Figure 6 below. The security and efficiency features of message 208 can be useful for module 101 to efficiently balance potentially competing priorities of conserving battery life/bandwidth utilization/energy while maintaining security.

Figure 5a

Figure 5a a is a flow chart illustrating exemplary steps for a module to process a response from the server, including verifying a server's identity and decrypting instructions, in accordance with exemplary embodiments. Module 101 can perform the steps illustrated in Figure 5a in order to securely and efficiently process a response 209 from server 105. The steps illustrated in Figure 5b may comprise steps 307a and 307b illustrated in Figure 3. Module 101 can receive response 209 using IP:port 204, as illustrated in Figure 2. Response 209 can be formatted according to the UDP protocol or UDP Lite protocol, although other possibilities exist as well for the transport layer formatting of response 209, including TCP.

At step 407, module 101 can process the packet using the appropriate transport layer protocol, such as UDP. In this step 407, the body of the packet comprising response 209 can be extracted, and a checksum, if any, can be calculated to verify the integrity. An exemplary format of response 209 is depicted and described in connection with Figure 6 below. Note that if the UDP Lite protocol is utilized, the checksum may optionally only apply to the packet header. At step 406, module 101 can process and remove channel coding, if channel coding is present in response 209. Note that if a wireless network 102 comprises a IEEE 802.15.4 network, then UDP Lite may preferably utilized, and UDP Lite may preferably be utilized if wireless network 102 is a PLMN mobile network and the PLMN mobile network supports UDP Lite protocol. Channel coding techniques utilized in step 406 could include block codes and convolution codes, and can use related algorithms as used in channel coding 406 in Figure 4. By processing channel coding in step 406, module 101 can correct potential bit errors received in response 209. As noted above, the use of channel coding 406 can be preferred, since any bit errors received within server encrypted data 504 in response 209 could break (i) a cryptographic algorithms 141 used by module 101 at subsequent step 514, and/or (ii) the verification of a server digital signature 506 at step 501a.

At step 501, module 101 can read and record the server identity 206. Server identity 206 may preferably be a string that is external to server encrypted data 504 within response 209, as illustrated in Figure 6 below. The server identity 206 can preferably match a server identity 206 used in message 208. The server identity 206 could also comprise the source IP address 106 of response 209, or a domain name resolving to the source IP address 106, or a domain name associated with IP address 206. Server identity

Petitioner Samsung Ex-1004, 0086

206 may also be uniquely associated with an identity in the "Common Name" (CN) field of a certificate 122 for server 105. Receiving or processing a server identity within a response 206 may optionally be omitted, if module 101 can select the appropriate server public key 114 without first obtaining server identity 206. At step 501a, module 101 can validate and verify the server identity 206 using the server digital signature 506 inserted by server 105 in response 209. Server digital signature 506 can comprise a secure hash signature, where server 105 generated the hash signature using as input into a digital signature algorithms 141d (i) the server private key 105c and (ii) at least a portion of the server encrypted data 504. Module 101 can utilize the server public key 114 recorded in memory to securely validate the server digital signature 504, also by using digital signature algorithms 141d.

The server digital signature 504 can be verified according to public key infrastructure (PKI) standards such as the National Institute of Standards (NIST) "FIPS 186-4: Digital Signature Standard", or IETF RFC 6979 titled "Deterministic Usage of the Digital Signature Algorithm (DSA) and Elliptic Curve Digital Signature Algorithm (ECDSA)". Other PKI standards or proprietary methods for securely verifying a server digital signature 504 may be utilized as well. Also, server digital signature 506 could optionally be included in server encrypted data 504, where step 501a could take place after step 505. But, since server digital signature 506 may comprise a secure hash signature, any benefits from ciphering the secure hash may be small while requiring additional processor resources.

Note that if module 101 had previously received server digital signature 506 in a previous response 209, then steps 501 and 502 may optionally be omitted within a subsequent response 209. In other words, after module 101 receives a valid server digital signature 504, server 105 may then transmit a subsequent server digital signature 506 periodically according to rules based upon the security requirements of the application. As one example, if (a) after sending a symmetric key 127 in a message 208 to server 105 and receiving a response 209 to the message 208 with (i) a valid server digital signature 506 and (ii) a server encrypted data 503 using symmetric key 127, then (b) module 101 can subsequently have reasonable assurance that subsequent responses 209 using symmetric key 127 are also from server 105. According to a preferred exemplary embodiment, when module 101 sends a new symmetric key 127 using an asymmetric ciphering algorithms 141b, the response 209 from server 105 with server encrypted data 504 (where the server encrypted data 504 was created using the new symmetric key 127) can preferably include or be associated with a server digital signature 506 in either the response 209 or another packet from server 105.

Although not illustrated in Figure 5b, upon completing step 501a, module 101 may also optionally verify the server identity 206 of server 105 using a certificate 122 associated with server 105 and the public key of a certificate authority 118. Module 101 could request a certificate 122 associated with server 105 and calculate a secure hash signature 123 using cryptographic algorithms 141 and a certificate authority public

Petitioner Samsung Ex-1004, 0087

key 131 (illustrated in Figure 1a). Other possibilities exist as well for module 101 to verify the identity of server 105 without departing from the scope of the present invention. As one alternative, module 101 could utilize Domain Name System Security Extensions (DNSSEC), as specified in multiple IETF RFCs including RFC 4033, 4034, and 4035 to securely resolve server identity 206 into IP address 106. For example, module 101 could verify that the source IP address within response 209 matches a DNSSEC record for server name 206.

After verifying server digital signature 506 in step 501a, module 101 can record an authenticated server encrypted data 504 from server 105. Authenticated server encrypted data 504 may comprise an acknowledgement that server 105 received message 208. Authenticated server encrypted data 504 may be useful if the UDP or UDP Lite protocol is used to send message 208, since UDP is a connectionless protocol and module 101 may need confirmation that server 105 received message 208. Note that if steps 501 and 501a are omitted, then authenticated server encrypted data 504 may comprise a simple acknowledgement that server 105 received message 208. Although not illustrated in Figure 5a, if module 101 does not receive response 209 or server encrypted data 504 before a timer expires, such as within an exemplary duration of 2 seconds, then module 101 can resend message 208.

At step 505, module 101 can decrypt server encrypted data 504 using either (i) module private key 112 as a decryption key if asymmetric ciphering 141a is utilized to process server encrypted data 504, or (ii) symmetric key 127 if symmetric ciphering 141b is utilized to process server encrypted data 504. Module 101 can utilize cryptographic algorithms 141 and the key in order to decrypt the server encrypted data 504 at step 505. Module 101 can utilize techniques to decrypt server encrypted data 504 that are described in connection with creating module encrypted data 403 described in Figure 4 above. If server encrypted data 504 uses an asymmetric ciphering, the cryptographic algorithms 141 used in step 505 may be processed according to RSA algorithms 153, elliptic curve cryptography (ECC) algorithms 154, or other algorithms for public key cryptography, as described previously herein. ECC algorithms 154 may be preferred with asymmetric ciphering in order to maintain high security with small key lengths, compared to RSA, in order to minimize the message lengths, radio frequency spectrum utilization, and processing power required by wireless module 101. If server encrypted data 504 uses symmetric ciphering 141b, the cryptographic algorithms 141 can use symmetric key 127 to decrypt server encrypted data 504 at step 505.

Module 101 and server 105 could utilize a pre-agreed protocol in order to select the use of asymmetric ciphering 141a or symmetric ciphering 141b in a response 209. According to an exemplary embodiment, module 101 and server 105 (i) utilize asymmetric ciphering 141a when transmitting symmetric keys 127 or other keys such as pre-shared secret keys, new private keys, etc., and (ii) utilize symmetric ciphering 141b at other times (i.e. when not sending/receiving a key). Since the exemplary response 209

Petitioner Samsung Ex-1004, 0088

illustrated in Figure 6 does not contain a symmetric key, module 101 can utilize symmetric ciphering 141b in a step 505 with symmetric key 127 to decrypt server encrypted data 504 at step 505.

Response 209 may include a module instruction 502. By including module instruction 502 in server encrypted data 504 and response 209, the module instruction 502 can be read and processed by device 101 at step 507, after the server encrypted data 504 is decrypted at step 505. Module 101 can subsequently perform the module instruction 502 in step 507. Note that server encrypted data 504 may optionally include an acknowledgement that message 208 was received by server 105. In this manner, an "ACK" response to message 208 can be securely transmitted by server 105 and received by module 101. Additional details for exemplary module instruction 502 and the processing of a module instruction 502 by module 101 are depicted and described in connection with Figure 4 of U.S. Patent Application Serial No. 14/064,618, filed October 28, 2013 in the name of John Nix, entitled "A Set of Servers for "Machine-to-Machine" Communications using Public Key Infrastructure," which is hereby incorporated by reference in its entirety. Upon completion of the processing of response 209 illustrated in Figure 5b, module 101 can perform functions such entering the sleep or dormant states illustrated at step 308 in Figure 3a, thus conserving battery life (if present in module 101) or energy while maintaining a secure, robust, and highly scalable system 100.

Figure 5b

Figure 5b is a flow chart illustrating exemplary steps for a module to communicate with a server, including the module deriving public and private keys, in accordance with exemplary embodiments. In order to utilize communications secured with PKI techniques such as, but not limited to, private keys, public keys, certificates, and identities, a module 101 may preferably obtain or generate the keys and utilize a module identity 110 and/or a certificate 122 in a secure manner. Given that a plurality of modules 101 may be deployed in potentially remote places or inconvenient locations for manually changing a SIM card or UICC card, also potentially without frequent contact with end users and/or technicians, the use of secure PKI techniques for a module 101 can create a significant set of challenges for the generation of module public key 111 and module private key 112, as well as properly and securely obtaining a certificate 122 with an module identity 110. Using conventional technology, significant challenges and costs can be incurred when (i) module 101 has already been deployed, such as collecting data from a monitored unit 119, and (ii) module 101 needs to utilize a new set of module private key 112 and module public key 111. The steps depicted and described for a module 101 to securely derive and implement module PKI keys may also be used with an

Petitioner Samsung Ex-1004, 0089

eUICC 163 in order to for an eUICC 163 to securely establish a derived module private key 112 and derived module public key 111 within an activated eUICC profile 313, as depicted in Figure 3b above.

Exemplary embodiments that include derivation or processing of a new module private key 112 and module public key 111 may utilize the particular steps and procedures contemplated herein, in order to minimize any potential human intervention (with related costs) while continuing to maintain or also enhance security, compared either (i) externally generating module private key 112, and/or (ii) continuing to use the same module private key 112 for the lifetime of module 101. Over a long period of operating time for a module 101, such as, but not limited to, several years or longer, there may be many reasons module 101 may need a new pair of PKI keys, such as, but not limited to, (i) expiration of a certificate 122, or the certificate 122 of a parent signature authority, (ii) the transfer of ownership or control of module 101, where the prior ownership could have direct or indirect access to the module private key 112, (iii) supporting a new server 105 that has different security requirements or a different set of cryptographic parameters 126 (longer keys, different ECC curves, different cryptographic algorithms 141, etc.), (iv) revocation of a public key in a chain of signatures associated with a certificate 122, (v) in the event of a "factory reset" condition or similar circumstances where a prior key pair previously recorded in a nonvolatile memory may no longer be available, and (vi) the use of a module PKI key pair 314 within network credentials 314 for activated eUICC profiles 313, where (a) the network credentials 314 are used to access a wireless network 102, and (b) module 101 may prefer to connect with multiple different wireless networks 102 over time using different network credentials 314. In the case of (ii) above, new ownership of module 101 may require a module 101 to utilize a new module private key 112 since the old ownership may have access to an old module private key 112. In the case of (iii) above, a new server 105 may require a pair of public/private keys incompatible with a prior set of public/private keys utilized by module 101 and/or a certificate 122 for module 101.

Other possibilities exist as well for reasons why a module 101 and/or server 105 may prefer for a module 101 to utilize a new module public key 111 and new module private key 112. In an exemplary embodiment, module 101 may generate a new public/private key periodically in order to enhance the security of a system 100. A benefit of a system 100 supporting periodic generation of keys by module 101 is that the key length can be shortened in order to obtain a similar level of security, and the processing power and energy consumption, with energy possibly supplied by a battery 105k, can be reduced through the use of shorter key lengths. In other words, over time such as, but not limited to, several months or years, the use of a plurality of different pairs of public/private keys for module 101 with shorter key lengths can be both more secure and energy efficient than using a single pair of public/private keys with a longer key length for the lifetime of module 101. Shorter key lengths may also be more compatible with processing power constraints of a module 101. Or, a longer key length for public/private keys could also be utilized and periodically

Petitioner Samsung Ex-1004, 0090

rotated for increased security. In exemplary embodiments, module 101 and/or server 105 may prefer for module 101 to periodically generate new public and private keys. In addition, a mobile network operator 108 may prefer for a module 101 with an eUICC to periodically rotate, change, or lengthen a key K for accessing a wireless network 102, and the periodic generation of a new module PKI key pair 315 can support a periodic derivation of a new secret shared network key K 129d (as described in Figure 9b and Figure 11), which could be used to connect with wireless network 102.

The general approach adopted by most mobile phone networks over the past two decades has been founded upon the use of a pre-shared secret key (i.e. a "PSK") recorded in subscriber identity module (SIM) or UICC cards, such as the Ki pre-shared secret key in 2G or 3G networks, secret key K in 4G LTE networks, and specified in related standards. The use of a pre-shared secret key recorded in transferred physical media may work or be sufficient for mobile phones, where the SIMs can often be easily replaced, but the use of a pre-shared secret key K or Ki in a SIM or UICC may not be suitable for a module 101 and mobile network operator 108 for many circumstances. As one example, significant costs may be incurred by swapping out a SIM card for already deployed modules 101, especially if they are in remote locations or continually moving such as, but not limited to, a tracking device on a container, pallet, truck, or automobile. In an exemplary embodiment, a module 101 may preferably record multiple pairs of public/private keys 111/112 for various and different functions, such as, but not limited to, connecting to different servers 105, connecting to different wireless networks 102, using different module PKI key pairs 315 for different network access credentials 315 in different activated eUICC profiles 313, etc. As contemplated herein, recording more than one public/private key 111/112 can comprise module 101 recording a plurality of pairs of module public keys 111 and module private keys 112. Also as contemplated herein the module private key 112 for a module 101 can be different than a private key in a Diffie-Hellman key exchange, since the module private key 112 can be used to process a module digital signature 405, where a receiving node for a message with a module digital signature 405 can verify the signature using a module public key 111. In exemplary embodiments, one pair comprising a first module public key 111 and a first module private key 112 can be identified or selected from a different pair comprising a second module public key 111 and a second module private key 112 using a module public key identity 111a.

The number of pairs of public/private keys useful to a module 101 concurrently could be several, such as, but not limited to, an exemplary three or more actively used public/private keys, although other possibilities exist as well. Manually trying to change or add a new SIM card each time a new security key is required may not be efficient or feasible. Or in another exemplary embodiment, the multiple pairs of private and public keys could be used in sequence, such that module 101 with server 105 or wireless network 102 utilizes a single module public key 111 and module private key 112 at any given point in time. In the case

Petitioner Samsung Ex-1004, 0091

where module 101 with a module identity 110 derives or generates more than one module private key 112 and module public key 111 during the lifetime of module 101 and sends the derived module public keys 111 over time to a set of servers 1010 (illustrated in Figure 10 below) or a wireless network 102, this case may be considered a module 101 sending a series of module public keys for a module identity 110. The various PKI key pairs in the series may also use either different sets of cryptographic parameters 126 or the same set of cryptographic parameters 126. A first pair of PKI keys could be associated with a mobile network operator 108 and a second pair of PKI keys could be associated with a wireless network 102. The series of module public keys 111 (with corresponding module private keys 112) can be processed, generated, calculated, and/or derived by a CPU 101b with key pair generation algorithms 141e and a random number generator 128. The random number generator 128 can use input from a sensor 101f, a radio 101z, a clock 160, and/or a temporary random seed file 139.

In exemplary embodiments, module 101 can use a module public key 111 for sending a module encrypted data 403 or receiving a server encrypted data 504 by sending the module public key 111 to a server 105 in order to support (i) the module encrypted data 403 to be decrypted (such as, but not limited to, using a step 413 as depicted and described in connection with Figure 4 of U.S. Patent Application Serial No. 14/064,618, filed October 28, 2013 in the name of John Nix), or (ii) the server encrypted data 504 to be encrypted (such as, but not limited to, using a step 503 as depicted and described in connection with Figure 5a of U.S. Patent Application Serial No. 14/064,618, filed October 28, 2013 in the name of John Nix). In addition, a server 105 can use a module public key 111 for sending a module encrypted data 403 or receiving a server encrypted data 504 by inputting the module public key 111 into a key derivation function 141f in order to derive or process a derived shared secret key 129b, which could be used with a symmetric key 127. Other possibilities exist as well for module 101 to use its own module public key 111 with cryptographic algorithms for communicating with a server 105.

Figure 5b illustrates exemplary steps that can be performed with module 101, including using a module program 101i, for generating, deriving, and/or updating a module public key 111 and module private key 112. The steps illustrated in Figure 5b include both (i) an "initial" or "startup" case where module 101 has not previously derived keys (or keys not internally derived may not have been loaded), and (ii) a subsequent or "follow on" time where module 101 can generate or derive keys after keys were initially obtained or derived. Note that efficient and secure methods and systems contemplated herein, including in Figure 5b, may also be utilized with a regular consumer mobile phone, or smartphone, as a module 101. Mobile phones as module 101 can benefit from (i) deriving a module public key 111 and a module private key 112, (ii) sending module encrypted data 403 in a message 208 using the derived keys, and (iii) receiving a server encrypted data 504 in a response 209 also using the derived keys.

Petitioner Samsung Ex-1004, 0092

In exemplary embodiments where module 101 comprises a mobile phone, then sensor 101f may comprise a microphone and actuator 101y may comprise a speaker, and other possibilities exist as well to those of ordinary skill in the art for module 101 to comprise a mobile phone. In addition, a mobile phone as a module 101 could utilize an eUICC 163, and the derived module public key 111 and module private key 112 could be used for network credentials 314 in an activated eUICC profile 313. In other words, an embodiment illustrated in Figure 5b contemplates that an eUICC 163 can use a derived module PKI key pair 315 as network access credentials 314 in future wireless networks 102 and related standards, such that the mobile operator network 108 does not depend on, or require a pre-shared secret key K for access to the wireless network 102. Alternatively, and as illustrated in Figure 9b and Figure 11, a derived module PKI key pair 315 could be used in an eUICC 163 to derive a secret shared network key K 129d, which could be used as the primary key for authenticating with a wireless network 102. The present invention contemplates both embodiments discussed in the previous two sentences, including an eUICC 163 with a first activated eUICC profile 313 where the network access credentials 314 use a module PKI key pair 315, and a second activated eUICC profile 313 where the network access credentials 314 use a derived secret shared network key K 129d. The first activated eUICC profile 313 could be used by a module 101 for connecting with a first wireless network 102 (which could comprise a WiMAX network that utilizes a module PKI key pair 315 for authentication), and the second eUICC profile 313 could be used by a module 101 for connecting with a second wireless network 102 (which could comprise an LTE Advanced network that utilizes a shared secret key K for authentication).

At step 511, during manufacturing of module 101, including manufacturing of sub-components such as, but not limited to, a circuit board, assembly of hardware components illustrated in Figure 1c, etc., a module identity 110 could be written into the hardware, and could comprise a serial number, International Mobile Equipment Identity (IMEI) number, Ethernet MAC address, or a similar persistent identification for a module 101. An IEMI number may be used with a mobile phone as module 101, in a preferred embodiment. For security purposes, the module identity 110 may preferably be written into a read-only location or protected location or protected memory or protected address, such as, but not limited to, a readable location on a system bus 101d, which could also comprise a ROM 101c. Recording and utilizing module identity 110 is also depicted and described in connection with Figure 1c, Figure 2, and elsewhere herein. Alternatively, module identity 110 could be recorded in a non-volatile memory such as, but not limited to, a flash memory 101w.

At step 512, module 101 can be distributed to end users and also installed with a monitored unit 119. If module 101 is a mobile phone, then monitored unit 119 could be a person that carries the mobile phone. Also note that a monitored unit 119 could be omitted, and a module 101 could use the techniques

Petitioner Samsung Ex-1004, 0093

contemplated herein. At step 513, a shared secret key 510, parameters 126, and a server address 207 can be recorded in a nonvolatile memory 101w. As depicted in Figure 5b at a step 513, in an exemplary embodiment a first received eUICC profile 311 could alternatively be recorded in a nonvolatile memory 101w, and the first received eUICC profile 311 could include the shared secret key 510, the set of cryptographic parameters 126, and the server address 207. As contemplated herein, for an embodiment that utilizes an eUICC 163 for module 101, the shared secret key 510 in a received eUICC profile 311 can comprise an initial key K 325 for connecting with a wireless network 102.

Parameters 126 may comprise settings for a cryptographic algorithms 141 as illustrated in Figure 1i and Figure 1d, including (i) key lengths, (ii) algorithms to utilize for key generation or ciphering, such as, but not limited to, selecting RSA algorithms 153 or ECC algorithms 154, (iii) a specific secure hash algorithm 141c to utilize, such as, but not limited to, SHA-256 or SHA-3, (iv) an expiration date of the module public key 111, (v) a maximum time value for an expiration time 133 associated with a symmetric key 127, (vi) a ECC parameters 137 or an ECC standard curve 138 as parameters 126 in Figure 1h of U.S. Patent Application Serial No. 14/055,606, filed October 16, 2013 in the name of John Nix, (vii) the specification of or values for a padding scheme for use with a digital signature algorithms 141d, and/or similar or related values for using cryptographic algorithms 141d . Although not illustrated in Figure 5b, at step 513 a configuration file could also be loaded into non-volatile memory, where the configuration file includes a plurality of fields specifying the operation of module 101. The shared secret key 510, parameters 126, and server address 207 could be included in a configuration file.

Continuing at step 513, server identity 206 could be utilized in place of or in addition to server address 207, and in this case module 101 can later perform a DNS or DNSSEC lookup using server identity 206 in order to obtain server address 207 for use in a message 208, such as the destination address. Shared secret key 510 and server address 207 (or server identity 206) could also be recorded in a ROM 101c at step 513. Step 513 may also be performed concurrently with step 511 or step 512. According to an exemplary embodiment, a manufacturer may perform step 513 and in this case step 513 could take place concurrently with step 511. A manufacturer or distributor could load an initial eUICC profile into an eUICC 163 of module 101, such as a first received eUICC profile 311 illustrated at step 513 in Figure 5b, and in this case step 513 could take place before step 512. In another embodiment, a distributor of module 101 could perform step 513 and in this case step 513 could take place concurrently with step 512. Alternatively, step 513 may be performed by a technician or end user after manufacturing and distribution and before module 101 begins collecting sensor data with a monitored unit. Other possibilities exist as well for the sequence of steps 511 through 513 illustrated in Figure 5b without departing from the scope of the present invention. In general, the order of steps illustrated in various exemplary flow charts contemplated herein can be changed if

Petitioner Samsung Ex-1004, 0094

the revised order or sequence of steps can obtain the same or equivalent end result for the sequence of steps in the exemplary flow charts.

Note that step 513 may take place multiple times during the lifetime of a module 101, and in this case (a) the first time step 513 is conducted, step 513 could be conducted concurrent with steps 511 or 512, and (b) a subsequent time step 513 is conducted, step 513 could be conducted after the receipt of a response 209, where the response 209 includes either (i) a second shared secret key 510, server address 207, and also potentially a new module identity 110 or (ii) a new received eUICC profile 311. In other words, although not illustrated in Figure 5b, a module 101 could return to step 513 from later steps upon the equivalent of a "factory reset", or similar command where flash memory 101w and other nonvolatile memory would be cleared. In an exemplary embodiment where step 513 takes place a second time may potentially be the transfer of ownership or control of module 101, or a another embodiment where step 513 takes place a second time could be the upload of new firmware that is incompatible with a previous configuration file. In any case, (i) shared secret key 510 can preferably be uniquely associated with module 101 (i.e. any given shared secret key 510 may belong only to an individual module 101), or (ii) a module 101 could record another received eUICC profile 311 a second time that a step 513 could occur during the lifetime of a module 101.

Shared secret key 510 may comprise a pre-shared secret key 129a, as described in Figure 1c. Shared secret key 510 may be recorded in a received eUICC profile 311 if an eUICC 163 and related profiles are utilized, but the use of an eUICC 163 is not required in some embodiments of the present invention. In an exemplary embodiment, a module 101 could also utilize a eUICC 163 for connection to a wireless network 102, but a module 101 (i) does not need to use any keys associated with the eUICC 163 in order to communicate with a server 105 or set of servers 1010 and (ii) can separately utilize the techniques, module PKI keys, and other aspects of various embodiments contemplated herein. In other words, for some embodiments of the present invention contemplated herein, a module 101 can use an eUICC 163 for the purposes of connecting with a wireless network 102 (possibly without deriving a module PKI key pair 315 for an activated eUICC profile 313), but the module 101 can separately and independently use steps illustrated in Figure 5b and other Figures to communicate with a server 105. If (A), (i) module 101 has already derived a module private key 112 and module public key 111 and (ii) a module 101 is not utilizing an eUICC 163 and related profiles (including times when step 513 is being conducted at a second or additional time as contemplated in the previous paragraph), then (B) shared secret key 510 may comprise (i) a key received in a server encrypted data 504 including possibly a symmetric key 127, or (ii) a derived shared secret key 129b. Derived shared secret key 129b could be obtained by server 105 from using a key derivation function 141f such as ECDH 159 and module public key 111 and server private key 105c, using a

Petitioner Samsung Ex-1004, 0095

module public key 111 that has already been derived or used by module 101 (such as if at least one module private key 112 and module public key 111 had already been used or derived before step 513).

As contemplated herein in an exemplary embodiment where an eUICC 163 is not being utilized by a module 101 for encrypting data with a server 105 (but an eUICC 163 could be used for access to a wireless network 102), an initial module private key 112b and initial module public key 111b could be derived outside module 101 and loaded into a nonvolatile memory such as flash memory 101w at a prior time before step 513, and the shared secret key 510 could be received by module 101 using the initial module private key 112b and initial module public key 111b (such as, but not limited to, receiving the shared secret key 510 in a server encrypted data 504 using the initial module private key 112b which had been loaded). Step 513 could then comprise a later time after the server encrypted data 504 has been received that includes the shared secret key 510, where module 101 may (i) prefer to begin utilizing keys that module 101 internally derives using cryptographic algorithms 141 at a subsequent step 515 or step 316 instead of (ii) continuing to use the initial module public key 111b and initial module private key 112b that were derived outside of the module 101, such as, but not limited to, possibly loaded into a nonvolatile memory from an external source. In other words, module 101 could begin operation with PKI keys that are initially loaded, but then change to using PKI keys derived by module 101.

In the embodiment where (i) shared secret key 510 has not been received by module 101 in a server encrypted data 504, and (ii) a module 101 is not utilizing an eUICC 163 for the purposes of communicating with a server 105 (but could use an eUICC 163 for separate purposes of gaining access to a wireless network 102), shared secret key 510 for a step 513 could be obtained and loaded by a distributor, installer, or end user into a nonvolatile memory such as, but not limited to, flash memory 101w in the form of a pre-shared secret key 129a, where pre-shared secret key 129a was obtained using a module identity 110 and pre-shared secret key code 134 as depicted and described in connection with Figure 1e of U.S. Patent Application Serial No. 14/055,606, filed October 16, 2013 in the name of John Nix. Module 101 could also utilize a first pre-shared secret key 129a, including a first pre-shared secret key 129a entered by potentially a distributor, installer, or end-user described in Figure 1e, to derive shared secret key 510. Other possibilities exist as well for shared secret key 510 in a step 513, and shared secret key 510 can be useful for the proper identification and/or authentication of module 101 upon module 101's generation of a private key 112 and public key 111, as described below including step 517.

If module 101 is a mobile phone, as contemplated herein, shared secret key 510 could be loaded by a distributor or company selling or servicing the mobile phone, or shared secret key 510 in a step 513 could be obtained by the end user or subscriber accessing a web page associated with a mobile operator for a wireless network 102 associated with the mobile phone and/or SIM card. In an exemplary embodiment where

Petitioner Samsung Ex-1004, 0096

module 101 is a mobile phone and an eUICC 163 is being utilized by a module 101, the shared secret key 510 could be recorded in a received eUICC profile 311, as illustrated in Figure 3b. In another exemplary embodiment where module 101 is a mobile phone and an eUICC 163 is being utilized by a module 101, the shared secret key 510 could comprise an initial key K 325 recorded in a set of received MNO network access credentials 312.

Also note that as contemplated herein, an initial module private key 112b and initial module public key 111b could be recorded into nonvolatile memory at step 513. For example, a manufacturer, distributor, installer, technician, or end-user could load the initial module private key 112b and initial module public key 111b, where the initial module public key 111b would be utilized to authenticate at step 517 below a subsequent set of public/private keys derived by module 101 at step 515 below. In this case, the initial module public key 111b and/or initial module private key 112b described in the previous two sentences could comprise the shared secret key 510. In another embodiment, the initial module public key 111b and initial module private key 112b could be recorded in a SIM or UICC, and the SIM or UICC could be either virtual or physical such as, but not limited to, a SIM card, including a Universal Integrated Circuit Card (UICC) or an embedded UICC (eUICC). A set of servers 1010 (as illustrated in Figure 10) could also record the initial module public key 111b recorded in the SIM (including an eUICC), and the set of servers 1010 could authenticate a message or a subsequent module public key 111b derived by module 101 (such as in a step 515 below) using the initial module public key 111b. In other words, for an exemplary embodiment, an eUICC 163 or a profile within an eUICC 163 could record an initial module public key 111b and initial module private key 112b, and (i) the eUICC 163 could use the initial PKI keys for authenticating a subsequent, derived module public key 111, and (ii) the derived module public key 111 could be recorded within an activated MNO network access credentials 314 associated with an activated eUICC profile 313.

The use of an initial module public key 111b and/or initial module private key 112b are also depicted and described in connection with Figure 5b of U.S. Patent Application Serial No. 14/055,606, filed October 16, 2013 in the name of John Nix, which is hereby incorporated by reference in its entirety. Thus, Figure 5b also contemplates an embodiment where shared secret key 510 at step 513 comprises an initial public/private key pair for module 101 that is not internally derived by module 101, including keys derived at step 515. Note that the contemplation of the use of shared secret key 510 as a pre-shared secret key 129a within the present invention may be different than the use of a pre-shared secret key within a subscriber identity module (SIM) card as commonly supported by wireless networks 102 with mobile phones in 2013, one reason being the shared secret key 510 can be used by a server 105 and a module 101 to authenticate a derived module public key 111, but conventional technology does not contemplate that a pre-shared secret key within a SIM

Petitioner Samsung Ex-1004, 0097

or UICC could be directly read (i.e. moved into a RAM memory 101e) by a module 101 in order to authenticate a derived module public key 111.

At step 514, module 101 can read module identity 110 using a read-only address. Module 101 can read module identity 110 directly from read-only hardware address by using system bus 101d, including from a ROM 101c, or module 101 can read module identity 110 from a nonvolatile memory such as a flash memory 101w. A step 514 may also be optionally omitted in embodiments where module 101 utilizes an eUICC 163, and in this case the module 101 can read the network module identity 101b from the received eUICC profile 311 acquired in a step 513 above. Step 514 could also take place after step 515 below. At step 515 or a profile activation 316 step, module 101 can derive module private key 112 and a corresponding module public key 111 using (i) random number generator 128, (ii) cryptographic parameters 126, (iii) cryptographic algorithms 141, and/or (iv) a key pair generation algorithm 141e. The derived module private key 112 and module public key 111 can comprise a module PKI key pair 315. As contemplated herein, a step 515 could also comprise a profile activation 316 step, such that a received eUICC profile 311 without a module PKI key pair 315 can be converted or transformed into an activated eUICC profile 313 with a module PKI key pair 315. Module 101 at step 515 or a step 316 and elsewhere in the present invention can be a mobile phone such as, but not limited to, a smartphone, and the mobile phone could include an eUICC 163. Module private key 112 and corresponding module public key 111 can be derived using a key pair generation algorithm 141e according to a wide range of parameters 126, and can utilize different algorithms for different pairs of keys, such as, but not limited to, RSA 153 or ECC 154.

Key derivation at a step 515, including the use of a profile activation step 316, could generate keys of various lengths, such as, but not limited to, 2048 bits with RSA 153 or 283 bits with ECC 154, and other possibilities exist as well. If using ECC 154 to derive a pair of keys for module 101, step 515 could also accommodate the use of different elliptic curves for compatibility with server 105, such as, but not limited to, the use of odd-characteristic curves, Koblitz curves. The use of the set of parameters from a step 513 in a step 515 or step 316 can ensure the derived keys by module 101 use a compatible or identical elliptic curve or defined elliptic curve equation as server 105, etc. In a step 513 or a step 316 in Figure 5b, module 101 can use ECC parameters 137 or an ECC standard curve 138 in a parameters 126 to derive module private key 112 and/or module public key 111. Note that the use of an eUICC 163 is not required for some embodiments, and a step 515 can be used to derive a module private key 112 and a module public key 112 for the purposes of communicating with a server 105 without using or depending upon an eUICC 163 and related profiles.

Deriving keys in step 515 or a profile activation step 316 could also comprise using values such as constants or variables in a set of cryptographic parameters 126 to define an elliptic curve equation for use

Petitioner Samsung Ex-1004, 0098

with an ECC algorithm 154. For the embodiment where module 101 derives module PKI key pair 315 within an activated network credentials 314, a profile activation step 316 can utilize the set of cryptographic parameters 126 within a received eUICC profile 311, and the set of cryptographic parameters 126 could be used with a key pair generation algorithm 141e to derive the module PKI key pair 315. The values or constants to define an equation for an elliptic curve could be input into a key pair generation algorithms 141e in the form of ECC parameters 137 or an ECC standard curve 138. In alternative embodiments, an RSA algorithm 153 can be used for deriving module PKI keys instead of ECC algorithms 154. In an exemplary embodiment, where a parameters 126 does not include constants and variables for defining an elliptic curve equation, a key pair generation algorithms 141e could use pre-defined elliptic curves with ECC algorithms 154 such as, but not limited to, standardized, named curves in ECC standard curve 138 including exemplary values such as, but not limited to, sect283k1, sect283r1, sect409k1, sect409r1, etc. Exemplary, standardized named curves, as opposed to module 101 and server 105 using an internally generated elliptic curve equation using cryptographic parameters 126, are also identified as example curves in IETF RFC 5480, titled "Elliptic Curve Cryptography Subject Public Key Information". Thus, module 101 could use either standardized elliptic curves, or a separate defined elliptic curve equation as specified in a set of cryptographic parameters 126. Or, module 101 could use RSA algorithms 153 with key pair generation algorithms 141e such that derived keys for module 101 can be used with RSA algorithms 153 within a set of cryptographic algorithms 141. In embodiments where module 101 uses an RSA algorithm 153 to derive a module private key 112 and a module public key 111 in a step 515 or a step 316, the set of cryptographic parameters 126 can include a modulus for the RSA algorithm 153.

For embodiments where elliptic curve cryptography is used by a module 101 instead of RSA-based cryptography, the curve for module 101 to utilize in deriving module public key 111 and module private key 112 at step 515 or a profile activation step 316 could be specified in a set of cryptographic parameters 126. Consequently, the parameters of keys generated by module 101 at step 515 or a profile activation step 316 (including key length or algorithms utilized) may be selected based upon the requirements of the application and can be included in a parameters 126. When deriving keys at step 515 or a profile activation step 316, module 101 may also utilize data from sensor 101f, radio 101z, a bus 101d, a physical interface 101a, memory 101e, and/or a clock 160 in order to generate a seed 128b for random number generator 128, or random number generator 128 could utilize these inputs directly. A random number 128a can be input into key pair generation algorithm 141e in order to derive the module public key 111 and module private key 112. Note that with ECC algorithms 154, a module private key 112 can be a random number 128a in one embodiment, and the module public key 111 can be derived with a key pair generation algorithms 141e using the module private key 112 comprising the random number 128a.

Petitioner Samsung Ex-1004, 0099

For embodiments where a module 101 uses an eUICC 163, module 101 could also derive or calculate a key K module token 1103 at a step 316 in Figure 5b, along with the derived module private key 112 and module public key 111. A key K module token 1103 is depicted and described in connection with Figure 9b and Figure 11 below. Key k module token 1103 could comprise (i) the module public key 111, in embodiments where module 101 and server 105 use an ECDH 159 key exchange, or (ii) another value or number for a server 105 to derive a secret shared network key K 129d using a network key K derivation algorithm 1101 (in Figure 11 below). Other possibilities exist as well for a key K module token 1103 calculated by a module 101 in a step 316 in order for a server 105 to utilize the key K module token 1103 in a network key K derivation algorithm 1101 without departing from the scope of the present invention.

Upon key derivation at step 515 or a profile activation step 316, module private key 112 and module public key 111 can be recorded in a nonvolatile memory 101w. For the use of a profile activation step 316 in Figure 5b, the module private key 112 and module public key 111 can also be recorded with a set of activated mobile network operator (MNO) network access credentials 314 for an activated eUICC profile 313, and the activated eUICC profile 313 could be recorded in a eUICC 163. The eUICC could also be recorded in a nonvolatile memory 101w. Module private key 112 can preferably not be transmitted or sent outside module 101. Also note that over a potential lifetime of a decade or more of operation of module 101, each time a new module private key 112 may be required (for various potential reasons outlined above), including multiple instances of a profile activation step 316, the external recording and/or transferring of module private key 112 incurs a potential security risk. Security risks can be compounded if the external location records private keys 112 for a plurality of modules 101. Also, by internally generating private key 112 at step 515, which could comprise a profile activation step 316, module 101 can overcome significant limitations and costs requiring the distribution of a pre-shared secret key Ki or K in the form of a SIM card or UICC or similar physical distribution of a pre-shared secret key, after module 101 begins operations.

In comparison with conventional technology, the use of a shared secret key 510 in the present invention does not require physical distribution of a new shared secret key 510 after module 101 begins operations such as, but not limited to, sending a module encrypted data 403, and a shared secret key 510 could be recorded in a received eUICC profile 311 for embodiments that use a eUICC 163. Module 101's key derivation and related steps could also be triggered by either (i) a bootloader program 125, where the bootloader program 125 determines that memory within module 101 does not contain a module private key 112, or (ii) via a module instruction 502 such as, but not limited to, a "key generation" or "derive new keys" command in a response 209 from a server, and other possibilities exist as well. Thus, in accordance with a preferred exemplary embodiment, the derivation of a module public key 111 and a module private key 112 at a step 515 in Figure 5 does not require the use of a profile activation step 316, and the derivation of the

Petitioner Samsung Ex-1004, 0100

module PKI keys does not require and optionally may not be associated with or depend upon the use of an eUICC 163.

Note that module 101's generation of keys after deployment and installation may create challenges for authentication of a new module public key 111 with module identity 110, since module 101 may be connecting to server 105, wireless network 102, or mobile network operator 108 via the IP Network 107 or an open or public network such as a wireless network 102 that may comprise many modules 101 or mobile phones. After module 101 creates new module public key 111 and module private key 112 at step 515 or a profile activation step 316, at step 516 module 101 can send a message 208 with the module identity 110, the new module public key 111, and cryptographic parameters 126 or 126a. In an exemplary embodiment where a module 101 uses a profile activation step 316 with an eUICC 163 in Figure 5b, the server 105 receiving the message 208 with the module identity 110 (possibly in the form of a network module identity 110b) and new module public key 111 could reside within or be associated with a mobile network 102. Parameters 126 in message 208 at step 516 can represent the parameters 126 used to generate the module public key 111.

In exemplary embodiments where an eUICC 163 is being utilized in a Figure 5b, module 101 can send a key K module token 1103 to a mobile network operator 108 in a step 516. Key K module token 1103 could be calculated in a step 316 above, although other possibilities exist as well for the timing or sequence when a module 101 calculated a key K module token 1103 without departing from the scope of the present invention. The exemplary used of a key K module token 1103 is also depicted and described below in connection with Figure 11 and Figure 9b below. Key K module token 1103 could comprise (i) the derived module public key 111, or (ii) another value or number for a server 105 associated with a mobile network operator 108 to derive a secret shared network key K 129d. Steps 516 and step 517 illustrated in Figure 5b could be combined into a step 522, and a step 522 can be utilized by a module 101 in embodiments where an eUICC 163 is utilized and a module 101 performs or conducts the steps illustrated in Figure 9b.

Also, as contemplated herein, a step 516 and a step 517 illustrated in Figure 5b may optionally be combined or the order of a step 516 and a step 517 changed. In an exemplary embodiment, the receipt of data within a step 516 could only be possible if a module 101 using a module identity 110 or 110b had previously been authenticated before a step 516. In other words, a module 101 and a server 105 could take steps not illustrated in Figure 5b before step 516 to authenticate module 101 before a step 516, including both nodes using a shared secret key 510, which could also comprise an initial key K 325. In this case, where module 101 could be authenticated before a step 516, the authentication of a message 208 in a step 517 could be considered automatic, since the module 101 could be authenticated before a step 516. Other possibilities for a module 101 to authoritatively send data in a step 516 are possible as well without departing from the scope of the present invention.

Petitioner Samsung Ex-1004, 0101

Parameters 126 in message 208 at step 516 may also be optionally omitted, in an embodiment where a server 105 and a module 101 can pre-agree (before a step 516 illustrated in Figure 5b) on the set of cryptographic parameters 126 or 126a associated with the module public key 111. The sub-steps for a server 105 to receive a message 208 are also depicted and described in connection with Figure 2 above. Parameters 126 within a message 208 can comprise descriptive values for new module public key 111. Note that at step 516, server 105 does not need to receive new module public key 111 in the form of a certificate 122 (although it could be in the form of a certificate 122). New module public key 111 could be received by server 105 within a string or field within a body 602 of a TCP/UDP packet 601a, illustrated in Figure 8 below. As depicted in step 516 shown in Figure 8 below, message 208 at step 516 can also optionally include a module public key identity 111a, which can be recorded in module database 105k along with module identity 110 and module public key 111a.

According to an exemplary embodiment where an eUICC 163 is not being utilized, a first source (IP:port) number received in a first message 208 at step 516 can be different than a second source IP:port number in a second message 208 at step 518 below, wherein a response 209 send in step 519 below can preferably be sent to the second source IP:port number received in the second message 208 at step 518 in order to traverse a firewall 104 (as depicted and described in connection with packet 209a in Figure 2). In other words, the proper destination IP:port for a response 209 to a module 101 can change over time, such as the proper destination IP:port changing due to the use of sleep states by module 101 and/or function of a firewall 104. Consequently, according to an exemplary embodiment, a response 209 can utilize a destination IP:port number equal to the source IP:port number received in the last (i.e. most recent) message 208 from module 101 received by server 105.

At step 517, server 105 can authenticate the message 208 received in step 516 using the shared secret key 510 described in a step 513 or profile activation step 316. Server 105 could record the shared secret key 510 before step 517 in a module database 105k. If step 517 occurs for the first time in a lifetime of module 101, then shared secret key 510 could comprise a pre-shared secret key 129a recorded by server 105 in a module database 105k illustrated in Figure 1a and Figure 1m. If step 517 occurs at subsequent time, then server 105 could have sent shared secret key 510 in a server encrypted data 504 and recorded shared secret key 510 in a module database 105k for later use (such as at step 517). For the embodiment where a module 101 uses an eUICC and the steps illustrated in Figure 5b to connect with a wireless network 102, the shared secret key 510 could be recorded in a received eUICC profile 311, and the shared secret key 510 could comprise an initial key K 325 within the received eUICC profile 313 from a step 513. For the embodiment where a module 101 uses an eUICC and the steps illustrated in Figure 5b to connect with a wireless network 102, the shared secret key 510 in a step 517 can comprise an initial key K 325.

Petitioner Samsung Ex-1004, 0102

In a step 517, server 105 can authenticate the message 208 according to message digest, or using the shared secret key 510, possibly in the form of a initial key K 325, to process a symmetric key 127 within a symmetric ciphering algorithm 141b, where the successful encryption and decryption of data within message 208 using the shared secret key 510 on both ends could be confirmation that message 208 is authenticated, since both parties would only be able to mutually successfully encrypt and decrypt by sharing the same shared secret key 510. As contemplated herein, the term "authenticating a public key" may refer to "authenticating a message that includes the public key", and both may refer to validating or verifying that a recorded module identity 110, possibly in the form of a network module identity 110b, accessed by server 105 from a module database 105k is associated with a receive module public key 111. In the case where an eUICC 163 is utilized by a module 101 to connect with a wireless network 102, a network module identity 110b may be utilized instead of a module identity 110 (i.e. the server 105 could use a recorded network module identity 110b instead of the module identity 110 for authentication of the derived module public key 111).

Other possibilities exist as well for server 105 to use a shared secret key 510 in order to authenticate a message 208 that contains a new module public key 111 (where module 101 contains a new module private key 112) or a key K module token 1103. In one embodiment, message 208 in step 516 could include a module digital signature 405 using secure hash algorithms 141c, where both the module 101 and the server 105 input a string combing at least a portion of the shared secret key 510 and a portion of the new module public key 111 into the secure hash algorithms 141c in order to obtain the module digital signature 405. Module 101 could send the module digital signature 405 to server 105 in a message 208. Additional embodiments for the authentication of a new module public key 111 or a key K module token 1103 for a step 517 is also depicted and described in a step 1202 of Figure 12 in U.S. Patent Application Serial No. 14/064,618, filed October 28, 2013 in the name of John Nix, which is hereby incorporated by reference in its entirety. Thus, the present invention contemplates the authentication and/or verification of either (i) new module public key 111 or key K module token 1103 or (ii) a message 208 that includes new module public key 111 or key K module token 1103 according to steps that use alternatives to a shared secret key 510 for the authentication.

According to some exemplary embodiments, new module public key 111 or key K module token 1103 from a step 515 or profile activation step 316 can be authenticated and/or verified as being properly associated with a recorded module identity 110 in server 105 (i) without the use of a shared secret key 510, and/or (ii) with alternatives to using shared secret key 510. After receiving authenticated new module public key 111 in steps 516 and 517, according to a preferred exemplary embodiment, server 105 can preferably only accept and process (A) either incoming (i) a symmetric keys 127 ciphered with a asymmetric ciphering

Petitioner Samsung Ex-1004, 0103

algorithm 141a, and/or (ii) incoming server instructions 414, when (B) the next or a subsequent incoming message 208 from module 101 using module identity 110 also includes a valid module digital signature 405 verified by using the new module public key 111, received at step 516.

According to an exemplary embodiment, shared secret key 510 can be associated with a module public key identity 111a, and shared secret key 510 can be used to authenticate a particular value for a module public key identity 111a. In this embodiment, (i) a message 208 with module public key 111 and a first module public key identity 111a may be authenticated using a shared secret key 510, but (ii) a second message with module public key 111 and a second module public key identity 111a may not be authenticated using the same shared secret key 510. Thus, in accordance with an exemplary embodiment, shared secret key 510 can be used for both (i) a single time for authenticating a module public key 111 or a key K module token 1103 received in a step 516, and (ii) authenticating a module public key 111 with a particular value for the module public key identity 111a. Note that module public key identity 111a can be particularly useful with key revocation, such that a key revocation could specify a particular module public key identity 111a (associated with a particular module public key 111) to be revoked, but other module public keys 111 for a module 101 and module identity 110 with different module public key identities 111a could remain valid and not revoked.

Although not illustrated in Figure 5b, for embodiments where an eUICC 163 is not utilized to authenticate and encrypt data between module 101 and server 105, server 105 could operate with a certificate authority 118 in order to utilize a new module public key 111, as described in this paragraph. In this case, server 105 could bypass the authentication at step 517, but certificate authority 118 may perform step 517 in order to sign the certificate 122, including possibly using shared secret key 510 to authenticate module public key 111. At step 516, new module public key 111 could be received by server 105 in the form of a uniform resource locator (URL) or domain name for download of a certificate 122 corresponding to the new module public key 111. Using a certificate authority 118 in conjunction with step 516 is also depicted and described in connection with Figure 5b of U.S. Patent Application Serial No. 14/055,606, filed October 16, 2013 in the name of John Nix, which is hereby incorporated by reference in its entirety.

After steps 516 and 517, which could be combined into a step 522, server 105 can update a module database 105k using the module identity 110 or network module identity 110b to insert or update the new module public key 111 or key K module token 1103, and parameters 126 associated with new module public key 111. As contemplated herein, a set of servers 1010 (illustrated in Figure 10 below) could collectively perform the function of a single server 105, and thus multiple separate computers could comprise a server 105. Server 105 may communicate with a plurality of modules 101, and thus could utilize a module database 105k in order to record the new module public key 111 or key K module token 1103 and parameters 126

Petitioner Samsung Ex-1004, 0104

with the module identity 110. In one embodiment, the module identity 110 could preferably operate as an index within a table of module database 105k in order to speed reads and writes from the table used with module public key 111, parameters 126, and also selecting a symmetric key 127 for a symmetric ciphering algorithm 141b in later messages. As described in Figure 1d, Figure 1i, and elsewhere herein, parameters 126 can include data useful for the operation of cryptographic algorithms 141 and module public key 111. According to a preferred exemplary embodiment, some modules 101 in a system 100 could utilize a first elliptic curve, such as, but not limited to, using a first set of ECC parameters 137 or first ECC standard curve 138 within a parameters 126, and other modules 101 could utilize a second and different elliptic curve within a parameters 126, such as, but not limited to, a second set of ECC parameters 137 or second ECC standard curve 138. The different sets of parameters 126 for different modules 101 using different module identities 110 could be recorded in the module database 101k.

After verifying the new module public key 111 in a step 517, at step 518 of Figure 5b, module 101 could send a second message 208, and the second message 208 can include a module identity 110 and module encrypted data 403. In embodiments where (i) an eUICC 163 is utilized, and (ii) server 105 belongs to a wireless network 102 such as a wireless network operator 108, then the term "module identity 110" as contemplated throughout the present invention can comprise a network module identity 110b. A module identity 110 comprising an identity associated with hardware for module 101 can be used with an eUICC 163 (since the eUICC may use multiple network module identities 110b). Although not illustrated in Figure 5b, the second message 208 could also include a module digital signature 405, wherein the module digital signature is created with the new module public key 111 received in step 516. Server 105 could then utilize the steps illustrated in Figure 4 in order to process the incoming message 208 with the new module public key 111, including using the module identity 110 sent by a module 101 in the second message 208 at step 518 to select the new module public key 111 and subsequently verify a module digital signature 405 using the new module public key 111 and digital signature algorithm 141d. Also as discussed in Figure 4 in connection with processing a message 208, module 101 could encrypt the module encrypted data 403 in the second message 208 in a step 518 by using server public key 114. In one embodiment, the second message 208 as illustrated in Figure 5b, which could be the next message after authenticating module public key 111 in step 517, could include a symmetric key 127.

The module encrypted data 403 in step 518 could include a symmetric key 127 for utilization with a symmetric cipher 141b, where symmetric key 127 could be ciphered with an asymmetric ciphering algorithm 141a. In another embodiment, module 101 could also send sensor data in a module encrypted data 403 at step 518. Or, at step 518 the second message 208 could be a signal and/or data (such as a random number 128a) for server 105 to use a key derivation function 141f with the server public key 114 and the new module

Petitioner Samsung Ex-1004, 0105

public key 111 (received at step 516) to create a new derived shared key 129b for use with symmetric ciphering algorithms 141b in subsequent messages 208. In other words, in some embodiments derived shared key 129b can function as a symmetric key 127. If the second message 208 in step 518 comprises a signal and/or data for server 105 to derive a new derived shared key 129b, then this second message 208 could then optionally leave off module encrypted data 403 and/or a module digital signature 405. The successful use of a new derived shared key 129b (using the new module public key 111, possible received in step 516, and existing server public key 114) with symmetric ciphering algorithms 141b at subsequent steps by both module 101 and server 105 can indicate to each the communications are mutually authenticated. Second message 208 at a step 518 could also include a server instruction 414, a security token 401, and/or a timestamp value 604, and other possibilities exist as well without departing from the scope of the present invention.

At step 519, module 101 can receive a response 209 from server 105, where the response 209 includes server encrypted data 504 and a module instruction 502. Module 101 could take the steps to receive and process response 209 as depicted and described in connection with Figure 5a. Response 209 could be formatted according to the exemplary response 209 illustrated in Figure 6a below. The module instruction 502 could be an acknowledgement 501 that the second message 208 sent in step 518 was received by server 105.

In an exemplary embodiment where module 101 utilizes an eUICC 163 to connect with a wireless network 102, module 101 could use a step 519 to receive second, received eUICC profile 311 at a step 519. The second, received eUICC profile 311 could be included within the server encrypted data 504, but the second, received eUICC profile 311 may also optionally comprise a file or set of files that are encrypted and in this case the encrypted, second, received eUICC profile 311 in a step 519 could optionally be received in a response 209 without a server encrypted data 504 (i.e. the server 105 may optionally not add additional encryption from a Figure 5a to the profile 311 if the profile 311 is already encrypted). The new, received eUICC profile 311 received by a module 101 in a step 519 could provide information, such as, but not limited to, a set of network parameters 310 and a set of network access credentials 312 for connecting with a second, different wireless network 102 than the wireless network 102 utilized to receive the response 209 at a step 519. The profile 311 received in a step 519 could comprise receiving several sets of related data (possibly in different but related responses 209), such as a first set that includes network access credentials 312 and a second set of data that includes network parameters 310 or cryptographic parameters 126. Module 101 could use the second, received eUICC profile 311 in order to change network access credentials 314 and connect with a different wireless network 102 (or possibly change network access credentials 314 for connecting with the same wireless network 102).

Petitioner Samsung Ex-1004, 0106

In this embodiment where a module 101 uses an eUICC 163, module 101 could receive the profile 311 from an eUICC subscription manager 164 at a step 519, where the eUICC subscription manager 164 uses a server 105 and sends a response 209 with the profile 311 to the module 101 in a step 519. The message 208 with the module identity 110 from the previous step 518 could be sent to the server 105 associated with the eUICC subscription manager 164. The module 101 could send (a) the module identity 110 read from a hardware address such as a protected memory in a step 514 above to (b) the eUICC subscription manager 164 in the previous step 518 in order to receive the profile 311 in a step 519. Note that (a) the mobile network operator 108 providing connectivity and access to the IP Network 107 in previous steps in Figure 5b, such as, but not limited to, a previous step 518 could comprise (b) the eUICC subscription manager 164 sending the profile 311 received by a module 101 in a step 519. Or, the eUICC subscription manager 164 receiving the message 208 in a step 518 could be a different entity than MNO 108, such as module provider 109 (where module provider 109 in Figure 1a is also illustrated as an eUICC subscription manager 164). Other possibilities exist as well for the location/operator of an eUICC subscription manager 164 receiving the message 208 in a step 518 (in order to send the response 209 with the profile 311) without departing from the scope of the present invention.

At step 520, module 101 can send a third message 208 with a confirmation 414 to server 105. Confirmation 414 can be used to signal proper execution of module instruction 502 from a step 519, if module instruction 502 comprised an instruction other than an "ACK" or acknowledgement 501. In the embodiment where a module 101 received a second, received eUICC profile 311 at step 519, the step 520 could comprise a signal from module 101 back to server 105 that the received eUICC profile 311 has been properly received, passes integrity checks, and/or is compatible with module 101, etc. In an embodiment where module instruction 502 in step 519 comprises an acknowledgement 501 from server 105, then the confirmation 414 may omitted and in this case step 520 could be skipped.

At step 521 server 105 can determine or evaluate if (i) a new module public key 111 and/or certificate 122 are required for continued operation, or (ii) the use of the second, received eUICC profile 311 from a step 519 is preferred for connecting to a second wireless network 102. One reason for the need of new keys could be the expiration of a certificate 122 for module 101, or the desire to utilize a different set of cryptographic parameters 126 such as, but not limited to, a longer key length for increase security or the use of a different ECC parameters 137 or a different ECC standard curve 138 with cryptographic algorithms 141. As described elsewhere herein and above in this Figure 5b, many other possibilities exist for reasons why module 101 and/or server 105 can prefer for module 101 to utilize a new module public key 111 and new module private key 112. Either server 105 or module 101 may determine that the use of a new module public key 111 and new module private key 112 may be preferred at step 521. If module 101 determines that

Petitioner Samsung Ex-1004, 0107

the use of a new module public key 111 and new module private key 112 is preferred or desirable, module 101 could send server 105 a signal that new keys will be generated either before step 521 or at step 521.

Upon determining at step 521 either (i) new keys are desirable or (ii) the use of the second, received eUICC profile 311 is preferred, then module 101 could derive new private and public keys by returning to step 515 or step 316, as illustrated in Figure 5b. In the embodiment where an eUICC 163 is used, as described above, a module 101 could activate the second, received eUICC profile 311 upon returning to a step 316 and derive a second module PKI key pair 315 for the second, received eUICC profile 311. The second module PKI key pair 315 can be different than the first module PKI key pair 315 associated with the first received eUICC profile 311 from a step 513. Although not illustrated in Figure 5b, upon determining "yes" at step 521, server 105 could send a module instruction 502 of "new key generation" and also a new or current set of cryptographic parameters 126 to utilize with the new module private key 112 and module public key 111. In accordance with exemplary embodiments, module instruction 502, including the "new key generation" instruction and set of parameters 126, can be received in a response 209 after module 101 wakes from a sleep or dormant state and sends a message 208 after waking from the sleep or dormant state. If module 101 determines that new keys are not required or desirable at step 521 (including the use of the second received eUICC profile 311 from a step 519 is not required at one instance of a step 521 but the use of a received eUICC profile 311 could be preferred at a subsequent instance of a step 521), module 101 can then proceed to step 309 and wait according to a sleep or idle timer before sending the next message 208 to a server 105.

Although not illustrated in Figure 5b, in embodiments where module 101 uses an eUICC 163 and receives an eUICC profile 311 in a step 519, upon determining the value "yes" at a step 521, module 101 could proceed to a step 905 depicted and described in connection with Figure 9b and follow the subsequent set of steps using the received eUICC profile 311 from a step 519. In the embodiment where an eUICC 163 is utilized by module 101 for connecting to a wireless network 102, upon determining the value "no" at a step 521, a step 309 in Figure 5b could comprise the module 101 waiting to send a periodic "location update" request in order to signal to a wireless network 102 that module 101 continues to be attached in an idle state. In other exemplary embodiments, a module 101 could use a regular SIM or UICC in order to connect with wireless network 102, and module 101 could use the steps illustrated in Figure 5b to connect with a server 105 without an eUICC 163.

Figure 6

Figure 6 is a simplified message flow diagram illustrating an exemplary message sent by a module, and an exemplary response received by the module, in accordance with exemplary embodiments. Figure 6

Petitioner Samsung Ex-1004, 0108

illustrates exemplary details within message 208 sent by module 101 and also response 209 received by module 101. Message 208 may comprise a TCP/UDP packet 601a sent from module 101 source IP:port 204 to server 105 destination IP:port 207. According to an exemplary embodiment, UDP or UDP Lite formatting for TCP/UDP packet 601a may be preferred. Source IP:port 204 and destination IP:port 207 in message 208 may be included within a header in TCP/UDP packet 601a. Although a single message 208, response 209, module 101, and server 105 are shown in Figure 6a, system 100 as illustrated in Figure 2 and other systems depicted herein may comprise a plurality of each of the nodes and datagrams illustrated in Figure 6. As contemplated herein, the term "datagram" may also refer to a "packet", such that referring to as datagram 601a can be equivalent to referring to packet 601a. Note that when using TCP protocol, a packet within a series of TCP messages can also be a datagram 601a.

TCP/UDP packet 601a may include a body 602, which can represent the data payload of TCP/UDP packet 601a. The data payload of message 208 can optionally include channel coding 406 as described in Figure 4 above, if the transport protocol for TCP/UDP packet 601a supports the transmission of bit errors in the body 602 (as opposed to entirely dropping the packet), such as, but not limited to, with the UDP Lite protocol. Support for the transmission of bit errors in body 602 by wireless network 102 would be preferred over entirely discarding a packet, since the programs or algorithms used by a module controller 105x could include support for and utilization of channel coding 406. Without UDP Lite formatting, message 208 can alternatively sent by module 101 as a UDP datagram, such as if wireless network 102 (or a wired connection) does not support the UDP Lite protocol.

Note that if (A) message 208 comprises (i) regular UDP or TCP formatting (i.e. not UDP Lite or similar variations) within an IPv6 network, or (ii) a UDP or TCP format within an IPv4 network with a checksum 603 enabled (i.e. checksum 603 not equal to zero), then (B) channel coding 406 may optionally be omitted. Checksum 603 can comprise a value to for an integrity check of a packet 601a, and the calculation and use of checksum 603 is defined in IETF standards for TCP and UDP packets. In accordance with an exemplary embodiment, including the use of IPv6 for IP Network 107 and a UDP datagram for message 208 and response 209, a checksum 603 sent by module 101 in a message 208 does not equal a checksum 603 in the message 208 received by server 105, in the case where firewall 104 is present and the firewall 104 performs network address translation.

The body 602 can include a module identity 110, module encrypted data 403, and channel coding 406. The module identity 110 in Figure 6 is illustrated as an encrypted module identity 110a, and the encrypted module identity 110a could be processed using a ciphering algorithm within a set of cryptographic algorithms 141 to convert the module identity 110 into an encrypted module identity 110a. Although not illustrated in Figure 6, body 602 could also include a module digital signature 405, as illustrated in Figure 6

Petitioner Samsung Ex-1004, 0109

of U.S. Patent Application Serial No. 14/039,401. Module identity 110 in the form of an encrypted module identity 110a is illustrated in Figure 6 as external to module encrypted data 403, although module identity 110 may optionally only be included in module encrypted data 403, and in this case module identity 110 would not be external to module encrypted data 403 in a body 602. By including module identity 110 as external to module encrypted data 403, server 105 can use the unencrypted module identity 110 in order to select either (i) the appropriate module public key 111 to verify module digital signature 405 if an asymmetric cipher 141a is used within cryptographic algorithms 141, or (ii) the appropriate symmetric key 127 for a set of cryptographic algorithms 141 to decrypt the module encrypted data 403. Module public key 111 and symmetric key 127 may preferably be recorded in a module database 105k, such that server 105 can access a plurality of public keys 111 or symmetric keys 127 associated with different module identities 110 with different bodies 602 for a plurality of modules 101, which is also illustrated in Figure 1m.

Thus, by including module identity 110 external to module encrypted data 403, server 105 can utilize the module identity 110 to query a module database 105k and select the appropriate module public key 111 or symmetric key 127. As noted previously, module identity 110 could comprise a string or number that is uniquely associated with module identity 110, such as, but not limited to, a session identity, as opposed to being a module identity 110 that is read from hardware in module 101 such as, but not limited to, an IMEI number, Ethernet MAC address, etc. Module identity 110 is illustrated in Figure 6 as a session identity that is a different representation of module identity 110 of a serial number such as in Figure 2, but in both cases the values can comprise a module identity 110 since the values can be uniquely associated with module 101 at different points in time.

According to an exemplary embodiment where asymmetric ciphering 141a of module encrypted data 403 is utilized, such as (i) the first message 208 sent by module 101 and (ii) where a symmetric key 127 had not been previously exchanged, module identity 110 can be (a) within module encrypted data and (b) not external to module encrypted data 403. In this case, server 105 can utilize server private key 105c to, in sequence, decrypt module encrypted data 403, extract module identity 110 from the decrypted module encrypted data 403, and then used the module identity 110 to select module public key 111 from module database 105k in order to verify a module digital signature 405. In a related embodiment, if a module identity 110 is in body 602 and external to module encrypted data 403, then module identity 110 could be obfuscated or otherwise ciphered according to a pre-agreed algorithm with server 105, such that server 105 can utilize the obfuscated or ciphered module identity 110 to select a module public key 111 from module database 105k. The value of "[Encrypted Module Identity]" shown in Figure 6 could comprise an encrypted module identity 110a, and the algorithm token 190 in the form of a random number 128a could be used with a secret ciphering algorithm 141h illustrated in Figure 1g to convert a module identity 110 to an encrypted

Petitioner Samsung Ex-1004, 0110

module identity 110a and also to convert an encrypted module identity 110a to a module identity 110. The use of an algorithm token 190 in a message 208 illustrated in Figure 6 can be optionally omitted in exemplary embodiments. According to an exemplary embodiment where (i) symmetric ciphering 141b of module encrypted data 403 is utilized, such as after a first message 208 had already been sent by module 101 and a symmetric key 127 had previously been exchanged, then (ii) module identity 110 can be external to module encrypted data 403 and in body 602 in order for server 105 to utilize module identity 110 and select symmetric key 127 from a module database 105k, thereby enabling server 105 to decrypt the module encrypted data 403 using the selected symmetric key 127 and a symmetric ciphering algorithm 141b.

In exemplary embodiments, a module digital signature 405 may optionally be omitted from body 602 after module 101 has previously sent symmetric key 127 in a previous message 208 to the message 208 illustrated in Figure 6. In other words, in a series of messages 208, module 101 can preferably change from (i) using asymmetric ciphering 141a with in a previous message 208 that includes symmetric key 127 in a module encrypted data 403 (where the initial message 208 also includes module digital signature 405 and module identity 110) to (ii) using symmetric ciphering 141b with subsequent messages 208 without module digital signature 405 in the series (where the subsequent messages 208 can optionally include an encrypted module identity 110a external to module encrypted data 403 for server 105 to select the appropriate symmetric key 127). Message 208 illustrated in Figure 6 can comprise a subsequent message 208 as described in the previous sentence. A series of messages 208 could begin when the initial message 208 is sent by module 101 and end when expiration time 133 of symmetric key 127 has transpired, and subsequently a new series of messages 208 could begin where the first message 208 in the new series of messages changes back to asymmetric ciphering 141a with initial message 208 that includes symmetric key 127 in a module encrypted data 403 (where the initial message 208 also includes a new module digital signature 405). An example of the initial message 208 described in this paragraph can comprise message 208 illustrated in Figure 6 of U.S. Patent Application Serial No. 14/039,401, filed September 27, 2013 in the name of John Nix, which is hereby incorporated by reference in its entirety. Other possibilities exist as well without departing from the scope of the present invention.

Using a message 208 with a module digital signature 405 can be both more efficient and overall more secure than digest authentication (such as the digest authentication described in IETF RFC 2069), although using digest-based authentication may be alternatively used. The use of a module digital signature 405 requires only a single packet for message 208 and a single packet for response 209 for secure communication between module 101 and server 105. Module encrypted data 403 illustrated in Figure 6 can be processed using the steps and algorithms described in Figure 4. Note that module encrypted data 403 as illustrated in Figure 6 is shown in a plaintext form for ease of illustration, but actual module encrypted data 403 within

Petitioner Samsung Ex-1004, 0111

body 602 of a packet 601a could be transmitted as binary, hexadecimal, Base64 binary-to-text encoding, or other encoding rules, and strings of the actual data within module encrypted data 403 would not normally be human readable.

In an exemplary embodiment, encryption by module 101 may optionally be omitted, and the server instruction 414 with corresponding data could be included within a message 208 without encryption within the body 602, such as if security could be maintained at the network level. As one example for this embodiment without encryption, server instruction 414 could be included in body 602 as plaintext. The encryption and/or security could be applied through other means, such as, but not limited to, the use of symmetric ciphering 141b such as AES 155 at the data-link layer, where packets transmitted through a wireless network 102 could be encrypted at the data-link layer, but after conversion to a network-layer message such as the exemplary datagram 601a illustrated in Figure 6, the datagram 601a could optionally omit encryption such as a module encrypted data 403.

Module encrypted data 403 can include a server instruction 414, a server identity 206, a module identity 110, a security token 401, a timestamp 604, and a sensor measurement 305. The server instruction 414 can represent the purpose of the message 208 for server 105, and Figure 6 illustrates an "update" for server instruction 414. An update for server instruction 414 could be used to periodically notify server 105 of regular, periodic sensor measurements 305 acquired by a sensor 101f or also data from a plurality of sensors. An update for server instruction 414 may also comprise a periodic report regarding monitored unit 119, and a server instruction 414 is described in Figure 4. Other server instructions 414 besides an "update" may be included in a module encrypted data 403 within a body 602. The "update" illustrated in message 208 in Figure 6 can also include a new symmetric key 127, and the module encrypted data 403 illustrated in Figure 6 may comprise the use of either an asymmetric ciphering 141a with public/private keys, or (ii) symmetric ciphering 141b with a symmetric key 127.

An initial transmission or negotiation of a symmetric key 127 may preferably utilize asymmetric ciphering 141a and the use of a public key as an encryption key and a private key as a decryption key. Subsequent transmission of a new symmetric key 127 may utilize either (i) a symmetric cipher 141b with a previously negotiated but still valid symmetric key 127 (i.e. expiration time 133 has not transpired), or (ii) asymmetric ciphering 141a. If the data within instruction 414 is longer than the maximum data length supported by a selected asymmetric ciphering algorithm 141a and the public/private key pair, then module encrypted data 403 within message 208 can be broken up into several sections, such that the data within each section is less than the maximum data length supported by the asymmetric ciphering algorithm 141a and key length. In an exemplary embodiment, a first symmetric key 127 can be used with module encrypted data 403 and a second symmetric key 127 can be used with server encrypted data 504. The first symmetric key 127

Petitioner Samsung Ex-1004, 0112

and second symmetric key 127 can be different, including using a first symmetric ciphering algorithm 141b with the first symmetric key and a second symmetric ciphering algorithm 141b with the second symmetric key 127. In another exemplary embodiment, in order to reduce the number of messages required to be transmitted and thus save power usage by a module 101, symmetric key 127 used with module encrypted data 403 and server encrypted data 504 can be the same and rotated periodically such, but not limited to, when expiration time 133 for a symmetric key 127 transpires.

Module identity 110 within module encrypted data 403 can represent the identity of module 110, and could represent a serial number read by module 101 from a read-only hardware address. Module identity 110 is described in Figure 1c and can represent a unique identifier of module 101. Module identity 110, such as an encrypted module identity 110a, outside module encrypted data 403 can represent a string or number that is different than a serial number that can be used by module 101 within a module encrypted data 403. Security token 401 within module encrypted data 403 can represent a random string in order to make message 208 reasonably unique and thus system 100 in Figure 2 and other systems illustrated herein robust against replay attacks. Security token 401 is described in Figure 5a. Timestamp 604 can represent a time value that module 101 sends message 208 or a time value that module 101 acquired sensor data 305. Sensor data 305 is described with the description of a sensor 101f in Figure 1c, and sensor data 305 can represent data module 101 acquires using sensor 101f. Sensor data 305 within message 208 may be stored by server 105 in a module database 105k, or potentially forwarded to another server such as, but not limited to, a module provider 109 for additional processing. Sensor data 305 can comprise a wide range of values for a sensor 101f besides the exemplary value of a temperature reading shown in Figure 6, including raw sensor data, compressed sensor data, and processed or averaged data. The specific sensor data 305 shown in Figure 6 is illustrated to be exemplary and not limiting for sending and receiving sensor data. Sensor data 305 may also be referred to as a sensor measurement 305.

Figure 6 also illustrates exemplary details within response 209 sent by server 105. Response 209 may comprise a TCP/UDP packet 601b sent from server 105 IP:port 207 the IP address 210 and port number 605, where IP address 210 represents the external IP address of wireless network firewall 104, if present, and port number 605 is the source port in message 208 as received by server 105 (i.e. the source port in message 208 after traversing the firewall 104 illustrated in Figure 6a). Thus, IP:port with IP address 210 and port number 605 in response 209 may be different than IP:port 204 in message 208, since the presence of a wireless network firewall 104 may perform NAT routing, which could change the source IP address and source port number from IP:port 204 to IP address 210 and port number 605 in message 208, as received by server 105. The use of wireless network firewall 104 in wireless network 102 may require that response 209 be sent from IP:port 207 to IP address 210 and port number 605 in order to be properly processed by firewall

Petitioner Samsung Ex-1004, 0113

104 and forwarded to module 101 at IP:port 204. Source IP:port 207 and destination IP address 210 and port number 605 in response 209 may be included within a header in TCP/UDP packet 601b, as illustrated in Figure 6. TCP/UDP packet 601b could comprise a regular UDP packet, a UDP Lite packet, or a TCP datagram, or similar protocols supported by an IP Network 107. TCP/UDP packets 601a and 601b may utilize the same protocol.

As noted previously, the use of checksums may be mandatory in IPv6 networks, and thus a response 209 comprising a packet 601b can include a checksum value 603 (illustrated in message 208 but not response 209) for the header. The use of firewalls such as firewall 104 can change the header values in a packet 601b. In accordance with a preferred exemplary embodiment, a first checksum value 603 within a response 209 sent by server 105 can be different and/or not equal to a second checksum value 603 within the response 209 received by module 101. Likewise, in an exemplary embodiment, a first checksum value 603 within a message 208 sent by a module 101 can be different and/or not equal to a second checksum value 603 within the message 208 received by server 105, potentially due to the presence of a firewall 104 or other router that performs network address translation, where the destination IP address within a response 209 sent by a server 105 is different than the IP address 204 of a module 101.

A UDP, TCP, or UDP Lite datagram as a TCP/UDP packet 601b within response 209 may include a body 606. Body 606 may comprise the payload or data within a UDP, TCP, or UDP Lite packet. Body 606 can include a server identity 206, a server digital signature 506 (not shown in Figure 6), server encrypted data 504, and channel coding 406. Server identity 206 is illustrated in Figure 6 as external to server encrypted data 504 within body 606, but server identity 206 may optionally be included in server encrypted data 504 instead. Module 101 may communicate with a plurality of servers 105, and server identity 206 as external to server encrypted data 504 can allow module 101 to select the appropriate symmetric key 127 to utilize for decrypting server encrypted data 504 (since each of the multiple servers 105 that module 101 communicates with may utilize a different symmetric key 127).

Also note that the server identity 206 can be similar to module identity 110, such that multiple different values for server identity 206 could be utilized in different systems illustrated herein, but each of the different values could preferably be uniquely associated with a server 105. As one example, server identity 206, outside server encrypted data 504 as illustrated in Figure 6, may comprise a session identity or session identifier, as opposed to a different server identity 206 that could comprise a hardware serial number or domain name for server 105. Thus, server identity 206 outside a server encrypted data 504 may be a different string or representation than server identity 206 within server encrypted data 504, but both strings/numbers used for server identity 206 in response 209 could be associated with server 105. In an exemplary embodiment, a set of servers 105n can collectively use a server identity 206.

Petitioner Samsung Ex-1004, 0114

Although not illustrated in Figure 6, a server digital signature 506 in body 606 can comprise a secure hash signature of a subset of body 606, where the subset of body 606 can comprise server encrypted data 504, and/or server identity 206 as illustrated in Figure 6. The use of a server digital signature 506 in a body 606 is illustrated in Figure 6 of U.S. Patent Application Serial No. 14/039,401, filed September 27, 2013 in the name of John Nix, which is hereby incorporated by reference in its entirety. In this manner, module 101 can utilize server digital signature 506 to authenticate that response 209 was sent by server 105. Channel coding 406 in body 606 is also depicted and described in connection with Figure 5 above. The server digital signature 506 may optionally be omitted as well.

Body 606 may include server encrypted data 504. Server encrypted data 504 is depicted and described in connection with Figure 5a above. Server encrypted data 504 may include an acknowledgement 501, wherein acknowledgement 501 can notify module 101 that message 208 has been received by server 105. As illustrated in Figure 6, server encrypted data 504 may optionally also include a module instruction 502 for module 101. The module instruction 502 could be a string that contains instructions or configuration parameters for module 101, such as an order to change state, parameters regarding the monitoring of monitored unit 119, server names or addresses, radio frequency parameters, timer values, settings for actuator 101y, etc. A module instruction 502 is depicted and described in connection with Figure 5a above. The exemplary module instruction 502 illustrated in Figure 6 comprises a "key generation" 608 instruction for module 101 derive a new set of keys, also depicted and described in connection with Figure 5b above at a step 515 or step 316.

In an embodiment where module 101 uses an eUICC 163, server encrypted data 504 could include a received eUICC profile 311. An example of a server 105 sending a server encrypted data 504 with a received eUICC profile 311 is depicted and described in connection with step 519 of Figure 5b. In an exemplary embodiment, the server 105 sending the received eUICC profile 311 can be different than a server 105 receiving sensor data 305. In these embodiments where the server 105 sending the received eUICC profile 311 is different than the server 105 receiving sensor data 305, module 101 can send the server 105 (possibly associated with or operated by an eUICC subscription manager 164) a message 208 before receiving the response 209 with the server encrypted data 504 containing the received eUICC profile 311. The message 208 to the server 105 operated by an eUICC subscription manager 164 could include a module digital signature 405 processed by a module 101 using the derived module private key 112 in a module PKI key pair 315. In this manner, the server 105 associated with the eUICC subscription manager 164 can verify the message 208 is sent by the correct and/or authenticated module 101 before sending the received eUICC profile 311 in a response 209. Note that a received eUICC profile 311 may be encrypted with a either (i) a symmetric ciphering algorithm 141b or an asymmetric ciphering algorithm 141a before encapsulation in a

Petitioner Samsung Ex-1004, 0115

message 208, and in this case the server encrypted data 504 for receiving the received eUICC profile 311 may optionally be omitted. In other words, the received eUICC profile 311 may not need additional encryption by a server 105 for transmission since the received eUICC profile 311 may already be encrypted.

Other possibilities for a module instruction 502 within a response 209 are possible as well without departing from the scope of the present invention. Although not depicted in Figure 6 or Figure 2, if response 209 includes a module instruction 502, according to an exemplary embodiment, module 101 can preferably send a second message 208 to server 105, where the second message 208 includes a confirmation that module instruction 502 was successfully executed or implemented by module 101. This confirmation could be included in a server instruction 414 for server 105 within a second message 208, and the confirmation could include a timestamp value 604 for when the module instruction 502 was executed. A timestamp value 604 may be useful for tracking time of actions and data collected, when a module 101 may only periodically have access to a network 102 and also may periodically be dormant or sleep.

Also, although a server encrypted data 504 may be included within a body 606 in exemplary embodiments, body 606 may optionally omit server encrypted data 504 and include data from server 105 or a set of servers 1010 (illustrated in Figure 10) that is not encrypted, such as, but not limited to, plaintext. As one example in this case, acknowledgement 501 could be included in body 606 as plaintext. Also, although not illustrated in Figure 6, server encrypted data 504 could include a symmetric key 127 for module 101 to utilize with symmetric ciphering 141b in cryptographic algorithms 141 for processing a module encrypted data 403 in subsequent messages 208 and/or responses 209. Server encrypted data 504 in a response 209 may include a security token 401. Security token 401 may be a random string and may also be generated by either server 105 or module 101. If security token 401 is generated by module 101, then security token 401 may be included in message 208 and also utilized by server 105 in response 209, as illustrated in Figure 6. Other possibilities exist as well without departing from the scope of the present invention.

Figure 7

Figure 7 is a flow chart illustrating exemplary steps for a module to derive a series of public keys and private keys, including sending and authenticating the derived public keys, in accordance with exemplary embodiments. In order to utilize communications secured with PKI techniques such as private keys, public keys, certificates, and identities, a module 101 may preferably obtain or generate the keys and certificate in a secure manner. Given that a plurality of modules 101 may be deployed in potentially remote places, without frequent contact with end users or technicians, the use of secure PKI techniques for a module 101 can create a significant set of challenges for the generation of module public key 111 and module private key 112, as

Petitioner Samsung Ex-1004, 0116

well as properly and securely obtaining a certificate 122 with an module identity 110. Using conventional technology, significant challenges and costs can be incurred when (i) module 101 has already been deployed, such as collecting data from a monitored unit 119, and (ii) module 101 needs to utilize either (a) a new set of module private key 112 and module public key 111 or (b) a new UICC card. In exemplary embodiments, a module 101 could implement steps within Figure 7 in order to utilize an eUICC 163 in order to connect with a wireless network 102. The use of an eUICC 163 for connecting with a wireless network 102 is optional, and the steps illustrated in Figure 7 can be conducted without the use of an eUICC 163.

The proper use of a new set of module private key 112 and module public key 111 may utilize the particular steps and procedures contemplated herein, in order to minimize any potential human intervention (with related costs) while continuing to maintain security. Over a long period of operating time for a module 101, such as a decade or longer, there may be many reasons module 101 may need a new pair of PKI keys, such as (i) expiration of a certificate, or the certificate of a parent signature authority, (ii) the transfer of ownership or control of module 101, where the prior ownership could have direct or indirect access to the module private key 112, (iii) supporting a new server 105 that has different security requirements or a different set of cryptographic parameters 126 (such as, but not limited to longer keys, different ECC curves, etc.), (iv) revocation of a public key in a chain of signatures 123 within a certificate 122, and/or (v) the use of a module PKI key pair 314 within network credentials 314 for activated eUICC profiles 313, where (a) the network credentials 314 are used to access a wireless network 102, and (b) module 101 may prefer to connect with multiple different wireless networks 102 over time using different network credentials 314. In the case of (ii), new ownership of module 101 may require a module 101 to utilize a new module private key 112. In the case of (iii) a new server 105 may require a pair of public/private keys incompatible with a prior set of public/private keys utilized by module 101 and/or a certificate 122 for module 101. For embodiments where module 101 and server 105 derive a new secret shared network key K 129d, module 101 may derive a new module private key 112 in order to derive the new secret shared network key K 129d for connecting with a different wireless network 102. Other possibilities exist as well for reasons a module 101 may need to derive a new module public key 111 and new module private key 112.

The general approach adopted by most mobile phone networks over the past two decades has been founded upon the use of a pre-shared secret key recorded in SIM cards and UICCs, such as the Ki secret key in 2G/3G networks and shared secret key K in 4G LTE networks. That approach may work for mobile phones, where the SIMs can often be easily replaced, but the use of a pre-shared secret key in a SIM may not be suitable for a module 101 and mobile network operator 108. As one example, significant costs may be incurred by swapping out a SIM card for already deployed modules 101, especially if they are in remote locations or continually moving such as a tracking device on a container or pallet, or a truck or automobile.

Petitioner Samsung Ex-1004, 0117

Next, a module 101 may preferably record multiple pairs of public/private keys 111/112 for various functions, such as connecting to different servers 105, connecting to different wireless networks 102, etc. The number of pairs of public/private keys useful to a module 101 concurrently could be many, such as an exemplary two or more actively used public/private keys. Trying to change or add a new SIM card each time a new security key is required may not be efficient or feasible. Figure 7 illustrates exemplary steps that can be performed with module 101, including using a module program 101i, for generating and/or updating a module public key 111 and module private key 112. The steps illustrated in Figure 7 include both (i) an "initial" or "startup" case where module 101 has not previously derived keys, and (ii) a subsequent or "follow on" time where module 101 can generate or derive keys after the initial derivation of keys. The steps illustrated for the derivation of new module PKI keys in Figure 7 can also be used for an eUICC 163.

At step 701, during manufacturing of module 101, including manufacturing of sub-components such as a circuit board or assembly of hardware components illustrated in Figure 1c, etc., a module identity 110 could be written into the hardware, and could comprise a serial number, International Mobile Equipment Identity (IMEI) number, Ethernet MAC address, etc. For security purposes, a module identity 110 may preferably be written into a read-only location, such as a readable location on a system bus 101d, which could also comprise a ROM 101c. The read-only location could also comprise a protected memory or protected address within module 101. A protected memory could also comprise a memory location within a ROM 101c. Recording and utilizing module identity 110 is also depicted and described in connection with Figure 1c, Figure 2, and elsewhere herein. Alternatively, module identity 101 could be recorded in a non-volatile memory such as a flash memory 101w. For embodiments where a module 101 utilizes an eUICC 163 in order to connect with a wireless network 102, the module identity 110 as depicted in Figure 7 can comprise a network module identity 110b, and the network module identity 110b does not need to be written to a read-only location in module 101, but rather can be written to a nonvolatile memory such as, but not limited to, a flash memory 101w.

At step 702, module 101 can be distributed to end users and also installed with a monitored unit 119. At step 703, parameters 126, and a server address 207 can be recorded in a nonvolatile memory 101w. Parameters 126 may comprise settings or values for a cryptographic algorithms 141 as illustrated in Figure 1d and Figure 1i, including (i) key lengths, (ii) algorithms to utilize for key generation or ciphering, such as the specification of an elliptic curve utilized illustrated as parameters 126 in Figure 1i, (iii) a specific secure hash algorithm 141c to utilize, such as SHA-256 or SHA-3, (iv) an expiration date of the public key 111, and/or (v) a maximum time value for an expiration time 133 associated with symmetric keys 127, etc. The parameters 126 in a step 703 could comprise either a first set of cryptographic parameters 126 or a first subset of cryptographic parameters 126a. Although not illustrated in Figure 7, at step 702 a configuration

Petitioner Samsung Ex-1004, 0118

file could also be loaded into non-volatile memory, where the configuration file includes a plurality of fields specifying the operation of module 101. The parameters 126, and server address 207 could be included in a configuration file.

Continuing at step 703, server name 206 could be utilized in place of or in addition to server address 207, and in this case module 101 can later perform a DNS or DNSSEC lookup using server identity 206 in order to obtain server address 207 for use in a message 208. Server address 207 (or server identity 206) could also be recorded in a ROM 101c at step 703. Step 703 may also be performed concurrently with step 701 or step 702. Note that step 703 may take place multiple times during the lifetime of a module 101, and in this case (a) the first time step 703 is conducted, step 703 could be conducted concurrent with steps 701 or 702, and (b) a subsequent time step 703 is conducted, step 703 could be conducted after the receipt of a response 209, where the response 209 includes a second server address 207, and also potentially a new module identity 110. In other words, although not illustrated in Figure 7, a module 101 could return to step 703 from later steps upon the equivalent of a "factory reset", or similar command where flash memory 101w and other nonvolatile memory would be cleared. One example could potentially be the transfer of ownership of module 101, or a second example could be the upload of new firmware that is incompatible with a previous configuration file.

Continuing at step 703, shared secret key 129 may comprise a shared secret key 129c or a pre-shared secret key 129a. Given that module 101 may not derive a private key until a step 515 illustrated below in Figure 7, a derived shared secret key 129b may not be available from a key derivation function 141f at step 702. A shared secret key 129c could be a value depicted and described in connection with Figure 1f. Shared secret key 129c can be calculated or processed using input of (i) a set of component parameters 101t and (ii) an algorithm token 190 into a shared secret algorithm 141g, where the output of shared secret algorithm 141g can be the shared secret key 129c. In an exemplary embodiment, shared secret key 129c may be calculated and determined by module 101 (i) without any prior communication with server 105 and also (ii) before module 101 receives a server public key 114. Although step 703 in Figure 7 illustrates module 101 as recording shared secret key 129 in a nonvolatile memory, module 101 could alternatively record shared secret key 129 (in the form of a key 129c or 129a) and algorithm token 190 in a volatile memory such as RAM 101e. For embodiments where the module 101 utilizes an eUICC 163 to connect with a wireless network 102, the recording of shared secret key 129 and related data in a step 703 can comprise recording a received eUICC profile 311. The shared secret key 129 can comprise a shared secret key 510 as depicted and described in connection with Figure 3b. In another emobidment, the shared secret key 129 in a step 703 could comprise the initial key K 325 recorded in a received eUICC profile 311, also depicted and described

Petitioner Samsung Ex-1004, 0119

in connection with Figure 3b. The first set of cryptographic parameters 126 and the server address 207 could also be recorded in the eUICC 163 in the form of a received eUICC profile 311.

In an exemplary embodiment, shared secret key 129 could be obtained and loaded by a distributor, installer, or end user into a nonvolatile memory such as flash memory 101w in the form of a pre-shared secret key 129a, where pre-shared secret key 129a was obtained using a module identity 110 and pre-shared secret key code 134 as depicted and described in connection with Figure 1c above. Module 101 could also utilize a first pre-shared secret key 129a, including a first pre-shared secret key 129a entered by potentially a distributor, installer, or end-user discussed in Figure 1c, to derive shared secret key 129. Other possibilities exist as well for shared secret key 129, and shared secret key 129 can be useful for either the authentication of module 101 and/or the proper identification of module 101 upon module 101's generation of a private key 112 and public key 111, as described below, including step 705. For embodiments where the module 101 utilizes an eUICC 163 to connect with a wireless network 102, an initial, received eUICC profile 311 could be loaded into a nonvolatile memory by a manufacturer, distributor, installer, or end-user, and the data for a step 703 could be recorded in the initial, received eUICC profile 311. Or, the module 101 could include both a UICC and an eUICC 163, and the module 101 could use the physical UICC to initially connect with a first wireless network 102, and subsequently use a received eUICC profile 311 and the eUICC 163 to connect with a second, subsequent wireless network 102.

In an exemplary embodiment, an initial module private key 112b and initial module public key 111b could be recorded into nonvolatile memory at step 703. For example, a manufacturer, distributor, installer, technician, or end-user could load the initial module private key 112b and initial module public key 111b, where the initial module public key 111b would be utilized to authenticate at step 705 a subsequent set of public/private keys derived by module 101 at step 704. In this case, the initial module public key 111b and/or initial module private key 112b described in the previous two sentences could comprise the shared secret key 129. One reason the initial module private key 112b with the initial module public key 111b could comprise a shared secret key 129 can be, if the initial module public key 111b and initial module private key 112b are present, (i) the initial module private key 112b and initial module public key 111b together have been "shared" in the sense that the initial module private key 112b has been located outside module 101 and in possession of an entity such as the manufacturer, distributor, installer, technician, or end-user in order to load the initial module private key (and initial module public key 111b is shared with server 105), (ii) the initial module private key 112b and initial module public key 111b can be used to authenticate a subsequent message 208 containing a public key internally derived by the module at step 704 below, and (iii) the initial module private key 112b would remain "secret" and not publicly shared. Thus, Figure 7 contemplates an

Petitioner Samsung Ex-1004, 0120

embodiment where shared secret key 129 at step 703 comprises an initial public/private key pair that is not internally derived by module 101.

Note that the contemplation of the use of shared secret key 129 as a pre-shared secret key 129a within the present invention may be different than the use of a pre-shared secret key within a SIM card. Specifically, as depicted and described in connection with Figure 1c and elsewhere herein, the shared secret key 129, comprising any of (i) a pre-shared secret key 129a, (ii) derived from a pre-shared secret key 129a, or (iii) a shared secret key 129c, may be moved by CPU 101b into a volatile memory such as RAM 101e, with subsequent access by cryptographic algorithms 141. In contrast, the pre-shared secret key within a SIM card or UICC for mobile phones is usually designed to prevent movement of the pre-shared secret key within a SIM or UICC into RAM 101e.

At step 704, module 101 can authenticate with a server 105 using the data from a nonvolatile memory recorded in step 703. In the embodiment where a module 101 uses an eUICC 163 to connect with a wireless network 102, the server 105 could be operated by a mobile network operator 108 and also could be associated with or reside in wireless network 102. In an exemplary embodiment, a module 101 can be distributed or installed between steps 703 and steps 704. In order to perform 2-way authentication at a step 704, module 101 can read module identity 110 using a read-only address or a protected address. Module 101 can read module identity 110 directly from read-only hardware address by using system bus 101d, including from a ROM 101c, or module 101 can read module identity 110 from a nonvolatile memory such as a flash memory 101w. Thus, the read-only address or protected address could comprise an address accessible on system bus 101d that is designated read-only for a period of time.

As contemplated herein, a protected address can comprise an address or a memory location that can be read-only (i) for a period of time and/or (ii) upon an elevated set of privileges not normally used in the operation of a module 101. The module identity 110 used in a step 704 for authentication could be recorded into a flash memory 101w by module 110 after a prior read of module identity 110 from a read-only address or a protected address. In this case (module 101 taking the step described in the previous sentence), reading module identity 110 from the nonvolatile memory at step 704 can also comprise module 101 reading module identity 110 using a read-only address or a protected address. Thus, although module 101 may read module identity 110 from a flash memory 101w, if (a) module 101 initially utilized a read-only address to record the module identity 110 into the flash memory 101w, then (b) reading module identity 110 from the flash memory 101w would comprise using a read-only address to read module identity 110. Other possibilities exist as well, such as the address that includes module identity 110 in either (i) a nonvolatile memory such as a ROM 101c or (ii) an address accessible on system bus 101d, could be designated for a period of time as available for a read-only or protected operations.

Petitioner Samsung Ex-1004, 0121

Note that using a module identity 110 from a read-only address or a protected address within module 101 can be important for the use of an eUICC 163. The module identity 110, possibly in the form of a hardware serial number or IMEI, can serve as the basis for an identifier or identity of module 101 with an eUICC subscription manager 164, since a network module identity 110b can change for the same module 101 over time as different received eUICC profiles 311 can be activated with different network module identities 110b. In other words, a module 101 can use the module identity 110 in order to receive a received eUICC profile 311 from an eUICC subscription manager 164 instead of, or in addition to, a network module identity 110b from the eUICC subscription manager 164 since a network module identity 110b can change for a module 101 over time when using an eUICC 163.

Continuing at step 704, module 101 can take steps to conduct a 2-way authentication with server 105. In order for module 101 to authenticate with server 105, module 101 can send a message 208 with a module identity 110 to the server address 207, which could belong to a server 105. In an exemplary embodiment, module identity 110 at a step 704, or any step where module 101 authenticates or verifies identity with a server 105, can comprise the form of an encrypted module identity 110a using a secret ciphering algorithm 141h as depicted and described in connection with Figure 1g. In this case, the message 208 with an encrypted module identity 110a would also preferably include the algorithm token 190 used by module 101 to derive the encrypted module identity 110. The server could extract the plaintext module identity 110 using a secret ciphering algorithm deciphering 162. Alternatively, the module identity 110 could be sent as plaintext in a step 704. In order to authenticate module 101 with module identity 110 at step 704, server 105 can utilize the shared secret key 129 to authenticate module 101 at step 704, such that after authentication, the contents of message 208 or additional messages 208 from module 101 can be further processed.

For embodiments where the module 101 utilizes an eUICC 163 to connect with a wireless network 102, the 2-way authentication using shared secret key 129 at a step 704 could comprise module 101 conducting a 2-way authentication with a server 105 associated with a subscription manager 164. The shared secret key 129 and related data in a step 704 could be read from a received eUICC profile 311. The shared secret key 129 can comprise a shared secret key 510 within a received eUICC profile 311. For embodiments where the module 101 utilizes an eUICC 163 to connect with a wireless network 102, the 2-way authentication could be conducted with an initial key K 325 in a step 704 using the standard 2-way authentication for an LTE and related networks where the wireless network 102 sends a RAND and AUTN, and module 101 sends a RES. In this case, the shared secret key 129 could comprise the initial key K 325.

Continuing at step 704, server 105 can authenticate module 101 using the module identity 110 in message 208 and a message digest, such as described in IETF RFC 2617, titled "HTTP Authentication: Basic and Digest Access Authentication". Other reasonably secure authentications techniques using a shared secret

Petitioner Samsung Ex-1004, 0122

key 129 could be utilized without departing from the scope of the present invention. In order to authenticate, module 101 could take steps to demonstrate to server 105 that module 101 holds the same shared secret key 129. Module 101 can properly respond to a challenge/nonce in a message digest authentication by sending a secure hash value calculated using (i) the challenge/nonce and (ii) the shared secret key 129. Or, module 101 could authenticate by generating a module digital signature 405 in message 208 using the shared secret key 129. In addition, module 101 could utilize the shared secret key 129 as a symmetric key 127 to encrypt a module encrypted data 403 with symmetric ciphering 141b, and if server 105 could properly decrypt the module encrypted data 403 using the same shared secret key 129 on the server, then server 105 would know the correct module 101 sent the message 208 and thereby would be authenticated. Other possibilities exist as well for a module 101 to authenticate with a server 105 using a shared secret key 129, or a shared secret key 510 or an initial key K 325 in the case where module 101 uses an eUICC 163 to connect with a wireless network 102, without departing from the scope of the present invention.

Continuing at step 704, module 101 can also preferably authenticate server 105 in order to complete a 2-way authentication. Module 101 can take steps to ensure or verify that server 105 with reasonable assurance also holds the shared secret key 129, or a shared secret key 510 or an initial key K 325 in the case where module 101 uses an eUICC 163 to connect with a wireless network 102. Module 101 could authenticate server 105 using message digest, such that module 101 issues a challenge/nonce, and verifying that server 105 properly responds to the challenge/nonce with a correct secure hash value, such as the output from a secure hash algorithms 141c. Or, server 105 could authenticate with module 101 by the module receiving a server digital signature 506 in a response 209 using the shared secret key 129. In addition, module 101 could utilize the shared secret key 129 as a symmetric key 127 to decrypt a received server encrypted data 504 with symmetric ciphering 141b, and if module 101 could properly decrypt the server encrypted data 504 using the shared secret key 129, then module 101 would know the correct server 105 sent the response 208 and thereby the server 105 would be authenticated. Other possibilities exist as well for a server 105 to authenticate with a module 101 using a shared secret key 129 without departing from the scope of the present invention.

Continuing at step 704, module 101 can receive a set of cryptographic parameters 126, preferably after module 101 completes authentication with server 105 (in order for server 105 to not send the set of cryptographic parameters 126 to 3rd parties). A set of cryptographic parameters 126 received in a step 704 can also comprise a second set of cryptographic parameters 126, where the second set of cryptographic parameters 126 could be different or the same as the first set of cryptographic parameters 126 from a step 703. The second set of cryptographic parameters 126 at a step 704 can comprise a subset of cryptographic parameters 126a as depicted and described in connection with Figure 1i. Module 101 could send the set of

Petitioner Samsung Ex-1004, 0123

cryptographic parameters 126 recorded in step 703 to the server 105, and the server 105 could respond with a subset of cryptographic parameters 126a. In another embodiment, server 105 could send module 101 the second set of cryptographic parameters 126 at step 704, and module 101 could send a subset of the cryptographic parameters 126a to the server. In embodiments where module 101 uses an eUICC 163, receiving the second set of cryptographic parameters 126 at a step 704 could comprise receiving a received eUICC profile 311 that includes the second set of cryptographic parameters 126.

At the conclusion of step 704 the module 101 and server 105 can preferably agree on a set of cryptographic parameters 126 for use with cryptographic algorithms 141 for further communication. Note that a module 101 and a server 105 can communicate a set of cryptographic parameters 126 by using a set of cryptographic parameters token 126c, such that a packet transmitted could contain the token 126c as an identifier for a set of cryptographic parameters 126. For example, a module 101 could send or receive the token 126c with an exemplary value of "Set A" illustrated in Figure 1i, instead of sending or receiving the complete set of cryptographic parameters 126. In an exemplary embodiment, the transmission of cryptographic parameters 126 or a token 126c at a step 704 comprises encrypting the cryptographic parameters with shared secret key 129 as a symmetric ciphering key 127 in a symmetric ciphering algorithm 141b. Note that receiving a second set of cryptographic parameters 126 could optionally be omitted from a step 704, and in this case the first set of cryptographic parameters 126 or subset of cryptographic parameters 126a from a step 703 could be used by a module 101 in a subsequent step 515 or a step 316 below in Figure 7. In embodiments where module 101 uses an eUICC 163, the second set of cryptographic parameters in a step 704 could comprise the set of cryptographic parameters 126 within a received eUICC profile 311, and a module 101 could receive the second set of cryptographic parameters 126 using a system bus 101d. In other words, when a module 101 is depicted in Figure 7 and other Figures herein as receiving data, exemplary embodiments contemplate that a CPU 101b within module 101 receiving the data using a system bus 101d, and thus the received data could also be locally stored or recorded within a module 101.

The module 101 can send cryptographic parameters 126 from step 703 in a module encrypted data 403 and the module 101 can receive cryptographic parameters 126 from the server in a server encrypted data 504. In this manner, module 101 can securely communicate cryptographic parameters 126 without first deriving a module public key 111 and module private key 112. An agreed subset of cryptographic parameters 126a as illustrated in Figure 1i may be necessary for module 101 to derive a compatible module public key 111 for the server 105. A system 100 and other systems illustrated herein can be flexible for supporting a wide range of modules 101 and servers 105, while remaining reasonably secure, by both (i) encrypting proposed cryptographic parameters 126 using the shared secret key 129 and (ii) agreeing on a subset of cryptographic parameters 126a as illustrated in Figure 1i.

Petitioner Samsung Ex-1004, 0124

After step 704, module 101 can then derive a first module public key 111 and a first module private key 112 pair, and record the values in a memory, which could comprise a nonvolatile memory such as flash memory 101w. In this manner, the key pair can be available to module 101 upon recovery from lost power. A module 101 could use (i) a step 515 depicted and described in connection with Figure 5b or, (ii) a step 316 depicted and described in connection with Figure 3b and Figure 5b in order to derive the key pair, and could also use the second set of cryptographic parameters 126 obtained through a step 704 above (which could comprise a subset of cryptographic parameters 126a). In embodiments where a module 101 uses an eUICC 163 to connect with a wireless network 102, a profile activation step 316 can be used in Figure 7 to populate or record a derived module PKI key pair 315 within an activated MNO network credentials 314 for an activated eUICC profile 313. At step 515, or a step 316 in Figure 7 for embodiments where a module 101 uses an eUICC profile 313, module 101 can derive module private key 112 and a corresponding module public key 111 using (i) random number generator 128, (ii) the second set of cryptographic parameters 126 or the second subset of cryptographic parameters 126a from a step 704, (iii) cryptographic algorithms 141, and (iv) a key pair generation algorithm 141e. In an embodiment where the set of cryptographic parameters 126 are omitted from a step 704, then (i) in a step 515 in Figure 7 module 101 could use the first set of cryptographic parameters 126 from step 703, or (ii) in a step 316 in Figure 7 module 101 could use the set of cryptographic parameters 126 recorded in the activated eUICC profile 313, which could also comprise the same or equivalent set of cryptographic parameters 126 recorded in the received eUICC profile 311. The set of cryptographic parameters 126 recorded in the activated eUICC profile 313 could also comprise a subset of cryptographic parameters 126a as illustrated in Figure 1i.

Module private key 112 and corresponding module public key 111 can be derived in a step 515 or a step 316 according to a wide range of parameters 126, and can be selected from different algorithms, such as RSA 153 or ECC 154. Key derivation at step 515 could generate keys of different lengths, such as 2048 bits with RSA 153 or 283 bits with ECC 154, and other possibilities exist as well. If using ECC 154 to derive a pair of keys for module 101, a step 515 or a step 316 in Figure 7 could also accommodate the use of different elliptic curves for compatibility with server 105, such as the use of odd-characteristic curves, Koblitz curves, etc. Additional example elliptic curves utilized in the generation or derivation of a key pair include the curves sect283k1, sect283r1, sect409k1, sect409r1, etc., which are identified as example curves in IETF RFC 5480, titled "Elliptic Curve Cryptography Subject Public Key Information".

The ECC curve for a derived module public key 111 and module private key 112 can be specified in a subset of cryptographic parameters 126a from a step 704. Consequently, the parameters of keys generated by module 101 at a step 515 (including key length or algorithms utilized) may be selected based upon the requirements of the application and can be included in a set of cryptographic parameters 126. When deriving

Petitioner Samsung Ex-1004, 0125

keys at a step 515 or a step 316, in an exemplary embodiment module 101 may also preferably utilize data from sensor 101f, radio 101z, a bus 101d, a physical interface 101a, memory 101e, and/or a clock 160 in order to generate a seed 128b for random number generator 128, or random number generator 128 could utilize these inputs directly. A random number can be input into key pair generation algorithm 141e in order to derive the module public key 111 and module public key 112 (with normally the module private key 112 being derived first with a key pair generation algorithm 141e). Since a module 101 may utilize a plurality of module 101 PKI key pairs during its lifetime, including the possibility of using multiple module private keys 112 concurrently, such as using different module private keys 112 for different purposes, in exemplary embodiments module 101 can also derive a module public key identity 111a for module public key 111 at a step 515 or a step 316 in Figure 7. At subsequent steps where module 101 sends the module public key 111, the module 101 can also send the module public key identity 111a. In this manner, module 101 and a server 105 can properly track which module public key 111 is being used for any given set of communications with module 101 using PKI.

Upon key derivation at step 515 of Figure 7, or a profile activation step 316 for embodiments where a module 101 uses an eUICC to connect with a wireless network 102, module private key 112 and module public key 111 can be recorded in a nonvolatile memory 101w. In an exemplary embodiment, module private key 112 is preferably not transmitted or sent outside module 101. Note that module 101's internal derivation, or processing or creation, of module private key 112 and corresponding module public key 111 can have many benefits. First, module private key 112 does not need to be recorded in any other location than within module 101, and thus may also be considered not shared. Recording module private key 112 only within module 101 avoids potential security risks of (i) storing or recording module private key 112 in other locations, such as with module provider 109, mobile network operator 108, or an installer or end user of module 101, and (ii) transferring module private key 112 from these other locations. A primary security risk from storage of module private key 112 outside module 101 is that unauthorized 3rd parties may gain access to the module private key 112.

For embodiments where a module 101 uses an eUICC 163 to connect with a wireless network 102, the derivation of a module PKI key pair in a step 316 can benefit a mobile network operator, since a module private key 112, which can serve as the foundation for subsequent communications with a wireless network 102, does not depend on the transmission of a module private key 112 through 3rd parties. In exemplary embodiments where a module 101 uses an eUICC 163 to connect with a wireless network 102, module private key 112 can be derived at other times besides during a profile activation 316 step, but the result of obtaining an activated eUICC profile 313 can include steps associated with a profile activation step 316 such

Petitioner Samsung Ex-1004, 0126

that an activated MNO network credentials 314 includes a module PKI key pair 315 that has been derived by a module 101.

Also note that over a potential lifetime of a decade or more of operation of module 101, each time a new module private key 112 may be required (for various potential reasons outlined above, including the use of new activated eUICC profiles 313 in embodiments where a module 101 uses an eUICC 163 to connect with a wireless network 102), the external recording and/or transferring of module private key 112 incurs a potential security risk. Security risks can be compounded if the external location records private keys 112 for a plurality of modules 101. Also, by internally generating private key 112 at a step 515 or a step 316, module 101 can overcome significant limitations and costs requiring the distribution of a pre-shared secret key Ki or K in the form of a SIM card or similar physical distribution of a pre-shared secret key.

At step 705, module 101 can send the module public key 111, and the module public key 111 could be sent to a server 105 in a message 208 that includes a module identity 110. In embodiments where a module 101 uses an eUICC 163 to connect with a wireless network 102, a module 101 can send the module public key 111 to a server 105 associated with the wireless network 102 in a step 705. The module 101 can also send the module public key identity 111a with the module public key 111 in a step 705. In an embodiment, the module 101 can send the module public key 111 to a server different than server 105 used in a step 704, and the different server could be a server associated with a certificate authority 118 an mobile network operator 108, or a subscription manager 164 if an eUICC 163 is used by module 101 to connect with a wireless network 102. The module identity 110 could be in the form of an encrypted module identity 110a, or a network module identity 110b in embodiments where a module 101 uses an eUICC 163. The module public key 111 could be sent either as plaintext or within a module encrypted data 403, where the shared secret key 129, or shared secret key 510 in embodiments where module 101 uses an eUICC 163, could be used as a symmetric key 127 with a symmetric ciphering algorithm 141b. By sending the module public key 111 in a module encrypted data 403, a system 100 and other systems contemplated herein may be kept more secure, since other nodes besides server 105 would not be able to (i) read the module public key 111 or (ii) use the module public key 111 for sending module 101 unauthorized or fraudulent server encrypted data 504 with an asymmetric ciphering algorithm 141a and the module public key 111.

Although not illustrated in Figure 7, at step 705 server 105 could authenticate message 208 at step 705 that includes the module public key 111 in order to ensure that module public key 111 is properly associated with module identity 110 and that module public key 111 is not fraudulently submitted by another node or module 101 attempting to send the data. In an exemplary embodiment, at step 705 module 101 could use the steps for authentication of the message 208 containing module public key 111 using the authentication from a step 704. In an exemplary embodiment, module 101 could perform steps to

Petitioner Samsung Ex-1004, 0127

authenticate with a server depicted and described in connection with step 1202 of Figure 12 in U.S. Patent Application Serial No. 14/064,618, filed October 28, 2013 in the name of John Nix. Or, if module 101 sends module public key 111 in a step 705 at a sufficiently short period of time after step 704, such as, but not limited to, less than an exemplary minute after step 704, then the previous authentication from step 704 may still be applicable. In this case, the authentication of module 101 at a step 705 could comprise the authentication of module 101 from the prior step 704. Other possibilities exist as well without departing from the scope of the present invention for a module 101 to securely send a derived module public key 111 to a server 105 in a step 705.

At step 706, module, module 101 can begin utilizing the new module public key 111 and module private key 112 derived in a step 515 or a step 316 in Figure 7, where new public key 111 was sent to a server 105 and authenticated in Step 705. In exemplary embodiments where module 101 uses an eUICC 163, before step 706 module 101 could also take the additional steps depicted and described in connection with Figure 9b below in order to obtain a secret shared network key K 129d for communication with wireless network 102. In exemplary embodiments where module 101 communicates with a server 105 independently of an eUICC 163 (other than possibly using an eUICC 163 to obtain access to IP Network 107), then the additional steps illustrated in Figure 9b to obtain a secure key K may be optionally omitted.

At a step 706, module 101 could begin following normal operations of a data reporting steps 101x illustrated in Figure 3. At step 706, module 101 can send a module encrypted data 403, where the module encrypted data 403 could include either (i) a symmetric key 127 ciphered with an asymmetric ciphering algorithm 141a and the server public key 114, or (ii) a server instruction 414 that could include a sensor measurement 305 or other data. If module encrypted data 403 at step 706 includes a server instruction 414, such as, but not limited to, an exemplary server instruction 414 depicted and described in connection with Figure 6, then module 101 could send or receive a symmetric key 127 before step 706 and cipher data in the module encrypted data using the symmetric key 127. Although not illustrated at step 706, module 101 can also send a module identity 110, an encrypted module identity 110a, or a network module identity 110b at a step 706. If module encrypted data 403 at step 706 includes data encrypted with an asymmetric ciphering algorithm 141a, the module 101 may also send a module digital signature 405 at a step 706.

At step 707, module 101 can receive a response 209, where the response 209 includes server encrypted data 504, and the server encrypted data 504 can include a module instruction 502. In this step 707 a server 105 can utilize the new module public key 111, resulting from the key generation by module 101 in a step 515 above in Figure 7, to encrypt server encrypted data 504 in one of two ways. First, server 105 can encrypt server encrypted data 504 using an asymmetric ciphering algorithm 141a by ciphering with the new module public key 111. Second, server 105 can encrypt server encrypted data 504 using a symmetric

Petitioner Samsung Ex-1004, 0128

ciphering algorithm 141b by utilizing a key derivation function 141f including steps for ECDH 159 and (i) the new module public key 111 and (ii) the server public key 114 in order to derive a commonly shared symmetric key 127, which could comprise a derived shared secret key 129b. In this second instance, module 101 can decrypt server encrypted data 504 in step 707 using a symmetric ciphering algorithm 141b and the commonly shared symmetric key 127 comprising a derived shared secret key 129b. Module instruction 502 at a step 707 could comprise an "acknowledgement" that a message 208 sent in a step 706 was properly received. Other possibilities exist as well for a module 101 to receive and process a server encrypted data 504 with a module instruction 502 in a step 707.

At step 708, module 101 or server 105 can determine or evaluate if a new module private key 112 and module public key 111 are required for continued operation. Another node associated with mobile network operator 108 besides server 105 could also determine if the use of new PKI keys are desirable in a step 708. Exemplary reasons for the generation of new keys by a module 101 were described at the beginning to this Figure 7. One reason could be the expiration of a certificate 122 for module 101, or equivalently the expiration of a time-to-live value for a module public key 111 if module public key 111 is not recorded in the form of a certificate 122. A second exemplary reason could be that module 101 may wish to connect with a new wireless network 102 that requires the use of PKI techniques for authentication, but also a different set of cryptographic parameters 126 or algorithms in order for module 101 to communicate through a new wireless network 102. In an exemplary embodiment, a set of cryptographic parameters 126 for a server 105 may change or be different than with a previous server 105, such as, but not limited to, (i) using a different elliptic curve or a different set of asymmetric ciphering algorithms 141a, or (ii) requiring longer key lengths. Module 101 may need to derive at a step 708 a new set of a compatible module public key 111 with a corresponding module private key 112. A third exemplary reason could be that module 101 prefers to use a different received eUICC profile 311 in order to connect with a different wireless network 102 than the wireless network 102 utilized for communication in a step 705 or step 706.

Other examples for reasons that a module 101 may need new public/private keys after installation with a monitored unit 119 exist as well, and any could be a reason for module 101 to determine to utilize new public/private keys. If module 101 and/or a server 105 determine that new keys are not required at step 708, module 101 can then proceed to a step 309 and wait for a specified interval before taking further action. As illustrated in Figure 7, the further action could comprise returning to a step 706 and the module could continue to periodically report data regarding a monitored unit 119 in the form of periodically sending a message 208 to server 105, and the message 208 could contain a sensor data 305, or other data for the remote monitoring and/or control of a monitored unit 119. In an exemplary embodiment, the determination at a step 708 could be made at other times as well, such as before a step 707 or a step 706.

Petitioner Samsung Ex-1004, 0129

Either a module 101 or a server 105 could determine if the use of new module 101 PKI keys are preferred or desirable in a step 708. As contemplated herein, the term "PKI keys" can refer to a pair of keys comprising a module public key 111 and a module private key 112. In the embodiment where a server 105 or another node associated with mobile network operator 108 determines or evaluates that the use of new module 101 PKI keys are preferred or required in a step 708, then at a step 607 a server 105 could send a signal to module 101 to derive new PKI keys. An exemplary signal for module 101 to derive new PKI keys in a step 607 could be in the form of an exemplary response 209 illustrated in Figure 6, where the response 209 includes a module instruction 502 of "derive new PKI key pair". If a module 101 determines on its own (i.e. without receiving a signal from a server 105 for deriving new keys), then step 607 may be omitted, and otherwise a step 607 can otherwise be useful or required in order to signal that a module 101 should derive new PKI keys. In an exemplary embodiment, a step 607 may require sending the module instruction 502 of "derive new PKI key pair" within a response 209, where module 101 may previously have sent a message 208. The reason can be that a module 101 may operate behind a firewall 104 or periodically sleep, and in this case a server 105 may not be able to send a module 101 the module instruction 502 at arbitrary times, but must wait until after module 101 first sends a message 208 before sending the module instruction 502 of "derive new PKI key pair" in a response 209.

A step 607 can also comprise a module 101 receiving a third set of cryptographic parameters 126 or a subset of cryptographic parameters 126a. A third set of cryptographic parameters 126 or a subset of cryptographic parameters 126a can also be optionally omitted from a step 607 and in this embodiment a prior set of cryptographic parameters 126 or a subset of cryptographic parameters 126a, such as the parameters 126 (i) received by a module 101 in a step 704 above, or (ii) initially recorded in a step 703 could apply. In a step 607 a module 101 can send a set of cryptographic parameters 126 and receive a third subset of cryptographic parameters 126a. Or, a module can receive a third set of cryptographic parameters 126 and send a subset of cryptographic parameters 126a. The subset of cryptographic parameters 126a could comprise a (i) single value such as specifying a named curve within an ECC standard curve 138, a modulus to use with an RSA algorithm 153, or a time value for a new module public key 112, or (ii) multiple values such as two or more selected from an exemplary subset of cryptographic parameters 126a illustrated in Figure 1i. Note that in a step 607 the module instruction 502 of "derive new PKI key pair" or a similar signal could be received by a module 101 in a separate packet than either a set of cryptographic parameters 126 or a subset of cryptographic parameters 126a.

In addition, in a step 607 the module instruction 502 of "derive new PKI key pair" or a similar signal could be received by a module 101 either as plaintext in a packet or within a server encrypted data 504. Further, in a step 607 the third set of cryptographic parameters 126 or the subset of cryptographic parameters

Petitioner Samsung Ex-1004, 0130

126a could be received by a module 101 either as plaintext in a packet or within a server encrypted data 504. As illustrated in Figure 7, the set of cryptographic parameters 126 or the subset of cryptographic parameters 126a could comprise a 3rd set of cryptographic parameters 126, and the 3rd set of cryptographic parameters 126 may be the same or different than a 2nd set of cryptographic parameters 126 received in a step 704. In an exemplary embodiment, a step 607 comprises receiving the third set of cryptographic parameters 126 and a module instruction 502 in the form of a received eUICC profile 311 for an eUICC 163. The data received by module 101 at a step 607 in Figure 7 could include a second received eUICC profile 311, for embodiments where a module 101 uses an eUICC 163 to connect with a wireless network 102, where the second received eUICC profile 311 can be different than a first eUICC profile 311 used in a step 316 in Figure 7.

At step 709 the module 101 can use the third set of cryptographic parameters 126 received in a step 607 to derive a second module private key 112 and a second module public key 111. Module 101 could use a step 515 or a step 316 in order to derive the second module private key 112 and second module public key 111 at a step 709. In embodiments where a module 101 uses an eUICC 163 to connect with a wireless network 102, a step 709 could comprise module 101 deriving a second module PKI key pair 315 for use in a second activated MNO network credentials 314 (different from the first set of activated MNO network credentials 314 from a step 316 above in Figure 7), and the third set of cryptographic parameters 126 in a step 709 could comprise the set of cryptographic parameters 126 received in the received eUICC profile 311 from a step 607 above. In other embodiments, the use of an eUICC 163 by module 101 is not required in a step 709, and a step 709 to derive new module PKI keys can be independent of the presence or use of an eUICC 163. In other words, a module 101 and a server 105 can use some embodiments of the present invention illustrated in Figure 7 and other Figures herein independently of the presence of an eUICC 163 and related profiles, while other embodiments may use an eUICC 163 and related profiles.

At step 709, module 101 can derive the second module private key 112 and a corresponding second module public key 111 using (i) random number generator 128, (ii) the third set of cryptographic parameters 126 or the third subset of cryptographic parameters 126a from a step 607, (iii) cryptographic algorithms 141, and (iv) a key pair generation algorithm 141e. In an embodiment where the second set of cryptographic parameters 126 are omitted from a step 607, then in a step 709 module 101 could use either (i) the first set of cryptographic parameters 126 from step 703 or (ii) the second set of cryptographic parameters 126 or 126a from a step 704. In a step 709 a module 101 can also derive and a assign a module public key identity 111a to be associated with the second module public key 111, where the module public key identity 111a can be used to identify and select the second module public key 111 from a first module public key 111 potentially from a step 515 above. In other words, a second module public key 111 can be associated with a second

Petitioner Samsung Ex-1004, 0131

module public key identity 111a and a first module public key identity can be associated with a first module public key identity 111.

According to the set of cryptographic parameters 126 or 126a used in a step 709, in an exemplary embodiment the module PKI keys derived in a step 709 can be associated with a different asymmetric ciphering algorithm 141a than the module PKI keys derived in a step 515 or a step 316 in Figure 7. For example, the first module PKI keys in a step 515 or step 316 in Figure 7 could utilize a first ECC standard curve 138, while the second module PKI keys in a step 709 could use a second ECC standard curve 138. Or, the first module PKI keys in a step 515 or a step 316 in Figure 7 could utilize an RSA algorithm 153, while the second module PKI keys in a step 709 could use an ECC algorithm 154. In another embodiment at step 709, the first module PKI keys in a step 515 or step 316 in Figure 7 could utilize an RSA algorithm 153 with a shorter key length, such as, but not limited to, an exemplary 1024 bits, while the second module PKI keys in a step 709 could use an RSA algorithm 153 with a longer key length such as, but not limited to, an exemplary 2048 bits. Further, the first module PKI keys in a step 515 or step 316 in Figure 7 and the second module PKI keys in a step 709 could use the same algorithm and key length. Other possibilities for differences or similarities between the first module PKI keys in a step 515 or step 316 and the second module PKI keys in a step 709 are possible as well without departing from the scope of the present invention.

After deriving the second module PKI keys in a step 709, at step 710 the module 101 can send the second module public key 111 with the module identity 110 to a server 105. In embodiments where a module 101 uses an eUICC 163 to connect with a wireless network 102, the module 101 can send the second module public key 111 associated with an activated eUICC profile 313 with the network module identity 110b to a server 105 associated with (i) wireless network 102 and/or (ii) subscription manager 164. In exemplary embodiments, the second module public key 111 can be sent with the second module public key identity 111a. The module 101 can send the data in a message 208. In an exemplary embodiment the module 101 can send (i) the second module public key 111 and a module identity 110, and (ii) authenticate or verify data sent by module 101 in a step 710 using the first module private key 112 from a step 515 or a step 316 in Figure 7. The authentication or verification of data sent by module 101 in a step 710 could comprise verifying or authenticating data sent with the second module public key 111, such as verifying or authenticating module identity 110 or a network module identity 110b. Or the authentication or verification of data sent by module 101 in a step 710 could comprise verifying or authenticating the second module public key 111, and other possibilities exist for a module 101 to send the second module public key in an authoritative manner.

In an exemplary embodiment, in a step 710 the module 101 can use the first module private key 112 to verify or authenticate the second module public key 111 sent using at least one of several sub-steps. The

Petitioner Samsung Ex-1004, 0132

sub-steps at a step 710 to verify the second module public key 111 using the first module private key 112 could comprise any of (i) sending the second module public key 111 and a module identity 110 with or in a module encrypted data 403 that uses a symmetric ciphering algorithm 141b, where the symmetric key 127 for encrypting and decrypting the module encrypted data 403 at step 710 could previously be communicated before step 710 using the first module private key 112 (such as, but not limited to, a module 101 receiving the symmetric key 127 from a server 105 in a server encrypted data 504, where the server encrypted data 504 was deciphered with an asymmetric ciphering algorithm 141a and the first module private key 112), (ii) sending the second module public key 111 and module identity 110 with a module digital signature 405 where the module digital signature 405 is calculated or processed by module 101 using the first module private key 112 from a step 515 in Figure 7, (iii) using a derived shared secret key 129b with a message digest authentication for verifying a sent message 208 with the second module public key 111 at step 710, where the derived shared secret key 129b was processed using a key derivation function 141f and the first module private key 112, and/or (iv) using a derived shared secret key 129b as a symmetric key 127 for encrypting data sent with the second module public key 111, where the derived shared secret key 129b was processed using a key derivation function 141f and the first module private key 112.

Other possibilities exist as well without departing from the scope of the present invention for using the first module private key 112 from a step 515 or a step 316 in order for a module 101 to verify or authenticate data sent with the second module public key 111 at a step 710. As illustrated in Figure 7, after step 710, the module 101 can return to a step 706 and continue regular operation such as, but not limited to, collecting sensor data 305 and sending the data periodically in a module encrypted data 403. In embodiments where a module 101 uses an eUICC 163, module 101 could send and receive application data with a second wireless network 102 after completing step 710. Upon returning to step 706, the module encrypted data 403 could use the second module PKI keys derived in a step 709. In embodiments where module 101 returns to step 706, depicted values for subsequent steps could increment, such upon returning to step 709 for a second time, then the depicted values for "second module public key" and "3rd parameters" could become "third module public key" and "4th parameters" at the second iteration of step 709, etc.

Benefits of using the first module private key 112 in authentication of the second module public key 111 at a step 710 include a server 105 could use the first module public key 111 received by server 105 in a step 705 in order to authenticate or verify the correct module 101 sends the second module public key 111. In addition, module 101 may communicate with a plurality of servers 105, including servers from different mobile network operators 108 over time. The plurality of servers 105 could share the first module public key 111 such that when a step 710 occurs, module 101 may send the second module public key 111 and module identity 110 to a different server 105 than the server 105 from a step 705 or step 706. In embodiments where

Petitioner Samsung Ex-1004, 0133

a module 101 uses an eUICC 163 in order to connect with a wireless network 102, either (i) different wireless networks 102 or (ii) an eUICC subscription manager 164 could share the first module public key 111 in order to authenticate the second module public key 111 in a step 710 of Figure 7.

In other words, the substeps described in connection with a step 710 as described in the preceding three paragraphs could be conducted by a server 105 using the first module public key 111 received in a step 705 in order to authenticate the second module public key 111 from a step 709 (and a module 101 could use the first module private key 112 for the authentication of the second module public key 111). By module 101 authenticating or verifying data with the second module public key 111 using the first module private key 112, the different server 105 could access and use the first module public key 111 in authentication or verification steps performed by the different server 105 in order for the server to securely receive the second module public key 111. Security for a server 105 in future steps, such as securely receiving future messages 208 after a step 710 can depend on a server 105 recording the correct second module public key 111 for a module 101, including preventing unauthorized or fraudulent parties from attempting to send the second module public key 111.

In an exemplary embodiment, the module identity 110 in a step 710, and other steps for communication a module identity 110 in Figure 7, could comprise an encrypted module identity 110a. Module 101 could sent the encrypted module identity 110a with an algorithm token 190, and a server 105 could use a secret ciphering algorithm deciphering 162 in order to convert the encrypted module identity 110a into a plaintext module identity 110. In this manner, the module identity 110 could be securely transmitted across a public network such as the IP Network 107. The second module public key 111 in a step 710 could be sent in a module encrypted data 403, such that third parties may not reasonably be able to read the plaintext second module public key 111. As noted elsewhere herein, any given module public key 111 may not need to be publicly shared and could remain confidential for an mobile network operator 108, and in this manner the security for communications between module 101 and server 105 can be further increased, since a potential attacker could be prevented from having reasonable access to a module public key 111. Further, module 101 could use a plurality of module public keys 111 for different purposes, including different module public keys being associated with different asymmetric ciphering algorithms 141a. A first module public key 111 could be used with a first wireless network 102 (possibly in the form of an activate MNO network credentials 314), a second module public key 111 could be used for verifying module digital signatures 405, and a third module public key 111 could be for a different mobile network operator 108, etc. The use of different module public keys 111 could be specified using a module public key identity 111a. In exemplary embodiments, a first subset of the module public keys 111 may be sent by a

Petitioner Samsung Ex-1004, 0134

module 101 in a module encrypted data 403 and a second subset of the module public keys 111 could be sent by the module 101 as plaintext within a datagram.

As illustrated in Figure 7, the collection of steps from step 515 through step 710, including loops through a step 309, can collectively comprise individual sub-steps for a step 712 as depicted in Figure 7. Step 712 can include a plurality of sub-steps including module 101 deriving a first set module PKI keys at a step 515, determining that a new set of module PKI keys are needed in a step 708, receiving a new set of cryptographic parameters 126, and deriving a second set of module PKI keys using the new set of cryptographic parameters 126 in a step 709, and sending the new, second module public key 111 while performing authentication in a step 710, etc. In addition, the collection of steps from step 702 through step 704 can comprise sub-steps for a step 711. A step 712, comprising the collection of sub-steps as depicted and described Figure 7, may be utilized in Figure 9a below. A step 711 may be utilized in Figure 10 below.

Figure 8

Figure 8 is a simplified message flow diagram illustrating an exemplary message sent by a module, wherein the message includes a derived module public key, in accordance with exemplary embodiments. As discussed in Figure 5b, there can be cases where module 101 derives a new module public key 111 and new module private key 112. On example would be the initial creation of the key pairs by module 101, and many other examples could exist as well. Figure 8 can illustrate an exemplary format and contents of a message 208 for steps 710 of Figure 7. This exemplary message 208 can also help to illustrate the significant differences from conventional technology and improvements for efficient and secure communications by utilizing embodiments contemplated herein. Since a message 208 illustrated in Figure 8 could be related to more than one module public key 111, as depicted and described herein the new module public key 111 can be referred to as new module public key 111' and the prior applicable module public key 111 can be referred to as module public key 111. Likewise, a new module public key identity 111a can be referred to as a new module public key identity 111a', and the prior applicable module public key identity 111a can be referred to as module public key identity 111a.

A message 208 illustrated in Figure 8 using a step 710 from Figure 7 can include (i) sending new module public key 111', a module public key identity 111a', a module identity 110, a server instruction 414, a security token 401, a subset of cryptographic parameters 126a associated with (i) the new module public key 111' and/(ii) or cryptographic algorithms 141 for using the new module public key 111'. Exemplary cryptographic parameters 126a illustrated in Figure 8 include (i) a secure hash algorithm 141c to utilize in signatures, which could comprise the SHA 256 algorithm as shown (which may also be known as the SHA-2

Petitioner Samsung Ex-1004, 0135

algorithm), (ii) a selected elliptic curve for use with ECC algorithms 154 or a modulus to use with RSA algorithms 153, and (iii) a time-to-live value for the new module public key 111', such as, but not limited to, the illustrated "time to live" value of 1 year shown in Figure 8. The time value for the validity of new module public key 111' could alternatively be specified in a set expiration date. Other values associated with cryptographic algorithms 141 could be included in a set of cryptographic parameters 126 as well, and the illustrated values are intended to be exemplary instead of limiting. In exemplary embodiments, the set of cryptographic parameters 126 in a message 208 could comprise a set of cryptographic parameters 126 depicted and described in connection with Figure 1i. Or, module 101 could send a set of cryptographic parameters token 126c to identify a set of cryptographic parameters 126 instead of sending the complete list of cryptographic parameters 126. Note that a set of cryptographic parameters 126 or 126a or token 126c could be optionally omitted in the message 208 illustrated in Figure 8 when a prior message 208 or step had negotiated or established the set of cryptographic parameters 126 or 126a to use with the new module public key 111'.

Additional values or fields within a message 208 associated with communicating a new module public key 111' with a server 105 could include a server instruction 414 of "new public key". This server instruction 414 could inform server 105 to utilize the new module public key 111' within the message 208. Module public key identity 111a' can include a sequence number or identity for the new module public key 111', such that module 101 or server 105 can properly reference and/or record the key from a plurality of module public keys 111 that could be associated with module identity 110. Although module public key identity 111a' is illustrated as a separate field in server instruction 414, module public key identity 111a' could optionally be included in a set of cryptographic parameters 126, such that the value within cryptographic parameters 126 specifies a current sequence number of module public key identity 111a' for the new module public key 111' included in a message 208. In addition, although the module public key identity 111a' illustrated in Figure 8 could be a sequence number, the module public key identity 111a' could also optionally be globally unique. For example, the module public key identity 111a' could comprise a combination of a unique serial number from a module 101 and then a sequence number. With a globally unique module public key identity 111a, a server 105 reading the module public key identity 111a could determine a module 101 with a module identity 110 associated with any given module public key identity 111a.

Other fields and features within a message 208 as illustrated in a Figure 8 can be similar or equivalent to the fields presented in Figure 6. In an exemplary embodiment, the new module public key 111' can be transmitted by a module 101 using at least one of (i) channel coding 406 for a body 602 of message 208 and/or (ii) forward error correction such that message 208 could be transmitted multiple times

Petitioner Samsung Ex-1004, 0136

concurrently in order to increase the probability of receipt by a server 105. In an exemplary embodiment, a message 208 containing the new module public key 111' could be sent by module 101 three times concurrently, and other possibilities exist as well. In an exemplary embodiment, the module identity 110 could be included within an encrypted module identity 110a. Module 101 could use a secret symmetric ciphering algorithm 161 to encrypt the module identity 110. In another embodiment illustrated in Figure 8, module identity 110 could be sent as plaintext within the message 208 that includes the new module public key 111'.

For a message 208 in Figure 8 comprising a message for a step 710 in Figure 7, each of (i) destination IP:port number 207, (ii) parameters 126, and (iii) shared secret key 510 could be updated by server 105 using a module instruction 502 within a server encrypted data 504 before message 208 illustrated in Figure 8 is transmitted or sent by module 101. After receiving message 208, server 105 can use the module identity 110 illustrated in a body 602 of Figure 8 to select at least one of (i) a symmetric key 127 associated with module identity 110, where the symmetric key 127 could comprise a session key, and/or (ii) a prior module public key 111 associated with the module identity 110. The symmetric key 127 could be established in steps such as a step 706 or the prior module public key 111 (i.e. not the new module public key 111' in Figure 8) sent in a step 705. The server 105 can use the selected symmetric key 127 or selected prior module public key 111 to authenticate message 208. As described in step 710 of Figure 7 and elsewhere herein, a server 105 may preferably authenticate message 208 that includes new module public key 111' in order to confirm that module public key 111 originated from physical module 101 with a hardware module identity 110 (as opposed to being an imposter submitting the new module public key 111'). In one example, successfully decryption the module encrypted data 403 using the symmetric key 127 would authenticate or verify the message 208, since only the valid and correct module 101 could reasonably have access to the symmetric key 127 to encrypt the new module public key 111'. Other possibilities exist as well for a module 101 to authenticate a message 208.

Although not illustrated in Figure 8, in an exemplary embodiment new module public key 111' could also be sent in a message 208, where the new module public key 111' and parameters 126 (if present) can be included in plaintext format within a datagram 601a. The security of a system 100 and other systems illustrated herein can be further increased by both (i) ciphering new module public key 111' and the set of cryptographic parameters 126, and (ii) only sharing the new module public key 111' in a confidential manner with server 105 and/or a set of servers 1010. If module 101 needed a module public key 111 for other purposes, such as, but not limited to, obtaining a certificate 122, then a second, publicly disclosed module public key 111 could be utilized to authenticate a message 208 from Figure 8 that is sent as plaintext without

Petitioner Samsung Ex-1004, 0137

symmetric ciphering 141b, where the second module public key 111 is different than and sent before the new module public key 111' that is sent to a server 105 in a module encrypted data 403.

Although not illustrated in Figure 8, in an exemplary embodiment, new module public key 111' can be authenticated with server 105 using a module digital signature 405. When message 208 illustrated in Figure 8 comprises a message for a step 710 illustrated in Figure 7, such that a prior module public key 111 has previously been sent to server 105 such as in a step 705, then message 208 could include a module digital signature 405 using the previous module private key 112 (i.e. not the new module private key 112 associated with the new module public key 111' in the message 208 shown in Figure 8). In another embodiment, module digital signature 405 could be omitted, and message 208 with new module public key 111' could be authenticated using a message digest algorithm and a shared secret key 129, where the shared secret key could be sent using a step 706 or 707 from Figure 7. Other possibilities for a module 101 to send a new module public key 111' in a message exist as well without departing from the scope of the present invention.

Figure 9a

Figure 9a is a flow chart illustrating exemplary steps for a module to use a shared secret key to authenticate with a server, in accordance with exemplary embodiments. In order to utilize communications secured with PKI techniques such as private keys, public keys, certificates, and identities, a module 101 may preferably obtain or generate these keys and certificate in a secure manner. In exemplary embodiments, the distribution of module 101 may include the possession or control of module 101 passing through entities outside of the control of a module provider 109 and/or a mobile network operator 108. Consequently, module 101 may need a secure method of authenticating with a server 105 after distribution and upon the initiation of operation with a monitored unit 119. Note that securely initiating communications after distribution, potentially through third parties outside the control of module provider 109 and/or mobile network operator 108 can be a challenge with conventional technology since keys such as a pre-shared secret key 129a (such as a traditional key K in a SIM) or private keys not internally derived may need to also pass through the distribution channel in order to initiate secure communication with conventional technology. Figure 9a illustrates an embodiment of the present invention, where a module 101 can begin secure communication with a server 105 without passing any keying material through a distribution channel. In this manner, (i) a system such as system 100 and other exemplary systems 100 can be made more secure, and (ii) the additional handling costs of passing keying material through a distribution channel, possibly in the form of a secret key in a SIM card or UICC, can be avoided.

At step 901, a manufacturer can complete manufacturing of a module 101, including assembling the hardware, software, and/or firmware components illustrated in Figure 1b and Figure 1c. A module identity

Petitioner Samsung Ex-1004, 0138

110 and component parameters 101t can be recorded in a step 901. The module identity 110 could be recorded in a protected address, such as, but not limited to a ROM 101c or other address on a system bus 101d. A protected address is also described in connection with Figure 7 and elsewhere herein. The component parameters 101t could be recorded with each of the exemplary components illustrated in Figure 1b, Figure 1c, and Figure 1e. Exemplary component parameters 101t are depicted and described in connection with Figure 1e. The component parameters 101t could be read using a system bus 101d and recorded into nonvolatile memory such as, but not limited to, flash memory 101w in a module 101. Or, the module manufacturer could read or specify the individual component parameters 101t before assembly of module 101 and record the collection of component parameters 101t into a file. At a step 901 the component parameters 101t could be recorded into a file for storage in module 101 and a server 105. In exemplary embodiments, both module 101 and server 105 can record the module identity 110 and component parameters 101t.

At step 902, a module program 101i, a first set of cryptographic parameters 126, and a server address 207 can be recorded into a nonvolatile memory such as, but not limited to, a flash memory 101w. Step 902 can occur at one of several possible points in time between module 101 manufacturing and installation with a monitored unit 119. Step 902 could be performed by the manufacturer during manufacturing. Step 902 could be performed by a distributor during distribution. Step 902 could be performed by a technician or end-user upon installation of module 101 with a monitored unit, and other possibilities exist as well for the time when a step 902 could occur. The server address 207 could comprise a server name 206 instead of an IP address, and module 101 could use the server name 206 at a later step to lookup a server IP address 207 using DNS or DNSSEC. A set of cryptographic parameters 126 are depicted and described in connection with Figure 1d and Figure 1i and elsewhere herein. A module program 101i is depicted and described in connection with Figure 1b. Note that many other parameters and values may be loaded into a non-volatile memory 101t besides the ones illustrated in step 902 of Figure 9a, including data for connecting with a wireless network 102, and Figure 9a illustrates an exemplary set of steps in order to utilize the efficient and secure systems and methods for communication contemplated herein. As one example, a module 101 could also include a SIM card, a UICC, or an embedded UICC 163 (eUICC), in addition to recording in a module 101 the data illustrated at step 902 of Figure 9a. In accordance with an exemplary embodiment, the data illustrated at a step 902 of Figure 9a can be recorded in a SIM card, UICC, or eUICC 163. For embodiments with an eUICC 163, the data recorded in a step 902 could be included within a received eUICC profile 311. Thus, although other embodiments of the present invention illustrated in Figure 9a (other embodiments contemplated in the previous two sentences) allows a module 101 to securely initiate communication with a server 105 without depending on pre-shared security keys such as a SIM card or eUICC 163, the pre-shared

Petitioner Samsung Ex-1004, 0139

materials in traditional mobile networks such as SIM cards and a eUICC could include the data and techniques contemplated herein.

At step 903, the module 101 can derive a shared secret key 129c using the component parameters 101t. In an exemplary embodiment, the module 101 can derive the shared secret key 129c using the steps depicted and described in connection with Figure 1f and Figure 1h. Module 101 could use the set of component parameters 101t and an algorithm token 190 as input into a shared secret algorithm 141g, with an output of the shared secret key 129c. Although not illustrated in Figure 9a, a server 105 could record or could query a module database 105k for the same set of component parameters 101t with the module identity 110 and shared secret algorithm 141g, and upon receipt of the module identity 110 and algorithm token 190, then the server 105 could derive the same shared secret key 129c.

After step 903, upon connection to the IP Network 107, possibly through a wireless network 102, module 101 could conduct a step 904. In step 904, module 101 can perform a 2-way authentication with a server 105 using the shared secret key 129c, where the shared secret key 129c in a step 904 could be derived in a step 903. The server address 207 as the destination of outbound packets, such as a message 208 to initiate the authentication, could be recorded in a step 902 above. Module 101 can send the algorithm token 190 used to derive the shared secret key 129c in a step 903 to the server 105 in a message 208, in order for the server 105 to derive the same shared secret key 129c, where the server 105 can use the same set of component parameters 101t and shared secret algorithm 141g as depicted and described in connection with Figure 1f. Note that a benefit of both nodes deriving the same or equal shared secret key 129c is that only the algorithm token 190 may need to be sent from module 101 to server 105 at a step 904, and the algorithm token 190 may also be sent as plaintext. Upon both nodes accessing the same shared secret key 129c, sub-steps can be taken by both nodes in order to conduct the 2-way authentication using the shared secret key 129c. In an exemplary embodiment, module 101 can conduct the 2-way authentication using wireless network standards such as, but not limited to, ETSI standard TR 131 900 v.10.0.0 and related documents.

At step 904, server 105 can authenticate module 101 using the module identity 110 received in a message 208 and a message digest algorithm, such as described in IETF RFC 2617, titled "HTTP Authentication: Basic and Digest Access Authentication", and other reasonably secure authentications techniques using a shared secret key 129c could be utilized without departing from the scope of the present invention. In order to authenticate, module 101 could take steps to demonstrate to server 105 that module 101 holds the same shared secret key 129c as server 105. Module 101 can properly respond to a challenge/nonce in the steps for a message digest by sending a secure hash value using (i) the challenge/nonce from a server 105 and (ii) the shared secret key 129c. Or, module 101 could authenticate by generating a module digital signature 405 in a message 208 using the shared secret key 129c. In addition,

Petitioner Samsung Ex-1004, 0140

module 101 could utilize the shared secret key 129c as a symmetric key 127 to encrypt a module encrypted data 403 with symmetric ciphering 141b, and if server 105 could properly decrypt the module encrypted data 403 using the same shared secret key 129c on the server, then server 105 would know the correct module 101 sent the message 208 and thereby would be authenticated. Other possibilities exist as well for a module 101 to authenticate with a server 105 using a shared secret key 129c and a step 904 in Figure 9a without departing from the scope of the present invention.

Continuing at step 904, module 101 can also preferably authenticate server 105 in order to complete a 2-way authentication. Module 101 can take steps to ensure or verify that server 105 with reasonable assurance also holds the shared secret key 129c. Module 101 could authenticate server 105 using message digest, such that module 101 issues a challenge/nonce, and verifying that server 105 properly responds to the challenge/nonce with a correct secure hash value, such as the output from a secure hash algorithms 141c. Or, server 105 could authenticate with module 101 by the module receiving a server digital signature 506 in a response 209 using the shared secret key 129c. In addition, module 101 could utilize the shared secret key 129c as a symmetric key 127 to decrypt a received server encrypted data 504 with symmetric ciphering 141b, and if module 101 could properly decrypt the server encrypted data 504 using the shared secret key 129c, then module 101 would reasonably know the correct server 105 sent the response 208 and thereby the server 105 would be authenticated. Other possibilities exist as well for a server 105 to authenticate with a module 101 using a shared secret key 129c without departing from the scope of the present invention.

Continuing at step 904, module 101 can receive a set of cryptographic parameters 126, preferably after module 101 completes authentication with server 105 (in order for server 105 to not send the set of cryptographic parameters 126 to unauthenticated 3rd parties). A set of cryptographic parameters 126 received in a step 904 can also comprise a second set of cryptographic parameters 126, where the second set of cryptographic parameters 126 could be different or the same as the first set of cryptographic parameters 126 from a step 902. The set of cryptographic parameters 126 at step 904 can comprise a subset of cryptographic parameters 126a as depicted and described in connection with Figure 1i. Module 101 could send the set of cryptographic parameters 126 recorded in step 902 to the server 105, and the server 105 could respond with a subset of cryptographic parameters 126a. In another embodiment, server 105 could send module 101 a set of cryptographic parameters 126 at step 904, and module 101 could send a subset of the cryptographic parameters 126a to the server. At step 904 either module 101 or server 105 could send the subset of cryptographic parameters 126a. In either case, at the conclusion of step 904 the module 101 and server 105 can preferably agree on a set of cryptographic parameters 126 for use with cryptographic algorithms 141 for further communication. In an exemplary preferred embodiment, a set of cryptographic parameters 126 sent and/or received at a step 904 may preferably be encrypted using the shared secret key

Petitioner Samsung Ex-1004, 0141

129c, such as using the shared secret key 129c as a symmetric ciphering key 127. In this manner, module 101 and server 105 can encrypt the set of cryptographic parameters 126 received in a step 904, without requiring the secure transmission of a different key other than the mutually derived shared secret key 129c.

After step 904, module 101 can then proceed to a step 712, where a step 712 is depicted and described in connection with Figure 7. As depicted and described in connection with Figure 7, step 712 can include a plurality of sub-steps including module 101 (i) deriving a first set module PKI keys at a step 515, (ii) determining that a new set of module PKI keys are needed in a step 708, (iii) receiving a new set of cryptographic parameters 126 in a step 607, and (iv) deriving a second set of module PKI keys using the new set of cryptographic parameters 126 in a step 709, and (v) sending the new, second module public key 111 with authentication in a step 710, etc. In this manner, module 101 can use a secret shared key 129c to initially establish secure communication with a server 105, and subsequently use the other steps illustrated in the present invention, such as, but not limited to, the steps illustrated in Figure 7, in order to securely derive a series of module PKI key pairs and authoritatively send a derived module public key 111.

Although not illustrated in Figure 9, in exemplary embodiments, there can be cases where a module 101 would return from step 712 back to prior steps, including steps 902, 903, and/or, 904. After module 101 begins operation, such as, but not limited to, collecting sensor data 305 associated with a monitored unit 119, module 101 could return to a step 904 upon connection with a new set of servers 1010 (illustrated in Figure 10 below) where module 101 may prefer to conduct a 2-way authentication of the set of servers 1010 in a step 904. In an exemplary embodiment, module 101 could utilize DNS and a server name 206 or a server identity 206 in order to query or lookup a destination IP address 106 in order to send a message 208. Since DNS records can change over time, and a mobile network operator 108 could utilize different servers 105 or set of servers 1010 over time, module 101 may determine that a destination IP address 106 associated with a DNS response can change. Upon a change in the IP address 106 associated with a server 105, in an exemplary embodiment, module 101 could return to a step 904 upon a change in IP address 106 in order to conduct the authentication of server 105 a second time. In this exemplary subsequent return to step 904, the module could also receive another set of cryptographic parameters 126 or 126a and use this set of cryptographic parameters 126 or 126a upon a subsequent return to step 712.

In another exemplary embodiment, module 101 could return to either a step 903 or step 902 upon a reset or equivalent operation of module 101. After module 101 begins operation, such as, but not limited to, collecting sensor data 305 associated with a monitored unit 119, module 101 could return to a step 903 or 902 upon receiving a reset command. The reset command could be received locally at module 101 by an end-user or technician, or remotely from a server 105 via a response 209 with a module instruction 502 of "reset" or a similar command. The reset command could comprise a "factory reset" command in order to

Petitioner Samsung Ex-1004, 0142

wipe confidential data from module 101. A "reset" command could be received by a module 101 for many different purposes, including (i) a change in ownership of module 101, (ii) a lack of payment from an end-user to mobile network operator 108, such that mobile network operator 108 determines that operation of module 101 (and associated variable costs such as the costs of using a network 102) should cease, (iii) a firmware upgrade of module 101 where the new firmware requires a new configuration, and other possibilities exist as well for a module 101 to receive a reset command. Upon receiving a reset command and returning to a step 902, module 101 could complete step 902 and subsequent steps. Upon receiving a reset command and returning to a step 903, module 101 could complete step 903 and subsequent steps.

Figure 9b

Figure 9b is a flow chart illustrating exemplary steps for a module to derive a shared secret key K using a derived module PKI key, in accordance with exemplary embodiments. Although the use of an embedded universal integrated circuit card (eUICC) such as an eUICC 163 depicted and described in Figure 1c and other Figures herein can provide significant benefits of reducing the costs and complexities associated with the physical distribution of media or units such as a physical SIM card or UICC, significant challenges and requirements have impeded the development and adoption of eUICC standards as of 2013, such as those proposed in ETSI TS 103 383 and related standards. One primary challenge has been the secure distribution of shared secret key K for operation with a wireless network 102 that functions as a PLMN based on ETSI standards, such as, but not limited to, 4G LTE networks and also networks using 4G LTE Advanced. Shared secret key K for a regular SIM or UICC can comprise the key K contemplated for a SIM in 3GPP TS 33.401 V12.9.0 and related standards, and shared secret key K can be used to derive session keys such as the cipher key (CK) and the integrity key (IK) as described in ETSI and 3GPP standards in order to a module 101 such as a mobile phone, mobile station, or user equipment to access a wireless network 102. Shared secret key K is normally recorded by both the wireless network 102 and a UICC within a module 101 using conventional technology.

Figure 9b illustrates and embodiment of the present invention where a module 101 can securely derive shared secret network key K 129d using a derived module private key 112. As described below in Figure 11, a network 102 can also derive the same shared secret network key K 129d, without requiring the recording or distribution of shared secret network key K 129d in a eUICC profile 311. Note that (i) an eUICC profile 311 could include an initial key K 325, which can comprise a shared secret key K contemplated in 3GPP TS 33.401 V12.9.0 and related standards, and (ii) the initial key K 325 could be used for an initial connection with wireless network 102 and the initial key K 325 could comprise a secret shared key 510 in Figure 9b, but module 101 and a mobile network operator 108 can use change from using the

Petitioner Samsung Ex-1004, 0143

initial key K 325 in an first connection by module 101 to wireless network 102 to using the derived shared secret network key K 129d in a second and subsequent connection by module 101 to wireless network 102. Using the steps depicted and described in Figure 9b, the derived shared secret network key K 129d does not need to be transmitted to or from a module 101, thereby increasing security. Further, the secure derivation of a shared secret network key K 129d by both a module 101 and a wireless network 102 can provide compatibility with the the well established and incumbent PLMN infrastructure that utilizes a pre-shared secret key K as currently recorded in a SIM card or UICC with conventional technology. In this manner, the use of an eUICC 163 by a module 101, where network credentials 314 could include or be associated with a derived module private key 112 as contemplated in the present invention, can remain compatible with incumbent PLMN infrastructure while achieving the security benefits of a module 101 and mobile operator network 108 mutually deriving shared secret key K.

At a step 905, a module 101 with an eUICC 163 can read a received eUICC profile 311. The received eUICC profile 311 could be recorded in a nonvolatile memory such as, but not limited to, a flash memory 101w. A module 101 could have previously received the received eUICC profile 311 from an eUICC subscription manager 164 or another entity, including a first wireless network 102. Or, the received eUICC profile 311 in a step 905 could be loaded into module 101 by a manufacturer, distributor, or end user. At a profile activation 316 step, a module 101 using the eUICC 163 can convert the received eUICC profile 311 into an activated eUICC profile 313. As contemplated herein and throughout the present invention, an activated eUICC profile 313 can comprise a selected and enabled network access application state as illustrated in Figure D.1 of ETSI TS 103 383 v.2013-02 for the activated eUICC profile 313, and other possibilities exist as well. In exemplary embodiments, the step 316 illustrated in Figure 9b can be performed concurrently with a step 906 below.

At a step 316, a module 101 can derive a module private key 112 and a module public key 111. Module 101 could use a step 316 in order to derive the module PKI key pair 315, and a module 101 can use sub-steps depicted and described in connection with a step 316 in Figure 3b, Figure 5b, and Figure 7. A module 101 could also use a step 515 as depicted and described in connection with Figure 5b and Figure 7 in order to derive the module private key 112 and module public key 111. Module 101 could also use a set of cryptographic algorithms 141, a key pair generation algorithm 141e, a random number generator 128, and a set of cryptographic parameters 126 to process or derive the module PKI key pair 315 at a step 316 in Figure 9b. Module private key 112 and module public key 111 could be processed and formatted according to either an RSA algorithm 153 or an ECC algorithm 154. The set of cryptographic parameters 126 could comprise a subset of cryptographic parameters 126a as illustrated in Figure 1i. A set of cryptographic parameters 126 used in a step 316 in Figure 9b for deriving the module PKI key pair 315 could be included

Petitioner Samsung Ex-1004, 0144

in the received eUICC profile 311, as illustrated in Figure 3b. Or, the set of cryptographic parameters 126 used in a step 316 in Figure 9b for deriving the module PKI key pair 315 could be included in the eUICC 163. In exemplary embodiments, module private key 112 and module public key 111 may utilize an ECC algorithm 154 in order to provide a higher level of security for a given key length. Module 101 could also calculate or process a key K module token 1103 at a step 316 in Figure 9b, and the use and function of a key K module token 1103 is depicted and described in connection with Figure 11 below.

Note that the actual step of key derivation could be performed independently of a profile activation step 316, such that a module 101 derives the module PKI key pair 315 before a profile activation 316 step, but upon completion of a profile activation step 316, an activated eUICC profile 313 can preferably include or be associated with a derived module private key 112 and derived module public key 111 in exemplary embodiments. In other words, in order for a module 101 to use an activated eUICC profile 311 (which could also comprise a selected and/or enabled profile) to connect with a wireless network 102, the activated eUICC profile 311 can preferably be associated with a derived module private key 112 and derived module public key 111, where the derived keys could be processed by module 101 using a key pair generation algorithm 141e. Module 101 could use a set of cryptographic parameters 126 recorded in a received eUICC profile 311 to derive the module PKI key pair 315.

At a step 906, the derived module public key 111 and derived module private key 112, which could be associated with an activated eUICC profile 313, resulting from a step 316 above in Figure 9b, can be recorded in a nonvolatile memory, such as, but not limited to, a flash memory 101w. In this manner, PKI keys could be later read by module 101 after a power off state or similar state where a RAM 101e could be flushed. Although not illustrated in Figure 9b, module 101 could also send the derived module public key 111 to the wireless network 102 and/or a server 105, such that other entities besides module 101 can use the derived module public key 111 for communication with module 101. Module 101 could use a step 517 to authenticate the derived module public key 111 sent. After a successful sending of the derived module public key 111 to the wireless network 102 and/or a server 105, module 101 could optionally choose to no longer record derived module public key 111 associated with a step 316 within nonvolatile memory of module 101.

At a step 907, module 101 could connect with a wireless network 102. The connection procedure could include an LTE attachment procedure and a series of steps for LTE authentication. A module 101 at a step 907 could promote from a detached state to an "radio resource connected" state using attachment and promotion procedures outlined in 3GPP specification TS 24.301 v12, entitled "Non-Access-Stratum (NAS) protocol for Evolved Packet System (EPS); Stage 3". In a first exemplary embodiment, module 101 could attach and authenticate with wireless network 102 in a step 907 using the initial key K 325 recorded in a

Petitioner Samsung Ex-1004, 0145

received eUICC profile 311, where the initial key K 325 recorded in a received eUICC profile 311 could comprise a first shared secret network K key (such as a pre-shared secret key K described in 3GPP TS 33.401 V12.9.0). Module 101 could also connect with and authenticate at a step 907 using the network module identity 101b recorded in a received eUICC profile 311. In the embodiment where an initial key K 325 comprises a first shared secret network K key, module 101 could authenticate with the network 102 using the standard procedure or receiving a RAND 912 and processing and sending a response RES 913, as described at step 910 below for Figure 9b. In an exemplary embodiment, a difference with authentication at a step 907 from authentication at a step 910 is that authentication at a step 907 could utilized the initial key K 325 recorded in a received eUICC profile 311, while a later authentication at a step 910 can utilize a different key.

Although not illustrated in Figure 9b, in another exemplary embodiment, module 101 can connect or complete an attachment procedure with wireless network 102 at a step 907 without a valid key K and network module identity 110b (or equivalently a "null" value for the key K and also possibly a "null" value for the network module identity 110b), and this case would also be synonymous or equivalent to a module 101 attaching to wireless network 102 without a valid SIM card or UICC. Note that both standards and deployed, operational wireless networks widely support the attachment of mobile phones without a valid SIM/UICC in order to support emergency services. Or, in an exemplary alternative embodiment for a step 907 module 101 could connect with wireless network 102 using a key K and network module identity 110b that are not valid, and/or not authenticated by a wireless network 102 or mobile network operator 108. This feature to support emergency calls/emergency services without a valid SIM card or UICC (or a valid or activated SIM/UICC with authenticated network access credentials) is also mandated by regulatory authorities in different countries, such as the Federal Communication Commission (FCC) in the US.

Consequently for this alternative embodiment contemplated for a step 907 in Figure 9b but not illustrated in Figure 9b, module 101 in a step 907 illustrated in Figure 9b could attach to a wireless network 102, where the module 101 and the network 102 use a null or invalid values for key K and/or network module identity 110b at a step 907. Module 101 at a step 907 could identify itself to wireless network 102 using either (i) a module identity 110 recorded in a non-volatile memory or (ii) a network module identity 110b recorded in a received eUICC profile 311, and other possibilities for the identity of module 101 in a step 907 when attaching to a wireless network 102 in an unauthenticated manner are possible as well for a step 907 without departing from the scope of the present invention. In this alternative exemplary embodiment for a step 907 (as one alternative to the step 907 depicted in Figure 9b), a module 101 at a step 907 could complete an attachment procedure as outlined in 3GPP specification TS 24.301 v12 without successfully completing an authentication procedure using a shared secret network K key or an initial key K

Petitioner Samsung Ex-1004, 0146

325 recorded in a received eUICC profile 311. In other words, the initial key K 325 for a step 907 does not have to be a valid, acceptable, and/or authenticated key K in order to use the steps illustrated in Figure 9b, although in some embodiments of the present invention the initial key K 325 can be a proper and authenticated key K for wireless network 102. The initial key K 325 used in a step 907 could also comprise a "null" value, and a "null" value for a key K is contemplated in LTE and related wireless network standards (in order to support mandated emergency services for module network operator 108).

After connecting with wireless network 107 in a step 907, at a step 908, module 101 can send wireless network 102 a key K module token 1103, where a key K module token 1103 is depicted and described in connection with Figure 11 below. The key K module token 1103 could be calculated or processed by module 101 in a step 316, although the key K module token 1103 could be derived at other times or steps as well. A message or packet sent from a module 101 to a server 105 associated with network 102 in a step 908 can also include any of (i) a module identity 110, (ii) an encrypted module identity 110a, and/or (iii) a network module identity 110b. A key K module token 1103 in a step 907 can comprise any of (i) a derived module public key 111, where the derived module public key 111 could be calculated in a step 906 above, (ii) a value processed by a module 101 for a Diffie Hellman key exchange, (iii) an algorithm token 190 for a shared secret algorithm 141g, and/or (iv) a number or string for a server 105 to use in a network key K derivation algorithm 1101 in order for mobile network operator 108 to derive a secret shared network key K 129d. In an exemplary embodiment, module 101 can send the key K module token 1103 to a server 105 such as, but not limited to, a home subscriber server (HSS) using a step 522 at a step 908.

At a step 908, module 101 can send a message 208 with a key K module token 1103 and authenticate data associated within the message, such as, but not limited to, a module identity 110. However, a separate authentication of a message with key K module token 1103 using a step 522 may optionally be omitted (thus depicting "908 And/Or 522" in Figure 9b), for embodiments where module 101 uses a valid, authenticated initial key K 325 for a step 907 above. In the embodiment described in the previous sentence, the steps for "And/Or 522" depicted in Figure 9b may be omitted, and thus the optional additional steps for 522 could be omitted with a step 908 for a Figure 9b. In other words, when module 101 uses a valid, authenticated initial key K 325 for a step 907, module 101 can send key K module token 1103 in a step 908, and separate, additional steps for authenticating the key K module token 1103 may not be required.

For other embodiments where module 101 connects with wireless network 102 using an invalid, unauthenticated, or "null" initial key K 325 (such as attaching in a manner for supporting emergency services but not regular subscriber service as described at Step 907), the steps for "And/Or 522" depicted in Figure 9b can be included, in order for a mobile network operator 108 to receive the key k module token 1103 in a secure manner. A module 101 sending the key K module token 1103 at a step 908 and 522 in Figure 9b

Petitioner Samsung Ex-1004, 0147

could authenticate the message, or data associated with the message, in a step 908 using a step 522. In exemplary embodiments, module 101 can attach to the wireless network 102 without successfully completing authentication (such as the data-link and network layer of the OSI stack not being authenticated), and send a message 208 with key K module token 1103 in a step 908 with a step 522 in Figure 9b. The message 208 with key K module token 1102 could be authenticated by a server 105 using a shared secret key 510, as depicted and described in connection with a step 517 of Figure 5b. In this manner, module 101 could use an eUICC 163 with a received eUICC profile 311 that contains both an initial key K 325 and a shared secret key 510. The initial key K 325 may not be valid and/or authenticated (or could comprise a "null" value). Module 101 could attach to the wireless network 102 in a manner that supports emergency services. Module 101 could send the key K module token 1103, and authenticate data associated with key K module token 1103 using a step 517 and the shared secret key 510. Note that the same value or number could be used for both initial key K 325 and shared secret key 510, although the values or numbers for the two keys could also be different.

In another embodiment for Figure 9b, a valid initial key K 325 can be utilized to authenticate a module 101 with a wireless network 102, where initial key K 325 comprises a pre-shared secret key K contemplated in 3GPP TS 33.401 V12.9.0 and used in a step 907. A separate shared secret key 510 can be used for authentication of application data such as sending key K module token 1103 in a message 208 to a server 105 in a step 908 with a step 522, where the authentication could use (i) a step 517 in step 522 and (ii) the shared secret key 510.

In exemplary embodiments, shared secret key 510 can be used by both module 101 and a mobile network operator 108 in a step 908 with a step 522 in order to verify and authenticate that a key K module token 1103 (or related data such as a module identity 110 and/or a network module identity 110b) is properly authenticated at a step 908 using a step 522, such that imposters or fraudulent submissions of key K module token 1103 could be reasonably be prevented or excluded from using a step 908. As noted above, the use of a step 522 with a shared secret key 510 can be optionally omitted, and the submission or sending of key K module token 1103 could be secured by using a valid, authenticated initial key K 325. Other possibilities for a module 101 to send a key K module token 1103 to a server 105 associated with a mobile network operator 108 are possible as well without departing from the scope of the present invention. Although not illustrated in Figure 9b, after sending the module key K token 1103 in a step 908, module 101 can detach from the wireless network 102. A subsequent re-attachment of module 101 at later steps, such as step 909 below, could utilize a different key K than the initial key K 325 used in a step 907, such as module 101 using the derived shared secret network key K 129c in a second attachment and connection procedure with the same wireless network 102.

Petitioner Samsung Ex-1004, 0148

At a step 909, a module 101 can derive a shared secret network key K 129d using the derived module private key 112 and a key derivation function 141f. The key derivation function 141f could use a Diffie-Hellman key exchange plus a set of cryptographic parameters 126 with the derived module private key 112 in order to derive the shared secret key K 129d. A key derivation function 141f could also use alternative algorithms to Diffie-Hellman, such as, but not limited to, ECDH 159, ANSI-X.9.63 160, or similar key exchange protocols, such that a module 101 could use the derived module private key 112 from a step 316 in order to derive a secret shared network key K 129d that is also shared with a wireless network 102. As contemplated herein, a step 909 can also comprise a module key K derivation algorithm 909, and a module key K derivation algorithm 909 is depicted and described below in Figure 11. As depicted in Figure 11, a step 909 comprising a module key K derivation algorithm 909 could also use input of a network key K token 1102. A key K network token 1102 for a step 909 can comprise any of (i) a network public key 165b, (ii) a value from MNO 108 for a Diffie Hellman key exchange, (iii) a server public key 114, and/or (iv) a number or string for a module 101 to use in a module key K derivation algorithm 909 in order for module 101 to derive a secret shared network key K 129d. The key K network token 1102 could be recorded in a received eUICC profile 311 or received by module 101 in a response 209 (not shown in Figure 9b) prior to step 909.

The output of a key derivation function 141f in a step 909 (also depicted and described in connection with Figure 11 below), using input at least in part of (i) the module private key 112, (ii) a set of cryptographic parameters 126 or 126a, and (iii) the key K network token 1102, could comprise a derived shared secret key 129b that is different than shared secret network key K 129d. As one example, the derived shared secret key 129b could have a different number of bits for derived shared secret key 129b than the 128 bit long key length for shared secret key K compatible with ETSI standards for LTE networks in 2013. In this exemplary case, a module 101 and a server 105 could perform additional key processing 141i to convert (A) a derived shared secret key 129b output by a key derivation function 141f in a step 909 into (B) a mutually derived shared secret network key K 129d.

The function of a shared secret network key K 129d (in the form of a key "K") is described in 3GPP TS 33.401 V12.9.0 and related standards, where shared secret key K is used to derive session keys such as a session cipher key (CK) and a session integrity key (IK) as described in ETSI and 3GPP standards. Conventional technology for the use of a shared secret key K contemplates that shared secret key K comprises a pre-shared secret key K recorded in (i) physical media such as a SIM or (ii) transferred electronic media such as an eUICC profile that would be delivered to a module 101 with an eUICC 163. In exemplary embodiments of the present invention, the shared secret network key K 129d is internally derived by a module 101 using (i) the derived module private key 112 from a step 316 and (ii) a step 909, which could also comprise the use of a module key K derivation algorithm 909. In this manner, module 101 can

Petitioner Samsung Ex-1004, 0149

process or obtain the shared secret network key K 129d without having the shared secret network key K 129d pass through 3rd parties (even in an encrypted electronic form), and thereby increase the security, convenience, and flexibility of a system 100 and other systems contemplated herein that utilize an eUICC 163 for a module 101 to connect with a wireless network 102. As depicted and described in connection with Figure 11 below, concurrent with step 909 a wireless network 102 or a mobile network operator 108 could also derive the same shared secret network key K 129d using a network key K derivation algorithm 1101. After mutual derivation of the same shared secret network key K 129d, module 101 and wireless network 102 can initiate regular communications on legacy and widely deployed wireless networks 102. Establishing regular communications with the widely deployed wireless networks 102 includes the derivation of subsequent session keys, after mutually obtaining a secure shared secret network key K 129d. Additional details for a step 909 are depicted and described in connection with Figure 11 below.

At step 910, after deriving shared secret network key K 129d from a step 909, where shared secret network key K 129d can also be derived by a mobile network operator 108, module 101 can use an eUICC 163 to reconnect with the wireless network 102 associated with the activated eUICC profile 313. The activated eUICC profile 313 could be obtained in a step 316 above. Module 101 can send the network module identity 110b to the wireless network 102, where the network module identity 110b can be recorded in the activated eUICC profile 313. Module 101 can use the derived shared secret network key K 129d from a step 909 to authenticate with wireless network 102 and/or mobile network operator 109 in a step 910, where the derived shared secret network key K 129d is different than the initial key K 325 used in a step 907 for a prior authentication with wireless network 102.

This exemplary change in a key K used with wireless network 102 in Figure 9b illustrates several important differences with conventional technology. First, the module 101 can use two different key Ks (comprising shared secret network key K 129d and initial key K 325) with the same wireless network 102 without physically changing a SIM or UICC. Second, module 101 can use an eUICC 163 and steps in Figure 9b with same activated eUICC profile 313 and two different key Ks in order to communicate with wireless network 102. Using conventional technology as of 2013, a change for a key K is not contemplated for the same activated eUICC profile 313 or a physical UICC. Further, conventional technology for an eUICC 163 does not contemplate that module 101 could derive a key K (in the form of a shared secret network key K 129d described herein) for use with an eUICC 163 that also can be mutually shared with MNO 108, without requiring the electronic distribution of key K, even in an encrypted or ciphered form.

Continuing at step 910, wireless network 102 and/or mobile operator network 108 can use ETSI standards for PLMN networks, including LTE and LTE advanced networks and standards such as 3GPP TS 24.301v10+, in order to authenticate, module 101 in a step 910. Upon reconnecting to wireless network 102,

Petitioner Samsung Ex-1004, 0150

module 101 can receive a random number in the form of a RAND 912 from the wireless network 102. The algorithm for authentication of module 101 with the wireless network 102 can comprise a form of message digest authentication. Module 101 can input the received RAND 912 and derived shared secret network key K 129d into a set of cryptographic algorithms 141 in order to obtain the response RES 913. An exemplary calculation of a RES 913 using a key K and RAND 912 is described in ETSI standard TR 131 900 v.10.0.0 and related documents. For exemplary embodiments that utilize Figure 9b, the set of cryptographic algorithms 141 for processing the response RES 913 can operate within an eUICC 163 within module 101.

Continuing with a step 910, as specified in ETSI/3GPP standards, the RAND 912 and an internally recorded key K (which could be the derived shared secret network key K 129d for a step 910 in the present invention) can also be subsequently used with a set of cryptographic algorithms 141 for the derivation of additional keys such as, but not limited to, a cipher key (CK) and an integrity key (IK) (described in a step 911 below). Exemplary embodiments of the present invention can utilize the derived secret shared network key K 129d instead of the key K recorded in a SIM or UICC in order to perform the same operations to derive CK, IK and related keys, thereby maintaining secure compatibility with the significant installed infrastructure in PLMN networks for supporting the use of key K in SIM/UICC cards for mobile phones in 2013 and future networks using a key K. Upon conclusion of a step 910, module 101 can send the response RES 913 to the wireless network 102 in order to authenticate. Wireless network 102 or MNO 108 could calculate the same RES 913 for the same RAND 912 using the shared secret network key K 129d mutually derived by wireless network 102 or MNO 108 (possibly using a network key K derivation algorithm 1101 illustrated in Figure 11 below), and thereby compare the RES 913 received from module 101 in a step 910 with the RES 913 internally calculated by MNO 108 using the same set of cryptographic algorithms 141 as module 101. Module 101 could be authenticated with network 102 using the network module identity 110b in the case the two RES 913 values match for network 102 (i.e. the received RES 913 matches the internally calculated RES 913).

After the internal, secure derivation of a shared secret network key K 129d in a step 909 and the authentication of module 101 with a wireless network 102 in a step 910, at a step 911 module 101 can begin the process of generating additional keys in order to securely transmit and receive application data with or through a wireless network 102. At step 911, module 101 can derive a cipher key (CK) 914 by inputting into a set of cryptographic algorithms 141 both RAND 912 and the derived shared secret network key K 129d. The RAND 912 and the derived shared secret network key K 129d could also be input into a key derivation function 141f within a set of cryptographic algorithms 141. An output of a key derivation function 141f in a step 911 can be CK 914, which could comprise a session key. The key derivation function 141f in a step 911 can utilize relevant algorithms for generating CK 914 specified in ETSI, 3GPP, or similar standards for

Petitioner Samsung Ex-1004, 0151

wireless networks, including WiMAX, such that module 101 can independently derive the same value for CK 914 at wireless network 102. CK 914 can subsequently be used with or for further deriving a symmetric key 127 with a symmetric ciphering algorithm 141b for encrypting data transmitted or sent to wireless network 102 by module 101 and decrypting data received. As one example, CK 914 could be used to derive a key Kupenc, where Kupenc is used to cipher data transmitted by a module 101 from a radio 101z to a base station 103.

Although not illustrated in Figure 9b, both module 101 and a wireless network 102 could derive several additional secret keys using the derived and mutually shared secret network key K 129d, and the additional keys could comprise values for an integrity key (IK), Kasme, Knasenc, Knasint, Kenb, and/or Kupenc. In this manner, and as illustrated in Figure 9b, the derivation of a module private key 112 can be used for the derivation of a shared secret network key K 129d, and shared secret network key K 129d can be the basis for secure communications between a module 101 and a mobile network 102, while keeping compatibility with existing and future standards for both mobile phones and deployed wireless networks 102.

Figure 10

Figure 10 is a simplified message flow diagram illustrating an exemplary system with exemplary data transferred between a module and a set of servers, in accordance with exemplary embodiments. System 1000 may comprise a module 101 and a set of servers 1010, where the set of servers 1010 can include a plurality of servers 105 and a shared module database 105k. Figure 10 illustrates module 101 communicating with a server 105, depicted as "server A" 105, although a module 101 could communicate with other servers within a set of servers 1010 as well. The set of servers 1010 could be associated with a mobile network operator 108 and the set of servers 1010 could operate in a coordinated manner through a network. In exemplary embodiments where a module 101 and a wireless network 102 mutually derive a shared secret network key K 129d, then the set of servers 1010 illustrated in Figure 10 could be (i) operated by a mobile network operator 108 and also be (ii) associated with a home subscriber server (HSS). Although not illustrated in Figure 10, module 101 could access a wireless network 102 and the IP Network 107 illustrated in Figure 1a in order to send data to and receive data from a server 105 within a set of servers 1010.

As illustrated in Figure 10, a module 101 can communicate with a server 105 using the steps and datagrams illustrated in other figures, including sending a message 208, receiving a response 209, using steps 711, 607, 709, and/or 710 as depicted and described in connection with Figure 7, and/or steps 316 and 516 from Figure 5b. Figure 10 illustrates some of many potential combinations of using these individual steps for an efficient and secure system. Other messages 208 may potentially flow before and/or after a "first

Petitioner Samsung Ex-1004, 0152

message" 208. This terminology of "first message", "second response", "second public key", etc. contemplated in various Figures herein may refer to the "first message", "second response", "second public key", "first set of parameters", etc. described in the illustrated flows within each Figure. Other messages, responses, keys, and parameters may be communicated before and/or after a depicted "first message", "second response", "second public key", etc. The depicted elements for Figures herein can comprise subsets of all messages, responses, keys, etc. that may also flow, and the subsets can depict various embodiments contemplated herein.

In exemplary embodiments, Figure 10 illustrates the establishment of secure communication between a module 101 and a set of servers 1010 for the case where (i) an existing, authenticated module public key 111 is available from external servers, and (ii) the existing module public key 111 can be used to send parameters for the module 101 to derive a new module PKI key pair. As one example, the optional step 711, before a step 1001, could be used to authoritatively record a module public key 111 with external servers such as those external servers shown in a step 1002 in Figure 10. The optional step 711 could include module 101 recording an initial module public key 111b that is not derived by module 101, but rather loaded into module 101 by a manufacturer, distributor, or end user, and the initial module public key 111b could be used by a module 101 and a server 105 to authenticate and/or encrypted subsequent communications related to a derived module public key 111. After the derived module public key 111 has been successfully authenticated or recorded by a server 105 or a set of servers 1010, then a server 105 or set of servers 1010 can begin using the derived module public key 111 for subsequent authentication and/or encryption for communication with a module 101, instead of continuing to use the initial module public key 111b.

In exemplary embodiments, (i) an initial module private key 112b could be recorded in a nonvolatile memory for module 101 prior to a step 1001 illustrated in Figure 10, possibly using a step 711, and (ii) a set of servers 1010 could use an initial module public key 111b associated with the initial module private key 112b in order to establish initial secure communications with a module 101 such as using a step 1004 to transfer a symmetric key 127 for ciphering a new, second set of cryptographic parameters 126, and then (iii) a module 101 could receive the ciphered second set of cryptographic parameters 126 with subsequent exemplary steps illustrated in Figure 10 to derive additional module PKI keys, and (iv) establish secure communication with a set of servers 1010 using the second set of cryptographic parameters 126 and the derived module PKI keys.

In an embodiment where module 101 records a "base" certificate 122 (with a corresponding "base" module private key 112) which are included with a module 101 by a manufacturer. A mobile network operator 108 can use the "base" certificate 122 to communicate further sets of cryptographic parameters 126 for deriving additional module PKI keys. The initial set of cryptographic parameters 126 and an initial

Petitioner Samsung Ex-1004, 0153

module public key 111b could be recorded in the "base" certificate 122, and the exemplary use of cryptographic parameters 126 in a certificate 122 is illustrated in Figure 1j. The initial set of cryptographic parameters 126 could also be referred to as a "base" set of cryptographic parameters 126. The module manufacturer, module provider 109, mobile network operator 108 , and/or wireless network 102 could agree on a common initial set of cryptographic parameters 126 (such as, but not limited to, agreeing that initial module PKI keys could be based on RSA and a length of 2048 bits). By agreeing to a common initial set of cryptographic parameters 126, different modules 101 from different manufactures could initially interoperate with different module providers 109 and/or M2M service providers 108 using the initial, "base" parameters. The entities such as the mobile network operator 108 and/or wireless network 102 could use the "base" or initial set of cryptographic parameters 126 with the "base" certificate 122 to establish secure communications where subsequent, different sets of cryptographic parameters 126 for deriving new module PKI keys could be securely communicated and/or negotiated.

A first optional step 711 can comprise series of sub-steps comprising a step 702, 703, and 704 as depicted and described in connection with Figure 7. Note that the use of an optional step 711 can be omitted, and other preliminary steps and communications could take place between a module 101 and a set of servers 1010 before a module 101 performs a step 1001. In another exemplary embodiment, a module 101 may have used the data from a step 711 in communicating with a different set of servers (not shown) than the set of servers 1010 illustrated in Figure 10, and the set of servers 1010 illustrated in Figure 10 may not have access to data from the different set of servers (not shown). The sub-steps for a step 711 can include a module distribution and installation step 702. As contemplated herein, the term "installation" can also refer to a subset of steps conducted by an end user or technician for activation, such that a module 101 performs initial steps to become operable upon completion of the "installation" or activation. In one embodiment, module 101 can comprise a mobile phone such as a smartphone and in this case "installation" in a step 702 within a step 711 can comprise an end user powers up the mobile phone or smartphone for an initial time. Also, in an exemplary embodiment where the optional step 711 is omitted, no data flows between a module 101 and a set of servers 1010 until the first message 208 at a step 1001 illustrated in Figure 10.

After a sub-step 702 in an optional step 711 in Figure 10, the next sub-step can comprise a sub-step 703 as depicted and described in Figure 7. In this sub-step 703, a module 101 can record in nonvolatile memory a shared secret key 129, a first set of cryptographic parameters 126, and a server address 207. As discussed above, a server address 207 could comprise a server name 206 in a step 703, which could subsequently be resolved via DNS into an IP address 106 for a server 106 (or a plurality of IP addresses 106 for a set of servers 1010). The use of a shared secret key 129 for a step 703 is depicted and described in connection with Figure 7. Note that for the purposes of the present invention contemplated herein, a shared

Petitioner Samsung Ex-1004, 0154

secret key can comprise any of a pre-shared secret key 129a, a derived shared secret key 129b, or a shared secret key 129c processed using a shared secret algorithm 141g. In addition, and as described in a step 703 in Figure 7, in an exemplary embodiment a shared secret key 129 can comprise the combination of an initial module private key 112b and an initial module public key 111b, and the use of the two initial keys can comprises a shared secret key 129 for a sub-step 703 in an optional step 711 in Figure 10. Also as described in Figure 7, a sub-step 703 could take place concurrently with a sub-step 702 or possibly concurrently with a sub-step 701, such as during manufacturing or before a module 101 leaves a manufacturing facility.

After a sub-step 703 in an optional step 711 in Figure 10, the next sub-step can comprise a sub-step 704 as depicted and described in Figure 7. In this sub-step 704, a module 101 can conduct a 2-way authentication with a set of servers 105 using the shared secret key 129. Upon mutual authentication, a module 101 can record a second set of cryptographic parameters 126. The second set of cryptographic parameters 126 could comprise a subset of cryptographic parameters 126a as illustrated in Figure 1i. Or, the second set of cryptographic parameters 126 could be equal to the first set of cryptographic parameters 126 from a sub-step 703. The details for a module 101 to perform a mutual authentication using shared secret key 129 and receiving a second set of cryptographic parameters 126 are depicted and described in connection with step 704 in Figure 7. In this manner, by using an optional step 711 before a step 1001, module 101 and a server 105 can be mutually authenticated before a step 1001.

At a step 1001 of Figure 10, a module 101 can send a first message 208, where the first message 208 can include a module identity 110 and a first public key identity 111a. As received by a server 105 within a set of servers 1010, the first message 208 in a step 1001 could include a first source IP:port number equal to IP address 210 and source port number 605. As sent by module 101, the first message 208 in a step 1001 could include a first source IP:port number equal to IP:port number 204. Although firewall 104 is illustrated in Figure 10 as operating as a "NAT Firewall", a firewall 104 in a system 1000 could also operate as a symmetric firewall without NAT functionality and in this case the first message 208 in a step 1001 as received by a set of servers 1010 could include a source IP:port number equal to IP:port 204. Note that module identity 110 in a step 1001 could be in the form of an encrypted module identity 110a, and a module 101 could use a secret ciphering algorithm 141h to convert the module identity 110 into an encrypted module identity 110a using a secret ciphering algorithm ciphering 162. If a first message 208 in a step 1001 includes an encrypted module identity 110a, then the first message 208 in a step 1001 could also optionally include an algorithm token 190. In an exemplary embodiment, within a system 1000 where a module 101 optionally used a step 711 before a step 1001, many messages could have previously flowed between module 101 and a set of servers 1010 before the first message 208 in a step 1001.

Petitioner Samsung Ex-1004, 0155

At a step 1002, a set of servers 1010 can use the module identity 110 and/or module public key identity 111a in order to query other servers such as a server associated with a certificate authority 118, a module provider 109, or an eUICC subscription manager 164 in order to receive a first module public key 111 or certificate 122 for the module identity 110 and/or module public key identity 111a. Note than in an exemplary preferred embodiment, module 101 may use a plurality of module public keys 111 and/or certificates within a relatively short period of time (such as, but not limited to, using more than one module public key 111 within the same month). Different exemplary multiple module public keys 111 used concurrently by a module 101 are described elsewhere herein. In this embodiment where module 101 uses multiple module public keys 111 and/or certificates 122 in a relatively short period of time, the module public key identity 111a can serve as a useful index or pointer to a particular module public key 111 that a module 101 prefers to utilize with a set of servers 1010.

In an exemplary embodiment for a step 1002, a module 101 could also optionally send the relevant module public key 111 in a step 1001, but a step 1002 may be conducted by a set of servers 1010 in order to verify, query, or obtain the module public key 111 and/or certificate 122 from other servers. For example, if a module 101 had not previously conducted the optional step 711 in a Figure 10, and no authoritative information is available about a module 101 to a set of servers 1010 (such as not having a shared secret key 129 available in the case where a step 711 was omitted), then a set of servers 1010 may preferably use the information in a message 208 received in a step 1001 to query the other servers illustrated in Figure 10 (i.e. servers for 118, 109, or 164) in a step 1002 in order to obtain verification of the module identity 110 and/or a module public key 111 received in a step 1001, including obtaining a certificate 122.

In an embodiment where module 101 sends the module public key 111 in a step 1001, the module 101 preferably includes the module identity 111a. Module 101 could also send a certificate 122 in a step 1001, but the set of servers 1010 can independently query other servers for the certificate 122 or module public key 111 (query using the module identity 110 or module public key identity 111a from a step 1001). The query to other servers can be used to independently and separately receive the module public key 111, in order for a set of servers 1010 verify or compare that a received module public key 111, which could comprise an initial module public key 111b loaded by a manufacturer, matches the module public key 111, possibly in the form of a certificate 122, received from an independent and authoritative third party.

In an exemplary embodiments for a step 1002, a set of servers 1010 can also query other servers such as a certificate authority 118, an mobile network operator 108, an eUICC subscription manager 164, and/or a shared module database 105k in order to receive a first set of cryptographic parameters 126. A set of cryptographic parameters 126 is depicted and described in connection with Figure 1d, Figure 1i, and Figure 7, and elsewhere herein. The first set of cryptographic parameters 126 in a step 1002 could comprise the

Petitioner Samsung Ex-1004, 0156

parameters 126a within a certificate 122 illustrated in a Figure 1j. Within a step 1002 a set of servers 1010 could receive a certificate 122 for a module 101 with the module identity 110 from another server illustrated, where the certificate 122 could include (i) the module public key 111, (ii) the module identity 110, (iii) a module public key identity 111a, and (iv) a signature 123 from a certificate authority 118. Within a step 1002, a set of servers 1010 could also verify a chain of signatures 123 within a certificate 122 for a module 101. A set of servers 1010 could use a different IP:port number than IP:port 207 to query external servers for information pertaining to a first module public key 111 and a first set of cryptographic parameters 126.

After a step 1002, at a step 1003 a set of servers 1010 could send a module 101 a response 209. In an exemplary embodiment, the response 209 can include a server digital signature 506, where module 101 can verify the server digital signature 506 using the server public key 114. In this manner, module 101 can authenticate the server identity 206 and verify or confirm that the module 101 is communicating with a correct server 105 (such as not receiving data from an imposter or a "man in the middle" attack). The server 105 preferably sends the response 209 to the source IP:port received in the first message 208 in step 1001. Note that for embodiments which utilize an eUICC 163 and the mutual derivation of a secret shared network key K 129d, then the server digital signature 506 in a step 1003 could comprise a an authorization number "AUTN" associated with a RAND 912 depicted and described in connection with Figure 9b. Server digital signature 506 could be optionally omitted in a step 1003 in embodiments where module 101 performs a step 711 before a step 1001, as illustrated in Figure 10.

At a step 1004, a symmetric key 127 could be sent either from (i) a set of servers 1010 or (ii) a module 101 using an asymmetric ciphering algorithm 141a and either (i) the module public key 111 from a step 1002 or (ii) the server public key 114, respectively. Values for using an asymmetric ciphering algorithm 141a could be specified from the first set of cryptographic parameters 126 at either a step 1002 or a step 1001. The set of servers 1010 could record the symmetric key 127 from a step 1004 in a shared module database 105k, such that different servers 105 within a set of servers 1010 could use the symmetric key 127 in communication with the module 101. An exemplary datagram 601a that includes a symmetric key 127 within an encrypted data that uses asymmetric ciphering 141a is illustrated in element 701a of Figure 7 of U.S. Patent Application Serial No. 14/039,401, filed September 27, 2013 in the name of John Nix, which is hereby incorporated by reference in its entirety. Note that for embodiments which utilize an eUICC 163 and the mutual derivation of a secret shared network key K 129d, then the use of asymmetric ciphering for communicating a symmetric key 127 in a step 1004 may be optionally omitted, and each side (i.e. module 101 and a set of servers 1010 associated with a wireless network 102) could mutually derive the secret shared network key K 129d instead of sending or receiving a symmetric key 127 across a network.

Petitioner Samsung Ex-1004, 0157

At a step 1005, a set of servers 1010 could record that the use of a second set of cryptographic parameters 126 for a module 101 may be preferred. A step 1005 could take place earlier in the sequence of message flow illustrated in Figure 10, such as even before a step 1001. An example of the case in the previous sentence could be where a set of servers 1010 needs to initially communicate with a module 101 using a "base" set of cryptographic parameters 126 with an initial module public key 111b, and after initial secure communication is established, then the set of servers 1010 could use a different set of cryptographic parameters 126 and request that the module 101 derive a new set of module PKI keys using the different set of cryptographic parameters 126. In another embodiment, a relatively long period of time such as several years could transpire between a step 1004 and a step 1005 (with many additional messages not shown in a Figure 10 communicated between a module 101 and a server 105 in the time between a step 1004 and a step 1005). Over time and for various commercial and security needs, a preferred set of cryptographic parameters 126 can change, such as the use of longer key lengths, or adoption of new asymmetric ciphering algorithms 141a, including the use of new ECC curves. Consequently, in a step 1005, a set of servers 1010 could record a second set of cryptographic parameters 126.

At a step 607 in Figure 10, a module 101 could receive the second set of cryptographic parameters 126 from the set of servers 1010. Although not illustrated in Figure 10, a module 101 preferably sends a message 208 with the module identity 110 to the set of servers 1010 after a step 1004 and before a step 607, with the result that firewall 104 ports will be temporarily opened and bound so that a server 105 in a set of servers 1010 can send a response 209 back to the module 101. A step 607 with a response 209 is also depicted and described in connection with Figure 6 and Figure 7. The terminology depicted for a response 209 at a step 607 of "209 : 504 : ..." can refer from left to right as the structure for an exemplary response 209 illustrated in Figure 6, where the response 209 can include server encrypted data 504, and the server encrypted data can include either (i) a second set of cryptographic parameters 126, or (ii) a eUICC profile 311. The second set of cryptographic parameters 126 in a response 209 can be included in a server encrypted data 504. In this manner, the second set of cryptographic parameters 126 can remain confidential and reasonably securely received by a module 101.

Note that the symmetric key 127, or session key, used to cipher the second set of cryptographic parameters 126 in a step 607 in Figure 10 could be communicated in a step 1004 above or a similar step using an asymmetric ciphering algorithm 141a. In an exemplary embodiment, the second set of cryptographic parameters 126 in a step 607 in Figure 10 may not be encrypted and can also be sent as plaintext within a response 209. In addition, the set of cryptographic parameters 126 in a step 607 in Figure 10 may be communicated in the form of a reference to a set of cryptographic parameters 126 from the use of a set of cryptographic parameters token 126c (and thus a name or identity of the set of parameters 126 could

Petitioner Samsung Ex-1004, 0158

be communicated instead of the full set of cryptographic parameters 126). As contemplated herein, for any reference to a set of cryptographic parameters 126 in Figures 5b through Figure 10, the use of a set of cryptographic parameters token 126c can be substituted for communicating a complete list of cryptographic parameters 126.

For embodiments where a module 101 uses an eUICC 163, a step 607 illustrated in Figure 10 could comprise module 101 receiving a received eUICC profile 311, which could also contain the second set of cryptographic parameters 126. The inclusion of a received eUICC profile 311 within a step 607 is also described for a step 607 in connection with Figure 7. The received eUICC profile 311 could be included in a server encrypted data 504, and the server encrypted data 504 could be ciphered using a symmetric key 127 communicated in a step 1004. Or, the server encrypted data 504 for a step 607 could be ciphered with a different symmetric key 127. The set of servers 1010 could obtain the received eUICC profile 311 from an eUICC subscription manager 164. Note that a response 209 which includes a received eUICC profile 311 in a step 607 in Figure 10 can utilize a source IP:port number 207 that is different than a source IP:port number 207 in a response 209 in a step 1003 above. In other words, as contemplated herein, the numeric value for an IP:port number 207 can change over time, but a pair of datagrams comprising a message 208 and an resulting response 209 can utilize the same numeric value for an IP:port number 207.

At step 1006, a module 101 can send a subset of cryptographic parameters 126a, where the subset of cryptographic parameters 126a can be a subset of the cryptographic parameters 126 received in a step 607. Figure 1i above illustrates an exemplary "handshake" or "negotiation" of a set of cryptographic parameters 126 between a server 105 and a module 101, and the data illustrated in Figure 1i can apply to step 607 and step 1006 in Figure 10. Alternatively, the subset of cryptographic parameters 126a could be omitted, and the set of cryptographic parameters 126 received by a module 101 in a step 607 could be specific enough that module 101 does not need to select any options within the set of cryptographic parameters 126. In this case (where a step 1006 is optionally omitted), then a set of cryptographic parameters 126 in a step 607 could also comprise a subset of cryptographic parameters 126a. In addition, the terminology depicted for a message 208 at a step 1006 of "208 : 110 : 403 : with Subset 2nd Parameters 126a" can refer from left to right as the structure for an exemplary message 208 illustrated in Figure 6, with a message 208 containing a module identity 110 and a module encrypted data 403, where "Subset 2nd Parameters 126a" would be inside the module encrypted data 403.

Other data such as, but not limited to, source and destination IP:ports, a datagram packet header, and a checksum 603, plus optional channel coding 406 could be included in a packet comprising a message 208 sent by module 101 at a step 1006 and other messages 208 illustrated in Figure 10. In an exemplary embodiment, the second subset of cryptographic parameters 126a in a step 1006 in Figure 10 may not be

Petitioner Samsung Ex-1004, 0159

encrypted and can also be sent as plaintext within a message 208. In general, where the use of encrypted data in the form of a module encrypted data 403 or server encrypted data 504 is illustrated in various Figures, including Figure 10, the present invention contemplates that encryption may also be optionally omitted at the network layer and application layer and the data can be communicated as plaintext in these layers (but encryption could be performed at the data-link layer, such as ciphering data over a public wireless network 102). In an exemplary embodiment, module 101 can also use forward error correction at a step 1006, or other steps illustrated in Figure 10 and related Figures where a module 101 sends data, such that a module 101 can send multiple copies of the same or equivalent datagram comprising a message 208 in order to increase the probability that a server 105 or set of servers 1010 receives at least one datagram comprising a message 208.

At a step 709 or a step 316 in Figure 10, a module 101 can derive a new module public key 111 and a new module private key 112 using the parameters 126 negotiated or communicated between steps 607 and 1006. A step 316 in Figure 10 can include the use of an eUICC 163 for module 101, and a step 709 for Figure 10 can include embodiments that do not depend on the presence of an eUICC 163. The use of a step 709 is depicted and described in connection with Figure 7 above. Although the text for a step 709 is depicted in Figure 7 as "Module Derives 2nd Public Key 111 and 2nd Private Key 112 Pair, using 3rd Parameters 126", in the context of Figure 10, the second key pair would be derived using the second set of parameters 126 negotiated between steps 607 and 1006. In other words, the set of cryptographic parameters 126 used for a step 709 either in Figure 7 or Figure 10 can comprise the most recent set of cryptographic parameters communicated between a module 101 and a server 105. The module 101 PKI key pair resulting from a step 709 could comprise either a module PKI key pair that uses either ECC algorithms 154 or RSA algorithm 153. The key lengths and other parameters for a module 101 to process the module 101 PKI key pairs can be specified in the set of cryptographic parameters 126 negotiated or communicated between steps 607 and 1006.

At a step 709 in Figure 10, the module 101 could use a set of key pair generation algorithms 141e in a set of cryptographic algorithms 141a in order to derive a second module private key 112 and a corresponding second module public key 111. The first module public key 111 can be previously used in a step 1002 and the first module private key 112 can be previously used in a step 1004, although these first module 101 PKI keys could also be used in communication that is not shown (i) after a step 1004 within Figure 10 (such as the case where an extended period of time transpired between step 1004 and step 709 in Figure 10), and (ii) before a step 709 in Figure 10. A module 101 could determine that new module 101 PKI keys are preferred or desirable for many reasons before or upon a step 709, including the receipt of new cryptographic parameters 126 in a step 607, the transfer of ownership or control of module 101, the opening

Petitioner Samsung Ex-1004, 0160

of an enclosure for a module 101 where the first module private key 112 could be compromised, the receipt of a module instruction 502 of "derive new keys", and other reasons exist as well.

In the embodiments where either (i) an eUICC 163 is used by a module 101 to record a derived module private key 112 and a derived module public key 111, and/or (ii) module 101 and a wireless network 102 derive a shared secret key network key K 129d, a step 316 in Figure 10 could comprise the activation of a received eUICC profile 311, or similarly the derivation of a module PKI key pair 315 for an activated eUICC profile 313. The received eUICC profile 311 activated in a step 316 in Figure 10 could be received by a module 101 in a step 607 above. At a step 316 in Figure 10, a module 101 could use a step 316 as depicted and described in connection with a step 316 in Figures 9b, Figure 7, and Figure 5b, and Figure 3b. A module 101 could derive a new module private key 112 and a new module public key 111 at a step 316 using (i) a set of cryptographic algorithms 141, (ii) a set of cryptographic parameters 126 or 126a (and the set of cryptographic parameters 126a could be recorded in a receiving eUICC profile 311 being activated in a step 316 in Figure 10), (iii) a key pair generation algorithm 141e, and (iv) a random number generator 128. The derived module private key 112 and module public key 111 could be recorded in memory at a step 316 for further processing in additional subsequent steps.

At a step 710 within Figure 10, the module 101 can send a message 208 that includes the second module public key 111 derived at a step 709. The terminology depicted for a message 208 at a step 710 of "208 : 110 : 403 : 2nd 111a : 2nd 111" can refer from left to right as the structure for an exemplary message 208 illustrated in Figure 6, with a message 208 containing a module identity 110 and a module encrypted data 403, where the second module public key identity 111a and second module public key 111 could be inside the module encrypted data 403. In exemplary embodiments, the module public key identity 111a could optionally be omitted in a step 710 and the data within a message 208 could also optionally be sent as plaintext. In the embodiment where module 101 sends a message 208 with the derived module public key 111 at a step 710 and also encrypts the module public key 111 in a module encrypted data 403, the symmetric key 127 used with a symmetric ciphering algorithm 141b could be communicated between module 101 and a set of servers 1010 in a prior communication, such as, but not limited to, the transfers of a symmetric key 127 in a step 1004. Also, although a single instance of the transfer of a symmetric key 127 in a step 1004 is illustrated in Figure 10, over time multiple different symmetric keys 127 could be communicated between a module 101 and a set of servers 1010 using a step 1004 or similar secure transfer, before module 101 sends the derived, second module public key 111 in a step 710. In an exemplary embodiment, module 101 could use the most recent symmetric key 127 communicated between module 101 and a set of servers 1010 in order to send a module encrypted data 403 with the derived, second module public key 111 at a step 710 in Figure 10.

Petitioner Samsung Ex-1004, 0161

As illustrated in Figure 10, a step 516 from Figure 5b could also be utilized in Figure 10 for a module 101 to send the second module public key 111 or a key K module token 1103. In the embodiments where either (i) an eUICC 163 is used by a module 101 to record a derived module private key 112 and a derived module public key 111, or (ii) module 101 and a wireless network 102 derive a shared secret key network key K 129d, a step 516 in Figure 10 could comprise the module 101 sending a key K module token 1103 within a message 208, where a key K module token 1103 is depicted and described in connection with Figure 11 below. A key K module token 1103 could comprise the module public key 111 or could comprise other data for a wireless network 102 or MNO 108 to derive a secret shared network key K 129d, using a network key K derivation algorithm 1101 illustrated in Figure 11.

In an exemplary embodiment, the derived, second module public key 111 in a step 709 of Figure 10 could be sent outside the module encrypted data 403 (such as plaintext) in a message 208 at a step 710, but module encrypted data 403 could be used with the message 208 for either (i) sending other potentially sensitive data along with the module public key 111, such as, but not limited to, cryptographic parameters 126, or (ii) sending encrypted data using a symmetric key 127 such that a server 105 or set of servers 1010 could verify that module 101 has access to the symmetric key 127. Thus, the module encrypted data 403 in a message 208 at a step 710 could be used to authenticate or verify that the module public key 111 received in a message 208 properly belongs to a module 101 with a module identity 110. In other words, the proper processing of a module encrypted data 403 using a symmetric key 127 in a message 208 at step 710 can prevent imposters or the fraudulent submission of a module public key 111 in a step 710.

Note that a step 710 as depicted and described in connection with Figure 7 includes the authentication of the derived, second module public key 111, and a step 710 in Figure 10 can also include the steps for a module 101 to authoritatively send the derived, second module public key 111. For the embodiment where a server 105 uses a first module public key 111 (possibly from a step 1002) to authenticate a derived, second module public key 111 from a step 710, a server 105 that did not previously have or record the first module public key 111 could use the module identity 110 query other servers such as, but not limited to, a shared module database 105k, a certificate authority 118, or a mobile network operator 108 in order to obtain the first module public key 111 to authenticate or verify the derived, second module public key 112 received in a step 710.

The module identity 110 in a message 208 at a step 710 could be sent as an encrypted module identity 110a, such that the module identity 110 is ciphered or obfuscated. A module 101 could use a secret ciphering algorithm ciphering 162 or other techniques such as a symmetric ciphering algorithm 141b in order to send the module identity 110 as an encrypted module identity 110a. For and embodiment where module 101 sends module identity 110 as an encrypted module identity 110a where the encrypted module identity

Petitioner Samsung Ex-1004, 0162

110a is ciphered using a symmetric ciphering algorithm 141b, a key such as a symmetric key 127 to encrypt the module identity 110 into an encrypted module identity 110a could be communicated at a prior step such as, but not limited to, a step 1004. In general, the present invention contemplates that an encrypted module identity 110a can be used in place of a module identity 110 in Figures where a module 101 is depicted and described as sending a module identity 110.

The message 208 in a step 710 in Figure 10, as received by a server 105 can include a second source IP:port 210:605 that is different than the first source IP:port in a message 208 at a step 1001. The source IP:port 210:605 could change reasons including, but not limited to, (i) firewall 104 operating as a NAT firewall changes port bindings over time, (ii) the packets from module 101 to a set of servers 1010 route through different firewalls 104 over time, such as module 101 connecting to different networks 102 over time and a first network 102 is used by module 101 in a step 1001 and a second network 102 is used by a module 101 in a step 710, and (iii) a module 101 could use a different source IP:port number 204 for a step 1001 and a step 710. The present invention contemplates that module 101 can use a different source IP:port for sending the various messages 208 depicted and described in various Figures throughout the present invention (an correspondingly use the different IP:port numbers to receive various responses 209 to the message 208). The IP address 202 for a module 101 to use in an IP:port number 204 can change over time, such as if a module 101 uses different networks 102 for sending messages 208 over time.

Although a message 208 at a step 710 in a Figure 10 depicts a module 101 sending the message 208 at a step 710 to a server 105 within a set of servers 1010, a module 101 can send the message 208 at a step 710 to a different server than the server 105 illustrated in Figure 10. In other words, according to exemplary embodiments, a module 101 can send any of the messages 208 depicted in various Figures to different servers 105 over time, and the different servers 105 could communicate with other servers 105 such that the multiple servers 105 operate in a coordinated manner using a network, and the multiple servers 105 could function as a set of servers 1010. As one example, the first message 208 in a step 1001 could be sent to a first server 105, and the message 208 in a step 710 could be sent to a second server 105. The use of different servers 105 for a module 101 to send a message 208 could be identified by the use of a different destination IP address within the message 208. Other possibilities exist as well for the use of multiple servers 105 in a set of servers 1010 without departing from the scope of the present invention.

At a step 1007, after completing of a step 710 in Figure 10, a server 105 or set of servers 1010 can record the new, authenticated second module public key 111 with other servers illustrated. The data recorded by a server 105 could include the module identity 110, a module public key identity 111a, and a second module public key 111, plus an additional, optional subset of cryptographic parameters 126a. The data recorded by a server 105 in a step 1007 could be in the form of a certificate 122. In this manner, the second

Petitioner Samsung Ex-1004, 0163

module public key 111, possibly in the form of a certificate 122, can be made available to other servers 105 within a set of servers 1010 over time, and the other servers 105 could also use the subset of cryptographic parameters 126a in order to securely communicate with a module 101. The use of a step 1007 could also result in the second module public key 111 (with associated data such as a certificate 122, module identity 110, module public key identity 111a, and a subset of cryptographic parameters 126a for the second module public key 111) being made available to other servers outside of the set of servers 1010, such as a server 105 belonging to a different MNO 108 than a MNO 108 operating the set of servers 1010. Note that a step 1007 could be optionally omitted, and a set of servers 1010 could record the second module public key 111 internally, and the second module public key 111 could also be kept confidential and not shared with other servers, thereby further increasing the security of a system 100 and other systems illustrated herein.

At a step 1008, after sending a message 208 (which could comprise the message 208 in step 710 in Figure 10, or could comprise a different message 208 after a step 710 where the different message 208 after a step 710 is not illustrated in Figure 10), module 101 could receive a response 209 that includes a second symmetric key 127 that is ciphered using an asymmetric ciphering algorithm 141a. The response 209 in a step 1008 could include a server encrypted data 504. The server encrypted data 504 in a response 209 for a step 1008 that includes a second symmetric key 127 could be ciphered using the derived, authenticated, second module public key 111 sent by module 101 in a step 710. At a step 1008 the module 101 can decipher the server encrypted data 504 containing the second symmetric key 127 using the derived, second module private key 112 and an asymmetric ciphering algorithm 141a. A module 101 can use the second subset of cryptographic parameters 126a from a step 1006 with an asymmetric ciphering algorithm 141a in order to (i) decrypt the server encrypted data 504 received in a step 1008, and (ii) read the plaintext second symmetric key 127. An exemplary datagram 601a that includes a symmetric key 127 within an encrypted data that uses asymmetric ciphering 141a is illustrated in element 701a of Figure 7 of U.S. Patent Application Serial No. 14/039,401, filed September 27, 2013 in the name of John Nix, which is hereby incorporated by reference in its entirety. Note that in a step 1008, although the set of servers 105 are illustrated as sending the second symmetric key 127 in a response 209, the module 101 could alternatively send the second symmetric key 127 in a message 208, where the second symmetric key 127 could be within a module encrypted data 403 that is ciphered with an asymmetric ciphering algorithm 141a and the server public key 114 and also uses the second subset of cryptographic parameters 126 from a step 1006.

In another embodiment, a module 101 and a set of servers 1010 could conduct a key exchange such as Diffie Hellman, ANSI-X.9.63 160, or ECDH 159 in a step 1008 instead of transmitting and/or receiving the full second symmetric key 127. The key exchange could involve sending numbers or values, possibly including a random number 128a or a RAND 912, instead of the actual symmetric key 127, and a key

Petitioner Samsung Ex-1004, 0164

derivation function 141f could be used with the numbers or values sent to derive a shared secret key 129b. The shared secret key 129b could comprise the second symmetric key 127 for a step 1008 and a step 1009. As contemplated herein, in Figures such as Figure 10 where a symmetric key 127 is illustrated as communicated between two nodes, instead of a symmetric key 127 being directly communicated, values for a key derivation function 141f could communicated as a proxy for the symmetric keys 127 illustrated, and the nodes can use the values with a key derivation function 141f to determine the symmetric key 127. In other words, in various figures illustrated herein, where a symmetric key 127 is illustrated as communicated, values to determine a shared symmetric key 127 could be communicated instead, such as values input into a key derivation function 141f in order to output a derived shared secret key 129b that could comprise a symmetric key 127. As contemplated herein, the term "establish a symmetric key" can comprise either (i) sending or receiving the symmetric key 127 using an asymmetric ciphering algorithm 141a and PKI keys, or (ii) sending or receiving data for a key derivation function 141f such that a symmetric key 127 (possibly in the form of a derived shared key 129b) could be determined from the data sent or received for the key derivation function 141f.

At a step 1009, a module 101 can send a message 208 that includes a module encrypted data 403, where the module encrypted data 403 is ciphered using the second symmetric key 127. The second symmetric key 127 (or values for a key derivation function 141f to determine the second symmetric key 127) could be sent or received in a prior step 1008. The module encrypted data 403 using the second symmetric key 127 could include a server instruction 414, sensor data 305, a timestamp 604, and a security token 401. Security token 401 and timestamp 604 can prevent replay attacks. If a timestamp 604 is included in a module encrypted data 403, then a security token 401 could optionally be omitted in a step 1009. The message 208 in a step 1009 could contain data for a message 208 as depicted and described in connection with Figure 6. The module identity 110 could comprise an encrypted module identity 110a, although the module identity 110 could also be sent as plaintext or as a session identity such that the session identity (or temporary module identity 110) within a message 208 at a step 1009 can change over time but also be uniquely associated with a module identity 110 persistently associated with a module 101.

Figure 11

Figure 11 is a graphical illustration for a module and a network to mutually derive a shared secret key K, in accordance with exemplary embodiments. As described in Figure 9b, exemplary embodiments of the present invention can utilize a combination of an embedded UICC 163 with a module 101's derivation of a module private key 112 and module public key 111 in order to obtain a shared secret network key K 129d, such that shared secret network key K 129d can be utilized with existing and/or legacy mobile network

Petitioner Samsung Ex-1004, 0165

operator infrastructure, including at least one of a plurality of wireless networks 102. The shared secret network key K 129d depicted and described in this Figure 11 could comprise the shared secret key K used by a module 101 to authenticate and encrypt/decrypt data with a PLMN such as, but not limited to, mobile network operator networks of AT&T® and Verizon® that utilize LTE wireless WAN technology in 2013, and future networks as well that utilize a shared secret key K.

The eUICC 163 in a module 101 illustrated in Figure 1c could utilize a plurality of received eUICC profiles 311 in order to connect with multiple different wireless networks 102 without roaming (i.e. use an activated eUICC profile 313 with a corresponding activated MNO network access credentials 314 for different wireless networks 102 that a module 101 connects with). An activated eUICC profile 313 could be utilized to connect with several different base stations 103 across a wide geographical area that are associated with the same mobile network operator 108. A different connection to a second wireless network 102 could be associated with a different mobile network operator 108 that utilizes different network access credentials 314 for a different activated eUICC profile 313.

As illustrated in Figure 11, a module 101 could utilize a module key K derivation algorithm 909 in order to derive a secret shared network key K 129d in order connect and/or authenticate with a wireless network 102 operated by a mobile network operator 108, and the wireless network 102 could utilize a network key K derivation algorithm 1101 in order to share a common key K and support communication with a module 101. In this manner, a module 101 can utilize an eUICC 163 to share a key K with a network 102 without requiring (i) the physical distribution of a shared secret key K as specified and contemplated in current ETSI standards as of 2013, such as contemplated in 3GPP TS 33.401 V12.9.0 and related standards for a physical SIM or UICC or (ii) the electronic distribution of a shared secret key K as contemplated in ETSI TS 103 383 V12.0.0 and related standards for an eUICC. Future modules 101, wireless networks 102, and MNOs 108 could incorporate or support the internal derivation of a secret shared network key K 129d in order for a module 101 and a mobile network operator 108 to obtain the same shared key K without requiring the electronic transmission or physical distribution of a shared secret key K.

A module key K derivation algorithm 909 can comprise a series of steps and logic to input at least (i) a derived module private key 1102, and (ii) a key K network token 1102 and output at least a derived secret shared network key K 129d. The format and/or data for a key K network token 1102 as one input into a key derivation function 141f within a module key K derivation algorithm 909 can depend on the key derivation function 141f and embodiments for a key K network token 1102, which are described below. The secret shared network key 129d can be fully compatible with existing and/or future mobile network standards that utilize a shared secret key K, such that module 101 and MNO 108 could use the mutually derived secret

Petitioner Samsung Ex-1004, 0166

shared network key K 129d for all necessary steps in order to establish authenticated and secured communication with a wireless network 102.

A subset of the steps for using conventional technology with a key K in both authentication of a module 101 and deriving session keys for encryption are depicted and described in connection with Figure 9b, including (i) a step 910 of processing a RES 913 in response to a RAND 912 received by module 101, (ii) a step 911 of deriving a cipher key CK 914 using the RAND 912 and the derived secret shared network key K 129d, and also (iii) deriving additional keys using the RAND 912 and a key K, such as, but not limited to, values for an integrity key (IK), Kasme, Knasenc, Knasint, Kenb, and/or Kupenc. In other words, conventional technology contemplated using a pre-shared secret key K for the various steps listed in the prior sentence, but the present invention contemplates using a mutually derived secret shared network key K 129d in order to perform the same steps (and thus the present invention supports widely deployed wireless networks 102 and also future planned networks that continue to use a key K). In the present invention, a derived secret shared network key K 129d could be used to process or derive additional keys using a RAND 912, such as using a step 911 in Figure 9b. The derived additional keys could comprise symmetric keys 127 for use with symmetric ciphering algorithms 141b such as, but not limited to, an AES 155 ciphering. A module 101 could also use derived secret shared network key K 129d illustrated in a module key K derivation algorithm 909 with future wireless networks 102 that utilize different symmetric keys 127 than those listed above within this paragraph, where the different symmetric keys 127 are also derived from a shared secret key K.

The derived module private key 112 used for input by a module 101 in a module key K derivation algorithm 909 can be derived using a step 515 as depicted and described in connection with Figure 5b and/or Figure 7, or a profile activation step 316 as depicted and described in connection with Figure 3b, Figure 5b, and/or Figure 7. Module 101 could use at least a set of cryptographic algorithms 141, a key pair generation algorithm 141e, a random number generator 128, and a set of cryptographic parameters 126 to process or derive the module private key 112. Although not illustrated in Figure 11, module 101 could also derive a corresponding module public key 111 as well. The derived module private key 112 could utilize or be associated with an RSA algorithm 153 or an ECC algorithm 154, and the use of a set of cryptographic algorithms 141 for a module private key 112 can be specified in the set of cryptographic parameters 126 or a subset of cryptographic parameters 126a. An exemplary set of cryptographic parameters 126 and an exemplary subset of cryptographic parameters 126a are depicted and described in connection with Figure 1i and additional Figures herein. The subset of cryptographic parameters 126a illustrated in Figure 11 could comprise a set of cryptographic parameters 126. An exemplary set of cryptographic algorithms 141,

Petitioner Samsung Ex-1004, 0167

including a key derivation function 141f, are depicted and described in connection with Figure 1d, Figure 1i, and other Figures herein.

In exemplary embodiments, including the embodiments illustrated in Figure 11, the set of cryptographic parameters 126 for a key derivation function 141f in a module key K derivation algorithm 909 could be recorded in a received eUICC profile 311. Alternatively, the set of cryptographic parameters 126 could be recorded in an eUICC 163, or the set of cryptographic parameters 126 could be shared between a received eUICC profile 311 and an eUICC 163. The set of cryptographic algorithms 141, including (i) a key pair generation algorithms 141e used to process the module private key 112 in Figure 11, and (ii) a key derivation function 141f used in algorithm 909 in Figure 11, could be recorded in an eUICC 163, or a module program 101i, or shared between an eUICC 163 and a module program 101i. In exemplary embodiments, (i) the set of cryptographic algorithms 141, including key pair generation algorithms 141e and key derivation function 141f, (ii) the eUICC 163, (iii) the set of cryptographic parameters 126, and (iv) module key K derivation algorithm 909 can be recorded in a nonvolatile memory, such as, but not limited to, a nonvolatile memory 101w. In this manner, module 101 can store the algorithms and values when the module 101 is in a dormant or powered-off state. Other possibilities exist as well without departing from the scope of the present invention for the use and location of a set of cryptographic parameters 126 and a set of cryptographic algorithms 141 for (i) deriving a module private key 112 for a module 101 and (ii) utilizing a module key K derivation algorithm 909, without departing from the scope of the present invention.

As illustrated in Figure 11, the derived module private key 112 and key K network token 1102 can be input into a key derivation function 141f. The key derivation function 141f can use a subset of cryptographic parameters 126a and the inputs in order to output a derived shared secret key 129b. The use and function of a key derivation function 141f, as well as a derived shared secret key 129b is also depicted and described in connection with Figure 1d above. A key derivation function 141f in a module key K derivation algorithm 909 could comprise any of (i) a Diffie-Hellman key exchange, (ii) an ANSI-X.9.63 160 key derivation where an ECC algorithm is used with derived module private key 112, (iii) an ECDH 159 key derivation when an ECC algorithm is used with derived module private key 112, (iv) an ANSI-X.9.42 key derivation, or (v) similar and related algorithms for the derivation of a shared secret key 129b using a private key and a subset of cryptographic parameters 126a.

For an embodiment illustrated in Figure 11, a key derivation function 141f could use a Diffie-Hellman key exchange where the subset of cryptographic parameters 126a includes a multiplicative group of integers modulo p, where p is prime, and g is a primitive root mod p. In exemplary embodiments, p can be sufficiently large, such as, but not limited to, and exemplary prime number of at least 250 digits, and g can be a small number, such as, but not limited to, the number 5. In this embodiment where a key derivation

Petitioner Samsung Ex-1004, 0168

function 141f within a module key K derivation algorithm 909 uses a Diffie-Hellman key exchange, the key K network token 1102 could comprise a value received from network 102 associated with network private key 165a. In a Diffie-Hellman key exchange, key K network token 1102 could comprise a value equal to g^b mod p, where b equals the network private key 165a. Key K network token 1102 could be received by module 101 from network 102 either (i) after an authentication step 907 in Figure 9b using an initial key K 325, or (ii) key K network token 1102 could be recorded within a received eUICC profile 311 and module 101 could receive key K network token 1102 via a system bus 101d. Key K network token 1102 could also be received by module 101 in other steps as well, such as, but not limited to, a step 519, a step 607, and/or a step 707. As noted above in this Figure 11, the subset of cryptographic parameters 126a of p, g for a Diffie-Hellman key exchange can also be written to a received eUICC profile 311.

For another embodiment illustrated in Figure 11, a key derivation function 141f could use an ECDH 159 key exchange with elliptic curve cryptography, where the subset of cryptographic parameters 126a includes a common base point G. An ECDH 159 with common base point G is also described in Figure 1d. For this embodiment of a key derivation function 141f in a module key K derivation algorithm 909, module private key 111 and module public key 112 could comprise keys processed with an ECC algorithm 154, and module 101 could likewise derive the module PKI keys using a step 515 or a step 316. Key K network token 1102 could comprise a network public key 165b. The network private key 165a and network public key 165b could also be processed with an ECC algorithm 154 using the same or equivalent elliptic curve as module PKI keys. Key K network token 1102 could be received by module 101 from network 102 either (i) after an authentication step 907 using initial key K 325, or (ii) key K network token 1102 could be recorded within a received eUICC profile 311 and module 101 could receive key K network token 1102 via a system bus 101d. Key K network token 1102 could also be received by module 101 in other steps as well, such as, but not limited to, a step 519, a step 607, and/or a step 707

Other possibilities exist as well for the use of a key derivation function 141f and a subset of cryptographic parameters 126a within a module key K derivation algorithm 909 without departing from the scope of the present invention. Note a key exchange or a key derivation algorithm 141f other than (i) Diffie Hellman and/or (ii) ECDH 159 could utilize a different subset of cryptographic parameters 126a. For embodiments where a different algorithm than Diffie Hellman or ECDH 159 is utilized for a key derivation function 141f in a module key K derivation algorithm 909, then (i) a different subset of cryptographic parameters 126a and (ii) different or additional data than that depicted in Figure 11 could be utilized as well. With a different algorithm for a key derivation function 141f used in a module key K derivation algorithm 909, in exemplary embodiments the key derivation function 141f could utilize as a minimum input of a derived module private key 112 and a key K network token 1102. Key K network token 1102 for this

Petitioner Samsung Ex-1004, 0169

alternative embodiment could represent data for the key derivation function 141f that is different than the exemplary values for a key K network token 1102 described above with Diffi-Hellman or ECDH 159 for the key derivation function 141f.

In an exemplary embodiment, the use of a module private key 112 input into a key derivation function 141f within a module key K derivation algorithm 909 could be optionally omitted, and the derived shared secret key 129b within a module key K derivation algorithm 909 could comprise a shared secret key 129c processed with a shared secret algorithm 141g, using a set of component parameters 101t. As noted above in connection with Figure 1f and Figure 1g, a shared secret key 129c can be derived without input of data from a network 102 into the shared secret algorithm 141g, and thus in an exemplary embodiment module 101 could calculate a derived shared secret key 129b within a module key K derivation algorithm 909 without inputting data received from wireless network 102 into the key derivation function 141f. In other words, module 101 could use a shared secret key 129c as a derived shared secret key 129b in order to derive a shared secret network key K 129d without receiving data from wireless network 102. An algorithm token 190 for use with a shared secret algorithm 141g in a module key K derivation algorithm 909 can be included in a subset of cryptographic parameters 126a.

In preferred embodiments, a module key K derivation algorithm 909 and a network key K derivation algorithm 1101 can utilize the same or related key derivation functions 141f and the same or related subsets of cryptographic parameters 126a in order to obtain the same or equal value for the derived shared secret key 129b. In another embodiment, a key K network token 1102 for the key derivation function 141f that is different than Diffi Hellman or ECDH 159 could comprise a shared secret key 129c processed with a shared secret algorithm 141g, using a set of component parameters 101t.

In an exemplary embodiment, module 101 could derive a first module private key 112, where the first module private key 112 may optionally not be associated with a corresponding module public key 111. For this exemplary embodiment, module 101 could optionally derive a second module private key 112 that is associated with a corresponding module public key 111, and the second module private key 112 and corresponding module public key 111 could comprise a module PKI key pair 315. The derivation of a module PKI key pair 315 could optionally be omitted and still utilize the module key K derivation algorithm 909 illustrated in Figure 11. The first module private key 112 that is not associated with a corresponding module public key 111 could be utilized as the derived module private key 112 input into a key derivation function 141f within a module key K derivation algorithm 909. In this embodiment where the first module private key 112 that is not associated with a corresponding module public key 111 is utilized in a module key K derivation algorithm 909, then key K module token 1103 below in a network key K derivation algorithm

Petitioner Samsung Ex-1004, 0170

1101 can be data associated with the first module private key 112 as described in this paragraph as opposed to a first module public key 111 (since the first module public key 111 can be optionally omitted).

The output of a key derivation function 141f in a module key K derivation algorithm 909 can be a number comprising a derived shared secret key 129b, which is also depicted and described in connection with Figure 1d and Figure 1c. In exemplary embodiments, the use of a key derivation function 141f such as, but not limited to, a Diffie Hellman key exchange or ECDH 159, can output a key that is a different length than a key K for a wireless network 102 (or key Ki for use with 3G networks). As currently specified in ETSI/3GPP standards for LTE networks, the shared secret key K, (i) recorded in a SIM or UICC, and a MNO 108 HSS, and (ii) described in 3GPP TS 33.401 V12.9.0 and related standards, comprises a random number with a length of 128 bits. The length of key K for standards-based wireless networks 102 may be extended in the future. The use of shared secret key K for authentication of a module 101, and also for ciphering and data integrity, with a wireless network 102 that implements ETSI and/or 3GPP standards is also defined in the specifications ETSI TS 135 205 – 209 and related standards.

A key processing algorithm 141i within a module key K derivation algorithm 909 can (i) use as input the output of the key derivation function 141f in the form of a derived shared secret key 129b, and (ii) transform the derived shared secret key 129b into a number that is 128 bits in length (or other key lengths for key K supported by wireless network 102). In an exemplary embodiment, (i) the length of derived module private key 112, (ii) the length of parameters 126a, and (iii) an algorithm for key derivation function 141f in a module key K derivation algorithm 909 are selected such that the length of derived shared secret key 129b can be greater than the length of key K specified for wireless network 102. In this embodiment, the key processing algorithm 141i can take steps to (i) truncate derived shared secret key 129b, (ii) select a subset of bits within derived shared secret key 129b, and/or (iii) take steps to securely and/or randomly reduce the size of derived shared secret key 129b to match the key length of key K specified for wireless network 102. In exemplary embodiments, the key processing algorithm 141i within a module key K derivation algorithm 909 (or at least cryptographic parameters 126 for the key processing algorithm 141i in a module key K derivation algorithm 909) can be included in a received eUICC profile 311.

For embodiments where the derived shared secret key 129b in a module key K derivation algorithm 909 can be less than the key length of key K specified for wireless network 102, then key processing algorithm 141i can perform a key lengthening function, such as, but not limited to, using a secure hash algorithm 141c with input of at least the derived shared secret key 129b. The secure hash algorithm 141c could be selected such that the length of output of the secure hash algorithm 141c matches the length of key K specified for wireless network 102. The secure hash algorithm 141c for use in a module key K derivation algorithm 909 could be specified in a set of cryptographic parameters 126. Other possibilities exist as well

Petitioner Samsung Ex-1004, 0171

for a key processing algorithm 141i to lengthen a derived shared secret key 129b without departing from the scope of the present invention.

In an exemplary embodiment where the length of key K specified for wireless network 102 in the future equals 256 bits, key processing algorithm 141i could comprise an SHA-256 156 algorithm, such that the output of key processing algorithm 141i comprises a number with 256 bits in length, with input using a derived shared secret key 129b that could comprise a number less than, equal to, or greater than a length of 256 bits, and other possibilities for a key processing algorithm 141i exists as well. In exemplary embodiments, key processing algorithm 141i includes a secure hash algorithm 141c, such that the derived shared secret key 129b in a module key K derivation algorithm 909 is input into the secure hash algorithm 141c. Although not illustrated in Figure 1d above, a key processing algorithm 141i could be included in a set of cryptographic algorithms 141.

As depicted in Figure 11, the output of key processing algorithm 141i within a module key K derivation algorithm 909 can comprise a shared secret network key K 129d. A shared secret network key K 129d is also described in a step 909 depicted and described in connection with Figure 9b. Upon deriving the shared secret network key K 129d, module 101 could record the value in either an activated eUICC profile 313 or also possibly a received eUICC profile 311 (where the received eUICC profile 311 is not activated) within an eUICC 163. A wireless network 102 could utilize a network key K derivation algorithm 1101 in order to securely obtain the same value for shared secret network key K 129d. Module 101 and/or an eUICC 163 could then utilize the shared secret network key K 129d to connect with and/or authenticate with a wireless network 102 using the steps 910 and 911 depicted and described in connection with Figure 9b. In exemplary embodiments, module 101 and wireless network 102 could utilize the shared secret network key K 129d with the algorithms specified in ETSI TS 135 205 – 209, as well as subsequent and related standards, in order for module 101 to authenticate and/or connect with wireless network 102. Other possibilities exist as well without departing from the scope of the present invention.

A network key K derivation algorithm 1101 can be used by a wireless network 102 in order to derive a secret shared network key K 129d that is the same or equals the derived secret shared network key K 129d processed by a module 101 using a module key K derivation algorithm 909. In this manner, wireless network 102 and module 101 can both utilize the same, derived secret shared network key K 129d for communication. The commonly shared secret shared network key K 129d can be used by both module 101 and wireless network 102/mobile network operator 108 for (i) authentication and (i) the subsequent derivation of additional symmetric keys 127, where the additional symmetric keys 127 could be derived from a key derivation function 141f (where a key derivation function 141f would be used to derive symmetric

Petitioner Samsung Ex-1004, 0172

keys 127 in the form of derived shared secret keys 129b in a manner illustrated in Figure 1d that can be different than the use of a key derivation function 141f illustrated in Figure 11).

A server 105 as depicted and described in connection with Figure 1k and Figure 1m could reside in the network for a mobile network operator 108, where the wireless network 102 as illustrated in Figure 1a could comprise a radio access segment for the mobile network operator 108. The server 105 could also be part of a set of servers 1010, and the set of servers 1010 could also be within a network for a mobile network operator. The server 105 or set of servers 1010 could utilize the components depicted and described in connection with Figure 1k and Figure 1m in order to process and/or perform a network key K derivation algorithm 1101, including using (i) a storage 105m to record the key derivation function 141f and associated cryptographic parameters 126, (ii) a processor 105b to perform calculations in order to implement the key derivation function 141f, (iii) a system bus 105d in order to move data from storage into a RAM 105e for further processing, (iv) a physical interface 105a such as Ethernet to send and receive data, and (v) a module database 105k to record a network module identity 101b and a shared secret network key K 129d for each of a plurality of modules 101 that could connect to a wireless network 102. In exemplary embodiments, a home subscriber server (HSS) within an LTE network and subsequent, related networks including wireless networks based on LTE Advanced could operate or process a network key K derivation algorithm 1101, and the HSS could also function as a server 105 or a set of servers 1010 as contemplated herein.

A network key K derivation algorithm 1101 operating on a server 105, HSS, and/or set of servers 1010 can include a key derivation function 141f and a key processing algorithm 141i. The key derivation function 141f within a network key K derivation algorithm 1101 can be equivalent or the same algorithm as a key derivation function 141f used within a module key K derivation algorithm 909, as depicted and described in connection with this Figure 11 above. As illustrated in Figure 11, (i) a network private key 165a and (ii) a module key K token 1103 can be input into a key derivation function 141f within a network key K derivation algorithm 1101. The key derivation function 141f can use a subset of cryptographic parameters 126a and the input in order to output a derived shared secret key 129b. For an embodiment illustrated in Figure 11, a key derivation function 141f in a network key K derivation algorithm 1101 could use a Diffie-Hellman key exchange where the subset of cryptographic parameters 126a includes a multiplicative group of integers modulo p, where p is prime, and g is a primitive root mod p. In this embodiment where a key derivation function 141f within a network key K derivation algorithm 1101 uses a Diffie-Hellman key exchange (or similar key exchange protocols), the key K module token 1103 could comprise a value received from module 101 associated with module private key 112. The set of servers 1010 could receive the key K module token 1103 in a step 908 in Figure 9b or a step 516 in Figure 5b, and other possibilities exist as well for a server 1010 to receive the key K module token 1103.

Petitioner Samsung Ex-1004, 0173

In a Diffie-Hellman key exchange for a key derivation function 141f within a network key K derivation algorithm 1101, key K module token 1103 could comprise a value equal to g^a mod p, where a equals the module private key 112. Key K module token 1103 could be received from module 101 after an authentication step 907 using initial key K 325, and other possibilities exist as well without departing from the scope of the present invention. The subset of cryptographic parameters 126a of p, g for a Diffie-Hellman key exchange with a module 101 using a network module identity 101b can also be written to a module database 105k and also the received eUICC profile 311. In exemplary embodiments, a module database 105k can also record a plurality of received eUICC profiles 311 for a plurality of modules 101, where each module 101 uses either module identity 110 or network module identity 101b. In exemplary embodiments a different subset of cryptographic parameters 126a for a key derivation function 141f in a network key K derivation algorithm 1101 can be used for each module 101 in order to increase security.

For another embodiment illustrated in Figure 11, a key derivation function 141f could use an ECDH 159 key exchange with elliptic curve cryptography, where the subset of cryptographic parameters 126a includes a common base point G. For this embodiment where a key derivation function 141f in a network key K derivation algorithm 1101 comprises an ECDH 159 key exchange, network private key 165a and network public key 165b could comprise keys processed with an ECC algorithm 154. A server 105 or set of servers 1010 could derive the network private key 165a and network public key 165b using a key pair generation algorithm 141e. Key K module token 1103 could comprise a module public key 111, where the module private key 112 and module public key 111 could also be processed with an ECC algorithm 154 using the same or elliptic curve as the network PKI keys 165a and 165b. Key K module token 1103, in the form of a module public key 111 with an ECDH 159 for a key derivation function 141f in a network key K derivation algorithm 1101, could be received from module 101 after an authentication step 907 using an initial key K 325. Other possibilities exist as well for the use of a key derivation function 141f, key K module token 1103, and a subset of cryptographic parameters 126a both (i) within a network key K derivation algorithm 1101 and (ii) to derive a shared secret network key K 129d without departing from the scope of the present invention.

In an exemplary embodiment, the use of a network private key 165a input into a key derivation function 141f within a network key K derivation algorithm 1101 could be optionally omitted, and the derived shared secret key 129b within a network key K derivation algorithm 1101 could comprise a shared secret key 129c processed with a shared secret algorithm 141g, using a set of component parameters 101t. As noted above in connection with Figure 1f and Figure 1g, a shared secret key 129c can be derived without input of data from a module 101 into the shared secret algorithm 141g, and thus in an exemplary embodiment MNO 108 could calculate a derived shared secret key 129b within a network key K derivation algorithm 1101

Petitioner Samsung Ex-1004, 0174

without inputting data received from module 101 into the key derivation function 141f. In other words, MNO 108 (using a server 105) could use a shared secret key 129c as a derived shared secret key 129b in a network key K derivation algorithm 1101 in order to derive a shared secret network key K 129d without receiving data from module 101. An algorithm token 190 for use with a shared secret algorithm 141g in a network key K derivation algorithm 1101 can be included in a subset of cryptographic parameters 126a, and the subset of cryptographic parameters 126a could be included in the received eUICC profile 311 for a module 101. An HSS for a network 102 could process or create information for the received eUICC profile 311. As depicted and described in connection with Figure 1f, (i) a server 105, which could be operated by MNO 108, or (ii) MNO 108 could calculate shared secret key 129c using component parameters 101t for a module 101 with module identity 110 in a module database 105k.

For embodiments that do not use a shared secret key 129c in a network key K derivation algorithm 1101, the output of a key derivation function 141f in a network key K derivation algorithm 1101 can be a number or string comprising a derived shared secret key 129b, which is also depicted and described in connection with Figure 1d and Figure 1c. The derived shared secret key 129b in a network key K derivation algorithm 1101 can be the same or equivalent for a derived shared secret key 129b as described in a module key K derivation algorithm 909. The sub-steps and description for a derived shared secret key 129b in a module key K derivation algorithm 909 can apply for a derived shared secret key 129b in a network key K derivation algorithm 1101.

A key processing algorithm 141i within a network key K derivation algorithm 1101 can take the same or equivalent steps as described for a key processing algorithm 141i within a module key K derivation algorithm 909 described above in this Figure 11. For embodiments where the derived shared secret key 129b can be less than the key length of key K specified for wireless network 102, then key processing algorithm 141i can perform a key lengthening function, such as, but not limited to, using a secure hash algorithm 141c with at least input of the derived shared secret key 129b. The secure hash algorithm 141c could be selected such that the length of output of the secure hash algorithm 141c matches the length of key K specified for wireless network 102. The secure hash algorithm 141c for use in a network key K derivation algorithm 1101 could be specified in a set of cryptographic parameters 126. For embodiments where the length of derived shared secret key 129b in a network key K derivation algorithm 1101 can be greater than the length of key K specified for wireless network 102, the key processing algorithm 141i can take steps to (i) truncate derived shared secret key 129b, (ii) select a subset of bits within derived shared secret key 129b, and/or (iii) take steps to securely and/or randomly reduce the size of derived shared secret key 129b to match the key length of key K specified for wireless network 102. In exemplary embodiments, key processing algorithm 141i includes a secure hash algorithm 141c, such that the derived shared secret key 129b in a network key K

Petitioner Samsung Ex-1004, 0175

derivation algorithm 1101 is input into the secure hash algorithm 141c in order to output the secret shared network key K 129d.

In exemplary embodiments, the key processing algorithm 141i for a network key K derivation function 1101 can take the same or equal value for a derived shared secret key 129b in a module key K derivation function 909 and output the same or equal value for shared secret network key K 129d. One difference between a key processing algorithm 141i for a network key K derivation function 1101 and a a key processing algorithm 141i for a module key K derivation function 909 is that the a key processing algorithm 141i for a network key K derivation function 1101 can optionally include logic to detect a "collision", where the shared secret network key K 129d may already be used by a different module 101 using a different module identity 110 or network module identity 110b. In this case of a "collision" network 102 could take steps such as (i) requesting the module 101 derive a new and different shared secret key 129b (which could involve the use of a different random number 128a by module 101), or (ii) network 102 could take steps such that the same shared secret network key K 129d (in the case of a "collision) could be supported by two different modules 101 using two different module identities 110 or network module identities 110b.

As depicted in Figure 11, the output of key processing algorithm 141i within a network key K derivation algorithm 1101 can comprise a shared secret network key K 129d. A shared secret network key K 129d is also described in a step 909 depicted and described in connection with Figure 9b. Upon deriving the shared secret network key K 129d, MNO 108, using a server 105 or set of servers 1010 could record the value in within a module database 105k. The module database 105k could reside within an HSS or similar servers for an LTE and related networks. A module 101 could utilize a module key K derivation algorithm 909 in order to securely obtain the same value for shared secret network key K 129d. MNO 108 and wireless network 102 could then utilize the shared secret network key K 129d to connect with and/or authenticate a module 101 using the steps for a network in steps 910 and 911 depicted and described in connection with Figure 9b. In exemplary embodiments, module 101 and wireless network 102 could utilize the shared secret network key K 129d with the algorithms specified in ETSI TS 135 205 – 209, as well as subsequent and related standards, in order for module 101 to authenticate and/or connect with wireless network 102. Other possibilities exist as well without departing from the scope of the present invention.

Conclusion

Various exemplary embodiments have been described above. Those skilled in the art will understand, however, that changes and modifications may be made to those examples without departing from the scope of the claims.

Petitioner Samsung Ex-1004, 0176

CLAIMS

What is claimed is:

1. A mobile device comprising:

(a) an embedded Universal Integrated Circuit Card (eUICC);

(b) at least one processor; and

(c) a memory operatively connected to the at least one processor, the memory including processor executable code that, when executed by the at least one processor, causes the at least one processor to perform the steps of:

(1) recording, in the memory of the mobile device, (i) a mobile device public key and a mobile device private key, (ii) a pre-shared secret key, (iii) cryptographic parameters, and (iv) a mobile device identity;

(2) generating a message authentication code (MAC) using the pre-shared secret key for authentication with a first set of servers;

(3) receiving server encrypted data from the first set of servers, wherein the server encrypted data includes a set of the cryptographic parameters;

(4) decrypting the server encrypted data using the pre-shared secret key;

(5) storing a network public key, wherein the network public key is associated with (i) a second set of servers and (ii) a network private key;

(6) generating a mutually derived shared key using Elliptical Curve Diffie Hellman, wherein the mutually derived shared key is derived by the mobile device based on at least: (i) the mobile device private key; (ii) the network public key; and (iii) the set of the cryptographic parameters, wherein the mutually derived shared key is derived by the second set of servers based on at least:

Petitioner Samsung Ex-1004, 0177

(A) the mobile device public key associated with the mobile device private key;

(B) the network private key associated with the network public key; and

(C) the set of the cryptographic parameters;

(7) receiving from the second set of servers an encrypted profile for the eUICC; and

(8) decrypting the encrypted profile using the mutually derived shared key in order to store network access credentials.

2. The mobile device of claim 1, wherein the processor executable code, when executed by the at least one processor, further causes the at least one processor to generate module encrypted data associated with the first set of servers using the pre-shared secret key.

3. The mobile device of claim 2, wherein the module encrypted data includes at least a portion of the set of cryptographic parameters.

4. The mobile device of claim 1, wherein the set of the cryptographic parameters comprise a base point G.

5. The mobile device of claim 1, wherein the eUICC comprises a package soldered to a circuit board of the mobile device, and wherein the eUICC includes the at least one processor.

6. The mobile device of claim 1, wherein the network access credentials include at least a key K and a network module identity.

7. The mobile device of claim 1, wherein a module identity is stored in a protected nonvolatile memory.

8. The mobile device of claim 1, wherein the cryptographic parameters comprise values for defining an elliptic curve.

Petitioner Samsung Ex-1004, 0178

9. The mobile device of claim 1, wherein the processor executable code, when executed by the at least one processor, further causes the at least one processor to record a server identity and a port number for the first set of servers as part of element (c)(1).

10. The mobile device of claim 9, wherein the processor executable code, when executed by the at least one processor, further causes the at least one processor to generate a domain name system query for the first set of servers using the server identity after the recording in element (c)(1) and before the generating in element (c)(2).

11. The mobile device of claim 1, wherein the second set of servers (i) does not store the pre-shared secret key, and (ii) queries other servers for a certificate that includes a module public key.

12. The mobile device of claim 1, wherein the processor executable code, when executed by the at least one processor, further causes the at least one processor to perform steps of (i) receiving a server digital signature and (ii) verifying the server digital signature using a server public key prior to the generating in element (c)(6).

13. The mobile device of claim 12, wherein the server encrypted data includes the server digital signature.

14. The mobile device of claim 1, wherein the pre-shared secret key comprises a secret key that is shared between the mobile device and the first set of servers before the mobile device communicates with the first set of servers.

15. The mobile device of claim 1, wherein the mobile device performs a mutual authentication with the first set of servers using the pre-shared secret key.

Petitioner Samsung Ex-1004, 0179

16. The mobile device of claim 1, wherein the first set of servers is associated with an eUICC subscription manager.

17. The mobile device of claim 1, wherein the second set of servers is associated with a mobile network operator.

18. The mobile device of claim 1, wherein the processor executable code, when executed by the at least one processor, further causes the at least one processor to record a certificate for a module public key as part of the recording in element (c)(1), wherein the second set of servers receives the certificate using a module identity.

19. The mobile device of claim 1, wherein the processor executable code, when executed by the at least one processor, further causes the at least one processor to decrypt the encrypted profile using the mutually derived shared key in order to store network parameters as part of the decrypting in element (c)(8), wherein the network parameters include values for allowed radio frequency bands.

20. The mobile device of claim 1, wherein the eUICC includes the memory and the at least one processor.

21. The mobile device of claim 1, wherein the eUICC includes the at least one processor, and wherein the at least one processor comprises a separate cryptographic processing unit.

22. The mobile device of claim 1, wherein the memory comprises a nonvolatile memory connected to a system bus in the mobile device.


Petitioner Samsung Ex-1004, 0180

ABSTRACT

A module with an embedded universal integrated circuit card (eUICC) can include a received eUICC profile and a set of cryptographic algorithms. The received eUICC profile can include an initial shared secret key for authentication with a wireless network. The module can receive a key K network token and send a key K module token to the wireless network. The module can use the key K network token, a derived module private key, and a key derivation function to derive a secret shared network key K that supports communication with the wireless network. The wireless network can use the received key K module token, a network private key, and the key derivation function in order to derive the same secret shared network key K derived by the module. The module and the wireless network can subsequently use the mutually derived key K to communicate using traditional wireless network standards.

Petitioner Samsung Ex-1004, 0181

Figure 1a



Petitioner Samsung Ex-1004, 0182

Figure 1b






Figure 1c




Petitioner Samsung Ex-1004, 0183

Figure 1d



Petitioner Samsung Ex-1004, 0184

Figure 1e



Petitioner Samsung Ex-1004, 0185

Figure 1f






Figure 1g




Petitioner Samsung Ex-1004, 0186

Figure 1h



Petitioner Samsung Ex-1004, 0187

Figure 1i



Set of Cryptographic Parameters 126

Assymetric Ciphering Algorithms		
Standard Equations: 138	sect239k1, sect283k1, sect283r1	
Custom Equation:	Allowed	
Equation Values:	p, a, b, g, n 137	
Points formats:	ansiX962_compr_prime, uncompressed	
Symmetric Ciphering Algorithms		
Ciphers, key length:	AES - 128, 3TDEA, Serpent - 128	
Symmetric key vailidity:	> 1 day, <30 days	
Secure Hash Algorithms		
Algorithms, length:	SHA-224, SHA-256, SHA-384, SHA-3-512	
Digital Signature Algorithms		
Hash:	Any above	
Algorithm:	ECDSA, DSA	
Encoding Rules:	ASN.1 DER	
Key Pair Generation Algorithm		
Algorithms:	ECC	RSA
Length:	160-320;	2048 - 3072
Key pair validity:	>180 days, <730 Days	
General		
Security Token:	Mandatory	
Security Token Length:	>7 bytes, <20 bytes	
Module Identity:	Obfuscated - XOR, Algorithm A	
Certificate Required:	No	
Certificate Format:	X.509 v3	
Public key identity:	Yes	
Public key Authentication:	Last private key	
Public key encrypted:	Yes	
Padding:	Bit, ANSI X.923, PKCS7, other	
Padding For:	Hash, Digital Signature	126c
Key encoding:	ASN.1,	CSN.1
Encoding Rules:	BER	DER

Set "A"

Subset of Cryptographic Parameters 126a

141a **Assymetric Ciphering Algorithms**		
	Standard Equations:	sect239k1
	Custom Equation:	No
	Equation Values:	NA
	Points formats:	uncompressed
141b **Symmetric Ciphering Algorithms**		
	Ciphers, key length:	AES - 128 ← 155
	Symmetric key vailidity:	15 days ← 133
141c **Secure Hash Algorithms**		
	Algorithms, length:	SHA-256
141d **Digital Signature Algorithms**		
	Hash:	SHA-256
	Algorithm:	ECDSA ← 158
	Encoding Rules:	ASN.1 DER
141e **Key Pair Generation Algorithm**		
	Algorithms:	ECC ← 154
	Length:	239 bits ← 126e
	Key pair validity:	365 days
126b **General**		
401'	Security Token:	Yes
	Security Token Length:	8 bytes
110a'	Module Identity:	Obfuscasted - Algorithm A
122'	Certificate Required:	No
	Certificate Format:	NA
111a'	Public key identity:	Yes
517'	Public key Authentication:	Last private key
	Public key encrypted:	Yes
126c'	Padding:	Bit
	Padding For:	Hash, Digital Signature
126d'	Key encoding:	ASN.1
	Encoding Rules:	DER

Petitioner Samsung Ex-1004, 0188

Figure 1j

283 bit Elliptic Curve Key with SHA 256 Signature ("..." is long text removed)




Figure 1k






Figure 1m



Petitioner Samsung Ex-1004, 0190

Figure 2



Petitioner Samsung Ex-1004, 0191

Figure 3a





Figure 3b



Petitioner Samsung Ex-1004, 0192

Figure 4






Figure 5a




Petitioner Samsung Ex-1004, 0193

Figure 5b




Petitioner Samsung Ex-1004, 0194

Figure 6




Petitioner Samsung Ex-1004, 0195

Figure 7



Petitioner Samsung Ex-1004, 0196

Figure 8



Petitioner Samsung Ex-1004, 0197

Figure 9a






Figure 9b




Petitioner Samsung Ex-1004, 0198



Petitioner Samsung Ex-1004, 0199

Figure 11



Petitioner Samsung Ex-1004, 0200

Electronic Patent Application Fee Transmittal

Application Number:	
Filing Date:	
Title of Invention:	Key Derivation for a Module Using an Embedded Universal Integrated Circuit Card
First Named Inventor/Applicant Name:	John A. Nix
Filer:	Keith J. Barkaus/Victoria Gilmore
Attorney Docket Number:	63121/0224

Filed as Large Entity

Filing Fees for Utility under 35 USC 111(a)

Description	Fee Code	Quantity	Amount	Sub-Total in USD($)
Basic Filing:				
UTILITY APPLICATION FILING	1011	1	320	320
UTILITY SEARCH FEE	1111	1	700	700
UTILITY EXAMINATION FEE	1311	1	800	800
Pages:				
UTILITY APPL SIZE FEE PER 50 SHEETS >100	1081	1	420	420
Claims:				
CLAIMS IN EXCESS OF 20	1202	2	100	200
Miscellaneous-Filing:				

Description	Fee Code	Quantity	Amount	Sub-Total in USD($)
Petition:				
Patent-Appeals-and-Interference:				
Post-Allowance-and-Post-Issuance:				
Extension-of-Time:				
Miscellaneous:				
		Total in USD ($)		**2440**

Electronic Acknowledgement Receipt

EFS ID:	48387744
Application Number:	18229907
International Application Number:	
Confirmation Number:	7483
Title of Invention:	Key Derivation for a Module Using an Embedded Universal Integrated Circuit Card
First Named Inventor/Applicant Name:	John A. Nix
Customer Number:	1912
Filer:	Keith J. Barkaus/Victoria Gilmore
Filer Authorized By:	Keith J. Barkaus
Attorney Docket Number:	63121/0224
Receipt Date:	03-AUG-2023
Filing Date:	
Time Stamp:	15:07:06
Application Type:	Utility under 35 USC 111(a)

Payment information:

Submitted with Payment	yes
Payment Type	CARD
Payment was successfully received in RAM	$2440
RAM confirmation Number	E202383F07216625
Deposit Account	
Authorized User	
The Director of the USPTO is hereby authorized to charge indicated fees and credit any overpayment as follows:	

File Listing:

Document Number	Document Description	File Name	File Size(Bytes)/ Message Digest	Multi Part /.zip	Pages (if appl.)
1	Application Data Sheet	WebADS.pdf	196022 59b6feebae8729ed521794c41ce9bfd2e098dd8a	no	8
Warnings:					
Information:					
2	Power of Attorney	2-PowerofAtty.pdf	184547 36207b52901615105711ca64016a2e98a690112a	no	2
Warnings:					
Information:					
3	Oath or Declaration filed	3-Parent_Declaration.pdf	133299 1fde18adab666a6b2db64566ce55c7d5663f6548	no	1
Warnings:					
Information:					
4		4-Specification.pdf	616428 bb5dfa9c3524ff397bf32111287719bcac67eee6	yes	178

Multipart Description/PDF files in .zip description

Document Description	Start	End
Specification	1	173
Claims	174	177
Abstract	178	178

Warnings:					
Information:					
5	Drawings-only black and white line drawings	5-Figs.pdf	502597 635039ec385c5d05e0ae452f323ea37a034f8a59	no	19

Warnings:					
Information:					
6	Fee Worksheet (SB06)	fee-info.pdf	48771 37e9050c8748d1ec6ceb1b0fa476e627dc151d66	no	2
Warnings:					
Information:					
			Total Files Size (in bytes):	1681664	

This Acknowledgement Receipt evidences receipt on the noted date by the USPTO of the indicated documents, characterized by the applicant, and including page counts, where applicable. It serves as evidence of receipt similar to a Post Card, as described in MPEP 503.

New Applications Under 35 U.S.C. 111

If a new application is being filed and the application includes the necessary components for a filing date (see 37 CFR 1.53(b)-(d) and MPEP 506), a Filing Receipt (37 CFR 1.54) will be issued in due course and the date shown on this Acknowledgement Receipt will establish the filing date of the application.

National Stage of an International Application under 35 U.S.C. 371

If a timely submission to enter the national stage of an international application is compliant with the conditions of 35 U.S.C. 371 and other applicable requirements a Form PCT/DO/EO/903 indicating acceptance of the application as a national stage submission under 35 U.S.C. 371 will be issued in addition to the Filing Receipt, in due course.

New International Application Filed with the USPTO as a Receiving Office

If a new international application is being filed and the international application includes the necessary components for an international filing date (see PCT Article 11 and MPEP 1810), a Notification of the International Application Number and of the International Filing Date (Form PCT/RO/105) will be issued in due course, subject to prescriptions concerning national security, and the date shown on this Acknowledgement Receipt will establish the international filing date of the application.

Application Data Sheet 37 CFR 1.76	Attorney Docket Number	63121/0224
	Application Number	
Title of Invention	Key Derivation for a Module Using an Embedded Universal Integrated Circuit Card	

The application data sheet is part of the provisional or nonprovisional application for which it is being submitted. The following form contains the bibliographic data arranged in a format specified by the United States Patent and Trademark Office as outlined in 37 CFR 1.76.
This document may be completed electronically and submitted to the Office in electronic format using the Electronic Filing System (EFS) or the document may be printed and included in a paper filed application.

Secrecy Order 37 CFR 5.2:

☐ Portions or all of the application associated with this Application Data Sheet may fall under a Secrecy Order pursuant to 37 CFR 5.2 (Paper filers only. Applications that fall under Secrecy Order may not be filed electronically.)

Inventor Information:

Inventor 1

Legal Name

Prefix	Given Name	Middle Name	Family Name	Suffix
	John	A.	Nix	

Residence Information (Select One) ◉ US Residency ○ Non US Residency ○ Active US Military Service

City	Evanston	State/Province	IL	Country of Residence i	US

Mailing Address of Inventor:

Address 1	807 Davis Street, Unit 409		
Address 2			
City	Evanston	State/Province	IL
Postal Code	60201	Country i	US

All Inventors Must Be Listed - Additional Inventor Information blocks may be generated within this form by selecting the **Add** button. Add

Correspondence Information:

Enter either Customer Number or complete the Correspondence Information section below.
For further information see 37 CFR 1.33(a).

☐ **An Address is being provided for the correspondence Information of this application.**

Customer Number	1912		
Email Address	ptodocket@arelaw.com	Add Email	Remove Email

Application Information:

Title of the Invention	Key Derivation for a Module Using an Embedded Universal Integrated Circuit Card		
Attorney Docket Number	63121/0224	Small Entity Status Claimed	☐
Application Type	Nonprovisional		
Subject Matter	Utility		
Total Number of Drawing Sheets (if any)	19	Suggested Figure for Publication (if any)	

PTO/AIA/14 (08-15)
Approved for use through 04/30/2017. OMB 0651-0032
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

Application Data Sheet 37 CFR 1.76	Attorney Docket Number	63121/0224
	Application Number	
Title of Invention	Key Derivation for a Module Using an Embedded Universal Integrated Circuit Card	

Filing By Reference:

Only complete this section when filing an application by reference under 35 U.S.C. 111(c) and 37 CFR 1.57(a). Do not complete this section if application papers including a specification and any drawings are being filed. Any domestic benefit or foreign priority information must be provided in the appropriate section(s) below (i.e., "Domestic Benefit/National Stage Information" and "Foreign Priority Information").

For the purposes of a filing date under 37 CFR 1.53(b), the description and any drawings of the present application are replaced by this reference to the previously filed application, subject to conditions and requirements of 37 CFR 1.57(a).

Application number of the previously filed application	Filing date (YYYY-MM-DD)	Intellectual Property Authority or Country

Publication Information:

☐ Request Early Publication (Fee required at time of Request 37 CFR 1.219)

☐ **Request Not to Publish.** I hereby request that the attached application not be published under 35 U.S.C. 122(b) and certify that the invention disclosed in the attached application **has not and will not** be the subject of an application filed in another country, or under a multilateral international agreement, that requires publication at eighteen months after filing.

Representative Information:

Representative information should be provided for all practitioners having a power of attorney in the application. Providing this information in the Application Data Sheet does not constitute a power of attorney in the application (see 37 CFR 1.32).
Either enter Customer Number or complete the Representative Name section below. If both sections are completed the customer Number will be used for the Representative Information during processing.

Please Select One:	◉ Customer Number	○ US Patent Practitioner	○ Limited Recognition (37 CFR 11.9)
Customer Number	1912		

Prefix	**Given Name**	Middle Name	**Family Name**	Suffix	Remove
Registration Number					
Prefix	**Given Name**	Middle Name	**Family Name**	Suffix	Remove
Registration Number					

Additional Representative Information blocks may be generated within this form by selecting the **Add** button.

PTO/AIA/14 (08-15)
Approved for use through 04/30/2017. OMB 0651-0032
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

Application Data Sheet 37 CFR 1.76	Attorney Docket Number	63121/0224
	Application Number	
Title of Invention	Key Derivation for a Module Using an Embedded Universal Integrated Circuit Card	

Domestic Benefit/National Stage Information:

This section allows for the applicant to either claim benefit under 35 U.S.C. 119(e), 120, 121, 365(c), or 386(c) or indicate National Stage entry from a PCT application. Providing benefit claim information in the Application Data Sheet constitutes the specific reference required by 35 U.S.C. 119(e) or 120, and 37 CFR 1.78.
When referring to the current application, please leave the "Application Number" field blank.

Prior Application Status	Pending		Remove
Application Number	Continuity Type	Prior Application Number	Filing or 371(c) Date (YYYY-MM-DD)
	Continuation of	17304922	2021-06-28

Prior Application Status	Patented				Remove
Application Number	Continuity Type	Prior Application Number	Filing Date (YYYY-MM-DD)	Patent Number	Issue Date (YYYY-MM-DD)
17304922	Continuation of	16879325	2020-05-20	11082218	2021-08-03

Prior Application Status	Patented				Remove
Application Number	Continuity Type	Prior Application Number	Filing Date (YYYY-MM-DD)	Patent Number	Issue Date (YYYY-MM-DD)
16879325	Continuation of	16201401	2018-11-27	10700856	2020-06-30

Prior Application Status	Patented				Remove
Application Number	Continuity Type	Prior Application Number	Filing Date (YYYY-MM-DD)	Patent Number	Issue Date (YYYY-MM-DD)
16201401	Continuation of	15680758	2017-08-18	10187206	2019-01-22

Prior Application Status	Patented				Remove
Application Number	Continuity Type	Prior Application Number	Filing Date (YYYY-MM-DD)	Patent Number	Issue Date (YYYY-MM-DD)
15680758	Continuation of	15130146	2016-04-15	9742562	2017-08-22

Prior Application Status	Patented				Remove
Application Number	Continuity Type	Prior Application Number	Filing Date (YYYY-MM-DD)	Patent Number	Issue Date (YYYY-MM-DD)
15130146	Continuation of	14084141	2013-11-19	9319223	2016-04-19

Additional Domestic Benefit/National Stage Data may be generated within this form by selecting the **Add** button.

Foreign Priority Information:

PTO/AIA/14 (08-15)
Approved for use through 04/30/2017. OMB 0651-0032
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

Application Data Sheet 37 CFR 1.76	Attorney Docket Number	63121/0224
	Application Number	
Title of Invention	Key Derivation for a Module Using an Embedded Universal Integrated Circuit Card	

This section allows for the applicant to claim priority to a foreign application. Providing this information in the application data sheet constitutes the claim for priority as required by 35 U.S.C. 119(b) and 37 CFR 1.55. When priority is claimed to a foreign application that is eligible for retrieval under the priority document exchange program (PDX) the information will be used by the Office to automatically attempt retrieval pursuant to 37 CFR 1.55(i)(1) and (2). Under the PDX program, applicant bears the ultimate responsibility for ensuring that a copy of the foreign application is received by the Office from the participating foreign intellectual property office, or a certified copy of the foreign priority application is filed, within the time period specified in 37 CFR 1.55(g)(1).

Application Number	Country[i]	Filing Date (YYYY-MM-DD)	Access Code[i] (if applicable)
	US		

Additional Foreign Priority Data may be generated within this form by selecting the **Add** button.

Statement under 37 CFR 1.55 or 1.78 for AIA (First Inventor to File) Transition Applications

☐ This application (1) claims priority to or the benefit of an application filed before March 16, 2013 and (2) also contains, or contained at any time, a claim to a claimed invention that has an effective filing date on or after March 16, 2013.
NOTE: By providing this statement under 37 CFR 1.55 or 1.78, this application, with a filing date on or after March 16, 2013, will be examined under the first inventor to file provisions of the AIA.

PTO/AIA/14 (08-15)
Approved for use through 04/30/2017. OMB 0651-0032
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

Application Data Sheet 37 CFR 1.76	Attorney Docket Number	63121/0224
	Application Number	
Title of Invention	Key Derivation for a Module Using an Embedded Universal Integrated Circuit Card	

Authorization or Opt-Out of Authorization to Permit Access:

When this Application Data Sheet is properly signed and filed with the application, applicant has provided written authority to permit a participating foreign intellectual property (IP) office access to the instant application-as-filed (see paragraph A in subsection 1 below) and the European Patent Office (EPO) access to any search results from the instant application (see paragraph B in subsection 1 below).

Should applicant choose not to provide an authorization identified in subsection 1 below, applicant **must opt-out** of the authorization by checking the corresponding box A or B or both in subsection 2 below.

NOTE: This section of the Application Data Sheet is **ONLY** reviewed and processed with the **INITIAL** filing of an application. After the initial filing of an application, an Application Data Sheet cannot be used to provide or rescind authorization for access by a foreign IP office(s). Instead, Form PTO/SB/39 or PTO/SB/69 must be used as appropriate.

1. Authorization to Permit Access by a Foreign Intellectual Property Office(s)

A. Priority Document Exchange (PDX) - Unless box A in subsection 2 (opt-out of authorization) is checked, the undersigned hereby **grants the USPTO authority** to provide the European Patent Office (EPO), the Japan Patent Office (JPO), the Korean Intellectual Property Office (KIPO), the State Intellectual Property Office of the People's Republic of China (SIPO), the World Intellectual Property Organization (WIPO), and any other foreign intellectual property office participating with the USPTO in a bilateral or multilateral priority document exchange agreement in which a foreign application claiming priority to the instant patent application is filed, access to: (1) the instant patent application-as-filed and its related bibliographic data, (2) any foreign or domestic application to which priority or benefit is claimed by the instant application and its related bibliographic data, and (3) the date of filing of this Authorization. See 37 CFR 1.14(h)(1).

B. Search Results from U.S. Application to EPO - Unless box B in subsection 2 (opt-out of authorization) is checked, the undersigned hereby **grants the USPTO authority** to provide the EPO access to the bibliographic data and search results from the instant patent application when a European patent application claiming priority to the instant patent application is filed. See 37 CFR 1.14(h)(2).

The applicant is reminded that the EPO's Rule 141(1) EPC (European Patent Convention) requires applicants to submit a copy of search results from the instant application without delay in a European patent application that claims priority to the instant application.

2. Opt-Out of Authorizations to Permit Access by a Foreign Intellectual Property Office(s)

☐ A. Applicant **DOES NOT** authorize the USPTO to permit a participating foreign IP office access to the instant application-as-filed. If this box is checked, the USPTO will not be providing a participating foreign IP office with any documents and information identified in subsection 1A above.

☐ B. Applicant **DOES NOT** authorize the USPTO to transmit to the EPO any search results from the instant patent application. If this box is checked, the USPTO will not be providing the EPO with search results from the instant application.

NOTE: Once the application has published or is otherwise publicly available, the USPTO may provide access to the application in accordance with 37 CFR 1.14.

PTO/AIA/14 (08-15)
Approved for use through 04/30/2017. OMB 0651-0032
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

Application Data Sheet 37 CFR 1.76	Attorney Docket Number	63121/0224
	Application Number	
Title of Invention	Key Derivation for a Module Using an Embedded Universal Integrated Circuit Card	

Applicant Information:

Providing assignment information in this section does not substitute for compliance with any requirement of part 3 of Title 37 of CFR to have an assignment recorded by the Office.

Applicant 1

If the applicant is the inventor (or the remaining joint inventor or inventors under 37 CFR 1.45), this section should not be completed. The information to be provided in this section is the name and address of the legal representative who is the applicant under 37 CFR 1.43; or the name and address of the assignee, person to whom the inventor is under an obligation to assign the invention, or person who otherwise shows sufficient proprietary interest in the matter who is the applicant under 37 CFR 1.46. If the applicant is an applicant under 37 CFR 1.46 (assignee, person to whom the inventor is obligated to assign, or person who otherwise shows sufficient proprietary interest) together with one or more joint inventors, then the joint inventor or inventors who are also the applicant should be identified in this section.

Clear

◉ Assignee	○ Legal Representative under 35 U.S.C. 117	○ Joint Inventor
○ Person to whom the inventor is obligated to assign.	○ Person who shows sufficient proprietary interest	

If applicant is the legal representative, indicate the authority to file the patent application, the inventor is:

Name of the Deceased or Legally Incapacitated Inventor:	

If the Applicant is an Organization check here. ☒

Organization Name	Network-1 Technologies, Inc.

Mailing Address Information For Applicant:

Address 1	445 Park Avenue, Suite 912		
Address 2			
City	New York	**State/Province**	NY
Country[i]	US	Postal Code	10022
Phone Number		Fax Number	
Email Address			

Additional Applicant Data may be generated within this form by selecting the Add button.

PTO/AIA/14 (08-15)
Approved for use through 04/30/2017. OMB 0651-0032
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

Application Data Sheet 37 CFR 1.76	Attorney Docket Number	63121/0224
	Application Number	
Title of Invention	Key Derivation for a Module Using an Embedded Universal Integrated Circuit Card	

Assignee Information including Non-Applicant Assignee Information:

Providing assignment information in this section does not substitute for compliance with any requirement of part 3 of Title 37 of CFR to have an assignment recorded by the Office.

Assignee 1

Complete this section if assignee information, including non-applicant assignee information, is desired to be included on the patent application publication. An assignee-applicant identified in the "Applicant Information" section will appear on the patent application publication as an applicant. For an assignee-applicant, complete this section only if identification as an assignee is also desired on the patent application publication.

If the Assignee or Non-Applicant Assignee is an Organization check here. ☐

Prefix	**Given Name**	Middle Name	**Family Name**	Suffix

Mailing Address Information For Assignee including Non-Applicant Assignee:

Address 1			
Address 2			
City		**State/Province**	
Country i		Postal Code	
Phone Number		Fax Number	
Email Address			

Additional Assignee or Non-Applicant Assignee Data may be generated within this form by selecting the Add button.

PTO/AIA/14 (08-15)
Approved for use through 04/30/2017. OMB 0651-0032
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

Application Data Sheet 37 CFR 1.76	Attorney Docket Number	63121/0224
	Application Number	
Title of Invention	Key Derivation for a Module Using an Embedded Universal Integrated Circuit Card	

Signature:

NOTE: This Application Data Sheet must be signed in accordance with 37 CFR 1.33(b). **However, if this Application Data Sheet is submitted with the INITIAL filing of the application and either box A or B is not checked in subsection 2 of the "Authorization or Opt-Out of Authorization to Permit Access" section, then this form must also be signed in accordance with 37 CFR 1.14(c).**

This Application Data Sheet **must** be signed by a patent practitioner if one or more of the applicants is a **juristic entity** (e. g., corporation or association). If the applicant is two or more joint inventors, this form must be signed by a patent practitioner, **all** joint inventors who are the applicant, or one or more joint inventor-applicants who have been given power of attorney (e.g., see USPTO Form PTO/AIA/81) on behalf of **all** joint inventor-applicants.

See 37 CFR 1.4(d) for the manner of making signatures and certifications.

Signature	/Keith J. Barkaus/			Date (YYYY-MM-DD)	
First Name	Keith J.	Last Name	Barkaus	Registration Number	51431

Additional Signature may be generated within this form by selecting the Add button.

UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NUMBER	FILING or 371(c) DATE	GRP ART UNIT	FIL FEE REC'D	ATTY.DOCKET.NO	TOT CLAIMS	IND CLAIMS
18/229,907	08/03/2023		2440	63121/0224	22	1

CONFIRMATION NO. 7483

FILING RECEIPT

1912
AMSTER, ROTHSTEIN & EBENSTEIN LLP
405 LEXINGTON AVENUE
FLOOR 48
NEW YORK, NY 10174

OC000000060660297

Date Mailed: 08/16/2023

Receipt is acknowledged of this non-provisional utility patent application. The application will be taken up for examination in due course. Applicant will be notified as to the results of the examination. Any correspondence concerning the application must include the following identification information: the U.S. APPLICATION NUMBER, FILING DATE, NAME OF FIRST INVENTOR, and TITLE OF INVENTION. Fees transmitted by check or draft are subject to collection.

Please verify the accuracy of the data presented on this receipt. If an error is noted on this Filing Receipt, please submit a written request for a corrected Filing Receipt, including a properly marked-up ADS showing the changes with strike-through for deletions and underlining for additions. If you received a "Notice to File Missing Parts" or other Notice requiring a response for this application, please submit any request for correction to this Filing Receipt with your reply to the Notice. When the USPTO processes the reply to the Notice, the USPTO will generate another Filing Receipt incorporating the requested corrections provided that the request is grantable.

Inventor(s)

John A. Nix, Evanston, IL;

Applicant(s)

Network-1 Technologies, Inc., New York, NY;

Power of Attorney: The patent practitioners associated with Customer Number 1912

Domestic Priority data as claimed by applicant

This application is a CON of 17/304,922 06/28/2021 PAT 11,736,283
which is a CON of 16/879,325 05/20/2020 PAT 11,082,218
which is a CON of 16/201,401 11/27/2018 PAT 10,700,856
which is a CON of 15/680,758 08/18/2017 PAT 10,187,206
which is a CON of 15/130,146 04/15/2016 PAT 9,742,562
which is a CON of 14/084,141 11/19/2013 PAT 9,319,223

Foreign Applications for which priority is claimed (You may be eligible to benefit from the **Patent Prosecution Highway** program at the USPTO. Please see http://www.uspto.gov for more information.) - None.
Foreign application information must be provided in an Application Data Sheet in order to constitute a claim to foreign priority. See 37 CFR 1.55 and 1.76.

Permission to Access Application via Priority Document Exchange: Yes

Permission to Access Search Results: Yes

Petitioner Samsung Ex-1004, 0214

Applicant may provide or rescind an authorization for access using Form PTO/SB/39 or Form PTO/SB/69 as appropriate.

If Required, Foreign Filing License Granted: 08/15/2023
The country code and number of your priority application, to be used for filing abroad under the Paris Convention, is **US 18/229,907**
Projected Publication Date: 11/23/2023
Non-Publication Request: No
Early Publication Request: No
Title

Key Derivation for a Module Using an Embedded Universal Integrated Circuit Card

Preliminary Class

Statement under 37 CFR 1.55 or 1.78 for AIA (First Inventor to File) Transition Applications: No

PROTECTING YOUR INVENTION OUTSIDE THE UNITED STATES

Since the rights granted by a U.S. patent extend only throughout the territory of the United States and have no effect in a foreign country, an inventor who wishes patent protection in another country must apply for a patent in a specific country or in regional patent offices. Applicants may wish to consider the filing of an international application under the Patent Cooperation Treaty (PCT). An international (PCT) application generally has the same effect as a regular national patent application in each PCT-member country. The PCT process **simplifies** the filing of patent applications on the same invention in member countries, but **does not result** in a grant of "an international patent" and does not eliminate the need of applicants to file additional documents and fees in countries where patent protection is desired.

Almost every country has its own patent law, and a person desiring a patent in a particular country must make an application for patent in that country in accordance with its particular laws. Since the laws of many countries differ in various respects from the patent law of the United States, applicants are advised to seek guidance from specific foreign countries to ensure that patent rights are not lost prematurely.

Applicants also are advised that in the case of inventions made in the United States, the Director of the USPTO must issue a license before applicants can apply for a patent in a foreign country. The filing of a U.S. patent application serves as a request for a foreign filing license. The application's filing receipt contains further information and guidance as to the status of applicant's license for foreign filing.

Applicants may wish to consult the USPTO booklet, "General Information Concerning Patents" (specifically, the section entitled "Treaties and Foreign Patents") for more information on timeframes and deadlines for filing foreign patent applications. The guide is available either by contacting the USPTO Contact Center at 800-786-9199, or it can be viewed on the USPTO website at http://www.uspto.gov/web/offices/pac/doc/general/index.html.

For information on preventing theft of your intellectual property (patents, trademarks and copyrights), you may wish to consult the U.S. Government website, http://www.stopfakes.gov. Part of a Department of Commerce initiative, this website includes self-help "toolkits" giving innovators guidance on how to protect intellectual property in specific countries such as China, Korea and Mexico. For questions regarding patent enforcement issues, applicants may call the U.S. Government hotline at 1-866-999-HALT (1-866-999-4258).

Petitioner Samsung Ex-1004, 0215

LICENSE FOR FOREIGN FILING UNDER

Title 35, United States Code, Section 184

Title 37, Code of Federal Regulations, 5.11 & 5.15

GRANTED

The applicant has been granted a license under 35 U.S.C. 184, if the phrase "IF REQUIRED, FOREIGN FILING LICENSE GRANTED" followed by a date appears on this form. Such licenses are issued in all applications where the conditions for issuance of a license have been met, regardless of whether or not a license may be required as set forth in 37 CFR 5.15. The scope and limitations of this license are set forth in 37 CFR 5.15(a) unless an earlier license has been issued under 37 CFR 5.15(b). The license is subject to revocation upon written notification. The date indicated is the effective date of the license, unless an earlier license of similar scope has been granted under 37 CFR 5.13 or 5.14.

This license is to be retained by the licensee and may be used at any time on or after the effective date thereof unless it is revoked. This license is automatically transferred to any related applications(s) filed under 37 CFR 1.53(d). This license is not retroactive.

The grant of a license does not in any way lessen the responsibility of a licensee for the security of the subject matter as imposed by any Government contract or the provisions of existing laws relating to espionage and the national security or the export of technical data. Licensees should apprise themselves of current regulations especially with respect to certain countries, of other agencies, particularly the Office of Defense Trade Controls, Department of State (with respect to Arms, Munitions and Implements of War (22 CFR 121-128)); the Bureau of Industry and Security, Department of Commerce (15 CFR parts 730-774); the Office of Foreign AssetsControl, Department of Treasury (31 CFR Parts 500+) and the Department of Energy.

NOT GRANTED

No license under 35 U.S.C. 184 has been granted at this time, if the phrase "IF REQUIRED, FOREIGN FILING LICENSE GRANTED" DOES NOT appear on this form. Applicant may still petition for a license under 37 CFR 5.12, if a license is desired before the expiration of 6 months from the filing date of the application. If 6 months has lapsed from the filing date of this application and the licensee has not received any indication of a secrecy order under 35 U.S.C. 181, the licensee may foreign file the application pursuant to 37 CFR 5.15(b).

SelectUSA

The United States represents the largest, most dynamic marketplace in the world and is an unparalleled location for business investment, innovation, and commercialization of new technologies. The U.S. offers tremendous resources and advantages for those who invest and manufacture goods here. Through SelectUSA, our nation works to promote and facilitate business investment. SelectUSA provides information assistance to the international investor community; serves as an ombudsman for existing and potential investors; advocates on behalf of U.S. cities, states, and regions competing for global investment; and counsels U.S. economic development organizations on investment attraction best practices. To learn more about why the United States is the best country in the world to develop technology, manufacture products, deliver services, and grow your business, visit http://www.SelectUSA.gov or call +1-202-482-6800.

PATENT APPLICATION FEE DETERMINATION RECORD

Substitute for Form PTO-875

Application or Docket Number: 18/229,907

APPLICATION AS FILED - PART I

FOR	(Column 1) NUMBER FILED	(Column 2) NUMBER EXTRA	SMALL ENTITY RATE($)	SMALL ENTITY FEE($)	OR	OTHER THAN SMALL ENTITY RATE($)	OTHER THAN SMALL ENTITY FEE($)
BASIC FEE (37 CFR 1.16(a), (b), or (c))	N/A	N/A	N/A			N/A	320
SEARCH FEE (37 CFR 1.16(k), (i), or (m))	N/A	N/A	N/A			N/A	700
EXAMINATION FEE (37 CFR 1.16(o), (p), or (q))	N/A	N/A	N/A			N/A	800
TOTAL CLAIMS (37 CFR 1.16(i))	22 minus 20 =	* 2			OR	x 100 =	200
INDEPENDENT CLAIMS (37 CFR 1.16(h))	1 minus 3 =	*				x =	0
APPLICATION SIZE FEE (37 CFR 1.16(s))	If the specification and drawings exceed 100 sheets of paper, the application size fee due is $310 ($155 for small entity) for each additional 50 sheets or fraction thereof. See 35 U.S.C. 41(a)(1)(G) and 37 CFR 1.16(s).						420
MULTIPLE DEPENDENT CLAIM PRESENT (37 CFR 1.16(j))							0
* If the difference in column 1 is less than zero, enter "0" in column 2.			TOTAL			TOTAL	2240

APPLICATION AS AMENDED - PART II

		(Column 1) CLAIMS REMAINING AFTER AMENDMENT		(Column 2) HIGHEST NUMBER PREVIOUSLY PAID FOR	(Column 3) PRESENT EXTRA	SMALL ENTITY RATE($)	SMALL ENTITY ADDITIONAL FEE($)	OR	OTHER THAN SMALL ENTITY RATE($)	OTHER THAN SMALL ENTITY ADDITIONAL FEE($)
AMENDMENT A	Total (37 CFR 1.16(i))	*	Minus	**	=	x =		OR	x =	
	Independent (37 CFR 1.16(h))	*	Minus	***	=	x =		OR	x =	
	Application Size Fee (37 CFR 1.16(s))									
	FIRST PRESENTATION OF MULTIPLE DEPENDENT CLAIM (37 CFR 1.16(j))							OR		
						TOTAL ADD'L FEE		OR	TOTAL ADD'L FEE	

		(Column 1) CLAIMS REMAINING AFTER AMENDMENT		(Column 2) HIGHEST NUMBER PREVIOUSLY PAID FOR	(Column 3) PRESENT EXTRA	RATE($)	ADDITIONAL FEE($)		RATE($)	ADDITIONAL FEE($)
AMENDMENT B	Total (37 CFR 1.16(i))	*	Minus	**	=	x =		OR	x =	
	Independent (37 CFR 1.16(h))	*	Minus	***	=	x =		OR	x =	
	Application Size Fee (37 CFR 1.16(s))									
	FIRST PRESENTATION OF MULTIPLE DEPENDENT CLAIM (37 CFR 1.16(j))							OR		
						TOTAL ADD'L FEE		OR	TOTAL ADD'L FEE	

* If the entry in column 1 is less than the entry in column 2, write "0" in column 3.

** If the "Highest Number Previously Paid For" IN THIS SPACE is less than 20, enter "20".

*** If the "Highest Number Previously Paid For" IN THIS SPACE is less than 3, enter "3".

The "Highest Number Previously Paid For" (Total or Independent) is the highest found in the appropriate box in column 1.

UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NUMBER	FILING OR 371(C) DATE	FIRST NAMED APPLICANT	ATTY. DOCKET NO./TITLE
18/229,907	08/03/2023	John A. Nix	63121/0224

CONFIRMATION NO. 7483

1912
AMSTER, ROTHSTEIN & EBENSTEIN LLP
405 LEXINGTON AVENUE
FLOOR 48
NEW YORK, NY 10174

PUBLICATION NOTICE



Date Mailed: 11/24/2023

Title: Key Derivation for a Module Using an Embedded Universal Integrated Circuit Card

Publication No.US-2023-0379148-A1
Publication Date:11/23/2023

NOTICE OF PUBLICATION OF APPLICATION

The above-identified application will be electronically published as a patent application publication pursuant to 37 CFR 1.211, et seq. The patent application publication number and publication date are set forth above.

The publication may be accessed through the USPTO's publically available Searchable Databases via the Internet at www.uspto.gov. The direct link to access the publication is currently http://www.uspto.gov/patft/.

The publication process established by the Office does not provide for mailing a copy of the publication to applicant. A copy of the publication may be obtained from the Office upon payment of the appropriate fee set forth in 37 CFR 1.19(a)(1). Orders for copies of patent application publications are handled by the USPTO's Public Records Division. The Public Records Division can be reached by telephone at (571) 272-3150 or (800) 972-6382, by facsimile at (571) 273-3250, by mail addressed to the United States Patent and Trademark Office, Public Records Division, Alexandria, VA 22313-1450 or via the Internet.

In addition, information on the status of the application, including the mailing date of Office actions and the dates of receipt of correspondence filed in the Office, may also be accessed via the Internet through the Patent Electronic Business Center at www.uspto.gov using the public side of the Patent Application Information and Retrieval (PAIR) system. The direct link to access this status information is currently https://portal.uspto.gov/pair/PublicPair. Prior to publication, such status information is confidential and may only be obtained by applicant using the private side of PAIR.

Further assistance in electronically accessing the publication, or about PAIR, is available by calling the Patent Electronic Business Center at 1-866-217-9197.

Office of Data Managment, Application Assistance Unit (571) 272-4000, or (571) 272-4200, or 1-888-786-0101

Petitioner Samsung Ex-1004, 0218

PTO/SB/08a (02-18)
Approved for use through 11/30/2020. OMB 0651-0031
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

INFORMATION DISCLOSURE STATEMENT BY APPLICANT

(Not for submission under 37 CFR 1.99)

Application Number	18229907
Filing Date	2023-08-03
First Named Inventor	John A. Nix
Art Unit	
Examiner Name	
Attorney Docket Number	63121/0224

U.S.PATENTS Remove

Examiner Initial*	Cite No	Patent Number	Kind Code[1]	Issue Date	Name of Patentee or Applicant of cited Document	Pages,Columns,Lines where Relevant Passages or Relevant Figures Appear
	1	10169587	B1	2019-01-01	Nix	
	2	10621352	B2	2020-04-14	NIx	

If you wish to add additional U.S. Patent citation information please click the Add button. Add

U.S.PATENT APPLICATION PUBLICATIONS Remove

Examiner Initial*	Cite No	Publication Number	Kind Code[1]	Publication Date	Name of Patentee or Applicant of cited Document	Pages,Columns,Lines where Relevant Passages or Relevant Figures Appear
	1	20060021063	A1	2006-01-26	Hori	
	2	20100093347	A1	2010-04-15	Hahn et al.	
	3	20110158411	A1	2011-06-30	Medvinsky et al.	
	4	20210126801	A1	2021-04-29	Nix	

INFORMATION DISCLOSURE STATEMENT BY APPLICANT (Not for submission under 37 CFR 1.99)		
	Application Number	18229907
	Filing Date	2023-08-03
	First Named Inventor	John A. Nix
	Art Unit	
	Examiner Name	
	Attorney Docket Number	63121/0224

	5	20200280436	A1	2020-09-03	Nix	
	6	20210218560	A1	2021-07-15	Nix	
	7	20210184842	A1	2021-06-17	Nix	
	8	20210194681	A1	2021-06-24	Nix	
	9	20190356482	A1	2019-11-21	Nix	
	10	20200226258	A1	2020-07-16	Nix	
	11	20190313246	A1	2019-10-10	Nix	
	12	20210211279	A1	2021-07-08	Nix	
	13	20200162269	A1	2020-05-21	Nix	
	14	20200162247	A1	2020-05-21	Nix	
	15	20190332774	A1	2019-10-31	Nix	

INFORMATION DISCLOSURE STATEMENT BY APPLICANT (Not for submission under 37 CFR 1.99)		
	Application Number	18229907
	Filing Date	2023-08-03
	First Named Inventor	John A. Nix
	Art Unit	
	Examiner Name	
	Attorney Docket Number	63121/0224

	16	20110167272	A1	2011-07-07	Vladimir Y. Kolesnikov	

If you wish to add additional U.S. Published Application citation information please click the Add button. Add

FOREIGN PATENT DOCUMENTS Remove

Examiner Initial*	Cite No	Foreign Document Number[3]	Country Code[2] ¡	Kind Code[4]	Publication Date	Name of Patentee or Applicant of cited Document	Pages,Columns,Lines where Relevant Passages or Relevant Figures Appear	T[5]
	1	2518976	GB	A	2015-04-08	Vodafone IP Licensing Ltd		☐
	2	2021007235	WO	A1	2021-01-14	Nix		☐
	3	2021007235	WO	A1	2021-01-14	Nix		☐
	4	2021087221	WO	A1	2021-05-06	Nix		☐
	5	2020223319	WO	A1	2020-11-05	Nix		☐
	6	2020006162	WO	A1	2020-01-02	Nix		☐
	7	2019246206	WO	A1	2019-12-26	Nix		☐
	8	2019222319	WO	A1	2019-11-21	Nix		☐

INFORMATION DISCLOSURE STATEMENT BY APPLICANT (Not for submission under 37 CFR 1.99)		
	Application Number	18229907
	Filing Date	2023-08-03
	First Named Inventor	John A. Nix
	Art Unit	
	Examiner Name	
	Attorney Docket Number	63121/0224

	9	2019209598	WO	A1	2019-10-31	Nix		☐
	10	2019178312	WO	A1	2019-09-19	Nix		☐
	11	2020123959	WO	A1	2020-06-18	Nix		☐
	12	2020061023	WO	A1	2020-03-26	Nix		☐
	13	3110641	CA	A1	2019-10-31	Nix		☐
	14	3110468	CA	A1	2019-11-21	Nix		☐
	15	19803936	DE	A1	1999-08-05	Osram GmbH Siemens AG		☐
	16	3766222	EP	A1	2021-01-20	Nix		☐
	17	20130026351	KR	A	2013-03-13	SAMSUNG ELECTRONICS CO LTD	English Abstract	☒
	18	2013/048084	WO	A2	2013-04-04	SAMSUNG ELECTRONICS CO LTD	English Abstract	☐

If you wish to add additional Foreign Patent Document citation information please click the Add button Add

NON-PATENT LITERATURE DOCUMENTS Remove

EFS Web 2.1.18

INFORMATION DISCLOSURE STATEMENT BY APPLICANT

(Not for submission under 37 CFR 1.99)

Application Number	18229907
Filing Date	2023-08-03
First Named Inventor	John A. Nix
Art Unit	
Examiner Name	
Attorney Docket Number	63121/0224

Examiner Initials*	Cite No	Include name of the author (in CAPITAL LETTERS), title of the article (when appropriate), title of the item (book, magazine, journal, serial, symposium, catalog, etc), date, pages(s), volume-issue number(s), publisher, city and/or country where published.	T[5]
	1	Search Report issued in UK Application No. GB2108534.5 dated July 7, 2021.	☐
	2	European Patent Office Communication with European Search Report and European Search Opinion issued in EP 21182424.8 dated October 12, 2021.	☐
	3	European Patent Office Communication with European Search Report and European Search Opinion issued in EP 21182451.1 dated October 12, 2021.	☐
	4	European Patent Office Communication with European Search Report and European Search Opinion issued in EP 21182432.1 dated October 12, 2021.	☐
	5	TLS 1.3 Wish List Presentation, IETF 87 (Eric Rescorla), dated August 1, 2013.	☐

If you wish to add additional non-patent literature document citation information please click the Add button Add

EXAMINER SIGNATURE

Examiner Signature		Date Considered	

*EXAMINER: Initial if reference considered, whether or not citation is in conformance with MPEP 609. Draw line through a citation if not in conformance and not considered. Include copy of this form with next communication to applicant.

[1] See Kind Codes of USPTO Patent Documents at www.USPTO.GOV or MPEP 901.04. [2] Enter office that issued the document, by the two-letter code (WIPO Standard ST.3). [3] For Japanese patent documents, the indication of the year of the reign of the Emperor must precede the serial number of the patent document. [4] Kind of document by the appropriate symbols as indicated on the document under WIPO Standard ST.16 if possible. [5] Applicant is to place a check mark here if English language translation is attached.

INFORMATION DISCLOSURE STATEMENT BY APPLICANT

(Not for submission under 37 CFR 1.99)

Application Number	18229907
Filing Date	2023-08-03
First Named Inventor	John A. Nix
Art Unit	
Examiner Name	
Attorney Docket Number	63121/0224

CERTIFICATION STATEMENT

Please see 37 CFR 1.97 and 1.98 to make the appropriate selection(s):

☐ That each item of information contained in the information disclosure statement was first cited in any communication from a foreign patent office in a counterpart foreign application not more than three months prior to the filing of the information disclosure statement. See 37 CFR 1.97(e)(1).

OR

☐ That no item of information contained in the information disclosure statement was cited in a communication from a foreign patent office in a counterpart foreign application, and, to the knowledge of the person signing the certification after making reasonable inquiry, no item of information contained in the information disclosure statement was known to any individual designated in 37 CFR 1.56(c) more than three months prior to the filing of the information disclosure statement. See 37 CFR 1.97(e)(2).

☐ See attached certification statement.

☐ The fee set forth in 37 CFR 1.17 (p) has been submitted herewith.

☒ A certification statement is not submitted herewith.

SIGNATURE

A signature of the applicant or representative is required in accordance with CFR 1.33, 10.18. Please see CFR 1.4(d) for the form of the signature.

Signature	/Keith J. Barkaus/	Date (YYYY-MM-DD)	2023-12-05
Name/Print	Keith J. Barkaus	Registration Number	51,431

This collection of information is required by 37 CFR 1.97 and 1.98. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 1 hour to complete, including gathering, preparing and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.**

Privacy Act Statement

The Privacy Act of 1974 (P.L. 93-579) requires that you be given certain information in connection with your submission of the attached form related to a patent application or patent. Accordingly, pursuant to the requirements of the Act, please be advised that: (1) the general authority for the collection of this information is 35 U.S.C. 2(b)(2); (2) furnishing of the information solicited is voluntary; and (3) the principal purpose for which the information is used by the U.S. Patent and Trademark Office is to process and/or examine your submission related to a patent application or patent. If you do not furnish the requested information, the U.S. Patent and Trademark Office may not be able to process and/or examine your submission, which may result in termination of proceedings or abandonment of the application or expiration of the patent.

The information provided by you in this form will be subject to the following routine uses:

1. The information on this form will be treated confidentially to the extent allowed under the Freedom of Information Act (5 U.S.C. 552) and the Privacy Act (5 U.S.C. 552a). Records from this system of records may be disclosed to the Department of Justice to determine whether the Freedom of Information Act requires disclosure of these record s.

2. A record from this system of records may be disclosed, as a routine use, in the course of presenting evidence to a court, magistrate, or administrative tribunal, including disclosures to opposing counsel in the course of settlement negotiations.

3. A record in this system of records may be disclosed, as a routine use, to a Member of Congress submitting a request involving an individual, to whom the record pertains, when the individual has requested assistance from the Member with respect to the subject matter of the record.

4. A record in this system of records may be disclosed, as a routine use, to a contractor of the Agency having need for the information in order to perform a contract. Recipients of information shall be required to comply with the requirements of the Privacy Act of 1974, as amended, pursuant to 5 U.S.C. 552a(m).

5. A record related to an International Application filed under the Patent Cooperation Treaty in this system of records may be disclosed, as a routine use, to the International Bureau of the World Intellectual Property Organization, pursuant to the Patent Cooperation Treaty.

6. A record in this system of records may be disclosed, as a routine use, to another federal agency for purposes of National Security review (35 U.S.C. 181) and for review pursuant to the Atomic Energy Act (42 U.S.C. 218(c)).

7. A record from this system of records may be disclosed, as a routine use, to the Administrator, General Services, or his/her designee, during an inspection of records conducted by GSA as part of that agency's responsibility to recommend improvements in records management practices and programs, under authority of 44 U.S.C. 2904 and 2906. Such disclosure shall be made in accordance with the GSA regulations governing inspection of records for this purpose, and any other relevant (i.e., GSA or Commerce) directive. Such disclosure shall not be used to make determinations about individuals.

8. A record from this system of records may be disclosed, as a routine use, to the public after either publication of the application pursuant to 35 U.S.C. 122(b) or issuance of a patent pursuant to 35 U.S.C. 151. Further, a record may be disclosed, subject to the limitations of 37 CFR 1.14, as a routine use, to the public if the record was filed in an application which became abandoned or in which the proceedings were terminated and which application is referenced by either a published application, an application open to public inspections or an issued patent.

9. A record from this system of records may be disclosed, as a routine use, to a Federal, State, or local law enforcement agency, if the USPTO becomes aware of a violation or potential violation of law or regulation.

UNITED STATES
PATENT AND TRADEMARK OFFICE

P.O. Box 1450
Alexandria, VA 22313 - 1450
www.uspto.gov

ELECTRONIC ACKNOWLEDGEMENT RECEIPT

APPLICATION #	RECEIPT DATE / TIME	ATTORNEY DOCKET #
18/229,907	**12/05/2023 05:26:28 PM Z ET**	**63121/0224**

Title of Invention

Key Derivation for a Module Using an Embedded Universal Integrated Circuit Card

Application Information

APPLICATION TYPE	Utility - Nonprovisional Application under 35 USC 111(a)	PATENT #	-
CONFIRMATION #	7483	FILED BY	Victoria Gilmore
PATENT CENTER #	63499166	FILING DATE	08/03/2023
CUSTOMER #	1912	FIRST NAMED INVENTOR	John A. Nix
CORRESPONDENCE ADDRESS	-	AUTHORIZED BY	Keith Barkaus

Documents

TOTAL DOCUMENTS: 2

DOCUMENT	PAGES	DESCRIPTION	SIZE (KB)
1-Transmittal Letter.pdf	4	Transmittal Letter	131 KB
2-IDS1.pdf	7	Information Disclosure Statement (IDS) Form (SB08)	1011 KB

Digest

DOCUMENT	MESSAGE DIGEST(SHA-512)
1-Transmittal Letter.pdf	F9A6D9F4E2015714D6594D3C1FAA863B3404CE8234A2ECBF1 B3933BD4FB2771E125A044EA5EAA046B2EE068FAACFA000B3 F2DD22B975F07E26D6FABE608BB87C

2-IDS1.pdf 9F6F64E33E1F6B458AD2E7165C017E2BE3B9FEA4470B004B7291F8B98031689F108BC6A7C3EDD8C843CA4357CC108212A554EAEABA8F412BEA5641DB8957D9B6

This Acknowledgement Receipt evidences receipt on the noted date by the USPTO of the indicated documents, characterized by the applicant, and including page counts, where applicable. It serves as evidence of receipt similar to a Post Card, as described in MPEP 503.

New Applications Under 35 U.S.C. 111

If a new application is being filed and the application includes the necessary components for filing date (see 37 CFR 1.53(b)-(d) and MPEP 506), a Filing Receipt (37 CFR 1.54) will be issued in due course and the date shown on this Acknowledgement Receipt will establish the filing date of the application.

National Stage of an International Application under 35 U.S.C. 371

If a timely submission to enter the national stage of an international application is compliant with the conditions of 35 U.S.C. 371 and other applicable requirements a Form PCT/DO/EO/903 indicating acceptance of the application as a national stage submission under 35 U.S.C. 371 will be issued in addition to the Filing Receipt, in due course.

New International Application Filed with the USPTO as a Receiving Office

If a new international application is being filed and the international application includes the necessary components for an international filing date (see PCT Article 11 and MPEP 1810), a Notification of the International Application Number and of the International Filing Date (Form PCT/RO/105) will be issued in due course, subject to prescriptions concerning national security, and the date shown on this Acknowledgement Receipt will establish the international filing date of the application.

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant:	Network-1 Technologies, Inc.	Confirmation No.: 7483
Title:	Key Derivation for a Module Using an Embedded Universal Integrated Circuit Card	
Appl. No.:	18/229,907	
Filing Date:	August 3, 2023	
Examiner:	TBD	
Art Unit:	TBD	
Docket No.:	63121/0224	
Customer No.:	01912	

INFORMATION DISCLOSURE STATEMENT LETTER UNDER 37 CFR § 1.56

Patent Center
Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

Sir:

In accordance with the duty of disclosure under 37 C.F.R. §1.56, Applicant would like to direct the Examiner's attention to the references that are listed on the attached forms PTO/SB/08A. In addition to any copies of Foreign Patent Documents and Non-Patent Literature Documents submitted herewith, Applicant refers the Examiner to the references previously submitted to or cited by the Patent Office during prosecution of U.S. Patent Application No. 17/304,922 filed June 29, 2021, now U.S. Patent No. 11,736,283, U.S. Patent Application No. 16/879,325, filed May 20, 2020, now U.S. Patent No. 11,082,218, U.S. Patent Application No. 16/201,401 filed November 27, 2018, now U.S. Patent No. 10,700,856, U.S. Patent Application No. 15/680,758 filed August 18, 2017, now U.S. Patent No. 10,187,206. U.S. Patent Application No. 15/130,146 filed April 15, 2016, now U.S. Patent No. 9,742,562 and U.S. Patent Application No. 14/084,141 filed November 19, 2013, now U.S. Patent No. 9,319,223, from which the subject application claims priority under 35 U.S.C. §120. Accordingly, pursuant to 37 C.F.R. §

Petitioner Samsung Ex-1004, 0228

1.98(d), copies of previously cited or submitted references and Non-Patent Literature Documents are not included with this Information Disclosure Statement.

Reference to Related Patents and Co-Pending Applications

The below chart provides information regarding related issued patents and co-pending applications filed by the present Applicant:

Serial No.	Attorney Docket No.	Filing Date	Status
18/229,907	**63121/0224**	**2023-08-03**	**(Present Application) Pending - Case Docketed to Examiner**
18/111,669	63121/0222	2023-02-20	Non-Final OA mailed 2023-10-02
17/647,812	63121/0213	2022-01-13	USP 11,606,204
17/547,990	63121/0212	2021-12-10	USP 11,736,283
17/304,922	63121/0209	2021-06-28	USP 11,736,283
17/249,242	63121/0202	2021-02-24	Response to Non-Final OA filed 2023-11-13
16/879,325	63121/0198	2020-05-20	USP 11,082,218
16/843,107	63121/0197	2020-04-08	USP 11,283,603
16/721,153	63121/0195	2019-12-19	USP 11,539,681
16/593,561	63121/0190	2019-10-04	USP 11,258,595
16/453,682	63121/0184	2019-06-26	USP 11,233,780
16/271,455	63121/0181	2019-02-08	USP 10,594,679
16/271,428	63121/0180	2019-02-08	USP 10,523,432
16/201,401	63121/0179	2018-11-27	USP 10,700,856
16/200,118	63121/0178	2018-11-26	USP 10,498,530
16/110,804	63121/0168	2018-08-23	USP 10,382,422
16/036,506	63121/0167	2018-07-16	USP 10,530,575
15/983,957	63121/0163	2018-05-18	USP 10,177,911
15/973,012	63121/0162	2018-05-07	USP 10,250,386
15/972,914	63121/0161	2018-05-07	USP 10,652,017
15/928,848	63121/0160	2018-03-22	USP 10,084,768
15/010,905	63121/0157	2016-01-29	USP 9,641,327
15/680,758	63121/0147	2017-08-18	USP 10,187,206
15/162,292	63121/0146	2016-05-23	USP 10,362,012
14/751,119	63121/0145	2015-06-25	USP 9,961,060
15/457,700	63121/0144	2017-03-13	USP 9,998,281

Petitioner Samsung Ex-1004, 0229

15/583,968	63121/0143	2017-05-01	USP 10,057,059
15/043,293	63121/0142	2016-02-12	USP 9,998,280
15/642,088	63121/0141	2017-07-05	USP 10,003,461
15/130,146	63121/0140	2016-04-15	USP 9,742,562
15/162,302	63121/0139	2016-05-23	USP 9,698,981
14/789,255	63121/0138	2015-07-01	USP 9,596,078
14/139,419	63121/0137	2013-12-23	USP 9,351,162
14/136,711	63121/0136	2013-12-20	USP 9,300,473
14/099,329	63121/0135	2013-12-06	USP 9,100,175
14/084,141	63121/0134	2013-11-19	USP 9,319,223
14/064,618	63121/0133	2013-10-28	USP 9,118,464
14/055,606	63121/0132	2013-10-16	USP 9,276,740
14/039,401	63121/0131	2013-09-27	USP 9,288,059
14/023,181	63121/0130	2013-09-10	USP 9,350,550
AU 2019246774	63121-0199	2019-10-08	AU2019246774A1 Issued 2021-09-23
GB 1608573	63121-0151	2014-10-27	Published on 2016-08-03
GB 2100530	63121-0201	2014-10-27	Published on 2021-05-12
CA 2,965,119	63121-0152	2014-10-27	Published on 2015-05-07
HK 17101082.8	63121-0153	2014-10-27	Published on 2017-10-20
EU 14868381.6	63121-0154	2014-12-04	Published on 2017-01-04
CA 2,969,829	63121-0155	2014-12-04	Published on 2015-06-11
HK 17106540.3	63121-0156	2014-12-04	Published on 2018-01-19

The Examiner is invited to review the prosecution history of each of these applications, including the cited references of record and related office actions, as the Examiner deems appropriate.

* * * * *

Petitioner Samsung Ex-1004, 0230

This Information Disclosure Statement is being filed before the mailing date of a first Office Action on the merits in the present application. No certification or fee is required. Applicant(s) hereby petition(s) that the Information Disclosure Statement be considered. Please charge any fee deficiency or credit any overpayment to Deposit Account No. 01-1785, under Docket No. 63121/0224.

Respectfully submitted,

AMSTER, ROTHSTEIN & EBENSTEIN LLP
Attorneys for Applicant
405 Lexington Avenue
New York, NY 10174
(212) 336-8000

Dated: December 5, 2023

By: /Keith J. Barkaus/
Keith J. Barkaus
Reg. No. 51,431

Petitioner Samsung Ex-1004, 0231

Notice of References Cited	Application/Control No. 18/229,907	Applicant(s)/Patent Under Reexamination Nix, John A.	
	Examiner David García Cervetti	Art Unit 2419	Page 1 of 10

U.S. PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Name	CPC Classification	US Classification
*	A	US-20130122864-A1	2013-05-16	HAGGERTY; DAVID T.	G06F21/34	455/411
*	B	US-20160088096-A1	2016-03-24	QUIRICONI; Jean-Rémi	H04W4/50	709/219
*	C	US-20120190354-A1	2012-07-26	MERRIEN; Lionel	H04L67/34	455/422.1
*	D	US-20140287725-A1	2014-09-25	Lee; Jin Hyoung	H04W12/35	455/411
*	E	US-20140237101-A1	2014-08-21	Park; Jaemin	H04W8/205	709/223
*	F	US-20140235210-A1	2014-08-21	Park; Jaemin	H04W12/35	455/411
*	G	US-20140219447-A1	2014-08-07	Park; Jaemin	H04W12/35	380/247
*	H	US-20140140507-A1	2014-05-22	Park; Jaemin	H04W8/183	380/247
*	I	US-9020479-B1	2015-04-28	Somayajula; Siva Rama Kumar	H04W48/18	455/418
*	J	US-8965366-B1	2015-02-24	Somayajula; Siva Rama Kumar	H04W60/00	455/418
*	K	US-20140082358-A1	2014-03-20	Nakhjiri; Madjid	H04L9/0822	713/168
*	L	US-20150281964-A1	2015-10-01	Seo; Myoung Hee	H04W8/183	726/9
*	M	US-20150121495-A1	2015-04-30	Gao; Linyi	H04W12/04	726/6

FOREIGN PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Country	Name	CPC Classification
	N					
	O					
	P					
	Q					
	R					
	S					
	T					

NON-PATENT DOCUMENTS

*		Include as applicable: Author, Title Date, Publisher, Edition or Volume, Pertinent Pages)
	U	
	V	
	W	
	X	

*A copy of this reference is not being furnished with this Office action. (See MPEP § 707.05(a).)
Dates in YYYY-MM-DD format are publication dates. Classifications may be US or foreign.

Petitioner Samsung Ex-1004, 0232

U.S. PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Name	CPC Classification	US Classification
*	A	US-20140308991-A1	2014-10-16	Lee; Jin Hyoung	H04W12/35	455/558
*	B	US-20130340040-A1	2013-12-19	PARK; Chul Hyun	H04L63/08	726/3
*	C	US-20110213959-A1	2011-09-01	Bodi; MiklosTamas	H04W12/06	713/155
*	D	US-20110270747-A1	2011-11-03	Xu; Richard H.	H04M15/67	705/40
*	E	US-20160057725-A1	2016-02-25	Suh; Kyungjoo	G06K17/00	455/435.1
*	F	US-20160149903-A1	2016-05-26	Suh; Kyungjoo	H04L63/0428	713/156
*	G	US-20130157673-A1	2013-06-20	Brusilovsky; Alec	H04W12/02	455/450
*	H	US-20110268022-A1	2011-11-03	Xu; Richard H.	H04Q3/0025	370/328
*	I	US-20160127132-A1	2016-05-05	Lee; Duckey	H04L9/0819	713/156
*	J	US-20140357229-A1	2014-12-04	LEE; Duckey	H04W8/245	455/411
*	K	US-20130227646-A1	2013-08-29	Haggerty; David	H04L63/10	726/3
*	L	US-20130012168-A1	2013-01-10	Rajadurai; Rajavelsamy	H04W12/04	455/411
*	M	US-20130294602-A1	2013-11-07	Huxham; Horatio Nelson	H04L63/0853	380/255

FOREIGN PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Country	Name	CPC Classification
	N					
	O					
	P					
	Q					
	R					
	S					
	T					

NON-PATENT DOCUMENTS

*		Include as applicable: Author, Title Date, Publisher, Edition or Volume, Pertinent Pages)
	U	
	V	
	W	
	X	

*A copy of this reference is not being furnished with this Office action. (See MPEP § 707.05(a).)
Dates in YYYY-MM-DD format are publication dates. Classifications may be US or foreign.

Petitioner Samsung Ex-1004, 0233

U.S. PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Name	CPC Classification	US Classification
*	A	US-20140003604-A1	2014-01-02	CAMPAGNA; Matthew John	H04W12/069	380/247
*	B	US-20110269461-A1	2011-11-03	Xu; Richard H.	H04W8/183	455/435.2
*	C	US-20110269472-A1	2011-11-03	Xu; Richard H.	H04W40/02	455/445
*	D	US-20110269422-A1	2011-11-03	Xu; Richard H.	H04M17/20	455/411
*	E	US-20050058294-A1	2005-03-17	Chen, Liqun	H04L9/0847	380/277
*	F	US-9807605-B2	2017-10-31	Gao; Linyi	H04L63/0428	1/1
*	G	US-8577337-B2	2013-11-05	O'Leary; Edward A.	H04W12/068	455/410
*	H	US-20130344864-A1	2013-12-26	PARK; Chul Hyun	H04W8/18	455/432.3
*	I	US-9800993-B2	2017-10-24	Lee; Duckey	H04W12/126	1/1
*	J	US-9794775-B2	2017-10-17	Huber; Ulrich	H04W8/265	1/1
*	K	US-9674690-B2	2017-06-06	Lee; Hyung Jin	H04L63/205	1/1
*	L	US-9628981-B2	2017-04-18	Park; Jaemin	H04W8/205	1/1
*	M	US-9572016-B2	2017-02-14	Cormier; Jean-Philippe Paul	H04W8/183	1/1

FOREIGN PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Country	Name	CPC Classification
	N					
	O					
	P					
	Q					
	R					
	S					
	T					

NON-PATENT DOCUMENTS

*		Include as applicable: Author, Title Date, Publisher, Edition or Volume, Pertinent Pages)
	U	
	V	
	W	
	X	

*A copy of this reference is not being furnished with this Office action. (See MPEP § 707.05(a).)
Dates in YYYY-MM-DD format are publication dates. Classifications may be US or foreign.

Petitioner Samsung Ex-1004, 0234

U.S. PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Name	CPC Classification	US Classification
*	A	US-9332129-B2	2016-05-03	Li; Li	H04W4/50	1/1
*	B	US-9270653-B2	2016-02-23	Maria; Arturo	H04L63/062	1/1
*	C	US-20140082359-A1	2014-03-20	Nakhjiri; Madjid	H04L9/3066	713/168
*	D	US-20140120874-A1	2014-05-01	Kang; Hyun-Jeong	H04W12/041	455/411
*	E	US-6804357-B1	2004-10-12	Ikonen; Ari M.	H04N21/42204	348/14.05
*	F	US-9923724-B2	2018-03-20	Lee; Duckey	H04L9/0825	1/1
*	G	US-6842628-B1	2005-01-11	Arnold; Greg	H04L51/224	713/181
*	H	US-6256733-B1	2001-07-03	Thakkar; Dhanya	H04L63/065	380/279
*	I	US-20080044032-A1	2008-02-21	Lou; Dafu	H04L65/40	380/284
*	J	US-20120263298-A1	2012-10-18	Suh; Kyung-Joo	H04W4/50	380/255
*	K	US-20130283047-A1	2013-10-24	Merrien; Lionel	H04L67/306	713/164
*	L	US-20150350881-A1	2015-12-03	WEISS; Dieter	H04W12/04	455/558
*	M	US-5216715-A	1993-06-01	Markwitz; Wernhard	H04L9/321	713/181

FOREIGN PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Country	Name	CPC Classification
	N					
	O					
	P					
	Q					
	R					
	S					
	T					

NON-PATENT DOCUMENTS

*		Include as applicable: Author, Title Date, Publisher, Edition or Volume, Pertinent Pages)
	U	
	V	
	W	
	X	

*A copy of this reference is not being furnished with this Office action. (See MPEP § 707.05(a).)
Dates in YYYY-MM-DD format are publication dates. Classifications may be US or foreign.

Petitioner Samsung Ex-1004, 0235

U.S. PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Name	CPC Classification	US Classification
*	A	US-5642420-A	1997-06-24	Kuroda; Yasutsugu	H04L9/40	380/30
*	B	US-5664017-A	1997-09-02	Gressel; Carmi David	H04L9/0833	380/30
*	C	US-5852665-A	1998-12-22	Gressel; Carmi David	H04L9/0894	380/45
*	D	US-5995625-A	1999-11-30	Sudia; Frank W.	G06F21/6209	713/181
*	E	US-6721886-B1	2004-04-13	Uskela; Sami	H04L9/3271	713/168
*	F	US-8352739-B2	2013-01-08	Park; Young-Man	H04L63/06	713/169
*	G	US-20140329502-A1	2014-11-06	Lee; Jinhyoung	H04W12/04	455/411
*	H	US-20120011362-A1	2012-01-12	Lambert; Robert John	H04L9/0844	713/168
*	I	US-20060129848-A1	2006-06-15	Paksoy; Erdal	G06F21/35	713/193
*	J	US-8452017-B2	2013-05-28	Sherkin; Alexander	H04L9/0844	713/168
*	K	US-20120087493-A1	2012-04-12	CHIDAMBARAM; Avinash	H04L9/0841	713/182
*	L	US-20110035604-A1	2011-02-10	Habraken; G. Wouter	G07F7/1016	235/382
*	M	US-20060235796-A1	2006-10-19	Johnson; Bruce E.	G06Q20/12	705/26.1

FOREIGN PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Country	Name	CPC Classification
	N					
	O					
	P					
	Q					
	R					
	S					
	T					

NON-PATENT DOCUMENTS

*		Include as applicable: Author, Title Date, Publisher, Edition or Volume, Pertinent Pages)
	U	
	V	
	W	
	X	

*A copy of this reference is not being furnished with this Office action. (See MPEP § 707.05(a).)
Dates in YYYY-MM-DD format are publication dates. Classifications may be US or foreign.

Petitioner Samsung Ex-1004, 0236

U.S. PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Name	CPC Classification	US Classification
*	A	US-20060235795-A1	2006-10-19	Johnson; Bruce E.	G06Q20/02	705/26.1
*	B	US-20150058632-A1	2015-02-26	Beyer; Loraine	H04L65/1073	713/171
*	C	US-8874915-B1	2014-10-28	Rodoper; Mete	H04L9/0838	380/278
*	D	US-20140219448-A1	2014-08-07	Froels; Martin	H04L9/14	380/255
*	E	US-20140032898-A1	2014-01-30	YU; Zhao-Fu	H04N21/4181	713/159
*	F	US-20130301828-A1	2013-11-14	Gouget; Aline	H04L9/0844	380/44
*	G	US-20130290714-A1	2013-10-31	Hans; Sebastian	H04L9/3273	713/168
*	H	US-20130067552-A1	2013-03-14	Hawkes; Philip Michael	H04W12/08	726/7
*	I	US-20120284194-A1	2012-11-08	Liu; Jie	G07F7/08	705/66
*	J	US-20120084565-A1	2012-04-05	Wittenberg; Craig Henry	H04L9/3226	713/172
*	K	US-20120028608-A1	2012-02-02	SU; JEN-CHEN	H04W12/08	455/411
*	L	US-20080288773-A1	2008-11-20	Nguyen; Nam	H04L9/321	713/155
*	M	US-20080260149-A1	2008-10-23	Gehrmann; Christian M.	G06Q20/3821	380/247

FOREIGN PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Country	Name	CPC Classification
	N					
	O					
	P					
	Q					
	R					
	S					
	T					

NON-PATENT DOCUMENTS

*		Include as applicable: Author, Title Date, Publisher, Edition or Volume, Pertinent Pages)
	U	
	V	
	W	
	X	

*A copy of this reference is not being furnished with this Office action. (See MPEP § 707.05(a).)
Dates in YYYY-MM-DD format are publication dates. Classifications may be US or foreign.

Petitioner Samsung Ex-1004, 0237

U.S. PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Name	CPC Classification	US Classification
*	A	US-20080170697-A1	2008-07-17	Heinonen; Petteri	H04L63/0823	380/277
*	B	US-20070241182-A1	2007-10-18	Buer; Mark	H04L63/0853	235/380
*	C	US-20070050622-A1	2007-03-01	Rager; Kent D.	G06F21/445	713/168
*	D	US-20050246529-A1	2005-11-03	Hunt, Galen C.	H04L9/3263	713/168
*	E	US-11258595-B2	2022-02-22	Nix; John A.	H04L63/061	1/1
*	F	US-20210226781-A1	2021-07-22	ARKKO; Jari	H04L9/085	1/1
*	G	US-20210203488-A1	2021-07-01	STÅHL; Per	H04L9/0631	1/1
*	H	US-20210144551-A1	2021-05-13	LEE; Hyewon	H04W12/35	1/1
*	I	US-10743176-B1	2020-08-11	Khan; Taussif	H04W12/48	1/1
*	J	US-20200162269-A1	2020-05-21	Nix; John A.	H04L9/0825	1/1
*	K	US-20200089488-A1	2020-03-19	Yu; Xiaobo	G06F16/148	1/1
*	L	US-20200021993-A1	2020-01-16	YANG; Xiangying	H04L63/123	1/1
*	M	US-20190394053-A1	2019-12-26	Yu; Xiaobo	H04L63/0869	1/1

FOREIGN PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Country	Name	CPC Classification
	N					
	O					
	P					
	Q					
	R					
	S					
	T					

NON-PATENT DOCUMENTS

*		Include as applicable: Author, Title Date, Publisher, Edition or Volume, Pertinent Pages)
	U	
	V	
	W	
	X	

*A copy of this reference is not being furnished with this Office action. (See MPEP § 707.05(a).)
Dates in YYYY-MM-DD format are publication dates. Classifications may be US or foreign.

Petitioner Samsung Ex-1004, 0238

U.S. PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Name	CPC Classification	US Classification
*	A	US-20190373471-A1	2019-12-05	LI; Li	H04L9/3247	1/1
*	B	US-20190230087-A1	2019-07-25	Gharout; Said	H04W12/35	1/1
*	C	US-20190208417-A1	2019-07-04	KANG; Xin	H04W12/35	1/1
*	D	US-20190190723-A1	2019-06-20	LEE; Jung Do	H04L9/3231	1/1
*	E	US-20190140837-A1	2019-05-09	Cheng; Ziyao	H04W8/20	1/1
*	F	US-20130159710-A1	2013-06-20	Khan; Ahmer A.	H04L9/0891	713/168
*	G	US-7715822-B2	2010-05-11	Semple; James	H04L63/0853	455/433
*	H	US-20080130879-A1	2008-06-05	Heinonen; Petteri	H04L9/006	380/44
*	I	US-20060034494-A1	2006-02-16	Holloran; Robert W.	H04L9/3231	382/116
*	J	US-20150143125-A1	2015-05-21	Nix; John A.	H04W76/27	713/171
*	K	US-9247424-B2	2016-01-26	Haggerty; David T.	H04L63/10	1/1
*	L	US-20160226877-A1	2016-08-04	HAGGERTY; David T.	H04W8/183	1/1
*	M	US-9843585-B2	2017-12-12	Haggerty; David T.	H04W12/06	1/1

FOREIGN PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Country	Name	CPC Classification
	N					
	O					
	P					
	Q					
	R					
	S					
	T					

NON-PATENT DOCUMENTS

*		Include as applicable: Author, Title Date, Publisher, Edition or Volume, Pertinent Pages)
	U	
	V	
	W	
	X	

*A copy of this reference is not being furnished with this Office action. (See MPEP § 707.05(a).)
Dates in YYYY-MM-DD format are publication dates. Classifications may be US or foreign.

Petitioner Samsung Ex-1004, 0239

U.S. PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Name	CPC Classification	US Classification
*	A	US-9037112-B2	2015-05-19	Rajadurai; Rajavelsamy	H04W12/35	713/168
*	B	US-9451459-B2	2016-09-20	Lee; Jinhyoung	H04W12/35	1/1
*	C	US-9426654-B2	2016-08-23	Lee; Jin Hyoung	H04L63/0853	1/1
*	D	US-20160330624-A1	2016-11-10	LEE; Jin Hyoung	H04L63/0853	1/1
*	E	US-20180242153-A1	2018-08-23	LEE; Jin Hyoung	H04L63/0853	1/1
*	F	US-10091653-B2	2018-10-02	Lee; Jin Hyoung	H04W12/06	1/1
*	G	US-10462668-B2	2019-10-29	Lee; Jin Hyoung	H04L63/0823	1/1
*	H	US-9712996-B2	2017-07-18	Park; Jaemin	H04W12/04	1/1
*	I	US-20170289792-A1	2017-10-05	PARK; Jaemin	H04L67/306	1/1
*	J	US-20150126153-A1	2015-05-07	Spitz; Stephan	H04W12/06	455/26.1
*	K	US-20060179309-A1	2006-08-10	Cross; David B.	G06F21/6281	713/168
*	L	US-20040146015-A1	2004-07-29	Cross, David B.	H04L9/0894	370/328
*	M	US-8887257-B2	2014-11-11	Haggerty; David T.	H04W12/04	726/9

FOREIGN PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Country	Name	CPC Classification
	N					
	O					
	P					
	Q					
	R					
	S					
	T					

NON-PATENT DOCUMENTS

*		Include as applicable: Author, Title Date, Publisher, Edition or Volume, Pertinent Pages)
	U	
	V	
	W	
	X	

*A copy of this reference is not being furnished with this Office action. (See MPEP § 707.05(a).)
Dates in YYYY-MM-DD format are publication dates. Classifications may be US or foreign.

Petitioner Samsung Ex-1004, 0240

Notice of References Cited	Application/Control No. 18/229,907	Applicant(s)/Patent Under Reexamination Nix, John A.	
	Examiner David García Cervetti	Art Unit 2419	Page 10 of 10

U.S. PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Name	CPC Classification	US Classification
*	A	US-20140006786-A1	2014-01-02	Campagna; Matthew John	H04W12/04	713/171
*	B	US-20140004824-A1	2014-01-02	Campagna; Matthew John	H04L9/0866	455/411
*	C	US-20120072979-A1	2012-03-22	Cha; Inhyok	H04W12/069	726/8
*	D	US-20120023568-A1	2012-01-26	Cha; Inhyok	H04L63/0807	726/10
*	E	US-20100174907-A1	2010-07-08	Semple; James F.	H04W12/0431	713/169
	F					
	G					
	H					
	I					
	J					
	K					
	L					
	M					

FOREIGN PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Country	Name	CPC Classification
	N					
	O					
	P					
	Q					
	R					
	S					
	T					

NON-PATENT DOCUMENTS

*		Include as applicable: Author, Title Date, Publisher, Edition or Volume, Pertinent Pages)
	U	
	V	
	W	
	X	

*A copy of this reference is not being furnished with this Office action. (See MPEP § 707.05(a).)
Dates in YYYY-MM-DD format are publication dates. Classifications may be US or foreign.

Search Notes	Application/Control No.	Applicant(s)/Patent Under Reexamination
	18/229,907	Nix, John A.
	Examiner	**Art Unit**
	David García Cervetti	2419

CPC - Searched*		
Symbol	**Date**	**Examiner**
H04L9/0861 H04L9/006 H04L9/0662 H04L9/0816 H04L9/0841 H04L9/0844 H04L9/085 H04L9/088 H04L9/0891 H04L9/0894 H04L9/14 H04L9/30 H04L9/3239 H04L9/3247 H04L9/3249 H04L9/3263 H04L63/061 H04L63/0442 H04W12/03 H04W12/041 H04W12/06	03/08/2024	DGC

CPC Combination Sets - Searched*		
Symbol	**Date**	**Examiner**

US Classification - Searched*			
Class	**Subclass**	**Date**	**Examiner**

* See search history printout included with this form or the SEARCH NOTES box below to determine the scope of the search.

Search Notes		
Search Notes	**Date**	**Examiner**
inventor name search, acm, ieee, springer, google, scholar, ip.com, search history attached, global dossier	03/08/2024	DGC

Interference Search			
US Class/CPC Symbol	**US Subclass/CPC Group**	**Date**	**Examiner**

/David Garcia Cervetti/ Primary Examiner, Art Unit 2419	

Petitioner Samsung Ex-1004, 0242

Index of Claims	Application/Control No.	Applicant(s)/Patent Under Reexamination
	18/229,907	Nix, John A.
	Examiner	Art Unit
	David García Cervetti	2419

✓	Rejected	-	Cancelled	N	Non-Elected	A	Appeal
=	Allowed	÷	Restricted	I	Interference	O	Objected

CLAIMS										
☐ Claims renumbered in the same order as presented by applicant			☐ CPA		☐ T.D.		☐ R.1.47			
CLAIM		DATE								
Final	Original	03/08/2024								
	1	✓								
	2	✓								
	3	✓								
	4	✓								
	5	✓								
	6	✓								
	7	✓								
	8	✓								
	9	✓								
	10	✓								
	11	✓								
	12	✓								
	13	✓								
	14	✓								
	15	✓								
	16	✓								
	17	✓								
	18	✓								
	19	✓								
	20	✓								
	21	✓								
	22	✓								

Petitioner Samsung Ex-1004, 0243

Bibliographic Data

Application No: 18/229,907

Foreign Priority claimed: ○ Yes ◉ No

35 USC 119 (a-d) conditions met: ☑ Yes ☐ No ☐ Met After Allowance

Verified and Acknowledged: /David Garcia Cervetti/ DGC

Examiner's Signature Initials

Title: Key Derivation for a Module Using an Embedded Universal Integrated Circuit Card

---

FILING or 371(c) DATE	CLASS	GROUP ART UNIT	ATTORNEY DOCKET NO.
08/03/2023	713	2419	63121/0224
RULE			

APPLICANTS

Network-1 Technologies, Inc.,

INVENTORS

John A. Nix, Evanston, IL, UNITED STATES

CONTINUING DATA

This application is a CON of 17304922 06/28/2021 PAT 11736283

17304922 is a CON of 16879325 05/20/2020 PAT 11082218

16879325 is a CON of 16201401 11/27/2018 PAT 10700856

16201401 is a CON of 15680758 08/18/2017 PAT 10187206

15680758 is a CON of 15130146 04/15/2016 PAT 9742562

15130146 is a CON of 14084141 11/19/2013 PAT 9319223

FOREIGN APPLICATIONS

IF REQUIRED, FOREIGN LICENSE GRANTED**

08/15/2023

STATE OR COUNTRY

UNITED STATES

ADDRESS

AMSTER, ROTHSTEIN & EBENSTEIN LLP
405 LEXINGTON AVENUE
FLOOR 48
NEW YORK, NY 10174
UNITED STATES

FILING FEE RECEIVED

$2,440

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant:	Network-1 Technologies, Inc.	Confirmation No.: 7483
Title:	Key Derivation for a Module Using an Embedded Universal Integrated Circuit Card	
Appl. No.:	18/229,907	
Filing Date:	August 3, 2023	
Examiner:	TBD	
Art Unit:	TBD	
Docket No.:	63121/0224	
Customer No.:	01912	

INFORMATION DISCLOSURE STATEMENT LETTER UNDER 37 CFR § 1.56

Patent Center
Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

Sir:

In accordance with the duty of disclosure under 37 C.F.R. §1.56, Applicant would like to direct the Examiner's attention to the references that are listed on the attached forms PTO/SB/08A. In addition to any copies of Foreign Patent Documents and Non-Patent Literature Documents submitted herewith, Applicant refers the Examiner to the references previously submitted to or cited by the Patent Office during prosecution of U.S. Patent Application No. 17/304,922 filed June 29, 2021, now U.S. Patent No. 11,736,283, U.S. Patent Application No. 16/879,325, filed May 20, 2020, now U.S. Patent No. 11,082,218, U.S. Patent Application No. 16/201,401 filed November 27, 2018, now U.S. Patent No. 10,700,856, U.S. Patent Application No. 15/680,758 filed August 18, 2017, now U.S. Patent No. 10,187,206. U.S. Patent Application No. 15/130,146 filed April 15, 2016, now U.S. Patent No. 9,742,562 and U.S. Patent Application No. 14/084,141 filed November 19, 2013, now U.S. Patent No. 9,319,223, from which the subject application claims priority under 35 U.S.C. §120. Accordingly, pursuant to 37 C.F.R. §

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /DGC/

Petitioner Samsung Ex-1004, 0245

1.98(d), copies of previously cited or submitted references and Non-Patent Literature Documents are not included with this Information Disclosure Statement.

Reference to Related Patents and Co-Pending Applications

The below chart provides information regarding related issued patents and co-pending applications filed by the present Applicant:

Serial No.	Attorney Docket No.	Filing Date	Status
18/229,907	**63121/0224**	**2023-08-03**	**(Present Application) Pending - Case Docketed to Examiner**
18/111,669	63121/0222	2023-02-20	Non-Final OA mailed 2023-10-02
17/647,812	63121/0213	2022-01-13	USP 11,606,204
17/547,990	63121/0212	2021-12-10	USP 11,736,283
17/304,922	63121/0209	2021-06-28	USP 11,736,283
17/249,242	63121/0202	2021-02-24	Response to Non-Final OA filed 2023-11-13
16/879,325	63121/0198	2020-05-20	USP 11,082,218
16/843,107	63121/0197	2020-04-08	USP 11,283,603
16/721,153	63121/0195	2019-12-19	USP 11,539,681
16/593,561	63121/0190	2019-10-04	USP 11,258,595
16/453,682	63121/0184	2019-06-26	USP 11,233,780
16/271,455	63121/0181	2019-02-08	USP 10,594,679
16/271,428	63121/0180	2019-02-08	USP 10,523,432
16/201,401	63121/0179	2018-11-27	USP 10,700,856
16/200,118	63121/0178	2018-11-26	USP 10,498,530
16/110,804	63121/0168	2018-08-23	USP 10,382,422
16/036,506	63121/0167	2018-07-16	USP 10,530,575
15/983,957	63121/0163	2018-05-18	USP 10,177,911
15/973,012	63121/0162	2018-05-07	USP 10,250,386
15/972,914	63121/0161	2018-05-07	USP 10,652,017
15/928,848	63121/0160	2018-03-22	USP 10,084,768
15/010,905	63121/0157	2016-01-29	USP 9,641,327
15/680,758	63121/0147	2017-08-18	USP 10,187,206
15/162,292	63121/0146	2016-05-23	USP 10,362,012
14/751,119	63121/0145	2015-06-25	USP 9,961,060
15/457,700	63121/0144	2017-03-13	USP 9,998,281

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /DGC/

Petitioner Samsung Ex-1004, 0246

15/583,968	63121/0143	2017-05-01	USP 10,057,059
15/043,293	63121/0142	2016-02-12	USP 9,998,280
15/642,088	63121/0141	2017-07-05	USP 10,003,461
15/130,146	63121/0140	2016-04-15	USP 9,742,562
15/162,302	63121/0139	2016-05-23	USP 9,698,981
14/789,255	63121/0138	2015-07-01	USP 9,596,078
14/139,419	63121/0137	2013-12-23	USP 9,351,162
14/136,711	63121/0136	2013-12-20	USP 9,300,473
14/099,329	63121/0135	2013-12-06	USP 9,100,175
14/084,141	63121/0134	2013-11-19	USP 9,319,223
14/064,618	63121/0133	2013-10-28	USP 9,118,464
14/055,606	63121/0132	2013-10-16	USP 9,276,740
14/039,401	63121/0131	2013-09-27	USP 9,288,059
14/023,181	63121/0130	2013-09-10	USP 9,350,550
AU 2019246774	63121-0199	2019-10-08	AU2019246774A1 Issued 2021-09-23
GB 1608573	63121-0151	2014-10-27	Published on 2016-08-03
GB 2100530	63121-0201	2014-10-27	Published on 2021-05-12
CA 2,965,119	63121-0152	2014-10-27	Published on 2015-05-07
HK 17101082.8	63121-0153	2014-10-27	Published on 2017-10-20
EU 14868381.6	63121-0154	2014-12-04	Published on 2017-01-04
CA 2,969,829	63121-0155	2014-12-04	Published on 2015-06-11
HK 17106540.3	63121-0156	2014-12-04	Published on 2018-01-19

The Examiner is invited to review the prosecution history of each of these applications, including the cited references of record and related office actions, as the Examiner deems appropriate.

* * * * *

4868-1453-8132v.1

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /DGC/

Petitioner Samsung Ex-1004, 0247

This Information Disclosure Statement is being filed before the mailing date of a first Office Action on the merits in the present application. No certification or fee is required. Applicant(s) hereby petition(s) that the Information Disclosure Statement be considered. Please charge any fee deficiency or credit any overpayment to Deposit Account No. 01-1785, under Docket No. 63121/0224.

Respectfully submitted,

AMSTER, ROTHSTEIN & EBENSTEIN LLP
Attorneys for Applicant
405 Lexington Avenue
New York, NY 10174
(212) 336-8000

Dated: December 5, 2023

By: /Keith J. Barkaus/
Keith J. Barkaus
Reg. No. 51,431

/David Garcia Cervetti/ 03/08/2024

4868-1453-8132v.1

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /DGC/

Petitioner Samsung Ex-1004, 0248

PE2E SEARCH - Search History (Prior Art)

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	British Equivalents	Time Stamp
L229	1040	(fragment segment part portion section) near6 (object file document) AND user near6 (access$8 request$8) near8 (fragment segment part portion section) near6 (object file document) AND associa$8 near6 (uniqu$8 copy version (fragment segment part portion section) near6 (object file document)) near6 user AND (generat$8 split$8 break$8) near8 (fragment segment part portion section) near6 (object file document)	(US-PGPUB; USPAT)	OR	ON	ON	2024/01/08 10:58 AM
L230	808	(fragment segment part portion section) near6 (object file document) AND user near6 (access$8 request$8) near8 (fragment segment part portion section) near6 (object file document) AND associa$8 near6 (uniqu$8 copy version (fragment segment part portion section) near6 (object file document)) near6 user AND (generat$8 split$8 break$8) near8 (fragment segment part portion section) near6 (object file document) AND (@pd @prad @rlad @ptad @ad)<20180308	(US-PGPUB; USPAT)	OR	ON	ON	2024/01/08 10:59 AM
L231	5246	(enclosure housing) near8 (touch display screen).clm. AND temper$8 near6 sensor.clm.	(US-PGPUB; USPAT; USOCR; FIT (AP, AT, AU, BE, BG, BR, BY, CA, CH, CN, CS, CU, CZ, DD, DK, EA, EE, ES, FI, FR, GB, HR, HU, ID, IE, IL, IS, IT, JP, KR, LT, LU, LV, MA, MC, MD, MY, NL,	OR	ON	ON	2024/01/19 08:41 AM

Petitioner Samsung Ex-1004, 0249

			NO, NZ, PH, PL, PT, RO, RS, RU, SE, SG, SI, SK, SU, TH, TN, TR, TW, UA, VN, WO); FPRS; EPO; JPO; DERWENT; IBM_TDB)				
L232	1407	(enclosure housing) near8 (touch display screen).clm. AND temper$8 near6 sensor.clm.	(US-PGPUB; USPAT)	OR	ON	ON	2024/01/19 08:41 AM
L233	192	(enclosure housing) near8 (touch display screen).clm. WITH temper$8 near6 sensor.clm.	(US-PGPUB; USPAT)	OR	ON	ON	2024/01/19 08:41 AM
L234	84	(enclosure housing) near8 (touch display screen).clm. WITH temper$8 near6 sensor.clm. AND (tamper$8 detect$8).clm.	(US-PGPUB; USPAT)	OR	ON	ON	2024/01/19 08:42 AM
L235	645	(enclosure housing) near8 (touch display screen).clm. AND temper$8 near6 sensor.clm. AND (tamper$8 detect$8).clm.	(US-PGPUB; USPAT)	OR	ON	ON	2024/01/19 08:45 AM
L236	1	(enclosure housing) near8 (touch display screen).clm. AND temper$8 near6 sensor.clm. WITH (tamper$8).clm.	(US-PGPUB; USPAT)	OR	ON	ON	2024/01/19 08:45 AM
L237	25	(enclosure housing) near8 (touch display screen).clm. AND temper$8.clm. AND (tamper$8).clm.	(US-PGPUB; USPAT)	OR	ON	ON	2024/01/19 08:46 AM
L238	297	temper$8.clm. near8 (tamper$8).clm.	(US-PGPUB; USPAT)	OR	ON	ON	2024/01/19 08:49 AM
L239	797	(blockchain) same4 (mempool memory near4 pool mem$1pool)	(US-PGPUB; USPAT)	OR	ON	ON	2024/01/19 04:09 PM
L240	605	(blockchain) SAME (mempool memory near4 pool mem$1pool)	(US-PGPUB; USPAT)	OR	ON	ON	2024/01/19 04:09 PM
L241	188	(blockchain) SAME (mempool memory near4 pool mem$1pool)	(USPAT)	OR	ON	ON	2024/01/19 04:09 PM
L242	51	(blockchain) SAME (transaction near4	(USPAT)	OR	ON	ON	2024/01/19 04:10 PM

Petitioner Samsung Ex-1004, 0250

		(lifecycle life$1cycle))					
L243	513	(preimage pre$1image) near6 attack	(US-PGPUB; USPAT; USOCR; FIT (AP, AT, AU, BE, BG, BR, BY, CA, CH, CN, CS, CU, CZ, DD, DK, EA, EE, ES, FI, FR, GB, HR, HU, ID, IE, IL, IS, IT, JP, KR, LT, LU, LV, MA, MC, MD, MY, NL, NO, NZ, PH, PL, PT, RO, RS, RU, SE, SG, SI, SK, SU, TH, TN, TR, TW, UA, VN, WO); FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2024/02/05 01:49 PM
L244	314	(preimage pre$1image) near6 attack	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/05 01:49 PM
L245	352	(preimage pre$1image) near6 (attac$8 vulnera$8 weak$8) AND (hash$8 oneway one$1way)	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/05 01:50 PM
L246	320	(preimage pre$1image) near6 (attac$8 vulnera$8 weak$8) same4 (hash$8 oneway one$1way)	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/05 01:50 PM
L247	287	(preimage pre$1image) near6 (attac$8 vulnera$8 weak$8) same4 (hash$8 oneway one$1way) WITH (preimage pre$1image input$8 map$8)	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/05 01:52 PM
L248	216	(preimage pre$1image) near6 (attac$8 vulnera$8 weak$8) same4 (hash$8 oneway one$1way) WITH (preimage pre$1image input$8 map$8) WITH (output$8 result$8 value optimiz$8)	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/05 01:52 PM
L249	65	redact$8 near8 transcr$8.clm.	(US-PGPUB; USPAT; USOCR; FIT (AP, AT, AU, BE, BG, BR, BY, CA, CH, CN, CS, CU, CZ, DD, DK, EA, EE, ES, FI, FR, GB, HR, HU, ID, IE, IL, IS, IT, JP, KR, LT, LU, LV, MA, MC, MD, MY, NL, NO, NZ, PH, PL, PT, RO, RS, RU, SE, SG,	OR	ON	ON	2024/02/06 07:36 AM

Petitioner Samsung Ex-1004, 0251

			SI, SK, SU, TH, TN, TR, TW, UA, VN, WO); FPRS; EPO; JPO; DERWENT; IBM_TDB)				
L250	44	redact$8 near8 transcr$8.clm.	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/06 07:36 AM
L251	44734	first near4 (app application) near8 (link$8 associa$8) WITH second near4 (app application)	(US-PGPUB; USPAT; USOCR; FIT (AP, AT, AU, BE, BG, BR, BY, CA, CH, CN, CS, CU, CZ, DD, DK, EA, EE, ES, FI, FR, GB, HR, HU, ID, IE, IL, IS, IT, JP, KR, LT, LU, LV, MA, MC, MD, MY, NL, NO, NZ, PH, PL, PT, RO, RS, RU, SE, SG, SI, SK, SU, TH, TN, TR, TW, UA, VN, WO); FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2024/02/12 05:08 PM
L252	764	first near4 (app application) near8 (link$8 associa$8) WITH second near4 (app application) WITH user near4 (authentica$8 authori$8)	(US-PGPUB; USPAT; USOCR; FIT (AP, AT, AU, BE, BG, BR, BY, CA, CH, CN, CS, CU, CZ, DD, DK, EA, EE, ES, FI, FR, GB, HR, HU, ID, IE, IL, IS, IT, JP, KR, LT, LU, LV, MA, MC, MD, MY, NL, NO, NZ, PH, PL, PT, RO, RS, RU, SE, SG, SI, SK, SU, TH, TN, TR, TW, UA, VN, WO); FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2024/02/12 05:08 PM
L253	320	first near4 (app application) near8 (link$8 associa$8) WITH second near4 (app application) WITH user near4 (authentica$8 authori$8)	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/12 05:09 PM
L254	1	"20210012282".pn. AND (object near6 (hash$8 encryp$8))	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/13 08:56 AM
L255	1	"20210012282".pn. AND (provenance)	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/13 08:57 AM
L256	1	"20210012282".pn. AND (tag)	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/13 08:59 AM
L257	1	"20210012282".pn. AND (verif$8 valid$8 authenti$8 authoriz$8)	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/13 09:01 AM
L258	1	"20210012282".pn.	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/13

		AND (verif$8 near6 priori$8)					09:05 AM
L259	1	"20210012282".pn. AND (verif$8 near6 priori$8 AND hash$8)	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/13 09:06 AM
L260	1	"20210012282".pn. AND (verif$8 near6 priori$8 AND (verif$8 prior$8) near6 hash$8)	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/13 09:06 AM
L261	1	"20210012282".pn. AND (root trust genreat$8)	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/13 09:11 AM
L262	1053	(split$8 shar$8 divid$8 subdivi$8) near4 private near4 key same4 (mpc multiparty multi$1party)	(US-PGPUB; USPAT; USOCR; FIT (AP, AT, AU, BE, BG, BR, BY, CA, CH, CN, CS, CU, CZ, DD, DK, EA, EE, ES, FI, FR, GB, HR, HU, ID, IE, IL, IS, IT, JP, KR, LT, LU, LV, MA, MC, MD, MY, NL, NO, NZ, PH, PL, PT, RO, RS, RU, SE, SG, SI, SK, SU, TH, TN, TR, TW, UA, VN, WO); FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2024/02/23 03:48 PM
L263	304	(split$8 shar$8 divid$8 subdivi$8) near4 private near4 key same4 (mpc multiparty multi$1party)	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/23 03:49 PM
L264	583	(sign signing signed signature) WITH (split$8 shar$8 divid$8 subdivi$8) near6 key AND (mpc multiparty multi$1party)	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/23 03:53 PM
L265	312	(sign signing signed signature) WITH (split$8 shar$8 divid$8 subdivi$8) near6 key AND (mpc multiparty multi$1party) AND (certificate)	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/23 03:57 PM
L266	137	(sign signing signed signature) WITH (split$8 shar$8 divid$8 subdivi$8) near6 key same4 certif$8 AND (mpc multiparty multi$1party) AND (certificate)	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/23 03:57 PM
L267	287	("20230126356" "20230128131" "20100161956"	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/23 04:02 PM

Petitioner Samsung Ex-1004, 0253

		"8612753" "20230245111" "10958424" "11804957" "20020062451" "20230069934" "10389696" "10447674" "20170310652" "20210326442" "20170171174" "20060248333" "20220318907" "7447903" "11502827" "20230246817" "20230299942" "20190097982" "11089032" "20120185680" "11620387" "20190222583" "20060117177" "10129223" "11418329" "8683215" "10554636" "7987356" "20060013402" "20170171219" "20200021567" "11777721" "11811950" "11115394" "20070055878" "20170149740" "9705859" "10382409" "10412098" "20060050870" "10243968" "20220109660" "7697691" "20210258288" "20190296917" "11687667" "11811740" "20230104126" "7149310" "10637836" "11546169" "11677729" "20100150351" "20230269241" "7715565" "20190327210" "11038853" "10375067" "20230246850" "20230246822" "11240212" "9705674" "9667421" "20050027989" "20230053566" "20220385470" "20170005999" "9832171" "20200287876" "11722303" "10326597"					

Petitioner Samsung Ex-1004, 0254

		"7596697" "10601789" "20180324176" "10666436" "7055032" "20100202609" "11470054" "20080172559" "20090222658" "20140229737" "20140244998" "20180083929" "20170093581" "20210266161" "20040111607" "20200213283" "9544297" "20040068650" "10511591" "9608813" "20060182283" "11502834" "8660266" "20200266976" "20230308424" "20220021525" "10313312" "20170346819" "7865721" "20230291556" "20140310516" "20060182277" "20230163946" "9516002" "10754693" "11218317" "11695555" "20130042105" "20170195119" "20220038278" "20140229739" "20180198606" "20200012527" "20220173886" "11652616" "11522686" "20190173672" "7318155" "10652015" "8745379" "9762577" "9882900" "20230142978" "20180343127" "10218502" "8745372" "20140304503" "20210266147" "20210144004" "20130227286" "10121017" "8340287" "20190356650" "11582020" "20200252396" "9258117" "9208335" "11310036" "20230216662" "20210266154"				

Petitioner Samsung Ex-1004, 0255

		"20160182486" "10484365" "11546137" "10516543" "20110202755" "10210341" "20210266152" "20160156626" "10630682" "20220337432" "20020078354" "20190104118" "8312518" "20060184786" "8213608" "20220006626" "11552946" "11757658" "20150082399" "11206135" "10911431" "11489821" "20200036707" "10521595" "20060133615" "11824974" "11582045" "20020073309" "20060184787" "6970562" "20210377049" "8015409" "11329980" "20160241389" "11374771" "20210184864" "20160283723" "10097536" "11270006" "20210266304" "7630493" "20060184788" "11184160" "20200293698" "20050154889" "9984238" "20220377084" "20080082449" "8108670" "20230188364" "11606348" "20020076042" "6901512" "20080016337" "20180300489" "20020073310" "20220209944" "11405215" "10706182" "20180324175" "10211977" "20060072762" "20200193036" "20210266156" "20060182276"				

Petitioner Samsung Ex-1004, 0256

		"20200252382" "20210226938" "20220231858" "20090313470" "9367697" "20210266177" "20020078344" "20240061941" "20140229732" "20130013931" "9853979" "11095634" "9942034" "20180181756" "20020078353" "11036869" "11604901" "20190205540" "11036861" "8160244" "11757660" "7065642" "7386720" "20060072748" "10229270" "6940980" "11728974" "20200274711" "20220045867" "20170351879" "20120221854" "20120226904" "7565527" "11184157" "9590959" "11438161" "20210306162" "9100186" "9553854" "11258617" "11178116" "20220247554" "10798086" "8112628" "20190052463" "9992170" "6615350" "20210135872" "9300639" "20160323264" "20050166051" "10230730" "20060242407" "20150089244" "20180367509" "20140229729" "10127389" "10432401" "20150317487" "10277407" "20190080099" "10027484" "20220158855" "20180124056" "11671412" "7475247" "20190280883" "7599493" "20020071563" "10911457" "20020141593"					

Petitioner Samsung Ex-1004, 0257

		"10404670" "20190207942" "20170302459" "10503917" "20060013399" "20130276074" "7711120").pn.					
L268	273	("20230126356" "20230128131" "20100161956" "8612753" "20230245111" "10958424" "11804957" "20020062451" "20230069934" "10389696" "10447674" "20170310652" "20210326442" "20170171174" "20060248333" "20220318907" "7447903" "11502827" "20230246817" "20230299942" "20190097982" "11089032" "20120185680" "11620387" "20190222583" "20060117177" "10129223" "11418329" "8683215" "10554636" "7987356" "20060013402" "20170171219" "20200021567" "11777721" "11811950" "11115394" "20070055878" "20170149740" "9705859" "10382409" "10412098" "20060050870" "10243968" "20220109660" "7697691" "20210258288" "20190296917" "11687667" "11811740" "20230104126" "7149310" "10637836" "11546169" "11677729" "20100150351" "20230269241" "7715565" "20190327210" "11038853" "10375067"	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/23 04:03 PM

Petitioner Samsung Ex-1004, 0258

		"20230246850" "20230246822" "11240212" "9705674" "9667421" "20050027989" "20230053566" "20220385470" "20170005999" "9832171" "20200287876" "11722303" "10326597" "7596697" "10601789" "20180324176" "10666436" "7055032" "20100202609" "11470054" "20080172559" "20090222658" "20140229737" "20140244998" "20180083929" "20170093581" "20210266161" "20040111607" "20200213283" "9544297" "20040068650" "10511591" "9608813" "20060182283" "11502834" "8660266" "20200266976" "20230308424" "20220021525" "10313312" "20170346819" "7865721" "20230291556" "20140310516" "20060182277" "20230163946" "9516002" "10754693" "11218317" "11695555" "20130042105" "20170195119" "20220038278" "20140229739" "20180198606" "20200012527" "20220173886" "11652616" "11522686" "20190173672" "7318155" "10652015" "8745379" "9762577" "9882900" "20230142978" "20180343127" "10218502" "8745372" "20140304503"					

Petitioner Samsung Ex-1004, 0259

		"20210266147" "20210144004" "20130227286" "10121017" "8340287" "20190356650" "11582020" "20200252396" "9258117" "9208335" "11310036" "20230216662" "20210266154" "20160182486" "10484365" "11546137" "10516543" "20110202755" "10210341" "20210266152" "20160156626" "10630682" "20220337432" "20020078354" "20190104118" "8312518" "20060184786" "8213608" "20220006626" "11552946" "11757658" "20150082399" "11206135" "10911431" "11489821" "20200036707" "10521595" "20060133615" "11824974" "11582045" "20020073309" "20060184787" "6970562" "20210377049" "8015409" "11329980" "20160241389" "11374771" "20210184864" "20160283723" "10097536" "11270006" "20210266304" "7630493" "20060184788" "11184160" "20200293698" "20050154889" "9984238" "20220377084" "20080082449" "8108670" "20230188364" "11606348" "20020076042" "6901512"				

Petitioner Samsung Ex-1004, 0260

		"20080016337" "20180300489" "20020073310" "20220209944" "11405215" "10706182" "20180324175" "10211977" "20060072762" "20200193036" "20210266156" "20060182276" "20200252382" "20210226938" "20220231858" "20090313470" "9367697" "20210266177" "20020078344" "20240061941" "20140229732" "20130013931" "9853979" "11095634" "9942034" "20180181756" "20020078353" "11036869" "11604901" "20190205540" "11036861" "8160244" "11757660" "7065642" "7386720" "20060072748" "10229270" "6940980" "11728974" "20200274711" "20220045867" "20170351879" "20120221854" "20120226904" "7565527" "11184157" "9590959" "11438161" "20210306162" "9100186" "9553854" "11258617" "11178116" "20220247554" "10798086" "8112628" "20190052463" "9992170" "6615350" "20210135872" "9300639" "20160323264" "20050166051" "10230730" "20060242407" "20150089244" "20180367509" "20140229729" "10127389" "10432401" "20150317487"					

Petitioner Samsung Ex-1004, 0261

		"10277407" "20190080099" "10027484" "20220158855" "20180124056" "11671412" "7475247" "20190280883" "7599493" "20020071563" "10911457" "20020141593" "10404670" "20190207942" "20170302459" "10503917" "20060013399" "20130276074" "7711120").pn. AND (@pd @prad @rlad @ptad @ad)<20211028					
L269	43	(Artificial Intelligence) Similar to: 17/649,546 with 0 CPC Selections and 0 Text Selections Text: (US-20230130121-A1 OR US-20230128131-A1 OR US-20230126356-A1 OR US-20220094530-A1 OR WO-2022107151-A1 OR EP-4248611-A1 OR US-20180302217-A1 OR WO-2017115338-A1 OR US-20230299942-A1 OR CN-109787762-B OR US-20230153445-A1 OR US-10461943-B1 OR CN-108600222-A OR US-20230089865-A1 OR WO-2020172884-A1 OR US-11550933-B2 OR US-20210390189-A1 OR EP-3262784-A1 OR US-8745394-B1 OR US-11743044-B2 OR US-11258617-B1 OR US-20180034810-A1 OR CN-106953725-B OR US-20150074408-A1 OR CN-108242997-B OR US-11728974-B2 OR US-20090327731-A1 OR US-7370202-B2	(US-PGPUB; USPAT; USOCR; FIT (AP, AT, AU, BE, BG, BR, BY, CA, CH, CN, CS, CU, CZ, DD, DK, EA, EE, ES, FI, FR, GB, HR, HU, ID, IE, IL, IS, IT, JP, KR, LT, LU, LV, MA, MC, MD, MY, NL, NO, NZ, PH, PL, PT, RO, RS, RU, SE, SG, SI, SK, SU, TH, TN, TR, TW, UA, VN, WO))	OR	ON	ON	2024/02/23 04:10 PM

Petitioner Samsung Ex-1004, 0262

		OR EP-3850786-A1 OR WO-2020053851-A1 OR US-20230155811-A1 OR CN-109687959-B OR US-20230082949-A1 OR US-10263961-B2 OR US-20060095771-A1 OR US-20210377015-A1 OR US-11438168-B2 OR EP-4179692-A1 OR WO-2020182302-A1 OR US-20190312730-A1 OR EP-1807963-A2 OR US-11720891-B2 OR WO-2020135853-A1 OR US-9608814-B2 OR US-20230086968-A1 OR WO-2022269544-A1 OR US-8175269-B2 OR JP-2023535077-A OR US-11314888-B2 OR CN-114039722-A).did.					
L270	47	(Artificial Intelligence) Similar to: 17/649,546 with 0 CPC Selections and 1 Text Selection Text: (US-11388149-B2 OR US-7596697-B2 OR WO-2006078556-A2 OR US-20230130121-A1 OR US-20200382289-A1 OR US-20230126356-A1 OR US-20220321339-A1 OR US-11757634-B2 OR US-20220255731-A1 OR US-20200169410-A1 OR EP-3673609-A1 OR WO-2020006319-A1 OR WO-2019202586-A1 OR CN-115037435-A OR US-10887110-B2 OR US-20230128131-A1 OR US-20220131688-A1 OR US-11626980-B2 OR US-20070055878-A1 OR CN-111143894-A OR US-11201734-B2 OR GB-2611276-A OR US-9973496-B2 OR	(US-PGPUB; USPAT; USOCR; FIT (AP, AT, AU, BE, BG, BR, BY, CA, CH, CN, CS, CU, CZ, DD, DK, EA, EE, ES, FI, FR, GB, HR, HU, ID, IE, IL, IS, IT, JP, KR, LT, LU, LV, MA, MC, MD, MY, NL, NO, NZ, PH, PL, PT, RO, RS, RU, SE, SG, SI, SK, SU, TH, TN, TR, TW, UA, VN, WO))	OR	ON	ON	2024/02/23 04:11 PM

Petitioner Samsung Ex-1004, 0263

		US-20190372760-A1 OR US-11258617-B1 OR US-20220029796-A1 OR KR-20160105717-A OR KR-20230031278-A OR US-20220417032-A1 OR JP-2023535077-A OR EP-4179692-A1 OR US-20220045853-A1 OR US-7599493-B2 OR KR-101784488-B1 OR US-10686597-B1 OR US-11831755-B2 OR US-11509458-B2 OR US-11704150-B2 OR US-11108753-B2 OR WO-2016191376-A1 OR US-9813234-B2 OR US-10764261-B2 OR KR-20210127168-A OR US-20060182283-A1 OR US-20160335440-A1 OR US-20160277373-A1 OR CN-114785491-A OR US-20100202609-A1 OR US-11126709-B2 OR EP-3050011-A1).did.					
L271	49249470	rotating concentric circular	(US-PGPUB; USPAT; USOCR; FIT (AP, AT, AU, BE, BG, BR, BY, CA, CH, CN, CS, CU, CZ, DD, DK, EA, EE, ES, FI, FR, GB, HR, HU, ID, IE, IL, IS, IT, JP, KR, LT, LU, LV, MA, MC, MD, MY, NL, NO, NZ, PH, PL, PT, RO, RS, RU, SE, SG, SI, SK, SU, TH, TN, TR, TW, UA, VN, WO); FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2024/03/05 10:02 AM
L272	3670	rotating near4 concentric near4 circular	(US-PGPUB; USPAT; USOCR; FIT (AP, AT, AU, BE, BG, BR, BY, CA, CH, CN, CS, CU, CZ, DD, DK, EA, EE, ES, FI, FR, GB, HR, HU, ID, IE, IL, IS, IT, JP, KR, LT, LU, LV, MA, MC, MD, MY, NL, NO, NZ, PH, PL, PT, RO, RS, RU, SE, SG, SI, SK, SU, TH, TN, TR,	OR	ON	ON	2024/03/05 10:02 AM

Petitioner Samsung Ex-1004, 0264

			TW, UA, VN, WO); FPRS; EPO; JPO; DERWENT; IBM_TDB)				
L273	0	rotating near4 concentric near4 circular AND captcha	(US-PGPUB; USPAT; USOCR; FIT (AP, AT, AU, BE, BG, BR, BY, CA, CH, CN, CS, CU, CZ, DD, DK, EA, EE, ES, FI, FR, GB, HR, HU, ID, IE, IL, IS, IT, JP, KR, LT, LU, LV, MA, MC, MD, MY, NL, NO, NZ, PH, PL, PT, RO, RS, RU, SE, SG, SI, SK, SU, TH, TN, TR, TW, UA, VN, WO); FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2024/03/05 10:02 AM
L274	42	rotating ADJ concentric ADJ circular	(US-PGPUB; USPAT; USOCR; FIT (AP, AT, AU, BE, BG, BR, BY, CA, CH, CN, CS, CU, CZ, DD, DK, EA, EE, ES, FI, FR, GB, HR, HU, ID, IE, IL, IS, IT, JP, KR, LT, LU, LV, MA, MC, MD, MY, NL, NO, NZ, PH, PL, PT, RO, RS, RU, SE, SG, SI, SK, SU, TH, TN, TR, TW, UA, VN, WO); FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2024/03/05 10:04 AM
L275	414	(neural near6 network) near6 (password pass$1word passphrase pass$1phrase)	(US-PGPUB; USPAT; USOCR; FIT (AP, AT, AU, BE, BG, BR, BY, CA, CH, CN, CS, CU, CZ, DD, DK, EA, EE, ES, FI, FR, GB, HR, HU, ID, IE, IL, IS, IT, JP, KR, LT, LU, LV, MA, MC, MD, MY, NL, NO, NZ, PH, PL, PT, RO, RS, RU, SE, SG, SI, SK, SU, TH, TN, TR, TW, UA, VN, WO); FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2024/02/27 09:52 PM
L276	69	(neural near6 network) near6 (password pass$1word passphrase pass$1phrase)	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/27 09:52 PM
L277	209	(neural near6 network) same4 (generat$8 deriv$8) near6	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/27 09:53 PM

Petitioner Samsung Ex-1004, 0265

		(password pass$1word passphrase pass$1phrase)					
L278	7	xenomorphic	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/27 09:56 PM
L279	650	unpredictab$8 near6 (cryptogra$8)	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/27 09:57 PM
L280	1138	unpredictab$8 near6 (cryptogra$8 encrypt$8)	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/27 09:57 PM
L281	5	unpredictab$8 near6 (cryptogra$8 encrypt$8) same4 (neural near6 network)	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/27 09:58 PM
L282	39	unpredictab$8 near6 (cryptogra$8 encrypt$8) AND (neural near6 network)	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/27 09:58 PM
L283	1	"20230050628".pn. AND rac$8 near6 (node keynode neural)	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/28 09:10 AM
L284	1	"20230050628".pn. AND (rac$8 rac$8 near6 (node keynode neural))	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/28 09:10 AM
L285	1	"20230050628".pn. AND (biome$8)	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/28 09:14 AM
L286	5	(eeg) near6 key WITH (genera$8 deriv$8) AND (cryptogra$8 encrypt$8)	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/28 09:47 AM
L287	6	(eeg electro$1encephal$8) near6 key WITH (genera$8 deriv$8) AND (cryptogra$8 encrypt$8)	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/28 09:49 AM
L288	6	(eeg electro$1encephal$8 electroencephal$8) near6 key WITH (genera$8 deriv$8) AND (cryptogra$8 encrypt$8)	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/28 09:49 AM
L289	1	"9672760".pn.	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/28 10:25 AM
L290	6	("20190163559" "20180027009").pn.	(US-PGPUB; USPAT; USOCR; FIT (AP, AT, AU, BE, BG, BR, BY, CA, CH, CN, CS, CU, CZ, DD, DK, EA, EE, ES, FI, FR, GB, HR, HU, ID, IE, IL, IS, IT, JP, KR, LT, LU, LV,	OR	ON	ON	2024/02/29 10:59 AM

Petitioner Samsung Ex-1004, 0266

			MA, MC, MD, MY, NL, NO, NZ, PH, PL, PT, RO, RS, RU, SE, SG, SI, SK, SU, TH, TN, TR, TW, UA, VN, WO); FPRS; EPO; JPO; DERWENT; IBM_TDB)				
L291	2	("20190163559" "20180027009").pn.	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/29 10:59 AM
L292	8226	(section portion segment fragment clip) near6 (video stream) near8 (user person) near8 (authori$8 authenti$8 credenti$8 map$8 associat$8)	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/01 09:10 AM
L293	7636	(section portion segment fragment clip) near6 (video stream) near8 (user person) near6 (authori$8 authenti$8 credenti$8 map$8 associat$8)	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/01 09:10 AM
L294	646	(distrib$8 transm$8 send sending sent) near8 (section portion segment fragment clip) near6 (video stream) near8 (user person) near6 (authori$8 authenti$8 credenti$8 map$8 associat$8)	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/01 09:10 AM
L295	2039	(distrib$8 transm$8 send sending sent identif$8 determin$8) near8 (section portion segment fragment clip) near6 (video stream) near8 (user person) near6 (authori$8 authenti$8 credenti$8 map$8 associat$8)	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/01 09:11 AM
L296	265	(distrib$8 transm$8 send sending sent identif$8 determin$8) near8 (section portion segment fragment clip) near6 (video stream) near8 (user person) near6 (authori$8 authenti$8 credenti$8 map$8 associat$8) AND surve$8	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/01 09:12 AM
L297	265	(distrib$8 transm$8 send sending sent	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/01 09:12 AM

Petitioner Samsung Ex-1004, 0267

		identif$8 determin$8) near8 (section portion segment fragment clip) near6 (video stream) near8 (user person) near6 (authori$8 authenti$8 credenti$8 map$8 associat$8) AND surve$9					
L298	21	cervetti.xp. AND surveillance	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/01 09:44 AM
L299	19	cervetti.xp. AND surveillance AND (authori$8 authentic$8 permiss$8 credenti$8 associat$8 personnel)	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/01 09:46 AM
L300	15	cervetti.xp. AND surveillance same4 (authori$8 authentic$8 permiss$8 credenti$8 associat$8 personnel)	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/01 09:46 AM
L301	271570	encrypt$8 near6 key near6 (vault storage device usb manager)	(US-PGPUB; USPAT; USOCR; FIT (AP, AT, AU, BE, BG, BR, BY, CA, CH, CN, CS, CU, CZ, DD, DK, EA, EE, ES, FI, FR, GB, HR, HU, ID, IE, IL, IS, IT, JP, KR, LT, LU, LV, MA, MC, MD, MY, NL, NO, NZ, PH, PL, PT, RO, RS, RU, SE, SG, SI, SK, SU, TH, TN, TR, TW, UA, VN, WO); FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2024/02/27 09:05 PM
L302	85553	encrypt$8 near6 key near6 (vault storage device usb manager)	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/27 09:05 PM
L303	6405	encrypt$8 near6 key near6 (vault storage device usb manager) WITH (case casing housing)	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/27 09:05 PM
L304	794	encrypt$8 near6 key near6 (vault storage device usb manager) WITH (case casing housing) WITH (authentic$8 authori$8)	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/27 09:06 PM
L305	489	encrypt$8 near6 key near6 (vault storage device usb manager) WITH (personal) WITH (authentic$8 authori$8)	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/27 09:15 PM

L306	1	"20230306106".pn. AND (network$8 protect$8 secur$8)	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/28 10:48 AM
L307	1	"20230306106".pn. AND (detect$8 determin$8)	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/28 10:49 AM

PE2E SEARCH - Search History (Interference)

There are no Interference searches to show.

Doc code: IDS
Doc description: Information Disclosure Statement (IDS) Filed

PTO/SB/08a (02-18)
Approved for use through 11/30/2020. OMB 0651-0031
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

INFORMATION DISCLOSURE STATEMENT BY APPLICANT

(Not for submission under 37 CFR 1.99)

Application Number	18229907
Filing Date	2023-08-03
First Named Inventor	John A. Nix
Art Unit	
Examiner Name	
Attorney Docket Number	63121/0224

U.S.PATENTS Remove

Examiner Initial*	Cite No	Patent Number	Kind Code[1]	Issue Date	Name of Patentee or Applicant of cited Document	Pages,Columns,Lines where Relevant Passages or Relevant Figures Appear
	1	10169587	B1	2019-01-01	Nix	
	2	10621352	B2	2020-04-14	NIx	

If you wish to add additional U.S. Patent citation information please click the Add button. Add

U.S.PATENT APPLICATION PUBLICATIONS Remove

Examiner Initial*	Cite No	Publication Number	Kind Code[1]	Publication Date	Name of Patentee or Applicant of cited Document	Pages,Columns,Lines where Relevant Passages or Relevant Figures Appear
	1	20060021063	A1	2006-01-26	Hori	
	2	20100093347	A1	2010-04-15	Hahn et al.	
	3	20110158411	A1	2011-06-30	Medvinsky et al.	
	4	20210126801	A1	2021-04-29	Nix	

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /DGC/

INFORMATION DISCLOSURE STATEMENT BY APPLICANT

(Not for submission under 37 CFR 1.99)

Application Number	18229907
Filing Date	2023-08-03
First Named Inventor	John A. Nix
Art Unit	
Examiner Name	
Attorney Docket Number	63121/0224

	5	20200280436	A1	2020-09-03	Nix	
	6	20210218560	A1	2021-07-15	Nix	
	7	20210184842	A1	2021-06-17	Nix	
	8	20210194681	A1	2021-06-24	Nix	
	9	20190356482	A1	2019-11-21	Nix	
	10	20200226258	A1	2020-07-16	Nix	
	11	20190313246	A1	2019-10-10	Nix	
	12	20210211279	A1	2021-07-08	Nix	
	13	20200162269	A1	2020-05-21	Nix	
	14	20200162247	A1	2020-05-21	Nix	
	15	20190332774	A1	2019-10-31	Nix	

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /DGC/

INFORMATION DISCLOSURE STATEMENT BY APPLICANT

(Not for submission under 37 CFR 1.99)

Application Number	18229907
Filing Date	2023-08-03
First Named Inventor	John A. Nix
Art Unit	
Examiner Name	
Attorney Docket Number	63121/0224

	16	20110167272	A1	2011-07-07	Vladimir Y. Kolesnikov	

If you wish to add additional U.S. Published Application citation information please click the Add button. Add

FOREIGN PATENT DOCUMENTS Remove

Examiner Initial*	Cite No	Foreign Document Number[3]	Country Code[2]	Kind Code[4]	Publication Date	Name of Patentee or Applicant of cited Document	Pages,Columns,Lines where Relevant Passages or Relevant Figures Appear	T[5]
	1	2518976	GB	A	2015-04-08	Vodafone IP Licensing Ltd		☐
	2	2021007235	WO	A1	2021-01-14	Nix		☐
	3	2021007235	WO	A1	2021-01-14	Nix		☐
	4	2021087221	WO	A1	2021-05-06	Nix		☐
	5	2020223319	WO	A1	2020-11-05	Nix		☐
	6	2020006162	WO	A1	2020-01-02	Nix		☐
	7	2019246206	WO	A1	2019-12-26	Nix		☐
	8	2019222319	WO	A1	2019-11-21	Nix		☐

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /DGC/

INFORMATION DISCLOSURE STATEMENT BY APPLICANT

(Not for submission under 37 CFR 1.99)

Application Number	18229907
Filing Date	2023-08-03
First Named Inventor	John A. Nix
Art Unit	
Examiner Name	
Attorney Docket Number	63121/0224

	9	2019209598	WO	A1	2019-10-31	Nix		☐
	10	2019178312	WO	A1	2019-09-19	Nix		☐
	11	2020123959	WO	A1	2020-06-18	Nix		☐
	12	2020061023	WO	A1	2020-03-26	Nix		☐
	13	3110641	CA	A1	2019-10-31	Nix		☐
	14	3110468	CA	A1	2019-11-21	Nix		☐
	15	19803936	DE	A1	1999-08-05	Osram GmbH Siemens AG		☐
	16	3766222	EP	A1	2021-01-20	Nix		☐
	17	20130026351	KR	A	2013-03-13	SAMSUNG ELECTRONICS CO LTD	English Abstract	☒
	18	2013/048084	WO	A2	2013-04-04	SAMSUNG ELECTRONICS CO LTD	English Abstract	☐

If you wish to add additional Foreign Patent Document citation information please click the Add button Add

NON-PATENT LITERATURE DOCUMENTS Remove

EFS Web 2.1.18

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /DGC/

INFORMATION DISCLOSURE STATEMENT BY APPLICANT

(Not for submission under 37 CFR 1.99)

Application Number	18229907
Filing Date	2023-08-03
First Named Inventor	John A. Nix
Art Unit	
Examiner Name	
Attorney Docket Number	63121/0224

Examiner Initials*	Cite No	Include name of the author (in CAPITAL LETTERS), title of the article (when appropriate), title of the item (book, magazine, journal, serial, symposium, catalog, etc), date, pages(s), volume-issue number(s), publisher, city and/or country where published.	T[5]
	1	Search Report issued in UK Application No. GB2108534.5 dated July 7, 2021.	☐
	2	European Patent Office Communication with European Search Report and European Search Opinion issued in EP 21182424.8 dated October 12, 2021.	☐
	3	European Patent Office Communication with European Search Report and European Search Opinion issued in EP 21182451.1 dated October 12, 2021.	☐
	4	European Patent Office Communication with European Search Report and European Search Opinion issued in EP 21182432.1 dated October 12, 2021.	☐
	5	TLS 1.3 Wish List Presentation, IETF 87 (Eric Rescorla), dated August 1, 2013.	☐

If you wish to add additional non-patent literature document citation information please click the Add button Add

EXAMINER SIGNATURE

Examiner Signature	/David Garcia Cervetti/	Date Considered	03/08/2024

*EXAMINER: Initial if reference considered, whether or not citation is in conformance with MPEP 609. Draw line through a citation if not in conformance and not considered. Include copy of this form with next communication to applicant.

[1] See Kind Codes of USPTO Patent Documents at www.USPTO.GOV or MPEP 901.04. [2] Enter office that issued the document, by the two-letter code (WIPO Standard ST.3). [3] For Japanese patent documents, the indication of the year of the reign of the Emperor must precede the serial number of the patent document. [4] Kind of document by the appropriate symbols as indicated on the document under WIPO Standard ST.16 if possible. [5] Applicant is to place a check mark here if English language translation is attached.

EFS Web 2.1.18

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /DGC/

INFORMATION DISCLOSURE STATEMENT BY APPLICANT

(Not for submission under 37 CFR 1.99)

Application Number	18229907
Filing Date	2023-08-03
First Named Inventor	John A. Nix
Art Unit	
Examiner Name	
Attorney Docket Number	63121/0224

CERTIFICATION STATEMENT

Please see 37 CFR 1.97 and 1.98 to make the appropriate selection(s):

☐ That each item of information contained in the information disclosure statement was first cited in any communication from a foreign patent office in a counterpart foreign application not more than three months prior to the filing of the information disclosure statement. See 37 CFR 1.97(e)(1).

OR

☐ That no item of information contained in the information disclosure statement was cited in a communication from a foreign patent office in a counterpart foreign application, and, to the knowledge of the person signing the certification after making reasonable inquiry, no item of information contained in the information disclosure statement was known to any individual designated in 37 CFR 1.56(c) more than three months prior to the filing of the information disclosure statement. See 37 CFR 1.97(e)(2).

☐ See attached certification statement.

☐ The fee set forth in 37 CFR 1.17 (p) has been submitted herewith.

☒ A certification statement is not submitted herewith.

SIGNATURE

A signature of the applicant or representative is required in accordance with CFR 1.33, 10.18. Please see CFR 1.4(d) for the form of the signature.

Signature	/Keith J. Barkaus/	Date (YYYY-MM-DD)	2023-12-05
Name/Print	Keith J. Barkaus	Registration Number	51,431

This collection of information is required by 37 CFR 1.97 and 1.98. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 1 hour to complete, including gathering, preparing and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.**

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /DGC/

Privacy Act Statement

The Privacy Act of 1974 (P.L. 93-579) requires that you be given certain information in connection with your submission of the attached form related to a patent application or patent. Accordingly, pursuant to the requirements of the Act, please be advised that: (1) the general authority for the collection of this information is 35 U.S.C. 2(b)(2); (2) furnishing of the information solicited is voluntary; and (3) the principal purpose for which the information is used by the U.S. Patent and Trademark Office is to process and/or examine your submission related to a patent application or patent. If you do not furnish the requested information, the U.S. Patent and Trademark Office may not be able to process and/or examine your submission, which may result in termination of proceedings or abandonment of the application or expiration of the patent.

The information provided by you in this form will be subject to the following routine uses:

1. The information on this form will be treated confidentially to the extent allowed under the Freedom of Information Act (5 U.S.C. 552) and the Privacy Act (5 U.S.C. 552a). Records from this system of records may be disclosed to the Department of Justice to determine whether the Freedom of Information Act requires disclosure of these record s.

2. A record from this system of records may be disclosed, as a routine use, in the course of presenting evidence to a court, magistrate, or administrative tribunal, including disclosures to opposing counsel in the course of settlement negotiations.

3. A record in this system of records may be disclosed, as a routine use, to a Member of Congress submitting a request involving an individual, to whom the record pertains, when the individual has requested assistance from the Member with respect to the subject matter of the record.

4. A record in this system of records may be disclosed, as a routine use, to a contractor of the Agency having need for the information in order to perform a contract. Recipients of information shall be required to comply with the requirements of the Privacy Act of 1974, as amended, pursuant to 5 U.S.C. 552a(m).

5. A record related to an International Application filed under the Patent Cooperation Treaty in this system of records may be disclosed, as a routine use, to the International Bureau of the World Intellectual Property Organization, pursuant to the Patent Cooperation Treaty.

6. A record in this system of records may be disclosed, as a routine use, to another federal agency for purposes of National Security review (35 U.S.C. 181) and for review pursuant to the Atomic Energy Act (42 U.S.C. 218(c)).

7. A record from this system of records may be disclosed, as a routine use, to the Administrator, General Services, or his/her designee, during an inspection of records conducted by GSA as part of that agency's responsibility to recommend improvements in records management practices and programs, under authority of 44 U.S.C. 2904 and 2906. Such disclosure shall be made in accordance with the GSA regulations governing inspection of records for this purpose, and any other relevant (i.e., GSA or Commerce) directive. Such disclosure shall not be used to make determinations about individuals.

8. A record from this system of records may be disclosed, as a routine use, to the public after either publication of the application pursuant to 35 U.S.C. 122(b) or issuance of a patent pursuant to 35 U.S.C. 151. Further, a record may be disclosed, subject to the limitations of 37 CFR 1.14, as a routine use, to the public if the record was filed in an application which became abandoned or in which the proceedings were terminated and which application is referenced by either a published application, an application open to public inspections or an issued patent.

9. A record from this system of records may be disclosed, as a routine use, to a Federal, State, or local law enforcement agency, if the USPTO becomes aware of a violation or potential violation of law or regulation.

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /DGC/

Summaries with Thumbnails

Report Run Date: 2024-03-08
Results included: 50
Results Priority Date Range:
Results Publication Date Range: 1993-09-01 to 2013-10-01

Main Concept Document: US20230379148 (Key Derivation for a Module Using an Embedded Universal Integrated Circuit Card)
Collections (24): IEEE Xplore Publications: IEEE Periodicals, IEEE Xplore Publications: IEEE Conferences, IEEE Xplore Publications: IEEE Standards, IEEE Xplore Publications: IEEE Early Access, IEEE Xplore Publications:...
Filter: Publication Date: To 2013-11-19

Publication contains information from a representative family member.

Petitioner Samsung Ex-1004, 0277

Search Criteria

Main Concept Document: US20230379148 (Key Derivation for a Module Using an Embedded Universal Integrated Circuit Card)

Collections (24): IEEE Xplore Publications: IEEE Periodicals, IEEE Xplore Publications: IEEE Conferences, IEEE Xplore Publications: IEEE Standards, IEEE Xplore Publications: IEEE Early Access, IEEE Xplore Publications: SMPTE Periodicals, IEEE Xplore Publications: SMPTE Conferences, IEEE Xplore Publications: SMPTE Standards, IEEE Xplore Publications: MIT Press eBooks, IEEE Xplore Publications: Wiley-IEEE eBooks, IEEE Xplore Publications: IBM Periodicals, IEEE Xplore Publications: URSI Periodicals, IEEE Xplore Publications: VDE Conferences, IEEE Xplore Publications: Periodicals from China, IEEE Xplore Publications: Ericsson Technology Review, IP.com Prior Art Database: The IP.com Journal, IP.com Prior Art Database: Internet Society RFC, IP.com Prior Art Database: IBM TDB Archive, IP.com Prior Art Database: Legacy Journals, IP.com Prior Art Database: Software Patent Institute, OnePetro.org: Periodicals at OnePetro.org, OnePetro.org: Conferences at OnePetro.org, Other Literature: IBM Redbooks, Other Literature: PubMed Central, Other Literature: arXiv.org


Filter:

Publication Date: To 2013-11-19

Petitioner Samsung Ex-1004, 0278

5732849 | **Publication Date: 2011-01-01** |


WiMAX EndtoEnd Security Framework



Abstract:
This chapter contains sections titled: General Overview WiMAX Security Requirements End-to-End Security Architecture Security Zones Summary

5237851 | **Publication Date: 2007-01-01** |

Mobile Terminal Security




Abstract:
This chapter contains sections titled: Introduction WLAN and WPAN Security GSM and 3GPP Security Mobile Platform Layer Security Hardware Attacks on Mobile Equipment Conclusion References

Petitioner Samsung Ex-1004, 0279

5236634 | **Publication Date: 2005-01-01** |

IP Security



Abstract:
This chapter contains sections titled: Introduction Security of Telecommunications Services Security Objectives OSI Model for Cryptographic Security Message Confidentiality Data Integrity Identification of Participants Authentication of Participants Access Control Nonrepudiation Secure Management of Cryptographic Keys Exchange of Secret Keys: Kerberos Exchange of Public Keys Certificate Management Applications for Network Management Encryption Cracks Summary Appendix I: Areas Related to Security Policies Appendix II: Principles of Symmetric Encryption AII.1 Modes of Algorithm Utilization for Block Encryption AII.2 Examples of Symmetric Block Encryption Algorithms Appendix III: Principles of Public Key Encryption AIII.1 RSA AIII.2 Public Key Cryptography Standards AIII.3 Pretty Good Privacy AIII.4 Elliptic Curve Cryptography Appendix IV: Principles of the Digital Signature Algorithm References

738651 | **Publication Date: 1998-01-01** |

Mutual Authentication, Confidentiality, and Key MANagement (MACKMAN) system for mobile computing and wireless communication

Image not currently available

Abstract:
In any distributed networked environment, security systems for network access and communication are necessary to allow legitimate hosts on the network to access the network services while denying non-registered hosts. Ideally, such systems should ensure both confidentiality and integrity of messages exchanged over the network. We discuss the deficiencies with the registration and authentication services provided by Global System for Mobile Communication (GSM), Cellular Digital Packet Data (CDPD), and IS-41. Next, we present the design of the Mutual Authentication, Confidentiality, and Key MANagement (MACKMAN) system to provide a more secure registration and authentication service for mobile computing and wireless communication. The capabilities provided by MACKMAN include registration of legitimate hosts with the network, mutual authentication, and data confidentiality and integrity in a mobile and wireless environment. Data confidentiality and integrity are provided by using the...

Petitioner Samsung Ex-1004, 0280

1580513 | **Publication Date: 2006-02-01** |

Wireless Network Security and Interworking



Image not currently available

Abstract:
A variety of wireless technologies have been standardized and commercialized, but no single technology is considered the best because of different coverage and bandwidth limitations. Thus, interworking between heterogeneous wireless networks is extremely important for ubiquitous and high-performance wireless communications. Security in interworking is a major challenge due to the vastly different security architectures used within each network. The goal of this paper is twofold. First, we provide a comprehensive discussion of security problems and current technologies in 3G and WLAN systems. Second, we provide introductory discussions about the security problems in interworking, the state-of-the-art solutions, and open problems.

6772303 | **Publication Date: 2002-01-01** |

Wireless network security architecture



Image not currently available

Abstract:
Cellular bandits have exploited security limitations of analog technology from its infancy. First-generation analog system security has been primarily left up to system manufacturers and service providers. With the advent of digital technology (second generation [2G]), the standards organizations aggressively developed techniques and cryptographic methods to protect the service provider from fraudulent use of network resources and to provide user privacy. Third-generation (3G) digital wireless systems offer significant improvement of security techniques that address all known 2G deficiencies and allow strong service protection for many years to come. This paper discusses in detail the wireless security architecture evolution (voice and data) with special emphasis on the latest standards developed for 3G wireless systems, including 2G/3G interoperability issues. Both the Universal Mobile Telecommunications System (developed by the 3rd Generation Partnership Project [3GPP]) and CDMA2000...

Petitioner Samsung Ex-1004, 0281

1264392 | **Publication Date: 2003-01-01** |


Security overview for m-payed virtual ticketing

Image not currently available

Abstract:
The use of wireless and mobile devices is expanding worldwide; with a growing eagerness to find new and useful ways to apply mobile technologies. New applications, as mobile ticketing, can benefit of mobile-payment facility. This paper aims to provide a mobile ticketing system design for PDA, scalable to other mobile devices, presenting a wireless weaknesses overview and security building blocks for mobile ticket and mobile payment relying on.

5396931 | **Publication Date: 2009-01-01** |

Network Management and Security



Abstract:
This chapter contains sections titled: Introduction Contents The Information Technology Infrastructure Library The Enhanced Telecom Operations Map The Simple Network Management Protocol (SNMP) Security Requirements References

Petitioner Samsung Ex-1004, 0282

6768209 | **Publication Date: 2006-04-01** |


Security architecture for IP-based multi-service networks

Image not currently available

Abstract:
The telecommunications industry's transition to Internet Protocol (IP)-based networks is exciting and cost effective, but it also introduces new challenges for service providers, particularly as they begin to integrate Web services with communication services. Security is one key area that poses a significant challenge for service providers while at the same time providing opportunities for vendors. Because these new networks will have a number of service enablers and enriched services will be offered, application and user identity security becomes a chief concern. This paper focuses on IP-based services security architecture for evolving wireless and public domain networks, especially where Web services are brought into play. A Security Assertion Markup Language (SAML) is a basis for the security architecture, which incorporates federated architecture, authentication, encryption, and digital rights management. The paper also details a blended service scenario, highlighting enforcement...

5312361 | **Publication Date: 1999-01-01** |

Support Mechanisms



Abstract:
This chapter contains sections titled: Security Alarms Security Audit Log Key Distribution Directory Protocols for Security GSS-API-Security in a Box GULS-Soaring Security SSL3-Safe Surf IPsec Security Engineering

Petitioner Samsung Ex-1004, 0283

Petitioner Samsung Ex-1004, 0284

888163 | **Publication Date: 1998-01-01** |

Authentication protocols for wireless ATM networks



Image not currently available

Abstract:
With the growing acceptance of ATM as the standard for broadband networking and the increasing importance of wireless devices, it has become appropriate to extend ATM application to wireless platforms. Adding a wireless network to existing wired networks creates a new set of problems. Security functions have to be reconsidered since wired network security does not account for the open medium, mobile roaming. A necessary foundation for securing a network is the ability to authenticate entities. There is a need to authenticate users of the system so that the resources will not be misused by nonsubscribers. After authentication by a suitable protocol, two parties involved in communications should be entitled to believe that they are communicating with each other and not with intruders. Good authentication is that which allows entities to provide evidence that they know a particular secret without revealing the secret. It should not provide any information to impersonators or eavesdroppers...

4205180 | **Publication Date: 2006-11-01** |

Enabling Secure Mobile Access for Electronic Health Care Applications



Image not currently available

Abstract:
Medical applications have already been integrated into mobile devices (e.g. Tablet PCs, PDAs and smart phones) and are being used by medical personnel in treatment centers, for retrieving and examining patient's Electronic Health Records (EHR). In such mobile healthcare applications, specific attention is drawn towards the security requirements since the transmission of sensitive medical data through a public network renders the problem of communication privacy. In this paper we present an approach to transfer the medical records of an individual by using the existing infrastructure of mobile operators. To achieve that, we propose the application of existing technologies in 3G networks such as the generic bootstrapping architecture (GBA) to enable the secure transfer of EHR data. The paper presents the corresponding applicability scenarios, initial results from a prototype test bed and discusses the feasibility of the proposed solution along with its limitations

5644999 | **Publication Date: 2010-10-01** |

Forming Virtualized Secure Framework for Location Based Services (LBS) using Direct Anonymous Attestation (DAA) protocol

Image not currently available

Abstract:
The tremendous growth in mobile and wireless communications comes with more pervasive applications. Current mobile device platform does not allow a local or remote user to attest the target platform. The limitation of using existing software-based protection alone can be easily affected by malicious codes and it cannot assure its own integrity. In this paper, we explore a new approach of anonymity issues in Privacy Enhancing Technologies (PETs) which will result in the privacy enhancement of user personal data and location information in mobile network services. We create the foundation for running trusted applications, network and services on top of existing Mobile Location Protocol (MLP). We also propose a Virtualized Secure Framework between mobile devices (clients) and Location Based Services (LBS) Server in Virtual Machine (VM) environment based on Direct Anonymous Attestation protocol. Trusted Platform Module (TPM) acts as the foundation for mobile security mechanisms and privacy...

5593244 | **Publication Date: 2010-08-01** |

Security advances and challenges in 4G wireless networks


Image not currently available

Abstract:
This paper presents a study of security advances and challenges associated with emergent 4G wireless technologies. The paper makes a number of contributions to the field. First, it studies the security standards evolution across different generations of wireless standards. Second, the security-related standards, architecture and design for the LTE and WiMAX technologies are analyzed. Third, security issues and vulnerabilities present in the above 4G standards are discussed. Finally, we point to potential areas for future vulnerabilities and evaluate areas in 4G security which warrant attention and future work by the research and advanced technology industry.

Petitioner Samsung Ex-1004, 0285

5738981 | **Publication Date: 2011-02-01** |


LRAP: A Location-Based Remote Client Authentication Protocol for Mobile Environments



Abstract:
Mobile networks are driven by the need to provide more advanced services to mobile or nomadic computing devices, such as security services requiring remote client authentication. In such services, the user's location might be used as authentication factor, in addition to the typical authentication factors, like passwords, or one time tokens combined with the use of a physical device that a person owns, such as a card or a phone. Since the location information itself is subject to forging attacks, additional mechanisms must be used to certify its integrity. We propose LRAP, a novel protocol combining several authentication factors to securely authenticate a mobile user. In LRAP, the user's location can be determined and its correctness is certified by a third trusted party, called Local Element. As use case, we considered the payment service at the self-service gas stations, a widely available service vulnerable to several types of security attacks, and we proposed an LRAP-based service...

4682272 | **Publication Date: 2008-11-01** |

An Architecture to Support Multiple Subscriber Identity Applications Accessing Multiple Mobile Telecommunication Access Network Systems



Abstract:
With the advances in smart card technology it is quite possible to support more than one type of subscriber identity applications on the same smart card. We propose an architecture capable of hosting multi faceted subscriber identity applications which exploits common functions and data in a secure partitioned manner. The associated security mechanisms are also defined in order to realise its implementation on a single smart card. Our proposed architecture provides a harmonised secure authentication environment. The architecture is extensible to platforms on mobile devices and secure tokens operating across diverse access interfaces. Furthermore, we propose a set of protocols for secure communications between terminal, control module and hosted subscriber identity applications.

Petitioner Samsung Ex-1004, 0286

1691309 | **Publication Date: 2006-01-01** |

A Fast Elliptic Curve Based Key Agreement Protocol-on-Chip (PoC) for Securing Networked Embedded Systems




Image not currently available

Abstract:
Securing communication sessions between networked embedded systems is a major challenge that needs to be addressed as an increasing number of such systems become Internet-enabled. Securely and quickly establishing a session key between communicating nodes in a network requires authentication of node identities. In this paper, we propose a simple elliptic-curve based key negotiation protocol suitable for fully hardware implementation as a protocol on chip (PoC). The protocol uses the elliptic curve variants of both the Diffie Hellmann exchange and the digital signature algorithm. Timing results demonstrate that an end-to-end protocol run can be performed in as little as 28ms on a 25MHz clock, which is several times faster than previous microprocessor-based implementations of similar protocols. The results indicate that session keys can thereby have shorter lifetimes, since there is little computational overhead in re-generating them, thus enhancing overall security of the networked...

8640910 | **Publication Date: 2010-10-01** |

Operator-based over-the-air M2M wireless sensor network security



Image not currently available

Abstract:
We describe a novel method for over-the-air automated authentication and verification of machine-to-machine (M2M) wireless sensor networks using the existing authentication assets of a cellular telecom operator. We extend the standard Generic Bootstrapping Architecture (GBA) provided in the 3GPP specifications to implement our solution with minimal additional hardware and software requirements.

Petitioner Samsung Ex-1004, 0287

6687998 | **Publication Date: 2013-10-01** |

TSAF: Tamper-resistant and scalable mutual authentication framework for plug-in EV charging



Abstract:
Aligned with the roll-out of plug-in Electric Vehicles (EV), a key area of research to enable high EV penetration is a secure and efficient charging system for EV batteries. In recent literature on EVs, reliable and cost-efficient grid operations under high EV penetrations assume the need of EV charging load control. In this scenario, EV charging (and discharging) must be adapted in real time to current grid constraints and sudden grid status changes. However, for realizing these load control functions, grids and EVs should trust each other before executing the operation. Whenever an EV is plugged into a grid for charging, it must be authenticated by the grid; otherwise, EVs and grids are open to security threats that could result in serious safety hazards and billing issues. In this paper, we first view the EV authentication problem as a mutual-authentication problem within a mobile and hostile machine-to-machine (M2M) communication setting. We describe a mutual authentication system...

4622895 | **Publication Date: 2008-08-01** |

User Authentication Mechanism Using Java Card for Personalized IPTV Services



Abstract:
Internet protocol television (IPTV), becoming a popular business model, provides interactive and personalized service. IPTV provides identification, authentication and personalized services though Set-top box (STB) by a unique hardware identifier. This is based on box-level identification, which is inconsistent with IPTV's main intention of providing personalized services. The goal of the proposed system is to provide an opportunity to use the flexible user-centric authentication mechanism through Java card applets in the IPTV application server and 3G wideband code division multiple access (W-CDMA) networks. When a viewer watching IPTV is successfully authenticated, an authentication token allows the subscriber to conveniently use services which are adaptable to personal preference anywhere at anytime. In addition, this paper presents effectiveness and security analysis for verifying the proposal.

Petitioner Samsung Ex-1004, 0288

5636068 | **Publication Date: 2010-09-01** |

The Mobile Phone as a Multi OTP Device Using Trusted Computing



Image not currently available

Abstract:
The rapid growth in the number of online services leads to an increasing number of different digital identities each user needs to manage. As a result, many people feel overloaded with credentials, which in turn negatively impacts their abilityto manage them securely. Passwords are perhaps the most common type of credential used today. To avoid the tedious task of remembering difficult passwords, users often behave less securely by using low entropy and weak passwords. Weak passwords and bad password habits represent security threats to online services. Some solutions have been developed to eliminate the need for users to create and manage passwords. A typical solution is based on giving the user a hardware token that generates one-time-passwords, i.e. passwords for single session or transaction usage. Unfortunately, most of these solutions do not satisfy scalability and/or usability requirements, or they are simply insecure. In this paper, we propose a scalable OTP solution using...

5349788 | **Publication Date: 2009-08-01** |

Privacy Preserving Portable Health Record (P^3HR)




Image not currently available

Abstract:
Personal health records (PHRs) offer significant potential to stimulate transformational changes in health care delivery and self-care by patients. There is a gap between today's personal health records (PHRs) and what patients say they want and need from this electronic tool for managing their health information. Current barriers to PHR adoption among patients include cost, concerns that information is not protected or private, inconvenience, design shortcomings, and the inability to share information across organizations. We propose a novel architecture to bridge the gap based on Privacy Preserving Portable Health Record(P3HR), a device that incorporates a smart card into a USB flash drive which provides encrypted flash memory for secure mobile data storage. The salient features of the proposed Privacy Preserving Portable Health Record (P3HR) include: strong multifactor authentication using biometrics, public key infrastructure to verify the credentials of the applicants, SSL based...

Petitioner Samsung Ex-1004, 0289

IPCOM000003426D | **Publication Date: 2000-05-01** |

Internet Security Glossary (RFC2828)



Abstract:
This Glossary provides abbreviations, explanations, and recommendations for use of information system security terminology. This memo provides information for the Internet community.

S741699 | **Publication Date: 2010-07-01** |

Secure bridging in large scale deployment of Ethernet

Image not currently available

Abstract:
Considering the dominance of Ethernet with upcoming 100 Gbps line rate, service providers want to reduce their transport networks to simpler Layer-2 networks. Since existing Ethernet security mechanisms protect links in hop-by-hop basis, they cannot control access for disloyal authorized users in virtual or logical shared media infrastructure LANs. Also they leave data in clear inside intermediate systems, which increase threats when these systems are placed in public places. To address these critical security issues, we propose an authenticated on-demand secure bridging solution that can provide a point-to-point secure channel between Ingress and Egress Bridges across Bridged Ethernet network. To build such secure channel, we use Identity-based authenticated key agreement and signature protocol. Experimental results using our prototype software on a small multi-segment Ethernet network suggest that our solution is feasible, and guarantees secure bridging.

Petitioner Samsung Ex-1004, 0290

IPCOM000002336D | **Publication Date: 1993-09-01** |

DASS - Distributed Authentication Security Service (RFC1507)



Abstract:
The goal of DASS is to provide authentication services in a distributed environment which are both more secure and easier to use than existing mechanisms. This memo defines an Experimental Protocol for the Internet community. It does not specify an Internet standard.

5409813 | **Publication Date: 2010-02-05** |

IEEE Standard for Local and metropolitan area networks--Port-Based Network Access Control

Image not currently available

Abstract:
Port-based network access control allows a network administrator to restrict the use of IEEE 802 LAN service access points (ports) to secure communication between authenticated and authorized devices. This standard specifies a common architecture, functional elements, and protocols that support mutual authentication between the clients of ports attached to the same LAN and that secure communication between the ports, including the media access method independent protocols that are used to discover and establish the security associations used by IEEE 802.1AE MAC Security.

Petitioner Samsung Ex-1004, 0291

4547643 | **Publication Date: 2008-04-01** |

Trusted user authentication scheme combining password with fingerprint for mobile devices



Abstract:
Mobile equipment (ME) playing an important role of bridge between wireless network and mobile user has been facing more and more security threats. Trusted mobile platform (TMP) was proposed by TCG (trusted computing group) as a new mechanism to enhance the security of the resource-constrained ME. In this paper, we embark a new study on constructing a TMP according to ME's feature, and performing mutual authentication in mobile user domain. A smart-phone's processor is used as an example to demonstrate the constructing of TMP, along with which three methods for adding trusted platform module (TPM) in ME are presented respectively. In the framework of TMP, we also propose a user authentication scheme combining password and fingerprint with the USIM (universal subscriber identity module). The proposed scheme is validated through a performance analysis and experimental test. The validation result shows that our approach offers better efficiency and advanced security over the authentication...

5367679 | **Publication Date: 2009-12-22** |

IEEE Standard for Local and metropolitan area networks - Secure Device Identity



Abstract:
A secure device identifier (DevID) is cryptographically bound to a device and supports authentication of the devices identity. Locally significant identities can be securely associated with an initial manufacturer-provisioned DevID and used in provisioning and authentication protocols toallow a network administrator to establish the trustworthiness of a device and select appropriate policies for transmission and reception of data and control protocols to and from the device.

Petitioner Samsung Ex-1004, 0292

6672120 | **Publication Date: 2013-01-01** |

Secure deployment of SmartGrid equipment



Image not currently available

Abstract:
Introducing the SmartGrid goes in hand with the deployment of a large number of devices and with the establishment of a rather complex communication infrastructure. SmartGrid equipment like SmartMeters, other remote sensors, control equipment, or additional sub-stations, all have different security requirements. Common to all of them is that each device needs to be securely identified in the infrastructure and that proper security management needs to be in place. To allow for remote management, security functionality has to be incorporated in the design of a device. Furthermore, unique identities and establishment of cryptographic keys for secure communication requires an individual initial configuration of each device. Currently, this initial configuration is a manual operation executed during deployment, often by copying configuration data from memory devices such as USB tokens or SD cards. This paper introduces a novel and secure approach to support efficient roll-out processes in...

6781089 | **Publication Date: 2010-06-01** |

On new security mechanisms for identity management: Recognizing and meeting telecom operator and enterprise needs



Image not currently available

Abstract:
Initially created by the information technology industry, the identity management (IdM) concept has been increasingly recognized as a foundation for key new services by telecommunication network operators. Indeed, since telecom operators "own" wireless and wireline access, they also "own" a great deal of information about their subscribers. Based on those assets, telecom operators are in a unique position to offer a range of identity-based services — from home networking to straightforward authentication services for enterprise, to a complex blend of services, including financial and medical transactions. Conversely, by federating data from multiple application providers, coupled with single sign-on (SSO), telecom operators can offer unique mash-up services. The technology underpinning the development of such services is centered on security (i.e., the interworking of a range of authentication, key exchange, and encryption mechanisms, along with appropriate policies). This paper...

Petitioner Samsung Ex-1004, 0293

Flexible Authentication Technique for Ubiquitous Wireless Communication using Passport and Visa Tokens



Abstract:
The development of mobile devices (CPU, memory, and storage) and the introduction of mobile networks (Ad-Hoc, Wi-Fi, WiMAX, and 3.5G) have opened new opportunities for next generation of mobile services. It becomes more convenience and desirable for mobile internet users to be connected everywhere. However, ubiquitous mobile access connectivity faces interoperation issues between wireless network providers and wireless network technologies. Although mobile users would like to get as many services as possible while they travel, there is a lack of technology to identify visited users in current foreign network authentication systems. This challenge lies in the fact that a foreign network provider does not initially have the authentication credentials of a mobile user. Existing approaches use roaming agreement to exchange authentication information between home network and foreign network. This paper proposes a roaming agreement-less approach designed based on our ubiquitous mobile access...

Data Protection Techniques, Cryptographic Protocols and PKI Systems in Modern Computer Networks



Abstract:
This tutorial is devoted to the emerging topic in domain of modern e-business systems - a computer network security based on public key infrastructure (PKI) systems. We consider possible vulnerabilities of the TCP/IP computer networks and possible techniques to eliminate them. We signify that only a general and multilayered security infrastructure could cope with possible attacks to the computer network systems. We evaluate security mechanisms on application, transport and network layers of ISO/OSI reference model and give examples of the today most popular security protocols applied in each of the mentioned layers. We recommend secure computer network systems that consist of combined security mechanisms on three different ISO/OSI reference model layers: application layer security based on strong user authentication, digital signature, confidentiality protection, digital certificates and hardware tokens, transport layer security based on establishment of a cryptographic tunnel between...

Petitioner Samsung Ex-1004, 0294

5931373 | **Publication Date: 2011-05-01** |

A New Convergent Identity System Based on EAP-TLS Smart Cards



Image not currently available

Abstract:
This paper presents a new identity system, named SSL-Identity, working with EAP-TLS smart cards. It details an innovative technology based on tiny SSL stacks deployed in billions of such devices embedded in USB dongles or mobile phones, and comments first experimental results. SSL-Identity is convergent because it works in fixed and mobile environment. It claims a strong mutual authentication between user and authentication server. We present the identity lifecycle in which a secure device is manufactured and then linked to one or several user's identities.

1247734 | **Publication Date: 2003-01-01** |

Smart card based security for fieldbus systems




Image not currently available

Abstract:
The provision of security services in fieldbus systems will gain in importance in the coming years. A need for such services is easiest seen in fieldbus systems for building automation as they give ample opportunities for mischievous adversaries to tamper with. Without loss of generality we discuss different ways to integrate security services in fieldbus systems after pointing out possible security deficiencies in three widely used fieldbus systems for building automation. Exemplarily, we show how to integrate security services to the LonWorks system. To do so we introduce a secure smart card and discuss the security services that were implemented, based on some simple but realistic assumptions about a possible security policy.

Petitioner Samsung Ex-1004, 0295

5237773 | **Publication Date: 2007-01-01** |

Index



Abstract:
No abstract.

1435744 | **Publication Date: 2005-06-01** |

Security for Industrial Communication Systems

Image not currently available

Abstract:
Modern industrial communication networks are increasingly based on open protocols and platforms that are also used in the office IT and Internet environment. This reuse facilitates development and deployment of highly connected systems, but also makes the communication system vulnerable to electronic attacks. This paper gives an overview of IT security issues in industrial automation systems which are based on open communication systems. First, security objectives, electronic attack methods, and the available countermeasures for general IT systems are described. General security objectives and best practices are listed. Particularly for the TCP/IP protocol suite, a wide range of cryptography-based secure communication protocols is available. The paper describes their principles and scope of application. Next, we focus on industrial communication systems, which have a number of security-relevant characteristics distinct from the office IT systems. Confidentiality of transmitted data may...

Petitioner Samsung Ex-1004, 0296

6767886 | **Publication Date: 2005-07-01** |

Authentication across heterogeneous networks



Abstract:
In the beyond third-generation (3G) vision, the convergence of different access network technologies is realized and end-user devices are able to roam seamlessly among them. Seamless roaming requires authentication to a network, which may require interaction with an end user that results in the termination of ongoing service sessions and, therefore, inhibits seamless roaming. Furthermore, some access technologies may support a plethora of authentication protocols, making selection of the appropriate method(s) of authentication challenging for an end user. We propose a solution involving single sign-on authentication that allows the end user to roam between different administrative domains and access network technologies (e.g., wireline and wireless). Our solution integrates a number of authentication mechanisms and does not require any end-user interactions while roaming, thus enabling a seamless roaming experience. We describe a prototype implementation of this solution using General...

1588324 | **Publication Date: 2005-01-01** |

FIrDA-SSL: experiments with securing communication in PANs



Abstract:
In personal area networks (PANs), a personal operating space (POS) surrounds the person up to 10 meters in all directions and it contains several types of wireless devices exchanging data between them (intra-PAN communication), or with devices from another POS or as part of broader networks (inter-PAN communication). Security is seen as a "big issue" both for intra and inter-PAN communication. The security mechanisms or protocols involved should also run on user devices within a reasonable amount of time. Clearly one of the first issues to be addressed in PANs is to transfer information securely and we provide a practical approach for this issue. In practice, we want to enable the exchange of "personal" data only to authenticated parties and doing this with standard protocols, client software or commercial products available at the moment. We developed a tool named FirDA-SSL (Footprint Irda SSL transfer) for secure transfer of small amounts of data, like a credit card number, or a...

Petitioner Samsung Ex-1004, 0297

10023171 | **Publication Date: 2010-02-17** |

SSMS - A Secure SMS Messaging Protocol for the M-payment Systems



Abstract:
The GSM network with the greatest worldwide number of users, succumbs to several security vulnerabilities. The short message service (SMS) is one of its superior and well-tried services with a global availability in the GSM networks. The main contribution of this paper is to introduce a new secure application layer protocol, called SSMS, to efficiently embed the desired security attributes in the SMS messages to be used as a secure bearer in the m-payment systems. SSMS efficiently embeds the confidentiality, integrity, authentication, and non-repudiation in the SMS messages. It provides an elliptic curve-based public key solution that uses public keys for the secret key establishment of a symmetric encryption. It also provides the attributes of public verification and forward secrecy. It efficiently makes the SMS messaging suitable for the m-payment applications where the security is the great concern. Comment: 6 Pages, 5 Figures

4493913 | **Publication Date: 2008-02-01** |

Subscriber Authentication in Cellular Networks with Trusted Virtual SIMs



Abstract:
The primary goal of this paper is to design a software replacement for a Subscriber Identity Module (SIM) based on the TCG MPWG Reference Architecture in order to access a mobile cellular network and its offered services. Therefor, we introduce a virtual software SIM (vSIM) with comparable usage and security characteristics like the traditional smartcard-based solution. Additionally, running a virtual SIM as a trusted and protected software on a mobile device allow significant expansion of services by introducing new usage scenarios and business models, cost reduction and more flexibility. Our approach demonstrates the substitutability of a SIM card with an adequate trusted software module supported and protected by a trustworthy operating system. In particular we propose several methods for authentication and enrollment of a subscriber.

Petitioner Samsung Ex-1004, 0298

4625610 | **Publication Date: 2008-07-01** |

SSMS - A secure SMS messaging protocol for the m-payment systems



Abstract:
The GSM network with the greatest worldwide number of users, succumbs to several security vulnerabilities. The short message service (SMS) is one of its superior and well-tried services with a global availability in the GSM networks. The main contribution of this paper is to introduce a new secure application layer protocol, called SSMS, to efficiently embed the desired security attributes in the SMS messages to be used as a secure bearer in the m-payment systems. SSMS efficiently embeds the confidentiality, integrity, authentication, and non-repudiation in the SMS messages. It provides an elliptic curve-based public key solution that uses public keys for the secret key establishment of a symmetric encryption. It also provides the attributes of public verification and forward secrecy. It efficiently makes the SMS messaging suitable for the m-payment applications where the security is the great concern.

5337047 | **Publication Date: 2009-10-01** |

Pervasive service access with SIM-based VPN



Abstract:
Mobile users need to have access to internal resources on their enterprise or home network from remote locations in an efficient but secure way. Currently, such a secured access is realised with Virtual Private Network (VPN) connections. Although operational, the current VPN solutions suffer of severe limitations. Most of the VPN solutions are not sufficiently secured since they are using weak authentication. The more secured ones are quite often expensive and require the usage of security tokens that demand administration from the service provider. On the user's side there is a need for additional care and attention since he/she has to carry an extra device. This paper presents a VPN solution that remedies the mentioned limitations by re-using an existing device, namely the mobile phone and its SIM card as a security token. Another ingenuity of the solution lies on the separation of the authentication phase from the rest of the VPN establishment process making possible the usage of...

Petitioner Samsung Ex-1004, 0299

6583548 | **Publication Date: 2013-07-01** |

Seamless authentication across heterogeneous networks using Generic Bootstrapping systems

Image not currently available

Abstract:
With the increasing demand for mobile data services and increased availability of multimode devices with multiple wireless interfaces, seamless mobility and service continuity across heterogeneous networks has become a differentiating service for Operators to offer users an enhanced mobile experience. In recent years, the Federated Identity Management (IdM) standards and technologies have rapidly evolved to address security, user experience, and privacy needs from an application layer perspective or as seen from the end user. As a result of these Federated IdM activities, a Single Sign-On (SSO) concept has been created in which a user may use a single set of authentication credentials to gain access to multiple independent Application Services. This paper provides an overview of the various layers of security in a communications protocol stack and then presents an approach to achieve seamless mobility across heterogeneous networks based on Federated Identity systems. By leveraging a...

1265853 | **Publication Date: 2003-12-01** |

Efficient authentication and key distribution in wireless IP networks

Image not currently available

Abstract:
Emerging broadband access technologies such as 802.11 are enabling the introduction of wireless IP services to an increasing number of users. Market forecasts suggest that a new class of network providers, commonly referred to as wireless Internet service providers, will deploy public wireless networks based on these new technologies. In order to offer uninterrupted IP service combined with ubiquitous seamless mobility, these multiprovider networks need to be integrated with each other, as well as with wide-area wireless technologies such as third-generation cdma2000 and UMTS. Therefore, efficient authentication and dynamic key exchange protocols that support heterogeneous domains as well as networks with roaming agreements across trust boundaries are key to the success of wide-area wireless IP infrastructures. In this article we first describe a simple network model that accounts fro heterogeneity in network service providers, and put forward the requirements any authentication and...

Petitioner Samsung Ex-1004, 0300

6649425 | **Publication Date: 2013-06-01** |

Seamless authentication and mobility across heterogeneous networks using federated identity systems



Image not currently available

Abstract:
With the increasing demand for mobile data services and increased availability of multimode devices with multiple wireless interfaces, seamless mobility and service continuity across heterogeneous networks has become a differentiating service for Operators to offer users an enhanced mobile experience. In recent years, the Federated Identity Management (IdM) standards and technologies have rapidly evolved to address security, user experience, and privacy needs from an application layer perspective or as seen from the end user. As a result of these Federated IdM activities, a Single Sign-On (SSO) concept has been created in which a user may use a single set of authentication credentials to gain access to multiple independent Application Services. This paper provides an overview of the various layers of security in a communications protocol stack and then presents an approach to achieve seamless mobility across heterogeneous networks based on Federated Identity systems. By leveraging a...

6445261 | **Publication Date: 1997-01-01** |

Scalability and flexibility in authentication services: the KryptoKnight approach




Image not currently available

Abstract:
This paper studies the issues of flexibility and scalability in the context of network security. In particular, it concentrates on authentication and key distribution services suited for a variety of communication paradigms, network environments, and end-devices. We present the design criteria, specification, and step-by-step construction of authentication and key distribution services based on experience in the KryptoKnight project. The central goal of the KryptoKnight project was the construction of basic network security functions in a minimal, flexible (thus, versatile) and scalable manner. Protocol minimality (in terms of resource usage) and flexibility are not merely theoretical goals; they have clear advantages in environments where computational resources are limited and connectivity is restricted. KryptoKnight was aimed at such environments: small and anemic wireless devices, simple network and data-link entities, embedded micro-devices and other special-purpose communication...

Petitioner Samsung Ex-1004, 0301

5237825 | **Publication Date: 2007-01-01** |

PKI Systems



Abstract:
This chapter contains sections titled: Introduction Origins of Cryptography Overview of PKI Systems Components of PKI Systems Procedures of PKI Systems Current and Future Aspects of PKI Systems Conclusions References

6069725 | **Publication Date: 2011-11-01** |

WiMAX subscriber and mobile station authentication challenges


Image not currently available

Abstract:
This article examines the subject of authentication within WiMAX (IEEE 802.16-2009) based wireless metropolitan networks. The two WiMAX authentication mechanisms (PKM versions 1 and 2) are discussed and a number of aspects affecting their authentication capabilities presented. Of particular n4056792ote is the handling of digital certificates and the lack of multiple certificate authority support. This lack essentially prevents the interoperability of WiMAX devices produced by different manufactures. Proposed recommendations are presented that should improve how WiMAX authentication operates and allow for mixed manufacturer device interoperability.

Petitioner Samsung Ex-1004, 0302

1493584 | **Publication Date: 2005-01-01** |


A two-factor mobile authentication scheme for secure financial transactions



Abstract:
Many authentication schemes are based on parties possessing cryptographic keys often held on smart cards or other tamper-proof devices. Modern portable devices (e.g. PDAs, Smartphones) are enriched with advanced functionalities and thus could soon become both the preferred portable computing device (thereby substituting laptop computers) and a personal trusted device. This paper presents a novel two-factor authentication scheme whereby a Bluetooth-enabled handheld device is used to enforce basic password-based authentication thus improving convenience and usability. The main building block is a simple and efficient two-party authentication protocol based on a shared string (including the case of low entropy human memorable passwords) and on well known cryptographic primitives. The discussion relates to the banking sector but our scheme is readily adaptable to other more general contexts.

IPCOM000157212D | **Publication Date: 2007-08-01** |

Internet Security Glossary, Version 2 (RFC4949)



Abstract:
This Glossary provides definitions, abbreviations, and explanations of terminology for information system security. The 334 pages of entries offer recommendations to improve the comprehensibility of written material that is generated in the Internet Standards Process (RFC 2026). The recommendations follow the principles that such writing should (a) use the same term or definition whenever the same concept is mentioned; (b) use terms in their plainest, dictionary sense; (c) use terms that are already well-established in open publications; and (d) avoid terms that either favor a particular vendor or favor a particular technology or mechanism over other, competing techniques that already exist or could be developed. This memo provides information for the Internet community.

Petitioner Samsung Ex-1004, 0303

PE2E SEARCH - Search History (Prior Art)

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	British Equivalents	Time Stamp
L203	2	"11736283".pn.	(US-PGPUB; USPAT; USOCR; FIT (AP, AT, AU, BE, BG, BR, BY, CA, CH, CN, CS, CU, CZ, DD, DK, EA, EE, ES, FI, FR, GB, HR, HU, ID, IE, IL, IS, IT, JP, KR, LT, LU, LV, MA, MC, MD, MY, NL, NO, NZ, PH, PL, PT, RO, RS, RU, SE, SG, SI, SK, SU, TH, TN, TR, TW, UA, VN, WO); FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2024/03/08 10:27 AM
L204	1	"11736283".pn.	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/08 10:27 AM
L205	110769	(H04L9/0861 H04L9/006 H04L9/0662 H04L9/0816 H04L9/0841 H04L9/0844 H04L9/085 H04L9/088 H04L9/0891 H04L9/0894 H04L9/14 H04L9/30 H04L9/3239 H04L9/3247 H04L9/3249 H04L9/3263 H04L63/061 H04L63/0442 H04W12/03 H04W12/041 H04W12/06).cpc.	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/08 11:40 AM
L206	1	"20230379148".PN. AND (euicc uicc circuit integrated)	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/08 12:43 PM
L207	162	(euicc e$1uicc uicc universal near4 integrated near4 (chip card circuit) smartcard smart$1card sim esim e$1sim subscrib$8 near4 identi$8 near4 module).clm. AND (public private pair) near6 key.clm. AND (authenti$8 authori$8 verif$8 valid$8 determin$8 identif$8) near6 (server gatekeeper gateway	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/08 12:48 PM

Petitioner Samsung Ex-1004, 0304

		provider) near8 (shared secret preshared pre$1shared public private pair) near6 key.clm.					
L208	96	(euicc e$1uicc uicc universal near4 integrated near4 (chip card circuit) smartcard smart$1card sim esim e$1sim subscrib$8 near4 identi$8 near4 module).clm. AND (public private pair) near6 key.clm. AND (authenti$8 authori$8 verif$8 valid$8 determin$8 identif$8) near6 (server gatekeeper gateway provider) near8 (shared secret preshared pre$1shared public private pair) near6 key.clm. AND (@pd @prad @rlad @ptad @ad)<"20131120"	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/08 12:51 PM
L209	44	(Artificial Intelligence) Similar to: 18/229,907 with 0 CPC Selections and 0 Text Selections Text: (US-11736283-B2 OR US-20230379148-A1 OR US-20210351923-A1 OR US-11082218-B2 OR US-20160234020-A1 OR US-20150143125-A1 OR US-20200280439-A1 OR US-9319223-B2 OR US-20170373845-A1 OR GB-2593108-A OR US-9742562-B2 OR GB-2588867-A OR US-11606204-B2 OR US-20220141010-A1 OR US-20230208629-A1 OR AU-2014342646-A1 OR US-11258595-B2 OR US-20220103538-A1 OR US-20190097794-A1 OR CA-2969829-C OR AU-2019246774-B2 OR US-10700856-B2 OR	(US-PGPUB; USPAT; USOCR; FIT (AP, AT, AU, BE, BG, BR, BY, CA, CH, CN, CS, CU, CZ, DD, DK, EA, EE, ES, FI, FR, GB, HR, HU, ID, IE, IL, IS, IT, JP, KR, LT, LU, LV, MA, MC, MD, MY, NL, NO, NZ, PH, PL, PT, RO, RS, RU, SE, SG, SI, SK, SU, TH, TN, TR, TW, UA, VN, WO))	OR	ON	ON	2024/03/08 01:09 PM

Petitioner Samsung Ex-1004, 0305

		US-20210184846-A1 OR US-10084768-B2 OR US-20180212946-A1 OR US-9288059-B2 OR EP-3908024-B1 OR US-10187206-B2 OR EP-3908025-A1 OR EP-3908025-B1 OR US-20150180653-A1 OR US-20150296379-A1 OR US-9300473-B2 OR EP-3908023-B1 OR US-20170237561-A1 OR US-9998280-B2 OR US-20160149709-A1 OR US-20160164678-A1 OR US-9961060-B2 OR US-9998281-B2 OR WO-2015065913-A1 OR US-9641327-B2 OR US-20170188231-A1 OR US-20150304113-A1 OR US-9118464-B2 OR CA-2965119-A1 OR US-20180367522-A1 OR US-11233780-B2 OR US-20150121066-A1 OR US-10382422-B2).did.					
L210	39	(Artificial Intelligence) Similar to: 18/229,907 with 0 CPC Selections and 3 Text Selections Text: (US-20230085059-A1 OR US-20150372811-A1 OR AU-2015277000-A1 OR US-11736283-B2 OR US-20230379148-A1 OR AU-2015204470-B2 OR US-11394697-B2 OR AU-2019216646-A1 OR US-20200092269-A1 OR US-20210351923-A1 OR CN-111355749-A OR AU-2019216646-B2 OR US-20150200774-A1 OR CN-106664206-B OR AU-2015277000-B2 OR US-9967090-B2 OR EP-3158680-A1 OR US-20220353252-A1 OR US-10574633-B2 OR WO-2015195978-	(US-PGPUB; USPAT; USOCR; FIT (AP, AT, AU, BE, BG, BR, BY, CA, CH, CN, CS, CU, CZ, DD, DK, EA, EE, ES, FI, FR, GB, HR, HU, ID, IE, IL, IS, IT, JP, KR, LT, LU, LV, MA, MC, MD, MY, NL, NO, NZ, PH, PL, PT, RO, RS, RU, SE, SG, SI, SK, SU, TH, TN, TR, TW, UA, VN, WO))	OR	ON	ON	2024/03/08 01:10 PM

Petitioner Samsung Ex-1004, 0306

		A1 OR AU-2015204470-A1 OR US-20190260578-A1 OR EP-3158680-B1 OR US-20170222801-A1 OR EP-3860041-A1 OR US-10666428-B2 OR US-10313110-B2 OR EP-3860041-B1 OR CN-106664206-A OR WO-2015106248-A1 OR AU-2015277000-C1 OR US-20180205538-A1 OR EP-3095210-A1 OR WO-2019223851-A1 OR GB-2593108-A OR EP-4027576-A1 OR US-11683163-B2 OR US-20210184842-A1 OR US-9647832-B2 OR CN-111277597-B OR CN-111277597-A OR KR-20110090602-A OR WO-2019246206-A1 OR US-11546309-B2 OR KR-20160104603-A OR WO-2020172887-A1 OR US-11082218-B2 OR US-10129020-B2 OR EP-4027576-B1 OR US-20180205539-A1).did.					
L211	1335	(euicc e$1uicc uicc universal near4 integrated near4 (chip card circuit) smartcard smart$1card sim esim e$1sim subscrib$8 near4 identi$8 near4 module) same4 (public private pair) near6 key same4 (authenti$8 authori$8 verif$8 valid$8 determin$8 identif$8) near6 (server gatekeeper gateway provider) near8 (shared secret preshared pre$1shared public private pair) near6 key	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/08 01:15 PM
L212	221	(euicc e$1uicc uicc universal near4 integrated near4 (chip card circuit) smartcard smart$1card sim esim e$1sim subscrib$8 near4 identi$8 near4	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/08 01:17 PM

Petitioner Samsung Ex-1004, 0307

		module) same4 (public private pair) near6 key same4 (authenti$8 authori$8 verif$8 valid$8 determin$8 identif$8) near6 (server gatekeeper gateway provider) near8 (shared secret preshared pre$1shared public private pair) near6 key same4 (first second) near6 (server provider operator) near8 (public private pair) near6 key					
L213	18	("10169587"|"10621352"|"20060021063"|"20100093347"|"20110158411"|"20110167272"|"20190313246"|"20190332774"|"20190356482"|"20200162247"|"20200162269"|"20200226258"|"20200280436"|"20210126801"|"20210184842"|"20210194681"|"20210211279"|"20210218560").PN.	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/08 01:19 PM
L214	105	(euicc e$1uicc uicc universal near4 integrated near4 (chip card circuit) smartcard smart$1card sim esim e$1sim subscrib$8 near4 identi$8 near4 module) same4 (public private pair) near6 key same4 (authenti$8 authori$8 verif$8 valid$8 determin$8 identif$8) near6 (server gatekeeper gateway provider) near8 (shared secret preshared pre$1shared public private pair) near6 key same4 (first second) near6 (server provider operator) near8 (public private pair) near6 key AND (@pd @prad @rlad @ptad @ad)<"20131120"	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/08 01:42 PM
L215	22	(euicc e$1uicc uicc universal near4 integrated near4 (chip card circuit) smartcard	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/08 02:11 PM

Petitioner Samsung Ex-1004, 0308

		smart$1card sim esim e$1sim subscrib$8 near4 identi$8 near4 module) same4 (public private pair) near6 key same4 (authenti$8 authori$8 verif$8 valid$8 determin$8 identif$8) near6 (server gatekeeper gateway provider) near8 (shared secret preshared pre$1shared public private pair) near6 key same4 encrypted near4 profile AND (@pd @prad @rlad @ptad @ad)<"20131120"					
L216	24	(euicc e$1uicc uicc universal near4 integrated near4 (chip card circuit) smartcard smart$1card sim esim e$1sim subscrib$8 near4 identi$8 near4 module) AND (memory stor$8) near8 public WITH private WITH key WITH (shared preshared pre$1shared) AND encrypted near4 profile AND (@pd @prad @rlad @ptad @ad)<"20131120"	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/08 02:35 PM
L217	3350	(euicc e$1uicc uicc universal near4 integrated near4 (chip card circuit) smartcard smart$1card sim esim e$1sim subscrib$8 near4 identi$8 near4 module) AND (generat$8 deriv$8) near8 (shared preshared pre$1shared common symmetric) near6 key AND (@pd @prad @rlad @ptad @ad)<"20131120"	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/08 03:26 PM
L218	716	(euicc e$1uicc uicc universal near4 integrated near4 (chip card circuit) smartcard smart$1card sim esim e$1sim subscrib$8 near4 identi$8 near4 module) AND	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/08 03:26 PM

Petitioner Samsung Ex-1004, 0309

		(generat$8 deriv$8) near8 (shared preshared pre$1shared common symmetric) near6 key near8 (private public pair) near4 key AND (@pd @prad @rlad @ptad @ad)<"20131120"					
L219	182	(euicc e$1uicc uicc universal near4 integrated near4 (chip card circuit) smartcard smart$1card sim esim e$1sim subscrib$8 near4 identi$8 near4 module) same4 (generat$8 deriv$8) near8 (shared preshared pre$1shared common symmetric) near6 key near8 (private public pair) near4 key AND (@pd @prad @rlad @ptad @ad)<"20131120"	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/08 03:28 PM
L220	96	("11736283" "20210351923" "20160234020" "20190097794" "11082218" "20170373845" "10187206" "20200280439" "10700856" "9319223" "20150143125" "9742562" "20150180653" "9300473" "20150296379" "9961060" "20150163056" "20180367522" "20180212946" "10382422" "20160269386" "20190319937" "20200127991" "10084768" "11916893" "9100175" "20220103538" "20190173867" "11539681" "10594679" "11233780" "9351162" "20150180847" "10362012" "20190097793"	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/08 03:51 PM

Petitioner Samsung Ex-1004, 0310

		"20160164678" "20180270059" "9998280" "10177911" "10498530" "9288059" "20170188231" "20150095648" "20150304113" "20150121066" "20210184846" "20200235923" "20180262329" "9118464" "9596078" "9998281" "11283603" "10652017" "20160149709" "20170237561" "20230208629" "20180343117" "20220141010" "20150106616" "9641327" "20200036521" "9276740" "10530575" "10057059" "11606204" "11258595" "10296752" "20230208626" "20210211279" "10380362" "11621832" "20190087594" "20190220611" "20210342462" "20180330109" "11748500" "11080414" "11838417" "10204233" "20210409214" "20180144147" "20230396455" "20220360622" "20210352132" "11399055" "20220376904" "20240031137" "20200280436" "20220278833" "11849048" "11438176" "20220131709" "11777719" "11343084" "20170272945" "11228448" "20200295933" "20200162269" "10172000" "20170272944" "20200052905" "20230336332" "11128478" "10158991" "20220006625" "20230361994"					

Petitioner Samsung Ex-1004, 0311

		"20210185042" "11706025" "20190313246" "20210184842" "11683163" "20190156019" "20220078029" "11888594" "9906528" "20090191857" "10943005" "20160197922" "11626979" "20230231702" "20220239474" "20060182280" "20220295276" "11909870" "20210218560" "11582233" "11671265" "9300641" "11316672" "20200162247" "20230254163" "20130061055" "20210126801" "20220038269" "20090132813" "9843585" "11153080" "20180254897" "20190173673" "11722296" "10250386" "20230061038" "10523432" "20170302447" "11863663" "10621352" "20220209944" "10003461" "11751049" "10169587" "20160270000" "20150071139" "9350550" "11409896" "9419970" "20190332774" "9247424" "20220248221" "20200104554" "20200226258" "20200104553" "9698981" "20200266993" "10592710" "10554636" "20190097982" "11456873" "20160226877" "20220351263" "11784820" "10686603" "20200106618" "20220131700" "20220407712"					

Petitioner Samsung Ex-1004, 0312

		"8533803" "11232272" "20230216947" "20070055873" "11699047" "20200104891" "10733645" "11032075" "20200320598" "11423452" "10797882" "20220100975" "7844834" "20230306210" "20210203488" "11195174" "20220092589" "11588637" "9813245" "11770254" "20130227646" "10389533" "20160226828" "8887257" "20240064144" "20220368679" "20210097535" "20140365777" "20230162183" "9877194" "20220029994" "11882117" "20190305953" "10206106" "20230231715" "11824643" "20210258166" "11861604" "11843698" "20240022421" "11233645" "20200228332" "20200396078" "20200127840" "20180026787" "10057053" "20140006786" "20200265427" "20160065370" "11544707" "10129223" "20130227286" "8850545" "20210258162" "11438311" "20180249332" "10965465" "20150031413" "20150139424" "20140004824" "20200119924" "9088408" "20160227409" "20230142978"				

Petitioner Samsung Ex-1004, 0313

		"20230396441" "11610195" "20210398115" "8881257" "10841091" "20200104841" "20100174907" "20220129390" "10505738" "10685350" "10748138" "20220036349" "20150067813" "10607214" "20120023568" "20200242599" "11182785" "10630653" "7966000" "11341480" "20200104833" "20120072979" "20130080769" "20200260272" "11502844" "20200366490" "10182060" "8971851" "11728994" "10579998" "10887318" "20200252396" "11129019" "20240073018" "20200244462" "11811743" "20180109374" "20230344637" "20230308424" "20200184463" "10187202" "20230274256" "10778437" "20220368531" "20200106752" "20210385652" "10044713" "20220058645" "10887106" "20230051390" "20200235934" "10581611" "20200267129" "11004072" "20110238972" "20200106609" "11552946" "10554411" "20220109568" "20200106614").pn. AND (@pd @prad @rlad @ptad @ad)<"20131120"					

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	British Equivalents	Time Stamp
N182	1678	referen$8 near4 volt$8 near6 (generat$8 calcula$8 comput$8).clm. AND noise.clm.	(US-PGPUB; USPAT)	OR	ON	ON	2023/04/05 11:20 AM
N183	162	(euicc e$1uicc uicc universal near4 integrated near4 (chip card circuit) smartcard smart$1card sim esim e$1sim subscrib$8 near4 identi$8 near4 module).clm. AND (public private pair) near6 key.clm. AND (authenti$8 authori$8 verif$8 valid$8 determin$8 identif$8) near6 (server gatekeeper gateway provider) near8 (shared secret preshared pre$1shared public private pair) near6 key.clm.	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/08 12:50 PM

Petitioner Samsung Ex-1004, 0315

UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
18/229,907	08/03/2023	John A. Nix	63121/0224	7483

1912 7590 03/11/2024

AMSTER, ROTHSTEIN & EBENSTEIN LLP
405 LEXINGTON AVENUE
FLOOR 48
NEW YORK, NY 10174

EXAMINER
CERVETTI, DAVID GARCIA

ART UNIT	PAPER NUMBER
2419	

MAIL DATE	DELIVERY MODE
03/11/2024	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Office Action Summary	Application No. 18/229,907	Applicant(s) Nix, John A.	
	Examiner David García Cervetti	Art Unit 2419	AIA (FITF) Status Yes

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTHS FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

1)☑ Responsive to communication(s) filed on 03 August 2023.

☐ A declaration(s)/affidavit(s) under **37 CFR 1.130(b)** was/were filed on _____.

2a)☐ This action is **FINAL.** 2b) ☑ This action is non-final.

3)☐ An election was made by the applicant in response to a restriction requirement set forth during the interview on _____; the restriction requirement and election have been incorporated into this action.

4)☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims*

5) ☑ Claim(s) 1-22 is/are pending in the application.

5a) Of the above claim(s) _____ is/are withdrawn from consideration.

6) ☐ Claim(s) _____ is/are allowed.

7) ☑ Claim(s) 1-22 is/are rejected.

8) ☐ Claim(s) _____ is/are objected to.

9) ☐ Claim(s) _____ are subject to restriction and/or election requirement

* If any claims have been determined allowable, you may be eligible to benefit from the **Patent Prosecution Highway** program at a participating intellectual property office for the corresponding application. For more information, please see http://www.uspto.gov/patents/init_events/pph/index.jsp or send an inquiry to **PPHfeedback@uspto.gov.**

Application Papers

10)☐ The specification is objected to by the Examiner.

11)☑ The drawing(s) filed on 03 August 2023 is/are: a)☑ accepted or b)☐ objected to by the Examiner.

Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).

Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).

Priority under 35 U.S.C. § 119

12)☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).

Certified copies:

a)☐ All b)☐ Some** c)☐ None of the:

1.☐ Certified copies of the priority documents have been received.

2.☐ Certified copies of the priority documents have been received in Application No. _____.

3.☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

** See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

1) ☑ Notice of References Cited (PTO-892)

2) ☑ Information Disclosure Statement(s) (PTO/SB/08a and/or PTO/SB/08b) Paper No(s)/Mail Date 12/5/23.

3) ☐ Interview Summary (PTO-413) Paper No(s)/Mail Date _____.

4) ☐ Other: _____.

Petitioner Samsung Ex-1004, 0317

DETAILED ACTION

1. Claims 1-22 are pending and have been examined.

Notice of Pre-AIA or AIA Status

2. The present application, filed on or after March 16, 2013, is being examined under the first inventor to file provisions of the AIA.

Claim Rejections - 35 USC § 112

3. The following is a quotation of 35 U.S.C. 112(b):
(b) CONCLUSION.—The specification shall conclude with one or more claims particularly pointing out and distinctly claiming the subject matter which the inventor or a joint inventor regards as the invention.

4. The following is a quotation of 35 U.S.C. 112 (pre-AIA), second paragraph:
The specification shall conclude with one or more claims particularly pointing out and distinctly claiming the subject matter which the applicant regards as his invention.

5. Claims 1-22 are rejected under 35 U.S.C. 112(b) or 35 U.S.C. 112 (pre-AIA), second paragraph, as being indefinite for failing to particularly point out and distinctly claim the subject matter which the inventor or a joint inventor (or for applications subject to pre-AIA 35 U.S.C. 112, the applicant), regards as the invention.

6. Claim 1 recites the limitation "the steps". There is insufficient antecedent basis for this limitation in the claim.

7. In claim 1, it is indefinite what is intended by “a corresponding mobile device private key”, is this key “corresponding” to the device or to the mobile device public key.

8. This is not intended to be a complete list of such indefiniteness issues.

Double Patenting

9. Claims 1-22 are provisionally rejected under the judicially created doctrine of obviousness-type double patenting as being unpatentable over claims of Patent No. 9319223, 9742562, 10187206, 10498530, 10700856, 11258595, and 11082218. Although the conflicting claims are not identical, they are not patentably distinct from each other because

- “A mobile device comprising: (a) an embedded Universal Integrated Circuit Card (eUICC); (b) at least one processor; and (c) a memory operatively connected to the at least one processor, the memory including processor executable code that, when executed by the at least one processor, causes the at least one processor to perform the steps of: (1) recording, in the memory of the mobile device, (i) a mobile device public key and a mobile device private key, (ii) a pre-shared secret key, (iii) cryptographic parameters, and (iv) a mobile device identity; (2) generating a message authentication code (MAC) using the pre-shared secret key for authentication with a first set of servers; (3) receiving server encrypted data from the first set of servers, wherein the server encrypted data includes a set of the cryptographic parameters; (4) decrypting the server encrypted data using the pre-shared secret key; (5) storing a network public key, wherein the network public key is associated with (i) a second set of servers and (ii) a network private key; (6) generating a mutually derived shared key using Elliptical Curve Diffie Hellman, wherein the mutually derived shared key is derived

by the mobile device based on at least: (i) the mobile device private key; (ii) the network public key; and (iii) the set of the cryptographic parameters, wherein the mutually derived shared key is derived by the second set of servers based on at least: (A) the mobile device public key associated with the mobile device private key; (B) the network private key associated with the network public key; and (C) the set of the cryptographic parameters; (7) receiving from the second set of servers an encrypted profile for the eUICC; and(8) decrypting the encrypted profile using the mutually derived shared key in order to store network access credentials" (claim 1, instant application) is analogous to

- "A method for a module using an embedded universal integrated circuit card (eUICC) to derive a first shared secret key and a second shared secret key, the method comprising the module: storing a network public key and a module identity in the eUICC, wherein the module uses the network public key to authenticate an eUICC subscription manager; receiving a token for a key derivation function from the authenticated eUICC subscription manager; deriving a module private key and a module public key, wherein the module sends the derived module public key and the module identity to the eUICC subscription manager; deriving the first shared secret key using the key derivation function and a set of cryptographic parameters, wherein the key derivation function uses as input at least (i) the derived module private key, (ii) the set of cryptographic parameters, and (iii) the received token; deriving the second shared secret key using (i) a shared secret algorithm and (ii) the derived first shared secret key as a random number for the shared secret algorithm, wherein the shared secret algorithm uses a secure hash algorithm; and receiving an eUICC profile, wherein the eVICC uses the derived second shared secret key to decrypt the eUICC profile" (claim 1, patent 9319223) and analogous to
- "A method for a module using an embedded integrated circuit card (eUICC) to support authentication, the method comprising the module: reading a module identity from a protected memory and sending the module identity to an eUICC subscription manager; reading an eUICC subscription manager public key from the protected memory; authenticating the eUICC subscription manager using the eUICC subscription manager public key; receiving a first profile for the eUICC, wherein the first profile includes a first network module identity and a first key K, and wherein the module sends the module identity to the eUICC subscription manager before receiving the first profile; using the eUICC, the first network module identity, and the first key K to authenticate with a first wireless network; receiving from an eUICC subscription manager a server public key after authenticating with the first key K; deriving a shared secret key using (i) the received server public key, (ii) an eUICC private key, and (iii) a shared secret algorithm; receiving a second profile for the eUICC, wherein the module decrypts the second profile using the derived shared secret key, wherein the decrypted second profile includes a second network module identity and a second key K; and authenticating with a second wireless network using the second network module identity and the second key K" (claim 1, patent 9742562), and analogous to
- "A method for securely distributing a profile from a subscription manager system to a module comprising the steps of: (a) recording, in memory operatively connected to the subscription manager system, a digital signature algorithm comprising an elliptic curve digital signature algorithm; (b) recording, by the memory operatively connected to the subscription manager system, a server private key and a corresponding server public key, wherein the server public key and the server private key use elliptic curve cryptography; (c) recording, by the memory operatively connected to the subscription manager system, a symmetric ciphering algorithm, wherein the symmetric ciphering algorithm comprises an Advanced Encryption Standard with a 128 bit key length; (d) receiving, by the subscription manager system, a certificate associated with the module from a module provider system associated with a module provider, wherein the certificate includes a module public key; (e) receiving, by the subscription manager system, a challenge from the module; (f) generating, by the subscription manager system, a network private key and a corresponding network public key, using a key pair generation algorithm; (g) sending the generated network public key to the module; and (h) sending a digital signature and the challenge to the module, wherein the digital signature is generated using the server private key and the digital signature algorithm; (i) generating, by the subscription manager system, a mutually derived shared key using Elliptic Curve Diffie-Hellman based on at least: (1) the module public key, and (2) the network private key; wherein the mutually derived shared key is derived by the module based on at least: (i) a module private key associated with the module public key, and (ii) the network public key; (j) encrypting, by the subscription manager system, the profile using: (1) the symmetric ciphering algorithm, and (2) the mutually derived shared key; (k) sending, from the subscription manager system to the module, the encrypted profile, wherein the profile includes network access credentials for a wireless network" (claim 1, patent 10187206) ", and analogous to
- "A module for securely communicating over a wireless network comprises: (1) one or more processors; and (2) a first non-transitory computer-readable memory operatively connected to the one or more processors, the first non-transitory computer-readable memory having stored thereon machine-readable instructions that, when executed by the one or more processors cause the one or more processors to perform a method comprising steps of: (a) recording in the first non-transitory computer-readable memory, at least the following: (i) a first set of parameters for a secure hash algorithm; (ii) a second set of parameters for an elliptic curve algorithm; and (iii) a first public key which corresponds to a first private key; (b) deriving a module private key and a corresponding module public key using the second set of parameters; (c) generating a first shared secret key using a first elliptic curve Diffie-Hellman key exchange, and based at least in part, on the first public key; (d) sending, to a first computing device which is connected to the wireless network, a first message including the derived module public key, wherein at least a portion of the first message is encrypted using a third set of parameters that is based on a symmetric ciphering algorithm and the derived first shared secret key; (e) receiving, from the first computing device, a second message comprising encrypted data, which is encrypted, by the first computing device, using the symmetric ciphering algorithm and a derived second shared secret key, wherein the second shared secret key is derived by the first computing device using a

second elliptic curve Diffie-Hellman key exchange based at least, in part, on the derived module public key; and (f) decrypting the encrypted data using the third set of parameters and the derived second shared secret key" (claim 1, patent 10498530) ", and analogous to

- "A subscription manager system for distributing a profile to a module comprising: (1) one or more processors; and (2) first non-transitory computer-readable media operatively connected to the one or more processors and having stored thereon machine-readable instructions that, when executed by the one or more processors, cause the one or more processors to perform a method comprising steps of: (a) recording, in second non-transitory computer-readable media, a digital signature algorithm comprising an elliptic curve digital signature algorithm; (b) recording, in the second non-transitory computer-readable media, a module identity, a server private key, and a server certificate for a corresponding server public key, wherein the server public key and the server private key use the elliptic curve digital signature algorithm; (c) recording, in the second non-transitory computer-readable media, a symmetric ciphering algorithm, wherein the symmetric ciphering algorithm comprises an Advanced Encryption Standard with a 128 bit key length; (d) receiving a certificate associated with the module from a module provider system associated with a module provider, wherein the certificate includes the module identity, a module public key, and cryptographic parameters; (e) verifying the certificate associated with the module using a certificate authority; (f) sending, to the module, the server certificate, wherein the module verifies the server certificate using a certificate authority public key stored by the module; (g) receiving a challenge from the module; (h) generating a network private key and a corresponding network public key, using a key pair generation algorithm and the cryptographic parameters; (i) sending the generated network public key to the module; (j) sending a digital signature and the challenge to the module, wherein the digital signature is generated using the server private key, the challenge, and the digital signature algorithm, wherein the module verifies the digital signature using at least the server public key; (k) generating a mutually derived shared key using Elliptic Curve Diffie-Hellman based on at least: i. the module public key; ii. the network private key; and iii. the cryptographic parameters, wherein the mutually derived shared key is derived by the module based on at least: iv. a module private key associated with the module public key; v. the network public key; and vi. the cryptographic parameters; (l) encrypting the profile using: i. the symmetric ciphering algorithm, and ii. the mutually derived shared key; and (m) sending the encrypted profile, wherein the encrypted profile includes network access credentials for a wireless network" (claim 1, patent 10700856), and analogous to
- "A module with an embedded Universal Integrated Circuit Card (eUICC) comprising: (a) at least one processor; and (b) a memory operatively connected to the at least one processor, the memory including processor executable code that, when executed by the at least one processor, performs the steps of: (1) recording, in the memory of the module, (i) a module public key and a corresponding module private key, (ii) a pre-shared secret key, (iii) a set of cryptographic parameters, and (iv) a module identity, (2) generating, by the module, module encrypted data associated with a first set of servers using the pre-shared secret key which is also separately accessible by the first set of servers, wherein the module encrypted data includes at least a portion of the set of cryptographic parameters; (3) storing, by the module in the memory, a network public key, wherein the network public key is associated with (i) a second set of servers and (ii) a network private key; (4) generating, by the module in the memory, a mutually derived shared key using Elliptical Curve Diffie Hellman, wherein the mutually derived shared key is derived by the module based on at least: (i) the module private key; and (ii) the network public key, wherein the mutually derived shared key can be derived by the second set of servers based on at least: (A) the module public key associated with the module private key; and (B) the network private key associated with the network public key; (5) receiving from the second set of servers an encrypted profile for the eUICC; and (6) decrypting the encrypted profile with the mutually derived shared key in order to store network access credentials" (claim 1, patent 11082218).

10. This is a provisional obviousness-type double patenting rejection because the conflicting claims of the instant application have not in fact been patented.

11. The claims of the conflicting patents and/or applications contain every element of claims 1-22 of the instant application and thus anticipate the claims of the instant application. Claims 1-22 of the instant application therefore are not patently distinct from the copending application claims and as such are unpatentable for obvious-type double patenting. A later patent/application claim is not patentably distinct from an earlier claim if the later claim is anticipated by the earlier claim.

12. "A later patent claim is not patentably distinct from an earlier patent claim if the later claim is obvious over, or anticipated by, the earlier claim. In re Longi, 759 F.2d at 896, 225 USPQ at 651 (affirming a holding of obviousness-type double patenting because the claims at issue were obvious over claims in four prior art patents); In re Berg, 140 F.3d at 1437, 46 USPQ2d at 1233 (Fed. Cir. 1998) (affirming a holding of obviousness-type double patenting where a patent application claim to a genus is anticipated by a patent claim to a species with that genus). "ELI LILLY AND COMPANY v BARR

LABORATORIES, INC., United States Court of Appeals for the Federal Circuit, ON PETITION FOR REHEARING EN BANC (DECIDED: May 30, 2001).
13. "Claim 12 and Claim 13 are generic to the species of invention covered by claim 3 of the patent. Thus, the generic invention is "anticipated" by the species of the patented invention. Cf., Titanium Metals Corp. v. Banner, 778 F.2d 775, 227 USPQ 773 (Fed. Cir. 1985) (holding that an earlier species disclosure in the prior art defeats any generic claim) 4. This court's predecessor has held that, without a terminal disclaimer, the species claims preclude issuance of the generic claim. In re Van Ornum, 686 F.2d 937, 944, 214 USPQ 761, 767 (CCPA 1982); Schneller, 397 F.2d at 354. Accordingly, absent a terminal disclaimer, claims 12 and 13 were properly rejected under the doctrine of obviousness-type double patenting." (In re Goodman (CA FC) 29 USPQ2d 2010 (12/3/1993).

14. A rejection based on double patenting of the "same invention" type finds its support in the language of 35 U.S.C. 101 which states that "whoever invents or discovers any new and useful process... may obtain a patent therefor..." (Emphasis added). Thus, the term "same invention," in this context, means an invention drawn to identical subject matter. See *Miller v. Eagle Mfg. Co.*, 151 U.S. 186 (1894); *In re Vogel*, 422 F.2d 438, 164 USPQ 619 (CCPA 1970); *In re Ockert*, 245 F.2d 467, 114 USPQ 330 (CCPA 1957).

15. A statutory type (35 U.S.C. 101) double patenting rejection can be overcome by canceling or amending the claims that are directed to the same invention so they are no longer coextensive in scope. The filing of a terminal disclaimer cannot overcome a double patenting rejection based upon 35 U.S.C. 101.

16. Claims 1-22 are rejected under 35 U.S.C. 101 as claiming the same invention as that of claims 1-22 of prior U.S. Patent No. 11736283. This is a statutory double patenting rejection.

- "A mobile device comprising: (a) an embedded Universal Integrated Circuit Card (eUICC); (b) at least one processor; and (c) a memory operatively connected to the at least one processor, the memory including processor executable code that, when executed by the at least one processor, causes the at least one processor to perform the steps of: (1) recording, in the memory of the mobile device, (i) a mobile device public key and a mobile device private key, (ii) a pre-shared secret key, (iii) cryptographic parameters, and (iv) a mobile device identity; (2) generating a message authentication code (MAC) using the pre-shared secret key for authentication with a first set of servers; (3) receiving server encrypted data from the first set of servers, wherein the server encrypted data includes a set of the cryptographic parameters; (4) decrypting the server encrypted data using the pre-shared secret key; (5) storing a network public key, wherein the network public key is associated with (i) a second set of servers and (ii) a network private key; (6) generating a mutually derived shared key using Elliptical Curve Diffie Hellman, wherein the mutually derived shared key is derived by the mobile device based on at least: (i) the mobile device private key; (ii) the network public key; and (iii) the set of the cryptographic parameters, wherein the mutually derived shared key is derived by the second set of servers based on at least: (A) the mobile device public key associated with the mobile device private key; (B) the network private key associated with the network public key; and (C) the set of the cryptographic parameters; (7) receiving from the second set of servers an encrypted profile for the eUICC; and(8) decrypting the encrypted profile using the mutually derived shared key in order to store network access credentials" (claim 1, instant application) is the same as
- "A mobile device comprising: (a) an embedded Universal Integrated Circuit Card (eUICC); (b) at least one processor; and (c) a memory operatively connected to the at least one processor, the memory including processor executable code that, when executed by the at least one processor, causes the at least one processor to perform steps of: (1) recording, in the memory of the mobile device, (i) a mobile device public key and a mobile device private key, (ii) a pre-shared secret key, (iii) cryptographic parameters, and (iv) a mobile device identity; (2) generating a message authentication code (MAC) using the pre-shared secret key for authentication with a first set of servers; (3) receiving server encrypted data from the first set of servers,

wherein the server encrypted data includes a set of the cryptographic parameters; (4) decrypting the server encrypted data using the pre-shared secret key; (5) storing a network public key, wherein the network public key is associated with (i) a second set of servers and (ii) a network private key; (6) generating a mutually derived shared key using Elliptical Curve Diffie Hellman, wherein the mutually derived shared key is derived by the mobile device based on at least: (i) the mobile device private key; (ii) the network public key; and (iii) the set of the cryptographic parameters, wherein the mutually derived shared key is derived by the second set of servers based on at least: (A) the mobile device public key associated with the mobile device private key; (B) the network private key associated with the network public key; and (C) the set of the cryptographic parameters; (7) receiving from the second set of servers an encrypted profile for the eUICC; and (8) decrypting the encrypted profile using the mutually derived shared key in order to store network access credentials" (claim 1, 11736283).

Conclusion

17. Any inquiry concerning this communication or earlier communications from the examiner should be directed to David Garcia Cervetti whose telephone number is (571)272-5861. The examiner can normally be reached Monday-Friday 8AM-5PM.

18. Examiner interviews are available via telephone, in-person, and video conferencing using a USPTO supplied web-based collaboration tool. To schedule an interview, applicant is encouraged to use the USPTO Automated Interview Request (AIR) at http://www.uspto.gov/interviewpractice.

19. If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, HADI ARMOUCHE can be reached on (571)270-3618. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

20. Information regarding the status of published or unpublished applications may be obtained from Patent Center. Unpublished application information in Patent Center is available to registered users. To file and manage patent submissions in Patent Center, visit: https://patentcenter.uspto.gov. Visit https://www.uspto.gov/patents/apply/patent-center for more information about Patent Center and https://www.uspto.gov/patents/docx for information about filing in DOCX format. For additional questions, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

/David Garcia Cervetti/
Primary Examiner, Art Unit 2419

UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
18/229,907	08/03/2023	John A. Nix	63121/0224	7483

1912 7590 03/19/2024

AMSTER, ROTHSTEIN & EBENSTEIN LLP
405 LEXINGTON AVENUE
FLOOR 48
NEW YORK, NY 10174

EXAMINER
CERVETTI, DAVID GARCIA

ART UNIT	PAPER NUMBER
2419	

MAIL DATE	DELIVERY MODE
03/19/2024	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Petitioner Samsung Ex-1004, 0323

United States Patent and Trademark Office

Office of the Commissioner for Patents

Dear Applicant,

You recently received an Office action from your examiner. Review of your patent application is under way! You can continue to advertise or mark any products covered by your application for your invention as "Patent Pending" for as long as this application is pending. This letter provides information about how to continue through the patent application process and the help available to you on your journey.

Where are you in the patent application process? Your patent application is now in step 3, Application Prosecution (www.uspto.gov/UtilityPatentGuide.) Though the Office action includes a "rejection," that does not mean that you don't have a good idea you can patent. It means your examiner believes your application is not yet ready for allowance.

Ready to respond? Responding to the Office action is your opportunity to address the issues raised by your examiner. Responses must be timely, complete, and in writing. In your response, you may want to consider amending your application (www.uspto.gov/patents/maintain/responding-office-actions).

We provide Pro Se Assistance, support specifically geared for independent inventors without an agent or attorney. Visit www.uspto.gov/ProSePatents for a consolidated list of resources, including a sample amendment format. Full description of amendment formatting can be found at www.uspto.gov/web/offices/pac/mpep/s714.html. Call us at 866-767-3848, or email proseassistancecenter@uspto.gov.

Have questions about the Office action? Contact your examiner! A conversation with your examiner (called an "interview") may help clarify and resolve any issues and possibly identify what you can patent. While an interview does not stop the clock for your official response or substitute for a response, there is no fee for an interview. To schedule a call or video, you can:

1. use the USPTO's Automated Interview Request (AIR) form (www.uspto.gov/patents/uspto-automated-interview-request-air-form);
2. file the Applicant Initiated Interview Request form (PTOL-413A) (www.uspto.gov/sites/default/files/documents/PTOL413A.pdf); or
3. contact your examiner directly via telephone (contact information is provided at the end of your Office action).

Need help near you? We have regional offices across the country (www.uspto.gov/locations), as well as Patent and Trademark Resource Centers in libraries in nearly every state (www.uspto.gov/ptrc), with specialists standing by to help you at no cost.

Become a *registered* electronic filer (registered eFiler). As a registered eFiler, you can electronically view your submission, track progress of your application, and respond to USPTO correspondence. (www.uspto.gov/NewPatentFilers)

Contact us

- General information: USPTO Contact Center — 800-786-9199 • TTY/TDD 800-877-8339 • www.uspto.gov/help
- Patent Center: Patent Electronic Business Center www.uspto.gov/EBC
- Inventors Assistance Center www.uspto.gov/inventorassistance

Want to learn more?

- Hear about resources for startups, inventors, and entrepreneurs, as well as our initiatives engaging women, the military community, and others. These programs offer helpful tips and tricks on identifying and managing your IP, finding options for funding, and expanding your network to support your business.
  - www.uspto.gov/startups
  - www.uspto.gov/inventors
  - www.uspto.gov/initiatives
- Access our free services all in one spot. Find all of our contact centers, nationwide services, events, education and training. (www.uspto.gov/FreeServices)
- Connect with us on Instagram, LinkedIn, Twitter, Facebook, and YouTube.
- Hear about the great things we are doing by subscribing at www.uspto.gov/subscribe.

Best,

Vaishali Udupa
Commissioner for Patents
United States Patent and Trademark Office

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant:	Network-1 Technologies, Inc.	Confirmation No.: 7483
Title:	Key Derivation for a Module Using an Embedded Universal Integrated Circuit Card	
Appl. No.:	18/229,907	
Filing Date:	August 3, 2023	
Examiner:	Cervetti, David Garcia	
Art Unit:	2419	
Docket No.:	63121/0224	
Customer No.:	01912	

RESPONSE TO NON-FINAL OFFICE ACTION DATED MARCH 11, 2024

VIA EFS

Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

Sir:

This is a response to the Office Action dated March 11, 2024. A response to this Office Action is due on June 11, 2024. Accordingly, the present Amendment is being timely filed.

Please amend the above-identified application as follows:

Amendments to the Claims begins on page **2** of this paper.

Remarks begin on page **5** of this paper.

Petitioner Samsung Ex-1004, 0325

IN THE CLAIMS

Please amend the claims as follows:

1-22 (Cancelled)

23. (New) A method for a mobile device with an embedded universal integrated circuit card (eUICC) to securely communicate with a wireless network, the method performed by the mobile device, the method comprising:

a) storing, in the eUICC, a first module private key, a corresponding first module public key, and a network public key;

b) receiving, from a first server associated with the wireless network, an encrypted profile for the eUICC comprising cryptographic parameters, a module identity, and a key K;

c) generating a shared secret key using a first elliptic curve Diffie-Hellman (ECDH) key exchange with the first module private key and the network public key;

d) decrypting, with the shared secret key, at least a portion of the encrypted profile for the eUICC;

e) generating, by the eUICC, a second module public key and a corresponding second module private key;

f) sending, to a second server associated with the wireless network, the second module public key;

g) generating a symmetric key using a second ECDH key exchange with the second module private key and the cryptographic parameters;

h) generating, with the symmetric key, module encrypted data, the module encrypted data comprising the module identity; and

i) sending, to the servers, the module encrypted data.

24. (New) The method of claim 23, wherein the module identity comprises an international mobile subscriber identity (IMSI).

Petitioner Samsung Ex-1004, 0326

25. (New) The method of claim 23, wherein the module identity comprises a permanent identifier for the mobile device.

26. (New) The method of claim 23, wherein the cryptographic parameters comprise an identifier for a set of cryptographic parameters.

27. (New) The method of claim 23, further comprising in step c) deriving the shared secret key using an American National Standards Institute (ANSI) standard X-9.63 key derivation function.

28. (New) The method of claim 23, further comprising in step g) deriving the symmetric key using an ANSI standard X-9.63 key derivation function.

29. (New) The method of claim 23, wherein the first server mutually derives the shared secret key using the first ECDH key exchange with the first module public key and a network private key corresponding to the network public key.

30. (New) The method of claim 23, further comprising in step e), generating, by the eUICC, the second module public key and the second module private key using a random number generator and input from a sensor.

31. (New) The method of claim 23, further comprising in step h) generating, with the symmetric key and an Advanced Encryption Standard (AES), the module encrypted data.

32. (New) The method of claim 23, wherein steps g) and h) occur before step f).

33. (New) The method of claim 23, wherein the network public key is associated with an eUICC subscription manager.

Petitioner Samsung Ex-1004, 0327

34. (New) The method of claim 33, wherein (i) the eUICC subscription manager comprises the first server.

35. (New) The method of claim 23, further comprising: j) receiving, from the wireless network, a random number (RAND) and generating a response (RES) using the RAND and the key K.

36. (New) The method of claim 23, further comprising before step b), authenticating the first server by (i) receiving a server digital signature and (ii) verifying the server digital signature with a server public key.

37. (New) The method of claim 23, further comprising (i) in step a), storing a server name for the first server and a port number in a nonvolatile memory of the eUICC, and (ii) before step b) sending the first module public key to the first server.

38. (New) The method of claim 23, wherein the first server, the second server, and the wireless network are associated with a mobile network operator.

39. (New) The method of claim 23, wherein the eUICC comprises a processor, firmware, and protected memory.

40. (New) The method of claim 23, wherein the cryptographic parameters include a base point G for an elliptic curve.

41. (New) The method of claim 23, wherein the mobile device comprises a wireless device with a radio for communicating with a plurality of base stations for the wireless network.

42. (New) The method of claim 23, wherein the eUICC comprises a package soldered to a circuit board of the mobile device.

Petitioner Samsung Ex-1004, 0328

REMARKS

This is a response to the Office Action dated March 11, 2024. A response to this Office Action is due on June 11, 2024. Claims 1-22 were pending in the Office Action. Applicant has canceled claims 1-22 herein without prejudice or disclaimer and has added new claims 23-42 such that claims 23-42 are currently pending. Claim 23 is in independent form. No new matter has been added by the present Amendment.

In view of the below remarks, Applicant respectfully asserts that claims 23-42 are in condition for allowance.

In the event that the Examiner disagrees, Applicant respectfully requests that the Examiner contact Applicant's undersigned attorney by telephone prior to issuing another Office Action.

I. CLAIM REJECTIONS UNDER 35 U.S.C. § 112

Claims 1-22 are rejected under 35 U.S.C. 112(b) as allegedly being indefinite for failing to particularly point out and distinctly claim the subject matter which the inventor or a joint inventor regards as the invention. Office Action, pg. 2

While Applicant does not necessarily agree with this rejection, as noted above, claims 1-22 have been canceled without prejudice or disclaimer such that this rejection is believed to be moot.

Accordingly, Applicant respectfully requests withdrawal of the rejection under 35 U.S.C. § 112(b).

New claims 23-42 are believed to particularly point out and distinctly claim the subject matter that Applicant regards as the invention.

II. PROVISIONAL DOUBLE PATENTING

Claims 1-22 are provisionally rejected under the judicially created doctrine of obviousness-type double patenting as allegedly being unpatentable over the claims of U.S. Patent Nos. 9,319,223; 9,742,562; 10,187,206; 10,498,530; 10,700,856; 11,258,595 and 11,082218. Office Action, pgs. 2-5.

Petitioner Samsung Ex-1004, 0329

While Applicant does not necessarily agree with this rejection, as noted above, claims 1-22 have been canceled without prejudice or disclaimer such that the rejection of these claims is believed to be moot.

Accordingly, Applicant respectfully requests withdrawal of the provisional double patenting rejection.

Applicant respectfully submits that new claims 23-42 are patentably distinct from the claims of the above patents.

III. CLAIM REJECTIONS UNDER 35 U.S.C. § 101

Claims 1-22 are rejected under 35 U.S.C. 101 as allegedly claiming the same invention as that of claims 1-22 of prior U.S. Patent No. 11,736,283. Office Action, pg. 5-6.

While Applicant does not necessarily agree with this rejection, as noted above, claims 1-22 have been canceled without prejudice or disclaimer such that the rejection of these claims is believed to be moot.

Applicant respectfully requests withdrawal of the rejection under 35 U.S.C. § 101.

Applicant respectfully submits that new claims 23-42 are patentably distinct from U.S. Patent No. 11,736,283.

Reference to Related Patents and Co-Pending Applications

The below chart provides information regarding related issued patents and co-pending applications filed by the present Applicant:

Serial No.	Attorney Docket No.	Filing Date	Status
18/229,907	**63121/0224**	**2023-08-03**	**(Present Application) Pending - Case Docketed to Examiner**
18/111,669	63121/0222	2023-02-20	Non-Final OA mailed 2023-10-02
17/647,812	63121/0213	2022-01-13	USP 11,606,204
17/547,990	63121/0212	2021-12-10	USP 11,736,283
17/304,922	63121/0209	2021-06-28	USP 11,736,283
17/249,242	63121/0202	2021-02-24	Response to Non-Final OA filed 2023-11-13
16/879,325	63121/0198	2020-05-20	USP 11,082,218
16/843,107	63121/0197	2020-04-08	USP 11,283,603

Petitioner Samsung Ex-1004, 0330

16/721,153	63121/0195	2019-12-19	USP 11,539,681
16/593,561	63121/0190	2019-10-04	USP 11,258,595
16/453,682	63121/0184	2019-06-26	USP 11,233,780
16/271,455	63121/0181	2019-02-08	USP 10,594,679
16/271,428	63121/0180	2019-02-08	USP 10,523,432
16/201,401	63121/0179	2018-11-27	USP 10,700,856
16/200,118	63121/0178	2018-11-26	USP 10,498,530
16/110,804	63121/0168	2018-08-23	USP 10,382,422
16/036,506	63121/0167	2018-07-16	USP 10,530,575
15/983,957	63121/0163	2018-05-18	USP 10,177,911
15/973,012	63121/0162	2018-05-07	USP 10,250,386
15/972,914	63121/0161	2018-05-07	USP 10,652,017
15/928,848	63121/0160	2018-03-22	USP 10,084,768
15/010,905	63121/0157	2016-01-29	USP 9,641,327
15/680,758	63121/0147	2017-08-18	USP 10,187,206
15/162,292	63121/0146	2016-05-23	USP 10,362,012
14/751,119	63121/0145	2015-06-25	USP 9,961,060
15/457,700	63121/0144	2017-03-13	USP 9,998,281
15/583,968	63121/0143	2017-05-01	USP 10,057,059
15/043,293	63121/0142	2016-02-12	USP 9,998,280
15/642,088	63121/0141	2017-07-05	USP 10,003,461
15/130,146	63121/0140	2016-04-15	USP 9,742,562
15/162,302	63121/0139	2016-05-23	USP 9,698,981
14/789,255	63121/0138	2015-07-01	USP 9,596,078
14/139,419	63121/0137	2013-12-23	USP 9,351,162
14/136,711	63121/0136	2013-12-20	USP 9,300,473
14/099,329	63121/0135	2013-12-06	USP 9,100,175
14/084,141	63121/0134	2013-11-19	USP 9,319,223
14/064,618	63121/0133	2013-10-28	USP 9,118,464
14/055,606	63121/0132	2013-10-16	USP 9,276,740
14/039,401	63121/0131	2013-09-27	USP 9,288,059
14/023,181	63121/0130	2013-09-10	USP 9,350,550
AU 2019246774	63121-0199	2019-10-08	AU2019246774A1 Issued 2021-09-23
GB 1608573	63121-0151	2014-10-27	Published on 2016-08-03
GB 2100530	63121-0201	2014-10-27	Published on 2021-05-12

Petitioner Samsung Ex-1004, 0331

CA 2,965,119	63121-0152	2014-10-27	Published on 2015-05-07
HK 17101082.8	63121-0153	2014-10-27	Published on 2017-10-20
EU 14868381.6	63121-0154	2014-12-04	Published on 2017-01-04
CA 2,969,829	63121-0155	2014-12-04	Published on 2015-06-11
HK 17106540.3	63121-0156	2014-12-04	Published on 2018-01-19

The Examiner is invited to review the prosecution history of each of these applications, including the cited references of record and related office actions, as the Examiner deems appropriate.

Favorable reconsideration of the present application is respectfully requested.

If any fees are required in view of the foregoing, the Director is hereby authorized to charge any such fee to Deposit Account No. 01-1785.

Respectfully submitted,

AMSTER, ROTHSTEIN & EBENSTEIN LLP
Attorneys for Applicant
405 Lexington Avenue
New York, NY 10174
(212) 336-8000

Dated: New York, New York
March 28, 2024

By: /Keith J. Barkaus/
Keith J. Barkaus
Registration No. 51,431

4895-8029-7138v.1

Petitioner Samsung Ex-1004, 0332

UNITED STATES
PATENT AND TRADEMARK OFFICE

P.O. Box 1450
Alexandria, VA 22313 - 1450
www.uspto.gov

ELECTRONIC ACKNOWLEDGEMENT RECEIPT

APPLICATION #	RECEIPT DATE / TIME	ATTORNEY DOCKET #
18/229,907	**03/28/2024 05:30:50 PM Z ET**	**63121/0224**

Title of Invention

Key Derivation for a Module Using an Embedded Universal Integrated Circuit Card

Application Information

APPLICATION TYPE	Utility - Nonprovisional Application under 35 USC 111(a)	PATENT #	-
CONFIRMATION #	7483	FILED BY	Victoria GILMORE
PATENT CENTER #	64884514	FILING DATE	08/03/2023
CUSTOMER #	1912	FIRST NAMED INVENTOR	John A. Nix
CORRESPONDENCE ADDRESS	-	AUTHORIZED BY	Keith Barkaus

Documents

TOTAL DOCUMENTS: 3

DOCUMENT		PAGES	DESCRIPTION	SIZE (KB)
1-ResponsetoNFOA.pdf		8	-	158 KB
1-ResponsetoNFOA-A....pdf	(1-1)	1	Amendment/Request for Reconsideration-After Non-Final Rejection	124 KB
1-ResponsetoNFOA-CLM.pdf	(2-4)	3	Claims	128 KB
1-ResponsetoNFOA-REM.pdf	(5-8)	4	Applicant Arguments/Remarks Made in an Amendment	149 KB

Digest

DOCUMENT	MESSAGE DIGEST(SHA-512)

1-ResponsetoNFOA.pdf	EF521E04AF7C802525EC306DF1AA07EA8F8418A6479BC1AC4E45BD65E6AEB30949D70E7630AC70104F120246CE30FF91D65AC86A4189107C456F67FC1515D1EB
1-ResponsetoNFOA-A....pdf	26D51EF39AAE5F4C9CA0C8932116CA1341FBC5D36F1AB16EB62F4055206A4AD06ACB41BD8C4E9CC5CDFBA42DBC2395C4A35EAAF4B564827543C1B587533DE27D
1-ResponsetoNFOA-CLM.pdf	946A357E6053DB9656090C2C163E541CE69131FDE18CD8E639023D92DC34F33BA6F78E7EBFF4CE59E28188AD5566BEAA06D7CC8D04D73A83A470E75B56178424
1-ResponsetoNFOA-REM.pdf	C9CD84C0B10751BA3458691A2031AE8F3628B1D1654A226BFDF26E6AC5E3ADA6FCA436FC966674B9BD8C10BBDAA86B13F961496FBA8102EFF3ECF6F50C203EE8

This Acknowledgement Receipt evidences receipt on the noted date by the USPTO of the indicated documents, characterized by the applicant, and including page counts, where applicable. It serves as evidence of receipt similar to a Post Card, as described in MPEP 503.

New Applications Under 35 U.S.C. 111

If a new application is being filed and the application includes the necessary components for filing date (see 37 CFR 1.53(b)-(d) and MPEP 506), a Filing Receipt (37 CFR 1.54) will be issued in due course and the date shown on this Acknowledgement Receipt will establish the filing date of the application

National Stage of an International Application under 35 U.S.C. 371

If a timely submission to enter the national stage of an international application is compliant with the conditions of 35 U.S.C. 371 and other applicable requirements a Form PCT/DO/EO/903 indicating acceptance of the application as a national stage submission under 35 U.S.C. 371 will be issued in addition to the Filing Receipt, in due course.

New International Application Filed with the USPTO as a Receiving Office

If a new international application is being filed and the international application includes the necessary components for an international filing date (see PCT Article 11 and MPEP 1810), a Notification of the International Application Number and of the International Filing Date (Form PCT/RO/105) will be issued in due course, subject to prescriptions concerning national security, and the date shown on this Acknowledgement Receipt will establish the international filing date of the application.

Notice of References Cited	Application/Control No. 18/229,907	Applicant(s)/Patent Under Reexamination Nix, John A.	
	Examiner David García Cervetti	Art Unit 2419	Page 1 of 11

U.S. PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Name	CPC Classification	US Classification
*	A	US-9807605-B2	2017-10-31	Gao; Linyi	H04L63/0428	1/1
*	B	US-20110213959-A1	2011-09-01	Bodi; MiklosTamas	H04W12/06	713/155
*	C	US-8577337-B2	2013-11-05	O'Leary; Edward A.	H04W12/068	455/410
*	D	US-20130344864-A1	2013-12-26	PARK; Chul Hyun	H04W8/18	455/432.3
*	E	US-9800993-B2	2017-10-24	Lee; Duckey	H04W12/126	1/1
*	F	US-9794775-B2	2017-10-17	Huber; Ulrich	H04W8/265	1/1
*	G	US-9674690-B2	2017-06-06	Lee; Hyung Jin	H04W8/183	1/1
*	H	US-9628981-B2	2017-04-18	Park; Jaemin	H04W8/205	1/1
*	I	US-9572016-B2	2017-02-14	Cormier; Jean-Philippe Paul	H04W8/183	1/1
*	J	US-9332129-B2	2016-05-03	Li; Li	H04W4/50	1/1
*	K	US-9270653-B2	2016-02-23	Maria; Arturo	H04L63/062	1/1
*	L	US-20140082359-A1	2014-03-20	Nakhjiri; Madjid	H04L9/3066	713/168
*	M	US-20140120874-A1	2014-05-01	Kang; Hyun-Jeong	H04W12/041	455/411

FOREIGN PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Country	Name	CPC Classification
	N					
	O					
	P					
	Q					
	R					
	S					
	T					

NON-PATENT DOCUMENTS

*		Include as applicable: Author, Title Date, Publisher, Edition or Volume, Pertinent Pages)
	U	
	V	
	W	
	X	

*A copy of this reference is not being furnished with this Office action. (See MPEP § 707.05(a).)
Dates in YYYY-MM-DD format are publication dates. Classifications may be US or foreign.

Petitioner Samsung Ex-1004, 0335

U.S. PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Name	CPC Classification	US Classification
*	A	US-6804357-B1	2004-10-12	Ikonen; Ari M.	H04N21/42204	348/14.05
*	B	US-9923724-B2	2018-03-20	Lee; Duckey	H04L9/0825	1/1
*	C	US-20140329502-A1	2014-11-06	Lee; Jinhyoung	H04W12/04	455/411
*	D	US-6842628-B1	2005-01-11	Arnold; Greg	H04L51/224	713/181
*	E	US-8352739-B2	2013-01-08	Park; Young-Man	H04L63/06	713/169
*	F	US-6721886-B1	2004-04-13	Uskela; Sami	H04L9/3271	713/168
*	G	US-5995625-A	1999-11-30	Sudia; Frank W.	G06F21/6209	713/181
*	H	US-5852665-A	1998-12-22	Gressel; Carmi David	H04L9/0894	380/45
*	I	US-5664017-A	1997-09-02	Gressel; Carmi David	H04L9/0833	380/30
*	J	US-5642420-A	1997-06-24	Kuroda; Yasutsugu	H04L9/40	380/30
*	K	US-5216715-A	1993-06-01	Markwitz; Wernhard	H04L9/321	713/181
*	L	US-20150350881-A1	2015-12-03	WEISS; Dieter	H04W12/04	455/558
*	M	US-20130283047-A1	2013-10-24	Merrien; Lionel	H04L67/306	713/164

FOREIGN PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Country	Name	CPC Classification
	N					
	O					
	P					
	Q					
	R					
	S					
	T					

NON-PATENT DOCUMENTS

*		Include as applicable: Author, Title Date, Publisher, Edition or Volume, Pertinent Pages)
	U	
	V	
	W	
	X	

*A copy of this reference is not being furnished with this Office action. (See MPEP § 707.05(a).)
Dates in YYYY-MM-DD format are publication dates. Classifications may be US or foreign.

Petitioner Samsung Ex-1004, 0336

U.S. PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Name	CPC Classification	US Classification
*	A	US-20120263298-A1	2012-10-18	Suh; Kyung-Joo	H04W4/50	380/255
*	B	US-20080044032-A1	2008-02-21	Lou; Dafu	H04L65/40	380/284
*	C	US-20050058294-A1	2005-03-17	Chen, Liqun	H04L9/0847	380/277
*	D	US-6256733-B1	2001-07-03	Thakkar; Dhanya	H04L63/065	380/279
*	E	US-20160088096-A1	2016-03-24	QUIRICONI; Jean-Rémi	H04W4/50	709/219
*	F	US-20120190354-A1	2012-07-26	MERRIEN; Lionel	H04L67/34	455/422.1
*	G	US-20140287725-A1	2014-09-25	Lee; Jin Hyoung	H04W12/35	455/411
*	H	US-20140237101-A1	2014-08-21	Park; Jaemin	H04W8/205	709/223
*	I	US-20140235210-A1	2014-08-21	Park; Jaemin	H04W12/35	455/411
*	J	US-20140219447-A1	2014-08-07	Park; Jaemin	H04W12/35	380/247
*	K	US-20140140507-A1	2014-05-22	Park; Jaemin	H04W8/183	380/247
*	L	US-9020479-B1	2015-04-28	Somayajula; Siva Rama Kumar	H04W48/18	455/418
*	M	US-8965366-B1	2015-02-24	Somayajula; Siva Rama Kumar	H04W60/00	455/418

FOREIGN PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Country	Name	CPC Classification
	N					
	O					
	P					
	Q					
	R					
	S					
	T					

NON-PATENT DOCUMENTS

*		Include as applicable: Author, Title Date, Publisher, Edition or Volume, Pertinent Pages)
	U	
	V	
	W	
	X	

*A copy of this reference is not being furnished with this Office action. (See MPEP § 707.05(a).)
Dates in YYYY-MM-DD format are publication dates. Classifications may be US or foreign.

Petitioner Samsung Ex-1004, 0337

U.S. PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Name	CPC Classification	US Classification
*	A	US-20140082358-A1	2014-03-20	Nakhjiri; Madjid	H04L9/0822	713/168
*	B	US-20150281964-A1	2015-10-01	Seo; Myoung Hee	H04W8/183	726/9
*	C	US-20150121495-A1	2015-04-30	Gao; Linyi	H04W12/04	726/6
*	D	US-20140308991-A1	2014-10-16	Lee; Jin Hyoung	H04W12/35	455/558
*	E	US-20130340040-A1	2013-12-19	PARK; Chul Hyun	H04L63/08	726/3
*	F	US-20130122864-A1	2013-05-16	HAGGERTY; DAVID T.	G06F21/34	455/411
*	G	US-20110270747-A1	2011-11-03	Xu; Richard H.	H04M15/67	705/40
*	H	US-20160057725-A1	2016-02-25	Suh; Kyungjoo	G06K17/00	455/435.1
*	I	US-20160149903-A1	2016-05-26	Suh; Kyungjoo	H04L63/0428	713/156
*	J	US-20130157673-A1	2013-06-20	Brusilovsky; Alec	H04W12/02	455/450
*	K	US-20110268022-A1	2011-11-03	Xu; Richard H.	H04Q3/0025	370/328
*	L	US-20160127132-A1	2016-05-05	Lee; Duckey	H04L9/0819	713/156
*	M	US-20140357229-A1	2014-12-04	LEE; Duckey	H04W8/245	455/411

FOREIGN PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Country	Name	CPC Classification
	N					
	O					
	P					
	Q					
	R					
	S					
	T					

NON-PATENT DOCUMENTS

*		Include as applicable: Author, Title Date, Publisher, Edition or Volume, Pertinent Pages)
	U	
	V	
	W	
	X	

*A copy of this reference is not being furnished with this Office action. (See MPEP § 707.05(a).)
Dates in YYYY-MM-DD format are publication dates. Classifications may be US or foreign.

Petitioner Samsung Ex-1004, 0338

U.S. PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Name	CPC Classification	US Classification
*	A	US-20130227646-A1	2013-08-29	Haggerty; David	H04L63/10	726/3
*	B	US-20130012168-A1	2013-01-10	Rajadurai; Rajavelsamy	H04W12/04	455/411
*	C	US-20130294602-A1	2013-11-07	Huxham; Horatio Nelson	H04L63/0853	380/255
*	D	US-20140003604-A1	2014-01-02	CAMPAGNA; Matthew John	H04W12/069	380/247
*	E	US-20110269461-A1	2011-11-03	Xu; Richard H.	H04W8/183	455/435.2
*	F	US-20110269472-A1	2011-11-03	Xu; Richard H.	H04W40/02	455/445
*	G	US-20110269422-A1	2011-11-03	Xu; Richard H.	H04M17/20	455/411
*	H	US-20210152359-A1	2021-05-20	KIM; Tae-Gyun	H04L9/0819	1/1
*	I	US-20180276358-A1	2018-09-27	SAWAMURA; Satoshi	G06K19/07	1/1
*	J	US-20160034707-A1	2016-02-04	SAHU; Samir Kant	H04L9/0866	713/168
*	K	US-20150163209-A1	2015-06-11	KAWAMOTO; YOHEI	H04L63/08	726/6
*	L	US-11281813-B1	2022-03-22	Morgan; Thomas Scott	G06F21/72	1/1
*	M	US-20180176223-A1	2018-06-21	Hutchinson; Michael	H04L9/16	1/1

FOREIGN PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Country	Name	CPC Classification
	N					
	O					
	P					
	Q					
	R					
	S					
	T					

NON-PATENT DOCUMENTS

*		Include as applicable: Author, Title Date, Publisher, Edition or Volume, Pertinent Pages)
	U	
	V	
	W	
	X	

*A copy of this reference is not being furnished with this Office action. (See MPEP § 707.05(a).)
Dates in YYYY-MM-DD format are publication dates. Classifications may be US or foreign.

Petitioner Samsung Ex-1004, 0339

U.S. PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Name	CPC Classification	US Classification
*	A	US-20120011362-A1	2012-01-12	Lambert; Robert John	H04L9/0844	713/168
*	B	US-20060129848-A1	2006-06-15	Paksoy; Erdal	G06F21/35	713/193
*	C	US-8452017-B2	2013-05-28	Sherkin; Alexander	H04L9/0844	713/168
*	D	US-20120087493-A1	2012-04-12	CHIDAMBARAM; Avinash	H04L9/0841	713/182
*	E	US-20110035604-A1	2011-02-10	Habraken; G. Wouter	G07F7/1016	235/382
*	F	US-20060235796-A1	2006-10-19	Johnson; Bruce E.	G06Q20/12	705/26.1
*	G	US-20060235795-A1	2006-10-19	Johnson; Bruce E.	G06Q20/02	705/26.1
*	H	US-20150058632-A1	2015-02-26	Beyer; Loraine	H04L65/1073	713/171
*	I	US-8874915-B1	2014-10-28	Rodoper; Mete	H04L9/0838	380/278
*	J	US-20140219448-A1	2014-08-07	Froels; Martin	H04L9/14	380/255
*	K	US-20140032898-A1	2014-01-30	YU; Zhao-Fu	H04N21/4181	713/159
*	L	US-20130301828-A1	2013-11-14	Gouget; Aline	H04L9/0844	380/44
*	M	US-20130290714-A1	2013-10-31	Hans; Sebastian	H04L9/3273	713/168

FOREIGN PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Country	Name	CPC Classification
	N					
	O					
	P					
	Q					
	R					
	S					
	T					

NON-PATENT DOCUMENTS

*		Include as applicable: Author, Title Date, Publisher, Edition or Volume, Pertinent Pages)
	U	
	V	
	W	
	X	

*A copy of this reference is not being furnished with this Office action. (See MPEP § 707.05(a).)
Dates in YYYY-MM-DD format are publication dates. Classifications may be US or foreign.

Petitioner Samsung Ex-1004, 0340

Notice of References Cited	Application/Control No. 18/229,907	Applicant(s)/Patent Under Reexamination Nix, John A.	
	Examiner David García Cervetti	Art Unit 2419	Page 7 of 11

U.S. PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Name	CPC Classification	US Classification
*	A	US-20130067552-A1	2013-03-14	Hawkes; Philip Michael	H04W12/08	726/7
*	B	US-20120284194-A1	2012-11-08	Liu; Jie	G07F7/08	705/66
*	C	US-20120084565-A1	2012-04-05	Wittenberg; Craig Henry	H04L9/3226	713/172
*	D	US-20120028608-A1	2012-02-02	SU; JEN-CHEN	H04W12/08	455/411
*	E	US-20080288773-A1	2008-11-20	Nguyen; Nam	H04L9/321	713/155
*	F	US-20080260149-A1	2008-10-23	Gehrmann; Christian M.	G06Q20/3821	380/247
*	G	US-20080170697-A1	2008-07-17	Heinonen; Petteri	H04L63/0823	380/277
*	H	US-20070241182-A1	2007-10-18	Buer; Mark	H04L63/0853	235/380
*	I	US-20070050622-A1	2007-03-01	Rager; Kent D.	G06F21/445	713/168
*	J	US-20050246529-A1	2005-11-03	Hunt, Galen C.	H04L9/3263	713/168
*	K	US-11258595-B2	2022-02-22	Nix; John A.	H04L63/061	1/1
*	L	US-20210226781-A1	2021-07-22	ARKKO; Jari	H04L9/085	1/1
*	M	US-20210203488-A1	2021-07-01	STÅHL; Per	H04L9/0631	1/1

FOREIGN PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Country	Name	CPC Classification
	N					
	O					
	P					
	Q					
	R					
	S					
	T					

NON-PATENT DOCUMENTS

*		Include as applicable: Author, Title Date, Publisher, Edition or Volume, Pertinent Pages)
	U	
	V	
	W	
	X	

*A copy of this reference is not being furnished with this Office action. (See MPEP § 707.05(a).)
Dates in YYYY-MM-DD format are publication dates. Classifications may be US or foreign.

Petitioner Samsung Ex-1004, 0341

U.S. PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Name	CPC Classification	US Classification
*	A	US-20210144551-A1	2021-05-13	LEE; Hyewon	H04W12/043	1/1
*	B	US-10743176-B1	2020-08-11	Khan; Taussif	H04W12/48	1/1
*	C	US-20200162269-A1	2020-05-21	Nix; John A.	H04L9/14	1/1
*	D	US-20200089488-A1	2020-03-19	Yu; Xiaobo	G06F16/148	1/1
*	E	US-20200021993-A1	2020-01-16	YANG; Xiangying	H04L63/123	1/1
*	F	US-20190394053-A1	2019-12-26	Yu; Xiaobo	G06F21/33	1/1
*	G	US-20190373471-A1	2019-12-05	LI; Li	H04L9/3247	1/1
*	H	US-20190230087-A1	2019-07-25	Gharout; Said	H04W12/35	1/1
*	I	US-20190208417-A1	2019-07-04	KANG; Xin	H04W12/35	1/1
*	J	US-20190190723-A1	2019-06-20	LEE; Jung Do	H04L9/3231	1/1
*	K	US-20190140837-A1	2019-05-09	Cheng; Ziyao	H04W8/20	1/1
*	L	US-20130159710-A1	2013-06-20	Khan; Ahmer A.	H04L9/0891	713/168
*	M	US-7715822-B2	2010-05-11	Semple; James	H04L63/0853	455/433

FOREIGN PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Country	Name	CPC Classification
	N					
	O					
	P					
	Q					
	R					
	S					
	T					

NON-PATENT DOCUMENTS

*		Include as applicable: Author, Title Date, Publisher, Edition or Volume, Pertinent Pages)
	U	
	V	
	W	
	X	

*A copy of this reference is not being furnished with this Office action. (See MPEP § 707.05(a).)
Dates in YYYY-MM-DD format are publication dates. Classifications may be US or foreign.

Petitioner Samsung Ex-1004, 0342

Notice of References Cited	Application/Control No. 18/229,907	Applicant(s)/Patent Under Reexamination Nix, John A.	
	Examiner David García Cervetti	Art Unit 2419	Page 9 of 11

U.S. PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Name	CPC Classification	US Classification
*	A	US-20080130879-A1	2008-06-05	Heinonen; Petteri	H04L9/006	380/44
*	B	US-20060034494-A1	2006-02-16	Holloran; Robert W.	H04L9/3231	382/116
*	C	US-20150143125-A1	2015-05-21	Nix; John A.	H04W76/27	713/171
*	D	US-9247424-B2	2016-01-26	Haggerty; David T.	H04L63/10	1/1
*	E	US-20160226877-A1	2016-08-04	HAGGERTY; David T.	H04W8/183	1/1
*	F	US-9843585-B2	2017-12-12	Haggerty; David T.	H04W12/06	1/1
*	G	US-9037112-B2	2015-05-19	Rajadurai; Rajavelsamy	H04W12/35	713/168
*	H	US-9451459-B2	2016-09-20	Lee; Jinhyoung	H04W12/35	1/1
*	I	US-9426654-B2	2016-08-23	Lee; Jin Hyoung	H04L63/0853	1/1
*	J	US-20160330624-A1	2016-11-10	LEE; Jin Hyoung	H04L63/0853	1/1
*	K	US-20180242153-A1	2018-08-23	LEE; Jin Hyoung	H04L63/0853	1/1
*	L	US-10091653-B2	2018-10-02	Lee; Jin Hyoung	H04W12/06	1/1
*	M	US-10462668-B2	2019-10-29	Lee; Jin Hyoung	H04L63/0823	1/1

FOREIGN PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Country	Name	CPC Classification
	N					
	O					
	P					
	Q					
	R					
	S					
	T					

NON-PATENT DOCUMENTS

*		Include as applicable: Author, Title Date, Publisher, Edition or Volume, Pertinent Pages)
	U	
	V	
	W	
	X	

*A copy of this reference is not being furnished with this Office action. (See MPEP § 707.05(a).)
Dates in YYYY-MM-DD format are publication dates. Classifications may be US or foreign.

Petitioner Samsung Ex-1004, 0343

Notice of References Cited	Application/Control No. 18/229,907	Applicant(s)/Patent Under Reexamination Nix, John A.	
	Examiner David García Cervetti	Art Unit 2419	Page 10 of 11

U.S. PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Name	CPC Classification	US Classification
*	A	US-9712996-B2	2017-07-18	Park; Jaemin	H04W12/04	1/1
*	B	US-20170289792-A1	2017-10-05	PARK; Jaemin	H04L67/306	1/1
*	C	US-20150126153-A1	2015-05-07	Spitz; Stephan	H04W12/06	455/26.1
*	D	US-20060179309-A1	2006-08-10	Cross; David B.	G06F21/6281	713/168
*	E	US-20040146015-A1	2004-07-29	Cross, David B.	H04L9/0894	370/328
*	F	US-8887257-B2	2014-11-11	Haggerty; David T.	H04W12/04	726/9
*	G	US-20140006786-A1	2014-01-02	Campagna; Matthew John	H04W12/04	713/171
*	H	US-20140004824-A1	2014-01-02	Campagna; Matthew John	H04L9/0866	455/411
*	I	US-20120072979-A1	2012-03-22	Cha; Inhyok	H04W12/069	726/8
*	J	US-20120023568-A1	2012-01-26	Cha; Inhyok	H04L63/0807	726/10
*	K	US-20100174907-A1	2010-07-08	Semple; James F.	H04W12/0431	713/169
*	L	US-20220295288-A1	2022-09-15	Ståhl; Per	H04W12/069	1/1
*	M	US-20220095095-A1	2022-03-24	LIM; Taehyung	H04W8/24	1/1

FOREIGN PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Country	Name	CPC Classification
	N					
	O					
	P					
	Q					
	R					
	S					
	T					

NON-PATENT DOCUMENTS

*		Include as applicable: Author, Title Date, Publisher, Edition or Volume, Pertinent Pages)
	U	
	V	
	W	
	X	

*A copy of this reference is not being furnished with this Office action. (See MPEP § 707.05(a).)
Dates in YYYY-MM-DD format are publication dates. Classifications may be US or foreign.

Petitioner Samsung Ex-1004, 0344

Notice of References Cited	Application/Control No. 18/229,907	Applicant(s)/Patent Under Reexamination Nix, John A.	
	Examiner David García Cervetti	Art Unit 2419	Page 11 of 11

U.S. PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Name	CPC Classification	US Classification
*	A	US-20220046409-A1	2022-02-10	LIM; Taehyung	H04W8/205	1/1
*	B	US-20210314148-A1	2021-10-07	YANG; Xiangying	H04L9/088	1/1
*	C	US-20200351656-A1	2020-11-05	JOHANSSON; Petri Mikael	H04W4/70	1/1
*	D	US-20200137572-A1	2020-04-30	LEE; Hyewon	H04W12/04	1/1
*	E	US-20190097794-A1	2019-03-28	Nix; John A.	H04L9/3249	1/1
*	F	US-20180351945-A1	2018-12-06	LI; Li	H04W8/205	1/1
*	G	US-20180144147-A1	2018-05-24	Nix; John A.	H04W12/35	1/1
*	H	US-20180123803-A1	2018-05-03	PARK; Jong-Han	H04L9/14	1/1
*	I	US-20170338954-A1	2017-11-23	YANG; Xiangying	H04W12/35	1/1
*	J	US-20240022404-A1	2024-01-18	Nepstad; Tommie Andr? Andreassen	H04L9/50	1/1
*	K	US-20240022397-A1	2024-01-18	NAITO; Narumi	G06F21/6209	1/1
	L					
	M					

FOREIGN PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Country	Name	CPC Classification
	N					
	O					
	P					
	Q					
	R					
	S					
	T					

NON-PATENT DOCUMENTS

*		Include as applicable: Author, Title Date, Publisher, Edition or Volume, Pertinent Pages)
	U	
	V	
	W	
	X	

*A copy of this reference is not being furnished with this Office action. (See MPEP § 707.05(a).)
Dates in YYYY-MM-DD format are publication dates. Classifications may be US or foreign.

Search Notes	Application/Control No.	Applicant(s)/Patent Under Reexamination
	18/229,907	Nix, John A.
	Examiner	**Art Unit**
	David García Cervetti	2419

CPC - Searched*		
Symbol	**Date**	**Examiner**
H04L9/0861 H04L9/006 H04L9/0662 H04L9/0816 H04L9/0841 H04L9/0844 H04L9/085 H04L9/088 H04L9/0891 H04L9/0894 H04L9/14 H04L9/30 H04L9/3239 H04L9/3247 H04L9/3249 H04L9/3263 H04L63/061 H04L63/0442 H04W12/03 H04W12/041 H04W12/06	04/05/2024	DGC

CPC Combination Sets - Searched*		
Symbol	**Date**	**Examiner**

US Classification - Searched*			
Class	**Subclass**	**Date**	**Examiner**

* See search history printout included with this form or the SEARCH NOTES box below to determine the scope of the search.

Search Notes		
Search Notes	**Date**	**Examiner**
inventor name search, acm, ieee, springer, google, scholar, ip.com, search history attached, global dossier	04/05/2024	DGC

Interference Search			
US Class/CPC Symbol	**US Subclass/CPC Group**	**Date**	**Examiner**

/David Garcia Cervetti/ Primary Examiner, Art Unit 2419	

Petitioner Samsung Ex-1004, 0346

Index of Claims	Application/Control No.	Applicant(s)/Patent Under Reexamination
	18/229,907	Nix, John A.
	Examiner	Art Unit
	David García Cervetti	2419

✓	Rejected	-	Cancelled	N	Non-Elected	A	Appeal
=	Allowed	÷	Restricted	I	Interference	O	Objected

CLAIMS

☐ Claims renumbered in the same order as presented by applicant ☐ CPA ☐ T.D. ☐ R.1.47

CLAIM		DATE								
Final	Original	03/08/2024	04/06/2024							
	1	✓	-							
	2	✓	-							
	3	✓	-							
	4	✓	-							
	5	✓	-							
	6	✓	-							
	7	✓	-							
	8	✓	-							
	9	✓	-							
	10	✓	-							
	11	✓	-							
	12	✓	-							
	13	✓	-							
	14	✓	-							
	15	✓	-							
	16	✓	-							
	17	✓	-							
	18	✓	-							
	19	✓	-							
	20	✓	-							
	21	✓	-							
	22	✓	-							
	23		✓							
	24		✓							
	25		✓							
	26		✓							
	27		✓							
	28		✓							
	29		✓							
	30		✓							
	31		✓							
	32		✓							
	33		✓							
	34		✓							
	35		✓							
	36		✓							
	37		✓							
	38		✓							
	39		✓							
	40		✓							
	41		✓							
	42		✓							

Petitioner Samsung Ex-1004, 0347

PE2E SEARCH - Search History (Prior Art)

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	British Equivalents	Time Stamp
L203	2	"11736283".pn.	(US-PGPUB; USPAT; USOCR; FIT (AP, AT, AU, BE, BG, BR, BY, CA, CH, CN, CS, CU, CZ, DD, DK, EA, EE, ES, FI, FR, GB, HR, HU, ID, IE, IL, IS, IT, JP, KR, LT, LU, LV, MA, MC, MD, MY, NL, NO, NZ, PH, PL, PT, RO, RS, RU, SE, SG, SI, SK, SU, TH, TN, TR, TW, UA, VN, WO); FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2024/03/08 10:27 AM
L204	1	"11736283".pn.	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/08 10:27 AM
L205	110769	(H04L9/0861 H04L9/006 H04L9/0662 H04L9/0816 H04L9/0841 H04L9/0844 H04L9/085 H04L9/088 H04L9/0891 H04L9/0894 H04L9/14 H04L9/30 H04L9/3239 H04L9/3247 H04L9/3249 H04L9/3263 H04L63/061 H04L63/0442 H04W12/03 H04W12/041 H04W12/06).cpc.	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/08 11:40 AM
L206	1	"20230379148".PN. AND (euicc uicc circuit integrated)	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/08 12:43 PM
L207	162	(euicc e$1uicc uicc universal near4 integrated near4 (chip card circuit) smartcard smart$1card sim esim e$1sim subscrib$8 near4 identi$8 near4 module).clm. AND (public private pair) near6 key.clm. AND (authenti$8 authori$8 verif$8 valid$8 determin$8 identif$8) near6 (server gatekeeper gateway	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/08 12:48 PM

Petitioner Samsung Ex-1004, 0348

		provider) near8 (shared secret preshared pre$1shared public private pair) near6 key.clm.					
L208	96	(euicc e$1uicc uicc universal near4 integrated near4 (chip card circuit) smartcard smart$1card sim esim e$1sim subscrib$8 near4 identi$8 near4 module).clm. AND (public private pair) near6 key.clm. AND (authenti$8 authori$8 verif$8 valid$8 determin$8 identif$8) near6 (server gatekeeper gateway provider) near8 (shared secret preshared pre$1shared public private pair) near6 key.clm. AND (@pd @prad @rlad @ptad @ad)<"20131120"	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/08 12:51 PM
L209	44	(Artificial Intelligence) Similar to: 18/229,907 with 0 CPC Selections and 0 Text Selections Text: (US-11736283-B2 OR US-20230379148-A1 OR US-20210351923-A1 OR US-11082218-B2 OR US-20160234020-A1 OR US-20150143125-A1 OR US-20200280439-A1 OR US-9319223-B2 OR US-20170373845-A1 OR GB-2593108-A OR US-9742562-B2 OR GB-2588867-A OR US-11606204-B2 OR US-20220141010-A1 OR US-20230208629-A1 OR AU-2014342646-A1 OR US-11258595-B2 OR US-20220103538-A1 OR US-20190097794-A1 OR CA-2969829-C OR AU-2019246774-B2 OR US-10700856-B2 OR	(US-PGPUB; USPAT; USOCR; FIT (AP, AT, AU, BE, BG, BR, BY, CA, CH, CN, CS, CU, CZ, DD, DK, EA, EE, ES, FI, FR, GB, HR, HU, ID, IE, IL, IS, IT, JP, KR, LT, LU, LV, MA, MC, MD, MY, NL, NO, NZ, PH, PL, PT, RO, RS, RU, SE, SG, SI, SK, SU, TH, TN, TR, TW, UA, VN, WO))	OR	ON	ON	2024/03/08 01:09 PM

Petitioner Samsung Ex-1004, 0349

		US-20210184846-A1 OR US-10084768-B2 OR US-20180212946-A1 OR US-9288059-B2 OR EP-3908024-B1 OR US-10187206-B2 OR EP-3908025-A1 OR EP-3908025-B1 OR US-20150180653-A1 OR US-20150296379-A1 OR US-9300473-B2 OR EP-3908023-B1 OR US-20170237561-A1 OR US-9998280-B2 OR US-20160149709-A1 OR US-20160164678-A1 OR US-9961060-B2 OR US-9998281-B2 OR WO-2015065913-A1 OR US-9641327-B2 OR US-20170188231-A1 OR US-20150304113-A1 OR US-9118464-B2 OR CA-2965119-A1 OR US-20180367522-A1 OR US-11233780-B2 OR US-20150121066-A1 OR US-10382422-B2).did.					
L210	39	(Artificial Intelligence) Similar to: 18/229,907 with 0 CPC Selections and 3 Text Selections Text: (US-20230085059-A1 OR US-20150372811-A1 OR AU-2015277000-A1 OR US-11736283-B2 OR US-20230379148-A1 OR AU-2015204470-B2 OR US-11394697-B2 OR AU-2019216646-A1 OR US-20200092269-A1 OR US-20210351923-A1 OR CN-111355749-A OR AU-2019216646-B2 OR US-20150200774-A1 OR CN-106664206-B OR AU-2015277000-B2 OR US-9967090-B2 OR EP-3158680-A1 OR US-20220353252-A1 OR US-10574633-B2 OR WO-2015195978-	(US-PGPUB; USPAT; USOCR; FIT (AP, AT, AU, BE, BG, BR, BY, CA, CH, CN, CS, CU, CZ, DD, DK, EA, EE, ES, FI, FR, GB, HR, HU, ID, IE, IL, IS, IT, JP, KR, LT, LU, LV, MA, MC, MD, MY, NL, NO, NZ, PH, PL, PT, RO, RS, RU, SE, SG, SI, SK, SU, TH, TN, TR, TW, UA, VN, WO))	OR	ON	ON	2024/03/08 01:10 PM

Petitioner Samsung Ex-1004, 0350

		A1 OR AU-2015204470-A1 OR US-20190260578-A1 OR EP-3158680-B1 OR US-20170222801-A1 OR EP-3860041-A1 OR US-10666428-B2 OR US-10313110-B2 OR EP-3860041-B1 OR CN-106664206-A OR WO-2015106248-A1 OR AU-2015277000-C1 OR US-20180205538-A1 OR EP-3095210-A1 OR WO-2019223851-A1 OR GB-2593108-A OR EP-4027576-A1 OR US-11683163-B2 OR US-20210184842-A1 OR US-9647832-B2 OR CN-111277597-B OR CN-111277597-A OR KR-20110090602-A OR WO-2019246206-A1 OR US-11546309-B2 OR KR-20160104603-A OR WO-2020172887-A1 OR US-11082218-B2 OR US-10129020-B2 OR EP-4027576-B1 OR US-20180205539-A1).did.					
L211	1335	(euicc e$1uicc uicc universal near4 integrated near4 (chip card circuit) smartcard smart$1card sim esim e$1sim subscrib$8 near4 identi$8 near4 module) same4 (public private pair) near6 key same4 (authenti$8 authori$8 verif$8 valid$8 determin$8 identif$8) near6 (server gatekeeper gateway provider) near8 (shared secret preshared pre$1shared public private pair) near6 key	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/08 01:15 PM
L212	221	(euicc e$1uicc uicc universal near4 integrated near4 (chip card circuit) smartcard smart$1card sim esim e$1sim subscrib$8 near4 identi$8 near4	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/08 01:17 PM

Petitioner Samsung Ex-1004, 0351

		module) same4 (public private pair) near6 key same4 (authenti$8 authori$8 verif$8 valid$8 determin$8 identif$8) near6 (server gatekeeper gateway provider) near8 (shared secret preshared pre$1shared public private pair) near6 key same4 (first second) near6 (server provider operator) near8 (public private pair) near6 key					
L213	18	("10169587"|"10621352"|"20060021063"|"20100093347"|"20110158411"|"20110167272"|"20190313246"|"20190332774"|"20190356482"|"20200162247"|"20200162269"|"20200226258"|"20200280436"|"20210126801"|"20210184842"|"20210194681"|"20210211279"|"20210218560").PN.	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/08 01:19 PM
L214	105	(euicc e$1uicc uicc universal near4 integrated near4 (chip card circuit) smartcard smart$1card sim esim e$1sim subscrib$8 near4 identi$8 near4 module) same4 (public private pair) near6 key same4 (authenti$8 authori$8 verif$8 valid$8 determin$8 identif$8) near6 (server gatekeeper gateway provider) near8 (shared secret preshared pre$1shared public private pair) near6 key same4 (first second) near6 (server provider operator) near8 (public private pair) near6 key AND (@pd @prad @rlad @ptad @ad)<"20131120"	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/08 01:42 PM
L215	22	(euicc e$1uicc uicc universal near4 integrated near4 (chip card circuit) smartcard	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/08 02:11 PM

Petitioner Samsung Ex-1004, 0352

		smart$1card sim esim e$1sim subscrib$8 near4 identi$8 near4 module) same4 (public private pair) near6 key same4 (authenti$8 authori$8 verif$8 valid$8 determin$8 identif$8) near6 (server gatekeeper gateway provider) near8 (shared secret preshared pre$1shared public private pair) near6 key same4 encrypted near4 profile AND (@pd @prad @rlad @ptad @ad)<"20131120"					
L216	24	(euicc e$1uicc uicc universal near4 integrated near4 (chip card circuit) smartcard smart$1card sim esim e$1sim subscrib$8 near4 identi$8 near4 module) AND (memory stor$8) near8 public WITH private WITH key WITH (shared preshared pre$1shared) AND encrypted near4 profile AND (@pd @prad @rlad @ptad @ad)<"20131120"	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/08 02:35 PM
L217	3350	(euicc e$1uicc uicc universal near4 integrated near4 (chip card circuit) smartcard smart$1card sim esim e$1sim subscrib$8 near4 identi$8 near4 module) AND (generat$8 deriv$8) near8 (shared preshared pre$1shared common symmetric) near6 key AND (@pd @prad @rlad @ptad @ad)<"20131120"	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/08 03:26 PM
L218	716	(euicc e$1uicc uicc universal near4 integrated near4 (chip card circuit) smartcard smart$1card sim esim e$1sim subscrib$8 near4 identi$8 near4 module) AND	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/08 03:26 PM

Petitioner Samsung Ex-1004, 0353

		(generat$8 deriv$8) near8 (shared preshared pre$1shared common symmetric) near6 key near8 (private public pair) near4 key AND (@pd @prad @rlad @ptad @ad)<"20131120"					
L219	182	(euicc e$1uicc uicc universal near4 integrated near4 (chip card circuit) smartcard smart$1card sim esim e$1sim subscrib$8 near4 identi$8 near4 module) same4 (generat$8 deriv$8) near8 (shared preshared pre$1shared common symmetric) near6 key near8 (private public pair) near4 key AND (@pd @prad @rlad @ptad @ad)<"20131120"	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/08 03:28 PM
L220	96	("11736283" "20210351923" "20160234020" "20190097794" "11082218" "20170373845" "10187206" "20200280439" "10700856" "9319223" "20150143125" "9742562" "20150180653" "9300473" "20150296379" "9961060" "20150163056" "20180367522" "20180212946" "10382422" "20160269386" "20190319937" "20200127991" "10084768" "11916893" "9100175" "20220103538" "20190173867" "11539681" "10594679" "11233780" "9351162" "20150180847" "10362012" "20190097793"	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/08 03:51 PM

Petitioner Samsung Ex-1004, 0354

		"20160164678" "20180270059" "9998280" "10177911" "10498530" "9288059" "20170188231" "20150095648" "20150304113" "20150121066" "20210184846" "20200235923" "20180262329" "9118464" "9596078" "9998281" "11283603" "10652017" "20160149709" "20170237561" "20230208629" "20180343117" "20220141010" "20150106616" "9641327" "20200036521" "9276740" "10530575" "10057059" "11606204" "11258595" "10296752" "20230208626" "20210211279" "10380362" "11621832" "20190087594" "20190220611" "20210342462" "20180330109" "11748500" "11080414" "11838417" "10204233" "20210409214" "20180144147" "20230396455" "20220360622" "20210352132" "11399055" "20220376904" "20240031137" "20200280436" "20220278833" "11849048" "11438176" "20220131709" "11777719" "11343084" "20170272945" "11228448" "20200295933" "20200162269" "10172000" "20170272944" "20200052905" "20230336332" "11128478" "10158991" "20220006625" "20230361994"					

Petitioner Samsung Ex-1004, 0355

		"20210185042" "11706025" "20190313246" "20210184842" "11683163" "20190156019" "20220078029" "11888594" "9906528" "20090191857" "10943005" "20160197922" "11626979" "20230231702" "20220239474" "20060182280" "20220295276" "11909870" "20210218560" "11582233" "11671265" "9300641" "11316672" "20200162247" "20230254163" "20130061055" "20210126801" "20220038269" "20090132813" "9843585" "11153080" "20180254897" "20190173673" "11722296" "10250386" "20230061038" "10523432" "20170302447" "11863663" "10621352" "20220209944" "10003461" "11751049" "10169587" "20160270000" "20150071139" "9350550" "11409896" "9419970" "20190332774" "9247424" "20220248221" "20200104554" "20200226258" "20200104553" "9698981" "20200266993" "10592710" "10554636" "20190097982" "11456873" "20160226877" "20220351263" "11784820" "10686603" "20200106618" "20220131700" "20220407712"					

Petitioner Samsung Ex-1004, 0356

		"8533803" "11232272" "20230216947" "20070055873" "11699047" "20200104891" "10733645" "11032075" "20200320598" "11423452" "10797882" "20220100975" "7844834" "20230306210" "20210203488" "11195174" "20220092589" "11588637" "9813245" "11770254" "20130227646" "10389533" "20160226828" "8887257" "20240064144" "20220368679" "20210097535" "20140365777" "20230162183" "9877194" "20220029994" "11882117" "20190305953" "10206106" "20230231715" "11824643" "20210258166" "11861604" "11843698" "20240022421" "11233645" "20200228332" "20200396078" "20200127840" "20180026787" "10057053" "20140006786" "20200265427" "20160065370" "11544707" "10129223" "20130227286" "8850545" "20210258162" "11438311" "20180249332" "10965465" "20150031413" "20150139424" "20140004824" "20200119924" "9088408" "20160227409" "20230142978"				

Petitioner Samsung Ex-1004, 0357

		"20230396441" "11610195" "20210398115" "8881257" "10841091" "20200104841" "20100174907" "20220129390" "10505738" "10685350" "10748138" "20220036349" "20150067813" "10607214" "20120023568" "20200242599" "11182785" "10630653" "7966000" "11341480" "20200104833" "20120072979" "20130080769" "20200260272" "11502844" "20200366490" "10182060" "8971851" "11728994" "10579998" "10887318" "20200252396" "11129019" "20240073018" "20200244462" "11811743" "20180109374" "20230344637" "20230308424" "20200184463" "10187202" "20230274256" "10778437" "20220368531" "20200106752" "20210385652" "10044713" "20220058645" "10887106" "20230051390" "20200235934" "10581611" "20200267129" "11004072" "20110238972" "20200106609" "11552946" "10554411" "20220109568" "20200106614").pn. AND (@pd @prad @rlad @ptad @ad)<"20131120"					
L273	0	rotating near4	(US-PGPUB; USPAT;	OR	ON	ON	2024/03/05

Petitioner Samsung Ex-1004, 0358

		concentric near4 circular AND captcha	USOCR; FIT (AP, AT, AU, BE, BG, BR, BY, CA, CH, CN, CS, CU, CZ, DD, DK, EA, EE, ES, FI, FR, GB, HR, HU, ID, IE, IL, IS, IT, JP, KR, LT, LU, LV, MA, MC, MD, MY, NL, NO, NZ, PH, PL, PT, RO, RS, RU, SE, SG, SI, SK, SU, TH, TN, TR, TW, UA, VN, WO); FPRS; EPO; JPO; DERWENT; IBM_TDB)				10:02 AM
L274	42	rotating ADJ concentric ADJ circular	(US-PGPUB; USPAT; USOCR; FIT (AP, AT, AU, BE, BG, BR, BY, CA, CH, CN, CS, CU, CZ, DD, DK, EA, EE, ES, FI, FR, GB, HR, HU, ID, IE, IL, IS, IT, JP, KR, LT, LU, LV, MA, MC, MD, MY, NL, NO, NZ, PH, PL, PT, RO, RS, RU, SE, SG, SI, SK, SU, TH, TN, TR, TW, UA, VN, WO); FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2024/03/05 10:04 AM
L308	246	shared near4 secret near4 key.clm. AND elliptic near4 curve.clm.	(US-PGPUB; USPAT)	OR	ON	ON	2024/04/06 08:12 AM
L309	10	shared near4 secret near4 key.clm. AND elliptic near4 curve.clm. AND encrypted near4 profile.clm.	(US-PGPUB; USPAT)	OR	ON	ON	2024/04/06 08:12 AM
L310	68	(ecdh elliptic near4 curve) near8 key same4 encrypted near6 profile	(US-PGPUB; USPAT)	OR	ON	ON	2024/04/06 08:25 AM
L311	1	"20140082359".pn. AND (generat$8 deriv$8 calcula$8 comput$8)	(US-PGPUB; USPAT)	OR	ON	ON	2024/04/06 08:40 AM
L312	36	ansi near6 standard near4 key near6 derivation	(US-PGPUB; USPAT)	OR	ON	ON	2024/04/06 08:43 AM
L313	89	(euicc e$1uicc uicc universal near4 integrated) AND (ecdh elliptic near4 curve) near8 key AND encrypt$8 near6 profile	(US-PGPUB; USPAT)	OR	ON	ON	2024/04/06 08:46 AM
L314	89	(euicc e$1uicc uicc universal near4	(US-PGPUB; USPAT)	OR	ON	ON	2024/04/06 08:47 AM

Petitioner Samsung Ex-1004, 0359

		integrated) AND (ecdh elliptic near4 curve) near8 key AND encrypt$8 near6 profile AND (private public) near6 key					
L315	315968	(H04L9/0861 OR G06F21/33 OR G06F21/35 OR H04J11/00 OR H04L9/006 OR H04L9/0662 OR H04L9/0816 OR H04L9/0841 OR H04L9/0844 OR H04L9/085 OR H04L9/088 OR H04L9/0891 OR H04L9/0894 OR H04L9/14 OR H04L9/30 OR H04L9/3066 OR H04L9/32 OR H04L9/321 OR H04L9/3239 OR H04L9/3247 OR H04L9/3249 OR H04L9/3263 OR H04L12/2854 OR H04L63/0272 OR H04L63/0435 OR H04L63/0442 OR H04L63/045 OR H04L63/06 OR H04L63/061 OR H04L63/0807 OR H04L63/123 OR H04L63/166 OR H04L67/04 OR H04W4/70 OR H04W8/082 OR H04W12/02 OR H04W12/03 OR H04W12/04 OR H04W12/041 OR H04W12/06 OR H04W40/005 OR H04W52/0216 OR H04W52/0235 OR H04W52/0277 OR H04W76/27 OR H04W80/04 OR G06F2221/2105 OR G06F2221/2107 OR G06F2221/2115 OR H04L63/0464 OR H04L2209/24 OR H04L2209/56 OR	(US-PGPUB; USPAT)	OR	ON	ON	2024/04/06 09:13 AM

Petitioner Samsung Ex-1004, 0360

		H04L2209/72 OR H04L2209/80 OR H04L2209/805 OR H04W84/12 OR H04W88/12 OR Y02D30/70 OR H04W8/205).cpc.					
L316	168240	(H04L9/0861 G06F21/33 G06F21/35 H04L9/006 H04L9/0662 H04L9/0816 H04L9/0841 H04L9/0844 H04L9/085 H04L9/088 H04L9/0891 H04L9/0894 H04L9/14 H04L9/30 H04L9/3066 H04L9/32 H04L9/321 H04L9/3239 H04L9/3247 H04L9/3249 H04L9/3263 H04L63/0272 H04L63/0435 H04L63/0442 H04L63/045 H04L63/06 H04L63/061 H04L63/0807 H04L63/123 H04L63/166 H04W12/02 H04W12/03 H04W12/04 H04W12/041 H04W12/06 G06F2221/2105 G06F2221/2107 G06F2221/2115 H04L63/0464 H04L2209/24 H04L2209/56 H04L2209/72 H04L2209/80 H04L2209/805).cpc.	(US-PGPUB; USPAT)	OR	ON	ON	2024/04/06 09:14 AM
L317	2189	(H04L9/0861 G06F21/33 G06F21/35 H04L9/006 H04L9/0662 H04L9/0816 H04L9/0841 H04L9/0844 H04L9/085 H04L9/088 H04L9/0891 H04L9/0894 H04L9/14 H04L9/30 H04L9/3066 H04L9/32 H04L9/321 H04L9/3239 H04L9/3247 H04L9/3249 H04L9/3263	(US-PGPUB; USPAT)	OR	ON	ON	2024/04/06 09:28 AM

Petitioner Samsung Ex-1004, 0361

		H04L63/0272 H04L63/0435 H04L63/0442 H04L63/045 H04L63/06 H04L63/061 H04L63/0807 H04L63/123 H04L63/166 H04W12/02 H04W12/03 H04W12/04 H04W12/041 H04W12/06 G06F2221/2105 G06F2221/2107 G06F2221/2115 H04L63/0464 H04L2209/24 H04L2209/56 H04L2209/72 H04L2209/80 H04L2209/805).cpc. AND (encrypt$8 near6 profile)					
L318	330	(H04L9/0861 G06F21/33 G06F21/35 H04L9/006 H04L9/0662 H04L9/0816 H04L9/0841 H04L9/0844 H04L9/085 H04L9/088 H04L9/0891 H04L9/0894 H04L9/14 H04L9/30 H04L9/3066 H04L9/32 H04L9/321 H04L9/3239 H04L9/3247 H04L9/3249 H04L9/3263 H04L63/0272 H04L63/0435 H04L63/0442 H04L63/045 H04L63/06 H04L63/061 H04L63/0807 H04L63/123 H04L63/166 H04W12/02 H04W12/03 H04W12/04 H04W12/041 H04W12/06 G06F2221/2105 G06F2221/2107 G06F2221/2115 H04L63/0464 H04L2209/24 H04L2209/56	(US-PGPUB; USPAT)	OR	ON	ON	2024/04/06 09:29 AM

Petitioner Samsung Ex-1004, 0362

		H04L2209/72 H04L2209/80 H04L2209/805).cpc. AND (encrypt$8 near6 profile AND elliptic near4 curve)					
L319	92	(H04L9/0861 G06F21/33 G06F21/35 H04L9/006 H04L9/0662 H04L9/0816 H04L9/0841 H04L9/0844 H04L9/085 H04L9/088 H04L9/0891 H04L9/0894 H04L9/14 H04L9/30 H04L9/3066 H04L9/32 H04L9/321 H04L9/3239 H04L9/3247 H04L9/3249 H04L9/3263 H04L63/0272 H04L63/0435 H04L63/0442 H04L63/045 H04L63/06 H04L63/061 H04L63/0807 H04L63/123 H04L63/166 H04W12/02 H04W12/03 H04W12/04 H04W12/041 H04W12/06 G06F2221/2105 G06F2221/2107 G06F2221/2115 H04L63/0464 H04L2209/24 H04L2209/56 H04L2209/72 H04L2209/80 H04L2209/805).cpc. AND (encrypt$8 near6 profile AND elliptic near4 curve AND (uicc euicc universal near4 integrated e$1uicc))	(US-PGPUB; USPAT)	OR	ON	ON	2024/04/06 09:29 AM

PE2E SEARCH - Search History (Interference)

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	British Equivalents	Time Stamp
N183	162	(euicc e$1uicc uicc universal near4 integrated near4 (chip card circuit) smartcard smart$1card sim esim	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/08 12:50 PM

Petitioner Samsung Ex-1004, 0363

		e$1sim subscrib$8 near4 identi$8 near4 module).clm. AND (public private pair) near6 key.clm. AND (authenti$8 authori$8 verif$8 valid$8 determin$8 identif$8) near6 (server gatekeeper gateway provider) near8 (shared secret preshared pre$1shared public private pair) near6 key.clm.					

PE2E SEARCH - Search History (Prior Art)

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	British Equivalents	Time Stamp
L203	2	"11736283".pn.	(US-PGPUB; USPAT; USOCR; FIT (AP, AT, AU, BE, BG, BR, BY, CA, CH, CN, CS, CU, CZ, DD, DK, EA, EE, ES, FI, FR, GB, HR, HU, ID, IE, IL, IS, IT, JP, KR, LT, LU, LV, MA, MC, MD, MY, NL, NO, NZ, PH, PL, PT, RO, RS, RU, SE, SG, SI, SK, SU, TH, TN, TR, TW, UA, VN, WO); FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2024/03/08 10:27 AM
L204	1	"11736283".pn.	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/08 10:27 AM
L205	110769	(H04L9/0861 H04L9/006 H04L9/0662 H04L9/0816 H04L9/0841 H04L9/0844 H04L9/085 H04L9/088 H04L9/0891 H04L9/0894 H04L9/14 H04L9/30 H04L9/3239 H04L9/3247 H04L9/3249 H04L9/3263 H04L63/061 H04L63/0442 H04W12/03 H04W12/041 H04W12/06).cpc.	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/08 11:40 AM
L206	1	"20230379148".PN. AND (euicc uicc circuit integrated)	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/08 12:43 PM
L207	162	(euicc e$1uicc uicc universal near4 integrated near4 (chip card circuit) smartcard smart$1card sim esim e$1sim subscrib$8 near4 identi$8 near4 module).clm. AND (public private pair) near6 key.clm. AND (authenti$8 authori$8 verif$8 valid$8 determin$8 identif$8) near6 (server gatekeeper gateway	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/08 12:48 PM

Petitioner Samsung Ex-1004, 0365

		provider) near8 (shared secret preshared pre$1shared public private pair) near6 key.clm.					
L208	96	(euicc e$1uicc uicc universal near4 integrated near4 (chip card circuit) smartcard smart$1card sim esim e$1sim subscrib$8 near4 identi$8 near4 module).clm. AND (public private pair) near6 key.clm. AND (authenti$8 authori$8 verif$8 valid$8 determin$8 identif$8) near6 (server gatekeeper gateway provider) near8 (shared secret preshared pre$1shared public private pair) near6 key.clm. AND (@pd @prad @rlad @ptad @ad)<"20131120"	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/08 12:51 PM
L209	44	(Artificial Intelligence) Similar to: 18/229,907 with 0 CPC Selections and 0 Text Selections Text: (US-11736283-B2 OR US-20230379148-A1 OR US-20210351923-A1 OR US-11082218-B2 OR US-20160234020-A1 OR US-20150143125-A1 OR US-20200280439-A1 OR US-9319223-B2 OR US-20170373845-A1 OR GB-2593108-A OR US-9742562-B2 OR GB-2588867-A OR US-11606204-B2 OR US-20220141010-A1 OR US-20230208629-A1 OR AU-2014342646-A1 OR US-11258595-B2 OR US-20220103538-A1 OR US-20190097794-A1 OR CA-2969829-C OR AU-2019246774-B2 OR US-10700856-B2 OR	(US-PGPUB; USPAT; USOCR; FIT (AP, AT, AU, BE, BG, BR, BY, CA, CH, CN, CS, CU, CZ, DD, DK, EA, EE, ES, FI, FR, GB, HR, HU, ID, IE, IL, IS, IT, JP, KR, LT, LU, LV, MA, MC, MD, MY, NL, NO, NZ, PH, PL, PT, RO, RS, RU, SE, SG, SI, SK, SU, TH, TN, TR, TW, UA, VN, WO))	OR	ON	ON	2024/03/08 01:09 PM

Petitioner Samsung Ex-1004, 0366

		US-20210184846-A1 OR US-10084768-B2 OR US-20180212946-A1 OR US-9288059-B2 OR EP-3908024-B1 OR US-10187206-B2 OR EP-3908025-A1 OR EP-3908025-B1 OR US-20150180653-A1 OR US-20150296379-A1 OR US-9300473-B2 OR EP-3908023-B1 OR US-20170237561-A1 OR US-9998280-B2 OR US-20160149709-A1 OR US-20160164678-A1 OR US-9961060-B2 OR US-9998281-B2 OR WO-2015065913-A1 OR US-9641327-B2 OR US-20170188231-A1 OR US-20150304113-A1 OR US-9118464-B2 OR CA-2965119-A1 OR US-20180367522-A1 OR US-11233780-B2 OR US-20150121066-A1 OR US-10382422-B2).did.					
L210	39	(Artificial Intelligence) Similar to: 18/229,907 with 0 CPC Selections and 3 Text Selections Text: (US-20230085059-A1 OR US-20150372811-A1 OR AU-2015277000-A1 OR US-11736283-B2 OR US-20230379148-A1 OR AU-2015204470-B2 OR US-11394697-B2 OR AU-2019216646-A1 OR US-20200092269-A1 OR US-20210351923-A1 OR CN-111355749-A OR AU-2019216646-B2 OR US-20150200774-A1 OR CN-106664206-B OR AU-2015277000-B2 OR US-9967090-B2 OR EP-3158680-A1 OR US-20220353252-A1 OR US-10574633-B2 OR WO-2015195978-	(US-PGPUB; USPAT; USOCR; FIT (AP, AT, AU, BE, BG, BR, BY, CA, CH, CN, CS, CU, CZ, DD, DK, EA, EE, ES, FI, FR, GB, HR, HU, ID, IE, IL, IS, IT, JP, KR, LT, LU, LV, MA, MC, MD, MY, NL, NO, NZ, PH, PL, PT, RO, RS, RU, SE, SG, SI, SK, SU, TH, TN, TR, TW, UA, VN, WO))	OR	ON	ON	2024/03/08 01:10 PM

Petitioner Samsung Ex-1004, 0367

		A1 OR AU-2015204470-A1 OR US-20190260578-A1 OR EP-3158680-B1 OR US-20170222801-A1 OR EP-3860041-A1 OR US-10666428-B2 OR US-10313110-B2 OR EP-3860041-B1 OR CN-106664206-A OR WO-2015106248-A1 OR AU-2015277000-C1 OR US-20180205538-A1 OR EP-3095210-A1 OR WO-2019223851-A1 OR GB-2593108-A OR EP-4027576-A1 OR US-11683163-B2 OR US-20210184842-A1 OR US-9647832-B2 OR CN-111277597-B OR CN-111277597-A OR KR-20110090602-A OR WO-2019246206-A1 OR US-11546309-B2 OR KR-20160104603-A OR WO-2020172887-A1 OR US-11082218-B2 OR US-10129020-B2 OR EP-4027576-B1 OR US-20180205539-A1).did.					
L211	1335	(euicc e$1uicc uicc universal near4 integrated near4 (chip card circuit) smartcard smart$1card sim esim e$1sim subscrib$8 near4 identi$8 near4 module) same4 (public private pair) near6 key same4 (authenti$8 authori$8 verif$8 valid$8 determin$8 identif$8) near6 (server gatekeeper gateway provider) near8 (shared secret preshared pre$1shared public private pair) near6 key	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/08 01:15 PM
L212	221	(euicc e$1uicc uicc universal near4 integrated near4 (chip card circuit) smartcard smart$1card sim esim e$1sim subscrib$8 near4 identi$8 near4	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/08 01:17 PM

Petitioner Samsung Ex-1004, 0368

		module) same4 (public private pair) near6 key same4 (authenti$8 authori$8 verif$8 valid$8 determin$8 identif$8) near6 (server gatekeeper gateway provider) near8 (shared secret preshared pre$1shared public private pair) near6 key same4 (first second) near6 (server provider operator) near8 (public private pair) near6 key					
L213	18	("10169587"|"10621352"|"20060021063"|"20100093347"|"20110158411"|"20110167272"|"20190313246"|"20190332774"|"20190356482"|"20200162247"|"20200162269"|"20200226258"|"20200280436"|"20210126801"|"20210184842"|"20210194681"|"20210211279"|"20210218560").PN.	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/08 01:19 PM
L214	105	(euicc e$1uicc uicc universal near4 integrated near4 (chip card circuit) smartcard smart$1card sim esim e$1sim subscrib$8 near4 identi$8 near4 module) same4 (public private pair) near6 key same4 (authenti$8 authori$8 verif$8 valid$8 determin$8 identif$8) near6 (server gatekeeper gateway provider) near8 (shared secret preshared pre$1shared public private pair) near6 key same4 (first second) near6 (server provider operator) near8 (public private pair) near6 key AND (@pd @prad @rlad @ptad @ad)<"20131120"	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/08 01:42 PM
L215	22	(euicc e$1uicc uicc universal near4 integrated near4 (chip card circuit) smartcard	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/08 02:11 PM

Petitioner Samsung Ex-1004, 0369

		smart$1card sim esim e$1sim subscrib$8 near4 identi$8 near4 module) same4 (public private pair) near6 key same4 (authenti$8 authori$8 verif$8 valid$8 determin$8 identif$8) near6 (server gatekeeper gateway provider) near8 (shared secret preshared pre$1shared public private pair) near6 key same4 encrypted near4 profile AND (@pd @prad @rlad @ptad @ad)<"20131120"					
L216	24	(euicc e$1uicc uicc universal near4 integrated near4 (chip card circuit) smartcard smart$1card sim esim e$1sim subscrib$8 near4 identi$8 near4 module) AND (memory stor$8) near8 public WITH private WITH key WITH (shared preshared pre$1shared) AND encrypted near4 profile AND (@pd @prad @rlad @ptad @ad)<"20131120"	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/08 02:35 PM
L217	3350	(euicc e$1uicc uicc universal near4 integrated near4 (chip card circuit) smartcard smart$1card sim esim e$1sim subscrib$8 near4 identi$8 near4 module) AND (generat$8 deriv$8) near8 (shared preshared pre$1shared common symmetric) near6 key AND (@pd @prad @rlad @ptad @ad)<"20131120"	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/08 03:26 PM
L218	716	(euicc e$1uicc uicc universal near4 integrated near4 (chip card circuit) smartcard smart$1card sim esim e$1sim subscrib$8 near4 identi$8 near4 module) AND	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/08 03:26 PM

Petitioner Samsung Ex-1004, 0370

		(generat$8 deriv$8) near8 (shared preshared pre$1shared common symmetric) near6 key near8 (private public pair) near4 key AND (@pd @prad @rlad @ptad @ad)<"20131120"					
L219	182	(euicc e$1uicc uicc universal near4 integrated near4 (chip card circuit) smartcard smart$1card sim esim e$1sim subscrib$8 near4 identi$8 near4 module) same4 (generat$8 deriv$8) near8 (shared preshared pre$1shared common symmetric) near6 key near8 (private public pair) near4 key AND (@pd @prad @rlad @ptad @ad)<"20131120"	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/08 03:28 PM
L220	96	("11736283" "20210351923" "20160234020" "20190097794" "11082218" "20170373845" "10187206" "20200280439" "10700856" "9319223" "20150143125" "9742562" "20150180653" "9300473" "20150296379" "9961060" "20150163056" "20180367522" "20180212946" "10382422" "20160269386" "20190319937" "20200127991" "10084768" "11916893" "9100175" "20220103538" "20190173867" "11539681" "10594679" "11233780" "9351162" "20150180847" "10362012" "20190097793"	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/08 03:51 PM

Petitioner Samsung Ex-1004, 0371

		"20160164678" "20180270059" "9998280" "10177911" "10498530" "9288059" "20170188231" "20150095648" "20150304113" "20150121066" "20210184846" "20200235923" "20180262329" "9118464" "9596078" "9998281" "11283603" "10652017" "20160149709" "20170237561" "20230208629" "20180343117" "20220141010" "20150106616" "9641327" "20200036521" "9276740" "10530575" "10057059" "11606204" "11258595" "10296752" "20230208626" "20210211279" "10380362" "11621832" "20190087594" "20190220611" "20210342462" "20180330109" "11748500" "11080414" "11838417" "10204233" "20210409214" "20180144147" "20230396455" "20220360622" "20210352132" "11399055" "20220376904" "20240031137" "20200280436" "20220278833" "11849048" "11438176" "20220131709" "11777719" "11343084" "20170272945" "11228448" "20200295933" "20200162269" "10172000" "20170272944" "20200052905" "20230336332" "11128478" "10158991" "20220006625" "20230361994"					

Petitioner Samsung Ex-1004, 0372

		"20210185042" "11706025" "20190313246" "20210184842" "11683163" "20190156019" "20220078029" "11888594" "9906528" "20090191857" "10943005" "20160197922" "11626979" "20230231702" "20220239474" "20060182280" "20220295276" "11909870" "20210218560" "11582233" "11671265" "9300641" "11316672" "20200162247" "20230254163" "20130061055" "20210126801" "20220038269" "20090132813" "9843585" "11153080" "20180254897" "20190173673" "11722296" "10250386" "20230061038" "10523432" "20170302447" "11863663" "10621352" "20220209944" "10003461" "11751049" "10169587" "20160270000" "20150071139" "9350550" "11409896" "9419970" "20190332774" "9247424" "20220248221" "20200104554" "20200226258" "20200104553" "9698981" "20200266993" "10592710" "10554636" "20190097982" "11456873" "20160226877" "20220351263" "11784820" "10686603" "20200106618" "20220131700" "20220407712"					

Petitioner Samsung Ex-1004, 0373

		"8533803" "11232272" "20230216947" "20070055873" "11699047" "20200104891" "10733645" "11032075" "20200320598" "11423452" "10797882" "20220100975" "7844834" "20230306210" "20210203488" "11195174" "20220092589" "11588637" "9813245" "11770254" "20130227646" "10389533" "20160226828" "8887257" "20240064144" "20220368679" "20210097535" "20140365777" "20230162183" "9877194" "20220029994" "11882117" "20190305953" "10206106" "20230231715" "11824643" "20210258166" "11861604" "11843698" "20240022421" "11233645" "20200228332" "20200396078" "20200127840" "20180026787" "10057053" "20140006786" "20200265427" "20160065370" "11544707" "10129223" "20130227286" "8850545" "20210258162" "11438311" "20180249332" "10965465" "20150031413" "20150139424" "20140004824" "20200119924" "9088408" "20160227409" "20230142978"				

Petitioner Samsung Ex-1004, 0374

		"20230396441" "11610195" "20210398115" "8881257" "10841091" "20200104841" "20100174907" "20220129390" "10505738" "10685350" "10748138" "20220036349" "20150067813" "10607214" "20120023568" "20200242599" "11182785" "10630653" "7966000" "11341480" "20200104833" "20120072979" "20130080769" "20200260272" "11502844" "20200366490" "10182060" "8971851" "11728994" "10579998" "10887318" "20200252396" "11129019" "20240073018" "20200244462" "11811743" "20180109374" "20230344637" "20230308424" "20200184463" "10187202" "20230274256" "10778437" "20220368531" "20200106752" "20210385652" "10044713" "20220058645" "10887106" "20230051390" "20200235934" "10581611" "20200267129" "11004072" "20110238972" "20200106609" "11552946" "10554411" "20220109568" "20200106614").pn. AND (@pd @prad @rlad @ptad @ad)<"20131120"					
L263	304	(split$8 shar$8 divid$8	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/23

Petitioner Samsung Ex-1004, 0375

		subdivi$8) near4 private near4 key same4 (mpc multiparty multi$1party)					03:49 PM
L264	583	(sign signing signed signature) WITH (split$8 shar$8 divid$8 subdivi$8) near6 key AND (mpc multiparty multi$1party)	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/23 03:53 PM
L265	312	(sign signing signed signature) WITH (split$8 shar$8 divid$8 subdivi$8) near6 key AND (mpc multiparty multi$1party) AND (certificate)	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/23 03:57 PM
L266	137	(sign signing signed signature) WITH (split$8 shar$8 divid$8 subdivi$8) near6 key same4 certif$8 AND (mpc multiparty multi$1party) AND (certificate)	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/23 03:57 PM
L267	287	("20230126356" "20230128131" "20100161956" "8612753" "20230245111" "10958424" "11804957" "20020062451" "20230069934" "10389696" "10447674" "20170310652" "20210326442" "20170171174" "20060248333" "20220318907" "7447903" "11502827" "20230246817" "20230299942" "20190097982" "11089032" "20120185680" "11620387" "20190222583" "20060117177" "10129223" "11418329" "8683215" "10554636" "7987356" "20060013402" "20170171219" "20200021567" "11777721" "11811950" "11115394" "20070055878"	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/23 04:02 PM

Petitioner Samsung Ex-1004, 0376

		"20170149740" "9705859" "10382409" "10412098" "20060050870" "10243968" "20220109660" "7697691" "20210258288" "20190296917" "11687667" "11811740" "20230104126" "7149310" "10637836" "11546169" "11677729" "20100150351" "20230269241" "7715565" "20190327210" "11038853" "10375067" "20230246850" "20230246822" "11240212" "9705674" "9667421" "20050027989" "20230053566" "20220385470" "20170005999" "9832171" "20200287876" "11722303" "10326597" "7596697" "10601789" "20180324176" "10666436" "7055032" "20100202609" "11470054" "20080172559" "20090222658" "20140229737" "20140244998" "20180083929" "20170093581" "20210266161" "20040111607" "20200213283" "9544297" "20040068650" "10511591" "9608813" "20060182283" "11502834" "8660266" "20200266976" "20230308424" "20220021525" "10313312" "20170346819" "7865721" "20230291556" "20140310516" "20060182277" "20230163946"					

Petitioner Samsung Ex-1004, 0377

		"9516002" "10754693" "11218317" "11695555" "20130042105" "20170195119" "20220038278" "20140229739" "20180198606" "20200012527" "20220173886" "11652616" "11522686" "20190173672" "7318155" "10652015" "8745379" "9762577" "9882900" "20230142978" "20180343127" "10218502" "8745372" "20140304503" "20210266147" "20210144004" "20130227286" "10121017" "8340287" "20190356650" "11582020" "20200252396" "9258117" "9208335" "11310036" "20230216662" "20210266154" "20160182486" "10484365" "11546137" "10516543" "20110202755" "10210341" "20210266152" "20160156626" "10630682" "20220337432" "20020078354" "20190104118" "8312518" "20060184786" "8213608" "20220006626" "11552946" "11757658" "20150082399" "11206135" "10911431" "11489821" "20200036707" "10521595" "20060133615" "11824974" "11582045" "20020073309" "20060184787" "6970562" "20210377049" "8015409" "11329980" "20160241389"					

Petitioner Samsung Ex-1004, 0378

		"11374771" "20210184864" "20160283723" "10097536" "11270006" "20210266304" "7630493" "20060184788" "11184160" "20200293698" "20050154889" "9984238" "20220377084" "20080082449" "8108670" "20230188364" "11606348" "20020076042" "6901512" "20080016337" "20180300489" "20020073310" "20220209944" "11405215" "10706182" "20180324175" "10211977" "20060072762" "20200193036" "20210266156" "20060182276" "20200252382" "20210226938" "20220231858" "20090313470" "9367697" "20210266177" "20020078344" "20240061941" "20140229732" "20130013931" "9853979" "11095634" "9942034" "20180181756" "20020078353" "11036869" "11604901" "20190205540" "11036861" "8160244" "11757660" "7065642" "7386720" "20060072748" "10229270" "6940980" "11728974" "20200274711" "20220045867" "20170351879" "20120221854" "20120226904" "7565527" "11184157" "9590959" "11438161"					

Petitioner Samsung Ex-1004, 0379

		"20210306162" "9100186" "9553854" "11258617" "11178116" "20220247554" "10798086" "8112628" "20190052463" "9992170" "6615350" "20210135872" "9300639" "20160323264" "20050166051" "10230730" "20060242407" "20150089244" "20180367509" "20140229729" "10127389" "10432401" "20150317487" "10277407" "20190080099" "10027484" "20220158855" "20180124056" "11671412" "7475247" "20190280883" "7599493" "20020071563" "10911457" "20020141593" "10404670" "20190207942" "20170302459" "10503917" "20060013399" "20130276074" "7711120").pn.					
L268	273	("20230126356" "20230128131" "20100161956" "8612753" "20230245111" "10958424" "11804957" "20020062451" "20230069934" "10389696" "10447674" "20170310652" "20210326442" "20170171174" "20060248333" "20220318907" "7447903" "11502827" "20230246817" "20230299942" "20190097982" "11089032" "20120185680" "11620387"	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/23 04:03 PM

Petitioner Samsung Ex-1004, 0380

		"20190222583" "20060117177" "10129223" "11418329" "8683215" "10554636" "7987356" "20060013402" "20170171219" "20200021567" "11777721" "11811950" "11115394" "20070055878" "20170149740" "9705859" "10382409" "10412098" "20060050870" "10243968" "20220109660" "7697691" "20210258288" "20190296917" "11687667" "11811740" "20230104126" "7149310" "10637836" "11546169" "11677729" "20100150351" "20230269241" "7715565" "20190327210" "11038853" "10375067" "20230246850" "20230246822" "11240212" "9705674" "9667421" "20050027989" "20230053566" "20220385470" "20170005999" "9832171" "20200287876" "11722303" "10326597" "7596697" "10601789" "20180324176" "10666436" "7055032" "20100202609" "11470054" "20080172559" "20090222658" "20140229737" "20140244998" "20180083929" "20170093581" "20210266161" "20040111607" "20200213283" "9544297" "20040068650" "10511591" "9608813" "20060182283"					

Petitioner Samsung Ex-1004, 0381

		"11502834" "8660266" "20200266976" "20230308424" "20220021525" "10313312" "20170346819" "7865721" "20230291556" "20140310516" "20060182277" "20230163946" "9516002" "10754693" "11218317" "11695555" "20130042105" "20170195119" "20220038278" "20140229739" "20180198606" "20200012527" "20220173886" "11652616" "11522686" "20190173672" "7318155" "10652015" "8745379" "9762577" "9882900" "20230142978" "20180343127" "10218502" "8745372" "20140304503" "20210266147" "20210144004" "20130227286" "10121017" "8340287" "20190356650" "11582020" "20200252396" "9258117" "9208335" "11310036" "20230216662" "20210266154" "20160182486" "10484365" "11546137" "10516543" "20110202755" "10210341" "20210266152" "20160156626" "10630682" "20220337432" "20020078354" "20190104118" "8312518" "20060184786" "8213608" "20220006626" "11552946" "11757658" "20150082399" "11206135" "10911431"				

Petitioner Samsung Ex-1004, 0382

		"11489821" "20200036707" "10521595" "20060133615" "11824974" "11582045" "20020073309" "20060184787" "6970562" "20210377049" "8015409" "11329980" "20160241389" "11374771" "20210184864" "20160283723" "10097536" "11270006" "20210266304" "7630493" "20060184788" "11184160" "20200293698" "20050154889" "9984238" "20220377084" "20080082449" "8108670" "20230188364" "11606348" "20020076042" "6901512" "20080016337" "20180300489" "20020073310" "20220209944" "11405215" "10706182" "20180324175" "10211977" "20060072762" "20200193036" "20210266156" "20060182276" "20200252382" "20210226938" "20220231858" "20090313470" "9367697" "20210266177" "20020078344" "20240061941" "20140229732" "20130013931" "9853979" "11095634" "9942034" "20180181756" "20020078353" "11036869" "11604901" "20190205540" "11036861" "8160244" "11757660" "7065642"					

Petitioner Samsung Ex-1004, 0383

		"7386720" "20060072748" "10229270" "6940980" "11728974" "20200274711" "20220045867" "20170351879" "20120221854" "20120226904" "7565527" "11184157" "9590959" "11438161" "20210306162" "9100186" "9553854" "11258617" "11178116" "20220247554" "10798086" "8112628" "20190052463" "9992170" "6615350" "20210135872" "9300639" "20160323264" "20050166051" "10230730" "20060242407" "20150089244" "20180367509" "20140229729" "10127389" "10432401" "20150317487" "10277407" "20190080099" "10027484" "20220158855" "20180124056" "11671412" "7475247" "20190280883" "7599493" "20020071563" "10911457" "20020141593" "10404670" "20190207942" "20170302459" "10503917" "20060013399" "20130276074" "7711120").pn. AND (@pd @prad @rlad @ptad @ad)<20211028					
L269	43	(Artificial Intelligence) Similar to: 17/649,546 with 0 CPC Selections and 0 Text Selections Text: (US-20230130121-A1 OR US-20230128131-	(US-PGPUB; USPAT; USOCR; FIT (AP, AT, AU, BE, BG, BR, BY, CA, CH, CN, CS, CU, CZ, DD, DK, EA, EE, ES, FI, FR, GB, HR, HU, ID, IE, IL, IS, IT, JP, KR, LT, LU, LV,	OR	ON	ON	2024/02/23 04:10 PM

Petitioner Samsung Ex-1004, 0384

		A1 OR US-20230126356-A1 OR US-20220094530-A1 OR WO-2022107151-A1 OR EP-4248611-A1 OR US-20180302217-A1 OR WO-2017115338-A1 OR US-20230299942-A1 OR CN-109787762-B OR US-20230153445-A1 OR US-10461943-B1 OR CN-108600222-A OR US-20230089865-A1 OR WO-2020172884-A1 OR US-11550933-B2 OR US-20210390189-A1 OR EP-3262784-A1 OR US-8745394-B1 OR US-11743044-B2 OR US-11258617-B1 OR US-20180034810-A1 OR CN-106953725-B OR US-20150074408-A1 OR CN-108242997-B OR US-11728974-B2 OR US-20090327731-A1 OR US-7370202-B2 OR EP-3850786-A1 OR WO-2020053851-A1 OR US-20230155811-A1 OR CN-109687959-B OR US-20230082949-A1 OR US-10263961-B2 OR US-20060095771-A1 OR US-20210377015-A1 OR US-11438168-B2 OR EP-4179692-A1 OR WO-2020182302-A1 OR US-20190312730-A1 OR EP-1807963-A2 OR US-11720891-B2 OR WO-2020135853-A1 OR US-9608814-B2 OR US-20230086968-A1 OR WO-2022269544-A1 OR US-8175269-B2 OR JP-2023535077-A OR US-11314888-B2 OR CN-114039722-A).did.	MA, MC, MD, MY, NL, NO, NZ, PH, PL, PT, RO, RS, RU, SE, SG, SI, SK, SU, TH, TN, TR, TW, UA, VN, WO))				
L270	47	(Artificial Intelligence) Similar to: 17/649,546 with 0 CPC	(US-PGPUB; USPAT; USOCR; FIT (AP, AT, AU, BE, BG, BR, BY,	OR	ON	ON	2024/02/23 04:11 PM

Petitioner Samsung Ex-1004, 0385

		Selections and 1 Text Selection Text: (US-11388149-B2 OR US-7596697-B2 OR WO-2006078556-A2 OR US-20230130121-A1 OR US-20200382289-A1 OR US-20230126356-A1 OR US-20220321339-A1 OR US-11757634-B2 OR US-20220255731-A1 OR US-20200169410-A1 OR EP-3673609-A1 OR WO-2020006319-A1 OR WO-2019202586-A1 OR CN-115037435-A OR US-10887110-B2 OR US-20230128131-A1 OR US-20220131688-A1 OR US-11626980-B2 OR US-20070055878-A1 OR CN-111143894-A OR US-11201734-B2 OR GB-2611276-A OR US-9973496-B2 OR US-20190372760-A1 OR US-11258617-B1 OR US-20220029796-A1 OR KR-20160105717-A OR KR-20230031278-A OR US-20220417032-A1 OR JP-2023535077-A OR EP-4179692-A1 OR US-20220045853-A1 OR US-7599493-B2 OR KR-101784488-B1 OR US-10686597-B1 OR US-11831755-B2 OR US-11509458-B2 OR US-11704150-B2 OR US-11108753-B2 OR WO-2016191376-A1 OR US-9813234-B2 OR US-10764261-B2 OR KR-20210127168-A OR US-20060182283-A1 OR US-20160335440-A1 OR US-20160277373-A1 OR CN-114785491-A OR US-20100202609-A1 OR US-11126709-B2 OR EP-3050011-	CA, CH, CN, CS, CU, CZ, DD, DK, EA, EE, ES, FI, FR, GB, HR, HU, ID, IE, IL, IS, IT, JP, KR, LT, LU, LV, MA, MC, MD, MY, NL, NO, NZ, PH, PL, PT, RO, RS, RU, SE, SG, SI, SK, SU, TH, TN, TR, TW, UA, VN, WO))				

Petitioner Samsung Ex-1004, 0386

		A1).did.					
L271	49249470	rotating concentric circular	(US-PGPUB; USPAT; USOCR; FIT (AP, AT, AU, BE, BG, BR, BY, CA, CH, CN, CS, CU, CZ, DD, DK, EA, EE, ES, FI, FR, GB, HR, HU, ID, IE, IL, IS, IT, JP, KR, LT, LU, LV, MA, MC, MD, MY, NL, NO, NZ, PH, PL, PT, RO, RS, RU, SE, SG, SI, SK, SU, TH, TN, TR, TW, UA, VN, WO); FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2024/03/05 10:02 AM
L272	3670	rotating near4 concentric near4 circular	(US-PGPUB; USPAT; USOCR; FIT (AP, AT, AU, BE, BG, BR, BY, CA, CH, CN, CS, CU, CZ, DD, DK, EA, EE, ES, FI, FR, GB, HR, HU, ID, IE, IL, IS, IT, JP, KR, LT, LU, LV, MA, MC, MD, MY, NL, NO, NZ, PH, PL, PT, RO, RS, RU, SE, SG, SI, SK, SU, TH, TN, TR, TW, UA, VN, WO); FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2024/03/05 10:02 AM
L273	0	rotating near4 concentric near4 circular AND captcha	(US-PGPUB; USPAT; USOCR; FIT (AP, AT, AU, BE, BG, BR, BY, CA, CH, CN, CS, CU, CZ, DD, DK, EA, EE, ES, FI, FR, GB, HR, HU, ID, IE, IL, IS, IT, JP, KR, LT, LU, LV, MA, MC, MD, MY, NL, NO, NZ, PH, PL, PT, RO, RS, RU, SE, SG, SI, SK, SU, TH, TN, TR, TW, UA, VN, WO); FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2024/03/05 10:02 AM
L274	42	rotating ADJ concentric ADJ circular	(US-PGPUB; USPAT; USOCR; FIT (AP, AT, AU, BE, BG, BR, BY, CA, CH, CN, CS, CU, CZ, DD, DK, EA, EE, ES, FI, FR, GB, HR, HU, ID, IE, IL, IS, IT, JP, KR, LT, LU, LV, MA, MC, MD, MY, NL, NO, NZ, PH, PL, PT,	OR	ON	ON	2024/03/05 10:04 AM

Petitioner Samsung Ex-1004, 0387

			RO, RS, RU, SE, SG, SI, SK, SU, TH, TN, TR, TW, UA, VN, WO); FPRS; EPO; JPO; DERWENT; IBM_TDB)				
L275	414	(neural near6 network) near6 (password pass$1word passphrase pass$1phrase)	(US-PGPUB; USPAT; USOCR; FIT (AP, AT, AU, BE, BG, BR, BY, CA, CH, CN, CS, CU, CZ, DD, DK, EA, EE, ES, FI, FR, GB, HR, HU, ID, IE, IL, IS, IT, JP, KR, LT, LU, LV, MA, MC, MD, MY, NL, NO, NZ, PH, PL, PT, RO, RS, RU, SE, SG, SI, SK, SU, TH, TN, TR, TW, UA, VN, WO); FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2024/02/27 09:52 PM
L276	69	(neural near6 network) near6 (password pass$1word passphrase pass$1phrase)	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/27 09:52 PM
L277	209	(neural near6 network) same4 (generat$8 deriv$8) near6 (password pass$1word passphrase pass$1phrase)	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/27 09:53 PM
L278	7	xenomorphic	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/27 09:56 PM
L279	650	unpredictab$8 near6 (cryptogra$8)	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/27 09:57 PM
L280	1138	unpredictab$8 near6 (cryptogra$8 encrypt$8)	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/27 09:57 PM
L281	5	unpredictab$8 near6 (cryptogra$8 encrypt$8) same4 (neural near6 network)	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/27 09:58 PM
L282	39	unpredictab$8 near6 (cryptogra$8 encrypt$8) AND (neural near6 network)	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/27 09:58 PM
L283	1	"20230050628".pn. AND rac$8 near6 (node keynode neural)	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/28 09:10 AM
L284	1	"20230050628".pn. AND (rac$8 rac$8 near6 (node keynode neural))	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/28 09:10 AM
L285	1	"20230050628".pn. AND (biome$8)	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/28 09:14 AM

Petitioner Samsung Ex-1004, 0388

L286	5	(eeg) near6 key WITH (genera$8 deriv$8) AND (cryptogra$8 encrypt$8)	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/28 09:47 AM
L287	6	(eeg electro$1encephal$8) near6 key WITH (genera$8 deriv$8) AND (cryptogra$8 encrypt$8)	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/28 09:49 AM
L288	6	(eeg electro$1encephal$8 electroencephal$8) near6 key WITH (genera$8 deriv$8) AND (cryptogra$8 encrypt$8)	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/28 09:49 AM
L289	1	"9672760".pn.	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/28 10:25 AM
L290	6	("20190163559" "20180027009").pn.	(US-PGPUB; USPAT; USOCR; FIT (AP, AT, AU, BE, BG, BR, BY, CA, CH, CN, CS, CU, CZ, DD, DK, EA, EE, ES, FI, FR, GB, HR, HU, ID, IE, IL, IS, IT, JP, KR, LT, LU, LV, MA, MC, MD, MY, NL, NO, NZ, PH, PL, PT, RO, RS, RU, SE, SG, SI, SK, SU, TH, TN, TR, TW, UA, VN, WO); FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2024/02/29 10:59 AM
L291	2	("20190163559" "20180027009").pn.	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/29 10:59 AM
L292	8226	(section portion segment fragment clip) near6 (video stream) near8 (user person) near8 (authori$8 authenti$8 credenti$8 map$8 associat$8)	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/01 09:10 AM
L293	7636	(section portion segment fragment clip) near6 (video stream) near8 (user person) near6 (authori$8 authenti$8 credenti$8 map$8 associat$8)	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/01 09:10 AM
L294	646	(distrib$8 transm$8 send sending sent) near8 (section portion segment fragment clip) near6 (video stream)	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/01 09:10 AM

Petitioner Samsung Ex-1004, 0389

		near8 (user person) near6 (authori$8 authenti$8 credenti$8 map$8 associat$8)					
L295	2039	(distrib$8 transm$8 send sending sent identif$8 determin$8) near8 (section portion segment fragment clip) near6 (video stream) near8 (user person) near6 (authori$8 authenti$8 credenti$8 map$8 associat$8)	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/01 09:11 AM
L296	265	(distrib$8 transm$8 send sending sent identif$8 determin$8) near8 (section portion segment fragment clip) near6 (video stream) near8 (user person) near6 (authori$8 authenti$8 credenti$8 map$8 associat$8) AND surve$8	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/01 09:12 AM
L297	265	(distrib$8 transm$8 send sending sent identif$8 determin$8) near8 (section portion segment fragment clip) near6 (video stream) near8 (user person) near6 (authori$8 authenti$8 credenti$8 map$8 associat$8) AND surve$9	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/01 09:12 AM
L298	21	cervetti.xp. AND surveillance	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/01 09:44 AM
L299	19	cervetti.xp. AND surveillance AND (authori$8 authentic$8 permiss$8 credenti$8 associat$8 personnel)	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/01 09:46 AM
L300	15	cervetti.xp. AND surveillance same4 (authori$8 authentic$8 permiss$8 credenti$8 associat$8 personnel)	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/01 09:46 AM
L301	271570	encrypt$8 near6 key near6 (vault storage device usb manager)	(US-PGPUB; USPAT; USOCR; FIT (AP, AT, AU, BE, BG, BR, BY, CA, CH, CN, CS, CU, CZ, DD, DK, EA, EE, ES, FI, FR, GB, HR, HU, ID, IE, IL, IS, IT,	OR	ON	ON	2024/02/27 09:05 PM

Petitioner Samsung Ex-1004, 0390

			JP, KR, LT, LU, LV, MA, MC, MD, MY, NL, NO, NZ, PH, PL, PT, RO, RS, RU, SE, SG, SI, SK, SU, TH, TN, TR, TW, UA, VN, WO); FPRS; EPO; JPO; DERWENT; IBM_TDB)				
L302	85553	encrypt$8 near6 key near6 (vault storage device usb manager)	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/27 09:05 PM
L303	6405	encrypt$8 near6 key near6 (vault storage device usb manager) WITH (case casing housing)	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/27 09:05 PM
L304	794	encrypt$8 near6 key near6 (vault storage device usb manager) WITH (case casing housing) WITH (authentic$8 authori$8)	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/27 09:06 PM
L305	489	encrypt$8 near6 key near6 (vault storage device usb manager) WITH (personal) WITH (authentic$8 authori$8)	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/27 09:15 PM
L306	1	"20230306106".pn. AND (network$8 protect$8 secur$8)	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/28 10:48 AM
L307	1	"20230306106".pn. AND (detect$8 determin$8)	(US-PGPUB; USPAT)	OR	ON	ON	2024/02/28 10:49 AM
L308	246	shared near4 secret near4 key.clm. AND elliptic near4 curve.clm.	(US-PGPUB; USPAT)	OR	ON	ON	2024/04/06 08:12 AM
L309	10	shared near4 secret near4 key.clm. AND elliptic near4 curve.clm. AND encrypted near4 profile.clm.	(US-PGPUB; USPAT)	OR	ON	ON	2024/04/06 08:12 AM
L310	68	(ecdh elliptic near4 curve) near8 key same4 encrypted near6 profile	(US-PGPUB; USPAT)	OR	ON	ON	2024/04/06 08:25 AM
L311	1	"20140082359".pn. AND (generat$8 deriv$8 calcula$8 comput$8)	(US-PGPUB; USPAT)	OR	ON	ON	2024/04/06 08:40 AM
L312	36	ansi near6 standard near4 key near6 derivation	(US-PGPUB; USPAT)	OR	ON	ON	2024/04/06 08:43 AM
L313	89	(euicc e$1uicc uicc universal near4 integrated) AND (ecdh	(US-PGPUB; USPAT)	OR	ON	ON	2024/04/06 08:46 AM

Petitioner Samsung Ex-1004, 0391

L314	89	elliptic near4 curve) near8 key AND encrypt$8 near6 profile (euicc e$1uicc uicc universal near4 integrated) AND (ecdh elliptic near4 curve) near8 key AND encrypt$8 near6 profile AND (private public) near6 key	(US-PGPUB; USPAT)	OR	ON	ON	2024/04/06 08:47 AM

PE2E SEARCH - Search History (Interference)

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	British Equivalents	Time Stamp
N183	162	(euicc e$1uicc uicc universal near4 integrated near4 (chip card circuit) smartcard smart$1card sim esim e$1sim subscrib$8 near4 identi$8 near4 module).clm. AND (public private pair) near6 key.clm. AND (authenti$8 authori$8 verif$8 valid$8 determin$8 identif$8) near6 (server gatekeeper gateway provider) near8 (shared secret preshared pre$1shared public private pair) near6 key.clm.	(US-PGPUB; USPAT)	OR	ON	ON	2024/03/08 12:50 PM

Petitioner Samsung Ex-1004, 0392

UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
18/229,907	08/03/2023	John A. Nix	63121/0224	7483

1912 7590 04/09/2024

AMSTER, ROTHSTEIN & EBENSTEIN LLP
405 LEXINGTON AVENUE
FLOOR 48
NEW YORK, NY 10174

EXAMINER
CERVETTI, DAVID GARCIA

ART UNIT	PAPER NUMBER
2419	

MAIL DATE	DELIVERY MODE
04/09/2024	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Office Action Summary	Application No. 18/229,907	Applicant(s) Nix, John A.	
	Examiner David García Cervetti	Art Unit 2419	AIA (FITF) Status Yes

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTHS FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

1)☑ Responsive to communication(s) filed on 28 March 2024.

☐ A declaration(s)/affidavit(s) under **37 CFR 1.130(b)** was/were filed on _____.

2a)☑ This action is **FINAL.** 2b) ☐ This action is non-final.

3)☐ An election was made by the applicant in response to a restriction requirement set forth during the interview on _____; the restriction requirement and election have been incorporated into this action.

4)☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims*

5) ☑ Claim(s) 23-42 is/are pending in the application.

5a) Of the above claim(s) _____ is/are withdrawn from consideration.

6) ☐ Claim(s) _____ is/are allowed.

7) ☑ Claim(s) 23-42 is/are rejected.

8) ☐ Claim(s) _____ is/are objected to.

9) ☐ Claim(s) _____ are subject to restriction and/or election requirement

* If any claims have been determined allowable, you may be eligible to benefit from the **Patent Prosecution Highway** program at a participating intellectual property office for the corresponding application. For more information, please see http://www.uspto.gov/patents/init_events/pph/index.jsp or send an inquiry to **PPHfeedback@uspto.gov.**

Application Papers

10)☐ The specification is objected to by the Examiner.

11)☑ The drawing(s) filed on 03 August 2023 is/are: a)☑ accepted or b)☐ objected to by the Examiner.

Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).

Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).

Priority under 35 U.S.C. § 119

12)☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).

Certified copies:

a)☐ All b)☐ Some** c)☐ None of the:

1.☐ Certified copies of the priority documents have been received.

2.☐ Certified copies of the priority documents have been received in Application No. _____.

3.☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

** See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

1) ☑ Notice of References Cited (PTO-892)

2) ☐ Information Disclosure Statement(s) (PTO/SB/08a and/or PTO/SB/08b) Paper No(s)/Mail Date _____.

3) ☐ Interview Summary (PTO-413) Paper No(s)/Mail Date _____.

4) ☐ Other: _____.

DETAILED ACTION

1. Applicant's amendment filed 3/28/2024 has been fully considered.

2. Claims 23-42 are pending and have been examined. Claims 1-22 have been canceled.

Notice of Pre-AIA or AIA Status

3. The present application, filed on or after March 16, 2013, is being examined under the first inventor to file provisions of the AIA.

Response to Amendment

4. The statutory double patenting rejection is withdrawn in view of the cancellation of claims 1-22.

Double Patenting

5. Claims 1-22 are provisionally rejected under the judicially created doctrine of obviousness-type double patenting as being unpatentable over claims of Patent No. 9319223, 9742562, 10187206, 10498530, 10700856, 11258595, 11736283, and 11082218. Although the conflicting claims are not identical, they are not patentably distinct from each other because

- "A method for a mobile device with an embedded universal integrated circuit card (eUICC) to securely communicate with a wireless network, the method performed by the mobile device, the method comprising:a) storing, in the eUICC, a first module private key, a corresponding first module public key, and a network public key; b) receiving, from a first server associated with the wireless network, an encrypted profile for the eUICC comprising cryptographic parameters, a module identity, and a key K;c) generating a shared secret key using a first elliptic curve Diffie-Hellman (ECDH) key exchange with the first module private key and the network public key; d) decrypting, with the shared secret key, at least a portion of the encrypted profile for the eUICC; e) generating, by the eUICC, a second module public key and a corresponding second module private key; f) sending, to a second server associated with the wireless network, the second module public key; g) generating a symmetric key using a second ECDH key exchange with the second module private key and the cryptographic parameters; h) generating, with the symmetric key, module encrypted data, the module encrypted data comprising the module identity; and i) sending, to the servers, the module encrypted data" (claim 23, instant application) is analogous to
- "A method for a module using an embedded universal integrated circuit card (eUICC) to derive a first shared secret key and a second shared secret key, the method comprising the module: storing a network public key and a module identity in the eUICC, wherein the module uses the network public key to authenticate an eUICC subscription manager; receiving a token for a key derivation function from the authenticated eUICC subscription manager; deriving a module private key and a module public key, wherein the module sends the derived module public key and the module identity to the eUICC subscription manager; deriving the first shared secret key using the key derivation function and a set of cryptographic parameters, wherein the key derivation function uses as input at least (i) the derived module private key, (ii) the set of cryptographic parameters, and (iii) the received token; deriving the second shared secret key using (i) a shared secret algorithm and (ii) the derived first shared secret key as a random number for the shared secret algorithm, wherein the shared secret algorithm uses a secure hash algorithm; and receiving an eUICC profile, wherein the eVICC uses the derived second shared secret key to decrypt the eUICC profile" (claim 1, patent 9319223) and analogous to
- "A method for a module using an embedded integrated circuit card (eUICC) to support authentication, the method comprising the module: reading a module identity from a protected memory and sending the module identity to an eUICC subscription manager; reading an eUICC subscription manager public key from the protected memory; authenticating the eUICC subscription manager using the eUICC subscription manager public key; receiving a first profile for the eUICC, wherein the first profile includes a first network module identity and a first key K, and wherein the module sends the module identity to the eUICC subscription manager before receiving the first profile; using the eUICC, the first network module identity, and the first key K to authenticate with a first wireless network; receiving from an eUICC subscription manager a server public key after authenticating with the first key K; deriving a shared secret key using (i) the received server public key, (ii) an eUICC private key, and (iii) a shared secret algorithm; receiving a second profile for the eUICC, wherein the module decrypts the second profile using the derived shared secret key, wherein the decrypted

second profile includes a second network module identity and a second key K; and authenticating with a second wireless network using the second network module identity and the second key K" (claim 1, patent 9742562), and analogous to

- "A method for securely distributing a profile from a subscription manager system to a module comprising the steps of: (a) recording, in memory operatively connected to the subscription manager system, a digital signature algorithm comprising an elliptic curve digital signature algorithm; (b) recording, by the memory operatively connected to the subscription manager system, a server private key and a corresponding server public key, wherein the server public key and the server private key use elliptic curve cryptography; (c) recording, by the memory operatively connected to the subscription manager system, a symmetric ciphering algorithm, wherein the symmetric ciphering algorithm comprises an Advanced Encryption Standard with a 128 bit key length; (d) receiving, by the subscription manager system, a certificate associated with the module from a module provider system associated with a module provider, wherein the certificate includes a module public key; (e) receiving, by the subscription manager system, a challenge from the module; (f) generating, by the subscription manager system, a network private key and a corresponding network public key, using a key pair generation algorithm; (g) sending the generated network public key to the module; and (h) sending a digital signature and the challenge to the module, wherein the digital signature is generated using the server private key and the digital signature algorithm; (i) generating, by the subscription manager system, a mutually derived shared key using Elliptic Curve Diffie-Hellman based on at least: (1) the module public key, and (2) the network private key; wherein the mutually derived shared key is derived by the module based on at least: (i) a module private key associated with the module public key, and (ii) the network public key; (j) encrypting, by the subscription manager system, the profile using: (1) the symmetric ciphering algorithm, and (2) the mutually derived shared key; (k) sending, from the subscription manager system to the module, the encrypted profile, wherein the profile includes network access credentials for a wireless network" (claim 1, patent 10187206) ", and analogous to
- "A module for securely communicating over a wireless network comprises: (1) one or more processors; and (2) a first non-transitory computer-readable memory operatively connected to the one or more processors, the first non-transitory computer-readable memory having stored thereon machine-readable instructions that, when executed by the one or more processors cause the one or more processors to perform a method comprising steps of: (a) recording in the first non-transitory computer-readable memory, at least the following: (i) a first set of parameters for a secure hash algorithm; (ii) a second set of parameters for an elliptic curve algorithm; and (iii) a first public key which corresponds to a first private key; (b) deriving a module private key and a corresponding module public key using the second set of parameters; (c) generating a first shared secret key using a first elliptic curve Diffie-Hellman key exchange, and based at least in part, on the first public key; (d) sending, to a first computing device which is connected to the wireless network, a first message including the derived module public key, wherein at least a portion of the first message is encrypted using a third set of parameters that is based on a symmetric ciphering algorithm and the derived first shared secret key; (e) receiving, from the first computing device, a second message comprising encrypted data, which is encrypted, by the first computing device, using the symmetric ciphering algorithm and a derived second shared secret key, wherein the second shared secret key is derived by the first computing device using a second elliptic curve Diffie-Hellman key exchange based at least, in part, on the derived module public key; and (f) decrypting the encrypted data using the third set of parameters and the derived second shared secret key" (claim 1, patent 10498530) ", and analogous to
- "A subscription manager system for distributing a profile to a module comprising: (1) one or more processors; and (2) first non-transitory computer-readable media operatively connected to the one or more processors and having stored thereon machine-readable instructions that, when executed by the one or more processors, cause the one or more processors to perform a method comprising steps of: (a) recording, in second non-transitory computer-readable media, a digital signature algorithm comprising an elliptic curve digital signature algorithm; (b) recording, in the second non-transitory computer-readable media, a module identity, a server private key, and a server certificate for a corresponding server public key, wherein the server public key and the server private key use the elliptic curve digital signature algorithm; (c) recording, in the second non-transitory computer-readable media, a symmetric ciphering algorithm, wherein the symmetric ciphering algorithm comprises an Advanced Encryption Standard with a 128 bit key length; (d) receiving a certificate associated with the module from a module provider system associated with a module provider, wherein the certificate includes the module identity, a module public key, and cryptographic parameters; (e) verifying the certificate associated with the module using a certificate authority; (f) sending, to the module, the server certificate, wherein the module verifies the server certificate using a certificate authority public key stored by the module; (g) receiving a challenge from the module; (h) generating a network private key and a corresponding network public key, using a key pair generation algorithm and the cryptographic parameters; (i) sending the generated network public key to the module; (j) sending a digital signature and the challenge to the module, wherein the digital signature is generated using the server private key, the challenge, and the digital signature algorithm, wherein the module verifies the digital signature using at least the server public key; (k) generating a mutually derived shared key using Elliptic Curve Diffie-Hellman based on at least: i. the module public key; ii. the network private key; and iii. the cryptographic parameters, wherein the mutually derived shared key is derived by the module based on at least: iv. a module private key associated with the module public key; v. the network public key; and vi. the cryptographic parameters; (l) encrypting the profile using: i. the symmetric ciphering algorithm, and ii. the mutually derived shared key; and (m) sending the encrypted profile, wherein the encrypted profile includes network access credentials for a wireless network" (claim 1, patent 10700856), and analogous to
- "A module with an embedded Universal Integrated Circuit Card (eUICC) comprising: (a) at least one processor; and (b) a memory operatively connected to the at least one processor, the memory including

processor executable code that, when executed by the at least one processor, performs the steps of: (1) recording, in the memory of the module, (i) a module public key and a corresponding module private key, (ii) a pre-shared secret key, (iii) a set of cryptographic parameters, and (iv) a module identity, (2) generating, by the module, module encrypted data associated with a first set of servers using the pre-shared secret key which is also separately accessible by the first set of servers, wherein the module encrypted data includes at least a portion of the set of cryptographic parameters; (3) storing, by the module in the memory, a network public key, wherein the network public key is associated with (i) a second set of servers and (ii) a network private key; (4) generating, by the module in the memory, a mutually derived shared key using Elliptical Curve Diffie Hellman, wherein the mutually derived shared key is derived by the module based on at least: (i) the module private key; and (ii) the network public key, wherein the mutually derived shared key can be derived by the second set of servers based on at least: (A) the module public key associated with the module private key; and (B) the network private key associated with the network public key; (5) receiving from the second set of servers an encrypted profile for the eUICC; and (6) decrypting the encrypted profile with the mutually derived shared key in order to store network access credentials" (claim 1, patent 11082218).

6. This is a provisional obviousness-type double patenting rejection because the conflicting claims of the instant application have not in fact been patented.

7. The claims of the conflicting patents and/or applications contain every element of claims 23-42 of the instant application and thus anticipate the claims of the instant application. Claims 23-42 of the instant application therefore are not patently distinct from the copending application claims and as such are unpatentable for obvious-type double patenting. A later patent/application claim is not patentably distinct from an earlier claim if the later claim is anticipated by the earlier claim.

8. "A later patent claim is not patentably distinct from an earlier patent claim if the later claim is obvious over, or anticipated by, the earlier claim. In re Longi, 759 F.2d at 896, 225 USPQ at 651 (affirming a holding of obviousness-type double patenting because the claims at issue were obvious over claims in four prior art patents); In re Berg, 140 F.3d at 1437, 46 USPQ2d at 1233 (Fed. Cir. 1998) (affirming a holding of obviousness-type double patenting where a patent application claim to a genus is anticipated by a patent claim to a species with that genus). "ELI LILLY AND COMPANY v BARR LABORATORIES, INC., United States Court of Appeals for the Federal Circuit, ON PETITION FOR REHEARING EN BANC (DECIDED: May 30, 2001).

9. "Claim 12 and Claim 13 are generic to the species of invention covered by claim 3 of the patent. Thus, the generic invention is "anticipated" by the species of the patented invention. Cf., Titanium Metals Corp. v. Banner, 778 F.2d 775, 227 USPQ 773 (Fed. Cir. 1985) (holding that an earlier species disclosure in the prior art defeats any generic claim) 4. This court's predecessor has held that, without a terminal disclaimer, the species claims preclude issuance of the generic claim. In re Van Ornum, 686 F.2d 937, 944, 214 USPQ 761, 767 (CCPA 1982); Schneller, 397 F.2d at 354. Accordingly, absent a terminal disclaimer, claims 12 and 13 were properly rejected under the doctrine of obviousness-type double patenting." (In re Goodman (CA FC) 29 USPQ2d 2010 (12/3/1993).

Conclusion

10. The prior art made of record and not relied upon is considered pertinent to applicant's disclosure.

Nakhjiri (20140082359).

11. **THIS ACTION IS MADE FINAL.** Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

12. A shortened statutory period for reply to this final action is set to expire THREE MONTHS from the mailing date of this action. In the event a first reply is filed within TWO MONTHS of the mailing date

of this final action and the advisory action is not mailed until after the end of the THREE-MONTH shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event, however, will the statutory period for reply expire later than SIX MONTHS from the mailing date of this final action.

13. Any inquiry concerning this communication or earlier communications from the examiner should be directed to David Garcia Cervetti whose telephone number is (571)272-5861. The examiner can normally be reached Monday-Friday 8AM-5PM.

14. Examiner interviews are available via telephone, in-person, and video conferencing using a USPTO supplied web-based collaboration tool. To schedule an interview, applicant is encouraged to use the USPTO Automated Interview Request (AIR) at http://www.uspto.gov/interviewpractice.

15. If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, HADI ARMOUCHE can be reached on (571)270-3618. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

16. Information regarding the status of published or unpublished applications may be obtained from Patent Center. Unpublished application information in Patent Center is available to registered users. To file and manage patent submissions in Patent Center, visit: https://patentcenter.uspto.gov. Visit https://www.uspto.gov/patents/apply/patent-center for more information about Patent Center and https://www.uspto.gov/patents/docx for information about filing in DOCX format. For additional questions, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

/David Garcia Cervetti/
Primary Examiner, Art Unit 2419

UNITED STATES
PATENT AND TRADEMARK OFFICE

P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

ACKNOWLEDGEMENT OF CHANGE TO SMALL ENTITY STATUS

APPLICATION #	FILING OR 371(C) DATE	FIRST NAMED APPLICANT	ATTORNEY DOCKET #	REQUEST ID
18/229,907	08/03/2023	John A. Nix	63121/0224	221569

The entity status change request below filed through Patent Center on 05/29/2024 has been accepted.

Certifications

APPLICANT ASSERTING SMALL ENTITY STATUS. See 37CFR 1.27.

Signature

I certify, in accordance with 37 CFR 1.4(d)(4), that I am one of the signatories making the entity status change.

Signature	Name	Registration #
/Charles R. Macedo/	Charles Macedo	32781

PTO/SB/06 (09-11)
Approved for use through 1/31/2014. OMB 0651-0032
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

PATENT APPLICATION FEE DETERMINATION RECORD Substitute for Form PTO-875	Application or Docket Number 18/229,907	Filing Date 08/03/2023	☐ To be Mailed

ENTITY: ☐ LARGE ☑ SMALL ☐ MICRO

APPLICATION AS FILED - PART I

FOR	(Column 1) NUMBER FILED	(Column 2) NUMBER EXTRA		RATE ($)	FEE ($)
☐ BASIC FEE (37 CFR 1.16(a), (b), or (c))	N/A	N/A		N/A	
☐ SEARCH FEE (37 CFR 1.16(k), (i), or (m))	N/A	N/A		N/A	
☐ EXAMINATION FEE (37 CFR 1.16(o), (p), or (q))	N/A	N/A		N/A	
TOTAL CLAIMS (37 CFR 1.16(i))	minus 20 =	*		x $40 =	
INDEPENDENT CLAIMS (37 CFR 1.16(h))	minus 3 =	*		x $192 =	
☐ APPLICATION SIZE FEE (37 CFR 1.16(s))	If the specification and drawings exceed 100 sheets of paper, the application size fee due is $310 ($155 for small entity) for each additional 50 sheets or fraction thereof. See 35 U.S.C. 41(a)(1)(G) and 37 CFR 1.16(s).				
☐ MULTIPLE DEPENDENT CLAIM PRESENT (37 CFR 1.16(j))					
* If the difference in column 1 is less than zero, enter "0" in column 2.				TOTAL	

APPLICATION AS AMENDED - PART II

		(Column 1)		(Column 2)	(Column 3)			
AMENDMENT	05/29/2024	CLAIMS REMAINING AFTER AMENDMENT		HIGHEST NUMBER PREVIOUSLY PAID FOR	PRESENT EXTRA		RATE ($)	ADDITIONAL FEE ($)
	Total (37 CFR 1.16(i))	* 20	Minus	** 22	= 0		x $40 =	0
	Independent (37 CFR 1.16(h))	* 1	Minus	*** 2	= 0		x $192 =	0
	☐ Application Size Fee (37 CFR 1.16(s))							
	☐ FIRST PRESENTATION OF MULTIPLE DEPENDENT CLAIM (37 CFR 1.16(j))							
							TOTAL ADD'L FEE	0

		(Column 1)		(Column 2)	(Column 3)			
AMENDMENT		CLAIMS REMAINING AFTER AMENDMENT		HIGHEST NUMBER PREVIOUSLY PAID FOR	PRESENT EXTRA		RATE ($)	ADDITIONAL FEE ($)
	Total (37 CFR 1.16(i))	*	Minus	**	=		x $0 =	
	Independent (37 CFR 1.16(h))	*	Minus	***	=		x $0 =	
	☐ Application Size Fee (37 CFR 1.16(s))							
	☐ FIRST PRESENTATION OF MULTIPLE DEPENDENT CLAIM (37 CFR 1.16(j))							
							TOTAL ADD'L FEE	

* If the entry in column 1 is less than the entry in column 2, write "0" in column 3.	LIE
** If the "Highest Number Previously Paid For" IN THIS SPACE is less than 20, enter "20".	/DORIS M KING/
*** If the "Highest Number Previously Paid For" IN THIS SPACE is less than 3, enter "3".	
The "Highest Number Previously Paid For" (Total or Independent) is the highest number found in the appropriate box in column 1.	

This collection of information is required by 37 CFR 1.16. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 12 minutes to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.**

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

UNITED STATES
PATENT AND TRADEMARK OFFICE

P.O. Box 1450
Alexandria, VA 22313 - 1450
www.uspto.gov

TERMINAL DISCLAIMER TO OBVIATE A DOUBLE PATENTING REJECTION OVER A PRIOR PATENT

APPLICATION #	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET #
18229907	08/03/2023	John Nix	63121/0224

Title of Invention

Key Derivation for a Module Using an Embedded Universal Integrated Circuit Card

☑ Filing of terminal disclaimer does not obviate requirement for response under 37 CFR 1.111 to outstanding Office Action

☑ This electronic Terminal Disclaimer is not being used for a Joint Research Agreement.

Owner	Percent interest
Network-1 Technologies, Inc.	100%
Total	100%

The owner(s) of percent interest listed above in the instant application hereby disclaims, except as provided below, the terminal part of the statutory term of any patent granted on the instant application which would extend beyond the expiration date of the full statutory term of any patent granted on pending reference Application Number(s)

Application #	Filing Date

as the term of any patent granted on said reference application may be shortened by any terminal disclaimer filed prior to the grant of any patent on the pending reference application. The owner hereby agrees that any patent so granted on the instant application shall be enforceable only for and during such period that it and any patent granted on the reference application are commonly owned. This agreement runs with any patent granted on the

instant application and is binding upon the grantee, its successors or assigns.
In making the above disclaimer, the owner does not disclaim the terminal part of any patent granted on the instant application that would extend to the expiration date of the full statutory term of any patent granted on said reference application, "as the term of any patent granted on said reference application may be shortened by any terminal disclaimer filed prior to the grant of any patent on the pending reference application," in the event that any such patent granted on the pending reference application: expires for failure to pay a maintenance fee, is held unenforceable, is found invalid by a court of competent jurisdiction, is statutorily disclaimed in whole or terminally disclaimed under 37 CFR 1.321, has all claims canceled by a reexamination certificate, is reissued, or is in any manner terminated prior to the expiration of its full statutory term as shortened by any terminal disclaimer filed prior to its grant.

The owner(s) of percent interest listed above in the instant application hereby disclaims, except as provided below, the terminal part of the statutory term of any patent granted on the instant application which would extend beyond the expiration date of the full statutory term of prior patent number(s)

Patent #
9319223
9742562
10187206
10498530
10700856
11258595
11736283
11082218

as the term of said prior patent is presently shortened by any terminal disclaimer. The owner hereby agrees that any patent so granted on the instant application shall be enforceable only for and during such period that it and the prior patent are commonly owned. This agreement runs with any patent granted on the instant application and is binding upon the grantee, its successors or assigns.
In making the above disclaimer, the owner does not disclaim the terminal part of the term of any patent granted on the instant application that would extend to the expiration date of the full statutory term of the prior patent, "as the term of said prior patent is presently shortened by any terminal disclaimer," in the event that said prior patent later:
• expires for failure to pay a maintenance fee;
• is held unenforceable;
• is found invalid by a court of competent jurisdiction;
• is statutorily disclaimed in whole or terminally disclaimed under 37 CFR 1.321;

- has all claims canceled by a reexamination certificate;
- is reissued; or
- is in any manner terminated prior to the expiration of its full statutory term as presently shortened by any terminal disclaimer.

Terminal disclaimer fee under 37 CFR 1.20(d) included with Electronic Terminal Disclaimer request.

Applicant claims the following entity status:
Small

I hereby declare that all statements made herein of my own knowledge are true and that all statemnts made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

I certify, in accordance with 37 CFR 1.4(d)(4) that I am: An attorney or agent registered to practice before the Patent and Trademark Office who is of record in this application

Signature	Name	Registration #
/Keith J Barkaus/	Keith Barkaus	51431

---

* Statement under 37 CFR 3.73(b) is required if terminal disclaimer is signed by the assignee (owner). Form PTO/SB/96 may be used for making this certification. See MPEP 324.

UNITED STATES
PATENT AND TRADEMARK OFFICE

Commissioner for Patents
United States Patent and Trademark Office
P.O. Box 1450
Alexandria, VA 22313 - 1450
www.uspto.gov

APPROVAL LETTER

APPLICATION #	FILING DATE	APPLICANT/PATENT UNDER REEXAMINATION
18/229,907	08/03/2023	John Nix

Title of Invention

Key Derivation for a Module Using an Embedded Universal Integrated Circuit Card

Electronic terminal disclaimer filed on 05/29/2024

☑ Approved

This patent is subject to a Terminal Disclaimer

Approved / Disapproved by: Electronic Terminal Disclaimer automatically approved

UNITED STATES
PATENT AND TRADEMARK OFFICE

P.O. Box 1450
Alexandria, VA 22313 - 1450
www.uspto.gov

ELECTRONIC PAYMENT RECEIPT

APPLICATION #	RECEIPT DATE / TIME	ATTORNEY DOCKET #
18/229,907	05/29/2024 05:47:03 PM Z ET	63121/0224

Title of Invention

Key Derivation for a Module Using an Embedded Universal Integrated Circuit Card

Application Information

APPLICATION TYPE	Utility - Nonprovisional Application under 35 USC 111(a)	PATENT #	-
CONFIRMATION #	7483	FILED BY	Victoria GILMORE
PATENT CENTER #	65717733	AUTHORIZED BY	Keith Barkaus
CUSTOMER #	1912	FILING DATE	08/03/2023
CORRESPONDENCE ADDRESS	-	FIRST NAMED INVENTOR	John A. Nix

Payment Information

PAYMENT METHOD	PAYMENT TRANSACTION ID	PAYMENT AUTHORIZED BY
CARD / 1044	E20245SH48006653	Keith Barkaus

FEE CODE	DESCRIPTION	ITEM PRICE($)	QUANTITY	ITEM TOTAL($)
2814	STATUTORY DISCLAIMER, INCLUDING TERMINAL DISCLAIMER	170.00	1	170.00
			TOTAL AMOUNT:	$170.00

This Acknowledgement Receipt evidences receipt on the noted date by the USPTO of the indicated documents, characterized by the applicant, and including page counts, where applicable. It serves as evidence of receipt similar to a Post Card, as described in MPEP 503.

New Applications Under 35 U.S.C. 111

If a new application is being filed and the application includes the necessary components for filing date (see 37 CFR 1.53(b)-(d) and MPEP 506), a Filing Receipt (37 CFR 1.54) will be issued in due course and the date shown on this Acknowledgement Receipt will establish the filing date of the application.

National Stage of an International Application under 35 U.S.C. 371

If a timely submission to enter the national stage of an international application is compliant with the conditions of 35 U.S.C. 371 and other applicable requirements a Form PCT/DO/EO/903 indicating acceptance of the application as a national stage submission under 35 U.S.C. 371 will be issued in addition to the Filing Receipt, in due course.

New International Application Filed with the USPTO as a Receiving Office

If a new international application is being filed and the international application includes the necessary components for an international filing date (see PCT Article 11 and MPEP 1810), a Notification of the International Application Number and of the International Filing Date (Form PCT/RO/105) will be issued in due course, subject to prescriptions concerning national security, and the date shown on this Acknowledgement Receipt will establish the international filing date of the application.

UNITED STATES
PATENT AND TRADEMARK OFFICE

P.O. Box 1450
Alexandria, VA 22313 - 1450
www.uspto.gov

ELECTRONIC ACKNOWLEDGEMENT RECEIPT

APPLICATION #	RECEIPT DATE / TIME	ATTORNEY DOCKET #
18/229,907	**05/29/2024 05:47:03 PM Z ET**	**63121/0224**

Title of Invention

Key Derivation for a Module Using an Embedded Universal Integrated Circuit Card

Application Information

APPLICATION TYPE	Utility - Nonprovisional Application under 35 USC 111(a)	PATENT #	-
CONFIRMATION #	7483	FILED BY	Victoria GILMORE
PATENT CENTER #	65717733	FILING DATE	08/03/2023
CUSTOMER #	1912	FIRST NAMED INVENTOR	John A. Nix
CORRESPONDENCE ADDRESS	-	AUTHORIZED BY	Keith Barkaus

Documents

TOTAL DOCUMENTS: 2

DOCUMENT	PAGES	DESCRIPTION	SIZE (KB)
petition-request.pdf	3	Terminal Disclaimer-Filed (Electronic)	52 KB
grantLetter.pdf	1	Terminal Disclaimer-Electronic-Approved	19 KB

Digest

DOCUMENT	MESSAGE DIGEST(SHA-512)
petition-request.pdf	911FA3AF16501D2C4E9EC5A6E4F71456FC459F83874CF9CBA DDBEB1147493D16902D091C811ADCCE2E18A28681F6CF7489

	48FD053C49DE465859C62CB6FE9C24
grantLetter.pdf	CE37CC2CB33AB187536B23F84F745B8A36382422040CEF3424004FD006A6E718A410F1F30020908A07D58C5BFD5944D28E5FC73E8ADCBDFF29686F9F2B1940DB

This Acknowledgement Receipt evidences receipt on the noted date by the USPTO of the indicated documents, characterized by the applicant, and including page counts, where applicable. It serves as evidence of receipt similar to a Post Card, as described in MPEP 503.

New Applications Under 35 U.S.C. 111

If a new application is being filed and the application includes the necessary components for filing date (see 37 CFR 1.53(b)-(d) and MPEP 506), a Filing Receipt (37 CFR 1.54) will be issued in due course and the date shown on this Acknowledgement Receipt will establish the filing date of the application.

National Stage of an International Application under 35 U.S.C. 371

If a timely submission to enter the national stage of an international application is compliant with the conditions of 35 U.S.C. 371 and other applicable requirements a Form PCT/DO/EO/903 indicating acceptance of the application as a national stage submission under 35 U.S.C. 371 will be issued in addition to the Filing Receipt, in due course.

New International Application Filed with the USPTO as a Receiving Office

If a new international application is being filed and the international application includes the necessary components for an international filing date (see PCT Article 11 and MPEP 1810), a Notification of the International Application Number and of the International Filing Date (Form PCT/RO/105) will be issued in due course, subject to prescriptions concerning national security, and the date shown on this Acknowledgement Receipt will establish the international filing date of the application.

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant:	Network-1 Technologies, Inc.	Confirmation No.: 7483
Title:	Key Derivation for a Module Using an Embedded Universal Integrated Circuit Card	
Appl. No.:	18/229,907	
Filing Date:	August 3, 2023	
Examiner:	Cervetti, David Garcia	
Art Unit:	2419	
Docket No.:	63121/0224	
Customer No.:	01912	

RESPONSE TO FINAL OFFICE ACTION DATED APRIL 9, 2024

VIA EFS

Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

Sir:

This is a response to the Office Action dated April 9, 2024. A response to this Office Action is due on July 9, 2024. Accordingly, the present Amendment is being timely filed.

A Listing of the Claims begins on page **2** of this paper.

Remarks begin on page **6** of this paper.

Petitioner Samsung Ex-1004, 0409

IN THE CLAIMS

This Listing of Claims will replace all prior versions, and listings, of claims in the application:

1-22 (Cancelled)

23. (Previously Presented) A method for a mobile device with an embedded universal integrated circuit card (eUICC) to securely communicate with a wireless network, the method performed by the mobile device, the method comprising:

a) storing, in the eUICC, a first module private key, a corresponding first module public key, and a network public key;

b) receiving, from a first server associated with the wireless network, an encrypted profile for the eUICC comprising cryptographic parameters, a module identity, and a key K;

c) generating a shared secret key using a first elliptic curve Diffie-Hellman (ECDH) key exchange with the first module private key and the network public key;

d) decrypting, with the shared secret key, at least a portion of the encrypted profile for the eUICC;

e) generating, by the eUICC, a second module public key and a corresponding second module private key;

f) sending, to a second server associated with the wireless network, the second module public key;

g) generating a symmetric key using a second ECDH key exchange with the second module private key and the cryptographic parameters;

h) generating, with the symmetric key, module encrypted data, the module encrypted data comprising the module identity; and

i) sending, to the servers, the module encrypted data.

24. (Previously Presented) The method of claim 23, wherein the module identity comprises an international mobile subscriber identity (IMSI).

Petitioner Samsung Ex-1004, 0410

25. (Previously Presented) The method of claim 23, wherein the module identity comprises a permanent identifier for the mobile device.

26. (Previously Presented) The method of claim 23, wherein the cryptographic parameters comprise an identifier for a set of cryptographic parameters.

27. (Previously Presented) The method of claim 23, further comprising in step c) deriving the shared secret key using an American National Standards Institute (ANSI) standard X-9.63 key derivation function.

28. (Previously Presented) The method of claim 23, further comprising in step g) deriving the symmetric key using an ANSI standard X-9.63 key derivation function.

29. (Previously Presented) The method of claim 23, wherein the first server mutually derives the shared secret key using the first ECDH key exchange with the first module public key and a network private key corresponding to the network public key.

30. (Previously Presented) The method of claim 23, further comprising in step e), generating, by the eUICC, the second module public key and the second module private key using a random number generator and input from a sensor.

31. (Previously Presented) The method of claim 23, further comprising in step h) generating, with the symmetric key and an Advanced Encryption Standard (AES), the module encrypted data.

32. (Previously Presented) The method of claim 23, wherein steps g) and h) occur before step f).

Petitioner Samsung Ex-1004, 0411

33. (Previously Presented) The method of claim 23, wherein the network public key is associated with an eUICC subscription manager.

34. (Previously Presented) The method of claim 33, wherein (i) the eUICC subscription manager comprises the first server.

35. (Previously Presented) The method of claim 23, further comprising: j) receiving, from the wireless network, a random number (RAND) and generating a response (RES) using the RAND and the key K.

36. (Previously Presented) The method of claim 23, further comprising before step b), authenticating the first server by (i) receiving a server digital signature and (ii) verifying the server digital signature with a server public key.

37. (Previously Presented) The method of claim 23, further comprising (i) in step a), storing a server name for the first server and a port number in a nonvolatile memory of the eUICC, and (ii) before step b) sending the first module public key to the first server.

38. (Previously Presented) The method of claim 23, wherein the first server, the second server, and the wireless network are associated with a mobile network operator.

39. (Previously Presented) The method of claim 23, wherein the eUICC comprises a processor, firmware, and protected memory.

40. (Previously Presented) The method of claim 23, wherein the cryptographic parameters include a base point G for an elliptic curve.

41. (Previously Presented) The method of claim 23, wherein the mobile device comprises a wireless device with a radio for communicating with a plurality of base stations for the wireless network.

Petitioner Samsung Ex-1004, 0412

42. (Previously Presented) The method of claim 23, wherein the eUICC comprises a package soldered to a circuit board of the mobile device.

Petitioner Samsung Ex-1004, 0413

REMARKS

This is a response to the Office Action dated April 9, 2024. A response to this Office Action is due on June 11, 2024. Claims 23-42 are pending in the present application with claim 23 being is in independent form. No new matter has been added by the present Amendment.

In view of the below remarks, Applicant respectfully asserts that claims 23-42 are in condition for allowance.

In the event that the Examiner disagrees, Applicant respectfully requests that the Examiner contact Applicant's undersigned attorney by telephone prior to issuing another Office Action.

I. Provisional Double Patenting

Claims 23-42 are provisionally rejected under the judicially created doctrine of obviousness-type double patenting as allegedly being unpatentable over the claims of U.S. Patent Nos. 9,319,223; 9,742,562; 10,187,206; 10,498,530; 10,700,856; 11,258,595, 11,082,218 and 11,736,283. Office Action, pgs. 2-5.

While Applicant does not necessarily agree with the Examiner's double patenting rejections as set forth above, in an effort to advance prosecution of the present application, Applicant submits herewith a terminal disclaimer with respect to each of U.S. Patent Nos. 9,319,223; 9,742,562; 10,187,206; 10,498,530; 10,700,856; 11,258,595, 11,082,218 and 11,736,283 to overcome this rejection. Applicant respectfully submits that claims 23-42 are patentably distinct from the claims of the above patents.

Accordingly, Applicant respectfully requests withdrawal of the provisional double patenting rejection.

As there are no other rejections in the Office Action, Applicant respectfully submits that claims 23-42 are allowable over the cited art and are in condition for allowance.

II. Reference to Related Patents and Co-Pending Applications

The below chart provides information regarding related issued patents and co-pending applications filed by the present Applicant:

Petitioner Samsung Ex-1004, 0414

Serial No.	Attorney Docket No.	Filing Date	Status
18/229,907	**63121/0224**	**2023-08-03**	**(Present Application) Pending - Case Docketed to Examiner**
18/111,669	63121/0222	2023-02-20	Non-Final OA mailed 2023-10-02
17/647,812	63121/0213	2022-01-13	USP 11,606,204
17/547,990	63121/0212	2021-12-10	USP 11,736,283
17/304,922	63121/0209	2021-06-28	USP 11,736,283
17/249,242	63121/0202	2021-02-24	Response to Non-Final OA filed 2023-11-13
16/879,325	63121/0198	2020-05-20	USP 11,082,218
16/843,107	63121/0197	2020-04-08	USP 11,283,603
16/721,153	63121/0195	2019-12-19	USP 11,539,681
16/593,561	63121/0190	2019-10-04	USP 11,258,595
16/453,682	63121/0184	2019-06-26	USP 11,233,780
16/271,455	63121/0181	2019-02-08	USP 10,594,679
16/271,428	63121/0180	2019-02-08	USP 10,523,432
16/201,401	63121/0179	2018-11-27	USP 10,700,856
16/200,118	63121/0178	2018-11-26	USP 10,498,530
16/110,804	63121/0168	2018-08-23	USP 10,382,422
16/036,506	63121/0167	2018-07-16	USP 10,530,575
15/983,957	63121/0163	2018-05-18	USP 10,177,911
15/973,012	63121/0162	2018-05-07	USP 10,250,386
15/972,914	63121/0161	2018-05-07	USP 10,652,017
15/928,848	63121/0160	2018-03-22	USP 10,084,768
15/010,905	63121/0157	2016-01-29	USP 9,641,327
15/680,758	63121/0147	2017-08-18	USP 10,187,206
15/162,292	63121/0146	2016-05-23	USP 10,362,012
14/751,119	63121/0145	2015-06-25	USP 9,961,060
15/457,700	63121/0144	2017-03-13	USP 9,998,281
15/583,968	63121/0143	2017-05-01	USP 10,057,059
15/043,293	63121/0142	2016-02-12	USP 9,998,280
15/642,088	63121/0141	2017-07-05	USP 10,003,461
15/130,146	63121/0140	2016-04-15	USP 9,742,562
15/162,302	63121/0139	2016-05-23	USP 9,698,981
14/789,255	63121/0138	2015-07-01	USP 9,596,078
14/139,419	63121/0137	2013-12-23	USP 9,351,162
14/136,711	63121/0136	2013-12-20	USP 9,300,473
14/099,329	63121/0135	2013-12-06	USP 9,100,175

Petitioner Samsung Ex-1004, 0415

14/084,141	63121/0134	2013-11-19	USP 9,319,223
14/064,618	63121/0133	2013-10-28	USP 9,118,464
14/055,606	63121/0132	2013-10-16	USP 9,276,740
14/039,401	63121/0131	2013-09-27	USP 9,288,059
14/023,181	63121/0130	2013-09-10	USP 9,350,550
AU 2019246774	63121-0199	2019-10-08	AU2019246774A1 Issued 2021-09-23
GB 1608573	63121-0151	2014-10-27	Published on 2016-08-03
GB 2100530	63121-0201	2014-10-27	Published on 2021-05-12
CA 2,965,119	63121-0152	2014-10-27	Published on 2015-05-07
HK 17101082.8	63121-0153	2014-10-27	Published on 2017-10-20
EU 14868381.6	63121-0154	2014-12-04	Published on 2017-01-04
CA 2,969,829	63121-0155	2014-12-04	Published on 2015-06-11
HK 17106540.3	63121-0156	2014-12-04	Published on 2018-01-19

The Examiner is invited to review the prosecution history of each of these applications, including the cited references of record and related office actions, as the Examiner deems appropriate.

Favorable reconsideration of the present application is respectfully requested.

If any fees are required in view of the foregoing, the Director is hereby authorized to charge any such fee to Deposit Account No. 01-1785.

Respectfully submitted,

AMSTER, ROTHSTEIN & EBENSTEIN LLP
Attorneys for Applicant
405 Lexington Avenue
New York, NY 10174
(212) 336-8000

Dated: New York, New York
May 29, 2024

By: /Keith J. Barkaus/
Keith J. Barkaus
Registration No. 51,431

4872-9484-8950v.1

Petitioner Samsung Ex-1004, 0416

UNITED STATES
PATENT AND TRADEMARK OFFICE

P.O. Box 1450
Alexandria, VA 22313 - 1450
www.uspto.gov

ELECTRONIC ACKNOWLEDGEMENT RECEIPT

APPLICATION #	RECEIPT DATE / TIME	ATTORNEY DOCKET #
18/229,907	**05/29/2024 05:51:01 PM Z ET**	**63121/0224**

Title of Invention

Key Derivation for a Module Using an Embedded Universal Integrated Circuit Card

Application Information

APPLICATION TYPE	Utility - Nonprovisional Application under 35 USC 111(a)	PATENT #	-
CONFIRMATION #	7483	FILED BY	Victoria GILMORE
PATENT CENTER #	65723181	FILING DATE	08/03/2023
CUSTOMER #	1912	FIRST NAMED INVENTOR	John A. Nix
CORRESPONDENCE ADDRESS	-	AUTHORIZED BY	Keith Barkaus

Documents

TOTAL DOCUMENTS: 3

DOCUMENT		PAGES	DESCRIPTION	SIZE (KB)
1-Response to FOA.pdf		8	-	170 KB
1-Response to FOA-A.NE.pdf	(1-1)	1	Response After Final Action	121 KB
1-Response to FOA-CLM.pdf	(2-5)	4	Claims	126 KB
1-Response to FOA-REM.pdf	(6-8)	3	Applicant Arguments/Remarks Made in an Amendment	170 KB

Digest

DOCUMENT	MESSAGE DIGEST(SHA-512)
1-Response to FOA.pdf	7ED68DD18587E5C95D3632C52C711C96CBE129E13E91DA5F D27BAD36F4283B2FCEB0F4BB0CED14C0EE760621EAE3738F 8479FAEFBE6DDFC8CC2758D509CA99E3
1-Response to FOA-A.NE.pdf	AF307B55743959B62CF81E72E9D76AA3B700B0938E503AA6B B1ADD27B3E05B0E6EB2475262618 9AB8282C1FA734856684D 4AF78CDB722DAB58F778D77C2AAC90
1-Response to FOA-CLM.pdf	539EF7088AD995AB5BD8721D5A982FF7B3D34455D829E83A6 AF75987AAB7B37F9BD8879B18973E9EE0111F6301FD37116C A1F9D8D00414D1C1772A287F06D393
1-Response to FOA-REM.pdf	93A84D3C1029B7A8E9F8D2214FA2681AC494247E0CCF65525 3947D69884B68C53793CD7C13F4346FE6E6C385B8DE44D9DB 2279E4EBDF2FFED46079F32861586D

This Acknowledgement Receipt evidences receipt on the noted date by the USPTO of the indicated documents, characterized by the applicant, and including page counts, where applicable. It serves as evidence of receipt similar to a Post Card, as described in MPEP 503.

New Applications Under 35 U.S.C. 111

If a new application is being filed and the application includes the necessary components for filing date (see 37 CFR 1.53(b)-(d) and MPEP 506), a Filing Receipt (37 CFR 1.54) will be issued in due course and the date shown on this Acknowledgement Receipt will establish the filing date of the application.

National Stage of an International Application under 35 U.S.C. 371

If a timely submission to enter the national stage of an international application is compliant with the conditions of 35 U.S.C. 371 and other applicable requirements a Form PCT/DO/EO/903 indicating acceptance of the application as a national stage submission under 35 U.S.C. 371 will be issued in addition to the Filing Receipt, in due course.

New International Application Filed with the USPTO as a Receiving Office

If a new international application is being filed and the international application includes the necessary components for an international filing date (see PCT Article 11 and MPEP 1810), a Notification of the International Application Number and of the International Filing Date (Form PCT/RO/105) will be issued in due course, subject to prescriptions concerning national security, and the date shown on this Acknowledgement Receipt will establish the international filing date of the application.

UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
18/229,907	08/03/2023	John A. Nix	63121/0224	7483

1912 7590 06/25/2024

AMSTER, ROTHSTEIN & EBENSTEIN LLP
405 LEXINGTON AVENUE
FLOOR 48
NEW YORK, NY 10174

EXAMINER
CERVETTI, DAVID GARCIA

ART UNIT	PAPER NUMBER
2419	

MAIL DATE	DELIVERY MODE
06/25/2024	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Advisory Action Before the Filing of an Appeal Brief	**Application No.** 18/229,907	**Applicant(s)** Nix, John A.	
	Examiner David García Cervetti	**Art Unit** 2419	**AIA (FITF) Status** Yes

--The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

THE REPLY FILED 29 May 2024 FAILS TO PLACE THIS APPLICATION IN CONDITION FOR ALLOWANCE.

NO NOTICE OF APPEAL FILED

1. ☑ The reply was filed after a final rejection. No Notice of Appeal has been filed. To avoid abandonment of this application, applicant must timely file one of the following replies: (1) an amendment, affidavit, or other evidence, which places the application in condition for allowance; (2) a Notice of Appeal (with appeal fee) in compliance with 37 CFR 41.31; or (3) a Request for Continued Examination (RCE) in compliance with 37 CFR 1.114 if this is a utility or plant application. Note that RCEs are not permitted in design applications. The reply must be filed within one of the following time periods:
   a) ☐ The period for reply expires ____ months from the mailing date of the final rejection.
   b) ☑ The period for reply expires on: (1) the mailing date of this Advisory Action; or (2) the date set forth in the final rejection, whichever is later. In no event, however, will the statutory period for reply expire later than SIX MONTHS from the mailing date of the final rejection.
   c) ☐ A prior Advisory Action was mailed more than 3 months after the mailing date of the final rejection in response to a first after-final reply filed within 2 months of the mailing date of the final rejection.The current period for reply expires ____ months from the mailing date of *the prior Advisory Action* or SIX MONTHS from the mailing date of the final rejection, whichever is earlier.
   Examiner Note: If box 1 is checked, check either box (a), (b) or (c). ONLY CHECK BOX (b) WHEN THIS ADVISORY ACTION IS THE FIRST RESPONSE TO APPLICANTS FIRST AFTER-FINAL REPLY WHICH WAS FILED WITHIN TWO MONTHS OF THE FINAL REJECTION. ONLY CHECK BOX (c) IN THE LIMITED SITUATION SET FORTH UNDER BOX (c). See MPEP 706.07(f).

Extensions of time may be obtained under 37 CFR 1.136(a). The date on which the petition under 37 CFR 1.136(a) and the appropriate extension fee have been filed is the date for purposes of determining the period of extension and the corresponding amount of the fee. The appropriate extension fee under 37 CFR 1.17(a) is calculated from: (1) the expiration date of the shortened statutory period for reply originally set in the final Office action; or (2) as set forth in (b) or (c) above, if checked. Any reply received by the Office later than three months after the mailing date of the final rejection, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

NOTICE OF APPEAL

2. ☐ The Notice of Appeal was filed on _____. A brief in compliance with 37 CFR 41.37 must be filed within two months of the date of filing the Notice of Appeal (37 CFR 41.37(a)), or any extension thereof (37 CFR 41.37(e)), to avoid dismissal of the appeal. Since a Notice of Appeal has been filed, any reply must be filed within the time period set forth in 37CFR 41.37(a).

AMENDMENTS

3. ☐ The proposed amendments filed after a final rejection, but prior to the date of filing a brief, will not be entered because
   a) ☐ They raise new issues that would require further consideration and/or search (see NOTE below);
   b) ☐ They raise the issue of new matter (see NOTE below);
   c) ☐ They are not deemed to place the application in better form for appeal by materially reducing or simplifying the issues for appeal; and/or
   d) ☐ They present additional claims without canceling a corresponding number of finally rejected claims.
   NOTE: _____ (See 37 CFR 1.116 and 41.33(a)).
4. ☐ The amendments are not in compliance with 37 CFR 1.121. See attached Notice of Non-Compliant Amendment (PTOL-324).
5. ☐ Applicant's reply has overcome the following rejection(s): _____
6. ☐ Newly proposed or amended claim(s) _____ would be allowable if submitted in a separate, timely filed amendment canceling the non-allowable claim(s).
7. ☑ For purposes of appeal, the proposed amendment(s):(a) ☑ will not be entered, or (b) ☐ will be entered, and an explanation of how the new or amended claims would be rejected is provided below or appended.

AFFIDAVIT OR OTHER EVIDENCE

8. ☐ A declaration(s)/affidavit(s) under **37 CFR 1.130(b)** was/were filed on _____
9. ☐ The affidavit or other evidence filed after final action, but before or on the date of filing a Notice of Appeal will not be entered because applicant failed to provide a showing of good and sufficient reasons why the affidavit or other evidence is necessary and was not earlier presented. See 37 CFR 1.116(e).
10. ☐ The affidavit or other evidence filed after the date of filing the Notice of Appeal, but prior to the date of filing a brief, will not be entered because the affidavit or other evidence failed to overcome all rejections under appeal and/or appellant fails to provide a showing of good and sufficient reasons why it is necessary and was not earlier presented. See 37 CFR 41.33(d)(1).
11. ☐ The affidavit or other evidence is entered. An explanation of the status of the claims after entry is below or attached.

REQUEST FOR RECONSIDERATION/OTHER

12. ☑ The request for reconsideration has been considered but does NOT place the application in condition for allowance because: See Continuation Sheet.
13. ☐ Note the attached Information *Disclosure Statement*(s). (PTO/SB/08) Paper No(s). _____
14. ☐ Other: _____.

STATUS OF CLAIMS

15. The status of the claim(s) is (or will be) as follows:
    Claim(s) allowed:_____.
    Claim(s) objected to:_____.
    Claim(s) rejected:23-42.
    Claim(s) withdrawn from consideration:_____.

/David Garcia Cervetti/ Primary Examiner, Art Unit 2419	

Petitioner Samsung Ex-1004, 0420

Continuation of REQUEST FOR RECONSIDERATION/OTHER 12. The request for reconsideration has been considered but does NOT place the application in condition for allowance because: Applicant's remarks state that terminal disclaimer is being filed, but no disclaimer is on the record. Examiner reached out to Applicant's representative on June 7th and June 20th, however no response has been received.

DO NOT ENTER: /DGC/

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant:	Network-1 Technologies, Inc.	Confirmation No.: 7483
Title:	Key Derivation for a Module Using an Embedded Universal Integrated Circuit Card	
Appl. No.:	18/229,907	
Filing Date:	August 3, 2023	
Examiner:	Cervetti, David Garcia	
Art Unit:	2419	
Docket No.:	63121/0224	
Customer No.:	01912	

RESPONSE TO FINAL OFFICE ACTION DATED APRIL 9, 2024

VIA EFS

Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

Sir:

This is a response to the Office Action dated April 9, 2024. A response to this Office Action is due on July 9, 2024. Accordingly, the present Amendment is being timely filed.

A Listing of the Claims begins on page **2** of this paper.

Remarks begin on page **6** of this paper.

Petitioner Samsung Ex-1004, 0422

PTO/SB/06 (09-11)
Approved for use through 1/31/2014. OMB 0651-0032
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

PATENT APPLICATION FEE DETERMINATION RECORD Substitute for Form PTO-875	Application or Docket Number 18/229,907	Filing Date 08/03/2023	☐ To be Mailed

ENTITY: ☐ LARGE ☑ SMALL ☐ MICRO

APPLICATION AS FILED - PART I

FOR	(Column 1) NUMBER FILED	(Column 2) NUMBER EXTRA		RATE ($)	FEE ($)
☐ BASIC FEE (37 CFR 1.16(a), (b), or (c))	N/A	N/A		N/A	
☐ SEARCH FEE (37 CFR 1.16(k), (i), or (m))	N/A	N/A		N/A	
☐ EXAMINATION FEE (37 CFR 1.16(o), (p), or (q))	N/A	N/A		N/A	
TOTAL CLAIMS (37 CFR 1.16(i))	minus 20 =	*		x $40 =	
INDEPENDENT CLAIMS (37 CFR 1.16(h))	minus 3 =	*		x $ 192 =	
☐ APPLICATION SIZE FEE (37 CFR 1.16(s))	If the specification and drawings exceed 100 sheets of paper, the application size fee due is $310 ($155 for small entity) for each additional 50 sheets or fraction thereof. See 35 U.S.C. 41(a)(1)(G) and 37 CFR 1.16(s).				
☐ MULTIPLE DEPENDENT CLAIM PRESENT (37 CFR 1.16(j))					
* If the difference in column 1 is less than zero, enter "0" in column 2.				TOTAL	

APPLICATION AS AMENDED - PART II

		(Column 1)		(Column 2)	(Column 3)			
AMENDMENT	07/08/2024	CLAIMS REMAINING AFTER AMENDMENT		HIGHEST NUMBER PREVIOUSLY PAID FOR	PRESENT EXTRA		RATE ($)	ADDITIONAL FEE ($)
	Total (37 CFR 1.16(i))	* 20	Minus	** 22	= 0		x $40 =	0
	Independent (37 CFR 1.16(h))	* 1	Minus	*** 3	= 0		x $ 192 =	0
	☐ Application Size Fee (37 CFR 1.16(s))							
	☐ FIRST PRESENTATION OF MULTIPLE DEPENDENT CLAIM (37 CFR 1.16(j))							
							TOTAL ADD'L FEE	0

		(Column 1)		(Column 2)	(Column 3)			
AMENDMENT		CLAIMS REMAINING AFTER AMENDMENT		HIGHEST NUMBER PREVIOUSLY PAID FOR	PRESENT EXTRA		RATE ($)	ADDITIONAL FEE ($)
	Total (37 CFR 1.16(i))	*	Minus	**	=		x $0 =	
	Independent (37 CFR 1.16(h))	*	Minus	***	=		x $0 =	
	☐ Application Size Fee (37 CFR 1.16(s))							
	☐ FIRST PRESENTATION OF MULTIPLE DEPENDENT CLAIM (37 CFR 1.16(j))							
							TOTAL ADD'L FEE	

* If the entry in column 1 is less than the entry in column 2, write "0" in column 3.	SLIE
** If the "Highest Number Previously Paid For" IN THIS SPACE is less than 20, enter "20".	/DESHONNE T. MARTINO-RAY/
*** If the "Highest Number Previously Paid For" IN THIS SPACE is less than 3, enter "3".	
The "Highest Number Previously Paid For" (Total or Independent) is the highest number found in the appropriate box in column 1.	

This collection of information is required by 37 CFR 1.16. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 12 minutes to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.**

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

UNITED STATES
PATENT AND TRADEMARK OFFICE

P.O. Box 1450
Alexandria, VA 22313 - 1450
www.uspto.gov

ELECTRONIC ACKNOWLEDGEMENT RECEIPT

APPLICATION #	RECEIPT DATE / TIME	ATTORNEY DOCKET #
18/229,907	**07/08/2024 02:25:28 PM Z ET**	**63121/0224**

Title of Invention

Key Derivation for a Module Using an Embedded Universal Integrated Circuit Card

Application Information

APPLICATION TYPE	Utility - Nonprovisional Application under 35 USC 111(a)	PATENT #	-
CONFIRMATION #	7483	FILED BY	Victoria GILMORE
PATENT CENTER #	66270322	FILING DATE	08/03/2023
CUSTOMER #	1912	FIRST NAMED INVENTOR	John A. Nix
CORRESPONDENCE ADDRESS	-	AUTHORIZED BY	Keith Barkaus

Documents

TOTAL DOCUMENTS: 3

DOCUMENT		PAGES	DESCRIPTION	SIZE (KB)
1-SupplementalResponsetoFOA.pdf		10	-	159 KB
1-SupplementalResponsetoFOA-SA...pdf	(1-1)	1	Supplemental Response or Supplemental Amendment	122 KB
1-SupplementalResponsetoFOA-CLM.pdf	(2-5)	4	Claims	127 KB
1-SupplementalResponsetoFOA-REM.pdf	(6-10)	5	Applicant Arguments/Remarks Made in an Amendment	148 KB

Digest

DOCUMENT	MESSAGE DIGEST(SHA-512)
1-SupplementalResponsetoFOA.pdf	A04C64243FEE568EC2748D9A134517BEA6A7DE9F35F129A0496DB0DE0F70CCAAF79693AD7BAF9BD420DE547698CADA8E2A3A6433D7B87B50495696F69E90BAA5
1-SupplementalResponsetoFOA-SA...pdf	8C93D3C92206CB5DE4CE42D2F3CF6F7775C3BBFB9894B80A0A159F5C75D1F1BF5BB0359586FFBD22EC4474314B592A77A68F1BDA4013940231C72E25D4880471
1-SupplementalResponsetoFOA-CLM.pdf	AFDCCFB17A5E99E57CC7DAED5EFA537514837B97F6BEFC1B5EFDB497F2B90B9F313B7408F8B7E996DB154FD366819C52BAD8B659D02A254A8F4A299F579AAAB5
1-SupplementalResponsetoFOA-REM.pdf	4D87CEE8BA4A1B2E89694C72C27B108AFB4D38BF69E16860A331AC2B0E9E8A7EA7131C67B4087B0C486947C66C626B7725D94F2B1B785972B4193345A1095A07

This Acknowledgement Receipt evidences receipt on the noted date by the USPTO of the indicated documents, characterized by the applicant, and including page counts, where applicable. It serves as evidence of receipt similar to a Post Card, as described in MPEP 503.

New Applications Under 35 U.S.C. 111

If a new application is being filed and the application includes the necessary components for filing date (see 37 CFR 1.53(b)-(d) and MPEP 506), a Filing Receipt (37 CFR 1.54) will be issued in due course and the date shown on this Acknowledgement Receipt will establish the filing date of the application.

National Stage of an International Application under 35 U.S.C. 371

If a timely submission to enter the national stage of an international application is compliant with the conditions of 35 U.S.C. 371 and other applicable requirements a Form PCT/DO/EO/903 indicating acceptance of the application as a national stage submission under 35 U.S.C. 371 will be issued in addition to the Filing Receipt, in due course.

New International Application Filed with the USPTO as a Receiving Office

If a new international application is being filed and the international application includes the necessary components for an international filing date (see PCT Article 11 and MPEP 1810), a Notification of the International Application Number and of the International Filing Date (Form PCT/RO/105) will be issued in due course, subject to prescriptions concerning national security, and the date shown on this Acknowledgement Receipt will establish the international filing date of the application.

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant:	Network-1 Technologies, Inc.	Confirmation No.: 7483
Title:	Key Derivation for a Module Using an Embedded Universal Integrated Circuit Card	
Appl. No.:	18/229,907	
Filing Date:	August 3, 2023	
Examiner:	Cervetti, David Garcia	
Art Unit:	2419	
Docket No.:	63121/0224	
Customer No.:	01912	

SUPPLEMENTAL AMENDMENT IN RESPONSE TO ADVISORY ACTION DATED JUNE 25, 2024 AND FINAL OFFICE ACTION DATED APRIL 9, 2024

VIA EFS

Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

Sir:

This is a response to the Advisory Action dated June 25, 2024 and is a further response to the Office Action dated April 9, 2024. A response to the Office Action was filed on May 29, 2024 and the Advisory Action issued on June 25, 2024. A response to the Office Action is due on July 9, 2024. Accordingly, the present Amendment is being timely filed.

A Listing of the Claims begins on page **2** of this paper.

Remarks begin on page **6** of this paper.

Petitioner Samsung Ex-1004, 0426

IN THE CLAIMS

This Listing of Claims will replace all prior versions, and listings, of claims in the application:

1-22 (Cancelled)

23. (Previously Presented) A method for a mobile device with an embedded universal integrated circuit card (eUICC) to securely communicate with a wireless network, the method performed by the mobile device, the method comprising:

a) storing, in the eUICC, a first module private key, a corresponding first module public key, and a network public key;

b) receiving, from a first server associated with the wireless network, an encrypted profile for the eUICC comprising cryptographic parameters, a module identity, and a key K;

c) generating a shared secret key using a first elliptic curve Diffie-Hellman (ECDH) key exchange with the first module private key and the network public key;

d) decrypting, with the shared secret key, at least a portion of the encrypted profile for the eUICC;

e) generating, by the eUICC, a second module public key and a corresponding second module private key;

f) sending, to a second server associated with the wireless network, the second module public key;

g) generating a symmetric key using a second ECDH key exchange with the second module private key and the cryptographic parameters;

h) generating, with the symmetric key, module encrypted data, the module encrypted data comprising the module identity; and

i) sending, to the servers, the module encrypted data.

24. (Previously Presented) The method of claim 23, wherein the module identity comprises an international mobile subscriber identity (IMSI).

Petitioner Samsung Ex-1004, 0427

25. (Previously Presented) The method of claim 23, wherein the module identity comprises a permanent identifier for the mobile device.

26. (Previously Presented) The method of claim 23, wherein the cryptographic parameters comprise an identifier for a set of cryptographic parameters.

27. (Previously Presented) The method of claim 23, further comprising in step c) deriving the shared secret key using an American National Standards Institute (ANSI) standard X-9.63 key derivation function.

28. (Previously Presented) The method of claim 23, further comprising in step g) deriving the symmetric key using an ANSI standard X-9.63 key derivation function.

29. (Previously Presented) The method of claim 23, wherein the first server mutually derives the shared secret key using the first ECDH key exchange with the first module public key and a network private key corresponding to the network public key.

30. (Previously Presented) The method of claim 23, further comprising in step e), generating, by the eUICC, the second module public key and the second module private key using a random number generator and input from a sensor.

31. (Previously Presented) The method of claim 23, further comprising in step h) generating, with the symmetric key and an Advanced Encryption Standard (AES), the module encrypted data.

32. (Previously Presented) The method of claim 23, wherein steps g) and h) occur before step f).

Petitioner Samsung Ex-1004, 0428

33. (Previously Presented) The method of claim 23, wherein the network public key is associated with an eUICC subscription manager.

34. (Previously Presented) The method of claim 33, wherein (i) the eUICC subscription manager comprises the first server.

35. (Previously Presented) The method of claim 23, further comprising: j) receiving, from the wireless network, a random number (RAND) and generating a response (RES) using the RAND and the key K.

36. (Previously Presented) The method of claim 23, further comprising before step b), authenticating the first server by (i) receiving a server digital signature and (ii) verifying the server digital signature with a server public key.

37. (Previously Presented) The method of claim 23, further comprising (i) in step a), storing a server name for the first server and a port number in a nonvolatile memory of the eUICC, and (ii) before step b) sending the first module public key to the first server.

38. (Previously Presented) The method of claim 23, wherein the first server, the second server, and the wireless network are associated with a mobile network operator.

39. (Previously Presented) The method of claim 23, wherein the eUICC comprises a processor, firmware, and protected memory.

40. (Previously Presented) The method of claim 23, wherein the cryptographic parameters include a base point G for an elliptic curve.

41. (Previously Presented) The method of claim 23, wherein the mobile device comprises a wireless device with a radio for communicating with a plurality of base stations for the wireless network.

Petitioner Samsung Ex-1004, 0429

42. (Previously Presented) The method of claim 23, wherein the eUICC comprises a package soldered to a circuit board of the mobile device.

Petitioner Samsung Ex-1004, 0430

REMARKS

This is a response to the Advisory Action dated June 25, 2024 and is a further response to the Office Action dated April 9, 2024. A response to this Office Action was filed on May 29, 2024 and the due date to respond without extension is July 9, 2024. Claims 23-42 are pending in the present application with claim 23 being is in independent form. No new matter has been added by the present Amendment.

In the Advisory Action dated June 25, 2024, the Examiner indicated that a terminal disclaimer was not filed with Applicants prior response filed on May 29, 2024. During a telephone call on June 26, 2024, Applicant noted that a terminal disclaimer was filed on May 29, 2024 and was accepted. At that time, the Examiner noted that this filing was not reflected in the USPTO Patent Center, but indicated that he would look further into it. On July 5, 2024, during a telephone call, the Applicant's undersigned attorney and the Examiner confirmed that the previously filed terminal disclaimer and the acceptance thereof was now properly listed in Patent Center as being filed on May 29, 2024 with the prior amendment filed in the present application. The Examiner requested that Applicant's attorney file the present supplemental amendment in response to the Advisory Action to note the prior filing of the terminal disclaimer and acceptance and the fact that both are now properly listed in Patent Center. The remainder of the present supplemental amendment is the same as the amendment previously filed on May 29, 2024 except to note the prior filing of the terminal disclaimer and an update of the list of related applications.

In view of the prior and below remarks, Applicant respectfully asserts that claims 23-42 are in condition for allowance.

In the event that the Examiner disagrees, Applicant respectfully requests that the Examiner contact Applicant's undersigned attorney by telephone prior to issuing another Office Action.

I. Provisional Double Patenting

Claims 23-42 are provisionally rejected under the judicially created doctrine of obviousness-type double patenting as allegedly being unpatentable over the claims of U.S. Patent Nos. 9,319,223; 9,742,562; 10,187,206; 10,498,530; 10,700,856; 11,258,595, 11,082,218 and 11,736,283. Office Action, pgs. 2-5.

Petitioner Samsung Ex-1004, 0431

While Applicant does not necessarily agree with the Examiner's double patenting rejections as set forth above, in an effort to advance prosecution of the present application, Applicant submits herewith a terminal disclaimer with respect to each of U.S. Patent Nos. 9,319,223; 9,742,562; 10,187,206; 10,498,530; 10,700,856; 11,258,595 and 11,082218 to overcome this rejection. Applicant respectfully submits that claims 23-42 are patentably distinct from the claims of the above patents. As noted above, this terminal disclaimer referred to above was previously filed and accepted on May 29, 2024.

Accordingly, Applicant respectfully requests withdrawal of the provisional double patenting rejection.

As there are no other rejections in the Office Action, Applicant respectfully submits that claims 23-42 are allowable over the cited art and are in condition for allowance.

II. Reference to Related Patents and Co-Pending Applications

The below chart provides information regarding related issued patents and co-pending applications filed by the present Applicant:

Petitioner Samsung Ex-1004, 0432

Serial No.	Attorney Docket No.	Filing Date	Status
18/435,042	63121/230	2024-02-07	Pending – Awaiting First Office Act
18/587,462	63121/0229	2024-02-26	Pending – Awaiting First Office Action
18/435,042	63121/0228	2024-02-06	Pending – Awaiting First Office Action
18/438,147	63121/0227	2024-02-09	Pending – Awaiting First Office Action
18/416,534	63121/0226	2024-01-18	Pending – Awaiting First Office Action
18/433,664	63121/0225	2024-02-26	Pending – Awaiting First Office Action
18/229,907	**63121/0224**	**2023-08-03**	**(Present Application) Pending - Case Docketed to Examiner**
18/111,669	63121/0222	2023-02-20	USP 11,973,864
17/647,812	63121/0213	2022-01-13	USP 11,606,204
17/547,990	63121/0212	2021-12-10	USP 11,736,283
17/304,922	63121/0209	2021-06-28	USP 11,736,283
17/249,242	63121/0202	2021-02-24	USP 11,973,863
16/879,325	63121/0198	2020-05-20	USP 11,082,218
16/843,107	63121/0197	2020-04-08	USP 11,283,603
16/721,153	63121/0195	2019-12-19	USP 11,539,681
16/593,561	63121/0190	2019-10-04	USP 11,258,595
16/453,682	63121/0184	2019-06-26	USP 11,233,780
16/271,455	63121/0181	2019-02-08	USP 10,594,679
16/271,428	63121/0180	2019-02-08	USP 10,523,432
16/201,401	63121/0179	2018-11-27	USP 10,700,856
16/200,118	63121/0178	2018-11-26	USP 10,498,530
16/110,804	63121/0168	2018-08-23	USP 10,382,422
16/036,506	63121/0167	2018-07-16	USP 10,530,575
15/983,957	63121/0163	2018-05-18	USP 10,177,911
15/973,012	63121/0162	2018-05-07	USP 10,250,386
15/972,914	63121/0161	2018-05-07	USP 10,652,017
15/928,848	63121/0160	2018-03-22	USP 10,084,768
15/010,905	63121/0157	2016-01-29	USP 9,641,327
15/680,758	63121/0147	2017-08-18	USP 10,187,206
15/162,292	63121/0146	2016-05-23	USP 10,362,012
14/751,119	63121/0145	2015-06-25	USP 9,961,060
15/457,700	63121/0144	2017-03-13	USP 9,998,281
15/583,968	63121/0143	2017-05-01	USP 10,057,059
15/043,293	63121/0142	2016-02-12	USP 9,998,280
15/642,088	63121/0141	2017-07-05	USP 10,003,461

Petitioner Samsung Ex-1004, 0433

15/130,146	63121/0140	2016-04-15	USP 9,742,562
15/162,302	63121/0139	2016-05-23	USP 9,698,981
14/789,255	63121/0138	2015-07-01	USP 9,596,078
14/139,419	63121/0137	2013-12-23	USP 9,351,162
14/136,711	63121/0136	2013-12-20	USP 9,300,473
14/099,329	63121/0135	2013-12-06	USP 9,100,175
14/084,141	63121/0134	2013-11-19	USP 9,319,223
14/064,618	63121/0133	2013-10-28	USP 9,118,464
14/055,606	63121/0132	2013-10-16	USP 9,276,740
14/039,401	63121/0131	2013-09-27	USP 9,288,059
14/023,181	63121/0130	2013-09-10	USP 9,350,550
AU 2019246774	63121-0199	2019-10-08	AU2019246774A1 Issued 2021-09-23
GB 1608573	63121-0151	2014-10-27	Published on 2016-08-03
GB 2100530	63121-0201	2014-10-27	Published on 2021-05-12
CA 2,965,119	63121-0152	2014-10-27	Published on 2015-05-07
HK 17101082.8	63121-0153	2014-10-27	Published on 2017-10-20
EU 14868381.6	63121-0154	2014-12-04	Published on 2017-01-04
CA 2,969,829	63121-0155	2014-12-04	Published on 2015-06-11
HK 17106540.3	63121-0156	2014-12-04	Published on 2018-01-19

The Examiner is invited to review the prosecution history of each of these applications, including the cited references of record and related office actions, as the Examiner deems appropriate.

Favorable reconsideration of the present application is respectfully requested.

Petitioner Samsung Ex-1004, 0434

If any fees are required in view of the foregoing, the Director is hereby authorized to charge any such fee to Deposit Account No. 01-1785.

Respectfully submitted,

AMSTER, ROTHSTEIN & EBENSTEIN LLP
Attorneys for Applicant
405 Lexington Avenue
New York, NY 10174
(212) 336-8000

Dated: New York, New York
July 8, 2024

By: /Keith J. Barkaus/
Keith J. Barkaus
Registration No. 51,431

Petitioner Samsung Ex-1004, 0435

Notice of References Cited	Application/Control No. 18/229,907	Applicant(s)/Patent Under Reexamination Nix, John A.	
	Examiner David García Cervetti	Art Unit 2419	Page 1 of 11

U.S. PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Name	CPC Classification	US Classification
*	A	US-9807605-B2	2017-10-31	Gao; Linyi	H04L63/0428	1/1
*	B	US-20110213959-A1	2011-09-01	Bodi; MiklosTamas	H04W12/06	713/155
*	C	US-8577337-B2	2013-11-05	O'Leary; Edward A.	H04W12/068	455/410
*	D	US-20130344864-A1	2013-12-26	PARK; Chul Hyun	H04W8/18	455/432.3
*	E	US-9800993-B2	2017-10-24	Lee; Duckey	H04W12/126	1/1
*	F	US-9794775-B2	2017-10-17	Huber; Ulrich	H04W8/265	1/1
*	G	US-9674690-B2	2017-06-06	Lee; Hyung Jin	H04W8/183	1/1
*	H	US-9628981-B2	2017-04-18	Park; Jaemin	H04W8/205	1/1
*	I	US-9572016-B2	2017-02-14	Cormier; Jean-Philippe Paul	H04W8/183	1/1
*	J	US-9332129-B2	2016-05-03	Li; Li	H04W4/50	1/1
*	K	US-9270653-B2	2016-02-23	Maria; Arturo	H04L63/062	1/1
*	L	US-20140082359-A1	2014-03-20	Nakhjiri; Madjid	H04L9/3066	713/168
*	M	US-20140120874-A1	2014-05-01	Kang; Hyun-Jeong	H04W12/069	455/411

FOREIGN PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Country	Name	CPC Classification
	N					
	O					
	P					
	Q					
	R					
	S					
	T					

NON-PATENT DOCUMENTS

*		Include as applicable: Author, Title Date, Publisher, Edition or Volume, Pertinent Pages)
	U	
	V	
	W	
	X	

*A copy of this reference is not being furnished with this Office action. (See MPEP § 707.05(a).)
Dates in YYYY-MM-DD format are publication dates. Classifications may be US or foreign.

Petitioner Samsung Ex-1004, 0436

U.S. PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Name	CPC Classification	US Classification
*	A	US-6804357-B1	2004-10-12	Ikonen; Ari M.	H04N21/42204	348/14.05
*	B	US-9923724-B2	2018-03-20	Lee; Duckey	H04L9/0825	1/1
*	C	US-20140329502-A1	2014-11-06	Lee; Jinhyoung	H04W12/04	455/411
*	D	US-6842628-B1	2005-01-11	Arnold; Greg	H04L51/224	713/181
*	E	US-8352739-B2	2013-01-08	Park; Young-Man	H04L63/06	713/169
*	F	US-6721886-B1	2004-04-13	Uskela; Sami	H04L9/3271	713/168
*	G	US-5995625-A	1999-11-30	Sudia; Frank W.	G06F21/6209	713/181
*	H	US-5852665-A	1998-12-22	Gressel; Carmi David	H04L9/0894	380/45
*	I	US-5664017-A	1997-09-02	Gressel; Carmi David	H04L9/0833	380/30
*	J	US-5642420-A	1997-06-24	Kuroda; Yasutsugu	H04L9/40	380/30
*	K	US-5216715-A	1993-06-01	Markwitz; Wernhard	H04L9/321	713/181
*	L	US-20150350881-A1	2015-12-03	WEISS; Dieter	H04W12/04	455/558
*	M	US-20130283047-A1	2013-10-24	Merrien; Lionel	H04L67/306	713/164

FOREIGN PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Country	Name	CPC Classification
	N					
	O					
	P					
	Q					
	R					
	S					
	T					

NON-PATENT DOCUMENTS

*		Include as applicable: Author, Title Date, Publisher, Edition or Volume, Pertinent Pages)
	U	
	V	
	W	
	X	

*A copy of this reference is not being furnished with this Office action. (See MPEP § 707.05(a).)
Dates in YYYY-MM-DD format are publication dates. Classifications may be US or foreign.

Petitioner Samsung Ex-1004, 0437

Notice of References Cited	Application/Control No. 18/229,907	Applicant(s)/Patent Under Reexamination Nix, John A.	
	Examiner David García Cervetti	Art Unit 2419	Page 3 of 11

U.S. PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Name	CPC Classification	US Classification
*	A	US-20120263298-A1	2012-10-18	Suh; Kyung-Joo	H04W4/50	380/255
*	B	US-20080044032-A1	2008-02-21	Lou; Dafu	H04L65/40	380/284
*	C	US-20050058294-A1	2005-03-17	Chen, Liqun	H04L9/0847	380/277
*	D	US-6256733-B1	2001-07-03	Thakkar; Dhanya	H04L63/065	380/279
*	E	US-20160088096-A1	2016-03-24	QUIRICONI; Jean-Rémi	H04W4/50	709/219
*	F	US-20120190354-A1	2012-07-26	MERRIEN; Lionel	H04L63/083	455/422.1
*	G	US-20140287725-A1	2014-09-25	Lee; Jin Hyoung	H04W12/35	455/411
*	H	US-20140237101-A1	2014-08-21	Park; Jaemin	H04W8/205	709/223
*	I	US-20140235210-A1	2014-08-21	Park; Jaemin	H04W12/35	455/411
*	J	US-20140219447-A1	2014-08-07	Park; Jaemin	H04W12/35	380/247
*	K	US-20140140507-A1	2014-05-22	Park; Jaemin	H04W8/183	380/247
*	L	US-9020479-B1	2015-04-28	Somayajula; Siva Rama Kumar	H04W48/18	455/418
*	M	US-8965366-B1	2015-02-24	Somayajula; Siva Rama Kumar	H04W60/00	455/418

FOREIGN PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Country	Name	CPC Classification
	N					
	O					
	P					
	Q					
	R					
	S					
	T					

NON-PATENT DOCUMENTS

*		Include as applicable: Author, Title Date, Publisher, Edition or Volume, Pertinent Pages)
	U	
	V	
	W	
	X	

*A copy of this reference is not being furnished with this Office action. (See MPEP § 707.05(a).)
Dates in YYYY-MM-DD format are publication dates. Classifications may be US or foreign.

Petitioner Samsung Ex-1004, 0438

U.S. PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Name	CPC Classification	US Classification
*	A	US-20140082358-A1	2014-03-20	Nakhjiri; Madjid	H04L9/0822	713/168
*	B	US-20150281964-A1	2015-10-01	Seo; Myoung Hee	H04W8/183	726/9
*	C	US-20150121495-A1	2015-04-30	Gao; Linyi	H04W12/04	726/6
*	D	US-20140308991-A1	2014-10-16	Lee; Jin Hyoung	H04W12/35	455/558
*	E	US-20130340040-A1	2013-12-19	PARK; Chul Hyun	H04L63/08	726/3
*	F	US-20130122864-A1	2013-05-16	HAGGERTY; DAVID T.	G06F21/34	455/411
*	G	US-20110270747-A1	2011-11-03	Xu; Richard H.	H04M15/67	705/40
*	H	US-20160057725-A1	2016-02-25	Suh; Kyungjoo	H04W60/06	455/435.1
*	I	US-20160149903-A1	2016-05-26	Suh; Kyungjoo	H04L63/0428	713/156
*	J	US-20130157673-A1	2013-06-20	Brusilovsky; Alec	H04W12/02	455/450
*	K	US-20110268022-A1	2011-11-03	Xu; Richard H.	H04Q3/0025	370/328
*	L	US-20160127132-A1	2016-05-05	Lee; Duckey	H04L9/0819	713/156
*	M	US-20140357229-A1	2014-12-04	LEE; Duckey	H04W8/245	455/411

FOREIGN PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Country	Name	CPC Classification
	N					
	O					
	P					
	Q					
	R					
	S					
	T					

NON-PATENT DOCUMENTS

*		Include as applicable: Author, Title Date, Publisher, Edition or Volume, Pertinent Pages)
	U	
	V	
	W	
	X	

*A copy of this reference is not being furnished with this Office action. (See MPEP § 707.05(a).)
Dates in YYYY-MM-DD format are publication dates. Classifications may be US or foreign.

Petitioner Samsung Ex-1004, 0439

U.S. PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Name	CPC Classification	US Classification
*	A	US-20130227646-A1	2013-08-29	Haggerty; David	H04L63/10	726/3
*	B	US-20130012168-A1	2013-01-10	Rajadurai; Rajavelsamy	H04W12/04	455/411
*	C	US-20130294602-A1	2013-11-07	Huxham; Horatio Nelson	H04L63/0853	380/255
*	D	US-20140003604-A1	2014-01-02	CAMPAGNA; Matthew John	H04W12/069	380/247
*	E	US-20110269461-A1	2011-11-03	Xu; Richard H.	H04W8/183	455/435.2
*	F	US-20110269472-A1	2011-11-03	Xu; Richard H.	H04W40/02	455/445
*	G	US-20110269422-A1	2011-11-03	Xu; Richard H.	H04M17/20	455/411
*	H	US-20210152359-A1	2021-05-20	KIM; Tae-Gyun	H04L9/0819	1/1
*	I	US-20180276358-A1	2018-09-27	SAWAMURA; Satoshi	G06K19/07	1/1
*	J	US-20160034707-A1	2016-02-04	SAHU; Samir Kant	H04L9/0866	713/168
*	K	US-20150163209-A1	2015-06-11	KAWAMOTO; YOHEI	H04L63/08	726/6
*	L	US-11281813-B1	2022-03-22	Morgan; Thomas Scott	G06F21/72	1/1
*	M	US-20180176223-A1	2018-06-21	Hutchinson; Michael	H04L9/16	1/1

FOREIGN PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Country	Name	CPC Classification
	N					
	O					
	P					
	Q					
	R					
	S					
	T					

NON-PATENT DOCUMENTS

*		Include as applicable: Author, Title Date, Publisher, Edition or Volume, Pertinent Pages)
	U	
	V	
	W	
	X	

*A copy of this reference is not being furnished with this Office action. (See MPEP § 707.05(a).)
Dates in YYYY-MM-DD format are publication dates. Classifications may be US or foreign.

Petitioner Samsung Ex-1004, 0440

U.S. PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Name	CPC Classification	US Classification
*	A	US-20120011362-A1	2012-01-12	Lambert; Robert John	H04L9/0844	713/168
*	B	US-20060129848-A1	2006-06-15	Paksoy; Erdal	G06F21/35	713/193
*	C	US-8452017-B2	2013-05-28	Sherkin; Alexander	H04L9/0844	713/168
*	D	US-20120087493-A1	2012-04-12	CHIDAMBARAM; Avinash	H04L9/0841	713/182
*	E	US-20110035604-A1	2011-02-10	Habraken; G. Wouter	G07F7/1016	235/382
*	F	US-20060235796-A1	2006-10-19	Johnson; Bruce E.	G06Q20/12	705/26.1
*	G	US-20060235795-A1	2006-10-19	Johnson; Bruce E.	G06Q20/02	705/26.1
*	H	US-20150058632-A1	2015-02-26	Beyer; Loraine	H04L65/1073	713/171
*	I	US-8874915-B1	2014-10-28	Rodoper; Mete	H04L9/0838	380/278
*	J	US-20140219448-A1	2014-08-07	Froels; Martin	H04L9/14	380/255
*	K	US-20140032898-A1	2014-01-30	YU; Zhao-Fu	H04N21/4181	713/159
*	L	US-20130301828-A1	2013-11-14	Gouget; Aline	H04L9/0844	380/44
*	M	US-20130290714-A1	2013-10-31	Hans; Sebastian	H04L9/3273	713/168

FOREIGN PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Country	Name	CPC Classification
	N					
	O					
	P					
	Q					
	R					
	S					
	T					

NON-PATENT DOCUMENTS

*		Include as applicable: Author, Title Date, Publisher, Edition or Volume, Pertinent Pages)
	U	
	V	
	W	
	X	

*A copy of this reference is not being furnished with this Office action. (See MPEP § 707.05(a).)
Dates in YYYY-MM-DD format are publication dates. Classifications may be US or foreign.

Petitioner Samsung Ex-1004, 0441

U.S. PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Name	CPC Classification	US Classification
*	A	US-20130067552-A1	2013-03-14	Hawkes; Philip Michael	H04W12/08	726/7
*	B	US-20120284194-A1	2012-11-08	Liu; Jie	G07F7/08	705/66
*	C	US-20120084565-A1	2012-04-05	Wittenberg; Craig Henry	H04L9/3226	713/172
*	D	US-20120028608-A1	2012-02-02	SU; JEN-CHEN	H04W12/08	455/411
*	E	US-20080288773-A1	2008-11-20	Nguyen; Nam	H04L9/321	713/155
*	F	US-20080260149-A1	2008-10-23	Gehrmann; Christian M.	G06Q20/3821	380/247
*	G	US-20080170697-A1	2008-07-17	Heinonen; Petteri	H04L63/0823	380/277
*	H	US-20070241182-A1	2007-10-18	Buer; Mark	H04L63/0853	235/380
*	I	US-20070050622-A1	2007-03-01	Rager; Kent D.	G06F21/445	713/168
*	J	US-20050246529-A1	2005-11-03	Hunt, Galen C.	H04L9/3263	713/168
*	K	US-11258595-B2	2022-02-22	Nix; John A.	H04W12/04	1/1
*	L	US-20210226781-A1	2021-07-22	ARKKO; Jari	H04L9/085	1/1
*	M	US-20210203488-A1	2021-07-01	STÅHL; Per	H04L9/0631	1/1

FOREIGN PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Country	Name	CPC Classification
	N					
	O					
	P					
	Q					
	R					
	S					
	T					

NON-PATENT DOCUMENTS

*		Include as applicable: Author, Title Date, Publisher, Edition or Volume, Pertinent Pages)
	U	
	V	
	W	
	X	

*A copy of this reference is not being furnished with this Office action. (See MPEP § 707.05(a).)
Dates in YYYY-MM-DD format are publication dates. Classifications may be US or foreign.

Petitioner Samsung Ex-1004, 0442

U.S. PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Name	CPC Classification	US Classification
*	A	US-20210144551-A1	2021-05-13	LEE; Hyewon	H04W12/043	1/1
*	B	US-10743176-B1	2020-08-11	Khan; Taussif	H04W12/48	1/1
*	C	US-20200162269-A1	2020-05-21	Nix; John A.	H04L9/14	1/1
*	D	US-20200089488-A1	2020-03-19	Yu; Xiaobo	G06F16/148	1/1
*	E	US-20200021993-A1	2020-01-16	YANG; Xiangying	H04L63/123	1/1
*	F	US-20190394053-A1	2019-12-26	Yu; Xiaobo	H04W12/041	1/1
*	G	US-20190373471-A1	2019-12-05	LI; Li	H04L9/3247	1/1
*	H	US-20190230087-A1	2019-07-25	Gharout; Said	H04W12/35	1/1
*	I	US-20190208417-A1	2019-07-04	KANG; Xin	H04W12/35	1/1
*	J	US-20190190723-A1	2019-06-20	LEE; Jung Do	H04L9/3231	1/1
*	K	US-20190140837-A1	2019-05-09	Cheng; Ziyao	H04W8/20	1/1
*	L	US-20130159710-A1	2013-06-20	Khan; Ahmer A.	H04L9/0891	713/168
*	M	US-7715822-B2	2010-05-11	Semple; James	H04L63/0853	455/433

FOREIGN PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Country	Name	CPC Classification
	N					
	O					
	P					
	Q					
	R					
	S					
	T					

NON-PATENT DOCUMENTS

*		Include as applicable: Author, Title Date, Publisher, Edition or Volume, Pertinent Pages)
	U	
	V	
	W	
	X	

*A copy of this reference is not being furnished with this Office action. (See MPEP § 707.05(a).)
Dates in YYYY-MM-DD format are publication dates. Classifications may be US or foreign.

Petitioner Samsung Ex-1004, 0443

Notice of References Cited	Application/Control No. 18/229,907	Applicant(s)/Patent Under Reexamination Nix, John A.	
	Examiner David García Cervetti	Art Unit 2419	Page 9 of 11

U.S. PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Name	CPC Classification	US Classification
*	A	US-20080130879-A1	2008-06-05	Heinonen; Petteri	H04L9/006	380/44
*	B	US-20060034494-A1	2006-02-16	Holloran; Robert W.	H04L9/3231	382/116
*	C	US-20150143125-A1	2015-05-21	Nix; John A.	H04L9/3066	713/171
*	D	US-9247424-B2	2016-01-26	Haggerty; David T.	H04L63/10	1/1
*	E	US-20160226877-A1	2016-08-04	HAGGERTY; David T.	H04W8/183	1/1
*	F	US-9843585-B2	2017-12-12	Haggerty; David T.	H04W12/06	1/1
*	G	US-9037112-B2	2015-05-19	Rajadurai; Rajavelsamy	H04W12/35	713/168
*	H	US-9451459-B2	2016-09-20	Lee; Jinhyoung	H04W12/35	1/1
*	I	US-9426654-B2	2016-08-23	Lee; Jin Hyoung	H04L63/0853	1/1
*	J	US-20160330624-A1	2016-11-10	LEE; Jin Hyoung	H04L63/0853	1/1
*	K	US-20180242153-A1	2018-08-23	LEE; Jin Hyoung	H04L63/0853	1/1
*	L	US-10091653-B2	2018-10-02	Lee; Jin Hyoung	H04W12/06	1/1
*	M	US-10462668-B2	2019-10-29	Lee; Jin Hyoung	H04L63/0823	1/1

FOREIGN PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Country	Name	CPC Classification
	N					
	O					
	P					
	Q					
	R					
	S					
	T					

NON-PATENT DOCUMENTS

*		Include as applicable: Author, Title Date, Publisher, Edition or Volume, Pertinent Pages)
	U	
	V	
	W	
	X	

*A copy of this reference is not being furnished with this Office action. (See MPEP § 707.05(a).)
Dates in YYYY-MM-DD format are publication dates. Classifications may be US or foreign.

Petitioner Samsung Ex-1004, 0444

Notice of References Cited	Application/Control No. 18/229,907	Applicant(s)/Patent Under Reexamination Nix, John A.	
	Examiner David García Cervetti	Art Unit 2419	Page 10 of 11

U.S. PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Name	CPC Classification	US Classification
*	A	US-9712996-B2	2017-07-18	Park; Jaemin	H04W12/04	1/1
*	B	US-20170289792-A1	2017-10-05	PARK; Jaemin	H04L67/306	1/1
*	C	US-20150126153-A1	2015-05-07	Spitz; Stephan	H04W12/06	455/26.1
*	D	US-20060179309-A1	2006-08-10	Cross; David B.	G06F21/6281	713/168
*	E	US-20040146015-A1	2004-07-29	Cross, David B.	H04L9/0894	370/328
*	F	US-8887257-B2	2014-11-11	Haggerty; David T.	H04W12/04	726/9
*	G	US-20140006786-A1	2014-01-02	Campagna; Matthew John	H04W12/04	713/171
*	H	US-20140004824-A1	2014-01-02	Campagna; Matthew John	H04L9/0866	455/411
*	I	US-20120072979-A1	2012-03-22	Cha; Inhyok	H04W12/069	726/8
*	J	US-20120023568-A1	2012-01-26	Cha; Inhyok	H04L63/0807	726/10
*	K	US-20100174907-A1	2010-07-08	Semple; James F.	H04W12/0431	713/169
*	L	US-20220295288-A1	2022-09-15	St?hl; Per	H04L67/303	1/1
*	M	US-20220095095-A1	2022-03-24	LIM; Taehyung	H04W8/24	1/1

FOREIGN PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Country	Name	CPC Classification
	N					
	O					
	P					
	Q					
	R					
	S					
	T					

NON-PATENT DOCUMENTS

*		Include as applicable: Author, Title Date, Publisher, Edition or Volume, Pertinent Pages)
	U	
	V	
	W	
	X	

*A copy of this reference is not being furnished with this Office action. (See MPEP § 707.05(a).)
Dates in YYYY-MM-DD format are publication dates. Classifications may be US or foreign.

Petitioner Samsung Ex-1004, 0445

Notice of References Cited	Application/Control No. 18/229,907	Applicant(s)/Patent Under Reexamination Nix, John A.	
	Examiner David García Cervetti	Art Unit 2419	Page 11 of 11

U.S. PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Name	CPC Classification	US Classification
*	A	US-20220046409-A1	2022-02-10	LIM; Taehyung	H04W12/40	1/1
*	B	US-20210314148-A1	2021-10-07	YANG; Xiangying	H04L9/0822	1/1
*	C	US-20200351656-A1	2020-11-05	JOHANSSON; Petri Mikael	H04W4/70	1/1
*	D	US-20200137572-A1	2020-04-30	LEE; Hyewon	H04W12/35	1/1
*	E	US-20190097794-A1	2019-03-28	Nix; John A.	H04L9/3249	1/1
*	F	US-20180351945-A1	2018-12-06	LI; Li	H04W8/205	1/1
*	G	US-20180144147-A1	2018-05-24	Nix; John A.	H04W12/35	1/1
*	H	US-20180123803-A1	2018-05-03	PARK; Jong-Han	H04L9/14	1/1
*	I	US-20170338954-A1	2017-11-23	YANG; Xiangying	H04W12/35	1/1
*	J	US-20240022404-A1	2024-01-18	Nepstad; Tommie Andr? Andreassen	H04L9/50	1/1
*	K	US-20240022397-A1	2024-01-18	NAITO; Narumi	G06F21/6209	1/1
	L					
	M					

FOREIGN PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Country	Name	CPC Classification
	N					
	O					
	P					
	Q					
	R					
	S					
	T					

NON-PATENT DOCUMENTS

*		Include as applicable: Author, Title Date, Publisher, Edition or Volume, Pertinent Pages)
	U	
	V	
	W	
	X	

*A copy of this reference is not being furnished with this Office action. (See MPEP § 707.05(a).)
Dates in YYYY-MM-DD format are publication dates. Classifications may be US or foreign.

Petitioner Samsung Ex-1004, 0446

Index of Claims	Application/Control No.	Applicant(s)/Patent Under Reexamination
	18/229,907	Nix, John A.
	Examiner	Art Unit
	David García Cervetti	2419

✓	Rejected	-	Cancelled	N	Non-Elected	A	Appeal
=	Allowed	÷	Restricted	I	Interference	O	Objected

CLAIMS

☐ Claims renumbered in the same order as presented by applicant ☐ CPA ☐ T.D. ☐ R.1.47

CLAIM		DATE								
Final	Original	03/08/2024	04/06/2024	07/22/2024						
	1	✓	-	-						
	2	✓	-	-						
	3	✓	-	-						
	4	✓	-	-						
	5	✓	-	-						
	6	✓	-	-						
	7	✓	-	-						
	8	✓	-	-						
	9	✓	-	-						
	10	✓	-	-						
	11	✓	-	-						
	12	✓	-	-						
	13	✓	-	-						
	14	✓	-	-						
	15	✓	-	-						
	16	✓	-	-						
	17	✓	-	-						
	18	✓	-	-						
	19	✓	-	-						
	20	✓	-	-						
	21	✓	-	-						
	22	✓	-	-						
1	23		✓	=						
2	24		✓	=						
3	25		✓	=						
4	26		✓	=						
5	27		✓	=						
6	28		✓	=						
7	29		✓	=						
8	30		✓	=						
9	31		✓	=						
10	32		✓	=						
11	33		✓	=						
12	34		✓	=						
13	35		✓	=						
14	36		✓	=						
15	37		✓	=						
16	38		✓	=						
17	39		✓	=						
18	40		✓	=						
19	41		✓	=						
20	42		✓	=						

Petitioner Samsung Ex-1004, 0447

Search Notes	Application/Control No.	Applicant(s)/Patent Under Reexamination
	18/229,907	Nix, John A.
	Examiner	Art Unit
	David García Cervetti	2419

CPC - Searched*		
Symbol	Date	Examiner
H04L9/0861 H04L9/006 H04L9/0662 H04L9/0816 H04L9/0841 H04L9/0844 H04L9/085 H04L9/088 H04L9/0891 H04L9/0894 H04L9/14 H04L9/30 H04L9/3239 H04L9/3247 H04L9/3249 H04L9/3263 H04L63/061 H04L63/0442 H04W12/03 H04W12/041 H04W12/06	07/22/2024	DGC

CPC Combination Sets - Searched*		
Symbol	Date	Examiner

US Classification - Searched*			
Class	Subclass	Date	Examiner

* See search history printout included with this form or the SEARCH NOTES box below to determine the scope of the search.

Search Notes		
Search Notes	Date	Examiner
inventor name search, acm, ieee, springer, google, scholar, ip.com, search history attached, global dossier	07/22/2024	DGC

Interference Search			
US Class/CPC Symbol	US Subclass/CPC Group	Date	Examiner
H04L9	0861,006,0662,0816,0841,0844,085,088,0891,0894,14,30,3239,3247,3249,3263	07/22/2024	DGC
H04L63	061,0442	07/22/2024	DGC
H04W12	03,041,06	07/22/2024	DGC

/David Garcia Cervetti/ Primary Examiner, Art Unit 2419	

Petitioner Samsung Ex-1004, 0448

Search Notes	Application/Control No.	Applicant(s)/Patent Under Reexamination
	18/229,907	Nix, John A.
	Examiner	**Art Unit**
	David García Cervetti	2419

/David Garcia Cervetti/ Primary Examiner, Art Unit 2419	

Petitioner Samsung Ex-1004, 0449

Issue Classification	Application/Control No.	Applicant(s)/Patent Under Reexamination
	18/229,907	Nix, John A.
	Examiner	**Art Unit**
	David García Cervetti	2419

CPC						
Symbol					**Type**	**Version**
H04L	/	9	/	0861	F	2013-01-01
H04W	/	4	/	70	I	2018-02-01
H04W	/	76	/	27	I	2018-02-01
H04W	/	12	/	04	I	2013-01-01
H04L	/	9	/	0841	I	2013-01-01
H04W	/	52	/	0235	I	2013-01-01
H04L	/	9	/	3247	I	2013-01-01
H04L	/	9	/	32	I	2013-01-01
H04W	/	40	/	005	I	2013-01-01
H04W	/	12	/	06	I	2013-01-01
H04L	/	63	/	061	I	2013-01-01
H04J	/	11	/	00	I	2013-01-01
H04L	/	9	/	006	I	2013-01-01
G06F	/	21	/	35	I	2013-01-01
H04L	/	9	/	0894	I	2013-01-01
H04L	/	9	/	085	I	2013-01-01
H04W	/	52	/	0277	I	2013-01-01
H04L	/	9	/	321	I	2013-01-01
H04W	/	80	/	04	I	2013-01-01
H04L	/	63	/	166	I	2013-01-01
H04L	/	67	/	04	I	2013-01-01
H04L	/	9	/	3249	I	2013-01-01
H04L	/	9	/	088	I	2013-01-01
H04L	/	63	/	0272	I	2013-01-01
H04L	/	9	/	30	I	2013-01-01
H04L	/	63	/	123	I	2013-01-01
H04L	/	9	/	14	I	2013-01-01
H04W	/	8	/	082	I	2013-01-01
H04L	/	9	/	3066	I	2013-01-01
H04L	/	63	/	0442	I	2013-01-01
H04L	/	63	/	045	I	2013-01-01

NONE		**Total Claims Allowed:**	
(Assistant Examiner)	(Date)	20	
/David Garcia Cervetti/ Primary Examiner, Art Unit 2419	22 July 2024	O.G. Print Claim(s)	O.G. Print Figure
(Primary Examiner)	(Date)	1	1

U.S. Patent and Trademark Office — Part of Paper No.: 20240722

Petitioner Samsung Ex-1004, 0450

Issue Classification	Application/Control No.	Applicant(s)/Patent Under Reexamination
	18/229,907	Nix, John A.
	Examiner	**Art Unit**
	David García Cervetti	2419

CPC								
Symbol							**Type**	**Version**
H04W	/	52	/	0216			I	2013-01-01
H04L	/	63	/	0807			I	2013-01-01
H04L	/	9	/	0816			I	2013-01-01
H04L	/	12	/	2854			I	2013-01-01
H04L	/	9	/	3263			I	2013-01-01
H04W	/	12	/	02			I	2013-01-01
H04L	/	63	/	0435			I	2013-01-01
H04L	/	9	/	3239			I	2013-01-01
H04L	/	9	/	0662			I	2013-01-01
H04L	/	9	/	0891			I	2013-01-01
G06F	/	21	/	33			I	2013-01-01
H04L	/	9	/	0844			I	2013-01-01
H04L	/	63	/	06			I	2013-01-01
H04W	/	12	/	03			I	2021-01-01
H04W	/	12	/	041			I	2021-01-01
H04L	/	2209	/	72			A	2013-01-01
H04L	/	2209	/	805			A	2013-01-01
G06F	/	2221	/	2105			A	2013-01-01
H04W	/	84	/	12			A	2013-01-01
G06F	/	2221	/	2115			A	2013-01-01
H04L	/	63	/	0464			A	2013-01-01
G06F	/	2221	/	2107			A	2013-01-01
H04W	/	88	/	12			A	2013-01-01
H04L	/	2209	/	24			A	2013-01-01
H04L	/	2209	/	80			A	2013-01-01
H04L	/	2209	/	56			A	2013-01-01
Y02D	/	30	/	70			A	2020-08-01

NONE		**Total Claims Allowed:**	
(Assistant Examiner)	(Date)	20	
/David Garcia Cervetti/ Primary Examiner, Art Unit 2419	22 July 2024	O.G. Print Claim(s)	O.G. Print Figure
(Primary Examiner)	(Date)	1	1

U.S. Patent and Trademark Office — Part of Paper No.: 20240722

Petitioner Samsung Ex-1004, 0451

Issue Classification	Application/Control No.	Applicant(s)/Patent Under Reexamination
	18/229,907	Nix, John A.
	Examiner	**Art Unit**
	David García Cervetti	2419

CPC Combination Sets									
Symbol					**Type**	**Set**	**Ranking**	**Version**
	/		/					

NONE		**Total Claims Allowed:**	
(Assistant Examiner)	(Date)	20	
/David Garcia Cervetti/ Primary Examiner, Art Unit 2419	22 July 2024	O.G. Print Claim(s)	O.G. Print Figure
(Primary Examiner)	(Date)	1	1

U.S. Patent and Trademark Office — Part of Paper No.: 20240722

Petitioner Samsung Ex-1004, 0452

Issue Classification	Application/Control No.	Applicant(s)/Patent Under Reexamination
	18/229,907	Nix, John A.
	Examiner	**Art Unit**
	David García Cervetti	2419

INTERNATIONAL CLASSIFICATION					
CLAIMED					
H04L9/08	/	9	/	08	

NON-CLAIMED					
	/		/		

US ORIGINAL CLASSIFICATION	
CLASS	**SUBCLASS**

CROSS REFERENCES(S)						
CLASS	**SUBCLASS (ONE SUBCLASS PER BLOCK)**					

NONE (Assistant Examiner) (Date)	**Total Claims Allowed:** 20	
/David Garcia Cervetti/ Primary Examiner, Art Unit 2419 (Primary Examiner) 22 July 2024 (Date)	O.G. Print Claim(s) 1	O.G. Print Figure 1

Issue Classification	Application/Control No.	Applicant(s)/Patent Under Reexamination
	18/229,907	Nix, John A.
	Examiner	**Art Unit**
	David García Cervetti	2419

☐ Claims renumbered in the same order as presented by applicant ☐ CPA ☑ T.D. ☐ R.1.47

CLAIMS

Final	Original	Final	Original	Final	Original	Final	Original	Final	Original	Final	Original	Final	Original	Final	Original
	1		10		19	6	28	15	37						
	2		11		20	7	29	16	38						
	3		12		21	8	30	17	39						
	4		13		22	9	31	18	40						
	5		14	1	23	10	32	19	41						
	6		15	2	24	11	33	20	42						
	7		16	3	25	12	34								
	8		17	4	26	13	35								
	9		18	5	27	14	36								

NONE		**Total Claims Allowed:**	
(Assistant Examiner)	(Date)	20	
/David Garcia Cervetti/ Primary Examiner, Art Unit 2419	22 July 2024	O.G. Print Claim(s)	O.G. Print Figure
(Primary Examiner)	(Date)	1	1

U.S. Patent and Trademark Office Part of Paper No.: 20240722

Petitioner Samsung Ex-1004, 0454

OK TO ENTER: /DGC/

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant:	Network-1 Technologies, Inc.	Confirmation No.: 7483
Title:	Key Derivation for a Module Using an Embedded Universal Integrated Circuit Card	
Appl. No.:	18/229,907	
Filing Date:	August 3, 2023	
Examiner:	Cervetti, David Garcia	
Art Unit:	2419	
Docket No.:	63121/0224	
Customer No.:	01912	

SUPPLEMENTAL AMENDMENT IN RESPONSE TO ADVISORY ACTION DATED JUNE 25, 2024 AND FINAL OFFICE ACTION DATED APRIL 9, 2024

VIA EFS

Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

Sir:

This is a response to the Advisory Action dated June 25, 2024 and is a further response to the Office Action dated April 9, 2024. A response to the Office Action was filed on May 29, 2024 and the Advisory Action issued on June 25, 2024. A response to the Office Action is due on July 9, 2024. Accordingly, the present Amendment is being timely filed.

A Listing of the Claims begins on page **2** of this paper.

Remarks begin on page **6** of this paper.

Petitioner Samsung Ex-1004, 0455

PE2E SEARCH - Search History (Prior Art)

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	British Equivalents	Time Stamp
L320	190	(H04L9/0861 OR G06F21/33 OR G06F21/35 OR H04J11/00 OR H04L9/006 OR H04L9/0662 OR H04L9/0816 OR H04L9/0841 OR H04L9/0844 OR H04L9/085 OR H04L9/088 OR H04L9/0891 OR H04L9/0894 OR H04L9/14 OR H04L9/30 OR H04L9/3066 OR H04L9/32 OR H04L9/321 OR H04L9/3239 OR H04L9/3247 OR H04L9/3249 OR H04L9/3263 OR H04L12/2854 OR H04L63/0272 OR H04L63/0435 OR H04L63/0442 OR H04L63/045 OR H04L63/06 OR H04L63/061 OR H04L63/0807 OR H04L63/123 OR H04L63/166 OR H04L67/04 OR H04W4/70 OR H04W8/082 OR H04W12/02 OR H04W12/03 OR H04W12/04 OR H04W12/041 OR H04W12/06 OR H04W40/005 OR H04W52/0216 OR H04W52/0235 OR H04W52/0277 OR H04W76/27 OR H04W80/04 OR G06F2221/2105 OR G06F2221/2107 OR G06F2221/2115 OR H04L63/0464 OR H04L2209/24 OR H04L2209/56 OR H04L2209/72 OR	(US-PGPUB; USPAT; USOCR; FIT (AP, AT, AU, BE, BG, BR, BY, CA, CH, CN, CS, CU, CZ, DD, DK, EA, EE, ES, FI, FR, GB, HR, HU, ID, IE, IL, IS, IT, JP, KR, LT, LU, LV, MA, MC, MD, MY, NL, NO, NZ, PH, PL, PT, RO, RS, RU, SE, SG, SI, SK, SU, TH, TN, TR, TW, UA, VN, WO); FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2024/07/22 12:51 PM

Petitioner Samsung Ex-1004, 0456

		H04L2209/80 OR H04L2209/805 OR H04W84/12 OR H04W88/12 OR Y02D30/70 OR H04W8/205).cpc. AND (uicc euicc e$1uicc universal$8 near4 integrat$8 sim subscri$8) near8 private near4 key WITH public near4 key AND decryp$8 near6 key AND (elliptic$8 ecdh ec$1dh diffie) AND key near6 (agree$8 exchan$8) AND (uicc euicc universal$8 near4 integrat$8 sim subscri$8) AND server AND network near8 (public near4 key)					
L321	67	(H04L9/0861 OR G06F21/33 OR G06F21/35 OR H04J11/00 OR H04L9/006 OR H04L9/0662 OR H04L9/0816 OR H04L9/0841 OR H04L9/0844 OR H04L9/085 OR H04L9/088 OR H04L9/0891 OR H04L9/0894 OR H04L9/14 OR H04L9/30 OR H04L9/3066 OR H04L9/32 OR H04L9/321 OR H04L9/3239 OR H04L9/3247 OR H04L9/3249 OR H04L9/3263 OR H04L12/2854 OR H04L63/0272 OR H04L63/0435 OR H04L63/0442 OR H04L63/045 OR H04L63/06 OR H04L63/061 OR H04L63/0807 OR H04L63/123 OR H04L63/166 OR H04L67/04 OR H04W4/70 OR H04W8/082 OR H04W12/02 OR	(US-PGPUB; USPAT; USOCR; FIT (AP, AT, AU, BE, BG, BR, BY, CA, CH, CN, CS, CU, CZ, DD, DK, EA, EE, ES, FI, FR, GB, HR, HU, ID, IE, IL, IS, IT, JP, KR, LT, LU, LV, MA, MC, MD, MY, NL, NO, NZ, PH, PL, PT, RO, RS, RU, SE, SG, SI, SK, SU, TH, TN, TR, TW, UA, VN, WO); FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2024/07/22 12:54 PM

Petitioner Samsung Ex-1004, 0457

		H04W12/03 OR H04W12/04 OR H04W12/041 OR H04W12/06 OR H04W40/005 OR H04W52/0216 OR H04W52/0235 OR H04W52/0277 OR H04W76/27 OR H04W80/04 OR G06F2221/2105 OR G06F2221/2107 OR G06F2221/2115 OR H04L63/0464 OR H04L2209/24 OR H04L2209/56 OR H04L2209/72 OR H04L2209/80 OR H04L2209/805 OR H04W84/12 OR H04W88/12 OR Y02D30/70 OR H04W8/205).cpc. AND (uicc euicc e$1uicc universal$8 near4 integrat$8 sim subscri$8) near8 private near4 key WITH public near4 key AND decryp$8 near6 key AND (elliptic$8 ecdh ec$1dh diffie) AND key near6 (agree$8 exchan$8) AND (uicc euicc universal$8 near4 integrat$8 sim subscri$8) AND server AND network near8 (public near4 key) AND (@pd @prad @rlad @ptad @ad)<"20131120"					
L322	40	(H04L9/0861 OR G06F21/33 OR G06F21/35 OR H04J11/00 OR H04L9/006 OR H04L9/0662 OR H04L9/0816 OR H04L9/0841 OR H04L9/0844 OR H04L9/085 OR H04L9/088 OR H04L9/0891 OR H04L9/0894 OR H04L9/14 OR H04L9/30 OR H04L9/3066 OR	(US-PGPUB; USPAT)	OR	ON	ON	2024/07/22 12:55 PM

Petitioner Samsung Ex-1004, 0458

		H04L9/32 OR H04L9/321 OR H04L9/3239 OR H04L9/3247 OR H04L9/3249 OR H04L9/3263 OR H04L12/2854 OR H04L63/0272 OR H04L63/0435 OR H04L63/0442 OR H04L63/045 OR H04L63/06 OR H04L63/061 OR H04L63/0807 OR H04L63/123 OR H04L63/166 OR H04L67/04 OR H04W4/70 OR H04W8/082 OR H04W12/02 OR H04W12/03 OR H04W12/04 OR H04W12/041 OR H04W12/06 OR H04W40/005 OR H04W52/0216 OR H04W52/0235 OR H04W52/0277 OR H04W76/27 OR H04W80/04 OR G06F2221/2105 OR G06F2221/2107 OR G06F2221/2115 OR H04L63/0464 OR H04L2209/24 OR H04L2209/56 OR H04L2209/72 OR H04L2209/80 OR H04L2209/805 OR H04W84/12 OR H04W88/12 OR Y02D30/70 OR H04W8/205).cpc. AND (uicc euicc e$1uicc universal$8 near4 integrat$8 sim subscri$8) near8 private near4 key WITH public near4 key AND decryp$8 near6 key AND (elliptic$8 ecdh ec$1dh diffie) AND key near6 (agree$8 exchan$8) AND (uicc euicc universal$8 near4 integrat$8 sim subscri$8) AND server AND network near8					

Petitioner Samsung Ex-1004, 0459

		(public near4 key) AND (@pd @prad @rlad @ptad @ad)<"20131120"					

PE2E SEARCH - Search History (Interference)

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	British Equivalents	Time Stamp
N184	581	private near4 key WITH public near4 key.clm. AND decryp$8 near6 key.clm. AND (elliptic$8 ecdh ec$1dh diffie).clm.	(US-PGPUB; USPAT)	OR	ON	ON	2024/07/22 12:07 PM
N185	210	private near4 key WITH public near4 key.clm. AND decryp$8 near6 key.clm. AND (elliptic$8 ecdh ec$1dh diffie).clm. AND key near6 (agree$8 exchan$8).clm.	(US-PGPUB; USPAT)	OR	ON	ON	2024/07/22 12:08 PM
N186	30	private near4 key WITH public near4 key.clm. AND decryp$8 near6 key.clm. AND (elliptic$8 ecdh ec$1dh diffie).clm. AND key near6 (agree$8 exchan$8).clm. AND (uicc euicc universal$8 near4 integrat$8 sim subscri$8).clm.	(US-PGPUB; USPAT)	OR	ON	ON	2024/07/22 12:09 PM
N187	17	(uicc euicc e$1uicc universal$8 near4 integrat$8 sim subscri$8) near8 private near4 key WITH public near4 key.clm. AND decryp$8 near6 key.clm. AND (elliptic$8 ecdh ec$1dh diffie).clm. AND key near6 (agree$8 exchan$8).clm. AND (uicc euicc universal$8 near4 integrat$8 sim subscri$8).clm.	(US-PGPUB; USPAT)	OR	ON	ON	2024/07/22 12:21 PM
N188	7	(uicc euicc e$1uicc universal$8 near4 integrat$8 sim subscri$8) near8 private near4 key WITH public near4 key.clm. AND decryp$8 near6	(US-PGPUB; USPAT)	OR	ON	ON	2024/07/22 12:22 PM

Petitioner Samsung Ex-1004, 0460

		key.clm. AND (elliptic$8 ecdh ec$1dh diffie).clm. AND key near6 (agree$8 exchan$8).clm. AND (uicc euicc universal$8 near4 integrat$8 sim subscri$8).clm. AND server.clm. AND network.clm.					
N189	5	(uicc euicc e$1uicc universal$8 near4 integrat$8 sim subscri$8) near8 private near4 key WITH public near4 key.clm. AND decryp$8 near6 key.clm. AND (elliptic$8 ecdh ec$1dh diffie).clm. AND key near6 (agree$8 exchan$8).clm. AND (uicc euicc universal$8 near4 integrat$8 sim subscri$8).clm. AND server.clm. AND network near8 (public near4 key).clm.	(US-PGPUB; USPAT)	OR	ON	ON	2024/07/22 12:22 PM

UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

NOTICE OF ALLOWANCE AND FEE(S) DUE

1912 7590 08/01/2024

AMSTER, ROTHSTEIN & EBENSTEIN LLP
405 LEXINGTON AVENUE
FLOOR 48
NEW YORK, NY 10174

EXAMINER	
CERVETTI, DAVID GARCIA	
ART UNIT	PAPER NUMBER
2419	

DATE MAILED: 08/01/2024

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
18/229,907	08/03/2023	John A. Nix	63121/0224	7483

TITLE OF INVENTION: Key Derivation for a Module Using an Embedded Universal Integrated Circuit Card

APPLN. TYPE	ENTITY STATUS	ISSUE FEE DUE	PUBLICATION FEE DUE	PREV. PAID ISSUE FEE	TOTAL FEE(S) DUE	DATE DUE
nonprovisional	SMALL	$480	$0.00	$0.00	$480	11/01/2024

THE APPLICATION IDENTIFIED ABOVE HAS BEEN EXAMINED AND IS ALLOWED FOR ISSUANCE AS A PATENT. PROSECUTION ON THE MERITS IS CLOSED. THIS NOTICE OF ALLOWANCE IS NOT A GRANT OF PATENT RIGHTS. THIS APPLICATION IS SUBJECT TO WITHDRAWAL FROM ISSUE AT THE INITIATIVE OF THE OFFICE OR UPON PETITION BY THE APPLICANT. SEE 37 CFR 1.313 AND MPEP 1308.

THE ISSUE FEE AND PUBLICATION FEE (IF REQUIRED) MUST BE PAID WITHIN THREE MONTHS FROM THE MAILING DATE OF THIS NOTICE OR THIS APPLICATION SHALL BE REGARDED AS ABANDONED. THIS STATUTORY PERIOD CANNOT BE EXTENDED. SEE 35 U.S.C. 151. THE ISSUE FEE DUE INDICATED ABOVE DOES NOT REFLECT A CREDIT FOR ANY PREVIOUSLY PAID ISSUE FEE IN THIS APPLICATION. IF AN ISSUE FEE HAS PREVIOUSLY BEEN PAID IN THIS APPLICATION (AS SHOWN ABOVE), THE RETURN OF PART B OF THIS FORM WILL BE CONSIDERED A REQUEST TO REAPPLY THE PREVIOUSLY PAID ISSUE FEE TOWARD THE ISSUE FEE NOW DUE.

HOW TO REPLY TO THIS NOTICE:

I. Review the ENTITY STATUS shown above. If the ENTITY STATUS is shown as SMALL or MICRO, verify whether entitlement to that entity status still applies.

If the ENTITY STATUS is the same as shown above, pay the TOTAL FEE(S) DUE shown above.

If the ENTITY STATUS is changed from that shown above, on PART B - FEE(S) TRANSMITTAL, complete section number 5 titled "Change in Entity Status (from status indicated above)".

For purposes of this notice, small entity fees are 40% the amount of undiscounted fees, and micro entity fees are 20% the amount of undiscounted fees.

II. PART B - FEE(S) TRANSMITTAL, or its equivalent, must be completed and returned to the United States Patent and Trademark Office (USPTO) with your ISSUE FEE and PUBLICATION FEE (if required). If you are charging the fee(s) to your deposit account, section "4b" of Part B - Fee(s) Transmittal should be completed. If an equivalent of Part B is filed, a request to reapply a previously paid issue fee must be clearly made, and delays in processing may occur due to the difficulty in recognizing the paper as an equivalent of Part B.

III. All communications regarding this application must give the application number. Please direct all communications prior to issuance to Mail Stop ISSUE FEE unless advised to the contrary.

IMPORTANT REMINDER: Maintenance fees are due in utility patents issuing on applications filed on or after Dec. 12, 1980. It is patentee's responsibility to ensure timely payment of maintenance fees when due. More information is available at www.uspto.gov/PatentMaintenanceFees.

PTOL-85 (Rev. 11/23)

Petitioner Samsung Ex-1004, 0462

PART B - FEE(S) TRANSMITTAL

Complete and send this form, together with applicable fee(s), by mail or fax, or via the USPTO patent electronic filing system.

By mail, send to: Mail Stop ISSUE FEE
Commissioner for Patents
P.O. Box 1450
Alexandria, Virginia 22313-1450

By fax, send to: (571)-273-2885

INSTRUCTIONS: This form should be used for transmitting the ISSUE FEE and PUBLICATION FEE (if required). Blocks 1 through 5 should be completed where appropriate. All further correspondence will be mailed to the current correspondence address as indicated unless corrected below or directed otherwise in Block 1, by (a) specifying a new correspondence address; and/or (b) indicating a separate "FEE ADDRESS" for maintenance fee notifications. **Because electronic patent issuance may occur shortly after issue fee payment, any desired continuing application should preferably be filed prior to payment of this issue fee in order not to jeopardize copendency.**

CURRENT CORRESPONDENCE ADDRESS (Note: Use Block 1 for any change of address)

1912 7590 08/01/2024
AMSTER, ROTHSTEIN & EBENSTEIN LLP
405 LEXINGTON AVENUE
FLOOR 48
NEW YORK, NY 10174

Note: A certificate of mailing can only be used for domestic mailings of the Fee(s) Transmittal. This certificate cannot be used for any other accompanying papers. Each additional paper, such as an assignment or formal drawing, must have its own certificate of mailing or transmission.

Certificate of Mailing or Transmission

I hereby certify that this Fee(s) Transmittal is being deposited with the United States Postal Service with sufficient postage for first class mail in an envelope addressed to the Mail Stop ISSUE FEE address above, or being transmitted to the USPTO via the USPTO patent electronic filing system or by facsimile to (571) 273-2885, on the date below.

(Typed or printed name)
(Signature)
(Date)

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
18/229,907	08/03/2023	John A. Nix	63121/0224	7483

TITLE OF INVENTION: Key Derivation for a Module Using an Embedded Universal Integrated Circuit Card

APPLN. TYPE	ENTITY STATUS	ISSUE FEE DUE	PUBLICATION FEE DUE	PREV. PAID ISSUE FEE	TOTAL FEE(S) DUE	DATE DUE
nonprovisional	SMALL	$480	$0.00	$0.00	$480	11/01/2024

EXAMINER	ART UNIT	CLASS-SUBCLASS
CERVETTI, DAVID GARCIA	2419	713-168000

1. Change of correspondence address or indication of "Fee Address" (37 CFR 1.363).

❑ Change of correspondence address (or Change of Correspondence Address form PTO/AIA/122 or PTO/SB/122) attached.

❑ "Fee Address" indication (or "Fee Address" Indication form PTO/AIA/47 or PTO/SB/47; Rev 03-02 or more recent) attached. **Use of a Customer Number is required.**

2. For printing on the patent front page, list
(1) The names of up to 3 registered patent attorneys or agents OR, alternatively,
(2) The name of a single firm (having as a member a registered attorney or agent) and the names of up to 2 registered patent attorneys or agents. If no name is listed, no name will be printed.

1 _____
2 _____
3 _____

3. ASSIGNEE NAME AND RESIDENCE DATA TO BE PRINTED ON THE PATENT (print or type)

PLEASE NOTE: Unless an assignee is identified below, no assignee data will appear on the patent. If an assignee is identified below, the document must have been previously recorded, or filed for recordation, as set forth in 37 CFR 3.11 and 37 CFR 3.81(a). Completion of this form is NOT a substitute for filing an assignment.

(A) NAME OF ASSIGNEE (B) RESIDENCE: (CITY and STATE OR COUNTRY)

Please check the appropriate assignee category or categories (will not be printed on the patent) : ❑ Individual ❑ Corporation or other private group entity ❑ Government

4a. Fees submitted: ❑ Issue Fee ❑ Publication Fee (if required)

4b. Method of Payment: *(Please first reapply any previously paid fee shown above)*

❑ Electronic Payment via the USPTO patent electronic filing system ❑ Enclosed check ❑ Non-electronic payment by credit card (Attach form PTO-2038)

❑ The Director is hereby authorized to charge the required fee(s), any deficiency, or credit any overpayment to Deposit Account No. _____

5. **Change in Entity Status** (from status indicated above)

❑ Applicant certifying micro entity status. See 37 CFR 1.29

NOTE: Absent a valid certification of Micro Entity Status (see forms PTO/SB/15A and 15B), issue fee payment in the micro entity amount will not be accepted at the risk of application abandonment.

❑ Applicant asserting small entity status. See 37 CFR 1.27

NOTE: If the application was previously under micro entity status, checking this box will be taken to be a notification of loss of entitlement to micro entity status.

❑ Applicant changing to regular undiscounted fee status.

NOTE: Checking this box will be taken to be a notification of loss of entitlement to small or micro entity status, as applicable.

NOTE: This form must be signed in accordance with 37 CFR 1.31 and 1.33. See 37 CFR 1.4 for signature requirements and certifications.

Authorized Signature _____ Date _____

Typed or printed name _____ Registration No. _____

Petitioner Samsung Ex-1004, 0463

UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
18/229,907	08/03/2023	John A. Nix	63121/0224	7483

1912 7590 08/01/2024

AMSTER, ROTHSTEIN & EBENSTEIN LLP
405 LEXINGTON AVENUE
FLOOR 48
NEW YORK, NY 10174

EXAMINER	
CERVETTI, DAVID GARCIA	
ART UNIT	PAPER NUMBER
2419	

DATE MAILED: 08/01/2024

Determination of Patent Term Adjustment under 35 U.S.C. 154 (b)
(Applications filed on or after May 29, 2000)

The Office has discontinued providing a Patent Term Adjustment (PTA) calculation with the Notice of Allowance.

Section 1(h)(2) of the AIA Technical Corrections Act amended 35 U.S.C. 154(b)(3)(B)(i) to eliminate the requirement that the Office provide a patent term adjustment determination with the notice of allowance. See Revisions to Patent Term Adjustment, 78 Fed. Reg. 19416, 19417 (Apr. 1, 2013). Therefore, the Office is no longer providing an initial patent term adjustment determination with the notice of allowance. The Office will continue to provide a patent term adjustment determination with the Issue Notification Letter that is mailed to applicant approximately three weeks prior to the issue date of the patent, and will include the patent term adjustment on the patent. Any request for reconsideration of the patent term adjustment determination (or reinstatement of patent term adjustment) should follow the process outlined in 37 CFR 1.705.

Any questions regarding the Patent Term Extension or Adjustment determination should be directed to the Office of Patent Legal Administration at (571)-272-7702. Questions relating to issue and publication fee payments should be directed to the Customer Service Center of the Office of Patent Publication at 1-(888)-786-0101 or (571)-272-4200.

Petitioner Samsung Ex-1004, 0464

OMB Clearance and PRA Burden Statement for PTOL-85 Part B

The Paperwork Reduction Act (PRA) of 1995 requires Federal agencies to obtain Office of Management and Budget approval before requesting most types of information from the public. When OMB approves an agency request to collect information from the public, OMB (i) provides a valid OMB Control Number and expiration date for the agency to display on the instrument that will be used to collect the information and (ii) requires the agency to inform the public about the OMB Control Number's legal significance in accordance with 5 CFR 1320.5(b).

The information collected by PTOL-85 Part B is required by 37 CFR 1.311. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 30 minutes to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, Virginia 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, Virginia 22313-1450. Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Privacy Act Statement

The Privacy Act of 1974 (P.L. 93-579) requires that you be given certain information in connection with your submission of the attached form related to a patent application or patent. The United States Patent and Trademark Office (USPTO) collects the information in this record under authority of 35 U.S.C. 2. The USPTO's system of records is used to manage all applicant and owner information including name, citizenship, residence, post office address, and other information with respect to inventors and their legal representatives pertaining to the applicant's/ owner's activities in connection with the invention for which a patent is sought or has been granted. The applicable Privacy Act System of Records Notice for the information collected in this form is COMMERCE/PAT-TM-7 Patent Application Files, available in the Federal Register at 78 FR 19243 (March 29, 2013).
https://www.govinfo.gov/content/pkg/FR-2013-03-29/pdf/2013-07341.pdf

Routine uses of the information in this record may include disclosure to:

1) law enforcement, in the event that the system of records indicates a violation or potential violation of law;
2) a federal, state, local, or international agency, in response to its request;
3) a contractor of the USPTO having need for the information in order to perform a contract;
4) the Department of Justice for determination of whether the Freedom of Information Act (FOIA) requires disclosure of the record;
5) a Member of Congress submitting a request involving an individual to whom the record pertains, when the individual has requested the Member's assistance with respect to the subject matter of the record;
6) a court, magistrate, or administrative tribunal, in the course of presenting evidence, including disclosures to opposing counsel in the course of settlement negotiations;
7) the Administrator, General Services Administration (GSA), or their designee, during an inspection of records conducted by GSA under authority of 44 U.S.C. 2904 and 2906, in accordance with the GSA regulations and any other relevant (i.e., GSA or Commerce) directive, where such disclosure shall not be used to make determinations about individuals;
8) another federal agency for purposes of National Security review (35 U.S.C. 181) and for review pursuant to the Atomic Energy Act (42 U.S.C. 218(c));
9) the Office of Personnel Management (OPM) for personnel research purposes; and
10) the Office of Management and Budget (OMB) for legislative coordination and clearance.

If you do not furnish the information requested on this form, the USPTO may not be able to process and/or examine your submission, which may result in termination of proceedings, abandonment of the application, and/or expiration of the patent.

Notice of Allowability	Application No. 18/229,907	Applicant(s) Nix, John A.	
	Examiner David García Cervetti	Art Unit 2419	AIA (FITF) Status Yes

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address--

All claims being allowable, PROSECUTION ON THE MERITS IS (OR REMAINS) CLOSED in this application. If not included herewith (or previously mailed), a Notice of Allowance (PTOL-85) or other appropriate communication will be mailed in due course. **THIS NOTICE OF ALLOWABILITY IS NOT A GRANT OF PATENT RIGHTS.** This application is subject to withdrawal from issue at the initiative of the Office or upon petition by the applicant. See 37 CFR 1.313 and MPEP 1308.

1. ☑ This communication is responsive to 7/8/2024.
   ☐ A declaration(s)/affidavit(s) under **37 CFR 1.130(b)** was/were filed on _____.

2. ☐ An election was made by the applicant in response to a restriction requirement set forth during the interview on _____; the restriction requirement and election have been incorporated into this action.

3. ☑ The allowed claim(s) is/are 23-42 . As a result of the allowed claim(s), you may be eligible to benefit from the **Patent Prosecution Highway** program at a participating intellectual property office for the corresponding application. For more information, please see **http://www.uspto.gov/patents/init_events/pph/index.jsp** or send an inquiry to **PPHfeedback@uspto.gov.**

4. ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).

   Certified copies:

   a) ☐ All b) ☐ Some* c) ☐ None of the:

   1. ☐ Certified copies of the priority documents have been received.
   2. ☐ Certified copies of the priority documents have been received in Application No. _____ .
   3. ☐ Copies of the certified copies of the priority documents have been received in this national stage application from the International Bureau (PCT Rule 17.2(a)).

   * Certified copies not received: _____ .

Applicant has THREE MONTHS FROM THE "MAILING DATE" of this communication to file a reply complying with the requirements noted below. Failure to timely comply will result in ABANDONMENT of this application.
THIS THREE-MONTH PERIOD IS NOT EXTENDABLE.

5. ☐ CORRECTED DRAWINGS (as "replacement sheets") must be submitted.
   ☐ including changes required by the attached Examiner's Amendment / Comment or in the Office action of Paper No./Mail Date _____ .

   Identifying indicia such as the application number (see 37 CFR 1.84(c)) should be written on the drawings in the front (not the back) of each sheet. Replacement sheet(s) should be labeled as such in the header according to 37 CFR 1.121(d).

6. ☐ DEPOSIT OF and/or INFORMATION about the deposit of BIOLOGICAL MATERIAL must be submitted. Note the attached Examiner's comment regarding REQUIREMENT FOR THE DEPOSIT OF BIOLOGICAL MATERIAL.

Attachment(s)

1. ☑ Notice of References Cited (PTO-892)
2. ☐ Information Disclosure Statements (PTO/SB/08), Paper No./Mail Date _____.
3. ☐ Examiner's Comment Regarding Requirement for Deposit of Biological Material _____.
4. ☐ Interview Summary (PTO-413), Paper No./Mail Date. _____.
5. ☐ Examiner's Amendment/Comment
6. ☑ Examiner's Statement of Reasons for Allowance
7. ☐ Other _____.

/David Garcia Cervetti/
Primary Examiner, Art Unit 2419

Petitioner Samsung Ex-1004, 0466

DETAILED ACTION

1. Applicant's amendment filed 7/8/2024 has been fully considered.

2. Claims 23-42 are pending and have been examined. Claims 1-22 have been canceled.

Notice of Pre-AIA or AIA Status

3. The present application, filed on or after March 16, 2013, is being examined under the first inventor to file provisions of the AIA.

Response to Amendment

4. This communication warrants No Examiner's Reason for Allowance, applicant's reply makes evident the reasons for allowance, satisfying the "record as a whole" provision of the rule 37 CFR 1.104(e). Specifically, applicant's arguments filed on 7/8/2024 are persuasive, as such the reasons for allowance are in all probability evident from the record and no statement is deemed necessary (see MPEP 1302.14).

5. The provisional Double Patenting rejection is withdrawn in view of the Terminal Disclaimer filed on 5/29/2024.

Terminal Disclaimer

6. The terminal disclaimer filed on 5/29/2024 disclaiming the terminal portion of any patent granted on this application which would extend beyond the expiration date of US Patent No. 9319223, 9742562, 10187206, 10498530, 10700856, 11258595, 11736283, and 11082218 has been reviewed and is accepted. The terminal disclaimer has been recorded.

Allowable Subject Matter

7. Claims 23-42 are allowed.

8. Any comments considered necessary by applicant must be submitted no later than the payment of the issue fee and, to avoid processing delays, should preferably accompany the issue fee. Such submissions should be clearly labeled "Comments on Statement of Reasons for Allowance."

Conclusion

9. The prior art made of record and not relied upon is considered pertinent to applicant's disclosure. Nakhjiri (20140082359).

10. Any inquiry concerning this communication or earlier communications from the examiner should be directed to David Garcia Cervetti whose telephone number is (571)272-5861. The examiner can normally be reached Monday-Friday 8AM-5PM.

11. Examiner interviews are available via telephone, in-person, and video conferencing using a USPTO supplied web-based collaboration tool. To schedule an interview, applicant is encouraged to use the USPTO Automated Interview Request (AIR) at http://www.uspto.gov/interviewpractice.

12. If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, HADI ARMOUCHE can be reached on (571)270-3618. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

13. Information regarding the status of published or unpublished applications may be obtained from Patent Center. Unpublished application information in Patent Center is available to registered users. To file and manage patent submissions in Patent Center, visit: https://patentcenter.uspto.gov. Visit https://www.uspto.gov/patents/apply/patent-center for more information about Patent Center and https://www.uspto.gov/patents/docx for information about filing in DOCX format. For additional questions, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

/David Garcia Cervetti/
Primary Examiner, Art Unit 2419

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant:	Network-1 Technologies, Inc.	Confirmation No.: 7483
Title:	Key Derivation for a Module Using an Embedded Universal Integrated Circuit Card	
Appl. No.:	18/229,907	
Filing Date:	August 3, 2023	
Examiner:	Cervetti, David Garcia	
Art Unit:	2419	
Docket No.:	63121/0224	
Customer No.:	01912	

AMENDMENT AFTER NOTICE OF ALLOWANCE UNDER 37 C.F.R. 1.312

VIA EFS

Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

Sir:

Please enter the following amendments and consider the following remarks following the Notice of Allowance dated August 1, 2024.

Amendments to the Claims begin on page **2** of this paper.

Remarks begin on page **5** of this paper.

Petitioner Samsung Ex-1004, 0469

IN THE CLAIMS

This Listing of Claims will replace all prior versions, and listings, of claims in the application:

1-22 (Cancelled)

23. (Currently Amended) A method for a mobile device with an embedded universal integrated circuit card (eUICC) to securely communicate with a wireless network, the method performed by the mobile device, the method comprising:

a) storing, in the eUICC, a first module private key, a corresponding first module public key, and a network public key;

b) receiving, from a first server associated with the wireless network, an encrypted profile for the eUICC comprising cryptographic parameters, a module identity, and a key K;

c) generating a shared secret key using a first elliptic curve Diffie-Hellman (ECDH) key exchange with the first module private key and the network public key;

d) decrypting, with the shared secret key, at least a portion of the encrypted profile for the eUICC;

e) generating, by the eUICC, a second module public key and a corresponding second module private key;

f) sending, to a second server associated with the wireless network, the second module public key;

g) generating a symmetric key using a second ECDH key exchange with the second module private key and the cryptographic parameters;

h) generating, with the symmetric key, module encrypted data, the module encrypted data comprising the module identity; and

i) sending, to the ~~servers~~ second server, the module encrypted data.

24. (Previously Presented) The method of claim 23, wherein the module identity comprises an international mobile subscriber identity (IMSI).

Petitioner Samsung Ex-1004, 0470

25. (Previously Presented) The method of claim 23, wherein the module identity comprises a permanent identifier for the mobile device.

26. (Previously Presented) The method of claim 23, wherein the cryptographic parameters comprise an identifier for a set of cryptographic parameters.

27. (Previously Presented) The method of claim 23, further comprising in step c) deriving the shared secret key using an American National Standards Institute (ANSI) standard X-9.63 key derivation function.

28. (Previously Presented) The method of claim 23, further comprising in step g) deriving the symmetric key using an ANSI standard X-9.63 key derivation function.

29. (Previously Presented) The method of claim 23, wherein the first server mutually derives the shared secret key using the first ECDH key exchange with the first module public key and a network private key corresponding to the network public key.

30. (Previously Presented) The method of claim 23, further comprising in step e), generating, by the eUICC, the second module public key and the second module private key using a random number generator and input from a sensor.

31. (Previously Presented) The method of claim 23, further comprising in step h) generating, with the symmetric key and an Advanced Encryption Standard (AES), the module encrypted data.

32. (Previously Presented) The method of claim 23, wherein steps g) and h) occur before step f).

33. (Previously Presented) The method of claim 23, wherein the network public key is associated with an eUICC subscription manager.

Petitioner Samsung Ex-1004, 0471

34. (Currently Amended) The method of claim 33, wherein [[(i)]] the eUICC subscription manager comprises the first server.

35. (Previously Presented) The method of claim 23, further comprising: j) receiving, from the wireless network, a random number (RAND) and generating a response (RES) using the RAND and the key K.

36. (Previously Presented) The method of claim 23, further comprising before step b), authenticating the first server by (i) receiving a server digital signature and (ii) verifying the server digital signature with a server public key.

37. (Previously Presented) The method of claim 23, further comprising (i) in step a), storing a server name for the first server and a port number in a nonvolatile memory of the eUICC, and (ii) before step b) sending the first module public key to the first server.

38. (Previously Presented) The method of claim 23, wherein the first server, the second server, and the wireless network are associated with a mobile network operator.

39. (Previously Presented) The method of claim 23, wherein the eUICC comprises a processor, firmware, and protected memory.

40. (Previously Presented) The method of claim 23, wherein the cryptographic parameters include a base point G for an elliptic curve.

41. (Previously Presented) The method of claim 23, wherein the mobile device comprises a wireless device with a radio for communicating with a plurality of base stations for the wireless network.

42. (Previously Presented) The method of claim 23, wherein the eUICC comprises a package soldered to a circuit board of the mobile device.

Petitioner Samsung Ex-1004, 0472

REMARKS

The amendments to the claims and the following remarks are submitted under 37 CFR § 1.312 following the Notice of Allowance dated August 1, 2024.

Claims 23-42 are pending in the present application and have been allowed. Applicant has amended claims 23 and 34 to address minor informalities. It is submitted that no new matter has been introduced by this Amendment. Applicant respectfully requests that the foregoing amendments be promptly entered.

I. Reference to Related Patents and Co-Pending Applications

The below chart provides information regarding related issued patents and co-pending applications filed by the present Applicant:

Petitioner Samsung Ex-1004, 0473

Serial No.	Attorney Docket No.	Filing Date	Status
18/435,042	63121/230	2024-02-07	Pending – Awaiting First Office Action
18/587,462	63121/0229	2024-02-26	Pending – Awaiting First Office Action
18/435,042	63121/0228	2024-02-06	Pending – Awaiting First Office Action
18/438,147	63121/0227	2024-02-09	Pending – Awaiting First Office Action
18/416,534	63121/0226	2024-01-18	Pending – Awaiting First Office Action
18/433,664	63121/0225	2024-02-26	Pending – Awaiting First Office Action
18/229,907	**63121/0224**	**2023-08-03**	**(Present Application) Pending - Case Docketed to Examiner**
18/111,669	63121/0222	2023-02-20	USP 11,973,864
17/647,812	63121/0213	2022-01-13	USP 11,606,204
17/547,990	63121/0212	2021-12-10	USP 11,736,283
17/304,922	63121/0209	2021-06-28	USP 11,736,283
17/249,242	63121/0202	2021-02-24	USP 11,973,863
16/879,325	63121/0198	2020-05-20	USP 11,082,218
16/843,107	63121/0197	2020-04-08	USP 11,283,603
16/721,153	63121/0195	2019-12-19	USP 11,539,681
16/593,561	63121/0190	2019-10-04	USP 11,258,595
16/453,682	63121/0184	2019-06-26	USP 11,233,780
16/271,455	63121/0181	2019-02-08	USP 10,594,679
16/271,428	63121/0180	2019-02-08	USP 10,523,432
16/201,401	63121/0179	2018-11-27	USP 10,700,856
16/200,118	63121/0178	2018-11-26	USP 10,498,530
16/110,804	63121/0168	2018-08-23	USP 10,382,422
16/036,506	63121/0167	2018-07-16	USP 10,530,575
15/983,957	63121/0163	2018-05-18	USP 10,177,911
15/973,012	63121/0162	2018-05-07	USP 10,250,386
15/972,914	63121/0161	2018-05-07	USP 10,652,017
15/928,848	63121/0160	2018-03-22	USP 10,084,768
15/010,905	63121/0157	2016-01-29	USP 9,641,327
15/680,758	63121/0147	2017-08-18	USP 10,187,206
15/162,292	63121/0146	2016-05-23	USP 10,362,012
14/751,119	63121/0145	2015-06-25	USP 9,961,060
15/457,700	63121/0144	2017-03-13	USP 9,998,281
15/583,968	63121/0143	2017-05-01	USP 10,057,059
15/043,293	63121/0142	2016-02-12	USP 9,998,280
15/642,088	63121/0141	2017-07-05	USP 10,003,461
15/130,146	63121/0140	2016-04-15	USP 9,742,562

Petitioner Samsung Ex-1004, 0474

15/162,302	63121/0139	2016-05-23	USP 9,698,981
14/789,255	63121/0138	2015-07-01	USP 9,596,078
14/139,419	63121/0137	2013-12-23	USP 9,351,162
14/136,711	63121/0136	2013-12-20	USP 9,300,473
14/099,329	63121/0135	2013-12-06	USP 9,100,175
14/084,141	63121/0134	2013-11-19	USP 9,319,223
14/064,618	63121/0133	2013-10-28	USP 9,118,464
14/055,606	63121/0132	2013-10-16	USP 9,276,740
14/039,401	63121/0131	2013-09-27	USP 9,288,059
14/023,181	63121/0130	2013-09-10	USP 9,350,550
AU 2019246774	63121-0199	2019-10-08	AU2019246774A1 Issued 2021-09-23
GB 1608573	63121-0151	2014-10-27	Published on 2016-08-03
GB 2100530	63121-0201	2014-10-27	Published on 2021-05-12
CA 2,965,119	63121-0152	2014-10-27	Published on 2015-05-07
HK 17101082.8	63121-0153	2014-10-27	Published on 2017-10-20
EU 14868381.6	63121-0154	2014-12-04	Published on 2017-01-04
CA 2,969,829	63121-0155	2014-12-04	Published on 2015-06-11
HK 17106540.3	63121-0156	2014-12-04	Published on 2018-01-19

The Examiner is invited to review the prosecution history of each of these applications, including the cited references of record and related office actions, as the Examiner deems appropriate.

Favorable reconsideration of the present application is respectfully requested.

If any fees are required in view of the foregoing, the Director is hereby authorized to charge any such fee to Deposit Account No. 01-1785.

Respectfully submitted,

AMSTER, ROTHSTEIN & EBENSTEIN LLP
Attorneys for Applicant
405 Lexington Avenue
New York, NY 10174
(212) 336-8000

Dated: New York, New York
September 5, 2024

By: /Keith J. Barkaus/
Keith J. Barkaus
Registration No. 51,431

Petitioner Samsung Ex-1004, 0475

UNITED STATES
PATENT AND TRADEMARK OFFICE

P.O. Box 1450
Alexandria, VA 22313 - 1450
www.uspto.gov

ELECTRONIC ACKNOWLEDGEMENT RECEIPT

APPLICATION #	RECEIPT DATE / TIME	ATTORNEY DOCKET #
18/229,907	**09/05/2024 04:49:50 PM Z ET**	**63121/0224**

Title of Invention

Key Derivation for a Module Using an Embedded Universal Integrated Circuit Card

Application Information

APPLICATION TYPE	Utility - Nonprovisional Application under 35 USC 111(a)	PATENT #	-
CONFIRMATION #	7483	FILED BY	Victoria GILMORE
PATENT CENTER #	67062583	FILING DATE	08/03/2023
CUSTOMER #	1912	FIRST NAMED INVENTOR	John A. Nix
CORRESPONDENCE ADDRESS	-	AUTHORIZED BY	Keith Barkaus

Documents

TOTAL DOCUMENTS: 3

DOCUMENT		PAGES	DESCRIPTION	SIZE (KB)
1-PA-312 Amendment.pdf		7	-	153 KB
1-PA-312 Amendment-A.NA.pdf	(1-1)	1	Amendment after Notice of Allowance (Rule 312)	120 KB
1-PA-312 Amendment-CLM.pdf	(2-4)	3	Claims	125 KB
1-PA-312 Amendment-REM.pdf	(5-7)	3	Applicant Arguments/Remarks Made in an Amendment	143 KB

Digest

DOCUMENT	MESSAGE DIGEST(SHA-512)
1-PA-312 Amendment.pdf	CE550039D57EDFCE5AEAA4D661847C2D11192A4C6543DF7F

	01EBDC8EB557968F220805C5D204DFE8F732C4C92DD9B71A3368869B72E5B74622F80240A8A7B52B
1-PA-312 Amendment-A.NA.pdf	A8FB106EFC219FF59237B06F925AE8A201998A272BF77553BE3EA4A475401271987A5F23C33CC1517EEE9D7F6F90129ED3C2ACC0BB102F13CC98EE2E7048B804
1-PA-312 Amendment-CLM.pdf	41A6BED0B22A000B8D53F1041A9E2E8013765EDE07BD9397179B04C8020EC18F7F07DF8E71D2766C8DC20B056AB968340AA087C9E99FA88535896498C8A6F073
1-PA-312 Amendment-REM.pdf	7A0437C8530728916ED5494D16A75248532F98C1BF6E2E0332C906A7D082604F87B9717F5CD65006800493A62DB7F5EB4C7D624772578D4FEDD3ABD62FF35129

This Acknowledgement Receipt evidences receipt on the noted date by the USPTO of the indicated documents, characterized by the applicant, and including page counts, where applicable. It serves as evidence of receipt similar to a Post Card, as described in MPEP 503.

New Applications Under 35 U.S.C. 111

If a new application is being filed and the application includes the necessary components for filing date (see 37 CFR 1.53(b)-(d) and MPEP 506), a Filing Receipt (37 CFR 1.54) will be issued in due course and the date shown on this Acknowledgement Receipt will establish the filing date of the application

National Stage of an International Application under 35 U.S.C. 371

If a timely submission to enter the national stage of an international application is compliant with the conditions of 35 U.S.C. 371 and other applicable requirements a Form PCT/DO/EO/903 indicating acceptance of the application as a national stage submission under 35 U.S.C. 371 will be issued in addition to the Filing Receipt, in due course.

New International Application Filed with the USPTO as a Receiving Office

If a new international application is being filed and the international application includes the necessary components for an international filing date (see PCT Article 11 and MPEP 1810), a Notification of the International Application Number and of the International Filing Date (Form PCT/RO/105) will be issued in due course, subject to prescriptions concerning national security, and the date shown on this Acknowledgement Receipt will establish the international filing date of the application.

UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
18/229,907	08/03/2023	John A. Nix	63121/0224	7483

1912 7590 09/17/2024

AMSTER, ROTHSTEIN & EBENSTEIN LLP
405 LEXINGTON AVENUE
FLOOR 48
NEW YORK, NY 10174

EXAMINER
CERVETTI, DAVID GARCIA

ART UNIT	PAPER NUMBER
2419	

MAIL DATE	DELIVERY MODE
09/17/2024	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Petitioner Samsung Ex-1004, 0478

Response to Rule 312 Communication	Application No.	Applicant(s)	
	18/229,907	Nix, John A.	
	Examiner	Art Unit	AIA (FITF) Status
	David García Cervetti	2419	Yes

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

1. ☑ The amendment filed on 05 September 2024 under 37 CFR 1.312 has been considered, and has been:

a) ☑ entered.

b) ☐ entered as directed to matters of form not affecting the scope of the invention.

c) ☐ disapproved because the amendment was filed after the payment of the issue fee.

Any amendment filed after the date the issue fee is paid must be accompanied by a petition under 37 CFR 1.313(c)(1) and the required fee to withdraw the application from issue.

d) ☐ disapproved. See explanation below.

e) ☐ entered in part. See explanation below.

f) ☐ not entered because the supplemental or corrected Application Data sheet (ADS)

☐ was not accompanied by a petition to accept an unintentionally delayed claim under 37 CFR 1.55 or 27 CFR 1.78;

☐ did not identify the information being changed in accordance with 37 CFR 1.76(c)(2);

☐ was not properly signed in accordance with 37 CFR 1.76(e) (or 37 CFR 1.33(b) for applications filed prior to September 16, 2012).

/David Garcia Cervetti/
Primary Examiner, Art Unit 2419

Petitioner Samsung Ex-1004, 0479

OK TO ENTER: /DGC/

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant:	Network-1 Technologies, Inc.	Confirmation No.: 7483
Title:	Key Derivation for a Module Using an Embedded Universal Integrated Circuit Card	
Appl. No.:	18/229,907	
Filing Date:	August 3, 2023	
Examiner:	Cervetti, David Garcia	
Art Unit:	2419	
Docket No.:	63121/0224	
Customer No.:	01912	

AMENDMENT AFTER NOTICE OF ALLOWANCE UNDER 37 C.F.R. 1.312

VIA EFS

Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

Sir:

Please enter the following amendments and consider the following remarks following the Notice of Allowance dated August 1, 2024.

Amendments to the Claims begin on page **2** of this paper.

Remarks begin on page **5** of this paper.

Petitioner Samsung Ex-1004, 0480

UNITED STATES
PATENT AND TRADEMARK OFFICE

P.O. Box 1450
Alexandria, VA 22313 - 1450
www.uspto.gov

ELECTRONIC ACKNOWLEDGEMENT RECEIPT

APPLICATION #	RECEIPT DATE / TIME	ATTORNEY DOCKET #
18/229,907	**10/30/2024 05:28:35 PM Z ET**	**63121/0224**

Title of Invention

Key Derivation for a Module Using an Embedded Universal Integrated Circuit Card

Application Information

APPLICATION TYPE	Utility - Nonprovisional Application under 35 USC 111(a)	PATENT #	-
CONFIRMATION #	7483	FILED BY	Victoria GILMORE
PATENT CENTER #	67784906	FILING DATE	08/03/2023
CUSTOMER #	1912	FIRST NAMED INVENTOR	John A. Nix
CORRESPONDENCE ADDRESS	-	AUTHORIZED BY	Benjamin Halpern

Documents

TOTAL DOCUMENTS: 1

DOCUMENT	PAGES	DESCRIPTION	SIZE (KB)
224-PTOL-85.pdf	1	Issue Fee Payment (PTO-85B)	164 KB

Digest

DOCUMENT	MESSAGE DIGEST(SHA-512)
224-PTOL-85.pdf	D772DEE75A8EC7D1FBC3382450C7A5F0CC02CA9D7C186B4 3BCB082139624CB4C152422002D29D750BE792A86939813D47 76CC1F99E3D00F345872DDD6443FB10

This Acknowledgement Receipt evidences receipt on the noted date by the USPTO of the indicated documents, characterized by the applicant, and including page counts, where applicable. It serves as evidence of receipt similar to a Post Card, as described in MPEP 503.

New Applications Under 35 U.S.C. 111

If a new application is being filed and the application includes the necessary components for filing date (see 37 CFR 1.53(b)-(d) and MPEP 506), a Filing Receipt (37 CFR 1.54) will be issued in due course and the date shown on this Acknowledgement Receipt will establish the filing date of the application

National Stage of an International Application under 35 U.S.C. 371

If a timely submission to enter the national stage of an international application is compliant with the conditions of 35 U.S.C. 371 and other applicable requirements a Form PCT/DO/EO/903 indicating acceptance of the application as a national stage submission under 35 U.S.C. 371 will be issued in addition to the Filing Receipt, in due course.

New International Application Filed with the USPTO as a Receiving Office

If a new international application is being filed and the international application includes the necessary components for an international filing date (see PCT Article 11 and MPEP 1810), a Notification of the International Application Number and of the International Filing Date (Form PCT/RO/105) will be issued in due course, subject to prescriptions concerning national security, and the date shown on this Acknowledgement Receipt will establish the international filing date of the application.

UNITED STATES
PATENT AND TRADEMARK OFFICE

P.O. Box 1450
Alexandria, VA 22313 - 1450
www.uspto.gov

ELECTRONIC PAYMENT RECEIPT

APPLICATION #	RECEIPT DATE / TIME	ATTORNEY DOCKET #
18/229,907	**10/30/2024 05:28:35 PM Z ET**	**63121/0224**

Title of Invention

Key Derivation for a Module Using an Embedded Universal Integrated Circuit Card

Application Information

APPLICATION TYPE	Utility - Nonprovisional Application under 35 USC 111(a)	PATENT #	-
CONFIRMATION #	7483	FILED BY	Victoria GILMORE
PATENT CENTER #	67784906	AUTHORIZED BY	Benjamin Halpern
CUSTOMER #	1912	FILING DATE	08/03/2023
CORRESPONDENCE ADDRESS	-	FIRST NAMED INVENTOR	John A. Nix

Payment Information

PAYMENT METHOD	PAYMENT TRANSACTION ID	PAYMENT AUTHORIZED BY
CARD / 1077	**E20240TH29228402**	**Victoria GILMORE**

FEE CODE	DESCRIPTION	ITEM PRICE($)	QUANTITY	ITEM TOTAL($)
2501	UTILITY ISSUE FEE	480.00	1	480.00
			TOTAL AMOUNT:	**$480.00**

This Acknowledgement Receipt evidences receipt on the noted date by the USPTO of the indicated documents, characterized by the applicant, and including page counts, where applicable. It serves as evidence of receipt similar to a Post Card, as described in MPEP 503.

New Applications Under 35 U.S.C. 111

If a new application is being filed and the application includes the necessary components for filing date (see 37 CFR 1.53(b)-(d) and MPEP 506), a Filing Receipt (37 CFR 1.54) will be issued in due course and the date shown on this Acknowledgement Receipt will establish the filing date of the application

National Stage of an International Application under 35 U.S.C. 371

If a timely submission to enter the national stage of an international application is compliant with the conditions of 35 U.S.C. 371 and other applicable requirements a Form PCT/DO/EO/903 indicating acceptance of the application as a national stage submission under 35 U.S.C. 371 will be issued in addition to the Filing Receipt, in due course.

New International Application Filed with the USPTO as a Receiving Office

If a new international application is being filed and the international application includes the necessary components for an international filing date (see PCT Article 11 and MPEP 1810), a Notification of the International Application Number and of the International Filing Date (Form PCT/RO/105) will be issued in due course, subject to prescriptions concerning national security, and the date shown on this Acknowledgement Receipt will establish the international filing date of the application.

PART B - FEE(S) TRANSMITTAL

Complete and send this form, together with applicable fee(s), by mail or fax, or via the USPTO patent electronic filing system.

By mail, send to: Mail Stop ISSUE FEE
Commissioner for Patents
P.O. Box 1450
Alexandria, Virginia 22313-1450

By fax, send to: (571)-273-2885

INSTRUCTIONS: This form should be used for transmitting the ISSUE FEE and PUBLICATION FEE (if required). Blocks 1 through 5 should be completed where appropriate. All further correspondence will be mailed to the current correspondence address as indicated unless corrected below or directed otherwise in Block 1, by (a) specifying a new correspondence address; and/or (b) indicating a separate "FEE ADDRESS" for maintenance fee notifications. **Because electronic patent issuance may occur shortly after issue fee payment, any desired continuing application should preferably be filed prior to payment of this issue fee in order not to jeopardize copendency.**

CURRENT CORRESPONDENCE ADDRESS (Note: Use Block 1 for any change of address)

1912 7590 08/01/2024
AMSTER, ROTHSTEIN & EBENSTEIN LLP
405 LEXINGTON AVENUE
FLOOR 48
NEW YORK, NY 10174

Note: A certificate of mailing can only be used for domestic mailings of the Fee(s) Transmittal. This certificate cannot be used for any other accompanying papers. Each additional paper, such as an assignment or formal drawing, must have its own certificate of mailing or transmission.

Certificate of Mailing or Transmission

I hereby certify that this Fee(s) Transmittal is being deposited with the United States Postal Service with sufficient postage for first class mail in an envelope addressed to the Mail Stop ISSUE FEE address above, or being transmitted to the USPTO via the USPTO patent electronic filing system or by facsimile to (571) 273-2885, on the date below.

Benjamin M. Halpern	(Typed or printed name)
/Benjamin M. Halpern/	(Signature)
October 30, 2024	(Date)

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
18/229,907	08/03/2023	John A. Nix	63121/0224	7483

TITLE OF INVENTION: Key Derivation for a Module Using an Embedded Universal Integrated Circuit Card

APPLN. TYPE	ENTITY STATUS	ISSUE FEE DUE	PUBLICATION FEE DUE	PREV. PAID ISSUE FEE	TOTAL FEE(S) DUE	DATE DUE
nonprovisional	SMALL	$480	$0.00	$0.00	$480	11/01/2024

EXAMINER	ART UNIT	CLASS-SUBCLASS
CERVETTI, DAVID GARCIA	2419	713-168000

1. Change of correspondence address or indication of "Fee Address" (37 CFR 1.363).

☐ Change of correspondence address (or Change of Correspondence Address form PTO/AIA/122 or PTO/SB/122) attached.

☐ "Fee Address" indication (or "Fee Address" Indication form PTO/AIA/47 or PTO/SB/47; Rev 03-02 or more recent) attached. **Use of a Customer Number is required.**

2. For printing on the patent front page, list
(1) The names of up to 3 registered patent attorneys or agents OR, alternatively,
(2) The name of a single firm (having as a member a registered attorney or agent) and the names of up to 2 registered patent attorneys or agents. If no name is listed, no name will be printed.

1 Amster, Rothstein & Ebenstein LLP
2
3

3. ASSIGNEE NAME AND RESIDENCE DATA TO BE PRINTED ON THE PATENT (print or type)

PLEASE NOTE: Unless an assignee is identified below, no assignee data will appear on the patent. If an assignee is identified below, the document must have been previously recorded, or filed for recordation, as set forth in 37 CFR 3.11 and 37 CFR 3.81(a). Completion of this form is NOT a substitute for filing an assignment.

(A) NAME OF ASSIGNEE: Network-1 Technologies, Inc.

(B) RESIDENCE: (CITY and STATE OR COUNTRY): New York, NEW YORK

Please check the appropriate assignee category or categories (will not be printed on the patent) : ☐ Individual ☑ Corporation or other private group entity ☐ Government

4a. Fees submitted: ☑ Issue Fee ☐ Publication Fee (if required)

4b. Method of Payment: *(Please first reapply any previously paid fee shown above)*

☑ Electronic Payment via the USPTO patent electronic filing system ☐ Enclosed check ☐ Non-electronic payment by credit card (Attach form PTO-2038)

☑ The Director is hereby authorized to charge the required fee(s), any deficiency, or credit any overpayment to Deposit Account No. 011785

5. **Change in Entity Status** (from status indicated above)

☐ Applicant certifying micro entity status. See 37 CFR 1.29

NOTE: Absent a valid certification of Micro Entity Status (see forms PTO/SB/15A and 15B), issue fee payment in the micro entity amount will not be accepted at the risk of application abandonment.

☐ Applicant asserting small entity status. See 37 CFR 1.27

NOTE: If the application was previously under micro entity status, checking this box will be taken to be a notification of loss of entitlement to micro entity status.

☐ Applicant changing to regular undiscounted fee status.

NOTE: Checking this box will be taken to be a notification of loss of entitlement to small or micro entity status, as applicable.

NOTE: This form must be signed in accordance with 37 CFR 1.31 and 1.33. See 37 CFR 1.4 for signature requirements and certifications.

Authorized Signature /Benjamin M. Halpern/ Date October 30, 2024

Typed or printed name Benjamin M. Halpern Registration No. 46,494

PTOL-85 Part B (11/23) Approved for use through 03/31/2026 OMB 0651-0033 U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Petitioner Samsung Ex-1004, 0485

Notice of References Cited	Application/Control No. 18/229,907	Applicant(s)/Patent Under Reexamination Nix, John A.	
	Examiner David García Cervetti	Art Unit 2419	Page 10 of 11

U.S. PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Name	CPC Classification	US Classification
*	A	US-9712996-B2	2017-07-18	Park; Jaemin	H04W12/04	1/1
*	B	US-20170289792-A1	2017-10-05	PARK; Jaemin	H04L67/306	1/1
*	C	US-20150126153-A1	2015-05-07	Spitz; Stephan	H04W12/06	455/26.1
*	D	US-20060179309-A1	2006-08-10	Cross; David B.	G06F21/6281	713/168
*	E	US-20040146015-A1	2004-07-29	Cross, David B.	H04L9/0894	370/328
*	F	US-8887257-B2	2014-11-11	Haggerty; David T.	H04W12/04	726/9
*	G	US-20140006786-A1	2014-01-02	Campagna; Matthew John	H04W12/04	713/171
*	H	US-20140004824-A1	2014-01-02	Campagna; Matthew John	H04L9/0866	455/411
*	I	US-20120072979-A1	2012-03-22	Cha; Inhyok	H04W12/069	726/8
*	J	US-20120023568-A1	2012-01-26	Cha; Inhyok	H04L63/0807	726/10
*	K	US-20100174907-A1	2010-07-08	Semple; James F.	H04W12/0431	713/169
*	L	US-20220295288-A1	2022-09-15	~~St2hl~~; Per Stahl	H04L67/303	1/1
*	M	US-20220095095-A1	2022-03-24	LIM; Taehyung	H04W8/24	1/1

FOREIGN PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date YYYY-MM-DD	Country	Name	CPC Classification
Change(s) applied to document, /M.E.G./ 8/15/2024	N					
	O					
	P					
	Q					
	R					
	S					
	T					

NON-PATENT DOCUMENTS

*		Include as applicable: Author, Title Date, Publisher, Edition or Volume, Pertinent Pages)
	U	
	V	
	W	
	X	

*A copy of this reference is not being furnished with this Office action. (See MPEP § 707.05(a).)
Dates in YYYY-MM-DD format are publication dates. Classifications may be US or foreign.

Petitioner Samsung Ex-1004, 0486

UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	ISSUE DATE	PATENT NO.	ATTORNEY DOCKET NO.	CONFIRMATION NO.
18/229,907	12/10/2024	12166869	63121/0224	7483

1912 7590 11/20/2024

AMSTER, ROTHSTEIN & EBENSTEIN LLP
405 LEXINGTON AVENUE
FLOOR 48
NEW YORK, NY 10174

ISSUE NOTIFICATION

The projected patent number and issue date are specified above. The patent will issue electronically. The electronically issued patent is the official patent grant pursuant to 35 U.S.C. § 153. The patent may be accessed on or after the issue date through Patent Center at https://patentcenter.uspto.gov/. The patent will be available in both the public and the private sides of Patent Center. Further assistance in electronically accessing the patent, or about Patent Center, is available by calling the Patent Electronic Business Center at 1-888-217-9197.

The USPTO is implementing electronic patent issuance with a transition period, during which period the USPTO will mail a ceremonial paper copy of the electronic patent grant to the correspondence address of record. Additional copies of the patent (i.e., certified and presentation copies) may be ordered for a fee from the USPTO's Certified Copy Center at https://certifiedcopycenter.uspto.gov/index.html. The Certified Copy Center may be reached at (800)972-6382.

Determination of Patent Term Adjustment under 35 U.S.C. 154 (b)
(application filed on or after May 29, 2000)

The Patent Term Adjustment is 0 day(s). Any patent to issue from the above-identified application will include an indication of the adjustment on the front page.

If a Continued Prosecution Application (CPA) was filed in the above-identified application, the filing date that determines Patent Term Adjustment is the filing date of the most recent CPA.

Applicant will be able to obtain more detailed information by accessing the Patent Center (https://patentcenter.uspto.gov).

Any questions regarding the Patent Term Extension or Adjustment determination should be directed to the Office of Patent Legal Administration at (571)-272-7702. Questions relating to issue and publication fee payments should be directed to the Application Assistance Unit (AAU) of the Office of Patents Stakeholder Experience (OPSE), Stakeholder Support Division (SSD) at (571)-272-4200.

Petitioner Samsung Ex-1004, 0487

INVENTOR(s) (Please see PATENT CENTER site https://patentcenter.uspto.gov for additional inventors):

John A. Nix, Evanston, IL;

APPLICANT(s) (Please see PATENT CENTER site https://patentcenter.uspto.gov for additional applicants):

Network-1 Technologies, Inc., New York, NY;

The United States represents the largest, most dynamic marketplace in the world and is an unparalleled location for business investment, innovation, and commercialization of new technologies. The USA offers tremendous resources and advantages for those who invest and manufacture goods here. Through SelectUSA, our nation works to encourage and facilitate business investment. To learn more about why the USA is the best country in the world to develop technology, manufacture products, and grow your business, visit SelectUSA.gov.

Petitioner Samsung Ex-1004, 0488

UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
18/229,907	08/03/2023	John A. Nix	63121/0224	7483

1912 7590 12/10/2024

AMSTER, ROTHSTEIN & EBENSTEIN LLP
405 LEXINGTON AVENUE
FLOOR 48
NEW YORK, NY 10174

EXAMINER
CERVETTI, DAVID GARCIA

ART UNIT	PAPER NUMBER
2409	

MAIL DATE	DELIVERY MODE
12/10/2024	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

APPLICATION NO.	ISSUE DATE	PATENT NO.
18/229,907	10-Dec-2024	12166869

AMSTER, ROTHSTEIN & EBENSTEIN LLP
405 LEXINGTON AVENUE
NEW YORK, NY 10174

EGRANT NOTIFICATION

Your electronic patent grant (eGrant) is now available, which can be accessed via Patent Center at https://patentcenter.uspto.gov

The electronic patent grant is the official patent grant under 35 U.S.C. 153. For more information, please visit https://www.uspto.gov/electronicgrants

Petitioner Samsung Ex-1004, 0490