

(12) **United States Patent**
Robinson

(10) **Patent No.:** **US 9,585,766 B2**
(45) **Date of Patent:** **Mar. 7, 2017**

(54) **EXPANDABLE INTERVERTEBRAL CAGE ASSEMBLIES AND METHODS**

(2013.01); *A61F 2002/30629* (2013.01); *A61F 2002/30736* (2013.01); *A61F 2002/30827* (2013.01)

(71) Applicant: **Spectrum Spine IP Holdings, LLC**,
Atlanta, GA (US)

(58) **Field of Classification Search**
CPC *A61F 2/44*; *A61F 2/4425*; *A61F 2002/443*;
A61F 2/4455; *A61F 2/447*; *A61F 2002/4475*; *A61F 2/442*
See application file for complete search history.

(72) Inventor: **James C. Robinson**, Atlanta, GA (US)

(73) Assignee: **SPECTRUM SPINE IP HOLDINGS, LLC**, Atlanta, GA (US)

(56) **References Cited**

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 176 days.

U.S. PATENT DOCUMENTS

4,545,374 A	10/1985	Jacobson	
5,653,763 A	8/1997	Errico et al.	
6,102,950 A	8/2000	Vaccaro	
6,176,882 B1 *	1/2001	Biedermann et al.	 623/17.15

(Continued)

(21) Appl. No.: **13/962,879**

(22) Filed: **Aug. 8, 2013**

FOREIGN PATENT DOCUMENTS

(65) **Prior Publication Data**

US 2014/0148904 A1 May 29, 2014

EP	1504735	1/2008	
FR	2771282 A1 *	5/1999	 <i>A61F 2/44</i>
WO	2011124787	10/2011	

Primary Examiner — Eduardo C Robert
Assistant Examiner — Julianna N Harvey
(74) *Attorney, Agent, or Firm* — FisherBroyles, LLP;
Anthony J. DeVale

Related U.S. Application Data

(60) Provisional application No. 61/680,729, filed on Aug. 8, 2012, provisional application No. 61/787,744, filed on Mar. 15, 2013.

(51) **Int. Cl.**

A61F 2/44 (2006.01)
A61F 2/30 (2006.01)


(52) **U.S. Cl.**

CPC *A61F 2/447* (2013.01); *A61F 2002/30382* (2013.01); *A61F 2002/30448* (2013.01); *A61F 2002/30451* (2013.01); *A61F 2002/30457* (2013.01); *A61F 2002/30471* (2013.01); *A61F 2002/30492* (2013.01); *A61F 2002/30515* (2013.01); *A61F 2002/30579* (2013.01); *A61F 2002/30594* (2013.01); *A61F 2002/30598*

(57) **ABSTRACT**

An expandable assembly for insertion into an intervertebral space is presented. The assembly, in particular aspects, includes an elongate body comprising an upper portion and a lower portion, wherein the elongate body defines an internal longitudinal channel extending from a proximal opening to a distal cavity. The assembly may include an expander that is sized and shaped for insertion into the distal cavity, thereby selectively expanding the upper portion away from the lower portion. The elongate body may also include one or more bone graft windows a cap that is sized and shaped for insertion into the proximal opening.

28 Claims, 10 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

6,436,140	B1 *	8/2002	Liu	A61F 2/446 623/17.11
6,454,807	B1 *	9/2002	Jackson	623/17.15
6,582,431	B1	6/2003	Ray	
6,641,614	B1 *	11/2003	Wagner et al.	623/17.15
6,849,093	B2 *	2/2005	Michelson	623/17.15
6,893,464	B2	5/2005	Kiester	
6,902,547	B2	6/2005	Aves	
7,128,760	B2 *	10/2006	Michelson	A61F 2/446 606/247
7,431,735	B2	10/2008	Liu et al.	
7,674,297	B2	3/2010	Falahee	
8,007,537	B2	8/2011	Zucherman et al.	
8,105,382	B2	1/2012	Olmos et al.	
2002/0068977	A1 *	6/2002	Jackson	623/17.15
2002/0128713	A1	9/2002	Ferree	
2005/0015149	A1	1/2005	Michelson	
2006/0129244	A1	6/2006	Ensign	
2006/0206207	A1 *	9/2006	Dryer et al.	623/17.11
2007/0270968	A1	11/2007	Baynham	
2008/0161919	A1	7/2008	Melkent	
2010/0222816	A1	9/2010	Gabelberger	
2011/0093074	A1 *	4/2011	Glerum et al.	623/17.16
2011/0319997	A1 *	12/2011	Glerum et al.	623/17.15
2012/0059473	A1 *	3/2012	Weiman	A61F 2/44 623/17.16
2012/0143341	A1	6/2012	Zipnick	

* cited by examiner




FIG. 1A




FIG. 1B




FIG. 2A




FIG. 2B




FIG. 3A




FIG. 3B




FIG. 4A




FIG. 4B




FIG. 5A






FIG. 5B






FIG. 7




FIG. 8A




FIG. 8B




FIG. 9A




FIG. 9B




FIG. 10




FIG. 11




FIG. 12




FIG. 13A




FIG. 13B

1

EXPANDABLE INTERVERTEBRAL CAGE ASSEMBLIES AND METHODS

CONTINUITY

This application claims the benefit of and priority to U.S. Application No. 61/680,729, titled EXPANDABLE INTERVERTEBRAL CAGE ASSEMBLIES AND METHODS, filed on Aug. 8, 2012 and U.S. Application No. 61/787,744, titled EXPANDABLE INTERVERTEBRAL CAGE ASSEMBLIES AND METHODS, filed on Mar. 15, 2013, both of which are incorporated herein in their entirety.

BACKGROUND

The following disclosure relates generally to medical devices, systems and methods, including, for example, systems and methods for lumbar interbody fusion.

Surgical implantation of disc replacement material is typically used to provide support along the spinal column in cases where a portion of the patient's intervertebral anatomy has become weakened, diseased, or destroyed. Such support systems are also commonly used following a discectomy, where an intervertebral disc is surgically removed.

Most commonly, existing support systems typically operate by inhibiting normal movement between the adjacent vertebrae, thereby holding these vertebrae at fixed positions relative to one another, with the mechanical body of the supporting structure providing the needed support along the patient's spinal column. Such supporting systems are typically made of stainless steel, titanium, polymer (e.g., an organic polymer thermoplastic such as polyether ether ketone (PEEK)), carbon fiber, or ceramic and they are designed to permanently remain within the patient's body.

It is beneficial, in addition to fixation, to try to stimulate bone growth between the adjacent vertebrae. To do so, spine surgeons use bone graft material in addition to fixation devices. Bone graft doesn't heal or fuse the spine immediately; instead, bone graft provides a foundation or scaffold for the patient's body to grow new bone. Bone graft can stimulate new bone production. When new bone grows and solidifies, fusion occurs. Although instrumentation (e.g., screws, rods) is often used for initial stabilization (post-operative), it is the healing of bone that welds vertebrae together to create long-term stability. There are two general types of bone grafts: real bone and bone graft substitutes. Real bone can come from the patient (autograft) or from a donor bone (allograft). Also used in these types of surgery are bone substitute, osteoinductive agent, and bone cement.

There is a need for improved systems and methods for lumbar interbody fusion.

SUMMARY

An expandable assembly for insertion into an intervertebral space is disclosed. The assembly, in particular aspects, includes an elongate body comprising an upper portion and a lower portion, wherein the elongate body defines an internal longitudinal channel extending from a proximal opening to a distal cavity. The assembly may include an expander that is sized and shaped for insertion into the distal cavity, thereby selectively expanding the upper portion away from the lower portion. The elongate body may also include one or more bone graft windows a cap that is sized and shaped for insertion into the proximal opening.

2

BRIEF DESCRIPTION OF THE DRAWINGS

These and other features of the preferred embodiments of the present invention will become more apparent in the detailed description in which reference is made to the appended drawings wherein:

FIG. 1A is a perspective view of one aspect of an expandable cage for insertion into an intervertebral space in an unexpanded position;

FIG. 1B is a perspective view of the expandable cage of FIG. 1A in an expanded position;

FIG. 2A is a side elevational view of the expandable cage of FIG. 1A in the unexpanded position;

FIG. 2B is a side elevational view of the expandable cage of FIG. 1A in the expanded position;

FIG. 3A is a proximal end elevational view of the expandable cage of FIG. 1A in the unexpanded position;

FIG. 3B is a proximal end elevational view of the expandable cage of FIG. 1A in the expanded position;

FIG. 4A is a side elevational cut away view of the expandable cage of FIG. 1A in the unexpanded position, cut along line 4A-4A in FIG. 3A;

FIG. 4B is a side elevational cut away view of the expandable cage of FIG. 1A in the expanded position, cut along line 4B-4B in FIG. 3B;

FIG. 5A is a top plan view of the expandable cage of FIG. 1A in the unexpanded position;

FIG. 5B is a top plan view of the expandable cage of FIG. 1A in the expanded position;

FIG. 6A is a side elevational view of an expandable cage in an unexpanded position associated with an insertion tool;

FIG. 6B is a side elevational view of an expandable cage in an expanded position associated with an insertion tool;

FIG. 7 is a perspective view of an expander for use in an expandable cage;

FIG. 8A is a perspective view of one aspect of an expandable cage in the unexpanded position;

FIG. 8B is a perspective view of the expandable cage of FIG. 8A in the expanded position, showing at least one tongue in the distal end of the upper and lower portions for complimentary fit into a recess defined therein the expander;

FIG. 9A is a partially transparent perspective view of FIG. 8A;

FIG. 9B is a partially transparent perspective view of FIG. 8B;

FIG. 10 is a perspective view of the expander of FIGS. 8A and 8B;

FIG. 11 is a perspective view of the upper portion of FIGS. 8A and 8B;

FIG. 12 is a perspective view of the lower portion of FIGS. 8A and 8B;

FIG. 13a is a perspective view of one aspect of an expandable cage in the expandable position, showing at least one hook positioned on the inner surface of the upper and lower portions configured for complimentary receipt into a recess defined in the distal portion of the expander; and

FIG. 13b is a perspective view of the expandable cage of FIG. 13a in the unexpanded position.

DETAILED DESCRIPTION

The present systems and apparatuses and methods are understood more readily by reference to the following detailed description, examples, drawing, and claims, and their previous and following description. However, before the present devices, systems, and/or methods are disclosed and described, it is to be understood that this invention is not

3

limited to the specific devices, systems, and/or methods disclosed unless otherwise specified, as such can, of course, vary. It is also to be understood that the terminology used herein is for the purpose of describing particular aspects only and is not intended to be limiting.

The following description of the invention is provided as an enabling teaching of the invention. To this end, those skilled in the relevant art will recognize and appreciate that many changes can be made to the various aspects of the invention described herein, while still obtaining the beneficial results of the present invention. It will also be apparent that some of the desired benefits of the present invention can be obtained by selecting some of the features of the present invention without utilizing other features. Accordingly, those who work in the art will recognize that many modifications and adaptations to the present invention are possible and can even be desirable in certain circumstances and are a part of the present invention. Thus, the following description is provided as illustrative of the principles of the present invention and not in limitation thereof.

As used throughout, the singular forms “a,” “an” and “the” include plural referents unless the context clearly dictates otherwise. Thus, for example, reference to “a” component can include two or more such components unless the context indicates otherwise. Also, the words “proximal” and “distal” are used to describe items or portions of items that are situated closer to and away from, respectively, a user or operator such as a surgeon. Thus, for example, the tip or free end of a device may be referred to as the distal end, whereas the generally opposing end or handle may be referred to as the proximal end.

Ranges can be expressed herein as from “about” one particular value, and/or to “about” another particular value. When such a range is expressed, another aspect includes from the one particular value and/or to the other particular value. Similarly, when values are expressed as approximations, by use of the antecedent “about,” it will be understood that the particular value forms another aspect. It will be further understood that the endpoints of each of the ranges are significant both in relation to the other endpoint, and independently of the other endpoint.

As used herein, the terms “optional” or “optionally” mean that the subsequently described event or circumstance may or may not occur, and that the description includes instances where said event or circumstance occurs and instances where it does not.

Presented herein are systems, tools, and methods for supporting adjacent vertebrae of the spine, for example, as part of interbody spinal fusion surgery. Although the systems, tools, and methods are presented herein in the context of posterior lumbar interbody fusion (PLIF), direct lateral interbody fusion (DLIF), and transforaminal lumbar interbody fusion (TLIF), the assemblies and techniques may be useful in a variety of therapeutic contexts.

In one aspect, a cage assembly for the stabilization of an intervertebral space during a spinal fusion procedure is presented. As described herein, the cage assembly may comprise an expander such as an expansion screw or a shim which, when inserted, selectively expands the body of the cage assembly to a desired size. The cage assembly may include one or more openings or windows for receiving bone fusion material. The bone fusion material may comprise, for example and without limitation, autologous bone, allograft bone, bone substitute, osteoinductive agent, and/or bone cement. The cage assembly may also include a plug or cap to contain the bone fusion material and to add strength to the trailing side of the cage in weight bearing.

4

In one aspect, a cage assembly **1000** may include a generally elongate cage body **1010**, an expander **1032**, and an insertion tool **1060**, as shown in FIG. **1A**.

The cage body **1010** may be generally rectangular in cross-section. The body **1010** may include an upper portion **1012** and a lower portion **1018**. The outer surfaces of the two portions **1012**, **1018** may be ridged or grooved, laterally, as shown. The two portions **1012**, **1018** may be joined together by a pin-in-slot joint or another type of hinge **1070** near the proximal end. The space between the two portions **1012**, **1018** may form an internal passage or channel **1020** that extends lengthwise through the cage body **1010**. The cage body **1010** may also include one or more openings or windows **1050** for receiving bone fusion material.

As illustrated in FIG. **1A** and FIG. **1B**, the expander **1032** may be a keyed shim. Referring to the perspective view in FIG. **1A**, the shim has “key” on its distal portion. In this particular aspect, the key is generally conical in cross-section with a rectangular or square end, like the head of a bolt, and tapered on both sides. The key shape on the distal portion may be sized and shaped to fit within a distal cavity **1030**, as shown in Section A-A. In one aspect, the expander **1032** may include a set of keyed shims, each key having a discrete size and shape. The cage body **1010** may also include a number of cage bodies, each with a distal cavity **1030** having a different size and shape. The size and shape of the key, together with its matching distal cavity **1030**, may be used to create a cage body **1010** that opens to a desired height and angular orientation.

Referring again to the perspective view in FIG. **1A**, the proximal end of the keyed shim may include a proximal portion **1078**, which can be seen through the window **1050** in the upper portion **1012**. The proximal portion **1078** of the shim may include a socket or other feature for receiving the distal end of an insertion tool **1060**. The tool may be used to pull the keyed shim **1032** proximally until the key slides into the distal cavity. One aspect of a keyed shim **1032** is also illustrated in FIG. **2**. As shown, the proximal portion **1078** may be generally cylindrical in shape and may be suitable for grasping by the distal end of an insertion tool. The keyed shim **1032**, as shown, may also include side rails that are sized and shaped to engage with interior portions of the cage body **1010**.

The insertion tool **1060**, as shown in FIG. **1B**, may include a cannula **1062** and a drive rod **1068**. The distal end of the drive rod **1068** may include a specialized head or other tool for grasping or otherwise engaging the proximal portion **1078** of the keyed shim; e.g., a threaded portion. Once engaged, the drive rod **1068** may be used to pull the keyed shim proximally, or push it distally, into a desired position. Alternatively, the threaded rod may be rotated in order to actuate a change in the position of the expander **1032** to the desired position.

As shown in FIG. **1B**, the expander **1032** or keyed shim, when pulled proximally and into the distal cavity **1030**, will cause the two portions **1012**, **1018** of the cage body **1010** to expand or spread open. The pin-in-slot joint or hinge **1070** may allow the two portions **1012**, **1018** to expand or move vertically relative to one another, while also allowing the two portions **1012**, **1018** to rotate about the hinge **1070** thereby changing the angle of the upper portion **1012** and the bottom portion **1018** of the body. In this aspect, the keyed shim **1032** may induce an angular relationship in which the distal end of the cage body **1010** becomes more open than the proximal end. The cage body **1010**, as shown, may also include a set screw **1042** for insertion into the proximal portion **1078** of the keyed shim. The drive rod **1068** or

5

another tool inserted through the cannula **1062** may be used to rotate or otherwise drive the set screw **1042** into position. The set screw **1042**, in one aspect, may be sized and shaped to retain the expander **1032** firmly within its final position, such that the expander **1032** will not retreat or otherwise “back out” unless purposely driven by a tool, also aiding in containment of the fusion material within the cage assembly and strengthening the proximal wall of the construct.

In use, the cage assembly **1000** may be inserted using an insertion tool **1060** into an intervertebral space; for example, in the lumbar region of the spine. A drive rod **1068** or other tool may be used to grasp or otherwise engage with a proximal portion **1078** of the expander **1032**, and pull the expander **1032** proximally until its distal “key” is seated within a distal cavity **1030**. Section B-B of FIG. **1B** shows the key of the expander **1042** seated within the distal cavity **1030**.

In certain exemplified aspects, the cage assembly **1000** comprises means to prevent the separation of the upper portion **1012** and the lower portion **1018** prior to expansion. In one aspect, the distal portion **1080** of the shim **1032** defines at least one substantially longitudinal slot, groove, or recess **1082**. As shown in the figures, the distal portion of the shim can define a slot, groove, or recess on either side surface **1084**. In this aspect, the distal end **1113** of the upper portion **1012** and the distal end **1119** of the lower portion **1018** each comprise a tongue **1120**, **1122** sized such that both tongues can slide into and be retained within one of the recesses **1082** defined in the distal portion of the shim. The upper and lower portion can also have bilateral tongues, as shown in the figures. Referring to FIGS. **5** and **6**, in the unexpanded position, the tongues from both the upper and lower portion are retained within the recess(es) by portions of the shim. This permits insertion of the cage without the potential of the premature separation of the upper and lower portions. As the shim is moved proximally, the recess is moved proximally, while the tongues remain unmoved, essentially disengaging the tongues and recesses. Once the shim is moved sufficiently, the tongues disengage from the recess, enabling the upper and lower portions to expand as designed.

In another exemplified aspect, as illustrated in FIGS. **10** and **11**, the upper and lower portions can comprise a tongue, pin, or hook **1120**, **1122** positioned on each of their inner surfaces **1114**, **1117**. In this aspect, the distal portion of the shim defines a recess, slot, or hollow corresponding to each tongue, pin or hook such that, when the cage is in the unexpanded position, the hooks of the upper and lower portions are retained within the slots in the distal portion of the shim. As the shim is moved proximally, the slots are also moved proximally, while the hooks remain unmoved, essentially disengaging the hooks and slots and permitting expansion of the upper and lower portions.

In still another aspect, the upper and lower portions may be bonded together in a temporary fashion so they do not splay during insertion. For instance, a portion of the lower portion may be ultrasonically welded, glued, or otherwise bonded to a portion of the upper portion. Then, after insertion, the bond can be broken during and by the expansion of the of the upper and lower portions. It is also contemplated that the bond can be between the upper and/or lower portion and the insert.

Bone fusion material may be inserted into the one or more windows **1050** into the cage body **1010** as well as through the aperture in the proximal end of the expander **1078**, and thereby into the proximity of the surrounding bony struc-

6

tures, in order to promote fusion and to further secure the cage assembly **1000** in place.

Either before or after placement of the bone fusion material, a cap or set screw **1042** may be inserted (using a drive rod **1068** or another tool inserted through the cannula **1062**) into the proximal portion **1078** of the shim. The set screw **1042** helps contain the bone fusion material and also strengthens the proximal end wall of the cage body **1010**.

Also presented herein is a method for inserting and expanding a cage assembly within an intervertebral space in the spine.

In use, the cage assembly **1000** may be inserted into an intervertebral space; for example, in the lumbar region of the spine. An expander **1032** may be inserted through the proximal opening in the body **1010**. The expander **1032** may be driven by a tool so that it drives apart the two portions **1012**, **1018** of the body **1010**. In one aspect, the body **1010** is selectively expandable because the expander **1032** may be inserted and/or counter-inserted until the body **1010** achieves the size and shape desired by the surgeon.

Bone fusion material may be inserted into the one or more windows **1050** into the body **1010**, and thereby into the proximity of the surrounding bony structures, in order to further secure the cage assembly **1000** in place.

A cap **1042** such as the cap screw shown in FIG. **2B** may be inserted into the proximal end of the body **1010**. The cap **1042** helps contain the bone fusion material and also strengthens the proximal end wall of the cage body **1010**.

Although several aspects of the invention have been disclosed in the foregoing specification, it is understood by those skilled in the art that many modifications and other aspects of the invention will come to mind to which the invention pertains, having the benefit of the teaching presented in the foregoing description and associated drawings. It is thus understood that the invention is not limited to the specific aspects disclosed herein above, and that many modifications and other aspects are intended to be included within the scope of the appended claims. Moreover, although specific terms are employed herein, as well as in the claims which follow, they are used only in a generic and descriptive sense, and not for the purposes of limiting the described invention, nor the claims which follow.

I claim:

1. An expandable cage system for inserting an expandable cage into an intervertebral space comprising:

a cage body having an upper portion and a lower portion, the upper portion comprising a substantially planar upper portion outer surface and an upper portion inner surface and the lower portion comprising a substantially planar lower portion outer surface and a lower portion inner surface, wherein the upper portion and the lower portion define an internal passage therebetween; and

a monolithic elongate expander at least partially positioned therebetween the upper portion and the lower portion and in the internal passage, wherein the expander is configured to move proximally relative to the upper and lower portions from a first position to a second position, the expander comprising a distal nose portion to facilitate insertion into the intervertebral space, wherein in the first position, the expandable cage is unexpanded and the distal nose portion extends at least partially distally past a distal portion of the cage body, and wherein in the second position, the expandable cage is expanded, increasing the space between the upper portion outer surface and the lower portion outer surface, wherein the upper portion and lower portion

7

are hingedly connected to one another at a hinge point to permit vertical movement of the upper portion relative to the lower portion at the hinge point while also permitting the upper portion and the lower portion to rotate about the hinge point, thereby changing the angle of the upper portion relative to the lower portion; and

an insertion tool configured to engage a proximal end of the expandable cage, insert it into a desired position in the intervertebral space, and move the expander from the first position to the second position.

2. The system of claim 1, wherein the insertion tool moves the expander from the first position to the second position by pulling the expander proximally.

3. The system of claim 1, wherein the upper portion has an upper portion inner surface and the lower portion has a lower portion inner surface, and wherein portions of the distal portion of the expander are complementarily shaped with at least one of the upper portion inner surface and the lower portion inner surface, whereby pulling the expander proximally cams the distal portion of the expander against the at least one of the upper portion inner surface and the lower portion inner surface to expand the cage body.

4. The system of claim 1, further comprising a means to retain the cage body in the unexpanded position and resist expansion during insertion of the expandable cage into the intervertebral space.

5. The system of claim 1, wherein the proximal portion of the cage body defines an aperture in communication with the internal passage.

6. The system of claim 5, further comprising a set screw sized and shaped to complementarily fit within the aperture and retain the expander in the second position.

7. The system of claim 1, wherein a portion of the distal portion of the expander comprises a first side surface and a second side surface, wherein one of the side surfaces defines at least one substantially longitudinal slot.

8. The system of claim 7, wherein the distal end of the upper portion and the distal end of the lower portion each comprise a tongue sized for a complimentary fit within the at least one substantially longitudinal slot when the cage body is in the unexpanded position, and wherein moving the expander into the second position moves the tongue out of engagement with the substantially longitudinal slot.

9. The system of claim 8, wherein the upper and lower portions comprise bilateral tongues.

10. The system of claim 1, wherein the distal end of the upper and lower portions each comprise a hook positioned thereon the respective inner surface.

11. The system of claim 10, wherein the distal portion of the expander defines recesses for complimentary receipt of the respective hooks when the cage body is in the unexpanded position, and wherein moving the expander into the second position moves the hooks out of engagement with the recesses.

12. The system of claim 1, wherein a portion of the distal end of the upper portion and a portion of the distal end of the lower portion are bonded together when the cage body is in the unexpanded position, and wherein moving the expander into the second position breaks the bond, allowing the cage body to move into the expanded position.

13. The system of claim 1, wherein the cage body defines one or more windows in communication with the internal passage.

14. The system of claim 1, wherein the distal nose portion is integral with the elongate expander.

8

15. An expandable cage for insertion into an intervertebral space comprising:

a cage body having an upper portion and a lower portion, the upper portion comprising a substantially planar upper portion outer surface and an upper portion inner surface and the lower portion comprising a substantially planar lower portion outer surface and a lower portion inner surface, wherein the upper portion and lower portion are hingedly connected to one another at a hinge point to permit vertical movement of the upper portion relative to the lower portion at the hinge point while also permitting the upper portion and the lower portion to rotate about the hinge point, thereby changing the angle of the upper portion relative to the lower portion, and wherein the upper portion and the lower portion define an internal passage therebetween; and

a monolithic elongate expander at least partially positioned therebetween the upper portion and the lower portion and in the internal passage, wherein the expander is configured to move proximally relative to the upper and lower portions from a first position to a second position, the expander comprising a distal nose portion to facilitate insertion into the intervertebral space, wherein in the first position, the expandable cage is unexpanded and the distal nose portion extends at least partially distally past a distal portion of the cage body, and wherein in the second position, the expandable cage is expanded, increasing the space between the upper portion outer surface and the lower portion outer surface.

16. The expandable cage of claim 15, wherein the distal nose portion is integral with the elongate expander.

17. The expandable cage of claim 15, wherein the expander moves from the first position to the second position by pulling the expander proximally.

18. The expandable cage of claim 15, wherein the upper portion has an upper portion inner surface and the lower portion has a lower portion inner surface, and wherein portions of the distal portion of the expander are complementarily shaped with at least one of the upper portion inner surface and the lower portion inner surface, whereby pulling the expander proximally cams the distal portion of the expander against the at least one of the upper portion inner surface and the lower portion inner surface to expand the cage body.

19. The expandable cage of claim 15, further comprising a means to retain the cage body in the unexpanded position and resist expansion during insertion of the expandable cage into the intervertebral space.

20. The expandable cage of claim 15, wherein the proximal portion of the cage body defines an aperture in communication with the internal passage.

21. The expandable cage of claim 20, further comprising a set screw sized and shaped to complementarily fit within the aperture and retain the expander in the second position.

22. The expandable cage of claim 15, wherein a portion of the distal portion of the expander comprises a first side surface and a second side surface, wherein one of the side surfaces defines at least one substantially longitudinal slot.

23. The expandable cage of claim 22, wherein the distal end of the upper portion and the distal end of the lower portion each comprise a tongue sized for a complimentary fit within the at least one substantially longitudinal slot when the cage body is in the unexpanded position, and wherein moving the expander into the second position moves the tongue out of engagement with the substantially longitudinal slot.

24. The expandable cage of claim 23, wherein the upper and lower portions comprise bilateral tongues.

25. The expandable cage of claim 15, wherein the distal end of the upper and lower portions each comprise a hook positioned thereon the respective inner surface. 5

26. The expandable cage of claim 25, wherein the distal portion of the expander defines recesses for complimentary receipt of the respective hooks when the cage body is in the unexpanded position, and wherein moving the expander into the second position moves the hooks out of engagement with 10 the recesses.

27. The expandable cage of claim 15, wherein a portion of the distal end of the upper portion and a portion of the distal end of the lower portion are bonded together when the cage body is in the unexpanded position, and wherein 15 moving the expander into the second position breaks the bond, allowing the cage body to move into the expanded position.

28. The expandable cage of claim 15, wherein the cage body defines one or more windows in communication with 20 the internal passage.

* * * * *