



US 20110319997A1

(19) **United States**

(12) **Patent Application Publication**
Glerum et al.

(10) **Pub. No.: US 2011/0319997 A1**

(43) **Pub. Date: Dec. 29, 2011**

(54) **EXPANDABLE FUSION DEVICE AND
METHOD OF INSTALLATION THEREOF**

(52) **U.S. Cl. 623/17.15; 623/17.11**

(76) **Inventors:** **Chad Glerum**, Pennsburg, PA
(US); **Sean Suh**, Plymouth Meeting,
PA (US); **Jody L. Seifert**,
Birdsboro, PA (US)

(57) **ABSTRACT**


The present invention provides an expandable fusion device capable of being installed inside an intervertebral disc space to maintain normal disc spacing and restore spinal stability, thereby facilitating an intervertebral fusion. In one embodiment, the fusion device includes a body portion, a first endplate, and a second endplate, the first and second endplates capable of being moved in a direction away from the body portion into an expanded configuration or capable of being moved towards the body portion into an unexpanded configuration. The fusion device is capable of being deployed and installed in both configurations.


(21) **Appl. No.: 12/823,736**

(22) **Filed: Jun. 25, 2010**

Publication Classification

(51) **Int. Cl.**
A61F 2/44 (2006.01)








FIG. 3




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14






FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25

EXPANDABLE FUSION DEVICE AND METHOD OF INSTALLATION THEREOF

FIELD OF THE INVENTION

[0001] The present invention relates to the apparatus and method for promoting an intervertebral fusion, and more particularly relates to an expandable fusion device capable of being inserted between adjacent vertebrae to facilitate the fusion process.

BACKGROUND OF THE INVENTION

[0002] A common procedure for handling pain associated with intervertebral discs that have become degenerated due to various factors such as trauma or aging is the use of intervertebral fusion devices for fusing one or more adjacent vertebral bodies. Generally, to fuse the adjacent vertebral bodies, the intervertebral disc is first partially or fully removed. An intervertebral fusion device is then typically inserted between neighboring vertebrae to maintain normal disc spacing and restore spinal stability, thereby facilitating an intervertebral fusion.

[0003] There are a number of known conventional fusion devices and methodologies in the art for accomplishing the intervertebral fusion. These include screw and rod arrangements, solid bone implants, and fusion devices which include a cage or other implant mechanism which, typically, is packed with bone and/or bone growth inducing substances. These devices are implanted between adjacent vertebral bodies in order to fuse the vertebral bodies together, alleviating the associated pain.

[0004] However, there are drawbacks associated with the known conventional fusion devices and methodologies. For example, present methods for installing a conventional fusion device often require that the adjacent vertebral bodies be distracted to restore a diseased disc space to its normal or healthy height prior to implantation of the fusion device. In order to maintain this height once the fusion device is inserted, the fusion device is usually dimensioned larger in height than the initial distraction height. This difference in height can make it difficult for a surgeon to install the fusion device in the distracted intervertebral space.

[0005] As such, there exists a need for a fusion device capable of being installed inside an intervertebral disc space at a minimum to no distraction height and for a fusion device that can maintain a normal distance between adjacent vertebral bodies when implanted.

SUMMARY OF THE INVENTION

[0006] In an exemplary embodiment, the present invention provides an expandable fusion device capable of being installed inside an intervertebral disc space to maintain normal disc spacing and restore spinal stability, thereby facilitating an intervertebral fusion. In one embodiment, the fusion device includes a body portion, a first endplate, and a second endplate. The first and second endplates are capable of being moved in a direction away from the body portion into an expanded configuration or capable of being moved towards the body portion into an unexpanded configuration. The expandable fusion device is capable of being deployed and installed in the unexpanded configuration or the expanded configuration.

[0007] Further areas of applicability of the present invention will become apparent from the detailed description pro-

vided hereinafter. It should be understood that the detailed description and specific examples, while indicating the preferred or exemplary embodiments of the invention, are intended for purposes of illustration only and are not intended to limit the scope of the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

[0008] The present invention will become more fully understood from the detailed description and the accompanying drawings, wherein:

[0009] FIG. 1 is a side view of an embodiment of an expandable fusion device shown between adjacent vertebrae according to the present invention;

[0010] FIG. 2 is an exploded view of the expandable fusion device of FIG. 1;

[0011] FIG. 3 is a rear perspective view of the expandable fusion device of FIG. 1 shown in an unexpanded position;

[0012] FIG. 4 is a side cross-sectional view of the expandable fusion device of FIG. 1 shown with one of the endplates removed;

[0013] FIG. 5 is a side partial cross-sectional view of the expandable fusion device of FIG. 1 shown in an unexpanded position;

[0014] FIG. 6 is a side partial cross-sectional view of the expandable fusion device of FIG. 1 shown in an expanded position;

[0015] FIG. 7 is a side schematic view of the expandable fusion device of FIG. 1 having different endplates;

[0016] FIG. 8 is a partial side schematic view of the expandable fusion device of FIG. 1 showing different modes of endplate expansion;

[0017] FIG. 9 is a side schematic view of the expandable fusion device of FIG. 1 with artificial endplates shown between adjacent vertebrae;

[0018] FIG. 10 is a side view cross-sectional view of another embodiment of an expandable fusion device shown in an unexpanded position;

[0019] FIG. 11 is a side view cross-sectional view of the expandable fusion device of FIG. 10 shown in an expanded position;

[0020] FIG. 12 is a side view of the expandable fusion device of FIG. 10 showing the translation member and the ramped insert;

[0021] FIG. 13 is a front perspective view of the expandable fusion device of FIG. 10 showing the translation member and the ramped insert;

[0022] FIG. 14 is a rear perspective of another embodiment of an expandable fusion device with the endplates having a threaded hole;

[0023] FIG. 15 is a top view of another embodiment of an expandable fusion device shown in an unexpanded position;

[0024] FIG. 16 is a bottom view of the expandable fusion device of FIG. 15;

[0025] FIG. 17 is top view of the expandable fusion device of FIG. 15 shown in an expanded position;

[0026] FIG. 18 is an exploded perspective view of another embodiment of an expandable fusion device;

[0027] FIG. 19 is an end view of the expandable fusion device of FIG. 18 in an unexpanded position;

[0028] FIG. 20 is an end view of the expandable fusion device of FIG. 18 in an expanded position;

[0029] FIG. 21 is a perspective view of another embodiment of an expandable fusion device;

[0030] FIG. 22 is a top view of the expandable fusion device of FIG. 21;

[0031] FIG. 23 is a perspective view of the expandable fusion device of FIG. 21 with a closed end.

[0032] FIG. 24 is a front view of the expandable fusion device of FIG. 23 shown between adjacent vertebrae in an unexpanded position; and

[0033] FIG. 25 is a front view of the expandable fusion device of FIG. 23 shown between adjacent vertebrae in an expanded position.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0034] The following description of the preferred embodiment(s) is merely exemplary in nature and is in no way intended to limit the invention, its application, or uses.

[0035] A spinal fusion is typically employed to eliminate pain caused by the motion of degenerated disk material. Upon successful fusion, a fusion device becomes permanently fixed within the intervertebral disc space. Looking at FIG. 1, an exemplary embodiment of an expandable fusion device 10 is shown between adjacent vertebral bodies 2 and 3. The fusion device 10 engages the endplates 4 and 5 of the adjacent vertebral bodies 2 and 3 and, in the installed position, maintains normal intervertebral disc spacing and restores spinal stability, thereby facilitating an intervertebral fusion. The expandable fusion device 10 can be manufactured from a number of materials including titanium, stainless steel, titanium alloys, non-titanium metallic alloys, polymeric materials, plastics, plastic composites, PEEK, ceramic, and elastic materials.

[0036] In an exemplary embodiment, bone graft or similar bone growth inducing material can be introduced around and within the fusion device 10 to further promote and facilitate the intervertebral fusion. The fusion device 10, in one embodiment, is preferably packed with bone graft or similar bone growth inducing material to promote the growth of bone through and around the fusion device. Such bone graft may be packed between the endplates of the adjacent vertebral bodies prior to, subsequent to, or during implantation of the fusion device.

[0037] With reference to FIG. 2, an exploded perspective view of one embodiment of the fusion device 10 is shown. In an exemplary embodiment, the fusion device 10 includes a body portion 12, a first endplate 14, a second endplate 16, a translation member 18, an actuation member 20, and an insert 22.

[0038] With additional reference to FIGS. 3-6, in an exemplary embodiment, the body portion 12 has a first end 24, a second end 26, a first side portion 28 connecting the first end 24 and the second end 26, and a second side portion 29 on the opposing side of the body portion 12 connecting the first end 24 and the second end 26. The body portion 12 further includes an upper end 30, which is sized to receive at least a portion of the first endplate 14, and a lower end 32, which is sized to receive at least a portion of the second endplate 16.

[0039] The first end 24 of the body portion 12, in an exemplary embodiment, includes at least one angled surface 34, but can include multiple angled surfaces. The angled surface 34 can serve to distract the adjacent vertebral bodies when the fusion device 10 is inserted into an intervertebral space. In another preferred embodiment, it is contemplated that there are at least two opposing angled surfaces forming a generally

wedge shaped to distract the adjacent vertebral bodies when the fusion device 10 is inserted into an intervertebral space.

[0040] The second end 26 of the body portion 12, in an exemplary embodiment, includes an opening 36 which may include threading. In another exemplary embodiment, the opening 36 may include ratchet teeth instead of threading. The opening 36 extends from the second end 26 of the body portion 12 into a central opening (not illustrated) in the body portion 12. In one embodiment, the central opening is sized to receive the translation member 18, and the opening 36 is sized to threadingly receive the actuation member 20. In another exemplary embodiment, the opening 36 is sized to receive the actuation member 20 in a ratcheting fashion. In yet another exemplary embodiment, first side portion 28 and second side portion 29 each include a recess 38 located towards the second end 26 of the body portion 12. The recess 38 is configured and dimensioned to receive an insertion instrument (not shown) that assists in the insertion of the fusion device 10 into an intervertebral space.

[0041] Although the following discussion relates to the first endplate 14, it should be understood that it also equally applies to the second endplate 16 as the second endplate 16 is substantially identical to the first endplate 14 in embodiments of the present invention. Turning now to FIGS. 2-6, in an exemplary embodiment, the first endplate 14 has an upper surface 40, a lower surface 42, and a through opening 43. The through opening 43, in an exemplary embodiment, is sized to receive bone graft or similar bone growth inducing material and further allow the bone graft or similar bone growth inducing material to be packed in the central opening in the body portion 12.

[0042] In one embodiment, the lower surface 42 includes at least one extension 44 extending along at least a portion of the lower surface 42. As best seen in FIGS. 3 and 4, in an exemplary embodiment, the extension 44 can extend along a substantial portion of the lower surface 42, including, along each side of the endplate 14 and along the front end of the endplate 14. In another exemplary embodiment, the extension 44 includes at least one ramped portion 46, but can include any number of ramped portions, including two spaced ramped portions 46, 48 in the extension 44 that extend between each side of the endplate 14, as best seen in FIG. 4. It is contemplated that the slope of the ramped portions 46, 48 can be equal or can differ from each other. The effect of varying the slopes of the ramped portions 46, 48 is discussed below.

[0043] In an exemplary embodiment, the ramped portions 46, 48 further include grooved portions 47, 49 that are configured and dimensioned to receive angled surfaces 58, 60 of the translation member 18 and are oriented in an oblique fashion. In a preferred embodiment, the grooved portions 46, 48 are dovetail grooves configured and dimensioned to hold the angled surfaces 58, 60 of the translation member 18 while allowing the angled surfaces 58, 60 to slide against the ramped portions 46, 48.

[0044] Referring now to FIGS. 3-6, in one embodiment, the upper surface 40 of the first endplate 14 is flat and generally planar to allow the upper surface 40 of the endplate 14 to engage with the adjacent vertebral body 2. Alternatively, as shown in FIG. 7, the upper surface 40 can be curved convexly or concavely to allow for a greater or lesser degree of engagement with the adjacent vertebral body 2. It is also contemplated that the upper surface 40 can be generally planar but includes a generally straight ramped surface or a curved ramped surface. The ramped surface allows for engagement

with the adjacent vertebral body 2 in a lordotic fashion. Turning back to FIGS. 2-6, in an exemplary embodiment, the upper surface 40 includes texturing 50 to aid in gripping the adjacent vertebral bodies. Although not limited to the following, the texturing can include teeth, ridges, friction increasing elements, keels, or gripping or purchasing projections.

[0045] With reference to FIGS. 2 and 4-6, in an exemplary embodiment, the translation member 18 is sized to be received within the central opening of the body portion 12 and includes at least a first expansion portion 52. In another embodiment, the translation member 18 includes a first expansion portion 52 and a second expansion portion 54, the expansion portions 52, 54 being connected together via a bridge portion 56. It is also contemplated that there may be more than two expansion portions where each of the expansion portions is connected by a bridge portion. The expansion portions 52, 54 each have angled surfaces 58, 60 configured and dimensioned to engage the grooved portions 46, 48 of the first and second endplates 14, 16. In one embodiment, the translation member 18 includes an opening 62 in the first expansion portion 52, which is sized to receive a portion of the actuation member 20, as best seen in FIG. 4. In an exemplary embodiment, the first expansion portion 52 includes a central bore 63 that extends from the opening 62 and through the first expansion portion 52. In one embodiment, the translation member 18 includes a hole 64 in the second expansion portion 54, which is sized to receive nose 66, as best seen in FIGS. 5 and 6. In an exemplary embodiment, the hole 64 includes threading 68 for threadedly receiving a threaded end 70 of the nose 66, as shown on FIG. 6. The nose 66 is received in an opening 72 in the first end 34 of the body portion 12 to stabilize the translation member 18 in the central opening of the body portion 12.

[0046] In one embodiment, the translation member 18 includes a locking mechanism 74, which is configured and adapted to engage the actuation member 20. As illustrated, the locking mechanism 74 may extend from the first expansion portion 52. The locking mechanism 74 includes a slot 76 configured and adapted to receive extension 87 of the actuation member 20. In an exemplary embodiment, the locking mechanism 74 further includes a stop 78 (e.g., a rim, a lip, etc.) that engages the actuation member 20 when it is disposed in the slot 76.

[0047] Referring now to FIGS. 2-6, in an exemplary embodiment, the actuation member 20 has a first end 80, a second end 82, and threading (not illustrated) extending along at least a portion thereof from the first end 80 to the second end 82. The threading threadingly engages the threading that extends along a portion of opening 36 in the body portion 12. In another exemplary embodiment, the actuation member 20 includes ratchet teeth instead of threading. The ratchet teeth engage corresponding ratchet teeth in the opening 36 in the body portion 12. The first end 80 includes a recess 84 dimensioned to receive an instrument (not shown) that is capable of advancing the actuation member 20 with respect to the body portion 12 of the fusion device 10. In an embodiment, the actuation member 20 includes a bore 85, as best seen by FIG. 4, that extends from the recess 84 in the first end to the second end 82. The second end 82 of the actuation member 20 includes an extension 86 that is received within the opening 62 in the first expansion portion 52. In one embodiment, the extension 88 may include a lip portion 86 and a plurality of slits 88. The plurality of slits 88 are configured to receive inserts 22. Inserts 22 are provided to limit motion of the actuation member 20.

Once the lip portion 86 is placed into the slot 76 of the locking mechanism 74, the lip portion 86 will engage the stop 78 preventing longitudinal movement of the actuation member 20 with respect to the translation member 18. It is further contemplated that a pin member 90 can be included to further secure the actuation member 20 in the translation member 19. In an embodiment, the pin member 90 can be pressed into the central bore 85 of the actuation member 20 and the central bore 63 of the translation member, thereby preventing the actuation member 20 from disengaging from the translation member 18. Additionally, in an exemplary embodiment, the fusion device 10 can further include a chamfered tip 24 for distraction of adjacent vertebrae.

[0048] Turning now to FIGS. 1-6, a method of installing the expandable fusion device 10 is now discussed. Prior to insertion of the fusion device 10, the intervertebral space is prepared. In one method of installation, a discectomy is performed where the intervertebral disc, in its entirety, is removed. Alternatively, only a portion of the intervertebral disc can be removed. The endplates of the adjacent vertebral bodies 2, 3 are then scraped to create an exposed end surface for facilitating bone growth across the intervertebral space. The expandable fusion device 10 is then introduced into the intervertebral space, with the first end 22 of the body portion 12 being inserted first into the disc space followed by the second end 24. In an exemplary method, the fusion device 10 is in the unexpanded position when introduced into the intervertebral space. The wedged-shaped first end 22 should assist in distracting the adjacent vertebral bodies 2, 3, if necessary. This allows for the option of having little to no distraction of the intervertebral space prior to the insertion of the fusion device 10. In another exemplary method, the intervertebral space may be distracted prior to insertion of the fusion device 10. The distraction provide some benefits by providing greater access to the surgical site making removal of the intervertebral disc easier and making scraping of the endplates of the vertebral bodies 2, 3 easier.

[0049] With the fusion device 10 inserted into and seated in the appropriate position in the intervertebral disc space, the fusion device can then expanded into the expanded position, as best seen in FIGS. 1, 5, and 6. To expand the fusion device 10, an instrument is engaged with recess 84 in the actuation member 20. The instrument is used to rotate actuation member 20. As discussed above, actuation member 20 can be threadingly engaging body portion 12 and is engaged with translation member 18; thus, as the actuation member 20 is rotated in a first direction, the actuation member 20 and the translation member 18 move with respect to the body portion 12 toward the first end 22 of the body portion 12. In another exemplary embodiment, the actuation member 20 is moved in a linear direction with the ratchet teeth engaging as means for controlling the movement of the actuation member 20 and the translation member 18. As the translation member 18 moves, the angled surfaces 58, 60 of the expansion portions 52, 54 push against the ramped portions 46, 48 of the endplates 14, 16 pushing endplates 14, 16 outwardly into the expanded position with the angled surfaces 58, 60 riding along the grooved portions 47, 48 of the ramped portions 46, 48. This can best be seen in FIGS. 5 and 6. Since the expansion of the fusion device 10 is actuated by a rotational input, the expansion of the fusion device 10 is infinite. In other words, the endplates 14, 16 can be expanded to an infinite number of heights dependent on the rotational advancement of the actuation member 20. As discussed above, the fusion device 10

includes a locking mechanism 22 which assists in retaining the endplates 14, 16 at the desired height.

[0050] It should also be noted that the expansion of the endplates 14, 16 can be varied based on the differences in the dimensions of the ramped portions 46, 48 and the angled surfaces 58, 60. As best seen in FIG. 8, the endplates 14, 16 can be expanded in any of the following ways: straight rise expansion, straight rise expansion followed by a toggle into a lordotic expanded configuration, or a phase off straight rise into a lordotic expanded configuration.

[0051] Turning back to FIGS. 1-6, in the event the fusion device 10 needs to be repositioned or revised after being installed and expanded, the fusion device 10 can be contracted back to the unexpanded configuration, repositioned, and expanded again once the desired positioning is achieved. To contract the fusion device 10, the instrument is engaged with recess 84 in the actuation member 20. The instrument is used to rotate actuation member 20. As discussed above, actuation member 20 can be threadingly engaging body portion 12 and is engaged with translation member 18; thus, as the actuation member 20 is rotated in a second direction, opposite the first direction, the actuation member 20 and translation member 18 move with respect to the body portion 12 toward the second end 26 of the body portion 12. As the translation member 18 moves, the angled surfaces 58, 60 of the translation member 18 ride along the grooved portions 47, 49 pulling the endplates 14, 16 inwardly into the unexpanded position.

[0052] With reference now to FIG. 9, fusion device 10 is shown with an exemplary embodiment of artificial endplates 100. Artificial endplates 100 allows the introduction of lordosis even when the endplates 14 and 16 of the fusion device 10 are generally planar. In one embodiment, the artificial endplates 100 have an upper surface 102 and a lower surface 104. The upper surfaces 102 of the artificial endplates 100 have at least one spike 106 to engage the adjacent vertebral bodies. The lower surfaces 104 have complementary texturing or engagement features on their surfaces to engage with the texturing or engagement features on the upper endplate 14 and the lower endplate 16 of the fusion device 10. In an exemplary embodiment, the upper surface 102 of the artificial endplates 100 have a generally convex profile and the lower surfaces 104 have a generally parallel profile to achieve lordosis. In another exemplary embodiment, fusion device 10 can be used with only one artificial endplate 100 to introduce lordosis even when the endplates 14 and 16 of the fusion device 10 are generally planar. The artificial endplate 100 can either engage endplate 14 or engage endplate 16 and function in the same manner as described above with respect to two artificial endplates 100.

[0053] Referring now to FIGS. 10 and 11, an alternative embodiment of the fusion device 10 is shown. In an exemplary embodiment, the fusion device 10 includes a body portion 12, a first endplate 14, a second endplate 16, a translation member 18, and an actuation member 20. In the illustrated embodiment, the fusion device further includes a first ramped insert 120 and a second ramped insert 122.

[0054] Although the following discussion relates to the first ramped insert 120, it should be understood that it also equally applies to the second ramped insert 122 as the second ramped insert 122 is substantially identical to the first ramped insert 120 in embodiments of the present invention. Turning now to FIGS. 10-13, in an exemplary embodiment, the first ramped insert 120 includes a first ramped portion 124 and a second

ramped portion 126, the first and second ramped portions 124, 126 being connected by a bridge portion 128. The ramped portions 124, 126 each have grooved portions 130, 132 configured and dimensioned to receive angled surfaces 58, 60 of the translation member. The ramped portions 124, 126 can be oriented in an oblique fashion, as illustrated. In a preferred embodiment, the grooved portions 130, 132 are dovetail grooves configured and dimensioned to hold the angled surfaces 58, 60 of the translation member 18 while allowing the angled surfaces 58, 60 to slide against the ramped portions 124, 126.

[0055] In an exemplary embodiment, the first ramped insert 120 should be configured and dimensioned to be engaged with the first endplate 14. In an embodiment, the first and second ramped portions 124, 126 include snap connectors 134, 136 for securing the first ramped insert 120 to the first endplate. It should be understood that the snap connectors 134, 136 are merely illustrative and that other suitable mechanisms for securing the first ramped insert 120 with the first endplate 14 may be used.

[0056] Referring to FIGS. 10-13, in an exemplary embodiment, the translation member 18 is sized to be received within the central opening of the body portion 12 and includes at least a first expansion portion 52. In another embodiment, the translation member 18 includes a first expansion portion 52 and a second expansion portion 54, the expansion portions 52, 54 being connected together via a bridge portion 56. It is also contemplated that there may be more than two expansion portions where each of the expansion portions is connected by a bridge portion. The expansion portions 52, 54 each have angled surfaces 58, 60 configured and dimensioned to engage the grooved portions 130, 132 of the first and second ramped inserts 120, 122. In one embodiment, the angled surfaces 58, 60 include corresponding grooved portions 138, 140, as best seen in FIG. 13, that slidably engaged the grooved portions 130, 132 of the first and second ramped inserts 120, 122.

[0057] In one embodiment, the expansion portion 52 includes an opening 62, which is sized to receive a portion of the actuation member 20, and the expansion portion 62 includes a nose 66, which is received within an opening 72 in the first end 34 of the body portion 12 to stabilize the translation member 18 in the central opening of the body portion 12. In an embodiment, the nose 66 is integral with the expansion portion 62. In an embodiment (shown on FIGS. 2 and 4-6), the nose 66 is threadingly engaged with the expansion portion 62. In an embodiment, the translation member 18 includes a locking mechanism 74 to engage the actuation member 20, as illustrated in FIGS. 2-6. However, it should be understood that other suitable mechanisms may be used to secure the actuation member 20 within the translation member 18. For example, the actuation member 20 may include an extension 87 having a lip portion 86 (shown on FIGS. 2 and 4-6) that engages the expansion portion 62. The extension 87 may, for example, be configured to flex inwardly reducing its diameter when received in the opening 62. Once the lip portion 86 of the extension 87 is advanced beyond the end of the opening 62, the extension portion 87 will return back to its original diameter and the lip portion 86 will engage the expansion portion 60.

[0058] The expandable fusion device 10 of FIGS. 10-13 can be inserted into the intervertebral space in a manner similar to that the previously described with respect to FIGS. 1-6. After insertion, the expandable fusion device 10 of FIGS. 10-13 can be expanded into the expanded position, as best

seen in FIGS. 10 and 11. To expand the fusion device 10, an instrument is engaged with recess 84 in the actuation member 20. The instrument is used to rotate actuation member 20. As discussed above, actuation member 20 can be threadingly engaging body portion 12 and is engaged with translation member 18; thus, as the actuation member 20 is rotated in a first direction, the actuation member 20 and the translation member 18 move with respect to the body portion 12 toward the first end 22 of the body portion 12. In another exemplary embodiment, the actuation member 20 is moved in a linear direction with the ratchet teeth engaging as means for controlling the movement of the actuation member 20 and the translation member 18. As the translation member 18 moves, the angled surfaces 58, 60 of the expansion portions 52, 54 push against the ramped portions 124, 126 of the first and second ramped inserts 120, 122 while riding along the grooved portions 130, 132, thus pushing first and second ramped inserts 120, 122 outwardly. Because the first and second ramped inserts 120, 122 are engaged with the endplates 14, 16, the endplates 14, 16 are also pushed outwardly into the expanded position.

[0059] After expansion, the expandable fusion device 10 can be contracted back to the unexpanded configuration. To contract the fusion device 10, the instrument is engaged with recess 84 in the actuation member 20. The instrument is used to rotate actuation member 20. As discussed above, actuation member 20 can be threadingly engaging body portion 12 and is engaged with translation member 18; thus, as the actuation member 20 is rotated in a second direction, opposite the first direction, the actuation member 20 and translation member 18 move with respect to the body portion 12 toward the second end 26 of the body portion 12. As the translation member 18 moves, the angled surfaces 58, 60 of the translation member 18 ride along the grooved portions 130, 132 pulling the first and second ramped inserts 120, 122 and thus, the endplates 14, 16 inwardly into the unexpanded position.

[0060] Referring now to FIG. 14, an alternative embodiment of the fusion device 10 is shown. In an exemplary embodiment, the first endplate 14 and the second endplate 16 each include additional geometry to help securely hold the endplates 14, 16 in place. In an embodiment, the first endplate 14 and/or the second endplate 16 include threaded holes 141 through which the fasteners, such as screws 142, may be inserted. In an embodiment, the threaded holes 141 penetrate through the first endplate 14 and/or the second endplate 16 in an oblique fashion. It is contemplated that the screws 142 may be inserted through the threaded holes 141 and into adjacent vertebral bodies 2, 3, to further secure the first endplate 14 and the second endplate 16 to the vertebral bodies 2, 3. In some embodiments, these fasteners may be removed once a more long-term interface has been established, or alternatively the fasteners may remain in place indefinitely or until the fusion device 10 needs adjustment and/or replacement.

[0061] With reference now FIGS. 15-17, an alternative embodiment of the fusion device 10 is shown that expands laterally. Lateral expansion maximizes coverage of the intra-vertebral disc space for wider load distribution and stability providing a rigid foundation for fusion. In one embodiment, the fusion device 10 includes body portion 12, first endplate 144, and second endplate 146.

[0062] Although the following discussion relates to the first endplate 144, it should be understood that it also equally applies to the second endplate 146 as the second endplate 146 is substantially identical to the first endplate 144 in embodi-

ments of the present invention. Turning now to FIGS. 15-17, in an exemplary embodiment, the first endplate 144 has an upper surface 148, a lower surface 150, and an inner surface 151 facing the body portion 12. It is contemplated that the upper surface 148 will engage adjacent vertebral body 2 (seen on FIG. 1) and the lower surface 150 will engage adjacent vertebral body 3 (seen on FIG. 1). In one embodiment, the upper surface 148 and the lower surface 150 are each flat and generally planar to allow the upper surface 148 to engage with the adjacent vertebral body 3. Alternatively, the upper surface 148 and/or the lower surface 150 can be curved convexly or concavely to allow for a greater or lesser degree of engagement with the adjacent vertebral bodies 2, 3. It is also contemplated that the upper surface 148 and/or the lower surface 150 can be generally planar but includes a generally straight ramped surface or a curved ramped surface. The ramped surface allows for engagement with the adjacent vertebral body 2 and/or the adjacent vertebral body 3 in a lordotic fashion. In an exemplary embodiment, the upper surface 148 and/or lower surface 150 includes textures 152 to aid in gripping the adjacent vertebral bodies. Although not limited to the following, the texturing can include teeth, ridges, friction increasing elements, keels, or gripping or purchasing projections.

[0063] In one embodiment, the inner surface 151 includes at least one extension 154 extending along at least a portion of the inner surface 151. In an exemplary embodiment, the extension 154 can extend along a substantial portion of the inner surface 154, including, along each side of the endplate 144 and along the front end of the endplate 14. While not illustrated, the inner surface may include ramped surfaces and grooved portions in an exemplary embodiment. It is contemplated that the ramped surfaces and/or grooved portions may be similar to the ramped surfaces 46, 48 and grooved portion 47, 49 in extension 44 shown on FIGS. 4-6. In an embodiment, the extension 154 may include slots 156 oriented in an oblique fashion through which pins 158 may be inserted.

[0064] While not illustrated, the fusion device 10 further includes features to effectuate the lateral expansion of the first and second endplates 144, 146. In one embodiment, the fusion device 10 using a ramping system—similar to the system illustrated in FIGS. 2 and 4-6—for expanding the first and second endplates 144, 146. In an exemplary embodiment, the fusion device 10 further includes a translation member and actuation member, such as translation member 18 and actuation member 20 shown on FIGS. 2 and 4-6. It is contemplated that the translation member may include angled surfaces that push against ramped surfaces in the extension 154, expanding the first and second endplates 144, 146 outwardly and away from the body portion 12. In an embodiment, pins 156 disposed through the slots 154 may be retained in the translation member. In an alternative embodiment, dovetailing may be used for engagement of the angled surfaces and ramped surfaces. It should be understood that the translation member and actuation member in this embodiment may be similar to the translation member 18 and actuation member 20 described above with respect to FIGS. 1-6. In another embodiment, the fusion device 10 further includes first and second ramped inserts that are secured within the first and second endplates 144, 146. The first and second ramped inserts may be similar to the first and second ramped inserts 120, 122 described above with respect to FIGS. 10-13. It is contemplated that angled surfaces in the translation member may push against ramped surfaces in the ramped inserts push-

ing the ramped inserts outwardly. Because of their engagement with the first and second endplates **144**, **146**, the first and second endplates **144**, **146** may thus be expanded outwardly. In this manner, the first and second endplates **144**, **146** may be laterally expanded away from the body portion **12**. It should be understood that other suitable techniques may also be used to effectuate this lateral expansion.

[0065] With reference to FIG. **18**, an exploded perspective view of another embodiment of fusion device **10** is shown. In an exemplary embodiment, the fusion device **10** includes a body portion **12**, a first endplate **200**, a second endplate **202**, a third endplate **204**, a fourth endplate **206**, and a translation member **18**. In this embodiment, the fusion device **10** is configured to expand both vertically and laterally.

[0066] In an exemplary embodiment, the body portion **12** has a first end **24**, a second end **26**, a first side portion **28** connecting the first end **24** and the second end **26**, and a second side portion **29** on the opposing side of the body portion **12** connecting the first end **24** and the second end **26**. The body portion **12** further includes a top side portion **208** connecting the first end **24** and the second end **26**, and a bottom side portion **210** on the opposing side of the body portion **12** connecting the first end **24** and the second end **26**. The body portion **12** further includes first gap **212** between the top side portion **208** and the first side portion **28**, which is sized to receive at least a portion of the first endplate **200**. The body portion **12** further includes second gap **214** between the top side portion **208** and the second side portion **29**, which is sized to receive at least a portion of the second endplate **202**. The body portion **12** further includes third gap **216** between the bottom side portion **210** and the first side portion **28**, which is sized to receive at least a portion of the third endplate **204**. The body portion **12** further includes fourth gap **218** between the bottom side portion **210** and the second side portion **29**, which is sized to receive at least a portion of the fourth endplate **206**.

[0067] The first end **24** of the body portion **12**, in an exemplary embodiment, includes an opening **220**. The opening **220** extends from the first end **24** of the body portion **12** into a central opening **222**. In one embodiment, the central opening **222** is sized to receive the translation member **18**. The second end **26** of the body portion **12**, in an exemplary embodiment, includes an opening **36**, which extends from the second end **26** of the body portion **12** into the central opening **222**.

[0068] Although the following discussion relates to the first endplate **200**, it should be understood that it also equally applies to the second endplate **202**, the third endplate **204**, and the fourth endplate **206**, as these endplates **202**, **204**, **206** are substantially identical to the first endplate **200** in embodiments of the present invention. Turning now to FIGS. **18-20**, in an exemplary embodiment, the first endplate **14** has a first end **224** and a second end **226**. The first endplate further includes an upper surface **40** connecting the first end **224** and the second end **226** and a lower surface **42** on an opposing side of the endplate **200** connecting the first end **224** and the second end **226**. While not illustrated, the first endplate **14** may include a through opening sized to receive bone graft or similar bone growth inducing material and further allow the bone graft or similar bone growth inducing material to be packed in the central opening **222** in the body portion **12**.

[0069] In one embodiment, the lower surface **42** includes at least one first retaining socket **228** on the lower surface **42**. In an exemplary embodiment, the lower surface **42** includes a

first retaining socket **228** at the interior corner of the intersection of the first end **224** and the lower surface **42**, and a second retaining socket **230** at the interior corner of the intersection of the first end **224** and the lower surface **42**.

[0070] Referring now to FIGS. **18-20**, in one embodiment, the upper surface **40** of the first endplate **200** is curved convexly. Alternatively, the upper surface **40** is flat or curved concavely to allow for a greater or lesser degree of engagement with the adjacent vertebral body **2**. It is also contemplated that the upper surface **40** can be generally planar but includes a generally straight ramped surface or a curved ramped surface. The ramped surface allows for engagement with the adjacent vertebral body **2** in a lordotic fashion. In an exemplary embodiment, the upper surface **40** includes texturing **50** to aid in gripping the adjacent vertebral bodies. Although not limited to the following, the texturing can include teeth, ridges, friction increasing elements, keels, or gripping or purchasing projections.

[0071] With reference to FIG. **18**, in an exemplary embodiment, the translation member **18** is sized to be received within the central opening **222** of the body portion **12**. The translation member **18** should be sized to allow longitudinal translation within the central opening **222**. In an embodiment, the translation member **18** includes at least a first expansion portion **52**. In another embodiment, the translation member **18** includes a first expansion portion **52** and a second expansion portion **54**, the expansion portions **52**, **54** being connected together via a bridge portion **56**. It is also contemplated that there may be more than two expansion portions where each of the expansion portions is connected by a bridge portion. The expansion portions **52**, **54** each have angled surfaces **58**, **60**. In an embodiment, the angled surfaces **58**, **60** each comprise first end **229** and second end **231** with second end **231** being wider than the first end **229**. In an exemplary embodiment, the expansion portions **52**, **54** include grooved portions **232**, **234** on the edges of at least two sides (e.g., the lateral sides) of the angled surfaces **58**, **60**. The grooved portions **232**, **234** are configured and dimensioned to engage the first and second retaining sockets **228**, **230** on the endplates **200**, **202**, **204**, **206**. In an exemplary embodiment, the grooved portions **232**, **234** retain the first and second retaining sockets **228**, **230** in sliding engagement.

[0072] In one embodiment, the translation member **18** includes a first end **236** and a second end **238**. The first end **236** of the translation member includes an extension **240** sized to be received within the opening **220** in the first end **24** of the body portion **12**. While not illustrated, the second end **238** also can include a similar extension sized to be received within opening **32** in the second end **26** of the body portion **12**.

[0073] The expandable fusion device **10** of FIGS. **18-20** can be inserted into the intervertebral space in a manner similar to that the previously described with respect to FIGS. **1-6**. After insertion, the expandable fusion device **10** of FIGS. **18-20** can be expanded into the expanded position. As previously mentioned, the fusion device **10** shown on FIGS. **18-20** expands both vertically and laterally. To expand the fusion device **10**, the translation member **18** can be moved with respect to the body portion **12** toward the first end **24** of the body portion. An instrument can be used, in an exemplary embodiment. As the translation member **18** moves, the first retaining socket **228** and the second retaining socket **230** ride along the grooved portions **232**, **234** of the expansion portions **52**, **54** pushing the endplates **200**, **202**, **204**, **206** outwardly in the direction indicated by arrows **242**. In an embodiment, the

endplates **200**, **202**, **204**, **206** move outwardly in an oblique fashion to expand the fusion device **10** both vertically and laterally. The expanded configuration of the expansion device **10** is best seen in FIG. **20**.

[0074] After expansion, the expandable fusion device **10** can be contracted back to the unexpanded configuration. The unexpanded configuration of the fusion device **10** is best seen in FIG. **20**. To contract the fusion device **10**, the translation member **18** is moved with respect to the body portion **12** toward the second end **26** of the body portion **12**. As the translation member **18** moves, the first retaining socket **228** and the second retaining socket **230** ride along the grooved portions **232**, **234** of the expansion portions **52**, **54** pulling the endplates **200**, **202**, **204**, **206** inwardly in a direction opposite that indicated by arrows **242**. In an embodiment, the endplates **200**, **202**, **204**, **206** move inwardly in an oblique fashion to contract the fusion device **10** both vertically and laterally. The unexpanded configuration of the expansion device **10** is best seen in FIG. **19**.

[0075] With reference to FIGS. **21-22**, another embodiment of expandable fusion device **10** is shown. In an exemplary embodiment, the fusion device **10** includes a body portion **12**, a vertically expanding plate **300**, and a gear **302**. In this embodiment, a portion of the fusion device **10** is configured to expand vertically in at least one direction. In an exemplary embodiment, the vertically expanding plate **300** is configured to expand outwardly from the body portion **12**. It is contemplated that an expandable fusion device **10** may be used to correct spinal curvature due to, for example, scoliosis, lordosis, and the like.

[0076] In an exemplary embodiment, the body portion **12** has a first end **24**, a second end **26**, a first side portion **28** connecting the first end **24** and the second end **26**, and a second side portion **29** on the opposing side of the body portion **12** connecting the first end **24** and the second end **26**. The first end **24** of the body portion **12**, in an exemplary embodiment, includes at least one angled surface **34**, but can include multiple angled surfaces. The angled surface **34** can serve to distract the adjacent vertebral bodies when the fusion device **10** is inserted into an intervertebral space. In another preferred embodiment, it is contemplated that there are at least two opposing angled surfaces forming a generally wedge shaped to distract the adjacent vertebral bodies when the fusion device **10** is inserted into an intervertebral space. In yet another preferred embodiment, first side portion **28** and second side portion **29** each include a recess **38** located towards the second end **26** of the body portion **12**. The recess **38** is configured and dimensioned to receive an insertion instrument **304** that assists in the insertion of the fusion device **10** into an intervertebral space.

[0077] In an exemplary embodiment, the body portion **12** includes an upper engagement surface **306** extending from the first end **24** towards the second end **26**, and a lower engagement surface **308** extending between the first end **24** and the second end **26**. In an embodiment, the upper engagement surface **306** has a through opening **310**. Although not illustrated, the lower engagement surface **308** may have a through opening that is similar to through opening **310**. The through opening **310**, in an exemplary embodiment, is sized to receive bone graft or similar bone growth inducing material and further allow the bone graft or similar bone growth inducing material to be packed in the central opening in the body portion **12**. In an embodiment, at least a portion of the body portion **12** is removed to form a landing **312** in the body

portion **12**. In an exemplary embodiment, a portion of the upper engagement surface **306** and the second end **26** are removed to form the landing **312** having an upper surface **314**. While not illustrated, a portion of the lower engagement surface **308** and the second end **26** may be cut away, in an alternative embodiment, to form the landing **312**.

[0078] In one embodiment, the upper engagement surface **306** and the lower engagement surface **308** are flat and generally planar to allow engagement surfaces **306** to engage with the adjacent vertebral body **2** and the lower engagement surface **308** to engage with the adjacent vertebral body **3**. Alternatively, the upper engagement surface **306** and/or the lower engagement surface **308** can be curved convexly or concavely to allow for a greater or lesser degree of engagement with the adjacent vertebral bodies **2**, **3**. In an exemplary embodiment, the upper engagement surface **306** and/or the lower engagement surface includes texturing **312** to aid in gripping the adjacent vertebral bodies. Although not limited to the following, the texturing can include teeth, ridges, friction increasing elements, keels, or gripping or purchasing projections.

[0079] In an exemplary embodiment, vertically expanding plate **300** is coupled to an end of threaded bolt **318**, which is coupled to the gear **302**. In one embodiment, the threaded bolt **318** is in threaded engagement with the gear **302**. In an alternative embodiment, a bolt having ratchet teeth may be used instead of threaded bolt **318**. In an embodiment, the gear **302** is coupled to the landing **312**. In one embodiment, the gear **302** is rotatably coupled to the landing **312**.

[0080] The vertically expanding plate **300** includes a throughbore **319** and an upper surface **320**. In one embodiment, the vertically expanding plate **300** is generally circular in shape. Other suitable configurations of the expanding plate **300** may also be suitable. In an embodiment, the vertically expanding plate may be generally rectangular in shape with rounded corners, as best seen in FIG. **23**. In one embodiment, the vertically expanding plate **300** is flat and generally planar to allow upper surface **320** to engage with the adjacent vertebral body **2**. Alternatively, the upper surface **320** can be curved convexly or concavely to allow for a greater or lesser degree of engagement with the adjacent vertebral bodies. In an exemplary embodiment, the upper surface **320** includes texturing **322** to aid in gripping the adjacent vertebral bodies. Although not limited to the following, the texturing can include teeth, ridges, friction increasing elements, keels, or gripping or purchasing projections.

[0081] With reference to FIG. **23**, an alternative embodiment of the expandable fusion device **10** of FIGS. **21-22** is shown. In this embodiment, the gear **302** is enclosed within the body portion **12** towards the second end **26** of the body portion **12** with the vertically expanding plate **300** disposed at or above the upper engagement surface **306** of the body portion **12**. In an embodiment, the vertically expanding plate **300** is positioned towards the second end **26** of the body portion **12**. While not illustrated, the threaded bolt **318** extends through the upper engagement surface **306** and couples the vertically expanding plate **300** and the gear **302**. An actuator screw **324** extends through the first end **24** of the body portion **12** to engage the gear **302**. [Is this correct? The engagement is not shown on FIG. **23**.]

[0082] The expandable fusion device **10** of FIGS. **21-23** can be inserted in the intervertebral space in a manner similar to that the previously described with respect to FIGS. **1-6**. FIG. **24** illustrates the expandable fusion device **10** of FIG. **23**

between adjacent vertebral bodies **3**, **4** in an unexpanded position. After insertion, the expandable fusion device **10** of FIGS. **21-23** can be expanded into the expanded position. As previously mentioned, a portion of the fusion device shown on FIGS. **21-23** expands vertically in at least one direction. To partially expand the fusion device **10**, the gear **302** can be rotated in a first direction. An instrument **326** having a gear **328** disposed on a distal end **330** of the instrument may be used to rotate the gear **302**, as best seen on FIG. **22**. In another embodiment, an instrument (not illustrated) may be used to rotate actuation member **324** in a first direction. As discussed above, the actuation member **324** is engaged with gear **302**; thus, as the actuation member **324** is rotated in first direction, the gear **302** rotated in a first direction. The embodiment with the actuation member **324** is best seen in FIG. **23**. As the gear **302** rotates, the threaded bolt **318** extends outward from the gear **302**, thus extending the laterally expanding plate **300** outward from the body portion **12**. FIG. **25** illustrates the expandable fusion device **10** of FIG. **23** in an expanded position.

[0083] After expansion, the expandable fusion device **10** can be contracted back to the unexpanded position. The unexpanded position of the fusion device **10** is best seen in FIG. **24**. To contract the fusion device **10**, the gear **302** is rotated in a second direction that is opposite the first direction. The instrument **326** with the gear **328** may be used to rotate the gear **302**. Alternatively, an instrument may be used to rotate the actuation member **324** to turn the gear **302** in the second direction. As the gear **302** rotates in the second direction, the threaded bolt **318** retracts pulling the laterally expanding plate **300** inward into the unexpanded position.

[0084] Although the preceding discussion only discussed having a single fusion device **10** in the intervertebral space, it is contemplated that more than one fusion device **10** can be inserted in the intervertebral space. It is further contemplated that each fusion device **10** does not have to be finally installed in the fully expanded state. Rather, depending on the location of the fusion device **10** in the intervertebral disc space, the height of the fusion device **10** may vary from unexpanded to fully expanded.

[0085] The invention being thus described, it will be obvious that the same may be varied in many ways. Such variations are not to be regarded as a departure from the spirit and scope of the invention, and all such modifications as would be obvious to one skilled in the art are intended to be included within the scope of the following claims.

What is claimed is:

1. An intervertebral implant comprising:

- a body portion comprising a first end, a second end, a first side portion connecting the first end and the second end, and a second side portion connecting the first end and the second end, the first end, second end, first side portion and second side portion defining a central opening;
- a first endplate comprising an upper side, a lower side, a ramped portion, the ramped portion extending from the lower side into the central opening, the ramped portion comprising a grooved portion;
- a second endplate comprising an upper side, a lower side, and a ramped portion, the ramped portion extending from the lower side into the central opening, the ramped portion comprising a grooved portion; and
- a translation member comprising an expansion portion, at least a portion of the translation member is received within the central opening, the expansion portion com-

prising first and second angled surfaces, the first angled surface engaging the grooved portion of the first endplate, the second angled surface engaging the grooved portion of the second endplate;

wherein movement of the translation member in a first direction causes the first and second endplates to move in a direction away from the body portion and the movement of the translation member in a second direction causes the first and second endplates to move in a direction towards the body portion, and

wherein the movement of the translation member in the first direction moves the first angled surface along the grooved portion of the first endplate and the second angled surface along the grooved portion of the second endplate.

2. The intervertebral implant of claim 1, the intervertebral implant further comprising:

- a first ramped insert coupled to the lower side of the first endplate, the first ramped insert comprising the ramped portion of the first endplate; and
- a second ramped insert coupled to the lower side of the second endplate, the second ramped insert comprising the ramped portion of the second endplate.

3. The intervertebral implant of claim 1, further comprising an actuation member connected to the translation member, the actuation member having a first end and a second end, the first end comprising an extension that is received with an opening in the expansion portion of the translation member.

4. The intervertebral implant of claim 3, wherein the rotational movement of the actuation member results in the generally linear movement of the translation member.

5. The intervertebral implant of claim 3, wherein the extension of the actuation member comprises a lip portion, wherein the lip portion is received in a locking mechanism that extends from the expansion portion of the translation member, the locking mechanism comprising a slot configured to receive the lip portion of the extension and a stop configured to engage the lip portion when the lip portion is in the slot.

6. The intervertebral implant of claim 3, further comprising a pin member for securing the actuation member in the translation member, the pin member disposed through a central bore of the actuation member and through a central bore of the actuation member.

7. The intervertebral implant of claim 1, wherein the first endplate comprises an opening extending from the upper surface through the lower surface, the opening being in fluid communication with the central opening, and wherein the upper surface of the first endplate comprises at least one texturing selected from the group consisting of teeth, ridges, friction increasing elements, keels, gripping projections, and purchasing projections.

8. The intervertebral implant of claim 1, wherein the first endplate comprise a threaded hole, the threaded hole penetrating through the upper surface of the first endplate, the threaded hole extending through the first endplate in an oblique fashion.

9. The intervertebral implant of claim 1, wherein the translation member comprises a second expansion portion.

10. The intervertebral implant of claim 9, wherein the second expansion portion comprises first and second angled surfaces, the first angled surface engaging a second grooved portion of the first endplate, the second angled surface engaging a second grooved portion of the second endplate.

11. The intervertebral implant of claim 1, wherein first angled surface of the expansion portion engages the grooved portion of the first endplate in a slotted fashion.

12. The intervertebral implant of claim 1, wherein the grooved portions of the first and second endplates extend in a generally oblique manner.

13. The intervertebral implant of claim 1, wherein the first and second sides of the body portion each comprise a recessed portion configured and dimensioned for receiving an insertion instrument.

14. The intervertebral implant of claim 1, wherein the first end of the body portion includes at least one angled surface.

15. The intervertebral implant of claim 1, the intervertebral implant further comprising:

first and second artificial endplates, the artificial endplates each have an upper surface and a lower surface, the upper surfaces of the artificial endplates comprise a spike to engage the adjacent vertebral bodies and the lower surfaces of the artificial endplates comprise complementary texturing or engagement features to engage with texturing or engagement features on the first and second endplates,

wherein the upper surfaces of the artificial endplates have a generally convex profile and the lower surfaces have a generally parallel profile to achieve lordosis.

16. A method of installing an intervertebral implant, the method comprising:

positioning the intervertebral implant between adjacent vertebrae, the intervertebral implant comprising a body portion with a first end and a second end, the first end being inserted first into the disc space followed by the second end;

rotating an actuation member of the intervertebral implant in a first direction, the rotation of the actuation member causing a translation member of the implant to move in a first direction, the translation member comprising an expansion portion, the expansion portion comprising a first angled surface and a second angled surface, the first angled surface abutting and pushing against a ramped surface on a first endplate of the intervertebral implant while engaging a grooved portion on the ramped surface of the first endplate, and the second angled surface abutting and pushing against a ramped surface on a second endplate of the intervertebral implant while engaging a grooved portion on the ramped surface of the second endplate, thereby causing the first and second endplates to move in a direction away from the body portion into an expanded position.

17. An intervertebral implant having an expanded and unexpanded configuration, the implant comprising:

a body portion comprising a first end having at least one angled surface, a second end comprising an opening, a first side portion connecting the first end and the second end, and a second side portion connecting the first end and the second end, the first end, second end, first side portion and second side portion defining a central opening;

a first endplate comprising an upper side and a lower side; a first ramped insert coupled to the lower side of the first endplate, the first ramped insert comprising a first ramped portion and a second ramped portion, the first ramped portion comprise an obliquely oriented grooved portion, the second ramped portion comprising an obliquely oriented grooved portion;

a second endplate comprising an upper side and a lower side;

a second ramped insert coupled to the lower side of the first endplate, the second ramped insert comprising a first ramped portion and a second ramped portion, the first and second ramped portions each comprising an obliquely oriented grooved portion;

a translation member comprising a first expansion portion, a second expansion portion, and a locking mechanism, at least a portion of the translation member is received within the central opening,

wherein the first and second expansion portions each comprise first and second angled surfaces,

wherein the locking mechanism extends from the first expansion portion and comprises a slot and a stop;

an actuation member connected to the translation member, the actuation member comprising a first end and a second end, the first end comprising an extension that is received with the opening in the first expansion portion, the extension comprising a lip portion that is received in the slot in the locking mechanism and engages the stop of the lock mechanism;

wherein movement of the translation member in a first direction causes the first and second endplates to move in a direction away from the body portion and the movement of the translation member in a second direction causes the first and second endplates to move in a direction towards the body portion, and

wherein the first angled surface of the first expansion portion engages the first grooved portion of the first ramped portion in a dovetail fashion.

18. An intervertebral implant comprising:

a body portion comprising a first end, a second end, a first side portion connecting the first end and the second end, and a second side portion connecting the first end and the second end, the first end, second end, first side portion and second side portion defining a central opening;

a first endplate comprising an upper surface for engaging a first adjacent vertebral body, a lower surface for engaging a second adjacent vertebral body, an inner surface facing the body portion;

a second endplate comprising an upper surface for engaging a first adjacent vertebral body, a lower surface for engaging a second adjacent vertebral body, an inner surface facing the body portion;

a translation member, at least a portion of the translation member is received within the central opening,

wherein movement of the translation member in a first direction causes the first and second endplates to move in a lateral direction away from the body portion and the movement of the translation member in a second direction causes the first and second endplates to move in a lateral direction towards the body portion.

19. An intervertebral implant comprising:

a body portion comprising a first end, a second end, a first side portion connecting the first end and the second end, a second side portion connecting the first end and the second end, a top side portion connecting the first end and the second end, and a bottom side portion connecting the first end and the second end,

wherein the first end, second end, first side portion, second side portion, top side portion, and bottom side portion define a central opening,

wherein the top side portion and the first side portion define a first gap,
 wherein the top side portion and the second side portion define a second gap,
 wherein the bottom side portion and the first side portion define a third gap, and
 wherein the bottom side portion and the second side portion define a fourth gap;
 a first endplate comprising an upper surface and a lower surface, the lower surface at least partially disposed in the first gap;
 a second endplate comprising an upper surface and a lower surface, the lower surface at least partially disposed in the second gap;
 a third endplate comprising an upper surface and a lower surface, the lower surface at least partially disposed in the third gap;
 a fourth endplate comprising an upper surface and a lower surface, the lower surface at least partially disposed in the fourth gap;
 a translation member comprising an expansion portion, at least a portion of the translation member is received within the central opening, the expansion portion comprising first and second angled surfaces, the first and

second angled surfaces each comprising a first end and a second end, the second end being wider than the first end,
 wherein the first angled surface engages the first endplate and the second endplate, and
 wherein the second angled surface engages the third endplate and the fourth endplate,
 wherein movement of the translation member in a first direction causes the first and second endplates to move away from the body portion in an oblique fashion and the movement of the translation member in a second direction causes the first and second endplates to move in a direction towards the body portion in an oblique fashion.
20. An intervertebral implant comprising:
 a body portion comprising a first end, a second end, an upper engagement surface extending from the first end toward the second end, and a lower engagement surface extending between the first end and the second end;
 a gear coupled to the body portion; and
 a vertically expanding plate coupled to the gear;
 wherein rotation of the gear in a first direction causes the vertically expanding plate to move in a direction away from the body portion and the movement of the gear in a second direction causes the vertically expanding plate to move in a direction towards the body portion.

* * * * *