US011036371B2

(12) **United States Patent**
Keel et al.

(10) **Patent No.: US 11,036,371 B2**
(45) **Date of Patent: *Jun. 15, 2021**

(54) **METHODS AND APPARATUS FOR MANAGING AND EXCHANGING INFORMATION USING INFORMATION OBJECTS**

(71) Applicants: **Paul Erich Keel**, Cambridge, MA (US); **Jeffrey Huang**, Lausanne (CH)

(72) Inventors: **Paul Erich Keel**, Cambridge, MA (US); **Jeffrey Huang**, Lausanne (CH)

(73) Assignee: **Paul Erich Keel**, Cambridge, MA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **16/653,349**

(22) Filed: **Oct. 15, 2019**

(65) **Prior Publication Data**

US 2020/0117343 A1 Apr. 16, 2020

Related U.S. Application Data

(63) Continuation of application No. 15/806,912, filed on Nov. 8, 2017, now Pat. No. 10,664,141, which is a (Continued)

(51) **Int. Cl.**
G06F 3/0484 (2013.01)
G06F 16/22 (2019.01)
(Continued)

(52) **U.S. Cl.**
CPC ***G06F 3/04842*** (2013.01); ***G06F 3/0482*** (2013.01); ***G06F 3/04817*** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC G06F 3/04842; G06F 3/04817; G06F 3/0482; G06F 16/22; G06F 16/258;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,008,853 A 4/1991 Bly et al.
5,220,657 A 6/1993 Bly et al.
(Continued)

FOREIGN PATENT DOCUMENTS

JP 2004070614 A 3/2004
WO 0135269 A2 5/2001
WO 0165346 A2 9/2001

OTHER PUBLICATIONS


Keller R. et al. A bookmarking service for organizing and sharing URLs. Computer Networks and ISDN Systems 29 (1997) 1103-1114, 1.
(Continued)

Primary Examiner — Tadesse Hailu
(74) *Attorney, Agent, or Firm* — Sunstein LLP

(57) **ABSTRACT**

A computer-implemented method for interacting with at least one data item obtained from at least one source utilizes computer processes responsive to a user selection of the at least one data item and include causing configuring of each of the data items into a distinct information object by extracting, from each data item, extracted data including a picture, a heading, and a link to the data item, and causing storing of data corresponding to each of the information objects in a database system. The processes further include displaying a representation of each of at least two of the information objects in the database system, the representation being in a uniform format, wherein the format includes a card, and, within the card, in uniform locations thereof, the picture, the heading, a set of indicators, and a set of graphically accessible functions.

29 Claims, 14 Drawing Sheets



Related U.S. Application Data

continuation of application No. 15/243,497, filed on Aug. 22, 2016, now Pat. No. 9,817,562, which is a continuation of application No. 14/664,178, filed on Mar. 20, 2015, now Pat. No. 9,524,090, which is a continuation of application No. 13/925,031, filed on Jun. 24, 2013, now abandoned, which is a continuation of application No. 12/563,416, filed on Sep. 21, 2009, now Pat. No. 8,499,248, which is a continuation-in-part of application No. 11/118,301, filed on Apr. 29, 2005, now Pat. No. 7,640,511.

(60) Provisional application No. 61/116,747, filed on Nov. 21, 2008, provisional application No. 60/566,723, filed on Apr. 29, 2004.

(51) **Int. Cl.**

G06F 16/29	(2019.01)
G06F 16/25	(2019.01)
G06F 16/9535	(2019.01)
G06F 16/9537	(2019.01)
G06Q 10/10	(2012.01)
G06F 3/0481	(2013.01)
G06F 3/0482	(2013.01)
H04L 12/58	(2006.01)
H04L 29/08	(2006.01)

(52) **U.S. Cl.**

CPC ***G06F 16/22*** (2019.01); ***G06F 16/258*** (2019.01); ***G06F 16/29*** (2019.01); ***G06F 16/9535*** (2019.01); ***G06F 16/9537*** (2019.01); ***G06Q 10/10*** (2013.01); ***H04L 51/046*** (2013.01); ***H04L 67/10*** (2013.01); *Y10S 707/99933* (2013.01); *Y10S 707/99943* (2013.01)

(58) **Field of Classification Search**

CPC .. G06F 16/9537; G06F 16/29; G06F 16/9535; G06Q 10/10; H04L 51/046; H04L 67/10; Y10S 707/99933; Y10S 707/99943

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,732,229	A	3/1998	Dickinson	
6,049,806	A	4/2000	Crecine	
6,092,067	A	7/2000	Girling et al.	
6,119,147	A	9/2000	Toomey et al.	
6,230,185	B1	5/2001	Salas et al.	
6,266,649	B1	7/2001	Linden et al.	
6,289,362	B1	9/2001	Van Der Meer	
6,327,590	B1	12/2001	Chidlovskii et al.	
6,415,316	B1	7/2002	Van Der Meer	
6,597,377	B1	7/2003	MacPhail	
6,724,403	B1	4/2004	Santoro et al.	
6,768,999	B2	7/2004	Prager et al.	
6,781,920	B2	8/2004	Bates et al.	
6,829,619	B1	12/2004	Wakamatsu et al.	
6,912,505	B2	6/2005	Linden et al.	
6,931,591	B1	8/2005	Brown et al.	
6,973,456	B1	12/2005	Elgart	
7,028,264	B2	4/2006	Santoro et al.	
7,062,242	B2	6/2006	Dajer et al.	
7,113,917	B2	9/2006	Jacobi et al.	
7,185,290	B2	2/2007	Cadiz et al.	
7,310,612	B2	12/2007	McQueen, III et al.	
7,469,376	B2 *	12/2008	Chia	G06F 40/186 715/209
7,478,054	B1	1/2009	Adams et al.	
7,478,078	B2	1/2009	Lunt et al.	
7,543,237	B2	6/2009	Kontny et al.	
7,607,095	B2	10/2009	Marcos et al.	
7,640,511	B1	12/2009	Keel et al.	
7,681,112	B1	3/2010	Francis	
7,698,346	B2	4/2010	Henderson	
7,756,970	B2	7/2010	Ebert et al.	
7,765,490	B2	7/2010	Lai et al.	
7,904,323	B2	3/2011	Wynn et al.	
7,921,368	B2	4/2011	Moody et al.	
7,941,444	B2	5/2011	Cragun et al.	
8,042,063	B1	10/2011	Lin-Hendel	
8,078,615	B2	12/2011	Smith et al.	
8,249,885	B2	8/2012	Berkowitz et al.	
8,307,046	B2	11/2012	Ortiz et al.	
8,392,834	B2	3/2013	Obrador	
8,499,248	B1	7/2013	Keel et al.	
8,620,828	B1	12/2013	Harrison, Jr.	
8,635,531	B2 *	1/2014	Graham	G06F 16/40 715/716
8,743,148	B2	6/2014	Gegner et al.	
9,344,466	B1	5/2016	Abuzalaf et al.	
9,524,090	B1	12/2016	Keel et al.	
9,817,562	B2	11/2017	Keel et al.	
2001/0003214	A1	6/2001	Shastri et al.	
2002/0016725	A1	2/2002	Eichstaedt et al.	
2002/0054158	A1 *	5/2002	Asami	G06T 11/206 715/838
2002/0073059	A1 *	6/2002	Foster	G06F 16/25
2002/0080180	A1	6/2002	Mander et al.	
2002/0105541	A1	8/2002	Endou et al.	
2002/0113803	A1	8/2002	Samra et al.	
2002/0143877	A1	10/2002	Hackbarth et al.	
2002/0147661	A1	10/2002	Hatakama et al.	
2002/0169737	A1	11/2002	Armstrong et al.	
2002/0186257	A1	12/2002	Cadiz et al.	
2003/0009493	A1	1/2003	Parker et al.	
2003/0028595	A1	2/2003	Vogt et al.	
2003/0030678	A1	2/2003	Rosenholtz et al.	
2003/0074368	A1 *	4/2003	Schuetze	G06F 16/355
2003/0135565	A1	7/2003	Estrada	
2003/0158855	A1	8/2003	Farnham et al.	
2003/0158893	A1	8/2003	Komatsu et al.	
2003/0164856	A1	9/2003	Prager et al.	
2003/0169303	A1 *	9/2003	Islam	G06F 3/04817 715/836
2003/0208397	A1	11/2003	VanDusen	
2003/0217056	A1	11/2003	Allen et al.	
2004/0003097	A1	1/2004	Willis et al.	
2004/0049541	A1	3/2004	Swahn	
2004/0054428	A1	3/2004	Sheha et al.	
2004/0083274	A1	4/2004	Katiyar et al.	
2004/0139400	A1 *	7/2004	Allam	G06F 40/106 715/201
2004/0153445	A1	8/2004	Horvitz et al.	
2004/0177319	A1	9/2004	Horn	
2004/0193673	A1	9/2004	Samji et al.	
2004/0201609	A1	10/2004	Obrador	
2004/0205514	A1	10/2004	Sommerer et al.	
2004/0226048	A1 *	11/2004	Alpert	H04N 21/25891 725/109
2004/0261013	A1	12/2004	Wynn et al.	
2004/0267700	A1	12/2004	Dumais et al.	
2005/0080807	A1	4/2005	Beilinson et al.	
2005/0154639	A1	7/2005	Zetmeir	
2005/0165880	A1	7/2005	Moody et al.	
2005/0283395	A1	12/2005	Lesandrini et al.	
2007/0094099	A1	4/2007	Hodson et al.	
2008/0022220	A1	1/2008	Cheah	
2008/0126952	A1	5/2008	Shohfi et al.	
2011/0138289	A1	6/2011	Koren	
2012/0296974	A1	11/2012	Tabe	
2013/0073425	A1	3/2013	Hellal et al.	
2014/0222927	A1	8/2014	Glazer et al.	

OTHER PUBLICATIONS

Rounding M. Informal Awareness and Causal Interaction with the Notification Colleague. Master Thesis. Dept. of Computer Science,

(56) **References Cited**

OTHER PUBLICATIONS

University of Calgary, Alberta, Canada. Apr. 19, 2004, 2.
Greenberg S. et al. The Notification Collage: Posting Information to Public and Personal Displays. Yellow Series Report 2000-667-19, Dept. of Computer Science, University of Calgary, Alberta, Canada. Sep. 14, 2000, 2.
itList.com, Apr. 1996, May 29, 2004, 3.
Backflip.com, 1999, Jun. 23, 2004, 4.
Clickmarks.com, 1999, Oct. 12, 1999, 5.
HotLinks.com, 2000, Feb. 11, 2002, 6.
del.icio.us, 2003, Dec. 20, 2005, 7.
SPURL.net, 2004, Oct. 21, 2004, 8.
StumbleUpon.com, 2001 (estimated), Jun. 16, 2004, 9.
Flickr.com, Feb. 2004, Jun. 7, 2004, 10.
TheFacebook.com, Feb. 2004, 2005 (estimated), 11.
LiveJournal.com, 1999, Dec. 15, 2003, 12.
Multiply.com, Mar. 2004 (estimated), Jun. 19, 2004, 13.
Friendster.com, 2002, Sep. 2003 (estimated), 14.
MySpace.com, Aug. 2003, Apr. 4 2005 (estimated), 15.
LinkedIn.com, May 2003, 2004 (estimated), 16.
Blogger.com, 1999, Mar. 31, 2004, 17.
Eastgate Tinderbox, 2002, Jun. 6, 2004, 18.
Hi5.com, 2003, (unknown), 19.
Xanga.com, 1998, Jan. 21, 2006 (estimated), 20.
AsianAve.com, 1997, 2007 (estimated), 21.
MiGente.com, 2000, Jun. 3, 2004, 22.
vBulletin, 2000, Jun. 10, 2004, 23.
phpBB, 2000, Feb. 24, 2004 (estimated), 24.
Orkut.com, Jan. 2004, Nov. 2004 (estimated), 25.
Photobucket.com, May 3, 2003, Aug. 13, 2004, 26.
ImageShack.us, Nov. 12, 2003, Aug. 3, 2004, 27.
SixDegrees.com, 1997, Dec. 6, 2000, 28.
Reblog.org, 2003, Mar. 27, 2004, 29.
WebShotes.com, 1995, Jul. 3, 2004, 30.
Fotopic.com, 1999, Jun. 6, 2004, 31.
SanpFish.com, 2000, Jun. 3, 2004, 32.
SmugMug.com, 2002, Jul. 12, 2004, 33.
Amazon.com, 1994, Jul. 2, 2004, 34.
DeviantArt.com, 2002, Jun. 14, 2004, 35.
Fotki.com, 1998, Jun. 9, 2004, 36.
ShutterFly.com, 1999, Jun. 16, 2004, 37.
Winston et al., *EWall: Electronic Card Wall*, ONR CKM Workshop, Jan. 2004, 20 pages, Publication date unknown.
Winston et al., *EWall: Electronic Card Wall*, ONR CKM Workshop, Maryland, Jan. 2003, 25 pages, Publication date unknown.
Winston et al., *EWall: Electronic Card Wall*, ONR TC3 Workshop, San Diego, Jan. 2002, 26 pages, Publication date unknown.
Winston et al., *EWall: Electronic Card Wall*, ONR TC3 Workshop, San Diego, Nov. 2000, 8 pages, Not publicly released.
Fleming, *DCODE: Decision Making Constructs in a Distributed Environment*, ONR CKM Workshop, Maryland, Jan. 2003, 60 pages, Publication date unknown.
Fleming, *DCODE: Decision Making Constructs in a Distributed Environment*, ONR CKM Workshop, San Diego, Jan. 2004, 71 pages, Publication date unknown.
Fleming, *Information Exchange and Display in Asynchronous C2 Group Decision Making*, Jun. 2003, 38 pages, Publication date unknown.
Freeman et al., *Collaborative Critical Thinking*, ONR CKM Workshop, Maryland, Jan. 2003, 39 pages, Publication date unknown.
Warner et al., *CASC: The Process of Achieving Collaborative Knowledge in Asynchronous Collaboration*, ONR CKM Workshop, San Diego, Jan. 2004, 53 pages, Publication date unknown.
Bordetsky, *NPS GIGA Lab Testbed for CKM Projects*, ONR CKM Workshop, San Diego, Jan. 2004, 47 pages, Publication date unknown.
Anon., *EWall: Electronic Card Wall, Abstract*, in a screen capture taken from www.archive.org for date Jun. 6, 2001 of web page at ewall.mit.edu/abstract/index.html, Publication date unknown.
Winston, et al., *EWall: Computational Support for Decision Making in Collaborative Environments*, in a screen capture taken from www.archive.org for date Aug. 2, 2003 of web page at www.ai.mit.edu/research/ abstracts/ abstracts2002/user-interfaces/32winston.pdf, Publication date unknown.
Anon., *News View Examples*, in screen captures taken from www.archive.org for (a) date Apr. 19, 2001 of web page at destech.mit.edu/keel/test/news/share.pl and (b) date Apr. 7, 2003 of web page at ia.eversitas.com and (c) date Jun. 17, 2002 of web page at destech.mit.edu:80/phw/news/news.html.
Prante et al., *Developing CSCW Tools for Idea Finding—Empirical Results and Implications for Design*, Proceedings of the ACM Conference on Computer Supported Cooperative Work, New Orleans, Louisiana, ACM Press, Nov. 16-20, 2002, pp. 106-115.
Keel, *Declaration of Paul Erich Keel, Ph.D.*, signed and dated May 1, 2017, 5 pages.
Manning et al.—"Text Information Retrieval, Mining, and Exploitation", CS276B, Winter, 2003, 15 pages.
Fish et al.—"Quilt: a collaborative tool for cooperative writing", ACM, 1988, pp. 30-37.
Lai et al. "Object Lens: A 'Spreadsheet' for Cooperative Work", ACM Transactions on Office Information Services, vol. 6, No. 4, pp. 332-353, Oct. 1988.
Esenther—"Instant Co-Browsing Lightweight Real-Time Collaborative Web Browsing", Mitsubishi Electric Research Laboratories Inc., May 2002, 13 pages.

* cited by examiner



132-1
320
320
320
320
NEWS VIEW
DATABASE VIEW
EXCHANGE VIEW
305
310
315
320
320
300
WORKSPACE VIEW
130
110-1
COMPUTER SYSTEM
(E.G., USER STATION)
114
I/O INTERFACE
111
112
MEMORY
150-1
RELATION MAN.
APPLICATION
178-1 VIEW MAN.
180-1 CONN. MAN.
182-1 FILE MAN.
113
PROCESSOR
150-2
RELATION MAN.
PROCESS
178-2 VIEW MAN.
180-2 CONN. MAN.
182-2 FILE MAN.
115
COMM. INTERFACE
116
108-1
125
160
155
170
132-2
132-N
108-2
108-N
101
NETWORK
110-2
110-N
100

FIG. 1



320
ICON AREA
Pictures / Icons
Drawings
Text
BG Color
321
DATE / TIME BAR
324
AUTHOR BAR
325
HEADING BAR
326
6
2
Jan-02-2004 19:47 EST
Antonius Plus
MIT Mezzanine Area
322
INFORMATION BAR
Comment (#)
Ownership
Hyperlink
Attachement
Priority
Vote (#)
Log (#)
Permission
Notification
Location
HYPERLINKS
Internet Sites
Computer Files
Direcories
Executables
Database Items
Workspaces
ATTACHEMENTS
Computer Files
Executables

FIG. 2



360
Information Object (IO)
362
News View
(IOs displayed as rows of cards)
364
Workspace View
(IOs displayed as cards)
366
Map View
(IOs displayed as symbols)
368
Project View
(IOs displayed as time-lines)
370
Graph View
(IOs displayed as graphs)
372
List View
(IOs displayed as line-items)
... other Views

FIG. 3




FIG. 4B




FIG. 4A


Shared ETM Views
Instant Messaging System
Email
Shared File Systems
ETM Database
ETM Agent System

FIG. 5A



510
GET
SHARED
PUT
GET
PUT
GET
514
VISIBLE
512
PRIVATE
GET

FIG. 5B



610

FIG. 6A



620
Control Panels
630
Information Views
632a
632n
640
IO Editors
640a
640n

FIG. 6B




FIG. 6C

1. Buddy List
2. Object (Discussion Subject)
3. Message Indicator (Counter)
4. Object / Discussion Heading
5. Collaborative Ratings
6. Shared Files (List or Thumbnails)
7. Threaded Discussion
8. Participants
9. Meta-data and shared applications



700
710
712
714
718
720
722
724
726
728
730
Click to send/receive an IM message about a View (chat room)
Click to send/receive an IM message about an ID (chat room)
Click to allow a database to collect information from this window
Click to disallow a database to collect information from this window
Available resources on a database (cards, visualizations, statistics, etc.)
Send an ID to a user or a group of users
View of another user that is open to view/modify
Import/export IDs from/to
- IM systems
- Other User's Views
- Shared Views
- Email Tools
- Databases
- Agent Systems
Click to disallow a user to view this View
Click to allow a user to view/modify this View
Click to send/receive an IM message or ID to/from a user (chat)
Click to send an IM message or ID to a group of users

FIG. 7



800
Display
URL to a web site
Flash Executables
Movie Documents
Office Document
PDF Documents
Other Documents
Attachments
Updates
Remote RSS Files
Remote Objects
Remote Files

FIG. 8



900
Top Bar
902
Picture / Text
912
916
Functions
910
920
Heading
914
Collaboration
Modification Date / Time
2/14/08 9:35AM ET
Author / Source
New York Times
Reliability (all users, this user)
Rating / Vote
Importance / Priority
924
Value / Value Change
928
$18.95 +6.40%
Trade Bid
930
$102.05
$110.00
1d 09:12
Category
932
[News]
Time Frame (Schedule)
934
Text
Picture
PDF
Flash Executable
Office Document
No Reference
Hyperlink
Attachment
Workspace / NewsView
Card
Instant Messages
SMS
Forums
Twitter
Email
No Updates (Static, Unlocked)
Owner Controled (Dynamic)
RSS Stream (Dynamic)
No Connection
No Messages (IM, Forum, Graphics, Text)
Messages
New Messages
Not Shared
Shared
Recent Access
No Geographic Location
Geographic Location
recently updated
Dynamic, Locked, Updates
Static, Unlocked, No Updates

FIG. 9



1000
IO
IO
EWS
IO
RSS
News View
IO
RSS
IO
IO
IO
URL
IO
DOC
Workspace View
Filters

FIG. 10



1100
1110
PROVIDE THE INFORMATION OBJECT
1120
SHARE THE INFORMATION OBJECT AMONG A PLURALITY OF PARTICIPANTS
1130
ATTACH MULTI-MEDIA DATA TO THE INFORMATION OBJECT
1140
DISPLAY THE INFORMATION OBJECT IN ONE OF A PLURALITY OF VIEWS
1150
IN RESPONSE TO INTERACTION WITH ONE OF THE PLURALITY OF VIEWS BY ONE OF THE PARTICIPANTS, PROVIDE A COMMUNICATIONS PATH BETWEEN AT LEAST TWO OF THE PARTICIPANTS SHARING THE INFORMATION OBJECT

FIG. 11



1200
1110
PROVIDE THE INFORMATION OBJECT
1210
FILTER A WEB PAGE ASSOCIATED WITH A URL TO CREATE THE INFORMATION OBJECT BY AUTOMATICALLY EXTRACTING META-DATA INCLUDING AT LEAST ONE OF A HEADING, A PICTURE, AND LINK TO THE URL
1120
SHARE THE INFORMATION OBJECT AMONG A PLURALITY OF PARTICIPANTS
1220
TRANSFER THE INFORMATION OBJECT BETWEEN DIFFERENT INFORMATION VIEWS
1130
ATTACH MULTI-MEDIA DATA TO THE INFORMATION OBJECT
1230
LINK THE MULTI-MEDIA DATA TO THE INFORMATION OBJECT
1240
PROVIDE AN AUTOMATED PARTICIPANT, WHEREIN THE AUTOMATED PARTICIPANT INTERACTS WITH THE INFORMATION OBJECT
1242
LINK THE MULTI-MEDIA DATA TO THE INFORMATION OBJECT
1250
RETRIEVE INFORMATION BASED ON USER INTERACTION WITH THE INFORMATION OBJECT INCLUDING SPATIALLY ARRANGING THE INFORMATION OBJECT RELATIVE TO OTHER INFORMATION OBJECTS
1252
INTERACTION WITH THE AT LEAST ONE INFORMATION OBJECT INCLUDES ATTACHING AT LEAST ONE DOCUMENT TO THE INFORMATION OBJECT
To Step 1310 FIG. 13

FIG. 12



1300
1310
STORE A LINK TO AT LEAST ONE INFORMATION OBJECT TO HOST A CONVERSATION AMONG A GROUP OF PARTICIPANTS
THE INFORMATION OBJECT INCLUDES AT LEAST ONE LINK TO A DOCUMENT; A PLURALITY OF LINKS TO THE GROUP OF PARTICIPANTS; META-DATA RELATED TO THE CONVERSATION; AND A COMMUNICATION SYSTEM LINKING THE AT LEAST ONE INFORMATION OBJECT TO THE GROUP OF PARTICIPANTS
1320
PROVIDE A USER INTERFACE ON THE CLIENT SYSTEM
THE USER INTERFACE INCLUDE AN ICON REPRESENTING THE AT LEAST ONE INFORMATION OBJECT A CONTACT LIST; A LIST OF PARTICIPANTS LINKED TO THE AT LEAST ONE INFORMATION OBJECT; AND AN INFORMATION VIEW TO VISUALIZE THE AT LEAST ON INFORMATION OBJECT
1330
INFORMATION VIEW INCLUDES A NEWS VIEW HAVING AN ADAPTOR FOR RECEIVING NEWS FEEDS AND THE USER INTERFACE CHRONOLOGICALLY ORGANIZES INFORMATION CHRONOLOGICALLY IN A SUBJECT-TIME MATRIX
USER INTERFACE INCLUDES A ZOOMABLE, GRAPHICAL TIMELINE INCLUDING AUTOMATIC COMPRESSION OF THE SUBJECT-TIME MATRIX
NEWS FEED IS A SYNDICATION FEED

FIG. 13

METHODS AND APPARATUS FOR MANAGING AND EXCHANGING INFORMATION USING INFORMATION OBJECTS

RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 15/806,912, filed Nov. 8, 2017, which is a continuation of U.S. patent application Ser. No. 15/243,497, filed Aug. 22, 2016, now U.S. Pat. No. 9,817,562, which is a continuation of application Ser. No. 14/664,178, filed Mar. 20, 2015, now U.S. Pat. No. 9,524,090, which is a continuation of U.S. patent application Ser. No. 13/925,031, filed Jun. 24, 2013, now abandoned, which is a continuation of U.S. patent application Ser. No. 12/563,416, filed Sep. 21, 2009 (now U.S. Pat. No. 8,499,248, issued Jul. 30, 2013), entitled "METHODS AND APPARATUS FOR MANAGING AND EXCHANGING INFORMATION USING INFORMATION OBJECTS," which (i) claims the benefit of U.S. provisional application Ser. No. 61/116,747, filed Nov. 21, 2008, entitled "Information Objects (IOs) and Information Views (IVs)", and (ii) is a continuation in part of U.S. patent application Ser. No. 11/118,301, filed Apr. 29, 2005 (now U.S. Pat. No. 7,640,511, issued Dec. 29, 2009), entitled "METHODS AND APPARATUS FOR MANAGING AND INFERRING RELATIONSHIPS FROM INFORMATION," which claims the benefit of U.S. provisional application Ser. No. 60/566,723, filed Apr. 29, 2004, entitled "METHODS AND APPARATUS FOR MANAGING AND INFERRING RELATIONSHIPS FROM INFORMATION". All of these related applications are hereby incorporated herein by reference in their entirety.

STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH

This invention was made with Government support under Grant and/or Contract No. 'N00014-02-1-0132 and/or N00014-04-1-0569 and/or N00014-08-C-0206' awarded by the Office of Naval Research. The Government has certain rights in the invention.

BACKGROUND

Modern information processing systems allow users to collect and process large amounts of information. As an example, a typical computer system such as a personal computer includes an operating system that executes within the computer system to provide a graphical user interface to users of that computer system. A conventional graphical user interface typically includes a number of information objects such as graphical icons that represent information of relevance or importance to the user. The user accesses data and controls functionality of the computer system by selecting and operating such icons. By way of example, software applications such as word processors, graphical editing tools, web browsers and many others often provide graphical user interfaces that include a number of icons that have visual meaning to the user of the computer system. Typically, a software application renders icons to allow the user to invoke specific functionality or commands of that application and/or to allow the user to organize and access data. Many software applications use icons to represent data or files that the user can access by selecting (e.g., clicking) the icon representing the data. As an example, if a user selects an icon that represents a software application installed within the computer, the computer will begin execution of that application. Other icons on a graphical user interface can represent folders or files maintained by the operating system within a file system.

Many conventional software applications allow a user to develop or collect various portions of information or content for storage and future access. As an example, a word processor or other editing tool allows the user to create and edit documents. As another example, a web browser allows a user to navigate web pages provided by servers on remote computer networks such as the Internet to reference information on a variety of subjects. A conventional computer system allows a user to store information referenced or created by such applications as a set of documents or files that can be retrieved by the user at a later time.

Most conventional operating systems and many software applications also provide a way for a user to arrange a file system of the computer in order to organize documents and files in a manner that makes sense to the user. Computer operating systems typically organize file systems in a hierarchical manner allowing the user to create folders or directories with user-specified names. The user can store files within the folders in a manner that makes sense to that user. A file system is thus one of the most popular ways for users to organize and manage data and information of interest to those users.

Another mechanism that conventional applications and operating systems provide to allow users to organize and manage information of interest to that user is the ability to allow a user to spatially arrange information objects such as graphical icons in a way that makes intuitive sense to the user. As an example, on a conventional "desktop" work area provided by many operating systems, a user can place or position icons representing files, documents, applications, email messages, appointments or the like in any manner and at any position that the user may choose. In particular, such conventional applications allow the user to graphically maneuver the icons into position in relation to one another in a manner that makes sense to that user. Different users often organize icons on their desktop in different ways.

Information availability and accessibility is continuously increasing. The problem is that information commonly exists in different formats, resides in different locations, is dynamically changing, and is used and modified by different people. This makes it difficult for users to effectively monitor, analyze and exchange information.

SUMMARY

Conventional mechanisms and techniques that allow a user to visually organize, collect and manage information objects that represent various portions of information suffer from a variety of deficiencies. In particular, conventional computer-based applications such as operating system desktops and software application graphical user interfaces allow a user to collect and store numerous portions of content and information that are of interest to the user and allow a user to represent that information graphically (e.g. via icons), but do little to analyze relations that may exist between the icons and/or between the stored portions of content or data.

In particular, conventional information processing systems such as those noted above allow a user to organize and arrange various portions of data or other information as icons in a graphical user interface in a manner that makes sense to the user, but such systems do not promote conversations and collaboration among users.

Another deficiency with conventional information processing systems is that information is represented in different formats and, depending on the format, is stored in different locations. For example, conventional browsers store hyperlinks to web sites as bookmarks, whereas emails are located in mailboxes in mail handlers, files are stored in computer directories, and notes may be stored in files, and so forth. The proposed information object mechanism disclosed herein, referred to in some embodiments as IO*s*, solve this deficiency by introducing a standardized information format that represents a piece of information in an abstract way and links to an original piece of information and that has a standardized look thus allowing users to focus on and compare the information content and context rather than be distracted by the information format and location.

As an example of problems with conventional data processing systems, a user using a conventional content development application may spend large amounts of time collecting portions of content such as graphics, text, news stories, web pages, email messages, or other such information sources for collaborative production of a large content-based research project. Many users may be involved in this process. As each user collects portions of information using conventional information management systems, the users store and organize their respective portions of information within the computer file system. Each user may create icons on his or her desktop or other work areas that represent the respective portions of collected information. Each user might group icons for related pieces of information together in a list, within close proximity to each other, or in file directories. In conventional systems however, it is up to the user to identify what other portions of information might be of interest to the user that the user has not already identified and collected.

As an example, if the collaborative production being developed by the users is a project related to current events, each user may collect articles and stories related to that current event. Using conventional systems, it is up to each user to research and discover stories or other content related to that current event that might be available from a variety of different information sources. While conventional collaboration systems might provide a common repository for such collected information contributed by each user, there is little or no ordering to this information, other than an order specified by the users who place the content into the shared repository such as a file system or database. Each user must frequently communicate with other users in a highly manual manner (e.g. via a telephone call, email or other mechanism) to identify content that other users may have discovered and collected that might be of relevance to the production under development.

Such conventional information management systems do not automatically and dynamically analyze relations between user placed icons that represent the various pieces of available information in order to assist users in identifying other portions of content that many of interest to those users. More specifically, conventional systems do not analyze specific spatial relations, collaborative context relations, chronological context relations, and the like between information sources associated with icons arranged by a user to determine other portions of information, such as other portions of content collected by other users, that may be of relevance or interest to the user providing a specific spatial arrangement of his or her icons. As a result, conventional information management systems limit a user's knowledge of other available content and information to which that user may have interest. In particular, such systems limit available content to that content that a user can discover on their own.

As an example, using a conventional information discovery processes such as web searching, a user can quickly become overwhelmed with search results that are irrelevant to the information they are seeking. While some conventional web sites may attempt to suggest references to web pages that are similar in nature to those discovered when providing a particular search term, such additional references are simply provided based on frequently performed searches of other users and do not take into account current information already collected by the user performing the original search. Thus a conventional browser is not made aware that a user already has collected certain related pieces of information and has organized them in a spatially related manner.

In contrast, embodiments of the invention are based in part on the observations that conventional information collection management systems provide a significant cognitive burden on users caused by the increasing availability of information, the requirement for users to actively initiate a search for relevant information, the requirement for evaluation of the quality and feasibility of information, the need to collaborate remotely and asynchronously, as well as the necessity to dynamically adapt to changing circumstances. Modern information processing systems do not provide an automated ability to organize and identify information sources that come in many different formats. For example, information may be received in the form of a phone call, an email, an instant message, a computer file, a web site, a database item, a verbal comment, a radio transmission, a newspaper, a television spot, a magazine, or a security camera. The various formats often prevent the easy and efficient collection, organization, and comparison of information by conventional information processing systems.

Embodiments of the invention incorporate advanced graphical user interfaces and functions to address the shortcomings in conventional systems. These embodiments include Information Objects (IOs) and Information Views (IVs). IOs that are data files that can include other data files (such as documents, hyperlinks, and executables) as well as meta-data (such as ratings, discussion logs, and visualization parameters). IVs are computer windows for the visualization of IOs. IOs are rendered differently on different IVs allowing users to manage information in a customized format and in environments suited to particular tasks and circumstances. In certain embodiments the IO consolidates data, meta-data and communication features. For example, the IO can be an agenda item, a discussion, a hosted conversation, a topic, etc. Accordingly, the user can efficiently view and organize multiple IOs that represent different topics and that engage different groups of participants.

Advantageously IOs provide a means for users to package and visualize (static and dynamic) information in a standardized format. IOs can be viewed and modified differently on different IVs. IOs can be copied between the IVs of the same or different users. Copies of IOs remain synchronized if displayed on different IVs. IOs are associated with functions that enhance the collaborative use of information, for example, an object-based communication system that allows users to communicate through IOs and IVs.

Other benefits of Information Objects and Views include the ability to: consolidate task relevant information (e.g. from shared IVs to a private IVs);

display information in a custom and familiar format (e.g., in a wide variety of possible custom IVs);

maintain a standardized data format for different data visualization and management tools; and

easily move data between different data visualization and management tools; and easily exchange information among remotely distributed participants in a hosted conversation.

Using techniques disclosed herein, it is possible to create IOs transfer IOs between the same or different types of IVs, add additional IVs and additional functions for IOs, as well as a selection of IO components, IO functions on IVs. An electronic wall (EWall) embodiment provides one example for the visualization of IOs on an information view (IV) in which an IO can present itself as a EWall IO on a EWall Workspace View. A graphical user interface is provided for the management of multiple IVs, as well as new functions for the exchange of IOs and the collaborative use of IVs.

Embodiments of the invention as disclosed herein provide mechanisms and techniques for providing the IO, sharing the IO among a plurality of participants, attaching multimedia data to the IO. The technique further includes displaying the IO in one of a plurality of views and in response to interaction with one of the plurality of views by one of the participants, communicating with at least one different one of the participants sharing the IO.

The system disclosed herein provides a computational environment for the support of individual and collaborative decision-making and greatly enhances the quality and the speed of individual and collaborative brainstorming, problem-solving, information collecting and decision-making processes. More specifically, the system for providing hosted conversation among a group of participants disclosed herein includes a processor, a memory unit that stores instructions associated with an application executed by the processor, and an interconnect coupling the processor and the memory unit, enabling the computer system to execute the application and perform operations of: storing a link to at least one information object, the at least one information object, the information object includes at least one link to a document, a plurality of links to the group of participants, meta-data related to the conversation, and a communication system linking the at least one information object to the group of participants. The system further provides a user interface on the client system comprising: an icon representing the at least one information object, a contact list, a list of participants linked to the at least one information object and an information view to visualize the at least on information object.

In one configuration, the IOs are sometimes represented as "cards" on a graphical user interface. IOs reference different types of information formats thus making it easier for users to directly compare and study information in different formats. As used herein the term "card," "IO" and "information object" are used interchangeably, and a card is one example configuration or representation of an information object. AN IO includes a graphic icon area to display text or a picture associated with an information source, as well as other information pertaining to such things as ownership of that IO, creation time of the IO, and attribute indicators that indicate a current state of the IO, and a hyperlink to its associated information source. In a simplest embodiment, an IO is just an icon that represents some information and information represented by IOs may be stored in different locations and in different formats. In one configuration, an IO is different from an ordinary icon because it comes with hidden functionality such as a built-in instant messaging system and the ability to drag and drop content onto the IO. It is noted that the: instant messaging system includes communication media such as Instant Messaging System, email and SMS messaging, text messaging and other forms of real-time communication between participants.

In one configuration, the system applies a spatial relation algorithm that discovers spatial relations between positional information of at least two IO records in an IO database that are associated with IOs displayed on the graphical user interface in the first set of IOs. The relations between IOs can be stored in a database and the system can use discovered relations to identify a second set of information objects based on the relation(s) between the first set of information objects/IOs. The second set of information objects in an IO configuration is a second set of IOs that might be of interest to the user based on the analysis of the IOs already on display in a Workspace View associated with that user. The system can output an identity of the second set of information objects by displaying the second set of IOs on the graphical user interface for viewing by the user. The second set may be displayed in a prioritized and relevant manner based on relations discovered concerning the first set of IOs.

In this manner, the system can use IOs to show the user other sources of information, possibly from other users, or from a database, or from a dynamic source such as a news feed, that might be of interest to that user. News feeds include but are not limited to news, alerts, announcements, motion detection events triggering security cameras, emails, instant messages (IMs), short message services (SMSs), sensors, real time search results, and custom content. The system can thus assist a user in managing information and retrieving relevant information.

Embodiments of the invention include any type of computerized device, workstation, handheld or laptop computer, or the like configured with software and/or circuitry (e.g., a processor) to process any or all of the method operations disclosed herein. In other words, a computerized device or a processor that is programmed or configured to operate as explained herein is considered an embodiment of the invention.

Other embodiments of the invention that are disclosed herein include software programs to perform the steps and operations summarized above and disclosed in detail below. One such embodiment comprises a computer program product that has a computer-readable medium including computer program logic encoded thereon that, when performed in a computerized device having a coupling of a memory and a processor and a display, programs the processor to perform the operations disclosed herein. Such arrangements are typically provided as software, code and/or other data (e.g., data structures) arranged or encoded on a computer readable medium such as an optical medium (e.g., CD-ROM), floppy or hard disk or other a medium such as firmware or microcode in one or more ROM or RAM or PROM chips or as an Application Specific Integrated Circuit (ASIC). The software or firmware or other such configurations can be installed onto a computerized device to cause the computerized device to perform the techniques explained herein. Other configurations include various graphical representations of the IOs themselves, for example as displayed on a graphical user interface as will be explained in more detail.

It is to be understood that the system of the invention can be embodied strictly as a software program, as software and hardware, or as hardware alone such as within a processor, or within an operating system or within a software application.

BRIEF DESCRIPTION OF THE DRAWINGS

The foregoing and other objects, features and advantages of the invention will be apparent from the following more

particular description of embodiments of the invention, as illustrated in the accompanying drawings and figures in which like reference characters refer to the same parts throughout the different views. The drawings are not necessarily to scale, with emphasis instead being placed upon illustrating the embodiments, principles and concepts of the invention.

FIG. **1** is an example network environment including computer systems configured with a relation manager in accordance with one example embodiment disclosed herein.

FIG. **2** shows an example layout of an IO in accordance with one example embodiment disclosed herein.

FIG. **3** is a diagram of information flow and IOs present themselves differently on different IVs and can be copied between IVs in accordance with one example embodiment disclosed herein.

FIGS. **4**A and **4**B are diagrams of News Views that display news for multiple different news papers postings by different users.

FIG. **5**A is a diagram of IOs being exchanged between IVs of different users.

FIG. **5**B is a diagram of IOs being exchanged between Private, Visible and Shared Views.

FIG. **6**A is a diagram of an exemplary graphical user interface (GUI) Organization in accordance with one example embodiment disclosed herein.

FIG. **6**B is a more detailed diagram of the exemplary GUI Organization of FIG. **6**A.

FIG. **6**C is a diagram of an alternate exemplary GUI Organization in accordance with one example embodiment disclosed herein.

FIG. **7** is a diagram of a graphical user interface (GUI) which allows the users to select import/export IOs from/to IM systems, other users views, shared views, e-mail tools, databases, agent systems in accordance with one example embodiment disclosed herein.

FIG. **8** is a diagram of IO File Management An IO can "display" different types of files such as pictures, text, movies, flash applications (left), attach/hyperlink different types of files (middle), and dynamically update IO contents (right). in accordance with one example embodiment disclosed herein.

FIG. **9** is a diagram of IO components in accordance with one example embodiment disclosed herein.

FIG. **10** is a diagram of IO Operations in accordance with one example embodiment disclosed herein.

FIGS. **11-13** are flow charts of processing steps performed to the in accordance with embodiments disclosed herein.

DETAILED DESCRIPTION

FIG. **1** illustrates the computer-networking environment **100** suitable for use in explaining example embodiments of invention. The computer-networking environment **100** includes a network **101** such as a local area network (e.g., LAN) that interconnects a plurality of computer systems **110-1** through **110**-N that each execute respective relation managers **150** (application **150-1** and process **150-2**), view manager managers **178** (application **178-1** and process **178-2**), connections managers **180** (application **180-1** and process **180-2**) and **10** file managers **182** (application **182-1** and process **182-2**) under respective control of a plurality of users **108**. The computer systems **110** may be any type of computerized device such as a personal computer, laptop, workstation, mainframe terminal, or the like. In this example, each computer system **110** generally includes in interconnection mechanism **111** such as a data bus, motherboard or other circuitry that interconnects a memory **112**, a processor **113**, an input output interface **114** and a communications interface **115**. A display **130** such as a computer monitor and input output mechanism **116** couple to the computer system **110** via the input output interface **114**. The communications interface **115** allows communication with other computer systems **110-2** through **110**-N over the network **101**. The architecture of the computer system **110-1** is shown in FIG. **1** by way of example only. It is to be understood that the details of the example computer systems **110-2** through **110**-N can be similar to those of computer system **110-1** but are not shown in FIG. **1** due to drawing space limitations.

The memory **112** within each computer system **110** may be any type of computer readable medium such as random access memory (RAM), read only memory (ROM). The memory **112** may be fixed or removable from the computer system **110**, such as a floppy disk, magnetic disk, optical disk media (e.g., CD ROM) or the like.

In one embodiment, the memory **112** is encoded with computer program logic (e.g., software code) that includes a relation manager application **120-1**. When the processor **113** executes the relation manager application **150-1**, the processor **113** produces a relation manager process **150-2** that executes as explained herein to produce a graphical user interface **132-1** (the example being produced by the relation manager **150** in computer **110-1**) on the display **130** for viewing by the user **108**. The relation manager process **150-1** and application **150-2** are collectively referred to herein as simply the relation manager **150**. When referring to the relation manager **150**, it can thus be a reference to the executing process **150-2**, the application code **150-1**, or both. Each relation manager **150** in combination with the view manager **178**, connections manager **180** and file manager **182** process files and documents and produce a graphical user interface **132** that provides, to the user **108**, visual knowledge representation, dynamically updated content, hosted conversations, and interpretation and management based in part on spatial relationships. To do so, the managers **150**, **178**, **180** and **182** include a workspace server **151**, a news server **152**, an exchange server **153** and a database server **154** that each produce, respectively, a Workspace View **300**, a News View **305**, a database view **310** and an exchange view **315** within the graphical user interface **132**. The relation manager **150** adds discovered relations to IO's in a database **125** (the database **125** may already include relations that other people or software products added). The relation manager also provides the algorithms **155** to examine the network of relations to discover potentially relevant information.

The database **125** maintains a history of updates to the IOs to allow for inclusive reconstruction of a particular IO at given time.

The workspace server **151** produces the Workspace View **300** that in one configuration is a graphical user work area, such as a desktop, in which a user **108** is able to create and manipulate graphical information objects **310** that graphically represent information objects of interest to user **108**. The Workspace View **300** helps users **108** to create, collect, organize and understand information associated with each IO **320** and the relationships among information represented by the IO **320**. In one configuration, a generic client application such as a web browser accesses such views from respective servers **151** through **154** that may execute on the same or different computer systems **110**. In another alternative configuration, a dedicated client application includes or provides the Workspace View, the News View, the database

view, and the exchange view and implements the news server, the database server, and the exchange server. It is to be understood that the system described herein may be distributed or centralized and may operate among many computer systems with many users **108**.

Information Objects (IOs) are flexible data structures and can include data files that can include other data files as well as meta-data (for the display of IO contents and the use of IO functions on different IVs), present themselves differently depending on the IV they are displayed on, include the same data and functionality on any IV they are displayed on. IOs can be copied or transferred between the same or different types of IVs, copied or transferred between the IVs of the same or different users, remain synchronized if copied to multiple IVs, synchronized with dynamic data sources other than source-IOs, moved from an IV to the computer desktop, file system, or 3rd party applications, thus converting an IO into a regular computer file that can be exchanged through conventional means such as email or file sharing and can be moved from the computer desktop, file system or 3rd party applications to any IV.

Information Views (IVs) can include graphical user interfaces that render IOs in different ways (can be described as a optical lenses that allows users to view information in different ways) and can enable access to all IO parameters and functions.

Using system **110** a user can interact with an information object, the system **110** facilitates sharing the IO among a plurality of participants; provides controls for attaching multi-media data to the IO, displays the IO in one of a plurality of views; and in response to interaction with one of the plurality of views by one of the participants, provide a communications path between at least two of the participants sharing the **10**.

Directing attention briefly to FIG. **2**, an example layout of an information object (TO) **310** is shown. An IO **320** in this example provides a visually compact, standardized, and abstract representation of information that displays, reminds of, and/or links to the original piece of information associated with that IO **320**. Generally, an IO **320** is any graphical representation of an information object and may be considered the information object itself. The term "IO" as used herein can thus include anything from a simple icon that represents something such as a web page, a document, or a live information source, or an IO can be a more complex representation of such things. Both, the layout and the functionality of IOs **320** are highly modular in one configuration. This means that visual components and computational features can be individually turned on and off, and that additional visual components and computational features can easily be integrated. Furthermore, the colors and fonts of all IO components are customizable. In one embodiment, IOs **320** are visually subdivided into six segments in one configuration that can expand and contract depending on their contents.

The icon area **321** allows for the placement of graphical and/or textual material that can help users **108** to quickly visually locate IOs among many other IOs as well as to memorize and recall the data, information or knowledge associated with that IO **320**. Users **108** can copy and paste pictures and text from various computer applications into the icon area. Users can also drag and drop pictures and text from web browsers and file managers into the icon area **321**. Furthermore, users can directly draw and write into the icon area **321**. The background color of the icon area **321** is also customizable allowing users to visually group and highlight IOs. Typically, the icon area **321** includes an IO graphic such as an icon, picture or other graphical information that represents information associated with that TO. As an example, if an HTML document such as a web page is of interest to a user, that user can create an IO to represent that web page. The IO can include a picture from the web page or a reduced sized version of the web page as its graphic.

The IOs **320** include an information bar **322** that accommodates an interface and visual indicators for complementary IO functions. A small rectangular box that includes an icon or in some cases a numerical counter represents each available IO function. Three distinct colors visually indicate the status of each function. In one configuration, the color gray is used for inactive functions, the color green is used for active functions and the color red is used for functions that require user attention. Every function can be individually turned on and off. The information bar **322** also allows for the customization and addition of functions specific to particular situations and work tasks. The following is a list of example functions and is not intended to limit the invention to information objects (e.g., IOs **320**) including such functions. A reference function allows users to hyperlink or to attach related information. A location function is used to associate IOs **320** with a geographic location. The location Algorithm indicates geographic locations for which cards (IOs) are available. In other words, if a card (TO) is associated with a geographic location then the Location Algorithm will represent this card with an icon on a map. Multiple cards in similar geographic locations do not produce multiple icons but a single icon of enlarged size. A typical application is a newspaper that marks on a world map all locations for which news is available. A control function enables automatic IO updates. A comment function allows for the addition of comments and annotations. A vote function allows collaborating users to exchange their opinions about the relevance of IOs. Every user is given one supporting vote for each card (TO). The icon color indicates the addition of recent and the presence of past votes. The numerical counter next to the icon displays the total number of supporting votes. An access log function provides users with a detailed record about the IO history. The Log Function provides users with a detailed record indicating the dates, times and names of all users that previously viewed, copied or modified the card (TO). The icon color indicates recent and past log entries. The counter next to the icon displays the number of log entries. This functionality allows users to review the evolution, collaborative use, and authorship history of cards (IOs). A personal note function is used to announce and send IOs **320** to specific users. A priority function allows users to categorize and highlight IOs.

The date/time bar **324** displays the date and time of the most recent IO modification. The relation manager **150** can use the date/time bar indication to reconstruct the chronology of contributions from different users and sources. The author bar **325** displays the name of the user who last modified the IO **320** or the information source the IO **320** has been copied from. The author bar **325** provides an indication of the IO editor and is used to compare contributions from different users and sources. The heading bar **326** allows users **108** to complement IOs **320** with a brief description or some keywords such as a title. The heading bar **326** effectively complements the icon area **321** by introducing language as an additional means for the abstract representation of data, information and knowledge. While the icon area **321** is particularly useful for the visual navigation of large IO arrangements, the heading bar **326** is focused on supporting the quick and easy recollection of IO meanings and contents.

The creation and use of IOs **320** can fundamentally shift the way analysts and decision-makers comprehend and think about information during sense-making activities. The creation of IOs **320** engages users **108** into a process of converting, standardizing, abstracting, and associating information while the use of IOs **320** fosters a strong focus on relating information uninfluenced by the format and location of information. Humans like to think of data, information and knowledge as objects that they collect, compare, and organize. The conversion of data and information (as well as the externalization of knowledge) into virtual and physical objects accommodates this way of thinking. Dealing with virtual and physical objects such as files on a computer desktop or documents on a table effectively increases a human's ability to deal with complex sense-making tasks. A standardized IO size and layout is convenient to collect, compare, and organize IOs **320**. Configurations disclosed herein are based in part on the observation that the benefits of standardized information objects are present in various everyday objects. For example, index cards, credit cards, business cards, slides, photographs and postcards are usually of equal size and layout so they can conveniently be stored, accessed, and processed. The abstract representation of data, information and knowledge with IOs **320** engages a human's visual recognition in ways that decreases information access time and allows for the processing of large amounts of information. Furthermore, the process of creating IOs **320** requires users to circumscribe the contents associated with IOs **320** in a visually and mentally fast accessible and easily comprehensible format thus encouraging a more careful analysis and understanding of the contents associated with IOs. The concept and use of abstract visual and textual reminders is also present in various everyday objects. For example, desktop icons and thumbnail views allow users to easily locate and organize computer files. Military ribbons use abstract visual representations to provide service, mission and award specific information on a small clothing area. Traffic signs depend on abstract visual representations that are easy to spot and understand by pedestrians and car drivers.

In one configuration, an IO **320** does not include information per se but only serves as a reminder for the presence of a particular piece of data, information or knowledge. The separation between IOs **320** and content associated with IOs **320** allows for the compact visualization and organization of large amounts of information. AN IO **320** may be viewed as a meaningfully labeled hyperlink to a piece of content available in a remote location. Users **108** can easily arrange and rearrange IOs **320** in the workspace **300**. Users **108** benefit from this process by developing a good understanding of the IO contents and the relations among IOs **320** (e.g., context). The use of IO arrangements also benefits collaborative sense-making tasks. People of different backgrounds, interests and foci have their unique ways of relating information. The collaborative development of IO arrangements can help people to determine intersecting views as well as to develop a shared understanding of a particular information space. Information objects are thus each represented as respective IOs **320** in this configuration.

The IO attribute indicators shown in FIG. **2** can indicate an IO state that can include such things as ownership of the IO, a geographic location associated with the IO, a time of creation of information associated with the IO, and other information. Depending upon the configuration, each IO **320** can further include features such as an instant messaging capability allowing to users in a distributed system to share access to an IO in order to exchange comments or messages between themselves concerning information associated with the IO. In one configuration, the system displays, within the IO perimeter, at least one messaging icon operable by a user to send a message to an IO associated with at least one other user, thus enabling collaboration. In one configuration, clicking on the messaging icon allows users to add a time/author stamped message to an IO **320** that all users **108-2** through **108**-N can see if they have a copy of this IO **320**. For any user **108**, the icon lights red if the IO **320** includes new messages that the user has not yet looked at, green if it includes messages that the user previously looked at, and gray if the IO includes no messages. The counter next to the icon displays the number of messages. It is to be understood a that reference to an IO **320** refers to an implementation of an information object, and as will be explained shortly, algorithms disclosed herein can analyze information about IOs, such as spatial relationships between IOs, and that such algorithms and processing can be applied to other representations of information objects besides IOs, such as desktop icons, physical locations of physical items such as items on a store shelf, and so forth.

Returning attention back to the graphical user interface **132** in FIG. **1**, the Workspace View **300** presents users with an empty canvas for the creation and grouping of IOs **320**. In one configuration, the Workspace View **300** can be the desktop of a computer system **110** provided by an operating system, such as the Windows Desktop provided by the Windows family of operating systems made by Microsoft Corporation of Redmond Wash., USA (Windows is a registered trademark of Microsoft Corporation). The Workspace View **300** is designed to support individual and collaborative sense-making tasks such as information analysis, planning, decision-making, brainstorming, and problem-solving. The Workspace View **300** functionality will provide users **108** with the means to efficiently create, collect, organize, analyze, and discuss information. In one configuration, IOs **320** may be created manually or semi-automatically. The manual creation of IOs **320** requires the user **108** to position an empty IO **320** on the Workspace View **300** and complement it with a picture, a heading, and a reference to an information source by simply dragging and dropping pictures, texts, hyperlinks, files, or file folders onto IOs **320**. The semi-automatic creation of IOs **320** allows users to drag and drop pictures, text, hyperlinks, URLs, files, and file folders directly onto the Workspace View **300**. This action will cause the workspace server **151** to create a new IO **320** with the content of the dropped item linked or attached to the IO **320** and with a picture and a heading added to an icon area and the heading bar (to be explained) of the IO **320**. Furthermore, users will be able to create cards (IOs) from within various computer applications (after installing a plugin) by clicking a bottom. Users **108** may also copy IOs **320** from the News View **305**, the database view **310** or the exchange view **315**. Furthermore, a user **108** can copy IOs **320** from the Workspace View **300** to the computer desktop or file system (and vice versa) thus converting IOs **320** into regular computer files. This functionality has a variety of applications such as to exchange IOs **320** by email or to convert IOs **320** for use with other software applications. Automated IO creation is provided as well that allows a user for example to specify a file system or path or URL or database identity and the system can traverse records, documents, web pages, files and the like within the specified path, database or domain and can convert each record, file or page into an IO for use in the system.

Below are steps a user **108** can perform to create a card. The relation manager **150** creates and displays a new card in

the workspace view. The user **108** may have performed a drag and drop of some content onto the workspace view **300**, or may have selected a pull down menu in the workspace view to create a new card **320**. In response, the relation manager **150** creates a new card record **160** in the database to correspond to the new card in the workspace view **300**. The relation manager **150** associates an information source identified by the first user to the new card **320** created in the workspace view. In the case of a drag and drop, the information source can be identified via the information dragged into the workspace view **300**. If the user created a new card from pull down menu selection, the workspace view **300** can prompt the user to specify a specific information source (that can be hyperlinked or embedded) such as a file system path and filename, a URL or some other indicator. The relation manager **150** stores card attributes and an identity of the information source in the new card record **160** in the card database. The relation manager **150** stores a card creation time in the new card record. The relation manager **150** stores a card position in the new card record **160**. The card position indicates positional information such as a corner pixel location (or a hierarchical location such as a specific window, directory, or desktop) as well as a window size of the new card **320** within the workspace view **300** of the first user **108**. The relation manager **150** stores an identity of the first user in the new card record **160**. The user for a new card becomes the author of that card **320**. Once a card **320** is created, pictures and text can be dragged and dropped onto the icon area and text can be dragged and dropped on the heading bar of the card to cause those areas to automatically change. In this manner, a user **108** can create a card by simply dragging a hyperlink or file or other digital material onto the workspace view **300**. A new card **320** is created where the hyperlink or file is dropped, a picture is added automatically (by searching the hyperlink destination or the file contents for an appropriate graphic), the heading is added automatically (usually the web site or file name), and a link or embedded attachment is automatically created from the file or the web site reference by the hyperlink.

In one embodiment the relation manager **150** allows a user to easily arrange, compare, and evaluate IOs **320** thus ensuring that users **108** will not be distracted by different information formats but focus on information contents. Each individual user **108** can determine the particular arrangement or spatial (vertical, horizontal, overlapping, proximal) layout of the graphical IOs **108** on his or her Workspace View that might indicate meaning to that user **108**. For example, a user **108** may group IOs that represent related information sources in a relatively close proximity to one another thus defining tight spatial relationships between those IOs.

The system is able to analyze spatial relationships that exist between IOs **320** in each users Workspace View **300** in order to identify other information objects (e.g., other IOs **320**) that may be of interest to that user **108**. Based on this analysis, the relation manager **150** can identify other information sources by showing other IOs **320** that might be of interest to that user. Embodiments disclosed herein are based in part on the observation that the spatial arrangement of a first set of objects such as IOs **320** in the Workspace View **300** can be used to identify relationships between those objects and can be further used to identify other objects (such as other IOs) that may be of importance to a user who created the initial spatial relation between the first set of objects in the Workspace View **300**.

The Workspace View **300** introduces several options for the grouping of IOs **320**. One option is to increase the size of one IO **320** so as to accommodate several other IOs **320** inside its boundaries. Moving an IO **320** will drag along all IOs **320** within its boundaries. A second option is to overlap IOs **320**. Moving an IO **320** inside a cluster of overlapping IOs **320** will drag along the entire cluster of IOs **320**. A third option is to use multiple workspaces for the grouping of IOs **320**. A fourth option is to link IOs **320** to an entire IO arrangement. A mouse-click onto such an IO **320** will then open another Workspace View **300** and display the IO arrangement. Further details on contents and layout of IOs **320** will be explained shortly.

The news server **152** produces (i.e. provides information feeds for) the News View **305** to allow users **108** to collect IOs **320** for addition to the Workspace View **300**. IOs **320** in the News View **305** represent information from a variety of other information sources. Feed examples includes news, alerts, announcements, motion detections on security cameras, emails, IMs, SMSs, sensors, real time search results, and custom content. An analogy of the News View **305** is a "news stand" in which recent or periodic information is available. In one configuration, the News View **305** displays the contents IOs **320** from news servers **151** that may be distributed through the network **101** within one of more computer systems **110**. IOs **320** in the News View **305** can be organized by time and information sources (e.g., by topic or content area) as well as by geographic locations associated with the information represented by each IO **320**, and can be filtered for user specific keywords. Users **108** are able to copy IOs **320** between the Workspace View **300** and the News Views **305**. IOs **320** copied from the News View **305** to the Workspace View **300** may be static and not change in content, or such IOs **320** may dynamically adapt to modifications in content so that as the information source associated with an IO **320** produces new information.

In one configuration, the system can display IOs in various arrangements within the News View **305**. In particular, the News View **305** can display a timeline arrangement of IOs **320**. The timeline arrangement provides a visualization that represents and organizes knowledge using a grid comprising of a timeline categorization for IOs on the horizontal axis and subject categorization on the vertical axis. In an alternative configuration, the new server **152** can display a map arrangement that provides a visualization that represents and organizes knowledge using a world-map or a floor plan comprising of geographical categorization for IOs. As an example, a News View can organize and arrange IOs in an ordered list or as a table with rows and columns of IOs organized horizontally by time and vertically by information sources. In such a configuration, new IOs for newly discovered information can be inserted on the left pushing existing IOs to the right. The time scale can be irregular and optimized to display the largest number of IOs possible. The rows of IOs in the News View can automatically expand and contract depending on the number of IOs to be shown in each row.

In this manner, the system disclosed herein provides a novel process for information retrieval and processing based on information collection support. In one example, the News View **305** displays incoming information in IOs **320** from user selected information sources. The users **108** can copy relevant information from the News View **305** to the Workspace View **300** or can create new information directly in the Workspace View **300** by creating new IOs. The user(s) **108** can study, organize, and categorize the information on the Workspace View **300**. In one configuration, if the Workspace View is connected to a server then all content and established relations are made accessible to this server. The user

can use two Workspace Views if he wishes to separate between information that is public and private. Other users **108** view the information on the news, database or exchange views **395**, **310** and **315** and can also copy relevant information from the news, database, and exchange views **305**, **310**, and **315** to their personal Workspace Views **300**. The system can track and analyze this movement of information from source to destination and can use this IO usage and movement data based on user identifiers, locations of IOs, arrangements of IOs, contents of IOs, times of movement and copying, and other such information in processing algorithms to infer or identify relationships between IOs and to suggest other IOs that reference other information that may be of interest to a user.

The News View **305** provides users **108** with the technology to effectively monitor and visualize additions and modifications from information sources such as web sites, databases, security cameras, alarm systems, sensors, news feeds and so forth. Every information item is displayed as an IO **320**. In one configuration, the News View **305** can organize and arrange IOs **320** in an ordered list or as a table with rows and columns of IOs **320** organized horizontally by time and vertically by information sources, such as by geographic origination or relation of the new story associated with the IO **320**. In another configuration, the News View has several visualization options such as displaying the IO arrangement in a table or displaying the IO arrangement on a geographic map. In one configuration, new IOs **320** for newly discovered information can be inserted on the left in an appropriate row pushing existing IOs **320** to the right. The time scale can be irregular and optimized to display the largest number of IOs **320** possible. The rows of IOs **320** in the News View **305** can automatically expand and contract depending on the number of IOs **320** to be shown. The News View **305** can include an adaptor for receiving news feeds and the user interface chronologically organizes information chronologically in a subject-time matrix. The News View **305** row can combine multiple data streams so that a row includes a group of data streams. A News View row can also display other data formats as well (email, search results, sensor data gathered though a file transfer protocol (FTP) in addition to displaying RSS streams.

The News View **305** offers a variety of tools for the exploration and collaborative use of information. As an example, a user **108** can copy IOs **320** from the News View **305** to the Workspace View **300** thus allowing users to easily collect, compare and organize new information. IOs **320** copied from the News View **305** to the Workspace View **300** may be static or dynamic as noted above. A static IO **320** is an exact copy of the IO on the News View **305**. In one configuration, a dynamic IO **320** continuously updates itself to reflect the most recent (left-most) IO on the News View row it was copied from. FIG. **9** below shows another example layout and additional IO features.

In this manner, the system disclosed herein provides a novel process for exchanging information and for asynchronous, decentralized, remote, and cross-organizational collaboration. In particular, users **108** use their individual Workspace Views **300** to organize and analyze information. The exchange server **153** produces the exchange view **315** to display cards (IOs) **320** that are concurrently displayed in one or more workspace views **300** of at least one other user **108**. The exchange view **315** can display cards (IOs) **320** in prioritized order, or alternatively can display cards **320** the way they are arranged on another users Workspace. This allows users **108** to view each other's Workspaces **300** as they appear to those other users **108**. The exchange view **315** displays (in prioritized or chronological order in one configuration) the IOs **320** created by all collaborating users **108** (or those with the appropriate access permissions or security levels). The exchange server **153** manages the display and exchange of card (TO) information between exchange views **315** and can include filter features to allow a user **108** to only see cards (IOs) from selected users **108** (as opposed to all cards (IOs) in all workspaces **300** of all users **108**). The users **108** can copy relevant IOs **320** from their exchange views **315** to their Workspace Views **300**. Users **108** can take "ownership" over IOs **320** copied from their exchange views **315** and these IOs **320** are now modifiable by the user **108**. In one configuration, when a user takes ownership of an IO **320**, the IO **320** is no longer synchronized with a counterpart IO on the IO author's Workspace View. In another configuration, once an IO **320** is owned exclusively by a user **108**, these IOs **320** can no longer be used for collaboration such as by "instant messaging," IO commenting, or "IO voting."

FIG. **3** show a diagram **360** of an IO **320** as viewed in several IVs. The diagram **360** also shows how IOs present themselves differently on different IVs and can be copied between IVs. The following are examples of the various IVs (not intended to be limiting). The News View **362** displays the contents of RSS streams (and other dynamic information sources) as IOs arranged in a table, organized by time in horizontal and by information sources, subject or category in vertical direction. New IOs are inserted on the left pushing existing IOs to the right. The time scale is irregular and optimized to display the largest number of Ms possible (meaning time segments without IOs are automatically removed). The rows automatically expand and contract depending on the number of news items (makes all rows display similar numbers of IOs). Users can add RSS files by simply dropping an IO or an RSS URL onto a row in News View. A News View row can include multiple RSS streams (multiple streams are automatically combined). The News View can be used to display a wide variety of information such as newspaper news, emails instant messages, motion activity on web cameras, eBay and Craigslist postings, company internal announcements and alerts. The News View can also be used as a RSS feed generator. For example, a user could create an empty News View that all users can view and add IOs to. Users can copy News View rows or individual IOs to other IVs. A copy of a News View row onto a Workspace View would result in a single IO that dynamically updates itself and that displays the most recent item in the associated RSS feeds. The primary purpose of the News View is to help users monitor large numbers of RSS feeds in a quick and easy comprehensible format.

The Workspace View **364** displays IOs in a game IO like format. The visual components of the IOs are customizable and expandable. Users can modify IO parameters in a so-called IO editor (see Illustration **3** and **4**). For example, users can add files to IOs, view and modify ratings, or discuss the IO contents with other users through the built-in instant messaging system or shared white board. If a user moves a regular file or a URL from a computer file system or a web browser onto the Workspace View then an IO is automatically created with the file attached or the URL hyperlinked. The Workspace View is designed to allow users to easily collect, organize and compare information in different formats and locations. For example, a Workspace View may be used for web shopping allowing users to quickly drag and drop items of interest from different web sites (such as Amazon, eBay, and Craigslist) onto the Workspace View for the subsequent comparison of options and prices. Since IO components can be dynamic (meaning that

they can automatically retrieve content updates from dynamic information sources) the user can also use a collection of IOs to monitor changes to prices and bids.

The Map View **366** is a geographic map display that represents IOs as location items. A location item presents itself as (one or more) symbols (of choice) on the map. The location item allows access to all IO functionality available in other IVs. If the geographic location associated with a location item is dynamic then the symbol would automatically update its location on the map. If a location item is copied to a Workspace View then it will present itself as an IO with the geographic location accessible and modifiable through the IO Editor. The Map View is primarily designed for military use but has a wide range of commercial applications as well. For example, a user could create a public Map View with hiking paths. Other users could copy hiking paths of interest from this public Map View to their personal Map View s or other IVs, discuss hiking paths through the IO instant messaging feature, or rate the quality of hiking paths through the IO rating system.

The Project View **368** is a time planning and calendar display (similar to MS Project) that allows users to represent IOs as time bars. IOs in this IV also maintain all the contents and functionalities of IOs displayed on other IVs. Moving an IO from the Project View to the Workspace View would create an IO that displays the time frame with a time bar on the IO or a time frame in the calendar tool of the IO Editor. The Project View is primarily designed for people that need to compare and modify time related IO parameters. For example, the Project View may be used to review and modify IOs that represent tasks scheduled for execution during particular time frames, resources that are only available during particular time frames or people that are only available during particular time frames.

The Graph View **370** displays IOs as line or bar graphs. This particular IV is primarily designed for comparing statistical data associated with IOs such as stock quotes, bids and sensor data.

The List View **372** is a spread sheet like display (similar to the Microsoft® Office Excel spreadsheet program) that allows users to represent IO parameters in a table format. The List View is primarily designed for people that need to compare and modify particular IO parameters such as, for example, the cost of sales items or the specifications of resources referenced by individual IOs.

Now referring to FIGS. **4**A and **4**B, screen shots show News Views that display news for multiple different news papers (FIG. **4**A) and postings by different users (FIG. **4**B).

FIG. **5**A shows a diagram of IOs being exchanged between IVs of different users. FIG. **5**B shows a diagram of IOs being exchanged between Private, Visible and Shared Views. There are various ways in which IOs can be exchanged between the IVs of the same and of different users such as:

by copying IOs from the personal IV of another user (Users can make their personal IVs accessible to other users. An IV can be Shared **510** (read/write), Visible **512** (read) or Private **514**;

by sending IOs to a particular user or group of users through the integrated instant messaging system or a commercial instant messaging system;

by sending IOs to a particular user or group of users through email;

by making IOs available through shared file systems; and

by retrieving IOs from our database (The database automatically collects and organizes IOs from the IVs of different users.

A variety of data visualization and access tools allow for the easy retrieval of IOs from the database, for example, in conjunction with an EWall Agent System; and by retrieving IOs from a Discovery View. The Discovery View presents individual users with a custom selection of potentially relevant IOs, and in one embodiment consolidates the Exchange View (**315**) and Database View (**310**). In this embodiment, the Discovery View not only displays related information in the IO database **125** but can also display related information found by other web services (e.g., related products for one selected product provided by online sellers or search engines). The Database Views (Discovery Views) **310** of individual users **108** display (in prioritized order) cards (IOs) **320** available in the database (as records **160**) that are related or relevant to the cards (IOs) **320** on a user's workspace view **300** based on the relations discovered via application of the relation processing algorithms **155**.

The relation manager **150** is able to analyze the spatial arrangement of the cards **320** as provided by the user **108** in the workspace view **300** in order to deduce or infer relations between the information sources associated with the cards **320**. In response, the database server **154** can provides other cards based on matching card records **160** maintained in the card database **125** that may be of interest to that user based on the analysis of the spatial arrangement of the cards **320** on that user's workspace view **300**. The database server **154** is thus capable of inventing or deriving additional relations **170** based on the analysis of previous relations. For example if card A is related to card B and card B is related to card C, then the database server **154** can decide to relate card A and C because the indirect relation suggests a partial correlation. In this manner, the system disclosed herein provides a novel process for organizational knowledge management based on information merging. Users **108** use their individual workspace views **300** (or operating system desktops and file systems) to organize and analyze information. Additions to the workspace views of all users are collected in the card database **125**. The database items including the relations **170** and the card records **160** are combined into one coherent network of cards using the relation processing algorithms **155**. The number of relations **170** between individual cards **320** may differ and can indicate the "strength" or "importance" of a relation **170** (or its unimportance or weakness). Relations **170** in the database **125** may be complementary or conflicting, speculative or concrete. The database views **310** of individual users **108** display (in prioritized order) cards **320** available in the database (as records **160**) that are related or relevant to the cards **320** on a user's workspace view **300** based on the relations discovered via application of the relation processing algorithms **155**.

The activities and contents on the individual users Workspace Views are monitored and recorded by the Recognition Functions. The Recognition Functions maintain a record of all active and erased cards including a list of all current and past owners and users of individual cards. The Recognition Functions record and combine all explicit relations among cards established by the users as well as all implicit relations established by the Algorithms. The Recognition Functions keep track of all interactions that take place among users. An interaction is registered if a user copies a card, views the content associated with a card, or adds a comment, vote or notification to a card.

The relation manager **150** analyzes card (TO) records **160** and card relations **170** within the card (TO) database **125**. The results of this analysis can produce an indication of other card records **160** in the card database **125** that correspond to other cards **320** that are not currently displayed in

the workspace view **300** of the user **108**, but that might be of interest to that user operating that workspace view **300**. A transformation algorithm **155** that can, for example, compare the combination of spatial relationships **170** that identify closely placed cards **320** in the workspace view **300**. For those cards **320** that are close to each other, the transformation algorithm **155** can compare the content of those cards (i.e., can compare the information sources referenced by these cards) to identify a common subject. Alternatively, the transformation algorithm **155** can compare the creation time of closely spaced cards. In another alternative, the transformation algorithm **155** can compare user identities of users **108** who have accessed these cards. Using these metrics (e.g. a common creation time window, or a common subject, common users or use patterns), the transformation algorithm **155** can identify, in order of relevance, a set of resultant cards not already placed in that user's workspace **300**. These can be shown to the user in the database view **310**. Additionally, the current arrangement of exchange view cards **320** can be reordered to reflect the newly discovered relations of the group of cards so that cards of other users that might be of importance to the user (that are already in the exchange view) are more to the front of the line or list in the exchange view to be more noticeable to that user. In one configuration, cards **320** displayed on views not only hint relevant information but also inform about people (the authors of the cards) with relevant knowledge on a particular topic. This can foster the creation of teams or communities of interest and help to build knowledge-based relationships between people due to information objects those people spatially organize in particular ways.

The relation manager **150** applies at least one interpretation algorithm **155** between card (TO) records **160** in the card database **125** to create relations **170** between card records **160** in the card database **125**. The relation manager **150** applies a spatial relation algorithm **155** that discovers spatial relations **170** between position information of at least two card records **160** in the card database **125** that are associated with cards **320** displayed on the graphical user interface **132** in the first set of cards. The relation manager **150** identifies implicit relations between cards in the first set of cards displayed on the graphical user interface based on proximity of cards on the graphical user interface. Thus, how close or far apart cards are can determine a strength or week relationship between cards **320**. The relation manager **150** identifies implicit relations between cards in the first set of cards displayed on the graphical user interface based on horizontal alignment of cards **320** on the graphical user interface **132**. Horizontal alignment can be suggestive of a list of items and transformation algorithms **155** can perform analysis of cards **320** arranged horizontally to suggest other cards that might be successor cards in the list. The relation manager **150** identifying implicit relations between cards in the first set of cards displayed on the graphical user interface based on vertical alignment of cards on the graphical user interface. Likewise, vertical arrangements of cards **320** might also be suggestive of a card list. The relation manager **150** identifying implicit relations between cards in the first set of cards displayed on the graphical user interface based on at least some overlap of cards on the graphical user interface. Overlapping cards can suggest a grouping relationship. It is to be understood that the spatial relations noted above are not limited to vertical, horizontal and overlap. Other spatial relations can exist and be analyzed as well, such as relative size relations between cards, or exclusive (i.e. alone) or particular placement (e.g. in a certain corner, in center, etc.) of cards **320** in certain regions within the graphical user interface **132**. Additionally, spatial processing algorithms can recognize card clusters that define groups of cards in close proximity to one another that create a cluster that is distinct from other clusters of other cards **320**. The relation manager can detect and analyze other relations as well besides spatial relations. As an example, context relations concerning use, access (e.g. copying) or other operations on cards can be detected that are based on time of card creation or modification, which users access a card, and relation of content between cards that have similar or relating subject matter. The relation manager **150** applies at least one context relation interpretation algorithm **155** to discover contextual relations between card records **160** in the card database **125**. The contextual relations **155** indicate commonality between at least two card records **160** based one or more relationship criteria. In one configuration, the relation manager **150** can detect and analyze chronological context of the at least two card records (e.g., sequence of creation or modification of card information). In another configuration, the relation manager **150** can detect and analyze collaborative context by at least two users **108** of at least two cards **320** respectively associated with the card records **160**. An example of collaborative context is when two or more users share two (or more) cards such as by providing comments to those cards, or using instant messaging to discuss information associated with the cards, or via other common access (e.g., copying to workspace) to the cards by those two or more users. In another configuration, the relation manager **150** can detect and analyze similarities of content identified by the at least two card records using keyword or subject or title matching, for example. In this manner, using contextual relations, the relation manager **150** can determine, for example, that if user A and B use the same card then other cards used by user A and B are more likely to become related. Card content can include content displayed on the card, parameters associated with the card, or information content hyperlinked to the card or metadata about the card (e.g., creation time, time of last access, time of last copy, user access history, etc.) that might not be readily visible from viewing the cards in a view. In one configuration, the database contents are evaluated based on the relations between cards. The relation manager **150** can thus establish relationships among cards **320** based on comparison of content and spatial history of card usage. Content relations are established based on a comparison of card contents such as headings, contents of hyperlinked files, and image descriptions, whereas context relations are established based on the spatial location of cards, the collaborative use of cards, or the virtual organization of cards (e.g. the hierarchical organization of files in computer directories). For example, two relations between two cards can be valued more than one relation between two cards. This is because two relations between two cards means that two different algorithms both established a relation between these two cards, although such relations may have been established for different reasons.

Four distinct types of Database Algorithms examine the networked contents of databases by defining a starting point, a search path, an end point, and the order in which the search results are returned: The first type of Database Algorithms defines the Start Point of a database search. The Start Point refers to a node (TO) in a database from where directly and indirectly related information is being retrieved. A Start Point may be defined though a conventional database query that contains text or graphical information. This means that a Start Point might reflect a node that contains similarities with information that a particular user is currently working

with, focusing on, or searching for. A Start Point can also be the most recently active node in the database such as the most recently added, retrieved, traversed, or modified node. Furthermore, a Start Point might be defined through so-called "Stimuli" or "Focal Points" that are placed and dynamically displaced by the Database Algorithms. The Start Point continuously changes its location and multiple Start Points may exist simultaneously. In the case of multiple Start Points the search progresses in parallel from multiple locations and in multiple directions. Every search returns the node referenced by the Start Point as well as a selection of directly and indirectly connected nodes. The selection of related nodes is defined by the Search Path. By default, the second node returned is the adjacent node with the most relations. The same procedure applies for all subsequent nodes unless specified differently by the Search Path. The second type of Database Algorithms defines the Search Path. The search path determines how the network is traversed. Every search initiates at a Start Point and proceeds by examining adjacent nodes. By default, adjacent nodes with many relations are examined first. Previously examined nodes are ignored. The Database Algorithms offer a variety of options for the examination of less heavily connected nodes. For example, the Curiosity Algorithm is used to increase the probability for the examination of weaker branches. In addition, the Persistence Algorithm determines how many nodes associated with weaker branches will be considered. Other Database Algorithms dynamically define and modify the Search Path based on the relevance of currently explored nodes. The relevance of nodes is determined based on the card contents or the card authors. For example, a card may not contain relevant content but its author may be known for having created cards that contain relevant content. Thus, the author is considered a specialist in this particular area and the cards created by the author are given preference. The third type of Database Algorithms defines the End Point of a Search Path. The End Point may be determined through an analysis of the card contents, the distance from the Start Point, or the time passed since the start of an examination. In other words, the End Point represents either a satisfying search result or a state of decreasing patience or tiredness. For example, the Patience Algorithm terminates a search after the examination of certain number of nodes. The fourth type of Database Algorithms orders the search results. By default, the search result is a string of nodes that reflects the sequence in which the nodes were examined. Other criteria of organizing the search results include the distance of nodes from the Start Point, the number of relations associated with individual nodes, or the card properties such as card sizes, modification dates, authors, contents, notifications, comments, votes, accesses, font types, font styles, font sizes, pictures, and locations.

The Unity Algorithm sorts cards (IOs) by the number of current and past users of individual cards. A card user is defined as somebody who created, copied, took ownership, reviewed the content, commented, or voted for a particular card. The Unity Algorithm assumes that the activity associated with a card is a meaningful way to determine the importance and popularity of the card. The Weight Algorithm sorts cards by the number of relations associated with individual cards may be related twice with card B and once with card C. Thus, card A is associated with three relations, card B with two relations, and card C with one relation. The Weight Algorithm assumes that number of links associated with a card is a meaningful way to determine the importance and popularity of the card. The Relevance Algorithm is the same as the Weight Algorithms yet only considers relations that connect with cards the user is using. For example, a card on a user's Exchange View may be related to four cards only one of which the user is using on his Workspace View. Thus, the number of associated relations for this card is assumed one rather than four. The Relevance Algorithm is particularly useful to spot cards that have some relevance with cards the user is already using. The Group Algorithm fosters the information exchange among users that have had frequent interactions in the past. The Group Algorithm considers an interaction when a user copies a card from another user, takes ownership over another user's card, or adds a comment or a vote to another user's card. The Group Algorithms orders cards based on the number of interactions that a particular user had with the individual card authors.

FIG. **6**A is a diagram of an exemplary GUI Organization including graphical user interface **610** for the management of IVs in accordance with one example embodiment disclosed herein. FIG. **6**B is a more detailed diagram of the exemplary GUI Organization of FIG. **6**A. In one embodiment, the GUI Organization includes three columns. The left column **620** includes displays **622** and **624** provided by the View Manager **178** and the Communication Manager **180**, respectively. The View Manager **178** displays all available IVs, allows users to open individual IVs, and enables users to modify the access rights of individual IVs. The View Manager **178** also displays representations of servers, databases, agent systems (e.g., EWall Agent System) and users in the collaborative environment. The Connection Manger **180** allows users to communicate with other users, exchange IOs with other users, access the IVs of other users, import IOs from databases and agent systems, as well as to control the export of IOs to databases and agent systems. The middle column **630** is used to display one or more IVs **632***a*-**632***n*. The right column **640** includes the IO Editors **640***a*-**640***n*. IO Editors **640***a*-**640***n* are tools that allow users to view and modify IO parameters and operate IO functions. The information displayed in IO Editors always refers to the currently selected IO or group of IOs.

FIG. **6**C is a diagram of an alternate exemplary GUI **660** in accordance with one example embodiment disclosed herein. Graphical user interface **660** for displaying an information objects includes a discussion subject **602**, a message indicator **603**, threaded discussion window **607**, a list of participants linked to the information object **608**, a collaborative rating **605** including a ranking of importance, a buddy list **601**, a discussion heading **604**, a list of attachments **606** and meta-data and shared applications **609**. In other embodiments the graphical user interface for displaying information objects includes a geographic map, category keywords and auction information. In other embodiments the attachments include thumbnails of multimedia data.

FIG. **7** is a diagram of a GUI **700** showing several features of the system **110** available to the user including control **710** which when clicked sends or receives an IM message about a view. This is a means for enhancing a hosted conversation, for example in a chat room. The GUI **700** further includes control **712** click to send/receive an IM message about an IO, for example in a chat room. The following controls can also be used: control **714** allows a database to collect information from the corresponding window; control; **716** disallows a database to collect information from the corresponding window; control **720** sends an IO to a user or a group of users; control **724** disallows a user to view details of the corresponding view; control **726** allows a user to view/modify the corresponding view; control **728** sends or receives an IM message or IO to or from the user, for

example in a chat room; and control **730** sends an IM message or IO to a group of users, for example in a chat room. Indicator **718** indicates available resources in a database (cards, visualizations, statistics, etc.) and indicator **722** indicates a view of another user that is open for viewing or modification. GUI **700** allows the users to import and export IOs from and to IM systems, other users views, shared views, e-mail tools, databases, agent systems.

FIG. **8** is a diagram of IO File Management **800** which allows an IO to display the content of different types of files **802** including such as content from: a web site **810**, flash applications **812**, movies **814**, pictures, text from office documents **816**, PDF documents **818** and other documents **820**. In operation, the IO file manager **182** processes attachments, hyperlinked web content from the different file types **802** and remote sources **806** including remote RSS files **822**, remote objects **824** and remote files **826** to create and dynamically update IO contents.

A user **108** can create an IO by simply dragging a hyperlink or file or other digital material onto the Workspace View **300**. A new IO is created where the hyperlink or file is dropped, a picture is added automatically (by searching the hyperlink destination or the file contents for an appropriate graphic), the heading is added automatically (typically the web site or file name), and a link or embedded attachment is automatically created from the file or the web site reference by the hyperlink

FIG. **9** is a diagram of IO components expanding on the basic IO components described above in FIG. **2**. IOs include default and custom parameters and functions. IO parameters and functions are best explained with IOs rendered on Workspace Views. IOs can display a large number of IO parameters and function without the need for the user to access the IO Editor. The IO layout can be customized to only display the IO parameters and function the user wants to see. The following list provides a few examples of IO parameters and functions as they would appear in different sections (Bars) of an IO on a Workspace View.

Picture/Text bar **902** allows the insertion and display of text, pictures, PDF files, active Flash applications (can run inside the Picture/Text Bar), Office documents, and additional applications, file types and multi-media data. Function Bar **910** displays icons that serve as status indicators and that link to particular IO Editors.

A Bubble Icon **912** opens an IO Editor window that allows users to exchange comments, share a white board, contribute to a forum, or insert notes. The "bubble" icon **912** is rendered white if no user added any information, gray if one or more user added information and red if one or more users added information that the viewer has not yet looked at. An optional calendar tool allows users to compare their availabilities and schedule a "chat" session ahead of time.

A Flag Icon **914** links to a map display in the IO Editor allowing users to view and modify geographic locations associated with an IO. A Person Icon **916** indicates whether a particular IO is used by other users and links to an IO Editor that allows the IO owner to view the list of IO users as well as to assign access restrictions to IO contents. A File Icon **918** allows users to add and access (any number of) attachments and hyperlinks to an IO and allow for contents to be partially or fully encrypted. An Arrow Icon **920** allows users to add, modify and control dynamic information sources (e.g., to control automatic updates to IO contents retrieved from dynamic information sources such as Email accounts, RSS feeds, sensors, motion detectors and security cameras or web sites). Users can activate one or more Reliability/Ratings/Votes/Importance/Priority Bars (collectively referred to as bars **924**) for the individual and collaborative evaluation of information. IOs can be evaluated on a scale from 1 to 5 (represented by 5 boxes). Filled boxes represent the average evaluations of all IO users while the arrow symbol indicates the individual rating of the IO viewer.

Trade bar **930** and Value/Value Change bar **928** comprise a trading feature that allows users to trade IO contents or items referenced by IOs. For example, an IO could represent a stock (market item) and allow users to monitor, buy and sell stocks; an item on eBay or Craigslist and allow users to monitor and manage bids; or an item on Amazon and display its current purchase price. Users associate IOs with one or more categories using a Category bar **932** that allows for faster IO searches on IVs and databases. Users associate IOs with a time or time frame using Time Frame/Schedule bar **934**, for example, displayed on IOs as a point or as a bar on a time scale. The time scale is the same for all IOs and can be set in the preference menu, e.g. left side of the bar=−12 hours, middle=now, right=+12 hours. The point or bar on the time scale will move from left to right in accordance to the real time. Graphic display **940** shows various display options for icons on the various function bars.

In one embodiment the system **110** provides hosted conversation among a group of participants using the integrated instant messaging system facilities which provide a communication system linking an IO to a group of participants. Each system component (TO, IV, Database, Agent System) and participant is linked to the instant messaging system (also known as a chat room). The IO can include a link to a document, links to the group of participants, meta-data related to the conversation and communication system which links the IO to the group of participants. The process of initiating a hosted conversation begins when a user starts a discussion or a collaborative project by first creating a new IO and then adding data, meta-data and linking participants to the IO.

For example, to communicate about the contents of an IO the user would click the bubble icon **912** on this IO in the user interface on the client system to "chat" (about this IO) with other participant who maintains a copy of this IO. Clicking on the "bubble" icon **912** associated with a participants (or group of participants) listed in a contact list and linked by the connection manger **180** would initiate a "chat" session with those participants. The hosted conversation includes a list of participants linked to the at least one information object and an IV to visualize the at least on information object. Clicking on the "bubble" icon **912** associated with the IV in the View Manager would initiate a "chat" session (about this IV) with every other participant who has access to this IV. The integrated instant messaging system is also used to exchange IOs between users. An IO can simply be dragged and dropped onto a user icon which subsequently sends a copy of this IO to the intended recipient. The instant messaging functionality can be complemented with any other IO parameter and function such as, for example, a function that allows users to assign ratings to databases, agent systems, users or IVs. One important benefit of this system is that it allows users to stay engaged in a large number of discussions about particular subjects represented by different users, IOs or IVs. Advantageously the user can organize and monitor a large number of IOs where every IO represents a different issue that may be discussed with a different groups of participants.

Thus system **110** provides a graphical interface for displaying an information object which includes displaying a threaded discussion window, a list of participants linked to

the information object, a collaborative rating including a ranking of importance, a buddy list, a discussion heading; and a list of attachments.

FIG. **10** is a diagram of IO operations including IO creation. IOs can be created manually or automatically. The automatic creation converts a non-IO object or file into an IO if a user imports a non-IO file from any application into an IV. For example, if a user drags a URL of an item for sale on the Amazon web site onto the Workspace View, the resulting IO would display an image of the item in the Picture Bar, the name of the item in the Heading Bar, the cost of the item in the Value Bar, and hyperlinks to the Amazon web site where the item is advertised. Filters include the rules and manage the conversion from non-IO files to IOs.

Generally, IOs can be manually created such as by creating a blank IO and then specifying an information source to which that IO refers. The IO look can be complemented with a picture, explanatory text, a heading and other visual attributes by simply dragging and dropping pictures and text fragments onto the IO. Alternatively, in another mode, IOs can be semi-automatically created in a Workspace View or on a desktop by dragging an information object such as hyperlink, document, file or URL onto the Workspace View in which case a new IO is automatically formed and associated with the hyperlinked data, file or document. The IO picture and the IO heading are added automatically if an appropriate picture and heading can be extracted from the dragged information object or if an appropriate picture can be found in a database that matches the file name or within some of the content of the dragged information object. In yet another mode, an automated IO creation process can traverses a set of records or files, such as a database or file system or all web pages within a certain URL and can perform automatic creation of IOs from each database record, web page, or file. As an example, entire databases or file systems or all documents below or within a certain URL or domain on the Internet can automatically be converted into IOs using the semi-automatic creation of IOs but in a non-manual way that does not require a user dragging and dropping of each file, document or URL onto a view.

The following Workspace View examples detail several exemplary user interactions with IOs and IVs. A user can drag a URL from a web browser onto a Workspace View which will create an IO that hyperlinks to that URL and automatically extracts (from the URL destination) a picture and a heading that is displayed in the IO's picture and heading bar. The user can drag an RSS URL onto a Workspace View which will create an IO that visualizes the most recent item in the RSS file/s and that continuously updates itself. The user can drag a regular document (file) onto a Workspace View which will create an IO with the document attached. Dragging a document onto an IO also attaches the document. The user can import an IO from another user into the Workspace View which will create an IO copy that is synchronized with the original IO. The user can drag an IO from the Workspace View to the computer desktop which will create an IO file. The user can drag an IO from a News View row to the Workspace View which will create an IO copy that is synchronized with the original IO. The user can drag a News View Row to the Workspace View which will create an IO that visualizes the most recent item in the RSS file/s and that continuously updates itself. In another embodiment, a user can drag a buddy icon from an instant messaging system onto the IO or drag an IO the buddy icon to initiate a conversation or to link the "buddy" to the IO. In this manner, links are formed between the information object and one of the plurality of participants by selecting the information object and selecting the participant from a displayed list of participants and the system **110** associates participants and information objects by indicating a connection between an icon from an instant messaging system and the information object.

The following News View examples detail several exemplary user interactions with IOs and IVs. The user can drag one or more RSS URLs onto a News View row which will add and displays the content of RSS URLs on the News View row as a sequence of IOs. The user can drag and drop a Workspace View ID onto a News View row which will display IO additions and modification on that Workspace. The user can drag and drop an IO onto a News View row which will add that IO to the IO sequence. The user can drag an IO from a News View row to the computer desktop which will create an IO. The user can drag a News View row to the computer desktop which will create an IO.

FIG. **11** diagrams the overall process of interacting with an information object. In step **1110**, the system provides the information object (I/O), for example on a GUI display as described above. A new IO can be created from scratch or by using a filter, or an existing IO can be shared, copied, transferred, etc. as described above. Next, in step **1120**, the IO is shared among a plurality of participants. In step **1130**, multi-media data can be optionally attached to the information object. In step **1140**, the information object is displayed in one of a plurality of views. Finally in step **1150**, in response to interaction with one of the plurality of views by one of the participants, a communications path between at least two of the participants sharing the information object is provided by the connection manager **180**.

FIG. **12** is a flow chart of processing steps showing additional details in conjunction with flow char **1100** FIG. **11**, that system **110** performs to allow interactions with an information object in accordance with embodiments disclosed herein. In one embodiment, step **1210** provides the information object by filtering a web page associated with a URL to create the information object by automatically extracting meta-data including at least one of a heading, a picture, and link to the URL. In step **1220**, the information object is shared among a plurality of participants by transferring the information object between different information views. In step **1230**, the multi-media data is linked to the information object

In step **1240**, an automated participant is provided. The automated participant interacts with the information object. In some embodiments, there is no distinction between a user and an automated participant (e.g., a participant based on a computational system). In step **1250**, information is retrieved based on user interaction with the information object including spatially arranging the information object relative to other information objects. In step **1252**, interaction with the information object includes attaching at least one document to the information object.

FIG. **13** is a flow chart of processing steps that system **110** performs to support a hosted conversation among a group of participants including interactions with an information object in accordance with embodiments disclosed herein. In step **1310**, a link to at least one information object is stored to host a conversation among a group of participants. The information object includes at least one link to a document; a plurality of links to the group of participants; meta-data related to the conversation; and a communication system linking the at least one information object to the group of participants provided by connection manager **180**.

In step **1320**, a user interface on the client system is provided. The user interface includes an icon representing

the at least one information object a contact list; a list of participants linked to the at least one information object; and an information view to visualize the at least on information object. In step **1330**, an Information View is displayed that includes a News View having an adaptor for receiving news feeds and the user interface chronologically organizes information chronologically in a subject-time matrix. The user interface further includes a zoomable, graphical timeline including automatic compression of the subject-time matrix and in one embodiment the news feed is a syndication feed.

While configurations of the system and method have been particularly shown and described with references to configurations thereof, it will be understood by those skilled in the art that various changes in form and details may be made therein without departing from the scope of the invention. As an example, the order of processing steps in the flow charts is not limited to the order shown herein. Accordingly, the present invention is not limited by the example configurations provided above.

What is claimed is:

1. A computer-implemented method, in which at least one computer initiates execution of software instructions to perform computer processes, the method being for interacting with at least one data item obtained from at least one source, the at least one source being external to the at least one computer, the computer processes comprising:

responsive to a user selection of the at least one data item:

causing configuring of each of the data items into a distinct information object by extracting, from each data item, extracted data including a picture and a heading, and causing storing of data corresponding to each of the information objects, including a link to the at least one data item, in a database system;

displaying a representation of each of at least two of the information objects in the database system, the representation being in a uniform format, wherein the format includes a card, and, within the card, in uniform locations thereof, the picture, the heading, a set of indicators, and a set of graphically accessible functions including:

a comment function, by which users having access to the card comment function can exchange comments relating to the card, such comments being associated with the information object represented by the card;

a vote function, by which users having access to the card vote function can vote for the card, such votes being associated with the information object represented by the card;

a copy function, by which users having access to the card copy function in a first collection of cards of a first user can cause the card to appear in a second collection of cards of a second user; and

a link function, by which users having access to the card link function can invoke the link to the data item; and wherein the set of indicators includes:

an indicator reflecting commenting activity associated with the card; and

wherein the database system has been configured to allow (i) each user to have at least one user-selected collection of cards representing information objects in the database system and (ii) cards, regardless of the collections in which they may have first appeared, to be made accessible and copyable across card collections of different users.

2. A method according to claim **1**, the computer processes further comprising:

displaying a graphical button, which, when invoked while content is being displayed, causes the displayed content to be handled as one of the data items, namely, by configuring the displayed content as a new information object and making a representation of the new information object available for display in the uniform format.

3. A method according to claim **1**, wherein the format includes within the card an indication of a date of creation.

4. A method according to claim **1**, wherein the format includes a user-accessible report relating to users who copied the information object.

5. A method according to claim **1**, further comprising:

displaying in a computing device of a first user, a first view of a first set of cards that constitute a first collection of the first user; and

also displaying in the computing device of the first user, a second view of a second set of cards that constitute a collection of a second user.

6. A method according to claim **5**, further comprising:

responsive to (i) a graphical selection, by the first user, of a card in the second view and (ii) a copy command that has been graphically entered by the first user, causing the selected card to be copied from the second view to the first view, so that the selected card in the collection of the second user appears in the first collection of the first user.

7. A method according to claim **5**, further comprising:

responsive to (i) a graphical selection, by the first user, of a card in the first view and (ii) a send command that has been graphically entered by the first user, causing the selected card to be sent to the second user, so that the selected card in the collection of the first user is made available to the second user to be included in the collection of the second user.

8. A method according to claim **1**, further comprising:

on a user-entered command, causing a card to be shared with another user when the card and the other user have been graphically selected.

9. A method according to claim **1**, further comprising:

on a user-entered command, causing a card to be shared with another user via an instant message sent through an integrated instant messaging system as a result of graphical selection by a first user.

10. A method according to claim **1**, further comprising:

displaying in a computing device of a first user, a first view of a first set of cards that constitute a first collection of the first user;

also displaying in the computing device of the first user, a second view of a second set of cards, outside of the first collection, wherein any given member of the second set of cards is both included in a collection of another user and the other user has been selected by the first user; and

wherein each of the cards in the second view can, on a user-entered command, be caused to be copied to the first view.

11. A method according to claim **10**, wherein each of the cards in the second view is displayed in an order determined by a criterion selected from the group consisting of the information object's creation time, its access time, and combinations thereof.

12. A method according to claim **1**, wherein the set of indicators includes:

an indicator reflecting voting activity associated with the card.

13. A method according to claim 12, wherein the indicator reflecting voting activity associated with the card provides a numeric count of the voting activity.

14. A method according to claim 1, wherein the indicator reflecting commenting activity associated with the card provides a numeric count of the commenting activity.

15. A computer-implemented method, in which at least one computer initiates execution of software instructions to perform computer processes, the method being for interacting with at least one data item obtained from at least one source, the at least one source being external to the at least one computer, the computer processes comprising:

responsive to a user selection of the at least one data item:

causing configuring of each of the data items into a distinct information object by extracting, from each data item, extracted data including a picture and a heading, and causing storing of data corresponding to each of the information objects in a database system;

displaying a representation of each of at least two of the information objects in the database system, the representation being in a uniform format, wherein the format includes a card, and, within the card, in uniform locations thereof, the picture, the heading, a set of indicators, and a set of graphically accessible functions including:

a comment function, by which users having access to the card comment function can exchange comments relating to the card, such comments being associated with the information object represented by the card;

a vote function, by which users having access to the card vote function can vote for the card, such votes being associated with the information object represented by the card;

a copy function, by which users having access to the card copy function in a first collection of cards of a first user can cause the card to appear in a second collection of cards of a second user; and

wherein the set of indicators includes:

an indicator reflecting commenting activity associated with the card; and

wherein the database system has been configured to allow (i) each user to have at least one user-selected collection of cards representing information objects in the database system and (ii) cards, regardless of the collections in which they may have first appeared, to be made accessible and copyable across card collections of different users.

16. A method according to claim 15, wherein the extracted data from each data item includes at least the picture and the heading and wherein the heading is included within the card.

17. A method according to claim 15, the computer processes further comprising:

displaying a graphical button, which, when invoked while content is being displayed, causes the displayed content to be handled as one of the data items, namely, by configuring the displayed content as a new information object and making a representation of the new information object available for display in the uniform format.

18. A method according to claim 15, wherein the format includes within the card an indication of a date of creation.

19. A method according to claim 15, wherein the format includes a user-accessible report relating to users who copied the information object.

20. A method according to claim 15, further comprising:

displaying in a computing device of a first user, a first view of a first set of cards that constitute a first collection of the first user; and

also displaying in the computing device of the first user, a second view of a second set of cards that constitute a collection of a second user.

21. A method according to claim 20, further comprising:

responsive to (i) a graphical selection, by the first user, of a card in the second view and (ii) a copy command that has been graphically entered by the first user, causing the selected card to be copied from the second view to the first view, so that the selected card in the collection of the second user appears in the first collection of the first user.

22. A method according to claim 20, further comprising:

responsive to (i) a graphical selection, by the first user, of a card in the first view and (ii) a send command that has been graphically entered by the first user, causing the selected card to be sent to the second user, so that the selected card in the collection of the first user is made available to the second user to be included in the collection of the second user.

23. A method according to claim 15, further comprising:

on a user-entered command, causing a card to be shared with another user when the card and the other user have been graphically selected.

24. A method according to claim 15, further comprising:

on a user-entered command, causing a card to be shared with another user via an instant message sent through an integrated instant messaging system as a result of graphical selection by a first user.

25. A method according to claim 15, further comprising:

displaying in a computing device of a first user, a first view of a first set of cards that constitute a first collection of the first user;

also displaying in the computing device of the first user, a second view of a second set of cards, outside of the first collection, wherein any given member of the second set of cards is both included in a collection of another user and the other user has been selected by the first user; and wherein each of the cards in the second view can, on a user-entered command, be caused to be copied to the first view.

26. A method according to claim 25, wherein each of the cards in the second view is displayed in an order determined by a criterion selected from the group consisting of the information object's creation time, its access time, and combinations thereof.

27. A method according to claim 15, wherein the set of indicators includes:

an indicator reflecting voting activity associated with the card.

28. A method according to claim 27, wherein the indicator reflecting voting activity associated with the card provides a numeric count of the voting activity.

29. A method according to claim 15, wherein the indicator reflecting commenting activity associated with the card provides a numeric count of the commenting activity.

* * * * *