

(12) **United States Patent**
Moskowitz et al.

(10) **Patent No.:** **US 11,903,849 B2**
(45) **Date of Patent:** **Feb. 20, 2024**

(54) **INTERVERTEBRAL IMPLANT AND TOOL ASSEMBLY**

(58) **Field of Classification Search**
CPC ... A61F 2/447; A61F 2/4455; A61F 2002/448
See application file for complete search history.

(71) Applicant: **Moskowitz Family LLC**, Rockville, MD (US)

(56) **References Cited**

(72) Inventors: **Ahmnon D. Moskowitz**, Rockville, MD (US); **Pablo A. Valdivia Y. Alvarado**, Cambridge, MA (US); **Mosheh T. Moskowitz**, Rockville, MD (US); **Nathan C. Moskowitz**, Rockville, MD (US)

U.S. PATENT DOCUMENTS

2,360,942 A 10/1944 Ellerstein et al.
4,064,881 A 12/1977 Meredith
(Continued)

FOREIGN PATENT DOCUMENTS

FR 2727003 5/1996
KR 20-0290058 9/2002
(Continued)

OTHER PUBLICATIONS

U.S. Appl. No. 60/869,088, filed Dec. 7, 2006, Olmos et al.
(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **17/706,873**

(22) Filed: **Mar. 29, 2022**

(65) **Prior Publication Data**

US 2022/0218498 A1 Jul. 14, 2022

Related U.S. Application Data

(63) Continuation of application No. 16/744,755, filed on Jan. 16, 2020, which is a continuation of application
(Continued)

(51) **Int. Cl.**
A61F 2/44 (2006.01)
A61F 2/46 (2006.01)
(Continued)


(52) **U.S. Cl.**
CPC **A61F 2/4611** (2013.01); **A61B 17/0642** (2013.01); **A61B 17/7064** (2013.01);
(Continued)

Primary Examiner — Ellen C Hammond
(74) *Attorney, Agent, or Firm* — Fish & Richardson P.C.

(57) **ABSTRACT**

A self-drilling bone fusion screw apparatus is disclosed which includes at least first and second sliding boxes. A first screw member having a tapered end and a threaded body is disposed within the first sliding box, and a second screw member having a tapered end and a threaded body disposed within the second sliding box. An adjuster adjusts the height of the sliding boxes. The screw members are screwed into vertebral bodies in order to fuse the vertebral bodies together. A plurality of the self-drilling bone fusion screw apparatuses may be attached together and/or integrated via a plate or cage. Also disclosed is a cervical facet staple that includes a curved staple base and at least two prongs attached to the bottom surface of the curved staple base.

21 Claims, 38 Drawing Sheets



Related U.S. Application Data

- No. 15/944,117, filed on Apr. 3, 2018, now Pat. No. 10,537,442, which is a continuation of application No. 15/894,471, filed on Feb. 12, 2018, now Pat. No. 10,390,969, which is a continuation of application No. 13/210,157, filed on Aug. 15, 2011, now Pat. No. 9,889,022, which is a continuation of application No. 13/084,543, filed on Apr. 11, 2011, now Pat. No. 8,353,913, and a continuation of application No. 13/108,982, filed on May 16, 2011, now Pat. No. 9,005,293, said application No. 13/084,543 is a continuation of application No. 11/842,855, filed on Aug. 21, 2007, now Pat. No. 7,942,903, said application No. 13/108,982 is a continuation of application No. 11/842,855, filed on Aug. 21, 2007, now Pat. No. 7,942,903, which is a continuation-in-part of application No. 11/536,815, filed on Sep. 29, 2006, now Pat. No. 7,846,188, which is a continuation-in-part of application No. 11/208,644, filed on Aug. 23, 2005, now Pat. No. 7,704,279.
- (60) Provisional application No. 60/670,231, filed on Apr. 12, 2005.
- (51) **Int. Cl.**
A61B 17/064 (2006.01)
A61B 17/70 (2006.01)
A61B 17/80 (2006.01)
A61B 17/88 (2006.01)
A61B 17/86 (2006.01)
A61B 17/92 (2006.01)
A61B 17/00 (2006.01)
A61F 2/28 (2006.01)
A61F 2/30 (2006.01)
A61B 17/17 (2006.01)
- (52) **U.S. Cl.**
 CPC *A61B 17/809* (2013.01); *A61B 17/8635* (2013.01); *A61B 17/8875* (2013.01); *A61B 17/8894* (2013.01); *A61B 17/92* (2013.01); *A61F 2/447* (2013.01); *A61F 2/4465* (2013.01); *A61B 17/0644* (2013.01); *A61B 17/1757* (2013.01); *A61B 17/86* (2013.01); *A61B 2017/00407* (2013.01); *A61B 2017/0641* (2013.01); *A61B 2017/0648* (2013.01); *A61B 2017/922* (2013.01); *A61F 2002/2835* (2013.01); *A61F 2002/3055* (2013.01); *A61F 2002/30133* (2013.01); *A61F 2002/30387* (2013.01); *A61F 2002/30448* (2013.01); *A61F 2002/30507* (2013.01); *A61F 2002/30579* (2013.01); *A61F 2002/30593* (2013.01); *A61F 2002/30604* (2013.01); *A61F 2002/30772* (2013.01); *A61F 2002/30878* (2013.01); *A61F 2002/30879* (2013.01); *A61F 2002/30904* (2013.01); *A61F 2002/448* (2013.01); *A61F 2002/4627* (2013.01); *A61F 2002/4681* (2013.01); *A61F 2002/4687* (2013.01); *A61F 2220/005* (2013.01); *A61F 2220/0025* (2013.01); *A61F 2230/0015* (2013.01); *A61F 2250/0007* (2013.01)
- (56) **References Cited**
 U.S. PATENT DOCUMENTS
 4,505,273 A 3/1985 Braun
 4,554,914 A 11/1985 Kapp et al.
- 4,599,086 A 7/1986 Doty
 4,636,217 A 1/1987 Ogilvie et al.
 4,904,261 A 2/1990 Dove et al.
 4,960,420 A 10/1990 Goble et al.
 4,997,432 A 3/1991 Keller
 5,005,749 A 4/1991 Aranyi
 5,062,850 A 11/1991 MacMillan et al.
 5,123,926 A 6/1992 Pisharodi
 5,192,327 A 3/1993 Brantigan
 5,236,460 A 8/1993 Barber
 5,290,312 A 3/1994 Kojimoto et al.
 5,352,229 A 10/1994 Goble
 5,390,683 A 2/1995 Pisharodi
 5,405,391 A 4/1995 Henderson et al.
 5,413,583 A 5/1995 Wohlers
 5,425,490 A 6/1995 Goble et al.
 5,454,819 A 10/1995 Knoepfner
 5,514,180 A 5/1996 Heggeness et al.
 5,522,899 A 6/1996 Michelson
 5,609,635 A 3/1997 Michelson
 5,658,335 A 8/1997 Allen
 5,660,188 A 8/1997 Groiso
 5,662,655 A 9/1997 Laboureau
 5,665,122 A 9/1997 Kambin
 5,667,472 A 9/1997 Finn et al.
 5,713,912 A 2/1998 Porter
 5,782,832 A 7/1998 Larsen et al.
 5,800,550 A 9/1998 Sertich
 5,865,848 A 2/1999 Baker
 5,888,223 A 3/1999 Bray, Jr.
 5,916,224 A 6/1999 Esplin
 5,951,574 A 9/1999 Stefanchik et al.
 5,960,522 A 10/1999 Boe
 5,968,054 A 10/1999 Yeatts et al.
 5,976,136 A 11/1999 Bailey et al.
 6,066,175 A 5/2000 Henderson et al.
 6,102,950 A 8/2000 Vaccaro
 6,120,503 A 9/2000 Michelson
 6,126,689 A 10/2000 Brett
 6,176,882 B1 1/2001 Biedermann et al.
 6,179,873 B1 1/2001 Zientek
 6,224,602 B1 5/2001 Hayes
 6,235,034 B1 5/2001 Bray
 6,322,562 B1 11/2001 Wolter
 6,325,805 B1 12/2001 Ogilvie
 6,336,928 B1 1/2002 Guerin et al.
 6,342,074 B1 1/2002 Simpson
 6,368,350 B1 4/2002 Erickson et al.
 6,375,682 B1 4/2002 Fleischmann et al.
 6,419,704 B1 7/2002 Ferree
 6,432,106 B1 8/2002 Fraser
 6,443,989 B1 9/2002 Jackson
 6,454,806 B1 9/2002 Cohen et al.
 6,454,807 B1 9/2002 Jackson
 6,458,159 B1 10/2002 Thalgott
 6,527,804 B1 3/2003 Gauchet et al.
 6,533,818 B1 3/2003 Weber et al.
 6,558,423 B1 5/2003 Michelson
 6,562,074 B2 5/2003 Gerbec et al.
 6,572,653 B1 6/2003 Simonson
 6,579,318 B2 6/2003 Varga et al.
 6,582,468 B1 6/2003 Gauchet
 6,613,055 B2 9/2003 Di Emdio
 6,629,998 B1* 10/2003 Lin A61F 2/447 623/17.11
 6,641,614 B1 11/2003 Wagner et al.
 6,652,533 B2 11/2003 O'Neil
 6,655,243 B2 12/2003 Anderson et al.
 6,706,070 B1 3/2004 Wagner et al.
 6,716,247 B2 4/2004 Michelson
 6,719,794 B2 4/2004 Gerber
 6,723,126 B1 4/2004 Berry
 6,730,127 B2 5/2004 Michelson
 6,733,532 B1 5/2004 Gauchet et al.
 6,733,535 B2 5/2004 Michelson
 6,746,450 B1 6/2004 Wall
 6,752,832 B2 6/2004 Neumann
 6,764,491 B2 7/2004 Frey et al.
 6,770,094 B2 8/2004 Fehling et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,773,437 B2	8/2004	Ogilvie	9,889,022 B2	2/2018	Moskowitz et al.
6,824,564 B2	11/2004	Crozet	9,895,238 B2	2/2018	Moskowitz et al.
6,849,093 B2	2/2005	Michelson	9,907,674 B2	3/2018	Moskowitz
6,852,117 B2	2/2005	Orlowski	10,238,505 B2	3/2019	Moskowitz et al.
6,890,355 B2	5/2005	Michelson	10,307,268 B2	6/2019	Moskowitz et al.
6,904,308 B2	6/2005	Frisch et al.	10,478,319 B2	11/2019	Moskowitz et al.
6,905,512 B2	6/2005	Paes et al.	2002/0068977 A1	6/2002	Jackson
6,953,477 B2	10/2005	Berry	2002/0143338 A1	10/2002	Orbay et al.
6,955,671 B2	10/2005	Uchikubo	2002/0143399 A1	10/2002	Sutcliffe
6,962,606 B2	11/2005	Dove et al.	2002/0161443 A1	10/2002	Michelson
6,972,019 B2	12/2005	Michelson	2003/0130737 A1	7/2003	McGahan et al.
6,974,480 B2	12/2005	Messerli et al.	2003/0149438 A1	8/2003	Nichols et al.
7,001,385 B2	2/2006	Bonutti	2004/0015315 A1	1/2004	Kreider
7,030,904 B2	4/2006	Adair et al.	2004/0039387 A1 *	2/2004	Gause A61B 17/1735
7,033,394 B2	4/2006	Michelson			606/907
7,037,258 B2	5/2006	Chatenever et al.	2004/0088054 A1	5/2004	Berry
7,077,864 B2	7/2006	Byrd et al.	2004/0122424 A1 *	6/2004	Ferree A61F 2/2846
7,097,615 B2	8/2006	Banik et al.			606/279
7,135,043 B2	11/2006	Nakahara et al.	2004/0162558 A1	8/2004	Hegde
7,172,627 B2	2/2007	Fiere et al.	2004/0177531 A1	9/2004	DiBenedetto et al.
7,211,112 B2	5/2007	Baynham et al.	2004/0186482 A1	9/2004	Kolb et al.
7,232,464 B2	6/2007	Mathieu et al.	2004/0186569 A1	9/2004	Berry
7,238,203 B2	7/2007	Bagga et al.	2004/0193272 A1	9/2004	Zubok et al.
7,326,248 B2	2/2008	Michelson	2004/0204717 A1	10/2004	Fanger et al.
7,442,209 B2	10/2008	Michelson	2004/0220571 A1	11/2004	Assaker et al.
7,442,299 B2	10/2008	Lee et al.	2004/0254644 A1	12/2004	Taylor
7,588,573 B2	9/2009	Berry	2005/0027362 A1	2/2005	Williams et al.
7,615,059 B2	11/2009	Watschke et al.	2005/0049590 A1	3/2005	Alleyne et al.
7,618,456 B2	11/2009	Mathieu et al.	2005/0177235 A1	8/2005	Baynham et al.
7,628,816 B2	12/2009	Mageri et al.	2005/0177236 A1	8/2005	Mathieu et al.
7,704,279 B2	4/2010	Moskowitz et al.	2005/0216084 A1	9/2005	Fleischmann
7,727,246 B2	6/2010	Sixto et al.	2005/0256576 A1	11/2005	Moskowitz et al.
7,753,958 B2	7/2010	Gordon et al.	2005/0261769 A1	11/2005	Moskowitz et al.
7,758,617 B2	7/2010	Lott et al.	2005/0273170 A1	12/2005	Navarro et al.
7,763,078 B2	7/2010	Peterman et al.	2005/0278026 A1	12/2005	Gordon et al.
7,776,047 B2	8/2010	Fanger et al.	2006/0022180 A1	2/2006	Selness
7,776,093 B2	8/2010	Wolek	2006/0058876 A1	3/2006	Laurence
7,803,162 B2	9/2010	Marnay et al.	2006/0129244 A1	6/2006	Ensign
7,828,849 B2	11/2010	Lim	2006/0155285 A1	7/2006	Anderson et al.
7,846,207 B2 *	12/2010	Lechmann A61F 2/4465	2006/0217713 A1	9/2006	Serhan
		623/17.11	2006/0241621 A1	10/2006	Moskowitz et al.
7,862,616 B2	1/2011	Lechmann et al.	2006/0253201 A1	11/2006	McLuen
7,875,076 B2	1/2011	Mathieu et al.	2007/0049943 A1	3/2007	Moskowitz et al.
7,887,591 B2	2/2011	Aebi et al.	2007/0167678 A1	7/2007	Moskowitz et al.
7,942,903 B2	5/2011	Moskowitz et al.	2007/0191850 A1	8/2007	Kim
7,959,675 B2	6/2011	Gately	2007/0198089 A1	8/2007	Moskowitz et al.
7,972,363 B2	7/2011	Moskowitz et al.	2007/0213820 A1	9/2007	Magerl et al.
7,985,255 B2	7/2011	Bray et al.	2007/0250167 A1	10/2007	Bray et al.
8,029,512 B2	10/2011	Paltzer	2007/0250172 A1	10/2007	Moskowitz et al.
8,034,060 B2	10/2011	Keren et al.	2007/0270968 A1	11/2007	Baynham
8,105,367 B2	1/2012	Austin et al.	2007/0276498 A1	11/2007	Aebi et al.
8,114,162 B1	2/2012	Bradley	2008/0033440 A1	2/2008	Moskowitz et al.
8,137,405 B2	3/2012	Kostuik et al.	2008/0045968 A1	2/2008	Yu et al.
8,167,949 B2	5/2012	Tyber et al.	2008/0177307 A1	7/2008	Moskowitz et al.
8,172,854 B2	5/2012	Blain et al.	2008/0183293 A1	7/2008	Parry et al.
8,268,000 B2 *	9/2012	Waugh A61F 2/4465	2008/0249569 A1 *	10/2008	Waugh A61F 2/447
		623/17.16			606/249
8,273,127 B2	9/2012	Jones et al.	2008/0249575 A1 *	10/2008	Waugh A61F 2/447
8,328,851 B2	12/2012	Curran			606/301
8,328,872 B2	12/2012	Duffield et al.	2008/0249625 A1	10/2008	Waugh et al.
8,353,913 B2	1/2013	Moskowitz et al.	2008/0281424 A1	11/2008	Parry et al.
8,388,686 B2	3/2013	Aebi et al.	2008/0281425 A1	11/2008	Thalgott et al.
8,403,986 B2	3/2013	Michelson	2009/0030520 A1 *	1/2009	Biedermann A61F 2/447
8,414,651 B2	4/2013	Tyber et al.			606/301
8,419,797 B2	4/2013	Biedermann et al.	2009/0080997 A1	3/2009	Johnson
8,425,607 B2	4/2013	Waugh et al.	2009/0105830 A1	4/2009	Jones et al.
8,540,774 B2	9/2013	Kueenzi et al.	2009/0105831 A1	4/2009	Jones et al.
8,613,761 B2	12/2013	Lindermann et al.	2009/0112271 A1	4/2009	Moskowitz et al.
8,696,681 B2	4/2014	Harris et al.	2009/0182430 A1	7/2009	Tyber et al.
8,728,165 B2	5/2014	Parry et al.	2009/0187218 A1	7/2009	Schaffhausen et al.
8,790,405 B2	7/2014	Biedermann et al.	2009/0210062 A1	8/2009	Thalgott et al.
8,845,731 B2	9/2014	Weiman	2009/0224023 A1	9/2009	Moskowitz et al.
8,882,813 B2	11/2014	Jones et al.	2009/0234455 A1	9/2009	Moskowitz et al.
9,333,095 B2	5/2016	Beaurain et al.	2010/0100138 A1	4/2010	Reynolds
9,393,130 B2	7/2016	Suddaby et al.	2010/0145460 A1	6/2010	McDonough et al.
			2010/0305704 A1	12/2010	Messerli et al.
			2010/0324606 A1	12/2010	Moskowitz et al.
			2011/0125269 A1	5/2011	Moskowitz et al.
			2011/0137349 A1	6/2011	Moskowitz et al.

(56)

References Cited**U.S. PATENT DOCUMENTS**

2011/0172774	A1	7/2011	Varela
2011/0178600	A1	7/2011	Moskowitz et al.
2011/0208312	A1	8/2011	Moskowitz et al.
2011/0288646	A1	11/2011	Moskowitz et al.
2011/0295327	A1	12/2011	Moskowitz et al.
2011/0295371	A1	12/2011	Moskowitz et al.
2011/0307011	A1	12/2011	Moskowitz et al.
2011/0319935	A1	12/2011	Moskowitz et al.
2012/0010714	A1	1/2012	Moskowitz et al.
2012/0271423	A1	10/2012	Wallenstein et al.
2012/0277870	A1	11/2012	Wolters et al.
2012/0323330	A1	12/2012	Kueenzi et al.
2012/0330419	A1	12/2012	Moskowitz et al.
2013/0018468	A1	1/2013	Moskowitz et al.
2013/0018469	A1	1/2013	Moskowitz et al.
2013/0018470	A1	1/2013	Moskowitz et al.
2013/0023991	A1	1/2013	Moskowitz et al.
2013/0023992	A1	1/2013	Moskowitz et al.
2013/0053962	A1	2/2013	Moskowitz et al.
2013/0060339	A1	3/2013	Duffield et al.
2013/0073044	A1	3/2013	Gamache
2013/0173002	A1	7/2013	Moskowitz et al.
2013/0211526	A1	8/2013	Alheid et al.
2013/0282017	A1	10/2013	Moskowitz et al.
2014/0249629	A1	9/2014	Moskowitz et al.
2015/0025637	A1	1/2015	Moskowitz et al.
2015/0105824	A1	4/2015	Moskowitz et al.
2015/0148847	A1	5/2015	Moskowitz et al.
2016/0374830	A1	12/2016	Moskowitz et al.
2017/0252178	A1	9/2017	Moskowitz et al.
2018/0311052	A1	11/2018	Moskowitz
2018/0344477	A1	12/2018	Lechmann et al.

FOREIGN PATENT DOCUMENTS

WO	WO 1999/038463	8/1999
WO	WO 2004/093749	11/2004
WO	WO 2006/091503	8/2006

OTHER PUBLICATIONS

Auguste et al., "Expandable cylindrical cages in the cervical spine: a review of 22 cases," J. Neurosurg. Spine, 4:285-291, 2006, Exhibit No. 1006 in Case IPR2020-01303, U.S. Pat. No. 10,307,268.

Auguste et al., "Expandable cylindrical cages in the cervical spine: a review of 22 cases," J. Neurosurg. Spine, 4:285-291, 2006, Exhibit No. 1006 in Case IPR2020-01304, U.S. Pat. No. 10,307,268.

Auguste et al., "Expandable cylindrical cages in the cervical spine: a review of 22 cases," J. Neurosurg. Spine, 4:285-291, 2006, Exhibit No. 1006 in Case IPR2020-01305, U.S. Pat. No. 10,478,319.

Auguste et al., "Expandable cylindrical cages in the cervical spine: a review of 22 cases," J. Neurosurg. Spine, 4:285-291, 2006, Exhibit No. 1006 in Case IPR2020-01306, U.S. Pat. No. 10,478,319.

Auguste et al., "Expandable cylindrical cages in the cervical spine: a review of 22 cases," J. Neurosurg. Spine, 4:285-291, 2006, Exhibit No. 1006 in Case IPR2020-01307, U.S. Pat. No. 8,353,913.

Auguste et al., "Expandable cylindrical cages in the cervical spine: a review of 22 cases," J. Neurosurg. Spine, 4:285-291, 2006, Exhibit No. 1006 in Case IPR2020-01308, U.S. Pat. No. 9,889,022.

Boakye et al., "The Poly-ether-ether-ketone (PEEK) Spacer," Thieme Medical Publishers, Inc., 333 Seventh Ave., New York, NY 10001, 6 pages, Exhibit No. 1007 in Case IPR2020-01303, U.S. Pat. No. 10,307,268.

Boakye et al., "The Poly-ether-ether-ketone (PEEK) Spacer," Thieme Medical Publishers, Inc., 333 Seventh Ave., New York, NY 10001, 6 pages, Exhibit No. 1007 in Case IPR2020-01304, U.S. Pat. No. 10,307,268.

Boakye et al., "The Poly-ether-ether-ketone (PEEK) Spacer," Thieme Medical Publishers, Inc., 333 Seventh Ave., New York, NY 10001, 6 pages, Exhibit No. 1007 in Case IPR2020-01305, U.S. Pat. No. 10,478,319.

Boakye et al., "The Poly-ether-ether-ketone (PEEK) Spacer," Thieme Medical Publishers, Inc., 333 Seventh Ave., New York, NY 10001, 6 pages, Exhibit No. 1007 in Case IPR2020-01306, U.S. Pat. No. 10,478,319.

Boakye et al., "The Poly-ether-ether-ketone (PEEK) Spacer," Thieme Medical Publishers, Inc., 333 Seventh Ave., New York, NY 10001, 6 pages, Exhibit No. 1007 in Case IPR2020-01307, U.S. Pat. No. 8,353,913.

Boakye et al., "The Poly-ether-ether-ketone (PEEK) Spacer," Thieme Medical Publishers, Inc., 333 Seventh Ave., New York, NY 10001, 6 pages, Exhibit No. 1007 in Case IPR2020-01308, U.S. Pat. No. 9,889,022.

Centinel Spine, [https://www.centinelspine.com/corp_producthistory.php, Retrieved on Jun. 4, 2020 11:48:58 PM], 7 pages, Exhibit No. 1009 in Case IPR2020-01303, U.S. Pat. No. 10,307,268.

Centinel Spine, [https://www.centinelspine.com/corp_producthistory.php, Retrieved on Jun. 4, 2020 11:48:58 PM], 7 pages, Exhibit No. 1009 in Case IPR2020-01304, U.S. Pat. No. 10,307,268.

Centinel Spine, [https://www.centinelspine.com/corp_producthistory.php, Retrieved on Jun. 4, 2020 11:48:58 PM], 7 pages, Exhibit No. 1009 in Case IPR2020-01305, U.S. Pat. No. 10,478,319.

Centinel Spine, [https://www.centinelspine.com/corp_producthistory.php, Retrieved on Jun. 4, 2020 11:48:58 PM], 7 pages, Exhibit No. 1009 in Case IPR2020-01306, U.S. Pat. No. 10,478,319.

Centinel Spine, [https://www.centinelspine.com/corp_producthistory.php, Retrieved on Jun. 4, 2020 11:48:58 PM], 7 pages, Exhibit No. 1009 in Case IPR2020-01307, U.S. Pat. No. 8,353,913.

Centinel Spine, [https://www.centinelspine.com/corp_producthistory.php, Retrieved on Jun. 4, 2020 11:48:58 PM], 7 pages, Exhibit No. 1009 in Case IPR2020-01308, U.S. Pat. No. 9,889,022.

Cheung and Leong, "Spinal Instrumentation Overview in Lumbar Degenerative Disorders: Cages," Spinal Instrumentation Overview, Ch. 26, 8 pages, Exhibit No. 1008 in Case IPR2020-01303, U.S. Pat. No. 10,307,268.

Cheung and Leong, "Spinal Instrumentation Overview in Lumbar Degenerative Disorders: Cages," Spinal Instrumentation Overview, Ch. 26, 8 pages, Exhibit No. 1008 in Case IPR2020-01304, U.S. Pat. No. 10,307,268.

Cheung and Leong, "Spinal Instrumentation Overview in Lumbar Degenerative Disorders: Cages," Spinal Instrumentation Overview, Ch. 26, 8 pages, Exhibit No. 1008 in Case IPR2020-01305, U.S. Pat. No. 10,478,319.

Cheung and Leong, "Spinal Instrumentation Overview in Lumbar Degenerative Disorders: Cages," Spinal Instrumentation Overview, Ch. 26, 8 pages, Exhibit No. 1008 in Case IPR2020-01306, U.S. Pat. No. 10,478,319.

Cheung and Leong, "Spinal Instrumentation Overview in Lumbar Degenerative Disorders: Cages," Spinal Instrumentation Overview, Ch. 26, 8 pages, Exhibit No. 1008 in Case IPR2020-01307, U.S. Pat. No. 8,353,913.

Cheung and Leong, "Spinal Instrumentation Overview in Lumbar Degenerative Disorders: Cages," Spinal Instrumentation Overview, Ch. 26, 8 pages, Exhibit No. 1008 in Case IPR2020-01308, U.S. Pat. No. 9,889,022.

Dickman, "Internal Fixation and Fusion of the Lumbar Spine Using Threaded Interbody Cages," [https://www.barrowneuro.org/education/grand-rounds-publications-and-media/barrow-quarterly/, Retrieved on Jun. 20, 2020], 41 pages, Exhibit No. 1010 in Case IPR2020-01303, U.S. Pat. No. 10,307,268.

Dickman, "Internal Fixation and Fusion of the Lumbar Spine Using Threaded Interbody Cages," [https://www.barrowneuro.org/education/grand-rounds-publications-and-media/barrow-quarterly/, Retrieved on Jun. 20, 2020], 41 pages, Exhibit No. 1010 in Case IPR2020-01304, U.S. Pat. No. 10,307,268.

Dickman, "Internal Fixation and Fusion of the Lumbar Spine Using Threaded Interbody Cages," [https://www.barrowneuro.org/education/grand-rounds-publications-and-media/barrow-quarterly/, Retrieved on Jun. 20, 2020], 41 pages, Exhibit No. 1010 in Case IPR2020-01305, U.S. Pat. No. 10,478,319.

Dickman, "Internal Fixation and Fusion of the Lumbar Spine Using Threaded Interbody Cages," [https://www.barrowneuro.org/education/grand-rounds-publications-and-media/barrow-quarterly/, Retrieved

(56)

References Cited**OTHER PUBLICATIONS**

on Jun. 20, 2020], 41 pages, Exhibit No. 1010 in Case IPR2020-01306, U.S. Pat. No. 10,478,319.

Dickman, "Internal Fixation and Fusion of the Lumbar Spine Using Threaded Interbody Cages," [https://www.barrowneuro.org/education/grand-rounds-publications-and-media/barrow-quarterly/], Retrieved on Jun. 20, 2020], 41 pages, Exhibit No. 1010 in Case IPR2020-01307, U.S. Pat. No. 8,353,913.

Dickman, "Internal Fixation and Fusion of the Lumbar Spine Using Threaded Interbody Cages," [https://www.barrowneuro.org/education/grand-rounds-publications-and-media/barrow-quarterly/], Retrieved on Jun. 20, 2020], 41 pages, Exhibit No. 1010 in Case IPR2020-01308, U.S. Pat. No. 9,889,022.

Dieter Grob et al., "Clinical Experience With the Dynesys Semirigid Fixation System for the Lumbar Spine," *Spine*, vol. 30, No. 3, 2005, pp. 324-331.

Dryer, "Affinity Anterior Cervical Cage System," Thieme Medical Publisher, Inc., New York, New York, 2005, 9 pages, Exhibit No. 1011 in Case IPR2020-01303, U.S. Pat. No. 10,307,268.

Dryer, "Affinity Anterior Cervical Cage System," Thieme Medical Publisher, Inc., New York, New York, 2005, 9 pages, Exhibit No. 1011 in Case IPR2020-01304, U.S. Pat. No. 10,307,268.

Dryer, "Affinity Anterior Cervical Cage System," Thieme Medical Publisher, Inc., New York, New York, 2005, 9 pages, Exhibit No. 1011 in Case IPR2020-01305, U.S. Pat. No. 10,478,319.

Dryer, "Affinity Anterior Cervical Cage System," Thieme Medical Publisher, Inc., New York, New York, 2005, 9 pages, Exhibit No. 1011 in Case IPR2020-01306, U.S. Pat. No. 10,478,319.

Dryer, "Affinity Anterior Cervical Cage System," Thieme Medical Publisher, Inc., New York, New York, 2005, 9 pages, Exhibit No. 1011 in Case IPR2020-01307, U.S. Pat. No. 8,353,913.

Dryer, "Affinity Anterior Cervical Cage System," Thieme Medical Publisher, Inc., New York, New York, 2005, 9 pages, Exhibit No. 1011 in Case IPR2020-01308, U.S. Pat. No. 9,889,022.

E.K. Wai et al., "Disk Replacement Arthroplasties: Can The Success of Hip and Knee Replacements be Repeated in the Spine?," *Seminars in Spine Surgery*, vol. 15, No. 4 (Dec. 2003), pp. 473-482.

Folman et al., "Posterior Lumbar Interbody Fusion for Degenerative Disc Disease Using a Minimally Invasive B-Twin Expandable Spinal Spacer," *Journal of Spinal Disorders & Techniques*, Oct. 2003, 16(5):455-60, Exhibit No. 1012 in Case IPR2020-01303, U.S. Pat. No. 10,307,268.

Folman et al., "Posterior Lumbar Interbody Fusion for Degenerative Disc Disease Using a Minimally Invasive B-Twin Expandable Spinal Spacer," *Journal of Spinal Disorders & Techniques*, Oct. 2003, 16(5):455-60, Exhibit No. 1012 in Case IPR2020-01304, U.S. Pat. No. 10,307,268.

Folman et al., "Posterior Lumbar Interbody Fusion for Degenerative Disc Disease Using a Minimally Invasive B-Twin Expandable Spinal Spacer," *Journal of Spinal Disorders & Techniques*, Oct. 2003, 16(5):455-60, Exhibit No. 1012 in Case IPR2020-01305, U.S. Pat. No. 10,478,319.

Folman et al., "Posterior Lumbar Interbody Fusion for Degenerative Disc Disease Using a Minimally Invasive B-Twin Expandable Spinal Spacer," *Journal of Spinal Disorders & Techniques*, Oct. 2003, 16(5):455-60, Exhibit No. 1012 in Case IPR2020-01306, U.S. Pat. No. 10,478,319.

Folman et al., "Posterior Lumbar Interbody Fusion for Degenerative Disc Disease Using a Minimally Invasive B-Twin Expandable Spinal Spacer," *Journal of Spinal Disorders & Techniques*, Oct. 2003, 16(5):455-60, Exhibit No. 1012 in Case IPR2020-01307, U.S. Pat. No. 8,353,913.

Folman et al., "Posterior Lumbar Interbody Fusion for Degenerative Disc Disease Using a Minimally Invasive B-Twin Expandable Spinal Spacer," *Journal of Spinal Disorders & Techniques*, Oct. 2003, 16(5):455-60, Exhibit No. 1012 in Case IPR2020-01308, U.S. Pat. No. 9,889,022.

Globus Medical, Inc., Petitioner v. *Moskowitz Family LLC*, Patent Owner Petition for Inter Partes Review of U.S. Pat. No. 10,307,268 Pursuant to 35 U.S.C. §§ 311-319 and 37 C.F.R. § 42, dated Jul. 21, 2020, 75 pages.

Globus Medical, Inc., Petitioner v. *Moskowitz Family LLC*, Patent Owner Petition for Inter Partes Review of U.S. Pat. No. 10,307,268 Pursuant to 35 U.S.C. §§ 311-319 and 37 C.F.R. § 42, dated Jul. 21, 2020, 79 pages.

Globus Medical, Inc., Petitioner v. *Moskowitz Family LLC*, Patent Owner Petition for Inter Partes Review of U.S. Pat. No. 10,478,319 Pursuant to 35 U.S.C. §§ 311-319 and 37 C.F.R. § 42, dated Jul. 21, 2020, 78 pages.

Globus Medical, Inc., Petitioner v. *Moskowitz Family LLC*, Patent Owner Petition for Inter Partes Review of U.S. Pat. No. 10,478,319 Pursuant to 35 U.S.C. §§ 311-319 and 37 C.F.R. § 42, dated Jul. 21, 2020, 83 pages.

Globus Medical, Inc., Petitioner v. *Moskowitz Family LLC*, Patent Owner Petition for Inter Partes Review of U.S. Pat. No. 8,353,913 Pursuant to 35 U.S.C. §§ 311-319 and 37 C.F.R. § 42, dated Jul. 21, 2020, 69 pages.

Globus Medical, Inc., Petitioner v. *Moskowitz Family LLC*, Patent Owner Petition for Inter Partes Review of U.S. Pat. No. 9,889,022 Pursuant to 35 U.S.C. §§ 311-319 and 37 C.F.R. § 42, dated Jul. 21, 2020, 68 pages.

Globus Medical, Inc., v. *Moskowitz Family LLC*, "Decision Denying Institution of Inter Partes Review 35 U.S.C. § 314", IPR2020-01303, U.S. Pat. No. 10,307,268, Paper 7, dated Jan. 26, 2021, 38 pages.

Globus Medical, Inc., v. *Moskowitz Family LLC*, "Decision Denying Institution of Inter Partes Review 35 U.S.C. § 314", IPR2020-01304, U.S. Pat. No. 10,307,268, Paper 7, dated Jan. 27, 2021, 34 pages.

Globus Medical, Inc., v. *Moskowitz Family LLC*, "Decision Denying Institution of Inter Partes Review 35 U.S.C. § 314", IPR2020-01305, U.S. Pat. No. 10,478,319, Paper 7, dated Jan. 8, 2021, 31 pages.

Globus Medical, Inc., v. *Moskowitz Family LLC*, "Decision Denying Institution of Inter Partes Review 35 U.S.C. § 314", IPR2020-01306, U.S. Pat. No. 10,478,319, Paper 7, dated Jan. 8, 2021, 34 pages.

Globus Medical, Inc., v. *Moskowitz Family LLC*, "Decision Denying Institution of Inter Partes Review 35 U.S.C. § 314", IPR2020-01307, U.S. Pat. No. 8,353,913, Paper 7, dated Dec. 21, 2020, 18 pages.

Globus Medical, Inc., v. *Moskowitz Family LLC*, "Decision Denying Institution of Inter Partes Review 35 U.S.C. § 314", IPR2020-01308, U.S. Pat. No. 9,889,022, Paper 8, dated Jan. 25, 2021, 24 pages.

Globus Medical, Inc., v. *Moskowitz Family LLC*, "Declaration of Jorge A. Ochoa, Ph.D., P.E.," Case IPR2020-01303 & 01304, U.S. Pat. No. 10,307,268, dated Jul. 21, 2020, 127 pages (Exhibit No. 1003).

Globus Medical, Inc., v. *Moskowitz Family LLC*, "Declaration of Jorge A. Ochoa, Ph.D., P.E.," Case IPR2020-01305 & 01306, U.S. Pat. No. 10,478,319, dated Jul. 21, 2020, 141 pages (Exhibit No. 1003).

Globus Medical, Inc., v. *Moskowitz Family LLC*, "Declaration of Jorge A. Ochoa, Ph.D., P.E.," Case IPR2020-01307, U.S. Pat. No. 8,353,913, dated Jul. 21, 2020, 67 pages (Exhibit No. 1003).

Globus Medical, Inc., v. *Moskowitz Family LLC*, "Declaration of Jorge A. Ochoa, Ph.D., P.E.," Case IPR2020-01308, U.S. Pat. No. 9,889,022, dated Jul. 21, 2020, 65 pages (Exhibit No. 1003).

Guyver and Ohnmeiss, "Degenerative Disc Disease: Fusion Cages and Dowels," Lippincott Williams & Wilkins, Philadelphia, PA, 2004, Ch. 35, 12 pages, Exhibit No. 1013 in Case IPR2020-01303, U.S. Pat. No. 10,307,268.

Guyver and Ohnmeiss, "Degenerative Disc Disease: Fusion Cages and Dowels," Lippincott Williams & Wilkins, Philadelphia, PA, 2004, Ch. 35, 12 pages, Exhibit No. 1013 in Case IPR2020-01304, U.S. Pat. No. 10,307,268.

(56)

References Cited**OTHER PUBLICATIONS**

- Guyer and Ohnmeiss, "Degenerative Disc Disease: Fusion Cages and Dowels," Lippincott Williams & Wilkins, Philadelphia, PA, 2004, Ch. 35, 12 pages, Exhibit No. 1013 in Case IPR2020-01305, U.S. Pat. No. 10,478,319.
- Guyer and Ohnmeiss, "Degenerative Disc Disease: Fusion Cages and Dowels," Lippincott Williams & Wilkins, Philadelphia, PA, 2004, Ch. 35, 12 pages, Exhibit No. 1013 in Case IPR2020-01306, U.S. Pat. No. 10,478,319.
- Guyer and Ohnmeiss, "Degenerative Disc Disease: Fusion Cages and Dowels," Lippincott Williams & Wilkins, Philadelphia, PA, 2004, Ch. 35, 12 pages, Exhibit No. 1013 in Case IPR2020-01307, U.S. Pat. No. 8,353,913.
- Guyer and Ohnmeiss, "Degenerative Disc Disease: Fusion Cages and Dowels," Lippincott Williams & Wilkins, Philadelphia, PA, 2004, Ch. 35, 12 pages, Exhibit No. 1013 in Case IPR2020-01308, U.S. Pat. No. 9,889,022.
- Holte et al., "Anterior lumbar fusion using a hybrid interbody graft," *Eur. Spine J.*, 3:32-38, 1994, Exhibit No. 1014 in Case IPR2020-01303, U.S. Pat. No. 10,307,268.
- Holte et al., "Anterior lumbar fusion using a hybrid interbody graft," *Eur. Spine J.*, 3:32-38, 1994, Exhibit No. 1014 in Case IPR2020-01304, U.S. Pat. No. 10,307,268.
- Holte et al., "Anterior lumbar fusion using a hybrid interbody graft," *Eur. Spine J.*, 3:32-38, 1994, Exhibit No. 1014 in Case IPR2020-01305, U.S. Pat. No. 10,478,319.
- Holte et al., "Anterior lumbar fusion using a hybrid interbody graft," *Eur. Spine J.*, 3:32-38, 1994, Exhibit No. 1014 in Case IPR2020-01306, U.S. Pat. No. 10,478,319.
- Holte et al., "Anterior lumbar fusion using a hybrid interbody graft," *Eur. Spine J.*, 3:32-38, 1994, Exhibit No. 1014 in Case IPR2020-01307, U.S. Pat. No. 8,353,913.
- Holte et al., "Anterior lumbar fusion using a hybrid interbody graft," *Eur. Spine J.*, 3:32-38, 1994, Exhibit No. 1014 in Case IPR2020-01308, U.S. Pat. No. 9,889,022.
- International Search Report (ISR) and Written Opinion of the International Searching Authority, dated Dec. 3, 2007, International Application No. PCT/US 07/05005.
- International Search Report (ISR) and Written Opinion of the International Searching Authority, dated Jul. 9, 2008, International Application No. PCT/US2007021013.
- International Search Report (ISR) and Written Opinion of the International Searching Authority, dated May 21, 2008, International Application No. PCT/US2007/021015.
- Lane et al., "Transperitoneal Approach to the Intervertebral Disc in the Lumbar Area," *Annals of Surgery*, Mar. 1948, 127(3):537, Exhibit No. 1015 in Case IPR2020-01303, U.S. Pat. No. 10,307,268.
- Lane et al., "Transperitoneal Approach to the Intervertebral Disc in the Lumbar Area," *Annals of Surgery*, Mar. 1948, 127(3):537, Exhibit No. 1015 in Case IPR2020-01304, U.S. Pat. No. 10,307,268.
- Lane et al., "Transperitoneal Approach to the Intervertebral Disc in the Lumbar Area," *Annals of Surgery*, Mar. 1948, 127(3):537, Exhibit No. 1015 in Case IPR2020-01305, U.S. Pat. No. 10,478,319.
- Lane et al., "Transperitoneal Approach to the Intervertebral Disc in the Lumbar Area," *Annals of Surgery*, Mar. 1948, 127(3):537, Exhibit No. 1015 in Case IPR2020-01306, U.S. Pat. No. 10,478,319.
- Lane et al., "Transperitoneal Approach to the Intervertebral Disc in the Lumbar Area," *Annals of Surgery*, Mar. 1948, 127(3):537, Exhibit No. 1015 in Case IPR2020-01307, U.S. Pat. No. 8,353,913.
- Lane et al., "Transperitoneal Approach to the Intervertebral Disc in the Lumbar Area," *Annals of Surgery*, Mar. 1948, 127(3):537, Exhibit No. 1015 in Case IPR2020-01308, U.S. Pat. No. 9,889,022.
- Michelson et al., "BAK/C Interbody Fusion System: A Threaded Cylindrical Cage for Cervical Fusion," Thieme Medical Publisher, Inc., New York, New York, 2005, 10 pages, Exhibit No. 1016 in Case IPR2020-01303, U.S. Pat. No. 10,307,268.
- Michelson et al., "BAK/C Interbody Fusion System: A Threaded Cylindrical Cage for Cervical Fusion," Thieme Medical Publisher, Inc., New York, New York, 2005, 10 pages, Exhibit No. 1016 in Case IPR2020-01306, U.S. Pat. No. 10,478,319.
- Michelson et al., "BAK/C Interbody Fusion System: A Threaded Cylindrical Cage for Cervical Fusion," Thieme Medical Publisher, Inc., New York, New York, 2005, 10 pages, Exhibit No. 1016 in Case IPR2020-01307, U.S. Pat. No. 8,353,913.
- Michelson et al., "BAK/C Interbody Fusion System: A Threaded Cylindrical Cage for Cervical Fusion," Thieme Medical Publisher, Inc., New York, New York, 2005, 10 pages, Exhibit No. 1016 in Case IPR2020-01308, U.S. Pat. No. 9,889,022.
- Prpa et al., "Lumbar Interbody Cages," *Sug. Pro.*, Ch. 41, pp. 489-502, 2005, Exhibit No. 1017 in Case IPR2020-01303, U.S. Pat. No. 10,307,268.
- Prpa et al., "Lumbar Interbody Cages," *Sug. Pro.*, Ch. 41, pp. 489-502, 2005, Exhibit No. 1017 in Case IPR2020-01304, U.S. Pat. No. 10,307,268.
- Prpa et al., "Lumbar Interbody Cages," *Sug. Pro.*, Ch. 41, pp. 489-502, 2005, Exhibit No. 1017 in Case IPR2020-01305, U.S. Pat. No. 10,478,319.
- Prpa et al., "Lumbar Interbody Cages," *Sug. Pro.*, Ch. 41, pp. 489-502, 2005, Exhibit No. 1017 in Case IPR2020-01306, U.S. Pat. No. 10,478,319.
- Prpa et al., "Lumbar Interbody Cages," *Sug. Pro.*, Ch. 41, pp. 489-502, 2005, Exhibit No. 1017 in Case IPR2020-01307, U.S. Pat. No. 8,353,913.
- Prpa et al., "Lumbar Interbody Cages," *Sug. Pro.*, Ch. 41, pp. 489-502, 2005, Exhibit No. 1017 in Case IPR2020-01308, U.S. Pat. No. 9,889,022.
- Richard D. Guyer et al., "Intervertebral Disc Prostheses," *Spine Journal*, vol. 28, No. 15S, Supp. to Aug. 1, 2003, pp. S15-S23.
- Ryu and Kim, "Cervical Carbon Fiber Interbody Fusion Cage: Bengal System," Thieme Medical Publisher, Inc., New York, New York, 2005, 8 pages, Exhibit No. 1018 in Case IPR2020-01303, U.S. Pat. No. 10,307,268.
- Ryu and Kim, "Cervical Carbon Fiber Interbody Fusion Cage: Bengal System," Thieme Medical Publisher, Inc., New York, New York, 2005, 8 pages, Exhibit No. 1018 in Case IPR2020-01304, U.S. Pat. No. 10,307,268.
- Ryu and Kim, "Cervical Carbon Fiber Interbody Fusion Cage: Bengal System," Thieme Medical Publisher, Inc., New York, New York, 2005, 8 pages, Exhibit No. 1018 in Case IPR2020-01305, U.S. Pat. No. 10,478,319.
- Ryu and Kim, "Cervical Carbon Fiber Interbody Fusion Cage: Bengal System," Thieme Medical Publisher, Inc., New York, New York, 2005, 8 pages, Exhibit No. 1018 in Case IPR2020-01306, U.S. Pat. No. 10,478,319.
- Ryu and Kim, "Cervical Carbon Fiber Interbody Fusion Cage: Bengal System," Thieme Medical Publisher, Inc., New York, New York, 2005, 8 pages, Exhibit No. 1018 in Case IPR2020-01307, U.S. Pat. No. 8,353,913.
- Ryu and Kim, "Cervical Carbon Fiber Interbody Fusion Cage: Bengal System," Thieme Medical Publisher, Inc., New York, New York, 2005, 8 pages, Exhibit No. 1018 in Case IPR2020-01308, U.S. Pat. No. 9,889,022.
- Schimmel et al., "PEEK Cages in Lumbar Fusion," *Clin. Spine Surg.*, 29(5):E252-E258, Jun. 2016, Exhibit No. 1019 in Case IPR2020-01303, U.S. Pat. No. 10,307,268.
- Schimmel et al., "PEEK Cages in Lumbar Fusion," *Clin. Spine Surg.*, 29(5):E252-E258, Jun. 2016, Exhibit No. 1019 in Case IPR2020-01304, U.S. Pat. No. 10,307,268.
- Schimmel et al., "PEEK Cages in Lumbar Fusion," *Clin. Spine Surg.*, 29(5):E252-E258, Jun. 2016, Exhibit No. 1019 in Case IPR2020-01305, U.S. Pat. No. 10,478,319.
- Schimmel et al., "PEEK Cages in Lumbar Fusion," *Clin. Spine Surg.*, 29(5):E252-E258, Jun. 2016, Exhibit No. 1019 in Case IPR2020-01306, U.S. Pat. No. 10,478,319.

(56)

References Cited**OTHER PUBLICATIONS**

Schimmel et al., "PEEK Cages in Lumbar Fusion," Clin. Spine Surg., 29(5):E252-E258, Jun. 2016, Exhibit No. 1019 in Case IPR2020-01307, U.S. Pat. No. 8,353,913.

Schimmel et al., "PEEK Cages in Lumbar Fusion," Clin. Spine Surg., 29(5):E252-E258, Jun. 2016, Exhibit No. 1019 in Case IPR2020-01308, U.S. Pat. No. 9,889,022.

Synfix, "Evolution System," Online Product, Date, 1 page, Exhibit No. 1021 in Case IPR2020-01303, U.S. Pat. No. 10,307,268.

Synfix, "Evolution System," Online Product, Date, 1 page, Exhibit No. 1021 in Case IPR2020-01304, U.S. Pat. No. 10,307,268.

Synfix, "Evolution System," Online Product, Date, 1 page, Exhibit No. 1021 in Case IPR2020-01305, U.S. Pat. No. 10,478,319.

Synfix, "Evolution System," Online Product, Date, 1 page, Exhibit No. 1021 in Case IPR2020-01306, U.S. Pat. No. 10,478,319.

Synfix, "Evolution System," Online Product, Date, 1 page, Exhibit No. 1021 in Case IPR2020-01307, U.S. Pat. No. 8,353,913.

Synfix, "Evolution System," Online Product, Date, 1 page, Exhibit No. 1021 in Case IPR2020-01308, U.S. Pat. No. 9,889,022.

Synthes "SynFix-LR. Implant and instrumentation for stand alone anterior lumbar interbody fusion (ALIF)," 2006, 26 pages, Exhibit No. 1020 in Case IPR2020-01303, U.S. Pat. No. 10,307,268.

Synthes "SynFix-LR. Implant and instrumentation for stand alone anterior lumbar interbody fusion (ALIF)," 2006, 26 pages, Exhibit No. 1020 in Case IPR2020-01304, U.S. Pat. No. 10,307,268.

Synthes "SynFix-LR. Implant and instrumentation for stand alone anterior lumbar interbody fusion (ALIF)," 2006, 26 pages, Exhibit No. 1020 in Case IPR2020-01305, U.S. Pat. No. 10,478,319.

Synthes "SynFix-LR. Implant and instrumentation for stand alone anterior lumbar interbody fusion (ALIF)," 2006, 26 pages, Exhibit No. 1020 in Case IPR2020-01306, U.S. Pat. No. 10,478,319.

Synthes "SynFix-LR. Implant and instrumentation for stand alone anterior lumbar interbody fusion (ALIF)," 2006, 26 pages, Exhibit No. 1020 in Case IPR2020-01307, U.S. Pat. No. 8,353,913.

Synthes "SynFix-LR. Implant and instrumentation for stand alone anterior lumbar interbody fusion (ALIF)," 2006, 26 pages, Exhibit No. 1020 in Case IPR2020-01308, U.S. Pat. No. 9,889,022.

Vincent C. Traynelis, "Prosthetics and Biologics: The Wave of the Future," Clinical Neurosurgery, vol. 50, Proceedings of the Congress of Neurological Surgeons, Philadelphia, PA 2002, Chapter 9, pp. 207-219.

Wagner et al., "Surgical Stabilization of the Equine Cervical Spine," Veterinary Surg., 8:1-6, Jan.-Mar. 1979, Exhibit No. 1023 in Case IPR2020-01303, U.S. Pat. No. 10,307,268.

Wagner et al., "Surgical Stabilization of the Equine Cervical Spine," Veterinary Surg., 8:1-6, Jan.-Mar. 1979, Exhibit No. 1023 in Case IPR2020-01304, U.S. Pat. No. 10,307,268.

Wagner et al., "Surgical Stabilization of the Equine Cervical Spine," Veterinary Surg., 8:1-6, Jan.-Mar. 1979, Exhibit No. 1023 in Case IPR2020-01305, U.S. Pat. No. 10,478,319.

Wagner et al., "Surgical Stabilization of the Equine Cervical Spine," Veterinary Surg., 8:1-6, Jan.-Mar. 1979, Exhibit No. 1023 in Case IPR2020-01306, U.S. Pat. No. 10,478,319.

Wagner et al., "Surgical Stabilization of the Equine Cervical Spine," Veterinary Surg., 8:1-6, Jan.-Mar. 1979, Exhibit No. 1023 in Case IPR2020-01307, U.S. Pat. No. 8,353,913.

Wagner et al., "Surgical Stabilization of the Equine Cervical Spine," Veterinary Surg., 8:1-6, Jan.-Mar. 1979, Exhibit No. 1023 in Case IPR2020-01308, U.S. Pat. No. 9,889,022.

Weiner and Fraser, "Spine Update Lumbar Interbody Cages," Spine, 23(5):634-640, 1998, Exhibit No. 1024 in Case IPR2020-01303, U.S. Pat. No. 10,307,268.

Weiner and Fraser, "Spine Update Lumbar Interbody Cages," Spine, 23(5):634-640, 1998, Exhibit No. 1024 in Case IPR2020-01304, U.S. Pat. No. 10,307,268.

Weiner and Fraser, "Spine Update Lumbar Interbody Cages," Spine, 23(5):634-640, 1998, Exhibit No. 1024 in Case IPR2020-01305, U.S. Pat. No. 10,478,319.

Weiner and Fraser, "Spine Update Lumbar Interbody Cages," Spine, 23(5):634-640, 1998, Exhibit No. 1024 in Case IPR2020-01306, U.S. Pat. No. 10,478,319.

Weiner and Fraser, "Spine Update Lumbar Interbody Cages," Spine, 23(5):634-640, 1998, Exhibit No. 1024 in Case IPR2020-01307, U.S. Pat. No. 8,353,913.

Weiner and Fraser, "Spine Update Lumbar Interbody Cages," Spine, 23(5):634-640, 1998, Exhibit No. 1024 in Case IPR2020-01308, U.S. Pat. No. 9,889,022.

Wilke et al., "Primary stabilizing effect of interbody fusion devices for the cervical spine: an in vitro comparison between three different cage types and bone cement," Eur. Spine J., 2000, 9:410-416, Exhibit No. 1025 in Case IPR2020-01303, U.S. Pat. No. 10,307,268.

Wilke et al., "Primary stabilizing effect of interbody fusion devices for the cervical spine: an in vitro comparison between three different cage types and bone cement," Eur. Spine J., 2000, 9:410-416, Exhibit No. 1025 in Case IPR2020-01304, U.S. Pat. No. 10,307,268.

Wilke et al., "Primary stabilizing effect of interbody fusion devices for the cervical spine: an in vitro comparison between three different cage types and bone cement," Eur. Spine J., 2000, 9:410-416, Exhibit No. 1025 in Case IPR2020-01305, U.S. Pat. No. 10,478,319.

Wilke et al., "Primary stabilizing effect of interbody fusion devices for the cervical spine: an in vitro comparison between three different cage types and bone cement," Eur. Spine J., 2000, 9:410-416, Exhibit No. 1025 in Case IPR2020-01306, U.S. Pat. No. 10,478,319.

Wilke et al., "Primary stabilizing effect of interbody fusion devices for the cervical spine: an in vitro comparison between three different cage types and bone cement," Eur. Spine J., 2000, 9:410-416, Exhibit No. 1025 in Case IPR2020-01307, U.S. Pat. No. 8,353,913.

Wilke et al., "Primary stabilizing effect of interbody fusion devices for the cervical spine: an in vitro comparison between three different cage types and bone cement," Eur. Spine J., 2000, 9:410-416, Exhibit No. 1025 in Case IPR2020-01308, U.S. Pat. No. 9,889,022.

Wiseman et al., "Posterior Lumbar Interbody Fusion," Surgical Procedures, Ch. 39, 24 pages, Exhibit No. 1026 in Case IPR2020-01303, U.S. Pat. No. 10,307,268.

Wiseman et al., "Posterior Lumbar Interbody Fusion," Surgical Procedures, Ch. 39, 24 pages, Exhibit No. 1026 in Case IPR2020-01304, U.S. Pat. No. 10,307,268.

Wiseman et al., "Posterior Lumbar Interbody Fusion," Surgical Procedures, Ch. 39, 24 pages, Exhibit No. 1026 in Case IPR2020-01305, U.S. Pat. No. 10,478,319.

Wiseman et al., "Posterior Lumbar Interbody Fusion," Surgical Procedures, Ch. 39, 24 pages, Exhibit No. 1026 in Case IPR2020-01306, U.S. Pat. No. 10,478,319.

Wiseman et al., "Posterior Lumbar Interbody Fusion," Surgical Procedures, Ch. 39, 24 pages, Exhibit No. 1026 in Case IPR2020-01307, U.S. Pat. No. 8,353,913.

Wiseman et al., "Posterior Lumbar Interbody Fusion," Surgical Procedures, Ch. 39, 24 pages, Exhibit No. 1026 in Case IPR2020-01308, U.S. Pat. No. 9,889,022.

* cited by examiner




Fig. 1A




Fig. 1B




Fig. 1C




Fig. 1D




Fig. 1E




Fig. 2A




Fig. 2B




Fig. 2C




Fig. 3




Fig. 4A




Fig. 4B




FIG. 4C




Fig. 5A




Fig. 5B




Fig. 5C




Fig. 5D




Fig. 5E




Fig. 5F




Fig. 5G




FIG. 5H




FIG. 5I




Fig. 6A




Fig. 6B




Fig. 7A




Fig. 7B




Fig. 8A




Fig. 8B




Fig. 8C




Fig. 9A




Fig. 9B




Fig. 10A




Fig. 10B




Fig. 10C




Fig. 11A




Fig. 11B




Fig. 11C




Fig. 12A




Fig. 12B

1

INTERVERTEBRAL IMPLANT AND TOOL ASSEMBLY

This application is a Continuation Application of U.S. application Ser. No. 16/744,755, filed Jan. 16, 2020, which is a Continuation Application of U.S. application Ser. No. 15/944,117, filed Apr. 3, 2018 (now U.S. Pat. No. 10,537,442), which is a Continuation Application of U.S. application Ser. No. 15/894,471, filed Feb. 12, 2018 (now U.S. Pat. No. 10,390,969), which is a Continuation of U.S. application Ser. No. 13/210,157, filed Aug. 15, 2011 (now U.S. Pat. No. 9,889,022), which is a Continuation of U.S. application Ser. No. 13/084,543, filed Apr. 11, 2011 (now U.S. Pat. No. 8,353,913) and Ser. No. 13/108,982, filed May 16, 2011 (now U.S. Pat. No. 9,005,293).

U.S. application Ser. No. 13/084,543 is a Continuation of Ser. No. 11/842,855, filed Aug. 21, 2007 (now U.S. Pat. No. 7,942,903). U.S. application Ser. No. 13/108,982 is a Continuation of Ser. No. 11/842,855, filed Aug. 21, 2007 (now U.S. Pat. No. 7,942,903), which is a Continuation-in-Part of U.S. application Ser. No. 11/536,815, filed Sep. 29, 2006 (now U.S. Pat. No. 7,846,188), which is a Continuation-in-Part of U.S. application Ser. No. 11/208,644, filed Aug. 23, 2005 (now U.S. Pat. No. 7,704,279), which claims priority of U.S. Provisional Application Ser. No. 60/670,231, filed Apr. 12, 2005; the entire contents of all the above identified patent applications are hereby incorporated by reference.

FIELD OF INVENTION

The present invention relates to a unique universal bidirectional screw (BDS) system, and in particular its application to the spine, also referred to as bi-directional fixing transvertebral (BDFT) screws which can be used as a stand-alone intervertebral device which combines the dual functions of an intervertebral spacer which can be filled with bone fusion material(s), as well as a transvertebral bone fusion screw apparatus. In the posterior lumbosacral and thoracic spine, BDFT screw/box constructs can be used independently or supplemented with a novel horizontal mini-plate which prevents upward bone graft intrusion into the thecal sac and nerves. In the anterior lumbosacral spine BDFT screw box constructs can be inserted into and supplemented by a circumferential cage. These posteriorly and anteriorly placed stand-alone intervertebral body fusion constructs may obviate the need for supplemental pedicle screw fixation.

The present invention also relates to stand-alone or supplemental posterior cervical and lumbar calibrated interarticular joint stapling devices which may obviate and/or lessen the need for supplemental pedicle screw fixation.

DESCRIPTION OF THE RELEVANT ART

The history and evolution of instrumented spinal fusion in the entire human spine has been reviewed in our two prior copending application Ser. No. 11/536,815, filed on Sep. 29, 2006, and Ser. No. 11/208,644, filed on Aug. 23, 2005, the related contents of which are hereby incorporated by reference. Currently the majority of posterior cervical and almost all anterior and posterior lumbosacral and thoracic fusion techniques are typically supplemented with pedicle screw placement. Complications of pedicle screw placement in cervical, thoracic and lumbar spine include duration of procedure, significant tissue dissection and muscle retraction, misplaced screws with neural and/or vascular injury, excessive blood loss, need for transfusions, prolonged

2

recovery, incomplete return to work, and excess rigidity leading to adjacent segmental disease requiring further fusions and re-operations. Recent advances in pedicle screw fixation including minimally invasive and image-guided technology, and the development of flexible rods, imperfectly address some but not all of these issues.

Complications of all current spinal interbody fusion devices is their lack of coverage of the majority of the cross-sectional area of the vertebral endplates, and their lack of adequate, if any capacity to penetrate bone, and hence the heightened risk of implant extrusion. Furthermore the bone and biological bone fusion agents which are packed into the intervertebral space can easily blossom and grow upward into the thecal sac causing neural compression, in the absence of a physical barrier between the fusing growing bone, and the thecal sac.

SUMMARY

Herein we describe multiple device embodiments which combine in a single construct the dual functions of an intervertebral spacer maintaining disc space height, and transvertebral body fusion screws.

We also introduce an entirely novel horizontal mini-plate capping off the intervertebral space capable of functioning as a physical barrier preventing upward bone intrusion and/or compression of the ventral thecal sac, and traversing and exciting nerve roots.

Furthermore, we present an advanced mechanism in calibrated posterior facet joint stapling compared to our previous designs illustrated in our co-pending patents. We also introduce the entirely novel concept of posterior cervical facet staples to obviate and/or diminish the need for posterior cervical pedicle screw instrumented fusion. Using combinations and permutations of different embodiments of cervical facet staples in a modular manner advances

To achieve safe, effective and minimally invasive segmental spinal fusion, applicants propose the use of novel bi-directional fixing transvertebral (BDFT) screws which can be strategically inserted via anterior or posterior surgical spinal approaches into the anterior and middle columns of the intervertebral disc space. In our previous applications these bi-directional screws employed turning a wormed driving screw which turns a spur gear which in turn simultaneously turns a rostral oriented screw into the cephalad vertebral body, and a caudal directed screw into the caudal vertebral body. The vertebral bodies above and below the disc space by virtue of their engagement and penetration by the BDFT screws are thus linked, interlocked, and eventually biologically fused with placement of intervertebral bone agents.

In this current application one or more of the described embodiments may eliminate the intervening wormed driving screws and gears required by previous designs, e.g., a gearless screw box is achieved. We have designed a screw box to be placed inter-vertebrally, either unilaterally or bilaterally, in particular, posteriorly between vertebral bodies. The housing screw box incorporates built-in screw and/or drill guides which allow the direct placement and insertion of two self drilling screws which are driven in two opposing directions into superior and inferior vertebral bodies, respectively. One screw within the screw box is angled superiorly, and the other screw in the screw box is angled inferiorly.

In yet another embodiment, in addition to these features we designed an expanding screw box with sliding triangular bases to house two screws driven in two opposing directions

3

which can be expanded in two simultaneous directions, height and depth, by turning a built-in screw adjuster. This is accomplished by a combined positioning tool/screw guide/cage expander to further enhance trajectory precision and to simultaneously expand the screw box in height and depth to custom-fit the individual disc space height. This embodiment has two sub-embodiments; one has two laterally oriented BDFT screws, and the other has a lateral and a medial oriented BDFT screw. These innovations represent a continued evolution of our concept of expandable fusion cages described in our previous co-pending patents.

In yet another embodiment we designed a screw box which houses only one, instead of two screws. Each box allows the placement of one superior or inferior directed screw on one side (left or right), and the contra lateral screw box device allows placement of an inferior or superior oriented screw which goes in the opposite direction of the contra lateral device. In totality these two separate single screw boxes fuse the superior and inferior vertebrae. The potential advantage of this embodiment is that it diminishes the width of the screw box in cases where it might be favorable to have less nerve root retraction with a smaller width device.

In all screw-box embodiments, a rostral-directed screw is passed through one built-in screw guide of the device which then is inserted and screwed into the superior vertebral body. Then a caudally directed screw is passed through an adjacent built-in screw guide which then is inserted and screwed into the inferior vertebral body. The novelty of this design is the built-in prescribed angles of the integral screw guides which allow the posterior transvertebral penetration into the vertebral bodies. This is a truly amazing feat accomplished in the posterior lumbar spine considering the small anatomically restricted work zone within which to work, which is very narrowly prescribed by obtuse angulations between screw and intervertebral bone surfaces, and by nerve root, facet joint and pedicle. We have also designed a positioning tool for the placement of the non-expandable screw boxes which has a screwdriver with a flexible shaft specifically designed to fit these devices if a straight screw driver impedes screw placement. Hence these external tools provide the means in any circumstance to accomplish precision screw trajectory. The embodiments described herein compared to our previous co-pending patent designs, streamline and ease production of bi-directionally oriented transvertebral screws, and allows placement of longer and wider screws with greater bone penetration to provide yet a sturdier fusion construct. The designs are also easily modifiable for anterior placement into the cervical spine. The expandable embodiment of the screw box can also be enlarged and modified to be suitable for cervical, thoracic and lumbar vertebral body replacements.

The box casings have multiple perforations to allow both screw traversal and horizontal bone packing preventing upward vertical migration of bone. The boxes prevent subsidence. Both the inside of the denuded intervertebral space, and the screw boxes can be packed with autologous or allograft bone, BMP, DBX or similar osteoconductive material. Posteriorly or anteriorly in the lumbar

It is believed that BDFT-screw constructs provide as strong or stronger segmental fusion as pedicle screws without the complications arising from pedicle screw placement which include screw misplacement with potential nerve and/or vascular injury, violation of healthy facets, possible pedicle destruction, blood loss, and overly rigid fusions. By placing screws across the intervertebral space from vertebral body to vertebral body, engaging anterior and middle spinal

4

columns, and not the vertebral bodies via the transpedicular route, the healthy facet joints, if they exist, are preserved. Because this technique accomplishes both anterior and middle column fusion, without rigidly fixating the posterior column, it in essence creates a flexible fusion. This device therefore is a flexible fusion device because the preserved posterior facet joints retain their function achieving at least a modicum of mobility and hence a less rigid (i.e. a flexible) fusion.

The very advantage of transpedicular screws which facilitate a strong solid fusion by rigidly engaging all three spinal columns is the same mechanical mechanism whereby complete inflexibility of all columns is incurred thereby leading to increasing rostral and caudal segmental stress which leads to an increased rate of re-operation.

Transvertebral fusion also leads to far less muscle retraction, blood loss, and significant reduction in O.R. time. Thus the complication of pedicular screw pull-out and hence high re-operation rate associated with the current embodiment of flexible fusion pedicle screws/rods is obviated. The lumbosacral screw box embodiments and BDFT screws can be introduced via posterior lateral, transforaminal or anterior interbody fusion approaches/techniques. Although one can opt to supplement these screws with transpedicular screws there would be no absolute need for supplemental pedicle screw fixation with these operative techniques.

BDFT screw constructs outlined here can also be combined with novel zero-profile horizontal cervical and, lumbar/thoracic mini-plates. Likewise one or two of these devices can be inserted anteriorly with or without circumferential cage supplementation.

Because the BDFT screws engage a small percentage of the rostral and caudal vertebral body surface area, multilevel fusions can be performed with these devices.

Previous improvements included a novel calibrated lumbar/thoracic facet stapling device which staples the inferior articulating facet of the superior segment to the superior articulating facet of the caudal vertebral segment unilaterally or bilaterally, which may minimize motion until interbody fusion occurs. In the present patent application we introduce a new design of the staple enhancing its calibrating capability.

In this patent application we also introduce a novel posterior cervical facet stapling device which staples the inferior articulating facet of the superior cervical segment with the superior articulating facet of the caudal vertebral segment unilaterally or bilaterally.

The advantage of cervical facet staples is speed and safety. The risks of cervical facet pedicle screw fixation which include nerve root and vertebral artery injuries are completely obviated. Thus they thereby achieve the same function of pedicle screws without the risks.

Placement of different embodiments of the cervical facet staples along unilateral and/or bilateral facet joints in a modular manner, lead to differing degrees of calibrated motion joint motion hence introducing for the first time the concept of calibrated cervical fusion.

Currently failed anterior lumbar arthroplasties are salvaged by combined anterior and posterior fusions. BDFT screw constructs could be utilized as a one-step salvage operation for failed/extruded anteriorly placed lumbar artificial discs obviating the above salvage procedure which has far greater morbidity.

For example, in one general aspect, a self-drilling bone fusion screw apparatus includes a first sliding box, a second sliding box, positioned relative to the first sliding box, a first screw member having a tapered end and a threaded body

5

disposed within the first sliding box, a second screw member having a tapered end and a threaded body disposed within the second sliding box, and an adjuster for adjusting the height of the sliding boxes.

Implementations of this aspect may include one or more of the following features. For example, the first and second screw members may be medially aligned. At least one of the first and second screw members may be laterally aligned. The first and second screw members are laterally aligned. One of the first and second screw members is laterally aligned and the other screw member is laterally aligned. The first and second sliding boxes may be substantially triangularly shaped. The triangularly shaped first and second sliding boxes may include a sliding rail and ridged surfaces. The triangularly shaped first and second sliding boxes may include holes for bone grafts. The adjuster may include a screw.

In another general aspect, a self-drilling bone fusion screw apparatus includes a box, a first screw member having a tapered end and a threaded body disposed at least partially within the box and laterally aligned with the box, a second screw member having a tapered end and a threaded body disposed at least partially within the box and laterally aligned with the box, and a plurality of ridges disposed on along the sides of the box.

Implementations of this aspect may include one or more of the following features. For example, the apparatus may include bone graft holes. The apparatus may be attachable to a second self-drilling fusion screw apparatus via a plate.

In another general aspect, a self-drilling bone fusion screw apparatus may include a first box, a first screw member having a tapered end and a threaded body disposed at least partially within the first box and laterally aligned with the first box, a second box, a second screw member having a tapered end and a threaded body disposed at least partially within the second box and laterally aligned with the second box, and an attachment member for engaging the first and second boxes.

Implementations of this aspect may include one or more of the following features. For example, the self-drilling bone fusion screw apparatus may include bone graft holes. The plate may be directly joined to the first and second boxes by a plurality of screws. The attachment member for engaging the first and second boxes may include a plate or the attachment member may include a circumferential cage defining at least one recess. The first and the second boxes may be positioned within or securely held within the recess of the circumferential cage, e.g., with an interference fit.

In another general aspect, a tool assembly for manipulating a self-drilling bone fusion screw apparatus includes a handle, a gripper cooperating with the handle and having a plurality of prongs, a screw guide, held in place the plurality of prongs, for controlling the direction of self-drilling screws that are screwed into a vertebral body.

Implementations of this aspect may include one or more of the following features. For example, the tool assembly for manipulating a self-drilling bone fusion screw apparatus may include a key for controlling an adjustment device which controls the height of the self-drilling bone fusion screw apparatus. The tool assembly according to claim may include a driver assembly. The driver assembly may include a handle, a drive bit portion, and a flexible drive shaft extending between the handle and the drive bit portion for manipulating a screw of an expandable or non-expandable screw box. The assembly may include one or more of an expandable screw box and/or a non-expandable screw box. The boxes may include one or more screws. The screw

6

boxes may be joined by or include an attachment member, such as a plate and/or a circumferential cage.

In another general aspect, a cervical facet staple includes a curved staple base, at least two prongs attached to the bottom surface of the curved staple base, and an insertion member disposed on the top surface of the curved staple base.

Implementations of this aspect may include one or more of the following features. For example, the staple may include at least four prongs attached to the bottom surface of the curved staple base. The insertion member may include a threaded insert.

In another general aspect, an impaction tool for a cervical facet staple includes a handle, a stem attached to the handle, a plurality of wings for contacting the cervical facet staple, and an insertion member for coupling the cervical facet staple to the impaction tool.

Implementations of this aspect may include one or more of the following features. For example, the handle may include a flattened portion that can be struck by a mallet.

In another general aspect, a lumbar facet staple includes a pair of rotating arms, at least two prongs attached to the inner surfaces of the rotating arms, a plurality of spurs attached to one of the rotating arms, and a ratchet attached to one of the rotating arms. The rotating arms and prongs are rotated to a closed position to staple a lumbar facet joint.

BRIEF DESCRIPTION OF DRAWINGS

FIGS. 1A-D illustrate the Lumbar intervertebral screw box with one lateral oriented BDFT screw and one medially oriented two BDFT screw (Embodiment IA) in sagittal-oblique (FIG. 1A), superior perspective (FIG. 1B), inferior perspective (FIG. 1C) and exploded (FIG. 1D) views.

FIG. 1E illustrates the lumbar intervertebral expandable screw box with two lateral oriented BDFT screws (Embodiment IB; sagittal-oblique view).

FIGS. 2A-C illustrate the Lumbar intervertebral non-expandable screw box with two BDFT screws (Embodiment II) in lateral (FIG. 2A), oblique (FIG. 2B), and superior perspective (FIG. 2C) views.

FIG. 3 illustrates a superior oblique perspective view of left and right lumbar intervertebral non-expandable screw boxes with one BDFT screw (Embodiment III).

FIGS. 4A-B illustrate the horizontal intervertebral zero-profile mini-plate prior to insertion (FIG. 4A), and after insertion (FIG. 4B) into two non-expandable lumbar intervertebral screw boxes with two BDFT screws.

FIG. 4C illustrates two non-expandable lumbar intervertebral screw boxes with two screws within a large circumferential cage for anterior placement into the lumbar spine.

FIGS. 5A-C illustrate the positioning tool/screw guide/box expander in oblique perspective (FIG. 5A), lateral (FIG. 5B), and exploded (FIG. 5C) views.

FIG. 5D illustrates a superior oblique perspective view of the positioning tool/drill guide/box expander component.

FIGS. E-G illustrate the sequential steps (I-III) of the positioning tool/screw guide/box expander assembly. Step I (FIG. 5E), step II (FIG. 5F), and step III (FIG. 5G).

FIGS. 5H-I illustrate the positioning tool for impaction and placement of the non-expandable screw box with two transvertebral screws. Embodiment I has a rectangular positioning handle (FIG. 5H), and embodiment II has a circular positioning handle (FIG. 5I).

7

FIGS. 6A-B illustrate the insertion of expandable Lumbar bi-directional screw box with two BDFT screws into the Lumbar spine in oblique (FIG. 6A) and lateral (FIG. 6B) views.

FIGS. 7A-B illustrate the cervical facet staple (Embodiment I) in lateral (FIG. 7A) and oblique (FIG. 7B) views.

FIGS. 8-C illustrate the cervical facet staple (Embodiment II) in oblique (FIG. 8A), superior perspective (FIG. 8B) and inferior-oblique (FIG. 8C) views.

FIG. 9A illustrates the two-pronged cervical facet staple inserter/impactor (Embodiment I).

FIG. 9B illustrates the two-pronged cervical facet staple inserter/impactor inserted into the staple (Embodiment I).

FIG. 10A illustrates the four pronged cervical facet staple inserter/impactor (Embodiment II).

FIG. 10B illustrates the four pronged cervical facet staple inserter/impactor inserted into the cervical facet staple (Embodiment II).

FIG. 10C illustrates an inferior-oblique perspective view of the four-pronged cervical facet staple inserter/impactor (Embodiment II).

FIG. 11A illustrates placement of two-pronged cervical facet staples in a three-dimensional cervical spine.

FIG. 11B illustrates placement of four-pronged cervical facet staples in a three-dimensional cervical spine.

FIG. 11C illustrates modular placement of two and four pronged cervical facet staples in a three-dimensional cervical spine to achieve differing calibrated degrees of flexibility.

FIGS. 12A-B illustrate the Lumbar facet joint staple with a calibrated ratcheting mechanism in opened (Figure A) and closed (Figure B) positions.

DETAILED DESCRIPTION OF THE INVENTION

1. The Medical Device

Referring to FIGS. 1-6, the above described problem can be solved in the thoracic and lumbar spine by insertion into the denuded intervertebral disc space multiple embodiments of screw box constructs with BDFT screws.

FIGS. 1A-D illustrate three-dimensional views of the Lumbar intervertebral expandable screw box 100 with two BDFT screws 101, 102; one lateral and one medially oriented (Embodiment IA). FIG. 1E illustrates a sagittal-oblique view of the lumbar intervertebral expandable screw box 120 with two lateral oriented BDFT screws 121, 122 (Embodiment IB).

The expandable box 100 consists of top and bottom triangular sliding bases 103, 104 (FIGS. 1-D). The superior and inferior segments of the height/depth adjusting screw 105 are integrated and connected to the two separate top and bottom triangular bases 103, 104, respectively. By turning this adjusting screw 105 back and forth i.e. clock-wise, and counter clockwise, the sliding rails 106 of the top triangular base 103 (FIG. 1D) slide up and down the rail inserts 107 on the bottom triangular base 104 (FIG. 1D). This action will simultaneously alter the intervertebral height and depth of the screw box 100 allowing individualized custom fitting of the screw box 100 conforming to the dimensions of the disc space.

Transvertebral screw 101 penetrates the top base 103, and transvertebral screw 102 traverses the bottom base 104 of the screw box 100. The two screws 101, 102 traverse the screw box 100 in opposing directions, bi-directionally (whether they are lateral or medially oriented). The external edges of the triangular bases 103, 104 in contact with

8

vertebral body surfaces include ridges 107. This facilitates the screw box's 100 incorporation into and fusion with the superior and inferior vertebral bodies (FIGS. 1A-E). Both top and bottom screw box bases 103, 104 are perforated with holes 108 to allow bone placement for fusion. The entire construct, furthermore, is hollow to allow bone filling. Hence this device functions as both an intervertebral bone fusion spacer and bi-directional transvertebral screw fusion device.

FIGS. 2A-C illustrate three-dimensional views of the Lumbar intervertebral non-expandable screw box 200 with two BDFT screws 201, 202 (Embodiment II). Screws 201 and 202 perforate and orient in opposing, superior and inferior directions. There are holes 208 and hollow spaces allowing packaging with bone. There are also holes which allow the traversal of screws. The superior and inferior edges include ridges 207 to facilitate integration and fusion with superior and inferior vertebral bodies. The non-expandable screw box 200 may include a screw insert 209 to attach a horizontal mini-plate (not shown). The self-contained internalized drill guides are at a 25 degree angle. The screw boxes can be designed with the internalized drill guides with different angles and/or different positions within the box.

FIGS. 2A-2C illustrate that the lumbar intervertebral non-expandable screw box 200 includes a top wall 220, top surface 221 of the top wall 220, bottom surface 222 of the top wall 220, side surface 223 of the top wall 220, first and second sidewalls 224, open space 226, first internal screw hole 240, first entry opening 249, first exit opening 245, first and second outer indentations 228 formed in respective first and second outer side surfaces 230, second internal screw hole 242, second entry opening 251, second exit opening 252, threaded hole 209 (also referred to as screw insert and circular opening herein), and rectangular indentation 232. The lumbar intervertebral non-expandable screw box 200 also includes an aperture 208 (also referred to as holes or circular side hole herein) and an inner side surface 233 of the sidewall 224. Each of the first and second outer indentations 228 includes a top boundary 211 and a bottom boundary 213.

FIG. 3 illustrates a three-dimensional view of left and right lumbar intervertebral non-expandable screw boxes 300a, 300b with one BDFT screw 301 or 302 (Embodiment III). It is roughly half the width of Embodiments I and II. Screw 301 is inserted into screw box 300a (left) and screw 302 is inserted into screw box 300b (right). There are holes 308 and hollow spaces allowing packing of bone to achieve biological fusion. The combined effect of one superior oriented and one inferior oriented screw fuses the superior and inferior vertebral bodies with small constructs. This also enables placement of larger dimension screws compared to embodiments I and II.

FIGS. 4A and B illustrate three-dimensional views of the horizontal intervertebral zero profile mini-plate 400 with two non-expandable lumbar intervertebral screw boxes 300a, 300b housing two BDFT screws 301, 302. FIG. 4A illustrates the perforations 401 within the plate 400 through which small plate securing screws 310 will be inserted to connect it to the built-in screw holes of the screw box 300a, 300b (FIG. 4B). The horizontal mini-plate 400 together with the top surfaces of left and right screw boxes 300a, 300b provide a physical barrier between the underlying bone placed beneath it (not illustrated), and the thecal sac and nerve roots above it (not illustrated).

FIG. 4C illustrates two screw boxes 300c, 300d within a circumferential cage 420 (2 in 1) construct which is designed for anterior placement into the lumbar spine. There

are slots **308a**, **308b** for bone graft placement, both outside and inside the boxes. The circumferential cage **420** has perforations **401a** for the placement of transvertebral screws (not shown).

FIGS. 5A-C illustrate three-dimensional views of the external drill/screw guide-box expander **500** which assists in screw trajectory and box expansion (embodiments IA-B). For embodiments II and III, the same instrument is utilized; however, an expanding Allen key component is not used.

The key components of this device include an Allen key **501**, a spring **502**, a handle **503**, a griper **504** and a screw guide **505**. The Allen key **501** when inserted in the insertion **514** and turned, turns the screw adjuster (FIG. 5C) which in turn regulates top and bottom triangular screw box base sliding, and hence box **200** width and depth. The griper **504** has griper prongs **506** which insert into grooves of the screw guide **505** and the screw box **200** (FIGS. 5A-D) thus perfectly aligning them.

FIG. 5D illustrates a superior oblique view of the screw guide **505** demonstrating insertions **509** for griper prong **506**, built-in trajectory guides **511**, **512** for insertions of screws **101** and **102**, and the Allen key **501**.

FIGS. 5E-G illustrate three-dimensional views of the sequential steps necessary for the external guide assembly. FIG. 5E illustrates the insertion of the Allen key **501** into the handle **503**. FIG. 5F illustrates the insertion of the handle **503** through the spring **502** and griper **504**. FIG. 5G illustrates insertion of the griper **504** into the screw guide **505**.

FIGS. 5H-I illustrate three-dimensional views of a positioning tool **500a** for impaction and placement of two transvertebral screws **201**, **202** in the non-expandable screw box **200**. The driver assembly **550** consists of a screw driver **551**, a flexible shaft **552** and a square recess bit **553**. This facilitates turning the screws **201**, **202** into the bone. The flexible shaft **552** facilitates the avoidance of spinous processes which might hinder the screw driving if the shaft **552** were straight. The positioning tool **500a** can have a rectangular handle, Embodiment I (Figure 5H), or a circular handle, Embodiment II (FIG. 5I). This serves to position the screw box within the intervertebral space, and screws **201**, **202** within the screw box. Once positioned, the screw box can be impacted by tapping the handle with a mallet (not shown). The positioning tool's **500a** griper handle inserts into the screw guide and the box, which maintains alignment.

FIG. 6A illustrates a three-dimensional view of insertion of the construct (Embodiment I) into the lumbar intervertebral disc space.

FIG. 6B illustrates a three dimensional lateral view of insertion of the construct (Embodiment I) into the disc space with short screws. Placement with longer screws would capture more bone.

FIGS. 7A and B illustrate three-dimensional views of the two-pronged cervical facet staple **700** (Embodiment I). There is a staple base **701** which is contoured to align with the curved surface of the cervical facet joints. There is a superior impactor threaded insert **702**. An impactor can be screwed into this insert **702** and then impacted with a mallet. The two spikes **703**, **704** perforate the inferior and superior facets of the superior and inferior vertebral bodies hence leading to cervical facet joint fusion. The spikes can be designed with ridges and/or fishhooks to facilitate irreversible extraction.

FIGS. 8A-C illustrate three-dimensional views of the four-pronged cervical facet staple **800** (Embodiment II). Likewise it has a staple base **805** contoured specifically for the surface of the facet joint. It also has an impactor insert

806. The insertion of a device with four prongs **801-804** instead of two prongs further limits the degrees of motion of the joint hence making the fusion more rigid.

FIGS. 9A-B illustrate a three-dimensional view of the two-pronged cervical staple impactor **900**. It has a handle **901**, a stem **902**, and a screw insert **903** which can be screwed into the threaded staple insert. The impactor has two wings **904** which keep the staple base edges in place facilitating staple impaction. The handle **901** of the impactor **900** is broad in order to allow impaction by a mallet.

FIGS. 10A-C illustrate three-dimensional views of the four-pronged cervical staple impactor **1000** (Embodiment II). It has the same features as the two-pronged impactor **900**, except its wings **1004** are broader accommodating the broader staple base. The impactor **1000** also includes a handle **1001**, a stem **1002**, and an impact screw **1003**.

FIG. 11A illustrates a three-dimensional view of placement of the two pronged cervical facet staple **700** into a cervical spine model having vertebral body **1103** and lamina **1104**. One staple **700** is perched on the joint **1101** prior to impaction. The other staple **700** is impacted.

FIG. 11B illustrates a three-dimensional view of placement of the four pronged cervical facet staple **800** into a cervical spine pre and post impaction.

FIG. 11C illustrates the concept of modularity and incremental diminution of movement of the joint by the modular placement of different combinations and permutations of varying numbers of two and four pronged cervical facet staples **700**, **800**. If one wishes to have the most flexible (least rigid) fusion, one would place a unilateral two pronged staple **700**. One can increase i.e. calibrate increasing degrees of rigidity by increasing the number of prongs penetrating the facet joints bilaterally. In FIG. 11C each facet joint is fused using a total number of six prongs. One side this is accomplished by using three two pronged staples **700**, and on the other side using one four pronged staple **800** and one two pronged staple **700**. These two embodiments can be mixed and matched unilaterally or bilaterally to vary the degree of rigidity and conversely flexibility of fusion. The most flexible fusion at one level would be accomplished by one staple **700** (2 prongs). The highest level of rigidity would be achieved by placing two four pronged staples **800** on both sides totaling sixteen prongs. Intermediate degrees of relative joint motion can be modulated by insertion into the cervical facet joints staples in two-four prong increments from 2-16. Each additional prong further limits the degree of facet joint motion hence increasing rigidity, and conversely decreasing flexibility. Thus the novel modular use of these embodiments heralds an era of flexible cervical spine fusion.

FIGS. 12A-B illustrate a lumbar facet joint staple **1200** in open and closed positions and having staple prongs **1203**. This lumbar facet staple has been thoroughly described in our previous co-pending patent application Ser. No. 14/536,815, filed on Sep. 29, 2006, and Ser. No. 11/208,644, filed on Aug. 23, 2005, the relevant portion of each of which is hereby incorporated by reference hereinafter. The new improvement of this device includes a ratchet **1201**. The staple **1200** can be incrementally closed with increased ratcheting over increasing number of spurs **1202**. This achieves increasing calibrated levels of lumbar facet joint fusion, and conversely diminishing joint flexibility. This new designs further enhances the capacity to achieve flexible fusions in the lumbar spine.

2. The Surgical Method

Exemplary surgical steps for practicing one or more of the foregoing embodiments will now be described.

11

The posterior lumbar spine implantation of all the screw box **100**, **200**, **300** embodiments, with BDFT screws, and horizontal mini-plate **400** can be implanted via previously described posterior lumbar interbody fusion (PLIF) or posterior transforaminal lumbar interbody fusion (TLIF) procedures. The procedures can be performed open, microscopic, closed tubular or endoscopic. Fluoroscopic guidance can be used with any of these procedures.

After adequate induction of anesthesia, the patient is placed in the prone position. A midline incision is made for a PLIF procedure, and one or two parallel paramedian incisions or a midline incision is made for the TLIF procedure. For the PLIF, a unilateral or bilateral facet sparing hemi-laminotomy is created to introduce screw box **100**, **200**, **300** embodiments I-III into the disc space, after it is adequately prepared.

For the TLIF procedure, after unilateral or bilateral dissection and drilling of the inferior articulating surface and the medial superior articulating facet the far lateral disc space is entered and a circumferential discectomy is performed. The disc space is prepared and the endplates exposed.

Then one screw box **100**, **200**, **300** of either embodiments I-III is placed on either right, left or both sides. Then another screw box of embodiments **100**, **200**, **300** I-III is placed on the contralateral side. For embodiment I the external screw guide **505**/box expander is attached to the screw box (FIGS. 5A-H). First the Allen key **501** is screwed until the box conforms perfectly to the height and depth of the space. Then a pilot hole can be drilled or an awl can start a pilot hole in the vertebral bodies. Then a transvertebral screw is screwed into the vertebral body via the built-in box screw guides **505**. For difficult angles, an angled screw driver can be employed.

For embodiments II-III the same method is used for placing screws, except the Allen key **501** is not utilized in the absence of plate expansion.

If bilateral constructs have been inserted, bone is packed into the intervertebral space, as well as within the device. Then the horizontal intervertebral zero profile mini-plate **400** is slid beneath the thecal sac and is secured to both left and right screw boxes with small mini-plate screws **210** (FIGS. 4A-B). This prevents bone intrusion into the thecal sac and hence possible nerve root compression.

FIGS. 6A and B illustrate the process of insertion and final placement of the construct into the lumbar spine. The mini-plates **400** can come in different horizontal lengths and widths to accommodate different intra and inter-patient disc space diameters. The BDFT screws can come in different widths, lengths and thread designs.

The anterior thoracic and lumbar spine implantation of one, two or three screw box constructs **100**, **200**, **300** and BDFT screws can be performed in a similar manner to the posterior application. Likewise, a horizontal mini-plate **400** can be used to cap two or three screw box constructs **100**, **200**, **300** (one placed midline deeply, one placed left and one placed right, forming a triangulation). Alternatively two screw box constructs may be placed into a circumferential ring for anterior placement. Anterior placement of these devices can be performed into the L4/5 and L5/S1 spaces on the supine anesthetized patient via previously described open microscopic or endoscopic techniques. Once the disc space is exposed and discectomy and space preparation are performed, placement of one, two or three screw box embodiments **100**, **200**, **300** (I-III) or a 2 in 1 construct can be placed. The screw placement is facilitated by the internal screw guides, and different positioning tools ((FIG. 5). A

12

right angled screw driver and/or ratchet could alternatively be employed. A capping mini-plate **400** may be applied if desirable. The mechanism of screw placement and mini-plate **400** attachment are identical to what was described above.

The posterior placement of screw box constructs **100**, **200**, **300** alone or combined with horizontal mini-plates **400** into the thoracic spine can be performed via previously described transpedicular approaches; open or endoscopic. The anterior placement into the thoracic spine can be accomplished via a trans-thoracic approach. Once the disc space is exposed via either approach, any combination of the above mention Embodiments (I-III) can be inserted. Engagement of the devices is identical to what was mentioned above.

For posterior placement of cervical facet staple **700**, **800** embodiments, after adequate induction of anesthesia the patient is flipped prone and his head and neck secured. A single midline or two para-median incisions are made for unilateral or bilateral or multilevel placement of staples. Ultimately the facet joint is exposed. Alternatively and preferably this can be performed percutaneously under fluoroscopic guidance with intravenous sedation. The staple **700**, **800** (Embodiments I or II) is loaded into the impactor **900**, **1000**. The staple **700**, **800** is placed on the two articulating cervical facets, and then impacted into the joint. To achieve modular calibrated fusion different combinations and permutations of cervical facet staples can be inserted ranging from a single unilateral two pronged staple providing a high degree of flexibility to a total of four bilaterally placed four pronged staples **800** (16 prongs) leading to the highest degree of rigidity. Additional bone may or may not be placed in its vicinity to facilitate permanent and solid fusion. This procedure can be performed open, closed, percutaneously, tubular, endoscopically or microscopically. FIGS. 11A-C illustrates placement of the staples **700**, **800** in the cervical spine.

We have previously described surgical placement of the lumbar facet joint staple in our two co-pending patents. The surgical procedure for this device is identical to that which has been previously mentioned.

The present inventions may provide effective and safe techniques that overcome the problems associated with current transpedicular based cervical, thoracic and lumbar fusion technology, and for many degenerative stable and unstable spine disease. These inventions could replace much pedicle screw-based instrumentation in many but not all degenerative spine conditions.

The speed and simplicity of placement of cervical and lumbar facet staples, and placement of Lumbar screw box—BDFT constructs far exceeds that of current pedicle screw technology. Furthermore, these devices have markedly significantly decreased risk of misguided screw placement, and hence decreased risk of neural and vascular injury, and blood loss. In the lumbar spine BDFT screw constructs and facet staples could be applied modularly in different combinations to achieve different degrees of rigidity (flexibility). Patients having these devices would have decreased recovery and back to work time. These devices most likely lead to similar if not equal fusion with significantly less morbidity, and hence overall make them a major advance in the evolution of spinal instrumented technology leading to advances in the care of the spinal patient.

Another major novelty and advance is the introduction of simple and safe modular calibrated cervical flexible fusion. To our knowledge neither a similar device nor a similar

13

mathematical concept of modular joint flexibility/fusion calibration has been postulated for the cervical spine or for any other articulating joint.

To our knowledge there have not been any previously described similar posterior lumbar and thoracic combined spacer and screw constructs. These devices can similarly be modified to stabilize bone fractures throughout the entire body. To our knowledge the description of zero to subzero profile anterior or posterior horizontal spinal plates which traverse the diameter of the disc space has not been previously described.

We claim:

1. An intervertebral implant comprising:

a top wall including a top surface, a first side surface perpendicular to the top surface, a second side surface opposite of the first side surface, and a bottom surface opposite the top surface;

a bottom wall opposite the top wall;

a first sidewall;

a second sidewall opposite the first sidewall, wherein the top wall, bottom wall, first sidewall and second sidewall comprise a unitary structure and define an open space capable of receiving bone filling for biological bone fusion;

a circular opening extending normally into the top surface of the top wall;

an indentation extending into the top surface of the top wall at an intersection between the top surface of the top wall and the first side surface of the top wall, wherein the indentation has first and second straight edges when viewed from a direction normal to the top surface of the top wall, and wherein the first straight edge of the indentation is perpendicular to the second straight edge of the indentation; and

an internal screw hole defined by the intervertebral implant and extending from an entry opening formed in the top wall to an exit opening formed at least partially in the bottom surface of the top wall and at least partially in one of the first and second side surfaces of the top wall;

wherein the intervertebral implant does not include a faceplate to retain a screw in the internal screw hole.

2. The intervertebral implant of claim 1, wherein the exit opening of the internal screw hole is configured such that the screw extending through the internal screw hole exits at the exit opening at least partially into the open space.

3. The intervertebral implant of claim 2, wherein the intervertebral implant is configured to be inserted into a disc space between a first vertebral body and a second vertebral body and to provide fusion of the first vertebral body to the second vertebral body via biological bone fusion and screw fusion.

4. The intervertebral implant of claim 1, wherein the internal screw hole is a first internal screw hole, and the intervertebral implant further comprises:

at least a second internal screw hole extending from a second entry opening formed in the top wall to a second exit opening, the second internal screw hole oriented in a different direction than the first internal screw hole.

5. The intervertebral implant of claim 1, further comprising:

a first outer indentation on a first outer side surface of the first sidewall;

a second outer indentation on a second outer side surface of the second sidewall, wherein the second outer indentation is positioned opposite of the first outer indentation, wherein an entirety of the first outer indentation is

14

positioned closer to the top surface of the top wall than to a bottom of the bottom wall, and an entirety of the second outer indentation is positioned closer to the top surface of the top wall than to the bottom of the bottom wall.

6. The intervertebral implant of claim 1, wherein at least one of the first and second side surfaces of the top wall and a side surface of the bottom wall are each patterned with a plurality of surface features to create a rough side surface.

7. The intervertebral implant of claim 6, wherein at least some of the plurality of surface features are positioned on at least one of the first and second side surfaces of the top wall closer to the top surface of the top wall than the exit opening.

8. The intervertebral implant of claim 7, wherein the plurality of surface features are ridges extending from at least one of the first and second side surfaces of the top wall and the side surface of the bottom wall, the ridges positioned around the open space capable of receiving bone filling for biological bone fusion.

9. The intervertebral implant of claim 1, wherein the entry opening is formed only in the top surface of the top wall.

10. The intervertebral implant of claim 1, and further comprising:

means to facilitate incorporation of the intervertebral implant into and fusion with superior and inferior vertebral bodies, wherein the first side surface extends across each of the top wall, the bottom wall, and the first and second sidewalls, wherein the second side surface extends across each of the top wall, the bottom wall, and the first and second sidewalls, wherein the means to facilitate incorporation of the intervertebral implant into and fusion with superior and inferior vertebral bodies is positioned on the first side surface on at least part of each of the top wall, the bottom wall, and the first and second sidewalls, and wherein the means to facilitate incorporation of the intervertebral implant into and fusion with superior and inferior vertebral bodies is positioned on the second side surface on at least part of each of the top wall, the bottom wall, and the first and second sidewalls.

11. The intervertebral implant of claim 10, wherein a portion of the first side surface that extends across the bottom wall is substantially ridge-free.

12. The intervertebral implant of claim 1, wherein the first side surface extends across each of the top wall, the bottom wall, and the first and second sidewalls, wherein the second side surface extends across each of the top wall, the bottom wall, and the first and second sidewalls, wherein a first plurality of ridges are positioned on the first side surface with at least a first portion of the first side surface being substantially ridge-free such that the first plurality of ridges cover more of a left side of the first side surface than a right side of the first side surface, and wherein a second plurality of ridges are positioned on the second side surface with at least a first portion of the first side surface being substantially ridge-free.

13. An implant system comprising:

an intervertebral implant comprising:

a top wall including a top surface and a bottom surface opposite the top surface;

a bottom wall opposite the top wall;

a first sidewall having a first outer side surface;

a second sidewall having a second outer side surface positioned opposite the first outer side surface of the first sidewall, wherein the top wall, bottom wall, first sidewall and second sidewall comprise a unitary structure and define an open space capable of receiving

15

ing bone filling for biological bone fusion, and wherein the first sidewall and the second sidewall define apertures from their respective first and second outer side surfaces to respective first and second inner side surfaces, the apertures connected to the open space and configured to promote biological bone fusion through the first sidewall and the second sidewall; and

a first internal screw hole defined by the intervertebral implant and extending from a first entry opening formed in the top wall to a first exit opening formed at least partially in the bottom surface of the top wall and at least partially in a first side surface of the top wall;

a second internal screw hole defined by the intervertebral implant and extending from a second entry opening formed in the top wall to a second exit opening formed at least partially in the bottom surface of the top wall and at least partially in a second side surface of the top wall;

the intervertebral implant including a plurality of surface features on the first and second side surfaces of the top wall and also on first and second side surfaces of the bottom wall, wherein the surface features are on at least middle portions of the first and second side surfaces of the top wall and first and second side surfaces of the bottom wall;

the intervertebral implant including a first indentation on the first outer side surface of the first sidewall of the intervertebral implant and a second indentation on the second outer side surface of the second sidewall of the intervertebral implant, the first indentation having a first bottom boundary positioned closer to the top surface of the top wall than to a bottom of the bottom wall such that an entirety of the first indentation is positioned closer to the top surface of the top wall than to the bottom of the bottom wall, and the second indentation having a second bottom boundary positioned closer to the top surface of the top wall than to the bottom of the bottom wall; and

a tool comprising:

an elongate shaft having a first end and a second end; and

a gripper at the first end of the elongate shaft, the gripper comprising a first prong and a second prong, wherein the first prong and the second prong are capable of respectively engaging the first indentation and the second indentation of the intervertebral implant.

14. The implant system of claim 13, wherein the second internal screw hole is configured to orient a screw in a different direction than the first internal screw hole, the implant system further comprising:

a first screw disposed in the first internal screw hole and at least partially within the intervertebral implant; and a second screw disposed in the second internal screw hole and at least partially within the intervertebral implant; wherein each of the first internal screw hole and second internal screw hole is angled to bi-directionally orient the first screw and the second screw in opposite directions.

16

15. An intervertebral implant system comprising:

a top wall including a top surface, a first side surface perpendicular to the top surface, a second side surface opposite of the first side surface, and a bottom surface opposite the top surface;

a bottom wall opposite the top wall;

a first sidewall;

a second sidewall opposite the first sidewall, wherein the top wall, bottom wall, first sidewall and second sidewall comprise a unitary structure and define an open space capable of receiving bone filling for biological bone fusion;

a circular opening extending normally into the top surface of the top wall;

an indentation extending into the top surface of the top wall at an intersection between the top surface of the top wall and the first side surface of the top wall;

a first internal screw hole extending from a first entry opening formed in the top wall to a first exit opening formed at least partially in the bottom surface of the top wall and at least partially in the first side surface of the top wall; and a second internal screw hole extending from a second entry opening formed in the top wall to a second exit opening formed at least partially in the bottom surface of the top wall and at least partially in the second side surface of the top wall.

16. The intervertebral implant system of claim 15, wherein the circular opening is formed in the indentation.

17. The intervertebral implant system of claim 15, wherein the intervertebral implant system does not include a faceplate to retain a screw in the first or the second internal screw hole.

18. The intervertebral implant system of claim 15, wherein the indentation has first and second straight edges when view from a direction normal to the top surface of the top wall, and wherein the first straight edge of the indentation is perpendicular to the second straight edge of the indentation.

19. The intervertebral implant system of claim 15, and further comprising:

means to facilitate incorporation of the intervertebral implant system into and fusion with superior and inferior vertebral bodies, wherein the first side surface extends across each of the top wall, the bottom wall, and the first and second sidewalls, wherein the second side surface extends across each of the top wall, the bottom wall, and the first and second sidewalls, wherein the means to facilitate incorporation of the intervertebral implant system into and fusion with superior and inferior vertebral bodies is positioned on the first side surface on at least part of each of the top wall, the bottom wall, and the first and second sidewalls, and wherein the means to facilitate incorporation of the intervertebral implant system into and fusion with superior and inferior vertebral bodies is positioned on the second side surface on at least part of each of the top wall, the bottom wall, and the first and second sidewalls.

20. The intervertebral implant system of claim 15, wherein the first side surface extends across each of the top wall, the bottom wall, and the first and second sidewalls, wherein the second side surface extends across each of the top wall, the bottom wall, and the first and second sidewalls, wherein a first plurality of ridges are positioned on the first side surface with at least a first portion of the first side surface being substantially ridge-free such that the first plurality of ridges cover more of a left side of the first side

17

surface than a right side of the first side surface, and wherein a second plurality of ridges are positioned on the second side surface with at least a first portion of the first side surface being substantially ridge-free.

21. The intervertebral implant system of claim **20**,
wherein a portion of the first side surface that extends across the bottom wall is substantially ridge-free.

* * * * *

18