US011539663B2

(12) **United States Patent**
Chasman et al.

(10) **Patent No.: US 11,539,663 B2**
(45) **Date of Patent: Dec. 27, 2022**

(54) **SYSTEM AND METHOD FOR MIDSERVER FACILITATION OF LONG-HAUL TRANSPORT OF TELEMETRY FOR CLOUD-BASED SERVICES**

(71) Applicant: **QOMPLX, Inc.**, Tysons, VA (US)

(72) Inventors: **Mike Chasman**, Herndon, VA (US); **Jeffrey Chung**, Reston, VA (US); **Jason Crabtree**, Vienna, VA (US); **Luka Jurukovski**, Arlington, VA (US); **Richard Kelley**, Woodbridge, VA (US); **Artem Panasenkov**, Reston, VA (US); **Andrew Sellers**, Monument, CO (US)

(73) Assignee: **QOMPLX, INC.**, Tysons, VA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 802 days.

(21) Appl. No.: **16/412,340**

(22) Filed: **May 14, 2019**

(65) **Prior Publication Data**

US 2020/0014659 A1 Jan. 9, 2020

Related U.S. Application Data

(63) Continuation-in-part of application No. 16/267,893, filed on Feb. 5, 2019, which is a continuation-in-part
(Continued)

(51) **Int. Cl.**
H04L 9/40 (2022.01)
G06F 8/61 (2018.01)
(Continued)

(52) **U.S. Cl.**
CPC ***H04L 63/0218*** (2013.01); ***G06F 8/61*** (2013.01); ***G06F 9/44505*** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC H04L 63/0218; H04L 12/4641; H04L 41/0806; H04L 63/0272; H04L 63/0428;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,669,000 A 9/1997 Jessen et al.
7,072,863 B1 7/2006 Philips et al.
(Continued)

FOREIGN PATENT DOCUMENTS

CN 105302532 B 6/2018

OTHER PUBLICATIONS

Himes (Using Ansible to generate complex configs, May 31, 2018, 5 pages) (Year: 2018).*
(Continued)

Primary Examiner — Oleg Korsak
(74) *Attorney, Agent, or Firm* — Galvin Patent Law LLC; Brian R. Galvin

(57) **ABSTRACT**

A system and method that uses midservers located between the business enterprise computer infrastructure and the cloud-based infrastructure to collect, aggregate, analyze, transform, and securely transmit data from a multitude of computing devices and peripherals at an external network to a cloud-based service.

6 Claims, 18 Drawing Sheets



Related U.S. Application Data

of application No. 16/248,133, filed on Jan. 15, 2019, which is a continuation-in-part of application No. 15/813,097, filed on Nov. 14, 2017, now abandoned, which is a continuation-in-part of application No. 15/616,427, filed on Jun. 7, 2017, now abandoned, which is a continuation-in-part of application No. 14/925,974, filed on Oct. 28, 2015, now abandoned, application No. 16/412,340, which is a continuation-in-part of application No. 16/267,893, filed on Feb. 5, 2019, which is a continuation-in-part of application No. 16/248,133, filed on Jan. 15, 2019, which is a continuation-in-part of application No. 15/806,697, filed on Nov. 8, 2017, now abandoned, which is a continuation-in-part of application No. 15/376,657, filed on Dec. 13, 2016, now Pat. No. 10,402,906, which is a continuation-in-part of application No. 15/237,625, filed on Aug. 15, 2016, now Pat. No. 10,248,910, which is a continuation-in-part of application No. 15/206,195, filed on Jul. 8, 2016, now abandoned, which is a continuation-in-part of application No. 15/186,453, filed on Jun. 18, 2016, now abandoned, which is a continuation-in-part of application No. 15/166,158, filed on May 26, 2016, which is a continuation-in-part of application No. 15/141,752, filed on Apr. 28, 2016, now Pat. No. 10,860,962, which is a continuation-in-part of application No. 15/091,563, filed on Apr. 5, 2016, now Pat. No. 10,204,147, and a continuation-in-part of application No. 14/986,536, filed on Dec. 31, 2015, now Pat. No. 10,210,255, and a continuation-in-part of application No. 14/925,974, filed on Oct. 28, 2015, now abandoned, application No. 16/412,340, which is a continuation-in-part of application No. 16/267,893, filed on Feb. 5, 2019, which is a continuation-in-part of application No. 16/248,133, filed on Jan. 15, 2019, which is a continuation-in-part of application No. 15/806,697, filed on Nov. 8, 2017, now abandoned, which is a continuation-in-part of application No. 15/343,209, filed on Nov. 4, 2016, now Pat. No. 11,087,403, which is a continuation-in-part of application No. 15/237,625, filed on Aug. 15, 2016, now Pat. No. 10,248,910, and a continuation-in-part of application No. 15/229,476, filed on Aug. 5, 2016, now Pat. No. 10,454,791, which is a continuation-in-part of application No. 15/206,195, filed on Jul. 8, 2016, now abandoned, application No. 16/412,340, which is a continuation-in-part of application No. 16/267,893, filed on Feb. 5, 2019, which is a continuation-in-part of application No. 16/248,133, filed on Jan. 15, 2019, which is a continuation-in-part of application No. 15/673,368, filed on Aug. 9, 2017, now abandoned, which is a continuation-in-part of application No. 15/376,657, filed on Dec. 13, 2016, now Pat. No. 10,402,906, application No. 16/412,340, which is a continuation-in-part of application No. 16/267,893, filed on Feb. 5, 2019, which is a continuation-in-part of application No. 16/248,133, filed on Jan. 15, 2019, which is a continuation-in-part of application No. 15/849,901, filed on Dec. 21, 2017, now Pat. No. 11,023,284, which is a continuation-in-part of application No. 15/835,312, filed on Dec. 7, 2017, now Pat. No. 11,055,451, which is a continuation-in-part of application No. 15/186,453, filed on Jun. 18, 2016, now abandoned, application No. 16/412,340, which is a continuation-in-part of application No. 16/267,893, filed on Feb. 5, 2019, which is a continuation-in-part of application No. 16/248,133, filed on Jan. 15, 2019, which is a continuation-in-part of application No. 15/849,901, filed on Dec. 21, 2017, now Pat. No. 11,023,284, which is a continuation-in-part of application No. 15/835,436, filed on Dec. 7, 2017, now Pat. No. 10,572,828, which is a continuation-in-part of application No. 15/790,457, filed on Oct. 23, 2017, now Pat. No. 10,884,999, which is a continuation-in-part of application No. 15/790,327, filed on Oct. 23, 2017, now Pat. No. 10,860,951, which is a continuation-in-part of application No. 15/616,427, filed on Jun. 7, 2017, now abandoned, and a continuation-in-part of application No. 15/141,752, filed on Apr. 28, 2016, now Pat. No. 10,860,962.

(60) Provisional application No. 62/568,298, filed on Oct. 4, 2017, provisional application No. 62/568,291, filed on Oct. 4, 2017.

(51) **Int. Cl.**

H04L 41/0806	(2022.01)
G06F 9/445	(2018.01)
G06F 9/455	(2018.01)
H04L 67/104	(2022.01)
H04L 67/141	(2022.01)
H04L 12/46	(2006.01)
G06N 99/00	(2019.01)

(52) **U.S. Cl.**

CPC ***G06F 9/45533*** (2013.01); ***G06N 99/00*** (2013.01); ***H04L 12/4641*** (2013.01); ***H04L 41/0806*** (2013.01); ***H04L 63/0272*** (2013.01); ***H04L 63/0428*** (2013.01); ***H04L 63/0807*** (2013.01); ***H04L 63/1441*** (2013.01); ***H04L 67/104*** (2013.01); ***H04L 67/141*** (2013.01)

(58) **Field of Classification Search**

CPC H04L 63/0807; H04L 63/1441; H04L 67/104; H04L 67/141; G06F 8/61; G06F 9/44505; G06F 9/45533; G06N 99/00

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2007/0021955	A1	1/2007	Tolone et al.
2007/0043656	A1	2/2007	Lancaster
2008/0027690	A1	1/2008	Watts
2008/0221949	A1	9/2008	Delurgio et al.
2009/0222562	A1	9/2009	Liu et al.
2011/0208681	A1	8/2011	Kuecuekyan
2012/0116743	A1	5/2012	Ayala et al.
2012/0266244	A1	10/2012	Green et al.
2014/0156806	A1	6/2014	Karpistsenko et al.
2014/0279762	A1	9/2014	Xaypanya et al.
2015/0149979	A1	5/2015	Talby et al.
2015/0169294	A1	6/2015	Brock et al.
2015/0186427	A1	7/2015	Logothetis et al.
2015/0379424	A1	12/2015	Dirac et al.
2016/0078361	A1	3/2016	Brueckner et al.
2016/0092557	A1	3/2016	Stojanovic et al.
2016/0164905	A1	6/2016	Phinney et al.
2016/0364307	A1	12/2016	Garg et al.
2017/0193110	A1	7/2017	Crabtree et al.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2017/0323089 A1 11/2017 Duggal et al.
2018/0115519 A1* 4/2018 Bonomi H04L 63/1458

OTHER PUBLICATIONS

MatthiasLohr (Provide a method Peer.close(), Mar. 27, 2013, 5 pages) (Year: 2013).*
Microsoft (What's New in Kerberos Authentication, Aug. 31, 2016, 22 pages) (Year: 2016).*

* cited by examiner


Network
110
112
111
DMZ
120
Cloud Service
130
User Endpoints
160
On-Site Servers
150
AD Server / Domain Controller
152
Midserver
151
Log Sources
140

Fig. 1


Customer Network Monitoring Agents 210
Cloud sources 211
Endpoint Response 211
Network Traffic 212
Events & Metrics 213
Active Directory 214
Process Monitoring 215
230
Midserver 220
Proxy 240
Cloud Service Data Ingestion 250
Load Balancer 251
Syslog Servers 252
Distributed Messaging 253
Ingest Pipelines 254
Knowledge Graph 255

Fig. 2


Cloud Service
310
VPN
320
347
N
336
N
Log
Sources
341
User
Endpoint
342
Domain
Controller
346
AD
Server
345
Midserver
344
On-Site Servers
343
Main Office
340
Domain
Controller
335
AD
Server
334
On-Site Servers
333
Satellite Office
330
Log
Sources
331
User
Endpoint
332

Fig. 3


Cloud Service
410
427
437
Satellite Office
420
On-Site Servers
423
Midserver
424
AD
Server
425
Domain
Controller
426
Log
Sources
421
User
Endpoint
422
Main Office
430
On-Site Servers
433
Midserver
434
AD
Server
435
Domain
Controller
436
Log
Sources
431
User
Endpoint
432

Fig. 4


PcapKrb Agent 501
ConMon Agent 502
OSQuery Agent 503
ADMon Agent 504
Other 505
Midservers 510
Rabbit Container 511
NGINX Container 512
Syslog Container 513
ConMon 514
OSQuery 515
520
Reverse Proxy 531
Internal Server 532
Load balancer 533

Fig. 5A


RabbitMQ
541
Logs-listener
542
Syslog-server
543
ORS
544
OSQuery
Agent Handler
545
ConMon Agent
Handler
546
ConMon
Service
547
Stats Aggregator
548
Observed System
540

Fig. 5B


Incident Service
558
MySQL
559
Mongo
560
MySQL
557
Cloud
Front-end
561
MySQL
552
GraphStack
Service
555
MDTSDB Service
556
Enrichment
Service
553
DCG
554
Redis
551

Fig. 5C


Cloud-Based Service Side 620
Midserver Side 610
600
Mid-server 611
ZeroTier Controller 612
613a
613b
Secret Key
Initial connection request
ssh (ZeroTier) Midserver playbook
Ansible Server 621
Config Controller 622
Secrets
* API
* VPN certs
* API Key (ConMon)
* Secret Key (ConMon)
* Secret Key (Osquery)
* URL (customer)
Deployment Vault 623
Secrets
External Nginx 624
DCOS Nginx 625
Microservices & Container Orchestration xxx
616
615
VPN
TLS
TLS
TLS
TLS
TLS
Container Orchestration 614
Nginx
RabbitMQ
syslog-ng
ConMon
Osquery

Fig. 6


Cloud-Based Service 740
700
Cloud Computing Service 710
Virtual Network Peer VM 731
Cloud-Based Service Network 730
CCS Server 722
VM1 721a
VM2 721b
VMn 721n
Customer Virtual Network 720

Fig. 7


Cloud-Based Service 830
800
Cloud Computing Service 810
Virtual Network Peer VM 823
CCS Server 822
Customer Virtual Network 820
VM1 821a
VM2 821b
VMn 821n

Fig. 8


Domain Controller 912
Forged Silver Ticket
Host 913
Access Granted
Attack
Client 911
910
Domain Controller 902
Forged Golden Ticket
Access Granted
Host 903
Attack
Client 901
900

Fig. 9


DC/KDC
1002
Kerberos-enabled service
1003
1000
Client request TGT from KDC
Authentication service sends encrypted TGT and session key
Client server access from TGS
TGS sends encrypted session key and ticket
Client server access from TGS
Server sends encrypted time stamp from client validation
Privileged User
1001
Ledger of Kerberos requests and responses
1004

Fig. 10


Message Source
1101
FPRS Split Stage
1102
Select Stage
(OTHER)
1103
Select Stage (No
message)
1105
Select Stage
(ERROR)
1107
Select Stage
(Message present)
1109
JSON Field
Extractor
1104
Enrichment Stage
1106
ASN1 Decoder
Stage
1108

Fig. 11A


MDTSDB Sink
1111
JSON Field Extractor
1112
MDTSDB Sink
1113
FPRS Split Stage
1114
Select Stage (OTHER)
1115
No-Op Sink
1116
Select Stage (DC_SYNC)
1117
AMP Alert Conversion Stage
1118
Select Stage (DC_SHADOW)
1120
AMP Alert Conversion Stage
1121
MDTSDB Sink
1119

Fig. 11B


Interfaces
15
Remote Storage
16
14
10
Local Storage
11
12
Processors
13

Fig. 12


28
Inputs
27
Outputs
26
Storage
25
Memory
20
24
Clients
23
Services
22
OSes
21
Processors

Fig. 13


Servers
32
Remote Storage
34
Config
35
Ext Svcs
37
Network(s)
31
30
Remote Storage
33
Sec.
36

Fig. 14


AC
46
PSU
45
54
NIC
53
HDD
52
42
51
RTC
NVM
44
I/O
Mouse
50
48
Keyboard
49
Mem
Display
40
43
47
CPU
41

Fig. 15

SYSTEM AND METHOD FOR MIDSERVER FACILITATION OF LONG-HAUL TRANSPORT OF TELEMETRY FOR CLOUD-BASED SERVICES

CROSS-REFERENCE TO RELATED APPLICATIONS

Application No.	Date Filed	Title
Current application	Herewith	SYSTEM AND METHOD FOR MIDSERVER FACILITATION OF LONG-HAUL TRANSPORT OF TELEMETRY FOR CLOUD-BASED SERVICES
		Is a continuation-in-part of:
16/267,893	Feb. 5, 2019	SYSTEM AND METHODS FOR DETECTING AND CHARACTERIZING ELECTROMAGNETIC EMISSIONS
		which is a continuation-in-part of:
16/248,133	Jan. 15, 2019	SYSTEM AND METHOD FOR MULTI-MODEL GENERATIVE SIMULATION MODELING OF COMPLEX ADAPTIVE SYSTEMS
		which is a continuation-in-part of:
15/813,097	Nov. 14, 2017	EPISTEMIC UNCERTAINTY REDUCTION USING SIMULATIONS, MODELS AND DATA EXCHANGE
		which is a continuation-in-part of:
15/616,427	Jun. 7, 2017	RAPID PREDICTIVE ANALYSIS OF VERY LARGE DATA SETS USING AN ACTOR-DRIVEN DISTRIBUTED COMPUTATIONAL GRAPH
		which claims benefit of, and priority to:
14/925,974	Oct. 28, 2015	RAPID PREDICTIVE ANALYSIS OF VERY LARGE DATA SETS USING THE DISTRIBUTED COMPUTATIONAL GRAPH
Current application	Herewith	SYSTEM AND METHOD FOR MIDSERVER FACILITATION OF LONG-HAUL TRANSPORT OF TELEMETRY FOR CLOUD-BASED SERVICES
		Is a continuation-in-part of:
16/267,893	Feb. 5, 2019	SYSTEM AND METHODS FOR DETECTING AND CHARACTERIZING ELECTROMAGNETIC EMISSIONS
		which is a continuation-in-part of:
16/248,133	Jan. 15, 2019	SYSTEM AND METHOD FOR MULTI-MODEL GENERATIVE SIMULATION MODELING OF COMPLEX ADAPTIVE SYSTEMS
		which is also a continuation-in-part of:
15/806,697	Nov. 8, 2017	MODELING MULTI-PERIL CATASTROPHE USING A DISTRIBUTED SIMULATION ENGINE
		which is a continuation-in-part of:
15/376,657	Dec. 13, 2016	QUANTIFICATION FOR INVESTMENT VEHICLE MANAGEMENT EMPLOYING AN ADVANCED DECISION PLATFORM
		which is a continuation-in-part of:
15/237,625	Aug. 15, 2016	DETECTION MITIGATION AND REMEDIATION OF CYBERATTACKS EMPLOYING AN ADVANCED CYBER-DECISION PLATFORM
		which is a continuation-in-part of:
15/206,195	Jul. 8, 2016	ACCURATE AND DETAILED MODELING OF SYSTEMS WITH LARGE COMPLEX DATASETS USING A DISTRIBUTED SIMULATION ENGINE
		which is a continuation-in-part of:
15/186,453	Jun. 18, 2016	SYSTEM FOR AUTOMATED CAPTURE AND ANALYSIS OF BUSINESS INFORMATION FOR RELIABLE BUSINESS VENTURE OUTCOME PREDICTION
		which is a continuation-in-part of:
15/166,158	May 26, 2016	SYSTEM FOR AUTOMATED CAPTURE AND ANALYSIS OF BUSINESS INFORMATION FOR SECURITY AND CLIENT-FACING INFRASTRUCTURE RELIABILITY
		which is a continuation-in-part of:

-continued

Application No.	Date Filed	Title
15/141,752	Apr. 28, 2016	SYSTEM FOR FULLY INTEGRATED CAPTURE, AND ANALYSIS OF BUSINESS INFORMATION RESULTING IN PREDICTIVE DECISION MAKING AND SIMULATION
		which is a continuation-in-part of:
15/091,563	Apr. 5, 2016	SYSTEM FOR CAPTURE, ANALYSIS AND STORAGE OF TIME SERIES DATA FROM SENSORS WITH HETEROGENEOUS REPORT INTERVAL PROFILES
		and is also a continuation-in-part of:
14/986,536	Dec. 31, 2015	DISTRIBUTED SYSTEM FOR LARGE VOLUME DEEP WEB DATA EXTRACTION
		and is also a continuation-in-part of:
14/925,974	Oct. 28, 2015	RAPID PREDICTIVE ANALYSIS OF VERY LARGE DATA SETS USING THE DISTRIBUTED COMPUTATIONAL GRAPH
Current application	Herewith	SYSTEM AND METHOD FOR MIDSERVER FACILITATION OF LONG-HAUL TRANSPORT OF TELEMETRY FOR CLOUD-BASED SERVICES
		Is a continuation-in-part of:
16/267,893	Feb. 5, 2019	SYSTEM AND METHODS FOR DETECTING AND CHARACTERIZING ELECTROMAGNETIC EMISSIONS
		which is a continuation-in-part of:
16/248,133	Jan. 15, 2019	SYSTEM AND METHOD FOR MULTI-MODEL GENERATIVE SIMULATION MODELING OF COMPLEX ADAPTIVE SYSTEMS
		which is a continuation-in-part of:
15/806,697	Nov. 8, 2017	MODELING MULTI-PERIL CATASTROPHE USING A DISTRIBUTED SIMULATION ENGINE
		which is a continuation-in-part of:
15/343,209	Nov. 4, 2016	RISK QUANTIFICATION FOR INSURANCE PROCESS MANAGEMENT EMPLOYING AN ADVANCED DECISION PLATFORM
		which is a continuation-in-part of:
15/237,625	Aug. 15, 2016	DETECTION MITIGATION AND REMEDIATION OF CYBERATTACKS EMPLOYING AN ADVANCED CYBER-DECISION PLATFORM
		and is also a continuation-in-part of:
15/229,476	Aug. 5, 2016	HIGHLY SCALABLE DISTRIBUTED CONNECTION INTERFACE FOR DATA CAPTURE FROM MULTIPLE NETWORK SERVICE SOURCES
		which is a continuation-in-part of:
15/206,195	Jul. 8, 2016	ACCURATE AND DETAILED MODELING OF SYSTEMS WITH LARGE COMPLEX DATASETS USING A DISTRIBUTED SIMULATION ENGINE
Current application	Herewith	SYSTEM AND METHOD FOR MID SERVER FACILITATION OF LONG-HAUL TRANSPORT OF TELEMETRY FOR CLOUD-BASED SERVICES
		Is a continuation-in-part of:
16/267,893	Feb. 5, 2019	SYSTEM AND METHODS FOR DETECTING AND CHARACTERIZING ELECTROMAGNETIC EMISSIONS
		which is a continuation-in-part of:
16/248,133	Jan 15, 2019	SYSTEM AND METHOD FOR MULTI-MODEL GENERATIVE SIMULATION MODELING OF COMPLEX ADAPTIVE SYSTEMS
		which is a continuation-in-part of:
15/673,368	Aug. 9, 2017	AUTOMATED SELECTION AND PROCESSING OF FINANCIAL MODELS
		which is a continuation-in-part of:
15/376,657	Dec. 13, 2016	QUANTIFICATION FOR INVESTMENT VEHICLE MANAGEMENT EMPLOYING AN ADVANCED DECISION PLATFORM

-continued

Application No.	Date Filed	Title
Current application	Herewith	SYSTEM AND METHOD FOR MIDSERVER FACILITATION OF LONG-HAUL TRANSPORT OF TELEMETRY FOR CLOUD-BASED SERVICES
		Is a continuation-in-part of:
16/267,893	Feb. 5, 2019	SYSTEM AND METHODS FOR DETECTING AND CHARACTERIZING ELECTROMAGNETIC EMISSIONS
		which is a continuation-in-part of:
16/248,133	Jan. 15, 2019	SYSTEM AND METHOD FOR MULTI-MODEL GENERATIVE SIMULATION MODELING OF COMPLEX ADAPTIVE SYSTEMS
		which is a continuation-in-part of:
15/849,901	Dec. 21, 2017	SYSTEM AND METHOD FOR OPTIMIZATION AND LOAD BALANCING OF COMPUTER CLUSTERS
		which is a continuation-in-part of:
15/835,312	Dec. 7, 2017	SYSTEM AND METHODS FOR MULTI-LANGUAGE ABSTRACT MODEL CREATION FOR DIGITAL ENVIRONMENT SIMULATIONS
15/186,453	Jun. 18, 2016	SYSTEM FOR AUTOMATED CAPTURE AND ANALYSIS OF BUSINESS INFORMATION FOR RELIABLE BUSINESS VENTURE OUTCOME PREDICTION
Current application	Herewith	SYSTEM AND METHOD FOR MID SERVER FACILITATION OF LONG-HAUL TRANSPORT OF TELEMETRY FOR CLOUD-BASED SERVICES
		Is a continuation-in-part of:
16/267,893	Feb. 5, 2019	SYSTEM AND METHODS FOR DETECTING AND CHARACTERIZING ELECTROMAGNETIC EMISSIONS
		which is a continuation-in-part of:
16/248,133	Jan. 15, 2019	SYSTEM AND METHOD FOR MULTI-MODEL GENERATIVE SIMULATION MODELING OF COMPLEX ADAPTIVE SYSTEMS
		which is a continuation-in-part of:
15/849,901	Dec. 21, 2017	SYSTEM AND METHOD FOR OPTIMIZATION AND LOAD BALANCING OF COMPUTER CLUSTERS
		which is a continuation-in-part of:
15/835,436	Dec. 7, 2017	TRANSFER LEARNING AND DOMAIN ADAPTATION USING DISTRIBUTABLE DATA MODELS
		which is a continuation-in-part of:
15/790,457	Oct. 23, 2017	DISTRIBUTABLE MODEL WITH BIASES CONTAINED WITHIN DISTRIBUTED DATA
		which claims benefit of, and priority to:
62/568,298	Oct. 4, 2017	DISTRIBUTABLE MODEL WITH BIASES CONTAINED IN DISTRIBUTED DATA
		and is also a continuation-in-part of:
15/790,327	Oct. 23, 2017	DISTRIBUTABLE MODEL WITH DISTRIBUTED DATA
		which claims benefit of, and priority to:
62/568,291	Oct. 4, 2017	DISTRIBUTABLE MODEL WITH DISTRIBUTED DATA
		and is also a continuation-in-part of:
15/616,427	Jun. 7, 2017	RAPID PREDICTIVE ANALYSIS OF VERY LARGE DATA SETS USING AN ACTOR-DRIVEN DISTRIBUTED COMPUTATIONAL GRAPH
		and is also a continuation-in-part of:
15/141,752	Apr. 28, 2016	SYSTEM FOR FULLY INTEGRATED CAPTURE, AND ANALYSIS OF BUSINESS INFORMATION RESULTING IN PREDICTIVE DECISION MAKING AND SIMULATION

the entire specification of each of which is incorporated herein by reference.

BACKGROUND OF THE INVENTION

Field of the Art

The disclosure relates to the field of computer technology, more specifically to the field of computer architectures for enterprise data collection, analysis, and transmission to cloud-based services.

Discussion of the State of the Art

As cloud-based computing services become more popular, management of the data collection from a business and transmission of that data to a cloud-based service become more complicated. Large business enterprises can have thousands of computers and peripherals, many of which are now mobile devices. Collection, management, and security of data from those many devices becomes particularly important where data is being transferred to a cloud-based service.

When a large business enterprise uses a cloud-based computing service, heterogeneous data transfer between cloud services and large offices or campuses for organizations presents numerous problems, including lack of reliable data collection methods, poor standardized support for connection-oriented protocols by network appliances, security concerns with unfiltered or poorly filtered data, and bandwidth concerns with constantly streaming data which may result in network slowdown due to unprioritized data transfer. Additionally, larger business enterprises may have thousands of computing devices sending data to a cloud-based service on separate connections, and each such connection represents an additional security risk. Further, current data collection and models do not scale well for adding new data sources and flexible adhoc queries, resulting in too much data being passed, no context for data and data sources oftentimes, unqueryable data and data sources, inability to flexibly and quickly add new data sources such as new devices or user accounts which generate new data for analysis, and log management and data storage become expensive and disorganized.

The problem is compounded by the use of black box threat detection methods, where data management and security optimization are not possible for each organization or user of a cloud-based service. Particularly in the context of data ingestion systems, it is often unclear from a data stream what portion of the data results in triggering of certain security alerts, requiring many costly hours of analytics at best, or resulting in missed errors or security concerns at worst.

What is needed is a computer architecture and methodology that allows for collection, aggregation, analysis, transformation, and secure transmission of data from a multitude of computing devices and peripherals at a business enterprise network to a cloud-based service.

SUMMARY OF THE INVENTION

Accordingly, the inventor has conceived, and reduced to practice, a system and method that uses midservers integrated with the business enterprise computer infrastructure and the cloud-based infrastructure to collect, aggregate, analyze, transform, and securely transmit data from a multitude of computing devices and peripherals at an external network to a cloud-based service. The following non-limiting summary of the invention is provided for clarity, and should be construed consistently with embodiments described in the detailed description below.

According to a preferred embodiment, a system for ingestion of data into a cloud-based service from an external network is disclosed, comprising: a midserver configured to function as an interface between an external network and a cloud-based service comprising at least a processor, a memory, and a plurality of programming instructions stored in the memory and operating on the processor: receive data from a plurality of computing devices on the external network; run one or more containerized services to process the received data; and securely transmit the processed data to a cloud-based service.

According to another preferred embodiment, a method for ingestion of data into a cloud-based service from an external network is disclosed, comprising the steps of: installing a midserver as an interface between an external network and a cloud-based service, the midserver comprising at least a processor, a memory, and a plurality of programming instructions stored in the memory and operating on the processor: receiving data from a plurality of computing devices on the external network; running one or more containerized services to process the received data; and securely transmitting the processed data to a cloud-based service.

According to an aspect of an embodiment, the containerized services include one or more of the following types of containerized services: traffic processors, sensors, management services, and utilities.

According to an aspect of an embodiment, the midserver is installed at the same location from which some part of the external network is operated.

BRIEF DESCRIPTION OF THE DRAWING FIGURES

The accompanying drawings illustrate several aspects and, together with the description, serve to explain the principles of the invention according to the aspects. It will be appreciated by one skilled in the art that the particular arrangements illustrated in the drawings are merely exemplary, and are not to be considered as limiting of the scope of the invention or the claims herein in any way.

FIG. **1** is a diagram of an exemplary midserver system architecture.

FIG. **2** is a diagram of an exemplary midserver architecture showing data input to a midserver and the ingestion of forwarded data from a midserver through a proxy to a cloud service.

FIG. **3** is a diagram of an exemplary midserver architecture between multiple office locations.

FIG. **4** is diagram of another exemplary midserver architecture between multiple office locations.

FIG. **5**A is a partial diagram of an exemplary advanced cyber-decision platform utilizing midserver architecture.

FIG. **5**B is a partial diagram of an exemplary advanced cyber-decision platform utilizing midserver architecture.

FIG. **5**C is a partial diagram of an exemplary advanced cyber-decision platform utilizing midserver architecture.

FIG. **6** is a diagram showing an exemplary architecture and methodology for midserver deployment, automated onboarding of data, and endpoint transparent data transport.

FIG. **7** is an exemplary method for deploying a midserver where the business enterprise network is located on, or utilizes, a cloud computing service such as Amazon Web Services (AWS) or Microsoft's Azure.

FIG. **8** is another exemplary method for deploying a midserver where the business enterprise network is located on, or utilizes, a cloud computing service such as Amazon Web Services (AWS) or Microsoft's Azure.

FIG. **9** is a diagram showing an overview of the methodology of two of several known Kerberos attacks.

FIG. **10** is a diagram showing an overview of the use of a ledger of Kerberos requests and responses to provide security against Kerberos attacks.

FIG. **11**A is a partial diagram of an exemplary analytic workflow for validation of a Kerberos ticket-based security protocol for use in an observed system.

FIG. **11**B is a partial diagram of an exemplary analytic workflow for validation of a Kerberos ticket-based security protocol for use in an observed system.

FIG. **12** is a block diagram illustrating an exemplary hardware architecture of a computing device.

FIG. **13** is a block diagram illustrating an exemplary logical architecture for a client device.

FIG. **14** is a block diagram showing an exemplary architectural arrangement of clients, servers, and external services.

FIG. **15** is another block diagram illustrating an exemplary hardware architecture of a computing device.

DETAILED DESCRIPTION

The inventor has conceived, and reduced to practice, a system and method that uses midservers located between the business enterprise computer infrastructure and the cloud-based infrastructure to collect, aggregate, analyze, transform, and securely transmit data from a multitude of computing devices and peripherals at an external network to a cloud-based service.

One method of data collection from large business enterprises for cloud-based computing is through agent based monitoring. In agent-based monitoring, software "agents" are installed on each computing device to collect data and then forward the data to the cloud-based service. Using agent-based monitoring, it may be necessary to install hundreds or thousands of agents on an external network to collect the required data. Each of these agents, in turn, establish an outgoing network connection to provide data to the cloud-based service. While secure transport protocols such as TLS can ensure data security, the overall number of connections to monitor at the business network edge increases substantially. This causes even more noise for network defenders to sift through. By aggregating data at midservers multiple connections can be presented over the network as a single secure connection to enterprise cloud-based systems (wlog using standard VPN or similar encryption-based network transport technologies). Thousands of connections from a large business enterprise can be reduced to a single connection or a small number of connections. It should be noted that another method of gathering data from a business enterprise network is through port mirroring. The terms "agent" and "port mirroring" are exemplary only, and do not exclude other methods of gathering data from a business enterprise network.

Midserver architecture also solves the problem that not all devices support secure data transport. For example, many devices do not natively support sending system log messages using TLS. In order to support system log traffic the data must be wrapped in a secure protocol before leaving the network. A midserver can provide this type of capability by collecting and wrapping the data before it leaves the network.

Midservers can optimize the ingestion of data into the cloud-based service by transforming the data prior to forwarding upstream. It is possible to process the data on the external network computers using an agent or additional software, but this adds complexity to the agent or requires more software installed on customer site. A midserver can act as a local processing station (often called "pre-processing") for data transformations such as compression, protocol wrapping, port bending, and many others.

Midservers can be used to prevent data loss during transmission, especially for network data that is transitory in nature. For many protocols the sender/receiver can adjust for a degraded connection without any loss of data integrity. Additionally, in some other cases the originating message can be reproduced meaning that a loss of data has little impact on the capability. For example, some agents query the current state of the system and then forward the results to a fleet manager. If the results are somehow lost during transit it is possible to issue the same query and try again. However, other data sources such as network packet captures are much less forgiving. Systems that capture ephemeral network traffic are especially impacted by data lost in transit. A midserver can mitigate this risk by providing traffic buffering in the event that the backhaul connection goes down. When the connection is reestablished, the buffers will empty and continue forwarding as usual.

The midserver architecture may be designed to operate as a bastion host that runs a collection of containerized services. It is assumed that midservers are cyber security targets and are likely to be compromised at some point. Ideally, therefore, the midserver should be designed to reduce data loss and further access to the enterprise network to which it is attached. Midservers should not be a primary data store, and should only buffer data when connections are lost. Midservers should have only the minimum software necessary to operate, and least privilege should be enforced for access. Midservers may be configured as a single server instance or as a clusters of redundant servers to provide additional resiliency.

The midserver runs a plurality of containerized services that serve to collect, aggregate, analyze, transform, and securely transmit data. The containerized service run by the midserver can be roughly categorized in four ways: traffic processors, sensors, management services, and utilities.

Containers acting as traffic processors are primarily used to receive forwarded traffic from a customer network, transform the traffic if necessary, and then forward the traffic upstream over the primary connection. Several examples of traffic processing containerized services are: reverse proxy containers, system log containers, and messaging containers. An example of a reverse proxy containerized service is Nginx. The Nginx proxy (nginx-pxy) provides reverse proxy capabilities that allows customer traffic to send approved data through the midserver. Data and log sources that support the proxy protocol will connect to this service. The service also provides traffic transform capabilities such as http to https forwarding and others as supported by Nginx. In a system log containerized service, the service provides log consolidation and forwarding capabilities for logs sent using the system log protocol. The service also provides message shaping and enrichment such as adding additional contextual fields to log sources if needed. An example of a messaging containerized service is RabbitMQ, The RabbitMQ service acts as a proxy for advanced messaging queueing protocol (AMQP) messages using the Shovel plugin. The service is primarily used for queuing and forwarding of traffic generated by messaging agents, and can

support any AMQP traffic as needed. Another traffic processing containerized service example is Consul, which provides service discovery and is may be used to support RabbitMQ configurations in a midserver cluster.

Containers acting as sensors can monitor and generate data rather than just process data from other sensors or data sources.

Management containers are used for providing management consoles or services for midserver administrators. Examples of management containers include the Nginx management proxy and Portainer. The Nginx management proxy (nginx-mgt) is responsible for managing connections to management interfaces on containers. This containerized service acts a firewall to only allow traffic to management pages and services originating from approved address spaces. Portainer provides a lightweight management UI which allows adminstrators to easily manage and monitor the other container services on the midserver.

Utility containers are special purpose tools used to aid in configuration or deployment of a midserver.

Consolidating these containerized services at the midserver allows for large-scale, reliable ingestion (i.e., one or more of collection, aggregating, analysis (pre-processing), transformation (pre-processing), and secure transmission) of data into a cloud-based service from an external network. This improves data consistency, reliability, efficiency of bandwidth usage, and security. Using the midserver as a gateway to the cloud-based service dramatically reduces the number of connections at the business enterprise's network edge, greatly reducing the number of avenues of attack and improving network security.

One or more different aspects may be described in the present application. Further, for one or more of the aspects described herein, numerous alternative arrangements may be described; it should be appreciated that these are presented for illustrative purposes only and are not limiting of the aspects contained herein or the claims presented herein in any way.

One or more of the arrangements may be widely applicable to numerous aspects, as may be readily apparent from the disclosure. In general, arrangements are described in sufficient detail to enable those skilled in the art to practice one or more of the aspects, and it should be appreciated that other arrangements may be utilized and that structural, logical, software, electrical and other changes may be made without departing from the scope of the particular aspects. Particular features of one or more of the aspects described herein may be described with reference to one or more particular aspects or figures that form a part of the present disclosure, and in which are shown, by way of illustration, specific arrangements of one or more of the aspects. It should be appreciated, however, that such features are not limited to usage in the one or more particular aspects or figures with reference to which they are described. The present disclosure is neither a literal description of all arrangements of one or more of the aspects nor a listing of features of one or more of the aspects that must be present in all arrangements.

Headings of sections provided in this patent application and the title of this patent application are for convenience only, and are not to be taken as limiting the disclosure in any way.

Devices that are in communication with each other need not be in continuous communication with each other, unless expressly specified otherwise. In addition, devices that are in communication with each other may communicate directly or indirectly through one or more communication means or intermediaries, logical or physical.

A description of an aspect with several components in communication with each other does not imply that all such components are required. To the contrary, a variety of optional components may be described to illustrate a wide variety of possible aspects and in order to more fully illustrate one or more aspects. Similarly, although process steps, method steps, algorithms or the like may be described in a sequential order, such processes, methods and algorithms may generally be configured to work in alternate orders, unless specifically stated to the contrary. In other words, any sequence or order of steps that may be described in this patent application does not, in and of itself, indicate a requirement that the steps be performed in that order. The steps of described processes may be performed in any order practical. Further, some steps may be performed simultaneously despite being described or implied as occurring non-simultaneously (e.g., because one step is described after the other step). Moreover, the illustration of a process by its depiction in a drawing does not imply that the illustrated process is exclusive of other variations and modifications thereto, does not imply that the illustrated process or any of its steps are necessary to one or more of the aspects, and does not imply that the illustrated process is preferred. Also, steps are generally described once per aspect, but this does not mean they must occur once, or that they may only occur once each time a process, method, or algorithm is carried out or executed. Some steps may be omitted in some aspects or some occurrences, or some steps may be executed more than once in a given aspect or occurrence.

When a single device or article is described herein, it will be readily apparent that more than one device or article may be used in place of a single device or article. Similarly, where more than one device or article is described herein, it will be readily apparent that a single device or article may be used in place of the more than one device or article.

The functionality or the features of a device may be alternatively embodied by one or more other devices that are not explicitly described as having such functionality or features. Thus, other aspects need not include the device itself.

Techniques and mechanisms described or referenced herein will sometimes be described in singular form for clarity. However, it should be appreciated that particular aspects may include multiple iterations of a technique or multiple instantiations of a mechanism unless noted otherwise. Process descriptions or blocks in figures should be understood as representing modules, segments, or portions of code which include one or more executable instructions for implementing specific logical functions or steps in the process. Alternate implementations are included within the scope of various aspects in which, for example, functions may be executed out of order from that shown or discussed, including substantially concurrently or in reverse order, depending on the functionality involved, as would be understood by those having ordinary skill in the art.

Definitions

"Bastion host" as used herein means a computer that is deliberately exposed on a public network as the primary or only node or the network exposed to the outside world. A bastion host processes and filters all incoming traffic and prevents malicious traffic from entering the network.

"Ingestion" as used herein means the transfer of data into a cloud-based service.

"Midserver" as used herein means a server that functions as an interface between an external network and a cloud-

based service, and which runs one or more containerized services that perform one or more of: collecting, aggregating, analyzing, filtering, transforming, and securely transmitting data. A midserver may also be configured as a bastion host.

Conceptual Architecture

FIG. **1** is a diagram of an exemplary midserver system architecture. A network **110** exists connecting a cloud service **130**, through a firewall or security layer **112**, as well as an on-site security layer or firewall **111** with some organization which may wish to connect over a network **110** to a cloud service **130**. A demilitarized zone ("DMZ," also known as a perimeter network or screened subnet) **120** is present which may present the forward-facing network connections and functionality of an organization's network or services, which may be forwarded data or interface further with on-site servers **150** and user endpoints **160**, or data log sources **140**. On-site servers **150** may include a midserver **151** for collecting, aggregating, analyzing, filtering, transforming, and securely transmitting data data transfers and interactions with a cloud service **130**, typically co-located with the enterprise domain controller (or Active Directory (AD) server) **152** for exploration of network-enabled directories and to control access to and authenticate security requests on the network for other connected servers **150**. A midserver **151** in this implementation may be used for streamlined communications with a cloud service **130** including a single point of connectivity with the service, a ticket form of security adding further security to such a connected system, and a batch method of data transfer, allowing numerous other servers **150** or endpoints **160** or log sources **140** to communicate with the midserver which then collates data for transfer to a cloud server **130**, which may further collate data received from the cloud service **130**, for ease of analysis and which allows for other forms of network optimization to take place which are not present in systems where numerous endpoints and servers maintain individual connections to a cloud service **130**, also allowing for new data sources including servers **150** and endpoints **160** to be added swiftly and integrated into the system for connection to the cloud service **130** rapidly and easily due to the midserver **151** acting as an interface between the service **130** and the other possible endpoint **160** or server **150**.

FIG. **2** is a diagram of an exemplary midserver architecture showing data input to a midserver and the ingestion of forwarded data from a midserver through a proxy to a cloud service. Cloud sources **211** of customer monitoring agents **210** may provide input to a proxy server **240** behind a firewall **230** which filters data going in and out of an organization's network. These sources of customer network monitoring agents **210** may include data that is gathered from online tools such as social media crawlers or any other source of customer network monitoring from a cloud service or network **211**. On-site data monitoring tools and processes include endpoint responses **211**, network traffic data **212**, events and metrics **213** which may include metadata about devices, users, or other connected assets, active directory **214** usage, and process monitoring **215** which may monitor active processes on connected assets such as operations performed on a connected network endpoint such as a computer workstation. Data from these sources is sent to a midserver **220** which may be on-site or connected to via a Virtual Private Network (VPN), before the data is sent to through an organizations firewall **230** to a proxy server **240**, to be forwarded to a cloud service's data ingestion pipeline **250**. Such a data ingestion pipeline **250** may include the use of a load balancer **251** to aid in processing of received data loads from differing sources, system log servers **252** which may record the reception and content of data or any other metadata about the connection to a proxy server **240** and the activity of the load balancer **251**, before forwarding data to a distributed messaging system **253** which may separate received data and data streams into related "topics" which may be defined by the sender's identity, metadata about the streams or batches of data, or some other qualifier. Ingestion pipelines **254** may process data by filtering, mapping, parsing, and sanitizing data received, before adding it to a temporal knowledge graph **255** representing a graph of assets, people, events, processes, services, and "tickets" of concerns, as well as data about the edges connecting such nodes in the graph such as their relationship, over time.

FIG. **3** is a diagram of an exemplary midserver architecture between multiple office locations. A cloud service **310** exists which connects to a may connect to a main office **340** but not a satellite office **330** over a network such as the Internet, with a VPN **320** connected between the networks of the offices. A satellite office **330** contains numerous assets including log sources **331**, user endpoints **332**, and a server or servers **333** which include the functionality of an Active Directory (AD) server **334** and domain controller **335**. Also operating on a satellite office **330** is firewall **336**, in addition to firewall on a main office's network **347**, which provides basic security to a satellite office's network **330** and a main office's network **340**. Connected via a VPN **320** with a satellite office **330** is a main office **340**, which comprises many of the same components, including log sources **341**, at least one user endpoint **342**, and a group of servers **343** including at least an AD server **345** and domain controller **346**, as well as a midserver **344**, which may communicate with a satellite office **330** to provide access to midserver functionality without using the satellite office's **330** bandwidth to external networks. Midservers **344** may be deployed as a single instance, or as a cluster depending on the traffic volume leaving the office **340** premise to support high availability operational requirements. These servers may be co-located with the domain controllers **346** and other servers **343**, but may be placed anywhere on the network. The exact number and configuration of midservers **344** may be tailored to the organizational environment and the specific overall network architecture. It is possible to place a midserver **344** (or cluster of such) at the main office **340** only, as shown in FIG. **3**. In this configuration, the agents (or log source **331**) installed at the satellite office **330** will forward all traffic across the VPN connection **320** to the Midserver **344** at the Main Office **340**, which will then forward the traffic to the cloud infrastructure **310** via the gateway at that location.

FIG. **4** is diagram of another exemplary midserver architecture between multiple office locations. An alternative configuration compared to FIG. **3** is shown, placing one or more midservers at the satellite office and allowing traffic to egress the network locally instead of through a VPN connection to other locations. A cloud service **410** exists which connects directly to a main office **430** and a satellite office **420** over a network such as the Internet. A satellite office **420** contains numerous assets including log sources **421**, user endpoints **422**, and a server or servers **423** which include the functionality of a midserver **424**, an Active Directory (AD) server **425**, and a domain controller **426**. Also operating on a satellite office **420** is firewall **427**, in addition to firewall on a main office's network **437**, which provides basic security to a satellite office's network **420** and main office network **430**. Connected also with a cloud service **410** is a main office network **430**, which comprises many of the same compo-

nents, including log sources **431**, at least one user endpoint **432**, and a group of servers **433** including at least an AD server **435** and domain controller **436**, as well as a midserver **434**, allowing for both office networks **420**, **430** to have midserver functionality without requiring a direct or virtual connection.

FIG. **5**A is a partial diagram of an exemplary advanced cyber-decision platform utilizing midserver architecture. A plurality of software agents may monitor an organization's network usage, including but not limited to a Kerberos messaging capture (PcapKrb) agent **501** continuous monitoring (Application Performance Monitoring) agents **502**, Osquery agents **503**, active directory monitoring (ADMon) agents **504**, and other agents **505** which may include, for example, data received from system log (syslog) data stores. The plurality of network monitoring agents may feed into a midserver or midservers **510** that may contain message and data processing containerized services, for example: a RabbitMQ container **511**, an NGINX container **512**, a system log container **513**, a continuous monitoring module **514**, an Osquery engine **515**. The midserver **510** The midserver **510** may communicate through a network firewall **520**, to a reverse proxy **531** which may mask the external-facing properties of an internal server **532** of a cloud service. A reverse proxy **531** may forward relevant data, or all data, received from a midserver **510**, to an internal server **532**, which utilizes a load balancer **533** to process data efficiently and effectively despite possibly asymmetrical or massive network loads, or dynamically changing loads.

FIG. **5**B is a partial diagram of an exemplary advanced cyber-decision platform utilizing midserver architecture. An observed system **540** is a system that is monitored by an exemplary advanced cyber-decision platform that may communicate with a midserver **510**, and may contain at least a message digestion and management service such as RabbitMQ **541**, a log listener **542** which communicates with a system log server **543** for the purpose of managing, monitoring, and storing system logs. An observed system may also include an Observer Reporting Server (ORS) **544**, which may communicate with an Osquery Agent Handler **545**, allowing management, recording, and monitoring of users and systems who use Osquery or a similar system to query a device or server similarly to a database, as is the purpose of Osquery. Also present is a ConMon Agent Handler **546** which my operate as an interface to continuous monitoring connected systems, acting as an interface for a ConMon service **547**, which receives further input from systems illustrated in FIG. **5**C and may communicate with a statistics aggregator **548**.

FIG. **5**C is a partial diagram of an exemplary advanced cyber-decision platform utilizing midserver architecture. Data flows from an observed system **540** into a directed computational graph (DCG) **554**, and a Multivariate Time-Series Database (MDTSDB) **556**. Data from a DCG **554** may move to an enrichment service **553**, connected to a plurality of differently structured databases such as MySQL **552** and Redis **551**, an enrichment service being able to store and record relevant graph data in these databases **552**, **551** and also forward related stored data to a DCG **554**, for the purpose of increased accuracy with data processing. A DCG **554** also may send data to a multi-dimensional time series database (MDTSDB) service **556** which relates all received data and records the temporal metadata, resulting in a multidimensional temporal graph with which to relate data, as generated with the help of a graphstack service **555**. A graphstack service manages data received from a MDTSDB service **556** and produces the final graph results, with both the results and operation of the MDTSDB **556** and graphstack service **555** being viewable from a cloud service's front end **561**, which may also communicate with a plurality of datastores **557**, **559**, **560**. A graphstack service **555** may also forward data to an enrichment service **553** for storage in the connected databases **551**, **552**, allowing for a constant stream of graph data to be maintained. Lastly, an incident service **558** may be used to receive incident or error data from a directed computational graph **554**, recording these incidents in a plurality of databases **559**, **560**.

FIG. **6** is a diagram showing an exemplary architecture and methodology **600** for midserver deployment, automated onboarding of data, and endpoint transparent data transport. Midserver deployment comprises establishment of a secure connection between the midserver side **610** and the cloud-based service side **620**. After a midserver **611** is physically installed, an automated package called a midserver Open Virtual Appliance (OVA) is installed and run on the midserver **611**. The OVA in this example is a virtual image pre-installed with only the minimal software on configurations required to initate the deployment process. The OVA will initiate a bootstrap process to establish a secure Peer-to-Peer (P2P) connection to the cloud-based service side. Using ZeroTier as an example of a P2P connection, the OVA will initiate a ZeroTier Controller **612**, which is responsible for admitting members to the VPN, issuing certificates, and issuing default configuration information. ZeroTier establishes a secure P2P connection over a virtually extensible local area network (VXLAN) called the Reachback Network. Once the initial connection is requested, a representative of the cloud-based service, either onsite **613***a* or offsite **613***b*, will verify and approve the connection using a secret key. After a secure connection is established between the midserver and the cloud-based service side at an Ansible server **621**, an Ansible playbook is automatically initiated. First, the playbook downloads the most recent configuration template from a configuration controller **622**. Next it connects to a deployment vault **623** instance to retrieve the customer specific configurations including any secrets (e.g. passwords, keys, etc) which will have been previously established by a representative of the cloud-based service **613***b*. A ZeroTier network application programming interface (API) acts as an adhoc Ansible inventory and a single source of truth for which systems have previously connected to the P2P network. Then, the playbook then begins configurating the midserver **611** via an ssh connection tunnel, establishing a primary backhaul virtual private network (VPN) connection to the cloud-based service. Once this connection is made the midserver tears down the Reachback Network and all communication is done over the VPN through a firewall **616** on the customer network edge. The VPN created using this methodology then allows containerized services **614** to forward data using transport layer security (TLS) **615** to the cloud-based service, allowing for longhaul transportation of data that is transparent to the network endpoint. Some implementations may use external web serving, reverse proxying, caching, and load balancing such as external Nginx **624**, data center load balancing and caching such as DCOS Nginx **625**, and microservices and container orchestration such as Nginx Plus **626**.

FIG. **7** is an exemplary method **700** for deploying a midserver where the business enterprise network is located on, or utilizes, a cloud computing service such as Amazon Web Services (AWS) or Microsoft's Azure. In cloud computing services, all or part of the business enterprise's network is run on the servers of the cloud computing service. Use of midserver architecture where the business enterprise

utilizes cloud computing services poses difficulties because the cloud computing service infrastructure is not controlled by the business enterprise, and thus the business enterprise may not be able to authorize the installation of 3rd party software (e.g., Kerberos agents, and other software agents that monitor network traffic) on all or a part of its network. The solution to this problem is to utilize the cloud computing service's functions that allow continuous streaming of virtual machine network traffic to a network packet collector or analytics tool. Using Microsoft's Azure Active Directory service and its virtual network terminal access point (vTAP) as an example, the Azure Active Directory (Azure AD) is a cloud-based identity and access management service that allows employees of a business enterprise to access both external and internal resources. The vTAP function allows continuous streaming of cloud computing service network traffic to a network packet collector or analytics tool, and operates in a manner roughly equivalent to traditional port mirroring. Where the business enterprise manages its own network of virtual machines on the cloud computing service, it may still be possible to install software agents, although use of a continuous streaming function may be more efficient. Where the business enterprise uses the cloud computing service for managed domain services, however, the business enterprise does not have authorization to install agents, and the continuous streaming (port mirroring) function will need to be used to deploy a midserver architecture. In this example, a customer (business enterprise) virtual network **720** is established within the cloud computing service **710**. The customer virtual network comprises a number of virtual machines **721***a-n*, operated on one or more of the cloud computing service **710** servers **722**. Separately, a cloud-based service network is established on the cloud computing service **710** and is controlled by the cloud-based service **740** to which data is to be forwarded. Using the continuous streaming function available on the cloud computing service **710**, for example vTAP for the Azure Active Directory service, a virtual machine on the cloud-based service network **730** is established as a virtual network peer VM **731** to the customer virtual network **720**, and all data from the customer virtual network **720** is continuously streamed from the cloud computing service server(s) **722** to the virtual network peer VM **731**, which forwards the data to the cloud-based service **740**.

FIG. **8** is another exemplary method **800** for deploying a midserver where the business enterprise network is located on, or utilizes, a cloud computing service such as Amazon Web Services (AWS) or Microsoft's Azure. In this example, a customer (business enterprise) virtual network **820** is established within the cloud computing service **810**. The customer virtual network comprises a number of virtual machines **821***a-n*, operated on one or more of the cloud computing service **810** servers **822**. The customer also operates on the customer virtual network **820** a virtual network peer VM **823** that is configured to aggregate and forward data to the cloud-based service **830**, using the continuous streaming function available on the cloud computing service **810**, for example vTAP for the Azure Active Directory service. In this manner, all data from the customer virtual network **820** is continuously streamed from the cloud computing service server(s) **822** to the virtual network peer VM **823**, which forwards the data to the cloud-based service **830**.

FIG. **9** is a diagram showing an overview of the methodology of two of several known Kerberos attacks. In the so-called "golden ticket" attack **900**, after a client computer **901** has been compromised, a forged ticket is sent to the domain controller **902**, which grants access to all servers in the network, and the host server **903** is accessed using the granted access. In the so-called "silver ticket" attack **910**, after a client computer **911** has been compromised, a forged ticket granting service (TGS) ticket is sent directly to the host server **913** to be attacked. The host server receiving the forged TGS ticket grants access to the client computer **911** to grant access tickets, which are then used to access the host server **913**. Unlike in the golden ticket attack, in the silver ticket attack, the domain controller **912** is not involved in granting access.

FIG. **10** is a diagram showing an overview of the use of a ledger of Kerberos requests and responses to provide security against Kerberos attacks **1000**. In a typical Kerberos authentication interaction, several requests and responses are sent between a user computer **1001**, a domain controller, **1002**, and a Kerberos-enabled service **1003**. Maintaining a ledger **1004** of these requests and responses effectively transforms the Kerberos protocol from a stateless to a stateful one, allowing confirmation of the validity of traffic and providing additional protection against Kerberos attacks.

FIG. **11**A is a partial diagram of a security analytic workflow validating an exemplary Kerberos ticket-based security protocol for use in an observed system in order to detect common attacks against the Kerberos protocol including those known by the industry as Golden Ticket, Silver Ticket, DCSync, and DCShadow. A messaging source **1101**, such as RabbitMQ or NGINX, forwards received data messages to a FPRS split stage **1102**, where specific message states are determined and separated to identify high priority tickets, and sent through appropriate processing pipelines. An "OTHER" stage **1103** represents unknown ticket priority and is forwarded to a JSON field extractor **1104** which extracts relevant data fields in Javascript Object Notation (JSON), which is a common data format for object representation in data analytics. A stage where no message is present **1105** represents a ticket with missing information, therefore being sent for an enrichment stage **1106** before being sent to a similar JSON field extractor **1104**. An error stage **1107** may also be reached, resulting in the ticket being sent to an Abstract Syntax Notation One (ASN1) decoder **1108**, ASN1 being a standard interface description language for defining data structures. If an otherwise normal message is present for a ticket stage **1109**, it is sent directly for JSON field extraction **1104**.

FIG. **11**B is a partial diagram of a security analytic workflow validating an exemplary Kerberos ticket-based security protocol for use in an observed system in order to detect common attacks against the Kerberos protocol including those known by the industry as Golden Ticket, Silver Ticket, DCSync, and DCShadow. JSON field data that is extracted **1104** is then forwarded for being placed into a MDTSDB **1111**, resulting in it being stored for later use in a temporal knowledge graph. After an error message is ASN1 decoded **1108**, it is sent for JSON field extraction **1112**, before also being recorded in a MDTSDB **1113**. Once a no-message stage has been enriched **1106**, it is sent to a secondary FPRS split stage **1114**, where the enriched ticket is now determined to possess either an unknown or "OTHER" stage message **1115** and not stored anywhere **1116**, or it has a DC_SYNC **1117** or DC_SHADOW **1120** message. In either of the latter two cases a the message is converted into an exemplary advanced malware protection (AMP) alert **1118**, **1121** and stored in an MDTSDB **1119**.

Hardware Architecture

Generally, the techniques disclosed herein may be implemented on hardware or a combination of software and hardware. For example, they may be implemented in an operating system kernel, in a separate user process, in a library package bound into network applications, on a specially constructed machine, on an application-specific integrated circuit ("ASIC"), or on a network interface card.

Software/hardware hybrid implementations of at least some of the aspects disclosed herein may be implemented on a programmable network-resident machine (which should be understood to include intermittently connected network-aware machines) selectively activated or reconfigured by a computer program stored in memory. Such network devices may have multiple network interfaces that may be configured or designed to utilize different types of network communication protocols. A general architecture for some of these machines may be described herein in order to illustrate one or more exemplary means by which a given unit of functionality may be implemented. According to specific aspects, at least some of the features or functionalities of the various aspects disclosed herein may be implemented on one or more general-purpose computers associated with one or more networks, such as for example an end-user computer system, a client computer, a network server or other server system, a mobile computing device (e.g., tablet computing device, mobile phone, smartphone, laptop, or other appropriate computing device), a consumer electronic device, a music player, or any other suitable electronic device, router, switch, or other suitable device, or any combination thereof. In at least some aspects, at least some of the features or functionalities of the various aspects disclosed herein may be implemented in one or more virtualized computing environments (e.g., network computing clouds, virtual machines hosted on one or more physical computing machines, or other appropriate virtual environments).

Referring now to FIG. **12**, there is shown a block diagram depicting an exemplary computing device **10** suitable for implementing at least a portion of the features or functionalities disclosed herein. Computing device **10** may be, for example, any one of the computing machines listed in the previous paragraph, or indeed any other electronic device capable of executing software- or hardware-based instructions according to one or more programs stored in memory. Computing device **10** may be configured to communicate with a plurality of other computing devices, such as clients or servers, over communications networks such as a wide area network a metropolitan area network, a local area network, a wireless network, the Internet, or any other network, using known protocols for such communication, whether wireless or wired.

In one embodiment, computing device **10** includes one or more central processing units (CPU) **12**, one or more interfaces **15**, and one or more busses **14** (such as a peripheral component interconnect (PCI) bus). When acting under the control of appropriate software or firmware, CPU **12** may be responsible for implementing specific functions associated with the functions of a specifically configured computing device or machine. For example, in at least one embodiment, a computing device **10** may be configured or designed to function as a server system utilizing CPU **12**, local memory **11** and/or remote memory **16**, and interface(s) **15**. In at least one embodiment, CPU **12** may be caused to perform one or more of the different types of functions and/or operations under the control of software modules or components, which for example, may include an operating system and any appropriate applications software, drivers, and the like.

CPU **12** may include one or more processors **13** such as, for example, a processor from one of the Intel, ARM, Qualcomm, and AMD families of microprocessors. In some embodiments, processors **13** may include specially designed hardware such as application-specific integrated circuits (ASICs), electrically erasable programmable read-only memories (EEPROMs), field-programmable gate arrays (FPGAs), and so forth, for controlling operations of computing device **10**. In a specific embodiment, a local memory **11** (such as non-volatile random access memory (RAM) and/or read-only memory (ROM), including for example one or more levels of cached memory) may also form part of CPU **12**. However, there are many different ways in which memory may be coupled to system **10**. Memory **11** may be used for a variety of purposes such as, for example, caching and/or storing data, programming instructions, and the like. It should be further appreciated that CPU **12** may be one of a variety of system-on-a-chip (SOC) type hardware that may include additional hardware such as memory or graphics processing chips, such as a QUALCOMM SNAPDRAGON™ or SAMSUNG EXYNOS™ CPU as are becoming increasingly common in the art, such as for use in mobile devices or integrated devices.

As used herein, the term "processor" is not limited merely to those integrated circuits referred to in the art as a processor, a mobile processor, or a microprocessor, but broadly refers to a microcontroller, a microcomputer, a programmable logic controller, an application-specific integrated circuit, and any other programmable circuit.

In one embodiment, interfaces **15** are provided as network interface cards (NICs). Generally, NICs control the sending and receiving of data packets over a computer network; other types of interfaces **15** may for example support other peripherals used with computing device **10**. Among the interfaces that may be provided are Ethernet interfaces, frame relay interfaces, cable interfaces, DSL interfaces, token ring interfaces, graphics interfaces, and the like. In addition, various types of interfaces may be provided such as, for example, universal serial bus (USB), Serial, Ethernet, FIREWIRE™, THUNDERBOLT™, PCI, parallel, radio frequency (RF), BLUETOOTH™, near-field communications (e.g., using near-field magnetics), 802.11 (WiFi), frame relay, TCP/IP, ISDN, fast Ethernet interfaces, Gigabit Ethernet interfaces, Serial ATA (SATA) or external SATA (ESATA) interfaces, high-definition multimedia interface (HDMI), digital visual interface (DVI), analog or digital audio interfaces, asynchronous transfer mode (ATM) interfaces, high-speed serial interface (HSSI) interfaces, Point of Sale (POS) interfaces, fiber data distributed interfaces (FDDIs), and the like. Generally, such interfaces **15** may include physical ports appropriate for communication with appropriate media. In some cases, they may also include an independent processor (such as a dedicated audio or video processor, as is common in the art for high-fidelity A/V hardware interfaces) and, in some instances, volatile and/or non-volatile memory (e.g., RAM).

Although the system shown in FIG. **12** illustrates one specific architecture for a computing device **10** for implementing one or more of the inventions described herein, it is by no means the only device architecture on which at least a portion of the features and techniques described herein may be implemented. For example, architectures having one or any number of processors **13** may be used, and such processors **13** may be present in a single device or distributed among any number of devices. In one embodiment, a single processor **13** handles communications as well as routing computations, while in other embodiments a sepa-

rate dedicated communications processor may be provided. In various embodiments, different types of features or functionalities may be implemented in a system according to the invention that includes a client device (such as a tablet device or smartphone running client software) and server systems (such as a server system described in more detail below).

Regardless of network device configuration, the system of the present invention may employ one or more memories or memory modules (such as, for example, remote memory block **16** and local memory **11**) configured to store data, program instructions for the general-purpose network operations, or other information relating to the functionality of the embodiments described herein (or any combinations of the above). Program instructions may control execution of or comprise an operating system and/or one or more applications, for example. Memory **16** or memories **11**, **16** may also be configured to store data structures, configuration data, encryption data, historical system operations information, or any other specific or generic non-program information described herein.

Because such information and program instructions may be employed to implement one or more systems or methods described herein, at least some network device embodiments may include nontransitory machine-readable storage media, which, for example, may be configured or designed to store program instructions, state information, and the like for performing various operations described herein. Examples of such nontransitory machine-readable storage media include, but are not limited to, magnetic media such as hard disks, floppy disks, and magnetic tape; optical media such as CD-ROM disks; magneto-optical media such as optical disks, and hardware devices that are specially configured to store and perform program instructions, such as read-only memory devices (ROM), flash memory (as is common in mobile devices and integrated systems), solid state drives (SSD) and "hybrid SSD" storage drives that may combine physical components of solid state and hard disk drives in a single hardware device (as are becoming increasingly common in the art with regard to personal computers), memristor memory, random access memory (RAM), and the like. It should be appreciated that such storage means may be integral and non-removable (such as RAM hardware modules that may be soldered onto a motherboard or otherwise integrated into an electronic device), or they may be removable such as swappable flash memory modules (such as "thumb drives" or other removable media designed for rapidly exchanging physical storage devices), "hot-swappable" hard disk drives or solid state drives, removable optical storage discs, or other such removable media, and that such integral and removable storage media may be utilized interchangeably. Examples of program instructions include both object code, such as may be produced by a compiler, machine code, such as may be produced by an assembler or a linker, byte code, such as may be generated by for example a JAVA™ compiler and may be executed using a Java virtual machine or equivalent, or files containing higher level code that may be executed by the computer using an interpreter (for example, scripts written in Python, Perl, Ruby, Groovy, or any other scripting language).

In some embodiments, systems according to the present invention may be implemented on a standalone computing system. Referring now to FIG. **13**, there is shown a block diagram depicting a typical exemplary architecture of one or more embodiments or components thereof on a standalone computing system. Computing device **20** includes processors **21** that may run software that carry out one or more functions or applications of embodiments of the invention, such as for example a client application **24**. Processors **21** may carry out computing instructions under control of an operating system **22** such as, for example, a version of MICROSOFT WINDOWS™ operating system, APPLE OSX™ or iOS™ operating systems, some variety of the Linux operating system, ANDROID™ operating system, or the like. In many cases, one or more shared services **23** may be operable in system **20**, and may be useful for providing common services to client applications **24**. Services **23** may for example be WINDOWS™ services, user-space common services in a Linux environment, or any other type of common service architecture used with operating system **21**. Input devices **28** may be of any type suitable for receiving user input, including for example a keyboard, touchscreen, microphone (for example, for voice input), mouse, touchpad, trackball, or any combination thereof. Output devices **27** may be of any type suitable for providing output to one or more users, whether remote or local to system **20**, and may include for example one or more screens for visual output, speakers, printers, or any combination thereof. Memory **25** may be random-access memory having any structure and architecture known in the art, for use by processors **21**, for example to run software. Storage devices **26** may be any magnetic, optical, mechanical, memristor, or electrical storage device for storage of data in digital form (such as those described above, referring to FIG. **12**). Examples of storage devices **26** include flash memory, magnetic hard drive, CD-ROM, and/or the like.

In some embodiments, systems of the present invention may be implemented on a distributed computing network, such as one having any number of clients and/or servers. Referring now to FIG. **14**, there is shown a block diagram depicting an exemplary architecture **30** for implementing at least a portion of a system according to an embodiment of the invention on a distributed computing network. According to the embodiment, any number of clients **33** may be provided. Each client **33** may run software for implementing client-side portions of the present invention; clients may comprise a system **20** such as that illustrated in FIG. **13**. In addition, any number of servers **32** may be provided for handling requests received from one or more clients **33**. Clients **33** and servers **32** may communicate with one another via one or more electronic networks **31**, which may be in various embodiments any of the Internet, a wide area network, a mobile telephony network (such as CDMA or GSM cellular networks), a wireless network (such as WiFi, WiMAX, LTE, and so forth), or a local area network (or indeed any network topology known in the art; the invention does not prefer any one network topology over any other). Networks **31** may be implemented using any known network protocols, including for example wired and/or wireless protocols.

In addition, in some embodiments, servers **32** may call external services **37** when needed to obtain additional information, or to refer to additional data concerning a particular call. Communications with external services **37** may take place, for example, via one or more networks **31**. In various embodiments, external services **37** may comprise web-enabled services or functionality related to or installed on the hardware device itself. For example, in an embodiment where client applications **24** are implemented on a smartphone or other electronic device, client applications **24** may obtain information stored in a server system **32** in the cloud or on an external service **37** deployed on one or more of a particular enterprise's or user's premises.

In some embodiments of the invention, clients **33** or servers **32** (or both) may make use of one or more specialized services or appliances that may be deployed locally or remotely across one or more networks **31**. For example, one or more databases **34** may be used or referred to by one or more embodiments of the invention. It should be understood by one having ordinary skill in the art that databases **34** may be arranged in a wide variety of architectures and using a wide variety of data access and manipulation means. For example, in various embodiments one or more databases **34** may comprise a relational database system using a structured query language (SQL), while others may comprise an alternative data storage technology such as those referred to in the art as "NoSQL" (for example, HADOOP CASSANDRA™, GOOGLE BIGTABLE™, and so forth). In some embodiments, variant database architectures such as column-oriented databases, in-memory databases, clustered databases, distributed databases, or even flat file data repositories may be used according to the invention. It will be appreciated by one having ordinary skill in the art that any combination of known or future database technologies may be used as appropriate, unless a specific database technology or a specific arrangement of components is specified for a particular embodiment herein. Moreover, it should be appreciated that the term "database" as used herein may refer to a physical database machine, a cluster of machines acting as a single database system, or a logical database within an overall database management system. Unless a specific meaning is specified for a given use of the term "database", it should be construed to mean any of these senses of the word, all of which are understood as a plain meaning of the term "database" by those having ordinary skill in the art.

Similarly, most embodiments of the invention may make use of one or more security systems **36** and configuration systems **35**. Security and configuration management are common information technology (IT) and web functions, and some amount of each are generally associated with any IT or web systems. It should be understood by one having ordinary skill in the art that any configuration or security subsystems known in the art now or in the future may be used in conjunction with embodiments of the invention without limitation, unless a specific security **36** or configuration system **35** or approach is specifically required by the description of any specific embodiment.

FIG. **15** shows an exemplary overview of a computer system **40** as may be used in any of the various locations throughout the system. It is exemplary of any computer that may execute code to process data. Various modifications and changes may be made to computer system **40** without departing from the broader scope of the system and method disclosed herein. Central processor unit (CPU) **41** is connected to bus **42**, to which bus is also connected memory **43**, nonvolatile memory **44**, display **47**, input/output (I/O) unit **48**, and network interface card (NIC) **53**. I/O unit **48** may, typically, be connected to keyboard **49**, pointing device **50**, hard disk **52**, and real-time clock **51**. NIC **53** connects to network **54**, which may be the Internet or a local network, which local network may or may not have connections to the Internet. Also shown as part of system **40** is power supply unit **45** connected, in this example, to a main alternating current (AC) supply **46**. Not shown are batteries that could be present, and many other devices and modifications that are well known but are not applicable to the specific novel functions of the current system and method disclosed herein. It should be appreciated that some or all components illustrated may be combined, such as in various integrated applications, for example Qualcomm or Samsung system-on-a-chip (SOC) devices, or whenever it may be appropriate to combine multiple capabilities or functions into a single hardware device (for instance, in mobile devices such as smartphones, video game consoles, in-vehicle computer systems such as navigation or multimedia systems in automobiles, or other integrated hardware devices).

In various embodiments, functionality for implementing systems or methods of the present invention may be distributed among any number of client and/or server components. For example, various software modules may be implemented for performing various functions in connection with the present invention, and such modules may be variously implemented to run on server and/or client components.

The skilled person will be aware of a range of possible modifications of the various embodiments described above. Accordingly, the present invention is defined by the claims and their equivalents.

What is claimed is:

1. A system for ingestion of data into a cloud-based service from an external network, comprising:

a midserver comprising at least a processor, a memory, and a plurality of programming instructions stored in the memory and operating on the processor, wherein the plurality of programming instructions, when operating on the processor, cause the processor to:

automatically install a virtual appliance software application, the virtual appliance software application configured to automatically load a plurality of stored configurations on the midserver;

establish a secure network connection to an external network;

receive data over a local network from a plurality of computing devices;

apply a plurality of transformations to at least a portion of the received data; and

retransmit the received data over the secure connection as a single data stream.

2. The system of claim **1**, wherein the containerized services include one or more of the following types of containerized services: traffic processors, sensors, management services, and utilities.

3. The system of claim **1**, wherein the midserver is installed at the same location from which some part of the external network is operated.

4. A method for ingestion of data into a cloud-based service from an external network, comprising the steps of:

installing a midserver comprising at least a processor, a memory, and a plurality of programming instructions stored in the memory and operating on the processor;

automatically installing, using the midserver, a virtual appliance software application, the virtual appliance software application configured to automatically load a plurality of stored configurations on the midserver;

establishing a secure network connection from the midserver to an external network;

receiving data over a local network from a plurality of computing devices;

applying a plurality of transformations to at least a portion of the received data; and

retransmitting the received data over the secure connection as a single data stream.

5. The method of claim **4**, further comprising the step of including one or more of the following types of containerized services: traffic processors, sensors, management services, and utilities.

6. The method of claim 4, further comprising the step of installing the midserver at the same location from which some part of the external network is operated.

* * * * *