

(12) **United States Patent**
Gogoi et al.

(10) **Patent No.:** **US 12,231,703 B2**
(45) **Date of Patent:** ***Feb. 18, 2025**

(54) **BITRATE AND PIPELINE PRESERVATION FOR CONTENT PRESENTATION**

(71) Applicant: **OpenTV, Inc.**, San Francisco, CA (US)

(72) Inventors: **Amarendra N. Gogoi**, Fremont, CA (US); **Sanjay Kumar Gupta**, Bangalore (IN); **Ravikant Swami**, Bangalore (IN)

(73) Assignee: **OpenTV, Inc.**, San Francisco, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **18/480,918**

(22) Filed: **Oct. 4, 2023**

(65) **Prior Publication Data**
US 2024/0107090 A1 Mar. 28, 2024

(52) **U.S. Cl.**
CPC **H04N 21/23655** (2013.01); **H04L 65/70** (2022.05); **H04N 21/2662** (2013.01)

(58) **Field of Classification Search**
None
See application file for complete search history.

(56) **References Cited**
U.S. PATENT DOCUMENTS
8,532,171 B1 9/2013 Narayanan et al.
8,887,215 B2 11/2014 Fisher
(Continued)

FOREIGN PATENT DOCUMENTS
CN 103354999 10/2013
CN 105393516 3/2016
(Continued)

OTHER PUBLICATIONS
“International Application Serial No. PCT US2018 046723, International Search Report mailed Oct. 22, 2018”, 2 pgs.
(Continued)

Related U.S. Application Data

(63) Continuation of application No. 17/454,169, filed on Nov. 9, 2021, now Pat. No. 11,825,139, which is a (Continued)


(30) **Foreign Application Priority Data**
Sep. 8, 2017 (IN) 201741031917

(51) **Int. Cl.**
H04N 21/2365 (2011.01)
H04L 65/70 (2022.01)
H04N 21/2662 (2011.01)

Primary Examiner — Stefan Gadomski
(74) *Attorney, Agent, or Firm* — Maier & Maier, PLLC

(57) **ABSTRACT**
Systems and methods for optimizing a content change process are provided. In example embodiments, a digital receiver causes playback of a first piece of content. The digital receiver receives a selection of a new piece of content for playback during the playback of the first piece of content. In response to the receiving of the selection, the digital receiver maintains a bitrate used for playback of the first piece of content to initiate playback of the new piece of content.

20 Claims, 5 Drawing Sheets



Related U.S. Application Data

continuation of application No. 16/645,598, filed as application No. PCT/US2018/046723 on Aug. 14, 2018, now Pat. No. 11,184,652.

(56) References Cited**U.S. PATENT DOCUMENTS**

9,244,678	B1	1/2016	Hatch et al.	
11,184,652	B2	11/2021	Gogoi et al.	
11,825,139	B2	11/2023	Gogoi et al.	
2004/0111526	A1 *	6/2004	Baldwin	H04N 21/44016 348/E5.005
2006/0215760	A1	9/2006	Monaco	
2008/0189352	A1 *	8/2008	Mitchell	H04L 1/22 709/201
2008/0195743	A1	8/2008	Brueck et al.	
2009/0254657	A1	10/2009	Melnyk et al.	
2010/0091888	A1	4/2010	Nemiroff	
2010/0118697	A1	5/2010	Shumate	
2010/0158101	A1	6/2010	Wu et al.	
2010/0329354	A1	12/2010	Kellerman et al.	
2011/0225302	A1	9/2011	Park et al.	
2011/0296047	A1	12/2011	Orr	
2011/0296458	A1	12/2011	Di et al.	
2012/0099022	A1	4/2012	Sundy et al.	
2012/0177101	A1	7/2012	Van Der Schaar	
2013/0097309	A1	4/2013	Ma et al.	
2013/0142499	A1	6/2013	Major et al.	
2014/0040498	A1 *	2/2014	Oyman	H04W 4/02 709/231
2014/0149497	A1	5/2014	Takagaki	
2014/0359150	A1 *	12/2014	Oran	H04N 21/64761 709/231
2015/0019629	A1 *	1/2015	Giladi	H04L 67/02 709/203
2015/0023404	A1 *	1/2015	Li	H04L 65/612 375/240.02
2015/0039726	A1	2/2015	Hoffert et al.	
2015/0052236	A1	2/2015	Friedrich et al.	
2015/0172352	A1	6/2015	Gopalakrishnan et al.	
2015/0188962	A1	7/2015	Bulava et al.	
2015/0281303	A1	10/2015	Yousef et al.	
2016/0119657	A1	4/2016	Sun	
2016/0173954	A1	6/2016	Speelmans et al.	
2016/0173957	A1	6/2016	Dutta et al.	
2016/0234504	A1	8/2016	Good et al.	
2017/0034233	A1	2/2017	Funge et al.	
2017/0064400	A1	3/2017	Riegel et al.	
2017/0070551	A1	3/2017	Phillips et al.	
2017/0070554	A1	3/2017	Mayrand	
2017/0070757	A1	3/2017	Phillips et al.	
2017/0070758	A1	3/2017	Phillips et al.	
2017/0085933	A1	3/2017	Czeck, Jr. et al.	
2017/0188056	A1	6/2017	Do et al.	
2017/0188072	A1	6/2017	Major	
2017/0220283	A1	8/2017	Zhang et al.	
2017/0230708	A1	8/2017	Phillips et al.	
2017/0244924	A1	8/2017	Shintani et al.	
2018/0063590	A1	3/2018	Her et al.	
2018/0205778	A1	7/2018	Forman et al.	
2018/0241796	A1	8/2018	Srinivasan et al.	
2018/0338170	A1	11/2018	Stokking et al.	
2018/0375915	A1	12/2018	Sridhar et al.	
2019/0334803	A1	10/2019	Ickin et al.	
2020/0099605	A1	3/2020	Mayrand	
2020/0267428	A1	8/2020	Gogoi et al.	
2022/0070510	A1	3/2022	Gogoi et al.	

FOREIGN PATENT DOCUMENTS

CN	106717001	5/2017
CN	107005553	8/2017
CN	111194565	5/2020
EP	1775953	4/2007
EP	3050307	8/2016

EP	3679738	10/2021
EP	3965466	6/2023
IN	202047011998	5/2020
TW	201229751	7/2012
TW	201931861	8/2019
TW	1826387	12/2023
TW	202415077	4/2024
WO	2016085094	6/2016
WO	WO-2016099356	A1 * 6/2016
WO	2019050660	3/2019

OTHER PUBLICATIONS

"International Application Serial No. PCT US2018 046723, Written Opinion mailed Oct. 22, 2018", 9 pgs.

"International Application Serial No. PCT US2018 046723, International Preliminary Report on Patentability mailed Apr. 1, 2020", 4 pgs.

"European Application Serial No. 18853974.6, Extended European Search Report mailed Sep. 29, 2020", 9 pgs.

"U.S. Appl. No. 16/645,598, Non Final Office Action mailed Jan. 7, 2021", 17 pgs.

"U.S. Appl. No. 16/645,598, Response filed Apr. 7, 2021 to Non Final Office Action mailed Jan. 7, 2021", 13 pgs.

"European Application Serial No. 18853974.6, Response filed Mar. 25, 2021 to Extended European Search Report mailed Sep. 29, 2020", 21 pgs.

"U.S. Appl. No. 16/645,598, Notice of Allowance mailed Jul. 21, 2021", 10 pgs.

"European Application Serial No. 21204823.5, Extended European Search Report mailed Dec. 8, 2021", 7 pgs.

"Taiwanese Application Serial No. 107126926, First Office Action mailed Dec. 10, 2021", with Concise Statement of Relevance, 8 pages.

"Taiwanese Application Serial No. 107126926, Response Filed Feb. 17, 2022 to First Office Action mailed Dec. 10, 2021", with English claims, 23 pages.

"Indian Application Serial No. 202047011998, First Examination Report mailed Apr. 7, 2022", 7 pgs.

"European Application Serial No. 21204823.5, Response filed Aug. 16, 2022 to Extended European Search Report mailed Dec. 8, 2021", 11 pgs.

"Taiwanese Application Serial No. 107126926, Decision of Rejection mailed Sep. 30, 2022", with machine English Translation, 15 pages.

"Indian Application Serial No. 202047011998, Response filed Oct. 6, 2022 to First Examination Report mailed Apr. 7, 2022", 18 pgs.

"U.S. Appl. No. 17/454,169, Non Final Office Action mailed Dec. 22, 2022", 28 pgs.

"Chinese Application Serial No. 201880065328.8, Office Action mailed Feb. 3, 2023", with machine translation, 16 pgs.

"U.S. Appl. No. 17/454,169, Response filed Mar. 22, 2023 to Non Final Office Action mailed Dec. 22, 2022", 11 pgs.

"U.S. Appl. No. 17/454,169, Examiner Interview Summary mailed Mar. 23, 2023", 2 pgs.

"Chinese Application Serial No. 201880065328.8, Response filed Mar. 31, 2023 to Office Action mailed Feb. 3, 2023", w English Claims, 58 pgs.

"International Application Serial No. PCT US2018 046723, Response filed Dec. 20, 2018 to Written Opinion mailed Oct. 22, 2018", 14 pgs.

"U.S. Appl. No. 17/454,169, Notice of Allowance mailed Jul. 5, 2023", 9 pgs.

"U.S. Appl. No. 17/454,169, Corrected Notice of Allowability mailed Aug. 9, 2023", 2 pgs.

"U.S. Appl. No. 17/454,169, 312 Amendment filed Sep. 14, 2023", 8 pgs.

"U.S. Appl. No. 17/454,169, PTO Response to Rule 312 Communication mailed Sep. 28, 2023", 2 pgs.

"U.S. Appl. No. 17/454,169, Supplemental Notice of Allowability mailed Oct. 19, 2023", 2 pgs.

"Taiwanese Application Serial No. 112146227, Office Action mailed Jan. 15, 2024", w o English Translation, 5 pgs.

(56)

References Cited

OTHER PUBLICATIONS

“Taiwanese Application Serial No. 112146227, Response filed Apr. 12, 2024 to Office Action mailed Jan. 15, 2024”, w english claims, 14 pgs.

Bouten, Niels, “In-Network Quality Optimization for Adaptive Video Streaming Services”, IEEE Transactions on Multimedia, (Oct. 13, 2014), 14 pgs.

Suman, Kalyan Mandal, “Intelligent Pre-fetching to Reduce Channel Switching Delay in IPTV Systems”, Internet Citation, (Jan. 1, 2009), 1-6.

Toshiaki, Ako, “A Novel Multichannel Streaming Scheme to Reduce Channel Switching Delay in Application Layer Multicast”, IEEE Systems Journal vol. 5, No. 4, (Dec. 1, 2011), 545-554.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5

1

**BITRATE AND PIPELINE PRESERVATION
FOR CONTENT PRESENTATION****CLAIM OF PRIORITY**

This application is a continuation of U.S. patent application Ser. No. 17/454,169 filed on Nov. 9, 2021, which is a continuation of U.S. patent application Ser. No. 16/645,598, filed on Mar. 9, 2020, which is a U.S. National Stage filing from PCT Application No. PCT/US2018/046723, filed on August 14, 2018, which claims priority to Indian Application Serial No. 201741031917, filed on Sep. 8, 2017, which are incorporated herein by reference in their entireties.

FIELD

The present disclosure generally relates to machines configured to the technical field of special-purpose machines that optimizes a content change process (e.g., channel change) including computerized variants of such special-purpose machines and improvements to such variants, and to the technologies by which such special-purpose machines become improved compared to other special-purpose machines that facilitate optimizing content changes. In particular, the present disclosure addresses systems and methods for preserving a download bitrate and a content playback pipeline during a content change process.

BACKGROUND

Conventionally, during a switch in content (e.g., caused by a channel change or a selection of a different piece of content), a delay occurs as certain information is obtained before the new piece of content (e.g., program, movie, show) is rendered and displayed. Additionally, for adaptive bitrate streaming content, the content typically starts streaming or download at a low (or lowest) bitrate before slowly increasing in bitrate until an optimum bitrate is achieved. This results in initial video or images being grainy. Furthermore, the delay may be increased by a need to build a content playback pipeline each time a change in content occurs.

BRIEF DESCRIPTION OF DRAWINGS

Various ones of the appended drawings merely illustrate example embodiments of the present invention and cannot be considered as limiting its scope.

FIG. 1 is a diagram illustrating an example environment for optimizing content changes;

FIG. 2 is a block diagram illustrating an example embodiment of components within a digital receiver in accordance with an example embodiment.

FIG. 3 is a flow diagram of a method for optimizing a content change process in accordance with example embodiments.

FIG. 4 is a flow diagram of a method for preserving a content deliver pipeline in accordance with example embodiments.

FIG. 5 is a diagrammatic representation of a machine in an example form of a computing system within which a set of instructions may be executed for causing the machine to perform any one or more of the methodologies discussed herein, according to an example embodiment.

DETAILED DESCRIPTION

The description that follows includes systems, methods, techniques, instruction sequences, and computing machine

2

program products that embody illustrative embodiments of the present inventive subject matter. In the following description, for purposes of explanation, numerous specific details are set forth in order to provide an understanding of various embodiments of the inventive subject matter. It will be evident, however, to those skilled in the art, that embodiments of the inventive subject matter may be practiced without some or other of these specific details. In general, well-known instruction instances, protocols, structures, and techniques have not been shown in detail. Examples merely typify possible variations. Unless explicitly stated otherwise, structures (e.g., structural components, such as modules) are optional and may be combined or subdivided, and operations (e.g., in a procedure, algorithm, or other function) may vary, in sequence or be combined or subdivided.

Example embodiments described herein provide systems and methods for optimizing content changes or switch in content being viewed, such as through a channel change or selection of a different piece of content from a watchlist. In some embodiments, the system uses navigational context (e.g., the way a user is interacting with an application) to identify content of (potential) interest to a viewer. The system then prefetches metadata for the content of interest from a content provider and stores the metadata to local cache. The metadata comprises preconditions for rendering and display of a piece of content that include a minimum set of data that a system can obtain without having to decrypt the content. The prefetched metadata may be used, in example embodiments, to determine whether to preserve at least a portion of a content playback pipeline (also referred to herein as a “content deliver pipeline” or simply a “pipeline”).

Conventionally, a same piece of content is broken up into segments (e.g., 10 second segments) and each segment is available in various bitrates. A low bitrate may be grainy, while a high bitrate will normally have better image quality. Typically, when playback of a new piece of content starts, the system does not know the quality of the network bandwidth. As a result, in order to start playback as quickly as possible, conventional systems start with a lowest bitrate. Thus, every time a user switches from one content to the next content, the playback will start with the lowest bitrate and slowly increase or improve according the capability of the network. In contrast, example embodiments, preserve a previous bitrate when switching to a new piece of content. That is, when a user selects a new piece of content to playback (e.g., switching from a previous piece of content to the new piece of content), example embodiments maintain or preserve a (heuristically determined) bitrate used for streaming or downloading the previous piece of content when initiating the playback of the new piece of content. This allows for starting playback as quickly as possible while also providing better image quality from the start.

Furthermore, in conventional systems, a switch or transition in content typically causes a previous content delivery pipeline to be deconstructed (e.g., resources previous acquired are released). Subsequently, a new pipeline is created for the new piece of content (e.g., new resources are acquired). In contrast, example embodiments may maintain or preserve a portion (or an entire) content delivery pipeline (e.g., comprising a source element, a demultiplexer (“demux”), a video decoder, and an audio decoder) used to obtain the previous piece of content instead of reconstructing a pipeline (e.g., destroying the content delivery pipeline and building a new content delivery pipeline). The preservation of the pipeline also allows for playback of the new content as quickly as possible.

3

As a result, one or more of the methodologies described herein facilitate solving the technical problem of optimizing content change (e.g., reducing time for a change in channel or loading of new content) regardless of the delivery channel—whether the content is broadcast (e.g., IPTV and multicast) or over-the-top (OTT). The methodologies include causing playback, by a digital receiver, of a first piece of content and receiving a selection of a new piece of content for playback during the playback of the first piece of content. In response to the receiving of the selection, the digital receiver maintains a bitrate used for playback of the first piece of content to initiate playback of the new piece of content. The methodologies further include determining whether to preserve at least a portion of a playback pipeline when switching to playback of the new piece of content. In some embodiments, preservation of at least a portion of the playback pipeline comprises determining whether to retrain an audio decoder and a video decoder of the pipeline when switching to playback of the new piece of content. Accordingly, one or more of the methodologies discussed herein improves upon latency during content changes while maintaining image quality. It is noted that content changes include a selection of a piece of content for viewing (e.g., from a content access page such as a favorites grid or via a programming guide) as well as channel changes (e.g., linear channels changes).

With reference to FIG. 1, an embodiment of an example environment **100** that enables optimizing content changes (e.g., reducing latency during channel changes or selection of a piece of content for viewing) is shown. In example embodiments, a digital receiver **102** of a user provides access to digital content and manages content change operations. In one embodiment, the digital receiver **102** is a set-top box. The digital receiver **102** is coupled to a viewing device **104** (e.g., a television or monitor) on which the user can view the digital content. In some embodiments, the digital receiver **102** (e.g., operations of the digital receiver **102**) may be combined with the viewing device **104** (e.g., a smart television, a tablet, or smartphone). The components of the digital receiver **102** used to perform operations of example embodiments will be discussed in more detail in connection with FIG. 2 below.

In some embodiments, the digital receiver **102** accesses (e.g., pulls, receives, retrieves) content via a network **106** from a content distribution network (CDN) server **108**. The CDN server **108** may obtain the content from one or more content providers **110** (e.g., servers of the content providers **110**). In example embodiments, the CDN server **108** may be associated with a third party service (e.g., Netflix, Hulu, YouTube, Amazon,) that stores and provides content, such as, for example but not limited to, over-the-top (OTT) content, video-on-demand (VOD) content, Internet content, or broadcast content to the digital receiver **102** via the network **106**. The content comprises text, images, audio, and/or video content (e.g., movies, television shows, videos), and in some embodiments comprise live (e.g., in real-time) content. In some embodiments, the content providers **110** provide content, over the network **106** directly to the digital receiver **102** for display on the viewing device **104**.

One or more portions of the network **106** may be an ad hoc network, an intranet, an extranet, a virtual private network (VPN), a local area network (LAN), a wireless LAN (WLAN), a wide area network (WAN), a wireless WAN (WWAN), a metropolitan area network (MAN), a portion of the Internet, a portion of the Public Switched Telephone Network (PSTN), a cellular telephone network, a

4

wireless network, a WiFi network, a WiMax network, a satellite network, a cable network, a broadcast network, another type of network, or a combination of two or more such networks. Any one or more portions of the network **106** may communicate information via a transmission or signal medium. As used herein, “transmission medium” refers to any intangible (e.g., transitory) medium that is capable of communicating (e.g., transmitting) instructions for execution by a machine (e.g., by one or more processors of such a machine), and includes digital or analog communication signals or other intangible media to facilitate communication of such software.

It is noted that the environment **100** shown in FIG. 1 is merely an example. For instance, any number of CDN servers **108** and content providers **110** may be embodied within the environment **100**. Additionally, some components of the environment **100** may be combined. For example, the functions of the digital receiver **102** may be embodied within the viewing device **104** to form a single device, such as a smart television, tablet, smartphone, or any other device that is capable of obtaining, rendering, and displaying content. Moreover, the functions described herein for any single system or machine may be subdivided among multiple systems or machines.

Any of the systems or machines (e.g., databases, devices, servers) shown in, or associated with, FIG. 1 may be, include, or otherwise be implemented in a special-purpose (e.g., specialized or otherwise non-generic) computer that has been modified (e.g., configured or programmed by software, such as one or more software modules of an application, operating system, firmware, middleware, or other program) to perform one or more of the functions described herein for that system or machine. For example, a special-purpose computer system able to implement any one or more of the methodologies described herein is discussed below with respect to FIG. 5, and such a special-purpose computer may accordingly be a means for performing any one or more of the methodologies discussed herein. Within the technical field of such special-purpose computers, a special-purpose computer that has been modified by the structures discussed herein to perform the functions discussed herein is technically improved compared to other special-purpose computers that lack the structures discussed herein or are otherwise unable to perform the functions discussed herein. Accordingly, a special-purpose machine configured according to the systems and methods discussed herein provides an improvement to the technology of similar special-purpose machines.

FIG. 2 is a block diagram illustrating an example embodiment of components within the digital receiver **102** in accordance with an example embodiment. In example embodiments, the digital receiver **102** manages access to content streamed over the network **106**. In particular, the digital receiver **102** prefetches metadata, preserves a bitrate used for playback (e.g., streaming or downloading) of a previous piece of content when initiating the playback of a new piece of content, and preserves at least a portion of a content delivery pipeline. To enable these operations, the digital receiver **102** comprises a player **202**, a content delivery pipeline **204** (also referred to as “pipeline”), a cache manager **206**, and a cache **208**, all of which may be configured to communicate with each other (e.g., over a bus, shared memory, or a switch). The digital receiver **102** comprises other components (not shown) that are not pertinent to operations of example embodiments.

The player **202** is configured to manage the pipeline **204**. In example embodiments, the player **204** instantiates (e.g.,

5

constructs) the pipeline **204** when a first piece of content is selected for display. A different pipeline may be constructed for each type of content. For example, the player **202** constructs a HTTP Live Streaming (HLS) pipeline for HLS content and constructs a Dynamic Adaptive Streaming over HTTP (DASH) pipeline for DASH content. The player **204** also decides whether to maintain at least a portion of the pipeline **204** or construct a new pipeline when a switch in content occurs (e.g., channel change or selection of new content for viewing). An example method for managing the preservation of the pipeline is discussed in further detail in connection with FIG. 4 below.

The pipeline **204** is constructed by the player **202** by acquiring appropriate resources for obtaining and processing content data in order to playback selected content. The resources of the pipeline **204** comprise a source element **212**, a demultiplexer ("demux") **214**, an audio decoder **216**, and a video decoder **218**. The source element **212** manages the downloading of content data for the selected piece of content. The source element **212** also manages bitrate adaptation at the digital receiver **102**. Specifically, the source element **212** remembers a last bitrate that is used for playback of a current/previous piece of content, and continues to use that bitrate for playback of the new content. As such, if the last bitrate is high, the source element **212** will start with the same high bitrate for the new content. If the new content cannot be playback at that bitrate, then the source element **212** will lower the bitrate. For example, if the downloading of the content takes less time than anticipated, there is spare bandwidth and the bitrate can be increased. Conversely, if the download is taking longer than anticipated, then the bitrate is decreased. As such, example embodiments, will start the playback of the new content at the previous/last bitrate instead of starting at a lower or lowest bitrate (and slowly increasing).

The demux demultiplexes the content data obtained from the CDN server **108** or the content provider **110** to obtain an audio signal and a video signal. The audio signal is transmitted to the audio decoder **216** for processing, while the video signal is transmitted to the video decoder **218** for processing. The results from the audio and video decoders **216** and **218** are output (e.g., transmitted) to the viewing device **104** for presentation to the user.

The cache manager **206** manages the prefetching of metadata for content that may potentially be selected for playback. In some embodiments, the cache manager **206** predicts content the user may be interested in viewing. For example, a user may be navigating a linear list of channels or programs (e.g., an electronic programming guide; "EPG") in a particular direction (e.g., up or down). In this embodiment, the cache manager **206** predicts a next set of content based on the direction of navigation on the linear list. In another example, the user may be viewing a video-on-demand (VoD) catalog or a watchlist of a user. If the user requests information or hovers over a selection for a piece of content, the cache manager **206** uses this as prediction that the piece of content is of interest to the user. Alternatively, the cache manager may consider all (or some) pieces of content in viewable portion of the catalog or watchlist as content of interest. In any of these cases, the cache manager **206** prefetches the metadata for the content of interest, and stores the prefetched data to the cache **208**. The metadata may comprise, for example, one or more uniform resource locators (URLs) where the chunks of content are available, URLs for different bit rates, license data (e.g., where to obtain a license from), and codec information. The codec information will be used by the player **202** to determine

6

whether to preserve at least a portion of the pipeline **204**, as will be discussed further below. If the user subsequently selects content for which the metadata is already prefetched, then the metadata can be accessed from the cache **208** instead of having to be retrieved over the network **106** from the CDN server **108** or the content provider **110** after selection. This will assist in the reduction of latency in playback.

Any one or more of the components (e.g., modules, decoders, resources) described herein may be implemented using hardware alone (e.g., one or more processors of a machine) or a combination of hardware and software. For example, any component described herein may physically include an arrangement of one or more of the processors or configure a processor (e.g., among one or more processors of a machine) to perform the operations described herein for that module. Accordingly, different components described herein may include and configure different arrangements of the processors at different points in time or a single arrangement of the processors at different points in time. Each component described herein is an example of a means for performing the operations described herein for that component. Moreover, any two or more of these components may be combined into a single component, and the functions described herein for a single component may be subdivided among multiple components. Furthermore, according to various example embodiments, components described herein as being implemented within a single machine, database, or device may be distributed across multiple machines, databases, or devices.

FIG. 3 is a flow diagram of an example method **300** for optimizing content change in accordance with example embodiments. In example embodiments, the method **300** is performed in part or in whole by components of the digital receiver **102**. Accordingly, the method **300** is described by way of example with reference to the digital receiver **102**. However, it shall be appreciated that at least some of the operations of the method **300** may be deployed on various other hardware configurations or be performed by similar components residing elsewhere in the environment **100**. Therefore, the method **300** is not intended to be limited to the digital receiver **102**.

In operation **302**, a first piece of content is caused to be played by the viewing device **104**. In example embodiments, the player **202** constructs the pipeline **204** for obtaining and processing the content data for the first piece of content. In particular, the player **202** acquires the source element **212**, the demux **214**, the audio decoder **216**, and the video decoder **218** to form the pipeline **204**. The data content is processed by the pipeline **204** and presented on the viewing device **104**.

In operation **304**, metadata for a set of one or more content of interest is prefetched. In example embodiments, the cache manager **206** predicts content of interest of a user and prefetches the metadata for the content of interest. The prefetched data is then stored to the cache **208**. The metadata may comprise, but is not limited to, one or more URLs where the chunks of content are available, one or more URL for different bit rates, license data (e.g., where to obtain a license from), and codec information.

In operation **306**, the player **202** receives an indication to switch to a new piece of content for playback. The indication may be received from a control device of the user (e.g., a remote controller). In some embodiments, the user may scroll through an EPG or be viewing a catalog or watchlist, and selects a new piece of content for viewing.

In operation 308, the digital receiver 102 maintains the bitrate when switching playback to the new piece of content. In example embodiments, when transitioning playback from an ongoing playback operation to a new playback operation, the source element 212 uses a heuristic bitrate derived for playback of the first piece of content for playback of the new piece of content. Thus, the source element 212 attempts to maintain or preserve the bitrate for playback as opposed to starting a new playback from the lowest possible bitrate. If the new piece of content cannot be delivered at that bitrate, then the source element 212 will lower the bitrate. As such, example embodiments, will start the download of the new content at the previous/last bitrate instead of starting at a lower or lowest bitrate (and slowly increasing). This allows playback of the new content at a most optimal bitrate instantly instead of having to heuristically re-compute the optimal bitrate starting from the lowest possible bitrate. Conventionally, the derivation of the optimal bitrate usually requires downloading several segments or chunks of content data resulting in a gradual improvement of picture quality. However, example embodiments that use the previous derived heuristic bitrate maintain the same level of image quality as that of the previous playback from a very beginning of playback for the new content.

In operation 310, a pipeline preservation process is performed to determine whether to maintain at least a portion of the pipeline used to playback the first piece of content for use with the playback of the new piece of content. Furthermore, if the pipeline is to be maintained or preserve, a determination is made as to whether all the resources of the pipeline should be preserved or only a portion of the pipeline preserved (e.g., only some of the resources are kept and others are released). The pipeline preservation process will be discussed in more detail in connection with FIG. 4.

FIG. 4 is a flow diagram of an example method 400 for preserving a content delivery pipeline in accordance with example embodiments. In example embodiments, the method 400 is performed in part or in whole by the player 202 with respect to the resources of the pipeline 204. Accordingly, the method 400 is described by way of example with reference to the player 202 and the pipeline 204. However, it shall be appreciated that at least some of the operations of the method 400 may be deployed on various other hardware configurations or be performed by similar components residing elsewhere in the environment 100. Therefore, the method 400 is not intended to be limited to the player 202 and the pipeline 204.

In operation 402, in response to receiving the indication to switch playback to new content, the cache manager 206 accesses the prefetched metadata stored in the cache 208 for the new content. The prefetched metadata for the new content may comprise one or more URLs where the new content is available, one or more URLs for different bit rates associated with the new content, license data for the new content, and codec information for the new content. The prefetched metadata may also indicate whether the new content is of a same type as the first piece of content. For example, the first piece of content and the new content may both be in a HTTP Live Streaming (HLS) format or both be in a Dynamic Adaptive Streaming over HTTP (DASH) format.

In operation 404, the player 202 determines whether the first piece of content and the new content are of the same content type. If the first piece of content and the new content are not of the same type (e.g., first piece of content is in HLS format and the new content is in DASH format), then the resources of the pipeline 204 (e.g., the source element 212,

the demux 214, the audio decoder 216, and the video decoder 218) are released in operation 406. Releasing all the resources of the pipeline 204 essentially deconstructs the pipeline 204. The player 202 then creates a new pipeline by acquiring other resources that are applicable to the content type of the new content.

If in operation 404 the player 202 determines that the first piece of content and the new content are of the same content type (e.g., both are HLS format), then in operation 408, codec information is detected for the new content. In example embodiments, the player 202 examines the prefetched metadata for the new content for the codec information. The codec information indicates types of decoders needed for the new content.

In operation 410, a determination is made by the player 202 as to whether the types of decoders needed for the new content is the same as the decoders currently in the pipeline 204 for the first piece of content. If the types of decoders needed is the same, then in operation 412 the entire pipeline 204 is preserved. In other words, the resources of the pipeline 204 are maintained and continued to be used to playback the new content.

However, if in operation 410 the player 202 determines that the new content needs different decoders, then in operation 414, the decoders (e.g., the audio decoder 216 and the video decoder 208) are released. Subsequently in operation 416, a remaining portion of the pipeline 204 (e.g., the source element 212 and the demux 214) are preserved or maintained. In these embodiments, the player 202 acquires a new set of decoders (e.g., a new audio decoder and a new video decoder) applicable to the new content, and adds the new set of decoders to the preserved portion of the pipeline 204.

While example embodiments are discussed with respect to pipeline and bitrate preservation applicable to both DASH and HLS, example embodiments for preservation of bitrate and the pipeline is applicable for any type of content that is adaptive in nature (e.g., where the content bitrate can change based on bandwidth).

FIG. 5 is a block diagram illustrating components of a machine 500, according to some example embodiments, able to read instructions 524 from a machine-storage medium 522 (e.g., a non-transitory machine-storage medium, a machine-readable storage medium, a computer-readable storage medium, or any suitable combination thereof) and perform any one or more of the methodologies discussed herein, in whole or in part. Specifically, FIG. 5 shows the machine 500 in the example form of a computer device (e.g., a computer) within which the instructions 524 (e.g., software, a program, an application, an applet, an app, or other executable code) for causing the machine 500 to perform any one or more of the methodologies discussed herein may be executed, in whole or in part.

For example, the instructions 524 may cause the machine 500 to execute the flow diagrams of FIGS. 3 and 4. The instructions 524 can transform the general, non-programmed machine 500 into a particular machine (e.g., specially configured machine) programmed to carry out the described and illustrated functions in the manner described.

In alternative embodiments, the machine 500 operates as a standalone device or may be connected (e.g., networked) to other machines. The machine 500 may be a server computer, a client computer, a personal computer (PC), a tablet computer, a laptop computer, a netbook, a set-top box (e.g. STB), a personal digital assistant (PDA), a cellular telephone, a smartphone, a web appliance, a network router, a network switch, a network bridge, a power adapter, or any

machine **500** capable of executing the instructions **524**, sequentially or otherwise, that specify actions to be taken by that machine **500**. Further, while only a single machine **500** is illustrated, the term “machine” shall also be taken to include a collection of machines that individually or jointly execute the instructions **524** to perform any one or more of the methodologies discussed herein.

The machine **500** includes a processor **502** (e.g., a central processing unit (CPU), a graphics processing unit (GPU), a digital signal processor (DSP), an application specific integrated circuit (ASIC), a radio-frequency integrated circuit (RFIC), or any suitable combination thereof), a main memory **504**, and a static memory **506**, which are configured to communicate with each other via a bus **508**. The processor **502** may contain microcircuits that are configurable, temporarily or permanently, by some or all of the instructions **524** such that the processor **502** is configurable to perform any one or more of the methodologies described herein, in whole or in part. For example, a set of one or more microcircuits of the processor **502** may be configurable to execute one or more modules (e.g., software modules) described herein.

The machine **500** may further include a graphics display **510** (e.g., a plasma display panel (PDP), a light emitting diode (LED) display, a liquid crystal display (LCD), a projector, a cathode ray tube (CRT), or any other display capable of displaying graphics or video). The machine **500** may also include an alphanumeric input device **512** (e.g., a keyboard or keypad), a cursor control device **514** (e.g., a mouse, a touchpad, a trackball, a joystick, a motion sensor, an eye tracking device, or other pointing instrument), a storage unit **516**, a signal generation device **518** (e.g., a sound card, an amplifier, a speaker, a headphone jack, or any suitable combination thereof), and a network interface device **520**.

The storage unit **516** includes the machine-storage medium **522** (e.g., a tangible machine-readable storage medium) on which are stored the instructions **524** embodying any one or more of the methodologies or functions described herein. The instructions **524** may also reside, completely or at least partially, within the main memory **504**, within the processor **502** (e.g., within the processor's cache memory), or both, before or during execution thereof by the machine **500**. Accordingly, the main memory **504** and the processor **502** may be considered machine-storage media **522** (e.g., tangible and non-transitory machine-storage media).

In some example embodiments, the machine **500** may be a portable computing device and have one or more additional input components (e.g., sensors or gauges). Examples of such input components include an image input component (e.g., one or more cameras), an audio input component (e.g., a microphone), a direction input component (e.g., a compass), a location input component (e.g., a global positioning system (GPS) receiver), an orientation component (e.g., a gyroscope), a motion detection component (e.g., one or more accelerometers), an altitude detection component (e.g., an altimeter), and a gas detection component (e.g., a gas sensor). Inputs handled by any one or more of these input components may be accessible and available for use by any of the modules described herein.

Executable Instructions and Machine-Storage Medium

The various memories (i.e., **504**, **506**, and/or memory of the processor(s) **502**) and/or storage unit **516** may store one or more sets of instructions and data structures (e.g., software) **524** embodying or utilized by any one or more of the methodologies or functions described herein. These instruc-

tions, when executed by processors) **502** cause various operations to implement the disclosed embodiments.

As used herein, the terms “machine-storage medium,” “device-storage medium,” “computer-storage medium” (referred to collectively as “machine-storage medium **522**”) mean the same thing and may be used interchangeably in this disclosure. The terms refer to a single or multiple storage devices and/or media (e.g., a centralized or distributed database, and/or associated caches and servers) that store executable instructions and/or data, as well as cloud-based storage systems or storage networks that include multiple storage apparatus or devices. The terms shall accordingly be taken to include, but not be limited to, solid-state memories, and optical and magnetic media, including memory internal or external to processors. Specific examples of machine-storage media, computer-storage media, and/or device-storage media **522** include non-volatile memory, including by way of example semiconductor memory devices, e.g., erasable programmable read-only memory (EPROM), electrically erasable programmable read-only memory (EEPROM), FPGA, and flash memory devices, magnetic disks such as internal hard disks and removable disks; magneto-optical disks; and CD-ROM and DVD-ROM disks. The terms machine-storage media, computer-storage media, and device-storage media **522** specifically exclude carrier waves, modulated data signals, and other such media, at least some of which are covered under the term “signal medium” discussed below.

Signal Medium:

The term “signal medium” or “transmission medium” shall be taken to include any form of modulated data signal, carrier wave, and so forth. The term “modulated data signal” means a signal that has one or more of its characteristics set or changed in such a manner as to encode information in the signal.

Computer Readable Medium

The terms “machine-readable medium,” “computer-readable medium” and “device-readable medium” mean the same thing and may be used interchangeably in this disclosure. The terms are defined to include both machine-storage media and signal media. Thus, the terms include both storage devices/media and carrier waves/modulated data signals.

The instructions **524** may further be transmitted or received over a communications network **526** using a transmission medium via the network interface device **520** and utilizing any one of a number of well-known transfer protocols (e.g., HTTP). Examples of communication networks **526** include a local area network (LAN), a wide area network (WAN), the Internet, mobile telephone networks, plain old telephone service (POTS) networks, and wireless data networks (e.g., WiFi, LTE, and WiMAX networks). The term “transmission medium” shall be taken to include any intangible medium that is capable of storing, encoding, or carrying instructions **524** for execution by the machine **500**, and includes digital or analog communications signals or other intangible medium to facilitate communication of such software.

Throughout this specification, plural instances may implement components, operations, or structures described as a single instance. Although individual operations of one or more methods are illustrated and described as separate operations, one or more of the individual operations may be performed concurrently, and nothing requires that the operations be performed in the order illustrated. Structures and functionality presented as separate components in example configurations may be implemented as a combined structure

11

or component. Similarly, structures and functionality presented as a single component may be implemented as separate components. These and other variations, modifications, additions, and improvements fall within the scope of the subject matter herein.

Certain embodiments are described herein as including logic or a number of components, modules, or mechanisms. Modules may constitute either software modules (e.g., code embodied on a machine-storage medium 522 or in a transmission signal) or hardware modules. A “hardware module” is a tangible unit capable of performing certain operations and may be configured or arranged in a certain physical manner. In various example embodiments, one or more computer systems (e.g., a standalone computer system, a client computer system, or a server computer system) or one or more hardware modules of a computer system (e.g., a processor 502 or a group of processors 502) may be configured by software (e.g., an application or application portion) as a hardware module that operates to perform certain operations as described herein.

In some embodiments, a hardware module may be implemented mechanically, electronically, or any suitable combination thereof. For example, a hardware module may include dedicated circuitry or logic that is permanently configured to perform certain operations. For example, a hardware module may be a special-purpose processor, such as a field-programmable gate array (FPGA) or an ASIC. A hardware module may also include programmable logic or circuitry that is temporarily configured by software to perform certain operations. For example, a hardware module may include software encompassed within a general-purpose processor or other programmable processor. It will be appreciated that the decision to implement a hardware module mechanically, in dedicated and permanently configured circuitry, or in temporarily configured circuitry (e.g., configured by software) may be driven by cost and time considerations.

Accordingly, the phrase “hardware module” should be understood to encompass a tangible entity, be that an entity that is physically constructed, permanently configured (e.g., hardwired), or temporarily configured (e.g., programmed) to operate in a certain manner or to perform certain operations described herein. As used herein, “hardware-implemented module” refers to a hardware module. Considering embodiments in which hardware modules are temporarily configured (e.g., programmed), each of the hardware modules need not be configured or instantiated at any one instance in time. For example, where a hardware module comprises a general-purpose processor configured by software to become a special-purpose processor, the general-purpose processor may be configured as respectively different special-purpose processors (e.g., comprising different hardware modules) at different times. Software may accordingly configure a processor, for example, to constitute a particular hardware module at one instance of time and to constitute a different hardware module at a different instance of time.

The various operations of example methods described herein may be performed, at least partially, by one or more processors that are temporarily configured (e.g., by software) or permanently configured to perform the relevant operations. Whether temporarily or permanently configured, such processors may constitute processor-implemented modules that operate to perform one or more operations or functions described herein. As used herein, “processor-implemented module” refers to a hardware module implemented using one or more processors.

12

Similarly, the methods described herein may be at least partially processor-implemented, a processor being an example of hardware. For example, at least some of the operations of a method may be performed by one or more processors or processor-implemented modules.

Examples

Example 1 is a method for optimizing a content change process. The method comprises causing playback, by a digital receiver, of a first piece of content, receiving, by the digital receiver, a selection of a new piece of content for playback during the playback of the first piece of content; and in response to the receiving of the selection, maintaining, by a processor of the digital receiver, a bitrate used for playback of the first piece of content to initiate playback of the new piece of content.

In example 2, the subject matter of example 1 can optionally include determining whether the new piece of content is of a same type as the first piece of content, and based on the new piece of content being the same type as the first piece of content, determining whether to preserve at least a portion of a playback pipeline.

In example 3, the subject matter of examples 1-2 can optionally include wherein the determining whether to preserve comprises detecting codec information for the new piece of content, the codec information indicating types of decoders needed for the new content; and determining whether an audio decoder and a video decoder in the pipeline are of the types indicated by the codec information.

In example 4, the subject matter of examples 1-3 can optionally include preserving the entire pipeline in response to the audio decoder and the video decoder in the pipeline being the types indicated by the codec information.

In example 5, the subject matter of examples 1-4 can optionally include releasing the audio decoder and the video decoder in the pipeline in response to the audio decoder and the video decoder in the pipeline being different than the types indicated by the codec information; and obtaining a new audio decoder and a new video decoder based on the codec information.

Example 6 is a system optimizing a content change process. The system includes one or more hardware processors and a storage device storing instructions that configure the one or more hardware processors to perform operations comprising causing playback of a first piece of content; receiving a selection of a new piece of content for playback during the playback of the first piece of content; and in response to the receiving of the selection, maintaining a bitrate used for playback of the first piece of content to initiate playback of the new piece of content.

In example 7, the subject matter of example 6 can optionally include determining whether the new piece of content is of a same type as the first piece of content, and based on the new piece of content being the same type as the first piece of content, determining whether to preserve at least a portion of a playback pipeline.

In example 8, the subject matter of examples 6-7 can optionally include wherein the determining whether to preserve comprises detecting codec information for the new piece of content, the codec information indicating types of decoders needed for the new content; and determining whether an audio decoder and a video decoder in the pipeline are of the types indicated by the codec information.

In example 9, the subject matter of examples 6-8 can optionally include preserving the entire pipeline in response

13

to the audio decoder and the video decoder in the pipeline being the types indicated by the codec information.

In example 10, the subject matter of examples 6-9 can optionally include releasing the audio decoder and the video decoder in the pipeline in response to the audio decoder and the video decoder in the pipeline being different than the types indicated by the codec information; and obtaining a new audio decoder and a new video decoder based on the codec information.

Example 11 is machine-readable medium storing instructions that when executed by one or more hardware processors of a machine, cause the machine to perform operations comprising causing playback of a first piece of content; receiving a selection of a new piece of content for playback during the playback of the first piece of content, and in response to the receiving of the selection, maintaining a bitrate used for playback of the first piece of content to initiate playback of the new piece of content.

In example 12, the subject matter of example 11 can optionally include determining whether the new piece of content is of a same type as the first piece of content; and based on the new piece of content being the same type as the first piece of content, determining whether to preserve at least a portion of a playback pipeline.

In example 13, the subject matter of examples 11-12 can optionally include wherein the determining whether to preserve comprises detecting codec information for the new piece of content, the codec information indicating types of decoders needed for the new content; and determining whether an audio decoder and a video decoder in the pipeline are of the types indicated by the codec information.

In example 14, the subject matter of examples 11-13 can optionally include preserving the entire pipeline in response to the audio decoder and the video decoder in the pipeline being the types indicated by the codec information.

In example 15, the subject matter of examples 11-14 can optionally include releasing the audio decoder and the video decoder in the pipeline in response to the audio decoder and the video decoder in the pipeline being different than the types indicated by the codec information; and obtaining a new audio decoder and a new video decoder based on the codec information.

Some portions of the subject matter discussed herein may be presented in terms of algorithms or symbolic representations of operations on data stored as bits or binary digital signals within a machine memory (e.g., a computer memory). Such algorithms or symbolic representations are examples of techniques used by those of ordinary skill in the data processing arts to convey the substance of their work to others skilled in the art. As used herein, an "algorithm" is a self-consistent sequence of operations or similar processing leading to a desired result. In this context, algorithms and operations involve physical manipulation of physical quantities. Typically, but not necessarily, such quantities may take the form of electrical, magnetic, or optical signals capable of being stored, accessed, transferred, combined, compared, or otherwise manipulated by a machine. It is convenient at times, principally for reasons of common usage, to refer to such signals using words such as "data," "content," "bits," "values," "elements," "symbols," "characters," "terms," "numbers," "numerals," or the like. These words, however, are merely convenient labels and are to be associated with appropriate physical quantities.

Unless specifically stated otherwise, discussions herein using words such as "processing," "computing," "calculating," "determining," "presenting," "displaying," or the like may refer to actions or processes of a machine (e.g., a

14

computer) that manipulates or transforms data represented as physical (e.g., electronic, magnetic, or optical) quantities within one or more memories (e.g., volatile memory, non-volatile memory, or any suitable combination thereof), registers, or other machine components that receive, store, transmit, or display information. Furthermore, unless specifically stated otherwise, the terms "a" or "an" are herein used, as is common in patent documents, to include one or more than one instance. Finally, as used herein, the conjunction "or" refers to a non-exclusive "or," unless specifically stated otherwise.

Although an overview of the inventive subject matter has been described with reference to specific example embodiments, various modifications and changes may be made to these embodiments without departing from the broader scope of embodiments of the present invention. For example, various embodiments or features thereof may be mixed and matched or made optional by a person of ordinary skill in the art. Such embodiments of the inventive subject matter may be referred to herein, individually or collectively, by the term "invention" merely for convenience and without intending to voluntarily limit the scope of this application to any single invention or inventive concept if more than one is, in fact, disclosed.

The embodiments illustrated herein are believed to be described in sufficient detail to enable those skilled in the art to practice the teachings disclosed. Other embodiments may be used and derived therefrom, such that structural and logical substitutions and changes may be made without departing from the scope of this disclosure. The Detailed Description, therefore, is not to be taken in a limiting sense, and the scope of various embodiments is defined only by the appended claims, along with the full range of equivalents to which such claims are entitled.

Moreover, plural instances may be provided for resources, operations, or structures described herein as a single instance. Additionally, boundaries between various resources, operations, modules, engines, and data stores are somewhat arbitrary, and particular operations are illustrated in a context of specific illustrative configurations. Other allocations of functionality are envisioned and may fall within a scope of various embodiments of the present invention. In general, structures and functionality presented as separate resources in the example configurations may be implemented as a combined structure or resource. Similarly, structures and functionality presented as a single resource may be implemented as separate resources. These and other variations, modifications, additions, and improvements fall within a scope of embodiments of the present invention as represented by the appended claims. The specification and drawings are, accordingly, to be regarded in an illustrative rather than a restrictive sense.

What is claimed is:

1. A method performed by a digital receiver, the method comprising:

receiving a selection of a new piece of content for playback during playback of a first piece of content; in response to the receiving of the selection, transitioning to the new piece of content;

determining whether the new piece of content is of a same content type as the first piece of content; and

based on the new piece of content being the same content type as the first piece of content, determining whether to preserve at least a portion of a playback pipeline used to play back the first piece of content, the playback pipeline comprising a source element to manage the downloading of content data for the new piece of

15

content, a demultiplexer, an audio decoder, and a video decoder, the preserving of at least the portion of the playback pipeline comprising preserving one or more of the source element, the demultiplexer, the audio decoder, or the video decoder used to obtain the first piece of content for the new piece of content.

2. The method of claim 1, wherein the determining whether to preserve comprises:

detecting codec information for the new piece of content, the codec information indicating types of decoders needed for the new piece of content; and

determining whether the audio decoder and the video decoder in the playback pipeline are of the types indicated by the codec information.

3. The method of claim 2, further comprising:

preserving an entirety of the playback pipeline in response to the audio decoder and the video decoder in the playback pipeline being the types indicated by the codec information.

4. The method of claim 2, further comprising:

releasing the audio decoder and the video decoder in the playback pipeline in response to the audio decoder and the video decoder in the playback pipeline being different than the types indicated by the codec information; and

obtaining a new audio decoder and a new video decoder based on the codec information.

5. The method of claim 2, wherein the detecting the codec information for the new piece of content comprises examining prefetched metadata for the new piece of content.

6. The method of any one of claim 1, wherein the transitioning to the new piece of content comprises initiating playback of the new piece of content using a bitrate used for playback of the first piece of content to maintain the bitrate for playback of the new piece of content.

7. The method of claim 6, further comprising:

during playback of the new piece of content using the bitrate, detecting whether the new piece of content can maintain playback at the bitrate; and

in response to detecting that the new piece of content cannot continue playback at the bitrate, lowering the bitrate.

8. The method of claim 1, further comprising:

based on the first piece of content and the new piece of content not being the same content type, deconstructing the playback pipeline by releasing the source element, the demultiplexer, the audio decoder, and the video decoder; and

creating a new playback pipeline by acquiring other resources that are applicable to a content type of the new piece of content.

9. The method of claim 1, wherein the receiving the selection, transitioning to the new piece of content, determining whether the new piece of content is of a same content type as the first piece of content, and determining whether to preserve is performed by a player of the digital receiver.

10. The method of claim 1, wherein the source element initiates the playback of the new piece of content using a same bitrate as the first piece of content and adjusts the bitrate in response to detecting that the new piece of content cannot continue playback at the bitrate.

11. A system comprising:

one or more hardware processors; and

a storage device storing instructions that configure the one or more hardware processors to perform operations comprising:

16

receiving a selection of a new piece of content for playback during playback of a first piece of content; in response to the receiving of the selection, transitioning to the new piece of content;

determining whether the new piece of content is of a same content type as the first piece of content; and based on the new piece of content being the same content type as the first piece of content, determining whether to preserve at least a portion of a playback pipeline used to play back the first piece of content, the playback pipeline comprising a source element to manage the downloading of content data for the new piece of content, a demultiplexer, an audio decoder, and a video decoder, the preserving of at least the portion of the playback pipeline comprising preserving one or more of the source element, the demultiplexer, the audio decoder, or the video decoder used to obtain the first piece of content for the new piece of content.

12. The system of claim 11, wherein the determining whether to preserve comprises:

detecting codec information for the new piece of content, the codec information indicating types of decoders needed for the new piece of content; and

determining whether the audio decoder and the video decoder in the playback pipeline are of the types indicated by the codec information.

13. The system of claim 12, wherein the operations further comprise:

preserving an entirety of the playback pipeline in response to the audio decoder and the video decoder in the playback pipeline being the types indicated by the codec information.

14. The system of claim 12, wherein the operations further comprise:

releasing the audio decoder and the video decoder in the playback pipeline in response to the audio decoder and the video decoder in the playback pipeline being different than the types indicated by the codec information; and

obtaining a new audio decoder and a new video decoder based on the codec information.

15. The system of claim 12, wherein the detecting the codec information for the new piece of content comprises examining prefetched metadata for the new piece of content.

16. The system of any one of claim 11, wherein the transitioning to the new piece of content comprises initiating playback of the new piece of content using a bitrate used for playback of the first piece of content to maintain the bitrate for playback of the new piece of content.

17. The system of claim 16, wherein the operations further comprise:

during playback of the new piece of content using the bitrate, detecting whether the new piece of content can maintain playback at the bitrate; and

in response to detecting that the new piece of content cannot continue playback at the bitrate, lowering the bitrate.

18. The system of claim 11, wherein the operations further comprise:

based on the first piece of content and the new piece of content not being the same content type, deconstructing the playback pipeline by releasing the source element, the demultiplexer, the audio decoder, and the video decoder; and

17

creating a new playback pipeline by acquiring other resources that are applicable to a content type of the new piece of content.

19. The system of claim 11, wherein the source element initiates the playback of the new piece of content using a same bitrate as the first piece of content and adjusts the bitrate in response to detecting that the new piece of content cannot continue playback at the bitrate. 5

20. A machine-storage medium storing instructions that when executed by one or more hardware processors of a machine, cause the machine to perform operations comprising: 10

receiving a selection of a new piece of content for playback during playback of a first piece of content; in response to the receiving of the selection, transitioning 15 to the new piece of content; determining whether the new piece of content is of a same content type as the first piece of content; and based on the new piece of content being the same content type as the first piece of content, determining whether 20 to preserve at least a portion of a playback pipeline used to play back the first piece of content, the playback pipeline comprising a source element to manage the downloading of content data for the new piece of content, a demultiplexer, an audio decoder, and a video 25 decoder, the preserving of at least the portion of the playback pipeline comprising preserving one or more of the source element, the demultiplexer, the audio decoder, or the video decoder used to obtain the first piece of content for the new piece of content. 30

* * * * *

18